


C&K MIL Series

1-4 Pole Miniature Right



Features/Benefits

- **Bushing option for panel mounting**
- **1 to 4 poles per bank and up to 5 banks per switch**
- **Totally sealed (insert molded contacts and terminals)**
- **Low profile – 12 mm above PCB**

Typical Applications

- **Telecom switching equipment**
- **Military communications**
- **Instrumentation**
- **Medical monitors**

Specifications

CONTACT RATING: Switch: 20 mA, 1 VA max. resistive load
Carry: 1 AMP.

ELECTRICAL LIFE: 20,000 operations.

OPERATING TORQUE: < 6 Ncm.

STOP STRENGTH: > 50 Ncm.

CONTACT RESISTANCE: < 40 mΩ

INSULATION RESISTANCE: 10⁹ Ω

DIELECTRIC STRENGTH: 500 V rms

OPERATING TEMPERATURE: -40°C to + 85°C

STORAGE TEMPERATURE: -55°C to + 85°C

NOTE: Specifications and materials listed above are for switches with standard options.
For information on specific and custom switches, consult Customer Service Center.

Materials

HOUSING: Thermoplastic (nylon) and thermoset (diallyl phthalate)

ACTUATOR: Steel

MOVABLE CONTACTS: Brass, gold plated.

ROTOR: Thermoset (polysulfone)

O-RING: Silicone

STATIONARY CONTACTS & TERMINALS: Brass, gold plated.

TERMINAL SEAL: Totally sealed (insert molded).

BUSHING: Brass

STOP PIN: Stainless steel

HARDWARE: Nut: Brass, nickel plated. Washer: Brass, nickel plated.

Gasket: Neopren.

Build-A-Switch

To order, simply select desired option from each category and place in the appropriate box. Available options are shown and described on pages K-23 thru K-25. For additional options not shown in catalog, consult Customer Service Center.

Rotary
K

Designation	MIL	Number of Banks	Switch Function	Switching Mode	Mounting Style	Actuator Option	Actuator Option Angle*	Actuator Option Length**
		1 (STD.) 1 Bank 2 2 Banks 3 3 Banks 4 4 Banks 5 5 Banks	112S (STD.) SP, 30° Index, 12 pos. no stop 102B02 SP, 30° Index, 2 pos. 103B03 SP, 30° Index, 3 pos. 104B04 SP, 30° Index, 4 pos. 105B05 SP, 30° Index, 5 pos. 106B06 SP, 30° Index, 6 pos. 107B07 SP, 30° Index, 7 pos. 108B08 SP, 30° Index, 8 pos. 109B09 SP, 30° Index, 9 pos. 110B10 SP, 30° Index, 10 pos. 111B11 SP, 30° Index, 11 pos. 112B12 (STD.) SP, 30° Index, 12 pos. 206S (STD.) DP, 30° Index, 6 pos. no stop 202B02 DP, 30° Index, 2 pos. 203B03 DP, 30° Index, 3 pos. 204B04 DP, 30° Index, 4 pos. 205B05 DP, 30° Index, 5 pos. 206B06 (STD.) DP, 30° Index, 6 pos. 303S 3P, 30° Index, 3 pos. no stop 302B02 3P, 30° Index, 2 pos. 303B03 3P, 30° Index, 3 pos. 402S 4P, 30° Index, 2 pos. no stop 402B02 4P, 30° Index, 2 pos.	N (STD.) Non-shorting BBM (break-before-make) C Shorting, MBB (make-before-break)	SD (STD.) Without panel mount AD (STD.) With panel mount	(NONE) (STD.) 4 mm diameter shaft M10X3 4 mm shaft with flat F2X1 4 mm shaft with screwdriver slot	(NONE) (STD.) K0 0° angle K30 30° angle K60 60° angle K90 90° angle K120 120° angle K180 180° angle K270 270° angle	25 (STD.) 25 mm standard shaft

* Other angles available by request
** Other lengths available by request.


C&K MIL Series

1-4 Pole Miniature Right

DESIGNATION




MIL



NUMBER OF BANKS







OPTION CODE	DIM. 'L'	WITH BUSHING DIM. 'L'
1	.770 (17,78)	.897 (22,78)
2	1.400 (35,56)	1.597 (40,56)
3	2.100 (53,34)	2.297 (58,34)
4	2.800 (71,12)	3.00 (76,12)
5	3.500 (88,90)	3.697 (93,90)




SWITCH FUNCTION




30° INDEXING		
NO. POLES	MODEL NO.	SWITCH FUNCTION
SP	112S	12 Position No Stops
	102B02	2 Positions
	103B03	3 Positions
	104B04	4 Positions
	105B05	5 Positions
	106B06	6 Positions
	107B07	7 Positions
	108B08	8 Positions
	109B09	9 Positions
	110B10	10 Positions
	111B11	11 Positions
	112B12	12 Positions




30° INDEXING		
NO. POLES	MODEL NO.	SWITCH FUNCTION
DP	206S	4 Position No Stops
	202B02	2 Positions
	203B03	3 Positions
	204B04	4 Positions
	205B05	5 Positions
	206B06	6 Positions
3P	303S	3 Positions No Stop
	302B02	2 Positions
	303B03	3 Positions
4P	402S	2 Positions No Stop
	402B02	2 Positions




1 POLE
2 - 12 POSITIONS



2 POLES
2 - 6 POSITIONS



3 POLES
2 - 3 POSITIONS



4 CIRCUITS
2 POSITIONS

C&K MIL Series

1-4 Pole Miniature Right

SWITCHING MODE




N (STD.) NON-SHORTING, BBM (break-before-make)

C SHORTING, MBB (make-before-break)


MOUNTING STYLE



SD WITHOUT




AD WITH PANEL MOUNT




ACTUATOR OPTION




(NONE) (STD.) .157 DIA. (4,0)



F2X1 SCREWDRIVER SLOT



M10X3 FLAT



Third Angle
Projection

Dimensions are shown: IN (mm)
Dimensions subject to change




K

Rotary


ACTUATOR OPTION ANGLE




(NONE) (STD.)




K0 (STD.) 0° ANGLE




K30 30°




K60 60°




K90 90°



K120 120°




K180 210°




K270 300°




K0 (STD.) 0° ANGLE




K30 30°



K60 60°



K90 90°



K120 120°

ACTUATOR LENGTH



25 0,25 mm (.984) STANDARD SHAFT

Other lengths available by request.



K

Rotary

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru