

### 452/454 Series Fuse



#### Agency Approvals

| AGENCY  | AGENCY FILE NUMBER | AMPERE RANGE |
|---|--------------------|--------------|
|  | E10480             | 0.375A - 12A |
|  | 29862              | 0.375A - 12A |
|  | NBK030205-E10480B  | 1A - 5A      |

#### Electrical Characteristics for Series

| % of Ampere Rating | Opening Time                    |
|--------------------|---------------------------------|
| 100%               | 4 hours, Minimum                |
| 200%               | 1 sec., Min.; 60 sec., Max.     |
| 300%               | 0.2 sec., Min.; 3 sec., Max     |
| 800%               | 0.02 sec., Min.; 0.1 sec., Max. |

#### Electrical Specifications by Item

| Ampere Rating (A) | Amp Code | Max Voltage Rating (V) | Interrupting Rating                                       | Nominal Cold Resistance (Ohms) | Nominal Melting I <sup>2</sup> t (A <sup>2</sup> sec) | Agency Approvals  |   |   |
|-------------------|----------|------------------------|---|--------------------------------|---|---|---|---|
|                   |          |                        |   |                                |   |  |  |  |
| 0.375             | .375     | 125                    | 50A @ 125 VAC/VDC<br>300A @ 32 VDC<br>PSE: 100A @ 100 VAC | 1.2000                         | 0.101   | x   | x   |   |
| 0.500             | .500     | 125                    |   | 0.7000                         | 0.240   | x   | x   |   |
| 0.750             | .750     | 125                    |   | 0.3600                         | 0.904   | x   | x   |   |
| 001.              | 001.     | 125                    |   | 0.2250                         | 1.98  | x   | x   | x   |
| 1.50              | 01.5     | 125                    |   | 0.0930                         | 3.65  | x   | x   | x   |
| 2.00              | 002.     | 125                    |   | 0.0625                         | 8.20  | x   | x   | x   |
| 2.50              | 02.5     | 125                    |   | 0.0450                         | 15.0  | x   | x   | x   |
| 3.00              | 003.     | 125                    |   | 0.0340                         | 20.16   | x   | x   | x   |
| 3.50              | 03.5     | 125                    |   | 0.0224                         | 26.53   | x   | x   | x   |
| 4.00              | 004.     | 125                    |   | 0.0186                         | 34.40   | x   | x   | x   |
| 5.00              | 005.     | 125                    |   | 0.0136                         | 53.72   | x   | x   | x   |
| 7.00              | 007.     | 75                     | 50A @ 72 VAC<br>50A @ 60 VDC<br>100A @ 75 VDC             | 0.0105                         | 123.83  | x   | x   |   |
| 8                 | 008.     | 75                     |   | 0.0088                         | 137.34  | x   | x   |   |
| 12                | 012.     | 75                     |   | 0.0061                         | 260.46  | x   | x   |   |

Notes:  
 - I<sup>2</sup>t calculated at 8ms.  
 - Resistance is measured at 10% of rated current, 25°C

#### Description

The NANO<sup>2</sup> Slo-Blo fuse has enhanced inrush withstand characteristics over the NANO<sup>2</sup> Fast-Acting fuse. The unique time delay feature of this fuse design helps solve the problem of nuisance “opening” by accommodating inrush currents that normally cause a fast-acting fuse to open.

#### Features

- Small size
- Wide range of current rating available (0.375A to 12A)
- Wide operating temperature range
- Low temperature derating
- RoHS compliant and Halogen Free

#### Applications

- Notebook PC
- LCD/PDPTV
- LCD monitor
- LCD/PDP panel
- LCD backlight inverter
- Portable DVD player
- Power supply
- Networking
- PC server
- Cooling fan system
- Storage system
- Telecom system
- Wireless basestation
- White goods
- Game console
- Office Automation equipment
- Battery charging circuit protection
- Industrial equipment

## Temperature Re-rating Curve



Note:

1. Rerating depicted in this curve is in addition to the standard derating of 25% for continuous operation.

## Average Time Current Curves



## Soldering Parameters

|  |                                    |  |
|--|------------------------------------|--|
| Reflow Condition                                       |                                    | Pb – Free assembly                     |
| Pre Heat   | - Temperature Min ( $T_{s(min)}$ ) | 150°C                                  |
|  | - Temperature Max ( $T_{s(max)}$ ) | 200°C                                  |
|  | - Time (Min to Max) ( $t_s$ )      | 60 – 120 secs                          |
| Average ramp up rate (Liquidus Temp ( $T_L$ ) to peak) |                                    | 5°C/second max.                        |
| $T_{s(max)}$ to $T_L$ - Ramp-up Rate                   |                                    | 5°C/second max.                        |
| Reflow   | - Temperature ( $T_L$ ) (Liquidus) | 217°C                                  |
|  | - Temperature ( $t_L$ )            | 60 – 90 seconds                        |
| Peak Temperature ( $T_p$ )                             |                                    | 260 <sup>+0/-5</sup> °C                |
| Time within 5°C of actual peak Temperature ( $t_p$ )   |                                    | 20 – 40 seconds                        |
| Ramp-down Rate   |                                    | 5°C/second max.                        |
| Time 25°C to peak Temperature ( $T_p$ )                |                                    | 8 minutes max.                         |
| Do not exceed  |                                    | 260°C                                  |
| Wave Soldering Parameters                              |                                    | 260°C Peak Temperature, 3 seconds max. |



### Product Characteristics

|  |   |
|--|---|
| <b>Materials</b>                             | <b>Body:</b> Ceramic<br><b>Terminations:</b><br>Gold-plated Caps / Sn-dipped Silver Plated Caps (452 Series)<br>Silver-plated Caps (454 Series) |
| <b>Product Marking</b>                       | Brand, Ampere Rating  |
| <b>Operating Temperature</b>                 | -55°C to 125°C  |
| <b>Moisture Sensitivity Level</b>            | Level 1, J-STD-020  |
| <b>Solderability</b>                         | MIL-STD-202, Method 208   |
| <b>Insulation Resistance (after Opening)</b> | MIL-STD-202, Method 302, Test Condition A (10,000 ohms minimum)   |

|                                     |   |
|-------------------------------------|---|
| <b>Thermal Shock</b>                | MIL-STD-202, Method 107, Test Condition B, 5 cycles, -65°C / +125°C, 15 minutes @ each extreme                              |
| <b>Mechanical Shock</b>             | MIL-STD-202, Method 213, Test I: Deenergized. 100G's pk amplitude, sawtooth wave 6ms duration, 3 cycles XYZ+xyz = 18 shocks |
| <b>Vibration</b>                    | MIL-STD-202, Method 201: 0.03" amplitude, 10-55 Hz in 1 min. 2hrs each XYZ=6hrs   |
| <b>Moisture Resistance</b>          | MIL-STD-202, Method 106, 10 cycles  |
| <b>Salt Spray</b>                   | MIL-STD-202, Method 101, Test Condition B (48hrs)   |
| <b>Resistance to Soldering Heat</b> | MIL-STD-202, Method 210, Test condition B (10 sec at 260°C)   |

### Dimensions



Recommended pad layout

### Part Numbering System



Notes:  
452 series may be ordered as "RoHS and HF (Gold Plated Caps)" ("L" suffix).  
454 series is available only as "RoHS and HF" version and does not require "L" suffix.  
Please do not include "L" suffix within 454 series ordering instructions.

### Packaging

| Packaging Option   | Packaging Specification        | Quantity | Quantity & Packaging Code |
|--------------------|--------------------------------|----------|---------------------------|
| 12mm Tape and Reel | EIA RS-481-1 (IEC 286, part 3) | 5000     | NR                        |
| 12mm Tape and Reel | EIA RS-481-1 (IEC 286, part 3) | 1000     | MR                        |

### Additional Information



**Datasheet 452 Series**



**Resources 452 Series**



**Samples 452 Series**



**Datasheet 454 Series**



**Resources 454 Series**



**Samples 454 Series**

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)