


### Features

1500W Peak Pulse Power Dissipation  
Voltage Range 6.8V - 400V  
Constructed with Glass Passivated Die  
Uni and Bidirectional Versions Available  
Excellent Clamping Capability  
Fast Response Time  
**Lead Free Finish, RoHS Compliant (Note 3)**



### Mechanical Data

Case: DO-201  
Case Material: Transfer Molded Epoxy. UL Flammability  
Classification Rating 94V-0  
Moisture Sensitivity: Level 1 per J-STD-020C  
Terminals: Finish - Tin. Leads: Axial, Solderable per  
MIL-STD-202 Method 208  
Ordering Information: See Page 4  
Marking: Unidirectional - Type Number and Cathode Band  
Marking: Bidirectional - Type Number Only  
Weight: 1.12 grams (approximate)

| DO-201               |       |      |
|----------------------|-------|------|
| Dim                  | Min   | Max  |
| A                    | 25.40 | —    |
| B                    | 8.50  | 9.53 |
| C                    | 0.96  | 1.06 |
| D                    | 4.80  | 5.21 |
| All Dimensions in mm |       |      |

### Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Characteristic                                                                                                                                                 | Symbol         | Value       | Unit             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-------------|------------------|
| Peak Power Dissipation at $t_p = 1.0\text{ms}$<br>(Non-repetitive current pulse, derated above $T_A = 25^\circ\text{C}$ )                                      | $P_{pk}$       | 1500        | W                |
| Steady State Power Dissipation at $T_L = 75^\circ\text{C}$ Lead Lengths 9.5 mm                                                                                 | $P_d$          | 5.0         | W                |
| Peak Forward Surge Current, 8.3 Single Half Sine Wave Superimposed on<br>Rated Load (8.3ms Single Half Sine Wave,<br>Duty Cycle = 4 pulses per minute maximum) | $I_{FSM}$      | 200         | A                |
| Forward Voltage @ $I_F = 50\text{A}$ 300 $\mu\text{s}$ Square Wave Pulse,<br>Unidirectional Only                                                               | $V_F$          | 3.5<br>5.0  | V                |
| Operating and Storage Temperature Range                                                                                                                        | $T_j, T_{STG}$ | -55 to +175 | $^\circ\text{C}$ |

- Notes:
- Suffix 'C' denotes bidirectional device.
  - For bidirectional devices having  $V_R$  of 10 volts and under, the  $I_R$  limit is doubled.
  - RoHS revision 13.2.2003. Glass and high temperature solder exemptions applied, see *EU Directive Annex Notes 5 and 7*.

| Type Number<br>(Note 1) | Type Number<br>(Note 1) | Reverse Standoff Voltage | Breakdown Voltage<br>$V_{BR}$ @ $I_T$ |         | Test Current | Max. Reverse Leakage<br>(Note 2)<br>@ $V_R$ | Max. Clamping Voltage<br>@ $I_{PP}$ | Max. Peak Pulse Current | Max. Voltage Temp. Variation of $V_{BR}$ |
|-------------------------|-------------------------|--------------------------|---------------------------------------|---------|--------------|---------------------------------------------|-------------------------------------|-------------------------|------------------------------------------|
| (UNI)                   | (BI)                    | $V_{RWM}$ (V)            | Min (V)                               | Max (V) | $I_T$ (mA)   | $I_R$ (A)                                   | $V_C$ (V)                           | $I_{PP}$ (A)            | %/°C                                     |
| 1.5KE6V8A               | 1.5KE6V8CA              | 5.80                     | 6.45                                  | 7.14    | 10           | 1000                                        | 10.5                                | 143.0                   | 0.057                                    |
| 1.5KE7V5A               | 1.5KE7V5CA              | 6.40                     | 7.13                                  | 7.88    | 10           | 500                                         | 11.3                                | 132.0                   | 0.061                                    |
| 1.5KE8V2A               | 1.5KE8V2CA              | 7.02                     | 7.79                                  | 8.61    | 10           | 200                                         | 12.1                                | 124.0                   | 0.065                                    |
| 1.5KE9V1A               | 1.5KE9V1CA              | 7.78                     | 8.65                                  | 9.55    | 1.0          | 50                                          | 13.4                                | 112.0                   | 0.068                                    |
| 1.5KE10A                | 1.5KE10CA               | 8.55                     | 9.50                                  | 10.50   | 1.0          | 10                                          | 14.5                                | 103.0                   | 0.073                                    |
| 1.5KE11A                | 1.5KE11CA               | 9.40                     | 10.50                                 | 11.60   | 1.0          | 5.0                                         | 15.6                                | 96.0                    | 0.075                                    |
| 1.5KE12A                | 1.5KE12CA               | 10.20                    | 11.40                                 | 12.60   | 1.0          | 5.0                                         | 16.7                                | 90.0                    | 0.078                                    |
| 1.5KE13A                | 1.5KE13CA               | 11.10                    | 12.40                                 | 13.70   | 1.0          | 5.0                                         | 18.2                                | 82.0                    | 0.081                                    |
| 1.5KE15A                | 1.5KE15CA               | 12.80                    | 14.30                                 | 15.80   | 1.0          | 5.0                                         | 21.2                                | 71.0                    | 0.084                                    |
| 1.5KE16A                | 1.5KE16CA               | 13.60                    | 15.20                                 | 16.80   | 1.0          | 5.0                                         | 22.5                                | 67.0                    | 0.086                                    |
| 1.5KE18A                | 1.5KE18CA               | 15.30                    | 17.10                                 | 18.90   | 1.0          | 5.0                                         | 25.2                                | 59.5                    | 0.088                                    |
| 1.5KE20A                | 1.5KE20CA               | 17.10                    | 19.00                                 | 21.00   | 1.0          | 5.0                                         | 27.7                                | 54.0                    | 0.090                                    |
| 1.5KE22A                | 1.5KE22CA               | 18.80                    | 20.90                                 | 23.10   | 1.0          | 5.0                                         | 30.6                                | 49.0                    | 0.092                                    |
| 1.5KE24A                | 1.5KE24CA               | 20.50                    | 22.80                                 | 25.20   | 1.0          | 5.0                                         | 33.2                                | 45.0                    | 0.094                                    |
| 1.5KE27A                | 1.5KE27CA               | 23.10                    | 25.70                                 | 28.40   | 1.0          | 5.0                                         | 37.5                                | 40.0                    | 0.096                                    |
| 1.5KE30A                | 1.5KE30CA               | 25.60                    | 28.50                                 | 31.50   | 1.0          | 5.0                                         | 41.4                                | 36.0                    | 0.097                                    |
| 1.5KE33A                | 1.5KE33CA               | 28.20                    | 31.40                                 | 34.70   | 1.0          | 5.0                                         | 45.7                                | 33.0                    | 0.098                                    |
| 1.5KE36A                | 1.5KE36CA               | 30.80                    | 34.20                                 | 37.80   | 1.0          | 5.0                                         | 49.9                                | 30.0                    | 0.099                                    |
| 1.5KE39A                | 1.5KE39CA               | 33.30                    | 37.10                                 | 41.00   | 1.0          | 5.0                                         | 53.9                                | 28.0                    | 0.100                                    |
| 1.5KE43A                | 1.5KE43CA               | 36.80                    | 40.90                                 | 45.20   | 1.0          | 5.0                                         | 59.3                                | 25.3                    | 0.101                                    |
| 1.5KE47A                | 1.5KE47CA               | 40.20                    | 44.70                                 | 49.40   | 1.0          | 5.0                                         | 64.8                                | 23.2                    | 0.101                                    |
| 1.5KE51A                | 1.5KE51CA               | 43.60                    | 48.50                                 | 53.60   | 1.0          | 5.0                                         | 70.1                                | 21.4                    | 0.102                                    |
| 1.5KE56A                | 1.5KE56CA               | 47.80                    | 53.20                                 | 58.80   | 1.0          | 5.0                                         | 77.0                                | 19.5                    | 0.103                                    |
| 1.5KE62A                | 1.5KE62CA               | 53.00                    | 58.90                                 | 65.10   | 1.0          | 5.0                                         | 85.0                                | 17.7                    | 0.104                                    |
| 1.5KE68A                | 1.5KE68CA               | 58.10                    | 64.60                                 | 71.40   | 1.0          | 5.0                                         | 92.0                                | 16.3                    | 0.104                                    |
| 1.5KE75A                | 1.5KE75CA               | 64.10                    | 71.30                                 | 78.80   | 1.0          | 5.0                                         | 103.0                               | 14.6                    | 0.105                                    |
| 1.5KE82A                | 1.5KE82CA               | 70.10                    | 77.90                                 | 86.10   | 1.0          | 5.0                                         | 113.0                               | 13.3                    | 0.105                                    |
| 1.5KE91A                | 1.5KE91CA               | 77.80                    | 86.50                                 | 95.50   | 1.0          | 5.0                                         | 125.0                               | 12.0                    | 0.106                                    |
| 1.5KE100A               | 1.5KE100CA              | 85.50                    | 95.00                                 | 105.00  | 1.0          | 5.0                                         | 137.0                               | 11.0                    | 0.106                                    |
| 1.5KE110A               | 1.5KE110CA              | 94.00                    | 105.00                                | 116.00  | 1.0          | 5.0                                         | 152.0                               | 9.9                     | 0.107                                    |
| 1.5KE120A               | 1.5KE120CA              | 102.00                   | 114.00                                | 126.00  | 1.0          | 5.0                                         | 165.0                               | 9.1                     | 0.107                                    |
| 1.5KE130A               | 1.5KE130CA              | 111.00                   | 124.00                                | 137.00  | 1.0          | 5.0                                         | 179.0                               | 8.4                     | 0.107                                    |
| 1.5KE150A               | 1.5KE150CA              | 128.00                   | 143.00                                | 158.00  | 1.0          | 5.0                                         | 207.0                               | 7.2                     | 0.108                                    |
| 1.5KE160A               | 1.5KE160CA              | 136.00                   | 152.00                                | 168.00  | 1.0          | 5.0                                         | 219.0                               | 6.8                     | 0.108                                    |
| 1.5KE170A               | 1.5KE170CA              | 145.00                   | 162.00                                | 179.00  | 1.0          | 5.0                                         | 234.0                               | 6.4                     | 0.108                                    |
| 1.5KE180A               | 1.5KE180CA              | 154.00                   | 171.00                                | 189.00  | 1.0          | 5.0                                         | 246.0                               | 6.1                     | 0.108                                    |
| 1.5KE200A               | 1.5KE200CA              | 171.00                   | 190.00                                | 210.00  | 1.0          | 5.0                                         | 274.0                               | 5.5                     | 0.108                                    |
| 1.5KE220A               | 1.5KE220CA              | 185.00                   | 209.00                                | 231.00  | 1.0          | 5.0                                         | 328.0                               | 4.6                     | 0.108                                    |
| 1.5KE250A               | 1.5KE250CA              | 214.00                   | 237.00                                | 263.00  | 1.0          | 5.0                                         | 344.0                               | 5.0                     | 0.110                                    |
| 1.5KE300A               | 1.5KE300CA              | 256.00                   | 285.00                                | 315.00  | 1.0          | 5.0                                         | 414.0                               | 5.0                     | 0.110                                    |
| 1.5KE350A               | 1.5KE350CA              | 300.00                   | 332.00                                | 368.00  | 1.0          | 5.0                                         | 482.0                               | 4.0                     | 0.110                                    |
| 1.5KE400A               | 1.5KE400CA              | 342.00                   | 380.00                                | 420.00  | 1.0          | 5.0                                         | 548.0                               | 4.0                     | 0.110                                    |

Notes: 1. Suffix 'C' denotes bidirectional device.  
2. For bidirectional devices having  $V_R$  of 10 volts and under, the  $I_R$  limit is doubled.




Fig. 1 Pulse Waveform




Fig. 2 Typical Total Capacitance




Fig. 3 Pulse Rating Curve




Fig. 4 Pulse Derating Curve




Fig. 5 Steady State Power Derating

**Ordering Information** (Note 4 & 5)

| Device           | Packaging | Shipping                |
|------------------|-----------|-------------------------|
| (Type Number)-B* | DO-201    | 1K/Bulk                 |
| (Type Number)-T* | DO-201    | 1K/Tape & Reel, 13-inch |

- Notes:
- \*Add "-B" or "-T" to the appropriate type number in Table 1. Example: 6.40 Reverse Standoff Voltage, UNI = 1.5KE7V5A-B.
  - For packaging details, visit our website at <http://www.diodes.com/datasheets/ap02008.pdf>.

**IMPORTANT NOTICE**

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)