

Specification for release

Customer :

Order Code : **8492121**

Description : **WE-USBH Connector with Integrated EMI & ESD function**

Package: **USB2.0 Type A THT**



Date: 2014-03-13

A Features:

- ESD Protection of data channels and VDD
- Common Mode Noise Rejection
- VDD Differential Mode Noise Rejection
- Provides ESD protection for each channel to
IEC 61000-4-2 (ESD) $\pm 15\text{kV}$ (air), $\pm 8\text{kV}$ (contact)
IEC 61000-4-4 (EFT) (5/50ns) 20A (I/O), 40A VDD
IEC 61000-4-5 (Lightning) 6A (8/20 μs)
- Ultra Low capacitance: 2pF typical
- Fast turn on and low clamping voltage

B Overview:




C Maximum Ratings:

Operating Supply Voltage	$V_{DD} - \text{GND}$	V_{DC}	6	V
ESD per IEC 61000-4-2 (Air / Contact)	D+/D- - GND	$V_{ESD,D+/D-}$	16 / 10	kV
ESD per IEC 61000-4-2 (Air / Contact)	$V_{DD} - \text{GND}$	$V_{ESD,VDD}$	30 / 20	kV
Operating Temperature		T_{Op}	-40 to +85	°C
Storage Temperature		T_{Sto}	-20 to +60	°C

D Material Characteristics:

Insulator	LCP UL-94V0
Color	Black
Contact	Phosphor Bronze
Contact Area Plating	Gold
Shielding	Brass
Mating Force / Unmating Force	35 N / 10 N
Quality Class	1500 Mating Cycles

E Schematic:



F Electrical Characteristics:

Characteristics			test conditions	tolerance	value	unit
Common Mode Impedance	D+/D-	Z	100MHz	± 25 %	90	Ω
Differential Mode Impedance	V _{DD} - GND	Z _{VDD}	100MHz	± 25 %	400	Ω
DC Resistance ¹	V _{DD}	R _{DC}	@ 20 °C	max.	150	mΩ
DC Resistance ¹	D+/D-	R _{DC}	@ 20 °C	max.	180	mΩ
Rated Voltage	V _{DD}	V _{DD}		max.	5	V
Breakdown Voltage ²	V _{DD} - GND	V _{BV}	I _{BV} =1mA	min.	6	V
Low Level Contact Resistance ¹		R _{CR}		max.	30	mΩ
Insertion Capacitance ²	D+/D- - GND	C _{IO}	f=1MHz	typ.	2	pF

¹) Resistance PCB-pin to connector-pin consists of $R_{DC} + R_{CR}$

²) TVS-Diode Array Specification figures

Approval/Release:	Kunde / customer			
Datum / date	Unterschrift / signature			
	Würth Elektronik			
Geprüft / checked	Kontrolliert / approved	Mle	Test-Version 2	2014-03-14
		OO	Test-Version	2011-01-27
		Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 -3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
http://www.we-online.com

Specification for release

Customer :

Order Code : **8492121**



Description : **WE-USBH Connector with Integrated EMI & ESD function**

Package: **USB2.0 Type A THT**





Date: 2014-03-13

G1 Impedance graph D+/D- (typical)



* 50Ω system impedance measured on PCB level

G2 Impedance graph V_{DD} - GND (typical)



** 50Ω system impedance measured on PCB level

H Test Equipment:

HP4191B for Z and a
GMC Metrahit 27I for R_{DC}
Agilent E4991A for SRF

J Test Conditions:

Humidity: 33%
Ambient temperature: +20°C

Approval/Release:

Kunde / customer

Datum / date

Unterschrift / signature

Würth Elektronik

Geprüft / checked

Kontrolliert / approved

Mle	Test-Version 2	2014-03-14	
OO	Test-Version	2011-01-27	
Name	Änderung / modification	Datum / date	

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 -3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>

Specification for release

Customer :

Order Code : **8492121**





Description : **WE-USBH Connector with Integrated EMI & ESD function**

Package: **USB2.0 Type A THT**




Date: 2014-03-13

K Dimensions:



L Recommended Land Pattern:



Approval/Release:	Kunde / customer			
Datum / date	Unterschrift / signature			
	Würth Elektronik			
		Mle	Test-Version 2	2014-03-14
		OO	Test-Version	2011-01-27
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 -3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>


Specification for release

Customer :
 Order Code : **8492121**
 Description : **WE-USBH Connector with Integrated EMI & ESD function**
 Package: **USB2.0 Type A THT**




Date: 2014-03-13

M Tape & Reel specifications:




Gurtspezifikation / Tape specification:

A	$1,42 \pm 0,1$	mm
B	$4,00 \pm 0,1$	mm
C	$1,50 \pm 0,05$	mm
D	$2,00 \pm 0,1$	mm
E	$1,75 \pm 0,1$	mm
F	$3,50 \pm 0,1$	mm
G	$1,30 \pm 0,1$	mm
H	$2,26 \pm 0,1$	mm
T	$0,23 \pm 0,05$	mm
W	$8,00 \pm 0,1$	mm



Rollenspezifikation / Reel Specification:

a	$178,0 \pm 0,1$	mm
b	$21,00 \pm 0,1$	mm
c	$50,00 \pm 0,1$	mm
d	$10,00 \pm 0,1$	mm



The force of tearing off cover tape is 0,2 to 0,7 N in arrow direction.

Approval/Release:	Kunde / customer			
Datum / date	Unterschrift / signature			
	Würth Elektronik			
		Mle	Test-Version 2	2014-03-14
		OO	Test-Version	2011-01-27
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 -3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru