




PRODUCT NUMBER
SEE SHEET 10

ODD COLUMN
CONTACT ROW ID
ODD AND EVEN
COLUMNS ARE
OFFSET

EVEN COLUMN
CONTACT ROW ID

CONNECTOR MATING FACE

HOUSING

SEE NOTE 6

IMLA

ORGANIZER

10125287-101LF
STANDARD MATE CONNECTOR

spec ref		---		dr		N Eppley		2013/04/24		projection		MM		size		A2		scale		1:1		
tolerance std		ASME Y14.5M		eng		Peng-Bing Fu		2017/11/08					ecn no		ELX-DG-28221-1							
TOLERANCES UNLESS OTHERWISE SPECIFIED		chr		Justin Chen		2017/11/29		rel level					Released									
		appr		Heaven Cen		2017/11/30		product family					ExaMAX									
surface		linear		0.X		±.3		Amphenol FCI			title		ExaMAX R.A. HEADER		dwg no		10125287		rev		B	
				0.XX		±.10																
				0.XXX		±.050																
		angular		0°		±°																


PDS: Rev :B

STATUS:Released

Printed: Dec 02, 2017


Amphenol
FCI

© 2016 APCI






10125287-201LF
ADVANCED MATE CONNECTOR
ADVANCED MATE POSITIONS ARE POSITIONS A1 AND A5 ONLY
FOR ALL OTHER DIMENSIONS SEE 10125287-101LF ON SHEET 1

spec ref				---		dr		N Eppley		2013/04/24		projection		MM		size		A2		scale		8:1	
tolerance std				TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		Peng-Bing Fu		2017/11/08						ecn no		ELX-DG-28221-1					
ASME Y14.5M						chr		Justin Chen		2017/11/29						product family		ExaMAX		rel level		Released	
						appr		Heaven Cen		2017/11/30													
surface		- ✓		linear		0.X 0.XX 0.XXX		±.3 ±.10 ±.050		Amphenol FCi		title		ExaMAX R.A. HEADER		dwg no		10125287		rev		B	
				angular		0°		±°		cat. no.		SEE TABLE		Product - Customer Drw		sheet 2 of 11							




10125287-401LF
ADVANCED MATE/SHORT DETECT CONNECTOR
ADVANCED MATE POSITIONS ARE POSITIONS A1 AND A5 ONLY
SHORT DETECT POSITIONS IS N2 ONLY
FOR ALL OTHER DIMENSIONS SEE 10125287-101LF ON SHEET 1


spec ref		---		dr		N Eppley		2013/04/24		projection		size		scale					
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		Peng-Bing Fu		2017/11/08						A2 8:1					
ASME Y14.5M				chr		Justin Chen		2017/11/29											
				appr		Heaven Cen		2017/11/30		product family		ExaMAX		ecn no		ELX-DG-28221-1			
												rel level		Released					
surface		- 		linear		Amphenol FCi		title		ExaMAX R.A. HEADER		dwg no		10125287		rev			
				0.X														±.3	
				0.XX														±.10	
				0.XXX		±.050													
				angular		±°													
								cat. no.		SEE TABLE		Product - Customer Drw		sheet 4 of 11		B			



DETAIL A
SCALE 20:1


RECOMMENDED PCB LAYOUT
10125287-Y01LF COMPONENT SIDE
SEE NOTES 7, 8, 9 & 11
SCALE 10:1

spec ref		---		dr		N Eppley		2013/04/24		projection				MM				size		A2		scale		1:1									
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		Peng-Bing Fu		2017/11/08				ecn no		ELX-DG-28221-1		rel level		Released															
ASME Y14.5M				chr		Justin Chen		2017/11/29				product family		ExaMAX																			
surface - 		linear		0.X ±.3 0.XX ±.10 0.XXX ±.050		Amphenol FCI		title		ExaMAX R.A. HEADER		ASS'Y, 4 PR, 84 POS, 6 IMLA, 11.9 MM		dwg no		10125287		rev		B													
																										cat. no.		SEE TABLE		Product - Customer Drw		sheet 5 of 11	
																										angular		0° ±.0					



Amphenol
FCi


© 2016 AFci

spec ref ---				dr	N Eppley	2013/04/24	projection 	MM 	size	A2	scale	8:1		
tolerance std				eng	Peng-Bing Fu	2017/11/08			ecn no	ELX-DG-28221-1				
ASME Y14.5M				TOLERANCES UNLESS OTHERWISE SPECIFIED					chr	Justin Chen	2017/11/29	rel level	Released	
				appr	Heaven Cen	2017/11/30	product family		ExaMAX					
surface - 	linear	0.X	±.3	Amphenol FCi	title	ExaMAX R.A. HEADER					dwg no	10125287	rev	B
		0.XX	±.10											
		0.XXX	±.050			ASS'Y, 4 PR, 84 POS, 6 IMLA, 11.9 MM								
	angular	0°	±°			cat. no.								

PDS: Rev :B



STATUS:Released

Printed: Dec 02, 2017



RECOMMENDED PCB LAYOUT FOR
10125287-Y1ALF THRU -Y1JLF
W/RIGHT GUIDANCE COMPONENT SIDE
SEE NOTES 7, 8, 9, 11 & 16

spec ref		---		dr		N Eppley		2013/04/24		projection		MM		size		A2		scale		8:1							
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		Peng-Bing Fu		2017/11/08						ecn no		ELX-DG-28221-1											
chr				Justin Chen		2017/11/29		rel level						Released													
ASME Y14.5M				appr		Heaven Cen		2017/11/30						product family		ExaMAX											
surface		- 		linear		0.X		±.3		Amphenol FCI		title		ExaMAX R.A. HEADER		dwg no		10125287		rev		B					
																								0.XX		±.10	
																								0.XXX		±.050	
																								angular		0°	
cat. no.		SEE TABLE		Product -		Customer Drw		sheet 7 of 11																			

























RECOMMENDED PCB LAYOUT FOR
10125287-Y2ALF THRU -Y2JLF
W/LEFT GUIDANCE COMPONENT SIDE
SEE NOTES 7, 8, 9, 11 & 16

spec ref				---		dr		N Eppley		2013/04/24		projection		MM		size		scale											
tolerance std				ASME Y14.5M		eng		Peng-Bing Fu		2017/11/08						A2		8:1											
TOLERANCES UNLESS OTHERWISE SPECIFIED						chr		Justin Chen		2017/11/29						ecn no				ELX-DG-28221-1									
						appr		Heaven Cen		2017/11/30						product family				ExaMAX				rel level		Released			
surface		- 		linear		0.X		±.3		Amphenol FCI		title		ExaMAX R.A. HEADER						dwg no		10125287		rev					
																										0.XX		±.10	
																										0.XXX		±.050	
				angular		0°		±°				cat. no.		SEE TABLE		Product - Customer Drw				sheet 9 of 11									

10125287 - Y Y Y L F

ASSEMBLY PART NUMBER	DESCRIPTION
10125287-1YYLF	STANDARD MATE
10125287-2YYLF	ADVANCED MATE
10125287-3YYLF	SHORT DETECT
10125287-4YYLF	ADVANCED MATE & SHORT DETECT

MODULE DESCRIPTION	DESIGNATION REPRESENTED IN DASH NUMBER									BASE MODULE
STANDARD NO GUIDANCE (SEE SHEET 1)	01									
RIGHT GUIDANCE MODULE (SEE SHEET 6)	1A	1B	1C	1D	1E	1F	1G	1H	1J (NO KEY)	
										
LEFT GUIDANCE MODULE (SEE SHEET 8)	2A	2B	2C	2D	2E	2F	2G	2H	2J (NO KEY)	
										

spec ref		---		dr		N Eppley		2013/04/24		projection				size		A2		scale		1:1	
tolerance std		TOLERANCES UNLESS OTHERWISE SPECIFIED		eng		Peng-Bing Fu		2017/11/08						ecn no		ELX-DG-28221-1					
ASME Y14.5M				chr		Justin Chen		2017/11/29						rel level		Released					
				appr		Heaven Cen		2017/11/30						product family		ExaMAX					
surface - 		linear				title		ExaMAX R.A. HEADER		dwg no		10125287		rev		B					
																		0.X		±.3	
																		0.XX		±.10	
																		0.XXX		±.050	
		angular		0°		±°		cat. no.		SEE TABLE		Product - Customer Drw		sheet 10 of 11							

1		2		3		4		5		6		7		8																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
NOTES:																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
A		① - CONNECTOR MATERIALS: HOUSING: HIGH TEMP THERMOPLASTIC, BLACK, UL94-V0 IMLA PLASTIC: HIGH TEMP THERMOPLASTIC, BLACK, UL94-V0 CONTACT: COPPER ALLOY ORGANIZER: HIGH TEMP THERMOPLASTIC, BLACK, UL94-V0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		B		2 - CONTACT PLATING: SEPARABLE INTERFACE: PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12-1096 INCLUDING TELCORDIA GR-1217-CORE (NOVEMBER 1995) CENTRAL OFFICE TEST SEQUENCE PRESS-FIT TAILS: TIN OVER NICKEL (LEAD FREE)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
C		3 - PRODUCT SPECIFICATION: GS-12-1096																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		4 - APPLICATION SPECIFICATION: GS-20-0361																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		5 - PACKAGING MEETS GS-14-920 LEAD FREE LABELING SPECIFICATION.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		⑥ - PRODUCT MARKING, (PROTOTYPE, PART NUMBER & LOT CODE), ON THIS SURFACE.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
D		⑦ - THE MINIMUM VIA SPACING BETWEEN STACKED CONNECTORS WILL BE 2.0 mm OR 3.0 mm AS DEFINED BY NOTE 7 ON THE MATING RECEPTACLE CUSTOMER DRAWING. REFER TO THE APPLICATION SPECIFICATION FOR DETAILS.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		⑧ - CONNECTOR OUTLINE MAY BE SCREEN PRINTED ONTO CUSTOMER PCB TO BE USED AS A GUIDE FOR MANUAL CONNECTOR PLACEMENT.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		⑨ - REFER TO CUSTOMER DRAWING 10119933 FOR INFORMATION ON PCB HOLE DIAMETERS AND PLATING OPTIONS																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		10 - THIS PRODUCT MEETS THE EUROPEAN UNION DIRECTIVES & OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-47-0004																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
E		⑪ - REFER TO ROUTING GUIDE GS-20-0511 FOR RECOMMENDATIONS ON OPTIMIZATION OF FOOTPRINT AND TRACE ROUTING LAYOUT.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		12 - THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10-30 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		⑬ - THE ADVANCED MATE HEADER, 10125287-2YYLF, WHEN MATED WITH AN ADVANCED MATE RECEPTACLE WILL PROVIDE 2 PAIRS OF MATING CONTACTS THAT MATE 0.75MM BEFORE THE REMAINDER OF THE SIGNAL AND GROUND CONTACTS.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		⑭ - THE SHORT DETECT HEADER, 10125287-3YYLF, WHEN MATED WITH A STANDARD MATE RECEPTACLE WILL PROVIDE 1 PAIR OF MATING CONTACTS THAT MATE 1.00 MM AFTER THE REMAINDER OF THE SIGNAL AND GROUND CONTACTS.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
F		⑮ - THE ADVANCED MATE/SHORT DETECT HEADER, 10125287-4YYLF, WHEN MATED WITH AN ADVANCED MATE RECEPTACLE WILL PROVIDE 2 PAIRS OF MATING CONTACTS THAT MATE 0.75 MM BEFORE THE REMAINDER OF THE SIGNAL AND GROUND CONTACTS AND 1 PAIR OF MATING CONTACTS THAT MATE 1.00 MM AFTER THE REMAINDER OF THE SIGNAL AND GROUND CONTACTS.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		⑯ - FOR CONNECTORS WITH EITHER A RIGHT OR LEFT GUIDE MODULE, TWO PHILLIPS PAN HEAD M2 HOLD-DOWN SCREWS MUST BE USED TO SECURE THE CONNECTOR TO THE PCB. THE SCREW LENGTH SHALL BE 2.0-6.0MM PLUS THE THICKNESS OF THE PCB. SCREWS ARE NOT PROVIDED WITH CONNECTOR.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		⑰ - LEFT / RIGHT INTEGRATED GUIDE ORIENTATION IS DETERMINED BY THE LOCATION OF THE GUIDE FEATURES WHEN LOOKING AT THE MATING FACE OF THE RIGHT ANGEL RECEPTACLE. THE LEFT / RIGHT DESIGNATION OF THE MATING HEADER IS DEFINED BY THE RIGHT ANGEL RECEPTACLE THAT IT MATES WITH (i. e. A RIGHT GUIDE RIGHT ANGEL HEADER MATES WITH A RIGHT ANGEL RECEPTACLE.)																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
		⑱ - ALL GROUND CONTACTS ARE COMMONED WITHIN A COLUMN.																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
<table><tr><td colspan="2">spec ref</td><td colspan="2">---</td><td colspan="2">dr</td><td colspan="2">N'Eppley</td><td colspan="2">2013/04/24</td><td colspan="2">projection</td><td colspan="2">MM</td><td colspan="2">size</td><td colspan="2">A2</td><td colspan="2">scale</td><td colspan="2">1:1</td></tr><tr><td colspan="2">tolerance std</td><td colspan="2">ASME Y14.5M</td><td colspan="2">eng</td><td colspan="2">Peng-Bing Fu</td><td colspan="2">2017/11/08</td><td colspan="2">chr</td><td colspan="2">Justin Chen</td><td colspan="2">2017/11/29</td><td colspan="2">ecn no</td><td colspan="2">ELX-DG-28221-1</td><td colspan="2"></td></tr><tr><td colspan="2">surface</td><td colspan="2">- ✓</td><td colspan="2">appr</td><td colspan="2">Heaven Cen</td><td colspan="2">2017/11/30</td><td colspan="2">product family</td><td colspan="2">ExaMAX</td><td colspan="2">rel level</td><td colspan="2">Released</td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td><td colspan="2"></td></tr><tr><td colspan="2"></td></tr></table>																spec ref		---		dr		N'Eppley		2013/04/24		projection		MM		size		A2		scale		1:1		tolerance std		ASME Y14.5M		eng		Peng-Bing Fu		2017/11/08		chr		Justin Chen		2017/11/29		ecn no		ELX-DG-28221-1				surface		- ✓		appr		Heaven Cen		2017/11/30		product family		ExaMAX		rel level		Released																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																	
spec ref		---		dr		N'Eppley		2013/04/24		projection		MM		size		A2		scale		1:1																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																									
tolerance std		ASME Y14.5M		eng		Peng-Bing Fu		2017/11/08		chr		Justin Chen		2017/11/29		ecn no		ELX-DG-28221-1																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
surface		- ✓		appr		Heaven Cen		2017/11/30		product family		ExaMAX		rel level		Released																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru