

2.4GHz Band SP3T Switch + LNA GaAs MMIC

■ GENERAL DESCRIPTION


The NJG1730MD7 is a 2.4GHz band SP3T Switch + low noise amplifier GaAs MMIC designed for wireless LAN and Bluetooth front-end applications.

The NJG1730MD7 features low insertion loss of Transmit/Bluetooth path and high gain and low noise figure of RX LNA mode.

The NJG1730MD7 has ESD protection devices to achieve excellent ESD performances.

A small and ultra-thin package of EQFN14-D7 is adopted.

■ PACKAGE OUTLINE



NJG1730MD7


■ APPLICATIONS

2.4GHz Band WLAN and Bluetooth front-end application

■ FEATURES

- Operating voltage $V_{DD}=3.6V$ typ.
- Operating frequency $freq=2400$ to $2500MHz$
- [RX LNA mode]
 - Operating current $10mA$ typ. @ $V_{DD}=3.6V$, $V_{CTL1}=V_{CTL4}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$
 - Small signal gain $15.0dB$ typ.
 - Noise figure $1.6dB$ typ.
 - Input power 1dB compression $-4dBm$ typ.
- [RX Bypass mode]
 - Operating current $4\mu A$ typ. @ $V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=V_{CTL4}=0V$
 - Input power 1dB compression $+9dBm$ typ.
- [TX mode]
 - Insertion loss $0.5dB$ typ.
 - Input power 0.1dB compression $+30dBm$ typ.
- [BT mode]
 - Insertion loss $0.6dB$ typ.
 - Input power 0.1dB compression $+26dBm$ typ.
- Package EQFN14-D7 (Package size: $1.6mm \times 1.6mm \times 0.397mm$ typ.)
- RoHS compliant and Halogen Free, MSL1

■ PIN CONFIGURATION



Pin Connection

- | | |
|-----------|-----------|
| 1. GND | 8. GND |
| 2. TX | 9. VDD |
| 3. VCTL2 | 10. BT |
| 4. GND | 11. GND |
| 5. GND | 12. VCTL3 |
| 6. LNAOUT | 13. VCTL1 |
| 7. VCTL4 | 14. ANT |
- Exposed Pad: GND

Note: Specifications and description listed in this datasheet are subject to change without notice.

■ ABSOLUTE MAXIMUM RATINGS

Ta=+25°C

PARAMETERS	SYMBOL	CONDITIONS	RATINGS	UNITS
Supply voltage	V _{DD}		5.5	V
Control voltage	V _{CTL}		5.5	V
Input power 1	P _{IN1}	ANT terminal, V _{DD} =3.6V, V _{CTL1} =3.3V V _{CTL2} =V _{CTL3} =0V, V _{CTL4} =3.3/0V	+15	dBm
Input power 2	P _{IN2}	TX terminal, V _{DD} =3.6V, V _{CTL2} =3.3V V _{CTL1} =V _{CTL3} =V _{CTL4} =0V	+25	dBm
Input power 3	P _{IN3}	BT terminal, V _{DD} =3.6V, V _{CTL3} =3.3V V _{CTL1} =V _{CTL2} =V _{CTL4} =0V	+25	dBm
Power dissipation	P _D	Four-layer FR4 PCB with through-hole (76.2x114.3mm), T _j =150°C	1300	mW
Operation temperature	T _{opr}		-40 to +85	°C
Storage temperature	T _{stg}		-55 to +150	°C

■ ELECTRICAL CHARACTERISTICS 1 (DC Characteristics)

V_{DD}=3.6V, V_{CTL(H)}=3.3V, V_{CTL(L)}=0V, Ta=+25°C, Z_s=Z_l=50Ω

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Supply voltage	V _{DD}		3.0	3.6	5.0	V
Control voltage 1(High)	V _{CTL1(H)}		2.8	3.3	5.0	V
Control voltage 2(High)	V _{CTL2(H)}		2.8	3.3	5.0	V
Control voltage 3(High)	V _{CTL3(H)}		2.8	3.3	5.0	V
Control voltage 4(High)	V _{CTL4(H)}		2.8	3.3	5.0	V
Control voltage 1(Low)	V _{CTL1(L)}		0.0	-	0.4	V
Control voltage 2(Low)	V _{CTL2(L)}		0.0	-	0.4	V
Control voltage 3(Low)	V _{CTL3(L)}		0.0	-	0.4	V
Control voltage 4(Low)	V _{CTL4(L)}		0.0	-	0.4	V
LNA operating current 1 (RX LNA mode)	I _{DD1}	RF OFF, V _{CTL1} =V _{CTL4} =3.3V, V _{CTL2} =V _{CTL3} =0V	-	10	14	mA
LNA operating current 2 (RX Bypass mode)	I _{DD2}	RF OFF, V _{CTL1} =3.3V, V _{CTL2} =V _{CTL3} =V _{CTL4} =0V	-	4	15	μA
LNA operating current 3 (Sleep mode)	I _{DD3}	RF OFF, V _{CTL1} =V _{CTL2} =V _{CTL3} =V _{CTL4} =0.4V	-	4	15	μA
LNA operating current 4 (VCTL OPEN)	I _{DD4}	RF OFF, V _{CTL1} =V _{CTL2} =V _{CTL3} =V _{CTL4} =open	-	4	15	μA
Control current 1	I _{CTL1}	RF OFF, V _{CTL1} =3.3V, V _{CTL2} =V _{CTL3} =V _{CTL4} =0V	-	5	20	μA
Control current 2	I _{CTL2}	RF OFF, V _{CTL2} =3.3V, V _{CTL1} =V _{CTL3} =V _{CTL4} =0V	-	5	20	μA
Control current 3	I _{CTL3}	RF OFF, V _{CTL3} =3.3V, V _{CTL1} =V _{CTL2} =V _{CTL4} =0V	-	5	20	μA
Control current 4	I _{CTL4}	RF OFF, V _{CTL4} =3.3V, V _{CTL1} =V _{CTL2} =V _{CTL3} =0V	-	5	20	μA

■ ELECTRICAL CHARACTERISTICS 2 (RF Characteristics: RX LNA mode, LNA+SP3T SW)

$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL4}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, freq=2400 to 2500MHz,
 $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$, with application circuit

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Small signal gain 1	Gain1	Exclude PCB and connector losses*1	13.0	15.0	17.0	dB
Gain flatness 1	Gflat1	f=2400 to 2420MHz, f=2440 to 2460MHz, f=2480 to 2500MHz	-	-	0.25	dB
Isolation 1	ISL1		-	28	-	dB
Noise figure 1	NF1	Exclude PCB and connector losses*2	-	1.6	1.9	dB
Input power at 1dB compression 1	$P_{-1dB(IN)1}$		-	-4	-	dBm
Input 3rd order Intercept point 1	IIP3_1	f1=freq, f2=freq+100kHz, $P_{IN}=-22dBm$	-	+7	-	dBm
ANT port return loss 1	RLi1		-	12	-	dB
LNAOUT port return loss 1	RLo1		-	10	-	dB
LNA switching time	Tsw1_1		-	100	400	ns
Other switching time	Tsw2_1		-	200	500	ns

*1) 0.36dB (2400MHz), 0.36dB (2450MHz), 0.37dB (2500MHz)

*2) 0.18dB (2400MHz), 0.18dB (2450MHz), 0.18dB (2500MHz)

■ ELECTRICAL CHARACTERISTICS 3 (RF Characteristics: RX Bypass mode, Bypass SW+SP3T SW)

$V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=V_{CTL4}=0V$, freq=2400 to 2500MHz,
 $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$, with application circuit

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Insertion loss 2	LOSS2	Exclude PCB and connector losses*3	4.0	6.0	8.0	dB
Input power at 1dB compression 2	$P_{-1dB(IN)2}$		-	+9	-	dBm
Input 3rd order Intercept point 2	IIP3_2	f1=freq, f2=freq+100kHz, $P_{IN}=-14dBm$	-	+13	-	dBm
ANT port return loss 2	RLi2		-	7	-	dB
LNAOUT port return loss 2	RLo2		-	7	-	dB

*3) 0.36dB (2400MHz), 0.36dB (2450MHz), 0.37dB (2500MHz)

■ ELECTRICAL CHARACTERISTICS 4 (RF Characteristics: TX mode)

$V_{DD}=3.6V$, $V_{CTL2}=3.3V$, $V_{CTL1}=V_{CTL3}=V_{CTL4}=0V$, freq=2400 to 2500MHz,
 $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$, with application circuit

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Insertion loss 3	LOSS3	$P_{IN}=+23dBm$, Exclude PCB and connector losses*4	-	0.5	0.7	dB
Input power at 0.1dB compression 3	$P_{-0.1dB(IN)3}$		-	+30	-	dBm
ANT port return loss 3	RLi3		-	22	-	dB
TX port return loss 3	RLo3		-	22	-	dB

*4) 0.34dB (2400MHz), 0.35dB (2450MHz), 0.36dB (2500MHz)

■ ELECTRICAL CHARACTERISTICS 5 (RF Characteristics: BT mode)

$V_{DD}=3.6V$, $V_{CTL3}=3.3V$, $V_{CTL1}=V_{CTL2}=V_{CTL4}=0V$, freq=2400 to 2500MHz,
 $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$, with application circuit

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Insertion loss 4	LOSS4	$P_{IN}=+20dBm$, Exclude PCB and connector losses*5	-	0.6	0.8	dB
Input power at 0.1dB compression 4	$P_{-0.1dB(IN)4}$		-	+26	-	dBm
ANT port return loss 4	RLi4		-	22	-	dB
BT port return loss 4	RLo4		-	22	-	dB

*5) 0.70dB (2400MHz), 0.72dB (2450MHz), 0.73dB (2500MHz)

■ ELECTRICAL CHARACTERISTICS 6 (RF Characteristics)

$V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $V_{CTL4}=3.3/0V$, freq=2400 to 2500MHz,
 $T_a=+25^{\circ}C$, $Z_s=Z_l=50\Omega$, with application circuit

PARAMETERS	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Gain dynamic range	GDR	Gain1+LOSS2	18.0	21.0	24.0	dB


■ TERMINAL INFORMATION

Pin No.	SYMBOL	DESCRIPTION
1	GND	Ground terminal. Please connect this terminal with ground plane as close as possible for excellent RF performance.
2	TX	RF transmitting signal input terminal. DC blocking capacitor is required for this port.
3	VCTL2	Control signal input terminal. This terminal is set to High-Level (+2.8 to +5.0V) or Low-Level (0 to +0.4V).
4	GND	Ground terminal. Please connect this terminal with ground plane as close as possible for excellent RF performance.
5	GND	Ground terminal. Please connect this terminal with ground plane as close as possible for excellent RF performance.
6	LNAOUT	RF receiving signal output terminal. No DC blocking capacitor is required for this port because of internal output matching circuit including DC blocking capacitor.
7	VCTL4	Control signal input terminal. This terminal is set to High-Level (+2.8 to +5.0V) or Low-Level (0 to +0.4V).
8	GND	Ground terminal. Please connect this terminal with ground plane as close as possible for excellent RF performance.
9	VDD	Positive voltage supply terminal. The positive voltage (+3.0 to +5.0V) has to be supplied. Please connect a bypass capacitor with GND terminal for excellent RF performance.
10	BT	Bluetooth terminal. No DC blocking capacitor is required for this port because of internal capacitor.
11	GND	Ground terminal. Please connect this terminal with ground plane as close as possible for excellent RF performance.
12	VCTL3	Control signal input terminal. This terminal is set to High-Level (+2.8 to +5.0V) or Low-Level (0 to +0.4V).
13	VCTL1	Control signal input terminal. This terminal is set to High-Level (+2.8 to +5.0V) or Low-Level (0 to +0.4V).
14	ANT	RF transmitting/receiving terminal. No DC blocking capacitor is required for this port because of internal capacitor.
Exposed Pad	GND	Ground terminal. Please connect this terminal with ground plane as close as possible for excellent RF performance, and through holes for GND should be placed near by the pin connection

ELECTRICAL CHARACTERISTICS (RX LNA mode)


$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL4}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $T_a=25^\circ C$, $Z_s=Z_l=50\Omega$

Gain, NF vs. Frequency




Gain, I_{DD} vs. P_{IN}

(f=2450MHz)




P-1dB(IN) vs. Frequency




P_{OUT} vs. P_{IN}

(f=2450MHz)




IIP3, OIP3 vs. Frequency

(f₁=2400~2500MHz, f₂=f₁+100kHz, P_{in}=-22dBm)




P_{OUT}, IM3 vs. P_{IN}

(f₁=2450MHz, f₂=2450.1MHz)




ELECTRICAL CHARACTERISTICS (RX LNA mode)


$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL4}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $T_a=25^\circ C$, $Z_s=Z_l=50\Omega$




S11, S22 (f=50MHz to 6GHz)



S21, S12 (f=50MHz to 6GHz)




VSWRi, VSWRo (f=50MHz to 6GHz)




Zin, Zout (f=50MHz to 6GHz)

■ ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{DD}=3.6V$, $V_{CTL1}=V_{CTL4}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $T_a=25^\circ C$, $Z_s=Z_l=50\Omega$



S11, S22 (f=50MHz to 20GHz)




S21, S12 (f=50MHz to 20GHz)

■ ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{CTL1}=V_{CTL4}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $T_a=25^\circ C$, $Z_s=Z_l=50\Omega$


K factor vs. Frequency




■ ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{CTL1}=V_{CTL4}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $T_a=25^\circ C$, $Z_s=Z_l=50\Omega$


Gain vs. V_{DD}
($f=2450MHz$)



NF vs. V_{DD}
($f=2450MHz$)




P-1dB(IN) vs. V_{DD}



IIP3, OIP3 vs. V_{DD}

($f_1=2450MHz$, $f_2=2450.1MHz$, $P_{in}=-22dBm$)




ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{CTL1}=V_{CTL4}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $Z_S=Z_I=50\Omega$


Gain vs. Ambient Temperature

(f=2450MHz)




NF vs. Ambient Temperature

(f=2450MHz)




Reverse Isolation vs. Ambient Temperature

(f=2450MHz)




P-1dB(IN) vs. Ambient Temperature

(f=2450MHz)



IIP3 vs. Ambient Temperature

(f1=2450MHz, f2=2450.1MHz, Pin=-22dBm)




■ ELECTRICAL CHARACTERISTICS (RX LNA mode)

$V_{CTL1}=V_{CTL4}=3.3V$, $V_{CTL2}=V_{CTL3}=0V$, $Z_s=Z_l=50\Omega$


ANT Port Return Loss vs. Ambient Temperature

($f=2450MHz$)




LNAOUT Port Return Loss vs. Ambient Temperature


($f=2450MHz$)



Switching Time vs. Ambient Temperature
(Bypass Mode to LNA Mode)




Switching Time vs. Ambient Temperature
(TX mode to Bypass Mode)



K factor vs. Frequency


($V_{DD}=3.6V$)




■ ELECTRICAL CHARACTERISTICS (RX Bypass mode)

$V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=V_{CTL4}=0V$, $T_a=25^\circ C$, $Z_s=Z_l=50\Omega$


Loss vs. Frequency




Loss, I_{DD} vs. P_{IN}




P-1dB(IN) vs. Frequency




P_{OUT} vs. P_{IN}



IIP3, OIP3 vs. Frequency




P_{OUT}, IM3 vs. P_{IN}




ELECTRICAL CHARACTERISTICS (RX Bypass mode)


$V_{DD}=3.6V$, $V_{CTL1}=3.3V$, $V_{CTL2}=V_{CTL3}=V_{CTL4}=0V$, $T_a=25^\circ C$, $Z_s=Z_l=50\Omega$




S11, S22 (f=50MHz to 6GHz)



S21, S12 (f=50MHz to 6GHz)



VSWRi, VSWRo (f=50MHz to 6GHz)




Zin, Zout (f=50MHz to 6GHz)

ELECTRICAL CHARACTERISTICS (RX Bypass mode)

$V_{CTL1}=3.3V, V_{CTL2}=V_{CTL3}=V_{CTL4}=0V, Z_S=Z_I=50\Omega$


Loss vs. Ambient Temperature

(f=2450MHz)




P-1dB(IN) vs. Ambient Temperature

(f=2450MHz)




IIP3 vs. Ambient Temperature

(f1=2450MHz, f2=2450.1MHz, Pin=-14dBm)




ANT Port Return Loss vs. Ambient Temperature

(f=2450MHz)




LNAOUT Port Return Loss vs. Ambient Temperature

(f=2450MHz)



GDR vs. Ambient Temperature


(f=2450MHz)



■ ELECTRICAL CHARACTERISTICS (TX mode)


$V_{DD}=3.6V$, $V_{CTL2}=3.3V$, $V_{CTL1}=V_{CTL3}=V_{CTL4}=0V$, $T_a=25^{\circ}C$, $Z_s=Z_l=50\Omega$

Loss vs. Frequency




Loss vs. P_{IN}

(f=2450MHz)




ELECTRICAL CHARACTERISTICS (TX mode)


$V_{DD}=3.6V$, $V_{CTL2}=3.3V$, $V_{CTL1}=V_{CTL3}=V_{CTL4}=0V$, $T_a=25^{\circ}C$, $Z_s=Z_l=50\Omega$




S11, S22 (f=50MHz to 6GHz)



S21, S12 (f=50MHz to 6GHz)



VSWRi, VSWRo (f=50MHz to 6GHz)




Zin, Zout (f=50MHz to 6GHz)

■ ELECTRICAL CHARACTERISTICS (TX mode)

$V_{DD}=3.6V$, $V_{CTL2}=3.3V$, $V_{CTL1}=V_{CTL3}=V_{CTL4}=0V$, $Z_s=Z_l=50\Omega$


Loss vs. Ambient Temperature

(f=2450MHz)




ANT Port Return Loss vs. Ambient Temperature

(f=2450MHz)



TX Port Return Loss vs. Ambient Temperature


(f=2450MHz)



■ ELECTRICAL CHARACTERISTICS (BT mode)


$V_{DD}=3.6V$, $V_{CTL3}=3.3V$, $V_{CTL1}=V_{CTL2}=V_{CTL4}=0V$, $T_a=25^\circ C$, $Z_s=Z_l=50\Omega$

Loss vs. Frequency




Loss vs. P_{IN}

(f=2450MHz)




ELECTRICAL CHARACTERISTICS (BT mode)


$V_{DD}=3.6V$, $V_{CTL3}=3.3V$, $V_{CTL1}=V_{CTL2}=V_{CTL4}=0V$, $T_a=25^\circ C$, $Z_s=Z_l=50\Omega$




S11, S22 (f=50MHz to 6GHz)



S21, S12 (f=50MHz to 6GHz)



VSWR_i, VSWR_o (f=50MHz to 6GHz)




Z_{in}, Z_{out} (f=50MHz to 6GHz)

■ ELECTRICAL CHARACTERISTICS (BT mode)

$V_{DD}=3.6V$, $V_{CTL3}=3.3V$, $V_{CTL1}=V_{CTL2}=V_{CTL4}=0V$, $Z_s=Z_l=50\Omega$


Loss vs. Ambient Temperature

(f=2450MHz)




ANT Port Return Loss vs. Ambient Temperature

(f=2450MHz)




BT Port Return Loss vs. Ambient Temperature

(f=2450MHz)



■ PIN CONFIGURATION




■ TRUTH TABLE

“H”= $V_{CTL}(H)$, “L”= $V_{CTL}(L)$

mode	VCTL1 (SW RX)	VCTL2 (SW TX)	VCTL3 (SW BT)	VCTL4 (LNA)	STATE					
					IDD	LNA	Bypass	RX SW	TX SW	BT SW
RX LNA	H	L	L	H	I_{DD1}	ON	OFF	ON	OFF	OFF
RX Bypass	H	L	L	L	I_{DD2}	OFF	ON	ON	OFF	OFF
TX	L	H	L	L	I_{DD2}	OFF	ON	OFF	ON	OFF
BT	L	L	H	L	I_{DD2}	OFF	ON	OFF	OFF	ON
Sleep	L	L	L	L	I_{DD3}	OFF	OFF	OFF	OFF	OFF


APPLICATION CIRCUIT



PARTS LIST

ID No.	Value	Notes
C1	1000pF	MURATA (GRM03 series)
C2 to C4	10pF	
C5	56pF	
R1	10kΩ	KOA (RK73B series)


■ APPLIED CIRCUIT BOARD EXAMPLE



PCB Information

Substrate:	FR-4
Thickness:	0.2mm
Microstrip line width:	0.4mm ($Z_0=50\Omega$)
PCB size:	35.2mm x 16.8mm




<PCB LAYOUT GUIDELINE>




PRECAUTIONS

- [1] All external parts should be placed as close as possible to the IC.
- [2] For avoiding the degradation of RF performance, the bypass capacitor (C1) should be placed as close as possible to VDD terminal.
- [3] For good RF performance, the ground terminals must be placed possibly close to ground plane of substrate, and through holes for GND should be placed near by the pin connection.


RECOMMENDED FOOTPRINT PATTERN (EQFN14-D7 Package Reference)

-  : Land
-  : Mask (Open area) *Metal mask thickness: 100μm
-  : Resist (Open area)

Package: 1.6mm x 1.6mm
Pin pitch: 0.4mm



PACKAGE OUTLINE (EQFN14-D7)



Mold material: Epoxy resin
 Substrate material: Cu
 Terminal treatment: Sn-Bi Plating
 Units: mm
 Weight: 3.4mg

Cautions on using this product

This product contains Gallium-Arsenide (GaAs) which is a harmful material.

- Do NOT eat or put into mouth.
- Do NOT dispose in fire or break up this product.
- Do NOT chemically make gas or powder with this product.
- To waste this product, please obey the relating law of your country.

This product may be damaged with electric static discharge (ESD) or spike voltage. Please handle with care to avoid these damages.

[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions.

The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[NJR:](#)

[NJG1730MD7](#) [NJG1730MD7-TE1](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru