

7957A Multi-Conductor - Category 5e DataTuff® 600V AWM Rated Twisted Pair Cable



For more Information
please call

1-800-Belden1



General Description:

24 AWG Bonded-Pairs solid bare copper conductors, polyolefin insulation, overall Beldfoil® (100%coverage) plus tinned copper braid shield (70% coverage), drain wire, industrial grade sunlight- and oil-resistant PVC jacket. Seq. marking at 2 ft. intervals

Usage (Overall)

Suitable Applications:

Industrial Ethernet, Harsh Environments, Category 5e, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments, CMX - Outdoor, EtherNet/IP™

Physical Characteristics (Overall)

Conductor

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 4 | 24 | Solid | BC - Bare Copper |

Total Number of Conductors:

8

Insulation

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin |

Outer Shield

Outer Shield Material:

| Layer # | Outer Shield Trade Name | Type | Outer Shield Material | Coverage (%) |
|---------|-------------------------|-------|------------------------------|--------------|
| 1 | Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100.000 |
| 2 | | Braid | TC - Tinned Copper | 70.000 |

Outer Shield Drain Wire AWG:

| AWG | Stranding | Drain Wire | Conductor Material |
|-----|-----------|--------------------|--------------------|
| 26 | Solid | TC - Tinned Copper | |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|---|
| Industrial Grade PVC - Polyvinyl Chloride |

Overall Cable

Overall Nominal Diameter:

0.330 in.

Pair

Pair Color Code Chart:

| Number | Color |
|--------|------------------------------|
| 1 | White/Blue Stripe & Blue |
| 2 | White/Orange Stripe & Orange |
| 3 | White/Green Stripe & Green |
| 4 | White/Brown Stripe & Brown |

Mechanical Characteristics (Overall)

Installation Temperature Range: -25°C To +75°C

Operating Temperature Range: -40°C To +75°C

Bulk Cable Weight: 50 lbs/1000 ft.

Max. Recommended Pulling Tension: 75 lbs.

Min. Bend Radius/Minor Axis: 1.320 in.

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

CEC/UL Specification:

CMR

7957A Multi-Conductor - Category 5e DataTuff® 600V AWM Rated Twisted Pair Cable

| | |
|---------------------------------------|--|
| AWM Specification: | UL Style 21047 |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| Other Standards: | TIA 1005 |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004 |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |
| Other Specification: | NEMA WC-63.1 Category 5e, EtherNet/IP™ Compliant |

Applicable Patents:

| |
|--|
| Country |
| www.belden.com/p |

Flame Test

| | |
|------------------|--------------|
| UL Flame Test: | UL1666 Riser |
| CSA Flame Test: | FT4 |
| IEEE Flame Test: | 1202 |

Suitability

| | |
|------------------------|-----|
| Suitability - Outdoor: | Yes |
| Sunlight Resistance: | Yes |
| Oil Resistance: | Yes |

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Mutual Capacitance:

| |
|---------------------|
| Capacitance (pF/ft) |
| 15 |

| | |
|---|-----|
| Maximum Capacitance Unbalance (pF/100 m): | 150 |
|---|-----|

Nominal Velocity of Propagation:

| |
|--------|
| VP (%) |
| 70 |

Maximum Delay:

| |
|------------------|
| Delay (ns/100 m) |
| 538 @ 100MHz |

Max. Delay Skew:

| |
|-----------------------|
| Delay Skew (ns/100 m) |
| 45 |

Maximum Conductor DC Resistance:

| |
|------------------------|
| DCR @ 20°C (Ohm/100 m) |
| 9.38 |

Max. Operating Voltage - UL:

| Voltage | Description |
|-----------|---------------------------|
| 300 V RMS | |
| 600 V RMS | Appliance Wiring Material |

Maximum DCR Unbalanced:

| |
|--------------------------|
| DCR Unbalance @ 20°C (%) |
| 3 |

Electrical Characteristics-Premise (Overall)

Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) | Min. SRL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|---------------|
| 1 | 2.0 | 65.3 | 62.3 | 63.0 | 60.0 | 20.0 | 20.0 |
| 4 | 4.1 | 56.3 | 53.3 | 51.0 | 49.0 | 23.6 | 23.6 |
| 8 | 5.8 | 51.8 | 48.8 | 46.0 | 43.0 | 25.4 | 25.4 |
| 10 | 6.5 | 50.3 | 47.3 | 43.0 | 41.0 | 26.0 | 26.0 |

7957A Multi-Conductor - Category 5e DataTuff® 600V AWM Rated Twisted Pair Cable

| | | | | | | | |
|-------|------|------|------|------|------|------|------|
| 16 | 8.2 | 47.3 | 44.3 | 39.0 | 36.0 | 26.0 | 26.0 |
| 20 | 9.3 | 45.8 | 42.8 | 36.5 | 33.5 | 26.0 | 26.0 |
| 25 | 10.4 | 44.3 | 41.3 | 33.9 | 30.9 | 25.5 | 25.5 |
| 31.25 | 11.7 | 42.9 | 39.9 | 31.0 | 28.0 | 25.0 | 25.0 |
| 62.5 | 17.0 | 38.4 | 35.4 | 22.0 | 19.0 | 23.5 | 23.5 |
| 100 | 22.0 | 35.3 | 32.3 | 14.0 | 11.0 | 22.5 | 22.5 |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-------------|------------------------------|------------------|------------------|--------------------|
| 1 | 100 ± 15 | 95-110 | 63.8 | 60.8 |
| 4 | 100 ± 15 | 95-110 | 51.7 | 48.7 |
| 8 | 100 ± 15 | 95-107 | 45.7 | 42.7 |
| 10 | 100 ± 15 | 95-107 | 43.8 | 40.8 |
| 16 | 100 ± 15 | 95-107 | 39.7 | 36.7 |
| 20 | 100 ± 15 | 95-107 | 37.7 | 34.7 |
| 25 | 100 ± 15 | 95-107 | 35.8 | 32.8 |
| 31.25 | 100 ± 15 | 95-107 | 33.9 | 30.9 |
| 62.5 | 100 ± 15 | 95-107 | 27.8 | 24.8 |
| 100 | 100 ± 15 | 95-107 | 23.8 | 20.8 |

Notes (Overall)

Notes: EtherNet/IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vendor Association, Inc. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581. Not intended for 600 V electrical power delivery.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|----------|-------------|-------------|-------|--------------------|
| 7957A 0021000 | 1,000 FT | 54.000 LB | RED | C | 4 PR #24 PP SH PVC |
| 7957A 0061000 | 1,000 FT | 54.000 LB | BLUE, LIGHT | | 4 PR #24 PP SH PVC |
| 7957A 0081000 | 1,000 FT | 54.000 LB | GRAY | C | 4 PR #24 PP SH PVC |
| 7957A 0101000 | 1,000 FT | 54.000 LB | BLACK | | 4 PR #24 PP SH PVC |
| 7957A 0102000 | 2,000 FT | 106.000 LB | BLACK | | 4 PR #24 PP SH PVC |
| 7957A 1NH1000 | 1,000 FT | 54.000 LB | TEAL 1NH | | 4 PR #24 PP SH PVC |

Notes:
C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-30-2014

© 2016 Belden, Inc.
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru