

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0850037029

Status:

Active

Overview:

[din_41612](#)

Description:

2.54mm (.100") Pitch DIN 41612 C Style Male Header, Right Angle, Through Hole, 0.80µm (32µ") Selective Gold (Au) Plating, 96 Circuits, with Mounting Clips, No Flux Proof, Lead free, High Temperature version

Documents:	
Drawing (PDF)	RoHS Certificate of Compliance (PDF)
Product Specification PS-85003-0001 (PDF)	

Agency Certification	
CSA	LR19980
UL	E29179
General	
Product Family	Backplane Connectors
Series	85003
Application	Backplane
Comments	With Mounting Clips. No Flux Proof. 5.4mm(.213") First-Mate-Last- Break Contacts. 4.8mm(.189") Normal Contacts
Component Type	PCB Header
Overview	din_41612
Product Name	IEC 603-2/DIN 41612
Style	C
Physical	
Circuits (Loaded)	96
Circuits (maximum)	96
Circuits Detail	Standard Contacts at: A:a2-a31; B:b2-b31, C:c2-c31 . First-Mate-Last- VBreak Contacts at: X:c1,c32; Y:b1,b32; Z:a1,a32
Color - Resin	Natural
Durability (mating cycles max)	400
First Mate / Last Break	Yes
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Columns	16
Number of Pairs	Open Pin Field
Number of Rows	3
Orientation	Right Angle
PC Tail Length (in)	0.118 In
PC Tail Length (mm)	3.00 mm
PCB Locator	No
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.60 mm
Packaging Type	Carton
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com

For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.


Search Parts in this Series

85003Series

Pitch - Term. Interface (in)	0.100 In
Pitch - Term. Interface (mm)	2.54 mm
Plating min: Mating (μin)	32
Plating min: Mating (μm)	0.80
Plating min: Termination (μin)	200
Plating min: Termination (μm)	5
Polarized to PCB	Yes
Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-55°C to +125°C
Termination Interface: Style	Through Hole
Electrical	
Current - Maximum per Contact	1A
Data Rate	622.0 Mbps
Voltage - Maximum	250V AC (RMS)
Material Info	
Reference - Drawing Numbers	
Packaging Specification	PK-85003-001
Product Specification	PS-85003-0001
Sales Drawing	SD-85003-7029

This document was generated on 05/17/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION



A = 30 STANDARD CONTACTS L = 3
B = 30 STANDARD CONTACTS L = 3
C = 30 STANDARD CONTACTS L = 3
Z = 2 FMLB CONTACTS +0.6 L = 3
Y = 2 FMLB CONTACTS +0.6 L = 3
X = 2 FMLB CONTACTS +0.6 L = 3
S = 96 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/O = CONTACT AREA LEVEL 2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	YES
DIMENSIONS	E-85003-0006 SHT 1-2

X	G2/O	c1,32
Y	G2/O	b1,32
Z	G2/O	a1,32
C	G2/O	c2-31
B	G2/O	b2-31
A	G2/O	a2-31
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

SL. NO.	DESCRIPTION	CONTACT SYMBOL	PART NUMBER	QTY
1	HOUSING		36521-0001	1
2	TERMINAL	A	36527-0005	30
3	TERMINAL	B	36527-0005	30
4	TERMINAL	C	36527-0005	30
5	TERMINAL	Z	36527-0011	2
6	TERMINAL	Y	36527-0011	2
7	TERMINAL	Z	36527-0011	2
8	FIXING CLIP	- - -	36526-0002	2

EC NO. I 2004-XXXX DRAWN N.S. 09/09/03 CHK'd G.L. 09/09/03 APPR G.L. 09/09/03		QUALITY SYMBOLS MAJOR CRITICAL	GENERAL TOLERANCES* (UNLESS SPECIFIED)		SCALE	DESIGN UNITS ☒ mm ☐ INCH	THIRD ANGLE PROJECTION 	DIMENSIONS: ☐ mm ☐ INCH ☒ mm ONLY		SHT	REV
			4 PLACES	± 0.1	± 0.1	DRAWN BY & DATE N.S. 09/09/03		TITLE: 96 POS MALE CONNECTOR		REVISE ON CAD ONLY	
			3 PLACES	± 0.1	± 0.1	CHECKED BY & DATE G.L. 09/09/03		ACCORDING DIN 41612 STYLE C CONTACTS ARRANGEMENT (HIGH TEMP CONNECTOR)			
			2 PLACES	± 0.1	± 0.1	APPROVED BY & DATE G.L. 09/09/03		MOLEX INCORPORATED			
			1 PLACE	± 0.1	± 0.1	ANGULAR $\pm$	CAD FILENAME E-85003-7029.S01	MATERIAL NO. 85003-7029	DRAWING NO. E-85003-7029	SHEET NO. 1 OF 1	SIZE D
A		REV	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.						

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru