



H

I D

- NOTES:
- "B" MEASURED AT BASE.
  - STANDARD LENGTH: 6 ft. (1.83m).
  - SEE CURRENT CATALOG FOR PART NUMBER DESIGNATIONS FOR TYPE, COLOR, AND LENGTH.
  - TYPE "FS" SOLID WALL DUCT, IS AVAILABLE, WITH SAME DIMENSIONS, BUT WITHOUT SLOTS IN THE WALLS.
  - DUCT TYPES "FS" AND "F" TO BE USED WITH TYPE "C" COVER. (SEE DWG # 34518-17)
  - DIMENSIONS IN PARENTHESES ARE IN METRIC.
  - ADHESIVE BACKED DUCT AND/OR DUCT WITH OR WITHOUT HOLES IS ALSO AVAILABLE.

PART NO. SYSTEM CHANNEL EXAMPLE:

FS 1.5 x 2 •• 6 NM -A

1.5" WIDE

2" HIGH

COLOR

LENGTH (FT)

NO MOUNTING HOLES

ADHESIVE BACKED

WAS DPC\_PVC\_F\_US\_01 (2)

CAD FILENAME/LAYERS D34301BA\_PVC\_F\_US\_02A.prt

-	.....	---	---	J. REV'D "T" DIM'S AND TOL'S.	.....	---	---		
-	.....	---	---	I. REV'D EXAMPLE: ADDED LENGTH	.....	---	---		
-	.....	---	---	H. ADDED HOLES TO VIEW	.....	---	---		
-	.....	---	---	G. CHANGED NOTES 4 & 7.	.....	---	---		
4	8-3-01	JCST	JKG	F. CHANGED TITLE TO INCLUDE "FS"	.....	---	---		
4	8-3-01	JCST	JKG	E. ADDED DUCT SIZES: .75x1, .75x2, 2.5x3, AND 4x1.5.	34301-03	JKG	JKG		
3	01-24-97	JBA	CEF	D. REV'D EXAMPLE: ADDED S, NM & -A.	34301-03	CEF	CEF		
3	01-24-97	JBA	CEF	C. ADDED NOTE #7.	34301-03	CEF	CEF		
2	10-18-95	DW	CEF	B. REV'D "T" DIM'S AND TOL'S.	34301-03	CEF			
2	10-18-95	DW	CEF	B. REV'D "T" DIM'S AND TOL'S.	34301-03	CEF			
1	10-26-93	DW	CEF	A. ADDED FS6X4 DUCT SIZE.	34301-03	CEF			
1	10-26-93	DW	CEF	A. ADDED FS6X4 DUCT SIZE.	34301-03	CEF			
R	3/17/93	DW	BKR	RELEASED TO PRODUCTION.	34301-03	CEF			
REV	DATE	BY	CHK	DESCRIPTION	ECN	CHK	CUST	SUP	

PANDUIT CORP. TINLEY PARK, ILLINOIS

WIRING DUCT, TYPE "F" & "FS" CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ± (.XX) ± (.1213.1) ANGLES ±		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.	
DRAWN BY LDB	MAT'L:	SCALE NONE	
DATE 3/1/93	POLYVINYL CHLORIDE	DRAWING NO. 34301-03	DWG A
CHECKED BY BKR		Sht 1 of 2	SIZE

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.



NOMINAL DUCT SIZE (W X H)	B	D	D TOL	H REF	K	T	T TOL	R
.5 X .5	.69 (17.5)	.38 (9.7)	±.014 (.4)	.50 (12.7)	ON C/L	.050 (1.3)	±.008 (.2)	N/A
.5 X 1	"	.75 (19.1)	±.020 (.5)	1.00 (25.4)		"	±.010 (.3)	N/A
.75 X .75	.94 (23.8)	.56 (14.3)	"	.75 (19.1)		"	±.008 (.2)	N/A
> .75 X 1	"	N/A	N/A	1.00 (25.4)	N/A	"	"	N/A
> .75 X 1.5	"	1.20 (30.5)	±.020 (.5)	1.50 (38.1)	ON C/L	.070 (1.8)	±.010 (.3)	N/A
> .75 X 2	"	N/A	N/A	2.00 (50.8)	N/A	.080 (2.0)	±.008 (.2)	N/A
1 X 1	1.25 (31.8)	.75 (19.1)	±.020 (.5)	1.00 (25.4)	ON CENTERLINE	.055 (1.4)	±.010 (.3)	N/A
1 X 1.5	"	1.20 (30.5)	"	1.50 (38.1)		.070 (1.8)	±.008 (.2)	N/A
1 X 2	"	1.63 (41.4)	±.030 (.8)	2.00 (50.8)		.080 (2.0)	±.015 (.4)	.712 (18.1)
1 X 3	"	2.63 (66.8)	"	3.00 (76.2)		.095 (2.4)	±.012 (.3)	1.212 (30.8)
1 X 4	"	3.63 (92.2)	"	4.00 (101.6)		.105 (2.7)	±.019 (.5)	1.700 (43.2)
1.5 X 1	1.75 (44.5)	.75 (19.1)	±.020 (.5)	1.00 (25.4)		.060 (1.5)	±.010 (.3)	N/A
1.5 X 1.5	"	1.20 (30.5)	"	1.50 (38.1)		.070 (1.8)	±.012 (.3)	N/A
1.5 X 2	"	1.63 (41.4)	±.030 (.8)	2.00 (50.8)		.080 (2.0)	"	.712 (18.1)
1.5 X 3	"	2.63 (66.8)	"	3.00 (76.2)		.095 (2.4)	±.010 (.3)	1.212 (30.8)
1.5 X 4	"	3.63 (92.2)	"	4.00 (101.6)		.105 (2.7)	±.012 (.3)	1.700 (43.2)

N/A = NOT AVAILABLE

NOMINAL DUCT SIZE (W X H)	B	D	D TOL	H REF	K	T	T TOL	R
2 X 1	2.25 (57.2)	.75 (19.1)	±.020 (.5)	1.00 (25.4)	.50 (12.7)	.060 (1.5)	±.010 (.3)	N/A
2 X 1.5	"	1.20 (30.5)	"	1.50 (38.1)	"	.070 (1.8)	±.012 (.3)	N/A
2 X 2	"	1.63 (41.4)	±.030 (.8)	2.00 (50.8)	"	.080 (2.0)	"	.712 (18.1)
2 X 3	"	2.63 (66.8)	"	3.00 (76.2)	"	.095 (2.4)	±.010 (.3)	1.212 (30.8)
2 X 4	"	3.63 (92.0)	"	4.00 (101.6)	"	.105 (2.7)	±.017 (.4)	1.700 (43.2)
2 X 5	"	4.63 (117.6)	±.040 (1.0)	5.00 (127.0)	"	.111 (2.8)	"	2.233 (56.7)
> 2.5 X 3	2.75 (69.8)	N/A	N/A	3.00 (76.2)	N/A	.095 (2.4)	±.015 (.4)	N/A
3 X 1	3.25 (82.6)	.75 (19.1)	±.020 (.5)	1.00 (25.4)	1.00 (25.4)	.065 (1.7)	±.010 (.3)	N/A
3 X 2	"	1.63 (41.4)	±.030 (.8)	2.00 (50.8)	"	.080 (2.0)	"	.712 (18.1)
3 X 3	"	2.63 (66.8)	"	3.00 (76.2)	"	.100 (2.5)	±.015 (.4)	1.212 (30.8)
3 X 4	"	3.63 (92.2)	"	4.00 (101.6)	"	.105 (2.7)	"	1.700 (43.2)
3 X 5	"	4.63 (117.6)	±.040 (1.0)	5.00 (127.0)	"	.115 (2.9)	±.012 (.3)	2.233 (56.7)
> 4 X 1.5	4.25 (108.0)	N/A	N/A	1.50 (38.1)	N/A	.070 (1.8)	±.008 (.2)	N/A
4 X 2	"	1.63 (41.4)	±.030 (.8)	2.00 (50.8)	1.50 (38.1)	.080 (2.0)	"	.712 (18.1)
4 X 3	"	2.63 (66.8)	"	3.00 (76.2)	"	.095 (2.4)	±.010 (.3)	1.212 (30.8)
4 X 4	"	3.63 (92.2)	"	4.00 (101.6)	"	.105 (2.7)	±.012 (.3)	1.700 (43.2)
4 X 5	"	4.63 (117.6)	±.040 (1.0)	5.00 (127.0)	"	.110 (2.8)	±.018 (.5)	2.233 (56.7)
> 6 X 4	6.25 (158.8)	N/A	N/A	4.00 (101.6)	N/A	.110 (2.8)	±.010 (.3)	N/A

N/A = NOT AVAILABLE

> = AVAILABLE AS "FS" ONLY.



WAS DPC\_PVC\_F\_US\_01

DIMENSIONS IN PARENTHESIS ARE IN METRIC.

CAD FILENAME/LAYERS

D34301BA\_PVC\_F\_US\_02

REV	DATE	BY	CHK	DESCRIPTION	ECN	CHK	CUST	SUP
4	8-3-01	JCST	JKG	SEE SHEET 1 FOR REVISION NUMBERS	34301-03	JKG	JKG	
3	01-24-97	JBA	CEF	SEE SHEET 1 FOR REVISION NUMBERS	34301-03	CEF	CEF	
2	10-18-95	DW	CEF	SEE SHEET 1 FOR REVISION NUMBERS	34301-03	CEF		
1	10-27-93	DW	CEF	SEE SHEET 1 FOR REVISION NUMBERS	34301-03	CEF		
R	3/17/93	DW	BKR	SEE SHEET 1 FOR REVISION NUMBERS	34301-03	CEF		

<h1>PANDUIT</h1>		CORP. TINLEY PARK, ILLINOIS	
<h2>WIRING DUCT, TYPE "F" &amp; "FS" CUSTOMER DRAWING</h2>			
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ± (.XX) ± (.1213.1) ANGLES ±		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.	
DRAWN BY DW	MAT'L: POLYVINYL CHLORIDE	SCALE NONE	
GATE 3/1/93	CHECKED BY BKR	DRAWING NO. 34301-03 Sht 2 of 2	DWG A SIZE

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)