

Cable gland - G-ESS-M40-L66L-NTES-S - 1411081

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Nickel-plated brass, Application: Ex, External cable diameter 23.5 mm ... 32.2 mm, Shielding: No, Connecting thread: M40, Color: silver

Product Features



Key commercial data

Packing unit	1 pc
Minimum order quantity	2 pc
Weight per Piece (excluding packing)	190.0 GRM
Custom tariff number	74199990
Country of origin	United Kingdom

Technical data

Dimensions

Length	43 mm
Length without connecting thread	28 mm
Connecting thread diameter	40 mm
Wrench size, union nut	50 mm
Wrench size, support	50 mm
Hexagon angular dimension GRP	55 mm
Length of the connecting thread	15 mm
External cable diameter	23.5 mm ... 32.2 mm

Ambient conditions

Degree of protection	IP66 (in the case of feed-through holes, a sealing ring should also be installed in order to maintain the degree of protection (e.g., item 1411283).)
----------------------	---

Cable gland - G-ESS-M40-L66L-NTES-S - 1411081

Technical data

Ambient conditions

	IP67 (in the case of feed-through holes, a sealing ring should also be installed in order to maintain the degree of protection (e.g., item 1411283).)
	IP68 (in the case of feed-through holes, a sealing ring should also be installed in order to maintain the degree of protection (e.g., item 1411283).)
Ambient temperature (operation)	-60 °C ... 130 °C

General

Cable gland material	Nickel-plated brass
Seal material	Thermoplastic elastomers
O-ring material	Viton
Thread type on connection side	M40
Color	silver
Standards/specifications	EN 60079-0, -1, -7, -15, -31
	IEC 60079-0, -1, -7, -15, -31
	EN 50262
	BS 6121: Part 1:1989
	IEC 62444
ATEX	Sira 13ATEX1068X
	Sira 13ATEX4074X
	Ex II 2/3G, II 1D, Ex d IIC Gb, Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da, Ex IM2 Ex d I Mb, Ex e I Mb
IECEx	IECEx SIR 13.0023X
	Ex d IIC Gb, Ex e IIC Gb, Ex nR IIC Gc, Ex ta IIIC Da, Ex d I Mb, Ex e I Mb

Classifications

eCl@ss

eCl@ss 5.1	27149109
eCl@ss 6.0	27149109
eCl@ss 8.0	27149109


ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Drawings

Cable gland - G-ESS-M40-L66L-NTES-S - 1411081

Dimensional drawing



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru