

MICRO SURFACE MOUNT RELAY

1 POLE—25 A

(For Automotive Applications)

FTR-P6 Series

RoHS Compliant

■ FEATURES

- Surface mount relays for automotive applications
- Miniature size (67% of the volume of FTR-P3 relays)
- High contact capacity with proven contact material
- (100,000 operations, 14V, 25A achieved even with reduced size).
- Coil power savings (800mW nominal achieved with state-of-the-art magnetic analysis design)
- Semi-quiet relay (average acoustic noise level: 60dB distance 5cm).
- RoHS Compliant since production

■ ORDERING INFORMATION

[Example] FTR-P6 G N 012 WA **
 (a) (b) (c) (d) (e) (f)

(a)	Series Name	FTR-P6 : FTR-P6 Series	
(b)	Contact Arrangement	G	: 1 Form C
(c)	Contact Gap	N	: 0.25 mm Gap
(d)	Nominal Voltage	010	: 10 VDC
		012	: 12 VDC
(e)	Contact Material	WA	: Silver-tin oxide alloy
(f)	Special product specification	Symbol to specify special specification product	

Note: The part number on the relay cover does not include 'FTR'

Example: Ordering part number: FTR-P6GN010WA

 Stamped part number: P6GN010WA



■ TYPICAL APPLICATIONS

Power window
Door lock

Power seat
Sun roof

Wiper

■ SPECIFICATIONS

Item			Specification
Contact	Arrangement		1 FormC
	Material		Silver Oxide Tin-Indium
	Voltage drop (resistance)		Max. 100 mV (1A, 12VDC)
	Contact rating		DC 14V, 25A (motor locked)
	Maximum Carrying Current		25 A/ 1 hour (20° C, nominal voltage applied to coil)
	Maximum Inrush Current		35 A
	Contact Resistance		100mΩ maximum(at 6VDC, 1A after stabilization)
	Minimum Switching Load (reference)		1A, 6VDC
Coil	Coil Power Consumption		Approximately 0.8 W (at rated coil voltage)
	Operating Temperature Range		-40° C to +85° C (no frost)
	Storage Temperature Range		-40° C to +100° C (no frost)
	Operating Humidity		45 to 85%RH
Insulation	Initial resistance		100MΩ maximum at 500VDC
	Dielectric withstanding voltage		500 VAC
Time	Operate (at nominal voltage)		10 ms maximum
	Release (at nominal voltage)		5 ms maximum
Life	Mechanical		1x10 ⁷ operations minimum (with no load for contact)
	Electrical		1x10 ⁶ operations minimum (14VDC 25A locked motor)
Other	Vibration resistance	Misoperation	10-55Hz,1.5mm double amplitude, 10 to 100Hz (45m/s ²)
		Endurance	10 to 100Hz (45m/ s ²)
	Shock resistance	Misoperation	100 m/s ² (11ms)
		Endurance	1000 m/ s ² (11ms)
	Weight		Approximately 3.3 grams

■ COIL DATA CHART

Model	Nominal Coil Voltage	Coil Resistance (±10% at 20° C)	Must Operate Voltage	Coil Power at Nominal Voltage
FTR-P6GN010WA	10VDC	135	6.3VDC (at 20° C) 7.9VDC (at 85° C)	0.8W
FTR-P6GN012WA	12VDC	180	7.3VDC (at 20° C) 9.2VDC (at 85° C)	0.8W


■ CHARACTERISTIC DATA

1. LIFE TEST (EXAMPLES)


- Test item

Inrush current: 25A
16VDC
motor locked
Min. 100K operations
0.5 seconds ON
5.5 seconds OFF


- Test circuit




- Current wave form



- Change of operate and release voltage




(Measured at 6 VDC, 1A wet)




- Test item

Inrush current: 20A
16VDC
motor free
Min. 400K operations
1.5 seconds ON
2.0 seconds OFF


- Test circuit




- Change of operate and release voltage




(Measured at 6 VDC, 1A wet)




- Current wave form




2. COIL TEMPERATURE RISE




3. OPERATING COIL VOLTAGE RANGE






4. VIBRATION RESISTANCE CHARACTERISTIC



5. SHOCK RESISTANCE CHARACTERISTIC




■ REFERENCE DATA




■ DIMENSIONS


• Dimensions



• Schematic (bottom view)




• PCB mounting hole layout (top view)



■ REFERENCE DATA

• Reflow Temperature Profile



Note: Temperature profile shows temperature of PC board surface.

Unit: mm

Fujitsu Components International Headquarter Offices

Japan

Fujitsu Component Limited
Gotanda-Chuo Building
3-5, Higashigotanda 2-chome, Shinagawa-ku
Tokyo 141 8630, Japan
Tel: (81-3) 5449-7010
Fax: (81-3) 5449-2626
Email: promothq@fcl.fujitsu.com
Web: www.fcl.fujitsu.com

North and South America

Fujitsu Components America, Inc.
250 E. Caribbean Drive
Sunnyvale, CA 94089 U.S.A.
Tel: (1-408) 745-4900
Fax: (1-408) 745-4970
Email: components@us.fujitsu.com
Web: <http://www.fujitsu.com/us/services/edevices/components/>

Europe

Fujitsu Components Europe B.V.
Diamantlaan 25
2132 WV Hoofddorp
Netherlands
Tel: (31-23) 5560910
Fax: (31-23) 5560950
Email: info@fceu.fujitsu.com
Web: emea.fujitsu.com/components/

Asia Pacific

Fujitsu Components Asia Ltd.
102E Pasir Panjang Road
#01-01 Citilink Warehouse Complex
Singapore 118529
Tel: (65) 6375-8560
Fax: (65) 6273-3021
Email: fcal@fcal.fujitsu.com
Web: <http://www.fujitsu.com/sg/services/micro/components/>

©2008 Fujitsu Components America, Inc. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

Fujitsu Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products Fujitsu Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice.
Rev. January 4, 2008

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru