

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

1704801022

Status:

Active

Overview:

Impact™ Backplane Connector and Cable Assembly System

Description:

Impact™ 85 Ohm Plus 5 Pair Right Angle Daughtercard, Unguided, 12 Columns, 180 Circuits, Plated Through Hole Dimension 0.39mm, Lead Free

Documents:

3D Model

Drawing (PDF)

Product Specification PS-170540-999 (PDF)

Application Specification AS-76060-990 (PDF)

RoHS Certificate of Compliance (PDF)

|                                |                                                       |
|--------------------------------|-------------------------------------------------------|
| Agency Certification           |                                                       |
| UL                             | E29179                                                |
| General                        |                                                       |
| Product Family                 | Backplane Connectors                                  |
| Series                         | 170480                                                |
| Application                    | Conventional, Daughtercard                            |
| Component Type                 | PCB Receptacle                                        |
| Overview                       | Impact™ Backplane Connector and Cable Assembly System |
| Product Name                   | Impact™                                               |
| UPC                            | 884982487079                                          |
| Physical                       |                                                       |
| Circuits (Loaded)              | 180                                                   |
| Circuits (maximum)             | 180                                                   |
| Color - Resin                  | Gray                                                  |
| Durability (mating cycles max) | 200                                                   |
| First Mate / Last Break        | No                                                    |
| Flammability                   | 94V-0                                                 |
| Guide to Mating Part           | No                                                    |
| Keying to Mating Part          | None                                                  |
| Material - Metal               | High Performance Alloy (HPA)                          |
| Material - Plating Mating      | Gold                                                  |
| Material - Plating Termination | Tin                                                   |
| Material - Resin               | High Temperature Thermoplastic                        |
| Net Weight                     | 23.143/g                                              |
| Number of Columns              | 12                                                    |
| Number of Pairs                | 5                                                     |
| Number of Rows                 | 15                                                    |
| Orientation                    | Right Angle                                           |
| PC Tail Length                 | 1.20mm                                                |
| PCB Locator                    | No                                                    |
| PCB Retention                  | None                                                  |
| PCB Thickness - Recommended    | 1.00mm                                                |
| Packaging Type                 | Tray                                                  |
| Pitch - Mating Interface       | 1.35mm, 1.90mm                                        |
| Pitch - Termination Interface  | 1.35mm, 1.90mm                                        |
| Plating min - Mating           | 0.762µm                                               |
| Polarized to PCB               | No                                                    |
| Stackable                      | No                                                    |
| Surface Mount Compatible (SMC) | No                                                    |
| Temperature Range - Operating  | -55°C to +85°C                                        |
| Termination Interface: Style   | Through Hole - Compliant Pin                          |

Electrical



Series image - Reference only

EU ELV

Not Relevant

EU RoHS

China RoHS

Compliant

REACH SVHC

Contains SVHC(2014 December 17): No

Halogen-Free

Status

Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com

Please visit the Contact Us section for any non-product compliance questions.

China ROHS

Green Image

ELV

Not Relevant

Search Parts in this Series

170480 Series

Mates With

170475 Impact™ 85 Ohm Plus Vertical Header

Application Tooling | FAQ

Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document.

Global

| Description                                                    | Product #  |
|----------------------------------------------------------------|------------|
| Impact Daughter Card Extraction Tool                           | 0622024300 |
| Press-In Tool for Daughter Card 5-Pair by 12-Column Assemblies | 0622018735 |

|                                    |                 |
|------------------------------------|-----------------|
| Current - Maximum per Contact      | 0.75A           |
| Data Rate                          | 25.0 Gbps       |
| Impedance                          | 85#             |
| Shield Type                        | N/A             |
| Shielded                           | No              |
| Voltage - Maximum                  | 30V AC (RMS)/DC |
| <b>Solder Process Data</b>         |                 |
| Lead-freeProcess Capability        | N/A             |
| <b>Material Info</b>               |                 |
| <b>Reference - Drawing Numbers</b> |                 |
| Application Specification          | AS-76060-990    |
| Electrical Model Document          | EE-170480-0001  |
| Product Specification              | PS-170540-999   |
| S-Parameter Model                  | SP-170480-0003  |
| Sales Drawing                      | SD-170480-0001  |
| Symbol/Footprint Data              | SYM-170480-1022 |

This document was generated on 06/22/2015

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)