2N6344A, 2N6348A, 2N6349A

Preferred Device

Triacs

Silicon Bidirectional Thyristors

Designed primarily for full-wave AC control applications, such as light dimmers, motor controls, heating controls and power supplies; or wherever full-wave silicon gate controlled solid-state devices are needed. Triac type thyristors switch from a blocking to a conducting state for either polarity of applied anode voltage with positive or negative gate triggering.

Features


- Blocking Voltage to 800 V
- All Diffused and Glass Passivated Junctions for Greater Parameter Uniformity and Stability
- Small, Rugged, Thermowatt Construction for Low Thermal Resistance, High Heat Dissipation and Durability
- Gate Triggering Guaranteed in all Four Quadrants
- For 400 Hz Operation, Consult Factory
- 8.0 A Devices Available as 2N6344 thru 2N6349
- Pb−Free Packages are Available*

*For additional information on our Pb−Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


ON Semiconductor®

http://onsemi.com


TRIACS
12 AMPERES RMS
600 thru 800 VOLTS



MARKING DIAGRAM



TO−220AB
CASE 221A
STYLE 4



2N634xA = Device Code
x = 4, 8, or 9
A = Assembly Location
Y = Year
WW = Work Week
G = Pb−Free Package

PIN ASSIGNMENT	
1	Main Terminal 1
2	Main Terminal 2
3	Gate
4	Main Terminal 2

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 2 of this data sheet.

Preferred devices are recommended choices for future use and best overall value.

© Semiconductor Components Industries, LLC, 2006

MAXIMUM RATINGS

Characteristics	Symbol	Value	Unit
*Peak Repetitive Off−State Voltage (Note 1) (Gate Open, T_J = −40 to +110°C, Sine Wave 50 to 60 Hz, Gate Open) 2N6344A, 2N6348A 2N6349A	V_{DRM}, V_{RRM}	 600 800	V
*On−State RMS Current (Full Cycle Sine Wave 50 to 60 Hz) (T_C = +80°C) (T_C = +95°C)	$I_{T(RMS)}$	 12 6.0	A
*Peak Non−repetitive Surge Current (One Full Cycle, 60 Hz, T_C = +80°C) Preceded and followed by rated current	I_{TSM}	100	A
Circuit Fusing Consideration (t = 8.3 ms)	I^2t	59	A^2s
*Peak Gate Power (T_C = +80°C, Pulse Width = 2.0 μs)	P_{GM}	20	W
*Average Gate Power (T_C = +80°C, t = 8.3 ms)	$P_{G(AV)}$	0.5	W
*Peak Gate Current (Pulse Width = 2.0 μs; T_C = +80°C)	I_{GM}	2.0	A
*Peak Gate Voltage (Pulse Width = 2.0 μs; T_C = +80°C)	V_{GM}	±10	V
*Operating Junction Temperature Range	T_J	−40 to +125	°C
*Storage Temperature Range	T_{stg}	−40 to +150	°C

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

*Indicates JEDEC Registered Data.

1. V_{DRM} and V_{RRM} for all types can be applied on a continuous basis. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
*Thermal Resistance, Junction−to−Case	$R_{\theta JC}$	2.0	°C/W
Maximum Lead Temperature for Soldering Purposes 1/8″ from Case for 10 Seconds	T_L	260	°C

ORDERING INFORMATION

Device	Package	Shipping
2N6344A	TO−220AB	500 Units / Box
2N6344AG	TO−220AB (Pb−Free)	
2N6348A	TO−220AB	
2N6348AG	TO−220AB (Pb−Free)	
2N6349A	TO−220AB	
2N6349AG	TO−220AB (Pb−Free)	


ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted; Electricals apply in either direction)

Characteristic		Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
*Peak Repetitive Blocking Current (V_D = Rated V_{DRM}, V_{RRM}; Gate Open)	T_J = 25°C	I_{DRM}, I_{RRM}	–	–	10	μA
	T_J = 110°C		–	–	2.0	mA
ON CHARACTERISTICS						
*Peak On-State Voltage (I_{TM} = ±17 A Peak; Pulse Width = 1 to 2 ms, Duty Cycle ≤ 2%)		V_{TM}	–	1.3	1.75	V
Gate Trigger Current (Continuous dc) (V_D = 12 Vdc, R_L = 100 Ω)		I_{GT}				mA
Quadrant I: MT2(+), G(+)	All		–	6.0	50	
Quadrant II: MT2(+), G(−)	2N6348A and 2N6349A only		–	6.0	75	
Quadrant III: MT2(−), G(−)	All		–	10	50	
Quadrant IV: MT2(−), G(+)	2N6348A and 2N6349A only		–	25	75	
*MT2(+), G(+); MT2(−), G(−) T_C = −40°C			–	–	100	
*MT2(+), G(−); MT2(−), G(+) T_C = −40°C			–	–	125	
Gate Trigger Voltage (Continuous dc) (V_D = 12 Vdc, R_L = 100 Ω)		V_{GT}				V
Quadrant I: MT2(+), G(+)	All		–	0.9	2.0	
Quadrant II: MT2(+), G(−)	2N6348A and 2N6349A only		–	0.9	2.5	
Quadrant III: MT2(−), G(−)	All		–	1.1	2.0	
Quadrant IV: MT2(−), G(+)	2N6348A and 2N6349A only		–	1.4	2.5	
*MT2(+), G(+); MT2(−), G(−) T_C = −40°C			–	–	2.5	
*MT2(+), G(−); MT2(−), G(+) T_C = −40°C			–	–	3.0	
Gate Non−Trigger Voltage (V_D = Rated V_{DRM}, R_L = 10 k Ω, T_J = 110°C) *MT2(+), G(+); MT2(−), G(−); MT2(+), G(−); MT2(−), G(+)		V_{GD}	0.2	–	–	V
Holding Current (V_D = 12 Vdc, Gate Open) Initiating Current = ±200 mA	T_C = 25°C	I_H	–	6.0	40	mA
	*T_C = −40°C		–	–	75	
*Turn-On Time (V_D = Rated V_{DRM}, I_{TM} = 17 A, I_{GT} = 120 mA, Rise Time = 0.1 μs, Pulse Width = 2 μs)		t_{gt}	–	1.5	2.0	μs
DYNAMIC CHARACTERISTICS						
Critical Rate of Rise of Commutation Voltage (V_D = Rated V_{DRM}, I_{TM} = 17 A, Commutating di/dt = 6.1 A/ms, Gate Unenergized, T_C = 80°C)		dv/dt(c)	–	5.0	–	V/μs


*Indicates JEDEC Registered Data.

Voltage Current Characteristic of Triacs (Bidirectional Device)

Symbol	Parameter
V_{DRM}	Peak Repetitive Forward Off State Voltage
I_{DRM}	Peak Forward Blocking Current
V_{RRM}	Peak Repetitive Reverse Off State Voltage
I_{RRM}	Peak Reverse Blocking Current
V_{TM}	Maximum On State Voltage
I_H	Holding Current



Quadrant Definitions for a Triac



All polarities are referenced to MT1.
With in−phase signals (using standard AC lines) quadrants I and III are used.




Figure 1. RMS Current Derating




Figure 2. On−State Power Dissipation




Figure 3. Typical Gate Trigger Voltage




Figure 4. Typical Gate Trigger Current




Figure 5. On−State Characteristics




Figure 6. Typical Holding Current




Figure 7. Maximum Non−Repetitive Surge Current





Figure 8. Typical Thermal Response

PACKAGE DIMENSIONS

TO−220AB
CASE 221A−07
ISSUE AA



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.570	0.620	14.48	15.75
B	0.380	0.405	9.66	10.28
C	0.160	0.190	4.07	4.82
D	0.025	0.035	0.64	0.88
F	0.142	0.147	3.61	3.73
G	0.095	0.105	2.42	2.66
H	0.110	0.155	2.80	3.93
J	0.014	0.022	0.36	0.55
K	0.500	0.562	12.70	14.27
L	0.045	0.060	1.15	1.52
N	0.190	0.210	4.83	5.33
Q	0.100	0.120	2.54	3.04
R	0.080	0.110	2.04	2.79
S	0.045	0.055	1.15	1.39
T	0.235	0.255	5.97	6.47
U	0.000	0.050	0.00	1.27
V	0.045	---	1.15	---
Z	---	0.080	---	2.04

STYLE 4:
PIN 1. MAIN TERMINAL 1
2. MAIN TERMINAL 2
3. GATE
4. MAIN TERMINAL 2

ON Semiconductor and ON are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. “Typical” parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including “Typicals” must be validated for each customer application by customer’s technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5773−3850

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

2N6344A/D

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru