



SPECIFICATION:

- CONTACT RESISTANCE: 20 MILIOHMS MAX
- DIELECTRIC WITHSTANDING VOLTAGE: 250 VAC MIN
- INSULATION RESISTANCE @ 500 VDC: 2,000 MEGAOHMS MIN
- MAX WORKING VOLTAGE: 250 VAC; 140VDC
- CURRENT CARRY @ WORKING VOLTAGE: 4 AMPS
- INSERT/WITHDRAWAL FORCE: TYPICAL 2.5/2 LBS
- TEMPERATURE RANGE: -20°C TO 85°C (OPERATING)
- THERMAL SHOCK: MIL-STD-202, METHOD 107G
- VIBRATION: MIL-STD-202, METHOD 201
- LIFE: 5,000 CYCLES
- CABLE SIZE: .250 DIA MAX
- THESE PRODUCTS ARE RoHS COMPLIANT.

MATERIAL:

- TIP ROD: COPPER ALLOY, TIN OR GOLD PLATED
- RING: COPPER ALLOY, TIN OR GOLD PLATED
- SLEEVE: COPPER ALLOY, TIN OR GOLD PLATED
- HANDLE: COPPER ALLOY, NICKEL PLATED OR BLACK EPOXY PAINT
- CABLE CLAMP: C.R.S., TIN PLATED
- TUBULAR INSULATOR: CLEAR PLASTIC

"A" DIA CABLE HOLE
SEE PART NUMBER TABLE

PART NUMBER	HANDLE	PLUG	"A"
35HDLNN	NICKEL	TIN	.29 DIA
35HDLBN	BLACK	TIN	.29 DIA
35HDLNAU	NICKEL	GOLD	.29 DIA
35HDLBAU	BLACK	GOLD	.29 DIA
35HDLNNS	NICKEL	TIN	.18 DIA
35HDLBNS	BLACK	TIN	.18 DIA
35HDLNAUS	NICKEL	GOLD	.18 DIA
35HDLBAUS	BLACK	GOLD	.18 DIA

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.							
					UNLESS OTHERWISE SPECIFIED	SIZE *	WIDTH *	MULT *	LBS/M *	TEMPER *		
0E	UPDATE	01/05/10	ZS	SRC	1. ALL DIMENSIONS IN INCHES - TWO PLACE DECIMALS ±0.02 - THREE PLACE DECIMALS ±0.005	FINISH *			MATERIAL *			
0D	UPDATE	10/10/08	ZS	SRC		SPEC No. *			SPEC No. *			
0C	STEP LOCK NUT	10/10/08	ZS	SRC		FIRST USED ON *		SCALE 2:1				
0B	UPDATE	04/29/08	ZS	SRC		DATE DRAWN	BY	CHKD	APVD			
0A	RELEASE	12/20/07	ZS	SRC		12/20/07	ZS	12/20/07	12/20/07			SHEET 1 OF 1
REV	ECO NUMBER	DATE	BY	APVD	DO NOT SCALE DRAWING					NAME	PART No.	REV
REVISIONS										3,5 MM STEREO PLUG, RoHS	35HD SERIES	0E

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru