Part No.	AL-513YD	Diff No.
5 mm	Round	Type: LED Lamps

Package Dimension：



Notes:
1. All dimensions are in millimeter.
2.An epoxy meniscus may extend about.
1. 5mm(0.059") down to the lead
3.Tolerances unless Dimension ±0.25mm

■ Features：

- Choice of various viewing angles.
- Available on Tape and Reel.
- Reliable and robust.

■ Descriptions：

- The series is specially designed for application requiring higher brightness.
- The LED lamps are available with different colors, intensity, epoxy colors etc.

■ Applications：

- TV set
- Monitor
- Telephone

Part No.	AL-513YD	Diff No.
5 mm	Round	Type: LED Lamps

PART NO.	Chip		Lens Color
	Material	Emitted Color	
AL-513YD	GaAsP/GaP	Yellow	Yellow Diffused

■ Absolute Maximum Ratings at Ta=25℃

Parameter	Symbol	Rating	Unit
Forward Current	I_F	20	mA
Operating Temperature	Topr	-40 to +85	℃
Storage Temperature	Tstg	-40 to +100	℃
Soldering Temperature	Tsol	260 ±5	℃
Electrostatic Discharge	ESD	1000	V
Power Dissipation	P_D	100	mW
Peak Forward Current (Duty 1/10@1KHz)	I_F (Peak)	160	mA
Reverse Voltage	V_R	5	V

■ Electronic Optical Characteristics：

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	I_V	／	8	／	mcd	I_F=20mA
Viewing Angle	2θ1/2	／	50	／	deg	I_F=20mA
Peak Wavelength	λ p	／	590	／	nm	I_F=20mA
Dominant Wavelength	λ d	／	585	／	nm	I_F=20mA
Spectrum Radiation Bandwidth	△λ	／	35	／	nm	I_F=20mA
Forward Voltage	V_F	／	2.1	2.6	V	I_F=20mA

Part No.	AL-513YD	Diff No.
5 mm	Round	Type: LED Lamps

■ Reliability test items and conditions：

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP：260℃ ± 5℃	5 SEC	76 PCS	0/1
2	Temperature Cycle	H：+85℃ 30min ∫ 5min L：-55℃ 30min	50 CYCLES	76 PCS	0/1
3	Thermal Shock	H：+100℃ 5min ∫ 10set L：-10℃ 5min	50 CYCLES	76 PCS	0/1
4	High Temperature Storage	TEMP：100℃	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP：-55℃	1000 HRS	76 PCS	0/1
6	DC Operating Life	TEMP：25℃ I_F=20mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85℃ / 85%RH	1000 HRS	76 PCS	0/1

Part No.	AL-513YD	Diff No.
5 mm	Round	Type: LED Lamps

◆ **TYPICAL ELECTRICAL-OPTICAL CHARACTERISTICS CURVES**





RELATIVE INTENSITY VS. WAVELENGTH(λp)

(1) GaAsP/GaAs 655nm/Red
(2) GaP 568nm/ Yellow Green
(3) GaAsP/GaP 585nm/Yellow
(4) GaAsP/GaP 635nm/Orange & Hi-Eff Red
(5) GaP 700nm/Bright Red
(6) GaAlAs/GaAs 660nm/Super Red
(8) GaAsP/GaP 610nm/Super Red
(9)- GaAlAs 880nm
(10)-GaAs/GaAs&GaAlAs/GaAs 940nm
(A)- GaN 430nm/Blue
(B)- InGaN 470nm/Blue
(C)- InGaN 502nm/Ultra Green
(D)- InGaN 523nm/Ultra Green

Part No.	AL-513YD	Diff No.
5 mm	Round	Type: LED Lamps

◆ CHARACTERISTICS DIAGRAMS

FORWARD CURRENT VS. FORWARD VOLTAGE



RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT



FORWARD CURRENT VS. AMBIENT TEMPERATURE





LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru