OMRON

Multi voltage photoelectric sensor in plastic housing with timer function

E3JM

The square sized E3JM family provides 12 to 240 VDC and 24 to 240 VAC power supply voltage, an enhanced sensing distance and a

timer function.

- 12 to 240 VDC and 24 to 240 VAC supply voltage
- Relay or solid state relay output
- Timer function



Ordering Information

Sensor type	Sensing	Connec-	Timer function	Order code		
	distance	tion		Relay output	DC SSR output	
		method			minus common	plus common
Through-beam	10 m	Terminal block	-	E3JM-10M4-G-N	E3JM-10S4-G-N	E3JM-10R4-G-N
		(with PG 13.5)	ON or OFF delay 0.1 s to 5 s	E3JM-10M4T-G-N	E3JM-10S4T-G-N	E3JM-10R4T-G-N
Retro-reflective with M.S.R.	4 m		-	E3JM-R4M4-G	E3JM-R4S4-G	E3JM-R4R4-G
			ON or OFF delay 0.1 s to 5 s	E3JM-R4M4T-G	E3JM-R4S4T-G	E3JM-R4R4T-G
Diffuse-reflective	700 mm (adjustable)		-	E3JM-DS70M4-G	E3JM-DS70S4-G	E3JM-DS70R4-G
			ON or OFF delay 0.1 s to 5 s	E3JM-DS70M4T-G	E3JM-DS70S4T-G	E3JM-DS70R4T-G

Accessories

Slit

Slit width	Sensing distance	Minimum sensing object (typical)	Model	Quantity	Remarks
1 mm × 20 mm	1.2 m	1 mm dia.	E39-S39	1 Slit each for Emitter and Receiver (2 Slits total)	(Seal-type long slit) Can be used with the Through-beam Model E3JM-10□4(T).

Reflectors

Name	Sensing distance (typical)	Model	Quantity	Remarks
Reflectors	4 m (rated value)	E39-R1	1	Provided with the E3JM-R4□4(T).
Small Reflectors	3.5 m	E39-R3	1	
Tape Reflectors	1 m (200 mm) (See note 2.)	E39-RS1	1	
	1.6 m (200 mm) (See note	E39-RS2	1	
	2.)			
	2 m (200 mm) (See note 2.)	E39-RS3	1	

Note 1. For the complete overview of available reflectors please refer to www.industrial.omron.eu or to the accessory datasheet E26E.2. Values in brackets are the minimum required distance between the Sensor and Reflector.

Mounting Bracket

Appearance	Model	Quantity	Remarks
A CONTRACTOR	E39-L53	1	Provided with the E3JM

Note: If a Through-beam Model is used, order two Mounting Brackets for the Emitter and Receiver respectively.

Specifications

Ratings/Characteristics

Item		Through-beam		Retro-reflective with M.S.R.		Diffuse-reflective		
		E3JM-10□4	E3JM-10□4T	E3JM-R4□4	E3JM-R4□4T	E3JM-DS7004	E3JM- DS70□4T	
Sensing distance		10 m	10 m		4 m (When using E39-R1)		White paper (200 × 200 mm): 700 mm	
Standard sensing o	bject	Opaque: 14.8-m	m dia. min.	Opaque: 75-mn	n dia.min.			
Differential travel						20% max. of sensing distance		
Directional angle		Both Emitter and 20°	d Receiver 3° to	1° to 5°				
Light source (wave	length)	Infrared LED (95	50 nm)	Red LED (660 r	nm)	Infrared LED (9	Infrared LED (950 nm)	
Power supply volta	ge	12 to 240 VDC± 24 to 240 VAC±	10%, ripple (p-p) 10%, 50/60 Hz	: 10% max.				
Power consumption	า	3 W max.		2 W max.				
Control output		Relay output (M 5 VDC, 10 mA n DC SSR output Light-ON/Dark-0	Models): SPDT 2 nin. (S, R Models):48 DN selectable	250 VAC, 3 A ma 3 VDC, 100 mA m	ax. (cosφ = 1) nax. (residual volt	age: 2 V max.)	ge: 2 V max.)	
Life expectancy	Mechanical	50,000,000 time	s min. (switching	frequency: 18,0	00 times/h)			
	Electrical	100,000 times n	nin. (switching fre	equency: 1,800 til	mes/h)			
Response time	Relay out- put	Operation or res	et: 30 ms max.					
	DC SSR output	Operation or res	et: 5 ms max.					
Sensitivity adjustme	ent					One-turn adjuster		
Timer function (See	e note.)	ON-delay/OFF-o Delay time: 0.1	delay/One-shot d to 5 s (adjustable	elay switch selec), only for E3JM-	table ⊡□□4T			
Ambient illumination side)	n (Receiver	Incandescent la	mp: 3,000 <i>l</i> x max	κ.				
Ambient temperatu	re	Operating:-25°0 Storage:-30°C t	perating:–25°C to 55°C (with no icing or condensation)					
Ambient humidity		Operating:45% to Storage:35% to	to 85% (with no c 95% (with no cor	condensation)	·			
Insulation resistance	e	20 MΩ min. at 5	00 VDC between	current-carrying	parts and case			
Dielectric strength		2,000 VAC, 50/6	30 Hz for 1 min. b	etween current-	carrying parts and	d case		
Vibration resis-	Destruction	10 to 55 Hz, 1.5	-mm double amp	litude for 2 hours	s each in X, Y, an	d Z directions		
tance	Malfunction	10 to 55 Hz, 1.5	-mm double amp	litude for 2 hours	s each in X, Y, an	d Z directions		
Shock resistance	Destruction	500 m/s ² 3 time	s each in X, Y, ar	nd Z directions				
	Malfunction	100 m/s ² 3 time	s each in X, Y, ar	nd Z directions				
Degree of protectio	n	IEC 60529: IP66	3					
Connection method	1	Terminal block					T	
Indicator		Light indicator (red), power in- dicator (red)	Operation indi- cator (red), power indicator (red)	Light indicator (red)	Operation indi- cator (red)	Light indicator (red)	Operation indi- cator (red)	
Weight (packed sta	te)	Approx. 270 g	Approx. 160 g Approx. 160		Approx. 160 g			
Material	Case	ABS						
	Lens	Methacrylic resi	n					
	Cover	Polycarbonate						
	Mounting Bracket	Iron						
Accessories		Mounting Brack reflector (E39-R	ounting Bracket (with screw), nut, terminal protection cover, one set of cable connection nuts, flector (E39-R1: only for retro-reflective models), instruction manual				ection nuts,	

Note: The timer cannot be disabled for Models with timer functions (E3JM-0.4T).

OMRON

Engineering Data

Parallel Operating Range (Typical) Through-beam



Operating Range (Typical) Diffuse-reflective

E3JM-DS70 4(T)



Excess Gain Ratio vs. Set Distance

(Typical)

Retro-reflective

E3JM-R4□4(T) (When Using E39-R1)



Parallel Operating Range (Typical) Through-beam

E3JM-10 \Box 4(T) with E39-S39 (Slit)



Size of Sensing Object vs. Sensing Distance Diffuse-reflective

E3JM-DS70
4(T)



Excess Gain Ratio vs. Set Distance

(Typical)

Retro-reflective

E3JM-R4 4(T) (When Using E39-R3)



Parallel Operating Range (Typical) Retro-reflective E3JM-R4□4(T) (When Using E39-R1)





(Typical) Through-beam E3JM-10□4(T)



Excess Gain Ratio vs. Set Distance (Typical) Diffuse-reflective

E3JM-DS70 4(T)



Operation

Output Circuit

Relay Output Models E3JM-□M4(T)



DC SSR Output Models E3JM-□S4(T)





Timing Charts

Models without Timer



Models with Timer

/ Warning

This product is not designed or rated for ensuring safety of persons. Do not use it for such purposes.

Connections

Through-beam Models



Retro-reflective Models



Diffuse-reflective Models



Precautions for Correct Use Switch Configuration

Models without Timer



Adjustment

Through-beam Models

For a E3JM with the timer function, the indicator will be lit when incident light is received while the mode is switched to Light-ON, and the indicator will be lit when light is interrupted while the mode is switched to Dark-ON.

Move the Emitter and Receiver horizontally and vertically, and locate them to the center of the range in which the Receiver indicator is lit.

Retro-reflective Models

The indicator of the Retro-reflective Model with the timer function is lit in the same way as for the Through-beam Model.

As with the Through-beam Model, adjust the Reflector and Sensor. Since the directional angle of the E3JM Retro-reflective Model is 1 to 5 degrees, pay careful attention when adjusting the Sensor.

Diffuse-reflective Models

The indicator of the Diffuse-reflective Model with the timer function is lit in the same way as for the Through-beam Model.

Sensing object









Sensitivity

- If a sensing object is present as shown above, turn the sensitivity adjuster clockwise to increase the sensitivity. Point (A) is where the indicator is lit.
- 2. Remove the sensing object and turn the adjuster clockwise. Point (B) is where the indicator is lit by background objects.
- **3.** Turn the adjuster counterclockwise to decrease the sensitivity, starting from the point (B). Point (C) is where the indicator is lit.
- **4.** The center point between the point (A) and point (C) is the optimum position. If the indicator is not lit by the background object at the maximum sensitivity, set to the center point between the point (A) and the maximum sensitivity.
- Note: The sensitivity adjuster may be damaged if an excessive force is applied.

Models with Timer



Switch Selection

Models without Timer

Models with Timer



Connecting and Wiring

Recommended outer diameter of cables is from 6 to 8 dia. Be sure to firmly tighten the cover in order to maintain waterproof and dustproof properties.

Cable End Treatment

Adjust the four wires to the same length when the Ta output is to be used only. If both the Ta and Tb outputs are to be used, treat them as shown in the following diagram.



Recommended Crimp Terminal Dimensions (Unit: mm)



Note: Use terminals with insulation tube (recommended crimp terminal: 1.25 to 3.5).

Terminal Protection Cover (Accessory)

The terminal protection cover is designed to improve safety by maintaining the sensitivity properties of the product and by preventing any contact with charged sections while it is being operated with the mode set to the timer mode. Mount the product as shown in the following diagram (mount the Through-beam Model on the Receiver side).



Output Relay Contact

If a load, such as contactor or valve is used that may produce arc when it is turned OFF, the NC (or NO) side may turn ON before the NO (or NC) side is turned OFF. When using both the NC and NO outputs, use an arc killer.

Connecting and Wiring DC SSR Output Models

When using the DC SSR output model, the total of the load current for the Light-ON output (NO) and that for the Dark-ON (NC) should be 100 mA max. If the total exceeds 100 mA, the load short-circuit protection function will be activated (this function will be reset when the power of the Photoelectric Sensor is turned OFF).

Ambient Conditions (Installation Area)

- The E3JM will malfunction if installed in the following places.
- Places where the E3JM is exposed to a dusty environment.
- Places where corrosive gases are produced.



• Places where the E3JM is directly exposed to water, oil, or chemicals.



Dimensions

Note 1. The operating mode switch and timer mode switch are located inside the cover.
 All units are in millimeters unless otherwise indicated.



Reflectors

E39-R1 (Provided with Retro-reflective Models)

Materials: Reflective side: PMMA (Acrylic resin) Back side: ABS resin



Seal-type Long Slit E39-S39



++ + 1±0.1	- ^{1.}	1
	-	-
	-	-

Small Reflector (Order Separately) E39-R3

Materials: Reflective side: PMMA (Acrylic resin) Back side: ABS resin





Tape Reflectors (Order Separately) E39-RS1



Materials: Acrylic

E39-RS2





Materials: Acrylic

0.5

E39-RS3



Materials: Acrylic

WARRANTY

OMRON's exclusive warranty is that the products are free from defects in materials and workmanship for a period of one year (or other period if specified) from date of sale by OMRON.

OMRON MAKES NO WARRANTY OR REPRESENTATION, EX-PRESS OR IMPLIED, REGARDING NON-INFRINGEMENT, MER-CHANTABILITY, OR FITNESS FOR PARTICULAR PURPOSE OF THE PRODUCTS. ANY BUYER OR USER ACKNOWLEDGES THAT THE BUYER OR USER ALONE HAS DETERMINED THAT THE PRODUCTS WILL SUITABLY MEET THE REQUIREMENTS OF THEIR INTENDED USE. OMRON DISCLAIMS ALL OTHER WAR-RANTIES, EXPRESS OR IMPLIED.

LIMITATIONS OF LIABILITY

OMRON SHALL NOT BE RESPONSIBLE FOR SPECIAL, INDI-RECT, OR CONSEQUENTIAL DAMAGES, LOSS OF PROFITS OR COMMERCIAL LOSS IN ANY WAY CONNECTED WITH THE PRODUCTS, WHETHER SUCH CLAIM IS BASED ON CONTRACT, WARRANTY, NEGLIGENCE, OR STRICT LIABILITY.

In no event shall responsibility of OMRON for any act exceed the individual price of the product on which liability is asserted.

IN NO EVENT SHALL OMRON BE RESPONSIBLE FOR WARRAN-TY, REPAIR, OR OTHER CLAIMS REGARDING THE PRODUCTS UNLESS OMRON'S ANALYSIS CONFIRMS THAT THE PROD-UCTS WERE PROPERLY HANDLED, STORED, INSTALLED, AND MAINTAINED AND NOT SUBJECT TO CONTAMINATION, ABUSE, MISUSE, OR INAPPROPRIATE MODIFICATION OR REPAIR.

SUITABILITY FOR USE

THE PRODUCTS CONTAINED IN THIS DOCUMENT ARE NOT SAFETY RATED. THEY ARE NOT DESIGNED OR RATED FOR EN-SURING SAFETY OF PERSONS, AND SHOULD NOT BE RELIED UPON AS A SAFETY COMPONENT OR PROTECTIVE DEVICE FOR SUCH PURPOSES. Please refer to separate catalogs for OM-RON's safety rated products.

OMRON shall not be responsible for conformity with any standards, codes, or regulations that apply to the combination of products in the

customer's application or use of the product.

At the customer's request, OMRON will provide applicable third party certification documents identifying ratings and limitations of use that apply to the products. This information by itself is not sufficient for a complete determination of the suitability of the products in combination with the end product, machine, system, or other application or use.

The following are some examples of applications for which particular attention must be given. This is not intended to be an exhaustive list of all possible uses of the products, nor is it intended to imply that the uses listed may be suitable for the products:

- Outdoor use, uses involving potential chemical contamination or electrical interference, or conditions or uses not described in this document.
- Nuclear energy control systems, combustion systems, railroad systems, aviation systems, medical equipment, amusement machines, vehicles, safety equipment, and installations subject to separate industry or government regulations.
- Systems, machines, and equipment that could present a risk to life or property.

Please know and observe all prohibitions of use applicable to the products.

NEVER USE THE PRODUCTS FOR AN APPLICATION INVOLVING SERIOUS RISK TO LIFE OR PROPERTY WITHOUT ENSURING THAT THE SYSTEM AS A WHOLE HAS BEEN DESIGNED TO ADDRESS THE RISKS, AND THAT THE OMRON PRODUCT IS PROPERLY RATED AND INSTALLED FOR THE INTENDED USE WITHIN THE OVERALL EQUIPMENT OR SYSTEM.

PERFORMANCE DATA

Performance data given in this document is provided as a guide for the user in determining suitability and does not constitute a warranty. It may represent the result of OMRON's test conditions, and the users must correlate it to actual application requirements. Actual performance is subject to the OMRON Warranty and Limitations of Liability.

CHANGE IN SPECIFICATIONS

Product specifications and accessories may be changed at any time based on improvements and other reasons.

It is our practice to change model numbers when published ratings or features are changed, or when significant construction changes are made. However, some specifications of the product may be changed without any notice. When in doubt, special model numbers may be assigned to fix or establish key specifications for your application on your request. Please consult with your OMRON representative at any time to confirm actual specifications of purchased products.

DIMENSIONS AND WEIGHTS

Dimensions and weights are nominal and are not to be used for manufacturing purposes, even when tolerances are shown.

ERRORS AND OMISSIONS

The information in this document has been carefully checked and is believed to be accurate; however, no responsibility is assumed for clerical, typographical, or proofreading errors, or omissions.

PROGRAMMABLE PRODUCTS

OMRON shall not be responsible for the user's programming of a programmable product, or any consequence thereof.

Cat. No. E203-E2-05

In the interest of product improvement, specifications are subject to change without notice.

OMRON EUROPE B.V.

Wegalaan 67-69, NL-2132 JD, Hoofddorp, The Netherlands Phone: +31 23 568 13 00 Fax: +31 23 568 13 88 www.industrial.omron.eu

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Omron:

E3JM-DS70M4-G E3JM-10S4-US OMS E3JM-R4R4T-G OMS E3JM-R4R4T-G-33 E3JM-10S4-US E3JM-R4R4T-G E3JM-DS70M4T-G E3JM-R4M4-G E3JM-R4M4T-G E3JM-DS70R4T-US



ООО "ЛайфЭлектроникс"

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru

www.lifeelectronics.ru