


# A Dimensions: [mm]









# **D Electrical Properties:**

Properties	Test conditions		Value	Unit	Tol.
Impedance @ 25 MHz 1 turn	25 MHz	Z	26	Ω	±25%
Impedance @ 100 MHz 1 turn	100 MHz	Z	66	Ω	±25%

# **E** General information:

Scale - 1:1

Storage Temperature (before assembly):  $-20^{\circ}$ C to  $+60^{\circ}$ C Operating Temperature:  $-25^{\circ}$ C to  $+125^{\circ}$ C Test conditions of Electrical Properties:  $20^{\circ}$ C, 33% RH if not specified differently

Scale - 1:1

For max. 30 poles at 1,27mm grid

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions 4.2 2012-11-28 SSt SSt Max-Eyth-Str. 1 4.1 2012-10-18 74638 Waldenburg Germany 4.0 2012-09-18 SSt SMu Tel. +49 (0) 79 42 945 - 0 www.we-online.com 3.0 2006-10-12 SMu eiSos@we-online.com DATE CHECKED

Projection

DESCRIPTION

# **WE-FLAT Flat Ferrite Core**

Order.- No.

7427214



SIZE A4


This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard and reliability standard and reliability standard and reliability standard is especially required or where a failure of the products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.



# **D2 General Properties:**

	Properties		Value	Unit	Tol.
Cable diameter	Number of poles		30		
Cable diameter	grid		1.27	mm	
Ferrite core	Material		3 W 800		
Ferrite core	Initial permeability	$\mu_{i}$	800		typ.
Ferrite core	Curie temperature	Т <sub>С</sub>	140	°C	typ.
Test cable	Applicable cable		AWG26		
Test cable	Applicable cable length		220	mm	

# **F Typical Impedance Characteristics:**



				Projection ————————————————————————————————————		DESCRIPTION  WE-FLAT Flat	Ferrite Core	
4.2	2012-11-28	SSt	SSt	Würth Elektronik eiSos GmbH EMC & Inductive Solutions	1 & Co. KG			
4.1	2012-10-18	SSt	SMu	Max-Eyth-Str. 1 74638 Waldenburg		Order No.	COMPLIANT	SIZE
4.0	2012-09-18	SSt	SMu	Germany Tel. +49 (0) 79 42 945 - 0		7407044	ROHS&REACH	SIZL
3.0	2006-10-12	SMu	-	www.we-online.com eiSos@we-online.com		7427214	I DATH ELEKTRONIK	A4
REV	DATE	BY	CHECKED	CIOUS SWC OTHING.COM				-

## **I Cautions and Warnings:**

# The following conditions apply to all goods within the product series of WE-FLAT of Würth Elektronik eiSos GmbH & Co. KG:

### General:

All recommendations according to the general technical specifications of the data-sheet have to be complied with.

The disposal and operation of the product within ambient conditions which probably alloy or harm the component surface has to be avoided.

If the product is molded in costumer applications, the molding material might shrink during and after hardening. Accordingly to this the product is exposed to the pressure of the molding material with the effect that the ferrite body is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endanger to be affected. After the molding material is cured, the ferrite body of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply for customer specific products.

Cleaning agents that are used to clean the application might damage or change the characteristics of the component or body.

The usage in acidly as well as salted environment can be the reason for oxide (rust) at the surface of the ferrite body, damage or changes at the characteristics of the material. The acidly or salted environment could have a negative effect on the long turn function of the product.

Direct mechanical impact to the product shall be prevented as the ferrite material of the ferrite body could flake or in the worst case it could break

## Product specific:

Follow all instructions mentioned in the datasheet, especially:

 Violation of the technical product specifications such as exceeding the maximal outer diameter of the cable will result in the loss of warranty.



				Projection ,		DESCRIPTION				
				<del></del>						
				7 )		WE-FLAT Flat	Ferrite Core			
4.2	2012-11-28	SSt	SSt	Wirth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com						
4.1	2012-10-18	SSt	SMu			Order No.	COMPLIANT			
4.0	2012-09-18	SSt	SMu			= 40=04 A	ROHS&REACH	OIZL		
3.0	2006-10-12	SMu	-			7427214	WORTH ELEKTRONIK	A4		
REV	DATE	BY	CHECKED	0.000@110 0.111110.00111						

## **J Important Notes:**

# The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

## 1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

### 2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications.

In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

### 3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

## 4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

### 5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.



## 6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered.

The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

### 7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG.

Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

#### 8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

				Projection		DESCRIPTION			
						WE-FLAT Flat	Forrita Cora		
				Würth Elektronik eiSos Gmbl EMC & Inductive Solutions	H & Co. KG	, WE-ILAI IIat	Territe oute		
4.2	2012-11-28	SSt	SSt	Max-Eyth-Str. 1					
4.1	2012-10-18	SSt	SMu	74638 Waldenburg		Order No.	COMPLIANT	SI7F	
4.0	2012-09-18	SSt	SMu	Germany Tel. +49 (0) 79 42 945 - 0		7407044	ROHS&REACH	OIZE	
3.0	2006-10-12	SMu	-	www.we-online.com eiSos@we-online.com		7427214 WÜRTH ELEKTRONIK			
REV	DATE	BY	CHECKED	CIOCOSSWC OTHITIC.COTT					



OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 P/C 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

## Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru