


## Features

- Fast Switching Speed: Maximum of 50 ns
- High Reverse Breakdown Voltage: 325V
- Low Leakage Current: Maximum of 50nA when  $V_R = 5V$  or Maximum of 150nA when  $V_R = 250V$  at Room Temperature
- Ultra Small Plastic SMD Package: 1.0mm x 0.6mm x 0.5mm
- **Lead, Halogen and Antimony Free, RoHS Compliant (Note 1)**
- **"Green" Device (Note 2)**


## Mechanical Data

- Case: X1-DFN1006-2
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - NiPdAu over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Weight: 0.0009 grams (approximate)

X1-DFN1006-2



Bottom View



Device Schematic


## Ordering Information (Note 3)

| Part Number | Case         | Packaging          |
|-------------|--------------|--------------------|
| BAS521LP-7  | X1-DFN1006-2 | 3,000/Tape & Reel  |
| BAS521LP-7B | X1-DFN1006-2 | 10,000/Tape & Reel |


- Notes:
1. No purposefully added lead. Halogen and Antimony Free.
  2. Diodes Inc.'s "Green" policy can be found on our website at <http://www.diodes.com>.
  3. For packaging details, go to our website at <http://www.diodes.com>.

## Marking Information

BAS521LP-7


 Top View  
 Dot Denotes  
 Cathode Side

BAS521LP-7B


 Top View  
 Bar Denotes  
 Cathode Side

98 = Product Type Marking Code

**Maximum Ratings** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                                        | Symbol           | Value | Unit |
|-------------------------------------------------------|------------------|-------|------|
| Repetitive Peak Reverse Voltage                       | V <sub>RRM</sub> | 325   | V    |
| Working Peak Reverse Voltage                          | V <sub>RWM</sub> | 325   | V    |
| DC Blocking Voltage                                   | V <sub>R</sub>   | 325   | V    |
| Forward Current (Note 4)                              | I <sub>F</sub>   | 400   | mA   |
| Non-Repetitive Peak Forward Surge Current @ t = 1.0μs | I <sub>FSM</sub> | 8.0   | A    |
| Repetitive Peak Forward Current @ t=8.3ms (Note 4)    | I <sub>FRM</sub> | 3.0   | A    |



**Thermal Characteristics**

| Characteristic                                      | Symbol                            | Value       | Unit |
|-----------------------------------------------------|-----------------------------------|-------------|------|
| Power Dissipation (Note 4)                          | P <sub>D</sub>                    | 400         | mW   |
| Thermal Resistance Junction to Ambient Air (Note 4) | R <sub>θJA</sub>                  | 312         | °C/W |
| Operating and Storage Temperature Range             | T <sub>J</sub> , T <sub>STG</sub> | -65 to +150 | °C   |

**Electrical Characteristics** @T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                     | Symbol             | Min | Max              | Unit           | Test Condition                                                                                            |
|------------------------------------|--------------------|-----|------------------|----------------|-----------------------------------------------------------------------------------------------------------|
| Reverse Breakdown Voltage (Note 5) | V <sub>(BR)R</sub> | 300 | —                | V              | I <sub>R</sub> = 100μA                                                                                    |
| Forward Voltage                    | V <sub>F</sub>     | —   | 1.1              | V              | I <sub>F</sub> = 100mA                                                                                    |
| Reverse Current (Note 5)           | I <sub>R</sub>     | —   | 50<br>150<br>100 | nA<br>nA<br>μA | V <sub>R</sub> = 5V<br>V <sub>R</sub> = 250V<br>V <sub>R</sub> = 250V, T <sub>J</sub> = 150°C             |
| Total Capacitance                  | C <sub>T</sub>     | —   | 5                | pF             | V <sub>R</sub> = 0, f = 1.0MHz                                                                            |
| Reverse Recovery Time              | t <sub>rr</sub>    | —   | 50               | ns             | I <sub>F</sub> = I <sub>R</sub> = 30mA,<br>I <sub>rr</sub> = 0.1 x I <sub>R</sub> , R <sub>L</sub> = 100Ω |

Notes: 4. Part mounted on FR-4 board with recommended pad layout, which can be found on our website at <http://www.diodes.com>.  
 5. Short duration pulse test used to minimize self-heating effect.






Fig. 3 Typical Reverse Characteristics






Fig. 4 Total Capacitance vs. Reverse Voltage

## Package Outline Dimensions



| X1-DFN1006-2         |      |       |      |
|----------------------|------|-------|------|
| Dim                  | Min  | Max   | Typ  |
| A                    | 0.47 | 0.53  | 0.50 |
| A1                   | 0    | 0.05  | 0.03 |
| b                    | 0.45 | 0.55  | 0.50 |
| D                    | 0.95 | 1.075 | 1.00 |
| E                    | 0.55 | 0.675 | 0.60 |
| e                    | -    | -     | 0.40 |
| L                    | 0.20 | 0.30  | 0.25 |
| R                    | 0.05 | 0.15  | 0.10 |
| All Dimensions in mm |      |       |      |

## Suggested Pad Layout



| Dimensions | Value (in mm) |
|------------|---------------|
| Z          | 1.1           |
| G          | 0.3           |
| X          | 0.7           |
| Y          | 0.4           |
| C          | 0.7           |

#### **IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

#### **LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2011, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)