

Material & Color Availability Chart

CABLE TIES

Available Styles

- Pan-Ty® Cable Ties - Clamp Ties, Marker and Flag Ties, Push Mount Ties, Lashing Ties, Releasable Ties

- Super-Grip® Cable Ties

- Dome-Top® Barb Ty Cable Ties - Clamp Ties, Marker and Flag Ties, Push Mount Ties, Dura-Ty™ Cable Ties

- Parallel-Entry Ties:
 - Contour-Ty™ Cable Ties,
 - Hyper-V™ In-Line Cable Ties,
 - Belt-Ty™ In-Line Cable Ties,
 - IN-LINE Cable Ties),
 - Elastomeric Cable Ties

- Hook and Loop Cable Ties:
 - Tak-Ty® Cable Ties (Cinch Ties, 15' & 75' Rolls, Strip Ties, Loop Ties, UL Listed Strip & Loop Ties, Stacked Strips)
 - Tak-Tape™ Rolls
 - Ultra-Cinch™ Cable Ties

- Sta-Strap® Cable Ties - Clamp Ties, Marker Ties

- Specialty Ties - Cable Marker Strap, Double Hose Clamp, Double Loop, Triple Loop, Locking Stud Mounted, Releasable Stud Mounted Ladder Ties, Bow-Ty, Chassis/Panel Mount Ties

CONTACTS

Customer Service Phone: 800-777-3300 • Fax: 708-532-1811 • Email: info@panduit.com • Website: www.panduit.com

Part Number System for Pan-Ty® Cable Ties

PLT

2

S

—

C

Type

PLT = Locking Tie
 PRT = Releasable Tie
 PLC = Locking Clamp
 PLF = Locking Flag
 PLM = Locking Marker
 PLP = Locking Push Mount
 PLWP = Locking Wing Push Mount
 PRLWP = Releasable Ladder Wing Push Mt.
 PRWP = Releasable Wing Push Mount
 PLUP = Locking Umbrella Push Mount

Size

Approx. Maximum Bundle Dia. (In)

Cross Section

SM = Subminiature
 M = Miniature
 I = Intermediate
 S = Standard
 LH = Light-Heavy
 H = Heavy
 EH = Extra-Heavy

Screw Hole Size

(Clamp Ties Only)
 - S4 = #4(M2.5)
 - S6 = #6 (M3)
 - S8 = #8 (M4)
 - S10 = #10 (M5)
 - S25 = 1/4 (M6)

Package Size

Q = 25
 L = 50
 C = 100
 TL = 250
 D = 500
 M = 1000
 VMR = 2 reels/2500 ea
 XMR = 2 reels/5000 ea

Mat'l / Color

See below

Material and Color Chart

| Material | Color | Panduit Suffix |
|--|----------------|----------------|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Weather Resistant Nylon 6.6 (meets Mil. Spec.) | Black | 00 |
| Nylon 6.6 | Brown | 1 |
| Nylon 6.6 | Red | 2 |
| Nylon 6.6 | Orange | 3 |
| Nylon 6.6 | Yellow | 4Y |
| Nylon 6.6 | Green | 5 |
| Nylon 6.6 | Blue | 6 |
| Nylon 6.6 | Purple | 7 |
| Nylon 6.6 | Gray | 8 |
| Nylon 6.6 | White | 10 |
| Nylon 6.6 | Telephone Gray | 14 |
| Nylon 6.6 | Black | 20 |
| Heat Stabilized Nylon 6.6 | Black | 30 |

| Material | Color | Panduit Suffix |
|---|--------------------|----------------|
| Heat Stabilized Nylon 6.6 | Natural | 39 |
| Nylon 6.6 | Fluorescent Orange | 53 |
| Nylon 6.6 | Fluorescent Yellow | 54 |
| Nylon 6.6 | Fluorescent Green | 55 |
| Nylon 6.6 | Fluorescent Pink | 59 |
| Flame Retardant Nylon 6.6 | Black | 60 |
| Flame Retardant Nylon 6.6 | Natural (Ivory) | 69 |
| PEEK (Polyetheretherketone) | Translucent Brown | 71 |
| TEFZEL [®] | Aqua Blue | 76 |
| Metal Detectable | Blue | 86 |
| Weather Resistant Polypropylene | Black | 100 |
| Polypropylene | Green | 109 |
| Nylon 12 | Black | 120 |
| Heat Stabilized Weather Resistant Nylon 6.6 | Black | 300 |
| HALAR [®] | Maroon | 702Y |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

[®]TEFZEL is a registered trademark of E. I. du Pont de Nemours and Company.

[®]HALAR is a registered trademark of Solvay Solexis, Inc.

Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|--------------------|-------------------|-----------------------|----------------|-------------------|------------------------------------|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| PLC1M-S4-C | ✓ | 0 | PLC1M-S4-M | ✓ | 0, 30 |
| PLC1.5I-S8-C | ✓ | 0 | PLC1.5I-S8-M | ✓ | 0, 30 |
| PLC2S-S6-C | ✓ | 0 | PLC2S-S6-M | ✓ | 0 |
| PLC2S-S10-C | ✓ | 0, 14 | PLC2S-S10-M | ✓ | 0, 20, 30 |
| PLC3S-S10-C | ✓ | 0 | PLC3S-S10-M | ✓ | 0 |
| PLC4S-S10-C | ✓ | 0 | PLC4S-S10-M | ✓ | 0, 30 |
| PLC2H-S25-L | ✓ | | PLC2H-S25-TL | ✓ | 0, 30 |
| PLC4H-S25-L | ✓ | 0 | PLC4H-S25-TL | ✓ | 0, 30 |
| PLF1M-C | ✓ | 0 | PLF1M-M | ✓ | 0, 2, 3, 4Y, 6, 10, 69 |
| PLF1MA-C | ✓ | 3, 4Y | PLF1MA-M | ✓ | 0, 2, 3, 4Y, 5, 6, 10 |
| PLF1MB-C | ✓ | | PLF1MB-M | ✓ | |
| | | | PLF1MC-M | ✓ | 3 |
| PLM1M-C | ✓ | 0 | PLM1M-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 69 |
| PLM2M-C | ✓ | | PLM2M-M | ✓ | 0, 4Y, 6 |
| PLM2S-C | ✓ | 0, 4Y | PLM2S-D | ✓ | 0, 2, 3, 4Y, 5, 6, 8 |
| PLM4S-C | ✓ | | PLM4S-D | ✓ | 0, 2, 4Y, 6 |
| PL2M2S-L | ✓ | 0 | PL2M2S-D | ✓ | 0, 4Y, 10 |

| Standard Packaging | | | Bulk Packaging | | |
|--------------------|-------------------|---|----------------|-------------------|--|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| PL3M2S-L | ✓ | | PL3M2S-D | ✓ | 0, 4Y |
| PLP1.5I-C | ✓ | | PLP1.5I-M | ✓ | 0, 30 |
| | | | PLP1S-M | ✓ | 0, 30 |
| | | | PLP1.5S-M | ✓ | |
| PLP2S-C | ✓ | | PLP2S-M | ✓ | 0, 30 |
| PLT.6SM-C | ✓ | 0 | PLT.6SM-M | ✓ | 0, 30 |
| PLT.7M-C | ✓ | | PLT.7M-M | ✓ | 0, 30 |
| PLT1M-C | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 30, 76, 86, 186, 702Y | PLT1M-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 20, 30, 53, 54, 55, 59, 60, 69, 76, 100, 109, 300, 702Y |
| | | | PLT1M-XMR | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 30 |
| PLT1.5M-C | ✓ | 0 | PLT1.5M-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 20, 30 |
| | | | PLT1.5M-XMR | ✓ | 0, 00, 30 |
| PLT2M-C | ✓ | 0 | PLT2M-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 69 |
| PLT1.5I-C | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30 | PLT1.5I-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 69, 100, 109, 120, 300 |
| PLT2I-C | ✓ | 0, 14, 30, 76, 86, 186 | PLT2I-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 20, 30, 53, 54, 55, 59, 69, 76, 300 |
| PLT2.5I-C | ✓ | 0 | PLT2.5I-M | ✓ | 0, 20 |
| PLT3I-C | ✓ | 0, 14 | PLT3I-M | ✓ | 0, 2, 3, 4Y, 5, 6, 8, 10, 14, 20, 30 |
| PLT4I-C | ✓ | 0, 14 | PLT4I-M | ✓ | 0, 2, 5, 6, 14, 20, 30 |
| PLT1S-C | ✓ | 0 | PLT1S-M | ✓ | 0, 30, 38, 300 |
| PLT1.5S-C | ✓ | 0 | PLT1.5S-M | ✓ | 0, 30 |
| PLT2S-C | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 71, 76, 86, 186, 702Y | PLT2S-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 38, 39, 53, 54, 55, 59, 60, 69, 71, 76, 100, 109, 120, 300, 702Y |
| | | | PLT2S-VMR | ✓ | 0, 30 |
| PLT2.5S-C | ✓ | 0 | PLT2.5S-M | ✓ | 0, 30 |
| PLT3S-C | ✓ | 0, 00, 2, 20, 30, 76, 86, 186, 702Y | PLT3S-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 53, 54, 55, 59, 76, 100, 109, 702Y |
| | | | PLT3S-VMR | ✓ | 30 |
| PLT4S-C | ✓ | 0, 00, 2, 3, 4Y, 5, 6, 8, 20, 30, 76, 86, 186 | PLT4S-M | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 14, 20, 30, 69, 76, 100, 109, 120, 300 |
| PLT4.5S-C | ✓ | 0 | PLT4.5S-M | ✓ | 0 |
| PLT5S-C | ✓ | 0 | PLT5S-M | ✓ | 0, 2, 3, 4Y, 5, 6, 8, 30 |
| PLT6LH-L | ✓ | 0 | PLT6LH-C | ✓ | 0 |
| PLT7LH-L | ✓ | 0 | PLT7LH-C | ✓ | 0, 30 |
| PLT8LH-L | ✓ | 0 | PLT8LH-C | ✓ | 0, 120 |
| PLT8LH-Q | | 0 | | | |
| PLT9LH-L | ✓ | 0 | PLT9LH-C | ✓ | 0, 30 |
| PLT10LH-L | ✓ | | PLT10LH-C | ✓ | |
| PLT2H-L | ✓ | 0 | PLT2H-TL | ✓ | 0, 2, 4Y, 6, 30, 100, 109, 300 |
| PLT2.5H-L | ✓ | 0 | PLT2.5H-TL | ✓ | 0 |
| PLT3H-L | ✓ | 0, 76, 86, 186 | PLT3H-TL | ✓ | 0, 30, 76, 100, 109 |
| PLT4H-L | ✓ | 0, 00, 76, 86, 186 | PLT4H-TL | ✓ | 0, 00, 1, 2, 3, 4Y, 5, 6, 10, 20, 30, 69, 76, 100, 109, 120, 300 |
| PLT4H-C | ✓ | 0 | | | |
| PLT5H-L | ✓ | 0 | PLT5H-C | ✓ | 0, 30 |
| PLT6H-L | ✓ | 0 | PLT6H-C | ✓ | 0, 30 |
| PLT8H-L | ✓ | 0 | PLT8H-C | ✓ | 0, 00, 30 |
| PLT8H-L | ✓ | 0 | | | |
| PLT13H-Q | ✓ | 0 | PLT13H-C | ✓ | 0, 3 |
| PLT2EH-Q | | 0 | PLT2EH-C | ✓ | 0 |
| | | | PLT3EH-NB-C | | 0 |
| PLT5EH-Q | ✓ | 0 | PLT5EH-C | ✓ | 0 |
| | | | PLT5EH-NB-C | | 0 |
| PLT6EH-Q | ✓ | 0 | PLT6EH-C | ✓ | 0 |
| | | | PLT6EH-NB-C | | 0 |
| PLT8EH-Q | | 0 | PLT8EH-C | ✓ | 0 |
| PLT10EH-Q | | 0 | PLT10EH-C | ✓ | 0 |
| PLT12EH-Q | | 0 | PLT12EH-C | ✓ | 0 |

| Standard Packaging | | | Bulk Packaging | | |
|--------------------|-------------------|-----------------------|----------------|-------------------|-----------------------|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| | | | PLUP40S-D | | 30 |
| | | | PLUP40SE-D | ✓ | 30 |
| PLWP1M-C | ✓ | | PLWP1M-D | ✓ | 0, 30 |
| PLWP1.5I-C | ✓ | | PLWP1.5I-D | ✓ | 30 |
| PLWP1S-C | ✓ | 0 | PLWP1S-D | ✓ | 0, 20, 30 |
| | | | PLWP1SA-D | ✓ | |
| | | | PLWP1SB-D | ✓ | |
| | | | PLWP1.5S-D | ✓ | 30 |
| | | | PLWP1.5SA-D | ✓ | |
| PLWP2S-C | ✓ | 0 | PLWP2S-D | ✓ | 0, 30 |
| | | | PLWP2SA-D | ✓ | |
| | | | PLWP2SB-D | ✓ | |
| | | | PLWP2H-TL | ✓ | 0, 30 |
| | | | PLWP3H-TL | ✓ | 0 |
| | | | PLWP30SC-D | | 30 |
| | | | PLWP40SC-D | | 30 |
| | | | PLWP40SD-D | | 30 |
| | | | PLWP50SC-D | | 30 |
| | | | PLWP50SE-D | | 30 |
| | | | PRLWP30S-D | | 30 |
| | | | PRLWP50S-D | | 30 |
| PRT1S-C | ✓ | 0 | PRT1S-M | ✓ | 0 |
| PRT1.5S-C | ✓ | 0 | PRT1.5S-M | ✓ | 0, 30 |
| PRT2S-C | ✓ | 0 | PRT2S-M | ✓ | 0, 2, 3, 4Y, 6, 7 |
| PRT3S-C | ✓ | 0 | PRT3S-M | ✓ | 0 |
| PRT4S-C | ✓ | 0 | PRT4S-M | ✓ | 0, 2, 3, 4Y, 6 |
| PRT2H-L | ✓ | 0 | PRT2H-TL | ✓ | 0 |
| PRT3H-L | ✓ | 0 | PRT3H-TL | ✓ | 0 |
| PRT4H-L | ✓ | 0 | PRT4H-TL | ✓ | 0 |
| PRT2EH-Q | | 0 | PRT2EH-C | ✓ | 0, 100 |
| PRT5EH-Q | ✓ | 0 | PRT5EH-C | ✓ | 0, 100 |
| PRT6EH-Q | ✓ | 0 | PRT6EH-C | ✓ | 0, 100 |
| PRT8EH-Q | | 0 | PRT8EH-C | ✓ | 0, 100 |
| PRT10EH-Q | | 0 | PRT10EH-C | ✓ | 0 |
| PRT12EH-Q | | 0 | PRT12EH-C | ✓ | 0 |
| PRWP1S-C | ✓ | | PRWP1S-D | ✓ | 0 |
| | | | PRWP1SA-D | ✓ | |
| | | | PRWP1SB-D | ✓ | |
| | | | PRWP1.5S-D | ✓ | 0, 20, 30 |
| | | | PRWP2S-D | ✓ | 0 |
| | | | PRWP2H-TL | ✓ | |

Part Number System for Super-Grip® Cable Ties

SG 200 S — C

| <u>Type</u> | <u>Size</u> | <u>Cross Section</u> | <u>Package Size</u> | <u>Material / Color</u> |
|------------------|---------------------------|--|---|-------------------------|
| SG = Locking Tie | Approx. Length (mm) | M = Miniature I = Intermediate S = Standard LH = Light-Heavy H = Heavy | L = 50 C = 100 TL = 250 M = 1000 | See below |

Material and Color Chart

| Material | Color | Panduit Suffix |
|-----------------------------|---------|----------------|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Heat Stabilized Nylon 6.6 | Black | 30 |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|--------------------|-------------------|-----------------------|----------------|-------------------|-----------------------|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| SG100M-C | ✓ | 0 | SG100M-M | ✓ | 0 |
| SG150I-C | ✓ | 0 | SG150I-M | ✓ | 0 |
| SG200S-C | ✓ | 0 | SG200S-M | ✓ | 0, 30 |
| SG250S-C | ✓ | 0 | | | |
| SG300S-C | ✓ | 0 | SG300S-M | ✓ | 0, 30 |
| SG370S-C | ✓ | 0 | SG370S-M | ✓ | 0 |
| SG350LH-L | ✓ | 0 | SG350LH-TL | ✓ | 0, 30 |
| SG450H-L | ✓ | 0 | SG450H-C | ✓ | 0 |

Part Number System for Dome-Top® Barb Ty & Dura-Ty™ Cable Ties

| BT | 2 | S | — | C | Material / Color |
|--------------------------|-------------|----------------------|---|---------------------|------------------|
| <u>Type</u> | <u>Size</u> | <u>Cross Section</u> | <u>Screw Hole Size</u> (Clamp Ties Only) | <u>Package Size</u> | |
| BT = Locking Tie | Approx. | M = Miniature | —S4 = #4 (M2.5) | Q = 25 | See below |
| BC = Clamp Tie | Maximum | I = Intermediate | —S6 = #6 (M3) | L = 50 | |
| BF = Flag Tie | Bundle | S = Standard | —S8 = #8 (M4) | C = 100 | |
| BM = Marker Tie | Dia. (In) | LH = Light-Heavy | —S10 = #10 (M5) | TL = 250 | |
| BP = Push Mount Tie | | H = Heavy | —S25 = 1/4 (M6) | D = 500 | |
| BW = Wing Push Mount Tie | | EH = Extra-Heavy | | M = 1000 | |
| DT = Locking Tie | | | | LR = 50' Reel | |

Material and Color Chart

| Material | Color | Panduit Suffix |
|-----------------------------|---------|----------------|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Nylon 6.6 | Brown | 1 |
| Nylon 6.6 | Red | 2 |
| Nylon 6.6 | Orange | 3 |
| Nylon 6.6 | Yellow | 4Y |
| Nylon 6.6 | Green | 5 |
| Nylon 6.6 | Blue | 6 |
| Nylon 6.6 | Purple | 7 |

| Material | Color | Panduit Suffix |
|---|-----------------|----------------|
| Nylon 6.6 | Gray | 8 |
| Nylon 6.6 | White | 10 |
| Nylon 6.6 | Telephone Gray | 14 |
| Nylon 6.6 | Black | 20 |
| Heat Stabilized Nylon 6.6 | Black | 30 |
| Heat Stabilized Nylon 6.6 | Natural | 39 |
| Flame Retardant Nylon 6.6 | Natural (Ivory) | 69 |
| Weather Resistant Acetal | Black | * |
| Heat Stabilized Weather Resistant Nylon 6.6 | Black | 300 |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

* Denotes Dura-Ty™ Weather Resistant Acetal material (no suffix).

Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|--------------------|-------------------|-----------------------|----------------|-------------------|---|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| | | | BC1M-S4-M | ✓ | 0 |
| | | | BC2M-S4-M | ✓ | 0 |
| | | | BC1.5I-S8-M | ✓ | 0 |
| BC2S-S10-C | ✓ | 0 | BC2S-S10-D | ✓ | 0 |
| | | | BC3S-S10-D | ✓ | 0 |
| BC4S-S10-C | ✓ | 0 | BC4S-S10-D | ✓ | 0, 30 |
| BC4LH-S25-L | ✓ | 0 | BC4LH-S25-TL | ✓ | 0 |
| BF1M-C | ✓ | | BF1M-M | ✓ | 0 |
| BF2M-C | ✓ | | BF2M-M | ✓ | 0 |
| BM1M-C | ✓ | | BM1M-M | ✓ | 0 |
| BM2M-C | ✓ | | BM2M-M | ✓ | 0 |
| BM2S-C | ✓ | | BM2S-D | ✓ | 0 |
| BM4S-C | ✓ | | BM4S-D | ✓ | 0 |
| | | | BP2S-D | | 0 |
| BT1M-C | ✓ | 0, 30 | BT1M-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 30, 39, 69, 300 |
| | | | BT1M-XMR | ✓ | 0, 30 |
| BT1.5M-C | ✓ | 0 | BT1.5M-M | ✓ | 0, 30, 69 |
| | | | BT1.5M-XMR | ✓ | 0, 30, 69 |
| BT2M-C | ✓ | 0 | BT2M-M | ✓ | 0, 2, 3, 4Y, 5, 6, 8, 30 |
| BT4M-C | ✓ | 0 | BT4M-M | ✓ | 0 |
| BT1.5I-C | ✓ | 0 | BT1.5I-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 30, 39 |
| BT2I-C | ✓ | 0 | BT2I-M | ✓ | 0, 30, 69, 300 |
| BT3I-C | ✓ | 0 | BT3I-M | ✓ | 0, 14, 30 |

| Standard Packaging | | | Bulk Packaging | | |
|--------------------|-------------------|-----------------------|----------------|-------------------|---|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| BT4I-C | ✓ | 0 | BT4I-M | ✓ | 0, 14 |
| BT2S-C | ✓ | 0 | BT2S-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10, 20, 30, 39, 69, 300 |
| BT3S-C | ✓ | 0, 2 | BT3S-M | ✓ | 0, 30, 39, 69, 300 |
| BT4S-C | ✓ | 0 | BT4S-M | ✓ | 0, 2, 3, 4Y, 5, 6, 7, 8, 10, 30, 39, 300 |
| BT2LH-L | ✓ | 0 | BT2LH-TL | ✓ | 0, 300 |
| BT3LH-L | ✓ | 0 | BT3LH-TL | ✓ | 0 |
| BT4LH-L | ✓ | 0 | BT4LH-TL | ✓ | 0, 30, 39, 69, 300 |
| BT5LH-L | ✓ | 0 | BT5LH-C | ✓ | 0, 300 |
| BT6LH-L | ✓ | 0 | BT6LH-C | ✓ | 0, 69, 300 |
| BT7LH-L | ✓ | 0 | BT7LH-C | ✓ | 0 |
| BT8LH-L | ✓ | 0 | BT8LH-C | ✓ | 0, 300 |
| BT9LH-L | ✓ | 0 | BT9LH-C | ✓ | 0, 300 |
| | | | BW1.5I-D | ✓ | |
| | | | BW2S-D | ✓ | 0 |
| | | | B2M2S-D | ✓ | 0 |
| | | | B3M2S-TL | ✓ | 0 |
| | | | B4M2S-TL | ✓ | 0 |
| DTHEH-Q0 | | * | | | |
| DTHH-Q0 | | * | | | |
| DTKEH-0 | | * | | | |
| DTKH-0 | | * | | | |
| DTREH-LR0 | | * | | | |
| DTRH-LR0 | | * | | | |
| DT4EH-L0 | | * | | | |
| DT8EH-Q0 | | * | | | |
| DT14EH-L0 | | * | DT14EH-C0 | | * |
| DT15EH-L0 | | * | | | |
| DT28EH-C0 | | * | | | |
| DT44EH-C0 | | * | | | |

Part Number System for Contour-Ty® and Belt-Ty™ Cable Ties

| <u>CBR</u> | <u>2</u> | <u>S</u> | <u>M</u> | <u>Material/Color</u> |
|--|---|--|--|-----------------------|
| <u>Type</u> | <u>Size</u> | <u>Cross Section</u> | <u>Package Size</u> | |
| CBR = Locking Tie ILT = Locking Tie | Approx. Maximum Bundle Dia. (In) | M = Miniature I = Intermediate S = Standard HS = Heavy-Standard LH = Light-Heavy | C = 100 TL = 250 D = 500 M = 1000 | See below |

Part Number System for IN-LINE and Hyper-V™ Cable Ties

| <u>IT</u> | <u>9</u> | <u>100</u> | <u>C</u> | <u>Material/Color</u> |
|--------------------------------------|--------------------------|-------------------------------------|---------------------|-----------------------|
| <u>Type</u> | <u>Width</u> | <u>Size</u> | <u>Package Size</u> | |
| HV = Locking Tie IT = Locking Tie | Approx. Width (mm) | Approx. Max. Bundle Dia. (mm) | C = 100 | See below |

Part Number System for Elastomeric Cable Ties

| <u>ERT</u> | <u>2</u> | <u>M</u> | <u>C</u> | <u>Material/Color</u> |
|-------------------------------------|----------------------------------|----------------------|---------------------|-----------------------|
| <u>Type</u> | <u>Size</u> | <u>Cross Section</u> | <u>Package Size</u> | |
| ERT = Elastomeric Releasable Tie | Approx. Max. Bundle Dia. (In) | M = Miniature | C = 100 | See below |

Material and Color Chart

| Material | Color | Panduit Suffix | Material | Color | Panduit Suffix |
|-----------------------------|-----------------|----------------|-----------|--------------------------|----------------|
| Nylon 6.6 | Natural | ✓ | Nylon 6.6 | Ultraviolet Red | UV2 |
| Weather Resistant Nylon 6.6 | Black | 0 | Nylon 6.6 | Ultraviolet Bright Red | UV2A |
| Nylon 6.6 | Brown | 1 | Nylon 6.6 | Ultraviolet Yellow | UV4Y |
| Nylon 6.6 | Red | 2 | Nylon 6.6 | Ultraviolet Butterscotch | UV4A |
| Nylon 6.6 | Orange | 3 | Nylon 6.6 | Ultraviolet Green | UV5A |
| Nylon 6.6 | Yellow | 4Y | Nylon 6.6 | Ultraviolet Hunter Green | UV5B |
| Nylon 6.6 | Green | 5 | Nylon 6.6 | Ultraviolet Dark Blue | UV6 |
| Nylon 6.6 | Blue | 6 | Nylon 6.6 | Ultraviolet Light Blue | UV6A |
| Nylon 6.6 | Purple | 7 | Nylon 6.6 | Ultraviolet Cobalt Blue | UV6B |
| Nylon 6.6 | Gray | 8 | Nylon 6.6 | Ultraviolet Purple | UV7A |
| Nylon 6.6 | White | 10 | Nylon 6.6 | Ultraviolet Gray | UV8 |
| TPU | Black | 20 | Nylon 6.6 | Ultraviolet Teal | UV11 |
| Heat Stabilized Nylon 6.6 | Black | 30 | Nylon 6.6 | Ultraviolet Magenta | UV16B |
| Heat Stabilized Nylon 6.6 | Natural | 39 | Nylon 6.6 | Ultraviolet Tan | UV18 |
| Flame Retardant Nylon 6.6 | Natural (Ivory) | 69 | | | |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|--------------------|-------------------|-----------------------|----------------|-------------------|---|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| | | | CBR1M-M | ✓ | 0, 30 |
| | | | CBR1.5M-M | ✓ | 0 |
| | | | CBR2M-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 10 |
| | | | CBR1.5I-M | ✓ | 0, 30 |
| | | | CBR3I-M | ✓ | 0, 1, 2, 3, 4Y, 5, 6, 7, 8, 10 |
| | | | CBR4I-M | ✓ | 0 |
| | | | CBR2S-M | ✓ | 0, 30, 39 |
| | | | CBR3S-M | ✓ | 0, 30, 69 |
| | | | CBR4S-M | ✓ | 0, 30 |
| | | | CBR2HS-D | ✓ | 0 |
| | | | CBR4LH-TL | ✓ | 0, 30 |
| | | | CBR6LH-C | ✓ | 0, 30 |
| | | | ERT2M-C | | 20 |
| | | | ERT3M-C | | 20 |
| | | | ERT4.5M-C | | 20 |
| | | | HV965-C | | 0 |
| | | | HV9100-C | | 0 |
| | | | HV9150-C | | 0 |
| | | | HV9250-C | | 0 |
| ILT2S-C | ✓ | 0 | ILT2S-M | ✓ | 0 |
| ILT3S-C | ✓ | 0 | ILT3S-M | ✓ | 0 |
| ILT4S-C | ✓ | 0 | ILT4S-M | ✓ | 0 |
| | | | ILT4LH-TL | ✓ | 0 |
| | | | ILT6LH-C | ✓ | 0 |
| | | | IT940-C | | 0 |
| | | | IT965-C | | 0 |
| | | | IT9100-C | | 0, UV2,4Y,6,6A,7A,8,16B |
| | | | IT9115-C | | 0, UV2,2A,4Y,4A,5A,5B, 6,6A,6B,7A, 8,11,16B, 18 |

Part Number System for Sta-Strap® Cable Ties

SST

1

M

—

C

Type

SST = Locking Tie
 SSC = Clamp Tie
 SSM = Marker Tie

Size

Approx.
 Maximum
 Bundle
 Dia. (In)

Cross Section

M = Miniature
 I = Intermediate
 S = Standard
 H = Heavy
 HH = Heavy Head

Screw Hole Size

(Clamp Ties Only)
 -S6 = #6 (M3)
 -S10 = #10 (M5)
 -S25 = ¼ (M6)

Package Size

L = 50
 C = 100
 D = 500
 M = 1000

Material/Color

See below

Material and Color Chart

| Material | Color | Panduit Suffix |
|-----------------------------|---------|----------------|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Nylon 6.6 | Red | 2 |

| Material | Color | Panduit Suffix |
|---------------------------|-------|----------------|
| Nylon 6.6 | Black | 20 |
| Heat Stabilized Nylon 6.6 | Black | 30 |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|--------------------|-------------------|-----------------------|----------------|-------------------|-----------------------|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| SSC2S-S6-C | ✓ | | SSC2S-S6-M | ✓ | 0 |
| SSC2S-S10-C | ✓ | | SSC2S-S10-M | ✓ | 0, 30 |
| SSC4S-S10-C | ✓ | | SSC4S-S10-M | ✓ | 0 |
| SSC4H-S25-L | ✓ | | SSC4H-S25-D | ✓ | 0 |
| SSM2S-C | ✓ | | SSM2S-D | ✓ | 0 |
| | | | SSM4S-D | ✓ | |
| SST1M-C | ✓ | 0 | SST1M-M | ✓ | 0, 20, 30 |
| SST1.5M-C | ✓ | | SST1.5M-M | ✓ | 0, 20, 30 |
| SST1.5I-C | ✓ | | SST1.5I-M | ✓ | 0 |
| SST2I-C | ✓ | | SST2I-M | ✓ | 0 |
| SST3I-C | ✓ | 0 | SST3I-M | ✓ | 0 |
| SST4I-C | ✓ | | SST4I-M | ✓ | 0 |
| | | | SST1.5S-M | ✓ | 0 |
| SST2S-C | ✓ | 0 | SST2S-M | ✓ | 0, 20, 30 |
| SST3S-C | ✓ | 0 | SST3S-M | ✓ | 0, 20, 30 |
| SST4S-C | ✓ | 0 | SST4S-M | ✓ | 0, 2, 30 |
| | | | SST2H-D | ✓ | 0 |
| | | | SST2HH-D | | 30 |
| SST4H-L | ✓ | 0 | SST4H-D | ✓ | 0, 30 |
| | | | SST4HH-D | | 30 |
| SST8H-L | ✓ | 0 | SST8H-D | ✓ | 0, 30 |

Part Number System for Specialty Cable Ties

PLST

4

H

S25

— TL

300

Type

CM4S = Cable Marker Strap
 PLB = Locking Bow Tie
 PL3B = Triple Loop Tie
 DHC = Double Hose Clamp
 PLST = Locking Stud Mounted Tie
 PRST = Releasable Stud Mount Ladder Style
 SSB = Sta-Strap® Bow-Ty™ Tie
 SSPM = Sta-Strap® Panel Mount

Size

Approx.
 Maximum
 Bundle
 Dia. (In)

Cross Section

S = Standard
 H = Heavy
 EH = Extra-Heavy

Stud Size

—S25 = M6
 —SC = 5mm
 —S14 = 5mm

Package Size

L = 50
 C = 100
 TL = 250
 D = 500
 M = 1000

**Material/
Color**

See below

Material and Color Chart

| Material | Color | Panduit Suffix |
|-----------------------------|---------|----------------|
| Nylon 6.6 | Natural | ✓ |
| Weather Resistant Nylon 6.6 | Black | 0 |
| Nylon 6.6 | Red | 2 |
| Nylon 6.6 | Gray | 8 |

| Material | Color | Panduit Suffix |
|---|-------|----------------|
| Heat Stabilized Nylon 6.6 | Black | 30 |
| Heat Stabilized Weather Resistant Nylon 6.6 | Black | 300 |

✓ Denotes Panduit Natural Nylon 6.6 (no suffix).

Part Number Availability List

| Standard Packaging | | | Bulk Packaging | | |
|--------------------|-------------------|-----------------------|----------------|-------------------|-----------------------|
| Part Number | Natural Nylon 6.6 | Material/Color Suffix | Part Number | Natural Nylon 6.6 | Material/Color Suffix |
| CM4S-L | | 2, 8 | | | |
| | | | DHC1.12X1.75-D | | 0 |
| PLB2S-C | ✓ | 0 | PLB2S-M | ✓ | 0, 30 |
| PLB3S-C | ✓ | 0 | PLB3S-M | ✓ | 0, 30 |
| PLB4S-C | ✓ | | PLB4S-M | ✓ | 0, 30, 39 |
| | | | PLB4H-TL | ✓ | 0, 30, 39 |
| | | | PLB5EH-C | | 0 |
| | | | PL3B5EH-C | | 0 |
| | | | PLST4HS25-TL | | 300 |
| | | | PLST30SC-D | | 30 |
| | | | PLST50SC-D | | 30 |
| | | | PRST30S-S14-M | | 30 |
| | | | PRST40SC-D | | 30 |
| SSB2S-C | ✓ | | SSB2S-M | ✓ | 0, 30 |
| SSPM2.5H-L | | 300 | SSPM2.5H-TL | | 300 |
| SSPM2.5HP-L | | 300 | SSPM2.5HP-TL | | 300 |
| SSPM4H-L | | 300 | SSPM4H-TL | | 300 |
| SSPM4HP-L | | 300 | SSPM4HP-TL | | 300 |
| | | | SSPM4HLP-TL | | 300 |

Part Number System for Tak-Ty® Hook & Loop Cable Ties

| HLT | 2 | I | X | 0 |
|--|---|----------------------------------|--|--------------|
| <u>Type</u> | <u>Size</u> | <u>Cross Section</u> | <u>Package Size</u> | <u>Color</u> |
| HL = Hook and Loop HLB = Hook and Loop Brick Pack HLC = HL Cinch Tie HLM = HL Miniature HLT = HL Loop Tie HLTP = HL Loop Tie Plenum-Rated HLS = HL Strip Tie HLSP = HL Strip Tie Plenum-Rated TTS = Tak-Tape™ Roll | Approx. Maximum Bundle Dia. (In) | I = Intermediate S = Standard | C = 100 X = 10 15R = 15' Roll 20R = 20' Roll 35R3 = 35' Rolls (3) 35RX = 35' Rolls (10) 75R = 75' Roll | See below |

Part Number System for Ultra-Cinch™ Hook & Loop Cable Ties

| UGCT | E | 3 | S | X | 0 |
|---|-----------------------------------|---|----------------------------------|---------------------|--------------|
| <u>Type</u> | <u>Mount</u> | <u>Size</u> | <u>Cross Section</u> | <u>Package Size</u> | <u>Color</u> |
| UCT = Cinch Tie UGCT = Grommet Cinch Tie | E = End Mount C = Center Mount | Approx. Maximum Bundle Dia. (In) | I = Intermediate S = Standard | X = 10 | See below |

Color Chart

| Color | Panduit Suffix | Color | Panduit Suffix |
|--------|----------------|--------|----------------|
| Black | 0 | Blue | 6 |
| Red | 2 | Gray | 8 |
| Orange | 3 | White | 10 |
| Yellow | 4 | Maroon | 12 |
| Green | 5 | | |

Part Number Availability List

| Standard Packaging | |
|--------------------|-------------------------|
| Part Number | Color Suffix |
| HLB2S-C | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLC3S-X | 0 |
| HLC5S-X | 0 |
| HLM-15R | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS-15R | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS-75R | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS1.5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS3S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLS5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLSP1.5S-X | 0, 12 |
| HLSP3S-X | 0, 12 |
| HLSP5S-X | 0, 12 |
| HLT2I-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLT3I-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| HLTP2I-X | 0, 12 |
| HLTP3I-X | 0, 12 |
| HLWM1.5S-X | 0 |
| HLWM3S-X | 0 |
| TTS-20R | 0 |
| TTS-35RX | 0 |
| TTS-35R3 | 0 |
| UCT3S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UCT5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UGCTC3S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UGCTC5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UGCTE3S-X | 0, 2, 3, 4, 5, 6, 8, 10 |
| UGCTE5S-X | 0, 2, 3, 4, 5, 6, 8, 10 |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru