


#### FEATURES


- Standard 7.0mm x 5.0mm, 6-Pad Surface Mount Package
- **Low Phase Jitter, 0.5ps RMS Maximum**
- LVPECL or LVDS Output
- Fundamental and 3<sup>rd</sup> Overtone Crystal Designs
- Frequency Range 19.44 – 320 MHz
- Frequency Stability  $\pm 50$  ppm Standard
- Operating Voltages +2.5Vdc or +3.3Vdc
- Operating Temperature to -40°C to +85°C
- Output Enable Standard
- Tape & Reel Packaging Standard, EIA-418
- **RoHS/Green Compliant [6/6]**



#### APPLICATIONS

Model 637 is ideal for applications such as broadband access, SerDes, Ethernet/Gigabit Ethernet, SONET/SDH and optical networking.

#### ORDERING INFORMATION



1] Refer to document 016-1454-0, Frequency Code Tables.



3-digits required for frequencies below 100MHz and 4-digits for frequencies 100MHz or greater.

2] Consult factory for availability of 6I Stability/Temperature combination.

**Not all performance combinations and frequencies may be available.**  
**Contact your local CTS Representative or CTS Customer Service for availability.**

#### PACKAGING INFORMATION [reference]

Device quantity is 1k pcs. maximum per 180mm reel.




## ELECTRICAL CHARACTERISTICS

| ELECTRICAL PARAMETERS | PARAMETER                   | SYMBOL               | CONDITIONS                            | MIN                | TYP  | MAX                | UNIT  |
|-----------------------|-----------------------------|----------------------|---------------------------------------|--------------------|------|--------------------|-------|
|                       | Maximum Supply Voltage      | $V_{CC}$             | -                                     | -0.5               | -    | 5.0                | V     |
|                       | Storage Temperature         | $T_{STG}$            | -                                     | -40                | -    | +100               | °C    |
|                       | Frequency Range             | $f_0$                | -                                     | 19.44              | -    | 320                | MHz   |
|                       | LVPECL                      |                      |                                       |                    |      |                    |       |
|                       | LVDS                        |                      |                                       |                    |      |                    |       |
|                       | Frequency Stability         | $\Delta f/f_0$       | All Inclusive, see Note 1.            | -                  | -    | 20, 25, 50, 100    | ± ppm |
|                       |                             |                      | 1st year aging                        | -                  | -    | 3                  |       |
|                       | Operating Temperature       | $T_A$                | -                                     | -20                | 25   | +70                | °C    |
|                       | Commercial                  |                      |                                       |                    |      |                    |       |
|                       | Industrial                  |                      |                                       | -40                |      | +85                |       |
|                       | Supply Voltage              | $V_{CC}$             | ± 5 %                                 | 2.38               | 2.5  | 2.63               | V     |
|                       |                             |                      |                                       | 3.14               | 3.3  | 3.47               |       |
|                       | Supply Current              | $I_{CC}$             | Maximum Load                          | -                  | -    | 88                 | mA    |
|                       | LVPECL                      |                      |                                       |                    |      |                    |       |
|                       | LVDS                        |                      |                                       | -                  | -    | 65                 |       |
|                       | Start Up Time               | $T_S$                | Application of $V_{CC}$               | -                  | 2    | 5                  | ms    |
|                       | Phase Jitter                | $t_{jrms}$           | Bandwidth 12 kHz - 20 MHz             | -                  | 0.3  | 0.5                | ps    |
|                       | Period Jitter RMS           | $p_{jrms}$           | -                                     | -                  | 2.1  | -                  |       |
|                       | Period Jitter Pk-Pk         |                      | -                                     | -                  | 22   | -                  |       |
|                       | Enable Function             |                      | Standby                               |                    |      |                    | V     |
|                       | Enable Input Voltage        | $V_{IH}$             | Pin 1 or 2 Logic '1', Output Enabled  | $0.7 \cdot V_{CC}$ | -    | -                  |       |
|                       | Disable Input Voltage       | $V_{IL}$             | Pin 1 or 2 Logic '0', Output Disabled | -                  | -    | $0.3 \cdot V_{CC}$ |       |
|                       | Disable Time                | $T_{PLZ}$            | Pin 1 or 2 Logic '0', Output Disabled | -                  | -    | 200                | ns    |
|                       | Enable Time                 | $T_{PLZ}$            | Pin 1 or 2 Logic '1', Output Enabled  | -                  | -    | 2                  | ms    |
|                       | <b>LVPECL WAVEFORM</b>      |                      |                                       |                    |      |                    |       |
|                       | Output Load                 | $R_L$                | Terminated to $V_{CC} - 2.0V$         | -                  | 50   | -                  | Ohms  |
|                       | Output Duty Cycle           | SYM                  | @ $V_{CC} - 1.3V$                     | 45                 | -    | 55                 | %     |
|                       | Output Voltage Levels       | $V_{OH}$<br>$V_{OL}$ | PECL Load, -20°C to +70°C             | $V_{CC} - 1.025$   | -    | $V_{CC} - 0.880$   | V     |
|                       | Logic '1' Level             |                      | PECL Load, -20°C to +70°C             | $V_{CC} - 1.810$   | -    | $V_{CC} - 1.620$   |       |
|                       | Logic '0' Level             | $V_{OH}$<br>$V_{OL}$ | PECL Load, -40°C to +85°C             | $V_{CC} - 1.085$   | -    | $V_{CC} - 0.880$   | V     |
|                       | Logic '1' Level             |                      | PECL Load, -40°C to +85°C             | $V_{CC} - 1.830$   | -    | $V_{CC} - 1.555$   |       |
|                       | Logic '0' Level             |                      |                                       |                    |      |                    |       |
|                       | Rise and Fall Time          | $T_R, T_F$           | @ 20% - 80% Levels                    | -                  | 0.3  | 0.7                | ns    |
|                       | <b>LVDS WAVEFORM</b>        |                      |                                       |                    |      |                    |       |
|                       | Output Load                 | $R_L$                | Between Outputs                       | -                  | 100  | -                  | Ohms  |
|                       | Output Duty Cycle           | SYM                  | @ 1.25V                               | 45                 | -    | 55                 | %     |
|                       | Differential Output Voltage | $V_{OD}$             | $R_L = 100$ Ohms                      | 247                | 350  | 454                | mV    |
|                       | Offset Voltage              | $V_{OS}$             | LVDS Load                             | 1.125              | 1.25 | 1.375              | V     |
|                       | Output Voltage Levels       | $V_{OH}$<br>$V_{OL}$ | LVDS Load                             | -                  | 1.43 | 1.6                | V     |
|                       | Logic '1' Level             |                      | LVDS Load                             | 0.9                | 1.1  | -                  |       |
|                       | Logic '0' Level             |                      |                                       |                    |      |                    |       |
|                       | Rise and Fall Time          | $T_R, T_F$           | @ 20% - 80% Levels                    | -                  | 0.4  | 0.7                | ns    |

Notes:

1. Inclusive of initial tolerance at time of shipment, changes in supply voltage, load, temperature and 1st year aging.

### LVPECL/LVDS OUTPUT WAVEFORM




### ENABLE TRUTH TABLE

| PIN 1 or Pin 2 | PIN 4 & 5 |
|----------------|-----------|
| Logic '1'      | Output    |
| Open           | Output    |
| Logic '0'      | High Z    |

The diagram shows a test circuit for an op-amp. A power supply is connected to a milliammeter (mA) and a voltmeter (VM). The voltmeter is connected across the D.U.T. (Device Under Test). A 0.01uF capacitor is connected between the input and output of the D.U.T. The D.U.T. is connected to a load resistor (RL = 50 Ohms) and a Vcc = 2.0V source. The output is measured at CH1 and CH2.

The drawing shows the mechanical specifications of the CTS6370STV package. The top view is a rectangle with a width dimension of  $(7.0 \pm 0.2)$  and  $0.276 \pm 0.008$ . The side view shows a height dimension of  $(5.0 \pm 0.2)$  and  $0.197 \pm 0.008$ . The package is labeled with "CTS\*\*YYWW", "6370STV", and "• XXXX". The bottom view shows a package with four shaded rectangular areas representing solder pads, with a dimension of  $(2.0)$  and  $0.079$  MA.

C<sub>BYPASS</sub> should be  $\geq 0.01 \mu\text{F}$ .



1. \*\* - Manufacturing Site Code.
2. YYWW – Date code, YY – year, WW – week.
3. O – Output Type. P or E = LVPECL, L or V = LVDS.
4. ST – Frequency stability/temperature code.  
[Refer to Ordering Information.]
5. V – Voltage code. 3 = 3.3V, 2 = 2.5V
6. xxxx – Frequency Code.  
3-digits, frequencies below 100MHz  
4-digits, frequencies 100MHz or greater.

Refer to document 016-1454-0, Frequency Code Tables.

1. Complete CTS part number, frequency value and date code information must appear on reel and carton labels.
2. Termination pads [e4]. Barrier-plating is nickel [Ni] with gold [Au] flash plate.
3. Reflow conditions per JEDEC J-STD-020; 260°C maximum, 20 seconds.
4. MSL = 1.

| PIN | SYMBOL          | DESCRIPTION                |
|-----|-----------------|----------------------------|
| 1   | EOH or N.C.     | Enable [std] or No Connect |
| 2   | N.C. or EOH     | No Connect or Enable [opt] |
| 3   | GND             | Circuit & Package Ground   |
| 4   | Output          | RF Output                  |
| 5   | Output          | Complimentary RF Output    |
| 6   | V <sub>CC</sub> | Supply Voltage             |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)