

Type AXLH -40 °C to +150 °C

High Temperature Axial Leaded Aluminum Electrolytic Capacitors

HIGH PERFORMANCE AXIAL LEADED ALUMINUM ELECTROLYTIC CAPACITORS



Type AXLH capacitors are a new generation of high performance aluminum electrolytic capacitors rated up to 2000 hours at 150 °C. They are designed for applications that place high demands on a capacitor. The capacitor's outstanding features include low ESR, low leakage current, a long shelf life and a high ripple current capability.

Highlights

- 150 °C Operating Temperature
- Up to 28 Amps RMS Continuous Ripple Current
- Capacitance Range: 470 µF to 4700 µF
- High Vibration Resistance
- Very Long Shelf Life
- Low Leakage Current

Specifications

Capacitance Range (100 Hz/+20 °C)	470 to 4700 µF					
Capacitance Tolerance (100 Hz/+20 °C)	-10/+30%					
Rated Voltage	25, 40, 63 Vdc					
Operating Temperature	-40 °C to +150 °C					
Leakage Current (at 20°C)	I = 0.003 CV +4.0 µA; after 5 minutes at rated voltage I = leakage current in µAmps C = rated capacitance in µF V = rated DC Working voltage in Volts					
Ripple Current vs. Frequency Correction Factors	Frequency (Hz)	100	300	1000	5000	100 kHz
	Ripple Current Correction Factor	0.35	0.57	0.8	1	1.04
Shelf Life	(+105 °C/0 Vdc): 5000 hours (+40 °C/0 Vdc): 10 years					
Standard	IEC 60384-4 long life grade 40/125/56					
RoHS Compliant						

Part Numbering System

AXLH

Type

222

Capacitance

222 = 2200 µF

P

Capacitance Tolerance

P = -10/+30%

025

Voltage Code

025 = 25 Vdc

040 = 40 Vdc

063 = 63 Vdc

E

Case Dia.Code

E = 20 mm

D

Case

Length Code

D = 27 mm

H = 35 mm

L = 43 mm

Type AXLH -40 °C to +150 °C

High Temperature Axial Leaded Aluminum Electrolytic Capacitors

Load Life Test	Test	Mount the capacitor on a heat sink with a low thermal resistance path. Apply the maximum rated voltage for 2000 hrs at +150°C with the +150°C maximum ripple current applied to the capacitor. After the test, measure the capacitance, ESR, and DCL at +20°C.
	ΔC	Capacitance will be within ±15% of the initial value
	ESR	ESR will be less than 2 times the initial value
	DCL	The leakage current will be within the specified value
	Appearance	No electrolyte leakage or other visible damage. The markings will be legible.
Vibration Test	Test	Clamp the case to the test fixture. Frequency range is 10 - 2000 Hz. Amplitude of 1.5mm or 20 g acceleration. Duration of test is 22 hours in each of three directions. After the test, measure the capacitance at +20°C.
	ΔC	Capacitance change from the initial measurement must not exceed 5%.
	Appearance	No electrolyte leakage or other visible damage.
Surge Voltage Test	Test	Subject the capacitor to 1000 surge voltage cycles at +150°C. For each cycle, apply 1.15 times the rated voltage for 30 seconds followed by no voltage for 5 min. and 30 seconds. The time constant for charging is 0.1 seconds. After one to two hours, measure the capacitance and esr.
	ΔC	Capacitance change from the initial measurement must not exceed 15%.
	ESR	The ESR will be < 2x initial value.
	Appearance	No electrolyte leakage or other visible damage.
Storage at Low Temperature Test	Test	Subject the capacitor to 72 hours at -55°C. After 16 hours at room temperature, measure the capacitance and DCL.
	ΔC	Capacitance change from the initial measurement must not exceed 10%.
	DCL	Leakage current will meet the initial specification.
	Appearance	No electrolyte leakage or other visible damage. The markings are to be legible.
Charge and Discharge Test	Test	Subject the capacitor to 1 million charge/discharge cycles at +20°C. For each cycle, apply the rated voltage for 0.5 seconds using a 0.1 second charge/discharge time constant. After the test, the following will apply;
	ΔC	Capacitance will be within ±10% of the initial value.
	Appearance	No electrolyte leakage or other visible damage.


Type AXLH -40 °C to +150 °C

High Temperature Axial Leaded Aluminum Electrolytic Capacitors

Ratings

Rated Capacitance 100Hz/+20°C (μF)	Capacitance Tolerance (%)	VDC	Cornell Dubilier Part Number	Case Size D x L (mm)	Max. ESR 100 Hz/+20°C (mΩ)	Max. ESR 100 kHz/+20°C (mΩ)	Rated Ripple Current ≥ 5kHz/+125°C (A)	Maximum Ripple Current ≥ 5kHz/+125°C (A)
2200	-10/+30	25	AXLH222P025ED	20 x 27	50	25	7.1	9.1
3300	-10/+30	25	AXLH332P025EH	20 x 35	34	17	8.9	11.3
4700	-10/+30	25	AXLH472P025EL	20 x 43	25	13	10.3	13.1
1500	-10/+30	40	AXLH152P040ED	20 x 27	57	22	7.3	9.3
2200	-10/+30	40	AXLH222P040EH	20 x 35	41	17	8.9	11.2
2700	-10/+30	40	AXLH272P040EL	20 x 43	32	13	10.1	12.8
470	-10/+30	63	AXLH471P063ED	20 x 27	125	32	5.5	7.0
680	-10/+30	63	AXLH681P063EH	20 x 35	87	23	6.9	8.7
900	-10/+30	63	AXLH901P063EL	20 x 43	67	18	8.1	10.2

Outline Drawings & Dimensions Table



Size Code	Dimensions in mm				Approximate Weight (grams)
	D	L	d	LL	
	± 0.5	± 1	± 0.03	± 2	
ED	20	26.5	1	40	13
EH	20	34.5	1	40	20
EL	20	42.5	1	40	24

Note: Bend leads at least 3.5 mm from the case.

Type AXLH -40 °C to +150 °C

High Temperature Axial Leaded Aluminum Electrolytic Capacitors

Heat-Sinked Ratings

Cornell Dubilier Part Number	Max. ESR 5-100 kHz 125-150°C (mΩ)	Maximum Ripple Current *		
		≥ 5 kHz/+125°C (A)	≥ 5 kHz/+140°C (A)	≥ 5 kHz/+150°C (A)
AXLH222P025ED	10.6	22.2	14	6.3
AXLH332P025EH	7.8	25.8	16.3	7.3
AXLH472P025EL	6.4	28.5	18	8.1
AXLH152P040ED	10	22.8	14.4	6.5
AXLH222P040EH	7.9	25.7	16.2	7.3
AXLH272P040EL	6.7	27.9	17.6	7.9
AXLH471P063ED	17.5	17.3	10.9	4.9
AXLH681P063EH	13	20	12.7	5.7
AXLH901P063EL	10.6	22.2	14	6.3

* When the capacitor is mounted to a heat-sink using low thermal resistance path.

Capacitor Markings

Marking

-- CDM ++
AXLH222P025ED
2200 uF 25VDC
160603

Description

Logo, Polarity Marks
CDE Part Number
Capacitance, Rated Voltage (VDC)
Date Code (Year, Week), Batch Number

Notice and Disclaimer: All product drawings, descriptions, specifications, statements, information and data (collectively, the "Information") in this datasheet or other publication are subject to change. The customer is responsible for checking, confirming and verifying the extent to which the Information contained in this datasheet or other publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without any guarantee, warranty, representation or responsibility of any kind, expressed or implied. Statements of suitability for certain applications are based on the knowledge that the Cornell Dubilier company providing such statements ("Cornell Dubilier") has of operating conditions that such Cornell Dubilier company regards as typical for such applications, but are not intended to constitute any guarantee, warranty or representation regarding any such matter – and Cornell Dubilier specifically and expressly disclaims any guarantee, warranty or representation concerning the suitability for a specific customer application, use, storage, transportation, or operating environment. The Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by Cornell Dubilier with reference to the use of any Cornell Dubilier products is given gratis (unless otherwise specified by Cornell Dubilier), and Cornell Dubilier assumes no obligation or liability for the advice given or results obtained. Although Cornell Dubilier strives to apply the most stringent quality and safety standards regarding the design and manufacturing of its products, in light of the current state of the art, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards (such as installation of protective circuitry or redundancies or other appropriate protective measures) in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage. Although all product-related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated in such warnings, cautions and notes, or that other safety measures may not be required.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru