

PD-9001GR

Single-port Gigabit PoE Midspan, 802.3at Compliant



Overview


Microsemi's PD-9001GR is a single port, high-power solution for remote powering of current and emerging high power applications. Generating up to 30W, the PD-9001GR enables remote power for a new range of applications including 802.11n Access Points, pan-tilt-zoom (PTZ) cameras and video-phones. It complies to IEEE 802.3at PoE standard and is backward compatible to IEEE802.3af. It can power both existing 10/100Base-T network devices and emerging wireless 1000Base-T devices such as WiMAX and wireless IEEE 802.11n access points.

PD-9001GR Features

- IEEE 802.3at compliant with 2-event classification
- IEEE 802.3af backward compatible
- Output power of 30W is guaranteed
- Supports 10/100/1000Base-T applications
- Compatible with IEEE 802.3af devices
- Safe: low power devices receive only the power they need
- Automatic Detection and Protection of non-standard Ethernet terminals
- Compact design fits easily in WLAN Access Point and IP Cameras installations

Specifications

| Feature | Description |
|--------------------------------------|--|
| No. of Ports | 1 |
| Data Rates | 10/100/1000 Mbps |
| Power over Ethernet Output | Pin Assignment and Polarity: Spare Pairs 7/8 (-) and 4/5 (+) Output Power Voltage: 55 VDC User Port Power: 30W (Guaranteed) |
| Input Power Requirements | AC Input Voltage: 100 to 240Vac (±10%) AC Input Current: 0.67A @ 100-240Vac AC Frequency: 50 to 60Hz |
| Dimensions | 51.8mm (W) x 34.8mm (H) x 160.5mm (L) ±0.5mm 2.04 in. x 1.37 in. x 6.31 in ±0.02 in |
| Weight | .44 lbs (200g) |
| Indicators | User Indicator: Channel Power (Green) |
| Connectors | Shielded RJ-45, EIA 568A and 568B |
| Environmental Conditions | Operating Ambient Temperature: Conditions -4°F to 104°F (-20 °C to 40°C) @30W -4°F to 131°F (-20 °C to 55°C) @22.5W |
| Environmental Conditions Reliability | Operating Humidity: Maximum 90%, Non-condensing |
| | Storage Temperature: -4° to 158°F (-20° to 70°C) |
| | Storage Humidity: Maximum 95%, Non-condensing |
| | Operating Altitude: -1000 to 10,000 ft. (-304.8 to 3048 m) |
| | MTBF: 100,000 hrs. @ 25°C |
| Thermal Rating | 20 BTU/Hr (@240VAC) |
| Warranty | 1-year |
| Regulatory Compliance | IEEE 802.3af (PoE), RoHS Compliant, WEEE Compliant, CE |
| Electromagnetic Emission & Immunity | FCC Part 15, Class B EN 55032 Class B (Emissions) EN 55024 (Immunity) VCCI |
| Safety | UL/EN/IEC 60950-1 (Ed.2) |



PD-9001GR

Single-port Gigabit PoE Midspan, 802.3at Compliant

Ordering Information

| Microsemi p/n | Name | Description |
|-----------------|---------------------|---|
| PD-9001GR/AT/AC | Microsemi PD-9001GR | Single-port, Gigabit PoE Midspan, 802.3at Compliant |

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.



Microsemi Corporate Headquarters
One Enterprise, Aliso Viejo, CA 92656 USA
Within the USA: +1 (800) 713-4113
Outside the USA: +1 (949) 380-6100
Sales: +1 (949) 380-6136
Fax: +1 (949) 215-4996
email: sales.support@microsemi.com
www.microsemi.com

Microsemi Corporation (MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense & security, aerospace and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions, setting the world's standard for time; voice processing devices; RF solutions; discrete components; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, Calif., and has approximately 3,600 employees globally. Learn more at www.microsemi.com.

©2017 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru