



## Main

|                               |                                                 |
|-------------------------------|-------------------------------------------------|
| Range of product              | OsiSense XX                                     |
| Sensor type                   | Ultrasonic sensor                               |
| Series name                   | General purpose                                 |
| Sensor name                   | XX2                                             |
| Sensor design                 | Cylindrical M30                                 |
| Detection system              | Diffuse                                         |
| [Sn] nominal sensing distance | 6.56 ft (2 m) adjustable with teach push-button |
| Material                      | Plastic                                         |
| Type of output signal         | Discrete                                        |
| Discrete output function      | 2 NO                                            |
| Wiring technique              | 4-wire                                          |
| Discrete output type          | PNP                                             |
| [Us] rated supply voltage     | 12...24 V DC with reverse polarity protection   |
| Electrical connection         | Male connector M12 4 pins                       |
| Product specific application  | For 2 levels monitoring                         |
| [Sd] sensing range            | 0.39...6.56 ft (0.12...2 m)                     |
| Beam angle                    | 10 °                                            |
| IP degree of protection       | IP67 conforming to IEC 60529                    |

## Complementary

|                                                   |                                                                                                                                       |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Enclosure material                                | ULTEM                                                                                                                                 |
| Front material                                    | Silicone                                                                                                                              |
| Thread type                                       | M30 x 1.5                                                                                                                             |
| Supply voltage limits                             | 10...28 V DC                                                                                                                          |
| Function available                                | Without synchronisation mode                                                                                                          |
| [Sa] assured operating distance                   | 0.39...6.56 ft (0.12...2 m) (teach mode)                                                                                              |
| Maximum differential travel                       | 0.1 in (2.5 mm)                                                                                                                       |
| Blind zone                                        | 0...4.72 in (0...120 mm)                                                                                                              |
| Transmission frequency                            | 200 kHz                                                                                                                               |
| Repeat accuracy                                   | 0.9 %                                                                                                                                 |
| Deviation angle from 90° of object to be detected | -10...10 °                                                                                                                            |
| Minimum size of detected object                   | Cylinder diameter 1.6 mm at 0.635 m                                                                                                   |
| Status LED                                        | 1 LED (green/red (flashing)) output state<br>1 LED (green/red (flashing)) setting-up assistance<br>1 LED (yellow) distance indication |
| Current consumption                               | 100 mA                                                                                                                                |
| Maximum switching current                         | 100 mA with overload and short-circuit protection                                                                                     |
| Voltage drop                                      | < 1 V                                                                                                                                 |
| Delay first up                                    | 1000 ms                                                                                                                               |
| Delay response                                    | 150 ms                                                                                                                                |
| Delay recovery                                    | 1000 ms                                                                                                                               |
| Marking                                           | CE                                                                                                                                    |
| Threaded length                                   | 1.77 in (45 mm)                                                                                                                       |
| Height                                            | 1.38 in (35 mm)                                                                                                                       |
| Width                                             | 1.38 in (35 mm)                                                                                                                       |
| Depth                                             | 3.35 in (85 mm)                                                                                                                       |
| Product weight                                    | 0.2 lb(US) (0.091 kg)                                                                                                                 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

|                                       |                                                        |
|---------------------------------------|--------------------------------------------------------|
| standards                             | IEC 60947-5-2                                          |
| product certifications                | CCSAus<br>UL                                           |
| ambient air temperature for operation | 32...122 °F (0...50 °C)                                |
| ambient air temperature for storage   | 14...176 °F (-10...80 °C)                              |
| vibration resistance                  | +/-1 mm conforming to IEC 60068-2-6 10...55 Hz         |
| shock resistance                      | 30 gn in all 3 axes 11 ms conforming to IEC 60068-2-27 |
| resistance to electrostatic discharge | 8 kV level 4 conforming to IEC 61000-4-2               |
| resistance to electromagnetic fields  | 9.14 V/yd (10 V/m) level 3 conforming to IEC 61000-4-3 |
| resistance to fast transients         | 1 kV level 3 conforming to IEC 61000-4-4               |


Offer Sustainability

|                                                                                                                            |                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Not Green Premium product                                                                                                  | Not Green Premium product                                                                                                  |
| Compliant - since 0836 - Schneider Electric declaration of conformity                                                      | Compliant - since 0836 - Schneider Electric declaration of conformity                                                      |
| Reference contains SVHC above the threshold - go to CaP for more details                                                   | Reference contains SVHC above the threshold                                                                                |
| Available                                                                                                                  | Available                                                                                                                  |
| WARNING: This product can expose you to chemicals including:                                                               | WARNING: This product can expose you to chemicals including:                                                               |
| Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |
| Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                              |

Contractual warranty


|                 |           |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|

Dimensions




Minimum Mounting Distances

Side by side



e : respect the distances indicated on the detection curves


Face to face



e > 4 x Sn

Wiring Diagram

NO + NO outputs, PNP



- (1) (+) Brown
- (2) NO output (White)
- (3) (-) Blue
- (4) NO output (Black)


BN Brown

WH White

BU Blue


BK Black

## Curves



- (1) Parallel movement
- (2) Distance
- (3) Blind zone for diffuse sensors.

## Operating Curves



- (1) Adjustable detection zone
- (2) Output pin 4 BK
- (3) Output pin 2 WH

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)