

# LTC7149

## 60V, Low IQ High Voltage, Negative Output Monolithic Synchronous Regulator

### DESCRIPTION

Demonstration circuit 2354A is a high input voltage, high efficiency synchronous monolithic step-down converter with negative output featuring the LTC7149. The DC2354A has wide input voltage range from 3.5V up to 55V. The output voltage of the DC2354A can be set as to  $-3.3V$  or  $-5V$  and “User Select” option of DC2354A allows output voltage to be in a range from 0V to  $-60V$ . However voltage difference between user-selected negative output voltage ( $-V_{OUT}$ ) and maximum input voltage ( $V_{IN}$ ), should not exceed 60V.  $|-V_{OUT}| + V_{IN} < 60V$ . DC2354A is capable of delivering up to 4A of output current, nevertheless at lower input voltage load current should be reduced in accordance to enclosed derating curves. DC2354A supports three operation modes: Fixed-frequency modulation, Burst Mode™ operation and user can synchronize it with external clock also. Fixed-frequency mode of operation maximizes the output current, reduces output voltage ripple, and yields a low noise switching spectrum. Burst Mode operation employs a variable frequency switching algorithm that minimizes the no-load input quiescent current and improves efficiency at light loads.

The DC2354A consumes less than  $15\mu A$  of quiescent current during shutdown and it consumes less than  $600\mu A$  at no-load conditions in Burst Mode of operation. The DC2354A has a standard operating frequency of 500kHz, but can be adjusted in a range between 300kHz and as high as 3MHz. LTC7149, which is used in DC2354A, integrates top and bottom N-Channel MOSFETs, significantly reducing overall circuit footprint. DC2354A was designed to support multiple footprints of input/output capacitors and inductors to accommodate variety of applications. The data sheet of LTC7149 gives a complete description functionality of this regulator; also contains operation and application information and must be read in conjunction with this manual for Demonstration circuit 2354A.

**Design files for this circuit board are available at <http://www.linear.com/demo/DC2354A>**

LT, LT, LTC, LTM, Linear Technology, the Linear logo and Burst Mode are registered trademarks of Linear Technology Corporation. All other trademarks are the property of their respective owners.

### PERFORMANCE SUMMARY Specifications are at $T_A = 25^\circ C$

PARAMETER	CONDITIONS/NOTES	VALUE
Minimum Input Voltage		3.5V
Maximum Input Voltage		55V
Output Voltage $V_{OUT}^-$ Regulation	$V_{IN} = 3.5V - 60V$	$-5V \pm 2\%$ or $-3.3V \pm 2\%$
Maximum Continuous Output Current	$V_{OUT}^-$	4A
Preset Operating Frequency	$R10 = 200k\Omega$	500kHz
External Clock Sync. Frequency Range		300kHz – 3MHz
Efficiency	$V_{IN} = 12V, V_{OUT}^- = -5V, I_{OUT} = 1A$ $V_{IN} = 12V, V_{OUT}^- = -3.3V, I_{OUT} = 1A$	90% 90%
Typical Output Ripple $V_{OUT}^-$	$V_{IN} = 12V, V_{OUT}^- = -5V, I_{OUT} = 1A$ (20MHz BW)	$<15mV_{P-P}$
Quiescent Current at Shutdown	$V_{IN} = 3.5V - 55V$	$<14\mu A$
Input Current at No-Load	$V_{IN} = 3.5V - 55V$ , Burst Mode Operation	$<600\mu A$

## QUICK START PROCEDURE

Demonstration circuit 2354A is easy to set up to evaluate the performance of the LTC7149. For proper measurement equipment configuration, set up the circuit according to the diagram in Figure 1. Before proceeding to test, insert shunt into JP2 (RUN) into OFF position, which connects the RUN pin to ground (GND), and thus, shutdown the output. Set jumper JP1 (MODE) into FCC (Forced Countries Conduction Mode) position. Set jumper JP3 ( $V_{OUT^-}$ ) into  $-5.0V$  position.

NOTE: When measuring the input or output voltage ripple, care must be taken to avoid a long ground lead on the oscilloscope probe. Measure the input or output voltage ripple by touching the probe tip directly across the  $V_{IN}$  or  $V_{OUT^-}$  and GND terminals. See Figure 2 for proper scope probe technique.

1. With the DC2354A set up according to the proper measurement and equipment in Figure 1, apply 16V at  $V_{IN}$ . Measure  $V_{OUT^-}$ ; it should read 0V. If desired, one can measure the shutdown supply current at this point. The supply current will be approximately 14 $\mu$ A, or less, in shutdown.
2. Turn on  $V_{OUT^-}$  of the circuit by inserting the shunt in header JP2 (RUN) into the ON position. The output voltage should be regulating. Measure  $V_{OUT^-}$  and it should measure  $-5.0V \pm 2\%$ . Vary the current load, which should not exceed 4A. Vary the input voltage from 3.5V to 55V, the  $V_{OUT^-}$ , it should measure  $-5.0V \pm 2\%$ . Maximum load current is function of input voltage and should be changed accordance to derating graphs on Figure 3.

3. Set JP2 (RUN) into OFF and then jumper JP3 ( $V_{OUT^-}$ ) into  $-3.3V$  position.
4. Turn on  $V_{OUT2}$  of the circuit by inserting the shunt in header JP2 (RUN) into the ON position. The output voltage should be regulating. Measure  $V_{OUT^-}$ , it should measure  $-3.3V \pm 2\%$  (do not apply more than the maximum voltage of 55V to the board or the part may be damaged). Vary the current load, which should not exceed 4A. Vary the input voltage from 3.5V to 55V, the  $V_{OUT^-}$ , it should measure  $-3.3V \pm 2\%$ .
5. Set output current to zero and move jumper JP1 (MODE) into BURST position and measure  $V_{OUT^-}$ , which should be  $-3.3V \pm 2\%$ .
6. Set output current to zero and move jumper JP1 (MODE) into BURST position and measure  $V_{OUT^-}$ , which should be  $-5V \pm 2\%$ .

DC2354A supports synchronization to external clock referenced to input GND; use EXT\_SYNC terminal for synchronization. PGOOD signal also referenced to input GND, to activate PGOOD functionality connect external voltage source to terminals VLOGIC and GND. DC2354A supports also EXTV<sub>CC</sub> function, however, EXTV<sub>CC</sub> is referenced to  $V_{OUT^-}$ . Remove R5 and install optional R33 10 $\Omega$  resistor if external EXTV<sub>CC</sub> voltage source is used.

**Note:** Do not apply more than the maximum voltage of 55V to the board or the part may be damaged.

# QUICK START PROCEDURE




Figure 1. Proper Measurement Equipment Setup

## QUICK START PROCEDURE




Figure 2. Measuring Input or Output Ripple




Figure 3. Output Current vs. Input Voltage Derating Charts




Figure 4. Efficiency vs. Load Current for Different Input Voltages

**QUICK START PROCEDURE**





Figure 5. Thermal Map,  $V_{IN}$  48V,  $V_{OUT^-}$  is -5V at 3.5A, No Air Flow

# DEMO MANUAL DC2354A

## PARTS LIST

QTY	REFERENCE	PART DESCRIPTION	MANUFACTURER/PART NUMBER
<b>Required Circuit Components</b>			
1	CIN1	CAP, 1210 2.2 $\mu$ F 10% 100V X7R	TDK C3225C7R1H225K
1	CIN2	CAP, 1210 10 $\mu$ F 10% 63V X7R	MURATA GRM32ER71J106KA12K
1	CIN3	CAP, 10 $\mu$ F 20% 63V ELEC	PANASONIC EEH-ZA1J100P
1	CIN4	CAP, 0805 1 $\mu$ F 10% 100V X7S	TDK C2012X7S2A105K125AB
2	COUT1, COUT2	CAP, 1210 22 $\mu$ F 10% 25V X7R	MURATA GRM32ER71E226KE15L
1	COUT3	CAP, X7R, 22 $\mu$ F, 25V, 1812	TDK, C4532X7R1E226M250KC
1	CTH	CAP, 0603 10nF 10% 50V X7R	AVX 06035A221KAT
1	CTHP	CAP, 0603, 220pF, 10%, 50V, NPO	AVX 06031A101KAT2A
1	CVCC	CAP, 0805 2.2 $\mu$ F 10% 16V X7R	AVX 0805YC225KAT2A
2	C1, C6	CAP, 0603 0.1 $\mu$ F 10% 50V X7R	TDK C1608X7R1H104K080AA
1	C5	CAP, 0603 1 $\mu$ F 20% 25V X7R	TDK C1608X7R1E105M080AB
1	L1	IND, 5.6 $\mu$ H	COILCRAFT XAL5050-562MEB
1	RTH	RES, 0603 511 $\Omega$ 1% 1/10W	VISHAY CRCW0603511RFKEA
2	R1, R13	RES, 0603 100k $\Omega$ 1% 1/10W	VISHAY CRCW0603100KFKEA
1	R2	RES, 0603 10M $\Omega$ 1% 1/10W	VISHAY CRCW060310M0FKEA
1	R5	RES, 0603 10 $\Omega$ 1% 0.1W	VISHAY CRCW060310RFKEA
2	R3, R4	RES, 0603 0 $\Omega$ JUMPER	VISHAY CRCW06030000Z0EA
1	R10	RES, 0603 200k $\Omega$ 1% 1/10W	VISHAY CRCW0603200KFKEA
1	R18	RES, 0805 1M $\Omega$ 1% 1/8W	VISHAY CRCW08051M00FKEA
1	R25	RES, 0603 137k $\Omega$ 1% 0.063W	VISHAY CRCW0603137KFKEA
1	R26	RES, 0603 1M $\Omega$ 1% 1/10W	VISHAY CRCW06031M00FKEA
1	R29	RES, 0603 196k $\Omega$ 1% 1/10W	VISHAY CRCW0603196KFKEA
1	R31	RES, 0603 20 $\Omega$ 1% 0.1W	VISHAY CRCW060320R0FKEA
1	R32	RES, 0603 100 $\Omega$ 1% 0.1W	VISHAY CRCW0603100RFKEA
1	U1	IC, NEGATIVE OUTPUT REGULATOR	LINEAR TECH. LTC7149EFE28#PBF
<b>Additional Demo Board Circuit Components</b>			
	R19, R27, R30, R33	RES, 0603 OPTION	OPTION
	C3, C4	CAP, 0603 OPTION	OPTION
	CIN5	CAP, OPTION	OPTION
<b>Hardware</b>			
12	E1, E2, E3, E4, E5, E6, E7, E9, E12, E13, E14, E15	TURRET	MILL MAX 2501-2-00-80-00-00-07-0
3	JP1, JP2, JP3	HEADER, 3-PIN, DBL ROW 2mm	SULLINS, NRPN032PAEN
4	MH1, MH2, MH3, MH4	STANDOFF, SNAP ON	KEYSTONE 8833
3	XJP1, XJP2, XJP3	SHUNT	SAMTEC 2SN-BK-G

SCHEMATIC DIAGRAM



REVISION HISTORY			
ECO	REV	DESCRIPTION	DATE
-	3.1	PROD	01/04/16

APPROVALS	
PCB DES:	<i>SMX</i>
APP ENG:	<i>QJP</i>

<p><b>CUSTOMER NOTICE</b>                  LINEAR TECHNOLOGY HAS MADE A BEST EFFORT TO DESIGN A CIRCUIT THAT MEETS CUSTOMER-SUPPLIED SPECIFICATIONS; HOWEVER, IT REMAINS THE CUSTOMER'S RESPONSIBILITY TO VERIFY THAT THE CIRCUIT MEETS ALL APPLICATION, COMPONENT SUBSTITUTION AND PRINTED CIRCUIT BOARD LAYOUT MAY SIGNIFICANTLY AFFECT CIRCUIT PERFORMANCE OR RELIABILITY. CONTACT LINEAR TECHNOLOGY APPLICATIONS ENGINEERING FOR ASSISTANCE.</p>	
<p>THIS CIRCUIT IS PROPRIETARY TO LINEAR TECHNOLOGY AND SUPPLIED FOR USE WITH LINEAR TECHNOLOGY PARTS.</p>	

<p>1630 McCarthy Blvd.                  Milpitas, CA 95035                  Phone: (408)432-1900                  Fax: (408)434-0507                  LTC CONFIDENTIAL - FOR CUSTOMER USE ONLY</p>	
<p><b>LINEAR TECHNOLOGY</b></p>	
<p>TITLE: SCHEMATIC                  HIGH VOLTAGE, NEGATIVE OUTPUT MONOLITHIC SYNCHRONOUS REGULATOR</p>	
SIZE	N/A
IC NO.	LTC149EFE28
REV.	3.1
DATE:	Monday, March 28, 2016
SCALE = NONE	
SHEET 1	OF 1

- NOTES: UNLESS OTHERWISE SPECIFIED,  
 1. ALL CAPACITORS AND RESISTORS ARE 0603.  
 2. ALL RESISTORS ARE 5%.

# DEMO MANUAL DC2354A

---

## DEMONSTRATION BOARD IMPORTANT NOTICE

Linear Technology Corporation (LTC) provides the enclosed product(s) under the following **AS IS** conditions:

This demonstration board (DEMO BOARD) kit being sold or provided by Linear Technology is intended for use for **ENGINEERING DEVELOPMENT OR EVALUATION PURPOSES ONLY** and is not provided by LTC for commercial use. As such, the DEMO BOARD herein may not be complete in terms of required design-, marketing-, and/or manufacturing-related protective considerations, including but not limited to product safety measures typically found in finished commercial goods. As a prototype, this product does not fall within the scope of the European Union directive on electromagnetic compatibility and therefore may or may not meet the technical requirements of the directive, or other regulations.

If this evaluation kit does not meet the specifications recited in the DEMO BOARD manual the kit may be returned within 30 days from the date of delivery for a full refund. **THE FOREGOING WARRANTY IS THE EXCLUSIVE WARRANTY MADE BY THE SELLER TO BUYER AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE. EXCEPT TO THE EXTENT OF THIS INDEMNITY, NEITHER PARTY SHALL BE LIABLE TO THE OTHER FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.**

The user assumes all responsibility and liability for proper and safe handling of the goods. Further, the user releases LTC from all claims arising from the handling or use of the goods. Due to the open construction of the product, it is the user's responsibility to take any and all appropriate precautions with regard to electrostatic discharge. Also be aware that the products herein may not be regulatory compliant or agency certified (FCC, UL, CE, etc.).

No License is granted under any patent right or other intellectual property whatsoever. **LTC assumes no liability for applications assistance, customer product design, software performance, or infringement of patents or any other intellectual property rights of any kind.**

LTC currently services a variety of customers for products around the world, and therefore this transaction **is not exclusive**.

**Please read the DEMO BOARD manual prior to handling the product.** Persons handling this product must have electronics training and observe good laboratory practice standards. **Common sense is encouraged.**

This notice contains important safety information about temperatures and voltages. For further safety concerns, please contact a LTC application engineer.

Mailing Address:

Linear Technology  
1630 McCarthy Blvd.  
Milpitas, CA 95035

Copyright © 2004, Linear Technology Corporation

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)  
Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)