

Type TDC Solid Tantalum Capacitors

Dipped, Radial Leaded, Solid Tantalum Capacitors



As a low cost alternative to molded solid tantalum capacitors, the Type TDC, constructed in a tough, radial dipped flame retardant plastic case, assures the user that it is a top performer with such attributes as low DCL, low ESR, low impedance and a great value with low in-place cost. The Type TDC is high shock and vibration resistant and is available in bulk or on radial tape and reel.

Highlights

- ◆ Tough plastic case
- ◆ Low DCL
- ◆ Low ESR and impedance
- ◆ Low cost
- ◆ Temperature stable
- ◆ UL94VO flammability rating
- ◆ Resistant to shock and vibration

Specifications

Capacitance Range: 0.10 μ F to 330 μ F
Voltage Range: 6 WVdc to 50 WVdc at 85 °C
Tolerance: \pm 10%, \pm 20%
Operating Temperature Range: -55 °C to +125 °C (with proper derating)

DC Leakage: +25 °C - See ratings limit
+85 °C - 10 x ratings limit
+125 °C - 12.5 x ratings limit

Capacitance Change Maximum: -10% @ -55 °C
+10% @ +85 °C
+12% @ +125 °C

Reverse Voltage (Non-continuous): 15% of rated voltage @ 25 °C
5% of rated voltage @ 85 °C
1% of rated voltage @ 125 °C

Reel Packaging:

Case Code	Quantity per Reel
E	1,000
F	1,000
G	1,000



Complies with the EU Directive 2002/95/EC requirement restricting the use of Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent chromium (Cr(VI)), PolyBrominated Biphenyls (PBB) and PolyBrominated Diphenyl Ethers (PBDE).

Type TDC Solid Tantalum Capacitors

Capacitor Outline Drawing



Dimensions - Inches (Millimeters)				
Case Code	D (Max.)	H (Max.)	Leads	
			S	Code
E	.175 (4.45)	.350 (8.89)	.125 (3.17) (Standard)	N
			.250 (6.35) (Special)	W
F	.250 (6.35)	.500 (12.7)	.125 (3.17) (Standard)	N
			.250 (6.35) (Special)	W
G	.350 (8.89)	.650 (16.51)	.250 (6.35) (Special)	W

E and F Case Codes:
Lead Spacing = $.125 \pm .025$
(3.17 ± .64)

G Case Code:
Lead Spacing = $.250 \pm .025$
(6.34 ± .64)

Ratings

Cap (µF)	Catalog Part Number	Case Code	Lead Spacing (S)	Max. DCL @ +25 °C (µA)	Max. DF @ +25 °C 120 Hz (%)	Cap (µF)	Catalog Part Number	Case Code	Lead Spacing (S)	Max. DCL @ +25 °C (µA)	Max. DF @ +25 °C 120 Hz (%)
6 WVdc; 8 Vdc Surge @ 85 °C						10 WVdc; 13 Vdc Surge @ 85 °C					
4 WVdc; 5 Vdc Surge @ 125 °C						7 WVdc; 9 Vdc Surge @ 125 °C					
3.3	TDC335*006NSE-F	E	0.125	0.5	5	2.2	TDC225*010NSE-F	E	0.125	0.5	5
3.9	TDC395*006NSE-F	E	0.125	0.5	5	2.7	TDC275*010NSE-F	E	0.125	0.5	5
4.7	TDC475*006NSE-F	E	0.125	0.5	5	3.3	TDC335*010NSE-F	E	0.125	0.5	5
5.6	TDC565*006NSE-F	E	0.125	0.5	5	3.9	TDC395*010NSE-F	E	0.125	0.5	5
6.8	TDC685*006NSE-F	E	0.125	0.5	5	4.7	TDC475*010NSE-F	E	0.125	0.5	5
8.2	TDC825*006NSE-F	E	0.125	0.5	6	5.6	TDC565*010NSE-F	E	0.125	0.5	5
10	TDC106*006NSE-F	E	0.125	0.5	6	6.8	TDC685*010NSE-F	E	0.125	0.5	5
12	TDC126*006NSE-F	E	0.125	0.6	6	8.2	TDC825*010NSE-F	E	0.125	0.7	6
15	TDC156*006NSF-F	F	0.125	0.7	6	10	TDC106*010NSF-F	F	0.125	0.8	6
18	TDC186*006NSF-F	F	0.125	0.9	6	12	TDC126*010NSF-F	F	0.125	1.0	6
22	TDC226*006NSF-F	F	0.125	1.1	6	15	TDC156*010NSF-F	F	0.125	1.2	6
27	TDC276*006NSF-F	F	0.125	1.3	6	18	TDC186*010NSF-F	F	0.125	1.4	6
33	TDC336*006NSF-F	F	0.125	1.6	6	22	TDC226*010NSF-F	F	0.125	1.8	6
39	TDC396*006NSF-F	F	0.125	1.9	6	27	TDC276*010NSF-F	F	0.125	2.2	6
47	TDC476*006NSF-F	F	0.125	2.3	6	33	TDC336*010NSF-F	F	0.125	2.6	6
56	TDC566*006NSF-F	F	0.125	2.7	6	39	TDC396*010NSF-F	F	0.125	3.1	6
68	TDC686*006NSF-F	F	0.125	3.3	6	47	TDC476*010NSF-F	F	0.125	3.8	6
82	TDC826*006NSF-F	F	0.125	3.9	8	56	TDC566*010NSF-F	F	0.125	4.5	6
100	TDC107*006NSF-F	F	0.125	4.8	8	68	TDC686*010NSF-F	F	0.125	5.4	6
120	TDC127*006WSG-F	G	0.25	5.8	8	82	TDC826*010WSG-F	G	0.25	6.6	8
150	TDC157*006WSG-F	G	0.25	7.2	8	100	TDC107*010WSG-F	G	0.25	8.0	8
180	TDC187*006WSG-F	G	0.25	8.6	8	120	TDC127*010WSG-F	G	0.25	9.6	8
220	TDC227*006WSG-F	G	0.25	10	8	150	TDC157*010WSG-F	G	0.25	10.0	8
270	TDC277*006WSG-F	G	0.25	10	8	180	TDC187*010WSG-F	G	0.25	10.0	8
330	TDC337*006WSG-F	G	0.25	10	8	220	TDC227*010WSG-F	G	0.25	10.0	8

* Indicates capacitance tolerance: K = ±10%, M = ±20%, (J = ±5%, Special Order)

CDE reserves the right to substitute a tighter tolerance, higher voltage capacitor within the same case size.

Type TDC Solid Tantalum Capacitors

Ratings

Cap (μ F)	Catalog Part Number	Case Code	Lead Spacing (S)	Max. DCL @ +25 °C (μ A)	Max. DF @ +25 °C 120 Hz (%)	Cap (μ F)	Catalog Part Number	Case Code	Lead Spacing (S)	Max. DCL @ +25 °C (μ A)	Max. DF @ +25 °C 120 Hz (%)
16 WVdc; 20 Vdc Surge @ 85 °C						20 WVdc; 26 Vdc Surge @ 85 °C					
10 WVdc; 12 Vdc Surge @ 125 °C						13 WVdc; 16 Vdc Surge @ 125 °C					
1.5	TDC155*016NSE-F	E	0.125	0.5	5	8.2	TDC825*020NSF-F	F	0.125	1.3	6
1.8	TDC185*016NSE-F	E	0.125	0.5	5	10	TDC106*020NSF-F	F	0.125	1.6	6
2.2	TDC225*016NSE-F	E	0.125	0.5	5	12	TDC126*020NSF-F	F	0.125	1.9	6
2.7	TDC275*016NSE-F	E	0.125	0.5	5	15	TDC156*020NSF-F	F	0.125	2.4	6
3.3	TDC335*016NSE-F	E	0.125	0.5	5	18	TDC186*020NSF-F	F	0.125	2.9	6
3.9	TDC395*016NSE-F	E	0.125	0.5	5	22	TDC226*020NSF-F	F	0.125	3.5	6
4.7	TDC475*016NSE-F	E	0.125	0.6	5	33	TDC336*020WSG-F	G	0.25	5.3	6
5.6	TDC565*016NSE-F	E	0.125	0.7	5	39	TDC396*020WSG-F	G	0.25	6.2	6
6.8	TDC685*016NSE-F	E	0.125	0.9	5	47	TDC476*020WSG-F	G	0.25	7.5	6
8.2	TDC825*016NSE-F	E	0.125	1.0	6	56	TDC566*020WSG-F	G	0.25	9.0	6
10	TDC106*016NSF-F	F	0.125	1.3	6	68	TDC686*020WSG-F	G	0.25	10.0	6
12	TDC126*016NSF-F	F	0.125	1.5	6	82	TDC826*020WSG-F	G	0.25	10.0	8
15	TDC156*016NSF-F	F	0.125	1.8	6	100	TDC107*020WSG-F	G	0.25	10.0	8
18	TDC186*016NSF-F	F	0.125	2.2	6	25 WVdc; 32 Vdc Surge @ 85 °C					
22	TDC226*016NSF-F	F	0.125	2.6	6	17 WVdc; 22 Vdc Surge @ 125 °C					
27	TDC276*016NSF-F	F	0.125	3.2	6	1.0	TDC105*025NSE-F	E	0.125	0.50	3
33	TDC336*016NSF-F	F	0.125	4.0	6	1.2	TDC125*025NSE-F	E	0.125	0.50	5
39	TDC396*016WSG-F	G	0.25	4.7	6	1.5	TDC155*025NSE-F	E	0.125	0.50	5
47	TDC476*016WSG-F	G	0.25	5.6	6	1.8	TDC185*025NSE-F	E	0.125	0.50	5
56	TDC566*016WSG-F	G	0.25	6.8	6	2.2	TDC225*025NSE-F	E	0.125	0.50	5
68	TDC686*016WSG-F	G	0.25	8.2	6	2.7	TDC275*025NSE-F	E	0.125	0.50	5
82	TDC826*016WSG-F	G	0.25	9.8	8	3.3	TDC335*025NSE-F	E	0.125	0.70	5
100	TDC107*016WSG-F	G	0.25	10.0	8	3.9	TDC395*025NSE-F	E	0.125	0.80	5
120	TDC127*016WSG-F	G	0.25	10.0	8	4.7	TDC475*025NSF-F	F	0.125	0.90	5
150	TDC157*016WSG-F	G	0.25	10.0	8	5.6	TDC565*025NSF-F	F	0.125	1.10	5
20 WVdc; 26 Vdc Surge @ 85 °C						6.8	TDC685*025NSF-F	F	0.125	1.40	5
13 WVdc; 16 Vdc Surge @ 125 °C						8.2	TDC825*025NSF-F	F	0.125	1.60	6
1.0	TDC105*020NSE-F	E	0.125	0.5	3	10	TDC106*025NSF--F	F	0.125	2.0	6
1.2	TDC125*020NSE-F	E	0.125	0.5	5	12	TDC126*025NSF-F	F	0.125	2.4	6
1.5	TDC155*020NSE-F	E	0.125	0.5	5	15	TDC156*025NSF-F	F	0.125	3.0	6
1.8	TDC185*020NSE-F	E	0.125	0.5	5	18	TDC186*025NSF-F	F	0.125	3.6	6
2.2	TDC225*020NSE-F	E	0.125	0.5	5	22	TDC226*025NSF-F	F	0.125	4.4	6
2.7	TDC275*020NSE-F	E	0.125	0.5	5	27	TDC276*025WSG-F	G	0.250	5.4	6
3.3	TDC335*020NSE-F	E	0.125	0.5	5	33	TDC336*025WSG-F	G	0.250	6.6	6
3.9	TDC395*020NSE-F	E	0.125	0.6	5	39	TDC396*025WSG-F	G	0.250	7.8	6
4.7	TDC475*020NSE-F	E	0.125	0.8	5	47	TDC476*025WSG-F	G	0.250	9.4	6
5.6	TDC565*020NSF-F	F	0.125	0.9	5	56	TDC566*025WSG-F	G	0.250	10.0	6
6.8	TDC685*020NSF-F	F	0.125	1.1	5	68	TDC686*025WSG-F	G	0.250	10.0	6

* Indicates capacitance tolerance: K = $\pm 10\%$, M = $\pm 20\%$, (J = $\pm 5\%$, Special Order)

CDE reserves the right to substitute a tighter tolerance, higher voltage capacitor within the same case size.

Type TDC Solid Tantalum Capacitors

Ratings

Cap (μ F)	Catalog Part Number	Case Code	Lead Spacing (S)	Max. DCL @ +25 °C (μ A)	Max. DF @ +25 °C 120 Hz (%)	Cap (μ F)	Catalog Part Number	Case Code	Lead Spacing (S)	Max. DCL @ +25 °C (μ A)	Max. DF @ +25 °C 120 Hz (%)
35 WVdc; 46 Vdc Surge @ 85 °C 23 WVdc; 28 Vdc Surge @ 125 °C						50 WVdc; 65 Vdc Surge @ 85 °C 33 WVdc; 40 Vdc Surge @ 125 °C					
0.10	TDC104*035NSE-F	E	0.125	0.5	3	.10	TDC104*050NSE-F	E	0.125	0.5	3
0.12	TDC124*035NSE-F	E	0.125	0.5	3	.12	TDC124*050NSE-F	E	0.125	0.5	3
0.15	TDC154*035NSE-F	E	0.125	0.5	3	.15	TDC154*050NSE-F	E	0.125	0.5	3
0.18	TDC184*035NSE-F	E	0.125	0.5	3	.18	TDC184*050NSE-F	E	0.125	0.5	3
0.22	TDC224*035NSE-F	E	0.125	0.5	3	.22	TDC224*050NSE-F	E	0.125	0.5	3
0.27	TDC274*035NSE-F	E	0.125	0.5	3	.27	TDC274*050NSE-F	E	0.125	0.5	3
0.33	TDC334*035NSE-F	E	0.125	0.5	3	.33	TDC334*050NSE-F	E	0.125	0.5	3
0.39	TDC394*035NSE-F	E	0.125	0.5	3	.39	TDC394*050NSE-F	E	0.125	0.5	3
0.47	TDC474*035NSE-F	E	0.125	0.5	3	.47	TDC474*050NSE-F	E	0.125	0.5	3
0.56	TDC564*035NSE-F	E	0.125	0.5	3	.56	TDC564*050NSE-F	E	0.125	0.5	3
0.68	TDC684*035NSE-F	E	0.125	0.5	3	.68	TDC684*050NSE-F	E	0.125	0.5	3
0.82	TDC824*035NSE-F	E	0.125	0.5	3	.82	TDC824*050NSE-F	E	0.125	0.5	3
1.0	TDC105*035NSE-F	E	0.125	0.5	3	1.0	TDC105*050NSE-F	E	0.125	0.5	3
1.2	TDC125*035NSE-F	E	0.125	0.5	5	1.2	TDC125*050NSE-F	E	0.125	0.5	5
1.5	TDC155*035NSE-F	E	0.125	0.5	5	1.5	TDC155*050NSE-F	E	0.125	0.6	5
1.8	TDC185*035NSE--F	E	0.125	0.5	5	1.8	TDC185*050NSF-F	F	0.125	0.7	5
2.2	TDC225*035NSE-F	E	0.125	0.6	5	2.2	TDC225*050NSF-F	F	0.125	0.9	5
2.7	TDC275*035NSF-F	F	0.125	0.7	5	2.7	TDC275*050NSF-F	F	0.125	1.1	5
3.3	TDC335*035NSF-F	F	0.125	0.9	5	3.3	TDC335*050NSF-F	F	0.125	1.3	5
3.9	TDC339*035NSF-F	F	0.125	1.0	5	3.9	TDC395*050NSF-F	F	0.125	1.6	5
4.7	TDC475*035NSF-F	F	0.125	1.3	5	4.7	TDC475*050NSF-F	F	0.125	1.9	5
5.6	TDC565*035NSF-F	F	0.125	1.6	5	5.6	TDC565*050NSF-F	F	0.125	2.2	5
6.8	TDC685*035NSF-F	F	0.125	1.9	5	6.8	TDC685*050WSG-F	G	0.25	2.7	5
8.2	TDC825*035NSF-F	F	0.125	2.3	6	8.2	TDC825*050WSG-F	G	0.25	3.3	6
10	TDC106*035NSF-F	F	0.125	2.8	6	10	TDC106*050WSG-F	G	0.25	4.0	6
12	TDC126*035WSG-F	G	0.25	3.4	6	12	TDC126*050WSG-F	G	0.25	4.8	6
15	TDC156*035WSG-F	G	0.25	4.2	6	15	TDC156*050WSG-F	G	0.25	6.0	6
18	TDC186*035WSG-F	G	0.25	5.0	6	18	TDC186*050WSG-F	G	0.25	7.2	6
22	TDC226*035WSG-F	G	0.25	6.2	6	22	TDC226*050WSG-F	G	0.25	8.8	6
27	TDC276*035WSG-F	G	0.25	7.6	6						
33	TDC336*035WSG-F	G	0.25	9.2	6						
39	TDC396*035WSG-F	G	0.25	10	6						
47	TDC476*035WSG-F	G	0.25	10	6						

* Indicates capacitance tolerance: K = \pm 10%, M = \pm 20%, (J = \pm 5%, Special Order)

CDE reserves the right to substitute a tighter tolerance, higher voltage capacitor within the same case size.

Part Numbering System

TDC	107	K	016	W	S	G	-F
Series	Capacitance	Tolerance	Voltage	Lead Spacing	Lead Length	Case Code	RoHS Compliant
TDC	394 = 0.39 μ F	J = \pm 5%	006 = 6 Vdc	N = .125	S = .187	E	-F = Compliant
	105 = 1.0 μ F	K = \pm 10%	010 = 10 Vdc	W = .250	T = Tape & Reel	F	Blank = Not Compliant
	225 = 2.2 μ F	M = \pm 20%	016 = 16 Vdc			G	
	186 = 18 μ F		020 = 20 Vdc				
	107 = 100 μ F		025 = 25 Vdc				
			035 = 35 Vdc				
			050 = 50 Vdc				

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru