

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0736443210

Status:


Active

Overview:

[hdm](#)

Description:

2.00mm (.079") Pitch HDM® Board-to-Board Backplane Header, Vertical, SMC, Press-Fit, Guide Post Location B, Polarizing Key Position F, 144 Circuits



Documents:

[Drawing \(PDF\)](#)

[RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

General

|                |                                     |
|----------------|-------------------------------------|
| Product Family | Backplane Connectors                |
| Series         | <a href="#">73644</a>               |
| Application    | Backplane                           |
| Comments       | Standard Press-Fit, Tin/Lead (SnPb) |
| Component Type | PCB Header                          |
| Overview       | <a href="#">hdm</a>                 |
| Product Name   | HDM®                                |
| Style          | N/A                                 |

Physical

|                                |                                  |
|--------------------------------|----------------------------------|
| Circuits (Loaded)              | 144                              |
| Circuits (maximum)             | 144                              |
| Color - Resin                  | Black, Natural                   |
| Durability (mating cycles max) | 250                              |
| First Mate / Last Break        | No                               |
| Flammability                   | 94V-0                            |
| Guide to Mating Part           | Yes                              |
| Keying to Mating Part          | Yes                              |
| Material - Metal               | Phosphor Bronze, Stainless Steel |
| Material - Plating Mating      | Gold                             |
| Material - Plating Termination | Tin                              |
| Material - Resin               | High Temperature Thermoplastic   |
| Number of Columns              | 24                               |
| Number of Pairs                | Open Pin Field                   |
| Number of Rows                 | 6                                |
| Orientation                    | Vertical                         |
| PC Tail Length (in)            | 0.138 In                         |
| PC Tail Length (mm)            | 3.50 mm                          |
| PCB Locator                    | No                               |
| PCB Retention                  | Yes                              |
| PCB Thickness Recommended (in) | 0.098 In                         |
| PCB Thickness Recommended (mm) | 2.50 mm                          |
| Packaging Type                 | Tube                             |
| Pitch - Mating Interface (in)  | 0.079 In                         |
| Pitch - Mating Interface (mm)  | 2.00 mm                          |
| Pitch - Term. Interface (in)   | 0.079 In                         |
| Pitch - Term. Interface (mm)   | 2.00 mm                          |
| Plating min: Mating (µin)      | 30                               |
| Plating min: Mating (µm)       | 0.75                             |
| Plating min: Termination (µin) | 15                               |
| Plating min: Termination (µm)  | 0.375                            |
| Polarized to PCB               | No                               |

EU RoHS

RoHS Compliant by Exemption

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

Not Reviewed

China RoHS



Pb

Need more information on product environmental compliance?

Email [productcompliance@molex.com](mailto:productcompliance@molex.com)  
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[73644Series](#)

Mates With

[73632](#) HDM PLUS® Board-to-Board Daughtercard Receptacle. [73780](#) HDM® Board-to-Board Daughtercard Receptacle

| Application Tooling   FAQ                                                                                                                                                       |                            |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| Tooling specifications and manuals are found by selecting the products below. Crimp Height Specifications are then contained in the Application Tooling Specification document. |                            |
| Global                                                                                                                                                                          |                            |
| Description                                                                                                                                                                     | Product #                  |
| Flat Rock Tooling for Pneumatic Press                                                                                                                                           | <a href="#">0622013700</a> |
| HDM® Backplane Insertion Signal Contact Tool                                                                                                                                    | <a href="#">0621001400</a> |
| HDM® Backplane Insertion Head for 144 Positions                                                                                                                                 | <a href="#">0622005703</a> |

|                                                                    |                              |                 |            |
|--------------------------------------------------------------------|------------------------------|-----------------|------------|
| Stackable                                                          | No                           | Extraction Tool | 0621001000 |
| Surface Mount Compatible (SMC)                                     | Yes                          |                 |            |
| Temperature Range - Operating                                      | -55°C to +105°C              |                 |            |
| Termination Interface: Style                                       | Through Hole - Compliant Pin |                 |            |
| <b>Electrical</b>                                                  |                              |                 |            |
| Current - Maximum per Contact                                      | 1A                           |                 |            |
| Data Rate                                                          | 1.0 Gbps                     |                 |            |
| Real Signals (per 25mm)                                            | 75                           |                 |            |
| Shielded                                                           | No                           |                 |            |
| Voltage - Maximum                                                  | 250V AC                      |                 |            |
| <b>Material Info</b>                                               |                              |                 |            |
| <b>Reference - Drawing Numbers</b>                                 |                              |                 |            |
| Packaging Specification                                            | PK-70873-0818                |                 |            |
| Sales Drawing                                                      | SDA-73644-****               |                 |            |
| HDM and High Density Metric are trademarks of Amphenol Corporation |                              |                 |            |

This document was generated on 05/14/2010

PLEASE CHECK [WWW.MOLEX.COM](http://WWW.MOLEX.COM) FOR LATEST PART INFORMATION

# NOTES:

1. MATERIALS: HOUSING - LIQUID CRYSTAL POLYMER (LCP), GLASS-FILLED, UL94V-0, COLOR: BLACK, TERMINAL - PHOSPHOR BRONZE.
2. FINISHES: SELECTIVE GOLD (Au) IN CONTACT AREA, 0.00076mm MINIMUM THICKNESS; NICKEL (Ni) AND GOLD FLASH OVERALL SELECTIVE GOLD (Au) IN CONTACT AREA, 0.00076mm MIN. THICKNESS; SELECTIVE TIN/LEAD (Sb/Pb) IN TAIL AREA; NICKEL (Ni) OVERALL.
3. THIS PART CONFORMS TO MOLEX PRODUCT SPECIFICATION PS-73670-9999.
4. FOR MIXED CONTACT MATING LENGTHS, CONSULT FACTORY FOR AVAILABILITY.
5. DIMENSIONS ARE IN MILLIMETERS.
6. FOR SPECIFIC MATERIAL NUMBERS, REFER TO SHEET 2.
7. PACKAGE PER PK-70873-0818.
8. PARTS MARKED WITH PART NUMBER AND DATE CODE, ON EITHER SIDE, APPROXIMATELY WHERE SHOWN.



|      |     |
|------|-----|
| 2    | D   |
| 1    | J   |
| MFG. | SH. |
| REV. |     |

REVISIONS: 2 = 0, 1 = 0, REVISE ONLY ON CAD SYSTEM

|                                        |  |                                                                                                                        |                  |
|----------------------------------------|--|------------------------------------------------------------------------------------------------------------------------|------------------|
| TITLE                                  |  | SALES ASSY, HDM BACKPLANE<br>MODULE, POLAR/GUIDE OPTION                                                                |                  |
| MOLEX INCORPORATED<br>LITSE,ILL. 60532 |  | SHEET NO.<br>1 OF 2                                                                                                    | DATE<br>96/12/18 |
| PART NO.                               |  | SDA-73644-****                                                                                                         |                  |
| SEE CHART                              |  | DIV. DA                                                                                                                |                  |
| FILE NAME<br>S73644X1 DGN              |  | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION. |                  |

|                                                          |                  |
|----------------------------------------------------------|------------------|
| DIMENSIONS SHOWN (METRIC) INCH                           |                  |
| UNLESS OTHERWISE SPECIFIED<br>TOLERANCES: ANGULAR ± 1/2° |                  |
| 3 PLACE                                                  | ± N/A ---        |
| 2 PLACE                                                  | ± N/A ± 0.05     |
| 1 PLACE                                                  | --- ± 0.10       |
| DRAFT WHERE APPLICABLE MUST<br>REMAIN WITHIN DIMENSIONS  |                  |
| DRWG.<br>BY JRR                                          | CHK'D.<br>BY SMR |
| APP'D.<br>BY CAB                                         | SCALE<br>2 : 1   |

|                                                 |  |                |
|-------------------------------------------------|--|----------------|
| REVISED<br>ECR UDT2000-0348<br>BINGHAM 99/10/12 |  | I              |
| REVISED<br>ECR UDT1999-0662<br>BINGHAM 99/05/18 |  | H              |
| REVISED<br>ECR UDT1999-2260<br>THOMAS 03/04/25  |  | J              |
| REVISED<br>ECR UDT1999-0476<br>BINGHAM 98/12/21 |  | G              |
| LTR. REVISIONS                                  |  | LTR. REVISIONS |



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)