

# Altech Corp.®

*Serving the Automation & Control Industry since 1984*



**Wire Duct**

## Standard Slot

**Supplied with lid**

| nominal size    | external dimensions  |                       | part no. selection |               |                |                | standard pack                 |               |
|-----------------|----------------------|-----------------------|--------------------|---------------|----------------|----------------|-------------------------------|---------------|
| w x h<br>inches | width<br>inches (mm) | height<br>inches (mm) | gray<br>PVC        | white<br>PVC  | black<br>PVC   | blue<br>PVC    | no. of lengths<br>6 1/2' each | total<br>feet |
|                 |                      |                       |                    |               |                |                |                               |               |
|                 |                      |                       |                    |               |                |                |                               |               |
|                 |                      |                       |                    |               |                |                |                               |               |
| 1" x 1 1/2"     | 1.14 (29)            | 1.61 (41)             | B25x40S-R          | B25x40S/W-R   | B25x40S/BL-R   | —              | 12                            | 78            |
| 1" x 2"         | 1.14 (29)            | 2.13 (54)             | B25x60S-R          | B25x60S/W-R   | B25x60S/BL-R   | B25x60S/BU-R   | 12                            | 78            |
| 1" x 3"         | 1.14 (29)            | 3.11 (79)             | B25x80S-R          | B25x80S/W-R   | B25x80S/BL-R   | B25x80S/BU-R   | 8                             | 52            |
| 1" x 4"         | 1.18 (30)            | 4.13 (105)            | B25x100S-R         | B25x100S/W-R  | B25x100S/BL-R  | B25x100S/BU-R  | 8                             | 52            |
|                 |                      |                       |                    |               |                |                |                               |               |
| 1 1/2" x 1 1/2" | 1.61 (41)            | 1.61 (41)             | B40x40S-R          | B40x40S/W-R   | B40x40S/BL-R   | —              | 12                            | 78            |
| 1 1/2" x 2"     | 1.61 (41)            | 2.13 (54)             | B40x60S-R          | B40x60S/W-R   | B40x60S/BL-R   | B40x60S/BU-R   | 8                             | 52            |
| 1 1/2" x 3"     | 1.54 (39)            | 3.11 (79)             | B40x80S-R          | B40x80S/W-R   | B40x80S/BL-R   | B40x80S/BU-R   | 8                             | 52            |
| 1 1/2" x 4"     | 1.69 (43)            | 4.13 (105)            | B40x100S-R         | B40x100S/W-R  | B40x100S/BL-R  | B40x100S/BU-R  | 8                             | 52            |
|                 |                      |                       |                    |               |                |                |                               |               |
| 2" x 1"         | 2.13 (54)            | 1.10 (28)             | B60x25S-R          | B60x25S/W-R   | B60x25S/BL-R   | —              | 12                            | 78            |
| 2" x 1 1/2"     | 2.13 (54)            | 1.61 (41)             | B60x40S-R          | B60x40S/W-R   | B60x40S/BL-R   | —              | 8                             | 52            |
| 2" x 2"         | 2.13 (54)            | 2.13 (54)             | B60x60S-R          | B60x60S/W-R   | B60x60S/BL-R   | B60x60S/BU-R   | 8                             | 52            |
| 2" x 3"         | 2.17 (55)            | 3.11 (79)             | B60x80S-R          | B60x80S/W-R   | B60x80S/BL-R   | B60x80S/BU-R   | 8                             | 52            |
| 2" x 4"         | 2.20 (56)            | 4.13 (105)            | B60x100S-R         | B60x100S/W-R  | B60x100S/BL-R  | —              | 4                             | 26            |
|                 |                      |                       |                    |               |                |                |                               |               |
| 3" x 1 1/2"     | 3.15 (80)            | 1.61 (41)             | B80x40S-R          | B80x40S/W-R   | B80x40S/BL-R   | —              | 8                             | 52            |
| 3" x 2"         | 3.07 (78)            | 2.13 (54)             | B80x60S-R          | B80x60S/W-R   | B80x60S/BL-R   | —              | 8                             | 52            |
| 3" x 3"         | 3.15 (80)            | 3.15 (80)             | B80x80S-R          | B80x80S/W-R   | B80x80S/BL-R   | B80x80S/BU-R   | 8                             | 52            |
| 3" x 4"         | 3.15 (80)            | 4.13 (105)            | B80x100S-R         | B80x100S/W-R  | B80x100S/BL-R  | B80x100S/BU-R  | 4                             | 26            |
|                 |                      |                       |                    |               |                |                |                               |               |
| 4" x 2"         | 4.21 (107)           | 2.13 (54)             | B100x60S-R         | B100x60S/W-R  | B100x60S/BL-R  | —              | 4                             | 26            |
| 4" x 3"         | 4.21 (107)           | 3.15 (80)             | B100x80S-R         | B100x80S/W-R  | B100x80S/BL-R  | B100x80S/BU-R  | 4                             | 26            |
| 4" x 4"         | 4.21 (107)           | 4.09 (104)            | B100x100S-R        | B100x100S/W-R | B100x100S/BL-R | B100x100S/BU-R | 4                             | 26            |
| 4" x 5"         | 4.21 (107)           | 5.12 (130)            | B100x130S-R        | B100x130S/W-R | B100x130S/BL-R | —              | 4                             | 26            |
|                 |                      |                       |                    |               |                |                |                               |               |
| 5" x 3"         | 5.16 (131)           | 3.07 (78)             | B130x80S-R         | B130x80S/W-R  | B130x80S/BL-R  | —              | 4                             | 26            |

## MATERIAL

self extinguishing PVC

## SERVICE TEMPERATURE

+5° F to +140° F (-15° C to +60° C)

## STANDARDS

base slots to DIN 43659

## STANDARD COLORS

gray, white, black & blue

## FLAMMABILITY

UL94 V-O rated material



*Serving the Automation & Control Industry Since 1984*

Altech Corp® • 908.806.9400 • 908.806.9490 (fax) • [www.altechcorp.com](http://www.altechcorp.com)



## Thin Slot

### Supplied with lid

| nominal size<br>w x h<br>inches | external dimensions  |                       | part no. selection |               |                | carton quantity               |               |
|---------------------------------|----------------------|-----------------------|--------------------|---------------|----------------|-------------------------------|---------------|
|                                 | width<br>inches (mm) | height<br>inches (mm) | gray<br>PVC        | white<br>PVC  | black<br>PVC   | no. of lengths<br>6 1/2' each | total<br>feet |
| 1" x 1 1/2"                     | 1.14 (29)            | 1.61 (41)             | B25x40T-R          | B25x40T/W-R   | B25x40T/BL-R   | 12                            | 78            |
| 1" x 2"                         | 1.14 (29)            | 2.13 (54)             | B25x60T-R          | B25x60T/W-R   | B25x60T/BL-R   | 12                            | 78            |
| 1" x 3"                         | 1.14 (29)            | 3.11 (79)             | B25x80T-R          | B25x80T/W-R   | B25x80T/BL-R   | 8                             | 52            |
| 1" x 4"                         | 1.18 (30)            | 4.13 (105)            | B25x100T-R         | B25x100T/W-R  | B25x100T/BL-R  | 8                             | 52            |
| 1 1/2" x 1 1/2"                 | 1.61 (41)            | 1.61 (41)             | B40x40T-R          | B40x40T/W-R   | B40x40T/BL-R   | 12                            | 78            |
| 1 1/2" x 2"                     | 1.61 (41)            | 2.13 (54)             | B40x60T-R          | B40x60T/W-R   | B40x60T/BL-R   | 8                             | 52            |
| 1 1/2" x 3"                     | 1.61 (41)            | 3.11 (79)             | B40x80T-R          | B40x80T/W-R   | B40x80T/BL-R   | 8                             | 52            |
| 1 1/2" x 4"                     | 1.69 (43)            | 4.13 (105)            | B40x100T-R         | B40x100T/W-R  | B40x100T/BL-R  | 8                             | 52            |
| 2" x 1 1/2"                     | 2.20 (56)            | 1.61 (41)             | B60x40T-R          | B60x40T/W-R   | B60x40T/BL-R   | 8                             | 52            |
| 2" x 2"                         | 2.13 (54)            | 2.13 (54)             | B60x60T-R          | B60x60T/W-R   | B60x60T/BL-R   | 8                             | 52            |
| 2" x 3"                         | 2.17 (55)            | 3.11 (79)             | B60x80T-R          | B60x80T/W-R   | B60x80T/BL-R   | 8                             | 52            |
| 2" x 4"                         | 2.20 (56)            | 4.13 (105)            | B60x100T-R         | B60x100T/W-R  | B60x100T/BL-R  | 4                             | 26            |
| 3" x 1 1/2"                     | 3.15 (80)            | 1.61 (41)             | B80x40T-R          | B80x40T/W-R   | B80x40T/BL-R   | 8                             | 52            |
| 3" x 2"                         | 3.07 (78)            | 2.13 (54)             | B80x60T-R          | B80x60T/W-R   | B80x60T/BL-R   | 8                             | 52            |
| 3" x 3"                         | 3.15 (80)            | 3.15 (80)             | B80x80T-R          | B80x80T/W-R   | B80x80T/BL-R   | 8                             | 52            |
| 3" x 4"                         | 3.15 (80)            | 4.13 (105)            | B80x100T-R         | B80x100T/W-R  | B80x100T/BL-R  | 4                             | 26            |
| 4" x 2"                         | 4.21 (107)           | 2.13 (54)             | B100x60T-R         | B100x60T/W-R  | B100x60T/BL-R  | 4                             | 26            |
| 4" x 3"                         | 4.21 (107)           | 3.15 (80)             | B100x80T-R         | B100x80T/W-R  | B100x80T/BL-R  | 4                             | 26            |
| 4" x 4"                         | 4.21 (107)           | 4.09 (104)            | B100x100T-R        | B100x100T/W-R | B100x100T/BL-R | 4                             | 26            |

#### MATERIAL

self extinguishing PVC

#### SERVICE TEMPERATURE

+5° F to +140° F (-15° C to +60° C)

#### STANDARDS

base slots to DIN 43659

#### STANDARD COLORS

gray, white & black

#### FLAMMABILITY

UL94 V-O rated material



ISO9001:2000 Certified



| Supplied with lid |                      |                       |                    |                |                 |                               |               |
|-------------------|----------------------|-----------------------|--------------------|----------------|-----------------|-------------------------------|---------------|
| nominal size      | external dimensions  |                       | part no. selection |                |                 | carton quantity               |               |
| w x h<br>inches   | width<br>inches (mm) | height<br>inches (mm) | gray<br>PVC        | white<br>PVC   | black<br>PVC    | no. of lengths<br>6 1/2' each | total<br>feet |
|                   |                      |                       |                    |                |                 |                               |               |
|                   |                      |                       |                    |                |                 |                               |               |
|                   |                      |                       |                    |                |                 |                               |               |
|                   |                      |                       |                    |                |                 |                               |               |
|                   |                      |                       |                    |                |                 |                               |               |
| 1" x 1 1/2"       | 1.14 (29)            | 1.61 (41)             | B25x40US-R         | B25x40US/W-R   | B25x40US/BL-R   | 12                            | 78            |
| 1" x 2"           | 1.14 (29)            | 2.13 (54)             | B25x60US-R         | B25x60US/W-R   | B25x60US/BL-R   | 12                            | 78            |
| 1" x 3"           | 1.14 (29)            | 3.11 (79)             | B25x80US-R         | B25x80US/W-R   | B25x80US/BL-R   | 8                             | 52            |
| 1" x 4"           | 1.18 (30)            | 4.13 (105)            | B25x100US-R        | B25x100US/W-R  | B25x100US/BL-R  | 8                             | 52            |
|                   |                      |                       |                    |                |                 |                               |               |
| 1 1/2" x 1 1/2"   | 1.61 (41)            | 1.61 (41)             | B40x40US-R         | B40x40US/W-R   | B40x40US/BL-R   | 12                            | 78            |
| 1 1/2" x 2"       | 1.61 (41)            | 2.13 (54)             | B40x60US-R         | B40x60US/W-R   | B40x60US/BL-R   | 8                             | 52            |
| 1 1/2" x 3"       | 1.54 (39)            | 3.11 (79)             | B40x80US-R         | B40x80US/W-R   | B40x80US/BL-R   | 8                             | 52            |
| 1 1/2" x 4"       | 1.69 (43)            | 4.13 (105)            | B40x100US-R        | B40x100US/W-R  | B40x100US/BL-R  | 8                             | 52            |
|                   |                      |                       |                    |                |                 |                               |               |
| 2" x 1"           | 2.13 (54)            | 1.10 (28)             | B60x25US-R         | B60x25US/W-R   | B60x25US/BL-R   | 12                            | 78            |
| 2" x 1 1/2"       | 2.13 (54)            | 1.61 (41)             | B60x40US-R         | B60x40US/W-R   | B60x40US/BL-R   | 8                             | 52            |
| 2" x 2"           | 2.13 (54)            | 2.13 (54)             | B60x60US-R         | B60x60US/W-R   | B60x60US/BL-R   | 8                             | 52            |
| 2" x 3"           | 2.17 (55)            | 3.11 (79)             | B60x80US-R         | B60x80US/W-R   | B60x80US/BL-R   | 8                             | 52            |
| 2" x 4"           | 2.20 (56)            | 4.13 (105)            | B60x100US-R        | B60x100US/W-R  | B60x100US/BL-R  | 4                             | 26            |
|                   |                      |                       |                    |                |                 |                               |               |
| 3" x 1 1/2"       | 3.15 (80)            | 1.61 (41)             | B80x40US-R         | B80x40US/W-R   | B80x40US/BL-R   | 8                             | 52            |
| 3" x 2"           | 3.07 (78)            | 2.13 (54)             | B80x60US-R         | B80x60US/W-R   | B80x60US/BL-R   | 8                             | 52            |
| 3" x 3"           | 3.15 (80)            | 3.15 (80)             | B80x80US-R         | B80x80US/W-R   | B80x80US/BL-R   | 8                             | 52            |
| 3" x 4"           | 3.15 (80)            | 4.13 (105)            | B80x100US-R        | B80x100US/W-R  | B80x100US/BL-R  | 4                             | 26            |
|                   |                      |                       |                    |                |                 |                               |               |
| 4" x 2"           | 4.21 (107)           | 2.13 (54)             | B100x60US-R        | B100x60US/W-R  | B100x60US/BL-R  | 4                             | 26            |
| 4" x 3"           | 4.21 (107)           | 3.15 (80)             | B100x80US-R        | B100x80US/W-R  | B100x80US/BL-R  | 4                             | 26            |
| 4" x 4"           | 4.21 (107)           | 4.09 (104)            | B100x100US-R       | B100x100US/W-R | B100x100US/BL-R | 4                             | 26            |
| 4" x 5"           | 4.21 (107)           | 5.12 (130)            | B100x130US-R       | B100x130US/W-R | B100x130US/BL-R | 4                             | 26            |
|                   |                      |                       |                    |                |                 |                               |               |
| 5" x 3"           | 5.16 (131)           | 3.07 (78)             | B130x80US-R        | B130x80US/W-R  | B130x80US/BL-R  | 4                             | 26            |

**UL**  
C **UL** US  
E161178

*A Leading Supplier For Over Twenty Years*  
Altech Corp® • 908.806.9400 • 908.806.9490 (fax) • [www.altechcorp.com](http://www.altechcorp.com)

## Product Features

The Panel building market has very specific needs. This unique cable management system developed specifically for use within cabinets and control panels. Select Standard, Thin, Closed Slot and Unslotted depending on the application. Available in a number of sizes and colors, manufactured in standard PVC material.

### CABLE RETENTION

Wiring duct design allows cables to be retained during installation, making routing and cable termination a simple process

### LID RETENTION

Friction bead on wider trunking provides excellent lid retention to combat vibration

### BREAK-OUT

Fingers can be removed easily without the use of cutting tools

### EASY INSTALLATION

Base slots are to DIN 43659, providing maximum flexibility for easy installation



### SIZE RANGE

- Wide range of sizes to cater to a broad spectrum of requirements
- New larger sizes with narrower profiles to reduce panel footprint

### MATERIALS

- The standard range is manufactured using self extinguishing PVC

### COLORS

- Gray, white and black are standard
- Blue is offered for intrinsically safe wiring applications
- Other colors available

## Standard Wiring Duct

PVC provides a lightweight self extinguishing wiring duct with excellent rigidity and performance characteristics.

### Standard Slot



- Wide fingers giving additional cable support
- Terminated wires can be re-routed easily
- 0.79" slot pitch
- 0.31" slot width
- 22 sizes, available in gray, white, black or blue

### Unslotted



- Ideal where no break-outs are required or side wall access is infrequent
- Complete cable protection
- 22 sizes, in either gray, white or black

### Thin Slot



- Ideal for use with slimmer terminal blocks where more access is required
- Improves appearance of panels with cables out in best position
- 0.39" slot pitch
- 0.16" slot width
- 19 sizes in a choice of gray, white or black

*Serving the Automation & Control Industry Since 1984*

**Altech Corp® • 908.806.9400 • 908.806.9490 (fax) • [www.altechcorp.com](http://www.altechcorp.com)**

## Altech Corp.®

Quality  
Endorsed  
Company



ISO 9001:2008  
CERTIFICATE



Altech Search

Google™ Custom Search

Home

Stock Check

Distributors

Information

News

Contact

Rep/Dist Login

Altech Mexico

### WEB TOOLS

Product Crossings

Request for Quote

Sample Request

Catalog Request

### PRODUCT MENU

Circuit Protection / Control >

Connectors >

Enclosures >

European Spare Parts >

Foot Switches

Interface Modules >

Power Supplies

Push Buttons & Pilot Lights >

Relays >

Sensors >

Terminal Blocks >

Tower Lights

Wire & Cable Management >

Home

### New Products and Promotions

## Serving the Automation & Control Industry Since 1984

### Circuit Protection



Circuit  
Protection  
Devices



Busbar  
and Power  
Distribution



Contactors,  
Overload  
Relays, Manual  
Motor Starters



Motor  
Disconnect  
Switches



European  
Fuses

### Connectors



Industrial  
Rectangular  
Connectors



Pin & Sleeve  
Devices



Receptacles

### Foot Switches



Foot  
Switches

### Sensors



Inductive  
Proximity  
Sensors

### Enclosures



Industrial  
Enclosures



DIN  
Enclosures

### Modules & Relays



Interface  
Modules



Safety  
Relays



Slimline  
Relays

### Power Supplies



Power  
Supplies

### Push Buttons



22 & 30 mm  
Push Buttons

### DIN Rail



DIN  
Rail

### Wire & Cable Management



Liquid Tight  
Strain Reliefs/  
Corrugated  
Tubes



Wire Duct


### Terminal Blocks



Din Rail  
Terminal  
Blocks



Panel Mount  
Terminal  
Blocks



Printed Circuit  
Board Terminal  
Blocks



Eurostrips



Distribution  
Blocks


### Miscellaneous



Ferrules




Custom  
Assembly



Marking &  
Engraving  
Systems



Power  
Semi-  
conductors



European  
Spare Parts

Altech Corporation  
35 Royal Road  
Flemington, NJ 08822-6000  
P 908.806.9400 • F 908.806.9490  
www.altechcorp.com

Altech Corp.® 555B-052013-5M  
Printed July 2013



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)