



| General ordering data | |
|---|---|
| Order No. | 1017000000 |
| Part designation | WTL 6/1/STB/32 |
| Version | Disconnect and modular disconnect terminal, 6 mm², Screw connection, Wemid, dark beige, TS 32 |
| EAN | 4008190169039 |
| Qty. | 50 pc(s). |

| Product notes | |
|---|---|
| Note, ordering data | TS32 version on request |
| Note, technical data | Use as 500 V disconnect terminal. Conductor connection H07V-K10, H07V-R10 and AWG 8/7 with tightening torque of 1.0 Nm. |
| Product description | Different current transformer circuits, e.g. for replacing measuring instruments or electricity meters, can be realised. |

| 2 clampable conductors (H05V/H07V) with equal cross-section (rated connection) | |
|---|---|
| Solid, min. | 0.5 mm² |
| Solid, max. | 2.5 mm² |
| Flexible, min. | 0.5 mm² |
| Flexible, max. | 2.5 mm² |
| Flexible with ferrule, min. (DIN 46228 pt 1) | 0.5 mm² |
| Flexible with ferrule, max. (DIN 46228 pt 1) | 2.5 mm² |

| Additional technical data | |
|---|---|
| Colour of insulating material | dark beige |
| Connection direction | on side |
| End plate required | Yes |
| Explosion-tested version "Ex e" | No |
| Installation advice | TS 32 |
| Insulating material | Wemid |
| Levels cross-connected internally | No |

| Additional technical data | |
|---|---|
| No. of identical terminals | 1 |
| No. of levels | 1 |
| No. of terminal strips per level | 2 |
| Open sides | right |
| Operating temperature range | - 50 °C, + 120 °C |
| Product family | W-Series |
| Type of connection | Screwed |
| Type of mounting | Snap-on |
| UL 94 flammability rating of insulation material | V-0 |
| Version | Test-disconnect terminals |

| CSA rating data | |
|---|---|
| Voltage (CSA) | 300 V |
| CSA current | 45 A |
| Min. cross-section (CSA) | AWG 20 |
| Max. cross-section (CSA) | AWG 8 |

| Conductors for clamping (additional connection) | |
|---|---|
| Flexible with ferrule, min. (DIN 46228 pt 1) | 0.5 mm² |
| Flexible with ferrule, max. (DIN 46228 pt 1) | 6 mm² |

| Conductors for clamping (rated connection) | |
|---|---|
| Clamping range, min. | 0.5 mm² |
| Clamping range, max. | 10 mm² |
| Type of connection | Screw connection |
| 2nd type of connection | screwed |
| Connection direction | on side |
| No. of connections | 2 |
| Stripping length | 12 mm |
| Clamping screw | M 3.5 |
| Blade size | 4.0 x 0.8 mm |
| Tightening torque range | 0.8...1.6 Nm |
| Torque level with DMS electric screwdriver | 3 |
| Gauge to IEC 60947-1 | A5 |
| Solid, min. | 0.5 mm² |
| Solid, max. | 10 mm² |
| Stranded, min. | 1.5 mm² |
| Stranded, max. | 10 mm² |
| Flexible, min. | 0.5 mm² |
| Flexible, max. | 10 mm² |
| Flexible with ferrule, min. (DIN 46228/1) | 0.5 mm² |
| Flexible with ferrule, max. (DIN 46228/1) | 6 mm² |
| Flexible, min., ferrule with plastic collar (DIN 46228 pt 4) | 0.5 mm² |
| Flexible, max., ferrule with plastic collar (DIN 46228 pt 4) | 6 mm² |
| AWG conductor size, min. | AWG 20 |
| AWG conductor size, max. | AWG 8 |
| AWG conductor size, min. | 0.52 mm² |
| AWG conductor size, max. | 8.37 mm² |

## Conductors for clamping (rated connection)

| Dimensions | |
|---|---|
| Width | 7.9 mm |
| Height of lowest version | 48.5 mm |
| Length | 65 mm |
| TS 32 offset | 32.5 mm |
| TS 35 offset | 15 mm |

| Disconnect terminals | |
|---|---|
| Cross-disconnect | sliding |
| Integral test socket | Yes |
| Slitting | sliding |
| Tightening torque range | 0.5...0.8 Nm |
| Torque level with DMS electric screwdriver | 3 |

| Rating data | |
|---|---|
| Rated cross-section | 6 mm² |
| Rated voltage | 630 V |
| Rated impulse voltage | 6 kV |
| Rated current | 41 A |
| Standards | IEC 60947-7-1 |
| Current with max. conductor | 57 A |
| Pollution severity | 3 |

| UL rating data | |
|---|---|
| Voltage (UL) | 300 V |
| Current (UL) | 45 A |
| Min. cross-section (UL) | AWG 20 |
| Max. cross-section (UL) | AWG 8 |

| Approvals | |
|---|---|
| Approvals institutes | |

| Classifications | |
|---|---|
| ETIM 2.0 | EC000902 |
| ETIM 3.0 | EC000902 |
| eClass 4.1 | 27-14-11-26 |
| eClass 5.0 | 27-14-11-26 |
| eClass 5.1 | 27-14-11-26 |

### Similar products

| Order No. | Part designation | Version |
|---|---|---|
| 1016700000 | WTL 6/1 | Disconnect and modular disconnect terminal, 6 mm², Screw connection, Wemid, dark beige, TS 35 |

| | | |
|---|---|---|
| 1934810000 | WTL 6/1 EN | Trenn- und Messtrennreihenklemme, 6 mm², Schraubanschluss, Wemid, dunkelbeige, TS 32 und TS 35 |
| 1019670000 | WTL 6/1 EN BL | |
| 1019760000 | WTL 6/1 EN GN | |
| 1934820000 | WTL 6/1 EN STB | Trenn- und Messtrennreihenklemme mit Steckbuchse, 6 mm², Schraubanschluss, Wemid, dunkelbeige, TS 32 und TS 35 |
| 1019680000 | WTL 6/1 EN STB BL | |
| 1019690000 | WTL 6/1 EN STB GR | |
| 1019710000 | WTL 6/1 EN STB RT | |
| 1019750000 | WTL 6/1 EN GE | |
| 1016900000 | WTL 6/1/STB | Disconnect and modular disconnect terminal, 6 mm², Screw connection, Wemid, dark beige, TS 35 |
| 1016950000 | WTL 6/1/STB RT | Disconnect and modular disconnect terminal, 6 mm², Screw connection, Wemid, dark beige, TS 35 |
| 1631820000 | WTL 6/1/STB/Q BL | Disconnect and modular disconnect terminal, 6 mm², Screw connection, Wemid, dark beige, TS 35 |
| 1631800000 | WTL 6/1/STB/Q GE | Disconnect and modular disconnect terminal, 6 mm², Screw connection, Wemid, dark beige, TS 35 |
| 1631790000 | WTL 6/1/STB/Q RT | Disconnect and modular disconnect terminal, 6 mm², Screw connection, Wemid, dark beige, TS 35 |
| 1631810000 | WTL 6/1/STB/Q SW | Disconnect and modular disconnect terminal, 6 mm², Screw connection, Wemid, dark beige, TS 35 |
| 1849200000 | WTL 6/1/STB/TNSC | Disconnect and modular disconnect terminal, 6 mm², Screw connection, Wemid, dark beige, TS 35 |
| 1938820000 | WTL 6/1/STB/TNSC/EN | Trenn- und Messtrennreihenklemme mit Steckbuchse und Trennschieber, 6 mm², Schraubanschluss, Wemid, dunkelbeige, TS 32 und TS 35 |

ООО «ЛайфЭлектроникс» “LifeElectronics” LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

*Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.*

*С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров*

*Мы предлагаем:*

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

*В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.*

*Конструкторский отдел помогает осуществить:*

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

*Тел: +7 (812) 336 43 04 (многоканальный)*
*Email: org@lifeelectronics.ru*

***www.lifeelectronics.ru***