

S8JX

Power Supplies



Cost Effective Power Supplies with Multiple Mounting Options

Wide range of DC output voltages

- » 5 V, 12 V, 15 V, 24 V, and 15W, 35W, 50W, 100W, 150W, 300W, 600W sizes

Universal input voltage

- » 85-264 VAC, 50/60 Hz (15W to 150W); switchable 100-120 VAC/200-240 VAC for 300W and 600W

Multiple mounting options

- » For panel design flexibility – DIN, front, bottom, or side

Series operation

- » Available for up to 2 power supplies

Parallel operation

- » Up to 5 units, 300W and 600W models

Extend machine life

- » With built-in overload and overvoltage protection

Approvals

- » UL, cUL, UL508 Listed, CE, SEMI F47, VDE

Adjustable voltage output (-10% to 15%)

Two-year warranty

S8JX Power Supplies

OMRON

Specifications & Ordering Information

| Power Rating | Output Voltage | Output Current | Dimensions H x W x D mm (inches) Max. DIN mount | Part Numbers | | | |
|--------------|----------------|----------------|--|--------------------|---------------------|---------------------|----------------------|
| | | | | Open Frame | | Covered Frame | |
| | | | | Front* Mount | DIN-rail Mount | Front* Mount | DIN-rail Mount |
| 15 W | 5 V | 3 A | 96 x 39.5 x 114.5 (3.78 x 1.56 x 4.51) | S8JX-G01505 | S8JX-G01505D | S8JX-G01505C | S8JX-G01505CD |
| | 12 V | 1.3 A | | S8JX-G01512 | S8JX-G01512D | S8JX-G01512C | S8JX-G01512CD |
| | 15 V | 1 A | | S8JX-G01515 | S8JX-G01515D | S8JX-G01515C | S8JX-G01515CD |
| | 24 V | 0.65 A | | S8JX-G01524 | S8JX-G01524D | S8JX-G01524C | S8JX-G01524CD |
| 35 W | 5 V | 7 A | 96 x 39.5 x 114.5 (3.78 x 1.56 x 4.51) | S8JX-G03505 | S8JX-G03505D | S8JX-G03505C | S8JX-G03505CD |
| | 12 V | 3 A | | S8JX-G03512 | S8JX-G03512D | S8JX-G03512C | S8JX-G03512CD |
| | 15 V | 2.4 A | | S8JX-G03515 | S8JX-G03515D | S8JX-G03515C | S8JX-G03515CD |
| | 24 V | 1.5 A | | S8JX-G03524 | S8JX-G03524D | S8JX-G03524C | S8JX-G03524CD |
| 50 W | 5 V | 10 A | 97 x 40 x 124.5 (3.82 x 1.57 x 4.90) | S8JX-G05005 | S8JX-G05005D | S8JX-G05005C | S8JX-G05005CD |
| | 12 V | 4.2 A | | S8JX-G05012 | S8JX-G05012D | S8JX-G05012C | S8JX-G05012CD |
| | 24 V | 2.1 A | | S8JX-G05024 | S8JX-G05024D | S8JX-G05024C | S8JX-G05024CD |
| 100 W | 5 V | 20 A | 97 x 50 x 174.5 (3.82 x 1.97 x 6.87) | S8JX-G10005 | S8JX-G10005D | S8JX-G10005C | S8JX-G10005CD |
| | 12 V | 8.5 A | | S8JX-G10012 | S8JX-G10012D | S8JX-G10012C | S8JX-G10012CD |
| | 24 V | 4.5 A | | S8JX-G10024 | S8JX-G10024D | S8JX-G10024C | S8JX-G10024CD |
| 150 W | 24 V | 6.5 A | 97 x 50 x 174.5 (3.82 x 1.97 x 6.87) | S8JX-G15024 | S8JX-G15024D | S8JX-G15024C | S8JX-G15024CD |
| 300 W | 24 V | 14 A | 96 x 110 x 204.8 (3.78 x 4.33 x 8.06) | — | — | S8JX-G30024C | S8JX-G30024CD |
| 600 W | 24 V | 27 A | 92 x 150 x 184.2 (3.62 x 5.90 x 7.25) | — | — | S8JX-G60024C | — |

* - Front mount models can also be side or bottom mounted. Front mounting bracket included. See datasheet for other optional mounting bracket details.

Optional Mounting Brackets

| Description | Part Numbers |
|--|-------------------|
| Mounting Bracket A (bottom mounting for 50 W models) | S82Y-JX05B |
| Mounting Bracket B (bottom mounting for 100 W: 24 V models) | S82Y-JX10B |
| Mounting Bracket C (bottom mounting for 100 W: 5 V and 12 V models and 150 W models) | S82Y-JX15B |
| Mounting Bracket D (front mounting for 100 W: 5 V and 12 V models and 150 W models) | S82Y-JX15F |

OMRON ELECTRONICS LLC • THE AMERICAS HEADQUARTERS • Schaumburg, IL USA • 847.843.7900 • 800.556.6766 • www.omron247.com

OMRON CANADA, INC. • HEAD OFFICE

Toronto, ON, Canada • 416.286.6465 • 866.986.6766 • www.omron247.com

OMRON ELECTRONICS MEXICO SA DE CV • HEAD OFFICE

Apodaca, N.L. • 52.811.156.99.10 • 001.800.556.6766 • mela@omron.com

OMRON ELETRÔNICA DO BRASIL LTDA • HEAD OFFICE

São Paulo, SP, Brasil • 55.11.2101.6300 • www.omron.com.br

T071-E02

Note: Specifications are subject to change.

© 2009 Omron Electronics LLC

Printed in U.S.A.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru