






NOTES:

1. MATERIAL: SEE TABLE
2. FINISHES: SEE TABLE
3. PRODUCT SPECIFICATION: NOT REQUIRED
4. PACKAGING: NOT REQUIRED
5. MATES WITH: NONE
6. "XX" REFERS TO THE NUMBER OF CIRCUITS.



4	XX	#3-48 SCREW W/WASHER	STEEL	Zn CLEAR CHROMATE
3	XX	TERMINAL	BRASS	TIN
2	XX	#3-48 SCREW	BRASS	NICKEL
1	1	SR BTS	THERMOPLASTIC	BLACK
ITEM	QTY.	DESCRIPTION	MATERIAL	FINISH

EC NO. ECN 3836
DRWN: JF 10-27-04
CHK: K
APPR: S

DESCRIPTION
REV

QUALITY SYMBOLS

MAJOR
CRITICAL
SPC
S

GENERAL TOLERANCES:
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±.0015	±.0015
3 PLACES	±.038	±.005
2 PLACES	±.13	±.01
1 PLACE	±.3	


ANGULAR: ±2°

DRAFT WHERE APPLICABLE MUST
REMAIN WITHIN DIMENSIONSSCALE
3:1DRAWN BY & DATE
W. HOWARD 10-7-03CHECKED BY & DATE
R. KEMP 10-9-03APPROVED BY & DATE
P. WALTZ 10-10-03CAD FILENAME
605XX-CDESIGN UNITS
☐ mm ☒ INCHTHIRD ANGLE
PROJECTION

TITLE: SR BTS, ASSY

MOLEX INCORPORATED

MATERIAL NO.
SEE CHARTDRAWING NO.
SD-38600-001SHEET NO.
1 OF 2THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.SIZE
B



PTH PATTERN

NUMBER OF CIRCUITS "XX"	DIM. "A"	DIM. "B"	MATERIAL NO. (OPT -C, -50)	MATERIAL NO. (OPT -C)	MATERIAL NO. (INSULATOR)
02	14.48 [1.570]	6.35 [1.250]	38600-7802	38600-6602	38608-2735
03	20.83 [1.820]	12.70 [1.500]	38600-7803	38600-6603	38608-2736
04	27.18 [1.070]	19.05 [1.750]	38600-7804	38600-6604	38608-2737
05	33.53 [1.320]	25.40 [1.000]	38600-7805	38600-6605	38608-2738
06	39.88 [1.570]	31.75 [1.250]	38600-7806	38600-6606	38608-2739
07	46.23 [1.820]	38.10 [1.500]	38600-7807	38600-6607	38608-2740
08	52.58 [2.070]	44.45 [1.750]	38600-7808	38600-6608	38608-2741
09	58.93 [2.320]	50.80 [2.000]	38600-7809	38600-6609	38608-2742
10	65.28 [2.570]	57.15 [2.250]	38600-7810	38600-6610	38608-2743
11	71.63 [2.820]	63.50 [2.500]	38600-7811	38600-6611	38608-2744
12	77.98 [3.070]	69.85 [2.750]	38600-7812	38600-6612	38608-2745
13	84.33 [3.320]	76.20 [3.000]	38600-7813	38600-6613	38608-2746
14	90.68 [3.570]	82.55 [3.250]	38600-7814	38600-6614	38608-2747
15	97.03 [3.820]	88.90 [3.500]	38600-7815	38600-6615	38608-2748
16	103.38 [4.070]	95.25 [3.750]	38600-7816	38600-6616	38608-2749
17	109.73 [4.320]	101.60 [4.000]	38600-7817	38600-6617	38608-2750
18	116.08 [4.570]	107.95 [4.250]	38600-7818	38600-6619	38608-2751
19	122.43 [4.820]	114.30 [4.500]	38600-7819	38600-6619	38608-2752
20	128.78 [5.070]	120.65 [4.750]	38600-7820	38600-6620	38608-2753
21	135.13 [5.320]	127.00 [5.000]	38600-7821	38600-6621	38608-2754
22	141.48 [5.570]	133.35 [5.250]	38600-7822	38600-6622	38608-2755
23	147.83 [5.820]	139.70 [5.500]	38600-7823	38600-6623	38608-2756
24	154.18 [6.070]	146.05 [5.750]	38600-7824	38600-6624	38608-2757
25	160.53 [6.320]	152.40 [6.000]	38600-7825	38600-6625	38608-2758
26	166.88 [6.570]	158.75 [6.250]	38600-7826	38600-6626	38608-2759
27	173.23 [6.820]	165.10 [6.500]	38600-7827	38600-6627	38608-2760
28	179.58 [7.070]	171.45 [6.750]	38600-7828	38600-6628	38608-2761
29	185.93 [7.320]	177.80 [7.000]	38600-7829	38600-6629	38608-2762
30	192.28 [7.570]	184.15 [7.250]	38600-7830	38600-6630	38608-2763
31	198.63 [7.820]	190.50 [7.500]	38600-7831	38600-6631	38608-2764
32	204.98 [8.070]	196.85 [7.750]	38600-7832	38600-6632	38608-2765

EC NO. SEE SHEET ONE DRAWN: CH X: APPR: REV		QUALITY SYMBOLS MAJOR CRITICAL C SPC S	GENERAL TOLERANCES: (UNLESS SPECIFIED) mm INCH 4 PLACES ±.0015 3 PLACES ±.038 ±.005 2 PLACES ±.13 ±.01 1 PLACE ±.3 ANGULAR: ±2° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SCALE 3:1 DESIGN UNITS mm INCH DRAWN BY & DATE W. HOWARD 10-7-03 CHECKED BY & DATE R. KEMP 10-9-03 APPROVED BY & DATE P. WALTZ 10-10-03 CAD FILENAME 605XX-C	THIRD ANGLE PROJECTION mm INCH mm ONLY TITLE: SR BTS, ASSY MOLEX INCORPORATED	PROJECT NO.	DIMENSIONS: ☒ mm INCH ☐ INCH mm ☐ mm ONLY		SHT	REV	
						MATERIAL NO. SEE CHART		DRAWING NO. SD-38600-001	SHEET NO. 2 OF 2		
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.											SIZE B

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru