

Intel Atom[®] Processor E3800 Product Family

Datasheet

October 2018

Revision 4.3



You may not use or facilitate the use of this document in connection with any infringement or other legal analysis concerning Intel products described herein. You agree to grant Intel a non-exclusive, royalty-free license to any patent claim thereafter drafted which includes subject matter disclosed herein.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document. Intel technologies' features and benefits depend on system configuration and may require enabled hardware, software or service activation. Performance varies depending on system configuration. No computer system can be absolutely secure. Check with your system manufacturer or retailer or learn more at intel.com.

The products described may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Intel disclaims all express and implied warranties, including without limitation, the implied warranties of merchantability, and fitness for a particular purpose, and non-infringement, as well as any warranty arising from course of performance, course of dealing, or usage in trade.


All information provided here is subject to change without notice. Contact your Intel representative to obtain the latest Intel product specifications and roadmaps

Copies of documents which have an order number and are referenced in this document may be obtained by calling 1-800-548-4725 or visit www.intel.com/design/literature.htm.

Intel, Intel Atom and the Intel logo, are trademarks of Intel Corporation in the U.S. and/or other countries.

*Other names and brands may be claimed as the property of others.

© 2018 Intel Corporation. All rights reserved.



Contents

1	Introduction	29
1.1	Terminology	31
1.2	Feature Overview	32
2	Physical Interfaces	38
2.1	Pin States Through Reset	40
2.2	System Memory Controller Interface Signals	41
2.3	PCI Express* 2.0 Interface Signals	43
2.4	USB 2.0 Host (EHCI/xHCI) Interface Signals	43
2.5	USB 2.0 HSIC Interface Signals	44
2.6	USB 3.0 (xHCI) Host Interface Signals	44
2.7	USB 2.0 Device (ULPI) Interface Signals	44
2.8	USB 3.0 Device Interface Signals	45
2.9	Serial ATA (SATA) 2.0 Interface Signals	46
2.10	Integrated Clock Interface Signals	46
2.11	Display - Digital Display Interface (DDI) Signals	47
2.12	Display - VGA Interface Signals	48
2.13	MIPI Camera Serial Interface (CSI) and ISP Interface Signals	48
2.14	Intel® High Definition Audio Interface Signals	49
2.15	Low Power Engine (LPE) for Audio (I ² S) Interface Signals	49
2.16	Storage Control Cluster (eMMC, SDIO, SD) Interface Signals	50
2.17	SIO - High Speed UART Interface Signals	51
2.18	SIO - I ² C Interface Signals	52
2.19	SIO - Serial Peripheral Interface (SPI) Signals	52
2.20	PCU - iLB - Real Time Clock (RTC) Interface Signals	53
2.21	PCU - iLB - Low Pin Count (LPC) Bridge Interface Signals	53
2.22	PCU - Serial Peripheral Interface (SPI) Signals	54
2.23	PCU - System Management Bus (SMBus) Interface Signals	55
2.24	PCU - Power Management Controller (PMC) Interface Signals	55
2.25	JTAG and Debug Interface Signals	56
2.26	Miscellaneous Signals	56
2.27	GPIO Signals	57
2.28	Power And Ground Pins	61
2.29	Hardware Straps	63
2.30	Configurable IO: GPIO Muxing	64
2.31	Reserved Pins	64
3	Register Access Methods	65
3.1	Fixed IO Register Access	65
3.2	Fixed Memory Mapped Register Access	65
3.3	IO Referenced Register Access	65
3.4	Memory Referenced Register Access	66
3.5	PCI Configuration Register Access	66
3.6	Message Bus Register Access	68
3.7	Register Field Access Types	69
4	Mapping Address Spaces	71
4.1	Physical Address Space Mappings	71
4.2	IO Address Space	77



4.3	PCI Configuration Space	79
5	Integrated Clock	82
5.1	Features	83
6	Power Management	86
6.1	Power Management Features	86
6.2	Power Management States Supported	86
6.3	Processor Core Power Management	91
6.4	Memory Controller Power Management	97
6.5	PCI Express* (PCIe*) Power Management	99
7	Power Up and Reset Sequence	100
7.1	SoC System States	100
7.2	Power Up Sequences	100
7.3	Power Down Sequences	105
7.4	Reset Behavior	108
8	Thermal Management	111
8.1	CPU Thermal Management Registers	111
8.2	Thermal Sensors	111
8.3	SoC Programmable Trips	112
8.4	Platform Trips	113
8.5	Thermal Throttling Mechanisms	113
8.6	Thermal Status	113
9	Electrical Specifications	114
9.1	Thermal Specifications	114
9.2	Storage Conditions	115
9.3	Voltage and Current Specifications	116
9.4	Crystal Specifications	126
9.5	DC Specifications	127
9.6	AC Specifications	149
10	Ballout and Package Information	209
10.1	SoC Attributes	209
10.2	Package Diagrams	210
10.3	Ball Name and Function by Location	211
10.4	Alphabetical Ball Name List	259
11	Processor Core	270
11.1	Features	270
11.2	Platform Identification and CPUID	273
11.3	References	274
12	System Memory Controller	275
12.1	Signal Descriptions	275
12.2	Features	279
12.3	System Memory Controller (D-Unit) Message Registers	283
13	SoC Transaction Router	318
13.1	Transaction Router A-Unit Message Registers	320
13.2	SoC Transaction Router PCI Config Access IO Registers	323
13.3	Transaction Router B-Unit Message Registers	325
13.4	Transaction Router C-Unit PCI Registers	340



13.5	Transaction Router C-Unit Message Registers	346
13.6	Transaction Router P-Unit Message Registers	351
14	Graphics, Video and Display	405
14.1	Features	405
14.2	SoC Graphics Display	406
14.3	Display Pipes	407
14.4	Display Physical Interfaces	407
14.5	References	413
14.6	3D Graphics and Video	413
14.7	Features	414
14.8	VED (Video Encode/Decode)	416
14.9	PCI Configuration Registers	419
14.10	Memory Mapped Registers (1 of 2)	445
14.11	Memory Mapped Registers (2 of 2)	637
14.12	Memory Mapped Registers (Read Only)	1029
14.13	Memory Mapped Registers (Write Only)	1035
15	MIPI-Camera Serial Interface (CSI) and ISP	1039
15.1	Signal Descriptions	1039
15.2	Features	1041
15.3	Imaging Subsystem Integration	1044
15.4	Functional Description	1046
15.5	MIPI-CSI-2 Receiver	1048
15.6	Register Map	1050
15.7	Image Signal Processor PCI Configuration Registers	1052
15.8	Image Signal Processor Memory Mapped IO Registers	1078
16	Storage Control Cluster (eMMC, SDIO, SD Card)	1746
16.1	Signal Descriptions	1746
16.2	Features	1748
16.3	References	1750
16.4	Register Map	1751
16.5	SDIO for Wifi PCI Configuration Registers	1753
16.6	SDIO for Wifi Memory Mapped IO Registers	1765
16.7	SD Card PCI Configuration Registers	1809
16.8	SD Card Memory Mapped IO Registers	1821
16.9	eMMC 4.5 PCI Configuration Registers	1865
16.10	eMMC 4.5 Memory Mapped IO Registers	1877
17	Serial ATA (SATA)	1921
17.1	Signal Descriptions	1921
17.2	Features	1922
17.3	References	1924
17.4	Register Map	1925
17.5	SATA PCI Configuration Registers	1926
17.6	SATA Legacy IO Registers	1955
17.7	SATA Index Pair IO Registers	1961
17.8	SATA AHCI Memory Mapped IO Registers	1963
17.9	SATA Primary Read Command IO Registers	2000
17.10	SATA Primary Write Command IO Registers	2005
17.11	SATA Primary Read Control IO Registers	2007
17.12	SATA Primary Write Control IO Registers	2008
17.13	SATA Secondary Read Command IO Registers	2009



17.14	SATA Secondary Write Command IO Registers.....	2014
17.15	SATA Secondary Read Control IO Registers	2016
17.16	SATA Secondary Write Control IO Registers.....	2017
17.17	SATA Lane 0 Electrical Register Address Map	2019
17.18	SATA Lane 0 Electrical Register Address Map	2049
17.19	SATA Lane 1 Electrical Register Address Map	2066
17.20	SATA Lane 1 Electrical Register Address Map	2096
18	USB Host Controller Interfaces (xHCI, EHCI)	2113
18.1	Signal Descriptions	2113
18.2	USB 3.0 xHCI (Extensible Host Controller Interface)	2115
18.3	USB 2.0 Enhanced Host Controller Interface (EHCI).....	2116
18.4	References.....	2117
18.5	Register Map.....	2118
18.6	USB xHCI PCI Configuration Registers	2120
18.7	USB xHCI Memory Mapped I/O Registers	2163
18.8	USB EHCI PCI Configuration Registers	2345
18.9	USB EHCI Memory Mapped IO Registers	2369
18.10	USB EHCI Electrical Message Bus Registers	2426
19	USB Device Controller Interfaces (3.0, ULPI)	2442
19.1	USB Device Controller	2444
19.2	References.....	2445
19.3	Register Map.....	2445
19.4	USB 3.0 Device PCI Configuration Registers	2446
19.5	USB 3.0 Device PCI Configuration Registers	2455
19.6	USB 3.0 Device Memory Mapped I/O Registers	2460
19.7	USB 3.0 Device Memory Mapped I/O Registers	2641
20	Intel® High Definition Audio	2661
20.1	Signal Descriptions	2662
20.2	Features.....	2663
20.3	References.....	2663
20.4	Register Map.....	2664
20.5	HD Audio PCI Configuration Registers	2666
20.6	HD Audio Memory Mapped I/O Registers.....	2697
21	Low Power Engine (LPE) for Audio (I²S)	2797
21.1	Signal Descriptions	2797
21.2	Features.....	2798
21.3	Detailed Block Level Description.....	2799
21.4	Software Implementation Considerations	2802
21.5	Clocks	2804
21.6	SSP (I ² S)	2807
21.7	Programming Model	2812
21.8	Register Map.....	2817
21.9	Low Power Audio PCI Configuration Registers	2818
21.10	pci_mem Address Map.....	2826
21.11	Memory Mapped Shim Registers	2837
21.12	Low Power Audio I ² S0 Address Map.....	2864
21.13	Low Power Audio I ² S0 Address Map.....	2884
21.14	Low Power Audio I ² S0 Address Map.....	2904
21.15	Low Power Audio DMA0 Memory Mapped IO Registers	2924
21.16	Low Power Audio DMA1 Memory Mapped IO Registers	3037



22	Intel® Trusted Execution Engine (TXE)	3150
22.1	Features	3150
22.2	Register Map	3151
22.3	Intel® TXE PCI Configuration Registers.....	3153
23	PCI Express* 2.0	3179
23.1	Signal Descriptions	3179
23.2	Features	3180
23.3	References	3183
23.4	Register Map	3183
23.5	PCI Configuration Registers	3184
23.6	PCI Express* PCI Configuration Registers	3185
23.7	PCI Express* Lane 0 Electrical Address Map	3229
23.8	PCI Express* Lane 0 Electrical Address Map	3259
23.9	PCI Express* Lane 1 Electrical Address Map	3277
23.10	PCI Express* Lane 1 Electrical Address Map	3307
23.11	PCI Express* Lane 2 Electrical Address Map	3325
23.12	PCI Express* Lane 2 Electrical Address Map	3355
23.13	PCI Express* Lane 3 Electrical Address Map	3373
23.14	PCI Express* Lane 3 Electrical Address Map	3403
24	Serial IO (SIO) Overview	3420
24.1	Serial I/O (SIO) Register Map	3420
24.2	SIO DMA PCI Configuration Registers for SPI, HSUART, PWM	3421
24.3	SIO DMA Memory Mapped I/O Registers for SPI, HSUART, PWM	3430
24.4	SIO DMA PCI Configuration Registers for I ² C.....	3604
24.5	SIO DMA Memory Mapped I/O Registers for I2C	3613
25	SIO - Serial Peripheral Interface (SPI)	3788
25.1	Signal Descriptions	3788
25.2	Features	3789
25.3	Register Map	3792
25.4	SIO SPI PCI Configuration Registers.....	3793
25.5	SIO SPI Memory Mapped I/O Registers	3802
26	SIO - I²C Interface	3819
26.1	Signal Descriptions	3819
26.2	Features	3820
26.3	Use	3826
26.4	References	3827
26.5	Register Map	3827
26.6	SIO I ² C 0 PCI Configuration Registers	3829
26.7	SIO I ² C 0 Memory Mapped I/O Registers	3838
26.8	SIO I ² C 1 PCI Configuration Registers	3877
26.9	SIO I ² C 1 PCI Configuration Registers	3887
26.10	SIO I ² C 2 PCI Configuration Registers	3926
26.11	SIO I ² C 2 Memory Mapped I/O Registers	3936
26.12	SIO I ² C 3 PCI Configuration Registers	3975
26.13	SIO I ² C 3 Memory Mapped I/O Registers	3985
26.14	SIO I ² C 4 PCI Configuration Registers	4024
26.15	SIO I ² C 4 Memory Mapped I/O Registers	4034
26.16	SIO I ² C 5 PCI Configuration Registers	4073
26.17	SIO I ² C 5 Memory Mapped I/O Registers	4083



26.18	SIO I ² C 6 PCI Configuration Registers	4122
26.19	SIO I ² C 6 Memory Mapped I/O Registers	4132
27	SIO – High Speed UART	4171
27.1	Signal Descriptions	4171
27.2	Features	4172
27.3	Use	4174
27.4	Register Map	4175
27.5	SIO HSUART 0 PCI Configuration Registers	4177
27.6	SIO HSUART 0 Memory Mapped I/O Registers	4186
27.7	PCU PMC Memory Mapped I/O Registers	4219
27.8	SIO HSUART 1 PCI Configuration Registers	4253
27.9	SIO HSUART 0 Memory Mapped I/O Registers	4262
28	SIO – Pulse Width Modulation (PWM)	4295
28.1	Signal Descriptions	4295
28.2	Features	4296
28.3	Use	4297
28.4	Register Map	4297
28.5	SIO PWM 0 PCI Configuration Registers	4299
28.6	SIO PWM 0 Memory Mapped I/O Registers	4308
28.7	SIO PWM 1 PCI Configuration Registers	4311
28.8	SIO PWM 1 Memory Mapped I/O Registers	4320
29	Platform Controller Unit (PCU) Overview	4323
29.1	Features	4323
29.2	PCU iLB LPC Port 80h I/O Registers	4325
30	PCU – Power Management Controller (PMC)	4332
30.1	Signal Descriptions	4332
30.2	Features	4334
30.3	USB Per-Port Register Write Control	4343
30.4	References	4343
30.5	Register Map	4343
30.6	PCU PMC IO Registers	4344
30.7	PCU iLB PMC I/O Registers	4347
31	PCU – Serial Peripheral Interface (SPI)	4364
31.1	Signal Descriptions	4364
31.2	Features	4365
31.3	Use	4377
31.4	Register Map	4379
31.5	PCU SPI for Firmware Memory Mapped I/O Registers	4380
32	PCU – Universal Asynchronous Receiver/Transmitter (UART)	4414
32.1	Signal Descriptions	4414
32.2	Features	4415
32.3	Use	4417
32.4	UART Enable/Disable	4417
32.5	IO Mapped Registers	4418
32.6	PCU iLB UART IO Registers	4419
33	PCU – System Management Bus (SMBus)	4428
33.1	Signal Descriptions	4428



33.2	Features	4429
33.3	Use	4437
33.4	References	4437
33.5	Register Map	4437
33.6	PCU SMBUS PCI Configuration Registers	4439
33.7	PCU SMBUS Memory Mapped I/O Registers	4453
33.8	PCU SMBUS I/O Registers	4465
34	PCU – Intel® Legacy Block (iLB) Overview	4477
34.1	Signal Descriptions	4477
34.2	Features	4478
34.3	PCU iLB Interrupt Decode and Route	4480
35	PCU – iLB – Low Pin Count (LPC) Bridge	4514
35.1	Signal Descriptions	4514
35.2	Features	4515
35.3	Use	4520
35.4	References	4522
35.5	Register Map	4522
35.6	PCU iLB Low Pin Count (LPC) Bridge PCI Configuration Registers	4524
35.7	PCU iLB LPC BIOS Control Memory Mapped I/O Registers	4541
36	PCU – iLB – Real Time Clock (RTC)	4542
36.1	Signal Descriptions	4542
36.2	Features	4543
36.3	Interrupts	4544
36.4	References	4546
36.5	Register Map	4546
36.6	IO Mapped Registers	4546
36.7	Indexed Registers	4546
36.8	PCU iLB Real Time Clock (RTC) I/O Registers	4548
37	PCU – iLB – 8254 Timers	4550
37.1	Signal Descriptions	4550
37.2	Features	4551
37.3	Use	4551
37.4	Register Map	4554
37.5	IO Mapped Registers	4554
37.6	PCU iLB 8254 Timers IO Registers	4555
38	PCU – iLB – High Precision Event Timer (HPET)	4560
38.1	Features	4560
38.2	References	4562
38.3	Register Map	4562
38.4	Memory Mapped Registers	4562
38.5	PCU iLB High Performance Event Timer (HPET) Memory Mapped IO Registers	4563
39	PCU – iLB – GPIO	4571
39.1	Signal Descriptions	4571
39.2	Features	4571
39.3	Legacy Use	4572
39.4	Memory Mapped Use	4572
39.5	Register Map	4574
39.6	GPIO Registers	4574



39.7	PCU iLB GPIO S0 IO Addressed Registers	4576
39.8	PCU iLB GPIO S0 Memory Addressed Registers	4600
39.9	PCU iLB GPIO S5 IO Addressed Registers	5044
39.10	PCU iLB GPIO S5 Memory Address Map	5058
40	PCU – iLB – Interrupt Decoding and Routing	5282
40.1	Features	5282
41	PCU – iLB – IO APIC	5284
41.1	Features	5284
41.2	Use	5286
41.3	Indirect I/O APIC Registers	5287
41.4	PCU iLB IO APIC Memory Mapped I/O Registers	5288
42	PCU – iLB – 8259 Programmable Interrupt Controllers (PIC)	5290
42.1	Features	5290
42.2	IO Mapped Registers	5297
42.3	PCU iLB 8259 Interrupt Controller (PIC) I/O Registers	5299

Figures

Figure 1	SoC Block Diagram	30
Figure 2	Signals (1 of 2)	38
Figure 3	Signals (2 of 2)	39
Figure 4	Physical Address Space - DRAM & MMIO	72
Figure 5	Physical Address Space - Low MMIO	73
Figure 6	Physical Address Space - DOS DRAM	74
Figure 7	Physical Address Space - SMM and Non-Snoop Mappings	75
Figure 8	Bus 0 PCI Devices and Functions	81
Figure 9	Clocking Example	83
Figure 10	Idle Power Management Breakdown of the Processor Cores	93
Figure 11	Package C-state Entry and Exit	95
Figure 12	RTC Power Well Timing Diagrams	101
Figure 13	G3/S5 to S0 Cold Boot Sequence	103
Figure 14	S0 to S3 to S4/S5 (Power Down) Sequence without S0ix	106
Figure 15	Definition of Differential Voltage and Differential Voltage Peak-to-Peak	132
Figure 16	Definition of Pre-emphasis	132
Figure 17	eMMC DC Bus signal level	135
Figure 18	Definition of VHYS in Table 169	147
Figure 19	SVID Timing Diagram	152
Figure 20	DDR3L DQ Setup/Hold Relationship to/from DQSP/DQSN (Read Operation) ..	154
Figure 21	DDR3L DQ and DM Valid before and after DQSP/DQSN (Write Operation)	155
Figure 22	DDR3L Write Pre-amble Duration	155
Figure 23	DDR3L Write Post-amble Duration	155
Figure 24	DDR3L Command Signals Valid before and after CK Rising Edge	155
Figure 25	DDR3L CKE Valid before and after CK Rising Edge	156
Figure 26	DDR3L CS# Valid before and after CK Rising Edge	156
Figure 27	DDR3L ODT Valid before CK Rising Edge	156
Figure 28	DDR3L Clock Cycle Time	156
Figure 29	DDR3L Skew between System Memory Differential Clock Pairs (CKP/CKN)	157
Figure 30	DDR3L CK High Time	157




Figure 31	DDR3L CK Low Time	157
Figure 32	DDR3L DQS Falling Edge Output Access Time to CK Rising Edge	157
Figure 33	DDR3L DQS Falling Edge Output Access Time From CK Rising Edge	158
Figure 34	DDR3L CK Rising Edge Output Access Time to the 1st DQS Rising Edge	158
Figure 35	VGA_DDCDATA, and VGA_DDCCLK Timing Diagram	162
Figure 36	Input Glitch Rejection of Low-Power Receivers	163
Figure 37	MIPI-CSI-2 Clock Definition	164
Figure 38	MIPI-CSI-2 Data to Clock Timing Definitions	164
Figure 39	SD Card Timing Diagram (DDR50)	166
Figure 40	SD card Output Timing Diagram (SDR25)	166
Figure 41	SD Card Input Timing Diagram (SDR12)	167
Figure 42	SD Card Input Timing Diagram (Default)	168
Figure 43	SD card Output Timing Diagram (Default)	168
Figure 44	SD Card Input Timing Diagram (High Speed)	169
Figure 45	SD card Output Timing Diagram (High Speed)	170
Figure 46	SDIO Timing Diagram (DDR50)	171
Figure 47	SDIO Output Timing Diagram (SDR25)	172
Figure 48	SDIO Output Timing Diagram (SDR12)	172
Figure 49	SDIO Input Timing Diagram (SDR12/25)	173
Figure 50	eMMC* Output Timing Diagram (High Speed Mode)	174
Figure 51	eMMC* DDR Timings	174
Figure 53	eMMC Clock Signal Timing Diagram (HS200 Mode)	175
Figure 52	eMMC* Input Timing Diagram (High Speed Mode)	175
Figure 54	eMMC Input Timing Diagram (HS200 Mode)	176
Figure 55	USB Rise and Fall Times	180
Figure 56	USB Full Speed Load	181
Figure 57	USB Differential Data Jitter for Low/Full- Speed	181
Figure 58	USB Differential-to-EOP Transition Skew and EOP Width for Low/Full-Speed .	181
Figure 59	USB 3.0 Signals AC Specification	182
Figure 60	ULPI Timing Diagram	183
Figure 61	V/I Curves for HDA_SDO buffers	184
Figure 62	Maximum AC Waveforms for 1.5 V Signaling	187
Figure 63	I ² S Slave Port Timings in I ² S Mode	189
Figure 64	I ² S Slave Port Timings in PCM Short Frame Mode	189
Figure 65	I ² S Slave Port Timings in PCM Long Frame Mode	190
Figure 66	PCI Express* Transmitter Eye	192
Figure 67	PCI Express* Receiver Eye	192
Figure 68	SPI AC Timing	194
Figure 69	SPI NOR Timing	195
Figure 70	SMBus Transaction	196
Figure 71	SMBus Timeout	196
Figure 72	Valid Delay from Rising Clock Edge	197
Figure 73	Output Enable Delay	197
Figure 74	Float Delay	198
Figure 75	Setup and Hold Times	198
Figure 76	Definition of Timing for F/S-Mode Devices on I ² C Bus	200
Figure 77	Definition of Timing for High Speed-Mode Devices on I ² C Bus	202
Figure 78	UART Timing Diagram	203
Figure 79	JTAG Timing Diagram	204
Figure 80	TAP Valid Delay Timing Waveform	205
Figure 81	Test Reset (TAP_TRST#), Async GTL Input and PROCHOT# Timing Waveform	205
Figure 82	Clock Cycle Time	206



Figure 83	Clock Timing	206
Figure 84	Valid Delay from Rising Clock Edge	206
Figure 85	Setup and Hold Times	206
Figure 86	Float Delay	207
Figure 87	Pulse Width.....	207
Figure 88	Output Enable Delay	207
Figure 89	Differential Clock Waveform (Measured Single-ended)	208
Figure 90	Differential Clock Waveform (Using Differential Probe for Measurement).....	208
Figure 91	Package Mechanical Drawing	210
Figure 92	Soc Transaction Router Register Map.....	319
Figure 93	HDMI Overview	411
Figure 94	DisplayPort* Overview.....	412
Figure 95	3D Graphics Block Diagram	414
Figure 96	Camera Connectivity	1041
Figure 97	Image Processing Components	1044
Figure 98	MIPI-CSI Bus Block Diagram	1048
Figure 99	MIPI CSI Register Map.....	1051
Figure 100	SD Memory Card Bus Topology	1749
Figure 101	SDIO Device Bus Topology	1750
Figure 102	eMMC Interface	1750
Figure 103	Storage Control Cluster Register Map	1752
Figure 104	SATA Register Map	1925
Figure 105	xHCI and EHCI Port Mapping	2115
Figure 106	USB Host Controller Register Map	2119
Figure 107	Intel® HD Audio Register Map	2664
Figure 108	Audio Cluster Block Diagram	2800
Figure 109	Memory Connections for LPE	2801
Figure 110	SSP CCLK Structure	2805
Figure 111	Programmable Serial Protocol Format	2811
Figure 112	Programmable Serial Protocol Format (Consecutive Transfers)	2811
Figure 113	Low Power Engine for Audio Register Map	2817
Figure 114	PCIe* 2.0 Lane 0 Signal Example.....	3180
Figure 115	Root Port Configuration Options	3181
Figure 116	PCI Express Register Map	3184
Figure 117	SPI Interface Signals.....	3788
Figure 118	Clock Phase and Polarity	3790
Figure 119	SIO - SPI Register Map.....	3792
Figure 120	Data Transfer on the I ² C Bus.....	3821
Figure 121	START and STOP Conditions.....	3822
Figure 122	Seven-Bit Address Format.....	3823
Figure 123	Ten-Bit Address Format	3823
Figure 124	Master Transmitter Protocol	3824
Figure 125	Master Receiver Protocol.....	3825
Figure 126	START Byte Transfer	3825
Figure 127	SIO - I ² C Register Map	3828
Figure 128	UART Data Transfer Flow	4172
Figure 129	SIO - HSUART Register Map	4176
Figure 130	PWM Signals	4295
Figure 131	PWM Block Diagram	4296
Figure 132	SIO - PWM Register Map.....	4298
Figure 133	Flash Descriptor Sections.....	4368
Figure 134	Dual Output Fast Read Timing	4374
Figure 135	PCU - SMBus Register Map	4438



Figure 136	LPC Interface Diagram	4516
Figure 137	PCU - iLB - LPC Register Map	4523
Figure 138	SIO - I ² C Register Map.....	4574
Figure 139	Detailed Block Diagram	5285
Figure 140	MSI Address and Data	5286

Tables

Table 1	Intel® Atom™ Processor E3800 Product Family SKUs	37
Table 2	Platform Power Well Definitions	40
Table 3	Default Buffer State Definitions	41
Table 4	DDR3L System Memory Signals.....	42
Table 5	PCI Express* 2.0 Interface Signals	43
Table 6	USB 2.0 Interface Signals.....	43
Table 7	USB 2.0 HSIC Interface Signals.....	44
Table 8	USB 3.0 Interface Signals.....	44
Table 9	USB 2.0 Device Interface Signals.....	45
Table 10	USB 3.0 Device Interface Signals.....	45
Table 11	SATA 2.0 Interface Signals	46
Table 12	Integrated Clock Interface Signals	46
Table 13	Digital Display Interface Signals	47
Table 14	VGA Interface Signals	48
Table 15	MIPI CSI Interface Signals.....	48
Table 16	HD Audio Interface Signals	49
Table 17	LPE Interface Signals	50
Table 18	Storage Control Cluster (eMMC, SDIO, SD) Interface Signals.....	50
Table 19	High Speed UART Interface Signals.....	51
Table 20	SIO - I ² C Interface Signals	52
Table 21	SIO - Serial Peripheral Interface (SPI) Signals.....	52
Table 22	PCU - iLB - Real Time Clock (RTC) Interface Signals.....	53
Table 23	PCU - iLB - LPC Bridge Interface Signals.....	54
Table 24	PCU - Serial Peripheral Interface (SPI) Signals	54
Table 25	PCU - System Management Bus (SMBus) Interface Signals	55
Table 26	PCU - Power Management Controller (PMC) Interface Signals	55
Table 27	JTAG and Debug Interface Signals	56
Table 28	Miscellaneous Signals and Clocks.....	56
Table 29	GPIO Signals	57
Table 30	Power and Ground Pins	62
Table 31	Straps	64
Table 32	Fixed IO Register Access Method Example (P80 Register)	65
Table 33	Fixed Memory Mapped Register Access Method Example (IDX Register)	65
Table 34	Referenced IO Register Access Method Example (HSTS Register)	66
Table 35	Memory Mapped Register Access Method Example (_MBAR Register).....	66
Table 36	PCI Register Access Method Example (VID Register)	66
Table 37	PCI CONFIG_ADDRESS Register (IO PORT CF8h) Mapping	67
Table 38	PCI Configuration Memory Bar Mapping.....	68
Table 39	MCR Description.....	68
Table 40	MCRX Description.....	69
Table 41	Register Access Types and Definitions	69
Table 42	Fixed Memory Ranges in the Platform Controller Unit (PCU)	76
Table 43	Fixed IO Ranges in the Platform Controller Unit (PCU)	77



Table 44	Fixed IO Ranges in the SoC Transaction Router, Serial ATA and PCIe* Blocks..	78
Table 45	Movable IO Ranges Decoded by PCI Devices on the IO Fabric	78
Table 46	PCI Devices and Functions	79
Table 47	SoC Clock Inputs	84
Table 48	SoC Clock Outputs	84
Table 49	SoC Sx-States to SLP_S*#	87
Table 50	General Power States for System	88
Table 51	ACPI PM State Transition Rules	88
Table 52	Processor Core/ States Support	89
Table 53	SoC Graphics Adapter State Control	89
Table 54	Main Memory States.....	90
Table 55	PCI Express* States	90
Table 56	G, S and C State Combinations.....	90
Table 57	D, S and C State Combinations.....	91
Table 58	Coordination of Core/Module Power States at the Package Level.....	94
Table 59	RTC Power Well Timing Parameters	101
Table 60	S4/S5 to S0 (Power Up) Sequence	104
Table 61	S3/S4/S5 to S0 Cause of Wake Events	107
Table 62	Types of Resets	109
Table 63	Temperature Reading Based on DTS (If TJ-MAX =90oC)	111
Table 64	Intel® Atom™ Processor E3800 Product Family Thermal Specifications.....	114
Table 65	Storage Conditions Prior to Board Attach.....	115
Table 66	Power Rail DC Specs and Max Current	116
Table 67	VCC and VNN Currents	118
Table 68	VCC and VNN DC Voltage Specifications	118
Table 69	IMVP7.0 Voltage Identification Reference	119
Table 70	ILB RTC Crystal Specification.....	126
Table 71	Integrated Clock Crystal Specification	127
Table 72	R,G,B/VGA DAC Display DC specification (Functional Operating Range)	128
Table 73	VGA_DDCCLK, VGA_DDCDATA Signal DC Specification	129
Table 74	VGA_HSYNC and VGA_VSYNC DC Specification	129
Table 75	DDI Main Transmitter DC specification	129
Table 76	DDI AUX Channel DC Specification	130
Table 77	DDI DDC Signal DC Specification (DDI[1:0]_DDCDATA, DDI[1:0]_DDCCLK) .	131
Table 78	DDI DDC Misc Signal DC Specification (DDI[1:0]_HPD, DDI[1:0]_BKLTCTL, DDI[1:0]_VDDEN, DDI[1:0]_BKLTEN)	131
Table 79	PCI Express* DC Receive Signal Characteristics	133
Table 80	PCI Express* DC Transmit Characteristics	133
Table 81	PCI Express* DC Clock Request Input Signal Characteristics	133
Table 82	MIPI HS-RX/MIPI LP-RX Minimum, Nominal, and Maximum Voltage Parameters .	133
Table 83	SDIO DC Specification	134
Table 84	SD Card DC Specification	134
Table 85	eMMC 4.5 Signal DC Electrical Specifications	135
Table 86	TAP Signal Group DC Specification (TAP_TCK, TAP_TRSRT#, TAP_TMS, TAP_TDI)	136
Table 87	TAP Signal Group DC Specification (TAP_TDO).....	136
Table 88	TAP Signal Group DC Specification (TAP_PRDY#, TAP_PREQ#).....	137
Table 89	DDR3L Signal Group DC Specifications.....	137
Table 90	HDA Signal Group DC Specifications	138
Table 91	SATA TX/RX Signal Group DC Specifications	142
Table 92	LPC Signal Group DC Specification (LPC_V1P8V3P3_S = 1.8V (ILB_LPC_AD][3:0], ILB_LPC_FRAME#, ILB_LPC_SERIRQ, ILB_LPC_CLKRUN#)).....	142



Table 93	LPC Signal Group DC Specification LPC_V1P8V3P3_S = 3.3V (ILB_LPC_AD[3:0], ILB_LPC_FRAME#, ILB_LPC_CLKRUN#).....	143
Table 94	SPI Signal Group DC Specification (PCU_SPI_MISO, PCU_SPI_CS[1:0]#, PCU_SPI_MOSI, PCU_SPI_CLK).....	143
Table 95	Power Management 1.8V Suspend Well Signal Group DC Specification	144
Table 96	PMC_RSTBTN# 1.8V Core Well Signal Group DC Specification.....	145
Table 97	Power Management & RTC Well Signal Group DC Specification (PMC_RSMRST#, PMC_CORE_PWROK, ILB_RTC_RST#)	145
Table 98	iLB RTC Well DC Specification (ILB_RTC_TEST#)	145
Table 99	iLB RTC Oscillator Optional DC Specification (ILB_RTC_X1).....	145
Table 100	PROCHOT# Signal Group DC Specification	146
Table 101	SVID Signal Group DC Specification (SVID_DATA, SVID_CLK, SVID_ALERT#)	146
Table 102	GPIO 3.3V Core Well Signal Group DC Specification(GPIO_S0_SC[101:0]) ...	147
Table 103	GPIO 3.3V Suspend Well Signal Group DC Specification (GPIO_S5[43:0])	147
Table 105	GPIO 1.8V Suspend Well Signal Group DC Specification (GPIO_S5[43:0])	148
Table 104	GPIO 1.8V Core Well Signal Group DC Specification (GPIO_S0_SC[101:0]) ..	148
Table 106	I ² C Signal Electrical Specifications	149
Table 107	Generic Clock Jitter AC Specification	150
Table 108	25 MHz Platform Clock AC Specification	151
Table 109	SVID AC Specification	151
Table 110	DDR3L Interface Timing Specification	152
Table 111	DDI Main Transmitter AC specification	158
Table 112	DDI AUX Channel AC Specification	160
Table 113	R,G,B / VGA DAC Display AC Specification	160
Table 114	VGA_HSYNC and VGA_VSYNC AC Specification	161
Table 115	VGA_DDCDATA, and VGA_DDCCLK Timing Specification	162
Table 116	MIPI-CSI-2 Receiver Characteristics	162
Table 117	MIPI-CSI-2 Clock Signal Specification.....	163
Table 118	MIPI CSI 2 Data Clock Timing Specifications	164
Table 119	SD Card AC Specification	165
Table 120	SD Card Default Speed AC Specification	167
Table 121	SD Card High Speed AC Specification	168
Table 122	SDIO AC Specification	170
Table 123	eMMC 4.5 AC Characteristics.....	173
Table 124	eMMC 4.5 AC Characteristics.....	175
Table 125	SATA Specification and Interface Timings	176
Table 126	USB 2.0 AC specification (HIGH SPEED)	178
Table 127	USB 2.0 AC specification (FULL SPEED)	179
Table 128	USB 2.0 AC specification (LOW SPEED)	179
Table 129	ULPI Signals AC Specification	182
Table 130	HDA_SDO 1.5V Buffer AC Specification	184
Table 131	HDA_SDI[x] 1.5V Buffer AC Specification	185
Table 132	1.5V Parameters for Maximum AC Signalling Waveforms	187
Table 133	Resistance value for the AC rating Waveform	187
Table 134	I ² S AC Timings	188
Table 135	I ² S Master Mode AC Timing	190
Table 136	PCI Express* Interface Timings	191
Table 137	SUS Clock Timings	193
Table 138	PCU - SPI AC Specification.....	193
Table 139	PCU - SPI NOR AC Specification.....	194
Table 140	SMBUS Clock Signal Timings.....	195
Table 141	SMBus Timing	195



Table 142	LPC AC Specifications (with loop back from ILB_LPC_CLK[0] to ILB_LPC_CLK[1])	197
Table 143	I ² C Fast/Standard Mode AC Specifications	198
Table 144	AC Specification for High Speed Mode I ² C—Bus Devices	201
Table 145	UART AC Specification	203
Table 146	JTAG AC Specification.....	203
Table 147	Boundary Scan AC Specification.....	204
Table 148	Ball Listing by Location with GPIO Muxed Functions	211
Table 149	Memory Channel 0 DDR3L Signals.....	276
Table 150	Memory Channel 1 DDR3L Signals.....	277
Table 151	ECC Signals and Memory Channel 1 Signal Muxing	279
Table 152	ECC Signals	279
Table 153	Supported DDR3L DRAM Devices	280
Table 154	Supported DDR3L Memory Size Per Rank	280
Table 155	Supported DDR3L ECC Memory Size Per Rank	281
Table 156	Supported DDR3L SO-DIMM Size	281
Table 157	Summary of Memory Controller Message Bus Registers—Port 0x01	283
Table 158	Summary of A-Unit Message Bus Registers—Port 0x00	320
Table 159	Summary of PCI Configuration Space Access I/O Registers.....	323
Table 160	Summary of B-Unit Message Bus Registers—Port 0x03	325
Table 161	Summary of C-Unit PCI Configuration Registers—0/0/0.....	340
Table 162	Summary of C-Unit Message Bus Registers—Port 0x08	346
Table 163	Summary of Transaction Router P-Unit Message Bus Registers—Port 0x04 ...	351
Table 164	Analog Display Interface Signals	407
Table 165	Analog Port Characteristics.....	408
Table 166	Display Physical Interfaces Signal Names	409
Table 167	Graphics clock frequency by SKUs.....	414
Table 168	Bay Trail-M/D Stepping POR for Video Encode/Decode	416
Table 169	Hardware Accelerated Video Decode Codec Support	417
Table 170	Summary of Graphics, Video and Display PCI Configuration Registers—0/2/0	419
Table 171	Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB	445
Table 172	Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB	637
Table 173	Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB.....	1029
Table 174	Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB.....	1035
Table 175	CSI Signals.....	1040
Table 176	GPIO Signals.....	1040
Table 177	Imaging Capabilities.....	1042
Table 178	Summary of Image Signal Processor PCI Configuration Registers—0/2/0	1052
Table 179	Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMAADR	1078
Table 180	eMMC Signals.....	1747
Table 181	SDIO Signals.....	1747
Table 182	SD Card Signals	1748
Table 183	Summary of SDIO for Wifi PCI Configuration Registers—0/17/0	1753
Table 184	Summary of SDIO for Wifi Memory Mapped I/O Registers—BAR	1765
Table 185	Summary of SD Card PCI Configuration Registers—0/18/0	1809
Table 186	Summary of SD Card Memory Mapped I/O Registers—BAR	1821
Table 187	Summary of eMMC 4.5 PCI Configuration Registers—0/23/0	1865
Table 188	Summary of eMMC 4.5 Memory Mapped I/O Registers—BAR.....	1877
Table 189	Signals	1922
Table 190	SATA Feature List	1922
Table 191	SATA/AHCI Feature Matrix	1923
Table 192	Summary of SATA PCI Configuration Registers—0/19/0	1926



Table 193	Summary of SATA Legacy I/O Registers—LBAR	1955
Table 194	Summary of SATA Index Pair I/O Registers—ABAR	1961
Table 195	Summary of SATA AHCI Memory Mapped I/O Registers—ABAR.....	1963
Table 196	Summary of SATA Primary Read Command I/O Registers—PCMDIDEBA.....	2000
Table 197	Summary of SATA Primary Write Command I/O Registers—PCMDIDEBA	2005
Table 198	Summary of SATA Primary Read Control I/O Registers—PCTLIDEBA.....	2007
Table 199	Summary of SATA Primary Write Control I/O Registers—PCTLIDEBA	2008
Table 200	Summary of SATA Secondary Read Command I/O Registers—SCMDIDEBA..	2009
Table 201	Summary of SATA Secondary Write Command I/O Registers—SCMDIDEBA ..	2014
Table 202	Summary of SATA Secondary Read Control I/O Registers—SCTLIDEBA.....	2016
Table 203	Summary of SATA Secondary Write Control I/O Registers—SCTLIDEBA	2017
Table 204	Summary of SATA Lane 0 Electrical Message Bus Registers—0xA3 (Global Offset 2200h)	2019
Table 205	Summary of SATA Lane 0 Electrical Message Bus Registers—0xA3 (Global Offset 2280h)	2049
Table 206	Summary of SATA Lane 1 Electrical Message Bus Registers—0xA3 (Global Offset 2400h)	2066
Table 207	Summary of SATA Lane 1 Electrical Message Bus Registers—0xA3 (Global Offset 2480h)	2096
Table 208	USB 3 SS Signals	2114
Table 209	USB 2 FS/HS Signals	2114
Table 210	USB 2 HSIC Signals	2114
Table 211	Summary of USB xHCI PCI Configuration Registers—0/20/0.....	2120
Table 212	Summary of USB xHCI Memory Mapped I/O Registers—MBAR	2163
Table 213	Summary of USB EHCI PCI Configuration Registers—0/29/0.....	2345
Table 214	Summary of USB EHCI Memory Mapped I/O Registers—MBAR	2369
Table 215	Summary of USB EHCI Message Bus Registers—0x43.....	2426
Table 216	USB 3.0 Device Signals	2443
Table 217	USB ULPI Device Signals	2443
Table 218	Summary of USB 3.0 Device PCI Configuration Registers—0/22/0.....	2446
Table 219	Summary of USB 3.0 Device PCI Configuration Registers—0/22/0.....	2455
Table 220	Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR	2460
Table 221	Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR	2641
Table 222	Signals	2662
Table 223	Summary of HD Audio PCI Configuration Registers—0/27/0	2666
Table 224	Summary of HD Audio Memory Mapped I/O Registers—AZLBAR.....	2697
Table 225	LPE Signals.....	2798
Table 226	Clock Frequencies	2804
Table 227	M/N Values, Examples	2806
Table 228	M/N Configurable Fields	2807
Table 229	Programmable Protocol Parameters	2812
Table 230	Summary of Low Power Audio PCI Configuration Registers—0/21/0.....	2818
Table 231	Summary of Memory Mapped I/O Registers—0/21/0	2826
Table 232	Summary of LPE Shim Memory Mapped I/O Registers—BAR.....	2837
Table 233	Summary of Low Power Audio I ² S0 Memory Mapped I/O Registers—BAR	2864
Table 234	Summary of Low Power Audio I ² S0 Memory Mapped I/O Registers—BAR	2884
Table 235	Summary of Low Power Audio I ² S0 Memory Mapped I/O Registers—BAR	2904
Table 236	Summary of Low Power Audio DMA0 Memory Mapped I/O Registers—lpe_bridge.BAR	2924
Table 237	Summary of Low Power Audio DMA1 Memory Mapped I/O Registers—lpe_bridge.BAR	3037
Table 238	Summary of TXE PCI Configuration Registers—0/26/0	3153
Table 239	Signals	3180
Table 240	Possible Interrupts Generated From Events/Packets	3182



Table 241	Interrupt Generated for INT[A-D] Interrupts.....	3182
Table 242	Summary of PCI Express* PCI Configuration Registers—0/28/0	3185
Table 243	Summary of PCI Express* Lane 0 Electrical Message Bus Registers—0xA6 (Global Offset 200h)	3229
Table 244	Summary of PCI Express* Lane 0 Electrical Message Bus Registers—0xA6 (Global Offset 280h)	3259
Table 245	Summary of PCI Express* Lane 1 Electrical Message Bus Registers—0xA6 (Global Offset 400h)	3277
Table 246	Summary of PCI Express* Lane 1 Electrical Message Bus Registers—0xA6 (Global Offset 480h)	3307
Table 247	Summary of PCI Express* Lane 2 Electrical Message Bus Registers—0xA6 (Global Offset 600h)	3325
Table 248	Summary of PCI Express* Lane 2 Electrical Message Bus Registers—0xA6 (Global Offset 680h)	3355
Table 249	Summary of PCI Express* Lane 3 Electrical Message Bus Registers—0xA6 (Global Offset 800h)	3373
Table 250	Summary of PCI Express* Lane 3 Electrical Message Bus Registers—0xA6 (Global Offset 880h)	3403
Table 251	Summary of DMA 1 PCI Configuration Registers—0/30/0.....	3421
Table 252	Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR	3430
Table 253	Summary of SIO DMA 2 PCI Configuration Registers—0/24/0	3604
Table 254	Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR	3613
Table 255	SPI Modes	3790
Table 256	Summary of SPI PCI Configuration Registers—0/30/5	3793
Table 257	Summary of SPI Memory Mapped I/O Registers—BAR.....	3802
Table 258	I2C[6:0] Signals	3819
Table 259	I ² C Definition of Bits in First Byte	3823
Table 260	Summary of I ² C 0 PCI Configuration Registers—0/24/1	3829
Table 261	Summary of I ² C 0 Memory Mapped I/O Registers—BAR	3838
Table 262	Summary of I ² C 1 PCI Configuration Registers—0/24/2	3877
Table 263	Summary of I ² C 1 Memory Mapped I/O Registers—BAR	3887
Table 264	Summary of I ² C 2 PCI Configuration Registers—0/24/3	3926
Table 265	Summary of I ² C 2 Memory Mapped I/O Registers—BAR	3936
Table 266	Summary of I ² C 3 PCI Configuration Registers—0/24/4	3975
Table 267	Summary of I ² C 3 Memory Mapped I/O Registers—BAR	3985
Table 268	Summary of I ² C 4 PCI Configuration Registers—0/24/5	4024
Table 269	Summary of I ² C 4 Memory Mapped I/O Registers—BAR	4034
Table 270	Summary of I ² C 5 PCI Configuration Registers—0/24/6	4073
Table 271	Summary of I ² C 5 Memory Mapped I/O Registers—BAR	4083
Table 272	Summary of I ² C 6 PCI Configuration Registers—0/24/7	4122
Table 273	Summary of I ² C 6 Memory Mapped I/O Registers—BAR	4132
Table 274	UART 1 Interface Signals	4171
Table 275	UART 2 Interface Signals	4172
Table 276	Sclock Frequencies from M/N Settings	4173
Table 277	Baud Rates Achievable with Different DLAB Settings.....	4173
Table 278	Summary of HSUART 0 PCI Configuration Registers—0/30/3	4177
Table 279	Summary of HSUART 1 Memory Mapped I/O Registers—BAR	4186
Table 280	Summary of PCU iLB PMC Memory Mapped I/O Registers—PMC_BASE_ADDRESS 4219	
Table 281	Summary of HSUART 1 PCI Configuration Registers—0/30/4	4253
Table 282	Summary of HSUART 1 Memory Mapped I/O Registers—BAR	4262
Table 283	Example PWM Output Frequency and Resolution	4297
Table 284	Summary of PWM 0 PCI Configuration Registers—0/30/1	4299
Table 285	Summary of PWM 0 Memory Mapped I/O Registers—BAR	4308




Table 286	Summary of PWM 1 PCI Configuration Registers—0/30/2	4311
Table 287	Summary of PWM 1 Memory Mapped I/O Registers—BAR	4320
Table 288	Summary of PCU iLB LPC Port 80h I/O Registers—	4325
Table 289	PMC Signals.....	4332
Table 290	Transitions Due to Power Failure	4335
Table 291	Transitions Due to Power Button.....	4336
Table 292	System Power Planes.....	4337
Table 293	Causes of SMI and SCI.....	4340
Table 294	INIT# Assertion Causes	4343
Table 295	Summary of PCI iLB PMC I/O Registers	4344
Table 296	Summary of PCU iLB PMC I/O Registers—ACPI_BASE_ADDRESS.....	4347
Table 297	SPI Signals.....	4365
Table 298	SPI Flash Regions.....	4366
Table 299	Region Size Versus Erase Granularity of Flash Components	4367
Table 300	Region Access Control.....	4369
Table 301	Hardware Sequencing Commands and Opcode Requirements	4373
Table 302	Recommended Pinout for 8-Pin Serial Flash Device	4376
Table 303	Recommended Pinout for 16-Pin Serial Flash Device.....	4376
Table 304	Summary of PCU SPI for Firmware Memory Mapped I/O Registers— SPI_BASE_ADDRESS	4380
Table 305	UART Signals	4414
Table 306	Baud Rate Examples	4415
Table 307	Register Access List	4418
Table 308	Summary of PCU iLB UART I/O Registers—	4419
Table 309	SMBus Signal Names	4429
Table 310	I ² C Block Read.....	4433
Table 311	Enable for PCU_SMB_ALERT#	4435
Table 312	Enables for SMBus Host Events	4435
Table 313	Enables for the Host Notify Command	4435
Table 314	Host Notify Format	4436
Table 315	Summary of PCU SMBUS PCI Configuration Registers—0/31/3.....	4439
Table 316	Summary of PCU SMBUS Memory Mapped I/O Registers—SMB_Config_MBARL ... 4453	4453
Table 317	Summary of PCU SMBUS I/O Registers—SMB_Config_IOBAR	4465
Table 318	iLB Signals	4478
Table 319	NMI Sources.....	4479
Table 320	Summary of PCU iLB Interrupt Decode and Route Memory Mapped I/O Registers— ILB_BASE_ADDRESS	4480
Table 321	LPC Signals	4515
Table 322	SERIRQ, Stop Frame Width to Operation Mode Mapping	4519
Table 323	SERIRQ Interrupt Mapping.....	4520
Table 324	Summary of PCU iLB Low Pin Count (LPC) Bridge PCI Configuration Registers—0/ 31/0	4524
Table 325	Summary of PCU iLB LPC BIOS Control Memory Mapped I/O Registers— RCRB_BASE_ADDRESS	4541
Table 326	RTC Signals.....	4543
Table 327	Register Bits Reset by ILB_RTC_RST# Assertion	4545
Table 328	I/O Registers Alias Locations.....	4546
Table 329	RTC Indexed Registers.....	4547
Table 330	Summary of PCU iLB Real Time Clock (RTC) I/O Registers—	4548
Table 331	8254 Signals	4550
Table 332	Counter Operating Modes	4552
Table 333	Register Aliases	4554



Table 334	Summary of PCU iLB 8254 Timers I/O Registers—	4555
Table 335	8254 Interrupt Mapping.....	4562
Table 336	Summary of PCU iLB High Performance Event Timer (HPET) Memory Mapped I/O Registers—	4563
Table 337	GPIO Signals.....	4571
Table 338	Summary of PCU iLB GPIO S0 IO Registers—GPIO_BASE_ADDRESS	4576
Table 339	Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE	4600
Table 340	Summary of PCU iLB GPIO S5 IO Registers—GBASE + 80h.....	5044
Table 341	Summary of iLB GPIO S5 Memory Mapped I/O Registers—I/OBASE + 0x2000.....	5058
Table 342	Summary of PCU iLB I/O APIC Memory Mapped I/O Registers—	5288
Table 343	Interrupt Controller Connections	5291
Table 344	Interrupt Status Registers.....	5292
Table 345	Content of Interrupt Vector Byte.....	5292
Table 346	I/O Registers Alias Locations	5298
Table 347	Summary of PCU iLB 8259 Interrupt Controller (PIC) I/O Registers—	5299



Revision History


Revision Number	Description	Revision Date
1.0	Initial release.	October 2013
1.5	Chapter 2, "Physical Interfaces" - Updated the table details of the GPIO Signals for GPIO_S0_SC[046], GPIO_S0_SC[047], GPIO_S0_SC[048], GPIO_S5[15], GPIO_S5[16], GPIO_S5[17]. Chapter 5, "Integrated Clock" - Added table note (SoC Clock Outputs) that Intel recommends 25 MHz. 19.2 MHz is not validated. Chapter 6, "Power Management" - De-featured C6IS for all SKUs. - Updated the table details of the SoC Sx-States to SLPT_S*# for PMC_PLTRST# from 0 or 1 to High or Low to match platform understanding. - Remove VCC and VNN from Bay Trail-M/D SoC Power Rail DC Specs & Max Current table. Chapter 7, "Power Up and Reset Sequence" - Updated the figure and notes of the S0 to S3 to S4/S5 (Power Down) Sequence. - Updated the table of the S4/S5 to S0 (Power Up) Sequence for t3 parameter from 100 max to 95 min (no max). Chapter 9, "Electrical Specifications" - Updated the table details of the 25 MHz Platform Clock AC Specification. Chapter 11, "Processor Core" - Updated 11.1 note on Thermal management support. Chapter 12, "System Memory Controller" - Updated 12.2.2 table title and details for "Supported DDR3L Memory Size Per Rank" and "Supported DDR3L SO-DIMM Size". Chapter 16, "Storage Control Cluster (eMMC, SDIO, SD Card)" - Updated the supported SDIO/SD card bandwidth is up to 400Mbps per seconds. Chapter 18, "USB Host Controller Interfaces (xHCI, EHCI)" - Added figure note of the xHCI and EHCI Port Mapping. - Updated USB configuration register to correctly reflect the power well. Chapter 22, "Intel® Trusted Execution Engine (TXE)" - Updated chapter title to Intel® Platform Trust Technology (PTT). Chapter 29, "Platform Controller Unit (PCU) Overview" - Added a note to Platform Clock Support section that Intel recommends 25 MHz as 19.2 MHz is not validated.	December 2013
2.0	Chapter 7, "Power Up and Reset Sequence" - Updated the 7.2.2 note 4 - OK to swap V1P0A and V1P8A - Measurement point for timing is 90% (10% on power down) Chapter 9, "Electrical Specifications" - Added S3 power spec per measurements - Added generic clock jitter specs	February 2014



Revision Number	Description	Revision Date
2.5	Chapter 2, "Physical Interfaces" - Updated 2.28 RTC_VCC detail Chapter 7, "Power Up and Reset Sequence" - Updated the 7.2.2 note 7 - Updated the 7.3.1 note 6 and note 7 - Measurement point for timing is 90% (10% on power down) Chapter 9, "Electrical Specifications" - Added 9.5.18 GPIO VIH max and VIL min - Added 9.5.19 I2C VIH max and VIL min	April 2014
3.0	Chapter 2, "Physical Interfaces" - Updated RTC_VCC detail Chapter 7, "Power Up and Reset Sequence" - Updated slew rate to 10ms. - Measurement point for timing is 10% on power down Chapter 9, "Electrical Specifications" - Added 9.5.18 GPIO VIH max and VIL min - Added 9.5.19 I2C VIH max and VIL min Chapter 11, "Processor Core" - Removed support on C1E and C6C Chapter 14, "Graphics, Video and Display" - Updated 14.10.11 MSR (MSR_READ) offset to 180000h Chapter 16, "Storage Control Cluster (eMMC, SDIO, SD Card)" - Updated the Preset value feature to not PoR. - Updated SDIO support SDR12/25. Chapter 22, "Intel® Trusted Execution Engine (TXE)" - Updated name of chapter to "Intel® Trusted Execution Engine (TXE)". - Clarified use of descriptor mode and other requirements for the boot SPI. - Added registers for Intel® TXE.	July 2014



Revision Number	Description	Revision Date
3.5	Chapter 2, "Physical Interfaces" - Changed Figure 3 USB_ULPI_REFCLK to output Chapter 5, "Integrated Clock" - Updated the MCSI clock to 80-500 MHz Chapter 7, "Power Up and Reset Sequence" - Updated Table 58, max tolerance time, to 2000us - to avoid in rush current - removed PMC_SUSPWRDNACK from figure 13 - updated PMC_SUSPWRDNACK in figure 14 Chapter 9, "Electrical Specifications" - Added SPI NOR AC Spec - Updated GPIO Vih/Vil min and max - changed the I2S max clock frequency to 12.288 MHz Chapter 11, "Processor Core" - Added Note: "L1 has parity protection and L2 has an ECC Protection." Chapter 12, "System Memory Controller" - Removed DECCSTAT OFFSET 61h register Chapter 13, "SoC Transaction Router" - Updated register TRR - OFFSET B1h Chapter 22, "Intel® Trusted Execution Engine (TXE)" - updated the SSP to support 24 bits data sample sizes Chapter 29, "Platform Controller Unit (PCU) Overview" - De-Featured Top Swap Mechanism	September 2014



Revision Number	Description	Revision Date
3.6	Chapter 1, "Introduction" - Changed Figure 1, "SoC Block Diagram" on page 34 - Changed Chapter 1, "Terminology" - Changed Chapter 1, "Display Controller" - Changed Chapter 1, "Graphics and Media Engine" - Changed Chapter 1, "SKU List" Chapter 2, "Physical Interfaces" - Changed Figure 3, "Signals (2 of 2)" on page 43 - Changed Chapter 2, "Pin States Through Reset" - Changed Table 9, "USB 2.0 Device Interface Signals" on page 49 - Changed Table 13, "Digital Display Interface Signals" on page 51 - Changed Chapter 2, "PCU – iLB – Low Pin Count (LPC) Bridge Interface Signals" - Changed Table 24, "PCU - Serial Peripheral Interface (SPI) Signals" on page 58 - Changed Table 30, "Power and Ground Pins" on page 66 Chapter 5, "Integrated Clock" - Updated Table 48, "SoC Clock Outputs" on page 88 Chapter 6, "Power Management" - Updated Table 50, "General Power States for System" on page 92 - Changed Chapter 6, "Package C-States" Chapter 7, "Power Up and Reset Sequence" - Updated Chapter 7, "G3 to S0" - Updated Table 63, "S3/S4/S5 to S0 Cause of Wake Events" on page 111 - Updated Chapter 7, "S0 to S3 and S4/S5/G3 Sequence" - Updated Chapter 7, "S0 to S3 to S4/S5 (Power Down) Sequence without S0ix" - Updated Table 63, "S3/S4/S5 to S0 Cause of Wake Events" on page 111 - Updated Chapter 7, "Reset Behavior" Chapter 8, "Thermal Management" - Updated Chapter 8, "Thermal Management" Chapter 9, "Electrical Specifications" - Updated Table 66, "Intel Atom® Processor E3800 Product Family Thermal Specifications" on page 118 - Updated Table 68, "Power Rail DC Specs and Max Current" on page 120 - Updated Table 69, "VCC and VNN Currents" on page 122 - Updated Table 75, "VGA_DDCCLK, VGA_DDCDATA Signal DC Specification" on page 133 - Updated Table 79, "DDI DDC Signal DC Specification (DDI[1:0]_DDCDATA, DDI[1:0]_DDCCLK)" on page 135 - Updated Table 83, "PCI Express* DC Clock Request Input Signal Characteristics" on page 137 - Updated Table 86, "SD Card DC Specification" on page 138 - Updated Table 87, "eMMC 4.5 Signal DC Electrical Specifications" on page 139 - Updated Table 88, "TAP Signal Group DC Specification (TAP_TCK, TAP_TRSRT#, TAP_TMS, TAP_TDI)" on page 140 - Updated Table 89, "TAP Signal Group DC Specification (TAP_TDO)" on page 140 - Updated Table 90, "TAP Signal Group DC Specification (TAP_PRDY#, TAP_PREQ#)" on page 141 - Updated Table 97, "Power Management 1.8V Suspend Well Signal Group DC Specification" on page 148 - Updated Table 100, "iLB RTC Well DC Specification (ILB_RTC_TEST#)" on page 149 - Added Table 105, "GPIO 3.3V Suspend Well Signal Group DC Specification (GPIO_S5[43:0])" on page 151 - Updated Table 106, "GPIO 1.8V Core Well Signal Group DC Specification (GPIO_S0_SC[101:0])" on page 152 - Updated Table 107, "GPIO 1.8V Suspend Well Signal Group DC Specification (GPIO_S5[43:0])" on page 152 - Updated Table 108, "I2C Signal Electrical Specifications" on page 153	January 2015



Revision Number	Description	Revision Date
3.6	- Updated Table 140, "PCU - SPI NOR AC Specification" on page 197 - Updated Table 140, "PCU - SPI NOR AC Specification" on page 197 Chapter 12, "System Memory Controller" - Updated Chapter 12, "Features" Chapter 14, "Graphics, Video and Display" - Updated Chapter 14, "Features" - Updated Chapter 14, "Video Engine" - Updated Table 170, "Hardware Accelerated Video Decode Codec Support" on page 423 Chapter 15, "MIPI-Camera Serial Interface (CSI) and ISP" - Updated Chapter 15, "Features" Updated Table 178, "Imaging Capabilities" on page 1048 Chapter 16, "Storage Control Cluster (eMMC, SDIO, SD Card)" - Updated Chapter 16, "SDIO/SD Card Interface Features" Chapter 21, "Low Power Engine (LPE) for Audio (I²S)" - Updated Chapter 21, "External Timer" - Updated Table 227, "Clock Frequencies" on page 2817 Chapter 30, "PCU – Power Management Controller (PMC)" - Updated Table 292, "Transitions Due to Power Button" on page 4348 - Updated Chapter 30, "PMC_RSTBTN# Signal" - Updated Table 293, "System Power Planes" on page 4349 - Updated Table 294, "Causes of SMI and SCI" on page 4352 Chapter 31, "PCU – Serial Peripheral Interface (SPI)" - Updated Chapter 31, "Descriptor Mode" Chapter 32, "PCU – Universal Asynchronous Receiver/Transmitter (UART)" - Updated Chapter 32, "UART Enable/Disable" Chapter 33, "PCU – System Management Bus (SMBus)" - Added Chapter 33, "SPD Write Disable" Chapter 34, "PCU – Intel® Legacy Block (iLB) Overview" - Updated Chapter 34, "Non-Maskable Interrupt"	January 2015



Revision Number	Description	Revision Date
3.7	Chapter 1 - Remove eSATA capable from Section 1.2.8 Chapter 7.2.1 - Updated Table 60 - Updated Table 61 Chapter 9.3 - Updated Table 68, Added AC Voltage Tolerance for Platform Rail Chapter 9.6.1 - Removed Figure 19, Crystal Clock Timing - Removed Table 106, Crystal Clock Timings Chapter 9.5.8 - Updated Table 91 Chapter Note: - Updated Table 140 - Added Figure 68 Chapter 9.6.19 - Updated Table 142 - Updated Figure 69 Chapter 19.6.87 - Added Note to Bit Range 31 Section 23.6 - Removed Note from Bit Range 28 Chapter 39 - Added a note to Chapter 39, "Memory Mapped Use" - Updated Section 39.8.299 - Removed the VLV_GPIO_configuration_primer_presentation - Removed cross reverences from Bit Rages 30:24, 22:16, 14:8, and 6:0 - Updated Section 39.8.300 - Removed cross reverences from Bit Rages 30:24, 22:16, 14:8, and 6:0 - Updated Section 39.8.301 - Removed cross reverences from Bit Rages 30:24, 22:16, 14:8, and 6:0 - Updated Section 39.8.302 - Removed cross reverences from Bit Rages 30:24, 22:16, 14:8, and 6:0 - Updated Section 39.10.143 - Removed the VLV2_GPIO_configuration_primer_presentation - Removed cross reverences from Bit Rages 30:24, 22:16, 14:8, and 6:0 - Updated Section 39.10.144 - Removed cross reverences from Bit Rages 30:24, 22:16, 14:8, and 6:0 - Updated Section 39.10.145 - Removed cross reverences from Bit Rages 30:24, 22:16, 14:8, and 6:0 - Updated Section 39.10.146 - Removed cross reverences from Bit Rages 30:24, 22:16, 14:8, and 6:0	April 2015



Revision Number	Description	Revision Date
3.8	Chapter 4 - Updated Table 42 Section 7.2.2 - Updated Note page 106, Delay timing changed from 2000 μs to 10 ms Chapter 9.3 - Updated Table 68, Added AC Voltage Tolerance for Platform Rail	June 2015
3.9	Chapter 2.7 - Revised Table 29. Chapter 4.2 - Added New Table 44 - Revised Table 45 Chapter 4.2.2.1 - Added Table 44 - Revised Table 45 Chapter 9.5.6 - Revised Table 99 - Revised Table 100 and added Note 3. Chapter 9.5.18 - Revised Table 104 through Table 107 Chapter 9.6.4 - Revised Table 111 Chapter 9.6.10.1 - Revised Table 125 Chapter 12.3.9 , DRFC (DRFC)—Offset 8h - Revised Bit Range 14:12 Chapter 17 - Added Note 1 Chapter 26.2.3 - Revised last bullet Chapter 26.2.3.3 - Master-Receiver and Slave-Transmitter paragraph revised. Chapter 26.3.1 Revised Step 6 bullets	October 2015



Revision Number	Description	Revision Date
4.0	Section 2.24 - Updated Table 26 Section 2.27 - Revised Table 29 Section 7.3 - Revised Note for Figure 12 Section 9.3 - Revised Table 70 Section 9.6.4 - Revised Table 113 Section 13.4 - Revised Table 162 - Added Table 13.4.8, "CUNIT_MSG_CTRL_REG_EXT—Offset D8h" on page 349 Section 16 - Added Second Note Section 30.1 - Revised Table 292 Section 30.7.15 Revised TCO Timer reload value	May 2016



Revision Number	Description	Revision Date
4.1	Section 1.2.1 - Updated Chapter 11 cross reference Section 1.2.2 - Updated Chapter 12 cross reference Section 1.2.3 - Updated Chapter 14 cross reference Section 1.2.4 - Updated Chapter 14 cross reference Section 1.2.5 - Updated Chapter 15 cross reference Section 1.2.6 - Updated Chapter 6 cross reference Section 1.2.7 - Updated Chapter 15 cross reference Section 1.2.8 - Updated Chapter 17 cross reference Section 1.2.9 - Updated Chapter 18 cross reference Section 1.2.10 - Updated Chapter 18 cross reference Section 1.2.11 - Updated Chapter 19 cross reference Section 1.2.12.1 - Updated Chapter 21 cross reference Section 1.2.12.2 - Updated Chapter 20 cross reference Section 1.2.13 - Updated Chapter 16 cross reference Section 1.2.14 - Updated Chapter 22 cross reference Section 1.2.15 - Updated Chapter 24 cross reference Section 1.2.16 - Updated Chapter 29 cross reference Section 1.2.17 - Updated Chapter 10 cross reference Section 6.1 - Revised second bullet statement and added new bullet Section 6.3.4.3 - Added new bullet Section 6.3.5 - Revised first paragraph - Added new and updated Table Notes - Removed Figure 11. Package C-state Entry and Exit Section 6.3.5.2, Package C1 removed	July 2016




Revision Number	Description	Revision Date
4.1 Cont.	Section 6.3.5.3 Revised bullet Section 6.3.5.3 , Package C7 State added	July 2016
4.2	Section 2.24 - Updated Table 26 Section 7.3.1 - Updated Section 63 Section 12.2.1 - Updated Section 157 Revised Section 26.7.1 , "I2C Control Register (IC_CON)—Offset 0h" Revised Section 26.9.2 , "I2C Target Address Register (IC_TAR)—Offset 4h" Revised Section 27.6.3 , "Interrupt Identification Register and FIFO Control Register. (IIR_FCR)—Offset 8h" Section 30.1 - Updated Table 290	December 2016



Revision Number	Description	Revision Date
4.3	Section 4.1.2 - Updated Table 42 Section 7.3.1 - Updated Table 12 - Updated Table 61 Section 9.6.10.1 - Updated Table 127 Removed Chapter "PCU - SPI AC Specification" Removed Figure "SPI AC Timing" Section 17.1 - Updated Table 192 Section 18.9 - Updated Section 215 - Added Section 18.9.24, "USB Test Per Port Register 1 (USB2_TEST_PERPORT_REG1_LANE0/1/2/3) - Offset 4113h/4213h/4313h/4413h" - Added Section 18.9.25, "Per Port RCOMP High Speed Pull down Register (PER_PORT_RCOMP_HS_PULLDOWN_REGISTER_LANE0/1/2/3) - Offset 4123h/4223h/4323h/4423h" - Added Section 18.9.26, "USB Per Port (USB2_PER_PORT_2_LANE0/1/2/3) - Offset 4126h/4226h/4326h/4426h" Section 26.7.2 - Updated table Section 27.2.2 - Updated Table 280 Revised Section 34.2.1 Revised Section 35.2.2 Revised Section 35.3.2.2 Section 35.6 - Updated Table 325 - Added Section 35.6.25, "Manufacturer ID (PCIE_REG_MANUFACTURER_ID) - Offset F8h" Section 39.10.91 - Added Notes	October 2018

§ §



1 Introduction


The Intel Atom[®] Processor E3800 Product Family is the Intel Architecture (IA) SoC that integrates the next generation Intel[®] processor core, Graphics, Memory Controller, and I/O interfaces into a single system-on-chip solution.


The figures below show the system level block diagram of the SoC. Refer to the subsequent chapters for detailed information on the functionality of the different interface blocks.

Notes: Throughout this document Intel Atom[®] Processor E3800 Product Family is referred to as the SoC or Processor.

This document details features of the silicon only. For platform support and software, contact your Intel representative.

Figure 1. SoC Block Diagram





1.1 Terminology

Term	Description
ACPI	Advanced Configuration and Power Interface
Cold Reset	A Host reset with Power Cycle. See Table 135
CRT	Cathode Ray Tube
CRU	Clock Reset Unit
DP	Display Port
DTS	Digital Thermal Sensor
EMI	Electro Magnetic Interference
eDP	embedded Display Port
HDMI	High Definition Multimedia Interface. HDMI supports standard, enhanced, or high-definition video, plus multi-channel digital audio on a single cable. HDMI transmits all Advanced Television Systems Committee (ATSC) HDTV standards and supports 8-channel digital audio, with bandwidth to spare for future requirements and enhancements (additional details available at http://www.hdmi.org/).
IGD	Internal Graphics Unit
Intel® TXE	Intel® Trusted Execution Engine
LCD	Liquid Crystal Display
LPE	Low Power Engine
MIPI CSI	MIPI Camera Interface Specification
MPEG	Moving Picture Experts Group
MSI	Message Signaled Interrupt. MSI is a transaction initiated outside the host, conveying interrupt information to the receiving agent through the same path that normally carries read and write commands.
MSR	Model Specific Register, as the name implies, is model-specific and may change from processor model number (n) to processor model number (n+1). An MSR is accessed by setting ECX to the register number and executing either the RDMSR or WRMSR instruction. The RDMSR instruction will place the 64 bits of the MSR in the EDX: EAX register pair. The WRMSR writes the contents of the EDX: EAX register pair into the MSR.
PCIe*	PCI Express* (PCIe*) is a high-speed serial interface. The PCIe* configuration is software-compatible with the existing PCI specifications.
PWM	Pulse Width Modulation
Rank	A unit of DRAM corresponding to the set of SDRAM devices that are accessed in parallel for a given transaction. For a 64-bit wide data bus using 8-bit (x8) wide SDRAM devices, a rank would be eight devices. Multiple ranks can be added to increase capacity without widening the data bus, at the cost of additional electrical loading.
SCI	System Control Interrupt. SCI is used in the ACPI protocol.
SDRAM	Synchronous Dynamic Random Access Memory
SERR	System Error. SERR is an indication that an unrecoverable error has occurred on an I/O bus.

Term	Description
SMI	System Management Interrupt is used to indicate any of several system conditions (such as thermal sensor events, throttling activated, access to System Management RAM, chassis open, or other system state related activity).
SIO	Serial I/O
TMDS	Transition-Minimized Differential Signaling. TMDS is a serial signaling interface used in DVI and HDMI to send visual data to a display. TMDS is based on low-voltage differential signaling with 8/10b encoding for DC balancing.
VCO	Voltage Controlled Oscillator
Warm Reset	Host Reset without Power Cycle. See Table 134

1.2 Feature Overview

All features subject to software availability.

1.2.1 Processor Core


See [Chapter 11, “Processor Core”](#) for more details.

- Up to four IA-compatible low power Intel® processor cores
 - One thread per core
- Two-wide instruction decode, out of order execution
- On-die, 32 KB 8-way L1 instruction cache and 24 KB 6-way L1 data cache per core
- On-die, 1 MB, 16-way L2 cache, shared per two cores
- L1 has parity protection and L2 has ECC protection
- 36-bit physical address, 48-bit linear address size support
- Supported C-states: C0, C1, C6
- Supports Intel® Virtualization Technology (Intel® VT-x)

1.2.2 System Memory Controller

See [Chapter 12, “System Memory Controller”](#) for more details.

- Supports up to two channels of DDR3L
- 64 bit data bus for each channel
- ECC supported in single channel mode only
- Supports x8 and x16 DDR3L SDRAM device data widths
- Supports DDR3L with 1066 or 1333 MT/s data rates
 - Total memory bandwidth supported is 8.5 GB/s (for 1066 MT/s single channel) scalable to 21.3GB/s(for 1333 MT/s dual channel)
- Supports different physical mappings of bank addresses to optimize performance



- Out-of-order request processing to increase performance
- Aggressive power management to reduce power consumption
- Proactive page closing policies to close unused pages

1.2.3 Display Controller

See [Chapter 14, "Graphics, Video and Display"](#) for more details.

- Support 2 DDI ports to enable eDP 1.3, DP 1.1a, DVI, or HDMI 1.4a
- Support 2 panel power sequence for 2 eDP ports
- Support Audio on DP and HDMI
- Supports Intel® Display Power Saving Technology (DPST) 6.0, Panel Self Refresh (PSR) and Display Refresh Rate Switching Technology (DRRS)
- Supports one VGA port

Note: These feature are not applicable to the E3805 SKU.

1.2.4 Graphics and Media Engine

See [Chapter 14, "Graphics, Video and Display"](#) for more details.

- Intel's 7th generation (Gen 7) graphics and media encode/decode engine
- VED video decoder in addition to Gen 7 Media decoder
- Supports DX*11, OpenGL 3.0 (OGL 3.0), OpenCL 1.2 (OCL 1.2), OpenGLES 2.0 (OGLES 2.0)
- GPU shader is capable of up to 8 gigaflops
- 4x anti-aliasing
- Full HW acceleration for decode of Up to 1080p@60fps and 3x 4kx2k @30fps (H.264/JPEG/MJPEG/MVC/MPEG-2 /WMV9/VC1)
- Full HW acceleration for encode of Up to 1080p@60fps and 1x 4kx2k @30fps (H.264)
- Supports 2.0 Stereoscopic 3D Stretch
- Polyphase 8 tap scaling
- HD HQV

Note: These feature are not applicable to the E3805 SKU.

1.2.5 Image Signal Processor

See [Chapter 15, "MIPI-Camera Serial Interface \(CSI\) and ISP"](#) for more details.

- Support up to three MIPI CSI ports
- Support for up to 24MP sensors

- Supports Stereoscopic Video

1.2.6 Power Management

See [Chapter 6, “Power Management”](#) for more details.

- ACPI 5.0 support
- Processor states: C0-C6
- Display device states: D0, D3
- Graphics device states: D0, D3
- System sleep states: S0, S3, S4, S5
- Dynamic I/O power reductions (disabling sense amps on input buffers, tristating output buffers)
- Active power-down of display links
- Downloadable power management firmware

1.2.7 PCI Express*

The SoC has four PCI Express* lanes and up to four PCI Express root ports, each supporting the PCI Express Base specification Rev 2.0 at a maximum of 5 Gbit/s data transfer rates. The root ports configurations are flexible and can be configured to be (4) x1, (2) x2's, (1) x2 plus (2) x1's, and (1) x4.

See [Chapter 15, “MIPI-Camera Serial Interface \(CSI\) and ISP”](#) for more details.

1.2.8 SATA


See [Chapter 17, “Serial ATA \(SATA\)”](#) for more details.

- Two (2) SATA Revision 2.0 ports
- Legacy IDE (including IRQ)/Native IDE/AHCI appearance to OS
- Partial/Slumber power management modes with wake
- Capable of 3 Gbit/s transfer rate

1.2.9 USB xHCI Controller

See [Chapter 18, “USB Host Controller Interfaces \(xHCI, EHCI\)”](#) for more details.

- Supports USB 3.0/2.0/1.1
- Implements xHCI software host controller interface
- One USB 3.0 Super Speed (SS) port
- Four ports multiplexed with EHCI controller that are High Speed/Full Speed (HS/FS)
- Two High Speed Inter Chip (HSIC) ports compliant with USB 2.0



1.2.10 USB 2.0 EHCI Controller

See [Chapter 18, “USB Host Controller Interfaces \(xHCI, EHCI\)”](#) for more details.

- Internal Rate Matching Hub to support USB 1.1 to 2.0 devices
- Four Ports multiplexed with xHCI controller
- Enhanced EHCI descriptor caching

1.2.11 USB 2.0 (ULPI) and 3.0 Device

See [Chapter 19, “USB Device Controller Interfaces \(3.0, ULPI\)”](#) for more details.

- Supports one USB 3.0 SS port with USB device compatibility
- Supports one ULPI port with HS/LS support

1.2.12 Audio Controllers

1.2.12.1 Low Power Engine (LPE) Audio

LPE is a complete audio solution based on an internal audio processing engine, which includes three I²S output ports. See [Chapter 21, “Low Power Engine \(LPE\) for Audio \(I²S\)”](#) for more details.

LPE supports:

- I²S and DDI with dedicated DMA
- MP3, AAC, AC3/DD+, WMA9, PCM (WAV)

Note: Codecs supported depend on software and may be different.

1.2.12.2 Intel® High Definition Audio (Intel® HD Audio)

See [Chapter 20, “Intel® High Definition Audio”](#) for more details.

- Four in + four out streams (Only 3 used)
- One stream for each DDI, available for HDMI and DP
- No wake on audio (modem) support

1.2.13 Storage Control Cluster (eMMC, SDIO, SD)

See [Chapter 16, “Storage Control Cluster \(eMMC, SDIO, SD Card\)”](#) for more details.

- Supports one SDIO 3.0 controller
- Supports one eMMC 4.5 controller
- Supports one SDXC controller



1.2.14 Intel® Trusted Execution Engine (Intel® TXE)

Intel® TXE is a security co-processor used to enable security features.

See [Chapter 22, “Intel® Trusted Execution Engine \(TXE\)”](#) for more details.

Security features include:

- Isolated execution environment for crypto operations (SKU-enabled)
- Supports secure boot - with customer programmable keys to secure code

Note: The SoC requires TXE firmware in the PCU SPI flash image to function. Contact your Intel® representative for details.

1.2.15 Serial I/O (SIO)

See [Chapter 24, “Serial IO \(SIO\) Overview”](#) for links to more information about each interface.

- Controller for external devices via SPI, UART, I²C or PWM
- Each port is multiplexed with general purpose I/O for configurations flexibility
- Supports up to 7 I²C, 2 HSUART, 2 PWM, 1 SPI interface

1.2.16 Platform Control Unit (PCU)


The platform controller unit is a collection of HW blocks, including SMBus, UART, debug/boot SPI and Intel legacy block (iLB), that are critical to implement a Windows* compatible platform. See [Chapter 29, “Platform Controller Unit \(PCU\) Overview”](#) for links to more information about each interface.

Key PCU features include:

- SMBus Host controller - supports SMBus 2.0 specification
- Universal Asynchronous Receiver/Transmitter (UART) with COM1 interface
- A Serial Peripheral Interface (SPI) for Flash only - stores boot FW and system configuration data
- Intel Legacy Block (iLB) supports legacy PC platform features
 - RTC, Interrupts, Timers, General Purpose I/Os (GPIO) and Peripheral interface (LPC for TPM) blocks.

1.2.17 Package

This SoC is packaged in a Flip-Chip Ball Grid Array (FCBGA) package with 1170 solder balls with 0.593 mm (minimum) ball pitch. The package dimensions are 25mm x 27mm. See [Chapter 10, “Ballout and Package Information”](#) for more details.



1.2.18 SKU List

Table 1. Intel Atom® Processor E3800 Product Family SKUs

SKU	Processor Number	CPU	TDP (W)	Core LFM (MHz)/HFM (GHz)	Tj (°C)	GFX Normal / Burst (MHz)	DDR (MT/s)
Premium	E3845	4	10	500 / 1.91	-40 to 110	542 / 792	1333
Hi	E3827	2	8	500 / 1.75	-40 to 110	542 / 792	1333
Intermediate	E3826	2	7	533 / 1.46	-40 to 110	533 / 667	1066
Mid	E3825	2	6	533 / 1.33	-40 to 110	533 / NA	1066
Entry	E3815	1	5	533 / 1.46	-40 to 110	400 / NA	1066
Headless	E3805	2	3	533 / 1.33	-40 to 110	NA	1066

§

2 Physical Interfaces

Many interfaces contain physical pins. These groups of pins make up the physical interfaces. Because of the large number of interfaces and the small size of the package, Some interfaces share their pins with GPIOs, while others use dedicated physical pins. This chapter summarizes the physical interfaces, including the diversity in GPIO multiplexing options.

Figure 2. Signals (1 of 2)





Figure 3. Signals (2 of 2)




2.1 Pin States Through Reset

This chapter describes the states of each signal before, during and directly after reset. Additionally, Some signals have internal pull-up/pull-down termination resistors, and their values are also provided (Term). Termination tolerances are +/- 50% unless otherwise specified by electrical specs (PCIe*, and other differential termination). All signals with the "+" symbol are muxed and may not be available without configuration. See [Section 2.30, "Configurable IO: GPIO Muxing" on page 68](#).

Note: The internal termination resistor values & pull directions described in this chapter are the power-on defaults. Firmware & software may change the termination value, pull direction or disable the termination completely, on a pin-by-pin basis, using the _PCONF0 register corresponding to that pin.

Table 2. Platform Power Well Definitions

Power Type	Power Well Description
V1P05S	1.05 V rail. On in S0 only.
V1P0A	1.0 V rail. On in S0 through S4/5.
V1P0S	1.0 V rail. On in S0 only.
V1P24A	1.24 V rail. On in S0 through S4/5.
V1P24S	1.24 V rail. On in S0 only.
V1P35U	1.35 V rail. On in S0 through S3.
V1P8A	1.8 V rail. On in S0 through S4/5.
V1P35S	1.35 V rail. On in S0 only.
V1P8S	1.8 V rail. On in S0 only.
V3P3A	3.3 V rail. On in S0 through S4/5.
VAUD	1.5 V rail for HD Audio. 1.8 V rail for I ² S. On in S0 only.
VCC	Variable core rail. On in S0 only.
VLPC	1.8 or 3.3 V rail for LPC. On in S0 only.
VNN	Variable rail. On in S0 only.
VPCIESATA	1.0 V rail for PCIe* and SATA. On in S0 only.
VRTC	RTC voltage rail. On in S0 through G3.
VSDIO	1.8 or 3.3 V rail for SD3. On in S0 only.
VSFR	1.35 V rail for internal PLLs. On in S0 only.
VUSB2	3.3 V rail. On in S0 through S4/5.
VVGA_GPIO	3.3 V rail for VGA sideband. On in S0 only.

**Table 3. Default Buffer State Definitions**

Buffer State	Description
High-Z	The SoC places this output in a high-impedance state. For inputs, external drivers are not expected.
Do Not Care	The state of the input (driven or tristated) does not affect the SoC. For outputs, it is assumed that the output buffer is in a high-impedance state.
V _{OH}	The SoC drives this signal high with a termination of 50 Ω .
V _{OL}	The SoC drives this signal low with a termination of 50 Ω .
Unknown	The SoC drives or expects an indeterminate value.
V _{IH}	The SoC expects/requires the signal to be driven high.
V _{IL}	The SoC expects/requires the signal to be driven low.
Pull-up	This signal is pulled high by a pull-up resistor (internal value specified in "Term" column).
Pull-down	This signal is pulled low by a pull-down resistor (internal value specified in "Term" column).
Running/T	The clock is toggling, or the signal is transitioning.
Off	The power plane for this signal is powered down. The SoC does not drive outputs, and inputs should not be driven to the SoC. (VSS on output)

2.2 System Memory Controller Interface Signals


See [Chapter 12, "System Memory Controller"](#) for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.



Table 4. DDR3L System Memory Signals

				Default Buffer State				
Signal Name	Dir	Term	Plat. Power	S4/S5	S3	Reset	Enter S0	Notes
DRAM0_CKP[2,0]	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM0_CKN[2,0]	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM0_CS#[2,0]	O	-	V1P35U	Off	V _{OH}	V _{OH}	V _{OH}	
DRAM0_CKE[2,0]	O	-	V1P35U	Off	V _{OL}	V _{OL}	V _{OL}	
DRAM0_CAS#	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM0_RAS#	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM0_WE#	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM0_BS[2:0]	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM0_DRAMRST#	O	-	V1P35U	Off	-	-	-	
DRAM0_ODT[2,0]	O	-	V1P35U	Off	V _{OL}	V _{OL}	V _{OL}	
DRAM0_DQ[63:0]	I/O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM0_DM[7:0]	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM0_DQSP[7:0]	I/O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM0_DQSN[7:0]	I/O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_CKP[2,0]	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_CKN[2,0]	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_CKE[2,0]	O	-	V1P35U	Off	V _{OL}	V _{OL}	V _{OL}	
DRAM1_CS#[2,0]	O	-	V1P35U	Off	V _{OH}	V _{OH}	V _{OH}	
DRAM1_CAS#	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_RAS#	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_WE#	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_BS[2:0]	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_DRAMRST#	O	-	V1P35U	Off	-	-	-	
DRAM1_ODT[2,0]	O	-	V1P35U	Off	V _{OL}	V _{OL}	V _{OL}	
DRAM1_DQ[63:0]	I/O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_DM[7:0]	O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_DQSP[7:0]	I/O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM1_DQSN[7:0]	I/O	-	V1P35U	Off	High-Z	High-Z	High-Z	
DRAM_VDD_S4_PWROK	I	-	V1P35U	V _{IL}	V _{IH}	Unknown	V _{IH}	
DRAM_CORE_PWROK	I	-	V1P35U	V _{IL}	V _{IL}	Unknown	V _{IH}	
DRAM_VREF	I	-	V1P35U					
DRAM_RCOMP[2:0]	-	-	V1P35U					



2.3 PCI Express* 2.0 Interface Signals

See Chapter 21, “PCI Express* 2.0” for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 5. PCI Express* 2.0 Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
PCIE_TXP[3:0]	O	50	VPCIESATA	Off	Off	V _{OL}	V _{OL}	
PCIE_TXN[3:0]	O	50	VPCIESATA	Off	Off	V _{OL}	V _{OL}	
PCIE_RXP[3:0]	I	50	VPCIESATA	Off	Off	High-Z	High-Z	
PCIE_RXN[3:0]	I	50	VPCIESATA	Off	Off	High-Z	High-Z	
PCIE_CLKP[3:0]	O	-	V1P0S	Off	Off	Running/ V _{IL}	Running/ V _{IL}	
PCIE_CLKN[3:0]	O	-	V1P0S	Off	Off	Running/ V _{IL}	Running/ V _{IL}	
PCIE_CLKREQ[3:0]#†	I	20k(H)	V1P8S	Off	Off	Pull_up	Pull_up	
PCIE_RCOMP_P/N	-	-						

NOTE: All signals with the “+” symbol are muxed and may not be available without configuration.

2.4 USB 2.0 Host (EHCI/xHCI) Interface Signals

See Chapter 18, “USB Host Controller Interfaces (xHCI, EHCI)” for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 6. USB 2.0 Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
USB_DN[3:0]	I/O	-	VUSB2					
USB_DP[3:0]	I/O	-	VUSB2					
USB_OC[1:0]#†	I	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
USB_RCOMP_I	I	-	-					
USB_RCOMP_O	O	-	-					

NOTE: All signals with the “+” symbol are muxed and may not be available without configuration.



2.5 USB 2.0 HSIC Interface Signals

See [Chapter 18, “USB Host Controller Interfaces \(xHCI, EHCI\)”](#) for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 7. USB 2.0 HSIC Interface Signals

				Default Buffer State				
Signal Name	Dir	Term	Plat. Power	S4/S5	S3	Reset	Enter S0	Notes
USB_HSIC0_DATA	I/O	-	V1P24A	Running	Running	V _{OH}	Running	
USB_HSIC0_STROBE	I/O	-	V1P24A	V _{OH}				
USB_HSIC1_DATA	I/O	-	V1P24A			V _{OH}		
USB_HSIC1_STROBE	I/O	-	V1P24A	V _{OH}				
USB_HSIC_RCOMP	I	-	V1P24A			V _{OH}		

2.6 USB 3.0 (xHCI) Host Interface Signals

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.


Table 8. USB 3.0 Interface Signals

				Default Buffer State				
Signal Name	Dir	Term	Plat. Power	S4/S5	S3	Reset	Enter S0	Notes
USB3_TXN[0]	O	-	V1P0A					
USB3_TXP[0]	O	-	V1P0A					
USB3_RXN[0]	I	-	V1P0A					
USB3_RXP[0]	I	-	V1P0A					
USB3_REXT[0]	I	-	V1P0A	V _{OL}	V _{OL}	V _{OH}	V _{OH}	

2.7 USB 2.0 Device (ULPI) Interface Signals

See [Chapter 19, “USB Device Controller Interfaces \(3.0, ULPI\)”](#) for more details.

Note: S0ix is not supported for Bay Trail-I SKUs.

**Table 9. USB 2.0 Device Interface Signals**

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
USB_ULPI_CLK ⁺	I	20k(L)	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down	Pull-down
USB_ULPI_DATA[0:7] ⁺	I/O	20k(L)	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down	Pull-down
USB_ULPI_DIR ⁺	I	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	Pull-up
USB_ULPI_NXT ⁺	I	20k(L)	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down	Pull-down
USB_ULPI_STP ⁺	O	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	Pull-up
USB_ULPI_REFCLK ⁺	O	20k(L)	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down	Pull-down
USB_ULPI_RST# ⁺	O	-	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down	Pull-down

NOTE: All signals with the “+” symbol are muxed and may not be available without configuration.

2.8 USB 3.0 Device Interface Signals

See [Chapter 19, “USB Device Controller Interfaces \(3.0, ULPI\)”](#) for more details.

Note: S0ix is not supported for Bay Trail-I SKUs.

Table 10. USB 3.0 Device Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
USB3DEV_TXN[0]	O	-	V1P0S					
USB3DEV_TXP[0]	O	-	V1P0S					
USB3DEV_RXN[0]	I	-	V1P0S					
USB3DEV_RXP[0]	I	-	V1P0S					
USB3DEV_REXT[0]	I	-	V1P0S					



2.9 Serial ATA (SATA) 2.0 Interface Signals

See [Chapter 17, “Serial ATA \(SATA\)”](#) for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 11. SATA 2.0 Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
SATA_TXP[1:0]	O		VPCIESATA	Off	Off			
SATA_TXN[1:0]	O		VPCIESATA	Off	Off			
SATA_RXP[1:0]	I		VPCIESATA	Off	Off			
SATA_RXN[1:0]	I		VPCIESATA	Off	Off			
SATA_LED#†	O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	Pull-up
SATA_GP[1:0]†	I	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	Pull-down
SATA_RCOMP_P/N	-	-	1.0 V					


NOTE: All signals with the “†” symbol are muxed and may not be available without configuration.

2.10 Integrated Clock Interface Signals

See [Chapter 5, “Integrated Clock”](#) for more details..

Table 12. Integrated Clock Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
ICLK_OSCIN	I	-		Off	Off	Running	Running	
ICLK_OSCOUT	O	-		Off	Off	Running	Running	
ICLK_ICOMP	-	-		Off	Off			
ICLK_RCOMP	-	-		Off	Off			
ICLK_DRAM_TERM[1:0]	-	-	-	Pull-down	Pull-down	Pull-down	Pull-down	
ICLK_USB_TERM[1:0]	-	-	-	Pull-down	Pull-down	Pull-down	Pull-down	



2.11 Display - Digital Display Interface (DDI) Signals

See Chapter 14, “Graphics, Video and Display” for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 13. Digital Display Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
DDIO_TXP[3:0]	O		V1P0S	Off	Off			
DDIO_TXN[3:0]	O		V1P0S	Off	Off			
DDIO_AUXP	I/O		V1P0S	Off	Off			
DDIO_AUXN	I/O		V1P0S	Off	Off			
DDIO_BKLTCTL ⁺	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
DDIO_BKLTEN ⁺	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
DDIO_DDCCLK ⁺	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
DDIO_DDCDATA ⁺	I/O	20k(L) ₁	V1P8S	Off	Off	Pull-down ¹	Pull-up ²	
DDIO_HPD ⁺	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
DDIO_VDDEN ⁺	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
DDI_RCOMP_P/N	-	-	V1P0S					
DDI1_TXP[3:0]	O		V1P0S	Off	Off			
DDI1_TXN[3:0]	O		V1P0S	Off	Off			
DDI1_AUXP	I/O		V1P0S	Off	Off			
DDI1_AUXN	I/O		V1P0S	Off	Off			
DDI1_BKLTCTL ⁺	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
DDI1_BKLTEN ⁺	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
DDI1_DDCCLK ⁺	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
DDI1_DDCDATA ⁺	I/O	20k(L) ₁	V1P8S	Off	Off	Pull-down ¹	Pull-up ²	
DDI1_HPD ⁺	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
DDI1_VDDEN ⁺	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	

NOTE: 1. The internal pull-down resistor is disabled upon assertion of PMC_CORE_PWROK.

NOTE: 2. When the corresponding DDI port is used, an external pull-up resistor is required.

NOTE: 3. All signals with the “+” symbol are muxed and may not be available without configuration.



2.12 Display – VGA Interface Signals

See [Chapter 14, “Graphics, Video and Display”](#) for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 14. VGA Interface Signals

Signal Name	Dir	Term	Plat. Power	Type	Default Buffer State				
					S4/S5	S3	Reset	Enter S0	Notes
VGA_RED	O		VVGA_GPIO		Off	Off	High-Z		
VGA_GREEN	O		VVGA_GPIO		Off	Off	High-Z		
VGA_BLUE	O		VVGA_GPIO		Off	Off	High-Z		
VGA_IREF					Off	Off	V _{OL}		
VGA_IRTN					Off	Off	High-Z		
VGA_HSYNC	O		VVGA_GPIO		Off	Off	V _{OL}		
VGA_VSYNC	O		VVGA_GPIO		Off	Off	V _{OL}		
VGA_DDCCLK	O		VVGA_GPIO		Off	Off	High-Z		
VGA_DDCDATA	I/O		VVGA_GPIO		Off	Off	High-Z		


2.13 MIPI Camera Serial Interface (CSI) and ISP Interface Signals

See [Chapter 15, “MIPI-Camera Serial Interface \(CSI\) and ISP”](#) for more details.

Note: S0ix is not supported for Bay Trail-I SKUs.

Table 15. MIPI CSI Interface Signals (Sheet 1 of 2)

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
MCSI1_CLKN	I		V1P24S	Off				
MCSI1_CLKP	I		V1P24S	Off				
MCSI1_DN[0:3]	I		V1P24S	Off				
MCSI1_DP[0:3]	I		V1P24S	Off				
MCSI2_CLKN	I		V1P24S	Off				
MCSI2_CLKP	I		V1P24S	Off				
MCSI2_DN[0]	I		V1P24S	Off				
MCSI2_DP[0]	I		V1P24S	Off				

**Table 15. MIPI CSI Interface Signals (Sheet 2 of 2)**

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
MCSI3_CLKN	I		V1P24S	Off				
MCSI3_CLKP	I		V1P24S	Off				
MCSI_RCOMP	-		V1P24S	Off	High-Z	High-Z	High-Z	

2.14 Intel® High Definition Audio Interface Signals

See Chapter 20, “Intel® High Definition Audio” for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 16. HD Audio Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
HDA_SDO ⁺	O	20k(L)	VAUD	Off	Off	Pull-down	Pull-down	
HDA_SDI[1:0] ⁺	I	20k(L)	VAUD	Off	Off	Pull-down	Pull-down	
HDA_CLK ⁺	O	20k(L)	VAUD	Off	Off	Pull-down	Pull-down	
HDA_RST# ⁺	O	20k(L)	VAUD	Off	Off	Pull-down	Pull-down	
HDA_SYNC ⁺	O	20k(L)	VAUD	Off	Off	Pull-down	Pull-down	
HDA_LPE_RCOMP	-							

NOTE: All signals with the “+” symbol are muxed and may not be available without configuration.

2.15 Low Power Engine (LPE) for Audio (I²S) Interface Signals

See Chapter 21, “Low Power Engine (LPE) for Audio (I²S)” for more details.

Note: S0ix is not supported for Bay Trail-I SKUs.



Table 17. LPE Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
LPE_I2S[2:0]_CLK	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
LPE_I2S[2:0]_FRM	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
LPE_I2S[2:0]_DATAOUT	O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
LPE_I2S[2:0]_DATAIN	I	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	


2.16 Storage Control Cluster (eMMC, SDIO, SD) Interface Signals

See Chapter 16, “Storage Control Cluster (eMMC, SDIO, SD Card)” for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 18. Storage Control Cluster (eMMC, SDIO, SD) Interface Signals (Sheet 1 of 2)

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
MMC1_D[7:0]†	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
MMC1_CMD†	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
MMC1_CLK†	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
MMC1_RST#†	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
MMC1_RCOMP	I/O	-	V1P8S					
SD2_D[3:0]†	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SD2_CMD†	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SD2_CLK†	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
SD3_D[3:0]†	I/O	20k(H)	VSDIO	Off	Off	Pull-up	Pull-up	
SD3_CMD†	I/O	20k(H)	VSDIO	Off	Off	Pull-up	Pull-up	
SD3_CLK†	I/O	20k(L)	VSDIO	Off	Off	Pull-down	Pull-down	
SD3_PWREN#†	O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SD3_CD#†	I	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SD3_1P8EN†	O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	

**Table 18. Storage Control Cluster (eMMC, SDIO, SD) Interface Signals (Sheet 2 of 2)**

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
SD3_WP [†]	I	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SD3_RCOMP	-	-	VSDIO					

NOTE: All signals with the "†" symbol are muxed and may not be available without configuration.

NOTE: VSDIO voltage selection is controlled by SD3_1P8EN. 3.3V is default due to pull-down. VSDIO can be either 1.8 or 3.3 V when these VSDIO referenced signals are configured to be GPIO's to meet different platform requirements.

2.17 SIO – High Speed UART Interface Signals

See [Chapter 27, "SIO – High Speed UART"](#) for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 19. High Speed UART Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
SIO_UART1_RXD [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_UART1_TXD [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_UART1_RTS# [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_UART1_CTS# [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_UART2_RXD [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_UART2_TXD [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_UART2_RTS# [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_UART2_CTS# [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	

NOTE: All signals with the "†" symbol are muxed and may not be available without configuration.



2.18 SIO – I²C Interface Signals

See [Chapter 26, "SIO - I²C Interface"](#) for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 20. SIO - I²C Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
SIO_I2C0_DATA [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C0_CLK [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C1_DATA [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C1_CLK [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C2_DATA [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C2_CLK [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C3_DATA [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C3_CLK [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C4_DATA [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C4_CLK [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C5_DATA [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C5_CLK [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C6_DATA [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_I2C6_CLK [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	

NOTE: All signals with the "†" symbol are muxed and may not be available without configuration.


2.19 SIO – Serial Peripheral Interface (SPI) Signals

See [Chapter 25, "SIO - Serial Peripheral Interface \(SPI\)"](#) for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 21. SIO - Serial Peripheral Interface (SPI) Signals (Sheet 1 of 2)

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
SIO_SPI_CLK [†]	I/O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down	
SIO_SPI_CS# [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	

**Table 21. SIO - Serial Peripheral Interface (SPI) Signals (Sheet 2 of 2)**

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
SIO_SPI_MOSI ⁺	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
SIO_SPI_MISO ⁺	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	

NOTE: All signals with the “+” symbol are muxed and may not be available without configuration.

2.20 PCU – iLB – Real Time Clock (RTC) Interface Signals

See Chapter 36, “PCU – iLB – Real Time Clock (RTC)” for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 22. PCU - iLB - Real Time Clock (RTC) Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
ILB_RTC_X1	I	-	VRTC	Running	Running	Running	Running	
ILB_RTC_X2	O	-	VRTC	Running	Running	Running	Running	
ILB_RTC_RST#	I	-	VRTC	V _{IH}	V _{IH}	V _{IH}	V _{IH}	
ILB_RTC_TEST#	I	-	VRTC	V _{IH}	V _{IH}	V _{IH}	V _{IH}	
ILB_RTC_EXTPAD	O	-	VRTC					

2.21 PCU – iLB – Low Pin Count (LPC) Bridge Interface Signals

See Chapter 35, “PCU – iLB – Low Pin Count (LPC) Bridge” for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Note: If the VGA interface is used, VLPC must have a nominal voltage of 3.3V.



Table 23. PCU - iLB - LPC Bridge Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
ILB_LPC_AD[3:0] [†]	I/O	20k(H)	VLPC	Off	Off	Pull-up	Running	
ILB_LPC_FRAME# [†]	I/O	20k(H)	VLPC	Off	Off	V _{OH}	Running	
ILB_LPC_SERIRQ [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Running	
ILB_LPC_CLKRUN# [†]	I/O	20k(H)	VLPC	Off	Off	Pull-up	Running	
ILB_LPC_CLK[1:0] [†]	I/O	20k(L)	VLPC	Off	Off	V _{OL}	Running	
LPC_RCOMP	-		VLPC					

NOTE: All signals with the "†" symbol are muxed and may not be available without configuration.

2.22 PCU – Serial Peripheral Interface (SPI) Signals

See Chapter 31, "PCU – Serial Peripheral Interface (SPI)" for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 24. PCU - Serial Peripheral Interface (SPI) Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
PCU_SPI_CLK	O	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Running	
PCU_SPI_CS[0]#	O	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Running	
PCU_SPI_CS[1]# [†]	O	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Running	
PCU_SPI_MOSI	I/O	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
PCU_SPI_MISO	I	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	

NOTE: All signals with the "†" symbol are muxed and may not be available without configuration.



2.23 PCU – System Management Bus (SMBus) Interface Signals

See Chapter 33, “PCU – System Management Bus (SMBus)” for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 25. PCU - System Management Bus (SMBus) Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	
PCU_SMB_CLK [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
PCU_SMB_DATA [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
PCU_SMB_ALERT# [†]	I/O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	

2.24 PCU – Power Management Controller (PMC) Interface Signals

See Chapter 30, “PCU – Power Management Controller (PMC)” for more details.

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 26. PCU - Power Management Controller (PMC) Interface Signals (Sheet 1 of 2)

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
PMC_PLTRST#	O	-	V1P8A	V _{OL}	V _{OL}	V _{OL} ->V _{OH}	V _{OH}	
PMC_PWRBTN# [†]	I	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
PMC_RSTBTN#	I	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up	
PMC_SUSPWRDNACK [†]	O	-	V1P8A	V _{OH} /V _{OL}	V _{OH} /V _{OL}	V _{OH} /V _{OL}	V _{OH} /V _{OL}	
PMC_SUS_STAT# [†]	O	-	V1P8A	V _{OL}	V _{OL}	V _{OL}	V _{OH}	
PMC_SUSCLK[0] [†]	O	-	V1P8A	Running	Running	Running	Running	
PMC_SUSCLK[3:1] [†]	O	-						
PMC_SLP_S3#	O	-	V1P8A	V _{OL}	V _{OL}	V _{OH}	V _{OH}	
PMC_SLP_S4#	O	-	V1P8A	V _{OL}	V _{OH}	V _{OH}	V _{OH}	
PMC_WAKE_PCIE[0]#	I	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
PMC_WAKE_PCIE[3:1]# [†]	I	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
PMC_ACPRESENT	I	20k(L)	V1P8A	High-Z	Pull-down	Pull-down	Pull-down	
PMC_BATLOW#	I	20k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	

**Table 26. PCU - Power Management Controller (PMC) Interface Signals (Sheet 2 of 2)**

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
PMC_CORE_PWROK	I		VRTC	V _{IL}	V _{IL}	V _{IL}	V _{IH}	
PMC_RSMRST#	I		VRTC	V _{IH}	V _{IH}	V _{IH}	V _{IH}	

NOTE: All signals with the "+" symbol are muxed and may not be available without configuration.

2.25 JTAG and Debug Interface Signals

Note: S0ix is not supported for Bay Trail-M/D SKUs and Bay Trail-I SKUs.

Table 27. JTAG and Debug Interface Signals

Signal Name	Dir	Term	Plat. Power	Default Buffer State				
				S4/S5	S3	Reset	Enter S0	Notes
TAP_TCK	I	2k(L)	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down	
TAP_TDI	I	2k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
TAP_TDO	O	-	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
TAP_TMS	I	2k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
TAP_TRST#	I	2k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
TAP_PRDY#	O	2k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	
TAP_PREQ#	I	2k(H)	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up	

2.26 Miscellaneous Signals

Table 28. Miscellaneous Signals and Clocks (Sheet 1 of 2)

Signal Name	Dir	Term	Plat. Power	Default Buffer State			
				S4/S5	S3	Reset	Enter S0
SVID_DATA	I/O	2k(H)	V1P0S	Off	Off	Pull-up	Pull-up
SVID_CLK	O	2k(H)	V1P0S	Off	Off	Pull-up	Pull-up
SVID_ALERT#	I	2k(H)	V1P0S	Off	Off	Pull-up	Pull-up
PROCHOT#	I/O	2k(H)	V1P0S	Off	Off	Pull-up	Pull-up
ILB_8254_SPKR†	O	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up
ILB_NMI†	I	20k(H)	V1P8S	Off	Off	Pull-up	Pull-up




Table 28. Miscellaneous Signals and Clocks (Sheet 2 of 2)

Signal Name	Dir	Term	Plat. Power	Default Buffer State			
				S4/S5	S3	Reset	Enter S0
PMC_PLT_CLK[5:0]†	O	20k(L)	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_RCOMP	-	-	V1P8S	Off	Off	Active	Active

NOTE: All signals with the “†” symbol are muxed and may not be available without configuration.

NOTE: GPIO_RCOMP provides compensation for the following pins: GPIO_S5[10], PMC_SUSPWRDNACK, PMC_SUSCLK[0], GPIO_S5[13], PMC_SLP_S4#, PMC_SLP_S3#, USB_ULPI_RST#, PMC_ACPRESENT, PMC_WAKE_PCIE[0]#, PMC_BATLOW#, PMC_PWRBTN#, PMC_PLTRST#, GPIO_S5[17], PMC_SUS_STAT#, USB_OC[1:0]#, GPIO_S5[09:00], GPIO_S5[30:22], TAP_TCK, TAP_TRST#, TAP_TMS, TAP_TDI, TAP_TDO, TAP_PRDY#, TAP_PREQ#

2.27 GPIO Signals

Most GPIO's are configurable via multiplexors. See “[Chapter 10, “Ballout and Package Information”](#) for configuration options with the interfaces presented in this chapter.

Table 29. GPIO Signals (Sheet 1 of 5)

Signal Name	Dir	Term	Plat. Power	Default Buffer State			
				S4/S5	S3	Reset	Enter S0
GPIO_S0_SC[000]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[001]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[002]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[003]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[004]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[005]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[006]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[007]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[008]†	I/O	20k,L	VAUD	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[009]†	I/O	20k,L	VAUD	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[010]†	I/O	20k,L	VAUD	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[011]†	I/O	20k,L	VAUD	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[012]†	I/O	20k,L	VAUD	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[013]†	I/O	20k,L	VAUD	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[014]†	I/O	20k,L	VAUD	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[015]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[016]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[017]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up



Table 29. GPIO Signals (Sheet 2 of 5)

Signal Name	Dir	Term	Plat. Power	Default Buffer State			
				S4/S5	S3	Reset	Enter S0
GPIO_S0_SC[018] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[019] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[020] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[021] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[022] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[023] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[024] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[025] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[026] [†]	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[027] [†]	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[028] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[029] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[030] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[031] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[032] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[033] [†]	I/O	20k,L	VSDIO	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[034] [†]	I/O	20k,H	VSDIO	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[035] [†]	I/O	20k,H	VSDIO	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[036] [†]	I/O	20k,H	VSDIO	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[037] [†]	I/O	20k,H	VSDIO	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[038] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[039] [†]	I/O	20k,H	VSDIO	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[040] [†]	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[041] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[042] [†]	I/O	20k,H	VLPC	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[043] [†]	I/O	20k,H	VLPC	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[044] [†]	I/O	20k,H	VLPC	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[045] [†]	I/O	20k,H	VLPC	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[046] [†]	I/O	20k,H	VLPC	Off	Off	1	1
GPIO_S0_SC[047] [†]	I/O	20k,L	VLPC	Off	Off	0	0
GPIO_S0_SC[048] [†]	I/O	20k,L	VLPC	Off	Off	0	0
GPIO_S0_SC[049] [†]	I/O	20k,H	VLPC	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[050] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[051] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[052] [†]	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up




Table 29. GPIO Signals (Sheet 3 of 5)

Signal Name	Dir	Term	Plat. Power	Default Buffer State			
				S4/S5	S3	Reset	Enter S0
GPIO_S0_SC[053]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[054]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[055]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[056]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[057]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[058]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[059]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[060]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[061]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[062]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[063]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[064]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[065]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[066]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[067]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[068]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[069]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[070]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[071]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[072]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[073]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[074]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[075]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[076]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[077]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[078]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[079]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[080]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[081]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[082]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[083]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[084]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[085]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[086]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[087]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up



Table 29. GPIO Signals (Sheet 4 of 5)

Signal Name	Dir	Term	Plat. Power	Default Buffer State			
				S4/S5	S3	Reset	Enter S0
GPIO_S0_SC[088]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[089]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[090]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[091]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[092]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[093]†	I/O	20k,H	V1P8S	Off	Off	Pull-up	Pull-up
GPIO_S0_SC[094]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[095]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[096]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[097]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[098]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[099]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[100]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S0_SC[101]†	I/O	20k,L	V1P8S	Off	Off	Pull-down	Pull-down
GPIO_S5[00]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[01]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[02]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[03]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[04]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[05]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[06]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[07]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[08]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[09]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[10]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[11]†	I/O	-	V1P8A	0/1	0/1	0	0/1
GPIO_S5[12]†	I/O	-	V1P8A	T	T	T	T
GPIO_S5[13]†	I/O	-	V1P8A	0	0	0	0/1
GPIO_S5[14]†	I/O	-	V1P8A	0	0	0	0/1
GPIO_S5[15]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[16]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[17]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[18]†	I/O	-	V1P8A	0	0	0	1
GPIO_S5[19]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[20]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up

Table 29. GPIO Signals (Sheet 5 of 5)

Signal Name	Dir	Term	Plat. Power	Default Buffer State			
				S4/S5	S3	Reset	Enter S0
GPIO_S5[21]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[22]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[23]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[24]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[25]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[26]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[27]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[28]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[29]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[30]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[31]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[32]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[33]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[34]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[35]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[36]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[37]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[38]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[39]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[40]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[41]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down
GPIO_S5[42]†	I/O	20k,H	V1P8A	Pull-up	Pull-up	Pull-up	Pull-up
GPIO_S5[43]†	I/O	20k,L	V1P8A	Pull-down	Pull-down	Pull-down	Pull-down

2.28 Power And Ground Pins

Power Rail Ball Name Format: [Function]_[Voltage]_[S-State]{_[Filter]}:


- [Function]: The SoC function associated with the power rail.
— E.g CORE, USB, ...
- [Voltage]: The nominal voltage associated with the power rail.
— E.g. 1P05, 3P3, VCC, ...
- [S-State]: The ACPI system state, from S0 to G3, when the this rail is turned off.
- [Filter]: An optional indicator that one or more power rail balls have unique filtering requirements or requirement to be uniquely identified.



Note: The Resume power well is a set of supply rails (where [S-State] = G3) that must be powered even when S3/4/5 states aren't used. The "Resume Well" is also referred to as the "Suspend Power Well", "Always on/SUS", "SUS power", or "SUS well".

Table 30. Power and Ground Pins (Sheet 1 of 2)

Power Rails	Platform Power	Nominal Voltages	First Off State
CORE_V1P05_S3	V1P05S	1.05 V	S3
CORE_VCC_S3	VCC	Variable	S3
CORE_VCC_SENSE	See CORE_VCC_S3		
CORE_VSS_SENSE	-	-	-
DDI_V1P0_S3	V1P0S	1.0 V	S3
DRAM_V1P0_S3	V1P0S	1.0 V	S3
DRAM_V1P35_S3_F1	VSFR	1.35 V	S3
DRAM_VDD_S4	V1P35U	1.35 V	S4
GPIO_V1P0_S3	V1P0S	1.0 V	S3
HDA_LPE_V1P5V1P8_S3	VAUD	1.5/1.8 V	S3
ICLK_V1P35_S3_F1	VSFR	1.35 V	S3
ICLK_V1P35_S3_F2	VSFR	1.35 V	S3
LPC_V1P8V3P3_S3	VLPC	1.8/3.3 V	S3
MIPI_V1P24_S3	V1P24S	1.24 V	S3
MIPI_V1P8_S3	V1P8S	1.8 V	S3
PCIE_SATA_V1P0_S3	VPCIESATA	1.0 V	S3
PCIE_V1P0_S3	VPCIESATA	1.0 V	S3
PCU_V1P8_G3	V1P8A	1.8 V	G3
PCU_V3P3_G3	V3P3A	3.3 V	G3
PMC_V1P8_G3	V1P8A	1.8 V	G3
RTC_VCC	VRTC	2.0-3.0 at SoC V3P3A(pre diode drop)	(normally battery backed)
SATA_V1P0_S3	VPCIESATA	1.0 V	S3
SD3_V1P8V3P3_S3	VSDIO	1.8/3.3 V	S3
SVID_V1P0_S3	V1P0S	1.0 V	S3
UNCORE_V1P0_G3	V1P0A	1.0 V	G3
UNCORE_V1P0_S3	V1P0S	1.0 V	S3
UNCORE_V1P35_S3_F1	VSFR	1.35 V	S3
UNCORE_V1P35_S3_F2	VSFR	1.35 V	S3
UNCORE_V1P35_S3_F3	VSFR	1.35 V	S3

**Table 30. Power and Ground Pins (Sheet 2 of 2)**

Power Rails	Platform Power	Nominal Voltages	First Off State
UNCORE_V1P35_S3_F4	VSFR	1.35 V	S3
UNCORE_V1P35_S3_F5	VSFR	1.35 V	S3
UNCORE_V1P35_S3_F6	VSFR	1.35 V	S3
UNCORE_V1P8_G3	V1P8A	1.8 V	G3
UNCORE_V1P8_S3	V1P8S	1.8 V	S3
UNCORE_VNN_S3	VNN	Variable	S3
UNCORE_VNN_SENSE	See UNCORE_VNN_S3		
USB_HSIC_V1P24_G3	V1P24A	1.24 V	G3
USB_ULPI_V1P8_G3	V1P8A	1.8 V	G3
USB_V1P0_S3	V1P0S	1.0 V	S3
USB_V1P8_G3	V1P8A	1.8 V	G3
USB_V3P3_G3	VUSB2	3.3 V	G3
USB_VSSA	-	-	-
USB3_V1P0_G3	V1P0A	1.0 V	G3
USB3DEV_V1P0_S3	V1P0S	1.0 V	S3
VGA_V1P0_S3	V1P0S	1.0 V	S3
VGA_V1P35_S3_F1	VSFR	1.35 V	S3
VGA_V3P3_S3	VVGA_GPIO	3.3 V	S3
VSS	-	-	-
VSSA	-	-	-

Note: USB_HSIC_V1P24_G3 pin(s) can be connected to V1P0A platform rail if USB HSIC is not used. MIPI_V1P24_S3 can be grounded if MIPI interfaces (CSI) aren't used.

Note: If the VGA interface is used, LPC_V1P8V3P3_S3 must have a nominal voltage of 3.3V.

2.29 Hardware Straps

All straps are sampled on the rising edge of PMC_CORE_PWROK. Defaults are based on internal termination.

Table 31. Straps

Signal Name	Function	Default	Strap Exit	Strap Description
GPIO_S0_SC[056]	Legacy	1b	PMC_CORE_PWROK de-asserted	Top Swap (A16 Override) 0 = Top address bit is inverted 1 = Top address bit is unchanged
GPIO_S0_SC[063]	Legacy	1b	PMC_CORE_PWROK de-asserted	BIOS Boot Selection 0 = LPC 1 = SPI
GPIO_S0_SC[065]	Legacy	1b	PMC_CORE_PWROK de-asserted	Security Flash Descriptors 0 = Override 1 = Normal Operation
DDIO_DDCDATA	Display	0b	PMC_CORE_PWROK de-asserted	DDIO Detect 0 = DDIO not detected 1 = DDIO detected
DDI1_DDCDATA	Display	0b	PMC_CORE_PWROK de-asserted	DDI1 Detect 0 = DDI1 not detected 1 = DDI1 detected


2.30 Configurable IO: GPIO Muxing

Not all interfaces may be active at the same time. To provide flexibility, some interfaces are muxed with configurable IO balls. An interface's signal is selected by a function number. See [Section 10.3, "Ball Name and Function by Location" on page 214](#) for details of which balls are muxed, and what functions are available by ball.

Note: Configurable IO defaults to function 0 at boot. All configurable IO with GPIO's for function 0 default to input at boot.

2.31 Reserved Pins

Reserved pins are non functional pins. Unless otherwise specified in this document or related collateral, reserved pins should not be connected to anything. RSVD_GND pins must be connect to the common ground plane (VSS), but don't provide a return path for currents.



3 Register Access Methods

There are six different common register access methods:

- Fixed IO Register Access
- Fixed Memory Mapped Register Access
- IO Referenced Register Access
- Memory Referenced Register Access
- PCI Configuration Register Access (Indirect - via Memory or IO registers)
- Message Bus Register Access (Indirect - via PCI Configuration Registers)

3.1 Fixed IO Register Access

Fixed IO registers are accessed by specifying their 16-bit address in a PORT IN and/or PORT OUT transaction from the CPU core. This allows direct manipulation of the registers. Fixed IO registers are unmovable register in IO space.

Table 32. Fixed IO Register Access Method Example (P80 Register)

Type: I/O Register (Size: 32 bits)	P80: 80h
--	-----------------

3.2 Fixed Memory Mapped Register Access

Fixed Memory Mapped IO (MMIO) registers are accessed by specifying their 32/36-bit address in a memory transaction from the CPU core. This allows direct manipulation of the registers. Fixed MMIO registers are unmovable registers in memory space.

Table 33. Fixed Memory Mapped Register Access Method Example (IDX Register)

Type: Memory Mapped I/O Register (Size: 32 bits)	IDX: FEC00000h
--	-----------------------

3.3 IO Referenced Register Access

IO referenced registers use programmable base address registers (BARs) to select a range of IO addresses that it will use to decode PORT IN and/or PORT OUT transactions from the CPU to directly access a register. Thus, the IO BARs act as pointers to blocks of actual IO registers. To access an IO referenced register for a specific IO base address, start with that base address and add the register's offset. Example pseudo code for an IO referenced register read is shown below:

```
Register_Snapshot = IOREAD([IO_BAR]+Register_Offset)
```



Base address registers are often located in the PCI configuration space and are programmable by the BIOS/OS. Other base address register types may include fixed memory registers, fixed IO registers or message bus registers.

Table 34. Referenced IO Register Access Method Example (HSTS Register)

Type: I/O Register (Size: 8bits)	HSTS: [_IOBAR] + 0h
	_IOBAR Type: PCI Configuration Register (Size: 32 bits)
	_IOBAR Reference: [B:0, D:31, F:3] + 20h

3.4 Memory Referenced Register Access

The SoC uses programmable base address registers (BARs) to set a range of physical address (memory) locations that it will use to decode memory reads and writes from the CPU to directly access a register. These BARs act as pointers to blocks of actual memory mapped IO (MMIO) registers. To access a memory referenced register for a specific base address, start with that base address and add the register's offset. Example pseudo code for a read is shown below:

```
Register_Snapshot = MEMREAD([Mem_BAR]+Register_Offset)
```

Base address registers are often located in the PCI configuration space and are programmable by the BIOS/OS. Other common base address register types include fixed memory registers and IO registers that point to MMIO register blocks.

Table 35. Memory Mapped Register Access Method Example (_MBAR Register)

Type: Memory Mapped I/O Register (Size: 8bits)	HSTS: [_MBAR] + 0h
	_MBAR Type: PCI Configuration Register (Size: 32 bits)
	_MBAR Reference: [B:0, D:31, F:3] + 10h

3.5 PCI Configuration Register Access

Access to PCI configuration space registers is performed through one of two different configuration access methods (CAMs):

- IO indexed - PCI CAM
- Memory mapped - PCI Enhanced CAM (ECAM)

Each PCI function has a standard PCI header consisting of 256 bytes for the IO access scheme (CAM), or 4096 bytes for the enhanced memory access method (ECAM). Invalid read accesses return binary strings of 1s.

Table 36. PCI Register Access Method Example (VID Register)

Type: PCI Configuration Register (Size: 16bits)	VID: [B:0, D:31, F:3] + 0h
---	-----------------------------------



3.5.1 PCI Configuration Access - CAM: IO Indexed Scheme

Accesses to configuration space using the IO method relies on two 32-bit IO registers:

- **CONFIG_ADDRESS** - IO Port CF8h
- **CONFIG_DATA** - IO Port CFCh

These two registers are both 32-bit registers in IO space. Using this indirect access mode, software uses CONFIG_ADDRESS (CF8h) as an index register, indicating which configuration space register to access, and CONFIG_DATA (CFCh) acts as a window to the register pointed to in CONFIG_ADDRESS. Accesses to CONFIG_ADDRESS (CF8h) are internally captured. Upon a read or write access to CONFIG_DATA (CFCh), configuration cycles will be generated to the PCI function specified by the address captured in CONFIG_ADDRESS. The format of the address is shown below.

Table 37. PCI CONFIG_ADDRESS Register (IO PORT CF8h) Mapping

Field	CONFIG_ADDRESS Bits
Enable PCI Config. Space Mapping	31
Reserved	30:24
Bus Number	23:16
Device Number	15:11
Function Number	10:08
Register/Offset Number	07:02

Note: Bit 31 of CONFIG_ADDRESS must be set for a configuration cycle to be generated.

Pseudo code for a PCI register read is shown below:

- MyCfgAddr[23:16] = bus; MyCfgAddr[15:11] = device; MyCfgAddr[10:8] = funct;
- MyCfgAddr[7:2] = dWordMask(offset); MyCfgAddr[31] = 1;
- IOWRITE(0xCF8, MyCfgAddr)
- Register_Snapshot = IOREAD(0xCFCh)

3.5.2 PCI Configuration Access - ECAM: Memory Mapped Scheme

A flat, 256 MiB memory space may also be allocated to perform configuration transactions. This is enabled through the BUNIT.BECREG message bus register (Port: 3h, Register: 27h) found in the SoC Transaction Router. BUNIT.BECREG allows remapping this 256 MiB region anywhere in physical memory space. Memory accesses within the programmed MMIO range result in configuration cycles to the appropriate PCI devices specified by the memory address as shown below.

Table 38. PCI Configuration Memory Bar Mapping

ECAM Memory Address Field	ECAM Memory Address Bits
Use from BAR: BUNIT.BECREG[31:28]	31:28
Bus Number	27:20
Device Number	19:15
Function Number	14:12
Register Number	11:02

Note: ECAM accesses are only possible when BUNIT.BECREG.ECENABLE (bit 0) is set.

Pseudo code for an enhanced PCI configuration register read is shown below:

- MyCfgAddr[27:20] = bus; MyCfgAddr[19:15] = device; MyCfgAddr[14:12] = funct;
- MyCfgAddr[11:2] = dw_offset; MyCfgAddr[31:28] = BECREG[31:28];
- Register_Snapshot = MEMREAD(MyCfgAddr)

3.6 Message Bus Register Access

Accesses to the message bus space is through the SoC Transaction Router's PCI configuration registers. This unit relies on three 32-bit PCI configuration registers to generate messages:

- Message Bus Control Register (MCR) - PCI[B:0,D:0,F:0] + D0h
- Message Data Register (MDR) - PCI[B:0,D:0,F:0] + D4h
- Message Control Register eXtension (MCRX) - PCI[B:0,D:0,F:0] + D8h

This indirect access mode is similar to PCI CAM. Software uses the MCR/MCRX as an index register, indicating which message bus space register to access (MCRX only when required), and MDR as the data register. Writes to the MCR trigger message bus transactions.

Writes to MCRX and MDR will be captured. Writes to MCR will generate an internal 'message bus' transaction with the opcode and target (port, offset, bytes) specified in the MCR and the captured MCRX. When a write opcode is specified in MCR, the data that was captured by MDR is used for the write. When a data read opcode is specified in MCR, the data will be available in the MDR register after the MCR write completes (non-posted). The format of MCR and MCRX are shown below.

Table 39. MCR Description (Sheet 1 of 2)

Field	MBPR Bits
OpCode (typically 10h for read, 11h for write)	31:24




Table 39. MCR Description (Sheet 2 of 2)

Field	MBPR Bits
Port	23:16
Offset/Register	15:08
Byte Enable	07:04

Table 40. MCRX Description

Field	MBPR Bits
Offset/Register Extension. This is used for messages sent to end points that require more than 8 bits for the offset/register. These bits are a direct extension of MCR[15:8].	31:08

Most message bus registers are located in the SoC Transaction Router. The default opcode messages for those registers are as follows:

- Message 'Read Register' Opcode: 06h
- Message 'Write Register' Opcode: 07h

Registers with different opcodes will be specified as applicable. Pseudo code of a message bus register read is shown below (where ReadOp==0x06):

- MyMCR[31:24] = ReadOp; MyMCR[23:16] = port; MyMCR[15:8] = offset;
- MyMCR[7:4] = 0xf
- PCIWRITE(0, 0, 0, 0xD0, MyMCR)
- Register_Snapshot = PCIREAD(0, 0, 0, 0xD4)

3.7 Register Field Access Types


Table 41. Register Access Types and Definitions (Sheet 1 of 2)

Access Type	Meaning	Description
RO	Read Only	In some cases, if a register is read only, writes to this register location have no effect. However, in other cases, two separate registers are located at the same location where a read accesses one of the registers and a write accesses the other register. See the I/O and memory map tables for details.
WO	Write Only	In some cases, if a register is write only, reads to this register location have no effect. However, in other cases, two separate registers are located at the same location where a read accesses one of the registers and a write accesses the other register. See the I/O and memory map tables for details.
R/W	Read/Write	A register with this attribute can be read and written.

**Table 41. Register Access Types and Definitions (Sheet 2 of 2)**

Access Type	Meaning	Description
R/WC	Read/Write Clear	A register bit with this attribute can be read and written. However, a write of 1 clears (sets to 0) the corresponding bit and a write of 0 has no effect.
R/WO	Read/Write-Once	A register bit with this attribute can be written only once after power up. After the first write, the bit becomes read only.
R/WLO	Read/Write, Lock-Once	A register bit with this attribute can be written to the non-locked value multiple times, but to the locked value only once. After the locked value has been written, the bit becomes read only.
Default	Default	When the processor is reset, it sets its registers to predetermined default states. The default state represents the minimum functionality feature set required to successfully bring up the system. Hence, it does not represent the optimal system configuration. It is the responsibility of the system initialization software to determine configuration, operating parameters, and optional system features that are applicable, and to program the processor registers accordingly.

§



4 Mapping Address Spaces

The SoC supports four different address spaces:

- [Physical Address Space Mappings](#)
- [IO Address Space](#)
- [PCI Configuration Space](#)
- [Message Bus Space](#)

The CPU core can only directly access *memory space* through memory reads and writes and *IO space* through the IN and OUT IO port instructions. *PCI configuration space* is indirectly accessed through IO or memory space, and the *Message Bus space* is accessed through PCI configuration space. See [Chapter 3, "Register Access Methods"](#) for details.

This chapter describes how the memory, IO, PCI and Message Bus spaces are mapped to interfaces in the SoC.

Note: See [Chapter 13, "SoC Transaction Router"](#) for registers specified in the chapter.

4.1 Physical Address Space Mappings

There are 64 GB (36-bits) of physical address space that can be used as:

- Memory Mapped IO (MMIO - IO fabric)
- Physical Memory (DRAM)

The CPU core can access the full physical address space, while downstream devices can only access SoC DRAM, and each CPU core's local APIC. Peer to peer transactions are not supported.

Most devices map their registers and memory to the physical address space. This chapter summarizes the possible mappings.

4.1.1 SoC Transaction Router Memory Map

The SoC Transaction Router maps the physical address space as follows:


- CPU core to DRAM
- CPU core to IO fabric (MMIO)
- CPU core to extended PCI registers (ECAM accesses)
- IO fabric to CPU cores (local APIC interrupts)

Although 64 GB (36-bits) of physical address space is accessible, some MMIO must exist for devices and software with 32-bit limits. Further, all DRAM should remain accessible for devices and software with access to memory above 4 GB. These goals are accomplished by moving a section DRAM to start at the fixed 4 GB boundary, leaving a hole below 4 GB for MMIO. This creates the following distinct memory regions:

- DOS DRAM + Low DRAM
- Low MMIO
- High DRAM
- High MMIO

There are two registers used to create these regions, BMBOUND and BMBOUND_HI. Their use is shown in [Figure 4](#).


Figure 4. Physical Address Space - DRAM & MMIO



4.1.1.1 Low MMIO

The low MMIO mappings are shown in Figure 5.

Figure 5. Physical Address Space - Low MMIO



By default, CPU core reads targeting the **Boot Vector** range (FFFFFFFFh-FFFF0000h) are sent to the boot Flash connected to the Platform Controller Unit, and write accesses target DRAM. This allows the boot strap CPU core to fetch boot code from the boot Flash, and then shadow that code to DRAM.

Upstream writes from the IO fabric to the **Local APIC** range (FEE00000h-FEF00000h) are sent to the appropriate CPU core's APIC.

Write accesses from a CPU core to the **Abort Page** range (FEB00000h-FEBFFFFFFh) will be dropped, and reads will always return all 1's in binary.


Accesses in the 256 MB **PCI ECAM** range starting at BECREG generate enhanced PCI configuration register accesses when enabled (BECREG.ECENABLE). Unlike traditional memory writes, writes to this range are non-posted when enabled. See [Chapter 3, "Register Access Methods"](#) for more details.

All other downstream accesses in the Low MMIO range are sent to the IO Fabric for further decode based on PCI resource allocations. The IO Fabric's subtractive agent (for unclaimed accesses) is the Platform Controller Hub.

4.1.1.2 DOS DRAM

The DOS DRAM is the memory space below 1 MB. In general, accesses from a processor targeting DOS DRAM target system DRAM. Exceptions are shown in the below figure.

Figure 6. Physical Address Space - DOS DRAM



Processor writes to the 64 KB (each) **PROM 'E'** and **'F'** segments (E0000h-EFFFFh and F0000h-FFFFFh) always target DRAM. The BMISC register is used to direct CPU core reads in these two segments to DRAM or the IO fabric (MMIO).

CPU core accesses to the 128 KB **VGA/CSEG** range (A0000h-BFFFFh) can target DRAM or the IO fabric (MMIO). The target is selected with the BMISC.ABSEGINDRAM register.


4.1.1.3 Additional Mappings

There are two additional mappings available in the SoC Transaction Router:

- SMM range
- Non-snoop range

Figure 7 shows these mappings.

Figure 7. Physical Address Space - SMM and Non-Snoop Mappings



SMI handlers running on a CPU core execute out of SMM memory. To protect this memory from non-CPU core access, the **SMM Range** (BSMMRRL-BSMMRRH) may be programmed anywhere in low or high DRAM space (1 MB aligned). This range will only allow accesses from the CPU cores.

To prevent snoops of the CPU cores when DMA devices access a specific memory region, the **Non-Snoopable Memory range** (BNOCACHE.Lower-BNOCACHE.Upper) can be programmed anywhere in physical address space. This range is enabled via the BNOCACHECTL register's enable bit (BNOCACHECTL.Enable).



4.1.2 IO Fabric (MMIO) Map

Memory accesses targeting MMIO are routed by the IO fabric to programmed PCI ranges, or routed to the PCU by default (subtractive agent). Programmed PCI ranges can be moved within low or high MMIO, and most can be disabled.

Note: Not all devices can be mapped to high MMIO.

Fixed MMIO is claimed by the Platform Controller Unit (PCU). The default regions are listed below. Movable ranges are not shown. See the register maps of all PCU devices for details.

Table 42. Fixed Memory Ranges in the Platform Controller Unit (PCU)


Device	Start Address	End Address	Comments
Low BIOS (Flash Boot)	000E0000h	000FFFFFFh	Starts 128 KB below 1 MB; Firmware/BIOS
IO APIC	FEC00000h	FEC00040h	Starts 20 MB below 4 GB
HPET	FED40000h	FED003FFh	Starts 19 MB below 4 GB
TPM (LPC)	FED40000h	FED40FFFh	Starts 16 KB above HPET range
High BIOS/Boot Vector	FFFF0000h	FFFFFFFFh	Starts 64 KB below 4 GB; Firmware/BIOS

The following PCI devices may claim memory resources in MMIO space:

- Graphics/Display (High MMIO capable)
- PCI Express* (High MMIO capable)
- SATA
- SD/MMC/SDIO
- SIO
- HD Audio
- Platform Controller Unit (PCU) (Multiple BARs)
- xHCI USB
- EHCI USB
- USB Device
- LPE/I²S
- ISP/MIPI-CSI

See each device's interface chapter for details.

Warning: Variable memory ranges should not be set to conflict with other memory ranges. There will be unpredictable results if the configuration software allows conflicts to occur. Hardware does not check for conflicts.



4.2 IO Address Space

There are 64 KB + 3 bytes of IO space (0h-10002h) for accessing IO registers. Most IO registers exist for legacy functions in the PCU or for PCI devices, while some are claimed by the SoC Transaction Router for graphics and for the PCI configuration space access registers.

4.2.1 SoC Transaction Router IO Map

The SoC claims IO transactions for VGA/Extended VGA found in the display/graphics interface. It also claims the two 32-bit registers at port CF8h and CFCh used to access PCI configuration space.

4.2.2 IO Fabric IO Map

4.2.2.1 PCU Fixed IO Address Ranges

Below table shows the fixed IO space ranges seen by a processor.

Table 43. Fixed IO Ranges in the Platform Controller Unit (PCU)

Device	IO Address	Comments
8259 Master	20h-21h, 24h-25h, 28h-29h, 2Ch-2Dh, 30h-31h, 34h-35h, 38h-39h, 3Ch-3Dh	
8254s	40h-43h, 50h-53h	
PS2 Control	60h, 64h	
NMI Controller	61h, 63h, 65h, 67h	
RTC	70h-77h	
Port 80h	80h-83h	
Init Register	92h	
8259 Slave	A0h-A1h, A4h-A5h, A8h-A9h, ACh-ADh, B0h-B1h, B4h-B5h, B8h-B9h, BCh-BDh, 4D0h-4D1h	
PCU UART	3F8h-3FFh	
Reset Control	CF9h	Overlaps PCI IO registers
Active Power Management	B2h-B3h	

Table 44. Fixed IO Ranges in the SoC Transaction Router, Serial ATA and PCIe* Blocks

Device	IO Address	Comments
SATA Legacy IDE Mode - Secondary Channel Legacy Taskfile Command Block	170h - 177h	
SATA Legacy IDE Mode - Primary Channel Legacy Taskfile Command Block	1F0h - 1F7h	
SATA Legacy IDE Mode - Secondary Channel Legacy Taskfile Control Block	374h - 377h	
SATA Legacy IDE Mode - Primary Channel Legacy Taskfile Control Block	3F4h - 3F7h	
PCI Express*: VGA Legacy Control & Status	3B0h - 3BBh, 3C0h - 3DFh	Only active if INTR_BCTRL.VE=1b
PCI Configuration Access Address	CF8h	
PCI Configuration Access Data	CFCh	


4.2.2.2 Variable IO Address Ranges

Table 45 shows the variable IO decode ranges. They are set using base address registers (BARs) or other similar means. Plug-and-play (PnP) software (PCI/ACPI) can use their configuration mechanisms to set and adjust these values.

Warning: The variable IO ranges should not be set to conflict with other IO ranges. There will be unpredictable results if the configuration software allows conflicts to occur. Hardware does not check for conflicts.

Table 45. Movable IO Ranges Decoded by PCI Devices on the IO Fabric (Sheet 1 of 2)

Device	Size (bytes)	Target
ACPI Power Management (PCU)	128	ACPI_BASE_ADDR (PM1BLK): PCI[B:0,D:31,F:0] + 40h
SMBus (PCU)	32	SMBA: PCI[B:0,D:31,F:3] + 20h
GPIO (PCU)	256	GBA: PCI[B:0,D:31,F:0] + 48h
RCBA (PCU)	1024	RCRB_BA: PCI[B:0,D:31,F:0] + F0h
Display Controller	8	IOBAR (PCI[B:0,D2,F:0] + 20h)
PCI Express: ISA Legacy	Variable ¹	IOBL_SSTS.IOBA (PCI[B:0,D28,F:0] + 1Ch)
SATA Native & AHCI Mode - Legacy IDE / AHCI Index Data Pair	32	LBAR (PCI[B:0,D19,F:0] + 20h)
SATA Native Mode - Serial ATA Index Data Pair	16	SIDPBA (PCI[B:0,D19,F:0] + 24h)
SATA Native Mode - Primary Command Block	8	PCMDBA (PCI[B:0,D19,F:0] + 10h)

**Table 45. Movable IO Ranges Decoded by PCI Devices on the IO Fabric (Sheet 2 of 2)**

Device	Size (bytes)	Target
SATA Native Mode - Secondary Command Block	8	SCMDBA (PCI[B:0,D19,F:0] + 18h)
SATA Native Mode - Primary Control Block	4	PCTLBA (PCI[B:0,D19,F:0] + 14h)
SATA Native Mode - Secondary Control Block	4	SCTLBA (PCI[B:0,D19,F:0] + 1Ch)

NOTES 1: Size is defined by the configuration of IOBL_SSTS.IOLA

4.3 PCI Configuration Space

All PCI devices/functions are shown below. Table below will always take priority.

Table 46. PCI Devices and Functions (Sheet 1 of 2)


Bus	Device	Function	Device ID	Device Description	Function Description
0	0	0	0F00h	SoC Transaction Router	
0	2	0	0F31h	Graphics & Display	
0	3	0	0F38h	Camera Image Signal Processor	
0	16	0	0F14h	Storage Control Cluster (SCC)	eMMC Port (de-featured - use Device 23 instead)
0	17	0	0F15h		SDIO Port
0	18	0	0F16h		SD Port
0	19	0	0F20h (IDE) 0F21h (IDE) 0F22h (AHCI) 0F23h (AHCI)	SATA	
0	20	0	0F35h	xHCI USB	
0	21	0	0F28h	Low Power Engine Audio	Host Bridge + three I ² S Ports (0-2)
0	22	0	0F37h	USB Device	
0	23	0	0F50h	Storage Control Cluster (SCC)	eMMC 4.5 Port
0	24	0	0F40h	Serial IO (SIO)	DMA
		1	0F41h		I ² C Port 1
		2	0F42h		I ² C Port 2
		3	0F43h		I ² C Port 3
		4	0F44h		I ² C Port 4
		5	0F45h		I ² C Port 5
		6	0F46h		I ² C Port 6
		7	0F47h		I ² C Port 7
0	26	0	0F18h	Trusted Execution Engine	



Table 46. PCI Devices and Functions (Sheet 2 of 2)

Bus	Device	Function	Device ID	Device Description	Function Description
0	27	0	0F04h	HD Audio	
0	28	0	0F48h	PCI Express*	Root Port 1
		1	0F4Ah		Root Port 2
		2	0F4Ch		Root Port 3
		3	0F4Eh		Root Port 4
0	29	0	0F34h	EHCI USB	
0	30	0	0F06h	Serial IO (SIO)	DMA
		1	0F08h		PWM Port 1
		2	0F09h		PWM Port 2
		3	0F0Ah		HSUART Port 1
		4	0F0Ch		HSUART Port 2
		5	0F0Eh		SPI Port
0	31	0	0F1Ch	Platform Controller Unit	LPC: Bridge to Intel Legacy Block
0	31	3	0F12h	Platform Controller Unit	SMBus Port

Figure 8. Bus 0 PCI Devices and Functions



§

5 **Integrated Clock**

Clocks are integrated, consisting of multiple variable frequency clock domains, across different voltage domains. This architecture achieves a low power clocking solution that supports the various clocking requirements of the SoC's many interfaces.





Figure 9. Clocking Example

5.1 Features

Platform clocking is provided internally by the Integrated Clock logic. No external clock chips are required for the SoC to function. All the required platform clocks are provided by two crystal inputs: a 25 MHz primary reference for the integrated clock block and a 32.768 kHz reference for the Real Time Clock (RTC) block.


The different inputs and outputs are listed below.

**Table 47. SoC Clock Inputs**

Clock Domain	Signal Name	Frequency	Usage/Description
Main	ICLK_OSCIN ICLK_OSCOUT	25 MHz	Reference crystal for the iCLK PLL
RTC	ILB_RTC_X1 ILB_RTC_X2	32.768 kHz	RTC crystal I/O for RTC block
MIPI CSI	MCSI1_CLKP/N MCSI2_CLKP/N MCSI3_CLKP/N	80-500 MHz	Clocks for cameras
LPC	ILB_LPC_CLK[1]	33 MHz	Can be configured as an input to compensate for board routing delays through Soft Strap.
USB PHY	USB_ULPI_CLK	60 MHz	Interface clock from ULPI PHY.

Table 48. SoC Clock Outputs (Sheet 1 of 2)

Clock Domain	Signal Name	Frequency	Usage/Description
Memory	DRAM0_CKP/N[2,0] DRAM1_CKP/N[2,0]	533/667 MHz	Drives the Memory ranks 0-1. Data rate (MT/s) is 2x the clock rate. Note: The frequency is fused in each SoC. It is not possible to support both frequencies on one SoC.
eMMC	MMC1_CLK MMC1_45_CLK	25-50 MHz 25-200 MHz	Clock for eMMC 4.41 devices Clock for eMMC 4.51 devices Actual clock can run as low as 400 kHz during initialization.
SDIO	SD2_CLK	25-50 MHz	Clock for SDIO devices
SD Card	SD3_CLK	25-50 MHz	Clock for SD card devices
SPI	PCU_SPI_CLK	20 MHz, 33 MHz, 50 MHz	Clock for SPI flash
PMIC/COMMS	PMC_SUSCLK[3:0]	32.768 kHz	Pass through clock from RTC oscillator
LPC	ILB_LPC_CLK[0:1]	33 MHz	Provided to devices requiring LPC clock
HDA	HDA_CLK	24 MHz	Serial clock for external HDA codec device
PCI Express	PCIE_CLKN[3:0] PCIE_CLKP[3:0]	100 MHz	Differential Clocks supplied to external PCI express devices based on assertion of PCIE_CLKREQ[3:0]# inputs
USB PHY	USB_ULPI_REFCLK	19.2 MHz	Clock for USB devices
HDMI	DDI[1:0]_TXP/N[3]	25-148.5 MHz	Differential clock for HDMI devices
HDMI DDC	DDI[1:0]_DDCCLK	100 kHz	Clock for HDMI DDC devices

**Table 48. SoC Clock Outputs (Sheet 2 of 2)**

Clock Domain	Signal Name	Frequency	Usage/Description
VGA DDC	VGA_DDCCLK	100 kHz	Clock for VGA DDC devices
SVID	SVID_CLK	25 MHz	Clock used by voltage regulator
I ² S	LPE_I2S[2:0]_CLK	12.5 MHz	Continuous serial clock for I ² S interfaces
Platform Clocks	PMC_PLT_CLK [5:0]	25 MHz	Platform clocks. For example: PLT_CLK [2:0] - Camera PLT_CLK [3] - Audio Codec PLT_CLK [4] - PLT_CLK [5] - COMMs
SIO SPI	SIO_SPI_CLK	15 MHz	SPI clock output
I ² C	SIO_I2C[6:0]_CLK	100 kHz, 400 kHz, 1 MHz, 3.4 MHz	I ² C clocks Note: In I2C Controller the parameter called IC_CAP_LOADING can be set to 400pf/100pf. As per specification 3.4MHz is supported in 100pf loading while 1.7MHz is the max frequency at 400pf load.
SMBus	PCU_SMB_CLK	10 kHz - 100 kHz	Drives SMBus device

§

6 Power Management

This chapter provides information on the following power management topics:

- ACPI States
- Processor Core
- PCI Express
- Integrated Graphics Controller

6.1 Power Management Features

- ACPI System States support (S0, S3, S4, S5)
- Processor Core/ States support (C0 – C6)
- Processor Package States Support (C0-C7)
- SoC Graphics Adapter States support D0 – D3.
- Support Link Power Management (LPM)
- Thermal throttling
- Dynamic I/O power reductions (disabling sense amps on input buffers, tri-stating output buffers)
- Active power down of Display links

6.2 Power Management States Supported

The Power Management states supported by the processor are described in this section.

6.2.1 S-State Definition


6.2.1.1 S0 - Full On

This is the normal operating state of the processor. In S0, the core processor will transition in and out of the various processor C-States and P-States.

6.2.1.2 S3 - Suspend to RAM (Standby)

S3 is a suspend state in which the core power planes of the processor are turned off and the suspend wells remain powered.

- All power wells are disabled, except for the suspend and RTC wells.
- The core processor's macro-state is saved in memory.



- Memory is held in self-refresh and the memory interface is disabled, except the CKE pin as it is powered from the memory voltage rail. CKE is driven low.

6.2.1.3 S4 - Suspend to Disk (Hibernate)

S4 is a suspend state in which most power planes of the processor are turned off, except for the suspend and RTC well. In this ACPI state, system context is saved to the hard disk.

Key features:

- No activity is allowed.
- All power wells are disabled, except for the suspend and RTC well.

6.2.1.4 S5 - Soft Off

From a hardware perspective the S5 state is identical to the S4 state. The difference is purely software; software does not write system context to hard disk when entering S5.

The following table shows the differences in the sleeping states with regards to the processor's output signals.

Table 49. SoC Sx-States to SLP_S*#

State	S0	S3	S4	S5	Reset w/o Power Cycle	Reset w/ Power Cycle
CPU Executing	In C0	OFF	OFF	OFF	No	OFF
PMC_SLP_S3#	HIGH	LOW	LOW	LOW	HIGH	LOW
PMC_SLP_S4#	HIGH	HIGH	LOW	LOW	HIGH	LOW
S0 Power Rails	ON	OFF	OFF	OFF	ON	OFF
PMC_PLTRST#	HIGH	LOW	LOW	LOW	LOW	LOW
PMC_SUS_STAT#	HIGH	LOW	LOW	LOW	HIGH	LOW
PCIe Links	L0, L1	L3	L3	L3	L3 Ready	L3

NOTES: The processor treats S4 and S5 requests the same. The processor does not have PMC_SLP_S5#. PMC_SUS_STAT# is required to drive low (asserted) even if core well is left on because PMC_SUS_STAT# also warns of upcoming reset.

6.2.2 System States


Table 50. General Power States for System

States/Sub-states	Legacy Name / Description
G0/S0/C0	FULL ON: CPU operating. Individual devices may be shut down to save power. The different CPU operating levels are defined by Cx states.
G0/S0/Cx	Cx State: CPU manages C-state itself.
G1/S3	Suspend-To-RAM(STR): The system context is maintained in system DRAM, but power is shut to non-critical circuits. Memory is retained, and refreshes continue. All external clocks are shut off; RTC clock and internal ring oscillator clocks are still toggling.
G1/S4	Suspend-To-Disk (STD): The context of the system is maintained on the disk. All of the power is shut down except power for the logic to resume. The S4 and S5 states are treated the same.
G2/S5	Soft-Off: System context is not maintained. All of the power is shut down except power for the logic to restart. A full boot is required to restart. A full boot is required when waking. The S4 and S5 states are treated the same.
SoC G3	SoC Mechanical OFF. System context is not maintained. All power to the SoC is shutdown except for the RTC. All of the power to the rest of the system is shut down except power for the logic to restart. No SoC "Wake" events are possible, because the SoC does not have any power. when SoC power returns, transition will depend on the state just prior to the entry to SoC G3.
G3	Mechanical OFF. System is not maintained. All power shutdown except for the RTC. No "Wake" events are possible, because the system does not have any power. This state occurs if the user removes the batteries, turns off a mechanical switch, or if the system power supply is at a level that is insufficient to power the "waking" logic. When system power returns, transition will depend on the state just prior to the entry to G3.

Table 51 shows the transitions rules among the various states. Note that transitions among the various states may appear to temporarily transition through intermediate states. These intermediate transitions and states are not listed in the table.

Table 51. ACPI PM State Transition Rules (Sheet 1 of 2)

Present State	Transition Trigger	Next State
G0/S0/C0	IA Code MWAIT or LVL Rd	C0/S0/Cx
	PM1_CNT.SLP_EN bit set	G1/Sx or G2/S5 state (specified by PM1_CNT.SLP_TYP)
	Power Button Override	G2/S5
	Mechanical Off/Power Failure	G3

**Table 51. ACPI PM State Transition Rules (Sheet 2 of 2)**

Present State	Transition Trigger	Next State
G0/S0/Cx	Cx break events which include: CPU snoop, MSI, Legacy Interrupt, AONT timer	G0/S0/C0
	Power Button Override	G2/S5
	System Power Failure	G3
G1/S3,G1/S4	Any Enabled Wake Event	G0/S0/C0
	Power button Override	G2/S5
	Resume Well Power Failure	G3
G2/S5	Any Enabled Wake Event	G0/S0/C0
	Resume Well Power Failure	G3
G3	Power Returns	Option to go to S0/C0 (reboot) or G2/S5 (stay off until power button pressed or other enabled wake event) or G1/S4 (if system state was S4 prior to the power failure). Some wake events are preserved through a power failure.

6.2.3 Processor States

Table 52. Processor Core/ States Support

State	Description
C0	Active mode, processor executing code
C1	AutoHALT state
C6	Deep Power Down. Prior to entering the Deep Power Down Technology (code named C6) State, The core process will flush its cache and save its core context to a special on die SRAM on a different power plane. Once Deep Power Down Technology (code named C6) sequence has completed. The core processor's voltage is completely shut off.

6.2.4 Integrated Graphics Display States

Table 53. SoC Graphics Adapter State Control

State	Description
D0	Full on, Display active
D3	Power off display



6.2.5 Integrated Memory Controller States

Table 54. Main Memory States

States	Description
Powerup	CKE asserted. Active mode.
Precharge Powerdown	CKE de-asserted (not self-refresh) with all banks closed.
Active Powerdown	CKE de-asserted (not self-refresh) with at least one bank active.
Self-Refresh	CKE de-asserted using device self-refresh

6.2.6 PCI Express* (PCIe*) States


Table 55. PCI Express* States

States	Description
L0	Full on – Active transfer state
L0s	First Active Power Management low power state – Low exit latency
L1	Lowest Active Power Management - Longer exit latency
L3	Lowest power state (power-off) – Longest exit latency

6.2.7 Interface State Combinations

Table 56. G, S and C State Combinations

Global (G) State	Sleep (S) State	Processor Core (C) State	Processor State	System Clocks	Description
G0	S0	C0	Full On	On	Full On
G0	S0	C1	Auto-Halt	On	Auto-Halt
G0	S0	C6	Deep Power Down	On	Deep Power Down
G1	S3	Power off		Off except RTC & internal ring OSC	Suspend to RAM
G1	S4	Power off		Off except RTC & internal ring OSC	Suspend to Disk
G2	S5	Power off		Off except RTC & internal ring OSC	Soft Off
G3	NA	Power Off		Power off	Hard Off

**Table 57. D, S and C State Combinations**

Graphics Adapter (D) State	Sleep (S) State	(C) State	Description
D0	S0	C0	Full On, Displaying
D0	S0	C1	Auto-Halt, Displaying
D0	S0	C6	Deep Sleep, Display Off
D3	S0	Any	Not Displaying
D3	S3		Not Displaying Graphics Core power off.
D3	S4		Not Displaying Suspend to disk Core power off

NOTE:S0ix is not supported for Bay Trail-M/D and Bay Trail-I.

6.3 Processor Core Power Management

While executing code, Enhanced Intel SpeedStep® Technology optimizes the processor's frequency and core voltage based on workload. Each frequency and voltage operating point is defined by ACPI as a P-state. When the processor is not executing code, it is idle. A low-power idle state is defined by ACPI as a C-state. In general, lower power C-states have longer entry and exit latencies.

6.3.1 Enhanced Intel SpeedStep® Technology

The following are the key features of Enhanced Intel SpeedStep® Technology:

- Applicable to Processor Core Voltage and Graphic Core Voltage
- Multiple frequency and voltage points for optimal performance and power efficiency. These operating points are known as P-states.
- Frequency selection is software controlled by writing to processor MSRs. The voltage is optimized based on the selected frequency:
 - If the target frequency is higher than the current frequency, Core_VCC_S3 is ramped up slowly to an optimized voltage. This voltage is signaled by the SVID signals to the voltage regulator. Once the voltage is established, the PLL locks on to the target frequency.
 - If the target frequency is lower than the current frequency, the PLL locks to the target frequency, then transitions to a lower voltage by signaling the target voltage on the SVID signals.
- The processor controls voltage ramp rates by requesting appropriate ramp rates from an external SVID controller.
- Because there is low transition latency between P-states, a significant number of transitions per second are possible.

- Thermal Monitor mode.
 - Refer to [Chapter 8, “Thermal Management”](#)

6.3.2 Dynamic Cache Sizing

Dynamic Cache Sizing allows the processor to flush and disable a programmable number of L2 cache ways upon each Deeper Sleep entry under the following condition:

- The C0 timer that tracks continuous residency in the Normal state, has not expired. This timer is cleared during the first entry into Deeper Sleep to allow consecutive Deeper Sleep entries to shrink the L2 cache as needed.
- The predefined L2 shrink threshold is triggered.

The number of L2 cache ways disabled upon each Deeper Sleep entry is configured in the BBL_CR_CTL3 MSR. The C0 timer is referenced through the CLOCK_CORE_CST_CONTROL_STT MSR. The shrink threshold under which the L2 cache size is reduced is configured in the PMG_CST_CONFIG_CONTROL MSR. If the ratio is zero, then the ratio will not be taken into account for Dynamic Cache Sizing decisions. Refer to the BIOS Writer’s Guide for more details.

6.3.3 Low-Power Idle States

When the processor core is idle, low-power idle states (C-states) are used to save power. More power savings actions are taken for numerically higher C-state. However, higher C-states have longer exit and entry latencies. Resolution of C-state occur at the thread, processor core, and processor core level.

6.3.3.1 Clock Control and Low-Power States

The processor core supports low power states at core level. The central power management logic ensures the entire processor core enters the new common processor core power state. For processor core power states higher than C1, this would be done by initiating a P_LVLx (P_LVL6) I/O read to all of the cores. States that require external intervention and typically map back to processor core power states. States for processor core include Normal (C0, C1).


The processor core implements two software interfaces for requesting low power states: MWAIT instruction extensions with sub-state specifies and P_LVLx reads to the ACPI P_BLK register block mapped in the processor core’s I/O address space. The P_LVLx I/O reads are converted to equivalent MWAIT C-state requests inside the processor core and do not directly result in I/O reads on the processor core bus. The monitor address does not need to be setup before using the P_LVLx I/O read interface. The sub-state specifications used for each P_LVLx read can be configured in a software programmable MSR by BIOS.

The Cx state ends due to a break event. Based on the break event, the processor returns the system to C0. The following are examples of such break events:

- Any unmasked interrupt goes active

- Any internal event that will cause an NMI or SMI_B
- CPU Pending Break Event (PBE_B)
- MSI

Figure 10. Idle Power Management Breakdown of the Processor Cores



6.3.4 Processor Core C-States Description

The following state descriptions assume that both threads are in common low power state.

6.3.4.1 Core C0 State

The normal operating state of a core where code is being executed.

6.3.4.2 Core C1 State

C1 is a low power state entered when a core execute a HLT or MWAIT(C1) instruction.

A System Management Interrupt (SMI) handler returns execution to either Normal state or the C1 state. See the *Intel® 64 and IA-32 Architecture Software Developer's Manual, Volume 3A/3B: System Programmer's Guide* for more information.

While a core is in C1 state, it processes bus snoops and snoops from other threads.

6.3.4.3 Core C6 State

Individual core can enter the C6 state by initiating a P_LVL3 I/O read or an MWAIT(C6) instruction. Before entering core C6, the core will save its architectural state to a dedicated SRAM. Once complete, a core will have its voltage reduced to zero volts. During exit, the core is powered on and its architectural state is restored.

There are various types of C-state:

- C6NS implies only the core should be powergated, but the L2 cache contents should be retained.
- C6FS implies the core should be powergates, and the L2 cache can be fully flushed to get even more power savings.


6.3.5 Package C-States

The processor supports package C0, C6 and C7 power states. The following is a summary of the general rules for package C-state entry. These apply to all package Cstates unless specified otherwise:

- Package C-state request is determined by the lowest numerical core C-state amongst all cores.
- A package C-state is automatically resolved by the processor depending on the core idle power states and the status of the platform components.
- Each core can be at a lower idle power state than the package if the platform does not grant the processor permission to enter a requested package C-state.
- The platform may allow additional power savings to be realized in the processor.
- For package C-states, the processor is not required to enter C0 before entering any other C-state.
- Entry in to a package C-state may be subject to auto-demotion - that is the processor may keep the package in a shallower package C-state then requested by the OS if the processor determines via heuristics that the shallower C-state results in better power/performance.

The processor exits a package C-state when a break event is detected. Depending on the type of break event, the processor does the following:

- If a core break event is received, the target core is activated and the break event message is forwarded to the target core.
 - If the break event is not masked, the target core enters the core C0 state and the processor enters package C0.
 - If the break event is masked, the processor attempts to re-enter its previous package state.
- If the break event was due to a memory access or snoop request.
 - But the platform did not request to keep the processor in a higher package C-state, the package returns to its previous C-state.
 - And the platform requests a higher power C-state, the memory access or snoop request is serviced and the package remains in the higher power C-state.

**Table 58. Coordination of Module and Core Power States at the Package Level**

Module C-State		Core/Module 1			
		C0	C1	C6NS	C6FS
Core 0	C0	C0	C0	C0	C0
	C1	C0	C0	C0	C0
	C6NS	C0	C0	C0	C6c
	C6FS	C0	C0	C6C	C6

Package C-State		Core/Module 1		
		C0	C6C	C6
Module 0	C0	C0	C0	C0
	C6C	C0	C6C	C6C
	C6	C0	C6C	C7

NOTE:

1. 2 Cores of the SoC will make up one module.

6.3.5.1 Package C0

The normal operating state for the processor. The processor remains in the normal state when at least one of its cores is in the C0 state or when the platform has not granted permission to the processor to go into a low power state. Individual cores may be in lower power idle states while the package is in C0.

6.3.5.2 Package C1

No additional power reduction actions are taken in the package C1 state.

The package enters the C1 low power state when:

- At least one core is in the C1 state.
- The other cores are in a C1 or lower power state.

No notification to the system occurs upon entry to C1.

6.3.5.3 Package C6 State

A processor enters the package C6 low power state when:

- At least one core is in the C6 state.

- The other cores are in a C6 or lower power state, and the processor has been granted permission by the platform.
- The platform has allowed a package C6 state.

In package C6 state, all cores have saved their architectural state and have had their core voltages reduced to zero volts.

6.3.6 Graphics Power Management

6.3.6.1 Graphics and video decoder C-State

GFX C-State (GC6) and VED C-state (VC6) are designed to optimize the average power to the graphics and video decoder engines during times of idleness. GFX C-state is entered when the graphics engine, has no workload being currently worked on and no outstanding graphics memory transactions. VED S-state is entered when the video decoder engine has no workload being currently worked on and no outstanding video memory transactions. When the idleness condition is met, the processor will power gate the Graphics and video decoder engines.


6.3.6.2 Intel® Display Power Saving Technology (Intel® DPST)

The Intel DPST technique achieves backlight power savings while maintaining visual experience. This is accomplished by adaptively enhancing the displayed image while decreasing the backlight brightness simultaneously. The goal of this technique is to provide equivalent end-user image quality at a decreased backlight power level.

1. The original (input) image produced by the operating system or application is analyzed by the Intel DPST subsystem. An interrupt to Intel® DPST software is generated whenever a meaningful change in the image attributes is detected. (A meaningful change is when the Intel DPST software algorithm determines that enough brightness, contrast, or color change has occurred to the displaying images that the image enhancement and backlight control needs to be altered.)
2. Intel DPST subsystem applies an image-specific enhancement to increase image contrast, brightness, and other attributes.
3. A corresponding decrease to the backlight brightness is applied simultaneously to produce an image with similar user-perceived quality (such as brightness) as the original image. Intel DPST 5.0 has improved the software algorithms and has minor hardware changes to better handle backlight phase-in and ensures the documented and validated method to interrupt hardware phase-in.

6.3.6.3 Intel® Automatic Display Brightness

The Intel Automatic Display Brightness feature dynamically adjusts the backlight brightness based upon the current ambient light environment. This feature requires an additional sensor to be on the panel front. The sensor receives the changing ambient light conditions and sends the interrupts to the Intel Graphics driver. As per the change



in Lux, (current ambient light illuminance), the new backlight setting can be adjusted through BLC. The converse applies for a brightly lit environment. Intel Automatic Display Brightness increases the back light setting.

6.3.6.4 Intel® Seamless Display Refresh Rate Switching Technology (Intel® SDRRS Technology)

When a Local Flat Panel (LFP) supports multiple refresh rates, the Intel® Display Refresh Rate Switching power conservation feature can be enabled. The higher refresh rate will be used when on plugged in power or when the end user has not selected/enabled this feature. The graphics software will automatically switch to a lower refresh rate for maximum battery life when the design application is on battery power and when the user has selected/enabled this feature.

There are two distinct implementations of Intel SDRRS—static and seamless. The static Intel SDRRS method uses a mode change to assign the new refresh rate. The seamless Intel SDRRS method is able to accomplish the refresh rate assignment without a mode change and therefore does not experience some of the visual artifacts associated with the mode change (SetMode) method.

6.4 Memory Controller Power Management

The main memory is power managed during normal operation and in low-power ACPI Cx states.

6.4.1 Disabling Unused System Memory Outputs

Any system memory (SM) interface signal that goes to a memory module connector in which it is not connected to any actual memory devices (such as DIMM connector is unpopulated, or is single-sided) is tri-stated. The benefits of disabling unused SM signals are:

- Reduced power consumption.
- Reduced possible overshoot/undershoot signal quality issues seen by the processor I/O buffer receivers caused by reflections from potentially un-terminated transmission lines.

When a given rank is not populated, the corresponding chip select and CKE signals are not driven.

At reset, all rows must be assumed to be populated, until it can be proven that they are not populated. This is due to the fact that when CKE is tristated with an SO-DIMM present, the DIMM is not guaranteed to maintain data integrity.

SCKE tri-state should be enabled by BIOS where appropriate, since at reset all rows must be assumed to be populated.

6.4.2 DRAM Power Management and Initialization

The processor implements extensive support for power management on the SDRAM interface. There are four SDRAM operations associated with the Clock Enable (CKE) signals, which the SDRAM controller supports. The processor drives four CKE pins to perform these operations.

6.4.2.1 Initialization Role of CKE

During power-up, CKE is the only input to the SDRAM that is recognized (other than the DDR3 reset pin) once power is applied. It must be driven LOW by the DDR controller to make sure the SDRAM components float DQ and DQS during power-up.

CKE signals remain LOW (while any reset is active) until the BIOS writes to a configuration register. Using this method, CKE is guaranteed to remain inactive for much longer than the specified 200 micro-seconds after power and clocks to SDRAM devices are stable.

6.4.2.2 Conditional Self-Refresh

Intel Rapid Memory Power Management (Intel RMPM) conditionally places memory into self-refresh in the package C3 and C6 low-power states. RMPM functionality depends on graphics/display state (relevant only when internal graphics is being used), as well as memory traffic patterns generated by other connected I/O devices.


When entering the Suspend-to-RAM (STR) state, the processor core flushes pending cycles and then places all SDRAM ranks into self refresh. In STR, the CKE signals remain LOW so the SDRAM devices perform self-refresh.

The target behavior is to enter self-refresh for the package C3 and C6 states as long as there are no memory requests to service.

6.4.2.3 Dynamic Power Down Operation

Dynamic power-down of memory is employed during normal operation. Based on idle conditions, a given memory rank may be powered down. The IMC implements aggressive CKE control to dynamically put the DRAM devices in a power down state. The processor core controller can be configured to put the devices in active power down (CKE deassertion with open pages) or precharge power down (CKE deassertion with all pages closed). Precharge power down provides greater power savings but has a bigger performance impact, since all pages will first be closed before putting the devices in power down mode.

If dynamic power-down is enabled, all ranks are powered up before doing a refresh cycle and all ranks are powered down at the end of refresh.



6.4.2.4 DRAM I/O Power Management

Unused signals should be disabled to save power and reduce electromagnetic interference. This includes all signals associated with an unused memory channel. Clocks can be controlled on a per SO-DIMM basis. Exceptions are made for per SO-DIMM control signals such as CS#, CKE, and ODT for unpopulated SO-DIMM slots.

The I/O buffer for an unused signal should be tri-stated (output driver disabled), the input receiver (differential sense-amp) should be disabled, and any DLL circuitry related ONLY to unused signals should be disabled. The input path must be gated to prevent spurious results due to noise on the unused signals (typically handled automatically when input receiver is disabled).

6.5 PCI Express* (PCIe*) Power Management

- Active power management support using L0s, and L1 states.
- All inputs and outputs disabled in L3 Ready state.

§

7 Power Up and Reset Sequence

This chapter provides information on the following topics:

- “Power Up Sequences”
- “Power Down Sequences”
- “Reset Behavior”

7.1 SoC System States

7.1.1 System Sleeping States Control (S-states)

The SoC supports the S0, S3, S4, and S5 sleep states. S4 and S5 states are identical from a hardware and power perspective. The differentiation is software determined (S4 = Suspend to Disk).

The SoC platform architecture assumes the usage of an external power management controller e.g., CPLD or PMIC. Some flows in this section refer to the power management controller for support of the S-states transitions.


The SoC sleep states are described in [Chapter 6, “Power Management”](#).

7.2 Power Up Sequences

7.2.1 RTC Power Well Transition (G5 to G3 States Transition)

When RTC_VCC (Real Time Clock power) is applied via RTC battery, the following occurs (see [Figure 11](#) for timing):

1. RTC_VCC ramps. ILB_RTC_TEST# should be low.
2. The system starts the real time clock oscillator.
3. A minimum of t1 units after RTC_VCC ramps, the external RTC RC circuit de-asserts ILB_RTC_TEST# and ILB_RTC_RTC#. The system is now in the G3 state. RTC oscillator is unlikely to be stable at this point.

Figure 11. RTC Power Well Timing Diagrams**Table 60. RTC Power Well Timing Parameters**

Parameter	Description	Min	Max	Units
t1	RTC_VCC to ILB_RTC_TEST# and ILB_RTC_RTC# de-assertion	18	-	ms

NOTES:

1. This delay is typically created from an RC circuit.
2. The oscillator startup times are component and design specific. A crystal oscillator can take several second to reach a large enough voltage swing. A silicon oscillator can have startups times <10 ms.

7.2.2 G3 to S0

The timings shown in Figure 12 occur when a board event such as AC power is applied or power management controller (PMIC) power button is pressed. The following occurs:

1. Suspend (SUS/Always On) wells ramp in the order shown.
2. The external power management controller de-asserts PMC_RSMRST# after the suspend rails become stable.
3. PMC_SUSCLK will begin toggling after the de-assertion of PMC_RSMRST#.
4. The system is now in S4/S5 state. Depending on policy bits (GEN_PMC1.PWR_FLR & GEN_PMC1.AG3E), the SoC either waits for a wake event to transition to S0 or continues to S0 state automatically.
5. The transition from S4/S5 to S0 is initiated.
6. The SoC de-asserts PMC_SLP_S4#, and the DRAM (VDD/Un-switched) well ramps.
7. After the DRAM power rail ramp, the external power management controller drives DRAM_VDD_S4_PWROK high.
8. The SoC de-asserts PMC_SLP_S3#, and the Core (S0/Switched On) wells ramp in the order shown.
9. After all of Core power rails are stable, external power management controller drives PMC_CORE_PWROK and DRAM_CORE_PWROK to HIGH, the SoC will then



fetch the descriptor region and soft straps data from the PCU located SPI interface, followed by the SoC de-asserting PMC_SUS_STAT#.

10. The SoC de-asserts PMC_PLTRST# after PMC_SUS_STAT# is stable. The PMC_PLTRST# is the main platform reset to other components.
11. The SoC will begin fetching data from the PCU-located SPI interface and proceed to finish initialization and start code execution (BIOS).

Note: There is no hard time requirement for transitions for the Always on/SUS rails (V1.0A, V1.2A, V1.8A, V3.3A). A 10 μ s to 10 ms delay is required for two adjacent rails of them to avoid inrush current which may be caused by multiple loads turning on simultaneously or fast charging of VR output decoupling.

Figure 12. G3/S5 to S0 Cold Boot Sequence





Table 61. S4/S5 to S0 (Power Up) Sequence

Parameter		Min	Max	Unit
t1	RTC_VCC to ILB_RTC_TEST# and ILB_RTC_RTC# de-assertion RTC_VCC to PMC_RSMRST# de-assertion	18	-	ms
t2	V3P3A (SUS Rails) valid to PMC_RSMRST# de-assertion (t1 still applies in applications without RTC battery)	10	-	us
t3	PMC_RSMRST# to Internal RTC Clock assumed stable ²	95		ms
t4	Internal RTC Clock assumed stable to PMC_SUSCLK[0] toggling ²	5		ms
t5	PMC_SLP_S4# de-assertion to PMC_SLP_S3# de-assertion	30	-	us
t6a	Core well stable to DRAM_CORE_PWROK and PMC_CORE_PWROK assertion (No PCIe devices)	10	-	ms
t6b	Core well stable to DRAM_CORE_PWROK and PMC_CORE_PWROK assertion (for power rails needed by PCIe devices)	99	-	ms
t7	DRAM/PMC_CORE_PWROK to PMC_SUS_STAT#	1	-	ms
t8	PMS_SUS_STAT# de-assertion to PMC_PLTRST# de-assertion	60	-	us
tx	PMC_SLP_S4# de-assertion to VDDQ ramp start	0	-	ms

NOTES:

1. RTC and SUS power rails may come up at the same time if no RTC battery is used.
2. Must ensure RTC clock is oscillating before these counts. SoC counts this time assuming a RTC clock of 32.768 KHz. Depending on how stable the oscillations are, however, this time can vary (+/-). This is effectively the *typical* amount of time the SoC waits to help ensure the clock is stable enough to proceed with power sequencing. It's more likely a min since RTC clock will typically run slow until stable.
3. Wake events shown in figure depend on platform configuration.
4. In the SUS rail sequence, V3P3A can be first in sequence if required for designs, otherwise it can end the SUS sequence.
5. An alternate SUS rail sequence allows swapping V1P8A with V1P0A.
6. For power rail sequences, at least 10us delay is required between rails to avoid inrush current caused by multiple loads turning on simultaneously and fast charging of VR output decoupling. A maximum delay of 2 ms is allowed. Measurement of delay is at the 90% of full voltage mark of the prior rail to 10% later rail.
7. VCC can follow VNN in the CORE rail sequence or at the same time. Reference platform sequences both at the same time.
8. "Board Event" is platform specific. Most likely enabled by a platform power management controller or PMIC via a dedicated power button or when AC power is applied.
9. For exit from S4 and S3 Events, see "Cause of Wake Events" table in this chapter. S4 wake is required from PMC_PWRBTN# without prior configuration. S3 wake event is only used when the platform directly transitions to S3 (STR).
10. The V1P35S rail "VGA_V1P35_S3_F1" must be powered on as shown above. All other V1P35S/VSFR ([X]_V1P35_S3_F[x]) rails can either power on as shown, or power on after V3P3S.
11. PMC_SUSPWRDNACK is intended to be used at power-down and, since its state after a power-down is variable, it is recommended that a system treats PMC_SUSRWRDNACK as a Do Not Care during power-on. For systems that are unable to treat PMC_SUSPWRDNACK as a Do Not Care during power-on, the following power-on state is always valid: - 1) PMC_SUSPWRDNACK will always be low, until PMC_SLP_S3# de-asserts, if PMC_SUSPWRDNACK was low upon entry into S5. PMC_SUSPWRDNACK is always low when entering S5 from G3.
12. Where no maximum timing is specified, it is expected that the maximum timing should typically be within one unit of time of the minimum timing, under normal operating conditions. Due to potential variability in operating conditions, no maximum timing can be guaranteed however.
13. When HDA_LPE_V1P5V1P8_S3 is powered by a V1P5S rail, the V1P5S rail sequencing should meet the same sequencing requirements as the V1P8S rail.



7.3 Power Down Sequences

7.3.1 S0 to S3 and S4/S5/G3 Sequence

Entry to Sleep states (S3, S4, S5) is initiated by any of the following methods:

- Setting the desired sleep type in PM1_CNT.SLP_TYP and setting PM1_CNT.SLP_EN.
- Detection of an external catastrophic temperature event may cause a transition to S5, if the system is designed to do so.

The following sequence applies to S0-S3 and S0-S4/S5 transitions.


1. The Operating System Power Management (OSPM) will handle the enabling or disabling of interrupt generation after S3 resume. The Operating System Power Management (OSPM) will need to read and clear Wake status information and the processing of the clearing wake status which will include enabling interrupts (both at the core level and platform level).
2. All interrupts in the processor need to be disabled before the S3 sequence is started (and re-enabled on exit). The CPU APIC must be disabled.
3. When the desired sleep state is set in the PM1_CNT.TYP and PM1_CNT.SLP_EN registers, a sleep state request is sent to the PMC.
4. The PMC flushes all the internal buffers to main memory.
5. The PMC places the PCI Express* devices into the L2/L3 state. The PMC will wait until the PCI Express* devices are in the L2/L3 state before proceeding. A timeout will occur in 1 ms if there is a non-functional PCI Express* device.


The Power Down Sequence is shown in [Figure 13](#) below.

Additional assumptions:

- Entry to a Cx state is mutually exclusive with software-initiated entry to a Sleep state. This is because the processor(s) can only perform one register access at a time. This requirement is enforced by the CPU as well as the OS. The system may hang if it attempts to do a C-state and S-state at the same time.
- The G3 system state cannot be entered via any software mechanism. The G3 state indicates a complete loss of power. In this state, the RTC well may or may not be powered by an external coin cell battery.
- An external Power Management Controller (PMIC/EC) can be used to put the SoC in G3 when the S4/S5 state is requested by the SoC. This is done to save power in S4/S5 state. This G3 like state, known as SoC G3, is enabled by removing SUS rails via when the SUSPWRDNACK pin is asserted on power down. Doing so prevents the use of any of SUS wake events including USB, RTC, and GPIOs including the power button. The external Power Management Controller (or re-application of power) is required to return to S0.

Figure 13. S0 to S3 to S4/S5 (Power Down) Sequence without S0ix



**Table 62. S0 to G3 (Power Down) Sequence**

Parameter	Description	Min	Max	Unit
t1	Power rail slew rate: From 90% to 10% of voltage typical	0.1	10	ms
t2	Tail to rail kick off delay ¹	0	3	ms

NOTES:

1. The rail to rail kick off delay min is 0 ms and max 3 ms.
2. The Power Down Slew rate min is 0.1 ms and max is 10 ms.
3. Switched/CORE rails should be turned off at the same time. Alternately, it's ok to turn off all Switch/CORE rails in the reverse order of power up paying attention to t2 timing if so. Both sequences are shown.
4. An alternate SUS rail sequence allows swapping V1P8A with V1P0A.
5. SUS rails are turned off only if entering SoC G3 state (SoC lets the board/PMIC power management system know if this is ok - that there are no wake up events expected by the SoC). They can turn off at the same time, or in reverse power up order, just like the Switched/CORE rails.
6. VDD_VTT shows a range of times at which it can turn off. Any time within this range is fine.
7. SLP_S3# can be active before or after DRAM_CORE_PWROK and PMC_CORE_PWROK, but DRAM_CORE_PWROK should go low before memory power rails go low and PMC_CORE_PWROK should go low before Switched/CORE rails go low.
8. Measurement of delays is at the 10% voltage mark. Contact your Intel representative for additional details.
9. The V1P35S rail "VGA_V1P35_S3_F1" must be powered down as shown above. All other V1P35S/VSFR ([X]_V1P35_S3_F[x]) rails can either power down as shown, or power down before V3P3S.

7.3.2 S3/S4/S5 to S0 (Exit Sleep States)

Sleep states (S3-S5) are exited based on Wake events. The Wake events will force the system to a full on state (S0), although some non-critical subsystems might still be powered down and have to be brought back manually. For example, the hard disk may be powered down during a sleep state, and have to be enabled via an I/O pin before it can be used. Upon exit from software-entered Sleep states (i.e., those initiated via the PM1_CNT.SLP_EN bit), the PM1_STS.EN.WAK_STS bit will be set.

To enable Wake Events, the possible causes of wake events (and their restrictions) are shown in [Table 63](#).

Table 63. S3/S4/S5 to S0 Cause of Wake Events (Sheet 1 of 2)

Cause	Type	How Enabled
RTC Alarm ¹	Internal	Set PM1_STS.EN.RTC_EN register bit
PMC_PWRBTN# (Power Button)	External	Default enabled as Wake event
GPIO_S5[7:0] ¹	External	GPE0a_EN register (after having gone to S5 via PM1_CNT.SLP_EN, but not after a power failure.) Note: GPIOs that are in the core well are not capable of waking the system from sleep states where the core well is not powered.

Table 63. S3/S4/S5 to S0 Cause of Wake Events (Sheet 2 of 2)

Cause	Type	How Enabled
PMC_WAKE_PCIE[0:3]# ¹ (PCI Express WAKE#)	External	PM1_STS_EN.PCIEXP_WAKE_DIS register bit Note: When the PMC_WAKE_PCIE# pin is active and the PM1_STS_EN.PCIEXP_WAKE_DIS register bit is clear, CPU will wake the platform.
Primary PME# ¹	Internal	GPE0a_EN.PME_B0_EN register bit. This wake status bit includes multiple internal agents: HD Audio EHCI (USB2) xHCI SATA Note: SATA can only trigger a wake event if it had asserted its PME prior to S3/S4/S5 entry and software doesn't clear GPE0a_STS.PME_B0_STS, a wake event would still result. PME_B0_S5_DIS bit is used to prevent these devices from waking from S5. Does not apply to wake from S3.
PMC - Initiated ¹	Internal	No enable bits. The PMC can wake the host independent of other wake events listed, if desired. A bit is provided in PRSTS for reporting this wake event to BIOS. Note that this wake event may be used as a wake trigger on behalf of some other wake source.

Note:


1. It is not possible to wake the SoC using this event after a Global Reset, Go-to-S5 type reset.
2. When the HDA_LPE_V1P5V1P8_S3 is powered by a V1P5S rail, the V1P5S rail sequencing should meet the same sequencing requirements as the V1P8S rail.

7.3.3 Handling Power Failures

The power failures can occur if the AC power or battery is removed. In this case, when the system was originally in a S0 state, power failure bit (GEN_PMCON1.PWR_FLR) is set after a power failure. Software can clear the bit. [Chapter 7, "Handling Power Failures"](#)

7.4 Reset Behavior

There are several ways to reset the processor.

**Table 64. Types of Resets (Sheet 1 of 2)**

Trigger	Description	Note
Write of 0Eh to Reset Control Register (RST_CNT)	Write of 0Eh to the Reset Control register	Host Reset with Power Cycle
Write of 06h to Reset Control Register (RST_CNT)	Write of 06h to the Reset Control register	Host Reset without Power Cycle with PMC_PLTRST# assertion
PMC_RSTBTN# & RST_CNT.full_rst = 0	User presses the reset button, causing the PMC_RSTBTN# signal to go active (after the debounce logic)	Host Reset without Power Cycle PMC_PLTRST# assertion enabled/ disabled by RST_CNT.sys_rst
Write of 4h to Reset Control Register (RST_CNT)	Write of 4h to Reset Control Register (RST_CNT)	Host Reset without Power Cycle without PMC_PLTRST# assertion
PMC_RSTBTN# & RST_CNT.full_rst = 1	User presses the reset button, causing the PMC_RSTBTN# signal to go active (after the debounce logic)	Host Reset with Power Cycle
Power Failure	PMC_CORE_PWROK signal goes inactive in S0/S1	Global Reset with Power Cycle
S3/S4/S5	The processor is reset when going to S3, S4 or S5 state	Sx Entry
Processor Thermal Trip	The internal thermal sensor signals a catastrophic temperature condition – transition to S5 and reset asserts	Global Reset, Go-to-S5
PMC_PWRBTN# Power Button Override	4-second press causes transition to S5 (and reset asserts)	Global Reset, Go-to-S5
CPU Shutdown with Policy to assert PMC_PLTRST#	Shutdown special cycle from CPU can cause either INIT or Reset Control-style PMC_PLTRST#	Global Reset with Power Cycle (if ETR.CF9GR = 1b) Host Reset with Power Cycle (if RST_CNT.full_rst= 1b), Host Reset without Power Cycle (others setting)
Write of 06h or 0Eh to Reset Control Register (RST_CNT)	ETR.CF9GR = 1b	Global Reset with Power Cycle
Host Partition Reset Entry Timeout	Host partition reset entry sequence took longer than the allowed timeout value (presumably due to a failure to receive one of the internal or external handshakes)	Global Reset with Power Cycle
S3/S4/S5 Entry Timeout	S3, S4, or S5 entry sequence took longer than the allowed timeout value (presumably due to a failure to receive one of the internal or external handshakes)	Global Reset, Go-to-S5




Table 64. Types of Resets (Sheet 2 of 2)

Trigger	Description	Note
PMC Watchdog Timer	PMC firmware watchdog time expires twice	Global Reset, Go-to-S5
TCO Watchdog Timer	TCO timer	RST_CNT.full_rst = 0: Host Reset without Power Cycle RST_CNT.full_rst = 1: Host Reset with Power Cycle
Host Reset promoted to Global Reset	During boot, TXE FW may promote a Host Reset to a Global Reset in order to apply new TXE or PMC firmware	Global Reset with Power Cycle

Note:

- Host Reset without Power Cycle: All processor functionality not required for correct operation during & after reset, excluding the PMC, is reset and the SoC remain in S0.
- Host Reset with Power Cycle: All processor functionality not required for correct operation during & after reset, excluding the PMC, is reset and the SoC transitions to S5 and then to S0.
- Global Reset with Power Cycle: All processor functionality not required for correct operation during & after reset, including the PMC, is reset and the SoC transitions to S5 and then S0.
- Global Reset, Go-to-S5: All processor functionality not required for correct operation upon wake, including the PMC, are reset and the SoC transitions to S5.



8 Thermal Management

The SoC's thermal management system helps in managing the overall thermal profile of the system to prevent overheating and system breakdown. The architecture implements various proven methods of maintaining maximum performance while remaining within the thermal spec. Throttling mechanisms are used to reduce power consumption when thermal limits of the device are exceeded and the system is notified of critical conditions via interrupts or thermal signalling pins. SoC thermal management differs from legacy implementations primarily by replacing dedicated thermal management hardware with firmware.

The thermal management features are:

- Eight digital thermal sensors (DTS)
- Supports a hardware trip point and four programmable trip points based on the temperature indicated by thermal sensors.
- Supports different thermal throttling mechanisms.

8.1 CPU Thermal Management Registers

The description of the control and status registers can be found in the *Bay Trail SoC BIOS Writer's Guide*.

8.2 Thermal Sensors

SoC provides thermal sensors that use ring oscillator based DTS (Digital Thermal Sensor) to provide more accurate measure of system thermals.

The SoC instantiates multiple digital thermal sensors (one DTS for each processor core, one for each BIU-Bus Interface Unit, and two for non-core SoC) and sensor grouping configurations are provided to optionally select the maximum of all sensors for thermal readout and interrupt generation.

DTS output are adjusted for silicon variations. For a given temperature the output from DTS is always the same irrespective of silicon.

Table 65. Temperature Reading Based on DTS (If $T_{J-MAX} = 90^{\circ}\text{C}$) (Sheet 1 of 2)

DTS Counter Value	Temperature Reading
127	90°C
137	80°C
147	70°C
157	60°C
167	50°C

Table 65. Temperature Reading Based on DTS (If $T_{J-MAX} = 90^{\circ}C$) (Sheet 2 of 2)

DTS Counter Value	Temperature Reading
177	40°C
187	30°C
197	20°C
207	10°C

Note: DTS encoding of 127 always represents T_{J-MAX} . If T_{J-MAX} is at 110°C instead of 90°C then the encoding 127 from DTS indicates 110°C, 137 indicates 90°C and so forth.

Thermal trip points are of two types:

- **Hard Trip:** The Catastrophic trip points generated by DTS's based on predefined temperature setting defined in fuses.
- **Programmable Trips:** four programmable trip settings (Hot, Aux2, Aux1, Aux0) that can be set by firmware/software. Default value for Hot Trip is from Fuses.

Note: DTS accuracy is around 8°C under 60°C and around 6°C above 60°C.

8.3 SoC Programmable Trips

Programmable trips can be programmed to cause different actions when triggered to reduce temperature of the die.

8.3.1 Aux3 Trip


By default, the Aux 3 (Hot Trip) point is set by fuses but the software/firmware has an option to set these to a different value.

This trip point is enabled by firmware to monitor and control the system temperature while the rest of the system is being set up.

8.3.2 Aux2, Aux1, Aux0 Trip

These are fully programmable trip points for general hardware protection mechanisms. The programmable trips are only active after software/firmware enables the trip.

Note: Unlike Aux3, the Aux[2:0] trip registers are defaulted to zero. To prevent spurious results, software/firmware should program the trip values prior to enabling the trip point.



8.4 Platform Trips

8.4.1 PROCHOT#

The platform components use the signal PROCHOT# to indicate thermal events to SoC.

The processor core HOT trip as well as the processor AUX 3 trip are individually sent to firmware, which internally combines them and drives the appropriate PROCHOT back. Assertion of the PROCHOT# input will trigger Thermal Monitor 1 or Thermal Monitor 2 throttling mechanisms if they are enabled.

8.5 Thermal Throttling Mechanisms

Thermal throttling mechanisms are implemented to try to reduce temperature by reducing power consumption in response to a HOT condition. Actions taken as a result of Thermal Trip indication can be as simple as throttling bandwidth and frequency to as drastic as shutting down the PLL's and the entire system. Actions are primarily taken in to prevent system breakdown and are dependent on the severity of the trips.

8.6 Thermal Status

The firmware captures Thermal Trip events (other than THERMTRIP) in status registers to trigger thermal actions. Associated with each event is a set of programmable actions. For a complete list of refer to the *Bay Trail SoC BIOS Writer's Guide*.

9 *Electrical Specifications*

This chapter is split into the following sections:

- “Thermal Specifications”
- “Storage Conditions”
- “Voltage and Current Specifications”
- “Crystal Specifications”
- “DC Specifications”
- “AC Specifications”


9.1 Thermal Specifications

These specifications define the operating thermal limits of the SoC. Thermal solutions not designed to provide the following level of thermal capability may affect the long-term reliability of the processor and system, but more likely result in performance throttling to ensure silicon junction temperatures within spec. For more details on thermal solution design, refer to this product's Thermal/Mechanical Design Guide.

This section specifies the thermal specifications for all SKUs. Some definitions are needed, however. “T_j Max” defines the maximum operating silicon junction temperature. Unless otherwise specified, all specifications in this document assume T_j Max as the worse case junction temperature. This is the temperature needed to ensure TDP specifications when running at guaranteed CPU and graphics frequencies. “TDP” defines the thermal dissipated power for a worse case estimated real world thermal scenario.

Table 66. Intel Atom® Processor E3800 Product Family Thermal Specifications

SKU	T _j Min/Max	TDP
E3845	-40 to 110 °C	10 W @ T _j Max
E3827	-40 to 110 °C	8 W @ T _j Max
E3826	-40 to 110 °C	7 W @ T _j Max
E3825	-40 to 110 °C	6 W @ T _j Max
E3815	-40 to 110 °C	5 W @ T _j Max
E3805	-40 to 110 °C	3 W @ T _j Max



9.2 Storage Conditions

This section specifies absolute maximum and minimum storage temperature and humidity limits for given time durations. Failure to adhere to the specified limits could result in physical damage to the component. If this is suspected, Intel recommends a visual inspection to determine possible physical damage to the silicon or surface components.

Table 67. Storage Conditions Prior to Board Attach

Symbol	Parameter	Min	Max
Tabsolute storage	Device storage temperature when exceeded for any length of time.	-25 °C	125 °C
Tshort term storage	The ambient storage temperature and time for up to 72 hours.	-25 °C	85 °C
Tsustained storage	The ambient storage temperature and time for up to 30 months.	-5 °C	40 °C
RHsustained storage	The maximum device storage relative humidity for up to 30 months.		60% @ 24 °C

Note:

- Specified temperatures are not to exceed values based on data collected. Exceptions for surface mount re-flow are specified by the applicable JEDEC standard. Non-adherence may affect processor reliability.
- Component product device storage temperature qualification methods may follow JESD22-A119 (low temperature) and JESD22-A103 (high temperature) standards when applicable for volatile memory.
- Component stress testing is conducted in conformance with JESD22-A104.
- The JEDEC J-JSTD-020 moisture level rating and associated handling practices apply to all moisture sensitive devices removed from the moisture barrier bag.

9.2.1 Post Board-Attach

The storage condition limits for the component once attached to the application board are not specified. Intel does not conduct component-level certification assessments post board-attach given the multitude of attach methods, socket types, and board types used by customers.

Provided as general guidance only, board-level Intel-branded products are specified and certified to meet the following temperature and humidity limits:


- Non-Operating Temperature Limit: -40 °C to 70 °C
- Humidity: 50% to 90%, non-condensing with a maximum wet-bulb of 28 °C

9.3 Voltage and Current Specifications

The I/O buffer supply voltages are specified at the SoC package balls. The tolerances shown in [Table 86](#) are inclusive of all noise from DC up to 20 MHz. The voltage rails should be measured with a bandwidth limited oscilloscope with a roll-off of 3 dB/decade above 20 MHz under all operating conditions. [Table 94](#) indicates which supplies are connected directly to a voltage regulator or to a filtered voltage rail. For voltage rails that are connected to a filter, they should be measured at the input of the filter. If the recommended platform decoupling guidelines cannot be met, the system designer will have to make trade-offs between the voltage regulator out DC tolerance and the decoupling performances of the capacitor network to stay within the voltage tolerances listed below.

Table 68. Power Rail DC Specs and Max Current

Platform Rail	Voltage Tolerances	Max Icc
V1P0A - UNCORE_V1P0_G3 - USB3_V1P0_G3	1.0 V DC: $\pm 2\%$ AC: $\pm 3\%$	375 mA
V1P24A - USB_HSIC_V1P24_G3 (Can connect to V1P0A when USB HSIC isn't used)	1.24 V DC: $\pm 3\%$ AC: $\pm 2\%$	35 mA
V1P8A - PCU_V1P8_G3 - PMC_V1P8_G3 - UNCORE_V1P8_G3 - USB_V1P8_G3 - USB_ULPI_V1P8_G3	1.8 V DC: $\pm 3\%$ AC: $\pm 2\%$	65 mA
V3P3A - PCU_V3P3_G3 - USB_V3P3_G3	3.3 V DC: $\pm 2\%$ AC: $\pm 3\%$	55 mA
V1P0S - GPIO_V1P0_S3 - PCIE_SATA_V1P0_S3 - PCIE_V1P0_S3 - SATA_V1P0_S3 - SVID_V1P0_S3 - USB3DEV_V1P0_S3 - USB_V1P0_S3 - VGA_V1P0_S3	1.0 V DC: $\pm 2\%$ AC: $\pm 3\%$	1.1 A
V1P0S - DRAM_V1P0_S3 - DDI_V1P0_S3 - UNCORE_V1P0_S3	1.0 V DC: $\pm 2\%$ AC: $\pm 3\%$	2.5 A

**Table 68. Power Rail DC Specs and Max Current**

Platform Rail	Voltage Tolerances	Max Icc
V1P05S - CORE_V1P05_S3	1.05 V DC: $\pm 2\%$ AC: $\pm 3\%$	1.3 A
V1P24S - MIPI_V1P24_S3 (can be grounded if MIPI CSI not used)	1.24 V DC: $\pm 2\%$ AC: $\pm 3\%$	45 mA
V1P35S (VSFR) - ICLK_V1P35_S3_F[2:1] - VGA_V1P35_S3_F1(grounded if VGA not used) - DRAM_V1P35_S3_F1 - UNCORE_V1P35_S3_F[6:1]	1.35 V DC: $\pm 3\%$ AC: $\pm 2\%$	400 mA
V1P5V1P8S (VAUD) - HDA_LPE_V1P5V1P8_S3	1.5 V (LV HDA) 1.8 V (LPE)	In V1P8S
V1P8S - UNCORE_V1P8_S3 - MIPI_V1P8_S3	1.8 V DC: $\pm 3\%$ AC: $\pm 2\%$	10 mA
V1P8V3P3S (VSDIO,VLPC) - LPC_V1P8V3P3_S3 - SD3_V1P8V3P3_S3	1.8 V 3.3 V DC: $\pm 2\%$ AC: $\pm 3\%$	8 mA
V3P3S - VGA_V3P3_S3	3.3 V DC: $\pm 2\%$ AC: $\pm 3\%$	35 mA
VCC - CORE_VCC_S3	See Table 70	See Table 69
VNN - UNCORE_VNN_S3	See Table 70	See Table 69
VDD - DRAM_VDD_S4	1.35 V DC: $\pm 2\%$ AC: $\pm 3\%$	1.3 A
VRTC - RTC_VCC	G3: 2-3.3 V at SoC Otherwise: V3P3A (pre diode drop)	100 μ A (6 μ A Avg.) (see note)

Note: RTC_VCC average current draw (G3) is specified at 27°C under battery conditions.

Note: S3/S4/S5 power is 20 mW max. S3/S4/S5 power is measured during S3/S4/S5 idle as a long term average over worst case silicon at room temperature (27°C). It is intended

to define a limit of the power consumed by the SoC during the S3/S4/S5 state for battery life estimates and power budgeting. Breakdown is as follows: < 4 mA on V1P8A, < 15 mA on V1P0A, < 1 mW on V1P35U/V3P3A/V1P24A.

Table 69. VCC and VNN Currents

SKU	VCC Icc Max	VNN Icc Max
E3845	9 A	10 A
E3827	4 A	10 A
E3826	4 A	10 A
E3825	4 A	9 A
E3815	2 A	8 A
E3805	4 A	7 A

9.3.1 VCC and VNN Voltage Specifications

Table 70 and Table 86 list the DC specifications for the SoC power rails. They are valid only while meeting specifications for junction temperature, clock frequency, and input voltages. Care should be taken to read all notes associated with each parameter.

Table 70. VCC and VNN DC Voltage Specifications


Symbol	Parameter	Min	Typ	Max	Unit	Note
CORE_VCC_S3 VID	Core VID (voltage) Target Range	0.40		1.0	V	1
UNCORE_VNN_S3 VID	Uncore VID (voltage) Target Range	0.50		1.05	V	1
CORE_VCC/ UNCORE_VNN V _{BOOT}	Default target V _{CC} /V _{NN} voltage for initial power up.		1.0 or 1.1		V	2
VCC/VNN Tolerance	Tolerance of VCC/VNN voltage at VID target.	-5		5	%	

NOTES:

- Each SoC is programmed with voltage identification value (VID), which is set at manufacturing and cannot be altered. Individual VID values are calibrated during manufacturing such that two SoCs at the same frequency may have different settings within the VID range above. VID targets employed by the SoC during a power management event are selected within the range uniquely hard-coded into each SoC.
- See the VR12/IMVP7 Pulse Width Modulation specification for additional details. Either value is ok.

9.3.2 Voltage Identification (VID)

The VID specifications for the SoC CORE_VCC_S3 and UNCORE_VNN_S3 are defined by the IMVP7 Pulse Width Modulation (PWM) Specification. Table 71 specifies the voltage level corresponding to the eight bit VID value transmitted over serial VID (SVID)



interface per IMVP7 specification. A '1' in this table refers to a high voltage level and a '0' refers to a low voltage level. If the voltage regulation circuit cannot supply the voltage that is requested, the voltage regulator must disable itself.

The SVID signals are CMOS push/pull drivers. Refer to [Table 103](#) for the DC specifications for these signals. The VID codes will change due to performance, temperature and/or current load changes in order to minimize the power of the part. A voltage range is provided in [Table 70](#). The specifications are set so that one voltage regulator can operate with all supported frequencies.

Individual SoC VID values may be set during manufacturing so that two devices at the same core frequency may have different default VID settings. This is shown in the VID range values in [Table 70](#). The SoC provides the ability to operate while transitioning to an adjacent VID and its associated voltage. This will represent a DC shift in the loadline.

Note: Table below lists all voltages possible per IMVP7 specification. Not all voltages are valid on actual SKUs.


Table 71. IMVP7.0 Voltage Identification Reference (Sheet 1 of 8)

VID7	VID6	VID5	VID4	VID3	VID2	VID1	VID0	Hex bit 1	Hex bit 0	V _{CC} (V)
0	0	0	0	0	0	0	0	0	0	0.00000
0	0	0	0	0	0	0	1	0	1	0.25000
0	0	0	0	0	0	1	0	0	2	0.25500
0	0	0	0	0	0	1	1	0	3	0.26000
0	0	0	0	0	1	0	0	0	4	0.26500
0	0	0	0	0	1	0	1	0	5	0.27000
0	0	0	0	0	1	1	0	0	6	0.27500
0	0	0	0	0	1	1	1	0	7	0.28000
0	0	0	0	1	0	0	0	0	8	0.28500
0	0	0	0	1	0	0	1	0	9	0.29000
0	0	0	0	1	0	1	0	0	A	0.29500
0	0	0	0	1	0	1	1	0	B	0.30000
0	0	0	0	1	1	0	0	0	C	0.30500
0	0	0	0	1	1	0	1	0	D	0.31000
0	0	0	0	1	1	1	0	0	E	0.31500
0	0	0	0	1	1	1	1	0	F	0.32000
0	0	0	1	0	0	0	0	1	0	0.32500
0	0	0	1	0	0	0	1	1	1	0.33000
0	0	0	1	0	0	1	0	1	2	0.33500
0	0	0	1	0	0	1	1	1	3	0.34000



Table 71. IMVP7.0 Voltage Identification Reference (Sheet 2 of 8)

VID7	VID6	VID5	VID4	VID3	VID2	VID1	VID0	Hex bit 1	Hex bit 0	V _{CC} (V)
0	0	0	1	0	1	0	0	1	4	0.34500
0	0	0	1	0	1	0	1	1	5	0.35000
0	0	0	1	0	1	1	0	1	6	0.35500
0	0	0	1	0	1	1	1	1	7	0.36000
0	0	0	1	1	0	0	0	1	8	0.36500
0	0	0	1	1	0	0	1	1	9	0.37000
0	0	0	1	1	0	1	0	1	A	0.37500
0	0	0	1	1	0	1	1	1	B	0.38000
0	0	0	1	1	1	0	0	1	C	0.38500
0	0	0	1	1	1	0	1	1	D	0.39000
0	0	0	1	1	1	1	0	1	E	0.39500
0	0	0	1	1	1	1	1	1	F	0.40000
0	0	1	0	0	0	0	0	2	0	0.40500
0	0	1	0	0	0	0	1	2	1	0.41000
0	0	1	0	0	0	1	0	2	2	0.41500
0	0	1	0	0	0	1	1	2	3	0.42000
0	0	1	0	0	1	0	0	2	4	0.42500
0	0	1	0	0	1	0	1	2	5	0.43000
0	0	1	0	0	1	1	0	2	6	0.43500
0	0	1	0	0	1	1	1	2	7	0.44000
0	0	1	0	1	0	0	0	2	8	0.44500
0	0	1	0	1	0	0	1	2	9	0.45000
0	0	1	0	1	0	1	0	2	A	0.45500
0	0	1	0	1	0	1	1	2	B	0.46000
0	0	1	0	1	1	0	0	2	C	0.46500
0	0	1	0	1	1	0	1	2	D	0.47000
0	0	1	0	1	1	1	0	2	E	0.47500
0	0	1	0	1	1	1	1	2	F	0.48000
0	0	1	1	0	0	0	0	3	0	0.48500
0	0	1	1	0	0	0	1	3	1	0.49000
0	0	1	1	0	0	1	0	3	2	0.49500
0	0	1	1	0	0	1	1	3	3	0.50000
0	0	1	1	0	1	0	0	3	4	0.50500
0	0	1	1	0	1	0	1	3	5	0.51000
0	0	1	1	0	1	1	0	3	6	0.51500
0	0	1	1	0	1	1	1	3	7	0.52000


**Table 71. IMVP7.0 Voltage Identification Reference (Sheet 3 of 8)**

VID7	VID6	VID5	VID4	VID3	VID2	VID1	VID0	Hex bit 1	Hex bit 0	V _{CC} (V)
0	0	1	1	1	0	0	0	3	8	0.52500
0	0	1	1	1	0	0	1	3	9	0.53000
0	0	1	1	1	0	1	0	3	A	0.53500
0	0	1	1	1	0	1	1	3	B	0.54000
0	0	1	1	1	1	0	0	3	C	0.54500
0	0	1	1	1	1	0	1	3	D	0.55000
0	0	1	1	1	1	1	0	3	E	0.55500
0	0	1	1	1	1	1	1	3	F	0.56000
0	1	0	0	0	0	0	0	4	0	0.56500
0	1	0	0	0	0	0	1	4	1	0.57000
0	1	0	0	0	0	1	0	4	2	0.57500
0	1	0	0	0	0	1	1	4	3	0.58000
0	1	0	0	0	1	0	0	4	4	0.58500
0	1	0	0	0	1	0	1	4	5	0.59000
0	1	0	0	0	1	1	0	4	6	0.59500
0	1	0	0	0	1	1	1	4	7	0.60000
0	1	0	0	1	0	0	0	4	8	0.60500
0	1	0	0	1	0	0	1	4	9	0.61000
0	1	0	0	1	0	1	0	4	A	0.61500
0	1	0	0	1	0	1	1	4	B	0.62000
0	1	0	0	1	1	0	0	4	C	0.62500
0	1	0	0	1	1	0	1	4	D	0.63000
0	1	0	0	1	1	1	0	4	E	0.63500
0	1	0	0	1	1	1	1	4	F	0.64000
0	1	0	1	0	0	0	0	5	0	0.64500
0	1	0	1	0	0	0	1	5	1	0.65000
0	1	0	1	0	0	1	0	5	2	0.65500
0	1	0	1	0	0	1	1	5	3	0.66000
0	1	0	1	0	1	0	0	5	4	0.66500
0	1	0	1	0	1	0	1	5	5	0.67000
0	1	0	1	0	1	1	0	5	6	0.67500
0	1	0	1	0	1	1	1	5	7	0.68000
0	1	0	1	1	0	0	0	5	8	0.68500
0	1	0	1	1	0	0	1	5	9	0.69000
0	1	0	1	1	0	1	0	5	A	0.69500
0	1	0	1	1	0	1	1	5	B	0.70000



Table 71. IMVP7.0 Voltage Identification Reference (Sheet 4 of 8)

VID7	VID6	VID5	VID4	VID3	VID2	VID1	VID0	Hex bit 1	Hex bit 0	V _{CC} (V)
0	1	0	1	1	1	0	0	5	C	0.70500
0	1	0	1	1	1	0	1	5	D	0.71000
0	1	0	1	1	1	1	0	5	E	0.71500
0	1	0	1	1	1	1	1	5	F	0.72000
0	1	1	0	0	0	0	0	6	0	0.72500
0	1	1	0	0	0	0	1	6	1	0.73000
0	1	1	0	0	0	1	0	6	2	0.73500
0	1	1	0	0	0	1	1	6	3	0.74000
0	1	1	0	0	1	0	0	6	4	0.74500
0	1	1	0	0	1	0	1	6	5	0.75000
0	1	1	0	0	1	1	0	6	6	0.75500
0	1	1	0	0	1	1	1	6	7	0.76000
0	1	1	0	1	0	0	0	6	8	0.76500
0	1	1	0	1	0	0	1	6	9	0.77000
0	1	1	0	1	0	1	0	6	A	0.77500
0	1	1	0	1	0	1	1	6	B	0.78000
0	1	1	0	1	1	0	0	6	C	0.78500
0	1	1	0	1	1	0	1	6	D	0.79000
0	1	1	0	1	1	1	0	6	E	0.79500
0	1	1	0	1	1	1	1	6	F	0.80000
0	1	1	1	0	0	0	0	7	0	0.80500
0	1	1	1	0	0	0	1	7	1	0.81000
0	1	1	1	0	0	1	0	7	2	0.81500
0	1	1	1	0	0	1	1	7	3	0.82000
0	1	1	1	0	1	0	0	7	4	0.82500
0	1	1	1	0	1	0	1	7	5	0.83000
0	1	1	1	0	1	1	0	7	6	0.83500
0	1	1	1	0	1	1	1	7	7	0.84000
0	1	1	1	1	0	0	0	7	8	0.84500
0	1	1	1	1	0	0	1	7	9	0.85000
0	1	1	1	1	0	1	0	7	A	0.85500
0	1	1	1	1	0	1	1	7	B	0.86000
0	1	1	1	1	1	0	0	7	C	0.86500
0	1	1	1	1	1	0	1	7	D	0.87000
0	1	1	1	1	1	1	0	7	E	0.87500
0	1	1	1	1	1	1	1	7	F	0.88000


**Table 71. IMVP7.0 Voltage Identification Reference (Sheet 5 of 8)**

VID7	VID6	VID5	VID4	VID3	VID2	VID1	VID0	Hex bit 1	Hex bit 0	V _{CC} (V)
1	0	0	1	0	0	0	0	8	0	0.88500
1	0	0	1	0	0	0	1	8	1	0.89000
1	0	0	1	0	0	1	0	8	2	0.89500
1	0	0	0	0	0	1	1	8	3	0.90000
1	0	0	0	0	1	0	0	8	4	0.90500
1	0	0	0	0	1	0	1	8	5	0.91000
1	0	0	0	0	1	1	0	8	6	0.91500
1	0	0	0	0	1	1	1	8	7	0.92000
1	0	0	0	1	0	0	0	8	8	0.92500
1	0	0	0	1	0	0	1	8	9	0.93000
1	0	0	0	1	0	1	0	8	A	0.93500
1	0	0	0	1	0	1	1	8	B	0.94000
1	0	0	0	1	1	0	0	8	C	0.94500
1	0	0	0	1	1	0	1	8	D	0.95000
1	0	0	0	1	1	1	0	8	E	0.95500
1	0	0	0	1	1	1	1	8	F	0.96000
1	0	0	0	0	0	0	0	9	0	0.96500
1	0	0	0	0	0	0	1	9	1	0.97000
1	0	0	0	0	0	1	0	9	2	0.97500
1	0	0	1	0	0	1	1	9	3	0.98000
1	0	0	1	0	1	0	0	9	4	0.98500
1	0	0	1	0	1	0	1	9	5	0.99000
1	0	0	1	0	1	1	0	9	6	0.99500
1	0	0	1	0	1	1	1	9	7	1.00000
1	0	0	1	1	0	0	0	9	8	1.00500
1	0	0	1	1	0	0	1	9	9	1.01000
1	0	0	1	1	0	1	0	9	A	1.01500
1	0	0	1	1	0	1	1	9	B	1.02000
1	0	0	1	1	1	0	0	9	C	1.02500
1	0	0	1	1	1	0	1	9	D	1.03000
1	0	0	1	1	1	1	0	9	E	1.03500
1	0	0	1	1	1	1	1	9	F	1.04000
1	0	1	1	0	0	0	0	A	0	1.04500
1	0	1	1	0	0	0	1	A	1	1.05000
1	0	1	1	0	0	1	0	A	2	1.05500
1	0	1	0	0	0	1	1	A	3	1.06000



Table 71. IMVP7.0 Voltage Identification Reference (Sheet 6 of 8)

VID7	VID6	VID5	VID4	VID3	VID2	VID1	VID0	Hex bit 1	Hex bit 0	V _{CC} (V)
1	0	1	0	0	1	0	0	A	4	1.06500
1	0	1	0	0	1	0	1	A	5	1.07000
1	0	1	0	0	1	1	0	A	6	1.07500
1	0	1	0	0	1	1	1	A	7	1.08000
1	0	1	0	1	0	0	0	A	8	1.08500
1	0	1	0	1	0	0	1	A	9	1.09000
1	0	1	0	1	0	1	0	A	A	1.09500
1	0	1	0	1	0	1	1	A	B	1.10000
1	0	1	0	1	1	0	0	A	C	1.10500
1	0	1	0	1	1	0	1	A	D	1.11000
1	0	1	0	1	1	1	0	A	E	1.11500
1	0	1	0	1	1	1	1	A	F	1.12000
1	0	1	0	0	0	0	0	B	0	1.12500
1	0	1	0	0	0	0	1	B	1	1.13000
1	0	1	0	0	0	1	0	B	2	1.13500
1	0	1	1	0	0	1	1	B	3	1.14000
1	0	1	1	0	1	0	0	B	4	1.14500
1	0	1	1	0	1	0	1	B	5	1.15000
1	0	1	1	0	1	1	0	B	6	1.15500
1	0	1	1	0	1	1	1	B	7	1.16000
1	0	1	1	1	0	0	0	B	8	1.16500
1	0	1	1	1	0	0	1	B	9	1.17000
1	0	1	1	1	0	1	0	B	A	1.17500
1	0	1	1	1	0	1	1	B	B	1.18000
1	0	1	1	1	1	0	0	B	C	1.18500
1	0	1	1	1	1	0	1	B	D	1.19000
1	0	1	1	1	1	1	0	B	E	1.19500
1	0	1	1	1	1	1	1	B	F	1.20000
1	1	0	0	0	0	0	0	C	0	1.20500
1	1	0	0	0	0	0	1	C	1	1.21000
1	1	0	0	0	0	1	0	C	2	1.21500
1	1	0	0	0	0	1	1	C	3	1.22000
1	1	0	0	0	1	0	0	C	4	1.22500
1	1	0	0	0	1	0	1	C	5	1.23000
1	1	0	0	0	1	1	0	C	6	1.23500
1	1	0	0	0	1	1	1	C	7	1.24000

**Table 71. IMVP7.0 Voltage Identification Reference (Sheet 7 of 8)**

VID7	VID6	VID5	VID4	VID3	VID2	VID1	VID0	Hex bit 1	Hex bit 0	V _{CC} (V)
1	1	0	0	1	1	0	0	C	8	1.24500
1	1	0	0	1	0	0	1	C	9	1.25000
1	1	0	0	1	0	1	0	C	A	1.25500
1	1	0	0	1	0	1	1	C	B	1.26000
1	1	0	0	1	0	0	0	C	C	1.26500
1	1	0	0	1	1	0	1	C	D	1.27000
1	1	0	0	1	1	1	0	C	E	1.27500
1	1	0	0	1	1	1	1	C	F	1.28000
1	1	0	1	0	1	0	0	D	0	1.28500
1	1	0	1	0	1	0	1	D	1	1.29000
1	1	0	1	0	0	1	0	D	2	1.29500
1	1	0	1	0	0	1	1	D	3	1.30000
1	1	0	1	0	1	0	0	D	4	1.30500
1	1	0	1	0	1	0	1	D	5	1.31000
1	1	0	1	0	1	1	0	D	6	1.31500
1	1	0	1	0	1	1	1	D	7	1.32000
1	1	0	1	1	0	0	0	D	8	1.32500
1	1	0	1	1	0	0	1	D	9	1.33000
1	1	0	1	1	0	1	0	D	A	1.33500
1	1	0	1	1	0	1	1	D	B	1.34000
1	1	0	1	1	1	0	0	D	C	1.34500
1	1	0	1	1	1	0	1	D	D	1.35000
1	1	0	1	1	1	1	0	D	E	1.35500
1	1	0	1	1	1	1	1	D	F	1.36000
1	1	1	0	0	0	0	0	E	0	1.36500
1	1	1	0	0	0	0	1	E	1	1.37000
1	1	1	0	0	0	1	0	E	2	1.37500
1	1	1	0	0	0	1	1	E	3	1.38000
1	1	1	0	0	1	0	0	E	4	1.38500
1	1	1	0	0	1	0	1	E	5	1.39000
1	1	1	0	0	1	1	0	E	6	1.39500
1	1	1	0	0	1	1	1	E	7	1.40000
1	1	1	0	1	0	0	0	E	8	1.40500
1	1	1	0	1	0	0	1	E	9	1.41000
1	1	1	0	1	0	1	0	E	A	1.41500
1	1	1	0	1	0	1	1	E	B	1.42000

Table 71. IMVP7.0 Voltage Identification Reference (Sheet 8 of 8)

VID7	VID6	VID5	VID4	VID3	VID2	VID1	VID0	Hex bit 1	Hex bit 0	V _{CC} (V)
1	1	1	0	1	1	0	0	E	C	1.42500
1	1	1	0	1	1	0	1	E	D	1.43000
1	1	1	0	1	1	1	0	E	E	1.43500
1	1	1	0	1	1	1	1	E	F	1.44000
1	1	1	1	0	0	0	0	F	0	1.44500
1	1	1	1	0	0	0	1	F	1	1.45000
1	1	1	1	0	0	1	0	F	2	1.45500
1	1	1	1	0	0	1	1	F	3	1.46000
1	1	1	1	0	1	0	0	F	4	1.46500
1	1	1	1	0	1	0	1	F	5	1.47000
1	1	1	1	0	1	1	0	F	6	1.47500
1	1	1	1	0	1	1	1	F	7	1.48000
1	1	1	1	1	0	0	0	F	8	1.48500
1	1	1	1	1	0	0	1	F	9	1.49000
1	1	1	1	1	0	1	0	F	A	1.49500
1	1	1	1	1	0	1	1	F	B	1.50000
1	1	1	1	1	1	0	0	F	C	1.49500
1	1	1	1	1	1	0	1	F	D	1.50000
1	1	1	1	1	1	1	0	F	E	1.49500
1	1	1	1	1	1	1	1	F	F	1.50000

9.4 Crystal Specifications

There are two crystal. One for RTC which maintains time and provides initial timing reference for power sequencing. The other is for the Integrated Clock, which covers clocking for the entire SoC.

Table 72. ILB RTC Crystal Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes
F _{RTC}	Frequency	-	32.768	-	kHz	1
T _{PPM}	Crystal frequency tolerance (see notes)	-	-	+/-50	ppm	1
R _{ESR}	ESR	-	-	50	kOhm	1
C _{X1,2}	Capacitance of X1, X2 pins				pF	1

NOTES:

- These are the specifications needed to select a crystal oscillator for the RTC circuit.



2. Crystal tolerance impacts RTC time. A 10 ppm crystal is recommended for 1.7 s tolerance per day, RTC circuit itself contributes addition 10 ppm for a total of 20 ppm in this example.

Table 73. Integrated Clock Crystal Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes
F _{ICLK}	Frequency	-	25	-	MHz	1
T _{PPM}	Crystal frequency tolerance & stability	-	-	+/-100	ppm	1
P _{DRIVE}	Crystal drive load	-	-	100	uW	1
R _{ESR}	ESR	-	-	100	Ohm	1
C _{LOAD}	Crystal load capacitance		18		pF	
C _{SHUNT}	Crystal shunt capacitance	-	-	6	pF	1
C _{IN/OUT}	Capacitance of oscillator pins				pF	1

NOTES:


1. These are the specifications needed to select a crystal oscillator for the Integrated Clock circuit. Crystal must be AT cut, fundamental, parallel resonance.

9.5 DC Specifications

Platform reference voltages are specified at DC only. V_{REF} measurements should be made with respect to the supply voltages specified in [“Voltage and Current Specifications”](#).

See the following DC Specifications in this section:

- [“Display DC Specification”](#)
- [“PCI Express* DC Specification”](#)
- [“MIPI-Camera Serial Interface \(CSI\) DC Specification”](#)
- [“SCC - SDIO DC Specification”](#)
- [“SCC - SD Card DC Specification”](#)
- [“SCC - eMMC 4.5 DC Specification”](#)
- [“SATA DC Specification”](#)
- [“JTAG \(TAP\) DC Specification”](#)
- [“DDR3L Memory Controller DC Specification”](#)
- [“USB 2.0 Host DC Specification”](#)
- [“USB 3.0 DC Specification”](#)
- [“PCU - iLB - LPC DC Specification”](#)
- [“PCU - SPI \(Platform Control Unit\) DC Specification”](#)
- [“PCU - Power Management/Thermal \(PMC\) & iLB RTC DC Specification”](#)
- [“SVID DC Specification”](#)
- [“GPIO DC Specification”](#)



- “SIO - I²C DC Specification”
- “SIO - UART DC Specification”
- “I²S (Audio) DC Specification”

Note: Care should be taken to read all notes associated with each parameter.

9.5.1 Display DC Specification

DC specifications for display interfaces:

- “Analog VGA Video DC Specification”
- “Digital Display Interface (DDI) Signals DC Specification”

9.5.1.1 Analog VGA Video DC Specification


Interface DC Specifications are referred to the VESA Video Signal Standard, version 1 revision 2.

Table 74. R,G,B/VGA DAC Display DC specification (Functional Operating Range)

Parameter	Min	Typ	Max	Units	Notes
Resolution		8		bits	1
Max Luminance (full-scale)	0.665	0.700	0.770	V	1,2,4 (white video level voltage)
Min Luminance		0.0		V	1,3,4 (black video level voltage)
LSB Current		73.2	8	μA	4,5
Integral Non Linearity (INL)	-1.0		+1.0	LSB	1,6
Differential Non-Linearity (DNL)	-1.0		+1.0	LSB	1,6
Video Channel-to-Channel Voltage amplitude mismatch			6	%	7
Monotonicity		Guaranteed			

NOTES:

1. Measured at each R,G,B termination according to the VESA Test Procedure – Evaluation of Analog Display Graphics Subsystems Proposal (Version 1, Draft 4, December 1, 2000).
2. Max steady-state amplitude
3. Min steady-state amplitude
4. Defined for a double 75 Ω termination
5. Set by external reference resistor value
6. INL & DNL measured and calculated according to VESA Video Signal Standards
7. Max fill-scale voltage difference among R,G,B outputs (percentage of steady-state full-scale voltage).

**Table 75. VGA_DDCCLK, VGA_DDCDATA Signal DC Specification**

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	VGA_V3P3_S3				
V _{IH}	Input High Voltage	2		V _{ref}	V	1
V _{IL}	Input Low Voltage	0		0.8	V	2
V _{OL}	Output Low Voltage	0		0.4	V	3
I _i	Input Pin Leakage	-45		45	μA	4

NOTES:

1. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value.
2. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value.
3. 3 mA sink current.
4. For V_{IN} between 0V and VGA_V3P3_S3. Measured when driver is tri-stated.

Table 76. VGA_HSYNC and VGA_VSYNC DC Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	VGA_V3P3_S3				
V _{OH}	Output High Voltage	2.4		V _{REF}	V	
V _{OL}	Output Low Voltage	0		0.5	V	
I _{OH}	Output High Current			8	mA	
I _{OL}	Output Low Current			8	mA	
I _i	Input Pin Leakage	-35		35	μA	1

NOTE:

1. For V_{IN} between 0-V and VGA_V3P3_S3. Measured when driver is tri-stated.

9.5.1.2 Digital Display Interface (DDI) Signals DC Specification**Table 77. DDI Main Transmitter DC specification**

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{TX-DIFFp-p-Level0}	Differential Peak-to-peak Output Voltage Level 0	0.34	0.4	0.46	V	1
V _{TX-DIFFp-p-Level1}	Differential Peak-to-peak Output Voltage Level 1	0.51	0.6	0.68	V	1
V _{TX-DIFFp-p-Level2}	Differential Peak-to-peak Output Voltage Level 2	0.69	0.8	0.92	V	1
V _{TX-DIFFp-p-Level3}	Differential Peak-to-peak Output Voltage Level 3	0.85	1.2	1.38	V	1
V _{TX-PREEMP-RATIO}	No Pre-emphasis	0.0	0.0	0.0	dB	1
	3.5 dB Pre-emphasis	2.8	3.5	4.2	dB	1

Table 77. DDI Main Transmitter DC specification


Symbol	Parameter	Min	Typ	Max	Units	Notes
	6.0 dB Pre-emphasis	4.8	6.0	7.2	dB	1
	9.5 dB Pre-emphasis	7.5	9.5	11.4	dB	1
V _{TX-DC-CM}	Tx DC Common Mode Voltage	0		2.0	V	1
RLTX-DIFF	Differential Return Loss at 0.675GHz at Tx Package pins	12			dB	4
	Differential Return Loss at 1.35 GHz at Tx Package pins	9			dB	4
C _{TX}	AC Coupling Capacitor	75		200	nF	5
V _{off}	Single Ended Standby (off), output voltage	-10		10	mV	6 @ AV _{cc}
V _{swing}	Single Ended output swing voltage	400		600	mV	
V _{OH} (<=165 MHz)	Single Ended high level, output voltage	-10		10	mv	6 @ AV _{cc}
V _{OH} (>165 MHz)	Single Ended high level, output voltage	-200		10	mV	6 @ AV _{cc}
V _{OL} (<=165 MHz)	Single Ended low level, output voltage	-600		-400	mV	6 @ AV _{cc}
V _{OL} (>165MHz)	Single Ended low level, output voltage	-700		-400	mV	6 @ AV _{cc}

NOTES:

1. For embedded connection, support of programmable voltage swing levels is optional.
2. Total drive current of the transmitter when it is shorted to its ground.
3. Common mode voltage is equal to V_{bias_Tx} voltage shown in [Figure 14](#).
4. Straight loss line between 0.675 GHz and 1.35 GHz.
5. All DisplayPort Main Link lanes as well as AUX CH must be AC coupled. AC coupling capacitors must be placed on the transmitter side. Placement of AC coupling capacitors on the receiver side is optional.
6. AV_{cc} =Analog Voltage level

Table 78. DDI AUX Channel DC Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{AUX-DIFFp-p}	AUX Peak-to-peak Voltage at a transmitting Device	0.29		1.38	V	1
V _{AUX-TERM_R}	AUX CH termination DC resistance		100		Ω	
V _{AUX-DC-CM}	AUX DC Common Mode Voltage	0		2.0	V	2

**Table 78. DDI AUX Channel DC Specification**

Symbol	Parameter	Min	Typ	Max	Units	Notes
$V_{\text{AUX-TURN-CM}}$	AUX turn around common mode voltage			0.3	V	3
$I_{\text{AUX_SHORT}}$	AUX Short Circuit Current Limit			90	mA	4
C_{AUX}	AC Coupling Capacitor	75		200	nF	5

NOTES:

- $V_{\text{AUX-DIFFP-P}} = 2 * |V_{\text{AUXP}} - V_{\text{AUXM}}|$
- Common mode voltage is equal to $V_{\text{bias_Tx}}$ (or $V_{\text{bias_Rx}}$) voltage.
- Steady state common mode voltage shift between transmit and receive modes of operation.
- Total drive current of the transmitter when it is shorted to its ground.
- All DisplayPort Main Link lanes as well as AUX CH must be AC coupled. AC coupling capacitors must be placed on the transmitter side. Placement of AC coupling capacitors on the receiver side is optional.

NOTES:

Table 79. DDI DDC Signal DC Specification (DDI[1:0]_DDCDATA, DDI[1:0]_DDCCLK)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V_{REF}	I/O Voltage	MIPI_V1P8_S3			V	
V_{IH}	Input High Voltage	$0.65 * V_{\text{REF}}$		V_{REF}	V	1
V_{IL}	Input Low Voltage	0		$0.35 * V_{\text{REF}}$	V	2
V_{OL}	Output Low Voltage	0		0.4	V	3
I_{i}	Input Pin Leakage	-30		30	μA	4

- V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value
- V_{IL} is defined as the maximum voltage level at a receiving agent that will be interpreted as a logical low value.
- 3mA sink current.
- For VIN between 0V and CORE_VCC_S3. Measured when driver is tri-stated.

Table 80. DDI DDC Misc Signal DC Specification (DDI[1:0]_HPD, DDI[1:0]_BKLTCTL, DDI[1:0]_VDDEN, DDI[1:0]_BKLTEN)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V_{REF}	I/O Voltage	MIPI_V1P8_S3			V	
V_{IH}	Input High Voltage	$0.65 * V_{\text{REF}}$		V_{REF}	V	1
V_{IL}	Input Low Voltage	0		$0.35 * V_{\text{REF}}$	V	2
Z_{pu}	Pull up Impedance	40	50	60	Ω	3
Z_{pd}	Pull down Impedance	40	50	60	Ω	3
I_{i}	Input Pin Leakage	-20		20	μA	4

- V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value
- V_{IL} is defined as the maximum voltage level at a receiving agent that will be interpreted as a logical low value.
- Measured at CORE_VCC_S3.
- For VIN between 0V and CORE_VCC_S3. Measured when driver is tri-stated.

Figure 14. Definition of Differential Voltage and Differential Voltage Peak-to-Peak






Figure 15. Definition of Pre-emphasis





9.5.2 PCI Express* DC Specification

Table 81. PCI Express* DC Receive Signal Characteristics

Symbol	Parameter	Min	Typ	Max	Unit	Notes
V _{RXDIFF} Gen1	Differential RX Peak to Peak	175		1200	mV	1
V _{RXDIFF} Gen2	Differential RX Peak to Peak	100		1200	mV	1

NOTE:

1. PCI Express differential peak to peak = $2 * |RXp[x] - RXn[x]|$

Table 82. PCI Express* DC Transmit Characteristics

Symbol	Parameter	Min	Typ	Max	Unit	Notes
V _{TXDIFF}	Differential TX Peak to Peak	800		1200	mV	1
V _{TXDIFF-LP}	Differential TX Peak to Peak (low power mode)	400		1200	mV	1

NOTE:

1. PCI Express differential peak to peak = $2 * |TXp[x] - TXn[x]|$

Table 83. PCI Express* DC Clock Request Input Signal Characteristics

Symbol	Parameter	Min	Typ	Max	Unit	Notes
V _{REF}	I/O Voltage	UNCORE_V1P8_S3				
V _{IL}	Input Low Voltage	0		0.3*V _{REF}	V	1
V _{IH}	Input High Voltage	0.65*V _{REF}		V _{REF}	V	1

9.5.3 MIPI-Camera Serial Interface (CSI) DC Specification

Table 84. MIPI HS-RX/MIPI LP-RX Minimum, Nominal, and Maximum Voltage Parameters (Sheet 1 of 2)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Notes
I _{LEAK}	Pin Leakage current	-10	-	10	μA	
MIPI-CSI HS-RX Mode						
V _{CMRX(DC)}	Common-mode voltage HS receive mode	70	-	330	mV	
V _{IDTH}	Differential input high threshold	-	-	70	mV	
V _{IDTL}	Differential input low threshold	-70	-	-	mV	
V _{IHHS}	Single-ended input high voltage	-	-	460	mV	
V _{ILHS}	Single-ended input low voltage	-40	-	-	mV	
V _{TERM-EN}	Single-ended threshold for HS termination enable	-	-	450	mV	
Z _{ID}	Differential input impedance	80	100	125	Ω	

**Table 84. MIPI HS-RX/MIPI LP-RX Minimum, Nominal, and Maximum Voltage Parameters (Sheet 2 of 2)**

Symbol	Parameter	Min.	Typ.	Max.	Unit	Notes
MIPI-CSI LP-RX Mode						
V _{IH}	Logic 1 input voltage	880	–	–	mV	
V _{IL}	Logic 0 input voltage, not in ULP state	–	–	550	mV	
V _{IL-ULPS}	Logic 0 input voltage, ULP state	–	–	300	mV	
V _{HYST}	Input hysteresis	25	–	–	mV	

9.5.4 SCC - SDIO DC Specification

Table 85 provides the SDIO DC Specification, for all other DC Specifications not listed in Table 85, refer to Table 106, "GPIO 1.8V Core Well Signal Group DC Specification (GPIO_S0_SC[101:0]).

Table 85. SDIO DC Specification

Symbol	Parameter	Min.	Typ.	Max.	Unit	Notes
V _{OH}	Output High Voltage	1.4	–	–	V	Measured at I _{OH} maximum.
I _{OH} /I _{OL}	Current at VoL/Voh	-2	–	–	mA	

9.5.5 SCC - SD Card DC Specification

Table 86 provides the SD Card DC Specification, for all other DC Specifications not listed in Table 86, refer to Table 106, "GPIO 1.8V Core Well Signal Group DC Specification (GPIO_S0_SC[101:0]).

Table 86. SD Card DC Specification

Symbol	Parameter	Min.	Max.	Unit
V _{REF}	I/O Voltage	SD3_V1P8V3P3_S3		
V _{OH}	Output High Voltage	0.75*V _{REF}	V _{REF}	V
V _{OL}	Output Low Voltage	0	0.125*V _{REF}	V
V _{IH} (3.3)	Input High Voltage (3.3 V)	0.625*V _{REF}	V _{REF}	V
V _{IL} (3.3)	Input Low Voltage (3.3 V)	0	0.25*V _{REF}	V
V _{PEAK} (3.3)	Peak Voltage on All lines	-0.3	V _{REF} +0.3	V
V _{IH} (1.8)	Input High Voltage (1.8 V)	1.28	V _{REF}	V


Table 86. SD Card DC Specification

Symbol	Parameter	Min.	Max.	Unit
V_{IL} (1.8)	Input Low Voltage (1.8 V)	0	0.58	V
V_{PEAK} (1.8)	Peak Voltage on All lines	-0.3	$V_{REF} + 0.3$	V
I_{OH}/I_{OL}	Current at VoL/Voh	-45	45	μA
$V_{hysteresis}$	Input Hysteresis	None		V
C_{LOAD}	Input Load Capacitance	4	9	pF

9.5.6 SCC - eMMC 4.5 DC Specification

Table 87. eMMC 4.5 Signal DC Electrical Specifications

Symbol	Parameter	Min	Max	Units
V_{REF}	I/O Voltage	UNCORE_V1P8_S3		
V_{OH}	Output HIGH voltage	$V_{REF} - 0.45$	V_{REF}	V
V_{OI}	Output LOW voltage	0	0.45	V
V_{IH}	Input HIGH voltage	$0.65 * V_{REF}$	$V_{REF} + 0.3$	V
V_{IL}	Input LOW voltage	-0.3	$0.35 * V_{REF}$	V
C_L	Bus Signal Line capacitance	-	30	pF
I_{LI}	Input Leakage Current	-2	2	μA
I_{LO}	Output Leakage Current	-2	2	μA

Figure 16. eMMC DC Bus signal level



9.5.7 JTAG (TAP) DC Specification

Table 88. TAP Signal Group DC Specification (TAP_TCK, TAP_TRST#, TAP_TMS, TAP_TDI)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	PMC_V1P8_G3				
V _{IH}	Input High Voltage	0.8*V _{REF}		V _{REF}	V	1
V _{IL}	Input Low Voltage	0		0.4*V _{REF}	V	2
Z _{pu}	Pull up Impedance			60	Ω	3
Z _{pd}	Pull down Impedance			60	Ω	3
R _{wpu}	Weak Pull Impedance	1		4	kΩ	3
R _{wpd}	Weak Pull Down Impedance	1		4	kΩ	3
R _{wpu-40K}	Weak Pull Up Impedance 40K	20		70	kΩ	4
R _{wpd-40K}	Weak Pull Down Impedance 40K	20		70	kΩ	4

NOTES:


1. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value
2. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value.
3. Measured at PMC_V1P8_G3/2.
4. R_{wpu_40k} and R_{wpd_40k} are only used for TAP_TRST#

Table 89. TAP Signal Group DC Specification (TAP_TDO)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	PMC_V1P8_G3				
V _{IH}	Input High Voltage	0.8*V _{REF}		V _{REF}	V	1
V _{IL}	Input Low Voltage	0		0.5*V _{REF}	V	2
Z _{pd}	Pull down Impedance			30	Ω	3
R _{wpu}	Weak Pull Impedance	1		4	kΩ	3
R _{wpd}	Weak Pull Down Impedance	1		4	kΩ	3

NOTES:

1. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value
2. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value.
3. Measured at PMC_V1P8_G3/2.

**Table 90. TAP Signal Group DC Specification (TAP_PRDY#, TAP_PREQ#)**

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	PMC_V1P8_G3				
V _{IH}	Input High Voltage	0.64*V _{REF}		V _{REF}	V	1
V _{IL}	Input Low Voltage	0		0.4*V _{REF}	V	2
Z _{pd}	Pull down Impedance			30	Ω	3
R _{wpu}	Weak Pull Impedance	1		4	kΩ	3

NOTES:

1. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value
2. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value.
3. Measured at PMC_V1P8_G3/2.

9.5.8 DDR3L Memory Controller DC Specification

Table 91. DDR3L Signal Group DC Specifications (Sheet 1 of 2)

Symbol	Parameter	Min	Type	Max	Units	Notes
V _{IL}	Input Low Voltage			DRAM_VREF - 200mV	V	1
V _{IH}	Input High Voltage	DRAM_VREF + 200mV			V	2, 3
V _{OL}	Output Low Voltage		(DRAM_VDD_S4 / 2) * (RON / (RON + RVTT_TERM))			3,4
V _{OH}	Output High Voltage		DRAM_VDD_S4 - ((DRAM_VDD_S4 / 2) * (RON / (RON + RVTT_TERM)))		V	3,4
I _{IL}	Input Leakage Current			5	μA	For all DRAM Signals
R _{ON}	DDR3L-RS Clock Buffer strength	26		40	Ω	5
C _{IO}	DQ/DQS/DQS# DDR3L-RS IO Pin Capacitance		3.0		pF	
V _{IH}	Input High Voltage	1.1			V	DRAM_VD D_S4_PW ROK DRAM_CO RE_PWRO K

Table 91. DDR3L Signal Group DC Specifications (Sheet 2 of 2)

Symbol	Parameter	Min	Type	Max	Units	Notes
V _{IL}	Input Low Voltage			0.3	V	DRAM_VDD_S4_PWORK DRAM_CORE_PWORK
Pin Leakage				100	μA	
V _{IH}	Input High Voltage	0.83			V	CMD/CTL
V _{IL}	Input Low Voltage			0.55	V	CMD/CTL
Pin Leakage				50	μA	

NOTES:

- V_{IL} is defined as the maximum voltage level at the receiving agent that will be received as a logical low value. DRAM_VREF is normally DRAM_VDD_S4/2
- V_{IH} is defined as the minimum voltage level at the receiving agent that will be received as a logical high value. DRAM_VREF is normally DRAM_VDD_S4/2
- V_{IH} and V_{OH} may experience excursions above DRAM_VDD_S4. However, input signal drivers must comply with the signal quality specifications.
- RON is DRAM driver resistance whereas RTT_TERM is DRAM ODT resistance which is controlled by DRAM.
-
- DDR3L-1333 CLK buffer Ron is 26ohm and SR target is 4V/ns; DQ-DQS buffer Ron is 30ohms and SR target is 4V/ns; CMD/CTL buffer Ron is 20ohms and SR target is 1.8V/ns.


9.5.9 Intel® HD Audio DC Specification

Table 92. HDA Signal Group DC Specifications

Symbol	Parameter	Condition	Min	Max	Unit	Notes
VCC _{HDA}	HDA Supply Voltage		HDA_LPE_V1P5V1P8_S3			
V _{IH_HDA}	Input High Voltage		0.6*VCC _{HDA}		V	
V _{IL_HDA}	Input Low Voltage			0.4*VCC _{HDA}	V	
V _{OH_HDA}	Output High Voltage	I _{out} = -500μA	0.9*VCC _{HDA}		V	
V _{OL_HDA}	Output Low Voltage	I _{out} = 1500μA		0.1*VCC _{HDA}	V	
I _{IL_HDA}	Input Leakage Current	0 < V _{in} < VCC _{HDA}		±175	μA	1
C _{IN_HDA}	Input Pin Capacitance			7.5	pF	
L _{PIN_HDA}	Pin Inductance			20	nH	2

NOTES:

- For HDA_SDI[x] buffers (or in general any bidirectional buffer with tri-state output), input leakage current also include hi-Z output leakage.
- This is a recommendation, not an absolute requirement.



9.5.10 USB 2.0 Host DC Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes
Supply Voltage:						
VBUS	High-power Port	4.75		5.25	V	2
VBUS	Low-power Port					
Supply Current:						
ICCPRT	High-power Hub Port (out)	500			mA	
ICCUPT	Low-power Hub Port (out)	100			mA	
ICCHPF	High-power Function (in)			500	mA	
ICCLPF	Low-power Function (in)			100	mA	
ICCINIT	Unconfigured Function/Hub (in)			100	mA	
ICCSH	Suspended High-power Device			2.5	mA	15
ICCSL	Suspended Low-power Device			500	μA	
Input Levels for Low-/full-speed:						
VIH	High (driven)	2.0			V	4
VIHZ	High (floating)	2.7		3.6	V	4
VIL	Low			0.8	V	4
VDI	Differential Input Sensitivity	0.2			V	(D+)-(D-) ; Figure; Note 4
VCM	Differential Common Mode Range	0.8		2.5	V	Includes VDI range; Figure; Note 4
Input Levels for High-speed:						
VHSSQ	High-speed squelch detection threshold (differential signal amplitude)	100		150	mV	
VHSDSC	High speed disconnect detection threshold (differential signal amplitude)	525		625	mV	
	High-speed differential input signaling levels					
VHSCM	High-speed data signaling common mode voltage range (guideline for receiver)	-50		500	mV	
Output Levels for Low-/full-speed:						
VOL	Low	0.0		0.3	V	4,5



Symbol	Parameter	Min	Typ	Max	Units	Notes
VOH	High (Driven)	2.8		3.6	V	4,6
VOSE1	SE1	0.8			V	
VCRS	Output Signal Crossover Voltage	1.3		2.0	V	10
Output Levels for High-speed:						
VHSOI	High-speed idle level	-10		10	mV	
VHSOH	High-speed data signaling high	360		440	mV	
VHSOL	High-speed data signaling low	-10		10	mV	
VCHIRPJ	Chirp J level (differential voltage)	700		1100	mV	
VCHIRPK	Chirp K level (differential voltage)	-900		-500	mV	
Decoupling Capacitance:						
CHPB	Downstream Facing Port Bypass Capacitance (per hub)	120			μF	
CRPB	Upstream Facing Port Bypass Capacitance	1.0		10.0	μF	9
Input Capacitance for Low-/full-speed:						
CIND	Downstream Facing Port			150	pF	2
CINUB	Upstream Facing Port (w/o cable)			100	pF	3
CEDGE	Transceiver edge rate control capacitance			75	pF	
Input Impedance for High-speed:						
	TDR spec for high-speed termination					
Terminations:						
RPU	Bus Pull-up Resistor on Upstream Facing Port	1.425		1.575	kΩ	1.5 kΩ ±5%
RPD	Bus Pull-down Resistor on Downstream Facing Port	14.25		15.75	kΩ	1.5 kΩ ±5%
ZINP	Input impedance exclusive of pull-up/pull-down (for low-/full speed)	300			kΩ	
VTERM	Termination voltage for upstream facing port pull-up (RPU)	3.0		3.6	V	
Terminations in High-speed:						
VHSTERM	Termination voltage in high speed	-10		10	mV	

NOTES:

1. Measured at A plug.
2. Measured at A receptacle.
3. Measured at B receptacle.



4. Measured at A or B connector.
5. Measured with RL of 1.425 k Ω to 3.6 V.
6. Measured with RL of 14.25 k Ω to GND.
7. Timing difference between the differential data signals.
8. Measured at crossover point of differential data signals.
9. The maximum load specification is the maximum effective capacitive load allowed that meets the target VBUS drop of 330 mV.
10. Excluding the first transition from the Idle state.
11. The two transitions should be a (nominal) bit time apart.
12. For both transitions of differential signaling.
13. Must accept as valid EOP.
14. Single-ended capacitance of D+ or D- is the capacitance of D+/D- to all other conductors and, if present, shield in the cable. That is, to measure the single-ended capacitance of D+, short D-, VBUS, GND, and the shield line together and measure the capacitance of D+ to the other conductors.
15. For high power devices (non-hubs) when enabled for remote wakeup.

9.5.11 USB 3.0 DC Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes
UI	Unit Interval	199.94		200.06	ps	1
V _{TX-DIFF-PP}	Differential peak-peak Tx voltage swing	0.9	1	1.05	V	
V _{TX-DIFF-PP-LOW}	Low-Power Differential peak-peak Tx voltage swing	0.4		1.2	V	2
V _{TX-DE-RATIO}	Tx De-Emphasis	3.45	3.5	3.65	dB	
R _{TX-DIFF-DC}	DC differential impedance	88		92	Ω	
V _{TX-RCV-DETECT}	The amount of voltage change allowed during Receiver Detection			0.6	V	3
C _{AC-COUPLING}	AC Coupling Capacitor	75		200	nF	4
t _{CDR_SLEW_MAX}	Maximum slew rate			10	ms/s	

NOTES:

1. The specified UI is equivalent to a tolerance of 300ppm for each device. Period does not account for SSC induced variations.
2. There is no de-emphasis requirement in this mode. De-emphasis is implementation specific for this mode.
3. Detect voltage transition should be an increase in voltage on the pin looking at the detect signal to avoid a high impedance requirement when an "off" receiver's input goes below output.
4. All transmitters shall be AC coupled. The AC coupling is required either within the media or within the transmitting component itself.

9.5.12 SATA DC Specification

Table 93. SATA TX/RX Signal Group DC Specifications

Symbol	Parameter	Min	Max	Unit	Notes
V _{IMIN_Gen1i}	Minimum Input Voltage for 1.5 Gb/s	325	-	mVdiffp-p	1
V _{IMAX_Gen1i}	Maximum Input Voltage for 1.5 Gb/s	-	600	mVdiffp-p	1
V _{IMIN_Gen2i}	Minimum Input Voltage for 3 Gb/s	275	-	mVdiffp-p	2
V _{IMAX_Gen2i}	Maximum Input Voltage for 3 Gb/s	-	750	mVdiffp-p	2
V _{OMIN_Gen1i,m}	Minimum Output Voltage for 1.5 Gb/s	400	-	mVdiffp-p	3
V _{OMAX_Gen1i,m}	Maximum Output Voltage for 1.5 Gb/s	-	600	mVdiffp-p	3
V _{OMIN_Gen2i,m}	Minimum Output Voltage for 3 Gb/s	400	-	mVdiffp-p	3
V _{OMAX_Gen2i,m}	Maximum Output Voltage for 3 Gb/s	-	700	mVdiffp-p	3

1. Applicable only when SATA port signaling rate is 1.5 Gb/s: SATA V_{diff, rx} is measured at the SATA connector on the receiver side (generally, the motherboard connector), where
SATA mVdiff p-p = 2*|SATA_RXP[x] - SATA_RXN[x]|
2. Applicable only when SATA port signaling rate is 3 Gb/s: SATA V_{diff, rx} is measured at the SATA connector on the receiver side (generally, the motherboard connector), where
SATA mVdiff p-p = 2*|SATA_RXP[x] - SATA_RXN[x]|
3. SATA V_{diff, tx} is measured at the SATA connector on the transmit side (generally, the motherboard connector), where SATA mVdiff p-p = 2*|SATA_TXP[x] - SATA_TXN[x]|

For SATA_GP[x] and SATA_LED#, Please refer to the GPIO Buffer (1.8V) DC Specification in section "GPIO DC Specification".

9.5.13 PCU - SMBUS DC Specification

For SMBUS, Please refer to the GPIO Buffer (1.8V) DC Specification in section "GPIO DC Specification".

9.5.14 PCU - iLB - LPC DC Specification

Table 94. LPC Signal Group DC Specification (LPC_V1P8V3P3_S = 1.8V (ILB_LPC_AD][3:0], ILB_LPC_FRAME#, ILB_LPC_SERIRQ, ILB_LPC_CLKRUN#))

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{IH}	Input High Voltage	1.27	1.8	1.8 +0.1	V	
V _{IL}	Input Low Voltage	-0.1	0	0.58	V	
V _{OH}	Output High Voltage	0.9 x 1.8			V	
V _{OL}	Output Low Voltage			0.1 x 1.8	V	
I _{OH}	Output High Current		1.5		mA	



Table 94. LPC Signal Group DC Specification (LPC_V1P8V3P3_S = 1.8V (ILB_LPC_AD[3:0], ILB_LPC_FRAME#, ILB_LPC_SERIRQ, ILB_LPC_CLKRUN#))

Symbol	Parameter	Min	Typ	Max	Units	Notes
I _{OL}	Output Low Current		-0.5		mA	
I _{LEAK}	Input Leakage Current			30	μA	
C _{IN}	Input Capacitance	1		9	pF	

Table 95. LPC Signal Group DC Specification LPC_V1P8V3P3_S = 3.3V (ILB_LPC_AD[3:0], ILB_LPC_FRAME#, ILB_LPC_CLKRUN#)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{IH}	Input High Voltage	0.5 x 3.3 + 0.7	3.3	3.3 + 0.1	V	1
V _{IL}	Input Low Voltage	-0.1	0	0.5 x 3.3 - 0.7	V	2
V _{OH}	Output High Voltage	0.9 x 3.3			V	3
V _{OL}	Output Low Voltage			0.1 x 3.3	V	3
I _{OH}	Output High Current		1.5		mA	3
I _{OL}	Output Low Current		-0.5		mA	3
I _{LEAK}	Input Leakage Current			30	μA	
C _{IN}	Input Capacitance	1		9	pF	

NOTES:

1. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value. Applies to ILB_LPC_AD[3:0], ILB_LPC_CLKRUN#
2. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value. Applies to ILB_LPC_AD[3:0], ILB_LPC_CLKRUN#
3. V_{OH} is tested with I_{out}=500uA, V_{OL} is tested with I_{out}=1500uA
4. Applies to ILB_LPC_AD[3:0], ILB_LPC_CLKRUN# and ILB_LPC_FRAME#
5. ILB_LPC_SERIRQ is always a 1.8V I/O irrespective of the value of LPC_V1P8V3P3_S.

9.5.15 PCU - SPI (Platform Control Unit) DC Specification

Table 96. SPI Signal Group DC Specification (PCU_SPI_MISO, PCU_SPI_CS[1:0]#, PCU_SPI_MOSI, PCU_SPI_CLK)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	PCU_1P8_G3			V	3
V _{IH}	Input High Voltage	0.5 * V _{REF}		V _{REF} + 0.5	V	2
V _{IL}	Input Low Voltage	-0.5		0.3 * V _{REF}	V	2
V _{OH}	Output High Voltage	0.9 * V _{REF}		1.8V	V	1
V _{OL}	Output Low Voltage			0.1 * V _{REF}	V	1
I _{OH}	Output High Current			1.5	mA	1
I _{OL}	Output Low Current	-0.5			mA	1

**NOTES:**

1. Applies to PCU_SPI_CS[1:0], PCU_SPI_CLK, PCU_SPI_MOSI
2. Applies to PCU_SPI_MISO and PCU_SPI_MOSI
3. The I/O buffer supply voltage is measured at the SoC package pins. The tolerances shown are inclusive of all noise from DC up to 20 MHz. In testing, the voltage rails should be measured with a bandwidth limited oscilloscope that has a rolloff of 3 dB/decade above 20 MHz.


9.5.16 PCU - Power Management/Thermal (PMC) & iLB RTC DC Specification

Table 97. Power Management 1.8V Suspend Well Signal Group DC Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	PCU_1P8_G3			V	
V _{IH}	Input High Voltage	0.8*V _{REF}			V	1
V _{IL}	Input Low Voltage			0.5*V _{REF}	V	2
V _{OH}	Output High Voltage	0.9*V _{REF}		V _{REF}	V	1
V _{OL}	Output Low Voltage			0.1*V _{REF}	V	1

NOTES:

1. The data in this table apply to signals - PMC_ACPRESENT, PMC_BATLOW#, PMC_PLTRST#, PMC_PWRBTN#, PMC_SLP_S4#, PMC_SUS_STAT#, PMC_SUSCLK[3:0], PMC_SUSPWRDNACK
2. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value
3. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value.

**Table 98. PMC_RSTBTN# 1.8V Core Well Signal Group DC Specification**

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	UNCORE_V1P8_S3			V	
V _{IH}	Input High Voltage	0.8* V _{REF}			V	1
V _{IL}	Input Low Voltage			0.5* V _{REF}	V	2

NOTES:

1. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value.
2. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value.

Table 99. Power Management & RTC Well Signal Group DC Specification (PMC_RSMRST#, PMC_CORE_PWROK, ILB_RTC_RST#)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	RTC_VCC				
V _{IH}	Input High Voltage	2.0	-	V _{REF} + 0.5	V	1
V _{IL}	Input Low Voltage	- 0.5	-	0.78	V	2
I _I	Input leakage Current	0.1	1	100	μA	3

- NOTES:**
1. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value.
 2. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value.
 3. I_I (Typical) is specified at 30°C. V_{IL} (Maximum) is specified at T_{jMAX}.

Table 100. iLB RTC Well DC Specification (ILB_RTC_TEST#)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{IH}	Input High Voltage	2.0	-	V _{REF} + 0.5	V	1
V _{IL}	Input Low Voltage	- 0.5	-	0.78	V	1

NOTES:

1. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value.
2. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value.

Table 101. ILB RTC Oscillator Optional DC Specification (ILB_RTC_X1)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{IH}	Input High Voltage	0.65	0.8	1.2	V	1
V _{IL}	Input Low Voltage			0.25	V	1

NOTES:

1. ILB_RTC_X1 DC specification is **only** used for applications with an active external clock source instead of a crystal. When a crystal is used (typical case) between ILB_RTC_X2 and ILB_RTC_X1, this spec is not used.



Table 102. PROCHOT# Signal Group DC Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	CORE_V1P0_S3				
V _{IH}	Input High Voltage	0.8*V _{REF}		V _{REF}	V	1
V _{IL}	Input Low Voltage			0.4*V _{REF}	V	2
V _{OH}	Output High Voltage	0.9*V _{REF}		V _{REF}	V	
V _{OL}	Output Low Voltage			0.1*V _{REF}	V	

NOTES:

1. V_{IH} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical high value
2. V_{IL} is defined as the minimum voltage level at a receiving agent that will be interpreted as a logical low value.

9.5.17 SVID DC Specification


Table 103. SVID Signal Group DC Specification (SVID_DATA, SVID_CLK, SVID_ALERT#)

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	SVID_V1P0_S3				
V _{IH}	Input High Voltage	0.65*V _{REF}			V	1
V _{IL}	Input Low Voltage			0.44*V _{REF}	V	1
V _{OH}	Output High Voltage				V	1
V _{OL}	Output Low Voltage			0.1*V _{REF}	V	4
V _{HYS}	Hysteresis Voltage	0.05			V	
R _{ON}	BUffer on Resistance	10		20	Ω	2
I _L	Leakage Current	-100		100	μA	3
C _{PAD}	Pad Capacitance			4.0	pF	4
V _{PIN}	Pin Capacitance			5.0	pF	

NOTES:

1. SVID_V1P0_S3 refers to instantaneous voltage VSS_SENSE
2. Measured at 0.31 * SVID_V1P0_S3
3. V_{IN} between 0V and SVID_V1P0_S3
4. CPAD includes die capacitance only. No package parasitic included.

Figure 17. Definition of VHYS in Table 169



9.5.18 GPIO DC Specification

GPIO Buffer is used across various interfaces on the SoC such as, GPIOs, I²C, I2S, SPI, SDIO, SVID, UART, JTAG and ULPI

Note: I_{OX}# -> Spec is used for those GPIO which does not have industrial spec. Those GPIO interfaces that have its own industrial spec shouldn't refer to this spec.

Table 104. GPIO 3.3V Core Well Signal Group DC Specification(GPIO_S0_SC[101:0])

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	UNCORE_V3P3_S3				
V _{IH}	Input High Voltage	0.61* V _{REF}		1.24*V _{REF}	V	
V _{IL}	Input Low Voltage	-0.21*V _{REF}		0.24*V _{REF}	V	
V _{OH}	Output High Voltage	0.95* V _{REF}		V _{REF}	V	
V _{OL}	Output Low Voltage	0		0.1* V _{REF}	V	
V _{Hys}	Input Hysteresis	0.1			V	
I _L	Leakage Current			5	μA	
I _{OH} #	Output High Current			3	mA	
I _{OL} #	Output Low Current			-3	mA	
C _{LOAD}	Load Capacitance	2		75	pF	

Table 105. GPIO 3.3V Suspend Well Signal Group DC Specification (GPIO_S5[43:0])

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	PMC_V3P3_G3			V	
V _{IH}	Input High Voltage	0.61* V _{REF}		1.24*V _{REF}	V	
V _{IL}	Input Low Voltage	-0.21*V _{REF}		0.24*V _{REF}	V	
V _{OH}	Output High Voltage	0.95* V _{REF}		V _{REF}	V	
V _{OL}	Output Low Voltage	0		0.1* V _{REF}	V	



Table 105. GPIO 3.3V Suspend Well Signal Group DC Specification (GPIO_S5[43:0])


Symbol	Parameter	Min	Typ	Max	Unit s	Notes
V _{Hys}	Input Hysteresis	0.1			V	
I _L	Leakage Current			5	μA	
I _{OH} #	Output High Current			3	mA	
I _{OL} #	Output Low Current			-3	mA	
C _{LOAD}	Load Capacitance	2		75	pF	

Table 106. GPIO 1.8V Core Well Signal Group DC Specification (GPIO_S0_SC[101:0])

Symbol	Parameter	Min	Typ	Max	Unit s	Notes
V _{REF}	I/O Voltage	UNCORE_V1P8_S3				
V _{IH}	Input High Voltage	0.65*V _{REF}		1.24*V _{REF}	V	
V _{IL}	Input Low Voltage	-0.21*V _{REF}		0.35 * V _{REF}	V	
V _{OH}	Output High Voltage	V _{REF} -0.45		V _{REF}	V	
V _{OL}	Output Low Voltage	0		0.45	V	
V _{Hys}	Input Hysteresis	0.1			V	
I _L	Leakage Current			5	μA	
I _{OH} #	Output High Current			3	mA	
I _{OL} #	Output Low Current			-3	mA	
C _{LOAD}	Load Capacitance	2		75	pF	

Table 107. GPIO 1.8V Suspend Well Signal Group DC Specification (GPIO_S5[43:0])

Symbol	Parameter	Min	Typ	Max	Unit s	Notes
V _{REF}	I/O Voltage	PMC_V1P8_G3			V	
V _{IH}	Input High Voltage	0.65*V _{REF}		1.24*V _{REF}	V	
V _{IL}	Input Low Voltage	-0.21*V _{REF}		0.35*V _{REF}	V	
V _{OH}	Output High Voltage	V _{REF} - 0.45		V _{REF}	V	
V _{OL}	Output Low Voltage	0		0.45	V	
V _{Hys}	Input Hysteresis	0.1			V	
I _L	Leakage Current			5	μA	
I _{OH} #	Output High Current			3	mA	
I _{OL} #	Output Low Current			-3	mA	
C _{LOAD}	Load Capacitance	2		75	pF	



9.5.19 SIO - I²C DC Specification

Table 108. I²C Signal Electrical Specifications

Symbol	Parameter	Min	Typ	Max	Units	Notes
V _{REF}	I/O Voltage	UNCORE_V1P8_S3			V	
V _{IH}	Input High Voltage	0.7 * V _{REF}		1.24 * V _{REF}	V	
V _{IL}	Input Low Voltage	0.21 * V _{REF}		0.3 * V _{REF}	V	
V _{OL}	Output Low Voltage	0		0.2 * V _{REF}	V	
V _{Hys}	Input Hysteresis	0.1			V	
C _{PIN}	Pin Capacitance	2		5	pF	

9.5.20 SIO - UART DC Specification

Refer to the GPIO Buffer (1.8V) DC Specification, mentioned [Section 106](#), “GPIO 1.8V Core Well Signal Group DC Specification (GPIO_S0_SC[101:0])” on page 152

9.5.21 I²S (Audio) DC Specification

Refer to the GPIO Buffer (1.8V) DC Specification, mentioned [Section 107](#), “GPIO 1.8V Suspend Well Signal Group DC Specification (GPIO_S5[43:0])” on page 152

9.6 AC Specifications

The timings specified in this section are defined at the SoC pads. Therefore, proper simulation of the signals is the only means to verify proper timing and signal quality.

See [Chapter 2](#), “Physical Interfaces” for signal definitions and [Chapter 10](#), “Ballout and Package Information” for the ball map. Generic timing diagrams can be found in “General AC Timing Diagrams”.

The timings specified in this section should be used in conjunction with the SoC signal integrity models provided by Intel.

See the following DC Specifications in this section:

- “Integrated Clock 25 MHz Crystal AC Specification”
- “Platform Clocks AC Specification”
- “SVID AC Specification”
- “DDR3L Memory Controller AC Specification”
- “Display AC Specifications”
- “MIPI-Camera Serial Interface (CSI) AC Specification”
- “SCC - SD Card AC Specification”
- “SSC - SDIO AC specification”



- "SCC - eMMC 4.5 AC Specification"
- "SATA AC Specification"
- "USB 3.0 AC Specification"
- "ULPI USB 2.0 Device AC Specification"
- "Intel® HD Audio AC Specification"
- "I²S (Audio) AC Specification"
- "PCI Express* AC Specification"
- "PCU - PMC - Suspended Clock AC Specification"
- "1. SUSCLK duty cycle can range from 30% minimum to 70% maximum."
- "PCU - SPI NOR AC Specification"
- "PCU - ILB - LPC AC Specification"
- "SIO - I²C AC Specifications"
- "SIO - UART AC Specification"
- "JTAG AC Specification"

Note: Care should be taken to read all notes associated with a particular timing parameter.

9.6.1 Integrated Clock 25 MHz Crystal AC Specification

See "Crystal Specifications" for crystal selection.

9.6.2 Generic Clock Jitter AC Specification


Applies to the following clocks unless overridden below: SIO_I2C[0:6]_CLK, PMC+PLT_CLK[0:6], SIO_SPI_CLK, LPE_I2S[0:2]_CLK, TAP_CLK, PCU_SPI_CLK, ILB_LPC_CLK[0:1], SD3_CLK, SD2_CLK, MMC1_CLK, HDA_CLK, SVID_CLK, DDI[0:1]_DDCCLK, VGA_DDCLK.

Table 109. Generic Clock Jitter AC Specification

Symbol	Parameter	Min.	Typ	Max.	Unit	Notes
T _{RISE/FALL}	Minimum and Maximum Rise/Fall Time	1.5		20	ns	1, 3
T _{DC}	Duty Cycle	45		55	%	2
T _{PEAKJIT}	Peak Jitter (cycle to cycle)			300	ps	2
T _{PERJIT}	Period Jitter (peak to peak)			500	ps	4
T _{TIE}	Time Interval Error (peak to peak)			400	ps	5
T _{LONG}	Long Term Accuracy	-100		100	ps	

NOTES:

1. Edge Rate is measured from 10%-90% of supply voltage.
2. Cycle to cycle jitter measure for 100K samples.



3. Based on trace length of 25–200 mm, total maximum far end capacitance of 5 pF, EDS of 10 pF and board impedance of 30–75 Ω .
4. Period jitter value is measured by adjusting an oscilloscope to display a little more than one complete clock cycle with the display set to infinite persistence. Scope trigger is set on the first edge, and the period jitter is captured by measuring spread/peak-peak value of the second edge. 100K samples.
5. The TIE is estimated by measuring how far each active edge of the clock varies from its ideal position. 100K samples.

9.6.3 Platform Clocks AC Specification

Table 110. 25 MHz Platform Clock AC Specification

Symbol	Parameter	Min.	Typ	Max.	Unit	Notes
F _{PLT}	Frequency		25		MHz	
T _{DC}	Duty Cycle	45		55	%	
T _{RISE/FALL}	Minimum and Maximum Rise/Fall Time	5		20	ns	
V _{SWING}	Voltage Swing		1.8		V	
T _{PEAKJIT}	Peak Jitter (c-c)	-300		300	ps	
T _{PERJIT}	Period Jitter			500	ps	

9.6.4 SVID AC Specification


Table 111. SVID AC Specification

Symbol	Parameter	Min.	Max.	Unit	Figure	Notes
F _{SVID}	SVID_CLK Frequency		25	MHz	18	
T _{DC}	SVID_CLK Duty Cycle	45	55	%		
T _{S_D}	SVID_DATA Input Setup Time	-2		ns	18	
T _{H_D}	SVID_DATA Input Hold Time	9		ns	18	
T _{CO_D}	Rising edge SVID_CLK to SVID_DATA Output	0	5	ns	18	
T _{RISE/FALL}	Minimum and Maximum Rise/Fall Time	0	5	ns		1, 2

NOTES:

1. Based on trace length of 0.2–4 inches, total maximum far end capacitance of 5 pF and board impedance of 25–75 Ω .
2. Measured from 30–70%

Figure 18. SVID Timing Diagram



9.6.5 DDR3L Memory Controller AC Specification

Note: The contents of this section are only valid for DRAM_VDD_S4 = 1.35V

Table 112. DDR3L Interface Timing Specification (Sheet 1 of 3)

Symbol	Parameter	Min	Max	Unit	Figure	Notes
DDR3L Electrical Characteristic and AC timings at 1066 MT/s						
T_{SLR_D}	DQ, DQSP, DQSN Input Slew Rate	3	5.5	V/ns		
System Memory Clock Timings						
$T_{CK(AVG)}$	Average CK Period		1.875	ns		
T_{CH}	Average CK High Time	0.45		tCKAV G		
T_{CL}	Average CK Low Time	0.45		tCKAV G		
T_{SKEW}	Skew between any System Memory Differential Clock Pair (CKP/CKN)		30	ps		
System Memory Command Signal Timings						
T_{CMD} (tCMDVB+tCMDVA)	Total CMD Buffer window available for command buffers (RAS#, CAS#, WE#, BS[2:0], MA)	1380		ps		1
System Memory Control Signal Timings						




Table 112. DDR3L Interface Timing Specification (Sheet 2 of 3)

Symbol	Parameter	Min	Max	Unit	Figure	Notes
T_{CTL} ($t_{CTLVB} + t_{CTLVA}$)	Total Control buffer Window available for Control buffers (CS#, CKE)	1400		ps		2
System Memory Data and Strobe Signal Timings						
$T_{DVB} + T_{VDA}$	Data, DQ and DM timing window available at the interface output for write commands. tDVB is data available before strobe and tDVA is data available after corresponding slope.	645		ps		3
$T_{SU} + T_{HD}$	Data, DQ Input Setup Plus Hold Time requirement for successful Read operation. These Setup and Hold numbers are measured w.r.t. corresponding strobe or Falling Edge	310		ps		4
T_{DQSS}	Strobe to rising clock edge during write.	-120		120	ps	
T_{WPRE}	DQSP/N Preamble duration (one dummy cycle)	0.9		tCKAV G		
T_{WPST}	DQSP/N Postamble Duration	0.4		tCKAV G		
DDR3L Electrical Characteristic and AC timings at 1333 MT/s. DRAM_VDD_S4 = 1.35 V						
T_{SLR_D}	DQ, DQSP, DQSN Input Slew Rate	3	5.5	V/ns		
System Memory Clock Timings						
$T_{CK(AVG)}$	Average CK Period		1.5	ns		
T_{CH}	Average CK High Time	0.45		tCKAV G		
T_{CL}	Average CK Low Time	0.45		tCKAV G		
T_{SKEW}	Skew between any System Memory Differential Clock Pair (CKP/CKN)		30	ps		
System Memory Command Signal Timings						
T_{CMD} ($t_{CMDVB} + t_{CMDVA}$)	Total CMD Buffer window available for command buffers (RAS#, CAS#, WE#, BS[2:0], MA)	1075		ps		1
System Memory Control Signal Timings						
T_{CTL} ($t_{CTLVB} + t_{CTLVA}$)	Total Control buffer Window available for Control buffers (CS#, CKE)	1125		ps		2
System Memory Data and Strobe Signal Timings						

Table 112. DDR3L Interface Timing Specification (Sheet 3 of 3)

Symbol	Parameter	Min	Max	Unit	Figure	Notes
$T_{DVB} + T_{VDA}$	Data, DQ and DM timing window available at the interface output for write commands. tDVB is data available before strobe and tDVA is data available after corresponding slope.	495		ps		3
$T_{SU} + T_{HD}$	Data, DQ Input Setup Plus Hold Time requirement for successful Read operation. These Setup and Hold numbers are measured w.r.t. corresponding strobe or Falling Edge	255		ps		4
T_{DQSS}		-120		120	ps	
T_{WPRE}	DQSP/N Preamble duration (one dummy cycle)	0.9		tCKAV G		
T_{WPST}	DQSP/N Postamble Duration	0.4		tCKAV G		

NOTES:

1. The CMD time is measured w.r.t. differential crossing of DRAM_CKP and DRAM_CKN. The tCMDVB and tCMDVA will be adjusted for proper CMD Setup and Hold time requirement at DRAM. The command timing assumes CMD-1N Mode.
2. The CTL time is measured w.r.t. differential crossing of DRAM_CKP and DRAM_CKN. The tCTLVB and tCTLVA will be adjusted for proper CTL Setup and Hold time requirement at DRAM.
3. The accurate strobe placement using write training algorithm will be performed which will guarantee the required Data setup/hold time w.r.t. strobe differential crossing at the DRAM input.
4. The Read training algorithm will center the DQS internally inside DRAM interface in order to have equal tSU and tHD timings.
5. All the timing windows are measured at 50% of the respective DRAM signal swing.

Figure 19. DDR3L DQ Setup/Hold Relationship to/from DQSP/DQSN (Read Operation)








Figure 20. DDR3L DQ and DM Valid before and after DQSP/DQSN (Write Operation)

Figure 21. DDR3L Write Pre-ample Duration

Figure 22. DDR3L Write Post-ample Duration

Figure 23. DDR3L Command Signals Valid before and after CK Rising Edge


Figure 24. DDR3L CKE Valid before and after CK Rising Edge




Figure 25. DDR3L CS# Valid before and after CK Rising Edge




Figure 26. DDR3L ODT Valid before CK Rising Edge




Figure 27. DDR3L Clock Cycle Time





Figure 28. DDR3L Skew between System Memory Differential Clock Pairs (CKP/CKN)


NOTE: x represents one differential clock pair, and y represents another differential clock pair within same channel.




Figure 29. DDR3L CK High Time

Figure 30. DDR3L CK Low Time

Figure 31. DDR3L DQS Falling Edge Output Access Time to CK Rising Edge


Figure 32. DDR3L DQS Falling Edge Output Access Time From CK Rising Edge





Figure 33. DDR3L CK Rising Edge Output Access Time to the 1st DQS Rising Edge



9.6.6 Display AC Specifications

9.6.6.1 DDI Main Transmitter AC specification

Table 113. DDI Main Transmitter AC specification (Sheet 1 of 2)

Symbol	Parameter	Min	Typ	Max	Units	Notes
f_{HBR}	Frequency for High Bit Rate	2.68569	2.7	2.70081	Gbps	1
f_{RBR}	Frequency for Reduced Bit Rate	1.61141	1.62	1.620048	Gbps	1
UI_High_Rate	Unit Interval for high bit rate (2.7 Gbps / lane)		370		ps	1
UI_Low_Rate	Unit Interval for high bit rate (1.62 Gbps / lane)		617		ps	1
Down_Spread_Amplitude	Link clock down Spreading	0		0.5	%	2
Down_Spread_Frequency	Link Clock down Spreading Frequency	30		33	kHz	3





Table 113. DDI Main Transmitter AC specification (Sheet 2 of 2)

Symbol	Parameter	Min	Typ	Max	Units	Notes
$T_{TX-EYE_CHIP_High_Rate}$	Minimum TX Eye Width at Tx package pins	0.72			UI	4
$T_{TX-EYE-MEDIAN-to-MAX-JITTER_CHIP_High_Rate}$	Maximum time between the jitter median and maximum deviation from the median at Tx package pins			0.147	UI	4
$T_{TX-EYE_CHIP_Low_Rate}$	Minimum TX Eye Width at Tx package pins	0.82			UI	5
$T_{TX-EYE-MEDIAN-to-MAX-JITTER_CHIP_Low_Rate}$	Maximum time between the jitter median and maximum deviation from the median at Tx package pins			0.09	UI	5
$T_{TX-RISE_CHIP}$, $T_{TX-FALL_CHIP}$	D+/D- TX Output Rise/Fall Time at Tx package pins	50		130	ps	6
ITX-SHORT	TX Short Circuit Current Limit			50	mA	7
$L_{TX-SKEWINTER_PAIR}$	Lane-to-Lane Output Skew at Tx package pins			2	UI	
$L_{TX-SKEWINTRA_PAIR}$	Lane Intra-pair Output Skew at Tx package pins			20	ps	
$T_{TX-RISE_FALL_MISMATCH_CHIPDIFF}$	Lane Intra-pair Rise-fall Time Mismatch at Tx package pins.			5	%	8
$F_{TX-REJECTION-BW}$	Clock Jitter Rejection Bandwidth			4	MHz	9
$V_{TX-AC-CM}$	TX AC Common Mode Voltage			20	mV	2
C_{TX}	AC Coupling Capacitor	75		200	nF	11
T_{RISE}/T_{FALL}	Rise time/ Fall time (20%-80%)	75		-	ps	
$V_{UNDERSHOOT}$	Undershoot, max			0.25 of full differential amplitude		
$L_{TX-SKEWINTER_PAIR}$	Intra-Pair skew at source connector			0.15 UI	ps	
$L_{TX-SKEWINTRA_PAIR}$	Intra-Pair skew at source connector			1.212	ns	12
	Clock duty cycle, min/average/max	40	50	60	%	
	TMDs differential Clock Jitter			0.25	UI	

NOTES:

- Frequency High limit = +300ppm; Low limit = -5300ppm
- Range: 0% ~ 0.5% when downspread enabled
- Range: 30 kHz ~ 33 kHz when downspread enabled.
- For High Bit Rate.
- For Reduced Bit Rate.
- At 20 to 80
- Total drive current of the transmitter when it is shorted to its ground.
- Informative. D+ rise to D- fall mismatch and D+ fall to D- rise mismatch.



9. Informative. Transmitter jitter must be measured at source connector pins using a signal analyzer that has a 2nd order PLL with tracking bandwidth of 20MHz (for D10.2 pattern) and damping factor of 1.428.
10. Measured at 1.62 GHz and 2.7 GHz (if supported), within the frequency tolerance range. Time-domain measurement using a spectrum analyzer.
11. All DisplayPort Main Link lanes as well as AUX CH must be AC coupled. AC coupling capacitors must be placed on the transmitter side. Placement of AC coupling capacitors on the receiver side is optional.
12. 0.20* Tcharacter @165MHz

Table 114. DDI AUX Channel AC Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes ¹
UI	AUX Unit Interval	0.4	0.5	0.6	μs	1
T _{AUX-BUS-PARK}	AUX CH bus park time	10			ns	2
T _{CYCLE-to-CYCLE} Jitter	Maximum allowable UI variation within a single transaction at connector pins of a transmitting Device			0.08	UI	3
	Maximum allowable variation for adjacent bit times within a single transaction at connector pins of a transmitting Device			0.04	UI	4
I _{AUX_SHORT}	AUX Short Circuit Current Limit			90	mA	5
C _{AUX}	AC Coupling Capacitor	75		200	nF	6

NOTES:

1. Results in the bit rate of 1Mbps including the overhead of ManchesterII coding.
2. Period after the AUX CH STOP condition for which the bus is parked
3. Equal to 48 ns maximum. The transmitting Device is a Source Device for a Request transaction and a Sink Device for a Reply Transaction
4. Equal to 24 ns maximum. The transmitting Device is a Source Device for a Request transaction and a Sink Device for a Reply Transaction.
5. Total drive current of the transmitter when it is shorted to its ground.
6. The AUX CH AC-coupling capacitor placed on both the DP upstream and downstream devices.

9.6.6.2 Analog VGA Display AC Specification

The VGA DAC (digital-to-analog converter) consists of three identical 8-bit DACs to provide red, green, and blue color components. Each DAC can output a current from 0 to 255 units of current, where one unit of current (LSB) is defined based on the VESA video signal standard.

Table 115. R,G,B / VGA DAC Display AC Specification (Sheet 1 of 2)

Symbol	Parameter	Min	Nom	Max	Unit	Notes
Pixel Clock Frequency = 300 MHz						
T _{RISE}	R,G,B Video Rise TIme	0.33		1.67	ns	1,2,8 (10-90% of "black"-to-"white" video transition)
T _{FALL}	R,G,B Video Fall TIme	0.33		1.67	ns	1,3,8 (90-10% of "black"-to-"white" video transition)
T _{SETTLING}	Settling time		1.0		ns	1,4,8
VO	Video Channel-to-Channel output skew		0.833		ns	1,5,8
	Overshoot/Undershoot	-0.084		+0.084	V	1,6,8 (0.7V full-scale voltage step)




Table 115. R,G,B / VGA DAC Display AC Specification (Sheet 2 of 2)

Symbol	Parameter	Min	Nom	Max	Unit	Notes
	Noise Injection Ratio		2.5		%	
Pixel Clock Frequency = 350 MHz						
T _{RISE}	R,G,B Video Rise Time	0.286		1.43	ns	1,2,8 (10-90% of "black"-to-"white" video transition)
T _{FALL}	R,G,B Video Fall Time	0.286		1.43	ns	1,3,8 (90-10% of "black"-to-"white" video transition)
T _{SETTLING}	Settling time		0.857		ns	1,4,8
VO	Video Channel-to-Channel output skew		0.714		ns	1,5,8
	Overshoot/Undershoot	-0.084		+0.084	V	1,6,8 (0.7V full-scale voltage step)
	Noise Injection Ratio		2.5		%	

NOTES:

1. Measured at each R,G,B termination according to the VESA Test Procedure - Evaluation of Analog Display Graphics Subsystems Proposal (Version 1, Draft 4, December 1, 2000).
2. R,G,B Max Video Rise/Fall Time: 50% of minimum pixel clock period
3. R,G,B Min Video Rise./Fall Time: 10% of minimum pixel clock period
4. Max settling time: 30% of minimum pixel clock period
5. Video channel-to-channel output skew: 25% of minimum pixel clock period
6. Overshoot/Undershoot: $\pm 12\%$ of "black"-to-"white" video step function
7. Noise Injection Ratio: 2.5% of maximum luminance voltage (dc to max pixel clock frequency)
8. R,G,B AC parameters are strongly dependent on the board design & implementation: actual performance may differ from values noted above depending on board implementation.

Table 116. VGA_HSYNC and VGA_VSYNC AC Specification

Symbol	Parameter	Min	Max	Units	Notes ¹
T _F	Fall Time	--	80% of minimum pixel clock period	ns	
T _R	Rise Time	--	80% of minimum pixel clock period	ns	
--	Overshoot/Undershoot	--	30% of high level signal voltage range	mA	1
--	Jitter (measured between Hsync pulses)	--	One half of the difference between max and min interval <15% of the pixel clock, DC to max.	V	2

NOTES:

1. No signal non-monotonicity / excursions allowed in the 0.5 to 2.4V range
2. Measured over 100,000 intervals. Horizontal refresh rate at all image format, worse-case screen patterns.


Table 117. VGA_DDCDATA, and VGA_DDCCLK Timing Specification

Symbol	Parameter	Standard mode 100kbits/s		Units	Figures
		Min	Max		
f_{SCL}	SCL Clock Frequency	0	100	kHz	34
t_{LOW}	Low Period of SCL Clock	4.7	--	μs	
t_{HIGH}	High Period of SCL Clock	4	--	μs	
t_R	Rise Time ¹ of Both SDA and SCL Signals	--	1000	ns	
t_F	Fall Time ¹ of Both SDA and SCL Signals	--	300	ns	
$t_{HD:DAT}$	Data Hold Time ³	0	--	μs	
$t_{SU:DAT}$	Data Setup Time	250	--	ns	

NOTES:

1. Measurement point for rise and fall time: $V_{IL}(\min) - V_{IL}(\max)$
2. $t_{HD:DAT}$ is the data hold time that is measured from the falling edge of SCL, applies to data in transmission and the acknowledge.

Figure 34. VGA_DDCDATA, and VGA_DDCCLK Timing Diagram



9.6.7 MIPI-Camera Serial Interface (CSI) AC Specification

Based on version 2 of the MIPI-CSI specification.

Table 118. MIPI-CSI-2 Receiver Characteristics (Sheet 1 of 2)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Notes
MIPI HS-Receiver Mode						
$\Delta V_{CMRX}(HF)$	Common-mode interference above 450 MHz	–	–	100	mV	2, 9
$\Delta V_{CMTX}(LF)$	Common-mode interference between 50–450 MHz	–50	–	50	mV	1, 4
C_{CM}	Common-mode termination	–	–	60	pF	3

Table 118. MIPI-CSI-2 Receiver Characteristics (Sheet 2 of 2)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Notes
S_{CDRX}	differential to common-mode	–	–	–26	dB	From 0 to f_{MAX} (1.33GHz)
MIPI LP-Receiver Mode						
e_{Spike}	Input pulse rejection	–	–	300	V*ps	5, 6, 7
T_{MIN-RX}	Minimum pulse width response	20	–	–	ns	8
V_{INT}	Peak interference amplitude	–	–	200	mV	
f_{INT}	Interference frequency	450	–	–	MHz	

NOTES:

- Excluding static ground shift of 50 mV.
- $\Delta V_{CMRX(HF)}$ is the peak amplitude of a sine wave superimposed on the receiver inputs.
- For higher bit rates a 14 pF capacitor is needed to meet the common-mode return loss specification.
- Voltage difference compared to the DC average common-mode potential.
- Time-voltage integration of a spike above V_{IL} when in the LP-0 state or below V_{IH} when in the LP-1 state.
- An impulse spike less than this will not change the receiver state.
- In addition to the required glitch rejection, designers shall ensure rejection of known RF-interference.
- An input pulse greater than this will toggle the output
- Improves on DPHY specification, which requires 100 mV maximum.

Figure 35. Input Glitch Rejection of Low-Power Receivers




Table 119. MIPI-CSI-2 Clock Signal Specification

Symbol	Clock Parameter	Min.	Typ.	Max.	Unit	Notes
UI_{INST}	UI Instantaneous (In 1 or 2 or 3 or 4 Lane configuration)	1 (1Gbps/ 500Mhz)		2.77 (163 Mbps/ 80Mhz)	ns	1

NOTE: ¹The minimum UI shall not be violated for any single bit period, that is, any DDR half cycle within a data burst.

Figure 36. MIPI-CSI-2 Clock Definition





Table 120. MIPI CSI 2 Data Clock Timing Specifications


Symbol	Parameter	Min.	Typ.	Max.	Units	Notes
TSETUP[RX]	Data to Clock Setup Time [receiver]	0.15	–	–	UI_{INST}	1, 2
THOLD[RX]	Clock to Data Hold Time [receiver]	0.15	–	–	UI_{INST}	1, 2

NOTES:

1. Total silicon and package delay budget of $0.3 \cdot UI_{INST}$
2. Total setup and hold window for receiver of $0.3 \cdot UI_{INST}$

Figure 37. MIPI-CSI-2 Data to Clock Timing Definitions





9.6.8 SCC - SD Card AC Specification

Table 121. SD Card AC Specification

Symbol	Parameter	Min.	Max.	Unit	Figure	Notes
$T_{wc}(DDR50)$	CLK cycle time for DDR50 Mode	19	–	ns	41	
$T_{wc}(SDR25)$	CLK cycle time for SDR25 Mode	19	–	ns	42	
$T_{wc}(SDR12)$	CLK cycle time for SDR12 Mode	39	–	ns	45	
$T_{ODLY}(DDR50)$	SD_CLK Transitioning Edge to SDIO_D	2	6	ns	41	
$T_{ODLY}(SDR25)$	SD_CLK Rising Edge to SDIO_D	2	12	ns	42	
$T_{ODLY}(SDR12)$	SD_CLK Falling Edge to SDIO_D	0	12	ns	45	
$T_{SU_SOC}(DDR)$	SoC setup time (data valid before clock launched)	3	–	ns	41 (For DDR50 Mode)	
$T_{SU_SOC}(SDR)$	SoC setup time (data valid before clock launched)	5	–	ns	40 (For SDR12/25 Mode)	
$T_{HD_SOC}(DDR)$	SoC hold time (data valid after clock launched)	2	–	ns	41 (For DDR50 Mode)	
$T_{HD_SOC}(SDR)$	SoC hold time (data valid after clock launched)	2	–	ns	40 (For SDR12/25 Mode)	
$T_{RISE\ CLK}/T_{FALL\ CLK}(1.8V)$	Clock Rise and Fall Time (1.8V operation)	1	4	ns		1, 2, 3, 4
$T_{RISE\ CLK}/T_{FALL\ CLK}(3.3V)$	Clock Rise and Fall Time (3.3V operation)	1	4	ns		1, 2, 3, 4

1. Based on trace length of 0.25"–4", 2–5 pF Far End Load for Port 0 AND 2–10 pF Far End Load (for Port 1 and Board impedance of 25–75 Ω).
2. Minimum time deviates from SDIO Specification 2.0, minimum time is not defined in specification.
3. Measured from 0.58–1.27V.

4. Takes into consideration EMI filter of 10 pF - 40 Ω -10 pF.

Figure 38. SD Card Timing Diagram (DDR50)




Figure 39. SD card Output Timing Diagram (SDR25)





Figure 40. SD Card Input Timing Diagram (SDR12)**9.6.8.1 SD Card Default Speed Specification****Table 122. SD Card Default Speed AC Specification**

Symbol	Parameter	Min.	Max.	Unit	Figure	Notes
f_{PP}	Clock Frequency Data transfer mode	0	25	MHz		
f_{OD}	Clock Frequency identification mode	0	400	kHz		1
t_{FL}	Clock low time	10	-	ns	Figure 54, 55	
t_{WH}	Clock High time	10	-	ns	Figure 54, 55	
t_{TLH}	Clock Rise time	-	10	ns	Figure 54, 55	
t_{THL}	Clock Fall time	-	10	ns	Figure 54, 55	
	Clock Overshoot	-	4.5	V		
	Clock undershoot	-1.5	-	V		
Outputs CMD,DAT (referenced to CLK)						
t_{ODLY}	Output Delay time during Data Transfer Mode	0	14	ns	Figure 55	
t_{ODLY}	Output Delay time during Identification Mode	0	50	ns	Figure 55	
Inputs CMD, DAT (referenced to CLK)						
t_{ISU}	Input Set-up time	5	-	ns	Figure 54	
t_{IH}	Input hold time	5	-	ns	Figure 54	

NOTES:

- 0 Hz means to stop the clock. The given minimum frequency range is for cases where continuous clock is required.

Figure 41. SD Card Input Timing Diagram (Default)





Figure 42. SD card Output Timing Diagram (Default)



9.6.8.2 SD Card High Speed Specification

Table 123. SD Card High Speed AC Specification (Sheet 1 of 2)

Symbol	Parameter	Min.	Max.	Unit	Figure	Notes
f_{PP}	Clock Frequency Data transfer mode	0	50	MHz		
t_{FL}	Clock low time	7	-	ns	Figure 56, 57	
t_{WH}	Clock High time	7	-	ns	Figure 56, 57	
t_{TLH}	Clock Rise time	-	3	ns	Figure 56, 57	
t_{THL}	Clock Fall time	-	3	ns	Figure 56, 57	
	Clock Overshoot	-	4.5	V		

Table 123. SD Card High Speed AC Specification (Sheet 2 of 2)

Symbol	Parameter	Min.	Max.	Unit	Figure	Notes
	Clock undershoot	-1.5	-	V		
Outputs CMD, DAT (referenced to CLK)						
t_{ODLY}	Output Delay time during Data Transfer Mode	-	14	ns	Figure 57	
t_{ODLY}	Output Delay time during Identification Mode	2.5	-	ns	Figure 57	
Inputs CMD, DAT (referenced to CLK)						
t_{ISU}	Input Set-up time	6	-	ns	Figure 56	
t_{IH}	Input hold time	2	-	ns	Figure 56	
C_L	Total Capacitance for each line	-	40	pF		

NOTES:

- 0 Hz means to stop the clock. The given minimum frequency range is for cases where continuous clock is required.



Figure 43. SD Card Input Timing Diagram (High Speed)

Figure 44. SD card Output Timing Diagram (High Speed)



9.6.9 SSC - SDIO AC specification

Table 124. SDIO AC Specification

Symbol	Parameter	Min.	Max.	Unit	Figure	Notes
$T_{wc}(DDR50)$	CLK cycle time for DDR50 Mode	19	–	ns	45	
$T_{wc}(SDR25)$	CLK cycle time for SDR25 Mode	19	–	ns	46	
$T_{wc}(SDR12)$	CLK cycle time for SDR12 Mode	39	–	ns	47	
$T_{ODLY}(DDR50)$	SD_CLK Transitioning Edge to SDIO_D	1.5	6	ns	45	
$T_{ODLY}(SDR25)$	SD_CLK Rising Edge to SDIO_D	3	11.9	ns	46	
$T_{ODLY}(SDR12)$	SD_CLK Falling Edge to SDIO_D	0	11.9	ns	47	
$T_{SU_SOC}(DDR)$	SoC setup time (data valid before clock launched)	1	–	ns	45 (For DDR50 Mode)	
$T_{SU_SOC}(SDR)$	SoC setup time (data valid before clock launched)	4	–	ns	48 (For SDR12/25 Mode)	
$T_{HD_SOC}(DDR)$	SoC hold time (data valid after clock launched)	2	–	ns	45 (For DDR50 Mode)	

Table 124. SDIO AC Specification

Symbol	Parameter	Min.	Max.	Unit	Figure	Notes
T_{HD_SOC} (SDR)	SoC hold time (data valid after clock launched)	2	–	ns	48 (For SDR12/25 Mode)	
$T_{RISE\ CLK}/$ $T_{FALL\ CLK}$ (1.8V)	Clock Rise and Fall Time (1.8V operation)	1	3	ns		1, 2, 3, 4
$T_{RISE\ CLK}/$ $T_{FALL\ CLK}$ (3.3V)	Clock Rise and Fall Time (3.3V operation)	1	3	ns		1, 2, 3, 4

NOTES:

1. Based on trace length of 0.25"–4", 2–5 pF Far End Load for Port 0 AND 2–10 pF Far End Load (for Port 1 and Board impedance of 25–75 Ω).
2. Minimum time deviates from SDIO Specification 2.0, minimum time is not defined in specification.
3. Measured from 0.58–1.27V.
4. Takes into consideration EMI filter of 10 pF - 40 Ω -10 pF.


Figure 45. SDIO Timing Diagram (DDR50)

Figure 46. SDIO Output Timing Diagram (SDR25)




Figure 47. SDIO Output Timing Diagram (SDR12)





Figure 48. SDIO Input Timing Diagram (SDR12/25)

9.6.10 SCC - eMMC 4.5 AC Specification

9.6.10.1 HS/DDR Mode AC Characteristics

Table 125. eMMC 4.5 AC Characteristics (Sheet 1 of 2)

Symbol	Parameter	Min.	Max.	Units	Figures	Notes
F_{pp}	Clock Frequency Data transfer Mode		200	MHZ		
$T_{wc(HS/DDR)}$	CLK Cycle Time (High Speed Mode and DDR Modes)	20	–	ns	49	
T_{DC}	CLK Duty Cycle	40	55	%		
$T_{ODLY(HS)}$	EMMC_CLK Rising Edge to EMMC_D (High Speed Mode)	–	13.7	ns	49	
$T_{ODLY(DDR)}$	EMMC_CLK Rising Edge to EMMC_D (DDR Mode)	1.5	7	ns	50	
$T_{OH(HS)}$	Output hold time (HS mode)	2.5	–	ns		
$T_{SU(HS)}$	EMMC_D Input Setup Time to EMMC_CLK Rising Edge (data read - HS mode)	1.5	–	ns	50	
$T_{H(HS)}$	EMMC_D Input Hold Time to EMMC_CLK Rising Edge (data read - HS mode)	3	–	ns	51	
$T_{SU(DDR)}$	EMMC_D Input Setup Time to EMMC_CLK Rising Edge (data read - DDR Mode)	2.5	–	ns	50	
$T_{H(DDR)}$	EMMC_D Input Setup Time to EMMC_CLK Rising Edge (data read-DDR Mode)	2.5	–	ns	50	
$T_{RISE(HS)}$	Rise Time (Output - HS mode)	–	3	ns		1, 2, 3
$T_{FALL(HS)}$	Fall Time (Output -HS mode)	–	3	ns		1, 2, 3

Table 125. eMMC 4.5 AC Characteristics (Sheet 2 of 2)

Symbol	Parameter	Min.	Max.	Units	Figures	Notes
$T_{RISE(DDR)}$	Rise Time (Output - DDR mode)	-	2	ns		1, 2, 3
$T_{FALL(DDR)}$	Fall Time (Output - DDR mode)	-	2	ns		1, 2, 3
T_{RSTW}	eMMC_RST# Pulse Width	1	-	μ s		
T_{RSTCA}	eMMC_RST# to Command Time	200	-	μ s		4
T_{RSTH}	eMMC_RST# High Period (interval time)	1	-	μ s		

NOTES:

1. Based on trace length of 0.25 – 2", 2–12 pF Far End Load and Board impedance of 25–75 Ω .
2. Measured from 35–65%.
3. Minimum time deviates from e-MMC* Specification 4.41, minimum time is not defined in the specification.
4. Seventy-four (74) clock cycles are required before issuing CMD1 or CMD0 with argument 0xFFFFFFFF.

Figure 49. eMMC* Output Timing Diagram (High Speed Mode)




Figure 50. eMMC* DDR Timings





Figure 51. eMMC* Input Timing Diagram (High Speed Mode)**9.6.10.2 HS200 Mode AC Characteristics****Table 126. eMMC 4.5 AC Characteristics**

Symbol	Parameter	Min.	Max.	Units	Figures	Notes
F_{pp}	Clock Frequency Data transfer Mode		200	MHZ		
T_{wc}	CLK Cycle Time	5	–	ns		
T_{DC}	CLK Duty Cycle	30	70	%		
T_{VW}	Output Valid Data Window	3.24	–	ns	70	
T_{ISU}	Input Setup Time	1.40	–	ns	70	
T_{IH}	Input Hold Time	0.8	–	ns	70	
T_{TLH}	Rise Time	–	1	ns	69	
T_{THL}	Fall Time	–	1	ns	69	



Figure 52. eMMC Clock Signal Timing Diagram (HS200 Mode)

Figure 53. eMMC Input Timing Diagram (HS200 Mode)



9.6.11 SATA AC Specification

Table 127. SATA Specification and Interface Timings (Sheet 1 of 3)

Symbol	Parameter	Gen1		Gen2		Units	Notes
		Min	Max	Min	Max		
UI	Unit Interval	666.43	670.23	333.21	335.11	ps	
Receiver Parameter							
Z_{diffRX}	RX Pair Differential Impedance	85	115	85	115	Ω	
$V_{RX-DIFF-PP}$	VdiffRX, RX Differential Input Voltage	325	600	275	750	mvPP	
$T_{RX-RISE}$	RX Rise Time	100	273	67	136	ps	
$T_{RX-FALL}$	RX Fall Time	100	273	67	136	ps	
$T_{RX-SKEW}$	RX Differential Skew		100	50	100	ps	
$V_{RX-CM-AC}$	Vcm,acRX,RX AC Common Mode Voltage		100	100	150	mvPP	
$F_{RX-CM-AC}$	AC Common Mode Frequency	3	200	2	200	MHz	
$T_{J-Con-DD-5}$	TJ at Connector, Data-Data, 5		0.43			UI	
$D_{J-Con-DD-5}$	DJ at Connector, Data-Data, 5		0.35			UI	
$T_{J-Con-DD-250}$	TJ at Connector, Data-Data, 250		0.60			UI	
$D_{J-Con-DD-250}$	DJ at Connector, Data-Data, 250		0.42			UI	
$T_{TJ-Con-CD-10}$	TJ at Connector, Clk-Data, fBAUD/10				0.46	UI	




Table 127. SATA Specification and Interface Timings (Sheet 2 of 3)

Symbol	Parameter	Gen1		Gen2		Units	Notes
T _{DJ-Con-CD-10}	DJ at Connector, Clk-Data, fBAUD/10				0.35	UI	
T _{TJ-Con-CD-500}	TJ at Connector, Clk-Data, fBAUD/500				0.60	UI	
T _{DJ-Con-CD-500}	DJ at Connector, Clk-Data, fBAUD/500				0.42	UI	
T _{jcon CD-1667}	Tj at Connector Clk-Data, fbaud/1667		.65		.65	UI	
D _{j con CD-1667}	Dj at Connector Clk-Data, fbaud/1667		.35		.35	UI	
RL _{DD11,RX}	Min Differential Mode return loss (limits 150 - 300 MHz)			18		dB	
	Min Differential Mode return loss (limits 1.2 - 2.4 GHz)			8		dB	
	Min Differential Mode return loss (limits 2.4 - 3.0 GHz)			3		dB	
RL _{CC11,RX}	RX Common Mode Return Loss (limits 150 - 600 MHz)			5		dB	
	RX Common Mode Return Loss (limits 1.2 - 2.4 GHz)			2		dB	
	RX Common Mode Return Loss (limits 3.0 - 5.0 GHz)			1		dB	
V _{diffRX}	RX Differential Input Voltage	240	600	240	750	mV	
Transmitter Parameter							
Z _{diffTX}	TX Pair Differential Impedance	85	115	85	115	Ω	
V _{TX-DIFF-PP}	VdiffTX, TX Differential Input Voltage	400	600	400	700	mvPP	
T _{TX-RISE}	TX Rise Time	100	273	67	136	ps	1
T _{TX-FALL}	TX Fall Time	100	273	67	136	ps	1
T _{TX-SKEW}	TX Differential Skew	-	20	-	20	ps	
V _{CM-AC}	TX AC Common Mode				50	mv	
T _{TJ-Con-DD-5}	TJ at Connector, Data-Data, 5 UI		0.355			UI	
T _{DJ-Con-DD-5}	DJ at Connector, Data-Data, 5 UI		0.175			UI	
T _{TJ-Con-DD-250}	TJ at Connector, Data-Data, 250 UI		0.470			UI	
D _{J-Con-DD-250}	DJ at Connector, Data-Data, 250		0.220			UI	
T _{TJ-Con-CD-10}	TJ at Connector, Clk-Data, fBAUD/10				0.30	UI	
T _{DJ-Con-CD-10}	DJ at Connector, Clk-Data, fBAUD/10				0.17	UI	

Table 127. SATA Specification and Interface Timings (Sheet 3 of 3)

Symbol	Parameter	Gen1		Gen2		Units	Notes
T _{TJ-Con-CD-500}	TJ at Connector, Clk-Data, fBAUD/500				0.37	UI	
T _{DJ-Con-CD-500}	DJ at Connector, Clk-Data, fBAUD/500				0.19	UI	
T _{jcon CD-1667}	Tj at Connector Clk-Data, fbaud/1667		.65		.65	UI	
D _{j con CD-1667}	Dj at Connector Clk-Data, fbaud/1667		.35		.35	UI	
RL _{DD11,TX}	Min Differential Mode return loss (limits 150 - 300 MHz)			14		dB	
	Min Differential Mode return loss (limits 1.2 - 2.4 GHz)			6		dB	
	Min Differential Mode return loss (limits 2.4 - 3.0 GHz)			3		dB	
RL _{CC11,TX}	RX Common Mode Return Loss (limits 150 - 600 MHz)			5 - 8		dB	
	RX Common Mode Return Loss (limits 1.2 - 2.4 GHz)			2		dB	
	RX Common Mode Return Loss (limits 3.0 - 5.0 GHz)			1		dB	
V _{RX-DIFF-PP}	VdiffRX, RX Differential Input Voltage	325	600	275	750	mvPP	
T _{RX-RISE}	RX Rise Time	100	273	67	136	ps	
T _{RX-FALL}	RX Fall Time	100	273	67	136	ps	
T _{RX-SKEW}	RX Differential Skew		100	50	100	ps	
V _{RX-CM-AC}	Vcm,acRX,RX AC Common Mode Voltage		100	100	150	mvPP	


NOTES:

- 20% - 80%
- All parameters measured at Rload = 100Ω ±10% load.
- For a detailed description of the symbols, see the *IEEE1596.3-1996* Standard.

9.6.12 USB 2.0 Host AC Specification

Table 128. USB 2.0 AC specification (HIGH SPEED)

Symbol	Parameter	Min	Max	Units	Notes	Fig
DRIVER CHARACTERISTICS:						
THSR	Rise Time (10% - 90%)	100		ps		
THSF	Fall Time (10% - 90%)	100		ps		
ZHS DRV	Driver Output Resistance (which also serves as high-speed termination)	40.5	49.5			

**Table 128. USB 2.0 AC specification (HIGH SPEED)**

Symbol	Parameter	Min	Max	Units	Notes	Fig
CLOCK TIMINGS:						
THSDRAT	High-speed Data Rate	479.7 60	480.2 40	Mb/s		
THSFRAM	Microframe Interval	124.9 375	125.0 625	us		

Table 129. USB 2.0 AC specification (FULL SPEED)

Symbol	Parameter	Min	Max	Units	Notes	Fig
DRIVER CHARACTERISTICS:						
TFR	Rise Time	4	20	ns		44,4 5
TFF	Fall Time	4	20	ns		44,4 5
TFRFM	Differential Rise and Fall Time Matching	90	111.1 1	%	10	
ZDRV	Driver Output Resistance for driver which is not high-speed capable	28	44			
CLOCK TIMINGS:						
TFDRATH S	Full-speed Data Rate for hubs and devices which are high-speed capable	11.99	12.00 60	Mb/s		
TFDRATE	Full-speed Data Rate for hubs and devices which are not high-speed capable	11.97	12.03 00	MB/s		
TFRAME	Frame Interval	0.999 5	1.000 5	ms		
FULL-SPEED DATA TIMINGS						
TDJ1 TDJ2	Source Jitter Total (including frequency tolerance): To Next Transition For Paired Transitions	-3.5 -4	3.5 4	ns ns	7,8,12 ,10	46
TFDEOP	Source Jitter for Differential Transition to SE0 Transition	-2	5	ns	8,11	47
TFEOPT	Source SE0 interval of EOP	160	175	ns		47

Table 130. USB 2.0 AC specification (LOW SPEED)

Symbol	Parameter	Min	Max	Units	Notes	Fig
DRIVER CHARACTERISTICS:						
TLR	Rise Time	75	300	ns		44
TFF	Fall Time	75	300	ns		44
TLRFM	Differential Rise and Fall Time Matching	80	125	%	10	

Table 130. USB 2.0 AC specification (LOW SPEED)

Symbol	Parameter	Min	Max	Units	Notes	Fig
CLOCK TIMINGS:						
TLDRATH S	Low-speed Data Rate for hubs and devices which are high-speed capable	1.499 25	1.500 75	Mb/s		
TLDRATE	Low-speed Data Rate for hubs and devices which are not high-speed capable	1.477 5	1.522 5	MB/s		
FULL-SPEED DATA TIMINGS						
TUDJ1 TUDJ2	Upstream facing port source Jitter Total (including frequency tolerance): To Next Transition For Paired Transitions	-95 -150	95 150	ns ns	7,8	46
TDDJ1 TDDJ2	Downstream facing port source Jitter Total (including frequency tolerance): To Next Transition For Paired Transitions	-25 -14	25 14	ns ns	7,8	46
TLDEOP	Source Jitter for Differential Transition to SE0 Transition	-40	100	ns	8,11	47
TLEOPT	Source SE0 interval of EOP	1.25	1.50	us		47

NOTES:

1. Measured at A plug.
2. Measured at A receptacle.
3. Measured at B receptacle.
4. Measured at A or B connector.
5. Measured with RL of 1.425 k Ω to 3.6 V.
6. Measured with RL of 14.25 k Ω to GND.
7. Timing difference between the differential data signals.
8. Measured at crossover point of differential data signals.
9. The maximum load specification is the maximum effective capacitive load allowed that meets the target VBUS drop of 330 mV.
10. Excluding the first transition from the Idle state.
11. The two transitions should be a (nominal) bit time apart.
12. For both transitions of differential signaling.
13. Must accept as valid EOP.
14. Single-ended capacitance of D+ or D- is the capacitance of D+/D- to all other conductors and, if present, shield in the cable. That is, to measure the single-ended capacitance of D+, short D-, VBUS, GND, and the shield line together and measure the capacitance of D+ to the other conductors.
15. For high power devices (non-hubs) when enabled for remote wakeup.


Figure 54. USB Rise and Fall Times


Figure 55. USB Full Speed Load




Figure 56. USB Differential Data Jitter for Low/Full-Speed





Figure 57. USB Differential-to-EOP Transition Skew and EOP Width for Low/Full-Speed



9.6.13 USB 3.0 AC Specification

Figure 58. USB 3.0 Signals AC Specification

Symbol	Parameter	Min	Max	Units	Notes
TMIN-PULSE-DJ	Deterministic min Pulse	-	0.96	UI	1
TMIN-PULSE-TJ	Tx min Pulse	-	0.90	UI	2
TTX-EYE	Transmitter Eye	0.625	-	UI	3
TTx-DJ-DD	Tx deterministic jitter	-	.205	UI	4

NOTES:

1. Tx pulse width variation that is deterministic.
2. Min Tx Pulse at 10^{-12} including Dj and Rj.
3. Includes all jitter sources.
4. Deterministic jitter only assuming the Dual Dirac distribution


9.6.14 ULPI USB 2.0 Device AC Specification

Table 131. ULPI Signals AC Specification

Symbol	Parameter	Min	Typ	Max	Units	Notes
F _{STEADY}	Clock frequency steady state	59.97	60	60.03	MHz	
TRISE/ FALL	Input clock rise/fall time	2		7	ns	1,2
TSC,TSD	Setup time (control in, 8-bit data in) relative to rising clock edge at host	6		-	ns	
THC,THD	Hold time (control in, 8-bit data in) relative to rising clock edge at host	0			ns	
TDC,TDD	Output delay (control in, 8-bit data in) relative to rising clock edge at host	0		-	ns	3
TRISE/ FALL	Rise/Fall time (control out, 8-bit data out)	2		7	ns	1,2,4

NOTES:

1. Based on trace length of 1–4", Far End Load of 1–5 pF and board impedance of 30–75 ohms.
2. Measured from 10–90%.
3. Minimum time deviates from ULPI Specification, minimum time is not defined in ULPI Specification.
4. Minimum time and Maximum time not mentioned in the ULPI Specification.

Figure 59. ULPI Timing Diagram

9.6.15 Intel® HD Audio AC Specification

9.6.15.1 1.5-V AC specification

The output driver on the Intel HD Audio electrical link must be able to deliver an initial voltage of at least V_{IL_HDA} or V_{IH_HDA} respectively at the receiver through the bus with known characteristic impedance and at the same time meeting signal quality requirements.

The minimum and maximum drive characteristics of Intel HD Audio output buffers are defined by the V/I curves. Table 132 and Figure 60 describe the SDO buffer AC drive specification where as the Table 133 and Figure 61 describe the AC drive specification of the HDA_SDI[x] buffers. The AC drive specification for HDA_SYNC, HDA_RST# and HDA_CLK buffers is same as that of HDA_SDO.

These curves should be interpreted as traditional 'DC' transistor curves with the following exceptions: 'DC drive point' is the only position on the curves at which steady state operation is intended, while the higher currents are only reached momentarily during bus switching transients. The 'AC drive point' (real definition of buffer strength) defines the minimum instantaneous current required to switch the bus.

Adherence to these curves should be evaluated at worst case conditions. Minimum pull up curve is evaluated at minimum $V_{CC_{HDA}}$ and high temperature. Minimum pull down curve is evaluated at minimum $V_{CC_{HDA}}$ and high temperature. The maximum curve test points are evaluated at maximum $V_{CC_{HDA}}$ and low temperature.

Inputs must be clamped to both ground and power rails. The clamp diode characteristics are also listed here for reference.

Figure 60. V/I Curves for HDA_SDO buffers




Table 132. HDA_SDO 1.5V Buffer AC Specification (Sheet 1 of 2)

Symbol	Parameter	Condition	Min	Max	Unit
I_{OH}	switching Current High	$0 < V_{O_HDA} < 0.7V_{CC_{HDA}}$	- 16.67 $V_{CC_{HDA}}$		mA
		$0.7V_{CC_{HDA}} < V_{O_HDA} < 0.9V_{CC_{HDA}}$	- 55.57($V_{CC_{HD}} - V_{out}$)		mA




Table 132. HDA_SDO 1.5V Buffer AC Specification (Sheet 2 of 2)

Symbol	Parameter	Condition	Min	Max	Unit
		$0.7V_{CC_{HDA}} < V_{O_HDA} < V_{CC_{HDA}}$		$(151.52/V_{CC_{HDA}}) * (V_{O_HDA} - V_{CC_{HDA}}) * (V_{O_HDA} + 0.4V_{CC_{HDA}})$	mA
	(Test Point)	$V_{O_HDA} = 0.7V_{CC_{HDA}}$		$-50V_{CC_{HDA}}$	mA
I_{OL}	Low Period of SCL Clock	$V_{CC_{HDA}} > V_{O_HDA} > 0.3V_{CC_{HDA}}$	$16.67V_{CC_{HDA}}$		mA
		$0.3V_{CC_{HDA}} > V_{O_HDA} > 0.1V_{CC_{HDA}}$	$57.57V_{out}$		mA
		$0.3V_{CC_{HDA}} > V_{O_HDA} > 0$		$(238.1/V_{CC_{HDA}}) * V_{O_HDA} * (V_{CC_{HDA}} - V_{O_HDA})$	mA
	(Test Point)	$V_{O_HDA} = 0.3V_{CC_{HDA}}$		$50V_{CC_{HDA}}$	mA
I_{CL}	Low Clamp Current	$-3 < V_{I_HDA} < -1$	$-25 + (V_{I_HDA} + 1)/0.015$		
I_{CH}	High Clamp Current	$V_{CC_{HDA}} + 4 > V_{in} > V_{CC_{HDA}} + 1$	$25 + (V_{I_HDA} - V_{CC_{HDA}} - 1)/0.015$		
Slew_r	Output rise Slew rate	$0.25V_{CC_{HDA}}$ to $0.75V_{CC_{HDA}}$	0.5	1.5	V/ns Slew rate (note1)
Slew_f	Output rise Slew rate	$0.75V_{CC_{HDA}}$ to $0.25V_{CC_{HDA}}$	0.5	1.5	V/ns Slew rate (note1)

NOTE:

1. Slew rate is to be interpreted as the cumulative edge rate across the specified range, ($0.25V_{CC_{HDA}}$ to $0.75V_{CC_{HDA}}$ load for rise and $0.75V_{CC_{HDA}}$ to $0.25V_{CC_{HDA}}$ load for fall), rather than instantaneous rate at any point within the transition range.

Table 133. HDA_SDI[x] 1.5V Buffer AC Specification (Sheet 1 of 2)

Symbol	Parameter	Condition	Min	Max	Unit
I_{OH}	switching Current High	$0 < V_{O_HDA} < 0.7V_{CC_{HDA}}$	$-9.38V_{CC_{HDA}}$		mA
		$0.7V_{CC_{HDA}} < V_{O_HDA} < 0.9V_{CC_{HDA}}$	$-31.27(V_{CC_{HDA}} - V_{O_HDA})$		mA

Table 133. HDA_SD1[x] 1.5V Buffer AC Specification (Sheet 2 of 2)


Symbol	Parameter	Condition	Min	Max	Unit
		$0.7V_{CC_{HDA}} < V_{O_HDA} < V_{CC_{HDA}}$		$(113.64/V_{CC_{HDA}}) * (V_{O_HDA} - V_{CC_{HDA}}) * (V_{O_HDA} + 0.4V_{CC_{HDA}})$	mA
	(Test Point)	$V_{O_HDA} = 0.7V_{CC_{HDA}}$		$-37.5V_{CC_{HDA}}$	mA
I_{OL}	Low Period of SCL Clock	$V_{CC_{HDA}} > V_{O_HDA} > 0.3V_{CC_{HDA}}$	$9.38V_{CC_{HDA}}$		mA
		$0.3V_{CC_{HDA}} > V_{O_HDA} > 0.1V_{CC_{HDA}}$	$31.27V_{O_HDA}$		mA
		$0.3V_{CC_{HDA}} > V_{O_HDA} > 0$		$(178.57/V_{CC_{HDA}}) * V_{O_HDA} * (V_{CC_{HDA}} - V_{O_HDA})$	mA
	(Test Point)	$V_{O_HDA} = 0.3V_{CC_{HDA}}$		$37.55V_{CC_{HDA}}$	mA
I_{CL}	Low Clamp Current	$-3 < V_{I_HDA} < -1$	$-25 + (V_{I_HDA} + 1)/0.015$		
I_{CH}	High Clamp Current	$V_{CC_{HDA}} + 4 > V_{I_HDA} > V_{CC_{HDA}} + 1$	$25 + (V_{I_HDA} - V_{CC_{HDA}} - 1)/0.015$		
Slew_r	Output rise Slew rate	$0.25V_{CC_{HDA}}$ to $0.75V_{CC_{HDA}}$	0.5	1.5	V/ns Slew rate (note1)
Slew_f	Output rise Slew rate	$0.75V_{CC_{HDA}}$ to $0.25V_{CC_{HDA}}$	0.5	1.5	V/ns Slew rate (note1)

NOTE:

- Slew rate is to be interpreted as the cumulative edge rate across the specified range, ($0.25V_{CC_{HDA}}$ to $0.75V_{CC_{HDA}}$ load for rise and $0.75V_{CC_{HDA}}$ to $0.25V_{CC_{HDA}}$ load for fall), rather than instantaneous rate at any point within the transition range.


9.6.15.2 Maximum AC Ratings and Device Protection

All Intel HD Audio buffers should be capable of withstanding continuous exposure to the waveform shown in [Figure 61](#). It is recommended that these waveforms be used as qualification criteria against which the long term reliability of each device is evaluated. [Table 134](#) and [Table 135](#) list the parameters of the waveform. This level of robustness should be guaranteed by design; it is not intended that this waveform should be used as a production test.



These waveforms are applied with the equivalent of a zero impedance voltage source, driving through a series resistor directly into each input or tri-stated output pin. The open-circuit voltage of the voltage source is shown in Figure 61, which is based on the worst case overshoot and undershoot expected in actual Intel HD Audio buses. The resistor values are calculated to produce the worst case current into an effective internal clamp diode.

Figure 61. Maximum AC Waveforms for 1.5 V Signaling



NOTE:

1. The voltage waveform is supplied at the resistor shown in the evaluation setup, not the package pin.
2. Any internal clamping in the device being tested will greatly reduce the voltage levels seen at the package pin.

Table 134. 1.5V Parameters for Maximum AC Signalling Waveforms

Symbol	Parameter	Min	Max	Unit
V_1	Overshoot Voltage		3.25	V
V_2	Undershoot Initial Voltage		1.65	V
V_3	Undershoot Voltage	-1.6		V
V_{pu}	Waveform peak-to-peak		3.25	V
V_{po}	Waveform peak-to-peak		3.25	V
t_{rf}	Rise/fall time	0.5	1.5	V/ns
f_{SDI}	Frequency of AC rating waveform as applied to SDI input buffers		24	MHz
f_{SDO}	Frequency of AC rating waveform as applied to SDO input buffers		24	MHz

Table 135. Resistance value for the AC rating Waveform

Condition	Value
Overshoot waveform at the codec	65 Ohms
Undershoot waveform at the codec	101 Ohms
Overshoot waveform at the controller	108 Ohms

Table 135. Resistance value for the AC rating Waveform

Condition	Value
Undershoot waveform at the controller	133 Ohms

NOTE:

1. The voltage waveform is supplied at the resistor shown in the evaluation setup, not the package pin.
2. Any internal clamping in the device being tested will greatly reduce the voltage levels seen at the package pin.

9.6.16 I²S (Audio) AC Specification

9.6.16.1 I²S Slave Mode AC Specification

Table 136. I²S AC Timings

Symbol	Parameter	Min.	Max.	Units	Figure	Notes
T _{DC}	Clock Duty Cycle	45	55	%	62, 63, 64	
T _{I2S}	Clock Frequency		12.25	MHz	62, 63, 64	
T _{S-RXD}	Setup for DATAIN with respect to the CLK active edge.	6	–	ns	62, 63, 64	1, 2, 3
T _{H-RXD}	Hold for DATAIN with respect to the CLK active edge.	6	–	ns	62, 63, 64	1, 2, 3
T _{S-FS}	Setup for FRM with respect to the CLK active edge.	6	–	ns	62, 63, 64	1, 2, 3
T _{H-FS}	Hold for FRM with respect to CLK active edge.	20	–	ns	62, 63, 64	1, 2, 3
T _{CO_TXD}	Tco of DATAOUT with respect to CLK active edge at the host	–	18	ns	62, 63, 64	1, 2, 3

NOTE:

1. Active edge refers to the mode selected.
2. For I²S mode, data launches at falling edge and is being captured at rising edge.
3. For PCM mode data launches at rising edge and is being captured at falling edge. PCM Mode has two different modes, Short Frame Mode and Long Frame Mode.
 - a. Short Frame Mode—FS is asserted one clock cycle earlier than data is launched by the Master.
 - b. Long Frame Mode—FS and Data are launched on the same clock edge by the Master.




Figure 62. I²S Slave Port Timings in I²S ModeFigure 63. I²S Slave Port Timings in PCM Short Frame Mode

Figure 64. I²S Slave Port Timings in PCM Long Frame Mode



9.6.16.2 I²S Master Mode AC Specification

Table 137. I²S Master Mode AC Timing

Symbol	Parameter	Min.	Max.	Units	Figure
T_{DC}	Clock Duty Cycle	45	55	%	
T_{I2S}	Clock Frequency		12.5	MHz	
T_{S-RXD}	Setup for DATAIN with respect to the CLK active edge	10	–	ns	
T_{H-RXD}	Hold for DATAIN with respect to the CLK active edge	10	–	ns	
T_{CO_TXD}	T_{CO} of DATAOUT with respect to CLK active edge at the SoC	–	10	ns	
T_{CO_FS}	T_{CO} of FRM with respect to CLK at the SoC		10	ns	



9.6.17 PCI Express* AC Specification

Table 138. PCI Express* Interface Timings

Symbol	Parameter	Min	Typ	Max	Unit	Figures	Notes
Transmitter and Receiver Timings							
UI	Unit Interval – PCI Express* Gen 1 (2.5 GT/s)	399.88		400.12	ps		5
UI	Unit Interval – PCI Express* Gen 2 (5.0 GT/s)	199.9		200.1	ps		5
T_{TX-EYE}	Minimum Transmission Eye Width	0.7		—	UI	65	1,2
$T_{TX-RISE/Fall}$ (Gen1)	TXP/TXN Rise/Fall time	0.125			UI		1,2
$T_{TX-RISE/Fall}$ (Gen2)	TXP/TXN Rise/Fall time	0.15			UI		1,2
T_{RX-EYE}	Minimum Receiver Eye Width	0.40		—	UI	66	3,4

NOTES:

- Specified at the measurement point into a timing and voltage compliance test load and measured over any 250 consecutive TX UIs. (Also refer to the Transmitter compliance eye diagram)
- A $T_{TX-EYE} = 0.70$ UI provides for a total sum of deterministic and random jitter budget of $T_{TXJITTER-MAX} = 0.30$ UI for the Transmitter collected over any 250 consecutive TX UIs. The $T_{TXEYE-MEDIAN-to-MAX-JITTER}$ specification ensures a jitter distribution in which the median and the maximum deviation from the median is less than half of the total TX jitter budget collected over any 250 consecutive TX UIs. It should be noted that the median is not the same as the mean. The jitter median describes the point in time where the number of jitter points on either side is approximately equal as opposed to the averaged time value.
- Specified at the measurement point and measured over any 250 consecutive UIs. The test load documented in the PCI Express* specification 2.0 should be used as the RX device when taking measurements (also refer to the Receiver compliance eye diagram). If the clocks to the RX and TX are not derived from the same reference clock, the TX UI recovered from 3500 consecutive UI must be used as a reference for the eye diagram.
- A $T_{RX-EYE} = 0.40$ UI provides for a total sum of 0.60 UI deterministic and random jitter budget for the Transmitter and interconnect collected any 250 consecutive UIs. The $T_{RX-EYE-MEDIAN-to-MAX-JITTER}$ specification ensures a jitter distribution in which the median and the maximum deviation from the median is less than half of the total 0.6 UI jitter budget collected over any 250 consecutive TX UIs. It should be noted that the median is not the same as the mean. The jitter median describes the point in time where the number of jitter points on either side is approximately equal as opposed to the averaged time value. If the clocks to the RX and TX are not derived from the same reference clock, the TX UI recovered from 3500 consecutive UI must be used as the reference for the eye diagram.
- Nominal Unit Interval is 400 ps for 2.5 GT/s and 200 ps for 5 GT/s.
- PCIe Reference clocks follow PCI Express* specification with the exception of edge rate: Max = 8.0 V/ns instead of 4.0 V/ns. There should be no DC termination of the clocks.

Figure 65. PCI Express* Transmitter Eye






Figure 66. PCI Express* Receiver Eye





9.6.18 PCU - PMC - Suspended Clock AC Specification

Table 139. SUS Clock Timings

Symbol	Parameter	Min	Max	Units	Notes	Figure
f_{susclk}	Operating Frequency	32		kHz	1	
t39	High time	9.5	-	μs	1	
t39a	Low Time	9.5	-	μs	1	

Note: 1. SUSCLK duty cycle can range from 30% minimum to 70% maximum.

9.6.19 PCU - SPI NOR AC Specification


Table 140. PCU - SPI NOR AC Specification

Sym	Parameter	Min	Max	Units	Notes
t180	Serial Clock Frequency	20, 33, 50		MHz	
t182	SPI Clock duty cycle at Host	45	55	%	
t183	Tco of PCU_SPI_MOSI with respect to serial clock falling edge at the host	0	5	ns	
t184	Setup of PCU_SPI_MISO with respect to serial clock falling edge at the host	11	-	ns	
t185	Hold of PCU_SPI_MISO with respect to serial clock falling edge at the host	0	-	ns	1, 2, 3
t186	Setup of PCU_SPI_CS[1:0]# with respect to serial clock falling edge at the host	12	-	ns	
t187	Hold of PCU_SPI_CS[1:0]# with respect to serial clock falling edge at the host	5	-	ns	
t188/t189	Min Idle (de-assertion) time for PCU_SPI_CLK signals	32	-	ns	
Trise/Tfall	Rise / Fall time	-	2	ns	1,2

NOTES:

1. Based on trace length of up to 4" and board impedance of 30–75 Ω Measured from 30–70%.
2. Total maximum, capacitance of 25 pF

Figure 67. SPI NOR Timing



9.6.20 PCU - SMBUS AC Specification

Table 141. SMBUS Clock Signal Timings

Symbol	Parameter	Min	Max	Unit	Notes	Figure
f_{smb}	Operating Frequency	10	100	kHz		
t_{HIGH}	High time	4.0	50	us	1	68
t_{LOW}	Low time	4.7		us		68
t_{RISE}	Rise time		1000	ns		68
t_{FALL}	Fall time		300	ns		68

1. The maximum high time (t_{HIGH} Max) provides a simple method for devices to detect bus idle conditions.



Table 142. SMBus Timing

Sym	Parameter	Min	Max	Units	Notes	Figure
$t_{\text{STOP_START}}$	Bus Tree Time Between Stop and Start Condition	4.7	—	μs		69
$t_{\text{START_HOLD}}$	Hold Time after (repeated) Start Condition. After this period, the first clock is generated.	4.0	—	μs		69
$t_{\text{START_SET}}$	Repeated Start Condition Setup Time	4.7	—	μs		69
$t_{\text{STOP_SET}}$	Stop Condition Setup Time	4.0	—	μs		69
$t_{\text{DATA_HOLD}}$	Data Hold Time	0	—	ns	1	69
$t_{\text{DATA_SET}}$	Data Setup Time	250	—	ns		69

Table 142. SMBus Timing

Sym	Parameter	Min	Max	Units	Notes	Figure
t_{DEV_TO}	Device Time Out	25	35	ms	2	
t_{SLVCLK_LOWEXT}	Cumulative Clock Low Extend Time (slave device)	—	25	ms	3	69
t_{MSTCLK_LOWEXT}	Cumulative Clock Low Extend Time (master device)	—	10	ms	4	69

1. t_{DATA_HOLD} has a minimum timing for I2C of 0 ns, while the minimum timing for SMBus is 300 ns.
2. A device will timeout when any clock low exceeds this value.
3. t_{SLVCLK_LOWEXT} is the cumulative time a slave device is allowed to extend the clock cycles in one message from the initial start to stop. If a slave device exceeds this time, it is expected to release both its clock and data lines and reset itself.
4. t_{MSTCLK_LOWEXT} is the cumulative time a master device is allowed to extend its clock cycles within each byte of a message as defined from start-to-ack, ack-to-ack or ack-to-stop.

Figure 68. SMBus Transaction**Figure 69. SMBus Timeout**

9.6.21 PCU - iLB - LPC AC Specification

Table 143. LPC AC Specifications (with loop back from ILB_LPC_CLK[0] to ILB_LPC_CLK[1])

Sym	Parameter	Min	Max	Units	Notes	Fig
T _{CO}	ILB_LPC_AD[3:0], ILB_LPC_FRAME#, ILB_LPC_SERIRQ Valid Delay from ILB_LPC_CLK[1] Rising	2	14	ns		73
T _{EN_AD}	ILB_LPC_AD[3:0], ILB_LPC_FRAME#, ILB_LPC_SERIRQ Output Enable Delay from ILB_LPC_CLK[1] Rising	2		ns		74
T _{FD_AD}	ILB_LPC_AD[3:0] Float Delay from ILB_LPC_CLK[1] Rising		28	ns		75
T _{SU_AD}	ILB_LPC_AD[3:0] Setup Time to ILB_LPC_CLK[1] Rising	7		ns		76
T _{HD_AD}	ILB_LPC_AD[3:0] Hold Time from ILB_LPC_CLK[1] Rising	0		ns		76
T _{ipc}	ILB_LPC_CLK[1:0] Duty Cycle	35	65	%	1	

NOTE:

1. High time is measured from 0.75 x PCU_1P8_G3. Low time is measured from 0.35 x PCU_1P8_G3
2. The load capacitance used for the LPC timing parameters is 30 pF
3. VT is 1/2 of LPC IO voltage

Figure 70. Valid Delay from Rising Clock Edge




Figure 71. Output Enable Delay






Figure 72. Float Delay**Figure 73. Setup and Hold Times**

9.6.22 SIO - I²C AC Specifications

9.6.22.1 I²C Fast/Standard Mode Electrical Specification

Table 144. I²C Fast/Standard Mode AC Specifications (Sheet 1 of 2)

Symbol	Parameter	Standard-Mode		Fast-Mode		Fast-Mode Plus		Units	Notes	Figure
		Min.	Max.	Min.	Max.	Min.	Max.			
f_{SCL}	I ² C_CLK clock frequency	0	100	0	400	0	1000	kHz		
$t_{HD:STA}$	Hold time (repeated) START condition. After this period, the first clock pulse is generated	4.0	–	0.6	–	0.26	–	μs		74
t_{LOW}	LOW period of the I ² C_CLK clock	4.7	–	1.3	–	0.5	–	μs		74
t_{HIGH}	HIGH period of the I ² C_CLK clock	4.0	–	0.6	–	0.26	–	μs		74




Table 144. I²C Fast/Standard Mode AC Specifications (Sheet 2 of 2)

Symbol	Parameter	Standard-Mode		Fast-Mode		Fast-Mode Plus		Units	Notes	Figure
		Min.	Max.	Min.	Max.	Min.	Max.			
t _{SU:STA}	Set-up time for a repeated START condition	4.7	–	0.6	–	0.26	–	μs		74
t _{HD:DAT}	Data hold time: I ² C-bus devices	0	–	0	–	0	–	ns		74
t _{SU:DAT}	Data set-up time	250	–	100	–	50	–	ns	1	74
t _r	Rise time of both I ² C_DATA and I ² C_CLK signals	–	1000	$20 + 0.1C_b^{(5)}$	300	–	120	ns	2, 3	74
t _f	Fall time of both I ² C_DATA and I ² C_CLK signals	1	300	1	300	1	120	ns	5	74
t _{SU:STO}	Set-up time for STOP condition	4.0	–	0.6	–	0.26	–	μs		74
t _{BUF}	Bus free time between a STOP and START condition	4.7	–	1.3	–	0.5	–	μs		
C _b	Capacitive load for each bus line	–	130	–	130	–	–	pF		
V _{nL}	Noise margin at the LOW level for each connected device (including hysteresis)	0.1 V _{DD}	–	0.1 V _{DD}	–	0.1 V _{DD}	–	V		
V _{nH}	Noise margin at the HIGH level for each connected device (including hysteresis)	0.2 V _{DD}	–	0.2 V _{DD}	–	0.2 V _{DD}	–	V		

NOTES:


1. A Fast-mode I2C-bus device can be used in a Standard-mode I2C-bus system, but the requirement t_{SU; DAT} ≥ 250 ns must then be met. This will automatically be the case if the device does not stretch the LOW period of the I2C_CLK signal. If such a device does stretch the LOW period of the I2C_CLK signal, it must output the next data bit to the I2C_DATA line t_{r max} + t_{SU; DAT} = 1000 + 250 = 1250 ns (according to the Standard-mode I2C-bus specification) before the I2C_CLK line is released.
2. C_b = total capacitance of one bus line in pF.
3. No Active current source PU on I2C_CLK signals. Rise time is based upon the Pull-up resistor mentioned in the Platform Design Guide.
4. The maximum t_{HD;DAT} could be 3.45 ms and 0.9 ms for Standard-mode and Fast-mode, but must be less than the maximum of t_{VDD;DAT} or t_{VDD;ACK} by a transition time. This maximum must only be met if the device does not stretch the LOW period (t_{LOW}) of the I2C_CLK signal. If the clock stretches the I2C_CLK, the data must be valid by the set-up time before it releases the clock.
5. Specification deviates from the minimum time compared to Industrial specification.

Figure 74. Definition of Timing for F/S-Mode Devices on I²C Bus

9.6.22.2 I²C High Speed Mode Electrical Specification

Table 145. AC Specification for High Speed Mode I²C—Bus Devices

Symbol	Parameter	C _b = 100 pF (max)		Units	Figure
		Min.	Max.		
f _{SCL}	I ² C_CLK clock frequency	0	1.7	MHz	
t _{SU:STA}	Set-Up time for a repeated START condition	160	–	ns	
t _{HD:STA}	Hold time (repeated) START condition.	160	–	ns	
t _{LOW}	LOW period of the I ² C_CLK clock	160	–	ns	
t _{HIGH}	HIGH period of the I ² C_CLK clock	60	–	ns	
t _{HD:DAT}	Data hold time: I ² C-bus devices	0	–	ns	
t _{SU:DAT}	Data set-up time	10	–	ns	
t _r CL	Rise time of I ² C_CLK signals	10	40	ns	
t _f CL	Fall time of I ² C_CLK signals	1	40	ns	
t _r CL1	Rise time of I ² C_CLK signal after a repeated START condition and after an acknowledge bit	10	40	ns	
t _r DA	Rise time of I ² C_DATA signals	10	80	ns	
t _f DA	Fall time of I ² C_DATA signals	1	80	ns	
t _{SU:STO}	Set-up time for STOP condition	160	–	ns	
V _{nL}	Noise margin at the LOW level for each connected device (including hysteresis)	0.1 V _{DD}	–	V	
V _{nH}	Noise margin at the HIGH level for each connected device (including hysteresis)	0.2 V _{DD}	–	V	

Figure 75. Definition of Timing for High Speed-Mode Devices on I²C Bus

9.6.23 SIO - UART AC Specification


Table 146. UART AC Specification

Symbol	Parameter	Min.	Max.	Unit	Notes
T_{RISE}	Maximum Rise Time	2.5	5	ns	1, 2
T_{FALL}	Maximum Fall Time	2.5	5	ns	1, 2
$T_{UARTFIL}$	UART Sampling Filter Period	20		ns	3

NOTES:

1. Based on total trace length of 1-4", Total maximum, capacitance of 27 pF and board impedance of 30-75Ω.
2. Measured from 10-90%.
3. Each bit including start and stop bit is sampled three times at center of a bit at an interval of 20 ns (minimum). If three sampled values do not agree, then UART noise error is generated.

Figure 76. UART Timing Diagram




9.6.24 JTAG AC Specification

Table 147. JTAG AC Specification

T# Parameter	Min	Max	Unit	Figure	Notes
T_P : TAP_TCK Period	15		ns		66 MHz
T_{CL} : TAP_TCK Clock Low Time	$0.4 * T_{JC}$		ns		
T_{CH} : TAP_TCK Clock High Time	$0.4 * T_{JC}$		ns		
T_{SU} : TAP_TDI, TAP_TMS Setup Time	11		ns	78	
T_H : TAP_TDI, TAP_TMS Hold Time	5		ns	78	
T_{CO} : TAP_TCK falling to TAP_TDO output valid		11	ns	78	
T_{CO} : TAP_TCK falling to TAP_TDO output high impedance		11	ns		
T_{18} : TAP_TRST# assert time	2		ns	79	


NOTES:

1. Unless otherwise noted, all specifications in this table apply to all SoC frequencies.
2. Not 100% tested. Specified by design characterization.
3. It is recommended that TAP_TMS be asserted while TAP_TRST# is being deasserted.
4. Board JTAG signal skew max = ± 500 ps.

Figure 77. JTAG Timing Diagram**Table 148. Boundary Scan AC Specification**


T# Parameter	Min	Max	Unit	Notes
Boundary scan all non test output/float delay	0.5	15	ns	Referenced to the falling edge of T_{CK}
Boundary scan all non test input setup	10		ns	Referenced to the falling edge of T_{CK}
Boundary scan all non test input hold	13		μs	Referenced to the falling edge of T_{CK}

Figure 78. TAP Valid Delay Timing Waveform



Refer to [Table 88](#), [Table 89](#), [Table 90](#) for TAP Signal Group DC specifications and [Table 147](#) for TAP Signal Group AC specifications.

Figure 79. Test Reset (TAP_TRST#), Async GTL Input and PROCHOT# Timing Waveform



9.6.25 General AC Timing Diagrams

Note that the measurement of the differential waveform according to these diagrams would have to be made directly at the load at the end of the line. In a real system, this is not possible because the end of the line is at the input pad of the SoC silicon.





Figure 80. Clock Cycle Time**Figure 81. Clock Timing****Figure 82. Valid Delay from Rising Clock Edge****Figure 83. Setup and Hold Times**

Figure 84. Float Delay




Figure 85. Pulse Width




Figure 86. Output Enable Delay




Figure 87. Differential Clock Waveform (Measured Single-ended)





Figure 88. Differential Clock Waveform (Using Differential Probe for Measurement)



§



10 *Ballout and Package Information*

The SoC comes in a **25 mm X 27 mm** Flip-Chip Ball Grid Array (FCBGA) package and consists of a silicon die mounted face down on an organic substrate populated with 1170 solder balls on the bottom side. Capacitors may be placed in the area surrounding the die. Because the die-side capacitors are electrically conductive, and only slightly shorter than the die height, care should be taken to avoid contacting the capacitors with electrically conductive materials. Doing so may short the capacitors and possibly damage the device or render it inactive.

The use of an insulating material between the capacitors and any thermal solution should be considered to prevent capacitor shorting. An exclusion, or keep out zone, surrounds the die and capacitors, and identifies the contact area for the package. Care should be taken to avoid contact with the package inside this area.

Refer to the *Bay Trail SoC Thermal and Mechanical Design Guide* for details on package mechanical dimensions and tolerance, as well as other key package attributes.


10.1 **SoC Attributes**

- Package parameters: 25 mm X 27 mm
- Ball Count: 1170

All Units: mm

Tolerances if not specified:

- .X: ± 0.1
- .XX: ± 0.05
- Angles: ± 1.0 degrees





10.3 Ball Name and Function by Location

Many I/O's are configurable GPIO's. These I/O's are multiplexed with other signals in the ball list. This table matches names and locations of every ball with all possible multiplexed signals (denoted as GPIO Functions). Configurable GPIO's default to function 0 during power on and may not match the ball name. BIOS (platform firmware) is responsible for enabling the platform specific configuration. Please see your BIOS vendor for details.

Note: The X & Y locations in Table 146 are measured in microns from the center of the package.

Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 1 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
A3	VSS	11951.46	-11814.05	-	-	-	-	-
A5	VSS	11170.41	-11814.05	-	-	-	-	-
A6	VSS	10446.51	-11814.05	-	-	-	-	-
A7	USB_HSIC_RCOMP	9748.01	-11814.05	-	-	-	-	-
A9	ILB_RTC_X2	8835.9	-11814.05	-	-	-	-	-
A11	VSS	7774.43	-11814.05	-	-	-	-	-
A13	GPIO_S5[09]	6802.63	-11814.05	GPIO_S5[09]	RESERVED	RESERVED	RESERVED	RESERVED
A15	VSS	5830.82	-11814.05	-	-	-	-	-
A17	GPIO_S5[03]	4859.02	-11814.05	GPIO_S5[03]	RESERVED	RESERVED	RESERVED	PMC_WAKE_PCIE[3]#
A19	VSS	3887.22	-11814.05	-	-	-	-	-
A21	PCU_SPI_MOSI	2915.41	-11814.05	PCU_SPI_MOSI	-	-	-	-
A23	VSS	1943.61	-11814.05	-	-	-	-	-
A25	SVID_DATA	971.8	-11814.05	SVID_DATA	-	-	-	-
A27	VSS	0	-11814.05	-	-	-	-	-
A29	RESERVED	-971.8	-11814.05	RESERVED	RESERVED	-	-	-
A31	VSS	-1943.61	-11814.05	-	-	-	-	-
A33	DRAM0_DQ[13]	-2915.41	-11814.05	-	-	-	-	-
A35	VSS	-3887.22	-11814.05	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 2 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
A37	DRAM0_DQ[11]	-4859.02	-11814.05	-	-	-	-	-
A39	VSS	-5830.82	-11814.05	-	-	-	-	-
A41	DRAM0_DQ[24]	-6802.63	-11814.05	-	-	-	-	-
A43	VSS	-7774.43	-11814.05	-	-	-	-	-
A45	DRAM0_DQ[26]	-8746.24	-11814.05	-	-	-	-	-
A47	VSS	-9620.5	-11814.05	-	-	-	-	-
A48	DRAM_VDD_S4	-10293.6	-11814.05	-	-	-	-	-
A49	VSS	-10992.1	-11814.05	-	-	-	-	-
A51	VSS	-11773.15	-11814.05	-	-	-	-	-
A52	VSS	-12382.75	-11814.05	-	-	-	-	-
B2	VSS	12382.75	-11382.76	-	-	-	-	-
B4	USB_HSIC0_DATA	11631.68	-11237.72	-	-	-	-	-
B5	USB_HSIC0_STROBE	11038.33	-11222.48	-	-	-	-	-
B6	UNCORE_V1P0_G3	10444.99	-11220.7	-	-	-	-	-
B7	PMC_CORE_PWROK	9851.64	-11229.59	-	-	-	-	-
B8	ILB_RTC_EXTPAD	9258.3	-11224.26	-	-	-	-	-
B10	PMC_RSMRST#	8260.33	-11428.98	-	-	-	-	-
B12	USB_ULPI_REFCLK	7288.53	-11428.98	GPIO_S5[43]	USB_ULPI_REFCLK	RESERVED	RESERVED	-
B14	GPIO_S5[06]	6316.73	-11428.98	GPIO_S5[06]	PMC_SUSCLK[2]	RESERVED	RESERVED	RESERVED
B16	GPIO_S5[01]	5344.92	-11428.98	GPIO_S5[01]	RESERVED	RESERVED	RESERVED	PMC_WAKE_PCIE[1]#
B18	GPIO_S5[00]	4373.12	-11428.98	GPIO_S5[00]	RESERVED	-	-	-
B20	USB_OC[1]#	3401.31	-11428.98	USB_OC[1]#	GPIO_S5[20]	-	-	-
B22	PCU_SPI_MISO	2429.51	-11428.98	PCU_SPI_MISO	-	-	-	-
B24	SVID_ALERT#	1457.71	-11428.98	SVID_ALERT#	-	-	-	-
B26	DDIO_BKLTCTL	485.9	-11428.98	RESERVED	RESERVED	DDIO_BKLTCTL	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 3 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
B28	DDIO_VDDEN	-485.9	-11428.98	RESERVED	RESERVED	DDIO_VDDEN	-	-
B30	RESERVED	-1457.71	-11428.98	RESERVED	RESERVED	-	-	-
B32	DRAM0_DQ[08]	-2429.51	-11428.98	-	-	-	-	-
B34	DRAM0_DQSN[1]	-3401.31	-11428.98	-	-	-	-	-
B36	DRAM0_DM[1]	-4373.12	-11428.98	-	-	-	-	-
B38	DRAM0_DQ[15]	-5344.92	-11428.98	-	-	-	-	-
B40	DRAM0_DQ[29]	-6316.73	-11428.98	-	-	-	-	-
B42	DRAM0_DM[3]	-7288.53	-11428.98	-	-	-	-	-
B44	DRAM0_DQSP[3]	-8260.33	-11428.98	-	-	-	-	-
B46	DRAM0_DQ[27]	-9258.3	-11224.26	-	-	-	-	-
B47	DRAM0_DQ[31]	-9851.64	-11229.59	-	-	-	-	-
B48	DRAM0_DQ[30]	-10444.99	-11220.7	-	-	-	-	-
B49	DRAM0_MA[14]	-11038.33	-11222.48	-	-	-	-	-
B50	DRAM0_MA[15]	-11631.68	-11237.72	-	-	-	-	-
B52	VSS	-12225.02	-11225.02	-	-	-	-	-
B53	VSS	-12814.05	-11382.76	-	-	-	-	-
C1	VSS	12814.05	-10951.46	-	-	-	-	-
C3	USB3_V1P0_G3	11644.38	-10644.38	-	-	-	-	-
C5	UNCORE_V1P0_G3	10579.86	-10642.85	-	-	-	-	-
C7	USB_RCOMPI	9553.19	-10709.15	-	-	-	-	-
C9	ILB_RTC_X1	8697.98	-11028.17	-	-	-	-	-
C11	ILB_RTC_TEST#	7774.43	-11070.59	-	-	-	-	-
C12	ILB_RTC_RST#	7288.53	-10729.98	-	-	-	-	-
C13	GPIO_S5[08]	6802.63	-11070.59	GPIO_S5[08]	RESERVED	RESERVED	RESERVED	RESERVED
C14	VSS	6316.73	-10729.98	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 4 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
C15	GPIO_S5[07]	5830.82	-11070.59	GPIO_S5[07]	PMC_SUSCLK[3]	RESERVED	RESERVED	RESERVED
C16	GPIO_S5[05]	5344.92	-10729.98	GPIO_S5[05]	PMC_SUSCLK[1]	RESERVED	RESERVED	RESERVED
C17	GPIO_S5[04]	4859.02	-11070.59	GPIO_S5[04]	RESERVED	RESERVED	RESERVED	RESERVED
C18	GPIO_S5[02]	4373.12	-10729.98	GPIO_S5[02]	RESERVED	RESERVED	RESERVED	PMC_WAKE_PCIE[2]#
C19	GPIO_S5[10]	3887.22	-11070.59	GPIO_S5[10]	RESERVED	RESERVED	RESERVED	-
C20	USB_OC[0]#	3401.31	-10729.98	USB_OC[0]#	GPIO_S5[19]	-	-	-
C21	PCU_SPI_CS[1]#	2915.41	-11070.59	PCU_SPI_CS[1]#	GPIO_S5[21]	-	-	-
C22	PCU_SPI_CLK	2429.51	-10729.98	PCU_SPI_CLK	-	-	-	-
C23	PCU_SPI_CS[0]#	1943.61	-11070.59	PCU_SPI_CS[0]#	-	-	-	-
C24	PROCHOT#	1457.71	-10729.98	PROCHOT#	-	-	-	-
C25	SVID_CLK	971.8	-11070.59	SVID_CLK	-	-	-	-
C26	DDIO_DDCDATA	479.81	-10715.24	RESERVED	RESERVED	DDIO_DDCDATA	-	-
C27	DDIO_BKLTEN	0	-11070.59	RESERVED	RESERVED	DDIO_BKLTEN	-	-
C28	DDIO_DDCCLK	-479.81	-10715.24	RESERVED	RESERVED	DDIO_DDCCLK	-	-
C29	RESERVED	-971.8	-11070.59	RESERVED	RESERVED	-	-	-
C30	RESERVED	-1457.71	-10729.98	MDSI_C_TE	-	-	-	-
C31	VSS	-1943.61	-11070.59	-	-	-	-	-
C32	DRAM0_DQ[09]	-2429.51	-10729.98	-	-	-	-	-
C33	DRAM0_DQ[12]	-2915.41	-11070.59	-	-	-	-	-
C34	VSS	-3401.31	-10729.98	-	-	-	-	-
C35	DRAM0_DQSP[1]	-3887.22	-11070.59	-	-	-	-	-
C36	DRAM0_DQ[10]	-4373.12	-10729.98	-	-	-	-	-
C37	DRAM0_DQ[14]	-4859.02	-11070.59	-	-	-	-	-
C38	DRAM0_DQ[21]	-5344.92	-10729.98	-	-	-	-	-
C39	VSS	-5830.82	-11070.59	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 5 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
C40	DRAM0_DQ[28]	-6316.73	-10729.98	-	-	-	-	-
C41	DRAM0_DQ[25]	-6802.63	-11070.59	-	-	-	-	-
C42	VSS	-7288.53	-10729.98	-	-	-	-	-
C43	DRAM0_DQSN[3]	-7774.43	-11070.59	-	-	-	-	-
C45	VSS	-8697.98	-11028.17	-	-	-	-	-
C47	DRAM0_CKE[0]	-9553.19	-10709.15	-	-	-	-	-
C49	VSS	-10579.86	-10642.85	-	-	-	-	-
C51	DRAM_VDD_S4	-11644.38	-10644.38	-	-	-	-	-
C53	VSS	-12814.05	-10773.16	-	-	-	-	-
D2	USB_HSIC1_STROBE	12237.72	-10631.68	-	-	-	-	-
D4	USB3_RXP[0]	11162.79	-10162.79	-	-	-	-	-
D6	USB_RCOMPO	10112.76	-10238.49	-	-	-	-	-
D10	ICLK_USB_TERM[1]	8307.32	-10168.38	-	-	-	-	-
D12	VSS	7316.72	-10137.14	-	-	-	-	-
D14	TAP_TCK	6326.12	-10136.63	TAP_TCK	-	-	-	-
D16	VSS	5335.52	-10136.63	-	-	-	-	-
D18	TAP_PRDY#	4388.36	-10136.63	TAP_PRDY#	-	-	-	-
D20	PMC_ACPRESENT	3386.07	-10136.63	PMC_ACPRESENT	-	-	-	-
D22	PMC_SLP_S3#	2438.91	-10136.63	PMC_SLP_S3#	-	-	-	-
D24	VSS	1448.31	-10136.63	-	-	-	-	-
D26	PMC_SUSPWRDNACK	462.79	-9994.65	PMC_SUSPWRDNACK	GPIO_S5[11]	-	-	-
D27	DDIO_HPD	0	-10365.99	RESERVED	RESERVED	DDIO_HPD	-	-
D28	MCSI_GPIO[02]	-462.79	-9994.65	RESERVED	MCSI_GPIO[02]	RESERVED	-	-
D30	VSS	-1448.31	-10136.63	-	-	-	-	-
D32	MCSI_GPIO[11]	-2438.91	-10136.63	RESERVED	MCSI_GPIO[11]	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 6 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
D34	MCSI_GPIO[05]	-3386.07	-10136.63	RESERVED	MCSI_GPIO[05]	RESERVED	-	-
D36	VSS	-4388.36	-10136.63	-	-	-	-	-
D38	VSS	-5335.52	-10136.63	-	-	-	-	-
D40	DRAM0_DQSP[2]	-6326.12	-10136.63	-	-	-	-	-
D42	DRAM0_DQ[23]	-7316.72	-10137.14	-	-	-	-	-
D44	DRAM_VDD_S4	-8307.32	-10168.38	-	-	-	-	-
D48	RESERVED	-10112.76	-10238.49	-	-	-	-	-
D50	DRAM0_MA[07]	-11162.79	-10162.79	-	-	-	-	-
D52	DRAM0_BS[2]	-12237.72	-10631.68	-	-	-	-	-
E1	VSS	12814.05	-10170.41	-	-	-	-	-
E2	USB_HSIC1_DATA	12222.48	-10038.33	-	-	-	-	-
E3	USB3_RXN[0]	11642.85	-9579.86	-	-	-	-	-
E8	VSS	9320.02	-9747	-	-	-	-	-
E19	VSS	3887.22	-9818.88	-	-	-	-	-
E35	VSS	-3887.22	-9818.88	-	-	-	-	-
E46	RESERVED	-9320.02	-9747	-	-	-	-	-
E51	DRAM0_MA[11]	-11642.85	-9579.86	-	-	-	-	-
E52	DRAM0_MA[09]	-12222.48	-10038.33	-	-	-	-	-
E53	VSS	-12814.05	-9992.11	-	-	-	-	-
F1	RESERVED	12814.05	-9446.51	-	-	-	-	-
F2	VSS	12220.7	-9444.99	-	-	-	-	-
F5	VSS	10565.13	-9301.73	-	-	-	-	-
F7	VSS	9712.2	-9301.73	-	-	-	-	-
F10	ICLK_USB_TERM[0]	8307.32	-9457.18	-	-	-	-	-
F12	TAP_TDI	7316.72	-9463.28	TAP_TDI	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 7 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
F14	TAP_TMS	6326.12	-9463.28	TAP_TMS	-	-	-	-
F16	TAP_PREQ#	5335.52	-9463.28	TAP_PREQ#	-	-	-	-
F18	GPIO_S5[13]	4362.2	-9463.28	RESERVED	GPIO_S5[13]	-	-	-
F19	VSS	3887.22	-9107.68	-	-	-	-	-
F20	PMC_PLTRST#	3412.24	-9463.28	PMC_PLTRST#	-	-	-	-
F22	PMC_SLP_S4#	2438.91	-9463.28	PMC_SLP_S4#	-	-	-	-
F24	VSS	1448.31	-9463.28	-	-	-	-	-
F26	PMC_WAKE_PCIE[0]#	525.02	-9404.35	PMC_WAKE_PCIE[0]#	GPIO_S5[15]	-	-	-
F27	VSS	0	-9107.68	-	-	-	-	-
F28	MCSI_GPIO[07]	-525.02	-9404.35	RESERVED	MCSI_GPIO[07]	RESERVED	-	-
F30	VSS	-1448.31	-9463.28	-	-	-	-	-
F32	MCSI_GPIO[06]	-2438.91	-9463.28	RESERVED	MCSI_GPIO[06]	RESERVED	-	-
F34	MCSI_GPIO[00]	-3412.24	-9463.28	RESERVED	MCSI_GPIO[00]	RESERVED	-	-
F35	VSS	-3887.22	-9107.68	-	-	-	-	-
F36	DRAM0_DQ[16]	-4362.2	-9463.28	-	-	-	-	-
F38	DRAM0_DM[2]	-5335.52	-9463.28	-	-	-	-	-
F40	DRAM0_DQSN[2]	-6326.12	-9463.28	-	-	-	-	-
F42	DRAM0_DQ[18]	-7316.72	-9463.28	-	-	-	-	-
F44	DRAM0_CKE[2]	-8307.32	-9457.18	-	-	-	-	-
F47	DRAM0_MA[12]	-9712.2	-9301.73	-	-	-	-	-
F49	DRAM_VDD_S4	-10565.13	-9301.73	-	-	-	-	-
F52	DRAM_VDD_S4	-12220.7	-9444.99	-	-	-	-	-
F53	DRAM_VDD_S4	-12814.05	-9293.61	-	-	-	-	-
G1	USB3DEV_V1P0_S3	12814.05	-8679.18	-	-	-	-	-
G2	USB_ULPI_CLK	12246.36	-8852.15	GPIO_S5[31]	USB_ULPI_CLK	RESERVED	RESERVED	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 8 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
G10	VSS	8307.32	-8763.76	-	-	-	-	-
G12	TAP_TRST#	7316.72	-8752.08	TAP_TRST#	-	-	-	-
G14	USB_DN[1]	6326.12	-8752.08	-	-	-	-	-
G16	TAP_TDO	5335.52	-8752.08	TAP_TDO	-	-	-	-
G18	PMC_SUS_STAT#	4362.2	-8752.08	PMC_SUS_STAT#	GPIO_S5[18]	-	-	-
G20	VSS	3412.24	-8752.08	-	-	-	-	-
G22	VSS	2438.91	-8752.08	-	-	-	-	-
G24	PMC_SUSCLK[0]	1448.31	-8752.08	PMC_SUSCLK[0]	GPIO_S5[12]	-	-	-
G26	VSS	474.98	-8752.08	-	-	-	-	-
G28	VSS	-474.98	-8752.08	-	-	-	-	-
G30	DDI1_DDCCLK	-1448.31	-8752.08	RESERVED	RESERVED	DDI1_DDCCLK	-	-
G32	VSS	-2438.91	-8752.08	-	-	-	-	-
G34	VSS	-3412.24	-8752.08	-	-	-	-	-
G36	DRAM0_DM[0]	-4362.2	-8752.08	-	-	-	-	-
G38	DRAM0_DQ[17]	-5335.52	-8752.08	-	-	-	-	-
G40	DRAM0_DQ[20]	-6326.12	-8752.08	-	-	-	-	-
G42	VSS	-7316.72	-8752.08	-	-	-	-	-
G44	DRAM0_DQ[22]	-8307.32	-8763.76	-	-	-	-	-
G52	DRAM0_MA[08]	-12246.36	-8852.15	-	-	-	-	-
G53	DRAM0_MA[05]	-12814.05	-8620.51	-	-	-	-	-
H3	USB_ULPI_STP	11928.86	-8350.76	GPIO_S5[42]	USB_ULPI_STP	RESERVED	RESERVED	-
H4	RESERVED	11257.79	-8307.32	-	-	-	-	-
H5	RESERVED	10546.59	-8307.32	-	-	-	-	-
H7	RESERVED	9835.39	-8307.32	-	-	-	-	-
H8	RESERVED	9124.19	-8307.32	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 9 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
H10	USB_DN[3]	8307.32	-8170.42	-	-	-	-	-
H19	VSS	3887.22	-8396.48	-	-	-	-	-
H27	VSS	0	-8396.48	-	-	-	-	-
H35	VSS	-3887.22	-8396.48	-	-	-	-	-
H44	DRAM0_MA[03]	-8307.32	-8170.42	-	-	-	-	-
H46	DRAM_VDD_S4	-9124.19	-8307.32	-	-	-	-	-
H47	DRAM0_MA[01]	-9835.39	-8307.32	-	-	-	-	-
H49	DRAM0_MA[06]	-10546.59	-8307.32	-	-	-	-	-
H50	DRAM0_MA[04]	-11257.79	-8307.32	-	-	-	-	-
H51	DRAM0_WE#	-11928.86	-8350.76	-	-	-	-	-
J1	VSS	12814.05	-7815.58	-	-	-	-	-
J3	USB_ULPI_DIR	12070.59	-7774.43	GPIO_S5[40]	USB_ULPI_DIR	RESERVED	RESERVED	-
J12	USB_DN[2]	7316.72	-8040.88	-	-	-	-	-
J14	USB_DP[1]	6326.12	-8040.88	-	-	-	-	-
J16	VSS	5335.52	-8040.88	-	-	-	-	-
J18	GPIO_S5[25]	4362.2	-8040.88	GPIO_S5[25]	RESERVED	RESERVED	RESERVED	RESERVED
J19	VSS	3887.22	-7685.28	-	-	-	-	-
J20	USB_ULPI_RST#	3412.24	-8040.88	RESERVED	GPIO_S5[14]	USB_ULPI_RST#	-	-
J22	VSS	2438.91	-8040.88	-	-	-	-	-
J24	GPIO_S5[17]	1448.31	-8040.88	RESERVED	GPIO_S5[17]	-	-	-
J26	PMC_PWRBTN#	474.98	-8040.88	PMC_PWRBTN#	GPIO_S5[16]	-	-	-
J27	VSS	0	-7685.28	-	-	-	-	-
J28	MCSI_GPIO[03]	-474.98	-8040.88	RESERVED	MCSI_GPIO[03]	RESERVED	-	-
J30	DDI1_BKLTEN	-1448.31	-8040.88	RESERVED	RESERVED	DDI1_BKLTEN	-	-
J32	VSS	-2438.91	-8040.88	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 10 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
J34	MCSI_GPIO[09]	-3412.24	-8040.88	RESERVED	MCSI_GPIO[09]	-	-	-
J35	VSS	-3887.22	-7685.28	-	-	-	-	-
J36	DRAM0_DQ[01]	-4362.2	-8040.88	-	-	-	-	-
J38	DRAM0_DQSP[0]	-5335.52	-8040.88	-	-	-	-	-
J40	VSS	-6326.12	-8040.88	-	-	-	-	-
J42	DRAM0_DQ[19]	-7316.72	-8040.88	-	-	-	-	-
J51	DRAM0_MA[13]	-12070.59	-7774.43	-	-	-	-	-
J53	VSS	-12814.05	-7774.43	-	-	-	-	-
K2	USB_ULPI_DATA[2]	12428.98	-7288.53	GPIO_S5[34]	USB_ULPI_DATA[2]	RESERVED	RESERVED	-
K3	USB_ULPI_DATA[3]	11729.97	-7288.53	GPIO_S5[35]	USB_ULPI_DATA[3]	RESERVED	RESERVED	-
K4	VSS	11137.14	-7316.72	-	-	-	-	-
K6	USB3_TXP[0]	10463.28	-7316.72	-	-	-	-	-
K7	USB3_TXN[0]	9752.08	-7316.72	-	-	-	-	-
K9	VSS	9040.88	-7316.72	-	-	-	-	-
K10	USB_DP[3]	8329.68	-7316.72	-	-	-	-	-
K12	USB_DP[2]	7316.72	-7339.58	-	-	-	-	-
K14	VSS	6326.12	-7329.68	-	-	-	-	-
K16	USB_DN[0]	5335.52	-7329.68	-	-	-	-	-
K18	GPIO_S5[27]	4362.2	-7329.68	GPIO_S5[27]	RESERVED	RESERVED	RESERVED	RESERVED
K20	GPIO_S5[28]	3412.24	-7329.68	GPIO_S5[28]	RESERVED	RESERVED	RESERVED	RESERVED
K22	VSS	2438.91	-7329.68	-	-	-	-	-
K24	GPIO_S5[22]	1448.31	-7329.68	GPIO_S5[22]	RESERVED	RESERVED	RESERVED	RESERVED
K26	PMC_BATLOW#	474.98	-7329.68	PMC_BATLOW#	-	-	-	-
K28	MCSI_GPIO[08]	-474.98	-7329.68	RESERVED	MCSI_GPIO[08]	RESERVED	-	-
K30	DDI1_HPD	-1448.31	-7329.68	RESERVED	RESERVED	DDI1_HPD	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 11 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
K32	VSS	-2438.91	-7329.68	-	-	-	-	-
K34	MCSI_GPIO[04]	-3412.24	-7329.68	RESERVED	MCSI_GPIO[04]	RESERVED	-	-
K36	VSS	-4362.2	-7329.68	-	-	-	-	-
K38	DRAM0_DQSN[0]	-5335.52	-7329.68	-	-	-	-	-
K40	DRAM0_DQ[06]	-6326.12	-7329.68	-	-	-	-	-
K42	DRAM0_DQ[07]	-7316.72	-7339.58	-	-	-	-	-
K44	DRAM0_BS[1]	-8329.68	-7316.72	-	-	-	-	-
K45	DRAM0_MA[00]	-9040.88	-7316.72	-	-	-	-	-
K47	DRAM0_BS[0]	-9752.08	-7316.72	-	-	-	-	-
K48	DRAM0_MA[10]	-10463.28	-7316.72	-	-	-	-	-
K50	VSS	-11137.14	-7316.72	-	-	-	-	-
K51	DRAM0_DQ[33]	-11729.97	-7288.53	-	-	-	-	-
K52	DRAM0_DQ[32]	-12428.98	-7288.53	-	-	-	-	-
L1	USB_ULPI_DATA[1]	12814.05	-6802.63	GPIO_S5[33]	USB_ULPI_DATA[1]	RESERVED	RESERVED	-
L3	USB_ULPI_DATA[7]	12070.59	-6802.63	GPIO_S5[39]	USB_ULPI_DATA[7]	RESERVED	RESERVED	-
L13	VSS	6750.56	-6914.9	-	-	-	-	-
L19	VSS	3887.22	-6974.08	-	-	-	-	-
L27	VSS	0	-6974.08	-	-	-	-	-
L35	VSS	-3887.22	-6974.08	-	-	-	-	-
L41	DRAM0_MA[02]	-6750.56	-6914.9	-	-	-	-	-
L51	DRAM0_DQ[36]	-12070.59	-6802.63	-	-	-	-	-
L53	DRAM0_DQ[37]	-12814.05	-6802.63	-	-	-	-	-
M2	USB_ULPI_DATA[4]	12428.98	-6316.73	GPIO_S5[36]	USB_ULPI_DATA[4]	RESERVED	RESERVED	-
M3	USB_ULPI_DATA[0]	11729.97	-6316.73	GPIO_S5[32]	USB_ULPI_DATA[0]	RESERVED	RESERVED	-
M4	USB3DEV_TXP[0]	11136.63	-6326.12	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 12 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
M6	USB3DEV_TXN[0]	10463.28	-6326.12	-	-	-	-	-
M7	USB3DEV_REXT[0]	9752.08	-6326.12	-	-	-	-	-
M9	RESERVED	9040.88	-6326.12	-	-	-	-	-
M10	RESERVED	8329.68	-6326.12	-	-	-	-	-
M12	USB3_REXT[0]	7618.48	-6326.12	-	-	-	-	-
M13	USB_PLL_MON	6907.28	-6326.12	-	-	-	-	-
M14	USB_V1P0_S3	6326.12	-6446.01	-	-	-	-	-
M16	USB_DP[0]	5335.52	-6618.48	-	-	-	-	-
M18	GPIO_S5[26]	4362.2	-6618.48	GPIO_S5[26]	RESERVED	RESERVED	RESERVED	RESERVED
M19	VSS	3887.22	-6262.88	-	-	-	-	-
M20	GPIO_S5[24]	3412.24	-6618.48	GPIO_S5[24]	RESERVED	RESERVED	RESERVED	RESERVED
M22	GPIO_S5[29]	2438.91	-6618.48	GPIO_S5[29]	RESERVED	RESERVED	RESERVED	RESERVED
M24	GPIO_S5[30]	1448.31	-6618.48	GPIO_S5[30]	RESERVED	RESERVED	RESERVED	RESERVED
M26	VSS	474.98	-6618.48	-	-	-	-	-
M27	VSS	0	-6262.88	-	-	-	-	-
M28	VSS	-474.98	-6618.48	-	-	-	-	-
M30	DDI1_BKLTCTL	-1448.31	-6618.48	RESERVED	RESERVED	DDI1_BKLTCTL	-	-
M32	MCSI_GPIO[01]	-2438.91	-6618.48	RESERVED	MCSI_GPIO[01]	RESERVED	-	-
M34	VSS	-3412.24	-6618.48	-	-	-	-	-
M35	VSS	-3887.22	-6262.88	-	-	-	-	-
M36	DRAM0_DQ[00]	-4362.2	-6618.48	-	-	-	-	-
M38	VSS	-5335.52	-6618.48	-	-	-	-	-
M40	DRAM0_DQ[03]	-6326.12	-6446.01	-	-	-	-	-
M41	DRAM_VDD_S4	-6907.28	-6326.12	-	-	-	-	-
M42	DRAM_VDD_S4	-7618.48	-6326.12	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 13 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
M44	DRAM0_CAS#	-8329.68	-6326.12	-	-	-	-	-
M45	DRAM0_RAS#	-9040.88	-6326.12	-	-	-	-	-
M47	VSS	-9752.08	-6326.12	-	-	-	-	-
M48	DRAM0_CKN[0]	-10463.28	-6326.12	-	-	-	-	-
M50	DRAM0_CKP[0]	-11136.63	-6326.12	-	-	-	-	-
M51	VSS	-11729.97	-6316.73	-	-	-	-	-
M52	DRAM0_DQSN[4]	-12428.98	-6316.73	-	-	-	-	-
N1	VSS	12814.05	-5830.82	-	-	-	-	-
N3	USB_ULPI_DATA[5]	12070.59	-5830.82	GPIO_S5[37]	USB_ULPI_DATA[5]	RESERVED	RESERVED	-
N16	VSS	5335.52	-5907.28	-	-	-	-	-
N18	USB_V3P3_G3	4362.2	-5907.28	-	-	-	-	-
N20	USB_V1P8_G3	3412.24	-5907.28	-	-	-	-	-
N22	PCU_V3P3_G3	2438.91	-5907.28	-	-	-	-	-
N24	GPIO_S5[23]	1448.31	-5907.28	GPIO_S5[23]	RESERVED	RESERVED	RESERVED	RESERVED
N26	GPIO_RCOMP	474.98	-5907.28	-	-	-	-	-
N28	CORE_VSS_SENSE	-474.98	-5907.28	-	-	-	-	-
N30	DDI1_VDDEN	-1448.31	-5907.28	RESERVED	RESERVED	DDI1_VDDEN	-	-
N32	MCSI_GPIO[10]	-2438.91	-5907.28	RESERVED	MCSI_GPIO[10]	-	-	-
N34	RESERVED	-3412.24	-5907.28	-	-	-	-	-
N36	DRAM0_DQ[05]	-4362.2	-5907.28	-	-	-	-	-
N38	VSS	-5335.52	-5907.28	-	-	-	-	-
N51	VSS	-12070.59	-5830.82	-	-	-	-	-
N53	DRAM0_DQSP[4]	-12814.05	-5830.82	-	-	-	-	-
P2	USB_ULPI_DATA[6]	12428.98	-5344.92	GPIO_S5[38]	USB_ULPI_DATA[6]	RESERVED	RESERVED	-
P3	USB_ULPI_NXT	11729.97	-5344.92	GPIO_S5[41]	USB_ULPI_NXT	RESERVED	RESERVED	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 14 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
P4	VSS	11136.63	-5335.52	-	-	-	-	-
P6	RESERVED	10463.28	-5335.52	-	-	-	-	-
P7	RESERVED	9752.08	-5335.52	-	-	-	-	-
P9	VSS	9040.88	-5335.52	-	-	-	-	-
P10	USB3DEV_RXP[0]	8329.68	-5335.52	-	-	-	-	-
P12	USB3DEV_RXN[0]	7618.48	-5335.52	-	-	-	-	-
P13	VSS	6907.28	-5335.52	-	-	-	-	-
P14	MCSI_RCOMP	6304.79	-5335.52	-	-	-	-	-
P16	VSS	5335.52	-5196.08	-	-	-	-	-
P18	USB_V3P3_G3	4362.2	-5196.08	-	-	-	-	-
P19	VSS	3887.22	-5551.68	-	-	-	-	-
P20	VSS	3412.24	-5196.08	-	-	-	-	-
P22	RTC_VCC	2438.91	-5196.08	-	-	-	-	-
P24	VSS	1448.31	-5196.08	-	-	-	-	-
P26	CORE_VCC_S3	474.98	-5196.08	-	-	-	-	-
P27	CORE_VCC_S3	0	-5551.68	-	-	-	-	-
P28	CORE_VCC_SENSE	-474.98	-5196.08	-	-	-	-	-
P30	DDI1_DDCDATA	-1448.31	-5196.08	RESERVED	RESERVED	DDI1_DDCDATA	-	-
P32	VSS	-2438.91	-5196.08	-	-	-	-	-
P34	RESERVED	-3412.24	-5196.08	-	-	-	-	-
P35	VSS	-3887.22	-5551.68	-	-	-	-	-
P36	DRAM0_DQ[04]	-4362.2	-5196.08	-	-	-	-	-
P38	VSS	-5335.52	-5196.08	-	-	-	-	-
P40	DRAM0_DQ[02]	-6304.79	-5335.52	-	-	-	-	-
P41	DRAM0_DRAMRST#	-6907.28	-5335.52	-	-	-	-	-



Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 15 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
P42	DRAM0_ODT[2]	-7618.48	-5335.52	-	-	-	-	-
P44	DRAM0_CS[0]#	-8329.68	-5335.52	-	-	-	-	-
P45	DRAM0_CS[2]#	-9040.88	-5335.52	-	-	-	-	-
P47	VSS	-9752.08	-5335.52	-	-	-	-	-
P48	DRAM0_CKN[2]	-10463.28	-5335.52	-	-	-	-	-
P50	DRAM0_CKP[2]	-11136.63	-5335.52	-	-	-	-	-
P51	DRAM0_DM[4]	-11729.97	-5344.92	-	-	-	-	-
P52	VSS	-12428.98	-5344.92	-	-	-	-	-
R1	RESERVED	12814.05	-4859.02	-	-	-	-	-
R3	RESERVED	12070.59	-4859.02	-	-	-	-	-
R51	DRAM0_DQ[38]	-12070.59	-4859.02	-	-	-	-	-
R53	DRAM0_DQ[39]	-12814.05	-4859.02	-	-	-	-	-
T2	RESERVED	12428.98	-4373.12	-	-	-	-	-
T3	RESERVED	11729.97	-4373.12	-	-	-	-	-
T4	MCSI3_CLKP	11136.63	-4388.36	-	-	-	-	-
T6	MCSI3_CLKN	10463.28	-4362.2	-	-	-	-	-
T7	MCSI1_CLKN	9752.08	-4362.2	-	-	-	-	-
T9	MCSI1_CLKP	9040.88	-4362.2	-	-	-	-	-
T10	MCSI1_DP[3]	8329.68	-4362.2	-	-	-	-	-
T12	MCSI1_DN[3]	7618.48	-4362.2	-	-	-	-	-
T13	MCSI2_DP[0]	6907.28	-4362.2	-	-	-	-	-
T14	MCSI2_DN[0]	6196.08	-4362.2	-	-	-	-	-
T40	VSS	-6196.08	-4362.2	-	-	-	-	-
T41	DRAM0_ODT[0]	-6907.28	-4362.2	-	-	-	-	-
T42	DRAM0_DQSP[5]	-7618.48	-4362.2	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 16 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
T44	DRAM0_DQSN[5]	-8329.68	-4362.2	-	-	-	-	-
T45	DRAM0_DQ[41]	-9040.88	-4362.2	-	-	-	-	-
T47	DRAM0_DQ[40]	-9752.08	-4362.2	-	-	-	-	-
T48	DRAM0_DQ[44]	-10463.28	-4362.2	-	-	-	-	-
T50	DRAM0_DQ[45]	-11136.63	-4388.36	-	-	-	-	-
T51	DRAM0_DQ[35]	-11729.97	-4373.12	-	-	-	-	-
T52	DRAM0_DQ[34]	-12428.98	-4373.12	-	-	-	-	-
U1	VSS	12814.05	-3887.22	-	-	-	-	-
U3	VSS	12070.59	-3887.22	-	-	-	-	-
U5	VSS	10818.88	-3887.22	-	-	-	-	-
U6	VSS	10107.68	-3887.22	-	-	-	-	-
U8	VSS	9396.48	-3887.22	-	-	-	-	-
U9	VSS	8685.28	-3887.22	-	-	-	-	-
U11	VSS	7974.08	-3887.22	-	-	-	-	-
U12	VSS	7262.88	-3887.22	-	-	-	-	-
U14	VSS	6551.68	-3887.22	-	-	-	-	-
U16	USB_VSSA	5307.33	-4313.94	-	-	-	-	-
U18	USB_V1P0_S3	4549.14	-4313.94	-	-	-	-	-
U19	USB_V1P0_S3	3790.95	-4313.94	-	-	-	-	-
U21	VSS	3032.76	-4313.94	-	-	-	-	-
U22	UNCORE_V1P0_G3	2274.57	-4313.94	-	-	-	-	-
U24	UNCORE_V1P8_G3	1516.38	-4313.94	-	-	-	-	-
U25	PMC_V1P8_G3	758.19	-4313.94	-	-	-	-	-
U27	CORE_VCC_S3	0	-4313.94	-	-	-	-	-
U29	CORE_VCC_S3	-758.19	-4313.94	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 17 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
U30	VSS	-1516.38	-4313.94	-	-	-	-	-
U32	VSS	-2274.57	-4313.94	-	-	-	-	-
U33	CORE_V1P05_S3	-3032.76	-4313.94	-	-	-	-	-
U35	CORE_V1P05_S3	-3790.95	-4313.94	-	-	-	-	-
U36	UNCORE_V1P35_S3_F4	-4549.14	-4313.94	-	-	-	-	-
U38	MIPI_V1P8_S3	-5307.33	-4313.94	-	-	-	-	-
U40	VSS	-6551.68	-3887.22	-	-	-	-	-
U42	VSS	-7262.88	-3887.22	-	-	-	-	-
U43	VSS	-7974.08	-3887.22	-	-	-	-	-
U45	VSS	-8685.28	-3887.22	-	-	-	-	-
U46	VSS	-9396.48	-3887.22	-	-	-	-	-
U48	VSS	-10107.68	-3887.22	-	-	-	-	-
U49	VSS	-10818.88	-3887.22	-	-	-	-	-
U51	VSS	-12070.59	-3887.22	-	-	-	-	-
U53	VSS	-12814.05	-3887.22	-	-	-	-	-
V2	RESERVED	12428.98	-3401.31	-	-	-	-	-
V3	RESERVED	11729.97	-3401.31	-	-	-	-	-
V4	RESERVED	11136.63	-3386.07	-	-	-	-	-
V6	RESERVED	10463.28	-3412.24	-	-	-	-	-
V7	VSS	9752.08	-3412.24	-	-	-	-	-
V9	MCSI1_DP[2]	9040.88	-3412.24	-	-	-	-	-
V10	MCSI1_DN[2]	8329.68	-3412.24	-	-	-	-	-
V12	VSS	7618.48	-3412.24	-	-	-	-	-
V13	MCSI2_CLKP	6907.28	-3412.24	-	-	-	-	-
V14	MCSI2_CLKN	6196.08	-3412.24	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 18 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
V16	VSS	5307.33	-3529.58	-	-	-	-	-
V18	USB_HSIC_V1P24_G3	4549.14	-3529.58	-	-	-	-	-
V19	VSS	3790.95	-3529.58	-	-	-	-	-
V21	VSS	3032.76	-3529.58	-	-	-	-	-
V22	UNCORE_V1P0_G3	2274.57	-3529.58	-	-	-	-	-
V24	UNCORE_V1P0_S3	1516.38	-3529.58	-	-	-	-	-
V25	PCU_V1P8_G3	758.19	-3529.58	-	-	-	-	-
V27	CORE_VCC_S3	0	-3529.58	-	-	-	-	-
V29	CORE_VCC_S3	-758.19	-3529.58	-	-	-	-	-
V30	CORE_VCC_S3	-1516.38	-3529.58	-	-	-	-	-
V32	SVID_V1P0_S3	-2274.57	-3529.58	-	-	-	-	-
V33	CORE_V1P05_S3	-3032.76	-3529.58	-	-	-	-	-
V35	VSS	-3790.95	-3529.58	-	-	-	-	-
V36	UNCORE_V1P35_S3_F3	-4549.14	-3529.58	-	-	-	-	-
V38	DRAM_VDD_S4	-5307.33	-3529.58	-	-	-	-	-
V40	VSS	-6196.08	-3412.24	-	-	-	-	-
V41	DRAM0_DQ[43]	-6907.28	-3412.24	-	-	-	-	-
V42	DRAM0_DM[5]	-7618.48	-3412.24	-	-	-	-	-
V44	VSS	-8329.68	-3412.24	-	-	-	-	-
V45	DRAM0_DQ[48]	-9040.88	-3412.24	-	-	-	-	-
V47	DRAM0_DQ[49]	-9752.08	-3412.24	-	-	-	-	-
V48	DRAM0_DQ[52]	-10463.28	-3412.24	-	-	-	-	-
V50	DRAM0_DQ[53]	-11136.63	-3386.07	-	-	-	-	-
V51	VSS	-11729.97	-3401.31	-	-	-	-	-
V52	DRAM0_DQ[56]	-12428.98	-3401.31	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 19 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
W1	RESERVED	12814.05	-2915.41	-	-	-	-	-
W3	RESERVED	12070.59	-2915.41	-	-	-	-	-
W51	DRAM0_DQ[57]	-12070.59	-2915.41	-	-	-	-	-
W53	DRAM0_DQ[60]	-12814.05	-2915.41	-	-	-	-	-
Y2	RESERVED	12428.98	-2429.51	-	-	-	-	-
Y3	RESERVED	11729.97	-2429.51	-	-	-	-	-
Y4	RESERVED	11136.63	-2438.91	-	-	-	-	-
Y6	RESERVED	10463.28	-2438.91	-	-	-	-	-
Y7	VSS	9752.08	-2438.91	-	-	-	-	-
Y9	VSS	9040.88	-2438.91	-	-	-	-	-
Y10	VSS	8329.68	-2438.91	-	-	-	-	-
Y12	MCSI1_DN[1]	7618.48	-2438.91	-	-	-	-	-
Y13	MCSI1_DP[1]	6907.28	-2438.91	-	-	-	-	-
Y14	VSS	6196.08	-2438.91	-	-	-	-	-
Y16	VSS	5307.33	-2745.23	-	-	-	-	-
Y18	USB3DEV_V1P0_S3	4549.14	-2745.23	-	-	-	-	-
Y19	USB3_V1P0_G3	3790.95	-2745.23	-	-	-	-	-
Y21	VSS	3032.76	-2745.23	-	-	-	-	-
Y22	UNCORE_V1P0_S3	2274.57	-2745.23	-	-	-	-	-
Y24	UNCORE_V1P0_S3	1516.38	-2745.23	-	-	-	-	-
Y25	VSS	758.19	-2745.23	-	-	-	-	-
Y27	CORE_VCC_S3	0	-2745.23	-	-	-	-	-
Y29	CORE_VCC_S3	-758.19	-2745.23	-	-	-	-	-
Y30	CORE_VCC_S3	-1516.38	-2745.23	-	-	-	-	-
Y32	CORE_V1P05_S3	-2274.57	-2745.23	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 20 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
Y33	VSS	-3032.76	-2745.23	-	-	-	-	-
Y35	DRAM_V1P0_S3	-3790.95	-2745.23	-	-	-	-	-
Y36	DRAM_V1P0_S3	-4549.14	-2745.23	-	-	-	-	-
Y38	DRAM_VDD_S4	-5307.33	-2745.23	-	-	-	-	-
Y40	DRAM0_DQ[42]	-6196.08	-2438.91	-	-	-	-	-
Y41	VSS	-6907.28	-2438.91	-	-	-	-	-
Y42	DRAM0_DQ[46]	-7618.48	-2438.91	-	-	-	-	-
Y44	VSS	-8329.68	-2438.91	-	-	-	-	-
Y45	DRAM0_DQ[55]	-9040.88	-2438.91	-	-	-	-	-
Y47	DRAM0_DQSP[6]	-9752.08	-2438.91	-	-	-	-	-
Y48	DRAM0_DQSN[6]	-10463.28	-2438.91	-	-	-	-	-
Y50	DRAM0_DM[6]	-11136.63	-2438.91	-	-	-	-	-
Y51	DRAM0_DQ[61]	-11729.97	-2429.51	-	-	-	-	-
Y52	DRAM0_DM[7]	-12428.98	-2429.51	-	-	-	-	-
AA1	VSS	12814.05	-1943.61	-	-	-	-	-
AA3	VSS	12070.59	-1943.61	-	-	-	-	-
AA16	VSS	5307.33	-1960.88	-	-	-	-	-
AA18	USB_ULPI_V1P8_G3	4549.14	-1960.88	-	-	-	-	-
AA19	VSS	3790.95	-1960.88	-	-	-	-	-
AA21	VSS	3032.76	-1960.88	-	-	-	-	-
AA22	TP2_CORE_VCC_S3	2274.57	-1960.88	-	-	-	-	-
AA24	UNCORE_VNN_S3	1516.38	-1960.88	-	-	-	-	-
AA25	UNCORE_V1P35_S3_F5	758.19	-1960.88	-	-	-	-	-
AA27	CORE_VCC_S3	0	-1960.88	-	-	-	-	-
AA29	CORE_VCC_S3	-758.19	-1960.88	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 21 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AA30	CORE_VCC_S3	-1516.38	-1960.88	-	-	-	-	-
AA32	VSS	-2274.57	-1960.88	-	-	-	-	-
AA33	CORE_V1P05_S3	-3032.76	-1960.88	-	-	-	-	-
AA35	VSS	-3790.95	-1960.88	-	-	-	-	-
AA36	DRAM_V1P0_S3	-4549.14	-1960.88	-	-	-	-	-
AA38	VSS	-5307.33	-1960.88	-	-	-	-	-
AA51	DRAM0_DQSN[7]	-12070.59	-1943.61	-	-	-	-	-
AA53	VSS	-12814.05	-1943.61	-	-	-	-	-
AB2	RESERVED	12428.98	-1457.71	-	-	-	-	-
AB3	RESERVED	11729.97	-1457.71	-	-	-	-	-
AB4	VSS	11136.63	-1448.31	-	-	-	-	-
AB6	VSS	10463.28	-1448.31	-	-	-	-	-
AB7	RESERVED	9752.08	-1448.31	-	-	-	-	-
AB9	RESERVED	9040.88	-1448.31	-	-	-	-	-
AB10	VSS	8329.68	-1448.31	-	-	-	-	-
AB12	MCSI1_DP[0]	7618.48	-1448.31	-	-	-	-	-
AB13	MCSI1_DN[0]	6907.28	-1448.31	-	-	-	-	-
AB14	RESERVED	6196.08	-1448.31	-	-	-	-	-
AB40	DRAM0_DQ[47]	-6196.08	-1448.31	-	-	-	-	-
AB41	VSS	-6907.28	-1448.31	-	-	-	-	-
AB42	DRAM_CORE_PWROK	-7618.48	-1448.31	-	-	-	-	-
AB44	DRAM0_DQ[54]	-8329.68	-1448.31	-	-	-	-	-
AB45	VSS	-9040.88	-1448.31	-	-	-	-	-
AB47	VSS	-9752.08	-1448.31	-	-	-	-	-
AB48	VSS	-10463.28	-1448.31	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 22 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AB50	VSS	-11136.63	-1448.31	-	-	-	-	-
AB51	VSS	-11729.97	-1457.71	-	-	-	-	-
AB52	DRAM0_DQSP[7]	-12428.98	-1457.71	-	-	-	-	-
AC1	DDI1_TXN[3]	12814.05	-971.8	-	-	-	-	-
AC3	DDI1_TXP[3]	12070.59	-971.8	-	-	-	-	-
AC16	VSS	5307.33	-1176.53	-	-	-	-	-
AC18	VSS	4549.14	-1176.53	-	-	-	-	-
AC19	VSS	3790.95	-1176.53	-	-	-	-	-
AC21	VSS	3032.76	-1176.53	-	-	-	-	-
AC22	UNCORE_VNN_S3	2274.57	-1176.53	-	-	-	-	-
AC24	UNCORE_VNN_S3	1516.38	-1176.53	-	-	-	-	-
AC25	VSS	758.19	-1176.53	-	-	-	-	-
AC27	CORE_VCC_S3	0	-1176.53	-	-	-	-	-
AC29	CORE_VCC_S3	-758.19	-1176.53	-	-	-	-	-
AC30	CORE_VCC_S3	-1516.38	-1176.53	-	-	-	-	-
AC32	CORE_V1P05_S3	-2274.57	-1176.53	-	-	-	-	-
AC33	VSS	-3032.76	-1176.53	-	-	-	-	-
AC35	VSS	-3790.95	-1176.53	-	-	-	-	-
AC36	VSS	-4549.14	-1176.53	-	-	-	-	-
AC38	VSS	-5307.33	-1176.53	-	-	-	-	-
AC51	DRAM0_DQ[59]	-12070.59	-971.8	-	-	-	-	-
AC53	DRAM0_DQ[58]	-12814.05	-971.8	-	-	-	-	-
AD2	DDI1_TXN[2]	12428.98	-485.9	-	-	-	-	-
AD3	DDI1_TXP[2]	11715.24	-479.81	-	-	-	-	-
AD4	RESERVED	10994.64	-462.79	-	-	-	-	-



Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 23 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AD6	RESERVED	10404.35	-525.02	-	-	-	-	-
AD7	VSS	9752.08	-474.98	-	-	-	-	-
AD9	RESERVED	9040.88	-474.98	-	-	-	-	-
AD10	RESERVED	8329.68	-474.98	-	-	-	-	-
AD12	RESERVED	7618.48	-474.98	-	-	-	-	-
AD13	ICLK_RCOMP	6907.28	-474.98	-	-	-	-	-
AD14	ICLK_ICOMP	6196.08	-474.98	-	-	-	-	-
AD16	MIPI_V1P24_S3	5307.33	-392.18	-	-	-	-	-
AD18	MIPI_V1P24_S3	4549.14	-392.18	-	-	-	-	-
AD19	VSS	3790.95	-392.18	-	-	-	-	-
AD21	VSS	3032.76	-392.18	-	-	-	-	-
AD22	UNCORE_VNN_S3	2274.57	-392.18	-	-	-	-	-
AD24	UNCORE_VNN_S3	1516.38	-392.18	-	-	-	-	-
AD25	VSS	758.19	-392.18	-	-	-	-	-
AD27	CORE_VCC_S3	0	-392.18	-	-	-	-	-
AD29	CORE_VCC_S3	-758.19	-392.18	-	-	-	-	-
AD30	CORE_VCC_S3	-1516.38	-392.18	-	-	-	-	-
AD32	VSS	-2274.57	-392.18	-	-	-	-	-
AD33	VSS	-3032.76	-392.18	-	-	-	-	-
AD35	DRAM_V1P0_S3	-3790.95	-392.18	-	-	-	-	-
AD36	DRAM_V1P35_S3_F1	-4549.14	-392.18	-	-	-	-	-
AD38	DRAM_VDD_S4	-5307.33	-392.18	-	-	-	-	-
AD40	RESERVED	-6196.08	-474.98	-	-	-	-	-
AD41	RESERVED	-6907.28	-474.98	-	-	-	-	-
AD42	DRAM_VDD_S4_PWROK	-7618.48	-474.98	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 24 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AD44	DRAM_RCOMP[0]	-8329.68	-474.98	-	-	-	-	-
AD45	DRAM_RCOMP[2]	-9040.88	-474.98	-	-	-	-	-
AD47	VSS	-9752.08	-474.98	-	-	-	-	-
AD48	DRAM0_DQ[50]	-10404.35	-525.02	-	-	-	-	-
AD50	DRAM0_DQ[51]	-10994.64	-462.79	-	-	-	-	-
AD51	DRAM0_DQ[63]	-11715.24	-479.81	-	-	-	-	-
AD52	DRAM0_DQ[62]	-12428.98	-485.9	-	-	-	-	-
AE1	VSS	12814.05	0	-	-	-	-	-
AE3	VSS	12070.59	0	-	-	-	-	-
AE4	VSS	11365.99	0	-	-	-	-	-
AE6	VSS	10107.68	0	-	-	-	-	-
AE8	VSS	9396.48	0	-	-	-	-	-
AE9	VSS	8685.28	0	-	-	-	-	-
AE11	VSS	7974.08	0	-	-	-	-	-
AE12	VSS	7262.88	0	-	-	-	-	-
AE14	VSS	6551.68	0	-	-	-	-	-
AE40	VSS	-6551.68	0	-	-	-	-	-
AE42	VSS	-7262.88	0	-	-	-	-	-
AE43	VSS	-7974.08	0	-	-	-	-	-
AE45	VSS	-8685.28	0	-	-	-	-	-
AE46	VSS	-9396.48	0	-	-	-	-	-
AE48	VSS	-10107.68	0	-	-	-	-	-
AE50	VSS	-11365.99	0	-	-	-	-	-
AE51	VSS	-12070.59	0	-	-	-	-	-
AE53	VSS	-12814.05	0	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 25 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AF2	DDI1_TXN[1]	12428.98	485.9	-	-	-	-	-
AF3	DDI1_TXP[1]	11715.24	479.81	-	-	-	-	-
AF4	PCIE_CLKP[0]	10994.64	462.79	-	-	-	-	-
AF6	PCIE_CLKN[0]	10404.35	525.02	-	-	-	-	-
AF7	PCIE_CLKP[1]	9752.08	474.98	-	-	-	-	-
AF9	PCIE_CLKN[1]	9040.88	474.98	-	-	-	-	-
AF10	VSS	8329.68	474.98	-	-	-	-	-
AF12	VSS	7618.48	474.98	-	-	-	-	-
AF13	RESERVED	6907.28	474.98	-	-	-	-	-
AF14	RESERVED	6196.08	474.98	-	-	-	-	-
AF16	UNCORE_V1P0_S3	5307.33	392.18	-	-	-	-	-
AF18	UNCORE_V1P0_S3	4549.14	392.18	-	-	-	-	-
AF19	UNCORE_V1P35_S3_F6	3790.95	392.18	-	-	-	-	-
AF21	UNCORE_V1P0_S3	3032.76	392.18	-	-	-	-	-
AF22	UNCORE_VNN_S3	2274.57	392.18	-	-	-	-	-
AF24	UNCORE_VNN_S3	1516.38	392.18	-	-	-	-	-
AF25	VSS	758.19	392.18	-	-	-	-	-
AF27	CORE_VCC_S3	0	392.18	-	-	-	-	-
AF29	CORE_VCC_S3	-758.19	392.18	-	-	-	-	-
AF30	TP_CORE_V1P05_S4	-1516.38	392.18	-	-	-	-	-
AF32	VSS	-2274.57	392.18	-	-	-	-	-
AF33	CORE_V1P05_S3	-3032.76	392.18	-	-	-	-	-
AF35	DRAM_V1P0_S3	-3790.95	392.18	-	-	-	-	-
AF36	DRAM_V1P0_S3	-4549.14	392.18	-	-	-	-	-
AF38	DRAM_VDD_S4	-5307.33	392.18	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 26 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AF40	RESERVED	-6196.08	474.98	-	-	-	-	-
AF41	RESERVED	-6907.28	474.98	-	-	-	-	-
AF42	ICLK_DRAM_TERM[0]	-7618.48	474.98	-	-	-	-	-
AF44	DRAM_VREF	-8329.68	474.98	-	-	-	-	-
AF45	DRAM_RCOMP[1]	-9040.88	474.98	-	-	-	-	-
AF47	VSS	-9752.08	474.98	-	-	-	-	-
AF48	DRAM1_DQ[50]	-10404.35	525.02	-	-	-	-	-
AF50	DRAM1_DQ[51]	-10994.64	462.79	-	-	-	-	-
AF51	DRAM1_DQ[63]	-11715.24	479.81	-	-	-	-	-
AF52	DRAM1_DQ[62]	-12428.98	485.9	-	-	-	-	-
AG1	DDI1_TXN[0]	12814.05	971.8	-	-	-	-	-
AG3	DDI1_TXP[0]	12070.59	971.8	-	-	-	-	-
AG16	VSS	5307.33	1176.53	-	-	-	-	-
AG18	ICLK_V1P35_S3_F2	4549.14	1176.53	-	-	-	-	-
AG19	UNCORE_V1P35_S3_F1	3790.95	1176.53	-	-	-	-	-
AG21	UNCORE_V1P0_S3	3032.76	1176.53	-	-	-	-	-
AG22	UNCORE_VNN_S3	2274.57	1176.53	-	-	-	-	-
AG24	UNCORE_VNN_S3	1516.38	1176.53	-	-	-	-	-
AG25	VSS	758.19	1176.53	-	-	-	-	-
AG27	CORE_VCC_S3	0	1176.53	-	-	-	-	-
AG29	CORE_VCC_S3	-758.19	1176.53	-	-	-	-	-
AG30	CORE_VCC_S3	-1516.38	1176.53	-	-	-	-	-
AG32	UNCORE_V1P35_S3_F2	-2274.57	1176.53	-	-	-	-	-
AG33	CORE_V1P05_S3	-3032.76	1176.53	-	-	-	-	-
AG35	CORE_V1P05_S3	-3790.95	1176.53	-	-	-	-	-



Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 27 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AG36	VSS	-4549.14	1176.53	-	-	-	-	-
AG38	VSS	-5307.33	1176.53	-	-	-	-	-
AG51	DRAM1_DQ[59]	-12070.59	971.8	-	-	-	-	-
AG53	DRAM1_DQ[58]	-12814.05	971.8	-	-	-	-	-
AH2	RSVD_GND[3]	12428.98	1457.71	-	-	-	-	-
AH3	RSVD_GND[2]	11729.97	1457.71	-	-	-	-	-
AH4	VSS	11136.63	1448.31	-	-	-	-	-
AH6	VSS	10463.28	1448.31	-	-	-	-	-
AH7	VSS	9752.08	1448.31	-	-	-	-	-
AH9	VSS	9040.88	1448.31	-	-	-	-	-
AH10	ICLK_OSCOUT	8329.68	1448.31	-	-	-	-	-
AH12	ICLK_OSCIN	7618.48	1448.31	-	-	-	-	-
AH13	RESERVED	6907.28	1448.31	-	-	-	-	-
AH14	RESERVED	6196.08	1448.31	-	-	-	-	-
AH40	DRAM1_DQ[47]	-6196.08	1448.31	-	-	-	-	-
AH41	VSS	-6907.28	1448.31	-	-	-	-	-
AH42	ICLK_DRAM_TERM[1]	-7618.48	1448.31	-	-	-	-	-
AH44	DRAM1_DQ[54]	-8329.68	1448.31	-	-	-	-	-
AH45	VSS	-9040.88	1448.31	-	-	-	-	-
AH47	VSS	-9752.08	1448.31	-	-	-	-	-
AH48	VSS	-10463.28	1448.31	-	-	-	-	-
AH50	VSS	-11136.63	1448.31	-	-	-	-	-
AH51	VSS	-11729.97	1457.71	-	-	-	-	-
AH52	DRAM1_DQSP[7]	-12428.98	1457.71	-	-	-	-	-
AJ1	VSS	12814.05	1943.61	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 28 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AJ3	VSS	12070.59	1943.61	-	-	-	-	-
AJ16	VSS	5307.33	1960.88	-	-	-	-	-
AJ18	DDI_V1P0_S3	4549.14	1960.88	-	-	-	-	-
AJ19	ICLK_V1P35_S3_F1	3790.95	1960.88	-	-	-	-	-
AJ21	VSS	3032.76	1960.88	-	-	-	-	-
AJ22	UNCORE_VNN_S3	2274.57	1960.88	-	-	-	-	-
AJ24	UNCORE_VNN_S3	1516.38	1960.88	-	-	-	-	-
AJ25	VSS	758.19	1960.88	-	-	-	-	-
AJ27	VSS	0	1960.88	-	-	-	-	-
AJ29	VSS	-758.19	1960.88	-	-	-	-	-
AJ30	VSS	-1516.38	1960.88	-	-	-	-	-
AJ32	VSS	-2274.57	1960.88	-	-	-	-	-
AJ33	VSS	-3032.76	1960.88	-	-	-	-	-
AJ35	VSS	-3790.95	1960.88	-	-	-	-	-
AJ36	DRAM_V1P0_S3	-4549.14	1960.88	-	-	-	-	-
AJ38	VSS	-5307.33	1960.88	-	-	-	-	-
AJ51	DRAM1_DQSN[7]	-12070.59	1943.61	-	-	-	-	-
AJ53	VSS	-12814.05	1943.61	-	-	-	-	-
AK2	DDI1_AUXN	12428.98	2429.51	-	-	-	-	-
AK3	DDI1_AUXP	11729.97	2429.51	-	-	-	-	-
AK4	PCIE_CLKN[2]	11136.63	2438.91	-	-	-	-	-
AK6	PCIE_CLKP[2]	10463.28	2438.91	-	-	-	-	-
AK7	RESERVED	9752.08	2438.91	-	-	-	-	-
AK9	RESERVED	9040.88	2438.91	-	-	-	-	-
AK10	VSS	8329.68	2438.91	-	-	-	-	-



Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 29 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AK12	DDI_RCOMP_P	7618.48	2438.91	-	-	-	-	-
AK13	DDI_RCOMP_N	6907.28	2438.91	-	-	-	-	-
AK14	VSS	6196.08	2438.91	-	-	-	-	-
AK16	VSS	5307.33	2745.23	-	-	-	-	-
AK18	PCIE_V1P0_S3	4549.14	2745.23	-	-	-	-	-
AK19	DDI_V1P0_S3	3790.95	2745.23	-	-	-	-	-
AK21	DDI_V1P0_S3	3032.76	2745.23	-	-	-	-	-
AK22	UNCORE_VNN_S3	2274.57	2745.23	-	-	-	-	-
AK24	UNCORE_VNN_S3	1516.38	2745.23	-	-	-	-	-
AK25	UNCORE_VNN_S3	758.19	2745.23	-	-	-	-	-
AK27	UNCORE_VNN_S3	0	2745.23	-	-	-	-	-
AK29	UNCORE_VNN_S3	-758.19	2745.23	-	-	-	-	-
AK30	UNCORE_VNN_S3	-1516.38	2745.23	-	-	-	-	-
AK32	UNCORE_VNN_S3	-2274.57	2745.23	-	-	-	-	-
AK33	VSS	-3032.76	2745.23	-	-	-	-	-
AK35	DRAM_V1P0_S3	-3790.95	2745.23	-	-	-	-	-
AK36	DRAM_V1P0_S3	-4549.14	2745.23	-	-	-	-	-
AK38	DRAM_VDD_S4	-5307.33	2745.23	-	-	-	-	-
AK40	DRAM1_DQ[42]	-6196.08	2438.91	-	-	-	-	-
AK41	VSS	-6907.28	2438.91	-	-	-	-	-
AK42	DRAM1_DQ[46]	-7618.48	2438.91	-	-	-	-	-
AK44	VSS	-8329.68	2438.91	-	-	-	-	-
AK45	DRAM1_DQ[55]	-9040.88	2438.91	-	-	-	-	-
AK47	DRAM1_DQSP[6]	-9752.08	2438.91	-	-	-	-	-
AK48	DRAM1_DQSN[6]	-10463.28	2438.91	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 30 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AK50	DRAM1_DM[6]	-11136.63	2438.91	-	-	-	-	-
AK51	DRAM1_DQ[61]	-11729.97	2429.51	-	-	-	-	-
AK52	DRAM1_DM[7]	-12428.98	2429.51	-	-	-	-	-
AL1	DDIO_AUXN	12814.05	2915.41	-	-	-	-	-
AL3	DDIO_AUXP	12070.59	2915.41	-	-	-	-	-
AL51	DRAM1_DQ[57]	-12070.59	2915.41	-	-	-	-	-
AL53	DRAM1_DQ[60]	-12814.05	2915.41	-	-	-	-	-
AM2	RSVD_GND[1]	12428.98	3401.31	-	-	-	-	-
AM3	RSVD_GND[0]	11729.97	3401.31	-	-	-	-	-
AM4	PCIE_CLKN[3]	11136.63	3386.07	-	-	-	-	-
AM6	PCIE_CLKP[3]	10463.28	3412.24	-	-	-	-	-
AM7	VSS	9752.08	3412.24	-	-	-	-	-
AM9	RESERVED	9040.88	3412.24	-	-	-	-	-
AM10	RESERVED	8329.68	3412.24	-	-	-	-	-
AM12	VSS	7618.48	3412.24	-	-	-	-	-
AM13	RESERVED	6907.28	3412.24	-	-	-	-	-
AM14	RESERVED	6196.08	3412.24	-	-	-	-	-
AM16	DDI_V1P0_S3	5307.33	3529.58	-	-	-	-	-
AM18	PCIE_V1P0_S3	4549.14	3529.58	-	-	-	-	-
AM19	VSS	3790.95	3529.58	-	-	-	-	-
AM21	PCIE_V1P0_S3	3032.76	3529.58	-	-	-	-	-
AM22	UNCORE_VNN_S3	2274.57	3529.58	-	-	-	-	-
AM24	VSS	1516.38	3529.58	-	-	-	-	-
AM25	VSS	758.19	3529.58	-	-	-	-	-
AM27	LPC_V1P8V3P3_S3	0	3529.58	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 31 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AM29	VSS	-758.19	3529.58	-	-	-	-	-
AM30	UNCORE_V1P8_S3	-1516.38	3529.58	-	-	-	-	-
AM32	HDA_LPE_V1P5V1P8_S3	-2274.57	3529.58	-	-	-	-	-
AM33	VSS	-3032.76	3529.58	-	-	-	-	-
AM35	VSS	-3790.95	3529.58	-	-	-	-	-
AM36	VSS	-4549.14	3529.58	-	-	-	-	-
AM38	DRAM_VDD_S4	-5307.33	3529.58	-	-	-	-	-
AM40	VSS	-6196.08	3412.24	-	-	-	-	-
AM41	DRAM1_DQ[43]	-6907.28	3412.24	-	-	-	-	-
AM42	DRAM1_DM[5]	-7618.48	3412.24	-	-	-	-	-
AM44	VSS	-8329.68	3412.24	-	-	-	-	-
AM45	DRAM1_DQ[48]	-9040.88	3412.24	-	-	-	-	-
AM47	DRAM1_DQ[49]	-9752.08	3412.24	-	-	-	-	-
AM48	DRAM1_DQ[52]	-10463.28	3412.24	-	-	-	-	-
AM50	DRAM1_DQ[53]	-11136.63	3386.07	-	-	-	-	-
AM51	VSS	-11729.97	3401.31	-	-	-	-	-
AM52	DRAM1_DQ[56]	-12428.98	3401.31	-	-	-	-	-
AN1	VSS	12814.05	3887.22	-	-	-	-	-
AN3	VSS	12070.59	3887.22	-	-	-	-	-
AN5	VSS	10818.88	3887.22	-	-	-	-	-
AN6	VSS	10107.68	3887.22	-	-	-	-	-
AN8	VSS	9396.48	3887.22	-	-	-	-	-
AN9	VSS	8685.28	3887.22	-	-	-	-	-
AN11	VSS	7974.08	3887.22	-	-	-	-	-
AN12	VSS	7262.88	3887.22	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 32 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AN14	VSS	6551.68	3887.22	-	-	-	-	-
AN16	VSSA	5307.33	4313.94	-	-	-	-	-
AN18	PCIE_SATA_V1P0_S3	4549.14	4313.94	-	-	-	-	-
AN19	SATA_V1P0_S3	3790.95	4313.94	-	-	-	-	-
AN21	PCIE_V1P0_S3	3032.76	4313.94	-	-	-	-	-
AN22	VSS	2274.57	4313.94	-	-	-	-	-
AN24	VGA_V3P3_S3	1516.38	4313.94	-	-	-	-	-
AN25	GPIO_V1P0_S3	758.19	4313.94	-	-	-	-	-
AN27	SD3_V1P8V3P3_S3	0	4313.94	-	-	-	-	-
AN29	UNCORE_V1P0_S3	-758.19	4313.94	-	-	-	-	-
AN30	UNCORE_V1P0_S3	-1516.38	4313.94	-	-	-	-	-
AN32	UNCORE_V1P8_S3	-2274.57	4313.94	-	-	-	-	-
AN33	VSS	-3032.76	4313.94	-	-	-	-	-
AN35	VSS	-3790.95	4313.94	-	-	-	-	-
AN36	VSS	-4549.14	4313.94	-	-	-	-	-
AN38	VSS	-5307.33	4313.94	-	-	-	-	-
AN40	VSS	-6551.68	3887.22	-	-	-	-	-
AN42	VSS	-7262.88	3887.22	-	-	-	-	-
AN43	VSS	-7974.08	3887.22	-	-	-	-	-
AN45	VSS	-8685.28	3887.22	-	-	-	-	-
AN46	VSS	-9396.48	3887.22	-	-	-	-	-
AN48	VSS	-10107.68	3887.22	-	-	-	-	-
AN49	VSS	-10818.88	3887.22	-	-	-	-	-
AN51	VSS	-12070.59	3887.22	-	-	-	-	-
AN53	VSS	-12814.05	3887.22	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 33 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AP2	DDIO_TXN[3]	12428.98	4373.12	-	-	-	-	-
AP3	DDIO_TXP[3]	11729.97	4373.12	-	-	-	-	-
AP4	PCIE_TXN[3]	11136.63	4388.36	-	-	-	-	-
AP6	PCIE_TXP[3]	10463.28	4362.2	-	-	-	-	-
AP7	PCIE_RXN[3]	9752.08	4362.2	-	-	-	-	-
AP9	PCIE_RXP[3]	9040.88	4362.2	-	-	-	-	-
AP10	PCIE_RXN[2]	8329.68	4362.2	-	-	-	-	-
AP12	PCIE_RXP[2]	7618.48	4362.2	-	-	-	-	-
AP13	PCIE_RCOMP_N	6907.28	4362.2	-	-	-	-	-
AP14	PCIE_RCOMP_P	6196.08	4362.2	-	-	-	-	-
AP40	VSS	-6196.08	4362.2	-	-	-	-	-
AP41	DRAM1_ODT[0]	-6907.28	4362.2	-	-	-	-	-
AP42	DRAM1_DQSP[5]	-7618.48	4362.2	-	-	-	-	-
AP44	DRAM1_DQSN[5]	-8329.68	4362.2	-	-	-	-	-
AP45	DRAM1_DQ[41]	-9040.88	4362.2	-	-	-	-	-
AP47	DRAM1_DQ[40]	-9752.08	4362.2	-	-	-	-	-
AP48	DRAM1_DQ[44]	-10463.28	4362.2	-	-	-	-	-
AP50	DRAM1_DQ[45]	-11136.63	4388.36	-	-	-	-	-
AP51	DRAM1_DQ[35]	-11729.97	4373.12	-	-	-	-	-
AP52	DRAM1_DQ[34]	-12428.98	4373.12	-	-	-	-	-
AR1	DDIO_TXN[2]	12814.05	4859.02	-	-	-	-	-
AR3	DDIO_TXP[2]	12070.59	4859.02	-	-	-	-	-
AR51	DRAM1_DQ[38]	-12070.59	4859.02	-	-	-	-	-
AR53	DRAM1_DQ[39]	-12814.05	4859.02	-	-	-	-	-
AT2	DDIO_TXP[1]	12428.98	5344.92	-	-	-	-	-



Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 34 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AT3	DDIO_TXN[1]	11729.97	5344.92	-	-	-	-	-
AT4	VSS	11136.63	5335.52	-	-	-	-	-
AT6	PCIE_TXN[2]	10463.28	5335.52	-	-	-	-	-
AT7	PCIE_TXP[2]	9752.08	5335.52	-	-	-	-	-
AT9	PCIE_RXN[1]	9040.88	5335.52	-	-	-	-	-
AT10	PCIE_RXP[1]	8329.68	5335.52	-	-	-	-	-
AT12	VSS	7618.48	5335.52	-	-	-	-	-
AT13	PCIE_RXN[0]	6907.28	5335.52	-	-	-	-	-
AT14	PCIE_RXP[0]	6304.79	5335.52	-	-	-	-	-
AT16	VSS	5335.52	5196.08	-	-	-	-	-
AT18	SATA_RCOMP_N	4362.2	5196.08	-	-	-	-	-
AT19	VSS	3887.22	5551.68	-	-	-	-	-
AT20	MMC1_D[3]	3412.24	5196.08	GPIO_S0_SC[020]	MMC1_D[3]	-	MMC1_45_D[3]	-
AT22	MMC1_CLK	2438.91	5196.08	GPIO_S0_SC[016]	MMC1_CLK	-	MMC1_45_CLK	-
AT24	VSS	1448.31	5196.08	-	-	-	-	-
AT26	MMC1_D[6]	474.98	5196.08	GPIO_S0_SC[023]	MMC1_D[6]	-	MMC1_45_D[6]	-
AT27	VSS	0	5551.68	-	-	-	-	-
AT28	SD3_D[0]	-474.98	5196.08	GPIO_S0_SC[034]	SD3_D[0]	-	-	-
AT30	VSS	-1448.31	5196.08	-	-	-	-	-
AT32	SIO_PWM[1]	-2438.91	5196.08	GPIO_S0_SC[095]	SIO_PWM[1]	-	-	-
AT34	RESERVED	-3412.24	5196.08	RESERVED	-	-	-	-
AT35	VSS	-3887.22	5551.68	-	-	-	-	-
AT36	DRAM1_DQ[17]	-4362.2	5196.08	-	-	-	-	-
AT38	VSS	-5335.52	5196.08	-	-	-	-	-
AT40	DRAM1_DQ[19]	-6304.79	5335.52	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 35 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AT41	DRAM1_DRAMRST#	-6907.28	5335.52	-	-	-	-	-
AT42	DRAM1_ODT[2]	-7618.48	5335.52	-	-	-	-	-
AT44	DRAM1_CS[0]#	-8329.68	5335.52	-	-	-	-	-
AT45	DRAM1_CS[2]#	-9040.88	5335.52	-	-	-	-	-
AT47	VSS	-9752.08	5335.52	-	-	-	-	-
AT48	DRAM1_CKN[2]	-10463.28	5335.52	-	-	-	-	-
AT50	DRAM1_CKP[2]	-11136.63	5335.52	-	-	-	-	-
AT51	DRAM1_DM[4]	-11729.97	5344.92	-	-	-	-	-
AT52	VSS	-12428.98	5344.92	-	-	-	-	-
AU1	VSS	12814.05	5830.82	-	-	-	-	-
AU3	VSS	12070.59	5830.82	-	-	-	-	-
AU16	SATA_RXP[0]	5335.52	5907.28	-	-	-	-	-
AU18	SATA_RCOMP_P	4362.2	5907.28	-	-	-	-	-
AU20	MMC1_D[7]	3412.24	5907.28	GPIO_S0_SC[024]	MMC1_D[7]	-	MMC1_45_D[7]	-
AU22	MMC1_D[1]	2438.91	5907.28	GPIO_S0_SC[018]	MMC1_D[1]	-	MMC1_45_D[1]	-
AU24	VSS	1448.31	5907.28	-	-	-	-	-
AU26	MMC1_D[5]	474.98	5907.28	GPIO_S0_SC[022]	MMC1_D[5]	-	MMC1_45_D[5]	-
AU28	SD3_D[2]	-474.98	5907.28	GPIO_S0_SC[036]	SD3_D[2]	-	-	-
AU30	VSS	-1448.31	5907.28	-	-	-	-	-
AU32	SIO_PWM[0]	-2438.91	5907.28	GPIO_S0_SC[094]	SIO_PWM[0]	-	-	-
AU34	SIO_UART1_RXD	-3412.24	5907.28	GPIO_S0_SC[070]	SIO_UART1_RXD	RESERVED	-	-
AU36	DRAM1_DQ[16]	-4362.2	5907.28	-	-	-	-	-
AU38	VSS	-5335.52	5907.28	-	-	-	-	-
AU51	VSS	-12070.59	5830.82	-	-	-	-	-
AU53	DRAM1_DQSP[4]	-12814.05	5830.82	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 36 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AV2	DDIO_TXN[0]	12428.98	6316.73	-	-	-	-	-
AV3	DDIO_TXP[0]	11729.97	6316.73	-	-	-	-	-
AV4	PCIE_TXN[1]	11136.63	6326.12	-	-	-	-	-
AV6	PCIE_TXP[1]	10463.28	6326.12	-	-	-	-	-
AV7	VSS	9752.08	6326.12	-	-	-	-	-
AV9	RESERVED	9040.88	6326.12	-	-	-	-	-
AV10	RESERVED	8329.68	6326.12	-	-	-	-	-
AV12	VSS	7618.48	6326.12	-	-	-	-	-
AV13	VSS	6907.28	6326.12	-	-	-	-	-
AV14	VSS	6326.12	6446.01	-	-	-	-	-
AV16	SATA_RXN[0]	5335.52	6618.48	-	-	-	-	-
AV18	VSS	4362.2	6618.48	-	-	-	-	-
AV19	VSS	3887.22	6262.88	-	-	-	-	-
AV20	MMC1_D[0]	3412.24	6618.48	GPIO_S0_SC[017]	MMC1_D[0]	-	MMC1_45_D[0]	-
AV22	MMC1_D[2]	2438.91	6618.48	GPIO_S0_SC[019]	MMC1_D[2]	-	MMC1_45_D[2]	-
AV24	VSS	1448.31	6618.48	-	-	-	-	-
AV26	MMC1_CMD	474.98	6618.48	GPIO_S0_SC[025]	MMC1_CMD	-	MMC1_45_CMD	-
AV27	VSS	0	6262.88	-	-	-	-	-
AV28	SD3_CMD	-474.98	6618.48	GPIO_S0_SC[039]	SD3_CMD	-	-	-
AV30	VSS	-1448.31	6618.48	-	-	-	-	-
AV32	SIO_SPI_CS#	-2438.91	6618.48	GPIO_S0_SC[066]	SIO_SPI_CS#	-	-	-
AV34	SIO_UART1_TXD	-3412.24	6618.48	GPIO_S0_SC[071]	SIO_UART1_TXD	RESERVED	-	-
AV35	VSS	-3887.22	6262.88	-	-	-	-	-
AV36	DRAM1_DQ[21]	-4362.2	6618.48	-	-	-	-	-
AV38	VSS	-5335.52	6618.48	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 37 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AV40	DRAM1_DQ[18]	-6326.12	6446.01	-	-	-	-	-
AV41	DRAM_VDD_S4	-6907.28	6326.12	-	-	-	-	-
AV42	DRAM_VDD_S4	-7618.48	6326.12	-	-	-	-	-
AV44	DRAM1_CAS#	-8329.68	6326.12	-	-	-	-	-
AV45	DRAM1_RAS#	-9040.88	6326.12	-	-	-	-	-
AV47	VSS	-9752.08	6326.12	-	-	-	-	-
AV48	DRAM1_CKN[0]	-10463.28	6326.12	-	-	-	-	-
AV50	DRAM1_CKP[0]	-11136.63	6326.12	-	-	-	-	-
AV51	VSS	-11729.97	6316.73	-	-	-	-	-
AV52	DRAM1_DQSN[4]	-12428.98	6316.73	-	-	-	-	-
AW1	VGA_IREF	12814.05	6802.63	-	-	-	-	-
AW3	VSS	12070.59	6802.63	-	-	-	-	-
AW13	VSS	6750.56	6914.9	-	-	-	-	-
AW19	VSS	3887.22	6974.08	-	-	-	-	-
AW27	VSS	0	6974.08	-	-	-	-	-
AW35	VSS	-3887.22	6974.08	-	-	-	-	-
AW41	DRAM1_MA[02]	-6750.56	6914.9	-	-	-	-	-
AW51	DRAM1_DQ[36]	-12070.59	6802.63	-	-	-	-	-
AW53	DRAM1_DQ[37]	-12814.05	6802.63	-	-	-	-	-
AY2	VGA_BLUE	12428.98	7288.53	-	-	-	-	-
AY3	VGA_IRTN	11729.97	7288.53	-	-	-	-	-
AY4	VSS	11137.14	7316.72	-	-	-	-	-
AY6	PCIE_TXN[0]	10463.28	7316.72	-	-	-	-	-
AY7	PCIE_TXP[0]	9752.08	7316.72	-	-	-	-	-
AY9	VSS	9040.88	7316.72	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 38 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
AY10	VSS	8329.68	7316.72	-	-	-	-	-
AY12	SATA_LED#	7316.72	7339.58	GPIO_S0_SC[002]	SATA_LED#	-	-	-
AY14	SATA_GP[1]	6326.12	7329.68	GPIO_S0_SC[001]	SATA_GP[1]	SATA_DEVSLP[0]	-	-
AY16	SATA_RXP[1]	5335.52	7329.68	-	-	-	-	-
AY18	MMC1_RCOMP	4362.2	7329.68	-	-	-	-	-
AY20	SD2_D[0]	3412.24	7329.68	GPIO_S0_SC[028]	SD2_D[0]	-	-	-
AY22	VSS	2438.91	7329.68	-	-	-	-	-
AY24	MMC1_D[4]	1448.31	7329.68	GPIO_S0_SC[021]	MMC1_D[4]	-	MMC1_45_D[4]	-
AY26	SD3_CLK	474.98	7329.68	GPIO_S0_SC[033]	SD3_CLK	-	-	-
AY28	SIO_SPI_MOSI	-474.98	7329.68	GPIO_S0_SC[068]	SIO_SPI_MOSI	-	-	-
AY30	SIO_SPI_CLK	-1448.31	7329.68	GPIO_S0_SC[069]	SIO_SPI_CLK	-	-	-
AY32	VSS	-2438.91	7329.68	-	-	-	-	-
AY34	SIO_UART1_CTS#	-3412.24	7329.68	GPIO_S0_SC[073]	SIO_UART1_CTS#	-	-	-
AY36	VSS	-4362.2	7329.68	-	-	-	-	-
AY38	DRAM1_DQSN[2]	-5335.52	7329.68	-	-	-	-	-
AY40	DRAM1_DQ[23]	-6326.12	7329.68	-	-	-	-	-
AY42	DRAM1_DQ[22]	-7316.72	7339.58	-	-	-	-	-
AY44	DRAM1_BS[1]	-8329.68	7316.72	-	-	-	-	-
AY45	DRAM1_MA[00]	-9040.88	7316.72	-	-	-	-	-
AY47	DRAM1_BS[0]	-9752.08	7316.72	-	-	-	-	-
AY48	DRAM1_MA[10]	-10463.28	7316.72	-	-	-	-	-
AY50	VSS	-11137.14	7316.72	-	-	-	-	-
AY51	DRAM1_DQ[33]	-11729.97	7288.53	-	-	-	-	-
AY52	DRAM1_DQ[32]	-12428.98	7288.53	-	-	-	-	-
BA1	VGA_GREEN	12814.05	7774.43	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 39 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BA3	VGA_RED	12070.59	7774.43	-	-	-	-	-
BA12	SATA_GP[0]	7316.72	8040.88	GPIO_S0_SC[000]	SATA_GP[0]	-	-	-
BA14	VSS	6326.12	8040.88	-	-	-	-	-
BA16	SATA_RXN[1]	5335.52	8040.88	-	-	-	-	-
BA18	SD2_CLK	4362.2	8040.88	GPIO_S0_SC[027]	SD2_CLK	-	-	-
BA19	VSS	3887.22	7685.28	-	-	-	-	-
BA20	SD2_D[2]	3412.24	8040.88	GPIO_S0_SC[030]	SD2_D[2]	-	-	-
BA22	VSS	2438.91	8040.88	-	-	-	-	-
BA24	MMC1_RST#	1448.31	8040.88	GPIO_S0_SC[026]	MMC1_RST#	SATA_DEVSLP[0]	MMC1_45_RST#	-
BA26	SD3_D[3]	474.98	8040.88	GPIO_S0_SC[037]	SD3_D[3]	-	-	-
BA27	VSS	0	7685.28	-	-	-	-	-
BA28	SIO_SPI_MISO	-474.98	8040.88	GPIO_S0_SC[067]	SIO_SPI_MISO	-	-	-
BA30	LPE_I2S2_FRM	-1448.31	8040.88	GPIO_S0_SC[063]	LPE_I2S2_FRM	RESERVED	-	-
BA32	VSS	-2438.91	8040.88	-	-	-	-	-
BA34	SIO_UART1_RTS#	-3412.24	8040.88	GPIO_S0_SC[072]	SIO_UART1_RTS#	-	-	-
BA35	VSS	-3887.22	7685.28	-	-	-	-	-
BA36	DRAM1_DQ[20]	-4362.2	8040.88	-	-	-	-	-
BA38	DRAM1_DQSP[2]	-5335.52	8040.88	-	-	-	-	-
BA40	VSS	-6326.12	8040.88	-	-	-	-	-
BA42	DRAM1_DQ[02]	-7316.72	8040.88	-	-	-	-	-
BA51	DRAM1_MA[13]	-12070.59	7774.43	-	-	-	-	-
BA53	VSS	-12814.05	7774.43	-	-	-	-	-
BB3	RESERVED	11928.86	8350.76	-	-	-	-	-
BB4	RESERVED	11257.79	8307.32	-	-	-	-	-
BB5	RSVD_GND[6]	10546.59	8307.32	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 40 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BB7	RSVD_GND[7]	9835.39	8307.32	-	-	-	-	-
BB8	UNCORE_VNN_SENSE	9124.19	8307.32	-	-	-	-	-
BB10	RSVD_GND[4]	8307.32	8170.42	-	-	-	-	-
BB19	VSS	3887.22	8396.48	-	-	-	-	-
BB27	VSS	0	8396.48	-	-	-	-	-
BB35	VSS	-3887.22	8396.48	-	-	-	-	-
BB44	DRAM1_MA[03]	-8307.32	8170.42	-	-	-	-	-
BB46	DRAM_VDD_S4	-9124.19	8307.32	-	-	-	-	-
BB47	DRAM1_MA[01]	-9835.39	8307.32	-	-	-	-	-
BB49	DRAM1_MA[06]	-10546.59	8307.32	-	-	-	-	-
BB50	DRAM1_MA[04]	-11257.79	8307.32	-	-	-	-	-
BB51	DRAM1_WE#	-11928.86	8350.76	-	-	-	-	-
BC1	VGA_DDCCLK	12814.05	8620.51	VGA_DDCCLK	-	-	-	-
BC2	VGA_DDCDATA	12246.36	8852.15	VGA_DDCDATA	-	-	-	-
BC10	RSVD_GND[5]	8307.32	8763.76	-	-	-	-	-
BC12	GPIO_S0_SC[056]	7316.72	8752.08	GPIO_S0_SC[056]	RESERVED	-	-	-
BC14	GPIO_S0_SC[058]	6326.12	8752.08	GPIO_S0_SC[058]	RESERVED	-	-	-
BC16	GPIO_S0_SC[061]	5335.52	8752.08	GPIO_S0_SC[061]	PCU_UART_RXD	-	-	-
BC18	SD2_CMD	4362.2	8752.08	GPIO_S0_SC[032]	SD2_CMD	-	-	-
BC20	VSS	3412.24	8752.08	-	-	-	-	-
BC22	VSS	2438.91	8752.08	-	-	-	-	-
BC24	SD3_CD#	1448.31	8752.08	GPIO_S0_SC[038]	SD3_CD#	-	-	-
BC26	VSS	474.98	8752.08	-	-	-	-	-
BC28	VSS	-474.98	8752.08	-	-	-	-	-
BC30	LPE_I2S2_DATAOUT	-1448.31	8752.08	GPIO_S0_SC[065]	LPE_I2S2_DATAOUT	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 41 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BC32	VSS	-2438.91	8752.08	-	-	-	-	-
BC34	VSS	-3412.24	8752.08	-	-	-	-	-
BC36	DRAM1_DM[2]	-4362.2	8752.08	-	-	-	-	-
BC38	DRAM1_DQ[04]	-5335.52	8752.08	-	-	-	-	-
BC40	DRAM1_DQ[01]	-6326.12	8752.08	-	-	-	-	-
BC42	VSS	-7316.72	8752.08	-	-	-	-	-
BC44	DRAM1_DQ[07]	-8307.32	8763.76	-	-	-	-	-
BC52	DRAM1_MA[08]	-12246.36	8852.15	-	-	-	-	-
BC53	DRAM1_MA[05]	-12814.05	8620.51	-	-	-	-	-
BD1	VGA_V1P35_S3_F1	12814.05	9293.61	-	-	-	-	-
BD2	VGA_HSYNC	12220.7	9444.99	VGA_HSYNC	-	-	-	-
BD5	SD3_WP	10565.13	9301.73	GPIO_S0_SC[007]	RESERVED	SD3_WP	-	-
BD7	PCIE_CLKREQ[1]#	9712.2	9301.73	GPIO_S0_SC[004]	PCIE_CLKREQ[1]#	-	-	-
BD10	SATA_TXP[1]	8307.32	9457.18	-	-	-	-	-
BD12	GPIO_S0_SC[055]	7316.72	9463.28	GPIO_S0_SC[055]	RESERVED	-	-	-
BD14	GPIO_S0_SC[057]	6326.12	9463.28	GPIO_S0_SC[057]	PCU_UART_TXD	-	-	-
BD16	GPIO_S0_SC[060]	5335.52	9463.28	GPIO_S0_SC[060]	RESERVED	-	-	-
BD18	SD2_D[3]_CD#	4362.2	9463.28	GPIO_S0_SC[031]	SD2_D[3]_CD#	-	-	-
BD19	VSS	3887.22	9107.68	-	-	-	-	-
BD20	SD2_D[1]	3412.24	9463.28	GPIO_S0_SC[029]	SD2_D[1]	-	-	-
BD22	SD3_PWREN#	2438.91	9463.28	GPIO_S0_SC[041]	SD3_PWREN#	-	-	-
BD24	VSS	1448.31	9463.28	-	-	-	-	-
BD26	SD3_D[1]	525.02	9404.35	GPIO_S0_SC[035]	SD3_D[1]	-	-	-
BD27	VSS	0	9107.68	-	-	-	-	-
BD28	LPE_I2S2_DATAIN	-525.02	9404.35	GPIO_S0_SC[064]	LPE_I2S2_DATAIN	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 42 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BD30	VSS	-1448.31	9463.28	-	-	-	-	-
BD32	SIO_UART2_RTS#	-2438.91	9463.28	GPIO_S0_SC[076]	SIO_UART2_RTS#	-	-	-
BD34	SIO_UART2_TXD	-3412.24	9463.28	GPIO_S0_SC[075]	SIO_UART2_TXD	-	-	-
BD35	VSS	-3887.22	9107.68	-	-	-	-	-
BD36	DRAM1_DQ[05]	-4362.2	9463.28	-	-	-	-	-
BD38	DRAM1_DM[0]	-5335.52	9463.28	-	-	-	-	-
BD40	DRAM1_DQSN[0]	-6326.12	9463.28	-	-	-	-	-
BD42	DRAM1_DQ[03]	-7316.72	9463.28	-	-	-	-	-
BD44	DRAM1_CKE[2]	-8307.32	9457.18	-	-	-	-	-
BD47	DRAM1_MA[12]	-9712.2	9301.73	-	-	-	-	-
BD49	DRAM_VDD_S4	-10565.13	9301.73	-	-	-	-	-
BD52	DRAM_VDD_S4	-12220.7	9444.99	-	-	-	-	-
BD53	DRAM_VDD_S4	-12814.05	9293.61	-	-	-	-	-
BE1	VSS	12814.05	9992.11	-	-	-	-	-
BE2	VSS	12222.48	10038.33	-	-	-	-	-
BE3	PCIE_CLKREQ[3]#	11642.85	9579.86	GPIO_S0_SC[006]	PCIE_CLKREQ[3]#	-	-	-
BE8	VSS	9320.02	9747	-	-	-	-	-
BE19	VSS	3887.22	9818.88	-	-	-	-	-
BE35	VSS	-3887.22	9818.88	-	-	-	-	-
BE46	RESERVED	-9320.02	9747	-	-	-	-	-
BE51	DRAM1_MA[11]	-11642.85	9579.86	-	-	-	-	-
BE52	DRAM1_MA[09]	-12222.48	10038.33	-	-	-	-	-
BE53	VSS	-12814.05	9992.11	-	-	-	-	-
BF2	VGA_VSYNC	12237.72	10631.68	VGA_VSYNC	-	-	-	-
BF4	VSS	11162.79	10162.79	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 43 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BF6	SATA_TXP[0]	10112.76	10238.49	-	-	-	-	-
BF10	SATA_TXN[1]	8307.32	10168.38	-	-	-	-	-
BF12	VSS	7316.72	10137.14	-	-	-	-	-
BF14	GPIO_S0_SC[059]	6326.12	10136.63	GPIO_S0_SC[059]	RESERVED	-	-	-
BF16	VSS	5335.52	10136.63	-	-	-	-	-
BF18	LPC_RCOMP	4388.36	10136.63	LPC_RCOMP	-	-	-	-
BF20	HDA_LPE_RCOMP	3386.07	10136.63	-	-	-	-	-
BF22	SD3_1P8EN	2438.91	10136.63	GPIO_S0_SC[040]	SD3_1P8EN	-	-	-
BF24	VSS	1448.31	10136.63	-	-	-	-	-
BF26	SD3_RCOMP	462.79	9994.65	-	-	-	-	-
BF27	SIO_I2C4_DATA	0	10365.99	GPIO_S0_SC[086]	SIO_I2C4_DATA	-	-	-
BF28	LPE_I2S2_CLK	-462.79	9994.65	GPIO_S0_SC[062]	LPE_I2S2_CLK	SATA_DEVSLEP[1]	RESERVED	-
BF30	VSS	-1448.31	10136.63	-	-	-	-	-
BF32	SIO_UART2_CTS#	-2438.91	10136.63	GPIO_S0_SC[077]	SIO_UART2_CTS#	-	-	-
BF34	SIO_UART2_RXD	-3386.07	10136.63	GPIO_S0_SC[074]	SIO_UART2_RXD	-	-	-
BF36	VSS	-4388.36	10136.63	-	-	-	-	-
BF38	VSS	-5335.52	10136.63	-	-	-	-	-
BF40	DRAM1_DQSP[0]	-6326.12	10136.63	-	-	-	-	-
BF42	DRAM1_DQ[06]	-7316.72	10137.14	-	-	-	-	-
BF44	DRAM_VDD_S4	-8307.32	10168.38	-	-	-	-	-
BF48	RESERVED	-10112.76	10238.49	-	-	-	-	-
BF50	DRAM1_MA[07]	-11162.79	10162.79	-	-	-	-	-
BF52	DRAM1_BS[2]	-12237.72	10631.68	-	-	-	-	-
BG1	VSS	12814.05	10773.16	-	-	-	-	-
BG3	PCIE_CLKREQ[0]#	11644.38	10644.38	GPIO_S0_SC[003]	PCIE_CLKREQ[0]#	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 44 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BG5	PCIE_CLKREQ[2]#	10579.86	10642.85	GPIO_S0_SC[005]	PCIE_CLKREQ[2]#	-	-	-
BG7	SATA_TXN[0]	9553.19	10709.15	-	-	-	-	-
BG9	PMC_RSTBTN#	8697.98	11028.17	PMC_RSTBTN#	-	-	-	-
BG11	PCU_SMB_ALERT#	7774.43	11070.59	GPIO_S0_SC[053]	PCU_SMB_ALERT#	-	-	-
BG12	PCU_SMB_DATA	7288.53	10729.98	GPIO_S0_SC[051]	PCU_SMB_DATA	-	-	-
BG13	ILB_LPC_SERIRQ	6802.63	11070.59	GPIO_S0_SC[050]	ILB_LPC_SERIRQ	-	-	-
BG14	ILB_LPC_AD[3]	6316.73	10729.98	GPIO_S0_SC[045]	ILB_LPC_AD[3]	-	-	-
BG15	ILB_LPC_CLK[0]	5830.82	11070.59	GPIO_S0_SC[047]	ILB_LPC_CLK[0]	-	-	-
BG16	ILB_LPC_CLKRUN#	5344.92	10729.98	GPIO_S0_SC[049]	ILB_LPC_CLKRUN#	-	-	-
BG17	ILB_LPC_FRAME#	4859.02	11070.59	GPIO_S0_SC[046]	ILB_LPC_FRAME#	-	-	-
BG18	GPIO_S0_SC[015]	4373.12	10729.98	GPIO_S0_SC[015]	I2S1_DATAIN	RESERVED	-	-
BG19	HDA_SDI[0]	3887.22	11070.59	GPIO_S0_SC[012]	I2S1_CLK	HDA_SDI[0]	-	-
BG20	HDA_SDO	3401.31	10729.98	GPIO_S0_SC[011]	I2S0_DATAIN	HDA_SDO	-	-
BG21	HDA_SDI[1]	2915.41	11070.59	GPIO_S0_SC[013]	I2S1_FRM	HDA_SDI[1]	-	-
BG22	HDA_RST#	2429.51	10729.98	GPIO_S0_SC[008]	I2S0_CLK	HDA_RST#	-	-
BG23	SIO_I2C0_CLK	1943.61	11070.59	GPIO_S0_SC[079]	SIO_I2C0_CLK	-	-	-
BG24	SIO_I2C1_DATA	1457.71	10729.98	GPIO_S0_SC[080]	SIO_I2C1_DATA	-	-	-
BG25	SIO_I2C2_DATA	971.8	11070.59	GPIO_S0_SC[082]	SIO_I2C2_DATA	-	-	-
BG26	SIO_I2C3_DATA	479.81	10715.24	GPIO_S0_SC[084]	SIO_I2C3_DATA	-	-	-
BG27	SIO_I2C4_CLK	0	11070.59	GPIO_S0_SC[087]	SIO_I2C4_CLK	-	-	-
BG28	SIO_I2C5_CLK	-479.81	10715.24	GPIO_S0_SC[089]	SIO_I2C5_CLK	-	-	-
BG29	SIO_I2C6_CLK	-971.8	11070.59	GPIO_S0_SC[091]	SIO_I2C6_CLK	SD3_WP	-	-
BG30	GPIO_S0_SC[093]	-1457.71	10729.98	RESERVED	GPIO_S0_SC[093]	-	-	-
BG31	VSS	-1943.61	11070.59	-	-	-	-	-
BG32	DRAM1_DQ[09]	-2429.51	10729.98	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 45 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BG33	DRAM1_DQ[12]	-2915.41	11070.59	-	-	-	-	-
BG34	VSS	-3401.31	10729.98	-	-	-	-	-
BG35	DRAM1_DQSP[1]	-3887.22	11070.59	-	-	-	-	-
BG36	DRAM1_DQ[10]	-4373.12	10729.98	-	-	-	-	-
BG37	DRAM1_DQ[14]	-4859.02	11070.59	-	-	-	-	-
BG38	DRAM1_DQ[00]	-5344.92	10729.98	-	-	-	-	-
BG39	VSS	-5830.82	11070.59	-	-	-	-	-
BG40	DRAM1_DQ[28]	-6316.73	10729.98	-	-	-	-	-
BG41	DRAM1_DQ[25]	-6802.63	11070.59	-	-	-	-	-
BG42	VSS	-7288.53	10729.98	-	-	-	-	-
BG43	DRAM1_DQSN[3]	-7774.43	11070.59	-	-	-	-	-
BG45	VSS	-8697.98	11028.17	-	-	-	-	-
BG47	DRAM1_CKE[0]	-9553.19	10709.15	-	-	-	-	-
BG49	VSS	-10579.86	10642.85	-	-	-	-	-
BG51	DRAM_VDD_S4	-11644.38	10644.38	-	-	-	-	-
BG53	VSS	-12814.05	10773.16	-	-	-	-	-
BH1	VSS	12814.05	11382.76	-	-	-	-	-
BH2	VSS	12225.02	11225.02	-	-	-	-	-
BH4	PMC_PLT_CLK[2]	11631.68	11237.72	GPIO_S0_SC[098]	PMC_PLT_CLK[2]	-	-	-
BH5	PMC_PLT_CLK[1]	11038.33	11222.48	GPIO_S0_SC[097]	PMC_PLT_CLK[1]	-	-	-
BH6	PMC_PLT_CLK[4]	10444.99	11220.7	GPIO_S0_SC[100]	PMC_PLT_CLK[4]	-	-	-
BH7	PMC_PLT_CLK[0]	9851.64	11229.59	GPIO_S0_SC[096]	PMC_PLT_CLK[0]	-	-	-
BH8	PMC_PLT_CLK[3]	9258.3	11224.26	GPIO_S0_SC[099]	PMC_PLT_CLK[3]	-	-	-
BH10	PCU_SMB_CLK	8260.33	11428.98	GPIO_S0_SC[052]	PCU_SMB_CLK	-	-	-
BH12	ILB_8254_SPKR	7288.53	11428.98	GPIO_S0_SC[054]	ILB_8254_SPKR	RESERVED	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 46 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BH14	ILB_LPC_CLK[1]	6316.73	11428.98	GPIO_S0_SC[048]	ILB_LPC_CLK[1]	-	-	-
BH16	ILB_LPC_AD[0]	5344.92	11428.98	GPIO_S0_SC[042]	ILB_LPC_AD[0]	-	-	-
BH18	GPIO_S0_SC[014]	4373.12	11428.98	GPIO_S0_SC[014]	I2S1_DATAOUT	RESERVED	-	-
BH20	HDA_SYNC	3401.31	11428.98	GPIO_S0_SC[009]	I2S0_FRM	HDA_SYNC	-	-
BH22	SIO_I2C0_DATA	2429.51	11428.98	GPIO_S0_SC[078]	SIO_I2C0_DATA	-	-	-
BH24	SIO_I2C1_CLK	1457.71	11428.98	GPIO_S0_SC[081]	SIO_I2C1_CLK	RESERVED	-	-
BH26	SIO_I2C3_CLK	485.9	11428.98	GPIO_S0_SC[085]	SIO_I2C3_CLK	-	-	-
BH28	SIO_I2C5_DATA	-485.9	11428.98	GPIO_S0_SC[088]	SIO_I2C5_DATA	-	-	-
BH30	GPIO_S0_SC[092]	-1457.71	11428.98	RESERVED	GPIO_S0_SC[092]	-	-	-
BH32	DRAM1_DQ[08]	-2429.51	11428.98	-	-	-	-	-
BH34	DRAM1_DQSN[1]	-3401.31	11428.98	-	-	-	-	-
BH36	DRAM1_DM[1]	-4373.12	11428.98	-	-	-	-	-
BH38	DRAM1_DQ[15]	-5344.92	11428.98	-	-	-	-	-
BH40	DRAM1_DQ[29]	-6316.73	11428.98	-	-	-	-	-
BH42	DRAM1_DM[3]	-7288.53	11428.98	-	-	-	-	-
BH44	DRAM1_DQSP[3]	-8260.33	11428.98	-	-	-	-	-
BH46	DRAM1_DQ[27]	-9258.3	11224.26	-	-	-	-	-
BH47	DRAM1_DQ[31]	-9851.64	11229.59	-	-	-	-	-
BH48	DRAM1_DQ[30]	-10444.99	11220.7	-	-	-	-	-
BH49	DRAM1_MA[14]	-11038.33	11222.48	-	-	-	-	-
BH50	DRAM1_MA[15]	-11631.68	11237.72	-	-	-	-	-
BH52	VSS	-12225.02	11225.02	-	-	-	-	-
BH53	VSS	-12814.05	11382.76	-	-	-	-	-
BJ2	VSS	12382.75	11814.05	-	-	-	-	-
BJ3	VSS	11773.15	11814.05	-	-	-	-	-



Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 47 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BJ5	VSS	10992.1	11814.05	-	-	-	-	-
BJ6	VGA_V1P0_S3	10293.6	11814.05	-	-	-	-	-
BJ7	VSS	9620.5	11814.05	-	-	-	-	-
BJ9	PMC_PLT_CLK[5]	8746.24	11814.05	GPIO_S0_SC[101]	PMC_PLT_CLK[5]	-	-	-
BJ11	VSS	7774.43	11814.05	-	-	-	-	-
BJ13	ILB_LPC_AD[2]	6802.63	11814.05	GPIO_S0_SC[044]	ILB_LPC_AD[2]	-	-	-
BJ15	VSS	5830.82	11814.05	-	-	-	-	-
BJ17	ILB_LPC_AD[1]	4859.02	11814.05	GPIO_S0_SC[043]	ILB_LPC_AD[1]	-	-	-
BJ19	VSS	3887.22	11814.05	-	-	-	-	-
BJ21	HDA_CLK	2915.41	11814.05	GPIO_S0_SC[010]	I2S0_DATAOUT	HDA_CLK	-	-
BJ23	VSS	1943.61	11814.05	-	-	-	-	-
BJ25	SIO_I2C2_CLK	971.8	11814.05	GPIO_S0_SC[083]	SIO_I2C2_CLK	-	-	-
BJ27	VSS	0	11814.05	-	-	-	-	-
BJ29	SIO_I2C6_DATA	-971.8	11814.05	GPIO_S0_SC[090]	SIO_I2C6_DATA	ILB_NMI	-	-
BJ31	VSS	-1943.61	11814.05	-	-	-	-	-
BJ33	DRAM1_DQ[13]	-2915.41	11814.05	-	-	-	-	-
BJ35	VSS	-3887.22	11814.05	-	-	-	-	-
BJ37	DRAM1_DQ[11]	-4859.02	11814.05	-	-	-	-	-
BJ39	VSS	-5830.82	11814.05	-	-	-	-	-
BJ41	DRAM1_DQ[24]	-6802.63	11814.05	-	-	-	-	-
BJ43	VSS	-7774.43	11814.05	-	-	-	-	-
BJ45	DRAM1_DQ[26]	-8746.24	11814.05	-	-	-	-	-
BJ47	VSS	-9620.5	11814.05	-	-	-	-	-
BJ48	DRAM_VDD_S4	-10293.6	11814.05	-	-	-	-	-




Table 149. Ball Listing by Location with GPIO Muxed Functions (Sheet 48 of 48)

Location	Ball Name	X-Location	Y-Location	GPIO F0	GPIO F1	GPIO F2	GPIO F3	GPIO F6
BJ49	VSS	-10992.1	11814.05	-	-	-	-	-
BJ51	VSS	-11773.15	11814.05	-	-	-	-	-
BJ52	VSS	-12382.75	11814.05	-	-	-	-	-



10.4 Alphabetical Ball Name List

Ball Name	Location	Ball Name	Location	Ball Name	Location
CORE_V1P05_S3	U33	DDIO_TXN[0]	AV2	DRAM0_CS[2]#	P45
CORE_V1P05_S3	U35	DDIO_TXN[1]	AT3	DRAM0_DM[0]	G36
CORE_V1P05_S3	V33	DDIO_TXN[2]	AR1	DRAM0_DM[1]	B36
CORE_V1P05_S3	Y32	DDIO_TXN[3]	AP2	DRAM0_DM[2]	F38
CORE_V1P05_S3	AA33	DDIO_TXP[0]	AV3	DRAM0_DM[3]	B42
CORE_V1P05_S3	AC32	DDIO_TXP[1]	AT2	DRAM0_DM[4]	P51
CORE_V1P05_S3	AF33	DDIO_TXP[2]	AR3	DRAM0_DM[5]	V42
CORE_V1P05_S3	AG33	DDIO_TXP[3]	AP3	DRAM0_DM[6]	Y50
CORE_V1P05_S3	AG35	DDIO_VDDEN	B28	DRAM0_DM[7]	Y52
CORE_VCC_S3	P26	DDI1_AUXN	AK2	DRAM0_DQ[00]	M36
CORE_VCC_S3	P27	DDI1_AUXP	AK3	DRAM0_DQ[01]	J36
CORE_VCC_S3	U27	DDI1_BKLTCTL	M30	DRAM0_DQ[02]	P40
CORE_VCC_S3	U29	DDI1_BKLTEN	J30	DRAM0_DQ[03]	M40
CORE_VCC_S3	V27	DDI1_DDCCLK	G30	DRAM0_DQ[04]	P36
CORE_VCC_S3	V29	DDI1_DDCDATA	P30	DRAM0_DQ[05]	N36
CORE_VCC_S3	V30	DDI1_HPD	K30	DRAM0_DQ[06]	K40
CORE_VCC_S3	Y27	DDI1_TXN[0]	AG1	DRAM0_DQ[07]	K42
CORE_VCC_S3	Y29	DDI1_TXN[1]	AF2	DRAM0_DQ[08]	B32
CORE_VCC_S3	Y30	DDI1_TXN[2]	AD2	DRAM0_DQ[09]	C32
CORE_VCC_S3	AA27	DDI1_TXN[3]	AC1	DRAM0_DQ[10]	C36
CORE_VCC_S3	AA29	DDI1_TXP[0]	AG3	DRAM0_DQ[11]	A37
CORE_VCC_S3	AA30	DDI1_TXP[1]	AF3	DRAM0_DQ[12]	C33
CORE_VCC_S3	AC27	DDI1_TXP[2]	AD3	DRAM0_DQ[13]	A33
CORE_VCC_S3	AC29	DDI1_TXP[3]	AC3	DRAM0_DQ[14]	C37
CORE_VCC_S3	AC30	DDI1_VDDEN	N30	DRAM0_DQ[15]	B38
CORE_VCC_S3	AD27	DDI_RCOMP_N	AK13	DRAM0_DQ[16]	F36
CORE_VCC_S3	AD29	DDI_RCOMP_P	AK12	DRAM0_DQ[17]	G38
CORE_VCC_S3	AD30	DDI_V1P0_S3	AJ18	DRAM0_DQ[18]	F42
CORE_VCC_S3	AF27	DDI_V1P0_S3	AK19	DRAM0_DQ[19]	J42
CORE_VCC_S3	AF29	DDI_V1P0_S3	AK21	DRAM0_DQ[20]	G40
CORE_VCC_S3	AG27	DDI_V1P0_S3	AM16	DRAM0_DQ[21]	C38
CORE_VCC_S3	AG29	DRAM0_BS[0]	K47	DRAM0_DQ[22]	G44
CORE_VCC_S3	AG30	DRAM0_BS[1]	K44	DRAM0_DQ[23]	D42
CORE_VCC_SENSE	P28	DRAM0_BS[2]	D52	DRAM0_DQ[24]	A41
CORE_VSS_SENSE	N28	DRAM0_CAS#	M44	DRAM0_DQ[25]	C41
DDIO_AUXN	AL1	DRAM0_CKE[0]	C47	DRAM0_DQ[26]	A45
DDIO_AUXP	AL3	DRAM0_CKE[2]	F44	DRAM0_DQ[27]	B46
DDIO_BKLTCTL	B26	DRAM0_CKN[0]	M48	DRAM0_DQ[28]	C40
DDIO_BKLTEN	C27	DRAM0_CKN[2]	P48	DRAM0_DQ[29]	B40
DDIO_DDCCLK	C28	DRAM0_CKP[0]	M50	DRAM0_DQ[30]	B48
DDIO_DDCDATA	C26	DRAM0_CKP[2]	P50	DRAM0_DQ[31]	B47
DDIO_HPD	D27	DRAM0_CS[0]#	P44	DRAM0_DQ[32]	K52



Ball Name	Location
DRAM0_DQ[33]	K51
DRAM0_DQ[34]	T52
DRAM0_DQ[35]	T51
DRAM0_DQ[36]	L51
DRAM0_DQ[37]	L53
DRAM0_DQ[38]	R51
DRAM0_DQ[39]	R53
DRAM0_DQ[40]	T47
DRAM0_DQ[41]	T45
DRAM0_DQ[42]	Y40
DRAM0_DQ[43]	V41
DRAM0_DQ[44]	T48
DRAM0_DQ[45]	T50
DRAM0_DQ[46]	Y42
DRAM0_DQ[47]	AB40
DRAM0_DQ[48]	V45
DRAM0_DQ[49]	V47
DRAM0_DQ[50]	AD48
DRAM0_DQ[51]	AD50
DRAM0_DQ[52]	V48
DRAM0_DQ[53]	V50
DRAM0_DQ[54]	AB44
DRAM0_DQ[55]	Y45
DRAM0_DQ[56]	V52
DRAM0_DQ[57]	W51
DRAM0_DQ[58]	AC53
DRAM0_DQ[59]	AC51
DRAM0_DQ[60]	W53
DRAM0_DQ[61]	Y51
DRAM0_DQ[62]	AD52
DRAM0_DQ[63]	AD51
DRAM0_DQSN[0]	K38
DRAM0_DQSN[1]	B34
DRAM0_DQSN[2]	F40
DRAM0_DQSN[3]	C43
DRAM0_DQSN[4]	M52
DRAM0_DQSN[5]	T44
DRAM0_DQSN[6]	Y48
DRAM0_DQSN[7]	AA51
DRAM0_DQSP[0]	J38
DRAM0_DQSP[1]	C35
DRAM0_DQSP[2]	D40
DRAM0_DQSP[3]	B44
DRAM0_DQSP[4]	N53

Ball Name	Location
DRAM0_DQSP[5]	T42
DRAM0_DQSP[6]	Y47
DRAM0_DQSP[7]	AB52
DRAM0_DRAMRST#	P41
DRAM0_MA[00]	K45
DRAM0_MA[01]	H47
DRAM0_MA[02]	L41
DRAM0_MA[03]	H44
DRAM0_MA[04]	H50
DRAM0_MA[05]	G53
DRAM0_MA[06]	H49
DRAM0_MA[07]	D50
DRAM0_MA[08]	G52
DRAM0_MA[09]	E52
DRAM0_MA[10]	K48
DRAM0_MA[11]	E51
DRAM0_MA[12]	F47
DRAM0_MA[13]	J51
DRAM0_MA[14]	B49
DRAM0_MA[15]	B50
DRAM0_ODT[0]	T41
DRAM0_ODT[2]	P42
DRAM0_RAS#	M45
DRAM0_WE#	H51
DRAM1_BS[0]	AY47
DRAM1_BS[1]	AY44
DRAM1_BS[2]	BF52
DRAM1_CAS#	AV44
DRAM1_CKE[0]	BG47
DRAM1_CKE[2]	BD44
DRAM1_CKN[0]	AV48
DRAM1_CKN[2]	AT48
DRAM1_CKP[0]	AV50
DRAM1_CKP[2]	AT50
DRAM1_CS[0]#	AT44
DRAM1_CS[2]#	AT45
DRAM1_DM[0]	BD38
DRAM1_DM[1]	BH36
DRAM1_DM[2]	BC36
DRAM1_DM[3]	BH42
DRAM1_DM[4]	AT51
DRAM1_DM[5]	AM42
DRAM1_DM[6]	AK50
DRAM1_DM[7]	AK52


Ball Name	Location
DRAM1_DQ[00]	BG38
DRAM1_DQ[01]	BC40
DRAM1_DQ[02]	BA42
DRAM1_DQ[03]	BD42
DRAM1_DQ[04]	BC38
DRAM1_DQ[05]	BD36
DRAM1_DQ[06]	BF42
DRAM1_DQ[07]	BC44
DRAM1_DQ[08]	BH32
DRAM1_DQ[09]	BG32
DRAM1_DQ[10]	BG36
DRAM1_DQ[11]	BJ37
DRAM1_DQ[12]	BG33
DRAM1_DQ[13]	BJ33
DRAM1_DQ[14]	BG37
DRAM1_DQ[15]	BH38
DRAM1_DQ[16]	AU36
DRAM1_DQ[17]	AT36
DRAM1_DQ[18]	AV40
DRAM1_DQ[19]	AT40
DRAM1_DQ[20]	BA36
DRAM1_DQ[21]	AV36
DRAM1_DQ[22]	AY42
DRAM1_DQ[23]	AY40
DRAM1_DQ[24]	BJ41
DRAM1_DQ[25]	BG41
DRAM1_DQ[26]	BJ45
DRAM1_DQ[27]	BH46
DRAM1_DQ[28]	BG40
DRAM1_DQ[29]	BH40
DRAM1_DQ[30]	BH48
DRAM1_DQ[31]	BH47
DRAM1_DQ[32]	AY52
DRAM1_DQ[33]	AY51
DRAM1_DQ[34]	AP52
DRAM1_DQ[35]	AP51
DRAM1_DQ[36]	AW51
DRAM1_DQ[37]	AW53
DRAM1_DQ[38]	AR51
DRAM1_DQ[39]	AR53
DRAM1_DQ[40]	AP47
DRAM1_DQ[41]	AP45
DRAM1_DQ[42]	AK40
DRAM1_DQ[43]	AM41



Ball Name	Location
DRAM1_DQ[44]	AP48
DRAM1_DQ[45]	AP50
DRAM1_DQ[46]	AK42
DRAM1_DQ[47]	AH40
DRAM1_DQ[48]	AM45
DRAM1_DQ[49]	AM47
DRAM1_DQ[50]	AF48
DRAM1_DQ[51]	AF50
DRAM1_DQ[52]	AM48
DRAM1_DQ[53]	AM50
DRAM1_DQ[54]	AH44
DRAM1_DQ[55]	AK45
DRAM1_DQ[56]	AM52
DRAM1_DQ[57]	AL51
DRAM1_DQ[58]	AG53
DRAM1_DQ[59]	AG51
DRAM1_DQ[60]	AL53
DRAM1_DQ[61]	AK51
DRAM1_DQ[62]	AF52
DRAM1_DQ[63]	AF51
DRAM1_DQSN[0]	BD40
DRAM1_DQSN[1]	BH34
DRAM1_DQSN[2]	AY38
DRAM1_DQSN[3]	BG43
DRAM1_DQSN[4]	AV52
DRAM1_DQSN[5]	AP44
DRAM1_DQSN[6]	AK48
DRAM1_DQSN[7]	AJ51
DRAM1_DQSP[0]	BF40
DRAM1_DQSP[1]	BG35
DRAM1_DQSP[2]	BA38
DRAM1_DQSP[3]	BH44
DRAM1_DQSP[4]	AU53
DRAM1_DQSP[5]	AP42
DRAM1_DQSP[6]	AK47
DRAM1_DQSP[7]	AH52
DRAM1_DRAMRST#	AT41
DRAM1_MA[00]	AY45
DRAM1_MA[01]	BB47
DRAM1_MA[02]	AW41
DRAM1_MA[03]	BB44
DRAM1_MA[04]	BB50
DRAM1_MA[05]	BC53
DRAM1_MA[06]	BB49

Ball Name	Location
DRAM1_MA[07]	BF50
DRAM1_MA[08]	BC52
DRAM1_MA[09]	BE52
DRAM1_MA[10]	AY48
DRAM1_MA[11]	BE51
DRAM1_MA[12]	BD47
DRAM1_MA[13]	BA51
DRAM1_MA[14]	BH49
DRAM1_MA[15]	BH50
DRAM1_ODT[0]	AP41
DRAM1_ODT[2]	AT42
DRAM1_RAS#	AV45
DRAM1_WE#	BB51
DRAM_CORE_PWROK	AB42
DRAM_RCOMP[0]	AD44
DRAM_RCOMP[1]	AF45
DRAM_RCOMP[2]	AD45
DRAM_V1P0_S3	Y35
DRAM_V1P0_S3	Y36
DRAM_V1P0_S3	AA36
DRAM_V1P0_S3	AD35
DRAM_V1P0_S3	AF35
DRAM_V1P0_S3	AF36
DRAM_V1P0_S3	AJ36
DRAM_V1P0_S3	AK35
DRAM_V1P0_S3	AK36
DRAM_V1P35_S3_F1	AD36
DRAM_VDD_S4	A48
DRAM_VDD_S4	C51
DRAM_VDD_S4	D44
DRAM_VDD_S4	F49
DRAM_VDD_S4	F52
DRAM_VDD_S4	F53
DRAM_VDD_S4	H46
DRAM_VDD_S4	M41
DRAM_VDD_S4	M42
DRAM_VDD_S4	V38
DRAM_VDD_S4	Y38
DRAM_VDD_S4	AD38
DRAM_VDD_S4	AF38
DRAM_VDD_S4	AK38
DRAM_VDD_S4	AM38
DRAM_VDD_S4	AV41
DRAM_VDD_S4	AV42

Ball Name	Location
DRAM_VDD_S4	BB46
DRAM_VDD_S4	BD49
DRAM_VDD_S4	BD52
DRAM_VDD_S4	BD53
DRAM_VDD_S4	BF44
DRAM_VDD_S4	BG51
DRAM_VDD_S4	BJ48
DRAM_VDD_S4_PWROK	AD42
DRAM_VREF	AF44
GPIO_RCOMP	N26
RESERVED	B30
GPIO_S0_SC[014]	BH18
GPIO_S0_SC[015]	BG18
GPIO_S0_SC[055]	BD12
GPIO_S0_SC[056]	BC12
GPIO_S0_SC[057]	BD14
GPIO_S0_SC[058]	BC14
GPIO_S0_SC[059]	BF14
GPIO_S0_SC[060]	BD16
GPIO_S0_SC[061]	BC16
GPIO_S0_SC[092]	BH30
GPIO_S0_SC[093]	BG30
GPIO_S5[00]	B18
GPIO_S5[01]	B16
GPIO_S5[02]	C18
GPIO_S5[03]	A17
GPIO_S5[04]	C17
GPIO_S5[05]	C16
GPIO_S5[06]	B14
GPIO_S5[07]	C15
GPIO_S5[08]	C13
GPIO_S5[09]	A13
GPIO_S5[10]	C19
GPIO_S5[13]	F18
GPIO_S5[17]	J24
GPIO_S5[22]	K24
GPIO_S5[23]	N24
GPIO_S5[24]	M20
GPIO_S5[25]	J18
GPIO_S5[26]	M18
GPIO_S5[27]	K18
GPIO_S5[28]	K20
GPIO_S5[29]	M22
GPIO_S5[30]	M24



Ball Name	Location
GPIO_V1P0_S3	AN25
HDA_CLK	BJ21
HDA_LPE_RCOMP	BF20
HDA_LPE_V1P5V1P8_S3	AM32
HDA_RST#	BG22
HDA_SDI[0]	BG19
HDA_SDI[1]	BG21
HDA_SDO	BG20
HDA_SYNC	BH20
ICLK_DRAM_TERM[0]	AF42
ICLK_DRAM_TERM[1]	AH42
ICLK_ICOMP	AD14
ICLK_OSCIN	AH12
ICLK_OSCOUT	AH10
ICLK_RCOMP	AD13
ICLK_USB_TERM[0]	F10
ICLK_USB_TERM[1]	D10
ICLK_V1P35_S3_F1	AJ19
ICLK_V1P35_S3_F2	AG18
ILB_8254_SPKR	BH12
ILB_LPC_AD[0]	BH16
ILB_LPC_AD[1]	BJ17
ILB_LPC_AD[2]	BJ13
ILB_LPC_AD[3]	BG14
ILB_LPC_CLK[0]	BG15
ILB_LPC_CLK[1]	BH14
ILB_LPC_CLKRUN#	BG16
ILB_LPC_FRAME#	BG17
ILB_LPC_SERIRQ	BG13
ILB_RTC_EXTPAD	B8
ILB_RTC_RST#	C12
ILB_RTC_TEST#	C11
ILB_RTC_X1	C9
ILB_RTC_X2	A9
LPC_RCOMP	BF18
LPC_V1P8V3P3_S3	AM27
LPE_I2S2_CLK	BF28
LPE_I2S2_DATAIN	BD28
LPE_I2S2_DATAOUT	BC30
LPE_I2S2_FRM	BA30
MCSI1_CLKN	T7
MCSI1_CLKP	T9
MCSI1_DN[0]	AB13
MCSI1_DN[1]	Y12

Ball Name	Location
MCSI1_DN[2]	V10
MCSI1_DN[3]	T12
MCSI1_DP[0]	AB12
MCSI1_DP[1]	Y13
MCSI1_DP[2]	V9
MCSI1_DP[3]	T10
MCSI2_CLKN	V14
MCSI2_CLKP	V13
MCSI2_DN[0]	T14
MCSI2_DP[0]	T13
MCSI3_CLKN	T6
MCSI3_CLKP	T4
MCSI_GPIO[00]	F34
MCSI_GPIO[01]	M32
MCSI_GPIO[02]	D28
MCSI_GPIO[03]	J28
MCSI_GPIO[04]	K34
MCSI_GPIO[05]	D34
MCSI_GPIO[06]	F32
MCSI_GPIO[07]	F28
MCSI_GPIO[08]	K28
MCSI_GPIO[09]	J34
MCSI_GPIO[10]	N32
MCSI_GPIO[11]	D32
MCSI_RCOMP	P14
MIPI_V1P8_S3	U38
MIPI_V1P24_S3	AD16
MIPI_V1P24_S3	AD18
MMC1_CLK	AT22
MMC1_CMD	AV26
MMC1_D[0]	AV20
MMC1_D[1]	AU22
MMC1_D[2]	AV22
MMC1_D[3]	AT20
MMC1_D[4]	AY24
MMC1_D[5]	AU26
MMC1_D[6]	AT26
MMC1_D[7]	AU20
MMC1_RCOMP	AY18
MMC1_RST#	BA24
PCIE_CLKN[0]	AF6
PCIE_CLKN[1]	AF9
PCIE_CLKN[2]	AK4
PCIE_CLKN[3]	AM4

Ball Name	Location
PCIE_CLKP[0]	AF4
PCIE_CLKP[1]	AF7
PCIE_CLKP[2]	AK6
PCIE_CLKP[3]	AM6
PCIE_CLKREQ[0]#	BG3
PCIE_CLKREQ[1]#	BD7
PCIE_CLKREQ[2]#	BG5
PCIE_CLKREQ[3]#	BE3
PCIE_RCOMP_N	AP13
PCIE_RCOMP_P	AP14
PCIE_RXN[0]	AT13
PCIE_RXN[1]	AT9
PCIE_RXN[2]	AP10
PCIE_RXN[3]	AP7
PCIE_RXP[0]	AT14
PCIE_RXP[1]	AT10
PCIE_RXP[2]	AP12
PCIE_RXP[3]	AP9
PCIE_SATA_V1P0_S3	AN18
PCIE_TXN[0]	AY6
PCIE_TXN[1]	AV4
PCIE_TXN[2]	AT6
PCIE_TXN[3]	AP4
PCIE_TXP[0]	AY7
PCIE_TXP[1]	AV6
PCIE_TXP[2]	AT7
PCIE_TXP[3]	AP6
PCIE_V1P0_S3	AK18
PCIE_V1P0_S3	AM18
PCIE_V1P0_S3	AM21
PCIE_V1P0_S3	AN21
PCU_SMB_ALERT#	BG11
PCU_SMB_CLK	BH10
PCU_SMB_DATA	BG12
PCU_SPI_CLK	C22
PCU_SPI_CS[0]#	C23
PCU_SPI_CS[1]#	C21
PCU_SPI_MISO	B22
PCU_SPI_MOSI	A21
PCU_V1P8_G3	V25
PCU_V3P3_G3	N22
PMC_ACPRESENT	D20
PMC_BATLOW#	K26
PMC_CORE_PWROK	B7



Ball Name	Location
PMC_PLT_CLK[0]	BH7
PMC_PLT_CLK[1]	BH5
PMC_PLT_CLK[2]	BH4
PMC_PLT_CLK[3]	BH8
PMC_PLT_CLK[4]	BH6
PMC_PLT_CLK[5]	BJ9
PMC_PLTRST#	F20
PMC_PWRBTN#	J26
PMC_RSMRST#	B10
PMC_RSTBTN#	BG9
PMC_SLP_S3#	D22
PMC_SLP_S4#	F22
PMC_SUS_STAT#	G18
PMC_SUSCLK[0]	G24
PMC_SUSPWRDNACK	D26
PMC_V1P8_G3	U25
PMC_WAKE_PCIE[0]#	F26
PROCHOT#	C24
RESERVED	A29
RESERVED	C29
RESERVED	C30
RESERVED	D48
RESERVED	E46
RESERVED	F1
RESERVED	H4
RESERVED	H5
RESERVED	H7
RESERVED	H8
RESERVED	M9
RESERVED	M10
RESERVED	N34
RESERVED	P6
RESERVED	P7
RESERVED	P34
RESERVED	R1
RESERVED	R3
RESERVED	T2
RESERVED	T3
RESERVED	V2
RESERVED	V3
RESERVED	V4
RESERVED	V6
RESERVED	W1
RESERVED	W3

Ball Name	Location
RESERVED	Y2
RESERVED	Y3
RESERVED	Y4
RESERVED	Y6
RESERVED	AB2
RESERVED	AB3
RESERVED	AB7
RESERVED	AB9
RESERVED	AB14
RESERVED	AD4
RESERVED	AD6
RESERVED	AD9
RESERVED	AD10
RESERVED	AD12
RESERVED	AD40
RESERVED	AD41
RESERVED	AF13
RESERVED	AF14
RESERVED	AF40
RESERVED	AF41
RESERVED	AH13
RESERVED	AH14
RESERVED	AK7
RESERVED	AK9
RESERVED	AM9
RESERVED	AM10
RESERVED	AM13
RESERVED	AM14
RESERVED	AT34
RESERVED	AV9
RESERVED	AV10
RESERVED	BB3
RESERVED	BB4
RESERVED	BE46
RESERVED	BF48
RSVD_GND[0]	AM3
RSVD_GND[1]	AM2
RSVD_GND[2]	AH3
RSVD_GND[3]	AH2
RSVD_GND[4]	BB10
RSVD_GND[5]	BC10
RSVD_GND[6]	BB5
RSVD_GND[7]	BB7
RTC_VCC	P22

Ball Name	Location
SATA_GP[0]	BA12
SATA_GP[1]	AY14
SATA_LED#	AY12
SATA_RCOMP_N	AT18
SATA_RCOMP_P	AU18
SATA_RXN[0]	AV16
SATA_RXN[1]	BA16
SATA_RXP[0]	AU16
SATA_RXP[1]	AY16
SATA_TXN[0]	BG7
SATA_TXN[1]	BF10
SATA_TXP[0]	BF6
SATA_TXP[1]	BD10
SATA_V1P0_S3	AN19
SD2_CLK	BA18
SD2_CMD	BC18
SD2_D[0]	AY20
SD2_D[1]	BD20
SD2_D[2]	BA20
SD2_D[3]_CD#	BD18
SD3_1P8EN	BF22
SD3_CD#	BC24
SD3_CLK	AY26
SD3_CMD	AV28
SD3_D[0]	AT28
SD3_D[1]	BD26
SD3_D[2]	AU28
SD3_D[3]	BA26
SD3_PWREN#	BD22
SD3_RCOMP	BF26
SD3_V1P8V3P3_S3	AN27
SD3_WP	BD5
SIO_I2C0_CLK	BG23
SIO_I2C0_DATA	BH22
SIO_I2C1_CLK	BH24
SIO_I2C1_DATA	BG24
SIO_I2C2_CLK	BJ25
SIO_I2C2_DATA	BG25
SIO_I2C3_CLK	BH26
SIO_I2C3_DATA	BG26
SIO_I2C4_CLK	BG27
SIO_I2C4_DATA	BF27
SIO_I2C5_CLK	BG28
SIO_I2C5_DATA	BH28



Ball Name	Location
SIO_I2C6_CLK	BG29
SIO_I2C6_DATA	BJ29
SIO_PWM[0]	AU32
SIO_PWM[1]	AT32
SIO_SPI_CLK	AY30
SIO_SPI_CS#	AV32
SIO_SPI_MISO	BA28
SIO_SPI_MOSI	AY28
SIO_UART1_CTS#	AY34
SIO_UART1_RTS#	BA34
SIO_UART1_RXD	AU34
SIO_UART1_TXD	AV34
SIO_UART2_CTS#	BF32
SIO_UART2_RTS#	BD32
SIO_UART2_RXD	BF34
SIO_UART2_TXD	BD34
SVID_ALERT#	B24
SVID_CLK	C25
SVID_DATA	A25
SVID_V1P0_S3	V32
TAP_PRDY#	D18
TAP_PREQ#	F16
TAP_TCK	D14
TAP_TDI	F12
TAP_TDO	G16
TAP_TMS	F14
TAP_TRST#	G12
TP2_CORE_VCC_S3	AA22
TP_CORE_V1P05_S4	AF30
UNCORE_V1P0_G3	B6
UNCORE_V1P0_G3	C5
UNCORE_V1P0_G3	U22
UNCORE_V1P0_G3	V22
UNCORE_V1P0_S3	V24
UNCORE_V1P0_S3	Y22
UNCORE_V1P0_S3	Y24
UNCORE_V1P0_S3	AF16
UNCORE_V1P0_S3	AF18
UNCORE_V1P0_S3	AF21
UNCORE_V1P0_S3	AG21
UNCORE_V1P0_S3	AN29
UNCORE_V1P0_S3	AN30
UNCORE_V1P8_G3	U24
UNCORE_V1P8_S3	AM30

Ball Name	Location
UNCORE_V1P8_S3	AN32
UNCORE_V1P35_S3_F1	AG19
UNCORE_V1P35_S3_F2	AG32
UNCORE_V1P35_S3_F3	V36
UNCORE_V1P35_S3_F4	U36
UNCORE_V1P35_S3_F5	AA25
UNCORE_V1P35_S3_F6	AF19
UNCORE_VNN_S3	AA24
UNCORE_VNN_S3	AC22
UNCORE_VNN_S3	AC24
UNCORE_VNN_S3	AD22
UNCORE_VNN_S3	AD24
UNCORE_VNN_S3	AF22
UNCORE_VNN_S3	AF24
UNCORE_VNN_S3	AG22
UNCORE_VNN_S3	AG24
UNCORE_VNN_S3	AJ22
UNCORE_VNN_S3	AJ24
UNCORE_VNN_S3	AK22
UNCORE_VNN_S3	AK24
UNCORE_VNN_S3	AK25
UNCORE_VNN_S3	AK27
UNCORE_VNN_S3	AK29
UNCORE_VNN_S3	AK30
UNCORE_VNN_S3	AK32
UNCORE_VNN_S3	AM22
UNCORE_VNN_SENSE	BB8
USB3_REXT[0]	M12
USB3_RXN[0]	E3
USB3_RXP[0]	D4
USB3_TXN[0]	K7
USB3_TXP[0]	K6
USB3_V1P0_G3	C3
USB3_V1P0_G3	Y19
USB_DN[0]	K16
USB_DN[1]	G14
USB_DN[2]	J12
USB_DN[3]	H10
USB_DP[0]	M16
USB_DP[1]	J14
USB_DP[2]	K12
USB_DP[3]	K10
USB_HSIC0_DATA	B4
USB_HSIC0_STROBE	B5

Ball Name	Location
USB_HSIC1_DATA	E2
USB_HSIC1_STROBE	D2
USB_HSIC_RCOMP	A7
USB_HSIC_V1P24_G3	V18
USB_OC[0]#	C20
USB_OC[1]#	B20
USB_PLL_MON	M13
USB_RCOMPI	C7
USB_RCOMPO	D6
USB_ULPI_CLK	G2
USB_ULPI_DATA[0]	M3
USB_ULPI_DATA[1]	L1
USB_ULPI_DATA[2]	K2
USB_ULPI_DATA[3]	K3
USB_ULPI_DATA[4]	M2
USB_ULPI_DATA[5]	N3
USB_ULPI_DATA[6]	P2
USB_ULPI_DATA[7]	L3
USB_ULPI_DIR	J3
USB_ULPI_NXT	P3
USB_ULPI_REFCLK	B12
USB_ULPI_RST#	J20
USB_ULPI_STP	H3
USB_ULPI_V1P8_G3	AA18
USB_V1P0_S3	M14
USB_V1P0_S3	U18
USB_V1P0_S3	U19
USB_V1P8_G3	N20
USB_V3P3_G3	N18
USB_V3P3_G3	P18
USB_VSSA	U16
USB3DEV_REXT[0]	M7
USB3DEV_RXN[0]	P12
USB3DEV_RXP[0]	P10
USB3DEV_TXN[0]	M6
USB3DEV_TXP[0]	M4
USB3DEV_V1P0_S3	G1
USB3DEV_V1P0_S3	Y18
VGA_BLUE	AY2
VGA_DDCCLK	BC1
VGA_DDCDATA	BC2
VGA_GREEN	BA1
VGA_HSYNC	BD2
VGA_IREF	AW1



Ball Name	Location
VGA_IRTN	AY3
VGA_RED	BA3
VGA_V1P0_S3	BJ6
VGA_V1P35_S3_F1	BD1
VGA_V3P3_S3	AN24
VGA_VSYNC	BF2
VSS	A3
VSS	A5
VSS	A6
VSS	A11
VSS	A15
VSS	A19
VSS	A23
VSS	A27
VSS	A31
VSS	A35
VSS	A39
VSS	A43
VSS	A47
VSS	A49
VSS	A51
VSS	A52
VSS	B2
VSS	B52
VSS	B53
VSS	C1
VSS	C14
VSS	C31
VSS	C34
VSS	C39
VSS	C42
VSS	C45
VSS	C49
VSS	C53
VSS	D12
VSS	D16
VSS	D24
VSS	D30
VSS	D36
VSS	D38
VSS	E1
VSS	E8
VSS	E19
VSS	E35

Ball Name	Location
VSS	E53
VSS	F2
VSS	F5
VSS	F7
VSS	F19
VSS	F24
VSS	F27
VSS	F30
VSS	F35
VSS	G10
VSS	G20
VSS	G22
VSS	G26
VSS	G28
VSS	G32
VSS	G34
VSS	G42
VSS	H19
VSS	H27
VSS	H35
VSS	J1
VSS	J16
VSS	J19
VSS	J22
VSS	J27
VSS	J32
VSS	J35
VSS	J40
VSS	J53
VSS	K4
VSS	K9
VSS	K14
VSS	K22
VSS	K32
VSS	K36
VSS	K50
VSS	L13
VSS	L19
VSS	L27
VSS	L35
VSS	M19
VSS	M26
VSS	M27
VSS	M28

Ball Name	Location
VSS	M34
VSS	M35
VSS	M38
VSS	M47
VSS	M51
VSS	N1
VSS	N16
VSS	N38
VSS	N51
VSS	P4
VSS	P9
VSS	P13
VSS	P16
VSS	P19
VSS	P20
VSS	P24
VSS	P32
VSS	P35
VSS	P38
VSS	P47
VSS	P52
VSS	T40
VSS	U1
VSS	U3
VSS	U5
VSS	U6
VSS	U8
VSS	U9
VSS	U11
VSS	U12
VSS	U14
VSS	U21
VSS	U30
VSS	U32
VSS	U40
VSS	U42
VSS	U43
VSS	U45
VSS	U46
VSS	U48
VSS	U49
VSS	U51
VSS	U53
VSS	V7



Ball Name	Location
VSS	V12
VSS	V16
VSS	V19
VSS	V21
VSS	V35
VSS	V40
VSS	V44
VSS	V51
VSS	Y7
VSS	Y9
VSS	Y10
VSS	Y14
VSS	Y16
VSS	Y21
VSS	Y25
VSS	Y33
VSS	Y41
VSS	Y44
VSS	AA1
VSS	AA3
VSS	AA16
VSS	AA19
VSS	AA21
VSS	AA32
VSS	AA35
VSS	AA38
VSS	AA53
VSS	AB4
VSS	AB6
VSS	AB10
VSS	AB41
VSS	AB45
VSS	AB47
VSS	AB48
VSS	AB50
VSS	AB51
VSS	AC16
VSS	AC18
VSS	AC19
VSS	AC21
VSS	AC25
VSS	AC33
VSS	AC35
VSS	AC36

Ball Name	Location
VSS	AC38
VSS	AD7
VSS	AD19
VSS	AD21
VSS	AD25
VSS	AD32
VSS	AD33
VSS	AD47
VSS	AE1
VSS	AE3
VSS	AE4
VSS	AE6
VSS	AE8
VSS	AE9
VSS	AE11
VSS	AE12
VSS	AE14
VSS	AE40
VSS	AE42
VSS	AE43
VSS	AE45
VSS	AE46
VSS	AE48
VSS	AE50
VSS	AE51
VSS	AE53
VSS	AF10
VSS	AF12
VSS	AF25
VSS	AF32
VSS	AF47
VSS	AG16
VSS	AG25
VSS	AG36
VSS	AG38
VSS	AH4
VSS	AH6
VSS	AH7
VSS	AH9
VSS	AH41
VSS	AH45
VSS	AH47
VSS	AH48
VSS	AH50

Ball Name	Location
VSS	AH51
VSS	AJ1
VSS	AJ3
VSS	AJ16
VSS	AJ21
VSS	AJ25
VSS	AJ27
VSS	AJ29
VSS	AJ30
VSS	AJ32
VSS	AJ33
VSS	AJ35
VSS	AJ38
VSS	AJ53
VSS	AK10
VSS	AK14
VSS	AK16
VSS	AK33
VSS	AK41
VSS	AK44
VSS	AM7
VSS	AM12
VSS	AM19
VSS	AM24
VSS	AM25
VSS	AM29
VSS	AM33
VSS	AM35
VSS	AM36
VSS	AM40
VSS	AM44
VSS	AM51
VSS	AN1
VSS	AN3
VSS	AN5
VSS	AN6
VSS	AN8
VSS	AN9
VSS	AN11
VSS	AN12
VSS	AN14
VSS	AN22
VSS	AN33
VSS	AN35



Ball Name	Location
VSS	AN36
VSS	AN38
VSS	AN40
VSS	AN42
VSS	AN43
VSS	AN45
VSS	AN46
VSS	AN48
VSS	AN49
VSS	AN51
VSS	AN53
VSS	AP40
VSS	AT4
VSS	AT12
VSS	AT16
VSS	AT19
VSS	AT24
VSS	AT27
VSS	AT30
VSS	AT35
VSS	AT38
VSS	AT47
VSS	AT52
VSS	AU1
VSS	AU3
VSS	AU24
VSS	AU30
VSS	AU38
VSS	AU51
VSS	AV7
VSS	AV12
VSS	AV13
VSS	AV14
VSS	AV18
VSS	AV19
VSS	AV24
VSS	AV27
VSS	AV30
VSS	AV35
VSS	AV38
VSS	AV47
VSS	AV51
VSS	AW3
VSS	AW13



Ball Name	Location
VSS	AW19
VSS	AW27
VSS	AW35
VSS	AY4
VSS	AY9
VSS	AY10
VSS	AY22
VSS	AY32
VSS	AY36
VSS	AY50
VSS	BA14
VSS	BA19
VSS	BA22
VSS	BA27
VSS	BA32
VSS	BA35
VSS	BA40
VSS	BA53
VSS	BB19
VSS	BB27
VSS	BB35
VSS	BC20
VSS	BC22
VSS	BC26
VSS	BC28
VSS	BC32
VSS	BC34
VSS	BC42
VSS	BD19
VSS	BD24
VSS	BD27
VSS	BD30
VSS	BD35
VSS	BE1
VSS	BE2
VSS	BE8
VSS	BE19
VSS	BE35
VSS	BE53
VSS	BF4
VSS	BF12
VSS	BF16
VSS	BF24
VSS	BF30




Ball Name	Location
VSS	BF36
VSS	BF38
VSS	BG1
VSS	BG31
VSS	BG34
VSS	BG39
VSS	BG42
VSS	BG45
VSS	BG49
VSS	BG53
VSS	BH1
VSS	BH2
VSS	BH52
VSS	BH53
VSS	BJ2
VSS	BJ3
VSS	BJ5
VSS	BJ7
VSS	BJ11
VSS	BJ15
VSS	BJ19
VSS	BJ23
VSS	BJ27
VSS	BJ31
VSS	BJ35
VSS	BJ39
VSS	BJ43
VSS	BJ47
VSS	BJ49
VSS	BJ51
VSS	BJ52
VSSA	AN16

§ §

11 Processor Core

Up to four out-of-order execution processor cores are supported, each dual core module supports up to 1 MiB of L2 cache.



11.1 Features

- Single, Dual or Quad Out-of-Order Execution (OOE) processor cores
- Primary 32 KiB, 8-way L1 instruction cache and 24 KiB, 6-way L1 write-back data cache
- Cores are grouped into dual-core modules: modules share a 1 MiB, 16-way L2 cache (2 MiB total for Quad Core)
 - Dual core SKU's use 512 KiB per core. Each core has a dedicated link to memory.
- L1 caches has Parity Protection and L2 cache has ECC Protection
- Intel® Streaming SIMD Extensions 4.1 and 4.2 (SSE4.1 and SSE4.2), which include new instructions for media and for fast XML parsing
- Intel® 64 architecture
- Support for IA 32-bit
- Support for Intel® VT-x
- Support for Intel® Carry-Less Multiplication Instruction (PCLMULQDQ)
- Support for a Digital Random Number Generator (via RDRAND instruction)
- Supports C0, C1, C6
- Thermal management support via Intel® Thermal Monitor (TM1 and TM2)
- Uses Power Aware Interrupt Routing (PAIR)
- Uses 22 nm process technology
- Real Time Instruction Trace for debug

- Supports RTIT

Note: Intel® Hyper-Threading Technology is not supported.

11.1.1 Intel® Virtualization Technology (Intel® VT)

Intel® Virtualization Technology (Intel® VT) makes a single system appear as multiple independent systems to software. This allows multiple, independent operating systems to run simultaneously on a single system. Intel® VT comprises technology components to support virtualization of platforms based on Intel architecture microprocessors and chipsets. Intel® Virtualization Technology for IA-32, Intel® 64 and Intel® Architecture (Intel® VT-x) added hardware support in the processor to improve the virtualization performance and robustness.

Intel® VT-x specifications and functional descriptions are included in the *Intel® 64 and IA-32 Architectures Software Developer's Manual, Volume 3B* and is available at: <http://www.intel.com/products/processor/manuals/index.htm>


Other Intel® VT documents can be referenced at: <http://www.intel.com/technology/virtualization/index.htm>

11.1.1.1 Intel® VT-x Objectives

- Robust: VMMs no longer need to use paravirtualization or binary translation. This means that they will be able to run off-the-shelf OSs and applications without any special steps.
- Enhanced: Intel® VT enables VMMs to run 64-bit guest operating systems on IA x86 processors.
- More reliable: Due to the hardware support, VMMs can now be smaller, less complex, and more efficient. This improves reliability and availability and reduces the potential for software conflicts.
- More secure: The use of hardware transitions in the VMM strengthens the isolation of VMs and further prevents corruption of one VM from affecting others on the same system. Intel® VT-x provides hardware acceleration for virtualization of IA platforms. Virtual Machine Monitor (VMM) can use Intel® VT-x features to provide improved reliable virtualized platform.

11.1.1.1.1 Intel® VT-x Features

- Extended Page Tables (EPT)
 - EPT is hardware assisted page table physical memory virtualization
 - Support guest VM execution in unpagged protected mode or in real-address mode
 - It eliminates VM exits from guest OS to the VMM for shadow page-table maintenance
- Virtual Processor IDs (VPID)



- A VM Virtual Processor ID is used to tag processor core hardware structures (such as TLBs) to allow a logic processor to cache information (such as TLBs) for multiple linear address spaces
- This avoids flushes on VM transitions to give a lower-cost VM transition time and an overall reduction in virtualization overhead
- Guest Preemption Timer
 - Mechanism for a VMM to preempt the execution of a guest OS VM after an amount of time specified by the VMM. The VMM sets a timer value before entering a guest.
 - The feature aids VMM developers in flexibility and Quality of Service (QoS) guarantees flexibility in guest VM scheduling and building Quality of Service (QoS) schemes
- Descriptor-Table Exiting
 - Descriptor-table exiting allows a VMM to protect a guest OS from internal (malicious software based) attack by preventing relocation of key system data structures like IDT (interrupt descriptor table), GDT (global descriptor table), LDT (local descriptor table), and TSS (task segment selector)
 - A VMM using this feature can intercept (by a VM exit) attempts to relocate these data structures and prevent them from being tampered by malicious software
- VM Functions
 - A VM function is an operation provided by the processor that can be invoked using the VMFUNC instruction from guest VM without a VM exit
 - A VM function to perform EPTP switching is supported and allows guest VM to load a new value for the EPT pointer, thereby establishing a different EPT paging structure hierarchy

11.1.2 Security and Cryptography Technologies

11.1.2.1 Advanced Encryption Standard New Instructions (AES-NI)

The processor supports Advanced Encryption Standard New Instructions (AES-NI) that are a set of Single Instruction Multiple Data (SIMD) instructions that enable fast and secure data encryption and decryption based on the Advanced Encryption Standard (AES). AES-NI are valuable for a wide range of cryptographic applications, for example: applications that perform bulk encryption/decryption, authentication, random number generation, and authenticated encryption. AES is broadly accepted as the standard for both government and industry applications, and is widely deployed in various protocols.

AES-NI consists of six Intel® SSE instructions. Four instructions, namely AESENC, AESENCLAST, AESDEC, and AESDELAST facilitate high performance AES encryption and decryption. The other two, AESIMC and AESKEYGENASSIST, support the AES key expansion procedure. Together, these instructions provide a full hardware for support AES, offering security, high performance, and a great deal of flexibility.

11.1.2.2 PCLMULQDQ Instruction

The processor supports the carry-less multiplication instruction, PCLMULQDQ. PCLMULQDQ is a Single Instruction Multiple Data (SIMD) instruction that computes the 128-bit carry-less multiplication of two, 64-bit operands without generating and propagating carries. Carry-less multiplication is an essential processing component of several cryptographic systems and standards. Hence, accelerating carry-less multiplication can significantly contribute to achieving high speed secure computing and communication.

11.1.2.3 Digital Random Number Generator

The processor introduces a software visible digital random number generation mechanism supported by a high quality entropy source. This capability is available to programmers through the new RDRAND instruction. The resultant random number generation capability is designed to comply with existing industry standards (ANSI X9.82 and NIST SP 800-90).


Some possible uses of the new RDRAND instruction include cryptographic key generation as used in a variety of applications including communication, digital signatures, secure storage, etc.

11.1.3 Power Aware Interrupt Routing

PAIR is an improvement in H/W routing of “redirectable” interrupts. Each core power-state is considered in the routing selection to reduce the power or performance impact of interrupts. System BIOS configures the routing algorithm, e.g. fixed-priority, rotating, hash, or PAIR, during setup via non-architectural register. The PAIR algorithm can be biased to optimize for power or performance and the largest gains will be seen in systems with high interrupt rates.

11.2 Platform Identification and CPUID

In addition to verifying the processor signature, the intended processor platform type must be determined to properly target the microcode update. The intended processor platform type is determined by reading bits [52:50] of the IA32_PLATFORM_ID register, (MSR 17h) within the processor. This is a 64-bit register that must be read using the RDMSR instruction. The 3 Platform Id bits, when read as a binary coded decimal (BCD) number, indicate the bit position in the microcode update header’s Processor Flags field that is asSoCiated with the installed processor.



Executing the CPUID instruction with EAX=1 will provide the following information.

EAX	Field description
[31:28]	Reserved
[27:20]	Extended Family value
[19:16]	Extended Model value
[15:13]	Reserved
[12]	Processor Type Bit
[11:8]	Family value
[7:4]	Model value
[3:0]	Stepping ID Value

11.3 References

For further details of Intel® 64 and IA-32 architectures refer to Intel® 64 and IA-32 Architectures Software Developer's Manual Combined Volumes:1, 2A, 2B, 2C, 3A, 3B, and 3C:

- <http://www.intel.com/content/www/us/en/processors/architectures-software-developer-manuals.html>

For more details on AES-NI refer to:

- Intel ® Performance Primitives (IPP) web page - <http://software.intel.com/en-us/intel-ipp/>
- White Paper on AES-NI - <http://software.intel.com/en-us/articles/intel-advanced-encryption-standard-aes-instructions-set/>


For more details on using the RDRAND instruction refer to Intel® Advanced Vector Extensions Programming Reference.

§

12 System Memory Controller

The system memory controller supports DDR3L protocol with up to two 64-bit wide dual rank channels at data rates up to 1333 MT/s. ECC is also available on a single channel.

Note: The memory data rate is fixed for each SKU. For example, a SKU that supports 1333 MT/s will only run at 1333 MT/s, nothing lower. For single channel use cases, Channel 0 must be used.



12.1 Signal Descriptions

See [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Type:** The buffer type found in [Chapter 9, "Electrical Specifications"](#)
- **Description:** A brief explanation of the signal's function




Table 150. Memory Channel 0 DDR3L Signals (Sheet 1 of 2)

Signal Name	Direction Type	Description
DRAM0_CKP[2,0] DRAM0_CKN[2,0]	O DDR3	SDRAM and inverted Differential Clock: (1 pair per Rank) The differential clock pair is used to latch the command into DRAM. Each pair corresponds to one rank on DRAM side.
DRAM0_CS[2,0]#	O DDR3	Chip Select: (1 per Rank). Used to qualify the command on the command bus for a particular rank.
DRAM0_CKE[2,0]	O DDR3	Clock Enable: (power management) It is used during DRAM power up/power down and Self refresh. <i>Note: DDR3L uses only DRAM0_CKE[2,0]. DRAM0_CKE[1,3] are not being used for DDR3L.</i>
DRAM0_MA[15:0]	O DDR3	Memory Address: Memory address bus for writing data to memory and reading data from memory. These signals follow common clock protocol w.r.t. DRAM0_CKN, DRAM0_CKP pairs
DRAM0_BS[2:0]	O DDR3	Bank Select: These signals define which banks are selected within each DRAM rank
DRAM0_RAS#	O DDR3	Row Address Select: Used with DRAM0_CAS# and DRAM0_WE# (along with DRAM0_CS#) to define the DRAM Commands
DRAM0_CAS#	O DDR3	Column Address Select: Used with DRAM0_RAS# and DRAM0_WE# (along with DRAM0_CS#) to define the DRAM Commands
DRAM0_WE#	O DDR3	Write Enable Control Signal: Used with DRAM0_WE# and DRAM0_CAS# (along with control signal, DRAM0_CS#) to define the DRAM Commands.
DRAM0_DQ[63:0]	I/O DDR3	Data Lines: Data signal interface to the DRAM data bus
DRAM0_DM[7:0]	O DDR3	Data Mask: DM is an output mask signal for write data. Output data is masked when DM is sampled HIGH coincident with that output data during a Write access. DM is sampled on both edges of DQS.
DRAM0_DQSP[7:0] DRAM0_DQSN[7:0]	I/O DDR3	Data Strobes: The data is captured at the crossing point of each 'P' and its complement 'N' during read and write transactions. For reads, the strobe crossover and data are edge aligned, whereas in the Write command, the strobe crossing is in the centre of the data window.
DRAM0_ODT[2,0]	O DDR3	On Die Termination: ODT signal going to DRAM in order to turn ON the DRAM ODT during Write.



Table 150. Memory Channel 0 DDR3L Signals (Sheet 2 of 2)

Signal Name	Direction Type	Description
DRAM_RCOMP[2]	O Analog	Resistor Compensation: This signal needs to be terminated to VSS on board (refer to platform design guide for resistor value). This external resistor termination scheme is used for Resistor compensation of DRAM ODT strength.
DRAM_RCOMP[1]	O Analog	Resistor Compensation: This signal needs to be terminated to VSS on board (refer to platform design guide for resistor value). This external resistor termination scheme is used for Resistor compensation of DQ buffers
DRAM_RCOMP[0]	O Analog	Resistor Compensation: This signal needs to be terminated to VSS on board (refer to platform design guide for resistor value). This external resistor termination scheme is used for Resistor compensation of CMD buffers.
DRAM_VREF	I Analog	Reference Voltage: DRAM interface Reference Voltage
DRAM_CORE_PWROK	I Asynchronous CMOS	Core Power OK: This signal indicates the status of the DRAM Core power supply (power on in S0).
DRAM_VDD_S4_PWR OK	I Asynchronous CMOS	VDD Power OK: Asserted once the VRM is settled. Used primarily in the DRAM PHY to determine S3 state.
DRAM0_DRAMRST#	O	DRAM Reset: This signal is used to reset DRAM devices.
ICLK_DRAM_TERM [1:0]	I/O	Pull-down to VSS through an 100kOhm 1% resistor.

Table 151. Memory Channel 1 DDR3L Signals (Sheet 1 of 2)

Signal Name	Direction Type	Description
DRAM1_CKP[2,0] DRAM1_CKN[2,0]	O DDR3	SDRAM and inverted Differential Clock: (1 pair per Rank) The differential clock pair is used to latch the command into DRAM. Each pair corresponds to one rank on DRAM side.
DRAM1_CS[2,0]#	O DDR3	Chip Select: (1 per Rank). Used to qualify the command on the command bus for a particular rank.
DRAM1_CKE[2,0]	O DDR3	Clock Enable: (power management) It is used during DRAM power up/power down and Self refresh. <i>Note: DDR3L uses only DRAM1_CKE[0,2]. DRAM1_CKE[1,3] are not being used for DDR3L.</i>




Table 151. Memory Channel 1 DDR3L Signals (Sheet 2 of 2)

Signal Name	Direction Type	Description
DRAM1_MA[15:0]	O DDR3	Memory Address: Memory address bus for writing data to memory and reading data from memory. These signals follow common clock protocol relative to DRAM1_CKN, DRAM1_CKP pairs
DRAM1_BS[2:0]	O DDR3	Bank Select: These signals define which banks are selected within each DRAM rank
DRAM1_RAS#	O DDR3	Row Address Select: Used with DRAM1_CAS# and DRAM1_WE# (along with DRAM1_CS#) to define the DRAM Commands
DRAM1_CAS#	O DDR3	Column Address Select: Used with DRAM1_RAS# and DRAM1_WE# (along with DRAM1_CS#) to define the DRAM Commands
DRAM1_WE#	O DDR3	Write Enable Control Signal: Used with DRAM1_WE# and DRAM1_CAS# (along with control signal, DRAM1_CS#) to define the DRAM Commands.
DRAM1_DQ[63:0]	I/O DDR3	Data Lines: Data signal interface to the DRAM data bus.
DRAM1_DM[7:0]	O DDR3	Data Mask: DM is an output mask signal for write data. Output data is masked when DM is sampled HIGH coincident with that output data during a Write access. DM is sampled on both edges of DQS.
DRAM1_DQSP[7:0] DRAM1_DQSN[7:0]	I/O DDR3	Data Strobes: The data is captured at the crossing point of DRAM1_DQSP[7:0] and its compliment 'N' during read and write transactions. For reads, the strobe crossover and data are edge aligned, whereas in the Write command, the strobe crossing is in the centre of the data window.
DRAM1_ODT[2,0]	O DDR3	On Die Termination: ODT signal going to DRAM in order to turn ON the DRAM ODT during Write.
DRAM1_DRAMRST#	O	Reset DRAM: This signal can be used to reset DRAM devices.

12.1.1 ECC Support

The system memory controller supports ECC. When ECC is enabled, only Memory Channel 0 will be active. Memory Channel 1 will be disabled and used for the ECC data signals. Signals on Memory Channel 1 not used for ECC will be tri-stated. The table below shows the details on the muxing relationship between the ECC signals and the Memory Channel 1 signals.

Note: Although ECC and non-ECC SO-DIMM's share the same socket, ECC SO-DIMMs are not pinout compatible with standard, non-ECC SO-DIMMs.

Table 152. ECC Signals and Memory Channel 1 Signal Muxing

Memory Channel 1 Signal Names	Ball #	Signal Names when ECC is Enabled
DRAM1_DQ[56]	AM52	DRAM0_ECC_DQ[0]
DRAM1_DQ[57]	AL51	DRAM0_ECC_DQ[1]
DRAM1_DQ[58]	AG53	DRAM0_ECC_DQ[2]
DRAM1_DQ[59]	AG51	DRAM0_ECC_DQ[3]
DRAM1_DQ[60]	AL53	DRAM0_ECC_DQ[4]
DRAM1_DQ[61]	AK51	DRAM0_ECC_DQ[5]
DRAM1_DQ[62]	AF52	DRAM0_ECC_DQ[6]
DRAM1_DQ[63]	AF51	DRAM0_ECC_DQ[7]
DRAM1_DM[7]	AK52	DRAM0_ECC_DM
DRAM1_DQSP[7]	AH52	DRAM0_ECC_DQSP
DRAM1_DQSN[7]	AJ51	DRAM0_ECC_DQSN


Table 153. ECC Signals

Signal Name	Direction Type	Description
DRAM0_ECC_DQ[7:0]	I/O DDR3	ECC Check Data Bits <i>These are muxed with channel 1.</i>
DRAM0_ECC_DM	O DDR3	ECC Data Mask: DM is an optional output mask signal for write data. Output data is masked when DM is sampled HIGH coincident with that output data during a Write access. DM is sampled on both edges of ECC_DQS. <i>This signal is muxed with channel 1 and may not be needed.</i>
DRAM0_ECC_DQSP DRAM0_ECC_DQSN	I/O DDR3	ECC Data Strobes: The data is captured at the crossing point the 'P' and its compliment 'N' during read and write transactions. For reads, the strobe crossover and data are edge aligned, whereas in the Write command, the strobe crossing is in the centre of the data window. <i>These are muxed with channel 1.</i>

12.2 Features

The system memory controller supports the following DDR3L DRAM technologies, Data Transfer Rates, SO-DIMM Modules and other features:

- DDR3L Data Transfer Rates (Fixed per SKU): 1066MT/s (Theoretical Maximum Bandwidth: 8.5 GB/s per channel) or 1333MT/s (Theoretical Maximum Bandwidth: 10.6 GB/s per channel)
- DDR3L SDRAM's (1.35 V DRAM interface I/Os, including DDR3L-RS)
- DDR3L DRAM Device Technology



- Standard 1Gb, 2Gb and 4Gb technologies and addressing
- Read latency 5, 6, 7, 8, 9, 10, 11
- Write latency 5, 6, 7, 8
- DDR3L SO-DIMM Modules (unbuffered)
 - Raw Card B = 1 rank of x8 SDRAM
 - Raw Card C = 1 rank of x16 SDRAM
 - Raw Card F = 2 ranks of x8 SDRAM
 - ECC Raw Card C = 1 rank of x8 SDRAM
 - ECC Raw Card D = 2 ranks of x8 SDRAM
 - No mixed Raw Card support
 - Contact your Intel representative for platform supportable memory configurations and limitations based on layout and firmware initialization (MRC) requirements
- Support Trunk Clock Gating
- Supports up to two 64-bit channels
 - Channel 0 only for single channel configuration
- ECC support for 64-bit data bus
- Support early SR exit
- Support slow power down

12.2.1 System Memory Technology Support

Table 154. Supported DDR3L DRAM Devices

DRAM Density	Data Width	Banks	Bank Address	Row Address	Column Address	Page Size
1Gb	x8	8	BA[2:0]	A[13:0]	A[9:0]	1KB
2Gb	x8	8	BA[2:0]	A[14:0]	A[9:0]	1KB
4Gb	x8	8	BA[2:0]	A[15:0]	A[9:0]	1KB
2Gb	x16	8	BA[2:0]	A[13:0]	A[9:0]	2KB

Table 155. Supported DDR3L Memory Size Per Rank

Memory Size/ Rank	DRAM Chips/ Rank	DRAM Chip Density	DRAM Chip Data Width	Page Size @ 64-bit Data Bus
1GB	8	1Gb	x8	8KB = 1KB * 8 chips

**Table 155. Supported DDR3L Memory Size Per Rank**

Memory Size/ Rank	DRAM Chips/ Rank	DRAM Chip Density	DRAM Chip Data Width	Page Size @ 64-bit Data Bus
2GB	8	2Gb	x8	8KB = 1KB * 8 chips
4GB	8	4Gb	x8	8KB = 1KB * 8 chips
1GB	4	2Gb	x16	8KB = 2KB * 4 chips

Table 156. Supported DDR3L ECC Memory Size Per Rank

Memory Size/ Rank	DRAM Chips/ Rank	DRAM Chip Density	DRAM Chip Data Width	Page Size @ 64-bit Data Bus
2GB	8	2Gb	x8	8KB = 1KB * 8 chips
4GB	8	4Gb	x8	8KB = 1KB * 8 chips

Table 157. Supported DDR3L SO-DIMM Size

DRAM Chip Density	Module Size	# of chips needed	DRAM Chip Data Width	Data Bus Width	# of Ranks needed	# of chips /rank
1Gbit	2GB	16	x8	x64	2	8
2Gbit	1GB	4	x16	x64	1	4
2Gbit	2GB	8 (9 w/ECC)	x8	x64	1	8
2Gbit	4GB	16 (18 w/ECC)	x8	x64	2	8
4Gbit	4GB	8 (9 w/ECC)	x8	x64	1	8
4Gbit	8GB	16 (18 w/ECC)	x8	x64	2	8

The frequency of system memory is fixed based on SKU. Timing parameters (CAS latency or CL + AL for DDR3, tRAS, tRCD, tRP) must be programmed to match within a channel (Contact your Intel field representative for more information on memory reference code (MRC)). The controller supports these configurations:

- Supports 1 SO-DIMM per channel.
- Each SO-DIMM can have 1 or 2 ranks.
- If a SO-DIMM has two ranks, then both ranks must be symmetrical (same chip width, same chip density, and same total memory size per rank).
- For dual channel population, the two channels must be populated symmetrically (chip width, density, ranks).
- The maximum total memory supported by the SoC is 8GB. Contact your Intel representative for guidelines on the specific SO-DIMM Raw cards supported.

12.3 System Memory Controller (D-Unit) Message Registers

Table 158. Summary of Memory Controller Message Bus Registers—Port 0x01

Offset	Register Name (Register Symbol)	Default Value
0-0h	"DRP—Offset 0h" on page 288	00000000h
1-1h	"DTR0—Offset 1h" on page 289	43001110h
2-2h	"DTR1 (DTR1)—Offset 2h" on page 291	02690320h
3-3h	"DTR2—Offset 3h" on page 293	00845544h
4-4h	"DTR3 (DTR3)—Offset 4h" on page 294	06406255h
5-5h	"DTR4 (DTR4)—Offset 5h" on page 295	00003322h
6-6h	"DPMC0 (DPMC0)—Offset 6h" on page 296	0B000000h
7-7h	"DPMC1 (DPMC1)—Offset 7h" on page 298	00000011h
8-8h	"DRFC (DRFC)—Offset 8h" on page 299	03012CA7h
9-9h	"DSCH (DSCH)—Offset 9h" on page 300	00071108h
A-Ah	"DCAL (DCAL)—Offset Ah" on page 301	00001300h
B-Bh	"DRMC (DRMC)—Offset Bh" on page 303	00000000h
C-Ch	"PMSTS (PMSTS)—Offset Ch" on page 303	00000000h
F-Fh	"DCO (DCO)—Offset Fh" on page 304	00000000h
10-10h	"DTRC (DTRC)—Offset 10h" on page 305	00000000h
12-12h	"DCBR (DCBR)—Offset 12h" on page 306	00000000h
20-20h	"DSTAT (DSTAT)—Offset 20h" on page 307	0000000Ah
21-21h	"PGTBL (PGTBL)—Offset 21h" on page 308	00000000h
31-31h	"MISRCCCLR (MISRCCCLR)—Offset 31h" on page 309	00000000h
32-32h	"MISRDDCLR (MISRDDCLR)—Offset 32h" on page 309	00000000h
34-34h	"MISRCCSIG (MISRCCSIG)—Offset 34h" on page 310	FFFFFFFFh
35-35h	"MISRDDSIG (MISRDDSIG)—Offset 35h" on page 310	FFFFFFFFh
37-37h	"MISRECCSIG (MISRECCSIG)—Offset 37h" on page 310	FFFFFFFFh
4A-4Ah	"SSKPD0 (SSKPD0)—Offset 4Ah" on page 311	00000000h
4B-4Bh	"SSKPD1—Offset 4Bh" on page 311	00000000h
50-50h	"BONUS0 (BONUS0)—Offset 50h" on page 312	00000000h
51-51h	"BONUS1—Offset 51h" on page 312	00000000h
60-60h	"DECCCTRL (DECCCTRL)—Offset 60h" on page 313	00000000h
62-62h	"DECCSBECNT (DECCSBECNT)—Offset 62h" on page 314	00000000h
70-70h	"DFUSESTAT (DFUSESTAT)—Offset 70h" on page 314	00000000h
80-83h	"DSCRMSEED (DSCRMSEED)—Offset 80h" on page 315	00000000h
81-81h	"DSCRMLO (DSCRMLO)—Offset 81h" on page 316	00000000h
82-82h	"DSCRMHI (DSCRMHI)—Offset 82h" on page 316	00000000h
E0-E0h	"PMSEL0 (PMSEL0)—Offset E0h" on page 317	00000000h
E1-E1h	"PMSEL1 (PMSEL1)—Offset E1h" on page 317	00000000h
E2-E2h	"PMSEL2—Offset E2h" on page 318	00000000h



Table 158. Summary of Memory Controller Message Bus Registers—Port 0x01

Offset	Register Name (Register Symbol)	Default Value
E3–E3h	"PMSEL3—Offset E3h" on page 319	00000000h
E8–E8h	"PMAUXMAX (PMAUXMAX)—Offset E8h" on page 319	00000000h
E9–E9h	"PMAUXMIN—Offset E9h" on page 320	00000000h
EA–EAh	"PMAUXMAX (PMAUXMAX)—Offset E8h" on page 319	00000000h

12.3.1 DRP—Offset 0h

DRAM Rank Population

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 0h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd_31_24_DRP	ENLPDDR3	DRAMTYPE	DIMM1MIRR	DIMM0MIRR	Rsvd_19_DRP	CKECOPY	RANKREMAP	DIMMFLIP
					Rsvd_15_DRP	RSIEN	Rsvd_13_DRP	DIMMDDEN1
								DIMMDWID1
					Rsvd_8_DRP			DIMMDDEN0
								DIMMDWID0
								RKEN3
								RKEN2
								RKEN1
								RKEN0

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RO	Rsvd_31_24_DRP: Reserved
23	0h RW/P/L	ENLPDDR3: Enable LPDDR3 Mode 0 - LPDDR2 1 - LPDDR3 Note: This bit is functional only when DRP.DRAMTYPE is set to LPDDR2
22	0h RW/P/L	DRAMTYPE: DRAM Type 0 - DDR3 1 - LPDDR2
21	0h RW/P/L	DIMM1MIRR: Address mapping to DIMM1 is mirrored. BIOS writes value defined in SPD Byte 63. Used as indication to Punit to flip MRS opcode to 2nd rank on DIMM1. This bit has no functional impact on Dunit. 0 - Standard 1 - Mirrored
20	0h RW/P/L	DIMM0MIRR: Address mapping to DIMM0 is mirrored. BIOS writes value defined in SPD Byte 63. Used as indication to Punit to flip MRS opcode to 2nd rank on DIMM0. This bit has no functional impact on Dunit. 0 - Standard 1 - Mirrored
19	0h RO	Rsvd_19_DRP: Reserved
18	0h RW/P/L	CKECOPY: Used for doubling CKE. 0 - no CKE copy 1 - Copy CKE[0] to CKE[1] and CKE[2] to CKE[3] Note: CKE to DDRIO also depends upon RANKREMAP and state of CA Training.
17	0h RW/P/L	RANKREMAP: Enables mapping logical rank to physical rank. 0 - no rank remap 1 - rank is remapped If (rank[0] is enabled) Map rank[1] to rank[2] Else (If rank[0] is disabled) Map rank[3:2] to rank[1:0]



Bit Range	Default & Access	Field Name (ID): Description
16	0h RW/P/L	DIMMFLIP: DIMM Flip Required. BIOS must set this bit to 1 if the total size of DIMM1 is greater than the total size of DIMM0. DIMM Flipping simplifies rank decoding in dual-DIMM configuration when the DIMMs are not equal in size by mapping the low addresses to the larger DIMM.
15	0h RO	Rsvd_15_DRP: Reserved
14	0h RW/P/L	RSIEN: Rank Select Interleave Enable. 0 - Rank Select Interleave Disabled 1 - Rank Select Interleave Enabled Note: Rank select interleave enable should be set the same for both the Dunit and Bunit.
13	0h RO	Rsvd_13_DRP: Reserved
12:11	0h RW/P/L	DIMMDDEN1: DIMM 1 Device Density. This sets the density of the DRAM devices populated in DIMM 1 (Rank 0 and Rank 1). 00 - 1Gbit 01 - 2Gbit 10 - 4Gbit 11 - 8Gbit
10:9	0h RW/P/L	DIMMDWID1: DIMM 1 Device Width. Indicates the width of the DRAM devices populated in DIMM 1 (Rank 0 and Rank 1). 00 - x8 01 - x16 10 - x32 11 - Reserved
8	0h RO	Rsvd_8_DRP: Reserved
7:6	0h RW/P/L	DIMMDDEN0: DIMM 0 Device Density. This sets the density of the DRAM devices populated in DIMM 0 (Rank 0 and Rank 1). 00 - 1Gbit 01 - 2Gbit 10 - 4Gbit 11 - 8Gbit
5:4	0h RW/P/L	DIMMDWID0: DIMM 0 Device Width. Indicates the width of the DRAM devices populated in DIMM 0 (Rank 0 and Rank 1). 00 - x8 01 - x16 10 - x32 11 - Reserved
3	0h RW/P/L	RKEN3: DIMM 1, Rank 1 Enabled. Should be set to 1 when DIMM1 is populated and has 2 ranks to enable the use of this rank. Otherwise, must be set to 0.
2	0h RW/P/L	RKEN2: DIMM 1, Rank 0 Enabled. Should be set to 1 when DIMM1 is populated to enable the use of this rank. Otherwise, must be set to 0.
1	0h RW/P/L	RKEN1: DIMM 0, Rank 1 Enabled. Should be set to 1 when DIMM0 is populated and has 2 ranks to enable the use of this rank. Otherwise, must be set to 0.
0	0h RW/P/L	RKEN0: DIMM 0, Rank 0 Enabled. Should be set to 1 when DIMM0 is populated to enable the use of this rank. Otherwise, must be set to 0.

12.3.2 DTR0—Offset 1h

DRAM Timing Register 0

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 1h

Op Codes:

h - Read, h - Write

Default: 43001110h



31				28			24			20			16			12			8			4			0																																										
0	1	0	0	0	0	1	1	0	0	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	1	0	0	0	0																																						
CKEDLY				Rsvd_27_26_DTR0				PMEDLY				Rsvd_23_DTR0				tZQoper				Rsvd_11				tZQCS				Rsvd_19_DTR0				tXSDLL				Rsvd_17_DTR0				tXS				Rsvd_15_DTR0				tCL				tRCD				tRP				Rsvd_3_2_DTR0				DFREQ			

Bit Range	Default & Access	Field Name (ID): Description
31:28	4h RW	CKEDLY: Additional delay between CK/CKB start and SRX command. This delay is needed for clock to stabilize to meet JEDEC requirements. Delay is CKEDLY multiples of 256 DRAM Clocks. 0ns to 9,600ns (DDR3-800) 0ns to 7,200ns (DDR3-1066)
27:26	0h RO	Rsvd_27_26_DTR0: Reserved
25:24	3h RW	PMEDLY: The delay, in DRAM clocks, between SR Entry command and Power-Mode message to DDRIO. 0h - 6 DRAM Clocks 1h - 8 DRAM Clocks 2h - 10 DRAM Clocks 3h - 12 DRAM Clocks
23	0h RO	Rsvd_23_DTR0: Reserved
22	0h RW	tZQoper: The delay, in DRAM clocks, between ZQC-Long command to any command. Note: ZQCL command during DRAM Init flow requires longer latency which is controlled by BIOS. 0h - 256 DRAM Clocks 1h - 384 DRAM Clocks
21	0h RO	Rsvd_11: Reserved
20	0h RW	tZQCS: The delay, in DRAM clocks, between a ZQC-Short command to any command. 0h - 64 DRAM Clocks 1h - 96 DRAM Clocks
19	0h RO	Rsvd_19_DTR0: Reserved
18	0h RW	tXSDLL: The delay, in DRAM clocks, between SRX command to any command requiring locked DLL. Only ZQCL can be sent before tXSDLL is done. 0h - tXS + 256 DRAM Clocks 1h - tXS + 384 DRAM Clocks
17	0h RO	Rsvd_17_DTR0: Reserved
16	0h RW	tXS: The delay, in DRAM clocks, between SRX command to command not requiring locked DLL. The Dunit can send a ZQCL command after tXS. JEDEC defines MAX(5CK, tRFC(min)+10ns) so both values take safety margin. 0h - 256 DRAM Clocks 1h - 384 DRAM Clocks
15	0h RO	Rsvd_15_DTR0: Reserved
14:12	1h RW	tCL: CAS Latency. Specifies the delay, in DRAM clocks, between the issue of a RD command and the return of valid data on the DQ bus. 0h - 5 DRAM Clocks (DDR3-800) 1h - 6 DRAM Clocks (DDR3-800, 1066, LPDDR2-800) 2h - 7 DRAM Clocks (DDR3-1066, 1333) 3h - 8 DRAM Clocks (DDR3-1066, 1333, 1600, LPDDR2-1066) 4h - 9 DRAM Clocks (DDR3-1333, 1600) 5h - 10 DRAM Clocks (DDR3-1333, 1600, LPDDR3-1333) 6h - 11 DRAM Clocks (DDR3-1600) 7h - Reserved



Bit Range	Default & Access	Field Name (ID): Description
11:8	1h RW	tRCD: Activate (RAS) to CAS Delay. Specifies the delay, in DRAM clocks, between an ACT command and a RD/WR command to the same bank. 0h - 5 DRAM Clocks (DDR3-800) 1h - 6 DRAM Clocks (DDR3-800, 1066. LPDDR2-800) 2h - 7 DRAM Clocks (DDR3-1066, 1333) 3h - 8 DRAM Clocks (DDR3-1066, 1333, 1600. LPDDR2-800, 1066) 4h - 9 DRAM Clocks (DDR3-1333, 1600) 5h - 10 DRAM Clocks (DDR3-1333, 1600. LPDDR2-800, 1066. LPDDR3-1333) 6h - 11 DRAM Clocks (DDR3-1600) 7h - 12 DRAM Clocks (LPDDR3-1333) 8h - 13 DRAM Clocks (LPDDR2-1066) 9h - 14 DRAM Clocks Ah - 15 DRAM Clocks Bh - 16 DRAM Clocks (LPDDR3-1333) Others - Reserved
7:4	1h RW	tRP: Precharge to Activate Delay. Specifies the delay, in DRAM clocks, between a PRE command and an ACT command to the same bank. 0h - 5 DRAM Clocks (DDR3-800) 1h - 6 DRAM Clocks (DDR3-800, 1066. LPDDR2-800) 2h - 7 DRAM Clocks (DDR3-1066, 1333) 3h - 8 DRAM Clocks (DDR3-1066, 1333, 1600. LPDDR2-800, 1066) 4h - 9 DRAM Clocks (DDR3-1333, 1600) 5h - 10 DRAM Clocks (DDR3-1333, 1600. LPDDR2-800, 1066. LPDDR3-1333) 6h - 11 DRAM Clocks (DDR3-1600) 7h - 12 DRAM Clocks (LPDDR3-1333) 8h - 13 DRAM Clocks (LPDDR2-1066) 9h - 14 DRAM Clocks Ah - 15 DRAM Clocks Bh - 16 DRAM Clocks (LPDDR3-1333) Others - Reserved
3:2	0h RO	Rsvd_3_2_DTR0: Reserved
1:0	0h RW	DFREQ: DRAM Frequency. Specifies the DDR3 frequency used by Dunit for computing proper cycle to cycle timings. Note: This configuration has no impact on the actual DRAM clock. 0h - DDR3-800 1h - DDR3-1066 2h - DDR3-1333 3h - DDR3-1600

12.3.3 DTR1 (DTR1)—Offset 2h

DRAM Timing Register 1

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 2h


Op Codes:

h - Read, h - Write

Default: 02690320h

31				28				24				20				16				12				8				4				0																			
0				0				0				0				0				0				0				0				0																			
Rsvd_31_DTR1				tRTP				Rsvd_27_26_DTR1				tRRD				tRAS				tFAW				Rsvd_15_14_DTR1				tCCD				tWTP				Rsvd_7_6_DTR1				tCMD				Rsvd_3_DTR1				tWCL			

Bit Range	Default & Access	Field Name (ID): Description
31	0h RO	Rsvd_31_DTR1: Reserved
30:28	0h RW	tRTP: Read to Precharge Delay. The minimal delay between RD command and PRE command to same bank. 00 - 4 DRAM Clocks (DDR3-800 DDR3-1066) 01 - 5 DRAM Clocks (DDR3-1333) 10 - 6 DRAM Clocks (DDR3-1600) 11 - 7 DRAM Clocks



Bit Range	Default & Access	Field Name (ID): Description
27:26	0h RO	Rsvd_27_26_DTR1: Reserved
25:24	2h RW	tRRD: Row Activation to Row Activation Delay. The minimal time interval between 2 ACT commands to any bank in the same DRAM device. Limits peak current profile. 00 - 4 DRAM Clocks (1KB page DDR3-800, 1066, 1333) (2KB page DDR3-800, LPDDR2-800) 01 - 5 DRAM Clocks (1KB page DDR3-1600) (2KB page DDR3-1333) 10 - 6 DRAM Clocks (2KB page DDR3-1066, 1600. LPDDR3-1333) 11 - 7 DRAM Clocks
23:20	6h RW	tRAS: Row Activation Period. The minimal delay, in DRAM clocks, between ACT command and PRE command to same bank. At least equal to tRCD + tCWL + tCCD + tWR 0h - 14 DRAM Clocks. 0h - Reserved 1h - 15 DRAM Clocks (DDR3-800) 2h - 16 DRAM Clocks 3h - 17 DRAM Clocks (LPDDR2-800) 4h - 18 DRAM Clocks 5h - 19 DRAM Clocks 6h - 20 DRAM Clocks (DDR3-1066) 7h - 21 DRAM Clocks 8h - 22 DRAM Clocks 9h - 23 DRAM Clocks (LPDDR2-1066) Ah - 24 DRAM Clocks (DDR3-1333) Bh - 25 DRAM Clocks Ch - 26 DRAM Clocks Dh - 27 DRAM Clocks Eh - 28 DRAM Clocks (DDR3-1600. LPDDR3-1333) Fh - 29 DRAM Clocks
19:16	9h RW	tFAW: Four Bank Activation Window. A rolling time-frame, in which a maximum of 4 ACT commands (per rank) can be sent. Limits peak current profile. 0h - Reserved 1h - Reserved 2h - 14 DRAM Clocks 3h - 16 DRAM Clocks (1KB page DDR3-800) 4h - 18 DRAM Clocks 5h - 20 DRAM Clocks (2KB page DDR3-800) (1KB page DDR3-1066, 1333. LPDDR2-800) 6h - 22 DRAM Clocks 7h - 24 DRAM Clocks (1KB page DDR3-1600) 8h - 26 DRAM Clocks 9h - 28 DRAM Clocks (2KB page DDR3-1066. LPDDR2-1066) Ah - 30 DRAM Clocks (2KB page DDR3-1333) Bh - 32 DRAM Clocks (2KB page DDR3-1600) Ch - 34 DRAM Clocks (LPDDR3-1333) Others - Reserved
15:14	0h RO	Rsvd_15_14_DTR1: Reserved
13:12	0h RW	tCCD: CAS to CAS delay. The minimum delay, in DRAM clocks, between 2 RD/WR commands. 0h - 4 DRAM Clocks: Functional mode. (DDR3-800, 1066, 1333, 1600) (LPDDR2-800, 1066) (LPDDR3-1333) 1h - 12 DRAM Clocks: DFX stretch mode (x2) 2h - 18 DRAM Clocks: DFX stretch mode (x4) 3h - Reserved
11:8	3h RW	tWTP: Write to Prechange. The minimum delay, in DRAM clocks, between a WR command and a PRE command to the same bank. Value should be computed as 4 + tWCL + tWR. 0h - 14 DRAM Clocks (LPDDR2-800) 1h - 15 DRAM Clocks (DDR3-800) 2h - 16 DRAM Clocks 3h - 17 DRAM Clocks (LPDDR2-1066) 4h - 18 DRAM Clocks (DDR3-1066) 5h - 19 DRAM Clocks 6h - 20 DRAM Clocks 7h - 21 DRAM Clocks (DDR3-1333. LPDDR3-1333) 8h - 22 DRAM Clocks 9h - 23 DRAM Clocks Ah - 24 DRAM Clocks (DDR3-1600) Bh - 25 DRAM Clocks Others - Reserved
7:6	0h RO	Rsvd_7_6_DTR1: Reserved
5:4	2h RW	tCMD: Command Transport Duration. The time period, in DRAM clocks, that a command occupies the DRAM command bus. 1N is the DDR3 basic requirement. 2N and 3N are extended modes for board signal-integrity. 0h - 1 DRAM Clock (1N) 1h - 2 DRAM Clocks (2N) 2h - 3 DRAM Clocks (3N)
3	0h RO	Rsvd_3_DTR1: Reserved
2:0	0h RW	tWCL: CAS Write Latency. The delay, in DRAM clocks, between the internal write command and the availability of the first bit of DRAM input data. 0h - 3 DRAM Clocks (LPDDR2-800) 1h - 4 DRAM Clocks (LPDDR2-1066) 2h - 5 DRAM Clocks (DDR3-800) 3h - 6 DRAM Clocks (DDR3-1066. LPDDR3-1333) 4h - 7 DRAM Clocks (DDR3-1333) 5h - 8 DRAM Clocks (DDR3-1600) Others - Reserved



Bit Range	Default & Access	Field Name (ID): Description
6:4	4h RW	tRRDD : Read to Read DQ delay, different DIMMs 0h - Reserved 1h - 6 DRAM Clocks (DDR3) 2h - 7 DRAM Clocks (LPDDR2-800, 1066. LPDDR3-1333) 3h - 8 DRAM Clocks 4h - 9 DRAM Clocks 5h - 10 DRAM Clocks 6h - 11 DRAM Clocks Others - Reserved
3	0h RO	Rsvd_3_DTR2 : Reserved
2:0	4h RW	tRRDR : Read to Read DQ delay, different ranks, same DIMM 0h - Reserved 1h - 6 DRAM Clocks (DDR3) 2h - 7 DRAM Clocks (LPDDR2-800, 1066. LPDDR3-1333) 3h - 8 DRAM Clocks 4h - 9 DRAM Clocks 5h - 10 DRAM Clocks 6h - 11 DRAM Clocks Others - Reserved

12.3.5 DTR3 (DTR3)—Offset 4h

DRAM Timing Register 3

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 4h

Op Codes:

h - Read, h - Write

Default: 06406255h

31				28				24				20				16				12				8				4				0																							
0				0				0				0				0				0				0				0				0																							
Rsvd_31_DTR3				DERATESTAT				DERATEOVR				ENDRATE				PWDDL				tXP				Rsvd_21_17_DTR3				tWRSR				Rsvd_12_DTR3				tWRSR				Rsvd_7_DTR3				tWRDD				Rsvd_3_DTR3				tWRDR			

Bit Range	Default & Access	Field Name (ID): Description
31	0h RO	Rsvd_31_DTR3 : Reserved
30	0h RO	DERATESTAT : Timing De-rating Status
29	0h RW	DERATEOVR : Enabled Timing De-rating Override
28	0h RW	ENDRATE : Enabled Dynamic Timing De-rating
27:24	6h RW	PWDDL : RD/WR command to Power-down delay. Non-JEDEC delay for performance enhancement. Delay = PWDDL x 4 DRAM Clocks.
23:22	1h RW	tXP : Delay from CKE asserted high to any DRAM command 0h - 2 DRAM Clocks (DDR3-800 2N) 1h - 3 DRAM Clocks (DDR3-800 1N) (DDR3-1066, 1333 2N) (LPDDR2-800) 2h - 4 DRAM Clocks (DDR3-1066, 1333 1N) (DDR3-1600 2N) (LPDDR2-1066) 3h - 5 DRAM Clocks (DDR3-1600 1N) (LPDDR3-1333)
21:17	0h RO	Rsvd_21_17_DTR3 : Reserved

Bit Range	Default & Access	Field Name (ID): Description
16:13	3h RW	tWRSR : Write to Read same rank command delay. Should be set to 4 + tWCL + tWTR. 0h - 11 DRAM Clocks (LPDDR2-800) 1h - 12 DRAM Clocks 2h - 13 DRAM Clocks (DDR3-800, LPDDR2-1066) 3h - 14 DRAM Clocks (DDR3-1066) 4h - 15 DRAM Clocks 5h - 16 DRAM Clocks (DDR3-1333, LPDDR3-1333) 6h - 17 DRAM Clocks 7h - 18 DRAM Clocks (DDR3-1600) 8h - 19 DRAM Clocks 9h - 20 DRAM Clocks Others - Reserved
12	0h RO	Rsvd_12_DTR3 : Reserved
11:8	2h RW	tRWSR : Read to Write same rank command delay. Should be set to tCL - tWCL + 6 + board delay if needed. 0h - 6 DRAM Clocks (DDR3) 1h - 7 DRAM Clocks 2h - 8 DRAM Clocks 3h - 9 DRAM Clocks 4h - 10 DRAM Clocks 5h - 11 DRAM Clocks (LPDDR2-800) 6h - 12 DRAM Clocks (LPDDR2-1066) 7h - 13 DRAM Clocks 8h - 14 DRAM Clocks 9h - 15 DRAM Clocks (LPDDR3-1333) Ah - 16 DRAM Clocks Bh - 17 DRAM Clocks Others - Reserved
7	0h RO	Rsvd_7_DTR3 : Reserved
6:4	5h RW	tWRDD : Write to Read DQ delay, different DIMMs 0h - 4 DRAM Clocks (LPDDR3-1333) 1h - 5 DRAM Clocks (LPDDR2-800, 1066) 2h - 6 DRAM Clocks (DDR3) 3h - 7 DRAM Clocks 4h - 8 DRAM Clocks 5h - 9 DRAM Clocks 6h - 10 DRAM Clocks Others - Reserved
3	0h RO	Rsvd_3_DTR3 : Reserved
2:0	5h RW	tWRDR : Write to Read DQ delay, different ranks, same DIMM 0h - Reserved 1h - 4 DRAM Clocks (LPDDR3-1333) 2h - 5 DRAM Clocks (LPDDR2-800, 1066) 3h - 6 DRAM Clocks (DDR3) 4h - 7 DRAM Clocks 5h - 8 DRAM Clocks 6h - 9 DRAM Clocks 7h - 10 DRAM Clocks

12.3.6 DTR4 (DTR4)—Offset 5h

DRAM Timing Register 4

Access Method


Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 5h

Op Codes:

Default: 00003322h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31:19	0h RO	Rsvd_31_19_DTR4: Reserved
18	0h RW	WRBODTDIS: Disable Write ODT on non-targeted DIMM. When writing to DIMM A, ODT is asserted to the target rank of DIMM A and also to the low rank of DIMM B. This defeature bit is used to disable ODT assertion to the opposite DIMM during write.
17	0h RW	RDOBDTDIS: Disable Read ODT. When reading from DIMM A, ODT is asserted to the low rank of DIMM B. This defeature bit is used to disable ODT assertion during reads.
16	0h RW	TRGSTRDIS: Write target rank is not stretched. When set, stretched ODT as defined above is not applied to the write target rank and ODT command is asserted for 6 DRAM clocks. Should not be used when ODT is pulled-in.
15	0h RO	Rsvd_15_DTR4: Reserved
14:12	3h RW	RDOBDTSTOP: Read command to ODT de-assert delay Value should be set to: RDOBDTSTRT+6+(WROBDTSTOP-WROBDTSTRT) 0h - 6 DRAM Clocks 1h - 7 DRAM Clocks 2h - 8 DRAM Clocks 3h - 9 DRAM Clocks 4h - 10 DRAM Clocks 5h - 11 DRAM Clocks 6h - 12 DRAM Clocks 7h - 13 DRAM Clocks Other - Reserved
11	0h RO	Rsvd_24: Reserved
10:8	3h RW	RDOBDTSTRT: Read command to ODT assert delay. Value should be set to tCMD+tCL-tWCL-ODT_PULLIN, where ODT_PULLIN must have the same value as in WROBDTSTRT. 0h - 0 DRAM Clocks 1h - 1 DRAM Clocks 2h - 2 DRAM Clocks 3h - 3 DRAM Clocks 4h - 4 DRAM Clocks 5h - 5 DRAM Clocks Other - Reserved
7	0h RO	Rsvd_7_DTR4: Reserved
6:4	2h RW	WROBDTSTOP: Write command to ODT de-assert delay. WROBDTSTOP 1N 2N 3N 0h WR+6 N/A N/A 1h WR+7 WR+6 N/A 2h WR+8 WR+7 WR+6 3h WR+9 WR+8 WR+7 4h WR+10 WR+9 WR+8 Other Reserved Reserved Reserved
3:2	0h RO	Rsvd_3_2_DTR4: Reserved
1:0	2h RW	WROBDTSTRT: WR command to ODT assert delay. JEDEC requires ODT to be asserted on the same clock with the WR command. Dunit allows to pull-in by 1 clock in 2N mode and by 1-2 clocks in 3N mode. For most DIMM configurations, this register should be programmed to same value as tCMD. A value of tCMD - ODT_PULLIN can be used according to the table below which shows the ODT command assertion with respect to the WR command assertion. WROBDTSTRT 1N 2N 3N 0h WR WR-1 WR-2 1h N/A WR WR-1 2h N/A N/A WR 3h Reserved Reserved Reserved

12.3.7 DPMC0 (DPMC0)—Offset 6h

DRAM Power Management Control 0

Access Method


Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 6h

Op Codes:

h - Read, h - Write

Default: 0B000000h



Intel Atom® Processor E3800 Product Family
Datasheet
297



Bit Range	Default & Access	Field Name (ID): Description
20	0h RW	PCLSWKOK: Wake Allowed for Page Close Timeout. Setting this bit to 1 indicates the Dunit can send DRAM devices a PD-Exit command in order to close single bank if the page timer expired. Note: This bit applies only to cases where at least one other bank in the same rank is open but not timed-out. If all banks in the rank timed-out, a PD-Exit command will be sent regardless of this bit. Must be set to 0 during init/training mode. 0h - Disable 1h - Enable
19	0h RO	Rsvd_19_DPMC0: Reserved
18:16	0h RW	PCLSTO: Page Close Timeout Period. Specifies the time frame, in ns, from last access to a DRAM page until that page may be scheduled for closing (by sending a PRE command). 0h - Disable page close timer (init/training) 1h - Immediate page close 2h - 30-60 ns to page close 3h - 60-120 ns to page close 4h - 120-240 ns to page close 5h - 240-480 ns to page close 6h - 480-960 ns to page close 7h - 1-2 s to page close
15:13	0h RO	Rsvd_15_13_DPMC0: Reserved
12:8	0h RW	PMOP: SPID Power Mode Opcode. The PM Message ID the Dunit will send to DDRIO on ispid_pm_pm bus after SR Entry command to DRAM. This message defines the DDRIO power-mode during SR period. Value can be changed on-the-fly to allow different power modes (for example, deeper PM for S3 than for C6). Power saving and Entry/Exit latencies are described in the MODMEM HAS.
7:0	0h RW	SREDLY: Self-Refresh Entry delay. The delay, in core-clocks, between PMI idle (no pending requests and PMI status is less than 2) and SR Entry when Dunit is in Dynamic SR mode.

12.3.8 DPMC1 (DPMC1)—Offset 7h

DRAM Power Management Control 1

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 7h

Op Codes:

h - Read, h - Write

Default: 00000011h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
Rsvd_31_6_DPMC1							CMDTRIST	Rsvd_3_1_DPMC1
								CSTRIST

Bit Range	Default & Access	Field Name (ID): Description
31:6	0h RO	Rsvd_31_6_DPMC1: Reserved



Bit Range	Default & Access	Field Name (ID): Description
5:4	1h RW	CMDTRIST: Tristate Command and Address Bus to DRAM 0h - CMD/ADDR are never tristated. 1h - CMD/ADDR are tristated only when all CKE are low. 2h - CMD/ADDR are tristated when no valid command. 3h - CMD/ADDR are tristated when no valid command but may never be tristated for less than 2 DRAM clocks. This mode is only valid when tCMD is set to 0h (1N mode).
3:1	0h RO	Rsvd_3_1_DPMC1: Reserved
0	1h RW	CSTRIST: Tristate Chip-Select 0 - Never tristate. 1 - TriState DRAM CS# pins from SRE to SRX+tXS. Note: DDRIO may tristate during SR so this adds on the boundaries.

12.3.9 DRFC (DRFC)—Offset 8h

DRAM Refresh Control

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 8h


Op Codes:

h - Read, h - Write

Default: 03012CA7h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	1	1	0
0	0	1	1	0	0	0	0	1
Rsvd_31_27_DRFC	CUREFRATE	Rsvd_23_22_DFRC	REFDBTCLR	REFSKWDIS	Rsvd_19_18_DFRC	REFCNTMAX	Rsvd_15_DRFC	tREFI Refresh Period
							REFWMPNC	REFWMHI
								REFWMLO

Bit Range	Default & Access	Field Name (ID): Description
31:27	0h RO	Rsvd_31_27_DRFC: Reserved
26:24	3h RO	CUREFRATE: Current Refresh Rate This value is updated by the Dunit TQ Poll logic after executing a Mode Register Read Command to the DRAM Device Temperature Mode Register (MR4). 0h - 4x tREFI, Low temperature operating limit exceeded 1h - 4x tREFI 2h - 2x tREFI 3h - 1x tREFI (= 85C) 4h - 0.5x tREFI (LPDDR3) 5h - 0.25x tREFI, do not de-rate AC timing 6h - 0.25x tREFI, de-rate AC timing 7h - 0.25x tREFI, High temperature operating limit exceeded Note: This is an LPDDR feature only.
23:22	0h RO	Rsvd_23_22_DFRC: Reserved
21	0h RW	REFDBTCLR: Clear Refresh Debit before SR Entry When this bit is set, if enough REF commands are pulled-in, Dunit will not send additional REF commands before SR Entry. 0h - Disabled 1h - Enabled
20	0h RW	REFSKWDIS: Refresh counters may be increased in 2 policies - skewed or simultaneously. 0h - counters are updated per rank every 1/4 tREFI period. 1h - all counters are updated every tREFI.



Bit Range	Default & Access	Field Name (ID): Description
19:18	0h RO	Rsvd_19_18_DRFC: Reserved
17:16	1h RW	REFCNTMAX: Refresh Max tREFI Interval. The maximum interval between ant two REF commands per rank. JEDEC allows a maximum of 9 x tREFI intervals. 0h - 6 x tREFI 1h - 7 x tREFI 2h - 8 x tREFI 3h - 9 x tREFI Should not be changed after initial setting.
15	0h RO	Rsvd_15_DRFC: Reserved
14:12	2h RW	tREFI Refresh Period: Specifies the average time between sending REF commands to DRAM. The Dunit will guarantee that the average time is met, but maintains a certain degree of flexibility in the exact REF scheduling in order to increase overall performance. 0h - Refresh disabled 1h - Reserved for pre-silicon simulation 2h - 3.9 μ s (Extended Temperature Range, 85-95°C) 3h - 7.8 μ s (Normal Temperature Range, 0-85°C).
11:8	Ch RW	REFWMPNC: Refresh Panic Watermark. When the refresh debit counter, per rank, is greater than this value, the Dunit will send a REF command even if there are some pending requests and regardless of the PMI status level. See DDR3 spec for Refresh Postponing/Pulling-In flexibility. May be changed to functional value after init sequence. Value should be greater than, or equal, to REFWMHI. 0h - Reserved 1h - Reserved 2h - Reserved 3h - Reserved 4h - Reserved 5h - Reserved 6h - Reserved 7h - Postpone 2 REF commands 8h - Postpone 3 REF commands 9h - Postpone 4 REF commands Ah - Postpone 5 REF commands Bh - Postpone 6 REF commands Ch - Postpone 7 REF commands Dh - Postpone 8 REF commands Others - Reserved
7:4	Ah RW	REFWMHI: Refresh High Watermark. When the refresh debit counter, per rank, is greater than this value, the Dunit will send a REF command even if there are some pending requests to the rank but not if the PMI status is equal to 3. See DDR3 spec for Refresh Postponing/Pulling-In flexibility. May be changed to functional value after init sequence. Value should be greater than, or equal, to REFWMLO. 0h - Reserved 1h - Reserved 2h - Reserved 3h - Reserved 4h - Reserved 5h - Reserved 6h - Reserved 7h - Postpone 2 REF commands 8h - Postpone 3 REF commands 9h - Postpone 4 REF commands Ah - Postpone 5 REF commands Bh - Postpone 6 REF commands Ch - Postpone 7 REF commands Dh - Postpone 8 REF commands Others - Reserved
3:0	7h RW	REFWMLO: Opportunistic Refresh Watermark. When the refresh debit counter, per rank, is greater than this value, the Dunit will send a REF command only if there are no pending requests to the rank and the PMI status is less than 3. See DDR3 spec for Refresh Postponing/Pulling-In flexibility. May be changed to functional value after init sequence. 0h - Reserved 1h - Reserved 2h - Reserved 3h - Reserved 4h - Reserved 5h - Reserved 6h - Reserved 7h - Postpone 2 REF commands 8h - Postpone 3 REF commands 9h - Postpone 4 REF commands Ah - Postpone 5 REF commands Bh - Postpone 6 REF commands Ch - Postpone 7 REF commands Dh - Postpone 8 REF commands Others - Reserved

12.3.10 DSCH (DSCH)—Offset 9h

DRAM Scheduler Control

Access Method


Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 9h

Op Codes:


h - Read, h - Write

Default: 00071108h



12.3.11 DCAL (DCAL)—Offset Ah

October 2018
Document Number: 538136, Rev. 4.3



October 2018
Document Number: 538136, Rev. 4.3



12.3.12 DRMC (DRMC)—Offset Bh

DRAM Reset Management Control

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + Bh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd_31_17_DRMC				COLDWAKE	Rsvd_15_13_DRMC	ODTMODE	ODTVAL	Rsvd_7_5_DRMC
							CKEMODE	CKEVAL

Bit Range	Default & Access	Field Name (ID): Description
31:17	0h RO	Rsvd_31_17_DRMC: Reserved
16	0h RW	COLDWAKE: BIOS should set this bit to 1 before sending WAKE command to Dunit after Cold Reset. For S3 Exit, or any other mode in which the DRAM is in SR, this bit must be set to 0.
15:13	0h RO	Rsvd_15_13_DRMC: Reserved
12	0h RW	ODTMODE: ODT Control Mode 0h - Dunit. 1h - SW override.
11:8	0h RW	ODTVAL: When ODTMODE is set to 1, ODT pins to DRAM are overridden by ODTVAL. Used only during init flow by BIOS.
7:5	0h RO	Rsvd_7_5_DRMC: Reserved
4	0h RW	CKEMODE: CKE Control Mode 0h - Dunit. 1h - SW override.
3:0	0h RW	CKEVAL: When CKEMODE is set to 1, CKE pins to DRAM are overridden by CKEVAL. Used only during init flow by BIOS.

12.3.13 PMSTS (PMSTS)—Offset Ch

Power Management Status

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + Ch

Op Codes:

h - Read, h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
			Rsvd_31_9_PMSTS			WRO	Rsvd_7_1_PMSTS	DISR

Bit Range	Default & Access	Field Name (ID): Description
31:9	0h RO	Rsvd_31_9_PMSTS: Reserved
8	0h RW/P	WRO: Warm Reset Occurred. Set by the Punit whenever a Reset Warn is received, and cleared by powergood=0. 0h: No Warm Reset occurred. 1h: Warm Reset occurred. BIOS Requirement. BIOS can check and clear this bit whenever executing POST code. This way BIOS knows that if the bit is set, then DISR indicates whether DRAM entered Self-Refresh.
7:1	0h RO	Rsvd_7_1_PMSTS: Reserved
0	0h RW/P	DISR: DRAM In Self-Refresh. Set by Dunit hardware after Channel is placed in self refresh as a result of a Power State or a Reset Warn sequence. Cleared by Dunit hardware before starting Channel 0 self refresh exit sequence initiated by a power management exit. Cleared by the BIOS by writing 1 in a warm reset (Reset# asserted while PWROK is asserted) exit sequence. 0 - DRAM not guaranteed to be in Self-Refresh. 1 - DRAM in Self-Refresh.

12.3.14 DCO (DCO)—Offset Fh

DRAM Control Operation

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + Fh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
IC	DIOIC	PMIDIS	PMICTL			REUTLOCK	Rsvd_7_1_DCO	DRPLOCK
				Rsvd_27_9_DCO				

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	IC: Dunit Initialization Complete. This bit should be set by BIOS after Dunit programming is complete and Dunit is ready to accept PMI requests and perform DRAM maintenance operations.



Access Method



Bit Range	Default & Access	Field Name (ID): Description
31:9	0h RO	Rsvd_31_9_DCBR: Reserved
8	0h RW	SRXNRQDIS: Disable Accepting Requests During Self Refresh Exit 0 - Load PMI requests to Dunit in SR Exit tXSDLL and ZQCoper period 1 - Load PMI requests only after tXSDLL and ZQCoper are complete
7:2	0h RO	Rsvd_7_2_DCBR: Reserved
1	0h RW	DMINV: Invert DRAM Data Mask 0 - Do not invert DRAM data mask 1 - Invert DRAM data mask
0	0h RW	PHSINV: Core/SPID CDC phase control invert. Backup inverter for internal phase indicator in Dunit.

12.3.17 DSTAT (DSTAT)—Offset 20h

Dunit Status

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 20h

Op Codes:

h - Read, h - Write

Default: 0000000Ah

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
0				0				0				0				0				0				0				0				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
Rsvd_31_DSTAT				MAXMEM				Rsvd_27_24_DSTAT				REFOPR3				REFOPR2				REFOPR1				REFOPR0				REFDBT3				REFDBT2				REFDBT1				REFDBT0				IPRQVLD7				IPRQVLD6				IPRQVLD5				IPRQVLD4				IPRQVLD3				IPRQVLD2				IPRQVLD1				IPRQVLD0				Rsvd_7_5_DSTAT				MNT_STATE																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							

Bit Range	Default & Access	Field Name (ID): Description
31	0h RO	Rsvd_31_DSTAT: Reserved
30:28	0h RO	MAXMEM: Reflects the fus_dun_max_supported_memory fuse
27:24	0h RO	Rsvd_27_24_DSTAT: Reserved
23	0h RO	REFOPR3: Rank 3 Refresh Dept is greater than DRFC.REFWMLO
22	0h RO	REFOPR2: Rank 2 Refresh Dept is greater than DRFC.REFWMLO
21	0h RO	REFOPR1: Rank 1 Refresh Dept is greater than DRFC.REFWMLO
20	0h RO	REFOPR0: Rank 0 Refresh Dept is greater than DRFC.REFWMLO



Bit Range	Default & Access	Field Name (ID): Description
19	0h RO	REFDBT3: Rank 3 has a Refresh Dept
18	0h RO	REFDBT2: Rank 2 has a Refresh Dept
17	0h RO	REFDBT1: Rank 1 has a Refresh Dept
16	0h RO	REFDBT0: Rank 0 has a Refresh Dept
15	0h RO	IPRQVLD7: IPREQ Entry 7 contains a valid request.
14	0h RO	IPRQVLD6: IPREQ Entry 6 contains a valid request.
13	0h RO	IPRQVLD5: IPREQ Entry 5 contains a valid request.
12	0h RO	IPRQVLD4: IPREQ Entry 4 contains a valid request.
11	0h RO	IPRQVLD3: IPREQ Entry 3 contains a valid request.
10	0h RO	IPRQVLD2: IPREQ Entry 2 contains a valid request.
9	0h RO	IPRQVLD1: IPREQ Entry 1 contains a valid request.
8	0h RO	IPRQVLD0: IPREQ Entry 0 contains a valid request.
7:5	0h RO	Rsvd_7_5_DSTAT: Reserved
4:0	0Ah RO	MNT_STATE: Dunit Maintenance Internal State

12.3.18 PGTBL (PGTBL)—Offset 21h

DRAM Page Table Status

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 21h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PGTBLVLD



12.3.21 MISRCCSIG (MISRCCSIG)—Offset 34h

MISR CMD/CTRL Signature

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 34h

Op Codes:

h - Read, h - Write

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
SIG								

Bit Range	Default & Access	Field Name (ID): Description
31:0	FFFFFFFh RO	SIG: MISR Signature: CMD/CTRL

12.3.22 MISRDDSIG (MISRDDSIG)—Offset 35h

MISR DM/DQ Signature

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 35h

Op Codes:

h - Read, h - Write

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
SIG								

Bit Range	Default & Access	Field Name (ID): Description
31:0	FFFFFFFh RO	SIG: MISR Signature: DM/DQ

12.3.23 MISRECCSIG (MISRECCSIG)—Offset 37h

MISR ECC Signature

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 37h

Op Codes:

h - Read, h - Write

Default: FFFFFFFFh



31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
SIG								

Bit Range	Default & Access	Field Name (ID): Description
31:0	FFFFFFFFh RO	SIG: MISR Signature ECC

12.3.24 SSKPD0 (SSKPD0)—Offset 4Ah

Sticky Scratchpad 0

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 4Ah

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
VAL								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW/P	VAL: General Purpose Scratchpad. May be used for BIOS for data storage. Value is preserved in warm-reset.

12.3.25 SSKPD1—Offset 4Bh

Sticky Scratchpad 1

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 4Bh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
VAL								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW/P	VAL: General Purpose Scratchpad. May be used for BIOS for data storage. Value is preserved in warm-reset.



12.3.26 BONUS0 (BONUS0)—Offset 50h

Bonus Register 0

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 50h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd_31_4_BONUS0							LPDDRCMDTRI	MRRCMDLY
							CATBUGFIX	SLOWPDXEN
							PERFMONEN	DISEARLYSRX

Bit Range	Default & Access	Field Name (ID): Description
31:7	0h RO	Rsvd_31_7_BONUS0 (Rsvd_31_4_BONUS0): Reserved
6	0h RW	LPDDRCMDTRI: Enable LPDDR CMD Tri-Stating
5:4	0h RW	MRRCMDLY: Adding additional delay on MRR followed by read and write command
3	0h RW	CATBUGFIX: This is a defeature bit for CA training and should be set to 0 for normal operation.
2	0h RW	SLOWPDXEN: This bit is for enabling slow powerdown exit.
1	0h RW	PERFMONEN: This bit is for enabling performance monitor.
0	0h RW	DISEARLYSRX: This bit is for enabling early SR exit.

12.3.27 BONUS1—Offset 51h

Bonus Register 1

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 51h

Op Codes:

h - Read, h - Write

Default: 00000000h



Access Method

Offset: [Port: 0x01] + 60h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:18	0h RO	Rsvd_31_18_DECCCTRL: Reserved
17	0h RW	ENCBGEN: DfX: Enable Generation of ECC check bits 0 - Disable check bit generation 1 - Enable check bit generation
16	0b RO	Rsvd_16_DECCCTRL: Reserved
15:8	00h RW	CBOV: DfX: Check Bit Override (Host Defined Value)
7	00h RW	CLRSBECNT: DfX: Clear SERR counter 0 - Allow single bit error count to increment 1 - Clear single bit error count
6:5	00h RW	SYNSEL: DfX: Select syndrome bits from 256b read data path. 0h - Selects syndrome bits from read data [63:0] 1h - Selects syndrome bits from read data [127:64] 2h - Selects syndrome bits from read data [191:128] 3h - Selects syndrome bits from read data [255:192]



Bit Range	Default & Access	Field Name (ID): Description
4:2	000h RW	CBOEN: DfX: Enable Check Bit Override on 256b write data path 0xx Host generated check bits disabled. 0h - Reserved 1h - Reserved 2h - Reserved 3h - Reserved 4h - Assert Host generated check bits on write data [63:0] 5h - Assert Host generated check bits on write data [127:64] 6h - Assert Host generated check bits on write data [191:128] 7h - Assert Host generated check bits on write data [255:192]
1	0h RW	DBEEN: Enable Double Bit Error Detect 0 - Disable double bit error detect 1 - Enable double bit error detect
0	0h RW	SBEEN: Enable Single Bit Error Detect and Correct 0 - Disable single bit error detect and correct 1 - Enable single bit error detect and correct

12.3.29 DECCSBECONT (DECCSBECONT)—Offset 62h

DECC Single Bit Error Count Register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 62h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DECCSBECONT

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RO	DECCSBECONT: ECC Single Bit Error Count Write a 1 to the CLRSBECONT bit in the DECCCTRL register to clear this register

12.3.30 DFUSESTAT (DFUSESTAT)—Offset 70h

Dunit fuse status register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + 70h

Op Codes:

h - Read, h - Write

Default: 00000000h



Access Method

Offset: [Port: 0x01] + 81h

h - Read, h - Write

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SCRMLO								

12.3.33 DSCRMHI (DSCRMHI)—Offset 82h

Access Method

Offset: [Port: 0x01] + 82h

h - Read, h - Write

31	28	24	20	16	12	8	4	0																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
SCRMI																															

October 2018
Document Number: 538136, Rev. 4.3



12.3.34 PMSELO (PMSELO)—Offset E0h

Performance Monitor Event Select 0

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + E0h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DPERFENST	Rsvd_31_14_PMSELO				EVTMSK0	Rsvd_7_4_PMSELO		EVTID

Bit Range	Default & Access	Field Name (ID): Description
31	0h RO	DPERFENST: Dunit Perfmon Enable Status. Reflects DFX Perfmon enable. 0 - Dunit perfmon is disabled. 1 - Dunit perfmon is enabled
30:14	0h RO	Rsvd_31_14_PMSELO: Reserved
13:8	0h RW	EVTMSK0: Event Mask
7:4	0h RO	Rsvd_7_4_PMSELO: Reserved
3:0	0h RW	EVTID: Event ID

12.3.35 PMSEL1 (PMSEL1)—Offset E1h

Performance Monitor Event Select 1

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + E1h

Op Codes:

h - Read, h - Write

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:14	0h RO	Rsvd_31_14_PMSEL1: Reserved
13:8	0h RW	EVTMSK1: Event Mask
7:4	0h RO	Rsvd_7_4_PMSEL1: Reserved
3:0	0h RW	EVTID: Event ID

12.3.36 PMSEL2—Offset E2h

Performance Monitor Event Select 2

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + E2h

Op Codes:

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:14	0h RO	Rsvd_31_14_PMSEL2: Reserved
13:8	0h RW	EVTMSK2: Event Mask
7:4	0h RO	Rsvd_7_4_PMSEL2: Reserved



Bit Range	Default & Access	Field Name (ID): Description
3:0	0h RW	EVTID: Event ID

12.3.37 PMSEL3—Offset E3h

Performance Monitor Event Select 3

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + E3h

Op Codes:

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
Rsvd_31_14_PNSEL3					EVTMSK3		Rsvd_7_4_PNSEL3		EVTID

Bit Range	Default & Access	Field Name (ID): Description
31:14	0h RO	Rsvd_31_14_PMSEL3: Reserved
13:8	0h RW	EVTMSK3: Event Mask
7:4	0h RO	Rsvd_7_4_PMSEL3: Reserved
3:0	0h RW	EVTID: Event ID

12.3.38 PMAUXMAX (PMAUXMAX)—Offset E8h

Performance Monitor Address Limit High

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + E8h

Op Codes:

h - Read, h - Write

Default: 00000000h



Performance Monitor Address Limit Low

Access Method

Type: Message Bus Register
(Size: 32 bits)

Op Codes:
h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd_31_28_PMAUXMIN	MIN							

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RO	Rsvd_31_28_PMAUXMIN: Reserved
27:0	0h RW	MIN: Minimal address or minimal latency count. When PMSEL0.EVTID == Ch, this register should be initialized to FFFh and at the end of the test bits [11:0] will contain the min latency. When PMSEL0/1/2.EVTID == 5h, this register should be initialized to the lowest address the Perfmon test will cover. Bits [27:0] of this register correspond to the physical address bits [32:8].



12.3.40 PMAUX (PMAUX)—Offset EAh

Performance Monitor Aux

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x01] + EAh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd_31_11_PMAUX						PMAUX2	PMAUX1	PMAUX0

Bit Range	Default & Access	Field Name (ID): Description
31:11	0h RO	Rsvd_31_11_PMAUX: Reserved
10:8	0h RW	PMAUX2: Additional mask and configuration. See Perfmon Guide.
7:4	0h RW	PMAUX1: Additional mask and configuration. See Perfmon Guide.
3:0	0h RW	PMAUX0: Additional mask and configuration. See Perfmon Guide.

13 SoC Transaction Router

The SoC Transaction Router is a central hub that routes transactions between the CPU cores, graphics controller, IO and the memory controller. In general, it handles:

- CPU Core Interface: Requests for CPU Core-initiated memory and IO read and write operations and processor-initiated message-signaled interrupt transactions
- Device MMIO and PCI configuration routing
- Buffering and memory arbitration
- PCI Config and MMIO accesses to host device (0/0/0)





Figure 90. Soc Transaction Router Register Map





13.1 Transaction Router A-Unit Message Registers

Table 159. Summary of A-Unit Message Bus Registers—Port 0x00

Offset	Register Name (Register Symbol)	Default Value
10–10h	"ACF8—Offset 10h" on page 324	00000000h
52–52h	"ADBGERRLOG—Offset 52h" on page 325	00000000h

13.1.1 ACF8—Offset 10h

A-Unit Configuration CF8 Value (ACF8) The A-Unit CF8 (PCI Configuration Address Register) is made available for save/restore purposes. This register is saved and restored by the Punit during S0iX transitions in order to ensure proper handling of a possible subsequent CFC transaction after returning from standby or hibernate state. This is carried over from Aunit implementation in LNC.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x00] + 10h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
CFG_MAP_EN	CF8_RESERVED_0				BUS_NUM	DEVICE_NUM	FUNCTION_NUM	DBL_WD	CF8_RESERVED_1

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	CFG_MAP_EN: Configuration Space Mapping Enable: This bit enables Configuration Space mapping. The value set by full-dword writes to I/O address CF8
30:24	0h RW	CF8_RESERVED_0: Reserved. The value set by full-dword writes to I/O address CF8
23:16	0h RW	BUS_NUM: Bus Number: This is the target Bus Number of the resulting Configuration request. The value set by full-dword writes to I/O address CF8
15:11	0h RW	DEVICE_NUM: Device Number: This is the target Device Number of the resulting Configuration request. The value set by full-dword writes to I/O address CF8
10:8	0h RW	FUNCTION_NUM: Function Number: This is the target Function Number of the resulting Configuration request. The value set by full-dword writes to I/O address CF8
7:2	0h RW	DBL_WD: Double Word: This is the target dword of the resulting Configuration request. The value set by full-dword writes to I/O address CF8
1:0	0h RW	CF8_RESERVED_1: Reserved. This field should be always set to 2'b00. The value set by full-dword writes to I/O address CF8



13.2 SoC Transaction Router PCI Config Access IO Registers

SoC Transaction Router PCI Config Access IO Registers

Table 160. Summary of PCI Configuration Space Access I/O Registers

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
CF8–CF8h	1	"ACF8—Offset CF8h" on page 327	00000000h
CFC–CFFh	4	"ACFC—Offset CFCh" on page 328	00000000h

13.2.1 ACF8—Offset CF8h

A-Unit Configuration CF8 Value (ACF8) The A-Unit CF8 (PCI Configuration Address Register) is made available for save/restore purposes. This register is saved and restored by the Punit during S0iX transitions in order to ensure proper handling of a possible subsequent CFC transaction after returning from standby or hibernate state. This is carried over from Aunit implementation in LNC.

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: CF8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CFG_MAP_EN	CF8_RESERVED_0	BUS_NUM	DEVICE_NUM	FUNCTION_NUM	DBL_WD	CF8_RESERVED_1		

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	CFG_MAP_EN: Configuration Space Mapping Enable: This bit enables Configuration Space mapping. The value set by full-dword writes to I/O address CF8
30:24	0h RW	CF8_RESERVED_0: Reserved. The value set by full-dword writes to I/O address CF8
23:16	0h RW	BUS_NUM: Bus Number: This is the target Bus Number of the resulting Configuration request. The value set by full-dword writes to I/O address CF8
15:11	0h RW	DEVICE_NUM: Device Number: This is the target Device Number of the resulting Configuration request. The value set by full-dword writes to I/O address CF8
10:8	0h RW	FUNCTION_NUM: Function Number: This is the target Function Number of the resulting Configuration request. The value set by full-dword writes to I/O address CF8
7:2	0h RW	DBL_WD: Double Word: This is the target dword of the resulting Configuration request. The value set by full-dword writes to I/O address CF8
1:0	0h RW	CF8_RESERVED_1: Reserved. This field should be always set to 2'b00. The value set by full-dword writes to I/O address CF8



13.2.2 ACFC—Offset CFCh

A-Unit Configuration CFC Value (ACFC) The A-Unit CFC (PCI Configuration Data Port).

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: CFCh

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
CFC_VAL								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	CFC_VAL: CFC Value: The value set by full-dword writes to I/O address CFC



13.3 Transaction Router B-Unit Message Registers

Table 161. Summary of B-Unit Message Bus Registers—Port 0x03

Offset	Register Name (Register Symbol)	Default Value
8–8h	"BBANKMASK—Offset 8h" on page 330	0000000Eh
9–9h	"BROWMASK—Offset 9h" on page 331	00FFFFFFEh
A–Ah	"BRANKMASK—Offset Ah" on page 332	00000004h
1A–1Ah	"BIMRDATA—Offset 1Ah" on page 333	00000000h
1B–1Bh	"BPMRVCTL—Offset 1Bh" on page 334	00000000h
23–23h	"BNOCACHE—Offset 23h" on page 335	00000000h
24–24h	"BNOCACHECTL—Offset 24h" on page 336	00000000h
25–25h	"BMBOUND—Offset 25h" on page 337	40000000h
26–26h	"BMBOUND_HI—Offset 26h" on page 337	80000000h
27–27h	"BECREG—Offset 27h" on page 338	00000000h
2E–2Eh	"BSMMRRL—Offset 2Eh" on page 339	00000000h
2F–2Fh	"BSMMRRH—Offset 2Fh" on page 340	00000000h
30–30h	"BC0AHASHCFG—Offset 30h" on page 340	00000000h
3E–3Eh	"BTHCTRL—Offset 3Eh" on page 342	00000001h
3F–3Fh	"BTHMASK—Offset 3Fh" on page 343	FFFFFFFFh



Access Method

Offset: [Port: 0x03] + 8h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_0				BANK_MASK				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	RESERVED_0: Reserved
23:0	0eh RW	BANK_MASK: Bank_mask: Bit mask that corresponds to the location of the bank bits within bits 35:12 of a system address



13.3.2 BROWMASK—Offset 9h

BUnit Row Mask (BROWMASK) The BROWMASK register is used by the address-aware scheduling mechanism to determine the bit location of the row bits within a 35 bit addresses. Bits 23:0 of this register are mapped to bits 35:12 of the addresses in the Bunit tag store

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 9h

Op Codes:

h - Read, h - Write

Default: 00FFFFFFh

31	28	24	20	16	12	8	4	0								
0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	0
RESERVED_0								ROW_MASK								

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	RESERVED_0: Reserved
23:0	ffffffeh RW	ROW_MASK: Row_mask: Bit mask that corresponds to the location of the row bits within bits 35:12 of a system address PnP: Value for perf and powerperf based on drp DIMMDEN0 8Gbit and x16 device which points to column in dunit HAS with rank size 4GB and width x16 (Set all the bits except column bits and we push all the bits up by 1 for system address which makes the mask from bit 14 to bit 34 of system address, hence the value 7ffffc). But VLV will support only 2 ranks so change it to 3ffffc PnP: Set the appropriate value from the Range based on rank density and device width of dram (Note: For 32Bit interfaces, for each of these, simply right shift the corresp option by 1)



Access Method

Offset: [Port: 0x03] + Ah

h - Read, h - Write

Default: 00000004h

Bit Range	Default & Access	Field Name (ID): Description
31:10	00h RO	RESERVED_0: Reserved
9:0	04h RW	RANK_MASK: Rank_mask: Bit mask that corresponds to the location of the rank bits within bits 35:26 of a system address PnP:Set the rankmask from the range based on the rank density and device width of dram used



Bit Range	Default & Access	Field Name (ID): Description
12	0h RO	UNS_IDI_OPC: Unsupported IDI Request Opcode
11:8	0h RO	VIOLATING_AGENT_ID: Protect Asset Access Violation Agent ID: This 4-bit value indicates which agent caused the last access violation if the interrupt is enabled. The Agent ID values are assigned starting with the IDI Attach Points first followed by the PFI Agents. For a configuration using 1 IDI Attach point the IDI Attach Point Agent ID would be 0 and the PFI Agent IDs would start at 1. For 2 IDI Attach Points the IDI Attach Points values would be 0 or 1 and the PFI Agent IDs would start at 2.
7:0	0h RO	VIOLATING_AGENT_ORDERID: Protect Asset Access Violation Order ID: This value indicates the Order ID of the agent that caused the last access violation, if the interrupt is enabled. If access violation was from an IDI attach point this field latches the LPID.

13.3.6 BNOCACHE—Offset 23h

BUnit Non-Cached Region (BNOCACHE) This register defines a region of memory that, when DMA devices behind PFI agents perform an access (whether snooped or not), will not cause an IDI snoop.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 23h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
UPPER_NO_SNOOP_BOUND				LOWER_NO_SNOOP_BOUND				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	UPPER_NO_SNOOP_BOUND: Upper Bound (UpperNoSnoopBound): These bits are compared with bits 35:20 of the incoming address to determine the upper 1MB aligned value of the non-snoop range when EnableNoSnoop is set.
15:0	0000h RW	LOWER_NO_SNOOP_BOUND: Lower Bound (LowerNoSnoopBound): These bits are compared with bits 35:20 of the incoming address to determine the lower 1MB aligned value of the protected range when EnableNoSnoop is set.



13.3.7 BNOCACHECTL—Offset 24h

BUnit Non-Cached Region (BNOCACHECTL)

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 24h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_0								ENABLE_NO_SNOOP

Bit Range	Default & Access	Field Name (ID): Description
31:1	0000h RO	RESERVED_0: Reserved
0	0h RW	ENABLE_NO_SNOOP: Enabled (EnableNoSnoop): When set, Bunit compares bits 35:20 incoming addresses to Upper and Lower NoSnoop Bounds to see if the transaction should be prevented from issuing a processor snoop operation



13.3.8 BMBOUND—Offset 25h

Bunit Memory/IO Boundary Register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 25h

Op Codes:

h - Read, h - Write

Default: 40000000h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	0	0	0	0
HOST_IO_BOUNDARY				RESERVED_0				SEND_ALL_ACCESS_MEM SEND_BOOT_VECTOR_TO_DRAM

Bit Range	Default & Access	Field Name (ID): Description
31:27	008h RW	HOST_IO_BOUNDARY: Host IO Boundary: Bits 31:27 are compared with incoming Host Memory Request addresses to understand whether the associated transactions should be routed to memory space (DRAM) or IO space. The Host IO Boundary starts at this address and continues up to the 4GB address, 0xFFFF_FFFF.
26:2	0000000h RO	RESERVED_0: Reserved
1	0h RW	SEND_ALL_ACCESS_MEM: Send All Accesses to Memory: When set, all accesses will be sent to memory, regardless of address.
0	0h RW	SEND_BOOT_VECTOR_TO_DRAM: When set accesses from 0xFFFF0000-0xFFFFFFFF will be sent to memory regardless of the Host IO Boundary setting.

13.3.9 BMBOUND_HI—Offset 26h

Bunit Memory/IO HI Boundary Register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 26h

Op Codes:

h - Read, h - Write

Default: 80000000h



31	28	24	20	16	12	8	4	0
1	0	0	0	0	0	0	0	0
HOST_IO_BOUND_HIGH				RESERVED_0				

Bit Range	Default & Access	Field Name (ID): Description
31:24	80h RW	HOST_IO_BOUND_HIGH: Host IO Boundary High: Bits 31:24 are compared with bits 35:28 of incoming addresses of all memory accesses above 4GB to understand whether the associated transactions should be routed to memory space (Bunit) or IO space (Aunit). If bits 35:28 of the address are greater than or equal to the Host IO Boundary High register field, then the transaction is routed to the MMIO space.
23:0	0000000h RO	RESERVED_0: Reserved

13.3.10 BECREG—Offset 27h

Bunit Extended Configuration Space Config

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 27h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
ECBASE				RESERVED_0				ECENABLE

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	ECBASE: EC Boundary (ECBase): Describes bits [31:28] of the range being used to access memory-mapped configuration space through the AUnit.
27:1	0000000h RO	RESERVED_0: Reserved
0	0h RW	ECENABLE: EC Enable (ECEnable): When set, causes the ECBase range to be compared to incoming Host Memory Request addresses. If bits [35:28] of a Memory access match the ECBase value, then a posted memory operation is treated as a non-posted operation by the T-unit and A-unit. Additionally, a Memory Write to Configuration Space will be serialized by T-unit and A-unit hardware as Non-Posted Writes



13.3.12 BSMRRH—Offset 2Fh

Bunit System Management Range Register Hi The SMM space is used to protect BIOS or other embedded code from corruption by the operating system. As such, the ranges below only should be set to cover memory space that is mapped into DRAM.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 2Fh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SMM_ENABLE	IWB_EN	PTI_TRACE_EN	RESERVED_0			SMMEND		

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	SMM_ENABLE: SMM Enable: Enables the error checking for the System Management region.
30	0h RW	IWB_EN: Enables IWB
29	0h RW	PTI_TRACE_EN: PTI Trace Enable: Enables snooping of transactions to the SMM region by PTI tracing agents. This bit should be set for VISA Lites so matches/hits to SMM region can be viewed.
28:16	000h RO	RESERVED_0: Reserved
15:0	000h RW	SMMEND: Upper Bound (SMMEnd): These bits are compared with bits 35:20 of the incoming address to determine the upper 1MB aligned value of the protected range .

13.3.13 BC0AHASHCFG—Offset 30h

The Bunit Address Hash Configuration register can be used to enable a hashing function for specifying the bank and rank bits used by the Dunit. When this Address Hashing function is enabled the Bunit Bank Mask and Rank Mask configuration registers should be disabled by writing it with all 0s.

Access Method


Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 30h

Op Codes:

h - Read, h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_0				DIMM1_RANK2_SIZE	DIMM1_PART_WIDTH	RESERVED_1	DIMM0_RANK0_SIZE	DIMM0_PART_WIDTH
							RANK3_ENABLE	RANK2_ENABLE
							RANK1_ENABLE	RANK0_ENABLE
							MEMORY_INTERFACE_WIDTH_32B64B	RANK_INTERLEAVE_ENABLE
								DRAM_ADDRESS_HASH_ENABLE

Bit Range	Default & Access	Field Name (ID): Description
31:18	0h RO	RESERVED_0: Reserved
17:15	0h RW	DIMM1_RANK2_SIZE: Configures the memory size of the ranks used by the address hash function for DIMM1. Note: If the Dunit DIMM Flip bit is set to 1 this field is the rank size for DIMM0. 0h = 128MB 1h = 256MB 2h = 512MB 3h = 1GB 4h = 2GB 5h = 4GB 6h = 8GB 7h = Reserved
14:13	0h RW	DIMM1_PART_WIDTH: Note: If the Dunit DIMM Flip bit is set to 1 this field is the part width for DIMM0. 0h: 8-bit 1h: 16-bit 2h: 32-bit 3h: Reserved
12	0h RO	RESERVED_1: Reserved
11:9	0h RW	DIMM0_RANK0_SIZE: Configures the memory size of the ranks used by the address hash function for DIMM0. Note: If Dunit DIMM Flip bit is set to 1 this field is the rank size for DIMM1. 0h = 128MB 1h = 256MB 2h = 512MB 3h = 1GB 4h = 2GB 5h = 4GB 6h = 8GB 7h = Reserved // PnP: Set based on how ranks are populated. Assuming RANK0,1 on DIMM0 are used.
8:7	0h RW	DIMM0_PART_WIDTH: Note: If the Dunit DIMM Flip bit is set to 1 this field is the part width for DIMM1. // PnP: Set based on how ranks are populated. Assuming x16 0h: 8-bit 1h: 16-bit 2h: 32-bit 3h: Reserved
6	0h RW	RANK3_ENABLE: When set Rank3 for DIMM1 is enable Note: If Dunit DIMM Flip bit is set to 1 this field is the rank enable for rank 1.
5	0h RW	RANK2_ENABLE: When set Rank2 for DIMM1 is enable Note: If Dunit DIMM Flip bit is set to 1 this field is the rank enable for rank 0.
4	0h RW	RANK1_ENABLE: When set Rank1 for DIMM0 is enable Note: If Dunit DIMM Flip bit is set to 1 this field is the rank enable for rank 3.
3	0h RW	RANK0_ENABLE: When set Rank0 for DIMM0 is enable Note: If Dunit DIMM Flip bit is set to 1 this field is the rank enable for rank 2.
2	0h RW	MEMORY_INTERFACE_WIDTH_32B64B: When set to 1: Configures the hashing function for 64b memory interface. When set to 0: Configures the hashing function for 32b memory interface.
1	0h RW	RANK_INTERLEAVE_ENABLE: When Set to 1: Enables hashing function to be used for Dunit Rank Select bits. When Set to 0: Disable the hashing function to be used for Dunit Rank Select bits. PnP: This has to match the RSIEN in DRP register in Dunit
0	0h RW	DRAM_ADDRESS_HASH_ENABLE: When Set to 1: Enables hashing function to be used for Dunit Bank and Rank Select bits. When Set to 0: Disable the hashing function to be used for Dunit Bank and Rank Select bits. When disabled the Dunit Bank and Rank select bits are specified using BBANKMASK And BRANKMASK configuration registers.



13.3.14 BTHCTRL—Offset 3Eh

BUnit Throttling Control (BTHCTRL)

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 3Eh

Op Codes:

h - Read, h - Write

Default: 00000001h

31	28	24	20	16	12	8	4	0															
0	0	0	0	0	0	0	0	1															
AGENT_THROTTLING_ENABLE				RESERVED_0				CLEAR_BW_COUNTER_ON_READS				COUNT_CORE_CLOCKS				ENABLE_BW_COUNTER_UPDATES				RANK_SELECTION_MASK			

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	AGENT_THROTTLING_ENABLE: Agent[15:0] Throttling Enable: Setting a bit in the 16 bit vector allows the BUnit to be configured to throttle Agents 0 to 15 requests in extreme conditions. /PnP: Leaving the Value for Power as ffff but will likely result in very low perf due to lower bandwidth.
15:11	0h RO	RESERVED_0: Reserved
10	0h RW	CLEAR_BW_COUNTER_ON_READS: When set clears the Bandwidth Counter when read.
9	0h RW	COUNT_CORE_CLOCKS: Count Core Clocks (CountCoreClocks): Debug feature used to cause the Bunit to send bandwidth usage updates based upon 1024 core-clock periods, rather than 1024 us periods. In addition, the values reported during bandwidth counter updates will represent 32-byte quantities transferred, instead of 8k byte quantities.
8	0h RW	ENABLE_BW_COUNTER_UPDATES: Enable Bandwidth Counter Updates (EnableBWCounterUpdates): The bandwidth counters always count the reads and writes to even and odd ranks. When updates are enabled, the Bunit will send an update message to the Punit roughly every millisecond with the current values contained in the bandwidth counters. When the message is sent, the counters are reset. When EnableBWCounterUpdates bit is clear, the counters will be reset only by the Clear Bandwidth Counters message.
7:0	01h RW	RANK_SELECTION_MASK: Rank Selection Mask (RankPickMask): Bit mask compared to bits [35:28] of the incoming addresses to determine whether that address maps to Rank 'A' or to Rank 'B'. PnP: Needs to match RANKMASK reg Note: Dunit RANK Hashing implemented for VLV XORs several address bits to create the Rank Select. Therefore this register no longer selects the actual Rank address of the request. Recommendation is to set this value to 0 and only use EVEN BW Counters in BBWC to determine total memory bandwidth.



13.3.15 BTHMASK—Offset 3Fh

Bunit Throttling Masks (BTHMASK) The BTHMASK register contains the fields that control BUnit throttling of transactions to DRAM. If any channel is throttled 100%, by its field being set to all zeroes, then a system deadlock is possible.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x03] + 3Fh

Op Codes:

h - Read, h - Write

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
ORWRITE_MASK								ERREAD_MASK

Bit Range	Default & Access	Field Name (ID): Description
31:24	FFh RW	ORWRITE_MASK: Odd Ranks Write Mask (ORWriteMask): The Odd Rank Write mask is an eight bit value that determines the 1us time slices during which write transactions bound for these DRAM ranks will be allowed to proceed through Bunit arbitration.
23:16	FFh RW	ORREAD_MASK: Odd Ranks Read Mask (ORReadMask): The Odd Rank Read mask is an eight bit value that determines the 1us time slices during which read transactions bound for these DRAM ranks will be allowed to proceed through Bunit arbitration.
15:8	FFh RW	ERWRITE_MASK: Even Rank Write Mask (ERWriteMask): The Even Rank Write mask is an eight bit value that determines the 1us time slices during which write transactions bound for these DRAM ranks will be allowed to proceed through Bunit arbitration.
7:0	FFh RW	ERREAD_MASK: Even Rank Read Mask (ERReadMask): The Even Rank Read mask is an eight bit value that determines the 1us time slices during which read transactions bound for these DRAM ranks will be allowed to proceed through Bunit arbitration.



Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–0h	1	"CUNIT_REG_DEVICEID—Offset 0h" on page 344	00008086h
4–4h	1	"CUNIT_CFG_REG_PCISTATUS—Offset 4h" on page 345	00000007h
8–8h	1	"CUNIT_CFG_REG_CLASSCODE—Offset 8h" on page 346	06000000h
C–Ch	1	"CUNIT_CFG_REG_HDR_TYPE—Offset Ch" on page 347	00000000h
2C–2Ch	1	"CUNIT_CFG_REG_STRAP_SSID—Offset 2Ch" on page 347	00000000h
D0–D3h	4	"CUNIT_MSG_CTRL_REG—Offset D0h" on page 348	00000000h
D4–D4h	1	"CUNIT_MSG_DATA_REG—Offset D4h" on page 348	00000000h
D8–D8h	1	"CUNIT_MSG_CTRL_REG_EXT—Offset D8h" on page 349	00000000h
F8–F8h	1	"CUNIT_MSG_CTRL_REG_EXT—Offset D8h" on page 349	00000000h

CUnit Configuration Register Device ID/Vendor ID. Device ID and Vendor ID Strapped in from top level. Reset value to strapDID[15:3],fuse[2:0], 16'h8086 these bits can be re-written from SETIDVALUE message 1st DW data byte 2, byte 3

Type: PCI Configuration Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
DEVICEID_VENDOR_ID				DEVICEID_BIT_22_19		DEVICEID_BIT_18_16		DEVICEID_BIT_15_0	

Bit Range	Default & Access	Field Name (ID): Description
31:23	0h RW	DEVICEID_VENDOR_ID: Device ID and Vendor ID bit [15:7] are strapped in from top level. These bits can be re-written from SETIDVALUE message 1st DW data byte 2, byte 3. for VLV/VLV2, final setting of this field is from SETIDVALUE message, while for TNG it uses the strapped setting. For all SOC's, the RDL default is set to the strapped setting in that SOC. Please refer to the SoC documentation to determine the proper Device ID for the chip.
22:19	0h RO	DEVICEID_bit_22_19 (DEVICEID_BIT_22_19): Device ID [6:3] Hardwired in the design. SETIDVALUE message will not re-write this field. RDL default is set to the strapped value
18:16	0h RO	DEVICEID_bit_18_16 (DEVICEID_BIT_18_16): Device ID [2:0]. Strapped in from top level and tied to fuses to determine product SKU. SETIDVALUE message will not re-write this field.



Bit Range	Default & Access	Field Name (ID): Description
15:0	8086h RO	DEVICEID_bit_15_0 (DEVICEID_BIT_15_0): Hardwired

13.4.2 CUNIT_CFG_REG_PCISTATUS—Offset 4h

Unit Configuration Register Device ID/Vendor ID

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:0, F:0] + 4h

Default: 00000007h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PCI_STATUS_PCI_CMD								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000007h RO	PCI_STATUS_PCI_CMD: PCI Status and PCI Command. Hardwired to 32'h00000007



Access Method

Offset: [B:0, D:0, F:0] + 8h

	31	28	24	20	16	12	8	4	0
	0	0	0	0	0	0	0	0	0
	0	0	1	1	0	0	0	0	0
	PCI_CLASSCODE_REVID				PCI_BIT_15_8				PCI_BIT_7_0

Bit Range	Default & Access	Field Name (ID): Description
31:16	0600h RO	PCI_CLASSCODE_REVID: PCI Class Code
15:8	00h RO	PCI_BIT_15_8: Hardwired to 8'h00
7:0	0h RW	PCI_BIT_7_0: PCI revision ID. these bits can be re-written from SETIDVALUE message 1st DW data byte 0



13.4.6 CUNIT_MSG_CTRL_REG—Offset D0h

Message Control Register (MCR) - provides the message bus command fields. A write to this register issues a message on the Message Network with the fields specified by the write data. All byte enables must be enabled when writing this register. The physical registers reside in the target unit. This register does not reside in the Cunit.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:0, F:0] + D0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MESSAGE_OPCODE	MESSAGE_PORT	MESSAGE_ADDRESS_OFFSET	MESSAGE_WR_BYTE_ENABLES	RESERVED				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h WO	MESSAGE_OPCODE: Opcode for message to be sent out on message network
23:16	00h WO	MESSAGE_PORT: Destination PortID for message to be sent out on message network
15:8	00h WO	MESSAGE_ADDRESS_OFFSET: Address offset for message to be sent out on message network
7:4	0h WO	MESSAGE_WR_BYTE_ENABLES: Active high byte enables which enable each of the corresponding bytes in the MDR when high.
3:0	00h WO	RESERVED: Reserved

13.4.7 CUNIT_MSG_DATA_REG—Offset D4h

Message Data Register (MDR) - provides the means to specify data to be written or retrieving data that was read during a message operation. For messages with a data payload, MDR must be written with the data to be sent prior to a write to MCR. For messages that return data, MDR contains the data read after the write to MCR completes.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:0, F:0] + D4h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
MESSAGE_DATA_REG								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	SIDEBAND_DATA_REG (MESSAGE_DATA_REG): Sideband Data Register (MDR)

13.4.8 CUNIT MSG CTRL REG EXT—Offset D8h

Message Control Register Extension for MCR/MDR provides bits 31:8 of the address/offset for sideband transactions that require it. Must be written before MCR. Returns to '0 after MCR is written.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:0, F:0] +D8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
MSG_CTRL_REG_EXT				RESERVED				

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000 RW	MSG_CTRL_REG_EXT: Message Control Register Extension for MCR/MDR
7:0	00h RO	RESERVED: Reserved


13.4.9 CUNIT MANUFACTURING ID—Offset F8h

CUnit Manufacturing ID Register

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:0, F:0] + F8h



October 2018
Document Number: 538136, Rev. 4.3

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
RESERVED				MANUFACTURING_ID_BIT_27_24				MANUFACTURING_ID_BIT_23_16				MANUFACTURING_ID_BIT_15_8				MANUFACTURING_ID_BIT_7_0																			

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	RESERVED: Reserved, these bits can be re-written frmo SETIDVALUE message 2nd DW data byte 3 upper nibble
27:24	0h RW	MANUFACTURING_ID_BIT_27_24: Dot Portion of Process, these bits can be re-written from SETIDVALUE message 2nd DW data byte 3 lower nibble
23:16	0h RW	MANUFACTURING_ID_BIT_23_16: Process Portion of Process ID, these bits can be re-written from SETIDVALUE message 2nd DW data byte 0
15:8	0h RW	MANUFACTURING_ID_BIT_15_8: Manufacturing ID (MID), these bits can be re-written from SETIDVALUE message 2nd DW data byte 1
7:0	0h RW	MANUFACTURING_ID_BIT_7_0: Manufacturing Stepping ID (MSID), these bits can be re-written from SETIDVALUE message 2nd DW data byte 2





Bit Range	Default & Access	Field Name (ID): Description
15:0	8086h RO	DEVICEID_bit_15_0 (DEVICEID_BIT_15_0): Hardwired

13.5.2 CUNIT_CFG_REG_PCISTATUS—Offset 1h

Unit Configuration Register Device ID/Vendor ID

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x08] + 1h

Op Codes:

Default: 00000007h

31	28	24	20	16	12	8	4	0															
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1
PCI_STATUS_PCI_CMD																							

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000007h RO	PCI_STATUS_PCI_CMD: PCI Status and PCI Command. Hardwired to 32'h00000007

13.5.3 CUNIT_CFG_REG_CLASSCODE—Offset 2h

CUnit Configuration register Header Type and Master Latency Time

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x08] + 2h

Op Codes:

Default: 06000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	1	1	0	0	0	0	0
PCI_CLASSCODE_REVID				PCI_BIT_15_8				PCI_BIT_7_0

Bit Range	Default & Access	Field Name (ID): Description
31:16	0600h RO	PCI_CLASSCODE_REVID: PCI Class Code
15:8	00h RO	PCI_BIT_15_8: Hardwired to 8'h00
7:0	0h RW	PCI_BIT_7_0: PCI revision ID. these bits can be re-written from SETIDVALUE message 1st DW data byte 0

13.5.4 CUNIT_CFG_REG_HDR_TYPE—Offset 3h

CUnit Configuration Register Device ID/Vendor ID

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x08] + 3h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MSTRLATENCY_HDRTYPE								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	MSTRLATENCY_HDRTYPE: Master Latency Timer and Header Type hardwired to 0



13.5.6 CUNIT_MANUFACTURING_ID—Offset 3Eh

CUnit Manufacturing ID Register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x08] + 3Eh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED	MANUFACTURING_ID_BIT_27_24	MANUFACTURING_ID_BIT_23_16	MANUFACTURING_ID_BIT_15_8	MANUFACTURING_ID_BIT_7_0				

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	RESERVED: Reserved, these bits can be re-written frmo SETIDVALUE message 2nd DW data byte 3 upper nibble
27:24	0h RW	MANUFACTURING_ID_BIT_27_24: Dot Portion of Process, these bits can be re-written from SETIDVALUE message 2nd DW data byte 3 lower nibble
23:16	0h RW	MANUFACTURING_ID_BIT_23_16: Process Portion of Process ID, these bits can be re-written from SETIDVALUE message 2nd DW data byte 0
15:8	0h RW	MANUFACTURING_ID_BIT_15_8: Manufacturing ID (MID), these bits can be re-written from SETIDVALUE message 2nd DW data byte 1
7:0	0h RW	MANUFACTURING_ID_BIT_7_0: Manufacturing Stepping ID (MSID), these bits can be re-written from SETIDVALUE message 2nd DW data byte 2



13.6 Transaction Router P-Unit Message Registers

Table 164. Summary of Transaction Router P-Unit Message Bus Registers—Port 0x04

Offset	Register Name (Register Symbol)	Default Value
1-1h	"THERMAL_SOC_TRIGGER—Offset 1h" on page 358	00000000h
2-2h	"CPU_POWER_BUDGET_CONTROL—Offset 2h" on page 360	00000000h
3-3h	"SOC_POWER_BUDGET_CONTROL—Offset 3h" on page 361	00000000h
4-4h	"TURBO_SOC_OVERRIDE—Offset 4h" on page 361	00000000h
5-5h	"BIOS_RESET_CPL—Offset 5h" on page 362	00000000h
6-6h	"BIOS_CONFIG—Offset 6h" on page 363	00000000h
1D-1Dh	"BIOSCFG_IPDEVTYPE—Offset 1Dh" on page 364	00000000h
1E-1Eh	"PUNIT_S0i2_PREWAKE—Offset 1Eh" on page 364	00000000h
1F-1Fh	"PUNIT_S0i3_PREWAKE—Offset 1Fh" on page 365	00000000h
32-32h	"VEDSSPM0—Offset 32h" on page 365	03000003h
33-33h	"VEDSSPM1—Offset 33h" on page 366	00000000h
36-36h	"DSPSSPM—Offset 36h" on page 367	00000000h
39-39h	"ISPSSPM0—Offset 39h" on page 368	03000003h
3A-3Ah	"ISPSSPM1—Offset 3Ah" on page 368	00000000h
3B-3Bh	"MIOSSPM—Offset 3Bh" on page 369	00000000h
60-60h	"PWRGT_CNT_CTRL—Offset 60h" on page 370	00000000h
61-61h	"PWRGT_STATUS—Offset 61h" on page 371	00000000h
62-62h	"PWRGT_INTREN—Offset 62h" on page 372	00000000h
7C-7Ch	"CPU_SOFT_STRAPS—Offset 7Ch" on page 374	00000000h
80-80h	"PTMC—Offset 80h" on page 375	00000000h
81-81h	"TTR0—Offset 81h" on page 377	00000000h
82-82h	"TTR1—Offset 82h" on page 377	00000000h
83-83h	"TTS—Offset 83h" on page 378	00000000h
84-84h	"TELB—Offset 84h" on page 378	00000000h
85-85h	"TELT—Offset 85h" on page 379	00000000h
86-86h	"TQPR—Offset 86h" on page 380	00000000h
88-88h	"GFXT—Offset 88h" on page 381	00000000h
89-89h	"VEDT—Offset 89h" on page 382	00000000h
8C-8Ch	"ISPT—Offset 8Ch" on page 383	00000000h
B0-B0h	"DTSC—Offset B0h" on page 384	00000000h
B1-B1h	"TRR—Offset B1h" on page 385	00000000h
B2-B2h	"PTPS—Offset B2h" on page 386	00000000h
B3-B3h	"PTTS—Offset B3h" on page 386	00000000h
B4-B4h	"PTSS—Offset B4h" on page 388	00000000h
B5-B5h	"TE_AUX0—Offset B5h" on page 389	00000000h
B6-B6h	"TE_AUX1—Offset B6h" on page 391	00000000h



Table 164. Summary of Transaction Router P-Unit Message Bus Registers—Port 0x04

Offset	Register Name (Register Symbol)	Default Value
B7-B7h	"TE_AUX2—Offset B7h" on page 392	00000000h
B8-B8h	"TE_AUX3—Offset B8h" on page 394	00000000h
B9-B9h	"TTE_VRIccMax—Offset B9h" on page 395	00000000h
BA-BAh	"TTE_VRHot—Offset BAh" on page 396	00000000h
BB-BBh	"TTE_XXPROCHOT—Offset BBh" on page 397	00000000h
BC-BCh	"TTE_SLM0—Offset BCh" on page 399	00000000h
BD-BDh	"TTE_SLM1—Offset BDh" on page 400	00000000h
BE-BEh	"BWTE—Offset BEh" on page 401	00000000h
BF-BFh	"TTE_SWT—Offset BFh" on page 402	00000000h
D1-D1h	"PUNIT_GPU_EC—Offset D1h" on page 404	00000000h
D2-D2h	"PUNIT_GPU_EC_VIRUS—Offset D2h" on page 404	00000000h
D3-D3h	"PUNIT_GPU_LFM—Offset D3h" on page 405	00000000h
D4-D4h	"PUNIT_GPU_FREQ_REQ—Offset D4h" on page 405	00000000h
D8-D8h	"PUNIT_GPU_FREQ_STS—Offset D8h" on page 406	00000000h
108-108h	"DPTF_TELB—Offset 108h" on page 406	00000000h
109-109h	"DPTF_GFXT—Offset 109h" on page 407	00000000h
10A-10Ah	"DPTF_VEDT—Offset 10Ah" on page 408	00000000h
10B-10Bh	"DPTF_VECT—Offset 10Bh" on page 408	00000000h
10C-10Ch	"DPTF_VSPT—Offset 10Ch" on page 409	00000000h
10D-10Dh	"DPTF_ISPT—Offset 10Dh" on page 410	00000000h

13.6.1 THERMAL_SOC_TRIGGER—Offset 1h

Driver Software (like Burst Mode Governor) may use this register to indicate TSKIN violation.

Access Method


Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 1h

Op Codes:

h - Read, h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	HOTTEST_DIE_TEMP_READING		UNUSED_TSKIN_WARNING_THRESHOLD		TSKIN_TEMP_STATUS1	UNUSED_PMICRO_ICC_MAX	UNUSED_TSKIN_TEMP_STATUS	UNUSED_TSKIN_SPARE
							UNUSED_TSKIN_WARNING	CPU_POWER
								UNUSED_TSKIN_VIOLATION

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RW	HOTTEST_DIE_TEMP_READING: Stores the hottest DTS sample of all thermal sensors in the CPU+SOC.
23:16	0h RW	UNUSED_TSKIN_WARNING_THRESHOLD: THIS FIELD IS UNUSED IN VLV/TNG. For platforms which implement a Tskin temperature sensor, this field can be used to specify the temperature limit above which TSKIN_WARNING will be set and Turbo operation will be disabled in the SOC.
15:12	0h RW	TSKIN_TEMP_STATUS1: THIS FIELD IS UNUSED IN VLV/TNG. For platforms which implement a Tskin temperature sensor, this field can be used to report the TSKIN temperature value for use by Punit firmware.
11	0h RO	UNUSED_PMICRO_ICC_MAX: THIS FIELD IS UNUSED IN VLV/TNG. Bit 11 is used indicate a Vcc Icc max condition. It is driven by the firmware when it gets a SVID update indicating a icc max hot condition. The firmware drives it back low when the hot condition is resolved when it gets a SVID update.
10:8	0h RW	UNUSED_TSKIN_TEMP_STATUS: THIS FIELD IS UNUSED IN VLV/TNG. For platforms which implement a Tskin temperature sensor, this field can be used to report the TSKIN temperature value for use by Punit firmware.
7:3	0h RW	UNUSED_TSKIN_SPARE: THIS FIELD IS UNUSED IN VLV/TNG. Spare for future tskin related controls
2	0h RW	UNUSED_TSKIN_WARNING: THIS FIELD IS UNUSED IN VLV/TNG. Early warning flag for TSKIN to be set by SCU, PUnit or platform driver to take early action to reduce power consumption...When asserted Punit will disable Turbo range of operation for CPU and GPU and limit operation to Guaranteed frequency. For systems which provide Tskin temperature punit may set this bit if Tskin exceeds TSKIN_WARNING_THRESHOLD...0 - Tskin warning is not triggered...1 - Tskin warning is triggered and CPU/GPU operation should be limited to Guaranteed frequencies.
1	0h RW	CPU_POWER: Reserved.
0	0h RW	UNUSED_TSKIN_VIOLATION: THIS FIELD IS UNUSED IN VLV/TNG. This bit can be set by the SOC or PUnit firmware to indicate that the system thermals are exceeding the Tskin spec. Setting this bit will trigger any enabled CPU thermal throttling mechanisms to take effect. Thermal throttling will remain active until this bit is cleared. For systems which provide Tskin temperature punit may set this bit if Tskin exceeds TSKIN_THROTTLE_THRESHOLD...0 tskin is not violated...1 trigger thermal throttling mechanisms to reduce platform temperature..



13.6.2 CPU_POWER_BUDGET_CONTROL—Offset 2h

TDP power budget utilization/budget for SOC; This register requires SAI security restriction.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 2h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED_7	SPARE	IBC_LIMIT_ENABLE	IBC_RATIO_LIMIT	RESERVED_3	TURBOEM_FCPU_FLOOR		TURBOEM_FCPU_GAIN	

Bit Range	Default & Access	Field Name (ID): Description
31	0h RO	RESERVED_7: reserved
30:25	0h RW	SPARE: Reserved.
24	0h RW	IBC_LIMIT_ENABLE: Enables IBC IA Pstate Limiting control. When set, the CPU frequency will be limited according to IBC_RATIO_LIMIT.
23:16	0h RW	IBC_RATIO_LIMIT: IBC IA Pstate Limiting control for GFX driver to limit the max CPU frequency (bounded by TURBOEM_FCPU_FLOOR and MAX_RATIO_1C). Will only take effect if IBC_LIMIT_ENABLE is set. The CPU ratio is limited to this ratio if Turbo is enabled in the system. Default value of 0 is mapped to MAX_RATIO_1C. Value of 1 is mapped to RATIO 1, etc.
15	0h RW	RESERVED_3: reserved
14:8	0h RW	TURBOEM_FCPU_FLOOR: Specifies the target ratio floor when the PL1 proportional controller or IBC_RATIO_LIMIT is in effect. Default value of 0 is mapped to GUAR_RATIO. Value of 1 is mapped to RATIO 1, etc. Note that values lower than LFM_RATIO may be clipped by hardware to LFM_RATIO.
7:0	0h RW	TURBOEM_FCPU_GAIN: Specifies the scaling factor for PL1 proportional controller to map CPU energy budget to ratio limit during Energy Management Turbo Mode. Target ratio = LFM_RATIO + energy_credit / (gain+1)



Bit Range	Default & Access	Field Name (ID): Description
31:5	0h RO	RESERVED_4: reserved
4:2	0h RW	SOC_TDP_POLICY: Overrides PKG_TURBO_CFG1[SOC_TDP_POLICY]. Refer PKG_TURBO_CFG1 register description for more info...Device Driver software may use this register to dynamically adjust power sharing configuration between CPU and SOC
1	0h RW	SOC_TDP_EN: Overrides PKG_TURBO_CFG1[SOC_TDP_EN]. Refer to PKG_TURBO_CFG1 register description for more info. ..Device Driver software may use this register to dynamically adjust power sharing configuration between CPU and SOC
0	0h RW	OVERRIDE_EN: Allows fields in this register to override corresponding Turbo MSR fields.

13.6.5 BIOS_RESET_CPL—Offset 5h

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 5h


Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0		
RESERVED_8						PUNIT_RTOS_DONE	RESERVED_5		BIOS_ALL_DONE	BIOS_RESET_DONE

Bit Range	Default & Access	Field Name (ID): Description
31:9	0h RO	RESERVED_9 (RESERVED_8): reserved
8	0h RW	PUNIT_RTOS_DONE: Punit will set this bit once firmware initialization of all tasks is completed. Simulation may poll this bit to hold-off code execution until Punit has safely initialized.
7:2	0h RW	RESERVED_5: Reserved
1	0h RW	BIOS_ALL_DONE: This bit indicates to the P unit that it can execute its periodic tasks.
0	0h RW	BIOS_RESET_DONE: This bit indicates to the P unit that the Patch loading is completed and the firmware can restart execution. Firmware will poll on this bit to be set. Note: This bit must be sticky once set and can only be cleared by a core reset.



13.6.6 BIOS_CONFIG—Offset 6h

Punit-BIOS controls

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 6h

Op Codes:

h - Read, h - Write

Default: 00000000h

31				28				24				20				16				12				8				4				0																			
0				0				0				0				0				0				0				0				0																			
ECC_EN				DUAL_CH_DIS				EFF_ECC_EN				EFF_DUAL_CH_EN				Reserved_9				BIOS_PDM				DFX_PDM_MODE				Reserved_6				DDRIO_PWRGATE				GFX_TURBO_DISABLE				Reserved_4				PCIE_PLLOFFOK_EN				USB_CACHING_EN			

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	ECC_EN: Setting this bit allows using a fused Dual Channel part as a single channel part with the second Channel being used for ECC.
30	0h RW	DUAL_CH_DIS: Setting this bit allows using a fused Dual Channel part as a single Channel part.
29	0h RW	EFF_ECC_EN: Effective ECC Status bit indicating if ECC is enabled(1) or disabled(0) based on the Fuse and the Downbin bit
28	0h RW	EFF_DUAL_CH_EN: Effective Dual Channel Status bit indicating if Dual Channel is enabled(1) or Single Channel is enabled(0)
27:18	0h RW	Reserved_9: Unused, reserved for future use.
17	0h RW	DFX_POWERGATING (BIOS_PDM): 0: Power Save Mode- Powergate DFX for power savings 1: PERF_MODE or PDM_MODE: Leave DFX blocks powered up BIOS must always set this bit before BIOS_RESET_CPL[1:0] bits are set. BYT-M and BYT-D segments leave DFX Powered up. BYT-T segments provide user option to leave DFX powered up or powered down. BIOS can change the DFX_Powergating bit to 0 to powergate DFX.
16	0h RW	DFX_PDM_MODE: This bit has effect only when DFX_Powergating (bit 17) is set. 0: PERF_MODE: Access to Performance Counters for SOCHAPs, Memory Traffic etc. 1: PDM_MODE: Memory BW counts not available but PDM debug messages are available
15:9	0h RW	Reserved_6: Reserved
8	0h RW	DDRIO_PWRGATE: Firmware sets bit 8 by default to disable ddrrio powergating in S0i3. If BIOS writes to this BYTE, it must set bit 8 to avoid clobbering firmware update. DDRIO_PWRGATE is not supported on VLV. This bit is relevant only for SKUs supporting S0i3.
7	0h RW	GFX_TURBO_DISABLE: Setting this bit will disable GFX TURBO, even if the Fuses enable it. Setting this bit is not recommended for VLV
6:2	0h RW	Reserved_4: Unused, reserved for future use.



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	s0i2_PREWAKE: BIOS or OS can program this register with a pre-wake value in Guaranteed MCLKs to hide some of the exit latency from S0i2 state to S0 state. P unit will subtract this value from the actual deadline programmed by the OS when requesting for a timer wake.

13.6.9 PUNIT_S0i3_PREWAKE—Offset 1Fh

BIOS or OS can program this register with a pre-wake value in Guaranteed MCLKs to hide some of the exit latency from S0i3 state to S0 state. P unit will subtract this value from the actual deadline programmed by the OS when requesting for a timer wake.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 1Fh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	s0i3_PREWAKE: S0i3 Prewake Deadline

13.6.10 VEDSSPM0—Offset 32h

Subsystem Config/Status for VED

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 32h

Op Codes:

h - Read, h - Write

Default: 03000003h





Bit Range	Default & Access	Field Name (ID): Description
28:24	0h RO	VEDFREQSTAT40: VED Frequency Status
23:13	0h RO	Reserved_3: Reserved
12:8	0h RW	VEDFREQGUAR40: VED Guaranteed Frequency- Place holder for future use.
7	0h RW	FREQVALID: if and only if this bit is set the freq requested in the FREQ field will be looked at by the Punit and will clear this field once the freq status is updated
6:5	0h RO	Reserved_6: Reserved
4:0	0h RW	VEDFREQ40: VED driver requested Frequency

13.6.12 DSPSSPM—Offset 36h

Subsystem Config/Status for Display

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 36h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSPFREQSTAT	Reserved_5				DSPFREQREQ	Reserved_7		Reserved_9

Bit Range	Default & Access	Field Name (ID): Description
31:30	0h RO	DSPFREQSTAT: Display frequency status
29:16	0h RO	Reserved_5: Reserved
15:14	0h RW	DSPFREQREQ: Display frequency request
13:8	0h RO	Reserved_7: Reserved
7:0	0h RO	Reserved_9: Reserved



Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RO	Reserved_1: Reserved
28:24	0h RO	ISPFREQSTAT40: ISP Frequency Status
23:13	0h RO	Reserved_3: Reserved
12:8	0h RW	ISPFREQGUAR40: ISP Guaranteed Frequency
7	0h RW	FREQVALID: if and only if this bit is set the freq requested in the FREQ field will be looked at by the Punit and will clear this field once the freq status is updated
6:5	0h RO	Reserved_6: Reserved
4:0	0h RW	ISPFREQ40: ISP driver requested Frequency

13.6.15 MIOSSPM—Offset 3Bh

Subsystem Config/Status for MIO

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 3Bh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1	MIOSS	Reserved_3	Reserved_4	MIOSSC				

Bit Range	Default & Access	Field Name (ID): Description
31:26	0h RO	Reserved_1: Reserved
25:24	0h RO	MIOSS: MIO Subsystem Status Status0x03 indicates powered off state, 0x00 indicates powered on state. P unit will write this field to register field to reflect the status for power up or power down for the MIPI IO .Driver is expected to poll for the power up status before accessing the IP.
23:8	0h RO	Reserved_3: Reserved
7:2	0h RO	Reserved_4: Reserved
1:0	0h RW	MIOSSC: MIO (CSI) SubsystemControl- 0x03 indicates powered off state, 0x00 indicates powered on state. Driver will write this field to register field to request power up or power down for the MIPI controller. Note the implementation does not actually power gate, but will turn off the clock trunks and apply reset to MIO .



Access Method

Offset: [Port: 0x04] + 60h

h - Read, h - Write

31				28				24				20				16				12				8				4				0																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																				
POWERGATE_RESERVED5				POWERGATE_RESERVED4				POWERGATE_RESERVED3				POWERGATE_RESERVED2				POWERGATE_RX1				POWERGATE_RX0				POWERGATE_TX3				POWERGATE_TX2				POWERGATE_TX1				POWERGATE_TX0				POWERGATE_CMNIN				POWERGATE_RESERVED1				POWERGATE_DISPLAY_CTL				POWERGATE_RESERVED0			

Bit Range	Default & Access	Field Name (ID): Description
31:30	0h RW	POWERGATE_RESERVED5: Reserved
29:28	0h RW	POWERGATE_RESERVED4: Reserved
27:26	0h RW	POWERGATE_RESERVED3: Reserved
25:24	0h RW	POWERGATE_RESERVED2: Reserved
23:22	0h RW	POWERGATE_RX1: Active power gate control for RX lane 0x03 indicates powered off state, 0x00 indicates powered on state
21:20	0h RW	POWERGATE_RX0: Active power gate control for RX lane 0x03 indicates powered off state, 0x00 indicates powered on state
19:18	0h RW	POWERGATE_TX3: Active power gate control for TX lane 0x03 indicates powered off state, 0x00 indicates powered on state
17:16	0h RW	POWERGATE_TX2: Active power gate control for TX lane 0x03 indicates powered off state, 0x00 indicates powered on state
15:14	0h RW	POWERGATE_TX1: Active power gate control for TX lane 0x03 indicates powered off state, 0x00 indicates powered on state



Bit Range	Default & Access	Field Name (ID): Description
13:12	0h RW	POWERGATE_TX0: Active power gate control for TX lane 0x03 indicates powered off state, 0x00 indicates powered on state
11:10	0h RW	POWERGATE_CMNLN: Active power gate control for common lane 0x03 indicates powered off state, 0x00 indicates powered on state. Driver will write this field to register field to request power up or power down for the DP10 common lane. Note that before powering up the TX/RX subsystems for DP10, from a power down state, CMNLN reset (POWERGATE_CMNLN) must be cycled
9:8	0h RW	POWERGATE_RESERVED1: Reserved
7:6	0h RW	POWERGATE_DISPLAY_CTL: Active power gate control for display, DP10x03 indicates powered off state, 0x00 indicates powered on state. Driver will write this field to register field to request power up or power down for the Display Controller
5:0	0h RW	POWERGATE_RESERVED0: Reserved

13.6.17 PWRGT_STATUS—Offset 61h

Power Gate Status; This register indicates the status of the voltage islands for the various blocks that the P unit controls. This register is updated by the firmware after servicing request from driver to power up / power down of the various islands. Each island is controlled by a 2-bit field. 00 -- no clock or power gating, 01 -- clock gating, 10 -- reset and 11 -- power gating. (Encoding is as follows: subsys 0 RENDER, 1 media, 3 -Display, DP10 : subsystem 5 Common lane, subs 6-9 TX, subs 10-11 RX)

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 61h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PWRGATESTATUS_RESERVED5	PWRGATESTATUS_RESERVED4	PWRGATESTATUS_RESERVED3	PWRGATESTATUS_RESERVED2	PWRGATESTATUS_RX1	PWRGATESTATUS_RX0	PWRGATESTATUS_TX3	PWRGATESTATUS_TX2	PWRGATESTATUS_TX1
								PWRGATESTATUS_TX0
								PWRGATESTATUS_CMNLN
								PWRGATESTATUS_RESERVED1
								PWRGATESTATUS_DISPLAY_CTL
								PWRGATESTATUS_RESERVED0
								PWRGATESTATUS_MEDIA
								PWRGATESTATUS_RENDER

Bit Range	Default & Access	Field Name (ID): Description
31:30	0h RW	PWRGATESTATUS_RESERVED5: Reserved
29:28	0h RW	PWRGATESTATUS_RESERVED4: Reserved



Bit Range	Default & Access	Field Name (ID): Description
27:26	0h RW	PWRGATESTATUS_RESERVED3: Reserved
25:24	0h RW	PWRGATESTATUS_RESERVED2: Reserved
23:22	0h RW	PWRGATESTATUS_RX1: Power gate status for RX. Status0x03 indicates powered off state, 0x00 indicates powered on state.
21:20	0h RW	PWRGATESTATUS_RX0: Power gate status for RX. Status0x03 indicates powered off state, 0x00 indicates powered on state.
19:18	0h RW	PWRGATESTATUS_TX3: Power gate status for TX. Status0x03 indicates powered off state, 0x00 indicates powered on state.
17:16	0h RW	PWRGATESTATUS_TX2: Power gate status for TX. Status0x03 indicates powered off state, 0x00 indicates powered on state.
15:14	0h RW	PWRGATESTATUS_TX1: Power gate status for TX. Status0x03 indicates powered off state, 0x00 indicates powered on state.
13:12	0h RW	PWRGATESTATUS_TX0: Power gate status for TX Status0x03 indicates powered off state, 0x00 indicates powered on state.
11:10	0h RW	PWRGATESTATUS_CMNLN: Power gate status for common lane. Status0x03 indicates powered off state, 0x00 indicates powered on state. P unit will write this field to register field to reflect the status for power up or power down for the DPIO common lane
9:8	0h RW	PWRGATESTATUS_RESERVED1: Reserved
7:6	0h RW	PWRGATESTATUS_DISPLAY_CTL: Power gate status for display, Status0x03 indicates powered off state, 0x00 indicates powered on state. P unit will write this field to register field to reflect the status for power up or power down for the Display controller .Driver is expected to poll for the power up status before accessing the IP.
5:4	0h RW	PWRGATESTATUS_RESERVED0: Reserved
3:2	0h RW	PWRGATESTATUS_MEDIA: Power gate status for media Status0x03 indicates powered off state, 0x00 indicates powered on state. P unit will write this field to register field to reflect the status for power up or power down for the Media IP. The request for power up or power down for media are hardware triggered.
1:0	0h RW	PWRGATESTATUS_RENDER: Power gate status for RENDer - Status0x03 indicates powered off state, 0x00 indicates powered on state. P unit will write this field to register field to reflect the status for power up or power down for the Render engine. The request for power up or power down for Render are hardware triggered.

13.6.18 PWRGT_INTREN—Offset 62h

Power Gate Interrupt enable;This register indicates the interrupt enables for the power islands for the various blocks that the P unit controls. The software driver sets this bit to trigger an interrupt when the particular subsystem is brought back to D0. There is one bit for each of the subsystem . At reset/powerup, all IE comes up as 0, indicating interrupts are not enabled. (Encoding is as follows: subsys 0 RENDer, 1 media, 3 - Display, no control hook for DPIO)

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 62h

Op Codes:

h - Read, h - Write



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PWRGINTREN_LISLAND_RESERVED12	PWRGINTREN_LISLAND_RESERVED11	PWRGINTREN_LISLAND_RESERVED10	PWRGINTREN_LISLAND_RESERVED9	PWRGINTREN_LISLAND_RESERVED8	PWRGINTREN_LISLAND_RESERVED7	PWRGINTREN_LISLAND_RESERVED6	PWRGINTREN_LISLAND_RESERVED5	PWRGINTREN_LISLAND_RESERVED4
PWRGINTREN_LISLAND_RESERVED3	PWRGINTREN_LISLAND_RESERVED2	PWRGINTREN_LISLAND_RESERVED1	PWRGINTREN_LISLAND_DISPLAY	PWRGINTREN_LISLAND_RESERVED0	PWRGINTREN_LISLAND_MEDIA	PWRGINTREN_LISLAND_RENDER	PWRGATEINTREN_RESERVED12	PWRGATEINTREN_RESERVED11
PWRGATEINTREN_RESERVED10	PWRGATEINTREN_RESERVED9	PWRGATEINTREN_RESERVED8	PWRGATEINTREN_RESERVED7	PWRGATEINTREN_RESERVED6	PWRGATEINTREN_RESERVED5	PWRGATEINTREN_RESERVED4	PWRGATEINTREN_RESERVED3	PWRGATEINTREN_RESERVED2
PWRGATEINTREN_RESERVED1	PWRGATEINTREN_DISPLAY	PWRGATEINTREN_RESERVED0	PWRGATEINTREN_MEDIA	PWRGATEINTREN_RENDER				

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	PWRGINTREN_LISLAND_RESERVED12: Reserved
30	0h RW	PWRGINTREN_LISLAND_RESERVED11: Reserved
29	0h RW	PWRGINTREN_LISLAND_RESERVED10: Reserved
28	0h RW	PWRGINTREN_LISLAND_RESERVED9: Reserved
27	0h RW	PWRGINTREN_LISLAND_RESERVED8: Reserved
26	0h RW	PWRGINTREN_LISLAND_RESERVED7: Reserved
25	0h RW	PWRGINTREN_LISLAND_RESERVED6: Reserved
24	0h RW	PWRGINTREN_LISLAND_RESERVED5: Reserved
23	0h RW	PWRGINTREN_LISLAND_RESERVED4: Reserved
22	0h RW	PWRGINTREN_LISLAND_RESERVED3: Reserved
21	0h RW	PWRGINTREN_LISLAND_RESERVED2: Reserved
20	0h RW	PWRGINTREN_LISLAND_RESERVED1: Reserved
19	0h RW	PWRGINTREN_LISLAND_DISPLAY: power gate Interrupt sts for local standby island display, no control hook for DPIIO. Not used for VLV
18	0h RW	PWRGINTREN_LISLAND_RESERVED0: Reserved
17	0h RW	PWRGINTREN_LISLAND_MEDIA: power gate Interrupt sts for local standby island media. Not used for VLV



Bit Range	Default & Access	Field Name (ID): Description
16	0h RW	PWRGINTREN_LISLAND_RENDERER: power gate Interrupt sts for local standby island RENder. Not used for VLV
15	0h RW	PWRGATEINTREN_RESERVED12: Reserved
14	0h RW	PWRGATEINTREN_RESERVED11: Reserved
13	0h RW	PWRGATEINTREN_RESERVED10: Reserved
12	0h RW	PWRGATEINTREN_RESERVED9: Reserved
11	0h RW	PWRGATEINTREN_RESERVED8: Reserved
10	0h RW	PWRGATEINTREN_RESERVED7: Reserved
9	0h RW	PWRGATEINTREN_RESERVED6: Reserved
8	0h RW	PWRGATEINTREN_RESERVED5: Reserved
7	0h RW	PWRGATEINTREN_RESERVED4: Reserved
6	0h RW	PWRGATEINTREN_RESERVED3: Reserved
5	0h RW	PWRGATEINTREN_RESERVED2: Reserved
4	0h RW	PWRGATEINTREN_RESERVED1: Reserved
3	0h RW	PWRGATEINTREN_DISPLAY: power gate interrupt status for display, no control hook for DPIO
2	0h RW	PWRGATEINTREN_RESERVED0: Reserved
1	0h RW	PWRGATEINTREN_MEDIA: power gate interrupt status for media
0	0h RW	PWRGATEINTREN_RENDERER: power gate interrupt status for RENder

13.6.19 CPU_SOFT_STRAPS—Offset 7Ch

Register for BIOS software configurable CPU Power on Reset Configuration. This register survives CPU-only reset and SOC Warm reset. BIOS can access is register using CFC/CF8 mechanism. Accessible through MSG Bus Port 04h.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 7Ch

Op Codes:

h - Read, h - Write



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_4						POC_NUM_CORES	RESERVED_2	POC_RUN_BIST

Bit Range	Default & Access	Field Name (ID): Description
31:11	0h RO	RESERVED_4: Reserved
10:8	0h RW	POC_NUM_CORES: Core defeature via BIOS...000b Do not defeature IA cores...001b Only 1 Logical Core is active...010b Only 2 Logical Cores are active...011b Only 3 Logical Cores are active...1xxb Reserved (for 8 Core config)... ..Exposed to CPU microcode as CLPU_CR_RESOLVED_CORE_VECTOR, CLPU_CR_RESOLVED_CORE_VECTOR and CLPU_CR_WHO_AM_I via RESET_CONFIG_CW (CPU PMlink space)... ..Punit will determine the RESOLVED_CORE_VECTOR based on the table in HSD Issue 1214773...
7:1	0h RO	RESERVED_2: Reserved
0	0h RW	POC_RUN_BIST: Writing a 1 will cause the CPU microcode to execute BIST on the L2\$ at CPU reset deassertion (CPU only reset or Warm Reset).

13.6.20 PTMC—Offset 80h

Programmable Thermtrip Management Control

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 80h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_1				CPU_MOD1 MOD0_THERM_EN	RESERVED_4	SW_TRIGGER BW_THROT_EN XXTS_THERM_EN PROCHOT_THERM_EN SVIDVR_ICC_EN SVID_THERM_EN	RESERVED_11	AUX3_THERM_EN AUX2_THERM_EN AUX1_THERM_EN AUX0_THERM_EN

Bit Range	Default & Access	Field Name (ID): Description
31:18	0h RO	RESERVED_1: Reserved



Bit Range	Default & Access	Field Name (ID): Description
17	0h RW	CPU_MOD1: CPU Module1: Indicates CPU Module0 can trigger thermal event
16	0h RW	MOD0_THERM_EN: CPU Module0: Indicates CPU Module0 can trigger thermal event
15:14	0h RO	RESERVED_4: Reserved
13	0h RW	SW_TRIGGER: Indicates Software can program SWT register to initiate thermal event
12	0h RW	BW_THROT_EN: Indicates excess memory bandwidth can trigger a thermal event
11	0h RW	XXTTS_THERM_EN: XXTTS (Reserved): Indicates Thermal Sensor from platform can trigger thermal event (Not supported in Valleyview)
10	0h RW	PROCHOT_THERM_EN: XXPCHOT: Indicates a Platform Prochot can cause thermal event
9	0h RW	SVIDVR_ICC_EN: Indicates the VR Icc Max can cause thermal event...The trip is triggered for both Vcc and Vnn
8	0h RW	SVID_THERM_EN: sVID(VR_Icc_Max/VR_Hot): Indicates VR status bits can cause thermal event
7:4	0h RO	RESERVED_11: Reserved
3	0h RW	AUX3_THERM_EN: AUX3: Indicates AUX3 (Hot Trip) can initiate a thermal event
2	0h RW	AUX2_THERM_EN: AUX2: Indicates AUX2 can initiate a thermal event
1	0h RW	AUX1_THERM_EN: AUX1: Indicates AUX1 can initiate a thermal event
0	0h RW	AUX0_THERM_EN: AUX0: Indicates AUX0 can initiate a thermal event



VLV Bandwidth Trip Thresholds

Access Method

Offset: [Port: 0x04] + 83h

Op Codes:

h - Read, h - Write

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RO	RESERVED_1: Reserved
15:8	0h RW	WR_THRESHOLD: Write Threshold: Indicates a threshold to initiate a trip for the throttle mechanism. This value will be compared against the total Write count FOR BOTH RANKS from the event counters when there is no internal thermal sensor configured for VLV protection.
7:0	0h RW	RD_THRESHOLD: Read Threshold: Same as Write Threshold but for Reads from BOTH RANKS.

13.6.24 TELB—Offset 84h

Thermal Enforcement Limits for Bandwidth Trips

Access Method

Offset: [Port: 0x04] + 84h

Op Codes:



Default: 00000000h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
R1_WR_MASK				R1_RD_MASK				R0_WR_MASK				R0_RD_MASK			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RW	R1_WR_MASK: Rank 1 Write Mask: Mask writes to Rank1
23:16	0h RW	R1_RD_MASK: Rank 1 Read Mask: Mask reads to Rank1
15:8	0h RW	R0_WR_MASK: Rank 0 Write Mask: Mask writes to Rank0
7:0	0h RW	R0_RD_MASK: Rank 0 Read Mask: Mask reads to Rank0

13.6.25 TELT—Offset 85h

Thermal Enforcement Limits for Thermal Trips

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 85h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
R1_WR_MASK				R1_RD_MASK				R0_WR_MASK				R0_RD_MASK			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RW	R1_WR_MASK: Rank 1 Write Mask: Mask writes to Rank1
23:16	0h RW	R1_RD_MASK: Rank 1 Read Mask: Mask reads to Rank1
15:8	0h RW	R0_WR_MASK: Rank 0 Write Mask: Mask writes to Rank0
7:0	0h RW	R0_RD_MASK: Rank 0 Read Mask: Mask reads to Rank0



Access Method

Offset: [Port: 0x04] + 86h

h - Read, h - Write

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:3	0h RW	Reserved_1: Reserved
2:0	0h RW	TQ_POLL_PERIOD: Def TQ Poll Period: This sets the frequency by which the Dunit polls the DRAM mode register MR4 to determine required refresh rate when thermal event occurs. ..000 1 x the current Refresh Period ..001 2 x the current Refresh Period ..010 4 x the current Refresh Period ..011 8 x the current Refresh Period ..100 16 x the current Refresh Period ..101 32 x the current Refresh Period ..110 64 x the current Refresh Period ..111 128 x the current Refresh Period..



13.6.27 GFXT—Offset 88h

GFXT Thermals Control - This register is used to enable clock (On clocks) throttling.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 88h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_1				TM2_THROT_GFX				TM1_THROT_GFX

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Reserved_1: Resered for future use
15:8	0h RW	TM2_THROT_GFX: TM2 Control for GFX
7:3	0h RW	Reserved_3: Reserved for future use
2:0	0h RW	TM1_THROT_GFX: TM1 Throttling for GFx..3 b000: No Throttle..3 b001: 12.5% Throttle..3 b010: 25% Throttle..3 b011: 37.5% Throttle..3 b100: 50% Throttle..3 b101: 67.5% Throttle..3 b110: 75% Throttle..3 b111: 87.5% Throttle..



13.6.28 VEDT—Offset 89h

VED Thermals Control - This register is used to enable clock (On clocks) throttling.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 89h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1								TM2_THROT_VED
								Reserved_3
								TM1_THROT_VED

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Reserved_1: Resered for future use
15:8	0h RW	TM2_THROT_VED: TM2 Control for VED
7:3	0h RW	Reserved_3: Reserved for future use
2:0	0h RW	TM1_THROT_VED: TM1 Throttling for Ved..3 b000: No Throttle..3 b001: 12.5% Throttle..3 b010: 25% Throttle..3 b011: 37.5% Throttle..3 b100: 50% Throttle..3 b101: 67.5% Throttle..3 b110: 75% Throttle..3 b111: 87.5% Throttle..



13.6.29 ISPT—Offset 8Ch

ISP Thermals Control - This register is used to enable clock (On clocks) throttling.

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 8Ch

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1								TM1_THROT_ISP

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Reserved_1: Resered for future use
15:8	0h RW	Reserved_2: Reserved
7:3	0h RW	Reserved_3: Reserved for future use
2:0	0h RW	TM1_THROT_ISP: TM1 Throttling for ISP..3 b000: No Throttle..3 b001: 12.5% Throttle..3 b010: 25% Throttle..3 b011: 37.5% Throttle..3 b100: 50% Throttle..3 b101: 67.5% Throttle..3 b110: 75% Throttle..3 b111: 87.5% Throttle..



13.6.30 DTSC—Offset B0h

Digital Thermal Sensor Control

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + B0h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_1								DTS1_ENABLE
								DTS0_ENABLE

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RO	RESERVED_1: Reserved
1	0h RW	DTS1_ENABLE: DTS 1 Enable (DTSE1): When set, enables power to DTS 1
0	0h RW	DTS0_ENABLE: DTS 0 Enable (DTSE0): When set, enables power to DTS 0



13.6.32 PTPS—Offset B2h

Programmable trip Point settings

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + B2h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
AUX3_TRIP_POINT				AUX2_TRIP_POINT				AUX1_TRIP_POINT				AUX0_TRIP_POINT			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RW	AUX3_TRIP_POINT: Aux3 Trip Point Setting
23:16	0h RW	AUX2_TRIP_POINT: Aux2 Trip Point Setting
15:8	0h RW	AUX1_TRIP_POINT: Aux1 Trip Point Setting
7:0	0h RW	AUX0_TRIP_POINT: Aux0 Trip Point Setting

13.6.33 PTTS—Offset B3h

Programmable Thermal trip Status

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + B3h

Op Codes:

h - Read, h - Write

Default: 00000000h



31				28				24				20				16				12				8				4				0																																																							
0				0				0				0				0				0				0				0				0				0																																																			
RESERVED_1																																MOD1_THERM_STATUS				MOD0_THERM_STATUS				RESERVED_4				SWT				BW_STATUS				THERMAL_STATUS				PROCHOT_THERM_STATUS				VR_ICC_THERM_STATUS				VR_HOT_THERM_STATUS				RESERVED_11				AUX3_THERM_STATUS				AUX2_THERM_STATUS				AUX1_THERM_STATUS				AUX0_THERM_STATUS			

Bit Range	Default & Access	Field Name (ID): Description
31:18	0h RO	RESERVED_1: Reserved
17	0h RO	MOD1_THERM_STATUS: CPU Module1: CPU Module 1 Trip Status
16	0h RO	MOD0_THERM_STATUS: CPU Module0: CPU Module 0 Trip Status
15:14	0h RO	RESERVED_4: Reserved
13	0h RO	SWT: Status to indicate that SW initiated a thermal event
12	0h RO	BW_STATUS: BW status
11	0h RO	THERMAL_STATUS: XXTTS (Reserved): Platform Thermal Sensor Status
10	0h RO	PROCHOT_THERM_STATUS: XXPROCHOT: Platform Prochot Status
9	0h RO	VR_ICC_THERM_STATUS: VR_Icc_Max: VR Icc Max Thermal Status
8	0h RO	VR_HOT_THERM_STATUS: VR_Hot: VR Hot Thermal Status
7:4	0h RO	RESERVED_11: Reserved
3	0h RO	AUX3_THERM_STATUS: AUX3: SoC PROCHOT/AUX3 Thermtrip Status
2	0h RO	AUX2_THERM_STATUS: AUX2: AUX2 Thermal Trip Status
1	0h RO	AUX1_THERM_STATUS: AUX1: AUX2 Thermal Trip Status
0	0h RO	AUX0_THERM_STATUS: AUX0: AUX2 Thermal Trip Status



13.6.34 PTTSS—Offset B4h

Programmable Thermal trip Sticky Status (NOTE: 1. Sticky status register is cleared by writing a 1 to it by software)

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + B4h

Op Codes:

h - Read, h - Write

Default: 00000000h

31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0																																			
RESERVED_1												MOD1_THERM_STATUS				MOD0_THERM_STATUS				RESERVED_4				SWT				BW_STATUS				THERMAL_STATUS				PROCHOT_THERM_STATUS				VR_ICC_THERM_STATUS				VR_HOT_THERM_STATUS				RESERVED_11				AUX3_THERM_STATUS				AUX2_THERM_STATUS				AUX1_THERM_STATUS				AUX0_THERM STATUS			

Bit Range	Default & Access	Field Name (ID): Description
31:18	0h RO	RESERVED_1: Reserved
17	0h RW	MOD1_THERM_STATUS: CPU Module1: CPU Module 1 Trip Status
16	0h RW	MOD0_THERM_STATUS: CPU Module0: CPU Module 0 Trip Status
15:14	0h RO	RESERVED_4: Reserved
13	0h RO	SWT: Status to indicate that SW initiated a thermal event
12	0h RO	BW_STATUS: BW status
11	0h RO	THERMAL_STATUS: XXTTS (Reserved): Platform Thermal Sensor Status
10	0h RW	PROCHOT_THERM_STATUS: XXPROCHOT: Platform Prochot Status
9	0h RW	VR_ICC_THERM_STATUS: VR_Icc_Max: VR Icc Max Thermal Status
8	0h RW	VR_HOT_THERM_STATUS: VR_Hot: VR Hot Thermal Status
7:4	0h RO	RESERVED_11: Reserved
3	0h RW	AUX3_THERM_STATUS: AUX3: SoC PROCHOT/AUX3 Thermtrip Status



Bit Range	Default & Access	Field Name (ID): Description
2	0h RW	AUX2_THERM_STATUS: AUX2: AUX2 Thermal Trip Status
1	0h RW	AUX1_THERM_STATUS: AUX1: AUX2 Thermal Trip Status
0	0h RW	AUX0_THERM_STATUS: AUX0: AUX2 Thermal Trip Status

13.6.35 TE_AUX0—Offset B5h

Thermal Event Aux0

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + B5h

Op Codes:

h - Read, h - Write


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_1				SLM1_PROCHOT_ENABLE	SLM0_PROCHOT_ENABLE	XXPROCHOT_ENABLE	RESERVED_5	Assert_APICA
				TQ_POLL	iUnitTM1	MSI_ENABLE	SMI_ENABLE	SCI_ENABLE
				SATA_THROTTLE_ENABLE	VSP_TM1_ENABLE	VEC_TM1_ENABLE	VED_TM1_ENABLE	GFX_VNN_THROT
				GFX_TM2_ENABLE	GFX_TM1_ENABLE	BW_THROT_ENABLE	DDR_REFRESH_ENABLE	

Bit Range	Default & Access	Field Name (ID): Description
31:19	0h RO	RESERVED_1: Reserved
18	0h RW	SLM1_PROCHOT_ENABLE: SLM1 PROCHOT Enable(Reserved for VLV)
17	0h RW	SLM0_PROCHOT_ENABLE: SLM0 PROCHOT Enable
16	0h RW	XXPROCHOT_ENABLE: XXPROCHOT Note: Unless in debug mode enable XXPROCHOT with caution because XXPROCHOT feedback into SoC via the Bi-Directional IO and could cause XXPROCHOT to trip as well
15	0h RO	RESERVED_5: Reserved
14	0h RW	Assert_APICA: Assert_APICA Enable
13	0h RW	TQ_POLL: TQ Poll rate Increase
12	0h RW	iUnitTM1: iUnit TM1



Bit Range	Default & Access	Field Name (ID): Description
11	0h RW	MSI_ENABLE: MSI Enable
10	0h RW	SMI_ENABLE: SMI Enable
9	0h RW	SCI_ENABLE: SCI Enable
8	0h RW	SATA_THROTTLE_ENABLE: SATA Throttle Enable
7	0h RW	VSP_TM1_ENABLE: VSP TM1 Enable
6	0h RW	VEC_TM1_ENABLE: VEC TM1 Enable
5	0h RW	VED_TM1_ENABLE: VED TM1 Enable
4	0h RW	GFX_VNN_THROT: Graphics Vnn Throttle (Reserved for VLV)
3	0h RW	GFX_TM2_ENABLE: GFX TM2 Enable....
2	0h RW	GFX_TM1_ENABLE: GFX TM1 Enable....
1	0h RW	BW_THROT_ENABLE: BW throttle Enable
0	0h RW	DDR_REFRESH_ENABLE: DDR 2X refresh Enable



13.6.36 TE_AUX1—Offset B6h

Thermal Event Aux1

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + B6h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_1				SLM1_PROCHOT_ENABLE	SLM0_PROCHOT_ENABLE	XXPROCHOT_ENABLE	RESERVED_5	Assert_APICA
				RESERVED_7	MSI_ENABLE	SMI_ENABLE	SCI_ENABLE	SATA_THROTTLE_ENABLE
					RESERVED_12	GFX_VNN_THROT	GFX_TM2_ENABLE	GFX_TM1_ENABLE
							BW_THROT_ENABLE	DDR_REFRESH_ENABLE

Bit Range	Default & Access	Field Name (ID): Description
31:19	0h RW	RESERVED_1: Reserved
18	0h RW	SLM1_PROCHOT_ENABLE: SLM1 PROCHOT Enable(Reserved for VLV)
17	0h RW	SLM0_PROCHOT_ENABLE: SLM0 PROCHOT Enable
16	0h RW	XXPROCHOT_ENABLE: XXPROCHOT Note: Unless in debug mode enable XXPROCHOT with caution because XXPROCHOT feedback into SoC via the Bi-Directional IO and could cause XXPROCHOT to trip as well
15	0h RW	RESERVED_5: Reserved
14	0h RW	Assert_APICA: Assert_APICA Enable
13:12	0h RW	RESERVED_7: Reserved
11	0h RW	MSI_ENABLE: MSI Enable
10	0h RW	SMI_ENABLE: SMI Enable
9	0h RW	SCI_ENABLE: SCI Enable
8	0h RW	SATA_THROTTLE_ENABLE: SATA Throttle Enable
7:5	0h RO	RESERVED_12: Reserved



Bit Range	Default & Access	Field Name (ID): Description
13:12	0h RW	RESERVED_7: Reserved
11	0h RW	MSI_ENABLE: MSI Enable
10	0h RW	SMI_ENABLE: SMI Enable
9	0h RW	SCI_ENABLE: SCI Enable
8	0h RW	SATA_THROTTLE_ENABLE: SATA Throttle Enable
7:5	0h RO	RESERVED_12: Reserved
4	0h RW	GFX_VNN_THROT: Graphics Vnn Throttle (Reserved for VLV)
3	0h RW	GFX_TM2_ENABLE: GFX TM2 Enable....
2	0h RW	GFX_TM1_ENABLE: GFX TM1 Enable....
1	0h RW	BW_THROT_ENABLE: BW throttle Enable
0	0h RW	DDR_REFRESH_ENABLE: DDR 2X refresh Enable



13.6.38 TE_AUX3—Offset B8h

Thermal Event Aux3

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + B8h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_1				SLM1_PROCHOT_ENABLE	SLM0_PROCHOT_ENABLE	XXPROCHOT_ENABLE	RESERVED_5	Assert_APICA
				RESERVED_7	MSI_ENABLE	SMI_ENABLE	SCI_ENABLE	SATA_THROTTLE_ENABLE
					RESERVED_12	GFX_VNN_THROT	GFX_TM2_ENABLE	GFX_TM1_ENABLE
							BW_THROT_ENABLE	DDR_REFRESH_ENABLE

Bit Range	Default & Access	Field Name (ID): Description
31:19	0h RW	RESERVED_1: Reserved
18	0h RW	SLM1_PROCHOT_ENABLE: SLM1 PROCHOT Enable(Reserved for VLV)
17	0h RW	SLM0_PROCHOT_ENABLE: SLM0 PROCHOT Enable
16	0h RW	XXPROCHOT_ENABLE: XXPROCHOT Note: Unless in debug mode enable XXPROCHOT with caution because XXPROCHOT feedback into SoC via the Bi-Directional IO and could cause XXPROCHOT to trip as well
15	0h RW	RESERVED_5: Reserved
14	0h RW	Assert_APICA: Assert_APICA Enable
13:12	0h RW	RESERVED_7: Reserved
11	0h RW	MSI_ENABLE: MSI Enable
10	0h RW	SMI_ENABLE: SMI Enable
9	0h RW	SCI_ENABLE: SCI Enable
8	0h RW	SATA_THROTTLE_ENABLE: SATA Throttle Enable
7:5	0h RO	RESERVED_12: Reserved



Bit Range	Default & Access	Field Name (ID): Description
4	0h RW	GFX_VNN_THROT: Graphics Vnn Throttle (Reserved for VLV)
3	0h RW	GFX_TM2_ENABLE: GFX TM2 Enable....
2	0h RW	GFX_TM1_ENABLE: GFX TM1 Enable....
1	0h RW	BW_THROT_ENABLE: BW throttle Enable
0	0h RW	DDR_REFRESH_ENABLE: DDR 2X refresh Enable

13.6.39 TTE_VRIccMax—Offset B9h

Thermal Trip Event VR_Icc_MAX

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + B9h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_1				SLM1_PROCHOT_ENABLE	SLM0_PROCHOT_ENABLE	XXPROCHOT_ENABLE	RESERVED_5	MSI_ENABLE
								SMT_ENABLE
								SCI_ENABLE
								SATA_THROTTLE_ENABLE
							RESERVED_10	
								GFX_VNN_THROT
								GFX_TM2_ENABLE
								GFX_TM1_ENABLE
								BW_THROT_ENABLE
								DDR_REFRESH_ENABLE

Bit Range	Default & Access	Field Name (ID): Description
31:19	0h RW	RESERVED_1: Reserved
18	0h RW	SLM1_PROCHOT_ENABLE: SLM1 PROCHOT Enable(Reserved for VLV)
17	0h RW	SLM0_PROCHOT_ENABLE: SLM0 PROCHOT Enable
16	0h RW	XXPROCHOT_ENABLE: XXPROCHOT Note: Unless in debug mode enable XXPROCHOT with caution because XXPROCHOT feedback into SoC via the Bi-Directional IO and could cause XXPROCHOT to trip as well
15:12	0h RW	RESERVED_5: Reserved
11	0h RW	MSI_ENABLE: MSI Enable



Bit Range	Default & Access	Field Name (ID): Description
17	0h RW	SLM0_PROCHOT_ENABLE: SLM0 PROCHOT Enable
16	0h RW	XXPROCHOT_ENABLE: XXPROCHOT Note: Unless in debug mode enable XXPROCHOT with caution because XXPROCHOT feedback into SoC via the Bi-Directional IO and could cause XXPROCHOT to trip as well
15:12	0h RW	RESERVED_5: Reserved
11	0h RW	MSI_ENABLE: MSI Enable
10	0h RW	SMI_ENABLE: SMI Enable
9	0h RW	SCI_ENABLE: SCI Enable
8	0h RW	SATA_THROTTLE_ENABLE: SATA Throttle Enable
7:5	0h RO	RESERVED_10: Reserved
4	0h RW	GFX_VNN_THROT: Graphics Vnn Throttle (Reserved for VLV)
3	0h RW	GFX_TM2_ENABLE: GFX TM2 Enable....
2	0h RW	GFX_TM1_ENABLE: GFX TM1 Enable....
1	0h RW	BW_THROT_ENABLE: BW throttle Enable
0	0h RW	DDR_REFRESH_ENABLE: DDR 2X refresh Enable

13.6.41 TTE_XXPROCHOT—Offset BBh

Thermal Trip Event XXPROCHOT

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + BBh

Op Codes:

h - Read, h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_1				SLM1_PROCHOT_ENABLE	SLM0_PROCHOT_ENABLE	XXPROCHOT_ENABLE	RESERVED_5	MSI_ENABLE
								SMI_ENABLE
								SCI_ENABLE
								SATA_THROTTLE_ENABLE
							RESERVED_10	GFX_VNN_THROT
								GFX_TM2_ENABLE
								GFX_TM1_ENABLE
								BW_THROT_ENABLE
								DDR_REFRESH_ENABLE

Bit Range	Default & Access	Field Name (ID): Description
31:19	0h RW	RESERVED_1: Reserved
18	0h RW	SLM1_PROCHOT_ENABLE: SLM1 PROCHOT Enable(Reserved for VLV)
17	0h RW	SLM0_PROCHOT_ENABLE: SLM0 PROCHOT Enable
16	0h RW	XXPROCHOT_ENABLE: XXPROCHOT Note: Unless in debug mode enable XXPROCHOT with caution because XXPROCHOT feedback into SoC via the Bi-Directional IO and could cause XXPROCHOT to trip as well
15:12	0h RW	RESERVED_5: Reserved
11	0h RW	MSI_ENABLE: MSI Enable
10	0h RW	SMI_ENABLE: SMI Enable
9	0h RW	SCI_ENABLE: SCI Enable
8	0h RW	SATA_THROTTLE_ENABLE: SATA Throttle Enable
7:5	0h RO	RESERVED_10: Reserved
4	0h RW	GFX_VNN_THROT: Graphics Vnn Throttle (Reserved for VLV)
3	0h RW	GFX_TM2_ENABLE: GFX TM2 Enable....
2	0h RW	GFX_TM1_ENABLE: GFX TM1 Enable....
1	0h RW	BW_THROT_ENABLE: BW throttle Enable
0	0h RW	DDR_REFRESH_ENABLE: DDR 2X refresh Enable



13.6.42 TTE_SLM0—Offset BCh

Thermal Trip Event SLM0

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + BCh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_1				SLM1_PROCHOT_ENABLE	SLM0_PROCHOT_ENABLE	XXPROCHOT_ENABLE	RESERVED_5	MSI_ENABLE
								SMI_ENABLE
								SCI_ENABLE
								SATA_THROTTLE_ENABLE
							RESERVED_10	
							GFX_VNN_THROT	
							GFX_TM2_ENABLE	
							GFX_TM1_ENABLE	
							BW_THROT_ENABLE	
							DDR_REFRESH_ENABLE	

Bit Range	Default & Access	Field Name (ID): Description
31:19	0h RW	RESERVED_1: Reserved
18	0h RW	SLM1_PROCHOT_ENABLE: SLM1 PROCHOT Enable(Reserved for VLV)
17	0h RW	SLM0_PROCHOT_ENABLE: SLM0 PROCHOT Enable
16	0h RW	XXPROCHOT_ENABLE: XXPROCHOT Note: Unless in debug mode enable XXPROCHOT with caution because XXPROCHOT feedback into SoC via the Bi-Directional IO and could cause XXPROCHOT to trip as well
15:12	0h RW	RESERVED_5: Reserved
11	0h RW	MSI_ENABLE: MSI Enable
10	0h RW	SMI_ENABLE: SMI Enable
9	0h RW	SCI_ENABLE: SCI Enable
8	0h RW	SATA_THROTTLE_ENABLE: SATA Throttle Enable
7:5	0h RO	RESERVED_10: Reserved
4	0h RW	GFX_VNN_THROT: Graphics Vnn Throttle (Reserved for VLV)
3	0h RW	GFX_TM2_ENABLE: GFX TM2 Enable....



Bit Range	Default & Access	Field Name (ID): Description
8	0h RW	SATA_THROTTLE_ENABLE: SATA Throttle Enable
7:5	0h RO	RESERVED_10: Reserved
4	0h RW	GFX_VNN_THROT: Graphics Vnn Throttle (Reserved for VLV)
3	0h RW	GFX_TM2_ENABLE: GFX TM2 Enable....
2	0h RW	GFX_TM1_ENABLE: GFX TM1 Enable....
1	0h RW	BW_THROT_ENABLE: BW throttle Enable
0	0h RW	DDR_REFRESH_ENABLE: DDR 2X refresh Enable

13.6.44 BWTE—Offset BEh

Band width Trip Event

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + BEh

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_1				SLM1_PROCHOT_ENABLE	SLM0_PROCHOT_ENABLE	XXPROCHOT_ENABLE	RESERVED_5	MSI_ENABLE
								SMI_ENABLE
								SCI_ENABLE
								SATA_THROTTLE_ENABLE
							RESERVED_10	
							GFX_VNN_THROT	
							GFX_TM2_ENABLE	
							GFX_TM1_ENABLE	
							BW_THROT_ENABLE	
							DDR_REFRESH_ENABLE	

Bit Range	Default & Access	Field Name (ID): Description
31:19	0h RW	RESERVED_1: Reserved
18	0h RW	SLM1_PROCHOT_ENABLE: SLM1 PROCHOT Enable(Reserved for VLV)
17	0h RW	SLM0_PROCHOT_ENABLE: SLM0 PROCHOT Enable
16	0h RW	XXPROCHOT_ENABLE: XXPROCHOT Note: Unless in debug mode enable XXPROCHOT with caution because XXPROCHOT feedback into SoC via the Bi-Directional IO and could cause XXPROCHOT to trip as well



Thermal trip event for software initiated thermal event

Type: Message Bus Register
(Size: 32 bits)

Op Codes:
h - Read, h - Write

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31:19	0h RO	RESERVED_1: Reserved
18	0h RW	SLM1_PROCHOT_ENABLE: SLM1 PROCHOT Enable(Reserved for VLV)
17	0h RW	SLM0_PROCHOT_ENABLE: SLM0 PROCHOT Enable
16	0h RW	XXPROCHOT_ENABLE: XXPROCHOT Note: Unless in debug mode enable XXPROCHOT with caution because XXPROCHOT feedsback into SoC via the Bi-Directional IO and could cause XXPROCHOT to trip as well
15:14	0h RO	RESERVED_5: Reserved
13	0h RW	TQ_POLL: TQ Poll rate Increase
12	0h RW	iUnitTM1: iUnit TM1
11	0h RW	MSI_ENABLE: MSI Enable
10	0h RW	SMI_ENABLE: SMI Enable
9	0h RW	SCI_ENABLE: SCI Enable
8	0h RW	SATA_THROTTLE_ENABLE: SATA Throttle Enable
7	0h RW	VSP_TM1_ENABLE: VSP TM1 Enable
6	0h RW	VEC_TM1_ENABLE: VEC TM1 Enable
5	0h RW	VED_TM1_ENABLE: VED TM1 Enable
4	0h RW	GFX_VNN_THROT: Graphics Vnn Throttle (Reserved for VLV)
3	0h RW	GFX_TM2_ENABLE: GFX TM2 Enable....
2	0h RW	GFX_TM1_ENABLE: GFX TM1 Enable....
1	0h RW	BW_THROT_ENABLE: BW throttle Enable
0	0h RW	DDR_REFRESH_ENABLE: DDR 2X refresh Enable



13.6.46 PUNIT_GPU_EC—Offset D1h

Punit GPU Energy Counter Register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + D1h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

GPU_EC

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	GPU_EC: GPU Energy Counter Information

13.6.47 PUNIT_GPU_EC_VIRUS—Offset D2h

Punit GPU Energy Counter Virus Register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + D2h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

GPU_EC_VIRUS

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	GPU_EC_VIRUS: Initialized to the Virus count value of GPU_EC.

13.6.48 PUNIT_GPU_LFM—Offset D3h

Punit GPU LFM Register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + D3h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SPARE_BITS							GPU_LFM	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	SPARE_BITS: Bits to be used in future
7:0	0h RW	GPU_LFM: Lowest supported GFX frequency.

13.6.49 PUNIT_GPU_FREQ_REQ—Offset D4h

Punit GPU Frequency Request Register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + D4h

Op Codes:

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SPARE_BITS							GFXFREQWISH	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	SPARE_BITS: Bits to be used in future
7:0	0h RW	GFXFREQWISH: Doorbell Register, Frequency Encoding for Frequency Requested in GFX Reg used by Render. For actual frequency encoding please refer Graphics HAS



13.6.50 PUNIT_GPU_FREQ_STS—Offset D8h

Punit GPU Frequency Status Register

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + D8h

Op Codes:

h - Read, h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED_7								STATUSFREQID
								CZ_CLK_FREQ
								RESERVED_4
								GPLLENABLE
								RESERVED_2
								GENFREQSTATUS

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RO	RESERVED_7: Reserved for future use
15:8	0h RO	STATUSFREQID: Frequency Encoding for the Frequency Reached
7:6	0h RO	CZ_CLK_FREQ: CZ clock Freq encoding is as follows: 00 = 800, 01=1066, 10=1333, 11=Invalid
5	0h RO	RESERVED_4: Reserved for future use
4	0h RO	GPLLENABLE: 0=graphics clocks not from GPLL...1=graphics clocks from GPLL...
3:1	0h RO	RESERVED_2: Reserved for future use
0	0h RO	GENFREQSTATUS: Status Register bit to be optionally used by Graphics Driver. This bit Indicates that frequency change is in progress

13.6.51 DPTF_TELB—Offset 108h

Thermal Enforcement Limits for Bandwidth Trips. Write to this Register also triggers Punit to take action to execute. In the RTL the register is listed as MMIO_SPARE4

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 108h

Op Codes:

h - Read, h - Write

Default: 00000000h



VED Thermals Control - This register is used to enable clock (On clocks) throttling. Write to this Register also triggers Punit to take action to execute. In the RTL the register is listed as MMIO_SPARE6

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 10Ah

Op Codes:

h - Read, h - Write

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Reserved_1: Resered for future use
15:8	0h RW	TM2_THROT_VED: TM2 Control for VED
7:3	0h RW	Reserved_3: Reserved for future use
2:0	0h RW	TM1_THROT_VED: TM1 Throttling for Ved.. b000: No Throttle.. b001: 12.5% Throttle.. b010: 25% Throttle.. b011: 37.5% Throttle.. b100: 50% Throttle.. b101: 67.5% Throttle.. b110: 75% Throttle.. b111: 87.5% Throttle..

13.6.54 DPTF_VECT—Offset 10Bh

VEC Thermals Control - This register is used to enable clock (On clocks) throttling. Write to this Register also triggers Punit to take action to execute. In the RTL the register is listed as MMIO_SPARE7

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 10Bh

Op Codes:

Default: 00000000h



ISP Thermals Control - This register is used to enable clock (On clocks) throttling. Write to this Register also triggers Punit to take action to execute. In the RTL the register is listed as MMIO_SPARE9

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x04] + 10Dh

Op Codes:

h - Read, h - Write


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1				Reserved_2				Reserved_3
								TM1_THROT_ISP

Intel Atom® Processor E3800 Product Family
Datasheet
410

14 Graphics, Video and Display

This section provides an overview of Graphics, Video and Display features of the SoC.

This chapter and all contents in it are not applicable to E3805 SKU.




14.1 Features

The key features of the individual blocks are as follows:

- Refreshed seventh generation Intel graphics core with four Execution Units (EUs)
 - 3D graphics hardware acceleration including support for DirectX*11, OCL 1.2, OGL ES Haili/2.0/1.1, OGL 3.2
 - Video decode hardware acceleration including support for H.264, MPEG2, MVC, VC-1, WMV9, JPEG/MJPEG and VP8 formats
 - Video encode hardware acceleration including support for H.264 and MPEG2
 - Display controller, incorporating the display planes, pipes and physical interfaces
 - Four planes available per pipe - 1x Primary, 2x Video Sprite and 1x Cursor- plus a single legacy VGA plane
 - A single Analog Display physical interface, implementing VGA support
 - Two multi-purpose Digital Display Interface (DDI) PHYs implementing HDMI, DVI, DisplayPort (DP) or Embedded DisplayPort (eDP) support

14.2 SoC Graphics Display



The Processor Graphics controller display pipe can be broken down into three components:

- Display Planes
- Display Pipes
- Display Physical Interfaces

A display plane is a single displayed surface in memory and contains one image (desktop, cursor, overlay). It is the portion of the display hardware logic that defines the format and location of a rectangular region of memory that can be displayed on a display output device and delivers that data to a display pipe. This is clocked by the Core Display Clock.

14.2.1 Primary Planes A and B

Planes A and B are the main display planes and are associated with Pipes A and B respectively. Each plane supports per-pixel alpha blending.

14.2.2 Video Sprite Planes A, B, C and D


Video Sprite Planes A, B, C and D are planes optimized for video decode. Planes A and B are associated with Pipe A and Planes C and D are associated with Pipe B.

14.2.3 Cursors A and B

Cursors A and B are small, fixed-sized planes dedicated for mouse cursor acceleration, and are associated with Planes A and B respectively.

14.2.4 VGA

VGA is used for boot, safe mode, legacy games, etc. It can be changed by an application without OS/driver notification, due to legacy requirements.



14.3 Display Pipes

The display pipe blends and synchronizes pixel data received from one or more display planes and adds the timing of the display output device upon which the image is displayed.

The display pipes A and B operate independently of each other at the rate of one pixel per clock. They can attach to any of the display interfaces.

14.4 Display Physical Interfaces

The display physical interfaces consist of output logic and pins that transmit the display data to the associated encoding logic and send the data to the display device. These interfaces can be subdivided into analog (VGA) and digital (DisplayPort*, Embedded DisplayPort*, DVI and HDMI*) interfaces.

14.4.1 Analog Display Physical Interface

The analog port provides a RGB signal output along with a HSYNC and VSYNC signal. There is an associated Display Data Channel (DDC) signal pair dedicated to the analog port. The intended target device is for a monitor with a VGA connector. Display devices such as LCD panels with analog inputs may work satisfactorily but no functionality is added to the signals to enhance that capability.

14.4.1.1 Signal Descriptions

Please see [Chapter 2, “Physical Interfaces”](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal’s function.

Table 165. Analog Display Interface Signals

Signal Name	Direction Plat. Power	Description
VGA_BLUE	O VGA_GPIO	Blue Analog Video Output: This signal is a VGA Analog video output from the internal color palette DAC.
VGA_GREEN	O VGA_GPIO	Green Analog Video Output: This signal is a VGA Analog video output from the internal color palette DAC.
VGA_RED	O VGA_GPIO	Red Analog Video Output: This signal is a VGA Analog video output from the internal color palette DAC.
VGA_HSYNC	O VGA_GPIO	VGA Horizontal Synchronization: This signal is used as the horizontal sync (polarity is programmable) or “sync interval”.

Table 165. Analog Display Interface Signals

Signal Name	Direction Plat. Power	Description
VGA_VSYNC	O VVGa_GPIO	VGA Vertical Synchronization: This signal is used as the horizontal sync (polarity is programmable) or "sync interval".
VGA_DDCCLK	I/O VVGa_GPIO	VGA DDC Clock: EDID support for an external VGA display
VGA_DDCDATA	I/O VVGa_GPIO	VGA DDC Data: EDID support for an external VGA display
VGA_IREF	I	Resistor Set: Set point resistor for the internal color palette DAC. A 357ohm+/-0.5% precision resistor is required between VGA_IREF and motherboard ground.
VGA_IRTN	O	This signal is the complement video signal output from the internal color palette DAC channels and this signal connects directly to the ground plane of the board.
LPC_RCOMP	-	VGA Impedance Compensation.

14.4.1.2 Features


Table 166 lists the characteristics of the analog port.

Table 166. Analog Port Characteristics

Signal	Port Characteristics	Support
RGB	Voltage range	0.7 Vp-p nominal only
	CRT/Monitor sense	Analog compare
	Analog copy protection	No
	Sync on green	No
HSYNC VSYNC	Voltage	3.3 V
	Enable/Disable	Port control
	Polarity adjust	VGA or port control
	Composite sync support	No
	Special flat panel sync	No
	Stereo sync	No
DDC	Voltage	External buffered to 5 V
	Control	Through GPIO interface

14.4.1.2.1 Integrated RAMDAC

The display function contains a RAM-based Digital-to-Analog Converter (RAMDAC) that transforms the digital data from the graphics and video subsystems to analog data for the VGA monitor. The SoC integrated 320 MHz RAMDAC supports resolutions up to 2560x1600 at 60 Hz. Three 8-bit DACs provide the R, G, and B signals to the monitor.



14.4.1.2.2 Sync Signals

HSYNC and VSYNC signals are digital and conform to TTL signal levels at the connector. Since these levels cannot be generated internal to the device, external level shifting buffers are required. These signals can be polarity adjusted and individually disabled in one of the two possible states. The sync signals should power up disabled in the high state. No composite sync or special flat panel sync support are included.

14.4.1.2.3 VESA/VGA Mode

VESA/VGA mode provides compatibility for pre-existing software that set the display mode using the VGA CRTC registers. Timings are generated based on the VGA register values and the timing generator registers are not used.

14.4.1.2.4 Display Data Channel (DDC)

DDC is a standard defined by VESA. Its purpose is to allow communication between the host system and display. Both configuration and control information can be exchanged allowing plug-and-play systems to be realized. Support for DDC 1 and 2 is implemented. The SoC uses the VGA_DDCCLK and VGA_DDCDATA signals to communicate with the analog monitor. The SoC does not generate these signals at 5 V so external pull-up resistors and level shifting circuitry should be implemented on the board.

14.4.2 Digital Display Interfaces

14.4.2.1 Signal Descriptions

See [Chapter 2, “Physical Interfaces”](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function

Table 167. Display Physical Interfaces Signal Names (Sheet 1 of 2)

Signal Name	Direction	Description	
		HDMI / DVI	DP / eDP
DDI[1,0]_TXP[0] DDI[1,0]_TXP[1] DDI[1,0]_TXP[2] DDI[1,0]_TXP[3]	O	Ports 1,0: Transmit Signals	
		TMDS[1,0]_DATAP[2]	DP[1,0]_MAINP[0]
		TMDS[1,0]_DATAP[1]	DP[1,0]_MAINP[1]
		TMDS[1,0]_DATAP[0]	DP[1,0]_MAINP[2]
		TMDS[1,0]_CLKP	DP[1,0]_MAINP[3]

Table 167. Display Physical Interfaces Signal Names (Sheet 2 of 2)

Signal Name	Direction	Description	
		HDMI / DVI	DP / eDP
DDI[1,0]_TXN[0] DDI[1,0]_TXN[1] DDI[1,0]_TXN[2] DDI[1,0]_TXN[3]	O	Ports 1,0: Transmit Complement Signals	
		TMD5[1,0]_DATAN[2]	DP[1,0]_MAINN[0]
		TMD5[1,0]_DATAN[1]	DP[1,0]_MAINN[1]
		TMD5[1,0]_DATAN[0]	DP[1,0]_MAINN[2]
		TMD5[1,0]_CLKN	DP[1,0]_MAINN[3]
DDI[1,0]_AUXP	I/O	Ports 1,0: Display Port Auxiliary Channel	
		Unused	DP[1,0]_AUXP
DDI[1,0]_AUXN	I/O	Ports 1,0: Display Port Auxiliary Channel Complement	
		Unused	DP[1,0]_AUXN
DDI[1,0]_HPD	I	Ports 1,0: Hot Plug Detect	
		TMD5[1,0]_HPD	DP[1,0]_HPD
DDI[1,0]_DDCCLK	I/O	Ports 1,0: DDC Clock	
		TMD5[1,0]_DDCCLK	Unused
DDI[1,0]_DDCDATA	I/O	Ports 1,0: DDC Data	
		TMD5[1,0]_DDCDATA	DP[1,0]_EN - Port 0 Enable Strap
DDI[1,0]_BKLCTL	O	Ports 1,0: Panel Backlight Brightness Control	
		HDMI / DVI / DP	eDP Only
		Unused	EDP[1,0]_BKLCTL
DDI[1,0]_BKLTEN	O	Ports 1,0: Panel Backlight Enable	
		HDMI / DVI / DP	eDP Only
		Unused	EDP[1,0]_BKLTEN
DDI[1,0]_VDDEN	O	Ports 1,0: Panel Power Enable	
		HDMI / DVI / DP	eDP Only
		Unused	EDP[1,0]_VDDEN
DDI_RCOMP_P/N	I/O	DDI RCOMP This signal is used for pre-driver slew rate compensation. An external precision resistor of 402 Ω $\pm$ 1% should be connected between DDI_RCOMP_P and DDI_RCOMP_N.	

14.4.2.2 Features

14.4.2.3 High Definition Multimedia Interface

The High-Definition Multimedia Interface (HDMI) is provided for transmitting digital audio and video signals from DVD players, set-top boxes and other audiovisual sources to television sets, projectors and other video displays. It can carry high quality multi-

channel audio data and all standard and high-definition consumer electronics video formats. HDMI display interface connecting the SoC and display devices utilizes transition minimized differential signaling (TMDS) to carry audiovisual information through the same HDMI cable.

HDMI includes three separate communications channels: TMDS, DDC, and the optional CEC (consumer electronics control) (not supported by the SoC). As shown in [Figure 91](#) the HDMI cable carries four differential pairs that make up the TMDS data and clock channels. These channels are used to carry video, audio, and auxiliary data. In addition, HDMI carries a VESA DDC. The DDC is used by an HDMI Source to determine the capabilities and characteristics of the sink.

Audio, video and auxiliary (control/status) data is transmitted across the three TMDS data channels. The video pixel clock is transmitted on the TMDS clock channel and is used by the receiver for data recovery on the three data channels. The digital display data signals driven natively through the SoC are AC coupled and needs level shifting to convert the AC coupled signals to the HDMI compliant digital signals.


The SoC HDMI interface is designed as per the High-Definition Multimedia Interface Specification 1.4. The SoC supports High-Definition Multimedia Interface Compliance Test Specification 1.4.

14.4.2.3.1 Stereoscopic Support on HDMI

SoC display supports HDMI 1.4 3D video formats. If the HDMI panel is detected to support 3D video format then the SW driver will program Pipe2dB for the correct pipe timing parameters.

The left and right frames can be loaded from independent frame buffers in the main memory. Depending on the input S3D format, the display controller can be enabled to perform frame repositioning, image scaling, line interleaving.

Figure 91. HDMI Overview



14.4.2.4 Digital Video Interface (DVI)

The Digital Ports can be configured to drive DVI-D. DVI uses TMDS for transmitting data from the transmitter to the receiver which is similar to the HDMI protocol but without the audio and CEC. Refer to the HDMI section for more information on the

signals and data transmission. To drive DVI-I through the back panel the VGA DDC signals are connected along with the digital data and clock signals from one of the Digital Ports. When a system has support for a DVI-I port, then either VGA or the DVI-D through a single DVI-I connector can be driven but not both simultaneously.


14.4.2.5 Display Port

Display Port is a digital communication interface that utilizes differential signalling to achieve a high bandwidth bus interface designed to support connections between PCs and monitors, projectors, and TV displays. Display Port is also suitable for display connections between consumer electronics devices such as high definition optical disc players, set top boxes, and TV displays.

A Display Port consists of a Main Link, Auxiliary channel, and a Hot Plug Detect signal. The Main Link is a uni-directional, high-bandwidth, and low latency channel used for transport of isochronous data streams such as uncompressed video and audio. The Auxiliary Channel (AUX CH) is a half-duplex bidirectional channel used for link management and device control. The Hot Plug Detect (HPD) signal serves as an interrupt request for the sink device.

The SoC supports DisplayPort Standard Version 1.1.

Figure 92. DisplayPort* Overview



14.4.2.6 Embedded DisplayPort (eDP)

Embedded DisplayPort (eDP) is an embedded version of the DisplayPort standard oriented towards applications such as notebook and All-In-One PCs. eDP is supported only on Digital Display Interfaces 0 and/or 1. Like DisplayPort, Embedded DisplayPort also consists of a Main Link, Auxiliary channel, and an optional Hot Plug Detect signal.

Each eDP port can be configured for up-to 4 lanes.

The SoC supports Embedded DisplayPort Standard Version 1.3.



14.4.2.6.1 DisplayPort Auxiliary Channel

A bidirectional AC coupled AUX channel interface replaces the I²C for EDID read, link management and device control. I²C-to-Aux bridges are required to connect legacy display devices.

14.4.2.6.2 Hot-Plug Detect (HPD)

The SoC supports HPD for Hot-Plug sink events on the HDMI and DisplayPort interfaces.

14.4.2.6.3 Integrated Audio over HDMI and DisplayPort

SoC can support two audio streams on DP/HDMI ports. Each stream can be programmable to either DDI port. HDMI/DP audio streams can be sent with video streams as follows.

LPE mode: In this mode the uncompressed or compressed audio sample buffers are generated either by OS the audio stack or by audio Lower Power Engine (LPE) and stored in system memory. The display controller fetches audio samples from these buffers, forms an SPDIF frame with VUCP and preamble (if needed), then sends out with video packets.

14.4.2.6.4 High-Bandwidth Digital Content Protection (HDCP)

HDCP is the technology for protecting high definition content against unauthorized copy or unreceptive between a source (computer, digital set top boxes, etc.) and the sink (panels, monitor, and TV). The SoC supports HDCP 1.4 for content protection over wired displays (HDMI, DisplayPort and Embedded DisplayPort).

14.5 References

- High-Definition Multimedia Interface Specification, Version 1.4
- High-bandwidth Digital Content Protection System, Revision 1.4
- VESA DisplayPort Standard, Version 1.1
- VESA Embedded DisplayPort Standard, Version 1.3

14.6 3D Graphics and Video

The SoC implements a derivative of the Generation 7 graphics engine which consists of rendering engine and bit stream encoder/decoder engine. The rendering engine is used for 3D rendering, media compositing and video encoding. The Graphics engine is built around four execution units (EUs).






Figure 93. 3D Graphics Block Diagram



14.7 Features

The 3D graphics pipeline architecture simultaneously operates on different primitives or on different portions of the same primitive. All the cores are fully programmable, increasing the versatility of the 3D Engine. The Gen 7.0 3D engine provides the following performance and power-management enhancements:

- Hierarchal-Z
- Video quality enhancements



14.7.1 3D Engine Execution Units

- The EUs perform 128-bit wide execution per clock.
- Support SIMD8 instructions for vertex processing and SIMD16 instructions for pixel processing.

14.7.2 3D Pipeline

14.7.2.1 Vertex Fetch (VF) Stage

The VF stage executes 3DPRIMITIVE commands. Some enhancements have been included to better support legacy D3D APIs as well as SGI OpenGL*.

14.7.2.2 Vertex Shader (VS) Stage

The VS stage performs shading of vertices output by the VF function. The VS unit produces an output vertex reference for every input vertex reference received from the VF unit, in the order received.

14.7.2.3 Geometry Shader (GS) Stage

The GS stage receives inputs from the VS stage. Compiled application-provided GS programs, specifying an algorithm to convert the vertices of an input object into some output primitives. For example, a GS shader may convert lines of a line strip into polygons representing a corresponding segment of a blade of grass centered on the line. Or it could use adjacency information to detect silhouette edges of triangles and output polygons extruding out from the edges.

14.7.2.4 Clip Stage

The Clip stage performs general processing on incoming 3D objects. However, it also includes specialized logic to perform a Clip Test function on incoming objects. The Clip Test optimizes generalized 3D Clipping. The Clip unit examines the position of incoming vertices, and accepts/rejects 3D objects based on its Clip algorithm.

14.7.2.5 Strips and Fans (SF) Stage

The SF stage performs setup operations required to rasterize 3D objects. The outputs from the SF stage to the Windower stage contain implementation-specific information required for the rasterization of objects and also supports clipping of primitives to some extent.

14.7.2.6 Windower/IZ (WIZ) Stage

The WIZ unit performs an early depth test, which removes failing pixels and eliminates unnecessary processing overhead.

The Windower uses the parameters provided by the SF unit in the object-specific rasterization algorithms. The WIZ unit rasterizes objects into the corresponding set of pixels. The Windower is also capable of performing dithering, whereby the illusion of a higher resolution when using low-bpp channels in color buffers is possible. Color dithering diffuses the sharp color bands seen on smooth-shaded objects.


14.7.3 Video Engine


The video engine is part of the Intel Processor Graphics for image processing, play-back and transcode of Video applications. Processor Graphics video engine has a dedicated fixed hardware pipe-line for high quality decode and encode of media content. This engine supports Full HW acceleration for decode of H.264, MPEG -2, MVC, VC-1, WMV9, JPEG/MJPEG contents along with encode of H.264 apart from various video processing features. The new Processor Graphics Video engine adds support for processing features such as frame rate conversion, image stabilization and gamut conversion.

14.8 VED (Video Encode/Decode)

Note:

The video engine is part of the Intel Processor Graphics for image processing, play-back and transcode of Video applications. Processor Graphics video engine has a dedicated fixed hardware pipe-line for high quality decode and encode of media content. SoC Video Encode Decode block incorporates VXD 392 video decode core.





14.8.1 Features

The features for the Video decode hardware accelerator in SoC are:

- VED core can be configured on a time division multiplex basis to handle single, dual and multi-stream HD decoding.
- VED provides full hardware acceleration support

Table 170. Hardware Accelerated Video Decode Codec Support

Category	Codec Format
Media decode rate	Upto 1080p@60fps and 3x 4kx2k @30fps (H.264/JPEG/ MJPEG/MVC/MPEG-2 /WMV9/VC1)
Media encode rate	Upto 1080p@60fps and 1x 4kx2k @30fps (H.264)



14.9 PCI Configuration Registers

Table 171. Summary of Graphics, Video and Display PCI Configuration Registers—0/2/0

Offset	Size	Register ID—Description	Default Value
0h	4	"DID—Offset 0h" on page 426	0F318086h
4h	4	"PCICMD_STS—Offset 4h" on page 426	00100000h
8h	4	"RID_CC—Offset 8h" on page 427	03000000h
Ch	4	"HDR—Offset Ch" on page 428	00000000h
10h	4	"GTTMMADR_LSB—Offset 10h" on page 428	00000000h
14h	4	"GTTMMADR_MSB—Offset 14h" on page 429	00000000h
18h	4	"GMADR_LSB—Offset 18h" on page 430	00000008h
1Ch	4	"GMADR_MSB—Offset 1Ch" on page 431	00000000h
20h	4	"IOBAR—Offset 20h" on page 431	00000001h
2Ch	4	"SSID_SID—Offset 2Ch" on page 432	00000000h
34h	4	"CAPPOINT—Offset 34h" on page 432	000000D0h
3Ch	4	"INTRLINE—Offset 3Ch" on page 433	00000100h
50h	4	"GGC—Offset 50h" on page 434	00000028h
5Ch	4	"BDSM—Offset 5Ch" on page 435	00000000h
60h	4	"MSAC—Offset 60h" on page 436	00020000h
70h	4	"BGSM—Offset 70h" on page 437	00000000h
74h	4	"PAVPC—Offset 74h" on page 437	00000000h
90h	4	"MSI_CAPID_MC—Offset 90h" on page 439	0000B005h
94h	4	"MA—Offset 94h" on page 440	00000000h
98h	4	"MD—Offset 98h" on page 440	00000000h
A4h	4	"AFLC—Offset A4h" on page 441	03060013h
A8h	4	"AFCTLSTS—Offset A8h" on page 441	00000000h
B0h	4	"VCID—Offset B0h" on page 442	01070009h
B4h	4	"VCID—Offset B0h" on page 442	00000000h
C4h	4	"FD—Offset C4h" on page 443	00000000h
D0h	4	"PMCAPID—Offset D0h" on page 444	00229001h
D4h	4	"PMCS—Offset D4h" on page 445	00000000h
E0h	4	"SWSMISCI—Offset E0h" on page 445	00000000h
E4h	4	"ASLE—Offset E4h" on page 447	00000000h
F8h	4	"MANID—Offset F8h" on page 447	00000000h
FCh	4	"ASLS—Offset FCh" on page 448	00000000h



PCI Device ID and Vendor ID Register

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

DID: [B:0, D:2, F:0] + 0h

Power Well: Core

Default: 0F318086h

31	28	24	20	16	12	8	4	0																						
0	0	0	0	1	1	1	1	0	0	1	1	0	0	0	1	1	0	0	0	0	1	0	0	0	0	1	0	1	1	0
DEVICEID_0																VENDORID_1														

Bit Range	Default & Access	Description
31:16	0F31h RO	DEVICEID (DEVICEID_0): DID: Identifier assigned to the dev2 PCI
15:0	8086h RO	VENDORID (VENDORID_1): VID: PCI standard identification for Intel

14.9.2 PCICMD_STS—Offset 4h

PCI Command Register and Status Register

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCICMD_STS: [B:0, D:2, F:0] + 4h

Power Well: Core

Default: 00100000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD_6				CAPABILITY_LIST_7	INTERRUPT_DISABLE_1		RSVD_2	
				INTERRUPT_STATUS_8			BUS_MASTER_ENABLE_3	
				RSVD_9			MEMORY_SPACE_ENABLE_4	
							TO SPACE FNARIF 5	

Bit Range	Default & Access	Description
31:21	000h RO	RSVD (RSVD_6): Reserved

14.9.7 GMADR_LSB—Offset 18h



This register is used to uniquely identify the subsystem where the PCI device resides.

Type: PCI Configuration Register
(Size: 32 bits)

SSID SID: [B:0, D:2, F:0] + 2Ch

Power Well: Core

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
SUBID_1					SUBVID_0				

Bit Range	Default & Access	Description
31:16	0000h RW/O	SUBID (SUBID_1): This value is used to identify the vendor of the subsystem. This register should be programmed by BIOS during boot-up. Once written, this register becomes Read_Only. This register can only be cleared by a Reset.
15:0	0000h RW/O	SUBVID (SUBVID_0): This value is used to identify the vendor of the subsystem. This register should be programmed by BIOS during boot-up. Once written, this register becomes Read_Only. This register can only be cleared by a Reset.

14.9.11 CAPPOINT—Offset 34h

This register points to a linked list of capabilities implemented by this device. For VV, the capability linked list is expected to be : (Head-34, PMCAP-D0, MSI-90, VID-B0, ..End)Old : (Head-34, PMCAP-D0, MSI-90, AFLC-A4, VID-B0, .. End)

Type: PCI Configuration Register
(Size: 32 bits)

CAPPOINT: [B:0, D:2, F:0] + 34h

Power Well: Core

Default: 000000D0h

14.9.12 INTRLINE—Offset 3Ch

14.9.13 GGC—Offset 50h



14.9.16 BGSM—Offset 70h

Base of GTT table in Gfx Stolen Memory SOXi Context Save/Restore : Yes. Note : IVB located this register in device 0, 0xB4. Mirrored into Device 2. The GTT table is located within Graphics Stolen Memory in DRAM space. The base of stolen memory will always be below 4G.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

BGSM: [B:0, D:2, F:0] + 70h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BGSM_0				RSVD_1				BGSM_LOCK_2

Bit Range	Default & Access	Description
31:20	000h RW/L	BGSM (BGSM_0): BGSM: Gfx Base of GTT Stolen Memory. This register contains bits 31 to 20 of the base address of GTT Table in stolen DRAM memory. BIOS determines the base of GTT stolen memory by subtracting the GTT graphics stolen memory size (PCI Device 2 offset 50 bits 9:8) from the Graphics Base of Data Stolen Memory (PCI Device 2 offset 5C bits 31:20). Signal : gvd_dsp_Cspgtbladdr_dczfwohdczfwoh[31:20].Note : was 4KB aligned on CDV ie. [31:12]
19:1	00000h RO	RSVD (RSVD_1): Reserved
0	0b RW/L	BGSM_LOCK (BGSM_LOCK_2): This bit will lock all writeable settings in this register including itself

14.9.17 PAVPC—Offset 74h

Protected Audio Video Control. Similar to IVB, BIOS will program this register for Valleyview (not the Gfx Driver). SOXi Context Save/Restore : Yes. For Valleyview, device 2 configuration accesses to 0x74 and Gfx MMIO accesses to 0x1082C0 will both alias to the same register. This register will be located within Gunit.WOPCMBASE is derived from : BDSMbase + GMS size - WOPCMSZ. Note : IVB currently derives from : TOLUD + WOPCMSZ

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PAVPC: [B:0, D:2, F:0] + 74h

Power Well: Core

Default: 00000000h



October 2018
Document Number: 538136, Rev. 4.3



14.9.18 MSI_CAPID_MC—Offset 90h

Message Signaled Interrupts Capability ID.SOXi Context Save/Restore : Yes. Message Signaled Control Register. SOXi Context Save/Restore : Yes

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MSI_CAPID_MC: [B:0, D:2, F:0] + 90h

Power Well: Core

Default: 0000B005h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	RSVD_2	ADDRESS_64_BIT_CAPABLE_3	MULTIPLE_MESSAGE_ENABLE_4	MULTIPLE_MESSAGE_CAPABLE_5	MSI_ENABLE_6	POINTER_TO_NEXT_CAPABILITY_0	CAPABILITY_ID_1	

Bit Range	Default & Access	Description
31:24	00h RO	RSVD (RSVD_2): Reserved
23	0b RO	ADDRESS_64_BIT_CAPABLE (ADDRESS_64_BIT_CAPABLE_3): C64: 32-bit capable only
22:20	000b RW	MULTIPLE_MESSAGE_ENABLE (MULTIPLE_MESSAGE_ENABLE_4): MME: This field is RW for software compatibility, but only a single message is ever generated. System software programs this field to indicate the actual number of messages allocated to this device. This number will be equal to or less than the number actually requested. The encoding is the same as for the MMC field below.
19:17	000b RO	MULTIPLE_MESSAGE_CAPABLE (MULTIPLE_MESSAGE_CAPABLE_5): MMC: This device is only single message capable System Software reads this field to determine the number of messages being requested by this device. Value: Number of requests 000: 1. 001- 111: Reserved
16	0b RW	MSI_ENABLE (MSI_ENABLE_6): MSIE: If set, MSI is enabled and traditional interrupts are not used to generate interrupts. PCICMDSTS.BME must be set for an MSI to be generated. 0 : MSI interrupts are disabled. 1 : MSI interrupts are enabled. Permits sending an MSI interrupt.
15:8	B0h RW/O	POINTER_TO_NEXT_CAPABILITY (POINTER_TO_NEXT_CAPABILITY_0): Points to the next item in the list (B0=VCID support). This register should be programmed by BIOS during boot-up. Once written, this register becomes Read_Only. This register can only be cleared by a Reset.
7:0	05h RO	CAPABILITY_ID (CAPABILITY_ID_1): CAPID: Indicates an MSI capability



Access Method

Power Well: Core

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
ADDRESS_0								RSVD_1

Bit Range	Default & Access	Description
31:2	00000000h RW	ADDRESS (ADDRESS_0): MA: Lower 32-bits of the system specified message address, always DW aligned. When the GVD issues an MSI interrupt as a MEMWR on the SCL, the memory address corresponds to the value of this field
1:0	00b RO	RSVD (RSVD_1): Reserved

14.9.20 MD—Offset 98h

Access Method

Power Well: Core

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD_0				DATA_1				

Bit Range	Default & Access	Description
31:16	0000h RO	RSVD (RSVD_0): Reserved
15:0	0000h RW	DATA (DATA_1): MD: This 16-bit field is programmed by system software. This is forms the lower word of data for the MSI write transaction.



14.9.21 AFLC—Offset A4h

FLR capability advertisement.SOXi Context Save/Restore : Yes

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

AFLC: [B:0, D:2, F:0] + A4h

Power Well: Core

Default: 03060013h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	1	1	0	0	0	0	1
0	0	0	0	1	1	0	0	1
RSVD_2		FLR_CAP_3	TP_CAP_4	LENGTH_5		NXT_PTR_0		CAP_ID_1

Bit Range	Default & Access	Description
31:26	00h RO	RSVD (RSVD_2): Reserved
25	1b RO	FLR_CAP (FLR_CAP_3): Function Level Reset Capability (FLR_CAP): 0: Function Level Reset is not supported 1: Function Level Reset is supported
24	1b RO	TP_CAP (TP_CAP_4): Transactions Pending Capability (TP_CAP): 0: Transactions Pending bit is not supported 1: Transactions Pending bit is supported
23:16	06h RO	LENGTH (LENGTH_5): Advanced Features Structure Length (LENGTH): The Advanced Features Capability structure is 6 bytes long.
15:8	00h RW/O	NXT_PTR (NXT_PTR_0): Next Pointer (NXT_PTR): Removed FLR capability per HSD 259253. Nulled the next pointer. Points to the next item in the list (B0=Vendor Capabilities ID)This register should be programmed by BIOS during boot-up. Once written, this register becomes Read_Only. This register can only be cleared by a Reset. Write once so capabilities list can be changed if needed.
7:0	13h RO	CAP_ID (CAP_ID_1): Capability Identifier (CAP_ID): A value of 13h identifies that this PCI Function is capable of Advanced Features.

14.9.22 AFCTLSTS—Offset A8h

FLR control. Advanced Feature Status.SOXi Context Save/Restore : Not required

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

AFCTLSTS: [B:0, D:2, F:0] + A8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0				RSVD_2		TP_3	RSVD_0	INIT_FLR_1

Vendor Capability ID.SOXi Context Save/Restore : Yes

Type: PCI Configuration Register
(Size: 32 bits) **VCID:** [B:0, D:2, F:0] + B0h

Default: 01070009h

Bit Range	Default & Access	Description
31:24	01h RO	VERSION (VERSION_0): VS: Identifies this as the first revision of the CAPID register definition
23:16	07h RO	LENGTH (LENGTH_1): LEN: this field has the value of 07h to indicate structure length (8 bytes)
15:8	00h RW/O	NEXT_CAPABILITY_POINTER (NEXT_CAPABILITY_POINTER_2): 00 indicates capability list ends here. This register should be programmed by BIOS during boot-up. Once written, this register becomes Read_Only. This register can only be cleared by a Reset. Write-once allowing the capability list to be changed.



Bit Range	Default & Access	Description
7:0	09h RO	CAPABILITY_ID_CID (CAPABILITY_ID_CID_3): Identifies this as a vendor dependent capability pointers

14.9.24 VC—Offset B4h

Vendor Capabilities. Any SKU related fuses would be added here.SOXi Context Save/Restore : Not required

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

VC: [B:0, D:2, F:0] + B4h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD_0								RSVD_1

Bit Range	Default & Access	Description
31:1	0000000h RO	Reserved (RSVD_0): Reserved
0	0b RO	Reserved (RSVD_1): Placeholder for sku related fusing. VLV has no need for this

14.9.25 FD—Offset C4h

Functional Disable. used by SBIOS, not by driver.SOXi Context Save/Restore : Yes

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

FD: [B:0, D:2, F:0] + C4h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RSVD_0 FUNCTION_DISABLE_1									



Power Management Capabilities ID and PM capabilities.SOXi Context Save/Restore :
Yes

Access Method

PMCAPIID: [B:0, D:2, F:0] + D0h

Power Well: Core

Default: 00229001h

Bit Range	Default & Access	Description
31:27	00h RO	PME_SUPPORT (PME_SUPPORT_2): PMES The graphics controller does not generate PME
26	0b RO	D2_SUPPORT (D2_SUPPORT_3): D2S: D2 not supported
25	0b RO	D1_SUPPORT (D1_SUPPORT_4): D1S: D1 not supported
24:22	000b RO	RSVD (RSVD_5): Reserved
21	1b RO	DEVICE_SPECIFIC_INITIALIZATION (DEVICE_SPECIFIC_INITIALIZATION_6): Hardwired to 1
20:19	00b RO	RSVD (RSVD_7): Reserved



Bit Range	Default & Access	Description
18:16	010b RO	VERSION (VERSION_8): Verion compliance with revision 1.1 of PCI PM spec
15:8	90h RW/O	NEXT_POINTER (NEXT_POINTER_0): Indicates the next item in the capabilities list.This register should be programmed by BIOS during boot-up. Once written, this register becomes Read_Only. This register can only be cleared by a Reset. Write once allowing changing of the capabilities list.
7:0	01h RO	CAPABILITIES_ID (CAPABILITIES_ID_1): CAPID: SIG defines this ID is 01h for PM

14.9.27 PMCS—Offset D4h

Power Management Control/Status. Driver doesn't use this register. SBIOS doesn't use this register SOXi Context Save/Restore : Yes.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PMCS: [B:0, D:2, F:0] + D4h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RSVD_0									POWER_STATE_PS_1

Bit Range	Default & Access	Description
31:2	00000000h RO	RSVD (RSVD_0): Reserved
1:0	00b RW	POWER_STATE_PS (POWER_STATE_PS_1): This field indicates the current power state of the IGD and can be used to set the IGD into a new power state. If software attempts to write an unsupported state to this field, write operation must complete normally on the bus, but the data is discarded and no state change occurs. On a transition from D3 to D0 the graphics controller is optionally reset to initial values. Behavior of the graphics controller in supported states is detailed in the power management section of the Bspec. Bits[1:0] Power state 00: D0 Default 01: D1 Not Supported 10: D2 Not Supported 11: D3 Signal : gvd_dsp_power_state_d3_zncznfwoh output to 2D.

14.9.28 SWSMISCI—Offset E0h

Software SMI or SCI. To generate a SW SMI event, software should program bit 15:0 and trigger SMI. Note : ILK/SNB/IVB had SCI and SMI separated (E0 and E8) As long as there is the potential that DVO port legacy drivers exist which expect this register at this address, this must be reserved for this register. The SCI mechanism for driver / BIOS communication. SMI is a system wide lock interrupt (halts the all the cores) as opposed to SCI. Vista and Win7 recommend to use the SCI. The SMI is slowly being



phased out. This register serves 2 purposes: 1) Support selection of SMI or SCI event source (SMISCISEL - bit15) 2) Event trigger (bit 0). To generate a SW SCI event, software (System BIOS/Graphics driver) should program bit 15 (SMISCISEL) to 1. This is typically programmed once (assuming SMIs are never triggered). On a ?0? to ?1? subsequent transition in bit 0 of this register (caused by a software write operation), GMCH sends a single SCI message. The SCI will set the DMISCI bit in its TCO1_STS register and TCOSCI_STS bit in its GPE0 register upon receiving this message from DMI. Once written as 1, software must write a ?0? to this bit to clear it, and all other write transitions (1-)0, 0-)0, 1-)1) or if bit 15 is ?0? will not cause GMCH to send SCI message to DMI link. To generate a SW SMI event, software should program bit 15 to 0 and trigger an SMI.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SWSMISCI: [B:0, D:2, F:0] + E0h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD_0				SMI_OR_SCI_EVENT_SELECT_1	SOFTWARE_SCRATCH_BITS_2			SMI_OR_SCI_EVENT_3

Bit Range	Default & Access	Description
31:16	0000h RO	RSVD (RSVD_0): Reserved
15	0b RW	SMI_OR_SCI_EVENT_SELECT (SMI_OR_SCI_EVENT_SELECT_1): MCS: SMI or SCI event select. 0 = SMI, 1 = SCI
14:1	0000h RW	SOFTWARE_SCRATCH_BITS (SOFTWARE_SCRATCH_BITS_2): Used by driver to communicate information to SBIOS
0	0b RW	SMI_OR_SCI_EVENT (SMI_OR_SCI_EVENT_3): MCE:MCS=1, setting this bit causes an SCI. MCS=0, setting this bit causes an SMI. A 1 to 0, 0 to 0 or 1 to 1 transition of this bit does not trigger any events. The graphics driver writes to this register as a means to interrupt the SBIOS



14.9.29 ASLE—Offset E4h

System Display Event Register. SBIOS writes this reg to generate interrupt to graphics/display driver.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

ASLE: [B:0, D:2, F:0] + E4h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ASLE_SCRATCH_TRIGGER_3_0			ASLE_SCRATCH_TRIGGER_2_1		ASLE_SCRATCH_TRIGGER_1_2		ASLE_SCRATCH_TRIGGER_0_3	

Bit Range	Default & Access	Description
31:24	00h RW	ASLE_SCRATCH_TRIGGER_3 (ASLE_SCRATCH_TRIGGER_3_0): AST3: The writing of this by field (byte) ? even if just writing back the original contents ? will trigger a display controller interrupt (when the memory interface register bits IER[0] = 1 and IMR[0] = 0). If written as part of a 16-bit or 32-bit write, only one interrupt is generated in common
23:16	00h RW	ASLE_SCRATCH_TRIGGER_2 (ASLE_SCRATCH_TRIGGER_2_1): AST2: The writing of this by field (byte) ? even if just writing back the original contents ? will trigger a display controller interrupt (when the memory interface register bits IER[0] = 1 and IMR[0] = 0). If written as part of a 16-bit or 32-bit write, only one interrupt is generated in common
15:8	00h RW	ASLE_SCRATCH_TRIGGER_1 (ASLE_SCRATCH_TRIGGER_1_2): AST1: The writing of this by field (byte) ? even if just writing back the original contents ? will trigger a display controller interrupt (when the memory interface register bits IER[0] = 1 and IMR[0] = 0). If written as part of a 16-bit or 32-bit write, only one interrupt is generated in common
7:0	00h RW	ASLE_SCRATCH_TRIGGER_0 (ASLE_SCRATCH_TRIGGER_0_3): AST0: The writing of this by field (byte) ? even if just writing back the original contents ? will trigger a display controller interrupt (when the memory interface register bits IER[0] = 1 and IMR[0] = 0). If written as part of a 16-bit or 32-bit write, only one interrupt is generated in common

14.9.30 MANID—Offset F8h


Manufacturing ID. SOXi Context Save/Restore : Not required

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MANID: [B:0, D:2, F:0] + F8h

Power Well: Core



October 2018
Document Number: 538136, Rev. 4.3

Default: 00000000h

31	28	24	20	16	12	8	4	0			
0	0	0	0	0	0	0	0	0			
RSVD_0				STEPPING_ID_1				MANUFACTURING_ID_2			

Bit Range	Default & Access	Description
31:24	00h RO	RSVD (RSVD_0): Reserved
23:16	00000000b RO	Stepping_ID (STEPPING_ID_1): Hardwired to strapRID[7:0] via top level metal.23:16 - Manufacturing Stepping ID (00 = A0)
15:0	0000h RO	MANUFACTURING_ID (MANUFACTURING_ID_2): Hardwired to strapMANID[15:0] via top level metal. 15:8 - Foundry (0Fh = Intel, Others = Reserved) 7:3 - Fab process 12h : Fab code for P1263 13h : P1264 14h : P1265 15h : P1266 ... 1Ah : P1271 (VV POR) Others : Reserved 2:0 - Identifies the dot process 000 = Code for 0 001 = Code for .1 (VV POR) 010 = Code for .2 110 = Code for .4 011 = Code for .7

14.9.31 ASLS—Offset FCh

ASL Storage. The Valleyview display driver does not need this register since memory Operational Region (OpRegion) is available. This register is kept for use as scratch space. SOXi Context Save/Restore : Yes This software scratch register only needs to be read/write accessible. The exact bit register usage must be worked out in common between System BIOS and driver software, but storage for switching/indicating up to 6 devices is possible with this amount. For each device, the ASL control method with require two bits for _DOD (BIOS detectable yes or no, VGA/NonVGA), one bit for _DGS (enable/disable requested), and two bits for _DCS (enabled now/disabled now, connected or not).

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

ASLS: [B:0, D:2, F:0] + FCh

Power Well: Core

Default: 00000000h

	31		28		24		20		16		12		8		4		0	
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	SCRATCH_0																	



Bit Range	Default & Access	Description
31:0	00000000h RW	SCRATCH (SCRATCH_0): This register provides a means for the BIOS to communicate with the driver. This definition of this scratch register is worked out in common between System BIOS and driver software. Storage for up to 6 devices is possible. For each device, the ASL control method requires two bits for _DOD (BIOS detectable yes or no, VGA/NonVGA), one bit for _DGS (enable/disable requested), and two bits for DCS (enabled now/disabled now, connected or not).



14.10 Memory Mapped Registers (1 of 2)

Table 172. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
3B4–3B4h	1	"CRX (CRX_MDA)—Offset 3B4h" on page 456	00h
3B5–3B5h	1	"CR (CR_MDA)—Offset 3B5h" on page 457	00h
3C0–3C0h	1	"ARX—Offset 3C0h" on page 458	00h
3C1–3C1h	1	"ARX—Offset 3C0h" on page 458	00h
3C4–3C4h	1	"SRX—Offset 3C4h" on page 459	00h
3C5–3C5h	1	"SRX—Offset 3C4h" on page 459	00h
3C6–3C6h	1	"DACMASK—Offset 3C6h" on page 460	00h
3C8–3C8h	1	"DACWX—Offset 3C8h" on page 461	00h
3C9–3C9h	1	"DACDATA—Offset 3C9h" on page 461	00h
3CA–3CAh	1	"FCR (FCR_Read)—Offset 3CAh" on page 462	00h
3CC–3CCh	1	"MSR (MSR_READ)—Offset 3CCh" on page 463	00h
3CE–3CEh	1	"GRX—Offset 3CEh" on page 464	00h
3CF–3CFh	1	"GRX—Offset 3CEh" on page 464	00h
3D4–3D4h	1	"CRX (CRX_CGA)—Offset 3D4h" on page 466	00h
3D5–3D5h	1	"CR (CR_CGA)—Offset 3D5h" on page 466	00h
5010–5013h	4	"GPIOCTL_0—Offset 5010h" on page 467	00000808h
5014–5017h	4	"GPIOCTL_1—Offset 5014h" on page 469	00000808h
5018–501Bh	4	"GPIOCTL_2—Offset 5018h" on page 471	00000808h
501C–501Fh	4	"GPIOCTL_3—Offset 501Ch" on page 472	00000808h
5020–5023h	4	"GPIOCTL_4—Offset 5020h" on page 474	00000808h
5100–5103h	4	"GMBUS0—Offset 5100h" on page 476	00000000h
5104–5107h	4	"GMBUS1—Offset 5104h" on page 477	00000000h
5108–510Bh	4	"GMBUS2—Offset 5108h" on page 479	00000800h
510C–510Fh	4	"GMBUS3—Offset 510Ch" on page 481	00000000h
5110–5113h	4	"GMBUS4—Offset 5110h" on page 482	00000000h
5120–5123h	4	"GMBUS5—Offset 5120h" on page 483	00000000h
5130–5133h	4	"GMBUS6—Offset 5130h" on page 484	00000000h
5134–5137h	4	"GMBUS7—Offset 5134h" on page 484	00000000h
6014–6017h	4	"DPLLA_CTRL—Offset 6014h" on page 485	00002000h
6018–601Bh	4	"DPLLB_CTRL—Offset 6018h" on page 488	00006000h
601C–601Fh	4	"DPLLAMD—Offset 601Ch" on page 491	00000003h
6020–6023h	4	"DPLLBMD—Offset 6020h" on page 493	00000003h
6024–6027h	4	"RAWCLK_FREQ—Offset 6024h" on page 494	0000007Dh
6104–6107h	4	"D_STATE—Offset 6104h" on page 495	20D00400h
6200–6203h	4	"DSPCLK_GATE_D—Offset 6200h" on page 496	10000000h
6204–6207h	4	"DPPSR_CGDIS—Offset 6204h" on page 499	00000200h



Table 172. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
6210–6213h	4	"RAMCLK_GATE_D—Offset 6210h" on page 502	00000000h
6500–6503h	4	"FW_BLC_SELF—Offset 6500h" on page 505	00000000h
6504–6507h	4	"MI_ARB—Offset 6504h" on page 506	00000000h
6508–650Bh	4	"CZCLK_CDCLK_FREQ_RATIO—Offset 6508h" on page 506	00000077h
650C–650Fh	4	"GCI_CONTROL—Offset 650Ch" on page 509	00004000h
6510–6513h	4	"GMBUSFREQ—Offset 6510h" on page 511	000000A0h
A000–A003h	4	"DPALETTE_A—Offset A000h" on page 512	00000000h
A800–A803h	4	"DPALETTE_B—Offset A800h" on page 512	00000000h
B000–B003h	4	"MIPIA_DEVICE_READY_REG—Offset B000h" on page 513	00000000h
B004–B007h	4	"MIPIA_INTR_STAT_REG—Offset B004h" on page 514	00000000h
B008–B00Bh	4	"MIPIA_INTR_EN_REG—Offset B008h" on page 516	00000000h
B00C–B00Fh	4	"MIPIA_DSI_FUNC_PRG__REG—Offset B00Ch" on page 518	00000001h
B010–B013h	4	"MIPIA_HS_TX_TIMEOUT_REG—Offset B010h" on page 519	00000000h
B014–B017h	4	"MIPIA_LP_RX_TIMEOUT_REG—Offset B014h" on page 520	00000000h
B018–B01Bh	4	"MIPIA_TURN_AROUND_TIMEOUT_REG—Offset B018h" on page 520	00000000h
B01C–B01Fh	4	"MIPIA_DEVICE_RESET_TIMER—Offset B01Ch" on page 521	00000000h
B020–B023h	4	"MIPIA_DPI_RESOLUTION_REG—Offset B020h" on page 522	00000000h
B024–B027h	4	"MIPIA_DBI_RESOLUTION_REG—Offset B024h" on page 522	00000000h
B028–B02Bh	4	"MIPIA_HORIZ_SYNC_PADDING_COUNT—Offset B028h" on page 523	00000000h
B02C–B02Fh	4	"MIPIA_HORIZ_BACK_PORCH_COUNT—Offset B02Ch" on page 524	00000000h
B030–B033h	4	"MIPIA_HORIZ_FRONT_PORCH_COUNT—Offset B030h" on page 524	00000000h
B034–B037h	4	"MIPIA_HORIZ_ACTIVE_AREA_COUNT—Offset B034h" on page 525	00000000h
B038–B03Bh	4	"MIPIA_VERT_SYNC_PADDING_COUNT—Offset B038h" on page 526	00000000h
B03C–B03Fh	4	"MIPIA_VERT_BACK_PORCH_COUNT—Offset B03Ch" on page 526	00000000h
B040–B043h	4	"MIPIA_VERT_FRONT_PORCH_COUNT—Offset B040h" on page 527	00000000h
B044–B047h	4	"MIPIA_HIGH_LOW_SWITCH_COUNT—Offset B044h" on page 528	00000000h
B048–B04Bh	4	"MIPIA_DPI_CTRL_REG—Offset B048h" on page 529	00000000h
B04C–B04Fh	4	"MIPIA_DPI_DATA_REGISTER—Offset B04Ch" on page 530	00000000h
B050–B053h	4	"MIPIA_INIT_COUNT_REGISTER—Offset B050h" on page 530	00000000h
B054–B057h	4	"MIPIA_MAX_RETURN_PKT_SIZE_REGISTER—Offset B054h" on page 531	00000000h
B058–B05Bh	4	"MIPIA_VIDEO_MODE_FORMAT_REGISTER—Offset B058h" on page 531	00000000h
B05C–B05Fh	4	"MIPIA_EOT_DISABLE_REGISTER—Offset B05Ch" on page 532	00000000h
B060–B063h	4	"MIPIA_LP_BYTECLK_REGISTER—Offset B060h" on page 534	00000000h
B064–B067h	4	"MIPIA_LP_GEN_DATA_REGISTER—Offset B064h" on page 535	00000000h
B068–B06Bh	4	"MIPIA_HS_GEN_DATA_REGISTER—Offset B068h" on page 535	00000000h
B06C–B06Fh	4	"MIPIA_LP_GEN_CTRL_REGISTER—Offset B06Ch" on page 536	00000000h
B070–B073h	4	"MIPIA_HS_GEN_CTRL_REGISTER—Offset B070h" on page 537	00000000h



Table 172. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
B074–B077h	4	"MIPIA_GEN_FIFO_STAT_REGISTER—Offset B074h" on page 538	1E060606h
B078–B07Bh	4	"MIPIA_HS_LS_DBI_ENABLE_REG—Offset B078h" on page 539	00000000h
B07C–B07Fh	4	"MIPIA_RESERVED—Offset B07Ch" on page 539	00000000h
B080–B083h	4	"MIPIA_DPHY_PARAM_REG—Offset B080h" on page 540	0B061A04h
B084–B087h	4	"MIPIA_DBI_BW_CTRL_REG—Offset B084h" on page 541	00000000h
B088–B08Bh	4	"MIPIA_CLK_LANE_SWITCHING_TIME_CNT—Offset B088h" on page 541	00000000h
B08C–B08Fh	4	"MIPIA_STOP_STATE_STALL—Offset B08Ch" on page 542	00000000h
B090–B093h	4	"MIPIA_INTR_STAT_REG_1—Offset B090h" on page 543	00000000h
B094–B097h	4	"MIPIA_INTR_EN_REG_1—Offset B094h" on page 543	00000000h
B100–B103h	4	"MIPIA_DBI_TYPEC_CTRL—Offset B100h" on page 544	00000000h
B104–B107h	4	"MIPIA_CTRL—Offset B104h" on page 545	00000000h
B108–B10Bh	4	"MIPIA_DATA_ADD—Offset B108h" on page 546	00000000h
B10C–B10Fh	4	"MIPIA_DATA_LEN—Offset B10Ch" on page 547	00000000h
B110–B113h	4	"MIPIA_CMD_ADD—Offset B110h" on page 547	00000000h
B114–B117h	4	"MIPIA_CMD_LEN—Offset B114h" on page 548	00000000h
B118–B11Bh	4	"MIPIA_RD_DATA_RETURN0—Offset B118h" on page 549	00000000h
B11C–B11Fh	4	"MIPIA_RD_DATA_RETURN1—Offset B11Ch" on page 549	00000000h
B120–B123h	4	"MIPIA_RD_DATA_RETURN2—Offset B120h" on page 550	00000000h
B124–B127h	4	"MIPIA_RD_DATA_RETURN3—Offset B124h" on page 551	00000000h
B128–B12Bh	4	"MIPIA_RD_DATA_RETURN4—Offset B128h" on page 551	00000000h
B12C–B12Fh	4	"MIPIA_RD_DATA_RETURN5—Offset B12Ch" on page 552	00000000h
B130–B133h	4	"MIPIA_RD_DATA_RETURN6—Offset B130h" on page 552	00000000h
B134–B137h	4	"MIPIA_RD_DATA_RETURN7—Offset B134h" on page 553	00000000h
B138–B13Bh	4	"MIPIA_RD_DATA_VALID—Offset B138h" on page 554	00000000h
B800–B803h	4	"MIPIC_DEVICE_READY_REG—Offset B800h" on page 554	00000000h
B804–B807h	4	"MIPIC_INTR_STAT_REG—Offset B804h" on page 555	00000000h
B808–B80Bh	4	"MIPIC_INTR_EN_REG—Offset B808h" on page 557	00000000h
B80C–B80Fh	4	"MIPIC_DSI_FUNC_PRG__REG—Offset B80Ch" on page 559	00000001h
B810–B813h	4	"MIPIC_HS_TX_TIMEOUT_REG—Offset B810h" on page 560	00000000h
B814–B817h	4	"MIPIC_LP_RX_TIMEOUT_REG—Offset B814h" on page 561	00000000h
B818–B81Bh	4	"MIPIC_TURN_AROUND_TIMEOUT_REG—Offset B818h" on page 562	00000000h
B81C–B81Fh	4	"MIPIC_DEVICE_RESET_TIMER—Offset B81Ch" on page 562	00000000h
B820–B823h	4	"MIPIC_DPI_RESOLUTION_REG—Offset B820h" on page 563	00000000h
B824–B827h	4	"MIPIC_DBI_RESOLUTION_REG—Offset B824h" on page 564	00000000h
B828–B82Bh	4	"MIPIC_HORIZ_SYNC_PADDING_COUNT—Offset B828h" on page 564	00000000h
B82C–B82Fh	4	"MIPIC_HORIZ_BACK_PORCH_COUNT—Offset B82Ch" on page 565	00000000h
B830–B833h	4	"MIPIC_HORIZ_FRONT_PORCH_COUNT—Offset B830h" on page 566	00000000h
B834–B837h	4	"MIPIC_HORIZ_ACTIVE_AREA_COUNT—Offset B834h" on page 566	00000000h



Table 172. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
B838–B83Bh	4	"MIPIC_VERT_SYNC_PADDING_COUNT—Offset B838h" on page 567	00000000h
B83C–B83Fh	4	"MIPIC_VERT_BACK_PORCH_COUNT—Offset B83Ch" on page 568	00000000h
B840–B843h	4	"MIPIC_VERT_FRONT_PORCH_COUNT—Offset B840h" on page 568	00000000h
B844–B847h	4	"MIPIC_HIGH_LOW_SWITCH_COUNT—Offset B844h" on page 569	00000000h
B848–B84Bh	4	"MIPIC_DPI_CTRL_REG—Offset B848h" on page 570	00000000h
B84C–B84Fh	4	"MIPIC_DPI_DATA_REGISTER—Offset B84Ch" on page 571	00000000h
B850–B853h	4	"MIPIC_INIT_COUNT_REGISTER—Offset B850h" on page 572	00000000h
B854–B857h	4	"MIPIC_MAX_RETURN_PKT_SIZE_REGISTER—Offset B854h" on page 572	00000000h
B858–B85Bh	4	"MIPIC_VIDEO_MODE_FORMAT_REGISTER—Offset B858h" on page 573	00000000h
B85C–B85Fh	4	"MIPIC_EOT_DISABLE_REGISTER—Offset B85Ch" on page 574	00000000h
B860–B863h	4	"MIPIC_LP_BYTECLK_REGISTER—Offset B860h" on page 576	00000000h
B864–B867h	4	"MIPIC_LP_GEN_DATA_REGISTER—Offset B864h" on page 577	00000000h
B868–B86Bh	4	"MIPIC_HS_GEN_DATA_REGISTER—Offset B868h" on page 577	00000000h
B86C–B86Fh	4	"MIPIC_LP_GEN_CTRL_REGISTER—Offset B86Ch" on page 578	00000000h
B870–B873h	4	"MIPIC_HS_GEN_CTRL_REGISTER—Offset B870h" on page 578	00000000h
B874–B877h	4	"MIPIC_GEN_FIFO_STAT_REGISTER—Offset B874h" on page 579	1E060606h
B878–B87Bh	4	"MIPIC_HS_LS_DBI_ENABLE_REG—Offset B878h" on page 581	00000000h
B87C–B87Fh	4	"MIPIC_RESERVED—Offset B87Ch" on page 581	00000000h
B880–B883h	4	"MIPIC_DPHY_PARAM_REG—Offset B880h" on page 582	0B061A04h
B884–B887h	4	"MIPIC_DBI_BW_CTRL_REG—Offset B884h" on page 583	00000000h
B888–B88Bh	4	"MIPIC_CLK_LANE_SWITCHING_TIME_CNT—Offset B888h" on page 583	00000000h
B88C–B88Fh	4	"MIPIC_STOP_STATE_STALL—Offset B88Ch" on page 584	00000000h
B890–B893h	4	"MIPIC_INTR_STAT_REG_1—Offset B890h" on page 585	00000000h
B894–B897h	4	"MIPIC_INTR_EN_REG_1—Offset B894h" on page 585	00000000h
B904–B907h	4	"MIPIC_CTRL—Offset B904h" on page 586	00000000h
B908–B90Bh	4	"MIPIC_DATA_ADD—Offset B908h" on page 587	00000000h
B90C–B90Fh	4	"MIPIC_DATA_LEN—Offset B90Ch" on page 587	00000000h
B910–B913h	4	"MIPIC_CMD_ADD—Offset B910h" on page 588	00000000h
B914–B917h	4	"MIPIC_CMD_LEN—Offset B914h" on page 589	00000000h
B918–B91Bh	4	"MIPIC_RD_DATA_RETURN0—Offset B918h" on page 589	00000000h
B91C–B91Fh	4	"MIPIC_RD_DATA_RETURN1—Offset B91Ch" on page 590	00000000h
B920–B923h	4	"MIPIC_RD_DATA_RETURN2—Offset B920h" on page 591	00000000h
B924–B927h	4	"MIPIC_RD_DATA_RETURN3—Offset B924h" on page 591	00000000h
B928–B92Bh	4	"MIPIC_RD_DATA_RETURN4—Offset B928h" on page 592	00000000h
B92C–B92Fh	4	"MIPIC_RD_DATA_RETURN5—Offset B92Ch" on page 592	00000000h
B930–B933h	4	"MIPIC_RD_DATA_RETURN6—Offset B930h" on page 593	00000000h
B934–B937h	4	"MIPIC_RD_DATA_RETURN7—Offset B934h" on page 594	00000000h



Table 172. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
B938–B93Bh	4	"MIPIC_RD_DATA_VALID—Offset B938h" on page 594	00000000h
60000–60003h	4	"HTOTAL_A—Offset 60000h" on page 595	00000000h
60004–60007h	4	"HBLANK_A—Offset 60004h" on page 596	00000000h
60008–6000Bh	4	"HSYNC_A—Offset 60008h" on page 597	00000000h
6000C–6000Fh	4	"VTOTAL_A—Offset 6000Ch" on page 598	00000000h
60010–60013h	4	"VBLANK_A—Offset 60010h" on page 599	00000000h
60014–60017h	4	"VSYNC_A—Offset 60014h" on page 600	00000000h
6001C–6001Fh	4	"PIPESRCA—Offset 6001Ch" on page 601	00000000h
60020–60023h	4	"BCLRPAT_A—Offset 60020h" on page 602	00000000h
60028–6002Bh	4	"VSYNCSHIFT_A—Offset 60028h" on page 603	00000000h
60030–60033h	4	"TRANSADATAM1—Offset 60030h" on page 604	7E000000h
60034–60037h	4	"TRANSADATAN1—Offset 60034h" on page 604	00000000h
60038–6003Bh	4	"TRANSADATAM2—Offset 60038h" on page 605	7E000000h
6003C–6003Fh	4	"TRANSADATAN2—Offset 6003Ch" on page 606	00000000h
60040–60043h	4	"TRANSADPLINKM1—Offset 60040h" on page 606	00000000h
60044–60047h	4	"TRANSADPLINKN1—Offset 60044h" on page 607	00000000h
60048–6004Bh	4	"TRANSADPLINKM2—Offset 60048h" on page 608	00000000h
6004C–6004Fh	4	"TRANSADPLINKN2—Offset 6004Ch" on page 608	00000000h
60050–60053h	4	"CRCCTRLREDA—Offset 60050h" on page 609	00000000h
60054–60057h	4	"CRCCTRLGREENA—Offset 60054h" on page 610	00000000h
60058–6005Bh	4	"CRCCTRLBLUEA—Offset 60058h" on page 610	00000000h
6005C–6005Fh	4	"CRCCTRLALPHA—Offset 6005Ch" on page 611	00000000h
60060–60063h	4	"CRCRESREDA—Offset 60060h" on page 612	00000000h
60064–60067h	4	"CRCRESGREENA—Offset 60064h" on page 612	00000000h
60068–6006Bh	4	"CRCRESBLUEA—Offset 60068h" on page 613	00000000h
6006C–6006Fh	4	"CRCRESALPHA—Offset 6006Ch" on page 614	00000000h
60070–60073h	4	"CRCCTRLRESIDUE2A—Offset 60070h" on page 615	00000000h
60080–60083h	4	"CRCRESRESIDUE2A—Offset 60080h" on page 615	00000000h
60090–60093h	4	"PSRCTLA—Offset 60090h" on page 616	00000000h
60094–60097h	4	"PSRSTATA—Offset 60094h" on page 618	00000000h
60098–6009Bh	4	"PSRCRC1A—Offset 60098h" on page 619	00000000h
6009C–6009Fh	4	"PSRCRC2A—Offset 6009Ch" on page 620	00000000h
600A0–600A3h	4	"VSCSDPA—Offset 600A0h" on page 621	00000000h
600B0–600B3h	4	"PIPEAWIDEGAMUTCOLORCORRECTIONC01_C00COEFFICIENTS—Offset 600B0h" on page 621	00000000h
600B4–600B7h	4	"PIPEAWIDEGAMUTCOLORCORRECTIONC02COEFFICIENT—Offset 600B4h" on page 622	00000000h
600B8–600BBh	4	"PIPEAWIDEGAMUTCOLORCORRECTIONC11_C10COEFFICIENTS—Offset 600B8h" on page 623	00000000h



Table 172. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
600BC–600BFh	4	"PIPEAWIDEGAMUTCOLORCORRECTIONC12COEFFICIENT—Offset 600BCh" on page 623	00000000h
600C0–600C3h	4	"PIPEAWIDEGAMUTCOLORCORRECTIONC21_C20COEFFICIENTS—Offset 600C0h" on page 624	00000000h
600C4–600C7h	4	"PIPEAWIDEGAMUTCOLORCORRECTIONC22COEFFICIENT—Offset 600C4h" on page 625	00000000h
60200–60203h	4	"VIDEO_DIP_CTL_A—Offset 60200h" on page 625	20200900h
60208–6020Bh	4	"VIDEO_DIP_DATA_A—Offset 60208h" on page 627	00000000h
60210–60213h	4	"VIDEO_DIP_GDCP_PAYLOAD_A—Offset 60210h" on page 628	00000000h
61000–61003h	4	"HTOTAL_B—Offset 61000h" on page 629	00000000h
61004–61007h	4	"HBLANK_B—Offset 61004h" on page 630	00000000h
61008–6100Bh	4	"HSYNC_B—Offset 61008h" on page 631	00000000h
6100C–6100Fh	4	"VTOTAL_B—Offset 6100Ch" on page 631	00000000h
61010–61013h	4	"VBLANK_B—Offset 61010h" on page 632	00000000h
61014–61017h	4	"VSYNC_B—Offset 61014h" on page 633	00000000h
6101C–6101Fh	4	"PIPEBSRC—Offset 6101Ch" on page 634	00000000h
61020–61023h	4	"BCLRPAT_B—Offset 61020h" on page 634	00000000h
61028–6102Bh	4	"VSYNCSHIFT_B—Offset 61028h" on page 635	00000000h
61030–61033h	4	"TRANSBDATAM1—Offset 61030h" on page 636	7E000000h
61034–61037h	4	"TRANSBDATAN1—Offset 61034h" on page 637	00000000h
61038–6103Bh	4	"TRANSBDATAM2—Offset 61038h" on page 638	7E000000h
6103C–6103Fh	4	"TRANSBDATAN2—Offset 6103Ch" on page 638	00000000h
61040–61043h	4	"TRANSBDPLINKM1—Offset 61040h" on page 639	00000000h
61044–61047h	4	"TRANSBDPLINKN1—Offset 61044h" on page 640	00000000h
61048–6104Bh	4	"TRANSBDPLINKM2—Offset 61048h" on page 640	00000000h
6104C–6104Fh	4	"TRANSBDPLINKN2—Offset 6104Ch" on page 641	00000000h

14.10.1 CRX (CRX_MDA)—Offset 3B4h

CRT Controller Index Register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3B4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h



14.10.3 ARX—Offset 3C0h

Attribute Controller Index Register. Includes the 22 registers that share this offset (with different indexes). -enum ARX_e

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
ARX_REGISTER_DESCRIPTIONS							
Bit Range	Default & Access	Field Name (ID): Description					
7:0	0b RW	ARX_REGISTER_DESCRIPTIONS: ARX indexed register descriptions					

14.10.4 AR—Offset 3C1h

AR index registers. Includes the 21 registers that share this offset (with different indexes.) -enum AR_e- in this document will lead to register definitions

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C1h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h



7				4					0
0	0	0	0	0	0	0	0	0	0
					AR_REGISTER_DESCRIPTIONS				

Bit Range	Default & Access	Field Name (ID): Description
7:0	0b RW	AR_REGISTER_DESCRIPTIONS: AR indexed register descriptions

14.10.5 SRX—Offset 3C4h

Sequencer Index

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
RESERVED					SEQUENCER_INDEX				



14.10.6 SR—Offset 3C5h

SR index registers

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C5h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
				SR_REGISTER_DESCRIPTIONS			

Bit Range	Default & Access	Field Name (ID): Description
7:0	0b RW	SR_REGISTER_DESCRIPTIONS: SR indexed register descriptions

14.10.7 DACMASK—Offset 3C6h

Pixel Data Mask Register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C6h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
				PIXEL_DATA_MASK			



Bit Range	Default & Access	Field Name (ID): Description
7:0	0b RW	PIXEL_DATA_MASK: In indexed-color mode, the 8 bits of this register are logically ANDed with the 8 bits of pixel data received from the frame buffer for each pixel. The result of this ANDing process becomes the actual index used to select color data positions within the palette. This has the effect of limiting the choice of color data positions that may be specified by the incoming 8-bit data. 0 = Corresponding bit in the resulting 8-bit index being forced to 0. 1 = Allows the corresponding bit in the resulting index to reflect the actual value of the corresponding bit in the incoming 8-bit pixel data.

14.10.8 DACWX—Offset 3C8h

Palette Write Index Register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C8h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
PALETTE_WRITE_INDEX							

Bit Range	Default & Access	Field Name (ID): Description
7:0	0b WO	PALETTE_WRITE_INDEX: The 8-bit index value programmed into this register chooses which of 256 standard color data positions within the palette are to be made accessible for being written via the Palette Data Register (DACDATA). The index value held in this register is automatically incremented when all three bytes of the color data position selected by the current index have been written. This register allows access to the palette even when running non-VGA display modes.

14.10.9 DACDATA—Offset 3C9h

Palette Data Register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C9h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h



7	4	0
0	0	0
PALETTE_DATA		

Bit Range	Default & Access	Field Name (ID): Description
7:0	0b RW	PALETTE_DATA: This byte-wide data port provides read or write access to the three bytes of data of each color data position selected using the Palette Read Index Register (DACRX) or the Palette Write Index Register (DACWX). The three bytes in each color data position are read or written in three successive read or write operations. The first byte read or written specifies the intensity of the red component of the color specified in the selected color data position. The second byte is for the green component, and the third byte is for the blue component. When writing data to a color data position, all three bytes must be written before the hardware will actually update the three bytes of the selected color data position. When reading or writing to a color data position, ensure that neither the Palette Read Index Register (DACRX) or the Palette Write Index Register (DACWX) are written to before all three bytes are read or written. A write to either of these two registers causes the circuitry that automatically cycles through providing access to the bytes for red, green and blue components to be reset such that the byte for the red component is the one that will be accessed by the next read or write operation via this register. This register allows access to the palette even when running non-VGA display modes. Writes to the palette can cause sparkle if not done during inactive video periods. This sparkle is caused by an attempt to write and read the same address on the same cycle. Anti-sparkle circuits will substitute the previous pixel value for the read output.

14.10.10 FCR (FCR_Read)—Offset 3CAh

Feature Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3CAh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7	4	0
0	0	0
RESERVED		
VSYNC_CONTROL		
RESERVED_1		

Bit Range	Default & Access	Field Name (ID): Description
7:4	0b RW	RESERVED: Read as 0.



Bit Range	Default & Access	Field Name (ID): Description
3	0b RW	VSYNC_CONTROL: This bit is provided for compatibility only and has no other function. Reads and writes to this bit have no effect other than to change the value of this bit. The previous definition of this bit selected the output on the VSYNC pin. 0 = Was used to set VSYNC out put on the VSYNC pin (default). 1 = Was used to set the log i cal 'OR' of VSYNC and Display Ena ble output on the VSYNC pin. This capability was not typically very useful..
2:0	0b RW	RESERVED_1: Read as 0.

14.10.11 MSR (MSR_READ)—Offset 3CCh

Miscellaneous Output

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3CCh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7	0	0	0	4	0	0	0	0
CRT_VSYNC_POLARITY	CRT_HSYNC_POLARITY	PAGE_SELECT	RESERVED	CLOCK_SELECT	A0000_BFFFFH_MEMORY_ACCESS_ENABLE	I_O_ADDRESS_SELECT		

Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	CRT_VSYNC_POLARITY: This is a legacy function that is used in native VGA modes. For most cases, sync polarity will be controlled by the port control bits. The VGA settings can be optionally selected for compatibility with the original VGA when used in the VGA native mode. Sync polarity was used in VGA to signal the monitor how many lines of active display are being generated. 0 = Positive Polarity (default). 1 = Negative Polarity.
6	0b RW	CRT_HSYNC_POLARITY: This is a legacy function that is used in native VGA modes. For most cases, sync polarity will be controlled by the port control bits. The VGA settings can be optionally selected for compatibility with the original VGA when used in the VGA native mode. 0 = Positive Polarity (default). 1 = Negative Polarity



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	PAGE_SELECT: In Odd/Even Memory Map Mode 1 (GR6), this bit selects the upper or lower 64 KB page in display memory for CPU access: 0 = Upper page (default) 1 = Lower page. Selects between two 64KB pages of frame buffer memory during standard VGA odd/even modes (modes 0h through 5h). Bit 1 of register GR06 can also program this bit in other modes. Note that this bit is would normally set to 1 by the software.
4	0b RW	RESERVED: Read as 0.
3:2	0b RW	CLOCK_SELECT: These bits can select the dot clock source for the CRT interface. The bits should be used to select the dot clock in standard native VGA modes only. When in the centering or upper left corner modes, these bits should be set to have no effect on the clock rate. The actual frequencies that these bits select, if they have any affect at all, is programmable through the DPLL registers that default to the standard values used for VGA. 00 = CLK0, 25.175 MHz (for standard VGA modes with 640 pixel (8-dot) horizontal resolution) (default) 01 = CLK1, 28.322 MHz. (for standard VGA modes with 720 pixel (9-dot) horizontal resolution) 10 = Was used to select an external clock (now unused) 11 = Reserved
1	0b RW	A0000_BFFFFH_MEMORY_ACCESS_ENABLE: VGA Compatibility bit enables access to local video memory (frame buffer) at A0000(BFFFFh). When disabled, accesses to VGA memory are blocked in this region. This bit is independent of and does not block CPU access to the video linear frame buffer at other addresses. Note that it is typical for AGP chipsets to shadow this register to allow proper steering of memory accesses to the proper bus. 0 = Prevent CPU access to memory/registers/ROM through the A0000-BFFFF VGA memory aperture (default). 1 = Allow CPU access to memory/registers/ROM through the A0000-BFFFF VGA memory aperture. This memory must be mapped as UC by the CPU; see VGA Host Access Memory Munging in Display and Overlay Functions.
0	0b RW	I_O_ADDRESS_SELECT: This bit selects 3Bxh or 3Dxh as the I/O address for the CRT Controller registers, the Feature Control Register (FCR), and Input Status Register 1 (ST01). Presently ignored (whole range is claimed), but will ignore 3Bx for color configuration or 3Dx for monochrome. Note that it is typical in AGP chipsets to shadow this bit and properly steer I/O cycles to the proper bus for operation where a MDA exists on another bus such as ISA. 0 = Select 3Bxh I/O address (MDA emulation) (default). 1 = Select 3Dxh I/O address (CGA emulation).

14.10.12 GRX—Offset 3CEh

GRX Graphics Controller Index Register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3CEh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h



7				4				0
0	0	0	0	0	0	0	0	0
RESERVED				SEQUENCER_REGISTER_INDEX				

Bit Range	Default & Access	Field Name (ID): Description
7:5	0b RW	RESERVED: Read as 0.
4:0	0b RW	SEQUENCER_REGISTER_INDEX: This field selects any one of the graphics controller registers (GR00-GR11]) to be accessed via the data port at I/O (or memory offset) location 3CFh.

14.10.13 GR—Offset 3CFh

GR index registers

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3CFh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7				4				0
0	0	0	0	0	0	0	0	0
				GR_REGISTER_DESCRIPTIONS				

Bit Range	Default & Access	Field Name (ID): Description
7:0	0b RW	GR_REGISTER_DESCRIPTIONS: GR indexed register descriptions



14.10.14 CRX (CRX_CGA)—Offset 3D4h

CRT Controller Index Register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3D4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7	4	0
0	0	0
RESERVED	CRT_CONTROLLER_INDEX	

Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	RESERVED: Read as 0.
6:0	0b RW	CRT_CONTROLLER_INDEX: These 7 bits are used to select any one of the CRT controller registers to be accessed via the data port at I/O location 3B5h or 3D5h, depending upon whether the graphics system is configured for MDA or CGA emulation. The data port memory address offsets are 3B5h/3D5h.

14.10.15 CR (CR_CGA)—Offset 3D5h

CR index registers

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3D5h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h



7	4	0
0	0	0
CR_REGISTER_DESCRIPTIONS		

Bit Range	Default & Access	Field Name (ID): Description
7:0	0b RW	CR_REGISTER_DESCRIPTIONS: CR indexed register descriptions

14.10.16 GPIOCTL_0—Offset 5010h

GPIO Control Registers GPIO I2C register (gmbus_register.v reg_gpio0, reg_gpio1, reg_gpio2, reg_gpio3, reg_gpio4)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 5010h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000808h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED						GPIO_DATA_IN_RO	GPIO_CLOCK_DATA_IN_RO	
						GPIO_DATA_VALUE_R_W	GPIO_CLOCK_DATA_VALUE_R_W	
						GPIO_DATA_MASK_WO	GPIO_CLOCK_DATA_MASK_WO	
						GPIO_DATA_DIRECTION_VALUE_R_W	GPIO_CLOCK_DIRECTION_VALUE_R_W	
						GPIO_DATA_DIRECTION_MASK_WO	GPIO_CLOCK_DIRECTION_MASK_WO	
						RESERVED_1		

Bit Range	Default & Access	Field Name (ID): Description
31:13	0b RW	RESERVED: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
12	0b RO	GPIO_DATA_IN_RO: This is the value that is sampled on the GPIO_Data pin as an input. This input is synchronized to the Core Clock domain. Because the default setting is this buffer is an input, this bit is undefined at reset. AccessType: Read Only
11	1b RW	GPIO_DATA_VALUE_R_W: This is the value that should be place on the GPIO Data pin as an output. This value is only written into the register if GPIO DATA MASK is also asserted. The value will appear on the pin if this data value is actually written to this register and the GPIO Data DIRECTION VALUE contains a value that will configure the pin as an output. Default = 1. The GPIO default clock data value is programmed to 1 in hardware. The hardware drives a default of 1 since the I2C interface defaults to a 1 . (this mimics the I2C external pull-ups on the bus)
10	0b WO	GPIO_DATA_MASK_WO: This is a mask bit to determine whether the GPIO DATA VALUE bit should be written into the register. This value is not stored and when read returns 0. 0 = Do NOT write GPIO Data Value bit (default). 1 = Write GPIO Data Value bit. AccessType: Write Only
9	0b RW	GPIO_DATA_DIRECTION_VALUE_R_W: This is the value that should be used to define the output enable of the GPIO Data pin. This value is only written into the register if GPIO Data DIRECTION MASK is also asserted. The value that will appear on the pin is defined by what is in the register for the GPIO DATA VALUE bit. 0 = Pin is configured as an input (default) 1 = Pin is configured as an output.
8	0b WO	GPIO_DATA_DIRECTION_MASK_WO: This is a mask bit to determine whether the GPIO DIRECTION VALUE bit should be written into the register. This value is not stored and when read always returns 0. 0 = Do NOT write GPIO Data Direction Value bit (default). 1 = Write GPIO Data Direction Value bit. AccessType: Write Only
7:5	0b RW	RESERVED_1: must be written with zeros.
4	0b RO	GPIO_CLOCK_DATA_IN_RO: This is the value that is sampled on the GPIO Clock pin as an input. This input is synchronized to the Core Clock domain. Because the default setting is this buffer is an input, this bit is undefined at reset. AccessType: Read Only
3	1b RW	GPIO_CLOCK_DATA_VALUE_R_W: This is the value that should be place on the GPIO Clk pin as an output. This value is only written into the register if GPIO Clock DATA MASK is also asserted. The value will appear on the pin if this data value is actually written to this register and the GPIO Clock DIRECTION VALUE contains a value that will configure the pin as an output. Default = 1. The GPIO default clock data value is programmed to 1 in hardware. The hardware drives a default of 1 since the I2C interface defaults to a 1 . (this mimics the I2C external pull-ups on the bus)
2	0b WO	GPIO_CLOCK_DATA_MASK_WO: This is a mask bit to determine whether the GPIO Clock DATA VALUE bit should be written into the register. This value is not stored and when read always returns 0. 0 = Do NOT write GPIO Clock Data Value bit (default). 1 = Write GPIO Clock Data Value bit. AccessType: Write Only
1	0b RW	GPIO_CLOCK_DIRECTION_VALUE_R_W: This is the value that should be used to define the output enable of the GPIO Clock pin. This value is only written into the register if GPIO Clock DIRECTION MASK is also asserted. The value that will appear on the pin is defined by what is in the register for the GPIO Clock DATA VALUE bit. 0 = Pin is configured as an input and the output driver is set to tri-state (default) 1 = Pin is configured as an output.



Bit Range	Default & Access	Field Name (ID): Description
0	0b WO	GPIO_CLOCK_DIRECTION_MASK_WO: This is a mask bit to determine whether the GPIO Clock DIRECTION VALUE bit should be written into the register. This value is not stored and when read returns 0. 0 = Do NOT update the GPIO Clock Direction Value bit on a write (default). 1 = Update the GPIO Clock Direction Value bit. on a write operation to this register. AccessType: Write Only

14.10.17 GPIOCTL_1—Offset 5014h

GPIO Control Registers GPIO I2C register (gmbus_register.v reg_gpio0, reg_gpio1, reg_gpio2, reg_gpio3, reg_gpio4)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 5014h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000808h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
RESERVED																												GPIO_DATA_IN_RO							
																												GPIO_DATA_VALUE_R_W							
																												GPIO_DATA_MASK_WO							
																												GPIO_DATA_DIRECTION_VALUE_R_W							
																												GPIO_DATA_DIRECTION_MASK_WO							
RESERVED_1																												GPIO_CLOCK_DATA_IN_RO							
																												GPIO_CLOCK_DATA_VALUE_R_W							
																												GPIO_CLOCK_DATA_MASK_WO							
																												GPIO_CLOCK_DIRECTION_VALUE_R_W							
																												GPIO_CLOCK_DIRECTION_MASK_WO							

Bit Range	Default & Access	Field Name (ID): Description
31:13	0b RW	RESERVED: Reserved.
12	0b RO	GPIO_DATA_IN_RO: This is the value that is sampled on the GPIO_Data pin as an input. This input is synchronized to the Core Clock domain. Because the default setting is this buffer is an input, this bit is undefined at reset. AccessType: Read Only
11	1b RW	GPIO_DATA_VALUE_R_W: This is the value that should be place on the GPIO Data pin as an output. This value is only written into the register if GPIO DATA MASK is also asserted. The value will appear on the pin if this data value is actually written to this register and the GPIO Data DIRECTION VALUE contains a value that will configure the pin as an output. Default = 1. The GPIO default clock data value is programmed to 1 in hardware. The hardware drives a default of 1 since the I2C interface defaults to a 1 . (this mimics the I2C external pull-ups on the bus)



Bit Range	Default & Access	Field Name (ID): Description
10	0b WO	GPIO_DATA_MASK_WO: This is a mask bit to determine whether the GPIO DATA VALUE bit should be written into the register. This value is not stored and when read returns 0. 0 = Do NOT write GPIO Data Value bit (default). 1 = Write GPIO Data Value bit. AccessType: Write Only
9	0b RW	GPIO_DATA_DIRECTION_VALUE_R_W: This is the value that should be used to define the output enable of the GPIO Data pin. This value is only written into the register if GPIO Data DIRECTION MASK is also asserted. The value that will appear on the pin is defined by what is in the register for the GPIO DATA VALUE bit. 0 = Pin is configured as an input (default) 1 = Pin is configured as an output.
8	0b WO	GPIO_DATA_DIRECTION_MASK_WO: This is a mask bit to determine whether the GPIO DIRECTION VALUE bit should be written into the register. This value is not stored and when read always returns 0. 0 = Do NOT write GPIO Data Direction Value bit (default). 1 = Write GPIO Data Direction Value bit. AccessType: Write Only
7:5	0b RW	RESERVED_1: must be written with zeros.
4	0b RO	GPIO_CLOCK_DATA_IN_RO: This is the value that is sampled on the GPIO Clock pin as an input. This input is synchronized to the Core Clock domain. Because the default setting is this buffer is an input, this bit is undefined at reset. AccessType: Read Only
3	1b RW	GPIO_CLOCK_DATA_VALUE_R_W: This is the value that should be place on the GPIO Clk pin as an output. This value is only written into the register if GPIO Clock DATA MASK is also asserted. The value will appear on the pin if this data value is actually written to this register and the GPIO Clock DIRECTION VALUE contains a value that will configure the pin as an output. Default = 1. The GPIO default clock data value is programmed to 1 in hardware. The hardware drives a default of 1 since the I2C interface defaults to a 1 . (this mimics the I2C external pull-ups on the bus)
2	0b WO	GPIO_CLOCK_DATA_MASK_WO: This is a mask bit to determine whether the GPIO Clock DATA VALUE bit should be written into the register. This value is not stored and when read always returns 0. 0 = Do NOT write GPIO Clock Data Value bit (default). 1 = Write GPIO Clock Data Value bit. AccessType: Write Only
1	0b RW	GPIO_CLOCK_DIRECTION_VALUE_R_W: This is the value that should be used to define the output enable of the GPIO Clock pin. This value is only written into the register if GPIO Clock DIRECTION MASK is also asserted. The value that will appear on the pin is defined by what is in the register for the GPIO Clock DATA VALUE bit. 0 = Pin is configured as an input and the output driver is set to tri-state (default) 1 = Pin is configured as an output.
0	0b WO	GPIO_CLOCK_DIRECTION_MASK_WO: This is a mask bit to determine whether the GPIO Clock DIRECTION VALUE bit should be written into the register. This value is not stored and when read returns 0. 0 = Do NOT update the GPIO Clock Direction Value bit on a write (default). 1 = Update the GPIO Clock Direction Value bit. on a write operation to this register. AccessType: Write Only



Bit Range	Default & Access	Field Name (ID): Description
9	0b RW	GPIO_DATA_DIRECTION_VALUE_R_W: This is the value that should be used to define the output enable of the GPIO Data pin. This value is only written into the register if GPIO Data DIRECTION MASK is also asserted. The value that will appear on the pin is defined by what is in the register for the GPIO DATA VALUE bit. 0 = Pin is configured as an input (default) 1 = Pin is configured as an output.
8	0b WO	GPIO_DATA_DIRECTION_MASK_WO: This is a mask bit to determine whether the GPIO DIRECTION VALUE bit should be written into the register. This value is not stored and when read always returns 0. 0 = Do NOT write GPIO Data Direction Value bit (default). 1 = Write GPIO Data Direction Value bit. AccessType: Write Only
7:5	0b RW	RESERVED_1: must be written with zeros.
4	0b RO	GPIO_CLOCK_DATA_IN_RO: This is the value that is sampled on the GPIO Clock pin as an input. This input is synchronized to the Core Clock domain. Because the default setting is this buffer is an input, this bit is undefined at reset. AccessType: Read Only
3	1b RW	GPIO_CLOCK_DATA_VALUE_R_W: This is the value that should be place on the GPIO Clk pin as an output. This value is only written into the register if GPIO Clock DATA MASK is also asserted. The value will appear on the pin if this data value is actually written to this register and the GPIO Clock DIRECTION VALUE contains a value that will configure the pin as an output. Default = 1. The GPIO default clock data value is programmed to 1 in hardware. The hardware drives a default of 1 since the I2C interface defaults to a 1 . (this mimics the I2C external pull-ups on the bus)
2	0b WO	GPIO_CLOCK_DATA_MASK_WO: This is a mask bit to determine whether the GPIO Clock DATA VALUE bit should be written into the register. This value is not stored and when read always returns 0. 0 = Do NOT write GPIO Clock Data Value bit (default). 1 = Write GPIO Clock Data Value bit. AccessType: Write Only
1	0b RW	GPIO_CLOCK_DIRECTION_VALUE_R_W: This is the value that should be used to define the output enable of the GPIO Clock pin. This value is only written into the register if GPIO Clock DIRECTION MASK is also asserted. The value that will appear on the pin is defined by what is in the register for the GPIO Clock DATA VALUE bit. 0 = Pin is configured as an input and the output driver is set to tri-state (default) 1 = Pin is configured as an output.
0	0b WO	GPIO_CLOCK_DIRECTION_MASK_WO: This is a mask bit to determine whether the GPIO Clock DIRECTION VALUE bit should be written into the register. This value is not stored and when read returns 0. 0 = Do NOT update the GPIO Clock Direction Value bit on a write (default). 1 = Update the GPIO Clock Direction Value bit. on a write operation to this register. AccessType: Write Only

14.10.19 GPIOCTL_3—Offset 501Ch

GPIO Control Registers GPIO I2C register (gmbus_register.v reg_gpio0, reg_gpio1, reg_gpio2, reg_gpio3, reg_gpio4)

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 501Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000808h



Intel Atom® Processor E3800 Product Family
Datasheet
473



Bit Range	Default & Access	Field Name (ID): Description
3	1b RW	GPIO_CLOCK_DATA_VALUE_R_W: This is the value that should be place on the GPIO Clk pin as an output. This value is only written into the register if GPIO Clock DATA MASK is also asserted. The value will appear on the pin if this data value is actually written to this register and the GPIO Clock DIRECTION VALUE contains a value that will configure the pin as an output. Default = 1. The GPIO default clock data value is programmed to 1 in hardware. The hardware drives a default of 1 since the I2C interface defaults to a 1 . (this mimics the I2C external pull-ups on the bus)
2	0b WO	GPIO_CLOCK_DATA_MASK_WO: This is a mask bit to determine whether the GPIO Clock DATA VALUE bit should be written into the register. This value is not stored and when read always returns 0. 0 = Do NOT write GPIO Clock Data Value bit (default). 1 = Write GPIO Clock Data Value bit. AccessType: Write Only
1	0b RW	GPIO_CLOCK_DIRECTION_VALUE_R_W: This is the value that should be used to define the output enable of the GPIO Clock pin. This value is only written into the register if GPIO Clock DIRECTION MASK is also asserted. The value that will appear on the pin is defined by what is in the register for the GPIO Clock DATA VALUE bit. 0 = Pin is configured as an input and the output driver is set to tri-state (default) 1 = Pin is configured as an output.
0	0b WO	GPIO_CLOCK_DIRECTION_MASK_WO: This is a mask bit to determine whether the GPIO Clock DIRECTION VALUE bit should be written into the register. This value is not stored and when read returns 0. 0 = Do NOT update the GPIO Clock Direction Value bit on a write (default). 1 = Update the GPIO Clock Direction Value bit. on a write operation to this register. AccessType: Write Only

14.10.20 GPIOCTL_4—Offset 5020h

GPIO Control Registers GPIO I2C register (gmbus_register.v reg_gpio0, reg_gpio1, reg_gpio2. reg_gpio3, reg_gpio4)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 5020h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000808h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED						GPIO_DATA_IN_RO	GPIO_CLOCK_DATA_IN_RO	
						GPIO_DATA_VALUE_R_W	GPIO_CLOCK_DATA_VALUE_R_W	
						GPIO_DATA_MASK_WO	GPIO_CLOCK_DATA_MASK_WO	
						GPIO_DATA_DIRECTION_VALUE_R_W	GPIO_CLOCK_DIRECTION_VALUE_R_W	
						GPIO_DATA_DIRECTION_MASK_WO	GPIO_CLOCK_DIRECTION_MASK_WO	
						RESERVED_1		



Bit Range	Default & Access	Field Name (ID): Description
31:13	0b RW	RESERVED: Reserved.
12	0b RO	GPIO_DATA_IN_RO: This is the value that is sampled on the GPIO_Data pin as an input. This input is synchronized to the Core Clock domain. Because the default setting is this buffer is an input, this bit is undefined at reset. AccessType: Read Only
11	1b RW	GPIO_DATA_VALUE_R_W: This is the value that should be place on the GPIO Data pin as an output. This value is only written into the register if GPIO DATA MASK is also asserted. The value will appear on the pin if this data value is actually written to this register and the GPIO Data DIRECTION VALUE contains a value that will configure the pin as an output. Default = 1. The GPIO default clock data value is programmed to 1 in hardware. The hardware drives a default of 1 since the I2C interface defaults to a 1 . (this mimics the I2C external pull-ups on the bus)
10	0b WO	GPIO_DATA_MASK_WO: This is a mask bit to determine whether the GPIO DATA VALUE bit should be written into the register. This value is not stored and when read returns 0. 0 = Do NOT write GPIO Data Value bit (default). 1 = Write GPIO Data Value bit. AccessType: Write Only
9	0b RW	GPIO_DATA_DIRECTION_VALUE_R_W: This is the value that should be used to define the output enable of the GPIO Data pin. This value is only written into the register if GPIO Data DIRECTION MASK is also asserted. The value that will appear on the pin is defined by what is in the register for the GPIO DATA VALUE bit. 0 = Pin is configured as an input (default) 1 = Pin is configured as an output.
8	0b WO	GPIO_DATA_DIRECTION_MASK_WO: This is a mask bit to determine whether the GPIO DIRECTION VALUE bit should be written into the register. This value is not stored and when read always returns 0. 0 = Do NOT write GPIO Data Direction Value bit (default). 1 = Write GPIO Data Direction Value bit. AccessType: Write Only
7:5	0b RW	RESERVED_1: must be written with zeros.
4	0b RO	GPIO_CLOCK_DATA_IN_RO: This is the value that is sampled on the GPIO Clock pin as an input. This input is synchronized to the Core Clock domain. Because the default setting is this buffer is an input, this bit is undefined at reset. AccessType: Read Only
3	1b RW	GPIO_CLOCK_DATA_VALUE_R_W: This is the value that should be place on the GPIO Clk pin as an output. This value is only written into the register if GPIO Clock DATA MASK is also asserted. The value will appear on the pin if this data value is actually written to this register and the GPIO Clock DIRECTION VALUE contains a value that will configure the pin as an output. Default = 1. The GPIO default clock data value is programmed to 1 in hardware. The hardware drives a default of 1 since the I2C interface defaults to a 1 . (this mimics the I2C external pull-ups on the bus)
2	0b WO	GPIO_CLOCK_DATA_MASK_WO: This is a mask bit to determine whether the GPIO Clock DATA VALUE bit should be written into the register. This value is not stored and when read always returns 0. 0 = Do NOT write GPIO Clock Data Value bit (default). 1 = Write GPIO Clock Data Value bit. AccessType: Write Only
1	0b RW	GPIO_CLOCK_DIRECTION_VALUE_R_W: This is the value that should be used to define the output enable of the GPIO Clock pin. This value is only written into the register if GPIO Clock DIRECTION MASK is also asserted. The value that will appear on the pin is defined by what is in the register for the GPIO Clock DATA VALUE bit. 0 = Pin is configured as an input and the output driver is set to tri-state (default) 1 = Pin is configured as an output.



Bit Range	Default & Access	Field Name (ID): Description
0	0b WO	GPIO_CLOCK_DIRECTION_MASK_WO: This is a mask bit to determine whether the GPIO Clock DIRECTION VALUE bit should be written into the register. This value is not stored and when read returns 0. 0 = Do NOT update the GPIO Clock Direction Value bit on a write (default). 1 = Update the GPIO Clock Direction Value bit. on a write operation to this register. AccessType: Write Only

14.10.21 GMBUS0—Offset 5100h

GMBUS Clock/Port Select gmbus clock and port select (gmbus_register.v reg_gmbus0)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 5100h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0							
0				0				0				0				0				0				0				0				0							
RESERVED																HOLD_TIME_EXTENSION				RESERVED_1				AKSV_BUFFER_SELECT				GMBUS_RATE_SELECT				RESERVED_2				PIN_PAIR_SELECT			

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	RESERVED: Reserved.
15	0b RW	HOLD_TIME_EXTENSION: This bit selects the hold time on the data line driven from the GMCH. 0 = Hold time of 0ns 1 = Hold time of 300 ns
14:12	0b RW	RESERVED_1: Reserved.
11	0b RW	AKSV_BUFFER_SELECT: [DevBLC, DevCTG, DevCDV] This bit selects whether the data to be written over GMBUS comes from the Aksv buffer for HDCP authentication, or from the GMBUS data buffer. Please note that when writing data from the Aksv buffer, all GMBUS protocol must be followed, including indicating the number of bytes to be transferred during the DATA phase of a GMBUS cycle. 0 (Default) Use the GMBUS data buffer (GMBUS3) for data transmission 1 Use the Aksv data buffer (GMBUS6 and GMBUS7) for data transmission. [DevBW, DevCL] Reserved:



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	SOFTWARE_CLEAR_INTERRUPT_SW_CLR_INT: This bit must be clear for normal operation. Setting the bit, then clearing it acts as local reset to the GMBUS controller. This bit is commonly used by software to clear a BUS_ERROR when a slave device delivers a NACK. 0 = If this bit is written as a zero when its current state is a one, will clear the HW_RDY bit and allows register writes to be accepted to the GMBUS registers (Write Protect Off). This bit is cleared to zero when an event causes the HW_RDY bit transition to occur. 1 = Asserted by software after servicing the GMBUS interrupt. Setting this bit causes the INT status bit to be cleared. Setting (1) this bit also asserts the HW_RDY bit (until this bit is written with a 0). When this bit is set, no writes to GMBUS registers will cause the contents to change with the exception of this bit which can be written.
30	0b RW	SOFTWARE_READY_SW_RDY: Data handshake bit used in conjunction with HW_RDY bit. 0 = De-asserted via the assertion event for HW_RDY bit 1 = When asserted by software, results in de-assertion of HW_RDY bit
29	0b RW	ENABLE_TIMEOUT_ENT: Enables timeout for slave response. When this bit is enabled and the slave device response has exceeded the timeout period, the GMBUS Slave Stall Timeout Error interrupt bit is set. 0 = disable timeout counter 1 = enable timeout counter
28	0b RW	RESERVED: Reserved.
27:25	0b RW	BUS_CYCLE_SELECT: 000 = No GMBUS cycle is generated. 001 = GMBUS cycle is generated without an INDEX, with no STOP, and ends with a WAIT 010 = Reserved 011 = GMBUS cycle is generated with an INDEX, with no STOP, and ends with a WAIT 100 = Generates a STOP if currently in a WAIT or after the completion of the current byte if active. 101 = GMBUS cycle is generated without an INDEX and with a STOP 110 = Reserved 111 = GMBUS cycle is generated with an INDEX and with a STOP GMBUS cycle will always consist of a START followed by Slave Address, followed by an optional read or write data phase. A read cycle with an index will consist of a START followed by a Slave Address a WRITE indication and the INDEX and then a RESTART with a Slave Address and an optional read data phase. The GMBUS cycle will terminate either with a STOP or by entering a wait state. The WAIT state is exited by generating a STOP or by starting another GMBUS cycle. This can only cause a STOP to be generated if a GMBUS cycle is generated, the GMBUS is currently in a data phase, or it is in a WAIT phase: Note that the three bits can be decoded as follows: 27 = STOP generated 26 = INDEX used 25 = cycle ends in a WAIT
24:16	0b RW	TOTAL_BYTE_COUNT: (9-bits). This determines the total number of bytes to be transferred during the DATA phase of a GMBUS cycle. The DATA phase can be prematurely terminated by generating a STOP while in the DATA phase (see Bus Cycle Select). Do not change the value of this field during GMBUS cycles transactions.
15:8	0b RW	_8_BIT_GMBUS_SLAVE_REGISTER_INDEX_INDEX: This field specifies the 8-bits of index to be used for the generated bus write transaction or the index used for the WRITE portion of the WRITE/READ pair. It only has an effect if the enable Index bit is set. Do not change this field during a GMBUS transaction.



Bit Range	Default & Access	Field Name (ID): Description
7:1	0b RW	_7_BIT_GMBUS_SLAVE_ADDRESS_SADDR: When a GMBUS cycle is to be generated using the Bus Cycle Select field, this field specifies the value of the slave address that is to be sent out. For use with 10-bit slave address devices, set this value to 11110XXb (where the last two bits (xx) are the two MSBs of the 10-bit address) and the slave direction bit to a write. This is followed by the first data byte being the 8 LSBs of the 10-bit slave address. Special Slave Addresses 0000 000R = General Call Address 0000 000W = Start byte 0000 001x = CBUS Address 0000 010x = Reserved 0000 011x = Reserved 0000 1xxx = Reserved 1111 1xxx = Reserved 1111 0xxx = 10-Bit addressing
0	0b RW	SLAVE_DIRECTION_BIT: When a GMBUS cycle is to be generated based on the Bus Cycle Select, this bit determines if the operation will be a read or a write. A read operation with the index enabled will perform a write with just the index followed by a re-start and a read. 1 = Indicates that a Read from the slave device operation is to be performed. 0 = Indicates that a Write to slave device operation is to be performed.

14.10.23 GMBUS2—Offset 5108h

GMBUS Status Register gmbus status (gmbus_register.v reg_gmbus2)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 5108h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000800h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
		RESERVED			INUSE			
					HARDWARE_WAIT_PHASE_HW_WAIT_PHASE_READ_ONLY			
					SLAVE_STALL_TIMEOUT_ERROR_READ_ONLY			
					GMBUS_INTERRUPT_STATUS_READ_ONLY			
					HARDWARE_READY_HW_RDY_READ_ONLY			
					NAK_INDICATOR_READ_ONLY			
					GMBUS_ACTIVE_GA_READ_ONLY			
							CURRENT_BYTE_COUNT_READ_ONLY	

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	RESERVED: Reserved.
15	0b RW/1C	INUSE: 0 = read operation that contains a zero in this bit position indicates that the GMBUS engine is now acquired and the subsequent reads of this register will now have this bit set. Writing a 0 to this bit has no effect. 1 = read operation that contains a one for this bit indicates that the GMBUS is currently allocated to someone else and In use . Once set, a write of a 1 to this bit indicates that the software has relinquished the GMBUS resource and will reset the value of this bit to a 0. Software wishing to arbitrate for the GMBUS resource can poll this bit until it reads a zero and will then own usage of the GMBUS controller. This bit has no effect on the hardware, and is only used as semaphore among various independent software threads that don t know how to synchronize their use of this resource that may need to use the GMBUS logic. Writing a one to this bit is software s indication that the software use of this resource is now terminated and it is available for other clients. AccessType: One to clear
14	0b RO	HARDWARE_WAIT_PHASE_HW_WAIT_PHASE_READ_ONLY: 0 = The GMBUS engine is not in a wait phase. 1 = Set when GMBUS engine is in wait phase. Wait phase is entered at the end of the current transaction when that transaction is selected not to terminate with a STOP. Once in a WAIT_PHASE, the software can now choose to generate a STOP cycle or a repeated start (RESTART) cycle followed by another GMBUS transaction on the GMBUS. AccessType: Read Only
13	0b RO	SLAVE_STALL_TIMEOUT_ERROR_READ_ONLY: This bit indicates that a slave stall timeout has occurred. It is tied to the Enable Timeout (ENT) bit. 0 = No slave timeout has occurred. 1 = A slave acknowledge timeout has occurred AccessType: Read Only



Bit Range	Default & Access	Field Name (ID): Description
12	0b RO	GMBUS_INTERRUPT_STATUS_READ_ONLY: This bit indicates that an event that causes a GMBUS interrupt has occurred. 0 = The conditions that could cause a GMBUS interrupt have not occurred or this bit has been cleared by software assertion of the SW_CLR_INT bit. 1 = GMBUS interrupt event occurred. This interrupt must have been one of the types enabled in the GMBUS4 register. [DevCDV, DevCTG]: Reserved AccessType: Read Only
11	1b RO	HARDWARE_READY_HW_RDY_READ_ONLY: This provides a method of detecting when the current software client routine can proceed with the next step in a sequence of GMBUS operations. This data handshake bit is used in conjunction with the SW_RDY bit. When this bit is changed to asserted by the GMBUS controller, it results in the de-assertion of the SW_RDY bit. 0 = Condition required for assertion has not occurred or when this bit was a one and: SW_RDY bit has been asserted. During a GMBUS read transaction, after the each read of the data register. During a GMBUS write transaction, after each write of the data register. SW_CLR_INT bit has been cleared. 1 = This bit is asserted under the following conditions: After a reset or when the transaction is aborted by the setting of the SW_CLR_INT bit. When an active GMBUS cycle has terminated with a STOP. When during a GMBUS write transaction, the data register needs and can accept another four bytes of data. During a GMBUS read transaction, this bit is asserted when the data register has four bytes of new data or the read transaction DATA phase is complete and the data register contains the last few bytes of the read data. This bit resumes to normal operation when the SW_CLR_INT bit is written to a 0. AccessType: Read Only
10	0b RO	NAK_INDICATOR_READ_ONLY: Was previously called Slave Acknowledge Timeout Error SATOER. 0 = No bus error has been detected or SW_CLR_INT has been written as a zero since the last bus error. 1 = Set by hardware if any expected device acknowledge is not received from the slave within the timeout. AccessType: Read Only
9	0b RO	GMBUS_ACTIVE_GA_READ_ONLY: This is a status bit that indicates whether the GMBUS controller is in an IDLE state or not. 0 = The GMBUS controller is currently IDLE. 1 = This indicates that the bus is in START, ADDRESS, INDEX, DATA, WAIT, or STOP Phase. Set when GMBUS hardware is not IDLE. AccessType: Read Only
8:0	0b RO	CURRENT_BYTE_COUNT_READ_ONLY: Can be used to determine the number of bytes currently transmitted/received by the GMBUS controller hardware. Set to zero at the start of a GMBUS transaction data transfer and incremented after the completion of each byte of the data phase. Note that because reads have internal storage, the byte count on a read operation may be ahead of the data that has been accepted from the data register. AccessType: Read Only

14.10.24 GMBUS3—Offset 510Ch

GMBUS Data Buffer gmbus data buffer (gmbus_register.v reg_gmbus3)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 510Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	DATA_BYTE_3: gmbus data buffer DATA Byte 3
23:16	0b RW	DATA_BYTE_2: gmbus data buffer DATA Byte 2
15:8	0b RW	DATA_BYTE_1: gmbus data buffer DATA Byte 1
7:0	0b RW	DATA_BYTE_0: gmbus data buffer DATA Byte 0

14.10.25 GMBUS4—Offset 5110h

GMBUS Interrupt Mask gmbus interrupt mask (gmbus_register.v reg_gmbus4)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 5110h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:5	0b RW	RESERVED: Reserved.



14.10.27 GMBUS6—Offset 5130h

GMBUS Aksv Buffer Low [DevBLC, DevCTG, DevCDV] gmbus data buffer
(gmbus_register.v reg_gmbus6)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 5130h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DATA_BYTE_3	DATA_BYTE_2	DATA_BYTE_1	DATA_BYTE_0					

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b WO	DATA_BYTE_3: gmbus data buffer DATA Byte 3
23:16	0b WO	DATA_BYTE_2: gmbus data buffer DATA Byte 2
15:8	0b WO	DATA_BYTE_1: gmbus data buffer DATA Byte 1
7:0	0b WO	DATA_BYTE_0: gmbus data buffer DATA Byte 0

14.10.28 GMBUS7—Offset 5134h

GMBUS Aksv Buffer High [DevBLC, DevCTG, DevCDV] gmbus data buffer
(gmbus_register.v reg_gmbus7)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 5134h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED						AKSV_SELECTION_BIT	DATA_BYTE_5	

Bit Range	Default & Access	Field Name (ID): Description
31:9	0b WO	RESERVED: MBZ
8	0b WO	AKSV_SELECTION_BIT: [DevVLVP]: 0 = The fuse value of the Aksv is used. 1 = The register value of the Aksv is used. Aksv Selection Bit [DevELK, DevCDV]: 0 = The register value of the Aksv is used. 1 = The fuse value of the Aksv is used. [DevBLC, DevCTG] Reserved
7:0	0b WO	DATA_BYTE_5: gmbus data buffer DATA Byte 5

14.10.29 DPLLA_CTRL—Offset 6014h

DPLL A Control Register DPLL A Control (cpdmmreg.v reg03_lt)

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6014h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00002000h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
25:24	0b RW	RESERVED: [DevCDV, DevVLVP] FPA0/FPA1 P2 Clock Divide: 00 = Divide by 10. This is used when Dot Clock =(270MHz in sDVO, HDMI, or DAC modes 01 = Divide by 5. This is used when Dot Clock)270MHz 10 = Reserved 11 = Reserved For DPLLA in LVDS mode, BITS(27:26)=10 00 = Divide by 14. This is used in Single-Channel LVDS 01 = Divide by 7. This is used in Dual-Channel LVDS 10 = Reserved 11 = Reserved
23:16	0b RW	RESERVED_1: [DevCDV, DevVLVP] FPA0/ FPA1 P1 Post Divisor: Writes to this byte cause the staging register contents to be written into the active register when in the VGA mode of operation. This will also occur when the VGA MSR register is written. 00000001b = Divide by one 00000010b = Divide by two 00000100b = Divide by three 00001000b = Divide by four 00010000b = Divide by five 00100000b = Divide by six 01000000b = Divide by seven 10000000b = Divide by Eight All other values are illegal and should not be used
15	0b RW	RESERVED_2: Write as zero PLLA Lock [DevCDV, DevVLVP] (RO) 1 - PLLA Lock 0 PLLA unlock
14	0b RW	VCC_VOLTAGE_SELECT: [DevVLVP] This control selects the VCC voltage in DPLL 0 = 1.0 V (default) 1 = voltage for LDO circuit (for TNG use) [DevCDV] Reserved
13	1b RW	DPLL_A_REFERENCE_INPUT_SELECT: [DevVLVP] This control selects the integrated core refclk or external OSC refclk as the input clock source to DPLL A. 0 = External refclk pad (27MHz) 1 = Integrated core refclk (default is 100 MHz) [DevCDV] Reserved PLL Reference Input Select: The PLL reference should be selected based on the display device that is being driven. The standard reference clock is used for CRT modes using the analog display port or LCD panels for both the sDVO connected transmitter or the integrated LVDS. TV Clock in should be selected when driving an sDVO connected TV encoder.



Bit Range	Default & Access	Field Name (ID): Description
12:9	0b RW	RESERVED_3: [DevCDV, DevVLVP] Parallel to Serial Load Pulse phase selection: Programmable select bits to choose the relative phase of the high speed (10X) DPLL clock used for generating the parallel to serial load pulse for digital display port on PCIe. The relative phase is the number of flop delays (phase 0 represents 1 flop delay) of the 1X parallel data synchronization signal in the 10X clock domain. The earliest selectable clock phase is 4. A phase selection of 10 or greater simply extends the flop delay count to sample delayed data. 0100 = use clock phase-4 0101 = use clock phase-5 0110 = use clock phase-6 (Default value) 0111 = use clock phase-7 1000 = use clock phase-8 1001 = use clock phase-9 1010 = use clock phase-10 1011 = use clock phase-11 1100 = use clock phase-12 1101 = use clock phase-13 Phases 0 through 3 are not available for Load Pulse selection. [DevCL] The following programming is recommended for Crestline based on PV timing analysis: 1101 use clock phase-13 [DevBLC, DevCTG] Reserved. Programming for load pulse is in PXP AFE config space.
8	0b RW	DISPLAY_RATE_SWITCH_PIPEA: [DevCTG, DevCDV, DevVLVP] Switching this bit (transition 0 to 1 or 1 to 0) causes the DSP HW to disable and then enable the DPLL during vblank (2 row) in order to switch the frequency at the DPLL (new dividers stored at the DPIO which is double buffered) (This bit is only available when bits 17:16 of the PIPEACONF register are 00) [DevBW, DevCL, DevBLC] Reserved
7:0	0b RO	DPIO_PHYSTATUS_READ_ONLY: [DevVLVP] This field contains the two 4-bit ModPhy lane status. One for PortB and one for PortC Bit 7:4 = Port C PhyStatus[3:0] Bit 3:0 = Port B PhyStatus[3:0] [DevBW, DevCL, DevBLC, DevCDV] Reserved [DevCTG] FPA1 P1 Post Divisor: Writes to this byte cause the staging register contents to be written into the active register when in the VGA mode of operation. This will also occur when the VGA MSR register is written. 00000001b - Divide by one 00000010b - Divide by two 00000100b - Divide by three 00001000b - Divide by four 00010000b - Divide by five 00100000b - Divide by six 01000000b - Divide by seven 10000000b - Divide by Eight All other values are illegal and should not be used AccessType: Read Only

14.10.30 DPLLB_CTRL—Offset 6018h

DPLL B Control Registers DPLL B Control (cpdmmreg.v reg04_It)

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6018h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00006000h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
27:26	0b RW	ENABLE_SINGLE_DPLL_B_FREQUENCY_FOR_BOTH_PIPES: [DevVLVP] When two pipes are enabled for eDP and both pipes can run with the same DP frequency either 162MHz or 270MHz. Setting this mode can allow using only DPLL_B to feed both pipes. DPLL_A should be shutdown to save power. 00 = Disabled 01 = Enabled 10 = Reserved 11 = Reserved [DevCDV] Reserved DPLL_B Mode Select : Configure the DPLL_B for various supported Display Modes 00 = Reserved 01 = DPLL_A in DAC/Serial DVO/UDI/Integrated TV mode 10 = DPLL_A in LVDS mode (Mobile devices ONLY) otherwise RESERVED 11 = DP
25:24	0b RW	RESERVED: [DevCDV, DevVLVP] FPB0/FPB1 P2 Clock Divide: 00 = Divide by 10. This is used when Dot Clock =(270MHz in sDVO, HDMI, or DAC modes 01 = Divide by 5. This is used when Dot Clock)270MHz 10 = Reserved 11 = Reserved For DPLL_B in LVDS mode, BITS(27:26)=10 00 = Divide by 14. This is used in Single-Channel LVDS 01 = Divide by 7. This is used in Dual-Channel LVDS 10 = Reserved 11 = Reserved
23:16	0b RW	RESERVED_1: [DevCDV, DevVLVP] FPB0/ FPB1 P1 Post Divisor: Writes to this byte cause the staging register contents to be written into the active register when in the VGA mode of operation. This will also occur when the VGA MSR register is written. 00000001b = Divide by one 00000010b = Divide by two 00000100b = Divide by three 00001000b = Divide by four 00010000b = Divide by five 00100000b = Divide by six 01000000b = Divide by seven 10000000b = Divide by Eight All other values are illegal and should not be used
15	0b RW	RESERVED_2: Write as zero PLL_B Lock [DevCDV, DevVLVP] (RO) 1 - PLL_B Lock 0 PLL_B unlock
14	1b RW	DPIO_COMMON_REGISTER_INTERFACE_CLOCK_SELECT_CRICKSEL: [DevVLVP] This bit is to control the clock source for DPIO Common Register Interface 0 = Use external reclk pad 1 = Use integrated core refclk (default)
13	1b RW	DPLL_B_REFERENCE_INPUT_SELECT: [DevVLVP] This control selects the integrated core refclk or external OSC refclk as the input clock source to DPLL_B. 0 = External refclk pad (27MHz) 1 = Integrated core refclk (default is 100 MHz) [DevCDV] Reserved PLL Reference Input Select: The PLL reference should be selected based on the display device that is being driven. The standard reference clock is used for CRT modes using the analog display port or LCD panels for both the sDVO connected transmitter or the integrated LVDS. TV Clock in should be selected when driving an sDVO connected TV encoder.



Bit Range	Default & Access	Field Name (ID): Description
12:9	0b RW	RESERVED_3: [DevCDV, DevVLVP] Parallel to Serial Load Pulse phase selection: Programmable select bits to choose the relative phase of the high speed (10X) DPLL clock used for generating the parallel to serial load pulse for digital display port on PCIe. The relative phase is the number of flop delays (phase 0 represents 1 flop delay) of the 1X parallel data synchronization signal in the 10X clock domain. The earliest selectable clock phase is 4. A phase selection of 10 or greater simply extends the flop delay count to sample delayed data. 0100 = use clock phase-4 0101 = use clock phase-5 0110 = use clock phase-6 (Default value) 0111 = use clock phase-7 1000 = use clock phase-8 1001 = use clock phase-9 1010 = use clock phase-10 1011 = use clock phase-11 1100 = use clock phase-12 1101 = use clock phase-13 Phases 0 through 3 are not available for Load Pulse selection. [DevCL] The following programming is recommended for Crestline based on PV timing analysis: 1101 use clock phase-13 [DevBLC, DevCTG] Reserved. Programming for load pulse is in PXP AFE config space.
8	0b RW	DISPLAY_RATE_SWITCH_PIPEB: [DevCTG, DevCDV, DevVLVP] Switching this bit (transition 0 to 1 or 1 to 0) causes the DSP HW to disable and then enable the DPLL during vblank (2 row) in order to switch the frequency at the DPLL (new dividers stored at the DPIO which is double buffered) (This bit is only available when bits 17:16 of the PIPEACONF register are 00) [DevBW, DevCL, DevBLC] Reserved
7:0	0b RW	RESERVED_4: [DevBW, DevCL, DevBLC, DevCDV, DevVLVP] [DevCTG] FPB1 P1 Post Divisor: Writes to this byte cause the staging register contents to be written into the active register when in the VGA mode of operation. This will also occur when the VGA MSR register is written. 00000001b - Divide by one 00000010b - Divide by two 00000100b - Divide by three 00001000b - Divide by four 00010000b - Divide by five 00100000b - Divide by six 01000000b - Divide by seven 10000000b - Divide by Eight All other values are illegal and should not be used

14.10.31 DPLLAMD—Offset 601Ch

DPLL A SDVO/HDMI Multiplier/Divisor Register Pipe A multiply (cpdmmreg.v reg15_lt)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 601Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000003h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
RESERVED	DPLL_A_HDMI_DIVIDER_HI_RES	RESERVED_1	DPLL_A_HDMI_DIVIDER_VGA	RESERVED_2	DPLL_A_SDVO_HDMI_MULTIPLIER_HI_RES	RESERVED_3	DPLL_A_SDVO_HDMI_MULTIPLIER_VGA	

Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	RESERVED: Reserved.
29:24	0b RW	DPLL_A_HDMI_DIVIDER_HI_RES: When the source is high resolution, this field determines the number of pixels to be included in the multiplied packet defined by the SDVO/HDMI multiplier. For SDVO and CRT, the only valid setting is 1x. HDMI example: If the pixel clock on the display should be 180MHz and the display PLL is set to 270MHz, two pixels and one fill code must be sent over HDMI (fixed frequency mode only). Therefore, the HDMI divider should be set to 2 and the SDVO/HDMI multiplier should be set to 3, since 180 MHz (pixel clock) = 2/3*270MHz (link character clock) This divider must be set to 1x for any mode except HDMI fixed frequency mode. Value in this register = number of pixels per packet 1 Default: 0000 1 pixel per packet (Default value, must be set to 1x for any mode except HDMI fixed frequency mode) Range: 0-63 (1 pixel per packet 64 pixels per packet)
23:22	0b RW	RESERVED_1: Reserved.
21:16	0b RW	DPLL_A_HDMI_DIVIDER_VGA: When the source is VGA, these bits specify the HDMI divider. The format of this field is the same as that of the hi-res divider.
15:14	0b RW	RESERVED_2: Reserved.
13:8	0b RW	DPLL_A_SDVO_HDMI_MULTIPLIER_HI_RES: This field determines the data multiplier for sDVO and is also applied to CRT. In order to keep the clock rate to a more narrow range of rates, the multiplier is set and the Display PLL programmed to a multiple of the display mode s actual clock rate. This is unrelated to the pixel multiply that is selectable per plane. 6x and higher multipliers can only be used for HDMI mode. Value in this register = multiplication factor - 1 Default: 000000 (1X) Range: 0 63 (1X 64X)
7:6	0b RW	RESERVED_3: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
5:0	000011b RW	DPLL_A_SDVO_HDMI_MULTIPLIER_VGA: When the source is VGA, these bits specify the HDMI multiplier. The format of this field is the same as that of the hi-res multiplier. 6x and higher multipliers can only be used for HDMI mode. Value in this register = multiplication factor - 1 Default: 000011 (4X) Range: 0 63 (1X 64X)

14.10.32 DPLLBMD—Offset 6020h

DPLL B SDVO/HDMI Multiplier/Divisor Register Pipe B multiplier (cpdmmreg.v reg16_lt)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6020h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000003h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
RESERVED	DPLL_B_HDMI_DIVIDER_HI_RES	RESERVED_1	DPLL_B_HDMI_DIVIDER_VGA	RESERVED_2	DPLL_B_SDVO_HDMI_MULTIPLIER_HI_RES	RESERVED_3	DPLL_B_SDVO_HDMI_MULTIPLIER_VGA	

Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	RESERVED: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29:24	0b RW	DPLL_B_HDMI_DIVIDER_HI_RES: When the source is high resolution, this field determines the number of pixels to be included in the multiplied packet defined by the SDVO/HDMI multiplier. For SDVO and CRT, the only valid setting is 1x. HDMI example: If the pixel clock on the display should be 180MHz and the display PLL is set to 270MHz, two pixels and one fill code must be sent over HDMI (fixed frequency mode only). Therefore, the HDMI divider should be set to 2 and the SDVO/HDMI multiplier should be set to 3, since $180 \text{ MHz (pixel clock)} = 2/3 * 270 \text{ MHz (link character clock)}$ This divider must be set to 1x for any mode except HDMI fixed frequency mode. Value in this register = number of pixels per packet - 1 Default: 0000 1 pixel per packet (Default value, must be set to 1x for any mode except HDMI fixed frequency mode) Range: 0-63 (1 pixel per packet 64 pixels per packet)
23:22	0b RW	RESERVED_1: Reserved.
21:16	0b RW	DPLL_B_HDMI_DIVIDER_VGA: When the source is VGA, these bits specify the HDMI divider. The format of this field is the same as that of the hi-res divider.
15:14	0b RW	RESERVED_2: Reserved.
13:8	0b RW	DPLL_B_SDVO_HDMI_MULTIPLIER_HI_RES: This field determines the data multiplier for sDVO and is also applied to CRT. In order to keep the clock rate to a more narrow range of rates, the multiplier is set and the Display PLL programmed to a multiple of the display mode's actual clock rate. This is unrelated to the pixel multiply that is selectable per plane. 6x and higher multipliers can only be used for HDMI mode. Value in this register = multiplication factor - 1 Default: 000011 (4X) Range: 0-63 (1X-64X)
7:6	0b RW	RESERVED_3: Reserved.
5:0	000011b RW	DPLL_B_SDVO_HDMI_MULTIPLIER_VGA: When the source is VGA, these bits specify the HDMI multiplier. The format of this field is the same as that of the hi-res multiplier. 6x and higher multipliers can only be used for HDMI mode. Value in this register = multiplication factor - 1 Default: 000000 (1X) Range: 0-63 (1X-64X)

14.10.33 RAWCLK_FREQ—Offset 6024h

Rawclk Frequency

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6024h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 0000007Dh

14.10.34 D_STATE—Offset 6104h



Bit Range	Default & Access	Field Name (ID): Description
15	0b RW	RESERVED: : MBZ
14:8	0000100b RW	DPLL_MIN_POWER_DOWN: (DevCDV): This is the minimum time required the DPLL to be power down until it is allowed to turn it on again. The HW counter using HRAW clk (5nsec) and has resolution of 160nsec (SEG DPLL required time is 0.5usec)
7:4	0b RW	RESERVED_1: : MBZ
3	0b RW	DOT_CLOCK_PLL_POWER_DOWN_IN_D3: This bit determines whether the PCI Power State Powers down the Dot Clock PLLs when in D3. A 0 on this bit does not power down the DPLLs, requiring software to gate them if necessary. When this bit is a 1, the dot PLLs are powered down when in D3. The PCI power state is determined by bits 1:0 of the PCI Power Management Control/Status register.
2	0b RW	RESERVED_2: Reserved.
1	0b RW	RESERVED_3: [DevCDV] Graphics Core Clock Gating: This bit determines whether the PCI Power State gates the Graphics Core clocks when in the D3 state. A 0 on this bit does not gate the clocks, requiring software to gate them if necessary. When this bit is a 1, the graphics core clocks are gated at the outputs of the PLLs when in D3. The PCI power state is determined by bits 1:0 of the PCI Power Management Control/Status register. This register field has no use in current products.
0	0b RW	DOT_CLOCK_GATING: This bit determines whether the PCI Power State gates the Dot clocks when in the D3 state. A 0 on this bit does not gate the clocks, requiring software to gate them if necessary. When this bit is a 1, the dot clocks are gated at the outputs of the PLLs when in D3. The PCI power state is determined by bits 1:0 of the PCI Power Management Control/Status register.

14.10.35 DSPCLK_GATE_D—Offset 6200h

Clock Gating Disable for Display Register clock gating (cpdmmreg.v reg12_It)

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6200h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 10000000h



31	28	24	20	16	12	8	4	0
0	0	0	1	0	0	0	0	0
HDCPUNIT_CLOCK_GATING_DISABLE	DPUNIT_PIPEB_CLOCK_GATING_DISABLE	VSUNIT_PIPE_A_CLOCK_GATING_DISABLE	VRHUNIT_CLOCK_GATING_DISABLE	VRDUNIT_CLOCK_GATING_DISABLE	AUDUNIT_CLOCK_GATING_DISABLE	DPUNIT_PIPEA_CLOCK_GATING_DISABLE	DPCUNIT_CLOCK_GATING_DISABLE	VSUNIT_PIPE_B_CLOCK_GATING_DISABLE
								SPRITE_D_CLOCK_GATING_DISABLE
								SPRITE_C_CLOCK_GATING_DISABLE
								SPRITE_B_CLOCK_GATING_DISABLE
								DVSUNIT_SPRITE_A_CLOCK_GATING_DISABLE
								DDBUNIT_CLOCK_GATING_DISABLE
								GMBUSUNIT_CLOCK_GATING_DISABLE
								DPRUNIT_CLOCK_GATING_DISABLE
								DPFUNIT_CLOCK_GATING_DISABLE
								DPLRUNIT_PIPE_A_CLOCK_GATING_DISABLE
								DPLSUNIT_PIPE_A_CLOCK_GATING_DISABLE
								DPTUNIT_CLOCK_GATING_DISABLE
								DPOUNIT_CLOCK_GATING_DISABLE
								DCUNIT_PIPE_A_CLOCK_GATING_DISABLE
								DCUNIT_PIPE_A_CLOCK_GATING_DISABLE
								DPGCUNIT_PIPE_B_CLOCK_GATING_DISABLE
								DPGCUNIT_PIPE_A_CLOCK_GATING_DISABLE
								DPTOUTUNIT_CLOCK_GATING_DISABLE
								OVFUNIT_CLOCK_GATING_DISABLE
								OVVUNIT_CLOCK_GATING_DISABLE
								DPLRUNIT_PIPE_B_CLOCK_GATING_DISABLE
								DPLSUNIT_PIPE_B_CLOCK_GATING_DISABLE
								DPBUNIT_PIPE_B_CLOCK_GATING_DISABLE
								DCUNIT_PIPE_B_CLOCK_GATING_DISABLE

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	HDCPUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBW]: Reserved. MBZ. This bit is not connected on [DevBW].
30	0b RW	DPUNIT_PIPEB_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
29	0b RW	VSUNIT_PIPE_A_CLOCK_GATING_DISABLE: [DevVLVP] (this bit used to be in PCI space in Calistoga) 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
28	1b RW	VRHUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function Clock gating should not be enabled for this unit (this bit should always be set to 1.) [DevBW]: Reserved. MBZ. This bit is not connected on [DevBW].
27	0b RW	VRDUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
26	0b RW	AUDUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBW]: Reserved. MBZ. This bit is not connected on [DevBW].
25	0b RW	DPUNIT_PIPEA_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
24	0b RW	DPCUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
23	0b RW	VSUNIT_PIPE_B_CLOCK_GATING_DISABLE: [DevVLVP] 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBW]: Reserved. MBZ. This bit is not connected on [DevBW]. [DevCDV] and [DevVLVP]: Reserved



Bit Range	Default & Access	Field Name (ID): Description
22	0b RW	SPRITE_D_CLOCK_GATING_DISABLE: [DevVLVP] 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBW]: Reserved. MBZ. This bit is not connected on [DevBW]. [DevCDV]: Reserved
21	0b RW	SPRITE_C_CLOCK_GATING_DISABLE: [DevVLVP] 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBW]: Reserved. MBZ. This bit is not connected on [DevBW]. [DevCDV]: Reserved
20	0b RW	SPRITE_B_CLOCK_GATING_DISABLE: [DevVLVP] 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBW] and [DevBLC]: Reserved. MBZ. This bit is not connected on [DevBW] and [DevBLC]. [DevCDV]: Reserved
19	0b RW	DVSUNIT_SPRITE_A_CLOCK_GATING_DISABLE: [DevBW] and [DevCL] 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBLC] and [DevCTG]: Reserved. MBZ. This bit is not connected on [DevBLC] and [DevCTG].
18	0b RW	DDBUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevCTG] Always program this bit to 1
17	0b RW	GMBUSUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
16	0b RW	DPRUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
15	0b RW	DPFUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
14	0b RW	DPLRUNIT_PIPE_A_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBW] and [DevBLC]: Reserved. MBZ. This bit is not connected on [DevBW] and [DevBLC].
13	0b RW	DPLSUNIT_PIPE_A_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBW] and [DevBLC]: Reserved. MBZ. This bit is not connected on [DevBW] and [DevBLC].
12	0b RW	DPTUNIT_CLOCK_GATING_DISABLE: [DevVLVP] [DevCDV] Dplunit Clock Gating Disable: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBW] and [DevBLC]: Reserved. MBZ. This bit is not connected on [DevBW] and [DevBLC].
11	0b RW	DPOUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
10	0b RW	DPBUNIT_PIPE_A_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
9	0b RW	DCUNIT_PIPE_A_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function



Bit Range	Default & Access	Field Name (ID): Description
8	0b RW	DPGCUNIT_PIPE_B_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
7	0b RW	DPGCUNIT_PIPE_A_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
6	0b RW	DPIOUNIT_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
5	0b RW	OVFUNIT_CLOCK_GATING_DISABLE: [DevBW, DevCL, DevCDV] [DevCTG] DPFCunit Clock Gating Disable: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
4	0b RW	OVBUNIT_CLOCK_GATING_DISABLE: [DevBW, DevCL, DevCDV] [DevCTG] DPFDunit Clock Gating Disable: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
3	0b RW	DPLRUNIT_PIPE_B_CLOCK_GATING_DISABLE: (not in CDV)
2	0b RW	DPLSUNIT_PIPE_B_CLOCK_GATING_DISABLE: (not in CDV)
1	0b RW	DPBUNIT_PIPE_B_CLOCK_GATING_DISABLE: [DevVLVP] [DevBW, DevCL, DevCDV] Ovuunit Clock Gating Disable: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBLC] and [DevCTG]: Reserved. MBZ. This bit is not connected on [DevBLC] and [DevCTG].
0	0b RW	DCUNIT_PIPE_B_CLOCK_GATING_DISABLE: [DevVLVP] [DevBW, DevCL, DevCDV] Ovlunit Clock Gating Disable: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function [DevBLC] and [DevCTG]: Reserved. MBZ. This bit is not connected on [DevBLC] and [DevCTG].

14.10.36 DPPSR_CGDIS—Offset 6204h

Panel Self Refresh Clock Gating Disable for Display PSR clock gating disable controls (cpdmmreg.v)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6204h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000200h



31	28				24	20				16				12				8				4				0					
LOW_POWER_SINGLE_PIPE_A_LPSSA_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
LOW_POWER_SINGLE_PIPE_B_LPSSA_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
RESERVED																															
DPIO_CLOCK_BUFFER_ENABLE_CLOCK_GATING_DISABLE																															
DISPLAY_PLANE_A_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DISPLAY_PLANE_B_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
SPRITE_A_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
SPRITE_B_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
SPRITE_C_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
SPRITE_D_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
CURSOR_A_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
CURSOR_B_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DISPLAY_BLENDER_A_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DISPLAY_BLENDER_B_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DISPLAY_GAMMA_CORRECTION_A_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DISPLAY_GAMMA_CORRECTION_B_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DISPLAY_GCI_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
AUDFUNIT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
AUDBUNIT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
CPDUNIT_PSR_CLOCK_GATING_DISABLE		1		0		0		0		0		0		0		0		0		0		0		0		0		0			
DDBMUNIT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DPFUNIT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DPTOUNIT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DISPLAYPORT_DPTUNIT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DPOINT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
HDCPUNIT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
VRDUNIT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
VRHUNIT_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
DISPLAY_FUSE_WRAPPER_PSR_CLOCK_GATING_DISABLE		0		0		0		0		0		0		0		0		0		0		0		0		0		0			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	LOW_POWER_SINGLE_PIPE_A_LPSSA_CLOCK_GATING_DISABLE: 0 = clock gating controlled by enabling logic. Pipe A shall be enabled 1 = Disable trunk clock gating on pipe A even when LPSSA is on
30	0b RW	LOW_POWER_SINGLE_PIPE_B_LPSSA_CLOCK_GATING_DISABLE: 0 = clock gating controlled by enabling logic. Pipe B shall be enabled 1 = Disable trunk clock gating on pipe B even when LPSSA is on
29:26	0b RW	RESERVED: Reserved.
25	0b RW	DPIO_CLOCK_BUFFER_ENABLE_CLOCK_GATING_DISABLE: 0 = clock gating controlled by DPIO clock buffer enable 1=Disable clock gating function by DPIO clock buffer enable
24	0b RW	DISPLAY_PLANE_A_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
23	0b RW	DISPLAY_PLANE_B_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
22	0b RW	SPRITE_A_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
21	0b RW	SPRITE_B_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
20	0b RW	SPRITE_C_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function



Bit Range	Default & Access	Field Name (ID): Description
19	0b RW	SPRITE_D_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
18	0b RW	CURSOR_A_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
17	0b RW	CURSOR_B_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
16	0b RW	DISPLAY_BLENDER_A_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
15	0b RW	DISPLAY_BLENDER_B_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
14	0b RW	DISPLAY_GAMMA_CORRECTION_A_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
13	0b RW	DISPLAY_GAMMA_CORRECTION_B_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
12	0b RW	DISPLAY_GCI_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
11	0b RW	AUDFUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function(default)
10	0b RW	AUDBUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
9	1b RW	CPDUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function (default)
8	0b RW	DDBMUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
7	0b RW	DPFUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
6	0b RW	DPIOUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
5	0b RW	DISPLAYPORT_DPTUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
4	0b RW	DPOUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
3	0b RW	HDCPUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
2	0b RW	VRDUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW	VRHUNIT_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function
0	0b RW	DISPLAY_FUSE_WRAPPER_PSR_CLOCK_GATING_DISABLE: 0 = Clock gating controlled by unit enabling logic 1 = Disable clock gating function

14.10.37 RAMCLK_GATE_D—Offset 6210h

GFX RAM Clock Gating Disable Register ([DevBLC, DevCTG, DevCDV, DevCL]) memory clock gating (cpdmmreg.v gfxramcg2)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6210h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED	PANEL_FITTER_RAM_CLOCK_GATING_DISABLE	CURSOR_DATA_BUFFER_RAM_CLOCK_GATING_DISABLE	AUDM_UNIT_RAM_CLOCK_GATING_DISABLE	RESERVED_1	DISPLAY_DATA_BUFFER1_RAM_CLOCK_GATING_DISABLE	HDCP_UNIT_RAM_CLOCK_GATING_DISABLE	DPTUNIT_RAM_CLOCK_GATING_DISABLE	RESERVED_2
								RESERVED_3
								RESERVED_4
								RESERVED_5
								RESERVED_6
								RESERVED_7
								RESERVED_8
								RESERVED_9
								RESERVED_10
								RESERVED_11
								RESERVED_12
								RESERVED_13
								RESERVED_14
								RESERVED_15
								RESERVED_16
								RESERVED_17
								RESERVED_18
								RESERVED_19
								RESERVED_20
								RESERVED_21
								RESERVED_22
								RESERVED_23
								RESERVED_24
								RESERVED_25

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	RESERVED: [DevCDV] TVOUT RAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
30	0b RW	PANEL_FITTER_RAM_CLOCK_GATING_DISABLE: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function



Bit Range	Default & Access	Field Name (ID): Description
29	0b RW	CURSOR_DATA_BUFFER_RAM_CLOCK_GATING_DISABLE: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
28	0b RW	AUDM_UNIT_RAM_CLOCK_GATING_DISABLE: [DevCTG, DevCDV] [DeBLC] Reserved. [DevCL] WIZ Z coeff readback return FIFO Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
27	0b RW	RESERVED_1: [DevCDV] [DevCTG] DPFC Unit RAM Clock Gating Disable: [DeBLC] Reserved. [DevCL] Display Data Buffer2 (Overlay) Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
26	0b RW	DISPLAY_DATA_BUFFER1_RAM_CLOCK_GATING_DISABLE: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
25	0b RW	HDCP_UNIT_RAM_CLOCK_GATING_DISABLE: [DevBLC, DevCTG, DevCDV] [DevCL] ME RAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
24	0b RW	DPTUNIT_RAM_CLOCK_GATING_DISABLE: [DevVLVP] [DevCTG, DevCDV] DPIOM Unit RAM Clock Gating Disable: [DeBLC] Reserved. [DevCL] WIZ polygon FIFO RAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
23	0b RW	RESERVED_2: [DevCDV] [DevBLC] and [DevCTG] Reserved. [DevCL] VF RAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
22	0b RW	RESERVED_3: [DevCDV] [DevBLC] and [DevCTG] Reserved. [DevCL] SF RAMClock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
21	0b RW	RESERVED_4: [DevCDV] [DevBLC] and [DevCTG] Reserved. [DevCL] WMIZ Latency FIFO Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
20	0b RW	RESERVED_5: [DevCDV] [DevBLC] and [DevCTG] Reserved. [DevCL] TC FIFO Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
19	0b RW	RESERVED_6: [DevBLC, DevCTG, DevCDV] [DevCL] SV FIFO Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
18	0b RW	RESERVED_7: [DevCDV] [DevBLC] and [DevCTG] BD Unit RAM Clock Gating Disable: [DevCL] Latency FIFO Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function



Bit Range	Default & Access	Field Name (ID): Description
17	0b RW	RESERVED_8: [DevCDV] [DevBLC] and [DevCTG] BF Unit RAM Clock Gating Disable: [DevCL] URB Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
16	0b RW	RESERVED_9: [DevCDV] [DevBLC] and [DevCTG] CS Unit RAM Clock Gating Disable: [DevCL] L2 Instruction Tag RAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
15	0b RW	RESERVED_10: [DevBLC, DevCDV] [DevCTG] FH Unit RAM Clock Gating Disable: [DevCL] Data RAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
14	0b RW	RESERVED_11: [DevCDV] [DevBLC] and [DevCTG] Reserved. [DevCL] TAG RAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
13	0b RW	RESERVED_12: [DevCDV] [DevBLC] and [DevCTG] Reserved. [DevCL] L2 Instruction Cache Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
12	0b RW	RESERVED_13: [DevCDV] [DevBLC] and [DevCTG] Reserved. [DevCL] MRFRAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
11	0b RW	RESERVED_14: [DevCDV] [DevBLC] and [DevCTG] VFM Unit RAM Clock Gating Disable: [DevCL] GRF RAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
10	0b RW	RESERVED_15: [DevCDV] [DevBLC] and [DevCTG] SFM Unit RAM Clock Gating Disable: [DevCL] Data Cache CAM Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
9	0b RW	RESERVED_16: [DevCDV] [DevBLC] and [DevCTG] WIZM Unit RAM Clock Gating Disable: [DevCL] Data Cache Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
8	0b RW	RESERVED_17: [DevCDV] [DevBLC] and [DevCTG] URB Unit RAM Clock Gating Disable: [DevCL] Render Cache Latency FIFO Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
7	0b RW	RESERVED_18: [DevCDV] [DevBLC] and [DevCTG] IC Unit RAM Clock Gating Disable: [DevCL] Render PA Tag RAM (Z) Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function
6	0b RW	RESERVED_19: [DevCDV] [DevBLC] and [DevCTG] ISC Unit RAM Clock Gating Disable: [DevCL] Render PA Tag RAM (Color) Clock Gating Disable: 0 = Enable RAM bank clock gating function (default) 1 = Disable RAM bank clock gating function



Display Arbiter

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6504h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h


Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:3	0b RW	RESERVED: Reserved.
2	0b RW	DISPLAY_TRICKLE_FEED_DISABLE: 1 Disable (Turn off trickle feed Display request). 0 Enable (Default)
1:0	0b RW	RESERVED_1: Reserved.

14.10.40 CZCLK_CDCLK_FREQ_RATIO—Offset 6508h

Display CZCLK/CDCLK FREQ Ratio for RMBUS sync

Access Method



October 2018
Document Number: 538136, Rev. 4.3

Bit Range	Default & Access	Field Name (ID): Description
8:4	00111b RO	DISPLAY_CDCLK_FREQUENCY_ENCODING: DISPLAY CDCLK FREQUENCY ENCODING (* symbol frequencies are POR) =====CDCLK FREQ.===== =====CDCLK DEVIDE RATIO===== =====CD REGISTER ENCODING===== =====SKU200===== =====SKU266===== =====SKU333===== =====CD===== =====ENCODING===== ===== ===== (DECIMAL)= ===== =====VCO 800===== =====VCO 1600===== =====VCO 2000===== =====QUAL GEN= ===== ===== ===== ===== ===== ===== ===== ===== (MHz)= ===== (MHz)===== ===== (MHz)===== =====RATIO===== =====5'b00001===== =====1===== =====1===== ===== =====800===== =====1600===== =====2000===== =====1===== =====5'b00010===== =====1.5===== =====2===== ===== =====533===== =====1067===== =====1333===== =====2===== =====5'b00011===== =====2===== =====3===== ===== =====400===== =====800===== =====1000===== =====3===== =====5'b00100===== =====2.5===== =====4===== ===== =====320*===== =====640===== =====800===== =====4===== =====5'b00101===== =====3===== =====5===== ===== =====267*===== =====533===== =====667===== =====5===== =====5'b00111===== =====4===== =====6===== ===== =====200*===== =====400===== =====500===== =====7===== =====5'b01000===== =====4.5===== =====7===== ===== =====178===== =====356===== =====444===== =====8===== =====5'b01001===== =====5===== =====9===== ===== =====160===== =====320*===== =====400===== =====9===== =====5'b01011===== =====6===== =====11===== ===== =====133===== =====267*===== =====300*===== =====11===== =====5'b01110===== =====7.5===== =====14===== ===== =====107===== =====213===== =====267*===== =====14===== =====5'b01111===== =====8===== =====15===== ===== =====100===== =====200*===== =====250===== =====15===== =====5'b10001===== =====9===== =====17===== ===== =====89===== =====178===== =====222===== =====17===== =====5'b10011===== =====10===== =====19===== ===== =====80===== =====160===== =====200*===== =====19===== =====5'b10111===== =====12===== =====23===== ===== =====67===== =====133===== =====167===== =====23===== =====5'b11101===== =====15===== =====29===== ===== =====53===== =====107===== =====133===== =====29===== =====5'b11111===== =====16===== =====31===== ===== =====50===== =====100===== =====125===== =====31===== ===== ===== ===== ===== ===== =====

Bit Range	Default & Access	Field Name (ID): Description
3:0	0111b RO	CORE_CLOCK_CZCLK_FREQUENCY_ENCODING: CORE CLOCK (CZCLK) FREQUENCY ENCODING (* symbol are POR freq for each SKU) ===== =====CZCLK FREQ===== =====CZCLK DEVIDE RATIO===== =====CZ REGISTER ENCODING===== =====SKU200===== =====SKU266===== =====SKU333===== =====CZ===== =====ENCODING===== ===== (DECIMAL)= ===== =====VCO 800===== =====VCO 1600===== =====VCO 2000===== =====QUAL GEN===== ===== ===== (MHz)= ===== (MHz)= ===== (MHz)= ===== =====RATIO===== ===== =====5'b00001===== =====1===== =====1===== =====800===== =====1600===== =====2000===== =====1===== ===== =====5'b00010===== =====1.5===== =====2===== =====533===== =====1067===== =====1333===== =====2===== ===== =====5'b00011===== =====2===== =====3===== =====400===== =====800===== =====1000===== =====3===== ===== =====5'b00100===== =====2.5===== =====4===== =====320===== =====640===== =====800===== =====4===== ===== =====5'b00101===== =====3===== =====5===== =====267===== =====533===== =====667===== =====5===== ===== =====5'b00111===== =====4===== =====6===== =====200*===== =====400===== =====500===== =====7===== ===== =====5'b01000===== =====4.5===== =====7===== =====178===== =====356===== =====444===== =====8===== ===== =====5'b01001===== =====5===== =====9===== =====160===== =====320===== =====400===== =====9===== ===== =====5'b01011===== =====6===== =====11===== =====133===== =====267*===== =====333*===== =====11===== ===== =====5'b01110===== =====7.5===== =====14===== =====107===== =====213===== =====267===== =====14===== ===== =====5'b01111===== =====8===== =====15===== =====100===== =====200*===== =====250===== =====15===== ===== =====

14.10.41 GCI CONTROL—Offset 650Ch

GCI Control Register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 650Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00004000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PFI_CREDIT_INFO_TO_BE_SENT_TO_PONDICHERRY_PFI	FORCE_PFI_CREDIT_RESEND_TO_SSA	RESERVED	AES_CLK_GATING_DISABLE	RESERVED_1	VGA_FAST_MODE_DISABLE	REQUEST_LATENCY_OVERRIDE	REQUEST_LATENCY_OVERRIDE_ENABLE	AES_DECRYPTION_BYPASS_ENABLE
								FORCE_AES_SESSION_KEYS_RESEND_TO_AES_BLOCK
								HP_ARBITRATION_MODE

Bit Range	Default & Access	Field Name (ID): Description
31:28	0b RW	PFI_CREDIT_INFO_TO_BE_SENT_TO_PONDICHERRY_PFI: Others = reserved 0111 = 15 credits 0110 = 14 credits 0101 = 13 credits 0100 = 12 credits 0011 = 11 credits 0010 = 10 credits 0001 = 9 credits 0000 = 8 credits available to PND (default) Based on the czclk/cdclk ratio, display driver has to determine the appropriate PFI credits to be used
27	0b RW	FORCE PFI CREDIT RESEND TO SSA (FORCE_PFI_CREDIT_RESEND_TO_SSA): 0 = Disable PFI credit to resend to SSA. Hardware is responsible to clear this bit after the PFI credit initialization request is sent. 1 = Enable PFI credit to resend to SSA. When driver sets this bit, Display PFI request engine will resend the new PFI credit bit [31:28] to SSA. Hardware is responsible to clear this bit after the PFI credit initialization request is sent.
26:25	0b RW	RESERVED: Reserved.
24	0b RW	AES_CLK_GATING_DISABLE: 0 = Enable clock gating for AES clock (default) 1 = Disable clock gating for AES clock
23:15	0b RW	RESERVED_1: Reserved.
14	1b RW	VGA_FAST_MODE_DISABLE: 0 = Fast Mode enabled. The Gfx mem arbiter can accept a vga display read request every clock. Note that the HP Address (G_HP_CONTROL[28:24]) and ID (G_HP_CONTROL[21:16]) FIFO depths must be set to a value greater than 1 when Fast Mode is enabled. 1 = Fast Mode disabled. (default) The Gfx mem arbiter can accept a vga display read request every other clock Programming note: VGA FAST MODE is not supported in VLVP.



Bit Range	Default & Access	Field Name (ID): Description
13:4	0b RW	REQUEST_LATENCY_OVERRIDE: If bit 3 of this register is set, the 10-btt Request Latency Override value programmed here is used as the latency offset from the global timer for requests that win arbitration. If bit 3 is not set, normal request latency from streamers is used. Programming note: This value should not be larger than the actual required request latency. Otherwise, it will cause underrun. The guideline is to use latency corresponds to low watermark level or even smaller. When this field is used, the actual request latency is defeatured, either zero or a small value is used but still not causing underrun.
3	0b RW	REQUEST_LATENCY_OVERRIDE_ENABLE: 1 = Request Latency Override values in bit[13:4] is used as the latency offset from global timer 0 = Request Latency Override values is disabled. Normal request latency from streamer is used. (default)
2	0b RW	AES_DECRYPTPTION_BYPASS_ENABLE: 0 = AES decryption engine is enabled (Default) 1 = AES decryption engine is bypassed
1	0b RW	FORCE_AES_SESSION_KEYS_RESEND_TO_AES_BLOCK: 0 = Disable sending AES session keys to AES when going from Panel Self Refresh (PSR) inactive to PSR active mode (Default). Hardware is responsible to clear this bit after this bit is set to resend the session keys. 1 = Enable sending AES session keys to AES engine when going from PSR inactive to PSR active mode. When driver sets this bit, PAVP engine will resend the session keys to AES engine. Hardware is responsible to clear this bit after the session keys are sent.
0	0b RW	HP_ARBITRATION_MODE: 0 = Select hierarchical arbiter 1 = Select backup round robin arbiter

14.10.42 GMBUSFREQ—Offset 6510h

GMBUS frequency binary encoding GMBUS Frequency Binary Encoding Register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6510h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 000000A0h

31	28	24	20	16	12	8	4	0					
0	0	0	0	0	0	0	1	0	1	0	0	0	0
RESERVED										CMBUS_CDCLK_FREQUENCY_CDFREQ			



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + A800h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				PIPE_B_RED_PALETTE_ENTRY				
				PIPE_B_GREEN_PALETTE_ENTRY				
				PIPE_B_BLUE_PALETTE_ENTRY				

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Read Only.
23:16	0b RW	PIPE_B_RED_PALETTE_ENTRY: 8-bit entries per red color channel in the palette
15:8	0b RW	PIPE_B_GREEN_PALETTE_ENTRY: 8-bit entries per green color channel in the palette
7:0	0b RW	PIPE_B_BLUE_PALETTE_ENTRY: 8-bit entries per blue color channel in the palette

14.10.45 MIPIA_DEVICE_READY_REG—Offset B000h

MIPI A Device Ready Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [GTTMMADR_LSB + 180000h] + B000h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0									
RESERVED																												BUS_POSSESSION				ULPS_STATE				DEVICE_READY			



Bit Range	Default & Access	Field Name (ID): Description
27	0b RW	HS_GENERIC_WR_FIFO_FULL: Set to indicate that the HS generic write fifo is full
26	0b RW	RX_PROT_VIOLATION: Set if DSI protocol violation error is reported in the acknowledge packet by the display device
25	0b RW	RX_INVALID_TX_LENGTH: Set if invalid transmission length error is reported in the acknowledge packet by the display device
24	0b RW	ACK_WITH_NO_ERROR: Set if acknowledge trigger message is received with out any error
23	0b RW	TURN_AROUND_ACK_TIMEOUT: Set if a turn around acknowledgement sequence is not received from the display device
22	0b RW	LP_RX_TIMEOUT: Set if a low power reception count expires this interrupt is generated
21	0b RW	HS_TX_TIMEOUT: Set if a high speed transmission prevails for more than the expected count value this interrupt is raised
20	0b RW	DPI_FIFO_UNDERRUN: Set to '1' if there is no data in the dpi fifo to make a in time delivery of the pixel data to the DSI receiver
19	0b RW	LOW_CONTENTION: Set to '1' if a LP low fault is registered by at the D-PHY contention detector
18	0b RW	HIGH_CONTENTION: Set to '1' if a LP high fault is registered by at the D-PHY contention detector
17	0b RW	TXDSI_VC_ID_INVALID: Set to '1' if the received virtual channel ID is invalid
16	0b RW	TXDSI_DATA_TYPE_NOT_RECOGNISED: Set to '1' if the received data type is not recognised
15	0b RW	TXCHECKSUM_ERROR: Set to '1' if the computed CRC differs from the received CRC value during the reception of packets by Arasan_DSI host.
14	0b RW	TXECC_MULTIBIT_ERROR: Set to '1' if there is no ECC correction for the packet or there are more than 2 bit errors in the packet received by Arasan_DSI_host
13	0b RW	TXECC_SINGLE_BIT_ERROR: Set to '1' if ECC syndrome was computed and is corrected for one bit error during the reception of packets by the Arasan_DSI_host
12	0b RW	TXFALSE_CONTROL_ERROR: Set to '1' if a control error is observed on the lanes by the Arasan_DSI_host
11	0b RW	RXDSI_VC_ID_INVALID: Set to '1' if the virtual channel ID is invalid by the display device is reported in the Acknowledge packet by the display device
10	0b RW	RXDSI_DATA_TYPE_NOT_RECOGNISED: Set to '1' if the data type is not recognised by the display device is reported in the Acknowledge packet by the display device
9	0b RW	RXCHECKSUM_ERROR: Set to '1' if the computed CRC differs from the received CRC value and is reported in the Acknowledge packet by the display device
8	0b RW	RXECC_MULTIBIT_ERROR: Set to '1' if there is no ECC correction for the packet or there are more than 2 bit errors in the packet is reported in the Acknowledge packet by the display device
7	0b RW	RXECC_SINGLE_BIT_ERROR: Set to '1' if ECC syndrome was computed and corrected for one bit error is reported in the Acknowledge packet by the display device
6	0b RW	RXFALSE_CONTROL_ERROR: Set to '1' if a control error is reported in the Acknowledge packet by the display device



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	RXHS_RECEIVE_TIMEOUT_ERROR: Set to '1' if the high speed receive timer value expires and data transfer lasts on the data lane is reported in the Acknowledge packet by the display device
4	0b RW	RX_LP_TX_SYNC_ERROR: Set to '1' if Low power transmission sync error occurs in the display device and is reported in the Acknowledge packet by the display device
3	0b RW	RXESCAPE_MODE_ENTRY_ERROR: Set to '1' if Escape Mode Entry command is not understandable by the display device and is reported in the Acknowledge packet by the display device
2	0b RW	RXEOTSYNCERROR: RX eot sync Error
1	0b RW	RXSOTSYNCERROR: Set to '1' if a start of transmission synchronisation error is reported in the Acknowledge packet by the display device
0	0b RW	RXSOTERROR: Set to '1' if a start of transmission error is reported in the Acknowledge packet by the display device

14.10.47 MIPIA_INTR_EN_REG—Offset B008h

mipi pipe A interrupt enable register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B008h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	RESERVED																												0
	SPL_PKT_SENT_INTERRUPT																												0
	GEN_READ_DATA_AVAIL																												0
	LP_GENERIC_WR_FIFO_FULL																												0
28	HS_GENERIC_WR_FIFO_FULL																												0
	RX_PROT_VIOLATION																												0
	RX_INVALID_TX_LENGTH																												0
24	ACK_WITH_NO_ERROR																												0
	TURN_AROUND_ACK_TIMEOUT																												0
	LP_RX_TIMEOUT																												0
	HS_TX_TIMEOUT																												0
20	DPL_FIFO_UNDERRUN																												0
	LOW_CONTENTION																												0
	HIGH_CONTENTION																												0
	TXDSI_VC_ID_INVALID																												0
16	TXDSI_DATA_TYPE_NOT_RECOGNISED																												0
	TXCHECKSUM_ERROR																												0
	TXECC_MULTIBIT_ERROR																												0
	TXECC_SINGLE_BIT_ERROR																												0
	TXFALSE_CONTROL_ERROR																												0
12	RXDSI_VC_ID_INVALID																												0
	RXDSI_DATA_TYPE_NOT_RECOGNISED																												0
	RXCHECKSUM_ERROR																												0
8	RXECC_MULTIBIT_ERROR																												0
	RXECC_SINGLE_BIT_ERROR																												0
	RXFALSE_CONTROL_ERROR																												0
	RXHS_RECEIVE_TIMEOUT_ERROR																												0
4	RX_LP_TX_SYNC_ERROR																												0
	RXESCAPE_MODE_ENTRY_ERROR																												0
	RXEOTSYNC_ERROR																												0
	RXSOTSYNC_ERROR																												0
	RXSOT_ERROR																												0

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	TEARING_EFFECT (RESERVED): set to enable tearing effect interrupt.
30	0b RW	SPL_PKT_SENT_INTERRUPT: Set to enable the confirmation of transmission of the DPI event specific commands set in the dpi control and dpi data register



Bit Range	Default & Access	Field Name (ID): Description
29	0b RW	GEN_READ_DATA_AVAIL: Set to enable Generic Read available interrupt
28	0b RW	LP_GENERIC_WR_FIFO_FULL: Set to indicate that the LP generic write fifo is full
27	0b RW	HS_GENERIC_WR_FIFO_FULL: Set to indicate that the HS generic write fifo is full
26	0b RW	RX_PROT_VIOLATION: Set to enable protocol violation error
25	0b RW	RX_INVALID_TX_LENGTH: Set to enable invalid transmission length error
24	0b RW	ACK_WITH_NO_ERROR: Set to enable acknowledge trigger message reception with out any error
23	0b RW	TURN_AROUND_ACK_TIMEOUT: Set to enable turn around acknowledgement ,sequence timeout
22	0b RW	LP_RX_TIMEOUT: Set to enable low power reception count timeouts
21	0b RW	HS_TX_TIMEOUT: Set to enable a high speed transmission timeout
20	0b RW	DPI_FIFO_UNDERRUN: Set to enable if there is no data in the dpi fifo to make a in time delivery of the pixel data to the DSI receiver
19	0b RW	LOW_CONTENTION: Set to enable a LP low fault interrupt
18	0b RW	HIGH_CONTENTION: Set to enable a LP high fault interrupt
17	0b RW	TXDSI_VC_ID_INVALID: Set to enable the interrupt if the received packets virtual channel ID is invalid
16	0b RW	TXDSI_DATA_TYPE_NOT_RECOGNISED: Set to enable the interrupt if the received packets data type is not recognised
15	0b RW	TXCHECKSUM_ERROR: Set to enable the interrupt if the computed CRC differs from the received CRC value for the received packets
14	0b RW	TXECC_MULTIBIT_ERROR: Set to enable the interrupt if there is no ECC correction for the packet or there are more than 2 bit errors in the packet received by Arasan DSI host
13	0b RW	TXECC_SINGLE_BIT_ERROR: Set to enable the interrupt if ECC syndrome was computed and is corrected for one bit error during the reception of packets by the Arasan DSI host
12	0b RW	TXFALSE_CONTROL_ERROR: Set to enable the interrupt for the control error,observed on the lanes by the Arasan_DSI_host
11	0b RW	RXDSI_VC_ID_INVALID: Set to enable the interrupt for invalid virtual channel ID in the acknowledgment packet reports
10	0b RW	RXDSI_DATA_TYPE_NOT_RECOGNISED: Set to enable the interrupt for the un recognised data type in the acknowledgment packet reports
9	0b RW	RXCHECKSUM_ERROR: Set to enable the interrupt for the computed CRC differs from the received CRC value in the acknowledgment packet reports
8	0b RW	RXECC_MULTIBIT_ERROR: Set to enable the interrupt for no ECC correction for the packet or there are more than 2 bit errors reported in the acknowledgment packet



Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	RXECC_SINGLE_BIT_ERROR: Set to enable the interrupt for ECC syndrome computation and one bit error correction for the acknowledgment packet
6	0b RW	RXFALSE_CONTROL_ERROR: Set to enable the interrupt for control error in the acknowledgment packet reports
5	0b RW	RXHS_RECEIVE_TIMEOUT_ERROR: Set to enable the interrupt for the high speed receive timeout Error in the acknowledgment packet reports
4	0b RW	RX_LP_TX_SYNC_ERROR: Set to enable the interrupt for Low power transmission sync error in the acknowledgment packet reports
3	0b RW	RXESCAPE_MODE_ENTRY_ERROR: Set to enable the interrupt for Escape Mode Entry command error in the acknowledgment packet reports
2	0b RW	RXEOTSYNC_ERROR: Set to enable the interrupt for End of transmission synchronisation Error in the acknowledgement packet reports
1	0b RW	RXSOTSYNC_ERROR: Set to enable the interrupt for start of transmission synchronisation error in the acknowledgement packet reports
0	0b RW	RXSOT_ERROR: Set to enable the interrupt for start of transmission error in the acknowledgment packet reports

14.10.48 MIPIA_DSI_FUNC_PRG__REG—Offset B00Ch

mipi pipe A dsi function program register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B00Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RESERVED				SUPPORTED_DATA_WIDTH_IN_COMMAND_MODE	RESERVED_1	SUPPORTED_FORMAT_IN_VIDEO_MODE	CHANNEL_NUMBER_FOR_COMMAND_MODE	CHANNEL_NUMBER_FOR_VIDEO_MODE
								DATA_LANES_PRG_REG



mipi pipe A LP RX timeout register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B014h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				LOW_POWER_RECEPTION_TIMEOUT_COUNTER				

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Reserved.
23:0	0b RW	LOW_POWER_RECEPTION_TIMEOUT_COUNTER: Timeout value to be checked for received short packets .If the timer expires the DSI Host enters stop state

14.10.51 MIPIA_TURN_AROUND_TIMEOUT_REG—Offset B018h

mipi pipe A turn around timeout register

Access Method



Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	RESERVED: Reserved.
15:0	0b RW	HORIZONTAL_FRONT_PORCH_COUNT: Shows the horizontal front porch value in terms of txbyteclkhs

14.10.58 MIPIA_HORIZ_ACTIVE_AREA_COUNT—Offset B034h

mipi A horizontal active area counter

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B034h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.10.61 MIPIA VERT FRONT PORCH COUNT—Offset B040h



Bit Range	Default & Access	Field Name (ID): Description
15:0	0b RW	HIGH_SPEED_TO_LOW_POWER_OR_LOW_POWER_TO_HIGH_SPEED_SWITCH_COUNT: High speed to low power or Low power to high speed switching time in terms of txbyteclkhs

14.10.63 MIPIA DPI CTRL REG—Offset B048h

mipi A dpi ctrl register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B048h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								0
RSTTRG								0
HS_LP								0
BACK_LIGHT_OFF								0
BACK_LIGHT_ON								0
COLOR_MODE_OFF								0
COLOR_MODE_ON								0
TURN_ON								0
SHUT_DOWN								0

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	RESERVED:
7	0b RW	RSTTRG: mipi A dpi ctrl reg RSTTRG
6	0b RW	HS_LP: Set to '0' to indicate the special packets are sent through the DSI link using HS transmission and set to '1' to indicate that the special packets are sent through the DSI link using low power mode
5	0b RW	BACK_LIGHT_OFF: Set to '1' to indicate a backlight OFF short packet has to be packetised for the DPI's virtual channel
4	0b RW	BACK_LIGHT_ON: Set to '1' to indicate a backlight ON short packet has to be packetised for the DPI's virtual channel
3	0b RW	COLOR_MODE_OFF: Set to '1' to indicate a color mode OFF short packet has to be packetised for the DPI's virtual channel
2	0b RW	COLOR_MODE_ON: Set to '1' to indicate a color mode ON short packet has to be packetised for the DPI's virtual channel
1	0b RW	TURN_ON: Set to '1' to indicate a turn on short packet has to be packetised for the DPI's virtual channel
0	0b RW	SHUT_DOWN: Set to '1' to indicate a shut down short packet has to be packetised for the DPI's virtual channel



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED							RANDOM_DPI_DISPLAY_RESOLUTION_DEFEATURE	
							MIPIA_DISABLE_VIDEO_BTA	
							IP_TG_CONFIG	
							VIDEO_MODE_FMT	

Bit Range	Default & Access	Field Name (ID): Description
31:5	0b RW	RESERVED: Reserved.
4	0b RW	RANDOM_DPI_DISPLAY_RESOLUTION_DEFEATURE: Set by the processor to support random DPI display resolution 0 - random DPI display resolution support disabled. 1 - random DPI display resolution support enabled.
3	0b RW	MIPIA_DISABLE_VIDEO_BTA: Set by the processor to inform the DSI controller to disable the BTA sent at the last blanking line of VFP. By default, this bit is set to 0.0 BTA sending at the last blanking line of VFP is enabled. 1 BTA sending at the last blanking line of VFP is disabled.
2	0b RW	IP_TG_CONFIG: Set by the processor to inform that the DSI controller should discontinue the DPI transfer after the last line of the VFP after ip_tg_enable deassertion. By default, this bit is set to 0. 0 - After ip_tg_enable deassertion, DSI Tx controller stops the DPI transfer immediately after the current packet is transmitted. 1 - After ip_tg_enable deassertion, DSI Tx controller discontinues the DPI transfer after the last line of the VFP
1:0	0b RW	VIDEO_MODE_FMT: Sets the Video mode format (packet sequence) to be supported in DSI. In Non Burst Mode, in addition to programming this register the horizontal active area count register value should also be programmed equal to RGB word count value. In Burst Mode, in addition to programming this register the horizontal active area count register value should also be programmed greater than the RGB word count value, leaving more time during a scan line for LP mode (saving power) or for multiplexing other transmissions onto the DSI link. 00 Reserved 01 - Non Burst Mode with Sync Pulse 10 - Non Burst Mode with Sync events 11 - Burst Mode

14.10.68 MIPIA_EOT_DISABLE_REGISTER—Offset B05Ch

mipi A eot disable register

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B05Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED							LP_RX_TIMEOUT_ERROR_RECOVERY_DISABLE	
							HS_TX_TIMEOUT_ERROR_RECOVERY_DISABLE	
							LOW_CONTENTION_RECOVERY_DISABLE	
							HIGH_CONTENTION_RECOVERY_DISABLE	
							TXDSL_TYPE_NOT_RECOGNISED_ERROR_RECOVERY_DISABLE	
							TXECC_MULTIBIT_ERR_RECOVERY_DISABLE	
							CLOCKSTOP	
							EOT_DIS	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	RESERVED: Reserved.
7	0b RW	LP_RX_TIMEOUT_ERROR_RECOVERY_DISABLE: Set by the processor to enable or disable the LP_Rx_timeout error recovery if the processor clears LP_Rx_timeout error interrupt. 0 - LP_Rx_timeout error recovery action will be taken by the DSI Tx controller if the processor clears the LP_Rx_timeout error interrupt. 1 - If the processor clears the LP_Rx_timeout error interrupt, LP_Rx_timeout error recovery action will not happen in DSI Tx controller. LP Rx timeout error interrupt will act as an informative interrupt
6	0b RW	HS_TX_TIMEOUT_ERROR_RECOVERY_DISABLE: Set by the processor to enable or disable the HS_Tx_timeout error recovery if the processor clears HS_Tx_timeout interrupt. 0 - HS_Tx_timeout error recovery action will be taken by the DSI Tx controller if the processor clears the HS_Tx_timeout error interrupt. 1 - If the processor clears the HS_Tx_timeout error interrupt, HS_Tx_timeout error recovery action will not happen in DSI Tx controller. HS Tx timeout error interrupt will act as an informative interrupt



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	LOW_CONTENTION_RECOVERY_DISABLE: Set by the processor to enable or disable the contention recovery procedure if the processor clears Low contention interrupt. 0 - Contention recovery will happen if the processor clears Low contention interrupt. 1 - If the processor clears the low contention interrupt, contention recovery procedure will not be initiated by the DSI Tx controller. Low contention interrupt will act as an informative interrupt
4	0b RW	HIGH_CONTENTION_RECOVERY_DISABLE: Set by the processor to enable or disable the contention recovery procedure if the processor clears High contention interrupt. 0 - Contention recovery will happen if the processor clears High contention interrupt. 1 - If the processor clears the high contention interrupt, contention recovery procedure will not be initiated by the DSI Tx controller. Ignore the High Contention Interrupt in MIPI_INTR_STAT_REG
3	0b RW	TXDSI_TYPE_NOT_RECOGNISED_ERROR_RECOVERY_DISABLE: Set by the processor to enable or disable the error recovery action to be taken by the DSI Tx controller if TxDSI data type not recognised error interrupt is cleared by the processor. 0 - Error recovery action will be taken if TxDSI data type not recognised error interrupt is cleared by the processor. 1 - If TxDSI data type not recognised error interrupt is cleared by the processor, error recovery action will not be taken by the DSI TX controller. Tx DSI data type not recognized error interrupt will act as an informative interrupt
2	0b RW	TXECC_MULTIBIT_ERR_RECOVERY_DISABLE: Set by the processor to enable or disable the error recovery action to be taken by the DSI Tx controller if Tx ECC multibit error interrupt is cleared by the processor. 0 - Error recovery action will be taken if Tx ECC multibit error interrupt is cleared by the processor. 1 - If Tx ECC multibit error interrupt is cleared by the processor, error recovery action will not be taken by the DSI TX controller. Tx multibit error interrupt will act as an informative interrupt
1	0b RW	CLOCKSTOP: Set by the processor to enable or disable clock stopping feature during BLLP timing in a DPI transfer in dual channel mode or during DPI only mode and also when there is no traffic in the DBI interface in DBI only enabled mode. By default this register value is 0. 0 - clock stopping disabled 1 - clock stopping enabled
0	0b RW	EOT_DIS: Set by the processor to enable or disable EOT short packet transmission. By default this register value is 0. For backward compatibility of earlier DSI systems, EOT short packet transmission can be disabled. 0 - EOT short packet transmission enabled 1 - EOT short packet transmission disabled

14.10.69 MIPIA_LP_BYTECLK_REGISTER—Offset B060h

mipi A LP bytclk register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B060h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
LP_GEN_DATA								

Intel Atom® Processor E3800 Product Family
Datasheet
535

14.10.72 MIPIA_LP_GEN_CTRL_REGISTER—Offset B06Ch

mipi A LP Gen CTRL register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B06Ch


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				WORD_COUNT				VIRTUAL_CHANNEL
								DATA_TYPE

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b WO	RESERVED: Reserved.
23:8	0b WO	WORD_COUNT: Specifies the word count for generic long packet Specifies the accompanied parameters for generic short packets. Note: Invalid parameters must be set to 00h
7:6	0b WO	VIRTUAL_CHANNEL: Used to specify the virtual channel for which the generic data transmission is intended



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				WORD_COUNT				VIRTUAL_CHANNEL
								DATA_TYPE

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b WO	RESERVED: Reserved.
23:8	0b WO	WORD_COUNT: Specifies the word count for generic long packet Specifies the accompanied parameters for generic short packets. Note: Invalid parameters must be set to 00h
7:6	0b WO	VIRTUAL_CHANNEL: Used to specify the virtual channel for which the generic data transmission is intended
5:0	0b WO	DATA_TYPE: Used to specify the generic data types 03h - Generic short write, no parameters 13h - Generic short write, 1 parameter 23h - Generic short write, 2 parameters 04h - Generic read, no parameters 14h - Generic read, 1 parameter 24h - Generic read 2 parameter 29h - Generic long write 05h - Manufacturer DCS short write, no parameter 15h - Manufacturer DCS short write, one parameter 06h - Manufacturer DCS read, no parameter 39h - Manufacturer DCS long write



Access Method

Offset: [GTTMMADR LSB + 180000h] + B074h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
538



Bit Range	Default & Access	Field Name (ID): Description
15:8	00011010b RW	CLK_ZERO_COUNT: TCLK_0_TIM_UI_CNT for dphy is programmed as clk zero count by the processor
7:6	0b RW	RESERVED_2: Reserved.
5:0	000100b RW	PREPARE_COUNT: TCLK_PREP_TIM_UI_CNT and THS_PREP_TIM_UI_CNT for dphy are programmed as prepare count by the processor

14.10.78 MIPIA DBI BW CTRL REG—Offset B084h

mipi A DBI BW ctrl register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B084h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BANDWIDTH_TIMER								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	BANDWIDTH_TIMER: DBI Bandwidth control Register. The bandwidth essential for transmitting 16 long packets containing 252 bytes meant for DCS write memory command is programmed in this register in terms of byte clocks. Based on the DSI transfer rate and the number of lanes configured the time taken to transmit 16 long packets in a DSI stream varies. Note: The value programmed in this timer must be greater than the actual time taken to carryout 16 long packets transmission in DSI stream plus the time taken to transmit two blanking packets

14.10.79 MIPIA CLK LANE SWITCHING TIME CNT—Offset B088h

mipi A clk clane switching time counter

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B088h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
LS_HS_SSW_CNT				HS_LS_PWR_SW_CNT				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	LS_HS_SSW_CNT: Low power to high speed switching time in terms byte clock (txbyteclkhs). This value is based on the byte clock (txbyteclkhs) and low power clock frequency (txclkesc). Typical value - Number of byte clocks required to switch from low power mode to high speed mode after txrequesths_clk is asserted. Current Value is ah = 10 txbyteclkhs
15:0	0b RW	HS_LS_PWR_SW_CNT: High speed to low power switching time in terms byte clock (txbyteclkhs). This value is based on the byte clock (txbyteclkhs) and low power clock frequency (txclkesc). Typical value - Number of byte clocks request to switch from high speed mode to low power mode after txrequesths_clk is de-asserted. Current Value is 14h = 20 txbyteclkhs

14.10.80 MIPIA_STOP_STATE_STALL—Offset B08Ch

mipi A stop state stall

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B08Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				MIPIA_STOP_STATE_STALL_COUNTER				



Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	RESERVED: reserved
7:0	0b RW	MIPIA_STOP_STATE_STALL_COUNTER: Delay between (stall the stop state signal) the data transfer is increased based on this counter value. This counter is calculated from txclksc. Note: If processor programs this register then it needs to reprogram the high_low_switch counter in B044h and lp_equivalent_byteclk reg in B060h to compensate this delay. High_low_switch_count B044h: High to low switch counter = Actual High to low switch + stop_sta_stall_reg value * Low power clock equivalence value in terms of byte clock LP equivalent byteclk register B060h: LP equivalent byteclk value = txclksc time/ txbyteclk time * (105 + stop_sta_stall_reg value) / 105 Minimum time of Low Power short packet transfer = 105 txclksc

14.10.81 MIPIA INTR STAT REG 1—Offset B090h

mipi A interrupt state register 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B090h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RESERVED									MIPIA_RX_CONNECTION_DETECTED

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	RESERVED: reserved
0	0b RW	MIPIA_RX_CONNECTION_DETECTED: Set to 1'b1 if the contention detected in the display device and is reported in the Acknowledge packet by the display device

14.10.82 MIPIA_INTR_EN_REG_1—Offset B094h

mipi A interrupt enable register 1

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B094h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								MIPIA_ENABLE_RX_CONNECTION_DETECTED

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	RESERVED: reserved
0	0b RW	MIPIA_ENABLE_RX_CONNECTION_DETECTED: Set to enable the interrupt for contention detected error in the acknowledgement packet reports

14.10.83 MIPIA_DBI_TYPEC_CTRL—Offset B100h

mipi A Dbit typeC ctrl

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B100h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
VAL	STATUS	OPTION	FREQ	RESERVED		OVERRIDE	OVERRIDE_COUNTER	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	VAL: 0= disable DBI TYPE-C interface (default) 1= enable DBI TYPE-C interface Driver to make sure that the command and data buffers are cleared before this bit is changed
30	0b RW	STATUS: command and data buffer empty and link completed sending out all serialized data and IDLE 0 = IDLE 1 = work in progress
29:28	0b RW	OPTION: TYPE-C option selection 00 option 1 01 option 2 10 option 3 11 no defined functionality
27:24	0b RW	FREQ: Type-C clock frequency ; A counter based onczclk is used to generate the TYPE-C Clock. So based on the czclk, a frequency close to the specified below will be generated. Not the exact frequency. 0000 1Mhz (default) 0001 1Mhz 0010 2Mhz 1111 15Mhz
23:9	0b RW	RESERVED: Reserved.
8	0b RW	OVERRIDE: Use override counter value to derive the TYPE-C clock frequency
7:0	0b RW	OVERRIDE_COUNTER: Override counter value to generate the TYPE-C clock

14.10.84 MIPIA_CTRL—Offset B104h

MIPI adapter has a control register with options to control width of the dbi bus and the divide value of the clock that needs to be supplied to the Clocks module so that a 2x divided clock can be provided to the MIPI D-PHY IP. Self refresh capability is in DCS commands. The other 3 controls bits (SD, CM and back light control) are now moved to MIPI IP registers.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B104h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:7	0b RW	NAME_BITS: Reserved
6:5	0b RW	ESCAPE_CLOCK_DIVIDER: Read Only Escape clock divider select for Pipe A and Pipe C Escape clock is shared by both Pipe A and Pipe C so it cant be set different. 00= 1 X (20 Mhz) (default) 01= X (10Mhz) 10= X (5Mhz) Changing this register can only be done when the MIPI device_ready is turned OFF
4:3	0b RW	STATUS: 2'b00: low priority on read requests to G-unit 2'b11 : high priority
2	0b RW	RGB_FLIP: 1'b0 : RGB data from disp2d is reverted to BGR 1'b1 : RGB data from disp2d is passed as is to MIPI IP
1:0	0b RW	MIPI_2X_CLOCK_DIVIDER: Reserved

14.10.85 MIPIA DATA ADD—Offset B108h

mipi A data ADD

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B108h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
DATA_MEM_ADDR								DATA_MEM_ADDR_1	DATA_VALID



Bit Range	Default & Access	Field Name (ID): Description
31:5	0b RW	DATA_MEM_ADDR: When there is updated data for the display panel, S/W programs this register with the memory address to read from
4:1	0b RW	DATA_MEM_ADDR_1: Reserved
0	0b RW	DATA_VALID: This bit is set by S/W when the mem_addr is written and is cleared by H/W when done reading the data from memory

14.10.86 MIPIA DATA LEN—Offset B10Ch

mipiA data length

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B10Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				DATA_LENGTH				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RW	RESERVED: Reserved.
19:0	0b RW	DATA_LENGTH: This field shows the remaining length of data that needs to be read from memory, Initially set by S/W and is decremented by H/W as reads are issued

14.10.87 MIPIA CMD ADD—Offset B110h

mipi A cmd ADD

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B110h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
23:16	0b RW	COMMAND_2: This is command 2 length (command + parameters) in bytes
15:8	0b RW	COMMAND_1: This is command 1 length (command + parameters) in bytes
7:0	0b RW	COMMAND_0: This is command 0 length (command + parameters) in bytes

14.10.89 MIPIA RD DATA RETURN0—Offset B118h

In addition to the command and data registers, adapter provides 8 read only registers for S/W to read the return data from the panel. At this time the usage case for the read path from the panel is for configuration reads only. Hence, more than 4 bytes of read are not allowed. Maximum read return size in the MIPI IP should be no greater than 32 bytes.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B118h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RD_DATA_RETURN_PANEL								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RO	RD_DATA_RETURN_PANEL: This is the configuration data returned from the panel

14.10.90 MIPIA RD DATA RETURN1—Offset B11Ch

Refer to the description of MIPIA_RD_DATA_RETURN0.


Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B11Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RO	RD_DATA_RETURN_PANEL: This is the configuration data returned from the panel

14.10.96 MIPIA_RD_DATA_RETURN7—Offset B134h

Refer to the description of MIPIA_RD_DATA_RETURN0.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B134h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h


Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RO	RD_DATA_RETURN_PANEL: This is the configuration data returned from the panel



Bit Range	Default & Access	Field Name (ID): Description
27	0b RW	HS_GENERIC_WR_FIFO_FULL: Set to indicate that the HS generic write fifo is full
26	0b RW	RX_PROT_VIOLATION: Set if DSI protocol violation error is reported in the acknowledge packet by the display device
25	0b RW	RX_INVALID_TX_LENGTH: Set if invalid transmission length error is reported in the acknowledge packet by the display device
24	0b RW	ACK_WITH_NO_ERROR: Set if acknowledge trigger message is received with out any error
23	0b RW	TURN_AROUND_ACK_TIMEOUT: Set if a turn around acknowledgement sequence is not received from the display device
22	0b RW	LP_RX_TIMEOUT: Set if a low power reception count expires this interrupt is generated
21	0b RW	HS_TX_TIMEOUT: Set if a high speed transmission prevails for more than the expected count value this interrupt is raised
20	0b RW	DPI_FIFO_UNDERRUN: Set to '1' if there is no data in the dpi fifo to make a in time delivery of the pixel data to the DSI receiver
19	0b RW	LOW_CONTENTION: Set to '1' if a LP low fault is registered by at the D-PHY contention detector
18	0b RW	HIGH_CONTENTION: Set to '1' if a LP high fault is registered by at the D-PHY contention detector
17	0b RW	TXDSI_VC_ID_INVALID: Set to '1' if the received virtual channel ID is invalid
16	0b RW	TXDSI_DATA_TYPE_NOT_RECOGNISED: Set to '1' if the received data type is not recognised
15	0b RW	TXCHECKSUM_ERROR: Set to '1' if the computed CRC differs from the received CRC value during the reception of packets by Arasan_DSI host.
14	0b RW	TXECC_MULTIBIT_ERROR: Set to '1' if there is no ECC correction for the packet or there are more than 2 bit errors in the packet received by Arasan_DSI_host
13	0b RW	TXECC_SINGLE_BIT_ERROR: Set to '1' if ECC syndrome was computed and is corrected for one bit error during the reception of packets by the Arasan_DSI_host
12	0b RW	TXFALSE_CONTROL_ERROR: Set to '1' if a control error is observed on the lanes by the Arasan_DSI_host
11	0b RW	RXDSI_VC_ID_INVALID: Set to '1' if the virtual channel ID is invalid by the display device is reported in the Acknowledge packet by the display device
10	0b RW	RXDSI_DATA_TYPE_NOT_RECOGNISED: Set to '1' if the data type is not recognised by the display device is reported in the Acknowledge packet by the display device
9	0b RW	RXCHECKSUM_ERROR: Set to '1' if the computed CRC differs from the received CRC value and is reported in the Acknowledge packet by the display device
8	0b RW	RXECC_MULTIBIT_ERROR: Set to '1' if there is no ECC correction for the packet or there are more than 2 bit errors in the packet is reported in the Acknowledge packet by the display device
7	0b RW	RXECC_SINGLE_BIT_ERROR: Set to '1' if ECC syndrome was computed and corrected for one bit error is reported in the Acknowledge packet by the display device
6	0b RW	RXFALSE_CONTROL_ERROR: Set to '1' if a control error is reported in the Acknowledge packet by the display device



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	RXHS_RECEIVE_TIMEOUT_ERROR: Set to '1' if the high speed receive timer value expires and data transfer lasts on the data lane is reported in the Acknowledge packet by the display device
4	0b RW	RX_LP_TX_SYNC_ERROR: Set to '1' if Low power transmission sync error occurs in the display device and is reported in the Acknowledge packet by the display device
3	0b RW	RXESCAPE_MODE_ENTRY_ERROR: Set to '1' if Escape Mode Entry command is not understandable by the display device and is reported in the Acknowledge packet by the display device
2	0b RW	RXEOTSYNCERROR: mipi C RX eot synce error
1	0b RW	RXSOTSYNCERROR: Set to '1' if a start of transmission synchronisation error is reported in the Acknowledge packet by the display device
0	0b RW	RXSOTERROR: Set to '1' if a start of transmission error is reported in the Acknowledge packet by the display device

14.10.100 MIPIC_INTR_EN_REG—Offset B808h

mipi C intrrupt En reg

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B808h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0																							
0	0	0	0	0	0	0	0	0																							
RESERVED	SPL_PKT_SENT_INTERRUPT	GEN_READ_DATA_AVAIL	LP_GENERIC_WR_FIFO_FULL	HS_GENERIC_WR_FIFO_FULL	RX_PROT_VIOLATION	RX_INVALID_TX_LENGTH	ACK_WITH_NO_ERROR	TURN_AROUND_ACK_TIMEOUT	LP_RX_TIMEOUT	HS_TX_TIMEOUT	DPL_FIFO_UNDERRUN	LOW_CONTENTION	HIGH_CONTENTION	TXDSI_VC_ID_INVALID	TXDSI_DATA_TYPE_NOT_RECOGNISED	TXCHECKSUM_ERROR	TXECC_MULTIBIT_ERROR	TXECC_SINGLE_BIT_ERROR	TXFALSE_CONTROL_ERROR	RXDSI_VC_ID_INVALID	RXDSI_DATA_TYPE_NOT_RECOGNISED	RXCHECKSUM_ERROR	RXECC_MULTIBIT_ERROR	RXECC_SINGLE_BIT_ERROR	RXFALSE_CONTROL_ERROR	RXHS_RECEIVE_TIMEOUT_ERROR	RX_LP_TX_SYNC_ERROR	RXESCAPE_MODE_ENTRY_ERROR	RXEOTSYNC_ERROR	RXSOTSYNC_ERROR	RXSOT_ERROR

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	TEARING_EFFECT (RESERVED): Set to enable tearing effect
30	0b RW	SPL_PKT_SENT_INTERRUPT: Set to enable the confirmation of transmission of the DPI event specific commands set in the dpi control and dpi data register



Bit Range	Default & Access	Field Name (ID): Description
29	0b RW	GEN_READ_DATA_AVAIL: Set to enable Generic Read available interrupt
28	0b RW	LP_GENERIC_WR_FIFO_FULL: Set to indicate that the LP generic write fifo is full
27	0b RW	HS_GENERIC_WR_FIFO_FULL: Set to indicate that the HS generic write fifo is full
26	0b RW	RX_PROT_VIOLATION: Set to enable protocol violation error
25	0b RW	RX_INVALID_TX_LENGTH: Set to enable invalid transmission length error
24	0b RW	ACK_WITH_NO_ERROR: Set to enable acknowledge trigger message reception with out any error
23	0b RW	TURN_AROUND_ACK_TIMEOUT: Set to enable turn around acknowledgement ,sequence timeout
22	0b RW	LP_RX_TIMEOUT: Set to enable low power reception count timeouts
21	0b RW	HS_TX_TIMEOUT: Set to enable a high speed transmission timeout
20	0b RW	DPI_FIFO_UNDERRUN: Set to enable if there is no data in the dpi fifo to make a in time delivery of the pixel data to the DSI receiver
19	0b RW	LOW_CONTENTION: Set to enable a LP low fault interrupt
18	0b RW	HIGH_CONTENTION: Set to enable a LP high fault interrupt
17	0b RW	TXDSI_VC_ID_INVALID: Set to enable the interrupt if the received packets virtual channel ID is invalid
16	0b RW	TXDSI_DATA_TYPE_NOT_RECOGNISED: Set to enable the interrupt if the received packets data type is not recognised
15	0b RW	TXCHECKSUM_ERROR: Set to enable the interrupt if the computed CRC differs from the received CRC value for the received packets
14	0b RW	TXECC_MULTIBIT_ERROR: Set to enable the interrupt if there is no ECC correction for the packet or there are more than 2 bit errors in the packet received by Arasan DSI host
13	0b RW	TXECC_SINGLE_BIT_ERROR: Set to enable the interrupt if ECC syndrome was computed and is corrected for one bit error during the reception of packets by the Arasan DSIhost
12	0b RW	TXFALSE_CONTROL_ERROR: Set to enable the interrupt for the control error,observed on the lanes by the Arasan_DSI_host
11	0b RW	RXDSI_VC_ID_INVALID: Set to enable the interrupt for invalid virtual channel ID in the acknowledgment packet reports
10	0b RW	RXDSI_DATA_TYPE_NOT_RECOGNISED: Set to enable the interrupt for the un recognised data type in the acknowledgment packet reports
9	0b RW	RXCHECKSUM_ERROR: Set to enable the interrupt for the computed CRC differs from the received CRC value in the acknowledgment packet reports
8	0b RW	RXECC_MULTIBIT_ERROR: Set to enable the interrupt for no ECC correction for the packet or there are more than 2 bit errors reported in the acknowledgment packet



Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	RXECC_SINGLE_BIT_ERROR: Set to enable the interrupt for ECC syndrome computation and one bit error correction for the acknowledgment packet
6	0b RW	RXFALSE_CONTROL_ERROR: Set to enable the interrupt for control error in the acknowledgment packet reports
5	0b RW	RXHS_RECEIVE_TIMEOUT_ERROR: Set to enable the interrupt for the high speed receive timeout Error in the acknowledgment packet reports
4	0b RW	RX_LP_TX_SYNC_ERROR: Set to enable the interrupt for Low power transmission sync error in the acknowledgment packet reports
3	0b RW	RXESCAPE_MODE_ENTRY_ERROR: Set to enable the interrupt for Escape Mode Entry command error in the acknowledgment packet reports
2	0b RW	RXEOTSYNC_ERROR: Set to enable the interrupt for End of transmission synchronisation Error in the acknowledgement packet reports
1	0b RW	RXSOTSYNC_ERROR: Set to enable the interrupt for start of transmission synchronisation error in the acknowledgement packet reports
0	0b RW	RXSOT_ERROR: Set to enable the interrupt for start of transmission error in the acknowledgment packet reports

14.10.101 MIPIC_DSI_FUNC_PRG__REG—Offset B80Ch

mipi C DSI func prg reg

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B80Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RESERVED				SUPPORTED_DATA_WIDTH_IN_COMMAND_MODE	RESERVED_1	SUPPORTED_FORMAT_IN_VIDEO_MODE	CHANNEL_NUMBER_FOR_COMMAND_MODE	CHANNEL_NUMBER_FOR_VIDEO_MODE
								DATA_LANES_PRG_REG





Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Reserved.
23:0	0b RW	HIGH_SPEED_TX_TIMEOUT_COUNTER: The maximum duration allowed for the DSI host ,to remain in high speed mode for a transmission. If the counter expires, HS mode is terminated with EOT and the lanes enter stop state

14.10.103 MIPIC_LP_RX_TIMEOUT_REG—Offset B814h

mipi C LP RX timeout req

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B814h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				LOW_POWER_RECEPTION_TIMEOUT_COUNTER				

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Reserved.
23:0	0b RW	LOW_POWER_RECEPTION_TIMEOUT_COUNTER: Timeout value to be checked for received short packets .If the timer expires the DSI Host enters stop state



Access Method

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RW	RESERVED: Reserved.
5:0	0b RW	TURN_AROUND_TIMEOUT_REGISTER: Timeout value to be checked after the DSI host makes a turn around in the direction of transfers. If the timer expires the DSI Host enters stop state

14.10.105 MIPIC_DEVICE_RESET_TIMER—Offset B81Ch

Access Method

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B820h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
VERTICAL_ADDRESS				HORIZONTAL_ADDRESS				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	VERTICAL_ADDRESS: Shows the vertical address count in lines
15:0	0b RW	HORIZONTAL_ADDRESS: Shows the horizontal address count in pixels

14.10.107 MIPIC DBI RESOLUTION REG—Offset B824h

mipi C DBI resolution reg

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B824h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RESERVED									DBI_FIFO_THRTL

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	RESERVED: Reserved.
1:0	0b RW	DBI_FIFO_THRTL: DBI FIFO's watermark can be set using the following bits so as to enable dbi_stall de-assertion whenever the below FIFO condition is reached: 00 - (1/2) DBI fifo empty 01 - (1/4) DBI fifo empty 10 - 7 locations are empty 11 - Reserved

14.10.108 MIPIC_HORIZ_SYNC_PADDING_COUNT—Offset B828h

mipi C horizxontal sync padding out

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [GTTMMADR LSB + 180000h] + B828h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h





Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	RESERVED: Reserved.
15:0	0b RW	VERTICAL_FRONT_PORCH_COUNT: Shows the vertical front porch value in terms of lines

14.10.115 MIPIC_HIGH_LOW_SWITCH_COUNT—Offset B844h

mipi C high low switch count

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B844h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								
HIGH_SPEED_TO_LOW_POWER_OR_LOW_POWER_TO_HIGH_SPEED_SWITCH_COUNT								

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	RESERVED: High speed to low power or Low power to high speed switching time in terms of txbyteclkhs
15:0	0b RW	HIGH_SPEED_TO_LOW_POWER_OR_LOW_POWER_TO_HIGH_SPEED_SWITCH_COUNT: High speed to low power or Low power to high speed switching time in terms of txbyteclkhs

14.10.116 MIPIC_DPI_CTRL_REG—Offset B848h

mipi C dpi ctrl reg

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B848h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.10.117 MIPIC_DPI_DATA_REGISTER—Offset B84Ch

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								COMMAND_BYTE

14.10.118 MIPIC_INIT_COUNT_REGISTER—Offset B850h

mipi C init counter register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B850h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				MASTER_INIT_TIMER				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	RESERVED: Reserved.
15:0	0b RW	MASTER_INIT_TIMER: Counter value in terms of low power clock to initialise the DS Host IP [TINT] that drives a stop state on the mipi's D-PHY bus

14.10.119 MIPIC_MAX_RETURN_PKT_SIZE_REGISTER—Offset B854h

mipi C max return PKT size register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B854h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
RESERVED																MAX_RETURN_PKT_SIZE																			

Bit Range	Default & Access	Field Name (ID): Description
31:10	0b RW	RESERVED: Reserved.
9:0	0b RW	MAX_RETURN_PKT_SIZE: Set the count value in bytes to collect the return data packet for reverse direction data flow in data lane0 in response to a DBI read operation

14.10.120 MIPIC_VIDEO_MODE_FORMAT_REGISTER—Offset B858h

mipi C video mode format register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B858h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								
RANDOM_DPI_DISPLAY_RESOLUTION_DEFEATURE								
MIPIC_DISABLE_VIDEO_BT								
IP_TG_CONFIG								
VIDEO_MODE_FMT								



Bit Range	Default & Access	Field Name (ID): Description
31:5	0b RW	RESERVED: Reserved.
4	0b RW	RANDOM_DPI_DISPLAY_RESOLUTION_DEFEATURE: Set by the processor to support random DPI display resolution 0 - random DPI display resolution support disabled. 1 - random DPI display resolution support enabled.
3	0b RW	MIPIC_DISABLE_VIDEO_BTA: Set by the processor to inform the DSI controller to disable the BTA sent at the last blanking line of VFP. By default, this bit is set to 0. 0- BTA sending at the last blanking line of VFP is enabled. 1 - BTA sending at the last blanking line of VFP is disabled.
2	0b RW	IP_TG_CONFIG: Set by the processor to inform that the DSI controller should discontinue the DPI transfer after the last line of the VFP after ip_tg_enable deassertion. By default, this bit is set to 0. 0 - After ip_tg_enable deassertion, DSI Tx controller stops the DPI transfer immediately after the current packet is transmitted. 1 - After ip_tg_enable deassertion, DSI Tx controller discontinues the DPI transfer after the last line of the VFP
1:0	0b RW	VIDEO_MODE_FMT: Sets the Video mode format (packet sequence) to be supported in DSI. In Non Burst Mode, in addition to programming this register the horizontal active area count register value should also be programmed equal to RGB word count value. In Burst Mode, in addition to programming this register the horizontal active area count register value should also be programmed greater than the RGB word count value, leaving more time during a scan line for LP mode (saving power) or for multiplexing other transmissions onto the DSI link. 00 Reserved 01 - Non Burst Mode with Sync Pulse 10 - Non Burst Mode with Sync events 11 - Burst Mode

14.10.121 MIPIC_EOT_DISABLE_REGISTER—Offset B85Ch

mipi C EOT disable register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B85Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED							LP_RX_TIMEOUT_ERROR_RECOVERY_DISABLE	
							HS_TX_TIMEOUT_ERROR_RECOVERY_DISABLE	
							LOW_CONTENTION_RECOVERY_DISABLE	
							HIGH_CONTENTION_RECOVERY_DISABLE	
							TXDSI_TYPE_NOT_RECOGNISED_ERROR_RECOVERY_DISABLE	
							TXECC_MULTIBIT_ERR_RECOVERY_DISABLE	
							CLOCKSTOP	
							EOT_DIS	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	RESERVED: Reserved.
7	0b RW	LP_RX_TIMEOUT_ERROR_RECOVERY_DISABLE: Set by the processor to enable or disable the LP_Rx_timeout error recovery if the processor clears LP_Rx_timeout error interrupt. 0 - LP_Rx_timeout error recovery action will be taken by the DSI Tx controller if the processor clears the LP_Rx_timeout error interrupt. 1 - If the processor clears the LP_Rx_timeout error interrupt, LP_Rx_timeout error recovery action will not happen in DSI Tx controller. LP Rx timeout error interrupt will act as an informative interrupt
6	0b RW	HS_TX_TIMEOUT_ERROR_RECOVERY_DISABLE: Set by the processor to enable or disable the HS_Tx_timeout error recovery if the processor clears HS_Tx_timeout interrupt. 0 - HS_Tx_timeout error recovery action will be taken by the DSI Tx controller if the processor clears the HS_Tx_timeout error interrupt. 1 - If the processor clears the HS_Tx_timeout error interrupt, HS_Tx_timeout error recovery action will not happen in DSI Tx controller. HS Tx timeout error interrupt will act as an informative interrupt
5	0b RW	LOW_CONTENTION_RECOVERY_DISABLE: Set by the processor to enable or disable the contention recovery procedure if the processor clears Low contention interrupt. 0 - Contention recovery will happen if the processor clears Low contention interrupt. 1 - If the processor clears the low contention interrupt, contention recovery procedure will not be initiated by the DSI Tx controller. Low contention interrupt will act as an informative interrupt
4	0b RW	HIGH_CONTENTION_RECOVERY_DISABLE: Set by the processor to enable or disable the contention recovery procedure if the processor clears High contention interrupt. 0 - Contention recovery will happen if the processor clears High contention interrupt. 1 - If the processor clears the high contention interrupt, contention recovery procedure will not be initiated by the DSI Tx controller. Ignore the High Contention Interrupt in MIPI_INTR_STAT_REG

14.10.125 MIPIC_LP_GEN_CTRL REGISTER—Offset B86Ch

mipi C LP Gen ctrl register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B86Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				WORD_COUNT				VIRTUAL_CHANNEL
								DATA_TYPE

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b WO	RESERVED: Reserved.
23:8	0b WO	WORD_COUNT: Specifies the word count for generic long packet Specifies the accompanied parameters for generic short packets. Note: Invalid parameters must be set to 00h
7:6	0b WO	VIRTUAL_CHANNEL: Used to specify the virtual channel for which the generic data transmission is intended
5:0	0b WO	DATA_TYPE: Used to specify the generic data types 03h - Generic short write, no parameters 13h - Generic short write, 1 parameter 23h - Generic short write, 2 parameters 04h - Generic read, no parameters 14h - Generic read, 1 parameter 24h - Generic read 2 parameter 29h - Generic long write 05h - Manufacturer DCS short write, no parameter 15h - Manufacturer DCS short write, one parameter 06h - Manufacturer DCS read, no parameter 39h - Manufacturer DCS long write

14.10.126 MIPIC HS GEN CTRL REGISTER—Offset B870h

mipiC HS

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B870h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.10.127 MIPIC GEN FIFO STAT REGISTER—Offset B874h

Intel Atom® Processor E3800 Product Family
Datasheet
579



31	28	24	20	16	12	8	4	0
0	0	0	1	1	1	1	0	0
0	0	0	0	0	0	0	0	0
0	1	1	0	0	0	0	0	0
RESERVED	DPI_FIFO_EMPTY	DBI_FIFO_EMPTY	LP_CTRL_FIFO_EMPTY	LP_CTRL_FIFO_FULL	RESERVED_1	HS_CTRL_FIFO_EMPTY	HS_CTRL_FIFO_HALF_EMPTY	HS_CTRL_FIFO_FULL
					RESERVED_2	LP_DATA_FIFO_EMPTY	LP_DATA_FIFO_HALF_EMPTY	LP_DATA_FIFO_FULL
						RESERVED_3	HS_DATA_FIFO_EMPTY	HS_DATA_FIFO_HALF_EMPTY
							HS_DATA_FIFO_HALF_EMPTY	HS_DATA_FIFO_FULL

Bit Range	Default & Access	Field Name (ID): Description
31:29	0b RO	RESERVED: Reserved.
28	1b RO	DPI_FIFO_EMPTY: Default 1
27	1b RO	DBI_FIFO_EMPTY: Default 1
26	1b RO	LP_CTRL_FIFO_EMPTY: Default 1
25	1b RO	LP_CTRL_FIFO_HALF_EMPTY: Default 1
24	0b RO	LP_CTRL_FIFO_FULL: Default 0
23:19	0b RO	RESERVED_1: Reserved.
18	1b RO	HS_CTRL_FIFO_EMPTY: Default 1
17	1b RO	HS_CTRL_FIFO_HALF_EMPTY: Default 1
16	0b RO	HS_CTRL_FIFO_FULL: Default 0
15:11	0b RO	RESERVED_2: Reserved.
10	1b RO	LP_DATA_FIFO_EMPTY: Default 1
9	1b RO	LP_DATA_FIFO_HALF_EMPTY: Default 1
8	0b RO	LP_DATA_FIFO_FULL: Default 0
7:3	0b RO	RESERVED_3: Reserved.
2	1b RO	HS_DATA_FIFO_EMPTY: Default 1
1	1b RO	HS_DATA_FIFO_HALF_EMPTY: Default 1



Bit Range	Default & Access	Field Name (ID): Description
0	0b RO	HS_DATA_FIFO_FULL: Default 0

14.10.128 MIPIC_HS_LS_DBI_ENABLE_REG—Offset B878h

Note : dbi_hs_lp_switch_reg has to be written only if DBI FIFO is empty

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B878h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								
DBI HS I/S SWITCH RE								

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	RESERVED: Reserved.
0	0b RW	DBI_HS_LS_SWITCH_RE: Set to 1 if DBI packets have to be transmitted in Low power mode Set to 0 if DBI packets have to be transmitted in High speed mode

14.10.129 MIPIC_RESERVED—Offset B87Ch

Reserved.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B87Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

14.10.130 MIPIC_DPHY_PARAM_REG—Offset B880h

14.10.131 MIPIC DBI BW CTRL REG—Offset B884h

mipi C DBI BW ctrl reg

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B884h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BANDWIDTH_TIMER								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	BANDWIDTH_TIMER: DBI Bandwidth control Register. The bandwidth essential for transmitting 16 long packets containing 252 bytes meant for DCS write memory command is programmed in this register in terms of byte clocks. Based on the DSI transfer rate and the number of lanes configured the time taken to transmit 16 long packets in a DSI stream varies. Note: The value programmed in this timer must be greater than the actual time taken to carryout 16 long packets transmission in DSI stream plus the time taken to transmit two blanking packets

14.10.132 MIPIC CLK LANE SWITCHING TIME CNT—Offset B888h

mipi C clk lane switching time count

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B888h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
LS_HS_SSW_CNT					HS_LS_PWR_SW_CNT			



Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	LS_HS_SSW_CNT: Low power to high speed switching time in terms byte clock (txbyteclkhs). This value is based on the byte clock (txbyteclkhs) and low power clock frequency (txclkesc). Typical value - Number of byte clocks required to switch from low power mode to high speed mode after txrequesths_clk is asserted. Current Value is ah = 10 txbyteclkhs
15:0	0b RW	HS_LS_PWR_SW_CNT: High speed to low power switching time in terms byte clock (txbyteclkhs). This value is based on the byte clock (txbyteclkhs) and low power clock frequency (txclkesc). Typical value - Number of byte clocks request to switch from high speed mode to low power mode after txrequesths_clk is de-asserted. Current Value is 14h = 20 txbyteclkhs

14.10.133 MIPIC STOP STATE STALL—Offset B88Ch

Access Method

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED							MIPIC_STOP_STATE_STALL_COUNTER	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	RESERVED: reserved
7:0	0b RW	MIPIC_STOP_STATE_STALL_COUNTER: Delay between (stall the stop state signal) the data transfer is increased based on this counter value. This counter is calculated from txclkesc. Note: If processor programs this register then it needs to reprogram the high_low_switch counter in B844h and lp_equivalent_byteclk reg in B860h to compensate this delay. High_low_switch_count B844h: High to low switch counter = Actual High to low switch + stop_sta_stall_reg value * Low power clock equivalence value in terms of byte clock LP equivalent byteclk register B860h: LP equivalent byteclk value = txclkesc time/ txbyteclk time * (105 + stop_sta_stall_reg value) / 105 Minimum time of Low Power short packet transfer = 105 txclkesc

14.10.134 MIPIC_INTR_STAT_REG_1—Offset B890h

mipi C intrrupt stat register 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B890h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RESERVED									
MPIC_RX_CONNECTION_DETECTED									

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	RESERVED: reserved
0	0b RW	MIPIC_RX_CONNECTION_DETECTED: Set to 1'b1 if the contention detected in the display device and is reported in the Acknowledge packet by the display device

14.10.135 MIPIC_INTR_EN_REG_1—Offset B894h

mipic interrupt enable register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B894h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	RESERVED: reserved
0	0b RW	MIPIC_ENABLE_RX_CONNECTION_DETECTED: Set to enable the interrupt for contention detected error in the acknowledgement packet reports

14.10.136 MIPIC_CTRL—Offset B904h

mipi ctrl reg

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B904h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h





Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B910h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:5	0b RW	COMMAND_MEM_ADDR: When there are new commands that need to be sent to the display panel, S/W programs this register with the memory address to read the commands from
4:3	0b RW	RESERVED: MBZ
2	0b RW	MIPIC_AUTO_PWG_ENABLE: Idle state: SW driver writes to this bit to enable auto power gating for MIPIC controller 0: default 1: auto power gate is enabled



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW	COMMAND_DATA_MODE: 0: data for memory write command from system buffer that is specified by MIPI data address register 1: data for memory write command from pipe A rendering
0	0b RW	COMMAND_VALID: This bit is set by S/W when the mem_addr is written and is cleared by H/W when done reading the data from memory

14.10.140 MIPIC_CMD_LEN—Offset B914h

mipiC commanf Length

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B914h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
COMMAND_3				COMMAND_2				COMMAND_1				COMMAND_0			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	COMMAND_3: This is command 3 length (command + parameters) in bytes
23:16	0b RW	COMMAND_2: This is command 2 length (command + parameters) in bytes
15:8	0b RW	COMMAND_1: This is command 1 length (command + parameters) in bytes
7:0	0b RW	COMMAND_0: This is command 0 length (command + parameters) in bytes

14.10.141 MIPIC RD DATA RETURN0—Offset B918h

mipi C Read data return 0

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B918h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.10.143 MIPIC RD DATA RETURN2—Offset B920h

```
mipi C read data return 2
```

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + B920h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RD_DATA_RETURN_PANEL								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RO	RD_DATA_RETURN_PANEL: This is the configuration data returned from the panel

14.10.144 MIPIC_RD_DATA_RETURN3—Offset B924h

```
mipi C read data return 3
```

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B924h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RD_DATA_RETURN_PANEL								

14.10.145 MIPIC_RD_DATA_RETURN4—Offset B928h

```
mipi C read data return 4
```

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B928h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RD_DATA_RETURN_PANEL								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RO	RD_DATA_RETURN_PANEL: This is the configuration data returned from the panel

14.10.146 MIPIC_RD_DATA_RETURN5—Offset B92Ch

```
mipi C read data return 5
```

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + B92Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h





Access Method

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

14.10.149 MIPIC_RD_DATA_VALID—Offset B938h

Access Method

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
28:16	0b RW	PIPE_A_VERTICAL_SYNC_END: This 13-bit field specifies the Vertical Sync End position expressed in terms of the absolute Line number relative to the vertical active display start. The value programmed should be the VSYNC End line position, where the first active line is considered line 0, the second active line is considered line 1, etc. This register should be loaded with Vactive+BottomBorder+FrontPorch+Sync-1. For interlaced display modes, hardware automatically divides this number by 2 to get the vertical sync end in each field. It does not count the two half lines that get added when operating in modes with half lines.
15:13	0b RW	RESERVED_1: Read Only.
12:0	0b RW	PIPE_A_VERTICAL_SYNC_START: This 13-bit field specifies the Vertical Sync Start position expressed in terms of the absolute line number relative to the vertical active display start. The value programmed should be the VSYNC Start line position, where the first active line is considered line 0, the second active line is considered line 1, etc. This register would be loaded with Vactive+BottomBorder+FrontPorch-1. For interlaced display modes, hardware automatically divides this number by 2 to get the vertical sync start in each field. It does not count the two half lines that get added when operating in modes with half lines.

14.10.156 PIPESRCA—Offset 6001Ch

Pipe A Source Image Size

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6001Ch


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				PIPE_A_HORIZONTAL_SOURCE_IMAGE_SIZE				
RESERVED_1				PIPE_A_VERTICAL_SOURCE_IMAGE_SIZE				

Bit Range	Default & Access	Field Name (ID): Description
31:28	0b RW	RESERVED: Write as zero



Bit Range	Default & Access	Field Name (ID): Description
12:0	0b RW	PIPE_A_SECOND_FIELD_VERTICAL_SYNC_SHIFT: This value specifies the vertical sync alignment for the start of the interlaced second field expressed in terms of the absolute pixel number relative to the horizontal active display start. This value will only be used if the PIPEACONF is programmed to an interlaced mode using vsync shift. Otherwise a legacy value of floor[htotal / 2] will be used. Typically, the interlaced second field vertical sync should start one pixel after the point halfway between successive horizontal syncs, so the value of this register should be programmed to: (horizontal sync start - floor[horizontal total / 2]) (use the actual horizontal sync start and horizontal total values and not the minus one values programmed into registers). This vertical sync shift only occurs during the interlaced second field. In all other cases the vertical sync start position is aligned with horizontal sync start.

14.10.159 TRANSADATAM1—Offset 60030h

Pipe A Data M value 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 60030h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 7E000000h

31		28				24				20				16				12				8				4				0			
0		1		1		1		1		0		0		0		0		0		0		0		0		0		0		0		0	
RESERVED		TU1_SIZE								RESERVED_1		PIPE_A_DATA_M1_VALUE																					

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	RESERVED: Project: All Format: MBZ
30:25	111111b RW	TU1_SIZE: Project: All This field is the size of the transfer unit for DP, minus one.
24	0b RW	RESERVED_1: Project: All Format: MBZ
23:0	0b RW	PIPE_A_DATA_M1_VALUE: Project: All This field is the M1 value for internal use of the DDA.

14.10.160 TRANSADATAN1—Offset 60034h

Pipe A Data N value 1

Access Method



Access Method

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				PIPE_A_LINK_M2_VALUE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Project: All Format: MBZ
23:0	0b RW	PIPE_A_LINK_M2_VALUE: Project: All This field is the M2 value for external transmission in the Main Stream Attributes.

14.10.166 TRANSADPLINKN2—Offset 6004Ch

Access Method

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				PIPE_A_LINK_N2_VALUE				



Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Project: All Format: MBZ
23:0	0b RW	PIPE_A_LINK_N2_VALUE: Project: All This field is the N2 value for external transmission in the Main Stream Attributes and VB-ID.

14.10.167 CRCCTRLREDA—Offset 60050h

Pipe A CRC Color Channel Control Register (Red)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 60050h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

		28				24				20				16				12				8				4				0			
		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
ENABLE_COLOR_CRC		CRC_SOURCE_SELECT				RESERVED				EXPECTED_CRC_VALUE																							

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	ENABLE_COLOR_CRC: Enables the CRC calculations. After being enabled for the first time, you need to wait for two VBLANK events for a valid CRC result. After that, a CRC will be generated each frame. 0 = CRC Calculations are disabled 1 = CRC Calculations are enabled
30:27	0b RW	CRC_SOURCE_SELECT: These bits select the source of the data to put into the CRC logic. 0000: Pipe A (Not available when DisplayPort or TV is enabled on this pipe) [DevVLVP] 0001: sDVOB/HDMI B (30 bit format. Only select when HDMI B is set to pipeA) [DevVLVP] 0010: sDVOB/HDMI C (30 bit format. Only select when HDMI C is set to pipeA) [DevVLVP] 0011: DisplayPort D (40 bit format) [DevCTG] 0100: TV Encoder outputs (30 bit format) 0101: TV filter outputs (30 bit format) 0110: DisplayPort B (40 bit format) [DevCTG, DevCDV, DevVLVP] 0111: DisplayPort C (40 bit format) [DevCTG, DevCDV, DevVLVP] 1000: Audio DP (Audio for DisplayPort (pcdclk). Only select when Audio is on DisplayPort on Pipe A) [DevVLVP] 1001: Audio HDMI (Audio for HDMI (dotclock) Only select when Audio is on HDMI on Pipe A) Others: Reserved
26:23	0b RW	RESERVED: Write as zero



Access Method

Offset: [GTTMMADR_LSB + 180000h] + 60068h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				COLOR_CHANNEL_CRC_RESULT_VALUE				



Pipe A A CRC Color Channel Result Register

Type: Memory Mapped I/O Register
(Size: 32 bits)

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:23	0b RO	RESERVED: Read only
22:0	0b RO	COLOR_CHANNEL_CRC_RESULT_VALUE: This field contains the resultant CRC value for the particular Color Channel at the end of a frame. A status bit can be used as an indication that the data is the valid result of a CRC calculation.



Pipe A Panel Self Refresh Control

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 60090h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Intel Atom® Processor E3800 Product Family
Datasheet
617



Pipe A PSR status register



Pipe A PSR CRC2 register

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RO	CRC_VALUE_BITS_15_0_OF_B_COMPONENT: crc values bits 15 to 0 of Blue component
15:0	0b RO	CRC_VALUE_BITS_15_0_OF_G_COMPONENT: crc values bits 15 to 0 of green component



14.10.181 VSCSDPA—Offset 600A0h

Pipe A VSC SDP register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 600A0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SDP_SEND_FREQUENCY	RESERVED				DB1	DB0		

Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	SDP_SEND_FREQUENCY: 00: off, not sending 01: send one every frame 10: send once 11: reserved Programming note: This field shall be programmed either send once or send one every frame when SW driver sets PSR active entry bit. When PSR is enabling this field is ignored. One SDP is sent in every frame until source is in PSR active state
29:16	0b RW	RESERVED: Reserved.
15:8	0b RW	DB1: : Programmed by display driver in manual mode, auto-generate by display controller in all other modes
7:0	0b RW	DB0: : Bits 7:4: Stereo Interface Method Specific Parameter Bits 3:0: Stereo Interface Method Code. This field is programmed by display driver for stereo display configuration

14.10.182 PIPEAWIDEGAMUTCOLORCORRECTIONC01_C00COEFFICIENTS—Offset 600B0h

When color correction matrix enable bit is set in PIPEACONF register, each of pixels in the pipe is multiplied with this matrix. Color matrix is used to convert pixels from one RGB color space to another RGB color space. There are many applications for the use of this matrix like gamut mapping between 72 percent color gamut to 92 percent color gamut. Each coefficient is a 12-bit signed fixed-point number. The application of coefficients are as follows:

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 600B0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED	C01_COEFFICIENT				RESERVED_1	C00_COEFFICIENT		

Bit Range	Default & Access	Field Name (ID): Description
31:28	0b RW	RESERVED: Reserved.
27:16	0b RW	C01_COEFFICIENT: 12-bit 2's complement signed value that is programmed for line. The range of the value can be from -1.999 to +1.999.
15:12	0b RW	RESERVED_1: Reserved.
11:0	0b RW	C00_COEFFICIENT: 12-bit 2's complement signed value that is programmed for line. The range of the value can be from -1.999 to +1.999.

14.10.183 PIPEA WIDE GAMUT COLOR CORRECTION C02 COEFFICIENT— Offset 600B4h

Refer to the description of the Pipe A Wide Gamut Color Correction C01_C00 register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 600B4h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED						C02_COEFFICIENT		





Bit Range	Default & Access	Field Name (ID): Description
20:19	0b RW	DIP_BUFFER_INDEX: Project: All Default Value: 00b This field is used during programming of different DIPs. These bits are used as an index to their respective DIP buffers. The transmission frequency must also be written when programming the buffer. Value Name Description Project 00b AVI AVI DIP (31 bytes of space available) All 01b Vendor-specific Vendor-specific DIP All 10b Reserved Reserved All 11b Source Product Source Product Description DIP All
18	0b RW	RESERVED_1: Project: All Format:
17:16	0b RW	VIDEO_DIP_TRANSMISSION_FREQUENCY: Project: All Default Value: 00b These bits dictate the frequency of Video DIP transmission for the DIP buffer index designated in bits 20:19. When writing Video DIP data, this value is also latched when the first DW of the Video DIP is written. When read, this value reflects the Video DIP transmission frequency for the Video DIP buffer designated in bits 20:19. This field shall be ignored for Gamut Metadata Packet transmission. Value Name Description Project 00b Send Once Send Once All 01b Every VSync Send Every VSync (Default for AVI) All 10b Every Other Vsync Send at least every other VSync All 11b Reserved Reserved All
15:12	0b RW	RESERVED_2: Project: All Format: MBZ
11:8	1001b RO	VIDEO_DIP_BUFFER_SIZE: Project: All AccessType: Read Only Default Value: ;1001b This reflects the buffer size in dwords available for the type of Video DIP being indexed by bits 20:19 of this register, including the header. It is hardwired to the maximum size of a Video DIP, 36 bytes. Please note that this count includes ECC bytes, which are not writable by software. These bits are immediately valid after write of the DIP index.
7:4	0b RW	RESERVED_3: Project: All Format: MBZ
3:0	0b RO	VIDEO_DIP_RAM_ACCESS_ADDRESS: Project: All AccessType: Read Only Selects the DWORD address for access to the Video DIP buffers. This value is automatically incremented after each read or write of the Video DIP Data Register. The value wraps back to zero when it autoincrements past the max address value of 0xF. This field change takes effect immediately after being written. The read value indicates the current access address.

14.10.189 VIDEO_DIP_DATA_A—Offset 60208h

Video Data Island Packet Data for Pipe A

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 60208h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:3	0b RW	RESERVED: Project: All Format: MBZ



Bit Range	Default & Access	Field Name (ID): Description
2	0b RW	GCP_COLOR_INDICATION: Project: All Default Value: 0b This bit must be set when in deep color mode. It may optionally be set for 24-bit mode. It must be set if the sink attached to Pipe A can receive GCP data. Value Name Description Project 0b Dont Indicate Dont indicate color depth. CD and PP bits in GCP set to zero All 1b Indicate Indicate color depth using CD bits in GCP. It will be set depending on programmed pixel depth in port control register All
1	0b RW	GCP_DEFAULT_PHASE_ENABLE: Project: All Default Value: 0b Indicates the video timings meet alignment requirements such that the following conditions are met: Htotal is an even number Hactive is an even number Hsync is an even number Front and back porches for Hsync are even numbers Vsync always starts on an even-numbered pixel within a line in interlaced modes (starting counting with 0) Value Name Description Project 0b Clear Default phase bit in GCP is cleared All 1b Require Met Default phase bit in GCP is set. All requirements must be met before setting this bit All
0	0b RW	GCP_AV_MUTE: Project: All Default Value: 0b Set AV mute bit in GCP Value Name Description Project 0b Clear AV mute bit in GCP is cleared. When this bit transitions to 0, the AV mute clear flag is sent in the next GCP packet All 1b Set AV mute bit in GCP is set. When this bit transitions to 1, the AV mute set flag is sent in the next GCP packet All

14.10.191 HTOTAL_B—Offset 61000h

Pipe B Horizontal Total Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61000h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED	PIPE_B_HORIZONTAL_TOTAL_DISPLAY			RESERVED_1	PIPE_B_HORIZONTAL_ACTIVE_DISPLAY			

14.10.193 HSYNC B—Offset 61008h

Pipe B Horizontal Sync Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61008h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED	PIPE_B_HORIZONTAL_SYNC_END				RESERVED_1	PIPE_B_HORIZONTAL_SYNC_START		

Bit Range	Default & Access	Field Name (ID): Description
31:29	0b RW	RESERVED: Write as zero.
28:16	0b RW	PIPE_B_HORIZONTAL_SYNC_END: See pipe A description.
15:13	0b RW	RESERVED_1: Write as zero.
12:0	0b RW	PIPE_B_HORIZONTAL_SYNC_START: See pipe A description

14.10.194 VTOTAL_B—Offset 6100Ch

Pipe B Vertical Total Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6100Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:29	0b RW	RESERVED: Write as zero.
28:16	0b RW	PIPE_B_VERTICAL_BLANK_END: See pipe A description.
15:13	0b RW	RESERVED_1: Write as zero.
12:0	0b RW	PIPE_B_VERTICAL_BLANK_START: See pipe A description.

14.10.196 VSYNC_B—Offset 61014h

Pipe B Vertical Sync Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61014h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0									
RESERVED				PIPE_B_VERTICAL_SYNC_END																RESERVED_1				PIPE_B_VERTICAL_SYNC_START															

Bit Range	Default & Access	Field Name (ID): Description
31:29	0b RW	RESERVED: Write as zero.
28:16	0b RW	PIPE_B_VERTICAL_SYNC_END: See pipe A description.
15:13	0b RW	RESERVED_1: Write as zero.
12:0	0b RW	PIPE_B_VERTICAL_SYNC_START: See pipe A description.

14.10.197 PIPEBSRC—Offset 6101Ch

Pipe B Source Image Size

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6101Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RESERVED		PIPE_B_HORIZONTAL_SOURCE_IMAGE_SIZE				RESERVED_1		PIPE_B_VERTICAL_SOURCE_IMAGE_SIZE	

Bit Range	Default & Access	Field Name (ID): Description
31:28	0b RW	RESERVED: Write as zero
27:16	0b RW	PIPE_B_HORIZONTAL_SOURCE_IMAGE_SIZE: See pipe A description.
15:12	0b RW	RESERVED_1: Write as zero
11:0	0b RW	PIPE_B_VERTICAL_SOURCE_IMAGE_SIZE: See pipe A description.

14.10.198 BCLRPAT_B—Offset 61020h

Pipe B Border Color Pattern Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61020h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
RESERVED				PIPE_B_RED_CHANNEL_COLOR_VALUE				PIPE_B_GREEN_CHANNEL_COLOR_VALUE				PIPE_B_BLUE_CHANNEL_COLOR_VALUE			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Reserved.
23:16	0b RW	PIPE_B_RED_CHANNEL_COLOR_VALUE: pipeB red color channel values
15:8	0b RW	PIPE_B_GREEN_CHANNEL_COLOR_VALUE: pipeB green color channel values
7:0	0b RW	PIPE_B_BLUE_CHANNEL_COLOR_VALUE: pipeB blue color channel values

14.10.199 VSYNCSHIFT_B—Offset 61028h

Vertical Sync Shift Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61028h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED						PIPE_B_SECOND_FIELD_VERTICAL_SYNC_SHIFT		

Bit Range	Default & Access	Field Name (ID): Description
31:13	0b RW	RESERVED: Write as zero.
12:0	0b RW	PIPE_B_SECOND_FIELD_VERTICAL_SYNC_SHIFT: This value specifies the vertical sync alignment for the start of the interlaced second field expressed in terms of the absolute pixel number relative to the horizontal active display start. This value will only be used if the PIPEBCONF is programmed to an interlaced mode using vsync shift. Otherwise a legacy value of floor[htotal / 2] will be used. Typically, the interlaced second field vertical sync should start one pixel after the point halfway between successive horizontal syncs, so the value of this register should be programmed to: (horizontal sync start - floor[horizontal total / 2]) (use the actual horizontal sync start and horizontal total values and not the minus one values programmed into registers). This vertical sync shift only occurs during the interlaced second field. In all other cases the vertical sync start position is aligned with horizontal sync start.

14.10.200 TRANSBDATAM1—Offset 61030h

Pipe B Data M value 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61030h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 7E000000h



31		28				24				20				16				12				8				4				0					
0		1		1		1		1		0		0		0		0		0		0		0		0		0		0		0		0		0	
RESERVED		TU1_SIZE								RESERVED_1		PIPE_B_DATA_M1_VALUE																							

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	RESERVED: Project: All Format: MBZ
30:25	111111b RW	TU1_SIZE: Project: All Default Value: ;111111b 64 See Pipe A description.
24	0b RW	RESERVED_1: Project: All Format: MBZ
23:0	0b RW	PIPE_B_DATA_M1_VALUE: Project: All See Pipe A description.

14.10.201 TRANSBDATAN1—Offset 61034h

Pipe B Data N value 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61034h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0										
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
RESERVED				PIPE_B_DATA_N1_VALUE														

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Project: All Format: MBZ

14.10.202 TRANSBDATAM2—Offset 61038h

Pipe B Data M value 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61038h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 7E000000h

31 28 24 20 16 12 8 4 0 0 1 1 1 1 1 1 0																															
RESERVED TU2_SIZE RESERVED_1 PIPE_B_DATA_M2_VALUE																															

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	RESERVED: Project: All Format: MBZ
30:25	111111b RW	TU2_SIZE: Project: All Default Value: ;111111b 64 See Pipe A description.
24	0b RW	RESERVED_1: Project: All Format: MBZ
23:0	0b RW	PIPE_B_DATA_M2_VALUE: Project: All See Pipe A description.

14.10.203 TRANSBDATAN2—Offset 6103Ch

Pipe B Data N value 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6103Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Project: All Format: MBZ
23:0	0b RW	PIPE_B_LINK_M2_VALUE: Project: All See Pipe A description.

14.10.207 TRANSBDPLINKN2—Offset 6104Ch

Pipe B Link N value 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 6104Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				PIPE_B_LINK_N2_VALUE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Project: All Format: MBZ
23:0	0b RW	PIPE_B_LINK_N2_VALUE: Project: All See Pipe A description.



14.11 Memory Mapped Registers (2 of 2)

Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
61050–61053h	4	"CRCCTRLREDB—Offset 61050h" on page 652	00000000h
61054–61057h	4	"CRCCTRLGREENB—Offset 61054h" on page 653	00000000h
61058–6105Bh	4	"CRCCTRLBLUEB—Offset 61058h" on page 654	00000000h
6105C–6105Fh	4	"CRCCTRLALPHAB—Offset 6105Ch" on page 655	00000000h
61060–61063h	4	"CRCRESREDB—Offset 61060h" on page 655	00000000h
61064–61067h	4	"CRCRESGREENB—Offset 61064h" on page 656	00000000h
61068–6106Bh	4	"CRCRESBLUEB—Offset 61068h" on page 657	00000000h
6106C–6106Fh	4	"CRCRESALPHAB—Offset 6106Ch" on page 658	00000000h
61070–61073h	4	"CRCCTRLRESIDUE2B—Offset 61070h" on page 658	00000000h
61080–61083h	4	"CRCRESRESIDUAL2B—Offset 61080h" on page 659	00000000h
61090–61093h	4	"PSRCTLB—Offset 61090h" on page 660	00000000h
61094–61097h	4	"PSRSTATB—Offset 61094h" on page 661	00000000h
61098–6109Bh	4	"PSRCRC1B—Offset 61098h" on page 662	00000000h
6109C–6109Fh	4	"PSRCRC2B—Offset 6109Ch" on page 663	00000000h
610A0–610A3h	4	"VSCSDPB—Offset 610A0h" on page 664	00000000h
610B0–610B3h	4	"PIPEBWIDEGAMUTCOLORCORRECTIONC01_C00COEFFICIENTS—Offset 610B0h" on page 665	00000000h
610B4–610B7h	4	"PIPEBWIDEGAMUTCOLORCORRECTIONC02COEFFICIENT—Offset 610B4h" on page 666	00000000h
610B8–610BBh	4	"PIPEBWIDEGAMUTCOLORCORRECTIONC11_C10COEFFICIENTS—Offset 610B8h" on page 666	00000000h
610BC–610BFh	4	"PIPEBWIDEGAMUTCOLORCORRECTIONC12COEFFICIENT—Offset 610BCh" on page 667	00000000h
610C0–610C3h	4	"PIPEBWIDEGAMUTCOLORCORRECTIONC21_C20COEFFICIENTS—Offset 610C0h" on page 668	00000000h
610C4–610C7h	4	"PIPEBWIDEGAMUTCOLORCORRECTIONC22COEFFICIENT—Offset 610C4h" on page 668	00000000h
61100–61103h	4	"ADPA—Offset 61100h" on page 669	00040000h
61104–61107h	4	"CRTIO_DFX—Offset 61104h" on page 672	00008000h
61110–61113h	4	"PORT_HOTPLUG_EN—Offset 61110h" on page 672	00000020h
61114–61117h	4	"PORT_HOTPLUG_STAT—Offset 61114h" on page 675	00000000h
61140–61143h	4	"SDVOHDMIB—Offset 61140h" on page 679	00000018h
61154–61157h	4	"SDVOHDMIB—Offset 61140h" on page 679	00000000h
61160–61163h	4	"HDMIC—Offset 61160h" on page 684	00000018h
61164–61167h	4	"DISPLAY_DIGITAL_PORT_HOT_PLUG_CONTROL_REGISTER—Offset 61164h" on page 688	00000000h
61168–6116Bh	4	"DV_DETERM—Offset 61168h" on page 690	00000000h
61170–61173h	4	"VIDEO_DIP_CTL_B—Offset 61170h" on page 691	20200900h
61174–61177h	4	"VIDEO_DIP_DATA_B—Offset 61174h" on page 693	00000000h



Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
61178–6117Bh	4	"VIDEO_DIP_GDCP_PAYLOAD_B—Offset 61178h" on page 693	00000000h
61190–61193h	4	"MIPIA_PORT_CTRL—Offset 61190h" on page 694	00000000h
61194–61197h	4	"MIPIA_TEARING_CTR—Offset 61194h" on page 697	00000000h
61198–6119Bh	4	"DPA_PIX_GEN_CTRL—Offset 61198h" on page 698	00000000h
611A0–611A3h	4	"MIPIA_AUTOPWG—Offset 611A0h" on page 699	00000000h
611B0–611B3h	4	"DPB_PIX_GEN_CTRL—Offset 611B0h" on page 699	00000000h
61200–61203h	4	"PIPEA_PP_STATUS—Offset 61200h" on page 701	08000000h
61204–61207h	4	"PIPEA_PP_CONTROL—Offset 61204h" on page 702	00000000h
61208–6120Bh	4	"PIPEA_PP_ON_DELAYS—Offset 61208h" on page 704	00000000h
6120C–6120Fh	4	"PIPEA_PP_OFF_DELAYS—Offset 6120Ch" on page 705	00000000h
61210–61213h	4	"PIPEA_PP_DIVISOR—Offset 61210h" on page 706	00270F04h
61230–61233h	4	"PFIT_CONTROL—Offset 61230h" on page 707	20000000h
61234–61237h	4	"PFIT_PGM_RATIOS—Offset 61234h" on page 709	00000000h
61238–6123Bh	4	"RESERVEDUSEDTOBEAUTOSCALINGRATIOSREADBACK—Offset 61238h" on page 710	00000000h
6123C–6123Fh	4	"RESERVEDUSEDTOBESCALINGINITIALPHASE—Offset 6123Ch" on page 710	00000000h
61250–61253h	4	"PIPEA_BLC_PWM_CLT2—Offset 61250h" on page 711	00000000h
61254–61257h	4	"PIPEA_BLC_PWM_CTL—Offset 61254h" on page 712	00000000h
61260–61263h	4	"PIPEA_BLM_HIST_CTL—Offset 61260h" on page 713	00000000h
61264–61267h	4	"PIPEA_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER—Offset 61264h" on page 714	00000000h
61268–6126Bh	4	"PIPEAHISTOGRAMTHRESHOLDGUARDBANDREGISTER—Offset 61268h" on page 715	00000000h
61300–61303h	4	"PIPEB_PP_STATUS—Offset 61300h" on page 716	08000000h
61304–61307h	4	"PIPEB_PP_CONTROL—Offset 61304h" on page 718	00000000h
61308–6130Bh	4	"PIPEB_PP_ON_DELAYS—Offset 61308h" on page 720	00000000h
6130C–6130Fh	4	"PIPEB_PP_OFF_DELAYS—Offset 6130Ch" on page 721	00000000h
61310–61313h	4	"PIPEB_PP_DIVISOR—Offset 61310h" on page 722	00270F04h
61350–61353h	4	"PIPEB_BLC_PWM_CLT2—Offset 61350h" on page 723	00000000h
61354–61357h	4	"PIPEB_BLC_PWM_CTL—Offset 61354h" on page 724	00000000h
61360–61363h	4	"PIPEB_BLM_HIST_CTL—Offset 61360h" on page 725	00000000h
61364–61367h	4	"PIPEB_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER—Offset 61364h" on page 726	00000000h
61368–6136Bh	4	"PIPEBHISTOGRAMTHRESHOLDGUARDBANDREGISTER—Offset 61368h" on page 727	00000000h
61700–61703h	4	"MIPIC_PORT_CTRL—Offset 61700h" on page 728	00000000h
61704–61707h	4	"MIPIC_TEARING_CTR—Offset 61704h" on page 729	00000000h
62000–62003h	4	"AUD_CONFIG_A—Offset 62000h" on page 730	00000000h
62010–62013h	4	"AUD_MISC_CTRL_A—Offset 62010h" on page 731	00000044h
62020–62023h	4	"AUD_VID_DID—Offset 62020h" on page 732	80862882h
62024–62027h	4	"AUD_RID—Offset 62024h" on page 733	00100000h

**Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
62028–6202Bh	4	"AUD_CTS_ENABLE_A—Offset 62028h" on page 734	00000000h
6204C–6204Fh	4	"AUD_PWRST—Offset 6204Ch" on page 735	00FFFFFFh
62050–62053h	4	"AUD_HDMIW_HDMIEDID_A—Offset 62050h" on page 737	00000000h
62054–62057h	4	"AUD_HDMIW_INFOFR_A—Offset 62054h" on page 738	00000000h
6207C–6207Fh	4	"AUD_PORT_EN_HD_CFG—Offset 6207Ch" on page 738	00077003h
62080–62083h	4	"AUD_OUT_DIG_CNVT_A—Offset 62080h" on page 740	00000000h
62084–62087h	4	"AUD_OUT_STR_DESC_A—Offset 62084h" on page 742	00000032h
62088–6208Bh	4	"AUD_OUT_CH_STR—Offset 62088h" on page 743	00000000h
620A8–620ABh	4	"AUD_PINW_CONNLNG_LIST—Offset 620A8h" on page 744	00030202h
620AC–620AFh	4	"AUD_PINW_CONNLNG_SEL—Offset 620ACh" on page 745	00000000h
620B4–620B7h	4	"AUD_CNTL_ST_A—Offset 620B4h" on page 746	00005400h
620C0–620C3h	4	"AUD_CNTL_ST2—Offset 620C0h" on page 748	00000000h
620D4–620D7h	4	"AUD_HDMIW_STATUS—Offset 620D4h" on page 749	00000000h
62100–62103h	4	"AUD_CONFIG_B—Offset 62100h" on page 751	00000000h
62110–62113h	4	"AUD_MISC_CTRL_B—Offset 62110h" on page 752	00000044h
62128–6212Bh	4	"AUD_CTS_ENABLE_B—Offset 62128h" on page 753	00000000h
62150–62153h	4	"AUD_HDMIW_HDMIEDID_B—Offset 62150h" on page 754	00000000h
62154–62157h	4	"AUD_HDMIW_INFOFR_B—Offset 62154h" on page 755	00000000h
62180–62183h	4	"AUD_OUT_DIG_CNVT_B—Offset 62180h" on page 755	00000000h
62184–62187h	4	"AUD_OUT_STR_DESC_B—Offset 62184h" on page 757	00000032h
621B4–621B7h	4	"AUD_CNTL_ST_B—Offset 621B4h" on page 758	00005400h
62F00–62F03h	4	"AUD_SSID_DBG—Offset 62F00h" on page 760	80860101h
62F04–62F07h	4	"AUD_PWST1_DBG—Offset 62F04h" on page 761	00000C0Fh
62F08–62F0Bh	4	"AUD_OUT_STR_DESC_A_DBG—Offset 62F08h" on page 762	00000032h
62F0C–62F0Fh	4	"AUD_OUT_DIG_CNVT_A_DBG—Offset 62F0Ch" on page 763	00000001h
62F14–62F17h	4	"AUD_PWST2_DBG—Offset 62F14h" on page 765	0000000Fh
62F18–62F1Bh	4	"AUD_OUT_STR_DESC_B_DBG—Offset 62F18h" on page 766	00000032h
62F1C–62F1Fh	4	"AUD_OUT_DIG_CNVT_B_DBG—Offset 62F1Ch" on page 767	00000001h
62F20–62F23h	4	"AUD_PORT_EN_B_DBG—Offset 62F20h" on page 769	00000003h
62F24–62F27h	4	"AUD_PWST3_DBG—Offset 62F24h" on page 771	00000003h
62F28–62F2Bh	4	"AUD_PORT_EN_C_DBG—Offset 62F28h" on page 771	00000003h
62F2C–62F2Fh	4	"AUD_PORT_EN_D_DBG—Offset 62F2Ch" on page 773	00000003h
62F38–62F3Bh	4	"AUD_CHICKENBIT_REG—Offset 62F38h" on page 774	00000001h
62F40–62F43h	4	"AUD_OUT_DIG_CNVT_A_DBG—Offset 62F40h" on page 775	00000000h
62F44–62F47h	4	"AUD_OUT_DIG_CNVTB_DBG—Offset 62F44h" on page 776	00000000h
62F60–62F63h	4	"AUD_CNTL_ST_B_DBG—Offset 62F60h" on page 776	00000000h
62F64–62F67h	4	"AUD_HDMIW_INFOFR_B_DBG—Offset 62F64h" on page 777	00000000h
62F70–62F73h	4	"AUD_CNTL_ST_C_DBG—Offset 62F70h" on page 778	00000000h
62F74–62F77h	4	"AUD_HDMIW_INFOFR_C_DBG—Offset 62F74h" on page 779	00000000h



Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
62F80–62F83h	4	"AUD_CNTL_ST_D_DBG—Offset 62F80h" on page 780	00000000h
62F84–62F87h	4	"AUD_HDMIW_INFOFR_D_DBG—Offset 62F84h" on page 781	00000000h
62F88–62F8Bh	4	"AUD_CONFIG_DEFAULT2_REG_PORTB—Offset 62F88h" on page 782	00000000h
62F8C–62F8Fh	4	"AUD_CONFIG_DEFAULT2_REG_PORTC—Offset 62F8Ch" on page 783	00000000h
62F90–62F93h	4	"AUD_CONFIG_DEFAULT2_REG_PORTD—Offset 62F90h" on page 783	00000000h
62F94–62F97h	4	"AUD_MCTSA—Offset 62F94h" on page 784	00000000h
62F98–62F9Bh	4	"AUD_MCTSB—Offset 62F98h" on page 784	00000000h
64100–64103h	4	"DP_B—Offset 64100h" on page 785	00000018h
64110–64113h	4	"DPB_AUX_CH_CTL—Offset 64110h" on page 788	00050000h
64114–64117h	4	"DPB_AUX_CH_DATA1—Offset 64114h" on page 789	00000000h
64118–6411Bh	4	"DPB_AUX_CH_DATA2—Offset 64118h" on page 790	00000000h
6411C–6411Fh	4	"DPB_AUX_CH_DATA3—Offset 6411Ch" on page 791	00000000h
64120–64123h	4	"DPB_AUX_CH_DATA4—Offset 64120h" on page 791	00000000h
64124–64127h	4	"DPB_AUX_CH_DATA5—Offset 64124h" on page 792	00000000h
64130–64133h	4	"DP_AUX_CH_AKSV_HI—Offset 64130h" on page 792	00000000h
64134–64137h	4	"DP_AUX_CH_AKSV_LO—Offset 64134h" on page 793	00000000h
64150–64153h	4	"DPB_AUX_TST—Offset 64150h" on page 794	00000000h
64200–64203h	4	"DP_C—Offset 64200h" on page 796	00000018h
64210–64213h	4	"DPC_AUX_CH_CTL—Offset 64210h" on page 798	00050000h
64214–64217h	4	"DPC_AUX_CH_DATA1—Offset 64214h" on page 800	00000000h
64218–6421Bh	4	"DPC_AUX_CH_DATA2—Offset 64218h" on page 800	00000000h
6421C–6421Fh	4	"DPC_AUX_CH_DATA3—Offset 6421Ch" on page 801	00000000h
64220–64223h	4	"DPC_AUX_CH_DATA4—Offset 64220h" on page 802	00000000h
64224–64227h	4	"DPC_AUX_CH_DATA5—Offset 64224h" on page 802	00000000h
64228–6422Bh	4	"DPC_AUX_TST—Offset 64228h" on page 803	00000000h
65000–65003h	4	"STREAM_A_LPE_AUD_CONFIG—Offset 65000h" on page 805	00000280h
65008–6500Bh	4	"STREAM_A_LPE_AUD_CH_STATUS_0—Offset 65008h" on page 807	00000000h
6500C–6500Fh	4	"STREAM_A_LPE_AUD_CH_STATUS_1—Offset 6500Ch" on page 807	00000000h
65010–65013h	4	"STREAM_A_LPE_AUD_HDMI_CTS_DP_MAUD—Offset 65010h" on page 808	00000000h
65014–65017h	4	"STREAM_A_LPE_AUD_HDMI_N_DP_NAUD—Offset 65014h" on page 809	00000000h
65020–65023h	4	"STREAM_A_LPE_AUD_BUFFER_CONFIG—Offset 65020h" on page 810	00000100h
65024–65027h	4	"STREAM_A_LPE_AUD_BUF_CH_SWP—Offset 65024h" on page 810	00FAC688h
65040–65043h	4	"STREAM_A_LPE_AUD_BUF_A_ADDR—Offset 65040h" on page 812	00000000h
65044–65047h	4	"STREAM_A_LPE_AUD_BUF_A_LENGTH—Offset 65044h" on page 812	00000000h
65048–6504Bh	4	"STREAM_A_LPE_AUD_BUF_B_ADDR—Offset 65048h" on page 813	00000000h
6504C–6504Fh	4	"STREAM_A_LPE_AUD_BUF_B_LENGTH—Offset 6504Ch" on page 814	00000000h
65050–65053h	4	"STREAM_A_LPE_AUD_BUF_C_ADDR—Offset 65050h" on page 814	00000000h
65054–65057h	4	"STREAM_A_LPE_AUD_BUF_C_LENGTH—Offset 65054h" on page 815	00000000h
65058–6505Bh	4	"STREAM_A_LPE_AUD_BUF_D_ADDR—Offset 65058h" on page 815	00000000h




Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
6505C–6505Fh	4	"STREAM_A_LPE_AUD_BUF_D_LENGTH—Offset 6505Ch" on page 816	00000000h
65060–65063h	4	"STREAM_A_LPE_AUD_CNTL_ST—Offset 65060h" on page 817	00000000h
65064–65067h	4	"STREAM_A_LPE_AUD_HDMI_STATUS—Offset 65064h" on page 818	00000000h
65068–6506Bh	4	"STREAM_A_LPE_AUD_HDMIW_INFOFR—Offset 65068h" on page 820	00000000h
65800–65803h	4	"STREAM_B_LPE_AUD_CONFIG—Offset 65800h" on page 821	00000280h
65808–6580Bh	4	"STREAM_B_LPE_AUD_CH_STATUS_0—Offset 65808h" on page 823	00000000h
6580C–6580Fh	4	"STREAM_B_LPE_AUD_CH_STATUS_1—Offset 6580Ch" on page 823	00000000h
65810–65813h	4	"STREAM_B_LPE_AUD_HDMI_CTS_DP_MAUD—Offset 65810h" on page 824	00000000h
65814–65817h	4	"STREAM_B_LPE_AUD_HDMI_N_DP_NAUD—Offset 65814h" on page 825	00000000h
65820–65823h	4	"STREAM_B_LPE_AUD_BUFFER_CONFIG—Offset 65820h" on page 826	00000100h
65824–65827h	4	"STREAM_B_LPE_AUD_BUF_CH_SWP—Offset 65824h" on page 826	00FAC688h
65840–65843h	4	"STREAM_B_LPE_AUD_BUF_A_ADDR—Offset 65840h" on page 828	00000000h
65844–65847h	4	"STREAM_B_LPE_AUD_BUF_A_LENGTH—Offset 65844h" on page 828	00000000h
65848–6584Bh	4	"STREAM_B_LPE_AUD_BUF_B_ADDR—Offset 65848h" on page 829	00000000h
6584C–6584Fh	4	"STREAM_B_LPE_AUD_BUF_B_LENGTH—Offset 6584Ch" on page 830	00000000h
65850–65853h	4	"STREAM_B_LPE_AUD_BUF_C_ADDR—Offset 65850h" on page 830	00000000h
65854–65857h	4	"STREAM_B_LPE_AUD_BUF_C_LENGTH—Offset 65854h" on page 831	00000000h
65858–6585Bh	4	"STREAM_B_LPE_AUD_BUF_D_ADDR—Offset 65858h" on page 831	00000000h
6585C–6585Fh	4	"STREAM_B_LPE_AUD_BUF_D_LENGTH—Offset 6585Ch" on page 832	00000000h
65860–65863h	4	"STREAM_B_LPE_AUD_CNTL_ST—Offset 65860h" on page 833	00000000h
65864–65867h	4	"STREAM_B_LPE_AUD_HDMI_STATUS—Offset 65864h" on page 835	00000000h
65868–6586Bh	4	"STREAM_B_LPE_AUD_HDMIW_INFOFR—Offset 65868h" on page 836	00000000h
70000–70003h	4	"PIPEA_DSL—Offset 70000h" on page 837	00000000h
70004–70007h	4	"PIPEA_SLC—Offset 70004h" on page 838	00000000h
70008–7000Bh	4	"PIPEACONF—Offset 70008h" on page 839	00000000h
70010–70013h	4	"PIPEAGCMAXRED—Offset 70010h" on page 843	00010000h
70014–70017h	4	"PIPEAGCMAXGREEN—Offset 70014h" on page 844	00010000h
70018–7001Bh	4	"PIPEAGCMAXBLUE—Offset 70018h" on page 845	00010000h
70024–70027h	4	"PIPEASTAT—Offset 70024h" on page 846	00000000h
70028–7002Bh	4	"DPFLIPSTAT—Offset 70028h" on page 850	00000000h
7002C–7002Fh	4	"DPINVGT—Offset 7002Ch" on page 852	00000000h
70030–70033h	4	"DSPARB—Offset 70030h" on page 854	80008000h
70034–70037h	4	"FW1—Offset 70034h" on page 855	3F8F0F0Fh
70038–7003Bh	4	"FW2—Offset 70038h" on page 856	0B0F0F0Fh
7003C–7003Fh	4	"FW3—Offset 7003Ch" on page 858	00000000h
70040–70043h	4	"PIPEAFRAMECOUNT—Offset 70040h" on page 859	00000000h
70044–70047h	4	"PIPEAFLIPCOUNTER—Offset 70044h" on page 860	00000000h
70048–7004Bh	4	"PIPEAMSAMISC—Offset 70048h" on page 860	00000000h
70050–70053h	4	"DDL1—Offset 70050h" on page 861	00000000h




Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
70054–70057h	4	"DDL2—Offset 70054h" on page 863	00000000h
70060–70063h	4	"DSPARB2—Offset 70060h" on page 864	00001111h
70064–70067h	4	"DSPHOWM—Offset 70064h" on page 865	00000000h
70068–7006Bh	4	"DSPHOWM1—Offset 70068h" on page 867	00000000h
70070–70073h	4	"FW4—Offset 70070h" on page 869	00040404h
70074–70077h	4	"FW5—Offset 70074h" on page 870	04040404h
70078–7007Bh	4	"FW6—Offset 70078h" on page 871	00000078h
7007C–7007Fh	4	"FW7—Offset 7007Ch" on page 872	040F040Fh
70080–70083h	4	"CURACNTR—Offset 70080h" on page 873	00000000h
70084–70087h	4	"CURABASE—Offset 70084h" on page 874	00000000h
70088–7008Bh	4	"CURAPOS—Offset 70088h" on page 876	00000000h
70090–70093h	4	"CURAPALET_0—Offset 70090h" on page 877	00000000h
70094–70097h	4	"CURAPALET_1—Offset 70094h" on page 878	00000000h
70098–7009Bh	4	"CURAPALET_2—Offset 70098h" on page 878	00000000h
7009C–7009Fh	4	"CURAPALET_3—Offset 7009Ch" on page 879	00000000h
700AC–700AFh	4	"CURLIVEBASE—Offset 700ACh" on page 880	00000000h
700C0–700C3h	4	"CURBCNTR—Offset 700C0h" on page 881	00000000h
700C4–700C7h	4	"CURBBASE—Offset 700C4h" on page 882	00000000h
700C8–700CBh	4	"CURBPOS—Offset 700C8h" on page 884	00000000h
700D0–700D3h	4	"CURBPALET_0—Offset 700D0h" on page 886	00000000h
700D4–700D7h	4	"CURBPALET_1—Offset 700D4h" on page 886	00000000h
700D8–700DBh	4	"CURBPALET_2—Offset 700D8h" on page 887	00000000h
700DC–700DFh	4	"CURBPALET_3—Offset 700DCh" on page 888	00000000h
700EC–700EFh	4	"CURBLIVEBASE—Offset 700ECh" on page 889	00000000h
7017C–7017Fh	4	"DSPAADDR—Offset 7017Ch" on page 890	00000000h
70180–70183h	4	"DSPACNTR—Offset 70180h" on page 891	00000000h
70184–70187h	4	"DSPALINOFF—Offset 70184h" on page 894	00000000h
70188–7018Bh	4	"DSPASTRIDE—Offset 70188h" on page 895	00000000h
70194–70197h	4	"DSPKEYVAL—Offset 70194h" on page 896	00000000h
70198–7019Bh	4	"DSPKEYMSK—Offset 70198h" on page 896	00000000h
7019C–7019Fh	4	"DSPASURF—Offset 7019Ch" on page 897	00000000h
701A4–701A7h	4	"DSPATILEOFF—Offset 701A4h" on page 898	00000000h
701AC–701AFh	4	"DSPASURFLIVE—Offset 701ACh" on page 899	00000000h
70400–70403h	4	"CBR1—Offset 70400h" on page 900	00000000h
70404–70407h	4	"CBR2—Offset 70404h" on page 902	00000000h
70408–7040Bh	4	"CCBR—Offset 70408h" on page 905	00000000h
7040C–7040Fh	4	"CBR3—Offset 7040Ch" on page 905	00000000h
70410–70413h	4	"SWF00—Offset 70410h" on page 907	00000000h
70414–70417h	4	"SWF01—Offset 70414h" on page 907	00000000h



Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
70418–7041Bh	4	"SWF02—Offset 70418h" on page 908	00000000h
7041C–7041Fh	4	"SWF03—Offset 7041Ch" on page 908	00000000h
70420–70423h	4	"SWF04—Offset 70420h" on page 909	00000000h
70424–70427h	4	"SWF05—Offset 70424h" on page 909	00000000h
70428–7042Bh	4	"SWF06—Offset 70428h" on page 910	00000000h
7042C–7042Fh	4	"SWF07—Offset 7042Ch" on page 910	00000000h
70430–70433h	4	"SWF08—Offset 70430h" on page 911	00000000h
70434–70437h	4	"SWF09—Offset 70434h" on page 911	00000000h
70438–7043Bh	4	"SWF0A—Offset 70438h" on page 912	00000000h
7043C–7043Fh	4	"SWF0B—Offset 7043Ch" on page 912	00000000h
70440–70443h	4	"SWF0C—Offset 70440h" on page 913	00000000h
70444–70447h	4	"SWF0D—Offset 70444h" on page 913	00000000h
70448–7044Bh	4	"SWF0E—Offset 70448h" on page 914	00000000h
7044C–7044Fh	4	"SWF0F—Offset 7044Ch" on page 914	00000000h
70450–70453h	4	"CBR4—Offset 70450h" on page 915	00000000h
71000–71003h	4	"PIPEB_DSL—Offset 71000h" on page 917	00000000h
71004–71007h	4	"PIPEB_SLC—Offset 71004h" on page 918	00000000h
71008–7100Bh	4	"PIPEBCONF—Offset 71008h" on page 919	00000000h
71010–71013h	4	"PIPEBGCMAXRED—Offset 71010h" on page 922	00010000h
71014–71017h	4	"PIPEBGCMAXGREEN—Offset 71014h" on page 923	00010000h
71018–7101Bh	4	"PIPEBGCMAXBLUE—Offset 71018h" on page 923	00010000h
71024–71027h	4	"PIPEBSTAT—Offset 71024h" on page 924	00000000h
71040–71043h	4	"PIPEBFRAMECOUNT—Offset 71040h" on page 928	00000000h
71044–71047h	4	"PIPEBFLIPCOUNT—Offset 71044h" on page 928	00000000h
71048–7104Bh	4	"PIPEBMSAMISC—Offset 71048h" on page 929	00000000h
7117C–7117Fh	4	"DSPBADDR—Offset 7117Ch" on page 930	00000000h
71180–71183h	4	"DSPBCNTR—Offset 71180h" on page 932	01000000h
71184–71187h	4	"DSPBLINOFFSET—Offset 71184h" on page 934	00000000h
71188–7118Bh	4	"DSPBSTRIDE—Offset 71188h" on page 935	00000000h
71194–71197h	4	"DSPBKEYVAL—Offset 71194h" on page 936	00000000h
71198–7119Bh	4	"DSPBKEYMSK—Offset 71198h" on page 937	00000000h
7119C–7119Fh	4	"DSPBSURF—Offset 7119Ch" on page 937	00000000h
711A4–711A7h	4	"DSPBTILEOFF—Offset 711A4h" on page 939	00000000h
711AC–711AFh	4	"DSPBSURFLIVE—Offset 711ACh" on page 940	00000000h
71200–71203h	4	"DSPBFLPQSTAT—Offset 71200h" on page 940	00000000h
71400–71403h	4	"VGACNTRL—Offset 71400h" on page 941	00000000h
71410–71413h	4	"SWF10—Offset 71410h" on page 944	00000000h
71414–71417h	4	"SWF11—Offset 71414h" on page 945	00000000h
71418–7141Bh	4	"SWF12—Offset 71418h" on page 945	00000000h




Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
7141C–7141Fh	4	"SWF13—Offset 7141Ch" on page 946	00000000h
71420–71423h	4	"SWF14—Offset 71420h" on page 946	00000000h
71424–71427h	4	"SWF15—Offset 71424h" on page 947	00000000h
71428–7142Bh	4	"SWF16—Offset 71428h" on page 947	00000000h
7142C–7142Fh	4	"SWF17—Offset 7142Ch" on page 948	00000000h
71430–71433h	4	"SWF18—Offset 71430h" on page 948	00000000h
71434–71437h	4	"SWF19—Offset 71434h" on page 949	00000000h
71438–7143Bh	4	"SWF1A—Offset 71438h" on page 949	00000000h
7143C–7143Fh	4	"SWF1B—Offset 7143Ch" on page 950	00000000h
71440–71443h	4	"SWF1C—Offset 71440h" on page 950	00000000h
71444–71447h	4	"SWF1D—Offset 71444h" on page 951	00000000h
71448–7144Bh	4	"SWF1E—Offset 71448h" on page 951	00000000h
7144C–7144Fh	4	"SWF1F—Offset 7144Ch" on page 952	00000000h
72180–72183h	4	"SPACNTR—Offset 72180h" on page 952	00000000h
72184–72187h	4	"SPALINOFF—Offset 72184h" on page 955	00000000h
72188–7218Bh	4	"SPASTRIDE—Offset 72188h" on page 956	00000000h
7218C–7218Fh	4	"SPAPOS—Offset 7218Ch" on page 956	00000000h
72190–72193h	4	"SPASIZE—Offset 72190h" on page 957	00000000h
72194–72197h	4	"SPAKEYMINVAL—Offset 72194h" on page 958	00000000h
72198–7219Bh	4	"SPAKEYMSK—Offset 72198h" on page 959	00000000h
7219C–7219Fh	4	"SPASURF—Offset 7219Ch" on page 959	00000000h
721A0–721A3h	4	"SPAKEYMAXVAL—Offset 721A0h" on page 961	00000000h
721A4–721A7h	4	"SPATILEOFF—Offset 721A4h" on page 962	00000000h
721A8–721ABh	4	"SPACONTALPHA—Offset 721A8h" on page 963	00000000h
721AC–721AFh	4	"SPALIVESURF—Offset 721ACh" on page 963	00000000h
721D0–721D3h	4	"SPACLRC0—Offset 721D0h" on page 965	01000000h
721D4–721D7h	4	"SPACLRC1—Offset 721D4h" on page 966	00000080h
721E0–721E3h	4	"SPAGAMC5—Offset 721E0h" on page 967	00C0C0C0h
721E4–721E7h	4	"SPAGAMC4—Offset 721E4h" on page 968	00808080h
721E8–721EBh	4	"SPAGAMC3—Offset 721E8h" on page 968	00404040h
721EC–721EFh	4	"SPAGAMC2—Offset 721ECh" on page 969	00202020h
721F0–721F3h	4	"SPAGAMC1—Offset 721F0h" on page 970	00101010h
721F4–721F7h	4	"SPAGAMC0—Offset 721F4h" on page 970	00080808h
72280–72283h	4	"SPBCNTR—Offset 72280h" on page 971	00000000h
72284–72287h	4	"SPBLINOFF—Offset 72284h" on page 974	00000000h
72288–7228Bh	4	"SPBSTRIDE—Offset 72288h" on page 974	00000000h
7228C–7228Fh	4	"SPBPOS—Offset 7228Ch" on page 975	00000000h
72290–72293h	4	"SPBSIZE—Offset 72290h" on page 976	00000000h
72294–72297h	4	"SPBKEYMINVAL—Offset 72294h" on page 976	00000000h

**Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
72298–7229Bh	4	"SPBKEYMSK—Offset 72298h" on page 977	00000000h
7229C–7229Fh	4	"SPBSURF—Offset 7229Ch" on page 978	00000000h
722A0–722A3h	4	"SPBKEYMAXVAL—Offset 722A0h" on page 979	00000000h
722A4–722A7h	4	"SPBTILEOFF—Offset 722A4h" on page 980	00000000h
722A8–722ABh	4	"SPBCONTALPHA—Offset 722A8h" on page 981	00000000h
722AC–722AFh	4	"SPBLIVESURF—Offset 722ACh" on page 982	00000000h
722D0–722D3h	4	"SPBCLRC0—Offset 722D0h" on page 983	01000000h
722D4–722D7h	4	"SPBCLRC1—Offset 722D4h" on page 984	00000080h
722E0–722E3h	4	"SPBGAMC5—Offset 722E0h" on page 985	00C0C0C0h
722E4–722E7h	4	"SPBGAMC4—Offset 722E4h" on page 986	00808080h
722E8–722EBh	4	"SPBGAMC3—Offset 722E8h" on page 986	00404040h
722EC–722EFh	4	"SPBGAMC2—Offset 722ECh" on page 987	00202020h
722F0–722F3h	4	"SPBGAMC1—Offset 722F0h" on page 988	00101010h
722F4–722F7h	4	"SPBGAMC0—Offset 722F4h" on page 988	00080808h
72380–72383h	4	"SPCCNTR—Offset 72380h" on page 989	00000000h
72384–72387h	4	"SPCLINOFF—Offset 72384h" on page 992	00000000h
72388–7238Bh	4	"SPCSTRIDE—Offset 72388h" on page 992	00000000h
7238C–7238Fh	4	"SPCPOS—Offset 7238Ch" on page 993	00000000h
72390–72393h	4	"SPCSIZE—Offset 72390h" on page 994	00000000h
72394–72397h	4	"SPCKEYMINVAL—Offset 72394h" on page 994	00000000h
72398–7239Bh	4	"SPCKEYMSK—Offset 72398h" on page 995	00000000h
7239C–7239Fh	4	"SPCSURF—Offset 7239Ch" on page 996	00000000h
723A0–723A3h	4	"SPCKEYMAXVAL—Offset 723A0h" on page 997	00000000h
723A4–723A7h	4	"SPCTILEOFF—Offset 723A4h" on page 998	00000000h
723A8–723ABh	4	"SPCCONTALPHA—Offset 723A8h" on page 999	00000000h
723AC–723AFh	4	"SPCLIVESURF—Offset 723ACh" on page 1000	00000000h
723D0–723D3h	4	"SPCCLRC0—Offset 723D0h" on page 1001	01000000h
723D4–723D7h	4	"SPCCLRC1—Offset 723D4h" on page 1002	00000080h
723E0–723E3h	4	"SPCGAMC5—Offset 723E0h" on page 1003	00C0C0C0h
723E4–723E7h	4	"SPCGAMC4—Offset 723E4h" on page 1004	00808080h
723E8–723EBh	4	"SPCGAMC3—Offset 723E8h" on page 1004	00404040h
723EC–723EFh	4	"SPCGAMC2—Offset 723ECh" on page 1005	00202020h
723F0–723F3h	4	"SPCGAMC1—Offset 723F0h" on page 1006	00101010h
723F4–723F7h	4	"SPCGAMC0—Offset 723F4h" on page 1006	00080808h
72414–72417h	4	"SWF30—Offset 72414h" on page 1007	00000000h
72418–7241Bh	4	"SWF31—Offset 72418h" on page 1007	00000000h
7241C–7241Fh	4	"SWF32—Offset 7241Ch" on page 1008	00000000h
72480–72483h	4	"SPDCNTR—Offset 72480h" on page 1008	00000000h
72484–72487h	4	"SPDLINOFF—Offset 72484h" on page 1011	00000000h



Table 173. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
72488–7248Bh	4	"SPDSTRIDE—Offset 72488h" on page 1012	00000000h
7248C–7248Fh	4	"SPDPOS—Offset 7248Ch" on page 1012	00000000h
72490–72493h	4	"SPDSIZE—Offset 72490h" on page 1013	00000000h
72494–72497h	4	"SPDKEYMINVAL—Offset 72494h" on page 1014	00000000h
72498–7249Bh	4	"SPDKEYMSK—Offset 72498h" on page 1015	00000000h
7249C–7249Fh	4	"SPDSURF—Offset 7249Ch" on page 1015	00000000h
724A0–724A3h	4	"SPDKEYMAXVAL—Offset 724A0h" on page 1017	00000000h
724A4–724A7h	4	"SPDTILEOFF—Offset 724A4h" on page 1018	00000000h
724A8–724ABh	4	"SPDONTALPHA—Offset 724A8h" on page 1019	00000000h
724AC–724AFh	4	"SPDLIVESURF—Offset 724ACh" on page 1019	00000000h
724D0–724D3h	4	"SPDCLRC0—Offset 724D0h" on page 1021	01000000h
724D4–724D7h	4	"SPDCLRC1—Offset 724D4h" on page 1022	00000080h
724E0–724E3h	4	"SPDGAMC5—Offset 724E0h" on page 1023	00C0C0C0h
724E4–724E7h	4	"SPDGAMC4—Offset 724E4h" on page 1024	00808080h
724E8–724EBh	4	"SPDGAMC3—Offset 724E8h" on page 1024	00404040h
724EC–724EFh	4	"SPDGAMC2—Offset 724ECh" on page 1025	00202020h
724F0–724F3h	4	"SPDGAMC1—Offset 724F0h" on page 1026	00101010h
724F4–724F7h	4	"SPDGAMC0—Offset 724F4h" on page 1026	00080808h
73000–73003h	4	"PCSRC—Offset 73000h" on page 1027	00000000h
73004–73007h	4	"PCSTAT—Offset 73004h" on page 1029	00000000h
73008–7300Bh	4	"PCSRC2—Offset 73008h" on page 1031	00000000h
7300C–7300Fh	4	"PCSTAT2—Offset 7300Ch" on page 1033	00000000h

14.11.1 CRCCTRLREDB—Offset 61050h

Pipe B CRC Color Control Register (Red)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61050h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Pipe B CRC Color Control Register

Access Method

Offset: [GTTMMADR_LSB + 180000h] + 61058h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

Intel Atom® Processor E3800 Product Family
Datasheet
654



Access Method

Offset: [GTTMMADR LSB + 180000h] + 61064h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

October 2018
Document Number: 538136, Rev. 4.3

14.11.7 CRCRESBLUEB—Offset 61068h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				EXPECTED_CRC_VALUE				

Bit Range	Default & Access	Field Name (ID): Description
31:23	0b RW	RESERVED: Write as zero
22:0	0b RW	EXPECTED_CRC_VALUE: Expected CRC Value for the Color Channel. This is the value used to generate the CRC error status and interrupt. Resultant CRC values are compared to this register after the completion of a CRC calculation. The status bit is in the PIPEBSTAT register.

14.11.10 CRCRESRESIDUAL2B—Offset 61080h

Pipe B CRC Result Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61080h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				COLOR_CHANNEL_CRC_RESULT_VALUE				

Bit Range	Default & Access	Field Name (ID): Description
31:23	0b RO	RESERVED: Read only



Pipe B PSR status register

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 61094h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0							
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0							
DISPLAY_LOCAL_STANDBY_STATE				RESERVED				REPEAT_FRAME_COUNTER				RESERVED_1				SDP_SENT				PSR_IN_TRANSITION				RESERVED_2				PSR_LAST_STATE				PSR_CURRENT_STATE							



Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RO	DISPLAY_LOCAL_STANDBY_STATE: :00: D0 idle state, fetch frame buffer from system memory 01: D0i1 not defined in VLVP 02: D0i2 PSR is active, display controller is trunk gated 03: D0i3 PSR is active, display controller is power gated
29:24	0b RO	RESERVED: Reserved.
23:16	0b RO	REPEAT_FRAME_COUNTER: : Number of identical frames has been sent by display controller. Value is not roll over at 255.
15:9	0b RO	RESERVED_1: Reserved.
8	0b RO	SDP_SENT: it indicates if SDP packet has been sent in current frame.
7	0b RO	PSR_IN_TRANSITION: There is a period that source already committed to PSR active but sink did not. SW should not change the source state at this time but wait until this status bit is clear. The wait time should in the range of 120-250us in the worst case.
6	0b RO	RESERVED_2: Reserved.
5:3	0b RO	PSR_LAST_STATE: indicate last source state that VLVP PSR state machine were in (debug) 000: PSR_disabled 001: PSR_inactive 010: PSR_transition_to_active 011: PSR_active no RFB update 100: PSR_active single frame update 101: PSR_exit
2:0	0b RO	PSR_CURRENT_STATE: indicate current source state that VLVP PSR state machine are in 000: PSR_disabled 001: PSR_inactive 010: PSR_transition_to_active 011: PSR_active no RFB update 100: PSR_active single frame update 101: PSR_exit

14.11.13 PSRCRC1B—Offset 61098h

Pipe B PSR CRC1 register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61098h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RO	CRC_VALUE_BITS_15_0_OF_R_COMPONENT: crc values bits 15 to 0 of Red component
15:1	0b RO	RESERVED: Reserved.
0	0b RO	CRC_VALID: CRC calculation complete and valid for previous frame.

14.11.14 PSRCRC2B—Offset 6109Ch

Pipe B PSR CRC2 register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6109Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Access Method

Offset: [GTTMMADR_LSB + 180000h] + 610A0h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

[illegible]



14.11.20 PIPEBWIDEGAMUTCOLORCORRECTIONC21_C20COEFFICIENTS— Offset 610C0h

Refer to the description of register
PIPEBWIDEGAMUTCOLORCORRECTIONC01_C00COEFFICIENTS.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 610C0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED	C21_COEFFICIENT				RESERVED_1	C20_COEFFICIENT		

Bit Range	Default & Access	Field Name (ID): Description
31:28	0b RW	RESERVED: Reserved.
27:16	0b RW	C21_COEFFICIENT: 12-bit 2 s complement signed value that is programmed for linea. The range of the value can be from -1.999 to +1.999.
15:12	0b RW	RESERVED_1: Reserved.
11:0	0b RW	C20_COEFFICIENT: 12-bit 2 s complement signed value that is programmed for linea. The range of the value can be from -1.999 to +1.999.

14.11.21 PIPEBWIDEGAMUTCOLORCORRECTIONC22COEFFICIENT— Offset 610C4h

Refer to the description of register
PIPEBWIDEGAMUTCOLORCORRECTIONC01_C00COEFFICIENTS.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 610C4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.11.22 ADPA—Offset 61100h

Access Method


Offset: [GTTMMADR_LSB + 180000h] + 61100h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00040000h

Intel Atom® Processor E3800 Product Family
Datasheet
669



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	Analog_DisplayPort_Enable: Project: All Default Value: 0b This bit enables or disables the analog port CRT DAC and syncs outputs. Value Name Description Project 0b Disable Disable the analog port DAC and disable output of syncs All 1b Enable Enable the analog port DAC and enable output of syncs All
30	0b RW	Pipe_Select: Project: All Default Value: 0b Determines which pipe output will feed this DAC port. Value Name Description Project 0b Pipe A Pipe A All 1b Pipe B Pipe B All
29:26	0b RW	Reserved: Project: All Format:
25:24	0b RO	CRT_Hot_Plug_Detection_Channel_Status: Project: All AccessType: Read Only Default Value: 00b These bits are set when a CRT hot plug or unplug event has been detected and indicate which color channels were attached. Write a one to these bits to clear the status. The rising or falling edges of these bits are ORed together to go to the main ISR CRT hot plug register bit. Value Name Description Project 00b None No channels attached All 01b Blue Blue channel only is attached All 10b Green Green channel only is attached All 11b Both Both blue and green channel attached All
23	0b RW	CRT_Hot_Plug_Detection_Enable: Project: All Default Value: 0b Hot plug detection is used to set status bits or an interrupt on the connection or disconnection of a CRT to the analog display port. Value Name Description Project 0b Disable CRT hot plug detection is disabled All 1b Enable CRT hot plug detection is enabled All
22	0b RW	CRT_Hot_Plug_Circuit_Activation_Period: Project: All Default Value: 0b This bit sets the activation period for the CRT hot plug circuit. Value Name Description Project 0b 64 cdclk 64 cdclk periods All 1b 128 cdclk 128 cdclk periods All
21	0b RW	CRT_Hot_Plug_Detect_Warmup_Time: Project: All Default Value: 0b This bit sets the warmup time for the CRT hot plug circuit. Value Name Description Project 0b 2M pcdclks 2M pcdclks warmup (approximately 5ms) All 1b 4M pcdclks 4M pcdclks warmup (approximately 10ms) All
20	0b RW	CRT_Hot_Plug_Detect_Sampling_Period: Project: All Default Value: 0b This bit determines the length of time between sampling periods when the transcoder is disabled. Value Name Description Project 0b 1G pcdclks 1G pcdclks (approximately 2 seconds) All 1b 2G pcdclks 2G pcdclks (approximately 4 seconds) All
19:18	01b RW	CRT_Hot_Plug_Voltage_Compare_Value: Project: All Default Value: 01b A0 Compare value for Vref to determine whether the analog port is connected to a CRT. Value Name Description Project 00b 80 80 All 01b A0 A0 (Default) All 10b C0 C0 All 11b E0 E0 (bit 17 must be = 1) All




Bit Range	Default & Access	Field Name (ID): Description
17	0b RW	CRT_Hot_Plug_Reference_Voltage: Project: All Default Value: 0b Value Name Description Project 0b 325mv 325mv All 1b 475mv 475mv (bits 19:18 must be = 11) All
16	0b RW	Force_CRT_Hot_Plug_Detect_Trigger: Project: All Default Value: 0b Triggers a CRT hotplug/unplug detection cycle independent of the hot plug detection enable bit. This bit is automatically cleared after the detection is completed. The result of this trigger is reflected in the CRT Hot Plug Detection Status. Software must reset status after a force CRT detect trigger. Value Name Description Project 0b No Trigger No Trigger All 1b Force Trigger Force Trigger All
15:10	0b RW	Reserved_1: Project: All Format:
9:5	0b RW	CRTFullScaleOutputVoltageTrimmingControl: Project: All Default Value: 0b This controls CRT output voltage trimming to ensure the output voltage is within VESA spec.
4	0b RW	VSYNC_Polarity_Control: Project: All Default Value: 0b The output VSYNC polarity is controlled by this bit. This is used to implement display modes that require inverted polarity syncs and to set the disabled state of the VSYNC signal. Value Name Description Project 0b Low Active Low All 1b High Active High All
3	0b RW	HSYNC_Polarity_Control: Project: All Default Value: 0b The output HSYNC polarity is controlled by this bit. This is used to implement display modes that require inverted polarity syncs and to set the disabled state of the HSYNC signal. Value Name Description Project 0b Low Active Low All 1b High Active High All
2	0b RW	Reserved_2: Project: All Forma
1	0b RW	Reserved_3: Project: All Forma Monochrome Enable: [DevVLVP] If the CRT display is a monochrom type, SW driver shall set this bit to enable the CRT circuit to drive only the green channel to CRT and gate off the red and blue channels. 0 = Monochrome disabled (default) 1 = Monochrome enabled
0	0b RW	Reserved_4: Project: All Forma Monochrome Enable: [DevVLVP] If the CRT display is a monochrom type, SW driver shall set this bit to enable the CRT circuit to drive only the green channel to CRT and gate off the red and blue channels. 0 = Monochrome disabled (default) 1 = Monochrome enabled 0 = 1.35V is used for analog supply voltage (default) 1 = 1.25V is used for analog supply voltage



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED	DISPLAYPORT_HDMI_B_HOT_PLUG_INTERRUPT_DETECT_ENABLE	DISPLAYPORT_HDMI_C_HOT_PLUG_INTERRUPT_DETECT_ENABLE	DISPLAYPORT_HDMI_D_HOT_PLUG_INTERRUPT_DETECT_ENABLE	SDVOB_HOT_PLUG_INTERRUPT_DETECT_ENABLE	SDVOC_HOT_PLUG_INTERRUPT_DETECT_ENABLE	PIPE_A_AUDIO_INTERRUPT_DETECT_ENABLE	PIPE_B_AUDIO_INTERRUPT_DETECT_ENABLE	RESERVED_1
								RESERVED_2
				DP_HOTPLUG_SHORT_PULSE_DURATION				RESERVED_3
						RESERVED_4	RESERVED_5	RESERVED_6
						RESERVED_7	RESERVED_8	RESERVED_9
							RESERVED_10	RESERVED_11

Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	RESERVED: mbz
29	0b RW	DISPLAYPORT_HDMI_B_HOT_PLUG_INTERRUPT_DETECT_ENABLE: [DevCDV, DevCTG, DevELK] This will enable the consideration of the hot plug interrupt status bit for DisplayPort B in the Port Hotplug Status register, offset 61114h. Please note that software must set this bit at boot in order to detect the HPD input buffer live state. Since setting this bit may generate an interrupt, it must not be cleared and reset as part of interrupt processing. 0 = DisplayPort or HDMIB Hot Plug Detect Disabled (Default) 1 = DisplayPort or HDMIB Hot Plug Detect Enabled
28	0b RW	DISPLAYPORT_HDMI_C_HOT_PLUG_INTERRUPT_DETECT_ENABLE: [DevCDV, DevCTG, DevELK] This will enable the consideration of the hot plug interrupt status bit for DisplayPort C in the Port Hotplug Status register, offset 61114h. Please note that software must set this bit at boot in order to detect the HPD input buffer live state. Since setting this bit may generate an interrupt, it must not be cleared and reset as part of interrupt processing. 0 = DisplayPort or HDMIC Hot Plug Detect Disabled (Default) 1 = DisplayPort or HDMIC Hot Plug Detect Enabled
27	0b RW	DISPLAYPORT_HDMI_D_HOT_PLUG_INTERRUPT_DETECT_ENABLE: [DevCTG] This will enable the consideration of the hot plug interrupt status bit for DisplayPort D in the Port Hotplug Status register, offset 61114h. Please note that software must set this bit at boot in order to detect the HPD input buffer live state. Since setting this bit may generate an interrupt, it must not be cleared and reset as part of interrupt processing. 0 = DisplayPort or HDMID Hot Plug Detect Disabled (Default) 1 = DisplayPort or HDMID Hot Plug Detect Enabled
26	0b RW	SDVOB_HOT_PLUG_INTERRUPT_DETECT_ENABLE: [DevCTG] This will enable the consideration of the hot plug interrupt status bit in the Port Hotplug Status register, offset 61114h. This bit enables detection on the SDVOB interrupt input pin pair. 0 = SDVOB Hot Plug Detect Disabled (Default) 1 = SDVOB Hot Plug Detect Enabled



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	SDVOC_HOT_PLUG_INTERRUPT_DETECT_ENABLE: [DevCTG] This will enable the consideration of the hot plug interrupt status bit in the Port Hotplug Status register, offset 61114h. This bit enables detection on the SDVOC interrupt input pin pair. 0 = SDVOC Hot Plug Detect Disabled (Default) 1 = SDVOC Hot Plug Detect Enabled
24	0b RW	PIPE_A_AUDIO_INTERRUPT_DETECT_ENABLE: [DevCDV, DevCL, DevCTG, DevVLVP] This bit enables consideration of the pipe A audio interrupt status bit in the Port Hotplug Status Register, offset 61114h. It relates to the HDMI port that has audio enabled and can only be used in combination with TMDS encoding. This bit is only to be used for integrated HDMI. 0 = Audio interrupt detect disabled (Default) 1 = Audio interrupt detect enabled
23	0b RW	PIPE_B_AUDIO_INTERRUPT_DETECT_ENABLE: [DevVLVP] This bit enables consideration of the pipe B audio interrupt status bit in the Port Hotplug Status Register, offset 61114h. It relates to the HDMI port that has audio enabled and can only be used in combination with TMDS encoding. This bit is only to be used for integrated HDMI. 0 = Audio interrupt detect disabled (Default) 1 = Audio interrupt detect enabled
22:19	0b RW	RESERVED_1: mbz
18	0b RW	RESERVED_2: [DevVLVP] MBZ TV Hot Plug Detect Interrupt Enable: [DevCL, DevCTG] This will enable the consideration of the TV hot plug interrupt status bit. 0 = TV Hot Plug Detect Disabled (bit 10 of the port hotplug status register no longer detects interrupts, Default) 1 = TV Hot Plug Detect Enabled
17:16	0b RW	DP_HOTPLUG_SHORT_PULSE_DURATION: [DevCDV, DevCTG, DevELK] These bits define the duration of the pulse defined as a short pulse for DisplayPort ports. Pulse less than this value is detected short pulse. Pulse larger than this value is detected long pulse. For DP, this shall use 2ms as threshold. 00 = 2mS (Default) 01 = 4.5mS 10 = 6mS 11 = 100mS
15:10	0b RW	RESERVED_3: mbz
9	0b RW	RESERVED_4: [DevVLVP] MBZ. This bit is the same as bit 23 in 61100h [DevCDV, DevCTG, DevBW, DevCL, DevBLC] CRT Hot plug Interrupt Enable: Hotplug detection is used to cause an interrupt or status bit based on the connection or disconnection of a CRT to the analog video connection. 0 = No hot plug interrupt is enabled (Default) 1 = Hot plug detection is enabled
8	0b RW	RESERVED_5: [DevVLVP] MBZ. This bit is the same as bit 22 in 61100h [DevCDV, DevCTG] CRT Hot plug Circuit Activation Period: This bit sets the activation period for the CRT hot plug circuit detection. Setting this bit to 1 is required for the correct operation of CRT DAC detection. 0 = 32 cdclk periods (Default) 1 = 64 cdclk periods
7	0b RW	RESERVED_6: [DevVLVP] MBZ. This bit is the same as bit 21 in 61100h [DevCDV, DevCTG, DevBW, DevCL, DevBLC] CRT DAC on time Value: Powerup time for 0 = CRT DAC requires 2M cdclks for warmup (Default) 1 = CRT DAC requires 4M cdclks for warmup



Bit Range	Default & Access	Field Name (ID): Description
6:5	01b RW	RESERVED_7: [DevVLVP] MBZ. This bit is the same as bit 19:18 in 61100h [DevCDV, DevCTG, DevBW, DevCL, DevBLC] CRT Hot plug Voltage Compare Value: Compare value for CRT hotplug detect Vref to determine whether the analog port is connected to a CRT. The voltage is forced at the beginning of the active region of the screen every 2 seconds. 00 = A0, 01 = B0, (Default) 10 = C0 11 = D0
4	0b RW	RESERVED_8: [DevVLVP] MBZ. This bit is the same as bit 20 in 61100h [DevCDV, DevCTG, DevBW, DevCL, DevBLC] CRT Hot Plug Detect Delay: This bit determines the length of time between polling periods when the DAC/pipe are disabled 0 = 1G cdcclk 1 = 2G cdcclk
3	0b RW	RESERVED_9: [DevVLVP] MBZ [DevCDV, DevCTG, DevBW, DevCL, DevBLC] Force CRT detect trigger: Triggers a CRT hotplug/unplug detection cycle independent of the interrupt enable bit. Bits 5:8 of this register must be correctly programmed when forcing a trigger. This bit is automatically cleared after the detection is completed. The result of this trigger is reflected in bits 9:8 of the port hotplug interrupt status register. The CRT interrupt status bit #11 in the hot plug status register (61114) will get set the first time Force CRC detect trigger is used after reset. Software must reset status after a force CRT detect trigger. 0 = No trigger (Default) 1 = Trigger
2	0b RW	RESERVED_10: [DevVLVP] MBZ. This bit is the same as bit 17 in 61100h [DevCTG-B] CRT DAC hot plug detection reference voltage selection: 0 = 325mv, bits[6:5] should be set to 01 (Default) 1 = 475mv, bits[6:5] should be set to 11
1:0	0b RW	RESERVED_11: mbz

14.11.25 PORT_HOTPLUG_STAT—Offset 61114h

CRT port control (dprrega.v porthotst_aR)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61114h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h




31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED	DISPLAYPORT_HDMIB_HOT_PLUG_INPUT_BUFFER_LIVE_STATE	DISPLAYPORT_HDMIC_HOT_PLUG_INPUT_BUFFER_LIVE_STATE	DISPLAYPORTD_HOT_PLUG_INPUT_BUFFER_LIVE_STATE	RESERVED_1	PIPE_B_AUDIO_INTERRUPT_LIVE_STATE	DISPLAYPORT_D_HOT_PLUG_INTERRUPT_DETECT_STATUS	DISPLAYPORT_C_HOT_PLUG_INTERRUPT_DETECT_STATUS	DISPLAYPORT_B_HOT_PLUG_INTERRUPT_DETECT_STATUS
					PIPE_A_AUDIO_INTERRUPT_LIVE_STATE	DIGITAL_PORT_B_AUDIO_REQUEST_LIVE_STATE	DIGITAL_PORT_C_AUDIO_REQUEST_LIVE_STATE	RESERVED_2
						CRT_HOT_PLUG_INTERRUPT_STATUS	TV_HOT_PLUG_INTERRUPT_STATUS	RESERVED_3
								RESERVED_4
						DISPLAYPORT_D_AUX_INTERRUPT_STATUS	DISPLAYPORT_C_AUX_INTERRUPT_STATUS	DISPLAYPORT_B_AUX_INTERRUPT_STATUS
						SDVO_C_HOT_PLUG_INTERRUPT_DETECT_STATUS	SDVO_B_HOT_PLUG_INTERRUPT_DETECT_STATUS	PIPE_A_AUDIO_INTERRUPT_DETECT_STATUS
								PIPE_B_AUDIO_INTERRUPT_DETECT_STATUS

Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	RESERVED: mbz
29	0b RO	DISPLAYPORT_HDMIB_HOT_PLUG_INPUT_BUFFER_LIVE_STATE: [DevCDV, DevCTG, DevELK] This bit is read-only. It reflects the real-time state of the of the hot plug input (HPD pin) on DisplayPort or HDMI B when bit 29 of the hotplug enable register, offset 61110h is set. This pin signal is active high. This does not feed into the first line interrupt status register. This bit should be read to confirm cable connection prior to attempting EDID read. 1 = HPD detected active 0 = HPD detected inactive AccessType: Read Only
28	0b RO	DISPLAYPORT_HDMIC_HOT_PLUG_INPUT_BUFFER_LIVE_STATE: [DevCDV, DevCTG, DevELK] This bit is read-only. It reflects the real-time state of the of the hot plug input (HPD pin) on DisplayPortC when bit of this register is set. This pin signal is active high. This does not feed into the first line interrupt status register. This bit should be read to confirm cable connection prior to attempting EDID read. 1 = HPD detected high 0 = HPD detected low AccessType: Read Only
27	0b RO	DISPLAYPORTD_HOT_PLUG_INPUT_BUFFER_LIVE_STATE: [DevCTG] This bit is read-only. It reflects the real-time state of the of the hot plug input (HPD pin) on DisplayPortD when bit of this register is set. This pin signal is active high. This does not feed into the first line interrupt status register. Please note that port D is intended for LFP use and therefore HPD may not be present. Bit 2 of the DPD control register must therefore be read to determine whether DPD is used in the system. 1 = HPD detected high 0 = HPD detected low AccessType: Read Only
26:24	0b RW	RESERVED_1: mbz



Bit Range	Default & Access	Field Name (ID): Description
23	0b RO	PIPE_B_AUDIO_INTERRUPT_LIVE_STATE: [DevVLVP] This read-only bit is used only in ports that use TMDS encoding. It reflects the state of the pipe B audio interrupt request for HDCP when bit 1 of this register is set. This pin signal is active high. It does not feed into the first line interrupt status register. 1 = HDCP invocation requested from audio 0 = HDCP disable requested from audio AccessType: Read Only
22:21	0b RW/1C	DISPLAYPORT_D_HOT_PLUG_INTERRUPT_DETECT_STATUS: [DevCTG] This reflects hot plug interrupt status on DisplayPort D. Graphics software must write a one to these bits to clear the status. This bit is used for either monitor hotplug/unplug or for notification of a sink event. This bit feeds into the first line interrupt status register when bit 27 of the hotplug enable status register is set. 00 = DisplayPort D Hot Plug event not detected 1x = DisplayPort D long pulse Hot Plug event detected X1 = DisplayPort D short pulse Hot Plug event detected AccessType: One to Clear
20:19	0b RW/1C	DISPLAYPORT_C_HOT_PLUG_INTERRUPT_DETECT_STATUS: [DevCDV, DevCTG, DevELK] This reflects hot plug interrupt status on DisplayPort or HDMI C. Graphics software must write a one to these bits to clear the status. This bit is used for either monitor hotplug/unplug or for notification of a sink event. This bit feeds into the first line interrupt status register when bit 28 of the hotplug enable status register is set. Please note that these bits should be considered in conjunction with bit 28, the hot plug input buffer live state, when determining further action: if bit 28 = 0, the bits should be cleared and the port must be disabled. 00 = DisplayPort/HDMI C Hot Plug event not detected 1x = DisplayPort/HDMI C long pulse Hot Plug event detected X1 = DisplayPort C short pulse Hot Plug event detected AccessType: One to Clear
18:17	0b RW/1C	DISPLAYPORT_B_HOT_PLUG_INTERRUPT_DETECT_STATUS: [DevCDV, DevCTG, DevELK] This reflects hot plug interrupt status on DisplayPort B. Graphics software must write a one to these bits to clear the status. This bit is used for either monitor hotplug/unplug or for notification of a sink event. This bit feeds into the first line interrupt status register when bit 29 of the hotplug enable status register is set. Please note that these bits should be considered in conjunction with bit 29, the hot plug input buffer live state, when determining further action: if bit 29 = 0, the bits should be cleared and the port must be disabled. 00 = DisplayPort/HDMI B Hot Plug event not detected 1x = DisplayPort/HDMI B long pulse Hot Plug event detected X1 = DisplayPort B short pulse Hot Plug event detected AccessType: One to Clear
16	0b RO	PIPE_A_AUDIO_INTERRUPT_LIVE_STATE: [DevCDV, DevCTG, DevCL] This read-only bit is used only in ports that use TMDS encoding. It reflects the state of the pipe A audio interrupt request for HDCP when bit 1 of this register is set. This pin signal is active high. It does not feed into the first line interrupt status register. 1 = HDCP invocation requested from audio 0 = HDCP disable requested from audio AccessType: Read Only
15	0b RO	DIGITAL_PORT_B_AUDIO_REQUEST_LIVE_STATE: [DevCDV, DevCTG, DevCL] This read-only bit is only used on ports using audio. It reflects the state of audio HDCP request when bit 17 of this register is set if audio is enabled on this port. This pin signal is active high. This does not feed into the first line interrupt status register. 1 = HDCP invocation requested from audio 0 = HDCP disable requested from audio AccessType: Read Only
14	0b RO	DIGITAL_PORT_C_AUDIO_REQUEST_LIVE_STATE: [DevCDV, DevCTG, DevCL] This read-only bit is only used on ports using audio. It reflects the state of audio HDCP request when bit 19 of this register is set if audio is enabled on this port. This pin signal is active high. This does not feed into the first line interrupt status register. 1 = HDCP invocation requested from audio 0 = HDCP disable requested from audio AccessType: Read Only
13:12	0b RW	RESERVED_2: mbz



Bit Range	Default & Access	Field Name (ID): Description
11	0b RW/1C	CRT_HOT_PLUG_INTERRUPT_STATUS: [DevCDV, DevCTG, DevBW, DevCL, DevBLC] This bit is set when a CRT hot plug or unplug event has been detected. A hot plug or unplug event is defined as the change in connection state of the CRT as determined by the hardware CRT detect sequence which is enabled through bit #9 (CRT hot plug interrupt enable) or bit #3 (Force CRT detect trigger) in the Port_HotPlug_En register 0x61110. After reset, the CRT is considered unconnected even if physically connected until the first detect sequence occurs. Physically plugging or unplugging the CRT device will also be detected as a change of connection state. Writing a 1 to this bit clears it. 0 = CRT Interrupt has not occurred 1 = CRT Interrupt has occurred AccessType: One to Clear
10	0b RW/1C	TV_HOT_PLUG_INTERRUPT_STATUS: [DevCTG, DevBW, DevCL, DevBLC] This bit is set when a TV hot plug or unplug event has been detected. Reflects the state of bit 31 of the TV DAC state register, offset 68004-68007h. Software must write a one to these bits to clear the status. 0 = TV Interrupt has not occurred 1 = TV Interrupt has occurred AccessType: One to Clear
9:8	0b RW/1C	RESERVED_3: [DevVLVP] MBZ. These info are recorded in 61100h ADPA register[25:24] [DevCDV, DevCTG, DevBW, DevCL, DevBLC] CRT Hot Plug Detection Status (read only): These bits are set when a CRT hot plug or unplug event has been detected. 00 = No channels attached (default) 01 = Blue channel only is attached 10 = Green channel only is attached 11 = Both blue and green channel attached AccessType: One to Clear
7	0b RW	RESERVED_4: mbz
6	0b RW/1C	DISPLAYPORT_D_AUX_INTERRUPT_STATUS: [DevCTG] This bit is set when a transaction on AUX channel D has completed or timed out. This bit feeds into the first line interrupt status register when bit 29 of the AUX channel D control register is set. Writing a 1 to this bit clears it. 0 = AUX channel D Interrupt has not occurred 1 = AUX channel D Interrupt has occurred AccessType: One to Clear
5	0b RW/1C	DISPLAYPORT_C_AUX_INTERRUPT_STATUS: [DevCTG, DevCDV] This bit is set when a transaction on AUX channel C has completed or timed out. This bit feeds into the first line interrupt status register when bit 29 of the AUX channel C control register is set. Writing a 1 to this bit clears it. 0 = AUX channel C Interrupt has not occurred 1 = AUX channel C Interrupt has occurred AccessType: One to Clear
4	0b RW/1C	DISPLAYPORT_B_AUX_INTERRUPT_STATUS: [DevCTG, DevCDV] This bit is set when a transaction on AUX channel B has completed or timed out. This bit feeds into the first line interrupt status register when bit 29 of the AUX channel B control register is set. Writing a 1 to this bit clears it. 0 = AUX channel B Interrupt has not occurred 1 = AUX channel B Interrupt has occurred AccessType: One to Clear
3	0b RW/1C	SDVO_C_HOT_PLUG_INTERRUPT_DETECT_STATUS: [DevCTG, DevCDV] This reflects hot plug interrupt status on SDVO port C. Graphics software must write a one to these bits to clear the status. This bit is used for either monitor hotplug/unplug or for notification of an HDCP state change request from the audio driver over SDVO only. This bit feeds into the first line interrupt status register when bit 25 of the hotplug enable status register is set. 0 = SDVO Hot Plug event not detected 1 = SDVO Hot Plug event detected AccessType: One to Clear



Bit Range	Default & Access	Field Name (ID): Description
2	0b RW/1C	SDVO_B_HOT_PLUG_INTERRUPT_DETECT_STATUS: [DevCTG, DevCDV] This reflects hot plug interrupt status on SDVO port B. Graphics software must write a one to these bits to clear the status. This bit is used for either monitor hotplug/unplug or for notification of an HDCP state change request from the audio driver over SDVO only. This bit feeds into the first line interrupt status register when bit 26 of the hotplug enable status register is set. 0 = SDVO Hot Plug event not detected 1 = SDVO Hot Plug event detected AccessType: One to Clear
1	0b RW/1C	PIPE_A_AUDIO_INTERRUPT_DETECT_STATUS: [DevCTG, DevCDV, DevCL] This reflects a request for integrated HDCP state change set by audio driver and propagated through the audio hardware. The graphics software must write a one to this bit to clear the status. Upon clearing this bit, the audio ready bit is cleared in the audio registers. The graphics software then must reset audio ready bit 14 in the audio control register, offset 620B4h to 1 when the HDCP interrupt has been serviced. This bit feeds into the first line interrupt status register when bit 24 of the hotplug enable status register is set 0 = Audio interrupt event not detected 1 = Audio interrupt event detected AccessType: One to Clear
0	0b RW/1C	PIPE_B_AUDIO_INTERRUPT_DETECT_STATUS: [DevCTG, DevCDV, DevCL] This reflects a request for integrated HDCP state change set by audio driver and propagated through the audio hardware. The graphics software must write a one to this bit to clear the status. Upon clearing this bit, the audio ready bit is cleared in the audio registers. The graphics software then must reset audio ready bit 14 in the audio control register, offset 620B4h to 1 when the HDCP interrupt has been serviced. This bit feeds into the first line interrupt status register when bit 23 of the hotplug enable status register is set 0 = Audio interrupt event not detected 1 = Audio interrupt event detected AccessType: One to Clear

14.11.26 SDVOHDMIB—Offset 61140h

Digital Display Port B Control Register HDMIB port control (dprrega.v sdvo_bQ)

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61140h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000018h




31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
0				0				0				0				0				0				0				0				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
SDVO_HDMIB_ENABLE_DIGITAL_DISPLAY_PORT_B_ENABLE				PIPE_SELECT				RESERVED				COLOR_FORMAT				RESERVED_1				SDVO_HDMIB_CLOCK_OUTPUT_INVERSION_TEST_MODE				SYMBOL_CLOCK_DUTY_CYCLE				RESERVED_2				RESERVED_3				RESERVED_4				RESERVED_5				ENCODING				NULL_PACKETS_ENABLED_DURING_VSYNC				COLOR_RANGE_SELECT				RESERVED_6				AUDIO_OUTPUT_ENABLE				HDCP_PORT_SELECT				SYNC_POLARITY				DIGITAL_PORT_B_DETECTED				RESERVED_7																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	SDVO_HDMIB_ENABLE_DIGITAL_DISPLAY_PORT_B_ENABLE: Disabling this port will put it in its lowest power state. Port enable takes place on the Vblank after being written. Both this bit and bit 6 of this register must be enabled to send audio over this port. This port must not be enabled simultaneously with DisplayPort B. [DevIBX] When disabling the port, software must temporarily enable the port with transcoder select (bit #30) cleared to 0 after disabling the port. This is workaround for hardware issue where the transcoder select set to 1 will prevent DisplayPortB from being enabled on transcoder A. [DevIBX] Software must write this bit twice when enabling the port (setting to 1) as a workaround for hardware issue that may result in first write getting masked. [DevIBX] Toggle this bit off then on at the end of mode set sequence when enabling HDMI 12-bit per color with pixel repeat 1 = Enable. This bit enables the Digital Display Port B interface for HDMI or SDVO modes. 0 = Disable and tristates the Digital Display Port B interface for HDMI or SDVO modes.
30	0b RW	PIPE_SELECT: This bit determines from which display pipe the source data will originate. This only applies to devices with dual display pipes. Pipe selection takes place on the Vblank after being written 0 = Pipe A 1 = Pipe B
29	0b RW	RESERVED: [DevCDV]: [DevCTG, DevBW, DevCL, DevBLC] Stall Select: This bit selects stall for external scaling functionality only on SDVO. Programming notes: It is only valid to have a single stall indication to a particular pipe. In cases where two ports are being driven from a single pipe, one of the ports must set this bit to 0. Only sDVOB or sDVOC can select the stall function, as only a single stall input is available between the two interfaces. Set the stall input to unused before programming the external device creating the stall. 0 = Stall input signal is unused on this port 1 = Stall input signal is used to stall the pipe attached to this port



Bit Range	Default & Access	Field Name (ID): Description
28:26	0b RW	COLOR_FORMAT: This field selects the number of bits per color sent to a receiver device connected to this port. Color format takes place on the Vblank after being written. Color format change must be done as a part of mode set since different color depths require different pixel clock settings. Selecting a pixel color depth higher or lower than the pixel color depth of the frame buffer results in dithering the output stream. 000 = 8 bits per color (Default, x3 mode) 001 = RESERVED for 10 bits per color 010 = RESERVED for 6 bits per color 011 = RESERVED 1xx = RESERVED
25:19	0b RW	RESERVED_1: Reserved.
18	0b RW	SDVO_HDMIB_CLOCK_OUTPUT_INVERSION_TEST_MODE: Please note that this applies to all modes and is instantly updated. 1 = sDVO/HDMIB Clock output is inverted 0 = sDVO/HDMIB Clock output is NOT inverted (DEFAULT)
17:16	0b RW	SYMBOL_CLOCK_DUTY_CYCLE: [DevCDV, DevCTG, DevCL] These bits control the output clock duty cycle to enable EMI mitigation on the external UDI link. 10/90 cycle has been measured to have ~13dB EMI improvement over a 50/50 duty cycle. 00 = (Default) 50/50 duty cycle: Clock output is 0000011111 01 = 10/90 duty cycle: Clock output is 0111111111 followed by 0000000001 10 = 20/80 duty cycle: Clock output is 0011111111 followed by 0000000011 11 = Reserved
15	0b RW	RESERVED_2: [DevCDV, DevVLVP]: [DevBW, DevCL, DevBLC] Port Lane Reversal: This bit reverses the order of the 4 lanes within the port. Port lane reversal takes place on the Vblank after being written. It is an OEM configurable feature. 0 = (Default) Not reversed 1 = Reversed
14	0b RW	RESERVED_3: Reserved.
13	0b RW	RESERVED_4: [DevCDV, DevVLVP]: [DevBW, DevCL, DevBLC] Clock Output Disable: This bit disables the clock output on the digital output port. For 8b/10b modes the clock output should be disabled. 0 = (Default) Clock output enabled 1 = Clock output disabled
12	0b RW	RESERVED_5: [DevCDV, DevVLVP]: [DevBW, DevCL, DevBLC, DevCDV] Scrambling enable: This bit enables scrambling for UDI-related modes using ANSI 8b/10b or TMDS encoding. It is not used with SDVO encoding. Software must set this bit appropriately when enabling the port. Scrambling is reset at the beginning of horizontal sync. 0 = Scrambling disabled (Default) 1 = Scrambling enabled
11:10	0b RW	ENCODING: [DevCDV, DevCTG, DevCL] These bits select among encoding types. It is set as part of the display detection process. Control codes for ANSI 8b/10b and TMDS encoding must be programmed using these bits. Please note that ANSI 8b/10b and TMDS encoding can only be enabled on one port at a time, as only one HPD pin is available for use between ports B and C. 00 = Reserved 01 = Reserved 10 = TMDS encoding ([DevCL, DevCTG, DevCDV, DevVLVP] external link and HDMI only) See the HDMI specification for control codes. In this mode, the external HPD pin is used to generate hotplug. In fixed frequency mode, start of fill and end of fill values for TMDS must be programmed using register 6114C. 11 = Reserved



Bit Range	Default & Access	Field Name (ID): Description
9	0b RW	NULL_PACKETS_ENABLED_DURING_VSYNC: This bit enables a null packet (32 bytes of a value of 0) to be sent when Vsync=1 on this port, required for HDMI operation. It also enables preambles and guardbands prior to the null packets, in accordance with the HDMI specification. It is only valid for modes that use TMDS encoding. 0 = Disable null infoframe packets when Vsync=1 on this port. (Default) 1 = Enable null infoframe packets when Vsync=1 on this port.
8	0b RW	COLOR_RANGE_SELECT: [DevCDV, DevCTG, DevCL] This bit is used to select the color range of RGB outputs in HDMI mode. It is only valid when using TMDS encoding and 8 bit per color mode. 0 = Apply full 0-255 color range to the output (Default) 1 = Apply 16-235 color range to the output
7	0b RW	RESERVED_6: [DevCDV]: [DevCTG, DevBW, DevCL, DevBLC] sDVOB Border Enable: This bit determines if the border data from native VGA or the timing generator is to be considered valid pixel data at the external component. 1 = Border to the sDVOB encoder is enabled. Blank# is used to generate the DE output (used in all cases except when the external scaler is used in a DVI panel, over SDVO) . 0 = Border to the sDVOB encoder is disabled. DE (Display Enable) is used
6	0b RW	AUDIO_OUTPUT_ENABLE: [DevCDV, DevCTG, DevCL] This bit directs audio to this port. When enabled and audio data is available, the audio data will be combined with the video data and sent over this port. The audio unit uses the status of this bit to indicate presence of the HDMI output to the audio driver. 0 = (Default) No audio output on this port 1 = Enable audio on this port
5	0b RW	HDCP_PORT_SELECT: [DevCDV, DevCTG, DevCL] This bit directs HDCP to this port. When enabled, the information sent on this port will be encrypted using HDCP. Please note that this bit does not enable encryption on its own, but must be used in conjunction with HDCP registers. 0 = (Default) No HDCP encryption on this port 1 = Enable HDCP on this port
4:3	11b RW	SYNC_POLARITY: Please note that sync polarity does not apply to ANSI coding. Indicates the polarity of Hsync and Vsync. Inverted polarity is transmitted as SYNC-BLANK-SYNC and standard polarity is transmitted as BLANK-SYNC-BLANK. For example, if Vsync is not inverted and Hsync is inverted, an Hsync period transmitted during Vsync would be transmitted as BLANK+VS+HS BLANK+VS BLANK+VS+HS. Please note that in native VGA modes, these bits have no effect. In native VGA modes, sync polarity is determined by VRshr3c2d76b[7:6], the VGA polarity bits in VGA control. 00 = VS and HS are active low (inverted) 01 = VS is active low (inverted), HS is active high 10 = VS is active high, HS is active low (inverted) 11 = (Default) VS and HS are active high
2	0b RO	DIGITAL_PORT_B_DETECTED: Read-only bit indicating whether a digital port B was detected during initialization. It signifies the level of the GMBUS port 4 (sDVO B/C) data line at boot. This bit is valid regardless of whether the port is enabled. 0 = Digital Port B not detected during initialization 1 = Digital Port B detected during initialization AccessType: Read Only
1:0	0b RW	RESERVED_7: MBZ



14.11.27 SDVO—Offset 61154h

DP2 - Digital Port DFT Register ;

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61154h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SDVO_DC_BALANCE_RESET	RESERVED				PORTC_AUX_LEAKAGE_ENABLE	PORTB_AUX_LEAKAGE_ENABLE	SCRAMBLED_1S_ON_PIPE_B	SCRAMBLED_1S_ON_PIPE_A
					IDLE_TIME_SPEEDUP_ON_PIPE_B	IDLE_TIME_SPEEDUP_ON_PIPE_A	TEST_PATTERN_8_BIT_PROGRAMMED_INPUT_ON_TRANSCODE_B	TEST_PATTERN_8_BIT_PROGRAMMED_INPUT_ON_TRANSCODE_A
					SCRAMBLED_0S_ON_TRANSCODE_B	SCRAMBLED_0S_ON_TRANSCODE_A	PRBS7_TEST_PATTERN_ON_TRANSCODE_B	PRBS7_TEST_PATTERN_ON_TRANSCODE_A
					SCRAMBLER_RESET_ONCE_A_FRAME_ON_TRANSCODE_B	SCRAMBLER_RESET_ONCE_A_FRAME_ON_TRANSCODE_A		

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	SDVO_DC_BALANCE_RESET: Project: All Format: Value Name Description Project 0b Not Reset DC Balance circuitry will not be reset on every frame All 1b Reset DC Balance circuitry will be reset on every frame All
30:14	0b RW	RESERVED: Project: All Format: MBZ
13	0b RW	PORTC_AUX_LEAKAGE_ENABLE: Project: All Format:
12	0b RW	PORTB_AUX_LEAKAGE_ENABLE: Project: All Format:
11	0b RW	SCRAMBLED_1S_ON_PIPE_B: Project: All Format: Value Name Description Project 0b Disable Disable scrambled 1s All 1b Enable Enable scrambled 1s All



Bit Range	Default & Access	Field Name (ID): Description
10	0b RW	SCRAMBLED_1S_ON_PIPE_A: Project: All Format: Value Name Description Project 0b Disable Disable scrambled 1s All 1b Enable Enable scrambled 1s All
9	0b RW	IDLE_TIME_SPEEDUP_ON_PIPE_B: Project: All Format: Value Name Description Project 0b Normal Normal idle time All 1b Speedup Speedup idle time All
8	0b RW	IDLE_TIME_SPEEDUP_ON_PIPE_A: Project: All Format: Value Name Description Project 0b Normal Normal idle time All 1b Speedup Speedup idle time All
7	0b RW	TEST_PATTERN_8_BIT_PROGRAMMED_INPUT_ON_TRANSCODE_B: Project: All Format: Value Name Description Project 0b Disable Disable the test pattern All 1b Enable Enable the test pattern All
6	0b RW	TEST_PATTERN_8_BIT_PROGRAMMED_INPUT_ON_TRANSCODE_A: Project: All Format: Value Name Description Project 0b Disable Disable the test pattern All 1b Enable Enable the test pattern All
5	0b RW	SCRAMBLED_0S_ON_TRANSCODE_B: Project: All Format: Value Name Description Project 0b Disable Disable the scramble 0s All 1b Enable Enable the scramble 0s All
4	0b RW	SCRAMBLED_0S_ON_TRANSCODE_A: Project: All Format: Value Name Description Project 0b Disable Disable the scramble 0s All 1b Enable Enable the scramble 0s All
3	0b RW	PRBS7_TEST_PATTERN_ON_TRANSCODE_B: Project: All Format: Value Name Description Project 0b Disable Disable the test pattern All 1b Enable Enable the test pattern All
2	0b RW	PRBS7_TEST_PATTERN_ON_TRANSCODE_A: Project: All Format: Value Name Description Project 0b Disable Disable the test pattern All 1b Enable Enable the test pattern All
1	0b RW	SCRAMBLER_RESET_ONCE_A_FRAME_ON_TRANSCODE_B: Project: All Format: Value Name Description Project 0b Disable Disable the scrambler reset once a frame All 1b Enable Enable the scrambler reset once a frame All
0	0b RW	SCRAMBLER_RESET_ONCE_A_FRAME_ON_TRANSCODE_A: All Format: Value Name Description Project 0b Disable Disable the scrambler reset once a frame All 1b Enable Enable the scrambler reset once a frame All

14.11.28 HDMIC—Offset 61160h

Digital Display Port C Register HDMIC port control (dprrega.v sdvo_cQ)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61160h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h




Default: 00000018h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SDVO_HDMIC_ENABLE_DIGITAL_DISPLAY_PORT_C_ENABLE	PIPE_SELECT	RESERVED	COLOR_FORMAT	RESERVED_1	SDVO_HDMIC_CLOCK_OUTPUT_INVERSION_TEST_MODE	SYMBOL_CLOCK_DUTY_CYCLE	RESERVED_2	RESERVED_3
							RESERVED_4	RESERVED_5
						ENCODING	NULL_PACKETS_ENABLED_DURING_VSYNC	COLOR_RANGE_SELECT
							SDVOC_BORDER_ENABLE	AUDIO_OUTPUT_ENABLE
							HDCP_PORT_SELECT	SYNC_POLARITY
							DIGITAL_PORT_C_DETECTED	DDI2_PORT_DETECTED
								RESERVED_6

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	SDVO_HDMIC_ENABLE_DIGITAL_DISPLAY_PORT_C_ENABLE: Disabling this port will put it in its lowest power state. Port enable takes place on the Vblank after being written. Both this bit and bit 6 of this register must be enabled to send audio over this port in HDMI. This port must not be enabled simultaneously with DisplayPort C. [DevIBX] When disabling the port, software must temporarily enable the port with transcoder select (bit #30) cleared to 0 after disabling the port. This is workaround for hardware issue where the transcoder select set to 1 will prevent DPC from being enabled on transcoder A. [DevIBX] Software must write this bit twice when enabling the port (setting to 1) as a workaround for hardware issue that may result in first write getting masked. [DevIBX] Toggle this bit off then on at the end of mode set sequence when enabling HDMI 12-bit per color with pixel repeat. 1 = Enable. This bit enables the Digital Display Port C interface for HDMI or DVI modes. 0 = Disable and tristates the Digital Display Port C interface for HDMI or DVI modes.
30	0b RW	PIPE_SELECT: This bit determines from which display pipe the source data will originate. This only applies to devices with dual display pipes. Pipe selection takes place on the Vblank after being written 0 = Pipe A 1 = Pipe B
29	0b RW	RESERVED: [DevCDV]: stall Select: This bit selects stall for external scaling functionality only on SDVO. Programming notes: It is only valid to have a single stall indication to a particular pipe. In cases where two ports are being driven from a single pipe, one of the ports must set this bit to 0. Only sDVOB or sDVOC can select the stall function, as only a single stall input is available between the two interfaces. Set the stall input to unused before programming the external device creating the stall. 0 = Stall input signal is unused on this port 1 = Stall input signal is used to stall the pipe attached to this port



Bit Range	Default & Access	Field Name (ID): Description
28:26	0b RW	COLOR_FORMAT: This field selects the number of bits per color sent to a receiver device connected to this port. Color format takes place on the Vblank after being written. Color format change must be done as a part of mode set since different color depths require different pixel clock settings. Selecting a pixel color depth higher or lower than the pixel color depth of the frame buffer results in dithering the output stream. 000 = 8 bits per color (Default) 001 = RESERVED for 10 bits per color 010 = RESERVED for 6 bits per color 011 = RESERVED 1xx = RESERVED
25:19	0b RW	RESERVED_1: Reserved.
18	0b RW	SDVO_HDMIC_CLOCK_OUTPUT_INVERSION_TEST_MODE: Please note that this applies to all modes and is instantly updated. 1 = sDVO/HDMI Clock output is inverted 0 = sDVO/HDMI Clock output is NOT inverted (DEFAULT)
17:16	0b RW	SYMBOL_CLOCK_DUTY_CYCLE: These bits control the output clock duty cycle to enable EMI mitigation on the external HDMI link. 10/90 cycle has been measured to have ~13dB EMI improvement over a 50/50 duty cycle. 00 = (Default) 50/50 duty cycle: Clock output is 0000011111 01 = 10/90 duty cycle: Clock output is 0111111111 followed by 0000000001 ([DevCL, DevCTG, DevCDV] HDMI only) 10 = 20/80 duty cycle: Clock output is 0011111111 followed by 0000000011 ([DevCL, DevCTG, DevCDV] HDMI only) 11 = Reserved
15	0b RW	RESERVED_2: [DevCTG, DevCDV, DevVLVP] Port Lane Reversal: This bit reverses the order of the 4 lanes within the port. Port lane reversal takes place on the Vblank after being written. It is an OEM configurable feature. 0 = (Default) Not reversed 1 = Reversed
14	0b RW	RESERVED_3: Reserved.
13	0b RW	RESERVED_4: [DevCTG, DevCDV, DevVLVP] Clock Output Disable: This bit disables the clock output on the digital output port. For 8b/10b modes the clock output should be disabled. 0 = (Default) Clock output enabled 1 = Clock output disabled ([DevCL] only)
12	0b RW	RESERVED_5: [DevCTG, DevCDV, DevVLVP]: Scrambling enable: This bit enables scrambling for UDI-related modes using ANSI 8b/10b or TMDS encoding. It is not used with SDVO encoding. Software must set this bit appropriately when enabling the port. Scrambling is reset at the beginning of horizontal sync. 0 Scrambling disabled (Default) 1 = Scrambling enabled ([DevCL] only)
11:10	0b RW	ENCODING: These bits select among encoding types. It is set as part of the display detection process. Control codes for ANSI 8b/10b and TMDS encoding must be programmed using these bits. Please note that ANSI 8b/10b and TMDS encoding can only be enabled on one port at a time, as only one HPD pin is available for use between ports B and C. 00 = Reserved 01 = Reserved 10 = TMDS encoding ([DevCL, DevCTG, DevCDV, DevVLVP] external link and HDMI only) See the HDMI specification for control codes. In this mode, the external HPD pin is used to generate hotplug. In fixed frequency mode, start of fill and end of fill values for TMDS must be programmed using register 6114C. 11 = Reserved



Bit Range	Default & Access	Field Name (ID): Description
9	0b RW	NULL_PACKETS_ENABLED_DURING_VSYNC: This bit enables a null packet (32 bytes of a value of 0) to be sent when Vsync=1 on this port, required for HDMI operation. It also enables preambles and guardbands prior to the null packets, in accordance with the HDMI specification. It is only valid for modes that use TMDS encoding. 0 = Disable null infoframe packets when Vsync=1 on this port. (Default) 1 = Enable null infoframe packets when Vsync=1 on this port.
8	0b RW	COLOR_RANGE_SELECT: This bit is used to select the color range of RGB outputs in HDMI mode. It is only valid when using TMDS encoding and 8 bit per color mode. 0 = Apply full 0-255 color range to the output (Default) 1 = Apply 16-235 color range to the output ([DevCL and DevCTG] only)
7	0b RW	SDVOC_BORDER_ENABLE: This bit determines if the border data from native VGA or the timing generator is to be considered valid pixel data at the external component. 1 = Border to the sDVOC encoder is enabled. Blank# is used to generate the DE output (used in all cases except when the external scaler is used in a DVI panel, over SDVO) . 0 = Border to the sDVOC encoder is disabled. DE (Display Enable) is used
6	0b RW	AUDIO_OUTPUT_ENABLE: ([DevCL, DevCTG, DevCDV]): This bit directs audio to this port. When enabled and audio data is available, the audio data will be combined with the video data and sent over this port. The audio unit uses the status of this bit to indicate presence of the HDMI output to the audio driver. 0 = (Default) No audio output on this port 1 = Enable audio on this port ([DevCL, DevCTG, DevCDV] only)
5	0b RW	HDCP_PORT_SELECT: This bit directs HDCP to this port. When enabled, the information sent on this port will be encrypted using HDCP. Please note that this bit does not enable encryption on its own, but must be used in conjunction with HDCP registers. 0 = (Default) No HDCP encryption on this port 1 = Enable HDCP on this port ([DevCL, DevCTG, DevCDV] only)
4:3	11b RW	SYNC_POLARITY: Please note that sync polarity does not apply to ANSI coding. Indicates the polarity of Hsync and Vsync. Inverted polarity is transmitted as SYNC-BLANK-SYNC and standard polarity is transmitted as BLANK-SYNC-BLANK. For example, if Vsync is not inverted and Hsync is inverted, an Hsync period transmitted during Vsync would be transmitted as BLANK+VS+HS BLANK+VS BLANK+VS+HS. Please note that in native VGA modes, these bits have no effect. In native VGA modes, sync polarity is determined by VRshr3c2d76b[7:6], the VGA polarity bits in VGA control. 00 = VS and HS are active low (inverted) 01 = VS is active low (inverted), HS is active high 10 = VS is active high, HS is active low (inverted) 11 = (Default) VS and HS are active high
2	0b RO	DIGITAL_PORT_C_DETECTED: Read-only bit indicating whether a digital port C was detected during initialization. It signifies the level of the GMBUS port 3 (port C) data line at boot. This bit is valid regardless of whether the port is enabled. 0 = Digital Port C not detected during initialization 1 = Digital Port C detected during initialization (default) AccessType: Read Only
1	0b RO	DDI2_PORT_DETECTED: Read-only bit indicating whether the DDI2 port was detected during initialization. It signifies the level of the GMBUS port 1 data line at boot. This bit is valid regardless of whether the port is enabled. 0 = DDI2 Port not detected during initialization 1 = DDI2 Port detected during initialization (default) AccessType: Read Only
0	0b RW	RESERVED_6: MBZ



Bit Range	Default & Access	Field Name (ID): Description
17:16	0b RW/1C	DIGITAL_PORT_D_HOT_PLUG_INTERRUPT_DETECT_STATUS: Project: All Default Value: 0b AccessType: One to Clear This reflects hot plug detect status on the digital port. Graphics software must write a one to these bits to clear the status. This bit is used for either monitor hotplug/unplug or for notification of a sink event. When either a long or short pulse is detected, one of these bits will set. These bits are ORed together to go to the main ISR hotplug register bit. - Value / Name / Description / Project 00 / No Detect / Digital port hot plug event not detected / All - X1 / Short Detect / Digital port short pulse hot plug event detected / All 1X / Long Detect / Digital port long pulse hot plug event detected / All
15:13	0b RW	RESERVED_1: Project: All Format:
12	0b RW	DIGITAL_PORT_C_HOT_PLUG_DETECT_INPUT_ENABLE: Project: All Default Value: 0b Controls the state of the HPD buffer for the digital port. The buffer state is independent of whether the port is enabled or not. - Value / Name / Description / Project 0 / Disable / Buffer disabled / All 1 / Enable / Buffer enabled. Hot plugs bit reflect the electrical state of the HPD pin / All
11:10	0b RW	DIGITAL_PORT_C_HOT_PLUG_SHORT_PULSE_DURATION: Project: All Default Value: 0b These bits define the duration of the pulse defined as a short pulse. - Value / Name / Description / Project 00 / 2ms / 2ms / All 01 / 4.5ms / 4.5mS / All 10 / 6ms / 6mS / All 11 / 100ms / 100mS / All
9:8	0b RW/1C	DIGITAL_PORT_C_HOT_PLUG_INTERRUPT_DETECT_STATUS: Project: All Default Value: 0b AccessType: One to Clear This reflects hot plug detect status on the digital port. Graphics software must write a one to these bits to clear the status. This bit is used for either monitor hotplug/unplug or for notification of a sink event. When either a long or short pulse is detected, one of these bits will set. These bits are ORed together to go to the main ISR hotplug register bit. - Value / Name / Description / Project 00 / No Detect / Digital port hot plug event not detected / All - X1 / Short Detect / Digital port short pulse hot plug event detected / All 1X / Long Detect / Digital port long pulse hot plug event detected / All
7:5	0b RW	RESERVED_2: Project: All Format:
4	0b RW	DIGITAL_PORT_B_HOT_PLUG_DETECT_INPUT_ENABLE: Project: All Default Value: 0b Controls the state of the HPD buffer for the digital port. The buffer state is independent of whether the port is enabled or not. - Value / Name / Description / Project 0 / Disable / Buffer disabled / All 1 / Enable / Buffer enabled. Hot plugs bit reflect the electrical state of the HPD pin / All
3:2	0b RW	DIGITAL_PORT_B_HOT_PLUG_SHORT_PULSE_DURATION: Project: All Default Value: 0b These bits define the duration of the pulse defined as a short pulse. - Value / Name / Description / Project 00 / 2ms / 2ms / All 01 / 4.5ms / 4.5ms / All 10 / 6ms / 6ms / All 11 / 100ms / 100ms / All



DV Determinism Mode Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61168h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:7	0b RW	RESERVED: Project: All Format:



Bit Range	Default & Access	Field Name (ID): Description
6	0b RW	DISPLAYPORT_D_PORT_ENABLE_OVERRIDE: Project: All Default Value: 0b - Value / Name / Description / Project 0b / Normal / Normal operation / All 1b / Override / DisplayPort D port enable override (controlled from sm10alertb_gp60_mgpio4 pin) / All
5	0b RW	DISPLAYPORT_C_PORT_ENABLE_OVERRIDE: Project: All Default Value: 0b Value Name Description Project 0b Normal Normal operation All 1b Override DisplayPort C port enable override (controlled from sus_statb_gp61 pin) All
4	0b RW	DISPLAYPORT_B_PORT_ENABLE_OVERRIDE: Project: All Default Value: 0b Value Name Description Project 0b Normal Normal operation All 1b Override DisplayPort B port enable override (controlled from gp57_mgpio5 pin) All
3	0b RW	DP_SDVO_HDMI_PIPE_ENABLE_OVERRIDE_FOR_DISPLAY_PIPE_B: Project: All Default Value: 0b Value Name Description Project 0b Normal Normal operation All 1b Override DP/SDVO/HDMI pipe enable override for display pipe B (controlled from gp74_batlowb pin) All
2	0b RW	DP_SDVO_HDMI_PIPE_ENABLE_OVERRIDE_FOR_DISPLAY_PIPE_A: Project: All Default Value: 0b Value Name Description Project 0b Normal Normal operation All 1b Override DP/SDVO/HDMI pipe enable override for display pipe A (controlled from slp_s4b pin) All
1	0b RW	CRT_LVDS_PIPE_ENABLE_OVERRIDE_FOR_DISPLAY_PIPE_B: Project: All Default Value: 0b Value Name Description Project 0b Normal Normal operation All 1b Override CRT/LVDS pipe enable override for display pipe B (controlled from susclk_gp62 pin) All
0	0b RW	CRT_LVDS_PIPE_ENABLE_OVERRIDE_FOR_DISPLAY_PIPE_A: Project: All Default Value: 0b Value Name Description Project 0b Normal Normal operation All 1b Override CRT/LVDS pipe enable override for display pipe A (controlled from slp_mb pin) All

14.11.31 VIDEO_DIP_CTL_B—Offset 61170h

Video DIP Control for Pipe B

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61170h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 20200900h



Bit Range	Default & Access	Field Name (ID): Description
31:3	0b RW	RESERVED: Project: All Format: MBZ
2	0b RW	GCP_COLOR_INDICATION: Project: All See Pipe A description.
1	0b RW	GCP_DEFAULT_PHASE_ENABLE: Project: All See Pipe A description.
0	0b RW	GCP_AV_MUTE: All See Pipe A description.

14.11.34 MIPIA_PORT_CTRL—Offset 61190h

mipi A port ctrl

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61190h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EN	ADJDLY_HSTX				MIPI_DUAL_LINK_MODE_APPLICABLE_ONLY_IF_MIPI_DUAL_LINK_MODE_IS_ENABLED_THROUGH_MIPI_LANES_CONFIGURATION_BITS			
					DITHER			
					RESERVED			
					SELFLOPPED_HSTX			
					RESERVED_1			
					FLISDSI_ADJDLY_HSTX_MIPIA			
					AFE_LATCHOUT			
					LPOUTPUT_HOLD			
					FLISDSI_ADJDLY_HSTX_MIPIC_HIGH_ORDER			
					MIPI14DPHY_AdjDly_HSTX_MIPI_C			
					CSB			
					CB			
					FLISDSI_AdjDly_HSTX_MIPI_C_LOWER_ORDER			
					DELAY			
					EFFECT			
					MIPI_LANES_CONFIGURATION			



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	EN: When this bit is disabled the MIPI DPI (video mode) is inactive and in it's low power state. When it is enable it starts to generate timing for this MIPI port 0 = The port is disabled and all MIPI DPI interface are disable (timing generator is off) 1 = The port is enabled
30:27	0b RW	ADJDLY_HSTX: These four bits act as an encoded count of the number of buffer delays to insert on the ckdsi2x clock going to the six flops that are storing the HS TX data and clock signals. Default is 4'b0000 which is the equivalent of 1 buffer delay. Will need to set these bits to a value determined by clock timing team before using the MIPI DSI HS TX feature
26	0b RW	MIPI_DUAL_LINK_MODE_APPLICABLE_ONLY_IF_MIPI_DUAL_LINK_MODE_IS_ENABLED_THROUGH_MIPI_LANES_CONFIGURATION_BITS: 0 = Front-Back mode (default) 1 = Pixel alternative mode
25	0b RW	DITHER: This bit enables or disables (bypassing) 8-6-bit color dithering function. The usage of this bit would be on for 18-bpp panels and off for 24-bpp panels. 0 = disabled 1 = enabled
24	0b RW	RESERVED: Reserved.
23	0b RW	SELFLOPPED_HSTX: This bit will be used to mux between the flopped (new) and unflopped (original) versions of the TX HS clock and data. Default 0 = pass through original unflopped version, if set to 1 = pass through the new flopped version of these signals. We probably need to enable validation to always set these to 1 during startup so we're fully testing this logic as it is the intended way we will run A0
22	0b RW	RESERVED_1: Reserved.
21:18	0b RW	FLISDSI_ADJDLY_HSTX_MIPIA: These four bits act as an encoded count of the number of buffer delays to insert on the ckdsi2x clock going to the six flops that are storing the HS TX data and clock signals. Default is 4'b0000 which is the equivalent of 1 buffer delay. Will need to set these bits to a value determined by clock timing team before using the MIPI DSI HS TX feature
17	0b RW	AFE_LATCHOUT: This bit reflect the value of the output latch of CLK A lane in DSI AFE b1 = current value of output latch is 1 (D-PHY is in LP11 state) b0 = current value of output latch is 0 (D-PHY is in LP00 state) The software driver can read this bit to see if the hold value (LP11 or LP00) to initialize from a sleep state (s0i1 or S0i3) correctly
16	0b RW	LPOUTPUT_HOLD: 0= disable transparent latche inside DSI AFE. Output are driven by latch value. 1= enable transparent latch inside DSI AFE so data are driven by DSI DPHY
15	0b RW	FLISDSI_ADJDLY_HSTX_MIPIC_HIGH_ORDER: The fourth bit of four bits act as an encoded count of the number of buffer delays to insert on the ckdsi2x clock going to the six flops that are storing the HS TX data and clock signals. Default is 1'b0 which is the equivalent of 1 buffer delay. Will need to set these bits to a value determined by clock timing team before using the MIPI DSI HS TX feature
14:11	0b RW	MIPI4DPHY_AdjDly_HSTX_MIPI_C: These four bits act as an encoded count of the number of buffer delays to insert on the ckdsi2x clock going to the six flops that are storing the HS TX data and clock signals.[Br] Default is 4'b0000 which is the equivalent of 1 buffer delay. Will need to set these bits to a value determined by clock timing team before using the MIPI DSI HS TX feature
10:9	0b RW	CSB: Clock input for bandgap voltage sample and hold circuit. Final setting will be based silicon characterization. 00b = 20mhz clock 01b = 10mhz clock 10b = 40mhz clock 11b = reserved



Access Method

Offset: [GTTMMADR LSB + 180000h] + 61198h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:28	0b RW	BIT_35_32_OF_DISPLAY_PIPE_A_PROGRAMMABLE_PIXEL_DATA_REGISTER_4: Project: All Default Value: 0b
27:24	0b RW	BIT_35_32_OF_DISPLAY_PIPE_A_PROGRAMMABLE_PIXEL_DATA_REGISTER_3: Project: All Default Value: 0b
23:20	0b RW	BIT_35_32_OF_DISPLAY_PIPE_A_PROGRAMMABLE_PIXEL_DATA_REGISTER_2: Project: All Default Value: 0b



Bit Range	Default & Access	Field Name (ID): Description
19:16	0b RW	BIT_35_32_OF_DISPLAY_PIPE_A_PROGRAMMABLE_PIXEL_DATA_REGISTER_1: Project: All Default Value: 0b
15:2	0b RW	RESERVED: Project: All Format:
1	0b RW	MODE_SELECT: Project: All Default Value: 0b Pixel generator mode select Value Name Description Project 0b LFSR LFSR All 1b Programmable Programmable pixel data register. Setting mode select to 1 will also start the 2-bit counter. All
0	0b RW	PIXEL_GENERATOR_ENABLE: All

14.11.37 MIPIA_AUTOPWG—Offset 611A0h

mipi A autopowergating

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 611A0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED: Reserved.

14.11.38 DPB_PIX_GEN_CTRL—Offset 611B0h

Display Pipe B Pixel Generator Control

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 611B0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.11.39 PIPEA_PP_STATUS—Offset 61200h

PipeA Panel Power Status Register ([DevCL, DevCTG, DevCDV]) PP Status (dplreg.v panel_pwr_sr)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61200h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 08000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
PANEL_POWER_ON_STATUS	REQUIRE_ASSET_STATUS	POWER_SEQUENCE_PROGRESS	POWER_CYCLE_DELAY_ACTIVE	RESERVED				INTERNAL_SEQUENCE_STATE_FOR_TEST_DEBUG

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	PANEL_POWER_ON_STATUS: 0 = Indicates that the panel power down sequencing has completed. A power cycle delay may be currently active. It is safe and allowed to program pipe timing and DPLL registers. If this bit is not a zero, it activates the register write protect and writes to those registers will be ignored unless the write protect key value is set in the panel sequencing control register. 1 = In conjunction with bits Power Sequence Progress field and Power Cycle Delay Active, this bit set to a one indicates that the panel is currently powered up or is currently in the power down sequence and it is unsafe to change the pipe timing and DPLL registers for the pipe that is assigned to the embedded panel output. If the embedded panel port is selected as the target for the panel control, Software is responsible for enabling the LCD display by writing a 1 to the port enable bit only after all pipe timing, DPLL registers are properly programmed, and the PLL has locked to the reference signal. This bit is cleared (set to 0) only after the panel power down sequencing is completed.



Bit Range	Default & Access	Field Name (ID): Description
30	0b RO	REQUIRE_ASSET_STATUS: This bit indicates the status of programming of the display PLL and the selected display port. This a power on cycle will not be allowed unless this status indicates that the required assets are programmed and ready for use. 0 = All required assets are not properly programmed. 1 = All required assets are ready for the driving of a panel. The following conditions determine that the assets are ready: 1) Display Pipe PLL Enabled and frequency locked (bit-31 of DPLL Control Register for the pipe attached to the embedded panel port). 2) Display Pipe Enabled (bit-31 of PIPECONF Pipe Configuration Register. For the pipe attached to the embedded panel port) 3) Embedded Panel Port is Programmed Enabled
29:28	0b RO	POWER_SEQUENCE_PROGRESS: 00 = Indicates that the panel is not in a power sequence 01 = Indicates that the panel is in a power up sequence (may include power cycle delay) 10 = Indicates that the panel is in a power down sequence 11 = Reserved
27	1b RO	POWER_CYCLE_DELAY_ACTIVE: Power cycle delays occur after a panel power down sequence or after a hardware reset. On reset, a power cycle delay will occur using the default value for the timing. 0 = A power cycle delay is not currently active 1 = A power cycle delay (T4) is currently active
26:4	0b RO	RESERVED: Reserved.
3:0	0b RO	INTERNAL_SEQUENCE_STATE_FOR_TEST_DEBUG: 0000 = Power Off Idle (S0.0) 0001 = Power Off, Wait for cycle delay (S0.1) 0010 = Power Off (S0.2) 0011 = Power Off (S0.3) 0100 = Reserved 0101 = Reserved 0110 = Reserved 0111 = Reserved 1000 = Power On Idle (S1.0) 1001 = Power On, (S1.1) 1010 = Power On, (S1.2) 1011 = Power On, Wait for cycle delay (S1.3) 1100 = Reserved 1101 = Reserved 1110 = Reserved 1111 = Reset

14.11.40 PIPEA_PP_CONTROL—Offset 61204h

PipeA Panel Power Control Register ([DevCL, DevCTG, DevCDV]) PP Control (dplrreg.v pnl_pwr_cntl)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61204h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
WRITE_PROTECT_KEY				RESERVED				EDP_PANEL_VDD_ENABLE
								BACKLIGHT_ENABLE
								POWER_DOWN_ON_RESET
								POWER_STATE_TARGET

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	WRITE_PROTECT_KEY: ABCD Write protect off When this field is programmed to anything except the write protect off setting and the panel is either powered up or in the process of a power up sequence, a set of registers involved in generation of panel timing or control become write protected. Any write cycles to those write protected registers, while they will complete as normal, will not change the value of the register when write protected. When this register field contains the write protect off key value, write protect will be unconditionally disabled. In situations where the embedded panel port is unused, the port should remain powered down and the write protect will be inactive. This field in normal operation should be left to all zeros and never programmed with the key value. It exists only to allow testing and workarounds. List of Write protected registers: (LVDS and Panel sequencing Registers): LVDS Digital Display Port Control Address: 61180h 61183h Pipe A Panel power on sequencing delays - Address: 61208-6120Bh Pipe A Panel power off sequencing delays Address: 6120Ch 6120Fh Pipe A Panel power cycle delay and Reference Divisor Address: 61210h 61213 (DPLL registers): DPLL Control Registers FPA0 DPLL Divisor Register FPA1 DPLL Divisor Register 1 FPB0 DPLL Divisor Register FPB1 DPLL Divisor Register 1 (Display Pipe timing registers except source size) HTOTAL Horizontal Total Register HBLANK Horizontal Blank Register HSYNC_ Horizontal Sync Register VTOTAL_ Vertical Total Register VBLANK_ Vertical Blank Register VSYNC_ Vertical Sync Register
15:4	0b RW	RESERVED: Reserved.
3	0b RW	EDP_PANEL_VDD_ENABLE: [DevCDV]: Enabling this bit enables the panel vdd if the embedded panel is DisplayPort, as indicated in bits 31:30 of the panel power on sequencing. Software must enable this bit for eDP link training. After eDP link training is done, software must disable it and let the normal panel power sequencing to take control. 0 = eDP panel Vdd disabled 1 = eDP panel Vdd enabled [DevCLN] Reserved
2	0b RW	BACKLIGHT_ENABLE: [DevCTG, DevCDV]: Enabling this bit enables the panel backlight if the embedded panel is DisplayPort, as indicated in bits 31:30 of the panel power on sequencing. Software must enable this bit after training the link, and disable it when disabling the panel power state target. 0 = Backlight disabled 1 = Backlight enabled [DevCL] Reserved



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW	POWER_DOWN_ON_RESET: Enabling this bit causes the panel to power down when a reset warning comes to the GMCH from the ICH. When system reset is initiated, the embedded panel port automatically begins the panel power down sequence. If the panel is not on during a reset event, this bit is ignored. 0 = Do not run panel power down sequence when reset is detected 1 = Run panel power down sequence when system is reset
0	0b RW	POWER_STATE_TARGET: Writing this bit can occur any time, it will only be used at the completion of any current power cycle. 0 = The panel power state target is off, if the panel is either on or in a power on sequence, a power off sequence is started as soon as the panel reaches the power on state. This may include a power cycle delay. If the panel is currently off, there is no change of the power state or sequencing done. 1 = The panel power state target is on, if the panel is in either the off state or a power off sequence, if all pre-conditions are met, a power on sequence is started as soon as the panel reaches the power off state. This may include a power cycle delay. If the panel is currently off, there is no change of the power state or sequencing done. While the panel is on or in a power on sequence, the register write lock will be enabled.

14.11.41 PIPEA_PP_ON_DELAYS—Offset 61208h

PipeA Panel Power on Sequencing Delays ([DevCL, DevCTG, DevCDV]) PP On Delay values (dplrreg.v DPLRppon_sd)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61208h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
PANEL_CONTROL_PORT_SELECT	RESERVED	POWER_UP_DELAY	RESERVED_1	POWER_ON_TO_BACKLIGHT_ENABLE_DELAY				



Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	PANEL_CONTROL_PORT_SELECT: These bits define to which port the embedded panel is connected. This is used for automatic control of the panel power. If the selected port is disabled or if the port is not on pipe-B, then, the power sequence will not allow a panel power up. 00 = Reserved 01 = Panel is connected to the embedded DisplayPort B 10 = Panel is connected to the embedded DisplayPort C 11 = Reserved The selection of non-existent ports are not allowed. This programming will disable panel power sequencing logic.
29	0b RW	RESERVED: Reserved.
28:16	0b RW	POWER_UP_DELAY: Programmable value of panel power sequencing delay during panel power up. This provides the time delay for the T1+T2 time sequence. The time unit used is the 100us timer.
15:13	0b RW	RESERVED_1: Reserved.
12:0	0b RW	POWER_ON_TO_BACKLIGHT_ENABLE_DELAY: Programmable value of panel power sequencing delay during panel power up. This provides the time delay for the T5 (T3 for DisplayPort) time sequence. The time unit used is the 100us timer.

14.11.42 PIPEA_PP_OFF_DELAYS—Offset 6120Ch

PipeA Panel Power off Sequencing Delays ([DevCL, DevCTG, DevCDV]) PP Delay Off values (dplrreg.v DPLRppoff_sd)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6120Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

14.11.43 PIPEA_PP_DIVISOR—Offset 61210h

PipeA Panel Power Cycle Delay and Reference Divisor ([DevCL, DevCTG, DevCDV]) PP Divisor (dplrreg.v DPLRrefdiv_pp_cd)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61210h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00270F04h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RESERVED		POWER_DOWN_DELAY				RESERVED_1		POWER_BACKLIGHT_OFF_TO_POWER_DOWN_DELAY	

Bit Range	Default & Access	Field Name (ID): Description
31:29	0b RW	RESERVED: Reserved.
28:16	0b RW	POWER_DOWN_DELAY: Programmable value of panel power sequencing delay during power up. This provides the time delay for the T3 (T5 for DisplayPort) time sequence. The time unit used is the 100us timer.
15:13	0b RW	RESERVED_1: Reserved.
12:0	0b RW	POWER_BACKLIGHT_OFF_TO_POWER_DOWN_DELAY: Programmable value of panel power sequencing delay during power down. This provides the time delay for the Tx (T4 for DisplayPort) time sequence. The time unit used is the 100us timer.



14.11.44 PFIT_CONTROL—Offset 61230h

Intel Atom® Processor E3800 Product Family
Datasheet
707



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
PANEL_FITTING_ENABLED	PIPE_SELECT	SCALING_MODE	FILTER_COEFFICIENT_SELECT	DEBUG_FORCE_TWO_LINE_MODE	DEBUG_FORCE_THREE_PIXEL_MODE_WHEN_IN_TWO_LINE_MODE	DEBUG_CREATE_EXTRA_STALLS_IN_VGA_MODE	RESERVED	RESERVED_1
								RESERVED_2
								RESERVED_3

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	PANEL_FITTING_ENABLED: Disables the panel fitting function by forcing pixels to bypass. Panel fitting must be disabled when running VGA native modes or interlaced modes on the same pipe. Panel fitting should be enabled or disabled before the pipe is enabled. 0 = Bypass the panel fitting (1:1 ratio) 1 = Enable panel fitting (Ratios include 1:1)
30:29	01b RW	PIPE_SELECT: Indicates the pipe attached to the panel fitter 00 = Panel fitter is attached to Display Pipe A. 01 = Panel fitter is attached to Display Pipe B. This is the default after reset. 10 = Reserved for pipe C 11 = Reserved for pipe D
28:26	0b RW	SCALING_MODE: 000 = Auto-scale (source and destination should have the same aspect ratios) 001 = Programmed scaling: Values in register 61234h will be used for horizontal and vertical scaling factors 010 = Pillarbox (example: 4:3 to 16:9 auto conversion) use only when destination has wider aspect ratio than source 011 = Letterbox (example: 16:9 to 4:3 auto conversion) use only when destination has taller aspect ratio than source 1xx = Reserved
25:24	0b RW	FILTER_COEFFICIENT_SELECT: Selects the set of predefined filter coefficients to use for panel fitting 00 = Fuzzy filtering 01 = Crisp edge enhancing filtering 10 = Median between fuzzy and crisp filtering 11 = Reserved
23	0b RW	DEBUG_FORCE_TWO_LINE_MODE: debug for two line mode
22	0b RW	DEBUG_FORCE_THREE_PIXEL_MODE_WHEN_IN_TWO_LINE_MODE: debug force three pixel mode when in two line mode



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RO	RESERVED: Reserved.

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED: Reserved.

14.11.48 PIPEA_BLC_PWM_CLT2—Offset 61250h

PipeA Backlight PWM Control Register 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61250h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PWM_ENABLE	RESERVED__MBZ	RESERVED__	BACKLIGHT_POLARITY	RESERVED	PHASE_IN_INTERRUPT_STATUS	PHASE_IN_ENABLE	PHASE_IN_INTERRUPT_ENABLE	PHASE_IN_TIME_BASE
								PHASE_IN_COUNT
								PHASE_IN_INCREMENT

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	PWM_ENABLE: This bit enables the PWM counter logic 0 = PWM disabled (drives 0 always) 1 = PWM enabled
30	0b RW	RESERVED__MBZ: Reserved.
29	0b RW	RESERVED_: Reserved.
28	0b RW	BACKLIGHT_POLARITY: This field controls the polarity of the PWM signal. 0 = Active High 1 = Active Low
27	0b RW	RESERVED: MBZ
26	0b RW/1C	PHASE_IN_INTERRUPT_STATUS: This bit will be set by hardware when a Phase-In interrupt has occurred. Software will clear this bit by writing a 1, which will reset the interrupt generation. [DevCL-A,B] Reserved AccessType: One to Clear
25	0b RW	PHASE_IN_ENABLE: Setting this bit enables a PWM phase in based on the programming of the Phase In registers below. This bit clears itself when the phase in is completed.



Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	BACKLIGHT_MODULATION_FREQUENCY: This field determines the number of time base events in total for a complete cycle of modulated backlight control. This field is normally set once during initialization based on the frequency of the clock that is being used and the desired PWM frequency. This value represents the period of the PWM stream in display core clocks ([DevCTG] 100MHz HRAW clocks) multiplied by 128 or 25MHz S0IX clocks multiplied by 16.
15:0	0b RW	BACKLIGHT_DUTY_CYCLE: This field determines the number of time base events for the active portion of the PWM backlight control. This should never be larger than the frequency field. A value of zero will turn the backlight off. A value equal to the backlight modulation frequency field will be full on. This field gets updated when it is desired to change the intensity of the backlight, it will take affect at the end of the current PWM cycle. This value represents the active time of the PWM stream in display core clock ([DevCTG] HRAW clock) periods multiplied by 128 or 25MHz S0IX clocks multiplied by 16.

14.11.50 PIPEA_BLM_HIST_CTL—Offset 61260h

PipeA Image Enhancement Histogram Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61260h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	IMAGE_ENHANCEMENT_HISTOGRAM_ENABLED: This bit enables the Image Enhancement histogram logic to collect data. 0 = Image histogram is disabled 1 = The Image histogram is enabled. When this bit is changed from a zero to a one, histogram calculations will begin after the next VBLANK of the assigned pipe.
30	0b RW	IMAGE_ENHANCEMENT_MODIFICATION_TABLE_ENABLED: This bit enables the Image Enhancement modification table. 0 = disabled 1 = enabled. When this bit is changed from a zero to a one, modifications begin after the next VBLANK of the assigned pipe.
29	0b RW	RESERVED_MBZ_IMAGE_ENHANCEMENT_PIPE_ASSIGNMENT: Each pipe has its own IE function
28:25	0b RW	RESERVED: Always write as 0 s.
24	0b RW	HISTOGRAM_MODE_SELECT: 0: YUV Luma Mode 1: HSV Intensity Mode - Reserved on [DevCL]
23:16	0b RW	SYNC_TO_PHASE_IN_COUNT: This field indicates the phase in count number on which the Image Enhancement table will be loaded if the Sync to Phase in is enabled.
15	0b RW	RESERVED_1: Always write as 0.
14:13	0b RW	ENHANCEMENT_MODE: 00: Direct look up mode 01: Additive mode 10: Multiplicative mode - Reserved on [DevCL] 11: Reserved
12	0b RW	SYNC_TO_PHASE_IN: Setting this bit enables the double buffered registers to be loaded on the phase in count value specified instead of the next vblank.
11	0b RW	BIN_REGISTER_FUNCTION_SELECT: This field indicates what data is being written to or read from the bin data register. 0 = Bin Threshold Count. A read from the bin data register returns that bin s threshold value from the most recent vblank load event (guardband threshold trip). Valid range for the Bin Index is 0 to 31. 1 = Bin Image Enhancement Value. Valid range for the Bin Index is 0 to 32
10:7	0b RW	RESERVED_2: Always write as 0's.
6:0	0b RW	BIN_REGISTER_INDEX_READ_ONLY: This field indicates the bin number whose data can be accessed through the bin data register. This value is automatically incremented by a read or a write to the bin data register if the busy bit is not set.

14.11.51 PIPEA_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER—Offset 61264h

PIPEA_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER index registers

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61264h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	PIPEA_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER_REGISTER_DESCRIPTOR ONS: PIPEA_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER indexed register descriptions

14.11.52 PIPEAHISTOGRAMTHRESHOLDGUARDBANDREGISTER—Offset 61268h

pipeA histogram threshold gurband register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61268h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
HISTOGRAM_INTERRUPT_ENABLE	HISTOGRAM_EVENT_STATUS_READ_ONLY			GUARDBAND_INTERRUPT_DELAY			THRESHOLD_GUARDBAND	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	HISTOGRAM_INTERRUPT_ENABLE: 0 = Disabled 1 = Enabled. This generates a histogram interrupt once a Histogram event occurs.
30	0b RO	HISTOGRAM_EVENT_STATUS_READ_ONLY: When a Histogram event has occurred, this will get set by the hardware. For any more Histogram events to occur, the software needs to clear this bit by writing a '1'. The default state for this bit is '0'. 0 = Histogram event has not occurred. 1 = Histogram event has occurred. AccessType: Read Only
29:22	0b RW	GUARDBAND_INTERRUPT_DELAY: An interrupt is generated after this many consecutive frames of the guardband threshold being surpassed. This value is double buffered on start of vblank. A value of 0 is invalid.
21:0	0b RW	THRESHOLD_GUARDBAND: This value is used to determine the guardband for the threshold interrupt generation. This single value is used for all the segments. This value is double buffered on start of vblank

14.11.53 PIPEB_PP_STATUS—Offset 61300h

PipeB Panel Power Status Register ([DevVLVP]) PP Status (dplrreg.v panel_pwr_sr)

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61300h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 08000000h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
3:0	0b RO	INTERNAL_SEQUENCE_STATE_FOR_TEST_DEBUG: 0000 = Power Off Idle (S0.0) 0001 = Power Off, Wait for cycle delay (S0.1) 0010 = Power Off (S0.2) 0011 = Power Off (S0.3) 0100 = Reserved 0101 = Reserved 0110 = Reserved 0111 = Reserved 1000 = Power On Idle (S1.0) 1001 = Power On, (S1.1) 1010 = Power On, (S1.2) 1011 = Power On, Wait for cycle delay (S1.3) 1100 = Reserved 1101 = Reserved 1110 = Reserved 1111 = Reset

14.11.54 PIPEB_PP_CONTROL—Offset 61304h

PipeB Panel Power Control Register ([DevVLVP]) PP Control (dplrrreg.v pnl_pwr_cntl)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [GTTMMADR_LSB + 180000h] + 61304h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
WRITE_PROTECT_KEY				RESERVED				EDP_PANEL_VDD_ENABLE
								BACKLIGHT_ENABLE
								POWER_DOWN_ON_RESET
								POWER_STATE_TARGET



Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	WRITE_PROTECT_KEY: ABCD Write protect off When this field is programmed to anything except the write protect off setting and the panel is either powered up or in the process of a power up sequence, a set of registers involved in generation of panel timing or control become write protected. Any write cycles to those write protected registers, while they will complete as normal, will not change the value of the register when write protected. When this register field contains the write protect off key value, write protect will be unconditionally disabled. In situations where the embedded panel port is unused, the port should remain powered down and the write protect will be inactive. This field in normal operation should be left to all zeros and never programmed with the key value. It exists only to allow testing and workarounds. List of Write protected registers: (Panel sequencing Registers): Pipe B Panel power on sequencing delays - Address: 61308-6130Bh Pipe B Panel power off sequencing delays Address: 6130Ch 6130Fh Pipe B Panel power cycle delay and Reference Divisor Address: 61310h 61313 (DPLL registers): DPLL Control Registers FPA0 DPLL Divisor Register FPA1 DPLL Divisor Register 1 FPB0 DPLL Divisor Register FPB1 DPLL Divisor Register 1 (Display Pipe timing registers except source size) HTOTAL Horizontal Total Register HBLANK Horizontal Blank Register HSYNC_ Horizontal Sync Register VTOTAL_ Vertical Total Register VBLANK_ Vertical Blank Register VSYNC_ Vertical Sync Register
15:4	0b RW	RESERVED: Reserved.
3	0b RW	EDP_PANEL_VDD_ENABLE: [DevCDV]: Enabling this bit enables the panel vdd if the embedded panel is DisplayPort, as indicated in bits 31:30 of the panel power on sequencing. Software must enable this bit for eDP link training. After eDP link training is done, software must disable it and let the normal panel power sequencing to take control. 0 = eDP panel Vdd disabled 1 = eDP panel Vdd enabled [DevCLN] Reserved
2	0b RW	BACKLIGHT_ENABLE: [DevCTG, DevCDV]: Enabling this bit enables the panel backlight if the embedded panel is DisplayPort, as indicated in bits 31:30 of the panel power on sequencing. Software must enable this bit after training the link, and disable it when disabling the panel power state target. 0 = Backlight disabled 1 = Backlight enabled [DevCL] Reserved
1	0b RW	POWER_DOWN_ON_RESET: Enabling this bit causes the panel to power down when a reset warning comes to the GMCH from the ICH. When system reset is initiated, the embedded panel port automatically begins the panel power down sequence. If the panel is not on during a reset event, this bit is ignored. 0 = Do not run panel power down sequence when reset is detected 1 = Run panel power down sequence when system is reset
0	0b RW	POWER_STATE_TARGET: Writing this bit can occur any time, it will only be used at the completion of any current power cycle. 0 = The panel power state target is off, if the panel is either on or in a power on sequence, a power off sequence is started as soon as the panel reaches the power on state. This may include a power cycle delay. If the panel is currently off, there is no change of the power state or sequencing done. 1 = The panel power state target is on, if the panel is in either the off state or a power off sequence, if all pre-conditions are met, a power on sequence is started as soon as the panel reaches the power off state. This may include a power cycle delay. If the panel is currently off, there is no change of the power state or sequencing done. While the panel is on or in a power on sequence, the register write lock will be enabled.



14.11.55 PIPEB_PP_ON_DELAYS—Offset 61308h

PipeB Panel Power on Sequencing Delays ([DevVLVP]) PP On Delay values (dplrreg.v DPLRpPON_SD)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61308h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
PANEL_CONTROL_PORT_SELECT	RESERVED	POWER_UP_DELAY	RESERVED_1	POWER_ON_TO_BACKLIGHT_ENABLE_DELAY				

Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	PANEL_CONTROL_PORT_SELECT: These bits define to which port the embedded panel is connected. This is used for automatic control of the panel power. If the selected port is disabled or if the port is not on pipe-B, then, the power sequence will not allow a panel power up. 00 = Reserved 01 = Panel is connected to the embedded DisplayPort B 10 = Panel is connected to the embedded DisplayPort C 11 = Reserved The selection of non-existent ports are not allowed. This programming will disable panel power sequencing logic.
29	0b RW	RESERVED: Reserved.
28:16	0b RW	POWER_UP_DELAY: Programmable value of panel power sequencing delay during panel power up. This provides the time delay for the T1+T2 time sequence. The time unit used is the 100us timer.
15:13	0b RW	RESERVED_1: Reserved.
12:0	0b RW	POWER_ON_TO_BACKLIGHT_ENABLE_DELAY: Programmable value of panel power sequencing delay during panel power up. This provides the time delay for the T5 (T3 for DisplayPort) time sequence. The time unit used is the 100us timer.



14.11.58 PIPEB_BLC_PWM_CLT2—Offset 61350h

PipeB Backlight PWM Control Register 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61350h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PWM_ENABLE	RESERVED	RESERVED_1	BACKLIGHT_POLARITY	RESERVED_2	PHASE_IN_INTERRUPT_STATUS	PHASE_IN_ENABLE	PHASE_IN_INTERRUPT_ENABLE	PHASE_IN_TIME_BASE
								PHASE_IN_COUNT
								PHASE_IN_INCREMENT

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	PWM_ENABLE: This bit enables the PWM counter logic 0 = PWM disabled (drives 0 always) 1 = PWM enabled
30	0b RW	RESERVED: MBZ
29	0b RW	RESERVED_1: Reserved.
28	0b RW	BACKLIGHT_POLARITY: This field controls the polarity of the PWM signal. 0 = Active High 1 = Active Low
27	0b RW	RESERVED_2: MBZ
26	0b RW/1C	PHASE_IN_INTERRUPT_STATUS: This bit will be set by hardware when a Phase-In interrupt has occurred. Software will clear this bit by writing a 1 , which will reset the interrupt generation. [DevCL-A,B] Reserved AccessType: One to Clear
25	0b RW	PHASE_IN_ENABLE: Setting this bit enables a PWM phase in based on the programming of the Phase In registers below. This bit clears itself when the phase in is completed.
24	0b RW	PHASE_IN_INTERRUPT_ENABLE: Setting this bit enables an interrupt to be generated when the PWM phase in is completed.

14.11.59 PIPEB_BLC_PWM_CTL—Offset 61354h



Bit Range	Default & Access	Field Name (ID): Description
15:0	0b RW	BACKLIGHT_DUTY_CYCLE: This field determines the number of time base events for the active portion of the PWM backlight control. This should never be larger than the frequency field. A value of zero will turn the backlight off. A value equal to the backlight modulation frequency field will be full on. This field gets updated when it is desired to change the intensity of the backlight, it will take affect at the end of the current PWM cycle. This value represents the active time of the PWM stream in display core clock ([DevCTG] HRAW clock) periods multiplied by 128 or 25MHz S0IX clocks multiplied by 16.

14.11.60 PIPEB_BLM_HIST_CTL—Offset 61360h

PipeB Image Enhancement Histogram Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61360h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	IMAGE_ENHANCEMENT_HISTOGRAM_ENABLED				28				24				20				16				12				8				4				0						
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0								
IMAGE_ENHANCEMENT_MODIFICATION_TABLE_ENABLED				RESERVED				HISTOGRAM_MODE_SELECT				SYNC_TO_PHASE_IN_COUNT				RESERVED_1				ENHANCEMENT_MODE				SYNC_TO_PHASE_IN				BIN_REGISTER_FUNCTION_SELECT				RESERVED_2				BIN_REGISTER_INDEX_READ_ONLY			
RESERVED_MBX_IMAGE_ENHANCEMENT_PIPE_ASSIGNMENT																																							

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	IMAGE_ENHANCEMENT_HISTOGRAM_ENABLED: This bit enables the Image Enhancement histogram logic to collect data. 0 = Image histogram is disabled 1 = The Image histogram is enabled. When this bit is changed from a zero to a one, histogram calculations will begin after the next VBLANK of the assigned pipe.



Bit Range	Default & Access	Field Name (ID): Description
30	0b RW	IMAGE_ENHANCEMENT_MODIFICATION_TABLE_ENABLED: This bit enables the Image Enhancement modification table. 0 = disabled 1 = enabled. When this bit is changed from a zero to a one, modifications begin after the next VBLANK of the assigned pipe.
29	0b RW	RESERVED_MBZ_IMAGE_ENHANCEMENT_PIPE_ASSIGNMENT: Each pipe has its own dedicated IE function.
28:25	0b RW	RESERVED: Always write as 0 s.
24	0b RW	HISTOGRAM_MODE_SELECT: 0: YUV Luma Mode 1: HSV Intensity Mode - Reserved on [DevCL]
23:16	0b RW	SYNC_TO_PHASE_IN_COUNT: This field indicates the phase in count number on which the Image Enhancement table will be loaded if the Sync to Phase in is enabled.
15	0b RW	RESERVED_1: Always write as 0.
14:13	0b RW	ENHANCEMENT_MODE: 00: Direct look up mode 01: Additive mode 10: Multiplicative mode - Reserved on [DevCL] 11: Reserved
12	0b RW	SYNC_TO_PHASE_IN: Setting this bit enables the double buffered registers to be loaded on the phase in count value specified instead of the next vblank.
11	0b RW	BIN_REGISTER_FUNCTION_SELECT: This field indicates what data is being written to or read from the bin data register. 0 = Bin Threshold Count. A read from the bin data register returns that bin s threshold value from the most recent vblank load event (guardband threshold trip). Valid range for the Bin Index is 0 to 31. 1 = Bin Image Enhancement Value. Valid range for the Bin Index is 0 to 32
10:7	0b RW	RESERVED_2: Always write as 0's.
6:0	0b RO	BIN_REGISTER_INDEX_READ_ONLY: This field indicates the bin number whose data can be accessed through the bin data register. This value is automatically incremented by a read or a write to the bin data register if the busy bit is not set. AccessType: Read Only

14.11.61 PIPEB_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER—Offset 61364h

PIPEB_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER index registers

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61364h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	PIPEB_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER_REGISTER_DESCRIPTORS : PIPEB_IMAGE_ENHANCEMENT_BIN_DATA_REGISTER indexed register descriptions

14.11.62 PIPEBHISTOGRAMTHRESHOLDGUARDBANDREGISTER—Offset 61368h

pipe B histogram threshold gurband register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61368h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
HISTOGRAM_INTERRUPT_ENABLE	HISTOGRAM_EVENT_STATUS_READ_ONLY	GUARDBAND_INTERRUPT_DELAY				THRESHOLD_GUARDBAND		

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	HISTOGRAM_INTERRUPT_ENABLE: 0 = Disabled 1 = Enabled. This generates a histogram interrupt once a Histogram event occurs.
30	0b RO	HISTOGRAM_EVENT_STATUS_READ_ONLY: When a Histogram event has occurred, this will get set by the hardware. For any more Histogram events to occur, the software needs to clear this bit by writing a '1'. The default state for this bit is '0'. 0 = Histogram event has not occurred. 1 = Histogram event has occurred. AccessType: Read Only
29:22	0b RW	GUARDBAND_INTERRUPT_DELAY: An interrupt is generated after this many consecutive frames of the guardband threshold being surpassed. This value is double buffered on start of vblank. A value of 0 is invalid.
21:0	0b RW	THRESHOLD_GUARDBAND: This value is used to determine the guardband for the threshold interrupt generation. This single value is used for all the segments. This value is double buffered on start of vblank

14.11.63 MIPIC_PORT_CTRL—Offset 61700h

mipi C port ctrl

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61700h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EN	RESERVED	DITHER	RESERVED_1	RESERVED_2	RESERVED_3	RESERVED_4	RESERVED_5	RESERVED_6
								RESERVED_7
							DELAY	EFFECT
								RESERVED_8



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	EN: When this bit is disabled the MIPI DPI (video mode) is inactive and in it's low power state. When it is enable it starts to generate timing for this MIPI port 0 = The port is disabled and all MIPI DPI interface are disable (timing generator is off) 1 = The port is enabled
30:26	0b RW	RESERVED: Reserved.
25	0b RW	DITHER: This bit enables or disables (bypassing) 8-6-bit color dithering function. The usage of this bit would be on for 18-bpp panels and off for 24-bpp panels. 0 = disabled 1 = enabled
24:22	0b RW	RESERVED_1: Reserved.
21	0b RW	RESERVED_2: Reserved.
20	0b RW	RESERVED_3: Reserved.
19	0b RW	RESERVED_4: Reserved.
18:16	0b RW	RESERVED_5: Reserved.
15	0b RW	RESERVED_6: Reserved.
14:5	0b RW	RESERVED_7: Reserved.
4	0b RW	DELAY: When set, the TE counter will be count down until
3:2	0b RW	EFFECT: 00: No tearing effect required - memory write start as soon as write data is available 01: TE trigger by MIPI DPHY and DSI protocol 10: TE trigger by GPIO pin 11: Reserved
1:0	0b RW	RESERVED_8: Reserved.

14.11.64 MIPIC_TEARING_CTR—Offset 61704h

mipi C tearing ctr

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 61704h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED				TE				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	RESERVED: Reserved.
15:0	0b RW	TE: Number of delay clocks from TE trigger to start sending data to DSI controller

14.11.65 AUD_CONFIG_A—Offset 62000h

Audio Configuration Pipe A

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62000h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED	N_VALUE_INDEX	UPPER_N_VALUE_TESTMODE	PIXEL_CLOCK_HDMI	LOWER_N_VALUE_TESTMODE	DISABLE_NCTS	RESERVED_1		
	N_PROGRAMMING_ENABLE_TESTMODE							

Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	RESERVED: Project: All Format:



Bit Range	Default & Access	Field Name (ID): Description
29	0b RW	N_VALUE_INDEX: Project: All Default Value: 0b Value Name Description Project 0b HDMI N value read on bits 27:20 and 15:4 reflects HDMI N value. Bits 27:20 and 15:4 are is programmable to any N value - default h7FA6. All 1b DP N value read on bits 27:20 and 15:4 reflects DP N value. Set this bit to 1 before programming N value register. When this is set to 1, 27:20 and 15:4 will reflect the current N value default h8000. All
28	0b RW	N_PROGRAMMING_ENABLE_TESTMODE: Project: All Security: Test This bit enables programming of N values for non-CEA modes. Please note that the Pipe to which audio is attached must be disabled when changing this field.
27:20	0b RW	UPPER_N_VALUE_TESTMODE: Project: All Security: Test These are bits [19:12] of programmable N values for non-CEA modes. Bit 25 of this register must also be written in order to enable programming. Please note that the Pipe to which audio is attached must be disabled when changing this field. This register can also be used to program N value for DP for a specific Port. Default value on this register when bit 29 is set to 1 is h7FA6
19:16	0b RW	PIXEL_CLOCK_HDMI: Project: All Default Value: 0b This is the target frequency of the CEA/HDMI video mode to which the audio stream is added. This value is used for generating N_CTS packets. This refers to only HDMI Pixel clock and does not refer to DP Link clock. DP Link clock does not require this programming. Note: The Pipe on which audio is attached must be disabled when changing this field. Value Name Description Project 0000b 25.2 / 1.001 MHz 25.2 / 1.001 MHz All 0001b 25.2 MHz 25.2 MHz Program this value for pixel clocks not listed in this field All 0010b 27 MHz 27 MHz All 0011b 27 * 1.001 MHz 27 * 1.001 MHz All 0100b 54 MHz 54 MHz All 0101b 54 * 1.001 MHz 54 * 1.001 MHz All 0110b 74.25 / 1.001 MHz 74.25 / 1.001 MHz All 0111b 74.25 MHz 74.25 MHz All 1000b 148.5 / 1.001 MHz 148.5 / 1.001 MHz All 1001b 148.5 MHz 148.5 MHz All Others Reserved Reserved All
15:4	0b RW	LOWER_N_VALUE_TESTMODE: Project: All Security: Test These are bits [11:0] of programmable N values for non-CEA modes. Bit 25 of this register must also be written in order to enable programming. Please note that the Pipe to which audio is attached must be disabled when changing this field. This register can also be used to program N value for DP for a specific Port. Default value on this register when bit 29 is set to 1 is h7FA6
3	0b RW	DISABLE_NCTS: Project: All Set this bit to disable N and CTS or M generation for CTM modes. This is to enable prediction of CRC in CTM modes.
2:0	0b RW	RESERVED_1: Project: All Format:

14.11.66 AUD_MISC_CTRL_A—Offset 62010h

Audio MISC Control for Pipe A

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62010h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000044h

14.11.67 AUD_VID_DID—Offset 62020h

Audio Vendor ID / Device ID

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62020h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED							RESERVED_1	
RESERVED							RESERVED_2	
RESERVED							RESERVED_3	
RESERVED							RESERVED_4	
RESERVED							RESERVED_5	
RESERVED							RESERVED_6	
RESERVED							RESERVED_7	
RESERVED							RESERVED_8	
RESERVED							RESERVED_9	
RESERVED							RESERVED_10	
RESERVED							RESERVED_11	
RESERVED							RESERVED_12	
RESERVED							RESERVED_13	
RESERVED							RESERVED_14	
RESERVED							RESERVED_15	
RESERVED							RESERVED_16	
RESERVED							RESERVED_17	
RESERVED							RESERVED_18	
RESERVED							RESERVED_19	
RESERVED							RESERVED_20	
RESERVED							RESERVED_21	
RESERVED							RESERVED_22	
RESERVED							RESERVED_23	
RESERVED							RESERVED_24	
RESERVED							RESERVED_25	
RESERVED							RESERVED_26	
RESERVED							RESERVED_27	
RESERVED							RESERVED_28	
RESERVED							RESERVED_29	
RESERVED							RESERVED_30	
RESERVED							RESERVED_31	
RESERVED							RESERVED_32	
RESERVED							RESERVED_33	
RESERVED							RESERVED_34	
RESERVED							RESERVED_35	
RESERVED							RESERVED_36	
RESERVED							RESERVED_37	
RESERVED							RESERVED_38	
RESERVED							RESERVED_39	
RESERVED							RESERVED_40	
RESERVED							RESERVED_41	
RESERVED							RESERVED_42	
RESERVED							RESERVED_43	
RESERVED							RESERVED_44	
RESERVED							RESERVED_45	
RESERVED							RESERVED_46	
RESERVED							RESERVED_47	
RESERVED							RESERVED_48	
RESERVED							RESERVED_49	
RESERVED							RESERVED_50	
RESERVED							RESERVED_51	
RESERVED							RESERVED_52	
RESERVED							RESERVED_53	
RESERVED							RESERVED_54	
RESERVED							RESERVED_55	
RESERVED							RESERVED_56	
RESERVED							RESERVED_57	
RESERVED							RESERVED_58	
RESERVED							RESERVED_59	
RESERVED							RESERVED_60	
RESERVED							RESERVED_61	
RESERVED							RESERVED_62	
RESERVED							RESERVED_63	
RESERVED							RESERVED_64	
RESERVED							RESERVED_65	
RESERVED							RESERVED_66	
RESERVED							RESERVED_67	
RESERVED							RESERVED_68	
RESERVED							RESERVED_69	
RESERVED							RESERVED_70	
RESERVED							RESERVED_71	
RESERVED							RESERVED_72	
RESERVED							RESERVED_73	
RESERVED							RESERVED_74	
RESERVED							RESERVED_75	
RESERVED							RESERVED_76	
RESERVED							RESERVED_77	
RESERVED							RESERVED_78	
RESERVED							RESERVED_79	
RESERVED							RESERVED_80	
RESERVED							RESERVED_81	
RESERVED							RESERVED_82	
RESERVED							RESERVED_83	
RESERVED							RESERVED_84	
RESERVED							RESERVED_85	
RESERVED							RESERVED_86	
RESERVED							RESERVED_87	
RESERVED							RESERVED_88	
RESERVED							RESERVED_89	
RESERVED							RESERVED_90	
RESERVED							RESERVED_91	
RESERVED							RESERVED_92	
RESERVED							RESERVED_93	
RESERVED							RESERVED_94	
RESERVED							RESERVED_95	
RESERVED							RESERVED_96	
RESERVED							RESERVED_97	
RESERVED							RESERVED_98	
RESERVED							RESERVED_99	
RESERVED							RESERVED_100	
RESERVED							RESERVED_101	
RESERVED							RESERVED_102	
RESERVED							RESERVED_103	
RESERVED							RESERVED_104	
RESERVED							RESERVED_105	
RESERVED							RESERVED_106	
RESERVED							RESERVED_107	
RESERVED							RESERVED_108	
RESERVED							RESERVED_109	
RESERVED							RESERVED_110	
RESERVED							RESERVED_111	
RESERVED							RESERVED_112	
RESERVED							RESERVED_113	
RESERVED							RESERVED_114	
RESERVED							RESERVED_115	
RESERVED							RESERVED_116	
RESERVED							RESERVED_117	
RESERVED							RESERVED_118	
RESERVED							RESERVED_119	
RESERVED							RESERVED_120	
RESERVED							RESERVED_121	
RESERVED							RESERVED_122	
RESERVED							RESERVED_123	
RESERVED							RESERVED_124	
RESERVED							RESERVED_125	
RESERVED							RESERVED_126	
RESERVED							RESERVED_127	
RESERVED							RESERVED_128	
RESERVED							RESERVED_129	
RESERVED							RESERVED_130	
RESERVED							RESERVED_131	
RESERVED							RESERVED_132	
RESERVED							RESERVED_133	
RESERVED							RESERVED_134	
RESERVED							RESERVED_135	
RESERVED							RESERVED_1	

Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	RESERVED: Project: All Format: MBZ
8	0b RW	SAMPLE_PRESENT_DISABLE: Project: All Security: Debug This bit is used to Disable sample present for HDMI or DP (Chicken Bit)
7:4	0100b RW	OUTPUT_DELAY: Project: All Default Value: 0100b The number of samples between when the sample is received from the HD Audio link and when it appears as an analog signal at the pin.
3	0b RW	RESERVED_1: Project: All Format: MBZ
2	1b RW	SAMPLE_FABRICATION_EN_BIT: Project: All Access: R/W Default Value: ;1b This bit indicates whether internal fabrication of audio samples is enabled during a link underrun. Value Name Description Project 0b Disable Audio fabrication disabled All 1b Enable Audio fabrication enabled All
1	0b RW	PRO_ALLOWED: Project: All Access: R/W Default Value: 0b By default, the audio device is configured to consumer mode and does not allow the mode to be changed to professional mode by an HD Audio verb. When Pro is allowed by setting this configuration bit, the HD Audio codec allows a verb to set the device into professional mode. Note: Setting this configuration bit does not change the default Pro bit value to be 1. Pro must be set to 1 through the normal process, using a verb. Value Name Description Project 0b Consumer Consumer use only All 1b Professional Professional use allowed All
0	0b RW	RESERVED_2: All Format: MBZ



Default: 80862882h

31	28	24	20	16	12	8	4	0
1	0	0	0	0	0	0	1	0
0	0	0	0	1	0	1	0	0
0	0	0	0	0	0	0	0	0
VENDOR_ID				DEVICE_ID				

Bit Range	Default & Access	Field Name (ID): Description
31:16	100000001 0000110b RO	VENDOR_ID: Project: All Format: U16 Used to identify the codec within the PnP system. This field is hardwired within the device. Value = 0x8086
15:0	001010001 0000010b RO	DEVICE_ID: Project: All Format: U16 Constant used to identify the codec within the PnP system. This field is set by the device hardware. Value = 0x2882 [Valleyview2]

14.11.68 AUD_RID—Offset 62024h

Audio Revision ID

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62024h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00100000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	1	0	0	0	0	0
RESERVED				MAJOR_REVISION	MINOR_REVISION	REVISION_ID	STEPPING_ID	

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RO	RESERVED: Project: All Format:
23:20	0001b RO	MAJOR_REVISION: Project: All Default Value: 0001b The major revision number (left of the decimal) of the HD Audio Spec to which the codec is fully compliant. This field is hardwired within the device. Value = 0x1
19:16	0b RO	MINOR_REVISION: Project: All The minor revision number (rights of the decimal) or dot number of the HD Audio Spec to which the codec is fully compliant. This field is hardwired within the device. Value = 0x0
15:8	0b RO	REVISION_ID: Project: All The vendors revision number for this given Device ID. This field is hardwired within the device. Value = 0x0

14.11.70 AUD_PWRST—Offset 6204Ch

Audio Power State (Function Group, Convertor, Pin Widget)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 6204Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00FFFFFFh

31				28				24				20				16				12				8				4				0																																																																							
0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1																																																																										
RESERVED								FUNCTION_GROUP_DEVICE_POWER_STATE_CURRENT								FUNCTION_GROUP_DEVICE_POWER_STATE_SET								CONVERTORB_WIDGET_POWER_STATE_CURRENT								CONVERTORB_WIDGET_POWER_STATE_REQUESTED								CONVERTORA_WIDGET_POWER_STATE_CURRENT								CONVERTORA_WIDGET_POWER_STATE_REQUESTED								PIND_WIDGET_POWER_STATE_CURRENT								PIND_WIDGET_POWER_STATE_SET								PINC_WIDGET_POWER_STATE_CURRENT								PINC_WIDGET_POWER_STATE_SET								PINB_WIDGET_POWER_STATE_CURRENT								PINB_WIDGET_POWER_STATE_SET							

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RO	RESERVED: Project: All Format:
23:22	11b RO	FUNCTION_GROUP_DEVICE_POWER_STATE_CURRENT: Project: All Format: Audio Power State Format Current power state Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All
21:20	11b RO	FUNCTION_GROUP_DEVICE_POWER_STATE_SET: Project: All Format: Audio Power State Format Power state that was set Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All



Bit Range	Default & Access	Field Name (ID): Description
19:18	11b RO	CONVERTORB_WIDGET_POWER_STATE_CURRENT: Project: All Format: Audio Power State Format Current power state Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All
17:16	11b RO	CONVERTORB_WIDGET_POWER_STATE_REQUESTED: Project: All Format: Audio Power State Format Power state that was requested by audio software Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All
15:14	11b RO	CONVERTORA_WIDGET_POWER_STATE_CURRENT: Project: All Format: Audio Power State Format Current power state Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All
13:12	11b RO	CONVERTORA_WIDGET_POWER_STATE_REQUESTED: Project: All Format: Audio Power State Format Power state that was requested by audio software Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All
11:10	11b RO	PIND_WIDGET_POWER_STATE_CURRENT: Project: All Format: Audio Power State Format Current power state Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All
9:8	11b RO	PIND_WIDGET_POWER_STATE_SET: Project: All Format: Audio Power State Format Power state that was set Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All
7:6	11b RO	PINC_WIDGET_POWER_STATE_CURRENT: Project: All Format: Audio Power State Format Current power state Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All



Bit Range	Default & Access	Field Name (ID): Description
5:4	11b RO	PINC_WIDGET_POWER_STATE_SET: Project: All Format: Audio Power State Format Power state that was set Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All
3:2	11b RO	PINB_WIDGET_POWER_STATE_CURRENT: Project: All Format: Audio Power State Current power state
1:0	11b RO	PINB_WIDGET_POWER_STATE_SET: Project: All Format: Audio Power State Format Power state that was set Project: All Default Value: ;11b D3 Value Name Description Project 00b D0 D0 All 01b,10b Unsupported Unsupported All 11b D3 D3 All

14.11.71 AUD HDMIW HDMIEDID A—Offset 62050h

HDMI Data EDID Block Pipe A

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62050h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EDID_HDMI_DATA_BLOCK								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	EDID_HDMI_DATA_BLOCK: Project: All Format: Please note that the contents of this buffer are not cleared when ELD is disabled. The contents of this buffer are cleared during gfx reset



Bit Range	Default & Access	Field Name (ID): Description
23:20	0b RO	STREAM_ID: Project: All Format: Represents the link stream used by the converter for data input or output. This value is set in the Channel ID and Stream ID through the Set Audio Output Converter Widget command. Default = 0 (stream 0)
19:16	0b RO	LOWEST_CHANNEL_NUMBER: Project: All Format: Represents the lowest channel used by the converter. This value is set in the Channel ID and Stream ID through the Set Audio Output Converter Widget command. Default = 0
15	0b RO	RESERVED_1: Project: All Format:
14:8	0b RO	CATEGORY_CODE: Project: All Format: S/PDIF IEC Category Code. This value is set in the Digital Converter 1 through the Set Audio Output Converter Widget command. Default = 0
7	0b RO	LEVEL: Project: All Format: S/PDIF IEC Generation Level. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Default = 0
6	0b RO	PRO: Project: All Default Value: 0b This bit indicates professional or consumer use of channel. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. This value can only be set to 1 if the Pro Allowed bit is set in the audio configuration register. Value Name Description Project 0b Consumer Consumer use All 1b Professional Professional use All
5	0b RO	NON_AUDIO: Project: All Default Value: 0b Data is non PCM format. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b PCM Data is PCM All 1b Non PCM Data is non PCM format All
4	0b RO	COPY: Project: All Default Value: 0b Copyright asserted. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b Not Asserted Copyright is not asserted All 1b Asserted Copyright is asserted All
3	0b RO	PRE: Project: All Default Value: 0b Filter preemphasis. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b Disabled Preemphasis is disabled All 1b Enabled Filter preemphasis is enabled All
2	0b RO	VCFG: Project: All Format: Validity Configuration. Determines S/PDIF transmitter behavior when data is not being transmitted. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Default = 0
1	0b RO	V: Project: All Format: Affects the validity flag transmitted in each subframe, and enables the S/PDIF transmitter to maintain connection during error or mute conditions. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Default = 0
0	0b RO	RESERVED_2: All Format: MBZ



Bit Range	Default & Access	Field Name (ID): Description
10:8	0b RO	SAMPLE_BASE_RATE_DIVISOR: Project: All Default Value: 000b 48 kHz Audio stream sample base rate divisor. Value Name Description Project 000b Div 1 Divide by 1 (48 kHz, 44.1 kHz) All 001b Div 2 Divide by 2 (24 kHz, 22.05 kHz) All 010b Div 3 Divide by 3 (16 kHz, 32 kHz) All 011b Div 4 Divide by 4 (11.025 kHz) All 100b Div 5 Divide by 5 (9.6 kHz) All 101b Div 6 Divide by 6 (8 kHz) All 110b Div 7 Divide by 7 All 111b Div 8 Divide by 8 (6 kHz) All
7	0b RO	RESERVED_3: Project: All Format: MBZ
6:4	011b RO	BITS_PER_SAMPLE: Project: All Default Value: 011b 32 bits Value Name Description Project 000b 8 bit The data will be packed in memory in 8 bit containers on 16 bit boundaries All 001b 16 bits The data will be packed in memory in 16 bit containers on 16 bit boundaries All 100b 20 bits The data will be packed in memory in 20 bit containers on 32 bit boundaries All 010b 24 bits The data will be packed in memory in 32 bit containers on 32 bit boundaries All 011b 32 bits The data will be packed in memory in 32 bit containers on 32 bit boundaries All Others Reserved Reserved All
3:0	0010b RO	NUMBER_OF_CHANNELS_IN_A_STREAM: Project: All Default Value: 0010b 3 channels in each frame Format: U4+1 Binary value plus 1. 0000 = 1, 1111 = 16 Number of channels in each frame of the stream.

14.11.76 AUD_OUT_CH_STR—Offset 62088h

Audio Channel ID and Stream ID

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62088h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	RESERVED		CONVERTER_CHANNEL_MAP_PORTD	DIGITAL_DISPLAY_AUDIO_INDEX_PORTD	CONVERTER_CHANNEL_MAP_PORTC	HDMI_INDEX_PORTC	CONVERTER_CHANNEL_MAP_PORTB	HDMI_INDEX_PORTB

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RO	RESERVED: Project: All Format:
23:20	0b RO	CONVERTER_CHANNEL_MAP_PORTD: Project: All The number in this field reflects the HD audio channel to which the Digital Display Audio channel in bits 19:16 is mapped. This field is read only
19:16	0b RO	DIGITAL_DISPLAY_AUDIO_INDEX_PORTD: Project: All This field is the Digital Display Audio channel number. When these bits are written, the audio channel number assigned to the Digital Display Audio channel number are reflected in bits 20:23 of this register.
15:12	0b RO	CONVERTER_CHANNEL_MAP_PORTC: Project: All The number in this field reflects the HD audio channel to which the Digital Display Audio channel in bits 11:8 is mapped. This field is read only
11:8	0b RO	HDMI_INDEX_PORTC: Project: All This field is the Digital Display Audio channel number. When these bits are written, the audio channel number assigned to the Digital Display Audio channel number are reflected in bits 12:15 of this register.
7:4	0b RO	CONVERTER_CHANNEL_MAP_PORTB: Project: All The number in this field reflects the HD audio channel to which the Digital Display Audio channel in bits 3:0 is mapped. This field is read only
3:0	0b RO	HDMI_INDEX_PORTB: Project: All This field is the Digital Display Audio channel number. When these bits are written, the audio channel number assigned to the Digital Display Audio channel number are reflected in bits 4:7 of this register.

14.11.77 AUD_PINW_CONNLNG_LIST—Offset 620A8h

Audio Connection List

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 620A8h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00030202h



Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RO	RESERVED: Project: All Format:
23:8	000000110 0000010b RO	CONNECTION_LIST_ENTRY: Project: All Default Value: 0000001100000010b Connection to Convertor Widget Node 0x0302
7	0b RO	LONG_FORM: Project: All Default Value: 0b This bit indicates whether the items in the connection list are long form or short form. This bit is hardwired to 0 (items in connection list are short form)
6:0	10b RO	CONNECTION_LIST_LENGTH: Project: All Default Value: 02h This field indicates the number of items in the connection list. If this field is 2, there is only one hardwired input possible, which is read from the Connection List, and there is no Connection Select Control.

Audio Connection Select

Access Method

Offset: [GTTMMADR LSB + 180000h] + 620ACh

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h



Audio Control State Register Pipe A

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 620B4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

31				28				24				20				16				12				8				4				0											
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 1 0 1				0 1 0 0				0 0 0 0				0 0 0 0				0 0 0 0											
RESERVED				DIP_PORT_SELECT				RESERVED_1				DIP_TYPE_ENABLE_STATUS				DIP_BUFFER_INDEX				DIP_TRANSMISSION_FREQUENCY				RESERVED_2				ELD_BUFFER_SIZE				ELD_ACCESS_ADDRESS				ELD_ACK				DIP_RAM_ACCESS_ADDRESS			



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	RESERVED: Project: All Format: MBZ
30:29	0b RO	DIP_PORT_SELECT: Project: All AccessType: Read Only Default Value: 00b This read-only bit reflects which port is used to transmit the DIP data. This can only change when DIP is disabled. If one or more audio-related DIP packets is enabled and audio is enabled on a digital port, these bits will reflect the digital port to which audio is directed. Value Name Description Project 00b Reserved Reserved All 01b Digital Port B Digital Port B All 10b Digital Port C Digital Port C All 11b Digital Port D Digital Port D All
28:25	0b RW	RESERVED_1: Project: All Format: MBZ
24:21	0b RO	DIP_TYPE_ENABLE_STATUS: Project: All AccessType: Read Only Default Value: 0000b These bits reflect the DIP types enabled. It can be updated while the port is enabled. Within 2 vblank periods, the DIP is guaranteed to have been transmitted. Disabling a DIP type results in setting the contents of that DIP buffer to zero. A reserved setting reflects a disabled DIP. Value Name Description Project XXX0b Disable Audio DIP disabled All XXX1b Enable Audio DIP enabled All XX0Xb Disable Generic 1 (ACP) DIP disabled All XX1Xb Enable Generic 1 (ACP) DIP enabled All X0XXb Disable Generic 2 DIP disabled All X1XXb Enable Generic 2 DIP enabled, can be used by ISRC1 or ISRC2 All 1XXXb Reserved Reserved All
20:18	0b RW	DIP_BUFFER_INDEX: Project: All Default Value: 0000b This field is used during read of different DIPs, and during read or write of ELD data. These bits are used as an index to their respective DIP or ELD buffers. When the index is not valid, the contents of the DIP will return all 0s. Value Name Description Project 000b Audio Audio DIP (31 bytes of address space, 31 bytes of data) All 001b Gen 1 Generic 1 (ACP) Data Island Packet (31 bytes of address space, 31 bytes of data) All 010b Gen 2 Generic 2 (ISRC1) Data Island Packet (31 bytes of address space, 31 bytes of data) All 011b Gen 3 Generic 3 (ISRC2) Data Island Packet (31 bytes of address space, 31 bytes of data) All 1XXb Reserved Reserved All
17:16	0b RO	DIP_TRANSMISSION_FREQUENCY: Project: All AccessType: Read Only Default Value: 00b These bits reflect the frequency of DIP transmission for the DIP buffer type designated in bits 20:18. When writing DIP data, this value is also latched when the first DW of the DIP is written. When read, this value reflects the DIP transmission frequency for the DIP buffer designated in bits 20:18. Value Name Description Project 00b Disable Disabled All 01b Reserved Reserved All 10b Send Once Send Once All 11b Best Effort Best effort (Send at least every other vsync) All
15	0b RW	RESERVED_2: Project: All Format: MBZ
14:10	10101b RO	ELD_BUFFER_SIZE: Project: All AccessType: Read only 10101 = This field reflects the size of the ELD buffer in DWORDs (84 Bytes of ELD)



Bit Range	Default & Access	Field Name (ID): Description
7:6	0b RW	RESERVED_1: Project: All Format:
5	0b RW	CP_READYC: Project: All Default Value: 0b See CP_ReadyD description. Value Name Description Project 0b Not Ready CP request pending or not ready to receive requests All 1b Ready CP request ready All
4	0b RW	ELD_VALIDC: Project: All Default Value: 0b See ELD_validD description. Value Name Description Project 0b Invalid ELD data invalid (default, when writing ELD data, set 0 by software) All 1b Valid ELD data valid (Set by video software only) All
3:2	0b RW	RESERVED_2: Project: All Format:
1	0b RW	CP_READYB: Project: All Default Value: 0b See CP_ReadyD description. Value Name Description Project 0b Not Ready CP request pending or not ready to receive requests All 1b Ready CP request ready All
0	0b RW	ELD_VALIDB: Project: All Default Value: 0b See ELD_validD description. Value Name Description Project 0b Invalid ELD data invalid (default, when writing ELD data, set 0 by software) All 1b Valid ELD data valid (Set by video software only) All

14.11.81 AUD_HDMIW_STATUS—Offset 620D4h

Audio HDMI Status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 620D4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CONV_B_CDCLK_DOTCLK_FIFO_UNDERRUN	CONV_B_CDCLK_DOTCLK_FIFO_OVERRUN	CONV_A_CDCLK_DOTCLK_FIFO_UNDERRUN	CONV_A_CDCLK_DOTCLK_FIFO_OVERRUN	RESERVED	BCLK_CDCLK_FIFO_OVERRUN	FUNCTION_RESET	RESERVED_1	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	CONV_B_CDCLK_DOTCLK_FIFO_UNDERRUN: Project: All This bit indicates an underrun in the FIFO inside the clock crossing logic between CDCLK and DOTCLK. Clearing this status bit is accomplished by writing a 1 to this bit through MMIO.
30	0b RW	CONV_B_CDCLK_DOTCLK_FIFO_OVERRUN: Project: All This bit indicates an overrun in the FIFO inside the clock crossing logic between CDCLK and DOTCLK. Clearing this status bit is accomplished by writing a 1 to this bit through MMIO.
29	0b RW	CONV_A_CDCLK_DOTCLK_FIFO_UNDERRUN: Project: All This bit indicates an underrun in the FIFO inside the clock crossing logic between CDCLK and DOTCLK. Clearing this status bit is accomplished by writing a 1 to this bit through MMIO.
28	0b RW	CONV_A_CDCLK_DOTCLK_FIFO_OVERRUN: Project: All This bit indicates an overrun in the FIFO inside the clock crossing logic between CDCLK and DOTCLK. Clearing this status bit is accomplished by writing a 1 to this bit through MMIO.
27:26	0b RW	RESERVED: Project: All Format:
25	0b RW	BCLK_CDCLK_FIFO_OVERRUN: Project: All This bit indicates an overrun in the FIFO inside the clock crossing logic between BCLK and CDCLK. Clearing this status bit is accomplished by writing a 1 to this bit through MMIO.
24	0b RW	FUNCTION_RESET: Project: All Security: Debug This bit indicates that an audio function reset occurred through the reset signal on the HD audio bus. Clearing this status bit is accomplished by writing a 1 to this bit through MMIO.
23:0	0b RW	RESERVED_1: Project: All Format:



14.11.82 AUD_CONFIG_B—Offset 62100h

Audio Configuration Pipe B

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62100h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED	N_VALUE_INDEX	N_PROGRAMMING_ENABLE_TESTMODE	UPPER_N_VALUE_TESTMODE	PIXEL_CLOCK_HDMI	LOWER_N_VALUE_TESTMODE	DISABLE_NCTS	RESERVED_1	

Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	RESERVED: Project: All Format:
29	0b RW	N_VALUE_INDEX: Project: All Default Value: 0b Value Name Description Project 0b HDMI N value read on bits 27:20 and 15:4 reflects HDMI N value. Bits 27:20 and 15:4 are is programmable to any N value - default h7FA6. All 1b DP N value read on bits 27:20 and 15:4 reflects DP N value. Set this bit to 1 before programming N value register. When this is set to 1, 27:20 and 15:4 will reflect the current N value default h8000. All
28	0b RW	N_PROGRAMMING_ENABLE_TESTMODE: Project: All Security: Test See Pipe A description.
27:20	0b RW	UPPER_N_VALUE_TESTMODE: Project: All Security: Test See Pipe A description

14.11.83 AUD_MISC_CTRL_B—Offset 62110h

Audio MISC Control for Pipe B

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62110h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000044h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 1 0 0	0 1 0 0
RESERVED						SAMPLE_PRESENT_DISABLE	OUTPUT_DELAY	RESERVED_1
								SAMPLE_FABRICATION_EN_BIT
								PRO_ALLOWED
								RESERVED_2

Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	RESERVED: Project: All Format: MBZ

14.11.86 AUD HDMIW INFOFR B—Offset 62154h

Audio Widget Data Island Packet Pipe B

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 62154h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DATA_ISLAND_PACKET_DATA								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RO	DATA_ISLAND_PACKET_DATA: Project: All Format: See Pipe A description.

14.11.87 AUD_OUT_DIG_CNVT_B—Offset 62180h

Audio Digital Converter Conv B

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62180h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
0	0b RO	RESERVED_2: All Format: MBZ

14.11.88 AUD_OUT_STR_DESC_B—Offset 62184h

Audio Stream Descriptor Format Conv B

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62184h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000032h

	31	28	24	20	16	12	8	4	0
	0	0	0	0	0	0	0	0	0
RESERVED									
HBR_ENABLE									
RESERVED_1									
CONVERTOR_CHANNEL_COUNT									
RESERVED_2									
SAMPLE_BASE_RATE									
SAMPLE_BASE_RATE_MULT									
SAMPLE_BASE_RATE_DIVISOR									
RESERVED_3									
BITS_PER_SAMPLE									
NUMBER_OF_CHANNELS_IN_A_STREAM									

Bit Range	Default & Access	Field Name (ID): Description
31:29	0b RO	RESERVED: Project: All Format:
28:27	0b RO	HBR_ENABLE: Project: All Format: See Conv A description.
26:21	0b RO	RESERVED_1: Project: All Format:
20:16	0b RO	CONVERTOR_CHANNEL_COUNT: Project: All Format: See Conv A description.
15	0b RO	RESERVED_2: Project: All Format:
14	0b RO	SAMPLE_BASE_RATE: Project: All Default Value: 0b 48 kHz See Conv A description. Value Name Description Project 0b 48 kHz 48 kHz All 1b 44.1 kHz 44.1 kHz All



Bit Range	Default & Access	Field Name (ID): Description
13:11	0b RO	SAMPLE_BASE_RATE_MULT: Project: All Default Value: 000b 48 kHz See Conv A description. Value Name Description Project 000b x1 x1 (48 kHz/44.1 kHz or less) All 001b x2 x2 (96 kHz, 88.2 kHz, 32 kHz) All 010b x3 x3 (144 kHz) All 011b x4 x4 (192 kHz, 176.4 kHz) All 1XXb Reserved Reserved All
10:8	0b RO	SAMPLE_BASE_RATE_DIVISOR: Project: All Default Value: 000b 48 kHz See Conv A description. Value Name Description Project 000b Div 1 Divide by 1 (48 kHz, 44.1 kHz) All 001b Div 2 Divide by 2 (24 kHz, 22.05 kHz) All 010b Div 3 Divide by 3 (16 kHz, 32 kHz) All 011b Div 4 Divide by 4 (11.025 kHz) All 100b Div 5 Divide by 5 (9.6 kHz) All 101b Div 6 Divide by 6 (8 kHz) All 110b Div 7 Divide by 7 All 111b Div 8 Divide by 8 (6 kHz) All
7	0b RO	RESERVED_3: Project: All Format: MBZ
6:4	011b RO	BITS_PER_SAMPLE: Project: All Default Value: 011b 32 bits Value Name Description Project 000b 8 bit The data will be packed in memory in 8 bit containers on 16 bit boundaries All 001b 16 bits The data will be packed in memory in 16 bit containers on 16 bit boundaries All 100b 20 bits The data will be packed in memory in 20 bit containers on 32 bit boundaries All 010b 24 bits The data will be packed in memory in 24 bit containers on 32 bit boundaries All 011b 32 bits The data will be packed in memory in 32 bit containers on 32 bit boundaries All others Res. Reserved All
3:0	0010b RO	NUMBER_OF_CHANNELS_IN_A_STREAM: Project: All Default Value: 0010b 3 channels in each frame Format: U4+1 Binary value plus 1. 0000 = 1, 1111 = 16 See Conv A description.

14.11.89 AUD_CNTL_ST_B—Offset 621B4h

Audio Control State Register Pipe B

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 621B4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00005400h



Intel Atom® Processor E3800 Product Family
Datasheet
759



14.11.91 AUD PWST1 DBG—Offset 62F04h

audion pwst1 debug

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 62F04h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000C0Fh

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
RESERVED						1	1	0	0	0	0	1	1	1	1
						FUNCTION_GROUP_DEVICE_POWER_STATE		RESERVED_1				CONVERTORA_WIDGET_POWER_STATE			
												PINB_WIDGET_POWER_STATE			

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b WO	RESERVED: Project: All Format: MBZ
11:10	11b WO	FUNCTION_GROUP_DEVICE_POWER_STATE: Project: All Default Value: ;11b D3 Power state that was set Value Name Description Project 00b D0 D0 All 01b, 10b Unsupported Unsupported All 11b D3 D3 (Default)
9:4	0b WO	RESERVED_1: Project: All Format: MBZ
3:2	11b WO	CONVERTORA_WIDGET_POWER_STATE: Project: All Default Value: ;11b D3 Power state that was requested by audio software Value Name Description Project 00b D0 D0 All 01b, 10b Unsupported Unsupported All 11b D3 D3 (Default)
1:0	11b WO	PINB_WIDGET_POWER_STATE: Project: All Default Value: ;11b D3 Power state that was set Value Name Description Project 00b D0 D0 All 01b, 10b Unsupported Unsupported All 11b D3 D3 (Default)

14.11.92 AUD OUT STR DESC A DBG—Offset 62F08h



Bit Range	Default & Access	Field Name (ID): Description
13:11	0b WO	SAMPLE_BASE_RATE_MULT: Project: All Default Value: 000b (48 KHz) Audio stream sample base rate multiple Value Name Description Project 000b 1x 48 kHz/44.1 kHz or less All 001b 2x x2 (96 kHz, 88.2 kHz, 32 kHz) All 010b 3x x3 (144 kHz) All 011b 4x x4 (192 kHz, 176.4 kHz) All 1XXb Reserved Reserved
10:8	0b WO	SAMPLE_BASE_RATE_DIVISOR: Project: All Default Value: 000b (indicates divide by 1 which results in 48 KHz) Audio stream sample base rate divisor Value Name Description Project 000b Divide by 1 Divide by 1 (48 kHz, 44.1 kHz) All 001b Divide by 2 Divide by 2 (24 kHz, 22.05 kHz) All 010b Divide by 3 Divide by 3 (16 kHz, 32 kHz) All 011b Divide by 4 Divide by 4 (11.025 kHz) All 100b Divide by 5 Divide by 5 (9.6 kHz) All 101b Divide by 6 Divide by 6 (8 kHz) All 110b Divide by 7 Divide by 7 All 111b Divide by Divide by 8 (6 kHz) All
7	0b WO	RESERVED_3: Project: All Format: MBZ
6:4	011b WO	BITS_PER_SAMPLE: Project: All Default Value: 011b (Indicates 24 bits) Audio stream sample base rate multiple Value Name Description Project 000b 8 bits The data will be packed in memory in 8 bit containers on 16 bit boundaries All 001b 16 bits The data will be packed in memory in 16 bit containers on 16 bit boundaries All 010b 24 bits The data will be packed in memory in 32 bit containers on 32 bit boundaries All 011b 32 bits The data will be packed in memory in 32 bit containers on 32 bit boundaries All 100b 20 bits The data will be packed in memory in 32 bit containers on 32 bit boundaries All Others Reserved Reserved
3:0	0010b WO	NUMBER_OF_CHANNELS_IN_A_STREAM: Project: All Format: U4+1 Default Value: 0010b (3 channels in each frame) Number of channels in each frame of the stream

14.11.93 AUD_OUT_DIG_CNVT_A_DBG—Offset 62F0Ch

These values are returned from the device as the Digital Converter response to a Get Audio Output Converter Widget command.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F0Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000001h



31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0				1																															
RESERVED								STREAM_ID								LOWEST_CHANNEL_NUMBER				RESERVED_1								CATEGORY_CODE								LEVEL				PRO				NON_AUDIO				COPY				PRE				VCFG				V				DIGEN			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b WO	RESERVED: Project: All Format: MBZ
23:20	0b WO	STREAM_ID: Project: All Represents the link stream used by the converter for data input or output. This value is set in the Channel ID and Stream ID through the Set Audio Output Converter Widget command. Default = 0 (stream 0)
19:16	0b WO	LOWEST_CHANNEL_NUMBER: Project: All Represents the lowest channel used by the converter. This value is set in the Channel ID and Stream ID through the Set Audio Output Converter Widget command. Default = 0
15	0b WO	RESERVED_1: Project: All Format: MBZ
14:8	0b WO	CATEGORY_CODE: Project: All S/PDIF IEC Category Code. This value is set in the Digital Converter 1 through the Set Audio Output Converter Widget command. Default = 0
7	0b WO	LEVEL: Project: All S/PDIF IEC Generation Level. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Default = 0
6	0b WO	PRO: Project: All This bit indicates professional or consumer use of channel. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. This value can only be set to 1 if the Pro Allowed bit is set in the audio configuration register. Value Name Description Project 0b Consumer Consumer use. Default (Consumer) All 1b Professional Professional use All
5	0b WO	NON_AUDIO: Project: All Data is non PCM format. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b PCM Data is PCM (Default) All 1b Non-PCM Data is non PCM format All
4	0b WO	COPY: Project: All Copyright asserted. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b Not Asserted Copyright is not asserted All 1b Asserted Copyright is asserted All
3	0b WO	PRE: Project: All Filter preemphasis. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b None Pre-emphasis is non All 1b Enabled Filter pre-emphasis is enabled All



Bit Range	Default & Access	Field Name (ID): Description
26:22	0b WO	RESERVED_1: Project: All Format: MBZ
21:16	0b WO	CONVERTOR_CHANNEL_COUNT: Project: All This reflects the Convertor Channel Count programmed through HDAudio.
15	0b WO	RESERVED_2: Project: All Format: MBZ
14	0b WO	SAMPLE_BASE_RATE: Project: All Default Value: 0b (48 KHz) Sampling base rate of audio stream Value Name Description Project 0b 48 kHz 48 kHz All 1b 44.1 kHz 44.1 kHz All
13:11	0b WO	SAMPLE_BASE_RATE_MULT: Project: All Default Value: 000b (48 KHz) Audio stream sample base rate multiple Value Name Description Project 000b 1x 48 kHz/44.1 kHz or less All 001b 2x x2 (96 kHz, 88.2 kHz, 32 kHz) All 010b 3x x3 (144 kHz) All 011b 4x x4 (192 kHz, 176.4 kHz) All 1XXb Reserved Reserved
10:8	0b WO	SAMPLE_BASE_RATE_DIVISOR: Project: All Default Value: 000b (indicates divide by 1 which results in 48 KHz) Audio stream sample base rate divisor Value Name Description Project 000b Divide by 1 Divide by 1 (48 kHz, 44.1 kHz) All 001b Divide by 2 Divide by 2 (24 kHz, 22.05 kHz) All 010b Divide by 3 Divide by 3 (16 kHz, 32 kHz) All 011b Divide by 4 Divide by 4 (11.025 kHz) All 100b Divide by 5 Divide by 5 (9.6 kHz) All 101b Divide by 6 Divide by 6 (8 kHz) All 110b Divide by 7 Divide by 7 All 111b Divide by Divide by 8 (6 kHz) All
7	0b WO	RESERVED_3: Project: All Format: MBZ
6:4	011b WO	BITS_PER_SAMPLE: Project: All Default Value: 011b (Indicates 24 bits) Audio stream sample base rate multiple Value Name Description Project 000b 8 bits The data will be packed in memory in 8 bit containers on 16 bit boundaries All 001b 16 bits The data will be packed in memory in 16 bit containers on 16 bit boundaries All 010b 24 bits The data will be packed in memory in 32 bit containers on 32 bit boundaries All 011b 32 bits The data will be packed in memory in 32 bit containers on 32 bit boundaries All 100b 20 bits The data will be packed in memory in 32 bit containers on 32 bit boundaries All Others Reserved Reserved
3:0	0010b WO	NUMBER_OF_CHANNELS_IN_A_STREAM: Project: All Format: U4+1 Default Value: 0010b (3 channels in each frame) Number of channels in each frame of the stream

14.11.96 AUD_OUT_DIG_CNVT_B_DBG—Offset 62F1Ch

HDAudio Verb: Converter Widget 70D/70E/73E/73F/706 These values are returned from the device as the Digital Converter response to a Get Audio Output Converter Widget command.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F1Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RESERVED				STREAM_ID	LOWEST_CHANNEL_NUMBER	RESERVED_1	CATEGORY_CODE	LEVEL PRO NON_AUDIO COPY PRE VCFG V DIGEN

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b WO	RESERVED: Project: All Format: MBZ
23:20	0b WO	STREAM_ID: Project: All Represents the link stream used by the converter for data input or output. This value is set in the Channel ID and Stream ID through the Set Audio Output Converter Widget command. Default = 0 (stream 0)
19:16	0b WO	LOWEST_CHANNEL_NUMBER: Project: All Represents the lowest channel used by the converter. This value is set in the Channel ID and Stream ID through the Set Audio Output Converter Widget command. Default = 0
15	0b WO	RESERVED_1: Project: All Format: MBZ
14:8	0b WO	CATEGORY_CODE: Project: All S/PDIF IEC Category Code. This value is set in the Digital Converter 1 through the Set Audio Output Converter Widget command. Default = 0
7	0b WO	LEVEL: Project: All S/PDIF IEC Generation Level. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Default = 0
6	0b WO	PRO: Project: All This bit indicates professional or consumer use of channel. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. This value can only be set to 1 if the Pro Allowed bit is set in the audio configuration register. Value Name Description Project 0b Consumer Consumer use. Default (Consumer) All 1b Professional Professional use All
5	0b WO	NON_AUDIO: Project: All Data is non PCM format. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b PCM Data is PCM (Default) All 1b Non-PCM Data is non PCM format All



Bit Range	Default & Access	Field Name (ID): Description
4	0b WO	COPY: Project: All Copyright asserted. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b Not Asserted Copyright is not asserted All 1b Asserted Copyright is asserted All
3	0b WO	PRE: Project: All Filter preemphasis. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b None Pre-emphasis is non All 1b Enabled Filter pre-emphasis is enabled All
2	0b WO	VCFG: Project: All Validity Configuration. Determines S/PDIF transmitter behavior when data is not being transmitted. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Default = 0
1	0b WO	V: Project: All Affects the validity flag transmitted in each subframe, and enables the S/PDIF transmitter to maintain connection during error or mute conditions. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Default = 0
0	1b WO	DIGEN: All Filter preemphasis. This value is set in the Digital Converter 2 through the Set Audio Output Converter Widget command. Value Name Description Project 0b Blocked Digital data is blocked from passing through the node, regardless of the state All 1b Passed Digital data can pass through the node (Default = 1, enabled) All

14.11.97 AUD_PORT_EN_B_DBG—Offset 62F20h

HDAudio Verb: PinWidget 707/3/734/701 These values are returned from the device as the Digital Converter response to a Get Audio Output Converter Widget command.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F20h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000003h

14.11.98 AUD PWST3 DBG—Offset 62F24h

HDAudio Verb: Pin Widget 705

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 62F24h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000003h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								PIND_WIDGET_POWER_STATE

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b WO	RESERVED: Project: All Format: MBZ
1:0	11b WO	PIND_WIDGET_POWER_STATE: Project: All Default Value: ;11b D3 Power state that was set Value Name Description Project 00b D0 D0 All 01b, 10b Unsupported Unsupported All 11b D3 D3 (Default)

14.11.99 AUD_PORT_EN_C_DBG—Offset 62F28h

HDAudio Verb: PinWidget 707/3/734/701 These values are returned from the device as the Digital Converter response to a Get Audio Output Converter Widget command.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F28h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000003h

14.11.100 AUD_PORT_EN_D DBG—Offset 62F2Ch



Bit Range	Default & Access	Field Name (ID): Description
1	1b WO	PORT_D_AMP_MUTE_STATUS: Access Read Only Project: All Project: All Default Value: ;1b Amp muted This read-only bit reflects the mute status of the amplifier Value Name Description Project 0b Amp not muted Amp not muted All 1b Amp muted Amp muted All
0	1b WO	PORT_D_OUT_ENABLE: All This bit reflects the state of the output path of the Pin Widget. When 0, audio is disabled . Default = 1

14.11.101 AUD_CHICKENBIT_REG—Offset 62F38h

audio chickenbit register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F38h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RESERVED								PLACE HOLDER FOR ECC_CHICKEN_BIT_PIPE_A ENABLE_MMIO_HDMI_AUDIO_VERB_PROGRAMMING

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b WO	RESERVED: Project: All Format: MBZ
1	0b WO	PLACE HOLDER FOR ECC_CHICKEN_BIT_PIPE_A: Project: All audr_ecc_flip_chicken_bit



Bit Range	Default & Access	Field Name (ID): Description
0	1b WO	ENABLE_MMIO_HDMI_AUDIO_VERB_PROGRAMMING: All Project: All Default Value: ;1b Amp muted This read-only bit reflects the mute status of the amplifier Value Name Description Project 0b HDAudio Programming through HDAudio Azalia All 1b MMIO Programming through MMIO Debug registers All

14.11.102 AUD_OUT_DIG_CNVT_DBG—Offset 62F40h

HDAudio Verb: Converter Widget 70E/73E These values are returned from the device as the Digital Converter response to a Get Audio Output Converter Widget command.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 62F40h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED						IEC_CODING_TYPE		RSVD_FOR_DIGITAL_CONVERTER_2A

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b WO	RESERVED: Project: All Format: MBZ
11:8	0b WO	IEC_CODING_TYPE: Project: All
7:0	0b WO	RSVD_FOR_DIGITAL__CONVERTER_2A: Project: All



14.11.103 AUD_OUT_DIG_CNVTB_DBG—Offset 62F44h

HDAudio Verb: Converter Widget 70E/73E These values are returned from the device as the Digital Converter response to a Get Audio Output Converter Widget command.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F44h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED						IEC_CODING_TYPE		RSVD_FOR_DIGITAL_CONVERTER_2B

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b WO	RESERVED: Project: All Format: MBZ
11:8	0b WO	IEC_CODING_TYPE: Project: All
7:0	0b WO	RSVD_FOR_DIGITAL_CONVERTER_2B: Project: All

14.11.104 AUD_CNTL_ST_B_DBG—Offset 62F60h

HDAudio Verb: Pin Widget 730/732

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F60h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED						INFOFRAME_CONTROL_FOR_CURRENTLY_INDEXED_FRAME	INFOFRAME_PACKET_INDEX	BYTE_OFFSET_INDEX_POINTER_LOCATION_5_BITS

Bit Range	Default & Access	Field Name (ID): Description
31:10	0b WO	RESERVED: Project: All Format: MBZ
9:8	0b WO	INFOFRAME_CONTROL_FOR_CURRENTLY_INDEXED_FRAME: Project: All Default Value: 00b disable xmit Value Name Description Project 00b Disable xmit Disable xmit All 01b Reserved Reserved All 10b Xmit once Xmit once All 11b Best Effort Best Effort All
7:5	0b WO	INFOFRAME_PACKET_INDEX: Project: All Default Value: 00b Audio Value Name Description Project 000b Audio Audio All 001b GP GP All 010b GP2 GP2 All 011b GP3 GP3 All 100b GP4 GP4 All Others Reserved Reserved All
4:0	0b WO	BYTE_OFFSET_INDEX_POINTER_LOCATION_5_BITS: Project: All

14.11.105 AUD_HDMIW_INFOFR_B_DBG—Offset 62F64h

HDAudio Verb: Pin Widget 731

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F64h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED							DATA_ISLAND_PACKET_DATA	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b WO	RESERVED: Project: All Format: MBZ
7:0	0b WO	DATA_ISLAND_PACKET_DATA: Project: All This reflects the contents of the DIP indexed by the DIP access address. The contents of this buffer are cleared during function reset or HD audio link reset.

14.11.106 AUD_CNTL_ST_C_DBG—Offset 62F70h

HDAudio Verb: Pin Widget 730/732

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F70h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:10	0b WO	RESERVED: Project: All Format: MBZ
9:8	0b WO	INFOFRAME_CONTROL_FOR_CURRENTLY_INDEXED_FRAME: Project: All Default Value: 00b disable xmit Value Name Description Project 00b Disable xmit Disable xmit All 01b Reserved Reserved All 10b Xmit once Xmit once All 11b Best Effort Best Effort All
7:5	0b WO	INFOFRAME_PACKET_INDEX: Project: All Default Value: 00b Audio Value Name Description Project 000b Audio Audio All 001b GP GP All 010b GP2 GP2 All 011b GP3 GP3 All 100b GP4 GP4 All Others Reserved Reserved All
4:0	0b WO	BYTE_OFFSET_INDEX_POINTER_LOCATION_5_BITS: Project: All

14.11.107 AUD_HDMIW_INFOFR_C_DBG—Offset 62F74h

HDAudio Verb: Pin Widget 731

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F74h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED						DATA_ISLAND_PACKET_DATA		

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b WO	RESERVED: Project: All Format: MBZ
7:0	0b WO	DATA_ISLAND_PACKET_DATA: Project: All This reflects the contents of the DIP indexed by the DIP access address. The contents of this buffer are cleared during function reset or HD audio link reset.

14.11.108 AUD_CNTL_ST_D_DBG—Offset 62F80h

HDAudio Verb: Pin Widget 730/732

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F80h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED						INFOFRAME_CONTROL_FOR_CURRENTLY_INDEXED_FRAME	INFOFRAME_PACKET_INDEX	BYTE_OFFSET_INDEX_POINTER_LOCATION_5_BITS

Bit Range	Default & Access	Field Name (ID): Description
31:10	0b WO	RESERVED: Project: All Format: MBZ
9:8	0b WO	INFOFRAME_CONTROL_FOR_CURRENTLY_INDEXED_FRAME: Project: All Default Value: 00b disable xmit Value Name Description Project 00b Disable xmit Disable xmit All 01b Reserved Reserved All 10b Xmit once Xmit once All 11b Best Effort Best Effort All
7:5	0b WO	INFOFRAME_PACKET_INDEX: Project: All Default Value: 00b Audio Value Name Description Project 000b Audio Audio All 001b GP GP All 010b GP2 GP2 All 011b GP3 GP3 All 100b GP4 GP4 All Others Reserved Reserved All
4:0	0b WO	BYTE_OFFSET_INDEX_POINTER_LOCATION_5_BITS: Project: All

14.11.109 AUD_HDMIW_INFOFR_D_DBG—Offset 62F84h

HDAudio Verb: Pin Widget 731

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F84h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED							DATA_ISLAND_PACKET_DATA	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b WO	RESERVED: Project: All Format: MBZ
7:0	0b WO	DATA_ISLAND_PACKET_DATA: Project: All This reflects the contents of the DIP indexed by the DIP access address. The contents of this buffer are cleared during function reset or HD audio link reset.

14.11.110 AUD_CONFIG_DEFAULT2_REG_PORTB—Offset 62F88h

HDAudio Verb: Pin Widget 738..73B

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F88h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

READ_BACK

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b WO	READ_BACK: Project: All Config Default 2 values of port B rgars being written using the 738/739/73A/73B



14.11.111 AUD_CONFIG_DEFAULT2_REG_PORTC—Offset 62F8Ch

HDAudio Verb: Pin Widget 738..73B

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F8Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
READ_BACK								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0b WO	READ_BACK: Project: All Config Default 2 values of port C rgars being written using the 738/739/73A/73B						

14.11.112 AUD_CONFIG_DEFAULT2_REG_PORTD—Offset 62F90h

HDAudio Verb: Pin Widget 738..73B

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F90h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
READ_BACK								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0b WO	READ_BACK: Project: All Config Default 2 values of port D rgars being written using the 738/739/73A/73B						

14.11.113 AUD MCTSA—Offset 62F94h

Audio M or CTS Pipe A Values Readback Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 62F94h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				BIT_23_0_OF_AUDIO_M_OR_CTS_VALUES_TO_PIPE_A				

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RO	RESERVED: Project: All Format: MBZ
23:0	0b RO	BIT_23_0_OF_AUDIO_M_OR_CTS__VALUES_TO_PIPE_A: Project: All

14.11.114 AUD_MCTSB—Offset 62F98h

Audio M or CTS Pipe B Values Readback Register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 62F98h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RO	RESERVED: Project: All Format: MBZ
23:0	0b RO	BIT_23_0_OF_AUDIO_M_OR_CTS__VALUES_TO_PIPE_B: Project: All


DisplayPort B Control Register [DevCTG, DevCDV] Display Port B control (dprrega_b0.vl_displayb1)

Type: Memory Mapped I/O Register
(Size: 32 bits)


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000018h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
21:19	0b RW	PORT_WIDTH_SELECTION: This bit selects the number of lanes to be enabled on the DisplayPort link. Port width selection takes place on the Vblank after being written. Port width change must be done as a part of mode set. 000 = x1 Mode (Default) 001 = x2 Mode. 010 = RESERVED 011 = x4 Mode. 1xx = RESERVED
18	0b RW	ENHANCED_FRAMING_ENABLE: This bit selects enhanced framing. It must be set when HDCP will be used invoked. 0 (Default) Enhanced framing disabled 1 Enhanced framing enabled. Locked once port is enabled. Updates when the port is disabled then re-enabled
17:16	0b RW	RESERVED_2: MBZ
15	0b RW	RESERVED_3: [DevCDV]: Port reversal [DevCTG]: Locked once port is enabled. Updates when the port is disabled then re-enabled
14:9	0b RW	RESERVED_4: MBZ
8	0b RW	ASR_ENABLE: [DevVLV2]: this bit enables the Alternate Scrambler Reset capability for eDP port to use alternate scrambler reset value of FFFEH 1 - ASR enable 0 ASR disable
7	0b RW	SCRAMBLING_DISABLE: [DevCTG, B-step only, DevCDV]: This bit disables scrambling for this port. 0 = Scrambling enabled (Default) 1 = Scrambling disabled, no SR after initialization at loop 2 of training
6	0b RW	AUDIO_OUTPUT_ENABLE: This bit enables audio on this output port. It may be enabled or disabled only when the link training is complete and set to Normal 0 = Audio output disabled 1 = Audio output enabled
5	0b RW	HDCP_PORT_SELECT: This bit directs HDCP to this port. When enabled, the information sent on this port will be encrypted using HDCP. Please note that this bit does not enable encryption on its own, but must be used in conjunction with HDCP registers. 0 = (Default) No HDCP encryption on this port 1 = Enable HDCP on this port
4:3	11b RW	SYNC_POLARITY: Indicates the polarity of Hsync and Vsync. Please note that in native VGA modes, these bits have no effect. In native VGA modes, sync polarity is determined by VRshr3c2d76b[7:6], the VGA polarity bits in VGA control. 00 = VS and HS are active low (inverted) 01 = VS is active low (inverted), HS is active high 10 = VS is active high, HS is active low (inverted) 11 = (Default) VS and HS are active high
2	0b RO	DIGITAL_DISPLAY_B_DETECTED: Read-only bit indicating whether a digital display was detected during initialization. It signifies the level of the GMBUS port 4 (port B) data line at boot. 0 = digital display not detected during initialization (Default) 1 = digital display detected during initialization AccessType: Read Only
1	0b RW	RESERVED_5: MBZ
0	0b RW	DISABLE_FRAMESTART_STALL: This bit, when set, will disable the framestart window to stall DP AV mixer from sending audio samples before framestart. This applies to BOTH pipes. 0 = Enable framestart window to stall audio samples. (default) 1 = Disable framestart window to stall audio samples.



Bit Range	Default & Access	Field Name (ID): Description
24:20	0b RW	MESSAGE_SIZE: This field is used to indicate the total number bytes to transmit (including the header). It also indicates the number of bytes received in a transaction (including the header). This field is valid only when the done bit is set and timeout or receive error has not occurred. Sync/Stop are not part of the message or the message size. Reads of this field will give the response message size. The read value will not be valid while Busy bit 31 is asserted. Message sizes of 0 or >20 are not allowed.
19:16	0101b RW	PRECHARGE_TIME: Used to determine the precharge time for the Aux Channel drivers. The value is the number of microseconds times 2. This depends on the 2X bit clock divider (bits 10:0) being programmed for 2MHz. Default is 5 decimal which gives 10us of precharge. Example: For 12us precharge, program 6 (12us/2us).
15	0b RW	AUX_AKSV_BUFFER_SELECT: This bit selects whether some of the data to be written over Display Port AUX comes from the Aksv buffer for HDCP authentication, or all from the AUX Data registers. Set this bit before initiating a transaction to write Aksv to the Display Port sink. All AUX protocol must be followed and Message Size set to 9 bytes. The first DWord transmitted will be from the AUX Data Register 1 for the header, then the DP_AUX_CH_AKSV_HI, then the last byte from DP_AUX_CH_AKSV_LO. The sink response is read back as usual from the AUX Data registers. More than one AUX channel can select to use the Aksv buffer simultaneously. 0 (Default) Use AUX Data registers for regular data transmission 1 Use Aksv Buffer for part of the data transmission.
14	0b RW	INVERT_MANCHESTER_TEST_MODE: 1 = Manchester code rising edge mid-clk signifies one (test mode) 0 = Manchester code rising edge mid-clk signifies zero (default)
13	0b RW	SYNC_ONLY_CLOCK_RECOVERY_TEST_MODE: 1 = Only recover clock during sync pattern (test mode) 0 = Recover clock during sync pattern and data phase (default)
12	0b RW	DISABLE_DE_GLITCH_TEST_MODE: 1 = Disable serial input de-glitch logic (test mode) 0 = Enable serial input de-glitch logic (default)
11	0b RW	DOUBLE_PRECHARGE_TEST_MODE: 1 = Precharge time is doubled 0 = Precharge time is as programmed
10:0	0b RW	_2X_BIT_CLOCK_DIVIDER: Used to determine the 2X bit clock the Aux Channel logic runs on. This value divides the input clock frequency down to 2X bit clock rate. The 2X bit clock rate is ideally 2MHz (0.5us). [DevCTG-A] the input clock is cddclk. [DevCTG-B, DevCDV] the input clock is hrawclk (200MHz) Example: For 300MHz input clock and desired 2MHz 2X bit clock, program 150 (300MHz/2MHz).

14.11.117 DPB_AUX_CH_DATA1—Offset 64114h

Display Port B AUX Data Register 1 [DevCTG, DevCDV]

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 64114h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.11.119 DPB_AUX_CH_DATA3—Offset 6411Ch

Display Port B AUX Data Register 3 [DevCTG, DevCDV] AuxB Data3 (dprrega_b0.v auxb_dpr_data3, ql_auxb_d3)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6411Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	AUX_CH_DATA3_31: 0): The third Dword of the message. The Msbyte is transmitted first. Only used if the message size is greater than 8. Reads will give the response data after transaction complete.

14.11.120 DPB_AUX_CH_DATA4—Offset 64120h

Display Port B AUX Data Register 4 [DevCTG, DevCDV] AuxB Data4 (dprrega_b0.v auxb_dpr_data4, ql_auxb_d4)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 64120h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
AKSV_BITS_7	AKSV_BITS_15	AKSV_BITS_23	AKSV_BITS_31					

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b WO	AKSV_BITS_7: 0]
23:16	0b WO	AKSV_BITS_15: 8]
15:8	0b WO	AKSV_BITS_23: 16]
7:0	0b WO	AKSV_BITS_31: 24]

14.11.123 DP_AUX_CH_AKSV_LO—Offset 64134h

Display Port AUX Aksv Buffer Low [DevCTG-B, DevCDV] AuxB AKSV High (dprrega_b0.v dpr_aux_aksv_lo)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 64134h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED	AKSV_BITS_39							

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b WO	RESERVED: MBZ
7:0	0b WO	AKSV_BITS_39: 32]



14.11.124 DPB_AUX_TST—Offset 64150h

Display Port B AUX Test Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 64150h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DPB_AUX_BUFFER_LOOPBACK_TEST_ENABLE	DPB_AUX_BUFFER_LOOPBACK_TEST_DONE	DPB_AUX_BUFFER_LOOPBACK_TEST_RESULT	DPB_AUX_FULL_TEST_ENABLE	RESERVED				DPB_AUX_SHORT_SYNC
								DPB_AUX_CONSTANT_05_TEST_PATTERN
								DPB_AUX_TIGHTEN_FREQUENCY_WINDOW
								DPB_AUX_LESS_GOOD_SYNC_05_REQUIRED
								DEGLITCH_AMOUNT
								RESERVED_1
								DPB_AUX_MULTIPLE_RECEIVED_EDGES_ERROR_ENABLE
								DPB_AUX_DEBUG_STATUS_READBACK
								RESERVED_2

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	DPB_AUX_BUFFER_LOOPBACK_TEST_ENABLE: Project: All Default Value: 0b Enables test for the DPB-AUX I/O buffer. A 16 cycle clock pattern is output to the I/O buffer and compared against the looped back buffer output. The input clock is cdclk. With input clock at 512MHz the pattern will be a 1 MHz clock. It scales down with lower clock frequencies. The result is found in DP-AUX Buffer Loopback Test Result after DP-AUX Buffer Loopback Test Done is set. Clear this bit to 0 after test is done to return DP-AUX to normal operation. Loopback Test can be run simultaneously on all AUX buffers. Do not enable DP-AUX Buffer Loopback Test and DP-AUX Full Test simultaneously. Value Name Description Project 0b Disable Test disabled All 1b Enable Enable test. All
30	0b RO	DPB_AUX_BUFFER_LOOPBACK_TEST_DONE: Project: All Default Value: 0b AccessType: Read Only DPB-AUX Buffer Loopback Test has been run and completed. This is not the done for the DP-AUX Full Test. Value Name Description Project 0b Not Done Test not done. DP-AUX Buffer Loopback Test Result is not valid All 1b Done Test done. DP-AUX Buffer Loopback Test Result is now valid All



Bit Range	Default & Access	Field Name (ID): Description
29	0b RO	DPB_AUX_BUFFER_LOOPBACK_TEST_RESULT: Project: All Default Value: 0b AccessType: Read Only Result of the DPB-AUX Buffer Loopback Test. Value is only valid after a DP-AUX Loopback Test Done is 1. This is not the result of the DP-AUX Full Test. Value Name Description Project 0b Pass Pass All 1b Fail All
28	0b RW	DPB_AUX_FULL_TEST_ENABLE: Project: All Default Value: 0b Enables test for the DPB-AUX core logic transmit and receive functions through the DPB-AUX and DPC-AUX buffers. DPB-AUX and DPC-AUX are interconnected through I/O buffer loopbacks. DPB-AUX is programmed as source to output a 20 byte test pattern. DPC-AUX is programmed as sink to receive the test pattern and reply with a different 20 byte test pattern. Test pattern 1 = 0xA55CC33E E770080C 0E0F0F8F CFEFF81C 3E77E3C8 Test pattern 2 = 0X183C7EE7 C381FF7F 3F1F0F07 030100EE 77CC33A5 Programming sequence: 1. Set DPB-AUX Full Test Enable to 1. 2. Program DPB_AUX_CH_DATA[1-5] with test pattern 1 to transmit as the source. 3. Program DPC_AUX_CH_DATA[1-5] with test pattern 2 to reply with as the sink. 4. Program all DPC_AUX_CH_CTL fields and set Send to 1. 5. Program all DPB_AUX_CH_CTL fields and set Send to 1. Then the test will start. Results checking sequence: 1. Poll DPB_AUX_CH_CTL for Done. To pass, Done must be set within 500us. 2. Read DPB_AUX_CH_CTL register. To pass, Timeout Error and Receive Error must be 0. 3. Read DPC_AUX_CH_CTL register. To pass, Receive Error must be 0. 4. Read DPB_AUX_CH_DATA[1-5] registers. To pass, they must contain test pattern 2. 5. Read DPC_AUX_CH_DATA[1-5] registers. To pass, they must contain test pattern 1. Clear this bit to 0 after test is done to return DP-AUX to normal operation. Test must be repeated with and without lane reversal to verify DPB-AUX buffer combinations. Only enable one DP-AUX Full Test at a time. To abort a test in progress, write the AUX_CH_CTL Send bits to 0 and Full Test Enable to 0. Value Name Description Project 0b Disable Test disabled All 1b Enable Enable test All
27:16	0b RW	RESERVED: Project: All Format:
15	0b RW	DPB_AUX_SHORT_SYNC: Project: All Output just 16 manchester 0s for sync (otherwise 26)
14	0b RW	DPB_AUX_CONSTANT_0S_TEST_PATTERN: Project: All Output neverending Manchester encoded 0s for electrical testing
13	0b RW	DPB_AUX_TIGHTEN_FREQUENCY_WINDOW: Project: All Tighten the window of allowable receive frequencies
12	0b RW	DPB_AUX_LESS_GOOD_SYNC_0S_REQUIRED: Project: All Check for only 8 good sync 0s instead of 12 when receiving
11:10	0b RW	DEGLITCH_AMOUNT: Project: All Default Value: 0b Select clock count for deglitch Value Name Description Project 00b 50 ns 25 clocks - GMBUS type - 50ns at 500MHz cclk All 01b 125 ns 1/4 2X bit clock divider value - 125ns All 10b 62.5 ns 1/8 2X bit clock divider value - 62.5ns All 11b 31.125 ns 1/16 2X bit clock divider value - 31.125ns All
9	0b RW	RESERVED_1: Project: All Format:
8	0b RW	DPB_AUX_MULTIPLE_RECEIVED_EDGES_ERROR_ENABLE: Project: All Default Value: 0b Value Name Description Project 0b Okay Multiple edges in window is okay All 1b Error Multiple edges in window is an error All



Access Method


Offset: [GTTMMADR LSB + 180000h] + 64200h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000018h

31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0																																			
DISPLAYPORT_C_ENABLE				PIPE_SELECT				LINK_TRAINING_PATTERN_ENABLE				RESERVED				RESERVED_1				PORT_WIDTH_SELECTION				ENHANCED_FRAMING_ENABLE				RESERVED_2				RESERVED_3				RESERVED_4				ASR_ENABLE				SCRAMBLING_DISABLE				AUDIO_OUTPUT_ENABLE				HDCP_PORT_SELECT				SYNC_POLARITY				DIGITAL_DISPLAY_C_DETECTED				RESERVED_5			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	DISPLAYPORT_C_ENABLE: Disabling this port will put it in its lowest power state. Port enable takes place on the Vblank after being written. Both this bit and bit 6 of this register must be enabled to send audio over this port. 1 = Enable. This bit enables the Display Port C interface. 0 = Disable and tristates the Display Port C interface.
30	0b RW	PIPE_SELECT: This bit determines from which display pipe the source data will originate. Pipe selection takes place on the Vblank after being written 0 = Pipe A 1 = Pipe B



Bit Range	Default & Access	Field Name (ID): Description
29:28	0b RW	LINK_TRAINING_PATTERN_ENABLE: These bits are used for link initialization as defined in the DisplayPort specification. Please note that the link must first be configured prior to sending training patterns. 00 Pattern 1 enabled: Repetition of D10.2 characters Default. 01 Pattern 2 enabled: Repetition of K28.5, D11.6, K28.5, D11.6, D10.2, D10.2, D10.2, D10.2, D10.2, D10.2. Please note that the entire pattern must complete before another pattern is sent. Scrambling initialization and disparity init commence at the end of the last iteration of pattern 2. 10 Idle Pattern enabled: Transmit BS followed by VB-ID with NoVideoStream_flag set to 1, five times 11 Link not in training: Send normal pixels
27:25	0b RW	RESERVED: [DevCDV]: Voltage swing level set [DevCTG]: These bits are used for setting the voltage swing for pattern 1, defined as Vdiff_pp in the DisplayPort specification. They mirror registers in the PCI express configuration. 000 0.4V (DEFAULT) 001 0.6V 010 0.8V 011 1.2V RESERVED 1xx RESERVED
24:22	0b RW	RESERVED_1: [DevCDV]: Pre-emphasis level set [DevCTG]: These bits are used for setting link pre-emphasis for pattern 2, as defined in the DisplayPort specification. They mirror registers in the PCI express configuration. 000 no pre-emphasis (default) 001 3.5dB pre-emphasis (1.5x) 010 6dB pre-emphasis (2x) 011 9.5dB pre-emphasis (3x) RESERVED 1xx RESERVED
21:19	0b RW	PORT_WIDTH_SELECTION: This bit selects the number of lanes to be enabled on the DisplayPort link. Port width selection takes place on the Vblank after being written. Port width change must be done as a part of mode set. 000 = x1 Mode (Default) 001 = x2 Mode. 010 = RESERVED 011 = x4 Mode. 1xx = RESERVED
18	0b RW	ENHANCED_FRAMING_ENABLE: This bit selects enhanced framing. It must be set when HDCP will be used invoked. 0 (Default) Enhanced framing disabled 1 Enhanced framing enabled. Locked once port is enabled. Updates when the port is disabled then re-enabled
17:16	0b RW	RESERVED_2: MBZ
15	0b RW	RESERVED_3: [DevCDV]: Port reversal [DevCTG]: Locked once port is enabled. Updates when the port is disabled then re-enabled
14:9	0b RW	RESERVED_4: MBZ
8	0b RW	ASR_ENABLE: [DevVLV2]: this bit enables the Alternate Scrambler Reset capability for eDP port to use alternate scrambler reset value of FFFeh 1 - ASR enable 0 ASR disable
7	0b RW	SCRAMBLING_DISABLE: [DevCTG, B-step only, DevCDV]: This bit disables scrambling for this port. 0 = Scrambling enabled (Default) 1 = Scrambling disabled, no SR after initialization at loop 2 of training
6	0b RW	AUDIO_OUTPUT_ENABLE: This bit enables audio on this output port. It may be enabled or disabled only when the link training is complete and set to Normal 0 = Audio output disabled 1 = Audio output enabled



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	HDCP_PORT_SELECT: This bit directs HDCP to this port. When enabled, the information sent on this port will be encrypted using HDCP. Please note that this bit does not enable encryption on its own, but must be used in conjunction with HDCP registers. 0 = (Default) No HDCP encryption on this port 1 = Enable HDCP on this port
4:3	11b RW	SYNC_POLARITY: Indicates the polarity of Hsync and Vsync. Please note that in native VGA modes, these bits have no effect. In native VGA modes, sync polarity is determined by VRshr3c2d76b[7:6], the VGA polarity bits in VGA control. 00 = VS and HS are active low (inverted) 01 = VS is active low (inverted), HS is active high 10 = VS is active high, HS is active low (inverted) 11 = (Default) VS and HS are active high
2	0b RO	DIGITAL_DISPLAY_C_DETECTED: Read-only bit indicating whether a digital display was detected during initialization. It signifies the level of the GMBUS port (sDVO B/C) data line at boot. 0 = digital display not detected during initialization (Default) 1 = digital display detected during initialization AccessType: Read only
1:0	0b RW	RESERVED_5: MBZ

14.11.126 DPC_AUX_CH_CTL—Offset 64210h

Display Port C AUX Channel Control [DevCTG] AuxC Data1 (dprrega_b0.v
auxc_dpr_data1, ql_auxc_d1)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [GTTMMADR_LSB + 180000h] + 64210h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00050000h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	SEND_BUSY: Setting this bit to a one initiates the transaction, when read this bit will be a 1 until the transmission completes. The transaction is completed when the response is received or when a timeout occurs. Do not write a 1 again until transaction completes. Writes of 0 will be ignored.
30	0b RW/1C	DONE: A sticky bit that indicates the transaction has completed. SW must write a 1 to this bit to clear the event. AccessType: One to Clear
29	0b RW	INTERRUPT_ON_DONE: Enable an interrupt in the hotplug status register when the transaction completes or times out.
28	0b RW/1C	TIME_OUT_ERROR: A sticky bit that indicates the transaction has timed out. SW must write a 1 to this bit to clear the event. AccessType: One to Clear
27:26	0b RW	TIME_OUT_TIMER_VALUE: 00: 400us (default) 01: 600us 10: 800us 11: 1600us The time count depends on the 2X bit clock divider (bits 10:0) being programmed for 2MHz.
25	0b RW/1C	RECEIVE_ERROR: A sticky bit that indicates that the data received was corrupted, not in multiples of a full byte, or more than 20 bytes. SW must write a 1 to this bit to clear the event. AccessType: One to Clear
24:20	0b RW	MESSAGE_SIZE: This field is used to indicate the total number bytes to transmit (including the header). It also indicates the number of bytes received in a transaction (including the header). This field is valid only only when the done bit is set and timeout or receive error has not occurred. Sync/Stop are not part of the message or the message size. Reads of this field will give the response message size. The read value will not be valid while Busy bit 31 is asserted. Message sizes of 0 or >20 are not allowed.
19:16	0101b RW	PRECHARGE_TIME: Used to determine the precharge time for the Aux Channel drivers. The value is the number of microseconds times 2. This depends on the 2X bit clock divider (bits 10:0) being programmed for 2MHz. Default is 5 decimal which gives 10us of precharge. Example: For 12us precharge, program 6 (12us/2us).
15	0b RW	AUX_AKSV_BUFFER_SELECT: This bit selects whether some of the data to be written over Display Port AUX comes from the Aksv buffer for HDCP authentication, or all from the AUX Data registers. Set this bit before initiating a transaction to write Aksv to the Display Port sink. All AUX protocol must be followed and Message Size set to 9 bytes. The first DWord transmitted will be from the AUX Data Register 1 for the header, then the DP_AUX_CH_AKSV_HI, then the last byte from DP_AUX_CH_AKSV_LO. The sink response is read back as usual from the AUX Data registers. More than one AUX channel can select to use the Aksv buffer simultaneously. 0 (Default) Use AUX Data registers for regular data transmission 1 Use Aksv Buffer for part of the data transmission.
14	0b RW	INVERT_MANCHESTER_TEST_MODE: 1 = Manchester code rising edge mid-clk signifies one (test mode) 0 = Manchester code rising edge mid-clk signifies zero (default)
13	0b RW	SYNC_ONLY_CLOCK_RECOVERY_TEST_MODE: 1 = Only recover clock during sync pattern (test mode) 0 = Recover clock during sync pattern and data phase (default)
12	0b RW	DISABLE_DE_GLITCH_TEST_MODE: 1 = Disable serial input de-glitch logic (test mode) 0 = Enable serial input de-glitch logic (default)
11	0b RW	DOUBLE_PRECHARGE_TEST_MODE: 1 = Precharge time is doubled 0 = Precharge time is as programmed



Bit Range	Default & Access	Field Name (ID): Description
10:0	0b RW	_2X_BIT_CLOCK_DIVIDER: Used to determine the 2X bit clock the Aux Channel logic runs on. This value divides the input clock frequency down to 2X bit clock rate. The 2X bit clock rate is ideally 2MHz (0.5us). [DevCTG-A] the input clock is cdcclk. [DevCTG-B] the input clock is hrawclk. Example: For 300MHz input clock and desired 2MHz 2X bit clock, program 150 (300MHz/2MHz).

14.11.127 DPC_AUX_CH_DATA1—Offset 64214h

Display Port C AUX Data Register 1 [DevCTG, DevCDV] AuxC Data1 (dprrega_b0.v auxc_dpr_data1, ql_auxc_d1)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 64214h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

AUX_CH_DATA1_31

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	AUX_CH_DATA1_31: 0]: The first DWord of the message. The MSbyte is transmitted first. Reads will give the response data after transaction complete.

14.11.128 DPC_AUX_CH_DATA2—Offset 64218h

Display Port C AUX Data Register 2 [DevCTG, DevCDV] AuxC Data2 (dprrega_b0.v auxc_dpr_data2, ql_auxc_d2)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 64218h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.11.130 DPC_AUX_CH_DATA4—Offset 64220h

Display Port C AUX Data Register 4 [DevCTG, DevCDV] AuxC Data4 (dprrega_b0.v auxc_dpr_data4, ql_auxc_d4)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 64220h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

AUX_CH_DATA4_31

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	AUX_CH_DATA4_31: 0]: The fourth DWord of the message. The MSbyte is transmitted first. Only used if the message size is greater than 12. Reads will give the response data after transaction complete.

14.11.131 DPC_AUX_CH_DATA5—Offset 64224h

Display Port C AUX Data Register 5 [DevCTG, DevCDV] AuxC Data5 (dprrega_b0.v auxc_dpr_data5, ql_auxc_d5)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 64224h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

AUX_CH_DATA5_31



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	AUX_CH_DATA5_31: 0]: The fifth DWord of the message. The MSbyte is transmitted first. Only used if the message size is greater than 16. Reads will give the response data after transaction complete.

14.11.132 DPC_AUX_TST—Offset 64228h

Display Port C AUX Test Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 64228h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DPC_AUX_BUFFER_LOOPBACK_TEST_ENABLE	DPC_AUX_BUFFER_LOOPBACK_TEST_DONE	DPC_AUX_BUFFER_LOOPBACK_TEST_RESULT	DPC_AUX_FULL_TEST_ENABLE	RESERVED	DPC_AUX_SHORT_SYNC	DPC_AUX_CONSTANT_OS_TEST_PATTERN	DPC_AUX_TIGHTEN_FREQUENCY_WINDOW	DPC_AUX_LESS_GOOD_SYNC_OS_REQUIRED
					DPC_AUX DEGLITCH_AMOUNT	RESERVED_1	DPC_AUX_MULTIPLE_RECEIVED_EDGES_ERROR_ENABLE	DPC_AUX_DEBUG_STATUS_READBACK
								RESERVED_2

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	DPC_AUX_BUFFER_LOOPBACK_TEST_ENABLE: Project: All Default Value: 0b See DPB description. Value Name Description Project 0b Disable Test disabled All 1b Enable Enable test. All
30	0b RO	DPC_AUX_BUFFER_LOOPBACK_TEST_DONE: Project: All Default Value: 0b AccessType: Read Only See DPB description. Value Name Description Project 0b Not Done Test not done. DP-AUX Buffer Loopback Test Result is not valid All 1b Done Test done. DP-AUX Buffer Loopback Test Result is now valid All



Bit Range	Default & Access	Field Name (ID): Description
29	0b RO	DPC_AUX_BUFFER_LOOPBACK_TEST_RESULT: Project: All Default Value: 0b AccessType: Read Only See description for DPB-AUX Buffer Loopback Test Result Value Name Description Project 0b Pass Pass All 1b Fail Fail All
28	0b RW	DPC_AUX_FULL_TEST_ENABLE: Project: All Default Value: 0b See DPB description. Value Name Description Project 0b Disable Test disabled All 1b Enable Enable test All
27:16	0b RW	RESERVED: Project: All Format:
15	0b RW	DPC_AUX_SHORT_SYNC: Project: All See DPB description.
14	0b RW	DPC_AUX_CONSTANT_0S_TEST_PATTERN: Project: All See DPB description.
13	0b RW	DPC_AUX_TIGHTEN_FREQUENCY_WINDOW: Project: All See DPB description.
12	0b RW	DPC_AUX_LESS_GOOD_SYNC_0S_REQUIRED: Project: All See DPB description.
11:10	0b RW	DPC_AUX_DEGLITCH_AMOUNT: Project: All Default Value: 0b See DPB description. Value Name Description Project 00b 50 ns 25 clocks - GMBUS type - 50ns at 500MHz cdclk All 01b 125 ns 1/4 2X bit clock divider value - 125ns All 10b 62.5 ns 1/8 2X bit clock divider value - 62.5ns All 11b 31.125 ns 1/16 2X bit clock divider value - 31.125ns All
9	0b RW	RESERVED_1: Project: All Format:
8	0b RW	DPC_AUX_MULTIPLE_RECEIVED_EDGES_ERROR_ENABLE: Project: All Default Value: 0b Value Name Description Project 0b Okay Multiple edges in window is okay All 1b Error Multiple edges in window is an error All
7:6	0b RW	DPC_AUX_DEBUG_STATUS_READBACK: Project: All Default Value: 0b Value Name Description Project 00b Program Readback of bit clock divide field gives the programmed clock frequency All 01b Recover Readback of bit clock divide field gives the recovered clock frequency All 10b Error Type Readback of bit clock divide field gives the error type All
5:0	0b RW	RESERVED_2: Project: All Format:



Bit Range	Default & Access	Field Name (ID): Description
12	0b RW	_16_BIT_CONTAINER: When this bit is set 16-bit sample is stored in 16-bit container format. When it is clear container is 32-bit for each sample regardless of valid bits (default) 1= 16-bit container 0= 32-bit container
11	0b RW	UNDERRUN_PACKET_BIT_SILENT_STREAM_ENABLE: Set this bit will enable HW to send valid zero-filled packet with Sample flat bit set when no sample buffer is available, NCTS packets (or Timestamp packet) are sent to keep sink in sync even no audio sound will heard. 1= send underrun packets (silent stream) 0= send null packets (default) Programming note: SW driver shall always set silent stream bit. When SW driver wants to pause audio, it shall invalidate the two newest allocated audio buffers. When the current audio buffers are processed, silent stream is sent automatically.
10	0b RW	USER_BIT_U: HW will clear this bit in each sub-frames it sends, But this bit allows to overwrite hardware setting for special operation like debug or testing for compliance 1= set U bit in sub-frame 0= clear U bit in sub-frame (default)
9	1b RW	VALIDITY_BIT_V: HW will set this bit in both each sub-frames it sends. But this bit allows to overwrite hardware setting for special operation like debug or testing for compliance 1= Set V bit in sub-frame (default) 0= clear V bit in sub-frame. For debug or testing
8	0b RW	SAMPLE_FLAT_BIT: When set the sample flat bit will be set in all HDMI sub-packets. 1= flat bit is set for valid sample 0= flat bit is not set for valid sample (default)
7	1b RW	SET_BLOCK_BEGIN_FOR_ALL_SUB_PACKETS: Controls the B bit in the header of only the first Audio Packet /frame of a 192 frame 60958 block in Layout 1 mode. This bit only applies to LPE HDMI mode. 0: The B bit will be set only for sub-packet 0 1: The B bit in the Audio sample packet header will be set for all valid sub-packets. (default)
6:4	0b RW	NUM_AUDIO_CHANNELS: 000: 2 channels (stereo) 001: 3 channels 010: 4 channels 011: 5 channels 100: 6 channels 101: 7 channels 110: 8 channels Note: When disable_bogus sample bit is clear HW will always treat odd number of channels similar to the next higher even number. Thus 3 is similar to 4, 5 to 6 and 7 to 8. This is because SW ensures that an even number of samples are packed in the audio buffers. Programming note: Bit 6 of this field is a write only bit. When reads back, it always returns zero. Ensure to write bit 6 to 1'b1 when programming for 6/7/8 audio channels.
3:2	0b RW	FORMAT: 00: L-PCM or IEC 61937 01: High Bit Rate IEC 61937 stream packet (not supported) 10: One Bit Audio Sample packet (not supported) 11: DST Audio Sample packet (not supported)
1	0b RW	LAYOUT: 0: Layout 0 (2-ch) 1: Layout 1 (3-8 ch) Note: Layout bit doesn't matter for HBR
0	0b RW	AUDIO_ENABLE: Controls generation of N/CTS and transmission of audio sample packets. 0: Audio sample packets are not transmitted, CTS calculation/transmission is disabled 1: Audio sample packets are transmitted and CTS calculation is enabled When enable audio unit will wait until the next vertical blank period before sending out the audio packets. When disable, audio unit may continue to send audio packet until the end of current active video frame before stopping.



Bit Range	Default & Access	Field Name (ID): Description
31:25	0b RW	RESERVED: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RW	BUFFER_ADDRESS: . This is physical address of audio sample buffer A, need to 64-byte aligned.
5:2	0b RW	RESERVED: Reserved.
1	0b RW	INTERRUPT_ENABLE: If enable hardware will generate an interrupt when it is done fetching this buffer
0	0b RW	BUFFER_VALID: . This bit is set by S/W when the mem_addr is written and is cleared by H/W when done reading the data from memory

14.11.147 STREAM_A_LPE_AUD_BUF_D_LENGTH—Offset 6505Ch

Length for Audio Buffer D

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6505Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RW	RESERVED: Reserved.
19:0	0b RW	BUFFER_LENGTH_: This field shows the remaining length of data that needs to be read from memory; Initially set by S/W for total of bytes that are valid and is decremented by H/W as reads are issued. Software must end buffer at the boundary of a audio sample with all of channel values of that sample are valid.



14.11.148 STREAM_A_LPE_AUD_CNTL_ST—Offset 65060h

LPE Audio Control State Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 65060h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED	RESERVED_1	RESERVED_	DIP_TYPE_ENABLE_STATUS_READ_ONLY	DIP_BUFFER_INDEX_R_W	DIP_TRANSMISSION_FREQUENCY_R_W	CP_READY RESERVED_R_W	RESERVED_2	RESERVED_1 RESERVED_3 DIP_RAM_ACCESS_ADDRESS_R_W

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	RESERVED: Reserved.
30:29	0b RW	RESERVED_1: Reserved.
28:25	0b RW	RESERVED_: for later DIP type if needed: Must be 0.
24:21	0b RW	DIP_TYPE_ENABLE_STATUS_READ_ONLY: These bits reflects the DIP types enabled. It can be updated while the port is enabled. Within 2 vblank periods, the DIP is guaranteed to have been transmitted. Disabling an DIP type results in setting the contents of that DIP buffer to zero. A reserved setting reflects a disabled DIP. XXX1 = Audio DIP enable status (Default = disabled) XX1X = Generic 1 (ACP) DIP enable status (Default = disabled) X1XX = Generic 2 (ISRC1) DIP enable status, can be used by ISRC1 or ISRC2 (Default = disabled) 1XXX = Reserved
20:18	0b RW	DIP_BUFFER_INDEX_R_W: This field is used during read or write of different DIPs, and during read or write of ELD data. These bits are used as an index to their respective DIP or ELD buffers. When the index is not valid, the contents of the DIP will return all 0s. 000 = (Default) Audio DIP (31 bytes of address space, 13 bytes of data) 001 = Generic 1 (ACP) Data Island Packet (31 bytes of address space, 11 bytes of data) 010 = Generic 2 (ISRC1) Data Island Packet (31 bytes of address space, 31 bytes of data) 011 = Generic 3 (ISRC2) Data Island Packet (31 bytes of address space, 31 bytes of data) 1XX = reserved



Bit Range	Default & Access	Field Name (ID): Description
17:16	0b RW	DIP_TRANSMISSION_FREQUENCY_R_W: These bits reflect the frequency of DIP transmission for the DIP buffer type designated in bits 20:18. When writing DIP data, this value is also latched when the first DW of the DIP is written. When read, this value reflects the DIP transmission frequency for the DIP buffer designated in bits 20:18. 00 = Disabled (Default) 01 = once per frame 10 = Send once 11 = Best effort (Send at least every other vsync)
15	0b RW	CP_READY: This R/W bit reflects the state of CP request from the audio unit. When an audio CP request has been serviced, it must be reset to 1 by the video software to indicate that the CP request has been serviced. 0 = CP request pending or not ready to receive requests (default) 1 = CP request ready CP_ready bit is programmable through Bit 14 for [DevCL, DevBLC]. CP_ready bit is programmable through Bit 15 for [DevCTG]. Bit 15 Reserved for [DevCL, DevBLC].
14	0b RW	RESERVED_R_W: ELD valid: This bit reflects the state of the ELD data written to the ELD RAM. After writing the ELD data, the video software must set this bit to 1 to indicate that the ELD data is valid. At audio codec initialization, or on a hotplug event, this bit is set to 0 by the video software. This bit is reflected in the audio pin complex widget as the ELD valid status bit. 0 = ELD data invalid (default, when writing ELD data, set 0 by software) 1 = ELD data valid (Set by video software only) ELD bit is programmable through Bit 13 for [DevCL, DevBLC]. ELD bit is programmable through Bit 14 for [DevCTG].
13:9	0b RW	RESERVED_2: ELD buffer size (read only) 10000 = This field reflects the size of the ELD buffer in DWORDs 13:9 reflects ELD buffer size for [DevCTG]. 12:9 reflects ELD buffer size for [DevCL, DevBLC].
8:5	0b RW	RESERVED_1: ELD access address (R/W): Selects the DWORD address for access to the ELD buffer (48 bytes). The value wraps back to zero when incremented past the max addressing value 0xF. This field change takes effect immediately after being written. The read value indicates the current access address.
4	0b RW	RESERVED_3: ELD ACK: Acknowledgement from the audio driver that ELD read has been completed
3:0	0b RW	DIP_RAM_ACCESS_ADDRESS_R_W: Selects the DWORD address for access to the DIP buffers. The value wraps back to zero when it incremented past the max addressing value of 0xF. This field change takes effect immediately after being written. The read value indicates the current access address.

14.11.149 STREAM_A_LPE_AUD_HDMI_STATUS—Offset 65064h

LPE Audio Status

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 65064h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SAMPLE_BUFFER_UNDERRUN	AUDIO_BANDWIDTH_UNDERRUN_DEBUG	LPE_AUDIO_BUFFER_DONE_STATUS	RESERVED	NUMBER_OF_SAMPLES_BEHIND_DEBUG	SAMPLE_BUFFER_UNDERRUN_INTERRUPT_ENABLE	AUDIO_BANDWIDTH_UNDERRUN_INTERRUPT_ENABLE	RESERVED_1	AZALIA_COMPATIBLE_MODE
								AUDIO_SAMPLE_RUN_RATE_DEBUG
								FUNCTION_RESET_R_W_ONLY

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/1C	SAMPLE_BUFFER_UNDERRUN: This bit indicates an underrun in the sample buffer to HDMI controller when it needs to send. This bit is set at the last line of active video when there are no more sample in any valid buffers and HDMI audio unit has not satisfied number of audio samples intended in that video frame. Clearing this status bit is accomplished by writing a 1 to this bit through MMIO. AccessType: One to Clear
30	0b RW/1C	AUDIO_BANDWIDTH_UNDERRUN_DEBUG: This bit indicates an underrun of audio samples at HDMI audio packet assembly even there is still available sample buffers. Audio bandwidth underrun should not happen in normal functionality but it may happen when audio setting is inappropriate and/or memory bus was blocked by other clients, etc... This bit is set at the last line of active video when there is valid samples in a valid buffer and HDMI audio unit has not satisfied number of audio samples intended in that video frame Clearing this status bit is accomplished by writing a 1 to this bit through MMIO. AccessType: One to Clear
29	0b RW/1C	LPE_AUDIO_BUFFER_DONE_STATUS: This bit is set when a LPE audio buffer is completed transferred all of its data to LPE audio unit. This bit is clear when write 1 to it AccessType: One to Clear
28:24	0b RW	RESERVED: Reserved.
23:16	0b RO	NUMBER_OF_SAMPLES_BEHIND_DEBUG: This field is read only to get the number of audio samples that controller needs to load and send at the time of reading. AccessType: Read Only
15	0b RW	SAMPLE_BUFFER_UNDERRUN_INTERRUPT_ENABLE: This bit is to enable the first line buffer underrun interrupt when sample buffer underrun status is detected 0 = LPE sample Buffer Underrun Interrupt Disabled 1 = LPE sample Buffer Underrun Interrupt Enabled
14	0b RW	AUDIO_BANDWIDTH_UNDERRUN_INTERRUPT_ENABLE: This bit is to enable the first line bandwidth underrun interrupt when bandwidth underrun status is detected 0 = LPE Bandwidth Underrun Interrupt Disabled 1 = LPE Bandwidth Underrun Interrupt Enabled
13:3	0b RW	RESERVED_1: Reserved.

14.11.150 STREAM_A_LPE_AUD_HDMIW_INFOFR—Offset 65068h

Bit Range	Default & Access	Field Name (ID): Description
2	0b RW	AZALIA_COMPATIBLE_MODE: This bit is to enable the vucp, PR, ECC to be generated in the Azalia way 0 = Disable Azalia compatible mode on vucp, PR, ECC 1 = Enable Azalia compatible mode on vucp, PR, ECC
1	0b RW	AUDIO_SAMPLE_RUN_RATE_DEBUG: When set it allows to fetch sample 128 times than the real sample rate to allow a faster drain of sample buffers.
0	0b RW	FUNCTION_RESET_R_W_ONLY: Write 1 to this bit will reset hardware within audio unit without needs of reset the full display controller. The FIFO and pointers will be reset and audio registers will be reset to default values. Write 0 will put the unit back to idle and ready to be programmed again.

14.11.150 STREAM_A_LPE_AUD_HDMIW_INFOFR—Offset 65068h

Audio HDMI Data Island Packet Data

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 65068h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DATA_ISLAND_PACKET_DATA								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	DATA_ISLAND_PACKET_DATA: When read, this returns the current value at the location specified in the Video DIP buffer index select and Video DIP RAM access address fields. The index used to address the RAM is incremented after each read or write of this register. DIP data can be read at any time. Data should be loaded into the RAM before enabling the transmission through the DIP type enable bit. Accesses to this register are on a per-DWORD basis



Bit Range	Default & Access	Field Name (ID): Description
12	0b RW	_16_BIT_CONTAINER: When this bit is set 16-bit sample is stored in 16-bit container format. When it is clear container is 32-bit for each sample regardless of valid bits (default) 1= 16-bit container 0= 32-bit container
11	0b RW	UNDERRUN_PACKET_BIT_SILENT_STREAM_ENABLE: Set this bit will enable HW to send valid zero-filled packet with Sample flat bit set when no sample buffer is available, NCTS packets (or Timestamp packet) are sent to keep sink in sync even no audio sound will heard. 1= send underrun packets (silent stream) 0= send null packets (default) Programming note: SW driver shall always set silent stream bit. When SW driver wants to pause audio, it shall invalidate the two newest allocated audio buffers. When the current audio buffers are processed, silent stream is sent automatically.
10	0b RW	USER_BIT_U: HW will clear this bit in each sub-frames it sends, But this bit allows to overwrite hardware setting for special operation like debug or testing for compliance 1= set U bit in sub-frame 0= clear U bit in sub-frame (default)
9	1b RW	VALIDITY_BIT_V: HW will set this bit in both each sub-frames it sends. But this bit allows to overwrite hardware setting for special operation like debug or testing for compliance 1= Set V bit in sub-frame (default) 0= clear V bit in sub-frame. For debug or testing
8	0b RW	SAMPLE_FLAT_BIT: When set the sample flat bit will be set in all HDMI sub-packets. 1= flat bit is set for valid sample 0= flat bit is not set for valid sample (default)
7	1b RW	SET_BLOCK_BEGIN_FOR_ALL_SUB_PACKETS: Controls the B bit in the header of only the first Audio Packet /frame of a 192 frame 60958 block in Layout 1 mode. This bit only applies to LPE HDMI mode. 0: The B bit will be set only for sub-packet 0 1: The B bit in the Audio sample packet header will be set for all valid sub-packets. (default)
6:4	0b RW	NUM: audio Channels 000: 2 channels (stereo) 001: 3 channels 010: 4 channels 011: 5 channels 100: 6 channels 101: 7 channels 110: 8 channels Note: When disable_bogus sample bit is clear HW will always treat odd number of channels similar to the next higher even number. Thus 3 is similar to 4, 5 to 6 and 7 to 8. This is because SW ensures that an even number of samples are packed in the audio buffers. Programming note: Bit 6 of this field is a write only bit. When reads back, it always returns zero. Ensure to write bit 6 to 1'b1 when programming for 6/7/8 audio channels.
3:2	0b RW	FORMAT: 00: L-PCM or IEC 61937 01: High Bit Rate IEC 61937 stream packet (not supported) 10: One Bit Audio Sample packet (not supported) 11: DST Audio Sample packet (not supported)
1	0b RW	LAYOUT: 0: Layout 0 (2-ch) 1: Layout 1 (3-8 ch) Note: Layout bit doesn't matter for HBR
0	0b RW	AUDIO_ENABLE: Controls generation of N/CTS and transmission of audio sample packets. 0: Audio sample packets are not transmitted, CTS calculation/transmission is disabled 1: Audio sample packets are transmitted and CTS calculation is enabled When enable audio unit will wait until the next vertical blank period before sending out the audio packets. When disable, audio unit may continue to send audio packet until the end of current active video frame before stopping.





Default: 00FAC688h

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RO	RESERVED: Reserved.
23:21	111b RO	SAMPLE_INDEX_FOR_SECOND_CHANNEL_OF_SUBPACKET_3: This field has the index of 32-byte buffer block that will be send out as the second channel sample of subpacket 3 in a HDMI audio packet
20:18	110b RO	SAMPLE_INDEX_FOR_FIRST_CHANNEL_OF_SUBPACKET_3: This field has the index of 32-byte buffer block that will be send out as the first channel sample of subpacket 1 in a HDMI audio packet
17:15	101b RO	SAMPLE_INDEX_FOR_SECOND_CHANNEL_OF_SUBPACKET_2: This field has the index of 32-byte buffer block that will be send out as the second channel sample of subpacket 0 in a HDMI audio packet
14:12	100b RO	SAMPLE_INDEX_FOR_FIRST_CHANNEL_OF_SUBPACKET_2: This field has the index of 32-byte buffer block that will be send out as the first channel sample of subpacket 0 in a HDMI audio packet
11:9	011b RO	SAMPLE_INDEX_FOR_SECOND_CHANNEL_OF_SUBPACKET_1: This field has the index of 32-byte buffer block that will be send out as the second channel sample of subpacket 1 in a HDMI audio packet
8:6	010b RO	SAMPLE_INDEX_FOR_FIRST_CHANNEL_OF_SUBPACKET_1: This field has the index of 32-byte buffer block that will be send out as the first channel sample of subpacket 1 in a HDMI audio packet
5:3	001b RO	SAMPLE_INDEX_FOR_SECOND_CHANNEL_OF_SUBPACKET_0: This field has the index of 32-byte buffer block that will be send out as the second channel sample of subpacket 0 in a HDMI audio packet
2:0	0b RO	SAMPLE_INDEX_FOR_FIRST_CHANNEL_OF_SUBPACKET_0: This field has the index of 32-byte buffer block that will be send out as the first channel sample of subpacket 0 in a HDMI audio packet



14.11.158 STREAM_B_LPE_AUD_BUF_A_ADDR—Offset 65840h

Address for Audio Buffer A

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 65840h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BUFFER_ADDRESS							RESERVED	INTERRUPT_ENABLE BUFFER_VALID

Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RW	BUFFER_ADDRESS: . This is physical address of audio sample buffer A, need to 64-byte aligned.
5:2	0b RW	RESERVED: Reserved.
1	0b RW	INTERRUPT_ENABLE: If enable hardware will generate an interrupt when it is done fetching this buffer
0	0b RW	BUFFER_VALID: . This bit is set by S/W when the mem_addr is written and is cleared by H/W when done reading the data from memory

14.11.159 STREAM_B_LPE_AUD_BUF_A_LENGTH—Offset 65844h

Length for Audio Buffer A

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 65844h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RW	BUFFER_ADDRESS: . This is physical address of audio sample buffer A, need to 64-byte aligned.
5:2	0b RW	RESERVED: Reserved.
1	0b RW	INTERRUPT_ENABLE: If enable hardware will generate an interrupt when it is done fetching this buffer
0	0b RW	BUFFER_VALID: . This bit is set by S/W when the mem_addr is written and is cleared by H/W when done reading the data from memory

14.11.163 STREAM B LPE AUD BUF C LENGTH—Offset 65854h

Length for Audio Buffer C

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 65854h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				BUFFER_LENGTH				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RW	RESERVED: Reserved.
19:0	0b RW	BUFFER_LENGTH_: This field shows the remaining length of data that needs to be read from memory; Initially set by S/W for total of bytes that are valid and is decremented by H/W as reads are issued. Software must end buffer at the boundary of a audio sample with all of channel values of that sample are valid.

14.11.164 STREAM B LPE_AUD_BUF_D ADDR—Offset 65858h

Address for Audio Buffer D

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 65858h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RW	BUFFER_ADDRESS: . This is physical address of audio sample buffer A, need to 64-byte aligned.
5:2	0b RW	RESERVED: Reserved.
1	0b RW	INTERRUPT_ENABLE: If enable hardware will generate an interrupt when it is done fetching this buffer
0	0b RW	BUFFER_VALID: . This bit is set by S/W when the mem_addr is written and is cleared by H/W when done reading the data from memory

14.11.165 STREAM_B_LPE_AUD_BUF_D_LENGTH—Offset 6585Ch

Length for Audio Buffer D

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 6585Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RW	RESERVED: Reserved.
19:0	0b RW	BUFFER_LENGTH_: This field shows the remaining length of data that needs to be read from memory; Initially set by S/W for total of bytes that are valid and is decremented by H/W as reads are issued. Software must end buffer at the boundary of a audio sample with all of channel values of that sample are valid.



Bit Range	Default & Access	Field Name (ID): Description
20:18	0b RW	DIP_BUFFER_INDEX_R_W: This field is used during read or write of different DIPs, and during read or write of ELD data. These bits are used as an index to their respective DIP or ELD buffers. When the index is not valid, the contents of the DIP will return all 0s. 000 = (Default) Audio DIP (31 bytes of address space, 13 bytes of data) 001 = Generic 1 (ACP) Data Island Packet (31 bytes of address space, 11 bytes of data) 010 = Generic 2 (ISRC1) Data Island Packet (31 bytes of address space, 31 bytes of data) 011 = Generic 3 (ISRC2) Data Island Packet (31 bytes of address space, 31 bytes of data) 1XX = reserved
17:16	0b RW	DIP_TRANSMISSION_FREQUENCY_R_W: These bits reflect the frequency of DIP transmission for the DIP buffer type designated in bits 20:18. When writing DIP data, this value is also latched when the first DW of the DIP is written. When read, this value reflects the DIP transmission frequency for the DIP buffer designated in bits 20:18. 00 = Disabled (Default) 01 = once per frame 10 = Send once 11 = Best effort (Send at least every other vsync)
15	0b RW	CP_READY: This R/W bit reflects the state of CP request from the audio unit. When an audio CP request has been serviced, it must be reset to 1 by the video software to indicate that the CP request has been serviced. 0 = CP request pending or not ready to receive requests (default) 1 = CP request ready CP_ready bit is programmable through Bit 14 for [DevCL, DevBLC]. CP_ready bit is programmable through Bit 15 for [DevCTG]. Bit 15 Reserved for [DevCL, DevBLC].
14	0b RW	RESERVED_2: ELD valid: This R/W bit reflects the state of the ELD data written to the ELD RAM. After writing the ELD data, the video software must set this bit to 1 to indicate that the ELD data is valid. At audio codec initialization, or on a hotplug event, this bit is set to 0 by the video software. This bit is reflected in the audio pin complex widget as the ELD valid status bit. 0 = ELD data invalid (default, when writing ELD data, set 0 by software) 1 = ELD data valid (Set by video software only) ELD bit is programmable through Bit 13 for [DevCL, DevBLC]. ELD bit is programmable through Bit 14 for [DevCTG].
13:9	0b RW	RESERVED_3: ELD buffer size (read only) 10000 = This field reflects the size of the ELD buffer in DWORDs 13:9 reflects ELD buffer size for [DevCTG]. 12:9 reflects ELD buffer size for [DevCL, DevBLC].
8:5	0b RW	RESERVED_: ELD access address (R/W): Selects the DWORD address for access to the ELD buffer (48 bytes). The value wraps back to zero when incremented past the max addressing value 0xF. This field change takes effect immediately after being written. The read value indicates the current access address.
4	0b RW	RESERVED_4: ELD ACK: Acknowledgement from the audio driver that ELD read has been completed
3:0	0b RW	DIP_RAM_ACCESS_ADDRESS_R_W: Selects the DWORD address for access to the DIP buffers. The value wraps back to zero when it incremented past the max addressing value of 0xF. This field change takes effect immediately after being written. The read value indicates the current access address.



14.11.167 STREAM_B_LPE_AUD_HDMI_STATUS—Offset 65864h

LPE Audio Status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 65864h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SAMPLE_BUFFER_UNDERRUN_STATUS	AUDIO_BANDWIDTH_UNDERRUN_DEBUG_STATUS	LPE_AUDIO_BUFFER_DONE_STATUS	RESERVED	NUMBER_OF_SAMPLES_BEHIND_DEBUG	SAMPLE_BUFFER_UNDERRUN_INTERRUPT_ENABLE	AUDIO_BANDWIDTH_UNDERRUN_INTERRUPT_ENABLE	RESERVED_1	AZALIA_COMPATIBLE_MODE
								AUDIO_SAMPLE_RUN_RATE_DEBUG
								FUNCTION_RESET_R_W_ONLY

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/1C	SAMPLE_BUFFER_UNDERRUN_STATUS: This bit indicates an underrun in the sample buffer to HDMI/DP controller when it needs to send. This bit is set at the last line of active video when there are no more sample in any valid buffers and HDMI/DP audio unit has not satisfied number of audio samples intended in that video frame. Clearing this status bit is accomplished by writing a 1 to this bit through MMIO. AccessType: One to Clear
30	0b RW/1C	AUDIO_BANDWIDTH_UNDERRUN_DEBUG_STATUS: This bit indicates an underrun of audio samples at HDMI audio packet assembly even there is still available sample buffers. Audio bandwidth underrun should not happen in normal functionality but it may happen when audio setting is inappropriate and/or memory bus was blocked by other clients, etc... This bit is set at the last line of active video when there is valid samples in a valid buffer and HDMI audio unit has not satisfied number of audio samples intended in that video frame. Clearing this status bit is accomplished by writing a 1 to this bit through MMIO. AccessType: One to Clear
29	0b RW/1C	LPE_AUDIO_BUFFER_DONE_STATUS: This bit is set when a LPE audio buffer is completed transferred all of its data to LPE audio unit. This bit is clear when write 1 to it. AccessType: One to Clear
28:24	0b RW	RESERVED: Reserved.





14.11.170 PIPEA_SLC—Offset 70004h

Pipe A Display Scan Line Count Range Compare

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70004h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
INCLUSIVE_EXCLUSIVE	RESERVED	START_SCAN_LINE_NUMBER				RESERVED_1	END_SCAN_LINE_NUMBER	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	INCLUSIVE_EXCLUSIVE: 1 = Inclusive: within the range. 0 = Exclusive: outside of the range.
30:29	0b RW	RESERVED: Read only.
28:16	0b RW	START_SCAN_LINE_NUMBER: [DevBLC, DevCTG, DevCDV] This field specifies the starting scan line number of the Scan Line Window. Format = U16 in scan lines, where scan line 0 is the first line of the display frame. Range = [0, Display Buffer height in lines-1]. [DevBW, DevCL] End Scan Line Number: This field specifies the ending scan line number of the Scan Line Window. Format = U16 in scan lines, where scan line 0 is the first line of the display frame. Range = [0, Display Buffer height in lines-1].
15:13	0b RW	RESERVED_1: Read only.
12:0	0b RW	END_SCAN_LINE_NUMBER: [DevBLC, DevCTG, DevCDV] This field specifies the ending scan line number of the Scan Line Window. Format = U16 in scan lines, where scan line 0 is the first line of the display frame. Range = [0, Display Buffer height in lines-1]. [DevBW] and [DevCL] Start Scan Line Number: This field specifies the starting scan line number of the Scan Line Window. Format = U16 in scan lines, where scan line 0 is the first line of the display frame. Range = [0, Display Buffer height in lines-1].



14.11.171 PIPEACONF—Offset 70008h

Pipe A Configuration Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70008h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h


Default: 00000000h



31	0	PIPE_A_ENABLE
0	0	PIPE_STATE
28	0	DSI_PLL_LOCK_LOCK
0	0	FRAME_START_DELAY
0	0	DISPLAY_PORT_AUDIO_ONLY_MODE
0	0	FORCE_BORDER
24	0	PIPE_A_GAMMA_UNIT_MODE
0	0	INTERLACED_MODE
20	0	MIPI_DISPLAY_SELF_REFRESH_MODE_FOR_MIPI_A_REFRESH
0	0	DISPLAY_OVERLAY_PLANES_OFF
0	0	CURSOR_PLANES_OFF
16	0	REFRESH_RATE_CXSR_MODE_ASSOCIATION
0	0	COLOR_CORRECTION_MATRIX_ENABLE_ON_PIPE_A_1_COLOR_CORRECTION_COEFFICIENTS_ARE_ENABLED_TO_PERFORM_COLOR_CORRECTION_0_COLOR_CORRECTION_COEFFICIENTS_ARE_DISABLED
12	0	DISPLAYPORT_POWER_MODE_SWITCH_DEVILVP
0	0	COLOR_RANGE_SELECT
0	0	S3D_SPRITE_ORDER
0	0	S3D_SPRITE_INTERLEAVING_FORMAT
8	0	RESERVED
0	0	BITS_PER_COLOR
4	0	DITHERING_ENABLE
0	0	DITHERING_TYPE
0	0	DDA_RESET_TEST_MODE
0	0	RESERVED_1



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	PIPE_A_ENABLE: Setting this bit to the value of one, turns on pipe A. This must be done before any planes are enabled on this pipe. Changing it to a zero should only be done when all planes that are assigned to this pipe have been disabled. Turning the pipe enable bit off disables the timing generator in this pipe. Plane disable occurs after the next VBLANK event after the plane is disabled. Synchronization pulses to the display are not maintained if the timing generator is disabled. Power consumption will be at its lowest state when disabled. A separate bit controls the DPLL enable for this pipe. Pipe timing registers should contain valid values before this bit is enabled. 0 = Disable 1 = Enable
30	0b RO	PIPE_STATE: This bit indicates the actual state of the pipe. Since there can be some delay between disabling the pipe and the pipe actually shutting off, this bit indicates the true current state of the pipe. 0 = Disabled 1 = Enabled AccessType: Read Only
29	0b RO	DSI_PLL_LOCK_LOCK: This bit indicates the clocks from DSI PLL are locked. 0 = Unlocked 1 = Locked AccessType: Read only
28:27	0b RW	FRAME_START_DELAY: (TEST MODE) Used to delay the frame start signal that is sent to the display planes. Normal operation uses the default 00 value and test modes can use the delayed frame start to shorten the test time. Care must be taken to insure that there are enough lines during VBLANK to support this setting. 00 = Frame Start occurs on the first HBLANK after the start of VBLANK 01 = Frame Start occurs on the second HBLANK after the start of VBLANK 10 = Frame Start occurs on the third HBLANK after the start of VBLANK 11 = Frame Start occurs on the forth HBLANK after the start of VBLANK
26	0b RW	DISPLAY_PORT_AUDIO_ONLY_MODE: [DevVLVP] Setting this bit to 1 indicates the DisplayPort will output audio only. 0 = DisplayPort will output Video or Video and Audio 1 = DisplayPort will output Audio only
25	0b RW	FORCE_BORDER: : (TEST MODE) 0 = Normal Operation 1 = Color information is ignored and border color is substituted during active region
24	0b RW	PIPE_A_GAMMA_UNIT_MODE: This bit selects which mode the pipe gamma correction logic works in. In the palette mode, it behaves as a 3X256x8 RAM lookup. VGA and indexed mode operation should use the palette in 8-bit mode. In the 10-bit gamma mode, it will act as a piecewise linear interpolation. Other gamma units such as in the overlay or sprite are unaffected by this bit. 0 = 8-bit Palette Mode 1 = 10-bit Gamma Mode
23:21	0b RW	INTERLACED_MODE: These bits are used for software control of interlaced behavior. They are updated immediately if the pipe is off, or in the vertical blank after programming if pipe is enabled. 0xx = Progressive 100 = Interlaced embedded panel using programmable vertical sync shift. (2x) 101 = Interlaced using vertical sync shift. Backup option to 110 setting. (2x) 110 = Interlaced with VSYNC/HSYNC Field Indication using legacy vertical sync shift. Used for SDVO. 111 = Interlaced with Field 0 Only using legacy vertical sync shift. Not used Note: VGA display modes, sDVO line stall, and Panel fitting do not work while in interlaced modes Setting the Interlaced embedded panel mode causes hardware to automatically modify the output to match the specifications of panels that support interlaced mode.
20	0b RW	MIPI_DISPLAY_SELF_REFRESH_MODE_FOR_MIPI_A_REFRESH: 0 = Normal Operation, display controller generate timing and refresh display panel at refresh rate 1 = Display self-refresh mode. Display controller update frame buffer in display module on demand only



Bit Range	Default & Access	Field Name (ID): Description
19	0b RW	DISPLAY_OVERLAY_PLANES_OFF: This bit when set will cause all enabled Display and overlay planes that are assigned to this pipe to be disabled by overriding the current setting of the plane enable bit, at the next VBLANK. Timing signals continue as they were but the screen becomes blank. Setting the bit back to a zero will then allow the display and overlay planes to resume on the following VBLANK. 0 = Normal Operation 1 = Planes assigned to this pipe are disabled.
18	0b RW	CURSOR_PLANES_OFF: This bit when set will cause all enabled cursor planes that are assigned to this pipe to be disabled by overriding the current setting of the plane enable bit, at the next VBLANK. Timing signals continue as they were but the cursor(s) no longer appear on the screen. Setting the bit back to a zero will then allow the cursor planes to resume on the following VBLANK. 0 = Normal Operation 1 = Planes assigned to this pipe are disabled.
17:16	0b RW	REFRESH_RATE_CXSR_MODE_ASSOCIATION: These bits select how refresh rates are tied to big FIFO mode on pipe A. When they are set to anything other than 00, bits 23:21 of this register must be programmed to 0xx. Switching between 01 and 10 settings directly is not allowed. Software must program this field to 00 before switching. Software is responsible for enabling this mode only for integrated display panels that support corresponding mode. 00 Default no dynamic refresh rate change enabled. Software control only. 01 Progressive-to-progressive refresh rate change enabled and tied to big FIFO mode. Pixel clock values set in FPA0/FPA1 settings in the DPLLA control register and FPA0/FPA1 divider registers. FPA0 is tied to non-big-FIFO mode 10 Progressive-to-interlaced refresh rate change enabled and tied to big FIFO mode. Pixel clock value does not change in this case. Scaling must be disabled in this mode. Uses programmable VS shift 11 Reserved
15	0b RW	COLOR_CORRECTION_MATRIX_ENABLE_ON_PIPE_A_1_COLOR_CORRECTION_COEFFICIENTS_ARE_ENABLED_TO_PERFORM_COLOR_CORRECTION_0_COLOR_CORRECTION_COEFFICIENTS_ARE_DISABLED_: 1 = Color Correction Coefficients are enabled to perform color correction 0 = Color Correction Coefficients are disabled
14	0b RW	DISPLAYPORT_POWER_MODE_SWITCH_DEVVLVP: This bit selects the software controlled progressive to progressive power saving mode (software controlled DRRS). Hardware Controlled Refresh Rate Select must be disabled when enabling this. Link and data M/N 1 values are used for normal settings, M/N 2 values are used for low power settings. 0 Normal progressive refresh rate (default) 1 Low Power progressive refresh rate
13	0b RW	COLOR_RANGE_SELECT: [DevVLVP]: This bit is used to select the color range of RGB outputs. 0 = Apply full 0-255 color range to the output (Default) 1 = Apply 16-235 color range to the output
12	0b RW	S3D_SPRITE_ORDER: This bit controls the blending order of the sprite planes for S3D support: 0 = Sprite A first. The first line or pixel comes from Sprite A (default) 1 = Sprite B first. The first line or pixel comes from Sprite B
11:10	0b RW	S3D_SPRITE_INTERLEAVING_FORMAT: These bits control the Sprite A/B interleaving format in S3D mode 00 = No interleaving 01 = Line interleaving 10 = Pixel interleaving 11 = Reserved
9:8	0b RW	RESERVED: [DevCDV, DevVLVP] MBZ Scrambling enable [DevCTG]: This bit enables scrambling for DisplayPort. Software must set this bit appropriately when enabling a DisplayPort output. 00 = Scrambling disabled (Default) 01 = Scrambling enabled, no SR after initialization at loop 2 of training 10 - RESERVED 11 = Scrambling and SR enabled. Scrambling is reset every 512 BS symbols.



Bit Range	Default & Access	Field Name (ID): Description
7:5	0b RW	BITS_PER_COLOR: [DevCTG, DevCDV, DevVLP]: This field selects the number of bits per color sent to a receiver device connected to this port. Color format takes place on the Vblank after being written. Color format change can be done independent of a pixel clock change in DisplayPort. Selecting a pixel color depth higher or lower than the pixel color depth of the frame buffer results in dithering the output stream. For further details on Display Port fixed frequency programming to accommodate these formats refer to DP Frequency Programming in DPLL section of Bspec. 000 = 8 bits per color (Default) 001 = 10 bits per color 010 = 6 bits per color 011 = RESERVED 1xx = RESERVED
4	0b RW	DITHERING_ENABLE: [DevCTG, DevCDV]: This bit enables dithering for DisplayPort 6bpc or 8bpc modes 0 Dithering disabled (Default) 1 Dithering enabled Programming note: Dithering should only be enabled for 8 bpc or 6 bpc.
3:2	0b RW	DITHERING_TYPE: [DevCTG, DevCDV]: This bit selects dithering type for DisplayPort 6bpc or 8bpc modes 00 - Spatial only (default) 01 - Spatio-Temporal 1 10 - Spatio-Temporal 2 (testmode) 11 - Temporal only (testmode)
1	0b RW	DDA_RESET_TEST_MODE: [DevCTG, DevCDV]: 0 Do not reset DDA 1 Reset DDA every 8th display frame
0	0b RW	RESERVED_1: Write as zero

14.11.172 PIPEAGCMAXRED—Offset 70010h

Pipe A Gamma Correction Max Red

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70010h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00010000h



Bit Range	Default & Access	Field Name (ID): Description
31:17	0b RW	RESERVED: Reserved.
16:0	100000000 00000000b RW	MAX_RED_GAMMA_CORRECTION_POINT: 129th reference point for red channel of the pipe piecewise linear gamma correction. The value should always be programmed to be less than or equal to 1024.0. Format: 11.6 Default: 0x10000

14.11.173 PIPEAGCMAXGREEN—Offset 70014h


Pipe A Gamma Correction Max Green

Access Method

Offset: [GTTMMADR_LSB + 180000h] + 70014h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00010000h



Bit Range	Default & Access	Field Name (ID): Description
31:17	0b RW	RESERVED: Reserved.
16:0	100000000 00000000b RW	MAX_GREEN_GAMMA_CORRECTION_POINT: 129th reference point for green channel of the pipe piecewise linear gamma correction. The value should always be programmed to be less than or equal to 1024.0. Format: 11.6 Default: 0x10000

Pipe A Gamma Correction Max Blue

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70018h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00010000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				MAX_BLUE_GAMMA_CORRECTION_POINT				

Bit Range	Default & Access	Field Name (ID): Description
31:17	0b RW	RESERVED: Reserved.
16:0	100000000 00000000b RW	MAX_BLUE_GAMMA_CORRECTION_POINT: 129th reference point for blue channel of the pipe piecewise linear gamma correction. The value should always be programmed to be less than or equal to 1024.0. Format: 11.6 Default: 0x10000



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
FIFO_A_UNDER_RUN_STATUS	SPRITE_B_FLIP_DONE_INTERRUPT_ENABLE	CRC_ERROR_ENABLE	CRC_DONE_ENABLE	GMBUS_EVENT_ENABLE	PLANE_A_FLIP_DONE_INTERRUPT_ENABLE	VERTICAL_SYNC_INTERRUPT_ENABLE	DISPLAY_LINE_COMPARE_ENABLE	DPST_EVENT_ENABLE
SPRITE_A_FLIP_DONE_INTERRUPT_ENABLE	ODD_FIELD_INTERRUPT_EVENT_ENABLE	EVEN_FIELD_INTERRUPT_EVENT_ENABLE	PERFORMANCE_COUNTER_EVENT_ENABLE	START_OF_VERTICAL_BLANK_INTERRUPT_ENABLE	FRAMESTART_INTERRUPT_ENABLE	PIPE_A_HORIZONTAL_BLANK_INTERRUPT_ENABLE	SPRITE_B_FLIP_DONE_INTERRUPT_STATUS	SPRITE_A_FLIP_DONE_INTERRUPT_STATUS
CRC_ERROR_INTERRUPT_STATUS	CRC_DONE_INTERRUPT_STATUS	GMBUS_INTERRUPT_STATUS	PLANE_A_FLIP_DONE_INTERRUPT_STATUS	VERTICAL_SYNC_INTERRUPT_STATUS	DISPLAY_LINE_COMPARE_INTERRUPT_STATUS	DPST_EVENT_STATUS	PIPE_A_PANEL_SELF_REFRESH_STATUS	ODD_FIELD_INTERRUPT_STATUS
EVEN_FIELD_INTERRUPT_STATUS	PERFORMANCE_MONITOR_EVENT_INTERRUPT	START_OF_VERTICAL_BLANK_INTERRUPT_STATUS	FRAMESTART_INTERRUPT_STATUS	PIPE_A_HORIZONTAL_BLANK_STATUS				

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/1C	FIFO_A_UNDER_RUN_STATUS: Set when a pipe A FIFO under-run occurs, cleared by a write of a 1. An underrun has occurred on an attempt to pop an empty FIFO. This does not feed into the first line interrupt status register. This will occur naturally during mode changes, to be useful, it should be cleared after a mode change has occurred. This bit is only valid after Pipe A has been completely configured. 1 = FIFO A Underflow occurred 0 = FIFO A Underflow did not occur AccessType: One to Clear
30	0b RW	SPRITE_B_FLIP_DONE_INTERRUPT_ENABLE: This will enable the consideration of the Sprite B flip done interrupt status bit in the first line interrupt logic 0 = Sprite B Flip Done Interrupt Disabled 1 = Sprite B Flip Done Interrupt Enabled
29	0b RW	CRC_ERROR_ENABLE: This will enable the consideration of the CRC error status bit in the first line interrupt/status logic. 0 = CRC Error Detect Disabled 1 = CRC Error Detect Enabled
28	0b RW	CRC_DONE_ENABLE: This will enable the consideration of the CRC error status bit in the first line interrupt/status logic. 0 = CRC Done Detect Disabled 1 = CRC Done Detect Enabled
27	0b RW	GMBUS_EVENT_ENABLE: This will enable the use of the GMBUS interrupt status bit in the first line interrupt/status logic. 0 = No GMBUS event enabled 1 = GMBUS event enabled
26	0b RW	PLANE_A_FLIP_DONE_INTERRUPT_ENABLE: This will enable the consideration of the Plane A flip done interrupt status bit in the first line interrupt logic 0 = Plane A flip done Interrupt/Status Disabled 1 = Plane A flip done Interrupt/Status Enabled
25	0b RW	VERTICAL_SYNC_INTERRUPT_ENABLE: This will enable the consideration of the vertical sync interrupt status bit in the first line interrupt logic. 0 = Vertical Sync Interrupt/Status Disabled 1 = Vertical Sync Interrupt/Status Enabled
24	0b RW	DISPLAY_LINE_COMPARE_ENABLE: This will enable the consideration of the line compare interrupt status bit in the first line interrupt/status logic. 0 = Display Line Compare Interrupt/Status Disabled 1 = Display Line Compare Interrupt/Status Enabled



Bit Range	Default & Access	Field Name (ID): Description
23	0b RW	DPST_EVENT_ENABLE: [DevCL, DevCTG, DevCDV]: This interrupt is generated by the DPST logic. 0 = No DPST event enabled 1 = DPST event enabled
22	0b RW	SPRITE_A_FLIP_DONE_INTERRUPT_ENABLE: This will enable the consideration of the Sprite A flip done interrupt status bit in the first line interrupt logic 0 = Sprite A Flip Done Interrupt Disabled 1 = Sprite A Flip Done Interrupt Enabled
21	0b RW	ODD_FIELD_INTERRUPT_EVENT_ENABLE: This bit should only be used when this pipe is in an interlaced display timing. 0 = Odd Field Event disable 1 = Odd Field Event enable
20	0b RW	EVEN_FIELD_INTERRUPT_EVENT_ENABLE: This bit should only be used when this pipe is in an interlaced display timing. 0 = Even field Event disable 1 = Even field Event enable
19	0b RW	PERFORMANCE_COUNTER_EVENT_ENABLE: performance counter event enable
18	0b RW	START_OF_VERTICAL_BLANK_INTERRUPT_ENABLE: This will enable the consideration of the start of vertical blank interrupt status bit in the first line interrupt/status logic. 0 = Start of Vertical Blank Interrupt/Status Disabled 1 = Start of Vertical Blank Interrupt/Status Enabled
17	0b RW	FRAMESTART_INTERRUPT_ENABLE: This will enable the consideration of the vertical blank interrupt status bit in the first line interrupt/status logic. 0 = Vertical Blank Interrupt/Status Disabled 1 = Vertical Blank Interrupt/Status Enabled
16	0b RW	PIPE_A_HORIZONTAL_BLANK_INTERRUPT_ENABLE: : This will enable the consideration of the start of horizontal blank interrupt status bit in the first line interrupt/status logic 0 = Start of Horizontal Blank Interrupt/Status Disabled 1 = Start of Horizontal Blank Interrupt/Status Enabled
15	0b RW/1C	SPRITE_B_FLIP_DONE_INTERRUPT_STATUS: MMIO Flip Event is completed on Sprite B 0 = Sprite B Flip Not Done 1 = Sprite B Flip Done AccessType: One to Clear
14	0b RW/1C	SPRITE_A_FLIP_DONE_INTERRUPT_STATUS: MMIO Flip Event is completed on Sprite A 0 = Sprite A Flip Not Done 1 = Sprite A Flip Done AccessType: One to Clear
13	0b RW/1C	CRC_ERROR_INTERRUPT_STATUS: This sticky status bit is set when a Pipe A CRC error is detected. It is cleared by a write of a one. For this bit to be meaningful, the pipe and pixel clock should be enabled and running. 0 = No CRC error has occurred 1 = CRC Error Detected AccessType: One to Clear
12	0b RW/1C	CRC_DONE_INTERRUPT_STATUS: This sticky status bit is set when Pipe A CRC calculation and compare are complete. It is cleared by a write of a one. For this bit to be meaningful, the pipe and pixel clock should be enabled and running. 0 = CRC Not Done 1 = CRC Done AccessType: One to Clear
11	0b RW/1C	GMBUS_INTERRUPT_STATUS: This status bit will be set on a GMBUS event. To use this bit in a polling manner, clear the bit by writing a one to it followed by the polling loop waiting for it to become set. 0 = GMBUS event has not occurred 1 = GMBUS event has occurred AccessType: One to Clear



Bit Range	Default & Access	Field Name (ID): Description
10	0b RW/1C	PLANE_A_FLIP_DONE_INTERRUPT_STATUS: Async/Sync Flip Event is completed on Display Plane A 0 = Plane A Flip Not Done 1 = Plane A Flip Done AccessType: One to Clear
9	0b RW/1C	VERTICAL_SYNC_INTERRUPT_STATUS: This bit provides a sticky status that is set when a pipe A vertical sync occurs, cleared by a write of a 1. For interlaced timing modes, this occurs once per field, when in progressive, it occurs once per frame. For this bit to be meaningful, the pipe and pixel clock should be enabled and running. 0 = Vertical Sync has not occurred 1 = Vertical Sync has occurred AccessType: One to Clear
8	0b RW/1C	DISPLAY_LINE_COMPARE_INTERRUPT_STATUS: Set when a pipe A compare match occurs, cleared by a write of a 1. 0 = Display Line Compare has not been satisfied 1 = Display Line Compare has been satisfied AccessType: One to Clear
7	0b RW/1C	DPST_EVENT_STATUS: [DevCL, DevCTG, DevCDV]: This bit is cleared when a write to this register occurs with this bit as a one. Writes with this bit as a zero has no effect on the value of the bit. Multiple DPST events (Histogram or Phase In) can cause this bit to be asserted, determination of which event occurred is done in the DPST registers. 0 = DPST Interrupt has not occurred on pipe A 1 = DPST Interrupt has occurred on pipe A AccessType: One to Clear
6	0b RW/1C	PIPE_A_PANEL_SELF_REFRESH_STATUS: This bit indicates interrupt is generated by the PSR controller and intends to send interrupt to SW driver when the PSR interrupt enable bit (70028h bit 22) is set. This is cleared when a write to this register occurs with this bit as a one. Write with this bit as a zero has no effect on the value of the bit. 0 = PSR Interrupt has not occurred on pipe A 1 = PSR interrupt has occurred on pipe A AccessType: One to Clear
5	0b RW/1C	ODD_FIELD_INTERRUPT_STATUS: This status bit will be set on a Odd field VBLANK event. This bit should only be used when this pipe is in an interlaced display timing. For synchronization with register updates, the actual event will occur one line after the start of VBLANK. To use this bit in a polling manner, clear the bit by writing a one to it followed by the polling loop waiting for it to become set. Note: This bit will not be set when pipe is in Interlaced with Field 0 Only using legacy vertical sync shift mode. 0 = Odd Field Vertical Blank has not occurred 1 = Odd Field Vertical Blank has occurred AccessType: One to Clear
4	0b RW/1C	EVEN_FIELD_INTERRUPT_STATUS: This status bit will be set on a even field VBLANK event. This bit should only be used when this pipe is in an interlaced display timing. For synchronization with register updates, the actual event will occur one line after the start of VBLANK. To use this bit in a polling manner, clear the bit by writing a one to it followed by the polling loop waiting for it to become set. Note: This bit will not be set when pipe is in Interlaced with Field 0 Only using legacy vertical sync shift mode. 0 = Even Field Vertical Blank has not occurred 1 = Even Field Vertical Blank has occurred AccessType: One to Clear
3	0b RW/1C	PERFORMANCE_MONITOR_EVENT_INTERRUPT: AccessType: One to Clear
2	0b RW/1C	START_OF_VERTICAL_BLANK_INTERRUPT_STATUS: This status bit will be set at the beginning of a VBLANK event. At this point, the double buffered display registers flip, taking their new values. To use this bit in a polling manner, clear the bit by writing a one to it followed by the polling loop waiting for it to become set. In MIPI DSR mode, GPIO TE trigger sets the Vblank Interrupt status 0 = Start of Vertical Blank has not occurred 1 = Start of Vertical Blank has occurred AccessType: One to Clear



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW/1C	FRAMESTART_INTERRUPT_STATUS: This status bit will be set on a VBLANK event, when the frame start occurs. The display registers are updated at the start of vertical blank, but the new register data is not utilized by the display pipeline until the point in the vertical blank period when the frame start occurs, which is the event that triggers this bit. To use this bit in a polling manner, clear the bit by writing a one to it followed by the polling loop waiting for it to become set. 0 = Vertical Blank has not occurred 1 = Vertical Blank has occurred AccessType: One to Clear
0	0b RW/1C	PIPE_A_HORIZONTAL_BLANK_STATUS: 0 = Pipe A Horizontal Blank has not occurred 1 = Pipe A Horizontal Blank has occurred AccessType: One to Clear

14.11.176 DPFLIPSTAT—Offset 70028h

Display FLIP Status Register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70028h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	RESERVED: MBZ
29	0b RW	DISPLAY_PIPE_B_LINE_COMPARE_INTERRUPT_STATUS_ENABLE: 0 = Display Pipe B Line Compare Interrupt Disabled 1 = Display Pipe B Line Compare Interrupt Enabled
28	0b RW	PIPE_B_HORIZONTAL_BLANK_INTERRUPT_ENABLE: 0 = Pipe B Horizontal Blank Interrupt Disabled 1 = Pipe B Horizontal Blank Interrupt Enabled
27	0b RW	PIPE_B_VERTICAL_BLANK_INTERRUPT_ENABLE: 0 = Pipe B Vertical Blank Interrupt Disabled 1 = Pipe B Vertical Blank Interrupt Enabled
26	0b RW	SPRITE_D_FLIP_DONE_INTERRUPT_ENABLE: 0 = Sprite D Flip Done Interrupt Disabled 1 = Sprite D Flip Done Interrupt Enabled
25	0b RW	SPRITE_C_FLIP_DONE_INTERRUPT_ENABLE: 0 = Sprite C Flip Done Interrupt Disabled 1 = Sprite C Flip Done Interrupt Enabled
24	0b RW	PLANE_B_FLIP_DONE_INTERRUPT_ENABLE: 0 = Plane B Flip Done Interrupt Disabled 1 = Plane B Flip Done Interrupt Enabled
23	0b RW	RESERVED_1: Reserved.
22	0b RW	PANEL_SELF_REFRESH_PSR_INTERRUPT_ENABLE_ON_PIPE_A_0_PSR_INTERRUPT_DISABLED_ON_PIPE_A_1_PSR_INTERRUPT_ENABLED_ON_PIPE_A: 0 = PSR interrupt Disabled on Pipe A 1 = PSR Interrupt Enabled on Pipe A
21	0b RW	DISPLAY_PIPE_A_LINE_COMPARE_INTERRUPT_STATUS_ENABLE: 0 = Display Pipe A Line Compare Interrupt Disabled 1 = Display Pipe A Line Compare Interrupt Enabled
20	0b RW	PIPE_A_HORIZONTAL_BLANK_INTERRUPT_ENABLE: 0 = Pipe A Horizontal Blank Interrupt Disabled 1 = Pipe A Horizontal Blank Interrupt Enabled
19	0b RW	PIPE_A_VERTICAL_BLANK_INTERRUPT_ENABLE: 0 = Pipe A Vertical Blank Interrupt Disabled 1 = Pipe A Vertical Blank Interrupt Enabled
18	0b RW	SPRITE_B_FLIP_DONE_INTERRUPT_ENABLE: 0 = Sprite B Flip Done Interrupt Disabled 1 = Sprite B Flip Done Interrupt Enabled
17	0b RW	SPRITE_A_FLIP_DONE_INTERRUPT_ENABLE: 0 = Sprite A Flip Done Interrupt Disabled 1 = Sprite A Flip Done Interrupt Enabled
16	0b RW	PLANE_A_FLIP_DONE_INTERRUPT_ENABLE: 0 = Plane A Flip Done Interrupt Disabled 1 = Plane A Flip Done Interrupt Enabled
15:0	0b RW	RESERVED_2: MBZ

14.11.177 DPINVGTT—Offset 7002Ch

Display Invalid GTT PTE Status Register

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7002Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				CURSOR_B_INVALID_GTT_PTE_INTERRUPT_ENABLE	RESERVED_1			
				CURSOR_A_INVALID_GTT_PTE_INTERRUPT_ENABLE				
				SPRITE_D_INVALID_GTT_PTE_INTERRUPT_ENABLE				
				SPRITE_C_INVALID_GTT_PTE_INTERRUPT_ENABLE				
				PLANE_B_INVALID_GTT_PTE_INTERRUPT_ENABLE				
				SPRITE_B_INVALID_GTT_PTE_INTERRUPT_ENABLE				
				SPRITE_A_INVALID_GTT_PTE_INTERRUPT_ENABLE				
				PLANE_A_INVALID_GTT_PTE_INTERRUPT_ENABLE				



Bit Range	Default & Access	Field Name (ID): Description
16	0b RW	PLANE_A_INVALID_GTT_PTE_INTERRUPT_ENABLE: 0 = Plane A Invalid GTT PTE Interrupt Disabled 1 = Plane A Invalid GTT PTE Interrupt Enabled
15:8	0b RW	RESERVED_1: MBZ
7	0b RW/1C	CURSOR_B_INVALID_GTT_PTE_STATUS: 0 = Cursor B encountered an invalid GTT PTE has not occurred 1 = Cursor B encountered an invalid GTT PTE has occurred AccessType: One to Clear
6	0b RW/1C	CURSOR_A_INVALID_GTT_PTE_STATUS: 0 = Cursor A encountered an invalid GTT PTE has not occurred 1 = Cursor A encountered an invalid GTT PTE has occurred AccessType: One to Clear
5	0b RW/1C	SPRITE_D_INVALID_GTT_PTE_STATUS: 0 = Sprite D encountered an invalid GTT PTE has not occurred 1 = Sprite D encountered an invalid GTT PTE has occurred. AccessType: One to Clear
4	0b RW/1C	SPRITE_C_INVALID_GTT_PTE_STATUS: 0 = Sprite C encountered an invalid GTT PTE has not occurred 1 = Sprite C encountered an invalid GTT PTE has occurred. AccessType: One to Clear
3	0b RW/1C	PLANE_B_INVALID_GTT_PTE_STATUS: 0 = Plane B encountered an invalid GTT PTE has not occurred 1 = Plane B encountered an invalid GTT PTE has occurred. AccessType: One to Clear
2	0b RW/1C	SPRITE_B_INVALID_GTT_PTE_STATUS: 0 = Sprite B encountered an invalid GTT PTE has not occurred 1 = Sprite B encountered an invalid GTT PTE has occurred. AccessType: One to Clear
1	0b RW/1C	SPRITE_A_INVALID_GTT_PTE_STATUS: 0 = Sprite A encountered an invalid GTT PTE has not occurred 1 = Sprite A encountered an invalid GTT PTE has occurred. AccessType: One to Clear
0	0b RW/1C	PLANE_A_INVALID_GTT_PTE_STATUS: 0 = Plane A encountered an invalid GTT PTE has not occurred 1 = Plane A encountered an invalid GTT PTE has occurred. AccessType: One to Clear

14.11.178 DSPARB—Offset 70030h

Display Arbitration Control

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70030h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 80008000h



14.11.179 FW1—Offset 70034h

Access Method

Offset: [GTTMMADR LSB + 180000h] + 70034h

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
855

14.11.180 FW2—Offset 70038h

Display FIFO Watermark Control 2

Access Method

31				28				24				20				16				12				8				4				0			
0	0	1	1	1	1	1	1	1	0	0	0	1	1	1	1	0	0	0	0	1	1	1	1	0	0	0	0	1	1	1	1				
DISPLAY_FIFO_SELF_REFRESH_WATERMARK_PROGRAMMING								RESERVED_				CURSOR_B_FIFO_WATERMARK_								DISPLAY_PLANE_B_FIFO_WATERMARK								DISPLAY_PLANE_A_FIFO_WATERMARK							

Bit Range	Default & Access	Field Name (ID): Description
31:23	00111111b RW	DISPLAY_FIFO_SELF_REFRESH_WATERMARK_PROGRAMMING: This register defines the value of the watermark used by the Display streamer in case the CPU is in C2/C3/C4 and the memory has entered self refresh. Number in 64Bs of space in FIFO above which the Display Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).Note [DevCL, DevCTG, DevCDV]: When calculating watermark values for 15/16bpp display formats, assume 32bpp for purposes of calculation using the high priority bandwidth analysis spreadsheet.
22	0b RW	RESERVED_: MBZ
21:16	001111b RW	CURSOR_B_FIFO_WATERMARK_: Number in 64Bs of space in the Cursor B FIFO above which the Cursor B Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet). DevBW, DevCL, DevCDV] Always program to 8.
15:8	00001111b RW	DISPLAY_PLANE_B_FIFO_WATERMARK: Number in 64Bs of space in FIFO above which the Display B Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet). [DevBW, DevCL, DevCDV] Always program to 8.
7:0	00001111b RW	DISPLAY_PLANE_A_FIFO_WATERMARK: Number in 64Bs of space in FIFO above which the Display A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet). [DevBW, DevCL, DevCDV] Always program to 8.



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70038h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 0B0F0F0Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	1	1	0
0	1	0	1	1	0	0	0	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1	1	1	1	1	1
0	1	0	1					

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	RESERVED: [DevCDV]: [DevCTG] FBC SR Watermark Enable: Enables the FBC watermarks to be used in the fetch calculation 0: disabled 1: enabled
30:28	0b RW	RESERVED_1: [DevCDV]: [DevCTG] FBC SR Watermark: Number of equivalent lines of the primary display SR watermark
27:24	1011b RW	RESERVED_2: [DevCDV] [DevCTG] FBC SR HPLL Watermark: Number of equivalent lines of the primary display SR HPLL watermark.
23:16	00001111b RW	RESERVED_3: [DevCDV]: [DevBLKC, DevCTG] Display Plane Sprite B FIFO Watermark Number in 64Bs of space in FIFO above which the Display Sprite B Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
15:14	0b RW	RESERVED_4: : MBZ
13:8	001111b RW	CURSOR_A_FIFO_WATERMARK: Number in 64Bs of space in the Cursor A FIFO above which the Cursor A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet). DevBW, DevCL, DevCDV] Always program to 8.



Bit Range	Default & Access	Field Name (ID): Description
7:0	00001111b RW	DEVBLKC_DEVCTG_DISPLAY_PLANE_SPRITE_A_FIFO_WATERMARK: Number in 64Bs of space in FIFO above which the Display Sprite A Stream will generate requests to Memory DevBW, DevCL] Display Plane C FIFO Watermark. Number in 64Bs of space in FIFO above which the Display C Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet). [DevBW, DevCL, DevCDV] Always program to 8.

14.11.181 FW3—Offset 7003Ch

Display FIFO Watermark Control 3

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7003Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ENABLE_HPLL_OFF_DURING_SELF_REFRESH	RESERVED	CURSOR_FIFO_SELF_REFRESH_WATERMARK	RESERVED_1	HPLL_SELF_REFRESH_CURSOR_WATERMARK	RESERVED_		HPLL_SELF_REFRESH_DISPLAY_WATERMARK	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	ENABLE_HPLL_OFF_DURING_SELF_REFRESH: . 0 = Disabled 1 = Enabled [DevCL] This bit may be enabled only if the BLC_PWM_CTL duty cycle register offset (0x61254) is programmed to 100% and non-legacy backlight is enabled. This restriction does not apply when I2C is used for back light modulation. [DevCL] When one or more display pipes are enabled, this bit should be disabled before accessing the 6XXXh MMIO register address space. Software must follow these steps: disable this bit (if enabled and one display pipe is enabled) wait for next vblank (switch from hrawclk back to cdclk will occur) access the 6XXXh address space as needed re-enable this bit Note that the wait on next vblank step requires an enabled display pipe.
30	0b RW	RESERVED: : MBZ



Bit Range	Default & Access	Field Name (ID): Description
29:24	0b RW	CURSOR_FIFO_SELF_REFRESH_WATERMARK: . Number in 64Bs of space in the Cursor FIFO above which the Cursor Stream will generate requests to Memory during self -refresh. (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
23:22	0b RW	RESERVED_1: : MBZ
21:16	0b RW	HPLL_SELF_REFRESH_CURSOR_WATERMARK: . Number in 64Bs of space in the Cursor FIFO above which the Cursor Stream will generate requests to Memory during HPLL self -refresh. (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
15:9	0b RW	RESERVED_: MBZ
8:0	0b RW	HPLL_SELF_REFRESH_DISPLAY_WATERMARK: . Number in 64Bs of space in the FIFO above which the Display Stream will generate requests to Memory during HPLL self -refresh. (Value should be as recommended in the high priority bandwidth analysis spreadsheet).

14.11.182 PIPEAFRAMECOUNT—Offset 70040h

Pipe A Frame Counter

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70040h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PIPE_A_FRAME_COUNT								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RO	PIPE_A_FRAME_COUNT: Provides read back of the display pipe frame counter. This counter increments on every start of vertical blank and rolls over back to 0 after 2^32 frames



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	HARDWARE_DRIVE_MSA_MISC1_ENABLE: This bit enables hardware to drive MSA MISC1 bit3:1 with the stereo 3D left/right eye field indication. Hardware will drive 000 when S3D mode is disabled, 001 when enabled and the upcoming video frame is right eye, 011 when enabled and the upcoming video frame is left eye. When this bit is disabled, software may manually program the MSA MISC1 Field S3D field in bit 2:0 in this register to set MISC1 bit 3:1 0 = Disable hardware driving MSA MISC1 bit 3:1. Allow software to manually program MSA MISC1 bit3:1 through MSA_MISC1_FIELD_S3D (default) 1 = Enable hardware to drive MSA MISC1 bit3:1 for S3D
30:3	0b RW	RESERVED: Reserved.
2:0	0b RW	MSA_MISC1_FIELD_S3D: This field provides software to manually program MSA MISC1 stereo video attribute for DisplayPort: 000 = No stereo video transported 001 = For progressive video, the next (upcoming) video frame is RIGHT eye 010 = Reserved 011 = For progressive video, the next (upcoming) video frame is LEFT eye 100 = Stacked top and bottom top half represents left-eye view and bottom half represents right-eye view 101 = Stacked top and bottom top half represents right-eye view and bottom half represents left-eye view

Intel Atom® Processor E3800 Product Family
Datasheet
861



31	28				24				20				16				12				8				4				0																																																																																																		
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																	
DISPLAY_CURSOR_A_DRAIN_LATENCY_PRECISION_SELECT				CURSOR_A_DRAIN_LATENCY_VALUE																												DISPLAY_SPRITE_B_DRAIN_LATENCY_PRECISION_SELECT				SPRITE_B_DRAIN_LATENCY_VALUE																												DISPLAY_SPRITE_A_DRAIN_LATENCY_PRECISION_SELECT				SPRITE_A_DRAIN_LATENCY_VALUE																												DISPLAY_PLANE_A_DRAIN_LATENCY_PRECISION_SELECT				DISPLAY_PLANE_A_DRAIN_LATENCY_VALUE																											

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	DISPLAY_CURSOR_A_DRAIN_LATENCY_PRECISION_SELECT: [DevVLVP] 1 use 64 as precision multiplier to increase precision to be stored in 7-bit Cursor A drain latency value 0 use 32 as precision multiplier to increase precision to be stored in 7-bit Cursor A drain latency value
30:24	0b RW	CURSOR_A_DRAIN_LATENCY_VALUE: [DevVLVP] For cursor latency, 4 BPP is assumed for all cursor formats. : Programmable drain latency value in time ticks per 64B FIFO entry
23	0b RW	DISPLAY_SPRITE_B_DRAIN_LATENCY_PRECISION_SELECT: [DevVLVP] 1 use 64 as precision multiplier to increase precision to be stored in 7-bit Sprite B drain latency value 0 use 32 as precision multiplier to increase precision to be stored in 7-bit Sprite B drain latency value
22:16	0b RW	SPRITE_B_DRAIN_LATENCY_VALUE: [DevVLVP] Programmable drain latency value in time ticks per 64B FIFO entry
15	0b RW	DISPLAY_SPRITE_A_DRAIN_LATENCY_PRECISION_SELECT: [DevVLVP] 1 use 64 as precision multiplier to increase precision to be stored in 7-bit Sprite A drain latency value 0 use 32 as precision multiplier to increase precision to be stored in 7-bit Sprite A drain latency value
14:8	0b RW	SPRITE_A_DRAIN_LATENCY_VALUE: [DevVLVP] Programmable drain latency value in time ticks per 64B FIFO entry
7	0b RW	DISPLAY_PLANE_A_DRAIN_LATENCY_PRECISION_SELECT: [DevVLVP] 1 use 64 as precision multiplier to increase precision to be stored in 7-bit Plane A drain latency value 0 use 32 as precision multiplier to increase precision to be stored in 7-bit Plane A drain latency value
6:0	0b RW	DISPLAY_PLANE_A_DRAIN_LATENCY_VALUE: [DevVLVP] Programmable drain latency value in time ticks per 64B FIFO entry



14.11.186 DDL2—Offset 70054h

Display FIFO Drain Latency 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70054h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28				24				20				16				12				8				4				0																																		
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																			
DISPLAY_CURSOR_B_DRAIN_LATENCY_PRECISION_SELECT				CURSOR_B_DRAIN_LATENCY_VALUE												DISPLAY_SPRITE_D_DRAIN_LATENCY_PRECISION_SELECT				SPRITE_D_DRAIN_LATENCY_VALUE												DISPLAY_SPRITE_C_DRAIN_LATENCY_PRECISION_SELECT				SPRITE_C_DRAIN_LATENCY_VALUE												DISPLAY_PLANE_B_DRAIN_LATENCY_PRECISION_SELECT				DISPLAY_PLANE_B_DRAIN_LATENCY_VALUE											

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	DISPLAY_CURSOR_B_DRAIN_LATENCY_PRECISION_SELECT: [DevVLVP] 1 use 64 as precision multiplier to increase precision to be stored in 7-bit Cursor B drain latency value 0 use 32 as precision multiplier to increase percision to be stored in 7-bit Cursor B drain latency value
30:24	0b RW	CURSOR_B_DRAIN_LATENCY_VALUE: [DevVLVP] For cursor latency, 4 BPP is assumed for all cursor formats
23	0b RW	DISPLAY_SPRITE_D_DRAIN_LATENCY_PRECISION_SELECT: [DevVLVP] 1 use 64 as precision multiplier to increase precision to be stored in 7-bit Sprite D drain latency value 0 use 32 as precision multiplier to increase percision to be stored in 7-bit Sprite D drain latency value
22:16	0b RW	SPRITE_D_DRAIN_LATENCY_VALUE: [DevVLVP]



Bit Range	Default & Access	Field Name (ID): Description
11:9	0b RW	RESERVED_1: Reserved.
8	1b RW	SPRITE_CSTART_HIGH_ORDER: This field is the high order bits for Sprite C Start pointer. Combined with lower order 8-bit Sprite C Start pointer, this field selects the end of the ram used for display B and the start of the RAM for Sprite C. If display B is unused, this field can be set to zero. The value should never exceed the size of the RAM (TOTALSIZE). The size of the display B FIFO will be (Sprite C START)*64 bytes.
7:5	0b RW	RESERVED_MBZ: Reserved.
4	1b RW	SPRITE_B_START_HIGH_ORDER: This field is the high order bits for Sprite B Start pointer. Combined with lower order 8-bit Sprite B Start pointer, this field selects the end of the ram used for Sprite A and the start of the RAM for Sprite B. If sprite A is unused, this field can be set to the same value as Sprite A START. If Sprite B is unused, this field can be set to TOTALSIZE-1. It must be programmed to a number greater than or equal to the value in Sprite A START and less than the total size of the RAM (TOTALSIZE). The size of the Sprite A FIFO will be (Sprite B START-Sprite A START)*64. The size of the Sprite B FIFO will be (TOTALSIZE-Sprite B START-1) *64 bytes. [DevBLC and DevCTG]: Reserved: Write as zero.
3:1	0b RW	RESERVED_MBZ_1: Reserved.
0	1b RW	SPRITE_A_START_HIGH_ORDER: This field is the high order bits for Sprite A Start pointer. Combined with lower order 8-bit Sprite A Start pointer, this field selects the end of the ram used for display A and the start of the RAM for Sprite A. If display A is unused, this field can be set to zero. The value should never exceed the size of the RAM (TOTALSIZE). The size of the display A FIFO will be (Sprite A START)*64 bytes.

14.11.188 DSPHOWM—Offset 70064h

Display FIFO WM High Order

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70064h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
15:13	0b RW	RESERVED_3: Reserved.
12	0b RW	DISPLAY_PLANE_B_FIFO_WATERMARK_HIGH_ORDER: This field is the high order bit for Display B FIFO WM. Combined with lower order 8-bit Display B FIFO WM, it forms a 9-bit Display B FIFO WM pointer. Number in 64Bs of space in FIFO above which the Display A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
11:9	0b RW	RESERVED_4: Reserved.
8	0b RW	SPRITE_B_FIFO_WATERMARK_HIGH_ORDER: This field is the high order bit for Sprite B FIFO WM. Combined with lower order 8-bit Sprite B FIFO WM, it forms a 9-bit Sprite B FIFO WM pointer. Number in 64Bs of space in FIFO above which the Display A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
7:5	0b RW	RESERVED_5: MBZ
4	0b RW	SPRITE_A_FIFO_WATERMARK_HIGH_ORDER: This field is the high order bit for Sprite A FIFO WM. Combined with lower order 8-bit Sprite A FIFO WM, it forms a 9-bit Sprite A FIFO WM pointer. Number in 64Bs of space in FIFO above which the Display A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
3:1	0b RW	RESERVED_6: MBZ
0	0b RW	DISPLAY_PLANE_A_FIFO_WATERMARK_HIGH_ORDER: This field is the high order bit for Display A FIFO WM. Combined with lower order 8-bit Display A FIFO WM, it forms a 9-bit Display A FIFO WM pointer. Number in 64Bs of space in FIFO above which the Display A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).

14.11.189 DSPHOWM1—Offset 70068h

Display FIFO WM1 High Order

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70068h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
15:13	0b RW	RESERVED_3: Reserved.
12	0b RW	DISPLAY_PLANE_B_FIFO_WATERMARK1_HIGH_ORDER: This field is the high order bit for Display B FIFO WM1. Combined with lower order 8-bit Display B FIFO WM1, it forms a 9-bit Display B FIFO WM1 pointer. Number in 64Bs of space in FIFO above which the Display A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
11:9	0b RW	RESERVED_4: Reserved.
8	0b RW	SPRITE_B_FIFO_WATERMARK1_HIGH_ORDER: This field is the high order bit for Sprite B FIFO WM1. Combined with lower order 8-bit Sprite B FIFO WM1, it forms a 9-bit Sprite B FIFO WM1 pointer. Number in 64Bs of space in FIFO above which the Display A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
7:5	0b RW	RESERVED_5: MBZ
4	0b RW	SPRITE_A_FIFO_WATERMARK1_HIGH_ORDER: This field is the high order bit for Sprite A FIFO WM1. Combined with lower order 8-bit Sprite A FIFO WM1, it forms a 9-bit Sprite A FIFO WM1 pointer. Number in 64Bs of space in FIFO above which the Display A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
3:1	0b RW	RESERVED_6: MBZ
0	0b RW	DISPLAY_PLANE_A_FIFO_WATERMARK1_HIGH_ORDER: This field is the high order bit for Display A FIFO WM1. Combined with lower order 8-bit Display A FIFO WM1, it forms a 9-bit Display A FIFO WM1 pointer. Number in 64Bs of space in FIFO above which the Display A Stream will generate requests to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).

14.11.190 FW4—Offset 70070h

Display FIFO Watermark1 Control 4

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70070h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00040404h



Bit Range	Default & Access	Field Name (ID): Description
31:24	00000100b RW	DISPLAY_B_FIFO_WATERMARK1: [DevCDV] Number in 64Bs of space in FIFO above which the Display B Stream will generate request with status 2
23:16	00000100b RW	DISPLAY_A_FIFO_WATERMARK1: [DevCDV] Number in 64Bs of space in FIFO above which the Display A Stream will generate request with status 2
15:14	0b RW	RESERVED: : MBZ
13:8	000100b RW	CURSOR_B_FIFO_WATERMARK1: DevCDV] Number in 64Bs of space in the Cursor B FIFO above which the Cursor B Stream will generate requests with status 2 to Memory (Value should be as recommended in the high priority bandwidth analysis spreadsheet).
7:6	0b RW	RESERVED_1: : MBZ
5:0	000100b RW	CURSORFIFO_SELF_REFRESH_WATERMARK1: DevCDV] Number in 64Bs of space in FIFO above which the Display Cursor Stream will generate request with status 2 during memory SR (Value should be as recommended in the high priority bandwidth analysis spreadsheet).


Display FIFO Watermark1 Control 6

Type: Memory Mapped I/O Register
(Size: 32 bits)

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
871




14.11.194 CURACNTR—Offset 70080h

Access Method

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31:30	0b RW	RESERVED: Write as zero.
29:28	0b RW	PIPE_SELECT: [DevBW, DevCL, DevCDV] A state machine handles the synchronization of the switch to both vertical blank signals. So as far as the software is concerned, when both display pipes are being used, it can be switched at any time; the hardware will synchronize the switch. 00 = HW cursor is attached to Display Pipe A. This is the default after reset. 01 = HW cursor is attached to Display Pipe B. 10 = Reserved for pipe C 11 = Reserved for pipe D [DevBLC] and [DevCTG] Reserved: Write as zero.
27	0b RW	POPOP_CURSOR_ENABLED: . This bit should be turned on when using Cursor A as a popup cursor. When in popup mode, hardware interprets the cursor base address as a physical address instead of a graphics address. 0 = Cursor A is hi-res 1 = Cursor A is popup
26	0b RW	CURSOR_GAMMA_ENABLE: This bit only has an effect when using the cursor in a non-VGA mode. In VGA pop-up operation, the cursor data will always bypass the gamma (palette) unit. 0 = Cursor pixel data bypasses gamma correction or palette (default). 1 = Cursor pixel data is gamma to be corrected in the pipe.
25:16	0b RW	RESERVED_1: Write as zero
15	0b RW	_180ROTATION: This mode causes the cursor to be rotated 180 . In addition to setting this bit, software must also set the base address to the lower right corner of the unrotated image. Only 32 bits per pixel cursors can be rotated. This field must be zero when the cursor format is 2 bits per pixel. 0 = No rotation 1 = 180 Rotation of 32 bit per pixel cursors
14:6	0b RW	RESERVED_2: Reserved.
5	0b RW	CURSOR_MODE_SELECT_BIT: See following table.
4	0b RW	RESERVED_3: Reserved.
3	0b RW	RESERVED_4: Reserved.
2:0	0b RW	CURSOR_MODE_SELECT: These three bits together with bit 5 select the mode for cursor as shown in the following table.

14.11.195 CURABASE—Offset 70084h

Cursor A Base Address Register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70084h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CURSOR_BASE_ADDRESS							RESERVED	POPUP_CURSOR_BASE_ADDRESS_MSBS
							DECRYPTION_REQUEST	

Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RW	CURSOR_BASE_ADDRESS: . This field specifies bits 31:6 of the graphics address of the base of the cursor. On [DevBW] and [DevCL] if the cursor is a popup, this field specifies bits 31:6 of the physical address of the base of the cursor, and bits 35:32 of the address are specified in the LSBs of this register. Popup cursor mode is selected within the CURACNTR register. The cursor surface address must be 4K byte aligned. The cursor must be in linear memory, it cannot be tiled. When performing 180 rotation, this offset must be the difference between the last pixel of the last line of the cursor data in its unrotated orientation and the cursor surface address. A write to this register also acts as a trigger event to force the update of active registers from the staging registers on the next display event. Each cursor register is double-buffered. The CPU writes to a set of holding registers. The active registers are updated from the holding registers following the leading edge of the vertical blank pulse. The update is postponed until the next vblank if a write cycle is active to any of the cursor registers at the time of the vblank. The update is also postponed if a write sequence is in progress. It is assumed that if the cursor mode is changed, the cursor image will also be changed. To prevent the cursor from appearing when it is only partially programmed, the active registers will not be updated until both the cursor control and base address registers have been programmed. If the cursor control register is written, the cursor base address must also be written before the change will be effective. However, the base address register may be changed (e.g., to change the shape of the cursor) without also writing to the control register. If both are to be written, the control register must be written first.
5	0b RW	RESERVED: MBZ
4	0b RW	DECRYPTION_REQUEST: This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register. 0 = Decryption request disabled (default) 1 = Decryption request enabled
3:0	0b RW	POPUP_CURSOR_BASE_ADDRESS_MSBS: ([DevBW] and [DevCL] Only). This field specifies bits 35:32 of the popup cursor physical address. If popup mode is not selected, this field is ignored.



14.11.196 CURAPOS—Offset 70088h

Cursor A Position Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70088h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CURSOR_Y_POSITION_SIGN_BIT	RESERVED	CURSOR_Y_POSITION_MAGNITUDE_BITS_11				CURSOR_X_POSITION_SIGN_BIT	RESERVED_1	CURSOR_X_POSITION_MAGNITUDE_BITS_11

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	CURSOR_Y_POSITION_SIGN_BIT: This bit provides the sign bit of a signed 13-bit value that specifies the horizontal position of cursor. (default is 0). For normal high resolution display modes, the cursor must have at least a single pixel positioned over the active screen. For use as a VGA Popup, the entire cursor must be positioned over the active area of the VGA image.
30:28	0b RW	RESERVED: Write as zero.
27:16	0b RW	CURSOR_Y_POSITION_MAGNITUDE_BITS_11: 0: This register provides the magnitude bits of a signed 12-bit value that specifies the vertical position of cursor. The sign bit of this value is provided by bit 31 of this register. (default is 0). For use as a VGA Popup, the entire cursor must be positioned over the active area of the VGA image. Enabling the border in VGA (VGA Border Enable bit in the VGA Config register) includes the border in what is considered the active area . For HDMI modes where the vertical zoom is greater than 1x, the position is specified using the zoomed grid. When performing 180 rotation, this field specifies the vertical position of the lower right corner relative to the end of the active video area in the unrotated orientation.
15	0b RW	CURSOR_X_POSITION_SIGN_BIT: This bit provides the sign bit of a signed 13-bit value that specifies the horizontal position of cursor. (default is 0).). For normal high resolution display modes, the cursor must have at least a single pixel positioned over the active screen. For use as a VGA Popup, the entire cursor must be positioned over the active area of the VGA image. Enabling the border in VGA (VGA Border Enable bit in the VGA Config register) includes the border in what is considered the active area .
14:12	0b RW	RESERVED_1: Write as zero.



Bit Range	Default & Access	Field Name (ID): Description
11:0	0b RW	CURSOR_X_POSITION_MAGNITUDE_BITS_11: 0: These 12 bits provide the signed 13-bit value that specifies the horizontal position of cursor. The sign bit is provided by bit 15 of this register. (default is 0) For HDMI modes where the horizontal zoom is greater than 1x, the position is specified using the zoomed grid. When performing 180 rotation, this field specifies the horizontal position of the lower right corner relative to the end of the active video area in the unrotated orientation.

14.11.197 CURAPALET 0—Offset 70090h

Cursor A Palette registers (4 Registers)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 70090h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				RED_OR_Y_VALUE				
				GREEN_OR_U_VALUE				
				BLUE_OR_V_VALUE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Write as zero.
23:16	0b RW	RED_OR_Y_VALUE: These registers specify the cursor palette. RGB data is full range unsigned numbers. YUV data will be unsigned for the Y and excess 128 notation for the UV values. The data can be pre-gamma corrected and bypass the gamma correction logic or passed through the gamma corrector.
15:8	0b RW	GREEN_OR_U_VALUE: These registers specify the cursor palette. RGB data is full range unsigned numbers. YUV data will be unsigned for the U and excess 128 notation for the YV values. The data can be pre-gamma corrected and bypass the gamma correction logic or passed through the gamma corrector.
7:0	0b RW	BLUE_OR_V_VALUE: These registers specify the cursor palette. RGB data is full range unsigned numbers. YUV data will be unsigned for the V and excess 128 notation for the YU values. The data can be pre-gamma corrected and bypass the gamma correction logic or passed through the gamma corrector.



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	RESERVED		RED_OR_Y_VALUE		GREEN_OR_U_VALUE		BLUE_OR_V_VALUE	

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Write as zero.
23:16	0b RW	RED_OR_Y_VALUE: These registers specify the cursor palette. RGB data is full range unsigned numbers. YUV data will be unsigned for the Y and excess 128 notation for the UV values. The data can be pre-gamma corrected and bypass the gamma correction logic or passed through the gamma corrector.
15:8	0b RW	GREEN_OR_U_VALUE: These registers specify the cursor palette. RGB data is full range unsigned numbers. YUV data will be unsigned for the U and excess 128 notation for the YV values. The data can be pre-gamma corrected and bypass the gamma correction logic or passed through the gamma corrector.
7:0	0b RW	BLUE_OR_V_VALUE: These registers specify the cursor palette. RGB data is full range unsigned numbers. YUV data will be unsigned for the V and excess 128 notation for the YU values. The data can be pre-gamma corrected and bypass the gamma correction logic or passed through the gamma corrector.

14.11.200 CURAPALET_3—Offset 7009Ch

Cursor A Palette registers (4 Registers)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7009Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	RESERVED		RED_OR_Y_VALUE		GREEN_OR_U_VALUE		BLUE_OR_V_VALUE	

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Write as zero.



Bit Range	Default & Access	Field Name (ID): Description
26	0b RW	CURSOR_GAMMA_ENABLE: 0 = Cursor pixel data bypasses gamma correction (default). 1 = Cursor pixel data is gamma to be corrected.
25:16	0b RW	RESERVED_2: Reserved.
15	0b RW	_180ROTATION: This mode causes the cursor to be rotated 180 . In addition to setting this bit, software must also set the base address to the lower right corner of the unrotated image. Only 32 bits per pixel cursors can be rotated. This field must be zero when the cursor format is 2 bits per pixel. 0 = No rotation 1 = 180 Rotation of 32 bit per pixel cursors
14:6	0b RW	RESERVED_3: Write as zero
5	0b RW	CURSOR_MODE_SELECT_BIT: See following table.
4:3	0b RW	RESERVED_4: reserved
2:0	0b RW	CURSOR_MODE_SELECT: These three bits together with bit 5 select the mode for cursor as shown in the following table.

14.11.203 CURBBASE—Offset 700C4h

Cursor B Base Address Register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 700C4h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CURSOR_BASE_ADDRESS								
RESERVED								
DECRYPTION_REQUEST_THIS_BIT_REQUESTS_DECRYPTION_TO_BE_ENABLED_FOR_THIS_PLANE								
POPUP_CURSOR_BASE_ADDRESS_MSB								



Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RW	CURSOR_BASE_ADDRESS: This register specifies the graphics address of the entire cursor. It also acts as a trigger event to force the update of active registers on the next display event. The cursor surface address must be 4K byte aligned. The cursor must be in linear memory, it cannot be tiled. When performing 180 rotation, this offset must be the difference between the last pixel of the last line of the cursor data in its unrotated orientation and the cursor surface address. A write to this register also acts as a trigger event to force the update of active registers from the staging registers on the next display event. Each cursor register is double-buffered. The CPU writes to a set of holding registers. The active registers are updated from the holding registers following the leading edge of the vertical blank pulse. The update is postponed until the next vblank if a write cycle is active to any of the cursor registers at the time of the vblank. The update is also postponed if a write sequence is in progress. It is assumed that if the cursor mode is changed, the cursor image will also be changed. To prevent the cursor from appearing when it is only partially programmed, the active registers will not be updated until both the cursor control and base address registers have been programmed. If the cursor control register is written, the cursor base address must also be written before the change will be effective. However, the base address register may be changed (e.g., to change the shape of the cursor) without also writing to the control register. If both are to be written, the control register must be written first.
5	0b RW	RESERVED: MBZ
4	0b RW	DECRYPTION_REQUEST_THIS_BIT_REQUESTS_DECRYPTION_TO_BE_ENABLED_FOR_THIS_PLANE: This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register. 0 = Decryption request disabled (default) 1 = Decryption request enabled
3:0	0b RW	POPUP_CURSOR_BASE_ADDRESS_MSBS: ([DevBW] and [DevCL] Only). This field specifies bits 35:32 of the popup cursor physical address. If popup mode is not selected, this field is ignored.

14.11.204 CURBPOS—Offset 700C8h

Cursor B Position Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 700C8h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CURSOR_Y_POSITION_SIGN_BIT	RESERVED	CURSOR_Y_POSITION_MAGNITUDE_BITS_11		CURSOR_X_POSITION_SIGN_BIT	RESERVED_1	CURSOR_X_POSITION_MAGNITUDE_BITS_11		

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	CURSOR_Y_POSITION_SIGN_BIT: This bit provides the sign bit of a signed 13-bit value that specifies the horizontal position of cursor. (default is 0).). For normal high resolution display modes, the cursor must have at least a single pixel positioned over the active screen.
30:28	0b RW	RESERVED: Write as zero.
27:16	0b RW	CURSOR_Y_POSITION_MAGNITUDE_BITS_11: 0: This register provides the magnitude bits of a signed 13-bit value that specifies the vertical position of cursor. The sign bit of this value is provided by bit 31 of this register. (default is 0) When performing 180 rotation, this field specifies the vertical position of the lower right corner relative to the end of the active video area in the unrotated orientation.
15	0b RW	CURSOR_X_POSITION_SIGN_BIT: This bit provides the sign bit of a signed 13-bit value that specifies the horizontal position of cursor. (default is 0).). For normal high resolution display modes, the cursor must have at least a single pixel positioned over the active screen. For HDMI modes where the vertical zoom is greater than 1x, the position is specified using the zoomed grid.
14:12	0b RW	RESERVED_1: Write as zero.
11:0	0b RW	CURSOR_X_POSITION_MAGNITUDE_BITS_11: 0: These 12 bits provide the signed 13-bit value that specifies the horizontal position of cursor. The sign bit is provided by bit 15 of this register. (default is 0) For HDMI modes where the horizontal zoom is greater than 1x, the position is specified using the zoomed grid. When performing 180 rotation, this field specifies the vertical position of the lower right corner relative to the end of the active video area in the unrotated orientation.



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED		RED_OR_Y		GREEN_OR_U_VALUE		BLUE_OR_V_VALUE		

14.11.209 CURBLIVEBASE—Offset 700ECh

Cursor B Live Base Address Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 700ECh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CURSOR_B_LIVE_BASE_ADDRESS								
RESERVED								
DECRYPTION_REQUEST_THIS_BIT_REQUESTS_DECRYPTION_TO_BE_ENABLED_FOR_THIS_PLANE								
POPUP_CURSOR_BASE_ADDRESS_MSB								

Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RO	CURSOR_B_LIVE_BASE_ADDRESS: This gives the live value of the surface base address as being currently used for Cursor B plane.
5	0b RO	RESERVED: MBZ



Bit Range	Default & Access	Field Name (ID): Description
11:4	0b RW	RESERVED: MBZ
3	0b RW	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All
2	0b RW	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register.
1:0	0b RW	RESERVED_1: MBZ

14.11.211 DSPACNTR—Offset 70180h

Display A Plane Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70180h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DISPLAY_PLANE_A_PRIMARY_A_ENABLE	DISPLAY_A_GAMMA_ENABLE	DISPLAY_A_SOURCE_PIXEL_FORMAT	PIPE_SELECT	KEY_WINDOW_ENABLE	KEY_ENABLE	PIXEL_MULTIPLY	RESERVED	RESERVED_1
								RESERVED_2
								DISPLAY_ROTATION_180
								RESERVED_3
								RESERVED_4
								RESERVED_5
								TILED_SURFACE
								RESERVED_6
								RESERVED_7
								S3D_FORCE_DISPLAY_A_BOTTOM

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	DISPLAY_PLANE_A_PRIMARY_A_ENABLE: When this bit is set, the primary plane will generate pixels for display. When set to zero, display plane A memory fetches cease and display is blanked (from this plane) at the next VBLANK event from the pipe that display A is assigned. The display pipe must be enabled to enable this plane. There is an override for the enable of this plane in the Pipe Configuration register. 1 = Enable 0 = Disable
30	0b RW	DISPLAY_A_GAMMA_ENABLE: This bit should only be changed after the plane has been disabled. It controls the bypassing of the display pipe gamma unit for this display plane s pixel data only. For 8-bit indexed display data, this bit should be set to a one. 0 = Display A pixel data bypasses the display pipe gamma correction logic (default). 1 = Display A pixel data is gamma corrected in the display pipe gamma correction logic.
29:26	0b RW	DISPLAY_A_SOURCE_PIXEL_FORMAT: These bits should only be changed after the plane has been disabled. Pixel formats with an alpha channel (8:8:8:8) should not use source keying. Pixel format of 8-bit indexed uses the palette. Before entering the blender, each source format is converted to 10 bits per pixel (details are described in the intermediate precision for the blender section of the Display Functions chapter). 000x = Reserved. 0010 = 8-bpp Indexed. 0011 = Reserved. 0100 = Reserved. 0101 = 16-bit BGRX (5:6:5:0) pixel format (XGA compatible). 0110 = 32-bit BGRX (8:8:8:8) pixel format. Ignore alpha. 0111 = 32-bit BGRA (8:8:8:8) pixel format. (with pre-multiplied alpha color format) 1000 = 32-bit RGBX (10:10:10:2) pixel format. Ignore alpha. 1001 = 32-bit RGBA (10:10:10:2) pixel format. (with pre-multiplied alpha color format) 1010 = 32-bit BGRX (10:10:10:2) pixel format Ignore alpha 1011 = 32-bit BGRA (10:10:10:2) pixel format (with pre-multiplied alpha color format) 1100 = 64-bit RGBX (16:16:16:16) 16 bit floating point pixel format. Ignore alpha. 1101 = 64-bit RGBA (16:16:16:16) 16-bit floating point pixel format (with pre-multiplied color format) 1110 = 32-bit RGBX (8:8:8:8) pixel format. Ignore alpha. 1111 = 32-bit RGBA (8:8:8:8) pixel format (with pre-multiplied color format)
25:24	0b RO	PIPE_SELECT: Plane A always ties to Pipe A. AccessType: Read Only Reserved



Bit Range	Default & Access	Field Name (ID): Description
23	0b RW	KEY_WINDOW_ENABLE: . This bit applies only to devices with a display plane C. This bit is set to one when the color key is used as a destination key for display C. Display plane C must be enabled on the same pipe and its Z-order should be programmed to be behind display A for this to be set to a one. 0 = Source Key applies to entire display plane A 1 = Source Key applies to only pixels within the intersection between Display A and Display C [DevBLC] and [DevCTG]: Reserved
22	0b RW	KEY_ENABLE: . This bit enables source keying for display A. Source keying allows a plane that is behind (below) this plane to show through where the display A key matches the display A data. This function is overloaded to provide display C destination keying when combined with the key window enable bit. Setting this bit is not allowed when the display pixel format includes an alpha channel. 0 = Source key is disabled 1 = Source key is enabled [DevBLC] and [DevCTG]: Reserved In destination keying, primary plane pixel will be made transparent when blending with sprite pixel as the destination if the primary src key matches with the primary pixel value.
21:20	0b RW	PIXEL_MULTIPLY: This cause the display plane to duplicate lines and pixels sent to the assigned pipe. In the pixel multiply mode, the horizontal pixels are doubled and lines are sent twice. Asynchronous flips are not used in this mode. Programming Notes: Asynchronous flips are not permitted when pixel multiply is enabled. 00 = No duplication 01 = Line/pixel Doubling 10 = Reserved 11 = Pixel Doubling only
19	0b RW	RESERVED: Software must preserve the contents of this bit.
18	0b RW	RESERVED_1: Write as zero
17:16	0b RW	RESERVED_2: Software must preserve the contents of this bit.
15	0b RW	_180DISPLAY_ROTATION: This mode causes the display plane to be rotated 180 . In addition to setting this bit, software must also set the base address to the lower right corner of the unrotated image. [DevCL] Do not enable 180 rotation together with Frame Buffer Compression 0 = No rotation 1 = 180 rotation
14	0b RW	RESERVED_3: [DevBW, DevCL, DevCDV]: [DevBLC] and [DevCTG] Display A Trickle Feed Enable: 0 = Trickle Feed Enabled - Display A data requests are sent whenever there is space in the Display Data Buffer. 1 = Trickle Feed Disabled - Display A data requests are sent in bursts. Note: On mobile products this bit will be ignored such that Trickle Feed is always disabled. [DevELK] Must always be programmed disabled
13	0b RW	RESERVED_4: [DevBW, DevCL, DevCDV]: [DevBLC] and [DevCTG] Display A Data Buffer Partitioning Control: 0 = Display A Data Buffer will encompass Sprite A buffer space when Sprite A is disabled. 1 = Display A Data Buffer will not use Sprite A buffer space when Sprite A is disabled. Note: When in C3xR Max FIFO mode, this bit will be ignored.
12:11	0b RW	RESERVED_5: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
10	0b RW	TILED_SURFACE: . This bit indicates that the display A surface data is in tiled memory. The tile pitch is specified in bytes in the DSPASTRIDE register. Only X tiling is supported for display surfaces. When this bit is set, it affects the hardware interpretation of the DSPATILEOFF, DSPALINOFF, and DSPASURF registers. 0 = Display A surface uses linear memory 1 = Display A surface uses X-tiled memory
9	0b RW	RESERVED_6: [DevBW, DevCL, DevCDV] Write as zero [DevBLC, DevCTG] Asynchronous Surface Address Update Enable: This bit will enable asynchronous updates of the surface address when written by MMIO. The surface address will change with the next TLB request or when start of vertical blank is reached. Updates during vertical blank may not complete until after the first few active lines are displayed. Restrictions: No command streamer initiated surface address updates are allowed when this bit is enabled. Only one asynchronous update may be made per frame. Must wait for vertical blank before again writing the surface address register. 0 = DSPASURF MMIO writes will update synchronous to start of vertical blank (default) 1 = DSPASURF MMIO writes will update asynchronously
8:1	0b RW	RESERVED_7: Write as zero
0	0b RW	S3D_FORCE_DISPLAY_A_BOTTOM: This bit will force the display A plane to be on the bottom of any sprite planes in the Z order. 0 = Display A Z-order is determined by the other control bits in pipe A 1 = Display A is forced to be on the bottom of any sprite planes in Z-order in pipe A

14.11.212 DSPALINOFF—Offset 70184h

Display A Linear Offset Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70184h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DISPLAY_A_OFFSET



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	DISPLAY_A_OFFSET: This register provides the panning offset into the display A plane. This value is added to the surface address to get the graphics address of the first pixel to be displayed. This offset must be at least pixel aligned. This offset is the difference between the address of the upper left pixel to be displayed and the display surface address. When performing 180 rotation, this offset must be the difference between the last pixel of the last line of the display data in its unrotated orientation and the display surface address.

14.11.213 DSPASTRIDE—Offset 70188h

Display A Stride Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70188h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR **LSB Reference:** [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DISPLAY_A_STRIDE								RSVD0

Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RW	DISPLAY_A_STRIDE: This is the stride for display A in bytes. When using linear memory, this must be 64 byte aligned. When using tiled memory, this must be 512 byte aligned. This value is used to determine the line to line increment for the display. This register is updated either through a command packet passed through the command stream or writes to this register. When it is desired to update both this and the start register, the stride register must be written first because the write to the start register is the trigger that causes the update of both registers on the next VBLANK event. When using tiled memory, the actual memory buffer stride is limited to a maximum of 16K bytes. [DevBW, DevCL, DevCDV] The display stride must be power of 2 when doing Async Flips. [DevBW, DevCL, DevCDV] The display stride must be 8KB or greater when doing Async Flips together with 180 rotation. The value in this register is updated through the command streamer during a synchronous flip.
5:0	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	DISPLAY_A_SURFACE_BASE_ADDRESS: . This address specifies the surface base address. When the surface is tiled, panning is specified using (x, y) offsets in the DSPATILEOFF register. When the surface is in linear memory, panning is specified using a linear offset in the DSPALINOFF register. This address must be 4K aligned. When performing asynchronous flips and the display surface is in tiled memory, this address must be 256K aligned. This register can be written directly through software or by command packets in the command stream. It represents an offset from the graphics memory aperture base and is mapped to physical pages through the global GTT. [DevBW] and [DevCL]: This address must be 128K aligned for linear memory.
11:4	0b RW	RESERVED: Reserved.
3	0b RW	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All
2	0b RW	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register.
1:0	0b RW	RESERVED_1: MBZ

14.11.217 DSPATILEOFF—Offset 701A4h

Display A Tiled Offset Register


Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 701A4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h



Bit Range	Default & Access	Field Name (ID): Description
31:28	0b RW	RESERVED: Write as zero
27:16	0b RW	PLANE_START_Y_POSITION: These 12 bits specify the vertical position in lines of the beginning of the active display plane relative to the display surface. When performing 180 rotation, this field specifies the vertical position of the lower right corner relative to the start of the active display plane in the unrotated orientation.
15:12	0b RW	RESERVED_1: Write as zero
11:0	0b RW	PLANE_START_X_POSITION: These 12 bits specify the horizontal offset in pixels of the beginning of the active display plane relative to the display surface. When performing 180 rotation, this field specifies the horizontal position of the lower right corner relative to the start of the active display plane in the unrotated orientation. [DevBW, DevCL, DevCDV] When display stride is 16KB and doing Asynch Flips, do not program the offset to give pans of 7680 to 8191 bytes.

Display A Live Surface Base Address Register [DevCTG-B, DevCDV]

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 701ACh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DISPLAY_A_LIVE_SURFACE_BASE_ADDRESS								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RO	DISPLAY_A_LIVE_SURFACE_BASE_ADDRESS: . This gives the live value of the surface base address as being currently used for the plane.

14.11.219 CBR1—Offset 70400h

Chicken Bit Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [GTTMMADR_LSB + 180000h] + 70400h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PND_DEADLINE_CALCULATION_DISABLE	VGA_OOO_QUEUE_DEPTH			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
S0IX_PWM_BACKLIGHT_CLOCK_MUX_SELECT	HPD_PORT_D_49_95MS_TIME_FLAG_BYPASS			ELPIN_409_SELECT	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
GM DEGLITCH_EMUL_MODE	HPD_PORT_C_49_95MS_TIME_FLAG_BYPASS			HPD_INPUT_ENABLE	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	HPD_PORT_B_49_95MS_TIME_FLAG_BYPASS			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	RESERVED			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	ELPIN_409_SELECT			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	HPD_INPUT_ENABLE			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	CR12_WRITE_COUNTER_RESET			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	RESERVED_2			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	MONITOR_DETECTION			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	INVERT_DPO_FIELD			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	RESERVED_3			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	HPD_TEST_MODE			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	SDVOC_SELECT			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	SDVOB_SELECT			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	VGA_STALL			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	RESERVED_4			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	PIXEL_SIZE			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	IMMEDIATE_ASYNCHRONOUS_FLIPS			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	PIPE_B_FRAME_START_POSITION			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	PIPE_B_PALETTE_WRITE_ENABLE			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	PIPE_A_PALETTE_WRITE_ENABLE			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	VRD_FONT_FIFO_REQUEST_DELAY_ENABLE			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	PIPE_A_FRAME_START_POSITION			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	RESERVED_6			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	PLLB_SAFE_SHUTDOWN_OVERRIDE			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE
	PLLA_SAFE_SHUTDOWN_OVERRIDE			CR12_WRITE_COUNTER_RESET	SDVOC_SELECT	IMMEDIATE_ASYNCHRONOUS_FLIPS	PIPE_A_FRAME_START_POSITION	PLLB_SAFE_SHUTDOWN_OVERRIDE



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	PND_DEADLINE_CALCULATION_DISABLE: 1 = PND deadline scheme is disabled. Latency deadline calculation is based on the pre-programmed watermark level and the 2-bit FIFO status region. 0 = PND deadline scheme is enabled. Latency deadline calculation is based on actual FIFO level
30	0b RW	S0IX_PWM_BACKLIGHT_CLOCK_MUX_SELECT: This bit is used to select the new pwm backlight control during s0ix mode 0 = select s0ix pwm backlight control based on 25 MHz oscillator clock (default) 1 = select normal pwm backlight control based on hrawclk Programming note: This bit is programmed to select either 200MHz refclk from CCK or 25MHz refclk from XTAL. This bit cannot be changed on the fly.
29	0b RW	GM_DEGLITCH_EMUL_MODE: GM deglitch emulation mode
28:26	0b RW	VGA_OOO_QUEUE_DEPTH: 0xx = Disable out-of-order stall logic for VGA 100 = Enable out-of-order VGA stall depth of 64 101 = Enable out-of-order VGA stall depth of 48 110 = Enable out-of-order VGA stall depth of 32 111 = Enable out-of-order VGA stall depth of 16
25	0b RW	HPD_PORT_D_49_95MS_TIME_FLAG_BYPASS: bypass 49_95ms time flag in Port D Not Used
24	0b RW	HPD_PORT_C_49_95MS_TIME_FLAG_BYPASS: bypass 49_95ms time flag in Port C Programming note: VLV uses HPD deglitch time as 50us. For glitches between 50us and 250us during hot plug event, driver may see multiple hpd interrupts, driver shall either service them or ignore them.
23	0b RW	HPD_PORT_B_49_95MS_TIME_FLAG_BYPASS: bypass 49_95ms time flag in Port B Programming note: VLV uses HPD deglitch time as 50us. For glitches between 50us and 250us during hot plug event, driver may see multiple hpd interrupts, driver shall either service them or ignore them.
22	0b RW	RESERVED: Reserved.
21	0b RW	ELPIN_409_SELECT: This bit is used to select one of the elpin 409 bug fixes 0 = vrd_ci_rreq 1 = count comparator
20	0b RW	HPD_INPUT_PIN_DISABLE (HPD_INPUT_ENABLE): [DevVLVP]: this bit is used to disable HPD detection in the Display core from using HPD input pin pin 0 = HPD Input pin is enabled to detect HPD detection by Display core (default) 1 = HPD input is pin is disabled to detect HPD detection by Display core
19	0b RW	CR12_WRITE_COUNTER_RESET: 0 = Disable CR12 write counter reset 1 = Enable CR12 write counter reset
18	0b RW	RESERVED_2: Reserved.
17	0b RW	MONITOR_DETECTION: This bit is used to test the monitor detection. Do not program unless directed.
16	0b RW	INVERT_DPO_FIELD: Invert DPO interlaced field output. This bit is used to invert the field sense input to the planes from DPO.
15	0b RW	RESERVED_3: Reserved.
14	0b RW	HPD_TEST_MODE: load programmable value for filter and long pulse value of HPD register 0x70408.
13	0b RW	SDVOC_SELECT: sdvoc deglitch logic output select
12	0b RW	SDVOB_SELECT: sdvob deglitch logic output select



Bit Range	Default & Access	Field Name (ID): Description
11	0b RW	VGA_STALL: Stall native mode VGA when frequency is over 50 MHz. This bit is only used during VGA native mode.
10	0b RW	RESERVED_4: to prevent async flip failures.
9	0b RW	PIXEL_SIZE: This bit changes the VGA pixel width and height calculations.
8	0b RW	IMMEDIATE_ASYNCHRONOUS_FLIPS: This bit causes asynchronous flips to complete immediately upon the start of the vertical blank period. When enabling this feature, frame start should also be moved to the end of the vertical blank period by setting the frame start position bit.
7	0b RW	PIPE_B_FRAME_START_POSITION: This bit changes the position of frame start on pipe B. This feature is used in conjunction with the immediate asynchronous flips bit to enable fast asynchronous flips during vertical blanking. 0 = frame start occurs at start of the vertical blank period 1 = frame start occurs at end of the vertical blank period Default: 1, causing frame start to occur at the end of vertical blank
6	0b RW	PIPE_B_PALETTE_WRITE_ENABLE: Disables anti-collision logic in the palette during non-blanking periods on pipe B.
5	0b RW	PIPE_A_PALETTE_WRITE_ENABLE: Disables anti-collision logic in the palette during non-blanking periods on pipe A
4	0b RW	VRD_FONT_FIFO_REQUEST_DELAY_ENABLE: This bit enable VRD font read request delay in VGA mode
3	0b RW	PIPE_A_FRAME_START_POSITION: This bit changes the position of frame start on pipe A. This feature is used in conjunction with the immediate asynchronous flips bit to enable fast asynchronous flips during vertical blanking. 0 = frame start occurs at start of the vertical blank period 1 = frame start occurs at end of the vertical blank period Default: 1, causing frame start to occur at the end of vertical blank
2	0b RW	RESERVED_6: Reserved.
1	0b RW	PLL_B_SAFE_SHUTDOWN_OVERRIDE: This bit disables the dependency for pipe B to be disabled before the PLL is shut down
0	0b RW	PLLA_SAFE_SHUTDOWN_OVERRIDE: This bit disables the dependency for pipe A to be disabled before the PLL is shut down

14.11.220 CBR2—Offset 70404h

Chicken2 Bit Register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70404h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0				

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	DPRDDB_VGAENRST_DIS: Enable rise and fall detection of DPRvgadis for DDB reset (dprddb_vgaenrst_dis)
30:28	0b RW	RESERVED: Reserved.
27	0b RW	DCN_447625: : - x8 support for hybrid gfx, Kwasi requested (dpr_dpio_x8_conc_sel)
26	0b RW	DPIOMBUNIT: ignoring EDP logic when enabling Lanes by the dptc_otxoenb [DevVLVP]: Reserved
25	0b RW	DPSSEL_OVERRIDE: when this chicken bit is set override the selects to 0 (dpsel_override) timeslice_sync_rst_b = DPRVGAdis mrchicken2_Q[25]
24	0b RW	DITHERING_ENHANCE_DISABLE: Anh need for dithering enhance (dithering_enhance_disable)
23	0b RW	EDGE: edgeA/Bvblank, edgeDPSA/Bvblank, curA/Bedgevblank,
22	0b RW	DPRAUDM_EARLY_HDE_DISABLE: Chicken bit to Audio unit to disable early RAM FIFO read in 2-channel mode (DPRAUDM_early_hde_disable)
21	0b RW	DPLRUNIT: Selects cdclk for pwm logic, pwm logic, uses hrawclk by default (select cdclk in scan mode or by setting a chicken bit) [DevVLVP]: Reserved
20	0b RW	DPRAUDM_CKGATE_PKTCTRL_IDLE_DIS: Chicken bit to disable audclk gating when pktcontrol FSM is idle (DPRAUDM_ckgate_pktctrl_idle_dis)
19	0b RW	DPR_DPIO_PORTOFF_NOT_HBLK_CHICKEN: This bit is needed to qualify the port off with hblank to take care of fragmented audio packet sent off. When chicken bit is enabled, the port off is dependent upon state of hblank, else the legacy behavior rules (dpr_dpio_portoff_not_hblk_chicken)
18	0b RW	MMIO_WRITE_EVENT: 0: mmio_write_event = RMDecPipeSLC_pre 1: mmio_write_event = 1'b0
17	0b RW	DBLATEN_ARMED_CURA_B: Dblaten_armed_curA/B



Bit Range	Default & Access	Field Name (ID): Description
16	0b RW	HPD_INTR_FIX: Freezes hpd_intr_fix, hpd_intr_fix, hpd_intr_fix
15	0b RW	RESERVED_1: Reserved.
14	0b RW	PORT_B_LANES_READY_IGNORE: 1: Lanes considered as ready for normal operation 0: usual operation: Lanes readiness indications arrived from DPIO SEG outputs [DevVLVP]: Reserved
13	0b RW	PORT_C_LANES_READY_IGNORE: 1: Lanes considered as ready for normal operation 0: usual operation: Lanes readiness indications arrived from DPIO SEG outputs [DevVLVP]: Reserved
12	0b RW	DPLLS_OK_IGNORE: 1: Both mPHY DPLLs considered as OK ('1'). Lanes can be enabled. 0: usual operation: DPLL readiness indications arrived from DPIO SEG outputs [DevVLVP]: Reserved
11	0b RW	DPR_DPS_NOA_SCALEEN: This bit is to enable viewing critical control signals that were added as a result of Cantiga B0 Overlay changes. Default = 0. (dpr_dps_noa_scaleen) 0: Non-scaling signals are sent to NOA bus 1: Scaling signals are sent to the NOA bus
10	0b RW	DPR_VS_AFLIPTOTAL_CHICKEN: This chicken bit bypasses the current logic used for calculating the number of requests to make for an asynchronous flip. It will be helpful because the current logic is very difficult to validate. (dpr_vs_afliptotal_chicken)
9	0b RW	DPR_VS_BYTEEN_CHICKEN: This chicken bit bypasses the current logic used for selecting the proper byte enables. It is intended to address byte enables during asynchronous flips, but it was easier to bypass the entire byte-enable circuit instead. HSD bug #1932963. (dpr_vs_byteen_chicken)
8	0b RW	DPR_VS_AFLIPADDR_CHICKEN: This chicken bit bypasses the current logic used for selecting the starting fetch address of an asynchronous flip. HSD bug #1932964. (dpr_vs_aflipaddr_chicken)
7:6	0b RW	DPRDDB_SYNC_SELECT: When set vsync reset is asserted and when clear no reset is asserted. (dprddb_novsyncreset) This selects between VRVSYNC and hi-res VSYCN when set with dprvrd_novsyncreset also set sync_select novsyncreset. (dprddb_sync_select) X0 = No Vsync reset 01 = VGA vsync or hi-res between Nat and UL mode 11 = VGA vsync reset in both UL and native
5	0b RW	DDBMUNIT: C0 ECO1 chicken bit defaulted to fix enable
4	0b RW	HDCPUNIT: EGLK A5 ECO1 Fix. Read Data Fix For RMBus Protocol. vsmunit: Lock Up Issue.
3:2	0b RW	DPRVGA_DPBSTALL_UL_THRESHOLD: VGATEST2 issue fix, Stall throttling done during horiz_blank and UL mode is asserted. (DPRVGA_dpbstall_ul_threshold). 01: DPB to VGA stall during UL mode
1	0b RW	DPRAUDM_SAMPLE_PRESENT_DISABLE: When set this bit will disable the sample present bits being set in layout 1 mode of Audio. Default is to enable sample present on Audio. (DPRAUDM_sample_present_disable) vsmunit: FBC/SR Power Fix
0	0b RW	RESERVED_2: [DevVLVP] MBZ. This bit si the same as bit 31 in 70450h rega_loadcount_crtdetect

14.11.221 CCBR—Offset 70408h

ChickenCount Bit Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70408h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
HPD_AND_CRT_DETECT_TEST_MODES								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	HPD_AND_CRT_DETECT_TEST_MODES: HPD and CRT detect test mode

14.11.222 CBR3—Offset 7040Ch

Chicken3 Bit Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7040Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
3:2	0b RW	AUXC_GMBUS_CONNECTION: Selectes gmbus connection for AUXC [DevVLVP]: Reserved
1:0	0b RW	AUXB_GMBUS_CONNECTION: Selectes gmbus connection for AUXB [DevVLVP]: Reserved

14.11.223 SWF00—Offset 70410h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 70410h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_ : for Video BIOS and Drivers

14.11.224 SWF01—Offset 70414h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70414h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

14.11.225 SWF02—Offset 70418h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70418h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_ : for Video BIOS and Drivers

14.11.226 SWF03—Offset 7041Ch

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7041Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_ : for Video BIOS and Drivers

14.11.235 SWF0C—Offset 70440h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70440h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_ : for Video BIOS and Drivers

14.11.236 SWF0D—Offset 70444h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70444h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

	31	28				24				20				16				12				8				4				0				
	0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0
	RESERVED																																	



Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_: for Video BIOS and Drivers

14.11.239 CBR4—Offset 70450h

Display Chicken Bits 4 ;

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 70450h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
REGA_LOADCOUNT_CRTDETECT	HPD_TEST_MODE	RESERVED	FLIP_MSA_VERTICAL_TOTAL_IN_INTERLACE_MODE	DRPO_DPT_FIELD_INVERT	CRC_DOUBLEBUFFER_DISABLE	HPD_GLITCH_REMOVAL_COUNT_VALUE_SELECTION	SDVO_RX_FIX	LVDS_LEGACY_WRITE_PROTECTION
				PCH_FIELD_ID_FIX	RESERVED_1			
						DAC_DOUBLE_LINEARITY_REGISTER		
							DAC_DBL_LIN_RED_CHANNEL_COUNTER_SOURCE_SELECT	
							DAC_DBL_LIN_BLUE_CHANNEL_COUNTER_SOURCE_SELECT	
							DAC_DBL_LIN_GREEN_CHANNEL_COUNTER_SOURCE_SELECT	
							DAC_DBL_LIN_COUNTER_2_OVERRIDE_SELECT	
							DAC_DBL_LIN_RGB_DAC_DFT_MODE_ENABLE	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	REGA_LOADCOUNT_CRTDETECT: Project: All Format: Load initial value to crt detect counter
30	0b RW	HPD_TEST_MODE: Project: All Default Value: 0b Load programmable value for filter and long pulse value of HPD Value Name Description Project 0b Short Pulse Short Pulse All 1b Long Pulse Long Pulse All
29	0b RW	RESERVED: Project: All Format: PBC



Bit Range	Default & Access	Field Name (ID): Description
28	0b RW	FLIP_MSA_VERTICAL_TOTAL_IN_INTERLACE_MODE: Project: All Format: Set to 1 to flip MSA vtotal
27	0b RW	DRPO_DPT_FIELD_INVERT: Project: All Format: Invert interlaced field ID output from dptunit.
26	0b RW	CRC_DOUBLEBUFFER_DISABLE: Project: All Format: Disable doublebuffering on CRCs so enable/disable and source select will happen immediately.
25	0b RW	HPD_GLITCH_REMOVAL_COUNT_VALUE_SELECTION: Project: All Default Value: 0b Value Name Description Project 0b 500us 500us glitch removal All 1b 50us 50us glitch removal All
24:21	0b RW	SDVO_RX_FIX: Project: All Format: Program SDVO receiver fix values [DevVLVP]: Reserved
20	0b RW	LVDS_LEGACY_WRITE_PROTECTION: Project: All Format: [DevVLVP]: Reserved
19	0b RW	PCH_FIELD_ID_FIX: Project: All Format: 1: CPU and PCH field IDs are independent 0: CPU field ID is tied to PCH field ID [DevVLVP]: Reserved
18:16	0b RW	RESERVED_1: Project: All Format: MBZ
15:8	0b RW	DAC_DOUBLE_LINEARTY_REGISTER: Project: All Format: Project: DevIBX-B Value Name Description Project 00b Disable Normal RGB operation, no test mode enabled All 01b Counter 1 Counter 1 All 10b Inverse Counter 1 Inverse of counter 1 All 11b Counter 2 Counter 2 All
7:6	0b RW	DAC_DBL_LIN_RED_CHANNEL_COUNTER_SOURCE_SELECT: Project: DevIBX-B Default Value: 00b DefaultVaueDesc BitFieldDesc Value Name Description Project 00b Disable Normal RGB operation, no test mode enabled All 01b Counter 1 Counter 1 All 10b Inverse Counter 1 Inverse of Counter 1 All 11b Counter 2 Counter 2 All Programming Notes Notes Errata Description Project # Desc All
5:4	0b RW	DAC_DBL_LIN_BLUE_CHANNEL_COUNTER_SOURCE_SELECT: Project: DevIBX-B Default Value: 00b Value Name Description Project 00b Disable Normal RGB operation, no test mode enabled All 01b Counter 1 Counter 1 All 10b Inverse Counter 1 Inverse of counter 1 All 11b Counter 2 Counter 2 All
3:2	0b RW	DAC_DBL_LIN_GREEN_CHANNEL_COUNTER_SOURCE_SELECT: Project: DevIBX-B Default Value: 00b Value Name Description Project 00b Disable Normal RGB operation, no test mode enabled All 01b Counter 1 Counter 1 All 10b Inverse Counter 1 Inverse of counter 1 All 11b Counter 2 Counter 2 All



14.11.241 PIPEB_SLC—Offset 71004h

Pipe B Display Scan Line Range Compare Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71004h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
INCLUSIVE_EXCLUSIVE	RESERVED	START_SCAN_LINE_NUMBER				RESERVED_1	END_SCAN_LINE_NUMBER	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	INCLUSIVE_EXCLUSIVE: 1 = Inclusive Within Range, 0 = Exclusive Out of Range
30:29	0b RW	RESERVED: Read only.
28:16	0b RW	START_SCAN_LINE_NUMBER: [DevBLC, DevCTG, DevCDV] This field specifies the starting scan line number of the Scan Line Window. Format = U16 in scan lines, where scan line 0 is the first line of the display frame. Range = [0, Display Buffer height in lines-1]. [DevBW] and [DevCL] End Scan Line Number: This field specifies the ending scan line number of the Scan Line Window. Format = U16 in scan lines, where scan line 0 is the first line of the display frame. Range = [0, Display Buffer height in lines-1].
15:13	0b RW	RESERVED_1: Read only.
12:0	0b RW	END_SCAN_LINE_NUMBER: [DevBLC, DevCTG, DevCDV] This field specifies the ending scan line number of the Scan Line Window. Format = U16 in scan lines, where scan line 0 is the first line of the display frame. Range = [0, Display Buffer height in lines-1]. [DevBW] and [DevCL] Start Scan Line Number: This field specifies the starting scan line number of the Scan Line Window. Format = U16 in scan lines, where scan line 0 is the first line of the display frame. Range = [0, Display Buffer height in lines-1].



14.11.242 PIPEBCONF—Offset 71008h

Pipe B Configuration Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71008h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PIPE_B_ENABLE	PIPE_STATE	RESERVED	FRAME_START_DELAY	DISPLAY_PORT_AUDIO_ONLY_MODE	FORCE_BORDER	PIPE_B_GAMMA_UNIT_MODE	INTERLACED_MODE	MIPI_DISPLAY_SELF_REFRESH_MODE_FOR_MIPI_B
								DISPLAY_OVERLAY_PLANES_OFF
								CURSOR_PLANES_OFF
								REFRESH_RATE_CXSR_MODE_ASSOCIATION
								COLOR_CORRECTION_MATRIX_ENABLE_ON_PIPE_B
								DISPLAYPORT_POWER_MODE_SWITCH_DEVLVP
								COLOR_RANGE_SELECT
								S3D_SPRITE_ORDER
								S3D_SPRITE_INTERLEAVING_FORMAT
								RESERVED_1
								BITS_PER_COLOR
								DITHERING_ENABLE
								DITHERING_TYPE
								DDA_RESET_TEST_MODE
								RESERVED_2

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	PIPE_B_ENABLE: Setting this bit to the value of one, turns on pipe B. This must be done before any planes are enabled on this pipe. Changing it to a zero should only be done when all planes that are assigned to this pipe have been disabled. Turning the pipe enable bit off disables the timing generator in this pipe. Plane disable occurs after the next VBLANK event after the plane is disabled. Synchronization pulses to the display are not maintained if the timing generator is disabled. Power consumption will be at its lowest state when disabled. A separate bit controls the DPLL enable for this pipe. Pipe timing registers should contain valid values before this bit is enabled. Disabling the Pipe and changing the timing registers and re-enabling the pipe before the next VBLANK will cause the mode change to occur at the end of the current frame. This requires no wait on the software s part. On the other hand, if this is the disabling of the pipe, that does require a software wait for VBLANK to occur. Synchronization pulses to the display are not maintained if the timing generator is disabled. Power consumption is at it s lowest state. 1 = Enable 0 = Disable
30	0b RO	PIPE_STATE: This bit indicates the actual state of the pipe. Since there can be some delay between disabling the pipe and the pipe actually shutting off, this bit indicates the true current state of the pipe. 0 = Disabled 1 = Enabled AccessType: Read Only



Bit Range	Default & Access	Field Name (ID): Description
29	0b RW	RESERVED: Write as zero.
28:27	0b RW	FRAME_START_DELAY: Used to delay the frame start signal that is sent to the display planes. Normal operation uses the default 00 value and test modes can use the delayed frame start to shorten the test time. This would be set to 00 for normal operation. 00 = Frame Start occurs on the first HBLANK after the start of VBLANK 01 = Frame Start occurs on the second HBLANK after the start of VBLANK 10 = Frame Start occurs on the third HBLANK after the start of VBLANK 11 = Frame Start occurs on the forth HBLANK after the start of VBLANK
26	0b RW	DISPLAY_PORT_AUDIO_ONLY_MODE: [DevVLVP] Setting this bit to 1 indicates the DisplayPort will output audio only. 0 = DisplayPort will output Video or Video and Audio 1 = DisplayPort will output Audio only
25	0b RW	FORCE_BORDER: : (TEST MODE)0 = Normal Operation 1 = Color information is ignored and border color is substituted during active region
24	0b RW	PIPE_B_GAMMA_UNIT_MODE: . This bit selects which mode the pipe gamma correction logic works in. In the palette mode, it behaves as a 3X256x8 RAM lookup. VGA and indexed mode operation should use the palette in 8-bit mode. In the 10-bit gamma mode, it will act as a piecewise linear interpolation. Other gamma units such as in the overlay and sprite are unaffected by this bit.0 = 8-bit Palette Mode 1 = 10-bit Gamma Mode
23:21	0b RW	INTERLACED_MODE: These bits are used for software control of interlaced behavior. They are updated immediately if the pipe is off, or in the vertical blank after programming if pipe is enabled. 0xx = Progressive 100 = Interlaced embedded panel using programmable vertical sync shift (2x) 101 = Interlaced using vertical sync shift. Backup option to setting 110. (2x) 110 = Interlaced with VSYNC/HSYNC Field Indication using legacy vertical sync shift. Used for SDVO. 111 = Interlaced with Field 0 Only using legacy vertical sync shift. Not used. Note: VGA display modes, sDVO line stall, and Panel fitting do not work while in interlaced modes Setting the Interlaced embedded panel mode causes hardware to automatically modify the output to match the specifications of panels that support interlaced mode.
20	0b RW	MIPI_DISPLAY_SELF_REFRESH_MODE_FOR_MIPI_B: .0 = Normal Operation, display controller generate timing and refresh display panel at refresh rate 1 = Display self-refresh mode. Display controller update frame buffer in display module on demand only
19	0b RW	DISPLAY_OVERLAY_PLANES_OFF: . This bit when set will cause all enabled Display and overlay planes that are assigned to this pipe to be disabled by overriding the current setting of the plane enable bit, at the next VBLANK. Timing signals continue as they were but the screen becomes blank. Setting the bit back to a zero will then allow the display and overlay planes to resume on the following VBLANK.0 = Normal Operation 1 = Planes assigned to this pipe are disabled.
18	0b RW	CURSOR_PLANES_OFF: . This bit when set will cause all enabled cursor planes that are assigned to this pipe to be disabled by overriding the current setting of the plane enable bit, at the next VBLANK. Timing signals continue as they were but the screen becomes blank. Setting the bit back to a zero will then allow the cursor planes to resume on the following VBLANK. 0 = Normal Operation 1 = Planes assigned to this pipe are disabled.



Bit Range	Default & Access	Field Name (ID): Description
17:16	0b RW	REFRESH_RATE_CXSR_MODE_ASSOCIATION: These bits select how refresh rates are tied to CxSR on pipe B. When they are set to anything other than 00, bits 23:21 of this register must be programmed to 0xx. Switching between 01 and 10 settings directly is not allowed. Software must program this field to 00 before switching. Software is responsible for enabling this mode only for integrated display panels that support corresponding mode. 00 Default no dynamic refresh rate change enabled. Software control only. 01 Progressive-to-progressive refresh rate change enabled and tied to CxSR. Pixel clock values set in FPB0/FPB1 settings in the DPLL control register and FPB0/FPB1 divider registers. 10 Progressive-to-interlaced refresh rate change enabled and tied to CxSR. Pixel clock value does not change in this case. Scaling must be disabled in this mode. Uses programmable VS shift 11 Reserved
15	0b RW	COLOR_CORRECTION_MATRIX_ENABLE_ON_PIPE_B: 1 = Color Correction Coefficients are enabled to perform color correction 0 = Color Correction Coefficients are disabled
14	0b RW	DISPLAYPORT_POWER_MODE_SWITCH_DEVVLVP: This bit selects the software controlled progressive to progressive power saving mode (software controlled DRRS). Hardware Controlled Refresh Rate Select must be disabled when enabling this. Link and data M/N 1 values are used for normal settings, M/N 2 values are used for low power settings. 0 Normal progressive refresh rate (default) 1 Low Power progressive refresh rate
13	0b RW	COLOR_RANGE_SELECT: [DevVLVP]: This bit is used to select the color range of RGB outputs. 0 = Apply full 0-255 color range to the output (Default) 1 = Apply 16-235 color range to the output
12	0b RW	S3D_SPRITE_ORDER: This bit controls the blending order of the sprite planes for S3D support: 0 = Sprite C first. The first line or pixel comes from Sprite C (default) 1 = Sprite D first. The first line or pixel comes from Sprite D
11:10	0b RW	S3D_SPRITE_INTERLEAVING_FORMAT: These bits control the Sprite C/D interleaving format in S3D mode 00 = No interleaving 01 = Line interleaving 10 = Pixel interleaving 11 = Reserved
9:8	0b RW	RESERVED_1: [DevCDV, DevVLVP] MBZ Scrambling enable [DevCTG]: This bit enables scrambling for DisplayPort. Software must set this bit appropriately when enabling a DisplayPort output. 00 = Scrambling disabled (Default) 01 = Scrambling enabled, no SR after initialization at loop 2 of training 10 - RESERVED 11 = Scrambling and SR enabled. Scrambling is reset every 512 BS symbols.
7:5	0b RW	BITS_PER_COLOR: [DevCTG, DevCDV, DevVLVP]: This field selects the number of bits per color sent to a receiver device connected to this port. Color format takes place on the Vblank after being written. Color format change can be done independent of a pixel clock change. Selecting a pixel color depth higher or lower than the pixel color depth of the frame buffer results in dithering the output stream. For further details on Display Port fixed frequency programming to accommodate these formats refer to DP Frequency Programming in DPLL section of Bspec. 000 = 8 bits per color (Default) 001 = 10 bits per color 010 = 6 bits per color 011 = RESERVED 1xx = RESERVED
4	0b RW	DITHERING_ENABLE: [DevCTG, DevCDV]: This bit enables dithering for DisplayPort 6bpc or 8bpc modes 0 Dithering disabled (Default) 1 Dithering enabled Programming Note: Dithering should only be enabled for 8bpc or 6bpc.

14.11.246 PIPEBSTAT—Offset 71024h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				MAX_BLUE_GAMMA_CORRECTION_POINT				

Bit Range	Default & Access	Field Name (ID): Description
31:17	0b RW	RESERVED: Reserved.
16:0	100000000 00000000b RW	MAX_BLUE_GAMMA_CORRECTION_POINT: . 129th reference point for blue channel of the pipe piecewise linear gamma correction. The value should always be programmed to be less than or equal to 1024.0.Format: 11.6 Default: 0x10000

14.11.246 PIPEBSTAT—Offset 71024h

Pipe B Status

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71024h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h




31	0	PIPE_B_UNDERFLOW_STATUS
	0	SPRITE_D_FLIP_DONE_INTERRUPT_ENABLE
	0	CRC_ERROR_ENABLE
	0	CRC_DONE_ENABLE
28	0	PERFORMANCE_COUNTER2_INTERRUPT_ENABLE
	0	PLANE_B_FLIP_DONE_INTERRUPT_ENABLE
	0	VERTICAL_SYNC_INTERRUPT_ENABLE
	0	DISPLAY_LINE_COMPARE_ENABLE
	0	BLM_EVENT_ENABLE
	0	SPRITE_C_FLIP_DONE_INTERRUPT_ENABLE
	0	ODD_FIELD_INTERRUPT_EVENT_ENABLE
	0	EVEN_FIELD_INTERRUPT_EVENT_ENABLE
20	0	PANEL_SELF_REFRESH_PSR_INTERRUPT_ENABLE_ON_PIPE_B
	0	START_OF_VERTICAL_BLANK_INTERRUPT_ENABLE
	0	PIPE_B_FRAMESTART_INTERRUPT_ENABLE
	0	PIPE_B_HORIZONTAL_BLANK_INTERRUPT_ENABLE
16	0	SPRITE_D_FLIP_DONE_INTERRUPT_STATUS
	0	SPRITE_C_FLIP_DONE_INTERRUPT_STATUS
	0	CRC_ERROR_STATUS
	0	CRC_DONE_INTERRUPT_STATUS
12	0	SECOND_PERFORMANCE_COUNTER2_INTERRUPT_STATUS
	0	PLANE_B_FLIP_DONE_INTERRUPT_STATUS
	0	PIPE_B_VERTICAL_SYNC_STATUS
	0	PIPE_B_DISPLAY_LINE_COMPARE_STATUS
8	0	BLM_IMAGE_BRIGHTNESS_STATUS
	0	RESERVED
	0	ODD_FIELD_INTERRUPT_STATUS
4	0	EVEN_FIELD_INTERRUPT_STATUS
	0	PIPE_B_PANEL_SELF_REFRESH_STATUS
	0	START_OF_VERTICAL_BLANK_INTERRUPT_STATUS
	0	PIPE_B_FRAMESTART_INTERRUPT_STATUS
0	0	PIPE_B_HORIZONTAL_BLANK_STATUS

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/1C	PIPE_B_UNDERFLOW_STATUS: This bit is set when an underflow occurs at the display pipe B. It is cleared by writing a one to this bit. This event will occur naturally during mode changes, to be effective, it should be cleared after a mode change. This bit is only valid after Pipe B has been completely configured. 1 = FIFO B Underflow occurred 0 = FIFO B Underflow did not occur AccessType: One to Clear
30	0b RW	SPRITE_D_FLIP_DONE_INTERRUPT_ENABLE: This will enable the consideration of the Sprite D flip done interrupt status bit in the first line interrupt logic 0 = Sprite D Flip Done Interrupt Disabled 1 = Sprite D Flip Done Interrupt Enabled
29	0b RW	CRC_ERROR_ENABLE: This will enable the consideration of the CRC error status bit in the first line interrupt/status logic. 0 = CRC Error Detect Disabled 1 = CRC Error Detect Enabled
28	0b RW	CRC_DONE_ENABLE: This will enable the consideration of the CRC done status bit in the first line interrupt/status logic. 0 = CRC Done Detect Disabled 1 = CRC Done Detect Enabled
27	0b RW	PERFORMANCE_COUNTER2_INTERRUPT_ENABLE: This bit enables the second performance counter interrupt. 0 = Second Performance Counter2 Interrupt Status Disabled 1 = Second Performance Counter2 interrupt Status Enabled
26	0b RW	PLANE_B_FLIP_DONE_INTERRUPT_ENABLE: This will enable the consideration of the Plane B flip done interrupt status bit in the first line interrupt logic 0 = Plane B flip done Interrupt/Status Disabled 1 = Plane B flip done Interrupt/Status Enabled
25	0b RW	VERTICAL_SYNC_INTERRUPT_ENABLE: 0 = Vertical Sync Interrupt/Status Disabled 1 = Vertical Sync Interrupt/Status Enabled



Bit Range	Default & Access	Field Name (ID): Description
24	0b RW	DISPLAY_LINE_COMPARE_ENABLE: 0 = Pipe B Display Line Compare Status Report Disabled 1 = Pipe B Display Line Compare Status report Enabled
23	0b RW	BLM_EVENT_ENABLE: [DevCL, DevCTG, DevCDV]: This interrupt is generated by the image brightness segment comparators. Which segment cause an interrupt are controlled by the BLM Histogram control register. 0 = No BLM event enabled 1 = BLM event enabled
22	0b RW	SPRITE_C_FLIP_DONE_INTERRUPT_ENABLE: This will enable the consideration of the Sprite C flip done interrupt status bit in the first line interrupt logic 0 = Sprite C Flip Done Interrupt Disabled 1 = Sprite C Flip Done Interrupt Enabled
21	0b RW	ODD_FIELD_INTERRUPT_EVENT_ENABLE: . This bit should only be used when this pipe is in an interlaced display timing.0 = Odd Field Event disable 1 = Odd Field Event enable
20	0b RW	EVEN_FIELD_INTERRUPT_EVENT_ENABLE: . This bit should only be used when this pipe is in an interlaced display timing.0 = Even field Event disable 1 = Even field Event enable
19	0b RW	PANEL_SELF_REFRESH_PSR_INTERRUPT_ENABLE_ON_PIPE_B: 0 = PSR interrupt Disabled on Pipe B 1 = PSR Interrupt Enabled on Pipe B
18	0b RW	START_OF_VERTICAL_BLANK_INTERRUPT_ENABLE: This will enable the consideration of the start of vertical blank interrupt status bit in the first line interrupt/status logic. 0 = Start of Vertical Blank Interrupt/Status Disabled 1 = Start of Vertical Blank Interrupt/Status Enabled
17	0b RW	PIPE_B_FRAMESTART_INTERRUPT_ENABLE: This will enable the consideration of the vertical blank interrupt status bit in the first line interrupt/status logic. 0 = Pipe B Framestart Interrupt/Status Disabled 1 = Pipe B Framestart Interrupt/Status Enabled
16	0b RW	PIPE_B_HORIZONTAL_BLANK_INTERRUPT_ENABLE: : This will enable the consideration of the start of horizontal blank interrupt status bit in the first line interrupt/status logic0 = Start of Horizontal Blank Interrupt/Status Disabled 1 = Start of Horizontal Blank Interrupt/Status Enabled
15	0b RW/1C	SPRITE_D_FLIP_DONE_INTERRUPT_STATUS: MMIO Flip Event is completed on Sprite D 0 = Sprite D Flip Not Done 1 = Sprite D Flip Done AccessType: One to Clear
14	0b RW/1C	SPRITE_C_FLIP_DONE_INTERRUPT_STATUS: MMIO Flip Event is completed on Sprite C 0 = Sprite C Flip Not Done 1 = Sprite C Flip Done AccessType: One to Clear
13	0b RW/1C	CRC_ERROR_STATUS: This bit is set when a Pipe B CRC error is detected. It is cleared by a write of a one. 0 = No CRC Error 1 = CRC Error detected AccessType: One to Clear
12	0b RW/1C	CRC_DONE_INTERRUPT_STATUS: This bit is set when Pipe B CRC calculation and compare are complete. It is cleared by a write of a one. 0 = CRC Not Done 1 = CRC Done AccessType: One to Clear



Bit Range	Default & Access	Field Name (ID): Description
11	0b RW/1C	SECOND_PERFORMANCE_COUNTER2_INTERRUPT_STATUS: This bit is set when the second performance counter2 generates an interrupt. It is cleared by a write of a one. 0 = Second performance counter interrupt event not asserted 1 = Second performance counter interrupt event asserted AccessType: One to Clear
10	0b RW/1C	PLANE_B_FLIP_DONE_INTERRUPT_STATUS: Async/Sync Flip Event is completed on Display Plane B 0 = Plane B Flip Not Done 1 = Plane B Flip Done AccessType: One to Clear
9	0b RW/1C	PIPE_B_VERTICAL_SYNC_STATUS: 0 = Vertical Sync not asserted 1 = Vertical Sync asserted AccessType: One to Clear
8	0b RW/1C	PIPE_B_DISPLAY_LINE_COMPARE_STATUS: This bit is cleared when a write to this register occurs with this bit as a one. Writes with this bit as a zero has no effect on the value of the bit. 0 = Display Line Compare Status not asserted 1 = Display Line Compare Status asserted AccessType: One to Clear
7	0b RW/1C	BLM_IMAGE_BRIGHTNESS_STATUS: [DevCL, DevCTG, DevCDV]: This bit is cleared when a write to this register occurs with this bit as a one. Writes with this bit as a zero has no effect on the value of the bit. 0 = DPST Interrupt has not occurred on pipe B 1 = DPST Interrupt has occurred on pipe B AccessType: One to Clear
6	0b RW	RESERVED: MBZ
5	0b RW/1C	ODD_FIELD_INTERRUPT_STATUS: . This status bit will be set on a Odd field VBLANK event. This bit should only be used when this pipe is in an interlaced display timing. For synchronization with register updates, the actual event will occur one line after the start of VBLANK. To use this bit in a polling manner, clear the bit by writing a one to it followed by the polling loop waiting for it to become set.Note: This bit will not be set when pipe is in Interlaced with Field 0 Only using legacy vertical sync shift mode. 0 = Odd Field Vertical Blank has not occurred 1 = Odd Field Vertical Blank has occurred AccessType: One to Clear
4	0b RW/1C	EVEN_FIELD_INTERRUPT_STATUS: . This status bit will be set on a even filed VBLANK event. This bit should only be used when this pipe is in an interlaced display timing. For synchronization with register updates, the actual event will occur one line after the start of VBLANK. To use this bit in a polling manner, clear the bit by writing a one to it followed by the polling loop waiting for it to become set.Note: This bit will not be set when pipe is in Interlaced with Field 0 Only using legacy vertical sync shift mode. 0 = Even Field Vertical Blank has not occurred 1 = Even Field Vertical Blank has occurred AccessType: One to Clear
3	0b RW/1C	PIPE_B_PANEL_SELF_REFRESH_STATUS: This bit indicates interrupt is generated by the PSR controller and intends to send interrupt to SW driver when the PSR interrupt enable bit (70028h bit 22) is set. This is cleared when a write to this register occurs with this bit as a one. Write with this bit as a zero has no effect on the value of the bit. 0 = PSR Interrupt has not occurred on pipe B 1 = PSR interrupt has occurred on pipe B AccessType: One to Clear
2	0b RW/1C	START_OF_VERTICAL_BLANK_INTERRUPT_STATUS: This status bit will be set at the beginning of a VBLANK event. At this point, the double buffered display registers flip, taking their new values. To use this bit in a polling manner, clear the bit by writing a one to it followed by the polling loop waiting for it to become set. In MIPI DSR mode, GPIO TE trigger sets the Vblank Interrupt status 0 = Start of Vertical Blank has not occurred 1 = Start of Vertical Blank has occurred AccessType: One to Clear



Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	DISPLAY_B_START_ADDRESS_BITS: This register provides the start address of the display B plane or the first eye when running in stereo mode. This address must be at least pixel aligned. This register can be written directly through software or by command packets in the command stream. It represents an offset from the graphics memory aperture base and is mapped to physical pages through the global GTT. This address must be 4K aligned. When performing asynchronous flips and the display surface is in tiled memory, this address must be 256K aligned. This register can be written directly through software or by command packets in the command stream. It represents an offset from the graphics memory aperture base and is mapped to physical pages through the global GTT. If the device supports trusted operation and this plane is not marked trusted, the memory pages must not be marked NoDMA . Write to this register triggers async flip The async flip address is written into the Display B Base Address register 0x7119C
11:4	0b RW	RESERVED_MBZ: Reserved.
3	0b RW	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All
2	0b RW	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register.
1:0	0b RW	RESERVED_MBZ_1: Reserved.

14.11.251 DSPBCNTR—Offset 71180h

Display B/Sprite Plane Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 71180h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h


Default: 01000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	DISPLAY_B_SPRITE_PRIMARY_B_ENABLE: This bit will enable or disable the display B/sprite. When this bit is set, the plane will generate pixels for display. When set to zero, memory fetches cease and display is blanked (from this plane) at the next VBLANK event from the pipe that this plane is assigned. At least one of the display pipes must be enabled to enable this plane. There is an override for the enable of this plane in the Pipe Configuration register. 1 = Enable 0 = Disable
30	0b RW	DISPLAY_B_SPRITE_GAMMA_ENABLE: This bit should only be changed after the plane has been disabled. It controls the bypassing of the display pipe gamma unit for this display plane pixel data only. For 8-bit indexed display data, this bit should be set to a one. 0 = Display B pixel data bypasses the pipe gamma correction logic (default). 1 = Display B pixel data is gamma corrected in the pipe gamma correction logic



Bit Range	Default & Access	Field Name (ID): Description
29:26	0b RW	DISPLAY_B_SOURCE_PIXEL_FORMAT: This field selects the pixel format for the sprite/display B. Pixel formats with an alpha channel (8:8:8:8) should not use source keying. Before entering the blender, each source format is converted to 10 bits per pixel (details are described in the intermediate precision for the blender section of the Display Functions chapter). 000x = Reserved. 0010 = 8-bpp Indexed. 0011 = Reserved. 0100 = Reserved. 0101 = 16-bit BGRX (5:6:5:0) pixel format (XGA compatible). 0110 = 32-bit BGRX (8:8:8:8) pixel format. Ignore alpha. 0111 = 32-bit BGRA (8:8:8:8) pixel format. (with pre-multiplied alpha color format) 1000 = 32-bit RGBX (10:10:10:2) pixel format. Ignore alpha. 1001 = 32-bit RGBA (10:10:10:2) pixel format. (with pre-multiplied alpha color format) 1010 = 32-bit BGRX (10:10:10:2) pixel format Ignore alpha 1011 = 32-bit BGRA (10:10:10:2) pixel format (with pre-multiplied alpha color format) 1100 = 64-bit RGBX (16:16:16:16) 16 bit floating point pixel format. Ignore alpha. 1101 = 64-bit RGBA (16:16:16:16) 16-bit floating point pixel format (with pre-multiplied color format) 1110 = 32-bit RGBX (8:8:8:8) pixel format. Ignore alpha. 1111 = 32-bit RGBA (8:8:8:8) pixel format (with pre-multiplied color format)
25:24	01b RO	PIPE_SELECT: Plane B always ties to Pipe B. Reserved AccessType: Read Only
23	0b RW	KEY_WINDOW_ENABLE: This applies only to devices with a Display Plane C. It determines what area of the screen the source key compare should be applied. This bit is set to one when the color key is used as a destination key for display C. Display plane C must be enabled on the same pipe and display A should not be enabled on this pipe for this to be used. The function is only effective when display C is enabled and defined by Z-order to be behind display B. 0 = If keying is enabled, it applies to the entire display B plane 1 = If keying is enabled, it applies only to the intersection between display B and display C [DevBLC] and [DevCTG]: Reserved
22	0b RW	SOURCE_KEY_ENABLE: When used as a sprite or a secondary this enables source color keying. Sprite pixel values that match the key will become transparent. Source keying allows a plane that is behind (below) this plane to show through where the display B data matches the display B key. This function is overloaded to provide display C destination keying when combined with the key window enable bit.. Setting this bit is not allowed when the display pixel format includes an alpha channel. 0 = Sprite source key is disabled (default) 1 = Sprite source key is enabled. [DevBLC] and [DevCTG]: Reserved In destination keying, primary plane pixel will be made transparent when blending with sprite pixel as the destination if the primary src key matches with the primary pixel value.
21:20	0b RW	PIXEL_MULTIPLY: This cause the display plane to duplicate lines and pixels sent to the assigned pipe. In the line/pixel doubling mode, the horizontal pixels are doubled and lines are sent twice. Asynchronous flips are not used in this mode. Programming Notes: Asynchronous flips are not permitted when pixel multiply is enabled. 00 = No duplication 01 = Line/pixel Doubling 10 = Reserved 11 = Pixel Doubling only
19:16	0b RW	RESERVED: Write as zero
15	0b RW	_180DISPLAY_ROTATION: This mode causes the display plane to be rotated 180 . In addition to setting this bit, software must also set the base address to the lower right corner of the unrotated image. [DevCL] Do not enable 180 rotation together with Frame Buffer Compression 0 = No rotation 1 = 180 rotation



Bit Range	Default & Access	Field Name (ID): Description
14	0b RW	RESERVED_1: [DevBW, DevCL, DevCDV] [DevBLC, DevCTG] Display B Trickle Feed Enable: 0 = Trickle Feed Enabled - Display B data requests are sent whenever there is space in the Display Data Buffer. 1 = Trickle Feed Disabled - Display B data requests are sent in bursts. Note: On mobile products this bit will be ignored such that Trickle Feed is always disabled. [DevELK] Must always be programmed disabled
13	0b RW	RESERVED_2: [DevBW, DevCL, DevCDV] [DevBLC, DevCTG] Display B Data Buffer Partitioning Control: 0 = Display B Data Buffer will encompass Sprite B buffer space when Sprite B is disabled. 1 = Display B Data Buffer will not use Sprite B buffer space when Sprite B is disabled. Note: When in C3xR Max FIFO mode, this bit will be ignored.
12:11	0b RW	RESERVED_3: Reserved.
10	0b RW	TILED_SURFACE: This bit indicates that the display B surface data is in tiled memory. The tile pitch is specified in bytes in the DSPBSTRIDE register. Only X tiling is supported for display surfaces. When this bit is set, it affects the hardware interpretation of the DSPBLINOFF, DSPBTILEOFF, and DSPBSURF registers. 0 = Display B surface uses linear memory 1 = Display B surface uses X-tiled memory
9	0b RW	RESERVED_4: [DevBW, DevCL, DevCDV] Write as zero [DevBLC, DevCTG] Asynchronous Surface Address Update Enable: This bit will enable asynchronous updates of the surface address when written by MMIO. The surface address will change with the next TLB request or when start of vertical blank is reached. Updates during vertical blank may not complete until after the first few active lines are displayed. Restrictions: No command streamer initiated surface address updates are allowed when this bit is enabled. Only one asynchronous update may be made per frame. Must wait for vertical blank before again writing the surface address register. 0 = DSPBSURF MMIO writes will update synchronous to start of vertical blank (default) 1 = DSPBSURF MMIO writes will update asynchronously
8:1	0b RW	RESERVED_5: Write as zero
0	0b RW	S3D_FORCE_DISPLAY_B_BOTTOM: This bit will force the display B plane to be on the bottom of any sprite planes in the Z order. 0 = Display B Z-order is determined by the other control bits in pipe B 1 = Display B is forced to be on the bottom of any sprite planes in Z-order in pipe B

14.11.252 DSPBLINOFFSET—Offset 71184h

Display B/Sprite Linear Offset Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71184h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.11.255 DSPBKEYMSK—Offset 71198h

Sprite Color Key Mask Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71198h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
RESERVED				RED_MASK_VALUE				GREEN_MASK_VALUE				BLUE_MASK_VALUE			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: reserved
23:16	0b RW	RED_MASK_VALUE: Specifies the color key mask for the sprite red/Cr channel.
15:8	0b RW	GREEN_MASK_VALUE: Specifies the color key mask for the sprite green/Y channel.
7:0	0b RW	BLUE_MASK_VALUE: Specifies the color key mask for the sprite blue/Cb channel.

14.11.256 DSPBSURF—Offset 7119Ch

Display B Surface Address Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7119Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DISPLAY_B_SURFACE_BASE_ADDRESS						RESERVED_MBZ	FLIP_SOURCE	DECRIPTION_REQUEST
								RESERVED_MBZ_1

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	DISPLAY_B_SURFACE_BASE_ADDRESS: This address specifies the surface base address. When the surface is tiled, panning is specified using (x, y) offsets in the DSPBTILEOFF register. When the surface is in linear memory, panning is specified using a linear offset in the DSPBLINOFF register. This address must be 4K aligned. When performing asynchronous flips and the display surface is in tiled memory, this address must be 256K aligned. This register can be written directly through software or by command packets in the command stream. It represents an offset from the graphics memory aperture base and is mapped to physical pages through the global GTT. [DevBW] and [DevCL]: This address must be 128K aligned for linear memory.
11:4	0b RW	RESERVED_MBZ: Reserved.
3	0b RW	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All



Bit Range	Default & Access	Field Name (ID): Description
2	0b RW	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register.
1:0	0b RW	RESERVED_MBZ_1: Reserved.

14.11.257 DSPBTILEOFF—Offset 711A4h

Display B Tiled Offset Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 711A4h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h


31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RESERVED		PLANE_START_Y_POSITION				RESERVED_1		PLANE_START_X_POSITION	

Bit Range	Default & Access	Field Name (ID): Description
31:28	0b RW	RESERVED: Write as zero
27:16	0b RW	PLANE_START_Y_POSITION: These 12 bits specify the vertical position in lines of the beginning of the active display plane relative to the display surface. When performing 180 rotation, this field specifies the vertical position of the lower right corner relative to the start of the active display plane in the unrotated orientation.
15:12	0b RW	RESERVED_1: Write as zero



31	28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
VGA_DISPLAY_DISABLE				RESERVED				VGA_BORDER_ENABLE				VGA_CENTERING_ENABLE				VGA_PALETTE_READ_SELECT				VGA_PALETTE_A_WRITE_DISABLE				DUAL_PIPE_VGA_PALETTE_B_WRITE_DISABLE				LEGACY_VGA_8_BIT_PALETTE_ENABLE				PALETTE_BYPASS_TEST_MODE				NINE_DOT_DISABLE				RESERVED				RESERVED_1																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
VGA_POP_UP_2X_CENTERED_MODE_SCALING								VGA_PIPE_SELECT				VGA_PALETTE_READ_SELECT				VGA_PALETTE_A_WRITE_DISABLE				DUAL_PIPE_VGA_PALETTE_B_WRITE_DISABLE				LEGACY_VGA_8_BIT_PALETTE_ENABLE				PALETTE_BYPASS_TEST_MODE				NINE_DOT_DISABLE				RESERVED																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
BLINK_DUTY_CYCLE				VSYNC_BLINK_RATE				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED				RESERVED			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	VGA_DISPLAY_DISABLE: This bit will disable the VGA compatible display mode. It has no effect on VGA register or A0000-BFFFF memory aperture accesses which are controlled by the PCI configuration and VGA register settings. VGA display should only be enabled if all display planes other than VGA are disabled. After enabling the VGA, most display planes need to stay disabled, only the VGA popup (cursor A) can be enabled. The VGA display is never trusted. No secrets are allowed in the pre-allocated memory and VGA is limited to access only that memory. During trusted operation (when registers are locked via Lock), this bit will always act as if it was set to a one (disabled VGA display). VGA 132 Column text mode is not supported. 0 = VGA Display Enabled 1 = VGA Display Disabled
30	0b RW	VGA_POP_UP_2X_CENTERED_MODE_SCALING: When this bit is set to a one, the VGA and pop-up data is scaled using pixel doubling in both the horizontal and vertical direction for use on un-scaled flat panel displays. Setting this bit allows the VGA to run at higher dot clock frequencies and creates a larger (4x the size) image for better quality on larger displays. It is intended for use in one of the centering modes when not using the internal panel fitting. Do not use it for native VGA modes or when internal panel fitting is used to scale VGA. In the situations where it is used, for 1280 wide or larger panels this bit should be set. For exactly 1280 wide panels, the Nine-dot disable bit should also be set. This operation is in addition to the VGA functions that double the pixels and lines. 0 = VGA display is normal size 1 = VGA and VGA popup data is doubled in the horizontal and vertical direction.
29	0b RW	VGA_PIPE_SELECT: This bit only applies to devices with dual pipe support. For devices with a single display pipe, this bit will be ignored. For dual pipe devices, this bit determines which pipe is to receive the VGA display data. This must be changed only when the VGA display is in the disabled state via the VGA display disable bit or during the write to enable VGA display. 0 = Selects Assigns the VGA display to Pipe A 1 = Selects Assigns the VGA display to Pipe B
28:27	0b RW	RESERVED_: Software must preserve the contents of these bits.



Bit Range	Default & Access	Field Name (ID): Description
26	0b RW	VGA_BORDER_ENABLE: This bit determines if the VGA border areas during VGA centering modes are included in the active display area and do or do not appear on integrated TV encoder output and devices that use centering such as on DVO connected flat panel, TV displays, or integrated panels. For use with the internal panel fitting logic, the border if enabled will be scaled along with the pixel data. Setting this bit allows the popup to be positioned overlapping the border area of the image. 0 = VGA Border areas are not included in the image size calculations for centering only active area. 1 = VGA Border areas are enabled and is passed to the display pipe for display and used in the image size calculation for centering modes
25:24	0b RW	VGA_CENTERING_ENABLE: VGA centering modes use the pipe timing generators to determine the actual display timings. This would normally correspond to the display panel size and timings. The VGA registers determine the centered VGA image height and width. The VGA border may or may not be considered in the calculation selected by the VGA Border Enable bit. For a proper image, the VGA image size should not exceed the pipe timing generator active rectangle. When using the internal panel fitting logic, the horizontal image size needs to be less than or equal to 2048 pixels to generate a proper image. The VGA image will either be centered within the pipe timing rectangle or appear in the upper left corner. Upper left corner centered mode is generally used for external panel scaling where the DVO stall signal is used and is always used for internal panel fitting operation. When panel fitter is enabled on the same pipe as VGA this register setting is ignored and upper left corner centered mode is always selected. When centering is disabled, the VGA CRTC registers determine the display timing compatible with legacy VGA devices for driving CRT like devices. 00 = VGA centering is disabled, VGA operates in Native VGA mode or when driving integrated TV 01 = VGA centering is enabled, VGA image appears in the center of the larger rectangle 10 = VGA centering is enabled, VGA image appears in the upper left corner of the larger rectangle 11 = VGA centering is enabled, VGA image appears in the upper left corner of the larger rectangle
23	0b RW	VGA_PALETTE_READ_SELECT: This bit only applies to dual display pipe devices and determines which palette VGA palette read accesses will occur from. 0 = VGA palette reads will access Palette A (default). 1 = VGA palette reads will access Palette B VGA palette reads are reads from I/O address 0x3c9.
22	0b RW	VGA_PALETTE_A_WRITE_DISABLE: This determines which palette the VGA palette writes will have as a destination. One or both palettes can be the destination. If both are disabled, writes will not affect the palette RAM contents. 0 = VGA palette writes will update Palette A (default). 1 = VGA palette writes will not update Palette A VGA palette writes are writes to I/O address 0x3C9h.
21	0b RW	DUAL_PIPE_VGA_PALETTE_B_WRITE_DISABLE: This determines which palette the VGA palette writes will have as a destination. One or both palettes can be the destination. If both are disabled, writes will not affect the palette RAM contents. 0 = VGA palette writes will update Palette B (default). 1 = VGA palette writes will not update Palette B VGA palette writes are writes to I/O address 0x3C9h.
20	0b RW	LEGACY_VGA_8_BIT_PALETTE_ENABLE: This bit only affects reads and writes to the palette through VGA I/O addresses. In the 6-bit mode, the 8-bits of data are shifted up two bits on the write (upper two bits are lost) and shifted two bits down on the read. It provides backward compatibility for original VGA programs (in it s default state) as well as VESA VBE support for 8-bit palette. It does not affect palette accesses through the palette register MMIO path. 0 = 6-bit DAC (default). 1 = 8-bit DAC.
19	0b RW	PALETTE_BYPASS_TEST_MODE: 0 = Pass VGA data through the palette for translation (Normal Operation) 1 = Bypass the palette for allowing testing without loading palette both VGA and popup data will bypass the palette in this mode.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	NINE_DOT_DISABLE: Prevents DOS applications from setting the VGA display into a real 9-dot per character operation mode, instead the device emulates that using 8-dots per character. This is intended to provide VGA compatibility on DVI type connectors and integrated panels where there would otherwise not be room for the 720 horizontal pixels or 1440 pixels when horizontally doubled. The VGA register bit SR01(0) functionality is disabled. VGA panning control handles the pseudo 9-dot mode when both this bit is set and SR01(0) is clear. 0 = Enable use of 9-dot enable bit in VGA registers 1 = Ignore the 9-dot per character bit and always use 8
17	0b RW	RESERVED: Reserved.
16:8	0b RW	RESERVED__1: Software must preserve the contents of these bits.
7:6	0b RW	BLINK_DUTY_CYCLE: Controls the VGA text mode blink duty cycle relative to the cursor blink duty cycle. 00 = 100% Duty Cycle, Full Cursor Rate (Default) 01 = 25% Duty Cycle, Cursor Rate 10 = 50% Duty Cycle, Cursor Rate 11 = 75% Duty Cycle, Cursor Rate
5:0	0b RW	VSYNC_BLINK_RATE: Controls the VGA blink rate in terms of the number of VSYNCs per on/off cycle. These bits are programmed with the (VSYNCs/cycle)/2-1. The proper programming of this register is determined by the VSYNC rate that the display requires when in a VGA display mode.

14.11.261 SWF10—Offset 71410h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71410h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

RESERVED

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_: for Video BIOS and Drivers

14.11.262 SWF11—Offset 71414h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 71414h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_ : for Video BIOS and Drivers

14.11.263 SWF12—Offset 71418h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71418h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_ : for Video BIOS and Drivers



14.11.264 SWF13—Offset 7141Ch

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7141Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0b RW	RESERVED_: for Video BIOS and Drivers						

14.11.265 SWF14—Offset 71420h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71420h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0b RW	RESERVED_: for Video BIOS and Drivers						



14.11.268 SWF17—Offset 7142Ch

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7142Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0b RW	RESERVED_: for Video BIOS and Drivers						

14.11.269 SWF18—Offset 71430h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71430h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0b RW	RESERVED_: for Video BIOS and Drivers						



14.11.272 SWF1B—Offset 7143Ch

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7143Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0b RW	RESERVED_: for Video BIOS and Drivers						

14.11.273 SWF1C—Offset 71440h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71440h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0b RW	RESERVED_: for Video BIOS and Drivers						

14.11.274 SWF1D—Offset 71444h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 71444h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_ : for Video BIOS and Drivers

14.11.275 SWF1E—Offset 71448h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 71448h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_ : for Video BIOS and Drivers



14.11.276 SWF1F—Offset 7144Ch

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7144Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0b RW	RESERVED_: for Video BIOS and Drivers						

14.11.277 SPACNTR—Offset 72180h

Sprite A Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72180h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SPRITE_A_ENABLE	SPRITE_A_GAMMA_ENABLE	SPRITE_A_SOURCE_PIXEL_FORMAT	SPRITE_A_PIPE_SELECT	RESERVED	SPRITE_SOURCE_KEY_ENABLE	PIXEL_MULTIPLY	COLOR_CONVERSION_DISABLED	YUV_FORMAT
							YUV_BYTE_ORDER	_180DISPLAY_ROTATION
					RESERVED_1		TILED_SURFACE	
						RESERVED_2		SPRITE_A_BOTTOM
								RESERVED_3
								SPRITE_A_Z_ORDER



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	SPRITE_A_ENABLE: This bit will enable or disable the Sprite A. When this bit is set, the plane will generate pixels for display to be combined by the blender for the target pipe. When set to zero, memory fetches cease and display is blanked (from this plane) at the next VBLANK event from the pipe that this plane is assigned. At least one of the display pipes must be enabled to enable this plane. There is an override for the enable of this plane in the Pipe Configuration register. This bit only has an effect when the plane is not trusted. When the plane is marked trusted, this bit will be overridden and the display disabled when the registers are unlocked. 1 = Enable 0 = Disable
30	0b RW	SPRITE_A_GAMMA_ENABLE: There are two gamma adjustments possible in the Sprite A data path. This bit controls the gamma correction in the display pipe not the gamma control in this plane. It affects only the pixel data from this display plane. For pixel format of 8-bit indexed, this bit should be set to a one. Gamma correction logic that is contained in the Sprite A logic is disabled by loading the default values into those registers. When this plane is marked as trusted, this bit should always be set to zero to force the pipe gamma to be always be bypassed. 0 = Sprite A pixel data bypasses the display pipe gamma correction logic (default). 1 = Sprite A pixel data is gamma corrected in the pipe gamma correction logic
29:26	0b RW	SPRITE_A_SOURCE_PIXEL_FORMAT: This field selects the pixel format for the sprite/Sprite A. Pixel formats with an alpha channel should not use source keying. Before entering the blender, each source format is converted to 10 bits per pixel (details are described in the intermediate precision for the blender section of the Display Functions chapter). 0000 = YUV 4:2:2 packed (see byte order below). 0001 = Reserved. 0010 = 8-bpp Indexed. 0011 = Reserved. 0100 = Reserved. 0101 = 16-bit BGRX (5:6:5:0) pixel format (XGA compatible). 0110 = 32-bit BGRX (8:8:8:8) pixel format. Ignore alpha. 0111 = 32-bit BGRA (8:8:8:8) pixel format with pre-multiplied alpha channel. 1000 = 32-bit RGBX (10:10:10:2) pixel format. Ignore alpha. 1001 = 32-bit RGBA (10:10:10:2) pixel format 1010 = Reserved. 1011 = Reserved. 1100 = Reserved. 1101 = Reserved. 1110 = 32-bit RGBX (8:8:8:8) pixel format. Ignore alpha. 1111 = 32-bit RGBA (8:8:8:8)
25:24	0b RW	SPRITE_A_PIPE_SELECT: Sprite A always ties to pipe A. Reserved.
23	0b RW	RESERVED: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22	0b RW	SPRITE_SOURCE_KEY_ENABLE: When used as a sprite in the 16/32-bpp modes without alpha this enables source color keying. Sprite pixel values that match (within range) the key will become transparent. Setting this bit is not allowed when the Sprite A pixel format includes an alpha channel. [DevBW] Erratum: This bit must always be set to 0 when Sprite A pixel format is YUV 0 = Sprite source key is disabled (default) 1 = Sprite source key is enabled. Each sprite has built in source keying enabled/disabled. If the source keying is disabled and no alpha blending is enabled, the pixels are tagged as opaque. If sprite source keying is enabled and no alpha blending is enabled, it works as follows: For YUV sprite data, each yuv channel data is compared with the corresponding channel's key color Low and High (each channel inrange can be masked out). If all three channels are in range between the low and high key values, it is considered source compared. For RGB sprite data, each 24-bit RGB pixel data is compared with the 24-bit key value (note it only uses the 24-bit Low key value for comparison). Each 24-bit has to be equal (each bit comparison can also be masked out) for the source compared. If the sprite source data compare and matches, then the sprite data will be tagged as transparent when blending with its destination pixel. If the sprite source data does not compare, then the sprite data will be tagged as opaque when blending with its destination pixel.
21:20	0b RW	PIXEL_MULTIPLY: This cause the display plane to duplicate lines and pixels sent to the assigned pipe. In the line/pixel doubling mode, the horizontal pixels are doubled and lines are sent twice. This is a method of scaling the source image by two (both H and V). 00 = No line/Pixel duplication 01 = Line/Pixel Doubling 10 = Line Doubling only 11 = Pixel Doubling only
19	0b RW	COLOR_CONVERSION_DISABLED: This bit enables or disables the color conversion logic. Color conversion is intended to be used with the formats that support YUV formats such as the YUV 4:2:2 packed format and x:8:8:8 and 8:8:8:8 formats. Formats such as RGB5:5:5 and 5:6:5 do not have YUV versions. 0 = Pixel data is sent through the conversion logic (only applies to YUV formats) 1 = Pixel data is not sent through the YUV-)>RGB conversion logic.
18	0b RW	YUV_FORMAT: This bit specifies the source YUV format for the YUV to RGB color conversion operation. This field is ignored when source data is RGB. 0 = ITU-R Recommendation BT.601 1 = ITU-R Recommendation BT.709
17:16	0b RW	YUV_BYTE_ORDER: This field is used to select the byte order when using YUV 4:2:2 data formats. For other formats, this field is ignored. 00 = YUYV 01 = UYYV 10 = VYVU 11 = VYUY
15	0b RW	_180DISPLAY_ROTATION: This mode causes the display plane to be rotated 180 . In addition to setting this bit, software must also set the base address to the lower right corner of the unrotated image and calculate the x, y offset as relative to the lower right corner. 0 = No rotation 1 = 180 rotation
14:11	0b RW	RESERVED_1: Reserved.
10	0b RW	TILED_SURFACE: This bit indicates that the Sprite A surface data is in tiled memory. The tile pitch is specified in bytes in the DSPCSTRIDE register. Only X tiling is supported for display surfaces. When this bit is set, it affects the hardware interpretation of the DSPCTILEOFF, DSPCLINOFF, and DSPCSURFADDR registers. 0 = Sprite A surface uses linear memory 1 = Sprite A surface uses X-tiled memory
9:3	0b RW	RESERVED_2: Write as zero




Sprite A Linear Offset Register

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72184h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SPRITE_A_OFFSET								



31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
RESERVED				SPRITE_HEIGHT												RESERVED_1				SPRITE_WIDTH															

Intel Atom® Processor E3800 Product Family
Datasheet
957

14.11.283 SPAKEYMSK—Offset 72198h

Sprite A Color Key Mask Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72198h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RESERVED									RED_CHANNEL_ENABLE
									GREEN_CHANNEL_ENABLE
									BLUE_CHANNEL_ENABLE

Bit Range	Default & Access	Field Name (ID): Description
31:3	0b RW	RESERVED: Write as zero
2	0b RW	RED_CHANNEL_ENABLE: Specifies the source color key enable for the red/Cr channel.
1	0b RW	GREEN_CHANNEL_ENABLE: Specifies the source color key enable for the green/Y channel.
0	0b RW	BLUE_CHANNEL_ENABLE: Specifies the source color key enable for the blue/Cb channel

14.11.284 SPASURF—Offset 7219Ch

Sprite A Surface Address Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7219Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0			
0	0	0	0	0	0	0	0	0			
SPRITE_A_SURFACE_BASE_ADDRESS						RESERVED			FLIP_SOURCE	DECRIPTION_REQUEST	RESERVED_1

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	SPRITE_A_SURFACE_BASE_ADDRESS: This address specifies the surface base address. When the surface is tiled, panning is specified using (x, y) offsets in the DSPCTILEOFF register. When the surface is in linear memory, panning is specified using a linear offset in the DSPCLINOFF register. This address must be 4K aligned. This register can be written directly through software or by command packets in the command stream. It represents an offset from the graphics memory aperture base and is mapped to physical pages through the global GTT. If the device supports trusted operation and this plane is not marked trusted, the memory pages must not be marked NoDMA . The value in this register is updated through the command streamer during synchronous flips. [DevBW] and [DevCL]: This address must be 128K aligned for linear memory.
11:4	0b RW	RESERVED: : MBZ
3	0b RW	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All

14.11.287 SPACONTALPHA—Offset 721A8h

Sprite A Constant Alpha Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 721A8h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0			
0	0	0	0	0	0	0	0	0			
ENABLE_CONSTANT_ALPHA				RESERVED				SPRITE_A_CONSTANT_ALPHA_VALUE			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	ENABLE_CONSTANT_ALPHA: Sprite A Sprite constant alpha provides a way to apply an alpha value to all video sprite pixels. Each pixel color channel is multiplied by the constant alpha before proceeding to the blender. This can be used to create fade out effects. This is intended for CE device use where the video sprite might still be used to generate video output. 0 Sprite A Sprite Constant Alpha is disabled 1 Sprite A Sprite Constant Alpha is enabled
30:8	0b RW	RESERVED: : MBZ
7:0	0b RW	SPRITE_A_CONSTANT_ALPHA_VALUE: This field provides the alpha value when constant alpha is enabled. A value of FF means fully opaque and a value of zero means fully transparent. Values in between those values allow for a blending of sprite with other surfaces.

14.11.288 SPALIVESURF—Offset 721ACh

Sprite A Live Surface Address Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 721ACh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SPRITE_A_LIVE_SURFACE_BASE_ADDRESS						RESERVED	FLIP_SOURCE	0
							DECRIPTION_REQUEST	0
							RESERVED_1	0
								0

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RO	SPRITE_A_LIVE_SURFACE_BASE_ADDRESS: This gives the live value of the surface base address as being currently used for the Sprite A plane.
11:4	0b RO	RESERVED: : MBZ
3	0b RO	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All



Bit Range	Default & Access	Field Name (ID): Description
2	0b RO	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register. ValueNameDescriptionProject 0b Not requested Decryption not requested All 1b Requested Decryption requested All
1:0	0b RO	RESERVED_1: MBZ

14.11.289 SPACLR0—Offset 721D0h

Sprite A Color Correction 0 Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 721D0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 01000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				CONTRAST				BRIGHTNESS

Bit Range	Default & Access	Field Name (ID): Description
31:27	0b RW	RESERVED: Reserved.

14.11.290 SPACLRC1—Offset 721D4h



Bit Range	Default & Access	Field Name (ID): Description
7:0	11000000b RW	BLUE_U_CB: gamma correction mapping Blue to CB

14.11.292 SPAGAMC4—Offset 721E4h

Sprite A Gamma Correction Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 721E4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00808080h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED				RED_V_CR	GREEN_Y			BLUE_U_CB



Access Method

Offset: [GTTMMADR LSB + 180000h] + 721F0h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
RESERVED				RED_V_CR				GREEN_Y				BLUE_U_CB			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Reserved.
23:16	00010000b RW	RED_V_CR: gamma correction mapping Red to CR
15:8	00010000b RW	GREEN_Y: gamma correction mapping green to Y
7:0	00010000b RW	BLUE_U_CB: gamma correction mapping Blue to CB

14.11.296 SPAGAMC0—Offset 721F4h

Access Method

Offset: [GTTMMADR LSB + 180000h] + 721F4h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
RESERVED				RED_V_CR				GREEN_Y				BLUE_U_CB			



Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: reserved
23:16	00001000b RW	RED_V_CR: gamma correction mapping Red to CR
15:8	00001000b RW	GREEN_Y: gamma correction mapping green to Y
7:0	00001000b RW	BLUE_U_CB: gamma correction mapping Blue to CB

14.11.297 SPBCNTR—Offset 72280h

Sprite B Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72280h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SPRITE_B_ENABLE	SPRITE_B_GAMMA_ENABLE	SPRITE_B_SOURCE_PIXEL_FORMAT	SPRITE_B_PIPE_SELECT	RESERVED	SPRITE_SOURCE_KEY_ENABLE	PIXEL_MULTIPLY	COLOR_CONVERSION_DISABLED	YUV_FORMAT
								YUV_BYTE_ORDER
								_180DISPLAY_ROTATION
								RESERVED_1
								TILED_SURFACE
								RESERVED_2
								SPRITE_B_BOTTOM
								RESERVED_3
								SPRITE_B_Z_ORDER

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	SPRITE_B_ENABLE: This bit will enable or disable the Sprite B. When this bit is set, the plane will generate pixels for display to be combined by the blender for the target pipe. When set to zero, memory fetches cease and display is blanked (from this plane) at the next VBLANK event from the pipe that this plane is assigned. At least one of the display pipes must be enabled to enable this plane. There is an override for the enable of this plane in the Pipe Configuration register. This bit only has an effect when the plane is not trusted. When the plane is marked trusted, this bit will be overridden and the display disabled when the registers are unlocked. 1 = Enable 0 = Disable



Bit Range	Default & Access	Field Name (ID): Description
30	0b RW	SPRITE_B_GAMMA_ENABLE: There are two gamma adjustments possible in the Sprite B data path. This bit controls the gamma correction in the display pipe not the gamma control in this plane. It affects only the pixel data from this display plane. For pixel format of 8-bit indexed, this bit should be set to a one. Gamma correction logic that is contained in the Sprite B logic is disabled by loading the default values into those registers. When this plane is marked as trusted, this bit should always be set to zero to force the pipe gamma to be always be bypassed. 0 = Sprite B pixel data bypasses the display pipe gamma correction logic (default). 1 = Sprite B pixel data is gamma corrected in the pipe gamma correction logic
29:26	0b RW	SPRITE_B_SOURCE_PIXEL_FORMAT: This field selects the pixel format for the sprite/Sprite B. Pixel formats with an alpha channel should not use source keying. Before entering the blender, each source format is converted to 10 bits per pixel (details are described in the intermediate precision for the blender section of the Display Functions chapter). 0000 = YUV 4:2:2 packed (see byte order below). 0001 = Reserved 0010 = 8-bpp Indexed. 0011 = Reserved. 0100 = Reserved. 0101 = 16-bit BGRX (5:6:5:0) pixel format (XGA compatible). 0110 = 32-bit BGRX (8:8:8:8) pixel format. Ignore alpha. 0111 = 32-bit BGRA (8:8:8:8) pixel format with pre-multiplied alpha channel. 1000 = 32-bit RGBX (10:10:10:2) pixel format. Ignore alpha. 1001 = 32-bit RGBA (10:10:10:2) pixel format 1010 = Reserved. 1011 = Reserved. 1100 = Reserved. 1101 = Reserved. 1110 = 32-bit RGBX (8:8:8:8) pixel format. Ignore alpha. 1111 = 32-bit RGBA (8:8:8:8)
25:24	0b RW	SPRITE_B_PIPE_SELECT: Sprite B always ties to Pipe A. Reserved
23	0b RW	RESERVED: Reserved.
22	0b RW	SPRITE_SOURCE_KEY_ENABLE: When used as a sprite in the 16/32-bpp modes without alpha this enables source color keying. Sprite pixel values that match (within range) the key will become transparent. Setting this bit is not allowed when the Sprite B pixel format includes an alpha channel. [DevBW] Erratum: This bit must always be set to 0 when Sprite B pixel format is YUV 0 = Sprite source key is disabled (default) 1 = Sprite source key is enabled.
21:20	0b RW	PIXEL_MULTIPLY: This cause the display plane to duplicate lines and pixels sent to the assigned pipe. In the line/pixel doubling mode, the horizontal pixels are doubled and lines are sent twice. This is a method of scaling the source image by two (both H and V). 00 = No line/Pixel duplication 01 = Line/Pixel Doubling 10 = Line Doubling only 11 = Pixel Doubling only
19	0b RW	COLOR_CONVERSION_DISABLED: This bit enables or disables the color conversion logic. Color conversion is intended to be used with the formats that support YUV formats such as the YUV 4:2:2 packed format and x:8:8:8 and 8:8:8:8 formats. Formats such as RGB5:5:5 and 5:6:5 do not have YUV versions. 0 = Pixel data is sent through the conversion logic (only applies to YUV formats) 1 = Pixel data is not sent through the YUV-)RGB conversion logic.
18	0b RW	YUV_FORMAT: This bit specifies the source YUV format for the YUV to RGB color conversion operation. This field is ignored when source data is RGB. 0 = ITU-R Recommendation BT.601 1 = ITU-R Recommendation BT.709



Bit Range	Default & Access	Field Name (ID): Description
17:16	0b RW	YUV_BYTE_ORDER: This field is used to select the byte order when using YUV 4:2:2 data formats. For other formats, this field is ignored. 00 = YUYV 01 = UYVY 10 = YVYU 11 = VYUY
15	0b RW	_180DISPLAY_ROTATION: This mode causes the display plane to be rotated 180 . In addition to setting this bit, software must also set the base address to the lower right corner of the unrotated image and calculate the x, y offset as relative to the lower right corner. 0 = No rotation 1 = 180 rotation
14:11	0b RW	RESERVED_1: Reserved.
10	0b RW	TILED_SURFACE: This bit indicates that the Sprite B surface data is in tiled memory. The tile pitch is specified in bytes in the DSPCSTRIDE register. Only X tiling is supported for display surfaces. When this bit is set, it affects the hardware interpretation of the DSPCTILEOFF, DSPCLINOFF, and DSPCSURFADDR registers. 0 = Sprite B surface uses linear memory 1 = Sprite B surface uses X-tiled memory
9:3	0b RW	RESERVED_2: Write as zero
2	0b RW	SPRITE_B_BOTTOM: This bit will force the Sprite B plane to be on the bottom of the Z order. If the plane is marked as trusted, it only applies to the Z order of the trusted planes. 0 = Sprite B Z order is determined by the other control bits 1 = Sprite B is forced to be on the bottom of the Z order.
1	0b RW	RESERVED_3: Reserved.
0	0b RW	SPRITE_B_Z_ORDER: With Sprite A and B z-order, bottom control bits, Sprite B plane is placed in a specific z-order among other planes in pipe A. Display Pipe A Z-orders SA zorderSA bottomSB zorderSB bottomResulting Pipe Z-order (from bottom to top)Source Keying 0000PA SA SB CAPA in Black 1000PA SB SA CAPA in Black 0001SB PA SA CAuse src keying on SB 0011SB PA SA CAuse src keying on SB 1001SB SA PA CAuse src keying on SA 1011SB SA PA CAuse src keying on SA 0100SA PA SB CAuse src keying on SA 1100SA PA SB CAuse src keying on SA 0110SA SB PA CAuse src keying on SB 1110SA SB PA CAuse src keying on SB 0: Sprite B z-order is disabled 1: Sprite B z-order is enabled

14.11.301 SPBSIZE—Offset 72290h

Sprite B Height and Width Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 72290h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
RESERVED				SPRITE_HEIGHT												RESERVED_1				SPRITE_WIDTH															

Bit Range	Default & Access	Field Name (ID): Description
31:28	0b RW	RESERVED: Write as zero
27:16	0b RW	SPRITE_HEIGHT: This register field is used to specify the height of the sprite in lines. The value in the register is the height minus one. The defined sprite rectangle must always be completely contained within the displayable area of the screen image.
15:12	0b RW	RESERVED_1: Write as zero
11:0	0b RW	SPRITE_WIDTH: This register field is used to specify the width of the sprite in pixels. This does not have to be the same as the stride but should be less than or equal to the stride (converted to pixels). The value in the register is the width minus one. The defined sprite rectangle must always be completely contained within the displayable area of the screen image. The sprite width is limited to even values when YUV source pixel format is used (actual width, not the width minus one value).

14.11.302 SPBKEYMINVAL—Offset 72294h

Sprite B Color Key Min Value Register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72294h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



14.11.303 SPBKEYMSK—Offset 72298h

Access Method

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RESERVED									RED_CHANNEL_ENABLE
									GREEN_CHANNEL_ENABLE
									BLUE_CHANNEL_ENABLE

Intel Atom® Processor E3800 Product Family
Datasheet
977



Bit Range	Default & Access	Field Name (ID): Description
3	0b RW	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All
2	0b RW	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register. ValueNameDescriptionProject 0b Not requested Decryption not requested All 1b Requested Decryption requested All
1:0	0b RW	RESERVED_MBZ_1: Reserved.

14.11.305 SPBKEYMAXVAL—Offset 722A0h

Sprite B Color Key Max Value Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 722A0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h





Bit Range	Default & Access	Field Name (ID): Description
2	0b RO	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register. ValueNameDescriptionProject 0b Not requested Decryption not requested All 1b Requested Decryption requested All
1:0	0b RO	RESERVED_MBZ_1: Reserved.

14.11.309 SPBCLRC0—Offset 722D0h

Sprite B Color Correction 0 Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 722D0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 01000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	1	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED	CONTRAST			RESERVED_1			BRIGHTNESS	

Bit Range	Default & Access	Field Name (ID): Description
31:27	0b RW	RESERVED: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
26:16	0b RW	SATURATION_AND_HUE_SIN_SH_SIN: This 11-bit signed fixed-point number is in 2 s complement (s3i.7f) format with the MSB as the sign, next 3 MSBs as the integer value and the last 7 LSBs as the fraction value. This field can be used in two modes. When full range YUV data is operated on, this field contains the saturation value. When the range-limited YCbCr data is used, software should program this field with the product of the saturation multiplier value multiplied by the CbCr range scale factor (=128/112). Similar to the contrast field, there is no limit for saturation reduction saturation = 0 means all pixels become the same value. However, increasing contrast can only be increased by a factor less than 8. For example, the largest contrast with value of 0x7.7F can bring input range [0, 32] to a full display color range of [0, 255]. Bypassing Hue, even for source data in RGB format, is accomplished by programming this field to 0.0.
15:10	0b RW	RESERVED_1: Reserved.
9:0	001000000 0b RW	SATURATION_AND_HUE_COS_SH_COS: This unsigned fixed-point number is in 3i.7f format with the first 3 MSBs be the integer value and the last 7 LSBs be the fraction value. This field can be used in two modes. When full range YUV data is operated on, this field contains the saturation value. When the range-limited YCbCr data is used, software should program this field with the product of the saturation multiplier value multiplied by the CbCr range scale factor (=128/112). Similar to the contrast field, there is no limit for saturation reduction saturation = 0 means all pixels become the same value. However, increasing contrast can only be increased by a factor less than 8. For example, the largest contrast with value of 0x7.7F can bring input range [0, 32] to a full display color range of [0, 255]. Bypassing Saturation, even for source data in RGB format, is accomplished by programming this field to 1.0.

14.11.311 SPBGAMC5—Offset 722E0h

Sprite B Gamma Correction Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 722E0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00C0C0C0h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
0	0	0	0	0	0	0	0	0							
RESERVED				RED_V_CR				GREEN_Y				BLUE_U_CB			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: reserved
23:16	11000000b RW	RED_V_CR: gamma correction mapping Red to CR
15:8	11000000b RW	GREEN_Y: gamma correction mapping green to Y



Bit Range	Default & Access	Field Name (ID): Description
7:0	11000000b RW	BLUE_U_CB: gamma correction mapping Blue to CB

14.11.312 SPBGAMC4—Offset 722E4h

Sprite B Gamma Correction Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 722E4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00808080h

31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED	RESERVED	RED_V_CR	RED_V_CR	GREEN_Y	GREEN_Y	BLUE_U_CB	BLUE_U_CB	BLUE_U_CB

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: reserved
23:16	10000000b RW	RED_V_CR: gamma correction mapping Red to CR
15:8	10000000b RW	GREEN_Y: gamma correction mapping Green to Y
7:0	10000000b RW	BLUE_U_CB: gamma correction mapping CB

14.11.313 SPBGAMC3—Offset 722E8h

Sprite B Gamma Correction Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 722E8h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00404040h



Access Method

Offset: [GTTMMADR LSB + 180000h] + 722F0h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00101010h

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: reserved
23:16	00010000b RW	RED_V_CR: gamma correction mapping red to CR
15:8	00010000b RW	GREEN_Y: gamma correction mapping green to Y
7:0	00010000b RW	BLUE_U_CB: gamma correction mapping blue to CB

14.11.316 SPBGAMC0—Offset 722F4h

Access Method

Offset: [GTTMMADR LSB + 180000h] + 722F4h

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00080808h

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: reserved
23:16	00001000b RW	RED_V_CR: gamma correction mapping Red to CR
15:8	00001000b RW	GREEN_Y: gamma correction mapping green to Y
7:0	00001000b RW	BLUE_U_CB: gamma correction mapping blue to CB

14.11.317 SPCNTR—Offset 72380h

Sprite C Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72380h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SPRITE_C_ENABLE	SPRITE_C_GAMMA_ENABLE	SPRITE_C_SOURCE_PIXEL_FORMAT	SPRITE_C_PIPE_SELECT	RESERVED	SPRITE_SOURCE_KEY_ENABLE	PIXEL_MULTIPLY	COLOR_CONVERSION_DISABLED	YUV_FORMAT
								YUV_BYTE_ORDER
								_180DISPLAY_ROTATION
								RESERVED_1
								TILED_SURFACE
								RESERVED_2
								SPRITE_C_BOTTOM
								RESERVED_3
								SPRITE_C_Z_ORDER


Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	SPRITE_C_ENABLE: This bit will enable or disable the Sprite C. When this bit is set, the plane will generate pixels for display to be combined by the blender for the target pipe. When set to zero, memory fetches cease and display is blanked (from this plane) at the next VBLANK event from the pipe that this plane is assigned. At least one of the display pipes must be enabled to enable this plane. There is an override for the enable of this plane in the Pipe Configuration register. This bit only has an effect when the plane is not trusted. When the plane is marked trusted, this bit will be overridden and the display disabled when the registers are unlocked. 1 = Enable 0 = Disable



Bit Range	Default & Access	Field Name (ID): Description
30	0b RW	SPRITE_C_GAMMA_ENABLE: There are two gamma adjustments possible in the Sprite C data path. This bit controls the gamma correction in the display pipe not the gamma control in this plane. It affects only the pixel data from this display plane. For pixel format of 8-bit indexed, this bit should be set to a one. Gamma correction logic that is contained in the Sprite C logic is disabled by loading the default values into those registers. When this plane is marked as trusted, this bit should always be set to zero to force the pipe gamma to be always be bypassed. 0 = Sprite C pixel data bypasses the display pipe gamma correction logic (default). 1 = Sprite C pixel data is gamma corrected in the pipe gamma correction logic
29:26	0b RW	SPRITE_C_SOURCE_PIXEL_FORMAT: This field selects the pixel format for the sprite/Sprite C. Pixel formats with an alpha channel should not use source keying. Before entering the blender, each source format is converted to 10 bits per pixel (details are described in the intermediate precision for the blender section of the Display Functions chapter). 0000 = YUV 4:2:2 packed (see byte order below). 0001 = Reserved 0010 = 8-bpp Indexed. 0011 = Reserved. 0100 = Reserved. 0101 = 16-bit BGRX (5:6:5:0) pixel format (XGA compatible). 0110 = 32-bit BGRX (8:8:8:8) pixel format. Ignore alpha. 0111 = 32-bit BGRA (8:8:8:8) pixel format with pre-multiplied alpha channel. 1000 = 32-bit RGBX (10:10:10:2) pixel format. Ignore alpha. 1001 = 32-bit RGBA (10:10:10:2) pixel format 1010 = Reserved. 1011 = Reserved. 1100 = Reserved. 1101 = Reserved. 1110 = 32-bit RGBX (8:8:8:8) pixel format. Ignore alpha. 1111 = 32-bit RGBA (8:8:8:8)
25:24	0b RW	SPRITE_C_PIPE_SELECT: Sprite C always ties to Pipe B Reserved.
23	0b RW	RESERVED: Reserved.
22	0b RW	SPRITE_SOURCE_KEY_ENABLE: When used as a sprite in the 16/32-bpp modes without alpha this enables source color keying. Sprite pixel values that match (within range) the key will become transparent. Setting this bit is not allowed when the Sprite C pixel format includes an alpha channel. [DevBW] Erratum: This bit must always be set to 0 when Sprite C pixel format is YUV 0 = Sprite source key is disabled (default) 1 = Sprite source key is enabled.
21:20	0b RW	PIXEL_MULTIPLY: This cause the display plane to duplicate lines and pixels sent to the assigned pipe. In the line/pixel doubling mode, the horizontal pixels are doubled and lines are sent twice. This is a method of scaling the source image by two (both H and V). 00 = No line/Pixel duplication 01 = Line/Pixel Doubling 10 = Line Doubling only 11 = Pixel Doubling only
19	0b RW	COLOR_CONVERSION_DISABLED: This bit enables or disables the color conversion logic. Color conversion is intended to be used with the formats that support YUV formats such as the YUV 4:2:2 packed format and x:8:8:8 and 8:8:8:8 formats. Formats such as RGB5:5:5 and 5:6:5 do not have YUV versions. 0 = Pixel data is sent through the conversion logic (only applies to YUV formats) 1 = Pixel data is not sent through the YUV-)RGB conversion logic.
18	0b RW	YUV_FORMAT: This bit specifies the source YUV format for the YUV to RGB color conversion operation. This field is ignored when source data is RGB. 0 = ITU-R Recommendation BT.601 1 = ITU-R Recommendation BT.709



Bit Range	Default & Access	Field Name (ID): Description
17:16	0b RW	YUV_BYTE_ORDER: This field is used to select the byte order when using YUV 4:2:2 data formats. For other formats, this field is ignored. 00 = YUYV 01 = UYVY 10 = YVYU 11 = VYUY
15	0b RW	_180DISPLAY_ROTATION: This mode causes the display plane to be rotated 180 . In addition to setting this bit, software must also set the base address to the lower right corner of the unrotated image and calculate the x, y offset as relative to the lower right corner. 0 = No rotation 1 = 180 rotation
14:11	0b RW	RESERVED_1: Reserved.
10	0b RW	TILED_SURFACE: This bit indicates that the Sprite C surface data is in tiled memory. The tile pitch is specified in bytes in the DSPCSTRIDE register. Only X tiling is supported for display surfaces. When this bit is set, it affects the hardware interpretation of the DSPCTILEOFF, DSPCLINOFF, and DSPCSURFADDR registers. 0 = Sprite C surface uses linear memory 1 = Sprite C surface uses X-tiled memory
9:3	0b RW	RESERVED_2: Write as zero
2	0b RW	SPRITE_C_BOTTOM: This bit will force the Sprite C plane to be on the bottom of the Z order. If the plane is marked as trusted, it only applies to the Z order of the trusted planes. 0 = Sprite C Z order is determined by the other control bits 1 = Sprite C is forced to be on the bottom of the Z order.
1	0b RW	RESERVED_3: Reserved.
0	0b RW	SPRITE_C_Z_ORDER: With Sprite C and D z-order, bottom control bits, Sprite C plane is placed in a specific z-order among other planes in pipe B. Display Pipe B Z-orders SC zorderSC bottomSD zorderSD bottomResulting Pipe Z-order (from bottom to top)Source Keying 0000PB SC SD CBPB in Black 1000PB SD SC CBPB in Black 0001SD PB SC CBuse src keying on SD 0011SD PB SC CBuse src keying on SD 1001SD SC PB CBuse src keying on SC 1011SD SC PB CBuse src keying on SC 0100SC PB SD CBuse src keying on SC 1100SC PB SD CBuse src keying on SC 0110SC SD PB CBuse src keying on SD 1110SC SD PB CBuse src keying on SD 0101Not Allowed 0111Not Allowed 1101Not Allowed 1111Not Allowed 1010Not Allowed 1011Not Allowed 0: Sprite C z-order is disabled 1: Sprite C z-order is enabled



14.11.323 SPCKEYMSK—Offset 72398h

Access Method

GTTMMADR LSB Reference: [B:0, D:2, F:0] + 10h

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
995



Bit Range	Default & Access	Field Name (ID): Description
3	0b RW	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All
2	0b RW	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register. ValueNameDescriptionProject 0b Not requested Decryption not requested All 1b Requested Decryption requested All
1:0	0b RW	RESERVED_1: : MBZ

14.11.325 SPCKEYMAXVAL—Offset 723A0h

Sprite C Color Key Max Value Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 723A0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h





Bit Range	Default & Access	Field Name (ID): Description
2	0b RO	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register. ValueNameDescriptionProject 0b Not requested Decryption not requested All 1b Requested Decryption requested All
1:0	0b RO	RESERVED_1: MBZ

14.11.329 SPCCLRC0—Offset 723D0h

Sprite C Color Correction 0 Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 723D0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 01000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:27	0b RW	RESERVED: Reserved.

14.11.331 SPCGAMC5—Offset 723E0h



Bit Range	Default & Access	Field Name (ID): Description
7:0	11000000b RW	BLUE_U_CB: gamma correction mapping Blue to CB

14.11.332 SPCGAMC4—Offset 723E4h

Sprite C Gamma Correction Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 723E4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00808080h

31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED				RED_V_CR	GREEN_Y			
					BLUE_U_CB			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: reserved
23:16	10000000b RW	RED_V_CR: gamma correction mapping Red to CR
15:8	10000000b RW	GREEN_Y: gamma correction mapping Green to Y
7:0	10000000b RW	BLUE_U_CB: gamma correction mapping CB

14.11.333 SPCGAMC3—Offset 723E8h

Sprite C Gamma Correction Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 723E8h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00404040h



Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: reserved
23:16	00001000b RW	RED_V_CR: gamma correction mapping Red to CR
15:8	00001000b RW	GREEN_Y: gamma correction mapping Green to Y
7:0	00001000b RW	BLUE_U_CB: gamma correction mapping Blue to CB

14.11.337 SWF30—Offset 72414h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72414h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b RW	RESERVED_ : for Video BIOS and Drivers

14.11.338 SWF31—Offset 72418h

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72418h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



312824201612840																															
00																															

14.11.339 SWF32—Offset 7241Ch

Software Flag Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7241Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

312824201612840																															
00																															

14.11.340 SPDCNTR—Offset 72480h

Sprite D Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72480h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)


GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28				24				20				16				12				8				4				0																																		
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																			
SPRITE_D_ENABLE				SPRITE_D_GAMMA_ENABLE				SPRITE_D_SOURCE_PIXEL_FORMAT				RESERVED				SPRITE_SOURCE_KEY_ENABLE				PIXEL_MULTIPLY				COLOR_CONVERSION_DISABLED				YUV_FORMAT				YUV_BYTE_ORDER				_180DISPLAY_ROTATION				RESERVED_1				TILED_SURFACE				RESERVED_2				SPRITE_D_BOTTOM				RESERVED_3				SPRITE_D_Z_ORDER			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	SPRITE_D_ENABLE: This bit will enable or disable the Sprite D. When this bit is set, the plane will generate pixels for display to be combined by the blender for the target pipe. When set to zero, memory fetches cease and display is blanked (from this plane) at the next VBLANK event from the pipe that this plane is assigned. At least one of the display pipes must be enabled to enable this plane. There is an override for the enable of this plane in the Pipe Configuration register. This bit only has an effect when the plane is not trusted. When the plane is marked trusted, this bit will be overridden and the display disabled when the registers are unlocked. 1 = Enable 0 = Disable
30	0b RW	SPRITE_D_GAMMA_ENABLE: There are two gamma adjustments possible in the Sprite D data path. This bit controls the gamma correction in the display pipe not the gamma control in this plane. It affects only the pixel data from this display plane. For pixel format of 8-bit indexed, this bit should be set to a one. Gamma correction logic that is contained in the Sprite D logic is disabled by loading the default values into those registers. When this plane is marked as trusted, this bit should always be set to zero to force the pipe gamma to be always be bypassed. 0 = Sprite D pixel data bypasses the display pipe gamma correction logic (default). 1 = Sprite D pixel data is gamma corrected in the pipe gamma correction logic
29:26	0b RW	SPRITE_D_SOURCE_PIXEL_FORMAT: This field selects the pixel format for the sprite/Sprite D. Pixel formats with an alpha channel should not use source keying. Before entering the blender, each source format is converted to 10 bits per pixel (details are described in the intermediate precision for the blender section of the Display Functions chapter). 0000 = YUV 4:2:2 packed (see byte order below). 0001 = Reserved. 0010 = 8-bpp Indexed. 0011 = Reserved. 0100 = Reserved. 0101 = 16-bit BGRX (5:6:5:0) pixel format (XGA compatible). 0110 = 32-bit BGRX (8:8:8:8) pixel format. Ignore alpha. 0111 = 32-bit BGRA (8:8:8:8) pixel format with pre-multiplied alpha channel. 1000 = 32-bit RGBX (10:10:10:2) pixel format. Ignore alpha. 1001 = 32-bit RGBA (10:10:10:2) pixel format 1010 = Reserved. 1011 = Reserved. 1100 = Reserved. 1101 = Reserved. 1110 = 32-bit RGBX (8:8:8:8) pixel format. Ignore alpha. 1111 = 32-bit RGBA (8:8:8:8)
25:24	0b RW	SPRITE_D_PIPE_SELECT: Sprite D always ties to Pipe B. Reserved.



Bit Range	Default & Access	Field Name (ID): Description
23	0b RW	RESERVED: Reserved.
22	0b RW	SPRITE_SOURCE_KEY_ENABLE: When used as a sprite in the 16/32-bpp modes without alpha this enables source color keying. Sprite pixel values that match (within range) the key will become transparent. Setting this bit is not allowed when the Sprite D pixel format includes an alpha channel. [DevBW] Erratum: This bit must always be set to 0 when Sprite D pixel format is YUV 0 = Sprite source key is disabled (default) 1 = Sprite source key is enabled.
21:20	0b RW	PIXEL_MULTIPLY: This cause the display plane to duplicate lines and pixels sent to the assigned pipe. In the line/pixel doubling mode, the horizontal pixels are doubled and lines are sent twice. This is a method of scaling the source image by two (both H and V). 00 = No line/Pixel duplication 01 = Line/Pixel Doubling 10 = Line Doubling only 11 = Pixel Doubling only
19	0b RW	COLOR_CONVERSION_DISABLED: This bit enables or disables the color conversion logic. Color conversion is intended to be used with the formats that support YUV formats such as the YUV 4:2:2 packed format and x:8:8:8 and 8:8:8:8 formats. Formats such as RGB5:5:5 and 5:6:5 do not have YUV versions. 0 = Pixel data is sent through the conversion logic (only applies to YUV formats) 1 = Pixel data is not sent through the YUV->RGB conversion logic.
18	0b RW	YUV_FORMAT: This bit specifies the source YUV format for the YUV to RGB color conversion operation. This field is ignored when source data is RGB. 0 = ITU-R Recommendation BT.601 1 = ITU-R Recommendation BT.709
17:16	0b RW	YUV_BYTE_ORDER: This field is used to select the byte order when using YUV 4:2:2 data formats. For other formats, this field is ignored. 00 = YUYV 01 = UYVY 10 = YVYU 11 = VYUY
15	0b RW	_180DISPLAY_ROTATION: This mode causes the display plane to be rotated 180 . In addition to setting this bit, software must also set the base address to the lower right corner of the unrotated image and calculate the x, y offset as relative to the lower right corner. 0 = No rotation 1 = 180 rotation
14:11	0b RW	RESERVED_1: Reserved.
10	0b RW	TILED_SURFACE: This bit indicates that the Sprite D surface data is in tiled memory. The tile pitch is specified in bytes in the DSPCSTRIDE register. Only X tiling is supported for display surfaces. When this bit is set, it affects the hardware interpretation of the DSPCTILEOFF, DSPCLINOFF, and DSPCSURFADDR registers. 0 = Sprite D surface uses linear memory 1 = Sprite D surface uses X-tiled memory
9:3	0b RW	RESERVED_2: Write as zero
2	0b RW	SPRITE_D_BOTTOM: This bit will force the Sprite D plane to be on the bottom of the Z order. If the plane is marked as trusted, it only applies to the Z order of the trusted planes. 0 = Sprite D Z order is determined by the other control bits 1 = Sprite D is forced to be on the bottom of the Z order.
1	0b RW	RESERVED_3: Reserved.



14.11.342 SPDSTRIDE—Offset 72488h

Sprite D Stride Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 72488h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SPRITE_D_STRIDE								RESERVED

Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RW	SPRITE_D_STRIDE: This is the stride for Sprite D in bytes. When using linear memory, this must be 64 byte aligned. When using tiled memory, this must be 256 byte aligned. This register is updated through a command packet passed through the command stream or writes to this register. When it is desired to update both this and the start register, the stride register must be written first because the write to the start register is the trigger that causes the update of both registers on the next VBLANK event. When using tiled memory, the actual memory buffer stride is limited to a maximum of 16K bytes.
5:0	0b RW	RESERVED: Reserved.

14.11.343 SPDPOS—Offset 7248Ch

Sprite D Position Register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7248Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				SPRITE_HEIGHT				RESERVED_1
				SPRITE_WIDTH				

Intel Atom® Processor E3800 Product Family
Datasheet
1013

14.11.346 SPDKEYMSK—Offset 72498h

Sprite D Color Key Mask Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 72498h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RESERVED									RED_CHANNEL_ENABLE
									GREEN_CHANNEL_ENABLE
									BLUE_CHANNEL_ENABLE

Bit Range	Default & Access	Field Name (ID): Description
31:3	0b RW	RESERVED: Write as zero
2	0b RW	RED_CHANNEL_ENABLE: Specifies the source color key enable for the red/Cr channel.
1	0b RW	GREEN_CHANNEL_ENABLE: Specifies the source color key enable for the green/Y channel.
0	0b RW	BLUE_CHANNEL_ENABLE: Specifies the source color key enable for the blue/Cb channel

14.11.347 SPDSURF—Offset 7249Ch

Sprite D Surface Address Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7249Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



31				28				24				20				16				12				8				4				0											
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0											
SPRITE_D_SURFACE_BASE_ADDRESS																												RESERVED				FLIP_SOURCE				DECRIPTION_REQUEST				RESERVED_1			

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	SPRITE_D_SURFACE_BASE_ADDRESS: This address specifies the surface base address. When the surface is tiled, panning is specified using (x, y) offsets in the DSPCTILEOFF register. When the surface is in linear memory, panning is specified using a linear offset in the DSPCLINOFF register. This address must be 4K aligned. This register can be written directly through software or by command packets in the command stream. It represents an offset from the graphics memory aperture base and is mapped to physical pages through the global GTT. If the device supports trusted operation and this plane is not marked trusted, the memory pages must not be marked NoDMA . The value in this register is updated through the command streamer during synchronous flips. [DevBW] and [DevCL]: This address must be 128K aligned for linear memory.
11:4	0b RW	RESERVED: : MBZ
3	0b RW	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All



Bit Range	Default & Access	Field Name (ID): Description
2	0b RW	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register. ValueNameDescriptionProject 0b Not requested Decryption not requested All 1b Requested Decryption requested All
1:0	0b RW	RESERVED_1: MBZ

14.11.348 SPDKEYMAXVAL—Offset 724A0h

Sprite D Color Key Max Value Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 724A0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
RESERVED				RED_KEY_MAX_VALUE				GREEN_KEY_MAX_VALUE				BLUE_KEY_MAX_VALUE			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: Write as zero

14.11.350 SPDCONTALPHA—Offset 724A8h

Sprite D Constant Alpha Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 724A8h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0			
0	0	0	0	0	0	0	0	0			
ENABLE_CONSTANT_ALPHA				RESERVED				SPRITE_D_CONSTANT_ALPHA_VALUE			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	ENABLE_CONSTANT_ALPHA: Sprite D Sprite constant alpha provides a way to apply an alpha value to all video sprite pixels. Each pixel color channel is multiplied by the constant alpha before proceeding to the blender. This can be used to create fade out effects. This is intended for CE device use where the video sprite might still be used to generate video output. 0 Sprite D Constant Alpha is disabled 1 Sprite D Constant Alpha is enabled
30:8	0b RW	RESERVED: : MBZ
7:0	0b RW	SPRITE_D_CONSTANT_ALPHA_VALUE: This field provides the alpha value when constant alpha is enabled. A value of FF means fully opaque and a value of zero means fully transparent. Values in between those values allow for a blending of sprite with other surfaces.

14.11.351 SPDLIVESURF—Offset 724ACh

Sprite D Live Surface Address Register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 724ACh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RO	SPRITE_D_LIVE_SURFACE_BASE_ADDRESS: This gives the live value of the surface base address as being currently used for Sprite D
11:4	0b RO	RESERVED: : MBZ
3	0b RO	FLIP_SOURCE: Project: All Default Value: 0b This bit indicates if the source of the flip is CS or BCS so display can send the flip done response to the appropriate destination. ValueNameDescriptionProject 0b CS Flip source is CS All 1b BCS Flip source is BCS All



Bit Range	Default & Access	Field Name (ID): Description
2	0b RO	DECRYPTION_REQUEST: Project: All Default Value: 0b This bit requests decryption to be enabled for this plane. This request will be qualified with the separate decryption allow message in order to create the decryption enable. This bit is only allowed to change on a synchronous flip, but once set with a synchronous flip, the bit can remain set while using asynchronous flips. This value is loaded into the surface base address register of the associated plane. Usage must conform to the rules outlined in the plane surface base address register. ValueNameDescriptionProject 0b Not requested Decryption not requested All 1b Requested Decryption requested All
1:0	0b RO	RESERVED_1: MBZ

14.11.352 SPDCLRC0—Offset 724D0h

Sprite D Color Correction 0 Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 724D0h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 01000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED				CONTRAST				BRIGHTNESS

Bit Range	Default & Access	Field Name (ID): Description
31:27	0b RW	RESERVED: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
7:0	11000000b RW	BLUE_U_CB: gamma correction mapping Blue to CB

14.11.355 SPDGAMC4—Offset 724E4h

Sprite D Gamma Correction Registers

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 724E4h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00808080h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED				RED_V_CR	GREEN_Y		BLUE_U_CB	
							</	



Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	RESERVED: reserved
23:16	00001000b RW	RED_V_CR: gamma correction mapping Red to CR
15:8	00001000b RW	GREEN_Y: gamma correction mapping Green to Y
7:0	00001000b RW	BLUE_U_CB: gamma correction mapping blue to CB

14.11.360 PCSRC—Offset 73000h

Performance Counter Source Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 73000h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PERFORMANCE_COUNTER_ENABLE	RESERVED	RESET_COUNTER	MAX_OR_MIN	SOURCE_FOR_PERFORMANCE_COUNTER	RESERVED_1	PERFORMANCE_COUNTER_THRESHOLD_VALUE		

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	PERFORMANCE_COUNTER_ENABLE: This bit enables the performance counter. 0 = Performance counter is disabled 1 = Performance counter is enabled.
30	0b RW	RESERVED: Reserved.
29	0b RW	RESET_COUNTER: This bit indicates when the counter will be reset. 1 = Reset after each frame, summing all events in the frame 0 = Reset after each event within the frame



Bit Range	Default & Access	Field Name (ID): Description
28	0b RW	MAX_OR_MIN: This bit tells whether the stored counter value for an event is the maximum or the minimum value. The previous value is used to do the compare. 0 = Stored value is the maximum latency 1 = Stored value is the minimum latency
27:22	0b RW	SOURCE_FOR_PERFORMANCE_COUNTER: These bits indicate the source for the performance counter. 000000 = Overlay Register Request Latency [DevBW] and [DevCL] 000001 = VGA Font Request Latency 000010 = VGA Character Request Latency 000011 = Display A FIFO Status 000100 = Display B FIFO Status 000101 = Sprite A FIFO Status 000110 = Cursor A FIFO Status 000111 = Cursor B FIFO Status 001000 = Display Streamer A TLB Latency 001001 = Display Streamer B TLB Latency 001010 = Sprite Streamer A TLB Latency 001011 = Cursor Streamer A TLB Latency 001100 = Cursor Streamer B TLB Latency 001101 = Overlay Streamer TLB Latency [DevBW] and [DevCL] 001110 = Display Streamer A Request Latency 001111 = Display Streamer B Request Latency 010000 = Sprite Streamer A Request Latency 010001 = Cursor Streamer A Request Latency 010010 = Cursor Streamer B Request Latency 010011 = Overlay Streamer Request Latency [DevBW] and [DevCL] 010100 = Display A Command Request Latency 010101 = Display B Command Request Latency 010110 = Sprite A Command Request Latency 010111 = Cursor A Command Request Latency 011000 = Cursor B Command Request Latency 011001 = Overlay Command Request Latency [DevBW] and [DevCL] 011010 = DPFC Dummy Read [DevCTG] 011011 = DPFC Self Refresh [DevCTG] 011100 = Sprite B FIFO status 011101 = Sprite C FIFO status 011110 = Sprite D FIFO status 011111 = Sprite B TLB Request Latency 100000 = Sprite C TLB Request Latency 100001 = Sprite D TLB Request Latency 100010 = Sprite B Request Latency 100011 = Sprite C Request Latency 100100 = Sprite D Request Latency 100101 = Sprite B Command Request Latency 100110 = Sprite C Command Request Latency 100111 = Sprite D Command Request Latency 101000 = SR exit to data HP Put (measure the latency from the SRexit failing edge to the first data HP Put. This event shall be measured by either planeA, SpriteA, SpriteB, or CurA in pipeA) 101001 = InSR to data HP Put (measure the latency from any data request made during inSR is active to the first data HP Put. This event shall be measured by either planeA, SpriteA, SpriteB, or CurA in pipeA) 101010 = SR exit to TLB HP Put (measure the latency from the SRexit failing edge to the first TLB HP Put. This event shall be measured by either planeA, SpriteA, SpriteB, or CurA in pipeA) 101011 = InSR to TLB HP Put (measure the latency from any TLB request made during inSR is active to the first TLB HP Put. This event shall be measured by either planeA, SpriteA, SpriteB, or CurA in pipeA)
21:16	0b RW	RESERVED_1: Write as zero.
15:0	0b RW	PERFORMANCE_COUNTER_THRESHOLD_VALUE: This value is used to compare against the performance counter. If the performance counter matches this value, an interrupt is generated if the interrupt bit is enabled. When the source selected is DDB FIFO status, the threshold value is used to program the value needed to monitor in the DDB FIFO. No interrupt is generated in this condition.



14.11.361 PCSTAT—Offset 73004h

Performance Counter Status Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 73004h


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
OVERFLOW	RESET_COUNTER	MAX_OR_MIN	SOURCE_FOR_PERFORMANCE_COUNTER	RESERVED		PERFORMANCE_COUNTER_VALUE		

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	OVERFLOW: This bit indicates whether the 16 bit counter overflowed or not. 0 = Counter is valid 1 = Counter is invalid since it overflowed
30	0b RO	RESET_COUNTER: This bit indicates when the counter will be reset. 1 = Reset after each frame, sum of all event in the frame 0 = Reset after each event within the frame
29	0b RO	MAX_OR_MIN: This bit tells whether the stored counter value for an event is the maximum or the minimum value of the previous event. 0 = Stored value is the maximum latency 1 = Stored value is the minimum latency



Bit Range	Default & Access	Field Name (ID): Description
28:23	0b RO	SOURCE_FOR_PERFORMANCE_COUNTER: These bits indicate the source for the performance counter. 000000 = Overlay Register Request Latency [DevBW] and [DevCL] 000001 = VGA Font Request Latency 000010 = VGA Character Request Latency 000011 = Display A FIFO Status 000100 = Display B FIFO Status 000101 = Sprite A FIFO Status 000110 = Cursor A FIFO Status 000111 = Cursor B FIFO Status 001000 = Display Steamer A TLB Latency 001001 = Display Steamer B TLB Latency 001010 = Sprite Steamer A TLB Latency 001011 = Cursor Steamer A TLB Latency 001100 = Cursor Steamer B TLB Latency 001101 = Overlay Steamer TLB Latency [DevBW] and [DevCL] 001110 = Display Steamer A Request Latency 001111 = Display Steamer B Request Latency 010000 = Sprite Steamer A Request Latency 010001 = Cursor Steamer A Request Latency 010010 = Cursor Steamer B Request Latency 010011 = Overlay Steamer Request Latency [DevBW] and [DevCL] 010100 = Display A Command Request Latency 010101 = Display B Command Request Latency 010110 = Sprite A Command Request Latency 010111 = Cursor A Command Request Latency 011000 = Cursor B Command Request Latency 011001 = Overlay Command Request Latency [DevBW] and [DevCL] 011010 = DPFC Dummy Read [DevCTG] 011011 = DPFC Self Refresh [DevCTG] 011100 = Sprite B FIFO status 011101 = Sprite C FIFO status 011110 = Sprite D FIFO status 011111 = Sprite B TLB Request Latency 100000 = Sprite C TLB Request Latency 100001 = Sprite D TLB Request Latency 100010 = Sprite B Request Latency 100011 = Sprite C Request Latency 100100 = Sprite D Request Latency 100101 = Sprite B Command Request Latency 100110 = Sprite C Command Request Latency 100111 = Sprite D Command Request Latency 101000 = SR exit to data HP Put (measure the latency from the SRexit failing edge to the first data HP Put. This event shall be measured by either planeA, SpriteA, SpriteB, or CurA in pipeA) 101001 = InSR to data HP Put (measure the latency from any data request made during inSR is active to the first data HP Put. This event shall be measured by either planeA, SpriteA, SpriteB, or CurA in pipeA) 101010 = SR exit to TLB HP Put (measure the latency from the SRexit failing edge to the first TLB HP Put. This event shall be measured by either planeA, SpriteA, SpriteB, or CurA in pipeA) 101011 = InSR to TLB HP Put (measure the latency from any TLB request made during inSR is active to the first TLB HP Put. This event shall be measured by either planeA, SpriteA, SpriteB, or CurA in pipeA)
22:16	0b RO	RESERVED: Write as zero.
15:0	0b RO	PERFORMANCE_COUNTER_VALUE: This is the value of the performance counter for the source indicated in the source field.

14.11.362 PCSRC2—Offset 73008h

Performance Counter Source2 Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR LSB + 180000h] + 73008h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED								
RESERVED_1								
RESET_COUNTER								
MAX_OR_MIN								
	SOURCE_FOR_PERFORMANCE_COUNTER							
			RESERVED_2					
						PERFORMANCE_COUNTER_THRESHOLD_VALUE		

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	RESERVED: Programming note: This second performance counter is enabled by the enable bit in the PCSRC1 bit 31.
30	0b RW	RESERVED_1: Reserved.
29	0b RW	RESET_COUNTER: This bit indicates when the counter will be reset. 1 = Reset after each frame, summing all events in the frame 0 = Reset after each event within the frame
28	0b RW	MAX_OR_MIN: This bit tells whether the stored counter value for an event is the maximum or the minimum value. The previous value is used to do the compare. 0 = Stored value is the maximum latency 1 = Stored value is the minimum latency



Bit Range	Default & Access	Field Name (ID): Description
27:22	0b RW	SOURCE_FOR_PERFORMANCE_COUNTER: These bits indicate the source for the performance counter. 000000 = Overlay Register Request Latency [DevBW] and [DevCL] 000001 = VGA Font Request Latency 000010 = VGA Character Request Latency 000011 = Display A FIFO Status 000100 = Display B FIFO Status 000101 = Sprite A FIFO Status 000110 = Cursor A FIFO Status 000111 = Cursor B FIFO Status 001000 = Display Streamer A TLB Latency 001001 = Display Streamer B TLB Latency 001010 = Sprite Streamer A TLB Latency 001011 = Cursor Streamer A TLB Latency 001100 = Cursor Streamer B TLB Latency 001101 = Overlay Streamer TLB Latency [DevBW] and [DevCL] 001110 = Display Streamer A Request Latency 001111 = Display Streamer B Request Latency 010000 = Sprite Streamer A Request Latency 010001 = Cursor Streamer A Request Latency 010010 = Cursor Streamer B Request Latency 010011 = Overlay Streamer Request Latency [DevBW] and [DevCL] 010100 = Display A Command Request Latency 010101 = Display B Command Request Latency 010110 = Sprite A Command Request Latency 010111 = Cursor A Command Request Latency 011000 = Cursor B Command Request Latency 011001 = Overlay Command Request Latency [DevBW] and [DevCL] 011010 = DPFC Dummy Read [DevCTG] 011011 = DPFC Self Refresh [DevCTG] 011100 = Sprite B FIFO status 011101 = Sprite C FIFO status 011110 = Sprite D FIFO status 011111 = Sprite B TLB Request Latency 100000 = Sprite C TLB Request Latency 100001 = Sprite D TLB Request Latency 100010 = Sprite B Request Latency 100011 = Sprite C Request Latency 100100 = Sprite D Request Latency 100101 = Sprite B Command Request Latency 100110 = Sprite C Command Request Latency 100111 = Sprite D Command Request Latency 101000 = SR exit to data HP Put (measure the latency from the SRexit failing edge to the first data HP Put. This event shall be measured by either planeB, SpriteC, SpriteD, or CurB in pipeB) 101001 = InSR to data HP Put (measure the latency from any data request made during inSR is active to the first data HP Put. This event shall be measured by either planeB, SpriteC, SpriteD, or CurB in pipeB) 101010 = SR exit to TLB HP Put (measure the latency from the SRexit failing edge to the first TLB HP Put. This event shall be measured by either planeB, SpriteC, SpriteD, or CurB in pipeB) 101011 = InSR to TLB HP Put (measure the latency from any TLB request made during inSR is active to the first TLB HP Put. This event shall be measured by either planeB, SpriteC, SpriteD, or CurB in pipeB)
21:16	0b RW	RESERVED_2: Write as zero.
15:0	0b RW	PERFORMANCE_COUNTER_THRESHOLD_VALUE: This value is used to compare against the performance counter. If the performance counter matches this value, an interrupt is generated if the interrupt bit is enabled. When the source selected is DDB FIFO status, the threshold value is used to program the value needed to monitor in the DDB FIFO. No interrupt is generated in this condition.



14.11.363 PCSTAT2—Offset 7300Ch

Performance Counter Status2 Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [GTTMMADR_LSB + 180000h] + 7300Ch

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
OVERFLOW	RESET_COUNTER	MAX_OR_MIN	SOURCE_FOR_PERFORMANCE_COUNTER	RESERVED		PERFORMANCE_COUNTER_VALUE		

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	OVERFLOW: This bit indicates whether the 16 bit counter overflowed or not. 0 = Counter is valid 1 = Counter is invalid since it overflowed
30	0b RO	RESET_COUNTER: This bit indicates when the counter will be reset. 1 = Reset after each frame, sum of all event in the frame 0 = Reset after each event within the frame
29	0b RO	MAX_OR_MIN: This bit tells whether the stored counter value for an event is the maximum or the minimum value of the previous event. 0 = Stored value is the maximum latency 1 = Stored value is the minimum latency



Bit Range	Default & Access	Field Name (ID): Description
28:23	0b RO	SOURCE_FOR_PERFORMANCE_COUNTER: These bits indicate the source for the performance counter. 000000 = Overlay Register Request Latency [DevBW] and [DevCL] 000001 = VGA Font Request Latency 000010 = VGA Character Request Latency 000011 = Display A FIFO Status 000100 = Display B FIFO Status 000101 = Sprite A FIFO Status 000110 = Cursor A FIFO Status 000111 = Cursor B FIFO Status 001000 = Display Steamer A TLB Latency 001001 = Display Steamer B TLB Latency 001010 = Sprite Steamer A TLB Latency 001011 = Cursor Steamer A TLB Latency 001100 = Cursor Steamer B TLB Latency 001101 = Overlay Steamer TLB Latency [DevBW] and [DevCL] 001110 = Display Steamer A Request Latency 001111 = Display Steamer B Request Latency 010000 = Sprite Steamer A Request Latency 010001 = Cursor Steamer A Request Latency 010010 = Cursor Steamer B Request Latency 010011 = Overlay Steamer Request Latency [DevBW] and [DevCL] 010100 = Display A Command Request Latency 010101 = Display B Command Request Latency 010110 = Sprite A Command Request Latency 010111 = Cursor A Command Request Latency 011000 = Cursor B Command Request Latency 011001 = Overlay Command Request Latency [DevBW] and [DevCL] 011010 = DPFC Dummy Read [DevCTG] 011011 = DPFC Self Refresh [DevCTG] 011100 = Sprite B FIFO status 011101 = Sprite C FIFO status 011110 = Sprite D FIFO status 011111 = Sprite B TLB Request Latency 100000 = Sprite C TLB Request Latency 100001 = Sprite D TLB Request Latency 100010 = Sprite B Request Latency 100011 = Sprite C Request Latency 100100 = Sprite D Request Latency 100101 = Sprite B Command Request Latency 100110 = Sprite C Command Request Latency 101001 = InSR to HP Put (first put after inSR failing edge) 101000 = SR exit to data HP Put (measure the latency from the SRexit failing edge to the first data HP Put. This event shall be measured by either planeB, SpriteC, SpriteD, or CurB in pipeB) 101001 = InSR to data HP Put (measure the latency from any data request made during inSR is active to the first data HP Put. This event shall be measured by either planeB, SpriteC, SpriteD, or CurB in pipeB) 101010 = SR exit to TLB HP Put (measure the latency from the SRexit failing edge to the first TLB HP Put. This event shall be measured by either planeB, SpriteC, SpriteD, or CurB in pipeB) 101011 = InSR to TLB HP Put (measure the latency from any TLB request made during inSR is active to the first TLB HP Put. This event shall be measured by either planeB, SpriteC, SpriteD, or CurB in pipeB)
22:16	0b RO	RESERVED: Write as zero.
15:0	0b RO	PERFORMANCE_COUNTER_VALUE: This is the value of the performance counter for the source indicated in the source field.



14.12 Memory Mapped Registers (Read Only)

Table 174. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
3BA–3BAh	1	"ST01 (ST01_MDA)—Offset 3BAh" on page 1035	00h
3C2–3C2h	1	"ST00—Offset 3C2h" on page 1036	00h
3C7–3C7h	1	"DACSTATE—Offset 3C7h" on page 1037	00h
3DA–3DAh	1	"ST01 (ST01_CGA)—Offset 3DAh" on page 1038	00h

14.12.1 ST01 (ST01_MDA)—Offset 3BAh

Input Status 1

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3BAh


GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7	0	0	0	4	0	0	0	0	0
RESERVED_AS_PER_VGA_SPECIFICATION	RESERVED	VIDEO_FEEDBACK_1_0	VER_TL_CAL_RETRACE_VIDEO	RESERVED_1	DIS_PLAY_ENA_BLE_OUTPUT				

Bit Range	Default & Access	Field Name (ID): Description
7	0b RO	RESERVED_AS_PER_VGA_SPECIFICATION: Read as 0s.
6	0b RO	RESERVED: Read as 0.
5:4	0b RO	VIDEO_FEEDBACK_1_0: These are diagnostic video bits that are selected by the Color Plane Enable Register. These bits that are programmably connected to 2 of the 8 color bits sent to the palette. Bits 4 and 5 of the Color Plane Enable Register (AR12) selects which two of the 8 possible color bits become connected to these 2 bits of this register. The current software normally does not use these 2 bits. They exist for EGA compatibility.



Bit Range	Default & Access	Field Name (ID): Description
3	0b RO	VER_TI_CAL_RETRACE_VIDEO: 0 = VSYNC inactive (Indicates that a vertical retrace interval is not taking place). 1 = VSYNC active (Indicates that a vertical retrace interval is taking place). Note: VGA pixel generation is not locked to the display output but is loosely coupled. A VSYNC indication may not occur during the actual VSYNC going to the display but during the VSYNC that is generated as part of the VGA pixel generation. The exact relationship will vary with the VGA display operational mode. This status bit will remain active when the VGA is disabled and the device is running in high resolution modes (non-VGA) to allow for applications that (now it is incorrect) use these status registers bits. In this case, the status will come from the pipe that the VGA is assigned to. Bits 4 and 5 of the Vertical Retrace End Register (CR11) previously could program this bit to generate an interrupt at the start of the vertical retrace interval. This ability to generate interrupts at the start of the vertical retrace interval is a feature that is largely unused by legacy software. Interrupts are not supported through the VGA register bits.
2:1	0b RO	RESERVED_1: Read as 0s.
0	0b RO	DIS_PLAY_ENA_BLE_OUTPUT: Display Enable is a status bit (bit 0) in VGA Input Status Register 1 that indicates when either a horizontal retrace interval or a vertical retrace interval is taking place. This was used with the IBM* EGA graphics system (and the ones that preceded it, including MDA and CGA). In those cases, it was important to check the status of this bit to ensure that one or the other retrace intervals was taking place before reading from or writing to the frame buffer. In these earlier systems, reading from or writing to frame buffer at times outside the retrace intervals meant that the CRT controller would be denied access to the frame buffer. This resulted in either snow or a flickering display. This bit provides compatibility with software designed for those early graphics controllers. This bit is currently used in DOS applications that access the palette to prevent the sparkle associated with read and write accesses to the palette ram with the same address on the same clock cycle. This status bit will remain active when the VGA display is disabled and the device is running in high resolution modes (non-VGA) to allow for applications that (now considered incorrect) use these status registers bits. In this case, the status will come from the pipe that the VGA is assigned to. When in panel fitting VGA or centered VGA operation, the meaning of these bits will not be consistent with native VGA timings. 0 = Active display data is being sent to the display. Neither a horizontal retrace interval or a vertical retrace interval is currently taking place. 1 = Either a horizontal retrace interval (horizontal blanking) or a vertical retrace interval (vertical blanking) is currently taking place.

14.12.2 ST00—Offset 3C2h

Input Status 0

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C2h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h



7	0	0	0	4	0	0	0	0	0
CRT_INTER_RUPT_PENDING			RESERVED	RGB_COMPARATOR_SENSE				RESERVED_1	

Bit Range	Default & Access	Field Name (ID): Description
7	0b RO	CRT_INTER_RUPT_PENDING: This bit is here for EGA compatibility and will always return zero. Note that the generation of interrupts was originally enabled, through bits [4,5] of the Vertical Retrace End Register (CR11). This ability to generate interrupts at the start of the vertical retrace interval is a feature that is typically unused by DOS software and therefore is only supported through other means for use under a operating system support. 0 = CRT (vertical retrace interval) interrupt is not pending. 1 = CRT (vertical retrace interval) interrupt is pending
6:5	0b RO	RESERVED: Read as 0s.
4	0b RO	RGB_COMPARATOR_SENSE: This bit returns the state of the output of the RGB output comparator(s). Video BIOS uses this bit during POST to determine whether the display is connected and if it is a color or monochrome CRT. BIOS blanks the screen or clears the frame buffer to display only black. Next, BIOS outputs a ramp to the D-to-A converters to test for the presence of a color display by determining which code cause the comparator to switch. Finally, if the BIOS does not detect any termination resistors on Red or Blue, it tests for the presence of a display using the Green signal. The result of each such test is read via this bit. 0 = Below threshold 1 = Above threshold
3:0	0b RO	RESERVED_1: Read as 0s.

14.12.3 DACSTATE—Offset 3C7h

DAC State Register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C7h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7	0	0	0	4	0	0	0	0	0
				RESERVED				DAC_STATE	



Bit Range	Default & Access	Field Name (ID): Description
7:2	0b RO	RESERVED: Read as 0.
1:0	0b RO	DAC_STATE: This field indicates which of the two index registers was most recently written. Bits [1:0] Index Register Indicated 00 Palette Write Index Register at I/O Address 3C7h (default) 01 Reserved 10 Reserved 11 Palette Read Index Register at I/O Address 3C8h

14.12.4 ST01 (ST01_CGA)—Offset 3DAh

Input Status 1

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3DAh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7	4	0
0	0	0
RESERVED_AS_PER_VGA_SPECIFICATION	RESERVED	VIDEO_FEEDBACK_1_0
		VER_TI_CAL_RETRACE_VIDEO
		RESERVED_1
		DIS_PLAY_ENA_BLE_OUTPUT

Bit Range	Default & Access	Field Name (ID): Description
7	0b RO	RESERVED_AS_PER_VGA_SPECIFICATION: Read as 0s.
6	0b RO	RESERVED: Read as 0.
5:4	0b RO	VIDEO_FEEDBACK_1_0: These are diagnostic video bits that are selected by the Color Plane Enable Register. These bits that are programmably connected to 2 of the 8 color bits sent to the palette. Bits 4 and 5 of the Color Plane Enable Register (AR12) selects which two of the 8 possible color bits become connected to these 2 bits of this register. The current software normally does not use these 2 bits. They exist for EGA compatibility.



Bit Range	Default & Access	Field Name (ID): Description
3	0b RO	VER_TI_CAL_RETRACE_VIDEO: 0 = VSYNC inactive (Indicates that a vertical retrace interval is not taking place). 1 = VSYNC active (Indicates that a vertical retrace interval is taking place). Note: VGA pixel generation is not locked to the display output but is loosely coupled. A VSYNC indication may not occur during the actual VSYNC going to the display but during the VSYNC that is generated as part of the VGA pixel generation. The exact relationship will vary with the VGA display operational mode. This status bit will remain active when the VGA is disabled and the device is running in high resolution modes (non-VGA) to allow for applications that (now it is incorrect) use these status registers bits. In this case, the status will come from the pipe that the VGA is assigned to. Bits 4 and 5 of the Vertical Retrace End Register (CR11) previously could program this bit to generate an interrupt at the start of the vertical retrace interval. This ability to generate interrupts at the start of the vertical retrace interval is a feature that is largely unused by legacy software. Interrupts are not supported through the VGA register bits.
2:1	0b RO	RESERVED_1: Read as 0s.
0	0b RO	DIS_PLAY_ENA_BLE_OUTPUT: Display Enable is a status bit (bit 0) in VGA Input Status Register 1 that indicates when either a horizontal retrace interval or a vertical retrace interval is taking place. This was used with the IBM* EGA graphics system (and the ones that preceded it, including MDA and CGA). In those cases, it was important to check the status of this bit to ensure that one or the other retrace intervals was taking place before reading from or writing to the frame buffer. In these earlier systems, reading from or writing to frame buffer at times outside the retrace intervals meant that the CRT controller would be denied access to the frame buffer. This resulted in either snow or a flickering display. This bit provides compatibility with software designed for those early graphics controllers. This bit is currently used in DOS applications that access the palette to prevent the sparkle associated with read and write accesses to the palette ram with the same address on the same clock cycle. This status bit will remain active when the VGA display is disabled and the device is running in high resolution modes (non-VGA) to allow for applications that (now considered incorrect) use these status registers bits. In this case, the status will come from the pipe that the VGA is assigned to. When in panel fitting VGA or centered VGA operation, the meaning of these bits will not be consistent with native VGA timings. 0 = Active display data is being sent to the display. Neither a horizontal retrace interval or a vertical retrace interval is currently taking place. 1 = Either a horizontal retrace interval (horizontal blanking) or a vertical retrace interval (vertical blanking) is currently taking place.



14.13 Memory Mapped Registers (Write Only)

Table 175. Summary of Display Memory Mapped I/O Registers—GTTMMADR_LSB

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
3BA–3BAh	1	"FCR (FCR_MDA_Write)—Offset 3BAh" on page 1041	00h
3C2–3C2h	1	"MSR (MSR_Write)—Offset 3C2h" on page 1042	00h
3C7–3C7h	1	"DACRX—Offset 3C7h" on page 1043	00h
3DA–3DAh	1	"FCR (FCR_CGA_Write)—Offset 3DAh" on page 1044	00h

14.13.1 FCR (FCR_MDA_Write)—Offset 3BAh

Feature Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3BAh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7	4	0
0	0	0
RESERVED		VSYNC_CONTROL
		RESERVED_1

Bit Range	Default & Access	Field Name (ID): Description
7:4	0b RW	RESERVED: Read as 0.
3	0b RW	VSYNC_CONTROL: This bit is provided for compatibility only and has no other function. Reads and writes to this bit have no effect other than to change the value of this bit. The previous definition of this bit selected the output on the VSYNC pin. 0 = Was used to set VSYNC out put on the VSYNC pin. (default). 1 = Was used to set the logical 'OR' of VSYNC and Display Enable output on the VSYNC pin. This capability was not typically very useful..
2:0	0b RW	RESERVED_1: Read as 0.



14.13.2 MSR (MSR_Write)—Offset 3C2h

Miscellaneous Output

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C2h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7	0	0	0	4	0	0	0	0
CRT_VSYNC_POLARITY	CRT_HSYNC_POLARITY	PAGE_SELECT	RESERVED	CLOCK_SELECT	A0000_BFFFFH_MEMORY_ACCESS_ENABLE	I_O_ADDRESS_SELECT		

Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	CRT_VSYNC_POLARITY: This is a legacy function that is used in native VGA modes. For most cases, sync polarity will be controlled by the port control bits. The VGA settings can be optionally selected for compatibility with the original VGA when used in the VGA native mode. Sync polarity was used in VGA to signal the monitor how many lines of active display are being generated. 0 = Positive Polarity (default). 1 = Negative Polarity.
6	0b RW	CRT_HSYNC_POLARITY: This is a legacy function that is used in native VGA modes. For most cases, sync polarity will be controlled by the port control bits. The VGA settings can be optionally selected for compatibility with the original VGA when used in the VGA native mode. 0 = Positive Polarity (default). 1 = Negative Polarity
5	0b RW	PAGE_SELECT: In Odd/Even Memory Map Mode 1 (GR6), this bit selects the upper or lower 64 KB page in display memory for CPU access: 0 = Upper page (default) 1 = Lower page. Selects between two 64KB pages of frame buffer memory during standard VGA odd/even modes (modes 0h through 5h). Bit 1 of register GR06 can also program this bit in other modes. Note that this bit is would normally set to 1 by the software.
4	0b RW	RESERVED: Read as 0.



Bit Range	Default & Access	Field Name (ID): Description
3:2	0b RW	CLOCK_SELECT: These bits can select the dot clock source for the CRT interface. The bits should be used to select the dot clock in standard native VGA modes only. When in the centering or upper left corner modes, these bits should be set to have no effect on the clock rate. The actual frequencies that these bits select, if they have any affect at all, is programmable through the DPLL registers that default to the standard values used for VGA. 00 = CLK0, 25.175 MHz (for standard VGA modes with 640 pixel (8-dot) horizontal resolution) (default) 01 = CLK1, 28.322 MHz. (for standard VGA modes with 720 pixel (9-dot) horizontal resolution) 10 = Was used to select an external clock (now unused) 11 = Reserved
1	0b RW	A0000_BFFFFH_MEMORY_ACCESS_ENABLE: VGA Compatibility bit enables access to local video memory (frame buffer) at A0000(BFFFFh). When disabled, accesses to VGA memory are blocked in this region. This bit is independent of and does not block CPU access to the video linear frame buffer at other addresses. Note that it is typical for AGP chipsets to shadow this register to allow proper steering of memory accesses to the proper bus. 0 = Prevent CPU access to memory/registers/ROM through the A0000-BFFFF VGA memory aperture (default). 1 = Allow CPU access to memory/registers/ROM through the A0000-BFFFF VGA memory aperture. This memory must be mapped as UC by the CPU; see VGA Host Access Memory Munging in Display and Overlay Functions.
0	0b RW	I_O_ADDRESS_SELECT: This bit selects 3Bxh or 3Dxh as the I/O address for the CRT Controller registers, the Feature Control Register (FCR), and Input Status Register 1 (ST01). Presently ignored (whole range is claimed), but will ignore 3Bx for color configuration or 3Dx for monochrome. Note that it is typical in AGP chipsets to shadow this bit and properly steer I/O cycles to the proper bus for operation where a MDA exists on another bus such as ISA. 0 = Select 3Bxh I/O address (MDA emulation) (default). 1 = Select 3Dxh I/O address (CGA emulation).

14.13.3 DACRX—Offset 3C7h

Palette Read Index Register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3C7h

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
PALETTE_READ_INDEX							



Bit Range	Default & Access	Field Name (ID): Description
7:0	0b WO	PALETTE_READ_INDEX: The 8-bit index value programmed into this register chooses which of 256 standard color data positions within the palette are to be made accessible for being read from via the Palette Data Register (DACDATA). The index value held in this register is automatically incremented when all three bytes of the color data position selected by the current index have been read. A write to this register will abort a uncompleted palette write sequence. This register allows access to the palette even when running non-VGA display modes.

14.13.4 FCR (FCR_CGA_Write)—Offset 3DAh

Feature Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [GTTMMADR_LSB + 180000h] + 3DAh

GTTMMADR_LSB Type: PCI Configuration Register (Size: 32 bits)

GTTMMADR_LSB Reference: [B:0, D:2, F:0] + 10h

Default: 00h


7		4		0
0	0	0	0	0
RESERVED			VSYNC_CONTROL	RESERVED_1

Bit Range	Default & Access	Field Name (ID): Description
7:4	0b RW	RESERVED: Read as 0.
3	0b RW	VSYNC_CONTROL: This bit is provided for compatibility only and has no other function. Reads and writes to this bit have no effect other than to change the value of this bit. The previous definition of this bit selected the output on the VSYNC pin. 0 = Was used to set VSYNC out put on the VSYNC pin (default). 1 = Was used to set the logical 'OR' of VSYNC and Display Enable output on the VSYNC pin. This capability was not typically very useful..
2:0	0b RW	RESERVED_1: Read as 0.

15 MIPI-Camera Serial Interface (CSI) and ISP

Note: The MIPI CSI and controller front end interfaces with three sensors and is capable of simultaneously acquiring three streams, one from each sensor. These three streams are presented to the ISP.

Note: If a 1-lane sensor needs to be connected to a MIPI-CSI port, that port must use a 1-lane port configuration.



15.1 Signal Descriptions

See [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function



Table 176. CSI Signals


Signal Name	Direction Plat. Power	Description
MCSI1_CLKP/N	I V1P24S	Clock Lane: MIPI CSI input clock lane 0 for port 1.
MCSI1_DP/N[3:0]	I V1P24S	Data Lanes: Four MIPI CSI Data Lanes (0-3) for port 1. Lanes 2 and 3 can optionally used as data lanes for port 3.
MCSI2_CLKP/N	I V1P24S	Clock Lane: MIPI CSI input clock lane 0 for port 2.
MCSI2_DP/N[0]	I V1P24S	Data Lane: Single MIPI CSI Data Lanes for port 2.
MCSI3_CLKP/N	I V1P24S	Clock Lane: MIPI CSI input clock lane 0 for port 3.
MCSI_RCOMP	I/O	Resistor Compensation: This is for pre-driver slew rate compensation for the MIPI CSI Interface. Contact your Intel representative for details.

Table 177. GPIO Signals (Sheet 1 of 2)

Signal Name	Direction Plat. Power	Description
MCSI_GPIO[00]	I/O V1P8S	Output from shutter switch when its pressed halfway. This switch state is used to trigger the Auto focus LED for Xenon Flash or Torch mode for LED Flash
MCSI_GPIO[01]	I/O V1P8S	Output from shutter switch when its pressed full way. This switch state is used to trigger Xenon flash or LED Flash
MCSI_GPIO[02]	I/O V1P8S	Active high control signal to Xenon Flash to start charging the Capacitor
MCSI_GPIO[03]	I/O V1P8S	Active low output from Xenon Flash to indicate that the capacitor is fully charged and is ready to be triggered
MCSI_GPIO[04]	I/O V1P8S	Active high Xenon Flash trigger / Enables Torch Mode on LED Flash IC
MCSI_GPIO[05]	I/O V1P8S	Enables Red Eye Reduction LED for Xenon / Triggers STROBE on LED Flash IC /
MCSI_GPIO[06]	I/O V1P8S	Camera Sensor 0 Strobe Output to SoC to indicate beginning of capture / Active high signal to still camera to power down the device.
MCSI_GPIO[07]	I/O V1P8S	Camera Sensor 1 Strobe Output to SoC to indicate beginning of capture / Active high signal to still camera to power down the device.

Table 177. GPIO Signals (Sheet 2 of 2)

Signal Name	Direction Plat. Power	Description
MCSI_GPIO[08]	I/O V1P8S	Active high signal to video camera to power down the device.
MCSI_GPIO[09]	I/O V1P8S	Active low output signal to reset digital still camera #0.
MCSI_GPIO[10]	I/O V1P8S	Active low output signal to reset digital still camera #1
MCSI_GPIO[11]	I/O V1P8S	Active low output signal to reset digital video camera

Figure 94. Camera Connectivity


15.2 Features

- Integrated MIPI-CSI 2.0 interface
- Image Signal Processor (ISP) with DMA and local SRAM
- Imaging data is received by the MIPI-CSI interface and is relayed to the ISP for processing
- Up to five MIPI-CSI 2.0 data lanes
 - Each lane can operate at up to 1GT/s. resulting in roughly 800 Mbit/s of actual pixels
- The MIPI-CSI interface supports lossless compressed image streams to increase the effective bandwidth without losing data



- Up to 24MP sensors supported, and full HD 1080p60
 - Can also support Stereo HD 1080p30
- Up to 3 cameras can be operated simultaneously
 - Stereoscopic Captures
 - Front + Back Camera Usage

15.2.1 Imaging Capabilities

The following table summarizes imaging capabilities.

Table 178. Imaging Capabilities

Feature	Capabilities
Sensor interface	Configurable MIPI-CSI2 interfaces. 3 sensors: x2, x2, x1 or x3, x1, x1 2 sensors: x4, x1
Simultaneous sensors	Up to 3 simultaneous sensors
2D Image capture	24MP @ 15fps
2D video capture	Up to 1080p60
Input formats (Sensor -> SoC)	RAW 8, 10, 12, 14, RGB444, 565, 888, YUV420, 422, JPEG.
Output formats (SoC -> Sensor)	YUV422, YUV420, RAW
Special Features	Image and video stabilization Low light noise reduction Burst mode capture Memory to memory processing 3A (Auto Exposure (AE), Auto White Balance (AWB) and Auto Focus (AF)) High Dynamic Range (HDR) Multi-focus Zero shutter lag


15.2.2 Simultaneous Acquisition

All three cameras can be active at the same time.

SoC will support on-the-fly processing for only one image at a time. While this image is being processed on-the-fly, images from the other two cameras are saved to DRAM for later processing.

15.2.3 Primary Camera Still Image Resolution

Maximum still image resolution for the primary camera in post-processing mode is limited by the resolution of the sensors. Currently 24 Mpixel sensors are supported.



Maximum primary camera on-the-fly still image resolution for primary camera is 16 Mpixel at 18 fps.

Higher resolution, or higher frame rates are supported as long as the product of resolution and frame rate does not exceed 288 Mpixels/s (= 16 Mpixels * 18 fps).

Maximum primary camera on-the-fly stereoscopic still image resolution for primary camera is 8 Mpixel for each of the left and right images at 18 fps. The number of Mpixels can be increased by decreasing the frame rate.

15.2.4 Burst Mode Support

The SoC supports capturing multiple images back to back at maximum sensor resolution. At least 5 images must be captured in burst mode. The maximum number of images that can be so captured is limited only by available system memory. These images need not be processed on-the-fly.

15.2.5 Continuous Mode Capture

SoC supports capturing images and saving them to DRAM in a ring of frame buffers continuously at maximum sensor resolution. These images must then be fetched and processed on-the-fly by the ISP. This adds a round trip to memory for every frame and increases the bandwidth requirements.

15.2.6 Secondary Camera Still Image Resolution

Maximum secondary camera still image resolution is 4 Mpixel at 15 fps.

15.2.7 Primary Camera Video Resolution

Maximum primary camera video resolution is 1080p60.

Maximum primary camera dual video resolution is 1080p30.

Maximum stereo resolution is 1080p30.

15.2.8 Secondary Camera Video Resolution

Maximum secondary camera video resolution is 1080p30.

15.2.9 Bit Depth

Capable of processing 14-bit images at the stated performance levels.


Capable of processing 18-bit images at half the performance levels, i.e. process on-the-fly 16 Mpixel 18-bit images at 7 fps instead of 15 fps.

Capable of processing up to 18-bit precision.

The higher precision processing will be employed mainly for high dynamic range imaging (HDR).

15.3 Imaging Subsystem Integration

Figure 95. Image Processing Components




15.3.1 CPU Core

The CPU core augments the signal processing capabilities of the hardware to perform post-processing on images such as auto focus, auto white balance, and auto exposure. The CPU also runs the drivers that control the GPIOs and I²C for sensor control.

15.3.2 Imaging Signal Processor (ISP)

The ISP (Imaging Signal Processor) includes a 64-way vector processor enabling high quality camera functionality. Key features include support of three camera sensors.



15.3.2.1 MIPI-CSI-2 Ports

The SoC has three MIPI clock lanes and five MIPI data lanes. The Analog Front End (AFE) and Digital Physical Layer (DPHY) take these lanes and connects them to three virtual ports. Two data lanes are dedicated to each of the rear facing cameras and the remaining one data lane is connected to the front facing camera. The MIPI interfaces follow the MIPI-CSI-2 specifications as defined by the MIPI Alliance. They support YUV420, YUV422, RGB444, RGB555, RGB565, RGB 888 and RAW 8b/10b/12b. Both MIPI ports support compression settings specified in MIPI-CSI-2 draft specification 1.01.00 Annex E. The compression is implemented in Hardware with support for Predictor 1 and Predictor 2. Supported compression schemes:


- 12-8-12
- 12-7-12
- 12-6-12
- 10-8-10
- 10-7-10
- 10-6-10

The data compression schemes above use an X-Y-Z naming convention where X is the number of bits per pixel in the original image, Y is the encoded (compressed) bits per pixel and Z is the decoded (uncompressed) bits per pixel.

15.3.2.2 Camera Sideband for Camera Interface

Twelve (12) GPIO signals are allocated for camera functions, refer to [Table 177](#) for signal names. These GPIOs are multiplexed and are available for other usages without powering on the ISP. The ISP provides a timing control block through which the GPIOs can be controlled to support assertion, de-assertion, pulse widths and delay. The configuration below of camera GPIOs is just an example of how the GPIOs can be used. Several of these functions could be implemented using I²C, depending on the sensor implementation for the platform.

- Sensor Reset signals
 - Force hardware reset on one or more of the sensors.
- Sensor Single Shot Trigger signal
 - Indicate that the target sensor needs to send a full frame in a single shot mode, or to capture the full frame for flash synchronization.
- PreLight Trigger signal
 - Light up a pilot lamp prior to firing the flash for preventing red-eye.
- Flash Trigger signal
 - Indicate that a full frame is about to be captured. The Flash fires when it detects an assertion of the signal.
- Sensor Strobe Trigger signal
 - Asserted by the target sensor to indicate the start of a full frame, when it is configured in the single shot mode, or to indicate a flash exposed frame for flash synchronization.



15.4 Functional Description

At a high level, the Camera Subsystem supports the following modes:

- Preview
- Image capture
- Video capture

15.4.1 Preview Mode

Once the ISP and the camera subsystem is enabled, the ISP goes into the preview mode where very low resolution frames, such as VGA/480p (programmable), are being processed.

15.4.2 Image Capture

During the image capture mode, the camera subsystem can acquire at a peak throughput of 24 Mpixels @ 15fps. While doing this, it continues to output preview frames simultaneously.

- The ISP can output RAW, RGB or YUV formats. The ISP can capture one full frame at a time or perform burst mode capture, where up to five full back-to-back frames are recorded.
- The ISP will not limit the number of back-to-back full frames captured, but the number is programmable and determined on how much memory can be allocated dynamically.
- The ISP can process all the frames on the fly and writes to memory only after fully processing the frames, without requiring download of any part of the frame for further processing.
 - The exceptions to this approach are image stabilization and some other advanced functions requiring temporal information over multiple frames.

The ISP can support image stabilization in image capture model.

- The ISP initially outputs preview frames.
- When the user decides to capture the picture, image stabilization is enabled. The ISP checks the previous frame for motion and compensates for it appropriately.


Auto Exposure (AE), Auto Focus (AF), and Auto White Balance (AWB), together known as 3A, are implemented in the CPU to provide flexibility.

15.4.3 Video Capture

During video recording, the ISP can capture video up to 1080p @ 60 fps and output preview frames concurrently. The ISP output video frames to memory in YUV420 or YUV422 format.

15.4.4 ISP Overview

The Camera Subsystem consists of 2 parts, the hardware subsystem and a software stack that implements the ISP functionality on top of this hardware.



The core of the ISP is a vector processor. The vector processor is supported by the following components:

- Interfaces for data and control
- A small input formatter that parallelizes the data
- A scalar (RISC) processor, for system control and low-rate processing
- An accelerator for scaling, digital zoom, and lens distortion correction
- A DMA engine transfers large amounts of data such as input and output image data or large parameter sets between LPDDR2 and the ISP block.

15.4.5 Memory Management Unit (MMU)

The camera subsystem has capabilities to deal with a virtual address space, since a contiguous memory range in the order 16–32MB cannot be guaranteed by the OS.

15.4.5.1 Interface

The MMU performs the lookup required for address translation from a virtual to physical 32-bit address. The lookup tables are stored external to the system. The MMU performs the lookup through a master interface without burst support that is connected to the Open Core Protocol (OCP) master of the subsystem. The MMU configuration registers can be accessed through a 32-bit Core I/O (CIO) slave interface. Additionally there is a 32-bit CIO slave interface connected to the address translator.

15.5 MIPI-CSI-2 Receiver


MIPI-CSI-2 devices are camera serial interface devices. They are categorized into two types, a CSI transmitter device with Camera Control Interface (CCI) slave and CSI receiver device with CCI master.

Data transfer by means of MIPI-CSI is unidirectional that is, from transmitter to receiver. CCI data transfer is bidirectional between the CCI slave and master.

Camera Serial Interface Bus (CSI) is a type of serial bus that enables transfer of data between a Transmitter device and a receiver device. The CSI device has a point-to-point connections with another CSI device by means of D-PHYs and as shown in Figure 96.

Similarly, CCI (Camera Control Interface bus) is a type of serial bus that enables transfer back and forth between the master CCI and a Slave CCI Unit.

Figure 96. MIPI-CSI Bus Block Diagram



D-PHY data lane signals are transferred point-to-point differentially using two signal lines and a clock lane. There are two signaling modes, a high speed mode that operates at 1000Mbps and a low power mode that works at 10Mbps. The mode is set to low power mode and a stop state at start up/power up. Depending on the desired data transfer type, the lanes switch between high and low power modes.



The CCI interface consists of an I²C bus which has a clock line and a bidirectional data line.

The MIPI-CSI-2 devices operate in a layered fashion. There are 5 layers identified at the receiver and transmitter ends.

MIPI-CSI-2 Functional Layers:

- **PHY Layer:**
 - An embedded electrical layer sends and detects start of packet signalling and end of packet signalling on the data lanes. It contains a serializer and deserializer unit to interface with the PPI / lane management unit. There is also a clock divider unit to source and receive the clock during different modes of operation.
- **PPI/Lane Management Unit:**
 - This layer does the lane buffering and distributes the data in the lanes as programmed in a round robin manner and also merges them for the PLI/Low Level Protocol unit.
- **PLI/Low Level Protocol Unit:**
 - This layer packetizes as well as de-packetizes the data with respect to channels, frames, colors and line formats. There are ECC generator and corrector units to recover the data free from errors in the packet headers. There is also a CRC checker or CRC generator unit to pack the payload data with CRC checksum bits for payload data protection.
- **Pixel/Byte to Byte/Pixel Packing Formats:**
 - Conversion of pixel formats to data bytes in the payload data is done depending on the type of image data supported by the application. It also re-converts the raw data bytes to pixel format understandable to the application layer.
- **Application:**
 - Depending on the type of formats, camera types, capability of the camera used by the transmitter, the application layer recovers the image formats and reproduces the image in the display unit. It also works on de-framing the data into pixel-to-packing formats. High level encoding and decoding of image data is handled in the application unit.

15.5.1 MIPI-CSI-2 Receiver Features

CSI Features:

- Compliant to CSI-2 MIPI specification for Camera Serial Interface (Version 1.00)
- Supports standard D-PHY transceiver compliant to the MIPI Specification
- Supports PHY data programmability up to four lanes.
- Supports PHY data time-out programming.
- Has controls to start and re-start the CSI-2 data transmission for synchronization failures and to support recovery.



- The ISP may not support all the data formats that the CSI-2 receiver can handle.
—Refer to [Table 178](#) for formats supported by the ISP
- Supports all generic short packet data types.
- Single Image Signal Processor interface for pixel transfers to support multiple image streams for all virtual channel numbers.


D-PHY Features:

- Supports synchronous transfer in high speed mode with a bit rate of 80-1000Mb/s
- Supports asynchronous transfer in low power mode with a bit rate of 10Mb/s.
- Differential signalling for HS data
- Spaced one-hot encoding for Low Power [LP] data
- Data lanes support transfer of data in high speed as well as low power modes.
- Supports ultra low power mode, escape mode, and high speed mode
- Has a clock divider unit to generate clock for parallel data reception and transmission from and to the PPI unit.
- Activates and disconnects high speed terminators for reception and control mode.
- Activates and disconnects low power terminators for reception and transmission.

15.6 Register Map

Refer to [Chapter 3, “Register Access Methods”](#) and [Chapter 4, “Mapping Address Spaces”](#) for additional information.

Figure 97. MIPI CSI Register Map



§



15.7 Image Signal Processor PCI Configuration Registers

Table 179. Summary of Image Signal Processor PCI Configuration Registers—0/2/0

Offset	Size	Register ID—Description	Default Value
0h	4	"iunit_ID_type (ID)—Offset 0h" on page 1059	0F388086h
4h	4	"iunit_PCICMDSTS_type (PCICMDSTS)—Offset 4h" on page 1059	00100000h
8h	4	"iunit_RIDCC_type (RIDCC)—Offset 8h" on page 1060	04800001h
Ch	4	"iunit_HDR_type (HDR)—Offset Ch" on page 1061	00000000h
10h	4	"iunit_ISPMADR_type (ISPMADR)—Offset 10h" on page 1061	00000000h
2Ch	4	"iunit_SSID_type (SSID)—Offset 2Ch" on page 1062	00000000h
34h	4	"iunit_CAPPOINT_type (CAPPOINT)—Offset 34h" on page 1062	00000080h
3Ch	4	"iunit_INTR_type (INTR)—Offset 3Ch" on page 1062	00000000h
80h	4	"iunit_PMCAP_type (PMCAP)—Offset 80h" on page 1063	00229001h
84h	4	"iunit_PMCS_type (PMCS)—Offset 84h" on page 1064	00000000h
90h	4	"iunit_MSI_CAPID_type (MSI_CAPID)—Offset 90h" on page 1064	00000005h
94h	4	"iunit_MSI_ADDRESS_type (MSI_ADDRESS)—Offset 94h" on page 1065	00000000h
98h	4	"iunit_MSI_DATA_type (MSI_DATA)—Offset 98h" on page 1066	00000000h
9Ch	4	"iunit_INTERRUPT_CONTROL_type (INTERRUPT_CONTROL)—Offset 9Ch" on page 1066	00000100h
B0h	4	"iunit_PERF0_type (PERF0)—Offset B0h" on page 1067	00000000h
B4h	4	"iunit_PERF1_type (PERF1)—Offset B4h" on page 1068	00000000h
B8h	4	"iunit_PERF2_type (PERF2)—Offset B8h" on page 1068	00000000h
BCh	4	"iunit_PERF3_type (PERF3)—Offset BCh" on page 1069	00000000h
C0h	4	"iunit_MISR0_type (MISR0)—Offset C0h" on page 1069	FFFFFFFFh
C4h	4	"iunit_MISR1_type (MISR1)—Offset C4h" on page 1070	FFFFFFFFh
C8h	4	"iunit_MISR2_type (MISR2)—Offset C8h" on page 1070	FFFFFFFFh
CCh	4	"iunit_MISR3_type (MISR3)—Offset CCh" on page 1071	FFFFFFFFh
D0h	4	"iunit_MANUFACTURING_ID_type (MANUFACTURING_ID)—Offset D0h" on page 1071	00000000h
D4h	4	"iunit_IUNIT_ACCESS_CTRL_VIOL_type (IUNIT_ACCESS_CTRL_VIOL)—Offset D4h" on page 1071	00000000h
D8h	4	"iunit_IUNIT_DEADLINE_STATUS_type (IUNIT_DEADLINE_STATUS)—Offset D8h" on page 1072	00000000h
DCh	4	"iunit_IUNIT_AFE_HS_CONTROL_type (IUNIT_AFE_HS_CONTROL)—Offset DCh" on page 1073	64000A00h
E0h	4	"iunit_IUNIT_AFE_RCOMP_CONTROL_type (IUNIT_AFE_RCOMP_CONTROL)—Offset E0h" on page 1074	00000000h
E4h	4	"iunit_IUNIT_AFE_TRIM_CONTROL_type (IUNIT_AFE_TRIM_CONTROL)—Offset E4h" on page 1075	00000000h
E8h	4	"iunit_IUNIT_CSI_CONTROL_type (IUNIT_CSI_CONTROL)—Offset E8h" on page 1076	000003F8h
ECh	4	"iunit_IUNIT_DEADLINE_CONTROL_type (IUNIT_DEADLINE_CONTROL)—Offset ECh" on page 1077	040A0100h



Bit Range	Default & Access	Description
31:21	0h RO	RSVD_31_21: Reserved
20	1b RO	CAP: CAPABILITY_LIST: Indicates that the CAPPOINT register at 34h provides an offset into PCI Configuration Space containing a pointer to the location of the first item in the list.
19	0b RO	IS: INTERRUPT_STATUS: Reflects the state of the interrupt in the camera device. Is set to 1 if IER and IIR are both set. Otherwise is set to 0.
18:11	0h RO	RSVD_18_11: Reserved
10	0b RW	ID: INTERRUPT_DISABLE: When 1, blocks the sending of ASSERT_INTA and DEASSERT_INTA messages to the Intel Legacy Block (ILB). The interrupt status is not blocked from being reflected in PCICMDSTS.IS. When 0, permits the sending of ASSERT_INTA and DEASSERT_INTA messages to the ILB.
9:3	0h RO	RSVD_9_3: Reserved
2	0h RW	BME: BUS_MASTER_ENABLE: Enables ISP to function as a PCI compliant master. When 0, blocks the sending of MSI interrupts. When 1, permits the sending of MSI interrupts.
1	0h RW	MSE: MEMORY_SPACE_ENABLE: When set, accesses to this device's memory space is enabled. When 1, the ISP will compare the incoming address on the IOSF bus with ISPMADDR(31:22). If there is a match and if the IOSF command is either a MEMRD or MEMWR, the ISP will select the command and present it on the AHB bus. When 0, the ISP will not claim MEMRD or MEMWR IOSF commands.
0	0h RO	RSVD_0_0: Reserved

15.7.3 iunit_RIDCC_type (RIDCC)—Offset 8h

Revision Identification and Class Codes

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

RIDCC: [B:0, D:3, F:0] + 8h

Default: 04800001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
BCC				SCC				PID

Bit Range	Default & Access	Description
31:24	04h RO	BCC: BASE_CLASS_CODE: Indicates a multimedia device.
23:16	80h RO	SCC: SUB_CLASS_CODE: Indicates other multimedia device.
15:8	0h RO	PI: PROGRAMMING_INTERFACE: Default programming interface.
7:0	01h RO	RID: REVISION_ID: The value in this field reflects the value of strapRID(7:0) (which is an input pin of ISP) and can be changed with each stepping of the silicon.



Bit Range	Default & Access	Description
21:0	0h RO	RSVD_21_0: Reserved

15.7.6 iunit_SSID_type (SSID)—Offset 2Ch

Subsystem Identifiers

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SSID: [B:0, D:3, F:0] + 2Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSID

Bit Range	Default & Access	Description
31:0	0h RO	SSID: SUBSYSTEM_IDENTIFIERS: The value in this field is a copy of the SSID register programmed by the graphics device driver or BIOS in the Device 0/2/0 PCI header. To change the subsystem ID, write to Device 0/2/0 SSID instead of to this SSID.

15.7.7 iunit_CAPPOINT_type (CAPPOINT)—Offset 34h

Capabilities Pointer

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

CAPPOINT: [B:0, D:3, F:0] + 34h

Default: 00000080h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

RSVD_31_8

CAP

Bit Range	Default & Access	Description
31:8	0h RO	RSVD_31_8: Reserved
7:0	80h RO	CAP: CAPABILITIES_POINTER: The first item in the capabilities list is at address 80h.

15.7.8 iunit_INTR_type (INTR)—Offset 3Ch

Interrupt. This register is programmed by SBIOS.

Power Management Control/Status.

Type: PCI Configuration Register
(Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:2	0h RO	RSVD_31_2: Reserved
1:0	0h RW	PS: POWER_STATE: Power management is implemented by writing to control registers in the PUNIT. This field may be programmed by the software driver, but no action is taken based on writing to this field.

15.7.11 iunit_MSI_CAPID_type (MSI_CAPID)—Offset 90h

Message Signaled Interrupts Capability ID and Control Register

Type: PCI Configuration Register
(Size: 32 bits)

Default: 00000005h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
RSVD_31_24				C64	MME	MMC	MSIE	NEXT_CAP
								CAPID

Bit Range	Default & Access	Description
31:24	0h RO	RSVD_31_24: Reserved
23	0h RO	C64: 64_BIT_ADDRESS_CAPABLE: 32-bit capable only.
22:20	0h RW	MME: MULTIPLE_MESSAGE_ENABLE: This field is RW for software compatibility, but only a single message is ever generated.
19:17	0h RO	MMC: MULTIPLE_MESSAGE_CAPABLE: This device is only single message capable.
16	0h RW	MSIE: MSI_ENABLE: If set, MSI is enabled. PCICMDSTS.BME must be set for an MSI to be generated. When 0, blocks the sending of a MSI interrupt. The interrupt status is not blocked from being reflected in the PCICMDSTS.IS bit. When 1, permits sending of a MSI interrupt.
15:8	0h RO	NEXT_CAP: POINTER_TO_NEXT_CAPABILITY: Indicates this is the last item in the list.
7:0	05h RO	CAPID: CAPABILITY_ID: Indicates an MSI capability.

15.7.12 iunit_MSI_ADDRESS_type (MSI_ADDRESS)—Offset 94h

MSI Message Address

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MSI_ADDRESS: [B:0, D:3, F:0] + 94h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MA								RSVD_1_0

Bit Range	Default & Access	Description
31:2	0h RW	MA: MSI_ADDRESS: System specified message address, always DW aligned. When the ISP issues an MSI interrupt as a MEMWR on the IOSF, the memory address used is 12xFEE, MSI_ADDRESS[19:0].
1:0	0h RO	RSVD_1_0: Reserved



15.7.13 iunit_MSI_DATA_type (MSI_DATA)—Offset 98h

MSI Message Data

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MSI_DATA: [B:0, D:3, F:0] + 98h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD_31_16				MD				

Bit Range	Default & Access	Description
31:16	0h RO	RSVD_31_16: Reserved
15:0	0h RW	MD: MSI_DATA: This 16-bit field is programmed by system software and is driven onto the lower word of data during the data phase of the MSI write transaction. When the ISP issues an MSI interrupt as a MEMWR on the IOSF, the write data corresponds to the value of this field.

15.7.14 iunit_INTERRUPT_CONTROL_type (INTERRUPT_CONTROL)—Offset 9Ch

INTERRUPT_CONTROL

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

INTERRUPT_CONTROL: [B:0, D:3, F:0] + 9Ch

Default: 00000100h

31				28				24				20				16				12				8				4				0							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0								
RSVD_31_25								IER		RSVD_23_17								IIR		RSVD_15_9								IMR		RSVD_7_1								ISR	

Bit Range	Default & Access	Description
31:25	0h RO	RSVD_31_25: Reserved



Bit Range	Default & Access	Description
24	0h RW	IIR: IER: This is an enable bit that allows the sending of an interrupt to the CPU using either MSI or INTR mechanisms. The interrupt is sent immediately to the CPU. The firmware running on the ISP guarantees ordering by reading the last data write from memory before raising the interrupt. 1 = If MSI_ENABLE is set, then an MSI is sent to the CPU when the IIR bit is set, or if the IIR bit remains set after software writes to this register. If INTERRUPT_DISABLE is not set, then an ASSERT_INTA message is sent to the Intel Legacy Block (ILB) when the IIR bit is set by hardware, or if the IIR bit remains set after software writes to this register. If software clears the IIR bit, and INTERRUPT_DISABLE is not set then a DEASSERT_INTA message is sent to the ILB. 0 = Do not generate an MSI even if the MSI_ENABLE bit is set. Do not send ASSERT_INTA or DEASSERT_INTA messages to the ILB even if the INTERRUPT_DISABLE bit is not set.
23:17	0h RO	RSVD_23_17: Reserved
16	0h RW/1C	IIR: IIR: This is the persistent value of the interrupt bit. It is set by hardware, and cleared by software. Software must write a 1 to clear this bit. Writing a 0 is a NOP. If both software and hardware attempt to write to this field in the same clock cycle, hardware wins. 1 = An interrupt was received from the vendor IP when the IMR bit was not set, and software has not yet cleared it. 0 = There is no pending interrupt.
15:9	0h RO	RSVD_15_9: Reserved
8	1b RW	IMR: IMR: Interrupt Mask bit. 1 = IIR bit will not be set when the ISR bit is set. 0 = IIR bit will be set when the ISR bit is set.
7:1	0h RO	RSVD_7_1: Reserved
0	0h RO	ISR: ISR: Reflects the state of the interrupt line from the vendor IP, after it is synchronized to the cclk domain.

15.7.15 iunit_PERF0_type (PERF0)—Offset B0h

Performance

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PERF0: [B:0, D:3, F:0] + B0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

CRIFLO

Bit Range	Default & Access	Description
31:0	0h RW/SE	CRIFLO: IUNIT has four performance counters. When counting is enabled, the 11-bit reads_in_flight counter keeps track of the number of outstanding reads that have been requested, but not yet returned back at the OCP master interface. The 11-bit max_reads_in_flight counter keeps track of the maximum number of reads in flight in any given clock cycle. Each clock cycle, if there are any reads in flight, the reads_in_flight counter is added to a 64-bit cumulative_reads_in_flight counter, and the 48-bit active_cycles counter is incremented by 1. Reading this register returns bits 31:0 of the cumulative_reads_in_flight counter. This counter should be read only after counting is disabled. Reading while the counters are enabled will return undefined values. All four counters are disabled at reset. Writing (any value) to this register, will enable all four counters.



31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
MISR0								

Bit Range	Default & Access	Description
31:0	FFFFFFFFh RW/C	MISR0: MISR0: Write to this register address clears this MISR. This is a 8:1 compression MISR capturing the 256-bit write data on the OCP interface between ISP_CSS and Iunit wrapper.

15.7.20 iunit_MISR1_type (MISR1)—Offset C4h

OCF Master Read Data

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MISR1: [B:0, D:3, F:0] + C4h

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
MISR1								

Bit Range	Default & Access	Description
31:0	FFFFFFFFh RW/C	MISR1: MISR1: Write to this register address clears this MISR. This is a 8:1 compression MISR capturing the 256-bit read return data on the OCP interface between ISP_CSS and Iunit wrapper.

15.7.21 iunit_MISR2_type (MISR2)—Offset C8h

OCF Master Address and Control

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MISR2: [B:0, D:3, F:0] + C8h

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
MISR2								

Bit Range	Default & Access	Description
31:0	FFFFFFFFh RW/C	MISR2: MISR2: Write to this register address clears this MISR. This is a 4:1 compression MISR capturing the control signals on the OCP Master port in the Iunit.



15.7.22 iunit_MISR3_type (MISR3)—Offset CCh

Scalar Processor output

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MISR3: [B:0, D:3, F:0] + CCh

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
MISR3								

Bit Range	Default & Access	Description
31:0	FFFFFFFh RW/C	MISR3: MISR3: Write to this register address clears this MISR. This is a 4:1 compression MISR capturing the output signals of the Scalar Processor.

15.7.23 iunit_MANUFACTURING_ID_type (MANUFACTURING_ID)—Offset D0h

Manufacturing ID

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MANUFACTURING_ID: [B:0, D:3, F:0] + D0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD_31_24				MID				

Bit Range	Default & Access	Description
31:24	0h RO	RSVD_31_24: Reserved
23:0	0h RO	MID: MANUFACTURING_ID: Hardwired to strapMANID(23:0).


15.7.24 iunit_IUNIT_ACCESS_CTRL_VIOL_type (IUNIT_ACCESS_CTRL_VIOL)—Offset D4h

IUNIT Access control violation register

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

IUNIT_ACCESS_CTRL_VIOL: [B:0, D:3, F:0] + D4h



Bit Range	Default & Access	Description
31	0b RW	EN_INTR_ACCESS_CTRL_VIOL: Enable Interrupt on access control violation: When set, the IUNIT will latch violation information into this register and send an interrupt request (opcode 0XEE) and (port 0x04) to the PUNIT.
30:21	00h RO	RSVD_30_21: Reserved
20	0b RW	SAI_VIOL: SAI_VIOL: If set, the IUNIT has detected an SAI violation and has captured the status in this register. This bit must be cleared by software in order for IUNIT to capture the next violation.
19	0b RW	MULTIPLE_SAI_VIOL: If set, more than one SAI violation has been detected in the IUNIT. Status for the 1st violation has been captured in this register. It is recommend that software clear this bit whenever it clears bit[20] of this register.
18:15	0h RO	RSVD_18_15: Reserved
14:8	00h RW	VIOL_SAI: VIOL_SAI: SAI bits that triggered the violation: This 7-bit value indicates the SAI of the subsequent transaction which caused the violation.
7	0b RO	RSVD_7_7: Reserved
6:0	00h RW	INITIAL_SAI: INITIAL_SAI: This 7-bit value indicates the SAI of the initial transaction for SAI mismatch error codes.

IUNIT Deadline Status Register

Type: PCI Configuration Register
(Size: 32 bits)

IUNIT_DEADLINE_STATUS: [B:0, D:3, F:0] + D8h

Default: 00000000h





Bit Range	Default & Access	Description
31:24	64h RW	HS_CLK_UNGATE_DLY: HS_CLK_UNGATE_DLY: Delay between the assertion of HS enable and the ungating of the HS clocks going to the DPHY logic for all clock lanes. HS clocks are gated by default and are ungated after Tclk-settle time. The range of this field is 0 nsec to 510 nsec in increments of 2 nsec, with reset value 0x64 indicating 200 nsec. Note that we use czclk to increment the counter, hence the actual delay can be as much as 10 nsec larger than the programmed value.
23:22	0h RW	RSVD_23_22: Reserved
21:20	00b RW	CSI3_CLK_HS_TERM_OVRD: CSI3_CLK_HS_TERM_OVRD: Override for HS termination enable for CSI3 clock lane. 00b = Use the termination enable output from the DPHY IP and gate XOR clocks in high speed mode; 01b = Keep HS termination (and HS enable) always on; 10b = Generate HS termination by sampling the CP/CN lines using coreclk and gate XOR clocks in high speed mode; 11b = Use the termination enable output from the DPHY IP;
19:18	00b RW	CSI2_CLK_HS_TERM_OVRD: CSI2_CLK_HS_TERM_OVRD: Override for HS termination enable for CSI2 clock lane. 00b = Use the termination enable output from the DPHY IP and gate XOR clocks in high speed mode; 01b = Keep HS termination (and HS enable) always on; 10b = Generate HS termination by sampling the CP/CN lines using coreclk and gate XOR clocks in high speed mode; 11b = Use the termination enable output from the DPHY IP;
17:16	00b RW	CSI1_CLK_HS_TERM_OVRD: CSI1_CLK_HS_TERM_OVRD: Override for HS termination enable for CSI1 clock lane. 00b = Use the termination enable output from the DPHY IP and gate XOR clocks in high speed mode; 01b = Keep HS termination (and HS enable) always on; 10b = Generate HS termination by sampling the CP/CN lines using coreclk and gate XOR clocks in high speed mode; 11b = Use the termination enable output from the DPHY IP;
15:8	0Ah RW	HS_CLK_EN_DLY: HS_CLK_EN_DLY: Delay between the assertion of HS termination enable and the assertion of HS enable for all clock lanes. The range of this field is 0 nsec to 510 nsec in increments of 2 nsec, with reset value 0x0A indicating 20 nsec. Note that we use czclk to increment the counter, hence the actual delay can be as much as 10 nsec larger than the programmed value.
7:0	0h RW	HS_DATA_EN_DLY: HS_DATA_EN_DLY: Delay between the assertion of HS termination enable and the assertion of HS enable for all data lanes. The range of this field is 0 nsec to 510 nsec in increments of 2 nsec, with reset value 0x0 indicating 0 nsec. Note that we use czclk to increment the counter, hence the actual delay can be as much as 10 nsec larger than the programmed value.

15.7.27 iunit_IUNIT_AFE_RCOMP_CONTROL_type (IUNIT_AFE_RCOMP_CONTROL)—Offset E0h


AFE RCOMP control

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

IUNIT_AFE_RCOMP_CONTROL: [B:0, D:3, F:0] + E0h

Default: 00000000h



15.7.28 iunit_IUNIT_AFE_TRIM_CONTROL_type (IUNIT AFE TRIM CONTROL)—Offset E4h

IUNIT AFE TRIM CONTROL: [B:0, D:3, F:0] + E4h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
ICS13_HSRXCLKTRIM				ICS12_HSRXCLKTRIM				ICS12_HSRXDATA1TRIM				ICS11_HSRXCLKTRIM												ICS11_HSRXDATA1TRIM											

Intel Atom® Processor E3800 Product Family
Datasheet
1075





Bit Range	Default & Access	Description
1:0	0h RW	DS: DEADLINE_SCHEME: 11b = Reserved; 10b = Reserved; 01b = When WAKEUP is asserted, FDD is added to the current global timer to compute DN. With each request, the deadline sent to Pondicherry is either DN, or the sum of the global timer and MDD, whichever is larger. After each request is sent, DN is computed by adding DI for each 32Byte request sent to either DN or the sum of the global timer and MDD, whichever is larger. Each clock cycle, DN is checked to make sure it is greater than the current global timer, else it is set to the global timer.; 00b = When WAKEUP is asserted, FDD is added to the current global timer to compute DN. With each request, the deadline sent to Pondicherry is either DN, or the sum of the global timer and MDD, whichever is larger. After each request is sent, DN is computed by adding DI for each 32Byte request sent to DN. Each cycle, DN is checked to make sure that it is either greater than the current global timer, or is less than the global timer by no more than 64 usec, else it is set to the global timer minus 64 usec.

15.7.31 iunit_IUNIT_RCOMP_STATUS_type (IUNIT_RCOMP_STATUS)—Offset F0h

IUNIT RCOMP Status Register

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

IUNIT_RCOMP_STATUS: [B:0, D:3, F:0] + F0h

Default: 16161616h

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
0				0				0				1				0				0				0				1				0				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1				0				0				1			

Bit Range	Default & Access	Description
31	0b RO	CALIB_EXIT_TOGGLE_LIMIT: CALIB_EXIT_TOGGLE_LIMIT: If set, indicates that the last calibration cycle exited because the number of toggles matched the value specified by the CSI_HS_ROGGLE_LIMIT_CREG_ENC field of the IUNIT_RCOMP_CONTROL register.
30:24	16h RO	CSI3_RCOMP_UPDATE_VALUE: MIPI CSI3 RCOMP value: Current RCOMP value on MIPI CSI3 port
23	0b RO	CALIB_EXIT_0101: CALIB_EXIT_0101: If set, indicates that the last calibration cycle exited because the last four states of rcompcountup were 0101
22:16	16h RO	CSI2_RCOMP_UPDATE_VALUE: MIPI CSI2 RCOMP value: Current RCOMP value on MIPI CSI2 port
15	0b RO	CALIB_EXIT_1010: CALIB_EXIT_1010: If set, indicates that the last calibration cycle exited because the last four states of rcompcountup were 1010



Bit Range	Default & Access	Description
14:8	16h RO	CSI1_RCOMP_UPDATE_VALUE: MIPI CSI1 RCOMP value: Current RCOMP value on MIPI CSI1 port
7	0b RO	CALIB_EXIT_ERROR: CALIB_EXIT_ERROR: If set, indicates that the last calibration cycle exited due to an error condition.
6:0	16h RO	CSI_RCOMP_CALIBRATION_VALUE: MIPI CSI RCOMP value from last calibration cycle

15.7.32 iunit_IUNIT_RCOMP_CONTROL_type (IUNIT_RCOMP_CONTROL)—Offset F4h

MIPI CSI RCOMP control register

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

IUNIT_RCOMP_CONTROL: [B:0, D:3, F:0] + F4h

Default: 00200001h

31	28	24	20	16	12	8	4	0					
0	0	0	0	0	0	0	0	1					
RSVD_31_24				CSI_HS_OVR_CLK_GATE_ON_UPDATE	CSI_HS_RCOMP_UPDATE_MODE	CSI_HS_TOGGLE_LIMIT_CREG_ENC	CSI_HS_CALIB_LOOP_DELAY	RSVD_15_11	CSI3_HS_RCOMP_OVR_ENABLE	CSI2_HS_RCOMP_OVR_ENABLE	CSI1_HS_RCOMP_OVR_ENABLE	CSI_HS_RCOMP_OVR_CODE	CSI_HS_RCOMP_ENABLE

Bit Range	Default & Access	Description
31:24	0h RW	RSVD_31_24: Reserved
23	0b RW	CSI_HS_OVR_CLK_GATE_ON_UPDATE: CSI_HS_OVR_CLK_GATE_ON_UPDATE: If cleared, the high speed clock going to the digital logic is gated when RCOMP update is happening. The clock is gated for a minimum of 100 nsec. If this bit is set, then the high speed clock is not gated during the update cycle.
22:21	01b RW	CSI_HS_RCOMP_UPDATE_MODE: CSI_HS_RCOMP_UPDATE_MODE: 00b = RCOMP is updated if the clock lane is in LP11 state. 01b = RCOMP is updated if all the data lanes are in LP11 state. 10b = RCOMP is updated immediately after calibration is completed, or the CSI[1-3]_HS_RCOMP_OVR_ENABLE bits are written to 1 by software. 11b = Reserved.
20:19	0h RW	CSI_HS_TOGGLE_LIMIT_CREG_ENC: CSI_HS_TOGGLE_LIMIT_CREG_ENC: HS state machine toggle limit. Number of times RCOMP state machine will toggle before exiting. 2'b00: 6 toggles; 2'b01: 4 toggles; 2'b10: 8 toggles; 2'b11: 10 toggles;



Bit Range	Default & Access	Description
18:16	0h RW	CSI_HS_CALIB_LOOP_DELAY: CSI_HS_CALIB_LOOP_DELAY: Delay after applying a new RCOMP value to the AFE, before sampling the count up/down input from the AFE. 0h=)50-53ns; 1h=)60ns; 2h=)70-72ns; 3h=)80-83ns; 4h=)90ns; 5h=)100-102ns; 6h=)125-128ns; 7h=)150ns. At the start of each RCOMP calibration cycle, the state machine waits for 8x this delay before starting to sample the count up/down signal.
15:11	0h RW	RSVD_15_11: Reserved
10	0b RW	CSI3_HS_RCOMP_OVR_ENABLE: CSI3_HS_RCOMP_OVR_ENABLE: If set, then the CSI_HS_RCOMP_OVRD field is used as the RCOMP value during the update cycle for CSI port 3. If clear, then the output of the RCOMP calibration engine (stored in CSI_RCOMP_CALIBRATION_VALUE field of IUNIT_RCOMP_STATUS register) is used as the RCOMP value during the update cycle for CSI port 3.
9	0b RW	CSI2_HS_RCOMP_OVR_ENABLE: CSI2_HS_RCOMP_OVR_ENABLE: If set, then the CSI_HS_RCOMP_OVRD field is used as the RCOMP value during the update cycle for CSI port 2. If clear, then the output of the RCOMP calibration engine (stored in CSI_RCOMP_CALIBRATION_VALUE field of IUNIT_RCOMP_STATUS register) is used as the RCOMP value during the update cycle for CSI port 2.
8	0b RW	CSI1_HS_RCOMP_OVR_ENABLE: CSI1_HS_RCOMP_OVR_ENABLE: If set, then the CSI_HS_RCOMP_OVRD field is used as the RCOMP value during the update cycle for CSI port 1. If clear, then the output of the RCOMP calibration engine (stored in CSI_RCOMP_CALIBRATION_VALUE field of IUNIT_RCOMP_STATUS register) is used as the RCOMP value during the update cycle for CSI port 1.
7:1	0h RW	CSI_HS_RCOMP_OVR_CODE: CSI_HS_RCOMP_OVR_CODE: Software defined value to use as the RCOMP value for CSI[1-3] ports if the CSI[1-3]_HS_RCOMP_OVR_ENABLE fields are set.
0	1b RW	CSI_HS_RCOMP_ENABLE: CSI_HS_RCOMP_ENABLE: Enable CSI HS RCOMP. (Note: This bit does not affect the initial RCOMP at the de-assertion of reset which is controlled by the fuse FB_disable_initial_RCOMP.)

15.7.33 iunit_IUNIT_STATUS_type (IUNIT_STATUS)—Offset F8h

IUNIT Status Register

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

IUNIT_STATUS: [B:0, D:3, F:0] + F8h

Default: 0000EB01h

31				28				24				20				16				12				8				4				0																			
0				0				0				0				0				1				1				0				0				0				0				0				1			
RSVD_31_18																ISCLK				CZCLK				RSVD_7_7				TCGSM				RSVD_3_3				LCGSM				ISP_BUSY											


Bit Range	Default & Access	Description
31:18	0h RO	RSVD_31_18: Reserved
17:13	07h RO	ISCLK: Reflects the value of cck_isp_isclk_ratio_zcznfwh input pin.
12:8	0Bh RO	CZCLK: Reflects the value of cck_XXX_czclk_ratio_zcznfwh input pin.



Bit Range	Default & Access	Description
28:24	0h RW	PERF_MASK: PERF_MASK: This field determines the amount of performance throttling applied to ispclk. The value of this field determines how many beat periods of ispclk are killed, where a beat period is defined as 16 ispclk cycles. A 16 cycle period was chosen to make the throttling independent of the actual clock ratio between ispclk and coreclk. Note that clock gating should be enabled when thermal throttling is enabled.
23:22	0h RW	RSVD_23_22: Reserved
21	0h RW	DISABLE_ISM_IDLE_FREEZE: DISABLE_ISM_IDLE_FREEZE: When IUNIT receive a RESET_WARN message from PUNIT, it will freeze the IOSF primary Idle State Machine (among other things), before sending an OK_TO_RESET message to PUNIT. If the DISABLE_ISM_IDLE_FREEZE bit is set, IUNIT will not freeze the ISM in the IDLE state as part of this reset sequence.
20	0h RW	DISABLE_OCP_PHASE_ORDERING: DISABLE_OCP_PHASE_ORDERING: By default, IUNIT will follow the OCP phase ordering protocol and wait until a write command is accepted before accepting the write data corresponding to that command. If the DISABLE_OCP_PHASE_ORDERING bit is set, the IUNIT wrapper will accept the write data independent of the write command.
19	0h RW	ICACHE_CMD_WEIGHT: ICACHE_CMD_WEIGHT: 0b = Requests from the OCP master port sending Icache miss traffic will win arbitration over requests from the OCP master port that sends pixel data traffic. 1b = Requests from the two OCP master interfaces will be accepted in a round robin fashion.
18:16	0h RW	THERM_MASK: THERM_MASK: This field determines the amount of thermal throttling applied to ispclk. The value of this field determines how many beat periods of ispclk are killed, where a beat period is defined as 16 ispclk cycles. A 16 cycle period was chosen to make the throttling independent of the actual clock ratio between ispclk and coreclk. 000 = No throttling; 001 = 12.5% throttling; 010 = 25% throttling; 011 = 37.5% throttling; 100 = 50% throttling; 101 = 62.5% throttling; 110 = 75% throttling; 111 = 87.5% throttling;
15:8	01h RW	MID: MIN_IDLE_DELAY: Minimum wait time after the rising edge of idle, before the clock gating state machine will start the sequence to gate ispclk. Range is 0 to 130 usec. Unit is 0.512 usec. Reset value of 8'h1 indicates MID = 0.512 usec.
7	0b RW	RCOMPCLK_GATING_DISABLE: 1 = Disable clock gating for rcompclk. 0 = Enable clock gating for rcompclk. Note: All clock gating is disabled by hardware while reset is asserted, regardless of the state of this field.
6:5	00b RW	ISPCLK_GATING_DISABLE: ISPCLK_GATING_DISABLE: 11 = Disable local clock gating and trunk clock gating for ispclk.; 10 = Enable local clock gating for ispclk, but disable trunk clock gating.; 01 = Reserved; 00 = Enable local clock gating and trunk clock gating for ispclk. Note: All clock gating is disabled by hardware while reset is asserted, regardless of the state of this field.
4	0b RW	DDMA: 1 = Disable DMA. Stop sending any requests on the IB PFI port. 0 = Enable DMA. IB PFI port operates normally.
3:2	0h RW	SRSE: SOFT_RESET_SEQUENCE_ENABLE: If SRSE=2b00: When an IUNIT_RESET_WARN message is received from PUNIT, IUNIT will a) stop accepting requests on the IOSF primary interface, b) stop accepting new requests from the OCP master interface, c) wait until read data from all earlier read requests received from the OCP master interface have been returned by SSA, d) wait until SSA reads data for all earlier PFI write requests, and e) wait for all DPHY lanes to enter stop state (LP11), and then f) send an IUNIT_OK_TO_RESET posted message to PUNIT. If SRSE=2b01: When an IUNIT_RESET_WARN message is received from PUNIT, IUNIT will a) stop accepting requests on the IOSF primary interface, b) stop accepting new requests from the OCP master interface, c) wait until read data from all earlier read requests received from the OCP master interface have been returned by SSA, d) wait until SSA reads data for all earlier PFI write requests, and then e) send an IUNIT_OK_TO_RESET posted message to PUNIT. If SRSE=2b10: When an IUNIT_RESET_WARN message is received from PUNIT, IUNIT will wait for all DPHY lanes to enter stop state (LP11), and then send an IUNIT_OK_TO_RESET posted message to PUNIT. If SRSE=2b11: When an IUNIT_RESET_WARN message is received from PUNIT, IUNIT will immediately send an IUNIT_OK_TO_RESET posted message to PUNIT.



Bit Range	Default & Access	Description
1	1b RW	IBEWC: IB_ENABLE_WRITE_COMBINING: When set, enables the combining of adjacent 32-byte write requests to the same cache line. When cleared, each 32-byte write request is sent as a separate request on the IB interface.
0	1b RW	IBERC: IB_ENABLE_READ_COMBINING: When set, enables the combining of adjacent 32-byte read requests to the same cache line. When cleared, each 32-byte read request is sent as a separate request on the IB interface.



15.8 Image Signal Processor Memory Mapped IO Registers

Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR

Offset	Size	Register ID—Description	Default Value
0h	4	"reg_gpd_gp_reg_reg_gp_sdram_wakeup_type (gpd_gp_reg_reg_gp_sdram_wakeup)—Offset 0h" on page 1124	00000000h
4h	4	"reg_gpd_gp_reg_reg_gp_idle_type (gpd_gp_reg_reg_gp_idle)—Offset 4h" on page 1125	00000000h
8h	4	"reg_gpd_gp_reg_reg_gp_irq_req0_type (gpd_gp_reg_reg_gp_irq_req0)—Offset 8h" on page 1126	00000000h
Ch	4	"reg_gpd_gp_reg_reg_gp_irq_req1_type (gpd_gp_reg_reg_gp_irq_req1)—Offset Ch" on page 1126	00000000h
10h	4	"reg_gpd_gp_reg_reg_gp_sp_stream_stat_type (gpd_gp_reg_reg_gp_sp_stream_stat)—Offset 10h" on page 1127	00022022h
14h	4	"reg_gpd_gp_reg_reg_gp_sp_stream_stat_b_type (gpd_gp_reg_reg_gp_sp_stream_stat_b)—Offset 14h" on page 1129	00000000h
18h	4	"reg_gpd_gp_reg_reg_gp_isp_stream_stat_type (gpd_gp_reg_reg_gp_isp_stream_stat)—Offset 18h" on page 1131	02200000h
1Ch	4	"reg_gpd_gp_reg_reg_gp_mod_stream_stat_type (gpd_gp_reg_reg_gp_mod_stream_stat)—Offset 1Ch" on page 1133	AA88A222h
20h	4	"reg_gpd_gp_reg_reg_gp_sp_stream_stat_irq_cond_type (gpd_gp_reg_reg_gp_sp_stream_stat_irq_cond)—Offset 20h" on page 1135	00000000h
24h	4	"reg_gpd_gp_reg_reg_gp_sp_stream_stat_b_irq_cond_type (gpd_gp_reg_reg_gp_sp_stream_stat_b_irq_cond)—Offset 24h" on page 1136	00000000h
28h	4	"reg_gpd_gp_reg_reg_gp_isp_stream_stat_irq_cond_type (gpd_gp_reg_reg_gp_isp_stream_stat_irq_cond)—Offset 28h" on page 1137	00000000h
2Ch	4	"reg_gpd_gp_reg_reg_gp_mod_stream_stat_irq_cond_type (gpd_gp_reg_reg_gp_mod_stream_stat_irq_cond)—Offset 2Ch" on page 1137	00000000h
30h	4	"reg_gpd_gp_reg_reg_gp_sp_stream_stat_irq_enable_type (gpd_gp_reg_reg_gp_sp_stream_stat_irq_enable)—Offset 30h" on page 1138	00000000h
34h	4	"reg_gpd_gp_reg_reg_gp_sp_stream_stat_b_irq_enable_type (gpd_gp_reg_reg_gp_sp_stream_stat_b_irq_enable)—Offset 34h" on page 1139	00000000h
38h	4	"reg_gpd_gp_reg_reg_gp_isp_stream_stat_irq_enable_type (gpd_gp_reg_reg_gp_isp_stream_stat_irq_enable)—Offset 38h" on page 1139	00000000h
3Ch	4	"reg_gpd_gp_reg_reg_gp_mod_stream_stat_irq_enable_type (gpd_gp_reg_reg_gp_mod_stream_stat_irq_enable)—Offset 3Ch" on page 1140	00000000h
40h	4	"reg_gpd_gp_reg_reg_gp_switch_if_type (gpd_gp_reg_reg_gp_switch_if)—Offset 40h" on page 1141	00000000h
44h	4	"reg_gpd_gp_reg_reg_gp_switch_gdc1_type (gpd_gp_reg_reg_gp_switch_gdc1)—Offset 44h" on page 1142	00000000h
48h	4	"reg_gpd_gp_reg_reg_gp_switch_gdc2_type (gpd_gp_reg_reg_gp_switch_gdc2)—Offset 48h" on page 1142	00000000h
4Ch	4	"reg_gpd_gp_reg_reg_gp_srst_type (gpd_gp_reg_reg_gp_srst)—Offset 4Ch" on page 1143	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
50h	4	"reg_gpd_gp_reg_reg_gp_slv_reg_srst_type (gpd_gp_reg_reg_gp_slv_reg_srst)—Offset 50h" on page 1145	00000000h
100h	4	"reg_gpd_tc_FifoWriteCmd_type (gpd_tc_FifoWriteCmd)—Offset 100h" on page 1146	00000000h
400h	4	"reg_gpd_c_gpio_reg_gpio_doe_type (gpd_c_gpio_reg_gpio_doe)—Offset 400h" on page 1146	00000000h
404h	4	"reg_gpd_c_gpio_reg_gpio_do_select_type (gpd_c_gpio_reg_gpio_do_select)—Offset 404h" on page 1147	00000000h
408h	4	"reg_gpd_c_gpio_reg_gpio_do_0_type (gpd_c_gpio_reg_gpio_do_0)—Offset 408h" on page 1147	00000000h
40Ch	4	"reg_gpd_c_gpio_reg_gpio_do_1_type (gpd_c_gpio_reg_gpio_do_1)—Offset 40Ch" on page 1148	00000000h
410h	4	"reg_gpd_c_gpio_reg_gpio_do_pwm_cnt_0_type (gpd_c_gpio_reg_gpio_do_pwm_cnt_0)—Offset 410h" on page 1148	00000000h
414h	4	"reg_gpd_c_gpio_reg_gpio_do_pwm_cnt_1_type (gpd_c_gpio_reg_gpio_do_pwm_cnt_1)—Offset 414h" on page 1149	00000000h
418h	4	"reg_gpd_c_gpio_reg_gpio_do_pwm_cnt_2_type (gpd_c_gpio_reg_gpio_do_pwm_cnt_2)—Offset 418h" on page 1150	00000000h
41Ch	4	"reg_gpd_c_gpio_reg_gpio_do_pwm_cnt_3_type (gpd_c_gpio_reg_gpio_do_pwm_cnt_3)—Offset 41Ch" on page 1150	00000000h
420h	4	"reg_gpd_c_gpio_reg_gpio_do_pwm_main_cnt_type (gpd_c_gpio_reg_gpio_do_pwm_main_cnt)—Offset 420h" on page 1151	00000000h
424h	4	"reg_gpd_c_gpio_reg_gpio_do_pwm_enable_type (gpd_c_gpio_reg_gpio_do_pwm_enable)—Offset 424h" on page 1152	00000000h
428h	4	"reg_gpd_c_gpio_reg_gpio_di_debouncemethod_type (gpd_c_gpio_reg_gpio_di_debouncemethod)—Offset 428h" on page 1152	00000000h
42Ch	4	"reg_gpd_c_gpio_reg_gpio_di_debounce_cnt0_type (gpd_c_gpio_reg_gpio_di_debounce_cnt0)—Offset 42Ch" on page 1153	00000000h
430h	4	"reg_gpd_c_gpio_reg_gpio_di_debounce_cnt1_type (gpd_c_gpio_reg_gpio_di_debounce_cnt1)—Offset 430h" on page 1154	00000000h
434h	4	"reg_gpd_c_gpio_reg_gpio_di_debounce_cnt2_type (gpd_c_gpio_reg_gpio_di_debounce_cnt2)—Offset 434h" on page 1154	00000000h
438h	4	"reg_gpd_c_gpio_reg_gpio_di_debounce_cnt3_type (gpd_c_gpio_reg_gpio_di_debounce_cnt3)—Offset 438h" on page 1155	00000000h
43Ch	4	"reg_gpd_c_gpio_reg_gpio_di_activelevel_type (gpd_c_gpio_reg_gpio_di_activelevel)—Offset 43Ch" on page 1155	00000FFFh
440h	4	"reg_gpd_c_gpio_reg_gpio_di_debouncemethod_type (gpd_c_gpio_reg_gpio_di_debouncemethod)—Offset 428h" on page 1152	00000FFFh
500h	4	"reg_gpd_irq_ctrl_reg_irq_edge_type (gpd_irq_ctrl_reg_irq_edge)—Offset 500h" on page 1157	00000000h
504h	4	"reg_gpd_irq_ctrl_reg_irq_mask_type (gpd_irq_ctrl_reg_irq_mask)—Offset 504h" on page 1157	00000000h
508h	4	"reg_gpd_irq_ctrl_reg_irq_status_type (gpd_irq_ctrl_reg_irq_status)—Offset 508h" on page 1157	00000000h
50Ch	4	"reg_gpd_irq_ctrl_reg_irq_clear_type (gpd_irq_ctrl_reg_irq_clear)—Offset 50Ch" on page 1159	00000000h
510h	4	"reg_gpd_irq_ctrl_reg_irq_enable_type (gpd_irq_ctrl_reg_irq_enable)—Offset 510h" on page 1159	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMADR (Continued)

Offset	Size	Register ID—Description	Default Value
514h	4	"reg_gpd_irq_ctrl_reg_irq_level_not_pulse_type (gpd_irq_ctrl_reg_irq_level_not_pulse)—Offset 514h" on page 1160	00000000h
518h	4	"reg_gpd_irq_ctrl_reg_irq_str_out_enable_type (gpd_irq_ctrl_reg_irq_str_out_enable)—Offset 518h" on page 1160	00000000h
600h	4	"reg_gpd_gptimer_reg_reset_type (gpd_gptimer_reg_reset)—Offset 600h" on page 1161	00000000h
604h	4	"reg_gpd_gptimer_overall_enable_type (gpd_gptimer_overall_enable)—Offset 604h" on page 1161	00000000h
608h	4	"reg_gpd_gptimer_enable_timer_0_type (gpd_gptimer_enable_timer_0)—Offset 608h" on page 1162	00000000h
60Ch	4	"reg_gpd_gptimer_enable_timer_1_type (gpd_gptimer_enable_timer_1)—Offset 60Ch" on page 1162	00000000h
610h	4	"reg_gpd_gptimer_enable_timer_2_type (gpd_gptimer_enable_timer_2)—Offset 610h" on page 1163	00000000h
614h	4	"reg_gpd_gptimer_enable_timer_3_type (gpd_gptimer_enable_timer_3)—Offset 614h" on page 1164	00000000h
618h	4	"reg_gpd_gptimer_enable_timer_4_type (gpd_gptimer_enable_timer_4)—Offset 618h" on page 1164	00000000h
61Ch	4	"reg_gpd_gptimer_enable_timer_5_type (gpd_gptimer_enable_timer_5)—Offset 61Ch" on page 1165	00000000h
620h	4	"reg_gpd_gptimer_enable_timer_6_type (gpd_gptimer_enable_timer_6)—Offset 620h" on page 1165	00000000h
624h	4	"reg_gpd_gptimer_enable_timer_7_type (gpd_gptimer_enable_timer_7)—Offset 624h" on page 1166	00000000h
628h	4	"reg_gpd_gptimer_value_timer_0_type (gpd_gptimer_value_timer_0)—Offset 628h" on page 1166	00000000h
62Ch	4	"reg_gpd_gptimer_value_timer_1_type (gpd_gptimer_value_timer_1)—Offset 62Ch" on page 1167	00000000h
630h	4	"reg_gpd_gptimer_value_timer_2_type (gpd_gptimer_value_timer_2)—Offset 630h" on page 1167	00000000h
634h	4	"reg_gpd_gptimer_value_timer_3_type (gpd_gptimer_value_timer_3)—Offset 634h" on page 1168	00000000h
638h	4	"reg_gpd_gptimer_value_timer_4_type (gpd_gptimer_value_timer_4)—Offset 638h" on page 1168	00000000h
63Ch	4	"reg_gpd_gptimer_value_timer_5_type (gpd_gptimer_value_timer_5)—Offset 63Ch" on page 1169	00000000h
640h	4	"reg_gpd_gptimer_value_timer_6_type (gpd_gptimer_value_timer_6)—Offset 640h" on page 1169	00000000h
644h	4	"reg_gpd_gptimer_value_timer_7_type (gpd_gptimer_value_timer_7)—Offset 644h" on page 1170	00000000h
648h	4	"reg_gpd_gptimer_count_type_timer_0_type (gpd_gptimer_count_type_timer_0)—Offset 648h" on page 1170	00000000h
64Ch	4	"reg_gpd_gptimer_count_type_timer_1_type (gpd_gptimer_count_type_timer_1)—Offset 64Ch" on page 1171	00000000h
650h	4	"reg_gpd_gptimer_count_type_timer_2_type (gpd_gptimer_count_type_timer_2)—Offset 650h" on page 1172	00000000h
654h	4	"reg_gpd_gptimer_count_type_timer_3_type (gpd_gptimer_count_type_timer_3)—Offset 654h" on page 1172	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMADR (Continued)

Offset	Size	Register ID—Description	Default Value
658h	4	"reg_gpd_gptimer_count_type_timer_4_type (gpd_gptimer_count_type_timer_4)—Offset 658h" on page 1173	00000000h
65Ch	4	"reg_gpd_gptimer_count_type_timer_5_type (gpd_gptimer_count_type_timer_5)—Offset 65Ch" on page 1173	00000000h
660h	4	"reg_gpd_gptimer_count_type_timer_6_type (gpd_gptimer_count_type_timer_6)—Offset 660h" on page 1174	00000000h
664h	4	"reg_gpd_gptimer_count_type_timer_7_type (gpd_gptimer_count_type_timer_7)—Offset 664h" on page 1175	00000000h
668h	4	"reg_gpd_gptimer_signal_select_timer_0_type (gpd_gptimer_signal_select_timer_0)—Offset 668h" on page 1175	00000000h
66Ch	4	"reg_gpd_gptimer_signal_select_timer_1_type (gpd_gptimer_signal_select_timer_1)—Offset 66Ch" on page 1176	00000000h
670h	4	"reg_gpd_gptimer_signal_select_timer_2_type (gpd_gptimer_signal_select_timer_2)—Offset 670h" on page 1177	00000000h
674h	4	"reg_gpd_gptimer_signal_select_timer_3_type (gpd_gptimer_signal_select_timer_3)—Offset 674h" on page 1177	00000000h
678h	4	"reg_gpd_gptimer_signal_select_timer_4_type (gpd_gptimer_signal_select_timer_4)—Offset 678h" on page 1178	00000000h
67Ch	4	"reg_gpd_gptimer_signal_select_timer_5_type (gpd_gptimer_signal_select_timer_5)—Offset 67Ch" on page 1179	00000000h
680h	4	"reg_gpd_gptimer_signal_select_timer_6_type (gpd_gptimer_signal_select_timer_6)—Offset 680h" on page 1179	00000000h
684h	4	"reg_gpd_gptimer_signal_select_timer_7_type (gpd_gptimer_signal_select_timer_7)—Offset 684h" on page 1180	00000000h
688h	4	"reg_gpd_gptimer_irq_trigger_value_0_type (gpd_gptimer_irq_trigger_value_0)—Offset 688h" on page 1181	00000000h
68Ch	4	"reg_gpd_gptimer_irq_trigger_value_1_type (gpd_gptimer_irq_trigger_value_1)—Offset 68Ch" on page 1181	00000000h
690h	4	"reg_gpd_gptimer_irq_timer_select_0_type (gpd_gptimer_irq_timer_select_0)—Offset 690h" on page 1182	00000000h
694h	4	"reg_gpd_gptimer_irq_timer_select_1_type (gpd_gptimer_irq_timer_select_1)—Offset 694h" on page 1182	00000000h
698h	4	"reg_gpd_gptimer_irq_enable_0_type (gpd_gptimer_irq_enable_0)—Offset 698h" on page 1183	00000000h
69Ch	4	"reg_gpd_gptimer_irq_enable_1_type (gpd_gptimer_irq_enable_1)—Offset 69Ch" on page 1183	00000000h
10000h	4	"reg_scp_stat_and_ctrl_type (scp_stat_and_ctrl)—Offset 10000h" on page 1184	000000A0h
10004h	4	"reg_scp_base_address_type (scp_base_address)—Offset 10004h" on page 1185	00000000h
10008h	4	"reg_scp_unused_2_type (scp_unused_2)—Offset 10008h" on page 1186	00000000h
10010h	4	"reg_scp_base_addr_seg_0_MI_xmem_master_int_type (scp_base_addr_seg_0_MI_xmem_master_int)—Offset 10010h" on page 1186	00000000h
10014h	4	"reg_scp_base_addr_seg_0_MI_config_ilm_conf_ilm_master_type (scp_base_addr_seg_0_MI_config_ilm_conf_ilm_master)—Offset 10014h" on page 1187	00000000h
10018h	4	"reg_scp_unused_6_type (scp_unused_6)—Offset 10018h" on page 1188	00000000h
1001Ch	4	"reg_scp_unused_7_type (scp_unused_7)—Offset 1001Ch" on page 1188	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
10024h	4	"reg_scp_debug_pc_type (scp_debug_pc)—Offset 10024h" on page 1188	00000000h
10028h	4	"reg_scp_stall_stat_fifo_loc_mt_am_inst_0_op0_type (scp_stall_stat_fifo_loc_mt_am_inst_0_op0)—Offset 10028h" on page 1189	00000000h
1002Ch	4	"reg_scp_unused_11_type (scp_unused_11)—Offset 1002Ch" on page 1190	00000000h
10030h	4	"reg_scp_pmem_slave_access_type (scp_pmem_slave_access)—Offset 10030h" on page 1191	00000000h
20000h	4	"reg_isp_stat_and_ctrl_type (isp_stat_and_ctrl)—Offset 20000h" on page 1191	000000A0h
20004h	4	"reg_isp_base_address_type (isp_base_address)—Offset 20004h" on page 1193	00000000h
20008h	4	"reg_isp_unused_2_type (isp_unused_2)—Offset 20008h" on page 1193	00000000h
20010h	4	"reg_isp_base_addr_seg_0_MI_base_config_mem_master_type (isp_base_addr_seg_0_MI_base_config_mem_master)—Offset 20010h" on page 1194	00000000h
20014h	4	"reg_isp_unused_5_type (isp_unused_5)—Offset 20014h" on page 1194	00000000h
2001Ch	4	"reg_isp_debug_pc_type (isp_debug_pc)—Offset 2001Ch" on page 1195	00000000h
20020h	4	"reg_isp_stall_stat_base_config_mem_iam_op0_type (isp_stall_stat_base_config_mem_iam_op0)—Offset 20020h" on page 1195	00000000h
20024h	4	"reg_isp_unused_9_type (isp_unused_9)—Offset 20024h" on page 1197	00000000h
20028h	4	"reg_isp_pmem_slave_access_type (isp_pmem_slave_access)—Offset 20028h" on page 1197	00000000h
30000h	4	"reg_ifmt_ift_prim_IF_sw_rst_type (ifmt_ift_prim_IF_sw_rst)—Offset 30000h" on page 1198	00000000h
30004h	4	"reg_ifmt_ift_prim_IF_start_line_type (ifmt_ift_prim_IF_start_line)—Offset 30004h" on page 1198	00000000h
30008h	4	"reg_ifmt_ift_prim_IF_start_column_type (ifmt_ift_prim_IF_start_column)—Offset 30008h" on page 1199	00000000h
3000Ch	4	"reg_ifmt_ift_prim_IF_Cropped_height_type (ifmt_ift_prim_IF_Cropped_height)—Offset 3000Ch" on page 1199	00000000h
30010h	4	"reg_ifmt_ift_prim_IF_Cropped_width_type (ifmt_ift_prim_IF_Cropped_width)—Offset 30010h" on page 1200	00000000h
30014h	4	"reg_ifmt_ift_prim_IF_Vert_Decim_type (ifmt_ift_prim_IF_Vert_Decim)—Offset 30014h" on page 1201	00000000h
30018h	4	"reg_ifmt_ift_prim_IF_Horiz_Decim_type (ifmt_ift_prim_IF_Horiz_Decim)—Offset 30018h" on page 1201	00000000h
3001Ch	4	"reg_ifmt_ift_prim_IF_Horiz_Deinter_type (ifmt_ift_prim_IF_Horiz_Deinter)—Offset 3001Ch" on page 1202	00000000h
30020h	4	"reg_ifmt_ift_prim_IF_Left_Pad_type (ifmt_ift_prim_IF_Left_Pad)—Offset 30020h" on page 1202	00000000h
30024h	4	"reg_ifmt_ift_prim_IF_EOF_Offset_type (ifmt_ift_prim_IF_EOF_Offset)—Offset 30024h" on page 1203	00000000h
30028h	4	"reg_ifmt_ift_prim_IF_Start_addr_type (ifmt_ift_prim_IF_Start_addr)—Offset 30028h" on page 1203	00000000h
3002Ch	4	"reg_ifmt_ift_prim_IF_End_addr_type (ifmt_ift_prim_IF_End_addr)—Offset 3002Ch" on page 1204	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
30030h	4	"reg_ifmt_ift_prim_IF_incr_type (ifmt_ift_prim_IF_incr)—Offset 30030h" on page 1205	00000000h
30034h	4	"reg_ifmt_ift_prim_IF_YUV_420_format_type (ifmt_ift_prim_IF_YUV_420_format)—Offset 30034h" on page 1205	00000000h
30038h	4	"reg_ifmt_ift_prim_IF_Vsynch_active_low_type (ifmt_ift_prim_IF_Vsynch_active_low)—Offset 30038h" on page 1206	00000000h
3003Ch	4	"reg_ifmt_ift_prim_IF_Hsynch_active_low_type (ifmt_ift_prim_IF_Hsynch_active_low)—Offset 3003Ch" on page 1206	00000000h
30040h	4	"reg_ifmt_ift_prim_IF_ReEnable_type (ifmt_ift_prim_IF_ReEnable)—Offset 30040h" on page 1207	00000000h
30044h	4	"reg_ifmt_ift_prim_IF_block_input_type (ifmt_ift_prim_IF_block_input)—Offset 30044h" on page 1207	00000000h
30048h	4	"reg_ifmt_ift_prim_IF_Vert_Deinter_type (ifmt_ift_prim_IF_Vert_Deinter)—Offset 30048h" on page 1208	00000000h
30100h	4	"reg_ifmt_ift_prim_IF_FSM_Sync_status_type (ifmt_ift_prim_IF_FSM_Sync_status)—Offset 30100h" on page 1209	00000000h
30104h	4	"reg_ifmt_ift_prim_FSM_Sync_counter_type (ifmt_ift_prim_FSM_Sync_counter)—Offset 30104h" on page 1209	00000000h
30108h	4	"reg_ifmt_ift_prim_FSM_Crop_status_type (ifmt_ift_prim_FSM_Crop_status)—Offset 30108h" on page 1210	00000000h
3010Ch	4	"reg_ifmt_ift_prim_FSM_Crop_line_counter_type (ifmt_ift_prim_FSM_Crop_line_counter)—Offset 3010Ch" on page 1211	00000000h
30110h	4	"reg_ifmt_ift_prim_FSM_Crop_pixel_counter_type (ifmt_ift_prim_FSM_Crop_pixel_counter)—Offset 30110h" on page 1211	00000000h
30114h	4	"reg_ifmt_ift_prim_FSM_Deinterl_idx_buffer_type (ifmt_ift_prim_FSM_Deinterl_idx_buffer)—Offset 30114h" on page 1212	00000000h
30118h	4	"reg_ifmt_ift_prim_FSM_Horiz_Decim_cnt_type (ifmt_ift_prim_FSM_Horiz_Decim_cnt)—Offset 30118h" on page 1213	00000000h
3011Ch	4	"reg_ifmt_ift_prim_FSM_Vertic_Decim_cnt_type (ifmt_ift_prim_FSM_Vertic_Decim_cnt)—Offset 3011Ch" on page 1213	00000000h
30120h	4	"reg_ifmt_ift_prim_FSM_Vertic_Block_Decim_cnt_type (ifmt_ift_prim_FSM_Vertic_Block_Decim_cnt)—Offset 30120h" on page 1214	00000000h
30124h	4	"reg_ifmt_ift_prim_IF_FSM_Padding_status_type (ifmt_ift_prim_IF_FSM_Padding_status)—Offset 30124h" on page 1215	00000000h
30128h	4	"reg_ifmt_ift_prim_IF_FSM_Padding_elem_idx_type (ifmt_ift_prim_IF_FSM_Padding_elem_idx)—Offset 30128h" on page 1215	00000000h
3012Ch	4	"reg_ifmt_ift_prim_IF_FSM_Vec_Sup_type (ifmt_ift_prim_IF_FSM_Vec_Sup)—Offset 3012Ch" on page 1216	00000000h
30130h	4	"reg_ifmt_ift_prim_IF_FSM_Vec_Sup_Buf_full_type (ifmt_ift_prim_IF_FSM_Vec_Sup_Buf_full)—Offset 30130h" on page 1217	00000000h
30134h	4	"reg_ifmt_ift_prim_IF_FSM_Vec_Sup_rd_accept_type (ifmt_ift_prim_IF_FSM_Vec_Sup_rd_accept)—Offset 30134h" on page 1217	00000001h
30138h	4	"reg_ifmt_ift_prim_IF_Pixel_Fifo_status_type (ifmt_ift_prim_IF_Pixel_Fifo_status)—Offset 30138h" on page 1218	00000001h
30200h	4	"reg_ifmt_ift_prim_b_IF_sw_rst_type (ifmt_ift_prim_b_IF_sw_rst)—Offset 30200h" on page 1219	00000000h
30204h	4	"reg_ifmt_ift_prim_b_IF_start_line_type (ifmt_ift_prim_b_IF_start_line)—Offset 30204h" on page 1219	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
30208h	4	"reg_ifmt_ift_prim_b_IF_start_column_type (ifmt_ift_prim_b_IF_start_column)—Offset 30208h" on page 1220	00000000h
3020Ch	4	"reg_ifmt_ift_prim_b_IF_Cropped_height_type (ifmt_ift_prim_b_IF_Cropped_height)—Offset 3020Ch" on page 1220	00000000h
30210h	4	"reg_ifmt_ift_prim_b_IF_Cropped_width_type (ifmt_ift_prim_b_IF_Cropped_width)—Offset 30210h" on page 1221	00000000h
30214h	4	"reg_ifmt_ift_prim_b_IF_Vert_Decim_type (ifmt_ift_prim_b_IF_Vert_Decim)—Offset 30214h" on page 1222	00000000h
30218h	4	"reg_ifmt_ift_prim_b_IF_Horiz_Decim_type (ifmt_ift_prim_b_IF_Horiz_Decim)—Offset 30218h" on page 1222	00000000h
3021Ch	4	"reg_ifmt_ift_prim_b_IF_Horiz_Deinter_type (ifmt_ift_prim_b_IF_Horiz_Deinter)—Offset 3021Ch" on page 1223	00000000h
30220h	4	"reg_ifmt_ift_prim_b_IF_Left_Pad_type (ifmt_ift_prim_b_IF_Left_Pad)—Offset 30220h" on page 1223	00000000h
30224h	4	"reg_ifmt_ift_prim_b_IF_EOF_Offset_type (ifmt_ift_prim_b_IF_EOF_Offset)—Offset 30224h" on page 1224	00000000h
30228h	4	"reg_ifmt_ift_prim_b_IF_Start_addr_type (ifmt_ift_prim_b_IF_Start_addr)—Offset 30228h" on page 1225	00000000h
3022Ch	4	"reg_ifmt_ift_prim_b_IF_End_addr_type (ifmt_ift_prim_b_IF_End_addr)—Offset 3022Ch" on page 1225	00000000h
30230h	4	"reg_ifmt_ift_prim_b_IF_incr_type (ifmt_ift_prim_b_IF_incr)—Offset 30230h" on page 1226	00000000h
30234h	4	"reg_ifmt_ift_prim_b_IF_YUV_420_format_type (ifmt_ift_prim_b_IF_YUV_420_format)—Offset 30234h" on page 1226	00000000h
30238h	4	"reg_ifmt_ift_prim_b_IF_Vsynch_active_low_type (ifmt_ift_prim_b_IF_Vsynch_active_low)—Offset 30238h" on page 1227	00000000h
3023Ch	4	"reg_ifmt_ift_prim_b_IF_Hsynch_active_low_type (ifmt_ift_prim_b_IF_Hsynch_active_low)—Offset 3023Ch" on page 1228	00000000h
30240h	4	"reg_ifmt_ift_prim_b_IF_ReEnable_type (ifmt_ift_prim_b_IF_ReEnable)—Offset 30240h" on page 1228	00000000h
30244h	4	"reg_ifmt_ift_prim_b_IF_block_input_type (ifmt_ift_prim_b_IF_block_input)—Offset 30244h" on page 1229	00000000h
30248h	4	"reg_ifmt_ift_prim_b_IF_Vert_Deinter_type (ifmt_ift_prim_b_IF_Vert_Deinter)—Offset 30248h" on page 1229	00000000h
30300h	4	"reg_ifmt_ift_prim_b_IF_FSM_Sync_status_type (ifmt_ift_prim_b_IF_FSM_Sync_status)—Offset 30300h" on page 1230	00000000h
30304h	4	"reg_ifmt_ift_prim_b_FSM_Sync_counter_type (ifmt_ift_prim_b_FSM_Sync_counter)—Offset 30304h" on page 1231	00000000h
30308h	4	"reg_ifmt_ift_prim_b_FSM_Crop_status_type (ifmt_ift_prim_b_FSM_Crop_status)—Offset 30308h" on page 1231	00000000h
3030Ch	4	"reg_ifmt_ift_prim_b_FSM_Crop_line_counter_type (ifmt_ift_prim_b_FSM_Crop_line_counter)—Offset 3030Ch" on page 1232	00000000h
30310h	4	"reg_ifmt_ift_prim_b_FSM_Crop_pixel_counter_type (ifmt_ift_prim_b_FSM_Crop_pixel_counter)—Offset 30310h" on page 1233	00000000h
30314h	4	"reg_ifmt_ift_prim_b_FSM_Deinterl_idx_buffer_type (ifmt_ift_prim_b_FSM_Deinterl_idx_buffer)—Offset 30314h" on page 1233	00000000h
30318h	4	"reg_ifmt_ift_prim_b_FSM_Horiz_Decim_cnt_type (ifmt_ift_prim_b_FSM_Horiz_Decim_cnt)—Offset 30318h" on page 1234	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
3031Ch	4	"reg_ifmt_ift_prim_b_FSM_Vertic_Decim_cnt_type (ifmt_ift_prim_b_FSM_Vertic_Decim_cnt)—Offset 3031Ch" on page 1235	00000000h
30320h	4	"reg_ifmt_ift_prim_b_FSM_Vertic_Block_Decim_cnt_type (ifmt_ift_prim_b_FSM_Vertic_Block_Decim_cnt)—Offset 30320h" on page 1235	00000000h
30324h	4	"reg_ifmt_ift_prim_b_IF_FSM_Padding_status_type (ifmt_ift_prim_b_IF_FSM_Padding_status)—Offset 30324h" on page 1236	00000000h
30328h	4	"reg_ifmt_ift_prim_b_IF_FSM_Padding_elem_idx_type (ifmt_ift_prim_b_IF_FSM_Padding_elem_idx)—Offset 30328h" on page 1237	00000000h
3032Ch	4	"reg_ifmt_ift_prim_b_IF_FSM_Vec_Sup_type (ifmt_ift_prim_b_IF_FSM_Vec_Sup)—Offset 3032Ch" on page 1237	00000000h
30330h	4	"reg_ifmt_ift_prim_b_IF_FSM_Vec_Sup_Buf_full_type (ifmt_ift_prim_b_IF_FSM_Vec_Sup_Buf_full)—Offset 30330h" on page 1238	00000000h
30334h	4	"reg_ifmt_ift_prim_b_IF_FSM_Vec_Sup_rd_accept_type (ifmt_ift_prim_b_IF_FSM_Vec_Sup_rd_accept)—Offset 30334h" on page 1239	00000001h
30338h	4	"reg_ifmt_ift_prim_b_IF_Pixel_Fifo_status_type (ifmt_ift_prim_b_IF_Pixel_Fifo_status)—Offset 30338h" on page 1239	00000001h
30400h	4	"reg_ifmt_ift_sec_IF_sw_rst_type (ifmt_ift_sec_IF_sw_rst)—Offset 30400h" on page 1240	00000000h
30404h	4	"reg_ifmt_ift_sec_IF_start_line_type (ifmt_ift_sec_IF_start_line)—Offset 30404h" on page 1241	00000000h
30408h	4	"reg_ifmt_ift_sec_IF_start_column_type (ifmt_ift_sec_IF_start_column)—Offset 30408h" on page 1241	00000000h
3040Ch	4	"reg_ifmt_ift_sec_IF_Cropped_height_type (ifmt_ift_sec_IF_Cropped_height)—Offset 3040Ch" on page 1242	00000000h
30410h	4	"reg_ifmt_ift_sec_IF_Cropped_width_type (ifmt_ift_sec_IF_Cropped_width)—Offset 30410h" on page 1243	00000000h
30414h	4	"reg_ifmt_ift_sec_IF_Vert_Decim_type (ifmt_ift_sec_IF_Vert_Decim)—Offset 30414h" on page 1243	00000000h
30418h	4	"reg_ifmt_ift_sec_IF_Horiz_Decim_type (ifmt_ift_sec_IF_Horiz_Decim)—Offset 30418h" on page 1244	00000000h
3041Ch	4	"reg_ifmt_ift_sec_IF_Horiz_Deinter_type (ifmt_ift_sec_IF_Horiz_Deinter)—Offset 3041Ch" on page 1244	00000000h
30420h	4	"reg_ifmt_ift_sec_IF_Left_Pad_type (ifmt_ift_sec_IF_Left_Pad)—Offset 30420h" on page 1245	00000000h
30424h	4	"reg_ifmt_ift_sec_IF_EOF_Offset_type (ifmt_ift_sec_IF_EOF_Offset)—Offset 30424h" on page 1245	00000000h
30428h	4	"reg_ifmt_ift_sec_IF_Start_addr_type (ifmt_ift_sec_IF_Start_addr)—Offset 30428h" on page 1246	00000000h
3042Ch	4	"reg_ifmt_ift_sec_IF_End_addr_type (ifmt_ift_sec_IF_End_addr)—Offset 3042Ch" on page 1247	00000000h
30430h	4	"reg_ifmt_ift_sec_IF_incr_type (ifmt_ift_sec_IF_incr)—Offset 30430h" on page 1247	00000000h
30434h	4	"reg_ifmt_ift_sec_IF_YUV_420_format_type (ifmt_ift_sec_IF_YUV_420_format)—Offset 30434h" on page 1248	00000000h
30438h	4	"reg_ifmt_ift_sec_IF_Vsync_active_low_type (ifmt_ift_sec_IF_Vsync_active_low)—Offset 30438h" on page 1248	00000000h




Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
3043Ch	4	"reg_ifmt_ift_sec_IF_Hsynch_active_low_type (ifmt_ift_sec_IF_Hsynch_active_low)—Offset 3043Ch" on page 1249	00000000h
30440h	4	"reg_ifmt_ift_sec_IF_ReEnable_type (ifmt_ift_sec_IF_ReEnable)—Offset 30440h" on page 1250	00000000h
30444h	4	"reg_ifmt_ift_sec_IF_block_input_type (ifmt_ift_sec_IF_block_input)—Offset 30444h" on page 1250	00000000h
30448h	4	"reg_ifmt_ift_sec_IF_Vert_Deinter_type (ifmt_ift_sec_IF_Vert_Deinter)—Offset 30448h" on page 1251	00000000h
30500h	4	"reg_ifmt_ift_sec_IF_FSM_Sync_status_type (ifmt_ift_sec_IF_FSM_Sync_status)—Offset 30500h" on page 1251	00000000h
30504h	4	"reg_ifmt_ift_sec_FSM_Sync_counter_type (ifmt_ift_sec_FSM_Sync_counter)—Offset 30504h" on page 1252	00000000h
30508h	4	"reg_ifmt_ift_sec_FSM_Crop_status_type (ifmt_ift_sec_FSM_Crop_status)—Offset 30508h" on page 1253	00000000h
3050Ch	4	"reg_ifmt_ift_sec_FSM_Crop_line_counter_type (ifmt_ift_sec_FSM_Crop_line_counter)—Offset 3050Ch" on page 1253	00000000h
30510h	4	"reg_ifmt_ift_sec_FSM_Crop_pixel_counter_type (ifmt_ift_sec_FSM_Crop_pixel_counter)—Offset 30510h" on page 1254	00000000h
30514h	4	"reg_ifmt_ift_sec_FSM_Deinterl_idx_buffer_type (ifmt_ift_sec_FSM_Deinterl_idx_buffer)—Offset 30514h" on page 1255	00000000h
30518h	4	"reg_ifmt_ift_sec_FSM_Horiz-Decim_cnt_type (ifmt_ift_sec_FSM_Horiz-Decim_cnt)—Offset 30518h" on page 1255	00000000h
3051Ch	4	"reg_ifmt_ift_sec_FSM_Vertic-Decim_cnt_type (ifmt_ift_sec_FSM_Vertic-Decim_cnt)—Offset 3051Ch" on page 1256	00000000h
30520h	4	"reg_ifmt_ift_sec_FSM_Vertic_Block-Decim_cnt_type (ifmt_ift_sec_FSM_Vertic_Block-Decim_cnt)—Offset 30520h" on page 1257	00000000h
30524h	4	"reg_ifmt_ift_sec_IF_FSM_Padding_status_type (ifmt_ift_sec_IF_FSM_Padding_status)—Offset 30524h" on page 1257	00000000h
30528h	4	"reg_ifmt_ift_sec_IF_FSM_Padding_elem_idx_type (ifmt_ift_sec_IF_FSM_Padding_elem_idx)—Offset 30528h" on page 1258	00000000h
3052Ch	4	"reg_ifmt_ift_sec_IF_FSM_Vec_Sup_type (ifmt_ift_sec_IF_FSM_Vec_Sup)—Offset 3052Ch" on page 1259	00000000h
30530h	4	"reg_ifmt_ift_sec_IF_FSM_Vec_Sup_Buf_full_type (ifmt_ift_sec_IF_FSM_Vec_Sup_Buf_full)—Offset 30530h" on page 1259	00000000h
30534h	4	"reg_ifmt_ift_sec_IF_FSM_Vec_Sup_rd_accept_type (ifmt_ift_sec_IF_FSM_Vec_Sup_rd_accept)—Offset 30534h" on page 1260	00000001h
30538h	4	"reg_ifmt_ift_sec_IF_Pixel_Fifo_status_type (ifmt_ift_sec_IF_Pixel_Fifo_status)—Offset 30538h" on page 1261	00000001h
30600h	4	"reg_ifmt_mem_cpy_MemCopy_sw_rst_type (ifmt_mem_cpy_MemCopy_sw_rst)—Offset 30600h" on page 1261	00000000h
30604h	4	"reg_ifmt_mem_cpy_MemCopy_in_endian_type (ifmt_mem_cpy_MemCopy_in_endian)—Offset 30604h" on page 1262	00000000h
30608h	4	"reg_ifmt_mem_cpy_MemCopy_out_endian_type (ifmt_mem_cpy_MemCopy_out_endian)—Offset 30608h" on page 1263	00000000h
3060Ch	4	"reg_ifmt_mem_cpy_MemCopy_bit_swap_type (ifmt_mem_cpy_MemCopy_bit_swap)—Offset 3060Ch" on page 1263	00000000h
30610h	4	"reg_ifmt_mem_cpy_MemCopy_block_synch_type (ifmt_mem_cpy_MemCopy_block_synch)—Offset 30610h" on page 1264	00000000h




Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMADR (Continued)

Offset	Size	Register ID—Description	Default Value
30614h	4	"reg_ifmt_mem_cpy_MemCopy_packet_sync_type (ifmt_mem_cpy_MemCopy_packet_sync)—Offset 30614h" on page 1265	00000000h
30618h	4	"reg_ifmt_mem_cpy_MemCopy_rd_post_wr_sync_type (ifmt_mem_cpy_MemCopy_rd_post_wr_sync)—Offset 30618h" on page 1265	00000000h
3061Ch	4	"reg_ifmt_mem_cpy_MemCopy_dual_input_type (ifmt_mem_cpy_MemCopy_dual_input)—Offset 3061Ch" on page 1266	00000000h
30620h	4	"reg_ifmt_mem_cpy_MemCopy_ReEnable_type (ifmt_mem_cpy_MemCopy_ReEnable)—Offset 30620h" on page 1267	00000000h
30700h	4	"reg_ifmt_mem_cpy_MemCopy_token_data_type (ifmt_mem_cpy_MemCopy_token_data)—Offset 30700h" on page 1267	00000000h
30704h	4	"reg_ifmt_mem_cpy_MemCopy_FSM_Sync_status_type (ifmt_mem_cpy_MemCopy_FSM_Sync_status)—Offset 30704h" on page 1268	00000000h
30708h	4	"reg_ifmt_mem_cpy_MemCopy_FSM_Sync_bytes_cnt_type (ifmt_mem_cpy_MemCopy_FSM_Sync_bytes_cnt)—Offset 30708h" on page 1269	00000000h
3070Ch	4	"reg_ifmt_mem_cpy_MemCopy_FSM_Sync_token_cnt_type (ifmt_mem_cpy_MemCopy_FSM_Sync_token_cnt)—Offset 3070Ch" on page 1269	00000000h
30710h	4	"reg_ifmt_mem_cpy_MemCopy_FSM_Pack_idx_cnt_type (ifmt_mem_cpy_MemCopy_FSM_Pack_idx_cnt)—Offset 30710h" on page 1270	00000000h
30714h	4	"reg_ifmt_mem_cpy_MemCopy_FSM_Buf_Sup_status_type (ifmt_mem_cpy_MemCopy_FSM_Buf_Sup_status)—Offset 30714h" on page 1271	00000000h
30718h	4	"reg_ifmt_mem_cpy_MemCopy_FSM_Buf_Sup_cnt_type (ifmt_mem_cpy_MemCopy_FSM_Buf_Sup_cnt)—Offset 30718h" on page 1271	00000000h
3071Ch	4	"reg_ifmt_mem_cpy_MemCopy_FSM_CioWr_status_type (ifmt_mem_cpy_MemCopy_FSM_CioWr_status)—Offset 3071Ch" on page 1272	00000004h
30720h	4	"reg_ifmt_mem_cpy_MemCopy_FSM_CioWr_addr_type (ifmt_mem_cpy_MemCopy_FSM_CioWr_addr)—Offset 30720h" on page 1273	00000000h
30800h	4	"reg_ifmt_gp_reg_IFMT_input_switch_lut_reg0_type (ifmt_gp_reg_IFMT_input_switch_lut_reg0)—Offset 30800h" on page 1274	00000000h
30804h	4	"reg_ifmt_gp_reg_IFMT_input_switch_lut_reg1_type (ifmt_gp_reg_IFMT_input_switch_lut_reg1)—Offset 30804h" on page 1274	00000000h
30808h	4	"reg_ifmt_gp_reg_IFMT_input_switch_lut_reg2_type (ifmt_gp_reg_IFMT_input_switch_lut_reg2)—Offset 30808h" on page 1275	00000000h
3080Ch	4	"reg_ifmt_gp_reg_IFMT_input_switch_lut_reg3_type (ifmt_gp_reg_IFMT_input_switch_lut_reg3)—Offset 3080Ch" on page 1276	00000000h
30810h	4	"reg_ifmt_gp_reg_IFMT_input_switch_lut_reg4_type (ifmt_gp_reg_IFMT_input_switch_lut_reg4)—Offset 30810h" on page 1276	00000000h
30814h	4	"reg_ifmt_gp_reg_IFMT_input_switch_lut_reg5_type (ifmt_gp_reg_IFMT_input_switch_lut_reg5)—Offset 30814h" on page 1277	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
30818h	4	"reg_ifmt_gp_reg_IFMT_input_switch_lut_reg6_type (ifmt_gp_reg_IFMT_input_switch_lut_reg6)—Offset 30818h" on page 1277	00000000h
3081Ch	4	"reg_ifmt_gp_reg_IFMT_input_switch_lut_reg7_type (ifmt_gp_reg_IFMT_input_switch_lut_reg7)—Offset 3081Ch" on page 1278	00000000h
30820h	4	"reg_ifmt_gp_reg_IFMT_input_switch_fsync_lut_type (ifmt_gp_reg_IFMT_input_switch_fsync_lut)—Offset 30820h" on page 1278	00000000h
30824h	4	"reg_ifmt_gp_reg_IFMT_srst_type (ifmt_gp_reg_IFMT_srst)—Offset 30824h" on page 1279	00000000h
30828h	4	"reg_ifmt_gp_reg_IFMT_slv_reg_srst_type (ifmt_gp_reg_IFMT_slv_reg_srst)—Offset 30828h" on page 1280	00000000h
3082Ch	4	"reg_ifmt_gp_reg_IFMT_input_switch_ch_id_fmt_type_type (ifmt_gp_reg_IFMT_input_switch_ch_id_fmt_type)—Offset 3082Ch" on page 1281	00000000h
30A00h	4	"reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge)—Offset 30A00h" on page 1281	00000000h
30A04h	4	"reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_mask_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_mask)—Offset 30A04h" on page 1282	00000000h
30A08h	4	"reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_status_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_status)—Offset 30A08h" on page 1283	00000000h
30A0Ch	4	"reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_clear_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_clear)—Offset 30A0Ch" on page 1283	00000000h
30A10h	4	"reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_enable_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_enable)—Offset 30A10h" on page 1284	00000000h
30A14h	4	"reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge_pulse_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge_pulse)—Offset 30A14h" on page 1285	00000000h
40000h	4	"reg_isp_dma_DMA_FSM_Command_type (isp_dma_DMA_FSM_Command)—Offset 40000h" on page 1285	00000001h
41000h	4	"reg_isp_dma_DMA_CH0_Packing_setup_type (isp_dma_DMA_CH0_Packing_setup)—Offset 41000h" on page 1286	00000000h
41004h	4	"reg_isp_dma_DMA_CH1_Packing_setup_type (isp_dma_DMA_CH1_Packing_setup)—Offset 41004h" on page 1287	00000000h
41008h	4	"reg_isp_dma_DMA_CH2_Packing_setup_type (isp_dma_DMA_CH2_Packing_setup)—Offset 41008h" on page 1287	00000000h
4100Ch	4	"reg_isp_dma_DMA_CH3_Packing_setup_type (isp_dma_DMA_CH3_Packing_setup)—Offset 4100Ch" on page 1288	00000000h
41010h	4	"reg_isp_dma_DMA_CH4_Packing_setup_type (isp_dma_DMA_CH4_Packing_setup)—Offset 41010h" on page 1289	00000000h
41014h	4	"reg_isp_dma_DMA_CH5_Packing_setup_type (isp_dma_DMA_CH5_Packing_setup)—Offset 41014h" on page 1290	00000000h
41018h	4	"reg_isp_dma_DMA_CH6_Packing_setup_type (isp_dma_DMA_CH6_Packing_setup)—Offset 41018h" on page 1291	00000000h
4101Ch	4	"reg_isp_dma_DMA_CH7_Packing_setup_type (isp_dma_DMA_CH7_Packing_setup)—Offset 4101Ch" on page 1291	00000000h
41020h	4	"reg_isp_dma_DMA_CH8_Packing_setup_type (isp_dma_DMA_CH8_Packing_setup)—Offset 41020h" on page 1292	00000000h
41024h	4	"reg_isp_dma_DMA_CH9_Packing_setup_type (isp_dma_DMA_CH9_Packing_setup)—Offset 41024h" on page 1293	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41028h	4	"reg_isp_dma_DMA_CH10_Packing_setup_type (isp_dma_DMA_CH10_Packing_setup)—Offset 41028h" on page 1294	00000000h
4102Ch	4	"reg_isp_dma_DMA_CH11_Packing_setup_type (isp_dma_DMA_CH11_Packing_setup)—Offset 4102Ch" on page 1294	00000000h
41030h	4	"reg_isp_dma_DMA_CH12_Packing_setup_type (isp_dma_DMA_CH12_Packing_setup)—Offset 41030h" on page 1295	00000000h
41034h	4	"reg_isp_dma_DMA_CH13_Packing_setup_type (isp_dma_DMA_CH13_Packing_setup)—Offset 41034h" on page 1296	00000000h
41038h	4	"reg_isp_dma_DMA_CH14_Packing_setup_type (isp_dma_DMA_CH14_Packing_setup)—Offset 41038h" on page 1297	00000000h
4103Ch	4	"reg_isp_dma_DMA_CH15_Packing_setup_type (isp_dma_DMA_CH15_Packing_setup)—Offset 4103Ch" on page 1297	00000000h
41040h	4	"reg_isp_dma_DMA_CH16_Packing_setup_type (isp_dma_DMA_CH16_Packing_setup)—Offset 41040h" on page 1298	00000000h
41044h	4	"reg_isp_dma_DMA_CH17_Packing_setup_type (isp_dma_DMA_CH17_Packing_setup)—Offset 41044h" on page 1299	00000000h
41048h	4	"reg_isp_dma_DMA_CH18_Packing_setup_type (isp_dma_DMA_CH18_Packing_setup)—Offset 41048h" on page 1300	00000000h
4104Ch	4	"reg_isp_dma_DMA_CH19_Packing_setup_type (isp_dma_DMA_CH19_Packing_setup)—Offset 4104Ch" on page 1300	00000000h
41050h	4	"reg_isp_dma_DMA_CH20_Packing_setup_type (isp_dma_DMA_CH20_Packing_setup)—Offset 41050h" on page 1301	00000000h
41054h	4	"reg_isp_dma_DMA_CH21_Packing_setup_type (isp_dma_DMA_CH21_Packing_setup)—Offset 41054h" on page 1302	00000000h
41058h	4	"reg_isp_dma_DMA_CH22_Packing_setup_type (isp_dma_DMA_CH22_Packing_setup)—Offset 41058h" on page 1303	00000000h
4105Ch	4	"reg_isp_dma_DMA_CH23_Packing_setup_type (isp_dma_DMA_CH23_Packing_setup)—Offset 4105Ch" on page 1303	00000000h
41060h	4	"reg_isp_dma_DMA_CH24_Packing_setup_type (isp_dma_DMA_CH24_Packing_setup)—Offset 41060h" on page 1304	00000000h
41064h	4	"reg_isp_dma_DMA_CH25_Packing_setup_type (isp_dma_DMA_CH25_Packing_setup)—Offset 41064h" on page 1305	00000000h
41068h	4	"reg_isp_dma_DMA_CH26_Packing_setup_type (isp_dma_DMA_CH26_Packing_setup)—Offset 41068h" on page 1306	00000000h
41070h	4	"reg_isp_dma_DMA_CH28_Packing_setup_type (isp_dma_DMA_CH28_Packing_setup)—Offset 41070h" on page 1306	00000000h
41074h	4	"reg_isp_dma_DMA_CH29_Packing_setup_type (isp_dma_DMA_CH29_Packing_setup)—Offset 41074h" on page 1307	00000000h
41078h	4	"reg_isp_dma_DMA_CH30_Packing_setup_type (isp_dma_DMA_CH30_Packing_setup)—Offset 41078h" on page 1308	00000000h
4107Ch	4	"reg_isp_dma_DMA_CH31_Packing_setup_type (isp_dma_DMA_CH31_Packing_setup)—Offset 4107Ch" on page 1309	00000000h
41100h	4	"reg_isp_dma_DMA_CH0_dev_stride_A_type (isp_dma_DMA_CH0_dev_stride_A)—Offset 41100h" on page 1309	00000000h
41104h	4	"reg_isp_dma_DMA_CH1_dev_stride_A_type (isp_dma_DMA_CH1_dev_stride_A)—Offset 41104h" on page 1310	00000000h
41108h	4	"reg_isp_dma_DMA_CH2_dev_stride_A_type (isp_dma_DMA_CH2_dev_stride_A)—Offset 41108h" on page 1310	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
4110Ch	4	"reg_isp_dma_DMA_CH3_dev_stride_A_type (isp_dma_DMA_CH3_dev_stride_A)—Offset 4110Ch" on page 1311	00000000h
41110h	4	"reg_isp_dma_DMA_CH4_dev_stride_A_type (isp_dma_DMA_CH4_dev_stride_A)—Offset 41110h" on page 1311	00000000h
41114h	4	"reg_isp_dma_DMA_CH5_dev_stride_A_type (isp_dma_DMA_CH5_dev_stride_A)—Offset 41114h" on page 1312	00000000h
41118h	4	"reg_isp_dma_DMA_CH6_dev_stride_A_type (isp_dma_DMA_CH6_dev_stride_A)—Offset 41118h" on page 1312	00000000h
4111Ch	4	"reg_isp_dma_DMA_CH7_dev_stride_A_type (isp_dma_DMA_CH7_dev_stride_A)—Offset 4111Ch" on page 1313	00000000h
41120h	4	"reg_isp_dma_DMA_CH8_dev_stride_A_type (isp_dma_DMA_CH8_dev_stride_A)—Offset 41120h" on page 1313	00000000h
41124h	4	"reg_isp_dma_DMA_CH9_dev_stride_A_type (isp_dma_DMA_CH9_dev_stride_A)—Offset 41124h" on page 1314	00000000h
41128h	4	"reg_isp_dma_DMA_CH10_dev_stride_A_type (isp_dma_DMA_CH10_dev_stride_A)—Offset 41128h" on page 1314	00000000h
4112Ch	4	"reg_isp_dma_DMA_CH11_dev_stride_A_type (isp_dma_DMA_CH11_dev_stride_A)—Offset 4112Ch" on page 1315	00000000h
41130h	4	"reg_isp_dma_DMA_CH12_dev_stride_A_type (isp_dma_DMA_CH12_dev_stride_A)—Offset 41130h" on page 1315	00000000h
41134h	4	"reg_isp_dma_DMA_CH13_dev_stride_A_type (isp_dma_DMA_CH13_dev_stride_A)—Offset 41134h" on page 1316	00000000h
41138h	4	"reg_isp_dma_DMA_CH14_dev_stride_A_type (isp_dma_DMA_CH14_dev_stride_A)—Offset 41138h" on page 1317	00000000h
4113Ch	4	"reg_isp_dma_DMA_CH15_dev_stride_A_type (isp_dma_DMA_CH15_dev_stride_A)—Offset 4113Ch" on page 1317	00000000h
41140h	4	"reg_isp_dma_DMA_CH16_dev_stride_A_type (isp_dma_DMA_CH16_dev_stride_A)—Offset 41140h" on page 1318	00000000h
41144h	4	"reg_isp_dma_DMA_CH17_dev_stride_A_type (isp_dma_DMA_CH17_dev_stride_A)—Offset 41144h" on page 1318	00000000h
41148h	4	"reg_isp_dma_DMA_CH18_dev_stride_A_type (isp_dma_DMA_CH18_dev_stride_A)—Offset 41148h" on page 1319	00000000h
4114Ch	4	"reg_isp_dma_DMA_CH19_dev_stride_A_type (isp_dma_DMA_CH19_dev_stride_A)—Offset 4114Ch" on page 1319	00000000h
41150h	4	"reg_isp_dma_DMA_CH20_dev_stride_A_type (isp_dma_DMA_CH20_dev_stride_A)—Offset 41150h" on page 1320	00000000h
41154h	4	"reg_isp_dma_DMA_CH21_dev_stride_A_type (isp_dma_DMA_CH21_dev_stride_A)—Offset 41154h" on page 1320	00000000h
41200h	4	"reg_isp_dma_DMA_CH0_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH0_dev_Pack_left_crop_and_elem_A)—Offset 41200h" on page 1321	00000000h
41204h	4	"reg_isp_dma_DMA_CH1_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH1_dev_Pack_left_crop_and_elem_A)—Offset 41204h" on page 1322	00000000h
41208h	4	"reg_isp_dma_DMA_CH2_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH2_dev_Pack_left_crop_and_elem_A)—Offset 41208h" on page 1323	00000000h
4120Ch	4	"reg_isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_A)—Offset 4120Ch" on page 1324	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41210h	4	"reg_isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_A)—Offset 41210h" on page 1325	00000000h
41214h	4	"reg_isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_A)—Offset 41214h" on page 1326	00000000h
41218h	4	"reg_isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_A)—Offset 41218h" on page 1327	00000000h
4121Ch	4	"reg_isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_A)—Offset 4121Ch" on page 1328	00000000h
41220h	4	"reg_isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_A)—Offset 41220h" on page 1329	00000000h
41224h	4	"reg_isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_A)—Offset 41224h" on page 1330	00000000h
41228h	4	"reg_isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_A)—Offset 41228h" on page 1331	00000000h
4122Ch	4	"reg_isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_A)—Offset 4122Ch" on page 1332	00000000h
41230h	4	"reg_isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_A)—Offset 41230h" on page 1333	00000000h
41234h	4	"reg_isp_dma_DMA_CH13_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH13_dev_Pack_left_crop_and_elem_A)—Offset 41234h" on page 1334	00000000h
41238h	4	"reg_isp_dma_DMA_CH14_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH14_dev_Pack_left_crop_and_elem_A)—Offset 41238h" on page 1335	00000000h
4123Ch	4	"reg_isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_A)—Offset 4123Ch" on page 1336	00000000h
41240h	4	"reg_isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_A)—Offset 41240h" on page 1337	00000000h
41244h	4	"reg_isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_A)—Offset 41244h" on page 1338	00000000h
41248h	4	"reg_isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_A)—Offset 41248h" on page 1339	00000000h
4124Ch	4	"reg_isp_dma_DMA_CH19_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH19_dev_Pack_left_crop_and_elem_A)—Offset 4124Ch" on page 1340	00000000h
41250h	4	"reg_isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_A)—Offset 41250h" on page 1341	00000000h
41254h	4	"reg_isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_A)—Offset 41254h" on page 1342	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41258h	4	"reg_isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_A)—Offset 41258h" on page 1343	00000000h
4125Ch	4	"reg_isp_dma_DMA_CH23_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH23_dev_Pack_left_crop_and_elem_A)—Offset 4125Ch" on page 1344	00000000h
41260h	4	"reg_isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_A)—Offset 41260h" on page 1345	00000000h
41264h	4	"reg_isp_dma_DMA_CH25_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH25_dev_Pack_left_crop_and_elem_A)—Offset 41264h" on page 1346	00000000h
41268h	4	"reg_isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_A)—Offset 41268h" on page 1347	00000000h
4126Ch	4	"reg_isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_A)—Offset 4126Ch" on page 1348	00000000h
41270h	4	"reg_isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_A)—Offset 41270h" on page 1349	00000000h
41274h	4	"reg_isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_A)—Offset 41274h" on page 1350	00000000h
41278h	4	"reg_isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_A)—Offset 41278h" on page 1351	00000000h
4127Ch	4	"reg_isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_A)—Offset 4127Ch" on page 1352	00000000h
412C0h	4	"reg_isp_dma_DMA_CH22_dev_stride_A_type (isp_dma_DMA_CH22_dev_stride_A)—Offset 412C0h" on page 1353	00000000h
412C4h	4	"reg_isp_dma_DMA_CH23_dev_stride_A_type (isp_dma_DMA_CH23_dev_stride_A)—Offset 412C4h" on page 1354	00000000h
412C8h	4	"reg_isp_dma_DMA_CH24_dev_stride_A_type (isp_dma_DMA_CH24_dev_stride_A)—Offset 412C8h" on page 1354	00000000h
412CCh	4	"reg_isp_dma_DMA_CH25_dev_stride_A_type (isp_dma_DMA_CH25_dev_stride_A)—Offset 412CCh" on page 1355	00000000h
412D0h	4	"reg_isp_dma_DMA_CH26_dev_stride_A_type (isp_dma_DMA_CH26_dev_stride_A)—Offset 412D0h" on page 1355	00000000h
412D4h	4	"reg_isp_dma_DMA_CH27_dev_stride_A_type (isp_dma_DMA_CH27_dev_stride_A)—Offset 412D4h" on page 1356	00000000h
412D8h	4	"reg_isp_dma_DMA_CH28_dev_stride_A_type (isp_dma_DMA_CH28_dev_stride_A)—Offset 412D8h" on page 1357	00000000h
412DCh	4	"reg_isp_dma_DMA_CH29_dev_stride_A_type (isp_dma_DMA_CH29_dev_stride_A)—Offset 412DCh" on page 1357	00000000h
412E0h	4	"reg_isp_dma_DMA_CH30_dev_stride_A_type (isp_dma_DMA_CH30_dev_stride_A)—Offset 412E0h" on page 1358	00000000h
412E4h	4	"reg_isp_dma_DMA_CH31_dev_stride_A_type (isp_dma_DMA_CH31_dev_stride_A)—Offset 412E4h" on page 1358	00000000h
41300h	4	"reg_isp_dma_DMA_CH0_Device_Xb_A_type (isp_dma_DMA_CH0_Device_Xb_A)—Offset 41300h" on page 1359	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41304h	4	"reg_isp_dma_DMA_CH1_Device_Xb_A_type (isp_dma_DMA_CH1_Device_Xb_A)—Offset 41304h" on page 1359	00000000h
41308h	4	"reg_isp_dma_DMA_CH2_Device_Xb_A_type (isp_dma_DMA_CH2_Device_Xb_A)—Offset 41308h" on page 1360	00000000h
4130Ch	4	"reg_isp_dma_DMA_CH3_Device_Xb_A_type (isp_dma_DMA_CH3_Device_Xb_A)—Offset 4130Ch" on page 1361	00000000h
41310h	4	"reg_isp_dma_DMA_CH4_Device_Xb_A_type (isp_dma_DMA_CH4_Device_Xb_A)—Offset 41310h" on page 1361	00000000h
41314h	4	"reg_isp_dma_DMA_CH5_Device_Xb_A_type (isp_dma_DMA_CH5_Device_Xb_A)—Offset 41314h" on page 1362	00000000h
41318h	4	"reg_isp_dma_DMA_CH6_Device_Xb_A_type (isp_dma_DMA_CH6_Device_Xb_A)—Offset 41318h" on page 1363	00000000h
4131Ch	4	"reg_isp_dma_DMA_CH7_Device_Xb_A_type (isp_dma_DMA_CH7_Device_Xb_A)—Offset 4131Ch" on page 1363	00000000h
41320h	4	"reg_isp_dma_DMA_CH8_Device_Xb_A_type (isp_dma_DMA_CH8_Device_Xb_A)—Offset 41320h" on page 1364	00000000h
41324h	4	"reg_isp_dma_DMA_CH9_Device_Xb_A_type (isp_dma_DMA_CH9_Device_Xb_A)—Offset 41324h" on page 1365	00000000h
41328h	4	"reg_isp_dma_DMA_CH10_Device_Xb_A_type (isp_dma_DMA_CH10_Device_Xb_A)—Offset 41328h" on page 1365	00000000h
4132Ch	4	"reg_isp_dma_DMA_CH11_Device_Xb_A_type (isp_dma_DMA_CH11_Device_Xb_A)—Offset 4132Ch" on page 1366	00000000h
41330h	4	"reg_isp_dma_DMA_CH12_Device_Xb_A_type (isp_dma_DMA_CH12_Device_Xb_A)—Offset 41330h" on page 1367	00000000h
41334h	4	"reg_isp_dma_DMA_CH13_Device_Xb_A_type (isp_dma_DMA_CH13_Device_Xb_A)—Offset 41334h" on page 1367	00000000h
41338h	4	"reg_isp_dma_DMA_CH14_Device_Xb_A_type (isp_dma_DMA_CH14_Device_Xb_A)—Offset 41338h" on page 1368	00000000h
4133Ch	4	"reg_isp_dma_DMA_CH15_Device_Xb_A_type (isp_dma_DMA_CH15_Device_Xb_A)—Offset 4133Ch" on page 1369	00000000h
41340h	4	"reg_isp_dma_DMA_CH16_Device_Xb_A_type (isp_dma_DMA_CH16_Device_Xb_A)—Offset 41340h" on page 1369	00000000h
41344h	4	"reg_isp_dma_DMA_CH17_Device_Xb_A_type (isp_dma_DMA_CH17_Device_Xb_A)—Offset 41344h" on page 1370	00000000h
41348h	4	"reg_isp_dma_DMA_CH18_Device_Xb_A_type (isp_dma_DMA_CH18_Device_Xb_A)—Offset 41348h" on page 1371	00000000h
4134Ch	4	"reg_isp_dma_DMA_CH19_Device_Xb_A_type (isp_dma_DMA_CH19_Device_Xb_A)—Offset 4134Ch" on page 1371	00000000h
41350h	4	"reg_isp_dma_DMA_CH20_Device_Xb_A_type (isp_dma_DMA_CH20_Device_Xb_A)—Offset 41350h" on page 1372	00000000h
41354h	4	"reg_isp_dma_DMA_CH21_Device_Xb_A_type (isp_dma_DMA_CH21_Device_Xb_A)—Offset 41354h" on page 1373	00000000h
41358h	4	"reg_isp_dma_DMA_CH22_Device_Xb_A_type (isp_dma_DMA_CH22_Device_Xb_A)—Offset 41358h" on page 1373	00000000h
4135Ch	4	"reg_isp_dma_DMA_CH23_Device_Xb_A_type (isp_dma_DMA_CH23_Device_Xb_A)—Offset 4135Ch" on page 1374	00000000h
41360h	4	"reg_isp_dma_DMA_CH24_Device_Xb_A_type (isp_dma_DMA_CH24_Device_Xb_A)—Offset 41360h" on page 1375	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41364h	4	"reg_isp_dma_DMA_CH25_Device_Xb_A_type (isp_dma_DMA_CH25_Device_Xb_A)—Offset 41364h" on page 1375	00000000h
41368h	4	"reg_isp_dma_DMA_CH26_Device_Xb_A_type (isp_dma_DMA_CH26_Device_Xb_A)—Offset 41368h" on page 1376	00000000h
4136Ch	4	"reg_isp_dma_DMA_CH27_Device_Xb_A_type (isp_dma_DMA_CH27_Device_Xb_A)—Offset 4136Ch" on page 1377	00000000h
41370h	4	"reg_isp_dma_DMA_CH28_Device_Xb_A_type (isp_dma_DMA_CH28_Device_Xb_A)—Offset 41370h" on page 1377	00000000h
41374h	4	"reg_isp_dma_DMA_CH29_Device_Xb_A_type (isp_dma_DMA_CH29_Device_Xb_A)—Offset 41374h" on page 1378	00000000h
41378h	4	"reg_isp_dma_DMA_CH30_Device_Xb_A_type (isp_dma_DMA_CH30_Device_Xb_A)—Offset 41378h" on page 1379	00000000h
4137Ch	4	"reg_isp_dma_DMA_CH31_Device_Xb_A_type (isp_dma_DMA_CH31_Device_Xb_A)—Offset 4137Ch" on page 1379	00000000h
41400h	4	"reg_isp_dma_DMA_CH0_dev_stride_B_type (isp_dma_DMA_CH0_dev_stride_B)—Offset 41400h" on page 1380	00000000h
41404h	4	"reg_isp_dma_DMA_CH1_dev_stride_B_type (isp_dma_DMA_CH1_dev_stride_B)—Offset 41404h" on page 1380	00000000h
41408h	4	"reg_isp_dma_DMA_CH2_dev_stride_B_type (isp_dma_DMA_CH2_dev_stride_B)—Offset 41408h" on page 1381	00000000h
4140Ch	4	"reg_isp_dma_DMA_CH3_dev_stride_B_type (isp_dma_DMA_CH3_dev_stride_B)—Offset 4140Ch" on page 1382	00000000h
41410h	4	"reg_isp_dma_DMA_CH4_dev_stride_B_type (isp_dma_DMA_CH4_dev_stride_B)—Offset 41410h" on page 1382	00000000h
41414h	4	"reg_isp_dma_DMA_CH5_dev_stride_B_type (isp_dma_DMA_CH5_dev_stride_B)—Offset 41414h" on page 1383	00000000h
41418h	4	"reg_isp_dma_DMA_CH6_dev_stride_B_type (isp_dma_DMA_CH6_dev_stride_B)—Offset 41418h" on page 1383	00000000h
4141Ch	4	"reg_isp_dma_DMA_CH7_dev_stride_B_type (isp_dma_DMA_CH7_dev_stride_B)—Offset 4141Ch" on page 1384	00000000h
41420h	4	"reg_isp_dma_DMA_CH8_dev_stride_B_type (isp_dma_DMA_CH8_dev_stride_B)—Offset 41420h" on page 1384	00000000h
41424h	4	"reg_isp_dma_DMA_CH9_dev_stride_B_type (isp_dma_DMA_CH9_dev_stride_B)—Offset 41424h" on page 1385	00000000h
41428h	4	"reg_isp_dma_DMA_CH10_dev_stride_B_type (isp_dma_DMA_CH10_dev_stride_B)—Offset 41428h" on page 1385	00000000h
4142Ch	4	"reg_isp_dma_DMA_CH11_dev_stride_B_type (isp_dma_DMA_CH11_dev_stride_B)—Offset 4142Ch" on page 1386	00000000h
41430h	4	"reg_isp_dma_DMA_CH12_dev_stride_B_type (isp_dma_DMA_CH12_dev_stride_B)—Offset 41430h" on page 1386	00000000h
41434h	4	"reg_isp_dma_DMA_CH13_dev_stride_B_type (isp_dma_DMA_CH13_dev_stride_B)—Offset 41434h" on page 1387	00000000h
41438h	4	"reg_isp_dma_DMA_CH14_dev_stride_B_type (isp_dma_DMA_CH14_dev_stride_B)—Offset 41438h" on page 1387	00000000h
4143Ch	4	"reg_isp_dma_DMA_CH15_dev_stride_B_type (isp_dma_DMA_CH15_dev_stride_B)—Offset 4143Ch" on page 1388	00000000h
41440h	4	"reg_isp_dma_DMA_CH16_dev_stride_B_type (isp_dma_DMA_CH16_dev_stride_B)—Offset 41440h" on page 1388	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41444h	4	"reg_isp_dma_DMA_CH17_dev_stride_B_type (isp_dma_DMA_CH17_dev_stride_B)—Offset 41444h" on page 1389	00000000h
41448h	4	"reg_isp_dma_DMA_CH18_dev_stride_B_type (isp_dma_DMA_CH18_dev_stride_B)—Offset 41448h" on page 1389	00000000h
4144Ch	4	"reg_isp_dma_DMA_CH19_dev_stride_B_type (isp_dma_DMA_CH19_dev_stride_B)—Offset 4144Ch" on page 1390	00000000h
41450h	4	"reg_isp_dma_DMA_CH20_dev_stride_B_type (isp_dma_DMA_CH20_dev_stride_B)—Offset 41450h" on page 1391	00000000h
41454h	4	"reg_isp_dma_DMA_CH21_dev_stride_B_type (isp_dma_DMA_CH21_dev_stride_B)—Offset 41454h" on page 1391	00000000h
41458h	4	"reg_isp_dma_DMA_CH22_dev_stride_B_type (isp_dma_DMA_CH22_dev_stride_B)—Offset 41458h" on page 1392	00000000h
4145Ch	4	"reg_isp_dma_DMA_CH23_dev_stride_B_type (isp_dma_DMA_CH23_dev_stride_B)—Offset 4145Ch" on page 1392	00000000h
41460h	4	"reg_isp_dma_DMA_CH24_dev_stride_B_type (isp_dma_DMA_CH24_dev_stride_B)—Offset 41460h" on page 1393	00000000h
41468h	4	"reg_isp_dma_DMA_CH26_dev_stride_B_type (isp_dma_DMA_CH26_dev_stride_B)—Offset 41468h" on page 1393	00000000h
4146Ch	4	"reg_isp_dma_DMA_CH27_dev_stride_B_type (isp_dma_DMA_CH27_dev_stride_B)—Offset 4146Ch" on page 1394	00000000h
41470h	4	"reg_isp_dma_DMA_CH28_dev_stride_B_type (isp_dma_DMA_CH28_dev_stride_B)—Offset 41470h" on page 1394	00000000h
41474h	4	"reg_isp_dma_DMA_CH29_dev_stride_B_type (isp_dma_DMA_CH29_dev_stride_B)—Offset 41474h" on page 1395	00000000h
41478h	4	"reg_isp_dma_DMA_CH30_dev_stride_B_type (isp_dma_DMA_CH30_dev_stride_B)—Offset 41478h" on page 1396	00000000h
4147Ch	4	"reg_isp_dma_DMA_CH31_dev_stride_B_type (isp_dma_DMA_CH31_dev_stride_B)—Offset 4147Ch" on page 1396	00000000h
41500h	4	"reg_isp_dma_DMA_CH0_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH0_dev_Pack_left_crop_and_elem_B)—Offset 41500h" on page 1397	00000000h
41504h	4	"reg_isp_dma_DMA_CH1_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH1_dev_Pack_left_crop_and_elem_B)—Offset 41504h" on page 1398	00000000h
41508h	4	"reg_isp_dma_DMA_CH2_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH2_dev_Pack_left_crop_and_elem_B)—Offset 41508h" on page 1398	00000000h
4150Ch	4	"reg_isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_B)—Offset 4150Ch" on page 1399	00000000h
41510h	4	"reg_isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_B)—Offset 41510h" on page 1400	00000000h
41514h	4	"reg_isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_B)—Offset 41514h" on page 1401	00000000h
41518h	4	"reg_isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_B)—Offset 41518h" on page 1402	00000000h




Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
4151Ch	4	"reg_isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_B)—Offset 4151Ch" on page 1403	00000000h
41520h	4	"reg_isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_B)—Offset 41520h" on page 1404	00000000h
41524h	4	"reg_isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_B)—Offset 41524h" on page 1405	00000000h
41528h	4	"reg_isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_B)—Offset 41528h" on page 1406	00000000h
4152Ch	4	"reg_isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_B)—Offset 4152Ch" on page 1407	00000000h
41530h	4	"reg_isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_B)—Offset 41530h" on page 1408	00000000h
41534h	4	"reg_isp_dma_DMA_CH13_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH13_dev_Pack_left_crop_and_elem_B)—Offset 41534h" on page 1409	00000000h
41538h	4	"reg_isp_dma_DMA_CH14_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH14_dev_Pack_left_crop_and_elem_B)—Offset 41538h" on page 1410	00000000h
4153Ch	4	"reg_isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_B)—Offset 4153Ch" on page 1411	00000000h
41540h	4	"reg_isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_B)—Offset 41540h" on page 1412	00000000h
41544h	4	"reg_isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_B)—Offset 41544h" on page 1413	00000000h
41548h	4	"reg_isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_B)—Offset 41548h" on page 1414	00000000h
4154Ch	4	"reg_isp_dma_DMA_CH19_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH19_dev_Pack_left_crop_and_elem_B)—Offset 4154Ch" on page 1415	00000000h
41550h	4	"reg_isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_B)—Offset 41550h" on page 1416	00000000h
41554h	4	"reg_isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_B)—Offset 41554h" on page 1417	00000000h
41558h	4	"reg_isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_B)—Offset 41558h" on page 1418	00000000h
4155Ch	4	"reg_isp_dma_DMA_CH23_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH23_dev_Pack_left_crop_and_elem_B)—Offset 4155Ch" on page 1419	00000000h
41560h	4	"reg_isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_B)—Offset 41560h" on page 1420	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41564h	4	"reg_isp_dma_DMA_CH25_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH25_dev_Pack_left_crop_and_elem_B)—Offset 41564h" on page 1421	00000000h
41568h	4	"reg_isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_B)—Offset 41568h" on page 1422	00000000h
4156Ch	4	"reg_isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_B)—Offset 4156Ch" on page 1423	00000000h
41570h	4	"reg_isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_B)—Offset 41570h" on page 1424	00000000h
41574h	4	"reg_isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_B)—Offset 41574h" on page 1425	00000000h
41578h	4	"reg_isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_B)—Offset 41578h" on page 1426	00000000h
4157Ch	4	"reg_isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_B)—Offset 4157Ch" on page 1427	00000000h
41600h	4	"reg_isp_dma_DMA_CH0_Device_Xb_B_type (isp_dma_DMA_CH0_Device_Xb_B)—Offset 41600h" on page 1428	00000000h
41604h	4	"reg_isp_dma_DMA_CH1_Device_Xb_B_type (isp_dma_DMA_CH1_Device_Xb_B)—Offset 41604h" on page 1429	00000000h
41608h	4	"reg_isp_dma_DMA_CH2_Device_Xb_B_type (isp_dma_DMA_CH2_Device_Xb_B)—Offset 41608h" on page 1430	00000000h
4160Ch	4	"reg_isp_dma_DMA_CH3_Device_Xb_B_type (isp_dma_DMA_CH3_Device_Xb_B)—Offset 4160Ch" on page 1430	00000000h
41610h	4	"reg_isp_dma_DMA_CH4_Device_Xb_B_type (isp_dma_DMA_CH4_Device_Xb_B)—Offset 41610h" on page 1431	00000000h
41614h	4	"reg_isp_dma_DMA_CH5_Device_Xb_B_type (isp_dma_DMA_CH5_Device_Xb_B)—Offset 41614h" on page 1432	00000000h
41618h	4	"reg_isp_dma_DMA_CH6_Device_Xb_B_type (isp_dma_DMA_CH6_Device_Xb_B)—Offset 41618h" on page 1432	00000000h
4161Ch	4	"reg_isp_dma_DMA_CH7_Device_Xb_B_type (isp_dma_DMA_CH7_Device_Xb_B)—Offset 4161Ch" on page 1433	00000000h
41620h	4	"reg_isp_dma_DMA_CH8_Device_Xb_B_type (isp_dma_DMA_CH8_Device_Xb_B)—Offset 41620h" on page 1434	00000000h
41624h	4	"reg_isp_dma_DMA_CH9_Device_Xb_B_type (isp_dma_DMA_CH9_Device_Xb_B)—Offset 41624h" on page 1434	00000000h
41628h	4	"reg_isp_dma_DMA_CH10_Device_Xb_B_type (isp_dma_DMA_CH10_Device_Xb_B)—Offset 41628h" on page 1435	00000000h
4162Ch	4	"reg_isp_dma_DMA_CH11_Device_Xb_B_type (isp_dma_DMA_CH11_Device_Xb_B)—Offset 4162Ch" on page 1436	00000000h
41630h	4	"reg_isp_dma_DMA_CH12_Device_Xb_B_type (isp_dma_DMA_CH12_Device_Xb_B)—Offset 41630h" on page 1436	00000000h
41634h	4	"reg_isp_dma_DMA_CH13_Device_Xb_B_type (isp_dma_DMA_CH13_Device_Xb_B)—Offset 41634h" on page 1437	00000000h
41638h	4	"reg_isp_dma_DMA_CH14_Device_Xb_B_type (isp_dma_DMA_CH14_Device_Xb_B)—Offset 41638h" on page 1438	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
4163Ch	4	"reg_isp_dma_DMA_CH15_Device_Xb_B_type (isp_dma_DMA_CH15_Device_Xb_B)—Offset 4163Ch" on page 1438	00000000h
41640h	4	"reg_isp_dma_DMA_CH16_Device_Xb_B_type (isp_dma_DMA_CH16_Device_Xb_B)—Offset 41640h" on page 1439	00000000h
41644h	4	"reg_isp_dma_DMA_CH17_Device_Xb_B_type (isp_dma_DMA_CH17_Device_Xb_B)—Offset 41644h" on page 1440	00000000h
41648h	4	"reg_isp_dma_DMA_CH18_Device_Xb_B_type (isp_dma_DMA_CH18_Device_Xb_B)—Offset 41648h" on page 1440	00000000h
4164Ch	4	"reg_isp_dma_DMA_CH19_Device_Xb_B_type (isp_dma_DMA_CH19_Device_Xb_B)—Offset 4164Ch" on page 1441	00000000h
41650h	4	"reg_isp_dma_DMA_CH20_Device_Xb_B_type (isp_dma_DMA_CH20_Device_Xb_B)—Offset 41650h" on page 1442	00000000h
41654h	4	"reg_isp_dma_DMA_CH21_Device_Xb_B_type (isp_dma_DMA_CH21_Device_Xb_B)—Offset 41654h" on page 1442	00000000h
41658h	4	"reg_isp_dma_DMA_CH22_Device_Xb_B_type (isp_dma_DMA_CH22_Device_Xb_B)—Offset 41658h" on page 1443	00000000h
4165Ch	4	"reg_isp_dma_DMA_CH23_Device_Xb_B_type (isp_dma_DMA_CH23_Device_Xb_B)—Offset 4165Ch" on page 1444	00000000h
41660h	4	"reg_isp_dma_DMA_CH24_Device_Xb_B_type (isp_dma_DMA_CH24_Device_Xb_B)—Offset 41660h" on page 1444	00000000h
41664h	4	"reg_isp_dma_DMA_CH25_Device_Xb_B_type (isp_dma_DMA_CH25_Device_Xb_B)—Offset 41664h" on page 1445	00000000h
41668h	4	"reg_isp_dma_DMA_CH26_Device_Xb_B_type (isp_dma_DMA_CH26_Device_Xb_B)—Offset 41668h" on page 1446	00000000h
4166Ch	4	"reg_isp_dma_DMA_CH27_Device_Xb_B_type (isp_dma_DMA_CH27_Device_Xb_B)—Offset 4166Ch" on page 1446	00000000h
41670h	4	"reg_isp_dma_DMA_CH28_Device_Xb_B_type (isp_dma_DMA_CH28_Device_Xb_B)—Offset 41670h" on page 1447	00000000h
41674h	4	"reg_isp_dma_DMA_CH29_Device_Xb_B_type (isp_dma_DMA_CH29_Device_Xb_B)—Offset 41674h" on page 1448	00000000h
41678h	4	"reg_isp_dma_DMA_CH31_Device_Xb_B_type (isp_dma_DMA_CH31_Device_Xb_B)—Offset 41678h" on page 1448	00000000h
41700h	4	"reg_isp_dma_DMA_CH0_Yb_type (isp_dma_DMA_CH0_Yb)—Offset 41700h" on page 1449	00000000h
41704h	4	"reg_isp_dma_DMA_CH1_Yb_type (isp_dma_DMA_CH1_Yb)—Offset 41704h" on page 1450	00000000h
41708h	4	"reg_isp_dma_DMA_CH2_Yb_type (isp_dma_DMA_CH2_Yb)—Offset 41708h" on page 1450	00000000h
4170Ch	4	"reg_isp_dma_DMA_CH3_Yb_type (isp_dma_DMA_CH3_Yb)—Offset 4170Ch" on page 1451	00000000h
41710h	4	"reg_isp_dma_DMA_CH4_Yb_type (isp_dma_DMA_CH4_Yb)—Offset 41710h" on page 1451	00000000h
41714h	4	"reg_isp_dma_DMA_CH5_Yb_type (isp_dma_DMA_CH5_Yb)—Offset 41714h" on page 1452	00000000h
41718h	4	"reg_isp_dma_DMA_CH6_Yb_type (isp_dma_DMA_CH6_Yb)—Offset 41718h" on page 1452	00000000h
4171Ch	4	"reg_isp_dma_DMA_CH7_Yb_type (isp_dma_DMA_CH7_Yb)—Offset 4171Ch" on page 1453	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41720h	4	"reg_isp_dma_DMA_CH8_Yb_type (isp_dma_DMA_CH8_Yb)—Offset 41720h" on page 1454	00000000h
41724h	4	"reg_isp_dma_DMA_CH9_Yb_type (isp_dma_DMA_CH9_Yb)—Offset 41724h" on page 1454	00000000h
41728h	4	"reg_isp_dma_DMA_CH10_Yb_type (isp_dma_DMA_CH10_Yb)—Offset 41728h" on page 1455	00000000h
4172Ch	4	"reg_isp_dma_DMA_CH11_Yb_type (isp_dma_DMA_CH11_Yb)—Offset 4172Ch" on page 1455	00000000h
41730h	4	"reg_isp_dma_DMA_CH12_Yb_type (isp_dma_DMA_CH12_Yb)—Offset 41730h" on page 1456	00000000h
41734h	4	"reg_isp_dma_DMA_CH13_Yb_type (isp_dma_DMA_CH13_Yb)—Offset 41734h" on page 1456	00000000h
41738h	4	"reg_isp_dma_DMA_CH14_Yb_type (isp_dma_DMA_CH14_Yb)—Offset 41738h" on page 1457	00000000h
4173Ch	4	"reg_isp_dma_DMA_CH15_Yb_type (isp_dma_DMA_CH15_Yb)—Offset 4173Ch" on page 1458	00000000h
41740h	4	"reg_isp_dma_DMA_CH16_Yb_type (isp_dma_DMA_CH16_Yb)—Offset 41740h" on page 1458	00000000h
41744h	4	"reg_isp_dma_DMA_CH17_Yb_type (isp_dma_DMA_CH17_Yb)—Offset 41744h" on page 1459	00000000h
41748h	4	"reg_isp_dma_DMA_CH18_Yb_type (isp_dma_DMA_CH18_Yb)—Offset 41748h" on page 1459	00000000h
4174Ch	4	"reg_isp_dma_DMA_CH19_Yb_type (isp_dma_DMA_CH19_Yb)—Offset 4174Ch" on page 1460	00000000h
41750h	4	"reg_isp_dma_DMA_CH20_Yb_type (isp_dma_DMA_CH20_Yb)—Offset 41750h" on page 1460	00000000h
41754h	4	"reg_isp_dma_DMA_CH21_Yb_type (isp_dma_DMA_CH21_Yb)—Offset 41754h" on page 1461	00000000h
41758h	4	"reg_isp_dma_DMA_CH22_Yb_type (isp_dma_DMA_CH22_Yb)—Offset 41758h" on page 1462	00000000h
4175Ch	4	"reg_isp_dma_DMA_CH23_Yb_type (isp_dma_DMA_CH23_Yb)—Offset 4175Ch" on page 1462	00000000h
41760h	4	"reg_isp_dma_DMA_CH24_Yb_type (isp_dma_DMA_CH24_Yb)—Offset 41760h" on page 1463	00000000h
41764h	4	"reg_isp_dma_DMA_CH25_Yb_type (isp_dma_DMA_CH25_Yb)—Offset 41764h" on page 1463	00000000h
41768h	4	"reg_isp_dma_DMA_CH26_Yb_type (isp_dma_DMA_CH26_Yb)—Offset 41768h" on page 1464	00000000h
4176Ch	4	"reg_isp_dma_DMA_CH27_Yb_type (isp_dma_DMA_CH27_Yb)—Offset 4176Ch" on page 1464	00000000h
41770h	4	"reg_isp_dma_DMA_CH28_Yb_type (isp_dma_DMA_CH28_Yb)—Offset 41770h" on page 1465	00000000h
41774h	4	"reg_isp_dma_DMA_CH29_Yb_type (isp_dma_DMA_CH29_Yb)—Offset 41774h" on page 1466	00000000h
4177Ch	4	"reg_isp_dma_DMA_CH31_Yb_type (isp_dma_DMA_CH31_Yb)—Offset 4177Ch" on page 1466	00000000h
41800h	4	"reg_isp_dma_DMA_CH0_pending_command_type (isp_dma_DMA_CH0_pending_command)—Offset 41800h" on page 1467	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41804h	4	"reg_isp_dma_DMA_CH1_pending_command_type (isp_dma_DMA_CH1_pending_command)—Offset 41804h" on page 1467	00000000h
41808h	4	"reg_isp_dma_DMA_CH2_pending_command_type (isp_dma_DMA_CH2_pending_command)—Offset 41808h" on page 1468	00000000h
4180Ch	4	"reg_isp_dma_DMA_CH3_pending_command_type (isp_dma_DMA_CH3_pending_command)—Offset 4180Ch" on page 1469	00000000h
41810h	4	"reg_isp_dma_DMA_CH4_pending_command_type (isp_dma_DMA_CH4_pending_command)—Offset 41810h" on page 1469	00000000h
41814h	4	"reg_isp_dma_DMA_CH5_pending_command_type (isp_dma_DMA_CH5_pending_command)—Offset 41814h" on page 1470	00000000h
41818h	4	"reg_isp_dma_DMA_CH6_pending_command_type (isp_dma_DMA_CH6_pending_command)—Offset 41818h" on page 1471	00000000h
4181Ch	4	"reg_isp_dma_DMA_CH7_pending_command_type (isp_dma_DMA_CH7_pending_command)—Offset 4181Ch" on page 1471	00000000h
41820h	4	"reg_isp_dma_DMA_CH8_pending_command_type (isp_dma_DMA_CH8_pending_command)—Offset 41820h" on page 1472	00000000h
41824h	4	"reg_isp_dma_DMA_CH9_pending_command_type (isp_dma_DMA_CH9_pending_command)—Offset 41824h" on page 1473	00000000h
41828h	4	"reg_isp_dma_DMA_CH10_pending_command_type (isp_dma_DMA_CH10_pending_command)—Offset 41828h" on page 1473	00000000h
4182Ch	4	"reg_isp_dma_DMA_CH11_pending_command_type (isp_dma_DMA_CH11_pending_command)—Offset 4182Ch" on page 1474	00000000h
41830h	4	"reg_isp_dma_DMA_CH12_pending_command_type (isp_dma_DMA_CH12_pending_command)—Offset 41830h" on page 1475	00000000h
41834h	4	"reg_isp_dma_DMA_CH13_pending_command_type (isp_dma_DMA_CH13_pending_command)—Offset 41834h" on page 1475	00000000h
41838h	4	"reg_isp_dma_DMA_CH14_pending_command_type (isp_dma_DMA_CH14_pending_command)—Offset 41838h" on page 1476	00000000h
4183Ch	4	"reg_isp_dma_DMA_CH15_pending_command_type (isp_dma_DMA_CH15_pending_command)—Offset 4183Ch" on page 1477	00000000h
41840h	4	"reg_isp_dma_DMA_CH16_pending_command_type (isp_dma_DMA_CH16_pending_command)—Offset 41840h" on page 1477	00000000h
41844h	4	"reg_isp_dma_DMA_CH17_pending_command_type (isp_dma_DMA_CH17_pending_command)—Offset 41844h" on page 1478	00000000h
41848h	4	"reg_isp_dma_DMA_CH18_pending_command_type (isp_dma_DMA_CH18_pending_command)—Offset 41848h" on page 1479	00000000h
4184Ch	4	"reg_isp_dma_DMA_CH19_pending_command_type (isp_dma_DMA_CH19_pending_command)—Offset 4184Ch" on page 1479	00000000h
41850h	4	"reg_isp_dma_DMA_CH20_pending_command_type (isp_dma_DMA_CH20_pending_command)—Offset 41850h" on page 1480	00000000h
41854h	4	"reg_isp_dma_DMA_CH21_pending_command_type (isp_dma_DMA_CH21_pending_command)—Offset 41854h" on page 1481	00000000h
41858h	4	"reg_isp_dma_DMA_CH22_pending_command_type (isp_dma_DMA_CH22_pending_command)—Offset 41858h" on page 1481	00000000h
4185Ch	4	"reg_isp_dma_DMA_CH23_pending_command_type (isp_dma_DMA_CH23_pending_command)—Offset 4185Ch" on page 1482	00000000h
41860h	4	"reg_isp_dma_DMA_CH24_pending_command_type (isp_dma_DMA_CH24_pending_command)—Offset 41860h" on page 1483	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
41864h	4	"reg_isp_dma_DMA_CH25_pending_command_type (isp_dma_DMA_CH25_pending_command)—Offset 41864h" on page 1483	00000000h
41868h	4	"reg_isp_dma_DMA_CH26_pending_command_type (isp_dma_DMA_CH26_pending_command)—Offset 41868h" on page 1484	00000000h
4186Ch	4	"reg_isp_dma_DMA_CH27_pending_command_type (isp_dma_DMA_CH27_pending_command)—Offset 4186Ch" on page 1485	00000000h
41870h	4	"reg_isp_dma_DMA_CH28_pending_command_type (isp_dma_DMA_CH28_pending_command)—Offset 41870h" on page 1485	00000000h
41874h	4	"reg_isp_dma_DMA_CH29_pending_command_type (isp_dma_DMA_CH29_pending_command)—Offset 41874h" on page 1486	00000000h
41878h	4	"reg_isp_dma_DMA_CH30_pending_command_type (isp_dma_DMA_CH30_pending_command)—Offset 41878h" on page 1487	00000000h
4187Ch	4	"reg_isp_dma_DMA_CH31_pending_command_type (isp_dma_DMA_CH31_pending_command)—Offset 4187Ch" on page 1487	00000000h
42000h	4	"reg_isp_dma_DMA_command_token_type (isp_dma_DMA_command_token)—Offset 42000h" on page 1488	00000000h
42004h	4	"reg_isp_dma_DMA_command_src_addr_type (isp_dma_DMA_command_src_addr)—Offset 42004h" on page 1489	00000000h
42008h	4	"reg_isp_dma_DMA_command_dst_addr_type (isp_dma_DMA_command_dst_addr)—Offset 42008h" on page 1489	00000000h
4200Ch	4	"reg_isp_dma_DMA_command_ctrl_id_type (isp_dma_DMA_command_ctrl_id)—Offset 4200Ch" on page 1490	00000000h
42010h	4	"reg_isp_dma_DMA_FSM_Ctrl_status_type (isp_dma_DMA_FSM_Ctrl_status)—Offset 42010h" on page 1490	00000001h
42014h	4	"reg_isp_dma_DMA_FSM_Pack_status_type (isp_dma_DMA_FSM_Pack_status)—Offset 42014h" on page 1491	00000001h
42018h	4	"reg_isp_dma_DMA_FSM_request_status_type (isp_dma_DMA_FSM_request_status)—Offset 42018h" on page 1492	00000000h
4201Ch	4	"reg_isp_dma_DMA_FSM_write_status_type (isp_dma_DMA_FSM_write_status)—Offset 4201Ch" on page 1493	00000000h
42110h	4	"reg_isp_dma_DMA_FSM_Ctrl_dev_idx_type (isp_dma_DMA_FSM_Ctrl_dev_idx)—Offset 42110h" on page 1493	00000000h
42114h	4	"reg_isp_dma_DMA_FSM_Pack_cnt_Yb_type (isp_dma_DMA_FSM_Pack_cnt_Yb)—Offset 42114h" on page 1494	00000000h
42118h	4	"reg_isp_dma_DMA_FSM_Request_cnt_Yb_type (isp_dma_DMA_FSM_Request_cnt_Yb)—Offset 42118h" on page 1495	00000000h
4211Ch	4	"reg_isp_dma_DMA_FSM_Write_cnt_Y_type (isp_dma_DMA_FSM_Write_cnt_Y)—Offset 4211Ch" on page 1495	00000000h
42210h	4	"reg_isp_dma_DMA_FSM_Ctrl_req_addr_type (isp_dma_DMA_FSM_Ctrl_req_addr)—Offset 42210h" on page 1496	00000000h
42214h	4	"reg_isp_dma_DMA_FSM_Pack_req_cnt_Xb_type (isp_dma_DMA_FSM_Pack_req_cnt_Xb)—Offset 42214h" on page 1496	00000000h
42218h	4	"reg_isp_dma_DMA_FSM_Request_cnt_Xb_type (isp_dma_DMA_FSM_Request_cnt_Xb)—Offset 42218h" on page 1497	00000000h
4221Ch	4	"reg_isp_dma_DMA_FSM_Write_cnt_Xb_type (isp_dma_DMA_FSM_Write_cnt_Xb)—Offset 4221Ch" on page 1498	00000000h
42310h	4	"reg_isp_dma_DMA_FSM_Ctrl_req_stride_type (isp_dma_DMA_FSM_Ctrl_req_stride)—Offset 42310h" on page 1499	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
42314h	4	"reg_isp_dma_DMA_FSM_Pack_wr_cnt_Xb_type (isp_dma_DMA_FSM_Pack_wr_cnt_Xb)—Offset 42314h" on page 1499	00000000h
42318h	4	"reg_isp_dma_DMA_FSM_Req_remining_Xb_type (isp_dma_DMA_FSM_Req_remining_Xb)—Offset 42318h" on page 1500	00000000h
4231Ch	4	"reg_isp_dma_DMA_FSM_Wr_remining_Xb_type (isp_dma_DMA_FSM_Wr_remining_Xb)—Offset 4231Ch" on page 1501	00000000h
42410h	4	"reg_isp_dma_DMA_FSM_Ctrl_req_Xb_type (isp_dma_DMA_FSM_Ctrl_req_Xb)—Offset 42410h" on page 1501	00000000h
42418h	4	"reg_isp_dma_DMA_FSM_Req_burst_cnt_type (isp_dma_DMA_FSM_Req_burst_cnt)—Offset 42418h" on page 1502	0000FFFFh
4241Ch	4	"reg_isp_dma_DMA_FSM_Wr_burst_cnt_type (isp_dma_DMA_FSM_Wr_burst_cnt)—Offset 4241Ch" on page 1503	0000FFFFh
42510h	4	"reg_isp_dma_DMA_FSM_Ctrl_req_Yb_type (isp_dma_DMA_FSM_Ctrl_req_Yb)—Offset 42510h" on page 1503	00000000h
42610h	4	"reg_isp_dma_DMA_FSM_Ctrl_Pack_req_dev_idx_type (isp_dma_DMA_FSM_Ctrl_Pack_req_dev_idx)—Offset 42610h" on page 1504	00000000h
42710h	4	"reg_isp_dma_DMA_FSM_Ctrl_Pack_wr_dev_idx_type (isp_dma_DMA_FSM_Ctrl_Pack_wr_dev_idx)—Offset 42710h" on page 1505	00000000h
42810h	4	"reg_isp_dma_DMA_FSM_Ctrl_Wr_addr_type (isp_dma_DMA_FSM_Ctrl_Wr_addr)—Offset 42810h" on page 1505	00000000h
42910h	4	"reg_isp_dma_DMA_FSM_Ctrl_Wr_stride_type (isp_dma_DMA_FSM_Ctrl_Wr_stride)—Offset 42910h" on page 1506	00000000h
42A10h	4	"reg_isp_dma_DMA_FSM_Ctrl_pack_req_Xb_type (isp_dma_DMA_FSM_Ctrl_pack_req_Xb)—Offset 42A10h" on page 1506	00000000h
42B10h	4	"reg_isp_dma_DMA_FSM_Ctrl_pack_Yb_type (isp_dma_DMA_FSM_Ctrl_pack_Yb)—Offset 42B10h" on page 1507	00000000h
42C10h	4	"reg_isp_dma_DMA_FSM_Ctrl_pack_wr_Xb_type (isp_dma_DMA_FSM_Ctrl_pack_wr_Xb)—Offset 42C10h" on page 1508	00000000h
42D10h	4	"reg_isp_dma_DMA_FSM_Ctrl_pack_req_elem_type (isp_dma_DMA_FSM_Ctrl_pack_req_elem)—Offset 42D10h" on page 1508	00000000h
42E10h	4	"reg_isp_dma_DMA_FSM_Ctrl_pack_wr_elem_type (isp_dma_DMA_FSM_Ctrl_pack_wr_elem)—Offset 42E10h" on page 1509	00000000h
42F10h	4	"reg_isp_dma_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id_type (isp_dma_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id)—Offset 42F10h" on page 1510	00000000h
43000h	4	"reg_isp_dma_Dev_Interf_0_req_side_type (isp_dma_Dev_Interf_0_req_side)—Offset 43000h" on page 1511	00000000h
43004h	4	"reg_isp_dma_Dev_Interf_1_req_side_type (isp_dma_Dev_Interf_1_req_side)—Offset 43004h" on page 1511	00000006h
43008h	4	"reg_isp_dma_Dev_Interf_2_req_side_type (isp_dma_Dev_Interf_2_req_side)—Offset 43008h" on page 1512	00000006h
43100h	4	"reg_isp_dma_Dev_Interf_0_snd_side_type (isp_dma_Dev_Interf_0_snd_side)—Offset 43100h" on page 1513	00000004h
43104h	4	"reg_isp_dma_Dev_Interf_1_snd_side_type (isp_dma_Dev_Interf_1_snd_side)—Offset 43104h" on page 1514	00000006h
43108h	4	"reg_isp_dma_Dev_Interf_2_snd_side_type (isp_dma_Dev_Interf_2_snd_side)—Offset 43108h" on page 1514	00000006h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMADR (Continued)

Offset	Size	Register ID—Description	Default Value
43200h	4	"reg_isp_dma_Dev_Interf_0_Fifo_status_type (isp_dma_Dev_Interf_0_Fifo_status)—Offset 43200h" on page 1515	00000004h
43204h	4	"reg_isp_dma_Dev_Interf_1_Fifo_status_type (isp_dma_Dev_Interf_1_Fifo_status)—Offset 43204h" on page 1516	00000004h
43208h	4	"reg_isp_dma_Dev_Interf_2_Fifo_status_type (isp_dma_Dev_Interf_2_Fifo_status)—Offset 43208h" on page 1517	00000004h
43300h	4	"reg_isp_dma_Dev_Interf_0_Req_complete_burst_type (isp_dma_Dev_Interf_0_Req_complete_burst)—Offset 43300h" on page 1518	00000000h
43304h	4	"reg_isp_dma_Dev_Interf_1_Req_complete_burst_type (isp_dma_Dev_Interf_1_Req_complete_burst)—Offset 43304h" on page 1519	00000000h
43308h	4	"reg_isp_dma_Dev_Interf_2_Req_complete_burst_type (isp_dma_Dev_Interf_2_Req_complete_burst)—Offset 43308h" on page 1520	00000000h
43408h	4	"reg_isp_dma_Dev_Interf_2_Max_burst_Size_type (isp_dma_Dev_Interf_2_Max_burst_Size)—Offset 43408h" on page 1520	0000007Fh
50000h	4	"reg_gdc1_reg0_type (gdc1_reg0)—Offset 50000h" on page 1521	00000000h
50004h	4	"reg_gdc1_woi_x_type (gdc1_woi_x)—Offset 50004h" on page 1522	00000000h
50008h	4	"reg_gdc1_woi_y_type (gdc1_woi_y)—Offset 50008h" on page 1522	00000000h
5000Ch	4	"reg_gdc1_bpp_type (gdc1_bpp)—Offset 5000Ch" on page 1523	00000000h
50010h	4	"reg_gdc1_fryipxfrx_start_type (gdc1_fryipxfrx_start)—Offset 50010h" on page 1523	00000000h
50014h	4	"reg_gdc1_oxdim_type (gdc1_oxdim)—Offset 50014h" on page 1524	00000000h
50018h	4	"reg_gdc1_oydim_type (gdc1_oydim)—Offset 50018h" on page 1524	00000000h
5001Ch	4	"reg_gdc1_src_addr_type (gdc1_src_addr)—Offset 5001Ch" on page 1525	00000000h
50020h	4	"reg_gdc1_src_end_type (gdc1_src_end)—Offset 50020h" on page 1525	00000000h
50024h	4	"reg_gdc1_src_wrap_type (gdc1_src_wrap)—Offset 50024h" on page 1526	00000000h
50028h	4	"reg_gdc1_src_stride_type (gdc1_src_stride)—Offset 50028h" on page 1526	00000000h
5002Ch	4	"reg_gdc1_dst_addr_type (gdc1_dst_addr)—Offset 5002Ch" on page 1527	00000000h
50030h	4	"reg_gdc1_dst_stride_type (gdc1_dst_stride)—Offset 50030h" on page 1527	00000000h
50034h	4	"reg_gdc1_dx_type (gdc1_dx)—Offset 50034h" on page 1528	00000000h
50038h	4	"reg_gdc1_dy_type (gdc1_dy)—Offset 50038h" on page 1528	00000000h
5003Ch	4	"reg_gdc1_P0_primX_ixdim_type (gdc1_P0_primX_ixdim)—Offset 5003Ch" on page 1529	00000000h
50040h	4	"reg_gdc1_P0_primY_iydim_type (gdc1_P0_primY_iydim)—Offset 50040h" on page 1529	00000000h
50044h	4	"reg_gdc1_P1_primX_type (gdc1_P1_primX)—Offset 50044h" on page 1530	00000000h
50048h	4	"reg_gdc1_P1_primY_type (gdc1_P1_primY)—Offset 50048h" on page 1530	00000000h
5004Ch	4	"reg_gdc1_P2_primX_type (gdc1_P2_primX)—Offset 5004Ch" on page 1531	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
50050h	4	"reg_gdc1_P2_primY_type (gdc1_P2_primY)—Offset 50050h" on page 1531	00000000h
50054h	4	"reg_gdc1_P3_primX_type (gdc1_P3_primX)—Offset 50054h" on page 1532	00000000h
50058h	4	"reg_gdc1_P3_primY_type (gdc1_P3_primY)—Offset 50058h" on page 1532	00000000h
5005Ch	4	"reg_gdc1_perf_mode_type (gdc1_perf_mode)—Offset 5005Ch" on page 1533	00000000h
50060h	4	"reg_gdc1_interp_type_type (gdc1_interp_type)—Offset 50060h" on page 1534	00000000h
50064h	4	"reg_gdc1_scan_mode_type (gdc1_scan_mode)—Offset 50064h" on page 1534	00000000h
50068h	4	"reg_gdc1_proc_mode_type (gdc1_proc_mode)—Offset 50068h" on page 1535	00000000h
60000h	4	"reg_gdc2_reg0_type (gdc2_reg0)—Offset 60000h" on page 1535	00000000h
60004h	4	"reg_gdc2_woi_x_type (gdc2_woi_x)—Offset 60004h" on page 1536	00000000h
60008h	4	"reg_gdc2_woi_y_type (gdc2_woi_y)—Offset 60008h" on page 1536	00000000h
6000Ch	4	"reg_gdc2_bpp_type (gdc2_bpp)—Offset 6000Ch" on page 1537	00000000h
60010h	4	"reg_gdc2_fryipxfrx_start_type (gdc2_fryipxfrx_start)—Offset 60010h" on page 1537	00000000h
60014h	4	"reg_gdc2_oxdim_type (gdc2_oxdim)—Offset 60014h" on page 1538	00000000h
60018h	4	"reg_gdc2_oydim_type (gdc2_oydim)—Offset 60018h" on page 1538	00000000h
6001Ch	4	"reg_gdc2_src_addr_type (gdc2_src_addr)—Offset 6001Ch" on page 1539	00000000h
60020h	4	"reg_gdc2_src_end_type (gdc2_src_end)—Offset 60020h" on page 1539	00000000h
60024h	4	"reg_gdc2_src_wrap_type (gdc2_src_wrap)—Offset 60024h" on page 1540	00000000h
60028h	4	"reg_gdc2_src_stride_type (gdc2_src_stride)—Offset 60028h" on page 1540	00000000h
6002Ch	4	"reg_gdc2_dst_addr_type (gdc2_dst_addr)—Offset 6002Ch" on page 1541	00000000h
60030h	4	"reg_gdc2_dst_stride_type (gdc2_dst_stride)—Offset 60030h" on page 1541	00000000h
60034h	4	"reg_gdc2_dx_type (gdc2_dx)—Offset 60034h" on page 1542	00000000h
60038h	4	"reg_gdc2_dy_type (gdc2_dy)—Offset 60038h" on page 1542	00000000h
6003Ch	4	"reg_gdc2_P0_primX_ixdim_type (gdc2_P0_primX_ixdim)—Offset 6003Ch" on page 1543	00000000h
60040h	4	"reg_gdc2_P0_primY_iydim_type (gdc2_P0_primY_iydim)—Offset 60040h" on page 1543	00000000h
60044h	4	"reg_gdc2_P1_primX_type (gdc2_P1_primX)—Offset 60044h" on page 1544	00000000h
60048h	4	"reg_gdc2_P1_primY_type (gdc2_P1_primY)—Offset 60048h" on page 1544	00000000h
6004Ch	4	"reg_gdc2_P2_primX_type (gdc2_P2_primX)—Offset 6004Ch" on page 1545	00000000h
60050h	4	"reg_gdc2_P2_primY_type (gdc2_P2_primY)—Offset 60050h" on page 1545	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
60054h	4	"reg_gdc2_P3_primX_type (gdc2_P3_primX)—Offset 60054h" on page 1546	00000000h
60058h	4	"reg_gdc2_P3_primY_type (gdc2_P3_primY)—Offset 60058h" on page 1546	00000000h
6005Ch	4	"reg_gdc2_perf_mode_type (gdc2_perf_mode)—Offset 6005Ch" on page 1547	00000000h
60060h	4	"reg_gdc2_interp_type_type (gdc2_interp_type)—Offset 60060h" on page 1548	00000000h
60064h	4	"reg_gdc2_scan_mode_type (gdc2_scan_mode)—Offset 60064h" on page 1548	00000000h
60068h	4	"reg_gdc2_proc_mode_type (gdc2_proc_mode)—Offset 60068h" on page 1549	00000000h
70000h	4	"reg_data_out_sys_c_mmu_MMU_invalidate_cache_type (data_out_sys_c_mmu_MMU_invalidate_cache)—Offset 70000h" on page 1549	00000000h
70004h	4	"reg_data_out_sys_c_mmu_MMU_page_table_base_type (data_out_sys_c_mmu_MMU_page_table_base)—Offset 70004h" on page 1550	00000000h
80100h	4	"reg_inp_sys_csi_receiver_csi1_dev_ready_type (inp_sys_csi_receiver_csi1_dev_ready)—Offset 80100h" on page 1550	00000000h
80104h	4	"reg_inp_sys_csi_receiver_csi1_int_status_type (inp_sys_csi_receiver_csi1_int_status)—Offset 80104h" on page 1551	00000000h
80108h	4	"reg_inp_sys_csi_receiver_csi1_int_enable_type (inp_sys_csi_receiver_csi1_int_enable)—Offset 80108h" on page 1553	00000000h
8010Ch	4	"reg_inp_sys_csi_receiver_csi1_func_prg_type (inp_sys_csi_receiver_csi1_func_prg)—Offset 8010Ch" on page 1554	0007FFFFh
80110h	4	"reg_inp_sys_csi_receiver_csi1_init_cnt_type (inp_sys_csi_receiver_csi1_init_cnt)—Offset 80110h" on page 1555	00000000h
8011Ch	4	"reg_inp_sys_csi_receiver_csi_backend_fs_ls_type (inp_sys_csi_receiver_csi_backend_fs_ls)—Offset 8011Ch" on page 1555	00000002h
80120h	4	"reg_inp_sys_csi_receiver_csi_backend_ls_dvalid_type (inp_sys_csi_receiver_csi_backend_ls_dvalid)—Offset 80120h" on page 1556	00000002h
80124h	4	"reg_inp_sys_csi_receiver_csi_backend_dvalid_le_type (inp_sys_csi_receiver_csi_backend_dvalid_le)—Offset 80124h" on page 1557	00000002h
80128h	4	"reg_inp_sys_csi_receiver_csi_backend_le_fe_type (inp_sys_csi_receiver_csi_backend_le_fe)—Offset 80128h" on page 1557	00000002h
8012Ch	4	"reg_inp_sys_csi_receiver_csi_backend_fe_fs_type (inp_sys_csi_receiver_csi_backend_fe_fs)—Offset 8012Ch" on page 1558	00000002h
80130h	4	"reg_inp_sys_csi_receiver_csi_backend_le_ls_type (inp_sys_csi_receiver_csi_backend_le_ls)—Offset 80130h" on page 1559	00000004h
80134h	4	"reg_inp_sys_csi_receiver_csi_backend_two_pixel_en_type (inp_sys_csi_receiver_csi_backend_two_pixel_en)—Offset 80134h" on page 1559	00000000h
80138h	4	"reg_inp_sys_csi_receiver_csi1_raw16_18_data_id_type (inp_sys_csi_receiver_csi1_raw16_18_data_id)—Offset 80138h" on page 1560	00000000h
8013Ch	4	"reg_inp_sys_csi_receiver_csi1_sync_cnt_type (inp_sys_csi_receiver_csi1_sync_cnt)—Offset 8013Ch" on page 1561	FFFFFFFFh



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
80140h	4	"reg_inp_sys_csi_receiver_csi1_rx_cnt_type (inp_sys_csi_receiver_csi1_rx_cnt)—Offset 80140h" on page 1561	FFFFFFFFh
80144h	4	"reg_inp_sys_csi_receiver_csi_backend_rst_type (inp_sys_csi_receiver_csi_backend_rst)—Offset 80144h" on page 1562	00000000h
80148h	4	"reg_inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc0_type (inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc0)—Offset 80148h" on page 1563	00000000h
8014Ch	4	"reg_inp_sys_csi_receiver_csi_backend_comp_reg1_vc0_type (inp_sys_csi_receiver_csi_backend_comp_reg1_vc0)—Offset 8014Ch" on page 1564	00000000h
80150h	4	"reg_inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc1_type (inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc1)—Offset 80150h" on page 1565	00000000h
80154h	4	"reg_inp_sys_csi_receiver_csi_backend_comp_reg1_vc1_type (inp_sys_csi_receiver_csi_backend_comp_reg1_vc1)—Offset 80154h" on page 1566	00000000h
80158h	4	"reg_inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc2_type (inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc2)—Offset 80158h" on page 1567	00000000h
8015Ch	4	"reg_inp_sys_csi_receiver_csi_backend_comp_reg1_vc2_type (inp_sys_csi_receiver_csi_backend_comp_reg1_vc2)—Offset 8015Ch" on page 1569	00000000h
80160h	4	"reg_inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc3_type (inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc3)—Offset 80160h" on page 1569	00000000h
80164h	4	"reg_inp_sys_csi_receiver_csi_backend_comp_reg1_vc3_type (inp_sys_csi_receiver_csi_backend_comp_reg1_vc3)—Offset 80164h" on page 1571	00000000h
80168h	4	"reg_inp_sys_csi_receiver_csi_backend_raw18_reg_type (inp_sys_csi_receiver_csi_backend_raw18_reg)—Offset 80168h" on page 1572	00000000h
8016Ch	4	"reg_inp_sys_csi_receiver_csi_backend_force_raw8_reg_type (inp_sys_csi_receiver_csi_backend_force_raw8_reg)—Offset 8016Ch" on page 1572	00000000h
80170h	4	"reg_inp_sys_csi_receiver_csi_backend_raw16_reg_type (inp_sys_csi_receiver_csi_backend_raw16_reg)—Offset 80170h" on page 1573	00000000h
80200h	4	"reg_inp_sys_csi_receiver_csi2_dev_ready_type (inp_sys_csi_receiver_csi2_dev_ready)—Offset 80200h" on page 1574	00000000h
80204h	4	"reg_inp_sys_csi_receiver_csi2_int_status_type (inp_sys_csi_receiver_csi2_int_status)—Offset 80204h" on page 1575	00000000h
80208h	4	"reg_inp_sys_csi_receiver_csi2_int_enable_type (inp_sys_csi_receiver_csi2_int_enable)—Offset 80208h" on page 1576	00000000h
8020Ch	4	"reg_inp_sys_csi_receiver_csi2_func_prg_type (inp_sys_csi_receiver_csi2_func_prg)—Offset 8020Ch" on page 1577	0007FFFFh
80210h	4	"reg_inp_sys_csi_receiver_csi2_init_cnt_type (inp_sys_csi_receiver_csi2_init_cnt)—Offset 80210h" on page 1578	00000000h
80238h	4	"reg_inp_sys_csi_receiver_csi2_raw16_18_data_id_type (inp_sys_csi_receiver_csi2_raw16_18_data_id)—Offset 80238h" on page 1579	00000000h
8023Ch	4	"reg_inp_sys_csi_receiver_csi2_sync_cnt_type (inp_sys_csi_receiver_csi2_sync_cnt)—Offset 8023Ch" on page 1579	000000FFh



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
80240h	4	"reg_inp_sys_csi_receiver_csi2_rx_cnt_type (inp_sys_csi_receiver_csi2_rx_cnt)—Offset 80240h" on page 1580	000000FFh
80300h	4	"reg_inp_sys_csi_receiver_csi3_dev_ready_type (inp_sys_csi_receiver_csi3_dev_ready)—Offset 80300h" on page 1581	00000000h
80304h	4	"reg_inp_sys_csi_receiver_csi3_int_status_type (inp_sys_csi_receiver_csi3_int_status)—Offset 80304h" on page 1581	00000000h
80308h	4	"reg_inp_sys_csi_receiver_csi3_int_enable_type (inp_sys_csi_receiver_csi3_int_enable)—Offset 80308h" on page 1583	00000000h
8030Ch	4	"reg_inp_sys_csi_receiver_csi3_func_prg_type (inp_sys_csi_receiver_csi3_func_prg)—Offset 8030Ch" on page 1584	0007FFFFh
80310h	4	"reg_inp_sys_csi_receiver_csi3_init_cnt_type (inp_sys_csi_receiver_csi3_init_cnt)—Offset 80310h" on page 1585	00000000h
80338h	4	"reg_inp_sys_csi_receiver_csi3_raw16_18_data_id_type (inp_sys_csi_receiver_csi3_raw16_18_data_id)—Offset 80338h" on page 1585	00000000h
8033Ch	4	"reg_inp_sys_csi_receiver_csi3_sync_cnt_type (inp_sys_csi_receiver_csi3_sync_cnt)—Offset 8033Ch" on page 1586	0000FFFFh
80340h	4	"reg_inp_sys_csi_receiver_csi3_rx_cnt_type (inp_sys_csi_receiver_csi3_rx_cnt)—Offset 80340h" on page 1587	00000000h
80800h	4	"reg_inp_sys_csi_receiver_csi_be_gen_sh_acc_ovl_type (inp_sys_csi_receiver_csi_be_gen_sh_acc_ovl)—Offset 80800h" on page 1588	00000000h
80804h	4	"reg_inp_sys_csi_receiver_csi_sh_be_srst_type (inp_sys_csi_receiver_csi_sh_be_srst)—Offset 80804h" on page 1588	00000000h
80808h	4	"reg_inp_sys_csi_receiver_csi_sh_be_two_ppc_type (inp_sys_csi_receiver_csi_sh_be_two_ppc)—Offset 80808h" on page 1589	00000000h
8080Ch	4	"reg_inp_sys_csi_receiver_csi_sh_be_comp_reg_vc0_type (inp_sys_csi_receiver_csi_sh_be_comp_reg_vc0)—Offset 8080Ch" on page 1590	00000000h
80810h	4	"reg_inp_sys_csi_receiver_csi_sh_be_comp_reg_vc1_type (inp_sys_csi_receiver_csi_sh_be_comp_reg_vc1)—Offset 80810h" on page 1591	00000000h
80814h	4	"reg_inp_sys_csi_receiver_csi_sh_be_comp_reg_vc2_type (inp_sys_csi_receiver_csi_sh_be_comp_reg_vc2)—Offset 80814h" on page 1592	00000000h
80818h	4	"reg_inp_sys_csi_receiver_csi_sh_be_comp_reg_vc3_type (inp_sys_csi_receiver_csi_sh_be_comp_reg_vc3)—Offset 80818h" on page 1594	00000000h
8081Ch	4	"reg_inp_sys_csi_receiver_csi_sh_be_sel_be_type (inp_sys_csi_receiver_csi_sh_be_sel_be)—Offset 8081Ch" on page 1595	00000000h
80820h	4	"reg_inp_sys_csi_receiver_csi_sh_be_raw16_reg_type (inp_sys_csi_receiver_csi_sh_be_raw16_reg)—Offset 80820h" on page 1595	00000000h
80824h	4	"reg_inp_sys_csi_receiver_csi_sh_be_raw18_reg_type (inp_sys_csi_receiver_csi_sh_be_raw18_reg)—Offset 80824h" on page 1596	00000000h
80828h	4	"reg_inp_sys_csi_receiver_csi_sh_be_force_raw8_reg_type (inp_sys_csi_receiver_csi_sh_be_force_raw8_reg)—Offset 80828h" on page 1597	00000000h
8082Ch	4	"reg_inp_sys_csi_receiver_csi_sh_be_irq_stat_reg_type (inp_sys_csi_receiver_csi_sh_be_irq_stat_reg)—Offset 8082Ch" on page 1598	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
80830h	4	"reg_inp_sys_csi_receiver_csi_sh_be_irq_stat_clear_reg_type (inp_sys_csi_receiver_csi_sh_be_irq_stat_clear_reg)—Offset 80830h" on page 1598	00000000h
80834h	4	"reg_inp_sys_csi_receiver_csi_sh_be_custom_enable_reg_type (inp_sys_csi_receiver_csi_sh_be_custom_enable_reg)—Offset 80834h" on page 1599	00000000h
81000h	4	"reg_inp_sys_capt_unit_a_reg_CaptStartMode_type (inp_sys_capt_unit_a_reg_CaptStartMode)—Offset 81000h" on page 1600	00000000h
81004h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Start_Addr_type (inp_sys_capt_unit_a_reg_Capt_Start_Addr)—Offset 81004h" on page 1601	00000000h
81008h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Mem_Region_Size_type (inp_sys_capt_unit_a_reg_Capt_Mem_Region_Size)—Offset 81008h" on page 1601	00000080h
8100Ch	4	"reg_inp_sys_capt_unit_a_reg_Capt_Num_Mem_Regions_type (inp_sys_capt_unit_a_reg_Capt_Num_Mem_Regions)—Offset 8100Ch" on page 1602	00000003h
81010h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Init_type (inp_sys_capt_unit_a_reg_Capt_Init)—Offset 81010h" on page 1603	00000000h
81014h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Start_Addr_type (inp_sys_capt_unit_a_reg_Capt_Start_Addr)—Offset 81014h" on page 1601	00000000h
81018h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Stop_type (inp_sys_capt_unit_a_reg_Capt_Stop)—Offset 81018h" on page 1604	00000000h
8101Ch	4	"reg_inp_sys_capt_unit_a_reg_Capt_Packet_Length_type (inp_sys_capt_unit_a_reg_Capt_Packet_Length)—Offset 8101Ch" on page 1605	00000000h
81020h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Received_Length_type (inp_sys_capt_unit_a_reg_Capt_Received_Length)—Offset 81020h" on page 1605	00000000h
81024h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Received_Short_Packets_type (inp_sys_capt_unit_a_reg_Capt_Received_Short_Packets)—Offset 81024h" on page 1606	00000000h
81028h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Received_Long_Packets_type (inp_sys_capt_unit_a_reg_Capt_Received_Long_Packets)—Offset 81028h" on page 1606	00000000h
8102Ch	4	"reg_inp_sys_capt_unit_a_reg_Capt_Last_Command_type (inp_sys_capt_unit_a_reg_Capt_Last_Command)—Offset 8102Ch" on page 1607	0000000Fh
81030h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Next_Command_type (inp_sys_capt_unit_a_reg_Capt_Next_Command)—Offset 81030h" on page 1608	0000000Fh
81034h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Last_Acknowledge_type (inp_sys_capt_unit_a_reg_Capt_Last_Acknowledge)—Offset 81034h" on page 1608	0000000Fh
81038h	4	"reg_inp_sys_capt_unit_a_reg_Capt_Next_Acknowledge_type (inp_sys_capt_unit_a_reg_Capt_Next_Acknowledge)—Offset 81038h" on page 1609	0000000Fh
8103Ch	4	"reg_inp_sys_capt_unit_a_reg_Capt_FSM_State_Info_type (inp_sys_capt_unit_a_reg_Capt_FSM_State_Info)—Offset 8103Ch" on page 1609	00000000h
82000h	4	"reg_inp_sys_capt_unit_b_reg_CaptStartMode_type (inp_sys_capt_unit_b_reg_CaptStartMode)—Offset 82000h" on page 1610	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
82004h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Start_Addr_type (inp_sys_capt_unit_b_reg_Capt_Start_Addr)—Offset 82004h" on page 1611	00000000h
82008h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Mem_Region_Size_type (inp_sys_capt_unit_b_reg_Capt_Mem_Region_Size)—Offset 82008h" on page 1612	00000080h
8200Ch	4	"reg_inp_sys_capt_unit_b_reg_Capt_Num_Mem_Regions_type (inp_sys_capt_unit_b_reg_Capt_Num_Mem_Regions)—Offset 8200Ch" on page 1612	00000003h
82010h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Init_type (inp_sys_capt_unit_b_reg_Capt_Init)—Offset 82010h" on page 1613	00000000h
82014h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Start_Addr_type (inp_sys_capt_unit_b_reg_Capt_Start_Addr)—Offset 82004h" on page 1611	00000000h
82018h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Stop_type (inp_sys_capt_unit_b_reg_Capt_Stop)—Offset 82018h" on page 1614	00000000h
8201Ch	4	"reg_inp_sys_capt_unit_b_reg_Capt_Packet_Length_type (inp_sys_capt_unit_b_reg_Capt_Packet_Length)—Offset 8201Ch" on page 1615	00000000h
82020h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Received_Length_type (inp_sys_capt_unit_b_reg_Capt_Received_Length)—Offset 82020h" on page 1615	00000000h
82024h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Received_Short_Packets_type (inp_sys_capt_unit_b_reg_Capt_Received_Short_Packets)—Offset 82024h" on page 1616	00000000h
82028h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Received_Long_Packets_type (inp_sys_capt_unit_b_reg_Capt_Received_Long_Packets)—Offset 82028h" on page 1617	00000000h
8202Ch	4	"reg_inp_sys_capt_unit_b_reg_Capt_Last_Command_type (inp_sys_capt_unit_b_reg_Capt_Last_Command)—Offset 8202Ch" on page 1617	0000000Fh
82030h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Next_Command_type (inp_sys_capt_unit_b_reg_Capt_Next_Command)—Offset 82030h" on page 1618	0000000Fh
82034h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Last_Acknowledge_type (inp_sys_capt_unit_b_reg_Capt_Last_Acknowledge)—Offset 82034h" on page 1618	0000000Fh
82038h	4	"reg_inp_sys_capt_unit_b_reg_Capt_Next_Acknowledge_type (inp_sys_capt_unit_b_reg_Capt_Next_Acknowledge)—Offset 82038h" on page 1619	0000000Fh
8203Ch	4	"reg_inp_sys_capt_unit_b_reg_Capt_FSM_State_Info_type (inp_sys_capt_unit_b_reg_Capt_FSM_State_Info)—Offset 8203Ch" on page 1620	00000000h
83000h	4	"reg_inp_sys_capt_unit_c_reg_CaptStartMode_type (inp_sys_capt_unit_c_reg_CaptStartMode)—Offset 83000h" on page 1621	00000000h
83004h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Start_Addr_type (inp_sys_capt_unit_c_reg_Capt_Start_Addr)—Offset 83004h" on page 1621	00000000h
83008h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Mem_Region_Size_type (inp_sys_capt_unit_c_reg_Capt_Mem_Region_Size)—Offset 83008h" on page 1622	00000080h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
8300Ch	4	"reg_inp_sys_capt_unit_c_reg_Capt_Num_Mem_Regions_type (inp_sys_capt_unit_c_reg_Capt_Num_Mem_Regions)—Offset 8300Ch" on page 1623	00000003h
83010h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Init_type (inp_sys_capt_unit_c_reg_Capt_Init)—Offset 83010h" on page 1623	00000000h
83014h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Start_Addr_type (inp_sys_capt_unit_c_reg_Capt_Start_Addr)—Offset 83004h" on page 1621	00000000h
83018h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Stop_type (inp_sys_capt_unit_c_reg_Capt_Stop)—Offset 83018h" on page 1625	00000000h
8301Ch	4	"reg_inp_sys_capt_unit_c_reg_Capt_Packet_Length_type (inp_sys_capt_unit_c_reg_Capt_Packet_Length)—Offset 8301Ch" on page 1625	00000000h
83020h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Received_Length_type (inp_sys_capt_unit_c_reg_Capt_Received_Length)—Offset 83020h" on page 1626	00000000h
83024h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Received_Short_Packets_type (inp_sys_capt_unit_c_reg_Capt_Received_Short_Packets)—Offset 83024h" on page 1626	00000000h
83028h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Received_Long_Packets_type (inp_sys_capt_unit_c_reg_Capt_Received_Long_Packets)—Offset 83028h" on page 1627	00000000h
8302Ch	4	"reg_inp_sys_capt_unit_c_reg_Capt_Last_Command_type (inp_sys_capt_unit_c_reg_Capt_Last_Command)—Offset 8302Ch" on page 1628	0000000Fh
83030h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Next_Command_type (inp_sys_capt_unit_c_reg_Capt_Next_Command)—Offset 83030h" on page 1628	0000000Fh
83034h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Last_Acknowledge_type (inp_sys_capt_unit_c_reg_Capt_Last_Acknowledge)—Offset 83034h" on page 1629	0000000Fh
83038h	4	"reg_inp_sys_capt_unit_c_reg_Capt_Next_Acknowledge_type (inp_sys_capt_unit_c_reg_Capt_Next_Acknowledge)—Offset 83038h" on page 1629	0000000Fh
8303Ch	4	"reg_inp_sys_capt_unit_c_reg_Capt_FSM_State_Info_type (inp_sys_capt_unit_c_reg_Capt_FSM_State_Info)—Offset 8303Ch" on page 1630	00000000h
84000h	4	"reg_inp_sys_acq_unit_reg_Acq_Start_Addr_type (inp_sys_acq_unit_reg_Acq_Start_Addr)—Offset 84000h" on page 1631	00000000h
84004h	4	"reg_inp_sys_acq_unit_reg_Acq_Mem_Region_Size_type (inp_sys_acq_unit_reg_Acq_Mem_Region_Size)—Offset 84004h" on page 1632	00000080h
84008h	4	"reg_inp_sys_acq_unit_reg_Acq_Num_Mem_Regions_type (inp_sys_acq_unit_reg_Acq_Num_Mem_Regions)—Offset 84008h" on page 1632	00000003h
8400Ch	4	"reg_inp_sys_acq_unit_reg_Acq_Init_type (inp_sys_acq_unit_reg_Acq_Init)—Offset 8400Ch" on page 1633	00000000h
84010h	4	"reg_inp_sys_acq_unit_reg_Acq_Received_Short_Packets_type (inp_sys_acq_unit_reg_Acq_Received_Short_Packets)—Offset 84010h" on page 1634	00000000h
84014h	4	"reg_inp_sys_acq_unit_reg_Acq_Received_Long_Packets_type (inp_sys_acq_unit_reg_Acq_Received_Long_Packets)—Offset 84014h" on page 1634	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
84018h	4	"reg_inp_sys_acq_unit_reg_Acq_Last_Command_type (inp_sys_acq_unit_reg_Acq_Last_Command)—Offset 84018h" on page 1635	0000000Fh
8401Ch	4	"reg_inp_sys_acq_unit_reg_Acq_Next_Command_type (inp_sys_acq_unit_reg_Acq_Next_Command)—Offset 8401Ch" on page 1635	0000000Fh
84020h	4	"reg_inp_sys_acq_unit_reg_Acq_Last_Acknowledge_type (inp_sys_acq_unit_reg_Acq_Last_Acknowledge)—Offset 84020h" on page 1636	0000000Fh
84024h	4	"reg_inp_sys_acq_unit_reg_Acq_Next_Acknowledge_type (inp_sys_acq_unit_reg_Acq_Next_Acknowledge)—Offset 84024h" on page 1637	0000000Fh
84028h	4	"reg_inp_sys_acq_unit_reg_Acq_FSM_State_Info_type (inp_sys_acq_unit_reg_Acq_FSM_State_Info)—Offset 84028h" on page 1637	00000000h
8402Ch	4	"reg_inp_sys_acq_unit_reg_Acq_Int_Cntr_Info_type (inp_sys_acq_unit_reg_Acq_Int_Cntr_Info)—Offset 8402Ch" on page 1638	00000000h
85000h	4	"reg_inp_sys_dma_DMA_FSM_Command_type (inp_sys_dma_DMA_FSM_Command)—Offset 85000h" on page 1639	00000000h
86000h	4	"reg_inp_sys_dma_DMA_CH0_Packing_setup_type (inp_sys_dma_DMA_CH0_Packing_setup)—Offset 86000h" on page 1640	00000000h
86100h	4	"reg_inp_sys_dma_DMA_CH0_dev_stride_A_type (inp_sys_dma_DMA_CH0_dev_stride_A)—Offset 86100h" on page 1641	00000000h
86200h	4	"reg_inp_sys_dma_DMA_CH0_dev_Pack_left_crop_and_elem_A_type (inp_sys_dma_DMA_CH0_dev_Pack_left_crop_and_elem_A)—Offset 86200h" on page 1641	00000000h
86300h	4	"reg_inp_sys_dma_DMA_CH0_Device_Xb_A_type (inp_sys_dma_DMA_CH0_Device_Xb_A)—Offset 86300h" on page 1642	00000000h
86400h	4	"reg_inp_sys_dma_DMA_CH0_dev_stride_B_type (inp_sys_dma_DMA_CH0_dev_stride_B)—Offset 86400h" on page 1643	00000000h
86500h	4	"reg_inp_sys_dma_DMA_CH0_dev_Pack_left_crop_and_elem_B_type (inp_sys_dma_DMA_CH0_dev_Pack_left_crop_and_elem_B)—Offset 86500h" on page 1643	00000000h
86600h	4	"reg_inp_sys_dma_DMA_CH0_Device_Xb_B_type (inp_sys_dma_DMA_CH0_Device_Xb_B)—Offset 86600h" on page 1644	00000000h
86700h	4	"reg_inp_sys_dma_DMA_CH0_Yb_type (inp_sys_dma_DMA_CH0_Yb)—Offset 86700h" on page 1645	00000000h
86800h	4	"reg_inp_sys_dma_DMA_CH0_pending_command_type (inp_sys_dma_DMA_CH0_pending_command)—Offset 86800h" on page 1646	00000000h
87000h	4	"reg_inp_sys_dma_DMA_command_token_type (inp_sys_dma_DMA_command_token)—Offset 87000h" on page 1646	00000000h
87004h	4	"reg_inp_sys_dma_DMA_command_src_addr_type (inp_sys_dma_DMA_command_src_addr)—Offset 87004h" on page 1647	00000000h
87008h	4	"reg_inp_sys_dma_DMA_command_dst_addr_type (inp_sys_dma_DMA_command_dst_addr)—Offset 87008h" on page 1647	00000000h
8700Ch	4	"reg_inp_sys_dma_DMA_command_ctrl_id_type (inp_sys_dma_DMA_command_ctrl_id)—Offset 8700Ch" on page 1648	00000000h
87010h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_status_type (inp_sys_dma_DMA_FSM_Ctrl_status)—Offset 87010h" on page 1649	00000001h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
87014h	4	"reg_inp_sys_dma_DMA_FSM_Pack_status_type (inp_sys_dma_DMA_FSM_Pack_status)—Offset 87014h" on page 1649	00000000h
87018h	4	"reg_inp_sys_dma_DMA_FSM_request_status_type (inp_sys_dma_DMA_FSM_request_status)—Offset 87018h" on page 1650	00000000h
8701Ch	4	"reg_inp_sys_dma_DMA_FSM_write_status_type (inp_sys_dma_DMA_FSM_write_status)—Offset 8701Ch" on page 1651	00000000h
87110h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_dev_idx_type (inp_sys_dma_DMA_FSM_Ctrl_dev_idx)—Offset 87110h" on page 1652	00000000h
87114h	4	"reg_inp_sys_dma_DMA_FSM_Pack_cnt_Yb_type (inp_sys_dma_DMA_FSM_Pack_cnt_Yb)—Offset 87114h" on page 1652	00000000h
87118h	4	"reg_inp_sys_dma_DMA_FSM_Request_cnt_Yb_type (inp_sys_dma_DMA_FSM_Request_cnt_Yb)—Offset 87118h" on page 1653	00000000h
8711Ch	4	"reg_inp_sys_dma_DMA_FSM_Write_cnt_Y_type (inp_sys_dma_DMA_FSM_Write_cnt_Y)—Offset 8711Ch" on page 1654	00000000h
87210h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_req_addr_type (inp_sys_dma_DMA_FSM_Ctrl_req_addr)—Offset 87210h" on page 1654	00000000h
87214h	4	"reg_inp_sys_dma_DMA_FSM_Pack_req_cnt_Xb_type (inp_sys_dma_DMA_FSM_Pack_req_cnt_Xb)—Offset 87214h" on page 1655	00000000h
87218h	4	"reg_inp_sys_dma_DMA_FSM_Request_cnt_Xb_type (inp_sys_dma_DMA_FSM_Request_cnt_Xb)—Offset 87218h" on page 1656	00000000h
8721Ch	4	"reg_inp_sys_dma_DMA_FSM_Write_cnt_Xb_type (inp_sys_dma_DMA_FSM_Write_cnt_Xb)—Offset 8721Ch" on page 1656	00000000h
87310h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_req_stride_type (inp_sys_dma_DMA_FSM_Ctrl_req_stride)—Offset 87310h" on page 1657	00000000h
87314h	4	"reg_inp_sys_dma_DMA_FSM_Pack_wr_cnt_Xb_type (inp_sys_dma_DMA_FSM_Pack_wr_cnt_Xb)—Offset 87314h" on page 1658	00000000h
87318h	4	"reg_inp_sys_dma_DMA_FSM_Req_remining_Xb_type (inp_sys_dma_DMA_FSM_Req_remining_Xb)—Offset 87318h" on page 1658	00000000h
8731Ch	4	"reg_inp_sys_dma_DMA_FSM_Wr_remining_Xb_type (inp_sys_dma_DMA_FSM_Wr_remining_Xb)—Offset 8731Ch" on page 1659	00000000h
87410h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_req_Xb_type (inp_sys_dma_DMA_FSM_Ctrl_req_Xb)—Offset 87410h" on page 1660	00000000h
87418h	4	"reg_inp_sys_dma_DMA_FSM_Req_burst_cnt_type (inp_sys_dma_DMA_FSM_Req_burst_cnt)—Offset 87418h" on page 1660	0000FFFFh
8741Ch	4	"reg_inp_sys_dma_DMA_FSM_Wr_burst_cnt_type (inp_sys_dma_DMA_FSM_Wr_burst_cnt)—Offset 8741Ch" on page 1661	0000FFFFh
87510h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_req_Yb_type (inp_sys_dma_DMA_FSM_Ctrl_req_Yb)—Offset 87510h" on page 1662	00000000h
87610h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_Pack_req_dev_idx_type (inp_sys_dma_DMA_FSM_Ctrl_Pack_req_dev_idx)—Offset 87610h" on page 1662	00000000h
87710h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_Pack_wr_dev_idx_type (inp_sys_dma_DMA_FSM_Ctrl_Pack_wr_dev_idx)—Offset 87710h" on page 1663	00000000h




Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMADR (Continued)

Offset	Size	Register ID—Description	Default Value
87810h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_Wr_addr_type (inp_sys_dma_DMA_FSM_Ctrl_Wr_addr)—Offset 87810h" on page 1664	00000000h
87910h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_Wr_stride_type (inp_sys_dma_DMA_FSM_Ctrl_Wr_stride)—Offset 87910h" on page 1664	00000000h
87A10h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_pack_req_Xb_type (inp_sys_dma_DMA_FSM_Ctrl_pack_req_Xb)—Offset 87A10h" on page 1665	00000000h
87B10h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_pack_Yb_type (inp_sys_dma_DMA_FSM_Ctrl_pack_Yb)—Offset 87B10h" on page 1666	00000000h
87C10h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_pack_wr_Xb_type (inp_sys_dma_DMA_FSM_Ctrl_pack_wr_Xb)—Offset 87C10h" on page 1666	00000000h
87D10h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_pack_req_elem_type (inp_sys_dma_DMA_FSM_Ctrl_pack_req_elem)—Offset 87D10h" on page 1667	00000000h
87E10h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_pack_wr_elem_type (inp_sys_dma_DMA_FSM_Ctrl_pack_wr_elem)—Offset 87E10h" on page 1668	00000000h
87F10h	4	"reg_inp_sys_dma_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id_type (inp_sys_dma_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id)—Offset 87F10h" on page 1668	00000000h
88000h	4	"reg_inp_sys_dma_Dev_Interf_0_req_side_type (inp_sys_dma_Dev_Interf_0_req_side)—Offset 88000h" on page 1669	00000000h
88004h	4	"reg_inp_sys_dma_Dev_Interf_1_req_side_type (inp_sys_dma_Dev_Interf_1_req_side)—Offset 88004h" on page 1670	00000006h
88100h	4	"reg_inp_sys_dma_Dev_Interf_0_snd_side_type (inp_sys_dma_Dev_Interf_0_snd_side)—Offset 88100h" on page 1671	00000004h
88104h	4	"reg_inp_sys_dma_Dev_Interf_1_snd_side_type (inp_sys_dma_Dev_Interf_1_snd_side)—Offset 88104h" on page 1672	00000006h
88200h	4	"reg_inp_sys_dma_Dev_Interf_0_Fifo_status_type (inp_sys_dma_Dev_Interf_0_Fifo_status)—Offset 88200h" on page 1673	00000004h
88204h	4	"reg_inp_sys_dma_Dev_Interf_1_Fifo_status_type (inp_sys_dma_Dev_Interf_1_Fifo_status)—Offset 88204h" on page 1674	00000004h
88300h	4	"reg_inp_sys_dma_Dev_Interf_0_Req_complete_bust_type (inp_sys_dma_Dev_Interf_0_Req_complete_bust)—Offset 88300h" on page 1675	00000000h
88304h	4	"reg_inp_sys_dma_Dev_Interf_1_Req_complete_bust_type (inp_sys_dma_Dev_Interf_1_Req_complete_bust)—Offset 88304h" on page 1676	00000000h
88400h	4	"reg_inp_sys_dma_Dev_Interf_1_Max_burst_Size_type (inp_sys_dma_Dev_Interf_1_Max_burst_Size)—Offset 88400h" on page 1677	0000007Fh
89000h	4	"reg_inp_sys_inp_ctrl_inpsys_captA_start_addr_type (inp_sys_inp_ctrl_inpsys_captA_start_addr)—Offset 89000h" on page 1677	00000000h
89004h	4	"reg_inp_sys_inp_ctrl_inpsys_captB_start_addr_type (inp_sys_inp_ctrl_inpsys_captB_start_addr)—Offset 89004h" on page 1678	00000000h
89008h	4	"reg_inp_sys_inp_ctrl_inpsys_captC_start_addr_type (inp_sys_inp_ctrl_inpsys_captC_start_addr)—Offset 89008h" on page 1679	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
8900Ch	4	"reg_inpsys_inpsys_ctrl_inpsys_captA_mem_region_size_type (inp_sys_inpsys_ctrl_inpsys_captA_mem_region_size)—Offset 8900Ch" on page 1679	00000080h
89010h	4	"reg_inpsys_inpsys_ctrl_inpsys_captB_mem_region_size_type (inp_sys_inpsys_ctrl_inpsys_captB_mem_region_size)—Offset 89010h" on page 1680	00000080h
89014h	4	"reg_inpsys_inpsys_ctrl_inpsys_captC_mem_region_size_type (inp_sys_inpsys_ctrl_inpsys_captC_mem_region_size)—Offset 89014h" on page 1681	00000080h
89018h	4	"reg_inpsys_inpsys_ctrl_inpsys_captA_num_mem_regions_type (inp_sys_inpsys_ctrl_inpsys_captA_num_mem_regions)—Offset 89018h" on page 1681	00000003h
8901Ch	4	"reg_inpsys_inpsys_ctrl_inpsys_captB_num_mem_regions_type (inp_sys_inpsys_ctrl_inpsys_captB_num_mem_regions)—Offset 8901Ch" on page 1682	00000003h
89020h	4	"reg_inpsys_inpsys_ctrl_inpsys_captC_num_mem_regions_type (inp_sys_inpsys_ctrl_inpsys_captC_num_mem_regions)—Offset 89020h" on page 1683	00000003h
89024h	4	"reg_inpsys_inpsys_ctrl_inpsys_acq_start_addr_type (inp_sys_inpsys_ctrl_inpsys_acq_start_addr)—Offset 89024h" on page 1684	00000000h
89028h	4	"reg_inpsys_inpsys_ctrl_inpsys_acq_mem_region_size_type (inp_sys_inpsys_ctrl_inpsys_acq_mem_region_size)—Offset 89028h" on page 1684	00000080h
8902Ch	4	"reg_inpsys_inpsys_ctrl_inpsys_acq_num_mem_regions_type (inp_sys_inpsys_ctrl_inpsys_acq_num_mem_regions)—Offset 8902Ch" on page 1685	00000003h
89030h	4	"reg_inpsys_inpsys_ctrl_inpsys_ctrl_init_type (inp_sys_inpsys_ctrl_inpsys_ctrl_init)—Offset 89030h" on page 1686	00000000h
89034h	4	"reg_inpsys_inpsys_ctrl_inpsys_last_cmd_type (inp_sys_inpsys_ctrl_inpsys_last_cmd)—Offset 89034h" on page 1686	0000000Fh
89038h	4	"reg_inpsys_inpsys_ctrl_inpsys_next_cmd_type (inp_sys_inpsys_ctrl_inpsys_next_cmd)—Offset 89038h" on page 1687	0000000Fh
8903Ch	4	"reg_inpsys_inpsys_ctrl_inpsys_last_ack_type (inp_sys_inpsys_ctrl_inpsys_last_ack)—Offset 8903Ch" on page 1687	0000000Fh
89040h	4	"reg_inpsys_inpsys_ctrl_inpsys_next_ack_type (inp_sys_inpsys_ctrl_inpsys_next_ack)—Offset 89040h" on page 1688	0000000Fh
89044h	4	"reg_inpsys_inpsys_ctrl_inpsys_top_fsm_state_type (inp_sys_inpsys_ctrl_inpsys_top_fsm_state)—Offset 89044h" on page 1688	00000000h
89048h	4	"reg_inpsys_inpsys_ctrl_inpsys_captA_fsm_state_type (inp_sys_inpsys_ctrl_inpsys_captA_fsm_state)—Offset 89048h" on page 1689	00000000h
8904Ch	4	"reg_inpsys_inpsys_ctrl_inpsys_captB_fsm_state_type (inp_sys_inpsys_ctrl_inpsys_captB_fsm_state)—Offset 8904Ch" on page 1690	00000000h
89050h	4	"reg_inpsys_inpsys_ctrl_inpsys_captC_fsm_state_type (inp_sys_inpsys_ctrl_inpsys_captC_fsm_state)—Offset 89050h" on page 1690	00000000h
89054h	4	"reg_inpsys_inpsys_ctrl_inpsys_acq_fsm_state_type (inp_sys_inpsys_ctrl_inpsys_acq_fsm_state)—Offset 89054h" on page 1691	00000000h
89058h	4	"reg_inpsys_inpsys_ctrl_inpsys_capt_reserve_one_mem_region_type (inp_sys_inpsys_ctrl_inpsys_capt_reserve_one_mem_region)—Offset 89058h" on page 1692	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
8A000h	4	"reg_inp_sys_gpreg_str_multicastA_sel_type (inp_sys_gpreg_str_multicastA_sel)—Offset 8A000h" on page 1693	00000000h
8A004h	4	"reg_inp_sys_gpreg_str_multicastB_sel_type (inp_sys_gpreg_str_multicastB_sel)—Offset 8A004h" on page 1694	00000000h
8A008h	4	"reg_inp_sys_gpreg_str_multicastC_sel_type (inp_sys_gpreg_str_multicastC_sel)—Offset 8A008h" on page 1694	00000000h
8A00Ch	4	"reg_inp_sys_gpreg_str_mux_sel_type (inp_sys_gpreg_str_mux_sel)—Offset 8A00Ch" on page 1695	00000000h
8A010h	4	"reg_inp_sys_gpreg_str_mon_status_type (inp_sys_gpreg_str_mon_status)—Offset 8A010h" on page 1695	00000000h
8A014h	4	"reg_inp_sys_gpreg_str_mon_irq_cond_type (inp_sys_gpreg_str_mon_irq_cond)—Offset 8A014h" on page 1697	00000000h
8A018h	4	"reg_inp_sys_gpreg_str_mon_irq_en_type (inp_sys_gpreg_str_mon_irq_en)—Offset 8A018h" on page 1698	00000000h
8A01Ch	4	"reg_inp_sys_gpreg_isys_srst_type (inp_sys_gpreg_isys_srst)—Offset 8A01Ch" on page 1699	00000000h
8A020h	4	"reg_inp_sys_gpreg_isys_slv_reg_srst_type (inp_sys_gpreg_isys_slv_reg_srst)—Offset 8A020h" on page 1700	00000000h
8A024h	4	"reg_inp_sys_gpreg_str_deint_portA_cnt_type (inp_sys_gpreg_str_deint_portA_cnt)—Offset 8A024h" on page 1701	00000000h
8A028h	4	"reg_inp_sys_gpreg_str_deint_portB_cnt_type (inp_sys_gpreg_str_deint_portB_cnt)—Offset 8A028h" on page 1702	00000000h
8B008h	4	"reg_inp_sys_fifo_adapter_CSI_generic_short_packet_available_type (inp_sys_fifo_adapter_CSI_generic_short_packet_available)—Offset 8B008h" on page 1702	00000001h
8C000h	4	"reg_inp_sys_irq_ctrl_irq_edge_type (inp_sys_irq_ctrl_irq_edge)—Offset 8C000h" on page 1703	00000000h
8C004h	4	"reg_inp_sys_irq_ctrl_irq_mask_type (inp_sys_irq_ctrl_irq_mask)—Offset 8C004h" on page 1704	00000000h
8C008h	4	"reg_inp_sys_irq_ctrl_irq_status_type (inp_sys_irq_ctrl_irq_status)—Offset 8C008h" on page 1705	00000000h
8C00Ch	4	"reg_inp_sys_irq_ctrl_irq_clear_type (inp_sys_irq_ctrl_irq_clear)—Offset 8C00Ch" on page 1706	00000000h
8C010h	4	"reg_inp_sys_irq_ctrl_irq_en_type (inp_sys_irq_ctrl_irq_en)—Offset 8C010h" on page 1708	00000000h
8C014h	4	"reg_inp_sys_irq_ctrl_irq_level_not_pulse_type (inp_sys_irq_ctrl_irq_level_not_pulse)—Offset 8C014h" on page 1709	00000000h
90000h	4	"reg_isel_gpr_reg_gp_syncgen_enable_type (isel_gpr_reg_gp_syncgen_enable)—Offset 90000h" on page 1710	00000000h
90004h	4	"reg_isel_gpr_reg_gp_syncgen_free_running_type (isel_gpr_reg_gp_syncgen_free_running)—Offset 90004h" on page 1710	00000000h
90008h	4	"reg_isel_gpr_reg_gp_syncgen_pause_type (isel_gpr_reg_gp_syncgen_pause)—Offset 90008h" on page 1711	00000000h
9000Ch	4	"reg_isel_gpr_reg_gp_nr_frames_type (isel_gpr_reg_gp_nr_frames)—Offset 9000Ch" on page 1712	00000000h
90010h	4	"reg_isel_gpr_reg_gp_syngen_nr_pix_type (isel_gpr_reg_gp_syngen_nr_pix)—Offset 90010h" on page 1712	00000000h
90014h	4	"reg_isel_gpr_reg_gp_syngen_nr_lines_type (isel_gpr_reg_gp_syngen_nr_lines)—Offset 90014h" on page 1713	00000000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
90018h	4	"reg_isel_gpr_reg_gp_syngen_hblank_cycles_type (isel_gpr_reg_gp_syngen_hblank_cycles)—Offset 90018h" on page 1714	00000000h
9001Ch	4	"reg_isel_gpr_reg_gp_syngen_vblank_cycles_type (isel_gpr_reg_gp_syngen_vblank_cycles)—Offset 9001Ch" on page 1714	00000000h
90020h	4	"reg_isel_gpr_reg_gp_isel_sof_type (isel_gpr_reg_gp_isel_sof)—Offset 90020h" on page 1715	00000000h
90024h	4	"reg_isel_gpr_reg_gp_isel_eof_type (isel_gpr_reg_gp_isel_eof)—Offset 90024h" on page 1716	00000000h
90028h	4	"reg_isel_gpr_reg_gp_isel_sol_type (isel_gpr_reg_gp_isel_sol)—Offset 90028h" on page 1716	00000000h
9002Ch	4	"reg_isel_gpr_reg_gp_isel_eol_type (isel_gpr_reg_gp_isel_eol)—Offset 9002Ch" on page 1717	00000000h
90030h	4	"reg_isel_gpr_reg_gp_isel_lfsr_enable_type (isel_gpr_reg_gp_isel_lfsr_enable)—Offset 90030h" on page 1717	00000000h
90034h	4	"reg_isel_gpr_reg_gp_isel_lfsr_enable_b_type (isel_gpr_reg_gp_isel_lfsr_enable_b)—Offset 90034h" on page 1718	00000000h
90038h	4	"reg_isel_gpr_reg_gp_isel_lfsr_reset_value_type (isel_gpr_reg_gp_isel_lfsr_reset_value)—Offset 90038h" on page 1719	00000000h
9003Ch	4	"reg_isel_gpr_reg_gp_isel_tpg_enable_type (isel_gpr_reg_gp_isel_tpg_enable)—Offset 9003Ch" on page 1719	00000000h
90040h	4	"reg_isel_gpr_reg_gp_isel_tpg_enable_b_type (isel_gpr_reg_gp_isel_tpg_enable_b)—Offset 90040h" on page 1720	00000000h
90044h	4	"reg_isel_gpr_reg_gp_isel_hor_cnt_mask_type (isel_gpr_reg_gp_isel_hor_cnt_mask)—Offset 90044h" on page 1721	00000000h
90048h	4	"reg_isel_gpr_reg_gp_isel_ver_cnt_mask_type (isel_gpr_reg_gp_isel_ver_cnt_mask)—Offset 90048h" on page 1721	00000000h
9004Ch	4	"reg_isel_gpr_reg_gp_isel_xy_cnt_mask_type (isel_gpr_reg_gp_isel_xy_cnt_mask)—Offset 9004Ch" on page 1722	00000000h
90050h	4	"reg_isel_gpr_reg_gp_isel_hor_cnt_delta_type (isel_gpr_reg_gp_isel_hor_cnt_delta)—Offset 90050h" on page 1723	00000000h
90054h	4	"reg_isel_gpr_reg_gp_isel_ver_cnt_delta_type (isel_gpr_reg_gp_isel_ver_cnt_delta)—Offset 90054h" on page 1723	00000000h
90058h	4	"reg_isel_gpr_reg_gp_isel_tpg_mode_type (isel_gpr_reg_gp_isel_tpg_mode)—Offset 90058h" on page 1724	00000000h
9005Ch	4	"reg_isel_gpr_reg_gp_isel_tpg_red1_type (isel_gpr_reg_gp_isel_tpg_red1)—Offset 9005Ch" on page 1725	00000000h
90060h	4	"reg_isel_gpr_reg_gp_isel_tpg_green1_type (isel_gpr_reg_gp_isel_tpg_green1)—Offset 90060h" on page 1725	00000000h
90064h	4	"reg_isel_gpr_reg_gp_isel_tpg_blue1_type (isel_gpr_reg_gp_isel_tpg_blue1)—Offset 90064h" on page 1726	00000000h
90068h	4	"reg_isel_gpr_reg_gp_isel_tpg_red2_type (isel_gpr_reg_gp_isel_tpg_red2)—Offset 90068h" on page 1727	00000000h
9006Ch	4	"reg_isel_gpr_reg_gp_isel_tpg_green2_type (isel_gpr_reg_gp_isel_tpg_green2)—Offset 9006Ch" on page 1727	00000000h
90070h	4	"reg_isel_gpr_reg_gp_isel_tpg_blue2_type (isel_gpr_reg_gp_isel_tpg_blue2)—Offset 90070h" on page 1728	00000000h
90074h	4	"reg_isel_gpr_reg_gp_isel_ch_id_type (isel_gpr_reg_gp_isel_ch_id)—Offset 90074h" on page 1729	00000000h




Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
90078h	4	"reg_isel_gpr_reg_gp_isel_fmt_type_type (isel_gpr_reg_gp_isel_fmt_type)—Offset 90078h" on page 1729	00000000h
9007Ch	4	"reg_isel_gpr_reg_gp_isel_data_sel_type (isel_gpr_reg_gp_isel_data_sel)—Offset 9007Ch" on page 1730	00000000h
90080h	4	"reg_isel_gpr_reg_gp_isel_sband_sel_type (isel_gpr_reg_gp_isel_sband_sel)—Offset 90080h" on page 1730	00000000h
90084h	4	"reg_isel_gpr_reg_gp_isel_sync_sel_type (isel_gpr_reg_gp_isel_sync_sel)—Offset 90084h" on page 1731	00000000h
90088h	4	"reg_isel_gpr_reg_gp_syncgen_hor_cnt_type (isel_gpr_reg_gp_syncgen_hor_cnt)—Offset 90088h" on page 1732	00000000h
9008Ch	4	"reg_isel_gpr_reg_gp_syncgen_ver_cnt_type (isel_gpr_reg_gp_syncgen_ver_cnt)—Offset 9008Ch" on page 1732	00000000h
90090h	4	"reg_isel_gpr_reg_gp_syncgen_frame_cnt_type (isel_gpr_reg_gp_syncgen_frame_cnt)—Offset 90090h" on page 1733	00000000h
90094h	4	"reg_isel_gpr_reg_gp_soft_reset_type (isel_gpr_reg_gp_soft_reset)—Offset 90094h" on page 1734	00000000h
90100h	4	"reg_isel_fa_send_to_GP_FIFO_type (isel_fa_send_to_GP_FIFO)—Offset 90100h" on page 1734	00000000h
90108h	4	"reg_isel_fa_check_send_to_GP_FIFO_type (isel_fa_check_send_to_GP_FIFO)—Offset 90108h" on page 1735	00000001h
90200h	4	"reg_isel_irq_ctrl_reg_irq_edge_type (isel_irq_ctrl_reg_irq_edge)—Offset 90200h" on page 1736	00000000h
90204h	4	"reg_isel_irq_ctrl_reg_irq_mask_type (isel_irq_ctrl_reg_irq_mask)—Offset 90204h" on page 1736	00000000h
90208h	4	"reg_isel_irq_ctrl_reg_irq_status_type (isel_irq_ctrl_reg_irq_status)—Offset 90208h" on page 1737	00000000h
9020Ch	4	"reg_isel_irq_ctrl_reg_irq_clear_type (isel_irq_ctrl_reg_irq_clear)—Offset 9020Ch" on page 1737	00000000h
90210h	4	"reg_isel_irq_ctrl_reg_irq_enable_type (isel_irq_ctrl_reg_irq_enable)—Offset 90210h" on page 1738	00000000h
90214h	4	"reg_isel_irq_ctrl_reg_irq_level_not_pulse_type (isel_irq_ctrl_reg_irq_level_not_pulse)—Offset 90214h" on page 1739	00000000h
A0000h	4	"reg_icache_out_sys_c_mmu_MMU_invalidate_cache_type (icache_out_sys_c_mmu_MMU_invalidate_cache)—Offset A0000h" on page 1739	00000000h
A0004h	4	"reg_icache_out_sys_c_mmu_MMU_page_table_base_type (icache_out_sys_c_mmu_MMU_page_table_base)—Offset A0004h" on page 1740	00000000h
B0000h	8	"mem_scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_first_type (scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_first)—Offset B0000h" on page 1741	0000000000000000h
B7FF8h	8	"mem_scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_last_type (scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_last)—Offset B7FF8h" on page 1741	0000000000000000h
1C0000h	2	"mem_isp_simd_vamem1_asp_lut_sl_ipvamem_asp_lut_first_type (isp_simd_vamem1_asp_lut_sl_ipvamem_asp_lut_first)—Offset 1C0000h" on page 1742	0000h
1C0FFEh	2	"mem_isp_simd_vamem1_asp_lut_sl_ipvamem_asp_lut_last_type (isp_simd_vamem1_asp_lut_sl_ipvamem_asp_lut_last)—Offset 1C0FFEh" on page 1742	0000h



Table 180. Summary of Image Signal Processor Memory Mapped I/O Registers—ISPMMADR (Continued)

Offset	Size	Register ID—Description	Default Value
1D0000h	2	"mem_isp_simd_vamem2_asp_lut_sl_ipvamem_asp_lut_first_type (isp_simd_vamem2_asp_lut_sl_ipvamem_asp_lut_first)—Offset 1D0000h" on page 1743	0000h
1D0FFEh	2	"mem_isp_simd_vamem2_asp_lut_sl_ipvamem_asp_lut_last_type (isp_simd_vamem2_asp_lut_sl_ipvamem_asp_lut_last)—Offset 1D0FFEh" on page 1743	0000h
1E0000h	2	"mem_isp_simd_vamem3_asp_lut_sl_ipvamem_asp_lut_first_type (isp_simd_vamem3_asp_lut_sl_ipvamem_asp_lut_first)—Offset 1E0000h" on page 1744	0000h
1E0FFEh	2	"mem_isp_simd_vamem3_asp_lut_sl_ipvamem_asp_lut_last_type (isp_simd_vamem3_asp_lut_sl_ipvamem_asp_lut_last)—Offset 1E0FFEh" on page 1744	0000h
1F0000h	4	"mem_isp_simd_histogram_asp_histogram_sl_iphist_asp_histogram_first_type (isp_simd_histogram_asp_histogram_sl_iphist_asp_histogram_first)—Offset 1F0000h" on page 1745	00000000h
1F0FFCh	4	"mem_isp_simd_histogram_asp_histogram_sl_iphist_asp_histogram_last_type (isp_simd_histogram_asp_histogram_sl_iphist_asp_histogram_last)—Offset 1F0FFCh" on page 1745	00000000h
200000h	4	"mem_isp_base_dmem_data_mem_sl_ipdmem_data_mem_first_type (isp_base_dmem_data_mem_sl_ipdmem_data_mem_first)—Offset 200000h" on page 1746	00000000h
203FFCh	4	"mem_isp_base_dmem_data_mem_sl_ipdmem_data_mem_last_type (isp_base_dmem_data_mem_sl_ipdmem_data_mem_last)—Offset 203FFCh" on page 1746	00000000h
300000h	4	"mem_scp_dmem_mem_sl_ip_dmem_mem_first_type (scp_dmem_mem_sl_ip_dmem_mem_first)—Offset 300000h" on page 1747	00000000h
307FFCh	4	"mem_scp_dmem_mem_sl_ip_dmem_mem_last_type (scp_dmem_mem_sl_ip_dmem_mem_last)—Offset 307FFCh" on page 1747	00000000h
380008h	4	"reg_fa_sp_isp_send_to_SP_type (fa_sp_isp_send_to_SP)—Offset 380008h" on page 1748	00000000h
38000Ch	4	"reg_fa_sp_isp_send_to_ISP_type (fa_sp_isp_send_to_ISP)—Offset 38000Ch" on page 1748	00000000h
380010h	4	"reg_fa_sp_isp_check_receive_from_SP_type (fa_sp_isp_check_receive_from_SP)—Offset 380010h" on page 1749	00000001h
380014h	4	"reg_fa_sp_isp_check_receive_from_ISP_type (fa_sp_isp_check_receive_from_ISP)—Offset 380014h" on page 1749	00000001h
380018h	4	"reg_fa_sp_isp_check_send_to_SP_type (fa_sp_isp_check_send_to_SP)—Offset 380018h" on page 1750	00000000h
38001Ch	4	"reg_fa_sp_isp_check_send_to_ISP_type (fa_sp_isp_check_send_to_ISP)—Offset 38001Ch" on page 1751	00000000h

15.8.1 reg_gpd_gp_reg_reg_gp_sdram_wakeup_type (gpd_gp_reg_reg_gp_sdram_wakeup)—Offset 0h

Access Method

Intel Atom® Processor E3800 Product Family
Datasheet
1125



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_irq_req0								
reg_gp_irq_req0								

Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_gp_irq_req0: Unused
0	0h RW	reg_gp_irq_req0: possibly causes an interrupt request (if the host interrupt controller is properly configured)

15.8.4 reg_gpd_gp_reg_reg_gp_irq_req1_type (gpd_gp_reg_reg_gp_irq_req1)—Offset Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_irq_req1: [ISPMMAADR] + Ch

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_irq_req1								reg_gp_irq_req1

Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_gp_irq_req1: Unused
0	0h RW	reg_gp_irq_req1: possibly causes an interrupt request (if the host interrupt controller is properly configured)

15.8.5 reg_gpd_gp_reg_reg_gp_sp_stream_stat_type (gpd_gp_reg_reg_gp_sp_stream_stat)—Offset 10h

Indicate the status of the streaming ports of the scalar processor. All valid and accept signals of the scalar processor are reflected in this register and in reg_gp_sp_stream_stat_b.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_sp_stream_stat: [ISPMMADR] + 10h


ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00022022h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SP_STR_MON_PIFB2SP_accept	SP_STR_MON_PIFB2SP_valid	SP_STR_MON_SP2PIFB_accept	SP_STR_MON_SP2PIFB_valid	SP_STR_MON_SP2PIF_accept	SP_STR_MON_SP2PIF_valid	SP_STR_MON_ISYS2SP_accept	SP_STR_MON_ISYS2SP_valid	SP_STR_MON_SP2ISYS_accept
SP_STR_MON_SP2ISYS_valid	SP_STR_MON_GPD2SP_accept	SP_STR_MON_GPD2SP_valid	SP_STR_MON_SP2GPD_accept	SP_STR_MON_SP2GPD_valid	SP_STR_MON_ISP2SP_accept	SP_STR_MON_ISP2SP_valid	SP_STR_MON_SP2ISP_accept	SP_STR_MON_SP2ISP_valid
SP_STR_MON_DMA2SP_accept	SP_STR_MON_DMA2SP_valid	SP_STR_MON_SP2DMA_accept	SP_STR_MON_SP2DMA_valid	SP_STR_MON_MC2SP_accept	SP_STR_MON_MC2SP_valid	SP_STR_MON_SP2MC_accept	SP_STR_MON_SP2MC_valid	SP_STR_MON_SIF2SP_accept
SP_STR_MON_SIF2SP_valid	SP_STR_MON_SP2SIF_accept	SP_STR_MON_SP2SIF_valid						

Bit Range	Default & Access	Description
31	0h RO	SP_STR_MON_PIFB2SP_accept: Returns the value 1 if the SP can accept an acknowledge token from the FIFO between the primary input formatter B acknowledge port and the SP. Returns the value 0 if the SP cannot accept a token on this SP input port.



Bit Range	Default & Access	Description
30	0h RO	SP_STR_MON_PIFB2SP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the primary input formatter B acknowledge port and the SP, is present on the primary input formatter B input port of the SP. Returns the value 0 if there is no valid acknowledge token available on this SP input port.
29	0h RO	SP_STR_MON_SP2PIFB_accept: Returns the value 1 if the command FIFO between SP and the Primary input formatter B can accept a command from the SP. Returns the value 0 if this FIFO cannot accept a token from the SP.
28	0h RO	SP_STR_MON_SP2PIFB_valid: Returns the value 1 if SP sends a command using the streaming port connected to the Primary Input Formatter B command FIFO. Returns the value 0 if the SP does not send a command to this FIFO
27	0h RO	SP_STR_MON_PIF2SP_accept: Returns the value 1 if the SP can accept an acknowledge token from the FIFO between the primary input formatter acknowledge port and the SP. Returns the value 0 if the SP cannot accept a token on this SP input port.
26	0h RO	SP_STR_MON_PIF2SP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the primary input formatter acknowledge port and the SP, is present on the primary input formatter input port of the SP. Returns the value 0 if there is no valid acknowledge token available on this SP input port.
25	0h RO	SP_STR_MON_SP2PIF_accept: Returns the value 1 if the command FIFO between SP and the Primary input formatter can accept a command from the SP. Returns the value 0 if this command FIFO cannot accept a command from the SP.
24	0h RO	SP_STR_MON_SP2PIF_valid: Returns the value 1 if SP sends a command using the streaming port connected to the Primary Input Formatter command FIFO. Returns the value 0 if the SP does not send a command to the Primary Input formatter
23	0h RO	SP_STR_MON_ISYS2SP_accept: Returns the value 1 if the SP can accept an acknowledge token from the FIFO between the input system acknowledge port and the SP. Returns the value 0 if the SP cannot accept a token on this SP input port.
22	0h RO	SP_STR_MON_ISYS2SP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the input system acknowledge port and the SP, is present on the input system input port of the SP. Returns the value 0 if there is no valid acknowledge token available on this SP input port.
21	0h RO	SP_STR_MON_SP2ISYS_accept: Returns the value 1 if the command FIFO between SP and the input system can accept a command from the SP. Returns the value 0 if this command FIFO cannot accept a command from the SP.
20	0h RO	SP_STR_MON_SP2ISYS_valid: Returns the value 1 if SP sends a command using the streaming port connected to the input system command FIFO. Returns the value 0 if the SP does not send a command to the input system
19	0h RO	SP_STR_MON_GPD2SP_accept: Returns the value 1 if the SP can accept a token from the streaming FIFO between the fifo adapter in GP devices and the SP. Returns 0 if the SP cannot accept a token from this FIFO.
18	0h RO	SP_STR_MON_GPD2SP_valid: Returns the value 1 if the streaming FIFO between the fifo adapter in GP devices and the SP has a valid token for the SP. Returns the value 0 if this FIFO is empty.
17	1h RO	SP_STR_MON_SP2GPD_accept: Returns the value 1 if the token FIFO between SP and fifo adapter can accept a token from the SP. Returns the value 0 if this token FIFO is full.
16	0h RO	SP_STR_MON_SP2GPD_valid: Returns the value 1 if SP sends a token using the streaming port connected to the token FIFO between the SP and the fifo adapter in GP_devices. Returns the value 0 if the SP does not send a token to the fifo adapter.
15	0h RO	SP_STR_MON_ISP2SP_accept: Returns the value 1 if the SP can accept a token from the streaming FIFO between the ISP and the SP. Returns 0 if the SP cannot accept a token from this FIFO.
14	0h RO	SP_STR_MON_ISP2SP_valid: Returns the value 1 if the streaming FIFO between the ISP and the SP has a valid token for the SP. Returns the value 0 if this FIFO is empty
13	1h RO	SP_STR_MON_SP2ISP_accept: Returns the value 1 if the token FIFO between SP and ISP can accept a token from the SP. Returns the value 0 if this token FIFO is full.

Bit Range	Default & Access	Description
12	0h RO	SP_STR_MON_SP2ISP_valid: Returns the value 1 if SP sends a token using the streaming port connected to the ISP token FIFO. Returns the value 0 if the SP does not send a token to the ISP
11	0h RO	SP_STR_MON_DMA2SP_accept: Returns the value 1 if the SP can accept an acknowledge token from the FIFO between the DMA acknowledge port and the SP. Returns the value 0 if the SP cannot accept a token on this SP input port.
10	0h RO	SP_STR_MON_DMA2SP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the DMA acknowledge port and the SP, is present on the DMA input port of the SP. Returns the value 0 if there is no valid acknowledge token available on this SP input port.
9	0h RO	SP_STR_MON_SP2DMA_accept: Returns the value 1 if the command FIFO between SP and the DMA can accept a command from the SP. Returns the value 0 if this command FIFO cannot accept a command from the SP.
8	0h RO	SP_STR_MON_SP2DMA_valid: Returns the value 1 if SP sends a command using the streaming port connected to the DMA command FIFO. Returns the value 0 if the SP does not send a command to the DMA
7	0h RO	SP_STR_MON_MC2SP_accept: Returns the value 1 if the SP can accept an acknowledge token from the FIFO between the stream2mem acknowledge port and the SP. Returns the value 0 if the SP cannot accept a token on this SP input port.
6	0h RO	SP_STR_MON_MC2SP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the stream2mem acknowledge port and the SP, is present on the stream2mem input port of the SP. Returns the value 0 if there is no valid acknowledge token available on this SP input port.
5	1h RO	SP_STR_MON_SP2MC_accept: Returns the value 1 if the command FIFO between SP and the stream2mem can accept a command from the SP. Returns the value 0 if this command FIFO is full.
4	0h RO	SP_STR_MON_SP2MC_valid: Returns the value 1 if SP sends a command using the streaming port connected to the stream2mem command FIFO. Returns the value 0 if the SP does not send a command to the stream2mem
3	0h RO	SP_STR_MON_SIF2SP_accept: Returns the value 1 if the SP can accept an acknowledge token from the FIFO between the secondary input formatter acknowledge port and the SP. Returns the value 0 if the SP cannot accept a token on this SP input port.
2	0h RO	SP_STR_MON_SIF2SP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the secondary input formatter acknowledge port and the SP, is present on the secondary input formatter input port of the SP. Returns the value 0 if there is no valid acknowledge token available on this SP input port.
1	1h RO	SP_STR_MON_SP2SIF_accept: Returns the value 1 if the command FIFO between SP and the secondary input formatter can accept a command from the SP. Returns the value 0 if this command FIFO is full.
0	0h RO	SP_STR_MON_SP2SIF_valid: Returns the value 1 if SP sends a command using the streaming port connected to the Secondary Input Formatter command FIFO. Returns the value 0 if the SP does not send a command to the Secondary Input formatter

15.8.6 reg_gpd_gp_reg_reg_gp_sp_stream_stat_b_type (gpd_gp_reg_reg_gp_sp_stream_stat_b)—Offset 14h

Indicate the status of the streaming ports of the scalar processor. All valid and accept signals of the scalar processor are reflected in this register and in reg_gp_sp_stream_stat.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_sp_stream_stat_b: [ISPMADDR] + 14h


ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_sp_stream_stat_b							SP_STR_MON_GDC22SP_accept	SP_STR_MON_GDC22SP_valid
							SP_STR_MON_SP2GDC2_accept	SP_STR_MON_SP2GDC2_valid
							SP_STR_MON_GDC12SP_accept	SP_STR_MON_GDC12SP_valid
							SP_STR_MON_SP2GDC1_accept	SP_STR_MON_SP2GDC1_valid

Bit Range	Default & Access	Description
31:8	0h RW	unused_reg_gp_sp_stream_stat_b: Unused
7	0h RO	SP_STR_MON_GDC22SP_accept: Returns the value 1 if the SP can accept an acknowledge token from the FIFO between the GDC2 acknowledge port and the SP. Returns the value 0 if the SP cannot accept a token on this SP input port.
6	0h RO	SP_STR_MON_GDC22SP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the GDC2 acknowledge port and the SP, is present on the GDC2 input port of the SP. Returns the value 0 if there is no valid acknowledge token available on this SP input port.
5	0h RO	SP_STR_MON_SP2GDC2_accept: Returns the value 1 if the command FIFO between SP and GDC2 can accept a command from the SP. Returns the value 0 if this command FIFO cannot accept a command from the SP.
4	0h RO	SP_STR_MON_SP2GDC2_valid: Returns the value 1 if SP sends a command using the streaming port connected to GDC2 command FIFO. Returns the value 0 if the SP does not send a command to GDC2
3	0h RO	SP_STR_MON_GDC12SP_accept: Returns the value 1 if the SP can accept an acknowledge token from the FIFO between the GDC1 acknowledge port and the SP. Returns the value 0 if the SP cannot accept a token on this SP input port.
2	0h RO	SP_STR_MON_GDC12SP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the GDC1 acknowledge port and the SP, is present on the GDC1 input port of the SP. Returns the value 0 if there is no valid acknowledge token available on this SP input port.
1	0h RO	SP_STR_MON_SP2GDC1_accept: Returns the value 1 if the command FIFO between SP and GDC1 can accept a command from the SP. Returns the value 0 if this command FIFO cannot accept a command from the SP.
0	0h RO	SP_STR_MON_SP2GDC1_valid: Returns the value 1 if SP sends a command using the streaming port connected to GDC1 command FIFO. Returns the value 0 if the SP does not send a command to GDC1



15.8.7 reg_gpd_gp_reg_reg_gp_isp_stream_stat_type (gpd_gp_reg_reg_gp_isp_stream_stat)—Offset 18h

Indicate the status of the streaming ports of the vector processor. All valid and accept signals of the vector processor are reflected in this register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_isp_stream_stat: [ISPMMADR] + 18h


ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h


Default: 02200000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_isp_stream_stat	ISP_STR_MON_SP2ISP_accept	ISP_STR_MON_SP2ISP_valid	ISP_STR_MON_ISP2SP_accept	ISP_STR_MON_ISP2SP_valid	ISP_STR_MON_GPD2ISP_accept	ISP_STR_MON_GPD2ISP_valid	ISP_STR_MON_ISP2GPD_accept	ISP_STR_MON_ISP2GPD_valid
	ISP_STR_MON_GDC22ISP_accept	ISP_STR_MON_GDC22ISP_valid	ISP_STR_MON_GDC12ISP_accept	ISP_STR_MON_GDC12ISP_valid	ISP_STR_MON_ISP2GDC1_accept	ISP_STR_MON_ISP2GDC1_valid	ISP_STR_MON_DMA2ISP_accept	ISP_STR_MON_DMA2ISP_valid
	ISP_STR_MON_ISP2DMA_accept	ISP_STR_MON_ISP2DMA_valid	ISP_STR_MON_PIFB2ISP_accept	ISP_STR_MON_PIFB2ISP_valid	ISP_STR_MON_ISP2PIFB_accept	ISP_STR_MON_ISP2PIFB_valid	ISP_STR_MON_PIF2ISP_accept	ISP_STR_MON_PIF2ISP_valid
	ISP_STR_MON_ISP2PIFB_accept	ISP_STR_MON_ISP2PIFB_valid	ISP_STR_MON_ISP2PIF_accept	ISP_STR_MON_ISP2PIF_valid	ISP_STR_MON_ISP2PIF_accept	ISP_STR_MON_ISP2PIF_valid	ISP_STR_MON_ISP2PIF_accept	ISP_STR_MON_ISP2PIF_valid

Bit Range	Default & Access	Description
31:28	0h RW	unused_reg_gp_isp_stream_stat: Unused
27	0h RO	ISP_STR_MON_SP2ISP_accept: Returns the value 1 if the ISP can accept a token from the streaming FIFO between the SP and the ISP. Returns 0 if the ISP cannot accept a token from this FIFO.
26	0h RO	ISP_STR_MON_SP2ISP_valid: Returns the value 1 if the streaming FIFO between the SP and the ISP has a valid token for the ISP. Returns the value 0 if this FIFO is empty
25	1h RO	ISP_STR_MON_ISP2SP_accept: Returns the value 1 if the token FIFO between ISP and SP can accept a token from the ISP. Returns the value 0 if this token FIFO is full.
24	0h RO	ISP_STR_MON_ISP2SP_valid: Returns the value 1 if ISP sends a token using the streaming port connected to the SP token FIFO. Returns the value 0 if the ISP does not send a token to the SP
23	0h RO	ISP_STR_MON_GPD2ISP_accept: Returns the value 1 if the ISP can accept a token from the streaming FIFO between the fifo adapter in GP devices and the ISP. Returns 0 if the ISP cannot accept a token from this FIFO.
22	0h RO	ISP_STR_MON_GPD2ISP_valid: Returns the value 1 if the streaming FIFO between the fifo adapter in GP devices and the ISP has a valid token for the ISP. Returns the value 0 if this FIFO is empty.
21	1h RO	ISP_STR_MON_ISP2GPD_accept: Returns the value 1 if the token FIFO between ISP and fifo adapter can accept a token from the ISP. Returns the value 0 if this token FIFO is full.
20	0h RO	ISP_STR_MON_ISP2GPD_valid: Returns the value 1 if ISP sends a token using the streaming port connected to the token FIFO between the ISP and the fifo adapter in GP_devices. Returns the value 0 if the ISP does not send a token to the fifo adapter.



Bit Range	Default & Access	Description
19	0h RO	ISP_STR_MON_GDC22ISP_accept: Returns the value 1 if the ISP can accept an acknowledge token from the FIFO between the GDC2 acknowledge port and the ISP. Returns the value 0 if the ISP cannot accept a token on this ISP input port.
18	0h RO	ISP_STR_MON_GDC22ISP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the GDC2 acknowledge port and the ISP, is present on the GDC2 input port of the ISP. Returns the value 0 if there is no valid acknowledge token available on this ISP input port.
17	0h RO	ISP_STR_MON_ISP2GDC2_accept: Returns the value 1 if the command FIFO between ISP and GDC2 can accept a command from the ISP. Returns the value 0 if this command FIFO is full.
16	0h RO	ISP_STR_MON_ISP2GDC2_valid: Returns the value 1 if ISP sends a command using the streaming port connected to the GDC2 command FIFO. Returns the value 0 if the ISP does not send a command to GDC2
15	0h RO	ISP_STR_MON_GDC12ISP_accept: Returns the value 1 if the ISP can accept an acknowledge token from the FIFO between the GDC1 acknowledge port and the ISP. Returns the value 0 if the ISP cannot accept a token on this ISP input port.
14	0h RO	ISP_STR_MON_GDC12ISP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the GDC1 acknowledge port and the ISP, is present on the GDC1 input port of the ISP. Returns the value 0 if there is no valid acknowledge token available on this ISP input port.
13	0h RO	ISP_STR_MON_ISP2GDC1_accept: Returns the value 1 if the command FIFO between ISP and GDC1 can accept a command from the ISP. Returns the value 0 if this command FIFO is full.
12	0h RO	ISP_STR_MON_ISP2GDC1_valid: Returns the value 1 if ISP sends a command using the streaming port connected to the GDC1 command FIFO. Returns the value 0 if the ISP does not send a command to GDC1
11	0h RO	ISP_STR_MON_DMA2ISP_accept: Returns the value 1 if the ISP can accept an acknowledge token from the FIFO between the DMA acknowledge port and the ISP. Returns the value 0 if the ISP cannot accept a token on this ISP input port.
10	0h RO	ISP_STR_MON_DMA2ISP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the DMA acknowledge port and the ISP, is present on the DMA input port of the ISP. Returns the value 0 if there is no valid acknowledge token available on this ISP input port.
9	0h RO	ISP_STR_MON_ISP2DMA_accept: Returns the value 1 if the command FIFO between ISP and the DMA can accept a command from the ISP. Returns the value 0 if this command FIFO cannot accept a token from the ISP.
8	0h RO	ISP_STR_MON_ISP2DMA_valid: Returns the value 1 if ISP sends a command using the streaming port connected to the DMA command FIFO. Returns the value 0 if the ISP does not send a command to the DMA
7	0h RO	ISP_STR_MON_PIFB2ISP_accept: Returns the value 1 if the ISP can accept an acknowledge token from the FIFO between the primary input formatter B acknowledge port and the ISP. Returns the value 0 if the ISP cannot accept a token on this ISP input port.
6	0h RO	ISP_STR_MON_PIFB2ISP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the primary input formatter B acknowledge port and the ISP, is present on the primary input formatter B input port of the ISP. Returns the value 0 if there is no valid acknowledge token available on this ISP input port.
5	0h RO	ISP_STR_MON_ISP2PIFB_accept: Returns the value 1 if the command FIFO between ISP and the Primary input formatter B can accept a command from the ISP. Returns the value 0 if this FIFO cannot accept a command from the ISP.
4	0h RO	ISP_STR_MON_ISP2PIFB_valid: Returns the value 1 if ISP sends a command using the streaming port connected to the Primary Input Formatter B command FIFO. Returns the value 0 if the ISP does not send a command to the Primary Input formatter B
3	0h RO	ISP_STR_MON_PIF2ISP_accept: Returns the value 1 if the ISP can accept an acknowledge token from the FIFO between the primary input formatter acknowledge port and the ISP. Returns the value 0 if the ISP cannot accept a token on this ISP input port.



Bit Range	Default & Access	Description
2	0h RO	ISP_STR_MON_PIF2ISP_valid: Returns the value 1 if a valid acknowledge token from the FIFO between the primary input formatter acknowledge port and the ISP, is present on the primary input formatter input port of the ISP. Returns the value 0 if there is no valid acknowledge token available on this ISP input port.
1	0h RO	ISP_STR_MON_ISP2PIF_accept: Returns the value 1 if the command FIFO between ISP and the Primary input formatter can accept a command from the ISP. Returns the value 0 if this command FIFO is full.
0	0h RO	ISP_STR_MON_ISP2PIF_valid: Returns the value 1 if ISP sends a command using the streaming port connected to the Primary Input Formatter command FIFO. Returns the value 0 if the ISP does not send a command to the Primary Input formatter

15.8.8 reg_gpd_gp_reg_reg_gp_mod_stream_stat_type (gpd_gp_reg_reg_gp_mod_stream_stat)—Offset 1Ch

Indicate the status of the streaming ports of the modules. All module's valid and accept ports used for control are reflected in this register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_mod_stream_stat: [ISPMADDR] + 1Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: AA88A222h

31	28	24	20	16	12	8	4	0
1 0 1 0	1 0 1 0	1 0 0 0	1 0 0 0	1 0 1 0	0 0 1 0	0 0 1 0	0 0 1 0	0 0 1 0
MOD_STR_MON_CELLS2GDC2_accept	MOD_STR_MON_CELLS2GDC2_valid	MOD_STR_MON_GDC22CELLS_accept	MOD_STR_MON_GDC22CELLS_valid	MOD_STR_MON_CELLS2GDC1_accept	MOD_STR_MON_CELLS2GDC1_valid	MOD_STR_MON_GDC12CELLS_accept	MOD_STR_MON_GDC12CELLS_valid	MOD_STR_MON_MON_SP2DMA_accept
MOD_STR_MON_MON_SP2DMA_valid	MOD_STR_MON_DMA2SP_accept	MOD_STR_MON_DMA2SP_valid	MOD_STR_MON_ISP2DMA_accept	MOD_STR_MON_ISP2DMA_valid	MOD_STR_MON_DMA2ISP_accept	MOD_STR_MON_DMA2ISP_valid	MOD_STR_MON_MON_SP2MC_accept	MOD_STR_MON_MON_SP2MC_valid
MOD_STR_MON_MON_MC2SP_accept	MOD_STR_MON_MON_MC2SP_valid	MOD_STR_MON_MON_SP2SIF_accept	MOD_STR_MON_MON_SP2SIF_valid	MOD_STR_MON_MON_SIF2SP_accept	MOD_STR_MON_MON_SIF2SP_valid	MOD_STR_MON_CELLS2PIFB_accept	MOD_STR_MON_CELLS2PIFB_valid	MOD_STR_MON_PIFB2CELLS_accept
MOD_STR_MON_PIFB2CELLS_valid	MOD_STR_MON_CELLS2PIFA_accept	MOD_STR_MON_CELLS2PIFA_valid	MOD_STR_MON_PIFA2CELLS_accept	MOD_STR_MON_PIFA2CELLS_valid				

Bit Range	Default & Access	Description
31	1h RO	MOD_STR_MON_CELLS2GDC2_accept: Returns the value 1 if the acknowledge FIFO between GDC2 and ISP/SP can accept an acknowledge token from GDC2. Returns the value 0 if this FIFO is full.
30	0h RO	MOD_STR_MON_CELLS2GDC2_valid: Returns the value 1 if GDC2 sends an acknowledge token using the streaming port connected to the acknowledge FIFO to the ISP/SP. Returns the value 0 if GDC2 does not send an acknowledge token to this FIFO.
29	1h RO	MOD_STR_MON_GDC22CELLS_accept: Returns the value 1 if GDC2 can accept a command token from the command FIFO between the ISP/SP and GDC2. Returns the value 0 if GDC2 cannot accept a command token.



Bit Range	Default & Access	Description
28	0h RO	MOD_STR_MON_GDC22CELLS_valid: Returns the value 1 if there is a command available on the command fifo between SP/ISP and GDC2. Returns the value 0 if the command FIFO for GDC2 is empty.
27	1h RO	MOD_STR_MON_CELLS2GDC1_accept: Returns the value 1 if the acknowledge FIFO between GDC1 and ISP/SP can accept an acknowledge token from GDC1. Returns the value 0 if this FIFO is full.
26	0h RO	MOD_STR_MON_CELLS2GDC1_valid: Returns the value 1 if GDC1 sends an acknowledge token using the streaming port connected to the acknowledge FIFO to the ISP/SP. Returns the value 0 if GDC1 does not send an acknowledge token to this FIFO.
25	1h RO	MOD_STR_MON_GDC12CELLS_accept: Returns the value 1 if GDC1 can accept a command token from the command FIFO between the ISP/SP and GDC1. Returns the value 0 if GDC1 cannot accept a command token.
24	0h RO	MOD_STR_MON_GDC12CELLS_valid: Returns the value 1 if there is a command available on the command fifo between SP/ISP and GDC1. Returns the value 0 if the command FIFO for GDC1 is empty.
23	1h RO	MOD_STR_MON_SP2DMA_accept: Returns the value 1 if the acknowledge FIFO between the DMA and SP can accept an acknowledge token from the DMA. Returns the value 0 if this FIFO is full.
22	0h RO	MOD_STR_MON_SP2DMA_valid: Returns the value 1 if DMA sends an acknowledge token using the streaming port connected to the acknowledge FIFO to the SP. Returns the value 0 if the DMA does not send an acknowledge token to this FIFO.
21	0h RO	MOD_STR_MON_DMA2SP_accept: Returns the value 1 if the DMA can accept a command token from the command FIFO between the SP and the DMA. Returns the value 0 if the DMA cannot accept a command token.
20	0h RO	MOD_STR_MON_DMA2SP_valid: Returns the value 1 if there is a command available on the command fifo between SP and the DMA. Returns the value 0 if the command FIFO for the DMA is empty.
19	1h RO	MOD_STR_MON_ISP2DMA_accept: Returns the value 1 if the acknowledge FIFO between the DMA and ISP can accept an acknowledge token from the DMA. Returns the value 0 if this FIFO is full.
18	0h RO	MOD_STR_MON_ISP2DMA_valid: Returns the value 1 if DMA sends an acknowledge token using the streaming port connected to the acknowledge FIFO to the ISP. Returns the value 0 if the DMA does not send an acknowledge token to this FIFO.
17	0h RO	MOD_STR_MON_DMA2ISP_accept: Returns the value 1 if the DMA can accept a command token from the command FIFO between the SP and the DMA. Returns the value 0 if the DMA cannot accept a command token.
16	0h RO	MOD_STR_MON_DMA2ISP_valid: Returns the value 1 if there is a command available on the command fifo between ISP and the DMA. Returns the value 0 if the command FIFO for the DMA is empty.
15	1h RO	MOD_STR_MON_SP2MC_accept: Returns the value 1 if stream2mem can accept a command token from the command FIFO between the SP and the stream2mem. Returns the value 0 if stream2mem cannot accept a command token.
14	0h RO	MOD_STR_MON_SP2MC_valid: Returns the value 1 if there is a command available on the command fifo between the SP and the stream2mem. Returns the value 0 if the command FIFO for the stream2mem is empty.
13	1h RO	MOD_STR_MON_MC2SP_accept: Returns the value 1 if the acknowledge FIFO between the stream2mem and the SP can accept an acknowledge token from the stream2mem. Returns the value 0 if this FIFO is full.
12	0h RO	MOD_STR_MON_MC2SP_valid: Returns the value 1 if the stream2mem sends an acknowledge token using its acknowledge output port connected to the acknowledge FIFO between the stream2mem and the SP. Returns the value 0 if the stream2mem does not send an acknowledge token to this FIFO.
11	0h RO	MOD_STR_MON_SP2SIF_accept: Returns the value 1 if secondary input formatter can accept a command token from the command FIFO between the SP and the secondary input formatter. Returns the value 0 if this FIFO is full.



Bit Range	Default & Access	Description
10	0h RO	MOD_STR_MON_SP2SIF_valid: Returns the value 1 if there is a command available on the command fifo between the SP and the secondary input formatter. Returns the value 0 if the command FIFO for the secondary input formatter is empty.
9	1h RO	MOD_STR_MON_SIF2SP_accept: Returns the value 1 if the acknowledge FIFO between the secondary input formatter and the SP can accept an acknowledge token from the secondary input formatter. Returns the value 0 if this FIFO is full.
8	0h RO	MOD_STR_MON_SIF2SP_valid: Returns the value 1 if the secondary input formatter sends an acknowledge token using its acknowledge output port connected to the acknowledge FIFO between the secondary input formatter and the SP. Returns the value 0 if the secondary input formatter does not send an acknowledge token to this FIFO.
7	0h RO	MOD_STR_MON_CELLS2PIFB_accept: Returns the value 1 if primary input formatter B can accept a command token from the command FIFO between the ISP/SP and the primary input formatter B. Returns the value 0 if the primary input formatter B cannot accept a command token.
6	0h RO	MOD_STR_MON_CELLS2PIFB_valid: Returns the value 1 if there is a command available on the command fifo between SP/ISP and the primary input formatter B. Returns the value 0 if the command FIFO for the primary input formatter B is empty.
5	1h RO	MOD_STR_MON_PIFB2CELLS_accept: Returns the value 1 if the acknowledge FIFO between the primary input formatter B and the ISP/SP can accept an acknowledge token from the primary input formatter B. Returns the value 0 if this command FIFO is full.
4	0h RO	MOD_STR_MON_PIFB2CELLS_valid: Returns the value 1 if primary input formatter B sends an acknowledge token using the streaming port connected to the acknowledge FIFO to the ISP/SP. Returns the value 0 if the primary input formatter B does not send an acknowledge token to this FIFO.
3	0h RO	MOD_STR_MON_CELLS2PIFA_accept: Returns the value 1 if primary input formatter A can accept a command token from the command FIFO between the ISP/SP and the primary input formatter A. Returns the value 0 if the primary input formatter A cannot accept a command token.
2	0h RO	MOD_STR_MON_CELLS2PIFA_valid: Returns the value 1 if there is a command available on the command fifo between SP/ISP and the primary input formatter A. Returns the value 0 if the command FIFO for the primary input formatter A is empty.
1	1h RO	MOD_STR_MON_PIFA2CELLS_accept: Returns the value 1 if the acknowledge FIFO between the primary input formatter A and the ISP/SP can accept an acknowledge token from the primary input formatter A. Returns the value 0 if this command FIFO is full.
0	0h RO	MOD_STR_MON_PIFA2CELLS_valid: Returns the value 1 if primary input formatter A sends an acknowledge token using the streaming port connected to the acknowledge FIFO to the ISP/SP. Returns the value 0 if the primary input formatter A does not send an acknowledge token to this FIFO.

15.8.9 reg_gpd_gp_reg_reg_gp_sp_stream_stat_irq_cond_type (gpd_gp_reg_reg_gp_sp_stream_stat_irq_cond)—Offset 20h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_sp_stream_stat_irq_cond:
[ISPMADR] + 20h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_sp_stream_stat_b_irq_cond:
[ISPMADR] + 24h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_sp_stream_stat_b_irq_cond								
reg_gp_sp_stream_stat_b_irq_cond								



Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_sp_stream_stat_irq_enable:
[ISPMADR] + 30h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_sp_stream_stat_irq_enable reg_gp_sp_stream_stat_irq_enable								



Bit Range	Default & Access	Description
31:16	0h RW	unused_reg_gp_sp_stream_stat_irq_enable: Unused
15:0	0h RW	reg_gp_sp_stream_stat_irq_enable: This register enables the SP streaming stat irq output for each of the 16 ports

15.8.14 reg_gpd_gp_reg_reg_gp_sp_stream_stat_b_irq_enable_type
(gpd_gp_reg_reg_gp_sp_stream_stat_b_irq_enable)—Offset
34h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_sp_stream_stat_b_irq_enable:
[ISPMMAADR] + 34h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_sp_stream_stat_b_irq_enable								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0
								0

Bit Range	Default & Access	Description
31:4	0h RW	unused_reg_gp_sp_stream_stat_b_irq_enable: Unused
3:0	0h RW	reg_gp_sp_stream_stat_b_irq_enable: This register enables the SP streaming stat b irq output for each of the 4 ports

15.8.15 **reg_gpd_gp_reg_reg_gp_isp_stream_stat_irq_enable_type**
(gpd_gp_reg_reg_gp_isp_stream_stat_irq_enable)—Offset
38h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_isp_stream_stat_irq_enable:
[ISPMADR] + 38h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_isp_stream_stat_irq_enable				reg_gp_isp_stream_stat_irq_enable				

Bit Range	Default & Access	Description
31:14	0h RW	unused_reg_gp_isp_stream_stat_irq_enable: Unused
13:0	0h RW	reg_gp_isp_stream_stat_irq_enable: This register enables the ISP streaming stat irq output for each of the 14 ports

15.8.16 reg_gpd_gp_reg_reg_gp_mod_stream_stat_irq_enable_type (gpd_gp_reg_reg_gp_mod_stream_stat_irq_enable)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_mod_stream_stat_irq_enable:
[ISPMADR] + 3Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_mod_stream_stat_irq_enable					reg_gp_mod_stream_stat_irq_enable			

Bit Range	Default & Access	Description
31:16	0h RW	unused_reg_gp_mod_stream_stat_irq_enable: Unused
15:0	0h RW	reg_gp_mod_stream_stat_irq_enable: This register enables the MOD streaming stat irq output for each of the 16 ports

15.8.17 reg_gpd_gp_reg_reg_gp_switch_if_type (gpd_gp_reg_reg_gp_switch_if)—Offset 40h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_switch_if: [ISPMMAADR] + 40h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_switch_if								
reg_gp_switch_if								

Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_gp_switch_if: Unused



Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_gp_switch_gdc1: Unused
0	0h RW	reg_gp_switch_gdc1: Selects the control stream switch for the GDC1. GDC1 can be controlled by the scalar processor (value=1) or the ISP (value=0)



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_switch_gdc2								reg_gp_switch_gdc2

Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_gp_switch_gdc2: Unused
0	0h RW	reg_gp_switch_gdc2: Selects the control stream switch for the GDC2. GDC2 can be controlled by the scalar processor (value=1) or the ISP (value=0)

15.8.20 reg_gpd_gp_reg_reg_gp_srst_type (gpd_gp_reg_reg_gp_srst)—Offset 4Ch

Soft reset for several modules in the system. If '1' is written to a bit, the module(s) connected to that bit are held in reset until a '0' is written to that bit.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gp_reg_reg_gp_srst: [ISPMMADR] + 4Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0																					
0	0	0	0	0	0	0	0	0																					
unused_reg_gp_srst	SRST_WBUS	SRST_HOST12BUS	SRST_NBUS	SRST_OCP2CIO	SRST_SP	SRST_SF_GDC2_CELLS	SRST_SF_GDC1_CELLS	SRST_SF_DMA_CELLS	SRST_SF_ISYS_SP	SRST_SF_MC_SP	SRST_SF_SIF_SP	SRST_SF_PIF_CELLS	SRST_SF_ISP_SP	SRST_DMA	SRST_SLV_GRP_BUS	SRST_ISP	SRST_VEC_BUS	SRST_GDC2	SRST_GDC1	SRST_IPT_SEC_PIPE	SRST_OSYS	SRST_FACELLFIFOS	SRST_GPTIMER	SRST_TC	SRST_GPIO	SRST_GPDEV_CBUS	SRST_IFMT_CBUS	SRST_ISEL_CBUS	SRST_ISYS_CBUS

Bit Range	Default & Access	Description
31:29	0h RW	unused_reg_gp_srst: Unused
28	0h RW	SRST_WBUS: soft reset bit for the wide bus



Bit Range	Default & Access	Description
27	0h RW	SRST_HOST12BUS: soft reset bit for the bus from host to fifo adapters
26	0h RW	SRST_NBUS: soft reset bit for the narrow bus
25	0h RW	SRST_OCP2CIO: soft reset bit for the OCP2CIO converter
24	0h RW	SRST_SP: soft reset bit for the SP
23	0h RW	SRST_SF_GDC2_CELLS: soft reset bit for the FIFOs between the GDC2 and the cells
22	0h RW	SRST_SF_GDC1_CELLS: soft reset bit for the FIFOs between the GDC1 and the cells
21	0h RW	SRST_SF_DMA_CELLS: soft reset bit for the FIFOs between the DMA and the cells
20	0h RW	SRST_SF_ISYS_SP: soft reset bit for the FIFOs between the input system and the SP
19	0h RW	SRST_SF_MC_SP: soft reset bit for the FIFOs between the stream2memory and the SP
18	0h RW	SRST_SF_SIF_SP: soft reset bit for the FIFOs between the secondary input formatter and the SP
17	0h RW	SRST_SF_PIF_CELLS: soft reset bit for the FIFOs between the primary input formatters and the cells
16	0h RW	SRST_SF_ISP_SP: soft reset bit for the FIFOs between SP and ISP
15	0h RW	SRST_DMA: soft reset bit for the DMA
14	0h RW	SRST_SLV_GRP_BUS: soft reset bit for the slave group bus
13	0h RW	SRST_ISP: soft reset bit for the isp (vector processor)
12	0h RW	SRST_VEC_BUS: soft reset bit for the vector bus
11	0h RW	SRST_GDC2: soft reset bit for the GDC2 block
10	0h RW	SRST_GDC1: soft reset bit for the GDC1 block
9	0h RW	SRST_IPT_SEC_PIPE: soft reset bit for the CIO pipeline after the secondary input formatter
8	0h RW	SRST_OSYS: soft reset bit for the blocks in the output system cluster
7	0h RW	SRST_FACELLFIFOS: soft reset bit for the fifo's connected to the fifo adapter between host and cells
6	0h RW	SRST_GPTIMER: soft reset bit for the GP timer block
5	0h RW	SRST_TC: soft reset bit for the timed controller block



Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_tc_FifoWriteCmd: [ISPMADR] + 100h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
FifoWriteCmd								

Bit Range	Default & Access	Description
31:0	0h WO	FifoWriteCmd: Timed controller Command input. A Timed Controller command consists of 5 32-bit tokens that need to be written sequentially to this register location

15.8.23 reg_gpd_c_gpio_reg_gpio_doe_type (gpd_c_gpio_reg_gpio_doe)—Offset 400h

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_c_gpio_reg_gpio_doe: [ISPMADR] + 400h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gpio_doe						reg_gpio_doe		

Bit Range	Default & Access	Description
31:12	0h RW	unused_reg_gpio_doe: Unused
11:0	0h RW	reg_gpio_doe: indicates for each bit whether it is intended to be an input (value='0') or an output (value='1')



Access Method

gpd_c_gpio_reg_gpio_do_1: [ISPMADR] + 40Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gpio_do_1						reg_gpio_do_1		

15.8.27 reg_gpd_c_gpio_reg_gpio_do_pwm_cnt_0_type (gpd_c_gpio_reg_gpio_do_pwm_cnt_0)—Offset 410h

Access Method

gpd_c_gpio_reg_gpio_do_pwm_cnt_0: [ISPMADR] + 410h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gpio_do_pwm_cnt_0								reg_gpio_do_pwm_cnt_0

Bit Range	Default & Access	Description
31:6	0h RW	unused_reg_gpio_do_pwm_cnt_0: Unused
5:0	0h RW	reg_gpio_do_pwm_cnt_0: indicates duty cycle for PWM output 0. value d means duty cycle d/64

15.8.28 reg_gpd_c_gpio_reg_gpio_do_pwm_cnt_1_type (gpd_c_gpio_reg_gpio_do_pwm_cnt_1)—Offset 414h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_c_gpio_reg_gpio_do_pwm_cnt_1: [ISPMMAADR] + 414h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gpio_do_pwm_cnt_1								reg_gpio_do_pwm_cnt_1

Bit Range	Default & Access	Description
31:6	0h RW	unused_reg_gpio_do_pwm_cnt_1: Unused



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:6	0h RW	unused_reg_gpio_do_pwm_cnt_2: Unused
5:0	0h RW	reg_gpio_do_pwm_cnt_2: indicates duty cycle for PWM output 2. value d means duty cycle d/64

15.8.30 reg_gpd_c_gpio_reg_gpio_do_pwm_cnt_3_type
(gpd c gpio reg gpio do pwm cnt 3)—Offset 41Ch

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_c_gpio_reg_gpio_do_pwm_main_cnt: [ISPMADR] + 420h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gpio_do_pwm_main_cnt				reg_gpio_do_pwm_main_cnt				

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:12	0h RW	unused_reg_gpio_do_pwm_enable: Unused
11:0	0h RW	reg_gpio_do_pwm_enable: indicates per bit whether PWM is on (value='1') or output is fixed '0' (value='0')

15.8.33 `reg_gpd_c_gpio_reg_gpio_di_debouncemethod_type`
(`gpd_c_gpio_reg_gpio_di_debouncemethod`)—Offset 428h

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_c_gpio_reg_gpio_di_debouncemethod: [ISPMADR] + 428h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
1152





15.8.36 reg_gpd_c_gpio_reg_gpio_di_debounce_cnt2_type
(gpd_c_gpio_reg_gpio_di_debounce_cnt2)—Offset 434h



Bit Range	Default & Access	Description
31:0	0h RW	reg_gpio_di_debounce_cnt2: Indicates the period an input has to be stable before passing its value to the output

15.8.37 [reg_gpd_c_gpio_reg_gpio_di_debounce_cnt3_type](#)
([gpd_c_gpio_reg_gpio_di_debounce_cnt3](#))—Offset 438h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_c_gpio_reg_gpio_di_debounce_cnt3: [ISPMADR] + 438h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_gpio_di_debounce_cnt3								

Bit Range	Default & Access	Description
31:0	0h RW	reg_gpio_di_debounce_cnt3: Indicates the period an input has to be stable before passing its value to the output

15.8.38 reg_gpd_c_gpio_reg_gpio_di_activelevel_type (gpd c gpio reg gpio di activelevel)—Offset 43Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_c_gpio_reg_gpio_di_activelevel: [ISPMADR] + 43Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000FFFh



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gpio_di						reg_gpio_di		

October 2018
Document Number: 538136, Rev. 4.3



15.8.40 reg_gpd_irq_ctrl_reg_irq_edge_type (gpd_irq_ctrl_reg_irq_edge)—Offset 500h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_irq_ctrl_reg_irq_edge: [ISPMMAADR] + 500h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	reg_irq_edge: indicates for each bit whether an interrupt request should be generated on a falling edge (value='0') or a rising edge (value='1').

15.8.41 reg_gpd_irq_ctrl_reg_irq_mask_type (gpd_irq_ctrl_reg_irq_mask)—Offset 504h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_irq_ctrl_reg_irq_mask: [ISPMMAADR] + 504h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	reg_irq_mask: indicates for each bit of irq_di whether it can generate an interrupt request (value='1') or not (value='0'). Setting will affect reg_irq_value as well as IRQ output pin

15.8.42 reg_gpd_irq_ctrl_reg_irq_status_type (gpd_irq_ctrl_reg_irq_status)—Offset 508h

Indicates for each bit whether a non-masked interrupt has been generated (value='1'). Can be cleared by writing a '1' into the the corresponding bit of the req_irq_clear register.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_irq_ctrl_reg_irq_status: [ISPMADDR] + 508h


ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
IRQ_STAT_SP_SMON_B	IRQ_STAT_DMA	IRQ_STAT_SW_1	IRQ_STAT_SW_0	IRQ_STAT_GPTIMER_1	IRQ_STAT_GPTIMER_0	IRQ_STAT_ISYS_2	IRQ_STAT_SP_DMEM_ERROR	IRQ_STAT_SP_IMEM_ERROR
IRQ_STAT_ISP_DMEM_ERROR	IRQ_STAT_ISP_BAMEM_ERROR	IRQ_STAT_ISP_PMEM_ERROR	IRQ_STAT_MOD_SMON	IRQ_STAT_ISP_SMON	IRQ_STAT_SP_SMON	IRQ_STAT_IFMT	IRQ_STAT_ISEL	IRQ_STAT_ISYS
IRQ_STAT_ISP	IRQ_STAT_SP	IRQ_STAT_GPIO_PINS						

Bit Range	Default & Access	Description
31	0h RO	IRQ_STAT_SP_SMON_B: Represents the irq status of the irq_out from the SP streaming monitor b
30	0h RO	IRQ_STAT_DMA: Represents the irq status of the DMA
29	0h RO	IRQ_STAT_SW_1: Represents the irq status of the GP register IRQ SW 1
28	0h RO	IRQ_STAT_SW_0: Represents the irq status of the GP register IRQ SW 0
27	0h RO	IRQ_STAT_GPTIMER_1: Represents the irq status of the irq[1] out signal from the GP Timer block
26	0h RO	IRQ_STAT_GPTIMER_0: Represents the irq status of the irq[0] out signal from the GP Timer block
25	0h RO	IRQ_STAT_ISYS_2: Represents the irq status of the irq out signal from the input system
24	0h RO	IRQ_STAT_SP_DMEM_ERROR: Represents the irq status of the error signal from the SP data memory
23	0h RO	IRQ_STAT_SP_IMEM_ERROR: Represents the irq status of the error signal from the SP instruction cache memory
22	0h RO	IRQ_STAT_ISP_DMEM_ERROR: Represents the irq status of the error signal from the ISP data memory
21	0h RO	IRQ_STAT_ISP_BAMEM_ERROR: Represents the irq status of the error signal from the ISP vector memory
20	0h RO	IRQ_STAT_ISP_PMEM_ERROR: Represents the irq status of the error signal from the ISP program memory
19	0h RO	IRQ_STAT_MOD_SMON: Represents the irq status of the irq_out from the MOD streaming monitor



Bit Range	Default & Access	Description
18	0h RO	IRQ_STAT_ISP_SMON: Represents the irq status of the irq_out from the ISP streaming monitor
17	0h RO	IRQ_STAT_SP_SMON: Represents the irq status of the irq_out from the SP streaming monitor
16	0h RO	IRQ_STAT_IFMT: Represents the irq status of the irq_out from the input formatting subsystem
15	0h RO	IRQ_STAT_ISEL: Represents the irq status of the irq_out from the input selector
14	0h RO	IRQ_STAT_ISYS: Represents the irq status of the irq_out from the input system
13	0h RO	IRQ_STAT_ISP: Represents the irq status of the irq_out from isp2300
12	0h RO	IRQ_STAT_SP: Represents the irq status of the irq_out from scalar processor
11:0	0h RO	IRQ_STAT_GPIO_PINS: Represents the irq status of the - potentially debounced - GPIO input pins

15.8.43 reg_gpd_irq_ctrl_reg_irq_clear_type (gpd_irq_ctrl_reg_irq_clear)—Offset 50Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_irq_ctrl_reg_irq_clear: [ISPMADDR] + 50Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h WO	reg_irq_clear: Clears (set to '0') bits in reg_irq_status. When writing a '1' into a bit of this register, the corresponding bit in the req_irq_status is cleared. When writing a '0' into a bit of this register, the corresponding bit in the req_irq_status is not affected.

15.8.44 reg_gpd_irq_ctrl_reg_irq_enable_type (gpd_irq_ctrl_reg_irq_enable)—Offset 510h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_irq_ctrl_reg_irq_enable: [ISPMADDR] + 510h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h



15.8.45 **reg_gpd_irq_ctrl_reg_irq_level_not_pulse_type**
(gpd_irq_ctrl_reg_irq_level_not_pulse)—Offset 514h

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_irq_ctrl_reg_irq_level_not_pulse: [ISPMADR] + 514h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_irq_level_not_pulse								

Bit Range	Default & Access	Description
31:0	0h RW	reg_irq_level_not_pulse: Indicates for each bit whether an interrupt cause is translated into a pulse (value='0') or into a constant level '1' (value='1') on the IRQ pin.

15.8.46 reg_gpd_irq_ctrl_reg_irq_str_out_enable_type (gpd_irq_ctrl_reg_irq_str_out_enable)—Offset 518h

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_irq_ctrl_reg_irq_str_out_enable: [ISPMMAADR] + 518h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_irq_str_out_enable								

Bit Range	Default & Access	Description
31:0	0h RW	reg_irq_str_out_enable: Indicates for each bit whether an interrupt cause as monitored by the reg_irq_status register also results in a send token on the irq_str_out port (value='1') or not (value='0')

15.8.47 reg_gpd_gptimer_reg_reset_type (gpd_gptimer_reg_reset)– Offset 600h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_reg_reset: [ISPMADR] + 600h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
							reg_reset	

Bit Range	Default & Access	Description
31:8	0h RW	unused_reg_reset: Unused
7:0	0h WO	reg_reset: GP Timer reset. Write '1' to bit x to reset timer x. Write 0xFF to reset all timers.

15.8.48 reg_gpd_gptimer_overall_enable_type (gpd_gptimer_overall_enable)—Offset 604h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

qpd qptimer overall enable: [ISPMMAADR] + 604h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h



	31	28	24	20	16	12	8	4	0		
	0	0	0	0	0	0	0	0	0	0	
	unused_overall_enable										overall_enable

Bit Range	Default & Access	Description
31:1	0h RW	unused_overall_enable: Unused
0	0h RW	overall_enable: GP Timer enable. Write '1' to enable all enabled timers, write '0' to disable all timers.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_enable_timer_0: [ISPMADR] + 608h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
				unused_enable_timer_0					enable_timer_0

Bit Range	Default & Access	Description
31:1	0h RW	unused_enable_timer_0: Unused
0	0h RW	enable_timer_0: GP Timer enable. Write '1' to enable timer 0. Write '0' to disable timer 0

15.8.50 reg_gpd_gptimer_enable_timer_1_type (gpd_gptimer_enable_timer_1)–Offset 60Ch

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_enable_timer_1: [ISPMADR] + 60Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_enable_timer_1								enable_timer_1

Bit Range	Default & Access	Description
31:1	0h RW	unused_enable_timer_1: Unused
0	0h RW	enable_timer_1: GP Timer enable. Write '1' to enable timer 1. Write '0' to disable timer 1

15.8.51 reg_gpd_gptimer_enable_timer_2_type (gpd_gptimer_enable_timer_2)—Offset 610h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_enable_timer_2: [ISPMADR] + 610h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_enable_timer_2								enable_timer_2

Bit Range	Default & Access	Description
31:1	0h RW	unused_enable_timer_2: Unused
0	0h RW	enable_timer_2: GP Timer enable. Write '1' to enable timer 2. Write '0' to disable timer 2



15.8.52 reg_gpd_gptimer_enable_timer_3_type (gpd_gptimer_enable_timer_3)—Offset 614h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_enable_timer_3: [ISPMMAADR] + 614h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_enable_timer_3								enable_timer_3

Bit Range	Default & Access	Description
31:1	0h RW	unused_enable_timer_3: Unused
0	0h RW	enable_timer_3: GP Timer enable. Write '1' to enable timer 3. Write '0' to disable timer 3

15.8.53 reg_gpd_gptimer_enable_timer_4_type (gpd_gptimer_enable_timer_4)—Offset 618h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_enable_timer_4: [ISPMMAADR] + 618h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_enable_timer_4								enable_timer_4



Bit Range	Default & Access	Description
31:1	0h RW	unused_enable_timer_4: Unused
0	0h RW	enable_timer_4: GP Timer enable. Write '1' to enable timer 4. Write '0' to disable timer 4

15.8.54 reg_gpd_gptimer_enable_timer_5_type (gpd_gptimer_enable_timer_5)—Offset 61Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_enable_timer_5: [ISPMADR] + 61Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
unused_enable_timer_5									
enable_timer_5									

Bit Range	Default & Access	Description
31:1	0h RW	unused_enable_timer_5: Unused
0	0h RW	enable_timer_5: GP Timer enable. Write '1' to enable timer 5. Write '0' to disable timer 5

15.8.55 reg_gpd_gptimer_enable_timer_6_type (gpd_gptimer_enable_timer_6)—Offset 620h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_enable_timer_6: [ISPMADR] + 620h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:1	0h RW	unused_enable_timer_7: Unused
0	0h RW	enable_timer_7: GP Timer enable. Write '1' to enable timer 7. Write '0' to disable timer 7

15.8.57 **reg_gpd_gptimer_value_timer_0_type**
(gpd_gptimer_value_timer_0)—Offset 628h

Access Method



Bit Range	Default & Access	Description
31:0	0h RO	value_timer_3: Returns the value of timer 3

15.8.61 reg_gpd_gptimer_value_timer_4_type (gpd_gptimer_value_timer_4)—Offset 638h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RO	value_timer_4: Returns the value of timer 4

15.8.62 reg_gpd_gptimer_value_timer_5_type (gpd_gptimer_value_timer_5)—Offset 63Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_value_timer_5: [ISPMMADR] + 63Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RO	value_timer_5: Returns the value of timer 5

15.8.63 reg_gpd_gptimer_value_timer_6_type (gpd_gptimer_value_timer_6)—Offset 640h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_value_timer_6: [ISPMMADR] + 640h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

value_timer_6

Bit Range	Default & Access	Description
31:0	0h RO	value_timer_6: Returns the value of timer 6

15.8.64 reg_gpd_gptimer_value_timer_7_type (gpd_gptimer_value_timer_7)—Offset 644h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_value_timer_7: [ISPMADDR] + 644h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

value_timer_7

Bit Range	Default & Access	Description
31:0	0h RO	value_timer_7: Returns the value of timer 7

15.8.65 reg_gpd_gptimer_count_type_timer_0_type (gpd_gptimer_count_type_timer_0)—Offset 648h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_count_type_timer_0: [ISPMADDR] + 648h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:2	0h RW	unused_count_type_timer_1: Unused
1:0	0h RW	count_type_timer_1: Indicates what needs to be counted by timer 1, 00- # cycles the signal is high (1), 01- # cycles the signal is low (0), 10- # changes from low to high, 11- # changes from high to low



Bit Range	Default & Access	Description
31:2	0h RW	unused_count_type_timer_3: Unused
1:0	0h RW	count_type_timer_3: Indicates what needs to be counted by timer 3, 00- # cycles the signal is high (1), 01- # cycles the signal is low (0), 10- # changes from low to high, 11- # changes from high to low

15.8.69 **reg_gpd_gptimer_count_type_timer_4_type**
(gpd_gptimer_count_type_timer_4)—Offset 658h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

qpd qptimer count type timer 4: [ISPMADR] + 658h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:2	0h RW	unused_count_type_timer_4: Unused
1:0	0h RW	count_type_timer_4: Indicates what needs to be counted by timer 4, 00- # cycles the signal is high (1), 01- # cycles the signal is low (0), 10- # changes from low to high, 11- # changes from high to low

15.8.70 reg_gpd_gptimer_count_type_timer_5_type (gpd_gptimer_count_type_timer_5)—Offset 65Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_count_type_timer_5: [ISPMADR] + 65Ch


ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:2	0h RW	unused_count_type_timer_6: Unused
1:0	0h RW	count_type_timer_6: Indicates what needs to be counted by timer 6, 00- # cycles the signal is high (1), 01- # cycles the signal is low (0), 10- # changes from low to high, 11- # changes from high to low



Bit Range	Default & Access	Description
31:6	0h RW	unused_signal_select_timer_0: Unused
5:0	0h RW	signal_select_timer_0: Selects which of the 55 input signals is counted by timer 0

15.8.74 reg_gpd_gptimer_signal_select_timer_1_type (gpd_gptimer_signal_select_timer_1)—Offset 66Ch

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_signal_select_timer_1: [ISPMADDR] + 66Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:6	0h RW	unused_signal_select_timer_1: Unused
5:0	0h RW	signal_select_timer_1: Selects which of the 55 input signals is counted by timer 1



15.8.75 reg_gpd_gptimer_signal_select_timer_2_type (gpd_gptimer_signal_select_timer_2)—Offset 670h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_signal_select_timer_2: [ISPMMAADR] + 670h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_signal_select_timer_2								signal_select_timer_2

Bit Range	Default & Access	Description
31:6	0h RW	unused_signal_select_timer_2: Unused
5:0	0h RW	signal_select_timer_2: Selects which of the 55 input signals is counted by timer 2

15.8.76 reg_gpd_gptimer_signal_select_timer_3_type (gpd_gptimer_signal_select_timer_3)—Offset 674h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_signal_select_timer_3: [ISPMMAADR] + 674h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:6	0h RW	unused_signal_select_timer_3: Unused
5:0	0h RW	signal_select_timer_3: Selects which of the 55 input signals is counted by timer 3

15.8.77 reg_gpd_gptimer_signal_select_timer_4_type (gpd_gptimer_signal_select_timer_4)—Offset 678h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_signal_select_timer_4: [ISPMADDR] + 678h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:6	0h RW	unused_signal_select_timer_4: Unused
5:0	0h RW	signal_select_timer_4: Selects which of the 55 input signals is counted by timer 4



15.8.78 reg_gpd_gptimer_signal_select_timer_5_type (gpd_gptimer_signal_select_timer_5)—Offset 67Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_signal_select_timer_5: [ISPMMA DR] + 67Ch

ISPMMA DR Type: PCI Configuration Register (Size: 32 bits)

ISPMMA DR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_signal_select_timer_5								signal_select_timer_5

Bit Range	Default & Access	Description
31:6	0h RW	unused_signal_select_timer_5: Unused
5:0	0h RW	signal_select_timer_5: Selects which of the 55 input signals is counted by timer 5

15.8.79 reg_gpd_gptimer_signal_select_timer_6_type (gpd_gptimer_signal_select_timer_6)—Offset 680h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_signal_select_timer_6: [ISPMMA DR] + 680h

ISPMMA DR Type: PCI Configuration Register (Size: 32 bits)

ISPMMA DR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:6	0h RW	unused_signal_select_timer_6: Unused
5:0	0h RW	signal_select_timer_6: Selects which of the 55 input signals is counted by timer 6

15.8.80 reg_gpd_gptimer_signal_select_timer_7_type (gpd_gptimer_signal_select_timer_7)—Offset 684h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_signal_select_timer_7: [ISPMADDR] + 684h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:6	0h RW	unused_signal_select_timer_7: Unused
5:0	0h RW	signal_select_timer_7: Selects which of the 55 input signals is counted by timer 7



15.8.83 reg_gpd_gptimer_irq_timer_select_0_type (gpd_gptimer_irq_timer_select_0)—Offset 690h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_irq_timer_select_0: [ISPMADDR] + 690h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_irq_timer_select_0								irq_timer_select_0

Bit Range	Default & Access	Description
31:3	0h RW	unused_irq_timer_select_0: Unused
2:0	0h RW	irq_timer_select_0: Indicates which of the 8 timers will be used for irq_0 generation

15.8.84 reg_gpd_gptimer_irq_timer_select_1_type (gpd_gptimer_irq_timer_select_1)—Offset 694h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_irq_timer_select_1: [ISPMADDR] + 694h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_irq_timer_select_1								irq_timer_select_1



Bit Range	Default & Access	Description
31:3	0h RW	unused_irq_timer_select_1: Unused
2:0	0h RW	irq_timer_select_1: Indicates which of the 8 timers will be used for irq_1 generation

15.8.85 **reg_gpd_gptimer_irq_enable_0_type**
(gpd_gptimer_irq_enable_0)—Offset 698h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_irq_enable_0: [ISPMMAADR] + 698h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
unused_irq_enable_0									
unused_irq_enable_0									

Bit Range	Default & Access	Description
31:1	0h RW	unused_irq_enable_0: Unused
0	0h RW	irq_enable_0: Enable interrupt 0

15.8.86 reg_gpd_gptimer_irq_enable_1_type (gpd_gptimer_irq_enable_1)—Offset 69Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gpd_gptimer_irq_enable_1: [ISPMMAADR] + 69Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_irq_enable_1								irq_enable_1

Bit Range	Default & Access	Description
31:1	0h RW	unused_irq_enable_1: Unused
0	0h RW	irq_enable_1: Enable interrupt 1

15.8.87 reg_scp_stat_and_ctrl_type (scp_stat_and_ctrl)—Offset 10000h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

scp_stat_and_ctrl: [ISPMADDR] + 10000h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 000000A0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_stat_and_ctrl				arb_period_dmem_Arb_mem_wp				1
arb_cont_dmem_Arb_mem_wp_source1				prefetch_enable_flag				0
arb_cont_dmem_Arb_mem_wp_source0				invalidate_cache_flag				1
				sleeping_irq_mask_flag				0
				ready_irq_mask_flag				0
				broken_irq_mask_flag				0
				irq_clear_flag				0
				stalling_flag				0
				sleeping_flag				0
				ready_flag				0
				broken_flag				0
				run_flag				0
				break_flag				0
				start_flag				0
				reset_flag				0

Bit Range	Default & Access	Description
31:29	0h RW	unused_stat_and_ctrl: Unused
28:24	0h RW	arb_cont_dmem_Arb_mem_wp_source1: Arbiter contender group bandwidth for dmem_Arb_mem_wp_source1



Bit Range	Default & Access	Description
23:19	0h RW	arb_cont_dmem_Arb_mem_wp_source0 : Arbiter contender group bandwidth for dmem_Arb_mem_wp_source0
18:14	0h RW	arb_period_dmem_Arb_mem_wp : Arbiter period for dmem_Arb_mem_wp
13	0h RW	prefetch_enable_flag : Prefetch enable flag for config_ilm_conf_ilm_icache
12	0h RW	invalidate_cache_flag : Invalidate cache flag for config_ilm_conf_ilm_icache
11	0h RW	sleeping_irq_mask_flag : Sleeping IRQ mask flag
10	0h RW	ready_irq_mask_flag : Ready IRQ mask flag
9	0h RW	broken_irq_mask_flag : Broken IRQ mask flag
8	0h RW	irq_clear_flag : IRQ clear flag
7	1h RO	stalling_flag : Stalling flag. Set to one when not executing an instruction.
6	0h RO	sleeping_flag : Sleeping flag
5	1h RO	ready_flag : Ready flag. Set to one when not executing a program.
4	0h RO	broken_flag : Broken flag
3	0h RW	run_flag : Run flag
2	0h RW	break_flag : Break flag
1	0h WO	start_flag : Start flag
0	0h WO	reset_flag : Reset flag

15.8.88 reg_scp_base_address_type (scp_base_address)—Offset 10004h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

scp_base_address: [ISPMADDR] + 10004h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

scp unused 2: [ISPMMADR] + 10008h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]

Bit Range	Default & Access	Description
31:0	0h RW	unused_2: Unused

15.8.90 reg_scp_base_addr_seg_0_MI_xmem_master_int_type
(scp_base_addr_seg_0 MI xmem master int)—Offset 10010h

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
scp_base_addr_seg_0_MI_xmem_master_int: [ISPMADR]
+ 10010h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
base_addr_seg_0_MI_xmem_master_int								

Bit Range	Default & Access	Description
31:0	0h RW	base_addr_seg_0_MI_xmem_master_int: Base address for segment 0 of master interface xmem_master_int

15.8.91 reg_scp_base_addr_seg_0_MI_config_ilm_conf_ilm_master_type
(scp_base_addr_seg_0_MI_config_ilm_conf_ilm_master)—
Offset 10014h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

scp_base_addr_seg_0_MI_config_ilm_conf_ilm_master:
[ISPMMAADR] + 10014h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
base_addr_seg_0_M1_config_ilm_conf_ilm_master								



Bit Range	Default & Access	Description
31:0	0h RW	base_addr_seg_0_MI_config_ilm_conf_ilm_master: Base address for segment 0 of master interface config_ilm_conf_ilm_master

15.8.92 reg_scp_unused_6_type (scp_unused_6)—Offset 10018h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

scp_unused_6: [ISPMADDR] + 10018h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	unused_6: Unused

15.8.93 reg_scp_unused_7_type (scp_unused_7)—Offset 1001Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

scp_unused_7: [ISPMADDR] + 1001Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	unused_7: Unused

15.8.94 reg_scp_debug_pc_type (scp_debug_pc)—Offset 10024h

Access Method



Default: 00000000h

[illegible]



Bit Range	Default & Access	Description
31:0	0h RW	unused_11: Unused

15.8.97 reg_scp_pmem_slave_access_type (scp_pmem_slave_access)—Offset 10030h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

scp_pmem_slave_access: [ISPMMAADR] + 10030h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	pmem_slave_access: Pmem slave access flag

15.8.98 reg_isp_stat_and_ctrl_type (isp_stat_and_ctrl)—Offset 20000h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_stat_and_ctrl: [ISPMMAADR] + 20000h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 000000A0h



Bit Range	Default & Access	Description
4	0h RO	broken_flag: Broken flag
3	0h RW	run_flag: Run flag
2	0h RW	break_flag: Break flag
1	0h WO	start_flag: Start flag
0	0h WO	reset_flag: Reset flag

15.8.99 reg_isp_base_address_type (isp_base_address)—Offset 20004h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_base_address: [ISPMADDR] + 20004h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	base_address: Start address

15.8.100 reg_isp_unused_2_type (isp_unused_2)—Offset 20008h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


isp_unused_2: [ISPMADDR] + 20008h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_base_addr_seg_0_MI_base_config_mem_master:
[ISPMADR] + 20010h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0

base_addr_seg_0_MI_base_config_mem_master

Bit Range	Default & Access	Description
31:0	0h RW	base_addr_seg_0_MI_base_config_mem_master: Base address for segment 0 of master interface base_config_mem_master

15.8.102 reg_isp_unused_5_type (isp_unused_5)—Offset 20014h

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_unused_5: [ISPMMADR] + 20014h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_stall_stat_base_config_mem_iam_op0				stall_stat_simd_histogram_loc_mt_am_inst_6_op0				
				stall_stat_simd_vamem3_loc_mt_am_inst_5_op0				
				stall_stat_simd_vamem2_loc_mt_am_inst_4_op0				
				stall_stat_simd_vamem1_loc_mt_am_inst_3_op0				
				stall_stat_simd_vmem_loc_mt_am_inst_2_op0				
				stall_stat_base_fifo_loc_mt_am_inst_1_op6				
				stall_stat_base_fifo_loc_mt_am_inst_1_op5				
				stall_stat_base_fifo_loc_mt_am_inst_1_op4				
				stall_stat_base_fifo_loc_mt_am_inst_1_op3				
				stall_stat_base_fifo_loc_mt_am_inst_1_op2				
				stall_stat_base_fifo_loc_mt_am_inst_1_op1				
				stall_stat_base_fifo_loc_mt_am_inst_1_op0				
				stall_stat_base_dmem_loc_mt_am_inst_0_op0				
				stall_stat_base_config_mem_iam_op1				
				stall_stat_base_config_mem_iam_op0				

Bit Range	Default & Access	Description
31:15	0h RW	unused_stall_stat_base_config_mem_iam_op0: Unused
14	0h RO	stall_stat_simd_histogram_loc_mt_am_inst_6_op0: Stalling flag for msink simd_histogram_loc_mt_am_inst_6_op0
13	0h RO	stall_stat_simd_vamem3_loc_mt_am_inst_5_op0: Stalling flag for msink simd_vamem3_loc_mt_am_inst_5_op0
12	0h RO	stall_stat_simd_vamem2_loc_mt_am_inst_4_op0: Stalling flag for msink simd_vamem2_loc_mt_am_inst_4_op0
11	0h RO	stall_stat_simd_vamem1_loc_mt_am_inst_3_op0: Stalling flag for msink simd_vamem1_loc_mt_am_inst_3_op0
10	0h RO	stall_stat_simd_vmem_loc_mt_am_inst_2_op0: Stalling flag for msink simd_vmem_loc_mt_am_inst_2_op0
9	0h RO	stall_stat_base_fifo_loc_mt_am_inst_1_op6: Stalling flag for msink base_fifo_loc_mt_am_inst_1_op6
8	0h RO	stall_stat_base_fifo_loc_mt_am_inst_1_op5: Stalling flag for msink base_fifo_loc_mt_am_inst_1_op5
7	0h RO	stall_stat_base_fifo_loc_mt_am_inst_1_op4: Stalling flag for msink base_fifo_loc_mt_am_inst_1_op4
6	0h RO	stall_stat_base_fifo_loc_mt_am_inst_1_op3: Stalling flag for msink base_fifo_loc_mt_am_inst_1_op3
5	0h RO	stall_stat_base_fifo_loc_mt_am_inst_1_op2: Stalling flag for msink base_fifo_loc_mt_am_inst_1_op2
4	0h RO	stall_stat_base_fifo_loc_mt_am_inst_1_op1: Stalling flag for msink base_fifo_loc_mt_am_inst_1_op1
3	0h RO	stall_stat_base_fifo_loc_mt_am_inst_1_op0: Stalling flag for msink base_fifo_loc_mt_am_inst_1_op0
2	0h RO	stall_stat_base_dmem_loc_mt_am_inst_0_op0: Stalling flag for msink base_dmem_loc_mt_am_inst_0_op0



Bit Range	Default & Access	Description
1	0h RO	stall_stat_base_config_mem_iam_op1 : Stalling flag for msink base_config_mem_iam_op1
0	0h RO	stall_stat_base_config_mem_iam_op0 : Stalling flag for msink base_config_mem_iam_op0

15.8.105 reg_isp_unused_9_type (isp_unused_9)—Offset 20024h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_unused_9: [ISPMMAADR] + 20024h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	unused_9 : Unused

15.8.106 reg_isp_pmem_slave_access_type (isp_pmem_slave_access)—Offset 20028h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_pmem_slave_access: [ISPMMAADR] + 20028h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

15.8.107 reg_ifmt_ift_prim_IF_sw_rst_type (ifmt_ift_prim_IF_sw_rst)–Offset 30000h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_sw_rst: [ISPMADR] + 30000h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
				unused_IF_sw_rst					IF_sw_rst

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_sw_rst: Unused
0	0h RW	IF_sw_rst: Software Reset

15.8.108 reg_ifmt_ift_prim_IF_start_line_type (ifmt_ift_prim_IF_start_line)—Offset 30004h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_start_line: [ISPMMADR] + 30004h**ISPMADR Type:** PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_start_line					IF_start_line			



Bit Range	Default & Access	Description
31:16	0h RW	unused_IF_start_line: Unused
15:0	0h RW	IF_start_line: Start line: number of line to skip before passing the 1st line

15.8.109 reg_ifmt_ift_prim_IF_start_column_type
(ifmt ift prim IF start column)—Offset 30008h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_start_column: [ISPMADR] + 30008h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_start_column					IF_start_column			

Bit Range	Default & Access	Description
31:16	0h RW	unused_IF_start_column: Unused
15:0	0h RW	IF_start_column: Start column: number pixel component to skip before passing the 1st of a line

15.8.110 reg_ifmt_ift_prim_IF_Cropped_height_type (ifmt ift prim IF Cropped height)—Offset 3000Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift_prim IF_Cropped_height: [ISPMMADR] + 3000Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_Cropped_width: [ISPMADR] + 30010h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_Cropped_width					IF_Cropped_width			

Intel Atom® Processor E3800 Product Family
Datasheet
1200



15.8.112 reg_ifmt_ift_prim_IF_Vert_Decim_type (ifmt_ift_prim_IF_Vert_Decim)—Offset 30014h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_Vert_Decim: [ISPMMAADR] + 30014h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_Vert_Decim						IF_Vert_Decim		

Bit Range	Default & Access	Description
31:12	0h RW	unused_IF_Vert_Decim: Unused
11:0	0h RW	IF_Vert_Decim: Vertical decimation factor

15.8.113 reg_ifmt_ift_prim_IF_Horiz_Decim_type (ifmt_ift_prim_IF_Horiz_Decim)—Offset 30018h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_Horiz_Decim: [ISPMMAADR] + 30018h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_Horiz_Decim						IF_Horiz_Decim		

15.8.114 reg_ifmt_ift_prim_IF_Horiz_Deinter_type
(ifmt_ift_prim_IF_Horiz_Deinter)—Offset 3001Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_Horiz_Deinter: [ISPMADR] + 3001Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
unused_IF_Horiz_Deinter									1F_Horiz_Deinter

Bit Range	Default & Access	Description
31:3	0h RW	unused_IF_Horiz_Deinter: Unused
2:0	0h RW	IF_Horiz_Deinter: Horizontal deinterleaving factor

15.8.115 reg_ifmt_ift_prim_IF_Left_Pad_type
(ifmt_ift_prim_IF_Left_Pad)—Offset 30020h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_Left_Pad: [ISPMADR] + 30020h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_EOF_Offset: [ISPMMAADR] + 30024h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_EOF_Offset				IF_EOF_Offset				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_EOF_Offset: Unused
23:0	0h RW	IF_EOF_Offset: End of line offset in bytes: number of bytes to add at the address at the end of a line

15.8.117 reg_ifmt_ift_prim_IF_Start_addr_type
(ifmt_ift_prim_IF_Start_addr)—Offset 30028h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_Start_addr: [ISPMADDR] + 30028h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_Start_addr				IF_Start_addr				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_Start_addr: Unused
23:0	0h RW	IF_Start_addr: Start address in bytes: memory buffer start address

15.8.118 reg_ifmt_ift_prim_IF_End_addr_type (ifmt_ift_prim_IF_End_addr)—Offset 3002Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_End_addr: [ISPMADDR] + 3002Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_End_addr				IF_End_addr				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_End_addr: Unused
23:0	0h RW	IF_End_addr: End address in bytes: memory buffer end address



15.8.119 reg_ifmt_ift_prim_IF_incr_type (ifmt_ift_prim_IF_incr)—Offset 30030h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_incr: [ISPMMAADR] + 30030h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_incr				IF_incr				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_incr: Unused
23:0	0h RW	IF_incr: Word increment in memory word: word increment value after writting each word

15.8.120 reg_ifmt_ift_prim_IF_YUV_420_format_type (ifmt_ift_prim_IF_YUV_420_format)—Offset 30034h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_YUV_420_format: [ISPMMAADR] + 30034h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
				unused_IF_YUV_420_format				IF_YUV_420_format



Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_Vsynch_active_low: Unused
0	0h RW	IF_Vsynch_active_low: Vertical synch active low: set to 1 if Vsynch and EndOffFrame are active low

15.8.122 reg_ifmt_ift_prim_IF_Hsynch_active_low_type
(ifmt ift_prim IF Hsynch active low)—Offset 3003Ch



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_ReEnable								
IF_ReEnable								

Intel Atom® Processor E3800 Product Family
Datasheet
1207



Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_block_input: [ISPMMAADR] + 30044h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_block_input								IF_block_input

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_block_input: Unused
0	0h RW	IF_block_input: Block input when no req: set to 1 to block data streaming input when no request is received

15.8.125 reg_ifmt_ift_prim_IF_Vert_Deinter_type (ifmt_ift_prim_IF_Vert_Deinter)—Offset 30048h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_Vert_Deinter: [ISPMMAADR] + 30048h


ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_Vert_Deinter								IF_Vert_Deinter

Bit Range	Default & Access	Description
31:3	0h RW	unused_IF_Vert_Deinter: Unused
2:0	0h RW	IF_Vert_Deinter: Vertical deinterleaving factor



Bit Range	Default & Access	Description
31:16	0h RW	unused_FSM_Sync_counter: Unused
15:0	0h RO	FSM_Sync_counter: FSM Sync counter: counts the pixel components of the request being served (starting from value 1)

15.8.128 reg_ifmt_ift_prim_FSM_Crop_status_type (ifmt_ift_prim_FSM_Crop_status)—Offset 30108h

FSM Crop status

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_FSM_Crop_status: [ISPMMAADR] + 30108h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:4	0h RW	unused_FSM_Crop_status: Unused
3	0h RO	FSM_Crop_error: Error flag: when set in combination with: Crop Line state unexpected vsynch or eof has been received; Req. Lines state unexpected vsynch or eof has been received; Req. Vectors state unexpected vsynch or eof has been received; another state an illegal state transition has occurred.



Bit Range	Default & Access	Description
2:0	0h RO	FSM_Crop_State: FSM State: State: 0)Idle -- 1)Wait Line -- 2)Crop Line -- 3)Crop Pixel -- 4)Pass pixel -- 5) Pass Line

15.8.129 reg_ifmt_ift_prim_FSM_Crop_line_counter_type
(ifmt_ift_prim_FSM_Crop_line_counter)—Offset 3010Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_FSM_Crop_line_counter: [ISPMADR] + 3010Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_FSM_Crop_line_counter				FSM_Crop_line_counter				

Bit Range	Default & Access	Description
31:15	0h RW	unused_FSM_Crop_line_counter: Unused
14:0	0h RO	FSM_Crop_line_counter: FSM Crop line counter

15.8.130 `reg_ifmt_ift_prim_FSM_Crop_pixel_counter_type`
(`ifmt_ift_prim_FSM_Crop_pixel_counter`)—Offset 30110h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_FSM_Crop_pixel_counter: [ISPMADR] + 30110h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								FSM_Deinterl_idx_buffer

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
1:0	0h RO	FSM_Deinterl_idx_buffer: FSM Deinterleaving idx buffer

15.8.132 reg_ifmt_ift_prim_FSM_Horiz_Decim_cnt_type
(ifmt_ift_prim_FSM_Horiz_Decim_cnt)—Offset 30118h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift prim FSM Horiz Decim cnt: [ISPMADR] + 30118h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_FSM_Horiz_Decim_cnt						FSM_Horiz_Decim_cnt		

Bit Range	Default & Access	Description
31:12	0h RW	unused_FSM_Horiz-Decim_cnt: Unused
11:0	0h RO	FSM_Horiz-Decim_cnt: FSM Horizontal Decimation counter

15.8.133 reg_ifmt_ift_prim_FSM_Vertic_Decim_cnt_type
(ifmt_ift_prim_FSM_Vertic_Decim_cnt)—Offset 3011Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_FSM_Vertic_Decim_cnt: [ISPMADR] + 3011Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	FSM_Vertic_Block_Decim_cnt
unused_FSM_Vertic_Block_Decim_cnt									

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
1:0	0h RO	FSM_Vertic_Block_Decim_cnt : FSM Vertical block decimation counter

15.8.135 reg_ifmt_ift_prim_IF_FSM_Padding_status_type
(ifmt_ift_prim_IF_FSM_Padding_status)—Offset 30124h

FSM Padding status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_FSM_Padding_status: [ISPMADR] + 30124h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:4	0h RW	unused_IF_FSM_Padding_status: Unused
3	0h RO	FSM_Padding_error: Error flag: when set in combination with: Left Padding state an unexpected vsynch or hsync has been received; Write state an unexpected vsynch or hsync has been received; Right padding state unexpected vsynch has been received; Send EOL state an unexpected vsynch has been received; another state an illegal state transition has occurred.
2:0	0h RO	FSM_Padding_State: FSM State: State: 0)Idle -- 1)Left Padding -- 2)Write -- 3)Right padding -- 4)Sending EOL

15.8.136 reg_ifmt_ift_prim_IF_FSM_Padding_elem_idx_type
(ifmt_ift_prim_IF_FSM_Padding_elem_idx)—Offset 30128h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_FSM_Padding_elem_idx: [ISPMADR] + 30128h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_FSM_Vec_Sup: [ISPMADR] + 3012Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
				unused_IF_FSM_Vec_Sup					IF_FSM_Vec_Sup

Intel Atom® Processor E3800 Product Family
Datasheet
1216



15.8.138 reg_ifmt_ift_prim_IF_FSM_Vec_Sup_Buf_full_type (ifmt_ift_prim_IF_FSM_Vec_Sup_Buf_full)—Offset 30130h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_FSM_Vec_Sup_Buf_full: [ISPMMAADR] + 30130h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_FSM_Vec_Sup_Buf_full								IF_FSM_Vec_Sup_Buf_full

Bit Range	Default & Access	Description
31:3	0h RW	unused_IF_FSM_Vec_Sup_Buf_full: Unused
2:0	0h RO	IF_FSM_Vec_Sup_Buf_full: FSM Vector support buf full: one-hot encoding flag signaling that the correspondent buffer is full

15.8.139 reg_ifmt_ift_prim_IF_FSM_Vec_Sup_rd_accept_type (ifmt_ift_prim_IF_FSM_Vec_Sup_rd_accept)—Offset 30134h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_FSM_Vec_Sup_rd_accept: [ISPMMAADR] + 30134h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_IF_FSM_Vec_Sup_rd_accept								IF_FSM_Vec_Sup_rd_accept

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_FSM_Vec_Sup_rd_accept: Unused
0	1h RO	IF_FSM_Vec_Sup_rd_accept: FSM Vector Support fifo rd accept flag

15.8.140 reg_ifmt_ift_prim_IF_Pixel_Fifo_status_type (ifmt_ift_prim_IF_Pixel_Fifo_status)—Offset 30138h

Pixel Fifo status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_IF_Pixel_Fifo_status: [ISPMADDR] + 30138h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_IF_Pixel_Fifo_status								Pixel_Fifo_rd_valid
								Pixel_Fifo_rd_accept
								Pixel_Fifo_wr_valid
								Pixel_Fifo_wr_accept

Bit Range	Default & Access	Description
31:4	0h RW	unused_IF_Pixel_Fifo_status: Unused

15.8.141 **reg_ifmt_ift_prim_b_IF_sw_rst_type**
(ifmt_ift_prim_b_IF_sw_rst)—Offset 30200h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)
ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_start_column				IF_start_column				

Bit Range	Default & Access	Description
31:16	0h RW	unused_IF_start_column: Unused
15:0	0h RW	IF_start_column: Start column: number pixel component to skip before passing the 1st of a line

15.8.144 reg_ifmt_ift_prim_b_IF_Cropped_height_type
(ifmt ift_prim_b IF_Cropped_height)—Offset 3020Ch

Intel Atom® Processor E3800 Product Family
Datasheet
1220

15.8.146 **reg_ifmt_ift_prim_b_IF_Vert_Decim_type**
(ifmt_ift_prim_b_IF_Vert_Decim)—Offset 30214h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift prim b IF Vert Decim: [ISPMADR] + 30214h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_Vert_Decim						IF_Vert_Decim		

Bit Range	Default & Access	Description
31:12	0h RW	unused_IF_Vert_Decim: Unused
11:0	0h RW	IF_Vert_Decim: Vertical decimation factor

15.8.147 reg_ifmt_ift_prim_b_IF_Horiz-Decim_type
(ifmt_ift_prim_b_IF_Horiz-Decim)—Offset 30218h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift prim b IF Horiz Decim: [ISPMMADR] + 30218h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
unused_IF_Horiz_Deinter									IF_Horiz_Deinter

Bit Range	Default & Access	Description
31:3	0h RW	unused_IF_Horiz_Deinter: Unused
2:0	0h RW	IF_Horiz_Deinter: Horizontal deinterleaving factor

15.8.149 **reg_ifmt_ift_prim_b_IF_Left_Pad_type**
(ifmt_ift_prim_b_IF_Left_Pad)—Offset 30220h

Intel Atom® Processor E3800 Product Family
Datasheet
1223



Bit Range	Default & Access	Description
31:6	0h RW	unused_IF_Left_Pad: Unused
5:0	0h RW	IF_Left_Pad: Left padding: pizel component to be padded at the beggining of each line

15.8.150 `reg_ifmt_ift_prim_b_IF_EOF_Offset_type`
(`ifmt_ift_prim_b_IF_EOF_Offset`)—Offset 30224h

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_EOF_Offset: Unused
23:0	0h RW	IF_EOF_Offset: End of line offset in bytes: number of bytes to add at the address at the end of a line



15.8.151 reg_ifmt_ift_prim_b_IF_Start_addr_type (ifmt_ift_prim_b_IF_Start_addr)—Offset 30228h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_IF_Start_addr: [ISPMMAADR] + 30228h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_Start_addr				IF_Start_addr				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_Start_addr: Unused
23:0	0h RW	IF_Start_addr: Start address in bytes: memory buffer start address

15.8.152 reg_ifmt_ift_prim_b_IF_End_addr_type (ifmt_ift_prim_b_IF_End_addr)—Offset 3022Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_IF_End_addr: [ISPMMAADR] + 3022Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_End_addr				IF_End_addr				



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_incr				IF_incr				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_incr: Unused
23:0	0h RW	IF_incr: Word increment in memory word: word increment value after writting each word

15.8.154 `reg_ifmt_ift_prim_b_IF_YUV_420_format_type`
(ifmt ift prim b IF YUV 420 format)—Offset 30234h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

15.8.155 reg_ifmt_ift_prim_b_IF_Vsynch_active_low_type
(ifmt_ift_prim_b_IF_Vsynch_active_low)—Offset 30238h



Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_Hsynch_active_low: Unused
0	0h RW	IF_Hsynch_active_low: Horizontal synch active low: set to 1 if Hsynch and EndOfLine are active low

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_ReEnable								IF_ReEnable



Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_ReEnable: Unused
0	0h RW	IF_ReEnable: Re-enable status update: set to 1 to re-enable status update after an error situation

15.8.158 `reg_ifmt_ift_prim_b_IF_block_input_type`
(ifmt ift_prim b_IF_block_input)—Offset 30244h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_IF_block_input: [ISPMADR] + 30244h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_block_input				IF_block_input				

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_block_input: Unused
0	0h RW	IF_block_input: Block input when no req: set to 1 to block data streaming input when no request is received

15.8.159 reg_ifmt_ift_prim_b_IF_Vert_Deinter_type
(ifmt_ift_prim_b_IF_Vert_Deinter)—Offset 30248h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_IF_Vert_Deinter: [ISPMADR] + 30248h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Access Method

ifmt_ift_prim_b_IF_FSM_Sync_status: [ISPMMAADR] + 30300h

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:4	0h RW	unused_IF_FSM_Sync_status: Unused
3	0h RO	FSM_Sync_error: Error flag: when set in combination with: Idle state an unknown command has been received; Req. Lines state an unexpected vsynch or eof has been received; Req. Vectors state an unexpected vsynch or eof has been received; another state an illegal state transition has occurred.



Bit Range	Default & Access	Description
2:0	0h RO	FSM_Sync_State: FSM State: State: 0)Idle -- 1)Req Frame -- 2)Req. Lines -- 3)Req. Vectors -- 4)Send Acknowledge

15.8.161 reg_ifmt_ift_prim_b_FSM_Sync_counter_type
(ifmt ift prim b FSM Sync counter)—Offset 30304h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift prim b FSM Sync counter: [ISPMMAADR] + 30304h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_FSM_Sync_counter				FSM_Sync_counter				

Bit Range	Default & Access	Description
31:16	0h RW	unused_FSM_Sync_counter: Unused
15:0	0h RO	FSM_Sync_counter: FSM Sync counter: counts the pixel components of the request being served (starting from value 1)

15.8.162 reg_ifmt_ift_prim_b_FSM_Crop_status_type
(ifmt_ift_prim_b_FSM_Crop_status)—Offset 30308h

FSM Crop status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift prim b FSM_Crop_status: [ISPMADR] + 30308h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_FSM_Crop_line_counter				FSM_Crop_line_counter				

Bit Range	Default & Access	Description
31:15	0h RW	unused_FSM_Crop_line_counter: Unused



Bit Range	Default & Access	Description
14:0	0h RO	FSM_Crop_line_counter: FSM Crop line counter

15.8.164 reg_ifmt_ift_prim_b_FSM_Crop_pixel_counter_type
(ifmt ift_prim_b FSM_Crop_pixel_counter)—Offset 30310h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_FSM_Crop_pixel_counter: [ISPMADR] + 30310h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_FSM_Crop_pixel_counter					FSM_Crop_pixel_counter			

Bit Range	Default & Access	Description
31:16	0h RW	unused_FSM_Crop_pixel_counter: Unused
15:0	0h RO	FSM_Crop_pixel_counter: FSM Crop pixel component counter

15.8.165 reg_ifmt_ift_prim_b_FSM_Deinterl_idx_buffer_type
(ifmt ift prim b FSM Deinterl idx buffer)—Offset 30314h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_FSM_Deinterl_idx_buffer: [ISPMADR] + 30314h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:2	0h RW	unused_FSM_Deinterl_idx_buffer: Unused
1:0	0h RO	FSM_Deinterl_idx_buffer: FSM Deinterleaving idx buffer

15.8.166 reg_ifmt_ift_prim_b_FSM_Horiz_Decim_cnt_type (ifmt_ift_prim_b_FSM_Horiz_Decim_cnt)—Offset 30318h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_FSM_Horiz_Decim_cnt: [ISPMADDR] + 30318h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:12	0h RW	unused_FSM_Horiz_Decim_cnt: Unused
11:0	0h RO	FSM_Horiz_Decim_cnt: FSM Horizontal Decimation counter



15.8.167 reg_ifmt_ift_prim_b_FSM_Vertic_Decim_cnt_type (ifmt_ift_prim_b_FSM_Vertic_Decim_cnt)—Offset 3031Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_FSM_Vertic_Decim_cnt: [ISPMMAADR] + 3031Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_FSM_Vertic_Decim_cnt						FSM_Vertic_Decim_cnt		

Bit Range	Default & Access	Description
31:12	0h RW	unused_FSM_Vertic_Decim_cnt: Unused
11:0	0h RO	FSM_Vertic_Decim_cnt: FSM Vertical decimation counter

15.8.168 reg_ifmt_ift_prim_b_FSM_Vertic_Block_Decim_cnt_type (ifmt_ift_prim_b_FSM_Vertic_Block_Decim_cnt)—Offset 30320h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_FSM_Vertic_Block_Decim_cnt: [ISPMMAADR] + 30320h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Access Method

ifmt_ift_prim_b_IF_FSM_Padding_status: [ISPMADR] + 30324h

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
unused_IF_FSM_Padding_status									FSM_Padding_error
									FSM_Padding_State



Bit Range	Default & Access	Description
31:4	0h RW	unused_IF_FSM_Padding_status: Unused
3	0h RO	FSM_Padding_error: Error flag: when set in combination with: Left Padding state an unexpected vsynch or hsync has been received; Write state an unexpected vsynch or hsync has been received; Right padding state unexpected vsynch has been received; Send EOL state an unexpected vsynch has been received; another state an illegal state transition has occurred.
2:0	0h RO	FSM_Padding_State: FSM State: State: 0)Idle -- 1)Left Padding -- 2)Write -- 3)Right padding -- 4)Sending EOL

15.8.170 `reg_ifmt_ift_prim_b_IF_FSM_Padding_elem_idx_type`
(ifmt ift prim b IF FSM Padding elem idx)—Offset 30328h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
ifmt_ift_prim_b_IF_FSM_Padding_elem_idx: [ISPMADR] +
30328h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_FSM_Padding_elem_idx								IF_FSM_Padding_elem_idx

Bit Range	Default & Access	Description
31:6	0h RW	unused_IF_FSM_Padding_elem_idx: Unused
5:0	0h RO	IF_FSM_Padding_elem_idx: FSM Padding element index counter

15.8.171 reg_ifmt_ift_prim_b_IF_FSM_Vec_Sup_type
(ifmt ift prim b IF FSM Vec Sup)—Offset 3032Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift prim b IF FSM Vec Sup: [ISPMMADR] + 3032Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h



Type: Memory Mapped I/O Register (Size: 32 bits)

ifmt_ift_prim_b_IF_FSM_Vec_Sup_Buf_full: [ISPMMAADR] + 30330h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								IF_FSM_Vec_Sup_Buf_full
unused_IF_FSM_Vec_Sup_Buf_full								

Bit Range	Default & Access	Description
31:3	0h RW	unused_IF_FSM_Vec_Sup_Buf_full: Unused
2:0	0h RO	IF_FSM_Vec_Sup_Buf_full: FSM Vector support buf full: one-hot encoding flag signaling that the correspondent buffer is full



15.8.173 reg_ifmt_ift_prim_b_IF_FSM_Vec_Sup_rd_accept_type (ifmt_ift_prim_b_IF_FSM_Vec_Sup_rd_accept)—Offset 30334h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_IF_FSM_Vec_Sup_rd_accept: [ISPMMAADR]
+ 30334h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_IF_FSM_Vec_Sup_rd_accept								IF_FSM_Vec_Sup_rd_accept

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_FSM_Vec_Sup_rd_accept: Unused
0	1h RO	IF_FSM_Vec_Sup_rd_accept: FSM Vector Support fifo rd accept flag

15.8.174 reg_ifmt_ift_prim_b_IF_Pixel_Fifo_status_type (ifmt_ift_prim_b_IF_Pixel_Fifo_status)—Offset 30338h

Pixel Fifo status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_prim_b_IF_Pixel_Fifo_status: [ISPMMAADR] +
30338h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_IF_Pixel_Fifo_status								Pixel_Fifo_rd_valid
								Pixel_Fifo_rd_accept
								Pixel_Fifo_wr_valid
								Pixel_Fifo_wr_accept

Bit Range	Default & Access	Description
31:4	0h RW	unused_IF_Pixel_Fifo_status: Unused
3	0h RO	Pixel_Fifo_rd_valid: Fifo has an element to be read
2	0h RO	Pixel_Fifo_rd_accept: IF accepts Pixel(s)
1	0h RO	Pixel_Fifo_wr_valid: There is an element to write into the Fifo
0	1h RO	Pixel_Fifo_wr_accept: Fifo is not full(1), Fifo is Full(0)

15.8.175 reg_ifmt_ift_sec_IF_sw_rst_type (ifmt_ift_sec_IF_sw_rst)—Offset 30400h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_sw_rst: [ISPMADDR] + 30400h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_sw_rst								IF_sw_rst

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_sw_rst: Unused



Bit Range	Default & Access	Description
0	0h RW	IF_sw_rst: Software Reset

15.8.176 reg_ifmt_ift_sec_IF_start_line_type
(ifmt ift sec IF start line)—Offset 30404h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_start_line: [ISPMADR] + 30404h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_start_line					IF_start_line			

Bit Range	Default & Access	Description
31:16	0h RW	unused_IF_start_line: Unused
15:0	0h RW	IF_start_line: Start line: number of line to skip before passing the 1st line

15.8.177 `reg_ifmt_ift_sec_IF_start_column_type`
(ifmt ift sec IF start column)—Offset 30408h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_start_column: [ISPMADR] + 30408h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	unused_IF_start_column: Unused
15:0	0h RW	IF_start_column: Start column: number pixel component to skip before passing the 1st of a line

15.8.178 reg_ifmt_ift_sec_IF_Cropped_height_type (ifmt_ift_sec_IF_Cropped_height)—Offset 3040Ch

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_Cropped_height: [ISPMADDR] + 3040Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	unused_IF_Cropped_height: Unused
15:0	0h RW	IF_Cropped_height: Cropped height: number of lines of the cropped image



15.8.179 reg_ifmt_ift_sec_IF_Cropped_width_type (ifmt_ift_sec_IF_Cropped_width)—Offset 30410h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_Cropped_width: [ISPMMAADR] + 30410h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_Cropped_width				IF_Cropped_width				

Bit Range	Default & Access	Description
31:16	0h RW	unused_IF_Cropped_width: Unused
15:0	0h RW	IF_Cropped_width: Cropped width: number of pixel component of the cropped image

15.8.180 reg_ifmt_ift_sec_IF_Vert-Decim_type (ifmt_ift_sec_IF_Vert-Decim)—Offset 30414h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_Vert-Decim: [ISPMMAADR] + 30414h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_Vert-Decim				IF_Vert-Decim				



Bit Range	Default & Access	Description
31:12	0h RW	unused_IF_Horiz_Decim: Unused
11:0	0h RW	IF_Horiz_Decim: Horizontal decimation factor

15.8.183 reg_ifmt_ift_sec_IF_Left_Pad_type
(ifmt ift sec IF Left Pad)—Offset 30420h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift sec IF Left Pad: [ISPMADDR] + 30420h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_Left_Pad								IF_Left_Pad

Bit Range	Default & Access	Description
31:6	0h RW	unused_IF_Left_Pad: Unused
5:0	0h RW	IF_Left_Pad: Left padding: pizel component to be padded at the beggining of each line

15.8.184 **reg_ifmt_ift_sec_IF_EOF_Offset_type**
(ifmt ift sec IF_EOF_Offset)—Offset 30424h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_EOF_Offset: [ISPMADDR] + 30424h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_EOF_Offset				IF_EOF_Offset				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_EOF_Offset: Unused
23:0	0h RW	IF_EOF_Offset: End of line offset in bytes: number of bytes to add at the address at the end of a line

15.8.185 reg_ifmt_ift_sec_IF_Start_addr_type (ifmt_ift_sec_IF_Start_addr)—Offset 30428h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_Start_addr: [ISPMADDR] + 30428h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_Start_addr				IF_Start_addr				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_Start_addr: Unused
23:0	0h RW	IF_Start_addr: Start address in bytes: memory buffer start address



15.8.186 reg_ifmt_ift_sec_IF_End_addr_type (ifmt_ift_sec_IF_End_addr)—Offset 3042Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_End_addr: [ISPMADDR] + 3042Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_End_addr				IF_End_addr				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_End_addr: Unused
23:0	0h RW	IF_End_addr: End address in bytes: memory buffer end address

15.8.187 reg_ifmt_ift_sec_IF_incr_type (ifmt_ift_sec_IF_incr)—Offset 30430h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_incr: [ISPMADDR] + 30430h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_IF_incr				IF_incr				

Bit Range	Default & Access	Description
31:24	0h RW	unused_IF_incr: Unused

15.8.188 `reg_ifmt_ift_sec_IF_YUV_420_format_type`
(`ifmt ift sec IF YUV 420 format`)—Offset 30434h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift sec IF YUV 420 format: [ISPMADR] + 30434h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_YUV_420_format: Unused
0	0h RW	IF_YUV_420_format: YUV 420 format: set to work on legacy format YUV420

15.8.189 reg_ifmt_ift_sec_IF_Vsynch_active_low_type
(ifmt ift_sec_IF_Vsynch_active_low)—Offset 30438h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_Vsynch_active_low: [ISPMADR] + 30438h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
unused_IF_Hsynch_active_low IF_Hsynch_active_low									

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_Hsynch_active_low: Unused
0	0h RW	IF_Hsynch_active_low: Horizontal synch active low: set to 1 if Hsynch and EndOfLine are active low



Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_ReEnable: Unused
0	0h RW	IF_ReEnable: Re-enable status update: set to 1 to re-enable status update after an error situation

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_block_input								
IF_block_input								



Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_block_input: Unused
0	0h RW	IF_block_input: Block input when no req: set to 1 to block data streaming input when no request is received

15.8.193 `reg_ifmt_ift_sec_IF_Vert_Deinter_type`
(`ifmt_ift_sec_IF_Vert_Deinter`)—Offset 30448h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt ift sec IF Vert Deinter: [ISPMADR] + 30448h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
IF_Vert_Deinter unused_IF_Vert_Deinter									IF_Vert_Deinter

Bit Range	Default & Access	Description
31:3	0h RW	unused_IF_Vert_Deinter: Unused
2:0	0h RW	IF_Vert_Deinter: Vertical deinterleaving factor

15.8.194 reg_ifmt_ift_sec_IF_FSM_Sync_status_type
(ifmt ift sec IF FSM Sync status)—Offset 30500h

FSM Sync status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_FSM_Sync_status: [ISPMMA DR] + 30500h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)
ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_FSM_Sync_counter					FSM_Sync_counter			

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_FSM_Crop_pixel_counter: [ISPMADR] + 30510h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_FSM_Crop_pixel_counter				FSM_Crop_pixel_counter				

Intel Atom® Processor E3800 Product Family
Datasheet
1254



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_FSM_Vertic_Decim_cnt						FSM_Vertic_Decim_cnt		

October 2018
Document Number: 538136, Rev. 4.3



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								IF_FSM_Padding_elem_idx



Bit Range	Default & Access	Description
31:6	0h RW	unused_IF_FSM_Padding_elem_idx: Unused
5:0	0h RO	IF_FSM_Padding_elem_idx: FSM Padding element index counter

15.8.205 **reg_ifmt_ift_sec_IF_FSM_Vec_Sup_type**
(ifmt ift_sec_IF_FSM_Vec_Sup)—Offset 3052Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_FSM_Vec_Sup: [ISPMADR] + 3052Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	TF_FSM_Vec_Sup
									TF_FSM_Vec_Sup

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_FSM_Vec_Sup: Unused
0	0h RO	IF_FSM_Vec_Sup: FSM Vector support error state: if set the FSM Vector support is in error state

15.8.206 `reg_ifmt_ift_sec_IF_FSM_Vec_Sup_Buf_full_type`
(`ifmt_ift_sec_IF_FSM_Vec_Sup_Buf_full`)—Offset 30530h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_FSM_Vec_Sup_Buf_full: [ISPMADR] + 30530h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IF_FSM_Vec_Sup_Buf_full								IF_FSM_Vec_Sup_Buf_full

Bit Range	Default & Access	Description
31:3	0h RW	unused_IF_FSM_Vec_Sup_Buf_full: Unused
2:0	0h RO	IF_FSM_Vec_Sup_Buf_full: FSM Vector support buf full: one-hot encoding flag signaling that the correspondent buffer is full

15.8.207 reg_ifmt_ift_sec_IF_FSM_Vec_Sup_rd_accept_type (ifmt_ift_sec_IF_FSM_Vec_Sup_rd_accept)—Offset 30534h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_FSM_Vec_Sup_rd_accept: [ISPMADDR] + 30534h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_IF_FSM_Vec_Sup_rd_accept								IF_FSM_Vec_Sup_rd_accept

Bit Range	Default & Access	Description
31:1	0h RW	unused_IF_FSM_Vec_Sup_rd_accept: Unused



Bit Range	Default & Access	Description
0	1h RO	IF_FSM_Vec_Sup_rd_accept: FSM Vector Support fifo rd accept flag

15.8.208 reg_ifmt_ift_sec_IF_Pixel_Fifo_status_type (ifmt_ift_sec_IF_Pixel_Fifo_status)—Offset 30538h

Pixel Fifo status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_ift_sec_IF_Pixel_Fifo_status: [ISPMADDR] + 30538h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_IF_Pixel_Fifo_status								Pixel_Fifo_rd_valid
								Pixel_Fifo_rd_accept
								Pixel_Fifo_wr_valid
								Pixel_Fifo_wr_accept

Bit Range	Default & Access	Description
31:4	0h RW	unused_IF_Pixel_Fifo_status: Unused
3	0h RO	Pixel_Fifo_rd_valid: Fifo has an element to be read
2	0h RO	Pixel_Fifo_rd_accept: IF accepts Pixel(s)
1	0h RO	Pixel_Fifo_wr_valid: There is an element to write into the Fifo
0	1h RO	Pixel_Fifo_wr_accept: Fifo is not full(1), Fifo is Full(0)

15.8.209 reg_ifmt_mem_cpy_MemCopy_sw_rst_type (ifmt_mem_cpy_MemCopy_sw_rst)—Offset 30600h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_mem_cpy_MemCopy_sw_rst: [ISPMADDR] + 30600h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h



Bit Range	Default & Access	Description
31:1	0h RW	unused_MemCopy_in_endian: Unused
0	0h RW	MemCopy_in_endian: Input endianness : set to 1 if input is big endian



15.8.211 reg_ifmt_mem_cpy_MemCopy_out_endian_type (ifmt_mem_cpy_MemCopy_out_endian)—Offset 30608h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_mem_cpy_MemCopy_out_endian: [ISPMMAADR] + 30608h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_MemCopy_out_endian								MemCopy_out_endian

Bit Range	Default & Access	Description
31:1	0h RW	unused_MemCopy_out_endian: Unused
0	0h RW	MemCopy_out_endian: Output endianness : set to 1 to deliver output input in big endian

15.8.212 reg_ifmt_mem_cpy_MemCopy_bit_swap_type (ifmt_mem_cpy_MemCopy_bit_swap)—Offset 3060Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_mem_cpy_MemCopy_bit_swap: [ISPMMAADR] + 3060Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





15.8.214 reg_ifmt_mem_cpy_MemCopy_packet_synch_type (ifmt_mem_cpy_MemCopy_packet_synch)—Offset 30614h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_mem_cpy_MemCopy_packet_synch: [ISPMADDR] + 30614h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_MemCopy_packet_synch								MemCopy_packet_synch

Bit Range	Default & Access	Description
31:1	0h RW	unused_MemCopy_packet_synch: Unused
0	0h RW	MemCopy_packet_synch: Packet synchronization pulse active low: set to 1 if start of packet and end of packet are active low

15.8.215 reg_ifmt_mem_cpy_MemCopy_rd_post_wr_sync_type (ifmt_mem_cpy_MemCopy_rd_post_wr_sync)—Offset 30618h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_mem_cpy_MemCopy_rd_post_wr_sync: [ISPMADDR] + 30618h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_MemCopy_dual_input				MemConv_dual_input				

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_mem_cpy_MemCopy_FSM_Sync_status: [ISPMADR] + 30704h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_MemCopy_FSM_Sync_status								
MemCopy_FSM_Sync_status								

Intel Atom® Processor E3800 Product Family
Datasheet
1268



Type: Memory Mapped I/O Register
(Size: 32 bits)

```
ifmt_mem_cpy_MemCopy_FSM_Pack_idx_cnt: [ISPMADR]
+ 30710h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_MemCopy_FSM_Pack_idx_cnt								
MemCopy_FSM_Pack_idx_cnt								



Bit Range	Default & Access	Description
31:2	0h RW	unused_MemCopy_FSM_Pack_idx_cnt: Unused
1:0	0h RO	MemCopy_FSM_Pack_idx_cnt: FSM Pack idx counter: element index

15.8.223 reg_ifmt_mem_cpy_MemCopy_FSM_Buf_Sup_status_type
(ifmt_mem_cpy_MemCopy_FSM_Buf_Sup_status)—Offset
30714h

Buffer Full and mask

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_mem_cpy_MemCopy_FSM_Buf_Sup_status:
[ISPMADR] + 30714h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h


Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
unused_MemCopy_FSM_Buf_Sup_status									field_mask
									field_full

Bit Range	Default & Access	Description
31:3	0h RW	unused_MemCopy_FSM_Buf_Sup_status: Unused
2	0h RO	field_mask: FSM Buffer support mask buffers full to the FSM CioWr
1:0	0h RO	field_full: FSM Buffer support one-hot encoding flagging when the buffer are full

15.8.224 reg_ifmt_mem_cpy_MemCopy_FSM_Buf_Sup_cnt_type
(ifmt_mem_cpy_MemCopy_FSM_Buf_Sup_cnt)—Offset 30718h

Access Method



15.8.226 reg_ifmt_mem_cpy_MemCopy_FSM_CioWr_addr_type
(ifmt_mem_cpy_MemCopy_FSM_CioWr_addr)—Offset 30720h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_mem_cpy_MemCopy_FSM_CioWr_addr: [ISPMADR] + 30720h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

15.8.228 reg_ifmt_gp_reg_IFMT_input_switch_lut_reg1_type
(ifmt_gp_reg_IFMT_input_switch_lut_reg1)—Offset 30804h

Intel Atom® Processor E3800 Product Family
Datasheet
1274



ifmt_gp_reg_IFMT_input_switch_lut_reg1: [ISPMADR] + 30804h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
IFMT_input_switch_lut_reg1								

Bit Range	Default & Access	Description
31:0	0h RW	IFMT_input_switch_lut_reg1: GP reg input switch data and hsync look-up table Register 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_gp_reg_IFMT_input_switch_lut_reg2: [ISPMADR] + 30808h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
IFMT_input_switch_lut_reg2								

Bit Range	Default & Access	Description
31:0	0h RW	IFMT_input_switch_lut_reg2: GP reg input switch data and hsync look-up table Register 2



15.8.230 reg_ifmt_gp_reg_IFMT_input_switch_lut_reg3_type (ifmt_gp_reg_IFMT_input_switch_lut_reg3)—Offset 3080Ch

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_gp_reg_IFMT_input_switch_lut_reg3: [ISPMADDR] + 3080Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	IFMT_input_switch_lut_reg3: GP reg input switch data and hsync look-up table Register 3

15.8.231 reg_ifmt_gp_reg_IFMT_input_switch_lut_reg4_type (ifmt_gp_reg_IFMT_input_switch_lut_reg4)—Offset 30810h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_gp_reg_IFMT_input_switch_lut_reg4: [ISPMADDR] + 30810h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





Bit Range	Default & Access	Description
31:0	0h RW	IFMT_input_switch_lut_reg4: GP reg input switch data and hsync look-up table Register 4

15.8.232 `reg_ifmt_gp_reg_IFMT_input_switch_lut_reg5_type`
(`ifmt_gp_reg_IFMT_input_switch_lut_reg5`)—Offset 30814h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
ifmt_gp_reg_IFMT_input_switch_lut_reg5: [ISPMADR] +
30814h
```

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28				24				20				16				12				8				4				0		
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
IFMT_input_switch_lut_reg5																															

Bit Range	Default & Access	Description
31:0	0h RW	IFMT_input_switch_lut_reg5: GP reg input switch data and hsync look-up table Register 5

15.8.233 `reg_ifmt_gp_reg_IFMT_input_switch_lut_reg6_type`
(ifmt_gp_reg_IFMT_input_switch_lut_reg6)—Offset 30818h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_gp_reg_IFMT_input_switch_lut_reg6: [ISPMADR] + 30818h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
IFMT_input_switch_lut_reg7								

15.8.235 reg_ifmt_gp_reg_IFMT_input_switch_fsync_lut_type
(ifmt_gp_reg_IFMT_input_switch_fsync_lut)—Offset 30820h

Intel Atom® Processor E3800 Product Family
Datasheet
1278



Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_gp_reg_IFMT_input_switch_fsync_lut: [ISPMMAADR] + 30820h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IFMT_input_switch_fsync_lut						IFMT_input_switch_fsync_lut		

Bit Range	Default & Access	Description
31:12	0h RW	unused_IFMT_input_switch_fsync_lut: Unused
11:0	0h RW	IFMT_input_switch_fsync_lut: GP reg input switch frame synchronization signal look-up table register

15.8.236 reg_ifmt_gp_reg_IFMT_srst_type (ifmt_gp_reg_IFMT_srst)—Offset 30824h

GP reg soft reset

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_gp_reg_IFMT_srst: [ISPMMAADR] + 30824h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IFMT_srst							mem_cpy	sec_ift
							prim_ift_b	prim_ift_a



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								mem_cpy
								sec_ift
								prim_ift_b
								prim_ift_a



15.8.238 reg_ifmt_gp_reg_IFMT_input_switch_ch_id_fmt_type_type (ifmt_gp_reg_IFMT_input_switch_ch_id_fmt_type)—Offset 3082Ch

GP reg input switch status register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_gp_reg_IFMT_input_switch_ch_id_fmt_type:
[ISPMADDR] + 3082Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IFMT_input_switch_ch_id_fmt_type							ch_id	fmt_type

Bit Range	Default & Access	Description
31:7	0h RW	unused_IFMT_input_switch_ch_id_fmt_type: Unused
6:5	0h RO	ch_id: Returns the channel id as it arrives at the input of the input switch
4:0	0h RO	fmt_type: Returns the format type as it arrives at the input of the input switch

15.8.239 reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge)—Offset 30A00h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge: [ISPMADDR] + 30A00h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IFMT_IRQ_ctrl_mask								IFMT_IRQ_ctrl_mask

October 2018
Document Number: 538136, Rev. 4.3



15.8.241 reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_status_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_status)—Offset 30A08h

IRQ controller STATUS

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_irq_ctrl_IFMT_IRQ_ctrl_status: [ISPMMAADR] + 30A08h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IFMT_IRQ_ctrl_status								sb_changed_irq_stat
								memcpy_irq_stat
								ift_sec_irq_stat
								ift_prim_b_irq_stat
								ift_prim_irq_stat

Bit Range	Default & Access	Description
31:5	0h RW	unused_IFMT_IRQ_ctrl_status: Unused
4	0h RO	sb_changed_irq_stat: Returns the status of the irq signal indicating a change in either the channel id or the format type
3	0h RO	memcpy_irq_stat: Returns the status of the irq generated by the stream to memory device
2	0h RO	ift_sec_irq_stat: Returns the status of the irq generated by the secondary input formatter
1	0h RO	ift_prim_b_irq_stat: Returns the status of the irq generated by the primary input formatter b
0	0h RO	ift_prim_irq_stat: Returns the status of the irq generated by the primary input formatter

15.8.242 reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_clear_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_clear)—Offset 30A0Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_irq_ctrl_IFMT_IRQ_ctrl_clear: [ISPMMAADR] + 30A0Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IFMT_IRQ_ctrl_enable								IFMT_IRQ_ctrl_enable

October 2018
Document Number: 538136, Rev. 4.3



15.8.244 reg_ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge_pulse_type (ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge_pulse)—Offset 30A14h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ifmt_irq_ctrl_IFMT_IRQ_ctrl_edge_pulse: [ISPMADDR] + 30A14h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_IFMT_IRQ_ctrl_edge_pulse								IFMT_IRQ_ctrl_edge_pulse

Bit Range	Default & Access	Description
31:5	0h RW	unused_IFMT_IRQ_ctrl_edge_pulse: Unused
4:0	0h RW	IFMT_IRQ_ctrl_edge_pulse: Indicates for each bit whether an interrupt cause is translated into a pulse (value='0') or into a constant level '1' (value='1') on the IRQ pin

15.8.245 reg_isp_dma_DMA_FSM_Command_type (isp_dma_DMA_FSM_Command)—Offset 40000h

FSM Command: Last command and State

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Command: [ISPMADDR] + 40000h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Error_state				RSVD0				Error_flag Stall_flag Run_flag Idle_flag



Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH0_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Description
1:0	0h RO	conn_id: Connection ID

15.8.247 reg_isp_dma_DMA_CH1_Packing_setup_type
(isp_dma_DMA_CH1_Packing_setup)—Offset 41004h

DMA CH 1 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma DMA_CH1 Packing setup: [ISPMADR] + 41004h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH1_Packing_setup								extend
								RSVD0
								conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH1_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.248 **reg_isp_dma_DMA_CH2_Packing_setup_type**
(isp_dma_DMA_CH2_Packing_setup)—Offset 41008h

DMA CH 2 PARAM 0: Packing setup

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH2_Packing_setup: [ISPMMAADR] + 41008h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH2_Packing_setup							extend	conn_id
							RSVD0	

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH2_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.249 reg_isp_dma_DMA_CH3_Packing_setup_type (isp_dma_DMA_CH3_Packing_setup)—Offset 4100Ch

DMA CH 3 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH3_Packing_setup: [ISPMMAADR] + 4100Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0		
unused_DMA_CH3_Packing_setup								extend	RSVD0	conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH3_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.250 reg_isp_dma_DMA_CH4_Packing_setup_type
(isp_dma_DMA_CH4_Packing_setup)—Offset 41010h

DMA CH 4 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH4_Packing_setup: [ISPMADR] + 41010h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH4_Packing_setup								extend
								RSVD0
								conn_id



Access Method

isp_dma DMA_CH5 Packing setup: [ISPMADDR] + 41014h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH5_Packing_setup								extend
								RSVD0
								conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH5_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID



15.8.255 reg_isp_dma_DMA_CH9_Packing_setup_type
(isp_dma_DMA_CH9_Packing_setup)—Offset 41024h



15.8.256 reg_isp_dma_DMA_CH10_Packing_setup_type (isp_dma_DMA_CH10_Packing_setup)—Offset 41028h

DMA CH 10 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH10_Packing_setup: [ISPMADDR] + 41028h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH10_Packing_setup							extend	conn_id
							RSVD0	

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH10_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.257 reg_isp_dma_DMA_CH11_Packing_setup_type (isp_dma_DMA_CH11_Packing_setup)—Offset 4102Ch

DMA CH 11 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH11_Packing_setup: [ISPMADDR] + 4102Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH11_Packing_setup								extend
								RSVD0
								conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH11_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.258 reg_isp_dma_DMA_CH12_Packing_setup_type
(isp_dma_DMA_CH12_Packing_setup)—Offset 41030h

DMA CH 12 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH12_Packing_setup: [ISPMMAADR] + 41030h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH12_Packing_setup								extend
								RSVD0
								conn_id



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH13_Packing_setup: [ISPMADR] + 41034h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH13_Packing_setup								extend
								RSVD0
								conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH13_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID



Access Method

isp_dma_DMA_CH16_Packing_setup: [ISPMMAADR] + 41040h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH16_Packing_setup								extend
								RSVD0
								conn_id



Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH16_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.263 reg_isp_dma_DMA_CH17_Packing_setup_type (isp_dma DMA_CH17_Packing_setup)—Offset 41044h

DMA CH 17 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH17_Packing_setup: [ISPMMAADR] + 41044h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0		
unused_DMA_CH17_Packing_setup								extend	RSVD0	conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH17_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID



15.8.264 reg_isp_dma_DMA_CH18_Packing_setup_type (isp_dma_DMA_CH18_Packing_setup)—Offset 41048h

DMA CH 18 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH18_Packing_setup: [ISPMADDR] + 41048h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH18_Packing_setup							extend	conn_id
							RSVD0	

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH18_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.265 reg_isp_dma_DMA_CH19_Packing_setup_type (isp_dma_DMA_CH19_Packing_setup)—Offset 4104Ch

DMA CH 19 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH19_Packing_setup: [ISPMADDR] + 4104Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0		
unused_DMA_CH19_Packing_setup								extend	RSVD0	conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH19_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.266 reg_isp_dma_DMA_CH20_Packing_setup_type
(isp_dma_DMA_CH20_Packing_setup)—Offset 41050h

DMA CH 20 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH20_Packing_setup: [ISPMMAADR] + 41050h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH20_Packing_setup								extend
								RSVD0
								conn_id



Access Method

isp_dma_DMA_CH21_Packing_setup: [ISPMADR] + 41054h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH21_Packing_setup								extend
								RSVD0
								conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH21_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.268 reg_isp_dma_DMA_CH22_Packing_setup_type
(isp_dma_DMA_CH22_Packing_setup)—Offset 41058h





Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH24_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.271 reg_isp_dma_DMA_CH25_Packing_setup_type
(isp_dma DMA_CH25_Packing_setup)—Offset 41064h

DMA CH 25 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH25_Packing_setup: [ISPMMAADR] + 41064h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH25_Packing_setup								extend
								RSVD0
								conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH25_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID



15.8.272 reg_isp_dma_DMA_CH26_Packing_setup_type (isp_dma_DMA_CH26_Packing_setup)—Offset 41068h

DMA CH 26 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH26_Packing_setup: [ISPMADDR] + 41068h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH26_Packing_setup							extend	conn_id
							RSVD0	

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH26_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.273 reg_isp_dma_DMA_CH28_Packing_setup_type (isp_dma_DMA_CH28_Packing_setup)—Offset 41070h

DMA CH 28 PARAM 0: Packing setup

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH28_Packing_setup: [ISPMADDR] + 41070h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH30_Packing_setup: [ISPMADR] + 41078h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)


ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH30_Packing_setup								extend
								RSVD0
								conn_id

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH30_Packing_setup: Unused
4	0h RO	extend: Zero(0)/Sign(1) extension
3:2	0b RO	RSVD0: Reserved
1:0	0h RO	conn_id: Connection ID

15.8.276 reg_isp_dma_DMA_CH31_Packing_setup_type
(isp_dma_DMA_CH31_Packing_setup)—Offset 4107Ch



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH0_dev_stride_A: DMA CH 0 PARAM 1: Device A stride

15.8.278 reg_isp_dma_DMA_CH1_dev_stride_A_type (isp_dma_DMA_CH1_dev_stride_A)—Offset 41104h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH1_dev_stride_A: [ISPMMAADR] + 41104h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH1_dev_stride_A: DMA CH 1 PARAM 1: Device A stride

15.8.279 reg_isp_dma_DMA_CH2_dev_stride_A_type (isp_dma_DMA_CH2_dev_stride_A)—Offset 41108h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH2_dev_stride_A: [ISPMMAADR] + 41108h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h



15.8.283 `reg_isp_dma_DMA_CH6_dev_stride_A_type`
(isp_dma DMA_CH6_dev_stride_A)—Offset 41118h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH6_dev_stride_A								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH6_dev_stride_A : DMA CH 6 PARAM 1: Device A stride

15.8.284 `reg_isp_dma_DMA_CH7_dev_stride_A_type`
(`isp_dma_DMA_CH7_dev_stride_A`)—Offset 4111Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH7_dev_stride_A: [ISPMADR] + 4111Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH7_dev_stride_A								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH7_dev_stride_A: DMA CH 7 PARAM 1: Device A stride

15.8.285 **reg_isp_dma_DMA_CH8_dev_stride_A_type**
(isp_dma_DMA_CH8_dev_stride_A)—Offset 41120h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


isp_dma_DMA_CH8_dev_stride_A: [ISPMADR] + 41120h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h



Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH8_dev_stride_A: DMA CH 8 PARAM 1: Device A stride

15.8.286 reg_isp_dma_DMA_CH9_dev_stride_A_type (isp_dma_DMA_CH9_dev_stride_A)—Offset 41124h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH9_dev_stride_A: [ISPMMAADR] + 41124h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH9_dev_stride_A: DMA CH 9 PARAM 1: Device A stride

15.8.287 reg_isp_dma_DMA_CH10_dev_stride_A_type (isp_dma_DMA_CH10_dev_stride_A)—Offset 41128h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH10_dev_stride_A: [ISPMMAADR] + 41128h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h



ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH12_dev_stride_A								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH12_dev_stride_A: DMA CH 12 PARAM 1: Device A stride

Access Method

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
DMA_CH13_dev_stride_A																															

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH13_dev_stride_A: DMA CH 13 PARAM 1: Device A stride



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH16_dev_stride_A: DMA CH 16 PARAM 1: Device A stride

15.8.294 reg_isp_dma_DMA_CH17_dev_stride_A_type
(isp_dma_DMA_CH17_dev_stride_A)—Offset 41144h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

312824201612840 00000000000000000000									
DMA_CH17_dev_stride_A									
Bit Range	Default & Access	Description							
31:0	0h RO	DMA_CH17_dev_stride_A: DMA CH 17 PARAM 1: Device A stride							

15.8.295 `reg_isp_dma_DMA_CH18_dev_stride_A_type`
(isp dma DMA CH18 dev stride A)—Offset 41148h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH18_dev_stride_A: [ISPMMAADR] + 41148h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0									
0	0	0	0	0	0	0	0	0	0
DMA_CH18_dev_stride_A									

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH18_dev_stride_A: DMA CH 18 PARAM 1: Device A stride

15.8.296 `reg_isp_dma_DMA_CH19_dev_stride_A_type`
(`isp_dma DMA_CH19_dev_stride A`)—Offset 4114Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH19_dev_stride A: [ISPMADR] + 4114Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)


ISPMADR Reference: [B:0, D:3, F:0] + 10h



ISPMADR Reference: [B:0, D:3, F:0] + 10h

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH20_dev_stride_A: DMA CH 20 PARAM 1: Device A stride

15.8.298 reg_isp_dma_DMA_CH21_dev_stride_A_type
(isp_dma_DMA_CH21_dev_stride_A)—Offset 41154h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH0_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.300 reg_isp_dma_DMA_CH1_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH1_dev_Pack_left_crop_and_elem_A)—Offset 41204h

DMA CH 1 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH1_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 41204h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH1_dev_Pack_left_crop_and_elem_A								
Dev_A_crop								
RSVD0								
Dev_A_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH1_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.301 reg_isp_dma_DMA_CH2_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH2_dev_Pack_left_crop_and_elem_A)– Offset 41208h

DMA CH 2 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH2_dev_Pack_left_crop_and_elem_A:
[ISPMADR] + 41208h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH2_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.302 reg_isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_A)—Offset 4120Ch

DMA CH 3 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 4120Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH3_dev_Pack_left_crop_and_elem_A								
Dev_A_crop								
RSVD0								
Dev_A_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH3_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.303 reg_isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_A)– Offset 41210h

DMA CH 4 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_A:
[ISPMADR] + 41210h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH4_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH4_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.304 reg_isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_A)—Offset 41214h

DMA CH 5 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_A:
[ISPMMADR] + 41214h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH5_dev_Pack_left_crop_and_elem_A								
Dev_A_crop								
RSVD0								
Dev_A_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH5_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.305 reg_isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_A)– Offset 41218h

DMA CH 6 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_A:
[ISPMADR] + 41218h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH6_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.306 reg_isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_A)—Offset 4121Ch

DMA CH 7 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 4121Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH7_dev_Pack_left_crop_and_elem_A								
Dev_A_crop								
RSVD0								
Dev_A_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH7_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.307 reg_isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_A)– Offset 41220h

DMA CH 8 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_A:
[ISPMADR] + 41220h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH8_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.308 reg_isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_A)—Offset 41224h

DMA CH 9 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_A:
[ISPMMADR] + 41224h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH9_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH9_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.309 reg_isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_A)—Offset 41228h

DMA CH 10 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_A:
[ISPMADR] + 41228h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH10_dev_Pack_left_crop_and_elem_A								
Dev_A_crop								
RSVD0								
Dev_A_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH10_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.310 reg_isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_A)– Offset 4122Ch

DMA CH 11 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_A:
[ISPMADDR] + 4122Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH11_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH11_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.311 reg_isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_A)– Offset 41230h

DMA CH 12 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 41230h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH12_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.312 reg_isp_dma_DMA_CH13_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH13_dev_Pack_left_crop_and_elem_A)—Offset 41234h

DMA CH 13 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH13_dev_Pack_left_crop_and_elem_A:
[ISPMADR] + 41234h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



15.8.313 reg_isp_dma_DMA_CH14_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH14_dev_Pack_left_crop_and_elem_A)–
Offset 41238h

Access Method

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH14_dev_Pack_left_crop_and_elem_A								
Dev_A_crop								
RSVD0								
Dev_A_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH14_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.314 reg_isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_A)—Offset 4123Ch

DMA CH 15 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_A:
[ISPMADDR] + 4123Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH15_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.315 reg_isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_A)—Offset 41240h

DMA CH 16 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 41240h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH16_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.316 reg_isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_A)—Offset 41244h

DMA CH 17 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_A:
[ISPMADR] + 41244h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH17_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH17_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.317 reg_isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_A)– Offset 41248h

DMA CH 18 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 41248h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH19_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH19_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.319 reg_isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_A)—Offset 41250h

DMA CH 20 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 41250h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH20_dev_Pack_left_crop_and_elem_A								
Dev_A_crop								
RSVD0								
Dev_A_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH20_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.320 reg_isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_A)– Offset 41254h

DMA CH 21 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_A:
[ISPMADDR] + 41254h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH21_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH21_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.321 reg_isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_A)—Offset 41258h

DMA CH 22 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_A:
[ISPMADDR] + 41258h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH23_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.323 reg_isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_A)—Offset 41260h

DMA CH 24 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 41260h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH24_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.324 reg_isp_dma_DMA_CH25_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH25_dev_Pack_left_crop_and_elem_A)—Offset 41264h

DMA CH 25 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH25_dev_Pack_left_crop_and_elem_A:
[ISPMADDR] + 41264h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH25_dev_Pack_left_crop_and_elem_A					Dev_A_crop	RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH25_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.325 reg_isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_A)—Offset 41268h

DMA CH 26 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 41268h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH26_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH26_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.326 reg_isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_A)—Offset 4126Ch

DMA CH 27 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_A:
[ISPMADDR] + 4126Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH27_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.327 reg_isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_A)—Offset 41270h

DMA CH 28 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 41270h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH28_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH28_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.328 reg_isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_A)– Offset 41274h

DMA CH 29 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_A:
[ISPMADDR] + 41274h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH29_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH29_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.329 reg_isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_A)—Offset 41278h

DMA CH 30 PARAM 2: Device A Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_A:
[ISPMMAADR] + 41278h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH30_dev_Pack_left_crop_and_elem_A				Dev_A_crop		RSVD0	Dev_A_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH30_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.330 reg_isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_A_type (isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_A)– Offset 4127Ch

DMA CH 31 PARAM 2: Device A Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_A:
[ISPMADDR] + 4127Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH31_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.331 reg_isp_dma_DMA_CH22_dev_stride_A_type (isp_dma_DMA_CH22_dev_stride_A)—Offset 412C0h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH22_dev_stride_A: [ISPMADR] + 412C0h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH22_dev_stride_A: DMA CH 22 PARAM 1: Device A stride

15.8.332 reg_isp_dma_DMA_CH23_dev_stride_A_type (isp_dma_DMA_CH23_dev_stride_A)—Offset 412C4h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH23_dev_stride_A: [ISPMADDR] + 412C4h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH23_dev_stride_A: DMA CH 23 PARAM 1: Device A stride

15.8.333 reg_isp_dma_DMA_CH24_dev_stride_A_type (isp_dma_DMA_CH24_dev_stride_A)—Offset 412C8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH24_dev_stride_A: [ISPMADDR] + 412C8h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h





Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH30_dev_stride_A: DMA CH 30 PARAM 1: Device A stride

15.8.340 reg_isp_dma_DMA_CH31_dev_stride_A_type
(isp_dma_DMA_CH31_dev_stride_A)—Offset 412E4h

Default: 00000000h

15.8.341 reg_isp_dma_DMA_CH0_Device_Xb_A_type
(isp dma DMA CH0 Device Xb A)—Offset 41300h



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH1_Device_Xb_A: [ISPMMAADR] + 41304h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH1_Device_Xb_A				DMA_CH1_Device_Xb_A				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH1_Device_Xb_A: Unused
15:0	0h RO	DMA_CH1_Device_Xb_A: DMA CH 1 PARAM 3: Device A block width (Xb)

15.8.343 reg_isp_dma_DMA_CH2_Device_Xb_A_type (isp_dma_DMA_CH2_Device_Xb_A)—Offset 41308h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH2_Device_Xb_A: [ISPMMAADR] + 41308h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH2_Device_Xb_A				DMA_CH2_Device_Xb_A				



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH5_Device_Xb_A				DMA_CH5_Device_Xb_A				

October 2018
Document Number: 538136, Rev. 4.3



15.8.347 reg_isp_dma_DMA_CH6_Device_Xb_A_type (isp_dma_DMA_CH6_Device_Xb_A)—Offset 41318h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH6_Device_Xb_A: [ISPMMAADR] + 41318h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH6_Device_Xb_A				DMA_CH6_Device_Xb_A				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH6_Device_Xb_A: Unused
15:0	0h RO	DMA_CH6_Device_Xb_A: DMA CH 6 PARAM 3: Device A block width (Xb)

15.8.348 reg_isp_dma_DMA_CH7_Device_Xb_A_type (isp_dma_DMA_CH7_Device_Xb_A)—Offset 4131Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH7_Device_Xb_A: [ISPMMAADR] + 4131Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH8_Device_Xb_A					DMA_CH8_Device_Xb_A			

October 2018
Document Number: 538136, Rev. 4.3



15.8.350 reg_isp_dma_DMA_CH9_Device_Xb_A_type (isp_dma_DMA_CH9_Device_Xb_A)—Offset 41324h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH9_Device_Xb_A: [ISPMMAADR] + 41324h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH9_Device_Xb_A				DMA_CH9_Device_Xb_A				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH9_Device_Xb_A: Unused
15:0	0h RO	DMA_CH9_Device_Xb_A: DMA CH 9 PARAM 3: Device A block width (Xb)

15.8.351 reg_isp_dma_DMA_CH10_Device_Xb_A_type (isp_dma_DMA_CH10_Device_Xb_A)—Offset 41328h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH10_Device_Xb_A: [ISPMMAADR] + 41328h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH11_Device_Xb_A: [ISPMADR] + 4132Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH11_Device_Xb_A					DMA_CH11_Device_Xb_A			

Intel Atom® Processor E3800 Product Family
Datasheet
1366



Bit Range	Default & Access	Description
15:0	0h RO	DMA_CH11_Device_Xb_A: DMA CH 11 PARAM 3: Device A block width (Xb)

15.8.353 reg_isp_dma_DMA_CH12_Device_Xb_A_type
(isp_dma DMA_CH12_Device_Xb_A)—Offset 41330h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH12_Device_Xb_A: [ISPMADR] + 41330h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH12_Device_Xb_A					DMA_CH12_Device_Xb_A			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH12_Device_Xb_A: Unused
15:0	0h RO	DMA_CH12_Device_Xb_A: DMA CH 12 PARAM 3: Device A block width (Xb)

15.8.354 reg_isp_dma_DMA_CH13_Device_Xb_A_type
(isp_dma_DMA_CH13_Device_Xb_A)—Offset 41334h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH13_Device_Xb_A: [ISPMADR] + 41334h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH14_Device_Xb_A: [ISPMADR] + 41338h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH14_Device_Xb_A				DMA_CH14_Device_Xb_A				

Intel Atom® Processor E3800 Product Family
Datasheet
1368



Bit Range	Default & Access	Description
15:0	0h RO	DMA_CH14_Device_Xb_A: DMA CH 14 PARAM 3: Device A block width (Xb)

15.8.356 reg_isp_dma_DMA_CH15_Device_Xb_A_type
(isp_dma DMA_CH15_Device_Xb_A)—Offset 4133Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH15_Device_Xb_A: [ISPMADR] + 4133Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH15_Device_Xb_A					DMA_CH15_Device_Xb_A			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH15_Device_Xb_A: Unused
15:0	0h RO	DMA_CH15_Device_Xb_A: DMA CH 15 PARAM 3: Device A block width (Xb)

15.8.357 reg_isp_dma_DMA_CH16_Device_Xb_A_type
(isp_dma_DMA_CH16_Device_Xb_A)—Offset 41340h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH16_Device_Xb_A: [ISPMADR] + 41340h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH16_Device_Xb_A: Unused
15:0	0h RO	DMA_CH16_Device_Xb_A: DMA CH 16 PARAM 3: Device A block width (Xb)

15.8.358 reg_isp_dma_DMA_CH17_Device_Xb_A_type
(isp_dma_DMA_CH17_Device_Xb_A)—Offset 41344h

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH17_Device_Xb_A: Unused



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH20_Device_Xb_A: [ISPMMAADR] + 41350h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH20_Device_Xb_A				DMA_CH20_Device_Xb_A				

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH23_Device_Xb_A: [ISPMADR] + 4135Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH23_Device_Xb_A					DMA_CH23_Device_Xb_A			

Intel Atom® Processor E3800 Product Family
Datasheet
1374



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH26_Device_Xb_A: [ISPMADR] + 41368h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH26_Device_Xb_A				DMA_CH26_Device_Xb_A				

Intel Atom® Processor E3800 Product Family
Datasheet
1376



Bit Range	Default & Access	Description
15:0	0h RO	DMA_CH26_Device_Xb_A: DMA CH 26 PARAM 3: Device A block width (Xb)

15.8.368 reg_isp_dma_DMA_CH27_Device_Xb_A_type
(isp_dma DMA_CH27_Device_Xb_A)—Offset 4136Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH27_Device_Xb_A: [ISPMADR] + 4136Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH27_Device_Xb_A					DMA_CH27_Device_Xb_A			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH27_Device_Xb_A: Unused
15:0	0h RO	DMA_CH27_Device_Xb_A: DMA CH 27 PARAM 3: Device A block width (Xb)

15.8.369 **reg_isp_dma_DMA_CH28_Device_Xb_A_type**
(isp_dma_DMA_CH28_Device_Xb_A)—Offset 41370h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH28_Device_Xb_A: [ISPMADR] + 41370h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH29_Device_Xb_A					DMA_CH29_Device_Xb_A			

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH31_Device_Xb_A: Unused
15:0	0h RO	DMA_CH31_Device_Xb_A: DMA CH 31 PARAM 3: Device A block width (Xb)

15.8.373 reg_isp_dma_DMA_CH0_dev_stride_B_type
(isp_dma_DMA_CH0_dev_stride_B)—Offset 41400h

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH0_dev_stride_B: DMA CH 0 PARAM 4: Device B stride

15.8.374 reg_isp_dma_DMA_CH1_dev_stride_B_type
(isp_dma_DMA_CH1_dev_stride_B)—Offset 41404h

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH3_dev_stride_B: [ISPMMA DR] + 4140Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH3_dev_stride_B								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH3_dev_stride_B: DMA CH 3 PARAM 4: Device B stride

15.8.377 `reg_isp_dma_DMA_CH4_dev_stride_B_type`
(isp_dma DMA_CH4_dev_stride_B)—Offset 41410h

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp dma DMA CH4 dev stride B: [ISPMADR] + 41410h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH4_dev_stride_B								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH4_dev_stride_B: DMA CH 4 PARAM 4: Device B stride



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH7_dev_stride_B: [ISPMADR] + 4141Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH7_dev_stride_B								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH7_dev_stride_B: DMA CH 7 PARAM 4: Device B stride

15.8.381 `reg_isp_dma_DMA_CH8_dev_stride_B_type`
(isp_dma DMA_CH8_dev_stride_B)—Offset 41420h

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH8_dev_stride_B: [ISPMADR] + 41420h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH8_dev_stride_B								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH8_dev_stride_B: DMA CH 8 PARAM 4: Device B stride



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH11_dev_stride_B: DMA CH 11 PARAM 4: Device B stride

15.8.385 reg_isp_dma_DMA_CH12_dev_stride_B_type
(isp_dma_DMA_CH12_dev_stride_B)—Offset 41430h

31	28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
DMA_CH12_dev_stride_B																																



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH15_dev_stride_B								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH15_dev_stride_B : DMA CH 15 PARAM 4: Device B stride

15.8.389 reg_isp_dma_DMA_CH16_dev_stride_B_type
(isp_dma DMA_CH16_dev_stride B)—Offset 41440h


Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h



Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH16_dev_stride_B: DMA CH 16 PARAM 4: Device B stride

15.8.390 reg_isp_dma_DMA_CH17_dev_stride_B_type (isp_dma_DMA_CH17_dev_stride_B)—Offset 41444h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH17_dev_stride_B: [ISPMMAADR] + 41444h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH17_dev_stride_B: DMA CH 17 PARAM 4: Device B stride

15.8.391 reg_isp_dma_DMA_CH18_dev_stride_B_type (isp_dma_DMA_CH18_dev_stride_B)—Offset 41448h

Access Method



ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH18_dev_stride_B								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH18_dev_stride_B: DMA CH 18 PARAM 4: Device B stride

15.8.392 reg_isp_dma_DMA_CH19_dev_stride_B_type
(isp_dma_DMA_CH19_dev_stride_B)—Offset 4144Ch

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
DMA_CH19_dev_stride_B																															

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH19_dev_stride_B: DMA CH 19 PARAM 4: Device B stride



Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH21_dev_stride_B: DMA CH 21 PARAM 4: Device B stride

15.8.395 reg_isp_dma_DMA_CH22_dev_stride_B_type (isp_dma_DMA_CH22_dev_stride_B)—Offset 41458h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH22_dev_stride_B: [ISPMADDR] + 41458h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DMA_CH22_dev_stride_B

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH22_dev_stride_B: DMA CH 22 PARAM 4: Device B stride

15.8.396 reg_isp_dma_DMA_CH23_dev_stride_B_type (isp_dma_DMA_CH23_dev_stride_B)—Offset 4145Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH23_dev_stride_B: [ISPMADDR] + 4145Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DMA_CH26_dev_stride_B

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH26_dev_stride_B: DMA CH 26 PARAM 4: Device B stride

15.8.399 reg_isp_dma_DMA_CH27_dev_stride_B_type (isp_dma_DMA_CH27_dev_stride_B)—Offset 4146Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH27_dev_stride_B: [ISPMADDR] + 4146Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DMA_CH27_dev_stride_B

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH27_dev_stride_B: DMA CH 27 PARAM 4: Device B stride

15.8.400 reg_isp_dma_DMA_CH28_dev_stride_B_type (isp_dma_DMA_CH28_dev_stride_B)—Offset 41470h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH30_dev_stride_B: [ISPMMAADR] + 41478h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
DMA_CH30_dev_stride_B																															

Bit Range	Default & Access	Description
31:0	0h RO	DMA_CH30_dev_stride_B : DMA CH 30 PARAM 4: Device B stride

15.8.403 reg_isp_dma_DMA_CH31_dev_stride_B_type
(isp_dma_DMA_CH31_dev_stride_B)—Offset 4147Ch

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH31_dev_stride_B: [ISPMMAADR] + 4147Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]



15.8.405 reg_ism_dma_DMA_CH1_dev_Pack_left_crop_and_elem_B_type (ism_dma_DMA_CH1_dev_Pack_left_crop_and_elem_B)– Offset 41504h

DMA CH 1 PARAM 5: Device B Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ism_dma_DMA_CH1_dev_Pack_left_crop_and_elem_B:
[ISPMADDR] + 41504h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH1_dev_Pack_left_crop_and_elem_B								
Dev_B_crop								
RSVD0								
Dev_B_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH1_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.406 reg_ism_dma_DMA_CH2_dev_Pack_left_crop_and_elem_B_type (ism_dma_DMA_CH2_dev_Pack_left_crop_and_elem_B)– Offset 41508h

DMA CH 2 PARAM 5: Device B Packing LSE cropping/Elements

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH2_dev_Pack_left_crop_and_elem_B:
[ISPMMADR] + 41508h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH2_dev_Pack_left_crop_and_elem_B					Dev_B_crop		RSVD0	Dev_B_elem

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH2_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.407 reg_isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_B)—Offset 4150Ch

DMA CH 3 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH3_dev_Pack_left_crop_and_elem_B:
[ISPMMADR] + 4150Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH3_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.408 reg_isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_B)—Offset 41510h

DMA CH 4 PARAM 5: Device B Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH4_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 41510h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH4_dev_Pack_left_crop_and_elem_B				Dev_B_crop		RSVD0	Dev_B_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH4_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.409 reg_isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_B)— Offset 41514h

DMA CH 5 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH5_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 41514h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH5_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.410 reg_isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_B)—Offset 41518h

DMA CH 6 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH6_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 41518h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH6_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.411 reg_isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_B)—Offset 4151Ch

DMA CH 7 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH7_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 4151Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH7_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.412 reg_isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_B)—Offset 41520h

DMA CH 8 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH8_dev_Pack_left_crop_and_elem_B:
[ISPMMADR] + 41520h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH8_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.413 reg_isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_B)—Offset 41524h

DMA CH 9 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH9_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 41524h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH9_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.414 reg_isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_B)—Offset 41528h

DMA CH 10 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH10_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 41528h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH10_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.415 reg_isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_B)– Offset 4152Ch

DMA CH 11 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH11_dev_Pack_left_crop_and_elem_B:
[ISPMADDR] + 4152Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH11_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.416 reg_isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_B)– Offset 41530h

DMA CH 12 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH12_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 41530h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



15.8.417 reg_isp_dma_DMA_CH13_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH13_dev_Pack_left_crop_and_elem_B)–
Offset 41534h

Access Method

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
1409



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH13_dev_Pack_left_crop_and_elem_B								
Dev_B_crop								
RSVD0								
Dev_B_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH13_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.418 reg_isp_dma_DMA_CH14_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH14_dev_Pack_left_crop_and_elem_B)—Offset 41538h

DMA CH 14 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH14_dev_Pack_left_crop_and_elem_B:
[ISPMADDR] + 41538h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH14_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.419 reg_isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_B)—Offset 4153Ch

DMA CH 15 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH15_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 4153Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH15_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.420 reg_isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_B)—Offset 41540h

DMA CH 16 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH16_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 41540h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH16_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.421 reg_isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_B)– Offset 41544h

DMA CH 17 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH17_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 41544h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH17_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.422 reg_isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_B)– Offset 41548h

DMA CH 18 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH18_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 41548h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH18_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.423 reg_isp_dma_DMA_CH19_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH19_dev_Pack_left_crop_and_elem_B)—Offset 4154Ch

DMA CH 19 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH19_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 4154Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH19_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.424 reg_isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_B)– Offset 41550h

DMA CH 20 PARAM 5: Device B Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH20_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 41550h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH20_dev_Pack_left_crop_and_elem_B				Dev_B_crop			RSVD0	Dev_B_elem

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH20_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.425 reg_isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_B)– Offset 41554h

DMA CH 21 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH21_dev_Pack_left_crop_and_elem_B:
[ISPMADDR] + 41554h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH21_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.426 reg_isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_B)– Offset 41558h

DMA CH 22 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH22_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 41558h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH22_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.427 reg_isp_dma_DMA_CH23_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH23_dev_Pack_left_crop_and_elem_B)—Offset 4155Ch

DMA CH 23 PARAM 5: Device B Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH23_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 4155Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH23_dev_Pack_left_crop_and_elem_B								
					Dev_B_crop			
RSVD0								
Dev_B_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH23_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.428 reg_isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_B)– Offset 41560h

DMA CH 24 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH24_dev_Pack_left_crop_and_elem_B:
[ISPMADDR] + 41560h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h




15.8.429 reg_isp_dma_DMA_CH25_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH25_dev_Pack_left_crop_and_elem_B)–
Offset 41564h

Access Method

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
1421



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH25_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.430 reg_isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_B)—Offset 41568h

DMA CH 26 PARAM 5: Device B Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH26_dev_Pack_left_crop_and_elem_B:
[ISPMADDR] + 41568h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH26_dev_Pack_left_crop_and_elem_B				Dev_B_crop			RSVD0	Dev_B_elem

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH26_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.431 reg_isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_B)– Offset 4156Ch

DMA CH 27 PARAM 5: Device B Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH27_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 4156Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH27_dev_Pack_left_crop_and_elem_B								
Dev_B_crop								
RSVD0								
Dev_B_elem								

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH27_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.432 reg_isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_B)– Offset 41570h

DMA CH 28 PARAM 5: Device B Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH28_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 41570h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH28_dev_Pack_left_crop_and_elem_B				Dev_B_crop		RSVD0	Dev_B_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH28_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.433 reg_isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_B) – Offset 41574h

DMA CH 29 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH29_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 41574h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH29_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.434 reg_isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_B)– Offset 41578h

DMA CH 30 PARAM 5: Device B Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH30_dev_Pack_left_crop_and_elem_B:
[ISPMADR] + 41578h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH30_dev_Pack_left_crop_and_elem_B				Dev_B_crop			RSVD0	Dev_B_elem

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH30_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.435 reg_isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_B_type (isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_B)– Offset 4157Ch

DMA CH 31 PARAM 5: Device B Packing LSE cropping/Elements

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH31_dev_Pack_left_crop_and_elem_B:
[ISPMMAADR] + 4157Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH31_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0b RO	RSVD0: Reserved
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.436 reg_isp_dma_DMA_CH0_Device_Xb_B_type (isp_dma_DMA_CH0_Device_Xb_B)—Offset 41600h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH0_Device_Xb_B: [ISPMADDR] + 41600h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH1_Device_Xb_B					DMA_CH1_Device_Xb_B			

Intel Atom® Processor E3800 Product Family
Datasheet
1429



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH2_Device_Xb_B: [ISPMADR] + 41608h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH2_Device_Xb_B					DMA_CH2_Device_Xb_B			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH2_Device_Xb_B: Unused
15:0	0h RO	DMA_CH2_Device_Xb_B: DMA CH 2 PARAM 6: Device B block width (Xb)

15.8.439 **reg_isp_dma_DMA_CH3_Device_Xb_B_type**
(isp_dma_DMA_CH3_Device_Xb_B)—Offset 4160Ch

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH3_Device_Xb_B: [ISPMADR] + 4160Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





15.8.441 reg_isp_dma_DMA_CH5_Device_Xb_B_type (isp_dma_DMA_CH5_Device_Xb_B)—Offset 41614h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH5_Device_Xb_B: [ISPMADDR] + 41614h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH5_Device_Xb_B				DMA_CH5_Device_Xb_B				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH5_Device_Xb_B: Unused
15:0	0h RO	DMA_CH5_Device_Xb_B: DMA CH 5 PARAM 6: Device B block width (Xb)

15.8.442 reg_isp_dma_DMA_CH6_Device_Xb_B_type (isp_dma_DMA_CH6_Device_Xb_B)—Offset 41618h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH6_Device_Xb_B: [ISPMADDR] + 41618h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





15.8.444 reg_isp_dma_DMA_CH8_Device_Xb_B_type (isp_dma_DMA_CH8_Device_Xb_B)—Offset 41620h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH8_Device_Xb_B: [ISPMMAADR] + 41620h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH8_Device_Xb_B				DMA_CH8_Device_Xb_B				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH8_Device_Xb_B: Unused
15:0	0h RO	DMA_CH8_Device_Xb_B: DMA CH 8 PARAM 6: Device B block width (Xb)

15.8.445 reg_isp_dma_DMA_CH9_Device_Xb_B_type (isp_dma_DMA_CH9_Device_Xb_B)—Offset 41624h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH9_Device_Xb_B: [ISPMMAADR] + 41624h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



15.8.446 **reg_isp_dma_DMA_CH10_Device_Xb_B_type**
(isp_dma_DMA_CH10_Device_Xb_B)—Offset 41628h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH10_Device_Xb_B					DMA_CH10_Device_Xb_B			

Intel Atom® Processor E3800 Product Family
Datasheet
1435



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH11_Device_Xb_B: Unused
15:0	0h RO	DMA_CH11_Device_Xb_B: DMA CH 11 PARAM 6: Device B block width (Xb)

15.8.448 reg_isp_dma_DMA_CH12_Device_Xb_B_type
(isp_dma_DMA_CH12_Device_Xb_B)—Offset 41630h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH14_Device_Xb_B: Unused
15:0	0h RO	DMA_CH14_Device_Xb_B: DMA CH 14 PARAM 6: Device B block width (Xb)

15.8.451 reg_isp_dma_DMA_CH15_Device_Xb_B_type
(isp_dma_DMA_CH15_Device_Xb_B)—Offset 4163Ch

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH16_Device_Xb_B					DMA_CH16_Device_Xb_B			

Intel Atom® Processor E3800 Product Family
Datasheet
1439



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH17_Device_Xb_B					DMA_CH17_Device_Xb_B			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH17_Device_Xb_B: Unused
15:0	0h RO	DMA_CH17_Device_Xb_B: DMA CH 17 PARAM 6: Device B block width (Xb)

15.8.454 **reg_isp_dma_DMA_CH18_Device_Xb_B_type**
(isp_dma_DMA_CH18_Device_Xb_B)—Offset 41648h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
1440



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH19_Device_Xb_B: Unused



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH20_Device_Xb_B					DMA_CH20_Device_Xb_B			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH20_Device_Xb_B: Unused
15:0	0h RO	DMA_CH20_Device_Xb_B: DMA CH 20 PARAM 6: Device B block width (Xb)

15.8.457 reg_isp_dma_DMA_CH21_Device_Xb_B_type
(isp_dma_DMA_CH21_Device_Xb_B)—Offset 41654h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
1442



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH23_Device_Xb_B: Unused
15:0	0h RO	DMA_CH23_Device_Xb_B: DMA CH 23 PARAM 6: Device B block width (Xb)

15.8.460 reg_isp_dma_DMA_CH24_Device_Xb_B_type
(isp_dma_DMA_CH24_Device_Xb_B)—Offset 41660h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH25_Device_Xb_B					DMA_CH25_Device_Xb_B			

Intel Atom® Processor E3800 Product Family
Datasheet
1445



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH26_Device_Xb_B				DMA_CH26_Device_Xb_B				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH26_Device_Xb_B: Unused
15:0	0h RO	DMA_CH26_Device_Xb_B: DMA CH 26 PARAM 6: Device B block width (Xb)

15.8.463 `reg_isp_dma_DMA_CH27_Device_Xb_B_type`
(`isp_dma_DMA_CH27_Device_Xb_B`)—Offset 4166Ch

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH28_Device_Xb_B: Unused



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH29_Device_Xb_B: Unused
15:0	0h RO	DMA_CH29_Device_Xb_B: DMA CH 29 PARAM 6: Device B block width (Xb)

15.8.466 reg_isp_dma_DMA_CH31_Device_Xb_B_type
(isp_dma_DMA_CH31_Device_Xb_B)—Offset 41678h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH1_Yb: [ISPMADR] + 41704h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH1_Yb					DMA_CH1_Yb			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH1_Yb: Unused
15:0	0h RO	DMA_CH1_Yb: DMA CH 1 PARAM 7: block Height (Yb)

15.8.469 reg_isp_dma_DMA_CH2_Yb_type (isp_dma_DMA_CH2_Yb)–
Offset 41708h

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH2_Yb: [ISPMADR] + 41708h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH2_Yb					DMA_CH2_Yb			



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH2_Yb: Unused
15:0	0h RO	DMA_CH2_Yb: DMA CH 2 PARAM 7: block Height (Yb)

15.8.470 reg_isp_dma_DMA_CH3_Yb_type (isp_dma_DMA_CH3_Yb)–
Offset 4170Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH3_Yb: [ISPMADR] + 4170Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH3_Yb				DMA_CH3_Yb				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH3_Yb: Unused
15:0	0h RO	DMA_CH3_Yb: DMA CH 3 PARAM 7: block Height (Yb)

15.8.471 reg_isp_dma_DMA_CH4_Yb_type (isp_dma_DMA_CH4_Yb)–
Offset 41710h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH4_Yb: [ISPMMADR] + 41710h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH5_Yb: [ISPMADR] + 41714h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH5_Yb					DMA_CH5_Yb			

15.8.473 reg_isp_dma_DMA_CH6_Yb_type (isp_dma_DMA_CH6_Yb)–
Offset 41718h

Intel Atom® Processor E3800 Product Family
Datasheet
1452



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH8_Yb: [ISPMADR] + 41720h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH8_Yb					DMA_CH8_Yb			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH8_Yb: Unused
15:0	0h RO	DMA_CH8_Yb: DMA CH 8 PARAM 7: block Height (Yb)

15.8.476 reg_isp_dma_DMA_CH9_Yb_type (isp_dma_DMA_CH9_Yb)–
Offset 41724h

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH9_Yb: [ISPMMADR] + 41724h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH9_yb					DMA_CH9_yb			



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH12_Yb					DMA_CH12_Yb			

15.8.480 reg_isp_dma_DMA_CH13_Yb_type (isp_dma_DMA_CH13_Yb)–
Offset 41734h

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH15_Yb: [ISPMMADR] + 4173Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH15_Yb					DMA_CH15_Yb			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH15_Yb: Unused
15:0	0h RO	DMA_CH15_Yb: DMA CH 15 PARAM 7: block Height (Yb)

15.8.483 reg_isp_dma_DMA_CH16_Yb_type (isp_dma_DMA_CH16_Yb)–
Offset 41740h

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH16_Yb: [ISPMMADR] + 41740h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH16_Yb					DMA_CH16_Yb			



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH19_Yb					DMA_CH19_Yb			

15.8.487 reg_isp_dma_DMA_CH20_Yb_type (isp_dma_DMA_CH20_Yb)–
Offset 41750h

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH22_Yb: Unused
15:0	0h RO	DMA_CH22_Yb: DMA CH 22 PARAM 7: block Height (Yb)

15.8.490 reg_isp_dma_DMA_CH23_Yb_type (isp_dma_DMA_CH23_Yb)–
Offset 4175Ch

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH23_Yb					DMA_CH23_Yb			



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH23_Yb: Unused
15:0	0h RO	DMA_CH23_Yb: DMA CH 23 PARAM 7: block Height (Yb)

15.8.491 reg_isp_dma_DMA_CH24_Yb_type (isp_dma_DMA_CH24_Yb)–
Offset 41760h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH24_Yb: [ISPMADR] + 41760h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH24_Yb					DMA_CH24_Yb			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH24_Yb: Unused
15:0	0h RO	DMA_CH24_Yb: DMA CH 24 PARAM 7: block Height (Yb)

15.8.492 reg_isp_dma_DMA_CH25_Yb_type (isp_dma_DMA_CH25_Yb)–
Offset 41764h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH25_Yb: [ISPMADR] + 41764h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH26_Yb: Unused
15:0	0h RO	DMA_CH26_Yb: DMA CH 26 PARAM 7: block Height (Yb)

15.8.494 reg_isp_dma_DMA_CH27_Yb_type (isp_dma_DMA_CH27_Yb)–
Offset 4176Ch



15.8.496 reg_isp_dma_DMA_CH29_Yb_type (isp_dma_DMA_CH29_Yb)— Offset 41774h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH29_Yb: [ISPMADDR] + 41774h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH29_Yb				DMA_CH29_Yb				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH29_Yb: Unused
15:0	0h RO	DMA_CH29_Yb: DMA CH 29 PARAM 7: block Height (Yb)

15.8.497 reg_isp_dma_DMA_CH31_Yb_type (isp_dma_DMA_CH31_Yb)— Offset 4177Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH31_Yb: [ISPMADDR] + 4177Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH31_Yb				DMA_CH31_Yb				



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_CH31_Yb: Unused
15:0	0h RO	DMA_CH31_Yb: DMA CH 31 PARAM 7: block Height (Yb)

15.8.498 `reg_isp_dma_DMA_CH0_pending_command_type`
(`isp_dma_DMA_CH0_pending_command`)—Offset 41800h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH0_pending_command: [ISPMADR] + 41800h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH0_pending_command								DMA_CH0_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH0_pending_command: Unused
3:0	0h RO	DMA_CH0_pending_command: DMA CH 0 PARAM 8: Pending commands which will use channel 0

15.8.499 reg_isp_dma_DMA_CH1_pending_command_type
(isp_dma_DMA_CH1_pending_command)—Offset 41804h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH1_pending_command: [ISPMADR] + 41804h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH1_pending_command: Unused
3:0	0h RO	DMA_CH1_pending_command: DMA CH 1 PARAM 8: Pending commands which will use channel 1

15.8.500 reg_isp_dma_DMA_CH2_pending_command_type (isp_dma_DMA_CH2_pending_command)—Offset 41808h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH2_pending_command: [ISPMADR] + 41808h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH2_pending_command: Unused
3:0	0h RO	DMA_CH2_pending_command: DMA CH 2 PARAM 8: Pending commands which will use channel 2

15.8.501 `reg_isp_dma_DMA_CH3_pending_command_type`
(`isp_dma_DMA_CH3_pending_command`)—Offset 4180Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH3_pending_command: [ISPMADR] + 4180Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH3_pending_command								DMA_CH3_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH3_pending_command: Unused
3:0	0h RO	DMA_CH3_pending_command: DMA CH 0 PARAM 8: Pending commands which will use channel 3

15.8.502 reg_isp_dma_DMA_CH4_pending_command_type
(isp_dma_DMA_CH4_pending_command)—Offset 41810h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH4_pending_command: [ISPMADR] + 41810h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH4_pending_command: Unused
3:0	0h RO	DMA_CH4_pending_command: DMA CH 4 PARAM 8: Pending commands which will use channel 4

15.8.503 reg_isp_dma_DMA_CH5_pending_command_type (isp_dma_DMA_CH5_pending_command)—Offset 41814h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH5_pending_command: [ISPMADR] + 41814h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH5_pending_command: Unused
3:0	0h RO	DMA_CH5_pending_command: DMA CH 5 PARAM 8: Pending commands which will use channel 5

15.8.504 `reg_isp_dma_DMA_CH6_pending_command_type`
(`isp_dma_DMA_CH6_pending_command`)—Offset 41818h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH6_pending_command: [ISPMADR] + 41818h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH6_pending_command								DMA_CH6_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH6_pending_command: Unused
3:0	0h RO	DMA_CH6_pending_command: DMA CH 6 PARAM 8: Pending commands which will use channel 6

15.8.505 `reg_isp_dma_DMA_CH7_pending_command_type`
(`isp_dma_DMA_CH7_pending_command`)—Offset 4181Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH7_pending_command: [ISPMADR] + 4181Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Default: 00000000h



Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH8_pending_command: Unused
3:0	0h RO	DMA_CH8_pending_command: DMA CH 8 PARAM 8: Pending commands which will use channel 6

15.8.507 `reg_isp_dma_DMA_CH9_pending_command_type`
(`isp_dma_DMA_CH9_pending_command`)—Offset 41824h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH9_pending_command: [ISPMADR] + 41824h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH9_pending_command								DMA_CH9_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH9_pending_command: Unused
3:0	0h RO	DMA_CH9_pending_command: DMA CH 9 PARAM 8: Pending commands which will use channel 7

15.8.508 reg_isp_dma_DMA_CH10_pending_command_type
(isp_dma_DMA_CH10_pending_command)—Offset 41828h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH10_pending_command: [ISPMADR] + 41828h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								DMA_CH11_pending_command



Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH11_pending_command: Unused
3:0	0h RO	DMA_CH11_pending_command: DMA CH 11 PARAM 8: Pending commands which will use channel 1

15.8.510 `reg_isp_dma_DMA_CH12_pending_command_type`
(`isp_dma_DMA_CH12_pending_command`)—Offset 41830h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH12_pending_command: [ISPMMAADR] + 41830h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH12_pending_command								DMA_CH12_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH12_pending_command: Unused
3:0	0h RO	DMA_CH12_pending_command: DMA CH 12 PARAM 8: Pending commands which will use channel 2

15.8.511 reg_isp_dma_DMA_CH13_pending_command_type
(isp_dma_DMA_CH13_pending_command)—Offset 41834h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH13_pending_command: [ISPMADR] + 41834h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH14_pending_command								0



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH17_pending_command: Unused
3:0	0h RO	DMA_CH17_pending_command: DMA CH 17 PARAM 8: Pending commands which will use channel 7

15.8.516 reg_isp_dma_DMA_CH18_pending_command_type
(isp dma DMA CH18 pending command)—Offset 41848h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH18_pending_command: [ISPMADR] + 41848h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH18_pending_command								DMA_CH18_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH18_pending_command: Unused
3:0	0h RO	DMA_CH18_pending_command: DMA CH 18 PARAM 8: Pending commands which will use channel 6

15.8.517 reg_isp_dma_DMA_CH19_pending_command_type
(isp_dma_DMA_CH19_pending_command)—Offset 4184Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH19_pending_command: [ISPMADR] + 4184Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH20_pending_command								DMA_CH20_pending_command



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	unused_DMA_CH23_pending_command
0	0	0	0	0	0	0	0	0	DMA_CH23_pending_command



Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH23_pending_command: Unused
3:0	0h RO	DMA_CH23_pending_command: DMA CH 20 PARAM 8: Pending commands which will use channel 3

15.8.522 reg_isp_dma_DMA_CH24_pending_command_type
(isp dma DMA CH24 pending command)—Offset 41860h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH24_pending_command: [ISPMADR] + 41860h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH24_pending_command								DMA_CH24_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH24_pending_command: Unused
3:0	0h RO	DMA_CH24_pending_command: DMA CH 24 PARAM 8: Pending commands which will use channel 4

15.8.523 reg_isp_dma_DMA_CH25_pending_command_type
(isp_dma DMA_CH25_pending_command)—Offset 41864h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH25_pending_command: [ISPMADR] + 41864h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH26_pending_command								0



Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH26_pending_command: Unused
3:0	0h RO	DMA_CH26_pending_command: DMA CH 26 PARAM 8: Pending commands which will use channel 6

15.8.525 reg_isp_dma_DMA_CH27_pending_command_type
(isp dma DMA CH27 pending command)—Offset 4186Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH27_pending_command: [ISPMADR] + 4186Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								DMA_CH27_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH27_pending_command: Unused
3:0	0h RO	DMA_CH27_pending_command: DMA CH 27 PARAM 8: Pending commands which will use channel 7

15.8.526 reg_isp_dma_DMA_CH28_pending_command_type
(isp_dma_DMA_CH28_pending_command)—Offset 41870h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH28_pending_command: [ISPMADR] + 41870h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH29_pending_command								DMA_CH29_pending_command



Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH29_pending_command: Unused
3:0	0h RO	DMA_CH29_pending_command: DMA CH 29 PARAM 8: Pending commands which will use channel 7

15.8.528 `reg_isp_dma_DMA_CH30_pending_command_type`
(`isp_dma_DMA_CH30_pending_command`)—Offset 41878h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH30_pending_command: [ISPMMAADR] + 41878h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
unused_DMA_CH30_pending_command								DMA_CH30_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH30_pending_command: Unused
3:0	0h RO	DMA_CH30_pending_command: DMA CH 30 PARAM 8: Pending commands which will use channel 6

15.8.529 reg_isp_dma_DMA_CH31_pending_command_type
(isp_dma_DMA_CH31_pending_command)—Offset 4187Ch

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_CH31_pending_command: [ISPMADR] + 4187Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH31_pending_command: Unused
3:0	0h RO	DMA_CH31_pending_command: DMA CH 30 PARAM 8: Pending commands which will use channel 7

15.8.530 reg_isp_dma_DMA_command_token_type (isp_dma_DMA_command_token)—Offset 42000h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_command_token: [ISPMADR] + 42000h


ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	DMA_command_token: Pending or last executed command token



15.8.535 reg_isp_dma_DMA_FSM_Pack_status_type
(isp_dma_DMA_FSM_Pack_status)—Offset 42014h

Default: 00000001h



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_request_status: [ISPMMAADR] + 42018h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_request_status								DMA_FSM_request_status



Bit Range	Default & Access	Description
31:2	0h RW	unused_DMA_FSM_request_status: Unused
1:0	0h RO	DMA_FSM_request_status: DMA FSM Request state: 0)Idle -- 1)req -- 2)Next line

15.8.537 `reg_isp_dma_DMA_FSM_write_status_type`
(`isp_dma_DMA_FSM_write_status`)—Offset 4201Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_write_status: [ISPMADR] + 4201Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
unused_DMA_FSM_write_status									DMA_FSM_write_status

Bit Range	Default & Access	Description
31:2	0h RW	unused_DMA_FSM_write_status: Unused
1:0	0h RO	DMA_FSM_write_status: DMA FSM Write state: 0)Idle -- 1)req -- 2)Next line

15.8.538 reg_isp_dma_DMA_FSM_Ctrl_dev_idx_type
(isp dma DMA FSM Ctrl dev idx)—Offset 42110h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Ctrl_dev_idx: [ISPMADR] + 42110h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Pack_cnt_Yb					DMA_FSM_Pack_cnt_Yb			

October 2018
Document Number: 538136, Rev. 4.3



15.8.540 reg_isp_dma_DMA_FSM_Request_cnt_Yb_type (isp_dma_DMA_FSM_Request_cnt_Yb)—Offset 42118h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Request_cnt_Yb: [ISPMMAADR] + 42118h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Request_cnt_Yb					DMA_FSM_Request_cnt_Yb			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Request_cnt_Yb: Unused
15:0	0h RO	DMA_FSM_Request_cnt_Yb: DMA FSM request counter height (Yb)

15.8.541 reg_isp_dma_DMA_FSM_Write_cnt_Y_type (isp_dma_DMA_FSM_Write_cnt_Y)—Offset 4211Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Write_cnt_Y: [ISPMMAADR] + 4211Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_FSM_Ctrl_req_addr								

15.8.543 reg_isp_dma_DMA_FSM_Pack_req_cnt_Xb_type
(isp_dma_DMA_FSM_Pack_req_cnt_Xb)—Offset 42214h

Intel Atom® Processor E3800 Product Family
Datasheet
1496



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Pack_req_cnt_Xb: [ISPMMAADR] + 42214h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Pack_req_cnt_Xb				DMA_FSM_Pack_req_cnt_Xb				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Pack_req_cnt_Xb: Unused
15:0	0h RO	DMA_FSM_Pack_req_cnt_Xb: DMA FSM pack request counter width (Xb)

15.8.544 reg_isp_dma_DMA_FSM_Request_cnt_Xb_type (isp_dma_DMA_FSM_Request_cnt_Xb)—Offset 42218h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Request_cnt_Xb: [ISPMMAADR] + 42218h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Request_cnt_Xb: Unused
15:0	0h RO	DMA_FSM_Request_cnt_Xb: DMA FSM Request counter width (Xb)

15.8.545 reg_isp_dma_DMA_FSM_Write_cnt_Xb_type (isp_dma_DMA_FSM_Write_cnt_Xb)—Offset 4221Ch

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Write_cnt_Xb: [ISPMMAADR] + 4221Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Write_cnt_Xb: Unused



Bit Range	Default & Access	Description
15:0	0h RO	DMA_FSM_Write_cnt_Xb: DMA FSM Write counter width (Xb)

15.8.546 reg_isp_dma_DMA_FSM_Ctrl_req_stride_type
(isp_dma_DMA_FSM_Ctrl_req_stride)—Offset 42310h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Ctrl_req_stride: [ISPMMAADR] + 42310h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_FSM_Ctrl_req_stride								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_FSM_Ctrl_req_stride: DMA FSM Control request stride

15.8.547 reg_isp_dma_DMA_FSM_Pack_wr_cnt_Xb_type
(isp_dma_DMA_FSM_Pack_wr_cnt_Xb)—Offset 42314h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Pack_wr_cnt_Xb: [ISPMMAADR] + 42314h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Pack_wr_cnt_Xb				DMA_FSM_Pack_wr_cnt_Xb				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Pack_wr_cnt_Xb: Unused
15:0	0h RO	DMA_FSM_Pack_wr_cnt_Xb: DMA FSM pack write counter width (Xb)

15.8.548 reg_isp_dma_DMA_FSM_Req_remining_Xb_type (isp_dma_DMA_FSM_Req_remining_Xb)—Offset 42318h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Req_remining_Xb: [ISPMADDR] + 42318h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Req_remining_Xb				DMA_FSM_Req_remining_Xb				



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Req_remining_Xb: Unused
15:0	0h RO	DMA_FSM_Req_remining_Xb: DMA FSM Request counter remaining word width

15.8.549 **reg_isp_dma_DMA_FSM_Wr_remining_Xb_type**
(isp_dma DMA FSM Wr remining Xb)—Offset 4231Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Wr_remining_Xb: [ISPMADR] + 4231Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Wr_remining_Xb				DMA_FSM_Wr_remining_Xb				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Wr_remining_Xb: Unused
15:0	0h RO	DMA_FSM_Wr_remining_Xb: DMA FSM Write counter remaining word width

15.8.550 reg_isp_dma_DMA_FSM_Ctrl_req_Xb_type
(isp_dma DMA FSM Ctrl req Xb)—Offset 42410h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Ctrl_req_Xb: [ISPMADR] + 42410h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
unused_DMA_FSM_Req_burst_cnt																DMA_FSM_Req_burst_cnt																			

October 2018
Document Number: 538136, Rev. 4.3

15.8.552 reg_isp_dma_DMA_FSM_Wr_burst_cnt_type
(isp_dma_DMA_FSM_Wr_burst_cnt)—Offset 4241Ch



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Ctrl_Pack_req_dev_idx: [ISPMADR] + 42610h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]



Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Ctrl_Wr_stride: [ISPMMAADR] + 42910h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_FSM_Ctrl_Wr_stride								

Bit Range	Default & Access	Description
31:0	0h RO	DMA_FSM_Ctrl_Wr_stride: DMA FSM Control write stride

15.8.558 reg_isp_dma_DMA_FSM_Ctrl_pack_req_Xb_type
(isp_dma_DMA_FSM_Ctrl_pack_req_Xb)—Offset 42A10h

Type: Memory Mapped I/O Register
(Size: 32 bits)


isp_dma_DMA_FSM_Ctrl_pack_req_Xb: [ISPMADR] + 42A10h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h



Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Ctrl_pack_req_Xb: Unused
15:0	0h RO	DMA_FSM_Ctrl_pack_req_Xb: DMA FSM Control FSM Pack request width (Xb)

15.8.559 reg_isp_dma_DMA_FSM_Ctrl_pack_Yb_type (isp_dma_DMA_FSM_Ctrl_pack_Yb)—Offset 42B10h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Ctrl_pack_Yb: [ISPMADDR] + 42B10h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Ctrl_pack_Yb: Unused



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Ctrl_pack_wr_Xb: Unused
15:0	0h RO	DMA_FSM_Ctrl_pack_wr_Xb: DMA FSM Control FSM Pack write width (Xb)

15.8.561 reg_isp_dma_DMA_FSM_Ctrl_pack_req_elem_type
(isp_dma_DMA_FSM_Ctrl_pack_req_elem)—Offset 42D10h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h





Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id: [ISPMADR]
+ 42F10h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id								ctrl_id
								RSVD0
								sign

Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id: Unused
4	0h RO	ctrl_id: Controller ID
3:1	0b RO	RSVD0: Reserved
0	0h RO	sign: element sign(1)/zero(0) extension



15.8.564 reg_isp_dma_Dev_Interf_0_req_side_type (isp_dma_Dev_Interf_0_req_side)—Offset 43000h

DMA Device interface 0 internal side status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_Dev_Interf_0_req_side: [ISPMMAADR] + 43000h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_Dev_Interf_0_req_side								ack_flag
								run_flag
								we_n_flag
								cs_flag

Bit Range	Default & Access	Description
31:4	0h RW	unused_Dev_Interf_0_req_side: Unused
3	0h RO	ack_flag: Ack flag
2	0h RO	run_flag: Run flag
1	0h RO	we_n_flag: We_n flag
0	0h RO	cs_flag: CS flag

15.8.565 reg_isp_dma_Dev_Interf_1_req_side_type (isp_dma_Dev_Interf_1_req_side)—Offset 43004h

DMA Device interface 1 internal side status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma_Dev_Interf_1_req_side: [ISPMMAADR] + 43004h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000006h





Bit Range	Default & Access	Description
31:4	0h RW	unused_Dev_Interf_2_req_side: Unused
3	0h RO	ack_flag: Ack flag
2	1h RO	run_flag: Run flag
1	1h RO	we_n_flag: We_n flag
0	0h RO	cs_flag: CS flag

15.8.567 reg_isp_dma_Dev_Interf_0_snd_side_type
(isp_dma_Dev_Interf_0_snd_side)—Offset 43100h

DMA Device interface 0 output side status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isp_dma Dev Interf 0 snd side: [ISPMADR] + 43100h


ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000004h

[illegible]


Bit Range	Default & Access	Description
31:4	0h RW	unused_Dev_Interf_0_snd_side: Unused
3	0h RO	ack_flag: Ack flag
2	1h RO	run_flag: Run flag
1	0h RO	we_n_flag: We_n flag
0	0h RO	cs_flag: CS flag



15.8.570 reg_isp_dma_Dev_Interf_0_Fifo_status_type
(isp dma Dev Interf 0 Fifo status)—Offset 43200h

Default: 00000004h





15.8.572 reg_isp_dma_Dev_Interf_2_Fifo_status_type
(isp_dma_Dev_Interf_2_Fifo_status)—Offset 43208h

Default: 00000004h





Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_Dev_Interf_2_Req_complete_bust								
Dev_Interf_2_Req_complete_bust								

Bit Range	Default & Access	Description
31:1	0h RW	unused_Dev_Interf_2_Req_complete_burst: Unused
0	0h RW	Dev_Interf_2_Req_complete_burst: DMA Device interface 2 Request only complete burst

15.8.576 reg_isp_dma_Dev_Interf_2_Max_burst_Size_type
(isp_dma_Dev_Interf_2_Max_burst_Size)—Offset 43408h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h



Default: 0000007Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	1	1
unused_Dev_Interf_2_Max_burst_Size							Dev_Interf_2_Max_burst_Size	

Bit Range	Default & Access	Description
31:8	0h RW	unused_Dev_Interf_2_Max_burst_Size: Unused
7:0	7Fh RW	Dev_Interf_2_Max_burst_Size: DMA Device interface 2 max burst size

15.8.577 reg_gdc1_reg0_type (gdc1_reg0)—Offset 50000h

Status register: Current opx, opy, top-level FSM state

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_reg0: [ISPMADDR] + 50000h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_reg0	OPX			not_used1	OPY			FSM0_state

Bit Range	Default & Access	Description
31:30	0h RW	unused_reg0: Unused
29:17	0h RO	OPX: OPX value
16:14	0h RO	not_used1: N/A



Access Method

gdc1_woi_x: [ISPMADR] + 50004h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_wol_x						wol_x		

15.8.579 `reg_gdc1_woi_y_type (gdc1_woi_y)`—Offset 50008h

Access Method

qdc1 woi y: [ISPMMADR] + 50008h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_woi_y							woi_y	



Bit Range	Default & Access	Description
31:6	0h RW	unused_woi_y: Unused
5:0	0h RO	woi_y: Configured Y dimension of the internal window-of-interest (local memory)

15.8.580 reg_gdc1_bpp type (gdc1_bpp)—Offset 5000Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

qdc1 bpp: [ISPMADR] + 5000Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_bpp								bpp

Bit Range	Default & Access	Description
31:4	0h RW	unused_bpp: Unused
3:0	0h RW	bpp: Bits per input/output pixel, allowed: 8, 10, 12, 14

15.8.581 `reg_gdc1_fryipxfrx_start_type (gdc1_fryipxfrx_start)`—Offset 50010h

Fractional component of the starting X and Y position for scaling given in fixed point notation

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_fryipxfrx_start: [ISPMADR] + 50010h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h




Bit Range	Default & Access	Description
31:26	0h RW	unused_fryipxfrx_start: Unused
25:16	0h RW	fry: Fractional component of the Y start
15:0	0h RW	ipxfrx: Integer (6) and Fractional (10) component of the X start

15.8.582 reg_gdc1_oxdim_type (gdc1_oxdim)—Offset 50014h

Bit Range	Default & Access	Description
31:13	0h RW	unused_oxdim: Unused
12:0	0h RW	oxdim: Output X dimension of the produced block of pixels

15.8.583 reg_gdc1_oydim_type (gdc1_oydim)—Offset 50018h

ISPMMADR Reference: [B:0, D:3, F:0] + 10h



Bit Range	Default & Access	Description
31:12	0h RW	unused_oydim: Unused
11:0	0h RW	oydim: Output Y dimension of the produced block of pixels

Access Method

gdc1_src_addr: [ISPMADR] + 5001Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:25	0h RW	unused_src_addr: Unused
24:0	0h RW	src_addr: Source (input) pixel base address [byte-based]

Access Method

gdc1_src_end: [ISPMADDR] + 50020h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:25	0h RW	unused_src_end: Unused
24:0	0h RW	src_end: End address. When reached wrap around. [byte-based]

15.8.586 reg_gdc1_src_wrap_type (gdc1_src_wrap)—Offset 50024h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_src_wrap: [ISPMADR] + 50024h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:25	0h RW	unused_src_wrap: Unused
24:0	0h RW	src_wrap: Wrap addr. Wrap here when src_end reached [byte-based]

15.8.587 reg_gdc1_src_stride_type (gdc1_src_stride)—Offset 50028h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_src_stride: [ISPMADR] + 50028h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_src_stride				src_stride				

Bit Range	Default & Access	Description
31:19	0h RW	unused_src_stride: Unused
18:0	0h RW	src_stride: Source (input) pixel stride [byte-based]

15.8.588 reg_gdc1_dst_addr_type (gdc1_dst_addr)—Offset 5002Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_dst_addr: [ISPMADR] + 5002Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_dst_addr				dst_addr				

Bit Range	Default & Access	Description
31:25	0h RW	unused_dst_addr: Unused
24:0	0h RW	dst_addr: Destination (output) pixel base address [byte-based]

15.8.589 `reg_gdc1_dst_stride_type (gdc1_dst_stride)`—Offset 50030h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_dst_stride: [ISPMADR] + 50030h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:19	0h RW	unused_dst_stride: Unused
18:0	0h RW	dst_stride: Destination (output) pixel stride [byte-based]

15.8.590 reg_gdc1_dx_type (gdc1_dx)—Offset 50034h

Default: 00000000h

Bit Range	Default & Access	Description
31:14	0h RW	unused_dx: Unused
13:0	0h RW	dx: Scaling only: Horizontal scaling factor

15.8.591 reg_gdc1_dy_type (gdc1_dy)—Offset 50038h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_dy					dy			

Bit Range	Default & Access	Description
31:14	0h RW	unused_dy: Unused
13:0	0h RW	dy: Scaling only: Vertical scaling factor

15.8.592 `reg_gdc1_P0_primX_ixdim_type (gdc1_P0_primX_ixdim) -`
Offset 5003Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

qdc1_P0_primX_ixdim: [ISPMMADR] + 5003Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_P0_primX_idxlim				P0_primX_idxlim				

Bit Range	Default & Access	Description
31:23	0h RW	unused_P0_primX_ixdim: Unused
22:0	0h RW	P0_primX_ixdim: P0(X) Tetragon mode: top-left coordinate (X), Scaling mode: dimension of the input region (X), fixed point notation, 13.10

15.8.593 `reg_gdc1_P0_primY_iydim_type (gdc1_P0_primY_iydim)–`
Offset 50040h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_P0_primY_iydim: [ISPMMADR] + 50040h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:22	0h RW	unused_P0_primY_iydim: Unused
21:0	0h RW	P0_primY_iydim: P0(Y) Tetragon mode: top-left coordinate (Y), Scaling mode: dimension of the input region (Y), fixed point notation, 12.10

15.8.594 reg_gdc1_P1_primX_type (gdc1_P1_primX)—Offset 50044h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_P1_primX: [ISPMADDR] + 50044h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:23	0h RW	unused_P1_primX: Unused
22:0	0h RW	P1_primX: P1(X) Tetragon mode only: top-right coordinate (X), fixed point notation, 13.10

15.8.595 reg_gdc1_P1_primY_type (gdc1_P1_primY)—Offset 50048h

Access Method

Intel Atom® Processor E3800 Product Family
Datasheet
1531



gdc1_P2_primY: [ISPMADR] + 50050h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_P2_primY				P2_primY				

Bit Range	Default & Access	Description
31:22	0h RW	unused_P2_primY: Unused
21:0	0h RW	P2_primY: P2(Y) Tetragon mode only: bottom-left coordinate (Y), fixed point notation 12.10

15.8.598 reg_gdc1_P3_primX_type (gdc1_P3_primX)—Offset 50054h

Access Method

gdc1_P3_primX: [ISPMADR] + 50054h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_P3_primX				P3_primX				

Bit Range	Default & Access	Description
31:23	0h RW	unused_P3_primX: Unused
22:0	0h RW	P3_primX: P3(X) Tetragon mode only: bottom-right coordinate (X), fixed point notation, 13.10

15.8.599 reg_gdc1_P3_primY_type (gdc1_P3_primY)—Offset 50058h

Access Method



15.8.601 reg_gdc1_interp_type_type (gdc1_interp_type)—Offset 50060h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_interp_type: [ISPMMAADR] + 50060h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_interp_type								interp_type

Bit Range	Default & Access	Description
31:2	0h RW	unused_interp_type: Unused
1:0	0h RW	interp_type: Type of interpolation: 00=NND ; 01=BLI ; 10=BCI ; 11=LUT

15.8.602 reg_gdc1_scan_mode_type (gdc1_scan_mode)—Offset 50064h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_scan_mode: [ISPMMAADR] + 50064h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_scan_mode								scan_mode

Bit Range	Default & Access	Description
31:1	0h RW	unused_scan_mode: Unused
0	0h RW	scan_mode: Scanning mode: 0 = STB (Slide To Bottom) ; 1 = STR (Slide To Right)



15.8.603 reg_gdc1_proc_mode_type (gdc1_proc_mode)—Offset 50068h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc1_proc_mode: [ISPMMAADR] + 50068h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_proc_mode								proc_mode

Bit Range	Default & Access	Description
31:1	0h RW	unused_proc_mode: Unused
0	0h RW	proc_mode: Processing mode: 0 = Rectangular-based scaling ; 1 = Tetragon-based scaling

15.8.604 reg_gdc2_reg0_type (gdc2_reg0)—Offset 60000h

Status register: Current opx, opy, top-level FSM state

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc2_reg0: [ISPMMAADR] + 60000h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg0	OPX				not_used1	OPY		FSM0_state

Bit Range	Default & Access	Description
31:30	0h RW	unused_reg0: Unused
29:17	0h RO	OPX: OPX value

15.8.605 reg_gdc2_woi_x_type (gdc2_woi_x)—Offset 60004h

Bit Range	Default & Access	Description
16:14	0h RO	not_used1: N/A
13:2	0h RO	OPY: OPY value
1:0	0h RO	FSM0_state: FSM0 state: 00=Idle ; 01=Busy-receiving data needed to kick the device ; 10=Busy-wait state ; 11=Busy-run state

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc2_woi_x: [ISPMADR] + 60004h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_wol_x						wol_x		

Bit Range	Default & Access	Description
31:12	0h RW	unused_woi_x: Unused
11:0	0h RO	woi_x: Configured X dimension of the internal window-of-interest (local memory)

15.8.606 reg_gdc2_woi_y_type (gdc2_woi_y)—Offset 60008h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc2_woi_y: [ISPMADR] + 60008h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_woi_y							woi_y	



Bit Range	Default & Access	Description
31:6	0h RW	unused_woi_y: Unused
5:0	0h RO	woi_y: Configured Y dimension of the internal window-of-interest (local memory)

15.8.607 reg_gdc2_bpp type (gdc2 bpp)—Offset 6000Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc2_bpp: [ISPMADR] + 6000Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_bpp								bpp

Bit Range	Default & Access	Description
31:4	0h RW	unused_bpp : Unused
3:0	0h RW	bpp : Bits per input/output pixel, allowed: 8, 10, 12, 14

15.8.608 `reg_gdc2_fryipxfrx_start_type (gdc2_fryipxfrx_start)`—Offset 60010h

Fractional component of the starting X and Y position for scaling given in fixed point notation

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc2_fryipxfrx_start: [ISPMADR] + 60010h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h




Bit Range	Default & Access	Description
31:26	0h RW	unused_fryipxfrx_start: Unused
25:16	0h RW	fry: Fractional component of the Y start
15:0	0h RW	ipxfrx: Integer (6) and Fractional (10) component of the X start

15.8.609 reg_gdc2_oxdim_type (gdc2_oxdim)—Offset 60014h

Bit Range	Default & Access	Description
31:13	0h RW	unused_oxdim: Unused
12:0	0h RW	oxdim: Output X dimension of the produced block of pixels

15.8.610 reg_gdc2_oydim_type (gdc2_oydim)—Offset 60018h

ISPMMADR Reference: [B:0, D:3, F:0] + 10h



Bit Range	Default & Access	Description
31:12	0h RW	unused_oydim: Unused
11:0	0h RW	oydim: Output Y dimension of the produced block of pixels

Access Method

gdc2_src_addr: [ISPMADR] + 6001Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:25	0h RW	unused_src_addr: Unused
24:0	0h RW	src_addr: Source (input) pixel base address [byte-based]

Access Method

gdc2_src_end: [ISPMADDR] + 60020h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:25	0h RW	unused_src_end: Unused
24:0	0h RW	src_end: End address. When reached wrap around. [byte-based]

15.8.613 reg_gdc2_src_wrap_type (gdc2_src_wrap)—Offset 60024h

Access Method

gdc2_src_wrap: [ISPMADR] + 60024h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:25	0h RW	unused_src_wrap: Unused
24:0	0h RW	src_wrap: Wrap addr. Wrap here when src_end reached [byte-based]

15.8.614 reg_gdc2_src_stride_type (gdc2_src_stride)—Offset 60028h

Access Method

gdc2_src_stride: [ISPMADR] + 60028h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		
unused_src_stride src_stride		
Bit Range	Default & Access	Description
31:19	0h RW	unused_src_stride: Unused
18:0	0h RW	src_stride: Source (input) pixel stride [byte-based]

15.8.615 reg_gdc2_dst_addr_type (gdc2_dst_addr)—Offset 6002Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc2_dst_addr: [ISPMADR] + 6002Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

312824201612840																															
0000				0000				00000				00000				00000				00000				00000							
unused_dst_addr								dst_addr																							

Bit Range	Default & Access	Description
31:25	0h RW	unused_dst_addr: Unused
24:0	0h RW	dst_addr: Destination (output) pixel base address [byte-based]

15.8.616 reg gdc2 dst stride type (gdc2 dst stride)—Offset 60030h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc2_dst_stride: [ISPMADR] + 60030h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:19	0h RW	unused_dst_stride: Unused
18:0	0h RW	dst_stride: Destination (output) pixel stride [byte-based]

15.8.617 reg_gdc2_dx_type (gdc2_dx)—Offset 60034h

Default: 00000000h

Bit Range	Default & Access	Description
31:14	0h RW	unused_dx: Unused
13:0	0h RW	dx: Scaling only: Horizontal scaling factor

15.8.618 reg_gdc2_dy_type (gdc2_dy)—Offset 60038h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_dy: Unused
13:0	0h RW	dy: Scaling only: Vertical scaling factor

15.8.619 `reg_gdc2_P0_primX_ixdim_type (gdc2_P0_primX_ixdim)–`
Offset 6003Ch

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Bit Range	Default & Access	Description
31:23	0h RW	unused_P0_primX_ixdim: Unused
22:0	0h RW	P0_primX_ixdim: P0(X) Tetragon mode: top-left coordinate (X), Scaling mode: dimension of the input region (X), fixed point notation, 13.10

15.8.620 reg_gdc2_P0_primY_iydim_type (gdc2_P0_primY_iydim)–
Offset 60040h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:22	0h RW	unused_P0_primY_iydim: Unused
21:0	0h RW	P0_primY_iydim: P0(Y) Tetragon mode: top-left coordinate (Y), Scaling mode: dimension of the input region (Y), fixed point notation, 12.10

15.8.621 reg_gdc2_P1_primX_type (gdc2_P1_primX)—Offset 60044h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc2_P1_primX: [ISPMADDR] + 60044h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:23	0h RW	unused_P1_primX: Unused
22:0	0h RW	P1_primX: P1(X) Tetragon mode only: top-right coordinate (X), fixed point notation, 13.10

15.8.622 reg_gdc2_P1_primY_type (gdc2_P1_primY)—Offset 60048h

Access Method



gdc2_P2_primY: [ISPMADR] + 60050h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_P2_primY				P2_primY				

Bit Range	Default & Access	Description
31:22	0h RW	unused_P2_primY: Unused
21:0	0h RW	P2_primY: P2(Y) Tetragon mode only: bottom-left coordinate (Y), fixed point notation 12.10

15.8.625 reg_gdc2_P3_primX_type (gdc2_P3_primX)—Offset 60054h

Access Method

gdc2_P3_primX: [ISPMMADR] + 60054h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_P3_primX				P3_primX				

Bit Range	Default & Access	Description
31:23	0h RW	unused_P3_primX: Unused
22:0	0h RW	P3_primX: P3(X) Tetragon mode only: bottom-right coordinate (X), fixed point notation, 13.10

15.8.626 reg_gdc2_P3_primY_type (gdc2_P3_primY)—Offset 60058h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:2	0h RW	unused_interp_type: Unused
1:0	0h RW	interp_type: Type of interpolation: 00=NND ; 01=BLI ; 10=BCI ; 11=LUT

15.8.629 reg_gdc2_scan_mode_type (gdc2_scan_mode)—Offset 60064h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:1	0h RW	unused_scan_mode: Unused
0	0h RW	scan_mode: Scanning mode: 0 = STB (Slide To Bottom) ; 1 = STR (Slide To Right)

15.8.630 reg_gdc2_proc_mode_type (gdc2_proc_mode)—Offset 60068h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

gdc2_proc_mode: [ISPMADR] + 60068h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	proc_mode
unused_proc_mode									

Bit Range	Default & Access	Description
31:1	0h RW	unused_proc_mode: Unused
0	0h RW	proc_mode: Processing mode: 0 = Rectangular-based scaling ; 1 = Tetragon-based scaling

15.8.631 reg_data_out_sys_c_mmu_MMU_invalidate_cache_type
(data_out_sys_c_mmu_MMU_invalidate_cache)–Offset
70000h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
data_out_sys_c_mmu_MMU_invalidate_cache: [ISPMADR]
+ 70000h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	MMU_invalidate_cache
unused_MMU_invalidate_cache									



Type: Memory Mapped I/O Register
(Size: 32 bits)

```
data_out_sys_c_mmu_MMU_page_table_base: [ISPMADR]
+ 70004h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_MMU_page_table_base				MMU_page_table_base				

Bit Range	Default & Access	Description
31:24	0h RW	unused_MMU_page_table_base: Unused
23:0	0h RW	MMU_page_table_base: Defines the physical page number of the page tables

15.8.633 `reg_inp_sys_csi_receiver_csi1_dev_ready_type`
(`inp_sys_csi_receiver_csi1_dev_ready`)—Offset 80100h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi1_dev_ready: [ISPMMAADR] + 80100h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
1550



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi1_dev_ready							mask_data_id_err	mask_ecc_double_bit_err
							mask_rx_data_timeout_err	mask_sot_sync_err
							mask_overrun_err	mask_init_time_out_err
							reserved_1	device_ready

Bit Range	Default & Access	Description
31:8	0h RW	unused_csi1_dev_ready: Unused
7	0h RW	mask_data_id_err: Set to mask error recovery when data ID error is detected
6	0h RW	mask_ecc_double_bit_err: Set to mask error recovery when ECC double bit error is detected
5	0h RW	mask_rx_data_timeout_err: Set to mask error recovery when receive data time out error is detected
4	0h RW	mask_sot_sync_err: Set to mask error recovery when start of transmission sync error is detected
3	0h RW	mask_overrun_err: set to mask overrun: NOT used now, can be discarded
2	0h RW	mask_init_time_out_err: Set to mask error recovery when initialization time out error is detected
1	0h RO	reserved_1: Reserved
0	0h RW	device_ready: Set to indicate that device is ready for reception

15.8.634 reg_inp_sys_csi_receiver_csi1_int_status_type (inp_sys_csi_receiver_csi1_int_status)—Offset 80104h

Interrupt Status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi1_int_status: [ISPMMADR] + 80104h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi1_int_status				err_line_sync	err_escape	err_data_timeout	err_frame_data	err_frame_sync
				err_id	err_crc	no_ecc_err	err_ecc_corr	err_ecc_double
					err_control	err_sot_sync_hs	err_sot_hs	sleep_mode_exit
								sleep_mode_entry
								err_init_timeout
								reserved_0

Bit Range	Default & Access	Description
31:17	0h RW	unused_csi1_int_status: Unused
16	0h RW/1C	err_line_sync: Set if line number for line start and line end packets do not match
15	0h RW/1C	err_escape: Set if an unrecognised escape entry command is received
14	0h RW/1C	err_data_timeout: Set if time taken to receive a packet exceeds programmed timeout value
13	0h RW/1C	err_frame_data: Set if data packets within a frame has errors
12	0h RW/1C	err_frame_sync: Set if frame start is not paired with frame end for same virtual channel
11	0h RW/1C	err_id: Set if packet header has a unrecognised data id
10	0h RW/1C	err_crc: Set if computed CRC differs from received value
9	0h RW/1C	no_ecc_err: Set if no ECC error detected in packet
8	0h RW/1C	err_ecc_corr: Set if ECC error detected and corrected for one bit
7	0h RW/1C	err_ecc_double: Set if ECC error detected for two or more bits
6	0h RW/1C	err_control: Set if DPHY flags a control error
5	0h RW/1C	err_sot_sync_hs: Set if DPHY flags start of transmission synchronisation error
4	0h RW/1C	err_sot_hs: Set if DPHY flags start of transmission error
3	0h RW/1C	sleep_mode_exit: Set if DPHY exits ultra low power state
2	0h RW/1C	sleep_mode_entry: Set if DPHY enters ultra low power state
1	0h RW/1C	err_init_timeout: Set if Initialization timeout error occurs on DPHY data lanes
0	0h RO	reserved_0: Always set to 0



15.8.635 reg_inp_sys_csi_receiver_csi1_int_enable_type (inp_sys_csi_receiver_csi1_int_enable)—Offset 80108h

Interrupt Enable

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi1_int_enable: [ISPMADDR] + 80108h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi1_int_enable				err_line_sync	err_escape	err_data_timeout	err_frame_data	err_frame_sync
				err_id	err_crc	no_ecc_err	err_ecc_corr	err_ecc_double
				err_control	err_sot_sync_hs	err_sot_hs	sleep_mode_exit	sleep_mode_entry
							err_init_timeout	overrun

Bit Range	Default & Access	Description
31:17	0h RW	unused_csi1_int_enable: Unused
16	0h RW	err_line_sync: Enable line sync error interrupt
15	0h RW	err_escape: Enable escape entry error interrupt
14	0h RW	err_data_timeout: Enable timeout error interrupt
13	0h RW	err_frame_data: Enable frame data error interrupt
12	0h RW	err_frame_sync: Enable frame sync error interrupt
11	0h RW	err_id: Enable data id error interrupt
10	0h RW	err_crc: Enable CRC error interrupt
9	0h RW	no_ecc_err: Enable no ECC error interrupt
8	0h RW	err_ecc_corr: Enable ECC error detected and corrected for one bit interrupt
7	0h RW	err_ecc_double: Enable ECC error detected for two or more bits interrupt
6	0h RW	err_control: Enable control error interrupt





Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp_sys_csi_receiver_csi_backend_ls_dvalid: [ISPMADR] +  
80120h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_is_dvalid								csi_backend_is_dvalid

Intel Atom® Processor E3800 Product Family
Datasheet
1556



Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp_sys_csi_receiver_csi_backend_fe_fs: [ISPMADR] +  
8012Ch
```

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
1558



Access Method

```
inp_sys_csi_receiver_csi1_raw16_18_data_id: [ISPMADR]
+ 80138h
```

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi1_rx_cnt: [ISPMADDR] + 80140h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
rx_cnt_4lane				rx_cnt_3lane				rx_cnt_1lane

Bit Range	Default & Access	Description
31:24	FFh RW	rx_cnt_4lane: Receive count value for 4 lane
23:16	FFh RW	rx_cnt_3lane: Receive count value for 3 lane
15:8	FFh RW	rx_cnt_2lane: Receive count value for 2 lane
7:0	FFh RW	rx_cnt_1lane: Receive count value for 1 lane

15.8.648 reg_inp_sys_csi_receiver_csi_backend_rst_type (inp_sys_csi_receiver_csi_backend_rst)—Offset 80144h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_rst: [ISPMADDR] + 80144h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_rst								csi_backend_rst

Bit Range	Default & Access	Description
31:1	0h RW	unused_csi_backend_rst: Unused



Bit Range	Default & Access	Description
0	0h RW	csi_backend_rst: Reset CSI Rx backend block

15.8.649 reg_inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc0_type (inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc0)—Offset 80148h

Compression and Prediction scheme register 0 for virtual channel 0

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc0:
[ISPMMAADR] + 80148h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_comp_pred_reg0_vc0	pred_usd_type6	comp_usd_type6	pred_usd_type5	comp_usd_type5	pred_usd_type4	comp_usd_type4	pred_usd_type3	comp_usd_type3
							pred_usd_type2	comp_usd_type2
								pred_usd_type1
								comp_usd_type1

Bit Range	Default & Access	Description
31:30	0h RW	unused_csi_backend_comp_pred_reg0_vc0: Unused
29:28	0h RW	pred_usd_type6: prediction algorithm for user defined type 6 data: 1 -) pred1, 2 -) pred2
27:25	0h RW	comp_usd_type6: compression format for user defined type 6 data: value between 1 to 6
24:23	0h RW	pred_usd_type5: prediction algorithm for user defined type 5 data: 1 -) pred1, 2 -) pred2
22:20	0h RW	comp_usd_type5: compression format for user defined type 5 data: value between 1 to 6
19:18	0h RW	pred_usd_type4: prediction algorithm for user defined type 4 data: 1 -) pred1, 2 -) pred2



Access Method

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
9:8	0h RW	pred_usd_type8: prediction algorithm for user defined type 8 data: 1 -) pred1, 2 -) pred2
7:5	0h RW	comp_usd_type8: compression format for user defined type 8 data: value between 1 to 6
4:3	0h RW	pred_usd_type7: prediction algorithm for user defined type 7 data: 1 -) pred1, 2 -) pred2
2:0	0h RW	comp_usd_type7: compression format for user defined type 7 data: value between 1 to 6

15.8.651 reg_inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc1_type (inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc1)– Offset 80150h

Compression and Prediction scheme register 0 for virtual channel 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc1:
[ISPMADDR] + 80150h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_comp_pred_reg0_vc1	pred_usd_type6	comp_usd_type6	pred_usd_type5	comp_usd_type5	pred_usd_type4	comp_usd_type4	pred_usd_type3	comp_usd_type3
							pred_usd_type2	comp_usd_type2
							pred_usd_type1	comp_usd_type1

Bit Range	Default & Access	Description
31:30	0h RW	unused_csi_backend_comp_pred_reg0_vc1: Unused
29:28	0h RW	pred_usd_type6: prediction algorithm for user defined type 6 data: 1 -) pred1, 2 -) pred2
27:25	0h RW	comp_usd_type6: compression format for user defined type 6 data: value between 1 to 6



Bit Range	Default & Access	Description
24:23	0h RW	pred_usd_type5: prediction algorithm for user defined type 5 data: 1 -) pred1, 2 -) pred2
22:20	0h RW	comp_usd_type5: compression format for user defined type 5 data: value between 1 to 6
19:18	0h RW	pred_usd_type4: prediction algorithm for user defined type 4 data: 1 -) pred1, 2 -) pred2
17:15	0h RW	comp_usd_type4: compression format for user defined type 4 data: value between 1 to 6
14:13	0h RW	pred_usd_type3: prediction algorithm for user defined type 3 data: 1 -) pred1, 2 -) pred2
12:10	0h RW	comp_usd_type3: compression format for user defined type 3 data: value between 1 to 6
9:8	0h RW	pred_usd_type2: prediction algorithm for user defined type 2 data: 1 -) pred1, 2 -) pred2
7:5	0h RW	comp_usd_type2: compression format for user defined type 2 data: value between 1 to 6
4:3	0h RW	pred_usd_type1: prediction algorithm for user defined type 1 data: 1 -) pred1, 2 -) pred2
2:0	0h RW	comp_usd_type1: compression format for user defined type 1 data: value between 1 to 6

15.8.652 **reg_inp_sys_csi_receiver_csi_backend_comp_reg1_vc1_type (inp_sys_csi_receiver_csi_backend_comp_reg1_vc1)–Offset 80154h**

Compression scheme register 1 for virtual channel 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_comp_reg1_vc1:
[ISPMADDR] + 80154h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_comp_reg1_vc1						pred_usd_type8	comp_usd_type8	pred_usd_type7
								comp_usd_type7

Bit Range	Default & Access	Description
31:10	0h RW	unused_csi_backend_comp_reg1_vc1: Unused
9:8	0h RW	pred_usd_type8: prediction algorithm for user defined type 8 data: 1 -) pred1, 2 -) pred2
7:5	0h RW	comp_usd_type8: compression format for user defined type 8 data: value between 1 to 6
4:3	0h RW	pred_usd_type7: prediction algorithm for user defined type 7 data: 1 -) pred1, 2 -) pred2
2:0	0h RW	comp_usd_type7: compression format for user defined type 7 data: value between 1 to 6

15.8.653 reg_inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc2_type (inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc2)—Offset 80158h

Compression and Prediction scheme register 0 for virtual channel 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc2:
[ISPMADDR] + 80158h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)
ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_comp_pred_reg0_vc2	pred_usd_type6	comp_usd_type6	pred_usd_type5	comp_usd_type5	pred_usd_type4	comp_usd_type4	pred_usd_type3	comp_usd_type3
							pred_usd_type2	comp_usd_type2
								pred_usd_type1
								comp_usd_type1

Bit Range	Default & Access	Description
31:30	0h RW	unused_csi_backend_comp_pred_reg0_vc2: Unused
29:28	0h RW	pred_usd_type6: prediction algorithm for user defined type 6 data: 1 -) pred1, 2 -) pred2
27:25	0h RW	comp_usd_type6: compression format for user defined type 6 data: value between 1 to 6
24:23	0h RW	pred_usd_type5: prediction algorithm for user defined type 5 data: 1 -) pred1, 2 -) pred2
22:20	0h RW	comp_usd_type5: compression format for user defined type 5 data: value between 1 to 6
19:18	0h RW	pred_usd_type4: prediction algorithm for user defined type 4 data: 1 -) pred1, 2 -) pred2
17:15	0h RW	comp_usd_type4: compression format for user defined type 4 data: value between 1 to 6
14:13	0h RW	pred_usd_type3: prediction algorithm for user defined type 3 data: 1 -) pred1, 2 -) pred2
12:10	0h RW	comp_usd_type3: compression format for user defined type 3 data: value between 1 to 6
9:8	0h RW	pred_usd_type2: prediction algorithm for user defined type 2 data: 1 -) pred1, 2 -) pred2
7:5	0h RW	comp_usd_type2: compression format for user defined type 2 data: value between 1 to 6
4:3	0h RW	pred_usd_type1: prediction algorithm for user defined type 1 data: 1 -) pred1, 2 -) pred2
2:0	0h RW	comp_usd_type1: compression format for user defined type 1 data: value between 1 to 6



15.8.654 reg_inp_sys_csi_receiver_csi_backend_comp_reg1_vc2_type (inp_sys_csi_receiver_csi_backend_comp_reg1_vc2)—Offset 8015Ch

Compression scheme register 1 for virtual channel 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_comp_reg1_vc2:
[ISPMADDR] + 8015Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_comp_reg1_vc2						pred_usd_type8	comp_usd_type8	pred_usd_type7
								comp_usd_type7

Bit Range	Default & Access	Description
31:10	0h RW	unused_csi_backend_comp_reg1_vc2: Unused
9:8	0h RW	pred_usd_type8: prediction algorithm for user defined type 8 data: 1 -) pred1, 2 -) pred2
7:5	0h RW	comp_usd_type8: compression format for user defined type 8 data: value between 1 to 6
4:3	0h RW	pred_usd_type7: prediction algorithm for user defined type 7 data: 1 -) pred1, 2 -) pred2
2:0	0h RW	comp_usd_type7: compression format for user defined type 7 data: value between 1 to 6

15.8.655 reg_inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc3_type (inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc3)—Offset 80160h

Compression and Prediction scheme register 0 for virtual channel 3

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_comp_pred_reg0_vc3:
[ISPMADDR] + 80160h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0																			
unused_csi_backend_comp_pred_reg0_vc3				pred_usd_type6				comp_usd_type6				pred_usd_type5				comp_usd_type5				pred_usd_type4				comp_usd_type4				pred_usd_type3				comp_usd_type3				pred_usd_type2				comp_usd_type2				pred_usd_type1				comp_usd_type1			

Bit Range	Default & Access	Description
31:30	0h RW	unused_csi_backend_comp_pred_reg0_vc3: Unused
29:28	0h RW	pred_usd_type6: prediction algorithm for user defined type 6 data: 1 -) pred1, 2 -) pred2
27:25	0h RW	comp_usd_type6: compression format for user defined type 6 data: value between 1 to 6
24:23	0h RW	pred_usd_type5: prediction algorithm for user defined type 5 data: 1 -) pred1, 2 -) pred2
22:20	0h RW	comp_usd_type5: compression format for user defined type 5 data: value between 1 to 6
19:18	0h RW	pred_usd_type4: prediction algorithm for user defined type 4 data: 1 -) pred1, 2 -) pred2
17:15	0h RW	comp_usd_type4: compression format for user defined type 4 data: value between 1 to 6
14:13	0h RW	pred_usd_type3: prediction algorithm for user defined type 3 data: 1 -) pred1, 2 -) pred2
12:10	0h RW	comp_usd_type3: compression format for user defined type 3 data: value between 1 to 6
9:8	0h RW	pred_usd_type2: prediction algorithm for user defined type 2 data: 1 -) pred1, 2 -) pred2
7:5	0h RW	comp_usd_type2: compression format for user defined type 2 data: value between 1 to 6
4:3	0h RW	pred_usd_type1: prediction algorithm for user defined type 1 data: 1 -) pred1, 2 -) pred2



Access Method

ISPMADR Type: PCI Configuration Register (Size: 32 bits)
ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_comp_reg1_vc3								
pred_usd_type8								
comp_usd_type8								
pred_usd_type7								
comp_usd_type7								

Bit Range	Default & Access	Description
31:10	0h RW	unused_csi_backend_comp_reg1_vc3: Unused
9:8	0h RW	pred_usd_type8: prediction algorithm for user defined type 8 data: 1 -) pred1, 2 -) pred2
7:5	0h RW	comp_usd_type8: compression format for user defined type 8 data: value between 1 to 6
4:3	0h RW	pred_usd_type7: prediction algorithm for user defined type 7 data: 1 -) pred1, 2 -) pred2
2:0	0h RW	comp_usd_type7: compression format for user defined type 7 data: value between 1 to 6



15.8.657 reg_inp_sys_csi_receiver_csi_backend_raw18_reg_type (inp_sys_csi_receiver_csi_backend_raw18_reg)—Offset 80168h

Configuration register for RAW 18 data type decode

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_raw18_reg: [ISPMADDR]
+ 80168h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_raw18_reg						format_en	format_option	format_id

Bit Range	Default & Access	Description
31:9	0h RW	unused_csi_backend_raw18_reg: Unused
8	0h RW	format_en: enable RAW 18 type decode
7:6	0h RW	format_option: format option for RAW 18 data type: 3 options possible (1,2,3)
5:0	0h RW	format_id: data id for RAW 18

15.8.658 reg_inp_sys_csi_receiver_csi_backend_force_raw8_reg_type (inp_sys_csi_receiver_csi_backend_force_raw8_reg)—Offset 8016Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_force_raw8_reg:
[ISPMADDR] + 8016Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_backend_raw16_reg: [ISPMADR]
+ 80170h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_backend_raw16_reg						format_en	format_option	format_id



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi2_dev_ready: [ISPMADR] + 80200h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi2_dev_ready								mask_data_id_err
								mask_ecc_double_bit_err
								mask_rx_data_timeout_err
								mask_sot_sync_err
								mask_overrun_err
								mask_init_time_out_err
								reserved_1
								device_ready

Bit Range	Default & Access	Description
31:8	0h RW	unused_csi2_dev_ready: Unused
7	0h RW	mask_data_id_err: Set to mask error recovery when data ID error is detected
6	0h RW	mask_ecc_double_bit_err: Set to mask error recovery when ECC double bit error is detected
5	0h RW	mask_rx_data_timeout_err: Set to mask error recovery when receive data time out error is detected
4	0h RW	mask_sot_sync_err: Set to mask error recovery when start of transmission sync error is detected
3	0h RW	mask_overrun_err: set to mask overrun: NOT used now, can be discarded



Bit Range	Default & Access	Description
2	0h RW	mask_init_time_out_err: Set to mask error recovery when initialization time out error is detected
1	0h RO	reserved_1: Reserved
0	0h RW	device_ready: Set to indicate that device is ready for reception

15.8.661 reg_inp_sys_csi_receiver_csi2_int_status_type
(inp_sys_csi_receiver_csi2_int_status)—Offset 80204h

Interrupt Status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp sys csi receiver csi2 int status: [ISPMADR] + 80204h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:17	0h RW	unused_csi2_int_status: Unused
16	0h RW/1C	err_line_sync: Set if line number for line start and line end packets do not match
15	0h RW/1C	err_escape: Set if an unrecognised escape entry command is received
14	0h RW/1C	err_data_timeout: Set if time taken to receive a packet exceeds programmed timeout value
13	0h RW/1C	err_frame_data: Set if data packets within a frame has errors
12	0h RW/1C	err_frame_sync: Set if frame start is not paired with frame end for same virtual channel
11	0h RW/1C	err_id: Set if packet header has a unrecognised data id
10	0h RW/1C	err_crc: Set if computed CRC differs from received value



Access Method

inp_sys_csi_receiver_csi2_int_enable: [ISPMADR] + 80208h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:17	0h RW	unused_csi2_int_enable: Unused



Bit Range	Default & Access	Description
16	0h RW	err_line_sync: Enable line sync error interrupt
15	0h RW	err_escape: Enable escape entry error interrupt
14	0h RW	err_data_timeout: Enable timeout error interrupt
13	0h RW	err_frame_data: Enable frame data error interrupt
12	0h RW	err_frame_sync: Enable frame sync error interrupt
11	0h RW	err_id: Enable data id error interrupt
10	0h RW	err_crc: Enable CRC error interrupt
9	0h RW	no_ecc_err: Enable no ECC error interrupt
8	0h RW	err_ecc_corr: Enable ECC error detected and corrected for one bit interrupt
7	0h RW	err_ecc_double: Enable ECC error detected for two or more bits interrupt
6	0h RW	err_control: Enable control error interrupt
5	0h RW	err_sot_sync_hs: Enable start of transmission synchronisation error interrupt
4	0h RW	err_sot_hs: Enable start of transmission error interrupt
3	0h RW	sleep_mode_exit: Enable sleep mode exit interrupt
2	0h RW	sleep_mode_entry: Enable sleep mode entry interrupt
1	0h RW	err_init_timeout: Enable Initialization timeout error interrupt
0	0h RW	overrun: Enable FIFO overrun interrupt: NOT available now, can be discarded

15.8.663 **reg_inp_sys_csi_receiver_csi2_func_prg_type** (inp_sys_csi_receiver_csi2_func_prg)—Offset 8020Ch

Functional Programming

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi2_func_prg: [ISPMADDR] + 8020Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 0007FFFFh





Bit Range	Default & Access	Description
7:0	0h RW	init_timer_reg_0: Byte 0 for power up timer

15.8.665 reg_inp_sys_csi_receiver_csi2_raw16_18_data_id_type
(inp_sys_csi_receiver_csi2_raw16_18_data_id)—Offset
80238h

RAW 16 and RAW 18 data ID register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp_sys_csi_receiver_csi2_raw16_18_data_id: [ISPMADR]
+ 80238h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi2_raw16_18_data_id				reserved_1514	raw18		reserved_76	raw16

Bit Range	Default & Access	Description
31:16	0h RW	unused_csi2_raw16_18_data_id: Unused
15:14	0h RO	reserved_1514: Reserved
13:8	0h RW	raw18: RAW 18 data ID
7:6	0h RO	reserved_76: Reserved
5:0	0h RW	raw16: RAW 16 data ID

15.8.666 reg_inp_sys_csi_receiver_csi2_sync_cnt_type
(inp_sys_csi_receiver_csi2_sync_cnt)—Offset 8023Ch

Synchronisation count value in terms of MIPI high speed byte clock

Access Method



Default: 000000FFh

[illegible]

Bit Range	Default & Access	Description
31:8	0h RW	unused_csi2_sync_cnt: Unused
7:0	FFh RW	sync_cnt_1lane: Synchronisation count value for 1 lane

15.8.667 reg_inp_sys_csi_receiver_csi2_rx_cnt_type
(inp_sys_csi_receiver_csi2_rx_cnt)—Offset 80240h

Receive count value in terms of MIPI high speed byte clock

Access Method

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 000000FFh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
unused_csi2_rx_cnt								rx_cnt_1lane

Bit Range	Default & Access	Description
31:8	0h RW	unused_csi2_rx_cnt: Unused
7:0	FFh RW	rx_cnt_1lane: Receive count value for 1 lane



15.8.668 reg_inp_sys_csi_receiver_csi3_dev_ready_type (inp_sys_csi_receiver_csi3_dev_ready)—Offset 80300h

Set after programming operational registers to enable receiver

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi3_dev_ready: [ISPMADR] + 80300h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi3_dev_ready							mask_data_id_err	mask_data_id_err
							mask_ecc_double_bit_err	mask_ecc_double_bit_err
							mask_rx_data_timeout_err	mask_rx_data_timeout_err
							mask_sot_sync_err	mask_sot_sync_err
							mask_overrun_err	mask_overrun_err
							mask_init_time_out_err	mask_init_time_out_err
							reserved_1	reserved_1
							device_ready	device_ready

Bit Range	Default & Access	Description
31:8	0h RW	unused_csi3_dev_ready: Unused
7	0h RW	mask_data_id_err: Set to mask error recovery when data ID error is detected
6	0h RW	mask_ecc_double_bit_err: Set to mask error recovery when ECC double bit error is detected
5	0h RW	mask_rx_data_timeout_err: Set to mask error recovery when receive data time out error is detected
4	0h RW	mask_sot_sync_err: Set to mask error recovery when start of transmission sync error is detected
3	0h RW	mask_overrun_err: set to mask overrun: NOT used now, can be discarded
2	0h RW	mask_init_time_out_err: Set to mask error recovery when initialization time out error is detected
1	0h RO	reserved_1: Reserved
0	0h RW	device_ready: Set to indicate that device is ready for reception

15.8.669 reg_inp_sys_csi_receiver_csi3_int_status_type (inp_sys_csi_receiver_csi3_int_status)—Offset 80304h

Interrupt Status

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi3_int_status: [ISPMMAADR] + 80304h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi3_int_status				err_line_sync	err_escape	err_data_timeout	err_frame_data	err_frame_sync
				err_id	err_crc	no_ecc_err	err_ecc_corr	err_ecc_double
				err_control	err_sot_sync_hs	err_sot_hs	sleep_mode_exit	sleep_mode_entry
				err_init_timeout	reserved_10			

Bit Range	Default & Access	Description
31:17	0h RW	unused_csi3_int_status: Unused
16	0h RW/1C	err_line_sync: Set if line number for line start and line end packets do not match
15	0h RW/1C	err_escape: Set if an unrecognised escape entry command is received
14	0h RW/1C	err_data_timeout: Set if time taken to receive a packet exceeds programmed timeout value
13	0h RW/1C	err_frame_data: Set if data packets within a frame has errors
12	0h RW/1C	err_frame_sync: Set if frame start is not paired with frame end for same virtual channel
11	0h RW/1C	err_id: Set if packet header has a unrecognised data id
10	0h RW/1C	err_crc: Set if computed CRC differs from received value
9	0h RW/1C	no_ecc_err: Set if no ECC error detected in packet
8	0h RW/1C	err_ecc_corr: Set if ECC error detected and corrected for one bit
7	0h RW/1C	err_ecc_double: Set if ECC error detected for two or more bits
6	0h RW/1C	err_control: Set if DPHY flags a control error
5	0h RW/1C	err_sot_sync_hs: Set if DPHY flags start of transmission synchronisation error
4	0h RW/1C	err_sot_hs: Set if DPHY flags start of transmission error
3	0h RW/1C	sleep_mode_exit: Set if DPHY exits ultra low power state



Bit Range	Default & Access	Description
2	0h RW/1C	sleep_mode_entry: Set if DPHY enters ultra low power state
1	0h RW/1C	err_init_timeout: Set if Initialization timeout error occurs on DPHY data lanes
0	0h RO	reserved_10: Always set to 0

15.8.670 reg_inp_sys_csi_receiver_csi3_int_enable_type (inp_sys_csi_receiver_csi3_int_enable)—Offset 80308h

Interrupt Enable

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi3_int_enable: [ISPMADDR] + 80308h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi3_int_enable				err_line_sync	err_escape	err_data_timeout	err_frame_data	err_frame_sync
				err_id	err_crc	no_ecc_err	err_ecc_corr	err_ecc_double
				err_control	err_sot_sync_hs	err_sot_hs	sleep_mode_exit	sleep_mode_entry
				err_init_timeout	overrun			

Bit Range	Default & Access	Description
31:17	0h RW	unused_csi3_int_enable: Unused
16	0h RW	err_line_sync: Enable line sync error interrupt
15	0h RW	err_escape: Enable escape entry error interrupt
14	0h RW	err_data_timeout: Enable timeout error interrupt
13	0h RW	err_frame_data: Enable frame data error interrupt
12	0h RW	err_frame_sync: Enable frame sync error interrupt
11	0h RW	err_id: Enable data id error interrupt
10	0h RW	err_crc: Enable CRC error interrupt





Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi3_raw16_18_data_id: [ISPMMAADR]
+ 80338h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_csi3_raw16_18_data_id				reserved_1514	raw18	reserved_76	raw16	

Bit Range	Default & Access	Description
31:16	0h RW	unused_csi3_raw16_18_data_id: Unused
15:14	0h RO	reserved_1514: Reserved
13:8	0h RW	raw18: RAW 18 data ID
7:6	0h RO	reserved_76: Reserved
5:0	0h RW	raw16: RAW 16 data ID

15.8.674 reg_inp_sys_csi_receiver_csi3_sync_cnt_type (inp_sys_csi_receiver_csi3_sync_cnt)—Offset 8033Ch

Synchronisation count value in terms of MIPI high speed byte clock

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi3_sync_cnt: [ISPMMAADR] + 8033Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000FFFFh



15.8.675 reg_inp_sys_csi_receiver_csi3_rx_cnt_type
(inp_sys_csi_receiver_csi3_rx_cnt)—Offset 80340h

Access Method

inp_sys_csi_receiver_csi3_rx_cnt: [ISPMADR] + 80340h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi3_rx_cnt				rx_cnt_2lane				rx_cnt_1lane

Intel Atom® Processor E3800 Product Family
Datasheet
1587



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
unused_csi_be_gen_sh_acc_ovl								
csi_be_gen_sh_acc_ovl								

Bit Range	Default & Access	Description
31:1	0h RW	unused_csi_be_gen_sh_acc_ovl: Unused
0	0h RW	csi_be_gen_sh_acc_ovl: Allows for overruling the accept signal generated by the generic short packet FIFO, going to the CSI receiver backend.

15.8.677 **reg_inp_sys_csi_receiver_csi_sh_be_srst_type**
(inp_sys_csi_receiver_csi_sh_be_srst)—Offset 80804h

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_sh_be_srst: [ISPMADR] + 80804h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_csi_sh_be_srst							srst_be_controller	0
							srst_one_2_two_channel	0
							srst_stream_demux	0
							srst_pixel_decoder	0
							srst_stream_mux	0
							srst_pixel_formatter	0
							srst_rate_conversion_fifo	0
							srst_header_extractor	0

Bit Range	Default & Access	Description
31:8	0h RW	unused_csi_sh_be_srst: Unused
7	0h RW	srst_be_controller: Soft resets the backend controller module
6	0h RW	srst_one_2_two_channel: Soft resets the one 2 two channel module
5	0h RW	srst_stream_demux: Soft resets the stream demux module
4	0h RW	srst_pixel_decoder: Soft resets the pixel decoder module
3	0h RW	srst_stream_mux: Soft resets the stream mux module
2	0h RW	srst_pixel_formatter: Soft resets the pixel formatter module
1	0h RW	srst_rate_conversion_fifo: Soft resets the rate conversion FIFO module
0	0h RW	srst_header_extractor: Soft resets the header extractor module

15.8.678 reg_inp_sys_csi_receiver_csi_sh_be_two_ppc_type (inp_sys_csi_receiver_csi_sh_be_two_ppc)—Offset 80808h

Sets the output rate of the backend and the precision

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_sh_be_two_ppc: [ISPMADR] + 80808h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Access Method

inp_sys_csi_receiver_csi_sh_be_comp_reg_vc0:
[ISPMADR] + 8080Ch

ISPMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]

Bit Range	Default & Access	Description
31	0h RW	pred_usd_type8: prediction algorithm for vc=0, user defined type 8 data: 0 -) pred1, 1 -) pred2
30:28	0h RW	comp_usd_type8: compression format for vc=0, user defined type 8 data: value between 0 to 6. 0-no compression



Bit Range	Default & Access	Description
27	0h RW	pred_usd_type7: prediction algorithm for vc=0, user defined type 7 data: 0 -) pred1, 1 -) pred2
26:24	0h RW	comp_usd_type7: compression format for vc=0, user defined type 7 data: value between 0 to 6. 0-no compression
23	0h RW	pred_usd_type6: prediction algorithm for vc=0, user defined type 6 data: 0 -) pred1, 1 -) pred2
22:20	0h RW	comp_usd_type6: compression format for vc=0, user defined type 6 data: value between 0 to 6. 0-no compression
19	0h RW	pred_usd_type5: prediction algorithm for vc=0, user defined type 5 data: 0 -) pred1, 1 -) pred2
18:16	0h RW	comp_usd_type5: compression format for vc=0, user defined type 5 data: value between 0 to 6. 0-no compression
15	0h RW	pred_usd_type4: prediction algorithm for vc=0, user defined type 4 data: 0 -) pred1, 1 -) pred2
14:12	0h RW	comp_usd_type4: compression format for vc=0, user defined type 4 data: value between 0 to 6. 0-no compression
11	0h RW	pred_usd_type3: prediction algorithm for vc=0, user defined type 3 data: 0 -) pred1, 1 -) pred2
10:8	0h RW	comp_usd_type3: compression format for vc=0, user defined type 3 data: value between 0 to 6. 0-no compression
7	0h RW	pred_usd_type2: prediction algorithm for vc=0, user defined type 2 data: 0 -) pred1, 1 -) pred2
6:4	0h RW	comp_usd_type2: compression format for vc=0, user defined type 2 data: value between 0 to 6. 0-no compression
3	0h RW	pred_usd_type1: prediction algorithm for vc=0, user defined type 1 data: 0 -) pred1, 1 -) pred2
2:0	0h RW	comp_usd_type1: compression format for vc=0, user defined type 1 data: value between 0 to 6. 0-no compression

15.8.680 reg_inp_sys_csi_receiver_csi_sh_be_comp_reg_vc1_type (inp_sys_csi_receiver_csi_sh_be_comp_reg_vc1)—Offset 80810h

Compression scheme register for virtual channel 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_sh_be_comp_reg_vc1:
[ISPMADDR] + 80810h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)
ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

15.8.681 reg_inp_sys_csi_receiver_csi_sh_be_comp_reg_vc2_type
(inp_sys_csi_receiver_csi_sh_be_comp_reg_vc2)–Offset
80814h

Compression scheme register for virtual channel 0

31				28				24				20				16				12				8				4				0																															
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0																															
pred_usd_type8				comp_usd_type8				pred_usd_type7				comp_usd_type7				pred_usd_type6				comp_usd_type6				pred_usd_type5				comp_usd_type5				pred_usd_type4				comp_usd_type4				pred_usd_type3				comp_usd_type3				pred_usd_type2				comp_usd_type2				pred_usd_type1				comp_usd_type1			

Bit Range	Default & Access	Description
31	0h RW	pred_usd_type8: prediction algorithm for vc=1, user defined type 8 data: 0 -) pred1, 1 -) pred2
30:28	0h RW	comp_usd_type8: compression format for vc=1, user defined type 8 data: value between 0 to 6. 0-no compression
27	0h RW	pred_usd_type7: prediction algorithm for vc=1, user defined type 7 data: 0 -) pred1, 1 -) pred2
26:24	0h RW	comp_usd_type7: compression format for vc=1, user defined type 7 data: value between 0 to 6. 0-no compression
23	0h RW	pred_usd_type6: prediction algorithm for vc=1, user defined type 6 data: 0 -) pred1, 1 -) pred2
22:20	0h RW	comp_usd_type6: compression format for vc=1, user defined type 6 data: value between 0 to 6. 0-no compression
19	0h RW	pred_usd_type5: prediction algorithm for vc=1, user defined type 5 data: 0 -) pred1, 1 -) pred2
18:16	0h RW	comp_usd_type5: compression format for vc=1, user defined type 5 data: value between 0 to 6. 0-no compression
15	0h RW	pred_usd_type4: prediction algorithm for vc=1, user defined type 4 data: 0 -) pred1, 1 -) pred2
14:12	0h RW	comp_usd_type4: compression format for vc=1, user defined type 4 data: value between 0 to 6. 0-no compression
11	0h RW	pred_usd_type3: prediction algorithm for vc=1, user defined type 3 data: 0 -) pred1, 1 -) pred2
10:8	0h RW	comp_usd_type3: compression format for vc=1, user defined type 3 data: value between 0 to 6. 0-no compression
7	0h RW	pred_usd_type2: prediction algorithm for vc=1, user defined type 2 data: 0 -) pred1, 1 -) pred2
6:4	0h RW	comp_usd_type2: compression format for vc=1, user defined type 2 data: value between 0 to 6. 0-no compression
3	0h RW	pred_usd_type1: prediction algorithm for vc=1, user defined type 1 data: 0 -) pred1, 1 -) pred2
2:0	0h RW	comp_usd_type1: compression format for vc=1, user defined type 1 data: value between 0 to 6. 0-no compression



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_sh_be_comp_reg_vc2:
[ISPMADDR] + 80814h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
pred_usd_type8	comp_usd_type8	pred_usd_type7	comp_usd_type7	pred_usd_type6	comp_usd_type6	pred_usd_type5	comp_usd_type5	pred_usd_type4
								comp_usd_type4
								pred_usd_type3
								comp_usd_type3
								pred_usd_type2
								comp_usd_type2
								pred_usd_type1
								comp_usd_type1

Bit Range	Default & Access	Description
31	0h RW	pred_usd_type8: prediction algorithm for vc=2, user defined type 8 data: 0 -) pred1, 1 -) pred2
30:28	0h RW	comp_usd_type8: compression format for vc=2, user defined type 8 data: value between 0 to 6. 0-no compression
27	0h RW	pred_usd_type7: prediction algorithm for vc=2, user defined type 7 data: 0 -) pred1, 1 -) pred2
26:24	0h RW	comp_usd_type7: compression format for vc=2, user defined type 7 data: value between 0 to 6. 0-no compression
23	0h RW	pred_usd_type6: prediction algorithm for vc=2, user defined type 6 data: 0 -) pred1, 1 -) pred2
22:20	0h RW	comp_usd_type6: compression format for vc=2, user defined type 6 data: value between 0 to 6. 0-no compression
19	0h RW	pred_usd_type5: prediction algorithm for vc=2, user defined type 5 data: 0 -) pred1, 1 -) pred2
18:16	0h RW	comp_usd_type5: compression format for vc=2, user defined type 5 data: value between 0 to 6. 0-no compression
15	0h RW	pred_usd_type4: prediction algorithm for vc=2, user defined type 4 data: 0 -) pred1, 1 -) pred2
14:12	0h RW	comp_usd_type4: compression format for vc=2, user defined type 4 data: value between 0 to 6. 0-no compression
11	0h RW	pred_usd_type3: prediction algorithm for vc=2, user defined type 3 data: 0 -) pred1, 1 -) pred2
10:8	0h RW	comp_usd_type3: compression format for vc=2, user defined type 3 data: value between 0 to 6. 0-no compression
7	0h RW	pred_usd_type2: prediction algorithm for vc=2, user defined type 2 data: 0 -) pred1, 1 -) pred2
6:4	0h RW	comp_usd_type2: compression format for vc=2, user defined type 2 data: value between 0 to 6. 0-no compression
3	0h RW	pred_usd_type1: prediction algorithm for vc=2, user defined type 1 data: 0 -) pred1, 1 -) pred2



Bit Range	Default & Access	Description
2:0	0h RW	comp_usd_type1: compression format for vc=2, user defined type 1 data: value between 0 to 6. 0-no compression

15.8.682 reg_inp_sys_csi_receiver_csi_sh_be_comp_reg_vc3_type (inp_sys_csi_receiver_csi_sh_be_comp_reg_vc3)—Offset 80818h

Compression scheme register for virtual channel 0

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_sh_be_comp_reg_vc3:
[ISPMADDR] + 80818h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
pred_usd_type8	comp_usd_type8	pred_usd_type7	comp_usd_type7	pred_usd_type6	comp_usd_type6	pred_usd_type5	comp_usd_type5	pred_usd_type4
comp_usd_type4	pred_usd_type3	comp_usd_type3	pred_usd_type2	comp_usd_type2	pred_usd_type1	comp_usd_type1		

Bit Range	Default & Access	Description
31	0h RW	pred_usd_type8: prediction algorithm for vc=3, user defined type 8 data: 0 -) pred1, 1 -) pred2
30:28	0h RW	comp_usd_type8: compression format for vc=3, user defined type 8 data: value between 0 to 6. 0-no compression
27	0h RW	pred_usd_type7: prediction algorithm for vc=3, user defined type 7 data: 0 -) pred1, 1 -) pred2
26:24	0h RW	comp_usd_type7: compression format for vc=3, user defined type 7 data: value between 0 to 6. 0-no compression
23	0h RW	pred_usd_type6: prediction algorithm for vc=3, user defined type 6 data: 0 -) pred1, 1 -) pred2
22:20	0h RW	comp_usd_type6: compression format for vc=3, user defined type 6 data: value between 0 to 6. 0-no compression
19	0h RW	pred_usd_type5: prediction algorithm for vc=3, user defined type 5 data: 0 -) pred1, 1 -) pred2
18:16	0h RW	comp_usd_type5: compression format for vc=3, user defined type 5 data: value between 0 to 6. 0-no compression
15	0h RW	pred_usd_type4: prediction algorithm for vc=3, user defined type 4 data: 0 -) pred1, 1 -) pred2
14:12	0h RW	comp_usd_type4: compression format for vc=3, user defined type 4 data: value between 0 to 6. 0-no compression



Bit Range	Default & Access	Description
11	0h RW	pred_usd_type3 : prediction algorithm for vc=3, user defined type 3 data: 0 -) pred1 1 -) pred2
10:8	0h RW	comp_usd_type3 : compression format for vc=3, user defined type 3 data: value between 0 to 6. 0-no compression
7	0h RW	pred_usd_type2 : prediction algorithm for vc=3, user defined type 2 data: 0 -) pred1 1 -) pred2
6:4	0h RW	comp_usd_type2 : compression format for vc=3, user defined type 2 data: value between 0 to 6. 0-no compression
3	0h RW	pred_usd_type1 : prediction algorithm for vc=3, user defined type 1 data: 0 -) pred1 1 -) pred2
2:0	0h RW	comp_usd_type1 : compression format for vc=3, user defined type 1 data: value between 0 to 6. 0-no compression

15.8.683 `reg_inp_sys_csi_receiver_csi_sh_be_sel_be_type`
(`inp sys csi receiver csi sh be sel be`)—Offset 8081Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_sh_be_sel_be: [ISPMADR] + 8081Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
unused_csi_sh_be_sel_be									
csi_sh_be_sel_be									

Bit Range	Default & Access	Description
31:1	0h RW	unused_csi_sh_be_sel_be: Unused
0	0h RW	csi_sh_be_sel_be: Selects which CSI Receiver Backend to use 0-Arasan Backend, 1-Silicon Hive Backend

15.8.684 reg_inp_sys_csi_receiver_csi_sh_be_raw16_reg_type
(inp_sys_csi_receiver_csi_sh_be_raw16_reg)—Offset 80820h

Configuration register for RAW 16 data type decode

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_sh_be_raw16_reg: [ISPMADR] + 80820h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_csi_sh_be_raw16_reg							format_en	format_id

Bit Range	Default & Access	Description
31:7	0h RW	unused_csi_sh_be_raw16_reg: Unused
6	0h RW	format_en: enable RAW 16 type decode
5:0	0h RW	format_id: data id for RAW 16

15.8.685 reg_inp_sys_csi_receiver_csi_sh_be_raw18_reg_type (inp_sys_csi_receiver_csi_sh_be_raw18_reg)—Offset 80824h

Configuration register for RAW 18 data type decode

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_csi_receiver_csi_sh_be_raw18_reg: [ISPMADR] + 80824h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Access Method

inp_sys_csi_receiver_csi_sh_be_force_raw8_reg:
[ISPMADR] + 80828h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
unused_csi_sh_be_force_raw8_reg							force_data_id		option_enable



Access Method

inp_sys_csi_receiver_csi_sh_be_irq_stat_reg: [ISPMADR]
+ 8082Ch

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:2	0h RW	unused_csi_sh_be_irq_stat_reg: Unused
1	0h RO	irq_premature_sop: If '1', sh_be has detected a premature sop
0	0h RO	irq_missing_sop: If '1', sh_be has detected a missing sop

15.8.688 reg_inp_sys_csi_receiver_csi_sh_be_irq_stat_clear_reg_type
(inp_sys_csi_receiver_csi_sh_be_irq_stat_clear_reg)—Offset
80830h

Access Method



Default: 00000000h



Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_CaptStartMode: Unused
0	0h RW	reg_CaptStartMode: Synchronize on any packet header or on a frame start

15.8.691 `reg_inp_sys_capt_unit_a_reg_Capt_Start_Addr_type`
(`inp_sys_capt_unit_a_reg_Capt_Start_Addr`)—Offset 81004h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_a_reg_Capt_Start_Addr: [ISPMMAADR] + 81004h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_Capt_Start_Addr							reg_Capt_Start_Addr	

Bit Range	Default & Access	Description
31:9	0h RW	unused_reg_Capt_Start_Addr: Unused
8:0	0h RW	reg_Capt_Start_Addr: Start Address of first memory region

15.8.692 **reg_inp_sys_capt_unit_a_reg_Capt_Mem_Region_Size_type**
(inp_sys_capt_unit_a_reg_Capt_Mem_Region_Size)—Offset
81008h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_a_reg_Capt_Mem_Region_Size:
[ISPMMAADR] + 81008h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000080h



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_a_reg_Capt_Num_Mem_Regions:
[ISPMADR] + 8100Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_Capt_Num_Mem_Regions							reg_Capt_Num_Mem_Regions	

15.8.694 **reg_inp_sys_capt_unit_a_reg_Capt_Init_type**
(inp_sys_capt_unit_a_reg_Capt_Init)—Offset 81010h



Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_Capt_Start: Unused
0	0h WO	reg_Capt_Start: Start Capturing

Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_Capt_Stop: Unused
0	0h WO	reg_Capt_Stop: Stop Capturing



Bit Range	Default & Access	Description
31:0	0h RO	reg_Capt_Received_Short_Packets: Number of received short packets

15.8.700 reg_inp_sys_capt_unit_a_reg_Capt_Received_Long_Packets_type (inp_sys_capt_unit_a_reg_Capt_Received_Long_Packets)—Offset 81028h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_Capt_Received_Long_Packets								

Bit Range	Default & Access	Description
31:0	0h RO	reg_Capt_Received_Long_Packets: Number of received long packets

15.8.701 reg_inp_sys_capt_unit_a_reg_Capt_Last_Command_type
(inp_sys_capt_unit_a_reg_Capt_Last_Command)—Offset
8102Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_a_reg_Capt_Last_Command:
[ISPMMA DR] + 8102Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh

[illegible]

Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Capt_Last_Command: Last command token accepted



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_a_reg_Capt_Next_Command:
[ISPMADR] + 81030h**ISPMADR Type:** PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_Capt_Next_Command								

Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Capt_Next_Command: Next command token to be accepted

15.8.703 reg_inp_sys_capt_unit_a_reg_Capt_Last_Acknowledge_type
(inp_sys_capt_unit_a_reg_Capt_Last_Acknowledge)—Offset
81034h

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_a_reg_Capt_Last_Acknowledge:
[ISPMADR] + 81034h**ISPMADR Type:** PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]



Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Capt_Last_Acknowledge: Last acknowledge token send

15.8.704 reg_inp_sys_capt_unit_a_reg_Capt_Next_Acknowledge_type (inp_sys_capt_unit_a_reg_Capt_Next_Acknowledge)—Offset 81038h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_a_reg_Capt_Next_Acknowledge:
[ISPMADDR] + 81038h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
reg_Capt_Next_Acknowledge								

Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Capt_Next_Acknowledge: Next acknowledge token to be send

15.8.705 reg_inp_sys_capt_unit_a_reg_Capt_FSM_State_Info_type (inp_sys_capt_unit_a_reg_Capt_FSM_State_Info)—Offset 8103Ch

Capture Unit State Machine Information

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_a_reg_Capt_FSM_State_Info:
[ISPMADDR] + 8103Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
unused_reg_Capt_FSM_State_Info												synchronizer_fsm_ps				synchronizer_fsm_s				synchronizer_fsm_ns				write2mem_fsm_ps				write2mem_fsm_s				write2mem_fsm_ns			

Bit Range	Default & Access	Description
31:15	0h RW	unused_reg_Capt_FSM_State_Info: Unused
14:12	0h RO	synchronizer_fsm_ps: Previous state of Synchronizer State Machine
11:9	0h RO	synchronizer_fsm_s: Current state of Synchronizer State Machine
8:6	0h RO	synchronizer_fsm_ns: Next state of Synchronizer State Machine
5:4	0h RO	write2mem_fsm_ps: Previous state of Write2Mem State Machine
3:2	0h RO	write2mem_fsm_s: Current state of Write2Mem State Machine
1:0	0h RO	write2mem_fsm_ns: Next state of Write2Mem State Machine

15.8.706 reg_inp_sys_capt_unit_b_reg_CaptStartMode_type (inp_sys_capt_unit_b_reg_CaptStartMode)—Offset 82000h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_CaptStartMode: [ISPMADDR] + 82000h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_CaptStartMode								reg_CaptStartMode

Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_CaptStartMode: Unused
0	0h RW	reg_CaptStartMode: Synchronize on any packet header or on a frame start

15.8.707 reg_inp_sys_capt_unit_b_reg_Capt_Start_Addr_type (inp_sys_capt_unit_b_reg_Capt_Start_Addr)—Offset 82004h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Start_Addr: [ISPMADDR] + 82004h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_Capt_Start_Addr							reg_Capt_Start_Addr	

Bit Range	Default & Access	Description
31:9	0h RW	unused_reg_Capt_Start_Addr: Unused
8:0	0h RW	reg_Capt_Start_Addr: Start Address of first memory region



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Mem_Region_Size:
[ISPMMAADR] + 82008h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31				28				24				20				16				12				8				4				0															
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0												
unused_reg_Capt_Mem_Region_Size																								reg_Capt_Mem_Region_Size																							

Bit Range	Default & Access	Description
31:9	0h RW	unused_reg_Capt_Mem_Region_Size: Unused
8:0	080h RW	reg_Capt_Mem_Region_Size: Memory region size

15.8.709 `reg_inp_sys_capt_unit_b_reg_Capt_Num_Mem_Regions_type`
(`inp_sys_capt_unit_b_reg_Capt_Num_Mem_Regions`)—Offset
8200Ch

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Num_Mem_Regions:
[ISPMADR] + 8200Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000003h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
unused_reg_Capt_Num_Mem_Regions							reg_Capt_Num_Mem_Regions	

Bit Range	Default & Access	Description
31:9	0h RW	unused_reg_Capt_Num_Mem_Regions: Unused
8:0	003h RW	reg_Capt_Num_Mem_Regions: Number of memory regions

15.8.710 reg_inp_sys_capt_unit_b_reg_Capt_Init_type (inp_sys_capt_unit_b_reg_Capt_Init)—Offset 82010h

Initialize Capture Unit

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Init: [ISPMADR] + 82010h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_reg_Capt_Init				restart_mem_reg_id				restart
								resync
								flush
								reset_reg

Bit Range	Default & Access	Description
31:22	0h RW	unused_reg_Capt_Init: Unused
21:13	0h WO	restart_mem_reg_id: Restart Memory Region ID



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Start: [ISPMADR] + 82014h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
unused_reg_Capt_Start									reg_Capt_Start

Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_Capt_Start: Unused
0	0h WO	reg_Capt_Start: Start Capturing


15.8.712 reg_inp_sys_capt_unit_b_reg_Capt_Stop_type
(inp_sys_capt_unit_b_reg_Capt_Stop)—Offset 82018h

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Stop: [ISPMADR] + 82018h**ISPMADR Type:** PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
1614



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Packet_Length:
[ISPMMAADR] + 8201Ch


ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_Capt_Packet_Length								

15.8.714 reg_inp_sys_capt_unit_b_reg_Capt_Received_Length_type
(inp_sys_capt_unit_b_reg_Capt_Received_Length)—Offset
82020h

Intel Atom® Processor E3800 Product Family
Datasheet
1615



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)
ISPMADR Reference: [B:0, D:3, F:0] + 10h

Bit Position	31	28	24	20	16	12	8	4	0			
Value	0	0	0	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RO	reg_Capt_Received_Length: (Incremental) received packet length of current multi-word packet (MWP)

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Received_Short_Packets:
[ISPMADR] + 82024h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)
ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_Capt_Received_Short_Packets								



Bit Range	Default & Access	Description
31:0	0h RO	reg_Capt_Received_Short_Packets: Number of received short packets

15.8.716 reg_inp_sys_capt_unit_b_reg_Capt_Received_Long_Packets_type (inp_sys_capt_unit_b_reg_Capt_Received_Long_Packets)—Offset 82028h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Received_Long_Packets:
[ISPMMA DR] + 82028h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_Capt_Received_Long_Packets								

Bit Range	Default & Access	Description
31:0	0h RO	reg_Capt_Received_Long_Packets: Number of received long packets

15.8.717 reg_inp_sys_capt_unit_b_reg_Capt_Last_Command_type
(inp_sys_capt_unit_b_reg_Capt_Last_Command)—Offset
8202Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Last_Command:
[ISPMMAADR] + 8202Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Next_Command:
[ISPMMAADR] + 82030h

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]

15.8.719 **reg_inp_sys_capt_unit_b_reg_Capt_Last_Acknowledge_type**
(inp_sys_capt_unit_b_reg_Capt_Last_Acknowledge)—Offset
82034h

Intel Atom® Processor E3800 Product Family
Datasheet
1618



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Last_Acknowledge:
[ISPMMAADR] + 82034h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
reg_Capt_Last_Acknowledge								

Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Capt_Last_Acknowledge: Last acknowledge token send

15.8.720 reg_inp_sys_capt_unit_b_reg_Capt_Next_Acknowledge_type (inp_sys_capt_unit_b_reg_Capt_Next_Acknowledge)—Offset 82038h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_b_reg_Capt_Next_Acknowledge:
[ISPMMAADR] + 82038h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
reg_Capt_Next_Acknowledge								



Access Method

inp_sys_capt_unit_b_reg_Capt_FSM_State_Info:
 [ISPMMAADR] + 8203Ch

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:15	0h RW	unused_reg_Capt_FSM_State_Info: Unused
14:12	0h RO	synchronizer_fsm_ps: Previous state of Synchronizer State Machine
11:9	0h RO	synchronizer_fsm_s: Current state of Synchronizer State Machine
8:6	0h RO	synchronizer_fsm_ns: Next state of Synchronizer State Machine
5:4	0h RO	write2mem_fsm_ps: Previous state of Write2Mem State Machine
3:2	0h RO	write2mem_fsm_s: Current state of Write2Mem State Machine
1:0	0h RO	write2mem_fsm_ns: Next state of Write2Mem State Machine



15.8.722 reg_inp_sys_capt_unit_c_reg_CaptStartMode_type (inp_sys_capt_unit_c_reg_CaptStartMode)—Offset 83000h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_CaptStartMode: [ISPMMAADR] + 83000h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_CaptStartMode								reg_CaptStartMode

Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_CaptStartMode: Unused
0	0h RW	reg_CaptStartMode: Synchronize on any packet header or on a frame start

15.8.723 reg_inp_sys_capt_unit_c_reg_Capt_Start_Addr_type (inp_sys_capt_unit_c_reg_Capt_Start_Addr)—Offset 83004h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_Start_Addr: [ISPMMAADR] + 83004h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_Mem_Region_Size:
[ISPMADR] + 83008h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0				
unused_reg_Capt_Mem_Region_Size												reg_Capt_Mem_Region_Size																							

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
8:0	080h RW	reg_Capt_Mem_Region_Size: Memory region size

15.8.725 **reg_inp_sys_capt_unit_c_reg_Capt_Num_Mem_Regions_type** (**inp_sys_capt_unit_c_reg_Capt_Num_Mem_Regions**)—Offset 8300Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_Num_Mem_Regions:
[ISPMMAADR] + 8300Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000003h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
unused_reg_Capt_Num_Mem_Regions							reg_Capt_Num_Mem_Regions	

Bit Range	Default & Access	Description
31:9	0h RW	unused_reg_Capt_Num_Mem_Regions: Unused
8:0	003h RW	reg_Capt_Num_Mem_Regions: Number of memory regions

15.8.726 **reg_inp_sys_capt_unit_c_reg_Capt_Init_type** (**inp_sys_capt_unit_c_reg_Capt_Init**)—Offset 83010h

Initialize Capture Unit

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_Init: [ISPMMAADR] + 83010h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
								reg_Capt_Start
								reg_Capt_Start



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_Received_Length:
[ISPMADR] + 83020h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

	31	28	24	20	16	12	8	4	0																							
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	reg_Capt_Received_Length																															

15.8.731 reg_inp_sys_capt_unit_c_reg_Capt_Received_Short_Packets_type (inp_sys_capt_unit_c_reg_Capt_Received_Short_Packets)—Offset 83024h

Intel Atom® Processor E3800 Product Family
Datasheet
1626



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_Last_Command:
[ISPMADDR] + 8302Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]

Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Capt_Last_Command: Last command token accepted

15.8.734 `reg_inp_sys_capt_unit_c_reg_Capt_Next_Command_type`
(`inp_sys_capt_unit_c_reg_Capt_Next_Command`)—Offset
83030h

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_Next_Command:
[ISPMMAADR] + 83030h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_Last_Acknowledge:
[ISPMADR] + 83034h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]

15.8.736 reg_inp_sys_capt_unit_c_reg_Capt_Next_Acknowledge_type
(inp_sys_capt_unit_c_reg_Capt_Next_Acknowledge)—Offset
83038h

Intel Atom® Processor E3800 Product Family
Datasheet
1629



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_Next_Acknowledge:
[ISPMADR] + 83038h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
reg_Capt_Next_Acknowledge								

Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Capt_Next_Acknowledge: Next acknowledge token to be send

15.8.737 reg_inp_sys_capt_unit_c_reg_Capt_FSM_State_Info_type (inp_sys_capt_unit_c_reg_Capt_FSM_State_Info)—Offset 8303Ch

Capture Unit State Machine Information

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_capt_unit_c_reg_Capt_FSM_State_Info:
[ISPMADR] + 8303Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_reg_Capt_FSM_State_Info								
synchronizer_fsm_ps								
synchronizer_fsm_s								
synchronizer_fsm_ns								
write2mem_fsm_ps								
write2mem_fsm_s								
write2mem_fsm_ns								

15.8.739 reg_inp_sys_acq_unit_reg_Acq_Mem_Region_Size_type
(inp_sys_acq_unit_reg_Acq_Mem_Region_Size)—Offset
84004h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp_sys_acq_unit_reg_Acq_Mem_Region_Size: [ISPMADR]
+ 84004h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000080h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
unused_reg_Acq_Mem_Region_Size							reg_Acq_Mem_Region_Size	

Bit Range	Default & Access	Description
31:9	0h RW	unused_reg_Acq_Mem_Region_Size: Unused
8:0	080h RW	reg_Acq_Mem_Region_Size: Memory region size

15.8.740 reg_inp_sys_acq_unit_reg_Acq_Num_Mem_Regions_type
(inp_sys_acq_unit_reg_Acq_Num_Mem_Regions)—Offset
84008h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_acq_unit_reg_Acq_Num_Mem_Regions:
[ISPMADR] + 84008h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000003h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
unused_reg_Acq_Num_Mem_Regions							reg_Acq_Num_Mem_Regions	

Bit Range	Default & Access	Description
31:9	0h RW	unused_reg_Acq_Num_Mem_Regions: Unused
8:0	003h RW	reg_Acq_Num_Mem_Regions: Number of memory regions

15.8.741 reg_inp_sys_acq_unit_reg_Acq_Init_type (inp_sys_acq_unit_reg_Acq_Init)—Offset 8400Ch

Initialize Acquisition Unit

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_acq_unit_reg_Acq_Init: [ISPMADDR] + 8400Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_reg_Acq_Init							resync	reset_reg
							RSVD0	

Bit Range	Default & Access	Description
31:3	0h RW	unused_reg_Acq_Init: Unused
2	0h WO	resync: Resynchronize the Acquisition Unit



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_acq_unit_reg_Acq_Received_Short_Packets:
[ISPMMAADR] + 84010h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_Acq_Received_Short_Packets								

Bit Range	Default & Access	Description
31:0	0h RO	reg_Acq_Received_Short_Packets: Number of received short packets

15.8.743 `reg_inp_sys_acq_unit_reg_Acq_Received_Long_Packets_type`
(`inp_sys_acq_unit_reg_Acq_Received_Long_Packets`)—Offset
84014h

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_acq_unit_reg_Acq_Received_Long_Packets:
[ISPMMAADR] + 84014h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



312824201612840																															
00000000000000000000000000000000																															
reg_Acq_Received_Long_Packets																															

15.8.744 **reg_inp_sys_acq_unit_reg_Acq_Last_Command_type**
(inp_sys_acq_unit_reg_Acq_Last_Command)—Offset 84018h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_acq_unit_reg_Acq_Last_Command: [ISPMADR] + 84018h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_Acq_Last_Command								

Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Acq_Last_Command: Last command token accepted

15.8.745 **reg_inp_sys_acq_unit_reg_Acq_Next_Command_type**
(inp_sys_acq_unit_reg_Acq_Next_Command)—Offset 8401Ch

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_acq_unit_reg_Acq_Next_Command: [ISPMMAADR] + 8401Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
reg_Acq_Next_Command								

Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Acq_Next_Command: Next command token to be accepted

15.8.746 reg_inp_sys_acq_unit_reg_Acq_Last_Acknowledge_type (inp_sys_acq_unit_reg_Acq_Last_Acknowledge)—Offset 84020h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_acq_unit_reg_Acq_Last_Acknowledge:
[ISPMMAADR] + 84020h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
reg_Acq_Last_Acknowledge								

Bit Range	Default & Access	Description
31:0	0000000Fh RO	reg_Acq_Last_Acknowledge: Last acknowledge token send



31				28				24				20				16				12				8				4				0																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																							
unused_reg_Acq_FSM_State_Info																																synchronizer_fsm_ps				synchronizer_fsm_s				synchronizer_fsm_ns				mem2stream_fsm_ps				mem2stream_fsm_s				mem2stream_fsm_ns			

Bit Range	Default & Access	Description
31:12	0h RW	unused_reg_Acq_FSM_State_Info: Unused
11:10	0h RO	synchronizer_fsm_ps: Previous state of Synchronizer State Machine
9:8	0h RO	synchronizer_fsm_s: Current state of Synchronizer State Machine
7:6	0h RO	synchronizer_fsm_ns: Next state of Synchronizer State Machine
5:4	0h RO	mem2stream_fsm_ps: Previous state of Mem2Stream State Machine
3:2	0h RO	mem2stream_fsm_s: Current state of Mem2Stream State Machine
1:0	0h RO	mem2stream_fsm_ns: Next state of Mem2Stream State Machine

15.8.749 reg_inp_sys_acq_unit_reg_Acq_Int_Cntr_Info_type (inp_sys_acq_unit_reg_Acq_Int_Cntr_Info)—Offset 8402Ch

Acq_Int_Cntr_Info

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_acq_unit_reg_Acq_Int_Cntr_Info: [ISPMADDR] + 8402Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_Acq_Int_Cntr_Info	transmit_cntr	RSVD0	superword_cntr	RSVD1		mwp_cntr		

Bit Range	Default & Access	Description
31	0h RW	unused_reg_Acq_Int_Cntr_Info: Unused
30:28	0h RO	transmit_cntr: Counter used for determining which word (part of a superword) to be send
27:25	0b RO	RSVD0: Reserved
24:16	0h RO	superword_cntr: Counts number of superwords read from wide bus (input buffer)
15:14	0b RO	RSVD1: Reserved
13:0	0h RO	mwp_cntr: Counts words in multi word packet

15.8.750 reg_inp_sys_dma_DMA_FSM_Command_type (inp_sys_dma_DMA_FSM_Command)—Offset 85000h

FSM Command: Last command and State

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Command: [ISPMMAADR] + 85000h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
		state			unused		Error	Stall
							Run	Idle

Bit Range	Default & Access	Description
31:16	0h RO	state: Lower 16 bits of the last command received and processed



Bit Range	Default & Access	Description
31:5	0h RW	unused_DMA_CH0_Packing_setup: Unused
4	0h RO	ext: Zero(0)/Sign(1) extension
3:1	0h RO	unused: unused
0	0h RO	conn: Connection ID



Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH0_dev_Pack_left_crop_and_elem_A: Unused
13:8	0h RO	Dev_A_crop: Device A left element cropping
7	0h RO	unused: unused
6:0	0h RO	Dev_A_elem: Device A element per word

15.8.754 reg_inp_sys_dma_DMA_CH0_Device_Xb_A_type (inp_sys_dma_DMA_CH0_Device_Xb_A)—Offset 86300h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_CH0_Device_Xb_A: [ISPMADDR] + 86300h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



15.8.755 `reg_inp_sys_dma_DMA_CH0_dev_stride_B_type`
(`inp_sys_dma_DMA_CH0_dev_stride_B`)—Offset 86400h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_CH0_dev_stride_B								

15.8.756 reg_inp_sys_dma_DMA_CH0_dev_Pack_left_crop_and_elem_B_type



(inp_sys_dma_DMA_CH0_dev_Pack_left_crop_and_elem_B)—Offset 86500h

DMA CH 0 PARAM 5: Device B Packing LSE cropping/Elements

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_CH0_dev_Pack_left_crop_and_elem_B
: [ISPMMAADR] + 86500h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH0_dev_Pack_left_crop_and_elem_B				Dev_B_crop		unused	Dev_B_elem	

Bit Range	Default & Access	Description
31:14	0h RW	unused_DMA_CH0_dev_Pack_left_crop_and_elem_B: Unused
13:8	0h RO	Dev_B_crop: Device B left element cropping
7	0h RO	unused: unused
6:0	0h RO	Dev_B_elem: Device B element per word

15.8.757 reg_inp_sys_dma_DMA_CH0_Device_Xb_B_type (inp_sys_dma_DMA_CH0_Device_Xb_B)—Offset 86600h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_CH0_Device_Xb_B: [ISPMMAADR] + 86600h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

15.8.759 reg_inp_sys_dma_DMA_CH0_pending_command_type
(inp_sys_dma_DMA_CH0_pending_command)—Offset 86800h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_CH0_pending_command: [ISPMADR] + 86800h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_CH0_pending_command								DMA_CH0_pending_command

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_CH0_pending_command: Unused
3:0	0h RO	DMA_CH0_pending_command: DMA CH 0 PARAM 8: Pending commands which will use channel 0

15.8.760 reg_inp_sys_dma_DMA_command_token_type
(inp_sys_dma_DMA_command_token)—Offset 87000h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_command_token: [ISPMADR] + 87000h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)
ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_command_ctrl_id								DMA_command_ctrl_id

Intel Atom® Processor E3800 Product Family
Datasheet
1648



15.8.764 reg_inp_sys_dma_DMA_FSM_Ctrl_status_type (inp_sys_dma_DMA_FSM_Ctrl_status)—Offset 87010h

DMA FSM Control state and flags

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Ctrl_status: [ISPMMAADR] + 87010h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_DMA_FSM_Ctrl_status							FSM	Error
								Stall
								Run
								Idle

Bit Range	Default & Access	Description
31:8	0h RW	unused_DMA_FSM_Ctrl_status: Unused
7:4	0h RO	FSM: FSM control state: 0)Idle -- 1)req_rcv -- 2)rcv -- 3)rcv_req -- 4)init
3	0h RO	Error: Error flag
2	0h RO	Stall: Stall flag
1	0h RO	Run: Run flag
0	1h RO	Idle: Idle flag

15.8.765 reg_inp_sys_dma_DMA_FSM_Pack_status_type (inp_sys_dma_DMA_FSM_Pack_status)—Offset 87014h

DMA FSM Pack state

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Pack_status: [ISPMMAADR] + 87014h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Pack_status								Error
								Stall
								Run
								Idle

Bit Range	Default & Access	Description
31:4	0h RW	unused_DMA_FSM_Pack_status: Unused
3	0h RO	Error: Error flag
2	0h RO	Stall: Stall flag
1	0h RO	Run: Run flag
0	0h RO	Idle: Idle flag

15.8.766 reg_inp_sys_dma_DMA_FSM_request_status_type (inp_sys_dma_DMA_FSM_request_status)—Offset 87018h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_request_status: [ISPMADDR] + 87018h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_write_status: [ISPMADR] + 8701Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
unused_DMA_FSM_write_status DMA_FSM_write_status									

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:1	0h RW	unused_DMA_FSM_Ctrl_dev_idx: Unused
0	0h RO	DMA_FSM_Ctrl_dev_idx: DMA FSM Control request device idx

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

15.8.770 reg_inp_sys_dma_DMA_FSM_Request_cnt_Yb_type
(inp_sys_dma_DMA_FSM_Request_cnt_Yb)—Offset 87118h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Request_cnt_Yb: [ISPMADR] + 87118h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Request_cnt_Yb					DMA_FSM_Request_cnt_Yb			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Request_cnt_Yb: Unused



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Write_cnt_Y: Unused
15:0	0h RO	DMA_FSM_Write_cnt_Y: DMA FSM Write counter height (Yb)

15.8.772 `reg_inp_sys_dma_DMA_FSM_Ctrl_req_addr_type`
(`inp_sys_dma_DMA_FSM_Ctrl_req_addr`)—Offset 87210h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Pack_req_cnt_Xb: [ISPMADR] + 87214h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Pack_req_cnt_Xb					DMA_FSM_Pack_req_cnt_Xb			

October 2018
Document Number: 538136, Rev. 4.3



15.8.774 reg_inpsys_dma_DMA_FSM_Request_cnt_Xb_type (inpsys_dma_DMA_FSM_Request_cnt_Xb)—Offset 87218h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inpsys_dma_DMA_FSM_Request_cnt_Xb: [ISPMADDR] + 87218h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Request_cnt_Xb				DMA_FSM_Request_cnt_Xb				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Request_cnt_Xb: Unused
15:0	0h RO	DMA_FSM_Request_cnt_Xb: DMA FSM Request counter width (Xb)

15.8.775 reg_inpsys_dma_DMA_FSM_Write_cnt_Xb_type (inpsys_dma_DMA_FSM_Write_cnt_Xb)—Offset 8721Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inpsys_dma_DMA_FSM_Write_cnt_Xb: [ISPMADDR] + 8721Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp_sys_dma_DMA_FSM_Ctrl_req_stride: [ISPMADR] +
87310h
```

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_FSM_Ctrl_req_stride								

Intel Atom® Processor E3800 Product Family
Datasheet
1657



15.8.777 reg_inp_sys_dma_DMA_FSM_Pack_wr_cnt_Xb_type (inp_sys_dma_DMA_FSM_Pack_wr_cnt_Xb)—Offset 87314h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Pack_wr_cnt_Xb: [ISPMADDR] + 87314h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Pack_wr_cnt_Xb				DMA_FSM_Pack_wr_cnt_Xb				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Pack_wr_cnt_Xb: Unused
15:0	0h RO	DMA_FSM_Pack_wr_cnt_Xb: DMA FSM pack write counter width (Xb)

15.8.778 reg_inp_sys_dma_DMA_FSM_Req_remining_Xb_type (inp_sys_dma_DMA_FSM_Req_remining_Xb)—Offset 87318h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Req_remining_Xb: [ISPMADDR] + 87318h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Wr_remining_Xb: [ISPMADR] + 8731Ch

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_FSM_Wr_remining_Xb					DMA_FSM_Wr_remining_Xb			



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_FSM_Ctrl_req_Xb								

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Ctrl_req_Xb: Unused
15:0	0h RO	DMA_FSM_Ctrl_req_Xb: DMA FSM Control request width (Xb)

15.8.781 reg_inp_sys_dma_DMA_FSM_Req_burst_cnt_type
(inp sys dma DMA FSM Req burst cnt)—Offset 87418h

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

Default: 0000FFFFh



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Wr_burst_cnt: [ISPMADR] + 8741Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_wr_burst_cnt					DMA_FSM_wr_burst_cnt			

October 2018
Document Number: 538136, Rev. 4.3

15.8.783 reg_inp_sys_dma_DMA_FSM_Ctrl_req_Yb_type
(inp_sys_dma_DMA_FSM_Ctrl_req_Yb)—Offset 87510h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Ctrl_req_Yb: [ISPMADR] + 87510h

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Ctrl_req_Yb					DMA_FSM_Ctrl_req_Yb			

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Ctrl_req_Yb: Unused
15:0	0h RO	DMA_FSM_Ctrl_req_Yb: DMA FSM Control request height (Yb)

15.8.784 reg_inp_sys_dma_DMA_FSM_Ctrl_Pack_req_dev_idx_type
(inp_sys_dma_DMA_FSM_Ctrl_Pack_req_dev_idx)—Offset
87610h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Ctrl_Pack_req_dev_idx:
[ISPMMAADR] + 87610h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Ctrl_Pack_req_dev_idx								DMA_FSM_Ctrl_Pack_req_dev_idx

Bit Range	Default & Access	Description
31:1	0h RW	unused_DMA_FSM_Ctrl_Pack_req_dev_idx: Unused
0	0h RO	DMA_FSM_Ctrl_Pack_req_dev_idx: DMA FSM Control pack request device idx

15.8.785 reg_inp_sys_dma_DMA_FSM_Ctrl_Pack_wr_dev_idx_type (inp_sys_dma_DMA_FSM_Ctrl_Pack_wr_dev_idx)—Offset 87710h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Ctrl_Pack_wr_dev_idx:
[ISPMADDR] + 87710h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Ctrl_Pack_wr_dev_idx								DMA_FSM_Ctrl_Pack_wr_dev_idx



Bit Range	Default & Access	Description
31:0	0h RO	DMA_FSM_Ctrl_Wr_addr: DMA FSM Control write address

15.8.787 reg_inp_sys_dma_DMA_FSM_Ctrl_Wr_stride_type
(inp_sys_dma_DMA_FSM_Ctrl_Wr_stride)—Offset 87910h

Default: 00000000h



15.8.789 reg_inp_sys_dma_DMA_FSM_Ctrl_pack_Yb_type (inp_sys_dma_DMA_FSM_Ctrl_pack_Yb)—Offset 87B10h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Ctrl_pack_Yb: [ISPMADDR] + 87B10h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Ctrl_pack_Yb				DMA_FSM_Ctrl_pack_Yb				

Bit Range	Default & Access	Description
31:16	0h RW	unused_DMA_FSM_Ctrl_pack_Yb: Unused
15:0	0h RO	DMA_FSM_Ctrl_pack_Yb: DMA FSM Control FSM Pack height (Yb)

15.8.790 reg_inp_sys_dma_DMA_FSM_Ctrl_pack_wr_Xb_type (inp_sys_dma_DMA_FSM_Ctrl_pack_wr_Xb)—Offset 87C10h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Ctrl_pack_wr_Xb: [ISPMADDR] + 87C10h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_FSM_Ctrl_pack_req_elem								DMA_FSM_Ctrl_pack_req_elem



Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp_sys_dma_DMA_FSM_Ctrl_pack_wr_elem: [ISPMADR]
+ 87E10h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_FSM_Ctrl_pack_wr_elem								DMA_FSM_Ctrl_pack_wr_elem

Bit Range	Default & Access	Description
31:7	0h RW	unused_DMA_FSM_Ctrl_pack_wr_elem: Unused
6:0	0h RO	DMA_FSM_Ctrl_pack_wr_elem: DMA FSM Control pack write element per word

15.8.793 `reg_inp_sys_dma_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id_type`
(`inp_sys_dma_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id`)—Offset
87F10h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id:
[ISPMMAADR] + 87F10h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id							ctrlID	unused
								ext

Bit Range	Default & Access	Description
31:6	0h RW	unused_DMA_FSM_Ctrl_pack_sz_ext_ctrl_id: Unused
5:4	0h RO	ctrlID: Controller ID
3:1	0h RO	unused: unused
0	0h RO	ext: element sign(1)/zero(0) extension

15.8.794 reg_inp_sys_dma_Dev_Interf_0_req_side_type (inp_sys_dma_Dev_Interf_0_req_side)—Offset 88000h

DMA Device interface 0 internal side status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


inp_sys_dma_Dev_Interf_0_req_side: [ISPMMAADR] + 88000h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h





15.8.796 reg_inp_sys_dma_Dev_Interf_0_snd_side_type
(inp_sys_dma_Dev_Interf_0_snd_side)—Offset 88100h

Default: 00000004h



[illegible]

Bit Range	Default & Access	Description
31:4	0h RW	unused_Dev_Interf_1_snd_side: Unused
3	0h RO	Error: Ack flag
2	1h RO	Stall: Run flag
1	1h RO	Run: We_n flag
0	0h RO	Idle: CS flag

15.8.798 reg_inp_sys_dma_Dev_Interf_0_Fifo_status_type
(inp_sys_dma_Dev_Interf_0_Fifo_status)—Offset 88200h

Device Interface 0 Fifo Status

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_Dev_Interf_0_Fifo_status: [ISPMMAADR] + 88200h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000004h



Bit Range	Default & Access	Description
31:17	0h RW	unused_Dev_Interf_1_Fifo_status: Unused
16:3	0h RO	Error: Fifo word counter
2	1h RO	Stall: Fifo is empty
1	0h RO	Run: Fifo is full
0	0h RO	Idle: Fifo will be full

Access Method

inp_sys_dma_Dev_Interf_0_Req_complete_bust:
[ISPMMAADR] + 88300h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_dma_Dev_Interf_1_Req_complete_bust:
[ISPMADR] + 88304h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Dev Interf 1 Req_complete_bust								



Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp_sys_inp_ctrl_inpsys_captB_start_addr: [ISPMADR] + 89004h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_inpsys_capitB_start_addr							inpsys_capitB_start_addr	

October 2018
Document Number: 538136, Rev. 4.3



Default: 00000080h

[illegible]



Bit Range	Default & Access	Description
31:9	0h RW	unused_inpsys_captB_mem_region_size: Unused
8:0	080h RW	inpsys_captB_mem_region_size: Input System Controller Capt B mem region size

15.8.808 reg_inp_sys_inp_ctrl_inpsys_captC_mem_region_size_type (inp_sys_inp_ctrl_inpsys_captC_mem_region_size)—Offset 89014h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_inp_ctrl_inpsys_captC_mem_region_size:
[ISPMMAADR] + 89014h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000080h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_inpsys_captC_mem_region_size							inpsys_captC_mem_region_size	

Bit Range	Default & Access	Description
31:9	0h RW	unused_inpsys_captC_mem_region_size: Unused
8:0	080h RW	inpsys_captC_mem_region_size: Input System Controller Capt C mem region size

15.8.809 reg_inp_sys_inp_ctrl_inpsys_captA_num_mem_regions_type (inp_sys_inp_ctrl_inpsys_captA_num_mem_regions)—Offset 89018h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_inp_ctrl_inpsys_captA_num_mem_regions:
[ISPMMAADR] + 89018h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h



Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp_sys_inp_ctrl_inpsys_captB_num_mem_regions:
[ISPMMAADR] + 8901Ch
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000003h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_insys_captB_num_mem_regions								
insys_captB_num_mem_regions								

Bit Range	Default & Access	Description
31:9	0h RW	unused_inpsys_captB_num_mem_regions: Unused
8:0	003h RW	inpsys_captB_num_mem_regions: Input System Controller Capt B number of mem regions

15.8.811 `reg_inp_sys_inp_ctrl_inpsys_captC_num_mem_regions_type`
(`inp_sys_inp_ctrl_inpsys_captC_num_mem_regions`)—Offset
89020h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
inp_sys_inp_ctrl_inpsys_captC_num_mem_regions:
[ISPMMAADR] + 89020h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000003h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_inpsys_captC_num_mem_regions								
								inpsys_captC_num_mem_regions
								0



Access Method

inp_sys_inp_ctrl_inpsys_acq_start_addr: [ISPMMAADR] + 89024h

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_inpsys_acq_start_addr							inpsys_acq_start_addr	

15.8.813 `reg_inp_sys_inp_ctrl_inpsys_acq_mem_region_size_type`
(`inp_sys_inp_ctrl_inpsys_acq_mem_region_size`)—Offset
89028h

Access Method

inp_sys_inp_ctrl_inpsys_acq_mem_region_size:
[ISPMMAADR] + 89028h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000080h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
unused_inpsys_acq_mem_region_size							inpsys_acq_mem_region_size	

Bit Range	Default & Access	Description
31:9	0h RW	unused_inpsys_acq_mem_region_size: Unused
8:0	080h RW	inpsys_acq_mem_region_size: Input System Controller Acquisition mem region size

15.8.814 reg_inp_sys_inp_ctrl_inpsys_acq_num_mem_regions_type (inp_sys_inp_ctrl_inpsys_acq_num_mem_regions)—Offset 8902Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_inp_ctrl_inpsys_acq_num_mem_regions:
[ISPMADR] + 8902Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000003h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_inpsys_acq_num_mem_regions							inpsys_acq_num_mem_regions	

15.8.815 `reg_inp_sys_inp_ctrl_inpsys_ctrl_init_type`
(`inp_sys_inp_ctrl_inpsys_ctrl_init`)—Offset 89030h

Input System Controller initialization register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_inp_ctrl_inpsys_ctrl_init: [ISPMADR] + 89030h**ISPMADR Type:** PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0			
0	0	0	0	0	0	0	0	0	0	0	0
unused_inpsys_ctrl_init										reserved	reset_registers

Bit Range	Default & Access	Description
31:3	0h RW	unused_inpsys_ctrl_init: Unused
2:1	0h RW	reserved: reserved bits, no action for now
0	0h RW	reset_registers: Reset all registers in Input System Controller

15.8.816 `reg_inp_sys_inp_ctrl_inpsys_last_cmd_type`
(`inp_sys_inp_ctrl_inpsys_last_cmd`)—Offset 89034h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_inp_ctrl_inpsys_last_cmd: [ISPMADR] + 89034h**ISPMADR Type:** PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
inpsys_last_cmd								

Bit Range	Default & Access	Description
31:0	0000000Fh RO	inpsys_last_cmd: Input System Controller last command register

15.8.817 reg_inp_sys_inp_ctrl_inpsys_next_cmd_type (inp_sys_inp_ctrl_inpsys_next_cmd)—Offset 89038h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_inp_ctrl_inpsys_next_cmd: [ISPMADDR] + 89038h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
inpsys_next_cmd								

Bit Range	Default & Access	Description
31:0	0000000Fh RO	inpsys_next_cmd: Input System Controller next command register

15.8.818 reg_inp_sys_inp_ctrl_inpsys_last_ack_type (inp_sys_inp_ctrl_inpsys_last_ack)—Offset 8903Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_inp_ctrl_inpsys_last_ack: [ISPMADDR] + 8903Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000Fh



Bit Range	Default & Access	Description
31:0	0000000Fh RO	inpsys_last_ack: Input System Controller last acknowledge register

15.8.819 reg_inp_sys_inp_ctrl_inpsys_next_ack_type
(inp_sys_inp_ctrl_inpsys_next_ack)—Offset 89040h

Bit Range	Default & Access	Description
31:0	0000000Fh RO	inpsys_next_ack: Input System Controller next acknowledge register

15.8.820 reg_inp_sys_inp_ctrl_inpsys_top_fsm_state_type
(inp_sys_inp_ctrl_inpsys_top_fsm_state)—Offset 89044h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ack_fsm_next_state			ack_fsm_current_state		cmd_fsm_next_state		cmd_fsm_current_state	

Bit Range	Default & Access	Description
31:24	0h RW	ack_fsm_next_state: Next state of top-ctrl Acknowledge FSM
23:16	0h RW	ack_fsm_current_state: Current state of top-ctrl Acknowledge FSM
15:8	0h RW	cmd_fsm_next_state: Next state of top-ctrl Command FSM
7:0	0h RW	cmd_fsm_current_state: Current state of top-ctrl Command FSM

15.8.821 reg_inp_sys_inp_ctrl_inpsys_captA_fsm_state_type (inp_sys_inp_ctrl_inpsys_captA_fsm_state)—Offset 89048h

Input System Controller captureA sub-ctrl current and next state info Register (FSM and DMA cmd state)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_inp_ctrl_inpsys_captA_fsm_state: [ISPMADR] + 89048h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)


ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
dma_cmd_next_state	dma_cmd_current_state		fsm_next_state			fsm_current_state		

Bit Range	Default & Access	Description
31:28	0h RW	dma_cmd_next_state: Next state of DMA cmd

15.8.822 reg_inp_sys_inp_ctrl_inpsys_captB_fsm_state_type
(inp_sys_inp_ctrl_inpsys_captB_fsm_state)—Offset 8904Ch



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_inp_ctrl_inpsys_capt_reserve_one_mem_region:
 [ISPMADR] + 89058h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_gpreg_str_multicastA_sel: [ISPMADR] + 8A000h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
unused_str_multicastA_sel									str_multicastA_sel



Access Method

inp_sys_gpreg_str_multicastB_sel: [ISPMADR] + 8A004h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								str_multicastB_sel
unused_str_multicastB_sel								

15.8.828 reg_inp_sys_gpreg_str_multicastC_sel_type
(inp_sys_gpreg_str_multicastC_sel)—Offset 8A008h

Access Method

inp_sys_gpreg_str_multicastC_sel: [ISPMADR] + 8A008h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_gpreg_str_mux_sel: [ISPMADDR] + 8A00Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_str_mux_sel								str_mux_sel

Bit Range	Default & Access	Description
31:2	0h RW	unused_str_mux_sel: Unused
1:0	0h RW	str_mux_sel: StreamMux_select

15.8.830 reg_inp_sys_gpreg_str_mon_status_type
(inp_sys_gpreg_str_mon_status)—Offset 8A010h

Streaming Monitor Status, [accept,valid] of streaming port



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_gpreg_str_mon_status: [ISPMADDR] + 8A010h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_str_mon_status		str_pixelB_deint_stat	str_pixelA_deint_stat	str_pixelB_stat	str_pixelA_stat	str_ctrl_out_stat	str_ctrl_in_stat	str_gensh_fifo_stat
						str_gensh_pkt_stat	str_mux_stat	str_captC_stat
								str_captB_stat
								str_captA_stat

Bit Range	Default & Access	Description
31:24	0h RW	unused_str_mon_status: Unused
23:22	0h RW	str_pixelB_deint_stat: Pixel B streaming output from Stream Deinterleaver
21:20	0h RW	str_pixelA_deint_stat: Pixel A streaming output from Stream Deinterleaver
19:18	0h RW	str_pixelB_stat: Pixel B streaming output from CSI receiver
17:16	0h RW	str_pixelA_stat: Pixel A streaming output from CSI receiver
15:14	0h RW	str_ctrl_out_stat: Control streaming output
13:12	0h RW	str_ctrl_in_stat: Control streaming input
11:10	0h RW	str_gensh_fifo_stat: Generic short FIFO streaming output
9:8	0h RW	str_gensh_pkt_stat: Generic short packet streaming output from CSI receiver
7:6	0h RW	str_mux_stat: Stream Mux streaming output
5:4	0h RW	str_captC_stat: Capture port C streaming output from CSI receiver
3:2	0h RW	str_captB_stat: Capture port B streaming output from CSI receiver
1:0	0h RW	str_captA_stat: Capture port A streaming output from CSI receiver



Access Method

inp_sys_gpreg_str_mon_irq_en: [ISPMADR] + 8A018h

ISPMADR Reference: [B:0, D:3, F:0] + 10h

	31				28				24				20				16				12				8				4				0			
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
																													str_pixelB_deint_irq_en							
																													str_pixelA_deint_irq_en							
																													str_pixelB_irq_en							
																													str_pixelA_irq_en							
																													str_ctrl_out_irq_en							
																													str_ctrl_in_irq_en							
																													str_gensh_fifo_irq_en							
																													str_gensh_pkt_irq_en							
																													str_mux_irq_en							
																													str_captC_irq_en							
																													str_captB_irq_en							
																													str_capfA_irq_en							

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
2	0h RW	str_captC_irq_en: Capture port C streaming output from CSI receiver
1	0h RW	str_captB_irq_en: Capture port B streaming output from CSI receiver
0	0h RW	str_captA_irq_en: Capture port A streaming output from CSI receiver

15.8.833 reg_inp_sys_gpreg_isys_srst_type (inp_sys_gpreg_isys_srst)—Offset 8A01Ch

Soft resets the modules of the input system. Writing a 1 to a field brings a module in reset, writing a 0 brings that module out of reset

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_gpreg_isys_srst: [ISPMADDR] + 8A01Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_isys_srst				srst_csi_rcv_be_out	srst_cfifo_acq	srst_cfifo_cap_c	srst_cfifo_cap_b	srst_cfifo_cap_a
				srst_dma	srst_wide_bus	srst_gensh_fifo	srst_cio2ahb	srst_str_mux
				srst_isys_top_ctrl	srst_isys_acq_ctrl	srst_isys_captC_sub_ctrl	srst_isys_captB_sub_ctrl	srst_isys_captA_sub_ctrl
				srst_acq	srst_capt_c	srst_capt_b	srst_capt_a	srst_multi_cast_c
								srst_multi_cast_b
								srst_multi_cast_a
								srst_capt_fifo_c
								srst_capt_fifo_b
								srst_capt_fifo_a

Bit Range	Default & Access	Description
31:25	0h RW	unused_isys_srst: Unused
24	0h RW	srst_csi_rcv_be_out: Soft resets the output of the csi receiver backend
23	0h RW	srst_cfifo_acq: Soft resets the control and acknowledge FIFOs for the acquisition unit
22	0h RW	srst_cfifo_cap_c: Soft resets the control and acknowledge FIFOs for capture unit C
21	0h RW	srst_cfifo_cap_b: Soft resets the control and acknowledge FIFOs for capture unit B
20	0h RW	srst_cfifo_cap_a: Soft resets the control and acknowledge FIFOs for capture unit A
19	0h RW	srst_dma: Soft resets the DMA



Bit Range	Default & Access	Description
18	0h RW	srst_wide_bus: Soft resets the wide bus including the CIO converter
17	0h RW	srst_gensh_fifo: Soft resets the generic short FIFO
16	0h RW	srst_cio2ahb: Soft resets the CIO2AHB adapter
15	0h RW	srst_str_mux: Soft resets the streaming mux
14	0h RW	srst_isys_top_ctrl: Soft resets the input system Top controller
13	0h RW	srst_isys_acq_ctrl: Soft resets the input system Acquisition sub-controller (controls data-path from selected captA/captB/captC/dma_acq to acq)
12	0h RW	srst_isys_captC_sub_ctrl: Soft resets the input system CaptureC sub-controller (controls data-path from captC to dma_captC)
11	0h RW	srst_isys_captB_sub_ctrl: Soft resets the input system CaptureB sub-controller (controls data-path from captB to dma_captB)
10	0h RW	srst_isys_captA_sub_ctrl: Soft resets the input system CaptureA sub-controller (controls data-path from captA to dma_captA)
9	0h RW	srst_acq: Soft resets the acquisition unit
8	0h RW	srst_capt_c: Soft resets the capture unit C
7	0h RW	srst_capt_b: Soft resets the capture unit B
6	0h RW	srst_capt_a: Soft resets the capture unit A
5	0h RW	srst_multi_cast_c: Soft resets multi cast C
4	0h RW	srst_multi_cast_b: Soft resets multi cast B
3	0h RW	srst_multi_cast_a: Soft resets multi cast A
2	0h RW	srst_capt_fifo_c: Soft resets the FIFO before multi cast C
1	0h RW	srst_capt_fifo_b: Soft resets the FIFO before multi cast B
0	0h RW	srst_capt_fifo_a: Soft resets the FIFO before multi cast A

15.8.834 **reg_inp_sys_gpreg_isys_slv_reg_srst_type** (inp_sys_gpreg_isys_slv_reg_srst)—Offset 8A020h

Soft resets the slave accessible registers of certain input system modules. Writing a 1 to a field brings the registers for a module to their default value, writing a 0 allows them to be overwritten

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_gpreg_isys_slv_reg_srst: [ISPMMAADR] + 8A020h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_isys_slv_reg_srst								srst_slv_reg_isys_ctrl
								srst_slv_reg_dma
								srst_slv_reg_acq
								srst_slv_reg_capt_c
								srst_slv_reg_capt_b
								srst_slv_reg_capt_a

Bit Range	Default & Access	Description
31:6	0h RW	unused_isys_slv_reg_srst: Unused
5	0h RW	srst_slv_reg_isys_ctrl: Soft resets the slave accessible registers of the input system controller
4	0h RW	srst_slv_reg_dma: Soft resets the slave accessible registers of the DMA
3	0h RW	srst_slv_reg_acq: Soft resets the slave accessible registers of the acquisition unit
2	0h RW	srst_slv_reg_capt_c: Soft resets the slave accessible registers of capture unit C
1	0h RW	srst_slv_reg_capt_b: Soft resets the slave accessible registers of capture unit B
0	0h RW	srst_slv_reg_capt_a: Soft resets the slave accessible registers of capture unit A

15.8.835 reg_inp_sys_gpreg_str_deint_portA_cnt_type (inp_sys_gpreg_str_deint_portA_cnt)—Offset 8A024h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_gpreg_str_deint_portA_cnt: [ISPMMAADR] + 8A024h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_str_deint_portB_cnt				str_deint_portB_cnt				

Bit Range	Default & Access	Description
31:16	0h RW	unused_str_deint_portB_cnt: Unused
15:0	0h RW	str_deint_portB_cnt: stream data count for portB of stream deinterleave block

October 2018
Document Number: 538136, Rev. 4.3



(inp_sys_fifo_adapter_CSI_generic_short_packet_available)—Offset 8B008h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_fifo_adapter_CSI_generic_short_packet_available
: [ISPMADDR] + 8B008h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_CSI_generic_short_packet_available								CSI_generic_short_packet_available

Bit Range	Default & Access	Description
31:1	0h RW	unused_CSI_generic_short_packet_available: Unused
0	1h RO	CSI_generic_short_packet_available: Returns 1 if there is a generic short packet available. Returns 0 if there is no generic short packet available.

15.8.838 reg_inp_sys_irq_ctrl_irq_edge_type (inp_sys_irq_ctrl_irq_edge)—Offset 8C000h

IRQ active edge select per interrupt input. Rising edge: 1, Falling edge: 0

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_irq_ctrl_irq_edge: [ISPMADDR] + 8C000h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

15.8.839 reg_inp_sys_irq_ctrl_irq_mask_type
(inp_sys_irq_ctrl_irq_mask)—Offset 8C004h

IRQ mask per interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_irq_ctrl_irq_mask: [ISPMADR] + 8C004h**ISPMADR Type:** PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31				28				24				20				16				12				8				4				0																																																							
0				0				0				0				0				0				0				0				0				0																																																			
unused_irq_edge																																																																																							
												strmon_irq																																																																											
												dma_irq				cio2ahb_irq																																																																							
																inpsys_ctrl_irq																																																																							
																acq_irq								captC_irq								captB_irq								captA_irq								csi_irq								csi_pkt_eol								csi_pkt_sol								csi_pkt_eof								csi_pkt_sof							

Bit Range	Default & Access	Description
31:19	0h RW	unused_irq_edge: Unused
18	0h RW	strmon_irq: Streaming monitor interrupt request
17	0h RO	dma_irq: DMA interrupt request
16	0h RW	cio2ahb_irq: CIO to AHB converter (for CSI receiver AHB slave) interrupt request
15:13	0h RW	inpsys_ctrl_irq: Input system controller interrupt request
12	0h RW	acq_irq: Acquisition unit interrupt request
11:10	0h RW	captC_irq: Capture unit C interrupt request
9:8	0h RW	captB_irq: Capture unit B interrupt request
7:6	0h RW	captA_irq: Capture unit A interrupt request
5:4	0h RW	csi_irq: CSI receiver interrupt request
3	0h RW	csi_pkt_eol: End of Line of Frame packet from CSI receiver
2	0h RW	csi_pkt_sol: Start of Line packet from CSI receiver
1	0h RW	csi_pkt_eof: End of Frame packet from CSI receiver
0	0h RW	csi_pkt_sof: Start of Frame packet from CSI receiver



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_irq_mask				strmon_irq	dma_irq	cio2ahb_irq	inpsys_ctrl_irq	acq_irq
								captC_irq
								captB_irq
								captA_irq
								csi_irq
								csi_pkt_eol
								csi_pkt_sol
								csi_pkt_eof
								csi_pkt_sof

Bit Range	Default & Access	Description
31:19	0h RW	unused_irq_mask: Unused
18	0h RW	strmon_irq: Streaming monitor interrupt request
17	0h RO	dma_irq: DMA interrupt request
16	0h RW	cio2ahb_irq: CIO to AHB converter (for CSI receiver AHB slave) interrupt request
15:13	0h RW	inpsys_ctrl_irq: Input system controller interrupt request
12	0h RW	acq_irq: Acquisition unit interrupt request
11:10	0h RW	captC_irq: Capture unit C interrupt request
9:8	0h RW	captB_irq: Capture unit B interrupt request
7:6	0h RW	captA_irq: Capture unit A interrupt request
5:4	0h RW	csi_irq: CSI receiver interrupt request
3	0h RW	csi_pkt_eol: End of Line of Frame packet from CSI receiver
2	0h RW	csi_pkt_sol: Start of Line packet from CSI receiver
1	0h RW	csi_pkt_eof: End of Frame packet from CSI receiver
0	0h RW	csi_pkt_sof: Start of Frame packet from CSI receiver

15.8.840 reg_inp_sys_irq_ctrl_irq_status_type (inp_sys_irq_ctrl_irq_status)—Offset 8C008h

IRQ status for each unmasked interrupt

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_irq_ctrl_irq_status: [ISPMADDR] + 8C008h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_irq_status				strmon_irq	dma_irq	cio2ahb_irq	inpsys_ctrl_irq	acq_irq
					captC_irq	captB_irq	captA_irq	csi_irq
						csi_pkt_eol	csi_pkt_sol	csi_pkt_eof
							csi_pkt_eof	csi_pkt_sof

Bit Range	Default & Access	Description
31:19	0h RW	unused_irq_status: Unused
18	0h RO	strmon_irq: Streaming monitor interrupt request
17	0h RO	dma_irq: DMA interrupt request
16	0h RO	cio2ahb_irq: CIO to AHB converter (for CSI receiver AHB slave) interrupt request
15:13	0h RO	inpsys_ctrl_irq: Input system controller interrupt request
12	0h RO	acq_irq: Acquisition unit interrupt request
11:10	0h RO	captC_irq: Capture unit C interrupt request
9:8	0h RO	captB_irq: Capture unit B interrupt request
7:6	0h RO	captA_irq: Capture unit A interrupt request
5:4	0h RO	csi_irq: CSI receiver interrupt request
3	0h RO	csi_pkt_eol: End of Line of Frame packet from CSI receiver
2	0h RO	csi_pkt_sol: Start of Line packet from CSI receiver
1	0h RO	csi_pkt_eof: End of Frame packet from CSI receiver
0	0h RO	csi_pkt_sof: Start of Frame packet from CSI receiver

15.8.841 reg_inp_sys_irq_ctrl_irq_clear_type (inp_sys_irq_ctrl_irq_clear)—Offset 8C00Ch

IRQ clear for interrupt set in irq_status



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_irq_ctrl_irq_clear: [ISPMMAADR] + 8C00Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_irq_clear				strmon_irq	dma_irq	cio2ahb_irq	inpsys_ctrl_irq	acq_irq
								captC_irq
								captB_irq
								captA_irq
								csi_irq
								csi_pkt_eol
								csi_pkt_sol
								csi_pkt_eof
								csi_pkt_sof

Bit Range	Default & Access	Description
31:19	0h RW	unused_irq_clear: Unused
18	0h WO	strmon_irq: Streaming monitor interrupt request
17	0h RO	dma_irq: DMA interrupt request
16	0h WO	cio2ahb_irq: CIO to AHB converter (for CSI receiver AHB slave) interrupt request
15:13	0h WO	inpsys_ctrl_irq: Input system controller interrupt request
12	0h WO	acq_irq: Acquisition unit interrupt request
11:10	0h WO	captC_irq: Capture unit C interrupt request
9:8	0h WO	captB_irq: Capture unit B interrupt request
7:6	0h WO	captA_irq: Capture unit A interrupt request
5:4	0h WO	csi_irq: CSI receiver interrupt request
3	0h WO	csi_pkt_eol: End of Line of Frame packet from CSI receiver
2	0h WO	csi_pkt_sol: Start of Line packet from CSI receiver
1	0h WO	csi_pkt_eof: End of Frame packet from CSI receiver
0	0h WO	csi_pkt_sof: Start of Frame packet from CSI receiver



15.8.842 reg_inpsys_irq_ctrl_irq_en_type (inp_sys_irq_ctrl_irq_en)– Offset 8C010h

IRQ enable per interrupt bit

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_irq_ctrl_irq_en: [ISPMADDR] + 8C010h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_irq_en				strmon_irq	dma_irq	cio2ahb_irq	inpsys_ctrl_irq	acq_irq
							captC_irq	captB_irq
								captA_irq
							csi_irq	
								csi_pkt_eol
								csi_pkt_sol
								csi_pkt_eof
								csi_pkt_sof

Bit Range	Default & Access	Description
31:19	0h RW	unused_irq_en: Unused
18	0h RW	strmon_irq: Streaming monitor interrupt request
17	0h RO	dma_irq: DMA interrupt request
16	0h RW	cio2ahb_irq: CIO to AHB converter (for CSI receiver AHB slave) interrupt request
15:13	0h RW	inpsys_ctrl_irq: Input system controller interrupt request
12	0h RW	acq_irq: Acquisition unit interrupt request
11:10	0h RW	captC_irq: Capture unit C interrupt request
9:8	0h RW	captB_irq: Capture unit B interrupt request
7:6	0h RW	captA_irq: Capture unit A interrupt request
5:4	0h RW	csi_irq: CSI receiver interrupt request
3	0h RW	csi_pkt_eol: End of Line of Frame packet from CSI receiver
2	0h RW	csi_pkt_sol: Start of Line packet from CSI receiver
1	0h RW	csi_pkt_eof: End of Frame packet from CSI receiver
0	0h RW	csi_pkt_sof: Start of Frame packet from CSI receiver



15.8.843 reg_inp_sys_irq_ctrl_irq_level_not_pulse_type (inp_sys_irq_ctrl_irq_level_not_pulse)—Offset 8C014h

IRQ setting per interrupt bit for level or pulse irq generation at output pin. Level: 1, Pulse: 0

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

inp_sys_irq_ctrl_irq_level_not_pulse: [ISPMADDR] + 8C014h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_irq_level_not_pulse				strmon_irq	dma_irq	cio2ahb_irq	inpsys_ctrl_irq	acq_irq
								captC_irq
								captB_irq
								captA_irq
								csi_irq
								csi_pkt_eol
								csi_pkt_sol
								csi_pkt_eof
								csi_pkt_sof

Bit Range	Default & Access	Description
31:19	0h RW	unused_irq_level_not_pulse: Unused
18	0h RW	strmon_irq: Streaming monitor interrupt request
17	0h RO	dma_irq: DMA interrupt request
16	0h RW	cio2ahb_irq: CIO to AHB converter (for CSI receiver AHB slave) interrupt request
15:13	0h RW	inpsys_ctrl_irq: Input system controller interrupt request
12	0h RW	acq_irq: Acquisition unit interrupt request
11:10	0h RW	captC_irq: Capture unit C interrupt request
9:8	0h RW	captB_irq: Capture unit B interrupt request
7:6	0h RW	captA_irq: Capture unit A interrupt request
5:4	0h RW	csi_irq: CSI receiver interrupt request
3	0h RW	csi_pkt_eol: End of Line of Frame packet from CSI receiver



Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_gp_syncgen_enable: Unused
0	0h RW	reg_gp_syncgen_enable: Enables (value=1) or disables (value=0) the Sync Generator.

15.8.845 reg_isel_gpr_reg_gp_syncgen_free_running_type
(isel_gpr_reg_gp_syncgen_free_running)—Offset 90004h

Default: 00000000h



15.8.847 `reg_isel_gpr_reg_gp_nr_frames_type`
(`isel_gpr_reg_gp_nr_frames`)—Offset 9000Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_nr_frames: [ISPMADR] + 9000Ch

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_nr_frames					reg_gp_nr_frames			

Bit Range	Default & Access	Description
31:14	0h RW	unused_reg_gp_nr_frames: Unused
13:0	0h RW	reg_gp_nr_frames: Sets the sync generator parameter Number of Frames

15.8.848 `reg_isel_gpr_reg_gp_syngen_nr_pix_type`
(`isel_gpr_reg_gp_syngen_nr_pix`)—Offset 90010h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_syngen_nr_pix: [ISPMADR] + 90010h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_syngen_nr_pix					reg_gp_syngen_nr_pix			

Bit Range	Default & Access	Description
31:14	0h RW	unused_reg_gp_syngen_nr_pix: Unused
13:0	0h RW	reg_gp_syngen_nr_pix: Sets the number of active pixels per line in the Sync Generator

15.8.849 reg_isel_gpr_reg_gp_syngen_nr_lines_type
(isel_gpr_reg_gp_syngen_nr_lines)—Offset 90014h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
isel_gpr_reg_gp_syngen_nr_lines: [ISPMMAADR] + 90014h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_syngen_nr_lines					reg_gp_syngen_nr_lines			

Bit Range	Default & Access	Description
31:14	0h RW	unused_reg_gp_syngen_nr_lines: Unused
13:0	0h RW	reg_gp_syngen_nr_lines: Sets the number of lines per frame in the Sync generator



15.8.850 reg_isel_gpr_reg_gp_syngen_hblank_cycles_type (isel_gpr_reg_gp_syngen_hblank_cycles)—Offset 90018h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_syngen_hblank_cycles: [ISPMADDR] + 90018h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_syngen_hblank_cycles				reg_gp_syngen_hblank_cycles				

Bit Range	Default & Access	Description
31:14	0h RW	unused_reg_gp_syngen_hblank_cycles: Unused
13:0	0h RW	reg_gp_syngen_hblank_cycles: Sets the number of cycles between the end-of-line and start-of-line pulses.

15.8.851 reg_isel_gpr_reg_gp_syngen_vblank_cycles_type (isel_gpr_reg_gp_syngen_vblank_cycles)—Offset 9001Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_syngen_vblank_cycles: [ISPMADDR] + 9001Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_isel_sof								
reg_gp_isel_sof								

Intel Atom® Processor E3800 Product Family
Datasheet
1715



Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_gp_isel_sol: Unused
0	0h RW	reg_gp_isel_sol: Sets the input selector gp_sol input.

15.8.855 `reg_isel_gpr_reg_gp_isel_eol_type`
(`isel_gpr_reg_gp_isel_eol`)—Offset 9002Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
isel_gpr_reg_gp_isel_eol: [ISPMADR] + 9002Ch
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:1	0h RW	unused_reg_gp_isel_eol: Unused
0	0h RW	reg_gp_isel_eol: Sets the input selector gp_eol input.

15.8.856 reg_isel_gpr_reg_gp_isel_lfsr_enable_type
(isel gpr reg gp isel lfsr enable)—Offset 90030h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_isel_lfsr_enable: [ISPMADR] + 90030h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
				unused_reg_gp_isel_lfsr_enable_b					reg_gp_isel_lfsr_enable_b

Intel Atom® Processor E3800 Product Family
Datasheet
1718



Bit Range	Default & Access	Description
0	0h RW	reg_gp_isel_lfsr_enable_b: Enables the PRBS for port b

15.8.858 reg_isel_gpr_reg_gp_isel_lfsr_reset_value_type
(isel_gpr_reg_gp_isel_lfsr_reset_value)—Offset 90038h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
isel_gpr_reg_gp_isel_lfsr_reset_value: [ISPMMAADR] + 90038h
```

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31	0h RW	unused_reg_gp_isel_lfsr_reset_value: Unused
30:0	0h RW	reg_gp_isel_lfsr_reset_value: Set the reset value of the LFSR in the PRBS of the Input selector

15.8.859 reg_isel_gpr_reg_gp_isel_tpg_enable_type
(isel_gpr_reg_gp_isel_tpg_enable)—Offset 9003Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_isel_tpg_enable: [ISPMADR] + 9003Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_isel_tpg_enable_b								
reg_gp_isel_tpg_enable_b								

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
0	0h RW	reg_gp_isel_tpg_enable_b: Enables the test pattern generator for port b

15.8.861 **reg_isel_gpr_reg_gp_isel_hor_cnt_mask_type**
(isel_gpr_reg_gp_isel_hor_cnt_mask)—Offset 90044h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
isel qpr req qp isel hor cnt mask: [ISPMADR] + 90044h
```

ISPMMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
unused_reg_gp_isel_hor_cnt_mask					reg_gp_isel_hor_cnt_mask			

Bit Range	Default & Access	Description
31:14	0h RW	unused_reg_gp_isel_hor_cnt_mask: Unused
13:0	0h RW	reg_gp_isel_hor_cnt_mask: Sets the horizontal counter mask in the Input selector

15.8.862 reg_isel_gpr_reg_gp_isel_ver_cnt_mask_type
(isel_gpr_reg_gp_isel_ver_cnt_mask)—Offset 90048h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_isel_ver_cnt_mask: [ISPMADR] + 90048h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:14	0h RW	unused_reg_gp_isel_ver_cnt_mask: Unused
13:0	0h RW	reg_gp_isel_ver_cnt_mask: Sets the vertical counter mask in the Input selector

15.8.863 reg_isel_gpr_reg_gp_isel_xy_cnt_mask_type (isel_gpr_reg_gp_isel_xy_cnt_mask)—Offset 9004Ch

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_isel_xy_cnt_mask: [ISPMADDR] + 9004Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:12	0h RW	unused_reg_gp_isel_xy_cnt_mask: Unused



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)
ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_isel_tpg_mode reg_gp_isel_tpg_mode								

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)
ISPMADR Reference: [B:0, D:3, F:0] + 10h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
unused_reg_gp_isel_tpg_blue1																reg_gp_isel_tpg_blue1																			

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

ISPMADR Type: PCI Configuration Register (Size: 32 bits)
ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_isel_tpg_blue2						reg_gp_isel_tpg_blue2		

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_syncgen_hor_cnt: [ISPMADR] + 90088h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_reg_gp_syncgen_hor_cnt					reg_gp_syncgen_hor_cnt			

Bit Range	Default & Access	Description
31:14	0h RW	unused_reg_gp_syncgen_hor_cnt: Unused
13:0	0h RO	reg_gp_syncgen_hor_cnt: Returns the value of the horizontal counter in the sync generator

15.8.879 **reg_isel_gpr_reg_gp_syncgen_ver_cnt_type**
(isel_gpr_reg_gp_syncgen_ver_cnt)—Offset 9008Ch

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_syncgen_ver_cnt: [ISPMADR] + 9008Ch

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



15.8.881 **reg_isel_gpr_reg_gp_soft_reset_type**
(isel_gpr_reg_gp_soft_reset)—Offset 90094h

Soft resets the modules in the input selector cluster

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_gpr_reg_gp_soft_reset: [ISPMADDR] + 90094h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								unused_reg_gp_soft_reset
								srst_fifo
								srst_tpg
								srst_prbs
								srst_syncen

Bit Range	Default & Access	Description
31:4	0h RW	unused_reg_gp_soft_reset: Unused
3	0h RW	srst_fifo: If 1, the fifo is held in reset mode. If 0, the fifo is not in reset state.
2	0h RW	srst_tpg: If 1, the TPG is held in reset mode. If 0, the TPG is not in reset state.
1	0h RW	srst_prbs: If 1, the PRBS is held in reset mode. If 0, the PRBS is not in reset state.
0	0h RW	srst_syncgen: If 1, the sync generator is held in reset mode. If 0, the sync generator is not in reset state.

15.8.882 reg_isel_fa_send_to_GP_FIFO_type
(isel_fa_send_to_GP_FIFO)—Offset 90100h


Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel fa send to GP FIFO: [ISPMADR] + 90100h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h



Bit Range	Default & Access	Description
31:26	0h RW	unused_send_to_GP_FIFO: Unused
25:0	0h WO	send_to_GP_FIFO: Send data to input selector GP FIFO

Access Method

isel_fa_check_send_to_GP_FIFO: [ISPMMAADR] + 90108h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h

Bit Range	Default & Access	Description
31:1	0h RW	unused_check_send_to_GP_FIFO: Unused
0	1h WO	check_send_to_GP_FIFO: Check for availability of GP FIFO. Returns 1 if a word can be send to the input selector, without it being stalled



Bit Range	Default & Access	Description
31:4	0h RW	unused_reg_irq_mask: Unused
3:0	0h RW	reg_irq_mask: indicates for each bit of irq_di whether it can generate an interrupt request (value='1') or not (value='0'). Setting will affect reg_irq_value as well as IRQ output pin

15.8.886 **reg_isel_irq_ctrl_reg_irq_status_type**
(isel irq ctrl reg irq status)—Offset 90208h

Indicates for each bit whether a non-masked interrupt has been generated (value='1'). Can be cleared by writing a '1' into the the corresponding bit of the req_irq_clear register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
isel irq ctrl reg irq status: [ISPMMAADR] + 90208h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
unused_reg_irq_status									irq_stat_syncgen_eol
									irq_stat_syncgen_sol
									irq_stat_syncgen_eof
									irq_stat_syncgen_sof

Bit Range	Default & Access	Description
31:4	0h RW	unused_reg_irq_status: Unused
3	0h RO	irq_stat_syncgen_eol: Represents the irq status of the eol (end of line) bit generated by the sync generator
2	0h RO	irq_stat_syncgen_sol: Represents the irq status of the sol (start of line) bit generated by the sync generator
1	0h RO	irq_stat_syncgen_eof: Represents the irq status of the eof (end of frame) bit generated by the sync generator
0	0h RO	irq_stat_syncgen_sof: Represents the irq status of the sof (start of frame) bit generated by the sync generator

15.8.887 `reg_isel_irq_ctrl_reg_irq_clear_type`
(isel irq ctrl reg irq clear)—Offset 9020Ch

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_irq_ctrl_reg_irq_clear: [ISPMMAADR] + 9020Ch

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_reg_irq_clear								reg_irq_clear

Bit Range	Default & Access	Description
31:4	0h RW	unused_reg_irq_clear: Unused
3:0	0h WO	reg_irq_clear: Clears (set to '0') bits in reg_irq_status. When writing a '1' into a bit of this register, the corresponding bit in the req_irq_status is cleared. When writing a '0' into a bit of this register, the corresponding bit in the req_irq_status is not affected.

15.8.888 reg_isel_irq_ctrl_reg_irq_enable_type (isel_irq_ctrl_reg_irq_enable)—Offset 90210h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

isel_irq_ctrl_reg_irq_enable: [ISPMMAADR] + 90210h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
unused_reg_irq_enable								reg_irq_enable

Bit Range	Default & Access	Description
31:4	0h RW	unused_reg_irq_enable: Unused
3:0	0h RW	reg_irq_enable: Indicates for each bit whether an interrupt cause as monitored by the req_irq_status register also affects the IRQ pin (value='1') or not (value='0')



Type: Memory Mapped I/O Register
(Size: 32 bits)

icache_out_sys_c_mmu_MMU_page_table_base:
[ISPMMAADR] + A0004h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_MMU_page_table_base				MMU_page_table_base				

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
23:0	0h RW	MMU_page_table_base: Defines the physical page number of the page tables

15.8.892 mem_scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_first_type (scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_first)—Offset B0000h

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_first: [ISPMMAADR] + B0000h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
prg_mem_first																

Bit Range	Default & Access	Description
63:0	0h RW	prg_mem_first: Read Latency of 1 cycles. Write latency of 0 cycles

15.8.893 mem_scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_last_type (scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_last)—Offset B7FF8h

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

scp_config_ilm_conf_ilm_prg_mem_sl_ip_pmem_prg_mem_last: [ISPMMAADR] + B7FF8h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
prg_mem_last																



Bit Range	Default & Access	Description
15:12	0b RO	RSVD0: Reserved
11:0	0h RW	asp_lut_first: Read Latency of 67 cycles. Write latency of 0 cycles

```
15.8.895 mem_isp_simd_vamem1_asp_lut_sl_ipvamem_asp_lut_last_type (isp_simd_vamem1_asp_lut_sl_ipvamem_asp_lut_last)-  
Offset 1C0FFeh
```

15	12	8	4	0
0	0	0	0	0
RSVD0		asp_lut_last		



Bit Range	Default & Access	Description
15:12	0b RO	RSVD0: Reserved
11:0	0h RW	asp_lut_last: Read Latency of 67 cycles. Write latency of 0 cycles

15.8.896 mem_isp_simd_vamem2_asp_lut_sl_ipvamem_asp_lut_first_type (isp_simd_vamem2_asp_lut_sl_ipvamem_asp_lut_first)—
Offset 1D0000h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

isp_simd_vamem2_asp_lut_sl_ipvamem_asp_lut_first:
[ISPMADDR] + 1D0000h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000h

	15			12				8				4				0
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	RSVD0				casp_lut_first											

Bit Range	Default & Access	Description
15:12	0b RO	RSVD0: Reserved
11:0	0h RW	asp_lut_first: Read Latency of 67 cycles. Write latency of 0 cycles

15.8.897 mem_isp_simd_vamem2_asp_lut_sl_ipvamem_asp_lut_last_type (isp_simd_vamem2_asp_lut_sl_ipvamem_asp_lut_last) — Offset 1D0FFh

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

isp_simd_vamem2_esp_lut_sl_ipvamem_esp_lut_last:
[ISPMMAADR] + 1D0FFeh

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 0000h

[illegible]



Type: Memory Mapped I/O Register
(Size: 16 bits)

isp_simd_vamem3_asp_lut_sl_ipvamem_asp_lut_first:
[ISPMADDR] + 1E0000h

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

	15		12			8			4			0
	0	0	0	0	0	0	0	0	0	0	0	0
RSVD0					asp_lut_first							

Bit Range	Default & Access	Description
15:12	0b RO	RSVD0: Reserved
11:0	0h RW	asp_lut_first: Read Latency of 67 cycles. Write latency of 0 cycles

```
15.8.899 mem_isp_simd_vamem3_esp_lut_sl_ipvamem_esp_lut_last_type (isp_simd_vamem3_esp_lut_sl_ipvamem_esp_lut_last)-
Offset 1E0FFh
```

Type: Memory Mapped I/O Register
(Size: 16 bits)

isp_simd_vamem3_esp_lut_sl_ipvamem_esp_lut_last:
[ISPMMAADR] + 1E0FFh

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

	15		12				8				4				0
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	RSVD0				asp_lut_last										



Bit Range	Default & Access	Description
15:12	0b RO	RSVD0: Reserved
11:0	0h RW	asp_lut_last: Read Latency of 67 cycles. Write latency of 0 cycles

15.8.900 `mem_isp_simd_histogram_asp_histogram_sl_iphist_asp_histogram_`
`ram_first_type`
`(isp_simd_histogram_asp_histogram_sl_iphist_asp_histogram`
`first)—Offset 1F0000h`

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

```
isp_simd_histogram_esp_histogram_sl_iphist_esp_histogram
am first: 1ISPMMADRT + 1F0000h
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0				asp_histogram_first				

Bit Range	Default & Access	Description
31:24	0b RO	RSVD0: Reserved
23:0	0h RW	asp_histogram_first: Read Latency of 66 cycles. Write latency of 0 cycles

15.8.901 `mem_isp_simd_histogram_asp_histogram_sl_iphist_asp_histogram_`
`ram_last_type`
`(isp_simd_histogram_asp_histogram_sl_iphist_asp_histogram_`
`_last)—Offset 1F0FFCh`

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

```
isp_simd_histogram_esp_histogram_sl_iphist_esp_histogram
am_last: [ISPMMADR] + 1F0FFCh
```

ISPMADR Type: PCI Configuration Register (Size: 32 bits)

ISPMADR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register (Size: 32 bits)

isp_base_dmem_data_mem_sl_ipdmem_data_mem_first: [ISPMMAADR] + 200000h

ISPMMAADR Type: PCI Configuration Register (Size: 32 bits)

ISPMMAADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
data_mem_first								

Bit Range	Default & Access	Description
31:0	0h RW	data_mem_first: Read Latency of 2 cycles. Write latency of 0 cycles

15.8.903 mem_isp_base_dmem_data_mem_sl_ipdmem_data_mem_last_type
(isp_base_dmem_data_mem_sl_ipdmem_data_mem_last)–
Offset 203FFCh

Intel Atom® Processor E3800 Product Family
Datasheet
1746



Memory dump showing a 32-bit address range from 0 to 31. The address 16 is highlighted, and the label 'mem_last' is positioned next to it.

Bit Range	Default & Access	Description
31:0	0h RW	mem_last: Read Latency of 2 cycles. Write latency of 0 cycles

15.8.906 reg_fa_sp_isp_send_to_SP_type (fa_sp_isp_send_to_SP)– Offset 380008h

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
send_to_SP								

Bit Range	Default & Access	Description
31:0	0h WO	send_to_SP: Send data to SP streaming input port

**15.8.907 reg_fa_sp_isp_send_to_ISP_type (fa_sp_isp_send_to_ISP)–
Offset 38000Ch**

ISPMMADR Reference: [B:0, D:3, F:0] + 10h

[illegible]



Bit Range	Default & Access	Description
31:0	0h WO	send_to_ISP: Send data to ISP streaming input port

15.8.908 reg_fa_sp_isp_check_receive_from_SP_type (fa_sp_isp_check_receive_from_SP)—Offset 380010h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

fa_sp_isp_check_receive_from_SP: [ISPMADDR] + 380010h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_check_receive_from_SP								check_receive_from_SP

Bit Range	Default & Access	Description
31:1	0h RW	unused_check_receive_from_SP: Unused
0	1h RO	check_receive_from_SP: Check for potential stalling for receiving data on SP streaming output port. Returns 1 if a receive from SP would lead to a stall. Returns 0 if a token is available from the SP.

15.8.909 reg_fa_sp_isp_check_receive_from_ISP_type (fa_sp_isp_check_receive_from_ISP)—Offset 380014h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

fa_sp_isp_check_receive_from_ISP: [ISPMADDR] + 380014h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000001h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
unused_check_receive_from_ISP								check_receive_from_ISP

Bit Range	Default & Access	Description
31:1	0h RW	unused_check_receive_from_ISP: Unused
0	1h RO	check_receive_from_ISP: Check for potential stalling for receiving data on ISP streaming output port. Returns 1 if a receive from ISP would lead to a stall. Returns 0 if a token is available from the ISP.

15.8.910 reg_fa_sp_isp_check_send_to_SP_type (fa_sp_isp_check_send_to_SP)—Offset 380018h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

fa_sp_isp_check_send_to_SP: [ISPMADDR] + 380018h

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_check_send_to_SP								check_send_to_SP

Bit Range	Default & Access	Description
31:1	0h RW	unused_check_send_to_SP: Unused
0	0h RO	check_send_to_SP: Check for potential stalling for sending data to SP streaming input port. Returns 1 if a send to SP would lead to a stall. Returns 0 when there is space left in the SP token FIFO



15.8.911 reg_fa_sp_isp_check_send_to_ISP_type (fa_sp_isp_check_send_to_ISP)—Offset 38001Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

fa_sp_isp_check_send_to_ISP: [ISPMADDR] + 38001Ch

ISPMADDR Type: PCI Configuration Register (Size: 32 bits)

ISPMADDR Reference: [B:0, D:3, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
unused_check_send_to_ISP								check_send_to_ISP

Bit Range	Default & Access	Description
31:1	0h RW	unused_check_send_to_ISP: Unused
0	0h RO	check_send_to_ISP: Check for potential stalling for sending data to ISP streaming input port. Returns 1 if a send to ISP would lead to a stall. Returns 0 when there is space left in the ISP token FIFO


16 Storage Control Cluster (eMMC, SDIO, SD Card)

The Storage Control Cluster (SCC) consists of SDIO, SD Card and eMMC controllers to support mass storage and IO devices.

- One eMMC 4.5 interface
- One SD Card 3.0 interface
- One SDIO 3.0 interface for SDIO-based WIFI

Note: All units in the SCC support both PCI mode and ACPI mode of operation. A level shifter may be needed on the platform for SDIO 3.0 compliance. An eMMC 4.41 controller also exists but shouldn't be used.

Note: eMMC* 5.0 is functional and backward compatible on the Bay Trail platform for features included in eMMC 4.5, with no guarantees the performance is as good as eMMC* 4.5.



16.1 Signal Descriptions

See [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function




Table 181. eMMC Signals

Signal Name	Direction Power	Description
MMC1_CLK	O V1P8S	eMMC Clock The frequency may vary between 400 kHz and 200 MHz.
MMC1_D[7:0]	I/O V1P8S	eMMC Port Data bits 0 to 7 Bidirectional port used to transfer data to and from eMMC device. By default, after power up or reset, only D[0] is used for data transfer. A wider data bus can be configured for data transfer, using either D[0]-D[3] or D[0]-D[7], by the MultiMedia Card controller. The MultiMedia Card includes internal pull-ups for data lines D[1]-D[7]. Immediately after entering the 4-bit mode, the card disconnects the internal pull ups of lines D[1], D[2], and D[3]. Correspondingly, immediately after entering to the 8-bit mode the card disconnects the internal pull-ups of lines D[1]-D[7].
MMC1_CMD	I/O V1P8S	eMMC Port Command This signal is used for card initialization and transfer of commands. It has two modes—open-drain for initialization, and push-pull for fast command transfer.
MMC1_RCOMP	-	eMMC RCOMP This signal is used for pre-driver slew rate compensation.
MMC1_RST#	O V1P8S	eMMC Reset Signals Active low to reset.

Table 182. SDIO Signals

Signal Name	Direction Power	Description
SD2_CLK	O V1P8S	SDIO Clock The frequency may vary between 24 and 50MHz.
SD2_D[2:0]	I/O V1P8S	SDIO Port Data bits 0 to 2 Bidirectional port used to transfer data to and from SDIO device. By default, after power up or reset, only D[0] is used for data transfer. A wider data bus can be configured for data transfer, using D[0]-D[3].
SD2_D[3]_CD#	I/O V1P8S	SDIO Port Data bit 3 Bidirectional port used to transfer data to and from the SDIO device. Also, Card Detect . Active low when device is present.
SD2_CMD	I/O V1P8S	SDIO Port Command This signal is used for card initialization and transfer of commands. It has two modes—open-drain for initialization, and push-pull for fast command transfer.




Table 183. SD Card Signals

Signal Name	Direction Power	Description
SD3_CLK	O VSDIO	SD Card Clock The frequency may vary between 24 and 50 MHz.
SD3_D[3:0]	I/O VSDIO	SD Card Data bits 0 to 3 Bidirectional port used to transfer data to and from SD card. By default, after power up or reset, only D[0] is used for data transfer. A wider data bus can be configured for data transfer, using D[0]-D[3].
SD3_CD#	I/O V1P8S	SD Card Detect Active low when a card is present. Floating (pulled high with internal PU) when a card is not present.
SD3_CMD	I/O VSDIO	SD Card Command This signal is used for card initialization and transfer of commands. It has two modes—open-drain for initialization, and push-pull for fast command transfer.
SD3_1P8EN	O V1P8S	SD Card 1.8V Enable Indicates the voltage of the SD Card to the power delivery subsystem. The default voltage (3.3 V) is requested when this signal is driven low. 1.8 V is requested when this signal is high. This voltage change applies to the SD3_V1P8V3P3_S3 (VSDIO) rail on the SoC.
SD3_RCOMP	-	SD Card RCOMP This signal is used for pre-driver slew rate compensation.
SD3_WP	I V1P8S	SD Card Write Protect Active high to protect from write.
SD3_PWREN#	O V1P8S	SD Card Power Enable This signal is used to enable power on a SD device.

16.2 Features

16.2.1 eMMC Interface Features

- eMMC 4.5 controller supported
- Transfers the data in 1 bit, 4 bit and 8 bit modes.
- Transfers data in the following speed classes: Baseline (1, 4, 8 bit up to 25Mhz), HS SDR/DDR (4, 8 bit up to 50Mhz) and HS200 (4, 8 bit up to 200MHz - 4.5 controller only)
- Cyclic Redundancy Check CRC7 for command and CRC16 for data integrity.
- Supports MMC Plus and MMC mobile.
- Supports both round-robin and priority-based arbitration for transmit operation.
- Run-time configurability of channel ID bits.



16.2.2 SDIO/SD Card Interface Features

- Up to 400Mbps per second data rate using 4 parallel data lines.
- Transfers the data in 1 bit and 4 bit SD modes and SPI mode.
- Transfers the data in following UHS-I modes: HS ,DDR50 and SDR12/25.
- Cyclic Redundancy Check CRC7 for command and CRC16 for data integrity.
- Designed to work with I/O cards, Read-only cards and Read/Write cards.
- Supports Read wait Control, Suspend/Resume operation.

Note: SDIO only validated with WIFI devices.

16.2.3 Storage Interfaces Overview


This section provides a very high level overview of the SD, SDIO, eMMC 4.5 specification. Refer to the SD and eMMC specifications for complete details.

16.2.3.1 SD Card 3.0 Bus Interface

The SD Card bus has a single master, single slaves (card), synchronous topology (refer to [Figure 98](#)). During initialization process commands are sent to the card, allowing the application to detect the card and assign logical addresses to the physical slot. All data communication in the Card Identification Mode uses the command line (CMD) only.

SD bus allows dynamic configuration of the number of data lines. After power up, by default, the SD Card will use only SD3_D[0] for data transfer. After initialization the host can change the bus width (number of active data lines). This feature allows easy trade off between hardware cost and system performance. Note that while DAT1-SD3_D[3:1] are not in use, the SoC will tri-state those signals.

Figure 98. SD Memory Card Bus Topology




16.2.3.2 SDIO 3.0 Interface

The SDIO interface is the very much like the SD card interface. The SoC supports one SDIO device for wireless devices only (no memory card support).


Note: SDIO interface does not support WAKE function.

Figure 99. SDIO Device Bus Topology



16.2.3.3 eMMC4.5 Interface


Figure 100.eMMC Interface



16.3 References

The controller is configured to comply with:

- SD Specification Part 01 Physical Layer Specification version 3.00, April 16, 2009
- SD Specification Part E1 SDIO Specification version 3.00, December 16, 2010
- SD Specification Part A2 SD Host Controller Standard Specification version 3.00, February 18, 2010
- SD Specification Part 03 security Specification version 1.01, April 15, 2001




- Embedded MultiMedia Card (eMMC) Product Standard v4.51, JESD84-A451

16.4 Register Map

Refer to [Chapter 3, "Register Access Methods"](#) and [Chapter 4, "Mapping Address Spaces"](#) for additional information.

Figure 101.Storage Control Cluster Register Map





Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Device ID (DEVICEID): Device ID identifies the particular AHB device. This is tied to a strap at the top level.
15:0	0000h RO	Vendor ID (VENDORID): Vendor ID is a unique ID provided by PCI SIG which identifies the manufacturer of the device. This is tied to a strap at the top level.

16.5.2 Status and Command Register (STATUSCOMMAND)—Offset 4h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + 4h

Default: 00100000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0	RMA	RCA	Reserved1	CAPLIST	INTR_STATUS	Reserved2	Reserved3	INTR_DISABLE
								Reserved4
								SERR_ENABLE
								Reserved5
								BME
								MSE
								Reserved6

Bit Range	Default & Access	Field Name (ID): Description
31:30	0h RO	Reserved0: Reserved.
29	0h RW/1C	Received Master Abort (RMA): If the completion status received from IOSF is UR, Bridge sets this bit. S/W writes a '1' to this bit to clear it. This bit will not be set for the Fabric port. This bit is not used for the Fabric Port
28	0h RW/1C	Received Target Abort (RCA): If the completion status received from IOSF is CA, Bridge sets this bit. S/W writes a 1 to this bit to clear it. This bit will not be set for the fabric port. This bit is not used for the Fabric Port
27:21	00h RO	Reserved1: Reserved.
20	1h RO	Capabilities List (CAPLIST): Hardwired to 1. Indicates that the controller contains a capabilities pointer list. The first item is pointed to by looking at configuration offset 34h. If PM capability is not required then this bit should be tied to 0.
19	0h RO	Interrupt Status (INTR_STATUS): This bit reflects state of interrupt in the device. Only when the Interrupt Disable bit in the command register is a 0 and this Interrupt Status bit is a 1, will the device's/function's INTx# signal be asserted. Setting the Interrupt Disable bit to a 1 has no effect on the state of this bit. This bit reflects Legacy interrupt status.
18:16	0h RO	Reserved2: Reserved.
15:11	00h RO	Reserved3: Reserved.
10	0h RW	Interrupt Disable (INTR_DISABLE): Setting this bit disables INTx assertion from Bridge. The interrupt disabled is legacy INTx# interrupt; i.e., Bridge does not send Interrupt Assert message through the IOSF SideBand Channel. Reset value of this bit is 0.
9	0h RO	Reserved4: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
8	0h RW	SERR# Enable (SERR_ENABLE): This bit controls the sending of DO_SERR messages on IOSF SB.
7:3	00h RO	Reserved5: Reserved.
2	0h RW	Bus Master Enable (BME): If this bit is 0, Bridge does not generate any new upstream transaction on IOSF as a master. Reset value of this bit is 0.
1	0h RW	Memory Space Enable (MSE): This bit controls Bridges response to downstream memory accesses. When set, accesses to the memory space of the device are enabled. Reset value of this bit is 0.
0	0h RO	Reserved6: Reserved.

16.5.3 Revision ID and Class Code Register (REVCLASSCODE)—Offset 8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + 8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Class Code (CLASS_CODES): This register is read-only and is used to identify the generic function of the device and, in some cases, a specific register level programming interface. The register is broken into three byte size fields. The upper byte (at offset 0Bh) is a base class code which broadly classifies the type of function the device performs. The middle byte (at offset 0Ah) is a sub-class code which identifies more specifically the function of the device. The lower byte (at offset 09h) identifies a specific register-level programming interface (if any) so that device independent software can interact with the device. This register is tied to a strap at the top level.
7:0	00h RO	Revision ID (RID): Identifies the revision of a particular AHB device. This is tied to a strap at the top level.

16.5.4 Cache Line Size, Latency Timer, and Header Type Register (CLLATHEADERBIST)—Offset Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + Ch

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0	MULFNDEV	HEADERTYPE	LATTIMER	CACHELINE_SIZE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	0h RO	Multifunction Device (MULFNDEV): This bit is always 0 for non-fabric ports. For fabric ports it is driven from the fabric_mult_function strap. A value of 1 indicates a multifunction device; a value of 0 indicates a single function device.
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Doesn't apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

16.5.5 Base Address Register (BAR)—Offset 10h

Each AHB device is a single function device with only a single BAR associated with it. Bits 31:4 indicate the Base Address register. Power-up software can determine how much address space the AHB Device requires by writing a value of all 1's to the register and then reading the value back. Bridge will return 0's in all don't-care address bits, effectively specifying the address space required. Unimplemented Base Address registers are hardwired to zero. This is the Size Indicator Read only bits of the register.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR	SIZEINDICATOR	PREFETCHABLE	TYPE	MESSAGE_SPACE				

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1s.



Bit Range	Default & Access	Field Name (ID): Description
11:4	00h RO	Size Indicator (Read Only) (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0s.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this bar is not prefetchable.
2:1	0h RO	Type (TYPE): '00' indicates that the BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE): 0 Indicates that this BAR is present in the memory space.

16.5.6 Base Address Register 1 (BAR1)—Offset 14h

Memory accesses to BAR1 region access the PCI configuration space for the LPIO device. BAR1 region is always 4K. However SW accesses through BAR1 should only access the regular PCI configuration space. BAR1 memory accesses which do not access a defined PCI configuration register are treated as accesses to a reserved register.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + 14h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		
						PREFETCHABLE1		
						TYPE1		
						MESSAGE_SPACE1		

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address Register1 (BASEADDR1): This field is present if BAR1 is enabled through private config space. If this register is disabled then this is RO and always returns 0.
11:4	00h RO	Size Indicator1 (SIZEINDICATOR1): Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE1): Indicates that this bar is not prefetchable.
2:1	0h RO	Type (TYPE1): '00' indicates that the BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE1): 0 Indicates that this BAR is present in the memory space.



16.5.8 Expansion ROM Base Address Register (EXPANSION_ROM_BASEADDR)—Offset 30h



16.5.9 Capabilities Pointer Register (CAPABILITYPTR)—Offset 34h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + 34h

Default: 00000080h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.
7:0	80h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. When PM capability is disabled, this register is 00h.

16.5.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
MAX_LAT				MIN_GNT				INTLINE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates that the device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates that the device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to communicate to software the interrupt line that the interrupt pin is connected to.



16.5.11 Power Management Capability ID Register (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + 80h

Default: 48030001h

31	28	24	20	16	12	8	4	0
0	1	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
PMESUPPORT				Reserved0				
				VERSION				
				NXTCAP				
				POWER_CAP				

Bit Range	Default & Access	Field Name (ID): Description
31:27	09h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. bit(11) X XXX1b - PME# can be asserted from D0 bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. bit(14) X 1XXXb - PME# can be asserted from D3hot. bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the private configuration space PME_Support XORed with the PME_Support strap.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.

16.5.12 Power Management Control and Status Register (PMECTRLSTATUS)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0					PMESTATUS	Reserved1		PMEEENABLE
								Reserved2
								NO_SOFT_RESET
								Reserved3
								POWERSTATE



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit in this register.
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.
3	1h RO	No Soft Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for upstream decode on fabric ports.

16.5.13 General Purpose Read Write Register1 (GEN_REGRW1)—Offset A0h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + A0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

GEN_REG_RW1

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	GEN_REG_RW1: capabilities over-ride for the sd/sdio/emmc host controller (bits 31:0)



16.5.14 General Purpose Read Write Register2 (GEN_REGRW2)—Offset A4h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + A4h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
CAP_REG_SEL	GEN_REG_RW2							

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	CAP_REG_SEL: select if the capability will come from the GEN PCI register or from a hard wire
30:0	0h RW	GEN_REG_RW2: capabilities over-ride for the sd/sdio/emmc host controller (bits 62:32)

16.5.15 General Purpose Read Write Register3 (GEN_REGRW3)—Offset A8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + A8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
GEN_REG_RW3								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	GEN_REG_RW3: Reserved.

16.5.16 General Purpose Read Write Register4 (GEN_REGRW4)—Offset ACh

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:17, F:0] + ACh



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



16.6 SDIO for Wifi Memory Mapped IO Registers

Table 185. Summary of SDIO for Wifi Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"SDMA System Address / Argument 2 Register (SYS_ADR)—Offset 0h" on page 1772	00000000h
4–5h	2	"Block Size Register (BLK_SIZE)—Offset 4h" on page 1773	0000h
6–7h	2	"Block Count Register (BLK_COUNT)—Offset 6h" on page 1774	0000h
8–Bh	4	"Argument 1 Register (ARGUMENT)—Offset 8h" on page 1775	00000000h
C–Dh	2	"Transfer Mode Register (TX_MODE)—Offset Ch" on page 1775	0000h
E–Fh	2	"Command Register (CMD)—Offset Eh" on page 1777	0000h
10–13h	4	"Response Register 0 (RESPONSE0)—Offset 10h" on page 1778	00000000h
14–17h	4	"Response Register 2 (RESPONSE2)—Offset 14h" on page 1779	00000000h
18–1Bh	4	"Response Register 4 (RESPONSE4)—Offset 18h" on page 1779	00000000h
1C–1Fh	4	"Response Register 6 (RESPONSE6)—Offset 1Ch" on page 1780	00000000h
20–23h	4	"Buffer Data Port Register (BUF_DATA_PORT)—Offset 20h" on page 1780	00000000h
24–27h	4	"Present State Register (PRE_STATE)—Offset 24h" on page 1781	1FFF0000h
28–28h	1	"Host Control 1 Register (HOST_CTL)—Offset 28h" on page 1784	00h
29–29h	1	"Power Control Register (PWR_CTL)—Offset 29h" on page 1785	00h
2A–2Ah	1	"Block Gap Control Register (_BLK_GAP_CTL)—Offset 2Ah" on page 1786	00h
2B–2Bh	1	"Wakeup Control Register (WAKEUP_CTL)—Offset 2Bh" on page 1787	00h
2C–2Dh	2	"Clock Control Register (CLK_CTL)—Offset 2Ch" on page 1788	0000h
2E–2Eh	1	"Timeout Control Register (TIMEOUT_CTL)—Offset 2Eh" on page 1790	00h
2F–2Fh	1	"Software Reset Register (SW_RST)—Offset 2Fh" on page 1791	00h
30–31h	2	"Normal Interrupt Status Register (NML_INT_STATUS)—Offset 30h" on page 1792	0000h
32–33h	2	"Error Interrupt Status Register (ERR_INT_STATUS)—Offset 32h" on page 1795	0000h
34–35h	2	"Normal Interrupt Status Enable (NRM_INT_STATUS_EN)—Offset 34h" on page 1797	0000h
36–37h	2	"Error Interrupt Status Enable Register (ERR_INT_STAT_EN)—Offset 36h" on page 1799	0000h
38–39h	2	"Normal Interrupt Signal Enable Register (NRM_INT_SIG_EN)—Offset 38h" on page 1800	0000h
3A–3Bh	2	"Error Interrupt Signal Enable Register (ERR_INT_SIG_EN)—Offset 3Ah" on page 1801	0000h
3C–3Fh	4	"Auto CMD12 Error Status Register and Host Control 2 Register (CMD12_ERR_STAT_HOST_CTRL_2)—Offset 3Ch" on page 1803	00000000h
40–43h	4	"Capabilities Register (CAPABILITIES)—Offset 40h" on page 1804	00000000h
44–47h	4	"Capabilities Register 2 (CAPABILITIES_2)—Offset 44h" on page 1805	00000000h
48–4Bh	4	"Maximum Current Capabilities Register (MAX_CUR_CAP)—Offset 48h" on page 1805	00000000h
50–51h	2	"Force Event Register for Auto CMD12 Error Status (FORCE_EVENT_CMD12_ERR_STAT)—Offset 50h" on page 1806	0000h

Table 185. Summary of SDIO for Wifi Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
52–53h	2	"Force Event Register for Error Interrupt Status (FORCE_EVENT_ERR_INT_STAT)—Offset 52h" on page 1807	0000h
54–54h	1	"ADMA Error Status Register (ADMA_ERR_STAT)—Offset 54h" on page 1808	00h
58–5Bh	4	"ADMA System Address Register (ADMA_SYS_ADDR)—Offset 58h" on page 1809	00000000h
70–73h	4	"Boot Timeout Control (BOOT_TIMEOUT_CTRL)—Offset 70h" on page 1810	00000000h
74–74h	1	"Debug Selection Register (DEBUG_SEL)—Offset 74h" on page 1811	00h
E0–E3h	4	"Shared Bus Control Register (SHARED_BUS)—Offset E0h" on page 1811	00000000h
F0–F0h	1	"SPI Interrupt Support Register (SPI_INT_SUP)—Offset F0h" on page 1813	00h
FC–FDh	2	"Slot Interrupt Status Register (SLOT_INT_STAT)—Offset FCh" on page 1813	0000h
FE–FFh	2	"Host Controller Version Register (HOST_CTRL_VER)—Offset FEh" on page 1814	B502h

16.6.1 SDMA System Address / Argument 2 Register (SYS_ADR)—Offset 0h

This register contains the physical system memory address used for DMA transfers or the second argument for the Auto CMD23.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h

Diagram illustrating the structure of the `sys_adr` field, which is 32 bits wide. The field is divided into eight 4-bit segments, each labeled with its starting bit position (31, 28, 24, 20, 16, 12, 8, 4). Each segment contains four bits, represented by circles. The label `sys_adr` is positioned vertically below the 16-bit mark.



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	SDMA System Address (sys_adr): (1) SDMA System Address This register contains the system memory address for a SDMA transfer. When the Host Controller stops a SDMA transfer, this register shall point to the system address of the next contiguous data position. It can be accessed only if no transaction is executing (i.e., after a transaction has stopped). Read operations during transfers may return an invalid value. The Host Driver shall initialize this register before starting a SDMA transaction. After SDMA has stopped, the next system address of the next contiguous data position can be read from this register. The SDMA transfer waits at each boundary specified by the Host SDMA Buffer Boundary in the Block Size register. The Host Controller generates a DMA Interrupt to request the Host Driver to update this register. The Host Driver sets the next system address of the next data position to this register. When the uppermost byte of this register (003h) is written, the Host Controller restarts the SDMA transfer. When restarting SDMA by the Resume command or by setting Continue Request in the Block Gap Control register, the Host Controller shall start at the next contiguous address stored here in the SDMA System Address register. ADMA does not use this register. (2) Argument 2 This register is used with the Auto CMD23 to set a 32-bit block count value to the argument of the CMD23 while executing Auto CMD23. If Auto CMD23 is used with ADMA, the full 32-bit block count value can be used. If Auto CMD23 is used without ADMA, the available block count value is limited by the Block Count register. 65535 blocks is the maximum value in this case.

16.6.2 Block Size Register (BLK_SIZE)—Offset 4h

This register is used to configure the number of bytes in a data block.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
tx_blk_size_12	boundary	tr_blk_size		

Bit Range	Default & Access	Field Name (ID): Description
15	0b RW	TX_BLK_SIZE_12 (tx_blk_size_12): Transfer Block Size 12th bit. This bit is added to support 4Kb Data block transfer.



Bit Range	Default & Access	Field Name (ID): Description
15:0	0000h RW	Blocks Count For Current Transfer (blk_count): This register is enabled when Block Count Enable in the Transfer Mode register is set to 1, and is valid only for multiple block transfers. The Host Driver shall set this register to a value between 1 and the maximum block count. The HC decrements the block count after each block transfer, and stops when the count reaches zero. Setting the block count to 0 results in no data blocks being transferred. This register should be accessed only when no transaction is executing (i.e., after transactions are stopped). During data transfer, read operations on this register may return an invalid value and write operations are ignored. When saving transfer context as a result of a Suspend command, the number of blocks yet to be transferred can be determined by reading this register. When restoring transfer context prior to issuing a Resume command, the HD shall restore the previously saved block count. 0000h = Stop Count 0001h = 1 block 0002h = 2 blocks ... - FFFFh = 65535 blocks

16.6.4 Argument 1 Register (ARGUMENT)—Offset 8h

This register contains the SD Command Argument.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

argument

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Command Argument 1 (argument): The SD Command Argument is specified as bit39-8 of Command-Format in the Physical Layer Specification.

16.6.5 Transfer Mode Register (TX_MODE)—Offset Ch

This register is used to control the operation of data transfers. The Host Driver shall set this register before issuing a command which transfers data (Refer to Data Present Select in the Command register), or before issuing a Resume command. The Host Driver shall save the value of this register when the data transfer is suspended (as a result of a Suspend command) and restore it before issuing a Resume command. To prevent data loss, the Host Controller shall implement write protection for this register during data transactions. Writes to this register shall be ignored when the Command Inhibit (DAT) in the Present State register is 1.

Access Method



Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd		boot_en	spi_mode	cmd_comp_ata
		blk_sel	data_tr_dir	auto_cmd_en
			blk_count_en	dma_en

Bit Range	Default & Access	Field Name (ID): Description
15:9	00h RO	Reserved (rsvd): Reserved.
8	0b RW	BOOT_EN (boot_en): To start boot operation for MMC4.3 1 - To start boot mode 0 - Stop the boot read
7	0b RW	SPI_MODE (spi_mode): SPI mode enable bit. 1 - SPI mode 0 - SD mode
6	0b RW	CMD_COMP_ATA (cmd_comp_ata): Command Completion Signal Enable for CE-ATA Device. ???1??? - Device will send command completion Signal ???0??? - Device will not send command completion Signal
5	0b RW	BLK_SEL (blk_sel): Multi / Single Block Select This bit is set when issuing multiple-block transfer commands using DAT line. For any other commands, this bit shall be set to 0. If this bit is 0, it is not necessary to set the Block Count register. (Refer to Table 2-8) 1 Multiple Block 0 Single Block
4	0b RW	Data Transfer Direction Select (data_tr_dir): This bit defines the direction of DAT line data transfers. The bit is set to 1 by the Host Driver to transfer data from the SD card to the SD Host Controller, and it is set to 0 for all other commands. 1 = Read (Card to Host) 0 = Write (Host to Card)
3:2	0b RW	AUTO_CMD_EN (auto_cmd_en): This field determines use of auto command functions 00b - Auto Command Disabled 01b - Auto CMD12 Enable 10b - Auto CMD23 Enable 11b - Reserved
1	0b RW	Block Count Enable (blk_count_en): This bit is used to enable the Block Count register, which is only relevant for multiple block transfers. When this bit is 0, the Block Count register is disabled, which is useful in executing an infinite transfer. (Refer to Table 2-8). If ADMA2 data transfer is more than 65535 blocks, this bit shall be set to 0. In this case, data transfer length is designated by Descriptor Table. 1 = Enable 0 = Disable
0	0b RW	DMA Enable (dma_en): This bit enables DMA functionality as described in section 1.4. DMA can be enabled only if it is supported as indicated in the Capabilities register. One of the DMA modes can be selected by DMA Select in the Host Control register. If DMA is not supported, this bit is meaningless and shall always read 0. If this bit is set to 1, a DMA operation shall begin when the Host Driver writes to the upper byte of Command register (00Fh). 1 = DMA Data transfer 0 = No data transfer or Non DMA data transfer



16.6.6 Command Register (CMD)—Offset Eh

The Host Driver shall check the Command Inhibit (DAT) bit and Command Inhibit (CMD) bit in the Present State register before writing to this register. Writing to the upper byte of this register triggers SD command generation. The Host Driver has the responsibility to write this register because the Host Controller does not protect for writing when Command Inhibit (CMD) is set.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + Eh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd	cmd_index	cmd_type	data_pr_sel	cmd_index_chk_en
			cmd_crc_chk_en	reserved
				resp_type_sel

Bit Range	Default & Access	Field Name (ID): Description
15:14	0h RO	Rsvd (rsvd): Reserved.
13:8	0h RW	Command Index (cmd_index): These bits shall be set to the command number (CMD0-63, ACMD0-63) that is specified in bits 45-40 of the Command-Format in the Physical Layer Specification and SDIO Card Specification.
7:6	00b RW	Command Type (cmd_type): There are three types of special commands: Suspend, Resume and Abort. These bits shall be set to 00b for all other commands. (1) Suspend Command If the Suspend command succeeds, the Host Controller shall assume the SD Bus has been released and that it is possible to issue the next command, which uses the DAT line. The Host Controller shall de-assert Read Wait for read transactions and stop checking busy for write transactions. The interrupt cycle shall start, in 4-bit mode. If the Suspend command fails, the Host Controller shall maintain its current state, and the Host Driver shall restart the transfer by setting Continue Request in the Block Gap Control register. (Refer to 3.12.1 Suspend Sequence). (2) Resume Command The Host Driver re-starts the data transfer by restoring the registers in the range of 000-00Dh. (Refer to Figure 1-4 in section 1.6 for the register map.) The Host Controller shall check for busy before starting write transfers. (3) Abort Command If this command is set when executing a read transfer, the Host Controller shall stop reads to the buffer. If this command is set when executing a write transfer, the Host Controller shall stop driving the DAT line. After issuing the Abort command, the Host Driver should issue a software reset. (Refer to 3.8 Abort Transaction). 11b = Abort -- CMD12, CMD52 for writing 'I/O Abort' in CCCR 10b = Resume -- CMD52 for writing 'Function Select' in CCCR 01b = Suspend -- CMD52 for writing 'Bus Suspend' in CCCR 00b = Normal -- Other commands
5	0b RW	Data Present Select (data_pr_sel): This bit is set to 1 to indicate that data is present and shall be transferred using the DAT line. It is set to 0 for the following: (1) Commands using only CMD line (ex. CMD52). (2) Commands with no data transfer but using busy signal on DAT[0] line (R1b or R5b ex. CMD38). (3) Resume command. 1 = Data Present 0 = No Data Present



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	Command Index Check Enable (cmd_index_chk_en): If this bit is set to 1, the Host Controller shall check the Index field in the response to see if it has the same value as the command index. If it is not, it is reported as a Command Index Error. If this bit is set to 0, the Index field is not checked. 1 = Enable 0 = Disable
3	0b RW	Command CRC Check Enable (cmd_crc_chk_en): If this bit is set to 1, the Host Controller shall check the CRC field in the response. If an error is detected, it is reported as a Command CRC Error. If this bit is set to 0, the CRC field is not checked. The position of CRC field is determined according to the length of the response. (Refer to definition in D01-00 and Table 2-10 below.) 1 = Enable 0 = Disable
2	0b RO	Reserved (reserved): Reserved.
1:0	0h RW	Response Type Select (resp_type_sel): 00 = No Response 01 = Response Length 136 10 = Response Length 48 11 = Response Length 48 check Busy after response

16.6.7 Response Register 0 (RESPONSE0)—Offset 10h

This register is used to store responses from SD cards.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 10h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

cmd_resp

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RO	Command Response (cmd_resp): The Table 2-12 describes the mapping of command responses from the SD Bus to this register for each response type. In the table, R[] refers to a bit range within the response data as transmitted on the SD Bus, REP[] refers to a bit range within the Response register



16.6.10 Response Register 6 (RESPONSE6)—Offset 1Ch

This register is used to store responses from SD cards.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

cmd_resp

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RO	Command Response (cmd_resp): The Table 2-12 describes the mapping of command responses from the SD Bus to this register for each response type. In the table, R[] refers to a bit range within the response data as transmitted on the SD Bus, REP[] refers to a bit range within the Response register

16.6.11 Buffer Data Port Register (BUF_DATA_PORT)—Offset 20h

32-bit data port register to access internal buffer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 20h

BAR Type: PCI Configuration Register (Size: 32 bits)


BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

buf_data

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Buffer Data (buf_data): The Host Controller buffer can be accessed through this 32-bit Data Port register. Refer to section 1.7.



Bit Range	Default & Access	Field Name (ID): Description
16	1b RO	Card Inserted (crd_ins): This bit indicates whether a card has been inserted. The Host Controller shall debounce this signal so that the Host Driver will not need to wait for it to stabilize. Changing from 0 to 1 generates a Card Insertion interrupt in the Normal Interrupt Status register and changing from 1 to 0 generates a Card Removal interrupt in the Normal Interrupt Status register. The Software Reset For All in the Software Reset register shall not affect this bit. If a card is removed while its power is on and its clock is oscillating, the Host Controller shall clear SD Bus Power in the Power Control register (Refer to Section 2.2.11) and SD Clock Enable in the Clock Control register (Refer to Section 2.2.14). When this bit is changed from 1 to 0, the Host Controller shall immediately stop driving CMD and DAT[3:0] (tri-state). In addition, the Host Driver should clear the Host Controller by the Software Reset For All in Software Reset register. The card detect is active regardless of the SD Bus Power. 1 = Card Inserted 0 = Reset or Debouncing or No Card
15:12	0h RO	Reserved1 (reserved1): Reserved.
11	0b RO	Buffer Read Enable (buf_rd_en): This status is used for non-DMA read transfers. The Host Controller may implement multiple buffers to transfer data efficiently. This read only flag indicates that valid data exists in the host side buffer. If this bit is 1, readable data exists in the buffer. A change of this bit from 1 to 0 occurs when all the block data is read from the buffer. A change of this bit from 0 to 1 occurs when block data is ready in the buffer and generates the Buffer Read Ready interrupt. 1 = Read enable 0 = Read disable
10	0b RO	Buffer Write Enable (buf_wr_en): This status is used for non-DMA write transfers. The Host Controller can implement multiple buffers to transfer data efficiently. This read only flag indicates if space is available for write data. If this bit is 1, data can be written to the buffer. A change of this bit from 1 to 0 occurs when all the block data is written to the buffer. A change of this bit from 0 to 1 occurs when top of block data can be written to the buffer and generates the Buffer Write Ready interrupt. The Host Controller should neither set Buffer Write Enable nor generate Buffer Write Ready Interrupt after the last block data is written to the Buffer Data Port Register. 1 = Write enable 0 = Write disable
9	0b RO	Read Transfer Active (rd_tx_active): This status is used for detecting completion of a read transfer. Refer to Section 3.12.3 for sequence details. This bit is set to 1 for either of the following conditions: - After the end bit of the read command. - When read operation is restarted by writing a 1 to Continue Request in the Block Gap Control register. This bit is cleared to 0 for either of the following conditions: - When the last data block as specified by block length is transferred to the System. - In case of ADMA2, end of read operation is designated by Descriptor Table. - When all valid data blocks in the Host Controller have been transferred to the System and no current block transfers are being sent as a result of the Stop At Block Gap Request being set to 1. A Transfer Complete interrupt is generated when this bit changes to 0. 1 = Transferring data 0 = No valid data



Bit Range	Default & Access	Field Name (ID): Description
8	0b RO	Write Transfer Active (wr_tx_active): This status indicates a write transfer is active. If this bit is 0, it means no valid write data exists in the Host Controller. Refer to Section 3.12.4 for more details on the sequence of events. This bit is set in either of the following cases: - After the end bit of the write command. - When write operation is restarted by writing a 1 to Continue Request in the Block Gap Control register. This bit is cleared in either of the following cases: - After getting the CRC status of the last data block as specified by the transfer count (Single and Multiple) In case of ADMA2, transfer count is designated by Descriptor Table. - After getting the CRC status of any block where data transmission is about to be stopped by a Stop At Block Gap Request. During a write transaction, a Block Gap Event interrupt is generated when this bit is changed to 0, as the result of the Stop At Block Gap Request being set. This status is useful for the Host Driver in determining non DAT line commands can be issued during write busy. 1 Transferring data 0 No valid data
7:3	00h RO	Reserved (reserved): Reserved.
2	0b RO	DAT Line Active (dat_ln_active): This bit indicates whether one of the DAT lines on SD Bus is in use. (a) In the case of read transactions This status indicates whether a read transfer is executing on the SD Bus. Changing this value from 1 to 0 generates a Block Gap Event interrupt in the Normal Interrupt Status register, as the result of the Stop At Block Gap Request being set. Refer to Section 3.12.3 for details on timing. This bit shall be set in either of the following cases: - After the end bit of the read command. - When writing a 1 to Continue Request in the Block Gap Control register to restart a read transfer. This bit shall be cleared in either of the following cases: - When the end bit of the last data block is sent from the SD Bus to the Host Controller. In case of ADMA2, the last block is designated by the last transfer of Descriptor Table. - When a read transfer is stopped at the block gap initiated by a Stop At Block Gap Request. The Host Controller shall stop read operation at the start of the interrupt cycle of the next block gap by driving Read Wait or stopping SD clock. If the Read Wait signal is already driven (due to data buffer cannot receive data), the Host Controller can continue to stop read operation by driving the Read Wait signal. It is necessary to support Read Wait in order to use suspend / resume function. (b) In the case of write transactions This status indicates that a write transfer is executing on the SD Bus. Changing this value from 1 to 0 generate a Transfer Complete interrupt in the Normal Interrupt Status register. Refer to Section 3.12.4 for sequence details. This bit shall be set in either of the following cases: - After the end bit of the write command. - When writing to 1 to Continue Request in the Block Gap Control register to continue a write transfer. This bit shall be cleared in either of the following cases: - When the SD card releases write busy of the last data block. If SD card does not drive busy signal for 8 SD Clocks, the Host Controller shall consider the card drive 'Not Busy'. In case of ADMA2, the last block is designated by the last transfer of Descriptor Table. - When the SD card releases write busy prior to waiting for write transfer as a result of a Stop At Block Gap Request. (c) Command with busy This status indicates whether a command indicates busy (ex. erase command for memory) is executing on the SD Bus. This bit is set after the end bit of the command with busy and cleared when busy is de-asserted. Changing this bit from 1 to 0 generate a Transfer Complete interrupt in the Normal Interrupt Status register. Refer Figure 2-11 to Figure 2-13. 1 = DAT Line Active 0 = DAT Line Inactive



Bit Range	Default & Access	Field Name (ID): Description
1	0b RO	Command Inhibit (DAT) (cmd_inhibit_dat): This status bit is generated if either the DAT Line Active or the Read Transfer Active is set to 1. If this bit is 0, it indicates the Host Controller can issue the next SD Command. Commands with busy signal belong to Command Inhibit (DAT) (ex. R1b, R5b type). Changing from 1 to 0 generates a Transfer Complete interrupt in the Normal Interrupt Status register. Note: The SD Host Driver can save registers in the range of 000-00Dh for a suspend transaction after this bit has changed from 1 to 0. 1 Cannot issue command which uses the DAT line 0 Can issue command which uses the DAT line
0	0b RO	Command Inhibit (CMD) (cmd_inhibit_cmd): Command Inhibit (CMD) If this bit is 0, it indicates the CMD line is not in use and the Host Controller can issue a SD Command using the CMD line. cleared when the command response is received. Auto CMD12 and Auto CMD23 consist of two responses. In this case, this bit is not cleared by the response of CMD12 or CMD23 but cleared by the response of a read/write command. Status issuing Auto CMD12 is not read from this bit. So if a command is issued during Auto CMD12 operation, Host Controller shall manage to issue two commands: CMD12 and a command set by Command register. Even if the Command Inhibit (DAT) is set to 1, commands using only the CMD line can be issued if this bit is 0. Changing from 1 to 0 generates a Command Complete Interrupt in the Normal Interrupt Status register. If the Host Controller cannot issue the command because of a command conflict error (Refer to Command CRC Error in Section 2.2.18) or because of Command Not Issued By Auto CMD12 Error (Refer to Section 2.2.23), this bit shall remain 1 and the Command Complete is not set. 1 Cannot issue command 0 Can issue command using only CMD line

16.6.13 Host Control 1 Register (HOST_CTL)—Offset 28h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
crd_det_sig_sel	crd_det_tst_lvl	sd8_bit_mode	dma_sel	hi_spd_en	data_tx_wid	led_ctl	

Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	Card Detect Signal Selection (crd_det_sig_sel): This bit selects source for the card detection. 1 = The Card Detect Test Level is selected (for test purposes) 0 = SDCD# is selected (for normal use) When the source for the card detection is switched, the interrupt should be disabled during the switching period by clearing the Interrupt Status/Signal Enable register in order to mask unexpected interrupt being caused by the glitch. The Interrupt Status/Signal Enable should be disabled during the period of debouncing.



Bit Range	Default & Access	Field Name (ID): Description
6	0b RW	Card Detect Test Level (crd_det_tst_lvl): This bit is enabled while the Card Detect Signal Selection is set to 1, and it indicates whether or not the card is inserted. 1 = Card Inserted 0 = No Card
5	0b RW	SD8 Bit Mode (sd8_bit_mode): This bit selects the data width of the HC. The HD shall select it to match the data width of the SD card.
4:3	00b RW	DMA Select (dma_sel): One of supported DMA modes can be selected. The host driver shall check support of DMA modes by referring the Capabilities register. Use of selected DMA is determined by DMA Enable of the Transfer Mode register. 00 = SDMA is selected 01 = Reserved (New assignment is not allowed) 10 = 32-bit Address ADMA2 is selected 11 = Reserved (will be modified by Version 4.00)
2	0b RW	High Speed Enable (hi_spd_en): This bit is optional. Before setting this bit, the Host Driver shall check the High Speed Support in the Capabilities register. If this bit is set to 0 (default), the Host Controller outputs CMD line and DAT lines at the falling edge of the SD Clock (up to 25MHz). If this bit is set to 1, the Host Controller outputs CMD line and DAT lines at the rising edge of the SD Clock (up to 50MHz). If Preset Value Enable in the Host Control 2 register is set to 1, Host Driver needs to reset SD Clock Enable before changing this field to avoid generating clock glitches. After setting this field, the Host Driver sets SD Clock Enable again. 1 = 4-bit mode 0 = 1-bit mode
1	0b RW	Data Transfer Width (data_tx_wid): Reserved.
0	0b RW	LED Control (led_ctl): This bit selects the data width of the Host Controller. The Host Driver shall set it to match the data width of the SD card. 1 = 4-bit mode 0 = 1-bit mode

16.6.14 Power Control Register (PWR_CTL)—Offset 29h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 29h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd	hw_rst	sd_bus_volt_sel
		sd_bus_pwr

Bit Range	Default & Access	Field Name (ID): Description
7:5	0h RO	Rsvd (rsvd): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	HW Reset (hw_rst): Reserved.
3:1	0h RW	SD Bus Voltage Select (sd_bus_volt_sel): By setting these bits, the Host Driver selects the voltage level for the SD card. Before setting this register, the Host Driver shall check the Voltage Support bits in the Capabilities register. If an unsupported voltage is selected, the Host System shall not supply SD Bus voltage. 111b = 3.3V (Typ.) 110b = 3.0V (Typ.) 101b = 1.8V (Typ.) 100b 000b Reserved
0	0b RW	SD Bus Power (sd_bus_pwr): Before setting this bit, the SD Host Driver shall set SD Bus Voltage Select. If the Host Controller detects the No Card state, this bit shall be cleared. If this bit is cleared, the Host Controller shall immediately stop driving CMD and DAT[3:0] (tri-state) and drive SDCLK to low level (Refer to Section 2.2.14) For SD Controller, this bit controls the bus voltage to SDMMC3. For SDIO Controller, power to SDIO device on SDMMC2 is not controlled by this bit. GPIO register and pin can be used to controller the SDIO device power. For eMMC Controller, power to eMMC device on SDMMC1 is not controlled by this bit. GPIO register and pin or alternative solutions can be used. 1 = Power on 0 = Power off

16.6.15 Block Gap Control Register (_BLK_GAP_CTL)—Offset 2Ah

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Ah

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd	drive_ccsd	int_blk_gap
		rd_wait_ctl
		cont_req
		stp_blk_gap_req

Bit Range	Default & Access	Field Name (ID): Description
7:5	0h RO	Reserved (rsvd): Reserved.
4	0b RW	DRIVE_CCSD (drive_ccsd): If the driver set this bit (change from ???0??? to ???1???), Host controller will send command completion.

Bit Range	Default & Access	Field Name (ID): Description
3	0b RW	Interrupt at Block Gap (int_blk_gap): This bit is valid only in 4-bit mode of the SDIO card and selects a sample point in the interrupt cycle. Setting to 1 enables interrupt detection at the block gap for a multiple block transfer. Setting to 0 disables interrupt detection during a multiple block transfer. If the SD card cannot signal an interrupt during a multiple block transfer, this bit should be set to 0. When the Host Driver detects an SD card insertion, it shall set this bit according to the CCCR of the SDIO card. 1 = Enabled 0 = Disabled
2	0b RW	Read Wait Control (rd_wait_ctl): The read wait function is optional for SDIO cards. If the card supports read wait, set this bit to enable use of the read wait protocol to stop read data using the DAT[2] line. Otherwise, the Host Controller has to stop the SD Clock to hold read data, which restricts commands generation. When the Host Driver detects an SD card insertion, it shall set this bit according to the CCCR of the SDIO card. If the card does not support read wait, this bit shall never be set to 1, otherwise DAT line conflict may occur. If this bit is set to 0, Suspend/Resume cannot be supported. 1 = Enable Read Wait Control 0 = Disable Read Wait Control
1	0b RW	Continue Request (cont_req): This bit is used to restart a transaction, which was stopped using the Stop At Block Gap Request. To cancel stop at the block gap, set Stop At Block Gap Request to 0 and set this bit 1 to restart the transfer. The Host Controller automatically clears this bit in either of the following cases: - In the case of a read transaction, the DAT Line Active changes from 0 to 1 as a read transaction restarts. - In the case of a write transaction, the Write Transfer Active changes from 0 to 1 as the write transaction restarts. Therefore, it is not necessary for Host Driver to set this bit to 0. If Stop At Block Gap Request is set to 1, any write to this bit is ignored. 1 = Restart 0 = Not affect
0	0b RW	Stop at Block Gap Request (stp_blk_gap_req): This bit is used to stop executing read and write transaction at the next block gap for non-DMA, SDMA and ADMA transfers. The Host Driver shall leave this bit set Copyright 2002-2011 SD Association SD Host Controller Simplified Specification Version 3.00 44 to 1 until the Transfer Complete is set to 1. Clearing both Stop At Block Gap Request and Continue Request shall not cause the transaction to restart. When Host Controller version is 1.00, the Host Driver can set this bit if the card supports Read Wait Control. When Host Controller version is 2.00 or later, the Host Driver can set this bit regardless of the card supports Read Wait Control. The Host Controller shall stop read transfer by using Read Wait or stopping SD clock. In case of write transfers in which the Host Driver writes data to the Buffer Data Port register, the Host Driver shall set this bit after all block data is written. If this bit is set to 1, the Host Driver shall not write data to Buffer Data Port register. This bit affects Read Transfer Active, Write Transfer Active, DAT Line Active and Command Inhibit (DAT) in the Present State register. Regarding detailed control of bits D01 and D00, refer to Section 3.8 and 3.12. 1 = Stop 0 = Transfer

16.6.16 Wakeup Control Register (WAKEUP_CTL)—Offset 2Bh

This register is mandatory for the Host Controller, but wakeup functionality depends on the Host Controller system hardware and software. The Host Driver shall maintain voltage on the SD Bus, by setting SD Bus Power to 1 in the Power Control register, when wakeup event via Card Interrupt is desired. Wakeup Event is not supported by Host Controller. Sideband wake via GPIO pin and register shall be used instead. During RTD3, GPIO register is readable and GPIO signal is routed to APIC.

Access Method



Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Bh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd		wakeup_en_sd_rm
		wakeup_en_sd_ins
		wakeup_en_crd_int

Bit Range	Default & Access	Field Name (ID): Description
7:3	0h RO	Reserved (rsvd): Reserved.
2	0b RW	Wakeup Event Enable On SD Card Removal (wakeup_en_sd_rm): This bit enables wakeup event via Card Removal assertion in the Normal Interrupt Status register. FN_WUS (Wake Up Support) in CIS does not affect this bit. 1 = Enable 0 = Disable
1	0b RW	Wakeup Event Enable On SD Card Insertion (wakeup_en_sd_ins): This bit enables wakeup event via Card Insertion assertion in the Normal Interrupt Status register. FN_WUS (Wake Up Support) in CIS does not affect this bit. 1 = Enable 0 = Disable
0	0b RW	Wakeup Event Enable On Card Interrupt (wakeup_en_crd_int): This bit enables wakeup event via Card Interrupt assertion in the Normal Interrupt Status register. This bit can be set to 1 if FN_WUS (Wake Up Support) in CIS is set to 1. 1 = Enable 0 = Disable

16.6.17 Clock Control Register (CLK_CTL)—Offset 2Ch

At the initialization of the Host Controller, the Host Driver shall set the SDCLK Frequency Select according to the Capabilities register.

Access Method


Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
sdclk_freq_sel				upper_sdclk_freq_sel
				rsvd
				sd_clk_en
				int_clk_stable
				int_clk_en

Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RW	SDCLK Frequency Select (sdclk_freq_sel): This register is used to select the frequency of the SDCLK pin. The definition of this field is dependent on the Host Controller Version. (1) 8-bit Divided Clock Mode This mode is supported by the Host Controller Version 1.00 and 2.00. The frequency is not programmed directly, rather, this register holds the divisor of the Base Clock Frequency For SD Clock in the capabilities register. Only the following settings are allowed. (1) 8-bit Divided Clock Mode 80h = base clock divided by 256 40h = base clock divided by 128 20h = base clock divided by 64 10h = base clock divided by 32 08h = base clock divided by 16 04h = base clock divided by 8 02h = base clock divided by 4 01h = base clock divided by 2 00h = base clock(10MHz and up) Setting 00h specifies the highest frequency of the SD Clock. When setting multiple bits, the most significant bit is used as the divisor, but it should not be set. The three default divider values can be calculated by the frequency that is defined by the Base Clock Frequency For SD Clock in the Capabilities register. 400KHz divider value 25MHz divider value 50MHz divider value According to the Physical Layer Specification, the maximum SD Clock frequency is 25 MHz in normal speed mode and 50MHz in high speed mode, and shall never exceed this limit. The frequency of the SDCLK is set by the following formula: Clock Frequency = (Base Clock) / divisor Thus, choose the smallest possible divisor which results in a clock frequency that is less than or equal to the target frequency. For example, if the Base Clock Frequency For SD Clock in the Capabilities register has the value 33MHz, and the target frequency is 25MHz, then choosing the divisor value of 01h will yield 16.5MHz, which is the nearest frequency less than or equal to the target. Similarly, to approach a clock value of 400KHz, the divisor value of 40h yields the optimal clock value of 258KHz. (2) 10-bit Divided Clock Mode Host Controller Version 3.00 supports this mandatory mode instead of the 8-bit Divided Clock Mode. The length of divider is extended to 10 bits, and all divider values shall be supported. 3FFh = 1/2046 Divided Clock - N = 1/2N Divided Clock (Duty 50%) 002h = 1/4 Divided Clock 001h = 1/2 Divided Clock 000h = Base Clock (10MHz and up) 3FFh = Base Clock * M / 1024 - N - 1 = Base Clock * M / N 002h = Base Clock * M / 3 001h = Base Clock * M / 2 000h = Base Clock * M This field depends on setting of Preset Value Enable in the Host Control 2 register. If Preset Value Enable = 0, this field is set by Host Driver. If the Preset Value Enable = 1, this field is automatically set to a value specified in one of Preset Value registers.



Bit Range	Default & Access	Field Name (ID): Description
7:6	0h RO	Upper Bits of SDCLK Frequency Select (upper_sdclk_freq_sel): Host Controller Versions 1.00 and 2.00 do not support these bits and they are treated as 00b fixed value (ROC). Host Controller Version 3.00 shall support these bits to expand SDCLK Frequency Select to 10-bit. Bit 07-06 is assigned to bit 09-08 of clock divider in SDCLK Frequency Select.
5:3	0h RO	Rsvd (rsvd): Reserved.
2	0b RW	SD Clock Enable (sd_clk_en): The Host Controller shall stop SDCLK when writing this bit to 0. SDCLK Frequency Select can be changed when this bit is 0. Then, the Host Controller shall maintain the same clock frequency until SDCLK is stopped (Stop at SDCLK=0). If the Card Inserted in the Present State register is cleared, this bit shall be cleared. 1 = Enable 0 = Disable
1	0b RO	Internal Clock Stable (int_clk_stable): This bit is set to 1 when SD clock is stable after writing to Internal Clock Enable in this register to 1. The SD Host Driver shall wait to set SD Clock Enable until this bit is set to 1. Note: This is useful when using PLL for a clock oscillator that requires setup time. 1 = Ready 0 = Not Ready
0	0b RW	Internal Clock Enable (int_clk_en): This bit is set to 0 when the Host Driver is not using the Host Controller, or when the Host Controller awaits a wakeup event. The Host Controller should stop its internal clock to go to a very low power state. Still, registers shall be able to be read and written. Clock starts to oscillate when this bit is set to 1. When clock oscillation is stable, the Host Controller shall set Internal Clock Stable in this register to 1. This bit shall not affect card detection. 1 = Oscillate 0 = Stop

16.6.18 Timeout Control Register (TIMEOUT_CTL)—Offset 2Eh

At the initialization of the Host Controller, the Host Driver shall set the Data Timeout Counter Value according to the Capabilities register.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Eh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00h

7		4		0
0	0	0	0	0
reserved				data_timeout_cnt_val



Bit Range	Default & Access	Field Name (ID): Description
7:4	0h RO	Rsvd (reserved): Reserved.
3:0	0h RW	Data Timeout Counter Value (data_timeout_cnt_val): This value determines the interval by which DAT line timeouts are detected. For more information about timeout generation, refer to the Data Timeout Error in the Error Interrupt Status register. Timeout clock frequency will be generated by dividing the base clock TMCLK value by this value. When setting this register, prevent inadvertent timeout events by clearing the Data Timeout Error Status Enable (in the Error Interrupt Status Enable register). 1111b Reserved 1110b = $TMCLK \times 2^{27}$ 0001b = $TMCLK \times 2^{14}$ 0000b = $TMCLK \times 2^{13}$

16.6.19 Software Reset Register (SW_RST)—Offset 2Fh

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Fh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
rsvd				sw_rst_dat_in		sw_rst_cmd_in	sw_rst_all

Bit Range	Default & Access	Field Name (ID): Description
7:3	0h RO	Reserved (rsvd): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2	0b RW	Software Reset For DAT Line (sw_rst_dat_in): Only part of data circuit is reset. DMA circuit is also reset. The following registers and bits are cleared by this bit: Buffer Data Port register • Buffer is cleared and initialized. Present State register • Buffer Read Enable • Buffer Write Enable • Read Transfer Active • Write Transfer Active • DAT Line Active • Command Inhibit (DAT) Block Gap Control register • Continue Request • Stop At Block Gap Request Normal Interrupt Status register • Buffer Read Ready • Buffer Write Ready • DMA Interrupt • Block Gap Event • Transfer Complete • 1 = Reset • 0 = Work When Auto or Dynamic Clock Gating is enabled for this controller, the Software Reset bit may require several reads before the bit clears.
1	0b RW	Software Reset For CMD Line (sw_rst_cmd_in): Only part of command circuit is reset. The following registers and bits are cleared by this bit: Present State register • Command Inhibit (CMD) Normal Interrupt Status register • Command Complete • 1 = Reset • 0 = Work When Auto or Dynamic Clock Gating is enabled for this controller, the Software Reset bit may require several reads before the bit clears.
0	0b RW	Software Reset For All (sw_rst_all): This reset affects the entire Host Controller except for the card detection circuit. Register bits of type ROC, RW, RW1C, RWAC are cleared to 0. During its initialization, the Host Driver shall set this bit to 1 to reset the Host Controller. The Host Controller shall reset this bit to 0 when Capabilities registers are valid and the Host Driver can read them. Additional use of Software Reset For All may not affect the value of the Capabilities registers. If this bit is set to 1, the host driver should issue reset command and reinitialize the SD card. • 1 = Reset • 0 = Work When Auto or Dynamic Clock Gating is enabled for this controller, the Software Reset bit may require several reads before the bit clears.

16.6.20 Normal Interrupt Status Register (NML_INT_STATUS)—Offset 30h

The Normal Interrupt Status Enable affects reads of this register, but Normal Interrupt Signal Enable does not affect these reads. An interrupt is generated when the Normal Interrupt Signal Enable is enabled and at least one of the status bits is set to 1. Writing 1 to a bit of RW1C attribute clears it; writing 0 keeps the bit unchanged. Writing 1 to a bit of ROC attribute keeps the bit unchanged. More than one status can be cleared with a single register write. The Card Interrupt is cleared when the card stops asserting the interrupt; that is, when the Card Driver services the interrupt condition.

Access Method



Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 30h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
err_int	boot_ter_int	boot_ck_rcv	re_tune	int_c
				int_b
				int_a
				crd_int
				crd_rm
				crd_ins
				buf_rd_rdy
				buf_wr_rdy
				dma_int
				blk_gap_event
				tx_comp
				cmd_comp

Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Error Interrupt (err_int): If any of the bits in the Error Interrupt Status register are set, then this bit is set. Therefore the Host Driver can efficiently test for an error by checking this bit first. This bit is read only. 1 = Error 0 = No Error
14	0b RW/1C	BOOT_TER_INT (boot_ter_int): boot ter int
13	0b RW/1C	BOOT_ACK_RCV (boot_ck_rcv): boot ack rcv
12	0b RO	Re-Tuning Event (re_tune): This status is set if Re-Tuning Request in the Present State register changes from 0 to 1. Host Controller requests Host Driver to perform re-tuning for next data transfer. Current data transfer (not large block count) can be completed without re-tuning. 1 Re-Tuning should be performed 0 Re-Tuning is not required
11	0b RO	INT_C (int_c): This status is set if INT_C is enabled and INT_C# pin is in low level. Writing this bit to 1 does not clear this bit. It is cleared by resetting the INT_C interrupt factor. Refer to the Shared Bus Control register. 1 = INT_C is detected 0 = No interrupt is detected
10	0b RO	INT_B (int_b): This status is set if INT_B is enabled and INT_B# pin is in low level. Writing this bit to 1 does not clear this bit. It is cleared by resetting the INT_B interrupt factor. Refer to the Shared Bus Control register. 1 = INT_B is detected 0 = No interrupt is detected
9	0b RO	INT_A (int_a): This status is set if INT_A is enabled and INT_A# pin is in low level. Writing this bit to 1 does not clear this bit. It is cleared by resetting the INT_A interrupt factor. Refer to the Shared Bus Control register. 1 = INT_A is detected 0 = No interrupt is detected



Bit Range	Default & Access	Field Name (ID): Description
8	0b RO	Card Interrupt (crd_int): Writing this bit to 1 does not clear this bit. It is cleared by resetting the SD card interrupt factor. In 1-bit mode, the Host Controller shall detect the Card Interrupt without SD Clock to support wakeup. In 4-bit mode, the card interrupt signal is sampled during the interrupt cycle, so there are some sample delays between the interrupt signal from the SD card and the interrupt to the Host System. When this status has been set and the Host Driver needs to start this interrupt service, Card Interrupt Status Enable in the Normal Interrupt Status Enable register may be set to 0 in order to clear the card interrupt statuses latched in the Host Controller and to stop driving the interrupt signal to the Host System. After completion of the card interrupt service (It should reset interrupt factors in the SD card and the interrupt signal may not be asserted), set Card Interrupt Status Enable to 1 and start sampling the interrupt signal again. Interrupt detected by DAT[1] is supported when there is a card per slot. In case of shared bus, interrupt pins are used to detect interrupts. If 000b is set to Interrupt Pin Select in the Shared Bus Control register, this status is effective. Non-zero value is set to Interrupt Pin Select, INT_A, INT_B or INT_C is then used to device interrupts. 1 = Generate Card Interrupt 0 = No Card Interrupt
7	0b RW/1C	Card Removal (crd_rm): This status is set if the Card Inserted in the Present State register changes from 1 to 0. When the Host Driver writes this bit to 1 to clear this status, the status of the Card Inserted in the Present State register should be confirmed. Because the card detect state may possibly be changed when the Host Driver clear this bit and interrupt event may not be generated. 1 = Card removed 0 = Card state stable or Debouncing
6	0b RW/1C	Card Insertion (crd_ins): This status is set if the Card Inserted in the Present State register changes from 0 to 1. When the Host Driver writes this bit to 1 to clear this status, the status of the Card Inserted in the Present State register should be confirmed, because the card detect state may possibly be changed when the Host Driver clears this bit and interrupt event may not be generated. 1 Card inserted 0 Card state stable or Debouncing
5	0b RW/1C	Buffer Read Ready (buf_rd_rdy): This status is set if the Buffer Read Enable changes from 0 to 1. Refer to the Buffer Read Enable in the Present State register. While performing tuning procedure (Execute Tuning is set to 1), Buffer Read Ready is set to 1 for every CMD19 execution. 1 = Ready to read buffer 0 = Not ready to read buffer
4	0b RW/1C	Buffer Write Ready (buf_wr_rdy): This status is set if the Buffer Write Enable changes from 0 to 1. Refer to the Buffer Write Enable in the Present State register. 1 = Ready to write buffer 0 = Not ready to write buffer
3	0b RW/1C	DMA Interrupt (dma_int): This status is set if the Host Controller detects the Host SDMA Buffer boundary during transfer. Refer to the Host SDMA Buffer Boundary in the Block Size register. Other DMA interrupt factors may be added in the future. In case of ADMA, by setting Int field in the descriptor table, Host Controller generates this interrupt. Suppose that it is used for debugging. This interrupt shall not be generated after the Transfer Complete. 1 = DMA Interrupt is generated 0 = No DMA Interrupt
2	0b RW/1C	Block Gap Event (blk_gap_event): If the Stop At Block Gap Request in the Block Gap Control register is set, this bit is set when both a read / write transaction is stopped at a block gap. If Stop At Block Gap Request is not set to 1, this bit is not set to 1. (1) In the case of a Read Transaction This bit is set at the falling edge of the DAT Line Active Status, when the transaction is stopped at SD Bus timing. The Read Wait shall be supported in order to use this function. Refer to Section 3.12.3 for timing details. p1(1) In the case of a Write Transaction This bit is set at the falling edge of Write Transfer Active Status (after getting CRC status at SD Bus timing). Refer to Section 3.12.4 for more details on the sequence of events. 1 = Transaction stopped at block gap 0 = No Block Gap Event



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW/1C	Transfer Complete (tx_comp): This bit is set when a read / write transfer and a command with busy is completed. (1) In the case of a Read Transaction This bit is set at the falling edge of Read Transfer Active Status. This interrupt is generated in two cases. The first is when a data transfer is completed as specified by data length (After the last data has been read to the Host System). The second is when data has stopped at the block gap and completed the data transfer by setting the Stop At Block Gap Request in the Block Gap Control register (After valid data has been read to the Host System). Refer to Section 3.12.3 for more details on the sequence of events. (2) In the case of a Write Transaction This bit is set at the falling edge of the DAT Line Active Status. This interrupt is generated in two cases. The first is when the last data is written to the SD card as specified by data length and the busy signal released. The second is when data transfers are stopped at the block gap by setting Stop At Block Gap Request in the Block Gap Control register and data transfers completed. (After valid data is written to the SD card and the busy signal released). Refer to Section 3.12.4 for more details on the sequence of events. (3) In the case of a command with busy This bit is set when busy is de-asserted. Refer to DAT Line Active and Command Inhibit (DAT) in the Present State register. Refer to the spec for the relationship between Transfer Complete and Data Timeout Error. 1 = Command execution is completed 0 = Not complete While performing tuning procedure (Execute Tuning is set to 1), Transfer Complete is not set to 1.
0	0b RW/1C	Command Complete (cmd_comp): This bit is set when get the end bit of the command response. Auto CMD12 and Auto CMD23 consist of two responses. Command Complete is not generated by the response of CMD12 or CMD23 but generated by the response of a read/write command. Refer to Command Inhibit (CMD) in the Present State register for how to control this bit. Command Timeout Error has higher priority than Command Complete. If both bits are set to 1, it can be considered that the response was not received correctly. For a tabular description of the relationship between these two bits, refer to the description of Command Complete in the spec. 1 = Command complete 0 = No command complete

16.6.21 Error Interrupt Status Register (ERR_INT_STATUS)—Offset 32h

Signals defined in this register can be enabled by the Error Interrupt Status Enable register, but not by the Error Interrupt Signal Enable register. The interrupt is generated when the Error Interrupt Signal Enable is enabled and at least one of the statuses is set to 1. Writing to 1 clears the bit, and writing to 0 keeps the bit unchanged. More than one status can be cleared at the one register write.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)


Offset: [BAR] + 32h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0



Bit Range	Default & Access	Field Name (ID): Description
15	0b RW	Vendor Specific Error Status (vend_spec_err_status): Reserved.
14	0b RW	Boot Command Timeout Error (boot_cmd_timeout_err): Occur if the boot are access command is issued to the agent which has no permission to access the boot area.
13	0b RW	CEATA Error (ceata_err): Occurs when ATA command termination has occured due to an error condition the device has encountered.
12	0b RW	Target Response Error (tgt_rsp_err): Occurs when detecting ERROR in m_hresp(dma transaction).
11:10	0h RO	Reserved (rsvd): Reserved.
9	0b RW	ADMA Error (adma_err): This bit is set when the Host Controller detects errors during ADMA based data transfer. The state of the ADMA at an error occurrence is saved in the ADMA Error Status Register. In addition, the Host Controller generates this Interrupt when it detects invalid descriptor data (Valid=0) at the ST_FDS state. ADMA Error State in the ADMA Error Status indicates that an error occurs in ST_FDS state. The Host Driver may find that Valid bit is not set at the error descriptor. 0 = error 1 = no error
8	0b RW	Auto CMD12 Error (cmd12_err): Auto CMD12 and Auto CMD23 use this error status. This bit is set when detecting that one of the bits D00-D04 in Auto CMD Error Status register has changed from 0 to 1. In case of Auto CMD12, this bit is set to 1, not only when the errors in Auto CMD12 occur but also when Auto CMD12 is not executed due to the previous command error. 1 = error 0 = no error
7	0b RW	Current Limit Error (cur_limit_err): By setting the SD Bus Power bit in the Power Control register, the Host Controller is requested to supply power for the SD Bus. If the Host Controller supports the Current Limit function, it can be protected from an illegal card by stopping power supply to the card in which case this bit indicates a failure status. Reading 1 means the Host Controller is not supplying power to SD card due to some failure. Reading 0 means that the Host Controller is supplying power and no error has occurred. The Host Controller may require some sampling time to detect the current limit. If the Host Controller does not support this function, this bit shall always be set to 0. 1 = power fail 0 = no error
6	0b RW	Data End Bit Error (data_end_bit_err): Occurs either when detecting 0 at the end bit position of read data which uses the DAT line or at the end bit position of the CRC Status. 1 = error 0 = no error
5	0b RW	Data CRC Error (data_crc_err): Occurs when detecting CRC error when transferring read data which uses the DAT line or when detecting the Write CRC status having a value of other than 010b.
4	0b RW	Data Timeout Error (data_timeout_err): This bit is set when detecting one of following timeout conditions. - Busy timeout for R1b,R5b type - Busy timeout after Write CRC status - Write CRC Status timeout - Read Data timeout 1 = time out 0 = no error



Bit Range	Default & Access	Field Name (ID): Description
3	0b RW	Command Index Error (cmd_index_err): This bit is set if a Command Index error occurs in the command response. 1 = error 0 = no error
2	0b RW	Command End Bit Error (cmd_end_bit_err): This bit is set when detecting that the end bit of a command response is 0. 1 = End Bit Error generated 0 = no error
1	0b RW	Command CRC Error (cmd_crc_err): Command CRC Error is generated in two cases. If a response is returned and the Command Timeout Error is set to 0 (indicating no timeout), this bit is set to 1 when detecting a CRC error in the command response. The Host Controller detects a CMD line conflict by monitoring the CMD line when a command is issued. If the Host Controller drives the CMD line to 1 level, but detects 0 level on the CMD line at the next SD clock edge, then the Host Controller shall abort the command (Stop driving CMD line) and set this bit to 1. The Command Timeout Error shall also be set to 1 to distinguish CMD line conflict (refer to tabular data in the spec. that explains the relationship between Command CRC Error and Command Timeout Error). 1 = CRC Error Generated. 0 = no error
0	0b RW	Command Timeout Error (cmd_timeout_err): This bit is set only if no response is returned within 64 SD clock cycles from the end bit of the command. If the Host Controller detects a CMD line conflict (in which case Command CRC Error shall also be set, as shown in tabular data in the spec that explains the relationship between this bit and Command CRC Error) this bit shall be set without waiting for 64 SD clock cycles, because the command will be aborted by the Host Controller. 1 = time out 0 = no Error

16.6.22 Normal Interrupt Status Enable (NRM_INT_STATUS_EN)—Offset 34h

Setting to 1 enables Interrupt Status. **Implementation Note:** The Host Controller may sample the card interrupt signal during interrupt period, and may hold its value in the flip-flop. If the **Card Interrupt Status Enable** is set to 0, the Host Controller shall clear all internal signals regarding Card Interrupt.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
fixed_0	rsvd	boot_term_int_en	boot_ack_rcv_en	crd_int_stat_en
		crd_rm_stat_en	crd_ins_stat_en	buf_rd_rdy_stat_en
		buf_wr_rdy_stat_en	dma_int_stat_en	blk_gap_event_stat_en
			tx_comp_stat_en	cmd_comp_stat_en



Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Fixed to 0 (fixed_0): The Host Driver shall control error interrupts using the Error Interrupt Status Enable register.
14:11	0h RO	Reserved (rsvd): Reserved.
10	0b RW	Boot Term Interrupt Enable (boot_term_int_en): 0 = Masked.
9	0b RW	Boot Acknowledge Receive Enable (boot_ack_rcv_en): 0 = Masked
8	0b RW	Card Interrupt Status Enable (crd_int_stat_en): If this bit is set to 0, the Host Controller shall clear interrupt request to the System. The Card Interrupt detection is stopped when this bit is cleared, and restarted when this bit is set to 1. The Host Driver may clear the Card Interrupt Status Enable before servicing the Card Interrupt, and may set this bit again after all interrupt requests from the card are cleared, to prevent inadvertent interrupts. 1 = enabled 0 = masked
7	0b RW	Card Removal Status Enable (crd_rm_stat_en): 1 = enabled 0 = masked
6	0b RW	Card Insertion Status Enable (crd_ins_stat_en): [1 = enabled 0 = masked
5	0b RW	Buffer Read Ready Status Enable (buf_rd_rdy_stat_en): 1 = enabled 0 = masked
4	0b RW	Buffer Write Ready Status Enable (buf_wr_rdy_stat_en): 1 = enabled 0 = masked
3	0b RW	DMA Interrupt Status Enable (dma_int_stat_en): 1 = enabled 0 = masked
2	0b RW	Block Gap Event Status Enable (blk_gap_event_stat_en): 1 = enabled 0 = masked
1	0b RW	Transfer Complete Status Enable (tx_comp_stat_en): 1 = enabled 0 = masked
0	0b RW	Command Complete Status Enable (cmd_comp_stat_en): 1 = enabled 0 = masked



16.6.23 Error Interrupt Status Enable Register (ERR_INT_STAT_EN)—Offset 36h

Setting to 1 enables interrupt status. **Implementation Note:** To detect CMD line conflict, the Host Driver must set both **Command Timeout Error Status Enable** and **Command CRC Error Status Enable** to 1.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 36h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd0	ceata_err_en	tgt_rsp_err_en	rsvd	tune_err_stat_en
		adma_err_stat_en	cmd12_err_stat_en	cur_limit_err_stat_en
			data_end_bit_err_stat_en	data_crc_err_stat_en
			data_timeout_err_stat_en	cmd_ind_err_stat_en
				cmd_end_bit_err_stat_en
				cmd_crc_err_stat_en
				cmd_timeout_err_stat_en

Bit Range	Default & Access	Field Name (ID): Description
15:14	0b RO	Rsvd0 (rsvd0): Reserved.
13	0b RW	CEATA Error Enable (ceata_err_en): 0 = masked
12	0b RW	Target Response Error Enable (tgt_rsp_err_en): 0 = masked
11	0b RO	Rsvd (rsvd): Reserved.
10	0b RW	Tuning Error Status Enable (tune_err_stat_en): 1 = enabled 0 = masked
9	0b RW	ADMA Error Status Enable (adma_err_stat_en): 1 = enabled 0 = masked
8	0b RW	Auto CMD12 Error Status Enable (cmd12_err_stat_en): 1 = enabled 0 = masked
7	0b RW	Current Limit Error Status Enable (cur_limit_err_stat_en): 1 = enabled 0 = masked
6	0b RW	Data End Bit Error Status Enable (data_end_bit_err_stat_en): 1 = enabled 0 = masked



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	Data CRC Error Status Enable (data_crc_err_stat_en): 1 = enabled 0 = masked
4	0b RW	Data Timeout Error Status Enable (data_timeout_err_stat_en): 1 = enabled 0 = masked
3	0b RW	Command Index Error Status Enable (cmd_ind_err_stat_en): 1 = enabled 0 = masked
2	0b RW	Command End Bit Error Status Enable (cmd_end_bit_err_stat_en): 1 = enabled 0 = masked
1	0b RW	Command CRC Error Status Enable (cmd_crc_err_stat_en): 1 = enabled 0 = masked
0	0b RW	Command Timeout Error Status Enable (cmd_timeout_err_stat_en): 1 = enabled 0 = masked

16.6.24 Normal Interrupt Signal Enable Register (NRM_INT_SIG_EN)—Offset 38h

This register is used to select which interrupt status is indicated to the Host System as the interrupt. These status bits all share the same 1 bit interrupt line. Setting any of these bits to 1 enables interrupt generation.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
fixed_0	rsvd	boot_term_int_sig_en	boot_ack_rcv_sig_en	crd_int_sig_en
		crd_rm_sig_en	crd_ins_sig_en	buf_rd_rdy_sig_en
		buf_wr_rdy_sig_en	dma_int_sig_en	blk_gap_event_sig_en
			tx_comp_sig_en	cmd_comp_sig_en

Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Fixed to 0 (fixed_0): The Host Driver shall control error interrupts using the Error Interrupt Signal Enable register.
14:11	0h RO	Reserved (rsvd): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
10	0b RW	Boot Terminate Interrupt Signal Enable (boot_term_int_sig_en): 0 = masked
9	0b RW	Boot Acknowledge Receive Signal Enable (boot_ack_rcv_sig_en): 0 = masked
8	0b RW	Card Interrupt Signal Enable (crd_int_sig_en): 1 = enabled 0 = masked
7	0b RW	Card Removal Signal Enable (crd_rm_sig_en): 1 = enabled 0 = masked
6	0b RW	Card Insertion Signal Enable (crd_ins_sig_en): 1 = enabled 0 = masked
5	0b RW	Buffer Read Ready Signal Enable (buf_rd_rdy_sig_en): 1 = enabled 0 = masked
4	0b RW	Buffer Write Ready Signal Enable (buf_wr_rdy_sig_en): 1 = enabled 0 = masked
3	0b RW	DMA Interrupt Signal Enable (dma_int_sig_en): 1 = enabled 0 = masked
2	0b RW	Block Gap Event Signal Enable (blk_gap_event_sig_en): 1 = enabled 0 = masked
1	0b RW	Transfer Complete Signal Enable (tx_comp_sig_en): 1 = enabled 0 = masked
0	0b RW	Command Complete Signal Enable (cmd_comp_sig_en): 1 = enabled 0 = masked

16.6.25 Error Interrupt Signal Enable Register (ERR_INT_SIG_EN)—Offset 3Ah

This register is used to select which interrupt status is sent to the Host System as the interrupt. These status bits all share the same 1 bit interrupt line. Setting any of these bits to 1 enables interrupt generation.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 3Ah

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
rsvd0	ceata_err_sig_en	tgt_err_rsp_sig_en	rsvd	tune_err_sig
				adma_err_sig_en
				cmd12_err_sig_en
				cur_limit_err_sig_en
				data_end_bit_err_sig_en
				data_crc_err_sig_en
				data_timeout_err_stat_en
				cmd_ind_err_stat_en
				cmd_end_bit_err_stat_en
				cmd_crc_err_stat_en
				cmd_timeout_err_stat_en

Bit Range	Default & Access	Field Name (ID): Description
15:14	0b RO	Rsvd0 (rsvd0): Reserved.
13	0b RW	CEATA_Error Signal Enable (ceata_err_sig_en): 0 = masked
12	0b RW	Target Error Response Signal Enable (tgt_err_rsp_sig_en): 0 = masked
11	0b RO	Reserved (rsvd): Reserved.
10	0b RW	Tuning Error Signal Enable (tune_err_sig): 1 = enabled 0 = masked
9	0b RW	ADMA Error Signal Enable (adma_err_sig_en): 1 = enabled 0 = masked
8	0b RW	Auto CMD12 Error Signal Enable (cmd12_err_sig_en): 1 = enabled 0 = masked
7	0b RW	Current Limit Error Signal Enable (cur_limit_err_sig_en): 1 = enabled 0 = masked
6	0b RW	Data End Bit Error Signal Enable (data_end_bit_err_sig_en): 1 = enabled 0 = masked
5	0b RW	Data CRC Error Signal Enable (data_crc_err_sig_en): 1 = enabled 0 = masked
4	0b RW	Data Timeout Error Signal Enable (data_timeout_err_stat_en): 1 = enabled 0 = masked
3	0b RW	Command Index Error Signal Enable (cmd_ind_err_stat_en): 1 = enabled 0 = masked
2	0b RW	Command End Bit Error Signal Enable (cmd_end_bit_err_stat_en): 1 = enabled 0 = masked

16.6.26 Auto CMD12 Error Status Register and Host Control 2 Register (CMD12_ERR_STAT_HOST_CTRL_2)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	Preset Value (preset_value): Host Controller Version 3.00 supports this bit. As the operating SDCLK frequency and I/O driver strength depend on the Host System implementation, it is difficult to determine these parameters in the Standard Host Driver. When Preset Value Enable is set to automatic This bit enables the functions defined in the Preset Value registers. 1 = Automatic Selection by Preset Value are Enabled 0 SDCLK and Driver Strength are controlled by Host Driver If this bit is set to 0, SDCLK Frequency Select, Clock Generator Select in the Clock Control register and Driver Strength Select in Host Control 2 register are set by Host Driver. If this bit is set to 1, SDCLK Frequency Select, Clock Generator Select in the Clock Control register and Driver Strength Select in Host Control 2 register are set by Host Controller as specified in the Preset Value registers.
30	0b RW	Asynchronous Interrupt (async_int): This bit can be set to 1 if a card support asynchronous interrupt and Asynchronous Interrupt Support is set to 1 in the Capabilities register. Asynchronous interrupt is effective when DAT[1] interrupt is used in 4-bit SD mode (and zero is set to Interrupt Pin Select in the Shared Bus Control register). If this bit is set to 1, the Host Driver can stop the SDCLK during asynchronous interrupt period to save power. During this period, the Host Controller continues to deliver Card Interrupt to the host when it is asserted by the Card. Usage: It is recommended that Synchronous Interrupt mode be used for SDIO Controller by setting this be to '0'. If Asynchronous Interrupt Enable mode is used, it is required that this bit remain '0' until SD initialization sequence is complete. 1 = Enabled 0 = Disabled



Bit Range	Default & Access	Field Name (ID): Description
29:24	0b RO	RSVD0: Reserved
23	0b RW	Sampling Clock (sampling_clock): This bit is set by tuning procedure when Execute Tuning is cleared.
22	0b RW/AC	Execute Tuning (execute_tuning): This bit is set to 1 to start tuning procedure and automatically cleared when tuning procedure is completed. The result of tuning is indicated to Sampling Clock Select. Tuning procedure is aborted by writing 0. Refer to the spec for more detail about tuning procedure. 1 = Execute Tuning 0 = Not Tuned or Tuning Completed
21:20	0b RW	Driver Strength (driver_strength): Host Controller output driver in 1.8V signaling is selected by this bit.
19	0b RW	Voltage Regulator Control for I/O Cell (vl): This bit controls voltage regulator for I/O cell.
18:16	0b RW	UHS Mode Select (uhs_mode): This field is used to select one of UHS-I modes.
15:8	0h RO	Rsvd (rsvd): Reserved.
7	0b RO	Command Not Issued By Auto CMD12 Error (cmd_not_iss_cmd12_err): Reserved.
6:5	0h RO	Rsvd1 (rsvd1): Reserved
4	0b RO	Auto CMD12 Index Error (cmd12_ind_err): Reserved.
3	0b RO	Auto CMD12 End Bit Error (cmd12_end_bit_err): Reserved.
2	0b RO	Auto CMD12 CRC Error (cmd12_crc_err): Reserved.
1	0b RO	Auto CMD12 Timeout Error (cmd12_timeout_err): Reserved.
0	0b RO	Auto CMD12 Not Executed (cmd12_not_exe): Reserved.

16.6.27 Capabilities Register (CAPABILITIES)—Offset 40h

This register provides the HD with information specific to the HC implementation. The HC may implement these values as fixed or loaded from flash memory during power on initialization.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h

16.6.28 Capabilities Register 2 (CAPABILITIES_2)—Offset 44h

312824201612840																															
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0																															
capabilities																															
Bit Range		Default & Access		Field Name (ID): Description																											
31:0		0b RO		Capabilities (capabilities): Reserved.																											

16.6.28 Capabilities Register 2 (CAPABILITIES_2)—Offset 44h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h

312824201612840																															
000																															

16.6.29 Maximum Current Capabilities Register (MAX_CUR_CAP)—Offset 48h

These registers indicate maximum current capability for each voltage. The value is meaningful if Voltage Support is set in the Capabilities register. If this information is supplied by the Host System via another method, all Maximum Current Capabilities register shall be 0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	rsvd		max_cur_1p8v		max_cur_3p0v		max_cur_3p3v	

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RO	Reserved (rsvd): Reserved.
23:16	00h RO	Maximum Current for 1.8V (max_cur_1p8v): Reserved.
15:8	00h RO	Maximum Current for 3.0V (max_cur_3p0v): Reserved.
7:0	00h RO	Maximum Current for 3.3V (max_cur_3p3v): Reserved.

16.6.30 Force Event Register for Auto CMD12 Error Status (FORCE_EVENT_CMD12_ERR_STAT)—Offset 50h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
	reserved0	non_cmd12_err	reserved	cmd12_ind_err
				cmd12_end_bit_err
				cmd12_crc_err
				cmd12_timeout_err
				cmd12_not_exe

Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RO	Reserved 0 (reserved0): Reserved.
7	0b RW	Force Event for Command Not Issued By Auto CMD12 Error (non_cmd12_err): 1 = Interrupt is generated 0 = No Interrupt
6:5	00b RO	Reserved (reserved): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	Force Event for Auto CMD12 Index Error (cmd12_ind_err): 1 = Interrupt is generated 0 = No Interrupt
3	0b RW	Force Event for Auto CMD12 End Bit Error (cmd12_end_bit_err): 1 = Interrupt is generated 0 = No Interrupt
2	0b RW	Force Event for Auto CMD12 CRC Error (cmd12_crc_err): 1 = Interrupt is generated 0 = No Interrupt
1	0b RW	Force Event for Auto CMD12 Timeout Error (cmd12_timeout_err): 1 = Interrupt is generated 0 = No Interrupt
0	0b RW	Force Event for Auto CMD12 Not Executed (cmd12_not_exe): 1 = Interrupt is generated 0 = No Interrupt

16.6.31 Force Event Register for Error Interrupt Status (FORCE_EVENT_ERR_INT_STAT)—Offset 52h

Error Interrupt Status register can be written. The effect of a write to this address will be reflected in the Error Interrupt Status Register if the corresponding bit of the Error Interrupt Status Enable Register is set.

- Writing 1 : set each bit of the Error Interrupt Status Register
- Writing 0 : no effect

Note: By setting this register, the Error Interrupt can be set in the Error Interrupt Status register. In order to generate interrupt signal, both the Error Interrupt Status Enable and Error Interrupt Signal Enable shall be set.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 52h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd0	ceata_err	tgt_rsp_err	rsvd	adma_err
				cmd12_err
				cur_limit_err
				data_end_bit_err
				data_crc_err
				data_timeout_err
				cmd_ind_err
				cmd_end_bit_err
				cmd_crc_err
				cmd_timeout_err
Bit Range	Default & Access	Field Name (ID): Description		
15:14	00b RO	Reserved 0 (rsvd0): Reserved.		



Bit Range	Default & Access	Field Name (ID): Description
13	0b RW	Force Event for CEATA Error (ceata_err): Reserved.
12	0b RW	Force Event for Target Response Error (tgt_rsp_err): Reserved.
11:10	0h RO	Reserved (rsvd): Reserved.
9	0b RW	Force Event for ADMA Error (adma_err): 1 = Interrupt is generated 0 = No Interrupt
8	0b RW	Force Event for Auto CMD12 Error (cmd12_err): 1 = Interrupt is generated 0 = No Interrupt
7	0b RW	Force Event for Current Limit Error (cur_limit_err): 1 = Interrupt is generated 0 = No Interrupt
6	0b RW	Force Event for Data End Bit Error (data_end_bit_err): 1 = Interrupt is generated 0 = No Interrupt
5	0b RW	Event for Data CRC Error (data_crc_err): 1 = Interrupt is generated 0 = No Interrupt
4	0b RW	Event for Data Timeout Error (data_timeout_err): 1 = Interrupt is generated 0 = No Interrupt
3	0b RW	Force Event for Command Index Error (cmd_ind_err): 1 = Interrupt is generated 0 = No Interrupt
2	0b RW	Force Event for Command End Bit Error (cmd_end_bit_err): 1 = Interrupt is generated 0 = No Interrupt
1	0b RW	Force Event for Command CRC Error (cmd_crc_err): 1 = Interrupt is generated 0 = No Interrupt
0	0b RW	Force Event for Command Timeout Error (cmd_timeout_err): 1 = Interrupt is generated 0 No Interrupt

16.6.32 ADMA Error Status Register (ADMA_ERR_STAT)—Offset 54h

When ADMA Error Interrupt occurs, the ADMA Error States field in this register holds the ADMA state and the ADMA System Address Register holds the address around the error descriptor. To recover from the error, the Host Driver requires the ADMA state to identify the error descriptor address as follows:

- ST_STOP: Previous location set in the ADMA System Address register is the error descriptor address
- ST_FDS: Current location set in the ADMA System Address register is the error descriptor address
- ST_CADR: This state is never set because do not generate ADMA error in this state.



- **ST_TFR:** Previous location set in the ADMA System Address register is the error descriptor address

The Host Controller generates the ADMA Error Interrupt when it detects invalid descriptor data (Valid=0) at the ST_FDS state. In this case, ADMA Error State indicates that an error occurs at ST_FDS state. The Host Driver may find that the Valid bit is not set in the error descriptor.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd		adma_err_state
		adma_len_mis_err

Bit Range	Default & Access	Field Name (ID): Description
7:3	0h RO	Reserved (rsvd): Reserved.
2	0b RO	ADMA Length Mismatch Error (adma_len_mis_err): This error occurs in the following 2 cases. • While Block Count Enable being set, the total data length specified by the Descriptor table is different from that specified by the Block Count and Block Length. • Total data length can not be divided by the block length. • 1 = Error • 0 = No Error
1:0	00b RO	ADMA Error State (adma_err_state): This field indicates the state of ADMA when error is occurred during ADMA data transfer. This field never indicates '10' because ADMA never stops in this state. Refer to the spec for tabular information about the relationship between this field and SYS_SDR register.

16.6.33 ADMA System Address Register (ADMA_SYS_ADDR)—Offset 58h

This register contains the physical Descriptor address used for ADMA data transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	ADMA System Address (adma_sys_addr): Reserved.

Bit Range	Default & Access	Field Name (ID): Description
31:0	00010000h RO	Preset Values (Preset_Values): Reserved.

16.6.34 Boot Timeout Control (BOOT_TIMEOUT_CTRL)—Offset 70h

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)
BAR Reference: [B:0, D:17, F:0] + 10h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

time_cnt_val

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
30:24	0h RW	Back-End Power Control (pwr_ctrl): Each bit of this field controls back-end power supply for an embedded device. Host interface voltage (VDDH) is not controlled by this field. The number of devices supported is specified by Number of Clock Pins, and a maximum of 7 devices can be controlled. - D24 Back-end Power Control for Device 1 - D25 Back-end Power Control for Device 2 - D26 Back-end Power Control for Device 3 - D27 Back-end Power Control for Device 4 - D28 Back-end Power Control for Device 5 - D29 Back-end Power Control for Device 6 - D30 Back-end Power Control for Device 7 The function of each bit is defined as follows: 0 = Back-end Power is Off 1 = Back-end Power is Supplied Back-End power control is effective for embedded memory devices in the Sleep State that support the Sleep command (CMD14) to reduce power consumption and embedded SDIO devices when IOEx is set to 0.
23	0b RO	RSVD1: Reserved
22:20	0h RW	Interrupt Pin Select (int_pin): Interrupt pin inputs are enabled by this field. Enable of unsupported interrupt pin is meaningless. 000b = Interrupt is detected by the Interrupt Cycle. - xx1b = INT_A is enabled - x1xb = INT_B is enabled 1xxb = INT_C is enabled
19	0b RO	RSVD2: Reserved
18:16	0h RW	Clock Pin Select (clk_pin): One of clock pin outputs is selected by this field. Selection of unsupported clock pins is meaningless. Refer to Figure 2-38 for the timing of clock outputs. 000b = Clock Pins are disabled 001b = CLK[1] is selected 010b = CLK[2] is selected ... 111b = CLK[7] is Selected
15	0b RO	RSVD3: Reserved
14:8	0h RO	Bus Width Preset (bus_width): Shared bus supports mixing of 4-bit and 8-bit bus width devices. Each bit of this field specifies the bus width for each embedded device. The number of devices supported is specified by Number of Clock Pins, and a maximum of 7 devices are supported. This field is effective when multiple devices are connected to a shared bus (Slot Type is set to 10b in the Capabilities register). In the other case, Extended Data Transfer Width in the Host Control 1 register is used to select 8-bit bus width. As use of 1-bit mode is not intended for shared bus, Data Transfer Width in the Host Control 1 register should be set to 1. - D24 = Bus width preset for Device 1 - D25 = Bus width preset for Device 2 - D26 = Bus width preset for Device 3 - D27 = Bus width preset for Device 4 - D28 = Bus width preset for Device 5 - D29 = Bus width preset for Device 6 - D30 = Bus width preset for Device 7 The function of each bit is defined as follows: 0 = 4 bit buswidth mode 1 = 8 bit buswidth mode
7:6	0b RO	RSVD4: Reserved



Bit Range	Default & Access	Field Name (ID): Description
5:4	0h RO	Number of Interrupt Pins (num_int_pin): This field indicates support of interrupt input pins for shared bus system. Three asynchronous interrupt pins are defined, INT_A#, INT_B# and INT_C#. Which interrupt pin is used is determined by the system. Each one is driven by open drain and then wired OR connection is possible. 00b = Interrupt Input Pin is not supported 01b = INTA is Supported 10b = INTA and INTB are supported 11b = INTA, INTB and INTC are supported
3	0b RO	RSVD5: Reserved
2:0	0h RO	Number of Clock Pins (num_clk_pin): This field indicates support of clock pins to select one of devices for shared bus system. Up to 7 clock pins can be supported. Shared bus is supported by specific system. Then the Standard Host Driver does not support control of these clock pins. 000b Shared bus is not supported 001b 1 SDCLK pin is supported 010b 2 SDCLK pins are supported ... 111b 7 SDCLK pins are supported

16.6.37 SPI Interrupt Support Register (SPI_INT_SUP)—Offset F0h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 00h

7	4	0
0	0	0
spi_int_support		

Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RW	SPI Interrupt Support (spi_int_support): This bit is set to indicate the assertion of interrupts in the SPI mode at any time, irrespective of the status of the card select (CS) line. If this bit is zero, then SDIO card can only assert the interrupt line in the SPI mode when the CS line is asserted.

16.6.38 Slot Interrupt Status Register (SLOT_INT_STAT)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:17, F:0] + 10h

Default: 0000h



Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RO	Reserved (reserved): Reserved.
7:0	00h RO	Interrupt Signal For Each Slot (int_sig_slot): These status bits indicate the logical OR of Interrupt Signal and Wakeup Signal for each slot. A maximum of 8 slots can be defined. If one interrupt signal is associated with multiple slots, the Host Driver can know which interrupt is generated by reading these status bits. By a power on reset or by setting Software Reset For All, the interrupt signal shall be de-asserted and this status shall read 00h. • Bit 00 = Slot 1 • Bit 01 = Slot 2 • Bit 02 = Slot 3 • • Bit 07 = Slot 8

16.6.39 Host Controller Version Register (HOST_CTRL_VER)—Offset FEh

Type: Memory Mapped I/O Register
(Size: 16 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)
BAR Reference: [B:0, D:17, F:0] + 10h

15			12				8				4				0
1	0	1	1	0	1	0	1	0	0	0	0	0	0	1	0
vend_ver_num								spec_ver_num							

Bit Range	Default & Access	Field Name (ID): Description
15:8	b5h RO	Vendor Version Number (vend_ver_num): This status is reserved for the vendor version number. The Host Driver should not use this status.
7:0	02h RO	Specification Version Number (spec_ver_num): This status indicates the Host Controller Spec. Version. The upper and lower 4-bits indicate the version. • 00h = SD Host Specification Version 1.00 • 01h = SD Host Specification Version 2.00, Including the feature of the ADMA and Test Register • 02h = SD Host Specification Version 3.00 • others = Reserved



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Device ID (DEVICEID): Device ID identifies the particular AHB device. This is tied to a strap at the top level.
15:0	0000h RO	Vendor ID (VENDORID): Vendor ID is a unique ID provided by PCI SIG which identifies the manufacturer of the device. This is tied to a strap at the top level.

16.7.2 Status and Command Register (STATUSCOMMAND)—Offset 4h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + 4h

Default: 00100000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0	RMA	RCA	Reserved1	CAPLIST	INTR_STATUS	Reserved2	Reserved3	INTR_DISABLE
								Reserved4
								SERR_ENABLE
								Reserved5
								BME
								MSE
								Reserved6

Bit Range	Default & Access	Field Name (ID): Description
31:30	0h RO	Reserved0: Reserved.
29	0h RW/1C	Received Master Abort (RMA): If the completion status received from IOSF is UR, Bridge sets this bit. S/W writes a '1' to this bit to clear it. This bit will not be set for the Fabric port. This bit is not used for the Fabric Port
28	0h RW/1C	Received Target Abort (RCA): If the completion status received from IOSF is CA, Bridge sets this bit. S/W writes a 1 to this bit to clear it. This bit will not be set for the fabric port. This bit is not used for the Fabric Port
27:21	00h RO	Reserved1: Reserved.
20	1h RO	Capabilities List (CAPLIST): Hardwired to 1. Indicates that the controller contains a capabilities pointer list. The first item is pointed to by looking at configuration offset 34h. If PM capability is not required then this bit should be tied to 0.
19	0h RO	Interrupt Status (INTR_STATUS): This bit reflects state of interrupt in the device. Only when the Interrupt Disable bit in the command register is a 0 and this Interrupt Status bit is a 1, will the device's/function's INTx# signal be asserted. Setting the Interrupt Disable bit to a 1 has no effect on the state of this bit. This bit reflects Legacy interrupt status.
18:16	0h RO	Reserved2: Reserved.
15:11	00h RO	Reserved3: Reserved.
10	0h RW	Interrupt Disable (INTR_DISABLE): Setting this bit disables INTx assertion from Bridge. The interrupt disabled is legacy INTx# interrupt; i.e., Bridge does not send Interrupt Assert message through the IOSF SideBand Channel. Reset value of this bit is 0.
9	0h RO	Reserved4: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
8	0h RW	SERR# Enable (SERR_ENABLE): This bit controls the sending of DO_SERR messages on IOSF SB.
7:3	00h RO	Reserved5: Reserved.
2	0h RW	Bus Master Enable (BME): If this bit is 0, Bridge does not generate any new upstream transaction on IOSF as a master. Reset value of this bit is 0.
1	0h RW	Memory Space Enable (MSE): This bit controls Bridges response to downstream memory accesses. When set, accesses to the memory space of the device are enabled. Reset value of this bit is 0.
0	0h RO	Reserved6: Reserved.

16.7.3 Revision ID and Class Code Register (REVCLASSCODE)—Offset 8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + 8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Class Code (CLASS_CODES): This register is read-only and is used to identify the generic function of the device and, in some cases, a specific register level programming interface. The register is broken into three byte size fields. The upper byte (at offset 0Bh) is a base class code which broadly classifies the type of function the device performs. The middle byte (at offset 0Ah) is a sub-class code which identifies more specifically the function of the device. The lower byte (at offset 09h) identifies a specific register-level programming interface (if any) so that device independent software can interact with the device. This register is tied to a strap at the top level.
7:0	00h RO	Revision ID (RID): Identifies the revision of a particular AHB device. This is tied to a strap at the top level.

16.7.4 Cache Line Size, Latency Timer, and Header Type Register (CLLATHEADERBIST)—Offset Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + Ch

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0	MULFNDEV	HEADERTYPE	LATTIMER	CACHELINE_SIZE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	0h RO	Multifunction Device (MULFNDEV): This bit is always 0 for non-fabric ports. For fabric ports it is driven from the fabric_mult_function strap. A value of 1 indicates a multifunction device; a value of 0 indicates a single function device.
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Doesn't apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

16.7.5 Base Address Register (BAR)—Offset 10h

Each AHB device is a single function device with only a single BAR associated with it. Bits 31:4 indicate the Base Address register. Power-up software can determine how much address space the AHB Device requires by writing a value of all 1's to the register and then reading the value back. Bridge will return 0's in all don't-care address bits, effectively specifying the address space required. Unimplemented Base Address registers are hardwired to zero. This is the Size Indicator Read only bits of the register.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR	SIZEINDICATOR	PREFETCHABLE	TYPE	MESSAGE_SPACE				

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1s.



Type: PCI Configuration Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SUBSYSTEMID					SUBSYSTEMVENDORID			

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW/O	Subsystem ID (SUBSYSTEMID): This register should be implemented for any function that could be instantiated more than once in a given system. Th is register makes it possible for the operating environment to distinguish one audio subsystem from the other. This is a Read Write Once register.
15:0	0000h RW/O	Subsystem Vendor ID (SUBSYSTEMVENDORID): This register should be implemented for any function that could be instantiated more than once in a given system. This register enables the operating environment to distinguish one subsystem from the other. This is a Read Write Once register.

16.7.8 Expansion ROM Base Address Register (EXPANSION_ROM_BASEADDR)—Offset 30h

Type: PCI Configuration Register
(Size: 32 bits) **Offset:** [B:0, D:18, F:0] + 30h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSTION_ROM_BASE								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Expansion ROM Base Address (EXPANSION_ROM_BASE): Value of all 0s indicates no support for Expansion ROM.



16.7.9 Capabilities Pointer Register (CAPABILITYPTR)—Offset 34h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + 34h

Default: 00000080h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.
7:0	80h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. When PM capability is disabled, this register is 00h.

16.7.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
MAX_LAT				MIN_GNT				INTLINE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates that the device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates that the device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to communicate to software the interrupt line that the interrupt pin is connected to.



16.7.11 Power Management Capability ID Register (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + 80h

Default: 48030001h

31	28	24	20	16	12	8	4	0
0	1	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
PMESUPPORT				Reserved0				
				VERSION				
				NXTCAP				
				POWER_CAP				

Bit Range	Default & Access	Field Name (ID): Description
31:27	09h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. bit(11) X XXX1b - PME# can be asserted from D0 bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. bit(14) X 1XXXb - PME# can be asserted from D3hot. bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the private configuration space PME_Support XORed with the PME_Support strap.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.

16.7.12 Power Management Control and Status Register (PMECTRLSTATUS)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0					PMESTATUS	Reserved1		PMEEENABLE
								Reserved2
								NO_SOFT_RESET
								Reserved3
								POWERSTATE



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit in this register.
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.
3	1h RO	No Soft Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for upstream decode on fabric ports.

16.7.13 General Purpose Read Write Register1 (GEN_REGRW1)—Offset A0h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + A0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

GEN_REG_RW1

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	GEN_REG_RW1: capabilities over-ride for the sd/sdio/emmc host controller (bits 31:0)



16.7.14 General Purpose Read Write Register2 (GEN_REGRW2)—Offset A4h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + A4h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
CAP_REG_SEL	GEN_REG_RW2							

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	CAP_REG_SEL: select if the capability will come from the GEN PCI register or from a hard wire
30:0	0h RW	GEN_REG_RW2: capabilities over-ride for the sd/sdio/emmc host controller (bits 62:32)

16.7.15 General Purpose Read Write Register3 (GEN_REGRW3)—Offset A8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + A8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
GEN_REG_RW3								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	GEN_REG_RW3: Reserved.

16.7.16 General Purpose Read Write Register4 (GEN_REGRW4)—Offset ACh

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:18, F:0] + ACh



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



16.8 SD Card Memory Mapped IO Registers

Table 187. Summary of SD Card Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"SDMA System Address / Argument 2 Register (SYS_ADR)—Offset 0h" on page 1828	00000000h
4–5h	2	"Block Size Register (BLK_SIZE)—Offset 4h" on page 1829	0000h
6–7h	2	"Block Count Register (BLK_COUNT)—Offset 6h" on page 1830	0000h
8–Bh	4	"Argument 1 Register (ARGUMENT)—Offset 8h" on page 1831	00000000h
C–Dh	2	"Transfer Mode Register (TX_MODE)—Offset Ch" on page 1831	0000h
E–Fh	2	"Command Register (CMD)—Offset Eh" on page 1833	0000h
10–13h	4	"Response Register 0 (RESPONSE0)—Offset 10h" on page 1834	00000000h
14–17h	4	"Response Register 2 (RESPONSE2)—Offset 14h" on page 1835	00000000h
18–1Bh	4	"Response Register 4 (RESPONSE4)—Offset 18h" on page 1835	00000000h
1C–1Fh	4	"Response Register 6 (RESPONSE6)—Offset 1Ch" on page 1836	00000000h
20–23h	4	"Buffer Data Port Register (BUF_DATA_PORT)—Offset 20h" on page 1836	00000000h
24–27h	4	"Present State Register (PRE_STATE)—Offset 24h" on page 1837	1FFF0000h
28–28h	1	"Host Control 1 Register (HOST_CTL)—Offset 28h" on page 1840	00h
29–29h	1	"Power Control Register (PWR_CTL)—Offset 29h" on page 1841	00h
2A–2Ah	1	"Block Gap Control Register (_BLK_GAP_CTL)—Offset 2Ah" on page 1842	00h
2B–2Bh	1	"Wakeup Control Register (WAKEUP_CTL)—Offset 2Bh" on page 1843	00h
2C–2Dh	2	"Clock Control Register (CLK_CTL)—Offset 2Ch" on page 1844	0000h
2E–2Eh	1	"Timeout Control Register (TIMEOUT_CTL)—Offset 2Eh" on page 1846	00h
2F–2Fh	1	"Software Reset Register (SW_RST)—Offset 2Fh" on page 1847	00h
30–31h	2	"Normal Interrupt Status Register (NML_INT_STATUS)—Offset 30h" on page 1848	0000h
32–33h	2	"Error Interrupt Status Register (ERR_INT_STATUS)—Offset 32h" on page 1851	0000h
34–35h	2	"Normal Interrupt Status Enable (NRM_INT_STATUS_EN)—Offset 34h" on page 1853	0000h
36–37h	2	"Error Interrupt Status Enable Register (ERR_INT_STAT_EN)—Offset 36h" on page 1855	0000h
38–39h	2	"Normal Interrupt Signal Enable Register (NRM_INT_SIG_EN)—Offset 38h" on page 1856	0000h
3A–3Bh	2	"Error Interrupt Signal Enable Register (ERR_INT_SIG_EN)—Offset 3Ah" on page 1857	0000h
3C–3Fh	4	"Auto CMD12 Error Status Register and Host Control 2 Register (CMD12_ERR_STAT_HOST_CTRL_2)—Offset 3Ch" on page 1859	00000000h
40–43h	4	"Capabilities Register (CAPABILITIES)—Offset 40h" on page 1860	00000000h
44–47h	4	"Capabilities Register 2 (CAPABILITIES_2)—Offset 44h" on page 1861	00000000h
48–4Bh	4	"Maximum Current Capabilities Register (MAX_CUR_CAP)—Offset 48h" on page 1861	00000000h
50–51h	2	"Force Event Register for Auto CMD12 Error Status (FORCE_EVENT_CMD12_ERR_STAT)—Offset 50h" on page 1862	0000h

Table 187. Summary of SD Card Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
52–53h	2	"Force Event Register for Error Interrupt Status (FORCE_EVENT_ERR_INT_STAT)—Offset 52h" on page 1863	0000h
54–54h	1	"ADMA Error Status Register (ADMA_ERR_STAT)—Offset 54h" on page 1864	00h
58–5Bh	4	"ADMA System Address Register (ADMA_SYS_ADDR)—Offset 58h" on page 1865	00000000h
70–73h	4	"Boot Timeout Control (BOOT_TIMEOUT_CTRL)—Offset 70h" on page 1866	00000000h
74–74h	1	"Debug Selection Register (DEBUG_SEL)—Offset 74h" on page 1866	00h
E0–E3h	4	"Shared Bus Control Register (SHARED_BUS)—Offset E0h" on page 1867	00000000h
F0–F0h	1	"SPI Interrupt Support Register (SPI_INT_SUP)—Offset F0h" on page 1869	00h
FC–FDh	2	"Slot Interrupt Status Register (SLOT_INT_STAT)—Offset FCh" on page 1869	0000h
FE–FFh	2	"Host Controller Version Register (HOST_CTRL_VER)—Offset FEh" on page 1870	B502h

16.8.1 SDMA System Address / Argument 2 Register (SYS_ADR)—Offset 0h

This register contains the physical system memory address used for DMA transfers or the second argument for the Auto CMD23.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h

Diagram illustrating the structure of the `sys_adr` register. The register is 32 bits wide, divided into four 8-bit fields. The top 8 bits are labeled 31, 28, 24, 20, 16, 12, 8, 4, 0. The bottom 8 bits are labeled 7, 6, 5, 4, 3, 2, 1, 0. The label `sys_adr` is positioned vertically below the register.



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	SDMA System Address (sys_adr): (1) SDMA System Address This register contains the system memory address for a SDMA transfer. When the Host Controller stops a SDMA transfer, this register shall point to the system address of the next contiguous data position. It can be accessed only if no transaction is executing (i.e., after a transaction has stopped). Read operations during transfers may return an invalid value. The Host Driver shall initialize this register before starting a SDMA transaction. After SDMA has stopped, the next system address of the next contiguous data position can be read from this register. The SDMA transfer waits at each boundary specified by the Host SDMA Buffer Boundary in the Block Size register. The Host Controller generates a DMA Interrupt to request the Host Driver to update this register. The Host Driver sets the next system address of the next data position to this register. When the uppermost byte of this register (003h) is written, the Host Controller restarts the SDMA transfer. When restarting SDMA by the Resume command or by setting Continue Request in the Block Gap Control register, the Host Controller shall start at the next contiguous address stored here in the SDMA System Address register. ADMA does not use this register. (2) Argument 2 This register is used with the Auto CMD23 to set a 32-bit block count value to the argument of the CMD23 while executing Auto CMD23. If Auto CMD23 is used with ADMA, the full 32-bit block count value can be used. If Auto CMD23 is used without ADMA, the available block count value is limited by the Block Count register. 65535 blocks is the maximum value in this case.

16.8.2 Block Size Register (BLK_SIZE)—Offset 4h

This register is used to configure the number of bytes in a data block.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
tx_blk_size_12	boundary	tr_blk_size		

Bit Range	Default & Access	Field Name (ID): Description
15	0b RW	TX_BLK_SIZE_12 (tx_blk_size_12): Transfer Block Size 12th bit. This bit is added to support 4Kb Data block transfer.



This register contains the SD Command Argument.

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [BAR] + 8h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
argument								

16.8.5 Transfer Mode Register (TX_MODE)—Offset Ch

Access Method



Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd		boot_en	spi_mode	cmd_comp_ata
		blk_sel	data_tr_dir	auto_cmd_en
			blk_count_en	dma_en

Bit Range	Default & Access	Field Name (ID): Description
15:9	00h RO	Reserved (rsvd): Reserved.
8	0b RW	BOOT_EN (boot_en): To start boot operation for MMC4.3 1 - To start boot mode 0 - Stop the boot read
7	0b RW	SPI_MODE (spi_mode): SPI mode enable bit. 1 - SPI mode 0 - SD mode
6	0b RW	CMD_COMP_ATA (cmd_comp_ata): Command Completion Signal Enable for CE-ATA Device. ???1??? - Device will send command completion Signal ???0??? - Device will not send command completion Signal
5	0b RW	BLK_SEL (blk_sel): Multi / Single Block Select This bit is set when issuing multiple-block transfer commands using DAT line. For any other commands, this bit shall be set to 0. If this bit is 0, it is not necessary to set the Block Count register. (Refer to Table 2-8) 1 Multiple Block 0 Single Block
4	0b RW	Data Transfer Direction Select (data_tr_dir): This bit defines the direction of DAT line data transfers. The bit is set to 1 by the Host Driver to transfer data from the SD card to the SD Host Controller, and it is set to 0 for all other commands. 1 = Read (Card to Host) 0 = Write (Host to Card)
3:2	0b RW	AUTO_CMD_EN (auto_cmd_en): This field determines use of auto command functions 00b - Auto Command Disabled 01b - Auto CMD12 Enable 10b - Auto CMD23 Enable 11b - Reserved
1	0b RW	Block Count Enable (blk_count_en): This bit is used to enable the Block Count register, which is only relevant for multiple block transfers. When this bit is 0, the Block Count register is disabled, which is useful in executing an infinite transfer. (Refer to Table 2-8). If ADMA2 data transfer is more than 65535 blocks, this bit shall be set to 0. In this case, data transfer length is designated by Descriptor Table. 1 = Enable 0 = Disable
0	0b RW	DMA Enable (dma_en): This bit enables DMA functionality as described in section 1.4. DMA can be enabled only if it is supported as indicated in the Capabilities register. One of the DMA modes can be selected by DMA Select in the Host Control register. If DMA is not supported, this bit is meaningless and shall always read 0. If this bit is set to 1, a DMA operation shall begin when the Host Driver writes to the upper byte of Command register (00Fh). 1 = DMA Data transfer 0 = No data transfer or Non DMA data transfer



16.8.6 Command Register (CMD)—Offset Eh

The Host Driver shall check the Command Inhibit (DAT) bit and Command Inhibit (CMD) bit in the Present State register before writing to this register. Writing to the upper byte of this register triggers SD command generation. The Host Driver has the responsibility to write this register because the Host Controller does not protect for writing when Command Inhibit (CMD) is set.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + Eh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd	cmd_index	cmd_type	data_pr_sel	cmd_index_chk_en
			cmd_crc_chk_en	reserved
				resp_type_sel

Bit Range	Default & Access	Field Name (ID): Description
15:14	0h RO	Rsvd (rsvd): Reserved.
13:8	0h RW	Command Index (cmd_index): These bits shall be set to the command number (CMD0-63, ACMD0-63) that is specified in bits 45-40 of the Command-Format in the Physical Layer Specification and SDIO Card Specification.
7:6	00b RW	Command Type (cmd_type): There are three types of special commands: Suspend, Resume and Abort. These bits shall be set to 00b for all other commands. (1) Suspend Command If the Suspend command succeeds, the Host Controller shall assume the SD Bus has been released and that it is possible to issue the next command, which uses the DAT line. The Host Controller shall de-assert Read Wait for read transactions and stop checking busy for write transactions. The interrupt cycle shall start, in 4-bit mode. If the Suspend command fails, the Host Controller shall maintain its current state, and the Host Driver shall restart the transfer by setting Continue Request in the Block Gap Control register. (Refer to 3.12.1 Suspend Sequence). (2) Resume Command The Host Driver re-starts the data transfer by restoring the registers in the range of 000-00Dh. (Refer to Figure 1-4 in section 1.6 for the register map.) The Host Controller shall check for busy before starting write transfers. (3) Abort Command If this command is set when executing a read transfer, the Host Controller shall stop reads to the buffer. If this command is set when executing a write transfer, the Host Controller shall stop driving the DAT line. After issuing the Abort command, the Host Driver should issue a software reset. (Refer to 3.8 Abort Transaction). 11b = Abort -- CMD12, CMD52 for writing 'I/O Abort' in CCCR 10b = Resume -- CMD52 for writing 'Function Select' in CCCR 01b = Suspend -- CMD52 for writing 'Bus Suspend' in CCCR 00b = Normal -- Other commands
5	0b RW	Data Present Select (data_pr_sel): This bit is set to 1 to indicate that data is present and shall be transferred using the DAT line. It is set to 0 for the following: (1) Commands using only CMD line (ex. CMD52). (2) Commands with no data transfer but using busy signal on DAT[0] line (R1b or R5b ex. CMD38). (3) Resume command. 1 = Data Present 0 = No Data Present



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	Command Index Check Enable (cmd_index_chk_en): If this bit is set to 1, the Host Controller shall check the Index field in the response to see if it has the same value as the command index. If it is not, it is reported as a Command Index Error. If this bit is set to 0, the Index field is not checked. 1 = Enable 0 = Disable
3	0b RW	Command CRC Check Enable (cmd_crc_chk_en): If this bit is set to 1, the Host Controller shall check the CRC field in the response. If an error is detected, it is reported as a Command CRC Error. If this bit is set to 0, the CRC field is not checked. The position of CRC field is determined according to the length of the response. (Refer to definition in D01-00 and Table 2-10 below.) 1 = Enable 0 = Disable
2	0b RO	Reserved (reserved): Reserved.
1:0	0h RW	Response Type Select (resp_type_sel): 00 = No Response 01 = Response Length 136 10 = Response Length 48 11 = Response Length 48 check Busy after response

16.8.7 Response Register 0 (RESPONSE0)—Offset 10h

This register is used to store responses from SD cards.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 10h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

cmd_resp

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RO	Command Response (cmd_resp): The Table 2-12 describes the mapping of command responses from the SD Bus to this register for each response type. In the table, R[] refers to a bit range within the response data as transmitted on the SD Bus, REP[] refers to a bit range within the Response register



16.8.10 Response Register 6 (RESPONSE6)—Offset 1Ch

This register is used to store responses from SD cards.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

cmd_resp

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RO	Command Response (cmd_resp): The Table 2-12 describes the mapping of command responses from the SD Bus to this register for each response type. In the table, R[] refers to a bit range within the response data as transmitted on the SD Bus, REP[] refers to a bit range within the Response register

16.8.11 Buffer Data Port Register (BUF_DATA_PORT)—Offset 20h

32-bit data port register to access internal buffer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 20h

BAR Type: PCI Configuration Register (Size: 32 bits)


BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

buf_data

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Buffer Data (buf_data): The Host Controller buffer can be accessed through this 32-bit Data Port register. Refer to section 1.7.



Bit Range	Default & Access	Field Name (ID): Description
16	1b RO	Card Inserted (crd_ins): This bit indicates whether a card has been inserted. The Host Controller shall debounce this signal so that the Host Driver will not need to wait for it to stabilize. Changing from 0 to 1 generates a Card Insertion interrupt in the Normal Interrupt Status register and changing from 1 to 0 generates a Card Removal interrupt in the Normal Interrupt Status register. The Software Reset For All in the Software Reset register shall not affect this bit. If a card is removed while its power is on and its clock is oscillating, the Host Controller shall clear SD Bus Power in the Power Control register (Refer to Section 2.2.11) and SD Clock Enable in the Clock Control register (Refer to Section 2.2.14). When this bit is changed from 1 to 0, the Host Controller shall immediately stop driving CMD and DAT[3:0] (tri-state). In addition, the Host Driver should clear the Host Controller by the Software Reset For All in Software Reset register. The card detect is active regardless of the SD Bus Power. 1 = Card Inserted 0 = Reset or Debouncing or No Card
15:12	0h RO	Reserved1 (reserved1): Reserved.
11	0b RO	Buffer Read Enable (buf_rd_en): This status is used for non-DMA read transfers. The Host Controller may implement multiple buffers to transfer data efficiently. This read only flag indicates that valid data exists in the host side buffer. If this bit is 1, readable data exists in the buffer. A change of this bit from 1 to 0 occurs when all the block data is read from the buffer. A change of this bit from 0 to 1 occurs when block data is ready in the buffer and generates the Buffer Read Ready interrupt. 1 = Read enable 0 = Read disable
10	0b RO	Buffer Write Enable (buf_wr_en): This status is used for non-DMA write transfers. The Host Controller can implement multiple buffers to transfer data efficiently. This read only flag indicates if space is available for write data. If this bit is 1, data can be written to the buffer. A change of this bit from 1 to 0 occurs when all the block data is written to the buffer. A change of this bit from 0 to 1 occurs when top of block data can be written to the buffer and generates the Buffer Write Ready interrupt. The Host Controller should neither set Buffer Write Enable nor generate Buffer Write Ready Interrupt after the last block data is written to the Buffer Data Port Register. 1 = Write enable 0 = Write disable
9	0b RO	Read Transfer Active (rd_tx_active): This status is used for detecting completion of a read transfer. Refer to Section 3.12.3 for sequence details. This bit is set to 1 for either of the following conditions: - After the end bit of the read command. - When read operation is restarted by writing a 1 to Continue Request in the Block Gap Control register. This bit is cleared to 0 for either of the following conditions: - When the last data block as specified by block length is transferred to the System. - In case of ADMA2, end of read operation is designated by Descriptor Table. - When all valid data blocks in the Host Controller have been transferred to the System and no current block transfers are being sent as a result of the Stop At Block Gap Request being set to 1. A Transfer Complete interrupt is generated when this bit changes to 0. 1 = Transferring data 0 = No valid data



Bit Range	Default & Access	Field Name (ID): Description
8	0b RO	Write Transfer Active (wr_tx_active): This status indicates a write transfer is active. If this bit is 0, it means no valid write data exists in the Host Controller. Refer to Section 3.12.4 for more details on the sequence of events. This bit is set in either of the following cases: - After the end bit of the write command. - When write operation is restarted by writing a 1 to Continue Request in the Block Gap Control register. This bit is cleared in either of the following cases: - After getting the CRC status of the last data block as specified by the transfer count (Single and Multiple) In case of ADMA2, transfer count is designated by Descriptor Table. - After getting the CRC status of any block where data transmission is about to be stopped by a Stop At Block Gap Request. During a write transaction, a Block Gap Event interrupt is generated when this bit is changed to 0, as the result of the Stop At Block Gap Request being set. This status is useful for the Host Driver in determining non DAT line commands can be issued during write busy. 1 Transferring data 0 No valid data
7:3	00h RO	Reserved (reserved): Reserved.
2	0b RO	DAT Line Active (dat_ln_active): This bit indicates whether one of the DAT lines on SD Bus is in use. (a) In the case of read transactions This status indicates whether a read transfer is executing on the SD Bus. Changing this value from 1 to 0 generates a Block Gap Event interrupt in the Normal Interrupt Status register, as the result of the Stop At Block Gap Request being set. Refer to Section 3.12.3 for details on timing. This bit shall be set in either of the following cases: - After the end bit of the read command. - When writing a 1 to Continue Request in the Block Gap Control register to restart a read transfer. This bit shall be cleared in either of the following cases: - When the end bit of the last data block is sent from the SD Bus to the Host Controller. In case of ADMA2, the last block is designated by the last transfer of Descriptor Table. - When a read transfer is stopped at the block gap initiated by a Stop At Block Gap Request. The Host Controller shall stop read operation at the start of the interrupt cycle of the next block gap by driving Read Wait or stopping SD clock. If the Read Wait signal is already driven (due to data buffer cannot receive data), the Host Controller can continue to stop read operation by driving the Read Wait signal. It is necessary to support Read Wait in order to use suspend / resume function. (b) In the case of write transactions This status indicates that a write transfer is executing on the SD Bus. Changing this value from 1 to 0 generate a Transfer Complete interrupt in the Normal Interrupt Status register. Refer to Section 3.12.4 for sequence details. This bit shall be set in either of the following cases: - After the end bit of the write command. - When writing to 1 to Continue Request in the Block Gap Control register to continue a write transfer. This bit shall be cleared in either of the following cases: - When the SD card releases write busy of the last data block. If SD card does not drive busy signal for 8 SD Clocks, the Host Controller shall consider the card drive 'Not Busy'. In case of ADMA2, the last block is designated by the last transfer of Descriptor Table. - When the SD card releases write busy prior to waiting for write transfer as a result of a Stop At Block Gap Request. (c) Command with busy This status indicates whether a command indicates busy (ex. erase command for memory) is executing on the SD Bus. This bit is set after the end bit of the command with busy and cleared when busy is de-asserted. Changing this bit from 1 to 0 generate a Transfer Complete interrupt in the Normal Interrupt Status register. Refer Figure 2-11 to Figure 2-13. 1 = DAT Line Active 0 = DAT Line Inactive



Bit Range	Default & Access	Field Name (ID): Description
1	0b RO	Command Inhibit (DAT) (cmd_inhibit_dat): This status bit is generated if either the DAT Line Active or the Read Transfer Active is set to 1. If this bit is 0, it indicates the Host Controller can issue the next SD Command. Commands with busy signal belong to Command Inhibit (DAT) (ex. R1b, R5b type). Changing from 1 to 0 generates a Transfer Complete interrupt in the Normal Interrupt Status register. Note: The SD Host Driver can save registers in the range of 000-00Dh for a suspend transaction after this bit has changed from 1 to 0. 1 Cannot issue command which uses the DAT line 0 Can issue command which uses the DAT line
0	0b RO	Command Inhibit (CMD) (cmd_inhibit_cmd): Command Inhibit (CMD) If this bit is 0, it indicates the CMD line is not in use and the Host Controller can issue a SD Command using the CMD line. cleared when the command response is received. Auto CMD12 and Auto CMD23 consist of two responses. In this case, this bit is not cleared by the response of CMD12 or CMD23 but cleared by the response of a read/write command. Status issuing Auto CMD12 is not read from this bit. So if a command is issued during Auto CMD12 operation, Host Controller shall manage to issue two commands: CMD12 and a command set by Command register. Even if the Command Inhibit (DAT) is set to 1, commands using only the CMD line can be issued if this bit is 0. Changing from 1 to 0 generates a Command Complete Interrupt in the Normal Interrupt Status register. If the Host Controller cannot issue the command because of a command conflict error (Refer to Command CRC Error in Section 2.2.18) or because of Command Not Issued By Auto CMD12 Error (Refer to Section 2.2.23), this bit shall remain 1 and the Command Complete is not set. 1 Cannot issue command 0 Can issue command using only CMD line

16.8.13 Host Control 1 Register (HOST_CTL)—Offset 28h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
crd_det_sig_sel	crd_det_tst_lv	sd8_bit_mode	dma_sel	hi_spd_en	data_tx_wid	led_ctl	

Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	Card Detect Signal Selection (crd_det_sig_sel): This bit selects source for the card detection. 1 = The Card Detect Test Level is selected (for test purposes) 0 = SD CD# is selected (for normal use) When the source for the card detection is switched, the interrupt should be disabled during the switching period by clearing the Interrupt Status/Signal Enable register in order to mask unexpected interrupt being caused by the glitch. The Interrupt Status/Signal Enable should be disabled during the period of debouncing.



Bit Range	Default & Access	Field Name (ID): Description
6	0b RW	Card Detect Test Level (crd_det_tst_lvl): This bit is enabled while the Card Detect Signal Selection is set to 1, and it indicates whether or not the card is inserted. 1 = Card Inserted 0 = No Card
5	0b RW	SD8 Bit Mode (sd8_bit_mode): This bit selects the data width of the HC. The HD shall select it to match the data width of the SD card.
4:3	00b RW	DMA Select (dma_sel): One of supported DMA modes can be selected. The host driver shall check support of DMA modes by referring the Capabilities register. Use of selected DMA is determined by DMA Enable of the Transfer Mode register. 00 = SDMA is selected 01 = Reserved (New assignment is not allowed) 10 = 32-bit Address ADMA2 is selected 11 = Reserved (will be modified by Version 4.00)
2	0b RW	High Speed Enable (hi_spd_en): This bit is optional. Before setting this bit, the Host Driver shall check the High Speed Support in the Capabilities register. If this bit is set to 0 (default), the Host Controller outputs CMD line and DAT lines at the falling edge of the SD Clock (up to 25MHz). If this bit is set to 1, the Host Controller outputs CMD line and DAT lines at the rising edge of the SD Clock (up to 50MHz). If Preset Value Enable in the Host Control 2 register is set to 1, Host Driver needs to reset SD Clock Enable before changing this field to avoid generating clock glitches. After setting this field, the Host Driver sets SD Clock Enable again. 1 = 4-bit mode 0 = 1-bit mode
1	0b RW	Data Transfer Width (data_tx_wid): Reserved.
0	0b RW	LED Control (led_ctl): This bit selects the data width of the Host Controller. The Host Driver shall set it to match the data width of the SD card. 1 = 4-bit mode 0 = 1-bit mode

16.8.14 Power Control Register (PWR_CTL)—Offset 29h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 29h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd		sd_bus_pwr
		sd_bus_volt_sel
		hw_rst

Bit Range	Default & Access	Field Name (ID): Description
7:5	0h RO	Rsvd (rsvd): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	HW Reset (hw_rst): Reserved.
3:1	0h RW	SD Bus Voltage Select (sd_bus_volt_sel): By setting these bits, the Host Driver selects the voltage level for the SD card. Before setting this register, the Host Driver shall check the Voltage Support bits in the Capabilities register. If an unsupported voltage is selected, the Host System shall not supply SD Bus voltage. 111b = 3.3V (Typ.) 110b = 3.0V (Typ.) 101b = 1.8V (Typ.) 100b 000b Reserved
0	0b RW	SD Bus Power (sd_bus_pwr): Before setting this bit, the SD Host Driver shall set SD Bus Voltage Select. If the Host Controller detects the No Card state, this bit shall be cleared. If this bit is cleared, the Host Controller shall immediately stop driving CMD and DAT[3:0] (tri-state) and drive SDCLK to low level (Refer to Section 2.2.14) For SD Controller, this bit controls the bus voltage to SDMMC3. For SDIO Controller, power to SDIO device on SDMMC2 is not controlled by this bit. GPIO register and pin can be used to controller the SDIO device power. For eMMC Controller, power to eMMC device on SDMMC1 is not controlled by this bit. GPIO register and pin or alternative solutions can be used. 1 = Power on 0 = Power off

16.8.15 Block Gap Control Register (_BLK_GAP_CTL)—Offset 2Ah

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Ah

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd	drive_ccsd	int_blk_gap
		rd_wait_ctl
		cont_req
		stp_blk_gap_req

Bit Range	Default & Access	Field Name (ID): Description
7:5	0h RO	Reserved (rsvd): Reserved.
4	0b RW	DRIVE_CCSD (drive_ccsd): If the driver set this bit (change from ???0??? to ???1???), Host controller will send command completion.

Bit Range	Default & Access	Field Name (ID): Description
3	0b RW	Interrupt at Block Gap (int_blk_gap): This bit is valid only in 4-bit mode of the SDIO card and selects a sample point in the interrupt cycle. Setting to 1 enables interrupt detection at the block gap for a multiple block transfer. Setting to 0 disables interrupt detection during a multiple block transfer. If the SD card cannot signal an interrupt during a multiple block transfer, this bit should be set to 0. When the Host Driver detects an SD card insertion, it shall set this bit according to the CCCR of the SDIO card. 1 = Enabled 0 = Disabled
2	0b RW	Read Wait Control (rd_wait_ctl): The read wait function is optional for SDIO cards. If the card supports read wait, set this bit to enable use of the read wait protocol to stop read data using the DAT[2] line. Otherwise, the Host Controller has to stop the SD Clock to hold read data, which restricts commands generation. When the Host Driver detects an SD card insertion, it shall set this bit according to the CCCR of the SDIO card. If the card does not support read wait, this bit shall never be set to 1, otherwise DAT line conflict may occur. If this bit is set to 0, Suspend/Resume cannot be supported. 1 = Enable Read Wait Control 0 = Disable Read Wait Control
1	0b RW	Continue Request (cont_req): This bit is used to restart a transaction, which was stopped using the Stop At Block Gap Request. To cancel stop at the block gap, set Stop At Block Gap Request to 0 and set this bit 1 to restart the transfer. The Host Controller automatically clears this bit in either of the following cases: - In the case of a read transaction, the DAT Line Active changes from 0 to 1 as a read transaction restarts. - In the case of a write transaction, the Write Transfer Active changes from 0 to 1 as the write transaction restarts. Therefore, it is not necessary for Host Driver to set this bit to 0. If Stop At Block Gap Request is set to 1, any write to this bit is ignored. 1 = Restart 0 = Not affect
0	0b RW	Stop at Block Gap Request (stp_blk_gap_req): This bit is used to stop executing read and write transaction at the next block gap for non-DMA, SDMA and ADMA transfers. The Host Driver shall leave this bit set Copyright 2002-2011 SD Association SD Host Controller Simplified Specification Version 3.00 44 to 1 until the Transfer Complete is set to 1. Clearing both Stop At Block Gap Request and Continue Request shall not cause the transaction to restart. When Host Controller version is 1.00, the Host Driver can set this bit if the card supports Read Wait Control. When Host Controller version is 2.00 or later, the Host Driver can set this bit regardless of the card supports Read Wait Control. The Host Controller shall stop read transfer by using Read Wait or stopping SD clock. In case of write transfers in which the Host Driver writes data to the Buffer Data Port register, the Host Driver shall set this bit after all block data is written. If this bit is set to 1, the Host Driver shall not write data to Buffer Data Port register. This bit affects Read Transfer Active, Write Transfer Active, DAT Line Active and Command Inhibit (DAT) in the Present State register. Regarding detailed control of bits D01 and D00, refer to Section 3.8 and 3.12. 1 = Stop 0 = Transfer

16.8.16 Wakeup Control Register (WAKEUP_CTL)—Offset 2Bh

This register is mandatory for the Host Controller, but wakeup functionality depends on the Host Controller system hardware and software. The Host Driver shall maintain voltage on the SD Bus, by setting SD Bus Power to 1 in the Power Control register, when wakeup event via Card Interrupt is desired. Wakeup Event is not supported by Host Controller. Sideband wake via GPIO pin and register shall be used instead. During RTD3, GPIO register is readable and GPIO signal is routed to APIC.

Access Method



Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Bh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd		wakeup_en_sd_rm
		wakeup_en_sd_ins
		wakeup_en_crd_int

Bit Range	Default & Access	Field Name (ID): Description
7:3	0h RO	Reserved (rsvd): Reserved.
2	0b RW	Wakeup Event Enable On SD Card Removal (wakeup_en_sd_rm): This bit enables wakeup event via Card Removal assertion in the Normal Interrupt Status register. FN_WUS (Wake Up Support) in CIS does not affect this bit. 1 = Enable 0 = Disable
1	0b RW	Wakeup Event Enable On SD Card Insertion (wakeup_en_sd_ins): This bit enables wakeup event via Card Insertion assertion in the Normal Interrupt Status register. FN_WUS (Wake Up Support) in CIS does not affect this bit. 1 = Enable 0 = Disable
0	0b RW	Wakeup Event Enable On Card Interrupt (wakeup_en_crd_int): This bit enables wakeup event via Card Interrupt assertion in the Normal Interrupt Status register. This bit can be set to 1 if FN_WUS (Wake Up Support) in CIS is set to 1. 1 = Enable 0 = Disable

16.8.17 Clock Control Register (CLK_CTL)—Offset 2Ch

At the initialization of the Host Controller, the Host Driver shall set the SDCLK Frequency Select according to the Capabilities register.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
sdclk_freq_sel				upper_sdclk_freq_sel
				rsvd
				sd_clk_en
				int_clk_stable
				int_clk_en

Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RW	SDCLK Frequency Select (sdclk_freq_sel): This register is used to select the frequency of the SDCLK pin. The definition of this field is dependent on the Host Controller Version. (1) 8-bit Divided Clock Mode This mode is supported by the Host Controller Version 1.00 and 2.00. The frequency is not programmed directly, rather, this register holds the divisor of the Base Clock Frequency For SD Clock in the capabilities register. Only the following settings are allowed. (1) 8-bit Divided Clock Mode • 80h = base clock divided by 256 • 40h = base clock divided by 128 • 20h = base clock divided by 64 • 10h = base clock divided by 32 • 08h = base clock divided by 16 • 04h = base clock divided by 8 • 02h = base clock divided by 4 • 01h = base clock divided by 2 • 00h = base clock(10MHz and up) Setting 00h specifies the highest frequency of the SD Clock. When setting multiple bits, the most significant bit is used as the divisor, but it should not be set. The three default divider values can be calculated by the frequency that is defined by the Base Clock Frequency For SD Clock in the Capabilities register. • 400KHz divider value • 25MHz divider value • 50MHz divider value According to the Physical Layer Specification, the maximum SD Clock frequency is 25 MHz in normal speed mode and 50MHz in high speed mode, and shall never exceed this limit. The frequency of the SDCLK is set by the following formula: Clock Frequency = (Base Clock) / divisor Thus, choose the smallest possible divisor which results in a clock frequency that is less than or equal to the target frequency. For example, if the Base Clock Frequency For SD Clock in the Capabilities register has the value 33MHz, and the target frequency is 25MHz, then choosing the divisor value of 01h will yield 16.5MHz, which is the nearest frequency less than or equal to the target. Similarly, to approach a clock value of 400KHz, the divisor value of 40h yields the optimal clock value of 258KHz. (2) 10-bit Divided Clock Mode Host Controller Version 3.00 supports this mandatory mode instead of the 8-bit Divided Clock Mode. The length of divider is extended to 10 bits, and all divider values shall be supported. • 3FFh = 1/2046 Divided Clock • N = 1/2N Divided Clock (Duty 50%) • 002h = 1/4 Divided Clock • 001h = 1/2 Divided Clock • 000h = Base Clock (10MHz and up) • 3FFh = Base Clock * M / 1024 • = Base Clock * M / N • N - 1 = Base Clock * M / N • = Base Clock * M / 3 • 002h = Base Clock * M / 3 • 001h = Base Clock * M / 2 • 000h = Base Clock * M This field depends on setting of Preset Value Enable in the Host Control 2 register. If Preset Value Enable = 0, this field is set by Host Driver. If the Preset Value Enable = 1, this field is automatically set to a value specified in one of Preset Value registers.



Bit Range	Default & Access	Field Name (ID): Description
7:6	0h RO	Upper Bits of SDCLK Frequency Select (upper_sdclk_freq_sel): Host Controller Versions 1.00 and 2.00 do not support these bits and they are treated as 00b fixed value (ROC). Host Controller Version 3.00 shall support these bits to expand SDCLK Frequency Select to 10-bit. Bit 07-06 is assigned to bit 09-08 of clock divider in SDCLK Frequency Select.
5:3	0h RO	Rsvd (rsvd): Reserved.
2	0b RW	SD Clock Enable (sd_clk_en): The Host Controller shall stop SDCLK when writing this bit to 0. SDCLK Frequency Select can be changed when this bit is 0. Then, the Host Controller shall maintain the same clock frequency until SDCLK is stopped (Stop at SDCLK=0). If the Card Inserted in the Present State register is cleared, this bit shall be cleared. 1 = Enable 0 = Disable
1	0b RO	Internal Clock Stable (int_clk_stable): This bit is set to 1 when SD clock is stable after writing to Internal Clock Enable in this register to 1. The SD Host Driver shall wait to set SD Clock Enable until this bit is set to 1. Note: This is useful when using PLL for a clock oscillator that requires setup time. 1 = Ready 0 = Not Ready
0	0b RW	Internal Clock Enable (int_clk_en): This bit is set to 0 when the Host Driver is not using the Host Controller, or when the Host Controller awaits a wakeup event. The Host Controller should stop its internal clock to go to a very low power state. Still, registers shall be able to be read and written. Clock starts to oscillate when this bit is set to 1. When clock oscillation is stable, the Host Controller shall set Internal Clock Stable in this register to 1. This bit shall not affect card detection. 1 = Oscillate 0 = Stop

16.8.18 Timeout Control Register (TIMEOUT_CTL)—Offset 2Eh

At the initialization of the Host Controller, the Host Driver shall set the Data Timeout Counter Value according to the Capabilities register.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Eh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00h

7		4		0
0	0	0	0	0
reserved				data_timeout_cnt_val



Bit Range	Default & Access	Field Name (ID): Description
7:4	0h RO	Rsvd (reserved): Reserved.
3:0	0h RW	Data Timeout Counter Value (data_timeout_cnt_val): This value determines the interval by which DAT line timeouts are detected. For more information about timeout generation, refer to the Data Timeout Error in the Error Interrupt Status register. Timeout clock frequency will be generated by dividing the base clock TMCLK value by this value. When setting this register, prevent inadvertent timeout events by clearing the Data Timeout Error Status Enable (in the Error Interrupt Status Enable register). 1111b Reserved 1110b = $TMCLK \times 2^{27}$ 0001b = $TMCLK \times 2^{14}$ 0000b = $TMCLK \times 2^{13}$

16.8.19 Software Reset Register (SW_RST)—Offset 2Fh

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Fh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
rsvd				sw_rst_dat_in		sw_rst_cmd_in	sw_rst_all

Bit Range	Default & Access	Field Name (ID): Description
7:3	0h RO	Reserved (rsvd): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2	0b RW	Software Reset For DAT Line (sw_rst_dat_in): Only part of data circuit is reset. DMA circuit is also reset. The following registers and bits are cleared by this bit: Buffer Data Port register • Buffer is cleared and initialized. Present State register • Buffer Read Enable • Buffer Write Enable • Read Transfer Active • Write Transfer Active • DAT Line Active • Command Inhibit (DAT) Block Gap Control register • Continue Request • Stop At Block Gap Request Normal Interrupt Status register • Buffer Read Ready • Buffer Write Ready • DMA Interrupt • Block Gap Event • Transfer Complete • 1 = Reset • 0 = Work When Auto or Dynamic Clock Gating is enabled for this controller, the Software Reset bit may require several reads before the bit clears.
1	0b RW	Software Reset For CMD Line (sw_rst_cmd_in): Only part of command circuit is reset. The following registers and bits are cleared by this bit: Present State register • Command Inhibit (CMD) Normal Interrupt Status register • Command Complete • 1 = Reset • 0 = Work When Auto or Dynamic Clock Gating is enabled for this controller, the Software Reset bit may require several reads before the bit clears.
0	0b RW	Software Reset For All (sw_rst_all): This reset affects the entire Host Controller except for the card detection circuit. Register bits of type ROC, RW, RW1C, RWAC are cleared to 0. During its initialization, the Host Driver shall set this bit to 1 to reset the Host Controller. The Host Controller shall reset this bit to 0 when Capabilities registers are valid and the Host Driver can read them. Additional use of Software Reset For All may not affect the value of the Capabilities registers. If this bit is set to 1, the host driver should issue reset command and reinitialize the SD card. • 1 = Reset • 0 = Work When Auto or Dynamic Clock Gating is enabled for this controller, the Software Reset bit may require several reads before the bit clears.

16.8.20 Normal Interrupt Status Register (NML_INT_STATUS)—Offset 30h

The Normal Interrupt Status Enable affects reads of this register, but Normal Interrupt Signal Enable does not affect these reads. An interrupt is generated when the Normal Interrupt Signal Enable is enabled and at least one of the status bits is set to 1. Writing 1 to a bit of RW1C attribute clears it; writing 0 keeps the bit unchanged. Writing 1 to a bit of ROC attribute keeps the bit unchanged. More than one status can be cleared with a single register write. The Card Interrupt is cleared when the card stops asserting the interrupt; that is, when the Card Driver services the interrupt condition.

Access Method



Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 30h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h


Default: 0000h

15	12	8	4	0
0	0	0	0	0
err_int	boot_ter_int	boot_ck_rcv	re_tune	int_c
				int_b
				int_a
				crd_int
				crd_rm
				crd_ins
				buf_rd_rdy
				buf_wr_rdy
				dma_int
				blk_gap_event
				tx_comp
				cmd_comp

Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Error Interrupt (err_int): If any of the bits in the Error Interrupt Status register are set, then this bit is set. Therefore the Host Driver can efficiently test for an error by checking this bit first. This bit is read only. 1 = Error 0 = No Error
14	0b RW/1C	BOOT_TER_INT (boot_ter_int): boot ter int
13	0b RW/1C	BOOT_ACK_RCV (boot_ck_rcv): boot ack rcv
12	0b RO	Re-Tuning Event (re_tune): This status is set if Re-Tuning Request in the Present State register changes from 0 to 1. Host Controller requests Host Driver to perform re-tuning for next data transfer. Current data transfer (not large block count) can be completed without re-tuning. 1 Re-Tuning should be performed 0 Re-Tuning is not required
11	0b RO	INT_C (int_c): This status is set if INT_C is enabled and INT_C# pin is in low level. Writing this bit to 1 does not clear this bit. It is cleared by resetting the INT_C interrupt factor. Refer to the Shared Bus Control register. 1 = INT_C is detected 0 = No interrupt is detected
10	0b RO	INT_B (int_b): This status is set if INT_B is enabled and INT_B# pin is in low level. Writing this bit to 1 does not clear this bit. It is cleared by resetting the INT_B interrupt factor. Refer to the Shared Bus Control register. 1 = INT_B is detected 0 = No interrupt is detected
9	0b RO	INT_A (int_a): This status is set if INT_A is enabled and INT_A# pin is in low level. Writing this bit to 1 does not clear this bit. It is cleared by resetting the INT_A interrupt factor. Refer to the Shared Bus Control register. 1 = INT_A is detected 0 = No interrupt is detected



Bit Range	Default & Access	Field Name (ID): Description
8	0b RO	Card Interrupt (crd_int): Writing this bit to 1 does not clear this bit. It is cleared by resetting the SD card interrupt factor. In 1-bit mode, the Host Controller shall detect the Card Interrupt without SD Clock to support wakeup. In 4-bit mode, the card interrupt signal is sampled during the interrupt cycle, so there are some sample delays between the interrupt signal from the SD card and the interrupt to the Host System. When this status has been set and the Host Driver needs to start this interrupt service, Card Interrupt Status Enable in the Normal Interrupt Status Enable register may be set to 0 in order to clear the card interrupt statuses latched in the Host Controller and to stop driving the interrupt signal to the Host System. After completion of the card interrupt service (It should reset interrupt factors in the SD card and the interrupt signal may not be asserted), set Card Interrupt Status Enable to 1 and start sampling the interrupt signal again. Interrupt detected by DAT[1] is supported when there is a card per slot. In case of shared bus, interrupt pins are used to detect interrupts. If 000b is set to Interrupt Pin Select in the Shared Bus Control register, this status is effective. Non-zero value is set to Interrupt Pin Select, INT_A, INT_B or INT_C is then used to device interrupts. 1 = Generate Card Interrupt 0 = No Card Interrupt
7	0b RW/1C	Card Removal (crd_rm): This status is set if the Card Inserted in the Present State register changes from 1 to 0. When the Host Driver writes this bit to 1 to clear this status, the status of the Card Inserted in the Present State register should be confirmed. Because the card detect state may possibly be changed when the Host Driver clear this bit and interrupt event may not be generated. 1 = Card removed 0 = Card state stable or Debouncing
6	0b RW/1C	Card Insertion (crd_ins): This status is set if the Card Inserted in the Present State register changes from 0 to 1. When the Host Driver writes this bit to 1 to clear this status, the status of the Card Inserted in the Present State register should be confirmed, because the card detect state may possibly be changed when the Host Driver clears this bit and interrupt event may not be generated. 1 Card inserted 0 Card state stable or Debouncing
5	0b RW/1C	Buffer Read Ready (buf_rd_rdy): This status is set if the Buffer Read Enable changes from 0 to 1. Refer to the Buffer Read Enable in the Present State register. While performing tuning procedure (Execute Tuning is set to 1), Buffer Read Ready is set to 1 for every CMD19 execution. 1 = Ready to read buffer 0 = Not ready to read buffer
4	0b RW/1C	Buffer Write Ready (buf_wr_rdy): This status is set if the Buffer Write Enable changes from 0 to 1. Refer to the Buffer Write Enable in the Present State register. 1 = Ready to write buffer 0 = Not ready to write buffer
3	0b RW/1C	DMA Interrupt (dma_int): This status is set if the Host Controller detects the Host SDMA Buffer boundary during transfer. Refer to the Host SDMA Buffer Boundary in the Block Size register. Other DMA interrupt factors may be added in the future. In case of ADMA, by setting Int field in the descriptor table, Host Controller generates this interrupt. Suppose that it is used for debugging. This interrupt shall not be generated after the Transfer Complete. 1 = DMA Interrupt is generated 0 = No DMA Interrupt
2	0b RW/1C	Block Gap Event (blk_gap_event): If the Stop At Block Gap Request in the Block Gap Control register is set, this bit is set when both a read / write transaction is stopped at a block gap. If Stop At Block Gap Request is not set to 1, this bit is not set to 1. (1) In the case of a Read Transaction This bit is set at the falling edge of the DAT Line Active Status, when the transaction is stopped at SD Bus timing. The Read Wait shall be supported in order to use this function. Refer to Section 3.12.3 for timing details. p1(1) In the case of a Write Transaction This bit is set at the falling edge of Write Transfer Active Status (after getting CRC status at SD Bus timing). Refer to Section 3.12.4 for more details on the sequence of events. 1 = Transaction stopped at block gap 0 = No Block Gap Event



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW/1C	Transfer Complete (tx_comp): This bit is set when a read / write transfer and a command with busy is completed. (1) In the case of a Read Transaction This bit is set at the falling edge of Read Transfer Active Status. This interrupt is generated in two cases. The first is when a data transfer is completed as specified by data length (After the last data has been read to the Host System). The second is when data has stopped at the block gap and completed the data transfer by setting the Stop At Block Gap Request in the Block Gap Control register (After valid data has been read to the Host System). Refer to Section 3.12.3 for more details on the sequence of events. (2) In the case of a Write Transaction This bit is set at the falling edge of the DAT Line Active Status. This interrupt is generated in two cases. The first is when the last data is written to the SD card as specified by data length and the busy signal released. The second is when data transfers are stopped at the block gap by setting Stop At Block Gap Request in the Block Gap Control register and data transfers completed. (After valid data is written to the SD card and the busy signal released). Refer to Section 3.12.4 for more details on the sequence of events. (3) In the case of a command with busy This bit is set when busy is de-asserted. Refer to DAT Line Active and Command Inhibit (DAT) in the Present State register. Refer to the spec for the relationship between Transfer Complete and Data Timeout Error. 1 = Command execution is completed 0 = Not complete While performing tuning procedure (Execute Tuning is set to 1), Transfer Complete is not set to 1.
0	0b RW/1C	Command Complete (cmd_comp): This bit is set when get the end bit of the command response. Auto CMD12 and Auto CMD23 consist of two responses. Command Complete is not generated by the response of CMD12 or CMD23 but generated by the response of a read/write command. Refer to Command Inhibit (CMD) in the Present State register for how to control this bit. Command Timeout Error has higher priority than Command Complete. If both bits are set to 1, it can be considered that the response was not received correctly. For a tabular description of the relationship between these two bits, refer to the description of Command Complete in the spec. 1 = Command complete 0 = No command complete

16.8.21 Error Interrupt Status Register (ERR_INT_STATUS)—Offset 32h

Signals defined in this register can be enabled by the Error Interrupt Status Enable register, but not by the Error Interrupt Signal Enable register. The interrupt is generated when the Error Interrupt Signal Enable is enabled and at least one of the statuses is set to 1. Writing to 1 clears the bit, and writing to 0 keeps the bit unchanged. More than one status can be cleared at the one register write.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 32h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0



Bit Range	Default & Access	Field Name (ID): Description
15	0b RW	Vendor Specific Error Status (vend_spec_err_status): Reserved.
14	0b RW	Boot Command Timeout Error (boot_cmd_timeout_err): Occur if the boot are access command is issued to the agent which has no permission to access the boot area.
13	0b RW	CEATA Error (ceata_err): Occurs when ATA command termination has occurred due to an error condition the device has encountered.
12	0b RW	Target Response Error (tgt_rsp_err): Occurs when detecting ERROR in m_hresp(dma transaction).
11:10	0h RO	Reserved (rsvd): Reserved.
9	0b RW	ADMA Error (adma_err): This bit is set when the Host Controller detects errors during ADMA based data transfer. The state of the ADMA at an error occurrence is saved in the ADMA Error Status Register. In addition, the Host Controller generates this Interrupt when it detects invalid descriptor data (Valid=0) at the ST_FDS state. ADMA Error State in the ADMA Error Status indicates that an error occurs in ST_FDS state. The Host Driver may find that Valid bit is not set at the error descriptor. 0 = error 1 = no error
8	0b RW	Auto CMD12 Error (cmd12_err): Auto CMD12 and Auto CMD23 use this error status. This bit is set when detecting that one of the bits D00-D04 in Auto CMD Error Status register has changed from 0 to 1. In case of Auto CMD12, this bit is set to 1, not only when the errors in Auto CMD12 occur but also when Auto CMD12 is not executed due to the previous command error. 1 = error 0 = no error
7	0b RW	Current Limit Error (cur_limit_err): By setting the SD Bus Power bit in the Power Control register, the Host Controller is requested to supply power for the SD Bus. If the Host Controller supports the Current Limit function, it can be protected from an illegal card by stopping power supply to the card in which case this bit indicates a failure status. Reading 1 means the Host Controller is not supplying power to SD card due to some failure. Reading 0 means that the Host Controller is supplying power and no error has occurred. The Host Controller may require some sampling time to detect the current limit. If the Host Controller does not support this function, this bit shall always be set to 0. 1 = power fail 0 = no error
6	0b RW	Data End Bit Error (data_end_bit_err): Occurs either when detecting 0 at the end bit position of read data which uses the DAT line or at the end bit position of the CRC Status. 1 = error 0 = no error
5	0b RW	Data CRC Error (data_crc_err): Occurs when detecting CRC error when transferring read data which uses the DAT line or when detecting the Write CRC status having a value of other than 010b.
4	0b RW	Data Timeout Error (data_timeout_err): This bit is set when detecting one of following timeout conditions. - Busy timeout for R1b,R5b type - Busy timeout after Write CRC status - Write CRC Status timeout - Read Data timeout 1 = time out 0 = no error



Bit Range	Default & Access	Field Name (ID): Description
3	0b RW	Command Index Error (cmd_index_err): This bit is set if a Command Index error occurs in the command response. 1 = error 0 = no error
2	0b RW	Command End Bit Error (cmd_end_bit_err): This bit is set when detecting that the end bit of a command response is 0. 1 = End Bit Error generated 0 = no error
1	0b RW	Command CRC Error (cmd_crc_err): Command CRC Error is generated in two cases. If a response is returned and the Command Timeout Error is set to 0 (indicating no timeout), this bit is set to 1 when detecting a CRC error in the command response. The Host Controller detects a CMD line conflict by monitoring the CMD line when a command is issued. If the Host Controller drives the CMD line to 1 level, but detects 0 level on the CMD line at the next SD clock edge, then the Host Controller shall abort the command (Stop driving CMD line) and set this bit to 1. The Command Timeout Error shall also be set to 1 to distinguish CMD line conflict (refer to tabular data in the spec. that explains the relationship between Command CRC Error and Command Timeout Error). 1 = CRC Error Generated. 0 = no error
0	0b RW	Command Timeout Error (cmd_timeout_err): This bit is set only if no response is returned within 64 SD clock cycles from the end bit of the command. If the Host Controller detects a CMD line conflict (in which case Command CRC Error shall also be set, as shown in tabular data in the spec that explains the relationship between this bit and Command CRC Error) this bit shall be set without waiting for 64 SD clock cycles, because the command will be aborted by the Host Controller. 1 = time out 0 = no Error

16.8.22 Normal Interrupt Status Enable (NRM_INT_STATUS_EN)—Offset 34h

Setting to 1 enables Interrupt Status. **Implementation Note:** The Host Controller may sample the card interrupt signal during interrupt period, and may hold its value in the flip-flop. If the **Card Interrupt Status Enable** is set to 0, the Host Controller shall clear all internal signals regarding Card Interrupt.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
fixed_0	rsvd	boot_term_int_en	boot_ack_rcv_en	crd_int_stat_en
		crd_rm_stat_en	crd_ins_stat_en	buf_rd_rdy_stat_en
		buf_wr_rdy_stat_en	dma_int_stat_en	blk_gap_event_stat_en
			tx_comp_stat_en	cmd_comp_stat_en



Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Fixed to 0 (fixed_0): The Host Driver shall control error interrupts using the Error Interrupt Status Enable register.
14:11	0h RO	Reserved (rsvd): Reserved.
10	0b RW	Boot Term Interrupt Enable (boot_term_int_en): 0 = Masked.
9	0b RW	Boot Acknowledge Receive Enable (boot_ack_rcv_en): 0 = Masked
8	0b RW	Card Interrupt Status Enable (crd_int_stat_en): If this bit is set to 0, the Host Controller shall clear interrupt request to the System. The Card Interrupt detection is stopped when this bit is cleared, and restarted when this bit is set to 1. The Host Driver may clear the Card Interrupt Status Enable before servicing the Card Interrupt, and may set this bit again after all interrupt requests from the card are cleared, to prevent inadvertent interrupts. 1 = enabled 0 = masked
7	0b RW	Card Removal Status Enable (crd_rm_stat_en): 1 = enabled 0 = masked
6	0b RW	Card Insertion Status Enable (crd_ins_stat_en): [1 = enabled 0 = masked
5	0b RW	Buffer Read Ready Status Enable (buf_rd_rdy_stat_en): 1 = enabled 0 = masked
4	0b RW	Buffer Write Ready Status Enable (buf_wr_rdy_stat_en): 1 = enabled 0 = masked
3	0b RW	DMA Interrupt Status Enable (dma_int_stat_en): 1 = enabled 0 = masked
2	0b RW	Block Gap Event Status Enable (blk_gap_event_stat_en): 1 = enabled 0 = masked
1	0b RW	Transfer Complete Status Enable (tx_comp_stat_en): 1 = enabled 0 = masked
0	0b RW	Command Complete Status Enable (cmd_comp_stat_en): 1 = enabled 0 = masked



16.8.23 Error Interrupt Status Enable Register (ERR_INT_STAT_EN)—Offset 36h

Setting to 1 enables interrupt status. **Implementation Note:** To detect CMD line conflict, the Host Driver must set both **Command Timeout Error Status Enable** and **Command CRC Error Status Enable** to 1.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 36h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15			12			8			4			0																																
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																														
rsvd0			ceata_err_en			tgt_rsp_err_en			rsvd			tune_err_stat_en			adma_err_stat_en			cmd12_err_stat_en			cur_limit_err_stat_en			data_end_bit_err_stat_en			data_crc_err_stat_en			data_timeout_err_stat_en			cmd_ind_err_stat_en			cmd_end_bit_err_stat_en			cmd_crc_err_stat_en			cmd_timeout_err_stat_en		

Bit Range	Default & Access	Field Name (ID): Description
15:14	0b RO	Rsvd0 (rsvd0): Reserved.
13	0b RW	CEATA Error Enable (ceata_err_en): 0 = masked
12	0b RW	Target Response Error Enable (tgt_rsp_err_en): 0 = masked
11	0b RO	Rsvd (rsvd): Reserved.
10	0b RW	Tuning Error Status Enable (tune_err_stat_en): 1 = enabled 0 = masked
9	0b RW	ADMA Error Status Enable (adma_err_stat_en): 1 = enabled 0 = masked
8	0b RW	Auto CMD12 Error Status Enable (cmd12_err_stat_en): 1 = enabled 0 = masked
7	0b RW	Current Limit Error Status Enable (cur_limit_err_stat_en): 1 = enabled 0 = masked
6	0b RW	Data End Bit Error Status Enable (data_end_bit_err_stat_en): 1 = enabled 0 = masked



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	Data CRC Error Status Enable (data_crc_err_stat_en): 1 = enabled 0 = masked
4	0b RW	Data Timeout Error Status Enable (data_timeout_err_stat_en): 1 = enabled 0 = masked
3	0b RW	Command Index Error Status Enable (cmd_ind_err_stat_en): 1 = enabled 0 = masked
2	0b RW	Command End Bit Error Status Enable (cmd_end_bit_err_stat_en): 1 = enabled 0 = masked
1	0b RW	Command CRC Error Status Enable (cmd_crc_err_stat_en): 1 = enabled 0 = masked
0	0b RW	Command Timeout Error Status Enable (cmd_timeout_err_stat_en): 1 = enabled 0 = masked

16.8.24 Normal Interrupt Signal Enable Register (NRM_INT_SIG_EN)—Offset 38h

This register is used to select which interrupt status is indicated to the Host System as the interrupt. These status bits all share the same 1 bit interrupt line. Setting any of these bits to 1 enables interrupt generation.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
fixed_0	rsvd	boot_term_int_sig_en	boot_ack_rcv_sig_en	crd_int_sig_en
		crd_rm_sig_en	crd_ins_sig_en	buf_rd_rdy_sig_en
		buf_wr_rdy_sig_en	dma_int_sig_en	blk_gap_event_sig_en
		tx_comp_sig_en	cmd_comp_sig_en	

Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Fixed to 0 (fixed_0): The Host Driver shall control error interrupts using the Error Interrupt Signal Enable register.
14:11	0h RO	Reserved (rsvd): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
10	0b RW	Boot Terminate Interrupt Signal Enable (boot_term_int_sig_en): 0 = masked
9	0b RW	Boot Acknowledge Receive Signal Enable (boot_ack_rcv_sig_en): 0 = masked
8	0b RW	Card Interrupt Signal Enable (crd_int_sig_en): 1 = enabled 0 = masked
7	0b RW	Card Removal Signal Enable (crd_rm_sig_en): 1 = enabled 0 = masked
6	0b RW	Card Insertion Signal Enable (crd_ins_sig_en): 1 = enabled 0 = masked
5	0b RW	Buffer Read Ready Signal Enable (buf_rd_rdy_sig_en): 1 = enabled 0 = masked
4	0b RW	Buffer Write Ready Signal Enable (buf_wr_rdy_sig_en): 1 = enabled 0 = masked
3	0b RW	DMA Interrupt Signal Enable (dma_int_sig_en): 1 = enabled 0 = masked
2	0b RW	Block Gap Event Signal Enable (blk_gap_event_sig_en): 1 = enabled 0 = masked
1	0b RW	Transfer Complete Signal Enable (tx_comp_sig_en): 1 = enabled 0 = masked
0	0b RW	Command Complete Signal Enable (cmd_comp_sig_en): 1 = enabled 0 = masked

16.8.25 Error Interrupt Signal Enable Register (ERR_INT_SIG_EN)—Offset 3Ah

This register is used to select which interrupt status is sent to the Host System as the interrupt. These status bits all share the same 1 bit interrupt line. Setting any of these bits to 1 enables interrupt generation.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 3Ah

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
rsvd0	ceata_err_sig_en	tgt_err_rsp_sig_en	rsvd	tune_err_sig
				adma_err_sig_en
				cmd12_err_sig_en
				cur_limit_err_sig_en
				data_end_bit_err_sig_en
				data_crc_err_sig_en
				data_timeout_err_stat_en
				cmd_ind_err_stat_en
				cmd_end_bit_err_stat_en
				cmd_crc_err_stat_en
				cmd_timeout_err_stat_en

Bit Range	Default & Access	Field Name (ID): Description
15:14	0b RO	Rsvd0 (rsvd0): Reserved.
13	0b RW	CEATA_Error Signal Enable (ceata_err_sig_en): 0 = masked
12	0b RW	Target Error Response Signal Enable (tgt_err_rsp_sig_en): 0 = masked
11	0b RO	Reserved (rsvd): Reserved.
10	0b RW	Tuning Error Signal Enable (tune_err_sig): 1 = enabled 0 = masked
9	0b RW	ADMA Error Signal Enable (adma_err_sig_en): 1 = enabled 0 = masked
8	0b RW	Auto CMD12 Error Signal Enable (cmd12_err_sig_en): 1 = enabled 0 = masked
7	0b RW	Current Limit Error Signal Enable (cur_limit_err_sig_en): 1 = enabled 0 = masked
6	0b RW	Data End Bit Error Signal Enable (data_end_bit_err_sig_en): 1 = enabled 0 = masked
5	0b RW	Data CRC Error Signal Enable (data_crc_err_sig_en): 1 = enabled 0 = masked
4	0b RW	Data Timeout Error Signal Enable (data_timeout_err_stat_en): 1 = enabled 0 = masked
3	0b RW	Command Index Error Signal Enable (cmd_ind_err_stat_en): 1 = enabled 0 = masked
2	0b RW	Command End Bit Error Signal Enable (cmd_end_bit_err_stat_en): 1 = enabled 0 = masked



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW	Command CRC Error Signal Enable (cmd_crc_err_stat_en): 1 = enabled 0 = masked
0	0b RW	Command Timeout Error Signal Enable (cmd_timeout_err_stat_en): 1 = enabled 0 = masked

16.8.26 Auto CMD12 Error Status Register and Host Control 2 Register (CMD12_ERR_STAT_HOST_CTRL_2)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	Preset Value (preset_value): Host Controller Version 3.00 supports this bit. As the operating SDCLK frequency and I/O driver strength depend on the Host System implementation, it is difficult to determine these parameters in the Standard Host Driver. When Preset Value Enable is set to automatic This bit enables the functions defined in the Preset Value registers. 1 = Automatic Selection by Preset Value are Enabled 0 SDCLK and Driver Strength are controlled by Host Driver If this bit is set to 0, SDCLK Frequency Select, Clock Generator Select in the Clock Control register and Driver Strength Select in Host Control 2 register are set by Host Driver. If this bit is set to 1, SDCLK Frequency Select, Clock Generator Select in the Clock Control register and Driver Strength Select in Host Control 2 register are set by Host Controller as specified in the Preset Value registers.
30	0b RW	Asynchronous Interrupt (async_int): This bit can be set to 1 if a card support asynchronous interrupt and Asynchronous Interrupt Support is set to 1 in the Capabilities register. Asynchronous interrupt is effective when DAT[1] interrupt is used in 4-bit SD mode (and zero is set to Interrupt Pin Select in the Shared Bus Control register). If this bit is set to 1, the Host Driver can stop the SDCLK during asynchronous interrupt period to save power. During this period, the Host Controller continues to deliver Card Interrupt to the host when it is asserted by the Card. Usage: It is recommended that Synchronous Interrupt mode be used for SDIO Controller by setting this be to '0'. If Asynchronous Interrupt Enable mode is used, it is required that this bit remain '0' until SD initialization sequence is complete. 1 = Enabled 0 = Disabled



Bit Range	Default & Access	Field Name (ID): Description
29:24	0b RO	RSVD0: Reserved
23	0b RW	Sampling Clock (sampling_clock): This bit is set by tuning procedure when Execute Tuning is cleared.
22	0b RW/AC	Execute Tuning (execute_tuning): This bit is set to 1 to start tuning procedure and automatically cleared when tuning procedure is completed. The result of tuning is indicated to Sampling Clock Select. Tuning procedure is aborted by writing 0. Refer to the spec for more detail about tuning procedure. 1 = Execute Tuning 0 = Not Tuned or Tuning Completed
21:20	0b RW	Driver Strength (driver_strength): Host Controller output driver in 1.8V signaling is selected by this bit.
19	0b RW	Voltage Regulator Control for I/O Cell (vl): This bit controls voltage regulator for I/O cell.
18:16	0b RW	UHS Mode Select (uhs_mode): This field is used to select one of UHS-I modes.
15:8	0h RO	Rsvd (rsvd): Reserved.
7	0b RO	Command Not Issued By Auto CMD12 Error (cmd_not_iss_cmd12_err): Reserved.
6:5	0h RO	Rsvd1 (rsvd1): Reserved
4	0b RO	Auto CMD12 Index Error (cmd12_ind_err): Reserved.
3	0b RO	Auto CMD12 End Bit Error (cmd12_end_bit_err): Reserved.
2	0b RO	Auto CMD12 CRC Error (cmd12_crc_err): Reserved.
1	0b RO	Auto CMD12 Timeout Error (cmd12_timeout_err): Reserved.
0	0b RO	Auto CMD12 Not Executed (cmd12_not_exe): Reserved.

16.8.27 Capabilities Register (CAPABILITIES)—Offset 40h

This register provides the HD with information specific to the HC implementation. The HC may implement these values as fixed or loaded from flash memory during power on initialization.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h



312824201612840																															
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0																															
capabilities																															
Bit Range		Default & Access		Field Name (ID): Description																											
31:0		0b RO		Capabilities (capabilities): Reserved.																											

16.8.28 Capabilities Register 2 (CAPABILITIES_2)—Offset 44h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h

312824201612840																															
000																															

16.8.29 Maximum Current Capabilities Register (MAX_CUR_CAP)—Offset 48h

These registers indicate maximum current capability for each voltage. The value is meaningful if Voltage Support is set in the Capabilities register. If this information is supplied by the Host System via another method, all Maximum Current Capabilities register shall be 0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	rsvd		max_cur_1p8v		max_cur_3p0v		max_cur_3p3v	

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RO	Reserved (rsvd): Reserved.
23:16	00h RO	Maximum Current for 1.8V (max_cur_1p8v): Reserved.
15:8	00h RO	Maximum Current for 3.0V (max_cur_3p0v): Reserved.
7:0	00h RO	Maximum Current for 3.3V (max_cur_3p3v): Reserved.

16.8.30 Force Event Register for Auto CMD12 Error Status (FORCE_EVENT_CMD12_ERR_STAT)—Offset 50h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
	reserved0	non_cmd12_err	reserved	cmd12_ind_err
				cmd12_end_bit_err
				cmd12_crc_err
				cmd12_timeout_err
				cmd12_not_exe

Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RO	Reserved 0 (reserved0): Reserved.
7	0b RW	Force Event for Command Not Issued By Auto CMD12 Error (non_cmd12_err): 1 = Interrupt is generated 0 = No Interrupt
6:5	00b RO	Reserved (reserved): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	Force Event for Auto CMD12 Index Error (cmd12_ind_err): 1 = Interrupt is generated 0 = No Interrupt
3	0b RW	Force Event for Auto CMD12 End Bit Error (cmd12_end_bit_err): 1 = Interrupt is generated 0 = No Interrupt
2	0b RW	Force Event for Auto CMD12 CRC Error (cmd12_crc_err): 1 = Interrupt is generated 0 = No Interrupt
1	0b RW	Force Event for Auto CMD12 Timeout Error (cmd12_timeout_err): 1 = Interrupt is generated 0 = No Interrupt
0	0b RW	Force Event for Auto CMD12 Not Executed (cmd12_not_exe): 1 = Interrupt is generated 0 = No Interrupt

16.8.31 Force Event Register for Error Interrupt Status (FORCE_EVENT_ERR_INT_STAT)—Offset 52h

Error Interrupt Status register can be written. The effect of a write to this address will be reflected in the Error Interrupt Status Register if the corresponding bit of the Error Interrupt Status Enable Register is set.

- Writing 1 : set each bit of the Error Interrupt Status Register
- Writing 0 : no effect

Note: By setting this register, the Error Interrupt can be set in the Error Interrupt Status register. In order to generate interrupt signal, both the Error Interrupt Status Enable and Error Interrupt Signal Enable shall be set.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 52h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd0	ceata_err	tgt_rsp_err	rsvd	adma_err
				cmd12_err
				cur_limit_err
				data_end_bit_err
				data_crc_err
				data_timeout_err
				cmd_ind_err
				cmd_end_bit_err
				cmd_crc_err
				cmd_timeout_err
Bit Range	Default & Access	Field Name (ID): Description		
15:14	00b RO	Reserved 0 (rsvd0): Reserved.		



Bit Range	Default & Access	Field Name (ID): Description
13	0b RW	Force Event for CEATA Error (ceata_err): Reserved.
12	0b RW	Force Event for Target Response Error (tgt_rsp_err): Reserved.
11:10	0h RO	Reserved (rsvd): Reserved.
9	0b RW	Force Event for ADMA Error (adma_err): 1 = Interrupt is generated 0 = No Interrupt
8	0b RW	Force Event for Auto CMD12 Error (cmd12_err): 1 = Interrupt is generated 0 = No Interrupt
7	0b RW	Force Event for Current Limit Error (cur_limit_err): 1 = Interrupt is generated 0 = No Interrupt
6	0b RW	Force Event for Data End Bit Error (data_end_bit_err): 1 = Interrupt is generated 0 = No Interrupt
5	0b RW	Event for Data CRC Error (data_crc_err): 1 = Interrupt is generated 0 = No Interrupt
4	0b RW	Event for Data Timeout Error (data_timeout_err): 1 = Interrupt is generated 0 = No Interrupt
3	0b RW	Force Event for Command Index Error (cmd_ind_err): 1 = Interrupt is generated 0 = No Interrupt
2	0b RW	Force Event for Command End Bit Error (cmd_end_bit_err): 1 = Interrupt is generated 0 = No Interrupt
1	0b RW	Force Event for Command CRC Error (cmd_crc_err): 1 = Interrupt is generated 0 = No Interrupt
0	0b RW	Force Event for Command Timeout Error (cmd_timeout_err): 1 = Interrupt is generated 0 = No Interrupt

16.8.32 ADMA Error Status Register (ADMA_ERR_STAT)—Offset 54h

When ADMA Error Interrupt occurs, the ADMA Error States field in this register holds the ADMA state and the ADMA System Address Register holds the address around the error descriptor. To recover from the error, the Host Driver requires the ADMA state to identify the error descriptor address as follows:

- ST_STOP: Previous location set in the ADMA System Address register is the error descriptor address
- ST_FDS: Current location set in the ADMA System Address register is the error descriptor address
- ST_CADR: This state is never set because do not generate ADMA error in this state.



- ST_TFR: Previous location set in the ADMA System Address register is the error descriptor address

The Host Controller generates the ADMA Error Interrupt when it detects invalid descriptor data (Valid=0) at the ST_FDS state. In this case, ADMA Error State indicates that an error occurs at ST_FDS state. The Host Driver may find that the Valid bit is not set in the error descriptor.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd		adma_len_mis_err
		adma_err_state

Bit Range	Default & Access	Field Name (ID): Description
7:3	0h RO	Reserved (rsvd): Reserved.
2	0b RO	ADMA Length Mismatch Error (adma_len_mis_err): This error occurs in the following 2 cases. • While Block Count Enable being set, the total data length specified by the Descriptor table is different from that specified by the Block Count and Block Length. • Total data length can not be divided by the block length. • 1 = Error • 0 = No Error
1:0	00b RO	ADMA Error State (adma_err_state): This field indicates the state of ADMA when error is occurred during ADMA data transfer. This field never indicates '10' because ADMA never stops in this state. Refer to the spec for tabular information about the relationship between this field and SYS_SDR register.

16.8.33 ADMA System Address Register (ADMA_SYS_ADDR)—Offset 58h

This register contains the physical Descriptor address used for ADMA data transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	ADMA System Address (adma_sys_addr): Reserved.

16.8.34 Boot Timeout Control (BOOT_TIMEOUT_CTRL)—Offset 70h

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Boot Data Timeout Counter Value (time_cnt_val): Reserved.

16.8.35 Debug Selection Register (DEBUG_SEL)—Offset 74h

7			4				0
0	0	0	0	0	0	0	0
			rsvd				debug_sel



Bit Range	Default & Access	Field Name (ID): Description
7:1	00h RO	Reserved (rsvd): Reserved.
0	0b WO	Debug Select (debug_sel): 1 = cmd register, interrupt status, transmitter module, ahb_iface module and clk sdcard signals are probed out. 0 = receiver module and fifo_ctrl module signals are probed out

16.8.36 Shared Bus Control Register (SHARED_BUS)—Offset E0h

This register is optional. The devices on shared bus are not intended to be controlled by the Standard Host Driver. This is because shared bus configuration depends on a host system; the devices on shared bus may be controlled by a specific driver of a host system.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + E0h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0															
0				0				0				0				0				0				0				0				0				0											
RSVD0				pwr_ctrl				RSVD1				int_pin				RSVD2				clk_pin				RSVD3				bus_width				RSVD4				num_int_pin				RSVD5				num_clk_pin			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	RSVD0: Reserved
30:24	0h RW	Back-End Power Control (pwr_ctrl): Each bit of this field controls back-end power supply for an embedded device. Host interface voltage (VDDH) is not controlled by this field. The number of devices supported is specified by Number of Clock Pins , and a maximum of 7 devices can be controlled. - D24 Back-end Power Control for Device 1 - D25 Back-end Power Control for Device 2 - D26 Back-end Power Control for Device 3 - D27 Back-end Power Control for Device 4 - D28 Back-end Power Control for Device 5 - D29 Back-end Power Control for Device 6 - D30 Back-end Power Control for Device 7 The function of each bit is defined as follows: 0 = Back-end Power is Off 1 = Back-end Power is Supplied Back-End power control is effective for embedded memory devices in the Sleep State that support the Sleep command (CMD14) to reduce power consumption and embedded SDIO devices when IOEx is set to 0.
23	0b RO	RSVD1: Reserved



Bit Range	Default & Access	Field Name (ID): Description
22:20	0h RW	Interrupt Pin Select (int_pin): Interrupt pin inputs are enabled by this field. Enable of unsupported interrupt pin is meaningless. 000b = Interrupt is detected by the Interrupt Cycle. - xx1b = INT_A is enabled - x1xb = INT_B is enabled 1xxb = INT_C is enabled
19	0b RO	RSVD2: Reserved
18:16	0h RW	Clock Pin Select (clk_pin): One of clock pin outputs is selected by this field. Selection of unsupported clock pins is meaningless. Refer to Figure 2-38 for the timing of clock outputs. 000b = Clock Pins are disabled 001b = CLK[1] is selected 010b = CLK[2] is selected ... 111b = CLK[7] is Selected
15	0b RO	RSVD3: Reserved
14:8	0h RO	Bus Width Preset (bus_width): Shared bus supports mixing of 4-bit and 8-bit bus width devices. Each bit of this field specifies the bus width for each embedded device. The number of devices supported is specified by Number of Clock Pins, and a maximum of 7 devices are supported. This field is effective when multiple devices are connected to a shared bus (Slot Type is set to 10b in the Capabilities register). In the other case, Extended Data Transfer Width in the Host Control 1 register is used to select 8-bit bus width. As use of 1-bit mode is not intended for shared bus, Data Transfer Width in the Host Control 1 register should be set to 1. - D24 = Bus width preset for Device 1 - D25 = Bus width preset for Device 2 - D26 = Bus width preset for Device 3 - D27 = Bus width preset for Device 4 - D28 = Bus width preset for Device 5 - D29 = Bus width preset for Device 6 - D30 = Bus width preset for Device 7 The function of each bit is defined as follows: 0 = 4 bit buswidth mode 1 = 8 bit buswidth mode
7:6	0b RO	RSVD4: Reserved
5:4	0h RO	Number of Interrupt Pins (num_int_pin): This field indicates support of interrupt input pins for shared bus system. Three asynchronous interrupt pins are defined, INT_A#, INT_B# and INT_C#. Which interrupt pin is used is determined by the system. Each one is driven by open drain and then wired OR connection is possible. 00b = Interrupt Input Pin is not supported 01b = INTA is Supported 10b = INTA and INTB are supported 11b = INTA, INTB and INTC are supported
3	0b RO	RSVD5: Reserved
2:0	0h RO	Number of Clock Pins (num_clk_pin): This field indicates support of clock pins to select one of devices for shared bus system. Up to 7 clock pins can be supported. Shared bus is supported by specific system. Then the Standard Host Driver does not support control of these clock pins. 000b Shared bus is not supported 001b 1 SDCLK pin is supported 010b 2 SDCLK pins are supported ... 111b 7 SDCLK pins are supported



16.8.37 SPI Interrupt Support Register (SPI_INT_SUP)—Offset F0h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
					spi_int_support				

Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RW	SPI Interrupt Support (spi_int_support): This bit is set to indicate the assertion of interrupts in the SPI mode at any time, irrespective of the status of the card select (CS) line. If this bit is zero, then SDIO card can only assert the interrupt line in the SPI mode when the CS line is asserted.

16.8.38 Slot Interrupt Status Register (SLOT_INT_STAT)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: 0000h

15				12				8				4				0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
reserved								int_sig_slot								

Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RO	Reserved (reserved): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RO	Interrupt Signal For Each Slot (int_sig_slot): These status bits indicate the logical OR of Interrupt Signal and Wakeup Signal for each slot. A maximum of 8 slots can be defined. If one interrupt signal is associated with multiple slots, the Host Driver can know which interrupt is generated by reading these status bits. By a power on reset or by setting Software Reset For All, the interrupt signal shall be de-asserted and this status shall read 00h. • Bit 00 = Slot 1 • Bit 01 = Slot 2 • Bit 02 = Slot 3 • • Bit 07 = Slot 8

16.8.39 Host Controller Version Register (HOST_CTRL_VER)—Offset FEh

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + FEh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:18, F:0] + 10h

Default: B502h

15	12	8	4	0
1	0	1	1	0
0	1	0	1	0
0	0	0	0	0
0	0	1	0	0
vend_ver_num				spec_ver_num

Bit Range	Default & Access	Field Name (ID): Description
15:8	b5h RO	Vendor Version Number (vend_ver_num): This status is reserved for the vendor version number. The Host Driver should not use this status.
7:0	02h RO	Specification Version Number (spec_ver_num): This status indicates the Host Controller Spec. Version. The upper and lower 4-bits indicate the version. • 00h = SD Host Specification Version 1.00 • 01h = SD Host Specification Version 2.00, Including the feature of the ADMA and Test Register • 02h = SD Host Specification Version 3.00 • others = Reserved



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Device ID (DEVICEID): Device ID identifies the particular AHB device. This is tied to a strap at the top level.
15:0	0000h RO	Vendor ID (VENDORID): Vendor ID is a unique ID provided by PCI SIG which identifies the manufacturer of the device. This is tied to a strap at the top level.

16.9.2 Status and Command Register (STATUSCOMMAND)—Offset 4h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + 4h

Default: 00100000h

31				28				24				20				16				12				8				4				0																											
0				0				0				0				0				0				0				0				0																											
Reserved0				RMA				RCA				Reserved1				CAPLIST				INTR_STATUS				Reserved2				Reserved3				INTR_DISABLE				Reserved4				SERR_ENABLE				Reserved5				BME				MSE				Reserved6			

Bit Range	Default & Access	Field Name (ID): Description
31:30	0h RO	Reserved0: Reserved.
29	0h RW/1C	Received Master Abort (RMA): If the completion status received from IOSF is UR, Bridge sets this bit. S/W writes a '1' to this bit to clear it. This bit will not be set for the Fabric port. This bit is not used for the Fabric Port
28	0h RW/1C	Received Target Abort (RCA): If the completion status received from IOSF is CA, Bridge sets this bit. S/W writes a 1 to this bit to clear it. This bit will not be set for the fabric port. This bit is not used for the Fabric Port
27:21	00h RO	Reserved1: Reserved.
20	1h RO	Capabilities List (CAPLIST): Hardwired to 1. Indicates that the controller contains a capabilities pointer list. The first item is pointed to by looking at configuration offset 34h. If PM capability is not required then this bit should be tied to 0.
19	0h RO	Interrupt Status (INTR_STATUS): This bit reflects state of interrupt in the device. Only when the Interrupt Disable bit in the command register is a 0 and this Interrupt Status bit is a 1, will the device's/function's INTx# signal be asserted. Setting the Interrupt Disable bit to a 1 has no effect on the state of this bit. This bit reflects Legacy interrupt status.
18:16	0h RO	Reserved2: Reserved.
15:11	00h RO	Reserved3: Reserved.
10	0h RW	Interrupt Disable (INTR_DISABLE): Setting this bit disables INTx assertion from Bridge. The interrupt disabled is legacy INTx# interrupt; i.e., Bridge does not send Interrupt Assert message through the IOSF SideBand Channel. Reset value of this bit is 0.
9	0h RO	Reserved4: Reserved.



Type: PCI Configuration Register
(Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Class Code (CLASS_CODES): This register is read-only and is used to identify the generic function of the device and, in some cases, a specific register level programming interface. The register is broken into three byte size fields. The upper byte (at offset 0Bh) is a base class code which broadly classifies the type of function the device performs. The middle byte (at offset 0Ah) is a sub-class code which identifies more specifically the function of the device. The lower byte (at offset 09h) identifies a specific register-level programming interface (if any) so that device independent software can interact with the device. This register is tied to a strap at the top level.
7:0	00h RO	Revision ID (RID): Identifies the revision of a particular AHB device. This is tied to a strap at the top level.

16.9.4 Cache Line Size, Latency Timer, and Header Type Register (CLLATHEADERBIST)—Offset Ch

Type: PCI Configuration Register
(Size: 32 bits)

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0	MULFNDEV	HEADERTYPE	LATTIMER	CACHELINE_SIZE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	0h RO	Multifunction Device (MULFNDEV): This bit is always 0 for non-fabric ports. For fabric ports it is driven from the fabric_mult_function strap. A value of 1 indicates a multifunction device; a value of 0 indicates a single function device.
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Doesnt apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesnt apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

16.9.5 Base Address Register (BAR)—Offset 10h

Each AHB device is a single function device with only a single BAR associated with it. Bits 31:4 indicate the Base Address register. Power-up software can determine how much address space the AHB Device requires by writing a value of all 1's to the register and then reading the value back. Bridge will return 0's in all don't-care address bits, effectively specifying the address space required. Unimplemented Base Address registers are hardwired to zero. This is the Size Indicator Read only bits of the register.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR	SIZEINDICATOR	PREFETCHABLE	TYPE	MESSAGE_SPACE				

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1s.



Bit Range	Default & Access	Field Name (ID): Description
11:4	00h RO	Size Indicator (Read Only) (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0s.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this bar is not prefetchable.
2:1	0h RO	Type (TYPE): '00' indicates that the BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE): 0 Indicates that this BAR is present in the memory space.

16.9.6 Base Address Register 1 (BAR1)—Offset 14h

Memory accesses to BAR1 region access the PCI configuration space for the LPIO device. BAR1 region is always 4K. However SW accesses through BAR1 should only access the regular PCI configuration space. BAR1 memory accesses which do not access a defined PCI configuration register are treated as accesses to a reserved register.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + 14h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		
						PREFETCHABLE1		
						TYPE1		
						MESSAGE_SPACE1		

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address Register1 (BASEADDR1): This field is present if BAR1 is enabled through private config space. If this register is disabled then this is RO and always returns 0.
11:4	00h RO	Size Indicator1 (SIZEINDICATOR1): Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE1): Indicates that this bar is not prefetchable.
2:1	0h RO	Type (TYPE1): '00' indicates that the BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE1): 0 Indicates that this BAR is present in the memory space.



Type: PCI Configuration Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SUBSYSTEMID					SUBSYSTEMVENDORID			

16.9.8 Expansion ROM Base Address Register (EXPANSION_ROM_BASEADDR)—Offset 30h

Type: PCI Configuration Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSTON_ROM_BASE								

Intel Atom® Processor E3800 Product Family
Datasheet
1876



16.9.9 Capabilities Pointer Register (CAPABILITYPTR)—Offset 34h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + 34h

Default: 00000080h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.
7:0	80h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. When PM capability is disabled, this register is 00h.

16.9.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
MAX_LAT				MIN_GNT				INTLINE
				Reserved0				INTPIN

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates that the device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates that the device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to communicate to software the interrupt line that the interrupt pin is connected to.



16.9.11 Power Management Capability ID Register (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + 80h

Default: 48030001h

31				28				24				20				16				12				8				4				0							
0	1	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1									
PMESUPPORT								Reserved0								VERSION								NXTCAP								POWER_CAP							

Bit Range	Default & Access	Field Name (ID): Description
31:27	09h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. bit(11) X XXX1b - PME# can be asserted from D0 bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. bit(14) X 1XXXb - PME# can be asserted from D3hot. bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the private configuration space PME_Support XORed with the PME_Support strap.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.

16.9.12 Power Management Control and Status Register (PMECTRLSTATUS)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0					PMESTATUS	Reserved1		PMEEENABLE
								Reserved2
								NO_SOFT_RESET
								Reserved3
								POWERSTATE



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit in this register.
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.
3	1h RO	No Soft Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for upstream decode on fabric ports.

16.9.13 General Purpose Read Write Register1 (GEN_REGRW1)—Offset A0h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + A0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

GEN_REG_RW1

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	GEN_REG_RW1: capabilities over-ride for the sd/sdio/emmc host controller (bits 31:0)



16.9.14 General Purpose Read Write Register2 (GEN_REGRW2)—Offset A4h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + A4h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
CAP_REG_SEL	GEN_REG_RW2							

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	CAP_REG_SEL: select if the capability will come from the GEN PCI register or from a hard wire
30:0	0h RW	GEN_REG_RW2: capabilities over-ride for the sd/sdio/emmc host controller (bits 62:32)

16.9.15 General Purpose Read Write Register3 (GEN_REGRW3)—Offset A8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + A8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
GEN_REG_RW3								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	GEN_REG_RW3: Reserved.

16.9.16 General Purpose Read Write Register4 (GEN_REGRW4)—Offset ACh

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:23, F:0] + ACh



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



16.10 eMMC 4.5 Memory Mapped IO Registers

Table 189. Summary of eMMC 4.5 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"SDMA System Address / Argument 2 Register (SYS_ADR)—Offset 0h" on page 1884	00000000h
4–5h	2	"Block Size Register (BLK_SIZE)—Offset 4h" on page 1885	0000h
6–7h	2	"Block Count Register (BLK_COUNT)—Offset 6h" on page 1886	0000h
8–Bh	4	"Argument 1 Register (ARGUMENT)—Offset 8h" on page 1887	00000000h
C–Dh	2	"Transfer Mode Register (TX_MODE)—Offset Ch" on page 1887	0000h
E–Fh	2	"Command Register (CMD)—Offset Eh" on page 1889	0000h
10–13h	4	"Response Register 0 (RESPONSE0)—Offset 10h" on page 1890	00000000h
14–17h	4	"Response Register 2 (RESPONSE2)—Offset 14h" on page 1891	00000000h
18–1Bh	4	"Response Register 4 (RESPONSE4)—Offset 18h" on page 1891	00000000h
1C–1Fh	4	"Response Register 6 (RESPONSE6)—Offset 1Ch" on page 1892	00000000h
20–23h	4	"Buffer Data Port Register (BUF_DATA_PORT)—Offset 20h" on page 1892	00000000h
24–27h	4	"Present State Register (PRE_STATE)—Offset 24h" on page 1893	1FFF0000h
28–28h	1	"Host Control 1 Register (HOST_CTL)—Offset 28h" on page 1896	00h
29–29h	1	"Power Control Register (PWR_CTL)—Offset 29h" on page 1897	00h
2A–2Ah	1	"Block Gap Control Register (_BLK_GAP_CTL)—Offset 2Ah" on page 1898	00h
2B–2Bh	1	"Wakeup Control Register (WAKEUP_CTL)—Offset 2Bh" on page 1899	00h
2C–2Dh	2	"Clock Control Register (CLK_CTL)—Offset 2Ch" on page 1900	0000h
2E–2Eh	1	"Timeout Control Register (TIMEOUT_CTL)—Offset 2Eh" on page 1902	00h
2F–2Fh	1	"Software Reset Register (SW_RST)—Offset 2Fh" on page 1903	00h
30–31h	2	"Normal Interrupt Status Register (NML_INT_STATUS)—Offset 30h" on page 1904	0000h
32–33h	2	"Error Interrupt Status Register (ERR_INT_STATUS)—Offset 32h" on page 1907	0000h
34–35h	2	"Normal Interrupt Status Enable (NRM_INT_STATUS_EN)—Offset 34h" on page 1909	0000h
36–37h	2	"Error Interrupt Status Enable Register (ERR_INT_STAT_EN)—Offset 36h" on page 1911	0000h
38–39h	2	"Normal Interrupt Signal Enable Register (NRM_INT_SIG_EN)—Offset 38h" on page 1912	0000h
3A–3Bh	2	"Error Interrupt Signal Enable Register (ERR_INT_SIG_EN)—Offset 3Ah" on page 1913	0000h
3C–3Fh	4	"Auto CMD12 Error Status Register and Host Control 2 Register (CMD12_ERR_STAT_HOST_CTRL_2)—Offset 3Ch" on page 1915	00000000h
40–43h	4	"Capabilities Register (CAPABILITIES)—Offset 40h" on page 1916	00000000h
44–47h	4	"Capabilities Register 2 (CAPABILITIES_2)—Offset 44h" on page 1917	00000000h
48–4Bh	4	"Maximum Current Capabilities Register (MAX_CUR_CAP)—Offset 48h" on page 1917	00000000h
50–51h	2	"Force Event Register for Auto CMD12 Error Status (FORCE_EVENT_CMD12_ERR_STAT)—Offset 50h" on page 1918	0000h



16.10.1 SDMA System Address / Argument 2 Register (SYS_ADR)—Offset 0h

Access Method

Offset: [BAR] + 0h

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	SDMA System Address (sys_adr): (1) SDMA System Address This register contains the system memory address for a SDMA transfer. When the Host Controller stops a SDMA transfer, this register shall point to the system address of the next contiguous data position. It can be accessed only if no transaction is executing (i.e., after a transaction has stopped). Read operations during transfers may return an invalid value. The Host Driver shall initialize this register before starting a SDMA transaction. After SDMA has stopped, the next system address of the next contiguous data position can be read from this register. The SDMA transfer waits at each boundary specified by the Host SDMA Buffer Boundary in the Block Size register. The Host Controller generates a DMA Interrupt to request the Host Driver to update this register. The Host Driver sets the next system address of the next data position to this register. When the uppermost byte of this register (003h) is written, the Host Controller restarts the SDMA transfer. When restarting SDMA by the Resume command or by setting Continue Request in the Block Gap Control register, the Host Controller shall start at the next contiguous address stored here in the SDMA System Address register. ADMA does not use this register. (2) Argument 2 This register is used with the Auto CMD23 to set a 32-bit block count value to the argument of the CMD23 while executing Auto CMD23. If Auto CMD23 is used with ADMA, the full 32-bit block count value can be used. If Auto CMD23 is used without ADMA, the available block count value is limited by the Block Count register. 65535 blocks is the maximum value in this case.

16.10.2 Block Size Register (BLK_SIZE)—Offset 4h

This register is used to configure the number of bytes in a data block.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
tx_blk_size_12	boundary	tr_blk_size		

Bit Range	Default & Access	Field Name (ID): Description
15	0b RW	TX_BLK_SIZE_12 (tx_blk_size_12): Transfer Block Size 12th bit. This bit is added to support 4Kb Data block transfer.



Bit Range	Default & Access	Field Name (ID): Description
15:0	0000h RW	Blocks Count For Current Transfer (blk_count): This register is enabled when Block Count Enable in the Transfer Mode register is set to 1, and is valid only for multiple block transfers. The Host Driver shall set this register to a value between 1 and the maximum block count. The HC decrements the block count after each block transfer, and stops when the count reaches zero. Setting the block count to 0 results in no data blocks being transferred. This register should be accessed only when no transaction is executing (i.e., after transactions are stopped). During data transfer, read operations on this register may return an invalid value and write operations are ignored. When saving transfer context as a result of a Suspend command, the number of blocks yet to be transferred can be determined by reading this register. When restoring transfer context prior to issuing a Resume command, the HD shall restore the previously saved block count. 0000h = Stop Count 0001h = 1 block 0002h = 2 blocks ... - FFFFh = 65535 blocks

16.10.4 Argument 1 Register (ARGUMENT)—Offset 8h

This register contains the SD Command Argument.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

argument

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Command Argument 1 (argument): The SD Command Argument is specified as bit39-8 of Command-Format in the Physical Layer Specification.

16.10.5 Transfer Mode Register (TX_MODE)—Offset Ch

This register is used to control the operation of data transfers. The Host Driver shall set this register before issuing a command which transfers data (Refer to Data Present Select in the Command register), or before issuing a Resume command. The Host Driver shall save the value of this register when the data transfer is suspended (as a result of a Suspend command) and restore it before issuing a Resume command. To prevent data loss, the Host Controller shall implement write protection for this register during data transactions. Writes to this register shall be ignored when the Command Inhibit (DAT) in the Present State register is 1.

Access Method



Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd		boot_en	spi_mode	cmd_comp_ata
		blk_sel	data_tr_dir	auto_cmd_en
			blk_count_en	dma_en

Bit Range	Default & Access	Field Name (ID): Description
15:9	00h RO	Reserved (rsvd): Reserved.
8	0b RW	BOOT_EN (boot_en): To start boot operation for MMC4.3 1 - To start boot mode 0 - Stop the boot read
7	0b RW	SPI_MODE (spi_mode): SPI mode enable bit. 1 - SPI mode 0 - SD mode
6	0b RW	CMD_COMP_ATA (cmd_comp_ata): Command Completion Signal Enable for CE-ATA Device. ???1??? - Device will send command completion Signal ???0??? - Device will not send command completion Signal
5	0b RW	BLK_SEL (blk_sel): Multi / Single Block Select This bit is set when issuing multiple-block transfer commands using DAT line. For any other commands, this bit shall be set to 0. If this bit is 0, it is not necessary to set the Block Count register. (Refer to Table 2-8) 1 Multiple Block 0 Single Block
4	0b RW	Data Transfer Direction Select (data_tr_dir): This bit defines the direction of DAT line data transfers. The bit is set to 1 by the Host Driver to transfer data from the SD card to the SD Host Controller, and it is set to 0 for all other commands. 1 = Read (Card to Host) 0 = Write (Host to Card)
3:2	0b RW	AUTO_CMD_EN (auto_cmd_en): This field determines use of auto command functions 00b - Auto Command Disabled 01b - Auto CMD12 Enable 10b - Auto CMD23 Enable 11b - Reserved
1	0b RW	Block Count Enable (blk_count_en): This bit is used to enable the Block Count register, which is only relevant for multiple block transfers. When this bit is 0, the Block Count register is disabled, which is useful in executing an infinite transfer. (Refer to Table 2-8). If ADMA2 data transfer is more than 65535 blocks, this bit shall be set to 0. In this case, data transfer length is designated by Descriptor Table. 1 = Enable 0 = Disable
0	0b RW	DMA Enable (dma_en): This bit enables DMA functionality as described in section 1.4. DMA can be enabled only if it is supported as indicated in the Capabilities register. One of the DMA modes can be selected by DMA Select in the Host Control register. If DMA is not supported, this bit is meaningless and shall always read 0. If this bit is set to 1, a DMA operation shall begin when the Host Driver writes to the upper byte of Command register (00Fh). 1 = DMA Data transfer 0 = No data transfer or Non DMA data transfer



16.10.6 Command Register (CMD)—Offset Eh

The Host Driver shall check the Command Inhibit (DAT) bit and Command Inhibit (CMD) bit in the Present State register before writing to this register. Writing to the upper byte of this register triggers SD command generation. The Host Driver has the responsibility to write this register because the Host Controller does not protect for writing when Command Inhibit (CMD) is set.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + Eh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd	cmd_index	cmd_type	data_pr_sel	cmd_index_chk_en
			cmd_crc_chk_en	reserved
				resp_type_sel

Bit Range	Default & Access	Field Name (ID): Description
15:14	0h RO	Rsvd (rsvd): Reserved.
13:8	0h RW	Command Index (cmd_index): These bits shall be set to the command number (CMD0-63, ACMD0-63) that is specified in bits 45-40 of the Command-Format in the Physical Layer Specification and SDIO Card Specification.
7:6	00b RW	Command Type (cmd_type): There are three types of special commands: Suspend, Resume and Abort. These bits shall be set to 00b for all other commands. (1) Suspend Command If the Suspend command succeeds, the Host Controller shall assume the SD Bus has been released and that it is possible to issue the next command, which uses the DAT line. The Host Controller shall de-assert Read Wait for read transactions and stop checking busy for write transactions. The interrupt cycle shall start, in 4-bit mode. If the Suspend command fails, the Host Controller shall maintain its current state, and the Host Driver shall restart the transfer by setting Continue Request in the Block Gap Control register. (Refer to 3.12.1 Suspend Sequence). (2) Resume Command The Host Driver re-starts the data transfer by restoring the registers in the range of 000-00Dh. (Refer to Figure 1-4 in section 1.6 for the register map.) The Host Controller shall check for busy before starting write transfers. (3) Abort Command If this command is set when executing a read transfer, the Host Controller shall stop reads to the buffer. If this command is set when executing a write transfer, the Host Controller shall stop driving the DAT line. After issuing the Abort command, the Host Driver should issue a software reset. (Refer to 3.8 Abort Transaction). 11b = Abort -- CMD12, CMD52 for writing 'I/O Abort' in CCCR 10b = Resume -- CMD52 for writing 'Function Select' in CCCR 01b = Suspend -- CMD52 for writing 'Bus Suspend' in CCCR 00b = Normal -- Other commands
5	0b RW	Data Present Select (data_pr_sel): This bit is set to 1 to indicate that data is present and shall be transferred using the DAT line. It is set to 0 for the following: (1) Commands using only CMD line (ex. CMD52). (2) Commands with no data transfer but using busy signal on DAT[0] line (R1b or R5b ex. CMD38). (3) Resume command. 1 = Data Present 0 = No Data Present



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	Command Index Check Enable (cmd_index_chk_en): If this bit is set to 1, the Host Controller shall check the Index field in the response to see if it has the same value as the command index. If it is not, it is reported as a Command Index Error. If this bit is set to 0, the Index field is not checked. 1 = Enable 0 = Disable
3	0b RW	Command CRC Check Enable (cmd_crc_chk_en): If this bit is set to 1, the Host Controller shall check the CRC field in the response. If an error is detected, it is reported as a Command CRC Error. If this bit is set to 0, the CRC field is not checked. The position of CRC field is determined according to the length of the response. (Refer to definition in D01-00 and Table 2-10 below.) 1 = Enable 0 = Disable
2	0b RO	Reserved (reserved): Reserved.
1:0	0h RW	Response Type Select (resp_type_sel): 00 = No Response 01 = Response Length 136 10 = Response Length 48 11 = Response Length 48 check Busy after response

16.10.7 Response Register 0 (RESPONSE0)—Offset 10h

This register is used to store responses from SD cards.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 10h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

cmd_resp

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RO	Command Response (cmd_resp): The Table 2-12 describes the mapping of command responses from the SD Bus to this register for each response type. In the table, R[] refers to a bit range within the response data as transmitted on the SD Bus, REP[] refers to a bit range within the Response register



16.10.10 Response Register 6 (RESPONSE6)—Offset 1Ch

This register is used to store responses from SD cards.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RO	Command Response (cmd_resp): The Table 2-12 describes the mapping of command responses from the SD Bus to this register for each response type. In the table, R[] refers to a bit range within the response data as transmitted on the SD Bus, REP[] refers to a bit range within the Response register

16.10.11 Buffer Data Port Register (BUF_DATA_PORT)—Offset 20h

32-bit data port register to access internal buffer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 20h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Buffer Data (buf_data): The Host Controller buffer can be accessed through this 32-bit Data Port register. Refer to section 1.7.



Bit Range	Default & Access	Field Name (ID): Description
16	1b RO	Card Inserted (crd_ins): This bit indicates whether a card has been inserted. The Host Controller shall debounce this signal so that the Host Driver will not need to wait for it to stabilize. Changing from 0 to 1 generates a Card Insertion interrupt in the Normal Interrupt Status register and changing from 1 to 0 generates a Card Removal interrupt in the Normal Interrupt Status register. The Software Reset For All in the Software Reset register shall not affect this bit. If a card is removed while its power is on and its clock is oscillating, the Host Controller shall clear SD Bus Power in the Power Control register (Refer to Section 2.2.11) and SD Clock Enable in the Clock Control register (Refer to Section 2.2.14). When this bit is changed from 1 to 0, the Host Controller shall immediately stop driving CMD and DAT[3:0] (tri-state). In addition, the Host Driver should clear the Host Controller by the Software Reset For All in Software Reset register. The card detect is active regardless of the SD Bus Power. 1 = Card Inserted 0 = Reset or Debouncing or No Card
15:12	0h RO	Reserved1 (reserved1): Reserved.
11	0b RO	Buffer Read Enable (buf_rd_en): This status is used for non-DMA read transfers. The Host Controller may implement multiple buffers to transfer data efficiently. This read only flag indicates that valid data exists in the host side buffer. If this bit is 1, readable data exists in the buffer. A change of this bit from 1 to 0 occurs when all the block data is read from the buffer. A change of this bit from 0 to 1 occurs when block data is ready in the buffer and generates the Buffer Read Ready interrupt. 1 = Read enable 0 = Read disable
10	0b RO	Buffer Write Enable (buf_wr_en): This status is used for non-DMA write transfers. The Host Controller can implement multiple buffers to transfer data efficiently. This read only flag indicates if space is available for write data. If this bit is 1, data can be written to the buffer. A change of this bit from 1 to 0 occurs when all the block data is written to the buffer. A change of this bit from 0 to 1 occurs when top of block data can be written to the buffer and generates the Buffer Write Ready interrupt. The Host Controller should neither set Buffer Write Enable nor generate Buffer Write Ready Interrupt after the last block data is written to the Buffer Data Port Register. 1 = Write enable 0 = Write disable
9	0b RO	Read Transfer Active (rd_tx_active): This status is used for detecting completion of a read transfer. Refer to Section 3.12.3 for sequence details. This bit is set to 1 for either of the following conditions: - After the end bit of the read command. - When read operation is restarted by writing a 1 to Continue Request in the Block Gap Control register. This bit is cleared to 0 for either of the following conditions: - When the last data block as specified by block length is transferred to the System. - In case of ADMA2, end of read operation is designated by Descriptor Table. - When all valid data blocks in the Host Controller have been transferred to the System and no current block transfers are being sent as a result of the Stop At Block Gap Request being set to 1. A Transfer Complete interrupt is generated when this bit changes to 0. 1 = Transferring data 0 = No valid data



Bit Range	Default & Access	Field Name (ID): Description
8	0b RO	Write Transfer Active (wr_tx_active): This status indicates a write transfer is active. If this bit is 0, it means no valid write data exists in the Host Controller. Refer to Section 3.12.4 for more details on the sequence of events. This bit is set in either of the following cases: - After the end bit of the write command. - When write operation is restarted by writing a 1 to Continue Request in the Block Gap Control register. This bit is cleared in either of the following cases: - After getting the CRC status of the last data block as specified by the transfer count (Single and Multiple) In case of ADMA2, transfer count is designated by Descriptor Table. - After getting the CRC status of any block where data transmission is about to be stopped by a Stop At Block Gap Request. During a write transaction, a Block Gap Event interrupt is generated when this bit is changed to 0, as the result of the Stop At Block Gap Request being set. This status is useful for the Host Driver in determining non DAT line commands can be issued during write busy. 1 Transferring data 0 No valid data
7:3	00h RO	Reserved (reserved): Reserved.
2	0b RO	DAT Line Active (dat_ln_active): This bit indicates whether one of the DAT lines on SD Bus is in use. (a) In the case of read transactions This status indicates whether a read transfer is executing on the SD Bus. Changing this value from 1 to 0 generates a Block Gap Event interrupt in the Normal Interrupt Status register, as the result of the Stop At Block Gap Request being set. Refer to Section 3.12.3 for details on timing. This bit shall be set in either of the following cases: - After the end bit of the read command. - When writing a 1 to Continue Request in the Block Gap Control register to restart a read transfer. This bit shall be cleared in either of the following cases: - When the end bit of the last data block is sent from the SD Bus to the Host Controller. In case of ADMA2, the last block is designated by the last transfer of Descriptor Table. - When a read transfer is stopped at the block gap initiated by a Stop At Block Gap Request. The Host Controller shall stop read operation at the start of the interrupt cycle of the next block gap by driving Read Wait or stopping SD clock. If the Read Wait signal is already driven (due to data buffer cannot receive data), the Host Controller can continue to stop read operation by driving the Read Wait signal. It is necessary to support Read Wait in order to use suspend / resume function. (b) In the case of write transactions This status indicates that a write transfer is executing on the SD Bus. Changing this value from 1 to 0 generate a Transfer Complete interrupt in the Normal Interrupt Status register. Refer to Section 3.12.4 for sequence details. This bit shall be set in either of the following cases: - After the end bit of the write command. - When writing to 1 to Continue Request in the Block Gap Control register to continue a write transfer. This bit shall be cleared in either of the following cases: - When the SD card releases write busy of the last data block. If SD card does not drive busy signal for 8 SD Clocks, the Host Controller shall consider the card drive 'Not Busy'. In case of ADMA2, the last block is designated by the last transfer of Descriptor Table. - When the SD card releases write busy prior to waiting for write transfer as a result of a Stop At Block Gap Request. (c) Command with busy This status indicates whether a command indicates busy (ex. erase command for memory) is executing on the SD Bus. This bit is set after the end bit of the command with busy and cleared when busy is de-asserted. Changing this bit from 1 to 0 generate a Transfer Complete interrupt in the Normal Interrupt Status register. Refer Figure 2-11 to Figure 2-13. 1 = DAT Line Active 0 = DAT Line Inactive



Bit Range	Default & Access	Field Name (ID): Description
1	0b RO	Command Inhibit (DAT) (cmd_inhibit_dat): This status bit is generated if either the DAT Line Active or the Read Transfer Active is set to 1. If this bit is 0, it indicates the Host Controller can issue the next SD Command. Commands with busy signal belong to Command Inhibit (DAT) (ex. R1b, R5b type). Changing from 1 to 0 generates a Transfer Complete interrupt in the Normal Interrupt Status register. Note: The SD Host Driver can save registers in the range of 000-00Dh for a suspend transaction after this bit has changed from 1 to 0. 1 Cannot issue command which uses the DAT line 0 Can issue command which uses the DAT line
0	0b RO	Command Inhibit (CMD) (cmd_inhibit_cmd): Command Inhibit (CMD) If this bit is 0, it indicates the CMD line is not in use and the Host Controller can issue a SD Command using the CMD line. cleared when the command response is received. Auto CMD12 and Auto CMD23 consist of two responses. In this case, this bit is not cleared by the response of CMD12 or CMD23 but cleared by the response of a read/write command. Status issuing Auto CMD12 is not read from this bit. So if a command is issued during Auto CMD12 operation, Host Controller shall manage to issue two commands: CMD12 and a command set by Command register. Even if the Command Inhibit (DAT) is set to 1, commands using only the CMD line can be issued if this bit is 0. Changing from 1 to 0 generates a Command Complete Interrupt in the Normal Interrupt Status register. If the Host Controller cannot issue the command because of a command conflict error (Refer to Command CRC Error in Section 2.2.18) or because of Command Not Issued By Auto CMD12 Error (Refer to Section 2.2.23), this bit shall remain 1 and the Command Complete is not set. 1 Cannot issue command 0 Can issue command using only CMD line

16.10.13 Host Control 1 Register (HOST_CTL)—Offset 28h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
crd_det_sig_sel	crd_det_tst_lv	sd8_bit_mode	dma_sel	hi_spd_en	data_tx_wid	led_ctl	

Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	Card Detect Signal Selection (crd_det_sig_sel): This bit selects source for the card detection. 1 = The Card Detect Test Level is selected (for test purposes) 0 = SDCD# is selected (for normal use) When the source for the card detection is switched, the interrupt should be disabled during the switching period by clearing the Interrupt Status/Signal Enable register in order to mask unexpected interrupt being caused by the glitch. The Interrupt Status/Signal Enable should be disabled during the period of debouncing.



Bit Range	Default & Access	Field Name (ID): Description
6	0b RW	Card Detect Test Level (crd_det_tst_lvl): This bit is enabled while the Card Detect Signal Selection is set to 1, and it indicates whether or not the card is inserted. 1 = Card Inserted 0 = No Card
5	0b RW	SD8 Bit Mode (sd8_bit_mode): This bit selects the data width of the HC. The HD shall select it to match the data width of the SD card.
4:3	00b RW	DMA Select (dma_sel): One of supported DMA modes can be selected. The host driver shall check support of DMA modes by referring the Capabilities register. Use of selected DMA is determined by DMA Enable of the Transfer Mode register. 00 = SDMA is selected 01 = Reserved (New assignment is not allowed) 10 = 32-bit Address ADMA2 is selected 11 = Reserved (will be modified by Version 4.00)
2	0b RW	High Speed Enable (hi_spd_en): This bit is optional. Before setting this bit, the Host Driver shall check the High Speed Support in the Capabilities register. If this bit is set to 0 (default), the Host Controller outputs CMD line and DAT lines at the falling edge of the SD Clock (up to 25MHz). If this bit is set to 1, the Host Controller outputs CMD line and DAT lines at the rising edge of the SD Clock (up to 50MHz). If Preset Value Enable in the Host Control 2 register is set to 1, Host Driver needs to reset SD Clock Enable before changing this field to avoid generating clock glitches. After setting this field, the Host Driver sets SD Clock Enable again. 1 = 4-bit mode 0 = 1-bit mode
1	0b RW	Data Transfer Width (data_tx_wid): Reserved.
0	0b RW	LED Control (led_ctl): This bit selects the data width of the Host Controller. The Host Driver shall set it to match the data width of the SD card. 1 = 4-bit mode 0 = 1-bit mode

16.10.14 Power Control Register (PWR_CTL)—Offset 29h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 29h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd	hw_rst	sd_bus_volt_sel
		sd_bus_pwr

Bit Range	Default & Access	Field Name (ID): Description
7:5	0h RO	Rsvd (rsvd): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	HW Reset (hw_rst): Reserved.
3:1	0h RW	SD Bus Voltage Select (sd_bus_volt_sel): By setting these bits, the Host Driver selects the voltage level for the SD card. Before setting this register, the Host Driver shall check the Voltage Support bits in the Capabilities register. If an unsupported voltage is selected, the Host System shall not supply SD Bus voltage. 111b = 3.3V (Typ.) 110b = 3.0V (Typ.) 101b = 1.8V (Typ.) 100b 000b Reserved
0	0b RW	SD Bus Power (sd_bus_pwr): Before setting this bit, the SD Host Driver shall set SD Bus Voltage Select. If the Host Controller detects the No Card state, this bit shall be cleared. If this bit is cleared, the Host Controller shall immediately stop driving CMD and DAT[3:0] (tri-state) and drive SDCLK to low level (Refer to Section 2.2.14) For SD Controller, this bit controls the bus voltage to SDMMC3. For SDIO Controller, power to SDIO device on SDMMC2 is not controlled by this bit. GPIO register and pin can be used to controller the SDIO device power. For eMMC Controller, power to eMMC device on SDMMC1 is not controlled by this bit. GPIO register and pin or alternative solutions can be used. 1 = Power on 0 = Power off

16.10.15 Block Gap Control Register (_BLK_GAP_CTL)—Offset 2Ah

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Ah

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd	drive_ccsd	int_blk_gap
		rd_wait_ctl
		cont_req
		stp_blk_gap_req

Bit Range	Default & Access	Field Name (ID): Description
7:5	0h RO	Reserved (rsvd): Reserved.
4	0b RW	DRIVE_CCSD (drive_ccsd): If the driver set this bit (change from ???0??? to ???1???), Host controller will send command completion.

Bit Range	Default & Access	Field Name (ID): Description
3	0b RW	Interrupt at Block Gap (int_blk_gap): This bit is valid only in 4-bit mode of the SDIO card and selects a sample point in the interrupt cycle. Setting to 1 enables interrupt detection at the block gap for a multiple block transfer. Setting to 0 disables interrupt detection during a multiple block transfer. If the SD card cannot signal an interrupt during a multiple block transfer, this bit should be set to 0. When the Host Driver detects an SD card insertion, it shall set this bit according to the CCCR of the SDIO card. 1 = Enabled 0 = Disabled
2	0b RW	Read Wait Control (rd_wait_ctl): The read wait function is optional for SDIO cards. If the card supports read wait, set this bit to enable use of the read wait protocol to stop read data using the DAT[2] line. Otherwise, the Host Controller has to stop the SD Clock to hold read data, which restricts commands generation. When the Host Driver detects an SD card insertion, it shall set this bit according to the CCCR of the SDIO card. If the card does not support read wait, this bit shall never be set to 1, otherwise DAT line conflict may occur. If this bit is set to 0, Suspend/Resume cannot be supported. 1 = Enable Read Wait Control 0 = Disable Read Wait Control
1	0b RW	Continue Request (cont_req): This bit is used to restart a transaction, which was stopped using the Stop At Block Gap Request. To cancel stop at the block gap, set Stop At Block Gap Request to 0 and set this bit 1 to restart the transfer. The Host Controller automatically clears this bit in either of the following cases: - In the case of a read transaction, the DAT Line Active changes from 0 to 1 as a read transaction restarts. - In the case of a write transaction, the Write Transfer Active changes from 0 to 1 as the write transaction restarts. Therefore, it is not necessary for Host Driver to set this bit to 0. If Stop At Block Gap Request is set to 1, any write to this bit is ignored. 1 = Restart 0 = Not affect
0	0b RW	Stop at Block Gap Request (stp_blk_gap_req): This bit is used to stop executing read and write transaction at the next block gap for non-DMA, SDMA and ADMA transfers. The Host Driver shall leave this bit set Copyright 2002-2011 SD Association SD Host Controller Simplified Specification Version 3.00 44 to 1 until the Transfer Complete is set to 1. Clearing both Stop At Block Gap Request and Continue Request shall not cause the transaction to restart. When Host Controller version is 1.00, the Host Driver can set this bit if the card supports Read Wait Control. When Host Controller version is 2.00 or later, the Host Driver can set this bit regardless of the card supports Read Wait Control. The Host Controller shall stop read transfer by using Read Wait or stopping SD clock. In case of write transfers in which the Host Driver writes data to the Buffer Data Port register, the Host Driver shall set this bit after all block data is written. If this bit is set to 1, the Host Driver shall not write data to Buffer Data Port register. This bit affects Read Transfer Active, Write Transfer Active, DAT Line Active and Command Inhibit (DAT) in the Present State register. Regarding detailed control of bits D01 and D00, refer to Section 3.8 and 3.12. 1 = Stop 0 = Transfer

16.10.16 Wakeup Control Register (WAKEUP_CTL)—Offset 2Bh

This register is mandatory for the Host Controller, but wakeup functionality depends on the Host Controller system hardware and software. The Host Driver shall maintain voltage on the SD Bus, by setting SD Bus Power to 1 in the Power Control register, when wakeup event via Card Interrupt is desired. Wakeup Event is not supported by Host Controller. Sideband wake via GPIO pin and register shall be used instead. During RTD3, GPIO register is readable and GPIO signal is routed to APIC.

Access Method



Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Bh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
rsvd				wakeup_en_sd_rm		wakeup_en_sd_ins	wakeup_en_crd_int

Bit Range	Default & Access	Field Name (ID): Description
7:3	0h RO	Reserved (rsvd): Reserved.
2	0b RW	Wakeup Event Enable On SD Card Removal (wakeup_en_sd_rm): This bit enables wakeup event via Card Removal assertion in the Normal Interrupt Status register. FN_WUS (Wake Up Support) in CIS does not affect this bit. 1 = Enable 0 = Disable
1	0b RW	Wakeup Event Enable On SD Card Insertion (wakeup_en_sd_ins): This bit enables wakeup event via Card Insertion assertion in the Normal Interrupt Status register. FN_WUS (Wake Up Support) in CIS does not affect this bit. 1 = Enable 0 = Disable
0	0b RW	Wakeup Event Enable On Card Interrupt (wakeup_en_crd_int): This bit enables wakeup event via Card Interrupt assertion in the Normal Interrupt Status register. This bit can be set to 1 if FN_WUS (Wake Up Support) in CIS is set to 1. 1 = Enable 0 = Disable

16.10.17 Clock Control Register (CLK_CTL)—Offset 2Ch

At the initialization of the Host Controller, the Host Driver shall set the SDCLK Frequency Select according to the Capabilities register.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
sdclk_freq_sel				upper_sdclk_freq_sel
				rsvd
				sd_clk_en
				int_clk_stable
				int_clk_en

Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RW	SDCLK Frequency Select (sdclk_freq_sel): This register is used to select the frequency of the SDCLK pin. The definition of this field is dependent on the Host Controller Version. (1) 8-bit Divided Clock Mode This mode is supported by the Host Controller Version 1.00 and 2.00. The frequency is not programmed directly, rather, this register holds the divisor of the Base Clock Frequency For SD Clock in the capabilities register. Only the following settings are allowed. (1) 8-bit Divided Clock Mode 80h = base clock divided by 256 40h = base clock divided by 128 20h = base clock divided by 64 10h = base clock divided by 32 08h = base clock divided by 16 04h = base clock divided by 8 02h = base clock divided by 4 01h = base clock divided by 2 00h = base clock(10MHz and up) Setting 00h specifies the highest frequency of the SD Clock. When setting multiple bits, the most significant bit is used as the divisor, but it should not be set. The three default divider values can be calculated by the frequency that is defined by the Base Clock Frequency For SD Clock in the Capabilities register. 400KHz divider value 25MHz divider value 50MHz divider value According to the Physical Layer Specification, the maximum SD Clock frequency is 25 MHz in normal speed mode and 50MHz in high speed mode, and shall never exceed this limit. The frequency of the SDCLK is set by the following formula: Clock Frequency = (Base Clock) / divisor Thus, choose the smallest possible divisor which results in a clock frequency that is less than or equal to the target frequency. For example, if the Base Clock Frequency For SD Clock in the Capabilities register has the value 33MHz, and the target frequency is 25MHz, then choosing the divisor value of 01h will yield 16.5MHz, which is the nearest frequency less than or equal to the target. Similarly, to approach a clock value of 400KHz, the divisor value of 40h yields the optimal clock value of 258KHz. (2) 10-bit Divided Clock Mode Host Controller Version 3.00 supports this mandatory mode instead of the 8-bit Divided Clock Mode. The length of divider is extended to 10 bits, and all divider values shall be supported. 3FFh = 1/2046 Divided Clock - N = 1/2N Divided Clock (Duty 50%) 002h = 1/4 Divided Clock 001h = 1/2 Divided Clock 000h = Base Clock (10MHz and up) 3FFh = Base Clock * M / 1024 - N - 1 = Base Clock * M / N 002h = Base Clock * M / 3 001h = Base Clock * M / 2 000h = Base Clock * M This field depends on setting of Preset Value Enable in the Host Control 2 register. If Preset Value Enable = 0, this field is set by Host Driver. If the Preset Value Enable = 1, this field is automatically set to a value specified in one of Preset Value registers.



Bit Range	Default & Access	Field Name (ID): Description
7:6	0h RO	Upper Bits of SDCLK Frequency Select (upper_sdclk_freq_sel): Host Controller Versions 1.00 and 2.00 do not support these bits and they are treated as 00b fixed value (ROC). Host Controller Version 3.00 shall support these bits to expand SDCLK Frequency Select to 10-bit. Bit 07-06 is assigned to bit 09-08 of clock divider in SDCLK Frequency Select.
5:3	0h RO	Rsvd (rsvd): Reserved.
2	0b RW	SD Clock Enable (sd_clk_en): The Host Controller shall stop SDCLK when writing this bit to 0. SDCLK Frequency Select can be changed when this bit is 0. Then, the Host Controller shall maintain the same clock frequency until SDCLK is stopped (Stop at SDCLK=0). If the Card Inserted in the Present State register is cleared, this bit shall be cleared. 1 = Enable 0 = Disable
1	0b RO	Internal Clock Stable (int_clk_stable): This bit is set to 1 when SD clock is stable after writing to Internal Clock Enable in this register to 1. The SD Host Driver shall wait to set SD Clock Enable until this bit is set to 1. Note: This is useful when using PLL for a clock oscillator that requires setup time. 1 = Ready 0 = Not Ready
0	0b RW	Internal Clock Enable (int_clk_en): This bit is set to 0 when the Host Driver is not using the Host Controller, or when the Host Controller awaits a wakeup event. The Host Controller should stop its internal clock to go to a very low power state. Still, registers shall be able to be read and written. Clock starts to oscillate when this bit is set to 1. When clock oscillation is stable, the Host Controller shall set Internal Clock Stable in this register to 1. This bit shall not affect card detection. 1 = Oscillate 0 = Stop

16.10.18 Timeout Control Register (TIMEOUT_CTL)—Offset 2Eh

At the initialization of the Host Controller, the Host Driver shall set the Data Timeout Counter Value according to the Capabilities register.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Eh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
reserved				data_timeout_cnt_val			



Bit Range	Default & Access	Field Name (ID): Description
7:4	0h RO	Rsvd (reserved): Reserved.
3:0	0h RW	Data Timeout Counter Value (data_timeout_cnt_val): This value determines the interval by which DAT line timeouts are detected. For more information about timeout generation, refer to the Data Timeout Error in the Error Interrupt Status register. Timeout clock frequency will be generated by dividing the base clock TMCLK value by this value. When setting this register, prevent inadvertent timeout events by clearing the Data Timeout Error Status Enable (in the Error Interrupt Status Enable register). 1111b Reserved 1110b = $TMCLK \times 2^{27}$ 0001b = $TMCLK \times 2^{14}$ 0000b = $TMCLK \times 2^{13}$

16.10.19 Software Reset Register (SW_RST)—Offset 2Fh

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 2Fh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
rsvd				sw_rst_dat_in		sw_rst_cmd_in	sw_rst_all

Bit Range	Default & Access	Field Name (ID): Description
7:3	0h RO	Reserved (rsvd): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2	0b RW	Software Reset For DAT Line (sw_rst_dat_in): Only part of data circuit is reset. DMA circuit is also reset. The following registers and bits are cleared by this bit: Buffer Data Port register • Buffer is cleared and initialized. Present State register • Buffer Read Enable • Buffer Write Enable • Read Transfer Active • Write Transfer Active • DAT Line Active • Command Inhibit (DAT) Block Gap Control register • Continue Request • Stop At Block Gap Request Normal Interrupt Status register • Buffer Read Ready • Buffer Write Ready • DMA Interrupt • Block Gap Event • Transfer Complete • 1 = Reset • 0 = Work When Auto or Dynamic Clock Gating is enabled for this controller, the Software Reset bit may require several reads before the bit clears.
1	0b RW	Software Reset For CMD Line (sw_rst_cmd_in): Only part of command circuit is reset. The following registers and bits are cleared by this bit: Present State register • Command Inhibit (CMD) Normal Interrupt Status register • Command Complete • 1 = Reset • 0 = Work When Auto or Dynamic Clock Gating is enabled for this controller, the Software Reset bit may require several reads before the bit clears.
0	0b RW	Software Reset For All (sw_rst_all): This reset affects the entire Host Controller except for the card detection circuit. Register bits of type ROC, RW, RW1C, RWAC are cleared to 0. During its initialization, the Host Driver shall set this bit to 1 to reset the Host Controller. The Host Controller shall reset this bit to 0 when Capabilities registers are valid and the Host Driver can read them. Additional use of Software Reset For All may not affect the value of the Capabilities registers. If this bit is set to 1, the host driver should issue reset command and reinitialize the SD card. • 1 = Reset • 0 = Work When Auto or Dynamic Clock Gating is enabled for this controller, the Software Reset bit may require several reads before the bit clears.

16.10.20 Normal Interrupt Status Register (NML_INT_STATUS)—Offset 30h

The Normal Interrupt Status Enable affects reads of this register, but Normal Interrupt Signal Enable does not affect these reads. An interrupt is generated when the Normal Interrupt Signal Enable is enabled and at least one of the status bits is set to 1. Writing 1 to a bit of RW1C attribute clears it; writing 0 keeps the bit unchanged. Writing 1 to a bit of ROC attribute keeps the bit unchanged. More than one status can be cleared with a single register write. The Card Interrupt is cleared when the card stops asserting the interrupt; that is, when the Card Driver services the interrupt condition.

Access Method



Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 30h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h


Default: 0000h

15	12	8	4	0
0	0	0	0	0
err_int	boot_ter_int	boot_ck_rcv	re_tune	int_c
				int_b
				int_a
				crd_int
				crd_rm
				crd_ins
				buf_rd_rdy
				buf_wr_rdy
				dma_int
				blk_gap_event
				tx_comp
				cmd_comp

Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Error Interrupt (err_int): If any of the bits in the Error Interrupt Status register are set, then this bit is set. Therefore the Host Driver can efficiently test for an error by checking this bit first. This bit is read only. 1 = Error 0 = No Error
14	0b RW/1C	BOOT_TER_INT (boot_ter_int): boot ter int
13	0b RW/1C	BOOT_ACK_RCV (boot_ck_rcv): boot ack rcv
12	0b RO	Re-Tuning Event (re_tune): This status is set if Re-Tuning Request in the Present State register changes from 0 to 1. Host Controller requests Host Driver to perform re-tuning for next data transfer. Current data transfer (not large block count) can be completed without re-tuning. 1 Re-Tuning should be performed 0 Re-Tuning is not required
11	0b RO	INT_C (int_c): This status is set if INT_C is enabled and INT_C# pin is in low level. Writing this bit to 1 does not clear this bit. It is cleared by resetting the INT_C interrupt factor. Refer to the Shared Bus Control register. 1 = INT_C is detected 0 = No interrupt is detected
10	0b RO	INT_B (int_b): This status is set if INT_B is enabled and INT_B# pin is in low level. Writing this bit to 1 does not clear this bit. It is cleared by resetting the INT_B interrupt factor. Refer to the Shared Bus Control register. 1 = INT_B is detected 0 = No interrupt is detected
9	0b RO	INT_A (int_a): This status is set if INT_A is enabled and INT_A# pin is in low level. Writing this bit to 1 does not clear this bit. It is cleared by resetting the INT_A interrupt factor. Refer to the Shared Bus Control register. 1 = INT_A is detected 0 = No interrupt is detected



Bit Range	Default & Access	Field Name (ID): Description
8	0b RO	Card Interrupt (crd_int): Writing this bit to 1 does not clear this bit. It is cleared by resetting the SD card interrupt factor. In 1-bit mode, the Host Controller shall detect the Card Interrupt without SD Clock to support wakeup. In 4-bit mode, the card interrupt signal is sampled during the interrupt cycle, so there are some sample delays between the interrupt signal from the SD card and the interrupt to the Host System. When this status has been set and the Host Driver needs to start this interrupt service, Card Interrupt Status Enable in the Normal Interrupt Status Enable register may be set to 0 in order to clear the card interrupt statuses latched in the Host Controller and to stop driving the interrupt signal to the Host System. After completion of the card interrupt service (It should reset interrupt factors in the SD card and the interrupt signal may not be asserted), set Card Interrupt Status Enable to 1 and start sampling the interrupt signal again. Interrupt detected by DAT[1] is supported when there is a card per slot. In case of shared bus, interrupt pins are used to detect interrupts. If 000b is set to Interrupt Pin Select in the Shared Bus Control register, this status is effective. Non-zero value is set to Interrupt Pin Select, INT_A, INT_B or INT_C is then used to device interrupts. 1 = Generate Card Interrupt 0 = No Card Interrupt
7	0b RW/1C	Card Removal (crd_rm): This status is set if the Card Inserted in the Present State register changes from 1 to 0. When the Host Driver writes this bit to 1 to clear this status, the status of the Card Inserted in the Present State register should be confirmed. Because the card detect state may possibly be changed when the Host Driver clear this bit and interrupt event may not be generated. 1 = Card removed 0 = Card state stable or Debouncing
6	0b RW/1C	Card Insertion (crd_ins): This status is set if the Card Inserted in the Present State register changes from 0 to 1. When the Host Driver writes this bit to 1 to clear this status, the status of the Card Inserted in the Present State register should be confirmed, because the card detect state may possibly be changed when the Host Driver clears this bit and interrupt event may not be generated. 1 Card inserted 0 Card state stable or Debouncing
5	0b RW/1C	Buffer Read Ready (buf_rd_rdy): This status is set if the Buffer Read Enable changes from 0 to 1. Refer to the Buffer Read Enable in the Present State register. While performing tuning procedure (Execute Tuning is set to 1), Buffer Read Ready is set to 1 for every CMD19 execution. 1 = Ready to read buffer 0 = Not ready to read buffer
4	0b RW/1C	Buffer Write Ready (buf_wr_rdy): This status is set if the Buffer Write Enable changes from 0 to 1. Refer to the Buffer Write Enable in the Present State register. 1 = Ready to write buffer 0 = Not ready to write buffer
3	0b RW/1C	DMA Interrupt (dma_int): This status is set if the Host Controller detects the Host SDMA Buffer boundary during transfer. Refer to the Host SDMA Buffer Boundary in the Block Size register. Other DMA interrupt factors may be added in the future. In case of ADMA, by setting Int field in the descriptor table, Host Controller generates this interrupt. Suppose that it is used for debugging. This interrupt shall not be generated after the Transfer Complete. 1 = DMA Interrupt is generated 0 = No DMA Interrupt
2	0b RW/1C	Block Gap Event (blk_gap_event): If the Stop At Block Gap Request in the Block Gap Control register is set, this bit is set when both a read / write transaction is stopped at a block gap. If Stop At Block Gap Request is not set to 1, this bit is not set to 1. (1) In the case of a Read Transaction This bit is set at the falling edge of the DAT Line Active Status, when the transaction is stopped at SD Bus timing. The Read Wait shall be supported in order to use this function. Refer to Section 3.12.3 for timing details. p1(1) In the case of a Write Transaction This bit is set at the falling edge of Write Transfer Active Status (after getting CRC status at SD Bus timing). Refer to Section 3.12.4 for more details on the sequence of events. 1 = Transaction stopped at block gap 0 = No Block Gap Event



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW/1C	Transfer Complete (tx_comp): This bit is set when a read / write transfer and a command with busy is completed. (1) In the case of a Read Transaction This bit is set at the falling edge of Read Transfer Active Status. This interrupt is generated in two cases. The first is when a data transfer is completed as specified by data length (After the last data has been read to the Host System). The second is when data has stopped at the block gap and completed the data transfer by setting the Stop At Block Gap Request in the Block Gap Control register (After valid data has been read to the Host System). Refer to Section 3.12.3 for more details on the sequence of events. (2) In the case of a Write Transaction This bit is set at the falling edge of the DAT Line Active Status. This interrupt is generated in two cases. The first is when the last data is written to the SD card as specified by data length and the busy signal released. The second is when data transfers are stopped at the block gap by setting Stop At Block Gap Request in the Block Gap Control register and data transfers completed. (After valid data is written to the SD card and the busy signal released). Refer to Section 3.12.4 for more details on the sequence of events. (3) In the case of a command with busy This bit is set when busy is de-asserted. Refer to DAT Line Active and Command Inhibit (DAT) in the Present State register. Refer to the spec for the relationship between Transfer Complete and Data Timeout Error. 1 = Command execution is completed 0 = Not complete While performing tuning procedure (Execute Tuning is set to 1), Transfer Complete is not set to 1.
0	0b RW/1C	Command Complete (cmd_comp): This bit is set when get the end bit of the command response. Auto CMD12 and Auto CMD23 consist of two responses. Command Complete is not generated by the response of CMD12 or CMD23 but generated by the response of a read/write command. Refer to Command Inhibit (CMD) in the Present State register for how to control this bit. Command Timeout Error has higher priority than Command Complete. If both bits are set to 1, it can be considered that the response was not received correctly. For a tabular description of the relationship between these two bits, refer to the description of Command Complete in the spec. 1 = Command complete 0 = No command complete

16.10.21 Error Interrupt Status Register (ERR_INT_STATUS)—Offset 32h

Signals defined in this register can be enabled by the Error Interrupt Status Enable register, but not by the Error Interrupt Signal Enable register. The interrupt is generated when the Error Interrupt Signal Enable is enabled and at least one of the statuses is set to 1. Writing to 1 clears the bit, and writing to 0 keeps the bit unchanged. More than one status can be cleared at the one register write.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)


Offset: [BAR] + 32h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0



Bit Range	Default & Access	Field Name (ID): Description
15	0b RW	Vendor Specific Error Status (vend_spec_err_status): Reserved.
14	0b RW	Boot Command Timeout Error (boot_cmd_timeout_err): Occur if the boot are access command is issued to the agent which has no permission to access the boot area.
13	0b RW	CEATA Error (ceata_err): Occurs when ATA command termination has occurred due to an error condition the device has encountered.
12	0b RW	Target Response Error (tgt_rsp_err): Occurs when detecting ERROR in m_hresp(dma transaction).
11:10	0h RO	Reserved (rsvd): Reserved.
9	0b RW	ADMA Error (adma_err): This bit is set when the Host Controller detects errors during ADMA based data transfer. The state of the ADMA at an error occurrence is saved in the ADMA Error Status Register. In addition, the Host Controller generates this Interrupt when it detects invalid descriptor data (Valid=0) at the ST_FDS state. ADMA Error State in the ADMA Error Status indicates that an error occurs in ST_FDS state. The Host Driver may find that Valid bit is not set at the error descriptor. 0 = error 1 = no error
8	0b RW	Auto CMD12 Error (cmd12_err): Auto CMD12 and Auto CMD23 use this error status. This bit is set when detecting that one of the bits D00-D04 in Auto CMD Error Status register has changed from 0 to 1. In case of Auto CMD12, this bit is set to 1, not only when the errors in Auto CMD12 occur but also when Auto CMD12 is not executed due to the previous command error. 1 = error 0 = no error
7	0b RW	Current Limit Error (cur_limit_err): By setting the SD Bus Power bit in the Power Control register, the Host Controller is requested to supply power for the SD Bus. If the Host Controller supports the Current Limit function, it can be protected from an illegal card by stopping power supply to the card in which case this bit indicates a failure status. Reading 1 means the Host Controller is not supplying power to SD card due to some failure. Reading 0 means that the Host Controller is supplying power and no error has occurred. The Host Controller may require some sampling time to detect the current limit. If the Host Controller does not support this function, this bit shall always be set to 0. 1 = power fail 0 = no error
6	0b RW	Data End Bit Error (data_end_bit_err): Occurs either when detecting 0 at the end bit position of read data which uses the DAT line or at the end bit position of the CRC Status. 1 = error 0 = no error
5	0b RW	Data CRC Error (data_crc_err): Occurs when detecting CRC error when transferring read data which uses the DAT line or when detecting the Write CRC status having a value of other than 010b.
4	0b RW	Data Timeout Error (data_timeout_err): This bit is set when detecting one of following timeout conditions. - Busy timeout for R1b,R5b type - Busy timeout after Write CRC status - Write CRC Status timeout - Read Data timeout 1 = time out 0 = no error



Bit Range	Default & Access	Field Name (ID): Description
3	0b RW	Command Index Error (cmd_index_err): This bit is set if a Command Index error occurs in the command response. 1 = error 0 = no error
2	0b RW	Command End Bit Error (cmd_end_bit_err): This bit is set when detecting that the end bit of a command response is 0. 1 = End Bit Error generated 0 = no error
1	0b RW	Command CRC Error (cmd_crc_err): Command CRC Error is generated in two cases. If a response is returned and the Command Timeout Error is set to 0 (indicating no timeout), this bit is set to 1 when detecting a CRC error in the command response. The Host Controller detects a CMD line conflict by monitoring the CMD line when a command is issued. If the Host Controller drives the CMD line to 1 level, but detects 0 level on the CMD line at the next SD clock edge, then the Host Controller shall abort the command (Stop driving CMD line) and set this bit to 1. The Command Timeout Error shall also be set to 1 to distinguish CMD line conflict (refer to tabular data in the spec. that explains the relationship between Command CRC Error and Command Timeout Error). 1 = CRC Error Generated. 0 = no error
0	0b RW	Command Timeout Error (cmd_timeout_err): This bit is set only if no response is returned within 64 SD clock cycles from the end bit of the command. If the Host Controller detects a CMD line conflict (in which case Command CRC Error shall also be set, as shown in tabular data in the spec that explains the relationship between this bit and Command CRC Error) this bit shall be set without waiting for 64 SD clock cycles, because the command will be aborted by the Host Controller. 1 = time out 0 = no Error

16.10.22 Normal Interrupt Status Enable (NRM_INT_STATUS_EN)—Offset 34h

Setting to 1 enables Interrupt Status. **Implementation Note:** The Host Controller may sample the card interrupt signal during interrupt period, and may hold its value in the flip-flop. If the **Card Interrupt Status Enable** is set to 0, the Host Controller shall clear all internal signals regarding Card Interrupt.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)


Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
fixed_0	rsvd	boot_term_int_en	boot_ack_rcv_en	crd_int_stat_en
		crd_rm_stat_en	crd_ins_stat_en	buf_rd_rdy_stat_en
		buf_wr_rdy_stat_en	dma_int_stat_en	blk_gap_event_stat_en
			tx_comp_stat_en	cmd_comp_stat_en



Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Fixed to 0 (fixed_0): The Host Driver shall control error interrupts using the Error Interrupt Status Enable register.
14:11	0h RO	Reserved (rsvd): Reserved.
10	0b RW	Boot Term Interrupt Enable (boot_term_int_en): 0 = Masked.
9	0b RW	Boot Acknowledge Receive Enable (boot_ack_rcv_en): 0 = Masked
8	0b RW	Card Interrupt Status Enable (crd_int_stat_en): If this bit is set to 0, the Host Controller shall clear interrupt request to the System. The Card Interrupt detection is stopped when this bit is cleared, and restarted when this bit is set to 1. The Host Driver may clear the Card Interrupt Status Enable before servicing the Card Interrupt, and may set this bit again after all interrupt requests from the card are cleared, to prevent inadvertent interrupts. 1 = enabled 0 = masked
7	0b RW	Card Removal Status Enable (crd_rm_stat_en): 1 = enabled 0 = masked
6	0b RW	Card Insertion Status Enable (crd_ins_stat_en): [1 = enabled 0 = masked
5	0b RW	Buffer Read Ready Status Enable (buf_rd_rdy_stat_en): 1 = enabled 0 = masked
4	0b RW	Buffer Write Ready Status Enable (buf_wr_rdy_stat_en): 1 = enabled 0 = masked
3	0b RW	DMA Interrupt Status Enable (dma_int_stat_en): 1 = enabled 0 = masked
2	0b RW	Block Gap Event Status Enable (blk_gap_event_stat_en): 1 = enabled 0 = masked
1	0b RW	Transfer Complete Status Enable (tx_comp_stat_en): 1 = enabled 0 = masked
0	0b RW	Command Complete Status Enable (cmd_comp_stat_en): 1 = enabled 0 = masked



16.10.23 Error Interrupt Status Enable Register (ERR_INT_STAT_EN)— Offset 36h

Setting to 1 enables interrupt status. **Implementation Note:** To detect CMD line conflict, the Host Driver must set both **Command Timeout Error Status Enable** and **Command CRC Error Status Enable** to 1.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 36h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd0	ceata_err_en	tgt_rsp_err_en	rsvd	tune_err_stat_en
				adma_err_stat_en
				cmd12_err_stat_en
				cur_limit_err_stat_en
				data_end_bit_err_stat_en
				data_crc_err_stat_en
				data_timeout_err_stat_en
				cmd_ind_err_stat_en
				cmd_end_bit_err_stat_en
				cmd_crc_err_stat_en
				cmd_timeout_err_stat_en

Bit Range	Default & Access	Field Name (ID): Description
15:14	0b RO	Rsvd0 (rsvd0): Reserved.
13	0b RW	CEATA Error Enable (ceata_err_en): 0 = masked
12	0b RW	Target Response Error Enable (tgt_rsp_err_en): 0 = masked
11	0b RO	Rsvd (rsvd): Reserved.
10	0b RW	Tuning Error Status Enable (tune_err_stat_en): 1 = enabled 0 = masked
9	0b RW	ADMA Error Status Enable (adma_err_stat_en): 1 = enabled 0 = masked
8	0b RW	Auto CMD12 Error Status Enable (cmd12_err_stat_en): 1 = enabled 0 = masked
7	0b RW	Current Limit Error Status Enable (cur_limit_err_stat_en): 1 = enabled 0 = masked
6	0b RW	Data End Bit Error Status Enable (data_end_bit_err_stat_en): 1 = enabled 0 = masked



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	Data CRC Error Status Enable (data_crc_err_stat_en): 1 = enabled 0 = masked
4	0b RW	Data Timeout Error Status Enable (data_timeout_err_stat_en): 1 = enabled 0 = masked
3	0b RW	Command Index Error Status Enable (cmd_ind_err_stat_en): 1 = enabled 0 = masked
2	0b RW	Command End Bit Error Status Enable (cmd_end_bit_err_stat_en): 1 = enabled 0 = masked
1	0b RW	Command CRC Error Status Enable (cmd_crc_err_stat_en): 1 = enabled 0 = masked
0	0b RW	Command Timeout Error Status Enable (cmd_timeout_err_stat_en): 1 = enabled 0 = masked

16.10.24 Normal Interrupt Signal Enable Register (NRM_INT_SIG_EN)—Offset 38h

This register is used to select which interrupt status is indicated to the Host System as the interrupt. These status bits all share the same 1 bit interrupt line. Setting any of these bits to 1 enables interrupt generation.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
fixed_0	rsvd	boot_term_int_sig_en	boot_ack_rcv_sig_en	crd_int_sig_en
		crd_rm_sig_en	crd_ins_sig_en	buf_rd_rdy_sig_en
		buf_wr_rdy_sig_en	dma_int_sig_en	blk_gap_event_sig_en
			tx_comp_sig_en	cmd_comp_sig_en

Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Fixed to 0 (fixed_0): The Host Driver shall control error interrupts using the Error Interrupt Signal Enable register.
14:11	0h RO	Reserved (rsvd): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
10	0b RW	Boot Terminate Interrupt Signal Enable (boot_term_int_sig_en): 0 = masked
9	0b RW	Boot Acknowledge Receive Signal Enable (boot_ack_rcv_sig_en): 0 = masked
8	0b RW	Card Interrupt Signal Enable (crd_int_sig_en): 1 = enabled 0 = masked
7	0b RW	Card Removal Signal Enable (crd_rm_sig_en): 1 = enabled 0 = masked
6	0b RW	Card Insertion Signal Enable (crd_ins_sig_en): 1 = enabled 0 = masked
5	0b RW	Buffer Read Ready Signal Enable (buf_rd_rdy_sig_en): 1 = enabled 0 = masked
4	0b RW	Buffer Write Ready Signal Enable (buf_wr_rdy_sig_en): 1 = enabled 0 = masked
3	0b RW	DMA Interrupt Signal Enable (dma_int_sig_en): 1 = enabled 0 = masked
2	0b RW	Block Gap Event Signal Enable (blk_gap_event_sig_en): 1 = enabled 0 = masked
1	0b RW	Transfer Complete Signal Enable (tx_comp_sig_en): 1 = enabled 0 = masked
0	0b RW	Command Complete Signal Enable (cmd_comp_sig_en): 1 = enabled 0 = masked

16.10.25 Error Interrupt Signal Enable Register (ERR_INT_SIG_EN)—Offset 3Ah

This register is used to select which interrupt status is sent to the Host System as the interrupt. These status bits all share the same 1 bit interrupt line. Setting any of these bits to 1 enables interrupt generation.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 3Ah

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
rsvd0	ceata_err_sig_en	tgt_err_rsp_sig_en	rsvd	tune_err_sig
				adma_err_sig_en
				cmd12_err_sig_en
				cur_limit_err_sig_en
				data_end_bit_err_sig_en
				data_crc_err_sig_en
				data_timeout_err_stat_en
				cmd_ind_err_stat_en
				cmd_end_bit_err_stat_en
				cmd_crc_err_stat_en
				cmd_timeout_err_stat_en

Bit Range	Default & Access	Field Name (ID): Description
15:14	0b RO	Rsvd0 (rsvd0): Reserved.
13	0b RW	CEATA_Error Signal Enable (ceata_err_sig_en): 0 = masked
12	0b RW	Target Error Response Signal Enable (tgt_err_rsp_sig_en): 0 = masked
11	0b RO	Reserved (rsvd): Reserved.
10	0b RW	Tuning Error Signal Enable (tune_err_sig): 1 = enabled 0 = masked
9	0b RW	ADMA Error Signal Enable (adma_err_sig_en): 1 = enabled 0 = masked
8	0b RW	Auto CMD12 Error Signal Enable (cmd12_err_sig_en): 1 = enabled 0 = masked
7	0b RW	Current Limit Error Signal Enable (cur_limit_err_sig_en): 1 = enabled 0 = masked
6	0b RW	Data End Bit Error Signal Enable (data_end_bit_err_sig_en): 1 = enabled 0 = masked
5	0b RW	Data CRC Error Signal Enable (data_crc_err_sig_en): 1 = enabled 0 = masked
4	0b RW	Data Timeout Error Signal Enable (data_timeout_err_stat_en): 1 = enabled 0 = masked
3	0b RW	Command Index Error Signal Enable (cmd_ind_err_stat_en): 1 = enabled 0 = masked
2	0b RW	Command End Bit Error Signal Enable (cmd_end_bit_err_stat_en): 1 = enabled 0 = masked



Bit Range	Default & Access	Field Name (ID): Description
29:24	0b RO	RSVD0: Reserved
23	0b RW	Sampling Clock (sampling_clock): This bit is set by tuning procedure when Execute Tuning is cleared.
22	0b RW/AC	Execute Tuning (execute_tuning): This bit is set to 1 to start tuning procedure and automatically cleared when tuning procedure is completed. The result of tuning is indicated to Sampling Clock Select. Tuning procedure is aborted by writing 0. Refer to the spec for more detail about tuning procedure. 1 = Execute Tuning 0 = Not Tuned or Tuning Completed
21:20	0b RW	Driver Strength (driver_strength): Host Controller output driver in 1.8V signaling is selected by this bit.
19	0b RW	Voltage Regulator Control for I/O Cell (vl): This bit controls voltage regulator for I/O cell.
18:16	0b RW	UHS Mode Select (uhs_mode): This field is used to select one of UHS-I modes.
15:8	0h RO	Rsvd (rsvd): Reserved.
7	0b RO	Command Not Issued By Auto CMD12 Error (cmd_not_iss_cmd12_err): Reserved.
6:5	0h RO	Rsvd1 (rsvd1): Reserved
4	0b RO	Auto CMD12 Index Error (cmd12_ind_err): Reserved.
3	0b RO	Auto CMD12 End Bit Error (cmd12_end_bit_err): Reserved.
2	0b RO	Auto CMD12 CRC Error (cmd12_crc_err): Reserved.
1	0b RO	Auto CMD12 Timeout Error (cmd12_timeout_err): Reserved.
0	0b RO	Auto CMD12 Not Executed (cmd12_not_exe): Reserved.

16.10.27 Capabilities Register (CAPABILITIES)—Offset 40h

This register provides the HD with information specific to the HC implementation. The HC may implement these values as fixed or loaded from flash memory during power on initialization.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h

312824201612840																															
00000000000000000000000000000000																															
capabilities																															
Bit Range		Default & Access		Field Name (ID): Description																											
31:0		0b RO		Capabilities (capabilities): Reserved.																											

16.10.28 Capabilities Register 2 (CAPABILITIES_2)—Offset 44h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h

312824201612840 0 0 0 0 0 0 0 0																															
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

16.10.29 Maximum Current Capabilities Register (MAX_CUR_CAP)—Offset 48h

These registers indicate maximum current capability for each voltage. The value is meaningful if Voltage Support is set in the Capabilities register. If this information is supplied by the Host System via another method, all Maximum Current Capabilities register shall be 0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	rsvd		max_cur_1p8v		max_cur_3p0v		max_cur_3p3v	

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RO	Reserved (rsvd): Reserved.
23:16	00h RO	Maximum Current for 1.8V (max_cur_1p8v): Reserved.
15:8	00h RO	Maximum Current for 3.0V (max_cur_3p0v): Reserved.
7:0	00h RO	Maximum Current for 3.3V (max_cur_3p3v): Reserved.

16.10.30 Force Event Register for Auto CMD12 Error Status (FORCE_EVENT_CMD12_ERR_STAT)—Offset 50h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
	reserved0	non_cmd12_err	reserved	cmd12_ind_err
				cmd12_end_bit_err
				cmd12_crc_err
				cmd12_timeout_err
				cmd12_not_exe

Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RO	Reserved 0 (reserved0): Reserved.
7	0b RW	Force Event for Command Not Issued By Auto CMD12 Error (non_cmd12_err): 1 = Interrupt is generated 0 = No Interrupt
6:5	00b RO	Reserved (reserved): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	Force Event for Auto CMD12 Index Error (cmd12_ind_err): 1 = Interrupt is generated 0 = No Interrupt
3	0b RW	Force Event for Auto CMD12 End Bit Error (cmd12_end_bit_err): 1 = Interrupt is generated 0 = No Interrupt
2	0b RW	Force Event for Auto CMD12 CRC Error (cmd12_crc_err): 1 = Interrupt is generated 0 = No Interrupt
1	0b RW	Force Event for Auto CMD12 Timeout Error (cmd12_timeout_err): 1 = Interrupt is generated 0 = No Interrupt
0	0b RW	Force Event for Auto CMD12 Not Executed (cmd12_not_exe): 1 = Interrupt is generated 0 = No Interrupt

16.10.31 Force Event Register for Error Interrupt Status (FORCE_EVENT_ERR_INT_STAT)—Offset 52h

Error Interrupt Status register can be written. The effect of a write to this address will be reflected in the Error Interrupt Status Register if the corresponding bit of the Error Interrupt Status Enable Register is set.

- Writing 1 : set each bit of the Error Interrupt Status Register
- Writing 0 : no effect

Note: By setting this register, the Error Interrupt can be set in the Error Interrupt Status register. In order to generate interrupt signal, both the Error Interrupt Status Enable and Error Interrupt Signal Enable shall be set.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + 52h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
rsvd0	ceata_err	tgt_rsp_err	rsvd	adma_err
				cmd12_err
				cur_limit_err
				data_end_bit_err
				data_crc_err
				data_timeout_err
				cmd_ind_err
				cmd_end_bit_err
				cmd_crc_err
				cmd_timeout_err

Bit Range	Default & Access	Field Name (ID): Description
15:14	00b RO	Reserved 0 (rsvd0): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
13	0b RW	Force Event for CEATA Error (ceata_err): Reserved.
12	0b RW	Force Event for Target Response Error (tgt_rsp_err): Reserved.
11:10	0h RO	Reserved (rsvd): Reserved.
9	0b RW	Force Event for ADMA Error (adma_err): 1 = Interrupt is generated 0 = No Interrupt
8	0b RW	Force Event for Auto CMD12 Error (cmd12_err): 1 = Interrupt is generated 0 = No Interrupt
7	0b RW	Force Event for Current Limit Error (cur_limit_err): 1 = Interrupt is generated 0 = No Interrupt
6	0b RW	Force Event for Data End Bit Error (data_end_bit_err): 1 = Interrupt is generated 0 = No Interrupt
5	0b RW	Event for Data CRC Error (data_crc_err): 1 = Interrupt is generated 0 = No Interrupt
4	0b RW	Event for Data Timeout Error (data_timeout_err): 1 = Interrupt is generated 0 = No Interrupt
3	0b RW	Force Event for Command Index Error (cmd_ind_err): 1 = Interrupt is generated 0 = No Interrupt
2	0b RW	Force Event for Command End Bit Error (cmd_end_bit_err): 1 = Interrupt is generated 0 = No Interrupt
1	0b RW	Force Event for Command CRC Error (cmd_crc_err): 1 = Interrupt is generated 0 = No Interrupt
0	0b RW	Force Event for Command Timeout Error (cmd_timeout_err): 1 = Interrupt is generated 0 = No Interrupt

16.10.32 ADMA Error Status Register (ADMA_ERR_STAT)—Offset 54h

When ADMA Error Interrupt occurs, the ADMA Error States field in this register holds the ADMA state and the ADMA System Address Register holds the address around the error descriptor. To recover from the error, the Host Driver requires the ADMA state to identify the error descriptor address as follows:

- ST_STOP: Previous location set in the ADMA System Address register is the error descriptor address
- ST_FDS: Current location set in the ADMA System Address register is the error descriptor address
- ST_CADR: This state is never set because do not generate ADMA error in this state.



- ST_TFR: Previous location set in the ADMA System Address register is the error descriptor address

The Host Controller generates the ADMA Error Interrupt when it detects invalid descriptor data (Valid=0) at the ST_FDS state. In this case, ADMA Error State indicates that an error occurs at ST_FDS state. The Host Driver may find that the Valid bit is not set in the error descriptor.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00h

7	4	0
0	0	0
rsvd		adma_err_state
		adma_len_mis_err

Bit Range	Default & Access	Field Name (ID): Description
7:3	0h RO	Reserved (rsvd): Reserved.
2	0b RO	ADMA Length Mismatch Error (adma_len_mis_err): This error occurs in the following 2 cases. • While Block Count Enable being set, the total data length specified by the Descriptor table is different from that specified by the Block Count and Block Length. • Total data length can not be divided by the block length. • 1 = Error • 0 = No Error
1:0	00b RO	ADMA Error State (adma_err_state): This field indicates the state of ADMA when error is occurred during ADMA data transfer. This field never indicates '10' because ADMA never stops in this state. Refer to the spec for tabular information about the relationship between this field and SYS_SDR register.

16.10.33 ADMA System Address Register (ADMA_SYS_ADDR)—Offset 58h

This register contains the physical Descriptor address used for ADMA data transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 70h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h

16.10.35 Debug Selection Register (DEBUG_SEL)—Offset 74h

Access Method

Offset: [BAR] + 74h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00h

7			4					0
0	0	0	0	0	0	0	0	0
			rsvd					debug_sel



Bit Range	Default & Access	Field Name (ID): Description
7:1	00h RO	Reserved (rsvd): Reserved.
0	0b WO	Debug Select (debug_sel): 1 = cmd register, interrupt status, transmitter module, ahb_iface module and clk sdcard signals are probed out. 0 = receiver module and fifo_ctrl module signals are probed out

16.10.36 Shared Bus Control Register (SHARED_BUS)—Offset E0h

This register is optional. The devices on shared bus are not intended to be controlled by the Standard Host Driver. This is because shared bus configuration depends on a host system; the devices on shared bus may be controlled by a specific driver of a host system.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0															
0				0				0				0				0				0				0				0				0				0											
RSVD0				pwr_ctrl				RSVD1				int_pin				RSVD2				clk_pin				RSVD3				bus_width				RSVD4				num_int_pin				RSVD5				num_clk_pin			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	RSVD0: Reserved
30:24	0h RW	Back-End Power Control (pwr_ctrl): Each bit of this field controls back-end power supply for an embedded device. Host interface voltage (VDDH) is not controlled by this field. The number of devices supported is specified by Number of Clock Pins , and a maximum of 7 devices can be controlled. - D24 Back-end Power Control for Device 1 - D25 Back-end Power Control for Device 2 - D26 Back-end Power Control for Device 3 - D27 Back-end Power Control for Device 4 - D28 Back-end Power Control for Device 5 - D29 Back-end Power Control for Device 6 - D30 Back-end Power Control for Device 7 The function of each bit is defined as follows: 0 = Back-end Power is Off 1 = Back-end Power is Supplied Back-End power control is effective for embedded memory devices in the Sleep State that support the Sleep command (CMD14) to reduce power consumption and embedded SDIO devices when IOEx is set to 0.
23	0b RO	RSVD1: Reserved



Bit Range	Default & Access	Field Name (ID): Description
22:20	0h RW	Interrupt Pin Select (int_pin): Interrupt pin inputs are enabled by this field. Enable of unsupported interrupt pin is meaningless. 000b = Interrupt is detected by the Interrupt Cycle. - xx1b = INT_A is enabled - x1xb = INT_B is enabled 1xxb = INT_C is enabled
19	0b RO	RSVD2: Reserved
18:16	0h RW	Clock Pin Select (clk_pin): One of clock pin outputs is selected by this field. Selection of unsupported clock pins is meaningless. Refer to Figure 2-38 for the timing of clock outputs. 000b = Clock Pins are disabled 001b = CLK[1] is selected 010b = CLK[2] is selected ... 111b = CLK[7] is Selected
15	0b RO	RSVD3: Reserved
14:8	0h RO	Bus Width Preset (bus_width): Shared bus supports mixing of 4-bit and 8-bit bus width devices. Each bit of this field specifies the bus width for each embedded device. The number of devices supported is specified by Number of Clock Pins, and a maximum of 7 devices are supported. This field is effective when multiple devices are connected to a shared bus (Slot Type is set to 10b in the Capabilities register). In the other case, Extended Data Transfer Width in the Host Control 1 register is used to select 8-bit bus width. As use of 1-bit mode is not intended for shared bus, Data Transfer Width in the Host Control 1 register should be set to 1. - D24 = Bus width preset for Device 1 - D25 = Bus width preset for Device 2 - D26 = Bus width preset for Device 3 - D27 = Bus width preset for Device 4 - D28 = Bus width preset for Device 5 - D29 = Bus width preset for Device 6 - D30 = Bus width preset for Device 7 The function of each bit is defined as follows: 0 = 4 bit buswidth mode 1 = 8 bit buswidth mode
7:6	0b RO	RSVD4: Reserved
5:4	0h RO	Number of Interrupt Pins (num_int_pin): This field indicates support of interrupt input pins for shared bus system. Three asynchronous interrupt pins are defined, INT_A#, INT_B# and INT_C#. Which interrupt pin is used is determined by the system. Each one is driven by open drain and then wired OR connection is possible. 00b = Interrupt Input Pin is not supported 01b = INTA is Supported 10b = INTA and INTB are supported 11b = INTA, INTB and INTC are supported
3	0b RO	RSVD5: Reserved
2:0	0h RO	Number of Clock Pins (num_clk_pin): This field indicates support of clock pins to select one of devices for shared bus system. Up to 7 clock pins can be supported. Shared bus is supported by specific system. Then the Standard Host Driver does not support control of these clock pins. 000b Shared bus is not supported 001b 1 SDCLK pin is supported 010b 2 SDCLK pins are supported ... 111b 7 SDCLK pins are supported



16.10.37 SPI Interrupt Support Register (SPI_INT_SUP)—Offset F0h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [BAR] + F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
					spi_int_support				

Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RW	SPI Interrupt Support (spi_int_support): This bit is set to indicate the assertion of interrupts in the SPI mode at any time, irrespective of the status of the card select (CS) line. If this bit is zero, then SDIO card can only assert the interrupt line in the SPI mode when the CS line is asserted.

16.10.38 Slot Interrupt Status Register (SLOT_INT_STAT)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: 0000h

15				12				8				4				0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
reserved								int_sig_slot								

Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RO	Reserved (reserved): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RO	Interrupt Signal For Each Slot (int_sig_slot): These status bits indicate the logical OR of Interrupt Signal and Wakeup Signal for each slot. A maximum of 8 slots can be defined. If one interrupt signal is associated with multiple slots, the Host Driver can know which interrupt is generated by reading these status bits. By a power on reset or by setting Software Reset For All, the interrupt signal shall be de-asserted and this status shall read 00h. • Bit 00 = Slot 1 • Bit 01 = Slot 2 • Bit 02 = Slot 3 • • Bit 07 = Slot 8

16.10.39 Host Controller Version Register (HOST_CTRL_VER)—Offset FEh

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [BAR] + FEh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:23, F:0] + 10h

Default: B502h

15	12	8	4	0
1	0	1	1	0
0	1	0	1	0
0	0	0	0	0
0	0	1	0	0
vend_ver_num				spec_ver_num

Bit Range	Default & Access	Field Name (ID): Description
15:8	b5h RO	Vendor Version Number (vend_ver_num): This status is reserved for the vendor version number. The Host Driver should not use this status.
7:0	02h RO	Specification Version Number (spec_ver_num): This status indicates the Host Controller Spec. Version. The upper and lower 4-bits indicate the version. • 00h = SD Host Specification Version 1.00 • 01h = SD Host Specification Version 2.00, Including the feature of the ADMA and Test Register • 02h = SD Host Specification Version 3.00 • others = Reserved

17 Serial ATA (SATA)

The SoC has one integrated SATA host controller that supports independent DMA operation on up to 2 ports and supports data transfer rates of 1.5 Gb/s (150 MB/s) and 3.0 Gb/s (300 MB/s). The SATA controller contains two modes of operation—a legacy mode using I/O space, and an AHCI mode using memory space. Software that uses legacy mode will not have AHCI capabilities.


The SoC supports the Serial ATA Specification, Revision 2.6. The SoC also supports several optional sections of the SATA Revision 2.0 Specifications: Extensions to Serial ATA 1.0 Specification, Revision 1.0 (AHCI support is required for some elements).

The SATA controllers feature two sets of interface signals (ports) that can be independently enabled or disabled (they cannot be tri-stated or driven low). Each interface is supported by an independent DMA controller.

The SATA controllers interact with an attached mass storage device through a register interface that is equivalent to that presented by a traditional IDE host adapter. The host software follows existing standards and conventions when accessing the register interface and follows standard command protocol conventions.

Note 1. SATA DevSlp (**Device Sleep**) is not part of revision 2.6 of the SATA specification, with which this processor is compliant. As such, any DEVSLP functionality of this processor is not specification compliant and should not be used.

Note 2. SATA interface transfer rates are independent of UDMA mode settings. SATA interface transfer rates will operate at the bus's maximum speed, regardless of the UDMA mode reported by the SATA device or the system BIOS.



17.1 Signal Descriptions

Please see [Chapter 2, "Physical Interfaces"](#) for additional details.



The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function

Table 190. Signals


Signal Name	Direction Plat. Power	Description
SATA_GP[0]	I V1P8S	Serial ATA 0 General Purpose: This is an input pin which can be configured as an interlock switch or as a general purpose I/O, depending on the platform. When used as an interlock switch status indication, this signal should be driven to '0' to indicate that the switch is closed, and to '1' to indicate that the switch is open.
SATA_GP[1]	I V1P8S	Serial ATA 1 General Purpose: Same as above.
SATA_LED#	O V1P8S	Serial ATA LED: This is an open-collector output pin driven during SATA command activity. It is to be connected to external circuitry that can provide the current to drive a platform LED. When active, the LED is on. When tristated, the LED is off.
SATA_TXP[1:0] SATA_TXN[1:0]	O VPCIESATA	Serial ATA Port 1 and 0: These are outbound high-speed differential signals to Port 1 and 0.
SATA_RXP[1:0] SATA_RXN[1:0]	I VPCIESATA	Serial ATA Port 1 and 0: These are inbound high-speed differential signals to Port 1 and 0.
SATA_RCOMP_P SATA_RCOMP_N	O	These pins are used to connect the external resistors used for Rcomp. Please contact your Intel representative for details.

17.2 Features

17.2.1 Supported Features

Table 191. SATA Feature List (Sheet 1 of 2)

Feature	Description
Native Command Queuing (NCQ)	Allows the device to reorder commands for more efficient data transfers
Auto Activate for DMA	Collapses a DMA Setup then DMA Activate sequence into a DMA Setup only
Hot Plug Support	Allows for device detection without power being applied and ability to connect and disconnect devices without prior notification to the system
Asynchronous Signal Recovery	Provides a recovery from a loss of signal or establishing communication after hot plug
3 Gb/s Transfer Rate	Capable of data transfers up to 3 Gb/s
ATAPI Asynchronous Notification	A mechanism for a device to send a notification to the host that the device requires attention

**Table 191. SATA Feature List (Sheet 2 of 2)**

Feature	Description
Host & Link Initiated Power Management	Capability for the host controller or device to request Partial and Slumber interface power states
Staggered Spin-Up	Enables the host to spin up hard drives sequentially to prevent power load problems on boot
Command Completion Coalescing	Reduces interrupt and completion overhead by allowing a specified number of commands to complete and then generating an interrupt to process the commands

Table 192. SATA/AHCI Feature Matrix

Feature	AHCI Disabled	AHCI Enabled
Native Command Queuing (NCQ)	N/A	Supported
Auto Activate for DMA	N/A	Supported
Hot Plug Support	N/A	Supported
Asynchronous Signal Recovery	N/A	Supported
3 Gb/s Transfer Rate	Supported	Supported
ATAPI Asynchronous Notification	N/A	Supported
Host & Link Initiated Power Management	N/A	Supported
Staggered Spin-Up	Supported	Supported
Command Completion Coalescing	N/A	N/A

17.2.2 Theory of Operation

17.2.2.1 Standard ATA Emulation

The SoC contains a set of registers that shadow the contents of the legacy IDE registers. The behavior of the Command and Control Block registers, PIO, and DMA data transfers, resets, and interrupts are all emulated.

Note: The SoC will assert INTR when the master device completes the EDD command regardless of the command completion status of the slave device. If the master completes EDD first, an INTR is generated and BSY will remain '1' until the slave completes the command. If the slave completes EDD first, BSY will be '0' when the master completes the EDD command and asserts INTR. Software must wait for busy to clear (0) before completing an EDD command, as required by the ATA5 through ATA7 (T13) industry standards.

17.2.2.2 48-Bit LBA Operation

The SATA host controller supports 48-bit LBA through the host-to-device register FIS when accesses are performed using writes to the task file. The SATA host controller will ensure that the correct data is put into the correct byte of the host-to-device FIS.



There are special considerations when reading from the task file to support 48-bit LBA operation. Software may need to read all 16-bits. Since the registers are only 8-bits wide and act as a FIFO, a bit must be set in the device/control register, which is at offset 3F6h for primary and 376h for secondary (or their native counterparts).

If software clears Bit 7 of the control register before performing a read, the last item written will be returned from the FIFO. If software sets Bit 7 of the control register before performing a read, the first item written will be returned from the FIFO.

17.2.3 AHCI Operation

The SoC provides hardware support for Advanced Host Controller Interface (AHCI), a programming interface for SATA host controllers developed through a joint industry effort. AHCI defines transactions between the SATA controller and software and enables advanced performance and usability with SATA. Platforms supporting AHCI may take advantage of performance features such as no master/slave designation for SATA devices—each device is treated as a master—and hardware assisted native command queuing. AHCI also provides usability enhancements such as Hot-Plug. AHCI requires appropriate software support (such as, an AHCI driver) and for some features, hardware support in the SATA device or additional platform hardware.

The SoC supports all of the mandatory features of the *Serial ATA Advanced Host Controller Interface Specification*, Revision 1.3 and many optional features, such as hardware assisted native command queuing, aggressive power management, LED indicator support, and Hot-Plug through the use of interlock switch support (additional platform hardware and software may be required depending upon the implementation).

Note: For reliable device removal notification while in AHCI operation without the use of interlock switches (surprise removal), interface power management should be disabled for the associated port.


17.3 References

- Serial ATA Specification rev 2.6
- Serial ATA Advanced Host Controller Interface (AHCI) Specification rev 1.3
- Serial ATA II: Extensions to Serial ATA 1.0 Specification, Revision 1.0

17.4 Register Map

See Chapters 3 and 4 for additional information.

Figure 102.SATA Register Map





17.5 SATA PCI Configuration Registers

Table 193. Summary of SATA PCI Configuration Registers—0/19/0

Offset	Size	Register ID—Description	Default Value
0h	4	"Identifiers (ID)—Offset 0h" on page 1933	0F208086h
4h	2	"Command (CMD)—Offset 4h" on page 1933	0000h
6h	2	"Device Status (STS)—Offset 6h" on page 1934	02B0h
8h	1	"Revision ID (RID)—Offset 8h" on page 1935	00h
9h	1	"Programming Interface (PI)—Offset 9h" on page 1936	8Ah
Ah	2	"Class Code (CC)—Offset Ah" on page 1936	0106h
Ch	1	"Cache Line Size (CLS)—Offset Ch" on page 1937	00h
Dh	1	"Master Latency Timer (MLT)—Offset Dh" on page 1937	00h
Eh	1	"Header Type (HTYPE)—Offset Eh" on page 1937	00h
10h	4	"Primary Command Block Base Address (PCMDBA)—Offset 10h" on page 1938	00000001h
14h	4	"Primary Control Block Base Address (PCTLBA)—Offset 14h" on page 1938	00000001h
18h	4	"Secondary Command Block Base Address (SCMDBA)—Offset 18h" on page 1939	00000001h
1Ch	4	"Secondary Control Block Base Address (SCTLBA)—Offset 1Ch" on page 1940	00000001h
20h	4	"Legacy IDE Base Address / AHCI Index Data Pair Base Address (LBAR)—Offset 20h" on page 1940	00000001h
24h	4	"AHCI Base Address/Serial ATA Index Data Pair Base Address (ABAR)—Offset 24h" on page 1941	00000000h
2Ch	4	"Sub System Identifiers (SS)—Offset 2Ch" on page 1942	00000000h
34h	1	"Capabilities Pointer (CAP)—Offset 34h" on page 1942	80h
3Ch	2	"Interrupt Information (INTR)—Offset 3Ch" on page 1942	0100h
3Eh	1	"Minimum Grant (MGNT)—Offset 3Eh" on page 1943	00h
3Fh	1	"Maximum Latency (MLAT)—Offset 3Fh" on page 1943	00h
40h	2	"Primary Timing (PTIM)—Offset 40h" on page 1944	0000h
42h	2	"Secondary Timing (STIM)—Offset 42h" on page 1945	0000h
44h	1	"Device 1 IDE Timing (D1TIM)—Offset 44h" on page 1946	00h
48h	1	"Synchronous DMA Control (Synchronous_DMA_Control)—Offset 48h" on page 1946	00h
4Ah	2	"Synchronous_DMA_Timing—Offset 4Ah" on page 1946	0000h
54h	4	"IDE I/O Configuration (IIOC)—Offset 54h" on page 1947	00000000h
70h	2	"PCI Power Management Capability ID (PID)—Offset 70h" on page 1947	A801h
72h	2	"Primary Command Block Base Address (PCMDBA)—Offset 10h" on page 1938	4003h
74h	2	"PCI Power Management Control and Status (PMCS)—Offset 74h" on page 1948	0008h
80h	2	"Message Signaled Interrupt Identifier (MID)—Offset 80h" on page 1949	7005h
82h	2	"Message Signaled Interrupt Message Control (MC)—Offset 82h" on page 1949	0000h
84h	4	"Message Signaled Interrupt Message Address (MA)—Offset 84h" on page 1950	00000000h
88h	2	"Message Signaled Interrupt Message Data (MD)—Offset 88h" on page 1950	0000h
90h	2	"Port Mapping Register (MAP)—Offset 90h" on page 1951	0420h



Bit Range	Default & Access	Description
15	0h RW/1C	Detected Parity Error (DPE): Set when the SATA Controller detects a parity error on its interface.
14	0h RW/1C	Signaled System Error (SSE): Set when SATA Controller generates an SERR#.
13	0h RW/1C	Received Master-Abort Status (RMA): Set when the SATA Controller receives a master abort to a cycle it generated.
12	0h RW/1C	Received Target-Abort Status (RTA): Set when the SATA Controller receives a target abort to a cycle it generated.
11	0h RW/1C	Signaled Target-Abort Status (STA): This bit must be set by a target device whenever it terminates a transaction with Target-Abort. Devices that will never signal Target-Abort do not need to implement this bit.
10:9	1h RO	DEVSEL# Timing Status (DEVT): Controls the device select time for the SATA Controller's PCI interface.
8	0h RW/1C	Master Data Parity Error Detected (DPD): Set when the SATA Controller, as a master, either detects a parity error or sees the parity error line asserted, and the parity error response bit (bit 6 of the command register) is set. This bit can only be set on read completions received from the backbone where there is a parity error.
7	1h RO	Fast Back-to-Back Capable (FBC): Reserved.
6	0b RO	RSVD0: Reserved
5	1h RO	66 MHz Capable (RSV): Reserved.
4	1h RO	Capabilities List (CL): Indicates the presence of a capabilities list. The minimum requirement for the capabilities list must be PCI power management for the SATA Controller.
3	0h RO	Interrupt Status (IS): Reflects the state of INTx# messages, IRQ14 or IRQ15. This bit is set when the interrupt is to be asserted. This bit is a 0 after the interrupt is cleared
2:0	0b RO	RSVD1: Reserved

17.5.4 Revision ID (RID)—Offset 8h

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

RID: [B:0, D:19, F:0] + 8h

Default: 00h

7	4	0
0	0	0
RID		

Bit Range	Default & Access	Description
7:0	00h RO	Revision ID (RID): Indicates stepping of the host controller hardware.



17.5.5 Programming Interface (PI)—Offset 9h

This register definition depends on the CC.SCC field. When the CC.SCC is 01h(IDE mode), register definition corresponds to 1st table. When CC.SCC is 06h(AHCI mode), register definition follows the 2nd table.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

PI: [B:0, D:19, F:0] + 9h

Default: 8Ah

7			4				0
1	0	0	0	1	0	1	0
BMS	RSVD0			SNC	SNE	PNC	PNE

Bit Range	Default & Access	Description
7	1h RO	Bus Master Support (BMS): Indicates the SATA Controller supports bus master operation.
6:4	0b RO	RSVD0: Reserved
3	1h RO	Secondary Mode Native Capable (SNC): Indicates that the secondary controller supports both legacy and native modes.
2	0h RW	Secondary Mode Native Enable (SNE): Determines the mode that the secondary channel is operating in. 0 corresponds to 'compatibility', 1 means PCI native. If this bit is set by SW, then the PNE bit must also be set by SW. While in theory these bits can be programmed separately, such a configuration is not supported by today's software and is not supported by this hardware. If this bit is left unchanged before switching, the result is indeterminate.
1	1h RO	Primary Mode Native Capable (PNC): Indicates that the primary controller supports both legacy and native modes.
0	0h RW	Primary Mode Native Enable (PNE): Determines the mode that the primary channel is operating in. 0 corresponds to 'compatibility', 1 means PCI native. If this bit is set by SW, then the SNE bit must also be set by SW. While in theory these bits can be programmed separately, such a configuration is not supported by today's software and is not supported by this hardware. If this bit is left unchanged before switching, the result is indeterminate.

17.5.6 Class Code (CC)—Offset Ah

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

CC: [B:0, D:19, F:0] + Ah

Default: 0106h

15		12		8		4		0
0	0	0	0	0	0	0	1	0
BCC				SCC				



Bit Range	Default & Access	Description
15:8	01h RO	Base Class Code (BCC): Indicates that this is a mass storage device.
7:0	06h RO	Sub Class Code (SCC): The value reported in this field is dependent on MAP.SMS and various fuses and configuration bits. The value is product specific. For VLV this field may read 01h (IDE) or 06h (AHCI).

17.5.7 Cache Line Size (CLS)—Offset Ch

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

CLS: [B:0, D:19, F:0] + Ch

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
CLS							

Bit Range	Default & Access	Description
7:0	00h RO	Cache Line Size (CLS): This register has no meaning for the SATA controller.

17.5.8 Master Latency Timer (MLT)—Offset Dh

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

MLT: [B:0, D:19, F:0] + Dh

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
MLT							

Bit Range	Default & Access	Description
7:0	00h RO	Master Latency Timer (MLT): This register has no meaning for the SATA controller.

17.5.9 Header Type (HTYPE)—Offset Eh

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

HTYPE: [B:0, D:19, F:0] + Eh

Default: 00h



7	4	0
0	0	0
MFD	HL	
Bit Range	Default & Access	Description
7	0h RO	Multi-function Device (MFD): Indicates this controller is not part of a multi-function device.
6:0	00h RO	Header Layout (HL): Indicates that the controller uses a target device layout.

17.5.10 Primary Command Block Base Address (PCMDBA)—Offset 10h

This 8-byte I/O space is used in Native Mode for the Primary Controller's Command Block.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCMDBA: [B:0, D:19, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RSVD0				BAR				RSVD1
								RTE

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:3	0h RW	Base Address (BAR): Base address of the I/O space (8 consecutive I/O locations).
2:1	0b RO	RSVD1: Reserved
0	1h RO	Resource Type Indicator (RTE): Indicates a request for IO space.

17.5.11 Primary Control Block Base Address (PCTLBA)—Offset 14h

This 4-byte I/O space is used in Native Mode for the Primary Controller's Control Block.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCTLBA: [B:0, D:19, F:0] + 14h

Default: 00000001h



31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	1	
RSVD0				BAR				RSVD1	RTF

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:2	0h RW	Base Address (BAR): Base address of the I/O space (4 consecutive I/O locations).
1	0b RO	RSVD1: Reserved
0	1h RO	Resource Type Indicator (RTE): Indicates a request for IO space.

17.5.12 Secondary Command Block Base Address (SCMDBA)—Offset 18h

This 8-byte I/O space is used in Native Mode for the Secondary Controller's Command Block.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SCMDBA: [B:0, D:19, F:0] + 18h

Default: 00000001h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	1	
RSVD0				BAR				RSVD1	RTF

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:3	0h RW	Base Address (BAR): Base address of the I/O space (8 consecutive I/O locations).
2:1	0b RO	RSVD1: Reserved
0	1h RO	Resource Type Indicator (RTE): Indicates a request for IO space.



17.5.13 Secondary Control Block Base Address (SCTLBA)—Offset 1Ch

This 4-byte I/O space is used in Native Mode for the Secondary Controller's Control Block.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SCTLBA: [B:0, D:19, F:0] + 1Ch

Default: 00000001h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	1	
RSVD0				BAR				RSVD1	RTF

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:2	0h RW	Base Address (BAR): Base address of the I/O space (4 consecutive I/O locations).
1	0b RO	RSVD1: Reserved
0	1h RO	Resource Type Indicator (RTE): Indicates a request for IO space.

17.5.14 Legacy IDE Base Address / AHCI Index Data Pair Base Address (LBAR)—Offset 20h

This BAR is used to allocate I/O space for the SFF-8038i mode of operation (aka Bus Master IDE) and if CC.SCC is not 01h, it is used to allocate I/O space for the AHCI index/data pair mechanism as well. Note that hardware does not clear the BA bits (including BA4) when switching from IDE mode to non-IDE mode or vice versa. BIOS is responsible for clearing those bits to 0 since the number of writable bits changes after mode switching.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

LBAR: [B:0, D:19, F:0] + 20h

Default: 00000001h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	1	
RSVD0				BA				RSVD1	RTF

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved




When the programming interface is not IDE (i.e. CC.SCC is not 01h), this register is named ABAR. When the programming interface is IDE, this register becomes SIDPBA. Note that hardware does not clear those BA bits when switching from IDE SKU to non-IDE SKU or vice versa. BIOS is responsible for clearing those bits to 0 since the number of writable bits changes after SKU switching (as indicated by a change in CC.SCC). In the case, this register will then have to be re-programmed to a proper value. When the programming interface is not IDE, the register represents a memory BAR allocating space for the AHCI memory registers. Note that bit[31:16] of this register must be programmed to a value greater than 0 to ensure the memory is mapped to an address of 1 MBytes and greater (i.e. ABAR must be 00010000h or greater). Otherwise, memory cycle targeting the ABAR range may not be accepted. When the programming interface is IDE, the register becomes an I/O BAR allocating 16 bytes of I/O space for the I/O mapped registers defined in Memory Registers. Note that although 16 bytes of locations are allocated, only 8 bytes are used as SINDX and SDATA registers; with the remaining 8 bytes preserved for future enhancement.

Type: PCI Configuration Register
(Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:4	0h RW	Base Address (BA): When programming interface is non IDE, this is base address of register memory space (aligned to 2 KB). Bits 31:11 are RW, bits 10:4 are RO of 0; When programming interface is IDE, this is base address of the I/O space. Bits 31:16 are RO of 0, bits 15:4 are RW
3	0h RO	Prefetchable (PF): When programming interface is non IDE, this indicates that this range is not prefetch-able
2:1	0h RO	Type (TP): When programming interface is non IDE, this indicates that this range can be mapped anywhere in 32-bit address space
0	0h RO	Resource Type Indicator (RTE): When programming interface is non IDE, this indicates a request for register memory space; When programming interface is IDE, this indicates a request for IO space.



7			4				0
0	0	0	0	0	0	0	0
MGT							

7			4				0
0	0	0	0	0	0	0	0
MLAT							



17.5.22 Secondary Timing (STIM)—Offset 42h

This controls the timings driven on the parallel cable.

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

STIM: [B:0, D:19, F:0] + 42h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
DE	D1STE	ISP	RSVD0	RCT
DTE1	PPE1	IE1	TIM1	DTE0
PPE0	IE0	TIM0		

Bit Range	Default & Access	Description
15	0h RW	Decode Enable (DE): Enables the SATA Controller to decode the Command Blocks (1F0-1F7h for primary, 170-177h for secondary or their native BAR equivalents) and Control Block (3F6h for primary and 376h for secondary or their native BAR equivalents). This bit still has functionality in SATA - if this bit is not set, the port that is mapped to this range will not be decoded.
14	0h RW	Device 1 Separate Timing Enable (D1STE): This register is not used by SATA controller.
13:12	0h RW	IORDY Sample Point (ISP): This register is not used by SATA controller.
11:10	0b RO	RSVD0: Reserved
9:8	0h RW	Recovery Time (RCT): This register is not used by SATA controller.
7	0h RW	Device 1 DMA Timing Enable (DTE1): This register is not used by SATA controller.
6	0h RW	Device 1 Prefetch/Posting Enable (PPE1): This register is not used by SATA controller.
5	0h RW	Device 1 IORDY Sample Point Enable (IE1): This register is not used by SATA controller.
4	0h RW	Device 1 Fast Timing Bank (TIM1): This register is not used by SATA controller.
3	0h RW	Device 0 DMA Timing Enable (DTE0): This register is not used by SATA controller.
2	0h RW	Device 0 Prefetch/Posting Enable (PPE0): This register is not used by SATA controller.
1	0h RW	Device 0 IORDY Sample Point Enable (IE0): This register is not used by SATA controller.
0	0h RW	Device 0 Fast Timing Bank (TIM0): This register is not used by SATA controller.



17.5.23 Device 1 IDE Timing (D1TIM)—Offset 44h

This register is not used by SATA controller.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

D1TIM: [B:0, D:19, F:0] + 44h

Default: 00h

7	4	0
0	0	0
RSVD		

Bit Range	Default & Access	Description
7:0	0h RW	RSVD: Reserved

17.5.24 Synchronous DMA Control (Synchronous_DMA_Control)—Offset 48h

This register is not used by SATA controller.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Synchronous_DMA_Control: [B:0, D:19, F:0] + 48h

Default: 00h

7	4	0
0	0	0
RSVD		

Bit Range	Default & Access	Description
7:0	0h RW	RSVD: Reserved

17.5.25 Synchronous_DMA_Timing—Offset 4Ah

This register is not used by SATA controller.

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

Synchronous_DMA_Timing: [B:0, D:19, F:0] + 4Ah

Default: 0000h

15	12	8	4	0
0	0	0	0	0
RSVD				

17.5.26 IDE I/O Configuration (IIOC)—Offset 54h



Bit Range	Default & Access	Description
15:11	08h RO	PME_Support: By default with CC.SCC=01h, the default value is 00000 which indicates no PME Support in IDE mode. When CC.SCC is not 01h in non-IDE mode, the default value is 01000 which indicates PME# can be generated from the D3HOT state in the SATA controller.
10	0h RO	D2_Support: The D2 state is not supported.
9	0h RO	D1_Support: The D1 state is not supported.
8:6	0h RO	Aux_Current: PME# from D3COLD state is not supported, therefore this field is 000b.
5	0h RO	Device Specific Initialization (DSI): Indicates that no device-specific initialization is required.
4	0b RO	RSVD0: Reserved
3	0h RO	PME Clock (PMEC): Indicates that PCI clock is not required to generate PME#.
2:0	3h RO	Version (VS): Indicates support for Revision 1.2 of the PCI Power Management Specification.

Access Method

PMCS: [B:0, D:19, F:0] + 74h

Default: 0008h

Bit Range	Default & Access	Description
15	0h RW	PME Status (PMES): This bit is set when a PME event is to be requested, and if this bit is set and PMEE is set, a PME# will be generated. -Note: Whenever CC.SCC=01h either by default or just being updated, hardware shall automatically change the attribute to RO of 0.
14:9	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Description
15:8	0b RO	RSVD0: Reserved
7	0h RO	64 Bit Address Capable (C64): Capable of generating a 32-bit message only.
6:4	0h RO	Multiple Message Enable (MME): When this field is cleared to 000 (and MSIE is set), only a single MSI message will be generated for all SATA ports, and bits [15:0] of the message vector will be driven from MD[15:0].
3:1	0h RO	Multiple Message Capable (MMC): Not supported.
0	0h RW	MSI Enable (MSIE): If set, MSI is enabled and traditional interrupt pins are not used to generate interrupts. Note that CMD.ID bit has not effect on MSI. Software must clear this bit to 0 to disable MSI first before changing the number of messages allocated in the MMC field. Software must also make sure this bit is cleared to 0 when operating in legacy mode (for AHCI SKUs when GHC.AE = 0). This bit is RW when CC.SCC is not 01h and is read-only 0 when CC.SCC is 01h.

17.5.32 Message Signaled Interrupt Message Address (MA)—Offset 84h

Bit Range	Default & Access	Description
31:2	0h RW	Address (ADDR): Lower 32 bits of the system specified message address, always DWORD aligned.
1:0	0b RO	RSVD0: Reserved

17.5.33 Message Signaled Interrupt Message Data (MD)—Offset 88h

Default: 0000h



Bit Range	Default & Access	Description
5	1h RW	SATA Port-to-Controller Configuration (SC): This bit changes number of SATA port availability within each SATA controller. When MAP.SPD[5] is 1 and MAP.SPD[4] is 1, this bit is reserved and is read-only 1 else it's RW-zero. When this bit is 0: Up to 2 SATA ports are available in the SATA controller 1 with port[1:0]. When this bit to 1: Up to 2 SATA ports are available in the SATA controller 1 with port [1:0]. For SMS=IDE mode, this bit should be 0 (note that this irrespective of the number of SATA ports). The number of port availability in this controller shall be discoverable thru this controller's config PCS.PxE, AHCI CAP.NP and AHCI PI[x] register fields. Prior to changing the state of this bit, all ports must be in quiescent state with no commands outstanding. Refer to Single and Dual Controller Switching Requirement for additional software and hardware requirements.
4:2	0b RO	RSVD1: Reserved
1:0	0h RO	Map Value (MV): This register is reserved.

17.5.35 Port Control and Status (PCS)—Offset 92h

By default, the SATA ports are set (by hardware) to the disabled state (e.g. bits[5:0] == 0) as a result of an initial power on reset. When enabled by software, the ports can transition between the on, partial, and slumber states and can detect devices. When disabled, the port is in the off state and cannot detect any devices. Note: AHCI specific notes: If an AHCI-aware or RAID enabled operating system is being booted then system BIOS shall insure that all supported SATA ports are enabled prior to passing control to the OS. Once the AHCI aware OS is booted it becomes the enabling/disabling policy owner for the individual SATA ports. This is accomplished by manipulating a port's PxSCTL.DET and PxCMD.SUD fields. Because an AHCI or RAID aware OS will typically not have knowledge of the PxE bits and because the PxE bits act as master on/off switches for the ports, pre-boot software must insure that these bits are set to 1 prior to booting the OS, regardless as to whether or not a device is currently on the port.

Access Method


Type: PCI Configuration Register
(Size: 16 bits)

PCS: [B:0, D:19, F:0] + 92h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
ORM	RSVD0	RSVD	PIP	POP
			RSVD1	PIE
				POE

Bit Range	Default & Access	Description
15	0h RW	OOB Retry Mode (ORM): When cleared, the SATA controller will not retry after an OOB failure. When set, the SATA controller will continue to retry after an OOB failure until successful (infinite retry). BIOS is requested to program this field to 1.
14	0b RO	RSVD0: Reserved
13:10	0h RO	RSVD: Reserved
9	0h RO	Port 1 Present (P1P): Same as POP, except for port 1.



31				28				24				20				16				12				8				4				0							
0				0				0				0				0				0				0				0				0							
REGLOCK				RSVD0				WRRSELMPS				RSVD1				URRE				URD				AIE				DEVIDSEL				FLRCSSEL				RSVD2			

Bit Range	Default & Access	Description
31	0h RW/O	Register Lock (REGLOCK): BIOS can set this bit to 1 to lock the following registers with RW/L attribute: CAP,CP, MID.NEXT, PIE.NEXT, SATACR0.NEXT. Once locked the register attribute of above list changes from RW/L to RO holding the existing value. BIOS is requested to program this field to 1 prior to hand off to OS. If BIOS needs the SATA host controller to change operation a few times (i.e. changing CC.SCC mode) and need different capability structures for each specific operation mode, BIOS need not activate the lock until BIOS is ready to hand off to OS. BIOS may need to separate write access to this byte offset (x9Fh) from write to the lower 3-byte of the dword (x9C-9Eh) if there is a need to program the lower 3-byte dword location early during boot process.
30:15	0b RO	RSVD0: Reserved
14:12	0h RW	Write Request_Size Select/Max_Payload_Size (WRRSELMP): These two bits select the max write request size that SATA host controller will initiate for DMA write to memory. SATA host controller will internally break up larger write request based on these bits. The request is address-aligned to the selected size. Defined encodings for this field are: 000b = 128 address aligned bytes max payload size; 111b = 64 address aligned bytes max payload size. All other values are reserved for SATA host controller.
11:10	0b RO	RSVD1: Reserved
9	0h RW	Unsupported Request Reporting Enable (URRE): If set to 1 by software, it allows reporting of an Unsupported Request as a system error. If both URRE and PCI configuration SERR# Enable registers are set to a 1, then the agent must set the Signaled System Error bit in the PCI Status register and send a DO_SERR message in IOSF-SB interface.
8	0h RW/1C	Unsupported Request Detected (URD): Set to 1 by hardware upon detecting an Unsupported Request on IOSF Primary interface that is not considered Advisory Non-Fatal. Cleared to 0 by SW.
7	0h RW/O	Alternate ID Enable (AIE): When programmed to 0, HW will report the following device id's: 2822h for desktop or 282Ah for mobile. When programmed to a 1, HW will not report these device id's. The value is product specific. Note: Programming this bit to a 1 will prevent the Windows in-box version of the Intel AHCI driver from loading on the platform - will require that the user perform an 'F6' install of the Intel driver that is appropriate for the reported DID. This field is applicable when the AHCI is configured for RAID mode of operation. It has no impact for AHCI and IDE modes of operation. Note: BIOS is recommended to program this bit prior to programming the MAP.SMS field to reflect RAID. This field is reset by Backbone Reset and BIOS is required to reprogram the value (either 0 or 1) after resuming from S3, S4 or S5. This insures that the value is properly and cannot be changed during runtime.
6	0h RW/O	AIE0 DevID Selection (DEVIDSEL): This register allows BIOS to select Device ID when AIE=0 and Server Feature Disable Fuse 7 =0. This bit only has effect in Desktop SKU. In Mobile SKU this bit has no effect at all. Refer to config register offset 09h PI for usage. 0 : 2822h; 1 : 2826h. NOTE: When Server Feature (SATA AIE DEVIDSEL) Disable Fuse 7 is programmed to 1, this disables the writeability of this DEVIDSEL register bit, and becomes RO with a value of 0, which only allows a choice of 2822h.
5	0h RW/O	FLR Capability Selection (FLRCSSEL): This allows the FLR Capability to be bypassed. Refer to config offset B0h. BIOS is requested to program this bit to 1 and config offset A8h SATACR0.NEXT to 00h.
4:0	0b RO	RSVD2: Reserved



17.5.38 SATA Initialization Register Index (SIRI)—Offset A0h

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SIRI: [B:0, D:19, F:0] + A0h

Default: 00h

7	4	0
0	0	0
IDX		RSVD0

Bit Range	Default & Access	Description
7:2	00h RW	Index (IDX): 6-bit index pointer into the 256-byte space. Data is written into the SIRD register and read from the SIRD register. This point to a DWord register. The byte enables on the SIRD register affect what will be written. Note that this 256-byte register space setting is applicable to all ports in both SATA controllers 1 and 2 (if supported). Refer to SATA Initialization Register section for detail of the register space.
1:0	0b RO	RSVD0: Reserved

17.5.39 SATA Initialization Register Data (SIRD)—Offset A4h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SIRD: [B:0, D:19, F:0] + A4h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DTA								

Bit Range	Default & Access	Description
31:0	00000000h RW	Data (DTA): 32-bit data value that is written to the register pointed to by SIRI, or read from the register pointed to by SIRI.

17.5.40 Serial ATA Capability Register 0 (SATACR0)—Offset A8h

This register shall be read-only 0 when CC.SCC is 01h. Note that the SATACR0.NEXT is not changed from RO to become RWO because there is an existing method (SATAGC.FLRCSSEL bit) to bypass the FLR Capability structure. And FLR Capability ID.NEXT is already indicating end of capability structure, it does not need change to be RWO.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SATACR0: [B:0, D:19, F:0] + A8h

Default: 00100012h



Bit Range	Default & Access	Description
31:24	0b RO	RSVD0 : Reserved
23:20	1h RO	Major Revision (MAJREV) : Major revision number of the SATA Capability Pointer implemented.
19:16	0h RO	Minor Revision (MINREV) : Minor revision number of the SATA Capability Pointer implemented.
15:8	00h RW/L	Next Capability Pointer (NEXT) : 00h indicating the final item in the Capability List. The RW/L register attribute allows for flexibility in determining the capability structure available in this PCI function. Refer to SATAGC.REGLOCK description in order to lock the register to become RO.
7:0	12h RO	Capability ID (CAP) : The value of 12h has been assigned by the PCI SIG to designate the SATA Capability pointer.

17.5.41 Serial ATA Capability Register 1 (SATACR1)—Offset ACh

Access Method

SATACR1: [B:0, D:19, F:0] + ACh

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:4	004h RO	BAR Offset (BAROFST): Indicates the offset into the BAR where the AHCI Index/Data pair are located (in Dword granularity). The Index and Data I/O registers are located at offset 10h within the I/O space defined by LBAR (BAR4). A value of 004h indicates offset 10h. 000h = 0h offset; 001h = 4h offset; 002h = 8h offset; 003h = Ch offset; 004h = 10h offset ... FFFh = 3FFFh offset (max 16 KB)
3:0	8h RO	BAR Location (BARLOC): Indicates the absolute PCI Configuration Register address of the BAR containing the Index/Data pair (in Dword granularity). The Index and Data I/O registers reside within the space defined by LBAR (BAR4) in the SATA controller. A value of 8h indicates offset 20h, which is LBAR (BAR4). 0000 - 0011b = reserved; 0100b = 10h =) BAR0; 0101b = 14h =) BAR1; 0110b = 18h =) BAR2; 0111b = 1Ch =) BAR3; 1000b = 20h =) LBAR; 1001b = 24h =) BAR5; 1010 - 1110b = reserved; 1111b = Index/Data pair in PCI Configuration space which is not supported.

17.5.42 FLR Capability ID (FLRCID)—Offset B0h

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

FLRCID: [B:0, D:19, F:0] + B0h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
NEXT			CID	

Bit Range	Default & Access	Description
15:8	00h RO	Next Capability (NEXT): 00h indicating the final item in the Capability List.
7:0	00h RO	Capability ID (CID): The value of this field depends on the FLRCSSSEL bit. SATAGC.FLRCSSSEL = 0, Capability ID = 13h; SATAGC.FLRCSSSEL = 1, Capability ID = 00h (capability is bypassed).

17.5.43 FLR Control (FLRCTL)—Offset B4h

This register shall be read-only 0 when SATAGC.FLRCSEL=1.

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

FLRCTL: [B:0, D:19, F:0] + B4h

Default: 0000h

15				12					8					4					0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
RSVD																			

Bit Range	Default & Access	Description
15:0	0h RO	RSVD: Reserved

17.5.44 Scratch Pad (SP)—Offset D0h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SP: [B:0, D:19, F:0] + D0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DT								



Bit Range	Default & Access	Description
27:24	8h RO	Dot portion of Process ID (DPID): Indicates the dot. Process is reflected in bits [7:0]. The value is product specific.
23:16	0h RO	Stepping Identifier (SID): This field is incremented for each stepping of the part. Note that this field can be used by software to differentiate steppings when the Revision ID may not change. The value is product specific.
15:8	0Fh RO	Manufacturer Identifier (MID): Indicates Intel.
7:0	B1h RO	Process/Dot Identifier (PID): Indicates the Process. Dot is reflected in bits [27:24]. The value is product specific.



17.6 SATA Legacy IO Registers

Table 194. Summary of SATA Legacy I/O Registers—LBAR

Offset	Size	Register ID—Description	Default Value
0h	1	"Primary Command (PCMD)—Offset 0h" on page 1961	00h
2h	1	"Primary Status (PSTS)—Offset 2h" on page 1962	00h
4h	4	"Primary Descriptor Table Pointer (PDTP)—Offset 4h" on page 1962	00000000h
8h	1	"Secondary Command (SCMD)—Offset 8h" on page 1963	00h
Ah	1	"Secondary Status (SSTS)—Offset Ah" on page 1963	00h
Ch	4	"Secondary Descriptor Table Pointer (SDTP)—Offset Ch" on page 1964	00000000h
10h	4	"AHCI Index Register (INDEX)—Offset 10h" on page 1965	00000000h
14h	4	"AHCI Data Register (DATA)—Offset 14h" on page 1966	00000000h

17.6.1 Primary Command (PCMD)—Offset 0h

Access Method

Type: I/O Register
(Size: 8 bits)

PCMD: [LBAR] + 0h

LBAR Type: PCI Configuration Register (Size: 32 bits)

LBAR Reference: [B:0, D:19, F:0] + 20h

Default: 00h

7	4	0
0	0	0
RSVD0	RWC	RSVD1
		START

Bit Range	Default & Access	Description
7:4	0b RO	RSVD0: Reserved
3	0h RW	Read / Write Control (RWC): Sets the direction of the bus master transfer: 0 = memory to device, 1 = device to memory. This bit must not be changed when the bus master function is active.
2:1	0b RO	RSVD1: Reserved
0	0h RW	Start/Stop Bus Master (START): Setting this bit enables bus master operation of the controller. Bus master operation does not actually start unless the Bus Master Enable bit in PCI configuration space is also set. Clearing it halts bus master operation. All state information is lost when this bit is written to 0; Master mode operation cannot be stopped and then resumed. If this bit is reset while bus master operation is still active and the device has not yet finished its data transfer, the bus master command is said to be aborted. If this bit is cleared to 0 prior to the DMA data transfer being initiated by the drive in a device to memory data transfer, then not DMAT will be sent to terminate the data transfer. SW intervention (e.g. sending SRST) is required to reset the interface in this condition. This bit is intended to be cleared by software after the data transfer is completed - as indicated by either the ACT bit being cleared in the status register, or the I bit being set in the status register, or both.



Bit Range	Default & Access	Description
31:2	00000000h RW	Descriptor Base Address (DBA): Corresponds to A[31:2]. This table must not cross a 64K boundary in memory. When read, the current value of the pointer is returned
1:0	0b RO	RSVD0: Reserved

17.6.4 Secondary Command (SCMD)—Offset 8h

Access Method

Type: I/O Register
(Size: 8 bits)

SCMD: [LBAR] + 8h

LBAR Type: PCI Configuration Register (Size: 32 bits)

LBAR Reference: [B:0, D:19, F:0] + 20h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
RSVD0				RWC	RSVD1		START

Bit Range	Default & Access	Description
7:4	0b RO	RSVD0: Reserved
3	0h RW	Read / Write Control (RWC): Sets the direction of the bus master transfer: 0 = memory to device, 1 = device to memory. This bit must not be changed when the bus master function is active.
2:1	0b RO	RSVD1: Reserved
0	0h RW	Start/Stop Bus Master (START): Setting this bit enables bus master operation of the controller. Bus master operation does not actually start unless the Bus Master Enable bit in PCI configuration space is also set. Clearing it halts bus master operation.

17.6.5 Secondary Status (SSTS)—Offset Ah

Access Method

Type: I/O Register
(Size: 8 bits)

SSTS: [LBAR] + Ah

LBAR Type: PCI Configuration Register (Size: 32 bits)

LBAR Reference: [B:0, D:19, F:0] + 20h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
S	D1DC	D0DC	RSVD0	1	ERR	ACT	



Access Method

SDTP: [LBAR] + Ch

LBAR Reference: [B:0, D:19, F:0] + 20h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DBA								RSVD0

Bit Range	Default & Access	Description
31:2	00000000h RW	Descriptor Base Address (DBA): Corresponds to A[31:2]. This table must not cross a 64K boundary in memory. When read, the current value of the pointer is returned
1:0	0b RO	RSVD0: Reserved



17.6.7 AHCI Index Register (INDEX)—Offset 10h

This registers are only available if CC.SCC is not 01h to index into all memory registers defined in Memory Registers and the message buffer used for enclosure management. If CC.SCC is 01h, these AHCI Index Data Pair registers are not accessible and SINDEX/SDATA register pair shall be used to index into a subset of the memory registers defined in (See Memory Registers for more information on which registers could be indexed).

Access Method

Type: I/O Register
(Size: 32 bits)

INDEX: [LBAR] + 10h

LBAR Type: PCI Configuration Register (Size: 32 bits)

LBAR Reference: [B:0, D:19, F:0] + 20h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0						INDEX		RSVD1

Bit Range	Default & Access	Description
31:11	0b RO	RSVD0: Reserved
10:2	000h RO	Index (INDEX): This Index register is used to select the Dword offset of the Memory Mapped AHCI register to be accessed. A Dword, Word or Byte access is specified by the active byte enables of the I/O access to the Data register.
1:0	0b RO	RSVD1: Reserved



17.6.8 AHCI Data Register (DATA)—Offset 14h

This registers are only available if CC.SCC is not 01h to index into all memory registers defined in Memory Registers and the message buffer used for enclosure management. If CC.SCC is 01h, these AHCI Index Data Pair registers are not accessible and SINDEXT/SDATA register pair shall be used to index into a subset of the memory registers defined in (See Memory Registers for more information on which registers could be indexed).

Access Method

Type: I/O Register
(Size: 32 bits)

DATA: [LBAR] + 14h

LBAR Type: PCI Configuration Register (Size: 32 bits)

LBAR Reference: [B:0, D:19, F:0] + 20h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DATA

Bit Range	Default & Access	Description
31:0	00000000h RW	Data (DATA): This Data register is a window through which data is read or written to the memory mapped register pointed to by the Index register. Note that a physical register is not actually implemented as the data is actually stored in the memory mapped registers. Since this is not a physical register, the default value is the same as the default value of the register pointed to by Index.



17.7.2 Serial ATA Data (SDATA)—Offset 4h

All of these I/O registers are in the core well. They are exposed only when CC.SCC is 01h (i.e. IDE programming interface). These are Index/Data Pair registers that are used to access the SerialATA superset registers (SerialATA Status, SerialATA Control and SerialATA Error). The I/O space for these registers is allocated through SIDPBA. Locations with offset from 08h to 0Fh are reserved for future expansion. Software write operations to the reserved locations shall have no effect while software read operations to the reserved locations shall return 0. Refer to Serial ATA Index/Data Pair Superset Registers for more details.

Access Method

Type: I/O Register
(Size: 32 bits)

SDATA: [ABAR] + 4h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DATA

Bit Range	Default & Access	Description
31:0	00000000h RW	Data (DATA): This Data register is a window through which data is read or written to from the register pointed to by the Serial ATA Index (SINDX) register above. Note that a physical register is not actually implemented as the data is actually stored in the memory mapped registers. Since this is not a physical register, the default value is the same as the default value of the register pointed to by SINDX.RIDX field.



17.8 SATA AHCI Memory Mapped IO Registers

Table 196. Summary of SATA AHCI Memory Mapped I/O Registers—ABAR

Offset	Size	Register ID—Description	Default Value
0h	4	"HBA Capabilities (GHC_CAP)—Offset 0h" on page 1970	DF20FF02h
4h	4	"HBA Capabilities (GHC_CAP)—Offset 0h" on page 1970	00000000h
8h	4	"Interrupt Status (IS)—Offset 8h" on page 1973	00000000h
Ch	4	"Ports Implemented (GHC_PI)—Offset Ch" on page 1973	00000000h
10h	4	"AHCI Version (VS)—Offset 10h" on page 1974	00010300h
24h	4	"HBA Capabilities Extended (GHC_CAP2)—Offset 24h" on page 1974	0000003Ch
A0h	4	"Vendor Specific (VSP)—Offset A0h" on page 1975	00000048h
A4h	4	"Vendor Specific Capabilities (VS_CAP)—Offset A4h" on page 1976	018002FEh
C4h	2	"Premium Feature Block (PFB)—Offset C4h" on page 1977	0000h
C8h	2	"SW Feature Mask (SFM)—Offset C8h" on page 1978	003Fh
100h	4	"Port-Command List Base Address (PxCLB0)—Offset 100h" on page 1979	00000000h
104h	4	"Port-Command List Base Address Upper 32-bits (PxCLBU0)—Offset 104h" on page 1979	00000000h
108h	4	"Port-FIS Base Address (PxFB0)—Offset 108h" on page 1980	00000000h
10Ch	4	"Port-FIS Base Address Upper 32-bits (PxFBU0)—Offset 10Ch" on page 1980	00000000h
110h	4	"Port-Interrupt Status (PxIS0)—Offset 110h" on page 1980	00000000h
114h	4	"Port-Interrupt Enable (PxIE0)—Offset 114h" on page 1982	00000000h
118h	4	"Port-Command (PxCMD0)—Offset 118h" on page 1984	00000004h
120h	4	"Port-Task File Data (PxTFD0)—Offset 120h" on page 1986	0000007Fh
124h	4	"Port-Signature (PxSIG0)—Offset 124h" on page 1987	FFFFFFFFh
128h	4	"Port-Serial ATA Status (PxSSTS0)—Offset 128h" on page 1987	00000000h
12Ch	4	"Port-Serial ATA Control (PxSCTL0)—Offset 12Ch" on page 1988	00000000h
130h	4	"Port-Serial ATA Error (PxSERR0)—Offset 130h" on page 1989	00000000h
134h	4	"Port-Serial ATA Active (PxSACT0)—Offset 134h" on page 1990	00000000h
138h	4	"Port-Commands Issued (PxCIO)—Offset 138h" on page 1990	00000000h
144h	4	"Port-Device Sleep (PxDEVSLP0)—Offset 144h" on page 1991	1E022852h
180h	4	"Port-Command List Base Address (PxCLB1)—Offset 180h" on page 1992	00000000h
184h	4	"Port-Command List Base Address Upper 32-bits (PxCLBU1)—Offset 184h" on page 1992	00000000h
188h	4	"Port-FIS Base Address (PxFB1)—Offset 188h" on page 1992	00000000h
18Ch	4	"Port-FIS Base Address Upper 32-bits (PxFBU1)—Offset 18Ch" on page 1993	00000000h
190h	4	"Port-Interrupt Status (PxIS1)—Offset 190h" on page 1993	00000000h
194h	4	"Port-Interrupt Enable (PxIE1)—Offset 194h" on page 1995	00000000h
198h	4	"Port-Command (PxCMD1)—Offset 198h" on page 1996	00000004h
1A0h	4	"Port-Task File Data (PxTFD1)—Offset 1A0h" on page 1999	0000007Fh
1A4h	4	"Port-Signature (PxSIG1)—Offset 1A4h" on page 1999	FFFFFFFFh
1A8h	4	"Port-Serial ATA Status (PxSSTS1)—Offset 1A8h" on page 2000	00000000h



Table 196. Summary of SATA AHCI Memory Mapped I/O Registers—ABAR (Continued)

Offset	Size	Register ID—Description	Default Value
1ACh	4	"Port-Serial ATA Control (PxSCTL1)—Offset 1ACh" on page 2001	00000000h
1B0h	4	"Port-Serial ATA Error (PxSERR1)—Offset 1B0h" on page 2001	00000000h
1B4h	4	"Port-Serial ATA Active (PxSACT1)—Offset 1B4h" on page 2003	00000000h
1B8h	4	"Port-Commands Issued (PxCI1)—Offset 1B8h" on page 2003	00000000h
1C4h	4	"Port-Device Sleep (PxDEVSLP1)—Offset 1C4h" on page 2003	1E022852h
580h	4	"Enclosure Management Message Format (EM_MF)—Offset 580h" on page 2004	00000000h
584h	4	"Enclosure Management LED (EM_LED)—Offset 584h" on page 2005	00000000h

17.8.1 HBA Capabilities (GHC_CAP)—Offset 0h

This register indicates basic capabilities of the HBA to driver software. The RWO bits in this register are only cleared upon Backbone Reset.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GHC_CAP: [ABAR] + 0h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h


Default: DF20FF02h

31	28	24	20	16	12	8	4	0
1	1	0	1	1	1	1	1	0
1	1	0	1	1	1	1	1	0
S64A	SCQA	SNNTF	SMPS	SSS	SALP	SAL	SCLO	ISS
								SNZO
								SAM
								SMP
								FBSS
								PMD
								SSC
								PSC
								NCS
								CCCS
								EMS
								SXS
								NP

Bit Range	Default & Access	Description
31	1h RW/O	Supports 64-bit Addressing (S64A): Indicates the S-ATA controller can access 64-bit data structures. The 32-bit upper bits of the port DMA Descriptor, the PRD Base, and each PRD entry are read/write.
30	1h RW/O	Supports Native Command Queuing Acceleration (SCQA): Indicates the SATA controller supports Serial-ATA Native Command Queuing. The HBA will handle DMA Setup FISes in hardware, including support for auto-activate optimization through the FIS.
29	0h RO	Supports SNotification Register (SNNTF): When set to 1, indicates that the HBA supports the PxSNNTF (SNotification) register and its associated functionality. When cleared to 0, the HBA does not support the PxSNNTF (SNotification) register and its associated functionality.
28	1h RW/O	Supports Mechanical Presence Switch (SMPS): When set to 1, the HBA supports mechanical presence switches on its ports for use in hot plug operations. When cleared to 0, this function is not supported. This value is loaded by the BIOS prior to OS initialization.
27	1h RW/O	Supports Staggered Spin-up (SSS): Indicates whether the S-ATA controller supports staggered spin-up on its ports, for use in balancing power spikes. This value is loaded by platform BIOS prior to OS initialization.
26	1h RW/O	Supports Aggressive Link Power Management (SALP): Indicates the S-ATA controller supports auto-generating link requests to the partial or slumber states when there are no commands to process. When cleared to 0, software shall treat the PxCMD.ALPE and PxCMD.ASP bits as reserved.



Bit Range	Default & Access	Description
25	1h RW/O	Supports Activity LED (SAL): Indicates the S-ATA controller supports a single output pin (SATALED#) which indicates activity.
24	1h RW/O	Supports Command List Override (SCLO): When set to 1, indicates that the HBA supports the PxCMD.CLO bit and its associated function. When cleared to 0, The HBA is not capable of clearing the BSY and DRQ bits in the Status register in order to issue software reset if these bits are still set from a previous operation.
23:20	2h RW/O	Interface Speed Support (ISS): Indicates the maximum speed the S-ATA controller can support on its ports. These encodings match the system software programmable PxSCTL.DET.SPD field. 0000 = Reserved; 0001 = Gen 1 (1.5 Gbps); 0010 = Gen 2 (3 Gbps); 0011 = Gen 3 (6 Gbps); 0100 - 1111 = Reserved.
19	0h RO	Supports Non-Zero DMA Offsets (SNZO): Reserved as per AHCI 1.3
18	0h RW/O	Supports AHCI mode only (SAM): The SATA controller may optionally support AHCI access mechanism only. A value of 0 indicates that in addition to the native AHCI mechanism (via ABAR), the SATA controller implements a legacy, task-file based register interface such as SFF-8038i. A value of 1 indicates that the SATA controller does not implement a legacy, task-file based register interface.
17	0h RO	Supports Port Multiplier (SMP): Not supported.
16	0h RO	FIS-based Switching Supported (FBSS): Not supported.
15	1h RO	PIO Multiple DRQ Block (PMD): If set to 1, the HBA supports multiple DRQ block data transfers for the PIO command protocol.
14	1h RW/O	Slumber State Capable (SSC): The SATA controller supports the slumber state.
13	1h RW/O	Partial State Capable (PSC): The SATA controller supports the partial state.
12:8	1Fh RO	Number of Command Slots (NCS): 1Fh indicating support for 32 slots.
7	0h RO	Command Completion Coalescing Supported (CCCS): When set to 1, indicates that the HBA supports command completion coalescing. When command completion coalescing is supported, the HBA has implemented the CCC_CTL and the CCC_PORTS global HBA registers. When cleared to 0, indicates that the HBA does not support command completion coalescing and the CCC_CTL and CCC_PORTS global HBA registers are not implemented.
6	0h RO	Enclosure Management Supported (EMS): Not supported
5	0h RW/O	Supports External SATA (SXS): When set to 1, indicates that the HBA has one or more Serial ATA ports that has a signal only connector that is externally accessible. If this bit is set, software may refer to the PxCMD.ESP bit to determine whether a specific port has its signal connector externally accessible as a signal only connector (i.e. power is not part of that connector). When the bit is cleared to 0, indicates that the HBA has no Serial ATA ports that have a signal only connector externally accessible.
4:0	02h RO	Number of Ports (NP): 0's based value indicating the maximum number of ports supported. Note that the number of ports indicated in this field may be more than the number of ports indicated in the PI register. Number of ports shall be dependent on MAP.SC and PCIe/SATA muxing configuration where if ANY of these parameter disable a particular port then that port is disabled and not counted. The maximum number of ports supported by SIP is 2 and the least is 0 (i.e. Function Disable). In the case of 0 port configuration, the value of NP is a don't care (while implementation has it fixed as 07h). Any combination in between is supported by SATA host controller. Indicates the number of supported ports.



17.8.2 Global HBA Control (GHC)—Offset 4h

This register controls various global actions of the HBA.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GHC: [ABAR] + 4h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31		28				24				20				16				12				8				4				0	
0		0		0		0		0		0		0		0		0		0		0		0		0		0		0			
AE		RSVD0																								MRSM		IE		HR	

Bit Range	Default & Access	Description
31	0h RW	AHCI Enable (AE): When set, indicates that an AHCI driver is loaded and communication to the HBA shall be via AHCI mechanisms. This can be used by an HBA that supports both legacy mechanisms (such as SFF-8038i) and AHCI to know when the HBA is running under an AHCI driver. When set, software shall only talk to the HBA using AHCI. The HBA will not have to allow command processing via both AHCI and legacy mechanisms. When cleared, software will only communicate with the HBA using legacy mechanisms. Software shall set this bit to 1 before accessing other AHCI registers. Note: The implementation of this bit is dependent upon the value of the CAP.SAM bit. If CAP.SAM is 0, then GHC.AE should be RW and shall have a reset value of 0. If CAP.SAM is 1, then AE shall be read only and shall have a reset value of 1.
30:3	0b RO	RSVD0: Reserved
2	0h RO	MSI Revert to Single Message (MRSM): When set to 1 by hardware, indicates that the HBA requested more than one MSI vector but has reverted to using the first vector only. When this bit is cleared to 0, the HBA has not reverted to single MSI mode (i.e. hardware is already in single MSI mode, software has allocated the number of messages requested, or hardware is sharing interrupt vectors if MC.MME (MC.MMC). The HBA may revert to single MSI mode when the number of vectors allocated by the host is less than the number requested. This bit shall only be set to 1 when the following conditions hold: MC.MSIE = 1 (MSI is enabled); MC.MMC = 0 (multiple messages requested); MC.MME = 0 (more than one message allocated); MC.MME != MC.MMC (messages allocated not equal to number requested). When this bit is set to 1, single MSI mode operation is in use and software is responsible for clearing bits in the IS register to clear interrupts. This bit shall be cleared to 0 by hardware when any of the four conditions stated is false. This bit is also cleared to 0 when MC.MSIE = 1 and MC.MME = 0h. In this case, the hardware has been programmed to use single MSI mode, and is not reverting to that mode. The HBA shall always revert to single MSI mode when the number of vectors allocated by the host is less than the number requested. Value of MRSM is a don't care when GHC.HR=1.
1	0h RW	Interrupt Enable (IE): This global bit enables interrupts from the HBA. When cleared (reset default), all interrupt sources from all ports are disabled. When set, interrupts are enabled.
0	0h RW/1S	HBA Reset (HR): When set by SW, this bit causes an internal reset of the HBA. All state machines that relate to data transfers and native command queuing will return to an idle condition, and all ports will be re-initialized via COMRESET. When the HBA has performed the reset action, it will reset this bit to 0. A software write of 0 will have no effect. For a description on which bits are reset when this bit is set, see the AHCI specification, section 10.3.3.



Bit Range	Default & Access	Description
3	1h RO	Supports RAID Platform ID Reporting (SRPIR): If set to 1, then indicates that the RAID Platform ID is reported via ABAR + C0h. Set to 0 if this ID is not reported via MMIO space.
2:0	0b RO	RSVD1: Reserved

17.8.8 Vendor Specific Capabilities (VS_CAP)—Offset A4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

VS_CAP: [ABAR] + A4h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 018002FEh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	1	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	1	0
1	1	1	1	1	1	1	1	0
PNRRO				RSVD0	MSL			PNMBRE

Bit Range	Default & Access	Description
31:16	0180h RO	PCIe NAND Remapped Register Offset (PNRRO): Specifies the DWORD offset within ABAR as to where the PCIe NAND AHCI BAR register space is remapped. Only valid when PNABRE = 1. This places the start of the PCIe NAND AHCI BAR register space at ABAR + 600h
15:12	0b RO	RSVD0: Reserved
11:1	17Fh RW	Memory Space Limit. (MSL): This field specifies the size of the remapped memory space for the PCIe NAND device. It is a 0-based field. Memory BAR offset from 0 to MSL of the PCIe NAND device are remapped under the integrated AHCI controller memory space. The remapped offset into the AHCI memory space and the value programmed in this field must not exceed the allocated 2k AHCI memory space of the integrated AHCI controller. The reset default of this field is 17Fh (i.e. bit[11:1] = 0010111111b) which specifies the size of the remapped memory space as 384 bytes.
0	0h RW/O	PCIe NAND Memory BAR Remapped Enable (PNMBRE): Set to 1 if a PCIe NAND device is present and remapping of its memory BAR register space is enabled. Cleared to 0 if there is no PCIe NAND device present or the remapping of its memory BAR register space is disabled.

17.8.9 RAID Platform ID (RPID)—Offset C0h

This register is used by the Intel Matrix Storage Manager OROM to match the features supported by the OROM with the platform on which the OROM is executing. This prevents the use of an OROM designed for newer chipsets from being use on older chipsets as this could reduce up-sell potential.


Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RPID: [ABAR] + C0h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h



17.8.14 Port-FIS Base Address (PxFB0)—Offset 108h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxFB0: [ABAR] + 108h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
FB							RSVD0	

Bit Range	Default & Access	Description
31:8	0000000h RW	FIS Base Address (FB): Indicates the 32-bit base for received FISes. This address must be 256-byte aligned as indicated by bits 31:08 being read/write. When FIS-based switching is in use, this structure is 4KB in length and the address shall be 4KB aligned. Note that these bits are not reset on a HBA reset.
7:0	0b RO	RSVD0: Reserved

17.8.15 Port-FIS Base Address Upper 32-bits (PxFBU0)—Offset 10Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxFBU0: [ABAR] + 10Ch

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
FBU								

Bit Range	Default & Access	Description
31:0	00000000h RW	FIS Base Address Upper (FBU): Indicates the upper 32-bits for the received FIS base for this port. Note that these bits are not reset on a HBA reset.

17.8.16 Port-Interrupt Status (PxIS0)—Offset 110h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

PxIS0: [ABAR] + 110h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h



31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
CPDS	TFES	HBFS	HBDS	IFS	INFS	RSVD0	OFS	IPMS	PRCS	RSVD1																		DMPS	PCS	DPS	UFS	SDBS	DSS	PSS	DHRS

Bit Range	Default & Access	Description
31	0h RO	Cold Presence Detect Status (CPDS): The SATA controller does not support cold presence detect.
30	0h RW/1C	Task File Error Status (TFES): This bit is set whenever the status register is updated by the device and the error bit (bit 0 of the Status field in the received FIS) is set.
29	0h RW/1C	Host Bus Fatal Error Status (HBFS): Indicates that the HBA encountered a host bus error that it cannot recover from, such as a bad software pointer. In PCI, such an indication would be a target or master abort.
28	0h RW/1C	Host Bus Data Error Status (HBDS): Indicates that the HBA encountered a data error (uncorrectable ECC / parity) when reading from or writing to system memory.
27	0h RW/1C	Interface Fatal Error Status (IFS): Indicates that the HBA encountered an error on the SATA interface which caused the transfer to stop.
26	0h RW/1C	Interface Non-fatal Error Status (INFS): Indicates that the HBA encountered an error on the SATA interface but was able to continue operation.
25	0b RO	RSVD0: Reserved
24	0h RW/1C	Overflow Status (OFS): Indicates that the HBA received more bytes from a device than was specified in the PRD table for the command.
23	0h RW/1C	Incorrect Port Multiplier Status (IPMS): Not supported
22	0h RO	PhyRdy Change Status (PRCS): When set to one indicates the internal PhyRdy signal changed state. This bit reflects the state of PxSERR.DIAG.N. This bit is RO and is only cleared when PxSERR.DIAG.N is cleared.
21:8	0b RO	RSVD1: Reserved
7	0h RW/1C	Device Mechanical Presence Status (DMPS): When set, indicates that a platform mechanical presence switch has been opened or closed, which may lead to a change in the connection state of the device. This bit is only valid in systems that support mechanical presence switch (CAP.SMPS and PxCMD.MPSP are set).
6	0h RO	Port Connect Change Status (PCS): 1=Change in Current Connect Status. 0=No change in Current Connect Status. This bit reflects the state of PxSERR.DIAG.X. This bit is only cleared when PxSERR.DIAG.X is cleared.
5	0h RW/1C	Descriptor Processed (DPS): A PRD with the I. bit set has transferred all of its data.
4	0h RO	Unknown FIS Interrupt (UFS): When set to 1 indicates that an unknown FIS was received and has been copied into system memory. This bit is cleared to 0 by software clearing the PxSERR.DIAG.F bit to 0. Note that this bit does not directly reflect the PxSERR.DIAG.F bit. PxSERR.DIAG.F is set immediately when an unknown FIS is detected, whereas this bit is set when the FIS is posted to memory. Software should wait to act on an unknown FIS until this bit is set to 1 or the two bits may become out of sync.
3	0h RW/1C	Set Device Bits Interrupt (SDBS): A Set Device Bits FIS has been received with the I. bit set and has been copied into system memory.
2	0h RW/1C	DMA Setup FIS Interrupt (DSS): A DMA Setup FIS has been received with the I. bit set and has been copied into system memory.



Bit Range	Default & Access	Description
1	0h RW/1C	PIO Setup FIS Interrupt (PSS): A PIO Setup FIS has been received with the I. bit set, it has been copied into system memory, and the data related to that FIS has been transferred. This bit shall be set even if the data transfer resulted in an error.
0	0h RW/1C	Device to Host Register FIS Interrupt (DHRS): A D2H register FIS has been received with the I. bit set, and has been copied into system memory.

17.8.17 Port-Interrupt Enable (PxIE0)—Offset 114h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxIE0: [ABAR] + 114h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0				0				0				0				0				0				0				0				0			
CPDS	TFEE	HBFE	HBDE	IFE	INFE	RSVD0	OFE	IPME	PRCE	RSVD1										DMPE	PCE	DPE	UFE	SDBE	DSE	PSE	DHRE								

Bit Range	Default & Access	Description
31	0h RO	Cold Presence Detect Enable (CPDS): The SATA controller does not support cold presence detect.
30	0h RW	Task File Error Enable (TFEE): When set, GHC.IE is set, and POS.TFES is set, the HBA shall generate an interrupt.
29	0h RW	Host Bus Fatal Error Enable (HBFE): When set, GHC.IE is set, and P0IS.HBFS is set, the HBA shall generate an interrupt.
28	0h RW	Host Bus Data Error Enable (HBDE): When set, GHC.IE is set, and P0IS.HBDS is set, the HBA shall generate an interrupt.
27	0h RW	Interface Fatal Error Enable (IFE): When set, GHC.IE is set, and P0IS.IFS is set, the HBA shall generate an interrupt.
26	0h RW	Interface Non-fatal Error Enable (INFE): When set, GHC.IE is set, and P0IS.INFS is set, the HBA shall generate an interrupt.
25	0b RO	RSVD0: Reserved
24	0h RW	Overflow Enable (OFE): When set, and GHC.IE and P0IS.OFS are set, the HBA shall generate an interrupt.
23	0h RW	Incorrect Port Multiplier Enable (IPME): When set, and GHC.IE and P0IS.IPMS are set, the HBA shall generate an interrupt.
22	0h RW	PhyRdy Change Interrupt Enable (PRCE): When set, and GHC.IE is set, and PxIS.PRCS is set, the HBA shall generate an interrupt.
21:8	0b RO	RSVD1: Reserved
7	0h RW	Device Mechanical Enable (DMPE): When set, and P0IS.DMPS is set, the HBA shall generate an interrupt.



Bit Range	Default & Access	Description
6	0h RW	Port Change Interrupt Enable (PCE): When set, GHC.IE is set, and P0IS.PCS is set, the HBA shall generate an interrupt.
5	0h RW	Descriptor Processed Interrupt Enable (DPE): When set, GHC.IE is set, and P0IS.DPS is set, the HBA shall generate an interrupt.
4	0h RW	Unknown FIS Interrupt Enable (UFE): When set, GHC.IE is set, and PxIS.UFS is set to 1, the HBA shall generate an interrupt.
3	0h RW	Set Device Bits FIS Interrupt Enable (SDBE): When set, GHC.IE is set, and P0IS.SDBS is set, the HBA shall generate an interrupt.
2	0h RW	DMA Setup FIS Interrupt Enable (DSE): When set, GHC.IE is set, and P0IS.DSS is set, the HBA shall generate an interrupt.
1	0h RW	PIO Setup FIS Interrupt Enable (PSE): When set, GHC.IE is set, and P0IS.PSS is set, the HBA shall generate an interrupt.
0	0h RW	Device to Host Register FIS Interrupt Enable (DHRE): When set, GHC.IE is set, and P0IS.DHRS is set, the HBA shall generate an interrupt.



17.8.18 Port-Command (PxCMD0)—Offset 118h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxCMD0: [ABAR] + 118h


ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000004h

31				28				24				20				16				12				8				4				0	
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0		
ICC				ASP	ALPE	DLAE	ATAPI	APSTE	FBSCP	ESP	CPD	MPSP	HPCP	PMA	RSVD0	CR	FR	MPSS	CCS				RSVD1	PSP	APSE	FRE	CLO	POD	SUD	ST			

Bit Range	Default & Access	Description
31:28	0h RW	Interface Communication Control (ICC): This is a four bit field which can be used to control reset and power states of the interface. If the Link layer is currently in the L_IDLE state, writes to this field shall cause the HBA to initiate a transition to the interface power management state requested. If the Link layer is not currently in the L_IDLE state, writes to this field shall have no effect. Fh -9h Reserved. 8h DEVSLP: This shall cause the HBA to assert the DEVSLP signal associated with the port; the HBA shall ignore the DEVSLP Idle Timeout value specified by PxDEVSLP.DITO. Software shall only request DEVSLP when the interface is in an idle state (i.e. PxCI is cleared to 0h and PxSACT is cleared to 0h); if the interface is not idle at the time the register is written, then the HBA takes no action and the interface remains in its current state. If PxCAP2.DESO is set to '1' and PxSSTS.IPM is not set to '6h', then the HBA takes no action and the interface remains in its current state. Additionally, the HBA shall not assert the DEVSLP signal until PHYRDY has been achieved (after a previous de-assertion). 7h Reserved 6h Slumber: This shall cause the HBA to request a transition of the interface to the Slumber state. The SATA device may reject the request and the interface shall remain in its current state. 5h-3h Reserved. 2h Partial: This shall cause the HBA to request a transition of the interface to the Partial state. The SATA device may reject the request and the interface shall remain in its current state. 1h Active: This shall cause the HBA to request a transition of the interface into the active state. If the requested transition is from the DEVSLP state, then the HBA shall wait until PxDEVSLP.DMAT has expired before de-asserting the DEVSLP signal. 0h No-Op / Idle: When software reads this value, it indicates the HBA is ready to accept a new interface control command, although the transition to the previously selected state may not yet have occurred. When system software writes a non-reserved value other than No-Op (0h), the HBA shall perform the action and update this field back to Idle (0h). If software writes to this field to change the state to a state the link is already in (i.e. interface is in the active state and a request is made to go to the active state), the HBA shall take no action and return this field to Idle. If the interface is in a low power state and the software wants to transition to a different low power state, software must first bring the link to active and then initiate the transition to the desired low power state (with the exception of DEVSLP). The transition to DEVSLP may occur from any other state if CAP2.DESO is cleared to '0'. If CAP2.DESO is set to '1', then DEVSLP may only be transitioned to if the link is in Slumber.
27	0h RW	Aggressive Slumber Partial (ASP): When set to 1, and the ALPE bit is set, the HBA shall aggressively enter Slumber state when it clears a bit in the PxCI or PxSACT register and the register values are 0h. When cleared, and the ALPE bit is set, the HBA will aggressively enter Partial state when it clears a bit in the PxCI or PxSACT register and the register values are both 0h. If CAP.SALP is cleared to 0, software shall treat this bit as reserved.
26	0h RW	Aggressive Link Power Management Enable (ALPE): When set, the HBA will aggressively enter a lower link power state (Partial or Slumber) based upon the setting of the ASP bit.
25	0h RW	Drive LED on ATAPI Enable (DLAE): When set, the HBA will drive the LED pin active for commands regardless of the state of PxCMD.ATAPI. When cleared, the HBA will only drive the LED pin active for commands if PxCMD.ATAPI is set to 0. This bit is set by software



Bit Range	Default & Access	Description
24	0h RW	Device is ATAPI (ATAPI): When set, the connected device is an ATAPI device. This bit is used by the HBA to control whether or not to generate the desktop LED when commands are active.
23	0h RW	Automatic Partial to Slumber Transitions Enabled (APSTE): When set to 1, the HBA may perform Automatic Partial to Slumber Transitions. When cleared to 0 - the port shall not perform Automatic Partial to Slumber Transitions. Software shall only set this bit to 1 - if CAP2.APST is set to 1; if CAP2.APST is cleared to 0 - software shall treat this bit as reserved.
22	0h RO	FIS-based Switching Capable Port (FBSCP): The SATA controller does not support FIS-Based Switching.
21	0h RW/O	External SATA Port (ESP): When set to 1, indicates that this port is routed externally and will be used with an external SATA device. When set to 1, CAP.SXS must also be set to 1. When cleared (0), indicates that this port is not routed externally and supports internal SATA devices only. If ESP is set to 1, then the port may experience hot plug events.
20	0h RO	Cold Presence Detection (CPD): The SATA controller does not support cold presence detect.
19	0h RW/O	Mechanical Presence Switch Attached to Port (MPSP): If set to 1, the platform supports a mechanical presence switch attached to this port. If cleared to 0, the platform does not support a mechanical presence switch attached to this port.
18	0h RW/O	Hot Plug Capable Port (HPCP): This indicates whether this port is connected to a device which can be hot plugged. SATA by definition is hot-pluggable, but not all platforms are constructed to allow the device to be removed (it may be screwed into the chassis, for example). This bit can be used by system software to indicate a feature such as eject device to the end-user.
17	0h RO	Port Multiplier Attached (PMA): Not supported
16	0b RO	RSVD0: Reserved
15	0h RO	Command List Running (CR): When this bit is set it indicates that the command list DMA engine for the port is running.
14	0h RO	FIS Receive Running (FR): When this bit is set it indicates that the FIS Receive DMA engine for the port is running.
13	0h RO	Mechanical Presence Switch State (MPSS): The MPSS bit reports the state of a mechanical presence switch attached to this port. If CAP.SMPS is set to 1 and the mechanical presence switch is closed then this bit is cleared to 0. If CAP.SMPS is set to 1 and the mechanical presence switch is open then this bit is set to 1. If CAP.SMPS is set to 0 then this bit is cleared to 0. Software should only use this bit if both CAP.SMPS and PxCMD.MPSP are set to 1.
12:8	00h RO	Current Command Slot (CCS): Indicates the current command slot the HBA is processing. This field is valid when the PxCMD.ST bit is set, and is constantly updated by the HBA. This field can be updated as soon as the HBA recognizes an active command slot, or at some point soon after when it begins processing the command. When PxCMD.ST transitions from a 1 to a 0, the HBA will reset this field to 0. After PxCMD.ST transitions from 0 to 1, the highest priority slot to issue from next is command slot 0. After the first command has been issued, the highest priority slot to issue from next is PxCMD.CCS + 1. For example, after the HBA has issued its first command, if PxCMD.CCS = 0h and PxCI is set to 3h, the next command that will be issued is from command slot 1.
7	0b RO	RSVD1: Reserved
6	0h RO	PHYSLP Present (PSP): If set to 1, the platform supports PHYSLP on this port. If cleared to 0, the platform does not support PHYSLP on this port. This bit may only be set to 1 if CAP2.SPS is set to 1.

17.8.19 Port-Task File Data (PxTFD0)—Offset 120h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxTFD0: [ABAR] + 120h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 0000007Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0				ERR				STS_BSY
								STS_RSVD0
								STS_DRQ
								STS_RSVD1
								STS_FRR

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:8	00h RO	Error (ERR): Contains the latest copy of the task file error register.



Bit Range	Default & Access	Description
11:8	0h RO	Interface Power Management (IPM): Indicates the current interface state. 0h = Device not present or communication not established. 1h = Interface in active state. 2h = Interface in PARTIAL power management state. 6h = Interface in SLUMBER power management state. 8h = PHYSLP asserted. All other values reserved. This field reflects the interface power management state for both device and host initiated power management. Note: If an automatic partial to slumber transition occurs, PxSSTS.IPM shall reflect that the host has entered slumber (PxSSTS.IPM = 6h.)
7:4	0h RO	Current Interface Speed (SPD): Indicates the negotiated interface communication speed. 0h = Device not present or communication not established. 1h = Generation 1 communication rate negotiated. 2h = Generation 2 communication rate negotiated. 3h = Generation 3 communication rate negotiated. All other values reserved
3:0	0h RO	Device Detection (DET): Indicates the interface device detection and Phy state. 0h = No device detected and Phy communication not established. 1h = Device presence detected but Phy communication not established. 3h = Device presence detected and Phy communication established. 4h = Phy in offline mode as a result of the interface being disabled or running in a BIST loopback mode. All other values reserved. Note that, while the true reset default value of this register is 0h, the value read from this register depends on drive presence and the point in time within the initialization process when the register is read. Note: The means by which the implementation determines device presence may be vendor specific. However, device presence shall always be indicated anytime a COMINIT signal is received.

17.8.22 Port-Serial ATA Control (PxSCTL0)—Offset 12Ch

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxSCTL0: [ABAR] + 12Ch

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
RSVD0												PMP				SPM				IPM				SPD				DET							

Bit Range	Default & Access	Description
31:20	0b RO	RSVD0: Reserved
19:16	0h RW	Port Multiplier Port (PMP): This field is not used by AHCI.
15:12	0h RW	Select Power Management (SPM): This field is not used by AHCI.
11:8	0h RW	Interface Power Management Transitions Allowed (IPM): Indicates which power states the HBA is allowed to transition to. If an interface power management state is not allowed via this register field, the HBA will not initiate that state and the HBA will PMNAKP any request from the device to enter that state. 0h No interface restrictions 1h Transitions to the PARTIAL state disabled 2h Transitions to the SLUMBER state disabled 3h Transitions to both PARTIAL and SLUMBER states disabled 4h Transitions to the DEVSLP power management state are disabled 5h Transitions to the Partial and DEVSLP power management states are disabled 6h Transitions to the Slumber and DEVSLP power management states are disabled 7h Transitions to the Partial, Slumber and DEVSLP power management states are disabled All other values reserved



Bit Range	Default & Access	Description
15:0	0000h RW/1C	Error (ERR): The ERR field contains error information for use by host software in determining the appropriate response to the error condition. If one or more of bits 11:8 of this register are set, the controller will stop the current transfer. 15:12 Reserved 11 Internal Error (E): The SATA controller failed due to a master or target abort when attempting to access system memory. 10 Protocol Error (P): A violation of the Serial ATA protocol was detected. 9 Persistent Communication or Data Integrity Error (C): A communication error that was not recovered occurred that is expected to be persistent. Persistent communications errors may arise from faulty interconnect with the device, from a device that has been removed or has failed, or a number of other causes. 8 Transient Data Integrity Error (T): A data integrity error occurred that was not recovered by the interface. 7:2 Reserved 1 Recovered Communications Error (M): Communications between the device and host was temporarily lost but was re-established. This can arise from a device temporarily being removed, from a temporary loss of Phy synchronization, or from other causes and may be derived from the PhyNRdy signal between the Phy and Link layers. 0 Recovered Data Integrity Error (I): A data integrity error occurred that was recovered by the interface through a retry operation or other recovery action.

17.8.24 Port-Serial ATA Active (PxSACT0)—Offset 134h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxSACT0: [ABAR] + 134h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	00000000h RW/1S	Device Status (DS): System software sets this bit for native command queuing commands prior to setting the PxCI.CI bit in the same command slot entry. This field is cleared via the Set Device Bits FIS.

17.8.25 Port-Commands Issued (PxCI0)—Offset 138h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxCI0: [ABAR] + 138h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Description
31:0	00000000h RW	Commands Issued (CI): This field is set by software to indicate to the HBA that a command has been built in system memory for a command slot and may be sent to the device. When the HBA receives a FIS which clears the BSY, ERR, and DRQ bits for the command, it clears the corresponding bit in this register for that command slot. Bits in this field shall only be set to 1 by software when PxCMD.ST is set to 1.

17.8.26 Port-Device Sleep (PxDEVSLP0)—Offset 144h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxDEVSLP0: [ABAR] + 144h


ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 1E022852h

31	28	24	20	16	12	8	4	0						
0	0	0	1	1	1	0	0	0	0	0	0	0	1	0
RSVD0	DM	DITO				MDAT	DETO			DSP	ADSE			

Bit Range	Default & Access	Description
31:29	0b RO	RSVD0: Reserved
28:25	Fh RW/O	DITO Multiplier (DM): 0's based value that specifies the DITO multiplier that the HBA applies to the specified DITO value, effectively extending the range of DITO from 1ms to 16368ms. A value of 0h indicates a multiplier of 1. A maximum multiplier of 16 may be applied. The HBA computes the total idle timeout as a product of DM and DITO (i.e. DITO actual = DITO * DM).
24:15	004h RW	DEVSLP Idle Timeout (DITO): This field specifies the amount of the time (in approximate 1ms granularity) that the HBA shall wait before driving the DEVSLP signal.
14:10	0Ah RW	DEVSLP Minimum Assertion Time (MDAT): This field specifies the minimum amount of time (in 1ms granularity) that the HBA must assert the DEVSLP signal before it may be de-asserted. The nominal value is 10ms and the minimum is 1ms depending on device identification information.
9:2	14h RW	DEVSLP Exit Timeout (DETO): This field specifies the maximum duration (in approximate 1ms granularity) from DEVSLP de-assertion until the device is ready to accept OOB. The nominal value is 20ms while the max value is 255ms depending on device identification information.
1	1h RW/O	DEVSLP Present (DSP): If set to 1, the platform supports DEVSLP on this port. If cleared to 0, the platform does not support DEVSLP on this port.
0	0h RW	Aggressive DEVSLP Enable (ADSE): When this bit is cleared to 0, the HBA does not enter DEVSLP unless software directed via PxCMD.ICC. This bit shall only be set to 1 if PxDEVSLP.DSP is set to 1. If this bit is set to 1 and software clears the bit to 0, then the HBA shall de-assert the DEVSLP signal if asserted.



Bit Range	Default & Access	Description
31	0h RO	Cold Presence Detect Status (CPDS): The SATA controller does not support cold presence detect.
30	0h RW/1C	Task File Error Status (TFES): This bit is set whenever the status register is updated by the device and the error bit (bit 0 of the Status field in the received FIS) is set.
29	0h RW/1C	Host Bus Fatal Error Status (HBFS): Indicates that the HBA encountered a host bus error that it cannot recover from, such as a bad software pointer. In PCI, such an indication would be a target or master abort.
28	0h RW/1C	Host Bus Data Error Status (HBDS): Indicates that the HBA encountered a data error (uncorrectable ECC / parity) when reading from or writing to system memory.
27	0h RW/1C	Interface Fatal Error Status (IFS): Indicates that the HBA encountered an error on the SATA interface which caused the transfer to stop.
26	0h RW/1C	Interface Non-fatal Error Status (INFS): Indicates that the HBA encountered an error on the SATA interface but was able to continue operation.
25	0b RO	RSVD0: Reserved
24	0h RW/1C	Overflow Status (OFS): Indicates that the HBA received more bytes from a device than was specified in the PRD table for the command.
23	0h RW/1C	Incorrect Port Multiplier Status (IPMS): Not supported
22	0h RO	PhyRdy Change Status (PRCS): When set to one indicates the internal PhyRdy signal changed state. This bit reflects the state of PxSERR.DIAG.N. This bit is RO and is only cleared when PxSERR.DIAG.N is cleared.
21:8	0b RO	RSVD1: Reserved
7	0h RW/1C	Device Mechanical Presence Status (DMPS): When set, indicates that a platform mechanical presence switch has been opened or closed, which may lead to a change in the connection state of the device. This bit is only valid in systems that support mechanical presence switch (CAP.SMPS and PxCMD.MPSP are set).
6	0h RO	Port Connect Change Status (PCS): 1=Change in Current Connect Status. 0=No change in Current Connect Status. This bit reflects the state of PxSERR.DIAG.X. This bit is only cleared when PxSERR.DIAG.X is cleared.
5	0h RW/1C	Descriptor Processed (DPS): A PRD with the I. bit set has transferred all of its data.
4	0h RO	Unknown FIS Interrupt (UFS): When set to 1 indicates that an unknown FIS was received and has been copied into system memory. This bit is cleared to 0 by software clearing the PxSERR.DIAG.F bit to 0. Note that this bit does not directly reflect the PxSERR.DIAG.F bit. PxSERR.DIAG.F is set immediately when an unknown FIS is detected, whereas this bit is set when the FIS is posted to memory. Software should wait to act on an unknown FIS until this bit is set to 1 or the two bits may become out of sync.
3	0h RW/1C	Set Device Bits Interrupt (SDBS): A Set Device Bits FIS has been received with the I. bit set and has been copied into system memory.
2	0h RW/1C	DMA Setup FIS Interrupt (DSS): A DMA Setup FIS has been received with the I. bit set and has been copied into system memory.
1	0h RW/1C	PIO Setup FIS Interrupt (PSS): A PIO Setup FIS has been received with the I. bit set, it has been copied into system memory, and the data related to that FIS has been transferred. This bit shall be set even if the data transfer resulted in an error.
0	0h RW/1C	Device to Host Register FIS Interrupt (DHRS): A D2H register FIS has been received with the I. bit set, and has been copied into system memory.



17.8.32 Port-Interrupt Enable (PxIE1)—Offset 194h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxIE1: [ABAR] + 194h


ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
CPDS	TFEE	HBFE	HBDE	IFE	INFE	RSVD0	OFE	IPME	PRCE	RSVD1										DMPE	PCE	DPE	UFE	SDBE	DSE	PSE	DHRE								

Bit Range	Default & Access	Description
31	0h RO	Cold Presence Detect Enable (CPDS): The SATA controller does not support cold presence detect.
30	0h RW	Task File Error Enable (TFEE): When set, GHC.IE is set, and P0IS.TFES is set, the HBA shall generate an interrupt.
29	0h RW	Host Bus Fatal Error Enable (HBFE): When set, GHC.IE is set, and P0IS.HBFS is set, the HBA shall generate an interrupt.
28	0h RW	Host Bus Data Error Enable (HBDE): When set, GHC.IE is set, and P0IS.HBDS is set, the HBA shall generate an interrupt.
27	0h RW	Interface Fatal Error Enable (IFE): When set, GHC.IE is set, and P0IS.IFS is set, the HBA shall generate an interrupt.
26	0h RW	Interface Non-fatal Error Enable (INFE): When set, GHC.IE is set, and P0IS.INFS is set, the HBA shall generate an interrupt.
25	0b RO	RSVD0: Reserved
24	0h RW	Overflow Enable (OFE): When set, and GHC.IE and P0IS.OFS are set, the HBA shall generate an interrupt.
23	0h RW	Incorrect Port Multiplier Enable (IPME): When set, and GHC.IE and P0IS.IPMS are set, the HBA shall generate an interrupt.
22	0h RW	PhyRdy Change Interrupt Enable (PRCE): When set, and GHC.IE is set, and PxIS.PRCS is set, the HBA shall generate an interrupt.
21:8	0b RO	RSVD1: Reserved
7	0h RW	Device Mechanical Enable (DMPE): When set, and P0IS.DMPS is set, the HBA shall generate an interrupt.
6	0h RW	Port Change Interrupt Enable (PCE): When set, GHC.IE is set, and P0IS.PCS is set, the HBA shall generate an interrupt.
5	0h RW	Descriptor Processed Interrupt Enable (DPE): When set, GHC.IE is set, and P0IS.DPS is set, the HBA shall generate an interrupt.
4	0h RW	Unknown FIS Interrupt Enable (UFE): When set, GHC.IE is set, and PxIS.UFS is set to 1, the HBA shall generate an interrupt.
3	0h RW	Set Device Bits FIS Interrupt Enable (SDBE): When set, GHC.IE is set, and P0IS.SDBS is set, the HBA shall generate an interrupt.



Bit Range	Default & Access	Description
2	0h RW	DMA Setup FIS Interrupt Enable (DSE): When set, GHC.IE is set, and P0IS.DSS is set, the HBA shall generate an interrupt.
1	0h RW	PIO Setup FIS Interrupt Enable (PSE): When set, GHC.IE is set, and P0IS.PSS is set, the HBA shall generate an interrupt.
0	0h RW	Device to Host Register FIS Interrupt Enable (DHRE): When set, GHC.IE is set, and P0IS.DHRS is set, the HBA shall generate an interrupt.

17.8.33 Port-Command (PxCMD1)—Offset 198h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxCMD1: [ABAR] + 198h


ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h


Default: 00000004h

31	28				24				20				16				12				8				4				0		
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
ICC				ASP	ALPE	DLAE	ATAPI	APSTE	FBSCP	ESP	CPD	MPSP	HPCP	PMA	RSVD0	CR	FR	MPSS	CCS				RSVD1	PSP	APSE	FRE	CLO	POD	SUD	ST	

Bit Range	Default & Access	Description
31:28	0h RW	Interface Communication Control (ICC): This is a four bit field which can be used to control reset and power states of the interface. If the Link layer is currently in the L_IDLE state, writes to this field shall cause the HBA to initiate a transition to the interface power management state requested. If the Link layer is not currently in the L_IDLE state, writes to this field shall have no effect. Fh -9h Reserved. 8h DEVSLP: This shall cause the HBA to assert the DEVSLP signal associated with the port; the HBA shall ignore the DEVSLP Idle Timeout value specified by PxDEVSLP.DITO. Software shall only request DEVSLP when the interface is in an idle state (i.e. PxCI is cleared to 0h and PxSACT is cleared to 0h); if the interface is not idle at the time the register is written, then the HBA takes no action and the interface remains in its current state. If PxCAP2.DESO is set to '1' and PxSSTS.IPM is not set to '6h', then the HBA takes no action and the interface remains in its current state. Additionally, the HBA shall not assert the DEVSLP signal until PHYRDY has been achieved (after a previous de-assertion). 7h Reserved 6h Slumber: This shall cause the HBA to request a transition of the interface to the Slumber state. The SATA device may reject the request and the interface shall remain in its current state. 5h-3h Reserved. 2h Partial: This shall cause the HBA to request a transition of the interface to the Partial state. The SATA device may reject the request and the interface shall remain in its current state. 1h Active: This shall cause the HBA to request a transition of the interface into the active state. If the requested transition is from the DEVSLP state, then the HBA shall wait until PxDEVSLP.DMAT has expired before de-asserting the DEVSLP signal. 0h No-Op / Idle: When software reads this value, it indicates the HBA is ready to accept a new interface control command, although the transition to the previously selected state may not yet have occurred. When system software writes a non-reserved value other than No-Op (0h), the HBA shall perform the action and update this field back to Idle (0h). If software writes to this field to change the state to a state the link is already in (i.e. interface is in the active state and a request is made to go to the active state), the HBA shall take no action and return this field to Idle. If the interface is in a low power state and the software wants to transition to a different low power state, software must first bring the link to active and then initiate the transition to the desired low power state (with the exception of DEVSLP). The transition to DEVSLP may occur from any other state if CAP2.DESO is cleared to '0'. If CAP2.DESO is set to '1', then DEVSLP may only be transitioned to if the link is in Slumber.



Bit Range	Default & Access	Description
27	0h RW	Aggressive Slumber Partial (ASP): When set to 1, and the ALPE bit is set, the HBA shall aggressively enter Slumber state when it clears a bit in the PxCI or PxSACT register and the register values are 0h. When cleared, and the ALPE bit is set, the HBA will aggressively enter Partial state when it clears a bit in the PxCI or PxSACT register and the register values are both 0h. If CAP.SALP is cleared to 0, software shall treat this bit as reserved.
26	0h RW	Aggressive Link Power Management Enable (ALPE): When set, the HBA will aggressively enter a lower link power state (Partial or Slumber) based upon the setting of the ASP bit.
25	0h RW	Drive LED on ATAPI Enable (DLAE): When set, the HBA will drive the LED pin active for commands regardless of the state of PxCMD.ATAPI. When cleared, the HBA will only drive the LED pin active for commands if PxCMD.ATAPI is set to 0. This bit is set by software
24	0h RW	Device is ATAPI (ATAPI): When set, the connected device is an ATAPI device. This bit is used by the HBA to control whether or not to generate the desktop LED when commands are active.
23	0h RW	Automatic Partial to Slumber Transitions Enabled (APSTE): When set to 1, the HBA may perform Automatic Partial to Slumber Transitions. When cleared to 0 - the port shall not perform Automatic Partial to Slumber Transitions. Software shall only set this bit to 1 - if CAP2.APST is set to 1; if CAP2.APST is cleared to 0 - software shall treat this bit as reserved.
22	0h RO	FIS-based Switching Capable Port (FBSCP): The SATA controller does not support FIS-Based Switching.
21	0h RW/O	External SATA Port (ESP): When set to 1, indicates that this port is routed externally and will be used with an external SATA device. When set to 1, CAP.SXS must also be set to 1. When cleared (0), indicates that this port is not routed externally and supports internal SATA devices only. If ESP is set to 1, then the port may experience hot plug events.
20	0h RO	Cold Presence Detection (CPD): The SATA controller does not support cold presence detect.
19	0h RW/O	Mechanical Presence Switch Attached to Port (MPSP): If set to 1, the platform supports a mechanical presence switch attached to this port. If cleared to 0, the platform does not support a mechanical presence switch attached to this port.
18	0h RW/O	Hot Plug Capable Port (HPCP): This indicates whether this port is connected to a device which can be hot plugged. SATA by definition is hot-pluggable, but not all platforms are constructed to allow the device to be removed (it may be screwed into the chassis, for example). This bit can be used by system software to indicate a feature such as eject device to the end-user.
17	0h RO	Port Multiplier Attached (PMA): Not supported
16	0b RO	RSVD0: Reserved
15	0h RO	Command List Running (CR): When this bit is set it indicates that the command list DMA engine for the port is running.
14	0h RO	FIS Receive Running (FR): When this bit is set it indicates that the FIS Receive DMA engine for the port is running.
13	0h RO	Mechanical Presence Switch State (MPSS): The MPSS bit reports the state of a mechanical presence switch attached to this port. If CAP.SMPS is set to 1 and the mechanical presence switch is closed then this bit is cleared to 0. If CAP.SMPS is set to 1 and the mechanical presence switch is open then this bit is set to 1. If CAP.SMPS is set to 0 then this bit is cleared to 0. Software should only use this bit if both CAP.SMPS and PxCMD.MPSP are set to 1.



Bit Range	Default & Access	Description
12:8	00h RO	Current Command Slot (CCS): Indicates the current command slot the HBA is processing. This field is valid when the PxCMD.ST bit is set, and is constantly updated by the HBA. This field can be updated as soon as the HBA recognizes an active command slot, or at some point soon after when it begins processing the command. When PxCMD.ST transitions from a 1 to a 0, the HBA will reset this field to 0. After PxCMD.ST transitions from 0 to 1, the highest priority slot to issue from next is command slot 0. After the first command has been issued, the highest priority slot to issue from next is PxCMD.CCS + 1. For example, after the HBA has issued its first command, if PxCMD.CCS = 0h and PxCI is set to 3h, the next command that will be issued is from command slot 1.
7	0b RO	RSVD1: Reserved
6	0h RO	PHYSLP Present (PSP): If set to 1, the platform supports PHYSLP on this port. If cleared to 0, the platform does not support PHYSLP on this port. This bit may only be set to 1 if CAP2.SPS is set to 1.
5	0h RW	Aggressive PHYSLP Enable (APSE): This bit is read/write for HBAs that support aggressive PHYSLP management (CAP2.SAPM == 1). This bit is read-only for HBAs that do not support aggressive PHYSLP management (CAP2.SPS == 0). When this bit is set to 1, the HBA shall assert the PHYSLP signal after the port has been idle (PxCI == 0h and PxSACT == 0h) for the amount of time specified by the GHC.PITO register. When this bit is cleared to 0, the HBA does not enter PHYSLP unless software directed via PxCMD.ICC. This bit shall only be set to 1 if PxCMD.PSP is set to 1. If this bit is set to 1 and software clears the bit to 0, then the HBA shall de-assert the PHYSLP signal if asserted.
4	0h RW	FIS Receive Enable (FRE): When set, the HBA may post received FISes into the FIS receive area pointed to by PxFB and PxFBU. When cleared, received FISes are not accepted by the HBA, except for the first D2H register FIS after the initialization sequence.
3	0h RW/1S	Command List Override (CLO): Setting this bit to 1 causes PxTFD.STS.BSY and PxTFD.STS.DRQ to be cleared to 0. This allows a software reset to be transmitted to the device regardless of whether the BSY and DRQ bits are still set in the PxTFD.STS register. The HBA sets this bit to 0 when PxTFD.STS.BSY and PxTFD.STS.DRQ have been cleared to 0. A write to this register with a value of 0 shall have no effect.
2	1h RO	Power On Device (POD): The SATA controller does not support cold presence detect.
1	0h RW	Spin-Up Device (SUD): This bit is read/write for HBAs that support staggered spin-up via CAP.SSS. This bit is read only 1 for HBAs that do not support staggered spin-up. On an edge detect from 0 to 1, the HBA shall start a COMRESET initialization sequence to the device. Clearing this bit causes no action on the interface. Clearing this bit to 0 does not cause any OOB signal to be sent on the interface. When this bit is cleared to 0 and PxSCTL.DET = 0h, the HBA will enter listen mode.
0	0h RW	Start (ST): When set, the HBA may process the command list. When cleared, the HBA may not process the command list. Whenever this bit is changed from a 0 to a 1, the HBA starts processing the command list at entry 0. Whenever this bit is changed from a 1 to a 0, the PxCI and PxSACT register is cleared by the HBA upon the HBA putting the controller into an idle state. PxTFD shall be updated also.

17.8.34 Port-Task File Data (PxTFD1)—Offset 1A0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxTFD1: [ABAR] + 1A0h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 0000007Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0				ERR				STS_BSY
								STS_RSVD0
								STS_DRQ
								STS_RSVD1
								STS_FRR

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:8	00h RO	Error (ERR): Contains the latest copy of the task file error register.
7	0h RO	Status Busy (STS_BSY): Status - Indicates the interface is busy.
6:4	7h RO	Status Rsvd0 (STS_RSVD0): Status - Not Applicable.
3	1h RO	Status Drq (STS_DRQ): Status - Indicates a data transfer is requested.
2:1	3h RO	Status Rsvd1 (STS_RSVD1): Status - Not Applicable.
0	1h RO	Status Err (STS_ERR): Status - Indicates an error during the transfer.

17.8.35 Port-Signature (PxSIG1)—Offset 1A4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxSIG1: [ABAR] + 1A4h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: FFFFFFFFh

[illegible]

Bit Range	Default & Access	Description
31:0	FFFFFFFFh RO	Signature (SIG): Contains the signature received from a device on the first D2H Register FIS.



17.8.36 Port-Serial ATA Status (PxSSTS1)—Offset 1A8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxSSTS1: [ABAR] + 1A8h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0						IPM	SPD	DET

Bit Range	Default & Access	Description
31:12	0b RO	RSVD0: Reserved
11:8	0h RO	Interface Power Management (IPM): Indicates the current interface state 0h = Device not present or communication not established. 1h = Interface in active state. 2h = Interface in PARTIAL power management state. 6h = Interface in SLUMBER power management state. 8h = PHYSLP asserted. All other values reserved. This field reflects the interface power management state for both device and host initiated power management. Note: If an automatic partial to slumber transition occurs, PxSSTS.IPM shall reflect that the host has entered slumber (PxSSTS.IPM = 6h.)
7:4	0h RO	Current Interface Speed (SPD): Indicates the negotiated interface communication speed. 0h = Device not present or communication not established. 1h = Generation 1 communication rate negotiated. 2h = Generation 2 communication rate negotiated. 3h = Generation 3 communication rate negotiated. All other values reserved
3:0	0h RO	Device Detection (DET): Indicates the interface device detection and Phy state. 0h = No device detected and Phy communication not established. 1h = Device presence detected but Phy communication not established. 3h = Device presence detected and Phy communication established. 4h = Phy in offline mode as a result of the interface being disabled or running in a BIST loopback mode. All other values reserved. Note that, while the true reset default value of this register is 0h, the value read from this register depends on drive presence and the point in time within the initialization process when the register is read. Note: The means by which the implementation determines device presence may be vendor specific. However, device presence shall always be indicated anytime a COMINIT signal is received.



17.8.37 Port-Serial ATA Control (PxSCTL1)—Offset 1ACh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxSCTL1: [ABAR] + 1ACh

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
		RSVD0		PMP	SPM	IPM	SPD	DET

Bit Range	Default & Access	Description
31:20	0b RO	RSVD0: Reserved
19:16	0h RW	Port Multiplier Port (PMP): This field is not used by AHCI.
15:12	0h RW	Select Power Management (SPM): This field is not used by AHCI.
11:8	0h RW	Interface Power Management Transitions Allowed (IPM): Indicates which power states the HBA is allowed to transition to. If an interface power management state is not allowed via this register field, the HBA will not initiate that state and the HBA will PMNAKP any request from the device to enter that state. 0h No interface restrictions 1h Transitions to the PARTIAL state disabled 2h Transitions to the SLUMBER state disabled 3h Transitions to both PARTIAL and SLUMBER states disabled 4h Transitions to the DEVSLP power management state are disabled 5h Transitions to the Partial and DEVSLP power management states are disabled 6h Transitions to the Slumber and DEVSLP power management states are disabled 7h Transitions to the Partial, Slumber and DEVSLP power management states are disabled All other values reserved
7:4	0h RW	Speed Allowed (SPD): Indicates the highest allowable speed of the interface. 0h No speed negotiation restrictions. 1h Limit speed negotiation to Generation 1 communication rate. 2h Limit speed negotiation to a rate not greater than Generation 2 communication rate. 3h Limit speed negotiation to a rate not greater than Generation 3 communication rate. All other values reserved. Note: If software changes SPD after port has been enabled, software is required to perform a port reset via DET=1h.
3:0	0h RW	Device Detection Initialization (DET): Controls HBA's device detection and interface initialization. 0h No device detection or initialization action requested. 1h Perform interface communication initialization sequence to establish communication. This is functionally equivalent to a hard reset and results in the interface being reset and communications reinitialized. While this field is 1h, COMRESET is continuously transmitted on the interface. Software should leave the DET field set to 1h for a minimum of 1 millisecond to ensure that a COMRESET is sent on the interface. 4h Disable the Serial ATA interface and put Phy in offline mode. All other values reserved. This field may only be changed when PxCMD.ST is '0'. Changing this field while the HBA is running results in undefined behavior. When PxCMD.ST is set to '1', this field should have a value of 0h. It is permissible to implement any of the Serial ATA defined behaviors for transmission of COMRESET when PxSCTL.DET = 1h

17.8.38 Port-Serial ATA Error (PxSERR1)—Offset 1B0h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

PxSERR1: [ABAR] + 1B0h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DIAG				ERR				

Bit Range	Default & Access	Description
31:16	0000h RW/1C	Diagnostics (DIAG): Contains diagnostic error information for use by diagnostic software in validating correct operation or isolating failure modes. Bit Field 31:27 Reserved 26 Exchanged (X): When set to one this bit indicates that a change in device presence has been detected since the last time this bit was cleared. The means by which the implementation determines that the device presence has changed is vendor specific. This bit shall always be set to one anytime a COMINIT signal is received. This bit is reflected in the POIS.PCS bit. 25 Unrecognized FIS Type (F): Indicates that one or more FISs were received by the Transport layer with good CRC, but had a type field that was not recognized. 24 Transport state transition error (T): Indicates that an error has occurred in the transition from one state to another within the Transport layer since the last time this bit was cleared. 23 Link Sequence Error (S): Indicates that one or more Link state machine error conditions were encountered. The Link Layer state machine defines the conditions under which the link layer detects an erroneous transition. 22 Handshake Error (H): Indicates that one or more R_ERR handshake response was received in response to frame transmission. Such errors may be the result of a CRC error detected by the recipient, a disparity or 8b/10b decoding error, or other error condition leading to a negative handshake on a transmitted frame. 21 CRC Error (C): Indicates that one or more CRC errors occurred with the Link Layer. 20 Disparity Error (D): This field is not used by AHCI. 19 10B to 8B Decode Error (B): Indicates that one or more 10B to 8B decoding errors occurred. 18 Comm Wake (W): Indicates that a Comm Wake signal was detected by the Phy. 17 Phy Internal Error (I): Indicates that the Phy detected some internal error. 16 PhyRdy Change (N): When set to 1 this bit indicates that the internal PhyRdy signal changed state since the last time this bit was cleared. The state of this bit is reflected in the PxIS.PRCs interrupt status bit and an interrupt will be generated if enabled.
15:0	0000h RW/1C	Error (ERR): The ERR field contains error information for use by host software in determining the appropriate response to the error condition. If one or more of bits 11:8 of this register are set, the controller will stop the current transfer. 15:12 Reserved 11 Internal Error (E): The SATA controller failed due to a master or target abort when attempting to access system memory. 10 Protocol Error (P): A violation of the Serial ATA protocol was detected. 9 Persistent Communication or Data Integrity Error (C): A communication error that was not recovered occurred that is expected to be persistent. Persistent communications errors may arise from faulty interconnect with the device, from a device that has been removed or has failed, or a number of other causes. 8 Transient Data Integrity Error (T): A data integrity error occurred that was not recovered by the interface. 7:2 Reserved 1 Recovered Communications Error (M): Communications between the device and host was temporarily lost but was re-established. This can arise from a device temporarily being removed, from a temporary loss of Phy synchronization, or from other causes and may be derived from the PhyNRdy signal between the Phy and Link layers. 0 Recovered Data Integrity Error (I): A data integrity error occurred that was recovered by the interface through a retry operation or other recovery action.



17.8.39 Port-Serial ATA Active (PxSACT1)—Offset 1B4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxSACT1: [ABAR] + 1B4h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	00000000h RW/1S	Device Status (DS): System software sets this bit for native command queuing commands prior to setting the PxCI.CI bit in the same command slot entry. This field is cleared via the Set Device Bits FIS.

17.8.40 Port-Commands Issued (PxCI1)—Offset 1B8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxC11: [ABAR] + 1B8h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	00000000h RW	Commands Issued (CI): This field is set by software to indicate to the HBA that a command has been built in system memory for a command slot and may be sent to the device. When the HBA receives a FIS which clears the BSY, ERR, and DRQ bits for the command, it clears the corresponding bit in this register for that command slot. Bits in this field shall only be set to 1 by software when PxCMD.ST is set to 1.

17.8.41 Port-Device Sleep (PxDEVSLP1)—Offset 1C4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PxDEVSLP1: [ABAR] + 1C4h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 1E022852h

31				28				24				20				16				12				8				4				0	
0	0	0	1	1	1	1	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	1	0	1	0	0	1	0			
RSVD0				DM				DITO								MDAT				DETO								DSP		ADSF			

Bit Range	Default & Access	Description
31:29	0b RO	RSVD0: Reserved
28:25	Fh RW/O	DITO Multiplier (DM): 0's based value that specifies the DITO multiplier that the HBA applies to the specified DITO value, effectively extending the range of DITO from 1ms to 16368ms. A value of 0h indicates a multiplier of 1. A maximum multiplier of 16 may be applied. The HBA computes the total idle timeout as a product of DM and DITO (i.e. DITO actual = DITO * DM).
24:15	004h RW	DEVSLP Idle Timeout (DITO): This field specifies the amount of the time (in approximate 1ms granularity) that the HBA shall wait before driving the DEVSLP signal.
14:10	0Ah RW	DEVSLP Minimum Assertion Time (MDAT): This field specifies the minimum amount of time (in 1ms granularity) that the HBA must assert the DEVSLP signal before it may be de-asserted. The nominal value is 10ms and the minimum is 1ms depending on device identification information.
9:2	14h RW	DEVSLP Exit Timeout (DETO): This field specifies the maximum duration (in approximate 1ms granularity) from DEVSLP de-assertion until the device is ready to accept OOB. The nominal value is 20ms while the max value is 255ms depending on device identification information.
1	1h RW/O	DEVSLP Present (DSP): If set to 1, the platform supports DEVSLP on this port. If cleared to 0, the platform does not support DEVSLP on this port.
0	0h RW	Aggressive DEVSLP Enable (ADSE): When this bit is cleared to 0, the HBA does not enter DEVSLP unless software directed via PxCMD.ICC. This bit shall only be set to 1 if PxDEVSLP.DSP is set to 1. If this bit is set to 1 and software clears the bit to 0, then the HBA shall de-assert the DEVSLP signal if asserted.

17.8.42 Enclosure Management Message Format (EM_MF)—Offset 580h

This register is not implemented in VLV.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

EM MF: [ABAR] + 580h

ABAR Type: PCI Configuration Register (Size: 32 bits)

ABAR Reference: [B:0, D:19, F:0] + 24h

Default: 00000000h

Diagram illustrating the 32-bit CSVD format. The top row shows bit positions 31, 28, 24, 20, 16, 12, 8, 4, and 0. The bottom row shows the bit fields: 0 0 0 0, 0 0 0 0, 0 0 0 0, 0 0 0 0, 0 0 0 0, 0 0 0 0, 0 0 0 0, 0 0 0 0, and 0. The label 'CSVD' is centered below the bit fields.

Bit Range	Default & Access	Description
31:0	0h RO	RSVD: Reserved.



17.9 SATA Primary Read Command IO Registers

Table 197. Summary of SATA Primary Read Command I/O Registers—PCMDIDEBA

Offset	Size	Register ID—Description	Default Value
1h	1	"Primary Channel Error register (P_ERROR)—Offset 1h" on page 2006	00h
2h	1	"Primary Channel Sector Count register (P_SECTOR_COUNT)—Offset 2h" on page 2006	00h
3h	1	"Primary Channel Sector Number register (P_SECTOR_NUMBER)—Offset 3h" on page 2007	00h
4h	1	"Primary Channel Cylinder Low register (P_CYL_LOW)—Offset 4h" on page 2008	00h
5h	1	"Primary Channel Cylinder High register (P_CYL_HIGH)—Offset 5h" on page 2008	00h
6h	1	"Primary Channel Device register (P_DRIVE_HEAD)—Offset 6h" on page 2009	00h
7h	1	"Primary Channel Status register (P_STATUS)—Offset 7h" on page 2009	00h

17.9.1 Primary Channel Error register (P_ERROR)—Offset 1h

Access Method

Type: I/O Register
(Size: 8 bits)

P_ERROR: [PCMDIDEBA] + 1h

PCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCMDIDEBA Reference: [B:0, D:19, F:0] + FCh

Default: 00h

7	4	0
0	0	0
P_ERROR_1		
Bit Range	Default & Access	Description
7:0	00h RW	Error (P_ERROR_1): Error.

17.9.2 Primary Channel Sector Count register (P_SECTOR_COUNT)—Offset 2h

Access Method


Type: I/O Register
(Size: 8 bits)

P_SECTOR_COUNT: [PCMDIDEBA] + 2h

PCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCMDIDEBA Reference: [B:0, D:19, F:0] + FCh

Default: 00h



Bit Range	Default & Access	Description
7:0	00h RW	Sector Count (P_SECTOR_COUNT_1): Sector Count.

17.9.3 Primary Channel Sector Number register (P_SECTOR_NUMBER)—Offset 3h

Access Method


Type: I/O Register
(Size: 8 bits)

P_SECTOR_NUMBER: [PCMDIDEBA] + 3h

PCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCMDIDEBA Reference: [B:0, D:19, F:0] + FCh

Default: 00h



Bit Range	Default & Access	Description
7:0	00h RW	Sector Number (P_SECTOR_NUMBER_1): Sector Number.



17.9.4 Primary Channel Cylinder Low register (P_CYL_LOW)—Offset 4h

Access Method


Type: I/O Register
(Size: 8 bits)

P_CYL_LOW: [PCMDIDEBA] + 4h

PCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCMDIDEBA Reference: [B:0, D:19, F:0] + FCh

Default: 00h



Bit Range	Default & Access	Description
7:0	00h RW	Cylinder Low (P_CYL_LOW_1): Cylinder Low.

17.9.5 Primary Channel Cylinder High register (P_CYL_HIGH)—Offset 5h

Access Method


Type: I/O Register
(Size: 8 bits)

P_CYL_HIGH: [PCMDIDEBA] + 5h

PCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCMDIDEBA Reference: [B:0, D:19, F:0] + FCh

Default: 00h



Bit Range	Default & Access	Description
7:0	00h RW	Cylinder High (P_CYL_HIGH_1): Cylinder High.



17.9.6 Primary Channel Device register (P_DRIVE_HEAD)—Offset 6h

Access Method

Type: I/O Register
(Size: 8 bits)

P_DRIVE_HEAD: [PCMDIDEBA] + 6h

PCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCMDIDEBA Reference: [B:0, D:19, F:0] + FCh

Default: 00h

7	0	0	0	4	0	0	0	0	0
RSVD0				P_DRIVE_HEAD_1	RSVD1				

Bit Range	Default & Access	Description
7:5	0b RO	RSVD0: Reserved
4	0h RW	Device (P_DRIVE_HEAD_1): Device.
3:0	0b RO	RSVD1: Reserved

17.9.7 Primary Channel Status register (P_STATUS)—Offset 7h

Access Method

Type: I/O Register
(Size: 8 bits)

P_STATUS: [PCMDIDEBA] + 7h


PCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCMDIDEBA Reference: [B:0, D:19, F:0] + FCh

Default: 00h

7	0	0	0	4	0	0	0	0	0
P_STATUS_BSY	P_STATUS_DRDY	P_STATUS_DF	RSVD0	P_STATUS_DRQ	RSVD1	P_STATUS_ERR_CHK			

Bit Range	Default & Access	Description
7	0h RW	BUSY (P_STATUS_BSY): BUSY.



Bit Range	Default & Access	Description
6	0h RW	Device Ready (P_STATUS_DRDY): Device Ready.
5	0h RW	Device Fault/Stream Error (P_STATUS_DF): Device Fault/Stream Error.
4	0b RO	RSVD0: Reserved
3	0h RW	Data Request (P_STATUS_DRQ): Data Request.
2:1	0b RO	RSVD1: Reserved
0	0h RW	ERR/CHK (P_STATUS_ERR_CHK): ERR/CHK.



17.10 SATA Primary Write Control IO Registers

Table 198. Summary of SATA Primary Write Control I/O Registers—PCTLIDEBA

Offset	Size	Register ID—Description	Default Value
2h	1	"Primary Channel Device Control register (P_DEVICE_CTRL)—Offset 2h" on page 2011	00h

17.10.1 Primary Channel Device Control register (P_DEVICE_CTRL)—Offset 2h

Access Method

Type: I/O Register
(Size: 8 bits)

P_DEVICE_CTRL: [PCTLIDEBA] + 2h

PCTLIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCTLIDEBA Reference: [B:0, D:19, F:0] + 104h

Default: 00h

7	4	0
0	0	0
RSVD0		RSVD1
P_DEVICE_CTRL_SRST		P_DEVICE_CTRL_nIEN

Bit Range	Default & Access	Description
7:3	0b RO	RSVD0: Reserved
2	0h RW	Soft Reset (P_DEVICE_CTRL_SRST): Soft Reset.
1	0h RW	Interrupt Enable, Negative Logic (P_DEVICE_CTRL_nIEN): Interrupt Enable, Negative Logic.
0	0b RO	RSVD1: Reserved



17.11 SATA Primary Read Control IO Registers

Table 199. Summary of SATA Primary Read Control I/O Registers—PCTLIDEBA

Offset	Size	Register ID—Description	Default Value
2h	1	"Primary Channel Alternate Status register (P_ALT_STATUS)—Offset 2h" on page 2012	00h

17.11.1 Primary Channel Alternate Status register (P_ALT_STATUS)—Offset 2h

Access Method

Type: I/O Register
(Size: 8 bits)

P_ALT_STATUS: [PCTLIDEBA] + 2h

PCTLIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCTLIDEBA Reference: [B:0, D:19, F:0] + 104h

Default: 00h

7	0	0	0	4	0	0	0	0
P_ALT_STATUS_BSY	P_ALT_STATUS_DRDY	P_ALT_STATUS_DF	RSVD0	P_ALT_STATUS_DRQ	RSVD1	P_ALT_STATUS_ERR_CHK		

Bit Range	Default & Access	Description
7	0h RW	BUSY (P_ALT_STATUS_BSY): BUSY.
6	0h RW	Device Ready (P_ALT_STATUS_DRDY): Device Ready.
5	0h RW	Device Fault/Stream Error (P_ALT_STATUS_DF): Device Fault/Stream Error.
4	0b RO	RSVD0: Reserved
3	0h RW	Data Request (P_ALT_STATUS_DRQ): Data Request.
2:1	0b RO	RSVD1: Reserved
0	0h RW	ERR/CHK (P_ALT_STATUS_ERR_CHK): ERR/CHK.



17.12 SATA Primary Write Control IO Registers

Table 200. Summary of SATA Primary Write Control I/O Registers—PCTLIDEBA

Offset	Size	Register ID—Description	Default Value
2h	1	"Primary Channel Device Control register (P_DEVICE_CTRL)—Offset 2h" on page 2013	00h

17.12.1 Primary Channel Device Control register (P_DEVICE_CTRL)—Offset 2h

Access Method

Type: I/O Register
(Size: 8 bits)

P_DEVICE_CTRL: [PCTLIDEBA] + 2h

PCTLIDEBA Type: PCI Configuration Register (Size: 32 bits)

PCTLIDEBA Reference: [B:0, D:19, F:0] + 104h

Default: 00h

7	4	0
0	0	0
RSVD0		RSVD1
P_DEVICE_CTRL_SRST		P_DEVICE_CTRL_nIEN

Bit Range	Default & Access	Description
7:3	0b RO	RSVD0: Reserved
2	0h RW	Soft Reset (P_DEVICE_CTRL_SRST): Soft Reset.
1	0h RW	Interrupt Enable, Negative Logic (P_DEVICE_CTRL_nIEN): Interrupt Enable, Negative Logic.
0	0b RO	RSVD1: Reserved



17.13 SATA Secondary Read Command IO Registers

Table 201. Summary of SATA Secondary Read Command I/O Registers—SCMDIDEBA

Offset	Size	Register ID—Description	Default Value
1h	1	"Secondary Channel Error register (S_ERROR)—Offset 1h" on page 2014	00h
2h	1	"Secondary Channel Sector Count register (S_SECTOR_COUNT)—Offset 2h" on page 2015	00h
3h	1	"Secondary Channel Sector Number register (S_SECTOR_NUMBER)—Offset 3h" on page 2015	00h
4h	1	"Secondary Channel Cylinder Low register (S_CYL_LOW)—Offset 4h" on page 2016	00h
5h	1	"Secondary Channel Cylinder High register (S_CYL_HIGH)—Offset 5h" on page 2016	00h
6h	1	"Secondary Channel Device register (S_DRIVE_HEAD)—Offset 6h" on page 2017	00h
7h	1	"Secondary Channel Status register (S_STATUS)—Offset 7h" on page 2018	00h

17.13.1 Secondary Channel Error register (S_ERROR)—Offset 1h

Access Method

Type: I/O Register
(Size: 8 bits)

S_ERROR: [SCMDIDEBA] + 1h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h

7	4	0
0	0	0
S_ERROR_1		
Bit Range	Default & Access	Description
7:0	00h RW	Error (S_ERROR_1): Error.



17.13.2 Secondary Channel Sector Count register (S_SECTOR_COUNT)—Offset 2h

Access Method

Type: I/O Register
(Size: 8 bits)

S_SECTOR_COUNT: [SCMDIDEBA] + 2h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
S_SECTOR_COUNT_1									

Bit Range	Default & Access	Description
7:0	00h RW	Sector Count (S_SECTOR_COUNT_1): Sector Count.

17.13.3 Secondary Channel Sector Number register (S_SECTOR_NUMBER)—Offset 3h

Access Method

Type: I/O Register
(Size: 8 bits)

S_SECTOR_NUMBER: [SCMDIDEBA] + 3h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
S_SECTOR_NUMBER_1									

Bit Range	Default & Access	Description
7:0	00h RW	Sector Number (S_SECTOR_NUMBER_1): Sector Number.



17.13.4 Secondary Channel Cylinder Low register (S_CYL_LOW)—Offset 4h

Access Method


Type: I/O Register
(Size: 8 bits)

S_CYL_LOW: [SCMDIDEBA] + 4h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h



Bit Range	Default & Access	Description
7:0	00h RW	Cylinder Low (S_CYL_LOW_1): Cylinder Low.

17.13.5 Secondary Channel Cylinder High register (S_CYL_HIGH)—Offset 5h

Access Method


Type: I/O Register
(Size: 8 bits)

S_CYL_HIGH: [SCMDIDEBA] + 5h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h



Bit Range	Default & Access	Description
7:0	00h RW	Cylinder High (S_CYL_HIGH_1): Cylinder High.



17.13.6 Secondary Channel Device register (S_DRIVE_HEAD)—Offset 6h

Access Method

Type: I/O Register
(Size: 8 bits)

S_DRIVE_HEAD: [SCMDIDEBA] + 6h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
RSVD0			S_DRIVE_HEAD_1	RSVD1			

Bit Range	Default & Access	Description
7:5	0b RO	RSVD0: Reserved
4	0h RW	Device (S_DRIVE_HEAD_1): Device.
3:0	0b RO	RSVD1: Reserved



17.13.7 Secondary Channel Status register (S_STATUS)—Offset 7h

Access Method

Type: I/O Register
(Size: 8 bits)

S_STATUS: [SCMDIDEBA] + 7h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h

7	0	0	0	4	0	0	0	0
S_STATUS_BSY	S_STATUS_DRDY	S_STATUS_DF	RSVD0	S_STATUS_DRQ	RSVD1	S_STATUS_ERR_CHK		

Bit Range	Default & Access	Description
7	0h RW	BUSY (S_STATUS_BSY): BUSY.
6	0h RW	Device Ready (S_STATUS_DRDY): Device Ready.
5	0h RW	Device Fault/Stream Error (S_STATUS_DF): Device Fault/Stream Error.
4	0b RO	RSVD0: Reserved
3	0h RW	Data Request (S_STATUS_DRQ): Data Request.
2:1	0b RO	RSVD1: Reserved
0	0h RW	ERR/CHK (S_STATUS_ERR_CHK): ERR/CHK.



17.14 SATA Secondary Write Command IO Registers

Table 202. Summary of SATA Secondary Write Command I/O Registers—SCMDIDEBA

Offset	Size	Register ID—Description	Default Value
1h	1	"Secondary Channel Features register (S_FEATURES)—Offset 1h" on page 2019	00h
7h	1	"Secondary Channel Command register (S_COMMAND)—Offset 7h" on page 2020	00h

17.14.1 Secondary Channel Features register (S_FEATURES)—Offset 1h

Access Method

Type: I/O Register
(Size: 8 bits)

S_FEATURES: [SCMDIDEBA] + 1h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
S_FEATURES_1									

Bit Range	Default & Access	Description
7:0	00h RW	Features (S_FEATURES_1): Features.



17.14.2 Secondary Channel Command register (S_COMMAND)—Offset 7h

Access Method

Type: I/O Register
(Size: 8 bits)

S_COMMAND: [SCMDIDEBA] + 7h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h

7	4	0
0	0	0
S_COMMAND_1		
Bit Range	Default & Access	Description
7:0	00h RW	Command (S_COMMAND_1): Command.



17.15 SATA Secondary Read Control IO Registers

Table 203. Summary of SATA Secondary Read Control I/O Registers—SCTLIDEBA

Offset	Size	Register ID—Description	Default Value
2h	1	"Secondary Channel Alternate Status register (S_ALT_STATUS)—Offset 2h" on page 2021	00h

17.15.1 Secondary Channel Alternate Status register (S_ALT_STATUS)—Offset 2h

Access Method

Type: I/O Register
(Size: 8 bits)

S_ALT_STATUS: [SCTLIDEBA] + 2h

SCTLIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCTLIDEBA Reference: [B:0, D:19, F:0] + 108h

Default: 00h

7	0	0	0	4	0	0	0	0
S_ALT_STATUS_BSY	S_ALT_STATUS_DRDY	S_ALT_STATUS_DF	RSVD0	S_ALT_STATUS_DRQ	RSVD1	S_ALT_STATUS_ERR_CHK		

Bit Range	Default & Access	Description
7	0h RW	BUSY (S_ALT_STATUS_BSY): BUSY.
6	0h RW	Device Ready (S_ALT_STATUS_DRDY): Device Ready.
5	0h RW	Device Fault/Stream Error (S_ALT_STATUS_DF): Device Fault/Stream Error.
4	0b RO	RSVD0: Reserved
3	0h RW	Data Request (S_ALT_STATUS_DRQ): Data Request.
2:1	0b RO	RSVD1: Reserved
0	0h RW	ERR/CHK (S_ALT_STATUS_ERR_CHK): ERR/CHK.



17.16 SATA Secondary Write Command IO Registers

Table 204. Summary of SATA Secondary Write Command I/O Registers—SCMDIDEBA

Offset	Size	Register ID—Description	Default Value
1h	1	"Secondary Channel Features register (S_FEATURES)—Offset 1h" on page 2022	00h
7h	1	"Secondary Channel Command register (S_COMMAND)—Offset 7h" on page 2023	00h

17.16.1 Secondary Channel Features register (S_FEATURES)—Offset 1h

Access Method

Type: I/O Register
(Size: 8 bits)

S_FEATURES: [SCMDIDEBA] + 1h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
S_FEATURES_1									

Bit Range	Default & Access	Description
7:0	00h RW	Features (S_FEATURES_1): Features.



17.16.2 Secondary Channel Command register (S_COMMAND)—Offset 7h

Access Method

Type: I/O Register
(Size: 8 bits)

S_COMMAND: [SCMDIDEBA] + 7h

SCMDIDEBA Type: PCI Configuration Register (Size: 32 bits)

SCMDIDEBA Reference: [B:0, D:19, F:0] + 100h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
S_COMMAND_1									
Bit Range	Default & Access	Description							
7:0	00h RW	Command (S_COMMAND_1): Command.							



17.17 SATA Lane 0 Electrical Register Address Map

Table 205. Summary of SATA Lane 0 Electrical Message Bus Registers—0xA3 (Global Offset 2200h)

Offset	Register ID—Description	Default Value
0h	"PCS_DWORD0 (pcs_dword0)—Offset 0h" on page 2026	00010080h
4h	"PCS_DWORD1 (pcs_dword1)—Offset 4h" on page 2028	00600060h
8h	"PCS_DWORD2 (pcs_dword2)—Offset 8h" on page 2029	00000000h
Ch	"PCS_DWORD3 (pcs_dword3)—Offset Ch" on page 2030	5515ACAAh
10h	"PCS_DWORD4 (pcs_dword4)—Offset 10h" on page 2031	575555C1h
14h	"PCS_DWORD5 (pcs_dword5)—Offset 14h" on page 2032	00003E63h
18h	"PCS_DWORD6 (pcs_dword6)—Offset 18h" on page 2033	FFFFFFFFh
1Ch	"PCS_DWORD7 (pcs_dword7)—Offset 1Ch" on page 2034	00000009h
20h	"PCS_DWORD8 (pcs_dword8)—Offset 20h" on page 2035	000000C4h
24h	"PCS_DWORD9 (pcs_dword9)—Offset 24h" on page 2036	00000000h
28h	"PCS_DWORD10 (pcs_dword10)—Offset 28h" on page 2038	00000000h
2Ch	"PCS_DWORD11 (pcs_dword11)—Offset 2Ch" on page 2039	0F000000h
30h	"PCS_DWORD12 (pcs_dword12)—Offset 30h" on page 2041	00250F00h
34h	"PCS_DWORD13 (pcs_dword13)—Offset 34h" on page 2042	00000000h
38h	"PCS_DWORD14 (pcs_dword14)—Offset 38h" on page 2042	007A0018h
3Ch	"PCS_DWORD15 (pcs_dword15)—Offset 3Ch" on page 2044	04100300h
40h	"PCS_DWORD16 (pcs_dword16)—Offset 40h" on page 2045	01000001h
44h	"PCS_DWORD17 (pcs_dword17)—Offset 44h" on page 2047	01000001h
48h	"PCS_DWORD18 (pcs_dword18)—Offset 48h" on page 2048	00008080h
4Ch	"PCS_DWORD19 (pcs_dword19)—Offset 4Ch" on page 2049	00004F10h
50h	"PCS_DWORD20 (pcs_dword20)—Offset 50h" on page 2050	80808080h
54h	"PCS_DWORD21 (pcs_dword21)—Offset 54h" on page 2051	80808080h
58h	"PCS_DWORD22 (pcs_dword22)—Offset 58h" on page 2052	00000000h
5Ch	"PCS_DWORD23 (pcs_dword23)—Offset 5Ch" on page 2053	00180888h
60h	"PCS_DWORD24 (pcs_dword24)—Offset 60h" on page 2053	0001C020h



Type: Message Bus Register
(Size: 32 bits)

Op Codes:

0h - Read, 1h - Write

31	28	24	20	16	12	8	4	
0	0	0	0	0	0	0	0	0
reg_txcfgchange_valid_delay_3_0								
0	0	0	0	0	0	0	0	0
reg_txcfgchange_rst_delay_3_0								
0	0	0	0	0	0	0	0	0
reserved500								
0	0	0	0	0	0	0	0	0
reg_txcfgchange_width_4_0								
0	0	0	0	1	0	0	0	0
reg_txcfgchange_ovrride								
reg_tx2_soft_reset_n								
reg_txswng_clkssel								
reg_rcvdetect_ovrd								
reg_rcvdetectd								
reg_rcvdetectfinished								
reg_rcvdetect_pulse_width_ovrd								
0	0	0	0	0	0	0	0	0
reg_rcvdetect_pulse_width_2_0								
0	0	0	0	0	0	0	0	0
reg_tx1_soft_reset_n								
1	0	0	0	0	0	0	0	0
reg_tx_8b10b_bypass								
reg_tx_laneup								
reg_left_txfifo_rst_master2								
0	0	0	0	0	0	0	0	0
reg_right_txfifo_rst_master2								
0	0	0	0	0	0	0	0	0
reg_plllinksynch_ovrdn								
reg_plllinksynch_ovrd								
reg_tx1_cmoddisactiv								

Intel Atom® Processor E3800 Product Family
Datasheet
2026



Bit Range	Default & Access	Description
11	0h RW	reg_rcvdetect_pulse_width_ovrd: override enable for rcvdetect_pulse_width
10:8	0h RW	reg_rcvdetect_pulse_width_2_0: override value for rcvdetect_pulse_width
7	1h RW	reg_tx1_soft_reset_n: Active low reset to independently reset Tx lane1 in Display Port 0: Lane 1 reset 1: Lane 1 active
6	0h RW	reg_tx_8b10b_bypass: Bypass 8b10b encoder (for SAPIS etc interface.) 0 = Disable 8b/10b encoder bypass 1 = Enable 8b/10b encoder bypass
5	0h RW	reg_tx_laneup: Unused in Tx
4	0h RW	reg_left_txfifo_rst_master2: override enable = reg_lanedeskew_strap_ovrd
3	0h RW	reg_right_txfifo_rst_master2: override enable = reg_lanedeskew_strap_ovrd
2	0h RW	reg_plllinksynch_ovrden: Override enable for reg_pllinsync_ovrd 0 = Use default delay in hardware 1 = Use reg_plllinksynch_ovrd
1	0h RW	reg_plllinksynch_ovrd: override value for plllinksynch
0	0h RW	reg_tx1_cmmdisparity: Sets the initial disparity during Compliance Measurement Mode, used together with pcs_txcompliance pulse. 0 = set negative disparity 1 = set positive disparity



Type: Message Bus Register
(Size: 32 bits)

Op Codes:

0h - Read, 1h - Write

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_txfsfm_4us_delay_7_0				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
reg_txfsfm_4us_delay_11_8				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
reg_pclk_rate_1_0				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
reg_phymode_2_0				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
reg_modeovren				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
reg_datawidth				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
soft_reset_n				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
reg_digineben				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
reg_strapgroup_ovrden				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
reg_yank_timer_done_b_ovrd				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0
reg_yank_timer_done_b_ovrd_en				0	0	0	0	0
				0	0	0	0	0
				0	0	0	0	0

Intel Atom® Processor E3800 Product Family
Datasheet
2028



Bit Range	Default & Access	Description
5	1h RW	soft_reset_n : Active low soft reset override
4	0h RW	reg_diginelben : Override for near end digital loopback.
3	0h RW	reg_digifelben : Override for far end digital loopback
2	0h RW	reg_strapgroup_ovrden : Override Enable for Strap Group
1	0h RW	reg_yank_timer_done_b_ovrd : Override for yank_timer_done_b
0	0h RW	reg_yank_timer_done_b_ovrd_en : Override Enable for yank_timer_done_b

17.17.3 PCS_DWORD2 (pcs_dword2)—Offset 8h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword2: [Port: 0xA3] + (2200h + 8h)


Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_pibiasoff_delay_3_0	cri_sqdbexittimer_override_3_0	cri_sqdbentrytimer_override_5_0	reg_rxdrcgtsqsel_1_0	cri_reut_SlaveSideDataCheckingEn	cri_sqdbtimer_ovren	cri_rxpwrfsm_timer_ovren	reg_rxdidle	cri_rxrawdata_sel
				cri_dynkalign_eco3302703_mode	cri_dynkalign_eco3302703_ovren	reg_rxpwrfsm_pibiasoff_ovrride	cri_reset_kalignick	cri_ebptrrst
							cri_comdispfix	cri_forcebankhit
							cri_kalignmode_1_0	cri_skpprocdis
								cri_elasticbuffer_maskdis

Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_pibiasoff_delay_3_0 : Override value for delay (in 2ns increments) between deassertion of opianclkbufen and opibiasen
27:24	0h RW	cri_sqdbexittimer_override_3_0 : Rx squelch exit debounce timer
23:18	0h RW	cri_sqdbentrytimer_override_5_0 : Rx squelch entry debounce timer
17:16	0h RW	reg_rxdrcgtsqsel_1_0 : Squelch output select



Bit Range	Default & Access	Description
15	0h RW	cri_reut_SlaveSideDataCheckingEn: Enable REUT slave side checking while in loopback slave
14	0h RW	cri_sqdbtimer_ovren: Squelch debounce timer override enable
13	0h RW	cri_rxpwrfsm_timer_ovren: Rx power management fsm timer override enable
12	0h RW	reg_rxidle: Chicken bit to override i_rxidle from controller and keep Rx in P0 or P0s
11	0h RW	cri_rxrawdata_sel: When asserted bypass K-align, 10b/8b decoder and Elastic buffer
10	0h RW	cri_dynkalign_eco3302703_mode: Kalign Mode Override Value When cri_dynkalign_eco3302703_ovren is set, this value selects kalignmode 0 - use register bits cri_kalignmode[1:0] to select kalignmode 1 - select the 4 COM kalign mode'
9	0h RW	cri_dynkalign_eco3302703_ovren: Kalign Mode Override Enable Overrides kalign mode select pin, allowing config bit kalignmode_override_val to select kalignmode.
8	0h RW	reg_rxpwrfsm_pibiasoff_override: When asserted selects reg_rxpwrfsm_pibiasoff_delay[3:0]
7	0h RW	cri_reset_kalignlck: When asserted resets Kalign lock indication and Kalign is performed again. The conditions when this would assert includes and is not restricted to any power management states (L0s, L1) or polling quiet states etc.
6	0h RW	cri_ebptrrst: Global broadcast to all lanes that the Elastic Buffer pointers should be reset. This is a pulse and will be generated when we need to reset the pointers because of collision or various other reasons.
5	0h RW	cri_comdispfix: Chicken bit to force disparity in dynamic K-align mode
4	0h RW	cri_forcebankhit: Chicken bit to enable data appear on NOA post k-align lock although k-align block is not achieving lock. This is only for NOA observeability and not for other purpose
3:2	0h RW	cri_kalignmode_1_0: KALIGN Mode Select 00 = dynamic kalign all the time. Accounts for bit slips on incoming stream which can cause symbol to be detected on different bank 10 = dynamic kalign up to L0 x1 = static kalign (same as GDG). Assumes symbol always detected on same data bank
1	0h RW	cri_skpprocdis: SKIP Ordered-Set Processing Disable When this configuration bit is asserted, then SKIP ordered=sets will be ignored (in EB block). Used in Elastic buffer block. 0 = Normal operation. SKIP ordered=sets will be processed by the Elastic Buffer 1 = SKIP processing disabled.
0	0h RW	cri_elasticbuffer_maskdis: Config bit (chicken bit) to disable the masking logic after elec idle ordered set is seen

17.17.4 PCS_DWORD3 (pcs_dword3)—Offset Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword3: [Port: 0xA3] + (2200h + Ch)

Op Codes:
0h - Read, 1h - Write

Default: 5515ACAAh

17.17.6 PCS_DWORD5 (pcs_dword5)—Offset 14h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs dword5: [Port: 0xA3] + (2200h + 14h)


Op Codes:

0h - Read, 1h - Write

Default: 00003E63h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 1 1	1 1 1 0	0 1 1 0	0 0 1 1
cri_dfx_patbufrain								
cri_dfx_prbspoly_2_0								
cri_dfx_patbufsize_1_0								
cri_dfx_patbufloop								
cri_dfx_patbufdwidth								
cri_dfx_patbufrainovr								
cri_dfx_marginmode								
cri_dfx_chk_sel								
cri_dfx_patchken								
cri_dfx_patgenen								
cri_dfx_clerrcnt								
cri_dfx_lcereset								
cri_dfx_lcestart								
cri_dfx_patbuf_7_0								
cri_dfx_patbuf_15_8								

Bit Range	Default & Access	Description
31	0h RW	cric_dfx_patbuftrain: Pattern Buffer Manual Training When DFXPATBUFTRAIN_OVR and DFXLCESTART are asserted, this manually controls whether the Pattern Buffers are in training or have completed training. 0 : Send training patterns (default) 1 : Send contents of DFXPATBUF
30:28	0h RW	cric_dfx_prbbspoly_2_0: PRBS Polynomial Select the polynomial to be used by the PRBS in the Pattern Generator and Pattern Checker. PRBS support 10b or 8b, which is indicated by the msb. 000 - $x^{16} + x^5 + x^4 + x^3 + 1$ (USB3/PCIe Scrambler) (8b) 001 - $x^{16} + x^{15} + x^{13} + x^4 + 1$ (SATA scrambler) (8b) 010 - $x^{31} + x^{28} + 1$ (8b) 011 - $x^7 + x^6 + 1$ (8b) 100 - $x^{15} + x^{14} + 1$ (10b) 101 - $x^{23} + x^{18} + 1$ (10b) 110 - $x^{31} + x^{28} + 1$ (10b) 111 - $x^7 + x^6 + 1$ (10b)
27:26	0h RW	cric_dfx_patbufsize_1_0: Pattern Buffer Size Select the size of the Pattern Buffer to use. The MSB will always be bit 79. The LSB will depend on this select and the DFXLCEDATAWIDTH (10b or 8b mode). 00 : full 80b buffer (Default) 01 : 70b (while in 10b mode), 56b (while in 8b mode) 10 : 40b (while in 10b mode), 32b (while in 8b mode) 11 : 10b (while in 10b mode), 8b (while in 8b mode)
25	0h RW	cric_dfx_patbufloop: Pattern Buffer Looping Enable Enables looping of the Pattern Buffer. By default, the contents of Pattern Buffer will be used once and stop. Alternatively, the Pattern Buffer will continue to loop until the DFXLCESTART is de-asserted. 0 : Run Pattern Buffer only once (default) 1 : Loop Pattern Buffer until stopped
24	0h RW	cric_dfx_patbufdwidth: Pattern Buffer Data Width Selects between 10 bit or 8 bit data width for the Pattern Buffer. Determines where in the Tx/Rx path the data is inserted/retrieved. 0 : 10b (default) 1 : 8b
23	0h RW	cric_dfx_patbuftrainovr: Pattern Buffer Training Override Enables manual training of the Pattern Buffer instead of the automated coordination between the Pattern Checker and Pattern Generator. When asserted, the DFXPATBUFTRAIN bit will be used to force when training is active and when it is complete. 0 : Automatic Training (default) 1 : Enable Manual Training



Bit Range	Default & Access	Description
22	0h RW	cri_dfx_marginmode: Margin mode Overrides standard setup configurations for use with Eye Width Margining. 0 : Standard Mode (default) 1 : Margin Mode enabled
21	0h RW	cri_dfx_chk_sel: Pattern Checker 8b10b Select This determines where Rx data is compared, either in the 10-bit domain before decode or after 10b-)8b decoding. 0: 10b domain 1: 8b domain
20	0h RW	cri_dfx_patchken: Pattern Checker Enable 0 : Disable Pattern Checker (default) 1 : Enable Pattern Checker
19	0h RW	cri_dfx_patgenen: Pattern Generator Enable This will activate the DfX bypass muxes in the PCS Tx path. 0 : Disable Pattern Generator (default) 1 : Enable Pattern Generator
18	0h RW	cri_dfx_clrerrcnt: Clear Error Counter Resets the Pattern Checker's error counter. 0 : Error Counter allowed to run (default) 1 : Error Counter held in reset
17	0h RW	cri_dfx_lcereset: Local Compare Engine Reset Resets all components of the Local Compare Engine in both the Pattern Generator and the Pattern Checker. 0 : LCE not in reset (default) 1 : LCE in reset
16	0h RW	cri_dfx_lcestart: Local Compare Engine Start Controls the starting and stopping of the LCE. Allows for simultaneous or independent start across lanes. Once stopped, a DFXLCERESET is usually required. 0 : LCE stopped (default) 1 : LCE running
15:8	3Eh RW	cri_dfx_patbuf_7_0: Pattern Buffer Storage In 10b mode, the buffer is read as eight 10b chunks. The first 10 bits should not equal the Comma Symbol: '0011111010' (or its inversion '1100000101'). In 8b mode, the buffer is read as eight 10b chunks, where the 10th bit is unused and the 9th bit is the K-bit indicator. The first 10 bits should not equal the Comma Symbol: 'xx10111100'. DFXPATBUF[78] should not = '1'.
7:0	63h RW	cri_dfx_patbuf_15_8: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.

17.17.7 PCS_DWORD6 (pcs_dword6)—Offset 18h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword6: [Port: 0xA3] + (2200h + 18h)

Op Codes:

0h - Read, 1h - Write

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
cri_dfx_prbseed_7_0	cri_dfx_prbseed_15_8	cri_dfx_prbseed_23_16	cri_dfx_prbseed_31_24					

Bit Range	Default & Access	Description
31:24	FFh RW	cri_dfx_prbseed_7_0: PRBS Seed Can be used for HVM determinism. The use of all zeroes can result in lockup.



Bit Range	Default & Access	Description
23:16	FFh RW	cri_dfx_prbsseed_15_8: PRBS Seed See cri_dfx_prbsseed[7:0] description.
15:8	FFh RW	cri_dfx_prbsseed_23_16: PRBS Seed See cri_dfx_prbsseed[7:0] description.
7:0	FFh RW	cri_dfx_prbsseed_31_24: PRBS Seed See cri_dfx_prbsseed[7:0] description.

17.17.8 PCS_DWORD7 (pcs_dword7)—Offset 1Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword7: [Port: 0xA3] + (2200h + 1Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000009h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0
dfx_cri_errcnt_7_0	dfx_cri_errcnt_15_8	i_rxcaldone	dfx_cri_lcemgnerr	cri_dfx_patgen2active	dfx_cri_patbufallfail	dfx_cri_patchkactive	dfx_cri_patgenactive	dfx_cri_lcetraindone
						dfx_cri_lcetrainactive	reserved501	cri_dfx_patgen2en
							cri_dfx_maxerrcnt_1_0	cri_dfx_prbstraincnt_3_0

Bit Range	Default & Access	Description
31:24	X RO	dfx_cri_errcnt_7_0: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
23:16	X RO	dfx_cri_errcnt_15_8: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
15	X RO	i_rxcaldone: RX Calibration Cycles Complete Indicator
14	X RO	dfx_cri_lcemgnerr: Local Compare Engine Margin Error Indicates that the error counter has reached its max value. This can be used by the Rx upartition during Margin Mode to determine when the eye width has closed.
13	X RO	cri_dfx_patgen2active: Pattern Generator 2 Active status indicator In a lane with two Tx paths, this indicates that the second Pattern Generator is in progress. The DFXPATGENACTIVE will only indicate that the first Pattern Generator is in progress.
12	X RO	dfx_cri_patbufallfail: Pattern Buffer All Fail status indicator Indicates that there has not been a single matching Pattern Buffer pattern. This could signify that an error occurred during training.
11	X RO	dfx_cri_patchkactive: Pattern Checker Active status indicator Indicates that the Pattern Checker is in progress (either Pattern Buffer or PRBS).
10	X RO	dfx_cri_patgenactive: Pattern Generator Active status indicator Indicates that the Pattern Generator is in progress (either Pattern Buffer or PRBS).



Bit Range	Default & Access	Description
9	X RO	dfx_cri_lcetraindone: Local Compare Engine Training Done status indicator Indicates that the Pattern Checker training is completed (either Pattern Buffer or PRBS). The Pattern Checker is now synchronized to the Pattern Generator.
8	X RO	dfx_cri_lcetrainactive: Local Compare Engine Training Active status indicator Indicates that the Pattern Checker training is in progress (either Pattern Buffer or PRBS).
7	0h RW	reserved501: reserved
6	0h RW	cri_dfx_patgen2en: Pattern Generator 2 Enable In a lane with two Tx paths, this enables the second Pattern Generator. The DFXPATGENEN will enable the first Pattern Generator. 0 : Disable second Pattern Generator (default) 1 : Enable second Pattern Generator
5:4	0h RW	cri_dfx_maxerrcnt_1_0: Maximum Error Count Selectable maximum value that the DFXERRCNT can reach before the Local Compare Engine is automatically stopped. 00 : 2 ¹⁶ (default) 01 : 2 ¹⁰ 10 : 2 ⁸ 11 : 2 ⁴
3:0	9h RW	cri_dfx_prbstraintcnt_3_0: PRBS Training Count The number of consecutive cycles that the Pattern Checker's PRBS must be error free before it is considered synchronized. Default is 9.

17.17.9 PCS_DWORD8 (pcs_dword8)—Offset 20h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword8: [Port: 0xA3] + (2200h + 20h)

Op Codes:

0h - Read, 1h - Write

Default: 000000C4h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_partial	reg_slumber	reg_tx2_cdr_override_2_0	reg_cdr_override_2_0	reg_ebuffmode	reg_usedclockchannel_1_0	reg_usedclockchannel_override	reg_gbl_override	reg_tx1_pclkon_inp2
								reg_tx2_pclkon_inp2
								reg_tx2_txenable
					cri_rxeb_ptr_init_3_0			
					reg_powerfsm_override	reg_suspend	reg_pclkcfcinput	reg_useqclock
							cri_rxeb_hiwater_3_0	
								cri_rxeb_lowwater_3_0

Bit Range	Default & Access	Description
31	0h RW	reg_partial: Override for i_partial
30	0h RW	reg_slumber: Override for i_slumber
29:27	0h RW	reg_tx2_cdr_override_2_0: Override for cdr_override strap for second tx2



Bit Range	Default & Access	Description
26:24	0h RW	reg_cdr_override_2_0: Override for cdr_override strap
23	0h RW	reg_ebuffmode: Override for ebuffmode (no functionality in p1271 phase1 design)
22:21	0h RW	reg_usedclockchannel_1_0: Selects the active clock channel
20	0h RW	reg_usedclockchannel_ovrride: When asserted selects reg_usedclockchannel[1:0]
19	0h RW	reg_gbl_ovrride: Global override select
18	0h RW	reg_tx1_pclkon_inp2: When asserted keeps PCLK running in P2 mode. For DP this is used for Lane1
17	0h RW	reg_tx2_pclkon_inp2: When asserted keeps PCLK running in P2 mode. This is reserved (no impact) for PCIe/DMI and used for DP Lane2
16	0h RW	reg_tx2_txenable: Override for i_txenable for tx2
15:12	0h RW	cri_rxeb_ptr_init_3_0: Config override for initial value of Rx elastic buffer read pointer
11	0h RW	reg_powerfsm_ovrride: When asserted overrides for Tx power fsm are selected
10	0h RW	reg_suspend: Override for suspend
9	0h RW	reg_pclkcfcinput: Override for pclkcfcinput strap
8	0h RW	reg_useqclock: Override for useqclock; MUX select for I or Q clk for TX clocking
7:4	Ch RW	cri_rxeb_hiwater_3_0: Elastic buffer high watermark based on which SKP is removed
3:0	4h RW	cri_rxeb_lowwater_3_0: Elastic buffer low watermark based on which SKP is added

17.17.10 PCS_DWORD9 (pcs_dword9)—Offset 24h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword9: [Port: 0xA3] + (2200h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved502	reg_strapgroup_4_0	reg_powerdown_1_0	reg_pcs_txcmnkeepdisable_ovrd	reg_straplane_5_0	reg_tx1_powerdown_override	reg_tx2_powerdown_override	reg_txdatavalid	reg_txdeemp_1_0
					reg_txmargin_2_0	reg_txswing	reg_txenable	reg_txterm_vcc_1_0
							reg_txdetrxlpbk	reg_txelectidle
							reg_txcompliance	reg_txoneszeroes
								reg_latencyoptim_1_0

Bit Range	Default & Access	Description
31	0h RW	reserved502: reserved
30:26	0h RW	reg_strapgroup_4_0: Override for i_strapgroup
25:24	0h RW	reg_powerdown_1_0: Override for i_powerdown
23	0h RW	reg_pcs_txcmnkeepdisable_ovrd: Override for ipcs_txcmnkeepdisable input 0: Use value on ipcs_txcmnkeepdisable input pin to determine o_txgohighz state in P2/slumber 1: Force pcs_txcmnkeepdisable to 0
22:18	0h RW	reg_straplane_5_0: Override for i_strapplane
17	0h RW	reg_tx1_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx1 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
16	0h RW	reg_tx2_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx2 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
15	0h RW	reg_txdatavalid: Override for i_txdatavalid (register is NOT used)
14:13	0h RW	reg_txdeemp_1_0: Override for i_txdeemph
12:10	0h RW	reg_txmargin_2_0: Override for i_txmargin
9	0h RW	reg_txswing: Override for i_txswing
8	0h RW	reg_txenable: Override for i_txenable
7:6	0h RW	reg_txterm_vcc_1_0: Override for txterm_vcc strap
5	0h RW	reg_txdetrxlpbk: Override for i_txdetrxlpbk
4	0h RW	reg_txelectidle: Override for i_txelectidle
3	0h RW	reg_txcompliance: Override for i_txcompliance



Bit Range	Default & Access	Description
2	0h RW	reg_txoneszeroes: Override for i_txoneszeroes
1:0	0h RW	reg_latencyoptim_1_0: Override for i_latencyoptim

17.17.11 PCS_DWORD10 (pcs_dword10)—Offset 28h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword10: [Port: 0xA3] + (2200h + 28h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
reg_rxpwrfsm_timer_WAIT_RX_PI_CLK_3_0	reg_rxpwrfsm_timer_ENABLE_RX_3_0	reg_rxpwrfsm_timer_RX_SQEN_3_0	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0		reg_clk_valid_cnt_7_0		reg_rxterm reg_rxpolarity reg_rxeqtrain reg_rxsquelchen cri_rxpwrfsm_sqentimer_ovrden reg_rxintftren_override reg_rxintftren_l reg_clk_valid_cnt_ovrd	

Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PI_CLK_3_0: Rx Power state m/c timer value used to enable PI clock
27:24	0h RW	reg_rxpwrfsm_timer_ENABLE_RX_3_0: Rx Power state m/c timer value used to enable receivers
23:20	0h RW	reg_rxpwrfsm_timer_RX_SQEN_3_0: Rx Power FSM Rx Squelch Enable Timer Override Value Affect squelch enable startup sequence during 'synchronous' squelch startup mode. 0000 - Invalid 0001 - 1 susclk period ... 1111 - 15 susclk period
19:16	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0: Rx Power state m/c timer value used to enable PI BIAS
15:8	0h RW	reg_clk_valid_cnt_7_0: Over ride value for clock valid delay in clock top block before toggling phystatus.
7	0h RW	reg_rxterm: Override for i_rxterm
6	0h RW	reg_rxpolarity: Override for i_rxpolarity



Type: Message Bus Register
(Size: 32 bits)

Op Codes:

0h - Read, 1h - Write

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
2039



Bit Range	Default & Access	Description
23	0h RW	i_clkbuf_iclken_ovrd: I-Clock Override for the DataLane
22	0h RW	i_clkbuf_qclken_ovrd: Q-Clock Override for the DataLane
21	0h RW	reserved503: reserved
20	0h RW	i_clkbuf_txclkmuxen_ovrd: TX Clock Selection Mux Override
19	0h RW	reserved504: reserved
18	0h RW	reg_tx2_cmmdisparity: Sets the initial disparity during Compliance Measurement Mode, used together with pcs_txcompliance pulse. For TX2 0 = set negative disparity 1 = set positive disparity
17	0h RW	reg_tx1_ctrl_override: overrides input parameter/controls for tx1
16	0h RW	reg_tx2_ctrl_override: overrides input parameter/controls for tx2
15	0h RW	reg_tx2_txterm_vcc_1: Override for txterm_vcc strap[1] for tx2 in DP family. Override enable for inspecmm for non-DP families (reg_inspecmm_ovrd_enable).
14	0h RW	reg_tx2_txterm_vcc_0: Override for txterm_vcc strap[0] for tx2 in DP family. Override value for inspecmm for non-DP families (reg_inspecmm_ovrd_value).
13	0h RW	reg_tx2_txdetrxlpbk: Override for i_txdetrxlpbk for tx2
12	0h RW	reg_tx2_txelectidle: Override for i_txelectidle for tx2
11	0h RW	reg_tx2_txcompliance: Override for i_txcompliance for tx2
10	0h RW	reg_tx2_txoneszeroes: Override for i_txoneszeroes for tx2
9:8	0h RW	reg_tx2_powerdown_1_0: Override for i_powerdown for tx2
7	0h RW	o_captesten_h: Enable testing of capacitors
6	X RO	i_captestout: Capacitor test result
5	0h RW	fuse_override: Overrides Lane fuses 1: override txterm_vcc, latencyoptim, cdr_override, rxterm_vcc 0: fuses not overridden
4	0h RW	i_clkbuf_ibiasen_ovrd: Override i_clkbuf_ibiasen value RX CML driver bias enable
3	0h RW	reg_lanedeskew_strap_ovrd_____: reserved
2	0h RW	reg_lane_reverse_____: reserved
1	0h RW	reg_left_txfifo_rst_master_____: reserved
0	0h RW	reg_right_txfifo_rst_master_____: reserved



17.17.13 PCS_DWORD12 (pcs_dword12)—Offset 30h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword12: [Port: 0xA3] + (2200h + 30h)

Op Codes:

0h - Read, 1h - Write

Default: 00250F00h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_tx fsm_200ns_ovrd		reg_tx fsm_200ns_delay_6_0	reg_loadgen2txen_fall_ovrd	reg_tx2_stagger_mult_2_0	reg_lanestagger_by_group	reg_tx1_stagger_mult_2_0	reserved509	reserved510
						reg_tx1_stagger_mask_4_0	reserved507	reg_lanestagger_strap_ovrd
							reserved508	reg_lanestagger_strap_4_0

Bit Range	Default & Access	Description
31	0h RW	reg_tx fsm_200ns_ovrd: Override reg_tx fsm_200ns_delay+G2
30:24	0h RW	reg_tx fsm_200ns_delay_6_0: Override value of counter for 200ns delay between txen and txloadgenen
23	0h RW	reg_loadgen2txen_fall_ovrd: reserved
22:20	2h RW	reg_tx2_stagger_mult_2_0: Stagger multiplier for Rx (or Tx1) (Same decoding as tx1_stagger_mult[2:0]) For Display, this multiplier applies to Tx2. For non-Display PHYs, this multiplier applies to the Rx. The multiplier limit for the Rx is 8x (3'b100); anything beyond that is invalid.
19	0h RW	reg_lanestagger_by_group: When = 1, uses group number for lane staggering, by devalues lane number is used.
18:16	5h RW	reg_tx1_stagger_mult_2_0: Stagger multiplier for Tx (or Tx1) These bits set the lane staggering multiplier for the transmitter based on the 'linkclk' period. 000 - 0x 001 - 1x 010 - 2x 011 - 4x 100 - 8x 101 - 16x 110 - 32x 111 - 64x For Display, this multiplier applies to Tx1.
15:14	0h RW	reserved509: reserved
13	0h RW	reserved510: reserved
12:8	Fh RW	reg_tx1_stagger_mask_4_0: Mask bit for lane number. Used to group lanes for staggering
7	0h RW	reserved507: reserved
6	0h RW	reg_lanestagger_strap_ovrd: When 1 config override for lane stagger strap (bits [4:0] of this register) is selected
5	0h RW	reserved508: reserved



Bit Range	Default & Access	Description
4:0	0h RW	reg_lanestagger_strap_4_0: Override for lane stagger strap

17.17.14 PCS_DWORD13 (pcs_dword13)—Offset 34h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword13: [Port: 0xA3] + (2200h + 34h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
visa_en	reserved512	visa_clk_sel1_4_0	visa_lane_sel1_7_0	visa_bypass	reserved511	visa_clk_sel0_4_0	visa_lane_sel0_7_0	

Bit Range	Default & Access	Description
31	0h RW	visa_en: VISA Enable for PCS VISA logic
30:29	0h RW	reserved512: reserved
28:24	0h RW	visa_clk_sel1_4_0: VISA Clock Select for Lane1. Selects the source synchronous clock to be used for data being sent on lane1.
23:16	0h RW	visa_lane_sel1_7_0: VISA Lane Select for Lane1. Selects the byte of data to be sent out on lane0.
15	0h RW	visa_bypass: VISA Bypass. Allows for signals to be passed asynchronously through VISA block. Applies to both lane0 and lane1. 0 : Flop signals in local VISA block (default) 1 : Bypass flops in local VISA block
14:13	0h RW	reserved511: reserved
12:8	0h RW	visa_clk_sel0_4_0: VISA Clock Select for Lane0. Selects the source synchronous clock to be used for data being sent on lane0.
7:0	0h RW	visa_lane_sel0_7_0: VISA Lane Select for Lane0. Selects the byte of data to be sent out on lane0.

17.17.15 PCS_DWORD14 (pcs_dword14)—Offset 38h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword14: [Port: 0xA3] + (2200h + 38h)

Op Codes:

0h - Read, 1h - Write



Default: 007A0018h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_clkbuf_stagger_ovrd	reg_clkbuf_stagger_cnt_10	reg_slowclk_ovrden	reg_txloadgenen2txen_fall_delay_4_0	o_cmlmuxsthse1_3_0	o_cmlsthse1_3_0	o_pcisel_3_0	o_pcqsel_3_0	o_phaseicen
								o_phaseqcen
								o_pcbypass
								o_slowclocken
								o_sclk250en
								cri_kalign_com_cnt

Bit Range	Default & Access	Description
31	0h RW	reg_clkbuf_stagger_ovrd: Override enable for reg_clkbuf_stagger_cnt
30	0h RW	reg_clkbuf_stagger_cnt_10: Counter override value for staggering delay of clock buffer control signals.
29	0h RW	reg_slowclk_ovrden: Slow Clock Override Enable When set 1'b1, reg_slowclocken and reg_sclk250en are valid. When cleared 1'b0, output of FSM will drive slow clock enable.
28:24	0h RW	reg_txloadgenen2txen_fall_delay_4_0: reserved
23:20	7h RW	o_cmlmuxsthse1_3_0: CML Mux strength control
19:16	Ah RW	o_cmlsthse1_3_0: RX CML driver strength
15:12	0h RW	o_pcisel_3_0: I clk phase correction control
11:8	0h RW	o_pcqsel_3_0: Q clk phase correction control
7	0h RW	o_phaseicen: Iclk phase correction enable.
6	0h RW	o_phaseqcen: Qclk phase correction enabled.
5	0h RW	o_pcbypass: Phase correction bypass.
4	1h RW	o_slowclocken: Slow clock 1 enable Only valid if slow clock override enable is set 1'b1
3	1h RW	o_sclk250en: Slow clock 2 enable Only valid if slow clock override enable is set 1'b1
2:0	0h RW	cri_kalign_com_cnt: Upper 3 bits of a 7-bit counter that counts number of COM characters found. Used for special SAPIs mode where spread spectrum clocking can be utilized. Note: This register is used in conjunction with another PCS register cri_kalignmode[1:0] = 10 Register value Minimum COM count to achieve symbol lock 000 - 18 001 - 34 010 - 50 011 - 66 100 - 82 101 - 98 110 - 114 111 - 130



17.17.16 PCS_DWORD15 (pcs_dword15)—Offset 3Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword15: [Port: 0xA3] + (2200h + 3Ch)


Op Codes:

0h - Read, 1h - Write

Default: 04100300h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reg_powermode_del_cfg_fifoctrlgen_2_0	reg_clkbuf_en_ovrd	o_deskewen	reserved514	reserved515	reserved516	o_obsselectlocaldown_h	o_obsselectlocalup	o_obsselectm1datadown
						o_obsselectm1dataup	o_obsselectm2_1_0	o_obsselectm1_1_0
						reg_clkbuf_stagger_cnt_1_0	reserved513	reg_clkbuf_stagger_cnt_9_2

Bit Range	Default & Access	Description
31:29	0h RW	reg_powermode_del_cfg_fifoctrlgen_2_0: Controls the delay from powermode change to Tx PCS data fifo pointer de-assertion 000 = 'd280 001 = 'd20 010 = 'd48 011 = 'd80 100 = 'd144 101 = 'd538 110 = 'd800 111 = 'd1023
28	0h RW	reg_clkbuf_en_ovrd: ClkBuf Override Enable When asserted, the overrides for the CLKBUF (i_clkbuf*_ovrd) are selected. Enable TX clock selection MUX
27	0h RW	o_deskewen: DFT output deskew enable
26	1h RW	reserved514: reserved
25	0h RW	reserved515: reserved
24	0h RW	reserved516: reserved
23	0h RW	o_obsselectlocaldown_h: N/N+1 Abut Obs-UP output control Selects local 'down' signals from current lane Tx1 (M1) and Rx/Tx2 (M2) or the iabut_obsup inputs to be driven on oabut_obsdown outputs. 0: select signals from the iabut_obsup inputs 1: select 'down' signals from the current lane
22	0h RW	o_obsselectlocalup: N/N+1 Abut Obs DOWN output control Selects local 'up' signals from current lane Tx1 (M1) and Rx/Tx2 (M2) or the iabut_obsdown inputs to be driven on oabut_obsdown outputs and to the current lane's Tx1 or Tx2. 0: select signals from the iabut_obsdown inputs 1: select 'up' signals from the current lane
21	0h RW	o_obsselectm1datadown: N/N+1 M1-M2 Down data control Selects local 'down' data input signals from M1 (Tx1) or M2 (Tx2 or Rx) to be sent to the obsselectlocaldown muxes that are controlled by bit 7. 0: select M2 (Tx2 or Rx) 1. select M1 (Tx1)



Bit Range	Default & Access	Description
20	1h RW	o_obsselectm1dataup: N/N+1 M1-M2 Up data control Selects local 'up' data input signals from M1 (Tx1) or M2 (Tx2 or Rx) to be sent to the obsselectlocalup muxes that are controlled by bit 6. 0: select M2 (Tx2 or Rx) 1. select M1 (Tx1)
19:18	0h RW	o_obsselectom2_1_0: N/N+1 M2 Output Select This controls which signals are sent to Tx2. These outputs are not used when M2 is a Receiver. 00: iabut_obsdown 01: iabut_obsup 10: output of local 'up' select muxes that are controlled by bit 6 11: GND
17:16	0h RW	o_obsselectom1_1_0: N/N+1 M1 Output Select This controls which signals are sent to Tx1. 00: iabut_obsdown 01: iabut_obsup 10: output of local 'up' select muxes that are controlled by bit 6 11: GND
15:14	0h RW	reg_clkbuf_stagger_cnt_1_0: Counter override value for staggering delay of clock buffer control signals.
13:8	3h RW	reserved513: reserved
7:0	0h RW	reg_clkbuf_stagger_cnt_9_2: Counter override value for staggering delay of clock buffer control signals.

17.17.17 PCS_DWORD16 (pcs_dword16)—Offset 40h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword16: [Port: 0xA3] + (2200h + 40h)


Op Codes:

0h - Read, 1h - Write


Default: 01000001h

31	28				24				20				16				12				8				4				0																																						
0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1																																						
squelch_shunt_ovrd_en				squelch_shunt_cnt_2_0				reserved520				i_rxsqfsm_timersel				i_rxsq_asyncmode_h				i_rxsquelchstby_h				reserved519				cri_dfx_evenoddmask_1_0				reserved518				cri_dfx_ice2patsrc_1_0				cri_dfx_icepatsrc_1_0				reserved517				txloadgen_ctr_val				cri_txhighpowerei_ovrden				cri_tx1highpowerei_ovrdval				cri_tx2highpowerei_ovrdval				p2_fast_exit_en			

Bit Range	Default & Access	Description
31	0h RW	sqelch_shunt_ovrd_en: Sqelch Shunt Pulse Duration Override Enable Overrides the hardware default shunt pulse duration value 1: Shunt Pulse Duration Override Enable 0: Shunt Pulse Duration Override Disable
30:28	0h RW	sqelch_shunt_cnt_2_0: Sqelch Shunt Pulse Duration Override Value 000 = No shunt pulse generated 001 = 1 susclk cycles ... 111 = 7 susclk cycles
27	0h RW	reserved520: reserved
26	0h RW	i_rxsqfsm_timersel: Sqelch FSM Timer Select 0 - Selects 25Mhz values for sqelch timer and shunt pulse generation . 1 - Selects 100Mhz values for sqelch timer and shunt pulse generation. This register is applicable to synchronous sqelch startup mode.



Bit Range	Default & Access	Description
25	0h RW	i_rxsq_asyncmode_h: Squelch Async Startup Mode This squelch startup mode is power state independent. When enabled, the squelchen signal sent to Modphy will asynchronously enable the squelch detector circuit. Once enabled, the squelch detector circuit will asynchronously send an unfiltered/unqualified squelch indication signal out of Modphy. The squelch indication signal will initially be unstable, so it is up to the consumer of this signal to filter/qualify it accordingly. The asynchronous squelch startup mode is beneficial because it significantly reduces the squelch startup latency. This decrease in latency does come at the cost of slightly higher power when squelch is not enabled as the IREF and Squelch Keeper circuits must remain enabled. When disabled, the squelch startup sequence is synchronous in nature and the squelch indication signal sent out of Modphy is stable/filtered.
24	1h RW	i_rxsquelchstby_h: Fast Squelch Enable Mode Bit to keep the IREF (ivrefen) on during P2 and reduce squelch startup time.
23:18	0h RW	reserved519: reserved
17:16	0h RW	cri_dfx_evenoddmask_1_0: Pattern Checker Even/Odd Bit Error Mask Select 00 : no masking; all errors will be counted 01: select odd path, mask even path; only errors on bits [1,3,5,7,9] are counted 10: select even path, mask odd path; only errors on bits [0,2,4,6,8] are counted 11: reserved;
15:12	0h RW	reserved518: reserved
11:10	0h RW	cri_dfx_lce2patsrc_1_0: Local Compare Engine 2 Pattern Source In a lane with two Tx paths, this selects between using Pattern Buffer or PRBS as source of LCE patterns for the second LCE. The DFXLCEPATSRC selects for the first LCE. 0 : Pattern Buffer (default) 1 : PRBS
9:8	0h RW	cri_dfx_lcepatsrc_1_0: Local Compare Engine Pattern Source. Selects between using Pattern Buffer or PRBS as source of LCE patterns. 00 : Pattern Buffer; use LCE default training pattern; 01: Pattern Buffer; use the first 40b of pattern buffer for training. 10: PRBS; use LCE default training pattern; 11: PRBS; use the first 40b of pattern buffer for training.
7:6	0h RW	reserved517: reserved
5:4	0h RW	txloadgen_ctr_val: TxLoadGen Pulse Width Control Controls the pulse width of txloadgenen from PCS to Tx upar. This is used in MAC initiated digital far end loopback mode in PCIE family. 00 - txloadgenen pulse width is 4 symbol clocks (default) 01 - txloadgenen pulse width is 2 symbol clocks 10 - txloadgenen pulse not generated 11 - txloadgenen pulse width is 6 symbol clocks
3	0h RW	cri_txhighpowerei_ovrden: TxHighPowerEI Override Mode Enable 0 - TxHighPowerEI to TxuPAR driven by Logic 1 - TxHighPowerEI to TxuPAR driven by override register value(s).
2	0h RW	cri_tx1highpowerei_ovrdval: Tx1HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx1HighPowerEI disabled 1 - Tx1HighPowerEI enabled
1	0h RW	cri_tx2highpowerei_ovrdval: Tx2HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx2HighPowerEI disabled 1 - Tx2HighPowerEI enabled
0	1h RW	p2_fast_exit_en: P2 Fast Exit Mode Enable Common Mode sustainer will be enabled during P2 when this bit is asserted. 1: P2 Fast Exit Mode Enable 0: P2 Fast Exit Mode Disable



Bit Range	Default & Access	Description
11	0h RW	lrc_rdy_pulsegen: LRC Ready PulseGen Generates a pulse 1 cal_clk cycle wide on the lrc_rdy signal to all four targets; does not recompute local Rcomp code. Values in DWD 0x14 (*rccodes[7:0]) will be latched into targets. User must clear this bit before generating another pulse. Note: User should disable PM and PER. FSM can take control and codes can be overridden.
10:9	0h RW	lrc_rdy_target_1_0: LRC Ready Pulse Target Indicates which lrc target to recompute when lrc_rdy_ovd is strobed 00: irefrccode 01: txrccode 10: rxtermrccode 11: rxvgarccode
8	0h RW	lrc_rdy_ovd: LRC Ready Override Recomputes the selected local rcomp code and generates a pulse 1 cal_clk cycle wide on the lrc_rdy signal that is selected in bits [2:1]. User must clear this bit before generating another pulse. Note: User should disable PM and PER. FSM can take control and codes can be overridden.
7	0h RW	rxtermpmrcen: PM RCOMP Enable for Rx Termination 1 - Enables the RCOMP update to occur while RX is in power management state if periodic RCOMP is enabled. If this bit is set and the PHY is not in a power management state, no update will occur. 0 - Disables power management qualifier to the RCOMP update; therefore RCOMP updates will be based on the state of the target periodic bit.
6	0h RW	rxvgapmrcen: PM RCOMP Enable for Rx VGA (Same description as the RxTerm PM Rcomp Enable.)
5	0h RW	txpmpmrcen: PM RCOMP Enable for Tx 1 - Enables the RCOMP update to occur while TX is in power management state if periodic RCOMP is enabled. If this bit is set and the PHY is not in a power management state, no update will occur. 0 - Disables power management qualifier to the RCOMP update; therefore RCOMP updates will be based on the state of the target periodic bit.
4	0h RW	irefpmrcen: IREF PM RCOMP Enable 1 - Enables the RCOMP update to occur while TX/RX is in the P1 or P2 (partial or slumber) power management state if periodic RCOMP is enabled. If this bit is set and the PHY is not in a power management state, no update will occur. 0 - Disables power management qualifier to the RCOMP update; therefore RCOMP updates will be based on the state of the target periodic bit.
3	0h RW	rxtermperrcen: Periodic RCOMP Enable for Rx Termination 1 - Enables the periodic RCOMP update for specified block. 0 - Disables periodic RCOMP update for specified block.
2	0h RW	rxvgaperrcen: Periodic RCOMP Enable for Rx VGA 1 - Enables the periodic RCOMP update for specified block. 0 - Disables periodic RCOMP update for specified block.
1	0h RW	txperrcen: Periodic RCOMP Enable for Tx 1 - Enables the periodic RCOMP update for specified block. 0 - Disables periodic RCOMP update for specified block.
0	1h RW	irefperrcen: Periodic RCOMP Enable for Iref 1 - Enables the periodic RCOMP update for specified block. 0 - Disables periodic RCOMP update for specified block.

17.17.19 PCS_DWORD18 (pcs_dword18)—Offset 48h

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword18: [Port: 0xA3] + (2200h + 48h)

Op Codes:

0h - Read, 1h - Write

Default: 00008080h




17.17.20 PCS DWORD19 (pcs_dword19)—Offset 4Ch

pcs_dword19: [Port: 0xA3] + (2200h + 4Ch)

0h - Read, 1h - Write

31				28				24				20				16				12				8				4				0																											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1	1	1	0	0	0	1	0	0	0	0																												
amp0calcode_7_0								cal_num				cal_start				cal_type				cal_inv				cal_rst				calclkdivsel_1_0				reserved525				calib_done				cal_fb_count				adc_acctime_1_0				adc_clkssel_1_0				adcmuxsel_2_0				adcstart			



Bit Range	Default & Access	Description
31:24	0h RW	iamp0calcode_7_0: IREF Opamp Calibration Codes These bits are written by the calibration state machine. Bit7 - Calibration enable that configures the target into a calibration mode Bit6 - Calibration sign bit Bit[5:0] - Calibration magnitude [lyonel to check bit7 functionality].
23:20	0h RW	cal_num: Calibration Number or Address numbers of cal targets or address for specific cal target if cal_type = 1
19	0h RW	cal_start: Calibration Start This bit is used to start a Cal cycle via IOSF-SB. The cal cycle will follow the normal cal cycle as set by cal_num, cal_type, cal_inv and cal_rst. The Cal cycle starts when this bit transitions 0 1 1 = Run Cal. 0 = wait (default)
18	0h RW	cal_type: Calibration Type Enable calibration of one cal target defined by cal_num 0 = multi 1 = single
17	0h RW	cal_inv: Calibration Feedback Invert Inverse the logic of counter increment decrement depends on the FB
16	0h RW	cal_rst: Calibration Reset Reset state machine
15:14	1h RW	calclkdivsel_1_0: Calibration Clock Divider Select 00 - div2 of CRICLK 01 - div4 of CRICLK 10 - div8 of CRICLK 11 - div16 of CRICLK Note: Calibration clock period target is 160nS
13	0h RO	reserved525: reserved
12	0h RO	calib_done: Calibration Completion Indicator
11:8	Fh RW	cal_fb_count: Calibration Cycle Count Limit per target Each calibration target is clocked for 16 * cal_fb_count clock cycles. Max is 240 clock cycles (default)
7:6	0h RW	adc_acctime_1_0: ADC Accumulation Time Select This selects the conversion time for the Analog to Digital Converter. ADC clock frequency is set by bits [5:4] in this register. 00: 1024 ADC clocks (default) 01: 512 ADC clocks 10: 256 ADC clocks 11: Infinite (ADC in continuous accumulation) Note: If LRC mode and set to '11', then adctime = 1024cycles.
5:4	1h RW	adc_clkssel_1_0: ADC Clock Frequency Select This selects the input clock frequency to the Analog to Digital Converter. 00: CRI clock div2 01: CRI clock div1 10: CRI clock div4 11: CRI clock div8 NOTE: Target is 50Mhz.
3:1	0h RW	adcmuxsel_2_0: ADC Analog Mux Select This selects the analog voltage input to the Analog to Digital Converter. 000: Vss 001: Vcc 010: LRC R1 voltage divider 011: LRC sense net 100: input from Tx 101: input from Rx (or Tx #2) 110: input from Clock 111: input from reference generator Note: Mux select is controlled by the FSM during LRC.
0	0h RW	adcstart: ADC start This bit resets the ADC counter and starts a new acquisition. This bit should remain 1'b1 while the ADC is active and acquiring data. 0: Disable ADC logic and analog circuitry 1: Enable ADC and start A2D conversion.

17.17.21 PCS_DWORD20 (pcs_dword20)—Offset 50h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword20: [Port: 0xA3] + (2200h + 50h)

Op Codes:

0h - Read, 1h - Write

Default: 80808080h



17.17.22 PCS DWORD21 (pcs_dword21)—Offset 54h

Default: 80808080h

Intel Atom® Processor E3800 Product Family
Datasheet
2051



Access Method

pcs dword22: [Port: 0xA3] + (2200h + 58h)

0h - Read, 1h - Write

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
rxvgarcoffset_7_0				rxtermircoffset_7_0				txrcoffset_7_0				irefrcoffset_7_0			

October 2018
Document Number: 538136, Rev. 4.3

17.17.24 PCS_DWORD23 (pcs_dword23)—Offset 5Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword23: [Port: 0xA3] + (2200h + 5Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00180888h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	1	0	0	0
iclkqcfg_spare_7_0								iclkcfg_spare_7				iclkqcfg_spare_6_3				iclkcfg_spare_2_0				reserved526				i_drvcfg_3_0				i_loadcfg_3_0				ipbiasctrl_3_0			

Bit Range	Default & Access	Description
31:24	0h RW	iclkqcfg_spare_7_0: (Bonus bits for Data Lane Clk Distrubtion block)
23	0h RW	iclkicfg_spare_7: Repurposed for IREF backup mode in DL Select bit to enable diode based IREF in DL 0 - functional mode, use IREFGEN loop output 1 - bypass IREF loop, use diode connected PMOS output Ensure IREF loop amp is enabled by forcing reg_ivrefen and ivrefen_ovrd to 1
22:19	3h RW	iclkicfg_spare_6_3: TX MUX tail current strength setting
18:16	0h RW	iclkicfg_spare_2_0: CLK Distribution Monitor MUX Select
15:12	0h RW	reserved526: reserved
11:8	8h RW	i_drvcfg_3_0: CLK: Driver Tail Current Control
7:4	8h RW	i_ploadcfg_3_0: CLK: Pbias Ref Current Selection
3:0	8h RW	ipbiasctrl_3_0: CLK: Pmos-Load Pbias Voltage Control

17.17.25 PCS_DWORD24 (pcs_dword24)—Offset 60h

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword24: [Port: 0xA3] + (2200h + 60h)

Op Codes:

0h - Read, 1h - Write

Default: 0001C020h



October 2018
Document Number: 538136, Rev. 4.3



Access Method

tx_dword1: [Port: 0xA6] + (280h + 4h)

Op Codes:

0h - Read, 1h - Write

Default: 20000000h

Bit Range	Default & Access	Description
31:30	0h RO	reserved510: reserved
29:24	20h RW	ofrcr2short3_5_0: number of slices in R2 for swing 3 (DE) MSB has no effect.
23:22	0h RO	reserved509: reserved
21:16	0h RO	reserved508: reserved
15:14	0h RO	reserved507: reserved
13:8	0h RO	reserved506: reserved

Bit Range	Default & Access	Description
7:6	0h RO	reserved505: reserved
5:0	0h RW	ofrcr2short0_5_0: number of slices in R2 for swing 0 (FS) MSB has no effect.

17.18.3 TX_DWORD2 (tx_dword2)—Offset 8h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword2: [Port: 0xA6] + (280h + 8h)

Op Codes:

0h - Read, 1h - Write

Default: 5580983Ah

31				28				24				20				16				12				8				4				0															
0				1				0				1				0				1				1				0				1				0				1				0			
omargin010_7_0												omargin000_7_0												ouniqtranscale_7_0								reserved511								ofrcslices_6_0							

Bit Range	Default & Access	Description
31:24	55h RW	omargin010_7_0: factor (X/128) of slices to use in main-R1 for full swing level. Used for ~2/3Vp2p
23:16	80h RW	omargin000_7_0: factor (X/128) of slices to use in main-R1 for full swing level. Used for ~1V p2p. To be used in Gen2 mode (Gen1/Gen2 depend on dataratefit and downscaleamp register)
15:8	98h RW	ouniqtranscale_7_0: scales the number of slices defined the ref circuit (or R-comp circuit) by factor of <code>ouniqtranscale[7:0]/128</code> The scaled amount of slices might be used in the full-swing Uis according to <code>ouniqtrangenmethod[1:0]</code> The scaled amount of slices might be used in the full-swing Uis according to <code>oscaledcompmethod[1:0]</code>
7	0h RO	reserved511: reserved
6:0	3Ah RW	ofrcslices_6_0: number of used slices if forced Used in compensated GPIO mode



17.18.6 TX_DWORD5 (tx_dword5)—Offset 14h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword5: [Port: 0xA6] + (280h + 14h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
ocalcinit	reserved515	reserved514	reserved513	reserved512				

Bit Range	Default & Access	Description
31	0h RW	ocalcinit: initiate calculation of swing-control circuit. rewrite to '0' and '1' to reinitiate the calculation
30:24	0h RO	reserved515: reserved
23:16	0h RO	reserved514: reserved
15:8	0h RO	reserved513: reserved
7:0	0h RO	reserved512: reserved

17.18.7 TX_DWORD6 (tx_dword6)—Offset 18h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword6: [Port: 0xA6] + (280h + 18h)

Op Codes:

0h - Read, 1h - Write

Default: 1F200000h

31	28	24	20	16	12	8	4	0
0	0	0	1	1	1	1	0	0
reserved520	onswbypass_6_0	reserved519	opswbypass_6_0	reserved518	reserved517	ocalcont	reserved516	

Bit Range	Default & Access	Description
31	0h RO	reserved520: reserved



Access Method

tx dword8: [Port: 0xA6] + (280h + 20h)

0h - Read, 1h - Write

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	0	1	0	1	0	1	0	1	0	1	0	0	0	0	0	0	0				
ontlptime_7_0								ofrcdcoup_1_0				obybycomp				obydfmode_4_0				odfpisodata1_7_0				odfpisodata0_1_0				reserved529				reserved528			

October 2018
Document Number: 538136, Rev. 4.3

17.18.10 TX DWORD9 (tx_dword9)—Offset 24h

Bit Range	Default & Access	Description
15:8	Ah RW	odftpisodata1_7_0 : 8 MSB of alternative data input to PISO Load of this data is enabled when bypdfmode=DFTPISOLOAD
7:6	2h RW	odftpisodata0_1_0 : 2 LSB of alternative data input to PISO Load of this data is enabled when bypdfmode=DFTPISOLOAD
5:3	0h RO	reserved529 : reserved
2:0	0h RO	reserved528 : reserved

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword9: [Port: 0xA6] + (280h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00430C06h

31				28				24				20				16				12				8				4				0							
0 0 0 0				0 0 0 0				0 1 0 0				0 0 1 1				0 0 0 0				1 1 0 0				0 0 0 0				0 0 1 1				0 0 1 1							
ontistrongpulling				ontlien				ontlowrefsel_2_0				onthighrefsel_2_0				ofrcsatamode_1_0				otxsusclkfreq_1_0				reserved530				orcvdtdtrefselnosus_1_0				orcvdtdtputime_7_0				ontlputime_7_0			

Bit Range	Default & Access	Description
31	0h RW	ontlstrongpulling : Make the NTL pulling resistors with stronger pulling. It will be required if leakage will be higher than expected
30	0h RW	ontlen : No-touch-leakage test enable
29:27	0h RW	ontllowrefsel_2_0 : Selects reference voltage for use when pads where pulled-down and were left to leak upwards
26:24	0h RW	ontlhighrefsel_2_0 : Selects reference voltage for use when pads where pulled-up and were left to leak downwards
23:22	1h RW	ofrcsatamode_1_0 : 00
21:20	0h RW	otxsusclckfreq_1_0 : Determines the clock frequency expected on ick_susslow clock pin. 00: in the range of 25MHz to 27MHz (default) 01: in the range of 25MHz - 62.5MHz 10: in the range of 37.5MHz - 100MHz 11: in the range of 62.5MHz - 125MHz
19:18	0h RO	reserved530 : reserved
17:16	3h RW	orcvdtctrefselnosus_1_0 : 2-LSBs of reference level for receive detect comparator to be used when core supply is active



Bit Range	Default & Access	Description
15:8	Ch RW	orcvtctputime_7_0: Time (ick_susslow cycles) to wait (a.k.a. step 2) before comparing pads to Vref to determine if there is a receiver on the far end. Value should be by the following Table: Sus-clock rate P1269.8 P1271.x 25MHz - 27MHz 9 12 25MHz - 62.5MHz 35 43 37.5MHz - 100MHz 64 76 62.5MHz - 125MHz 83 98
7:0	6h RW	ontlputime_7_0: [after step 1 of pulldown] time (ick_susslow cycles) to wait (step 2) and let the pads leak upwards before comparing pads to Vref to determine if the pad exceeded Vref as a result of leakage.

17.18.11 TX_DWORD10 (tx_dword10)—Offset 28h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword10: [Port: 0xA6] + (280h + 28h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28				24				20				16				12				8				4				0										
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0									
isparead_7_0				reserved532				reserved531				ircvdtctmpout				idftcaptestsig				idftrcvddetectedtxn				idftrcvddetectedtxp				idftrcvddetectfinished				intlfinished				intlpass_3_0			

Bit Range	Default & Access	Description
31:24	X RO	ispareread_7_0: spare reg read
23:16	0h RO	reserved532: reserved
15:10	0h RO	reserved531: reserved
9	0h RO	ircvdtctcpout: Flash Comparator Output Value
8	X RO	idftcaptestsig: reserved
7	0h RO	idftrcvddetectedtxn: Receive Detect Result for Txn
6	0h RO	idftrcvddetectedtxp: Receive Detect Result for Txp
5	0h RO	idftrcvddetectfinished: Receive Detect Process status
4	X RO	intlfinished: indication of NTL finished
3:0	X RO	intlpass_3_0: the four outputs of NTL test



17.18.12 TX_DWORD11 (tx_dword11)—Offset 2Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword11: [Port: 0xA6] + (280h + 2Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00001000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
oselsparetxclk_2_0	ofrcdotprocess_2_0	ofrcgohighzdis	ofrcgohighzen	ofrcstrongpddis	ofrcstrongpden	ofrcctxclkrootdis	ofrcctxclkrooten	reserved537
				ofrcpwrmodel1	ofrcpwrmodel0s	ofrcpwrmodel0	ofrccmkeepadnen	ofrccmkeepadpen
					ofrccmkeepadndis	ofrccmkeepadpdis	omakedeepfifo	ofrcclatencyopt_2_0
							reserved536	ofrcrcvdtcten
							otxrcvdtctckrate_1_0	reserved535
								reserved534
								reserved533
								oneloopbacken

Bit Range	Default & Access	Description
31:29	0h RW	oselsparetxclk_2_0: Selects data to be used as alternative to fast clock. 000: DAC clock if in DAC mode - Default. 001: cri100m clock 010: i_obsontx_psg 011: i_obsontx_nsg 100: ick_txsymbolclk 101: icksusslow 110: ick_dac 111: spare
28:26	0h RW	ofrcdotprocess_2_0: forces the dotprocess information OXX - information of dot process comes from i_dotprocess[1:0] input bus. 100: p1271 dot1 101: p1271 dot4 110: p1271 dot8 111: NA
25	0h RW	ofrcgohighzdis: forces disabling of high-z output
24	0h RW	ofrcgohighzen: forces enabling of high-z output
23	0h RW	ofrcstrongpddis: forces disabling of strong pull-down
22	0h RW	ofrcstrongpden: forces enabling of strong pull-down
21	0h RW	ofrcctxclkrootdis: forces disable of tx-clock output.
20	0h RW	ofrcctxclkrooten: forces tx-clock to operate and drive clock out.
19	0h RO	reserved537: reserved
18	0h RW	ofrcpwrmodel1: when asserted. Forces L1 state
17	0h RW	ofrcpwrmodel0s: when asserted. Forces L0s state
16	0h RW	ofrcpwrmodel0: when asserted. Forces L0 state
15	0h RW	ofrccmkeepadnen: Forces enabling of common-mode keeping of PadN



Bit Range	Default & Access	Description
14	0h RW	ofrcmkeeppadpen: Forces enabling of common-mode keeping of PadP
13	0h RW	ofrcmkeeppadndis: Forces disabling of common-mode keeping of PadN
12	1h RW	ofrcmkeeppadpdis: Forces disabling of common-mode keeping of PadP
11	0h RW	omakedeeperfifo: Make FIFO deeper by 1 symbol clock cycle. Still not implemented. Implementation costs 10 flops in symb clock domain. Implementation is required for 8bits PISO only which is in next phase of products.
10:8	0h RW	ofrc latencyoptim_2_0: Changes the latency from loadgenen assertion to the sampling of 10bits data into fast-clock domain. The latency is determined by Fuses (through i_latencyoptim[1:0]) + ... 0XX =) + 0 (Not changing the latency.) 100 =) - 4UI 101 =) - 2UI 110 =) + 2UI 111 =) + 4UI Important Note: When changing the latency too high or too low is will wrap-around what might cause data loss on beginning or end of transmitting. If you decide to plan with the latency consider changing 'omakedeeperfifo' too
7	0h RO	reserved536: reserved
6	0h RW	ofrcrcvdtcten: force initiation of Tx-detect-Rx procedure
5:4	0h RW	otxrcvdtctcltrate_1_0: determines the clock rate in the flash comparator. 00 - use sus-clock as is (25MHz in phase2) default 01 - use sus-clock by 4 10 - use sus-clock by 2 11 - reserved In phase1 the rate was 2'b10 susfreq125MHz
3	0h RO	reserved535: reserved
2	0h RO	reserved534: reserved
1	0h RO	reserved533: reserved
0	0h RW	oneloopbacken: Near-End LoopBack enable



17.18.13 TX_DWORD12 (tx_dword12)—Offset 30h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword12: [Port: 0xA6] + (280h + 30h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
otxclkbytsel_1_0	ofrcdataratefit_2_0	odistxfelbpin	otxclkampbypsn	otxclkampbypsp	reserved539	odfxanamuxen	odfxanamuxsel_1_0	obs_tx_gated_supply_1_0
					reserved538			
						oobsdigselectupn_3_0	oobsdigselectupp_3_0	oobsdigselectdownn_3_0
								oobsdigselectdownp_3_0

Bit Range	Default & Access	Description
31:30	0h RW	otxclkbytsel_1_0: Select if to bypass the divided normal clock with some other clock. 2'b00: Don't bypass. Regular clock. 2'b01: bypass the RX clock - dataratefit must be '11' 2'b10: Reserved 2'b11: bypass the sparetxclk clock - dataratefit must be '11'
29:27	0h RW	ofrcdataratefit_2_0: Forces TX data rate 3'b0XX - don't force a value. get it from the I/F pin 3'b100 - no divide (2UIs per clock cyc) 3'b101 - divide by 2 3'b110 - divide by 4 3'b111 - divide by 8 - used also for bypassing with other clocks
26	0h RW	odistxfelbpin: when asserted - disables the i_txfelben pin at the interface and force it 0. (needed in case the pin is asserted in KX or sata1 mode)
25	0h RW	otxclkampbypsn: 0': Normal operation '1': Enable of the passgate connected from the analog clock N to the control of the DC correction cell. The feedback OTA is disabled.
24	0h RW	otxclkampbypsp: 0': Normal operation '1': Enable of the passgate connected from the analog clock P to the control of the DC correction cell. The feedback OTA is disabled.
23	0h RO	reserved539: reserved
22	0h RW	odfxanamuxen: Enables analog signals probing mux out. When enabled the Vref of Tx-detect-Rx circuit is observed. Note that only one lane is allowed to have a the analog mux enabled to avoid collisions.
21:20	0h RW	odfxanamuxsel_1_0: selects analog signal to be sent to analog port in common lane. This bus has no affect at all currently because there is only one analog signal for observation which is observed by odfxanamuxen
19:18	0h RW	obs_tx_gated_supply_1_0: Monitor gated vcc supply to Tx upar
17:16	0h RO	reserved538: reserved
15:12	0h RW	oobsdigselectupn_3_0: selects data to be sent to observability port output 'o_obsup_nsg'. Same mapping as oobsdigselectdownn[3:0]
11:8	0h RW	oobsdigselectupp_3_0: selects data to be sent to observability port output 'o_obsup_psg'. Same mapping as oobsdigselectdownp[3:0]





Bit Range	Default & Access	Description
11:8	0h RW	ovisa1_lanesel_3_0 : VISA Lane Select for Lane1. Selects the byte of data to be sent out on lane1.
7	0h RW	ovisa_bypass : VISA Bypass. Allows for signals to be passed asynchronously through VISA block. Applies to both lane0 and lane1. 0 : Flop signals in local VISA block (default) 1 : Bypass flops in local VISA block
6:4	0h RW	ovisa0_clkssel_2_0 : VISA Clock Select for Lane0. Selects the source synchronous clock to be used for data being sent on lane0.
3:0	0h RW	ovisa0_lanesel_3_0 : VISA Lane Select for Lane0. Selects data byte to be driven out of VISA-0 byte. Can be either clocked or unclocked data

17.18.16 TX_DWORD15 (tx_dword15)—Offset 3Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword15: [Port: 0xA6] + (280h + 3Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved551	reserved550	reserved549	reserved548	reserved547	reserved546	reserved545	reserved544	

Bit Range	Default & Access	Description
31:30	0h RO	reserved551 : reserved
29:24	0h RO	reserved550 : The slices used in R2 for DE (PstC=X,C=Y,PreC=Y)
23:22	0h RO	reserved549 : reserved
21:16	0h RO	reserved548 : The slices used in R2 for FS (PstC=X,C=Y,PreC=X)
15	0h RO	reserved547 : reserved
14:8	0h RO	reserved546 : The slices used in R1 for DE (PstC=X,C=Y,PreC=Y)
7	0h RO	reserved545 : reserved
6:0	0h RO	reserved544 : The slices used in R1 for FS (PstC=X,C=Y,PreC=X)



17.19 SATA Lane 1 Electrical Register Address Map

Table 207. Summary of SATA Lane 1 Electrical Message Bus Registers—0xA3 (Global Offset 2400h)

Offset	Register ID—Description	Default Value
0h	"PCS_DWORD0 (pcs_dword0)—Offset 0h" on page 2072	00010080h
4h	"PCS_DWORD1 (pcs_dword1)—Offset 4h" on page 2074	00600060h
8h	"PCS_DWORD2 (pcs_dword2)—Offset 8h" on page 2075	00000000h
Ch	"PCS_DWORD3 (pcs_dword3)—Offset Ch" on page 2077	5515ACAAh
10h	"PCS_DWORD4 (pcs_dword4)—Offset 10h" on page 2078	575555C1h
14h	"PCS_DWORD5 (pcs_dword5)—Offset 14h" on page 2078	00003E63h
18h	"PCS_DWORD6 (pcs_dword6)—Offset 18h" on page 2080	FFFFFFFFh
1Ch	"PCS_DWORD7 (pcs_dword7)—Offset 1Ch" on page 2080	00000009h
20h	"PCS_DWORD8 (pcs_dword8)—Offset 20h" on page 2081	000000C4h
24h	"PCS_DWORD9 (pcs_dword9)—Offset 24h" on page 2083	00000000h
28h	"PCS_DWORD10 (pcs_dword10)—Offset 28h" on page 2084	00000000h
2Ch	"PCS_DWORD11 (pcs_dword11)—Offset 2Ch" on page 2085	0F000000h
30h	"PCS_DWORD12 (pcs_dword12)—Offset 30h" on page 2087	00250F00h
34h	"PCS_DWORD13 (pcs_dword13)—Offset 34h" on page 2088	00000000h
38h	"PCS_DWORD14 (pcs_dword14)—Offset 38h" on page 2089	007A0018h
3Ch	"PCS_DWORD15 (pcs_dword15)—Offset 3Ch" on page 2090	04100300h
40h	"PCS_DWORD16 (pcs_dword16)—Offset 40h" on page 2092	01000001h
44h	"PCS_DWORD17 (pcs_dword17)—Offset 44h" on page 2093	01000001h
48h	"PCS_DWORD18 (pcs_dword18)—Offset 48h" on page 2095	00008080h
4Ch	"PCS_DWORD19 (pcs_dword19)—Offset 4Ch" on page 2096	00004F10h
50h	"PCS_DWORD20 (pcs_dword20)—Offset 50h" on page 2097	80808080h
54h	"PCS_DWORD21 (pcs_dword21)—Offset 54h" on page 2098	80808080h
58h	"PCS_DWORD22 (pcs_dword22)—Offset 58h" on page 2099	00000000h
5Ch	"PCS_DWORD23 (pcs_dword23)—Offset 5Ch" on page 2099	00180888h
60h	"PCS_DWORD24 (pcs_dword24)—Offset 60h" on page 2100	0001C020h

17.19.1 PCS_DWORD0 (pcs_dword0)—Offset 0h

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword0: [Port: 0xA3] + (2400h + 0h)

Op Codes:

0h - Read, 1h - Write

Default: 00010080h



October 2018
Document Number: 538136, Rev. 4.3



Access Method

pcs dword1: [Port: 0xA3] + (2400h + 4h)

Op Codes:

0h - Read, 1h - Write

Default: 00600060h

Bit Range	Default & Access	Description
31:24	0h RW	reg_tx fsm_4us_delay_7_0: Override counter value for 4 us delay in tx fsm lane reset to tx biasen delay
23	0h RW	reg_softreset_enable: When '1' the soft_reset_n bit will control the lane reset When '0' the hardware reset will control the lane reset Note for DP: In addition to soft_reset_n, which will reset both TX0 and TX 1 in the lane, the reg_tx1_soft_reset_n bit can be used to reset only TX1 in the lane and reg_tx2_soft_reset_n bit can be used to reset only TX2
22	1h RW	cri_rxeb_eiosenable: When 1 enables EIOS based Rx power down



Bit Range	Default & Access	Description
21	1h RW	cri_rxdigfiltsq_enable: When 1 enables unsquelch based Rx power up in P0 or P0s
20	0h RW	reg_txfsfm_delay_ovrd: Override enable bit for reg_txfsfm_4us_delay
19:16	0h RW	reg_txfsfm_4us_delay_11_8: Override counter value for 4 us delay in txfsfm lane reset to txbiasen delay
15:14	0h RW	reg_pclk_rate_1_0: Override for pclk_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
13:12	0h RW	reg_rate_1_0: Override for i_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
11:9	0h RW	reg_phymode_2_0: Override for PHY Mode Selection 000 = PCIE 001 = USB3 010 = GbE 011 = SATA/SAPIS 100 = Display 101 = DMI 110 = CIO 111 =Reserved
8	0h RW	reg_modeovren: When asserted selects register override bits for phymode, datawidth etc
7:6	1h RW	reg_datawidth: Override for Tx data interface width. 00 - Unused 01 - x8/x10 width (default) 10 - x16/x20 width 11 - x32/x40 width
5	1h RW	soft_reset_n: Active low soft reset override
4	0h RW	reg_diginelben: Override for near end digital loopback.
3	0h RW	reg_digifelben: Override for far end digital loopback
2	0h RW	reg_strapgroup_ovrden: Override Enable for Strap Group
1	0h RW	reg_yank_timer_done_b_ovrd: Override for yank_timer_done_b
0	0h RW	reg_yank_timer_done_b_ovrd_en: Override Enable for yank_timer_done_b

17.19.3 PCS_DWORD2 (pcs_dword2)—Offset 8h

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword2: [Port: 0xA3] + (2400h + 8h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_pibiasoff_delay_3_0	cri_sqdbexittimer_override_3_0	cri_sqdbentrytimer_override_5_0	reg_rxdrcgtsqsel_1_0	cri_reut_SlaveSideDataCheckingEn	cri_sqdbtimer_ovren	cri_rxpwrfsm_timer_ovren	reg_rxidle	cri_rxrawdata_sel
				cri_dynkalign_eco3302703_mode	cri_dynkalign_eco3302703_ovren	reg_rxpwrfsm_pibiasoff_ovrride	cri_reset_kalignlck	cri_ebptrrst
							cri_comdispfix	cri_forcebankhit
							cri_kalignmode_1_0	cri_skpprocdis
								cri_elasticbuffer_maskdis

Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_pibiasoff_delay_3_0: Override value for delay (in 2ns increments) between deassertion of opianclkbufen and opibiasen
27:24	0h RW	cri_sqdbexittimer_override_3_0: Rx squelch exit debounce timer
23:18	0h RW	cri_sqdbentrytimer_override_5_0: Rx squelch entry debounce timer
17:16	0h RW	reg_rxdrcgtsqsel_1_0: Squelch output select
15	0h RW	cri_reut_SlaveSideDataCheckingEn: Enable REUT slave side checking while in loopback slave
14	0h RW	cri_sqdbtimer_ovren: Squelch debounce timer override enable
13	0h RW	cri_rxpwrfsm_timer_ovren: Rx power management fsm timer override enable
12	0h RW	reg_rxidle: Chicken bit to override i_rxidle from controller and keep Rx in P0 or P0s
11	0h RW	cri_rxrawdata_sel: When asserted bypass K-align, 10b/8b decoder and Elastic buffer
10	0h RW	cri_dynkalign_eco3302703_mode: Kalign Mode Override Value When cri_dynkalign_eco3302703_ovren is set, this value selects kalignmode 0 - use register bits cri_kalignmode[1:0] to select kalignmode 1 - select the 4 COM kalign mode'
9	0h RW	cri_dynkalign_eco3302703_ovren: Kalign Mode Override Enable Overrides kalign mode select pin, allowing config bit kalignmode_override_val to select kalignmode.
8	0h RW	reg_rxpwrfsm_pibiasoff_ovrride: When asserted selects reg_rxpwrfsm_pibiasoff_delay[3:0]
7	0h RW	cri_reset_kalignlck: When asserted resets Kalign lock indication and Kalign is performed again. The conditions when this would assert includes and is not restricted to any power management states (L0s, L1) or polling quiet states etc.
6	0h RW	cri_ebptrrst: Global broadcast to all lanes that the Elastic Buffer pointers should be reset. This is a pulse and will be generated when we need to reset the pointers because of collision or various other reasons.
5	0h RW	cri_comdispfix: Chicken bit to force disparity in dynamic K-align mode



Bit Range	Default & Access	Description
4	0h RW	cri_forcebankhit : Chicken bit to enable data appear on NOA post k-align lock although k-align block is not achieving lock. This is only for NOA observeability and not for other purpose
3:2	0h RW	cri_kalignmode_1_0 : KALIGN Mode Select 00 = dynamic kalign all the time. Accounts for bit slips on incoming stream which can cause symbol to be detected on different bank 10 = dynamic kalign up to L0 x1 = static kalign (same as GDG). Assumes symbol always detected on same data bank
1	0h RW	cri_skpprocdis : SKIP Ordered-Set Processing Disable When this configuration bit is asserted, then SKIP ordered=sets will be ignored (in EB block). Used in Elastic buffer block. 0 = Normal operation. SKIP ordered=sets will be processed by the Elastic Buffer 1 = SKIP processing disabled.
0	0h RW	cri_elasticbuffer_maskdis : Config bit (chicken bit) to disable the masking logic after elec idle ordered set is seen

17.19.4 PCS_DWORD3 (pcs_dword3)—Offset Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs dword3: [Port: 0xA3] + (2400h + Ch)

Op Codes:

Op codes:
0h - Read, 1h - Write

Default: 5515ACAAh

31	28	24	20	16	12	8	4	0							
0	1	0	1	0	1	0	1	0							
cri_dfx_patbuf_55_48				cri_dfx_patbuf_63_56				cri_dfx_patbuf_71_64				cri_dfx_patbuf_79_72			

Bit Range	Default & Access	Description
31:24	55h RW	cri_dfx_patbuf_55_48: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
23:16	15h RW	cri_dfx_patbuf_63_56: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
15:8	ACh RW	cri_dfx_patbuf_71_64: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
7:0	AAh RW	cri_dfx_patbuf_79_72: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.



17.19.5 PCS_DWORD4 (pcs_dword4)—Offset 10h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword4: [Port: 0xA3] + (2400h + 10h)

Op Codes:

0h - Read, 1h - Write

Default: 575555C1h

31	28	24	20	16	12	8	4	0
0	1	0	1	0	1	1	0	1
cri_dfx_patbuf_23_16				cri_dfx_patbuf_31_24				cri_dfx_patbuf_47_40

Bit Range	Default & Access	Description
31:24	57h RW	cri_dfx_patbuf_23_16: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
23:16	55h RW	cri_dfx_patbuf_31_24: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
15:8	55h RW	cri_dfx_patbuf_39_32: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
7:0	C1h RW	cri_dfx_patbuf_47_40: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.

17.19.6 PCS_DWORD5 (pcs_dword5)—Offset 14h

Access Method

Type: Message Bus Register
(Size: 32 bits)


pcs_dword5: [Port: 0xA3] + (2400h + 14h)

Op Codes:

0h - Read, 1h - Write

Default: 00003E63h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	1	1	1
cri_dfx_patbuftrain	cri_dfx_prbspoly_2_0	cri_dfx_patbufsize_1_0	cri_dfx_patbufwidth	cri_dfx_patbuftrainovr	cri_dfx_marginmode	cri_dfx_chk_sel	cri_dfx_patchken	cri_dfx_patchgen
				cri_dfx_clrerrcnt	cri_dfx_lcereset	cri_dfx_lcestart		
						cri_dfx_patbuf_7_0		cri_dfx_patbuf_15_8



Bit Range	Default & Access	Description
31	0h RW	cri_dfx_patbuftrain: Pattern Buffer Manual Training When DFXPATBUFTRAINOVR and DFXLCESTART are asserted, this manually controls whether the Pattern Buffers are in training or have completed training. 0 : Send training patterns (default) 1 : Send contents of DFXPATBUF
30:28	0h RW	cri_dfx_prbspoly_2_0: PRBS Polynomial Select the polynomial to be used by the PRBS in the Pattern Generator and Pattern Checker. PRBS support 10b or 8b, which is indicated by the msb. 000 - $x^{16} + x^5 + x^4 + x^3 + 1$ (USB3/PCIe Scrambler) (8b) 001 - $x^{16} + x^{15} + x^{13} + x^4 + 1$ (SATA scrambler) (8b) 010 - $x^{31} + x^{28} + 1$ (8b) 011 - $x^7 + x^6 + 1$ (8b) 100 - $x^{15} + x^{14} + 1$ (10b) 101 - $x^{23} + x^{18} + 1$ (10b) 110 - $x^{31} + x^{28} + 1$ (10b) 111 - $x^7 + x^6 + 1$ (10b)
27:26	0h RW	cri_dfx_patbufsize_1_0: Pattern Buffer Size Select the size of the Pattern Buffer to use. The MSB will always be bit 79. The LSB will depend on this select and the DFXLCEDATAWIDTH (10b or 8b mode). 00 : full 80b buffer (Default) 01 : 70b (while in 10b mode), 56b (while in 8b mode) 10 : 40b (while in 10b mode), 32b (while in 8b mode) 11 : 10b (while in 10b mode), 8b (while in 8b mode)
25	0h RW	cri_dfx_patbufloop: Pattern Buffer Looping Enable Enables looping of the Pattern Buffer. By default, the contents of Pattern Buffer will be used once and stop. Alternatively, the Pattern Buffer will continue to loop until the DFXLCESTART is de-asserted. 0 : Run Pattern Buffer only once (default) 1 : Loop Pattern Buffer until stopped
24	0h RW	cri_dfx_patbufdwidth: Pattern Buffer Data Width Selects between 10 bit or 8 bit data width for the Pattern Buffer. Determines where in the Tx/Rx path the data is inserted/retrieved. 0 : 10b (default) 1 : 8b
23	0h RW	cri_dfx_patbuftrainovr: Pattern Buffer Training Override Enables manual training of the Pattern Buffer instead of the automated coordination between the Pattern Checker and Pattern Generator. When asserted, the DFXPATBUFTRAIN bit will be used to force when training is active and when it is complete. 0 : Automatic Training (default) 1 : Enable Manual Training
22	0h RW	cri_dfx_marginmode: Margin mode Overrides standard setup configurations for use with Eye Width Margining. 0 : Standard Mode (default) 1 : Margin Mode enabled
21	0h RW	cri_dfx_chk_sel: Pattern Checker 8b10b Select This determines where Rx data is compared, either in the 10-bit domain before decode or after 10b-)8b decoding. 0: 10b domain 1: 8b domain
20	0h RW	cri_dfx_patchken: Pattern Checker Enable 0 : Disable Pattern Checker (default) 1 : Enable Pattern Checker
19	0h RW	cri_dfx_patgenen: Pattern Generator Enable This will activate the DFX bypass muxes in the PCS Tx path. 0 : Disable Pattern Generator (default) 1 : Enable Pattern Generator
18	0h RW	cri_dfx_clrerrcnt: Clear Error Counter Resets the Pattern Checker's error counter. 0 : Error Counter allowed to run (default) 1 : Error Counter held in reset
17	0h RW	cri_dfx_lcereset: Local Compare Engine Reset Resets all components of the Local Compare Engine in both the Pattern Generator and the Pattern Checker. 0 : LCE not in reset (default) 1 : LCE in reset
16	0h RW	cri_dfx_lcestart: Local Compare Engine Start Controls the starting and stopping of the LCE. Allows for simultaneous or independent start across lanes. Once stopped, a DFXLCERESET is usually required. 0 : LCE stopped (default) 1 : LCE running
15:8	3Eh RW	cri_dfx_patbuf_7_0: Pattern Buffer Storage In 10b mode, the buffer is read as eight 10b chunks. The first 10 bits should not equal the Comma Symbol: '0011111010' (or its inversion '1100000101'). In 8b mode, the buffer is read as eight 10b chunks, where the 10th bit is unused and the 9th bit is the K-bit indicator. The first 10 bits should not equal the Comma Symbol: 'xx10111100'. DFXPATBUF[78] should not = '1'.
7:0	63h RW	cri_dfx_patbuf_15_8: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.



17.19.7 PCS_DWORD6 (pcs_dword6)—Offset 18h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword6: [Port: 0xA3] + (2400h + 18h)

Op Codes:

0h - Read, 1h - Write

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
cri_dfx_prbseed_7_0								
cri_dfx_prbseed_15_8								
cri_dfx_prbseed_23_16								
cri_dfx_prbseed_31_24								

Bit Range	Default & Access	Description
31:24	FFh RW	cri_dfx_prbseed_7_0: PRBS Seed Can be used for HVM determinism. The use of all zeroes can result in lockup.
23:16	FFh RW	cri_dfx_prbseed_15_8: PRBS Seed See cri_dfx_prbseed[7:0] description.
15:8	FFh RW	cri_dfx_prbseed_23_16: PRBS Seed See cri_dfx_prbseed[7:0] description.
7:0	FFh RW	cri_dfx_prbseed_31_24: PRBS Seed See cri_dfx_prbseed[7:0] description.

17.19.8 PCS_DWORD7 (pcs_dword7)—Offset 1Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword7: [Port: 0xA3] + (2400h + 1Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000009h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
dfx_cri_errcnt_7_0								
dfx_cri_errcnt_15_8								
i_rxcaldone								
dfx_cri_lcemgnerr								
cri_dfx_patgen2active								
dfx_cri_patbufallfail								
dfx_cri_patchkactive								
dfx_cri_patgenactive								
dfx_cri_lctraindone								
dfx_cri_lctrainactive								
reserved501								
cri_dfx_patgen2en								
cri_dfx_maxerrcnt_1_0								
cri_dfx_prbstraincnt_3_0								



Bit Range	Default & Access	Description
31:24	X RO	dfx_cri_errcnt_7_0: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
23:16	X RO	dfx_cri_errcnt_15_8: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
15	X RO	i_rxcaldone: RX Calibration Cycles Complete Indicator
14	X RO	dfx_cri_lcemgnerr: Local Compare Engine Margin Error Indicates that the error counter has reached its max value. This can be used by the Rx upartition during Margin Mode to determine when the eye width has closed.
13	X RO	cri_dfx_patgen2active: Pattern Generator 2 Active status indicator In a lane with two Tx paths, this indicates that the second Pattern Generator is in progress. The DFXPATGENACTIVE will only indicate that the first Pattern Generator is in progress.
12	X RO	dfx_cri_patbufallfail: Pattern Buffer All Fail status indicator Indicates that there has not been a single matching Pattern Buffer pattern. This could signify that an error occurred during training.
11	X RO	dfx_cri_patchkactive: Pattern Checker Active status indicator Indicates that the Pattern Checker is in progress (either Pattern Buffer or PRBS).
10	X RO	dfx_cri_patgenactive: Pattern Generator Active status indicator Indicates that the Pattern Generator is in progress (either Pattern Buffer or PRBS).
9	X RO	dfx_cri_lcetraindone: Local Compare Engine Training Done status indicator Indicates that the Pattern Checker training is completed (either Pattern Buffer or PRBS). The Pattern Checker is now synchronized to the Pattern Generator.
8	X RO	dfx_cri_lcetrainactive: Local Compare Engine Training Active status indicator Indicates that the Pattern Checker training is in progress (either Pattern Buffer or PRBS).
7	0h RW	reserved501: reserved
6	0h RW	cri_dfx_patgen2en: Pattern Generator 2 Enable In a lane with two Tx paths, this enables the second Pattern Generator. The DFXPATGENEN will enable the first Pattern Generator. 0 : Disable second Pattern Generator (default) 1 : Enable second Pattern Generator
5:4	0h RW	cri_dfx_maxerrcnt_1_0: Maximum Error Count Selectable maximum value that the DFXERRCNT can reach before the Local Compare Engine is automatically stopped. 00 : 2^{16} (default) 01 : 2^{10} 10 : 2^8 11 : 2^4
3:0	9h RW	cri_dfx_prbstraincnt_3_0: PRBS Training Count The number of consecutive cycles that the Pattern Checker's PRBS must be error free before it is considered synchronized. Default is 9.

17.19.9 PCS_DWORD8 (pcs_dword8)—Offset 20h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword8: [Port: 0xA3] + (2400h + 20h)

Op Codes:

0h - Read, 1h - Write

Default: 000000C4h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reg_partial	reg_slumber	reg_tx2_cdr_override_2_0	reg_cdr_override_2_0	reg_ebuffmode	reg_usedclockchannel_1_0	reg_usedclockchannel_ovrride	reg_gbl_ovrride	reg_tx1_pclkon_inp2
								reg_tx2_pclkon_inp2
								reg_tx2_txenable
								cri_rxeb_ptr_init_3_0
								reg_powerfsm_ovrride
								reg_suspend
								reg_pclkcfginput
								reg_useqclock
								cri_rxeb_hiwater_3_0
								cri_rxeb_lowwater_3_0

Bit Range	Default & Access	Description
31	0h RW	reg_partial: Override for i_partial
30	0h RW	reg_slumber: Override for i_slumber
29:27	0h RW	reg_tx2_cdr_override_2_0: Override for cdr_override strap for second tx2
26:24	0h RW	reg_cdr_override_2_0: Override for cdr_override strap
23	0h RW	reg_ebuffmode: Override for ebuffmode (no functionality in p1271 phase1 design)
22:21	0h RW	reg_usedclockchannel_1_0: Selects the active clock channel
20	0h RW	reg_usedclockchannel_ovrride: When asserted selects reg_usedclockchannel[1:0]
19	0h RW	reg_gbl_ovrride: Global override select
18	0h RW	reg_tx1_pclkon_inp2: When asserted keeps PCLK running in P2 mode. For DP this is used for Lane1
17	0h RW	reg_tx2_pclkon_inp2: When asserted keeps PCLK running in P2 mode. This is reserved (no impact) for PCIe/DMI and used for DP Lane2
16	0h RW	reg_tx2_txenable: Override for i_txenable for tx2
15:12	0h RW	cri_rxeb_ptr_init_3_0: Config override for initial value of Rx elastic buffer read pointer
11	0h RW	reg_powerfsm_ovrride: When asserted overrides for Tx power fsm are selected
10	0h RW	reg_suspend: Override for suspend
9	0h RW	reg_pclkcfginput: Override for pclkcfginput strap
8	0h RW	reg_useqclock: Override for useqclock; MUX select for I or Q clk for TX clocking
7:4	Ch RW	cri_rxeb_hiwater_3_0: Elastic buffer high watermark based on which SKP is removed



Bit Range	Default & Access	Description
3:0	4h RW	cri_rxeb_lowwater_3_0: Elastic buffer low watermark based on which SKP is added

17.19.10 PCS_DWORD9 (pcs_dword9)—Offset 24h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword9: [Port: 0xA3] + (2400h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved502	reg_strapgroup_4_0	reg_powerdown_1_0	reg_pcs_txcmnkeepdisable_ovrd	reg_straplane_5_0	reg_tx1_powerdown_override	reg_tx2_powerdown_override	reg_txdatavalid	reg_txdeemp_1_0
					reg_txmargin_2_0	reg_txswing	reg_txenable	reg_txterm_vcc_1_0
							reg_txdetrxlpbk	reg_txelectidle
							reg_txcompliance	reg_txoneszeroes
								reg_latencyoptim_1_0

Bit Range	Default & Access	Description
31	0h RW	reserved502: reserved
30:26	0h RW	reg_strapgroup_4_0: Override for i_strapgroup
25:24	0h RW	reg_powerdown_1_0: Override for i_powerdown
23	0h RW	reg_pcs_txcmnkeepdisable_ovrd: Override for ipcs_txcmnkeepdisable input 0: Use value on ipcs_txcmnkeepdisable input pin to determine o_txgohighz state in P2/slumber 1: Force pcs_txcmnkeepdisable to 0
22:18	0h RW	reg_straplane_5_0: Override for i_straplane
17	0h RW	reg_tx1_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx1 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
16	0h RW	reg_tx2_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx2 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
15	0h RW	reg_txdatavalid: Override for i_txdatavalid (register is NOT used)
14:13	0h RW	reg_txdeemp_1_0: Override for i_txdeemph



Bit Range	Default & Access	Description
12:10	0h RW	reg_txmargin_2_0: Override for i_txmargin
9	0h RW	reg_txswing: Override for i_txswing
8	0h RW	reg_txenable: Override for i_txenable
7:6	0h RW	reg_txterm_vcc_1_0: Override for txterm_vcc strap
5	0h RW	reg_txdetrxlpbk: Override for i_txdetrxlpbk
4	0h RW	reg_txelectidle: Override for i_txelectidle
3	0h RW	reg_txcompliance: Override for i_txcompliance
2	0h RW	reg_txoneszeroes: Override for i_txoneszeroes
1:0	0h RW	reg_latencyoptim_1_0: Override for i_latencyoptim

17.19.11 PCS_DWORD10 (pcs_dword10)—Offset 28h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword10: [Port: 0xA3] + (2400h + 28h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_timer_WAIT_RX_PL_CLK_3_0	reg_rxpwrfsm_timer_ENABLE_RX_3_0	reg_rxpwrfsm_timer_RX_SEQEN_3_0	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0	reg_clk_valid_cnt_7_0	reg_rxterm	reg_rxpolarity	reg_rxeqtrain	reg_rxsquelchen
								cri_rxpwrfsm_sqentimer_ovrden
								reg_rxintfiter_ovrden
								reg_rxintfiter_l
								reg_clk_valid_cnt_ovrd



Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PI_CLK_3_0: Rx Power state m/c timer value used to enable PI clock
27:24	0h RW	reg_rxpwrfsm_timer_ENABLE_RX_3_0: Rx Power state m/c timer value used to enable receivers
23:20	0h RW	reg_rxpwrfsm_timer_RX_SQEN_3_0: Rx Power FSM Rx Squelch Enable Timer Override Value Affect squelch enable startup sequence during 'synchronous' squelch startup mode. 0000 - Invalid 0001 - 1 susclk period ... 1111 - 15 susclk period
19:16	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0: Rx Power state m/c timer value used to enable PI BIAS
15:8	0h RW	reg_clk_valid_cnt_7_0: Over ride value for clock valid delay in clock top block before toggling phystatus.
7	0h RW	reg_rxterm: Override for i_rxterm
6	0h RW	reg_rxpolarity: Override for i_rxpolarity
5	0h RW	reg_rxeqtrain: Override for i_rxeqtrain
4	0h RW	reg_rxsquelchen: Override for i_rxsquelchen
3	0h RW	cri_rxpwrfsm_sqentimer_ovrden: Squelch Enable Timer Override Enable Used to override the squelch enable timer in PCS with the timer value set by the Rx Squelch Enable timer register (reg_rxpwrfsm_timer_RX_SQEN[3:0]).
2	0h RW	reg_rxintfltren_override: Rx Integral Filter Override Select 0: selects i_rxintfltren_I input pin. 1: selects reg_rxintfltren_I register
1	0h RW	reg_rxintfltren_I: Override for Rx integral filter enable i_rxintfltren_I
0	0h RW	reg_clk_valid_cnt_ovrd: Override enable for reg_clk_valid_cnt

17.19.12 PCS_DWORD11 (pcs_dword11)—Offset 2Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword11: [Port: 0xA3] + (2400h + 2Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0F000000h



31	28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																						
0	0	0	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
reserved505				reg_tx2_stagger_mask_4_0				i_clkbuf_iclken_ovrd				i_clkbuf_qclken_ovrd				reserved503				i_clkbuf_txclkmuxen_ovrd				reserved504				reg_tx2_cmmdisparity				reg_tx1_ctrl_override				reg_tx2_ctrl_override				reg_tx2_txterm_vcc_1				reg_tx2_txterm_vcc_0				reg_tx2_txdetrxlpbk				reg_tx2_txelectidle				reg_tx2_txcompliance				reg_tx2_txoneszeroes				reg_tx2_powerdown_1_0				o_captesten_h				i_captestout				fuse_override				i_clkbuf_ibiasen_ovrd				reg_lanedeskew_strap_ovrd				reg_lane_reverse				reg_left_txfifo_rst_master				reg_right_txfifo_rst_master																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
reserved506																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																</			

Bit Range	Default & Access	Description
31:30	0h RW	reserved505: reserved
29	0h RW	reserved506: reserved
28:24	Fh RW	reg_tx2_stagger_mask_4_0: Mask bit for lane number. Used to group lanes for staggering. for tx2
23	0h RW	i_clkbuf_iclken_ovrd: I-Clock Override for the DataLane
22	0h RW	i_clkbuf_qclken_ovrd: Q-Clock Override for the DataLane
21	0h RW	reserved503: reserved
20	0h RW	i_clkbuf_txclkmuxen_ovrd: TX Clock Selection Mux Override
19	0h RW	reserved504: reserved
18	0h RW	reg_tx2_cmmdisparity: Sets the initial disparity during Compliance Measurement Mode, used together with pcs_txcompliance pulse. For TX2 0 = set negative disparity 1 = set positive disparity
17	0h RW	reg_tx1_ctrl_override: overrides input parameter/controls for tx1
16	0h RW	reg_tx2_ctrl_override: overrides input parameter/controls for tx2
15	0h RW	reg_tx2_txterm_vcc_1: Override for txterm_vcc strap[1] for tx2 in DP family. Override enable for inspecmm for non-DP families (reg_inspecmm_ovrd_enable).
14	0h RW	reg_tx2_txterm_vcc_0: Override for txterm_vcc strap[0] for tx2 in DP family. Override value for inspecmm for non-DP families (reg_inspecmm_ovrd_value).
13	0h RW	reg_tx2_txdetrxlpbk: Override for i_txdetrxlpbk for tx2



Bit Range	Default & Access	Description
31	0h RW	reg_txfsn_200ns_ovrd : Override reg_txfsn_200ns_delay+G2
30:24	0h RW	reg_txfsn_200ns_delay_6_0 : Override value of counter for 200ns delay between txen and txloadgenen
23	0h RW	reg_loadgen2txen_fall_ovrd : reserved
22:20	2h RW	reg_tx2_stagger_mult_2_0 : Stagger multiplier for Rx (or Tx1) (Same decoding as tx1_stagger_mult[2:0]) For Display, this multiplier applies to Tx2. For non-Display PHYs, this multiplier applies to the Rx. The multiplier limit for the Rx is 8x (3'b100); anything beyond that is invalid.
19	0h RW	reg_lanestagger_by_group : When = 1, uses group number for lane staggering, by devalues lane number is used.
18:16	5h RW	reg_tx1_stagger_mult_2_0 : Stagger multiplier for Tx (or Tx1) These bits set the lane staggering multiplier for the transmitter based on the 'linkclk' period. 000 - 0x 001 - 1x 010 - 2x 011 - 4x 100 - 8x 101 - 16x 110 - 32x 111 - 64x For Display, this multiplier applies to Tx1.
15:14	0h RW	reserved509 : reserved
13	0h RW	reserved510 : reserved
12:8	Fh RW	reg_tx1_stagger_mask_4_0 : Mask bit for lane number. Used to group lanes for staggering
7	0h RW	reserved507 : reserved
6	0h RW	reg_lanestagger_strap_ovrd : When 1 config override for lane stagger strap (bits [4:0] of this register) is selected
5	0h RW	reserved508 : reserved
4:0	0h RW	reg_lanestagger_strap_4_0 : Override for lane stagger strap

17.19.14 PCS_DWORD13 (pcs_dword13)—Offset 34h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword13: [Port: 0xA3] + (2400h + 34h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
visa_en	reserved512	visa_clk_sel1_4_0	visa_lane_sel1_7_0	visa_bypass	reserved511	visa_clk_sel0_4_0	visa_lane_sel0_7_0	



Bit Range	Default & Access	Description
29	0h RW	reg_slowclk_ovrden: Slow Clock Override Enable When set 1'b1, reg_slowclocken and reg_sclk250en are valid. When cleared 1'b0, output of FSM will drive slow clock enable.
28:24	0h RW	reg_txloadgenen2txen_fall_delay_4_0: reserved
23:20	7h RW	o_cmlmuxsthsel_3_0: CML Mux strength control
19:16	Ah RW	o_cmlsthsel_3_0: RX CML driver strength
15:12	0h RW	o_pcisel_3_0: I clk phase correction control
11:8	0h RW	o_pcqsel_3_0: Q clk phase correction control
7	0h RW	o_phaseicen: Iclk phase correction enable.
6	0h RW	o_phaseqcen: Qclk phase correction enabled.
5	0h RW	o_pcbypass: Phase correction bypass.
4	1h RW	o_slowclocken: Slow clock 1 enable Only valid if slow clock override enable is set 1'b1
3	1h RW	o_sclk250en: Slow clock 2 enable Only valid if slow clock override enable is set 1'b1
2:0	0h RW	cri_kalign_com_cnt: Upper 3 bits of a 7-bit counter that counts number of COM characters found. Used for special SAPIS mode where spread spectrum clocking can be utilized. Note: This register is used in conjunction with another PCS register cri_kalignmode[1:0] = 10 Register value Minimum COM count to achieve symbol lock 000 - 18 001 - 34 010 - 50 011 - 66 100 - 82 101 - 98 110 - 114 111 - 130

17.19.16 PCS_DWORD15 (pcs_dword15)—Offset 3Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword15: [Port: 0xA3] + (2400h + 3Ch)

Op Codes:


0h - Read, 1h - Write

Default: 04100300h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_powermode_del_cfg_fifoctrlgen_2_0	reg_clkbuf_en_ovrd	o_deskewen	reserved514	reserved515	reserved516	o_obsselectlocaldown_h	o_obsselectlocalup	o_obsselectm1datadown
						o_obsselectm1dataup	o_obsselectm2_1_0	o_obsselectm1_1_0
						reg_clkbuf_stagger_cnt_1_0	reserved513	reg_clkbuf_stagger_cnt_9_2

Bit Range	Default & Access	Description
31:29	0h RW	reg_powermode_del_cfg_fifoctrlgen_2_0: Controls the delay from powermode change to Tx PCS data fifo pointer de-assertion 000 = 'd280 001 = 'd20 010 = 'd48 011 = 'd80 100 = 'd144 101 = 'd538 110 = 'd800 111 = 'd1023
28	0h RW	reg_clkbuf_en_ovrd: ClkBuf Override Enable When asserted, the overrides for the CLKBUF (i_clkbuf_*_ovrd) are selected. Enable TX clock selection MUX
27	0h RW	o_deskewen: DFT output deskew enable
26	1h RW	reserved514: reserved
25	0h RW	reserved515: reserved
24	0h RW	reserved516: reserved
23	0h RW	o_obsselectlocaldown_h: N/N+1 Abut Obs-UP output control Selects local 'down' signals from current lane Tx1 (M1) and Rx/Tx2 (M2) or the iabut_obsdown inputs to be driven on oabut_obsup outputs. 0: select signals from the iabut_obsup inputs 1: select 'down' signals from the current lane
22	0h RW	o_obsselectlocalup: N/N+1 Abut Obs DOWN output control Selects local 'up' signals from current lane Tx1 (M1) and Rx/Tx2 (M2) or the iabut_obsdown inputs to be driven on oabut_obsdown outputs and to the current lane's Tx1 or Tx2. 0: select signals from the iabut_obsdown inputs 1: select 'up' signals from the current lane
21	0h RW	o_obsselectm1datadown: N/N+1 M1-M2 Down data control Selects local 'down' data input signals from M1 (Tx1) or M2 (Tx2 or Rx) to be sent to the obsselectlocaldown muxes that are controlled by bit 7. 0: select M2 (Tx2 or Rx) 1. select M1 (Tx1)
20	1h RW	o_obsselectm1dataup: N/N+1 M1-M2 Up data control Selects local 'up' data input signals from M1 (Tx1) or M2 (Tx2 or Rx) to be sent to the obsselectlocalup muxes that are controlled by bit 6. 0: select M2 (Tx2 or Rx) 1. select M1 (Tx1)
19:18	0h RW	o_obsselectm2_1_0: N/N+1 M2 Output Select This controls which signals are sent to Tx2. These outputs are not used when M2 is a Receiver. 00: iabut_obsdown 01: iabut_obsup 10: output of local 'up' select muxes that are controlled by bit 6 11: GND
17:16	0h RW	o_obsselectm1_1_0: N/N+1 M1 Output Select This controls which signals are sent to Tx1. 00: iabut_obsdown 01: iabut_obsup 10: output of local 'up' select muxes that are controlled by bit 6 11: GND
15:14	0h RW	reg_clkbuf_stagger_cnt_1_0: Counter override value for staggering delay of clock buffer control signals.



Bit Range	Default & Access	Description
13:8	3h RW	reserved513: reserved
7:0	0h RW	reg_clkbuf_stagger_cnt_9_2: Counter override value for staggering delay of clock buffer control signals.

17.19.17 PCS_DWORD16 (pcs_dword16)—Offset 40h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword16: [Port: 0xA3] + (2400h + 40h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h

31		28		24		20		16		12		8		4		0	
0		0		0		0		0		0		0		0		1	
squelch_shunt_ovrd_en		squelch_shunt_cnt_2_0		reserved520		i_rxsq fsm_timer sel		i_rxsq_asyncmode_h		i_rxsquelchstby_h		reserved519		cri_dfx_evenoddmask_1_0		reserved518	
												cri_dfx_lce2patsrc_1_0		cri_dfx_lcepatsrc_1_0		reserved517	
														txloadgen_ctr_val		cri_txhighpowerei_ovrden	
																cri_tx1highpowerei_ovrdval	
																cri_tx2highpowerei_ovrdval	
																p2_fast_exit_en	

Bit Range	Default & Access	Description
31	0h RW	squelch_shunt_ovrd_en: Squelch Shunt Pulse Duration Override Enable Overrides the hardware default shunt pulse duration value 1: Shunt Pulse Duration Override Enable 0: Shunt Pulse Duration Override Disable
30:28	0h RW	squelch_shunt_cnt_2_0: Squelch Shunt Pulse Duration Override Value 000 = No shunt pulse generated 001 = 1 susclk cycles ... 111 = 7 susclk cycles
27	0h RW	reserved520: reserved
26	0h RW	i_rxsq fsm_timer sel: Squelch FSM Timer Select 0 - Selects 25Mhz values for squelch timer and shunt pulse generation . 1 - Selects 100Mhz values for squelch timer and shunt pulse generation. This register is applicable to synchronous squelch startup mode.
25	0h RW	i_rxsq_asyncmode_h: Squelch Async Startup Mode This squelch startup mode is power state independent. When enabled, the squelchen signal sent to Modphy will asynchronously enable the squelch detector circuit. Once enabled, the squelch detector circuit will asynchronously send an unfiltered/unqualified squelch indication signal out of Modphy. The squelch indication signal will initially be unstable, so it is up to the consumer of this signal to filter/qualify it accordingly. The asynchronous squelch startup mode is beneficial because it significantly reduces the squelch startup latency. This decrease in latency does come at the cost of slightly higher power when squelch is not enabled as the IREF and Squelch Keeper circuits must remain enabled. When disabled, the squelch startup sequence is synchronous in nature and the squelch indication signal sent out of Modphy is stable/filtered.
24	1h RW	i_rxsquelchstby_h: Fast Squelch Enable Mode Bit to keep the IREF (ivrefen) on during P2 and reduce squelch startup time.



Bit Range	Default & Access	Description
23:18	0h RW	reserved519: reserved
17:16	0h RW	cri_dfx_evenoddmask_1_0: Pattern Checker Even/Odd Bit Error Mask Select 00 : no masking; all errors will be counted 01: select odd path, mask even path; only errors on bits [1,3,5,7,9] are counted 10: select even path, mask odd path; only errors on bits [0,2,4,6,8] are counted 11: reserved;
15:12	0h RW	reserved518: reserved
11:10	0h RW	cri_dfx_lce2patsrc_1_0: Local Compare Engine 2 Pattern Source In a lane with two Tx paths, this selects between using Pattern Buffer or PRBS as source of LCE patterns for the second LCE. The DFXLCEPATSR selects for the first LCE. 0 : Pattern Buffer (default) 1 : PRBS
9:8	0h RW	cri_dfx_lcepatsrc_1_0: Local Compare Engine Pattern Source. Selects between using Pattern Buffer or PRBS as source of LCE patterns. 00 : Pattern Buffer; use LCE default training pattern; 01: Pattern Buffer; use the first 40b of pattern buffer for training. 10: PRBS; use LCE default training pattern; 11: PRBS; use the first 40b of pattern buffer for training.
7:6	0h RW	reserved517: reserved
5:4	0h RW	txloadgen_ctr_val: TxLoadGen Pulse Width Control Controls the pulse width of txloadgenen from PCS to Tx upar. This is used in MAC initiated digital far end loopback mode in PCIE family. 00 - txloadgenen pulse width is 4 symbol clocks (default) 01 - txloadgenen pulse width is 2 symbol clocks 10 - txloadgenen pulse not generated 11 - txloadgenen pulse width is 6 symbol clocks
3	0h RW	cri_txhighpowerei_ovrden: TxHighPowerEI Override Mode Enable 0 - TxHighPowerEI to TxuPAR driven by Logic 1 - TxHighPowerEI to TxuPAR driven by override register value(s).
2	0h RW	cri_tx1highpowerei_ovrdval: Tx1HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx1HighPowerEI disabled 1 - Tx1HighPowerEI enabled
1	0h RW	cri_tx2highpowerei_ovrdval: Tx2HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx2HighPowerEI disabled 1 - Tx2HighPowerEI enabled
0	1h RW	p2_fast_exit_en: P2 Fast Exit Mode Enable Common Mode sustainer will be enabled during P2 when this bit is asserted. 1: P2 Fast Exit Mode Enable 0: P2 Fast Exit Mode Disable

17.19.18 PCS_DWORD17 (pcs_dword17)—Offset 44h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword17: [Port: 0xA3] + (2400h + 44h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h



Access Method

pcs_dword19: [Port: 0xA3] + (2400h + 4Ch)

0h - Read, 1h - Write

31				28				24				20				16				12				8				4				0																															
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1	1	1	0	0	0	1	0	0	0	0	0	0	0	0																												
iamp0calcode_7_0								cal_num								cal_start				cal_type				cal_inv				cal_rst				calclkdivsel_1_0				reserved525				calib_done				cal_fb_count				adc_acctime_1_0				adc_clkssel_1_0				adcmuxsel_2_0				adcstart			

Intel Atom[®] Processor E3800 Product Family
Datasheet
2096



Bit Range	Default & Access	Description
17	0h RW	cal_inv: Calibration Feedback Invert Inverse the logic of counter increment decrement depends on the FB
16	0h RW	cal_rst: Calibration Reset Reset state machine
15:14	1h RW	calclkdivsel_1_0: Calibration Clock Divider Select 00 - div2 of CRICLK 01 - div4 of CRICLK 10 - div8 of CRICLK 11 - div16 of CRICLK Note: Calibration clock period target is 160nS
13	0h RO	reserved525: reserved
12	0h RO	calib_done: Calibration Completion Indicator
11:8	Fh RW	cal_fb_count: Calibration Cycle Count Limit per target Each calibration target is clocked for 16 * cal_fb_count clock cycles. Max is 240 clock cycles (default)
7:6	0h RW	adc_acctime_1_0: ADC Accumulation Time Select This selects the conversion time for the Analog to Digital Converter. ADC clock frequency is set by bits [5:4] in this register. 00: 1024 ADC clocks (default) 01: 512 ADC clocks 10: 256 ADC clocks 11: Infinite (ADC in continuous accumulation) Note: If LRC mode and set to '11', then adctime = 1024cycles.
5:4	1h RW	adc_clkssel_1_0: ADC Clock Frequency Select This selects the input clock frequency to the Analog to Digital Converter. 00: CRI clock div2 01: CRI clock div1 10: CRI clock div4 11: CRI clock div8 NOTE: Target is 50Mhz.
3:1	0h RW	adcmuxsel_2_0: ADC Analog Mux Select This selects the analog voltage input to the Analog to Digital Converter. 000: Vss 001: Vcc 010: LRC R1 voltage divider 011: LRC sense net 100: input from Tx 101: input from Rx (or Tx #2) 110: input from Clock 111: input from reference generator Note: Mux select is controlled by the FSM during LRC.
0	0h RW	adcstart: ADC start This bit resets the ADC counter and starts a new acquisition. This bit should remain 1'b1 while the ADC is active and acquiring data. 0: Disable ADC logic and analog circuitry 1: Enable ADC and start A2D conversion.

17.19.21 PCS_DWORD20 (pcs_dword20)—Offset 50h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword20: [Port: 0xA3] + (2400h + 50h)

Op Codes:

0h - Read, 1h - Write

Default: 80808080h

31	28	24	20	16	12	8	4	0
1	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
rxvgarcode_7_0	rxtermrcode_7_0	txrrcode_7_0	irefrcode_7_0					



Access Method

pcs dword21: [Port: 0xA3] + (2400h + 54h)

0h - Read, 1h - Write

31	28	24	20	16	12	8	4	0							
1	0	0	0	0	0	0	0	0							
rxvgarscale_7_0				rxtermrscale_7_0				txrcscale_7_0				irefrscale_7_0			

Bit Range	Default & Access	Description
31:24	80h RW	rxvgarcscale_7_0: Rx VGA Rcomp Scale Multiplier The LRC code is multiplied by this value before applying the offset to generate the final rxvgarccode. 0xFF: Scale=1.99219 0xC0: Scale=1.5 0x80: Scale=1.0 0x40: Scale=0.5 0x00: Scale=0
23:16	80h RW	rxtermrcscale_7_0: Rx Termination Rcomp Scale Multiplier The LRC code is multiplied by this value before applying the offset to generate the final rxtermrcode. 0xFF: Scale=1.99219 0xC0: Scale=1.5 0x80: Scale=1.0 0x40: Scale=0.5 0x00: Scale=0
15:8	80h RW	txrcscale_7_0: Tx Rcomp Scale Multiplier The LRC code is multiplied by this value before applying the offset to generate the final txrrcode. 0xFF: Scale=1.99219 0xC0: Scale=1.5 0x80: Scale=1.0 0x40: Scale=0.5 0x00: Scale=0
7:0	80h RW	irefrcscale_7_0: Iref Rcomp Scale Multiplier The LRC code is multiplied by this value before applying the offset to generate the final irefrrcode. 0xFF: Scale=1.99219 0xC0: Scale=1.5 0x80: Scale=1.0 0x40: Scale=0.5 0x00: Scale=0



Bit Range	Default & Access	Description
16	1h RW	cri_lanereset_clkgatectl : 1: The assertion of lane reset will have the effect of gating the susclk and de-asserting the internal laneclkreq. This mode is only valid when the data lane dynamic clock gating mode is set to a non-zero value (i.e. 01, 10, and 11). 0: The assertion of lane reset will have no effect on the gating of susclk and state of the internal laneclkreq signal.
15	1h RW	cri_lanereqforce : Controls whether the internal laneclkreq will be forced to 1 or 0 when cfg_data_dynclkgate_mode is set to 00 or 10. 1: force laneclkreq high 0: force laneclkreq low. This mode will likely be used when one of the lanes is disabled while other lanes in the family are enabled. In this case the internal laneclkreq of the disabled lane should be de-asserted (not influencing the clk gating decision)
14:10	10h RW	cri_susclkdisable_delay_4_0 : This register will control the number of cycles to delay the susclk enable de-assertion, in addition to the de-assertion of the laneclkreq signal sent out of the datalane. The susclk enable must be continuously de-asserted for the duration of this delay in order for the de-asserted state to be captured by the clock gating controller. 5'b00000 - 0 Cycle Delay 5'b00001 - 1 Cycle Delay 5'b00010 - 2 Cycle Delay 5'b11110 - 30 Cycle Delay 5'b11111 - 31 Cycle Delay
9:8	0h RW	cri_data_dynclkgate_mode_1_0 : Controls the dynamic clock gating behavior in the data lane. 00 - susclk gating and laneclkreq disabled (Forced to configured value). In this mode the susclk will not be gated under any circumstances and the laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 01 - susclk gating disabled, laneclkreq enabled . In this mode the susclk will not be gated under any circumstances. The laneclkreq sent out of the data lane will toggle based on whether the lane power state, susclk need and the previous lane's laneclkreq signal. 10 - susclk gating enabled, laneclkreq disabled (forced to configured value) - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 11 - susclk gating and laneclkreq enabled - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the data lane will toggle based on the lane power state, susclk need and the previous lane's laneclkreq signal.
7	0h RW	cri_eios_waittime_ovren : EIOS Wait Time Override Enable for Rx Turn OFF 0: hardware value for EIOS wait timer is selected. 1: selects cri_eios_waittime[6:0]
6:0	20h RW	cri_eios_waittime_6_0 : EIOS Wait Time for Rx Turn OFF Represents override value timer in PCS that comes into play during EIOS based turn off Rx (Rx L0s) 0000000 - Timer is bypassed 0000001 - 1 PLL link clock period delay (2ns) 0000010 - 2 PLL link clock period delay (4ns) ... 0100000 - 32 PLL link clock periods delay (64ns) - default



Offset	Register ID—Description	Default Value
0h	"TX_DWORD0 (tx_dword0)—Offset 0h" on page 2102	2600003Ah
4h	"TX_DWORD1 (tx_dword1)—Offset 4h" on page 2103	20000000h
8h	"TX_DWORD2 (tx_dword2)—Offset 8h" on page 2104	5580983Ah
Ch	"TX_DWORD3 (tx_dword3)—Offset Ch" on page 2104	0C782040h
10h	"TX_DWORD4 (tx_dword4)—Offset 10h" on page 2106	2B404D55h
14h	"TX_DWORD5 (tx_dword5)—Offset 14h" on page 2107	00000000h
18h	"TX_DWORD6 (tx_dword6)—Offset 18h" on page 2107	1F200000h
1Ch	"TX_DWORD7 (tx_dword7)—Offset 1Ch" on page 2108	0038383Fh
20h	"TX_DWORD8 (tx_dword8)—Offset 20h" on page 2109	0600AA80h
24h	"TX_DWORD9 (tx_dword9)—Offset 24h" on page 2110	00430C06h
28h	"TX_DWORD10 (tx_dword10)—Offset 28h" on page 2111	00000000h
2Ch	"TX_DWORD11 (tx_dword11)—Offset 2Ch" on page 2112	00001000h
30h	"TX_DWORD12 (tx_dword12)—Offset 30h" on page 2113	00000000h
34h	"TX_DWORD13 (tx_dword13)—Offset 34h" on page 2115	00000000h
38h	"TX_DWORD14 (tx_dword14)—Offset 38h" on page 2116	00400000h
3Ch	"TX_DWORD15 (tx_dword15)—Offset 3Ch" on page 2117	00000000h
40h	"TX_DWORD16 (tx_dword16)—Offset 40h" on page 2118	00008A00h

17.20.1 TX DWORD0 (tx_dword0)—Offset 0h

Type: Message Bus Register
(Size: 32 bits)

tx dword0: [Port: 0xA3] + (2480h + 0h)

0h - Read, 1h - Write

31				28				24				20				16				12				8				4				0			
0	0	1	0	0	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	0	1	0				
reserved504				ofrcr1main3_6_0				reserved503				reserved502				reserved501				reserved500				ofrcdrv1r2				ofrcr1main0_6_0							

Bit Range	Default & Access	Description
31	0h RO	reserved504: reserved



Bit Range	Default & Access	Description
30:24	26h RW	ofrcr1main3_6_0 : number of slices in active R1 for swing 3 (DE)
23	0h RO	reserved503 : reserved
22:16	0h RO	reserved502 : reserved
15	0h RO	reserved501 : reserved
14:8	0h RO	reserved500 : reserved
7	0h RW	ofrcdrv1r2 : enable forcing number of used slices in all fir levels.
6:0	3Ah RW	ofrcr1main0_6_0 : number of slices in active R1 for swing 0 (FS)

17.20.2 TX_DWORD1 (tx_dword1)—Offset 4h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword1: [Port: 0xA3] + (2480h + 4h)


Op Codes:

0h - Read, 1h - Write

Default: 20000000h

31				28				24				20				16				12				8				4				0			
0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
reserved510				ofcr2short3_5_0				reserved509				reserved508				reserved507				reserved506				reserved505				ofcr2short0_5_0							

Bit Range	Default & Access	Description
31:30	0h RO	reserved510: reserved
29:24	20h RW	ofrcr2short3_5_0: number of slices in R2 for swing 3 (DE) MSB has no effect.
23:22	0h RO	reserved509: reserved
21:16	0h RO	reserved508: reserved
15:14	0h RO	reserved507: reserved
13:8	0h RO	reserved506: reserved



October 2018
Document Number: 538136, Rev. 4.3



Type: Message Bus Register
(Size: 32 bits)

Op Codes:

0h - Read, 1h - Write

31	28	24	20	16	12	8	4	0
0	0	1	0	1	0	1	1	0
ow2tapdeemph9p5_7_0								
0	0	1	0	0	0	0	0	0
ow2tapdeemph6p0_7_0								
0	1	0	0	1	1	0	1	0
ow2tapgen2deemph3p5_7_0								
0	1	0	1	0	1	0	1	0
ow2tapgen1deemph3p5_7_0								

Intel Atom® Processor E3800 Product Family
Datasheet
2106



17.20.6 TX_DWORD5 (tx_dword5)—Offset 14h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword5: [Port: 0xA3] + (2480h + 14h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
ocalcinit	reserved515	reserved514	reserved513	reserved512				

Bit Range	Default & Access	Description
31	0h RW	ocalcinit: initiate calculation of swing-control circuit. rewrite to '0' and '1' to reinitiate the calculation
30:24	0h RO	reserved515: reserved
23:16	0h RO	reserved514: reserved
15:8	0h RO	reserved513: reserved
7:0	0h RO	reserved512: reserved

17.20.7 TX_DWORD6 (tx_dword6)—Offset 18h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword6: [Port: 0xA3] + (2480h + 18h)

Op Codes:

0h - Read, 1h - Write

Default: 1F200000h

31	28	24	20	16	12	8	4	0
0	0	0	1	1	1	1	0	0
reserved520	onswbypass_6_0	reserved519	opswbypass_6_0	reserved518	reserved517	ocalcont	reserved516	

Bit Range	Default & Access	Description
31	0h RO	reserved520: reserved



Access Method

tx dword7: [Port: 0xA3] + (2480h + 1Ch)

0h - Read, 1h - Write

31				28				24				20				16				12				8				4				0															
0	0	0	0	0	0	0	0	0	0	1	1	1	0	0	0	0	0	1	1	1	0	0	0	0	0	1	1	1	1	1	1																
reserved527				reserved526				reserved525				reserved524				reserved523				oslrctrlr2_l_2_0				oslrctrlr2_h_2_0				reserved522				oslrctrl_l_2_0				oslrctrl_h_2_0				reserved521				or2bypass_5_0			

October 2018
Document Number: 538136, Rev. 4.3



Access Method

tx_dword9: [Port: 0xA3] + (2480h + 24h)

0h - Read, 1h - Write

0		31		28		24		20		16		12		8		4		0	
0		0		0		0		0		0		0		1		0		0	
ontlstrongpulling		ontlen		ontllowrefsel_2_0		ontlhighrefsel_2_0		ofrcsatamode_1_0		otxsusclkfreq_1_0		reserved530		orcvdctrefselnosus_1_0		orcvdctputime_7_0		ontlputime_7_0	

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
15:8	Ch RW	orcvtctputime_7_0: Time (ick_susslow cycles) to wait (a.k.a. step 2) before comparing pads to Vref to determine if there is a receiver on the far end. Value should be by the following Table: Sus-clock rate P1269.8 P1271.x 25MHz - 27MHz 9 12 25MHz - 62.5MHz 35 43 37.5MHz - 100MHz 64 76 62.5MHz - 125MHz 83 98
7:0	6h RW	ontlputime_7_0: [after step 1 of pulldown] time (ick_susslow cycles) to wait (step 2) and let the pads leak upwards before comparing pads to Vref to determine if the pad exceeded Vref as a result of leakage.

17.20.11 TX_DWORD10 (tx_dword10)—Offset 28h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword10: [Port: 0xA3] + (2480h + 28h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31				28				24				20				16				12				8				4				0																			
0				0				0				0				0				0				0				0				0																			
isparead_7_0								reserved532								reserved531								ircvdtctmpout				idftcaptestsig				idftrcvdetectedtxn				idftrcvdetectedtxp				idftrcvdetectedfinished				intfinished				intpass_3_0			

Bit Range	Default & Access	Description
31:24	X RO	ispareread_7_0: spare reg read
23:16	0h RO	reserved532: reserved
15:10	0h RO	reserved531: reserved
9	0h RO	ircvdtctcmpout: Flash Comparator Output Value
8	X RO	idftcaptestsig: reserved
7	0h RO	idftrcvdetectedtxn: Receive Detect Result for Txn
6	0h RO	idftrcvdetectedtxp: Receive Detect Result for Txp
5	0h RO	idftrcvdetectedfinished: Receive Detect Process status
4	X RO	intlfinished: indication of NTL finished
3:0	X RO	intlpass_3_0: the four outputs of NTL test



Bit Range	Default & Access	Description
14	0h RW	ofrcmkeeppadpen: Forces enabling of common-mode keeping of PadP
13	0h RW	ofrcmkeeppadndis: Forces disabling of common-mode keeping of PadN
12	1h RW	ofrcmkeeppadpdis: Forces disabling of common-mode keeping of PadP
11	0h RW	omakedeeperfifo: Make FIFO deeper by 1 symbol clock cycle. Still not implemented. Implementation costs 10 flops in symb clock domain. Implementation is required for 8bits PISO only which is in next phase of products.
10:8	0h RW	ofrlatencyoptim_2_0: Changes the latency from loadgenen assertion to the sampling of 10bits data into fast-clock domain. The latency is determined by Fuses (through i_latencyoptim[1:0]) + ... 0XX =) + 0 (Not changing the latency.) 100 =) - 4UI 101 =) - 2UI 110 =) + 2UI 111 =) + 4UI Important Note: When changing the latency too high or too low is will wrap-around what might cause data loss on beginning or end of transmitting. If you decide to plan with the latency consider changing 'omakedeeperfifo' too
7	0h RO	reserved536: reserved
6	0h RW	ofrcrcvdtcten: force initiation of Tx-detect-Rx procedure
5:4	0h RW	otxrcvdtctclkrate_1_0: determines the clock rate in the flash comparator. 00 - use sus-clock as is (25MHz in phase2) default 01 - use sus-clock by 4 10 - use sus-clock by 2 11 - reserved In phase1 the rate was 2'b10 susfreq125MHz
3	0h RO	reserved535: reserved
2	0h RO	reserved534: reserved
1	0h RO	reserved533: reserved
0	0h RW	oneloopbacken: Near-End LoopBack enable

17.20.13 TX_DWORD12 (tx_dword12)—Offset 30h

Access Method


Type: Message Bus Register
(Size: 32 bits)

tx_dword12: [Port: 0xA3] + (2480h + 30h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
otxclkbyssel_1_0	ofrcdataratefit_2_0	odistxfelbpin	otxclkampbypsn	otxclkampbypsp	reserved539	odfxanamuxen	odfxanamuxsel_1_0	obs_tx_gated_supply_1_0
								reserved538
								oobsdigselectupn_3_0
								oobsdigselectupp_3_0
								oobsdigselectdownn_3_0
								oobsdigselectdownp_3_0

Bit Range	Default & Access	Description
31:30	0h RW	otxclkbyssel_1_0: Select if to bypass the divided normal clock with some other clock. 2'b00: Don't bypass. Regular clock. 2'b01: bypass the RX clock - dataratefit must be '11' 2'b10: Reserved 2'b11: bypass the sparetxclk clock - dataratefit must be '11'
29:27	0h RW	ofrcdataratefit_2_0: Forces TX data rate 3'b0XX - don't force a value. get it from the I/F pin 3'b100 - no divide (2UIs per clock cyc) 3'b101 - divide by 2 3'b110 - divide by 4 3'b111 - divide by 8 - used also for bypassing with other clocks
26	0h RW	odistxfelbpin: when asserted - disables the i_txfelben pin at the interface and force it 0. (needed in case the pin is asserted in KX or sata1 mode)
25	0h RW	otxclkampbypsn: 0': Normal operation '1': Enable of the passgate connected from the analog clock N to the control of the DC correction cell. The feedback OTA is disabled.
24	0h RW	otxclkampbypsp: 0': Normal operation '1': Enable of the passgate connected from the analog clock P to the control of the DC correction cell. The feedback OTA is disabled.
23	0h RO	reserved539: reserved
22	0h RW	odfxanamuxen: Enables analog signals probing mux out. When enabled the Vref of Tx-detect-Rx circuit is observed. Note that only one lane is allowed to have a the analog mux enabled to avoid collisions.
21:20	0h RW	odfxanamuxsel_1_0: selects analog signal to be sent to analog port in common lane. This bus has no affect at all currently because there is only one analog signal for observation which is observed by odfxanamuxen
19:18	0h RW	obs_tx_gated_supply_1_0: Monitor gated vcc supply to Tx upar
17:16	0h RO	reserved538: reserved
15:12	0h RW	oobsdigselectupn_3_0: selects data to be sent to observability port output 'o_obsup_nsg'. Same mapping as oobsdigselectdownn[3:0]
11:8	0h RW	oobsdigselectupp_3_0: selects data to be sent to observability port output 'o_obsup_psg'. Same mapping as oobsdigselectdownp[3:0]
7:4	0h RW	oobsdigselectdownn_3_0: Reserved.
3:0	0h RW	oobsdigselectdownp_3_0: Reserved.



17.20.14 TX_DWORD13 (tx_dword13)—Offset 34h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword13: [Port: 0xA3] + (2480h + 34h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved543	ir2short3_5_0	reserved542	ir2short0_5_0	reserved541	ir1main3_6_0	reserved540	ir1main0_6_0	

Bit Range	Default & Access	Description
31:30	0h RO	reserved543: reserved
29:24	X RO	ir2short3_5_0: The slices used in R2 for DE (sub-DE in 3tap FIR) (PstC=Y,C=Y,PreC=Y)
23:22	0h RO	reserved542: reserved
21:16	X RO	ir2short0_5_0: The slices used in R2 for FS (sub-FS in 3tap FIR) (PstC=Y,C=Y,PreC=X)
15	0h RO	reserved541: reserved
14:8	X RO	ir1main3_6_0: The slices used in R1 for DE (sub-DE in 3tap FIR) (PstC=Y,C=Y,PreC=Y)
7	0h RO	reserved540: reserved
6:0	X RO	ir1main0_6_0: The slices used in R1 for FS (sub-FS in 3tap FIR) (PstC=Y,C=Y,PreC=X)

17.20.15 TX_DWORD14 (tx_dword14)—Offset 38h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword14: [Port: 0xA3] + (2480h + 38h)

Op Codes:

0h - Read, 1h - Write

Default: 00400000h

[illegible]

Bit Range	Default & Access	Description
31:30	0h RW	ospare1_1_0: reserved
29	0h RW	osimmode: Counter threshold of receive-detect, NTL, strong-common-mode is shortened dramatically for fast simulation purposes. (does not impose risk to circuitry but electrical spec will not met)
28	0h RW	ontlmodepin2pin: 0 - NTL procedure will be done per pad while both pads are pulled to the same rail. 1 - NTL procedure will be done per pad while the pads are pulled to opposite rails.
27	0h RW	ofrcdatapathdis: DFT feature to optionally be used with other registers
26	0h RW	ofrcdatapathen: DFT feature to optionally be used with other registers
25	0h RW	ofrcdrvbydis: DFT feature to optionally be used with other registers
24	0h RW	ofrcdrvbypen: DFT feature to optionally be used with other registers
23	0h RW	odfttxclkcaptesten: Enables the finger capacitor quality check in the DCC block in Tx-clock block. The test is for shorts between the capacitor terminals.
22	1h RW	otxdccbyps_l: Tx DCC Bypass Override Puts DCC (duty cycle correction) circuit in bypass mode 0 - clock's duty cycle is not fixed
21:19	0h RW	ofrcnmos32idv_2_0: change the value iabut_idvpmos32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
18:16	0h RW	ofrcpmos32idv_2_0: change the value iabut_idvpmos32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
15	0h RW	visa_en: VISA Enable for the Tx VISA logic
14:12	0h RW	ovisa1_clksel_2_0: VISA Clock Select for Lane1. Selects the source synchronous clock to be used for data being sent on lane1.



Bit Range	Default & Access	Description
11:8	0h RW	ovisa1_lanesel_3_0: VISA Lane Select for Lane1. Selects the byte of data to be sent out on lane1.
7	0h RW	ovisa_bypass: VISA Bypass. Allows for signals to be passed asynchronously through VISA block. Applies to both lane0 and lane1. 0 : Flop signals in local VISA block (default) 1 : Bypass flops in local VISA block
6:4	0h RW	ovisa0_clkssel_2_0: VISA Clock Select for Lane0. Selects the source synchronous clock to be used for data being sent on lane0.
3:0	0h RW	ovisa0_lanesel_3_0: VISA Lane Select for Lane0. Selects data byte to be driven out of VISA-0 byte. Can be either clocked or unclocked data

17.20.16 TX_DWORD15 (tx_dword15)—Offset 3Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword15: [Port: 0xA3] + (2480h + 3Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved551	reserved550	reserved549	reserved548	reserved547	reserved546	reserved545	reserved544	

Bit Range	Default & Access	Description
31:30	0h RO	reserved551: reserved
29:24	0h RO	reserved550: The slices used in R2 for DE (PstC=X,C=Y,PreC=Y)
23:22	0h RO	reserved549: reserved
21:16	0h RO	reserved548: The slices used in R2 for FS (PstC=X,C=Y,PreC=X)
15	0h RO	reserved547: reserved
14:8	0h RO	reserved546: The slices used in R1 for DE (PstC=X,C=Y,PreC=Y)
7	0h RO	reserved545: reserved
6:0	0h RO	reserved544: The slices used in R1 for FS (PstC=X,C=Y,PreC=X)




Type: Message Bus Register
(Size: 32 bits)

Op Codes:

0h - Read, 1h - Write

31	28	24	20	16	12	8	4	0			
0	0	0	0	0	0	0	0	0			
reserved554				reserved553				ocurcomp0ei_2_0			
								reserved552			
								omediumcmpadn_1_0			
								omediumcmpadp_1_0			
								ospare3_3_0			
								ospare2_3_0			

Bit Range	Default & Access	Description
31:24	0h RO	reserved554: reserved
23:16	0h RO	reserved553: reserved
15:13	4h RW	ocurconp0ei_2_0: current consumed (typically) 00X - 0.0mA - not active 01X - 0.9mA 10X - 1.8mA 11X - 2.7mA
12	0h RO	reserved552: reserved
11:10	2h RW	omediumcmpadn_1_0: During P0-EI pad-N will be on medium strength CM and will cause the following current consumption: 00 - 0.00mA (disable) 01 - 2.45mA 10 - 4.87mA 11 - 9.73mA
9:8	2h RW	omediumcmpadp_1_0: During P0-EI pad-P will be on medium strength CM and will cause the following current consumption: 00 - 0.00mA (disable) 01 - 2.45mA 10 - 4.87mA 11 - 9.73mA
7:4	0h RW	ospare3_3_0: 4 spare CRI register bits
3:0	0h RW	ospare2_3_0: 4 spare CRI register bits




18 USB Host Controller Interfaces (xHCI, EHCI)

The USB Host Controllers (xHCI, EHCI) supports:

- One (1) Super Speed (SS) port on xHCI
- Four (4) Low Speed (LS)/Full Speed (FS)/High Speed (HS) ports on xHCI or EHCI
- Two (2) High Speed (HS) High Speed Inter-Chip (HSIC) ports on xHCI

Note: The SS port must share a LS/FS/HS port to have a full SS connector leaving three LS/FS/HS ports available.

Note: Only one host controller (either xHCI or EHCI) can be used. To enable HSIC and SS ports, xHCI must be used.



18.1 Signal Descriptions

See [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function



Table 209. USB 3 SS Signals

Signal Name	Direction Plat. Power	Description
USB3_TXP/N[0]	O V1P0A	Data Out: High speed serialized data outputs. Used for debug mode in xHCI operation.
USB3_RXP/N[0]	I V1P0A	Data In: High speed serialized data inputs. Used for debug mode in xHCI operation.
USB3_REXT[0]	I	Resistor Compensation: An external resistor must be connected between this pin and package ground. Contact your Intel representative for details.


Table 210. USB 2 FS/HS Signals

Signal Name	Direction Plat. Power	Description
USB_DP/N[0:3]	I/O VUSB2	USB Data: High speed serialized data I/O. Note: USB_DP/N[1] used for debug mode in EHCI operation only. SS port must be implemented to have debug mode during xHCI operation.
USB_OC[0:1]#	I V1P8A	Over-Current Protection: Over-current notification for all USB ports (SS/FS/HS/LS).
USB_RCOMPI	I	Resistor Compensation: An external resistor must be connected. Contact your Intel representative for details.
USB_RCOMPO	O	Resistor Compensation: An external resistor must be connected. Contact your Intel representative for details.

Table 211. USB 2 HSIC Signals

Signal Name	Direction Plat. Power	Description
USB_HSIC[0:1]_DATA	I/O V1P24A	HSIC Data: High speed serialized data.
USB_HSIC[0:1]_STROBE	I/O V1P24A	HSIC Strobe: Strobe reference for data.
USB_HSIC_RCOMP	I	Resistor Compensation: An external resistor must be connected. Contact your Intel representative for details.

Figure 103.xHCI and EHCI Port Mapping



Note: xHCI (3.0) SS is the debug port for xHCI controller.

Note: EHCI (1/2.0) Port 1 is the debug port of the EHCI controller

18.2 USB 3.0 xHCI (Extensible Host Controller Interface)

The xHCI compliant host controller can control up to 7 USB host ports. It supports devices conforming to USB 1.x to 3.0 at bit rates up to 5 Gbps.

18.2.1 Features of USB 3.0 Host

The USB 3.0 Super Speed data interface is a four wire differential (TX and RX pairs) interface that supports simultaneous bi-directional data transmission. The interface supports a bit rate of 5 Gbps with a maximum theoretical data throughput over 3.2 Gbps due to 8b/10b symbol encoding scheme and protocol overhead (link flow control, packet framing and protocol overhead).

Low Frequency Periodic signaling (LFPS) is used to communicate initialization, training and power management information across a link that is in low power link state without using Super Speed signaling. This reduces power consumption.

The USB3.0 port may be paired with any USB2 port at the connector – selection of any USB2 port other than port 0 will require the appropriate mapping. [Figure 103](#) shows the USB3 port paired with USB2 port 0.

USB3.0 Controller Features

- Supported by xHCI software host controller interface
- USB3 port disable
- Supports local dynamic clock gating and trunk clock gating
- Supports USB 3.0 LPM (U0, U1, U2, and U3) and also a SS Disabled low power state



- Support for USB3 Debug Device

Note: Recommended not to disconnect the connection when a debug session is in progress.

18.2.2 Features of USB HSIC

HSIC is a 2-signal (strobe and data) source synchronous serial interface for on board inter-chip USB communication. The interface uses 240 MHz DDR signaling to provide High-Speed 480 Mb/s USB transfers which are 100% host driver compatible with traditional USB cable connected topologies. Full Speed (FS) and Low Speed (LS) USB transfers are not directly supported by the HSIC interface.

For details of HSIC applications supported, Contact local Intel Sales office.

Major feature and performance highlights are as follows:

- Supported by xHCI software host controller interface
- High-Speed 480 Mb/s data rate only
- Source-synchronous serial interface
- Interface Power is only consumed when a transfer is in progress
- No hot plug removal/attach at HSIC pins
- Signals driven at 1.2V standard LVCMOS levels
- Designed for low power applications
- Support for two host ports compliant to High Speed Inter-Chip Supplement (HSIC) to the USB 2.0 Specification. (USB 2.0)

18.3 USB 2.0 Enhanced Host Controller Interface (EHCI)


The EHCI compliant host controller supports up to 4 USB 2.0 ports in legacy mode. USB 2.0 allows data transfers up to 480 Mbps. The controller integrates a Root Matching Hub (RMH) to support USB 1.1 devices.

Note: The EHCI is not used when the xHCI is used. The EHCI is primarily present for legacy usage, in cases when xHCI support is not available.

Note: Intel recommends using the xHCI controller for the USB2.0 ports irrespective of whether USB3.0 ports are implemented. The EHCI controller is provided for legacy OS/driver compatibility which is generally not required for tablet platforms. Using the xHCI controller will deliver significant power and performance benefits.

When following this recommendation on a platform with no USB3.0 support, the Windows logo requirement of USB debug port may not be met. Please consult with Intel regarding the impact of this.

Note: Unlike the xHCI, bandwidth of all four ports on the EHCI is shared across a single HS (480 Mbps) internal link.



18.3.1 Features of EHCI USB 2.0 Controller

The EHCI USB2.0 Controller supports the following features:

- Compliant with the specification for: USB 1.x, 2.0 (1.5 Mbps, 12 Mbps, 480 Mbps).
- 4 Ports shared with xHCI controller
- Enhanced EHCI descriptor caching
- All ports provided through USB Rate Matching Hubs (RMH) to support FS/LS devices
- Supports one Debug port at USB2 transfer rates
- Supports of USB suspend mode including PLL turn off in S0.
- Supports wakeup from suspend states S5 and remote-suspend wakeup
- All USB2 ports provide support for HS/FS/LS devices
- Per port USB disable
- Supports local dynamic clock gating and trunk clock gating
- Supports USB 2.0 LPM (L0, L1 and L2 low power states)

18.4 References

USB 3.0 Specification

USB 2.0 Specification (Includes High-Speed Inter-Chip USB Electrical Specification)

18.4.1 Host Controller Specifications

Extensible Host Controller Interface (xHCI) Specification for USB 3.0 version 1.0

Enhanced Host Controller Interface (EHCI) Specification for USB 2.0



18.5 Register Map

Refer to [Chapter 3, “Register Access Methods”](#) and [Chapter 4, “Mapping Address Spaces”](#) for additional information.





Figure 104.USB Host Controller Register Map



- [Section 18.10, “USB EHCI Electrical Message Bus Registers” on page 2436](#)



18.6 USB xHCI PCI Configuration Registers

Table 212. Summary of USB xHCI PCI Configuration Registers—0/20/0

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–1h	2	"Vendor ID (VID)—Offset 0h" on page 2127	8086h
2–3h	2	"Device ID (DID)—Offset 2h" on page 2128	8C31h
4–5h	2	"Command (CMD)—Offset 4h" on page 2128	0000h
6–7h	2	"Device Status (STS)—Offset 6h" on page 2129	0290h
8–8h	1	"Revision ID (RID)—Offset 8h" on page 2131	00h
9–9h	1	"Programming Interface (PI)—Offset 9h" on page 2131	30h
A–Ah	1	"Sub Class Code (SCC)—Offset Ah" on page 2131	03h
B–Bh	1	"Base Class Code (BCC)—Offset Bh" on page 2132	0Ch
D–Dh	1	"Master Latency Timer (MLT)—Offset Dh" on page 2132	00h
E–Eh	1	"Header Type (HT)—Offset Eh" on page 2132	00h
10–17h	8	"Memory Base Address (MBAR)—Offset 10h" on page 2133	000000000000004h
2C–2Dh	2	"USB Subsystem Vendor ID (SSVID)—Offset 2Ch" on page 2134	0000h
2E–2Fh	2	"USB Subsystem ID (SSID)—Offset 2Eh" on page 2134	0000h
34–34h	1	"Capabilities Pointer (CAP_PTR)—Offset 34h" on page 2135	70h
3C–3Ch	1	"Interrupt Line (ILINE)—Offset 3Ch" on page 2135	00h
3D–3Dh	1	"Interrupt Pin (IPIN)—Offset 3Dh" on page 2135	00h
40–43h	4	"XHC System Bus Configuration 1 (XHCC1)—Offset 40h" on page 2136	000000FDh
44–47h	4	"XHC System Bus Configuration 2 (XHCC2)—Offset 44h" on page 2137	0003C000h
50–53h	4	"Clock Gating (XHCLKGTEN)—Offset 50h" on page 2139	00000120h
58–5Bh	4	"Audio Time Synchronization (AUDSYNC)—Offset 58h" on page 2142	00000000h
60–60h	1	"Serial Bus Release Number (SBRN)—Offset 60h" on page 2143	30h
61–61h	1	"Frame Length Adjustment (FLADJ)—Offset 61h" on page 2143	20h
62–62h	1	"Best Effort Service Latency (BESL)—Offset 62h" on page 2144	00h
70–70h	1	"PCI Power Management Capability ID (PM_CID)—Offset 70h" on page 2144	01h
71–71h	1	"Next Item Pointer #1 (PM_NEXT)—Offset 71h" on page 2145	80h
72–73h	2	"Power Management Capabilities (PM_CAP)—Offset 72h" on page 2145	C1C2h
74–75h	2	"Power Management Control/Status (PM_CS)—Offset 74h" on page 2146	0008h
80–80h	1	"Message Signaled Interrupt CID (MSI_CID)—Offset 80h" on page 2147	05h
81–81h	1	"Next item pointer (MSI_NEXT)—Offset 81h" on page 2148	00h
82–83h	2	"Message Signaled Interrupt Message Control (MSI_MCTL)—Offset 82h" on page 2148	0086h
84–87h	4	"Message Signaled Interrupt Message Address (MSI_MAD)—Offset 84h" on page 2149	00000000h
88–8Bh	4	"Message Signaled Interrupt Upper Address (MSI_MUAD)—Offset 88h" on page 2149	00000000h



18.6.2 Device ID (DID)—Offset 2h

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

Offset: [B:0, D:20, F:0] + 2h

Default: 8C31h

15	12	8	4	0
1	0	0	0	1
1	0	0	0	1
DID				

Bit Range	Default & Access	Field Name (ID): Description
15:0	8C31h RO/V	Device ID (DID): See Global Device ID table in Chap. 6 for value Power Well: Core

18.6.3 Command (CMD)—Offset 4h

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

Offset: [B:0, D:20, F:0] + 4h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
RSVD		ID	FBE	SERR
		WCC	PER	VPS
		MWI	SCE	BME
		MSE	IOSE	

Bit Range	Default & Access	Field Name (ID): Description
15:11	00h RO	Reserved (RSVD): Reserved. Power Well: Core
10	0b RW	Interrupt Disable (ID): When cleared to 0, the function is capable of generating interrupts. When 1, the function can not generate its interrupt to the interrupt controller. Note that the corresponding Interrupt Status bit is not affected by the interrupt enable. Power Well: Core
9	0b RO	Fast Back to Back Enable (FBE): Reserved. Power Well: Core
8	0b RW	SERR# Enable (SERR): When set to 1, the XHC is capable of generating (internally) SERR#. See section on error handling. Power Well: Core
7	0b RO	Wait Cycle Control (WCC): Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
6	0b RW	Parity Error Response (PER): When set to 1, the XHCI Host Controller will check for correct parity (on its internal interface) and halt operation when bad parity is detected during the data phase as recommended by the XHCI specification. Note that this applies to both requests and completions from the system interface. This bit must be set in order for the parity errors to generate SERR#. Power Well: Core
5	0b RO	VGA Palette Snoop (VPS): Reserved. Power Well: Core
4	0b RO	Memory Write Invalidate (MWI): Reserved. Power Well: Core
3	0b RO	Special Cycle Enable (SCE): Reserved. Power Well: Core
2	0b RW	Bus Master Enable (BME): When set, it allows XHC to act as a bus master. When cleared, it disable XHC from initiating transactions on the system bus. Power Well: Core
1	0b RW	Memory Space Enable (MSE): This bit controls access to the XHC Memory Space registers. If this bit is set, accesses to the XHC registers are enabled. The Base Address register for the XHC should be programmed before this bit is set. Power Well: Core
0	0b RO	I/O Space Enable (IOSE): Reserved as 0. Read-Only. Power Well: Core

18.6.4 Device Status (STS)—Offset 6h

Access Method


Type: PCI Configuration Register
(Size: 16 bits)

Offset: [B:0, D:20, F:0] + 6h

Default: 0290h

15	12	8	4	0
0	0	0	0	0
DPE	SSE	RMA	RTA	STA
				DEVT
				MDPED
				FBBC
				UDF
				MC
				CL
				IS
				RSVD

Bit Range	Default & Access	Field Name (ID): Description
15	0b RW/1C	Detected Parity Error (DPE): This bit is set by the Intel PCH whenever a parity error is seen on the internal interface to the XHC host controller, regardless of the setting of bit 6 or bit 8 in the Command register or any other conditions. Software clears this bit by writing a 1 to this bit location. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
14	0b RW/1C	Signaled System Error (SSE): This bit is set by the Intel PCH whenever it signals SERR# (internally). The SERR_EN bit (bit 8 in the Command Register) must be 1 for this bit to be set. See error handling section for complete list of conditions handled. Software clears this bit by writing a 1 to this bit location. Power Well: Core
13	0b RW/1C	Received Master-Abort Status (RMA): This bit is set when XHC, as a master, receives a master-abort status on a memory access. This is treated as a Host Error and halts the DMA engines. Software clears this bit by writing a 1 to this bit location. Power Well: Core
12	0b RW/1C	Received Target Abort Status (RTA): This bit is set when XHC, as a master, receives a target abort status on a memory access. This is treated as a Host Error and halts the DMA engines. Software clears this bit by writing a 1 to this bit location. Power Well: Core
11	0b RW/1C	Signaled Target-Abort Status (STA): This bit is used to indicate when the XHC function responds to a cycle with a target abort. Power Well: Core
10:9	01b RO	DEVSEL# Timing Status (DEVT): This 2-bit field defines the timing for DEVSEL# assertion. Read-Only. Power Well: Core
8	0b RW/1C	Master Data Parity Error Detected (MDPED): This bit is set by the Intel PCH whenever a data parity error is detected on a XHC read completion packet on the internal interface to the XHC host controller and bit 6 of the Command register is set to 1. Software clears this bit by writing a 1 to this bit location. Power Well: Core
7	1b RO	Fast Back-to-Back Capable (FBBC): Reserved as 1 Read-Only. Power Well: Core
6	0b RO	User Definable Features (UDF): Reserved as 0. Read-Only. Power Well: Core
5	0b RO	66 MHz Capable (MC): Reserved as 0. Read-Only. Power Well: Core
4	1b RO	Capabilities List (CL): Hardwired to 1 indicating that offset 34h contains a valid capabilities pointer. Power Well: Core
3	0b RO/V	Interrupt Status (IS): This read-only bit reflects the state of this function's interrupt at the input of the enable/disable logic. This bit is a 1 when the interrupt is asserted. This bit will be 0 when the interrupt is deasserted. The value reported in this bit is independent of the value in the Interrupt Enable bit. Power Well: Core
2:0	000b RO	Reserved (RSVD): Reserved. Power Well: Core



18.6.5 Revision ID (RID)—Offset 8h

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 8h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
RID									

Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RO/V	Revision ID (RID): See Chap 6 for value. Power Well: Core

18.6.6 Programming Interface (PI)—Offset 9h

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 9h

Default: 30h

7				4					0
0	0	1	1	1	0	0	0	0	0
PI									

Bit Range	Default & Access	Field Name (ID): Description
7:0	30h RO	Programming Interface (PI): A value of 30h indicates that this USB Host Controller conforms to the XHCI specification. Power Well: Core

18.6.7 Sub Class Code (SCC)—Offset Ah

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + Ah

Default: 03h

7				4					0
0	0	0	0	0	0	0	1	1	1
SCC									



7	4	0
0	0	0
MFB	CL	

Bit Range	Default & Access	Field Name (ID): Description
7	0b RO	Multi-Function Bit (MFB): Read only indicating single function device. Power Well: Core
6:0	00h RO	Configuration layout (CL): Hardwired to 0 to indicate a standard PCI configuration layout. Power Well: Core

18.6.11 Memory Base Address (MBAR)—Offset 10h

Value in this register will be different after the enumeration process.

Access Method

Type: PCI Configuration Register
(Size: 64 bits)

Offset: [B:0, D:20, F:0] + 10h

Default: 0000000000000004h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
BA												RSVD			Prefetchable	Type
																RTE

Bit Range	Default & Access	Field Name (ID): Description
63:16	00000000 000h RW	Base Address (BA): Bits (63:16) correspond to memory address signals (63:16), respectively. This gives 64 KB of relocatable memory space aligned to 64 KB boundaries. Power Well: Core
15:4	000h RO	Reserved (RSVD): Reserved. Read-Only 0, this indicates that this function is requesting an 64KB block of memory. Power Well: Core
3	0b RO	Prefetchable: This bit is hardwired to 0 indicating that this range should not be prefetched. Power Well: Core
2:1	10b RO	Type: If this field is hardwired to 00 it indicates that this range can be mapped anywhere within 32-bit address space. If this field is hardwired to 10 it indicates that this range can be mapped anywhere within 64-bit address space. Power Well: Core



18.6.14 Capabilities Pointer (CAP_PTR)—Offset 34h

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 34h

Default: 70h

7			4				0
0	1	1	1	0	0	0	0
				CAP_PTR			

Bit Range	Default & Access	Field Name (ID): Description
7:0	70h RO	Capabilities Pointer (CAP_PTR): This register points to the starting offset of the capabilities ranges. Power Well: Core

18.6.15 Interrupt Line (ILINE)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 3Ch

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
				ILINE			

Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RW	Interrupt Line (ILINE): This data is not used by the Intel PCH. It is used as a scratchpad register to communicate to software the interrupt line that the interrupt pin is connected to. Power Well: Core

18.6.16 Interrupt Pin (IPIN)—Offset 3Dh

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 3Dh

Default: 00h


7			4				0
0	0	0	0	0	0	0	0
				IPIN			



Type: PCI Configuration Register
(Size: 32 bits)

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	0	1
ACCTRL	EC01							RMTASERR	URD	URRE	IIL1E	XHCIL1E	D3IL1E	PCPWT	SWAXHCI	L23HRAWC			UTAGCP	UDAGCNP	UDAGCCP	UDAGC													

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	XHC Initiated L1 Enable (XHCIL1E): If set, allow the XHC initiated L1 power management to be enabled. Power Well: Core
17	0b RW	D3 Initiated L1 Enable (D3IL1E): If set, allow PCI device state D3 initiated L1 power management to be enabled. This bit can only be set if the XHCI L1 Override P2 chicken bit is set. Power Well: Core
16:12	00h RW	Periodic Complete Pre Wake Time (PCPWT): signal . This allows for platform wake time before the next scheduled periodic transaction. The value programmed in this field represents the # of bytes consumed in the current micro-frame which is required to allow for the periodic complete to de-assert. This allows for a programmable time to cause the periodic complete to de-assert prior to the start of the next micro-frame. Register Format: Bits (16:12) represents the # of bytes remaining with a 256B granularity. Periodic Complete will de-assert if the bytes consumed in the current micro-frame is less Power Well: Core
11	0h RW	SW Assisted xHC Idle (SWAXHCI): This bit being set will indicate xHC idleness (through SW means), which must be a '1' to allow L1 entry, and subsequently allow backbone clock to be gated. This bit is to be set by Intel xHCI driver after checking that the xHCI Controller will stay in idle state for a significant period of time, e.g. all ports disconnected. This bit can be cleared under the following conditions (see SWAXHCI Policy bits in xHC System Bus Configuration 2 register): n SW: SW could write 0 to clear this bit. n HW: HW, under policy control, will clear this bit on an MMIO access to the Host Controller. n HW: HW, under policy control, will clear this bit when HW exits Idle state. Power Well: Core
10:8	000b RW	L23 to Host Reset Acknowledge Wait Count (L23HRAWC): If programmed to non zero, it allows a wait period after the L23 PHY has shutdown before returning host reset acknowledge to PMC. 000: Disabled 001: 128 bb_cclk 010: 256 bb_cclk 011: 512 bb_cclk 100: 1024 bb_cclk 101: 2048 bb_cclk 110: 4096 bb_cclk 111: 131072 bb_cclk Power Well: Core
7:6	11b RW	Upstream Type Arbiter Grant Count Posted (UTAGCP): Grant count for IOSF upstream L2 request type arbiter for posted type Power Well: Core
5:4	11b RW	Upstream Type Arbiter Grant Count Non Posted (UDAGCNP): Grant count for IOSF upstream L2 type arbiter for non-posted type Power Well: Core
3:2	11b RW	Upstream Type Arbiter Grant Count Completion (UDAGCCP) (UDAGCCP): Grant count for IOSF upstream L2 type arbiter for completion type Power Well: Core
1:0	01b RW	Upstream Device Arbiter Grant Count (UDAGC) (UDAGC): Grant count for IOSF upstream L1 device arbiter Power Well: Core

18.6.18 XHC System Bus Configuration 2 (XHCC2)—Offset 44h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + 44h

Default: 0003C000h

31		28				24				20				16				12				8				4				0															
0		0		0		0		0		0		0		0		1		1		1		1		0		0		0		0		0		0		0									
OCCFGDONE		ECO1				DREQBCC				IDMA_RDREQSZCTRL				XHCUPRDROE IOSFSRAD				UNPPA				SWAXHCIP				RAWDD WAWDE				SWACXIHCB				SWADMILLIHB				L1FP2CGWC				RDREQSZCTRL			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/O	OC Configuration Done (OCCFGDONE): This bit is used by BIOS to prevent spurious switching during OC configuration. Any write this register bit will cause it to set. It must be set by BIOS after configuration of the OC mapping bits is complete. Once this bit is set, OC mapping shall not be changed by SW. Power Well: SUS
30:26	00h RW	ECO1: NOT for EDS ECO bits are used during silicon bringup for FIBing. Power Well: Core
25	0b RW	DMA Request Boundary Crossing Control (DREQBCC): This bit controls the boundary crossing limit of each Read/Write Request. 0: 4KB 1: 64B Power Well: Core
24:22	0h RW	IDMA Read Request Size Control (IDMA_RDREQSZCTRL): Read Request Size Control: This bit controls the maximum size of each Read Request. 000: 128B 001: 256B 011 - 110: Reserved 111: 64B Power Well: Core
21	0b RW	XHC Upstream Read Relaxed Ordering Enable (XHCUPRDROE): This policy controls the Relaxed Ordering attribute for upstream reads. 0 - xHC will clear RO for all upstream read requests. 1 - xHC will set RO for all upstream read requests. Power Well: Core
20	0b RW	IOSF Sideband Register Access Disable (IOSFSRAD): When set, it disables the IOSF sideband interface from accepting any host space register access. Power Well: Core
19:14	0Fh RW	Upstream Non-Posted Pre-Allocation (UNPPA): This field reserves data sizes, in 64 byte chunks, of the downstream completion resource. This value is zero based. 000000 - 111111: Pre-allocate 64 bytes - 4096 bytes If set greater than the default allows over-allocation If set less than default allows under-allocation Only allowed to be programmed when BME = 0 and no outstanding downstream completion Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
13:12	00b RW	SW Assisted xHC Idle Policy (SWAXHCIP): Note: Irrespective of the setting of this field, SW write of 0 to SWAXHCI will clear the bit. 00b (default): xHC HW clears SWAXHCI bit upon: n MMIO access to Host Controller OR n xHC HW exits Idle state 01b: xHC HW does not autonomously clear SWAXHCI bit. The bit could be cleared only by SW. 10b: xHC HW clears SWAXHCI upon MMIO access to Host Controller. xHC HW exit from Idle state will not clear SWAXHCI. 11b: Reserved Power Well: Core
11	0h RW	MMIO Read After MMIO Write Delay Disable (RAWDD): This field controls delay on MMIO Read after MMIO Write. 0b (Default): Delay MMIO Read after MMIO Write 1b: Do not delay MMIO Read after MMIO Write Note that this delay applies after the second of the two DW writes in the case where the IOSF Gasket splits a QW write into two single DW writes to the IP. Power Well: Core
10	0h RW	MMIO Write After MMIO Write Delay Enable (WAWDE): This field controls delay on MMIO Write after previous MMIO Write. 0b (Default): Do not delay MMIO Write after previous MMIO Write 1b: Delay MMIO Write after previous MMIO Write Note that the delay count does not apply on the second of the two DW writes that are generated by IOSF Gasket when it splits a QW write into two. In other words, the second of the two DW writes could happen without any delay with respect to the first DW write. This choice is being made for ease of ECO. The delay count, in this case, will apply after the second of the two DW writes. Power Well: Core
9:8	0h RW	SW Assisted Cx Inhibit (SWACXIH): This field controls how the DMI L1 inhibit signal from USB3 to PMC will behave. 00: Never inhibit Cx 01: Inhibit Cx when Isochronous Endpoint is active (PPT Behavior) 10: Inhibit Cx when Periodic Active as defined in 40.4.3.2.1 11: Always inhibit Cx Power Well: Core
7:6	0h RW	SW Assisted DMI L1 Inhibit (SWADMIL1IH): This field controls how the DMI L1 inhibit signal from USB3 to DMI will behave. 00: Never inhibit DMI L1. 01: Inhibit DMI L1 when Isochronous Endpoint is active (PPT Behavior). 10: Inhibit DMI L1 when Periodic Active as defined in 40.4.3.2.1. 11: Inhibit DMI L1 if XHCC1.SWAXHCI = 0. Power Well: Core
5:3	0h RW	L1 Force P2 Clock Gating Wait Count (L1FP2CGWC): If programmed to non zero, it allows L1 force P2 gating off the clock to be delayed after the time-out period specified. If wake up event is detected before the time-out, pclk remains alive and trigger L1 exit as though CPU host is causing the wake, 000: Disabled 001: 128 bb_cclk 010: 256 bb_cclk 011: 512 bb_cclk 100: 1024 bb_cclk 101: 2048 bb_cclk 110: 4096 bb_cclk 111: 131072 bb_cclk Power Well: Core
2:0	000b RW	Read Request Size Control (RDREQSZCTRL): Read Request Size Control: This bit controls the maximum size of each Read Request. 000: 128B 001: 256B 010: 512B 011 - 110: Reserved 111: 64B Power Well: Core


18.6.19 Clock Gating (XHCLKGTEN)—Offset 50h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + 50h

Default: 00000120h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
Rsvd2	NUEFBCGPS	SRAMPGTEN	SSLSE	USB2PLLSE	IOSFSTCGE	HSTCGE	SSTCGE	XHCIGEU3S
								XHCFTCLKSE
								XHCBBTCGIP1SO
								XHCHSTCGU2NRWE
								XHCUSB2PLSDLE
								HSUXDMIPLLE
								SSPLLSUE
								XHCBLCGE
								HSLTCGE
								SSLTCGE
								IOSFBTCGE
								IOSFBLCGE

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RO	Rsvd2: Reserved Power Well: Core
28	0b RW	Nak&#8217;ing USB2.0 EPs for Backbone Clock Gating and PLL Shutdown (NUEFBCGPS): This field controls whether Naking USB2.0 EPs, once in Naking low priority schedule, should be considered as active for the considerations for backbone clock gating and PLL shutdown or not. 0: Naking USB2.0 EPs are not considered to be active for Backbone Clock Gating and PLL Shutdown evaluation. 1: Naking USB2.0 EPs are considered to be active for Backbone clock gating and PLL shutdown evaluation. Power Well: Core
27	0b RW	SRAM Power Gate Enable (SRAMPGTEN): This register enables the SRAM Power Gating when PLL shutdown conditions for all clock domains have been met 0 - Disallow SRAM Power Gating. 1 - Allow SRAM Power Gating Power Well: Core
26	0h RW	SS Link PLL Shutdown Enable (SSLSE): This register enables the SS P3 state to be exposed to PXP PLL Shutdown conditions on behalf of all USB SS Ports ontop of trunk clock gating. 0 - P3 state NOT allowed to result in PXP PLL shutdown. 1- P3 state allowed to result in PXP PLL shutdown Power Well: Core
25	0h RW	USB2 PLL Shutdown Enable (USB2PLLSE): When set, this bit allows USB2 PLL to be shutdown when HS Link trunk clock is gated, and xHC can tolerate PLL spin up time for subsequent clock request. Note: if USB2 PLL Shutdown Disable Fuse is '1', hardware will always see '0' as an output from this register. BIOS reading this register should always return the correct value. Power Well: Core
24	0h RW	IOSF Sideband Trunk Clock Gating Enable (IOSFSTCGE): When set, this bit allows the IOSF sideband clock trunk to be gated when idle conditions are met. Power Well: Core
23:20	0h RW	HS Backbone PXP Trunk Clock Gate Enable (HSTCGE): This register determines the HS Ux state(s) which will be exposed to Backbone PXP trunk gating of core clock. Uy is a state allowed to result in trunk gating when ss_tcg_ux_en(x) is asserted. (0) ==) U0 or deeper (1) ==) NA (no support for U1) (2) ==) U2 (L1) or deeper (3) ==) U3 (L2) or deeper Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
19:16	0h RW	SS Backbone PXP Trunk Clock Gate Enable (SSTCGE): This register determines the SS Ux state(s) which will be exposed to Backbone PXP trunk gating of core clock. Uy is a state allowed to result in trunk gating when ss_tcg_ux_en(x) is asserted. (0) ==) U0 or deeper (1) ==) U1 or deeper (2) ==) U2 or deeper (3) ==) U3 or deeper Power Well: Core
15	0h RW	XHC Ignore_EU3S (XHCIGEU3S): This register determines if the xHC will use the EU3S as a condition to allow for Frame timer gating. 0 - xHC may allow frame timer to be gated when EU3S is set and all ports are in the required state. 1 - xHC may allow frame timer to be gated regardless of EU3S. Power Well: Core
14	0h RW	XHC Frame Timer Clock Shutdown Enable (XHCFTCLKSE): This register determines if the xHC will allow the frame timer clock to be gated. 0 - xHC will not allow ICC PLL 96MHz output to be shutdown thus keeping the frame timer running. 1 - xHC will allow ICC PLL 96MHz output to be shutdown under specific conditions. Power Well: Core
13	0h RW	XHC Backbone PXP Trunk Clock Gate In Presence of ISOCH EP (XHCBBTCGIPISO): This register controls the policy on allowing Backbone PXP trunk clock gate in the presence of IDLE ISOCH EP s with active DB. Allows the periodic active to be used in enabling Backbone PXP trunk clock gating of core clock. 0 Trunk gate of core clock is not allowed when ISOCH EP DB is set and ISOCH EP s are idle. 1 Allow trunk gate of core clock when ISOCH EP DB is set and ISOCH EP s are idle. Power Well: Core
12	0h RW	XHC HS Backbone PXP Trunk Clock Gate U2 non RWE (XHCSTCGU2NRWE): This register controls the policy on allowing Backbone PXP trunk gating of core clock when there is atleast 1 non Remote Wake Enabled HS Port in U2. 0 Prevent trunk gate of core clock when a non RWE HS Port is in U2. 1 Allow trunk gate of core clock when a non RWE HS Port is in U2. Power Well: Core
11:10	0h RW	XHC USB2 PLL Shutdown Lx Enable (XHCUSB2PLLSLE): This register determines the HS Link state(s) which will be exposed to USB2 PLL Shutdown conditions on behalf of all USB2 HS Ports. Ly is a state allowed to result in USB2 PLL Shutdown when en(x) is asserted. (0) ==) L1 or deeper (1) ==) L2 or deeper Power Well: Core
9:8	01b RW	HS Backbone PXP PLL Shutdown Ux Enable (HSUXDMIPLSE): This register determines the Ux state(s) which will be exposed to PXP PLL Shutdown conditions. PLL Shutdown is allowed in: 00b Disabled (Link states shall be disabled for DMI PLL shutdown) 01b U0 or conditions for 10b setting. 10b U2 or conditions for 11b setting. 10b U3, Disconnected, Disabled or Powered-Off. Power Well: Core
7:5	001b RW	SS Backbone PXP PLL Shutdown Ux Enable (SSPLLSUE): This register determines the Ux state(s) which will be exposed to DMI PLL Shutdown conditions. PLL Shutdown is allowed in: 000b Disabled (Link states shall be ignored for DMI PLL shutdown). 001b U0 or conditions for 010b setting 010b U1 or conditions for 011b setting 011b U2 or conditions for 100b setting 100b U3, Disconnected, Disabled or Powered-Off Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	XHC Backbone Local Clock Gating Enable (XHCBLCGE): When set, this bit allows XHCI Controller IP backbone clock to be locally gated when idle conditions are met. Note: if XHC Dynamic Clock Gating Disable Fuse is '1', hardware will always see '0' as an output from this register. BIOS reading this register should always return the correct value. Power Well: Core
3	0b RW	HS Link Trunk Clock Gating Enable (HSLTCGE): When set, this bit allows High Speed Link control's 480 MHz and its 48/60 MHz link clock trunk to be gated when idle conditions are met. Note: if XHC Dynamic Clock Gating Disable Fuse is '1', hardware will always see '0' as an output from this register. BIOS reading this register should always return the correct value. BIOS need to query fuses to see if HW is enabled. Power Well: Core
2	0b RW	SS Link Trunk Clock Gating Enable (SSLTCGE): When set, this bit allows the SuperSpeed Link control's 250 MHz and its divided 125 MHz link clock trunk to be gated when idle conditions are met. Note: if XHC Dynamic Clock Gating Disable Fuse is '1', hardware will always see '0' as an output from this register. BIOS reading this register should always return the correct value. BIOS need to query fuses to see if HW is enabled. Power Well: Core
1	0b RW	IOSF Backbone Trunk Clock Gating Enable (IOSFBTCGE): When set, this bit allows the IOSF backbone clock trunk to be gated when idle conditions are met. Power Well: Core
0	0b RW	IOSF Gasket Backbone Local Clock Gating Enable (IOSFBLCGE): When set, this bit allows the IOSF Gasket backbone clock to be locally gated when idle conditions are met. Note: if XHC Dynamic Clock Gating Disable Fuse is '1', hardware will always see '0' as an output from this register. BIOS reading this register should always return the correct value. BIOS need to query fuses to see if HW is enabled. Power Well: Core

18.6.20 Audio Time Synchronization (AUDSYNC)—Offset 58h

This 32 bit register is used for audio stream synchronization across different devices. Global signal sample_now captures a value in AUDSYNC register.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + 58h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd2	CMFI				Rsvd1	CMFB		

Bit Range	Default & Access	Field Name (ID): Description
31:30	0h RO	Rsvd2: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
29:16	0000h RO/V	Captured Frame List Current Index/Frame Number (CMFI): The value in this register is updated in response to sample_now signal. Bits (29:16) reflect state of bits (13:0) of FRINDEX Power Well: Core
15:13	0h RO	Rsvd1: Reserved. Power Well: Core
12:0	0000h RO/V	Captured Micro-frame BLIF (CMFB): The value is updated in response to sample_now signal and provides information about offset within micro-frame. Captured value represents number of 8 high-speed bit time units from start of micro-frame. At the beginning of micro-frame captured value will be 0 and increase to maximum value at the end. Default maximum value is 7499 but it may be changed as result of adjustment done in FLA. Power Well: Core

18.6.21 Serial Bus Release Number (SBRN)—Offset 60h

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 60h

Default: 30h

7			4				0
0	0	1	1	0	0	0	0
				SBRN			

Bit Range	Default & Access	Field Name (ID): Description
7:0	30h RO	Serial Bus Release Number (SBRN): A value of 30h indicates that this controller follows USB release 3.0. Power Well: SUS

18.6.22 Frame Length Adjustment (FLADJ)—Offset 61h

This feature is used to adjust any offset from the clock source that generates the clock that drives the SOF counter. When a new value is written into these six bits, the length of the frame is adjusted. Its initial programmed value is system dependent based on the accuracy of hardware USB clock and is initialized by system BIOS. This register should only be modified when the HChalted bit in the USBSTS register is a one. Changing value of this register while the host controller is operating yields undefined results.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 61h

Default: 20h



7	4	0
0	0	0
RSVD	FLTV	

Bit Range	Default & Access	Field Name (ID): Description
7:6	00b RO	Reserved (RSVD): . Power Well: SUS
5:0	20h RW	Frame Length Timing Value (FLTV): SOF micro-frame length) is equal to 59488 + value in this field. The default value is decimal 32 (20h), which gives a SOF cycle time of 60000. Frame Length (number of High Speed bit times) FLADJ Value (decimal) 59488 0 (00h) 59504 1 (01h) 59520 2 (02h) ... 59984 31 (1Fh) 60000 32 (20h) ... 60480 62 (3Eh) 60496 63 (3Fh) Each decimal value change to this register corresponds to 16 high-speed bit times. The SOF cycle time (number of SOF counter clock periods to generate a SOF micro-frame length) is equal to 59488 + value in this field. The default value is decimal 32 (20h), which gives a SOF cycle time of 60000. Frame Length (# High Speed bit times) FLADJ Value Power Well: SUS

18.6.23 Best Effort Service Latency (BESL)—Offset 62h

Bset Effort Service Latency.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 62h

Default: 00h

7	4	0
0	0	0
DBESLD	DBESL	

Bit Range	Default & Access	Field Name (ID): Description
7:4	0h RW/L	Default Best Effort Service Latency Deep (DBESLD): Default Best Effort Service Latency (DBESLD) If the value of this field is non-zero, it defines the recommended value for programming the PORTPMSC register BESLD field. This is programmed by BIOS based on platform parameters. Power Well: Core
3:0	0h RW/L	Default Best Effort Service Latency (DBESL): If the value of this field is non-zero, it defines the recommended value for programming the PORTPMSC register BESL field. This is programmed by BIOS based on platform parameters. Power Well: Core

18.6.24 PCI Power Management Capability ID (PM_CID)—Offset 70h

Access Method



Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 70h

Default: 01h

7				4				0
0	0	0	0	0	0	0	0	1
PM_CID								

Bit Range	Default & Access	Field Name (ID): Description
7:0	01h RO	PCI Power Management Capability ID (PM_CID): A value of 01h indicates that this is a PCI Power Management capabilities field. Power Well: Core

18.6.25 Next Item Pointer #1 (PM_NEXT)—Offset 71h

This register is modified and maintained by BIOS

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 71h

Default: 80h

7				4				0
1	0	0	0	0	0	0	0	0
PM_NEXT								

Bit Range	Default & Access	Field Name (ID): Description
7:0	80h RW/L	Next Item Pointer #1 (PM_NEXT): This register defaults to 80h, which indicates that the next capability registers begin at configuration offset 80h. This register is writable when the Access Control bit is set to '0'. This allows BIOS to effectively hide the next capability registers, if necessary. This register should only be written during system initialization before the plug-and-play software has enabled any master-initiated traffic. Values of: 80h implies next capability is MSI 00h implies that MSI capability is hidden. Note: This value is never expected to be programmed. Power Well: Core

18.6.26 Power Management Capabilities (PM_CAP)—Offset 72h

Normally, this register is read-only to report capabilities to the power management software. In order to report different power management capabilities depending on the system in which the Intel PCH is used, the write access to this register is controlled by the Access Control bit (ACCTRL). The value written to this register does not affect the hardware other than changing the value returned during a read. This register is modified and maintained by BIOS

Access Method



15	12	8	4	0
0	0 0 0 0	0 0 0 0	0 0 0 0	1 0 0 0
PME_Status	Data_Scale	Data_Select	PME_En	RSVD
				NSR
				RSVD2
				PowerState

Bit Range	Default & Access	Field Name (ID): Description
15	0b RW/1C	PME_Status: This bit is set when the Intel PCH XHC would normally assert the PME# signal independent of the state of the PME_En bit. Writing a 1 to this bit will clear it and cause the internal PME to deassert (if enabled). Writing a 0 has no effect. This bit must be explicitly cleared by the operating system each time the operating system is loaded. Power Well: SUS
14:13	00b RO	Data_Scale: The Intel PCH hardwires these bits to 00 because it does not support the associated Data register. Power Well: Core
12:9	0h RO	Data_Select: The Intel PCH hardwires these bits to 0000 because it does not support the associated Data register. Power Well: Core
8	0b RW	PME_En: A 1 enables the Intel PCH XHC to generate an internal PME signal when PME_Status is 1. This bit must be explicitly cleared by the operating system each time it is initially loaded. Power Well: SUS
7:4	0h RO	Reserved (RSVD): Reserved. Power Well: Core
3	1b RO	No Soft Reset (NSR):), this bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved. Upon transition from the D3hot to the D0 Initialized state, no additional operating system intervention is required to preserve Configuration Context beyond writing the PowerState bits. Transition from D3hot to D0 by a system or bus segment reset will return to the device state D0 Uninitialized with only PME context preserved if PME is supported and enabled. Power Well: Core
2	0b RO	Reserved (RSVD2): Reserved. Power Well: Core
1:0	00b RW	PowerState: This 2-bit field is used both to determine the current power state of XHC function and to set a new power state. The definition of the field values are: 00b - D0 state 11b - D3hot state If software attempts to write a value of 10b or 01b in to this field, the write operation must complete normally, however, the data is discarded and no state change occurs. When in the D3hot state, the Intel PCH must not accept accesses to the XHC memory range, but the configuration space must still be accessible. Power Well: Core

18.6.28 Message Signaled Interrupt CID (MSI_CID)—Offset 80h

Access Method



Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 80h

Default: 05h

7			4				0
0	0	0	0	0	1	0	1
C/D							

Bit Range	Default & Access	Field Name (ID): Description
7:0	05h RO	Capability ID (CID): Indicates that this is an MSI capability Power Well: Core

18.6.29 Next item pointer (MSI_NEXT)—Offset 81h

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Offset: [B:0, D:20, F:0] + 81h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
				NEXT			

Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RO	Next Pointer (NEXT): Indicates that this is the last item on the capability list Power Well: Core

18.6.30 Message Signaled Interrupt Message Control (MSI_MCTL)—Offset 82h

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

Offset: [B:0, D:20, F:0] + 82h

Default: 0086h

15			12				8				4				0
0	0	0	0	0	0	0	0	1	0	0	0	0	1	1	0
RSVD							PVM	C64	MME			MMC			MSIE

Bit Range	Default & Access	Field Name (ID): Description
15:9	00h RO	Reserved (RSVD): Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
8	0b RO	Per-Vector Masking Capable (PVM): Specifies whether controller supports MSI per vector masking. Not supported Power Well: Core
7	1b RO	64 Bit Address Capable (C64): Specifies whether capable of generating 64-bit messages. This device is 64-bit capable. Power Well: Core
6:4	0h RW	Multiple Message Enable (MME): Indicates the number of messages the controller should assert. This device supports multiple message MSI. Power Well: Core
3:1	011b RO	Multiple Message Capable (MMC): Indicates the number of messages the controller wishes to assert. This field must be set by HW to reflect the number of Interrupters supported. Encoding number of Vectors requested (number of Interrupters) 000 1 001 2 010 4 011 8 100 16 101 32 110-111 Reserved Power Well: Core
0	0b RW	MSI Enable (MSIE): If set to 1, MSI is enabled and the traditional interrupt pins are not used to generate interrupts. If cleared to 0, MSI operation is disabled and the traditional interrupt pins are used. Power Well: Core

18.6.31 Message Signaled Interrupt Message Address (MSI_MAD)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + 84h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Addr								RSVD

Bit Range	Default & Access	Field Name (ID): Description
31:2	00000000h RW	Addr: Lower DW of system specified message address, always DWORD aligned Power Well: Core
1:0	00b RO	Reserved (RSVD): Reserved. Power Well: Core

18.6.32 Message Signaled Interrupt Upper Address (MSI_MUAD)—Offset 88h

Access Method



Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + 88h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

UpperAddr

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Upper Addr (UpperAddr): Upper DW of system specified message address. Power Well: Core

18.6.33 Message Signaled Interrupt Message Data (MSI_MD)—Offset 8Ch

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

Offset: [B:0, D:20, F:0] + 8Ch

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0

Data

Bit Range	Default & Access	Field Name (ID): Description
15:0	0000h RW	Data: This 16-bit field is programmed by system software if MSI is enabled. Its content is driven onto the lower word (PCI AD(15:0)) during the data phase of the MSI memory write transaction. The Multiple Message Enable field (bits 6-4 of the Message Control register) defines the number of low order message data bits the function is permitted to modify to generate its system software allocated vectors. For example, a Multiple Message Enable encoding of 010 indicates the function has been allocated four vectors and is permitted to modify message data bits 1 and 0 (a function modifies the lower message data bits to generate the allocated number of vectors). If the Multiple Message Enable field is 000, the function is not permitted to modify the message data. Power Well: Core

18.6.34 High Speed Configuration 1 (HSCFG1)—Offset A0h


Not for EDS

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + A0h

Default: 00000100h



Intel Atom® Processor E3800 Product Family
Datasheet
2151




Default: 00002000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1				HSAAIM	HSOAAPEPM	HSIAAPEPM	HSIIPAPC	HSIIPANEPT
								HSIIPASIT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core
15	0h RW	HS ASYNC Active IN Mask (HSAAIM): Determines if the Async Active will mask/ignore IN EP s. 0 HS ASYNC Active will include IN EP s. 1 HS ASYNC Active will mask/ignore IN EP s. Power Well: Core
14	0h RW	HS OUT ASYNC Active Polling EP Mask (HSOAAPEPM): Determines if the Async Active for OUT HS/FS/LS masks/ignores EP s that are polling/PINGing (HS) due to NAK. 0 HS OUT ASYNC Active will include EP s that are polling. 1 HS OUT ASYNC Active will mask/ignore EP s that are polling. Power Well: Core
13	1h RW	HS IN ASYNC Active Polling EP Mask (HSIAAPEPM): Determines if the Async Active for IN HS/FS/LS masks/ignores EP s that are polling due to NAK. 0 HS IN ASYNC Active will include EP s that are polling. 1 HS IN ASYNC Active will mask/ignore EP s that are polling. Power Well: Core
12:11	0h RW	HS INTR IN Periodic Active Policy Control (HSIIPAPC): Controls how the HS INTR IN periodic active is used to generate the global periodic active. This will determine how the smallest service interval among active EP s and number of active EP s are used. 0 HS INTR IN periodic active will be used to generate periodic active if Service Interval Threshold OR Numb of EP Threshold values meet the requirement. 1 HS INTR IN periodic active will be used to generate periodic active if Service Interval Threshold AND Numb of EP Threshold values meet the requirement. 2 Always allow HS INTR EP s to be used in the generation of the global Periodic Active indication. 3 Never allow HS INTR EP s to be used in the generation of the global Periodic Active indication Power Well: Core
10:4	00h RW	HS INTR IN Periodic Active Num of EP Threshold (HSIIPANEPT): Defines the threshold used to determine if Periodic Active may include HS/FS/LS INTR IN EP active indication. If there are more than NumEPThreshold active HS/FS/LS INTR EP s then they may be included as part of the periodic active generation. Power Well: Core
3:0	0h RW	HS INTR IN Periodic Active Service Interval Threshold (HSIIPASIT): Defines the Service Interval threshold used to determine if Periodic Active will include HS/FS/LS INTR IN EP active indication. If there are any active HS/FS/LS INTR EP s with a service interval less than or equal to this threshold then they may be included as part of the periodic active generation. Power Well: Core

18.6.36 Super Speed Configuration 1 (SSCFG1)—Offset B0h

Refer to the switching flows section of this document. Not for EDS



Bit Range	Default & Access	Field Name (ID): Description
13	0b RW	MODPHY Power Gate Enable for non-U2 states (MPHYGENONU2): This bit controls whether LPT-LPT xHC will allow modPHY power gating or not when a port is in states other than U2. Note that this single bit controls all ports of xHC. 0b xHC shall not initiate Power Gate Request If xHC had initiated Power Gate Request before this bit is programmed to 0, xHC shall initiate the handshake to wake modPHY from power gated state. 1b xHC is enabled to initiate Power Gate Request if power gating conditions are met. Power Well: Core
12	0h RW	xHC SS Async Active Propagation Enable (SSAAPE): This register controls the ss async active exposure to PMC via the xHC active indication 0 SS Async Active is not propagated to PMC 1 SS Async Active is propagated to PMC Power Well: Core
11:8	0h RO	Rsvd2: Reserved Power Well: Core
7	1b RW	USB3 SS Port Polling Enable Active (SSPPENAB): 0: Allow blocking of USB3 Super-speed port from starting Polling.LFPS. 1: Disallow blocking of USB3 Super-speed port from starting Polling.LFPS (A stepping behavior). NOTE: When this bit is cleared, Polling.LFPS blocking is controlled by SSPPEN bit. Power Well: SUS
6	0h RW	ECO2: ECO bits are used during silicon bringup for FIBing. Power Well: SUS
5	0h RW	Receiver Detect Staggering Disable (RXDETSTGDIS): When set, this register bit disables receiver detect staggering between all 6 USB3 lanes Note that the bit is ONLY meant for SW to disable the staggering if desired. Once it is set to disabled, SW is not allowed to re-enable the staggering by clearing the bit. Power Well: SUS
4:3	1h RW	Gotorxelecidle Polling Timer Timeout Value (G2RXPTTV): Timeout value for Gotorxelecidle Polling Timer: 00: 1 to 2 us (Simulation speed up mode only). 01: 19 to 20 us (Default). 10: 23 to 24 us. 11: 199 to 200 us. This register needs to be programmed when G2RXPOLLTMREN = 0. Power Well: SUS
2	1b RW	Gotorxelecidle Polling Timer Enable (G2RXPTTE): If enabled (1), Gasket starts a timer after transmitting high speed data AND not receiving LFPS, and will only de-assert GoToRxElecIdle after timer expires during Polling. If disabled (0), Gasket will assert / de-assert GoToRxElecIdle purely based on Gotorxelecidle assertion upon RxElecIdle de-assertion (LFPS detected) enable bit (G2RXERXEE) and Gotorxelecidle assertion when not transmitting high speed data enable bit (G2RXETXHSDE) Power Well: SUS
1	1b RW	GotoRxElecIdle Assertion Upon RxElecIdle Exit Enable (G2RXERXEE): When enabled (set to '1'), allow Gasket to assert GoToRxElecIdle to UAFE to turn off its receiver upon the de-assertion of GoToRxElecIdle (LFPS detected). This bit needs to be programmed when the USB3 port is not enabled. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
0	1b RW	GotoRxElecIdle Assertion When Transmitting High Speed Data Enable (G2RXETXHSDE): When enabled (set to '1'), allow Gaskets to assert GoToRxElecIdle to UAFE to turn off its receiver when not transmitting high speed data: P0 and TxElecIdle = 1. This bit needs to be programmed when the USB3 port is not enabled. Power Well: SUS

18.6.37 XHCI USB2 Overcurrent Pin Mapping 1 (U2OCM1)—Offset C0h

The RW/L property of this register is controlled by OCCFDONE bit.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + C0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd1						OC2M	Rsvd0	OC1M

Bit Range	Default & Access	Field Name (ID): Description
31:12	0h RO	Rsvd1: Reserved Power Well: SUS
11:8	0h RW/L	OC2 Mapping (OC2M): Each bit position maps OC2 to a set of ports as follows: The OC2 pin is ganged to the overcurrent signal of each port that has its corresponding bit set. It is SW's responsibility to ensure that a given port's bit map is set only for one OC pin. Bit 15 14 13 12 11 10 9 8 Port 8 7 6 5 4 3 2 1 Power Well: SUS
7:4	0h RO	Rsvd0: Reserved Power Well: SUS
3:0	0h RW/L	OC1 Mapping (OC1M): Each bit position maps OC1 to a set of ports as follows: The OC1 pin is ganged to the overcurrent signal of each port that has its corresponding bit set. It is SW's responsibility to ensure that a given port's bit map is set only for one OC pin Bit 7 6 5 4 3 2 1 0 Port 8 7 6 5 4 3 2 1 Power Well: SUS

18.6.38 XHCI USB2 Overcurrent Pin Mapping 2 (U2OCM2)—Offset C4h

Reserved

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + C4h

Default: 00000000h





Bit Range	Default & Access	Field Name (ID): Description
8	0b RW/L	OC2 Mapping (OC2M): Each bit position maps OC2 to a set of ports as follows: The OC2 pin is ganged to the overcurrent signal of each port that has its corresponding bit set. It is SW's responsibility to ensure that a given port's bit map is set only for one OC pin. Bit 11 10 9 8 Port 4 3 2 1 Power Well: SUS
7:1	00h RO	Rsvd4: Reserved. Power Well: Core
0	0b RW/L	OC1 Mapping (OC1M): Each bit position maps OC1 to a set of ports as follows: The OC1 pin is ganged to the overcurrent signal of each port that has its corresponding bit set. It is SW's responsibility to ensure that a given port's bit map is set only for one OC pin Bit 3 2 1 0 Port 4 3 2 1 Power Well: SUS

18.6.40 XHCI USB3 Overcurrent Pin Mapping 2 (U3OCM2)—Offset CCh

The RW/L property of this register is controlled by OCCFDONE bit. Note: U3OCM2 allows the OC pins 8:5 to be mapped to the same 6 SS ports that U3OCM1 allows. This allows flexibility in pairing SS ports with HS ports at the connector. Care must be taken to make sure OC pin assignment is consistent across USB3 and USB2 ports (depending upon the pairing).

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + CCh

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	Rsvd1	OC8M	Rsvd2	OC7M	Rsvd3	OC6M	Rsvd4	OC5M

Bit Range	Default & Access	Field Name (ID): Description
31:25	00h RO	Rsvd1: Reserved. Power Well: Core
24	0b RW/L	OC8 Mapping (OC8M): Each bit position maps OC8 to a set of ports as follows: The OC8 pin is ganged to the overcurrent signal of each port that has its corresponding bit set. It is SW's responsibility to ensure that a given port's bit map is set only for one OC pin. Bit 24 Port 1 Power Well: SUS
23:17	00h RO	Rsvd2: Reserved. Power Well: Core



Access Method

Offset: [B:0, D:20, F:0] + D0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd1						USB2HCSSEL		

Bit Range	Default & Access	Field Name (ID): Description
31:9	000000h RO	Rsvd1: Reserved. Power Well: Core
8:0	000h RW	USB2 HC Selector (USB2HCSEL): This field maps the USB2 port between the XHCI and EHCI controller (it has no effect on USB3). When set to 1, Routes USB2 pins to the XHCI controller. Routes OC pin to XHCI (based on the mapping in the OC register). Masks the USB2 port from the EHCI. Masks OC pin from ECHI. When set to 0, Routes all the USB2 pins to the legacy EHCI. Routes OC pin to EHCI (based on the mapping in the OC register). Masks the USB2 port from the XHCI. Masks OC pin from XHCI. Port to bit mapping is in one-hot encoding, i.e. bit 0 controls port 1 and so on. Power Well: SUS



18.6.42 USB2 Port Routing Mask (USB2PRM)—Offset D4h

The RW/L property of this register is controlled by the ACCTRL bit.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + D4h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1							USB2HCSELM	

Bit Range	Default & Access	Field Name (ID): Description
31:9	000000h RO	Rsvd1: Reserved. Power Well: Core
8:0	000h RW/L	USB2 HC Selector Mask (USB2HCSELM): This field allows the BIOS to communicate to the OS which USB 2.0 ports can be switched from the EHCI controller to the xHCI controller. When set to 1, The OS may switch the USB 2.0 port between the EHCI and xHCI host controllers by modifying the corresponding USB2HCSEL bit. When set to 0, The OS shall not modify the corresponding USB2HCSEL bit. BIOS shall set this bit to a '1' if the corresponding USB2HCSEL bit is RW, unless it knows an internal USB 2.0 device attached to that port will not work under xHCI. Port to bit mapping is in one-hot encoding, i.e. bit 0 controls port 1 and so on. Power Well: Core

18.6.43 USB3 Port Routing (USB3PR)—Offset D8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + D8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1							USB3SSEN	

Bit Range	Default & Access	Field Name (ID): Description
31:4	0000000h RO	Rsvd1: Reserved. Power Well: Core



31				28				24				20				16				12				8				4				0																							
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0																							
Rsvd1								SPARE								USH_DEVID				XDD_EN				SRAMPWRGTDIS				USB2PLLSDIS				USBIOPMDIS				XHCDCGDIS				USBRDIS				SSPRTCNT				HSPRTCNT				XHCFD			

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Rsvd1: Reserved. Power Well: Core
23:14	000h RO/V	Spare Fuses (SPARE): Will be used for VLV2. Power Well: SUS
13:11	000b RO/V	USH DevID (USH_DEVID): LSB bits of USH PCIe Device ID The 3 LSB bits enable defining up to 8 separate USH SKUs if required Power Well: SUS
10	0b RO/V	Debug Device Enable (XDD_EN): 0 : Debug Device is Enabled 1: Debug Device is Disabled Power Well: SUS
9	0h RO/V	SRAM Power Gating Disable (SRAMPWRGTDIS): 0: SRAM Power Gating Enabled 1: SRAM Power Gating Disabled Power Well: SUS
8	0h RO/V	USB2 PLL Shutdown Disable (USB2PLLSDIS): 0: USB2 PLL shutdown enabled 1: USB2 PLL shutdown disabled Power Well: SUS
7	0h RO/V	USB I/O Power Management Disable (USBIOPMDIS): 0: USB2 HW LPM and USB3 HW Ux under XHC enabled 1: USB2 HW LPM and USB3 HW Ux under XHC disabled Power Well: SUS
6	0h RO/V	XHC Dynamic Clock Gating Disable (XHCDCGDIS): 0: USB3 (XHC) dynamic clock gating enabled 1: USB3 (XHC) dynamic clock gating disabled Power Well: SUS
5	0h RO/V	USBr Disable (USBRDIS): 0: USBr enabled 1: USBr disabled Power Well: SUS
4:3	0h RO/V	SS Port Count (SSPRTCNT): This field specifies number of SS ports present. Supported combinations are: 00: 6 SS ports 01: 4 SS ports 10: 2 SS ports 11: 0 SS ports Power Well: SUS
2:1	0h RO/V	HS Port Count (HSPRTCNT): This field specifies number HS ports present. Supported combinations are: 00: 14 HS ports 01: 12 HS ports 10: 10 HS ports 11: N/A (reserved) Power Well: SUS



Access Method

Offset: [B:0, D:20, F:0] + E4h

Bit Range	Default & Access	Field Name (ID): Description
31:4	0000000h RO	Rsvd1: Reserved. Power Well: Core
3:0	0h RW/O	USB2 Port Disable Override (USB2PDO): A '1' in a bit position prevents the corresponding USB2 port from reporting a Device Connection to the XHC. Power Well: SUS

18.6.47 USB3 Port Disable Override (USB3PDO)—Offset E8h

Access Method

Offset: [B:0, D:20, F:0] + E8h

Bit Range	Default & Access	Field Name (ID): Description
31:4	0000000h RO	Rsvd1: Reserved. Power Well: Core



Not for FDS

Access Method

Offset: [B:0, D:20, F:0] + F0h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Super Speed DFT CRC (SSDFTCRC): These register bits contain the value of Super Speed DFT CRC Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7	0h RW	Super Speed DFT LFPS Mode Select (SSDFTLMSEL): This bit selects the Super Speed DFT LFPS mode, and will only take effect when Super Speed HBP mode is enabled. 0b: HBP logic will internally loopback TX LFPS as RX LFPS and AFE RX LFPS path to the controller is disconnected. 1b: RX LFPS path works normally Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
11:8	0h RW	Loop Number (UTMILPBKLOOPN_3_0): Number of repeatable fixed pattern within a packet Note: Connect register bit 3 to counter bit 7, register bit 2 to counter bit 5, register bit 1 to counter bit 3, register bit 0 to counter bit 1. Counter bits 6, 4, 2 and 0 will be tied off to 0. Hence, the programmable loop number shall be: 0000b: 0 loop 0001b: 2 loops 0010b: 8 loops 0011b: 10 loops 1100b: 160 loops 1101b: 162 loops 1110b: 168 loops 1111b: 170 loops (max) Power Well: Core
7:6	0h RW	Operational Mode (UTMIOPMODE_1_0): Operational Mode in test mode. These signals select between various operational modes: 00b: Normal Operation 01b: Non-Driving 10b: Disable Bit Stuffing and NRZI encoding 11b: Reserved Power Well: Core
5	0h RW	Termination Select (UTMITERMSEL): Termination Select in test mode. This signal selects between the FS and HS terminations: 0b: HS termination enabled 1b: FS termination enabled Power Well: Core
4:3	0h RW	Transceiver Select (UTMIXCVRSELECT_1_0): Transceiver Select in test mode. This signal selects between the LS, FS and HS transceivers: 00b: HS transceiver enabled 01b: FS transceiver enabled 10b: LS transceiver enabled 11b: Reserved Power Well: Core
2:1	0h RO	UTMI+ Loopback Status (UTMILPBKSTS): Loopback Status for port selected by UTMIDFTPS 00b: Reset condition 01b: Comparator has started receiving data and the received data matches with the TX pattern. 10b: Comparator has started receiving data the received data does not match with the TX pattern but there was no assertion of RC error from UTMI. 11b: Comparator has started receiving data and RX ERROR was asserted for at least one clock by UTMI. Note that this does not reflect the status of pattern comparison since RX error from UTMI is unexpected for loopback. Power Well: Core
0	0h RW	Loopback Enable (UTMILPBKEN): Enable loopback test mode. If asserted, loopback test mode is enabled Power Well: Core

18.6.51 Manufacturing Process ID (MANID)—Offset F8h

Not for EDS

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + F8h

Default: 00000F00h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	1	1	1
0	0	0	0	0	0	0	0	0
Rsvd	DPID	SID	MNFR	PPID				



Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RO	Reserved (Rsvd): Reserved. Power Well: Core
27:24	0h RO/V	Dot Portion Process ID (DPID): See Chap 6 for value Power Well: Core
23:16	00h RO/V	Stepping ID (SID): This field is incremented for each stepping of the part. Note that this field can be used by software to differentiate stepping when the Revision ID may not change. See Chap 6 for value Power Well: Core
15:8	0Fh RO	Manufacturer (MNFR): 0Fh = Intel. Power Well: Core
7:0	00h RO/V	Process Portion Process ID (PPID): See Chap 6 for value Power Well: Core

18.6.52 DFT 3 (DFT3)—Offset FCh

Not for EDS

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:20, F:0] + FCh

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
UTMILPBKPAT				RSVD		UTMILPBKSEL_7_0		UTMILPBKPATSEL
								UTMILPBKTYPE

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	Loopback Pattern (UTMILPBKPAT): 2-byte pattern for loopback Note: This 2-byte pattern will be replicated to the upper 2-byte to form the DW pattern Power Well: Core
15:10	00h RO	Reserved (RSVD): Reserved Power Well: Core
9:2	00h RW	Loopback Lane Select (UTMILPBKSEL_7_0): Port is selected if the corresponding bit is selected Note: MSB is for UTMI+ Port13, LSB is for UTMI+ Port0 Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW	Loopback Pattern (UTMILPBKPATSEL): Near end loopback pattern generation type: 0b: Fixed pattern 1b: USB2 test packet Power Well: Core
0	0b RW	Loopback Type (UTMILPBKTYPE): Loopback Type in test mode. This signal selects between DNELB and ANELB, and will only take effect if DTUTMILPBKEN is set. 0b: Digital Near-End Loopback (DNELB) 1b: Analog Near-End Loopback (ANELB) Note: Analog Far-End Loopback (AFELB) is not supported Power Well: Core



18.7 USB xHCI Memory Mapped I/O Registers

Table 213. Summary of USB xHCI Memory Mapped I/O Registers—MBAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–0h	1	"Capability Registers Length (CAPLENGTH)—Offset 0h" on page 2176	80h
2–3h	2	"Host Controller Interface Version Number (HCIVERSION)—Offset 2h" on page 2176	0100h
4–7h	4	"Structural Parameters 1 (HCSPARAMS1)—Offset 4h" on page 2177	07000820h
8–Bh	4	"Structural Parameters 2 (HCSPARAMS2)—Offset 8h" on page 2178	84000054h
C–Fh	4	"Structural Parameters 3 (HCSPARAMS3)—Offset Ch" on page 2179	00040001h
10–13h	4	"Capability Parameters (HCCPARAMS)—Offset 10h" on page 2180	200071E1h
14–17h	4	"Doorbell Offset (DBOFF)—Offset 14h" on page 2182	00003000h
18–1Bh	4	"Runtime Register Space Offset (RTSOFF)—Offset 18h" on page 2182	00002000h
80–83h	4	"USB Command (USBCMD)—Offset 80h" on page 2183	00000000h
84–87h	4	"USB Status (USBSTS)—Offset 84h" on page 2185	00000001h
88–8Bh	4	"Page Size (PAGESIZE)—Offset 88h" on page 2187	00000001h
94–97h	4	"Device Notification Control (DNCTRL)—Offset 94h" on page 2188	00000000h
98–9Bh	4	"Command Ring Low (CRCR_LO)—Offset 98h" on page 2189	00000000h
9C–9Fh	4	"Command Ring High (CRCR_HI)—Offset 9Ch" on page 2190	00000000h
B0–B3h	4	"Device Context Base Address Array Pointer Low (DCBAAP_LO)—Offset B0h" on page 2191	00000000h
B4–B7h	4	"Device Context Base Address Array Pointer High (DCBAAP_HI)—Offset B4h" on page 2191	00000000h
B8–BBh	4	"Configure (CONFIG)—Offset B8h" on page 2192	00000000h
480–483h	4	"Port 1 Status and Control USB3 (PORTSC1USB2)—Offset 480h" on page 2193	000002A0h
484–487h	4	"Port 1 Power Management Status and Control USB2 (PORTPMSC1USB2)—Offset 484h" on page 2194	00000000h
48C–48Fh	4	"Port X Hardware LPM Control Register (PORTHLP1)—Offset 48Ch" on page 2196	00000000h
490–493h	4	"Port 2 Status and Control USB3 (PORTSC2USB2)—Offset 490h" on page 2197	000002A0h
494–497h	4	"Port 2 Power Management Status and Control USB2 (PORTPMSC2USB2)—Offset 494h" on page 2199	00000000h
49C–49Fh	4	"Port X Hardware LPM Control Register (PORTHLP2)—Offset 49Ch" on page 2200	00000000h
4A0–4A3h	4	"Port 3 Status and Control USB3 (PORTSC3USB2)—Offset 4A0h" on page 2200	000002A0h
4A4–4A7h	4	"Port 3 Power Management Status and Control USB2 (PORTPMSC3USB2)—Offset 4A4h" on page 2202	00000000h
4AC–4AFh	4	"Port X Hardware LPM Control Register (PORTHLP3)—Offset 4ACh" on page 2203	00000000h
4B0–4B3h	4	"Port 4 Status and Control USB3 (PORTSC4USB2)—Offset 4B0h" on page 2204	000002A0h
4B4–4B7h	4	"Port 4 Power Management Status and Control USB2 (PORTPMSC4USB2)—Offset 4B4h" on page 2206	00000000h



Table 213. Summary of USB xHCI Memory Mapped I/O Registers—MBAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
4BC–4BFh	4	"Port X Hardware LPM Control Register (PORTHLP4)—Offset 4BCh" on page 2207	00000000h
4C0–4C3h	4	"Port 8 Status and Control USB2 (PORTSC5USB2)—Offset 4C0h" on page 2208	000002A0h
4C4–4C7h	4	"Port 5 Power Management Status and Control USB2 (PORTPMSC5USB2)—Offset 4C4h" on page 2210	00000000h
4CC–4CFh	4	"Port X Hardware LPM Control Register (PORTHLP5)—Offset 4CCh" on page 2211	00000000h
4D0–4D3h	4	"Port 6 Status and Control USB2 (PORTSC6USB2)—Offset 4D0h" on page 2212	000002A0h
4D4–4D7h	4	"Port 6 Power Management Status and Control USB2 (PORTPMSC6USB2)—Offset 4D4h" on page 2214	00000000h
4DC–4DFh	4	"Port X Hardware LPM Control Register (PORTHLP6)—Offset 4DCh" on page 2215	00000000h
4E0–4E3h	4	"Port 1 Status and Control USB3 (PORTSC1USB3)—Offset 4E0h" on page 2215	000002A0h
4E4–4E7h	4	"Port 1 Power Management Status and Control USB3 (PORTPMSC1USB3)—Offset 4E4h" on page 2217	00000000h
4E8–4EBh	4	"Port 1 Link Info (PORTLI1)—Offset 4E8h" on page 2218	00000000h
2000–2003h	4	"Microframe Index (MFINDEX)—Offset 2000h" on page 2219	00000000h
2020–2023h	4	"Interrupter 1 Management (IMAN1)—Offset 2020h" on page 2219	00000000h
2024–2027h	4	"Interrupter 1 Moderation (IMOD1)—Offset 2024h" on page 2220	00000FA0h
2028–202Bh	4	"Event Ring Segment Table Size 1 (ERSTS1)—Offset 2028h" on page 2220	00000000h
2030–2033h	4	"Event Ring Segment Table Base Address Low 1 (ERSTBA_LO1)—Offset 2030h" on page 2221	00000000h
2034–2037h	4	"Event Ring Segment Table Base Address High 1 (ERSTBA_HI1)—Offset 2034h" on page 2222	00000000h
2038–203Bh	4	"Event Ring Dequeue Pointer Low 1 (ERDP_LO1)—Offset 2038h" on page 2222	00000000h
203C–203Fh	4	"Event Ring Dequeue Pointer High 1 (ERDP_HI1)—Offset 203Ch" on page 2223	00000000h
2040–2043h	4	"Interrupter 2 Management (IMAN2)—Offset 2040h" on page 2223	00000000h
2044–2047h	4	"Interrupter 2 Moderation (IMOD2)—Offset 2044h" on page 2224	00000FA0h
2048–204Bh	4	"Event Ring Segment Table Size 2 (ERSTS2)—Offset 2048h" on page 2225	00000000h
2050–2053h	4	"Event Ring Segment Table Base Address Low 2 (ERSTBA_LO2)—Offset 2050h" on page 2225	00000000h
2054–2057h	4	"Event Ring Segment Table Base Address High 2 (ERSTBA_HI2)—Offset 2054h" on page 2226	00000000h
2058–205Bh	4	"Event Ring Dequeue Pointer Low 2 (ERDP_LO2)—Offset 2058h" on page 2227	00000000h
205C–205Fh	4	"Event Ring Dequeue Pointer High 2 (ERDP_HI2)—Offset 205Ch" on page 2227	00000000h
2060–2063h	4	"Interrupter 3 Management (IMAN3)—Offset 2060h" on page 2228	00000000h
2064–2067h	4	"Interrupter 3 Moderation (IMOD3)—Offset 2064h" on page 2228	00000FA0h

**Table 213. Summary of USB xHCI Memory Mapped I/O Registers—MBAR (Continued)**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
2068–206Bh	4	"Event Ring Segment Table Size 3 (ERSTS3)—Offset 2068h" on page 2229	00000000h
2070–2073h	4	"Event Ring Segment Table Base Address Low 3 (ERSTBA_LO3)—Offset 2070h" on page 2230	00000000h
2074–2077h	4	"Event Ring Segment Table Base Address High 3 (ERSTBA_HI3)—Offset 2074h" on page 2230	00000000h
2078–207Bh	4	"Event Ring Dequeue Pointer Low 3 (ERDP_LO3)—Offset 2078h" on page 2231	00000000h
207C–207Fh	4	"Event Ring Dequeue Pointer High 3 (ERDP_HI3)—Offset 207Ch" on page 2232	00000000h
2080–2083h	4	"Interrupter 4 Management (IMAN4)—Offset 2080h" on page 2232	00000000h
2084–2087h	4	"Interrupter 4 Moderation (IMOD4)—Offset 2084h" on page 2233	00000FA0h
2088–208Bh	4	"Event Ring Segment Table Size 4 (ERSTS4)—Offset 2088h" on page 2233	00000000h
2090–2093h	4	"Event Ring Segment Table Base Address Low 4 (ERSTBA_LO4)—Offset 2090h" on page 2234	00000000h
2094–2097h	4	"Event Ring Segment Table Base Address High 4 (ERSTBA_HI4)—Offset 2094h" on page 2235	00000000h
2098–209Bh	4	"Event Ring Dequeue Pointer Low 4 (ERDP_LO4)—Offset 2098h" on page 2235	00000000h
209C–209Fh	4	"Event Ring Dequeue Pointer High 4 (ERDP_HI4)—Offset 209Ch" on page 2236	00000000h
20A0–20A3h	4	"Interrupter 5 Management (IMAN5)—Offset 20A0h" on page 2236	00000000h
20A4–20A7h	4	"Interrupter 5 Moderation (IMOD5)—Offset 20A4h" on page 2237	00000FA0h
20A8–20ABh	4	"Event Ring Segment Table Size 5 (ERSTS5)—Offset 20A8h" on page 2238	00000000h
20B0–20B3h	4	"Event Ring Segment Table Base Address Low 5 (ERSTBA_LO5)—Offset 20B0h" on page 2238	00000000h
20B4–20B7h	4	"Event Ring Segment Table Base Address High 5 (ERSTBA_HI5)—Offset 20B4h" on page 2239	00000000h
20B8–20BBh	4	"Event Ring Dequeue Pointer Low 5 (ERDP_LO5)—Offset 20B8h" on page 2240	00000000h
20BC–20BFh	4	"Event Ring Dequeue Pointer High 5 (ERDP_HI5)—Offset 20BCh" on page 2240	00000000h
20C0–20C3h	4	"Interrupter 6 Management (IMAN6)—Offset 20C0h" on page 2241	00000000h
20C4–20C7h	4	"Interrupter 6 Moderation (IMOD6)—Offset 20C4h" on page 2241	00000FA0h
20C8–20CBh	4	"Event Ring Segment Table Size 6 (ERSTS6)—Offset 20C8h" on page 2242	00000000h
20D0–20D3h	4	"Event Ring Segment Table Base Address Low 6 (ERSTBA_LO6)—Offset 20D0h" on page 2243	00000000h
20D4–20D7h	4	"Event Ring Segment Table Base Address High 6 (ERSTBA_HI6)—Offset 20D4h" on page 2243	00000000h
20D8–20DBh	4	"Event Ring Dequeue Pointer Low 6 (ERDP_LO6)—Offset 20D8h" on page 2244	00000000h
20DC–20DFh	4	"Event Ring Dequeue Pointer High 6 (ERDP_HI6)—Offset 20DCh" on page 2245	00000000h
20E0–20E3h	4	"Interrupter 7 Management (IMAN7)—Offset 20E0h" on page 2245	00000000h




Table 213. Summary of USB xHCI Memory Mapped I/O Registers—MBAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
20E4–20E7h	4	"Interrupter 7 Moderation (IMOD7)—Offset 20E4h" on page 2246	00000FA0h
20E8–20EBh	4	"Event Ring Segment Table Size 7 (ERSTS7)—Offset 20E8h" on page 2246	00000000h
20F0–20F3h	4	"Event Ring Segment Table Base Address Low 7 (ERSTBA_LO7)—Offset 20F0h" on page 2247	00000000h
20F4–20F7h	4	"Event Ring Segment Table Base Address High 7 (ERSTBA_HI7)—Offset 20F4h" on page 2248	00000000h
20F8–20FBh	4	"Event Ring Dequeue Pointer Low 7 (ERDP_LO7)—Offset 20F8h" on page 2248	00000000h
20FC–20FFh	4	"Event Ring Dequeue Pointer High 7 (ERDP_HI7)—Offset 20FCh" on page 2249	00000000h
2100–2103h	4	"Interrupter 8 Management (IMAN8)—Offset 2100h" on page 2249	00000000h
2104–2107h	4	"Interrupter 8 Moderation (IMOD8)—Offset 2104h" on page 2250	00000FA0h
2108–210Bh	4	"Event Ring Segment Table Size 8 (ERSTS8)—Offset 2108h" on page 2251	00000000h
2110–2113h	4	"Event Ring Segment Table Base Address Low 8 (ERSTBA_LO8)—Offset 2110h" on page 2251	00000000h
2114–2117h	4	"Event Ring Segment Table Base Address High 8 (ERSTBA_HI8)—Offset 2114h" on page 2252	00000000h
2118–211Bh	4	"Event Ring Dequeue Pointer Low 8 (ERDP_LO8)—Offset 2118h" on page 2253	00000000h
211C–211Fh	4	"Event Ring Dequeue Pointer High 8 (ERDP_HI8)—Offset 211Ch" on page 2253	00000000h
3000–3003h	4	"Door Bell 1 (DOORBELL1)—Offset 3000h" on page 2254	00000000h
3004–3007h	4	"Door Bell 2 (DOORBELL2)—Offset 3004h" on page 2255	00000000h
3008–300Bh	4	"Door Bell 3 (DOORBELL3)—Offset 3008h" on page 2256	00000000h
300C–300Fh	4	"Door Bell 4 (DOORBELL4)—Offset 300Ch" on page 2256	00000000h
3010–3013h	4	"Door Bell 5 (DOORBELL5)—Offset 3010h" on page 2257	00000000h
3014–3017h	4	"Door Bell 6 (DOORBELL6)—Offset 3014h" on page 2257	00000000h
3018–301Bh	4	"Door Bell 7 (DOORBELL7)—Offset 3018h" on page 2258	00000000h
301C–301Fh	4	"Door Bell 8 (DOORBELL8)—Offset 301Ch" on page 2258	00000000h
3020–3023h	4	"Door Bell 9 (DOORBELL9)—Offset 3020h" on page 2259	00000000h
3024–3027h	4	"Door Bell 10 (DOORBELL10)—Offset 3024h" on page 2260	00000000h
3028–302Bh	4	"Door Bell 11 (DOORBELL11)—Offset 3028h" on page 2260	00000000h
302C–302Fh	4	"Door Bell 12 (DOORBELL12)—Offset 302Ch" on page 2261	00000000h
3030–3033h	4	"Door Bell 13 (DOORBELL13)—Offset 3030h" on page 2261	00000000h
3034–3037h	4	"Door Bell 14 (DOORBELL14)—Offset 3034h" on page 2262	00000000h
3038–303Bh	4	"Door Bell 15 (DOORBELL15)—Offset 3038h" on page 2262	00000000h
303C–303Fh	4	"Door Bell 16 (DOORBELL16)—Offset 303Ch" on page 2263	00000000h
3040–3043h	4	"Door Bell 17 (DOORBELL17)—Offset 3040h" on page 2264	00000000h
3044–3047h	4	"Door Bell 18 (DOORBELL18)—Offset 3044h" on page 2264	00000000h
3048–304Bh	4	"Door Bell 19 (DOORBELL19)—Offset 3048h" on page 2265	00000000h
304C–304Fh	4	"Door Bell 20 (DOORBELL20)—Offset 304Ch" on page 2265	00000000h



Table 213. Summary of USB xHCI Memory Mapped I/O Registers—MBAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
3050–3053h	4	"Door Bell 21 (DOORBELL21)—Offset 3050h" on page 2266	00000000h
3054–3057h	4	"Door Bell 22 (DOORBELL22)—Offset 3054h" on page 2266	00000000h
3058–305Bh	4	"Door Bell 23 (DOORBELL23)—Offset 3058h" on page 2267	00000000h
305C–305Fh	4	"Door Bell 24 (DOORBELL24)—Offset 305Ch" on page 2268	00000000h
3060–3063h	4	"Door Bell 25 (DOORBELL25)—Offset 3060h" on page 2268	00000000h
3064–3067h	4	"Door Bell 26 (DOORBELL26)—Offset 3064h" on page 2269	00000000h
3068–306Bh	4	"Door Bell 27 (DOORBELL27)—Offset 3068h" on page 2269	00000000h
306C–306Fh	4	"Door Bell 28 (DOORBELL28)—Offset 306Ch" on page 2270	00000000h
3070–3073h	4	"Door Bell 29 (DOORBELL29)—Offset 3070h" on page 2270	00000000h
3074–3077h	4	"Door Bell 30 (DOORBELL30)—Offset 3074h" on page 2271	00000000h
3078–307Bh	4	"Door Bell 31 (DOORBELL31)—Offset 3078h" on page 2272	00000000h
307C–307Fh	4	"Door Bell 32 (DOORBELL32)—Offset 307Ch" on page 2272	00000000h
8000–8003h	4	"XCEP_SUPP_USB2_0—Offset 8000h" on page 2273	02000802h
8004–8007h	4	"XCEP_SUPP_USB2_1—Offset 8004h" on page 2273	20425355h
8008–800Bh	4	"XCEP_SUPP_USB2_2—Offset 8008h" on page 2274	30190601h
8010–8013h	4	"XCEP_SUPP_USB2_3 (Full Speed) (XCEP_SUPP_USB2_3)—Offset 8010h" on page 2275	000C0021h
8014–8017h	4	"XCEP_SUPP_USB2_4 (Low Speed) (XCEP_SUPP_USB2_4)—Offset 8014h" on page 2276	05DC0012h
8018–801Bh	4	"XCEP_SUPP_USB2_5 (High Speed) (XCEP_SUPP_USB2_5)—Offset 8018h" on page 2276	01E00023h
8020–8023h	4	"XCEP_SUPP_USB3_0—Offset 8020h" on page 2277	03000802h
8024–8027h	4	"XCEP_SUPP_USB3_1—Offset 8024h" on page 2278	20425355h
8028–802Bh	4	"XCEP_SUPP_USB3_2—Offset 8028h" on page 2278	10000107h
8030–8033h	4	"XCEP_SUPP_USB3_3—Offset 8030h" on page 2279	00050134h
8040–8043h	4	"XCEP_CMDM_STS0—Offset 8040h" on page 2280	00000CC1h
8044–8047h	4	"XCEP_CMDM_STS1—Offset 8044h" on page 2282	03FC0000h
8048–804Bh	4	"XCEP_CMDM_STS2—Offset 8048h" on page 2282	00000000h
804C–804Fh	4	"XCEP_CMDM_STS3—Offset 804Ch" on page 2283	00000000h
8050–8053h	4	"XCEP_CMDM_STS4—Offset 8050h" on page 2283	00000000h
8054–8057h	4	"XCEP_CMDM_STS5—Offset 8054h" on page 2284	00000000h
8070–8073h	4	"Host Controller Capability (HOST_CTRL_CAP_REG)—Offset 8070h" on page 2284	0000FCC0h
8078–807Bh	4	"Override EP Flow Control (HOST_CLR_MASK_REG)—Offset 8078h" on page 2285	00000000h
807C–807Fh	4	"Clear Active IN EP ID Control (HOST_CLR_IN_EP_VALID_REG)—Offset 807Ch" on page 2286	00000000h
8080–8083h	4	"Clear Poll Mask Control (HOST_CLR_PMASK_REG)—Offset 8080h" on page 2286	00000000h
8094–8097h	4	"Host Control Scheduler (HOST_CTRL_SCH_REG)—Offset 8094h" on page 2287	00008100h



Table 213. Summary of USB xHCI Memory Mapped I/O Registers—MBAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
80A0–80A3h	4	"Global Port Control (HOST_CTRL_PORT_CTRL)—Offset 80A0h" on page 2288	00003C0Fh
80C0–80C3h	4	"AUX Reset Control (AUX_CTRL_REG)—Offset 80C0h" on page 2289	015FC0F0h
80C4–80C7h	4	"Super Speed Bandwidth Overload (HOST_BW_OV_SS_REG)—Offset 80C4h" on page 2292	004A4008h
80C8–80CBh	4	"High Speed TT Bandwidth Overload (HOST_BW_OV_HS_REG)—Offset 80C8h" on page 2293	0001A01Fh
80CC–80CFh	4	"Bandwidth Overload Full Low Speed (HOST_BW_OV_FS_LS_REG)—Offset 80CCh" on page 2294	00014080h
80D0–80D3h	4	"System Bandwidth Overload (HOST_BW_OV_SYS_REG)—Offset 80D0h" on page 2294	00032010h
80D4–80D7h	4	"Scheduler Async Delay (HOST_CTRL_SCH_ASYNC_DELAY_REG)—Offset 80D4h" on page 2295	00000000h
80D8–80DBh	4	"AUX Power PHY Reset (UPOINTS_PON_RST_REG)—Offset 80D8h" on page 2296	00000000h
80E0–80E3h	4	"AUX Power Management Control (AUX_CTRL_REG1)—Offset 80E0h" on page 2297	808DBCA0h
80E4–80E7h	4	"Battery Charge (BATTERY_CHARGE_REG)—Offset 80E4h" on page 2299	00000000h
80E8–80EBh	4	"Port Watermark (HOST_CTRL_WATERMARK_REG)—Offset 80E8h" on page 2300	00800080h
80EC–80EFh	4	"SuperSpeed Port Link Control (HOST_CTRL_PORT_LINK_REG)—Offset 80ECh" on page 2301	18010600h
80F0–80F3h	4	"USB2 Port Link Control 1 (USB2_LINK_MGR_CTRL_REG1)—Offset 80F0h" on page 2303	310003A0h
80F4–80F7h	4	"USB2 Port Link Control 2 (USB2_LINK_MGR_CTRL_REG2)—Offset 80F4h" on page 2306	80C40620h
80F8–80FBh	4	"USB2 Port Link Control 3 (USB2_LINK_MGR_CTRL_REG3)—Offset 80F8h" on page 2307	F865EB6Bh
80FC–80FFh	4	"USB2 Port Link Control 4 (USB2_LINK_MGR_CTRL_REG4)—Offset 80FCh" on page 2307	00008003h
8100–8103h	4	"Bandwidth Calc Control (HOST_CTRL_BW_CTRL_REG)—Offset 8100h" on page 2308	00008008h
8108–810Bh	4	"Host Interface Control (HOST_IF_CTRL_REG)—Offset 8108h" on page 2309	00000001h
810C–810Fh	4	"Bandwidth Overload Burst (HOST_BW_OV_BURST_REG)—Offset 810Ch" on page 2309	00008020h
8128–812Fh	8	"USB Max Bandwidth Control 4 (HOST_CTRL_BW_MAX_REG)—Offset 8128h" on page 2310	0F42528505647F42h
8130–8133h	4	"USB2 Linestate Debug (LINESTATE_DEBUG_REG)—Offset 8130h" on page 2311	00000000h
8134–813Bh	8	"USB2 Protocol Gap Timer (USB2_PROTOCOL_GAP_TIMER_REG)—Offset 8134h" on page 2312	000C3C640C05140Ch
813C–813Fh	4	"USB2 Protocol Bus Timeout Timer (USB2_PROTOCOL_BTO_TIMER_REG)—Offset 813Ch" on page 2313	8D4258B8h
8140–8143h	4	"Power Scheduler Control-0 (PWR_SCHED_CTRL0)—Offset 8140h" on page 2314	0A019132h
8144–8147h	4	"Power Scheduler Control-2 (PWR_SCHED_CTRL2)—Offset 8144h" on page 2314	0000033Fh



Table 213. Summary of USB xHCI Memory Mapped I/O Registers—MBAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
8150–8153h	4	"Latency Tolerance Control 0 (HOST_IF_LAT_TOL_CTRL_REG0)—Offset 8150h" on page 2316	00000000h
8154–8157h	4	"AUX Power Management Control (AUX_CTRL_REG2)—Offset 8154h" on page 2317	01390206h
8164–8167h	4	"USB2 PHY Power Management Control (USB2_PHY_PMC)—Offset 8164h" on page 2320	000000FCh
8168–816Bh	4	"USB Power Gating Control (USB_PGC)—Offset 8168h" on page 2321	00000000h
816C–816Fh	4	"xHCI Aux Clock Control Register (XHCI_AUX_CCR)—Offset 816Ch" on page 2321	00000400h
8170–8173h	4	"USB LPM Parameters (USB_LPM_PARAM)—Offset 8170h" on page 2324	00090032h
8174–8177h	4	"xHC Latency Tolerance Parameters - LTV Control (XLTP_LTV1)—Offset 8174h" on page 2325	0040047Dh
8178–817Bh	4	"xHC Latency Tolerance Parameters LTV Control 2 (XLTP_LTV2)—Offset 8178h" on page 2327	000017FFh
817C–817Fh	4	"xHC Latency Tolerance Parameters - High Idle Time Control (XLTP_HITC)—Offset 817Ch" on page 2327	00000000h
8180–8183h	4	"xHC Latency Tolerance Parameters - Medium Idle Time Control (XLTP_MITC)—Offset 8180h" on page 2328	00000000h
8184–8187h	4	"xHC Latency Tolerance Parameters Low Idle Time Control (XLTP_LITC)—Offset 8184h" on page 2329	00000000h
8344–8347h	4	"USB EP Type Lock Policy (USB_EP_TLP)—Offset 8344h" on page 2330	00000000h
8348–834Bh	4	"USB EP Type Lock Policy - Port Control 1 (USB_EP_TLP1)—Offset 8348h" on page 2333	00000000h
834C–834Fh	4	"USB EP Type Lock Policy - Port Control 2 (USB_EP_TLP2)—Offset 834Ch" on page 2335	00000000h
8460–8463h	4	"USB Legacy Support Capability (USBLEGSUP)—Offset 8460h" on page 2336	00000801h
8464–8467h	4	"USB Legacy Support Control Status (USBLEGCTLSTS)—Offset 8464h" on page 2337	00000000h
8480–8483h	4	"Debug Capability ID Register (DCID)—Offset 8480h" on page 2338	0005000Ah
8484–8487h	4	"Debug Capability Doorbell Register (DCDB)—Offset 8484h" on page 2339	00000000h
8488–848Bh	4	"Debug Capability Event Ring Segment Table Size Register (DCERSTSZ)—Offset 8488h" on page 2340	00000000h
8490–8497h	8	"Debug Capability Event Ring Segment Table Base Address Register (DCERSTBA)—Offset 8490h" on page 2341	0000000000000000h
8498–849Fh	8	"Debug Capability Event Ring Dequeue Pointer Register (DCERDP)—Offset 8498h" on page 2341	0000000000000000h
84A0–84A3h	4	"Debug Capability Control Register (DCCTRL)—Offset 84A0h" on page 2342	00000000h
84A4–84A7h	4	"Debug Capability Status Register (DCST)—Offset 84A4h" on page 2343	00000000h
84A8–84ABh	4	"Debug Capability Port Status and Control Register (DCPORTSC)—Offset 84A8h" on page 2344	00000000h
84B0–84B7h	8	"Debug Capability Context Pointer Register (DCCP)—Offset 84B0h" on page 2346	0000000000000000h



Table 213. Summary of USB xHCI Memory Mapped I/O Registers—MBAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
84B8–84BBh	4	"Debug Capability Device Descriptor Info Register 1 (DCDDI1)—Offset 84B8h" on page 2347	00000000h
84BC–84BFh	4	"Debug Capability Device Descriptor Info Register 2 (DCDDI2)—Offset 84BCh" on page 2348	00000000h
8530–8533h	4	"Debug Capability Descriptor Parameters (DCDP)—Offset 8530h" on page 2348	00000000h
8538–853Bh	4	"Debug Device Control ODMA (DBGDEV_CTRL_ODMA_REG)—Offset 8538h" on page 2349	00000000h

18.7.1 Capability Registers Length (CAPLENGTH)—Offset 0h

This register is used as an offset to add to register base, to find the beginning of the Operational Register Space. This register is modified and maintained by BIOS.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

Offset: [MBAR] + 0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 80h

7	4	0
1	0	0
CAPLENGTH		

Bit Range	Default & Access	Field Name (ID): Description
7:0	80h RW/L	Capability Registers Length (CAPLENGTH): This field is used as an offset to add to register base, to find the beginning of the Operational Register Space. Power Well: Core

18.7.2 Host Controller Interface Version Number (HCIVERSION)—Offset 2h

This is a two-byte register containing a BCD encoding of the xHCI specification revision number supported by this host controller. The most significant byte of this register represents a major revision, and the least significant bit is the minor revision, e.g. 0100h corresponds to xHCI version 1.0. This register is modified and maintained by BIOS.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Offset: [MBAR] + 2h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



Default: 0100h

15	12	8	4	0
0	0	0	0	0
0	0	0	1	0
0	0	0	0	0
0	0	0	0	0
HCVERSION				

Bit Range	Default & Access	Field Name (ID): Description
15:0	0100h RO	Host Controller Interface Version Number (HCVERSION): This is a two-byte field containing a BCD encoding of the xHCI specification revision number supported by this host controller. The most significant byte of this field represents a major revision, and the least significant bit is the minor revision, e.g. 0100h corresponds to xHCI version 1.0. Power Well: Core

18.7.3 Structural Parameters 1 (HCSPARAMS1)—Offset 4h

This register defines basic structural parameters supported by this xHC implementation: Number of Device Slots support, Interrupters, Root Hub ports, etc. This register is modified and maintained by BIOS.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 07000820h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	1	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MaxPorts				Rsvd1		MaxIntrs		MaxSlots

Bit Range	Default & Access	Field Name (ID): Description
31:24	07h RO	Number of Ports (MaxPorts): This field specifies the maximum Port Number value, i.e the highest number of Port Register Sets that are addressable in the Operational Register Space (refer to the xHCI for USB specification). Valid values are in the range of 1h to FFh. The value in this field shall reflect the maximum Port Number value assigned by an <i>xHCI Supported Protocol Capability</i> , described in the xHCI for USB specification. Software shall refer to these capabilities to identify whether a specific Port Number is valid, and the protocol supported by the associated Port Register Set. Power Well: Core
23:19	00h RW/L	Rsvd1: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
25:8	00000h RW/L	Rsvd1: Reserved. Power Well: Core
7:4	5h RW/L	Event Ring Segment Table Max (ERSTMax): Valid values are 0-15. This field determines the maximum value supported by the <i>Event Ring Segment Table Base Size</i> registers (5.5.2.3.1), where The maximum number of Event Ring Segment Table entries = $2^{(ERST\ Max)}$ e.g. if the ERST Max = 7, then the xHC <i>Event Ring Segment Table(s)</i> supports up to 128 entries, if ERST Max = 15, then 32K entries, etc. Power Well: Core
3:0	4h RW/L	Isochronous Scheduling Threshold (IST): The value in this field indicates to system software the minimum distance (in time) that it is required to stay ahead of the host controller while adding TRBs, in order to have the host controller process them at the correct time. The value shall be specified in terms of number of frames/microframes. If bit [3] of IST is cleared to '0', software can add a TRB no later than IST[2:0] microframes before that TRB is scheduled to be executed. If bit [3] of IST is set to '1', software can add a TRB no later than IST[2:0] frames before that TRB is scheduled to be executed. Refer to the xHCI for USB specification for details on how software uses this information for scheduling isochronous transfers. Power Well: Core

18.7.5 Structural Parameters 3 (HCSPARAMS3)—Offset Ch

This register defines link exit latency related structural parameters. This register is modified and maintained by BIOS.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00040001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
U2DEL				Rsvd1				U1DEL

Bit Range	Default & Access	Field Name (ID): Description
31:16	0004h RW/L	U2 Device Exit Latency (U2DEL): Worst case latency to transition from U2 to U0. Applies to all root hub ports. The following are permissible values: 0000h = Zero 0001h = Less than 1 s 0002h = Less than 2 s 07FFh = Less than 2047 s. 0800-FFFFh = Reserved Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
15:8	00h RW/L	Rsvd1: Reserved. Power Well: Core
7:0	01h RW/L	U1 Device Exit Latency (U1DEL): Worst case latency to transition a root hub Port Link State (PLS) from U1 to U0. Applies to all root hub ports. The following are permissible values: 01h = Less than 1 s 02h = Less than 2 s ... 0Ah = Less than 10 s 0B-FFh = Reserved Power Well: Core

18.7.6 Capability Parameters (HCCPARAMS)—Offset 10h

The default values for all fields in this register are implementation dependent. This register defines optional capabilities supported by the xHCI. This register is modified and maintained by BIOS.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 10h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h


Default: 200071E1h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
xECP				MaxPSASize		Rsvd1	PAE	NSS
							LTC	LHRC
							PIND	PPC
								CSZ
								BNC
								AC64

Bit Range	Default & Access	Field Name (ID): Description
31:16	2000h RW/L	xHCI Extended Capabilities Pointer (xECP): This field indicates the existence of a capabilities list. The value of this field indicates a relative offset, in 32-bit words, from Base to the beginning of the first extended capability. For example, using the offset of Base is 1000h and the xECP value of 0068h, we can calculate the following effective address of the first extended capability: 1000h + (0068h ((2) -) 1000h + 01A0h -) 11A0h a. This is not tightly coupled with the USBBASE address register mapping control. Power Well: Core
15:12	7h RW/L	Maximum Primary Stream Array Size (MaxPSASize): This field identifies the maximum size Primary Stream Array that the xHC supports. The Primary Stream Array size = 2^(MaxPSASize+1). Valid MaxPSASize values are 0 to 15, where 0 indicates that Streams are not supported. Power Well: Core
11:9	0h RW/L	Rsvd1: Reserved. Power Well: Core




Bit Range	Default & Access	Field Name (ID): Description
8	1b RW/L	Parse All Event Data (PAE): This flag indicates whether the host controller implementation parses all Event Data TRBs while advancing to the next TD after a Short Packet, or skips all but the first Event Data TRB. A 1 in this bit indicates that all Event Data TRBs are parsed. A 0 in this bit indicates that only the first Event Data TRB is parsed. Refer to the xHCI for USB specification. Power Well: Core
7	1b RW/L	No Secondary SID Support (NSS): This flag indicates whether the host controller implementation supports Secondary Stream IDs. A 1 in this bit indicates that Secondary Stream ID decoding is not supported. A 0 in this bit indicates that Secondary Stream ID decoding is supported. Refer to the xHCI for USB specification. Power Well: Core
6	1b RW/L	Latency Tolerance Messaging Capability (LTC): This flag indicates whether the host controller implementation supports Latency Tolerance Messaging (LTM). A 1 in this bit indicates that LTM is supported. A 0 in this bit indicates that LTM is not supported. Refer to the xHCI for USB specification. Power Well: Core
5	1b RW/L	Light HC Reset Capability (LHRC): This flag indicates whether the host controller implementation supports a Light Host Controller Reset. A 1 in this bit indicates that Light Host Controller Reset is supported. A 0 in this bit indicates that Light Host Controller Reset is not supported. The value of this flag affects the functionality of the <i>Light Host Controller Reset</i> (LHCRST) flag in the USB_CMD register. Refer to the xHCI for USB specification. Power Well: Core
4	0b RW/L	Port Indicators (PIND): This bit indicates whether the xHC root hub ports support port indicator control. When this bit is a 1, the port status and control registers include a read/ writeable field for controlling the state of the port indicator. Refer to the xHCI for USB specification for the definition of the <i>Port Indicator Control</i> field. Power Well: Core
3	0b RO	Port Power Control (PPC): This flag indicates whether the host controller implementation includes port power control. A 1 in this bit indicates the ports have port power switches. A 0 in this bit indicates the port does not have port power switches. The value of this flag affects the functionality of the PP flag in each port status and control register. See the xHCI for USB specification. Power Well: Core
2	0b RW/L	Context Size (CSZ): If this bit is set to 1, then the xHC uses 64 byte Context data structures. If this bit is cleared to 0, then the xHC uses 32 byte Context data structures. Note: This flag does <i>not</i> apply to Stream Contexts. Power Well: Core
1	0b RW/L	BW Negotiation Capability (BNC): This flag identifies whether the xHC has implemented the Bandwidth Negotiation. Values for this flag have the following interpretation: 0 = BW Negotiation not implemented 1 = BW Negotiation implemented Refer to the xHCI for USB specification for more information on Bandwidth Negotiation. Power Well: Core



18.7.9 USB Command (USBCMD)—Offset 80h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Rsvd2																EU3S	EWE	CRS	CSS	LHCRST	Rsvd1				HSEE	INTE	HCRST	RS							

Intel Atom® Processor E3800 Product Family
Datasheet
2183



Bit Range	Default & Access	Field Name (ID): Description
9	0b RW	Controller Restore State (CRS): When set to 1, and HCHalted (HCH) = 1, then the xHC shall perform a Restore State operation and restore its internal state. When set to 1 and <i>Run/Stop</i> (R/S) = 1 or <i>HCHalted</i> (HCH) = 0, or when cleared to 0, no Restore State operation shall be performed. This flag always returns 0 when read. Refer to the <i>Restore State Status</i> (RSS) flag in the USBSTS register for information on Restore State completion. Refer to the xHCI for USB specification, for more information. Note that undefined behavior may occur if a Restore State operation is initiated while <i>Save State Status</i> (SSS) = 1. When this register is exposed by a Virtual Function (VF), this bit only controls restoring the state of the xHC instance presented by the selected VF. Refer to the xHCI for USB specification for more information. Power Well: Core
8	0b RW	Controller Save State (CSS): When written by software with 1 and HCHalted (HCH) = 1, then the xHC shall save any internal state that may be restored by a subsequent Restore State operation. When written by software with 1 and HCHalted (HCH) = 0, or written with 0, no Save State operation shall be performed. This flag always returns 0 when read. Refer to the <i>Save State Status</i> (SSS) flag in the USBSTS register for information on Save State completion. Refer to the xHCI for USB specification for more information on xHC Save/Restore operation. Note that undefined behavior may occur if a Save State operation is initiated while <i>Restore State Status</i> (RSS) = 1. When this register is exposed by a Virtual Function (VF), this bit only controls saving the state of the xHC instance presented by the selected VF. Refer to the xHCI for USB specification for more information. Power Well: Core
7	0b RW	Light Host Controller Reset (LHCRST): Optional normative. If the <i>Light HC Reset Capability</i> (LHRC) bit in the HCCPARAMS register is 1, then this flag allows the driver to reset the xHC without affecting the state of the ports. A system software read of this bit as 0 indicates the <i>Light Host Controller Reset</i> has completed and it is safe for software to re-initialize the xHC. A software read of this bit as a 1 indicates the <i>Light Host Controller Reset</i> has not yet completed. If not implemented, a read of this flag shall always return a 0. All registers in the Aux Power well shall maintain the values that had been asserted prior to the Light Host Controller Reset. (Refer to the xHCI for USB specification for more information.) When this register is exposed by a Virtual Function (VF), this bit only generates a Light Reset to the xHC instance presented by the selected VF, e.g. disabling the VF's device slots and setting the associated VF Run bit to Stopped. Refer to the xHCI for USB specification for more information. Power Well: Core
6:4	0h RO	Rsvd1: Reserved. Power Well: Core
3	0b RW	Host System Error Enable (HSEE): When this bit is a 1, and the HSE bit in the USBSTS register is a 1, the xHC shall assert out-of-band error signaling to the host. The signaling is acknowledged by software clearing the HSE bit. Refer to the xHCI for USB specification for more information. When this register is exposed by a Virtual Function (VF), the effect of the assertion of this bit on the Physical Function (PF0) is determined by the VMM. Refer to the xHCI for USB specification for more information. Power Well: Core




Bit Range	Default & Access	Field Name (ID): Description
2	0b RW	Interrupter Enable (INTE): This bit provides system software with a means of enabling or disabling the host system interrupts generated by Interrupters. When this bit is a 1, then Interrupter host system interrupt generation is allowed, i.e. the xHC shall issue an interrupt at the next interrupt threshold if the host system interrupt mechanism (e.g. MSI, MSIX, etc.) is enabled. The interrupt is acknowledged by a host system interrupt specific mechanism. When this register is exposed by a Virtual Function (VF), this bit only enables the set of Interrupters assigned to the selected VF. Power Well: Core
1	0b RW	Host Controller Reset (HCRST): This control bit is used by software to reset the host controller. The effects of this bit on the xHC and the Root Hub registers are similar to a Chip Hardware Reset. When software writes a 1 to this bit, the Host Controller resets its internal pipelines, timers, counters, state machines, etc. to their initial value. Any transaction currently in progress on the USB is immediately terminated. A USB reset shall not be driven on USB2 downstream ports, however a Hot or Warm Reset shall be initiated on USB3 Root Hub downstream ports. PCI Configuration registers are not affected by this reset. All operational registers, including port registers and port state machines are set to their initial values. Software shall reinitialize the host controller, as described in the xHCI for USB specification, in order to return the host controller to an operational state. This bit is cleared to 0 by the Host Controller when the reset process is complete. Software cannot terminate the reset process early by writing a 0 to this bit and shall not write any xHC Operational or Runtime registers until while HCRST is 1. Note, the completion of the xHC reset process is not gated by the Root Hub port reset process. Software shall not set this bit to 1 when the HCHalted (HCH) bit in the USBSTS register is a 0. Attempting to reset an actively running host controller may result in undefined behavior. When this register is exposed by a Virtual Function (VF), this bit only resets the xHC instance presented by the selected VF. Refer to the xHCI for USB specification for more information. Power Well: Core
0	0b RW	Run/Stop (RS): 1 = Run 0 = Stop When set to a 1, the xHC proceeds with execution of the schedule. The xHC continues execution as long as this bit is set to a 1. When this bit is cleared to 0, the xHC completes any current or queued commands or TDs, and any USB transactions associated with them, then halts. Refer to section 5.4.1.1 for more information on how R/S shall be managed. The xHC shall halt within 16 ms. after software clears the Run/Stop bit if the above conditions have been met. The HCHalted (HCH) bit in the USBSTS register indicates when the xHC has finished its pending pipelined transactions and has entered the stopped state. Software shall not write a 1 to this flag unless the xHC is in the Halted state (i.e. HCH in the USBSTS register is 1). Doing so may yield undefined results. Writing a 0 to this flag when the xHC is in the Running state (i.e. HCH = 0) and any Event Rings are in the Event Ring Full state (refer to section 4.9.4) may yield undefined results. When this register is exposed by a Virtual Function (VF), this bit only controls the run state of the xHC instance presented by the selected VF. Power Well: Core

18.7.10 USB Status (USBSTS)—Offset 84h

This register indicates pending interrupts and various states of the Host Controller. The status resulting from a transaction on the serial bus is not indicated in this register. Software sets a bit to '0' in this register by writing a '1' to it (RW1C). Refer to specification *eXtensible Host Controller Interface for Universal Serial Bus (xHCI)* for additional information concerning USB interrupt conditions.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 84h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000001h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1				
Rsvd3												HCE	CNR	SRE	RSS	SSS	Rsvd2				PCD	EINT	HSE	Rsvd1	HCH										

Bit Range	Default & Access	Field Name (ID): Description
31:13	00000h RO	Rsvd3: Reserved. Power Well: Core
12	0b RO	Host Controller Error (HCE): This bit is not preset in HC, this is deviation from xHCI 1.0 spec. Power Well: Core
11	0b RO	Controller Not Ready (CNR): This is deviation from xHCI 1.0 spec. Power Well: Core
10	0b RW/C	Save/Restore Error (SRE): If an error occurs during a Save or Restore operation, this bit shall be set to 1. This bit shall be cleared to 0 when a Save or Restore operation is initiated or when written with 1. Refer to the xHCI for USB specification for more information. When this register is exposed by a Virtual Function (VF), the VMM determines the state of this bit as a function of the Save/Restore completion status for the selected VF. Refer to the xHCI for USB specification for more information. Power Well: Core
9	0b RO	Restore State Status (RSS): When the Controller Restore State (CRS) flag in the USBCMD register is written with 1 this bit shall be set to 1 and remain 1 while the xHC restores its internal state. When the Restore State operation is complete, this bit shall be cleared to 0. Refer to the xHCI for USB specification for more information. When this register is exposed by a Virtual Function (VF), the VMM determines the state of this bit as a function of the restoring the state for the selected VF. Refer to the xHCI for USB specification for more information. Power Well: Core
8	0b RO	Save State Status (SSS): When the <i>Controller Save State</i> (CSS) flag in the USBCMD register is written with 1, this bit shall be set to 1 and remain 1 while the xHC saves its internal state. When the Save State operation is complete, this bit shall be cleared to 0. Refer to the xHCI for USB specification for more information. When this register is exposed by a Virtual Function (VF), the VMM determines the state of this bit as a function of the saving the state for the selected VF. Refer to the xHCI for USB specification for more information. Power Well: Core
7:5	0h RO	Rsvd2: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW/C	Port Change Detect (PCD): The xHC sets this bit to a 1 when any port has a change bit transition from a 0 to a 1. This bit is allowed to be maintained in the Aux Power well. Alternatively, it is also acceptable that on a D3 to D0 transition of the xHC, this bit is loaded with the OR of all of the PORTSC change bits. Refer to the xHCI for USB specification for more information. This bit provides system software an efficient means of determining if there has been Root Hub port activity. Refer to the xHCI for USB specification for more information. When this register is exposed by a Virtual Function (VF), the VMM determines the state of this bit as a function of the Root Hub Ports associated with the Device Slots assigned to the selected VF. Refer to the xHCI for USB specification for more information. Power Well: Core
3	0b RW/C	Event Interrupt (EINT): The xHC sets this bit to 1 when the <i>Interrupt Pending</i> (IP) bit of any Interrupter transitions from 0 to 1. Refer to the xHCI for USB specification for usage information. Software that uses <i>EINT</i> shall clear it prior to clearing any IP flags. A race condition may occur if software clears the <i>IP</i> flags, then clears the <i>EINT</i> flag, and between the operations another <i>IP</i> 0 to '1' transition occurs. In this case, the new IP transition shall be lost. When this register is exposed by a Virtual Function (VF), this bit is the logical 'OR' of the IP bits for the Interrupters assigned to the selected VF. And it shall be cleared to 0 when all associated interrupter IP bits are cleared, i.e. all the VFs Interrupter Event Ring(s) are empty. Refer to the xHCI for USB specification for more information. Power Well: Core
2	0b RW/C	Host System Error (HSE): The xHC sets this bit to 1 when a serious error is detected, either internal to the xHC or during a host system access involving the xHC module. (In a PCI system, conditions that set this bit to 1 include PCI Parity error, PCI Master Abort, and PCI Target Abort.) When this error occurs, the xHC clears the Run/Stop (R/S) bit in the USBCMD register to prevent further execution of the scheduled TDs. If the HSEE bit in the USBCMD register is a 1, the xHC shall also assert out-of-band error signaling to the host. Refer to the xHCI for USB specification for more information. When this register is exposed by a Virtual Function (VF), the assertion of this bit affects all VFs and reflects the Host System Error state of the Physical Function (PF0). Refer to the xHCI for USB specification for more information. Power Well: Core
1	0b RO	Rsvd1: Reserved. Power Well: Core
0	1b RO	HCHalted (HCH): This bit is a 0 whenever the <i>Run/Stop</i> (R/S) bit is a 1. The xHC sets this bit to 1 after it has stopped executing as a result of the <i>Run/Stop</i> (R/S) bit being cleared to 0, either by software or by the xHC hardware (e.g. internal error). If this bit is '1', then SOFs, microSOFs, or Isochronous Timestamp Packets (ITP) shall not be generated by the xHC, and any received Transaction Packet shall be dropped. When this register is exposed by a Virtual Function (VF), this bit only reflects the Halted state of the xHC instance presented by the selected VF. Refer to the xHCI for USB specification for more information. Power Well: Core

18.7.11 Page Size (PAGESIZE)—Offset 88h

The default value for this register is implementation dependent.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 88h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Rsvd1				PAGESIZE				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core
15:0	0001h RO	Page Size (PAGESIZE): This field defines the page size supported by the xHC implementation. This xHC supports a page size of $2^{(n+12)}$ if bit n is Set. For example, if bit 0 is Set, the xHC supports 4k byte page sizes. For a Virtual Function, this register reflects the page size selected in the <i>System Page Size</i> field of the SR-IOV Extended Capability structure. For the Physical Function 0, this register reflects the implementation dependent default xHC page size. Various xHC resources reference PAGESIZE to describe their minimum alignment requirements. The maximum possible page size is 128M. Power Well: Core

18.7.12 Device Notification Control (DNCTRL)—Offset 94h

This register is used by software to enable or disable the reporting of the reception of specific USB Device Notification Transaction Packets. A *Notification Enable* (Nx, where x = 0 to 15) flag is defined for each of the 16 possible device notification types. If a flag is set for a specific notification type, a Device Notification Event shall be generated when the respective notification packet is received. After reset, all notifications are disabled. Refer to specification *eXtensible Host Controller Interface for Universal Serial Bus (xHCI)*. This register shall be written as a Dword. Byte writes produce undefined results.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 94h


MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd1				NO_N15				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
2	0b RW/S	Command Abort (CA): Writing a '1' to this bit shall immediately terminate the currently executing command, stop the Command Ring, and generate a Command Completion Event with the Completion Code set to Command Ring Stopped. Refer to the xHCI for USB specification for more information on aborting a command. The next write to the <i>Host Controller Doorbell</i> with <i>DB Reason</i> field set to <i>Host Controller Command</i> shall restart the Command Ring operation. Writes to this flag are ignored by the xHC if <i>Command Ring Running</i> (CCR) = '0'. Reading this bit always returns '0'. Power Well: Core
1	0b RW/S	Command Stop (CS): Writing a '1' to this bit shall stop the operation of the Command Ring after the completion of the currently executing command, and generate a <i>Command Completion Event</i> with the <i>Completion Code</i> set to <i>Command Ring Stopped</i> and the <i>Command TRB Pointer</i> set to the current value of the <i>Command Ring Dequeue Pointer</i>. Refer to the xHCI for USB specification for more information on stopping a command. The next write to the <i>Host Controller Doorbell</i> with <i>DB Reason</i> field set to <i>Host Controller Command</i> shall restart the Command Ring operation. Writes to this flag are ignored by the xHC if <i>Command Ring Running</i> (CCR) = '0'. Reading this bit shall always return '0'. Power Well: Core
0	0b RW	Ring Cycle State (RCS): This bit identifies the value of the xHC <i>Consumer Cycle State</i> (CCS) flag for the TRB referenced by the <i>Command Ring Pointer</i>. Refer to the xHCI for USB specification for more information. Writes to this flag are ignored if <i>Command Ring Running</i> is '1'. If the CRCR is written while the Command Ring is stopped (CCR = '0'), then the value of this flag shall be used to fetch the first Command TRB the next time the <i>Host Controller Doorbell</i> register is written with the <i>DB Reason</i> field set to <i>Host Controller Command</i>. If the CRCR is <i>not</i> written while the Command Ring is stopped (CCR = '0'), then the Command Ring shall begin fetching Command TRBs using the current value of the <i>Internal Command Ring CCS</i> flag. Reading this flag always returns '0'. Power Well: Core

18.7.14 Command Ring High (CRCR_HI)—Offset 9Ch

The Command Ring Control Register provides Command Ring control and status capabilities, and identifies the address and Cycle bit state of the Command Ring Dequeue Pointer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 9Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

CRP



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Command Ring Pointer (CRP): This field defines high order bits of the initial value of the 64-bit Command Ring Dequeue Pointer. Writes to this field are ignored when <i>Command Ring Running</i> (CCR) = '1'. If the CRCR is written while the Command Ring is stopped (CCR = '0'), the value of this field shall be used to fetch the first Command TRB the next time the <i>Host Controller Doorbell</i> register is written with the DB Reason field set to Host Controller Command. If the CRCR is <i>not</i> written while the Command Ring is stopped (CRR = '0') then the Command Ring shall begin fetching Command TRBs at the current value of the internal xHC Command Ring Dequeue Pointer. Reading this field always returns '0'. Power Well: Core

18.7.15 Device Context Base Address Array Pointer Low (DCBAAP_LO)—Offset B0h

The Device Context Base Address Array Pointer Register identifies the base address of the Device Context Base Address Array. The memory structure referenced by this physical memory pointer is assumed to be physically contiguous and 64-byte aligned.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + B0h**MBAR Type:** PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
OCBAAP							Rsvd1	

Bit Range	Default & Access	Field Name (ID): Description
31:6	0000000h RW	Device Context Base Address Array Pointer (DCBAAP): This field defines low order bits of the 64-bit base address of the Device Context Pointer Array, which is a table of address pointers that reference Device Context structures for the devices attached to the host. Power Well: Core
5:0	00h RO	Rsvd1: Reserved. Power Well: Core

18.7.16 Device Context Base Address Array Pointer High (DCBAAP_HI)—Offset B4h

The Device Context Base Address Array Pointer Register identifies the base address of the Device Context Base Address Array. The memory structure referenced by this physical memory pointer is assumed to be physically contiguous and 64-byte aligned.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + B4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Device Context Base Address Array Pointer (DCBAAP): This field defines high order bits of the 64-bit base address of the Device Context Pointer Array, which is a table of address pointers that reference Device Context structures for the devices attached to the host. Power Well: Core

18.7.17 Configure (CONFIG)—Offset B8h

This register defines runtime xHC configuration parameters.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + B8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd1							MaxSlotsEn	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	Max Device Slots Enabled (MaxSlotsEn): This field specifies the maximum number of enabled Device Slots. Valid values are in the range of 0 to MaxSlots. Enabled Devices Slots are allocated contiguously, e.g. a value of 16 specifies that Device Slots 1 to 16 are active. A value of '0' disables all Device Slots. A disabled Device Slot shall not respond to Doorbell Register references. This field shall not be modified by software if the xHC is running (Run/Stop (R/S) = '1'). Power Well: Core



18.7.18 Port 1 Status and Control USB3 (PORTSC1USB2)—Offset 480h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 480h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 000002A0h

31				28				24				20				16				12				8				4				0																																																															
0				0				0				0				0				0				0				1				0				1				0				0				0																																															
WPR				DR				Rsvd2				WOE				WDE				WCE				CAS				CEC				PLC				PRC				OCC				WRC				PEC				CSC				LWS				PIC				Port_Speed				PP				PLS				PR				OCA				Rsvd1				PED				CCS			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/S	Warm Port Reset (WPR): Reserved. Power Well: SUS
30	0b RO	Device Removable (DR): Reserved. Power Well: Core
29:28	0h RO	Rsvd2: Reserved. Power Well: Core
27	0b RW	Wake on Over-current Enable (WOE): Note: This register is sticky. Power Well: SUS
26	0b RW	Wake on Disconnect Enable (WDE): Note: This register is sticky. Power Well: SUS
25	0b RW	Wake on Connect Enable (WCE): Note: This register is sticky. Power Well: SUS
24	0b RO	Cold Attach Status (CAS): Reserved. Power Well: SUS
23	0b RW/C	Port Config Error Change (CEC): Note: This register is sticky. Power Well: SUS
22	0b RW/C	Port Link State Change (PLC): Note: This register is sticky. Power Well: SUS
21	0b RW/C	Port Reset Change (PRC): Note: This register is sticky. Power Well: SUS
20	0b RW/C	Over-current Change (OCC): Note: This register is sticky. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
19	0b RW/C	Warm Port Reset Change (WRC): Note: This register is sticky. Power Well: SUS
18	0b RW/C	Port Enabled Disabled Change (PEC): Note: This register is sticky. Power Well: SUS
17	0b RW/C	Connect Status Change (CSC): Note: This register is sticky. Power Well: SUS
16	0b RW	Port Link State Write Strobe (LWS): Reserved. Power Well: SUS
15:14	0h RW	Port Indicator Control (PIC): Note: This register is sticky. Power Well: SUS
13:10	0h RW	Port Speed (Port_Speed): Note: This register is sticky. Power Well: SUS
9	1b RW	Port Power (PP): Note: This register is sticky. Power Well: SUS
8:5	5h RW	Port Link State (PLS): Note: This register is sticky. Power Well: SUS
4	0b RW/S	Port Reset (PR): Reserved. Power Well: SUS
3	0b RW	Over-current Active (OCA): Note: This register is sticky. Power Well: SUS
2	0b RO	Rsvd1: Reserved. Power Well: Core
1	0b RW/C	Port Enabled Disabled (PED): Note: This register is sticky. Power Well: SUS
0	0b RW	Current Connect Status (CCS): Note: This register is sticky. Power Well: SUS

18.7.19 Port 1 Power Management Status and Control USB2 (PORTPMSC1USB2)—Offset 484h

This register is in the Aux Power well. It is only reset by platform hardware during a cold reset or in response to a *Host Controller Reset* (HCRST). The USB2 Port Power Management Status and Control register provides the USB2 LPM parameters necessary for the xHC to generate a LPM Token to the downstream device.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 484h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
PTC				Rsvd1												HLE		L1DS				HIRD				RWE		L1S							

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	Port Test Control (PTC): Note: This register is sticky. Power Well: SUS
27:17	000h RO	Rsvd1: Reserved. Power Well: Core
16	0b RO	Hardware LPM Enable (HLE): Reserved. Power Well: SUS
15:8	00h RW	L1 Device Slot (L1DS): Note: This register is sticky. System software sets this field to indicate the ID of the Device Slot associated with the device directly attached to the Root Hub port. A value of 0 indicates no device is present. The xHC uses this field to lookup information necessary to generate the LPM Token packet. Power Well: SUS
7:4	0h RW	Best Effort Service Latency (HIRD): Note: This register is sticky. System software sets this field to indicate to the recipient device how long the xHC will drive resume if it (the xHC) initiates an exit from L1. For more information about <i>BESL</i> value encoding, refer to the xHCI for USB specification. Note that the <i>BESL</i> field is used by both software and hardware controlled LPM. Refer to the xHCI for USB specification for more information on <i>BESL</i> use and how <i>DBESL</i> may be used to establish an initial value for <i>BESL</i> . Power Well: SUS
3	0b RW	Remote Wake Enable (RWE): Note: This register is sticky. System software sets this flag to enable or disable the device for remote wake from L1. The value of this flag shall temporarily (while in L1) override the current setting of the Remote Wake feature set by the standard Set/ClearFeature() commands defined in Universal Serial Bus Specification, revision 2.0, Chapter 9. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
9:2	00h RW	L1 Timeout (L1TO): Timeout value for L1 inactivity timer. This field shall be set to 00h by assertion of PR to '1'. Following are permissible values: 00h: 128 us (default) 01h: 256 us. ... FFh: 65,280us Note: This register is sticky. Power Well: SUS
1:0	0h RW	Host Initiated Resume Duration Mode (HIRDM): Indicates which HIRD value should be used. The following are permissible values: 0 = Initiate L1 using HIRD only time out (default) 1 = Initiate HIRDDon timeout. If rejected by device, initiate L1 using HIRD 2,3 = Reserved Note: This register is sticky. Power Well: SUS

18.7.21 Port 2 Status and Control USB3 (PORTSC2USB2)—Offset 490h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 490h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 000002A0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
WPR	DR	Rsvd2	WOE	WDE	WCE	CAS	CEC	PLC
			PRC	OCC	WRC	PEC	CSC	LWS
						PIC	Port_Speed	PP
							PLS	PR
								OCA
								Rsvd1
								PED
								CCS

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/S	Warm Port Reset (WPR): Reserved. Power Well: SUS
30	0b RO	Device Removable (DR): Reserved. Power Well: Core
29:28	0h RO	Rsvd2: Reserved. Power Well: Core
27	0b RW	Wake on Over-current Enable (WOE): Note: This register is sticky. Power Well: SUS
26	0b RW	Wake on Disconnect Enable (WDE): Note: This register is sticky. Power Well: SUS
25	0b RW	Wake on Connect Enable (WCE): Note: This register is sticky. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
24	0b RO	Cold Attach Status (CAS): Reserved. Power Well: SUS
23	0b RW/C	Port Config Error Change (CEC): Note: This register is sticky. Power Well: SUS
22	0b RW/C	Port Link State Change (PLC): Note: This register is sticky. Power Well: SUS
21	0b RW/C	Port Reset Change (PRC): Note: This register is sticky. Power Well: SUS
20	0b RW/C	Over-current Change (OCC): Note: This register is sticky. Power Well: SUS
19	0b RW/C	Warm Port Reset Change (WRC): Note: This register is sticky. Power Well: SUS
18	0b RW/C	Port Enabled Disabled Change (PEC): Note: This register is sticky. Power Well: SUS
17	0b RW/C	Connect Status Change (CSC): Note: This register is sticky. Power Well: SUS
16	0b RW	Port Link State Write Strobe (LWS): Reserved. Power Well: SUS
15:14	0h RW	Port Indicator Control (PIC): Note: This register is sticky. Power Well: SUS
13:10	0h RW	Port Speed (Port_Speed): Note: This register is sticky. Power Well: SUS
9	1b RW	Port Power (PP): Note: This register is sticky. Power Well: SUS
8:5	5h RW	Port Link State (PLS): Note: This register is sticky. Power Well: SUS
4	0b RW/S	Port Reset (PR): Reserved. Power Well: SUS
3	0b RW	Over-current Active (OCA): Note: This register is sticky. Power Well: SUS
2	0b RO	Rsvd1: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW/C	Port Enabled Disabled (PED): Note: This register is sticky. Power Well: SUS
0	0b RW	Current Connect Status (CCS): Note: This register is sticky. Power Well: SUS

18.7.22 Port 2 Power Management Status and Control USB2 (PORTPMSC2USB2)—Offset 494h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 494h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PTC	Rsvd1				HLE	L1DS	HIRD	RWE
								L1S

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	Port Test Control (PTC): Note: This register is sticky. Power Well: SUS
27:17	000h RO	Rsvd1: Reserved. Power Well: Core
16	0b RO	Hardware LPM Enable (HLE): Reserved. Power Well: SUS
15:8	00h RW	L1 Device Slot (L1DS): Note: This register is sticky. Power Well: SUS
7:4	0h RW	Host Initiated Resume Duration (HIRD): Note: This register is sticky. Power Well: SUS
3	0b RW	Remote Wake Enable (RWE): Note: This register is sticky. Power Well: SUS
2:0	0h RW	L1 Status (L1S): Note: This register is sticky. Power Well: SUS



18.7.23 Port X Hardware LPM Control Register (PORTHLPM2)—Offset 49Ch

There are 9 PORTHLPM registers at offsets 48Ch, 49Ch, 4ACh, 4BCh, 4CCh, 4DCh, 4ECh, 4FCh and 50Ch. This register is reset only by platform hardware during cold reset or in response to a Host Controller Reset (HCRST). The field definitions depend on the protocol supported. For USB3, this register is reserved and shall be treated by software as RsvdP. For USB2, the definition is given below. Fields contain parameters necessary for xHC to automatically generate an LPM Token to the downstream device.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 49Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				HIRDD		L1TO		HIRDM

Bit Range	Default & Access	Field Name (ID): Description
31:14	00000h RO	RESERVED (RSVD): Reserved. Power Well: Core
13:10	0h RW	Host Initiated Resume Duration-Deep (HIRDD): System software sets this field to indicate to the recipient device how long the xHC will drive resume upon exit from L1. The HIRDD value is encoded as follows: 0h = 50 us (default) 1h = 125 us 2h = 200 us ... - Fh = 1.175ms The value of 0h is interpreted as 50 us. Each incrementing value adds 75 us to the previous value. Power Well: SUS
9:2	00h RW	L1 Timeout (L1TO): Timeout value for L1 inactivity timer. This field shall be set to 00h by assertion of PR to '1'. Following are permissible values: 00h: 128 us (default) 01h: 256 us. ... FFh: 65,280us Note: This register is sticky. Power Well: SUS
1:0	0h RW	Host Initiated Resume Duration Mode (HIRDM): Indicates which HIRD value should be used. The following are permissible values: 0 = Initiate L1 using HIRD only time out (default) 1 = Initiate HIRDDon timeout. If rejected by device, initiate L1 using HIRD 2,3 = Reserved Note: This register is sticky. Power Well: SUS

18.7.24 Port 3 Status and Control USB3 (PORTSC3USB2)—Offset 4A0h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4A0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 000002A0h

31				28				24				20				16				12				8				4				0																																																															
0				0				0				0				0				0				0				1				0				1				0				0				0																																															
WPR				DR				Rsvd2				WOE				WDE				WCE				CAS				CEC				PLC				PRC				OCC				WRC				PEC				CSC				LWS				PlC				Port_Speed				PP				PLS				PR				OCA				Rsvd1				PED				CCS			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/S	Warm Port Reset (WPR): Reserved. Power Well: SUS
30	0b RO	Device Removable (DR): Reserved. Power Well: Core
29:28	0h RO	Rsvd2: Reserved. Power Well: Core
27	0b RW	Wake on Over-current Enable (WOE): Note: This register is sticky. Power Well: SUS
26	0b RW	Wake on Disconnect Enable (WDE): Note: This register is sticky. Power Well: SUS
25	0b RW	Wake on Connect Enable (WCE): Note: This register is sticky. Power Well: SUS
24	0b RO	Cold Attach Status (CAS): Reserved. Power Well: SUS
23	0b RW/C	Port Config Error Change (CEC): Note: This register is sticky. Power Well: SUS
22	0b RW/C	Port Link State Change (PLC): Note: This register is sticky. Power Well: SUS
21	0b RW/C	Port Reset Change (PRC): Note: This register is sticky. Power Well: SUS
20	0b RW/C	Over-current Change (OCC): Note: This register is sticky. Power Well: SUS
19	0b RW/C	Warm Port Reset Change (WRC): Note: This register is sticky. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW/C	Port Enabled Disabled Change (PEC): Note: This register is sticky. Power Well: SUS
17	0b RW/C	Connect Status Change (CSC): Note: This register is sticky. Power Well: SUS
16	0b RW	Port Link State Write Strobe (LWS): Reserved. Power Well: SUS
15:14	0h RW	Port Indicator Control (PIC): Note: This register is sticky. Power Well: SUS
13:10	0h RW	Port Speed (Port_Speed): Note: This register is sticky. Power Well: SUS
9	1b RW	Port Power (PP): Note: This register is sticky. Power Well: SUS
8:5	5h RW	Port Link State (PLS): Note: This register is sticky. Power Well: SUS
4	0b RW/S	Port Reset (PR): Reserved. Power Well: SUS
3	0b RW	Over-current Active (OCA): Note: This register is sticky. Power Well: SUS
2	0b RO	Rsvd1: Reserved. Power Well: Core
1	0b RW/C	Port Enabled Disabled (PED): Note: This register is sticky. Power Well: SUS
0	0b RW	Current Connect Status (CCS): Note: This register is sticky. Power Well: SUS

18.7.25 Port 3 Power Management Status and Control USB2 (PORTPMSC3USB2)—Offset 4A4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4A4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PTC	Rsvd1				HLE	LIDS		HIRD
							RWE	L1S

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	Port Test Control (PTC): Note: This register is sticky. Power Well: SUS
27:17	000h RO	Rsvd1: Reserved. Power Well: Core
16	0b RO	Hardware LPM Enable (HLE): Reserved. Power Well: SUS
15:8	00h RW	L1 Device Slot (LIDS): Note: This register is sticky. Power Well: SUS
7:4	0h RW	Host Initiated Resume Duration (HIRD): Note: This register is sticky. Power Well: SUS
3	0b RW	Remote Wake Enable (RWE): Note: This register is sticky. Power Well: SUS
2:0	0h RW	L1 Status (L1S): Note: This register is sticky. Power Well: SUS

18.7.26 Port X Hardware LPM Control Register (PORTHLPM3)—Offset 4ACh

There are 9 PORTHLPM registers at offsets 48Ch, 49Ch, 4ACh, 4BCh, 4CCh, 4DCh, 4ECh, 4FCh and 50Ch. This register is reset only by platform hardware during cold reset or in response to a Host Controller Reset (HCRST). The field definitions depend on the protocol supported. For USB3, this register is reserved and shall be treated by software as RsvdP. For USB2, the definition is given below. Fields contain parameters necessary for xHC to automatically generate an LPM Token to the downstream device.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4ACh

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				HIRD		L1TO		HIRDM



Bit Range	Default & Access	Field Name (ID): Description
31:14	00000h RO	RESERVED (RSVD): Reserved. Power Well: Core
13:10	0h RW	Host Initiated Resume Duration-Deep (HIRDD): System software sets this field to indicate to the recipient device how long the xHC will drive resume upon exit from L1. The HIRDD value is encoded as follows: 0h = 50 us (default) 1h = 125 us 2h = 200 us ... - Fh = 1.175ms The value of 0h is interpreted as 50 us. Each incrementing value adds 75 us to the previous value. Power Well: SUS
9:2	00h RW	L1 Timeout (L1TO): Timeout value for L1 inactivity timer. This field shall be set to 00h by assertion of PR to '1'. Following are permissible values: 00h: 128 us (default) 01h: 256 us. ... FFh: 65,280us Note: This register is sticky. Power Well: SUS
1:0	0h RW	Host Initiated Resume Duration Mode (HIRDM): Indicates which HIRD value should be used. The following are permissible values: 0 = Initiate L1 using HIRD only time out (default) 1 = Initiate HIRDDon timeout. If rejected by device, initiate L1 using HIRD 2,3 = Reserved Note: This register is sticky. Power Well: SUS

18.7.27 Port 4 Status and Control USB3 (PORTSC4USB2)—Offset 4B0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4B0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 000002A0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
WPR	DR	Rsvd2	WOE	WDE	WCE	CAS	CEC	PLC
			PRC	OCC	WRC	PEC	CSC	LWS
								PTC
								Port_Speed
								PP
								PLS
								PR
								OCA
								Rsvd1
								PED
								CCS

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/S	Warm Port Reset (WPR): Reserved. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
30	0b RO	Device Removable (DR): Reserved. Power Well: Core
29:28	0h RO	Rsvd2: Reserved. Power Well: Core
27	0b RW	Wake on Over-current Enable (WOE): Note: This register is sticky. Power Well: SUS
26	0b RW	Wake on Disconnect Enable (WDE): Note: This register is sticky. Power Well: SUS
25	0b RW	Wake on Connect Enable (WCE): Note: This register is sticky. Power Well: SUS
24	0b RO	Cold Attach Status (CAS): Reserved. Power Well: SUS
23	0b RW/C	Port Config Error Change (CEC): Note: This register is sticky. Power Well: SUS
22	0b RW/C	Port Link State Change (PLC): Note: This register is sticky. Power Well: SUS
21	0b RW/C	Port Reset Change (PRC): Note: This register is sticky. Power Well: SUS
20	0b RW/C	Over-current Change (OCC): Note: This register is sticky. Power Well: SUS
19	0b RW/C	Warm Port Reset Change (WRC): Note: This register is sticky. Power Well: SUS
18	0b RW/C	Port Enabled Disabled Change (PEC): Note: This register is sticky. Power Well: SUS
17	0b RW/C	Connect Status Change (CSC): Note: This register is sticky. Power Well: SUS
16	0b RW	Port Link State Write Strobe (LWS): Reserved. Power Well: SUS
15:14	0h RW	Port Indicator Control (PIC): Note: This register is sticky. Power Well: SUS
13:10	0h RW	Port Speed (Port_Speed): Note: This register is sticky. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
9	1b RW	Port Power (PP): Note: This register is sticky. Power Well: SUS
8:5	5h RW	Port Link State (PLS): Note: This register is sticky. Power Well: SUS
4	0b RW/S	Port Reset (PR): Reserved. Power Well: SUS
3	0b RW	Over-current Active (OCA): Note: This register is sticky. Power Well: SUS
2	0b RO	Rsvd1: Reserved. Power Well: Core
1	0b RW/C	Port Enabled Disabled (PED): Note: This register is sticky. Power Well: SUS
0	0b RW	Current Connect Status (CCS): Note: This register is sticky. Power Well: SUS

18.7.28 Port 4 Power Management Status and Control USB2 (PORTPMSC4USB2)—Offset 4B4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4B4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PTC	Rsvd1				HLE	LIDS	HIRD	RWE L1S

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	Port Test Control (PTC): Note: This register is sticky. Power Well: SUS
27:17	000h RO	Rsvd1: Reserved. Power Well: Core
16	0b RO	Hardware LPM Enable (HLE): Reserved. Power Well: SUS





Bit Range	Default & Access	Field Name (ID): Description
29:28	0h RO	Rsvd2: Reserved. Power Well: Core
27	0b RW	Wake on Over-current Enable (WOE): Note: This register is sticky. Power Well: SUS
26	0b RW	Wake on Disconnect Enable (WDE): Note: This register is sticky. Power Well: SUS
25	0b RW	Wake on Connect Enable (WCE): Note: This register is sticky. Power Well: SUS
24	0b RO	Cold Attach Status (CAS): Reserved. Power Well: SUS
23	0b RW/C	Port Config Error Change (CEC): Note: This register is sticky. Power Well: SUS
22	0b RW/C	Port Link State Change (PLC): Note: This register is sticky. Power Well: SUS
21	0b RW/C	Port Reset Change (PRC): Note: This register is sticky. Power Well: SUS
20	0b RW/C	Over-current Change (OCC): Note: This register is sticky. Power Well: SUS
19	0b RW/C	Warm Port Reset Change (WRC): Note: This register is sticky. Power Well: SUS
18	0b RW/C	Port Enabled Disabled Change (PEC): Note: This register is sticky. Power Well: SUS
17	0b RW/C	Connect Status Change (CSC): Note: This register is sticky. Power Well: SUS
16	0b RW	Port Link State Write Strobe (LWS): Reserved. Power Well: SUS
15:14	0h RW	Port Indicator Control (PIC): Note: This register is sticky. Power Well: SUS
13:10	0h RW	Port Speed (Port_Speed): Note: This register is sticky. Power Well: SUS
9	1b RW	Port Power (PP): Note: This register is sticky. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
8:5	5h RW	Port Link State (PLS): Note: This register is sticky. Power Well: SUS
4	0b RW/S	Port Reset (PR): Reserved. Power Well: SUS
3	0b RW	Over-current Active (OCA): Note: This register is sticky. Power Well: SUS
2	0b RO	Rsvd1: Reserved. Power Well: Core
1	0b RW/C	Port Enabled Disabled (PED): Note: This register is sticky. Power Well: SUS
0	0b RW	Current Connect Status (CCS): Note: This register is sticky. Power Well: SUS

18.7.31 Port 5 Power Management Status and Control USB2 (PORTPMSC5USB2)—Offset 4C4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4C4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PTC	Rsvd1				HLE	L1DS	HIRD	RWE
								L1S

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	Port Test Control (PTC): Note: This register is sticky. Power Well: SUS
27:17	000h RO	Rsvd1: Reserved. Power Well: Core
16	0b RO	Hardware LPM Enable (HLE): Reserved. Power Well: SUS
15:8	00h RW	L1 Device Slot (L1DS): Note: This register is sticky. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
9:2	00h RW	L1 Timeout (L1TO): Timeout value for L1 inactivity timer. This field shall be set to 00h by assertion of PR to '1'. Following are permissible values: 00h: 128 us (default) 01h: 256 us. ... FFh: 65,280us Note: This register is sticky. Power Well: SUS
1:0	0h RW	Host Initiated Resume Duration Mode (HIRDM): Indicates which HIRD value should be used. The following are permissible values: 0 = Initiate L1 using HIRD only time out (default) 1 = Initiate HIRDDon timeout. If rejected by device, initiate L1 using HIRD 2,3 = Reserved Note: This register is sticky. Power Well: SUS

18.7.33 Port 6 Status and Control USB2 (PORTSC6USB2)—Offset 4D0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4D0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 000002A0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
WPR	DR	Rsvd2	WOE	WDE	WCE	CAS	CEC	PLC
			PRC	OCC	WRC	PEC	CSC	LWS
								PIC
								Port_Speed
								PP
								PLS
								PR
								OCA
								Rsvd1
								PED
								CCS

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/S	Warm Port Reset (WPR): Reserved. Power Well: SUS
30	0b RO	Device Removable (DR): Reserved. Power Well: Core
29:28	0h RO	Rsvd2: Reserved. Power Well: Core
27	0b RW	Wake on Over-current Enable (WOE): Note: This register is sticky. Power Well: SUS
26	0b RW	Wake on Disconnect Enable (WDE): Note: This register is sticky. Power Well: SUS
25	0b RW	Wake on Connect Enable (WCE): Note: This register is sticky. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
24	0b RO	Cold Attach Status (CAS): Reserved. Power Well: SUS
23	0b RW/C	Port Config Error Change (CEC): Note: This register is sticky. Power Well: SUS
22	0b RW/C	Port Link State Change (PLC): Note: This register is sticky. Power Well: SUS
21	0b RW/C	Port Reset Change (PRC): Note: This register is sticky. Power Well: SUS
20	0b RW/C	Over-current Change (OCC): Note: This register is sticky. Power Well: SUS
19	0b RW/C	Warm Port Reset Change (WRC): Note: This register is sticky. Power Well: SUS
18	0b RW/C	Port Enabled Disabled Change (PEC): Note: This register is sticky. Power Well: SUS
17	0b RW/C	Connect Status Change (CSC): Note: This register is sticky. Power Well: SUS
16	0b RW	Port Link State Write Strobe (LWS): Reserved. Power Well: SUS
15:14	0h RW	Port Indicator Control (PIC): Note: This register is sticky. Power Well: SUS
13:10	0h RW	Port Speed (Port_Speed): Note: This register is sticky. Power Well: SUS
9	1b RW	Port Power (PP): Note: This register is sticky. Power Well: SUS
8:5	5h RW	Port Link State (PLS): Note: This register is sticky. Power Well: SUS
4	0b RW/S	Port Reset (PR): Reserved. Power Well: SUS
3	0b RW	Over-current Active (OCA): Note: This register is sticky. Power Well: SUS
2	0b RO	Rsvd1: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW/C	Port Enabled Disabled (PED): Note: This register is sticky. Power Well: SUS
0	0b RW	Current Connect Status (CCS): Note: This register is sticky. Power Well: SUS

18.7.34 Port 6 Power Management Status and Control USB2 (PORTPMSC6USB2)—Offset 4D4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4D4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PTC		Rsvd1		HLE		L1DS		HIRD
							RWE	L1S

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	Port Test Control (PTC): Note: This register is sticky. Power Well: SUS
27:17	000h RO	Rsvd1: Reserved. Power Well: Core
16	0b RO	Hardware LPM Enable (HLE): Reserved. Power Well: SUS
15:8	00h RW	L1 Device Slot (L1DS): Note: This register is sticky. Power Well: SUS
7:4	0h RW	Host Initiated Resume Duration (HIRD): Note: This register is sticky. Power Well: SUS
3	0b RW	Remote Wake Enable (RWE): Note: This register is sticky. Power Well: SUS
2:0	0h RW	L1 Status (L1S): Note: This register is sticky. Power Well: SUS



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4E0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 000002A0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
WPR	DR	Rsvd2	WOE	WDE	WCE	CAS	CEC	PLC
			PRC	OCC	WRC	PEC	CSC	LWS
							PTC	
							Port_Speed	
							PP	
							PLS	
							PR	
							OCA	
							Rsvd1	
							PED	
							CCS	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/S	Warm Port Reset (WPR): Reserved. Power Well: SUS
30	0b RO	Device Removable (DR): Reserved. Power Well: Core
29:28	0h RO	Rsvd2: Reserved. Power Well: Core
27	0b RW	Wake on Over-current Enable (WOE): Note: This register is sticky. Power Well: SUS
26	0b RW	Wake on Disconnect Enable (WDE): Note: This register is sticky. Power Well: SUS
25	0b RW	Wake on Connect Enable (WCE): Note: This register is sticky. Power Well: SUS
24	0b RO	Cold Attach Status (CAS): Reserved. Power Well: SUS
23	0b RW/C	Port Config Error Change (CEC): Note: This register is sticky. Power Well: SUS
22	0b RW/C	Port Link State Change (PLC): Note: This register is sticky. Power Well: SUS
21	0b RW/C	Port Reset Change (PRC): Note: This register is sticky. Power Well: SUS
20	0b RW/C	Over-current Change (OCC): Note: This register is sticky. Power Well: SUS
19	0b RW/C	Warm Port Reset Change (WRC): Note: This register is sticky. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW/C	Port Enabled Disabled Change (PEC): Note: This register is sticky. Power Well: SUS
17	0b RW/C	Connect Status Change (CSC): Note: This register is sticky. Power Well: SUS
16	0b RW	Port Link State Write Strobe (LWS): Reserved. Power Well: SUS
15:14	0h RW	Port Indicator Control (PIC): Note: This register is sticky. Power Well: SUS
13:10	0h RW	Port Speed (Port_Speed): Note: This register is sticky. Power Well: SUS
9	1b RW	Port Power (PP): Note: This register is sticky. Power Well: SUS
8:5	5h RW	Port Link State (PLS): Note: This register is sticky. Power Well: SUS
4	0b RW/S	Port Reset (PR): Reserved. Power Well: SUS
3	0b RW	Over-current Active (OCA): Note: This register is sticky. Power Well: SUS
2	0b RO	Rsvd1: Reserved. Power Well: Core
1	0b RW/C	Port Enabled Disabled (PED): Note: This register is sticky. Power Well: SUS
0	0b RW	Current Connect Status (CCS): Note: This register is sticky. Power Well: SUS

18.7.37 Port 1 Power Management Status and Control USB3 (PORTPMSC1USB3)—Offset 4E4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4E4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h



31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
PTC				Rsvd1												HLE				L1DS				HIRD				RWE				L1S			

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	Port Test Control (PTC): Note: This register is sticky. Power Well: SUS
27:17	000h RO	Rsvd1: Reserved. Power Well: Core
16	0b RO	Hardware LPM Enable (HLE): Reserved. Power Well: SUS
15:8	00h RW	L1 Device Slot (L1DS): Note: This register is sticky. Power Well: SUS
7:4	0h RW	Host Initiated Resume Duration (HIRD): Note: This register is sticky. Power Well: SUS
3	0b RW	Remote Wake Enable (RWE): Note: This register is sticky. Power Well: SUS
2:0	0h RW	L1 Status (L1S): Note: This register is sticky. Power Well: SUS

18.7.38 Port 1 Link Info (PORTLI1)—Offset 4E8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 4E8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd1				LEC				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
15:0	0000h RO	Link Error Count (LEC): Reserved. Power Well: Core

18.7.39 Microframe Index (MFINDEX)—Offset 2000h

This register is used by the system software to determine the current periodic frame. The register value is incremented every 125 microseconds (once each microframe). This register is only incremented while *Run/Stop* = '1'. The value of this register affects the SOF value generated by USB2 Bus Instances.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2000h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd1					MI			

Bit Range	Default & Access	Field Name (ID): Description
31:14	00000h RO	Rsvd1: Reserved. Power Well: Core
13:0	0000h RO	Microframe Index (MI): Reserved. Power Well: Core

18.7.40 Interrupter 1 Management (IMAN1)—Offset 2020h

The Interrupter Management registers allow system software to enable, disable, detect and force xHC interrupts. There are 8 IMAN registers. $x = 1, 2, \dots, 8$.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2020h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	0	0
Rsvd1									IE	IP



Bit Range	Default & Access	Field Name (ID): Description
31:2	00000000h RO	Rsvd1: Reserved. Power Well: Core
1	0b RW	Interrupt Enable (IE): Reserved. Power Well: Core
0	0b RW/C	Interrupt Pending (IP): Reserved. Power Well: Core

18.7.41 Interrupter 1 Moderation (IMOD1)—Offset 2024h

The Interrupter Moderation Register controls the 'interrupt moderation' feature of an interrupter, allowing system software to throttle the interrupt rate generated by the xHC. There are 8 IMOD registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2024h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000FA0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	1	1	1
0	0	0	0	0	0	1	0	1
0	0	0	0	0	0	0	0	0
IMODC				IMODI				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	Interrupt Moderation Counter (IMODC): Down counter. Loaded with the IMODI value whenever IP is cleared to '0', counts down to '0' and stops. The associated interrupt shall be signaled whenever this counter is '0', the Event Ring is not empty, the IE and IP flags both equal '1', and EHB = '0'. This counter may be written directly by software at any time to alter the interrupt rate. Power Well: Core
15:0	0FA0h RW	Interrupt Moderation Interval (IMODI): Default = '4000' (~1 ms). Minimum inter-interrupt interval. The interval is specified in 250ns increments. A value of '0' disables interrupt throttling logic, and interrupts shall be generated immediately if IP = '0', EHB = '0', and the Event Ring is not empty. Power Well: Core

18.7.42 Event Ring Segment Table Size 1 (ERSTS1)—Offset 2028h

The *Event Ring Segment Table Size Register* defines the number of segments supported by the Event Ring Segment Table. There are 8 ERSTS registers. x = 1, 2, ... 8.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2028h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1				ERSTS				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core
15:0	0000h RW	Event Ring Segment Table Size (ERSTS): This field identifies the number of valid Event Ring Segment Table entries in the Event Ring Segment Table pointed to by the Event Ring Segment Table Base Address register. The maximum value supported by an xHC implementation for this register is defined by the ERST Max field in the HCSPARAMS2 register (see specification xHCI for USB). For Secondary Interrupters: Writing a value of 0 to this field disables the Event Ring. Any events targeted at this Event Ring when it is disabled shall result in undefined behavior of the Event Ring. For the Primary Interrupter: Writing a value of 0 to this field shall result in undefined behavior of the Event Ring. The Primary Event Ring cannot be disabled. Power Well: Core

18.7.43 Event Ring Segment Table Base Address Low 1 (ERSTBA_LO1)—Offset 2030h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_LOx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2030h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ERSTBA_LO							Rsvd1	



Bit Range	Default & Access	Field Name (ID): Description
31:6	0000000h RW	Event Ring Segment Table Base Address Register (ERSTBA_LO): This field defines the low order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core
5:0	00h RO	Rsvd1: Reserved. Power Well: Core

18.7.44 Event Ring Segment Table Base Address High 1 (ERSTBA_HI1)—Offset 2034h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_HIx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2034h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

ERSTBA_HI

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Segment Table Base Address (ERSTBA_HI): This field defines the high order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core

18.7.45 Event Ring Dequeue Pointer Low 1 (ERDP_LO1)—Offset 2038h

There are 8 ERDP_LOx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2038h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2040h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1								IE
								IP

Bit Range	Default & Access	Field Name (ID): Description
31:2	00000000h RO	Rsvd1: Reserved. Power Well: Core
1	0b RW	Interrupt Enable (IE): Reserved. Power Well: Core
0	0b RW/C	Interrupt Pending (IP): Reserved. Power Well: Core

18.7.48 Interrupter 2 Moderation (IMOD2)—Offset 2044h

The Interrupter Moderation Register controls the 'interrupt moderation' feature of an interrupter, allowing system software to throttle the interrupt rate generated by the xHC. There are 8 IMOD registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2044h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000FA0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
IMODC								IMODI

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	Interrupt Moderation Counter (IMODC): Default undefined. Down counter. Loaded with the IMODI value whenever IP is cleared to '0', counts down to '0' and stops. The associated interrupt shall be signaled whenever this counter is '0', the Event Ring is not empty, the IE and IP flags = '1', and EHB = '0'. This counter may be written directly by software at any time to alter the interrupt rate. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
15:0	0FA0h RW	Interrupt Moderation Interval (IMODI): Default = '4000' (~1 ms). Minimum inter-interrupt interval. The interval is specified in 250ns increments. A value of '0' disables interrupt throttling logic, and interrupts shall be generated immediately if IP = '0', EHB = '0', and the Event Ring is not empty. Power Well: Core

18.7.49 Event Ring Segment Table Size 2 (ERSTS2)—Offset 2048h

The *Event Ring Segment Table Size Register* defines the number of segments supported by the Event Ring Segment Table. There are 8 ERSTS registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2048h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1				ERSTS				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core
15:0	0000h RW	Event Ring Segment Table Size (ERSTS): This field identifies the number of valid Event Ring Segment Table entries in the Event Ring Segment Table pointed to by the Event Ring Segment Table Base Address register. The maximum value supported by an xHC implementation for this register is defined by the ERST Max field in the HCSPARAMS2 register (see specification xHCI for USB). For Secondary Interrupters: Writing a value of 0 to this field disables the Event Ring. Any events targeted at this Event Ring when it is disabled shall result in undefined behavior of the Event Ring. For the Primary Interrupter: Writing a value of 0 to this field shall result in undefined behavior of the Event Ring. The Primary Event Ring cannot be disabled. Power Well: Core

18.7.50 Event Ring Segment Table Base Address Low 2 (ERSTBA_LO2)—Offset 2050h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_Lox registers, with x = 1, 2, ... 8.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2050h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:6	0000000h RW	Event Ring Segment Table Base Address Register (ERSTBA_LO): This field defines the low order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core
5:0	00h RO	Rsvd1: Reserved. Power Well: Core

18.7.51 Event Ring Segment Table Base Address High 2 (ERSTBA_HI2)—Offset 2054h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_HIx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2054h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Segment Table Base Address (ERSTBA_HI): This field defines the high order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine: EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core

18.7.52 Event Ring Dequeue Pointer Low 2 (ERDP_LO2)—Offset 2058h

There are 8 ERDP_LOx registers, with $x = 1, 2, \dots, 8$.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2058h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	0	0
									ERDP	
									EHB	DEST

Bit Range	Default & Access	Field Name (ID): Description
31:4	0000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the low order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core
3	0b RW/C	Event Handler Busy (EHB): This flag shall be set to 1 when the IP bit is set to 1 and cleared to 0 by software when the Dequeue Pointer register is written. Refer to the xHCI for USB specification for more information. Power Well: Core
2:0	0h RW	Dequeue ERST Segment Index (DESI): This field may be used by the xHC to accelerate checking the Event Ring full condition. This field is written with the low order 3 bits of the offset of the ERST entry which defines the Event Ring segment that the Event Ring Dequeue Pointer resides in. Power Well: Core

18.7.53 Event Ring Dequeue Pointer High 2 (ERDP_HI2)—Offset 205Ch

There are 8 ERDP_HIx registers, with $x = 1, 2, \dots, 8$.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 205Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

ERDP

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the high order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core

18.7.54 Interrupter 3 Management (IMAN3)—Offset 2060h

The Interrupter Management registers allow system software to enable, disable, detect and force xHC interrupts. There are 8 IMAN registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2060h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Rsvd1

IE

IP

Bit Range	Default & Access	Field Name (ID): Description
31:2	00000000h RO	Rsvd1: Reserved. Power Well: Core
1	0b RW	Interrupt Enable (IE): Reserved. Power Well: Core
0	0b RW/C	Interrupt Pending (IP): Reserved. Power Well: Core

18.7.55 Interrupter 3 Moderation (IMOD3)—Offset 2064h

The Interrupter Moderation Register controls the 'interrupt moderation' feature of an interrupter, allowing system software to throttle the interrupt rate generated by the xHC. There are 8 IMOD registers. x = 1, 2, ... 8.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2064h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000FA0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	Interrupt Moderation Counter (IMODC): Down counter. Loaded with the IMODI value whenever <i>IP</i> is cleared to '0', counts down to '0' and stops. The associated interrupt shall be signaled whenever this counter is '0', the Event Ring is not empty, the IE and IP flags = '1', and EHB = '0'. This counter may be written directly by software at any time to alter the interrupt rate. Power Well: Core
15:0	0FA0h RW	Interrupt Moderation Interval (IMODI): Default = '4000' (~1 ms). Minimum inter-interrupt interval. The interval is specified in 250ns increments. A value of '0' disables interrupt throttling logic, and interrupts shall be generated immediately if IP = '0', EHB = '0', and the Event Ring is not empty. Power Well: Core

18.7.56 Event Ring Segment Table Size 3 (ERSTS3)—Offset 2068h

The *Event Ring Segment Table Size Register* defines the number of segments supported by the Event Ring Segment Table. There are 8 ERSTS3 registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2068h


MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
15:0	0000h RW	Event Ring Segment Table Size (ERSTS): This field identifies the number of valid Event Ring Segment Table entries in the Event Ring Segment Table pointed to by the Event Ring Segment Table Base Address register. The maximum value supported by an xHC implementation for this register is defined by the ERST Max field in the HCSPARAMS2 register (see specification xHCI for USB). For Secondary Interrupters: Writing a value of 0 to this field disables the Event Ring. Any events targeted at this Event Ring when it is disabled shall result in undefined behavior of the Event Ring. For the Primary Interrupter: Writing a value of 0 to this field shall result in undefined behavior of the Event Ring. The Primary Event Ring cannot be disabled. Power Well: Core

18.7.57 Event Ring Segment Table Base Address Low 3 (ERSTBA_LO3)—Offset 2070h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_LOx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2070h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ERSTBA_LO								Rsvd1

Bit Range	Default & Access	Field Name (ID): Description
31:6	0000000h RW	Event Ring Segment Table Base Address Register (ERSTBA_LO): This field defines the low order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core
5:0	00h RO	Rsvd1: Reserved. Power Well: Core

18.7.58 Event Ring Segment Table Base Address High 3 (ERSTBA_HI3)—Offset 2074h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_HIx registers, with x = 1, 2, ... 8.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2074h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Segment Table Base Address (ERSTBA_HI): This field defines the high order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core

18.7.59 Event Ring Dequeue Pointer Low 3 (ERDP_LO3)—Offset 2078h

There are 8 ERDP_LOx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2078h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:4	0000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the low order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core
3	0b RW/C	Event Handler Busy (EHB): This flag shall be set to 1 when the IP bit is set to 1 and cleared to 0 by software when the Dequeue Pointer register is written. Refer to the xHCI for USB specification for more information. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
2:0	0h RW	Dequeue ERST Segment Index (DESI): This field may be used by the xHC to accelerate checking the Event Ring full condition. This field is written with the low order 3 bits of the offset of the ERST entry which defines the Event Ring segment that the Event Ring Dequeue Pointer resides in. Power Well: Core

18.7.60 Event Ring Dequeue Pointer High 3 (ERDP_HI3)—Offset 207Ch

There are 8 ERDP_HIx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 207Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

ERDP

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the high order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core

18.7.61 Interrupter 4 Management (IMAN4)—Offset 2080h

The Interrupter Management registers allow system software to enable, disable, detect and force xHC interrupts. There are 8 IMAN registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2080h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Rsvd1

IE

IP



Bit Range	Default & Access	Field Name (ID): Description
31:2	00000000h RO	Rsvd1: Reserved. Power Well: Core
1	0b RW	Interrupt Enable (IE): Reserved. Power Well: Core
0	0b RW/C	Interrupt Pending (IP): Reserved. Power Well: Core

18.7.62 Interrupter 4 Moderation (IMOD4)—Offset 2084h

The Interrupter Moderation Register controls the 'interrupt moderation' feature of an interrupter, allowing system software to throttle the interrupt rate generated by the xHC. There are 8 IMOD registers. $x = 1, 2, \dots 8$.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2084h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000FA0h

31	28	24	20	16	12	8	4	0									
0	0	0	0	0	0	0	1	1	1	1	1	0	1	0	0	0	0
IMODC								IMODI									

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	Interrupt Moderation Counter (IMODC): Down counter. Loaded with the IMODI value whenever <i>IP</i> is cleared to '0', counts down to '0' and stops. The associated interrupt shall be signaled whenever this counter is '0', the Event Ring is not empty, the IE and IP flags = '1', and EHB = '0'. This counter may be written directly by software at any time to alter the interrupt rate. Power Well: Core
15:0	0FA0h RW	Interrupt Moderation Interval (IMODI): Default = '4000' (~1 ms). Minimum inter-interrupt interval. The interval is specified in 250ns increments. A value of '0' disables interrupt throttling logic, and interrupts shall be generated immediately if IP = '0', EHB = '0', and the Event Ring is not empty. Power Well: Core

18.7.63 Event Ring Segment Table Size 4 (ERSTS4)—Offset 2088h

The *Event Ring Segment Table Size Register* defines the number of segments supported by the Event Ring Segment Table. There are 8 ERSTS registers. $x = 1, 2, \dots 8$.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2088h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1				ERSTS				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core
15:0	0000h RW	Event Ring Segment Table Size (ERSTS): This field identifies the number of valid Event Ring Segment Table entries in the Event Ring Segment Table pointed to by the Event Ring Segment Table Base Address register. The maximum value supported by an xHC implementation for this register is defined by the ERST Max field in the HCSPARAMS2 register (see specification xHCI for USB). For Secondary Interrupters: Writing a value of 0 to this field disables the Event Ring. Any events targeted at this Event Ring when it is disabled shall result in undefined behavior of the Event Ring. For the Primary Interrupter: Writing a value of 0 to this field shall result in undefined behavior of the Event Ring. The Primary Event Ring cannot be disabled. Power Well: Core

18.7.64 Event Ring Segment Table Base Address Low 4 (ERSTBA_LO4)—Offset 2090h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_LOx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2090h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ERSTBA_LO							Rsvd1	



Bit Range	Default & Access	Field Name (ID): Description
31:6	0000000h RW	Event Ring Segment Table Base Address Register (ERSTBA_LO): This field defines the low order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core
5:0	00h RO	Rsvd1: Reserved. Power Well: Core

18.7.65 Event Ring Segment Table Base Address High 4 (ERSTBA_HI4)—Offset 2094h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_HIx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2094h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

ERSTBA_HI

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Segment Table Base Address (ERSTBA_HI): This field defines the high order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core

18.7.66 Event Ring Dequeue Pointer Low 4 (ERDP_LO4)—Offset 2098h

There are 8 ERDP_LOx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2098h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	0	0
ERDP									EHB	DESI

Bit Range	Default & Access	Field Name (ID): Description
31:4	0000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the low order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core
3	0b RW/C	Event Handler Busy (EHB): This flag shall be set to 1 when the IP bit is set to 1 and cleared to 0 by software when the Dequeue Pointer register is written. Refer to the xHCI for USB specification for more information. Power Well: Core
2:0	0h RW	Dequeue ERST Segment Index (DESI): This field may be used by the xHC to accelerate checking the Event Ring full condition. This field is written with the low order 3 bits of the offset of the ERST entry which defines the Event Ring segment that the Event Ring Dequeue Pointer resides in. Power Well: Core

18.7.67 Event Ring Dequeue Pointer High 4 (ERDP_HI4)—Offset 209Ch

Diagram illustrating the structure of the ERDP register, showing 32 bits divided into 8 nibbles (4 bits each), indexed from 31 down to 0. The label "ERDP" is positioned vertically below the register line, centered under the nibbles indexed 16 and 17.

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the high order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core

18.7.68 Interrupter 5 Management (IMAN5)—Offset 20A0h

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
15:0	0FA0h RW	Interrupt Moderation Interval (IMODI): Default = '4000' (~1 ms). Minimum inter-interrupt interval. The interval is specified in 250ns increments. A value of '0' disables interrupt throttling logic, and interrupts shall be generated immediately if IP = '0', EHB = '0', and the Event Ring is not empty. Power Well: Core

18.7.70 Event Ring Segment Table Size 5 (ERSTS5)—Offset 20A8h

The *Event Ring Segment Table Size Register* defines the number of segments supported by the Event Ring Segment Table. There are 8 ERSTS registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20A8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1				ERSTS				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core
15:0	0000h RW	Event Ring Segment Table Size (ERSTS): This field identifies the number of valid Event Ring Segment Table entries in the Event Ring Segment Table pointed to by the Event Ring Segment Table Base Address register. The maximum value supported by an xHC implementation for this register is defined by the ERST Max field in the HCSPARAMS2 register (see specification xHCI for USB). For Secondary Interrupters: Writing a value of 0 to this field disables the Event Ring. Any events targeted at this Event Ring when it is disabled shall result in undefined behavior of the Event Ring. For the Primary Interrupter: Writing a value of 0 to this field shall result in undefined behavior of the Event Ring. The Primary Event Ring cannot be disabled. Power Well: Core

18.7.71 Event Ring Segment Table Base Address Low 5 (ERSTBA_LO5)—Offset 20B0h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_LOx registers, with x = 1, 2, ... 8.

Access Method

18.7.73 Event Ring Dequeue Pointer Low 5 (ERDP_LO5)—Offset 20B8h

There are 8 ERDP_LOx registers, with $x = 1, 2, \dots, 8$.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20B8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	0	0
ERDP									EHB	DESI

Bit Range	Default & Access	Field Name (ID): Description
31:4	0000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the low order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core
3	0b RW/C	Event Handler Busy (EHB): This flag shall be set to 1 when the IP bit is set to 1 and cleared to 0 by software when the Dequeue Pointer register is written. Refer to the xHCI for USB specification for more information. Power Well: Core
2:0	0h RW	Dequeue ERST Segment Index (DESI): This field may be used by the xHC to accelerate checking the Event Ring full condition. This field is written with the low order 3 bits of the offset of the ERST entry which defines the Event Ring segment that the Event Ring Dequeue Pointer resides in. Power Well: Core

18.7.74 Event Ring Dequeue Pointer High 5 (ERDP_HI5)—Offset 20BCh

There are 8 ERDP_HIx registers, with $x = 1, 2, \dots, 8$.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20BCh

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

ERDP

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the high order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core

18.7.75 Interrupter 6 Management (IMAN6)—Offset 20C0h

The Interrupter Management registers allow system software to enable, disable, detect and force xHC interrupts. There are 8 IMAN registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20C0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Rsvd1


IE
IP

Bit Range	Default & Access	Field Name (ID): Description
31:2	00000000h RO	Rsvd1: Reserved. Power Well: Core
1	0b RW	Interrupt Enable (IE): Reserved. Power Well: Core
0	0b RW/C	Interrupt Pending (IP): Reserved. Power Well: Core

18.7.76 Interrupter 6 Moderation (IMOD6)—Offset 20C4h

The Interrupter Moderation Register controls the 'interrupt moderation' feature of an interrupter, allowing system software to throttle the interrupt rate generated by the xHC. There are 8 IMOD registers. x = 1, 2, ... 8.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20C4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000FA0h

[illegible]

18.7.77 Event Ring Segment Table Size 6 (ERSTS6)—Offset 20C8h

The *Event Ring Segment Table Size Register* defines the number of segments supported by the Event Ring Segment Table. There are 8 ERSTS registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20C8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

312824201612840																															
00000000000000000000000000000000																															
Rsvd1																ERSTS															
Bit Range		Default & Access		Field Name (ID): Description																											
31:16		0000h RO		Rsvd1: Reserved. Power Well: Core																											



Bit Range	Default & Access	Field Name (ID): Description
15:0	0000h RW	Event Ring Segment Table Size (ERSTS): This field identifies the number of valid Event Ring Segment Table entries in the Event Ring Segment Table pointed to by the Event Ring Segment Table Base Address register. The maximum value supported by an xHC implementation for this register is defined by the ERST Max field in the HCSPARAMS2 register (see xHCI for USB specification). For Secondary Interrupters: Writing a value of 0 to this field disables the Event Ring. Any events targeted at this Event Ring when it is disabled shall result in undefined behavior of the Event Ring. For the Primary Interrupter: Writing a value of 0 to this field shall result in undefined behavior of the Event Ring. The Primary Event Ring cannot be disabled. Power Well: Core

18.7.78 Event Ring Segment Table Base Address Low 6 (ERSTBA_LO6)—Offset 20D0h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_LOx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20D0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ERSTBA_LO								Rsvd1

Bit Range	Default & Access	Field Name (ID): Description
31:6	0000000h RW	Event Ring Segment Table Base Address Register (ERSTBA_LO): This field defines the low order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core
5:0	00h RO	Rsvd1: Reserved. Power Well: Core

18.7.79 Event Ring Segment Table Base Address High 6 (ERSTBA_HI6)—Offset 20D4h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_HIx registers, with x = 1, 2, ... 8.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20D4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

ERSTBA_HI

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Segment Table Base Address (ERSTBA_HI): This field defines the high order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core

18.7.80 Event Ring Dequeue Pointer Low 6 (ERDP_LO6)—Offset 20D8h

There are 8 ERDP_LOx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20D8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

ERDP

EHB

DESI

Bit Range	Default & Access	Field Name (ID): Description
31:4	00000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the low order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core
3	0b RW/C	Event Handler Busy (EHB): This flag shall be set to 1 when the IP bit is set to 1 and cleared to 0 by software when the Dequeue Pointer register is written. Refer to the xHCI for USB specification for more information. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
2:0	0h RW	Dequeue ERST Segment Index (DESI): This field may be used by the xHC to accelerate checking the Event Ring full condition. This field is written with the low order 3 bits of the offset of the ERST entry which defines the Event Ring segment that the Event Ring Dequeue Pointer resides in. Power Well: Core

18.7.81 Event Ring Dequeue Pointer High 6 (ERDP_HI6)—Offset 20DCh

There are 8 ERDP_HIx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20DCh

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

ERDP

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Dequeue Pointer (ERDP): This field defines the high order bits of the 64-bit address of the current Event Ring Dequeue Pointer. Power Well: Core

18.7.82 Interrupter 7 Management (IMAN7)—Offset 20E0h

The Interrupter Management registers allow system software to enable, disable, detect and force xHC interrupts. There are 8 IMAN registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20E0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Rsvd1

IE

IP



Bit Range	Default & Access	Field Name (ID): Description
31:2	00000000h RO	Rsvd1: Reserved. Power Well: Core
1	0b RW	Interrupt Enable (IE): Reserved. Power Well: Core
0	0b RW/C	Interrupt Pending (IP): Reserved. Power Well: Core

18.7.83 Interrupter 7 Moderation (IMOD7)—Offset 20E4h

Access Method

Offset: [MBAR] + 20E4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h


Default: 00000FA0h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	Interrupt Moderation Counter (IMODC): Down counter. Loaded with the IMODI value whenever <i>IP</i> is cleared to '0', counts down to '0' and stops. The associated interrupt shall be signaled whenever this counter is '0', the Event Ring is not empty, the IE and IP flags = '1', and EHB = '0'. This counter may be written directly by software at any time to alter the interrupt rate. Power Well: Core
15:0	0FA0h RW	Interrupt Moderation Interval (IMODI): Default = '4000' (~1 ms). Minimum inter-interrupt interval. The interval is specified in 250ns increments. A value of '0' disables interrupt throttling logic, and interrupts shall be generated immediately if IP = '0', EHB = '0', and the Event Ring is not empty. Power Well: Core

18.7.84 Event Ring Segment Table Size 7 (ERSTS7)—Offset 20E8h

Access Method





Bit Range	Default & Access	Field Name (ID): Description
31:6	0000000h RW	Event Ring Segment Table Base Address Register (ERSTBA_LO): This field defines the low order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core
5:0	00h RO	Rsvd1: Reserved. Power Well: Core

18.7.86 Event Ring Segment Table Base Address High 7 (ERSTBA_HI7)—Offset 20F4h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_HIx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20F4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

ERSTBA_HI

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Event Ring Segment Table Base Address (ERSTBA_HI): This field defines the high order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core

18.7.87 Event Ring Dequeue Pointer Low 7 (ERDP_LO7)—Offset 20F8h

There are 8 ERDP_LOx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 20F8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2100h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1								IE
								IP

Bit Range	Default & Access	Field Name (ID): Description
31:2	00000000h RO	Rsvd1: Reserved. Power Well: Core
1	0b RW	Interrupt Enable (IE): Reserved. Power Well: Core
0	0b RW/C	Interrupt Pending (IP): Reserved. Power Well: Core

18.7.90 Interrupter 8 Moderation (IMOD8)—Offset 2104h

The Interrupter Moderation Register controls the 'interrupt moderation' feature of an interrupter, allowing system software to throttle the interrupt rate generated by the xHC. There are 8 IMOD registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2104h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000FA0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
IMODC								IMODI

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	Interrupt Moderation Counter (IMODC): Down counter. Loaded with the IMODI value whenever IP is cleared to '0', counts down to '0' and stops. The associated interrupt shall be signaled whenever this counter is '0', the Event Ring is not empty, the IE and IP flags = '1', and EHB = '0'. This counter may be written directly by software at any time to alter the interrupt rate. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
15:0	0FA0h RW	Interrupt Moderation Interval (IMODI): Default = '4000' (~1 ms). Minimum inter-interrupt interval. The interval is specified in 250ns increments. A value of '0' disables interrupt throttling logic, and interrupts shall be generated immediately if IP = '0', EHB = '0', and the Event Ring is not empty. Power Well: Core

18.7.91 Event Ring Segment Table Size 8 (ERSTS8)—Offset 2108h

The *Event Ring Segment Table Size Register* defines the number of segments supported by the Event Ring Segment Table. There are 8 ERSTS registers. x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2108h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Rsvd1				ERSTS				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Rsvd1: Reserved. Power Well: Core
15:0	0000h RW	Event Ring Segment Table Size (ERSTS): This field identifies the number of valid Event Ring Segment Table entries in the Event Ring Segment Table pointed to by the Event Ring Segment Table Base Address register. The maximum value supported by an xHC implementation for this register is defined by the ERST Max field in the HCSPARAMS2 register (see specification xHCI for USB). For Secondary Interrupters: Writing a value of 0 to this field disables the Event Ring. Any events targeted at this Event Ring when it is disabled shall result in undefined behavior of the Event Ring. For the Primary Interrupter: Writing a value of 0 to this field shall result in undefined behavior of the Event Ring. The Primary Event Ring cannot be disabled. Power Well: Core

18.7.92 Event Ring Segment Table Base Address Low 8 (ERSTBA_LO8)—Offset 2110h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_Lox registers, with x = 1, 2, ... 8.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2110h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ERSTBA_LO								Rsvd1

Bit Range	Default & Access	Field Name (ID): Description
31:6	0000000h RW	Event Ring Segment Table Base Address Register (ERSTBA_LO): This field defines the low order bits of the start address of the Event Ring Segment Table. Writing this register sets the Event Ring State Machine:EREP Advancement to the Start state. Refer to the xHCI for USB specification for more information. This field shall not be modified if HCHalted (HCH) = 0. Power Well: Core
5:0	00h RO	Rsvd1: Reserved. Power Well: Core

18.7.93 Event Ring Segment Table Base Address High 8 (ERSTBA_HI8)—Offset 2114h

The *Event Ring Segment Table Base Address Register* identifies the start address of the Event Ring Segment Table. There are 8 ERSTBA_HIx registers, with x = 1, 2, ... 8.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2114h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ERSTBA_HI								



Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RW	DB Target (DBT): This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. • Device Context Doorbells (1-255) • 0 = Reserved • 1 = Control EP 0 Enqueue Pointer Update • 2 = EP 1 OUT Enqueue Pointer Update • 3 = EP 1 IN Enqueue Pointer Update • 4 = EP 2 OUT Enqueue Pointer Update • 5 = EP 2 IN Enqueue Pointer Update • ... • 30 = EP 15 OUT Enqueue Pointer Update • 31 = EP 15 IN Enqueue Pointer Update • 32:247 = Reserved • 248:255 = Vendor Defined • Host Controller Doorbell (0) • 0 = Command Doorbell • 248:255 = Vendor Defined This field returns '0' when read, and should be treated as 'undefined' by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0. Power Well: Core

18.7.97 Door Bell 2 (DOORBELL2)—Offset 3004h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3004h**MBAR Type:** PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core



18.7.98 Door Bell 3 (DOORBELL3)—Offset 3008h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3008h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.99 Door Bell 4 (DOORBELL4)—Offset 300Ch

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 300Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.102 Door Bell 7 (DOORBELL7)—Offset 3018h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3018h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.103 Door Bell 8 (DOORBELL8)—Offset 301Ch

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 301Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.104 Door Bell 9 (DOORBELL9)—Offset 3020h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3020h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.109 Door Bell 14 (DOORBELL14)—Offset 3034h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3034h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.110 Door Bell 15 (DOORBELL15)—Offset 3038h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3038h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.111 Door Bell 16 (DOORBELL16)—Offset 303Ch

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 303Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.116 Door Bell 21 (DOORBELL21)—Offset 3050h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3050h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.117 Door Bell 22 (DOORBELL22)—Offset 3054h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3054h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.118 Door Bell 23 (DOORBELL23)—Offset 3058h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3058h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.121 Door Bell 26 (DOORBELL26)—Offset 3064h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3064h**MBAR Type:** PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.122 Door Bell 27 (DOORBELL27)—Offset 3068h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3068h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.123 Door Bell 28 (DOORBELL28)—Offset 306Ch

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 306Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.124 Door Bell 29 (DOORBELL29)—Offset 3070h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3070h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.125 Door Bell 30 (DOORBELL30)—Offset 3074h

Door Bell registers are an array of 64 registers, with 0 to 32 being used by the XHC and the rest being reserved. Refer to the xHCI for USB specification for more information.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 3074h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DBSID				Rsvd1				DBT

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	DB Stream ID (DBSID): Refer to field descriptions for the DOORBELL1 register. Power Well: Core
15:8	00h RO	Rsvd1: Reserved. Power Well: Core
7:0	00h RW	DB Target (DBT): Refer to field descriptions for the DOORBELL1 register. Power Well: Core

18.7.128 XECP_SUPP_USB2_0—Offset 8000h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8000h**MBAR Type:** PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 02000802h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	1	0	0
USB2_MAJ_REV				NCP				SPID

Bit Range	Default & Access	Field Name (ID): Description
31:24	02h RO	USB Major Revision: 2.0 (USB2_MAJ_REV): Reserved. Power Well: Core
23:16	00h RO	USB Minor Revision (USB_MIN_REV): Reserved. Power Well: Core
15:8	08h RO	Next Capability Pointer (NCP): Reserved. Power Well: Core
7:0	02h RO	Supported Protocol ID (SPID): Reserved. Power Well: Core

18.7.129 XECP_SUPP_USB2_1—Offset 8004h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8004h**MBAR Type:** PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 20425355h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	1	0	0	0
0	1	0	0	0	0	1	0	0
0	0	1	0	0	1	0	0	1
0	0	1	1	0	0	1	1	0
0	1	0	1	0	1	0	1	0
0	1	0	1	0	1	0	1	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	20425355h RO	XECP_SUPP_USB2_1: Namestring USB Power Well: Core

18.7.130 XECP_SUPP_USB2_2—Offset 8008h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8008h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 30190601h

31				28				24				20				16				12				8				4				0			
0 0 1 1				0 0 0 0				0 0 0 1				1 0 0 1				0 0 0 0				0 1 1 0				0 0 0 0				0 0 0 1							
PROT_SPD_ID_CNT				Rsvd0				BLC				HLC				IHI				HSO				RSVD				CPC				CPO			

Bit Range	Default & Access	Field Name (ID): Description
31:28	3h RO	Protocol Speed ID Count (PROT_SPD_ID_CNT): 3 USB 2.0 Speed (High, Full, Low) Power Well: Core
27:21	00h RO	Rsvd0: Reserved. Power Well: Core
20	1b RO	BESL LPM Capability (BLC): Bit is set to 1 to indicate that the the ports described by this xHCI Supported Protocol Capability will apply BESL timing to BESL and BESLD fields of the PORTPMSC and PORTHLPMC registers. Power Well: Core
19	1b RO	Protocol Defined - Hardware LMP Capability (HLC): Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
18	0b RO	Protocol Defined - Integrated Hub Implementation (IHI): Reserved. Power Well: Core
17	0b RO	Protocol Defined - High SPeed Only (HSO): Reserved. Power Well: Core
16	1b RO	Reserved (RSVD): Reserved. Power Well: Core
15:8	06h RO	Compatible Port Count (CPC): Reserved. Power Well: Core
7:0	01h RO	Compatible Port Offset (CPO): Reserved. Power Well: Core

18.7.131 XECP_SUPP_USB2_3 (Full Speed) (XECP_SUPP_USB2_3)–Offset 8010h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8010h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 000C0021h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1				
PSIM												Rsvd0												PFD	PLT	PSIE	PSIV								

Bit Range	Default & Access	Field Name (ID): Description
31:16	000Ch RO	Protocol Speed ID Mantissa (PSIM): Reserved. Power Well: Core
15:9	00h RO	Rsvd0: Reserved. Power Well: Core
8	0b RO	PSI Full Duplex (PFD): Reserved. Power Well: Core
7:6	0h RO	PSI Type (PLT): Reserved. Power Well: Core
5:4	2h RO	Protocol Speed ID Exponent (PSIE): Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
3:0	1h RO	Protocol Speed ID Value (PSIV): Reserved. Power Well: Core

18.7.132 XECP_SUPP_USB2_4 (Low Speed) (XECP_SUPP_USB2_4)—Offset 8014h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8014h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 05DC0012h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	0	1	1
1	1	0	1	1	1	0	0	0
PSIM				Rsvd0		PFD	PLT	PSIE
								PSIV

Bit Range	Default & Access	Field Name (ID): Description
31:16	05DCh RO	Protocol Speed ID Mantissa (PSIM): Reserved. Power Well: Core
15:9	00h RO	Rsvd0: Reserved. Power Well: Core
8	0b RO	PSI Full Duplex (PFD): Reserved. Power Well: Core
7:6	0h RO	PSI Type (PLT): Reserved. Power Well: Core
5:4	1h RO	Protocol Speed ID Exponent (PSIE): Reserved. Power Well: Core
3:0	2h RO	Protocol Speed ID Value (PSIV): Reserved. Power Well: Core

18.7.133 XECP_SUPP_USB2_5 (High Speed) (XECP_SUPP_USB2_5)—Offset 8018h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8018h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



Bit Range	Default & Access	Field Name (ID): Description
23:16	00h RO	USB Minor Revision (USB_MIN_REV): Reserved. Power Well: Core
15:8	08h RO	Next Capability Pointer (NCP): Reserved. Power Well: Core
7:0	02h RO	Supported Protocol ID (SPID): Reserved. Power Well: Core

18.7.135 XECP_SUPP_USB3_1—Offset 8024h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8024h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 20425355h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	1	0	0	0
0	0	0	0	0	0	1	0	1
0	0	0	1	1	0	0	1	1
0	0	1	0	1	0	0	1	1
0	1	0	1	0	1	0	1	0
0	1	0	1	0	1	0	1	0
0	1	0	1	0	1	0	1	0
0	1	0	1	0	1	0	1	0

XECP_SUPP_USB2_1

Bit Range	Default & Access	Field Name (ID): Description
31:0	20425355h RO	XECP_SUPP_USB2_1: Namestring USB Power Well: Core

18.7.136 XECP_SUPP_USB3_2—Offset 8028h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8028h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 10000107h



18.7.138 XECP_CMDM_STS0—Offset 8040h

Bit Range	Default & Access	Field Name (ID): Description
7:6	0h RO	PSI Type (PLT): Reserved. Power Well: Core
5:4	3h RO	Protocol Speed ID Exponent (PSIE): Reserved. Power Well: Core
3:0	4h RO	Protocol Speed ID Value (PSIV): Reserved. Power Well: Core

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8040h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000CC1h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0h RO	IDMA_OWNS_CNTX: Indicates that IDMA module owns the context access currently Power Well: Core
30	0h RO	ODMA_OWNS_CNTX: Indicates that ODMA module owns the context access currently Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
29	0h RO	TRM_OWNS_CNTX: Indicates that TRM modules owns the context access currently Power Well: Core
28	0h RO	CMD_RING_REQUESTED_CNTX_LOCK: Indicates that Command Manager has requested a context lock Power Well: Core
27	0h RO	CMD_RING_STOP_IN_PROGRESS: Indicates that Command Ring stop command is in progress Power Well: Core
26	0h RO	SCH_UPDATE_CLR_EP_IN_PROGRESS: Indicates that clearing an EP out of schedule is in progress Power Well: Core
25	0h RO	ADDR_DEV_DONE: Indicates that current address device command is done by ODMA Power Well: Core
24	0h RO	ADDR_DEV_IN_PROGRESS: Indicates that ODMA has an address device command in progress Power Well: Core
23	0h RO	EP_STATE_UPDATE_IN_PROGRESS: Indicates that updating of EP state is in progress Power Well: Core
22	0h RO	EP_STATE_IN_PROGRESS_FROM_STOP_DUE_TO_DB: Indicates that doorbell manager is issuing an EP update due to a doorbell ring on an EP that is in stop state Power Well: Core
21	0h RO	EP_STATE_UPDATE_IN_PROGRESS_DUE_TO_EP_ERROR: Indicates that transfer ring manager is issuing an EP update due to an EP error condition detected Power Well: Core
20	0h RO	EP_STATE_UPDATE_IN_PROGRESS_DUE_TO_STALL: Indicates that transfere ring manager is issuing an EP state update due to stall received Power Well: Core
19	0h RO	Reserved (RSVD): Reserved. Power Well: Core
18	0h RO	STOP in progress (STOP_IN_PROGRESS): Indicates that a STOP on the Command Ring is in progress Power Well: Core
17	0h RO	commend ring has doorbell pending (CMD_RING_DB_PENDING): Indicates that the commend ring has doorbell pending Power Well: Core



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

EREPL

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Event Ring Enqueue Pointer Low (EREPL): Reserved. Power Well: Core

18.7.143 XECP_CMDM_STS5—Offset 8054h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8054h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

EREPL

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Event Ring Enqueue Pointer High (EREPL): Reserved. Power Well: Core

18.7.144 Host Controller Capability (HOST_CTRL_CAP_REG)—Offset 8070h

This register is modified and maintained by BIOS

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8070h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 0000FCC0h



31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RSVD						SNDC		EP_NUM	CTSM

Intel Atom® Processor E3800 Product Family
Datasheet
2285



Type: Memory Mapped I/O Register
(Size: 32 bits)

MBAR Type: PCI Configuration Register (Size: 64 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Clear Active IN EP ID Control (HOST_CLR_IN_EP_VALID_REG): This register is used to clear the internal valid IN EP array that TRM stored in order to guarantee one IN EP per port. This register allows software to clear the valid bit of each port IN EP. This field indicates the port number. For a 2port configuration, only bit1:0 are valid. It can scale for the max number of ports that we support. Power Well: Core

18.7.147 Clear Poll Mask Control (HOST_CLR_PMASK_REG)—Offset 8080h

Type: Memory Mapped I/O Register
(Size: 32 bits)

MBAR Type: PCI Configuration Register (Size: 64 bits)

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD						SNDC		REP_NUM
								CTSPM

Bit Range	Default & Access	Field Name (ID): Description
31:10	000000h RO	RESERVED (RSVD): Reserved. Power Well: Core
9:5	00h RW	Slot Number Default Config (SNDC): 5bits of slot number as a default configuration. It can scale to max of 128 slots Power Well: Core
4:1	0h RW	EP Number (EP_NUM): 4bits of EP number Power Well: Core
0	0b RW	Clear Internal Scheduler's Poll Mask (CISPM): This is a register that is used to clear the internal scheduler's poll mask that is used to indicate whether we need to poll this EP. This is used for USB2. Bit0 indicates the direction of the EP Power Well: Core

18.7.148 Host Control Scheduler (HOST_CTRL_SCH_REG)—Offset 8094h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8094h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00008100h

31				28				24				20				16				12				8				4				0											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	1	0	0	0	0	0	0	0												
SCHED_HOST_CTRL_CONT																TTE_HOST_CTRL								CACHE_SZ_CTRL				MAX_EP_SLOT				TO_SCRATCH_PAD_EN				SCHED_HOST_CTRL							

Bit Range	Default & Access	Field Name (ID): Description
31:21	000h RW	Scheduler Host Control Reg Cont (SCHED_HOST_CTRL_CONT): method of USB2 port periodic done check (off by default) Power Well: Core
20:13	04h RW	TTE Host Control (TTE_HOST_CTRL): (0): disable interrupt complete split limit to 3 microframes (1): disable checking of missed microframes (2): disable split error request w/NULL pointer on speculative INs with data payload and no TRB. (3): disable deferred split error request on speculative IN with data payload and no TRB. (7:4): reserved Power Well: Core

18.7.149 Global Port Control (HOST_CTRL_PORT_CTRL)—Offset 80A0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80A0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00003C0Fh

31				28				24				20				16				12				8				4				0															
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	0	0	0	0	0	1	1	1	1																
RSVD												EN_PP_REG_PDWN				RESERVED				EN_USB_PP2_EN				EN_U3P.CG				EN_P3_OVR_P2_RD				EN_UPP_RST_EP3				RSVD_1											



Bit Range	Default & Access	Field Name (ID): Description
31:20	000h RO	RESERVED (RSVD): Reserved. Power Well: Core
19	0b RW	Enable PCIe PHY Regulator Power Down (EN_PP_REG_PDWN): 0 = Disable PCIe PHY regulator power down mode 1 = Enable PCIe PHY regulator power down mode Power Well: Core
18:17	0h RW	Reserved (RESERVED): Reserved Power Well: Core
16	0b RW	Enable USB PHY p2_EN (EN_USB_PP2_EN): 0 = Disable USB PHY P2_EN 1 = Enable USB PHY P2_EN Power Well: Core
15	0b RW	Enable USB3 Port Clock Gate (EN_U3P_CG): 0 = Disable USB3 port clock gate 1 = Enable USB3 port clock gate Power Well: Core
14	0b RW	Enable P3 Override P2 RxDetect (EN_P3_OVR_P2_RD): 0 = Disable P3 overriding P2 in RxDetect 1 = Enable P3 overriding P2 in RxDetect Power Well: Core
13	1b RW	Enable USB PHY Pipe Reset Exit P3 (EN_UPP_RST_EP3): 0 = Disable a USB PHY pipe reset when exit P3 1 = Enable a USB PHY pipe reset when exit P3 Power Well: Core
12:0	1C0Fh RO	RESERVED (RSVD_1): Reserved. Power Well: Core

18.7.150 AUX Reset Control (AUX_CTRL_REG)—Offset 80C0h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80C0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 015FC0F0h



31		28		24		20		16		12		8		4		0														
0	0	0	0	0	0	0	1	1	1	1	0	0	0	1	1	0	0													
RST_U3_AM_PDL	RSVD	EN_PPIPE_PPHY_RST	EN_PPWRDN_PERST	DIS_PERST_MRST	DIS_PERST_HC	EN_FAST_RST	PREV_U3_LDRST	IGN_MPU_RST	RSVD_1	IGN_HC_RST_U2	IGN_HC_RST_UP_POR	EN_PLD_RST	EN_EEP_REL_PU	IGN_HC_RST_PPP	IGN_LRST_UPP	IGN_WR_UPP	ALL_CPLD_RST	IGN_HR_U3	IGN_WR_U3	IGN_MPU_RST_U3	IGN_MPU_RST_U2	IGN_MPU_RST_PC	IGN_MPU_RST_PP	IGN_HC_RST_UP	IGN_WRST_UP	EN_HC_RST_PPI	ALL_PO_PDRST	IGN_PERST_PSD	IGN_FRST_AUX_PU	TRIG_FRST

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	Reset USB3 AUX/Main PD Logic (RST_U3_AM_PDL): A reset that is designed to reset all USB3 port AUX + Main power domain logic. This is a debug function. It is called cold reset. A write of 1 to this register will issue a cold reset to USB3 ports. Power Well: SUS
30	0b RW	RESERVED (RSVD): Reserved. Power Well: SUS
29	0b RW	Enable PCIe PIPE Reset As PCIe PHY Reset (EN_PPIPE_PPHY_RST): This bit set to 1 selects the PCIe PIPE reset as a PCIe PHY power on reset. 0 selects the AUX powerup reset as a PCIe PHY powerup reset. Power Well: SUS
28	0b RW	Ensure PIPE Powerdown On PERST# (EN_PPWRDN_PERST): This bit ensures any PERST# being asserted will cause PIPE powerdown state transition to P1. Power Well: SUS
27	0b RW	Disable PERST# Main RST (DIS_PERST_MRST): There is a feature where we only allow PERST# to be treated as a main powerdown reset when it is asserted during the state that is not in D3. This bit disables this feature when it is set to 1. If this bit is set to 1, it means that any PERST# will be treated as a main power domain reset regardless of its Dstate. Power Well: SUS
26	0b RW	Disable PCIe PERST# Host Controller (DIS_PERST_HC): There is a feature where we can disable PCIe PERST# from reset the host controller until power management control module has done its clock switching. This is for a case where PM entered L23 and immediately PERST# asserted. This bit is designed to enable this feature when set to 1. Power Well: SUS
25	0b RW	Enable Fast Simulation Reset Mode (EN_FAST_RST): Enable a fast simulation mode for reset function. This is a feature for GLS Power Well: SUS
24	1b RW	Prevent USB3 Link Down Reset (PREV_U3_LDRST): When set to 1, prevent a reset being generated due to the USB3 port link down condition. Power Well: SUS
23	0b RW	Ignore Main Power Up Reset (IGN_MPU_RST): When set to 1, ignore the main power up reset for USB3 PIPE PHY reset. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
22	1b RW	RESERVED (RSVD_1): Reserved. Power Well: SUS
21	0b RW	Ignore HC Reset USB2 (IGN_HC_RST_U2): When set to '1', ignore HC reset to reset the USB2 Port logic. Power Well: SUS
20	1b RW	Ignore HC Reset USB PHY (IGN_HC_RST_UP_POR): When set to '1', ignore HC reset to the USB PHY power-on reset. Power Well: SUS
19	1b RW	Enable PCIe Link-Down Reset (EN_PLD_RST): Enable a reset due to a PCIe link-down condition. The PCIe link down condition will cause a HC reset linked. If this bit is set 1, the PCIe link down condition will only reset the PCIe core. Power Well: SUS
18	1b RW	Enable EEPROM Reload On Power Up (EN_EEP_REL_PU): When set to '1', enable EEPROM reload on every main power-up. Power Well: SUS
17	1b RW	Ignore HC Reset PCIe PHY PIPE (IGN_HC_RST_PPP): When set to '1', ignore HC reset to the PCIe PHY PIPE reset. Power Well: SUS
16	1b RW	Ignore LTSSM Reset USB PHY PIPE (IGN_LRST_UPP): When set to '1', ignore the LTSSM of USB link state transition caused reset to USB PHY PIPE reset. Power Well: SUS
15	1b RW	Ignore Warm Reset USB PHY Power (IGN_WR_UPP): When set to '1', ignore warm reset the USB PHY power on reset. Power Well: SUS
14	1b RW	Allow Core PCIe Link Down Reset (ALL_CPLD_RST): When set to '1', allow PCIe link down to cause a reset to the rest of the core. Power Well: SUS
13	0b RW	Ignore Hot Reset USB3 (IGN_HR_U3): When set to '1', ignore hot reset to the USB3 port logic. Power Well: SUS
12	0b RW	Ignore Warm Reset USB3 (IGN_WR_U3): When set to '1', ignore warm reset to the USB3 port logic Power Well: SUS
11	0b RW	Ignore Main Power Up Reset USB3 (IGN_MPU_RST_U3): When set to '1', ignore main power up reset to USB3 port logic. Power Well: SUS
10	0b RW	Ignore Main Power Up Reset USB2 (IGN_MPU_RST_U2): When set to '1', ignore main power up reset to USB2 port logic. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
9	0b RW	Ignore Main Power Up Reset PCIe Core (IGN_MPU_RST_PC): When set to '1', ignore main power up reset to PCIe core. Power Well: SUS
8	0b RW	Ignore Main Power Up Reset PCIe PHY (IGN_MPU_RST_PP): When set to '1', ignore main power up reset to PCIe PHY. Power Well: SUS
7	1b RW	Ignore HC Reset USB PHY (IGN_HC_RST_UP): When set to '1', ignore HC reset to the USB PHY. Power Well: SUS
6	1b RW	Ignore Warm Reset USB PHY (IGN_WRST_UP): When set to '1', ignore warm reset to the USB PHY. Power Well: SUS
5	1b RW	Enable HC Reset Per Port Isolation (EN_HC_RST_PPI): Enables the HC reset or per port reset isolation function. Power Well: Core
4	1b RW	Allow Power Off Power Domain Reset (ALL_PO_PDRST): When set to '1', allow main power off condition to trigger a main power domain reset. Power Well: SUS
3	0b RW	Ignore Wait For PERST# During Power Shut Down (IGN_PERST_PSD): When set to '1', ignore waiting for PERST# deassertion during main power shut down. Power Well: SUS
2	0b RW	Ignore Fundamental Reset During AUX Power Up (IGN_FRST_AUX_PU): If this bit is set and a fundamental reset is asserted during AUX power up, then PERST# shall be ignored and a timeout will be allowed to deassert fundamental reset instead. Power Well: SUS
1:0	0h RW	Trigger Fundamental Reset (TRIG_FRST): Writing to bit(1:0) to value of 2'b11 will cause a fundamental reset Power Well: SUS

18.7.151 Super Speed Bandwidth Overload (HOST_BW_OV_SS_REG)—Offset 80C4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80C4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 004A4008h





Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	RESERVED (RSVD): Reserved. Power Well: Core
23:12	014h RW	Per Packet Overhead FS BW (PP_OVRH_FSBW): BW calculation: Overhead per packet for FS BW calculations. see white paper. Power Well: Core
11:0	080h RW	Per Packet Overhead LS BW (PP_OVRH_LSBW): BW calculation: Overhead per packet for LS BW calculations. see white paper. Power Well: Core

18.7.154 System Bandwidth Overload (HOST_BW_OV_SYS_REG)—Offset 80D0h

Default: 00032010h

18.7.156 AUX Power PHY Reset (UPTS_PON_RST_REG)—Offset 80D8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80D8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD								ALL_SW_UP_RST




Bit Range	Default & Access	Field Name (ID): Description
27	0b RW	Allow Engine PERST Fundamental Reset (AL_PERST_FRST): When set to 1 allow engine to treat PERST# as a fundamental reset Power Well: SUS
26	0b RW	Overwrite PCIe P2 to P1 (OVR_PCIE_P2_P1): When set to 1 will overwrite a PCIe powerdown state of P2 to P1. Power Well: SUS
25	0b RW	Set Internal SSV 1 (SET_ISSV_1): When set to 1 set the internal SSV to 1. Power Well: SUS
24	0b RW	Clear Internal SSV 0 (CLR_ISSV_0): When set to 1 clear the internal SSV to 0. Power Well: SUS
23	1b RW	Enable save_restore_enable SW Loading (EN_SRE_SW_LD): This is a bit that enables the save_restore_enable signal being loaded when a software command has set Save bit. This is a debug function. Power Well: SUS
22	0b RW	RESERVED (RSVD_1): Reserved. Power Well: SUS
21	0b RW	Force save_restore 1 (FORCE_SR1): When set to 1, it will force the save_restore flag to 1. This flag is an bit to ensure that we have masked the update during low power state. If software write this bit to 1, it must write it to 0 in order to resume the normal save and restore function. Power Well: SUS
20	0b RW	cfg pcie txreg rd (CPTR): Reserved. Power Well: SUS
19	1b RW	cfg iob drivestrength[1] (CIDS1): Reserved. Power Well: SUS
18	1b RW	cfg iob drivestrength[0] (CIDS0): Reserved. Power Well: SUS
17	0b RW	Enable CFG USB P2 (EN_CFG_UP2): When set to '1' enable cfg usb p2 Power Well: SUS
16	1b RW	cfg clk gate dis (CCGD): Reserved. Power Well: SUS
15	1b RW	Enable CFG RXDET P3 (EN_CFG_RDP3): When set to '1' enable cfg rxdet p3 Power Well: SUS
14	0b RW	Enable CFG PIPE Reset (EN_CFG_PIPE_RST): When set to '1' enable cfg pipe rst Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
13	1b RW	Enable Filter TX Idle (EN_FILT_TX_IDLE): When set to 1 enables a filter function to TX electrical idle signal at PCIe PIPE. We have a filter that will set TXelecidle signal of PCIe PIPE to 1 whenever we are in isolation state or power down transition states. Power Well: SUS
12	1b RW	Enable Host Engine Generate PME (EN_HE_GEN_PME): This is a global switch to enable or not enable the host engine to generate a PME message. Power Well: SUS
11	1b RW	Enable Isolation (EN_ISOL): When set to '1' enable isolation Power Well: SUS
10	1b RW	Enable L1 Caused P2 Overwrite (EN_L1_P2_OVR): Set 1 to enable a new feature. This new feature is designed to use L1 as a state to identify whether we should do P2 Overwrite or not. We used to use P1 state to identify whether or not to invoke P2 overwrite function. Power Well: SUS
9	0b RW	Enable Core Clock Gating (EN_CORE_CG): When set to '1' enable core clock gating based on low power state entered Power Well: SUS
8	0b RW	Enable PHY Status Timeout (EN_PHY_STS_TO): When set to '1' enable PHY status timeout function which is designed to cover the PCIePHY issue that we may have not able to detect the PHY status toggle. Power Well: SUS
7	1b RW	Ignore aux_pm_en PCIe Core (IGN_APE_PC): When set to '1' ignore the aux_pm_en reg from PCIe core to continue the remote wake/clock switching support Power Well: SUS
6	0b RW	Enable P2 Overwrite P1 (EN_P2_OVR_P1): When set to '1' enable P2 overwrite P1 when PCIe core has indicated the transition from P0 to P1. This is to enable entering the even lower power state. Power Well: SUS
5	1b RW	Enable P2 Remote Wake (EN_P2_REM_WAKE): When set 1 '1' enable the remote wake function by allowing P2 clock/switching and P2 entering Power Well: SUS
4:1	0h RW	Forced PM State (FORCED_PM_STATE): Reserved. Power Well: SUS
0	0b RW	Initiate Force PM State (INIT_FPMS): When set to '1' force PM state to go to the state indicated in bit 4:1 Power Well: SUS

18.7.158 Battery Charge (BATTERY_CHARGE_REG)—Offset 80E4h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80E4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EN_DS_BC	RSVD						EN_P3_BC	EN_P2_BC
							EN_P1_BC	EN_P0_BC

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	Enable DM_SRC Battery Charge (EN_DS_BC): 1 - Always enable battery charge DM_SRC if not connected. Don't wait for portable device detect. (spec. ver. 1.2) 0 - Battery charge spec ver. 1.1. Power Well: SUS
30:4	0000000h RO	RESERVED (RSVD): Reserved. Power Well: Core
3	0b RW	Enable Port 3 Battery Charging (EN_P3_BC): 0 - Battery charging disabled (Physical Port #3) 1 - Battery charging enabled (Physical Port #3) Power Well: SUS
2	0b RW	Enable Port 2 Battery Charging (EN_P2_BC): 0 = Battery charging disabled (Physical Port #2) 1 = Battery charging enabled (Physical Port #2) Power Well: SUS
1	0b RW	Enable Port 1 Battery Charging (EN_P1_BC): 0 = Battery charging disabled (Physical Port #1) 1 = Battery charging enabled (Physical Port #1) Power Well: SUS
0	0b RW	Enable Port 0 Battery Charging (EN_P0_BC): 0 = Battery charging disabled (Physical Port #0) 1 = Battery charging enabled (Physical Port #0) Power Well: SUS

18.7.159 Port Watermark (HOST_CTRL_WATERMARK_REG)—Offset 80E8h


Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80E8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h



Bit Range	Default & Access	Field Name (ID): Description
31:16	0080h RW	RBUF water mark (RBUF_WM): Reserved. Power Well: Core
15:0	0080h RW	XBUF water mark (XBUF_WM): Reserved. Power Well: Core

Access Method

Offset: [MBAR] + 80ECh**MBAR Type:** PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 18010600h

Bit Range	Default & Access	Field Name (ID): Description
31:27	03h RW	Force LTSSM State (FORCE_LTSSM_ST): LTSSM state to be forced This value is for test purpose only. Power Well: Core
26	0b RW	Direct Link LTSSM State (DL_LTSSM_ST): 0 = Normal operation mode 1 = Direct link to a specific state specified by bit 31:27 This bit is for test purposes only. It shall be written 0 in normal operation mode. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Direct Link To U0 (DL_U0): 0 = Normal operation mode 1 = Direct link to U0 This bit is for test purposes only. It shall be written 0 in normal operation mode. Power Well: Core
24:21	0h RW	Forced Compliance Pattern (FORCED_CMP_PAT): Compliance pattern to be forced to enter compliance mode This value is for test purpose only. Power Well: Core
20	0b RW	Enable Link Error Slave Count (EN_LES_CNT): 0 = Disable link error slave count 1 = Enable link error slave count Power Well: Core
19:17	0h RW	Debug Mode Select (DEBUG_MD_SEL): Reserved. Power Well: Core
16:15	2h RW	PHY Low Power Latency (PHY_LP_LAT): This field defines the latency to drive the PHY to enter low power mode. 0 = 4 cycles 1 = 8 cycles 2 = 16 cycles 3 = 32 cycles Power Well: Core
14:12	0h RW	Link Recovery Minimum Time (LR_MIN_TM): This value defines the minimum time for the link to stay in Recovery.Active other than from U3. The granularity is 128us. Power Well: Core
11:9	3h RW	Link Polling Minimum Time (LP_MIN_TM): This value defines the minimum time for the link to stay in Polling.Active and Recovery.Active from U3. The granularity is 128us. Power Well: Core
8	0b RW	Force Link Accept PM Command (FORCE_LA_PMC): 0 = Normal operation mode 1 = Force link to accept power management command Power Well: Core
7	0b RW	Direct Link Recovery U0 (DL_REC_U0): 0 = Normal operation mode 1 = Direct link to Recovery from U0 Power Well: Core
6	0b RW	Link Fast Training Mode (LINK_FTM): 0 = Normal operation mode 1 = Link fast training mode This bit should be written 0 in normal operation. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	Disable Link Scrambler (DIS_LINK_SCRAM): 0 = Enable link scrambler 1 = Disable link scrambler Power Well: Core
4	0b RW	Direct Link U3 From U0 (DL_U3_U0): 0 = Normal operation mode 1 = Direct link to U3 from U0 This bit is for test purposes only. It shall be written 0 in normal operation mode. Power Well: Core
3	0b RW	Direct Link U3 From U0 (DL_U2_U0): 0 = Normal operation mode 1 = Direct link to U2 from U0 This bit is for test purposes only. It shall be written 0 in normal operation mode. Power Well: Core
2	0b RW	Direct Link U3 From U0 (DL_U1_U0): 0 = Normal operation mode 1 = Direct link to U1 from U0 This bit is for test purposes only. It shall be written 0 in normal operation mode. Power Well: Core
1	0b RW	Enable Link Loopback Master Mode (EN_LINK_LB_MAST): 0 = Disable link loopback master mode 1 = Enable link loopback master mode Power Well: Core
0	0b RW	Disable Link Compliance Mode (DIS_LINK_CM): 0 = Enable link compliance mode 1 = Disable link compliance mode Power Well: Core

18.7.161 USB2 Port Link Control 1 (USB2_LINK_MGR_CTRL_REG1)— Offset 80F0h

This set of registers is used to control the USB set of timers. They are spread over 4 registers each 32 bits wide.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80F0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 310003A0h

31	28	24	20	16	12	8	4	0
0	0	1	1	0	0	0	1	0
FSL_S_SEQ_DIS_DEL_7_0								
RSVD								
EN_DETECT_NOMINAL_PKT_EOP								
DIS_CHIRP_RESPONSE								
DIS_192B_LIM								
EXT_FSL_S_DIS								
UTMI_RST_SEL								
DIS_HS_DIS_WIN								
DIS_PERR_DET								
DIS_PF_IOUT								
DRV_RESK_FSL_S_SER								
EN_U2_DROP_PING				1				
EN_U2_FORCE_PING				0				
EN_U2_AUTO_PING				1				
DIS_PHY_SUSM				0				
UTMI_INT_CG_DIS				0				
DIS_PSUSM_DS				0				
FORCE_PHY_RST				0				
U2_ACC_SIM_TTM				0				

Bit Range	Default & Access	Field Name (ID): Description
31:24	31h RW	FS/LS Mode SE0 Disconnect Delay[7:0] (FSLS_SE0_DIS_DEL_7_0): # of microseconds of SE0 in FS/LS mode to register disconnect had occurred. Power Well: SUS
23:18	00h RW	Reserved (RSVD): Reserved. Power Well: SUS
17	0b RW	EN_DETECT_NOMINAL_PKT_EOP: 0 = Detect minimal packet EOP. 1 = Detect nominal packet EOP. Power Well: SUS
16	0b RW	Disable Chirp Response (DIS_CHIRP_RESPONSE): 0 = Normal 1 = Force full speed on host ports (disable chirp response) Power Well: SUS
15	0b RW	Disable 192 Byte Limit Check (DIS_192B_LIM): 0 = Enforce 192 byte limit on complete-split INs. Treat any packet) 192 as babble case. 1 = Disable 192 byte limit check. Power Well: SUS
14	0b RW	External Provided FS/LS Disconnect (EXT_FSLS_DIS): 0 = Internal FS/LS Disconnect from linestate(1:0) 1 = External provided FS/LS Disconnect from hostdisconnect input Power Well: SUS
13:12	0h RW	UTMI Reset Source Select (UTMI_RST_SEL): Select UTMI Reset Source (FRD UTMI Reset Only) 00 = HCRreset or Force PHY Reset or internal reset after disconnect/suspend for restart (default) 01,11 = UTMI reset = ~UTMI suspendm 10 = UTMI reset = ~UTMI suspendm and synchronization to port clk. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
11	0b RW	Disable HS Disconnect Window (DIS_HS_DIS_WIN): 0 = Enable HS Disconnect Window Function 1 = Disable HS Disconnect Window Function Power Well: SUS
10	0b RW	Disable Port Error Detection (DIS_PERR_DET): 0 = Enable Port Error Detection (default) 1 = Disable Port Error Detection Power Well: SUS
9	1b RW	Disable Peek Function for ISO-OUT (DIS_PF_IOUT): 0 = Enable Peek function for ISO-OUT (default) 1 = Disable Peek function for ISO-OUT Power Well: SUS
8	1b RW	Drive Resume-K FS/LS Serial Interface (DRV_RESK_FSLS_SER): 0 = Drive Resume-K on parallel Interface 1 = Drive Resume-K directly on FS/LS Serial Interface (default) Power Well: SUS
7	1b RW	Enable USB2 Drop-Ping (EN_U2_DROP_PING): 0 = Disable Drop-Ping Function in USB2 Protocol (default) 1 = Enable Drop-Ping Function in USB2 Protocol Power Well: SUS
6	0b RW	Enable USB2 Force-Ping (EN_U2_FORCE_PING): 0 = Disable Force-Ping Function in USB2 Protocol (default) 1 = Enable Force-Ping Function in USB2 Protocol Power Well: SUS
5	1b RW	Enable USB2 Auto-Ping (EN_U2_AUTO_PING): 0 = Disable Auto-Ping Function 1 = Enable Auto-Ping Function in USB2 Protocol (default) Power Well: SUS
4	0b RW	Disable PHY SuspendM (DIS_PHY_SUSM): 0 = PHY is suspend=U3,U2,disconnect (default) 1 = Disable PHY SuspendM in All States Power Well: SUS
3	0b RW	UTMI Internal Clock Gate Disable (UTMI_INT_CG_DIS): 0 = Normal operation (internal clock gated in U2,U3,disconnect) 1 = UTMI Internal Clock Gate Disable Power Well: SUS
2	0b RW	Disable PHY SuspendM in Disconnect State (DIS_PSUSM_DS): 0 = PHY is suspendM=0 in Disconnect State (default) 1 = Disable PHY SuspendM in Disconnect State Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
1	0b RW	Force PHY Reset (FORCE_PHY_RST): 0 = Normal Operation (default) 1 = Force PHY Reset Power Well: SUS
0	0b RW	USB2 Accelerated Simulation Timing (U2_ACC_SIM_TIM): 0 = Normal Operation (default - FPGA/ASIC) 1 = USB2 Accelerated Simulation Timing (default - simulation) Power Well: SUS

18.7.162 USB2 Port Link Control 2 (USB2_LINK_MGR_CTRL_REG2)—Offset 80F4h

This set of registers is used to control the USB set of timers. They are spread over 4 registers each 32 bits wide.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80F4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 80C40620h

31	28				24				20				16				12				8				4				0				
1	0	0	0	0	0	0	0	0	1	1	0	0	0	1	0	0	0	0	0	0	0	1	1	0	0	0	0	1	0	0	0	0	0
TOT_RST_DUR_0																																	
	CHIRPK_DUR																																



Bit Range	Default & Access	Field Name (ID): Description
4:0	00h RW	FS/LS Mode SE0 Disconnect Delay[12:8] (FSLS_SE0_DIS_DEL_12_8): # of microseconds of SE0 in FS/LS mode to register disconnect had occurred. Power Well: SUS

18.7.163 USB2 Port Link Control 3 (USB2_LINK_MGR_CTRL_REG3)– Offset 80F8h

This set of registers is used to control the USB set of timers. They are spread over 4 registers each 32 bits wide.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80F8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: F865FB6Bh

31	28	24	20	16	12	8	4	0												
1	1	1	1	1	0	0	0	0	0	1	1	0	0	1	0	1	1	0	1	1
U2_IGN_LS_DUR_3_0				U3_IGN_LS_DUR								TOT_RST_DUR_15_1								

Bit Range	Default & Access	Field Name (ID): Description
31:28	Fh RW	U2 Entry Ignore Linestate Changes Duration[3:0] (U2_IGN_LS_DUR_3_0): # of microseconds after entering U2, linestate changes are ignored as bus settles Power Well: SUS
27:15	10CBh RW	U3 Entry Ignore Linestate Changes Duration (U3_IGN_LS_DUR): # of microseconds after entering U3, linestate changes are ignored as bus settles Power Well: SUS
14:0	6B6Bh RW	Total Reset Duration[15:1] (TOT_RST_DUR_15_1): # of microseconds for total reset duration Power Well: SUS

18.7.164 USB2 Port Link Control 4 (USB2_LINK_MGR_CTRL_REG4)—Offset 80FCh

This set of registers is used to control the USB set of timers. They are spread over 4 registers each 32 bits wide.

Access Method



Bit Range	Default & Access	Field Name (ID): Description
31:22	000h RO	RESERVED (RSVD): Reserved. Power Well: Core
21:9	0040h RW	U2 Detect Remote Wake Delay (U2D_RWAKE_DEL): #of microseconds after detecting U2 remote wake condition to reflect K Power Well: SUS
8:0	003h RW	U2 Entry Ignore Linestate Changes Duration[12:4] (U2_IGN_LS_DUR_12_4): # of microseconds after entering U2, linestate changes are ignored as bus settles Power Well: SUS

18.7.165 Bandwidth Calc Control (HOST_CTRL_BW_CTRL_REG)—Offset 8100h

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved (RSVD): Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
15:0	8008h RW	Reserved (RSVD_1): Reserved. Power Well: Core

18.7.166 Host Interface Control (HOST_IF_CTRL_REG)—Offset 8108h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8108h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Rsvd1								HOSTIF

Bit Range	Default & Access	Field Name (ID): Description
31:1	00000000h RW	Rsrd1: Reserved. Power Well: Core
0	1b RW	Host IF (HOSTIF): Reserved. Power Well: Core

18.7.167 Bandwidth Overload Burst (HOST_BW_OV_BURST_REG)—Offset 810Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 810Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00008020h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				PB_OVRH_SBW				PB_OVRH_SSBW



Type: Memory Mapped I/O Register
(Size: 64 bits)

Offset: [MBAR] + 8128h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

6 3	6 0	5 6	5 2	4 8	4 4	4 0	3 6	3 2	2 8	2 4	2 0	1 6	1 2	8	4	0
0000	1111	0100	0010	0101	0010	1000	0101	0000	0101	0110	0100	0111	1111	0100	0010	
RSVD		PCIE_MAX_BW			TT_MAX_BW			FSLS_MAX_BW			HS_MAX_BW			SS_MAX_BW		

Intel Atom® Processor E3800 Product Family
Datasheet
2310



Bit Range	Default & Access	Field Name (ID): Description
23:12	647h RW	HS Max BW Units (HS_MAX_BW): Max. Number of BW units for HS ports. (denominator in 80% calculation) Power Well: Core
11:0	F42h RW	SS Max BW Units (SS_MAX_BW): Max. Number of BW units for SS ports. (denominator in 90% calculation) Power Well: Core

18.7.169 USB2 Linestate Debug (LINESTATE_DEBUG_REG)—Offset 8130h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8130h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																											
0				0				0				0				0				0				0				0				0																											
RSVD				P14_UTMI_LS				P13_UTMI_LS				P12_UTMI_LS				P11_UTMI_LS				P10_UTMI_LS				P9_UTMI_LS				P8_UTMI_LS				P7_UTMI_LS				P6_UTMI_LS				P5_UTMI_LS				P4_UTMI_LS				P3_UTMI_LS				P2_UTMI_LS				P1_UTMI_LS			

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RO	RESERVED (RSVD): Reserved. Power Well: Core
27:26	0h RO	Port 14 UTMI Linestate (P14_UTMI_LS): Reserved. Power Well: Core
25:24	0h RO	Port 13 UTMI Linestate (P13_UTMI_LS): Reserved. Power Well: Core
23:22	0h RO	Port 12 UTMI Linestate (P12_UTMI_LS): Reserved. Power Well: Core
21:20	0h RO	Port 11 UTMI Linestate (P11_UTMI_LS): Reserved. Power Well: Core
19:18	0h RO	Port 10 UTMI Linestate (P10_UTMI_LS): Reserved. Power Well: Core
17:16	0h RO	Port 9 UTMI Linestate (P9_UTMI_LS): Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
15:14	0h RO	Port 8 UTMI Linestate (P8_UTMI_LS): Reserved. Power Well: Core
13:12	0h RO	Port 7 UTMI Linestate (P7_UTMI_LS): Reserved. Power Well: Core
11:10	0h RO	Port 6 UTMI Linestate (P6_UTMI_LS): Reserved. Power Well: Core
9:8	0h RO	Port 5 UTMI Linestate (P5_UTMI_LS): Reserved. Power Well: Core
7:6	0h RO	Port 4 UTMI Linestate (P4_UTMI_LS): Reserved. Power Well: Core
5:4	0h RO	Port 3 UTMI Linestate (P3_UTMI_LS): Reserved. Power Well: Core
3:2	0h RO	Port 2 UTMI Linestate (P2_UTMI_LS): Reserved. Power Well: Core
1:0	0h RO	Port 1 UTMI Linestate (P1_UTMI_LS): Reserved. Power Well: Core

18.7.170 USB2 Protocol Gap Timer (USB2_PROTOCOL_GAP_TIMER_REG)—Offset 8134h

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

Offset: [MBAR] + 8134h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 000C3C640C05140Ch

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	1	1	0	0	1	1	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0
RSVD			LSTX_GAP_TIMER		LSRX_GAP_TIMER		LS_GAP_TIMER		FS_GAP_TIMER		HSRX_GAP_TIMER		HSTXSOF_GAP_TIMER		HSTX_GAP_TIMER	



Type: Memory Mapped I/O Register
(Size: 32 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

31	28	24	20	16	12	8	4	0			
0	0	0	0	1	0	1	0	0			
0	0	0	0	0	0	0	1	0			
0	0	0	0	0	1	1	0	0			
1	0	0	1	1	0	0	1	1			
0	0	0	0	1	0	0	0	1			
0	0	0	0	0	0	0	0	0			
ETH				BPSAW				BPSMID			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0ah RW	Engine Idle Hysteresis (EIH): This register controls the min. idle span that has to be observed from the engine idle indicators before the power state flags (xhc*_idle) will indicate a 1. Power Well: Core
23:12	019h RW	Backbone PLL Shutdown Advance Wake (BPSAW): This register controls the time before the next scheduled transaction where the Backbone PLL request will assert. - Register Format: - Bits [11:7] # of 125us uframes - Bits [6:0] # of microseconds (0-124) Power Well: Core
11:0	132h RW	Backbone PLL Shutdown Min. Idle Duration (BPSMID): The sum of this register plus the Backbone PLL Shutdown Advance Wake form to a Total Idle time. When the next scheduled periodic transaction is after present time + Total Idle, the Backbone PLL request will de-assert, allowing the PLL to shutdown. Register Format: - Bits [11:7] # of 125us uframes - Bits [6:0] # of microseconds (0-124) Power Well: Core

18.7.173 Power Scheduler Control-2 (PWR_SCHED_CTRL2)—Offset 8144h

These bit enable by EP type those EPs classes that are considered for determining next periodic active interval for pre-wake of the periodic_active signal. EP classes that are disabled may never be observed in setting of the periodic_active signal.



Bit Range	Default & Access	Field Name (ID): Description
0	1b RW	SS ISO-IN Alarm (SS_ISO_IN_ALARM): Reserved. Power Well: Core

18.7.174 Latency Tolerance Control 0 (HOST_IF_LAT_TOL_CTRL_REG0)—Offset 8150h

The Latency Tolerance Control Register is used by SW to control which BELT is returned when this register is read. SW shall write to this register to program a Slot-ID, Port-ID and BELT Select to determine which BELT is selected. When this register is read the selected BELT is returned.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8150h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BELT_SEL	Rsvd1				PORT_SEL	Rsvd	BELTV	SLOT_SEL

Bit Range	Default & Access	Field Name (ID): Description
31:30	0h WO	BELT Select (BELT_SEL): This field determines what value will be selected to read back from SW when reading this register. 0 = Returns the SW programmed Latency Tolerance Value 1 = Returns the Lowest BELT in the Host 2 = Returns the BELT for the requested Slot-ID (Slot Select) 3 = Returns the BELT for the requested Port-ID (Port Select) Power Well: Core
29:17	0h RO	Rsvd1: Reserved. Power Well: Core
16	0h WO	Port Select (PORT_SEL): Used to select the BELT for a given Port # when the BELT Select is programmed to select the Port-ID (this field is 0 based) Power Well: Core
15:12	0h RO	Rsvd: Reserved. Power Well: Core
11:5	0h RO	BELT Value (BELTV): Value of selected BELT is return in this field Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
4:0	00h RW	Slot Select (SLOT_SEL): Reads will return: BELT Value (BELTV) [4:0]: Value of selected BELT is return in this field Writes will control : Slot Select (): Used to select the BELT for a given Slot # when the BELT Select is programmed to select the Slot-ID (this field is zero based) Power Well: Core

18.7.175 AUX Power Management Control (AUX_CTRL_REG2)—Offset 8154h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8154h


MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 01390206h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0	RSVD	EN_L1_EXIT_NOTIF_PCIE	DIS_PL3_ON_DISCONNECT	TREAT_IDLE_AS_TS2_IN_LTSSM_WAIT_4_TS2	DIS_P2_OVERWRITE_DUE2_D3HOT	ENABLE_AUTO_U3_ENTRY_FROM_U2_U3	DIS_LINKDOWN_RST_DURING_LOW_POWER	EN_EXIT_DEEP_SLEEP_IF_PCIE_IN_P0
								U2_EXIT_LFPS_TIMER_VALUE
								EN_EXIT_DEEP_SLEEP_ON_USB_PORT_WAKEUP
								P3_ENTRY_TIMEOUT
								EN_U2_P3
								FINE_DM_SEL
								EN_LP_CORE_CG
								DIS_U3_PORT_SCE
								DEB_MODE_SEL
								EN_AWAK_NIDLE
								EN_PMC_P1_EXIT_P2
								EN_PP_CLK_ISOL
								EN_P2OVRP1_ADET

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RW	RESERVED0 (RSVD0): Reserved. Power Well: SUS
27:25	0h RW	RESERVED (RSVD): Reserved. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
24	1b RW	Enable L1 exit notification to SNPS PCIe core (EN_L1_EXIT_NOTIF_PCIE): This bit enables a L1 exit notification to SNPS PCIe core. There is a case where USB ports have waked up and AUX PM module has started the wakeup process. The AUX PM control state got into a wait for P0 state because it needs to wait until PCIe core to signal powerdown state change. Due to the fact that the core is in D3Hot, there is no run_stop bit set such that no internal interrupt will be fired. This causes the LTSSM of PCIe stayed in L1 even though AUX PM has known that it needs an L1 exit. This bit works together with bit21 of this register. 1 = enables this feature 0 = disables this feature. Power Well: SUS
23	0b RW	DISABLE PLC ON DISCONNECT (DIS_PLC_ON_DISCONNECT): 1 = do not assert PLC for disconnection 0 = assert PLC for disconnection Power Well: SUS
22	0b RW	TREAT_IDLE_AS_TS2_IN_LTSSM_WAIT_4_TS2: This bit enables a feature in PCIe core LTSSM to treat IDLE received as TS2 when LTSSM is in wait for TS2 receive state. This is a function requested from PHY where it is possible to not able to receive TS2 without error. 1 = treat Logic IDLE as TS2 received when in some PCIe LTSSM state. 0 = disable this feature. Power Well: SUS
21	1b RW	Disable p2 overwrite due to the D3HOT where PCIe core enters the L1 (DIS_P2_OVERWRITE_DUE2_D3HOT): We added a feature where if PCIe core LTSSM enters L1 due to the D3hot, the aux PM control will not start a P2 overwrite function in anticipating for the next L23 enter. 1 = disables p2 overwrite due to the D3HOT where PCIe core enters the L1. 0 = enables P2 overwrite even if we are in D3Hot. Power Well: SUS
20	1b RW	Enable the port to enter U3 automatically when in U1/U2 (ENABLE_AUTO_U3_ENTRY_FROM_U2_U3): 1 = enables the port to enter U3 automatically when in U1/U2 0 = disables the port to enter U3 automatically when in U1/U2 Power Well: SUS
19	1b RW	No linkdown reset is issued during low power state (DIS_LINKDOWN_RST_DURING_LOW_POWER): No linkdown reset is issued during low power state. Power Well: SUS
18	0b RW	EN_EXIT_DEEP_SLEEP_IF_PCIE_IN_P0: This bit enables a feature in AUX PM module where if PCIe core LTSSM is in P0 for a duration of time, we will exit the deep sleep state. This is for failure control in case. 1 = enable this feature 0 = disable this feature Power Well: SUS
17	0b RW	U2_EXIT_LFPS_TIMER_VALUE: This bit selects U2 exit LFPS timer value. 0 = 320ns 400ns in 25MHz domain 1 = 240ns 320ns in 25MHz domain Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	EN_EXIT_DEEP_SLEEP_ON_USB_PORT_WAKEUP: This bit enables a function that AUX PM module exits from the deep sleep state due to the USB ports wakeup level signal. We have added this feature where USB ports will generated a wakeup level signal to wakeup the AUX PM module if it is in deep sleep state and this level signal will be cleared if the change bits are updated by software. 1 = enables this function 0 = disables this function which means that a wakeup pulse generated from each USB PortSC event will wake up the AUX PM module from deep sleep if the D3 state is programmed. Power Well: SUS
15:14	0h RW	P3_ENTRY_TIMEOUT: This field defines the timeout value to enter P3 mode in U2. 00 = 7us 8us 01 = 511us 512us 10 = disables the timer (0us) 11 = disables the timer (0us) Power Well: SUS
13	0b RW	Enable U2 P3 Mode (EN_U2_P3): 0 = Disable U2 P3 mode 1 = Enable U2 P3 mode Power Well: SUS
12:11	0h RW	Fine Debug Mode Select (FINE_DM_SEL): Reserved. Power Well: SUS
10	0b RW	Enable Low Power State Based Core Clock Gating (EN_LP_CORE_CG): When set to '1', enable core clock gating based on low power state entered Power Well: SUS
9	1b RW	Disable USB3 Port Status Changed Event (DIS_U3_PORT_SCE): 0 = Enable USB3 port status change event generation if any change bit is not cleared 1 = Disable USB3 port status change event generation if any change bit is not cleared Bit 12 default 0 Power Well: SUS
8:4	00h RW	Debug Mode Select Register (DEB_MODE_SEL): Reserved. Power Well: SUS
3	0b RW	Enable Auto Wakeup Non-IDLE (EN_AWAK_NIDLE): When set to 1, enables the auto wakeup function when engine has identified non IDLE condition. Power Well: SUS
2	1b RW	Enable PM Control P1 Exit P2 (EN_PMC_P1_EXIT_P2): When set to 1, enables the PM control module to transition to P1 instead of P0 upon exit from P2. Power Well: SUS
1	1b RW	Enable PCIe PIPE CLK Isolation (EN_PP_CLK_ISOL): When set to 1, enables the PCIe PIPE CLK to be isolated when main power is removed. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Enable P2 Overwrite P1 Allowed Detect (EN_P2OVRP1_ADET): When set to 1, enables a function that can detect whether or not enable P2 overwrite P1 function. The condition to get to P2 overwrite is when engine is in idle conditions. This means that there is no ISO EP pending. Power Well: SUS

18.7.176 USB2 PHY Power Management Control (USB2_PHY_PMC)—Offset 8164h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8164h


MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 000000FCh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							EN_CMDM_TXRXB	EN_TTE_TXRXB
							EN_IDMA_TXRXB	EN_ODMA_TXRXB
							EN_TRM_TXRXB	EN_SCH_TXRXB
							EN_RXB_CD	EN_TXB_CD

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved (RSVD): Reserved. Power Well: Core
7	1b RW	EN_CMDM_TXRXB: Enable Command Manager Active indication for Tx/Rx Bias circuit HS Phy PM Policy Power Well: Core
6	1b RW	EN_TTE_TXRXB: Enable TTE Active indication for Tx/Rx Bias circuit HS Phy PM Policy Power Well: Core
5	1b RW	EN_IDMA_TXRXB: Enable IDMA Active indication for Tx/Rx Bias circuit HS Phy PM Policy Power Well: Core
4	1b RW	EN_ODMA_TXRXB: Enable ODMA Active indication for Tx/Rx Bias circuit HS Phy PM Policy Power Well: Core
3	1b RW	EN_TRM_TXRXB: Enable Transfer Manager Active indication for Tx/Rx Bias circuit HS Phy PM Policy Power Well: Core



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								RSVD
								USB SRAM PCF

Bit Range	Default & Access	Field Name (ID): Description
31:1	00000000h RO	Reserved (RSVD): Reserved. Power Well: Core
0	0b RW	USB SRAM power gating enable (USB_SRAM_PGE): When set enables power gating on USB ports. Usage of this bit is further qualified with xHCI SRAM Dynamic Power Gating Disable fuse. If the fuse disables dynamic power gating, setting this bit to 1 shall not enable power gating feature. This bit always returns the value that was written to it irrespective of the setting of xHCI SRAM Dynamic Power Gating Disable fuse. Power Well: Core

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 816Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000400h

31	28				24				20				16				12				8				4				0											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0									
RSVD																												PARUSB3_ENG_GEN	RSVD1	USB3_AC_CGE	RX_DT_ACG	U2R_BM_CG	FTCGPU2E	USB2_PC_TE	XHCI_AC_GE	XHCI_APMB_CGE	USB3_AC_TGE	USB3_AP_CGE	MPP_AC_GEU2	MPP_AC_GE_DDU3
																												PARUSB3_LINK_GEN												
																												PARUSB2_CLK_GEN												
																												USHIP_PCGEN												

Bit Range	Default & Access	Field Name (ID): Description
31:20	000h RO	Reserved (RSVD): Reserved.
19	0b RW	USB3 Partition Engine/Link trunk gating Enable (PARUSB3_ENG_GEN): When set to 1 enables gating of the SOSC trunk to the XHCI engine and link in the PARUSB3 partition. Power Well: SUS
18	0b RW	USB3 Partition Frame Timer trunk gating Enable (PARUSB3_LINK_GEN): When set to 1 enables gating of the SOSC trunk to the Frame timer in the PARUSB3 partition. Power Well: SUS
17	0b RW	USB2 link partition clock gating enable (PARUSB2_CLK_GEN): When set to 1 enables gating of the SOSC trunk to the USB2 link and Phy logic in the PARUSB2 partition. Power Well: SUS
16	0b RW	USB2/USHIP 12.5 MHz partition clock gating enable (USHIP_PCGEN): When set to 1 enables gating of the 12.5 MHz SOSC trunk to the USB2 and USHIP logic in the PARUSB2 partition. Power Well: SUS
15	0b RO	Reserved1 (RSVD1): Reserved
14	0b RW	USB3 Port Aux/Core clock gating enable (USB3_AC_CGE): When set, allows the aux_cclk clock into the USB3 port to be gated when conditions are met. Usage of this bit is further qualified with xHC Dynamic Clock Gating Disable fuse. If the fuse disables dynamic clock gating, Aux clock gating will not be enabled either. This bit always returns the value that was written to it, irrespective of the setting of xHC Dynamic Clock Gating Disable fuse. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
13:12	0h RW	Rx Detect Timer when port Aux Clock is Gated (RX_DT_ACG): This field defines the value of the timer used to perform Rx Detect when port Aux Clock has been gated. 0x0 = 100ms 0x1 = 12ms - Others = Reserved Note: This timer shall use the Fast Training Timer Tick (about 1us tick) for simulation purposes. For Fast Training mode, the above timeouts will become about 11us and about 100us, +/- implementation uncertainty, respectively. Power Well: SUS
11:8	4h RW	U2 Residency Before ModPHY Clock Gating (U2R_BM_CG): Before gating ModPHY Aux clock, Host Controller shall wait for this time in U2. This time is meant to ensure that the attached device has entered U2 as well. 0x0 = 1us 0x1 = 128us 0x2 = 256us 0x3 = 512us 0x4 = 640us 0x5 = 768us 0x6 = 896us 0x7 = 1024us - Others = Reserved Note: This counter shall start counting once pipe has entered PS3 state in response to link in U2. Power Well: SUS
7	0h RW	Frame Timer Clock Gating Ports in U2 Enable (FTCGPU2E): This bit, when set, allows Host Controller to gate the clock to the Frame Timer when ports are in U2. Power Well: SUS
6	0b RW	USB2 port clock throttle enable (USB2_PC_TE): When set, allows the Aux clock into the USB2 ports to be throttled when conditions allow. Power Well: SUS
5	0b RW	XHCI Engine Aux clock gating enable (XHCI_AC_GE): When set, allows the aux clock into the XHCI engine to be gated when idle. Usage of this bit is further qualified with xHC Dynamic Clock Gating Disable fuse. If the fuse disables dynamic clock gating, Aux clock gating will not be enabled either. This bit always returns the value that was written to it irrespective of the setting of xHC Dynamic Clock Gating Disable fuse. Power Well: SUS
4	0b RW	XHCI Aux PM block clock gating enable (XHCI_APMB_CGE): When set, allows the aux clock into the Aux PM block to be gated when idle. Usage of this bit is further qualified with xHC Dynamic Clock Gating Disable fuse. If the fuse disables dynamic clock gating, Aux clock gating will not be enabled either. This bit always returns the value that was written to it irrespective of the setting of xHC Dynamic Clock Gating Disable fuse. Power Well: SUS
3	0b RW	USB3 Aux Clock Trunk Gating Enable (USB3_AC_TGE): When set, allows Aux Clock Trunk feeding to USB3.0 ports to be gated when port Aux clock is gated at all USB3.0 ports and all USB3.0 modPHY instances. Usage of this bit is further qualified with xHC Dynamic Clock Gating Disable fuse. If the fuse disables dynamic clock gating, Aux clock gating will not be enabled either. This bit always returns the value that was written to it irrespective of the setting of xHC Dynamic Clock Gating Disable fuse. Power Well: SUS

18.7.179 USB LPM Parameters (USB_LPM_PARAM)—Offset 8170h

Bit Range	Default & Access	Field Name (ID): Description
2	0b RW	USB3 Port Aux/Port clock gating enable (USB3_AP_CGE): When set, allows the aux_pclk clock into the USB3 port to be gated when conditions are met. Usage of this bit is further qualified with xHC Dynamic Clock Gating Disable fuse. If the fuse disables dynamic clock gating, Aux clock gating will not be enabled either. This bit always returns the value that was written to it irrespective of the setting of xHC Dynamic Clock Gating Disable fuse. Power Well: SUS
1	0b RW	ModPHY port Aux clock gating enable in U2 (MPP_AC_GEU2): When set, allows the aux clock into the ModPhy to be gated when Link is in U2 and pipe has been in PS3 for at least the time defined by U2 Residency Before ModPHY Clock Gating field. Usage of this bit is further qualified with xHC Dynamic Clock Gating Disable fuse. If the fuse disables dynamic clock gating, Aux clock gating will not be enabled either. This bit always returns the value that was written to it irrespective of the setting of xHC Dynamic Clock Gating Disable fuse. Power Well: SUS
0	0b RW	ModPHY port Aux clock gating enable in Disconnected, U3 or Disabled (MPP_AC_GE_DDU3): When set, allows the aux clock into the ModPHY to be gated when Link is in Disconnected, U3 or Disabled state. Usage of this bit is further qualified with xHC Dynamic Clock Gating Disable fuse. If the fuse disables dynamic clock gating, Aux clock gating will not be enabled either. This bit always returns the value that was written to it irrespective of the setting of xHC Dynamic Clock Gating Disable fuse. Power Well: SUS

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8170h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00090032h

31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	1	0
RSVD				MIN_U3E_LFPS_D	MIN_U2_ELFPs_D	XHCI_MAX_PING_LFPS	RSVD_1	XHCI_BESL_HIRD_DT

Bit Range	Default & Access	Field Name (ID): Description
31:22	000h RO	Reserved (RSVD): Reserved. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
21:19	001b RW	Min U3 Exit LFPS Duration (MIN_U3E_LFPS_D): This field defines the minimum duration of LFPS driven by Host Controller upon U3 exit LFPS handshake. Note that there is an uncertainty of +-16us in actual duration driven by the Host Controller. • 0b000 = 96us • 0b001 = 160us • 0b010 = 224us • 0b011 = 288us • 0b100 = 352us • 0b101 = 416us • 0b110 = 480us • 0b111 = 544us Power Well: SUS
18:16	001b RW	Min U2 Exit LFPS Duration (MIN_U2_ELFPS_D): This field defines the minimum duration of LFPS driven by Host Controller upon U2 exit LFPS handshake. Note that there is an uncertainty of +-16us in actual duration driven by the Host Controller. • 0b000 = 96us • 0b001 = 160us • 0b010 = 224us • 0b011 = 288us • 0b100 = 352us • 0b101 = 416us • 0b110 = 480us • 0b111 = 544us Power Well: SUS
15	0b RW	Max PING LFPS Rx Detection (XHCI_MAX_PING_LFPS): This field defines the maximum timing for PING LFPS. If an incoming LFPS will be considered a PING if it has a timing such that it is less than or equal to the selected value. Otherwise it will be considered for the other types of LFPS. • 0b Max PING LFPS timing set to 256 ns (32 link clocks) • 1b Max PING LFPS timing set to 320 ns (40 link clocks) Power Well: SUSe
14:10	00h RO	Reserved (RSVD_1): Reserved. Power Well: Core
9:0	032h RW	xHCI BESL to HIRD Distance (XHCI_BESL_HIRD_DT): This field defines the gap between BESL and duration of Resume signalling from Host upon Host Initiated Resume from USB2.0 LPM. The default value of this register corresponds to xHCI spec defined 50us value. • Value BESL to HIRD Distance • 000h = 0us • 001h = 1us • 002h = 2us • 3FFh = 1023us Power Well: SUS

18.7.180 xHC Latency Tolerance Parameters - LTV Control (XLTP_LTV1)—Offset 8174h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8174h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 0040047Dh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DIS_SDT_IDL_NR	RSVD	XLTRTP	XLTRE	PA_LTV			USB2_PL0_LTV	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	Disable scheduler direct transition from IDLE to NO requirement (DIS_SDT_IDL_NR): 0 = (default) allow scheduler direct transition from IDLE to NO requirement 1 = Disable scheduler direct transition from IDLE to NO requirement Power Well: Core
30:26	00h RW	Reserved (RSVD): Reserved. Power Well: Core
25	0b RW	XHCI LTR Transition Policy (XLTRTP): When '0', LTR messaging state machine transitions from High, Medium, or Low LTR states to Active state upon the Alarm Timer timeout and stays in Active until the next service boundary. When '1', the LTR messaging state machine transitions through High ? Med ? Low ? Active states assuming enough latency is available for each transition. Power Well: Core
24	0b RW	XHCI LTR Enable (XLTRE): This bit must be set to enable LTV messaging from XHCI to the PMC. Power Well: Core
23:12	400h RW	Periodic Active LTV (PA_LTV): 23:22 Latency Scale 00b = Reserved 01b = Latency Value to be multiplied by 1024 10b = Latency Value to be multiplied by 32,768 11b = Latency Value to be multiplied by 1,048,576 21:12 Latency Value (ns) Defaults to 0 microseconds Power Well: Core



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 817Ch

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	MHIT				RSVD_1	HIWL		

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RO	Reserved (RSVD): Reserved. Power Well: Core
28:16	0000h RW	Minimum High Idle Time (MHIT): LTR value can be indicated. This value must be larger than HIWL. 12:7 - Time value in # of 125 Microsecond Bus Intervals (0 - 8ms) 6:0 - Fractional BI Time value in Microseconds (0 - 124 Microseconds) Power Well: Core
15:13	0h RO	Reserved (RSVD_1): Reserved. Power Well: Core
12:0	0000h RW	High Idle Wake Latency (HIWL): This is the latency to access memory from the High Idle Latency state This value must be larger than MIWL and LIWL. 12:7 - Time value in # of 125 Microseconds Bus Intervals (0 - 8ms) 6:0 - Fractional BI Time value in Microseconds (0 - 124 Microseconds) Power Well: Core

18.7.183 xHC Latency Tolerance Parameters - Medium Idle Time Control (XLTP_MITC)—Offset 8180h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8180h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	MMIT				RSVD_1	MIWL		



Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RO	Reserved (RSVD): Reserved. Power Well: Core
28:16	0000h RW	Minimum Medium Idle Time (MMIT): LTR value can be indicated. This value must be larger than MIWL. 12:7 - Time value in # of 125 Microseconds Bus Intervals (0 - 8ms) 6:0 - Fractional BI Time value in Microseconds (0 - 124 Microseconds) Power Well: Core
15:13	0h RO	Reserved (RSVD_1): Reserved. Power Well: Core
12:0	0000h RW	Medium Idle Wake Latency (MIWL): This is the latency to access memory from the Medium Idle Latency state. This value must be larger than LIWL. 12:7 - Time value in # of 125 Microseconds Bus Intervals (0 - 8ms) 6:0 - Fractional BI Time value in Microseconds (0 - 124 Microseconds) Power Well: Core

18.7.184 xHC Latency Tolerance Parameters Low Idle Time Control (XLTP_LITC)—Offset 8184h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8184h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	MLIT				RSVD_1	LIWL		

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RO	Reserved (RSVD): Reserved. Power Well: Core
28:16	0000h RW	Minimum Low Idle Time (MLIT): LTR value can be indicated. This value must be larger than LIWL. 12:7 - Time value in # of 125 Microseconds Bus Intervals (0 - 8ms) 6:0 - Fractional BI Time value in Microseconds (0 - 124 Microseconds) Power Well: Core
15:13	0h RO	Reserved (RSVD_1): Reserved. Power Well: Core

18.7.185 USB EP Type Lock Policy (USB_EP_TLP)—Offset 8344h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8344h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																																																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																							
RSVD								POL3_INT_IN				POL3_BULK_IN				POL3_ISOCH_IN				POL3_CTRL				POL3_INT_OUT				POL3_BULK_OUT				POL3_ISOCH_OUT				RSVD_1				POL2_INT_IN				POL2_BULK_IN				POL2_ISOCH_IN				POL2_CTRL				POL2_INT_OUT				POL2_BULK_OUT				POL2_ISOCH_OUT				RSVD_2				POL1_INT_IN				POL1_BULK_IN				POL1_ISOCH_IN				POL1_CTRL				POL1_INT_OUT				POL1_BULK_OUT				POL1_ISOCH_OUT				RSR_FP_TIPM_FN			

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved (RSVD): Reserved. Power Well: Core
23	0b RW/L	Policy 3 Interrupt IN EP Type (POL3_INT_IN): 1 - EP Type = 7 is allowed by Policy 3 0 - EP Type = 7 is not allowed by Policy 3 Power Well: Core
22	0b RW/L	Policy 3 Bulk IN EP Type (POL3_BULK_IN): 1 - EP Type = 6 is allowed by Policy 3 0 - EP Type = 6 is not allowed by Policy 3 Power Well: Core
21	0b RW/L	Policy 3 Isochronous IN EP Type (POL3_ISOCH_IN): 1 - EP Type = 5 is allowed by Policy 3 0 - EP Type = 5 is not allowed by Policy 3 Power Well: Core
20	0b RW/L	Policy 3 Control EP Type (POL3_CTRL): 1 - EP Type = 4 is allowed by Policy 3 0 - EP Type = 4 is not allowed by Policy 3 Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
19	0b RW/L	Policy 3 Interrupt OUT EP Type (POL3_INT_OUT): 1 - EP Type = 3 is allowed by Policy 3 0 - EP Type = 3 is not allowed by Policy 3 Power Well: Core
18	0b RW/L	Policy 3 Bulk OUT EP Type (POL3_BULK_OUT): 1 - EP Type = 2 is allowed by Policy 3 0 - EP Type = 2 is not allowed by Policy 3 Power Well: Core
17	0b RW/L	Policy 3 Isochronous OUT EP Type (POL3_ISOCH_OUT): 1 - EP Type = 1 is allowed by Policy 3 0 - EP Type = 1 is not allowed by Policy 3 Power Well: Core
16	0b RO	Reserved (RSVD_1): Reserved. Power Well: Core
15	0b RW/L	Policy 2 Interrupt IN EP Type (POL2_INT_IN): 1 - EP Type = 7 is allowed by policy 2 0 - EP Type = 7 is not allowed by policy 2 Power Well: Core
14	0b RW/L	Policy 2 Bulk IN EP Type (POL2_BULK_IN): 1 - EP Type = 6 is allowed by policy 2 0 - EP Type = 6 is not allowed by policy 2 Power Well: Core
13	0b RW/L	Policy 2 Isochronous IN EP Type (POL2_ISOCH_IN): 1 - EP Type = 5 is allowed by policy 2 0 - EP Type = 5 is not allowed by policy 2 Power Well: Core
12	0b RW/L	Policy 2 Control EP Type (POL2_CTRL): 1 - EP Type = 4 is allowed by policy 2 0 - EP Type = 4 is not allowed by policy 2 Power Well: Core
11	0b RW/L	Policy 2 Interrupt OUT EP Type (POL2_INT_OUT): 1 - EP Type = 3 is allowed by policy 2 0 - EP Type = 3 is not allowed by policy 2 Power Well: Core
10	0b RW/L	Policy 2 Bulk OUT EP Type (POL2_BULK_OUT): 1 - EP Type = 2 is allowed by policy 2 0 - EP Type = 2 is not allowed by policy 2 Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
9	0b RW/L	Policy 2 Isochronous OUT EP Type (POL2_ISOCH_OUT): 1 - EP Type = 1 is allowed by policy 2 0 - EP Type = 1 is not allowed by policy 2 Power Well: Core
8	0b RO	Reserved (RSVD_2): Reserved. Power Well: Core
7	0b RW/L	Policy 1 Interrupt IN EP Type (POL1_INT_IN): 1 - EP Type = 7 is allowed by policy 1 0 - EP Type = 7 is not allowed by policy 1 Power Well: Core
6	0b RW/L	Policy 1 Bulk IN EP Type (POL1_BULK_IN): 1 - EP Type = 6 is allowed by policy 1 0 - EP Type = 6 is not allowed by policy 1 Power Well: Core
5	0b RW/L	Policy 1 Isochronous IN EP Type (POL1_ISOCH_IN): 1 - EP Type = 5 is allowed by policy 1 0 - EP Type = 5 is not allowed by policy 1 Power Well: Core
4	0b RW/L	Policy 1 Control EP Type (POL1_CTRL): 1 - EP Type = 4 is allowed by policy 1 0 - EP Type = 4 is not allowed by policy 1 Power Well: Core
3	0b RW/L	Policy 1 Interrupt OUT EP Type (POL1_INT_OUT): 1 - EP Type = 3 is allowed by policy 1 0 - EP Type = 3 is not allowed by policy 1 Power Well: Core
2	0b RW/L	Policy 1 Bulk OUT EP Type (POL1_BULK_OUT): 1 - EP Type = 2 is allowed by policy 1 0 - EP Type = 2 is not allowed by policy 1 Power Well: Core
1	0b RW/L	Policy 1 Isochronous OUT EP Type (POL1_ISOCH_OUT): 1 - EP Type = 1 is allowed by policy 1 0 - EP Type = 1 is not allowed by policy 1 Power Well: Core
0	0b RW/L	USB EP Type Lock Policy match enable (USB_EP_TLPM_EN): Globally enable policy matching Power Well: Core



18.7.186 USB EP Type Lock Policy - Port Control 1 (USB_EP_TLP1)— Offset 8348h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8348h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EN_USB_LPM_RP16	EN_USB_LPM_RP15	EN_USB_LPM_RP14	EN_USB_LPM_RP13	EN_USB_LPM_RP12	EN_USB_LPM_RP11	EN_USB_LPM_RP10	EN_USB_LPM_RP9	EN_USB_LPM_RP8
EN_USB_LPM_RP7	EN_USB_LPM_RP6	EN_USB_LPM_RP5	EN_USB_LPM_RP4	EN_USB_LPM_RP3	EN_USB_LPM_RP2	EN_USB_LPM_RP1		

Bit Range	Default & Access	Field Name (ID): Description
31:30	0h RW/L	Enable USB Lock Policy match on root port number 16 (EN_USB_LPM_RP16): 00 = policy is not enabled for root port number 16 01 = policy 1 is enabled for root port number 16 10 = policy 2 is enabled for root port number 16 11 = policy 3 is enabled for root port number 16 Power Well: Core
29:28	0h RW/L	Enable USB Lock Policy match on root port number 15 (EN_USB_LPM_RP15): 00 = policy is not enabled for root port number 15 01 = policy 1 is enabled for root port number 15 10 = policy 2 is enabled for root port number 15 11 = policy 3 is enabled for root port number 15 Power Well: Core
27:26	0h RW/L	Enable USB Lock Policy match on root port number 14 (EN_USB_LPM_RP14): 00 = policy is not enabled for root port number 14 01 = policy 1 is enabled for root port number 14 10 = policy 2 is enabled for root port number 14 11 = policy 3 is enabled for root port number 14 Power Well: Core
25:24	0h RW/L	Enable USB Lock Policy match on root port number 13 (EN_USB_LPM_RP13): 00 = policy is not enabled for root port number 13 01 = policy 1 is enabled for root port number 13 10 = policy 2 is enabled for root port number 13 11 = policy 3 is enabled for root port number 13 Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
23:22	0h RW/L	Enable USB Lock Policy match on root port number 12 (EN_USB_LPM_RP12): 00 = policy is not enabled for root port number 12 01 = policy 1 is enabled for root port number 12 10 = policy 2 is enabled for root port number 12 11 = policy 3 is enabled for root port number 12 Power Well: Core
21:20	0h RW/L	Enable USB Lock Policy match on root port number 11 (EN_USB_LPM_RP11): 00 = policy is not enabled for root port number 11 01 = policy 1 is enabled for root port number 11 10 = policy 2 is enabled for root port number 11 11 = policy 3 is enabled for root port number 11 Power Well: Core
19:18	0h RW/L	Enable USB Lock Policy match on root port number 10 (EN_USB_LPM_RP10): 00 = policy is not enabled for root port number 10 01 = policy 1 is enabled for root port number 10 10 = policy 2 is enabled for root port number 10 11 = policy 3 is enabled for root port number 10 Power Well: Core
17:16	0h RW/L	Enable USB Lock Policy match on root port number 9 (EN_USB_LPM_RP9): 00 = policy is not enabled for root port number 9 01 = policy 1 is enabled for root port number 9 10 = policy 2 is enabled for root port number 9 11 = policy 3 is enabled for root port number 9 Power Well: Core
15:14	0h RW/L	Enable USB Lock Policy match on root port number 8 (EN_USB_LPM_RP8): 00 = policy is not enabled for root port number 8 01 = policy 1 is enabled for root port number 8 10 = policy 2 is enabled for root port number 8 11 = policy 3 is enabled for root port number 8 Power Well: Core
13:12	0h RW/L	Enable USB Lock Policy match on root port number 7 (EN_USB_LPM_RP7): 00 = policy is not enabled for root port number 7 01 = policy 1 is enabled for root port number 7 10 = policy 2 is enabled for root port number 7 11 = policy 3 is enabled for root port number 7 Power Well: Core
11:10	0h RW/L	Enable USB Lock Policy match on root port number 6 (EN_USB_LPM_RP6): 00 = policy is not enabled for root port number 6 01 = policy 1 is enabled for root port number 6 10 = policy 2 is enabled for root port number 6 11 = policy 3 is enabled for root port number 6 Power Well: Core
9:8	0h RW/L	Enable USB Lock Policy match on root port number 5 (EN_USB_LPM_RP5): 00 = policy is not enabled for root port number 5 01 = policy 1 is enabled for root port number 5 10 = policy 2 is enabled for root port number 5 11 = policy 3 is enabled for root port number 5 Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
31:25	00h RO	Rsvd2: Reserved. Power Well: Core
24	0b RW	HC OS Owned Semaphore (HCOSOS): Reserved. Power Well: SUS
23:17	00h RO	Rsvd1: Reserved. Power Well: Core
16	0b RW	HC BIOS Owned Semaphore (HCBIOSOS): Reserved. Power Well: SUS
15:8	08h RW/S	Next Capability Pointer (NextCP): Reserved. Power Well: SUS
7:0	01h RW/L	Capability ID (CID): Reserved. Power Well: SUS

18.7.189 USB Legacy Support Control Status (USBLEGCTLSTS)—Offset 8464h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8464h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																									
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																									
SMIBAR	SMIPCIC	SMIOSOC	Rsvd4								SMIHSE	Rsvd3				SMIEI	SMIBARE				SMIPCICE	SMIOSOE				Rsvd2				SMIHSEE	Rsvd1				USBSMIE																						

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW/C	SMI on BAR (SMIBAR): Reserved. Power Well: SUS
30	0b RW/C	SMI on PCI Command (SMIPCIC): Reserved. Power Well: SUS
29	0b RW/C	SMI on OS Ownership Change (SMIOSOC): Reserved. Power Well: SUS



Bit Range	Default & Access	Field Name (ID): Description
28:21	00h RO	Rsvd4: Reserved. Power Well: Core
20	0b RO	SMI on Host System Error (SMIHSE): Reserved. Power Well: SUS
19:17	0h RO	Rsvd3: Reserved. Power Well: Core
16	0b RO	SMI on Event Interrupt (SMIEI): Reserved. Power Well: SUS
15	0b RW	SMI on BAR Enable (SMIBARE): Reserved. Power Well: SUS
14	0b RW	SMI on PCI Command Enable (SMIPCICE): Reserved. Power Well: SUS
13	0b RW	SMI on OS Ownership Enable (SMIOSOE): Reserved. Power Well: SUS
12:5	00h RO	Rsvd2: Reserved. Power Well: Core
4	0b RW	SMI on Host System Error Enable (SMIHSEE): Reserved. Power Well: SUS
3:1	0h RO	Rsvd1: Reserved. Power Well: Core
0	0b RW	USB SMI Enable (USBSMIE): Reserved. Power Well: SUS

18.7.190 Debug Capability ID Register (DCID)—Offset 8480h

The Debug Capability *ID Register* links the USB Debug Capability into the xHCI list of Extended Capabilities and defines its basic capabilities. This register is modified and maintained by BIOS.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8480h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 0005000Ah



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	1	0	1	0
RSVD				DCERSTM	NCP			CID

Bit Range	Default & Access	Field Name (ID): Description
31:21	000h RO	Reserved (RSVD): Reserved. Power Well: Core
20:16	05h RW	Debug Capability Event Ring Segment Table Max (DCERSTM): Valid values are 0 15. This field determines the maximum value supported by the Debug Capability Event Ring Segment Table Base Size registers (see xHCI USB specification), where: The maximum number of Event Ring Segment Table entries = $2^{(DCERST\ Max)}$ e.g. if DCERST Max = 7, then the <i>Debug Capability Event Ring Segment Table(s)</i> supports up to 128 entries, 15 then 32K entries, etc. Note: This register is sticky. Power Well: Core
15:8	00h RW	Next Capability Pointer (NCP): This field indicates the location of the next capability with respect to the effective address of this capability. Refer to the xHCI USB specification for more information on this field. Note: This register is sticky. Power Well: Core
7:0	0Ah RW	Capability ID (CID): Refer to the xHCI USB specification for descriptions of the capabilities listed below. Note: This register is sticky. 0 = Reserved 1 = USB Legacy Support 2 = Supported Protocol 3 = Extended Power Management 4 = I/O Virtualization 5 = Message Interrupt 6 = Local Memory 7-9 = Reserved Power Well: Core

18.7.191 Debug Capability Doorbell Register (DCDB)—Offset 8484h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8484h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				DBTGT	RSVD_1			



18.7.193 Debug Capability Event Ring Segment Table Base Address Register (DCERSTBA)—Offset 8490h

The *Debug Capability Event Ring Segment Table Base Address Register* identifies the start address of the Debug Capability Event Ring Segment Table.

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

Offset: [MBAR] + 8490h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
ERSTBAR															RSVD	

Bit Range	Default & Access	Field Name (ID): Description
63:4	000000000 000000h RW	Event Ring Segment Table Base Address Register (ERSTBAR): This field defines the high order bits of the start address of the Debug Capability Event Ring Segment Table. Software shall initialize this register before setting the <i>Debug Capability Enable</i> field in the DCCTRL register to 1. Power Well: Core
3:0	0h RW	Reserved (RSVD): Reserved. Power Well: Core

18.7.194 Debug Capability Event Ring Dequeue Pointer Register (DCERDP)—Offset 8498h

The *Debug Capability Event Ring Dequeue Pointer Register* is written by software to define the Debug Capability Event Ring Dequeue Pointer location to the xHC. Software updates this pointer when it has finished the evaluation of an Event(s) on the Debug Capability Event Ring.

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

Offset: [MBAR] + 8498h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
DOP															RSVD	DEST



Bit Range	Default & Access	Field Name (ID): Description
63:4	00000000 000000h RW	Dequeue Pointer (DQP): This field defines the high order bits of the 64-bit address of the current Debug Capability Event Ring Dequeue Pointer. Software shall initialize this register before setting the <i>Debug Capability Enable</i> field in the DCCTRL register to '1'. Power Well: Core
3	0b RW	Reserved (RSVD): Reserved. Power Well: Core
2:0	0h RW	Dequeue ERST Segment Index (DESI): This field may be used by the xHC to accelerate checking the Event Ring full condition. This field is written with the low order 3 bits of the offset of the ERST entry which defines the Event Ring segment that the Event Ring Dequeue Pointer resides in. Power Well: Core

18.7.195 Debug Capability Control Register (DCCTRL)—Offset 84A0h

The *Debug Capability Control Register* is used to manage the Debug Capability.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 84A0h


MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DCE	DADDR			DMBS	RSVD			DRC HIT HOT LSE DCR

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	Debug Capability Enable (DCE): Setting this bit to a 1 enables xHCI USB Debug Capability operation. This bit is a 0 if the USB Debug Capability is disabled. Clearing this bit releases the Root Hub port assigned to the Debug Capability, and terminates any Debug Capability Transfer or Event Ring activity. Power Well: Core
30:24	00h RO	Device Address (DADDR): This field reports the USB device address assigned to the Debug Device during the enumeration process. This field is valid when the <i>DbC Run</i> bit is 1. Power Well: Core
23:16	00h RO	Debug Max Burst Size (DMBS): This field identifies the maximum burst size supported by the bulk endpoints of this DbC implementation. LPT-LP USB Debug Device does not support bursting. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
15:5	000h RO	Reserved (RSVD): Reserved. Power Well: Core
4	0b RW/C	DbC Run Change (DRC): This bit shall be set to '1' when DCR bit is cleared to '0', i.e. by any DbC Port State transition that exits the DbC-Configured state. While this bit is 1 the <i>Debug Capability Doorbell Register</i> (DCDB) is disabled. Software shall clear this bit to re-enable the DCDB. Power Well: Core
3	0b RW/S	Halt IN TR (HIT): While this bit is 1 the Debug Capability shall generate STALL TPs for all OUT DPs received for the IN TR. The Debug Capability shall clear this bit when a ClearFeature(ENDPOINT_HALT) request is received for the endpoint. This field is valid only when the Debug Capability is in Run Mode (DCR = 1). When not in Run Mode, this field shall return 0 when read, and writes will have no effect. Refer to the xHCI USB specification for more information. Power Well: Core
2	0b RW/S	Halt OUT TR (HOT): While this bit is 1 the Debug Capability shall generate STALL TPs for all IN TPs received for the OUT TR. The Debug Capability shall clear this bit when a ClearFeature(ENDPOINT_HALT) request is received for the endpoint. This field is valid only when the Debug Capability is in Run Mode (DCR = 1). When not in Run Mode, this field shall return 0 when read, and writes will have no effect. Refer to the xHCI USB specification for more information. Power Well: Core
1	0b RW	Link Status Event Enable (LSE): Setting this bit to a 1 enables the Debug Capability to generate Port Status Change Events due to the <i>Port Link Status Change</i> bit transitioning from a 0 to a 1. Refer to the xHCI USB specification for more information. Power Well: Core
0	0b RO	DbC Run (DCR): When 0, Debug Device is not in the Configured state. When 1, Debug Device is in the Configured state and bulk Data pipe transactions are accepted by Debug Capability and routed to the IN and OUT Transfer Rings. A 0 to 1 transition of the <i>Port Reset</i> (DCPORTSC:PR) bit will clear this bit to 0. Power Well: Core

18.7.196 Debug Capability Status Register (DCST)—Offset 84A4h

The *Debug Capability Status Register* reports capability related status information to software.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 84A4h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DPNUM	RSVD						ERNE	



Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Debug Port Number (DPNUM): This field provides the ID of the Root Hub port that the Debug Capability has been automatically attached to. The value is '0' when the Debug Capability is not attached to a Root Hub port. Power Well: Core
23:1	000000h RO	Reserved (RSVD): Reserved. Power Well: Core
0	0b RO	Event Ring Not Empty (ERNE): When '1', this field indicates that the Debug Capability Event Ring has a Transfer Event on it. It is automatically cleared to '0' by the xHC when the Debug Capability Event Ring is empty, i.e. the Debug Capability Enqueue Pointer is equal to the <i>Debug Capability Event Ring Dequeue Pointer</i> register. Power Well: Core

18.7.197 Debug Capability Port Status and Control Register (DCPORTSC)—Offset 84A8h

The fields of the *Debug Capability PORTSC Register* are defined below and provide information about the state of the Root Hub port that is assigned to the Debug Capability. Note that the fields in this register function differently than those in a normal *Port Status and Control Register* (described in section 5.4.8) because the Root Hub port assigned to the Debug Capability is acting as an Upstream Facing Port, not a Downstream Facing Port.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 84A8h


MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h


Default: 00000000h

31				28				24				20				16				12				8				4				0													
0				0				0				0				0				0				0				0				0													
RSVD								CEC		PLC		PRC		RSVD_1				CSC		RSVD_2				PSPD				RSVD_3				PLS				PR		RSVD_4				PED		CCS	

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved (RSVD): Reserved. Power Well: Core
23	0b RW/C	Port Config Error Change (CEC): This flag indicates that the port failed to configure its link partner. 0 = No change 1 = Port Config Error detected Software shall clear this bit by writing a '1' to it. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
22	0b RW/C	Port Link Status Change (PLC): This flag is set to '1' due to the following PLS transitions: - U0 -) U3 = Suspend signaling detected from Debug Host - U3 -) U0 = Resume complete - Polling -) Disabled = Training Error - Ux or Recovery -) Inactive = Error Software shall clear this bit by writing a '1' to it. This field is '0' if DCE is '0'. Power Well: Core
21	0b RW/C	Port Reset Change (PRC): This bit is set when reset processing on this port is complete (i.e. a '1' to '0' transition of PR). '0' = No change '1' = Reset complete Software shall clear this bit by writing a '1' to it. This field is '0' if DCE is '0'. Power Well: Core
20:18	0h RO	Reserved (RSVD_1): Reserved. Power Well: Core
17	0b RW/C	Connect Status Change (CSC): an already-set bit (i.e., the bit will remain '1'). Software shall clear this bit by writing a '1' to it. This field is '0' if DCE is '0'. Power Well: Core
16:14	0h RO	Reserved (RSVD_2): Reserved. Power Well: Core
13:10	0h RO	Port Speed (PSPD): This field identifies the speed of the port. This field is only relevant when a Debug Host is attached (CCS = '1') in all other cases, this field shall indicate Undefined Speed. 0 Undefined Speed 1-15 Protocol Speed ID (PSI) Refer to the xHCI for USB specification for the definition of PSIs. Note: The Debug Capability does not support LS, FS, or HS operation. Power Well: Core
9	0b RO	Reserved (RSVD_3): Reserved. Power Well: Core
8:5	0h RO	Port Link State (PLS): This field reflects its current link state. This field is only relevant when a Debug Host is attached (Debug Port Number) '0'). 0 = Link is in the U0 State 1 = Link is in the U1 State 2 = Link is in the U2 State 3 = Link is in the U3 State (Device Suspended) 4 = Link is in the Disabled State 5 = Link is in the RxDetect State 6 = Link is in the Inactive State 7 = Link is in the Polling State 8 = Link is in the Recovery State 9 = Link is in the Hot Reset State 15:10 = Reserved Note: Transitions between different states are not reflected until the transition is complete. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
4	0b RO	Port Reset (PR): '1' = Port is in Reset '0' = Port is not in Reset This bit is set to '1' when the bus reset sequence as defined in the USB Specification is detected on the Root Hub port assigned to the Debug capability. It is cleared when the bus reset sequence is completed by the Debug Host, and the DbC shall transition to the USB Default state. A '0' to '1' transition of this bit shall clear DCPORTSC PED ('0'). This field is '0' if DCE or CCS are '0'. Power Well: Core
3:2	0h RO	Reserved (RSVD_4): Reserved. Power Well: Core
1	0b RW	Port Enabled/Disabled (PED): '1' = Enabled. '0' = Disabled. This flag shall be set to '1' by a '0' to '1' transition of CCS or a '1' to '0' transition of the PR. When PED transitions from '1' to '0' due to the assertion of PR, the port's link shall transition to the Rx.Detect state. This flag may be used by software to enable or disable the operation of the Root Hub port assigned to the Debug Capability. The Debug Capability Root Hub port operation may be disabled by a fault condition (disconnect event or other fault condition, e.g. a LTSSM Polling substate timeout, tPortConfiguration timeout error, etc.), the assertion of DCPORTSC PR, or by software. 0 = Debug Capability Root Hub port is disabled. 1 = Debug Capability Root Hub port is enabled. When the port is disabled (PED = '0') the port's link shall enter the SS.Disabled state and remain there until PED is reasserted ('1') or DCE is negated ('0'). Note that the Root Hub port is remains mapped to Debug Capability while PED = '0'. While PED = '0' the Debug Capability will appear to be disconnected to the Debug Host. Note: This bit is not affected by PORTSC PR bit transitions. This field is '0' if DCE or CCS are '0'. Power Well: Core
0	0b RO	Current Connect Status (CCS): '1' = A Root Hub port is connected to a Debug Host and assigned to the Debug Capability. '0' = No Debug Host is present. This value reflects the current state of the port, and may not correspond to the value reported by the <i>Connect Status Change</i> (CSC) field in the <i>Port Status Change Event</i> that was generated by a '0' to '1' transition of this bit. This flag is '0' if Debug Capability Enable (DCE) is '0'. Power Well: Core

18.7.198 Debug Capability Context Pointer Register (DCCP)—Offset 84B0h

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

Offset: [MBAR] + 84B0h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 0000000000000000h



Bit Range	Default & Access	Field Name (ID): Description
63:4	00000000h 000000h RW	Debug Capability Context Pointer Register (DCCPR): This field defines the high order bits of the start address of the Debug Capability Context data structure associated with the Debug Capability. Software shall initialize this register before setting the Debug Capability Enable bit in the Debug Capability Control Register to '1'. Power Well: Core
3:0	0h RO	Reserved (RSVD): Reserved. Power Well: Core

18.7.199 Debug Capability Device Descriptor Info Register 1 (DCDDI1)—Offset 84B8h

The *Debug Capability Device Descriptor Register 1* identifies the Device Protocol and Vendor ID values that shall be reported by DbC in its Device Descriptor when it is enumerated by a Debug Host. Refer to section 9.6.1, Table 9-8 in the USB3 spec. This register shall be initialized before enabling the DbC (DCE = '1').

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 84B8h

MBAR Type: PCI Configuration Register (Size: 64 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW	Vendor ID (VID): This field is presented by the Debug Device in the USB Device Descriptor <i>idVendor</i> field. Power Well: Core
15:8	00h RO	Reserved (RSVD): Reserved. Power Well: Core



Type: Memory Mapped I/O Register
(Size: 32 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DREV					PTD			

18.7.201 Debug Capability Descriptor Parameters (DCDP)—Offset 8530h

Type: Memory Mapped I/O Register
(Size: 32 bits)

MBAR Reference: [B:0, D:20, F:0] + 10h

October 2018
Document Number: 538136, Rev. 4.3



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				EN_ACK_FCA	RSVD_1		EN_ACK_FIFO_ICA	
							RSVD_2	
							CL_OWN_CS	
							RET_OD_ACK_CR	
							RSVD_3	
							RET_ODCF_SM_IS	
							RET_ODRF_SM_IS	
							RET_ODRDF_SM_IS	
							RSVD_4	

Intel Atom® Processor E3800 Product Family
Datasheet
2349



Bit Range	Default & Access	Field Name (ID): Description
17:14	0h RO	Reserved (RSVD_1): Reserved. Power Well: Core
13	0b RW	Enable ACK FIFO ICA mechanisms (EN_ACK_FIFO_ICA): Setting this field will enable ACK FIFO individual credit accounting mechanisms for Async vs. Periodic Endpoints. ODMA will ensure that ample room exists in the ACK FIFO for expected device responses prior to initiating a given DP Power Well: Core
12:9	0h RO	Reserved (RSVD_2): Reserved. Power Well: Core
8	0b RW	Clear ownership of context semaphore (CL_OWN_CS): Setting this field generates a pulse that clears the ownership of the context semaphore that is shared between the Out DMA Response and Completion Finite State Machines Power Well: Core
7	0b RW	Return OD ACK credits (RET_OD_ACK_CR): Setting this field generates a pulse that implicitly returns all of the Out DMA ACK credits on all ports Power Well: Core
6	0b RO	Reserved (RSVD_3): Reserved. Power Well: Core
5	0b RW	Return ODCF SM to idle state (RET_ODCF_SM_IS): Setting this field generates a pulse that returns the Out DMA Completion Finite State Machine into the IDLE state Power Well: Core
4	0b RW	Return ODRF SM to idle state (RET_ODRF_SM_IS): Setting this field generates a pulse that returns the Out DMA Response Finite State Machine into the IDLE state Power Well: Core
3	0b RW	Return ODRDF SM to idle state (RET_ODRDF_SM_IS): Setting this field generates a pulse that returns the Out DMA Read Finite State Machine into the IDLE state Power Well: Core
2:0	0h RO	Reserved (RSVD_4): Reserved. Power Well: Core




18.8 USB EHCI PCI Configuration Registers

Table 214. Summary of USB EHCI PCI Configuration Registers—0/29/0

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–0h	1	"Vendor ID and Device ID (VID_DID)—Offset 0h" on page 2352	00008086h
4–4h	1	"Command and Device Status (CMD_STS)—Offset 4h" on page 2352	02900000h
8–Bh	4	"Revision ID and Programming Interface and Sub/Base Class Code (RID_PI_CC)—Offset 8h" on page 2355	0C032000h
C–Fh	4	"Reserved and Master Latency Timer and Header Type (RSVD_MLT_HT)—Offset Ch" on page 2356	00000000h
10–13h	4	"Memory Base Address (MBAR)—Offset 10h" on page 2357	00000000h
2C–2Fh	4	"USB2 Subsystem Vendor ID and USB2 Subsystem ID (SSVID_SSID)—Offset 2Ch" on page 2358	00000000h
34–37h	4	"Capabilities Pointer and Reserved (CAP_PTR_RSVD)—Offset 34h" on page 2358	00000050h
3C–3Fh	4	"Interrupt Line and Interrupt Pin and Reserved (ILINE_IPIN_RSVD)—Offset 3Ch" on page 2359	00000000h
50–53h	4	"PCI Power Management Capability ID and Next Item Pointer #1 and PM Capabilities (PM_CID_NEXT_CAP)—Offset 50h" on page 2359	C9C35801h
54–57h	4	"Power Management Control/Status (PM_CS)—Offset 54h" on page 2361	00000008h
58–5Bh	4	"Debug Port Capability ID and Next Item Pointer #2 and Debug Port Base Offset (DP_CID_NEXT_BASE)—Offset 58h" on page 2362	20A0980Ah
60–63h	4	"Serial Bus Release Number and Frame Length Adjustment and Port Wake Capability (SBRN_FLA_PWC)—Offset 60h" on page 2363	07FF2020h
64–67h	4	"Port Disable Override and RMH Device Removable (PDO_RMHDR)—Offset 64h" on page 2364	00000000h
68–6Bh	4	"USB2 Legacy Support Extended Capability (ULSEC)—Offset 68h" on page 2365	00000001h
6C–6Fh	4	"USB2 Legacy Support Control/Status (ULSCS)—Offset 6Ch" on page 2366	00000000h
70–73h	4	"Intel-Specific USB2 SMI (ISU2SMI)—Offset 70h" on page 2369	00000000h
74–77h	4	"OverCurrent Mapping (OCMAP)—Offset 74h" on page 2371	C0300C03h
7C–7Fh	4	"EHC Suspend Well Configuration and RMH Wake Control (EHCSUSCFGRMHWK)—Offset 7Ch" on page 2371	0000408Ch
F8–FBh	4	"Manufacturer's ID (MANID)—Offset F8h" on page 2374	00000F86h



Bit Range	Default & Access	Field Name (ID): Description
29	0b RWC	Received Master-Abort Status (RMA_0): This bit is set when USB2, as a master, receives a master-abort status on a memory access. This is treated as a Host Error and halts the DMA engines. This event can optionally generate an SERR# by setting the SERR# Enable bit and the SERR on Aborts Enable (bit 3, offset 84h). Software clears this bit by writing a '1' to this bit location. Power Well: Core
28	0b RWC	Received Target Abort Status (RTA_0): This bit is set when USB2, as a master, receives a target abort status on a memory access. This is treated as a Host Error and halts the DMA engines. This event can optionally generate an SERR# by setting the SERR# Enable bit and the SERR on Aborts Enable (bit 3, offset 84h). Software clears this bit by writing a '1' to this bit location. Power Well: Core
27	0b RO	Signaled Target-Abort Status (STA_0): This bit is used to indicate when the USB2 function responds to a cycle with a target abort. There is no reason for this to happen, so this bit will be hard-wired to '0'. Read-Only Power Well: Core
26:25	01b RO	DEVSEL# Timing Status (DEVT_0): This 2-bit field defines the timing for DEVSEL# assertion. Read-Only. Power Well: Core
24	0b RWC	Master Data Parity Error Detected (MDPED_0): This bit is set whenever a data parity error is detected on a USB2 read completion packet on the internal interface to the USB2 host controller and bit 6 of the Command register is set to 1. Software clears this bit by writing a '1' to this bit location. Power Well: Core
23	1b RO	Fast Back-to-Back Capable (FBCAP_0): Reserved as '1'. Power Well: Core
22	0b RO	User Definable Features (UDF_0): Reserved as '0' Power Well: Core
21	0b RO	66 Mhz Capable (CLKCAP_0): Reserved as '0' Power Well: Core
20	1b RO	Capabilities List (CAPLIST_0): Hardwired to '1' indicating that offset 34h contains a valid capabilities pointer. Power Well: Core
19	0b RO	Interrupt Status (INTRSTS_0): This read-only bit reflects the state of this function's interrupt at the input of the enable/disable logic. This bit is a 1 when the interrupt is asserted. This bit will be 0 when the interrupt is deasserted. The value reported in this bit is independent of the value in the Interrupt Enable bit. Power Well: Core
18:11	00000000b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
10	0b RW	Interrupt Disable (INTRDIS_0): When cleared to '0', the function is capable of generating interrupts. When '1', the function can not generate its interrupt to the interrupt controller. Note that the corresponding Interrupt Status bit is not affected by the interrupt enable. This bit defaults to '0'. This bit is added as part of the PCI 2.3 Specification. Power Well: Core
9	0b RO	Fast Back to Back Enable (FBE_0): Reserved as '0'. Power Well: Core
8	0b RW	SERR# Enable (SERREN_0): on a memory read completion (if SERR on Aborts Enable is also set) Detection of an address or command parity error and the Parity Error Response bit is setDetection of a data parity error (when the data is going to the EHC) and the Parity Error Response bit is set Power Well: Core
7	0b RO	Wait Cycle Control (WCC_0): Reserved as '0'. Power Well: Core
6	0b RW	Parity Error Response (PER_0): When set to 1, the USB2 Host Controller will check for correct parity (on its internal interface) and halt operation when bad parity is detected during the data phase as recommended by the EHCI specification. If it detects bad parity on the address or command phases when this bit is set to 1, the host controller does not take the cycle, halts the host controller (if currently not halted) and sets the host system error bit in the USBSTS register. Note that this applies to both requests and completions from the system interface. See section 9.19.2.4 for information regarding parity errors detected by the Prefetch DMA Engine. This bit must be set in order for the parity errors to generate SERR#. Power Well: Core
5	0b RO	VGA Palette Snoop (VGAPS_0): Reserved as '0' Power Well: Core
4	0b RO	Postable Memory Write Enable (PMWE_0): Reserved as '0' Power Well: Core
3	0b RO	Special Cycle Enable (SCE_0): Reserved as '0' Power Well: Core
2	0b RW	Bus Master Enable (BME_0): When set, bus mastering from EHCI is allowed, and will generate memory reads and writes for USB transfers. Notes on the EHC implementation: - Writes to change this bit occur immediately. Specifically, a write followed by a read will return the updated value. - When the BME bit is changed from 1 to 0, the EHC will cease accessing main memory within 2 microframes (250 usec). During this time, any number of reads and/or writes to memory may occur. - Clearing the BME bit shuts down the EHC DMA engines in the same manner that clearing the Run/Stop does. However, the schedule status bits and the HCHalted bit do not change based on the BME value. Power Well: Core
1	0b RW	Memory Space Enable (MSE_0): This bit controls access to the USB2 Memory Space registers. If this bit is set, accesses to the USB2 registers are enabled. The Base Address register for USB2 should be programmed before this bit is set. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
0	0b RO	I/O Space Enable (IOSE_0): Reserved as '0'. Power Well: Core

18.8.3 Revision ID and Programming Interface and Sub/Base Class Code (RID_PI_CC)—Offset 8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 8h

Default: 0C032000h

31	28	24	20	16	12	8	4	0
0	0	0	0	1	1	0	0	0
0	0	0	0	0	0	1	0	0
0	0	0	0	0	0	0	0	0
BCC_0				SCC_0				RID_0

Bit Range	Default & Access	Field Name (ID): Description
31:24	0Ch RO	Base Class Code (BCC_0): A value of 0Ch indicates that this is a Serial Bus controller. Power Well: Core
23:16	03h RO	Sub Class Code (SCC_0): A value of 03h indicates that this is a Universal Serial Bus Host Controller. Power Well: Core
15:8	20h RO	Programming Interface (PI_0): A value of 20h indicates that this USB2 Host Controller conforms to the EHCI specification. Power Well: Core
7:0	00h RO	Revision ID (RID_0): The value reported in this register indicates stepping of the host controller hardware. Power Well: Core



Type: PCI Configuration Register
(Size: 32 bits) **Offset:** [B:0, D:29, F:0] + 2Ch

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
USB2SSID_0				USB2SVID_0				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW/L	USB2 Subsystem ID (USB2SSID_0): BIOS sets the value in this register to identify the Subsystem ID. This register, in combination with the Subsystem Vendor ID register, enables the operating system to distinguish each subsystem from other(s). Writes to this register are enabled when the WRT_RDONLY bit (offset 80h, bit 0) is set to 1. Writes should be done as a single 16-bit cycle. Reset: none Power Well: Core
15:0	0000h RW/L	USB2 Subsystem Vendor ID (USB2SVID_0): This register, in combination with the USB2 Subsystem ID register, enables the operating system to distinguish each subsystem from the others. Writes to this register are enabled when the WRT_RDONLY bit (offset 80h, bit 0) is set to 1. Reset: none Power Well: Core

18.8.7 Capabilities Pointer and Reserved (CAP_PTR_RSVD)—Offset 34h

Type: PCI Configuration Register
(Size: 32 bits) **Offset:** [B:0, D:29, F:0] + 34h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD							CAP_PTR_0	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
7:0	50h RO	Capabilities Pointer (CAP_PTR_0): This register points to the starting offset of the USB2 capabilities ranges. Power Well: Core

18.8.8 Interrupt Line and Interrupt Pin and Reserved (ILINE IPIN RSVD)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 3Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				IPIN_0				ILINE_0

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved (RSVD): Reserved.
15:8	00h RO	Interrupt Pin (IPIN_0): Bits 3:0 reflect the value programmed in the interrupt pin registers in chipset configuration space. Bits 7:4 are hardwired to 0000b. NOTE: As a single function device, only INTA# may be used while the other three interrupt lines have no meaning. (refer to PCI 3.0 spec section 2.2.6 Interrupt Pins) Power Well: Core
7:0	00h RW	Interrupt line (ILINE_0): This data is not used by the SOC. It is used as a scratchpad register to communicate to software the interrupt line that the interrupt pin is connected to. Reset: core well and D3-to-D0. Power Well: Core

18.8.9 PCI Power Management Capability ID and Next Item Pointer #1 and PM Capabilities (PM_CID_NEXT_CAP)—Offset 50h

PCI Power Management Capabilities ID Next Item Pointer #1 Power Management Capabilities

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 50h

Default: C9C35801h



31				28				24				20				16				12				8				4				0			
1	1	0	0	1	0	0	1	1	1	0	0	0	0	1	1	0	1	0	1	1	1	0	0	0	0	0	0	0	0	0	1				
RSVD				D2SUP_0		D1SUP_0		AUXCUR_0		DSI_0		RSVD		PMECLK_0		VERS_0		PM_NEXT_0				PM_CID_0													

Bit Range	Default & Access	Field Name (ID): Description
31:27	11001b RO	Reserved (RSVD): Reserved.
26	0b RO	D2_Support (D2SUP_0): The D2 state is not supported. Reset: core well, but not D3-to-D0. Power Well: Core
25	0b RO	D1_Support (D1SUP_0): The D1 state is not supported. Reset: core well, but not D3-to-D0. Power Well: Core
24:22	111b RW/L	Aux_Current (AUXCUR_0): The USB2 SIP EHC reports 375mA maximum Suspend well current required when in the D3cold state. This value can be written by BIOS when a more accurate value is known. Power Well: Core
21	0b RO	DSI (DSI_0): The Intel EHC reports 0, indicating that no device-specific initialization is required. Reset: core well, but not D3-to-D0. Power Well: Core
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	PME Clock (PMECLK_0): The Intel EHC reports 0, indicating that no PCI clock is required to generate PME#. Reset: core well, but not D3-to-D0. Power Well: Core
18:16	011b RW/L	Version (VERS_0): Version: The Intel EHC reports 011, indicating that it complies with Revision 1.21 of the PCI Power Management Specification. Note: As contingency plan, the bit can be reverted by BIOS to 010b to support PCI PM Revision 1.1, by manipulating the offset80h Access Control register's WRT_RDONLY bit. Power Well: Core
15:8	58h RW/L	Next Item Pointer #1 (PM_NEXT_0): This register defaults to 58h, which indicates that the next capability registers begin at configuration offset 58h. This register is writable when the WRT_RDONLY bit is set. This allows BIOS to effectively hide the Debug Port capability registers, if necessary. This register should only be written during system initialization before the plug-and-play software has enabled any master-initiated traffic. Values of 58h implies Debug Port and FLR capabilities visible 98h implies Debug Port invisible, next capability is FLR 00h implies that both Debug port and FLR capability are hidden Note that this value is never expected to be programmed. Reset: core well, but not D3-to-D0 Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
7:0	01h RO	PCI Power Management Capability ID (PM_CID_0): A value of 01h indicates that this is a PCI Power Management capabilities field. Power Well: Core

18.8.10 Power Management Control/Status (PM CS)—Offset 54h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 54h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				PMESTS_0	DTScI_0	DTScI_0	PMEEN_0	RSVD
								NO_SOFT_RESET
								RSVD
								PWRST_0

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved (RSVD): Reserved.
15	0b RWC	PME_Status (PMESTS_0): This bit is set when the EHC would normally assert the PME# signal independent of the state of the PME_En bit. Writing a 1 to this bit will clear it and cause the internal PME to deassert (if enabled). Writing a 0 has no effect. This bit must be explicitly cleared by the operating system each time the operating system is loaded. Power Well: Resume
14:13	00b RO	Data_Scale (DTScI_0): because it does not support the associated Data register. Power Well: Resume
12:9	0h RO	Data_Select (DTSel_0): because it does not support the associated Data register. Power Well: Resume
8	0b RW	PME_En (PMEEN_0): A '1' enables the EHC to generate an internal PME signal when PME_Status is '1'. This bit must be explicitly cleared by the operating system each time it is initially loaded. Power Well: Resume
7:4	0000b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
3	1b RO	No Soft Reset (NO_SOFT_RESET): A '0' indicates device does perform an internal reset upon D3hot to D0 transition via software control of the PowerState bits. Configuration Context is lost. Full re-initialization sequence is needed to return the device to D0 Initialized.(Default to '1') Note: As contingency plan, the bit can be reverted by BIOS to 0, by manipulating the offset80h Access Control register's WRT_RDONLY bit. Power Well: Resume
2	0b RO	Reserved (RSVD): Reserved.
1:0	00b RW	PowerState (PWRST_0): This 2-bit field is used both to determine the current power state of EHC function and to set a new power state. The definition of the field values are: 00b - D0 state 11b - D3hot state If software attempts to write a value of 10b or 01b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3hot state, the accesses to the EHC memory range must not be accepted; but the configuration space must still be accessible. When not in the D0 state, the generation of the interrupt output is blocked. Specifically, the PIRQ[H] is not asserted when not in the D0 state. When software changes this value from the D3hot state to the D0 state, an internal warm (soft) reset is generated, and software must re-initialize the function. Power Well: Resume

18.8.11 Debug Port Capability ID and Next Item Pointer #2 and Debug Port Base Offset (DP_CID_NEXT_BASE)—Offset 58h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 58h

Default: 20A0980Ah

31				28				24				20				16				12				8				4				0			
0	0	1	0	0	0	0	0	1	0	1	0	0	0	0	0	1	0	0	1	1	0	0	0	0	0	0	0	1	0	1	0				
BARNUM_0				DPOFFSET_0												RSVD				DP_CID_0															

Bit Range	Default & Access	Field Name (ID): Description
31:29	001b RO	BAR Number (BARNUM_0): Read-Only. This field is hardwired to 001b to indicate the memory BAR at offset 10h in the EHCI configuration space. Reset: Not applicable. Power Well: Core
28:16	00A0h RO	Debug Port Offset (DPOFFSET_0): This field is hardwired to 0A0h to indicate that the debug port registers begin at offset A0h in the EHCI memory range. Reset: Not applicable. Power Well: Core
15:8	98h RO	Reserved (RSVD): Reserved.



Type: PCI Configuration Register
(Size: 32 bits)

[illegible]

October 2018
Document Number: 538136, Rev.4.3



Bit Range	Default & Access	Field Name (ID): Description
7:0	20h RO	Serial Bus Release Number (SBRN_0): value of 20h indicates that this controller follows USB release 2.0 Power Well: Resume

18.8.13 Port Disable Override and RMH Device Removable (PDO_RMHDR)—Offset 64h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 64h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	DRBM_0	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD

Bit Range	Default & Access	Field Name (ID): Description
31:25	0000000b RO	Reserved (RSVD): Reserved.
24:17	00h RW	Device Removable Bit Map (DRBM_0): A 1 in a given bit position in this field indicates that the corresponding downstream port of the RMH is connected to a non-removable device. A 0 indicates that the port is exposed to the user. Bits 8:1 are mapped to Ports 8:1. This bits control the value returned by the RMH in the DeviceRemovable field of the Hub Descriptor. A 1 in a given bit position in this register will result in the corresponding bit in the DeviceRemovable field of the hub descriptor being set to 1 as well (indicating that the port is connected to a non-removable device). System BIOS is expected to set these values upon Boot and resume from Sx states. Power Well: Core
16:8	00000000b RO	Reserved (RSVD): Reserved.
7:0	00h RO	Reserved (RSVD): Reserved.



18.8.14 USB2 Legacy Support Extended Capability (ULSEC)—Offset 68h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 68h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RSVD				HCOSOS_0	RSVD			
				HCBIOS_0	NxtEHCI CapP_0			
					CapID_0			

Bit Range	Default & Access	Field Name (ID): Description
31:25	0000000b RO	Reserved (RSVD): Reserved.
24	0b RW	HC OS Owned Semaphore (HCOSOS_0): System software sets this bit to request ownership of the EHCI controller. Ownership is obtained when this bit reads as 1 and the HC BIOS Owned Semaphore bit reads as clear. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
23:17	0000000b RO	Reserved (RSVD): Reserved.
16	0b RW	HC BIOS Owned Semaphore (HCBIOS_0): The BIOS sets this bit to establish ownership of the EHCI controller. System BIOS will clear this bit in response to a request for ownership of the EHCI controller by system software. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
15:8	00h RO	Next EHCI Capability Pointer (NxtEHCI CapP_0): A value of 00h indicates that there are no EHCI Extended Capability structures in this device. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
7:0	01h RO	Capability ID (CapID_0): A value of 01h indicates that this EHCI Extended Capability is the Legacy Support Capability. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume



18.8.15 USB2 Legacy Support Control/Status (ULSCS)—Offset 6Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 6Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SMIonBAR_0	SMIonPCICom_0	SMIonOSSC_0	RSVD	SMIonAA_0	SMIonHSE_0	SMIonFLR_0	SMIonPCD_0	SMIonUE_0
				SMIonSBC_0	SMIonBARE_0	SMIonPCICE_0	SMIonOSSOE_0	RSVD
								SMIonAAE_0
								SMIonHSEE_0
								SMIonFLRE_0
								SMIonPCE_0
								SMIonUSBEE_0
								SMIonUSBCE_0

Bit Range	Default & Access	Field Name (ID): Description
31	0b RWC	SMI on BAR (SMIonBAR_0): This bit is set to '1' whenever the Base Address Register (BAR) is written. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
30	0b RWC	SMI on PCI Command (SMIonPCICom_0): This bit is set to '1' whenever the PCI Command Register is written. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
29	0b RWC	SMI on OS Ownership Change (SMIonOSSC_0): This bit is set to '1' whenever the HC OS Owned Semaphore bit in the USB2 Legacy Support Extended Capability register transitions from 1 to a 0 or 0 to a 1. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
28:22	00h RO	Reserved (RSVD): Reserved.
21	0b RO	SMI on Async Advance (SMIonAA_0): Shadow bit of the Interrupt on Async Advance bit in the USB2STS register. To clear this bit system software must write a one to the Interrupt on Async Advance bit in the USB2STS register. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
20	0b RO	SMI on Host System Error (SMIonHSE_0): Shadow bit of Host System Error bit in the USB2STS. To clear this bit system software must write a one to the Host System Error bit in the USB2STS register. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
19	0b RO	SMI on Frame List Rollover (SMIonFLR_0): Shadow bit of Frame List Rollover bit in the USB2STS register. To clear this bit system software must write a one to the Frame List Rollover bit in the USB2STS register. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
18	0b RO	SMI on Port Change Detect (SMIonPCD_0): Shadow bit of Port Change Detect bit in the USB2STS register. To clear this bit system software must write a one to the Port Change Detect bit in the USB2STS register. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
17	0b RO	SMI on USB Error (SMIonUE_0): Shadow bit of USB Error Interrupt (USBERRINT) bit in the USB2STS register. To clear this bit system software must write a one to the USB Error Interrupt bit in the USB2STS register. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
16	0b RO	SMI on USB Complete (SMIoUSBC_0): Shadow bit of USB Interrupt (USBINT) bit in the USB2STS register. To clear this bit system software must write a one to the USB Interrupt bit in the USB2STS register. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
15	0b RW	SMI on BAR Enable (SMIonBARE_0): When this bit is '1' and SMIonBAR_0 is '1', then the host controller will issue an SMI. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
14	0b RW	SMI on PCI Command Enable (SMIonPCICE_0): When this bit is '1' and SMI on PCI Command is '1', then the host controller will issue an SMI. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
13	0b RW	SMI on OS Ownership Enable (SMIonOSSOE_0): When this bit is a one AND the OS Ownership Change bit is one, the host controller will issue an SMI. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
12:6	00h RO	Reserved (RSVD): Reserved.
5	0b RW	SMI on Async Advance Enable (SMIonAAE_0): When this bit is a one, and the SMI on Async Advance bit is a one, the host controller will issue an SMI immediately. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
4	0b RW	SMI on Host System Error Enable (SMIonHSEE_0): When this bit is a one, and the SMI on Host System Error is a one, the host controller will issue an SMI. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
3	0b RW	SMI on Frame List Rollover Enable (SMIonFLRE_0): When this bit is a one, and the SMI on Frame List Rollover bit is a one, the host controller will issue an SMI. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
2	0b RW	SMI on Port Change Enable (SMIonPCE_0): When this bit is a one, and the SMI on Port Change Detect bit is a one, the host controller will issue an SMI. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
1	0b RW	SMI on USB Error Enable (SMIonUSBEE_0): When this bit is a one, and the SMI on USB Error bit is a one, the host controller will issue an SMI immediately. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume
0	0b RW	SMI on USB Complete Enable (SMIonUSBCE_0): When this bit is a one, and the SMI on USB Complete bit is a one, the host controller will issue an SMI immediately. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition. Power Well: Resume



18.8.16 Intel-Specific USB2 SMI (ISU2SMI)—Offset 70h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 70h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SMIonPO1_0				SMIonPMCSR_0	SMIonAsync_0	SMIonPeriodic_0	SMIonCF_0	SMIonHCRst_0
							SMIonPOEn_0	
							SMIonPMSCREn_0	SMIonAsynCEn_0
							SMIonPeriodicEn_0	SMIonCFEn_0
							SMIonHCHaltedEn_0	SMIonHCRstEn_0

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RWC	SMI on PortOwner (SMIonPO1_0): Bits 29:22 correspond to the Port Owner bits for ports 1 (22) through 8 (29). These bits are set to '1' whenever the associated Port Owner bits transition from 0-)1 or 1-)0. Software clears these bits by writing a one. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
21	0b RWC	SMI on PMCSR (SMIonPMCSR_0): This bit is set to '1' whenever software modifies the Power State bits in the Power Management Control/Status register. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
20	0b RWC	SMI on Async (SMIonAsync_0): This bit is set to '1' whenever the Async Schedule Enable bit transitions from 1-)0 or 0-)1. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
19	0b RWC	SMI on Periodic (SMIonPeriodic_0): This bit is set to '1' whenever the Periodic Schedule Enable bit transitions from 1-)0 or 0-)1. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
18	0b RWC	SMI on CF (SMIonCF_0): This bit is set to '1' whenever the Configure Flag transitions from 1-)0 or 0-)1. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
17	0b RWC	SMI on HCHalted (SMIonHCHalted_0): This bit is set to '1' whenever HCHalted transitions to '1' as a result of the Run/Stop bit being cleared. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
16	0b RWC	SMI on HCRstet (SMIonHCRst_0): This bit is set to '1' whenever HCRSTET transitions to '1'. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
15:6	000h RW	SMI on PortOwner Enable (SMIonPOEn_0): When any of these bits are '1' and the corresponding SMI on PortOwner bits are '1', then the host controller will issue an SMI. Unused ports should have their corresponding bits cleared. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
5	0b RW	SMI on PMSCR Enable (SMIonPMSCREn_0): When this bit is '1' and SMI on PMSCR is '1', then the host controller will issue an SMI. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
4	0b RW	SMI on Async Enable (SMIonAsyncEn_0): When this bit is '1' and SMI on Async is '1', then the host controller will issue an SMI. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
3	0b RW	SMI on Periodic Enable (SMIonPeriodicEn_0): When this bit is '1' and SMI on Periodic is '1', then the host controller will issue an SMI. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
2	0b RW	SMI on CF Enable (SMIonCFEn_0): When this bit is '1' and SMI on CF is '1', then the host controller will issue an SMI. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
1	0b RW	SMI on HCHalted Enable (SMIonHCHaltedEn_0): When this bit is a '1' and SMI on HCHalted is '1', then the host controller will issue an SMI. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume
0	0b RW	SMI on HCRstet Enable (SMIonHCRstEn_0): When this bit is a '1' and SMI on HCHalted is '1', then the host controller will issue an SMI. This register is implemented in the Suspend Well. This register is only reset by the resume power well going low. It is not reset by the core power well going low or by a D3-to-D0 state transition Power Well: Resume



18.8.17 OverCurrent Mapping (OCMAP)—Offset 74h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 74h

Default: C0300C03h

31	28	24	20	16	12	8	4	0
1	1	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:24	C0h RW	OC Mapping D (OCMAPD_0): Each bit position maps OC4, for EHCI1 to a set of ports as follows: The OC4 pin is ganged to the overcurrent signal of each port that has its corresponding bit set. It is SW's responsibility to ensure that a given port's bit map is set only for one OC pin. Power Well: Resume
23:16	30h RW	OC Mapping C (OCMAPC_0): OC Mapping C. Each bit position maps OC3, for EHCI1 to a set of ports as follows: The OC3 pin is ganged to the overcurrent signal of each port that has its corresponding bit set. It is SW's responsibility to ensure that a given port's bit map is set only for one OC pin. Power Well: Resume
15:8	0Ch RW	OC Mapping B (OCMAPB_0): OC Mapping B. Each bit position maps OC2, for EHCI1 to a set of ports as follows: The OC2 pin is ganged to the overcurrent signal of each port that has its corresponding bit set. It is SW's responsibility to ensure that a given port's bit map is set only for one OC pin. Power Well: Resume
7:0	03h RW	OC Mapping A (OCMAPA_0): OC Mapping A: Each bit position maps OC1, for EHCI1 to a set of ports as follows: The OC1 pin is ganged to the overcurrent signal of each port that has its corresponding bit set. It is SW's responsibility to ensure that a given port's bit map is set only for one OC pin. Power Well: Core


18.8.18 EHC Suspend Well Configuration and RMH Wake Control (EHCSUSCFGRMHW C)—Offset 7Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:29, F:0] + 7Ch

Default: 0000408Ch



October 2018
Document Number: 538136, Rev.4.3



Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Reserved (RSVD): Reserved.
14	1b RO	Reserved (RSVD): Reserved.
13	0b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11:10	00b RO	Reserved (RSVD): Reserved.
9	0b RO	Reserved (RSVD): Reserved.
8	0b RO	Reserved (RSVD): Reserved.
7	1b RO	Reserved (RSVD): Reserved.
6	0b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	1b RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	0b RO	Reserved (RSVD): Reserved.
0	0b RO	Reserved (RSVD): Reserved.



18.9 USB EHCI Memory Mapped IO Registers

Table 215. Summary of USB EHCI Memory Mapped I/O Registers—MBAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–0h	1	"Capability Registers Length and HC Interface Version Number (CAP_HCIV)—Offset 0h" on page 2376	01000020h
4–4h	1	"Host Controller Structural Parameters (HCSPARAMS)—Offset 4h" on page 2377	00200008h
8–Bh	4	"Host Controller Capability Parameters (HCCPARAMS)—Offset 8h" on page 2379	00036881h
20–23h	4	"USB2 Command Register (USB2CMD)—Offset 20h" on page 2380	00080000h
24–27h	4	"USB2 Status (USB2STS)—Offset 24h" on page 2383	00001000h
28–2Bh	4	"USB2 Interrupt Enable (USB2INTR)—Offset 28h" on page 2385	00000000h
2C–2Fh	4	"Frame Index (FRINDEX)—Offset 2Ch" on page 2387	00000000h
30–33h	4	"Control Data Structure Segment Register (CTRLDSSEGMENT)—Offset 30h" on page 2387	00000000h
34–37h	4	"Periodic Frame List Base Address (PERIODICLISTBASE)—Offset 34h" on page 2388	00000000h
38–3Bh	4	"Current Asynchronous List Address (ASYNCLISTADDR)—Offset 38h" on page 2388	00000000h
60–63h	4	"Configure Flag Register (CONFIGFLAG)—Offset 60h" on page 2389	00000000h
64–67h	4	"Port Status and Control (PORTSC1)—Offset 64h" on page 2391	00003000h
68–6Bh	4	"Port Status and Control (PORTSC2)—Offset 68h" on page 2395	00003000h
6C–6Fh	4	"Port Status and Control (PORTSC3)—Offset 6Ch" on page 2400	00003000h
70–73h	4	"Port Status and Control (PORTSC4)—Offset 70h" on page 2404	00003000h
74–77h	4	"Port Status and Control (PORTSC5)—Offset 74h" on page 2409	00003000h
78–7Bh	4	"Port Status and Control (PORTSC6)—Offset 78h" on page 2413	00003000h
7C–7Fh	4	"Port Status and Control (PORTSC7)—Offset 7Ch" on page 2418	00003000h
80–83h	4	"Port Status and Control (PORTSC8)—Offset 80h" on page 2422	00003000h
A0–A0h	1	"Debug Port Control/Status Register (DP_CTRLSTS)—Offset A0h" on page 2427	00000000h
A4–A4h	1	"USB PIDs Register (DP_USB_PIDs)—Offset A4h" on page 2429	00000000h



18.9.1 Capability Registers Length and HC Interface Version Number (CAP_HCIV)—Offset 0h

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 0h

MBAR Type: PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
HCIVERSION_B0_0				RSVD				CAPLENGTH_0

Intel Atom® Processor E3800 Product Family
Datasheet
2376





Bit Range	Default & Access	Field Name (ID): Description
15:12	0h RO	Number of Companion Controllers (N_CC_0): This field indicates the number of companion controllers associated with this USB 2.0 host controller. A zero in this field indicates there are no companion host controllers. Port-ownership hand-off is not supported. Only high-speed devices are supported on the host controller root ports. A value larger than one in this field indicates there are companion USB 1.1 host controller(s). Port-ownership hand-offs are supported. High, Full- and Low-speed devices are supported on the host controller root ports. There are no companion controllers. This field is set to '0' as Read-Only bit. Power Well: Core
11:8	0h RO	Number of Ports per Companion Controller (N_PCC_0): This field indicates the number of ports supported per companion host controller. It is used to indicate the port routing configuration to system software. Read-Only. This register is only reset by the resume power well going low. It is not reset by a D3-to-D0 state transition or HCRESET (Host Controller Reset) Power Well: Core
7	0b RO	Port Routing Rules (PRR_0): This field indicates the method used by this implementation for how all ports are mapped to companion controllers. This is hardwired to 0, indicating that the first N_PCC (=2) ports are routed to the lowest numbered function companion host controller, the next N_PCC ports are routed to the next lowest function companion controller, and so on Power Well: Resume
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3:0	8h RW	N_PORTS (NPORTS_0): This field specifies the number of physical downstream ports implemented on this host controller. The value of this field determines how many port registers are addressable in the Operational Register Space. Valid values are in the range of 1H to FH. The default value for the EHCI controller indicates 8 ports. BIOS may overwrite the default value to properly describe the board or chip SKU . (please refer to RMH Configuration Details in section 1.23.2). A zero in this field is undefined. Integrated RMH - If USB_R is disabled, this should be updated by BIOS to 2 such that the EHC reports 2ports to be default, port 0 assigned to the RMH and port 1 assigned to the debug device. If USB-R is enabled, the number reported should be updated to 3 by BIOS (port 2 will be assigned to USB-R in this case) Legacy Mode - The default value for the EHCI controller indicates 8 ports. If USB-R support is enabled, BIOS should account for the additional ports in calculating the value to write to this field. Power Well: Resume



18.9.3 Host Controller Capability Parameters (HCCPARAMS)—Offset 8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 8h

MBAR Type: PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00036881h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RSVD				ASPFC_0	PSPFC_0	EECP_0	IST_0	RSVD
								ASPC_0
								PFLF_0
								AC64_0

Bit Range	Default & Access	Field Name (ID): Description
31:18	00000000 00000b RO	Reserved (RSVD): Reserved.
17	1b RW	Asynchronous Schedule Prefetch Capability (ASPFC_0): This bit indicates that the hardware supports the Async schedule prefetch enable bit in the USB command register. Power Well: Resume
16	1b RW	Periodic Schedule Prefetch Capability (PSPFC_0): This bit indicates that the EHC hardware supports the Periodic Schedule prefetch bit in the USB2 Command Register. Power Well: Core
15:8	68h RO	EHCI Extended Capabilities Pointer (EECP_0): This field is hardwired to 68h, indicating that the EHCI capabilities list exists and begins at offset 68h in the PCI configuration space. Power Well: Resume
7:4	8h RO	Isochronous Scheduling Threshold (IST_0): This field indicates, relative to the current position of the executing host controller, where software can reliably update the isochronous schedule. When bit [7] is zero, the value of the least significant 3 bits indicates the number of micro-frames a host controller hold a set of isochronous data structures (one or more) before flushing the state. When bit [7] is a one, then host software assumes the host controller may cache an isochronous data structure for an entire frame. Refer to the EHCI specification for details on how software uses this information for scheduling isochronous transfers. The Intel USB2 hardwires this field to 8h. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved (RSVD): Reserved.
23:16	08h RW	Interrupt Threshold Control (ITC_0): This field is used by system software to select the maximum rate at which the host controller will issue interrupts. The only valid values are defined below. If software writes an invalid value to this register, the results are undefined. Value Maximum Interrupt Interval 00h Reserved 01h 1 micro-frame 02h 2 micro-frames 04h 4 micro-frames 08h 8 micro-frames (default, equates to 1 ms) 10h 16 micro-frames (2 ms) 20h 32 micro-frames (4 ms) 40h 64 micro-frames (8 ms) Refer to Section 4 in the EHCI specification for interrupts affected by this field. Power Well: Core
15:14	00b RO	Reserved (RSVD): Reserved.
13	0b RO	Reserved (RSVD): Reserved.
12	0h RO	Reserved (RSVD): Reserved.
11:8	0h RO	Unimplemented Asynchronous Park Mode Bits (UAPMB_0): This field is hardwired to 000b because the host controller does not support this optional feature. Power Well: Core
7	0b RO	Light Host Controller Reset (LHCR_0): Read Only 0b. The Intel EHC does not implement this optional reset and hardwires this bit to 0. Power Well: Core
6	0b RW	Interrupt on Async Advance Doorbell (IAAD_0): This bit is used as a doorbell by software to tell the host controller to issue an interrupt the next time it advances asynchronous schedule. Software must write a 1 to this bit to ring the doorbell. When the host controller has evicted all appropriate cached schedule state, it sets the Interrupt on Async Advance status bit in the USBSTS register. If the Interrupt on Async Advance Enable bit in the USBINTR register is a one then the host controller will assert an interrupt at the next interrupt threshold. See the EHCI specification for operational details. The host controller sets this bit to a zero after it has set the Interrupt on Async Advance status bit in the USBSTS register to a one. Software should not write a one to this bit when the asynchronous schedule is disabled. Doing so will yield undefined results. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
5	0b RW	Asynchronous Schedule Enable (ASE_0): This bit controls whether the host controller skips processing the Asynchronous Schedule. Values mean: 0b Do not process the Asynchronous Schedule 1b Use the ASYNCLISTADDR register to access the Asynchronous Schedule. Power Well: Core
4	0b RW	Periodic Schedule Enable (PSE_0): This bit controls whether the host controller skips processing the Periodic Schedule. Values mean: 0b Do not process the Periodic Schedule 1b Use the PERIODICLISTBASE register to access the Periodic Schedule. Power Well: Core
3:2	00b RO	Frame List Size (FLS_0): This field is R/W only if Programmable Frame List Flag in the HCCPARAMS registers is set to a one. . This field specifies the size of the frame list. The size the frame list controls which bits in the Frame Index Register should be used for the Frame List Current index. Values mean: 00b 1024 elements (4096 bytes) Default value; 01b 512 elements (2048 bytes); 10b 256 elements (1024 bytes) - for resource-constrained environments Power Well: Core
1	0b RW	Host Controller Reset (HCRESET_0): This control bit used by software to reset the host controller. The effects of this on Root Hub registers are similar to a Chip Hardware Reset. When software writes a one to this bit, the Host Controller resets its internal pipelines, timers, counters, state machines, etc. to their initial value. Any transaction currently in progress on USB is immediately terminated. A USB reset is not driven on downstream ports. Note: PCI Configuration registers and Host Controller Capability Registers are not affected by this reset. All operational registers, including port registers and port state machines are set to their initial values. Port ownership will be disowned by the host controller(s), with the side effects described in the EHCI spec. Software must reinitialize the host controller in order to return the host controller to an operational state. This bit is set to zero by the Host Controller when the reset process is complete. Software cannot terminate the reset process early by writing a zero to this register. Software should not set this bit to a one when the HCHalted bit in the USBSTS register is a zero. Attempting to reset an actively running host controller will result in undefined behavior. This reset must be used to leave EHCI port test modes. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Run/Stop (RS_0): 1=Run. 0=Stop. When set to a 1, the Host Controller proceeds with execution of the schedule. The Host Controller continues execution as long as this bit is set to a 1. When this bit is set to 0, the Host Controller completes the current and any actively pipelined transactions on the USB and then halts. The Host Controller must halt within 16 microframes after software clears the Run bit. The HC Halted bit in the status register indicates when the Host Controller has finished its pending pipelined transactions and has entered the stopped state. Software should not write a 1 to this field unless the host controller is in the Halted state (i.e. HCHalted in the USBSTS register is a one). The following table explains how the different combinations of Run and Halted must be interpreted: Run/Stop Halted Interpretation 0 0 Valid- in the process of halting 0 1 Valid- halted 1 0 Valid- running 1 1 Invalid- the HCHalted bit clears immediately Memory read cycles initiated by the EHC that receive any status other than Successful will result in this bit being cleared (and also affect the Host Error bit). Power Well: Core

18.9.5 USB2 Status (USB2STS)—Offset 24h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 24h**MBAR Type:** PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00001000h

31	28	24	20	16	12	8	4	0						
0	0	0	0	0	0	0	0	0						
RSVD				ASS_0	PSS_0	RECL_0	HCHALT_0	RSVD	IAA_0	HSE_0	FLR_0	PCD_0	USBBERRINT_0	USBBERRINT_0

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved (RSVD): Reserved.




Bit Range	Default & Access	Field Name (ID): Description
15	0b RO	Asynchronous Schedule Status (ASS_0): This bit reports the current real status of the Asynchronous Schedule. If this bit is a zero then the status of the Asynchronous Schedule is disabled. If this bit is a one then the status of the Asynchronous Schedule is enabled. The Host Controller is not required to immediately disable or enable the Asynchronous Schedule when software transitions the Asynchronous Schedule Enable bit in the USBCMD register. When this bit and the Asynchronous Schedule Enable bit are the same value, the Asynchronous Schedule is either enabled (1) or disabled (0). Power Well: Core
14	0b RO	Periodic Schedule Status (PSS_0): This bit reports the current real status of the Periodic Schedule. If this bit is a zero then the status of the Periodic Schedule is disabled. If this bit is a one then the status of the Periodic Schedule is enabled. The Host Controller is not required to immediately disable or enable the Periodic Schedule when software transitions the Periodic Schedule Enable bit in the USBCMD register. When this bit and the Periodic Schedule Enable bit are the same value, the Periodic Schedule is either enabled (1) or disabled (0). The Prefetch-Based Pause feature prevents this bit from transitioning to 0 if it currently has a request pending, in addition to the regular Periodic DMA engine. Power Well: Core
13	0b RO	Reclamation (RECL_0): This is a read-only status bit, which is used to detect an empty asynchronous schedule. The operational model and valid transitions for this bit are described in Section 4 of the EHCI Specification. Power Well: Core
12	1b RO	HCHalted (HCHALT_0): This bit is a zero whenever the Run/Stop bit is a one. The Host Controller sets this bit to 1 after it has stopped executing as a result of the Run/Stop bit being set to 0, either by software or by the Host Controller hardware (e.g. internal error). The Prefetch-Based Pause feature prevents this bit from transitioning to 0 if it is currently has a request pending, in addition to the regular DMA engines. Power Well: Core
11:6	000000b RO	Reserved (RSVD): Reserved.
5	0b RWC	Interrupt on Async Advance (IAA_0): System software can force the host controller to issue an interrupt the next time the host controller advances the asynchronous schedule by writing a one to the Interrupt on Async Advance Doorbell bit in the USBCMD register. This status bit indicates the assertion of that interrupt source. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
4	0b RWC	Host System Error (HSE_0): The Host Controller sets this bit to 1 when a serious error occurs during a host system access involving the Host Controller module. Memory read cycles initiated by the EHC that receive any status other than Successful will result in this bit being set. When this error occurs, the Host Controller clears the Run/Stop bit in the Command register to prevent further execution of the scheduled TDs. A hardware interrupt is generated to the system (if enabled in the Interrupt Enable Register). Power Well: Core
3	0b RWC	Frame List Rollover (FLR_0): The Host Controller sets this bit to a one when the Frame List Index (see Section 9.3.2.4) rolls over from its maximum value to zero. Since the USB2 SIP only supports the 1024-entry Frame List Size, the Frame List Index rolls over every time FRNUM[13] toggles. Power Well: Core
2	0b RWC	Port Change Detect (PCD_0): The Host Controller sets this bit to a one when any port for which the Port Owner bit is set to zero has a change bit transition from a zero to a one or a Force Port Resume bit transition from a zero to a one as a result of a J-K transition detected on a suspended port. This bit will also be set as a result of the Connect Status Change being set to a one after system software has relinquished ownership of a connected port by writing a zero to a port's Port Owner bit. This bit is allowed to be maintained in the Auxiliary power well. Alternatively, it is also acceptable that on a D3 to D0 transition of the EHCI HC device, this bit is loaded with the OR of all of the PORTSC change bits (including: Force port resume, over-current change, enable/disable change and connect status change). Regardless of the implementation, whenever this bit is readable (i.e., in the D0 state), it must provide a valid view of the Port Status registers. Power Well: Core
1	0b RWC	USB Error Interrupt (USBERRINT_0): The Host Controller sets this bit to 1 when completion of a USB transaction results in an error condition (e.g., error counter underflow). If the TD on which the error interrupt occurred also had its IOC bit set, both this bit and Bit 0 are set. See the EHCI specification for a list of the USB errors that will result in this interrupt being asserted. Power Well: Core
0	0b RWC	USB Interrupt (USBINT_0): The Host Controller sets this bit to 1 on the completion of a USB transaction, which results in the retirement of a Transfer Descriptor that had its IOC bit set. The Host Controller also sets this bit to 1 when a short packet is detected (actual number of bytes received was less than the expected number of bytes). Power Well: Core

18.9.6 USB2 Interrupt Enable (USB2INTR)—Offset 28h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 28h

MBAR Type: PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							IAAE_0	0
							HSEE_0	0
							FLRE_0	0
							PCIE_0	0
							USBEIE_0	0
							USBIE_0	0

Bit Range	Default & Access	Field Name (ID): Description
31:6	0000000h RO	Reserved (RSVD): Reserved.
5	0b RW	Interrupt on Async Advance Enable (IAAE_0): When this bit is a one, and the Interrupt on Async Advance bit in the USBSTS register is a one, the host controller will issue an interrupt at the next interrupt threshold. The interrupt is acknowledged by software clearing the Interrupt on Async Advance bit. Power Well: Core
4	0b RW	Host System Error Enable (HSEE_0): When this bit is a one, and the Host System Error Status bit in the USBSTS register is a one, the host controller will issue an interrupt. The interrupt is acknowledged by software clearing the Host System Error bit. Power Well: Core
3	0b RW	Frame List Rollover Enable (FLRE_0): When this bit is a one, and the Frame List Rollover bit in the USBSTS register is a one, the host controller will issue an interrupt. The interrupt is acknowledged by software clearing the Frame List Rollover bit. Power Well: Core
2	0b RW	Port Change Interrupt Enable (PCIE_0): When this bit is a one, and the Port Change Detect bit in the USBSTS register is a one, the host controller will issue an interrupt. The interrupt is acknowledged by software clearing the Port Change Detect bit. Power Well: Core
1	0b RW	USB Error Interrupt Enable (USBEIE_0): When this bit is a one, and the USBERRINT bit in the USBSTS register is a one, the host controller will issue an interrupt at the next interrupt threshold. The interrupt is acknowledged by software by clearing the USBERRINT bit. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	USB Interrupt Enable (USBIE_0): When this bit is a one, and the USBINT bit in the USBSTS register is a one, the host controller will issue an interrupt at the next interrupt threshold. The interrupt is acknowledged by software by clearing the USBINT bit. Power Well: Core

18.9.7 Frame Index (FRINDEX)—Offset 2Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 2Ch

MBAR Type: PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD					FLCIFN_0			

Bit Range	Default & Access	Field Name (ID): Description
31:14	000000000 000000000 b RO	Reserved (RSVD): Reserved.
13:0	000000000 00000b RW	Frame List Current Index/Frame Number (FLCIFN_0): The value in this register increments at the end of each time frame (e.g. micro-frame). Bits (12:3) are used for the Frame List current index. This means that each location of the frame list is accessed 8 times (frames or micro-frames) before moving to the next index Power Well: Core

18.9.8 Control Data Structure Segment Register (CTRLDSSEGMENT)—Offset 30h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 30h**MBAR Type:** PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BALow_0): These bits correspond to memory address signals (31:12), respectively. Power Well: Core
11:0	000000000 000b RO	Reserved (RSVD): Reserved.

18.9.10 Current Asynchronous List Address (ASYNCLISTADDR)—Offset 38h



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 38h

MBAR Type: PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LPL_0								RSVD

Bit Range	Default & Access	Field Name (ID): Description
31:5	0000000h RW	Link Pointer Low (LPL_0): These bits correspond to memory address signals (31:5), respectively. This field may only reference a Queue Head (QH). Power Well: Core
4:0	0000b RO	Reserved (RSVD): Reserved.

18.9.11 Configure Flag Register (CONFIGFLAG)—Offset 60h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 60h

MBAR Type: PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD								CF_0

Bit Range	Default & Access	Field Name (ID): Description
31:1	00000000h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Configure Flag (CF_0): Host software sets this bit as the last action in its process of configuring the Host Controller. This bit controls the default port-routing control logic. Bit values and side-effects are listed below. See section 4 of the EHCI spec for operation details. 0b Port routing control logic default-routes each port to the classic host controllers. 1b Port routing control logic default-routes all ports to this host controller. This register is in the suspend power well. It is only reset by hardware when the suspend power is initially applied or in response to a host controller reset. Power Well: Resume

18.9.12 Port Status and Control (PORTSC1)—Offset 64h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [MBAR] + 64h**MBAR Type:** PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00003000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:23	000h RO	Reserved (RSVD): Reserved.
22	0b RW	Wake on Over-current Enable (WKOCE_P0_0): Writing this bit to a one enables the port to be sensitive to over-current conditions as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Over-current Active bit (bit 4 of this register) is set. Power Well: Resume
21	0b RW	Wake on Disconnect Enable (WKDSCNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device disconnects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from connected to disconnected (i.e., bit 0 of this register changes from 1 to 0). Power Well: Resume
20	0b RW	Wake on Connect Enable (WKCENTE_P0_0): Writing this bit to a one enables the port to be sensitive to device connects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from disconnected to connected (i.e., bit 0 of this register changes from 0 to 1). Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
19:16	0h RW	Port Test Control (PTC_P0_0): When this field is zero, the port is NOT operating in a test mode. A non-zero value indicates that it is operating in test mode and the specific test mode is indicated by the specific value. The encoding of the test mode bits are (0110b - 1111b are reserved): Bits Test Mode 0000b Test mode not enabled 0001b Test J_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0010b Test K_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0011b Test SE0_NAK 0100b Test Packet 0101b Test FORCE_ENABLE Refer to USB Specification Revision 2.0, Chapter 7 and the EHCI specification, Chapter 4 for details on each test mode. The EHC does not support the option to run the port tests while the Run/Stop bit is a one. Power Well: Resume
15:14	00b RW	Port Indicator Control (PIC_P0_0): Writing to these bits directly controls the corresponding LED output pins. Bit 15 is inverted to generate USBLEDG#(n) where n is the port number. Bit 14 is inverted to generate USBLEDA#(n). Software is responsible for controlling these as specified in the USB Specification Revision 2.0. Bit Value Meaning 00b Port indicators are off 01b Amber 10b Green 11b Undefined The Intel EHC only supports bit value of 00b. Other values will result in unspecified behavior. Power Well: Resume
13	1b RW	Port Owner (PO_P0_0): This bit unconditionally goes to a 0b when the Configure Flag makes a 0b to 1b transition. This bit unconditionally goes to 1b whenever the Configure Flag bit is zero. System software uses this field to release ownership of the port to a selected host controller (in the event that the attached device is not a high-speed device). Software writes a one to this bit when the attached device is not a high-speed device. A one in this bit means that a companion host controller owns and controls the port. See Section 4 of the EHCI Specification for operational details. Power Well: Resume
12	1b RO	Port Power (PP_P0_0): Hard-wired with a value of '1' on the Intel EHC. This indicates that the port does have power. Power Well: Resume
11:10	00b RO	Line Status (LS_P0_0): These bits reflect the current logical levels of the D+ (bit 11) and D- (bit 10) signal lines. These bits are used for detection of low-speed USB devices prior to the port reset and enable sequence. This field is valid only when the port enable bit is zero and the current connect status bit is set to a one. The encoding of the bits are: Bits(11:10) USB State Interpretation 00b SE0 Not Low-speed device, perform EHCI reset 10b J-state Not Low-speed device, perform EHCI reset 01b K-state Low-speed device, release ownership of port 11b Undefined Not Low-speed device, perform EHCI reset Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
9	0b RO	Reserved (RSVD): Reserved.
8	0b RW	Port Reset (PORTRST_P0_0): 1=Port is in Reset. 0=Port is not in Reset. Default = 0. When software writes a one to this bit (from a zero), the bus reset sequence as defined in the USB Specification Revision 2.0 is started. Software writes a zero to this bit to terminate the bus reset sequence. Software must keep this bit at a one long enough to guarantee the reset sequence, as specified in the USB Specification Revision 2.0, completes. Note: when software writes this bit to a one, it must also write a zero to the Port Enable bit. Note that when software writes a zero to this bit there may be a delay before the bit status changes to a zero. The bit status will not read as a zero until after the reset has completed. If the port is in high-speed mode after reset is complete, the host controller will automatically enable this port (e.g. set the Port Enable bit to a one). A host controller must terminate the reset and stabilize the state of the port within 2 milliseconds of software transitioning this bit from a one to a zero. For example: if the port detects that the attached device is high-speed during reset, then the host controller must have the port in the enabled state within 2ms of software writing this bit to a zero. The HCHalted bit in the USB2STS register should be a zero before software attempts to use this bit. The host controller may hold Port Reset asserted to a one when the HCHALTED bit is a one. The Run/Stop bit in the Command Register must be set in order for the Port Reset bit to be cleared. Power Well: Resume
7	0b RW	Suspend (SUSP_P0_0): 1=Port in suspend state. 0=Port not in suspend state. Port Enabled Bit and Suspend bit of this register define the port states as follows: Bits [Port Enabled, Suspend] Port State 0X Disable 10 Enable 11 Suspend When in suspend state, downstream propagation of data is blocked on this port, except for port reset. The blocking occurs at the end of the current transaction, if a transaction was in progress when this bit was written to a 1. In the suspend state, the port is sensitive to resume detection. Note that the bit status does not change until the port is suspended and that there may be a delay in suspending a port if there is a transaction currently in progress on the USB. A write of zero to this bit is ignored by the host controller. The host controller will unconditionally set this bit to a zero when: Software sets the Force Port Resume bit to a zero (from a one). Software sets the Port Reset bit to a one (from a zero). If host software sets this bit to a one when the port is not enabled (i.e. Port enabled bit is a zero) the results are undefined. Power Well: Resume




Bit Range	Default & Access	Field Name (ID): Description
6	0b RW	Force Port Resume (FPR_P0_0): 1= Resume detected/driven on port. 0=No resume (K-state) detected/driven on port. This functionality defined for manipulating this bit depends on the value of the Suspend bit. For example, if the port is not suspended (Suspend and Enabled bits are a one) and software transitions this bit to a one, then the effects on the bus are undefined. Software sets this bit to a 1 to drive resume signaling. The Host Controller sets this bit to a 1 if a J-to-K transition is detected while the port is in the Suspend state. When this bit transitions to a one because a J-to-K transition is detected, the Port Change Detect bit in the USBSTS register is also set to a one. If software sets this bit to a one, the host controller must not set the Port Change Detect bit. Note that when the EHCI controller owns the port, the resume sequence follows the defined sequence documented in the USB Specification Revision 2.0. The resume signaling (Full-speed 'K') is driven on the port as long as this bit remains a one. Software must appropriately time the Resume and set this bit to a zero when the appropriate amount of time has elapsed. Writing a zero (from one) causes the port to return to high-speed mode (forcing the bus below the port into a high-speed idle). This bit will remain a one until the port has switched to the high-speed idle. The host controller must complete this transition within 2 milliseconds of software setting this bit to a zero. Power Well: Resume
5	0b RWC	Over-current Change (OCC_P0_0): This bit gets set to a one when there is a change to the Over-current Active bit. Software clears this bit by writing a one to this bit position. The functionality of this bit is not dependent upon the port owner. Power Well: Resume
4	0b RO	Over-current Active (OACT_P0_0): 1=This port currently has an over-current condition. 0=This port does not have an over-current condition. This bit will automatically transition from a one to a zero when the over current condition is removed. The functionality of this bit is not dependent upon the port owner. The Intel EHC automatically disables the port when the over-current active bit is '1'. Power Well: Resume
3	0b RWC	Port Enable/Disable Change (PEDC_P0_0): 1=Port enabled/disabled status has changed. 0=No change. For the root hub, this bit gets set to a one only when a port is disabled due to the appropriate conditions existing at the EOF2 point (See Chapter 11 of the USB Specification for the definition of a port error). This bit is not set due to the Disabled-to-Enabled transition, nor due to a disconnect. Software clears this bit by writing a 1 to it. Power Well: Resume
2	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
21	0b RW	Wake on Disconnect Enable (WKDSCNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device disconnects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from connected to disconnected (i.e., bit 0 of this register changes from 1 to 0). Power Well: Resume
20	0b RW	Wake on Connect Enable (WKCNNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device connects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from disconnected to connected (i.e., bit 0 of this register changes from 0 to 1). Power Well: Resume
19:16	0h RW	Port Test Control (PTC_P0_0): When this field is zero, the port is NOT operating in a test mode. A non-zero value indicates that it is operating in test mode and the specific test mode is indicated by the specific value. The encoding of the test mode bits are (0110b - 1111b are reserved): Bits Test Mode 0000b Test mode not enabled 0001b Test J_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0010b Test K_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0011b Test SE0_NAK 0100b Test Packet 0101b Test FORCE_ENABLE Refer to USB Specification Revision 2.0, Chapter 7 and the EHCI specification, Chapter 4 for details on each test mode. The EHC does not support the option to run the port tests while the Run/Stop bit is a one. Power Well: Resume
15:14	00b RW	Port Indicator Control (PIC_P0_0): Writing to these bits directly controls the corresponding LED output pins. Bit 15 is inverted to generate USBLEDG#(n) where n is the port number. Bit 14 is inverted to generate USBLEDA#(n). Software is responsible for controlling these as specified in the USB Specification Revision 2.0. Bit Value Meaning 00b Port indicators are off 01b Amber 10b Green 11b Undefined The Intel EHC only supports bit value of 00b. Other values will result in unspecified behavior. Power Well: Resume
13	1b RW	Port Owner (PO_P0_0): This bit unconditionally goes to a 0b when the Configure Flag makes a 0b to 1b transition. This bit unconditionally goes to 1b whenever the Configure Flag bit is zero. System software uses this field to release ownership of the port to a selected host controller (in the event that the attached device is not a high-speed device). Software writes a one to this bit when the attached device is not a high-speed device. A one in this bit means that a companion host controller owns and controls the port. See Section 4 of the EHCI Specification for operational details. Power Well: Resume




Bit Range	Default & Access	Field Name (ID): Description
12	1b RO	Port Power (PP_P0_0): Hard-wired with a value of '1' on the Intel EHC. This indicates that the port does have power. Power Well: Resume
11:10	00b RO	Line Status (LS_P0_0): These bits reflect the current logical levels of the D+ (bit 11) and D- (bit 10) signal lines. These bits are used for detection of low-speed USB devices prior to the port reset and enable sequence. This field is valid only when the port enable bit is zero and the current connect status bit is set to a one. The encoding of the bits are: Bits(11:10) USB State Interpretation 00b SE0 Not Low-speed device, perform EHCI reset 10b J-state Not Low-speed device, perform EHCI reset 01b K-state Low-speed device, release ownership of port 11b Undefined Not Low-speed device, perform EHCI reset Power Well: Resume
9	0b RO	Reserved (RSVD): Reserved.
8	0b RW	Port Reset (PORTRST_P0_0): 1=Port is in Reset. 0=Port is not in Reset. Default = 0. When software writes a one to this bit (from a zero), the bus reset sequence as defined in the USB Specification Revision 2.0 is started. Software writes a zero to this bit to terminate the bus reset sequence. Software must keep this bit at a one long enough to guarantee the reset sequence, as specified in the USB Specification Revision 2.0, completes. Note: when software writes this bit to a one, it must also write a zero to the Port Enable bit. Note that when software writes a zero to this bit there may be a delay before the bit status changes to a zero. The bit status will not read as a zero until after the reset has completed. If the port is in high-speed mode after reset is complete, the host controller will automatically enable this port (e.g. set the Port Enable bit to a one). A host controller must terminate the reset and stabilize the state of the port within 2 milliseconds of software transitioning this bit from a one to a zero. For example: if the port detects that the attached device is high-speed during reset, then the host controller must have the port in the enabled state within 2ms of software writing this bit to a zero. The HCHalted bit in the USB2STS register should be a zero before software attempts to use this bit. The host controller may hold Port Reset asserted to a one when the HCHALTED bit is a one. The Run/Stop bit in the Command Register must be set in order for the Port Reset bit to be cleared. Power Well: Resume




Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	Suspend (SUSP_P0_0): 1=Port in suspend state. 0=Port not in suspend state. Port Enabled Bit and Suspend bit of this register define the port states as follows: Bits [Port Enabled, Suspend] Port State 0X Disable 10 Enable 11 Suspend When in suspend state, downstream propagation of data is blocked on this port, except for port reset. The blocking occurs at the end of the current transaction, if a transaction was in progress when this bit was written to a 1. In the suspend state, the port is sensitive to resume detection. Note that the bit status does not change until the port is suspended and that there may be a delay in suspending a port if there is a transaction currently in progress on the USB. A write of zero to this bit is ignored by the host controller. The host controller will unconditionally set this bit to a zero when: Software sets the Force Port Resume bit to a zero (from a one). Software sets the Port Reset bit to a one (from a zero). If host software sets this bit to a one when the port is not enabled (i.e. Port enabled bit is a zero) the results are undefined. Power Well: Resume
6	0b RW	Force Port Resume (FPR_P0_0): 1= Resume detected/driven on port. 0=No resume (K-state) detected/driven on port. This functionality defined for manipulating this bit depends on the value of the Suspend bit. For example, if the port is not suspended (Suspend and Enabled bits are a one) and software transitions this bit to a one, then the effects on the bus are undefined. Software sets this bit to a 1 to drive resume signaling. The Host Controller sets this bit to a 1 if a J-to-K transition is detected while the port is in the Suspend state. When this bit transitions to a one because a J-to-K transition is detected, the Port Change Detect bit in the USBSTS register is also set to a one. If software sets this bit to a one, the host controller must not set the Port Change Detect bit. Note that when the EHCI controller owns the port, the resume sequence follows the defined sequence documented in the USB Specification Revision 2.0. The resume signaling (Full-speed 'K') is driven on the port as long as this bit remains a one. Software must appropriately time the Resume and set this bit to a zero when the appropriate amount of time has elapsed. Writing a zero (from one) causes the port to return to high-speed mode (forcing the bus below the port into a high-speed idle). This bit will remain a one until the port has switched to the high-speed idle. The host controller must complete this transition within 2 milliseconds of software setting this bit to a zero. Power Well: Resume
5	0b RWC	Over-current Change (OCC_P0_0): This bit gets set to a one when there is a change to the Over-current Active bit. Software clears this bit by writing a one to this bit position. The functionality of this bit is not dependent upon the port owner. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
4	0b RO	Over-current Active (OACT_P0_0): 1=This port currently has an over-current condition. 0=This port does not have an over-current condition. This bit will automatically transition from a one to a zero when the over current condition is removed. The functionality of this bit is not dependent upon the port owner. The Intel EHC automatically disables the port when the over-current active bit is '1'. Power Well: Resume
3	0b RWC	Port Enable/Disable Change (PEDC_P0_0): 1=Port enabled/disabled status has changed. 0=No change. For the root hub, this bit gets set to a one only when a port is disabled due to the appropriate conditions existing at the EOF2 point (See Chapter 11 of the USB Specification for the definition of a port error). This bit is not set due to the Disabled-to-Enabled transition, nor due to a disconnect. Software clears this bit by writing a 1 to it. Power Well: Resume
2	0b RO	Reserved (RSVD): Reserved.
1	0b RWC	Connect Status Change (CSC_P0_0): 1=Change in Current Connect Status. 0=No change. Indicates a change has occurred in the port's Current Connect Status. The host controller sets this bit for all changes to the port device connect status, even if system software has not cleared an existing connect status change. For example, the insertion status changes twice before system software has cleared the changed condition, hub hardware will be 'setting' an already-set bit (i.e., the bit will remain set). Software sets this bit to 0 by writing a 1 to it. Power Well: Resume
0	0b RO	Current Connect Status (CCS_P0_0): 1=Device is present on port. 0=No device is present. This value reflects the current state of the port, and may not correspond directly to the event that caused the Connect Status Change bit (Bit 1) to be set. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
19:16	0h RW	Port Test Control (PTC_P0_0): When this field is zero, the port is NOT operating in a test mode. A non-zero value indicates that it is operating in test mode and the specific test mode is indicated by the specific value. The encoding of the test mode bits are (0110b - 1111b are reserved): Bits Test Mode 0000b Test mode not enabled 0001b Test J_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0010b Test K_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0011b Test SE0_NAK 0100b Test Packet 0101b Test FORCE_ENABLE Refer to USB Specification Revision 2.0, Chapter 7 and the EHCI specification, Chapter 4 for details on each test mode. The EHC does not support the option to run the port tests while the Run/Stop bit is a one. Power Well: Resume
15:14	00b RW	Port Indicator Control (PIC_P0_0): Writing to these bits directly controls the corresponding LED output pins. Bit 15 is inverted to generate USBLEDG#(n) where n is the port number. Bit 14 is inverted to generate USBLEDA#(n). Software is responsible for controlling these as specified in the USB Specification Revision 2.0. Bit Value Meaning 00b Port indicators are off 01b Amber 10b Green 11b Undefined The Intel EHC only supports bit value of 00b. Other values will result in unspecified behavior. Power Well: Resume
13	1b RW	Port Owner (PO_P0_0): This bit unconditionally goes to a 0b when the Configure Flag makes a 0b to 1b transition. This bit unconditionally goes to 1b whenever the Configure Flag bit is zero. System software uses this field to release ownership of the port to a selected host controller (in the event that the attached device is not a high-speed device). Software writes a one to this bit when the attached device is not a high-speed device. A one in this bit means that a companion host controller owns and controls the port. See Section 4 of the EHCI Specification for operational details. Power Well: Resume
12	1b RO	Port Power (PP_P0_0): Hard-wired with a value of '1' on the Intel EHC. This indicates that the port does have power. Power Well: Resume
11:10	00b RO	Line Status (LS_P0_0): These bits reflect the current logical levels of the D+ (bit 11) and D- (bit 10) signal lines. These bits are used for detection of low-speed USB devices prior to the port reset and enable sequence. This field is valid only when the port enable bit is zero and the current connect status bit is set to a one. The encoding of the bits are: Bits(11:10) USB State Interpretation 00b SE0 Not Low-speed device, perform EHCI reset 10b J-state Not Low-speed device, perform EHCI reset 01b K-state Low-speed device, release ownership of port 11b Undefined Not Low-speed device, perform EHCI reset Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
9	0b RO	Reserved (RSVD): Reserved.
8	0b RW	Port Reset (PORTRST_P0_0): 1=Port is in Reset. 0=Port is not in Reset. Default = 0. When software writes a one to this bit (from a zero), the bus reset sequence as defined in the USB Specification Revision 2.0 is started. Software writes a zero to this bit to terminate the bus reset sequence. Software must keep this bit at a one long enough to guarantee the reset sequence, as specified in the USB Specification Revision 2.0, completes. Note: when software writes this bit to a one, it must also write a zero to the Port Enable bit. Note that when software writes a zero to this bit there may be a delay before the bit status changes to a zero. The bit status will not read as a zero until after the reset has completed. If the port is in high-speed mode after reset is complete, the host controller will automatically enable this port (e.g. set the Port Enable bit to a one). A host controller must terminate the reset and stabilize the state of the port within 2 milliseconds of software transitioning this bit from a one to a zero. For example: if the port detects that the attached device is high-speed during reset, then the host controller must have the port in the enabled state within 2ms of software writing this bit to a zero. The HCHalted bit in the USB2STS register should be a zero before software attempts to use this bit. The host controller may hold Port Reset asserted to a one when the HCHALTED bit is a one. The Run/Stop bit in the Command Register must be set in order for the Port Reset bit to be cleared. Power Well: Resume
7	0b RW	Suspend (SUSP_P0_0): 1=Port in suspend state. 0=Port not in suspend state. Port Enabled Bit and Suspend bit of this register define the port states as follows: Bits [Port Enabled, Suspend] Port State 0X Disable 10 Enable 11 Suspend When in suspend state, downstream propagation of data is blocked on this port, except for port reset. The blocking occurs at the end of the current transaction, if a transaction was in progress when this bit was written to a 1. In the suspend state, the port is sensitive to resume detection. Note that the bit status does not change until the port is suspended and that there may be a delay in suspending a port if there is a transaction currently in progress on the USB. A write of zero to this bit is ignored by the host controller. The host controller will unconditionally set this bit to a zero when: Software sets the Force Port Resume bit to a zero (from a one). Software sets the Port Reset bit to a one (from a zero). If host software sets this bit to a one when the port is not enabled (i.e. Port enabled bit is a zero) the results are undefined. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
6	0b RW	Force Port Resume (FPR_P0_0): 1= Resume detected/driven on port. 0=No resume (K-state) detected/driven on port. This functionality defined for manipulating this bit depends on the value of the Suspend bit. For example, if the port is not suspended (Suspend and Enabled bits are a one) and software transitions this bit to a one, then the effects on the bus are undefined. Software sets this bit to a 1 to drive resume signaling. The Host Controller sets this bit to a 1 if a J-to-K transition is detected while the port is in the Suspend state. When this bit transitions to a one because a J-to-K transition is detected, the Port Change Detect bit in the USBSTS register is also set to a one. If software sets this bit to a one, the host controller must not set the Port Change Detect bit. Note that when the EHCI controller owns the port, the resume sequence follows the defined sequence documented in the USB Specification Revision 2.0. The resume signaling (Full-speed 'K') is driven on the port as long as this bit remains a one. Software must appropriately time the Resume and set this bit to a zero when the appropriate amount of time has elapsed. Writing a zero (from one) causes the port to return to high-speed mode (forcing the bus below the port into a high-speed idle). This bit will remain a one until the port has switched to the high-speed idle. The host controller must complete this transition within 2 milliseconds of software setting this bit to a zero. Power Well: Resume
5	0b RWC	Over-current Change (OCC_P0_0): This bit gets set to a one when there is a change to the Over-current Active bit. Software clears this bit by writing a one to this bit position. The functionality of this bit is not dependent upon the port owner. Power Well: Resume
4	0b RO	Over-current Active (OACT_P0_0): 1=This port currently has an over-current condition. 0=This port does not have an over-current condition. This bit will automatically transition from a one to a zero when the over current condition is removed. The functionality of this bit is not dependent upon the port owner. The Intel EHC automatically disables the port when the over-current active bit is '1'. Power Well: Resume
3	0b RWC	Port Enable/Disable Change (PEDC_P0_0): 1=Port enabled/disabled status has changed. 0=No change. For the root hub, this bit gets set to a one only when a port is disabled due to the appropriate conditions existing at the EOF2 point (See Chapter 11 of the USB Specification for the definition of a port error). This bit is not set due to the Disabled-to-Enabled transition, nor due to a disconnect. Software clears this bit by writing a 1 to it. Power Well: Resume
2	0b RO	Reserved (RSVD): Reserved.



Type: Memory Mapped I/O Register
(Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

	31	28	24	20	16	12	8	4	0
	0	0	0	0	0	0	0	0	0
	RSVD			WKOCE_P0_0 WKDSCNNT_P0_0 WKCNNTE_P0_0	PTC_P0_0	PIC_P0_0 PO_P0_0 PP_P0_0 LS_P0_0	RSVD PORTST_P0_0 SUSP_P0_0 FPR_P0_0 OCC_P0_0 OACT_P0_0 PEDC_P0_0	RSVD CSC_P0_0 CCS_P0_0	



Bit Range	Default & Access	Field Name (ID): Description
21	0b RW	Wake on Disconnect Enable (WKDSCNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device disconnects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from connected to disconnected (i.e., bit 0 of this register changes from 1 to 0). Power Well: Resume
20	0b RW	Wake on Connect Enable (WKCNNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device connects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from disconnected to connected (i.e., bit 0 of this register changes from 0 to 1). Power Well: Resume
19:16	0h RW	Port Test Control (PTC_P0_0): When this field is zero, the port is NOT operating in a test mode. A non-zero value indicates that it is operating in test mode and the specific test mode is indicated by the specific value. The encoding of the test mode bits are (0110b - 1111b are reserved): Bits Test Mode 0000b Test mode not enabled 0001b Test J_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0010b Test K_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0011b Test SE0_NAK 0100b Test Packet 0101b Test FORCE_ENABLE Refer to USB Specification Revision 2.0, Chapter 7 and the EHCI specification, Chapter 4 for details on each test mode. The EHC does not support the option to run the port tests while the Run/Stop bit is a one. Power Well: Resume
15:14	00b RW	Port Indicator Control (PIC_P0_0): Writing to these bits directly controls the corresponding LED output pins. Bit 15 is inverted to generate USBLEDG#(n) where n is the port number. Bit 14 is inverted to generate USBLEDA#(n). Software is responsible for controlling these as specified in the USB Specification Revision 2.0. Bit Value Meaning 00b Port indicators are off 01b Amber 10b Green 11b Undefined The Intel EHC only supports bit value of 00b. Other values will result in unspecified behavior. Power Well: Resume
13	1b RW	Port Owner (PO_P0_0): This bit unconditionally goes to a 0b when the Configure Flag makes a 0b to 1b transition. This bit unconditionally goes to 1b whenever the Configure Flag bit is zero. System software uses this field to release ownership of the port to a selected host controller (in the event that the attached device is not a high-speed device). Software writes a one to this bit when the attached device is not a high-speed device. A one in this bit means that a companion host controller owns and controls the port. See Section 4 of the EHCI Specification for operational details. Power Well: Resume




Bit Range	Default & Access	Field Name (ID): Description
12	1b RO	Port Power (PP_P0_0): Hard-wired with a value of '1' on the Intel EHC. This indicates that the port does have power. Power Well: Resume
11:10	00b RO	Line Status (LS_P0_0): These bits reflect the current logical levels of the D+ (bit 11) and D- (bit 10) signal lines. These bits are used for detection of low-speed USB devices prior to the port reset and enable sequence. This field is valid only when the port enable bit is zero and the current connect status bit is set to a one. The encoding of the bits are: Bits(11:10) USB State Interpretation 00b SE0 Not Low-speed device, perform EHCI reset 10b J-state Not Low-speed device, perform EHCI reset 01b K-state Low-speed device, release ownership of port 11b Undefined Not Low-speed device, perform EHCI reset Power Well: Resume
9	0b RO	Reserved (RSVD): Reserved.
8	0b RW	Port Reset (PORTRST_P0_0): 1=Port is in Reset. 0=Port is not in Reset. Default = 0. When software writes a one to this bit (from a zero), the bus reset sequence as defined in the USB Specification Revision 2.0 is started. Software writes a zero to this bit to terminate the bus reset sequence. Software must keep this bit at a one long enough to guarantee the reset sequence, as specified in the USB Specification Revision 2.0, completes. Note: when software writes this bit to a one, it must also write a zero to the Port Enable bit. Note that when software writes a zero to this bit there may be a delay before the bit status changes to a zero. The bit status will not read as a zero until after the reset has completed. If the port is in high-speed mode after reset is complete, the host controller will automatically enable this port (e.g. set the Port Enable bit to a one). A host controller must terminate the reset and stabilize the state of the port within 2 milliseconds of software transitioning this bit from a one to a zero. For example: if the port detects that the attached device is high-speed during reset, then the host controller must have the port in the enabled state within 2ms of software writing this bit to a zero. The HCHalted bit in the USB2STS register should be a zero before software attempts to use this bit. The host controller may hold Port Reset asserted to a one when the HCHALTED bit is a one. The Run/Stop bit in the Command Register must be set in order for the Port Reset bit to be cleared. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	Suspend (SUSP_P0_0): 1=Port in suspend state. 0=Port not in suspend state. Port Enabled Bit and Suspend bit of this register define the port states as follows: Bits [Port Enabled, Suspend] Port State 0X Disable 10 Enable 11 Suspend When in suspend state, downstream propagation of data is blocked on this port, except for port reset. The blocking occurs at the end of the current transaction, if a transaction was in progress when this bit was written to a 1. In the suspend state, the port is sensitive to resume detection. Note that the bit status does not change until the port is suspended and that there may be a delay in suspending a port if there is a transaction currently in progress on the USB. A write of zero to this bit is ignored by the host controller. The host controller will unconditionally set this bit to a zero when: Software sets the Force Port Resume bit to a zero (from a one). Software sets the Port Reset bit to a one (from a zero). If host software sets this bit to a one when the port is not enabled (i.e. Port enabled bit is a zero) the results are undefined. Power Well: Resume
6	0b RW	Force Port Resume (FPR_P0_0): 1= Resume detected/driven on port. 0=No resume (K-state) detected/driven on port. This functionality defined for manipulating this bit depends on the value of the Suspend bit. For example, if the port is not suspended (Suspend and Enabled bits are a one) and software transitions this bit to a one, then the effects on the bus are undefined. Software sets this bit to a 1 to drive resume signaling. The Host Controller sets this bit to a 1 if a J-to-K transition is detected while the port is in the Suspend state. When this bit transitions to a one because a J-to-K transition is detected, the Port Change Detect bit in the USBSTS register is also set to a one. If software sets this bit to a one, the host controller must not set the Port Change Detect bit. Note that when the EHCI controller owns the port, the resume sequence follows the defined sequence documented in the USB Specification Revision 2.0. The resume signaling (Full-speed 'K') is driven on the port as long as this bit remains a one. Software must appropriately time the Resume and set this bit to a zero when the appropriate amount of time has elapsed. Writing a zero (from one) causes the port to return to high-speed mode (forcing the bus below the port into a high-speed idle). This bit will remain a one until the port has switched to the high-speed idle. The host controller must complete this transition within 2 milliseconds of software setting this bit to a zero. Power Well: Resume
5	0b RWC	Over-current Change (OCC_P0_0): This bit gets set to a one when there is a change to the Over-current Active bit. Software clears this bit by writing a one to this bit position. The functionality of this bit is not dependent upon the port owner. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
4	0b RO	Over-current Active (OACT_P0_0): 1=This port currently has an over-current condition. 0=This port does not have an over-current condition. This bit will automatically transition from a one to a zero when the over current condition is removed. The functionality of this bit is not dependent upon the port owner. The Intel EHC automatically disables the port when the over-current active bit is '1'. Power Well: Resume
3	0b RWC	Port Enable/Disable Change (PEDC_P0_0): 1=Port enabled/disabled status has changed. 0=No change. For the root hub, this bit gets set to a one only when a port is disabled due to the appropriate conditions existing at the EOF2 point (See Chapter 11 of the USB Specification for the definition of a port error). This bit is not set due to the Disabled-to-Enabled transition, nor due to a disconnect. Software clears this bit by writing a 1 to it. Power Well: Resume
2	0b RO	Reserved (RSVD): Reserved.
1	0b RWC	Connect Status Change (CSC_P0_0): 1=Change in Current Connect Status. 0=No change. Indicates a change has occurred in the port's Current Connect Status. The host controller sets this bit for all changes to the port device connect status, even if system software has not cleared an existing connect status change. For example, the insertion status changes twice before system software has cleared the changed condition, hub hardware will be 'setting' an already-set bit (i.e., the bit will remain set). Software sets this bit to 0 by writing a 1 to it. Power Well: Resume
0	0b RO	Current Connect Status (CCS_P0_0): 1=Device is present on port. 0=No device is present. This value reflects the current state of the port, and may not correspond directly to the event that caused the Connect Status Change bit (Bit 1) to be set. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
19:16	0h RW	Port Test Control (PTC_P0_0): When this field is zero, the port is NOT operating in a test mode. A non-zero value indicates that it is operating in test mode and the specific test mode is indicated by the specific value. The encoding of the test mode bits are (0110b - 1111b are reserved): Bits Test Mode 0000b Test mode not enabled 0001b Test J_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0010b Test K_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0011b Test SE0_NAK 0100b Test Packet 0101b Test FORCE_ENABLE Refer to USB Specification Revision 2.0, Chapter 7 and the EHCI specification, Chapter 4 for details on each test mode. The EHC does not support the option to run the port tests while the Run/Stop bit is a one. Power Well: Resume
15:14	00b RW	Port Indicator Control (PIC_P0_0): Writing to these bits directly controls the corresponding LED output pins. Bit 15 is inverted to generate USBLEDG#(n) where n is the port number. Bit 14 is inverted to generate USBLEDA#(n). Software is responsible for controlling these as specified in the USB Specification Revision 2.0. Bit Value Meaning 00b Port indicators are off 01b Amber 10b Green 11b Undefined The Intel EHC only supports bit value of 00b. Other values will result in unspecified behavior. Power Well: Resume
13	1b RW	Port Owner (PO_P0_0): This bit unconditionally goes to a 0b when the Configure Flag makes a 0b to 1b transition. This bit unconditionally goes to 1b whenever the Configure Flag bit is zero. System software uses this field to release ownership of the port to a selected host controller (in the event that the attached device is not a high-speed device). Software writes a one to this bit when the attached device is not a high-speed device. A one in this bit means that a companion host controller owns and controls the port. See Section 4 of the EHCI Specification for operational details. Power Well: Resume
12	1b RO	Port Power (PP_P0_0): Hard-wired with a value of '1' on the Intel EHC. This indicates that the port does have power. Power Well: Resume
11:10	00b RO	Line Status (LS_P0_0): These bits reflect the current logical levels of the D+ (bit 11) and D- (bit 10) signal lines. These bits are used for detection of low-speed USB devices prior to the port reset and enable sequence. This field is valid only when the port enable bit is zero and the current connect status bit is set to a one. The encoding of the bits are: Bits(11:10) USB State Interpretation 00b SE0 Not Low-speed device, perform EHCI reset 10b J-state Not Low-speed device, perform EHCI reset 01b K-state Low-speed device, release ownership of port 11b Undefined Not Low-speed device, perform EHCI reset Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
9	0b RO	Reserved (RSVD): Reserved.
8	0b RW	Port Reset (PORTRST_P0_0): 1=Port is in Reset. 0=Port is not in Reset. Default = 0. When software writes a one to this bit (from a zero), the bus reset sequence as defined in the USB Specification Revision 2.0 is started. Software writes a zero to this bit to terminate the bus reset sequence. Software must keep this bit at a one long enough to guarantee the reset sequence, as specified in the USB Specification Revision 2.0, completes. Note: when software writes this bit to a one, it must also write a zero to the Port Enable bit. Note that when software writes a zero to this bit there may be a delay before the bit status changes to a zero. The bit status will not read as a zero until after the reset has completed. If the port is in high-speed mode after reset is complete, the host controller will automatically enable this port (e.g. set the Port Enable bit to a one). A host controller must terminate the reset and stabilize the state of the port within 2 milliseconds of software transitioning this bit from a one to a zero. For example: if the port detects that the attached device is high-speed during reset, then the host controller must have the port in the enabled state within 2ms of software writing this bit to a zero. The HCHalted bit in the USB2STS register should be a zero before software attempts to use this bit. The host controller may hold Port Reset asserted to a one when the HCHALTED bit is a one. The Run/Stop bit in the Command Register must be set in order for the Port Reset bit to be cleared. Power Well: Resume
7	0b RW	Suspend (SUSP_P0_0): 1=Port in suspend state. 0=Port not in suspend state. Port Enabled Bit and Suspend bit of this register define the port states as follows: Bits [Port Enabled, Suspend] Port State 0X Disable 10 Enable 11 Suspend When in suspend state, downstream propagation of data is blocked on this port, except for port reset. The blocking occurs at the end of the current transaction, if a transaction was in progress when this bit was written to a 1. In the suspend state, the port is sensitive to resume detection. Note that the bit status does not change until the port is suspended and that there may be a delay in suspending a port if there is a transaction currently in progress on the USB. A write of zero to this bit is ignored by the host controller. The host controller will unconditionally set this bit to a zero when: Software sets the Force Port Resume bit to a zero (from a one). Software sets the Port Reset bit to a one (from a zero). If host software sets this bit to a one when the port is not enabled (i.e. Port enabled bit is a zero) the results are undefined. Power Well: Resume




Bit Range	Default & Access	Field Name (ID): Description
6	0b RW	Force Port Resume (FPR_P0_0): 1= Resume detected/driven on port. 0=No resume (K-state) detected/driven on port. This functionality defined for manipulating this bit depends on the value of the Suspend bit. For example, if the port is not suspended (Suspend and Enabled bits are a one) and software transitions this bit to a one, then the effects on the bus are undefined. Software sets this bit to a 1 to drive resume signaling. The Host Controller sets this bit to a 1 if a J-to-K transition is detected while the port is in the Suspend state. When this bit transitions to a one because a J-to-K transition is detected, the Port Change Detect bit in the USBSTS register is also set to a one. If software sets this bit to a one, the host controller must not set the Port Change Detect bit. Note that when the EHCI controller owns the port, the resume sequence follows the defined sequence documented in the USB Specification Revision 2.0. The resume signaling (Full-speed 'K') is driven on the port as long as this bit remains a one. Software must appropriately time the Resume and set this bit to a zero when the appropriate amount of time has elapsed. Writing a zero (from one) causes the port to return to high-speed mode (forcing the bus below the port into a high-speed idle). This bit will remain a one until the port has switched to the high-speed idle. The host controller must complete this transition within 2 milliseconds of software setting this bit to a zero. Power Well: Resume
5	0b RWC	Over-current Change (OCC_P0_0): This bit gets set to a one when there is a change to the Over-current Active bit. Software clears this bit by writing a one to this bit position. The functionality of this bit is not dependent upon the port owner. Power Well: Resume
4	0b RO	Over-current Active (OACT_P0_0): 1=This port currently has an over-current condition. 0=This port does not have an over-current condition. This bit will automatically transition from a one to a zero when the over current condition is removed. The functionality of this bit is not dependent upon the port owner. The Intel EHC automatically disables the port when the over-current active bit is '1'. Power Well: Resume
3	0b RWC	Port Enable/Disable Change (PEDC_P0_0): 1=Port enabled/disabled status has changed. 0=No change. For the root hub, this bit gets set to a one only when a port is disabled due to the appropriate conditions existing at the EOF2 point (See Chapter 11 of the USB Specification for the definition of a port error). This bit is not set due to the Disabled-to-Enabled transition, nor due to a disconnect. Software clears this bit by writing a 1 to it. Power Well: Resume
2	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
21	0b RW	Wake on Disconnect Enable (WKDSCNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device disconnects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from connected to disconnected (i.e., bit 0 of this register changes from 1 to 0). Power Well: Resume
20	0b RW	Wake on Connect Enable (WKCNNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device connects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from disconnected to connected (i.e., bit 0 of this register changes from 0 to 1). Power Well: Resume
19:16	0h RW	Port Test Control (PTC_P0_0): When this field is zero, the port is NOT operating in a test mode. A non-zero value indicates that it is operating in test mode and the specific test mode is indicated by the specific value. The encoding of the test mode bits are (0110b - 1111b are reserved): Bits Test Mode 0000b Test mode not enabled 0001b Test J_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0010b Test K_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0011b Test SE0_NAK 0100b Test Packet 0101b Test FORCE_ENABLE Refer to USB Specification Revision 2.0, Chapter 7 and the EHCI specification, Chapter 4 for details on each test mode. The EHC does not support the option to run the port tests while the Run/Stop bit is a one. Power Well: Resume
15:14	00b RW	Port Indicator Control (PIC_P0_0): Writing to these bits directly controls the corresponding LED output pins. Bit 15 is inverted to generate USBLEDG#(n) where n is the port number. Bit 14 is inverted to generate USBLEDA#(n). Software is responsible for controlling these as specified in the USB Specification Revision 2.0. Bit Value Meaning 00b Port indicators are off 01b Amber 10b Green 11b Undefined The Intel EHC only supports bit value of 00b. Other values will result in unspecified behavior. Power Well: Resume
13	1b RW	Port Owner (PO_P0_0): This bit unconditionally goes to a 0b when the Configure Flag makes a 0b to 1b transition. This bit unconditionally goes to 1b whenever the Configure Flag bit is zero. System software uses this field to release ownership of the port to a selected host controller (in the event that the attached device is not a high-speed device). Software writes a one to this bit when the attached device is not a high-speed device. A one in this bit means that a companion host controller owns and controls the port. See Section 4 of the EHCI Specification for operational details. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
12	1b RO	Port Power (PP_P0_0): Hard-wired with a value of '1' on the Intel EHC. This indicates that the port does have power. Power Well: Resume
11:10	00b RO	Line Status (LS_P0_0): These bits reflect the current logical levels of the D+ (bit 11) and D- (bit 10) signal lines. These bits are used for detection of low-speed USB devices prior to the port reset and enable sequence. This field is valid only when the port enable bit is zero and the current connect status bit is set to a one. The encoding of the bits are: Bits(11:10) USB State Interpretation 00b SE0 Not Low-speed device, perform EHCI reset 10b J-state Not Low-speed device, perform EHCI reset 01b K-state Low-speed device, release ownership of port 11b Undefined Not Low-speed device, perform EHCI reset Power Well: Resume
9	0b RO	Reserved (RSVD): Reserved.
8	0b RW	Port Reset (PORTRST_P0_0): 1=Port is in Reset. 0=Port is not in Reset. Default = 0. When software writes a one to this bit (from a zero), the bus reset sequence as defined in the USB Specification Revision 2.0 is started. Software writes a zero to this bit to terminate the bus reset sequence. Software must keep this bit at a one long enough to guarantee the reset sequence, as specified in the USB Specification Revision 2.0, completes. Note: when software writes this bit to a one, it must also write a zero to the Port Enable bit. Note that when software writes a zero to this bit there may be a delay before the bit status changes to a zero. The bit status will not read as a zero until after the reset has completed. If the port is in high-speed mode after reset is complete, the host controller will automatically enable this port (e.g. set the Port Enable bit to a one). A host controller must terminate the reset and stabilize the state of the port within 2 milliseconds of software transitioning this bit from a one to a zero. For example: if the port detects that the attached device is high-speed during reset, then the host controller must have the port in the enabled state within 2ms of software writing this bit to a zero. The HCHalted bit in the USB2STS register should be a zero before software attempts to use this bit. The host controller may hold Port Reset asserted to a one when the HCHALTED bit is a one. The Run/Stop bit in the Command Register must be set in order for the Port Reset bit to be cleared. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	Suspend (SUSP_P0_0): 1=Port in suspend state. 0=Port not in suspend state. Port Enabled Bit and Suspend bit of this register define the port states as follows: Bits [Port Enabled, Suspend] Port State 0X Disable 10 Enable 11 Suspend When in suspend state, downstream propagation of data is blocked on this port, except for port reset. The blocking occurs at the end of the current transaction, if a transaction was in progress when this bit was written to a 1. In the suspend state, the port is sensitive to resume detection. Note that the bit status does not change until the port is suspended and that there may be a delay in suspending a port if there is a transaction currently in progress on the USB. A write of zero to this bit is ignored by the host controller. The host controller will unconditionally set this bit to a zero when: Software sets the Force Port Resume bit to a zero (from a one). Software sets the Port Reset bit to a one (from a zero). If host software sets this bit to a one when the port is not enabled (i.e. Port enabled bit is a zero) the results are undefined. Power Well: Resume
6	0b RW	Force Port Resume (FPR_P0_0): 1= Resume detected/driven on port. 0=No resume (K-state) detected/driven on port. This functionality defined for manipulating this bit depends on the value of the Suspend bit. For example, if the port is not suspended (Suspend and Enabled bits are a one) and software transitions this bit to a one, then the effects on the bus are undefined. Software sets this bit to a 1 to drive resume signaling. The Host Controller sets this bit to a 1 if a J-to-K transition is detected while the port is in the Suspend state. When this bit transitions to a one because a J-to-K transition is detected, the Port Change Detect bit in the USBSTS register is also set to a one. If software sets this bit to a one, the host controller must not set the Port Change Detect bit. Note that when the EHCI controller owns the port, the resume sequence follows the defined sequence documented in the USB Specification Revision 2.0. The resume signaling (Full-speed 'K') is driven on the port as long as this bit remains a one. Software must appropriately time the Resume and set this bit to a zero when the appropriate amount of time has elapsed. Writing a zero (from one) causes the port to return to high-speed mode (forcing the bus below the port into a high-speed idle). This bit will remain a one until the port has switched to the high-speed idle. The host controller must complete this transition within 2 milliseconds of software setting this bit to a zero. Power Well: Resume
5	0b RWC	Over-current Change (OCC_P0_0): This bit gets set to a one when there is a change to the Over-current Active bit. Software clears this bit by writing a one to this bit position. The functionality of this bit is not dependent upon the port owner. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
4	0b RO	Over-current Active (OACT_P0_0): 1=This port currently has an over-current condition. 0=This port does not have an over-current condition. This bit will automatically transition from a one to a zero when the over current condition is removed. The functionality of this bit is not dependent upon the port owner. The Intel EHC automatically disables the port when the over-current active bit is '1'. Power Well: Resume
3	0b RWC	Port Enable/Disable Change (PEDC_P0_0): 1=Port enabled/disabled status has changed. 0=No change. For the root hub, this bit gets set to a one only when a port is disabled due to the appropriate conditions existing at the EOF2 point (See Chapter 11 of the USB Specification for the definition of a port error). This bit is not set due to the Disabled-to-Enabled transition, nor due to a disconnect. Software clears this bit by writing a 1 to it. Power Well: Resume
2	0b RO	Reserved (RSVD): Reserved.
1	0b RWC	Connect Status Change (CSC_P0_0): 1=Change in Current Connect Status. 0=No change. Indicates a change has occurred in the port's Current Connect Status. The host controller sets this bit for all changes to the port device connect status, even if system software has not cleared an existing connect status change. For example, the insertion status changes twice before system software has cleared the changed condition, hub hardware will be 'setting' an already-set bit (i.e., the bit will remain set). Software sets this bit to 0 by writing a 1 to it. Power Well: Resume
0	0b RO	Current Connect Status (CCS_P0_0): 1=Device is present on port. 0=No device is present. This value reflects the current state of the port, and may not correspond directly to the event that caused the Connect Status Change bit (Bit 1) to be set. Power Well: Resume

18.9.18 Port Status and Control (PORTSC7)—Offset 7Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 7Ch

MBAR Type: PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00003000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:23	000h RO	Reserved (RSVD): Reserved.
22	0b RW	Wake on Over-current Enable (WKOCE_P0_0): Writing this bit to a one enables the port to be sensitive to over-current conditions as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Over-current Active bit (bit 4 of this register) is set. Power Well: Resume
21	0b RW	Wake on Disconnect Enable (WKDSCNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device disconnects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from connected to disconnected (i.e., bit 0 of this register changes from 1 to 0). Power Well: Resume
20	0b RW	Wake on Connect Enable (WKCENTE_P0_0): Writing this bit to a one enables the port to be sensitive to device connects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from disconnected to connected (i.e., bit 0 of this register changes from 0 to 1). Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
19:16	0h RW	Port Test Control (PTC_P0_0): When this field is zero, the port is NOT operating in a test mode. A non-zero value indicates that it is operating in test mode and the specific test mode is indicated by the specific value. The encoding of the test mode bits are (0110b - 1111b are reserved): Bits Test Mode 0000b Test mode not enabled 0001b Test J_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0010b Test K_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0011b Test SE0_NAK 0100b Test Packet 0101b Test FORCE_ENABLE Refer to USB Specification Revision 2.0, Chapter 7 and the EHCI specification, Chapter 4 for details on each test mode. The EHC does not support the option to run the port tests while the Run/Stop bit is a one. Power Well: Resume
15:14	00b RW	Port Indicator Control (PIC_P0_0): Writing to these bits directly controls the corresponding LED output pins. Bit 15 is inverted to generate USBLEDG#(n) where n is the port number. Bit 14 is inverted to generate USBLEDA#(n). Software is responsible for controlling these as specified in the USB Specification Revision 2.0. Bit Value Meaning 00b Port indicators are off 01b Amber 10b Green 11b Undefined The Intel EHC only supports bit value of 00b. Other values will result in unspecified behavior. Power Well: Resume
13	1b RW	Port Owner (PO_P0_0): This bit unconditionally goes to a 0b when the Configure Flag makes a 0b to 1b transition. This bit unconditionally goes to 1b whenever the Configure Flag bit is zero. System software uses this field to release ownership of the port to a selected host controller (in the event that the attached device is not a high-speed device). Software writes a one to this bit when the attached device is not a high-speed device. A one in this bit means that a companion host controller owns and controls the port. See Section 4 of the EHCI Specification for operational details. Power Well: Resume
12	1b RO	Port Power (PP_P0_0): Hard-wired with a value of '1' on the Intel EHC. This indicates that the port does have power. Power Well: Resume
11:10	00b RO	Line Status (LS_P0_0): These bits reflect the current logical levels of the D+ (bit 11) and D- (bit 10) signal lines. These bits are used for detection of low-speed USB devices prior to the port reset and enable sequence. This field is valid only when the port enable bit is zero and the current connect status bit is set to a one. The encoding of the bits are: Bits(11:10) USB State Interpretation 00b SE0 Not Low-speed device, perform EHCI reset 10b J-state Not Low-speed device, perform EHCI reset 01b K-state Low-speed device, release ownership of port 11b Undefined Not Low-speed device, perform EHCI reset Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
9	0b RO	Reserved (RSVD): Reserved.
8	0b RW	Port Reset (PORTRST_P0_0): 1=Port is in Reset. 0=Port is not in Reset. Default = 0. When software writes a one to this bit (from a zero), the bus reset sequence as defined in the USB Specification Revision 2.0 is started. Software writes a zero to this bit to terminate the bus reset sequence. Software must keep this bit at a one long enough to guarantee the reset sequence, as specified in the USB Specification Revision 2.0, completes. Note: when software writes this bit to a one, it must also write a zero to the Port Enable bit. Note that when software writes a zero to this bit there may be a delay before the bit status changes to a zero. The bit status will not read as a zero until after the reset has completed. If the port is in high-speed mode after reset is complete, the host controller will automatically enable this port (e.g. set the Port Enable bit to a one). A host controller must terminate the reset and stabilize the state of the port within 2 milliseconds of software transitioning this bit from a one to a zero. For example: if the port detects that the attached device is high-speed during reset, then the host controller must have the port in the enabled state within 2ms of software writing this bit to a zero. The HCHalted bit in the USB2STS register should be a zero before software attempts to use this bit. The host controller may hold Port Reset asserted to a one when the HCHALTED bit is a one. The Run/Stop bit in the Command Register must be set in order for the Port Reset bit to be cleared. Power Well: Resume
7	0b RW	Suspend (SUSP_P0_0): 1=Port in suspend state. 0=Port not in suspend state. Port Enabled Bit and Suspend bit of this register define the port states as follows: Bits [Port Enabled, Suspend] Port State 0X Disable 10 Enable 11 Suspend When in suspend state, downstream propagation of data is blocked on this port, except for port reset. The blocking occurs at the end of the current transaction, if a transaction was in progress when this bit was written to a 1. In the suspend state, the port is sensitive to resume detection. Note that the bit status does not change until the port is suspended and that there may be a delay in suspending a port if there is a transaction currently in progress on the USB. A write of zero to this bit is ignored by the host controller. The host controller will unconditionally set this bit to a zero when: Software sets the Force Port Resume bit to a zero (from a one). Software sets the Port Reset bit to a one (from a zero). If host software sets this bit to a one when the port is not enabled (i.e. Port enabled bit is a zero) the results are undefined. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
6	0b RW	Force Port Resume (FPR_P0_0): 1= Resume detected/driven on port. 0=No resume (K-state) detected/driven on port. This functionality defined for manipulating this bit depends on the value of the Suspend bit. For example, if the port is not suspended (Suspend and Enabled bits are a one) and software transitions this bit to a one, then the effects on the bus are undefined. Software sets this bit to a 1 to drive resume signaling. The Host Controller sets this bit to a 1 if a J-to-K transition is detected while the port is in the Suspend state. When this bit transitions to a one because a J-to-K transition is detected, the Port Change Detect bit in the USBSTS register is also set to a one. If software sets this bit to a one, the host controller must not set the Port Change Detect bit. Note that when the EHCI controller owns the port, the resume sequence follows the defined sequence documented in the USB Specification Revision 2.0. The resume signaling (Full-speed 'K') is driven on the port as long as this bit remains a one. Software must appropriately time the Resume and set this bit to a zero when the appropriate amount of time has elapsed. Writing a zero (from one) causes the port to return to high-speed mode (forcing the bus below the port into a high-speed idle). This bit will remain a one until the port has switched to the high-speed idle. The host controller must complete this transition within 2 milliseconds of software setting this bit to a zero. Power Well: Resume
5	0b RWC	Over-current Change (OCC_P0_0): This bit gets set to a one when there is a change to the Over-current Active bit. Software clears this bit by writing a one to this bit position. The functionality of this bit is not dependent upon the port owner. Power Well: Resume
4	0b RO	Over-current Active (OACT_P0_0): 1=This port currently has an over-current condition. 0=This port does not have an over-current condition. This bit will automatically transition from a one to a zero when the over current condition is removed. The functionality of this bit is not dependent upon the port owner. The Intel EHC automatically disables the port when the over-current active bit is '1'. Power Well: Resume
3	0b RWC	Port Enable/Disable Change (PEDC_P0_0): 1=Port enabled/disabled status has changed. 0=No change. For the root hub, this bit gets set to a one only when a port is disabled due to the appropriate conditions existing at the EOF2 point (See Chapter 11 of the USB Specification for the definition of a port error). This bit is not set due to the Disabled-to-Enabled transition, nor due to a disconnect. Software clears this bit by writing a 1 to it. Power Well: Resume
2	0b RO	Reserved (RSVD): Reserved.

18.9.19 Port Status and Control (PORTSC8)—Offset 80h

Bit Range	Default & Access	Field Name (ID): Description
1	0b RWC	Connect Status Change (CSC_P0_0): 1=Change in Current Connect Status. 0=No change. Indicates a change has occurred in the port's Current Connect Status. The host controller sets this bit for all changes to the port device connect status, even if system software has not cleared an existing connect status change. For example, the insertion status changes twice before system software has cleared the changed condition, hub hardware will be 'setting' an already-set bit (i.e., the bit will remain set). Software sets this bit to 0 by writing a 1 to it. Power Well: Resume
0	0b RO	Current Connect Status (CCS_P0_0): 1=Device is present on port. 0=No device is present. This value reflects the current state of the port, and may not correspond directly to the event that caused the Connect Status Change bit (Bit 1) to be set. Power Well: Resume

18.9.19 Port Status and Control (PORTSC8)—Offset 80h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + 80h**MBAR Type:** PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00003000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:23	000h RO	Reserved (RSVD): Reserved.
22	0b RW	Wake on Over-current Enable (WKOCE_P0_0): Writing this bit to a one enables the port to be sensitive to over-current conditions as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Over-current Active bit (bit 4 of this register) is set. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
21	0b RW	Wake on Disconnect Enable (WKDSCNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device disconnects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from connected to disconnected (i.e., bit 0 of this register changes from 1 to 0). Power Well: Resume
20	0b RW	Wake on Connect Enable (WKCNNTE_P0_0): Writing this bit to a one enables the port to be sensitive to device connects as wake-up events. When enabled to do so, the EHC sets the PME Status bit in the Power Management Control/Status Register (offset 54, bit 15) when the Current Connect Status changes from disconnected to connected (i.e., bit 0 of this register changes from 0 to 1). Power Well: Resume
19:16	0h RW	Port Test Control (PTC_P0_0): When this field is zero, the port is NOT operating in a test mode. A non-zero value indicates that it is operating in test mode and the specific test mode is indicated by the specific value. The encoding of the test mode bits are (0110b - 1111b are reserved): Bits Test Mode 0000b Test mode not enabled 0001b Test J_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0010b Test K_STATE- During this test mode the hardware forces pre-emphasis disabled to the AFE if bit 29 of the USB2 Safe Mode Register is set (config offset FCh.bit 29) 0011b Test SE0_NAK 0100b Test Packet 0101b Test FORCE_ENABLE Refer to USB Specification Revision 2.0, Chapter 7 and the EHCI specification, Chapter 4 for details on each test mode. The EHC does not support the option to run the port tests while the Run/Stop bit is a one. Power Well: Resume
15:14	00b RW	Port Indicator Control (PIC_P0_0): Writing to these bits directly controls the corresponding LED output pins. Bit 15 is inverted to generate USBLEDG#(n) where n is the port number. Bit 14 is inverted to generate USBLEDA#(n). Software is responsible for controlling these as specified in the USB Specification Revision 2.0. Bit Value Meaning 00b Port indicators are off 01b Amber 10b Green 11b Undefined The Intel EHC only supports bit value of 00b. Other values will result in unspecified behavior. Power Well: Resume
13	1b RW	Port Owner (PO_P0_0): This bit unconditionally goes to a 0b when the Configure Flag makes a 0b to 1b transition. This bit unconditionally goes to 1b whenever the Configure Flag bit is zero. System software uses this field to release ownership of the port to a selected host controller (in the event that the attached device is not a high-speed device). Software writes a one to this bit when the attached device is not a high-speed device. A one in this bit means that a companion host controller owns and controls the port. See Section 4 of the EHCI Specification for operational details. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
12	1b RO	Port Power (PP_P0_0): Hard-wired with a value of '1' on the Intel EHC. This indicates that the port does have power. Power Well: Resume
11:10	00b RO	Line Status (LS_P0_0): These bits reflect the current logical levels of the D+ (bit 11) and D- (bit 10) signal lines. These bits are used for detection of low-speed USB devices prior to the port reset and enable sequence. This field is valid only when the port enable bit is zero and the current connect status bit is set to a one. The encoding of the bits are: Bits(11:10) USB State Interpretation 00b SE0 Not Low-speed device, perform EHCI reset 10b J-state Not Low-speed device, perform EHCI reset 01b K-state Low-speed device, release ownership of port 11b Undefined Not Low-speed device, perform EHCI reset Power Well: Resume
9	0b RO	Reserved (RSVD): Reserved.
8	0b RW	Port Reset (PORTRST_P0_0): 1=Port is in Reset. 0=Port is not in Reset. Default = 0. When software writes a one to this bit (from a zero), the bus reset sequence as defined in the USB Specification Revision 2.0 is started. Software writes a zero to this bit to terminate the bus reset sequence. Software must keep this bit at a one long enough to guarantee the reset sequence, as specified in the USB Specification Revision 2.0, completes. Note: when software writes this bit to a one, it must also write a zero to the Port Enable bit. Note that when software writes a zero to this bit there may be a delay before the bit status changes to a zero. The bit status will not read as a zero until after the reset has completed. If the port is in high-speed mode after reset is complete, the host controller will automatically enable this port (e.g. set the Port Enable bit to a one). A host controller must terminate the reset and stabilize the state of the port within 2 milliseconds of software transitioning this bit from a one to a zero. For example: if the port detects that the attached device is high-speed during reset, then the host controller must have the port in the enabled state within 2ms of software writing this bit to a zero. The HCHalted bit in the USB2STS register should be a zero before software attempts to use this bit. The host controller may hold Port Reset asserted to a one when the HCHALTED bit is a one. The Run/Stop bit in the Command Register must be set in order for the Port Reset bit to be cleared. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
7	0b RW	Suspend (SUSP_P0_0): 1=Port in suspend state. 0=Port not in suspend state. Port Enabled Bit and Suspend bit of this register define the port states as follows: Bits [Port Enabled, Suspend] Port State 0X Disable 10 Enable 11 Suspend When in suspend state, downstream propagation of data is blocked on this port, except for port reset. The blocking occurs at the end of the current transaction, if a transaction was in progress when this bit was written to a 1. In the suspend state, the port is sensitive to resume detection. Note that the bit status does not change until the port is suspended and that there may be a delay in suspending a port if there is a transaction currently in progress on the USB. A write of zero to this bit is ignored by the host controller. The host controller will unconditionally set this bit to a zero when: Software sets the Force Port Resume bit to a zero (from a one). Software sets the Port Reset bit to a one (from a zero). If host software sets this bit to a one when the port is not enabled (i.e. Port enabled bit is a zero) the results are undefined. Power Well: Resume
6	0b RW	Force Port Resume (FPR_P0_0): 1= Resume detected/driven on port. 0=No resume (K-state) detected/driven on port. This functionality defined for manipulating this bit depends on the value of the Suspend bit. For example, if the port is not suspended (Suspend and Enabled bits are a one) and software transitions this bit to a one, then the effects on the bus are undefined. Software sets this bit to a 1 to drive resume signaling. The Host Controller sets this bit to a 1 if a J-to-K transition is detected while the port is in the Suspend state. When this bit transitions to a one because a J-to-K transition is detected, the Port Change Detect bit in the USBSTS register is also set to a one. If software sets this bit to a one, the host controller must not set the Port Change Detect bit. Note that when the EHCI controller owns the port, the resume sequence follows the defined sequence documented in the USB Specification Revision 2.0. The resume signaling (Full-speed 'K') is driven on the port as long as this bit remains a one. Software must appropriately time the Resume and set this bit to a zero when the appropriate amount of time has elapsed. Writing a zero (from one) causes the port to return to high-speed mode (forcing the bus below the port into a high-speed idle). This bit will remain a one until the port has switched to the high-speed idle. The host controller must complete this transition within 2 milliseconds of software setting this bit to a zero. Power Well: Resume
5	0b RWC	Over-current Change (OCC_P0_0): This bit gets set to a one when there is a change to the Over-current Active bit. Software clears this bit by writing a one to this bit position. The functionality of this bit is not dependent upon the port owner. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
4	0b RO	Over-current Active (OACT_P0_0): 1=This port currently has an over-current condition. 0=This port does not have an over-current condition. This bit will automatically transition from a one to a zero when the over current condition is removed. The functionality of this bit is not dependent upon the port owner. The Intel EHC automatically disables the port when the over-current active bit is '1'. Power Well: Resume
3	0b RWC	Port Enable/Disable Change (PEDC_P0_0): 1=Port enabled/disabled status has changed. 0=No change. For the root hub, this bit gets set to a one only when a port is disabled due to the appropriate conditions existing at the EOF2 point (See Chapter 11 of the USB Specification for the definition of a port error). This bit is not set due to the Disabled-to-Enabled transition, nor due to a disconnect. Software clears this bit by writing a 1 to it. Power Well: Resume
2	0b RO	Reserved (RSVD): Reserved.
1	0b RWC	Connect Status Change (CSC_P0_0): 1=Change in Current Connect Status. 0=No change. Indicates a change has occurred in the port's Current Connect Status. The host controller sets this bit for all changes to the port device connect status, even if system software has not cleared an existing connect status change. For example, the insertion status changes twice before system software has cleared the changed condition, hub hardware will be 'setting' an already-set bit (i.e., the bit will remain set). Software sets this bit to 0 by writing a 1 to it. Power Well: Resume
0	0b RO	Current Connect Status (CCS_P0_0): 1=Device is present on port. 0=No device is present. This value reflects the current state of the port, and may not correspond directly to the event that caused the Connect Status Change bit (Bit 1) to be set. Power Well: Resume



Bit Range	Default & Access	Field Name (ID): Description
16	0b RWC	DONE_STS (DONESTS_0): Read/Write-Clear. This bit is set by hardware to indicate that the request is complete. Writing a 1 to this bit will clear it if it is set. Writing a 0 to this bit has no effect. Reset default = 0 Power Well: Core
15:12	0000b RO	LINK_ID_STS (LINKIDSTS_0): Read-Only. This field identifies the link interface. It is hardwired to 0h to indicate that it is a USB Debug Port. Power Well: Core
11	0b RO	Reserved (RSVD): Reserved.
10	0b RO	IN_USE_CNT (INUSECNT_0): Set by software to indicate that the port is in use. Cleared by software to indicate that the port is free and may be used by other software. This bit is cleared after reset. (This bit has no affect on hardware.) Power Well: Core
9:7	000b RO	EXCEPTION_STS (EXCP_STS_0): Read-Only. This field indicates the exception when the ERROR_GOOD#_STS bit is set. This field should be ignored if the ERROR_GOOD#_STS bit is 0. 000 No Error. Note: this should not be seen, since this field should only be checked if there is an error. 001 Transaction error: indicates the USB2 transaction had an error (CRC, bad PID, timeout, etc.) 010 HW error. Request was attempted (or in progress) when port was suspended or reset. All Others are reserved Reset default = 000b Power Well: Core
6	0b RO	ERROR_GOOD_STS (ERRGOODSTS_0): Read-Only. The hardware clears this bit to 0 upon the proper completion of a read or write. The hardware sets this bit to indicate that an error has occurred. Details on the nature of the error are provided in the Exception field. Reset default = 0. Power Well: Core
5	0b RW	GO_CNT (GOCNT_0): Software sets this bit to cause the hardware to perform a read or write request. Writing a 0 to this bit has no effect. Writing a 1 to this bit when it is already set may result in undefined behavior. When set, the hardware clears this bit when the hardware sets the DONE_STS bit. Reset default = 0. Power Well: Core
4	0b RW	WRITE_READ_CNT (WRRDCNT_0): Software sets this bit to indicate that the current request is a write. Software clears this bit to indicate that the current request is a read. Reset default = 0. Power Well: Core



Bit Range	Default & Access	Field Name (ID): Description
3:0	0000b RW	DATA_LEN_CNT (DATALENCNT_0): This field is used to indicate the size of the data to be transferred. Reset default = 0h. For write operations, this field is set by software to indicate to the hardware how many bytes of data in Data Buffer are to be transferred to the console. A value of 0h indicates that a zero-length packet should be sent. A value of 1-8 indicates 1-8 bytes are to be transferred. Values 9-Fh are illegal and how hardware behaves if used is undefined. For read operations, this field is set by hardware to indicate to software how many bytes in Data Buffer are valid in response to a read operation. A value of 0h indicates that a zero length packet was returned and the state of Data Buffer is not defined. A value of 1-8 indicates 1-8 bytes were received. Hardware is not allowed to return values 9-Fh. The transferring of data always starts with byte 0 in the data area and moves toward byte 7 until the transfer size is reached. Power Well: Core

18.9.21 USB PIDs Register (DP USB PIDs)—Offset A4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + A4h

MBAR Type: PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
RSVD				RECEIVED_PID_STS_0				SEND_PID_CNT_0				TOKEN_PID_CNT_0			

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
23:16	00h RO	RECEIVED_PID_STS (RECEIVED_PID_STS_0): The hardware updates this field with the received PID for transactions in either direction. When the controller is writing data, this field is updated with the handshake PID that is received from the device. When the host controller is reading data, this field is updated with the data packet PID (if the device sent data), or the handshake PID (if the device NAKs the request). This field is valid when the hardware clears the GO_DONE#_CNT bit. Reset Default = 0. Power Well: Core
15:8	00h RW	SEND_PID_CNT (SEND_PID_CNT_0): The hardware sends this PID to begin the data packet when sending data to USB (ie. WRITE_READ#_CNT is asserted). Software will typically set this field to either DATA0 or DATA1 PID values. Reset Default = 0 Power Well: Core
7:0	00h RW	TOKEN_PID_CNT (TOKEN_PID_CNT_0): The hardware sends this PID as the Token PID for each USB transaction. Software will typically set this field to either IN, OUT or SETUP PID values. Reset Default = 0. Power Well: Core



18.9.23 Debug Port Config Register (DP_CFG)—Offset B0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [MBAR] + B0h

MBAR Type: PCI Configuration Register (Size: 32 bits)

MBAR Reference: [B:0, D:29, F:0] + 10h

Default: 00007F01h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RSVD				USB_ADDR_CNF_0				USB_ENDPT_CNF_0

Bit Range	Default & Access	Field Name (ID): Description
31:15	000000000 00000000b RO	Reserved (RSVD): Reserved.
14:8	7fh RW	USB_ADDRESS_CNF (USB_ADDR_CNF_0): 7-bit field that identifies the USB device address used by the controller for all Token PID generation. This is a R/W field that is set to 7Fh after reset Power Well: Core
7:4	0000b RO	Reserved (RSVD): Reserved.
3:0	01h RW	USB_ENDPOINT_CNF (USB_ENDPT_CNF_0): This 4-bit field identifies the endpoint used by the controller for all Token PID generation. This is a R/W field that is set to 01h after reset. Power Well: Core

18.9.24 USB Test Per Port Register 1 (USB2_TEST_PERPORT_REG1_LANE0/1/2/3) - Offset 4113h/4213h/4313h/4413h

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x43] + 4113h/4213h/4313h/4413h

Op Codes: 6h - Read, 7h - Write

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:29	0x0 RO	Reserved.
8	0x0 RW	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.
7:4	0x0 RW	Reserved.
3	0x0 RW	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.
2:0	RW	Reserved.

18.9.25 Per Port RCOMP High Speed Pull down Register (PER_PORT_RCOMP_HS_PULLDOWN_REGISTER_LANE0/1/2/3) - Offset 4123h/4223h/4323h/4423h

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x43] + 4123h/4223h/4323h/4423h

Op Codes: 6h - Read, 7h - Write

Default: 00000011h

Bit Range	Default & Access	Field Name (ID): Description
31:30	0x0 RO	Reserved.
29:24	0x0 RW	Reserved.
23:15	0x0 RO	Reserved.
14:8	0x0 RW	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.
7:5	0x0 RW	Reserved.
23:15	0x1 RW	Reserved.
14:8	0x0 RW	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.
2:0	0x1 RW	Restricted

18.9.26 USB Per Port (USB2_PER_PORT_2_LANE0/1/2/3) - Offset 4126h/4226h/4326h/4426h

Access Method



Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x43] + 4126h/4226h/4326h/4426h

Op Codes: 6h - Read, 7h - Write

Default: 00001249h

Bit Range	Default & Access	Field Name (ID): Description
31:13	0x0 RO	Reserved.
12:11	0x2 RW	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.
10:9	0x1 RO	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.
8	0x0 RW	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.

7:5	0x0 RW	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.
4:2	0x0 RW	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.
1:0	RW	This register field is used in the workaround in the erratum VL184. It is Reserved for all other purposes.



Offset	Register Name (Register Symbol)	Default Value
4100–4103h	“USB2 PER PORT (USB2_PER_PORT_LANE0)—Offset 4100h” on page 2436	0004F201h
4200–4203h	“USB2 PER PORT (USB2_PER_PORT_LANE1)—Offset 4200h” on page 2438	0004F201h
4300–4303h	“USB2 PER PORT (USB2_PER_PORT_LANE2)—Offset 4300h” on page 2440	0004F201h
4400–4403h	“USB2 PER PORT (USB2_PER_PORT_LANE3)—Offset 4400h” on page 2442	0004F201h
4500–4503h	“USB2 PER PORT (USB2_PER_PORT_LANE4)—Offset 4500h” on page 2443	0004F201h
4600–4603h	“USB2 PER PORT (USB2_PER_PORT_LANE5)—Offset 4600h” on page 2445	0004F201h
4700–4703h	“USB2 PER PORT (USB2_PER_PORT_LANE6)—Offset 4700h” on page 2447	0004F201h
4800–4803h	“USB2 PER PORT (USB2_PER_PORT_LANE7)—Offset 4800h” on page 2449	0004F201h

Access Method

Offset: [Port: 0x43] + 4100h

h - Read, h - Write

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:26	000000b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22	0b RO	Reserved (RSVD): Reserved.
21	0b RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19:17	010b RO	Reserved (RSVD): Reserved.
16	0b RO	Reserved (RSVD): Reserved.
15	1b RW	PerPort HS Transmitter Pre-emphasis (PERPORTTXPREEMPEN_0): Config bit (per port) Enables HS transmitter pre-emphasis for the respective ports 1 enabled pre-emphasis or when PORTRESERVED[0]=1 0 disabled pre-emphasis This has to be 1 if either to enable pre-emphasis or de-emphasis, 0 to completely turn OFF. Power Well: SUS
14	1b RW	PerPort Half Bit Pre-emphasis (PERPORTTXPEHALF_0): Config bit (per port) to select between half-bit or full-bit implementation 1 - select half-bit pre-emphasis 0 - select full-bit pre-emphasis or when PORTRESERVED[0]=1 in de-emphasis mode, this has to be 0 Power Well: SUS
13:11	110b RW	PerPort HS Pre-emphasis Bias (PERPORTPETXISSET_0): Config bit (per port) HS Pre-emphasis Bias current offset bit (2:0) Value Voh 000 0mV 001 11.250mV 010 16.875mV 011 28.125mV 100 28.125mV 101 39.375mV 110 45.000mV (default) 111 56.250mV Power Well: SUS
10:8	010b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.
6:4	000b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [Port: 0x43] + 4200h

h - Read, h - Write

31	28				24				20				16				12				8				4				0																										
0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1	1	1	0	0	1	0	0	0	0	0	0	0	1																								
RSVD				RSVD				RSVD				RSVD				RSVD				PERPORTTXPREEMPEN_0				PERPORTTXPEHALF_0				PERPORTPTXSET_0				RSVD				RSVD				PORTRESERVED				RSVD				RSVD				RSVD			

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
22	0b RO	Reserved (RSVD): Reserved.
21	0b RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19:17	010b RO	Reserved (RSVD): Reserved.
16	0b RO	Reserved (RSVD): Reserved.
15	1b RW	PerPort HS Transmitter Pre-emphasis (PERPORTTXPREEMPEN_0): Config bit (per port) Enables HS transmitter pre-emphasis for the respective ports 1 enabled pre-emphasis or when PORTRESERVED[0]=1 0 disabled pre-emphasis This has to be 1 if either to enable pre-emphasis or de-emphasis, 0 to completely turn OFF. Power Well: SUS
14	1b RW	PerPort Half Bit Pre-emphasis (PERPORTTXPEHALF_0): Config bit (per port) to select between half-bit or full-bit implementation 1 - select half-bit pre-emphasis 0 - select full-bit pre-emphasis or when PORTRESERVED[0]=1 in de-emphasis mode, this has to be 0 Power Well: SUS
13:11	110b RW	PerPort HS Pre-emphasis Bias (PERPORTPETXISSET_0): Config bit (per port) HS Pre-emphasis Bias current offset bit (2:0) Value Voh 000 0mV 001 11.250mV 010 16.875mV 011 28.125mV 100 28.125mV 101 39.375mV 110 45.000mV (default) 111 56.250mV Power Well: SUS
10:8	010b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.
6:4	000b RO	Reserved (RSVD): Reserved.
3	0b RW	DE-EMPHASIS ON/OFF FOR DEBUG (PORTRESERVED): Config bit to select De-emphasis mode ON/OFF for TX-HS debug purpose. 0 De-emphasis OFF (default) 1 De-emphasis ON In order to enable De-emphasis ON, ensure PERPORTTXPREEMPEN(0h15)=1 and PERPORTTXPEHALF(0h14)=0 Power Well: SUS
2	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
1	0b RO	Reserved (RSVD): Reserved.
0	1b RO	Reserved (RSVD): Reserved.

18.10.3 USB2 PER PORT (USB2_PER_PORT_LANE2)—Offset 4300h

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x43] + 4300h

Op Codes:

Default: 0004F201h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:26	000000b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22	0b RO	Reserved (RSVD): Reserved.
21	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19:17	010b RO	Reserved (RSVD): Reserved.
16	0b RO	Reserved (RSVD): Reserved.
15	1b RW	PerPort HS Transmitter Pre-emphasis (PERPORTTXPREEMPEN_0): Config bit (per port) Enables HS transmitter pre-emphasis for the respective ports 1 enabled pre-emphasis or when PORTRESERVED[0]=1 0 disabled pre-emphasis This has to be 1 if either to enable pre-emphasis or de-emphasis, 0 to completely turn OFF. Power Well: SUS
14	1b RW	PerPort Half Bit Pre-emphasis (PERPORTTXPEHALF_0): Config bit (per port) to select between half-bit or full-bit implementation 1 - select half-bit pre-emphasis 0 - select full-bit pre-emphasis or when PORTRESERVED[0]=1 in de-emphasis mode, this has to be 0 Power Well: SUS
13:11	110b RW	PerPort HS Pre-emphasis Bias (PERPORTPETXISSET_0): Config bit (per port) HS Pre-emphasis Bias current offset bit (2:0) Value Voh 000 0mV 001 11.250mV 010 16.875mV 011 28.125mV 100 28.125mV 101 39.375mV 110 45.000mV (default) 111 56.250mV Power Well: SUS
10:8	010b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.
6:4	000b RO	Reserved (RSVD): Reserved.
3	0b RW	DE-EMPHASIS ON/OFF FOR DEBUG (PORTRESERVED): Config bit to select De-emphasis mode ON/OFF for TX-HS debug purpose. 0 De-emphasis OFF (default) 1 De-emphasis ON In order to enable De-emphasis ON, ensure RERPORTTXPREEMPEN(0h15)=1 and PERPORTTXPEHALF(0h14)=0 Power Well: SUS
2	0b RO	Reserved (RSVD): Reserved.
1	0b RO	Reserved (RSVD): Reserved.
0	1b RO	Reserved (RSVD): Reserved.



Type: Message Bus Register
(Size: 32 bits)

Op Codes:

h - Read, h - Write

31	28				24				20				16				12				8				4				0														
0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1	1	1	0	0	1	0	0	0	0	0	0	0	1												
RSVD				RSVD				RSVD				RSVD				RSVD				RSVD				RSVD				PORTRESERVED				RSVD				RSVD				RSVD			

Bit Range	Default & Access	Field Name (ID): Description
31:26	000000b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22	0b RO	Reserved (RSVD): Reserved.
21	0b RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19:17	010b RO	Reserved (RSVD): Reserved.
16	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
15	1b RW	PerPort HS Transmitter Pre-emphasis (PERPORTTXPREEMPEN_0): Config bit (per port) Enables HS transmitter pre-emphasis for the respective ports 1 enabled pre-emphasis or when PORTRESERVED[0]=1 0 disabled pre-emphasis This has to be 1 if either to enable pre-emphasis or de-emphasis, 0 to completely turn OFF. Power Well: SUS
14	1b RW	PerPort Half Bit Pre-emphasis (PERPORTTXPEHALF_0): Config bit (per port) to select between half-bit or full-bit implementation 1 - select half-bit pre-emphasis 0 - select full-bit pre-emphasis or when PORTRESERVED[0]=1 in de-emphasis mode, this has to be 0 Power Well: SUS
13:11	110b RW	PerPort HS Pre-emphasis Bias (PERPORTPETXISSET_0): Config bit (per port) HS Pre-emphasis Bias current offset bit (2:0) Value Voh 000 0mV 001 11.250mV 010 16.875mV 011 28.125mV 100 28.125mV 101 39.375mV 110 45.000mV (default) 111 56.250mV Power Well: SUS
10:8	010b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.
6:4	000b RO	Reserved (RSVD): Reserved.
3	0b RW	DE-EMPHASIS ON/OFF FOR DEBUG (PORTRESERVED): Config bit to select De-emphasis mode ON/OFF for TX-HS debug purpose. 0 De-emphasis OFF (default) 1 De-emphasis ON In order to enable De-emphasis ON, ensure RERPORTTXPREEMPEN(0h15)=1 and PERPORTTXPEHALF(0h14)=0 Power Well: SUS
2	0b RO	Reserved (RSVD): Reserved.
1	0b RO	Reserved (RSVD): Reserved.
0	1b RO	Reserved (RSVD): Reserved.

18.10.5 USB2 PER PORT (USB2_PER_PORT_LANE4)—Offset 4500h

Access Method

Type: Message Bus Register
(Size: 32 bits)

Offset: [Port: 0x43] + 4500h

Op Codes:

h - Read, h - Write

Default: 0004F201h



Bit Range	Default & Access	Field Name (ID): Description
31:26	000000b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22	0b RO	Reserved (RSVD): Reserved.
21	0b RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19:17	010b RO	Reserved (RSVD): Reserved.
16	0b RO	Reserved (RSVD): Reserved.
15	1b RW	PerPort HS Transmitter Pre-emphasis (PERPORTTXPREEMPEN_0): Config bit (per port) Enables HS transmitter pre-emphasis for the respective ports 1 enabled pre-emphasis or when PORTRESERVED[0]=1 0 disabled pre-emphasis This has to be 1 if either to enable pre-emphasis or de-emphasis, 0 to completely turn OFF. Power Well: SUS
14	1b RW	PerPort Half Bit Pre-emphasis (PERPORTTXPEHALF_0): Config bit (per port) to select between half-bit or full-bit implementation 1 - select half-bit pre-emphasis 0 - select full-bit pre-emphasis or when PORTRESERVED[0]=1 in de-emphasis mode, this has to be 0 Power Well: SUS
13:11	110b RW	PerPort HS Pre-emphasis Bias (PERPORTPETXISSET_0): Config bit (per port) HS Pre-emphasis Bias current offset bit (2:0) Value Voh 000 0mV 001 11.250mV 010 16.875mV 011 28.125mV 100 28.125mV 101 39.375mV 110 45.000mV (default) 111 56.250mV Power Well: SUS
10:8	010b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
23	0b RO	Reserved (RSVD): Reserved.
22	0b RO	Reserved (RSVD): Reserved.
21	0b RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19:17	010b RO	Reserved (RSVD): Reserved.
16	0b RO	Reserved (RSVD): Reserved.
15	1b RW	PerPort HS Transmitter Pre-emphasis (PERPORTTXPREEMPEN_0): Config bit (per port) Enables HS transmitter pre-emphasis for the respective ports 1 enabled pre-emphasis or when PORTRESERVED[0]=1 0 disabled pre-emphasis This has to be 1 if either to enable pre-emphasis or de-emphasis, 0 to completely turn OFF. Power Well: SUS
14	1b RW	PerPort Half Bit Pre-emphasis (PERPORTTXPEHALF_0): Config bit (per port) to select between half-bit or full-bit implementation 1 - select half-bit pre-emphasis 0 - select full-bit pre-emphasis or when PORTRESERVED[0]=1 in de-emphasis mode, this has to be 0 Power Well: SUS
13:11	110b RW	PerPort HS Pre-emphasis Bias (PERPORTPETXISSET_0): Config bit (per port) HS Pre-emphasis Bias current offset bit (2:0) Value Voh 000 0mV 001 11.250mV 010 16.875mV 011 28.125mV 100 28.125mV 101 39.375mV 110 45.000mV (default) 111 56.250mV Power Well: SUS
10:8	010b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.
6:4	000b RO	Reserved (RSVD): Reserved.
3	0b RW	DE-EMPHASIS ON/OFF FOR DEBUG (PORTRESERVED): Config bit to select De-emphasis mode ON/OFF for TX-HS debug purpose. 0 De-emphasis OFF (default) 1 De-emphasis ON In order to enable De-emphasis ON, ensure RERPORTTXPREEMPEN(0h15)=1 and PERPORTTXPEHALF(0h14)=0 Power Well: SUS

18.10.8 USB2 PER PORT (USB2 PER PORT LANE7)—Offset 4800h



Bit Range	Default & Access	Field Name (ID): Description
21	0b RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19:17	010b RO	Reserved (RSVD): Reserved.
16	0b RO	Reserved (RSVD): Reserved.
15	1b RW	PerPort HS Transmitter Pre-emphasis (PERPORTTXPREEMPEN_0): Config bit (per port) Enables HS transmitter pre-emphasis for the respective ports 1 enabled pre-emphasis or when PORTRESERVED[0]=1 0 disabled pre-emphasis This has to be 1 if either to enable pre-emphasis or de-emphasis, 0 to completely turn OFF. Power Well: SUS
14	1b RW	PerPort Half Bit Pre-emphasis (PERPORTTXPEHALF_0): Config bit (per port) to select between half-bit or full-bit implementation 1 - select half-bit pre-emphasis 0 - select full-bit pre-emphasis or when PORTRESERVED[0]=1 in de-emphasis mode, this has to be 0 Power Well: SUS
13:11	110b RW	PerPort HS Pre-emphasis Bias (PERPORTPETXISSET_0): Config bit (per port) HS Pre-emphasis Bias current offset bit (2:0) Value Voh 000 0mV 001 11.250mV 010 16.875mV 011 28.125mV 100 28.125mV 101 39.375mV 110 45.000mV (default) 111 56.250mV Power Well: SUS
10:8	010b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.
6:4	000b RO	Reserved (RSVD): Reserved.
3	0b RW	DE-EMPHASIS ON/OFF FOR DEBUG (PORTRESERVED): Config bit to select De-emphasis mode ON/OFF for TX-HS debug purpose. 0 De-emphasis OFF (default) 1 De-emphasis ON In order to enable De-emphasis ON, ensure RERPORTTXPREEMPEN(0h15)=1 and PERPORTTXPEHALF(0h14)=0 Power Well: SUS
2	0b RO	Reserved (RSVD): Reserved.
1	0b RO	Reserved (RSVD): Reserved.




Bit Range	Default & Access	Field Name (ID): Description
0	1b RO	Reserved (RSVD): Reserved.

19 USB Device Controller Interfaces (3.0, ULPI)

The SoC implements a single USB 3.0 device controller, where the platform acts as a peripheral to another device or another PC.

The USB Device controller supports connections at Super Speed (3.0) on the USB3DEV interface, and High and Full speeds (2.0/1.x) on the ULPI interface. To support High and Full Speed devices on ULPI, an external PHY is required.

Note: The ULPI interface must be implemented even if only SuperSpeed support is required. The USB3DEV interface will not operate if the ULPI interface is disabled.



19.0.1 Signal Descriptions

See [Chapter 2, “Physical Interfaces”](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal’s function




Table 217. USB 3.0 Device Signals

Signal Name	Direction Plat. Power	Description
USB3DEV_RXP/N[0]	I V1P0S	Data In: High speed serialized data inputs
USB3DEV_TXP/N[0]	O V1P0S	Data Out: High speed serialized data outputs.
USB3DEV_REXT[0]		Resistor Compensation: An external resistor must be connected between this pin and package ground. Contact your Intel representative for details.

Table 218. USB ULPI Device Signals

Signal Name	Direction Plat. Power	Description
USB_ULPI_CLK	I V1P8A	Interface Clock By default, control and data signals are synchronous to clock.
USB_ULPI_DATA[7:0]	I/O V1P8A	Bi-directional data bus Driven low by the Link during idle. The Link starts a transfer by sending a non-zero pattern. The PHY must assert USB_ULPI_DIR before using the data bus. A turnaround cycle is required every time that USB_ULPI_DIR toggles.
USB_ULPI_DIR	I V1P8A	Direction of the data bus By default, USB_ULPI_DIR is low and the PHY listens for non-zero data from the Link. The PHY asserts USB_ULPI_DIR to get control of the data bus.
USB_ULPI_NXT	I V1P8A	Next Data The PHY drives USB_ULPI_NXT high to throttle the data bus
USB_ULPI_STP	O V1P8A	Stop data The Link drives USB_ULPI_STP high to signal the end of its data stream. The Link can also drive USB_ULPI_STP high to request data bus access from the PHY
USB_ULPI_REFCLK	O V1P8A	Reference clock ULPI reference clock for external PHY
USB_ULPI_RST#	O V1P8A	Reset Used to reset the external PHY. Not part of ULPI specification. Optionally used by driver.



19.1 USB Device Controller

The USB device controller can control one USB 3.0 Device port. Either a combo SS + ULPI Device port, or UPLI only port. It supports hosts conforming to USB 3.0 at bit rates up to 5 Gbps on USB3DEV interface as well as USB 2.0 hosts at up to 480 Mbps via a PHY on ULPI.

19.1.1 Features

Features supported by the Device Controller include:

- Enumerated by both ACPI and PCI. The USB3 device subsystem is designed to appear to the OS as a true PCI device. It will also support ACPI-enumerated methods.
- Device controller registers and data structures are implemented as extensions to the EHCI programmers interface.
- Support for LPM (Link Power Management)

Some of the key features of the ULPI device controller are:

- Supports up to 8 endpoints when acting as device
- 8-bit data interface transmitted at 60 MHz ULPI clock

Note: Recommended not to disconnect the connection when a debug session is in progress.

19.1.2 Power Management Features

The USB 3.0 device subsystem supports the following device power states:

- D0: Functional and highest power state.
- RTD3 (D3): Software managed deepest low power state in which state is saved/restored if needed prior to entry/exit


19.1.2.1 D0

This is the Functional and highest power state. The USB 3.0 device subsystem is in this state when the USB link is in U0 (U0 is the normal operational state where packets can be transmitted and received).

19.1.2.2 D3

D3 is a low power state that is used when the link is suspended; for example, U3 (U3 is a link state where a device is put into a suspend state. Significant link and device powers are saved).

This is a software directed state in which the controller is either power gated or the power is disabled.



19.1.3 Interrupts

A Functional Interrupt is generated by the logic in the USB device controller core to indicate the occurrence of an event needing application intervention. The design of the USB device core is such that events such as "link change" that would traditionally trigger an interrupt through an interrupt status register, are instead delivered to an 'Event buffer' in host memory, together with an interrupt indicating this.

19.2 References

Universal Serial Bus (USB) 3.0 Revision Specification

Universal Serial Bus (USB) 2.0 Revision Specification

ULPI Working Group: <http://www.ulpi.org/>

19.3 Register Map

See Chapters [Section 3, "Register Access Methods" on page 69](#) and [Section 4, "Mapping Address Spaces" on page 75](#) for additional information. Also note that the device controller also contains both device and host registers. The host functionality of this controller is not fully functional and should not be used. See the USB Host chapter for host controllers.



Type: PCI Configuration Register
(Size: 32 bits)

STATUSCOMMAND: [B:0, D:22, F:0] + 4h

Default: 00100000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0	RMA	RCA	Reserved1	CAPLIST	INTR_STATUS	Reserved2	Reserved3	INTR_DISABLE
								Reserved4
								SERR_ENABLE
							Reserved5	BME
								MSE
								Reserved6

Bit Range	Default & Access	Description
31:30	0h RO	Reserved0: Reserved.
29	0h RW/1C	RMA: Reserved.
28	0h RW/1C	RCA: Reserved.
27:21	00h RO	Reserved1: Reserved.
20	1h RO	CAPLIST: Reserved.
19	0h RO	INTR_STATUS: Reserved.
18:16	0h RO	Reserved2: Reserved.
15:11	00h RO	Reserved3: Reserved.
10	0h RW	INTR_DISABLE: Reserved.
9	0h RO	Reserved4: Reserved.
8	0h RW	SERR_ENABLE: Reserved.
7:3	00h RO	Reserved5: Reserved.
2	0h RW	BME: Reserved.
1	0h RW	MSE: Reserved.
0	0h RO	Reserved6: Reserved.



19.4.3 reg_REVCLASSCODE_type (REVCLASSCODE)—Offset 8h

REVCLASSCODE - Revision ID and Class Code

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

REVCLASSCODE: [B:0, D:22, F:0] + 8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Description
31:8	000000h RO	CLASS_CODES: Reserved.
7:0	00h RO	RID: Reserved.

19.4.4 reg_CLLATHEADERBIST_type (CLLATHEADERBIST)—Offset Ch

CLLATHEADERBIST - Cache Line Latency Header and BIST

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

CLLATHEADERBIST: [B:0, D:22, F:0] + Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0			MULFNDEV	HEADERTYPE		LATTIMER	CACHELINE_SIZE	

Bit Range	Default & Access	Description
31:24	00h RO	Reserved0: Reserved.
23	0h RO	MULFNDEV: Reserved.
22:16	00h RO	HEADERTYPE: Reserved.



Bit Range	Default & Access	Description
15:8	00h RO	LATTIMER: Reserved.
7:0	00h RW	CACHELINE_SIZE: Reserved.

19.4.5 reg_BAR_type (BAR)—Offset 10h

BAR -Base Address Register

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

BAR: [B:0, D:22, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:12	00000h RW	BASEADDR: Reserved.
11:4	00h RO	SIZEINDICATOR: Reserved.
3	0h RO	PREFETCHABLE: Reserved.
2:1	0h RO	TYPE: Reserved.
0	0h RO	MESSAGE_SPACE: Reserved.

19.4.6 reg_BAR1_type (BAR1)—Offset 14h

BAR1 -Base Address Register1

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

BAR1: [B:0, D:22, F:0] + 14h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		PREFETCHABLE1
								TYPE1
								MESSAGE_SPACE1

Bit Range	Default & Access	Description
31:12	00000h RW	BASEADDR1: Reserved.
11:4	00h RO	SIZEINDICATOR1: Reserved.
3	0h RO	PREFETCHABLE1: Reserved.
2:1	0h RO	TYPE1: Reserved.
0	0h RO	MESSAGE_SPACE1: Reserved.

19.4.7 reg_SUBSYSTEMID_type (SUBSYSTEMID)—Offset 2Ch

SUBSYSTEMID -Subsystem Vendor and Subsystem ID

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SUBSYSTEMID: [B:0, D:22, F:0] + 2Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SUBSYSTEMID						SUBSYSTEMVENDORID		

Bit Range	Default & Access	Description
31:16	0000h RW/O	SUBSYSTEMID: Reserved.
15:0	0000h RW/O	SUBSYSTEMVENDORID: Reserved.



Access Method

INTERRUPTREG: [B:0, D:22, F:0] + 3Ch

	31	28	24	20	16	12	8	4	0
	0	0	0	0	0	0	0	0	0
	MAX_LAT		MIN_GNT		Reserved0		INTPIN		INTLINE

Bit Range	Default & Access	Description
31:24	00h RO	MAX_LAT: Reserved.
23:16	00h RO	MIN_GNT: Reserved.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	INTPIN: Reserved.
7:0	00h RW	INTLINE: Reserved.

19.4.11 reg_POWERCAPID_type (POWERCAPID)—Offset 80h

Access Method

POWERCAPID: [B:0, D:22, F:0] + 80h

31				28				24				20				16				12				8				4				0			
0	1	0	0	1	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
PMESUPPORT				Reserved0				VERSION				NXTCAP				POWER_CAP																			

Bit Range	Default & Access	Description
31:27	09h RO	PMESUPPORT: Reserved.
26:19	00h RO	Reserved0: Reserved.



Bit Range	Default & Access	Description
18:16	3h RO	VERSION: Reserved.
15:8	00h RO	NXTCAP: Reserved.
7:0	01h RO	POWER_CAP: Reserved.

19.4.12 reg_PMECTRLSTATUS_type (PMECTRLSTATUS)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PMECTRLSTATUS: [B:0, D:22, F:0] + 84h

Default: 00000008h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0				PMESTATUS	Reserved1		PMEEENABLE	Reserved2
								NO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Description
31:16	0000h RO	Reserved0: Reserved.
15	0h RW/1C	PMESTATUS: Reserved.
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PMEENABLE: Reserved.
7:4	0h RO	Reserved2: Reserved.
3	1h RO	NO_SOFT_RESET: Reserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	POWERSTATE: Reserved.

19.4.13 reg_MANID_type (MANID)—Offset F8h

Manufacturers ID

Access Method



Type: PCI Configuration Register
(Size: 32 bits)

MANID: [B:0, D:22, F:0] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

MANID

Bit Range	Default & Access	Description
31:0	00000000h RO	MANID: Reserved.



Type: PCI Configuration Register
(Size: 32 bits)

STATUSCOMMAND: [B:0, D:22, F:0] + 4h

Default: 00100000h

31		28		24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
0		0		0		0		0		0		1		0		0		0		0		0		0		0		0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
Reserved0		RMA		RCA	Reserved1								CAPLIST	INTR_STATUS				Reserved2	Reserved3								INTR_DISABLE	Reserved4				SERR_ENABLE	Reserved5								BME	MSE	Reserved6																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																						

Bit Range	Default & Access	Description
31:30	0h RO	Reserved0: Reserved.
29	0h RW/1C	RMA: Reserved.
28	0h RW/1C	RCA: Reserved.
27:21	00h RO	Reserved1: Reserved.
20	1h RO	CAPLIST: Reserved.
19	0h RO	INTR_STATUS: Reserved.
18:16	0h RO	Reserved2: Reserved.
15:11	00h RO	Reserved3: Reserved.
10	0h RW	INTR_DISABLE: Reserved.
9	0h RO	Reserved4: Reserved.
8	0h RW	SERR_ENABLE: Reserved.
7:3	00h RO	Reserved5: Reserved.
2	0h RW	BME: Reserved.
1	0h RW	MSE: Reserved.
0	0h RO	Reserved6: Reserved.



19.5.3 reg_REVCLASSCODE_type (REVCLASSCODE)—Offset 8h

REVCLASSCODE - Revision ID and Class Code

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

REVCLASSCODE: [B:0, D:22, F:0] + 8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Description
31:8	000000h RO	CLASS_CODES: Reserved.
7:0	00h RO	RID: Reserved.

19.5.4 reg_CLLATHEADERBIST_type (CLLATHEADERBIST)—Offset Ch

CLLATHEADERBIST - Cache Line Latency Header and BIST

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

CLLATHEADERBIST: [B:0, D:22, F:0] + Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0		MULFNDEV	HEADERTYPE		LATTIMER	CACHELINE_SIZE		

Bit Range	Default & Access	Description
31:24	00h RO	Reserved0: Reserved.
23	0h RO	MULFNDEV: Reserved.
22:16	00h RO	HEADERTYPE: Reserved.



BAR -Base Address Register

Type: PCI Configuration Register
(Size: 32 bits)

	31			28			24			20			16			12			8			4			0				
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	BASEADDR																SIZEINDICATOR								PREFETCHABLE	TYPE		MESSAGE SPACE	

19.5.6 reg_BAR1_type (BAR1)—Offset 14h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
31:16	0000h RW/O	SUBSYSTEMID: Reserved.
15:0	0000h RW/O	SUBSYSTEMVENDORID: Reserved.



Access Method

EXPANSION ROM BASEADDR: [B:0, D:22, F:0] + 30h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSTON_ROM_BASE								

Bit Range	Default & Access	Description
31:0	00000000h RO	EXPANSION_ROM_BASE: Reserved.

19.5.9 reg_CAPABILITYPTR_type (CAPABILITYPTR)—Offset 34h

Access Method

CAPABILITYPTR: [B:0, D:22, F:0] + 34h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Description
31:8	000000h RO	Reserved0: Reserved.
7:0	80h RO	CAPPTR_POWER: Reserved.

19.5.12 reg_PMECTRLSTATUS_type (PMECTRLSTATUS)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PMECTRLSTATUS: [B:0, D:22, F:0] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0				PMESTATUS	Reserved1		PMEENABLE	Reserved2
								NO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Description
31:16	0000h RO	Reserved0: Reserved.
15	0h RW/1C	PMESTATUS: Reserved.
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PMEENABLE: Reserved.
7:4	0h RO	Reserved2: Reserved.
3	1h RO	NO_SOFT_RESET: Reserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	POWERSTATE: Reserved.

19.5.13 reg_MANID_type (MANID)—Offset F8h

Manufacturers ID

Access Method



19.6 USB 3.0 Device Memory Mapped I/O Registers

Table 221. Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR

Offset	Size	Register ID—Description	Default Value
0h	4	"CAPLENGTH—Offset 0h" on page 2480	00960020h
4h	4	"HCSPARAMS1—Offset 4h" on page 2481	0200017Fh
8h	4	"HCSPARAMS2—Offset 8h" on page 2482	140000F1h
Ch	4	"HCSPARAMS3—Offset Ch" on page 2482	07FF000Ah
10h	4	"HCCPARAMS—Offset 10h" on page 2483	0220F04Ch
14h	4	"DBOFF—Offset 14h" on page 2484	00000480h
18h	4	"RTSOFF—Offset 18h" on page 2485	00000440h
1Ch	4	"Rsvd_HC—Offset 1Ch" on page 2486	00000000h
20h	4	"USBCMD—Offset 20h" on page 2486	00000000h
24h	4	"USBSTS—Offset 24h" on page 2488	00000001h
28h	4	"PAGESIZE—Offset 28h" on page 2489	00000001h
34h	4	"DNCTRL—Offset 34h" on page 2489	00000000h
38h	4	"CRCR_LO—Offset 38h" on page 2490	00000000h
3Ch	4	"CRCR_HI—Offset 3Ch" on page 2491	00000000h
50h	4	"DCBAAP_LO—Offset 50h" on page 2492	00000000h
54h	4	"DCBAAP_HI—Offset 54h" on page 2492	00000000h
58h	4	"CONFIG—Offset 58h" on page 2493	00000000h
420h	4	"PORTSC1—Offset 420h" on page 2493	000002A0h
424h	4	"PORTPMSC1—Offset 424h" on page 2496	00000000h
428h	4	"PORTLI—Offset 428h" on page 2497	00000000h
42Ch	4	"PORTHLMC—Offset 42Ch" on page 2497	00000000h
430h	4	"PORTSC2—Offset 430h" on page 2498	000002A0h
434h	4	"PORTPMSC2—Offset 434h" on page 2501	00000000h
440h	4	"MFINDEX—Offset 440h" on page 2502	00000000h
444h	4	"RsvdZ—Offset 444h" on page 2502	00000000h
460h	4	"IMAN—Offset 460h" on page 2502	00000000h
464h	4	"IMOD—Offset 464h" on page 2503	00000FA0h
468h	4	"ERSTSZ—Offset 468h" on page 2504	00000000h
46Ch	4	"RsvdP—Offset 46Ch" on page 2504	00000000h
470h	4	"ERSTBA_LO—Offset 470h" on page 2505	00000000h
474h	4	"ERSTBA_HI—Offset 474h" on page 2505	00000000h
478h	4	"ERDP_LO—Offset 478h" on page 2506	00000000h
47Ch	4	"ERDP_HI—Offset 47Ch" on page 2506	00000000h
480h	4	"DB_0—Offset 480h" on page 2507	00000000h
484h	4	"DB_1—Offset 484h" on page 2508	00000000h
488h	4	"DB_2—Offset 488h" on page 2509	00000000h



Table 221. Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR (Continued)

Offset	Size	Register ID—Description	Default Value
48Ch	4	"DB_3—Offset 48Ch" on page 2510	00000000h
490h	4	"DB_4—Offset 490h" on page 2511	00000000h
494h	4	"DB_5—Offset 494h" on page 2512	00000000h
498h	4	"DB_6—Offset 498h" on page 2513	00000000h
49Ch	4	"DB_7—Offset 49Ch" on page 2514	00000000h
4A0h	4	"DB_8—Offset 4A0h" on page 2515	00000000h
4A4h	4	"DB_9—Offset 4A4h" on page 2516	00000000h
4A8h	4	"DB_10—Offset 4A8h" on page 2517	00000000h
4ACh	4	"DB_11—Offset 4ACh" on page 2518	00000000h
4B0h	4	"DB_12—Offset 4B0h" on page 2519	00000000h
4B4h	4	"DB_13—Offset 4B4h" on page 2520	00000000h
4B8h	4	"DB_14—Offset 4B8h" on page 2521	00000000h
4BCh	4	"DB_15—Offset 4BCh" on page 2522	00000000h
4C0h	4	"DB_16—Offset 4C0h" on page 2523	00000000h
880h	4	"USBLEGSUP—Offset 880h" on page 2524	00000401h
884h	4	"USBLEGCTLS—Offset 884h" on page 2525	00000000h
890h	4	"SUPTPRT2_DW0—Offset 890h" on page 2526	02000002h
894h	4	"SUPTPRT2_DW1—Offset 894h" on page 2526	02000110h
898h	4	"SUPTPRT2_DW2—Offset 898h" on page 2527	00080001h
8A0h	4	"SUPTPRT3_DW0—Offset 8A0h" on page 2528	03000002h
8A4h	4	"SUPTPRT3_DW1—Offset 8A4h" on page 2529	00000000h
8A8h	4	"SUPTPRT3_DW2—Offset 8A8h" on page 2529	00000000h
C100h	4	"GSBUSCFG0—Offset C100h" on page 2530	00000006h
C104h	4	"GSBUSCFG1—Offset C104h" on page 2531	00000F00h
C108h	4	"GTXTHRCFG—Offset C108h" on page 2532	230A0000h
C10Ch	4	"GRXTHRCFG—Offset C10Ch" on page 2532	22800000h
C110h	4	"GCTL—Offset C110h" on page 2533	45803000h
C118h	4	"GSTS—Offset C118h" on page 2535	3E800002h
C120h	4	"GSNPSID—Offset C120h" on page 2536	5533192Ah
C124h	4	"GGPIO—Offset C124h" on page 2536	00000000h
C128h	4	"GUID—Offset C128h" on page 2537	12345678h
C12Ch	4	"GUCTL—Offset C12Ch" on page 2537	7FC0C600h
C130h	4	"GBUSERRADDRLO—Offset C130h" on page 2538	00000000h
C134h	4	"GBUSERRADDRHI—Offset C134h" on page 2539	00000000h
C138h	4	"GPRTBIMAPLO—Offset C138h" on page 2539	00000000h
C13Ch	4	"GPRTBIMAPI—Offset C13Ch" on page 2540	00000000h
C140h	4	"GHWPARAMS0—Offset C140h" on page 2541	2020400Ah
C144h	4	"GHWPARAMS1—Offset C144h" on page 2542	0260C93Bh
C148h	4	"GHWPARAMS2—Offset C148h" on page 2543	008086A0h



Table 221. Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR (Continued)

Offset	Size	Register ID—Description	Default Value
C14Ch	4	"GHWPARAMS3—Offset C14Ch" on page 2543	10420089h
C150h	4	"GHWPARAMS4—Offset C150h" on page 2545	48822004h
C154h	4	"GHWPARAMS5—Offset C154h" on page 2545	04202088h
C158h	4	"GHWPARAMS6—Offset C158h" on page 2546	0C00AC20h
C15Ch	4	"GHWPARAMS7—Offset C15Ch" on page 2547	038807E6h
C160h	4	"GDBGFIFOSPACE—Offset C160h" on page 2548	00420000h
C164h	4	"GDBGLTSSM—Offset C164h" on page 2549	01010440h
C180h	4	"GPRTBIMAP_HSLO—Offset C180h" on page 2550	00000000h
C184h	4	"GPRTBIMAP_HSHI—Offset C184h" on page 2551	00000000h
C188h	4	"GPRTBIMAP_FSLO—Offset C188h" on page 2552	00000000h
C18Ch	4	"GPRTBIMAP_FSHI—Offset C18Ch" on page 2552	00000000h
C200h	4	"GUSB2PHYCFG—Offset C200h" on page 2553	0000A410h
C240h	4	"GUSB2I2CCTL—Offset C240h" on page 2554	00000000h
C280h	4	"GUSB2PHYACC—Offset C280h" on page 2555	00000000h
C2C0h	4	"GUSB3PIPECTL—Offset C2C0h" on page 2556	02044002h
C300h	4	"GTXFIFOSIZ0—Offset C300h" on page 2558	00000042h
C304h	4	"GTXFIFOSIZ1—Offset C304h" on page 2559	00420184h
C308h	4	"GTXFIFOSIZ2—Offset C308h" on page 2559	01C60184h
C30Ch	4	"GTXFIFOSIZ3—Offset C30Ch" on page 2560	034A0184h
C310h	4	"GTXFIFOSIZ4—Offset C310h" on page 2560	04CE0082h
C314h	4	"GTXFIFOSIZ5—Offset C314h" on page 2561	05500082h
C318h	4	"GTXFIFOSIZ6—Offset C318h" on page 2561	05D20082h
C31Ch	4	"GTXFIFOSIZ7—Offset C31Ch" on page 2562	06540082h
C320h	4	"GTXFIFOSIZ8—Offset C320h" on page 2562	06D60022h
C324h	4	"GTXFIFOSIZ9—Offset C324h" on page 2563	06F80022h
C328h	4	"GTXFIFOSIZ10—Offset C328h" on page 2563	071A0022h
C32Ch	4	"GTXFIFOSIZ11—Offset C32Ch" on page 2564	073C0022h
C330h	4	"GTXFIFOSIZ12—Offset C330h" on page 2564	075E0022h
C334h	4	"GTXFIFOSIZ13—Offset C334h" on page 2565	07800022h
C338h	4	"GTXFIFOSIZ14—Offset C338h" on page 2565	07A20022h
C33Ch	4	"GTXFIFOSIZ15—Offset C33Ch" on page 2566	07C40022h
C380h	4	"GRXFIFOSIZ0—Offset C380h" on page 2566	00000385h
C384h	4	"GRXFIFOSIZ1—Offset C384h" on page 2567	03850000h
C388h	4	"GRXFIFOSIZ2—Offset C388h" on page 2567	03850000h
C400h	4	"GEVNTADRLO—Offset C400h" on page 2568	00000000h
C404h	4	"GEVNTADRHI—Offset C404h" on page 2568	00000000h
C408h	4	"GEVNTSIZ—Offset C408h" on page 2568	00000000h
C40Ch	4	"GEVNTCOUNT—Offset C40Ch" on page 2569	00000000h
C600h	4	"GHWPARAMS8—Offset C600h" on page 2569	00002000h

**Table 221. Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR (Continued)**

Offset	Size	Register ID—Description	Default Value
C700h	4	"DCFG—Offset C700h" on page 2570	00080800h
C704h	4	"DCTL—Offset C704h" on page 2571	00000000h
C708h	4	"DEVTEEN—Offset C708h" on page 2572	00000000h
C70Ch	4	"DSTS—Offset C70Ch" on page 2573	00120004h
C710h	4	"DGCMDPAR—Offset C710h" on page 2574	00000000h
C714h	4	"DGCMDPAR—Offset C710h" on page 2574	00000000h
C720h	4	"DALEPENA—Offset C720h" on page 2575	00000000h
C800h	4	"DEPCMDPAR2_0—Offset C800h" on page 2576	00000000h
C804h	4	"DEPCMDPAR1_0—Offset C804h" on page 2576	00000000h
C808h	4	"DEPCMDPAR0_0—Offset C808h" on page 2577	00000000h
C80Ch	4	"DEPCMD_0—Offset C80Ch" on page 2577	00000000h
C810h	4	"DEPCMDPAR2_1—Offset C810h" on page 2578	00000000h
C814h	4	"DEPCMDPAR1_1—Offset C814h" on page 2578	00000000h
C818h	4	"DEPCMDPAR0_1—Offset C818h" on page 2579	00000000h
C81Ch	4	"DEPCMD_1—Offset C81Ch" on page 2579	00000000h
C820h	4	"DEPCMDPAR2_2—Offset C820h" on page 2580	00000000h
C824h	4	"DEPCMDPAR1_2—Offset C824h" on page 2580	00000000h
C828h	4	"DEPCMDPAR0_2—Offset C828h" on page 2581	00000000h
C82Ch	4	"DEPCMD_2—Offset C82Ch" on page 2581	00000000h
C830h	4	"DEPCMDPAR2_3—Offset C830h" on page 2582	00000000h
C834h	4	"DEPCMDPAR1_3—Offset C834h" on page 2582	00000000h
C838h	4	"DEPCMDPAR0_3—Offset C838h" on page 2583	00000000h
C83Ch	4	"DEPCMD_3—Offset C83Ch" on page 2583	00000000h
C840h	4	"DEPCMDPAR2_4—Offset C840h" on page 2584	00000000h
C844h	4	"DEPCMDPAR1_4—Offset C844h" on page 2584	00000000h
C848h	4	"DEPCMDPAR0_4—Offset C848h" on page 2585	00000000h
C84Ch	4	"DEPCMD_4—Offset C84Ch" on page 2585	00000000h
C850h	4	"DEPCMDPAR2_5—Offset C850h" on page 2586	00000000h
C854h	4	"DEPCMDPAR1_5—Offset C854h" on page 2586	00000000h
C858h	4	"DEPCMDPAR0_5—Offset C858h" on page 2587	00000000h
C85Ch	4	"DEPCMD_5—Offset C85Ch" on page 2587	00000000h
C860h	4	"DEPCMDPAR2_6—Offset C860h" on page 2588	00000000h
C864h	4	"DEPCMDPAR1_6—Offset C864h" on page 2588	00000000h
C868h	4	"DEPCMDPAR0_6—Offset C868h" on page 2589	00000000h
C86Ch	4	"DEPCMD_6—Offset C86Ch" on page 2589	00000000h
C870h	4	"DEPCMDPAR2_7—Offset C870h" on page 2590	00000000h
C874h	4	"DEPCMDPAR1_7—Offset C874h" on page 2590	00000000h
C878h	4	"DEPCMDPAR0_7—Offset C878h" on page 2591	00000000h
C87Ch	4	"DEPCMD_7—Offset C87Ch" on page 2591	00000000h




Table 221. Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR (Continued)

Offset	Size	Register ID—Description	Default Value
C880h	4	"DEPCMDPAR2_8—Offset C880h" on page 2592	00000000h
C884h	4	"DEPCMDPAR1_8—Offset C884h" on page 2593	00000000h
C888h	4	"DEPCMDPAR0_8—Offset C888h" on page 2593	00000000h
C88Ch	4	"DEPCMD_8—Offset C88Ch" on page 2593	00000000h
C890h	4	"DEPCMDPAR2_9—Offset C890h" on page 2594	00000000h
C894h	4	"DEPCMDPAR1_9—Offset C894h" on page 2595	00000000h
C898h	4	"DEPCMDPAR0_9—Offset C898h" on page 2595	00000000h
C89Ch	4	"DEPCMD_9—Offset C89Ch" on page 2596	00000000h
C8A0h	4	"DEPCMDPAR2_10—Offset C8A0h" on page 2596	00000000h
C8A4h	4	"DEPCMDPAR1_10—Offset C8A4h" on page 2597	00000000h
C8A8h	4	"DEPCMDPAR0_10—Offset C8A8h" on page 2597	00000000h
C8ACh	4	"DEPCMD_10—Offset C8ACh" on page 2598	00000000h
C8B0h	4	"DEPCMDPAR2_11—Offset C8B0h" on page 2599	00000000h
C8B4h	4	"DEPCMDPAR1_11—Offset C8B4h" on page 2599	00000000h
C8B8h	4	"DEPCMDPAR0_11—Offset C8B8h" on page 2599	00000000h
C8BCh	4	"DEPCMD_11—Offset C8BCh" on page 2600	00000000h
C8C0h	4	"DEPCMDPAR2_12—Offset C8C0h" on page 2601	00000000h
C8C4h	4	"DEPCMDPAR1_12—Offset C8C4h" on page 2601	00000000h
C8C8h	4	"DEPCMDPAR0_12—Offset C8C8h" on page 2602	00000000h
C8CCh	4	"DEPCMD_12—Offset C8CCh" on page 2602	00000000h
C8D0h	4	"DEPCMDPAR2_13—Offset C8D0h" on page 2603	00000000h
C8D4h	4	"DEPCMDPAR1_13—Offset C8D4h" on page 2603	00000000h
C8D8h	4	"DEPCMDPAR0_13—Offset C8D8h" on page 2604	00000000h
C8DCh	4	"DEPCMD_13—Offset C8DCh" on page 2604	00000000h
C8E0h	4	"DEPCMDPAR2_14—Offset C8E0h" on page 2605	00000000h
C8E4h	4	"DEPCMDPAR1_14—Offset C8E4h" on page 2606	00000000h
C8E8h	4	"DEPCMDPAR0_14—Offset C8E8h" on page 2606	00000000h
C8ECh	4	"DEPCMD_14—Offset C8ECh" on page 2606	00000000h
C8F0h	4	"DEPCMDPAR2_15—Offset C8F0h" on page 2607	00000000h
C8F4h	4	"DEPCMDPAR1_15—Offset C8F4h" on page 2608	00000000h
C8F8h	4	"DEPCMDPAR0_15—Offset C8F8h" on page 2608	00000000h
C8FCh	4	"DEPCMD_15—Offset C8FCh" on page 2609	00000000h
C900h	4	"DEPCMDPAR2_16—Offset C900h" on page 2609	00000000h
C904h	4	"DEPCMDPAR1_16—Offset C904h" on page 2610	00000000h
C908h	4	"DEPCMDPAR0_16—Offset C908h" on page 2610	00000000h
C90Ch	4	"DEPCMD_16—Offset C90Ch" on page 2611	00000000h
C910h	4	"DEPCMDPAR2_17—Offset C910h" on page 2612	00000000h
C914h	4	"DEPCMDPAR1_17—Offset C914h" on page 2612	00000000h
C918h	4	"DEPCMDPAR0_17—Offset C918h" on page 2612	00000000h



Table 221. Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR (Continued)

Offset	Size	Register ID—Description	Default Value
C91Ch	4	"DEPCMD_17—Offset C91Ch" on page 2613	00000000h
C920h	4	"DEPCMDPAR2_18—Offset C920h" on page 2614	00000000h
C924h	4	"DEPCMDPAR1_18—Offset C924h" on page 2614	00000000h
C928h	4	"DEPCMDPAR0_18—Offset C928h" on page 2615	00000000h
C92Ch	4	"DEPCMD_18—Offset C92Ch" on page 2615	00000000h
C930h	4	"DEPCMDPAR2_19—Offset C930h" on page 2616	00000000h
C934h	4	"DEPCMDPAR1_19—Offset C934h" on page 2616	00000000h
C938h	4	"DEPCMDPAR0_19—Offset C938h" on page 2617	00000000h
C93Ch	4	"DEPCMD_19—Offset C93Ch" on page 2617	00000000h
C940h	4	"DEPCMDPAR2_20—Offset C940h" on page 2618	00000000h
C944h	4	"DEPCMDPAR1_20—Offset C944h" on page 2619	00000000h
C948h	4	"DEPCMDPAR0_20—Offset C948h" on page 2619	00000000h
C94Ch	4	"DEPCMD_20—Offset C94Ch" on page 2619	00000000h
C950h	4	"DEPCMDPAR2_21—Offset C950h" on page 2620	00000000h
C954h	4	"DEPCMDPAR1_21—Offset C954h" on page 2621	00000000h
C958h	4	"DEPCMDPAR0_21—Offset C958h" on page 2621	00000000h
C95Ch	4	"DEPCMD_21—Offset C95Ch" on page 2622	00000000h
C960h	4	"DEPCMDPAR2_22—Offset C960h" on page 2622	00000000h
C964h	4	"DEPCMDPAR1_22—Offset C964h" on page 2623	00000000h
C968h	4	"DEPCMDPAR0_22—Offset C968h" on page 2623	00000000h
C96Ch	4	"DEPCMD_22—Offset C96Ch" on page 2624	00000000h
C970h	4	"DEPCMDPAR2_23—Offset C970h" on page 2625	00000000h
C974h	4	"DEPCMDPAR1_23—Offset C974h" on page 2625	00000000h
C978h	4	"DEPCMDPAR0_23—Offset C978h" on page 2625	00000000h
C97Ch	4	"DEPCMD_23—Offset C97Ch" on page 2626	00000000h
C980h	4	"DEPCMDPAR2_24—Offset C980h" on page 2627	00000000h
C984h	4	"DEPCMDPAR1_24—Offset C984h" on page 2627	00000000h
C988h	4	"DEPCMDPAR0_24—Offset C988h" on page 2628	00000000h
C98Ch	4	"DEPCMD_24—Offset C98Ch" on page 2628	00000000h
C990h	4	"DEPCMDPAR2_25—Offset C990h" on page 2629	00000000h
C994h	4	"DEPCMDPAR1_25—Offset C994h" on page 2629	00000000h
C998h	4	"DEPCMDPAR0_25—Offset C998h" on page 2630	00000000h
C99Ch	4	"DEPCMD_25—Offset C99Ch" on page 2630	00000000h
C9A0h	4	"DEPCMDPAR2_26—Offset C9A0h" on page 2631	00000000h
C9A4h	4	"DEPCMDPAR1_26—Offset C9A4h" on page 2632	00000000h
C9A8h	4	"DEPCMDPAR0_26—Offset C9A8h" on page 2632	00000000h
C9ACh	4	"DEPCMD_26—Offset C9ACh" on page 2632	00000000h
C9B0h	4	"DEPCMDPAR2_27—Offset C9B0h" on page 2633	00000000h
C9B4h	4	"DEPCMDPAR1_27—Offset C9B4h" on page 2634	00000000h



Table 221. Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR (Continued)

Offset	Size	Register ID—Description	Default Value
C9B8h	4	"DEPCMDPAR0_27—Offset C9B8h" on page 2634	00000000h
C9BCh	4	"DEPCMD_27—Offset C9BCh" on page 2635	00000000h
C9C0h	4	"DEPCMDPAR2_28—Offset C9C0h" on page 2635	00000000h
C9C4h	4	"DEPCMDPAR1_28—Offset C9C4h" on page 2636	00000000h
C9C8h	4	"DEPCMDPAR0_28—Offset C9C8h" on page 2636	00000000h
C9CCh	4	"DEPCMD_28—Offset C9CCh" on page 2637	00000000h
C9D0h	4	"DEPCMDPAR2_29—Offset C9D0h" on page 2638	00000000h
C9D4h	4	"DEPCMDPAR1_29—Offset C9D4h" on page 2638	00000000h
C9D8h	4	"DEPCMDPAR0_29—Offset C9D8h" on page 2638	00000000h
C9DCh	4	"DEPCMD_29—Offset C9DCh" on page 2639	00000000h
C9E0h	4	"DEPCMDPAR2_30—Offset C9E0h" on page 2640	00000000h
C9E4h	4	"DEPCMDPAR1_30—Offset C9E4h" on page 2640	00000000h
C9E8h	4	"DEPCMDPAR0_30—Offset C9E8h" on page 2641	00000000h
C9ECh	4	"DEPCMD_30—Offset C9ECh" on page 2641	00000000h
C9F0h	4	"DEPCMDPAR2_31—Offset C9F0h" on page 2642	00000000h
C9F4h	4	"DEPCMDPAR1_31—Offset C9F4h" on page 2642	00000000h
C9F8h	4	"DEPCMDPAR0_31—Offset C9F8h" on page 2643	00000000h
C9FCh	4	"DEPCMD_31—Offset C9FCh" on page 2643	00000000h
CC00h	4	"OCFG—Offset CC00h" on page 2644	00000000h
CC04h	4	"OCTL—Offset CC04h" on page 2645	00000040h
CC08h	4	"OEVT—Offset CC08h" on page 2646	80000000h
CC0Ch	4	"OEVTEN—Offset CC0Ch" on page 2648	00000000h
CC10h	4	"OSTS—Offset CC10h" on page 2649	00000019h
CC20h	4	"ADPCFG—Offset CC20h" on page 2650	00000000h
CC24h	4	"ADPCTL—Offset CC24h" on page 2650	00000000h
CC28h	4	"ADPEVT—Offset CC28h" on page 2651	00000000h
CC2Ch	4	"ADPEVTEN—Offset CC2Ch" on page 2652	00000000h
CC30h	4	"BCFG—Offset CC30h" on page 2653	00000000h
CC38h	4	"BCEVT—Offset CC38h" on page 2653	00000000h
CC3Ch	4	"BCEVTEN—Offset CC3Ch" on page 2654	00000000h

19.6.1 CAPLENGTH—Offset 0h

This register is used as an offset to add to register base to find the beginning of the Operational Register Space.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CAPLENGTH: [BAR] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h



Bit Range	Default & Access	Description
18:8	1h RO	MAXINTRS: Number of Interrupters (MaxIntrs). This field specifies the number of Interrupters implemented on this host controller. Each Interrupter may be allocated to a MSI or MSI-X vector and controls its generation and moderation. The value of this field determines how many Interrupter Register Sets are addressable in the Runtime Register Space (refer to section 5.5). Valid values are in the range of 1h to 400h. A 0 in this field is undefined.
7:0	7fh RO	MAXSLOTS: Number of Device Slots (MaxSlots). This field specifies the maximum number of Device Context Structures and Doorbell Array entries this host controller can support. Valid values are in the range of 1 to 255. The value of 0 is reserved.

19.6.3 HCSPARAMS2—Offset 8h

Host Controller Structural Parameters 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

HCSPARAMS2: [BAR] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 140000F1h

31				28				24				20				16				12				8				4				0									
0	0	0	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	0	0	1											
MAXSCRATCHPADBUFS								SPR		HCSPARAMS2_RSVD1																IOCINTERVAL								ERSTMAX				IST			

Bit Range	Default & Access	Description
31:27	02h RO	MAXSCRATCHPADBUFS: For xHCI 0.96, this field is Max Scratchpad Bufs / For xHCI 1.0, this field is Max Scratchpad Bufs Lo
26	1h RO	SPR: Scratchpad Restore (SPR)
25:13	0h RO	HCSPARAMS2_RSVD1: reserved
12:8	0h RO	IOCINTERVAL: This field is valid only for xHCI 0.96. For xHCI 1.0, this field is Reserved.
7:4	fh RO	ERSTMAX: Event Ring Segment Table Max (ERST Max)
3:0	1h RO	IST: Isochronous Scheduling Threshold (IST)

19.6.4 HCSPARAMS3—Offset Ch

Structural Parameters 3 Register



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

HCSPARAMS3: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 07FF000Ah

31	28	24	20	16	12	8	4	0														
0	0	0	0	0	1	1	1	1	1	1	1	0	0	0	0	0	0	0	1	0	1	0
U2_DEVICE_EXIT_LAT										HCSPARAMS3_RSVD						U1_DEVICE_EXIT_LAT						

Bit Range	Default & Access	Description
31:16	07ffh RO	U2_DEVICE_EXIT_LAT: Reserved.
15:8	0h RO	HCSPARAMS3_RSVD: Reserved.
7:0	0ah RO	U1_DEVICE_EXIT_LAT: Reserved.

19.6.5 HCCPARAMS—Offset 10h

Capability Parameters Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

HCCPARAMS: [BAR] + 10h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0220F04Ch

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																											
0				0				0				0				0				0				1				1				1				1				0				0				0				0																																																																																																																																																																																																																																																																																																																							
XECP																												MAXPSASIZE																												HCCPARAMS_RSVD																												SBD																												FSE																												NSS																												LTC																												LHRC																												PTND																												PPC																												CSZ																												BNC																												AC64																											

Bit Range	Default & Access	Description
31:16	220h RO	XECP: Based on configuration, core automatically updates it



Bit Range	Default & Access	Description
15:12	fh RO	MAXPSASIZE: Maximum Primary Stream Array Size
11:10	0h RO	HCCPARAMS_RSVD: Reserved
9	0h RO	SBD: Secondary Bandwidth Domain Reporting (SBD)
8	0h RO	FSE: For xHCI 0.96, this field is Force Stopped Event (FSE) / For xHCI 1.0, this field is Parse All Event Data (PAE)
7	0h RO	NSS: No Secondary SID Support (NSS). This flag indicates whether the host controller implementation supports Secondary Stream IDs. A 1 in this bit indicates that Secondary Stream ID decoding is not supported. A 0 in this bit indicates that Secondary Stream ID decoding is supported. (refer to Sections 4.12.2 and 6.2.3).
6	1h RO	LTC: Latency Tolerance Messaging Capability (LTC). This flag indicates whether the host controller implementation supports Latency Tolerance Messaging (LTM). A 1 in this bit indicates that LTM is supported. A 0 in this bit indicates that LTM is not supported. Refer to section 4.13.1 for more information on LTM.
5	0h RO	LHRC: Light HC Reset Capability (LHRC). This flag indicates whether the host controller implementation supports a Light Host Controller Reset. A 1 in this bit indicates that Light Host Controller Reset is supported. A 0 in this bit indicates that Light Host Controller Reset is not supported. The value of this flag affects the functionality of the Light Host Controller Reset (LHCRST) flag in the USBCMD register (refer to Section 5.4.1).
4	0h RO	PIND: Port Indicators (PIND). This bit indicates whether the xHC root hub ports support port indicator control. When this bit is a 1, the port status and control registers include a read/writeable field for controlling the state of the port indicator. Refer to Section 5.4.8 for definition of the Port Indicator Control field.
3	1h RO	PPC: Port Power Control (PPC). This flag indicates whether the host controller implementation includes port power control. A 1 in this bit indicates the ports have port power switches. A 0 in this bit indicates the port do not have port power switches. The value of this flag affects the functionality of the PP flag in each port status and control register (refer to Section 5.4.8).
2	1h RO	CSZ: Context Size (CSZ). If this bit is set to 1, then the xHC uses 64 byte Context data structures. If this bit is cleared to 0, then the xHC uses 32 byte Context data structures. Note: This flag does not apply to Stream Contexts.
1	0h RO	BNC: BW Negotiation Capability (BNC). This flag identifies whether the xHC has implemented the Bandwidth Negotiation. Values for this flag have the following interpretation: for Value 0 Description BW Negotiation not implemented. for Value 1 DescriptionBW Negotiation implemented. Refer to section 4.16 of xHCI specification for more information on Bandwidth Negotiation.
0	0h RO	AC64: 64-bit Addressing Capability (AC64). This flag documents the addressing range capability of this implementation. The value of this flag determines whether the xHC has implemented the high order 32 bits of 64 bit register and data structure pointer fields. Values for this flag have the following interpretation: for Value 0 Description 32-bit address memory pointers implemented. for Value 1 description 64-bit address memory pointers implemented. If 32-bit address memory pointers are implemented, the xHC shall ignore the high order 32 bits of 64 bit data structure pointer fields, and system software shall ignore the high order 32 bits of 64 bit xHC registers.

19.6.6 DBOFF—Offset 14h

Doorbell Offset Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DBOFF: [BAR] + 14h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h



Bit Range	Default & Access	Description
9	0h RW	CRS: Controller Restore State: This command is similar to the USB_CMD. CRS bit in host mode and initiates the restore process. When software sets this bit to '1', the controller immediately sets DSTS.RSS to '1'. When the controller has finished the restore process, it sets DSTS.RSS to '0'.
8	0h RW	CSS: Controller Save State: This command is similar to the USB_CMD. CSS bit in host mode and initiates the save process. When software sets this bit to '1', the controller immediately sets DSTS.SSS to '1'. When the controller has finished the save process, it sets DSTS.SSS to '0'.
7	0h RW	LHCRST: Light Host Controller Reset (LHCRST) RO or RW. Optional normative. Default = 0. If the Light HC Reset Capability (LHRC) bit in the HCCPARAMS register is 1, then this flag allows the driver to reset the xHC without affecting the state of the ports. A system software read of this bit as 0 indicates the Light Host Controller Reset has completed and it is safe for software to re-initialize the xHC. A software read of this bit as a 1 indicates the Light Host Controller Reset has not yet completed. If not implemented, a read of this flag shall always return a 0. All registers in the Aux Power well shall maintain the values that had been asserted prior to the Light Host Controller Reset. Refer to section 4.23.1 for more information. When this register is exposed by a Virtual Function (VF), this bit only generates a Light Reset to the xHC instance presented by the selected VF, e.g. Disable the VFs device slots and set the associated VF Run bit to Stopped. Refer to section 8 for more information.
6:4	0h RO	RSVD7: Reserved
3	0h RW	HSEE: Host System Error Enable (HSEE) RW. Default = 0. When this bit is a 1, and the HSE bit in the USBSTS register is a 1, the xHC shall assert out-of-band error signaling to the host. The signaling is acknowledged by software clearing the HSE bit. Refer to section 4.10.2.6 for more information. When this register is exposed by a Virtual Function (VF), the effect of the assertion of this bit on the Physical Function (PF0) is determined by the VMM. Refer to section 8 for more information.
2	0h RW	INTE: Interrupter Enable (INTE) RW. Default = 0. This bit provides system software with a means of enabling or disabling the host system interrupts generated by Interrupters. When this bit is a 1, then Interrupter host system interrupt generation is allowed, e.g. the xHC shall issue an interrupt at the next interrupt threshold if the host system interrupt mechanism (e.g. MSI, MSI-X, etc.) is enabled. The interrupt is acknowledged by a host system interrupt specific mechanism. When this register is exposed by a Virtual Function (VF), this bit only enables the set of Interrupters assigned to the selected VF. Refer to section 7.7.2 for more information.
1	0h RW	HCIRST: Host Controller Reset (HCIRST) RW. Default = 0. This control bit is used by software to reset the host controller. The effects of this bit on the xHC and the Root Hub registers are similar to a Chip Hardware Reset. When software writes a 1 to this bit, the Host Controller resets its internal pipelines, timers, counters, state machines, etc. to their initial value. Any transaction currently in progress on the USB is immediately terminated. A USB reset shall not be driven on USB2 downstream ports, however a Hot or Warm Reset shall be initiated on USB3 Root Hub downstream ports. PCI Configuration registers are not affected by this reset. All operational registers, including port registers and port state machines are set to their initial values. Software shall reinitialize the host controller as described in Section 4.1 in order to return the host controller to an operational state. This bit is cleared to 0 by the Host Controller when the reset process is complete. Software cannot terminate the reset process early by writing a 0 to this bit and shall not write any xHC Operational or Runtime registers until while HCIRST is 1. Note, the completion of the xHC reset process is not gated by the Root Hub port reset process. Software shall not set this bit to 1 when the HCHalted (HCH) bit in the USBSTS register is a 0. Attempting to reset an actively running host controller may result in undefined behavior. When this register is exposed by a Virtual Function (VF), this bit only resets the xHC instance presented by the selected VF. Refer to section 8 for more information.



Bit Range	Default & Access	Description
0	0h RW	R_S: Run/Stop (R/S) RW. Default = 0. 1 = Run. 0 = Stop. When set to a 1, the xHC proceeds with execution of the schedule. The xHC continues execution as long as this bit is set to a 1. When this bit is cleared to 0, the xHC completes any current or queued commands or TDs, and any USB transactions associated with them, then halts. Refer to section 5.4.1.1 for more information on how R/S shall be managed. The xHC shall halt within 16 ms. after software clears the Run/Stop bit if the above conditions have been met. The HCHalted (HCH) bit in the USBSTS register indicates when the xHC has finished its pending pipelined transactions and has entered the stopped state. Software shall not write a 1 to this flag unless the xHC is in the Halted state (i.e. HCH in the USBSTS register is 1). Doing so may yield undefined results. Writing a 0 to this flag when the xHC is in the Running state (i.e. HCH = 0) and any Event Rings are in the Event Ring Full state (refer to section 4.9.4) may result in lost events. When this register is exposed by a Virtual Function (VF), this bit only controls the run state of the xHC instance presented by the selected VF. Refer to section 8 for more information.

19.6.10 USBSTS—Offset 24h

USB Command Register Bit Definitions

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

USBSTS: [BAR] + 24h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000001h

31				28				24				20				16				12				8				4				0																											
0				0				0				0				0				0				0				0				0				1																							
RSVD11																HCE				CNR				SRE				RSS				SSS				RSVD10				PCD				EINT				HSE				RSVD9				HCH			

Bit Range	Default & Access	Description
31:13	0h RO	RSVD11: reserved
12	0h RO	HCE: Host Controller Error (HCE) - RO. Default = 0. 0' = No internal xHC error conditions exist '1' = Internal xHC error condition. This flag shall be set to indicate that an internal error condition has been detected which requires software to reset and reinitialize the xHC. Refer to section 4.24.1 of xhci specification for more information.
11	0h RO	CNR: Controller Not Ready (CNR) - RO. Default = '1'. '0' = Ready '1' = Not Ready. Software shall not write any Doorbell or Operational register of the xHC, other than the USBSTS register, until CNR = '0'. This flag is set by the xHC after a Chip Hardware Reset and cleared when the xHC is ready to begin accepting register writes. This flag shall remain cleared ('0') until the next Chip Hardware Reset.
10	0h RO	SRE: Save/Restore Error (SRE) -RW1C. Default = '0'. If an error occurs during a Save or Restore operation this bit shall be set to '1'. This bit shall be cleared to '0' when a Save or Restore operation is initiated or when written with '1'. Refer to section 4.23.2 of xhci specification for more information.
9	0h RO	RSS: Restore State Status: This bit is similar to the USBSTS.RSS in host mode. When the controller has finished the save process, it will complete the command by setting DSTS.RSS to '0'.
8	0h RO	SSS: Save State Status: This bit is similar to the USBSTS.SSS in host mode. When the controller has finished the save process, it will complete the command by setting DSTS.SSS to '0'



Bit Range	Default & Access	Description
7:5	0h RO	RSVD10: reserved
4	0h RW	PCD: Reserved.
3	0h RO	EINT: Reserved.
2	0h RO	HSE: Reg field HSE
1	0h RO	RSVD9: reserved
0	1h RO	HCH: Reg field HCH

19.6.11 PAGESIZE—Offset 28h

Page Size Register Bit Definitions. This register is used by software to enable or disable the reporting of the reception of specific USB Device Notification Transaction Packets. A Notification Enable (Nx, where x = 0 to 15) flag is defined for each of the 16 possible device notification types. If a flag is set for a specific notification type, a Device Notification Event shall be generated when the respective notification packet is received. After reset all notifications are disabled. Refer to section 6.4.2.7. This register shall be written as a Dword. Byte writes produce undefined results.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PAGESIZE: [BAR] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000001h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RSVD12				PAGE_SIZE				

Bit Range	Default & Access	Description
31:16	0h RO	RSVD12: reserved
15:0	1h RO	PAGE_SIZE: Reg field PAGE_SIZE

19.6.12 DNCTRL—Offset 34h

Device Notification Register Bit Definitions.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

DNCTRL: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD13				NO_N15				

Bit Range	Default & Access	Description
31:16	0h RO	RSVD13: reserved
15:0	0h RW	N0_N15: Reg field N0_N15

19.6.13 CRCR_LO—Offset 38h

Register CRCR_LO

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CRCR LO: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CMD_RING_PNTR								RSVD14
								CRR
								CA
								CS
								RCS

Bit Range	Default & Access	Description
31:6	0h RW	CMD_RING_PNTR: Command Ring Pointer - RW. Default = 0. This field defines high order bits of the initial value of the 64-bit Command Ring Dequeue Pointer. Writes to this field are ignored when Command Ring Running (CRR) = 1. If the CRCR is written while the Command Ring is stopped (CCR = 0), the value of this field shall be used to fetch the first Command TRB the next time the Host Controller Doorbell register is written with the DB Reason field set to Host Controller Command. If the CRCR is not written while the Command Ring is stopped (CCR = 0) then the Command Ring shall begin fetching Command TRBs at the current value of the internal xHC Command Ring Dequeue Pointer. Reading this field always returns 0.
5:4	0h RO	RSVD14: reserved



Bit Range	Default & Access	Description
3	0h RW	CRR: Command Ring Running (CRR) - RO. Default = 0. This flag is set to 1 if the Run/Stop (R/S) bit is 1 and the Host Controller Doorbell register is written with the DB Reason field set to Host Controller Command. It is cleared to 0 when the Command Ring is stopped after writing a 1 to the Command Stop (CS) or Command Abort (CA) flags, or if the R/S bit is cleared to 0.
2	0h RW	CA: Command Abort (CA) - RW1S. Default = 0. Writing a 1 to this bit shall immediately terminate the currently executing command, stop the Command Ring, and generate a Command Completion Event with the Completion Code set to Command Ring Stopped. Refer to section 4.6.1.2 for more information on aborting a command. The next write to the Host Controller Doorbell with DB Reason field set to Host Controller Command shall restart the Command Ring operation. Writes to this flag are ignored by the xHC if Command Ring Running (CRR) = 0. Reading this bit always returns 0.
1	0h RW	CS: Command Stop (CS) - RW1S. Default = 0. Writing a 1 to this bit shall stop the operation of the Command Ring after the completion of the currently executing command, and generate a Command Completion Event with the Completion Code set to Command Ring Stopped and the Command TRB Pointer set to the current value of the Command Ring Dequeue Pointer. Refer to section 4.6.1.1 for more information on stopping a command. The next write to the Host Controller Doorbell with DB Reason field set to Host Controller Command shall restart the Command Ring operation. Writes to this flag are ignored by the xHC if Command Ring Running (CRR) = 0. Reading this bit shall always return 0.
0	0h RW	RCS: Ring Cycle State (RCS) - RW. This bit identifies the value of the xHC Consumer Cycle State (CCS) flag for the TRB referenced by the Command Ring Pointer. Refer to section 4.9.3 for more information. Writes to this flag are ignored if Command Ring Running (CRR) is 1. If the CRCR is written while the Command Ring is stopped (CRR = 0), then the value of this flag shall be used to fetch the first Command TRB the next time the Host Controller Doorbell register is written with the DB Reason field set to Host Controller Command. If the CRCR is not written while the Command Ring is stopped (CRR = 0), then the Command Ring shall begin fetching Command TRBs using the current value of the internal Command Ring CCS flag. Reading this flag always returns 0.

19.6.14 CRCR_HI—Offset 3Ch

Register CRCR_HI

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CRCR_HI: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

CMD_RING_PNTR

Bit Range	Default & Access	Description
31:0	0h RW	CMD_RING_PNTR: Reg field CMD_RING_PNTR



19.6.15 DCBAAP_LO—Offset 50h

Register DCBAAP_LO

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DCBAAP_LO: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DEVICE_CONTEXT_BAAP								RSVD16

Bit Range	Default & Access	Description
31:6	0h RW	DEVICE_CONTEXT_BAAP: Reg field DEVICE_CONTEXT_BAAP
5:0	0h RO	RSVD16: reserved

19.6.16 DCBAAP_HI—Offset 54h

Register DCBAAP_HI

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


DCBAAP_HI: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)


BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DEVICE_CONTEXT_BAAP								



Bit Range	Default & Access	Description
31	0h RW	WPR: Warm Port Reset (WPR) RW1S/RsvdZ. Default = 0. When software writes a 1 to this bit, the Warm Reset sequence as defined in the USB3 Specification is initiated and the PR flag is set to 1. Once initiated, the PR, PRC, and WRC flags shall reflect the progress of the Warm Reset sequence. This flag shall always return 0 when read. Refer to section 4.19.5.1. of XHCI specification. This flag only applies to USB3 protocol ports. For USB2 protocol ports it shall be RsvdZ.
30	0h RW	DR: Device Removable (DR) - RO. This flag indicates if this port has a removable device attached. 1 = Device is non-removable. 0 = Device is removable.
29:28	0h RO	RSVD20: reserved
27	0h RW	WOE: Wake on Over-current Enable (WOE) RWS. Default = 0. Writing this bit to a 1 enables the port to be sensitive to over-current conditions as system wake-up events. Refer to section 4.15 for operational model.
26	0h RW	WDE: Wake on Disconnect Enable (WDE) RWS. Default = 0. Writing this bit to a 1 enables the port to be sensitive to device disconnects as system wake-up events. Refer to section 4.15 for operational model.
25	0h RW	WCE: Wake on Connect Enable (WCE) RWS. Default = 0. Writing this bit to a 1 enables the port to be sensitive to device connects as system wake-up events. Refer to section 4.15 for operational model.
24	0h RO	RSVD19: reserved
23	0h RW	CEC: Port Config Error Change (CEC) RW1CS/RsvdZ. Default = 0. This flag indicates that the port failed to configure its link partner. 0 = No change. 1 = Port Config Error detected. Software shall clear this bit by writing a '1' to it. Refer to section 4.19.2 for more information on change bit usage. Note: This flag is valid only for USB3 protocol ports. For USB2 protocol ports this bit shall be RsvdZ.
22	0h RW	PLC: Port Link State Change (PLC) RW1CS. Default = 0. This flag is set to 1 due to the following PLS transitions mentioned in the XHCI specification
21	0h RW	PRC: Port Reset Change (PRC) RW1CS. Default = 0. This flag is set to 1 due to a '1' to '0' transition of Port Reset (PR). e.g. when any reset processing (Warm or Hot) on this port is complete. Note that this flag shall not be set to 1 if the reset processing was forced to terminate due to software clearing PP or PED to '0'. 0 = No change. 1 = Reset complete. Software shall clear this bit by writing a '1' to it. Refer to section 4.19.5. Refer to section 4.19.2 for more information on change bit usage.
20	0h RW	OCC: Over-current Change (OCC) RW1CS. Default = 0. This bit shall be set to a 1 when there is a 0 to 1 or 1 to 0 transition of Over-current Active (OCA). Software shall clear this bit by writing a 1 to it. Refer to section 4.19.2 for more information on change bit usage.
19	0h RW	WRC: Warm Port Reset Change (WRC) RW1CS/RsvdZ. Default = 0. This bit is set when Warm Reset processing on this port completes. 0 = No change. 1 = Warm Reset complete. Note that this flag shall not be set to 1 if the Warm Reset processing was forced to terminate due to software clearing PP or PED to '0'. Software shall clear this bit by writing a '1' to it. Refer to section 4.19.5.1. Refer to section 4.19.2 for more information on change bit usage. This bit only applies to USB3 protocol ports. For USB2 protocol ports it shall be RsvdZ.
18	0h RW	PEC: Port Enabled/Disabled Change (PEC) RW1CS. Default = 0. 1 = change in PED. 0 = No change. Note that this flag shall not be set if the PED transition was due to software setting PP to 0. Software shall clear this bit by writing a 1 to it. Refer to section 4.19.2 for more information on change bit usage. For a USB2 protocol port, this bit shall be set to 1 only when the port is disabled due to the appropriate conditions existing at the EOF2 point (refer to section 11.8.1 of the USB2 Specification for the definition of a Port Error). For a USB3 protocol port, this bit shall never be set to 1.



Bit Range	Default & Access	Description
17	0h RW	CSC: Connect Status Change (CSC) RW1CS. Default = 0. 1 = Change in CCS. 0 = No change. This flag indicates a change has occurred in the ports Current Connect Status (CCS) or Cold Attach Status (CAS) bits. Note that this flag shall not be set if the CCS transition was due to software setting PP to 0, or the CAS transition was due to software setting WPR to 1. The xHC sets this bit to 1 for all changes to the port device connect status, even if system software has not cleared an existing Connect Status Change. For example, the insertion status changes twice before system software has cleared the changed condition, root hub hardware will be setting an already-set bit (i.e., the bit will remain 1). Software shall clear this bit by writing a 1 to it. Refer to section 4.19.2 for more information on change bit usage.
16	0h RW	LWS: Port Link State Write Strobe (LWS) RW. Default = 0. When this bit is set to 1 on a write reference to this register, this flag enables writes to the PLS field. When 0, write data in PLS field is ignored. Reads to this bit return 0.
15:14	0h RW	PIC: Port Indicator Control (PIC) RWS. Default = 0. Writing to these bits has no effect if the Port Indicators (PIND) bit in the HCCPARAMS register is a 0.
13:10	0h RW	PORTSPEED: Port Speed (Port Speed) ROS. Default = 0. This field identifies the speed of the connected USB Device. This field is only relevant if a device is connected (CCS = 1) in all other cases this field shall indicate Undefined Speed. (more information in the XHCI specification)
9	1h RW	PP: Port Power (PP) RWS. Default = 1. This flag reflects a port's logical, power control state. Because host controllers can implement different methods of port power switching, this flag may or may not represent whether (VBus) power is actually applied to the port. When PP equals a '0' the port is nonfunctional and shall not report attaches, detaches, or Port Link State (PLS) changes. However, the port shall report over-current conditions when PP = 0 if PPC = 0. After modifying PP, software shall read PP and confirm that it is reached its target state before modifying it again, undefined behavior may occur if this procedure is not followed. 0 = This port is in the Powered-off state. 1 = This port is not in the Powered-off state. If the Port Power Control (PPC) flag in the HCCPARAMS register is '1', then xHC has port power control switches and this bit represents the current setting of the switch ('0' = off, '1' = on). If the Port Power Control (PPC) flag in the HCCPARAMS register is '0', then xHC does not have port power control switches and each port is hard wired to power, and not affected by this bit. When an over-current condition is detected on a powered port, the xHC shall transition the PP bit in each affected port from a 1 to 0 (removing power from the port). Note: If this is an SSIC Port, then the DSP Disconnect process is initiated by '1' to '0' transition of PP. Refer to section 5.1.2 in the SSIC Spec for more information. Refer to section 4.19.4 for more information.
8:5	5h RW	PLS: Port Link State (PLS) RWS. Default = RxDetect (5). This field is used to power manage the port and reflects its current link state. When the port is in the Enabled state, system software may set the link U state by writing this field. System software may also write this field to force a Disabled to Disconnected state transition of the port.
4	0h RW	PR: Port Reset (PR) RW1S. Default = 0. 1 = Port Reset signaling is asserted. 0 = Port is not in Reset. When software writes a 1 to this bit generating a 0 to 1 transition, the bus reset sequence is initiated; USB2 protocol ports shall execute the bus reset sequence as defined in the USB2 Spec. USB3 protocol ports shall execute the Hot Reset sequence as defined in the USB3 Spec. PR remains set until reset signaling is completed by the root hub. Note that software shall write a 1 to this flag to transition a USB2 port from the Polling state to the Enabled state. Refer to sections 4.15.2.3 and 4.19.1.1. This flag is 0 if PP is 0.
3	0h RW	OCA: Over-current Active (OCA) RO. Default = 0. 1 = This port currently has an over-current condition. 0 = This port does not have an over-current condition. This bit shall automatically transition from a 1 to a 0 when the over-current condition is removed.
2	0h RO	RSVD18: reserved



Bit Range	Default & Access	Description
1	0h RW	PED: Port Enabled/Disabled (PED) RW1CS. Default = 0. 1 = Enabled. 0 = Disabled. Ports may only be enabled by the xHC. Software cannot enable a port by writing a 1 to this flag. A port may be disabled by software writing a 1 to this flag. This flag shall automatically be cleared to 0 by a disconnect event or other fault condition. Note that the bit status does not change until the port state actually changes. There may be a delay in disabling or enabling a port due to other host controller or bus events. When the port is disabled (PED = 0) downstream propagation of data is blocked on this port, except for reset. For USB2 protocol ports: When the port is in the Disabled state, software shall reset the port (PR = 1) to transition PED to 1 and the port to the Enabled state. For USB3 protocol ports: When the port is in the Polling state (after detecting an attach), the port shall automatically transition to the Enabled state and set PED to 1 upon the completion of successful link training. When the port is in the Disabled state, software shall write a 5 (RxDetect) to the PLS field to transition the port to the Disconnected state. Refer to section 4.19.1.2. PED shall automatically be cleared to 0 when PR is set to 1, and set to 1 when PR transitions from 1 to 0 after a successful reset. Refer to Port Reset (PR) bit for more information on how the PED bit is managed. Note that when software writes this bit to a 1, it shall also write a 0 to the PR bit. This flag is 0 if PP is 0.
0	0h RW	CCS: Current Connect Status (CCS) ROS. Default = 0. 1 = A device is connected to the port. 0 = A device is not connected. This value reflects the current state of the port, and may not correspond directly to the event that caused the Connect Status Change (CSC) bit to be set to 1. Refer to sections 4.19.3 and 4.19.4 for more details on the Connect Status Change (CSC) assertion conditions. This flag is 0 if PP is 0.

19.6.19 PORTPMSC1—Offset 424h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PORTPMSC1: [BAR] + 424h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
PORT_TEST_CONTROL	RSVD21				L1DS	HIRD		L1S
						RWE		

Bit Range	Default & Access	Description
31:28	0h RW	PORT_TEST_CONTROL: reserved
27:16	0h RO	RSVD21: reserved
15:8	0h RW	L1DS: Reg field L1DSLOT



Bit Range	Default & Access	Description
31	0h RW	WPR: Warm Port Reset (WPR) RW1S/RsvdZ. Default = 0. When software writes a 1 to this bit, the Warm Reset sequence as defined in the USB3 Specification is initiated and the PR flag is set to 1. Once initiated, the PR, PRC, and WRC flags shall reflect the progress of the Warm Reset sequence. This flag shall always return 0 when read. Refer to section 4.19.5.1. This flag only applies to USB3 protocol ports. For USB2 protocol ports it shall be RsvdZ.
30	0h RW	DR: Device Removable (DR) - RO. This flag indicates if this port has a removable device attached. 1 = Device is non-removable. 0 = Device is removable.
29:28	0h RO	RSVD25: reserved
27	0h RW	WOE: Wake on Over-current Enable (WOE) RWS. Default = 0. Writing this bit to a 1 enables the port to be sensitive to over-current conditions as system wake-up eventsn. Refer to section 4.15 for operational model.
26	0h RW	WDE: Wake on Disconnect Enable (WDE) RWS. Default = 0. Writing this bit to a 1 enables the port to be sensitive to device disconnects as system wake-up eventsn. Refer to section 4.15 for operational model.
25	0h RW	WCE: Wake on Connect Enable (WCE) RWS. Default = 0. Writing this bit to a 1 enables the port to be sensitive to device connects as system wake-up events . Refer to section 4.15 for operational model.
24	0h RO	RSVD24: reserved
23	0h RW	CEC: Port Config Error Change (CEC) RW1CS/RsvdZ. Default = 0. This flag indicates that the port failed to configure its link partner. 0 = No change. 1 = Port Config Error detected. Software shall clear this bit by writing a '1' to it. Refer to section 4.19.2 of XHCI specification for more information on change bit usage. Note: This flag is valid only for USB3 protocol ports. For USB2 protocol ports this bit shall be RsvdZ.
22	0h RW	PLC: Port Link State Change (PLC) RW1CS. Default = 0. This flag is set to 1 due to the PLS transitions in the XHCI specification
21	0h RW	PRC: Port Reset Change (PRC) RW1CS. Default = 0. This flag is set to 1 due to a '1' to '0' transition of Port Reset (PR). e.g. when any reset processing (Warm or Hot) on this port is complete. Note that this flag shall not be set to 1 if the reset processing was forced to terminate due to software clearing PP or PED to '0'. 0 = No change. 1 = Reset complete. Software shall clear this bit by writing a '1' to it. Refer to section 4.19.5. of XHCI specification. Refer to section 4.19.2 of XHCI specification. for more information on change bit usage.
20	0h RW	OCC: Over-current Change (OCC) RW1CS. Default = 0. This bit shall be set to a 1 when there is a 0 to 1 or 1 to 0 transition of Over-current Active (OCA). Software shall clear this bit by writing a 1 to it. Refer to section 4.19.2 for more information on change bit usage.
19	0h RW	WRC: Warm Port Reset Change (WRC) RW1CS/RsvdZ. Default = 0. This bit is set when Warm Reset processing on this port completes. 0 = No change. 1 = Warm Reset complete. Note that this flag shall not be set to 1 if the Warm Reset processing was forced to terminate due to software clearing PP or PED to '0'. Software shall clear this bit by writing a '1' to it. Refer to section 4.19.5.1. Refer to section 4.19.2 for more information on change bit usage. This bit only applies to USB3 protocol ports. For USB2 protocol ports it shall be RsvdZ.
18	0h RW	PEC: Port Enabled/Disabled Change (PEC) RW1CS. Default = 0. 1 = change in PED. 0 = No change. Note that this flag shall not be set if the PED transition was due to software setting PP to 0. Software shall clear this bit by writing a 1 to it. Refer to section 4.19.2 for more information on change bit usage. For a USB2 protocol port, this bit shall be set to 1 only when the port is disabled due to the appropriate conditions existing at the EOF2 point (refer to section 11.8.1 of the USB2 Specification for the definition of a Port Error). For a USB3 protocol port, this bit shall never be set to 1.



Bit Range	Default & Access	Description
17	0h RW	CSC: Connect Status Change (CSC) RW1CS. Default = 0. 1 = Change in CCS. 0 = No change. This flag indicates a change has occurred in the ports Current Connect Status (CCS) or Cold Attach Status (CAS) bits. Note that this flag shall not be set if the CCS transition was due to software setting PP to 0, or the CAS transition was due to software setting WPR to 1. The xHC sets this bit to 1 for all changes to the port device connect status, even if system software has not cleared an existing Connect Status Change. For example, the insertion status changes twice before system software has cleared the changed condition, root hub hardware will be setting an already-set bit (i.e., the bit will remain 1). Software shall clear this bit by writing a 1 to it. Refer to section 4.19.2 for more information on change bit usage.
16	0h RW	LWS: Port Link State Write Strobe (LWS) RW. Default = 0. When this bit is set to 1 on a write reference to this register, this flag enables writes to the PLS field. When 0, write data in PLS field is ignored. Reads to this bit return 0.
15:14	0h RW	PIC: Port Indicator Control (PIC) RWS. Default = 0. Writing to these bits has no effect if the Port Indicators (PIND) bit in the HCCPARAMS register is a 0
13:10	0h RW	PORTSPEED: Port Speed (Port Speed) ROS. Default = 0. This field identifies the speed of the connected USB Device. This field is only relevant if a device is connected (CCS = 1) in all other cases this field shall indicate Undefined Speed.
9	1h RW	PP: Port Power (PP) RWS. Default = 1. This flag reflects a port's logical, power control state. Because host controllers can implement different methods of port power switching, this flag may or may not represent whether (VBus) power is actually applied to the port. When PP equals a '0' the port is nonfunctional and shall not report attaches, detaches, or Port Link State (PLS) changes. However, the port shall report over-current conditions when PP = 0 if PPC = 0. After modifying PP, software shall read PP and confirm that it is reached its target state before modifying it again, undefined behavior may occur if this procedure is not followed. 0 = This port is in the Powered-off state. 1 = This port is not in the Powered-off state. If the Port Power Control (PPC) flag in the HCCPARAMS register is '1', then xHC has port power control switches and this bit represents the current setting of the switch ('0' = off, '1' = on). If the Port Power Control (PPC) flag in the HCCPARAMS register is '0', then xHC does not have port power control switches and each port is hard wired to power, and not affected by this bit. When an over-current condition is detected on a powered port, the xHC shall transition the PP bit in each affected port from a 1 to 0 (removing power from the port). Note: If this is an SSIC Port, then the DSP Disconnect process is initiated by '1' to '0' transition of PP. Refer to section 5.1.2 in the SSIC Spec for more information. Refer to section 4.19.4 for more information.
8:5	5h RW	PLS: Port Link State (PLS) RWS. Default = RxDetect (5). This field is used to power manage the port and reflects its current link state. When the port is in the Enabled state, system software may set the link U state by writing this field. System software may also write this field to force a Disabled to Disconnected state transition of the port.
4	0h RW	PR: Port Reset (PR) RW1S. Default = 0. 1 = Port Reset signaling is asserted. 0 = Port is not in Reset. When software writes a 1 to this bit generating a 0 to 1 transition, the bus reset sequence is initiated; USB2 protocol ports shall execute the bus reset sequence as defined in the USB2 Spec. USB3 protocol ports shall execute the Hot Reset sequence as defined in the USB3 Spec. PR remains set until reset signaling is completed by the root hub. Note that software shall write a 1 to this flag to transition a USB2 port from the Polling state to the Enabled state. Refer to sections 4.15.2.3 and 4.19.1.1. of XHCI specification. This flag is 0 if PP is 0.
3	0h RW	OCA: Over-current Active (OCA) RO. Default = 0. 1 = This port currently has an over-current condition. 0 = This port does not have an over-current condition. This bit shall automatically transition from a 1 to a 0 when the over-current condition is removed.
2	0h RO	RSVD23: reserved



19.6.24 MFINDEX—Offset 440h

Microframe Index Register Bit Definitions.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MFINDEX: [BAR] + 440h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD27					MICROFRAME_INDEX			

Bit Range	Default & Access	Description
31:14	0h RO	RSVD27: reserved
13:0	0h RO	MICROFRAME_INDEX: Reg field MICROFRAME_INDEX

19.6.25 RsvdZ—Offset 444h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RsvdZ: [BAR] + 444h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD28								

Bit Range	Default & Access	Description
31:0	0h RO	RSVD28: reserved

19.6.26 IMAN—Offset 460h

Interrupter Management Register Bit Definitions.



Bit Range	Default & Access	Description
31:4	0h RW	ERS_TABLE_BAR: Reg field ERS_TABLE_BAR
3:0	0h RO	RSVD32: reserved

19.6.31 ERSTBA_HI—Offset 474h

Default: 00000000h

Register ERDP LO

Type: Memory Mapped I/O Register
(Size: 32 bits)

ERDP_LO: [BAR] + 478h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	0	0
ERD_PNTR									EHB	DESI

19.6.33 ERDP_HI—Offset 47Ch

Register ERDP_HI

Access Method



Bit Range	Default & Access	Description
7:0	0h RW	DB_TARGET: DB Target RW. Doorbell Target. This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. Device Context Doorbells (1-255) for Value 0 the Definition is Reserved for Value 1 the Definition is Control EP 0 Enqueue Pointer Update for Value 2 the Definition is EP 1 OUT Enqueue Pointer Update for Value 3 the Definition is EP 1 IN Enqueue Pointer Update for Value 4 the Definition is EP 2 OUT Enqueue Pointer Update for Value 5 the Definition is EP 2 IN Enqueue Pointer Update . . . for Value 30 the Definition is EP 15 OUT Enqueue Pointer Update for Value 31 the Definition is EP 15 IN Enqueue Pointer Update for Value 32:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined Host Controller Doorbell (0) for Value 0 the Definition is Command Doorbell for Value 1:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined This field returns 0 when read and should be treated as undefined by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0.

19.6.35 DB 1—Offset 484h

The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB 1: [BAR] + 484h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Bit Range	Default & Access	Description
31:16	0h RW	DB_STREAM_ID: DB Stream ID - RW. Doorbell Stream ID. If the endpoint of a Device Context Doorbell defines Streams, then this field shall be used to identify which Stream of the endpoint the doorbell reference is targeting. System software is responsible for ensuring that the value written to this field is valid. If the endpoint defines Streams (MaxPStreams > 0), then 0, 65535 (No Stream) and 65534 (Prime) are reserved Stream ID values and shall not be written to this field. If the endpoint does not define Streams (MaxPStreams = 0) and a non-'0' value is written to this field, the doorbell reference shall be ignored. This field only applies to Device Context Doorbells and shall be cleared to 0 for Host Controller Command Doorbells. This field returns 0 when read.
15:8	0h RO	RSVD33: reserved



Bit Range	Default & Access	Description
7:0	0h RW	DB_TARGET: DB Target RW. Doorbell Target. This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. Device Context Doorbells (1-255) for Value 0 the Definition is Reserved for Value 1 the Definition is Control EP 0 Enqueue Pointer Update for Value 2 the Definition is EP 1 OUT Enqueue Pointer Update for Value 3 the Definition is EP 1 IN Enqueue Pointer Update for Value 4 the Definition is EP 2 OUT Enqueue Pointer Update for Value 5 the Definition is EP 2 IN Enqueue Pointer Update . . . for Value 30 the Definition is EP 15 OUT Enqueue Pointer Update for Value 31 the Definition is EP 15 IN Enqueue Pointer Update for Value 32:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined Host Controller Doorbell (0) for Value 0 the Definition is Command Doorbell for Value 1:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined This field returns 0 when read and should be treated as undefined by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0.

19.6.36 DB 2—Offset 488h

The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB_2: [BAR] + 488h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Bit Range	Default & Access	Description
31:16	0h RW	DB_STREAM_ID: DB Stream ID - RW. Doorbell Stream ID. If the endpoint of a Device Context Doorbell defines Streams, then this field shall be used to identify which Stream of the endpoint the doorbell reference is targeting. System software is responsible for ensuring that the value written to this field is valid. If the endpoint defines Streams (MaxPStreams > 0), then 0, 65535 (No Stream) and 65534 (Prime) are reserved Stream ID values and shall not be written to this field. If the endpoint does not define Streams (MaxPStreams = 0) and a non-'0' value is written to this field, the doorbell reference shall be ignored. This field only applies to Device Context Doorbells and shall be cleared to 0 for Host Controller Command Doorbells. This field returns 0 when read.
15:8	0h RO	RSVD33: reserved



Bit Range	Default & Access	Description
7:0	0h RW	DB_TARGET: DB Target RW. Doorbell Target. This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. Device Context Doorbells (1-255) for Value 0 the Definition is Reserved for Value 1 the Definition is Control EP 0 Enqueue Pointer Update for Value 2 the Definition is EP 1 OUT Enqueue Pointer Update for Value 3 the Definition is EP 1 IN Enqueue Pointer Update for Value 4 the Definition is EP 2 OUT Enqueue Pointer Update for Value 5 the Definition is EP 2 IN Enqueue Pointer Update . . . for Value 30 the Definition is EP 15 OUT Enqueue Pointer Update for Value 31 the Definition is EP 15 IN Enqueue Pointer Update for Value 32:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined Host Controller Doorbell (0) for Value 0 the Definition is Command Doorbell for Value 1:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined This field returns 0 when read and should be treated as undefined by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0.

19.6.37 DB 3—Offset 48Ch

The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB 3: [BAR] + 48Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Bit Range	Default & Access	Description
31:16	0h RW	DB_STREAM_ID: DB Stream ID - RW. Doorbell Stream ID. If the endpoint of a Device Context Doorbell defines Streams, then this field shall be used to identify which Stream of the endpoint the doorbell reference is targeting. System software is responsible for ensuring that the value written to this field is valid. If the endpoint defines Streams (MaxPStreams > 0), then 0, 65535 (No Stream) and 65534 (Prime) are reserved Stream ID values and shall not be written to this field. If the endpoint does not define Streams (MaxPStreams = 0) and a non-'0' value is written to this field, the doorbell reference shall be ignored. This field only applies to Device Context Doorbells and shall be cleared to 0 for Host Controller Command Doorbells. This field returns 0 when read.
15:8	0h RO	RSVD33: reserved



The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB 5: [BAR] + 494h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Intel Atom® Processor E3800 Product Family
Datasheet
2512



Bit Range	Default & Access	Description
7:0	0h RW	DB_TARGET: DB Target RW. Doorbell Target. This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. Device Context Doorbells (1-255) for Value 0 the Definition is Reserved for Value 1 the Definition is Control EP 0 Enqueue Pointer Update for Value 2 the Definition is EP 1 OUT Enqueue Pointer Update for Value 3 the Definition is EP 1 IN Enqueue Pointer Update for Value 4 the Definition is EP 2 OUT Enqueue Pointer Update for Value 5 the Definition is EP 2 IN Enqueue Pointer Update . . . for Value 30 the Definition is EP 15 OUT Enqueue Pointer Update for Value 31 the Definition is EP 15 IN Enqueue Pointer Update for Value 32:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined Host Controller Doorbell (0) for Value 0 the Definition is Command Doorbell for Value 1:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined This field returns 0 when read and should be treated as undefined by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0.

19.6.40 DB 6—Offset 498h

The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB 6: [BAR] + 498h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Bit Range	Default & Access	Description
31:16	0h RW	DB_STREAM_ID: DB Stream ID - RW. Doorbell Stream ID. If the endpoint of a Device Context Doorbell defines Streams, then this field shall be used to identify which Stream of the endpoint the doorbell reference is targeting. System software is responsible for ensuring that the value written to this field is valid. If the endpoint defines Streams (MaxPStreams > 0), then 0, 65535 (No Stream) and 65534 (Prime) are reserved Stream ID values and shall not be written to this field. If the endpoint does not define Streams (MaxPStreams = 0) and a non-'0' value is written to this field, the doorbell reference shall be ignored. This field only applies to Device Context Doorbells and shall be cleared to 0 for Host Controller Command Doorbells. This field returns 0 when read.
15:8	0h RO	RSVD33: reserved



Bit Range	Default & Access	Description
7:0	0h RW	DB_TARGET: DB Target RW. Doorbell Target. This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. Device Context Doorbells (1-255) for Value 0 the Definition is Reserved for Value 1 the Definition is Control EP 0 Enqueue Pointer Update for Value 2 the Definition is EP 1 OUT Enqueue Pointer Update for Value 3 the Definition is EP 1 IN Enqueue Pointer Update for Value 4 the Definition is EP 2 OUT Enqueue Pointer Update for Value 5 the Definition is EP 2 IN Enqueue Pointer Update . . . for Value 30 the Definition is EP 15 OUT Enqueue Pointer Update for Value 31 the Definition is EP 15 IN Enqueue Pointer Update for Value 32:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined Host Controller Doorbell (0) for Value 0 the Definition is Command Doorbell for Value 1:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined This field returns 0 when read and should be treated as undefined by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0.

19.6.41 DB 7—Offset 49Ch

Access Method

DB 7: [BAR] + 49Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Bit Range	Default & Access	Description
31:16	0h RW	DB_STREAM_ID: DB Stream ID - RW. Doorbell Stream ID. If the endpoint of a Device Context Doorbell defines Streams, then this field shall be used to identify which Stream of the endpoint the doorbell reference is targeting. System software is responsible for ensuring that the value written to this field is valid. If the endpoint defines Streams (MaxPStreams > 0), then 0, 65535 (No Stream) and 65534 (Prime) are reserved Stream ID values and shall not be written to this field. If the endpoint does not define Streams (MaxPStreams = 0) and a non-'0' value is written to this field, the doorbell reference shall be ignored. This field only applies to Device Context Doorbells and shall be cleared to 0 for Host Controller Command Doorbells. This field returns 0 when read.
15:8	0h RO	RSVD33: reserved



Bit Range	Default & Access	Description
7:0	0h RW	DB_TARGET: DB Target RW. Doorbell Target. This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. Device Context Doorbells (1-255) for Value 0 the Definition is Reserved for Value 1 the Definition is Control EP 0 Enqueue Pointer Update for Value 2 the Definition is EP 1 OUT Enqueue Pointer Update for Value 3 the Definition is EP 1 IN Enqueue Pointer Update for Value 4 the Definition is EP 2 OUT Enqueue Pointer Update for Value 5 the Definition is EP 2 IN Enqueue Pointer Update . . . for Value 30 the Definition is EP 15 OUT Enqueue Pointer Update for Value 31 the Definition is EP 15 IN Enqueue Pointer Update for Value 32:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined Host Controller Doorbell (0) for Value 0 the Definition is Command Doorbell for Value 1:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined This field returns 0 when read and should be treated as undefined by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0.

19.6.42 DB 8—Offset 4A0h

The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB 8: [BAR] + 4A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Bit Range	Default & Access	Description
31:16	0h RW	DB_STREAM_ID: DB Stream ID - RW. Doorbell Stream ID. If the endpoint of a Device Context Doorbell defines Streams, then this field shall be used to identify which Stream of the endpoint the doorbell reference is targeting. System software is responsible for ensuring that the value written to this field is valid. If the endpoint defines Streams (MaxPStreams > 0), then 0, 65535 (No Stream) and 65534 (Prime) are reserved Stream ID values and shall not be written to this field. If the endpoint does not define Streams (MaxPStreams = 0) and a non-'0' value is written to this field, the doorbell reference shall be ignored. This field only applies to Device Context Doorbells and shall be cleared to 0 for Host Controller Command Doorbells. This field returns 0 when read.
15:8	0h RO	RSVD33: reserved



Access Method

DB 9: [BAR] + 4A4h

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Bit Range	Default & Access	Description
31:16	0h RW	DB_STREAM_ID: DB Stream ID - RW. Doorbell Stream ID. If the endpoint of a Device Context Doorbell defines Streams, then this field shall be used to identify which Stream of the endpoint the doorbell reference is targeting. System software is responsible for ensuring that the value written to this field is valid. If the endpoint defines Streams (MaxPStreams > 0), then 0, 65535 (No Stream) and 65534 (Prime) are reserved Stream ID values and shall not be written to this field. If the endpoint does not define Streams (MaxPStreams = 0) and a non-'0' value is written to this field, the doorbell reference shall be ignored. This field only applies to Device Context Doorbells and shall be cleared to 0 for Host Controller Command Doorbells. This field returns 0 when read.
15:8	0h RO	RSVD33: reserved



Bit Range	Default & Access	Description
7:0	0h RW	DB_TARGET: DB Target RW. Doorbell Target. This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. Device Context Doorbells (1-255) for Value 0 the Definition is Reserved for Value 1 the Definition is Control EP 0 Enqueue Pointer Update for Value 2 the Definition is EP 1 OUT Enqueue Pointer Update for Value 3 the Definition is EP 1 IN Enqueue Pointer Update for Value 4 the Definition is EP 2 OUT Enqueue Pointer Update for Value 5 the Definition is EP 2 IN Enqueue Pointer Update . . . for Value 30 the Definition is EP 15 OUT Enqueue Pointer Update for Value 31 the Definition is EP 15 IN Enqueue Pointer Update for Value 32:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined Host Controller Doorbell (0) for Value 0 the Definition is Command Doorbell for Value 1:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined This field returns 0 when read and should be treated as undefined by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0.

19.6.45 DB_11—Offset 4ACh

The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB_11: [BAR] + 4ACh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID					RSVD33		DB_TARGET	

Bit Range	Default & Access	Description
31:16	0h RW	DB_STREAM_ID: DB Stream ID - RW. Doorbell Stream ID. If the endpoint of a Device Context Doorbell defines Streams, then this field shall be used to identify which Stream of the endpoint the doorbell reference is targeting. System software is responsible for ensuring that the value written to this field is valid. If the endpoint defines Streams (MaxPStreams > 0), then 0, 65535 (No Stream) and 65534 (Prime) are reserved Stream ID values and shall not be written to this field. If the endpoint does not define Streams (MaxPStreams = 0) and a non-'0' value is written to this field, the doorbell reference shall be ignored. This field only applies to Device Context Doorbells and shall be cleared to 0 for Host Controller Command Doorbells. This field returns 0 when read.
15:8	0h RO	RSVD33: reserved



The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB 13: [BAR] + 4B4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Intel Atom® Processor E3800 Product Family
Datasheet
2520

19.6.48 DB_14—Offset 4B8h



The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB 15: [BAR] + 4BCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Intel Atom® Processor E3800 Product Family
Datasheet
2522



Bit Range	Default & Access	Description
7:0	0h RW	DB_TARGET: DB Target RW. Doorbell Target. This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. Device Context Doorbells (1-255) for Value 0 the Definition is Reserved for Value 1 the Definition is Control EP 0 Enqueue Pointer Update for Value 2 the Definition is EP 1 OUT Enqueue Pointer Update for Value 3 the Definition is EP 1 IN Enqueue Pointer Update for Value 4 the Definition is EP 2 OUT Enqueue Pointer Update for Value 5 the Definition is EP 2 IN Enqueue Pointer Update . . . for Value 30 the Definition is EP 15 OUT Enqueue Pointer Update for Value 31 the Definition is EP 15 IN Enqueue Pointer Update for Value 32:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined Host Controller Doorbell (0) for Value 0 the Definition is Command Doorbell for Value 1:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined This field returns 0 when read and should be treated as undefined by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0.

19.6.50 DB 16—Offset 4C0h

The Doorbell Array is organized as an array of up to 256 Doorbell Registers. One 32-bit Doorbell Register is defined in the array for each Device Slot. System software utilizes the Doorbell Register to notify the xHC that it has Device Slot related work for the xHC to perform.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DB 16: [BAR] + 4C0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DB_STREAM_ID				RSVD33				DB_TARGET

Bit Range	Default & Access	Description
31:16	0h RW	DB_STREAM_ID: DB Stream ID - RW. Doorbell Stream ID. If the endpoint of a Device Context Doorbell defines Streams, then this field shall be used to identify which Stream of the endpoint the doorbell reference is targeting. System software is responsible for ensuring that the value written to this field is valid. If the endpoint defines Streams (MaxPStreams > 0), then 0, 65535 (No Stream) and 65534 (Prime) are reserved Stream ID values and shall not be written to this field. If the endpoint does not define Streams (MaxPStreams = 0) and a non-'0' value is written to this field, the doorbell reference shall be ignored. This field only applies to Device Context Doorbells and shall be cleared to 0 for Host Controller Command Doorbells. This field returns 0 when read.
15:8	0h RO	RSVD33: reserved



Bit Range	Default & Access	Description
7:0	0h RW	DB_TARGET: DB Target RW. Doorbell Target. This field defines the target of the doorbell reference. The table below defines the xHC notification that is generated by ringing the doorbell. Note that Doorbell Register 0 is dedicated to Command Ring and decodes this field differently than the other Doorbell Registers. Device Context Doorbells (1-255) for Value 0 the Definition is Reserved for Value 1 the Definition is Control EP 0 Enqueue Pointer Update for Value 2 the Definition is EP 1 OUT Enqueue Pointer Update for Value 3 the Definition is EP 1 IN Enqueue Pointer Update for Value 4 the Definition is EP 2 OUT Enqueue Pointer Update for Value 5 the Definition is EP 2 IN Enqueue Pointer Update . . . for Value 30 the Definition is EP 15 OUT Enqueue Pointer Update for Value 31 the Definition is EP 15 IN Enqueue Pointer Update for Value 32:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined Host Controller Doorbell (0) for Value 0 the Definition is Command Doorbell for Value 1:247 the Definition is Reserved for Value 248:255 the Definition is Vendor Defined This field returns 0 when read and should be treated as undefined by software. When the Command Doorbell is written, the DB Stream ID field shall be cleared to 0.

19.6.51 USBLEGSUP—Offset 880h

The USBLEGSUP capability requires support for Byte accesses for Semaphore address, refer to section 7.1.of xhci specification. usb legacy support capability DW

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

USBLEGSUP: [BAR] + 880h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000401h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
RSVD35		HC_OS_OWNED	RSVD34		HC_BIOS_OWNED	NEXT_CAPABILITY_POINTER		CAPABILITY_ID

Bit Range	Default & Access	Description
31:25	0h RO	RSVD35: reserved
24	0h RW	HC_OS_OWNED: Reg field HC_OS_OWNED SEMAPHORE
23:17	0h RO	RSVD34: reserved
16	0h RW	HC_BIOS_OWNED: Reg field HC_BIOS_OWNED SEMAPHORE
15:8	04h RO	NEXT_CAPABILITY_POINTER: Reg field NEXT_CAPABILITY_POINTER



Bit Range	Default & Access	Description
7:0	01h RO	CAPABILITY_ID: Reg field CAPABILITY_ID

19.6.52 USBLEGCTLSTS—Offset 884h

usb legacy support capability DW

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

USBLEGCTLSTS: [BAR] + 884h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0															
0				0				0				0				0				0				0				0				0															
SMI_ON_BAR				RSVD39				SMI_ON_HOST				RSVD38				SMI_ON_EVENT				SMI_ON_BAR_E				SMI_ON_PCI_E				SMI_ON_OS_E				RSVD37				SMI_ON_HOST_E				RSVD36				USB_SMI_ENABLE			
SMI_ON_PCI																																															
SMI_ON_OS																																															

Bit Range	Default & Access	Description
31	0h RO	SMI_ON_BAR: Reg field SMI_ON_BAR
30	0h RO	SMI_ON_PCI: Reg field SMI_ON_PCI COMMAND
29	0h RO	SMI_ON_OS: Reg field SMI_ON_OS OWNERSHIP CHANGE
28:21	0h RO	RSVD39: reserved
20	0h RO	SMI_ON_HOST: Reg field SMI_ON_HOST SYSTEM ERROR
19:17	0h RO	RSVD38: reserved
16	0h RO	SMI_ON_EVENT: Reg field SMI_ON_EVENT INTERRUPT
15	0h RW	SMI_ON_BAR_E: Reg field SMI_ON_BAR ENABLE
14	0h RW	SMI_ON_PCI_E: Reg field SMI_ON_PCI COMMAND ENABLE
13	0h RW	SMI_ON_OS_E: Reg field SMI_ON_OS OWNERSHIP ENABLE
12:5	0h RO	RSVD37: Reserved



flag Value After Reset: 0x0 Register SUPTPRT3 DW0

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
2528



Type: Memory Mapped I/O Register
(Size: 32 bits)

GRXTHRCFG: [BAR] + C10Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 22800000h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	1	0	0
0	0	0	1	0	1	0	0	0
GRXTHRCFG_RSVD3	USBRXPkTCNTSEL	GRXTHRCFG_RSVD2	USBRXPkTCNT	USBMAXRXBURSTSIZE		GRXTHRCFG_RSVD1		

Bit Range	Default & Access	Description
31:30	0h RO	GRXTHRCFG_RSVD3: Reserved
29	1h RW	USBRXPkTCNTSEL: USB ReceivePacket Count Enable: This field enables/disables the USB reception multi-packet thresholding: n 0: The core can only start reception on the USB when the RX FIFO has space for at least one packet. n 1: The core can only start reception on the USB when the RX FIFO has space for at least USBRxPktCnt amount of packets. This mode is only valid in the host mode. It is only used for SuperSpeed.
28	0h RO	GRXTHRCFG_RSVD2: Reserved
27:24	2h RW	USBRXPkTCNT: USB Receive Packet Count: This field specifies space (in number of packets) that must be available in the RX FIFO before the core can start the corresponding USB RX transaction (burst). This field is only valid when the USB Receive Packet Count Enable field is set to one. The valid values are from 1 to 15.
23:19	10h RW	USBMAXRXBURSTSIZE: USB Maximum Receive Burst Size: This field is only valid when USBRxPktCntSel is one. This field specifies the Maximum Bulk IN burst the core should do. When the system bus is slower than the USB, RX FIFO can overrun during a long burst. User can program a smaller value to this field to limit the RX burst size that the core can do. It only applies to SS Bulk, Isochronous, and Interrupt IN endpoints in the host mode. Valid values are from 1 to 16.
18:0	0h RO	GRXTHRCFG_RSVD1: Reserved

19.6.63 GCTL—Offset C110h

Global Common Register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

GCTL: [BAR] + C110h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 45803000h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
1	0h RW	GBLHIBERNATIONEN: This bit enables hibernation at the global level. If hibernation is not enabled via this bit, the PMU immediately accepts the D0-)D3 and D3-)D0 power state change requests, but does not save or restore any core state. In addition, the PMUs will never drive the PHY interfaces and let the core continue to drive the PHY interfaces.
0	0h RW	DSBLCLKGTNG: Disable Clock Gating

19.6.64 GSTS—Offset C118h

Global Status Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GSTS: [BAR] + C118h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 3E800002h

31		28				24				20				16				12				8				4				0	
0	0	1	1	1	1	1	1	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	
CBELT												RSVD7								OTG_IP	BC_IP	ADP_IP	Host_IP	Device_IP	CSRTIMEOUT	BUSERRADDRVLD	R6	CURMOD			

Bit Range	Default & Access	Description
31:20	3e8h RO	CBELT: Current BELT Value: In Host mode, this field indicates the minimum value of all received device BELT values and the BELT value that is set by the Set Latency Tolerance Value command.
19:11	0h RO	RSVD7: reserved
10	0h RO	OTG_IP: OTG Interrupt Pending: This field indicates that there is a pending interrupt pertaining to OTG in OEVT register.
9	0h RO	BC_IP: Battery Charger Interrupt Pending: This field indicates that there is a pending interrupt pertaining to BC in BCEVT register.
8	0h RO	ADP_IP: ADP Interrupt Pending: This field indicates that there is a pending interrupt pertaining to ADP in ADPEVT register.
7	0h RO	Host_IP: Host Interrupt Pending: This field indicates that there is a pending interrupt pertaining to xHC in the Host event queue.
6	0h RO	Device_IP: Device Interrupt Pending: This field indicates that there is a pending interrupt pertaining to peripheral (device) operation in the Device event queue.
5	0h RO	CSRTIMEOUT: CSR Timeout: When this bit is 1'b1, it indicates that software performed a write or read to a core register that could not be completed within DWC_USB3_CSR_ACCESS_TIMEOUT bus clock cycles (default: 65535).
4	0h RO	BUSERRADDRVLD: Bus Error Address Valid



Bit Range	Default & Access	Description
3:2	0h RO	R6: Reg field R6
1:0	2h RO	CURMOD: Reg field CURMOD

19.6.65 GSNPSID—Offset C120h

flag Value After Reset: 0x5533210a Global Synopsys ID Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GSNPSID: [BAR] + C120h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 5533192Ah

31	28	24	20	16	12	8	4	0
0	1	0	1	0	1	0	1	0
0	1	0	1	0	0	1	1	0
0	0	1	1	0	0	1	1	0
0	0	0	1	1	0	0	0	1
1	0	0	1	0	0	1	0	0
1	0	1	0	1	0	1	0	1
0	1	0	1	0	1	0	1	0

SYNOPSISID

Bit Range	Default & Access	Description
31:0	5533192ah RO	SYNOPSISID: flag Value After Reset: 0x5533210a Reg field SYNOPSISID

19.6.66 GGPIO—Offset C124h

Global General Purpose Input/Output Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GGPIO: [BAR] + C124h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

GPO

GPI

Bit Range	Default & Access	Description
31:16	0h RW	GPO: General Purpose Output: This field's value is driven out on the gp_o[15:0] core output port.



Bit Range	Default & Access	Description
15:0	0h RO	GPI: General Purpose Input: This field's read value reflects the gp_i[15:0] core input value.

19.6.67 GUID—Offset C128h

flag Value After Reset: 0x8086a0 Global User ID Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GUID: [BAR] + C128h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 12345678h

31	28	24	20	16	12	8	4	0								
0	0	0	1	0	0	1	0	0	0	1	1	1	1	0	0	0
USERID																

Bit Range	Default & Access	Description
31:0	12345678h RW	USERID: flag Value After Reset: 0x8086a0 Reg field USERID

19.6.68 GUCTL—Offset C12Ch

flag Value After Reset: 0x200ce00 Global User Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


GUCTL: [BAR] + C12Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 7FC0C600h

31				28				24				20				16				12				8				4				0																															
0				1				1				1				1				1				1				1				0																															
MAC3FLADJ																NOEXTRDL				PSQEXTRESSP				SPRSCTRLTRANSEN				RESBWHSEPS				CMDEVADDR				USBHSTINAUTORETRYEN				GUCTL_RSVD1				DTCT				DTFT															



Bit Range	Default & Access	Description
31:22	1ffh RW	MAC3FLADJ:
21	0h RW	NOEXTRDL:
20:18	0h RW	PSQEXTRRESSP:
17	0h RW	SPRSCTRLTRANSEN: Sparse Control Transaction Enable: Some devices are slow in responding to Control transfers. Scheduling multiple transactions in one microframe/frame can cause these devices to misbehave. If this bit is set to 1'b1, the host controller schedules transactions for a Control transfer in different microframes/frames.
16	0h RW	RESBWHSEPS: Reserving 85% Bandwidth for HS Periodic EPs
15	1h RW	CMDEVADDR: Compliance Mode for Device Address: When this bit is 1'b1, Slot ID may have different value than Device Address if max_slot_enabled (128. n 1'b1: Increment Device Address on each Address Device command. n 1'b0: Device Address is equal to Slot ID. The xHCI compliance requires this bit to be set to 1'. The 0' mode is for debug purpose only. This all ows you to easily identify a device connected to a port in the Lecroy or Eliisys trace during hardware debug. This bit is valid in Host and DRD configuration and is used in host mode operation only. Ignore this bit in device mode.
14	1h RW	USBHSTINAUTORETRYEN: Host IN Auto Retry: When set, this field enables the Auto Retry feature. For IN transfers (non-isochronous) that encounter data packets with CRC errors or internal overrun scenarios, the auto retry feature causes the Host core to reply to the device with a non-terminating retry ACK (that is, an ACK transaction packet with Retry = 1 and NumP != 0). If the Auto Retry feature is disabled (default), the core will respond with a terminating retry ACK (that is, an ACK transaction packet with Retry = 1 and NumP = 0). n 1'b0: Auto Retry Disabled n 1'b1: Auto Retry Enabled In device mode this bit should be 0
13:11	0h RO	GUCTL_RSVD1:
10:9	3h RW	DTCT: Device Timeout Coarse Tuning: This field is a Host mode parameter which determines how long the host waits for a response from device before considering a timeout. The core first checks the DTCT value. If it is 0, then the timeout value is defined by the DTFT. If it is non-zero, then it uses the following timeout values: n 2'b00: 0 usec -) use DTFT value instead n 2'b01: 500 usec n 2'b10: 1.5 msec n 2'b11: 6.5 msec
8:0	0h RW	DTFT: Device Timeout Fine Tuning: This field is a Host mode parameter which determines how long the host waits for a response from device before considering a timeout. For DTFT field to take effect, DTCT must be set to 2'b00. The DTFT value is the number of 125 MHz clocks * 256 to count before considering a device timeout. For the 125 MHz clk (8 ns period), this is calculated as follows: (DTFT value) * 256 * (8 ns) Quick Reference: n if DTFT = 0x2, 2*256*8 = 4usec timeout n if DTFT = 0x5, 5*256*8 = 10usec timeout n if DTFT = 0xA, 10*256*8 = 20usec timeout n if DTFT = 0x10, 16*256*8 = 32usec timeout n if DTFT = 0x19, 25*256*8 = 51usec timeout n if DTFT = 0x31, 49*256*8 = 100usec timeout n if DTFT = 0x62, 98*256*8 = 200usec timeout

19.6.69 GBUSERRADDRLO—Offset C130h

Register GBUSERRADDRLO

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

GBUSERRADDRLO: [BAR] + C130h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BUSERRADDR								



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BINUM8	BINUM7	BINUM6	BINUM5	BINUM4	BINUM3	BINUM2	BINUM1	

Bit Range	Default & Access	Description
31:28	0h RO	BINUM8: Reg field BINUM8
27:24	0h RO	BINUM7: Reg field BINUM7
23:20	0h RO	BINUM6: Reg field BINUM6
19:16	0h RO	BINUM5: Reg field BINUM5
15:12	0h RO	BINUM4: Reg field BINUM4
11:8	0h RO	BINUM3: Reg field BINUM3
7:4	0h RO	BINUM2: Reg field BINUM2
3:0	0h RW	BINUM1: flag Value After Reset: 0x1 Reg field BINUM1

19.6.72 GPRTBIMAPHI—Offset C13Ch

Register R

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GPRTBIMAPHI: [BAR] + C13Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd16	BINUM15	BINUM14	BINUM13	BINUM12	BINUM11	BINUM10	BINUM9	

Bit Range	Default & Access	Description
31:28	0h RO	Rsvd16: reserved
27:24	0h RO	BINUM15: Reg field BINUM15



Bit Range	Default & Access	Description
23:20	0h RO	BINUM14: Reg field BINUM14
19:16	0h RO	BINUM13: Reg field BINUM13
15:12	0h RO	BINUM12: Reg field BINUM12
11:8	0h RO	BINUM11: Reg field BINUM11
7:4	0h RO	BINUM10: Reg field BINUM10
3:0	0h RO	BINUM9: Reg field BINUM9

19.6.73 GHWPARAMS0—Offset C140h

Global Hardware Parameters Register 0

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GHWPARAMS0: [BAR] + C140h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 2020400Ah

31				28				24				20				16				12				8				4				0			
0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	1	0	1	0			
DWC_USB3_AWIDTH								DWC_USB3_SDWIDTH								DWC_USB3_MDWIDTH								DWC_USB3_SBUS_TYPE				DWC_USB3_MBUS_TYPE				DWC_USB3_MODE			

Bit Range	Default & Access	Description
31:24	20h RO	DWC_USB3_AWIDTH:
23:16	20h RO	DWC_USB3_SDWIDTH:
15:8	40h RO	DWC_USB3_MDWIDTH:
7:6	0h RO	DWC_USB3_SBUS_TYPE:
5:3	1h RO	DWC_USB3_MBUS_TYPE:



Bit Range	Default & Access	Description
22:21	3h RO	DWC_USB3_NUM_RAMs:
20:15	01h RO	DWC_USB3_DEVICE_NUM_INT:
14:12	4h RO	DWC_USB3_ASPACEWIDTH: Reserved.
11:9	4h RO	DWC_USB3_REQINFOWIDTH:
8:6	4h RO	DWC_USB3_DATAINFOWIDTH:
5:3	7h RO	DWC_USB3_BURSTWIDTH:
2:0	3h RO	DWC_USB3_IDWIDTH:

19.6.75 GHWPARAMS2—Offset C148h

Global Hardware Parameters Register 2

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GHWPARAMS2: [BAR] + C148h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 008086A0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DWC_USB3_USERID

Bit Range	Default & Access	Description
31:0	008086a0h RO	DWC_USB3_USERID:

19.6.76 GHWPARAMS3—Offset C14Ch

Global Hardware Parameters Register 3

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

GHWPARAMS3: [BAR] + C14Ch


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 10420089h

31	28	24	20	16	12	8	4	0
0	0	0	1	0	0	0	0	0
0	0	0	0	0	1	0	0	0
0	1	0	0	0	0	1	0	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
1	0	0	0	1	0	0	0	1
1	0	0	0	1	0	0	0	1

Bit Range	Default & Access	Description
31	0h RO	GHWPARAMS3_RSVD2:
30:23	20h RO	DWC_USB3_CACHE_TOTAL_XFER_RESOURCES:
22:18	10h RO	DWC_USB3_NUM_IN_EPS:
17:12	20h RO	DWC_USB3_NUM_EPS:
11	0h RO	DWC_USB3_ULPI_CARKIT:
10	0h RO	DWC_USB3_VENDOR_CTL_INTERFACE:
9:8	0h RO	GHWPARAMS3_RSVD1:
7:6	2h RO	DWC_USB3_HSPHY_DWIDTH:
5:4	0h RO	DWC_USB3_FSPHY_INTERFACE:
3:2	2h RO	DWC_USB3_HSPHY_INTERFACE:
1:0	1h RO	DWC_USB3_SSPHY_INTERFACE:



Bit Range	Default & Access	Description
31:16	0c00h RO	DWC_USB3_RAM0_DEPTH:
15	1h RO	DWC_USB3_EN_BUS_FILTERS:
14	0h RO	DWC_USB3_EN_BC:
13	1h RO	OTG_SS_Support: Reg field CORECONSULTANT
12	0h RO	ADPSupport: DWC_USB3_EN_ADP:
11	1h RO	HNPSupport: RSP/HNP Support Enabled: The application uses this bit to determine the DWC_usb3 core's RSP/HNP support. If DWC_USB3_EN_OTG=2, n 1'b0: RSP and HNP support is not enabled. The only exception for this rule is for SSPC-OTG devices where RSP support is not enabled, but HNP support is enabled. (Refer OCFG.SSPC-OTG bit) n 1'b1: RSP and HNP support is enabled If DWC_USB3_EN_OTG=1, n 1'b0: HNP support is not enabled n 1'b1: HNP support is enabled This bit is enabled only if HNP mode was specified for HNP Mode of Operation in coreConsultant (parameter DWC_USB3_EN_OTG is not 0, and DWC_USB3_MODE is DRD). Other wise, it reads 0.
10	1h RO	SRPSupport: SRP Support Enabled: The application uses this bit to determine the DWC_usb3 core's SRP support. n1'b0: SRP support is not enabled n 1'b1: SRP support is enabled This bit is 1'b1 when the parameter DWC_USB3_EN_OTG is not 0.
9:8	0h RO	ghwparams6_9_8: Reg field CORECONSULTANT
7	0h RO	DWC_USB3_EN_FPGA:
6	0h RO	GHWPARAMS6_RSVD:
5:0	20h RO	DWC_USB3_PSQ_FIFO_DEPTH:

Global Hardware Parameters Register 7

Access Method



Default: 038807E6h

[illegible]

Bit Range	Default & Access	Description
31:16	0388h RO	DWC_USB3_RAM2_DEPTH:
15:0	07e6h RO	DWC_USB3_RAM1_DEPTH:

19.6.81 GDBGFIFOSPACE—Offset C160h

flag Value After Reset: 0x820000 Global Debug Queue/FIFO Space Available Register

Access Method

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00420000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SPACE_AVAILABLE				RSVD8				FIFO_QUEUE_SELECT

Bit Range	Default & Access	Description
31:16	42h RO	SPACE_AVAILABLE: Reg field SPACE_AVAILABLE



Bit Range	Default & Access	Description
13:11	0h RO	LTDBPhyCmdState: LTSSM PHY command State: n 000: PHY_IDLE (PHY command state is in IDLE. No PHY request pending) n 001: PHY_DET (Request to start Receiver detection) n 010: PHY_DET_3 (Wait for Phy_Status (Receiver detection)) n 011: PHY_PWR_DLY (Delay Pipe3_PowerDown P0 -) P1/P2/P3 request) n 100: PHY_PWR_A (Delay for internal logic) n 101: PHY_PWR_B (Wait for Phy_Status(Power state change request))
10:9	2h RO	POWERDOWN: flag Value After Reset: 0x0 Reg field POWERDOWN
8	0h RO	RXEQTRAIN: RxEq Train
7:6	1h RO	TXDEEMPHASIS: flag Value After Reset: 0x0 Reg field TXDEEMPHASIS
5:3	0h RO	LTDBClkState: LTSSM Clock State: n 000: CLK_NORM (PHY is in non-P3 state and PCLK is running) n 001: CLK_TO_P3 (P3 entry request to PHY) n 010: CLK_WAIT1 (Wait for Phy_Status (P3 request)) n 011: CLK_P3 (PHY is in P3 and PCLK is not running) n 100: CLK_TO_P0 (P3 exit request to PHY) n 101: CLK_WAIT2 (Wait for Phy_Status (P3 exit request))
2	0h RO	TXSWING: Tx Swing
1	0h RO	RXTERMINATION: Rx Termination
0	0h RO	TXONESZEROS: Tx Ones/Zeros

19.6.83 GPRTBIMAP_HSLO—Offset C180h

High Speed port to bus instance mapping

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GPRTBIMAP_HSLO: [BAR] + C180h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BINUM8	BINUM7	BINUM6	BINUM5	BINUM4	BINUM3	BINUM2	BINUM1	

Bit Range	Default & Access	Description
31:28	0h RO	BINUM8: Reg field BINUM8
27:24	0h RO	BINUM7: Reg field BINUM7
23:20	0h RO	BINUM6: Reg field BINUM6



Bit Range	Default & Access	Description
19:16	0h RO	BINUM5: Reg field BINUM5
15:12	0h RO	BINUM4: Reg field BINUM4
11:8	0h RO	BINUM3: Reg field BINUM3
7:4	0h RO	BINUM2: Reg field BINUM2
3:0	0h RW	BINUM1: flag Value After Reset: 0x1 Reg field BINUM1

19.6.84 GPRTBIMAP_HSHI—Offset C184h

High Speed port to bus instance mapping

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GPRTBIMAP_HSHI: [BAR] + C184h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd16	BINUM15	BINUM14	BINUM13	BINUM12	BINUM11	BINUM10	BINUM9	

Bit Range	Default & Access	Description
31:28	0h RO	Rsvd16: reserved
27:24	0h RO	BINUM15: Reg field BINUM15
23:20	0h RO	BINUM14: Reg field BINUM14
19:16	0h RO	BINUM13: Reg field BINUM13
15:12	0h RO	BINUM12: Reg field BINUM12
11:8	0h RO	BINUM11: Reg field BINUM11
7:4	0h RO	BINUM10: Reg field BINUM10
3:0	0h RO	BINUM9: Reg field BINUM9



19.6.85 GPRTBIMAP_FSLO—Offset C188h

Register Full Speed port to bus instance mapping

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GPRTBIMAP_FSLO: [BAR] + C188h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BINUM8	BINUM7	BINUM6	BINUM5	BINUM4	BINUM3	BINUM2	BINUM1	

Bit Range	Default & Access	Description
31:28	0h RO	BINUM8: Reg field BINUM8
27:24	0h RO	BINUM7: Reg field BINUM7
23:20	0h RO	BINUM6: Reg field BINUM6
19:16	0h RO	BINUM5: Reg field BINUM5
15:12	0h RO	BINUM4: Reg field BINUM4
11:8	0h RO	BINUM3: Reg field BINUM3
7:4	0h RO	BINUM2: Reg field BINUM2
3:0	0h RW	BINUM1: flag Value After Reset: 0x1 Reg field BINUM1

19.6.86 GPRTBIMAP_FSHI—Offset C18Ch

Register Full Speed port to bus instance mapping

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GPRTBIMAP_FSHI: [BAR] + C18Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Rsvd16	BINUM15	BINUM14	BINUM13	BINUM12	BINUM11	BINUM10	BINUM9	

Bit Range	Default & Access	Description
31:28	0h RO	Rsvd16: reserved
27:24	0h RO	BINUM15: Reg field BINUM15
23:20	0h RO	BINUM14: Reg field BINUM14
19:16	0h RO	BINUM13: Reg field BINUM13
15:12	0h RO	BINUM12: Reg field BINUM12
11:8	0h RO	BINUM11: Reg field BINUM11
7:4	0h RO	BINUM10: Reg field BINUM10
3:0	0h RO	BINUM9: Reg field BINUM9

19.6.87 GUSB2PHYCFG—Offset C200h

Register Rs

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GUSB2PHYCFG: [BAR] + C200h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000A410h

31		28				24				20				16				12				8				4				0																																													
0		0		0		0		0		0		0		0		1		0		1		0		0		0		0		0																																													
PHYSOFTST		GUSB2PHYCFG_RSVD3																														ULPIEXTVBUSINDIACTOR	ULPIEXTVBUSDRV	ULPICLKSUM	ULPIAUTORES	GUSB2PHYCFG_RSVD2	USBTRDTIM																															GUSB2PHYCFG_RSVD1	ENBLSLPM	PHYSEL	SUSPENDUSB20	FSINTF	ULPI_UTMI_Sel	PHYIF	TOUTCALIB



Bit Range	Default & Access	Description
31	0h RW	PHYSOFTTRST: Reg field PHYSOFTTRST <i>Note:</i> A register value of 0 will asserts the reset otherwise a register value of 1 will de-assert
30:19	0h RO	GUSB2PHYCFG_RSVD3:
18	0h RW	ULPIEXTVBUSINDIACTOR: Reg field ULPIEXTVBUSINDIACTOR
17	0h RW	ULPIEXTVBUSDRV: Reg field ULPIEXTVBUSDRV
16	0h RW	ULPICKLSUSM: Reg field ULPICKLSUSM
15	1h RW	ULPIAUTORES: flag Value After Reset: 0x0 Reg field ULPIAUTORES
14	0h RO	GUSB2PHYCFG_RSVD2:
13:10	9h RW	USBTRDTIM: Reg field USBTRDTIM
9	0h RO	GUSB2PHYCFG_RSVD1:
8	0h RW	ENBLSLPM: Reg field ENBLSLPM
7	0h WO	PHYSEL: Reg field PHYSEL
6	0h RW	SUSPENDUSB20: SUSPENDUSB20
5	0h RO	FSINTF: Reg field FSINTF
4	1h RO	ULPI_UTMI_Sel: flag Value After Reset: 0x0 ULPI or UTMI+ Select: The application uses this bit to select a UTMI+ or ULPI Interface. n 1'b0: UTMI+ Interface n 1'b1: ULPI Interface This bit is writable only if UTMI+ and ULPI is specified for High-Speed PHY Interface(s) in coreConsultant configuration (DWC_USB3_HSPHY_INTERFACE = 3). Otherwise, this bit is Read Only and the value depends on the interface selected through DWC_USB3_HSPHY_INTERFACE.
3	0h RW	PHYIF: Reg field PHYIF
2:0	0h RW	TOUTCALIB:

19.6.88 GUSB2I2CCTL—Offset C240h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GUSB2I2CCTL: [BAR] + C240h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD	BSYDNE	ACK	RW	I2CDATSE0	I2CDEVADR	I2CSUSPCTL	I2CEN	ADDR
								REGADDR
								RWDATA

Bit Range	Default & Access	Description
31	0h RW	RSVD:
30	0h RW	BSYDNE: Reg field BSYDNE
29	0h RO	ACK:
28	0h RW	RW:
27	0h RW	I2CDATSE0: Reg field I2CDATSE0
26:25	0h RW	I2CDEVADR: Reg field I2CDEVADR
24	0h RW	I2CSUSPCTL: Reg field I2CSUSPCTL
23	0h RW	I2CEN: Reg field I2CEN
22:16	0h RW	ADDR: Reg field ADDR
15:8	0h RW	REGADDR: Reg field REGADDR
7:0	0h RW	RWDATA: Reg field RWDATA

19.6.89 GUSB2PHYACC—Offset C280h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GUSB2PHYACC: [BAR] + C280h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

19.6.90 GUSB3PIPECTL—Offset C2C0h

flag Value After Reset: 0x2020002

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GUSB3PIPECTL: [BAR] + C2C0h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 02044002h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
RSVD42				DISUIPIDRVR				NEWREGREQ				VSTSDONE				VSTSBSY				REGWR				REGADDR				VCTRL_EXTREGADDR				REGDATA			

Bit Range	Default & Access	Description
31:27	0h RO	RSVD42: reserved
26	0h RO	DISUIPIDRVR: Reg field DISUIPIDRVR
25	0h RO	NEWREGREQ: Reg field NEWREGREQ
24	0h RO	VSTSDONE: Reg field VSTSDONE
23	0h RO	VSTSBSY: Reg field VSTSBSY
22	0h RO	REGWR: Reg field REGWR
21:16	0h RO	REGADDR: Reg field REGADDR
15:8	0h RO	VCTRL_EXTREGADDR: TDB
7:0	0h RO	REGDATA: Reg field REGDATA



31	28				24				20				16				12				8				4				0																																																														
0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0																																																											
PHYSOFTRST				GUSB3PIPECTL_RSVD2				UX_EXIT_IN_PX				PING_ENHANCEMENT_EN				U1U2EXITFAIL_TO_RECOV				RequestP1P2P3				StartRxdetU3RxDet				DisRxDetU3RxDet				DELAYP1P2P3				DELAYP0TOP1P2P3TRANS				SUSPENDENABLE				DATWIDTH				ABORTRXDETU2EXIT				SKIPRXDET				LFPS0ALGN				P3P2TRANOK				P3EXSIGP2				LFPSFILTER				GUSB3PIPECTL_RSVD1				TX_SWING				TX_MARGIN				TX_DE_EMPHASIS				ELASTIC_BUFFER_MODE			

Bit Range	Default & Access	Description
31	0h RW	PHYSOFTIRST: Reg field PHYSOFTIRST
30:28	0h RO	GUSB3PIPECTL_RSVD2:
27	0h RW	UX_EXIT_IN_PX: Ux Exit in Px: n 0: The core does U1/U2/U3 exit in PHY power state P0 (default behavior) n 1: The core does U1/U2/U3 exit in PHY power state P1/P2/P3 respectively This bit is added for SS PHY workaround where SS PHY injects a glitch on pipe3_RxElecIdle while receiving Ux exit LFPS, and pipe3_PowerDown change is in progress. Note: This bit is used by third-party SS PHY. It should be set to '0' for Synopsys PHY.
26	0h RW	PING_ENHANCEMENT_EN: Ping Enhancement Enable: When set, the Downstream port U1 ping receive timeout becomes 500 ms instead of 300 ms. Minimum Ping.LFPS receive duration is 8 ns (one mac3_clk). This field is valid for Downstream port only. Note: This bit is used by third-party SS PHY. It should be set to '0' for Synopsys PHY.
25	1h RW	U1U2EXITFAIL_TO_RECOV: Reg field u1u2exitfail_to_recov
24	0h RW	REQUESTp1p2p3 (RequestP1P2P3):
23	0h RW	STARTRXDETU3RXDET (StartRxDetU3RxDet): Reg field StartRxDetU3RxDet
22	0h RW	DISRXDETU3RXDET (DisRxDetU3RxDet): Disable Receiver Detection in U3/Rx.Det: When set, the core does not do receiver detection in U3 or Rx.Detect state. DWC_USB3_GUSB3PIPECTL_INIT[23] should be used to start receiver detection manually. This bit is valid for Downstream ports only. Delay P1P2P3 Delay P0 to P1/P2/P3 request when entering U1/U2/U3 until (DWC_USB3_GUSB3PIPECTL_INIT[21:19]*8) 8B10B error occurs, or Pipe3_RxValid drops to 0. DWC_USB3_GUSB3PIPECTL_INIT[18] must be 1 to enable this functionality. Delay PHY power change from P0 to P1/P2/P3 when link state changing from U0 to U1/U2/U3 respectively. n 1'b1: When entering U1/U2/U3, delay the transition to P1/P2/P3 until the pipe3 signals, Pipe3_RxElecIdle is 1 and pipe3_RxValid is 0 n 1'b0: When entering U1/U2/U3, transition to P1/P2/P3 without checking for Pipe3_RxElecIdle and pipe3_RxValid. Note: This bit should be set to '1' for Synopsys PHY. It is also used by third-party SS PHY.
21:19	0h RW	DELAYP1P2P3: Reg field DelayP1P2P3
18	1h RW	DELAYP0TOP1P2P3TRANS:
17	0h RW	SUSPENDENABLE: Reg field SUSPENDENABLE
16:15	0h RO	DATWIDTH: Reg field DATWIDTH



Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

[illegible]



Bit Range	Default & Access	Description
15:0	0042h RW	TXFDEP_0:

19.6.92 GTXFIFOSIZ1—Offset C304h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GTXFIFOSIZ1: [BAR] + C304h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00420184h

[illegible]

Bit Range	Default & Access	Description
31:16	0042h RW	TXFSTADDR_1:
15:0	0184h RW	TXFDEP_1:

19.6.93 GTXFIFOSIZ2—Offset C308h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GTXFIFOSIZ2: [BAR] + C308h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 01C60184h

[illegible]

Bit Range	Default & Access	Description
31:16	01c6h RW	TXFSTADDR_2:



Bit Range	Default & Access	Description
15:0	0082h RW	TXFDEP_6:

19.6.98 GTXFIFOSIZ7—Offset C31Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GTXFIFOSIZ7: [BAR] + C31Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 06540082h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	1	0	0
0	1	1	0	0	1	0	0	0
0	1	0	1	0	1	0	0	0
0	0	0	0	0	0	0	0	0
1	0	0	0	0	0	0	0	0
0	0	0	1	0				
TXFSTADDR_7				TXFDEP_7				

Bit Range	Default & Access	Description
31:16	0654h RW	TXFSTADDR_7:
15:0	0082h RW	TXFDEP_7:

19.6.99 GTXFIFOSIZ8—Offset C320h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GTXFIFOSIZ8: [BAR] + C320h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 06D60022h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	1	0	0
0	1	1	0	1	0	1	0	0
1	1	0	1	0	1	1	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	1	0	0	0	0	0	0
0	0	1	0					
TXFSTADDR_8				TXFDEP_8				

Bit Range	Default & Access	Description
31:16	06d6h RW	TXFSTADDR_8:



Bit Range	Default & Access	Description
15:0	0022h RW	TXFDEP_12:

19.6.104 GTXFIFOSIZ13—Offset C334h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GTXFIFOSIZ13: [BAR] + C334h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 07800022h

[illegible]

Bit Range	Default & Access	Description
31:16	0780h RW	TXFSTADDR_13:
15:0	0022h RW	TXFDEP_13:

19.6.105 GTXFIFOSIZ14—Offset C338h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GTXFIFOSIZ14: [BAR] + C338h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 07A20022h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	1	1	1	1	0	0	1	0
TXFSTADDR_14				TXFDEP_14				

Bit Range	Default & Access	Description
31:16	07a2h RW	TXFSTADDR_14:



Bit Range	Default & Access	Description
15:0	0022h RW	TXFDEP_14:

19.6.106 GTXFIFOSIZ15—Offset C33Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GTXFIFOSIZ15: [BAR] + C33Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 07C40022h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	1	1	1
0	0	0	0	0	1	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:16	07c4h RW	TXFSTADDR_15:
15:0	0022h RW	TXFDEP_15:

19.6.107 GRXFIFOSIZ0—Offset C380h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GRXFIFOSIZ0: [BAR] + C380h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000385h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:16	0h RW	RXFSTADDR_0:



Bit Range	Default & Access	Description
15:0	0385h RW	RXFDEP_0:

19.6.108 GRXFIFOSIZ1—Offset C384h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GRXFIFOSIZ1: [BAR] + C384h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 03850000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RXFSTADDR_1				RXFDEP_1				

Bit Range	Default & Access	Description
31:16	0385h RW	RXFSTADDR_1:
15:0	0000h RW	RXFDEP_1:

19.6.109 GRXFIFOSIZ2—Offset C388h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GRXFIFOSIZ2: [BAR] + C388h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 03850000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RXFSTADDR_2				RXFDEP_2				

Bit Range	Default & Access	Description
31:16	0385h RW	RXFSTADDR_2:

19.6.110 GEVNTADRLO—Offset C400h

Bit Range	Default & Access	Description
15:0	0h RW	RXFDEP_2:

19.6.110 GEVNTADRLO—Offset C400h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GEVNTADRLO: [BAR] + C400h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:0	0h RW	EVNTADRLO: field EVNTADRLO

19.6.111 GEVNTADRHI—Offset C404h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GEVNTADRHI: [BAR] + C404h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:0	0h RW	EVNTADRHI: Reg field EVNTADRHI

19.6.112 GEVNTSIZ—Offset C408h

Access Method

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GHWPARAMS8: [BAR] + C600h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00002000h

	31	28	24	20	16	12	8	4	0
DWC_USB3_DCACHE_DEPTH_INFO	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	2000h RO	DWC_USB3_DCACHE_DEPTH_INFO:

19.6.115 DCFG—Offset C700h

flag Value After Reset: 0x80804 Device Configuration Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DCFG: [BAR] + C700h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00080800h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
DCFG_RSVD								IGNSTRMP		LPMCAP		NUPM				INTRNUM				PERPRINT		DEVADDR				DEVSPD									

Bit Range	Default & Access	Description
31:24	0h RO	DCFG_RSVD:
23	0h RW	IGNSTRMPP: Reserved



Bit Range	Default & Access	Description
22	0h RW	LPMCAPH: LPM Capable
21:17	04h RW	NUMP: Reg field NUMP
16:12	0h RW	INTRNUM: Reg field INTRNUM
11:10	2h RW	PERFRINT: Reg field PERFRINT
9:3	0h RW	DEVADDR: Reg field DEVADDR
2:0	0h RW	DEVSPD: flag Value After Reset: 0x4 Reg field DEVSPD

19.6.116 DCTL—Offset C704h

Device Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DCTL: [BAR] + C704h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31	0h RW	RUN_STOP: Run/Stop
30	0h RW	CSFTRST: Core Soft Reset
29	0h RW	LSFTRST: Light Soft Reset
28:24	0h RW	HIRDTHRES: Reg field HIRDTHRES
23	0h RW	APPL1RES: LPM Response Programmed by Application
22:21	0h RO	RSVD40: reserved



Bit Range	Default & Access	Description
12	0h RW	VENDEVTSTRCDEN: Vendor Device Test LMP Received Event
11	0h RW	EVNTOVERFLOWEN: Event Buffer Overflow Event Enable
10	0h RW	CMDCMPLTEN: Generic Command Complete Event Enable
9	0h RW	ERRTICERREVTEN: Erratic Error Event Enable
8	0h RW	RSVD39: reserved
7	0h RW	SOFTEVTEN: Start of
6	0h RW	EOPFEVTEN: End of Periodic Frame Event Enable
5	0h RW	RSVD3: reserved
4	0h RW	WKUPEVTEN: Resume/Remote Wakeup Detected Event Enable
3	0h RW	ULSTCNGEN: USB/Link State Change Event Enable
2	0h RW	CONNECTDONEVTEN: Connection Done Enable
1	0h RW	USBRSTEV TEN: USB Reset Enable
0	0h RW	DISSCONNEVTEN: Disconnect Detected Event Enable

19.6.118 DSTS—Offset C70Ch

flag Value After Reset: 0x20820004 Device Status Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTS: [BAR] + C70Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00120004h

31				28				24				20				16				12				8				4				0															
0 0 0 0				0 0 0 0				0 0 0 0				1 0 0 0				1 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 1 0 0															
DSTS_RSVD2				DCNRD				SRE				DSTS_RSVD1				RSS				SSS				COREIDLE				DEVCTRLHIL				USBLINKST				RXFFIOEMPTY				SOFFN				CONNECTSPD			

Reg field PARAMETER

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2 0: [BAR] + C800h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

[illegible]

19.6.123 DEPCMDPAR1_0—Offset C804h

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_0: [BAR] + C804h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Command Active
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.126 DEPCMDPAR2_1—Offset C810h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_1: [BAR] + C810h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PARAMETER

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.127 DEPCMDPAR1_1—Offset C814h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_1: [BAR] + C814h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Command Active
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.130 DEPCMDPAR2_2—Offset C820h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_2: [BAR] + C820h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PARAMETER

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.131 DEPCMDPAR1_2—Offset C824h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_2: [BAR] + C824h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.134 DEPCMDPAR2_3—Offset C830h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_3: [BAR] + C830h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PARAMETER

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.135 DEPCMDPAR1_3—Offset C834h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_3: [BAR] + C834h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.138 DEPCMDPAR2_4—Offset C840h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_4: [BAR] + C840h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PARAMETER

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.139 DEPCMDPAR1_4—Offset C844h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_4: [BAR] + C844h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.142 DEPCMDPAR2_5—Offset C850h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_5: [BAR] + C850h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PARAMETER

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reserved.

19.6.143 DEPCMDPAR1_5—Offset C854h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_5: [BAR] + C854h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Command Active
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.146 DEPCMDPAR2_6—Offset C860h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_6: [BAR] + C860h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PARAMETER

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.147 DEPCMDPAR1_6—Offset C864h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_6: [BAR] + C864h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Command Active
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.150 DEPCMDPAR2_7—Offset C870h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_7: [BAR] + C870h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PARAMETER

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.151 DEPCMDPAR1_7—Offset C874h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_7: [BAR] + C874h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

312824201612840																															
000																															

19.6.152 DEPCMDPAR0_7—Offset C878h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_7: [BAR] + C878h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0															
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0															
PARAMETER															

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.153 DEPCMD_7—Offset C87Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_7: [BAR] + C87Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Command Active
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.154 DEPCMDPAR2_8—Offset C880h

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER



19.6.155 DEPCMDPAR1_8—Offset C884h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_8: [BAR] + C884h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.156 DEPCMDPAR0_8—Offset C888h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_8: [BAR] + C888h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.157 DEPCMD_8—Offset C88Ch

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_8: [BAR] + C88Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STREAMNUM				CMDSTATUS	HIPRI_FORCERM	CMDACT	R39	CMDIOC
							RSVD90	CMDTYP

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Command Active
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.158 DEPCMDPAR2_9—Offset C890h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_9: [BAR] + C890h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								



Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.159 DEPCMDPAR1_9—Offset C894h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_9: [BAR] + C894h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.160 DEPCMDPAR0_9—Offset C898h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_9: [BAR] + C898h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER



19.6.161 DEPCMD_9—Offset C89Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_9: [BAR] + C89Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STREAMNUM				CMDSTATUS	HIPRI_FORCERM	CMDACT	R39	CMDIOC
							RSVD90	CMDTYP

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Command Active
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.162 DEPCMDPAR2_10—Offset C8A0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_10: [BAR] + C8A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_11: [BAR] + C8B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28				24				20				16				12				8				4				0					
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
PARAMETER																																		

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.169 DEPCMD_11—Offset C8BCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_11: [BAR] + C8BCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STREAMNUM				CMDSTATUS		HIPRI_FORCERM		CMDTYP
						CMDACT		
						R39		
						CMDIOC		
						RSVD90		

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Command Active
9	0h RW	R39: Reg field R39



Bit Range	Default & Access	Description
8	0h RW	CMDIOC: Command Interrupt on Complete
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.170 DEPCMDPAR2_12—Offset C8C0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_12: [BAR] + C8C0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.171 DEPCMDPAR1_12—Offset C8C4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_12: [BAR] + C8C4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

19.6.172 DEPCMDPAR0_12—Offset C8C8h

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_12: [BAR] + C8C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.173 DEPCMD_12—Offset C8CCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


DEPCMD_12: [BAR] + C8CCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STREAMNUM				CMDSTATUS		HIPRI_FORCERM	CMDACT	R39
						CMDIOC	RSVD90	CMDTYP



Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_13: [BAR] + C8D4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

[illegible]

19.6.176 DEPCMDPAR0_13—Offset C8D8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_13: [BAR] + C8D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

312824201612840																															
00000000000000000000000000000000																															
PARAMETER																															

19.6.177 DEPCMD_13—Offset C8DCh

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_13: [BAR] + C8DCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



19.6.178 DEPCMDPAR2_14—Offset C8E0h

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
2605



Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.180 DEPCMDPAR0_14—Offset C8E8h

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.181 DEPCMD_14—Offset C8ECh

October 2018
Document Number: 538136, Rev. 4.3



19.6.185 DEPCMD_15—Offset C8FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_15: [BAR] + C8FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STREAMNUM				CMDSTATUS	HIPRI_FORCERM	CMDACT	R39	CMDIOC
							RSVD90	CMDTYP

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.186 DEPCMDPAR2_16—Offset C900h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_16: [BAR] + C900h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



19.6.188 DEPCMDPAR0_16—Offset C908h



Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.191 DEPCMDPAR1 17—Offset C914h

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.192 DEPCMDPAR0_17—Offset C918h

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.194 DEPCMDPAR2_18—Offset C920h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_18: [BAR] + C920h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PARAMETER

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.195 DEPCMDPAR1_18—Offset C924h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_18: [BAR] + C924h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

PARAMETER

19.6.196 DEPCMDPAR0_18—Offset C928h

19.6.198 DEPCMDPAR2_19—Offset C930h

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_19: [BAR] + C930h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

Diagram illustrating the structure of a 32-bit register. The register is divided into eight 4-bit fields, each labeled with a bit range (31-28, 24-21, 20-17, 16-13, 12-9, 8-5, 4-1, 0-3) and containing the value 0. A vertical line labeled "PARAMETER" is positioned between the 16-13 and 12-9 bit ranges.

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.199 DEPCMDPAR1_19—Offset C934h

Access Method



Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.202 DEPCMDPAR2_20—Offset C940h

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reserved.



Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_20: [BAR] + C94Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STREAMNUM				CMDSTATUS	HIPRI_FORCERM	CMDACT	R39	CMDIOC
							RSVD90	CMDTYP

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reserved.
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.206 DEPCMDPAR2_21—Offset C950h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_21: [BAR] + C950h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.207 DEPCMDPAR1_21—Offset C954h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_21: [BAR] + C954h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

	31		28		24		20		16		12		8		4		0	
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	PARAMETER																	

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.208 DEPCMDPAR0_21—Offset C958h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_21: [BAR] + C958h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER



19.6.209 DEPCMD_21—Offset C95Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_21: [BAR] + C95Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																							
0				0				0				0				0				0				0				0				0																							
STREAMNUM																CMDSTATUS								HIPRI_FORCERM				CMDACT				R39				CMDIOC				RSVD90								CMDTYP							

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.210 DEPCMDPAR2_22—Offset C960h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_22: [BAR] + C960h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0															
PARAMETER															

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.211 DEPCMDPAR1_22—Offset C964h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_22: [BAR] + C964h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0															
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0															
PARAMETER															

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.212 DEPCMDPAR0_22—Offset C968h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_22: [BAR] + C968h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_23: [BAR] + C978h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

	0	4	8	12	16	20	24	28	31
0	0	0	0	0	0	0	0	0	0
PARAMETER									

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.217 DEPCMD_23—Offset C97Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_23: [BAR] + C97Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STREAMNUM				CMDSTATUS		HIPRI_FORCERM	CMDACT	R39
						CMDIOC	RSVD90	CMDTYP

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39



Bit Range	Default & Access	Description
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.218 DEPCMDPAR2 24—Offset C980h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2 24: [BAR] + C980h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.219 DEPCMDPAR1_24—Offset C984h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_24: [BAR] + C984h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

19.6.220 DEPCMDPAR0_24—Offset C988h

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_24: [BAR] + C988h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.221 DEPCMD_24—Offset C98Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_24: [BAR] + C98Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STREAMNUM				CMDSTATUS	HIPRI_FORCERM	CMDACT	R39	CMDIOC
							RSVD90	
								CMDTYP

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_25: [BAR] + C994h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
PARAMETER																																

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.224 DEPCMDPAR0_25—Offset C998h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_25: [BAR] + C998h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.225 DEPCMD_25—Offset C99Ch

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_25: [BAR] + C99Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



19.6.226 DEPCMDPAR2 26—Offset C9A0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Intel Atom® Processor E3800 Product Family
Datasheet
2631



Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.228 DEPCMDPAR0_26—Offset C9A8h

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.229 DEPCMD_26—Offset C9ACh

October 2018
Document Number: 538136, Rev. 4.3

19.6.231 DEPCMDPAR1_27—Offset C9B4h

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_27: [BAR] + C9B4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.232 DEPCMDPAR0_27—Offset C9B8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR0_27: [BAR] + C9B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER



19.6.233 DEPCMD_27—Offset C9BCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMD_27: [BAR] + C9BCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STREAMNUM				CMDSTATUS	HIPRI_FORCERM	CMDACT	R39	CMDIOC
							RSVD90	CMDTYP

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

19.6.234 DEPCMDPAR2_28—Offset C9C0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_28: [BAR] + C9C0h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



19.6.236 DEPCMDPAR0_28—Offset C9C8h



31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0				
STREAMNUM																CMDSTATUS								HIPRI_FORCERM				RSVD90				CMDTYP			
																								CMDACT											
																								R39											
																								CMDIOC											



Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.239 DEPCMDPAR1_29—Offset C9D4h

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.240 DEPCMDPAR0_29—Offset C9D8h

October 2018
Document Number: 538136, Rev. 4.3

19.6.242 DEPCMDPAR2_30—Offset C9E0h

Bit Range	Default & Access	Description
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2 30: [BAR] + C9E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.243 DEPCMDPAR1_30—Offset C9E4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR1_30: [BAR] + C9E4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PARAMETER								

19.6.246 DEPCMDPAR2_31—Offset C9F0h

Bit Range	Default & Access	Description
31:16	0h RW	STREAMNUM:
15:12	0h RW	CMDSTATUS: Reg field CMDSTATUS
11	0h RW	HIPRI_FORCERM: Reg field HIPRI_FORCERM
10	0h RW	CMDACT: Reg field CMDACT
9	0h RW	R39: Reg field R39
8	0h RW	CMDIOC: Reg field CMDIOC
7:4	0h RW	RSVD90: reserved
3:0	0h RW	CMDTYP: Reg field CMDTYP

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DEPCMDPAR2_31: [BAR] + C9F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

Diagram illustrating the structure of a 32-bit register. The register is divided into eight 4-bit segments, each labeled with a bit range (31-28, 27-24, 23-20, 19-16, 15-12, 11-8, 7-4, 3-0) and containing the value 0. A vertical line labeled 'PARAMETER' is positioned between the 16th and 17th bits.

Bit Range	Default & Access	Description
31:0	0h RW	PARAMETER: Reg field PARAMETER

19.6.247 DEPCMDPAR1_31—Offset C9F4h

Access Method



Access Method

OCFG: [BAR] + CC00h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:3	0h RO	RSVD0: reserved



Bit Range	Default & Access	Description
3	0h RW	SesReq: Session Request: n 1'b0: No session request n 1'b1: Session request The application sets this bit to initiate a session request on the USB. Writing 1'b1 to this field will trigger the core to send SRP (data line pulsing) on PHY interface. In the absence of OEVT.OTGBDevSessVldDetEvt after a session request, the application must wait for atleast TB_SRP_FAIL time (6 secs) before initiating another session request. This field returns 1'b0 when read.
2	0h RW	TermSelDLPulse: TermSel DLine Pulsing Selection: This bit selects utmi_termselect to drive data line pulse during SRP. n 1'b0: Data line pulsing using utmi_txvalid (default). n 1'b1: Data line pulsing using utmi_termsel.
1	0h RW	DevSetHNPEn: Device Set RSP/HNP Enable: n 1'b0: RSP/HNP is not enabled in the application n 1'b1: RSP/HNP is enabled in the application The application sets this bit in the following scenario: n In HS/FS mode, when it successfully receives a SetFeature.SetHNPEnable command from the connected USB host. n In SS mode, when it has sent a b3_ntf_hst_rel to the A-device, or the A-device has sent an a3_ntf_host_req. Note: The terminology RSP is used when the core is operating in SS mode, and HNP is used when the core is operating in non-SS mode.
0	0h RW	HstSetHNPEn: Host Set RSP/HNP Enable: n 1'b0: Host Set RSP/HNP is not enabled n 1'b1: Host Set RSP/HNP is enabled The application sets this bit in the following scenario: n In HS/FS mode, when it has successfully enabled HNP (using the SetFeature.SetHNPEnable command) from the connected device. n In SS mode, when it has successfully enabled b3_rsp_enable feature in RSP-capable Device using SetFeature command while operating as an A-Host, or when it has received a b3_ntf_hst_rel through SetFeature command while operating as A-peripheral. Note: The terminology RSP is used when the core is operating in SS mode, and HNP is used when the core is operating in non-SS mode.

19.6.252 OEVT—Offset CC08h

Value After Reset: 0x0 OTG Events Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

OEVT: [BAR] + CC08h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 80000000h

31	28	24	20	16	12	8	4	0
1	0	0	0	0	0	0	0	0
DeviceMode	RSVD0	OTGConIDStsChngEvt	RSVD1	OTGADevBHostEndEvt	OTGADevHostEndEvt	OTGADevHNPChngEvt	OTGADevSRPDetEvt	OTGADevSessEndDetEvt
				RSVD2	OTGBDevBHostEndEvt	OTGBDevHNPChngEvt	OTGBDevSessVldDetEvt	OTGBDevVBUSChngEvt
					RSVD3	BSesVld	HstNegSts	SesReqSts
								OEVTError

Bit Range	Default & Access	Description
31	1h RO	DeviceMode: Device Mode: Indicates whether the device is in A-device or B-device mode based on utmiotg_iddig n 1'b0: A-Device mode n1'b1: B-Device mode The rest of the OTG Event Information bits (OTGxxxxEvtInfo) in OEVT register will be based on the contents of this field.



Bit Range	Default & Access	Description
30:25	0h RO	RSVD0: reserved
24	0h RO	OTGConIDStsChngEvnt: Write Behavior: oneToClear Connector ID Status Change Event: Set in both A-Dev/B-Dev Mode. This event is generated when there is a change in connector ID status.
23:21	0h RO	RSVD1: reserved
20	0h RO	OTGADevBHostEndEvnt: Write Behavior: oneToClear A-device B-Host End Event: Set in A-device Mode Only. The event is generated when B-device has completed its host role. Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation.
19	0h RO	OTGADevHostEvnt: Write Behavior: oneToClear A-device host event: Set in A-device Mode Only. This event is generated when A-device enters host role. In HS/FS mode, it occurs after the initial connect to a B-device as A-host as well as when there is a role change from A-peripheral to A-host. Note: This bit is applicable only for OTG 2.0 mode of operation.
18	0h RO	OTGADevHNPChngEvnt: Write Behavior: oneToClear A-Dev HNP Change Event: Set in A-device Mode Only. The event is generated when there is an HNP attempt. Note: This bit is applicable only for OTG 2.0 mode of operation.
17	0h RO	OTGADevSRPDetEvnt: Write Behavior: oneToClear SRP Detect Event: Set in A-device Mode Only. This event is asserted when a session request from the B-device is detected via SRP. Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation.
16	0h RO	OTGADevSessEndDetEvnt: Write Behavior: oneToClear Session End Detected Event: Set in A-device Mode Only. This event is asserted when the utmisrp_avalid signal goes low indicating the end of a session. Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation
15:12	0h RO	RSVD2: Reserved
11	0h RO	OTGBDevBHostEndEvnt: Write Behavior: oneToClear B-Device B-Host End Event: Set in B-device Mode Only. This event is generated when B-device has completed its host role. Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation.
10	0h RO	OTGBDevHNPChngEvnt: Write Behavior: oneToClear B-Dev HNP Change Event: Set in B-Device Mode only. This event is generated when there is a Success or Failure of an HNP attempt. Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation.
9	0h RO	OTGBDevSessVldDetEvnt: Write Behavior: oneToClear Session Valid Detected Event: Set in B-device Mode Only. This event is asserted when there is a valid Vbus from A-device and B-device succeeds in starting a session. Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation.
8	0h RO	OTGBDevVBUSChngEvnt: Write Behavior: oneToClear Vbus Change Event: Set in B-device Mode Only. This event is asserted when the utmisrp_bvalid signal goes low (indicating the end of a session), or goes high. Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation.
7:4	0h RO	RSVD3: reserved
3	0h RO	BSesVld: Indicates the Device mode transceiver status. Indicates the Device mode transceiver status. The core updates this bit when OEVTEN.OTGBDevVBUSChngEvnt is set. 1b0: B-session is not valid 1b1: B-session is valid Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation.
2	0h RO	HstNegSts: Host Negotiation Status: The core updates this bit when any of the following bits is set: n OEVTEN.OTGADevHNPChngEvnt n OEVTEN.OTGBDevHNPChngEvnt This bit indicates Host Negotiation Success or Failure. n 1'b0: Host negotiation failure. In A-device, for HS/FS, this indicates an imminent end of session indication from the core. In B-device, for HS/LS, it indicates that the timer used to wait for an A-device to signal a connection (b_ase0_brst_tmout in OTG 2.0) timed out resulting in B-device staying as B-peripheral. n 1'b1: Host negotiation success. This indicates that the host negotiation was successful. Note: This bit is applicable only for OTG 2.0 mode of operation.



Bit Range	Default & Access	Description
1	0h RO	SesReqSts: Session Request Status: The core updates this bit when OEVTEN.OTGBDevSessVldDetEvnt is set. o 1'b0: Session request due to Vbus. This indicates that the session started due to Vbus without SRP detection by A-host. o 1'b1: Session request due to SRP. This indicates that the session started as a result of successful SRP detection by A-host. Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation.
0	0h RO	OEVTError: Write Behavior: oneToClear OTG Event Error: There are no errors currently defined.

19.6.253 OEVTEN—Offset CC0Ch

OTG Events Enable Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

OEVTEN: [BAR] + CC0Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0		OTGConIDStsChngEvntEn	RSVD1	OTGADevBHostEndEvntEn	OTGADevHostEvntEn	OTGADevHNPChngEvntEn	OTGADevSRPDetEvntEn	OTGADevSessEndDetEvntEn
					RSVD2	OTGBDevBHostEndEvntEn	OTGBDevHNPChngEvntEn	OTGBDevSessVldDetEvntEn
						OTGBDevVBUSChngEvntEn		RSVD3

Bit Range	Default & Access	Description
31:25	0h RO	RSVD0: reserved
24	0h RW	OTGConIDStsChngEvntEn: Connector ID Status Change Event (OTGConIDStsChngEvnt) Set in both A-Dev/B-Dev Mode: This Event is generated when there is a change in connector ID status
23:21	0h RO	RSVD1: reserved
20	0h RW	OTGADevBHostEndEvntEn: A-device B-Host End Event Enable (OTGADevBHostEndEvntEn) When this bit is set, OEVT.OTGADevBHostEndEvnt is enabled. Else the event is disabled.
19	0h RW	OTGADevHostEvntEn: A-device host event: When this bit is set, OEVT.OTGADevHostEvnt is enabled. If not, the event is disabled
18	0h RW	OTGADevHNPChngEvntEn: A-Dev HNP Change EventEn: When this bit is set, OEVT.OTGADevHNPChngEvnt is enabled. If not, the event is disabled
17	0h RW	OTGADevSRPDetEvntEn: SRP Detect Event Enable: When this bit is set, OEVT.OTGADevSRPDetEvnt is enabled. If not, the event is disabled



Bit Range	Default & Access	Description
2	0h RO	BSesVld: Indicates the Device mode transceiver status. Indicates the Device mode transceiver status. The core updates this bit when OEVTEN.OTGBDevVBUSChngEvnt is set. 1b0: B-session is not valid 1b1: B-session is valid Note: This bit is applicable for OTG 2.0 and OTG 3.0 modes of operation.
1	0h RO	ASesVld: Indicates the Host mode transceiver status. 1b0: A-session is not valid 1b1: A-session is valid
0	1h RO	ConIDSts: Connector ID Status: Indicates the connector ID status n 1'b0: The DWC_usb3 core is in A-device mode n 1'b1: The DWC_usb3 core is in B-device mode Note: The reset value of this field depends on the power-on value of the IDDIG signal from the PHY.

19.6.255 ADPCFG—Offset CC20h

ADP Configuration Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ADPCFG: [BAR] + CC20h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PrbPer	PrbDelta	PrbDschg	RSVD0					

Bit Range	Default & Access	Description
31:30	0h RW	PrbPer: Probe Period: These bits set the T_ADP_PRB as follows: n 2'b00: 0.775 sec n 2'b01: 1.55 sec n 2'b10: 2.275 sec n 2'b11: Reserved The scaledown values for PrbPer are: n 2'b00: 12.5ms n 2'b01: 18.75ms n 2'b10: 25 ms n 2'b11: 31.25 ms
29:28	0h RW	PrbDelta: Probe Delta: These bits set the resolution for RTIM value. They are defined in units of 32 kHz clock cycles as follows: n 2'b00: 1 cycles n 2'b01: 2 cycles n 2'b10: 3 cycles n 2'b11: 4 cycles For example, if this value is chosen to be 2'b01, it means that RTIM increments for every two 32 kHz clock cycles.
27:26	0h RW	PrbDschg: Probe Discharge: These bits set the time for TADP_DSCHG. They are defined as follows: n 2'b00: 4 msec n 2'b01: 8 msec n 2'b10: 16 msec n 2'b11: 32 msec The scaledown values for the PrbDschg are as follows: n 2'b00: 62.5 us n 2'b01: 125 us n 2'b10: 250 us n 2'b11: 500 us
25:0	0h RO	RSVD0: reserved

19.6.256 ADPCTL—Offset CC24h

ADP Control Register

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

ADPCTL: [BAR] + CC24h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0	EnaPrb	EnaSns	ADPEn	ADPRes	WB	RSVD1		

Bit Range	Default & Access	Description
31:29	0h RO	RSVD0: reserved
28	0h RW	EnaPrb: Enable Probe: When set to 1'b1 along with ADPEn, the core performs a probe operation.
27	0h RW	EnaSns: ADP Enable: When set to 1'b1, the core performs either ADP probing or sensing based on EnaPrb and EnaSns. ADPEn = 1'b0 gates the suspend clock for major portion of ADP related logic.
26	0h RW	ADPEn: ADP Enable: When set to 1'b1, the core performs either ADP probing or sensing based on EnaPrb and EnaSns. ADPEn = 1'b0 gates the suspend clock for major portion of ADP related logic.
25	0h RW	ADPRes: ADP Reset: When set to 1'b1, the ADP controller is reset. This bit is auto-cleared after the reset procedure is complete in the ADP controller.
24	0b RO	WB: Write Busy: n 1'b0: Write Completed n 1'b1: Write in Progress The application can read or write ADPCFG and ADPCTL registers only if this field is cleared. Hardware sets this bit when the write is in progress in the Suspend clock domain.
23:0	0h RO	RSVD1: reserved

19.6.257 ADPEVT—Offset CC28h

ADP Event Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ADPEVT: [BAR] + CC28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0	AdpPrbEvt	AdpSnsEvt	AdpTmoutEvt	ADPRstCmplEvt	RSVD1		RTIM	



Bit Range	Default & Access	Description
26	0h RW	ADPTmoutEvtEn: ADP Timeout Event Enable: When this bit is set, AdpTmoutEvtEn in ADPEVT register is enabled.
25	0h RW	ADPRstCmplItEvtEn: ADP Reset complete Event Enable: When this bit is set, ADPRstCmplItEvtEn in ADPEVT register is enabled.
24:0	0h RO	RSVD1: Reserved

19.6.259 BCFG—Offset CC30h

BC Configuration Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

BCFG: [BAR] + CC30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:2	0h RO	RSVD:
1	0h RW	IDDIG_SEL:
0	0h RW	CHIRP_EN:

19.6.260 BCEVT—Offset CC38h

BC Event Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

BCEVT: [BAR] + CC38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:25	0h RO	RSVD0: reserved
24	0h RO	MV_ChngEvnt:
23:5	0h RO	RSVD1:
4:0	0h RO	MultValIdBc:

19.6.261 BCEVTEN—Offset CC3Ch

BC Event Enable Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

BCEVTEN: [BAR] + CC3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:25	0h RO	RSVD0: reserved
24	0h RW	MV_ChngEvntEna:
23:0	0h RO	RSVD1: reserved



19.7 USB 3.0 Device Memory Mapped I/O Registers

Table 222. Summary of USB 3.0 Device Memory Mapped I/O Registers—BAR

Offset	Size	Register ID—Description	Default Value
8h	2	"APBFC_ILDOA0—Offset 8h" on page 2655	0000h
Ch	2	"APBFC_ILDOACLK0—Offset Ch" on page 2656	0000h
10h	2	"APBFC_ILDOS0—Offset 10h" on page 2657	0000h
14h	2	"APBFC_IPMA0—Offset 14h" on page 2658	0000h
18h	2	"APBFC_IPMA1—Offset 18h" on page 2660	0000h
1Ch	2	"APBFC_OPMA0—Offset 1Ch" on page 2661	0000h
20h	2	"APBFC_IPIPE0—Offset 20h" on page 2661	0000h
24h	2	"APBFC_IPIPE1A—Offset 24h" on page 2662	0000h
28h	2	"APBFC_IPIPE1B—Offset 28h" on page 2663	0000h
2Ch	2	"APBFC_IPIPE1C—Offset 2Ch" on page 2664	0000h
30h	2	"APBFC_IPIPE2—Offset 30h" on page 2664	0000h
34h	2	"APBFC_IPIPE3—Offset 34h" on page 2665	0000h
38h	2	"APBFC_OPIPE0—Offset 38h" on page 2666	0000h
3Ch	2	"APBFC_OPIPE1A—Offset 3Ch" on page 2667	0000h
40h	2	"APBFC_OPIPE1B—Offset 40h" on page 2668	0000h
44h	2	"APBFC_OPIPE1C—Offset 44h" on page 2669	0000h
48h	2	"APBFC_OPIPE2—Offset 48h" on page 2669	0000h
4Ch	2	"APBFC_OTG3_MISC0—Offset 4Ch" on page 2670	000Bh
50h	2	"APBFC_OTG3_MISC1—Offset 50h" on page 2671	0000h
54h	2	"APBFC_OTG3_MISC2—Offset 54h" on page 2671	1100h
58h	2	"APBFC_OTG3_MISC3—Offset 58h" on page 2672	7008h
5Ch	2	"APBFC_U3PMU_CFG0_REG—Offset 5Ch" on page 2673	0000h
60h	2	"APBFC_U3PMU_CFG1_REG—Offset 60h" on page 2674	0000h

19.7.1 APBFC_ILDOA0—Offset 8h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_ILDOA0: [BAR + 10F800h] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h



Bit Range	Default & Access	Description
15:10	0h RW	APBFC_ILDOA0_RSVD: Reserved.
9:5	0h RW	ildoa_trimoverride_reg: Reserved.
4	0b RW	ildoa_trimoverride_reg_sel: Reserved.
3	0b RW	ildoa_en_reg (ildoa_trimoverridesel_reg): Reserved.
2	0b RW	ildoa_trimoverridesel_reg_sel: Reserved.
1	0b RW	ildoa_en_reg: Reserved.
0	0b RW	lildoa_en_reg_sel: Reserved.

19.7.2 APBFC_ILDOACLK0—Offset Ch


Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_ILDOACLK0: [BAR + 10F800h] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h



19.7.3 APBFC_ILDOS0—Offset 10h

Type: Memory Mapped I/O Register
(Size: 16 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

October 2018
Document Number: 538136, Rev. 4.3

19.7.4 APBFC_IPMA0—Offset 14h

15	12	8	4	0			
0	0	0	0	0			
APBFC_ILDOS0_RSVD		ildos_trimoverride_reg	ildos_trimoverride_reg_sel	ildos_trimoverridesel_reg	ildos_trimoverridesel_reg_sel	ildos_en_reg	ildos_en_reg_sel

Bit Range	Default & Access	Description
15:10	0h RW	APBFC_ILDOS0_RSVD: Reserved.
9:5	0h RW	ildos_trimoverride_reg: Reserved.
4	0b RW	ildos_trimoverride_reg_sel: Reserved.
3	0b RW	ildos_trimoverridesel_reg: Reserved.
2	0b RW	ildos_trimoverridesel_reg_sel: Reserved.
1	0b RW	ildos_en_reg: Reserved.
0	0b RW	ildos_en_reg_sel: Reserved.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_IPMA0: [BAR + 10F800h] + 14h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h



15	0	0	0	12	0	0	0	8	0	0	0	4	0	0	0
IPMA_CMN_REFCLK_RCV_EN_REG	IPMA_CMN_REFCLK_RCV_EN_REG_SEL	IPMA_CMN_REFCLK_INT_SEL_REG	IPMA_CMN_REFCLK_INT_SEL_REG_SEL	IPMA_CMN_REFCLK_INT_B_REG	IPMA_CMN_REFCLK_INT_B_REG_SEL	IPMA_CMN_REFCLK_INT_REG	IPMA_CMN_REFCLK_INT_REG_SEL	IPMA_CMN_REFCLK_DISABLE_REG	IPMA_CMN_REFCLK_DISABLE_REG_SEL	IPMA_CMN_REFCLK_ALL_SEL_REG	IPMA_CMN_REFCLK_ALL_SEL_REG_SEL	IPMA_CMN_MACRO_EN_REG	IPMA_CMN_MACRO_EN_REG_SEL	IPMA_CMN_ANA_DISABLE_REG	IPMA_CMN_ANA_DISABLE_REG_SEL

Bit Range	Default & Access	Description
15	0b RW	IPMA_CMN_REFCLK_RCV_EN_REG: Reserved.
14	0b RW	IPMA_CMN_REFCLK_RCV_EN_REG_SEL: Reserved.
13	0b RW	IPMA_CMN_REFCLK_INT_SEL_REG: Reserved.
12	0b RW	IPMA_CMN_REFCLK_INT_SEL_REG_SEL: Reserved.
11	0b RW	IPMA_CMN_REFCLK_INT_B_REG: Reserved.
10	0b RW	IPMA_CMN_REFCLK_INT_B_REG_SEL: Reserved.
9	0b RW	IPMA_CMN_REFCLK_INT_REG: Reserved.
8	0b RW	IPMA_CMN_REFCLK_INT_REG_SEL: Reserved.
7	0b RW	IPMA_CMN_REFCLK_DISABLE_REG: Reserved.
6	0b RW	IPMA_CMN_REFCLK_DISABLE_REG_SEL: Reserved.
5	0b RW	IPMA_CMN_REFCLK_ALL_SEL_REG: Reserved.
4	0b RW	IPMA_CMN_REFCLK_ALL_SEL_REG_SEL: Reserved.
3	0b RW	IPMA_CMN_MACRO_EN_REG: Reserved.
2	0b RW	IPMA_CMN_MACRO_EN_REG_SEL: Reserved.
1	0b RW	IPMA_CMN_ANA_DISABLE_REG: Reserved.



Bit Range	Default & Access	Description
0	0b RW	IPMA_CMN_ANA_DISABLE_REG_SEL: Reserved.

19.7.5 APBFC_IPMA1—Offset 18h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_IPMA1: [BAR + 10F800h] + 18h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
APBFC_IPMA1_RSVD	ipma_cm_n_refclk_freqsel_reg	ipma_cm_n_refclk_freqsel_reg_sel	ipma_tx_ls_diag_data_reg	ipma_tx_ls_diag_data_reg_sel
			ipma_rx_epath_disable_reg	ipma_rx_epath_disable_reg_sel
			ipma_ls_diag_sel_reg	ipma_ls_diag_sel_reg_sel

Bit Range	Default & Access	Description
15:13	0h RO	APBFC_IPMA1_RSVD: Reserved.
12:7	0h RW	ipma_cm_n_refclk_freqsel_reg: Reserved.
6	0b RW	ipma_cm_n_refclk_freqsel_reg_sel: Reserved.
5	0b RW	ipma_tx_ls_diag_data_reg: Reserved.
4	0b RW	ipma_tx_ls_diag_data_reg_sel: Reserved.
3	0b RW	ipma_rx_epath_disable_reg: Reserved.
2	0b RW	ipma_rx_epath_disable_reg_sel: Reserved.
1	0b RW	ipma_ls_diag_sel_reg: Reserved.
0	0b RW	ipma_ls_diag_sel_reg_sel: Reserved.



19.7.6 APBFC_OPMA0—Offset 1Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_OPMA0: [BAR + 10F800h] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
APBFC_OPMA_RSVD				OPMA_RX_LS_DIAG_DATA_P_REG
				OPMA_RX_LS_DIAG_DATA_P_REG_SEL
				OPMA_RX_LS_DIAG_DATA_M_REG
				OPMA_RX_LS_DIAG_DATA_M_REG_SEL
				OPMA_CMN_REFCLK_ACTIVE_REG
				OPMA_CMN_REFCLK_ACTIVE_REG_SEL

Bit Range	Default & Access	Description
15:6	0h RW	APBFC_OPMA_RSVD: Reserved.
5	0b RW	OPMA_RX_LS_DIAG_DATA_P_REG: Reserved.
4	0b RW	OPMA_RX_LS_DIAG_DATA_P_REG_SEL: Reserved.
3	0b RW	OPMA_RX_LS_DIAG_DATA_M_REG: Reserved.
2	0b RW	OPMA_RX_LS_DIAG_DATA_M_REG_SEL: Reserved.
1	0b RW	OPMA_CMN_REFCLK_ACTIVE_REG: Reserved.
0	0b RW	OPMA_CMN_REFCLK_ACTIVE_REG_SEL: Reserved.

19.7.7 APBFC_IPIPE0—Offset 20h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_IPIPE0: [BAR + 10F800h] + 20h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h

19.7.8 APBFC_IPIPE1A—Offset 24h

Access Method

IPIPE_RX_TERM_REG	0	15
IPIPE_RX_TERM_REG_SEL	0	
IPIPE_RX_POLARITY_REG	0	
IPIPE_RX_POLARITY_REG_SEL	0	12
IPIPE_RX_EQ_TRAINING_REG	0	
IPIPE_RX_EQ_TRAINING_REG_SEL	0	
IPIPE_RESET_B_REG	0	
IPIPE_RESET_B_REG_SEL	0	8
IPIPE_POWERDOWN_REG	0	
IPIPE_POWERDOWN_REG_SEL	0	
IPIPE_PHY_MODE_REG	0	4
IPIPE_PHY_MODE_REG_SEL	0	
IPIPE_ELASTIC_BUF_MODE_REG	0	
IPIPE_ELASTIC_BUF_MODE_REG_SEL	0	0

Bit Range	Default & Access	Description
15	0b RW	IPIPE_RX_TERM_REG: Reserved.
14	0b RW	IPIPE_RX_TERM_REG_SEL: Reserved.
13	0b RW	IPIPE_RX_POLARITY_REG: Reserved.
12	0b RW	IPIPE_RX_POLARITY_REG_SEL: Reserved.
11	0b RW	IPIPE_RX_EQ_TRAINING_REG: Reserved.
10	0b RW	IPIPE_RX_EQ_TRAINING_REG_SEL: Reserved.
9	0b RW	IPIPE_RESET_B_REG: Reserved.
8	0b RW	IPIPE_RESET_B_REG_SEL: Reserved.
7:6	0h RW	IPIPE_POWERDOWN_REG: Reserved.
5	0b RW	IPIPE_POWERDOWN_REG_SEL: Reserved.
4:3	0h RW	IPIPE_PHY_MODE_REG: Reserved.
2	0b RW	IPIPE_PHY_MODE_REG_SEL: Reserved.
1	0b RW	IPIPE_ELASTIC_BUF_MODE_REG: Reserved.
0	0b RW	IPIPE_ELASTIC_BUF_MODE_REG_SEL: Reserved.



Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_IPIPE1A: [BAR + 10F800h] + 24h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
APBFC_IPIPE1A_RSVD				IPPIPE_TX_DATA_REG_SEL_A

Bit Range	Default & Access	Description
15:12	0h RO	APBFC_IPIPE1A_RSVD: Reserved.
11:1	0h RW	IPIPE_TX_DATA_REG_A: Reserved.
0	0b RW	IPIPE_TX_DATA_REG_SEL_A: Reserved.

19.7.9 APBFC_IPIPE1B—Offset 28h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_IPIPE1B: [BAR + 10F800h] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
APBFC_IPIPE1B_RSVD				IPPIPE_TX_DATA_REG_SEL_B

19.7.10 APBFC_IPIPE1C—Offset 2Ch

Bit Range	Default & Access	Description
15:12	0h RO	APBFC_IPIPE1B_RSVD: Reserved.
11:1	0h RW	IPIPE_TX_DATA_REG_B: Reserved.
0	0b RW	IPIPE_TX_DATA_REG_SEL_B: Reserved.

19.7.10 APBFC_IPIPE1C—Offset 2Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC IPIPE1C: [BAR + 10F800h] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
APBFC_IPIPE1C_RSVD		IPIPE_TX_DATA_REG_C		
		IPIPE_TX_DATA_REG_SEL_C		

Bit Range	Default & Access	Description
15:11	0h RO	APBFC_IPIPE1C_RSVD: Reserved.
10:1	0h RW	IPIPE_TX_DATA_REG_C: Reserved.
0	0b RW	IPIPE_TX_DATA_REG_SEL_C: Reserved.

19.7.11 APBFC_IPIPE2—Offset 30h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_IPIPE2: [BAR + 10F800h] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
IPIPE_TX_MARGIN_REG				IPIPE_TX_MARGIN_REG_SEL
				IPIPE_TX_ELEC_IDLE_REG
				IPIPE_TX_ELEC_IDLE_REG_SEL
				IPIPE_TX_DEEMPH_REG
				IPIPE_TX_DEEMPH_REG_SEL
				IPIPE_TX_DATA_K_REG
				IPIPE_TX_DATA_K_REG_SEL

Bit Range	Default & Access	Description
15:11	0h RW	IPIPE_TX_MARGIN_REG: Reserved.
10	0b RW	IPIPE_TX_MARGIN_REG_SEL: Reserved.
9	0b RW	IPIPE_TX_ELEC_IDLE_REG: Reserved.
8	0b RW	IPIPE_TX_ELEC_IDLE_REG_SEL: Reserved.
7:6	0h RW	IPIPE_TX_DEEMPH_REG: Reserved.
5	0b RW	IPIPE_TX_DEEMPH_REG_SEL: Reserved.
4:1	0h RW	IPIPE_TX_DATA_K_REG: Reserved.
0	0b RW	IPIPE_TX_DATA_K_REG_SEL: Reserved.

19.7.12 APBFC_IPIPE3—Offset 34h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_IPIPE3: [BAR + 10F800h] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
APBFC_IPIPE3_RSVD				IPIPE_TX_SWING_REG
				IPIPE_TX_SWING_REG_SEL
				IPIPE_TX_ONES_ZEROS_REG
				IPIPE_TX_ONES_ZEROS_REG_SEL
				IPIPE_TX_DET_RX_LPBK_REG
				IPIPE_TX_DET_RX_LPBK_REG_SEL

Bit Range	Default & Access	Description
15:6	0h RO	APBFC_IPIPE3_RSVD: Reserved.
5	0b RW	IPIPE_TX_SWING_REG: Reserved.
4	0b RW	IPIPE_TX_SWING_REG_SEL: Reserved.
3	0b RW	IPIPE_TX_ONES_ZEROS_REG: Reserved.
2	0b RW	IPIPE_TX_ONES_ZEROS_REG_SEL: Reserved.
1	0b RW	IPIPE_TX_DET_RX_LPBK_REG: Reserved.
0	0b RW	IPIPE_TX_DET_RX_LPBK_REG_SEL: Reserved.

19.7.13 APBFC_OPIPE0—Offset 38h

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_OPIPE0: [BAR + 10F800h] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
OPIPE_RX_DATA_K_REG				OPIPE_RX_DATA_K_REG_SEL
				OPIPE_RX_ELEC_IDLE_REG
				OPIPE_RX_ELEC_IDLE_REG_SEL
				OPIPE_POWER_PRESENT_REG
				OPIPE_POWER_PRESENT_REG_SEL
				OPIPE_PHY_STATUS_REG
				OPIPE_PHY_STATUS_REG_SEL
				OPIPE_DATA_BUS_WIDTH_REG
				OPIPE_DATA_BUS_WIDTH_REG_SEL
				OPIPE_CLK_REG
				OPIPE_CLK_REG_SEL

Bit Range	Default & Access	Description
15:12	0h RW	OPIPE_RX_DATA_K_REG: Reserved.
11	0b RW	OPIPE_RX_DATA_K_REG_SEL: Reserved.
10	0b RW	OPIPE_RX_ELEC_IDLE_REG: Reserved.
9	0b RW	OPIPE_RX_ELEC_IDLE_REG_SEL: Reserved.
8	0b RW	OPIPE_POWER_PRESENT_REG: Reserved.
7	0b RW	OPIPE_POWER_PRESENT_REG_SEL: Reserved.
6	0b RW	OPIPE_PHY_STATUS_REG: Reserved.
5	0b RW	OPIPE_PHY_STATUS_REG_SEL: Reserved.
4:3	0h RW	OPIPE_DATA_BUS_WIDTH_REG: Reserved.
2	0b RW	OPIPE_DATA_BUS_WIDTH_REG_SEL: Reserved.
1	0b RW	OPIPE_CLK_REG: Reserved.
0	0b RW	OPIPE_CLK_REG_SEL: Reserved.

19.7.14 APBFC_OPIPE1A—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_OPIPE1A: [BAR + 10F800h] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h



15	12	8	4	0
0	0	0	0	0
APBFC_OPIPE1A_REG_		OPIPE_RX_DATA_REG_A		OPIPE_RX_DATA_REG_A_SEL

Bit Range	Default & Access	Description
15:12	0h RW	APBFC_OPIPE1A_REG_: Reserved.
11:1	0h RW	OPIPE_RX_DATA_REG_A: Reserved.
0	0b RW	OPIPE_RX_DATA_REG_A_SEL: Reserved.

Access Method

APBFC_OPIPE1B: [BAR + 10F800h] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

15	12	8	4	0
0	0	0	0	0
APBFC_OPIPE1B_RSVD		OPIPE_RX_DATA_REG_B		
		OPIPE_RX_DATA_REG_B_SEL		

Bit Range	Default & Access	Description
15:12	0h RO	APBFC_OPIPE1B_RSVD: Reserved.
11:1	0h RW	OPIPE_RX_DATA_REG_B: Reserved.



15	12	8	4	0
0	0	0	0	0
APBFC_OPIPE2_RSVD				OPIPE_RX_VALID_REG
				OPIPE_RX_VALID_REG_SEL
				OPIPE_RX_STATUS_REG
				OPIPE_RX_STATUS_REG_SEL

Bit Range	Default & Access	Description
15:6	0h RO	APBFC_OPIPE2_RSVD: Reserved.
5	0b RW	OPIPE_RX_VALID_REG: Reserved.
4	0b RW	OPIPE_RX_VALID_REG_SEL: Reserved.
3:1	0h RW	OPIPE_RX_STATUS_REG: Reserved.
0	0b RW	OPIPE_RX_STATUS_REG_SEL: Reserved.

19.7.18 APBFC_OTG3_MISC0—Offset 4Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC_OTG3_MISC0: [BAR + 10F800h] + 4Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 000Bh

15	12	8	4	0
0	0	0	0	1
xm_rid_flis		xm_bmisc_info_flis		pme_en_flis
				bigendian_gs_flis
				bus_clken_gm_flis
				bus_clken_gs_flis

Bit Range	Default & Access	Description
15:12	0b RW	xm_rid_flis: Reserved.
11:8	0b RW	xm_bmisc_info_flis: Reserved.



Bit Range	Default & Access	Description
15:12	0001b RW	host_num_u3_port_flis: Reserved.
11:8	0001b RW	host_num_u2_port_flis: Reserved.
7:6	0b RW	hub_port_perm_attach_flis: Reserved.
5:4	00b RO	APBFC_OTG3_MISC2_RSVD: Reserved.
3:0	0b RW	xm_rmisc_info_flis: Reserved.

19.7.21 APBFC_OTG3_MISC3—Offset 58h

Default: 7008h

[illegible]



Bit Range	Default & Access	Description
15	0b RO	APBFC_OTG3_MISC3_RSVD: Reserved.
14	1b RW	xhc_bme_flis: Reserved.
13	1b RW	xhci_revision_flis: Reserved.
12:7	100000b RW	fladj_30mhz_reg_flis: Reserved.
6	0b RW	host_legacy_smi_bar_wr_flis: Reserved.
5	0b RW	host_legacy_smi_pci_cmd_reg_wr_flis: Reserved.
4	0b RW	host_msi_enable_flis: Reserved.
3	1b RW	host_port_power_control_present_flis: Reserved.
2	0b RW	host_u3_port_disable_flis: Reserved.
1	0b RW	host_u2_port_disable_flis: Reserved.
0	0b RW	xm_csysreq_flis: Reserved.

19.7.22 APBFC_U3PMU_CFG0_REG—Offset 5Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

APBFC U3PMU CFG0 REG: [BAR + 10F800h] + 5Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
p3p_u3pmu_cfg0_flg				

Bit Range	Default & Access	Description
15:0	0h RW	p3p_u3pmu_cfg0_flis: Reserved.



Type: Memory Mapped I/O Register
(Size: 16 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:22, F:0] + 10h

[illegible]


Bit Range	Default & Access	Description
15:0	0h RW	p3p_u3pmu_cfg1_flgis: Reserved.

20 Intel® High Definition Audio

The Intel® High Definition Audio (Intel® HD Audio) is an architecture and infrastructure to support high-quality audio implementations for PCs.

Note: The High Definition Audio interface is multiplexed on the same balls as LPE_I2S[1:0].

Note: When High Definition Audio is active, the LPE Audio functionality is disabled.



The Intel® High Definition Audio (Intel® HD Audio) controller consists of a set of DMA engines that are used to move samples of digitally encoded data between system memory and internal/external CODECs. The controller communicates with the internal/external CODECs over the Intel® HD Audio serial link. The output DMA engines move digital data from system memory to a D-A converter in a CODEC. The SoC implements a single Serial Data Output (SDO) signal that is connected to the external CODECs. The input DMA engines move digital data from the A-D converter in the CODEC to system memory. The platform supports up to two external CODECs by implementing two Serial Data Input (SDI) signals, each being dedicated to a single CODEC.

Audio software renders outbound, and processes inbound data to/from buffers in memory. The location of the individual buffers is described by a Buffer Descriptor List that is fetched and processed by the audio controller. The data in the buffers is arranged in a pre-defined format. The output DMA engines fetch the digital data from memory and reformat it based on the programmed sample rate, bits/sample and number of channels. The data from the output DMA engines is then combined and serially sent to the CODEC(s) over the Intel® HD Audio link. The input DMA engines receive data from the CODEC(s) over the Intel® HD Audio link and format the data based on the programmable attributes for that stream. The data is then written to memory in the predefined format for software to process. Each DMA engine moves one "stream" of data. A single CODEC can accept or generate multiple "streams" of data, one for each A-D or D-A converter in the CODEC. Multiple CODECs can accept the same output "stream" processed by a single DMA engine.



Codec commands and responses are also transported to and from the CODEC via DMA engines. The DMA engine dedicated to transporting commands from the Command Output Ring Buffer (CORB) in memory to the CODEC(s) is called the CORB engine. The DMA engine dedicated to transporting responses from the CODEC(s) to the Response Input Ring Buffer in memory is called the RIRB engine. Every command sent to a CODEC yields a response from that CODEC. Some commands are “broadcast” type commands in which case a response will be generated from each CODEC. A CODEC may also be programmed to generate unsolicited responses, which the RIRB engine also processes. The platform also supports Programmed IO-based Immediate Command/Response transport mechanism that can be used by BIOS prior to memory initialization.

20.1 Signal Descriptions

Please see [Chapter 2, “Physical Interfaces”](#) for additional details.


The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal’s function

Table 223. Signals

Signal Name	Direction Plat. Power	Description
HDA_RST#	O VAUD	Intel HD Audio Reset: Master H/W reset to external Codecs
HDA_SYNC	O VAUD	Intel HD Audio Sync: 48 kHz fixed rate
HDA_CLK	O VAUD	Intel HD Audio Bit Clock (Output): 24 MHz serial data clock generated by the Intel HD Audio controller
HDA_SDO	O VAUD	Intel HD Audio Data Out: Serial TDM data output to the Codec(s). The serial output is double-pumped for a bit rate of 48 Mb/s
HDA_SDI[1:0]	I/O VAUD	Intel HD Audio Serial Data In[1:0]: Serial TDM data input from the CODEC(s). The serial input is single-pumped for a bit rate of 24 Mb/s.
HDA_LPE_RCOMP	O	Impedance/ current Compensation Output.

The signals in the table above are all muxed and maybe used by other functions.



20.2 Features

The Intel® HD Audio Controller supports the following features:

- Supports MSI and legacy interrupt delivery
- Support for ACPI D3 and D0 Device States
- Supports up to:
 - 6 streams (three input, three output)
 - 16 channels per stream
 - 32 bits/sample
 - 192 kHz sample rate
- 24 MHz HDA_CLK supports
 - SDO double pumped at 48 Mb/s
 - SDI single pumped at 24 Mb/s
- Supports 1.5V mode only
- Supports optional Immediate Command/Response mechanism

20.3 References

High Definition Audio Specification, Revision 1.0a


- <http://www.intel.com/content/www/us/en/standards/high-definition-audio-specification.html>

20.4 Register Map

See Chapters 3 and 4 for additional information.

Note: PCI mode is supported, but not PCIe mode. Must set TM1.HAPD bit to 1b for PCI mode.

Figure 105.Intel® HD Audio Register Map





20.5 HD Audio PCI Configuration Registers

Table 224. Summary of HD Audio PCI Configuration Registers—0/27/0

Offset	Size	Register ID—Description	Default Value
0h	2	"VID—Offset 0h" on page 2680	8086h
2h	2	"DID—Offset 2h" on page 2680	0F04h
4h	2	"CMD—Offset 4h" on page 2681	0000h
6h	2	"STS—Offset 6h" on page 2682	0010h
8h	1	"RID—Offset 8h" on page 2683	00h
9h	1	"PI—Offset 9h" on page 2683	00h
Ah	1	"SCC—Offset Ah" on page 2683	03h
Bh	1	"BCC—Offset Bh" on page 2684	04h
Ch	1	"CLS—Offset Ch" on page 2684	00h
Dh	1	"LT—Offset Dh" on page 2685	00h
Eh	1	"HTYPE—Offset Eh" on page 2685	00h
Fh	1	"BIST—Offset Fh" on page 2685	00h
10h	4	"AZLBAR—Offset 10h" on page 2686	00000004h
14h	4	"AZUBAR—Offset 14h" on page 2686	00000000h
2Ch	2	"SVID—Offset 2Ch" on page 2687	0000h
2Eh	2	"SID—Offset 2Eh" on page 2687	0000h
34h	1	"CAPPTR—Offset 34h" on page 2687	50h
3Ch	1	"INTLN—Offset 3Ch" on page 2688	00h
3Dh	1	"INTPN—Offset 3Dh" on page 2688	01h
40h	1	"AZCTL—Offset 40h" on page 2689	01h
42h	1	"IOBC—Offset 42h" on page 2689	00h
43h	1	"TM1—Offset 43h" on page 2690	57h
4Ch	1	"DCKCTL—Offset 4Ch" on page 2690	00h
4Dh	1	"DCKSTS—Offset 4Dh" on page 2691	80h
50h	2	"PID—Offset 50h" on page 2691	6001h
52h	2	"PC—Offset 52h" on page 2692	C842h
54h	4	"PCS—Offset 54h" on page 2693	00000000h
60h	2	"MID—Offset 60h" on page 2693	7005h
62h	2	"MMC—Offset 62h" on page 2694	0080h
64h	4	"MMLA—Offset 64h" on page 2694	00000000h
68h	4	"MMUA—Offset 68h" on page 2695	00000000h
6Ch	2	"MMD—Offset 6Ch" on page 2695	0000h
70h	2	"PXID—Offset 70h" on page 2696	0010h
72h	2	"PXC—Offset 72h" on page 2696	0091h
74h	4	"DEVCAP—Offset 74h" on page 2697	10000000h
78h	2	"DEVCAP—Offset 74h" on page 2697	0800h

Table 224. Summary of HD Audio PCI Configuration Registers—0/27/0 (Continued)

Offset	Size	Register ID—Description	Default Value
7Ah	2	"DEVS—Offset 7Ah" on page 2698	0010h
F8h	4	"MANID—Offset F8h" on page 2699	00000F00h
100h	4	"VCCAP—Offset 100h" on page 2700	13010002h
104h	4	"PVCCAP1—Offset 104h" on page 2700	00000001h
108h	4	"PVCCAP2—Offset 108h" on page 2701	00000000h
10Ch	2	"PVCCTL—Offset 10Ch" on page 2701	0000h
10Eh	2	"PVCSTS—Offset 10Eh" on page 2702	0000h
110h	4	"VC0CAP—Offset 110h" on page 2702	00000000h
114h	4	"VC0CTL—Offset 114h" on page 2703	800000FFh
11Ah	2	"VC0STS—Offset 11Ah" on page 2704	0000h
11Ch	4	"VCICAP—Offset 11Ch" on page 2704	00000000h
120h	4	"VICCTL—Offset 120h" on page 2705	00000000h
126h	2	"VCISTS—Offset 126h" on page 2706	0000h
130h	4	"RCCAP—Offset 130h" on page 2706	00010005h
134h	4	"ESD—Offset 134h" on page 2707	0F000100h
140h	4	"L1DESC—Offset 140h" on page 2708	00000001h
148h	4	"L1LADD—Offset 148h" on page 2708	00000000h
14Ch	4	"L1UADD—Offset 14Ch" on page 2709	00000000h

20.5.1 VID—Offset 0h

Vendor ID

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

VID: [B:0, D:27, F:0] + 0h

Default: 8086h

15			12				8				4				0
1	0	0	0	0	0	0	0	1	0	0	0	0	1	1	0
VID															

Bit Range	Default & Access	Description
15:0	8086h RO	VID: Vendor ID

20.5.2 DID—Offset 2h

Device ID

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

DID: [B:0, D:27, F:0] + 2h



Bit Range	Default & Access	Description
1	0h RW	MSE: Memory space enable
0	0h RO	IOS: I/O space enabled. Not implemented.

20.5.4 STS—Offset 6h

Status

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

STS: [B:0, D:27, F:0] + 6h

Default: 0010h

15	12	8	4	0
0	0	0	0	0
0	0	0	1	0
DPE	SERRS	RMA	RTA	STA
				DEVT
		MDPE	FBC	Reserved
			C66	CLIST
			IS	Reserved_1

Bit Range	Default & Access	Description
15	0h RO	DPE: Detected parity error. Not implemented.
14	0h RO	SERRS: SERR Status
13	0h WOC	RMA: Recieved master abort
12	0h RO	RTA: Recieved target abort. Not implemented.
11	0h RO	STA: Signaled target abort. Not implemented.
10:9	0h RO	DEVT: DEVSEL timing status. Not implemented.
8	0h RO	MDPE: Master data parity error. Not implemented.
7	0h RO	FBC: Fast back to back capable. Not implemented.
6	0h RO	Reserved: Reserved
5	0h RO	C66: 66MHz capable. Not implemented.
4	1h RO	CLIST: Capabilities list exist
3	0h RO	IS: Interrupt Status. Shows legacy interrupt signal status. Doesn't apply to MSI.



Bit Range	Default & Access	Description
2:0	0h RO	Reserved_1: reserved

20.5.5 RID—Offset 8h

Revision ID

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

RID: [B:0, D:27, F:0] + 8h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
RID									

Bit Range	Default & Access	Description
7:0	0h RO	RID: Revision ID

20.5.6 PI—Offset 9h

Programming Interface

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

PI: [B:0, D:27, F:0] + 9h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
PI									

Bit Range	Default & Access	Description
7:0	0h RO	PI: Programming Interface

20.5.7 SCC—Offset Ah

Sub Class Code

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SCC: [B:0, D:27, F:0] + Ah

Default: 03h



7				4					0
0	0	0	0	0	0	0	1	1	
SCC									

Bit Range	Default & Access	Description
7:0	03h RO	SCC: Sub Class Code

20.5.8 BCC—Offset Bh

Base Class Code

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

BCC: [B:0, D:27, F:0] + Bh

Default: 04h

7				4					0
0	0	0	0	0	0	1	0	0	
BCC									

Bit Range	Default & Access	Description
7:0	04h RO	BCC: Base Class Code

20.5.9 CLS—Offset Ch

Cache line size

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

CLS: [B:0, D:27, F:0] + Ch

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	
CLS									

Bit Range	Default & Access	Description
7:0	0h RW	CLS: Cache line size



20.5.10 LT—Offset Dh

Latency timer

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

LT: [B:0, D:27, F:0] + Dh

Default: 00h

7	4	0
0	0	0
LT		

Bit Range	Default & Access	Description
7:0	0h RO	LT: Latency timer

20.5.11 HTYPE—Offset Eh

Header type

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

HTYPE: [B:0, D:27, F:0] + Eh

Default: 00h

7	4	0
0	0	0
HTYPE		

Bit Range	Default & Access	Description
7:0	0h RO	HTYPE: Header type

20.5.12 BIST—Offset Fh

Built in self test. Not implemented.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

BIST: [B:0, D:27, F:0] + Fh

Default: 00h

7	4	0
0	0	0
BIST		

20.5.15 SVID—Offset 2Ch

subsystem vendor ID

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

SVID: [B:0, D:27, F:0] + 2Ch

Default: 0000h

15				12					8					4					0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
SVID																			

Bit Range	Default & Access	Description
15:0	0h RWO	SVID : subsystem vendor ID. This field is written by BIOS. No hardware action is taken according to this register

20.5.16 SID—Offset 2Eh

subsystem ID

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

SID: [B:0, D:27, F:0] + 2Eh

Default: 0000h

15				12					8					4					0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
SID																			

Bit Range	Default & Access	Description
15:0	0h RWO	SID: subsystem ID. This field is written by BIOS. No hardware action is taken according to this register

20.5.17 CAPPTR—Offset 34h

Capabilities pointer

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

CAPPTR: [B:0, D:27, F:0] + 34h

Default: 50h

7			4				0
0	1	0	1	0	0	0	0
CAPPTR							



Bit Range	Default & Access	Description
7:0	50h RO	CAPPTR: Capabilities pointer

20.5.18 INTLN—Offset 3Ch

Interrupt Line

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

INTLN: [B:0, D:27, F:0] + 3Ch

Default: 00h

7	4	0
0	0	0
INTLN		

Bit Range	Default & Access	Description
7:0	0h RW	INTLN: Interrupt Line

20.5.19 INTPN—Offset 3Dh

Interrupt Pin

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

INTPN: [B:0, D:27, F:0] + 3Dh

Default: 01h

7	4	0
0	0	1
Reserved		INTPN

Bit Range	Default & Access	Description
7:4	0h RO	Reserved: Reserved
3:0	1h RO	IP (INTPN): Interrupt Pin



20.5.20 AZCTL—Offset 40h

Azalia controller

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

AZCTL: [B:0, D:27, F:0] + 40h

Default: 01h

7				4					0
0	0	0	0	0	0	0	0	0	1
Reserved									AZ_AC97

Bit Range	Default & Access	Description
7:1	0h RO	Reserved: Reserved
0	1h RO	AZ_AC97# (AZ_AC97): This register is always 1'b1 indicating Azalia

20.5.21 IOBC—Offset 42h

IO Buffer control

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

IOBC: [B:0, D:27, F:0] + 42h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
Reserved_0			ASRC		Reserved_1	AVDDIS	MVSEL	VMODE	

Bit Range	Default & Access	Description
7:6	0h RO	Reserved_0: Reserved
5:4	0h RO	ASRC: Audio buffer slew rate control
3	0h RO	Reserved_1: Reserved
2	0h RO	AVDDIS: Automatic voltage detector disable
1	0h RO	MVSEL: Manual voltage select



Bit Range	Default & Access	Description
0	0h RO	VMODE: voltage mode

20.5.22 TM1—Offset 43h

Test mode 1

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

TM1: [B:0, D:27, F:0] + 43h

Default: 57h

7			4				0
0	1	0	1	0	1	1	1
RSVD	RSVD	RSVD	RSVD	HAPD	RSVD	RSVD	RSVD

Bit Range	Default & Access	Description
7	0h RO	Reserved (RSVD): Reserved.
6	1h RO	Reserved (RSVD): Reserved.
5	0h RO	Reserved (RSVD): Reserved.
4	1h RO	Reserved (RSVD): Reserved.
3	0h RWO	HAPD: HD Audio PCI/PCIe# device
2	1h RO	Reserved (RSVD): Reserved.
1	1h RO	Reserved (RSVD): Reserved.
0	1h RO	Reserved (RSVD): Reserved.

20.5.23 DCKCTL—Offset 4Ch

Docking control

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

DCKCTL: [B:0, D:27, F:0] + 4Ch

Default: 00h



7				4					0
0	0	0	0	0	0	0	0	0	0
Reserved									DA

Bit Range	Default & Access	Description
7:1	0h RO	Reserved: reserved
0	0h RW	DA: Dock attach

20.5.24 DCKSTS—Offset 4Dh

Docking status

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

DCKSTS: [B:0, D:27, F:0] + 4Dh

Default: 80h

7				4					0
1	0	0	0	0	0	0	0	0	0
DS	Reserved								DM

Bit Range	Default & Access	Description
7	1h RWO	DS: Docking support
6:1	0h RO	Reserved: reserved
0	0h RO	DM: Dock Mated

20.5.25 PID—Offset 50h

Power Management Capability ID

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

PID: [B:0, D:27, F:0] + 50h

Default: 6001h



15	12	8	4	0
0	1	1	0	0
0	0	0	0	0
0	0	0	0	1
NEXTCAP				CAPID

Bit Range	Default & Access	Description
15:8	60h RO	NEXTCAP: Next Capability.
7:0	01h RO	CAPID: Capability ID.

20.5.26 PC—Offset 52h

Power Management Capabilities

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

PC: [B:0, D:27, F:0] + 52h

Default: C842h

15	12	8	4	0
1	1	0	0	1
0	0	0	0	0
0	1	0	0	0
0	0	1	0	0
PMES	D2S	D1S	AC	DSI
				Reserved
				PMEC
				VS

Bit Range	Default & Access	Description
15:11	19h RO	PMES: PME_Support (PMES): Indicates PME# can be generated from D3 and D0 states.
10	0h RO	D2S: D2 state. Not supported.
9	0h RO	D1S: D1 state. Not supported.
8:6	1h RO	AC: Aux Current
5	0h RO	DSI: Device specific initialization
4	0h RO	Reserved: Reserved
3	0h RO	PMEC: PME Clock. Does not apply.
2:0	2h RO	VS: Version (VS): Indicates support for Revision 1.1 of the PCI Power Management Specification.



20.5.27 PCS—Offset 54h

Power Management control and status

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCS: [B:0, D:27, F:0] + 54h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DT	BPCCE	B23	Reserved_0	PMES	Reserved_1	PMEE	Reserved_2	PS

Bit Range	Default & Access	Description
31:24	0h RO	DT: Data. Does not apply.
23	0h RO	BPCCE: Bus power control enable. Does not apply.
22	0h RO	B23: Does not apply.
21:16	0h RO	Reserved_0: Reserved
15	0h RW1C	PMES: PME Status (PMES): This bit is set when the Intel HD Audio controller would normally assert the PME# signal independent of the state of the PME_En bit. This bit resides in the Suspend well. This bit is in the Suspend well and cleared on a power-on reset. Software must not make assumptions about the reset state of this bit and must set it appropriately.
14:9	0h RO	Reserved_1: Reserved
8	0h RW	PMEE: PME enable
7:2	0h RO	Reserved_2: reserved
1:0	0h RW	PS: Power State (PS): This field is used both to determine the current power state of the Intel HD Audio controller and to set a new power state. The values are: 00 D0 state 11 D3HOT state If software attempts to write a value of 10b or 01b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, the Intel HD Audio controllers configuration space is available, but the I/O and memory spaces are not. Additionally, interrupts are blocked. When software changes this value from the D3HOT state to the D0 state, an internal warm (soft) reset is generated, and software must re-initialize the function.

20.5.28 MID—Offset 60h

MSI Capability ID

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

MID: [B:0, D:27, F:0] + 60h

Default: 7005h



Access Method

PXID: [B:0, D:27, F:0] + 70h

15	12	8	4	0
0	0	0	0	0
0	0	0	1	0
0	0	0	0	0
NEXTCAP			CAPID	

20.5.34 PXC—Offset 72h

Access Method

PXC: [B:0, D:27, F:0] + 72h

15				12					8					4					0
0	0		0	0	0	0	0	0	0	1	0	0	1	0	0	0	0	1	
Reserved				IMN				SI	DPT				CV						

October 2018
Document Number: 538136, Rev. 4.3



20.5.35 DEVCAP—Offset 74h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

DEVCAP: [B:0, D:27, F:0] + 74h

Default: 10000000h

31	28	24	20	16	12	8	4	0
0	0	0	1	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED	RSVD	SPLS	SPLV	RESERVED1	PIP	AIP	ABP	L1CAP
								L0SCAP
								ETCAP
								PFCAP
								MPCAP

Bit Range	Default & Access	Description
31:29	0h RO	RESERVED: reserved
28	1h RO	Reserved (RSVD): Reserved.
27:26	0h RO	SPLS: Captured Slot Power Limit Scale
25:18	0h RO	SPLV: Captured Slot Power Limit Value
17:15	0h RO	RESERVED1: reserved
14	0h RO	PIP: Power Indicator Present
13	0h RO	AIP: Attention Indicator Present
12	0h RO	ABP: Attention Button Present
11:9	0h RWO	L1CAP: Endpoint L1 Acceptable Latency
8:6	0h RWO	L0SCAP: Endpoint L0s Acceptable Latency
5	0h RO	ETCAP: Extended Tag Field Support
4:3	0h RO	PFCAP: Phantom Functions Supported
2:0	0h RO	MPCAP: Max Payload Size Supported

20.5.36 DEVC—Offset 78h

Device control

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

DEVC: [B:0, D:27, F:0] + 78h



Default: 0800h

15		12		8				4				0			
0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0
RSVD	MRRS			NSNPEN	AUXPEN	PEEN	ETEN	MAXPAY			ROEN	URREN	FEREN	NFEREN	CEREN

Bit Range	Default & Access	Description
15	0h RO	Reserved (RSVD): Reserved.
14:12	0h RO	MRRS: Max read request size
11	1h RW	NSNPEN: Enable No Snoop
10	0h RO	AUXPEN: Auxiliary Power PM Enable
9	0h RO	PEEN: Phantom Functions Enable
8	0h RO	ETEN: Extended Tag Field Enable
7:5	0h RO	MAXPAY: Max Payload Size
4	0h RO	ROEN: Enable Relaxed Ordering
3	0h RW	URREN: Unsupported Request Reporting Enable
2	0h RW	FEREN: Fatal Error Reporting Enable
1	0h RW	NFEREN: Non-Fatal Error Reporting Enable
0	0h RW	CEREN: Correctable Error Reporting Enable

20.5.37 DEVS—Offset 7Ah

Device status

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

DEVS: [B:0, D:27, F:0] + 7Ah

Default: 0010h

15				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0				
RESERVED										TXP	AUXDET	URDET	FEDET	NFEDET	CEDET				



Bit Range	Default & Access	Description
15:6	0h RO	RESERVED: RESERVED
5	0h RO	TXP: Transactions Pending
4	1h RO	AUXDET: AUX Power Detected
3	0h RO	URDET: Unsupported Request Detected
2	0h RO	FEDET: Fatal Error Detected
1	0h RO	NFEDET: Non-Fatal Error Detected
0	0h RO	CEDET: Correctable Error Detected

20.5.38 MANID—Offset F8h

Manufacturer ID

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MANID: [B:0, D:27, F:0] + F8h

Default: 00000F00h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	0	0	0	0	0	0	0				
RESERVED				DPID				SID				MNFR				PPID																			

Bit Range	Default & Access	Description
31:28	0h RO	RESERVED: RESERVED
27:24	0h RO	DPID: Dot Portion Process ID
23:16	0h RO	SID: Stepping ID
15:8	0Fh RO	MNFR: Manufacturer
7:0	0h RO	PPID: Process Portion Process ID



20.5.39 VCCAP—Offset 100h

Virtual Channel Cap Header

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

VCCAP: [B:0, D:27, F:0] + 100h

Default: 13010002h

31	28	24	20	16	12	8	4	0										
0	0	0	1	0	0	1	1	0	0	0	0	0	0	0	0	0	1	0
NXTCAP								CV	PCIECID									

Bit Range	Default & Access	Description
31:20	130h RWO	NXTCAP: Next Capability Offset (NXTCAP): Points to the next capability header, which is the Root Complex Link Declaration Enhanced Capability Header. This register is RWO to support removing the Root Complex Topology Capability from the PCI Express Extended Capability List. For systems which support the Root Complex Topology Capability Structure, boot BIOS should write a 130h to this register, otherwise boot BIOS should write a 000h to this register.
19:16	1h RWO	CV: Capability Version (CV): This register is RWO to support removing the PCI Express Extended Capabilities from Azalia. For systems which support the PCI Express Virtual Channel capability and the Root Complex Topology Capability Structure, boot BIOS should write a 1h to this register, otherwise boot BIOS should write a 0h to this register.
15:0	2h RWO	PCIECID: PCI Express Extended Capability ID (PCIECID): This register is RWO to support removing the PCI Express Extended Capabilities from Azalia. For systems which support the PCI Express Virtual Channel capability and the Root Complex Topology Capability Structure, boot BIOS should write a 0002h to this register, otherwise boot BIOS should write a 0000h to this register.

20.5.40 PVCCAP1—Offset 104h

Port VC Capability

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PVCCAP1: [B:0, D:27, F:0] + 104h

Default: 00000001h

31	28	24	20	16	12	8	4	0									
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
RESERVED												PARBTBLES	RC	RESERVED1	LPVCCNT	RESERVED2	VCCNT

Bit Range	Default & Access	Description
31:12	0h RO	RESERVED: RESERVED



Bit Range	Default & Access	Description
11:10	0h RO	PARBTBLES: Port Arbitration Table Entry Size
9:8	0h RO	RC: Reference Clock
7	0h RO	RESERVED1: RESERVED
6:4	0h RO	LPVCCNT: Low Priority Extended VC Count
3	0h RO	RESERVED2: RESERVED
2:0	1h RO	VCCNT: Extended VC Count

20.5.41 PVCCAP2—Offset 108h

Port VC Capability 2

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PVCCAP2: [B:0, D:27, F:0] + 108h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
VCARBTBL				RESERVED			VCARBCAP	

Bit Range	Default & Access	Description
31:24	0h RO	VCARBTBL: VC Arbitration Table Offset
23:8	0h RO	RESERVED: RESERVED
7:0	0h RO	VCARBCAP: VC Arbitration Capability

20.5.42 PVCCTL—Offset 10Ch

Port VC Control

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

PVCCTL: [B:0, D:27, F:0] + 10Ch

Default: 0000h



Bit Range	Default & Access	Description
15:4	0h RO	RESERVED: RESERVED
3:1	0h RO	VCARBSEL: VC Arbitration Select
0	0h RO	LVCARBTBL: Load VC Arbitration Table

20.5.43 PVCSTS—Offset 10Eh

Access Method

PVCSTS: [B:0, D:27, F:0] + 10Eh

Bit Range	Default & Access	Description
15:1	0h RO	RESERVED: RESERVED
0	0h RO	VCARBTLSTS: VC Arbitration Table Status

20.5.44 VC0CAP—Offset 110h

Access Method

VC0CAP: [B:0, D:27, F:0] + 110h

October 2018
Document Number: 538136, Rev. 4.3



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	PARBTBL	RESERVED	MTS	RST	APS	RESERVED1	PARBCAP	

Bit Range	Default & Access	Description
31:24	0h RO	PARBTBL: Port Arbitration Table Offset
23	0h RO	RESERVED: RESERVED
22:16	0h RO	MTS: Maximum Time Slots
15	0h RO	RST: Reject Snoop Transactions
14	0h RO	APS: Advanced Packet Switching
13:8	0h RO	RESERVED1: RESERVED
7:0	0h RO	PARBCAP: Port Arbitration Capability

20.5.45 VC0CTL—Offset 114h

VC0 Resource Control

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

VC0CTL: [B:0, D:27, F:0] + 114h

Default: 800000FFh

31	28	24	20	16	12	8	4	0
1	0	0	0	0	0	0	0	1
VC0EN	RESERVED	VC0ID	RESERVED1	PARBSEL	LPARBTBL	RESERVED2	VC0MAP	VC0MAP0

Bit Range	Default & Access	Description
31	1h RO	VC0EN: VC0 Enable
30:27	0h RO	RESERVED: RESERVED
26:24	0h RO	VC0ID: VC0 ID



VC0 Resource Status

Type: PCI Configuration Register
(Size: 16 bits)

VCOSTS: [B:0, D:27, F:0] + 11Ah

15	12			8			4			0			
0	0	0	0	0	0	0	0	0	0	0	0	0	
RESERVED											VCNP		PARBTBLSTS

20.5.47 VCICAP—Offset 11Ch

VCi Resource Capabilities

Type: PCI Configuration Register
(Size: 32 bits)

VCICAP: [B:0, D:27, F:0] + 11Ch

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
	PARBTBL	RESERVED	MTS	RST	APS	RESERVED1	PARBCAP	

Bit Range	Default & Access	Description
31:24	0h RO	PARBTBL: Port Arbitration Table Offset
23	0h RO	RESERVED: RESERVED
22:16	0h RO	MTS: Maximum Time Slots
15	0h RO	RST: Reject Snoop Transactions
14	0h RO	APS: Advanced Packet Switching
13:8	0h RO	RESERVED1: RESERVED
7:0	0h RO	PARBCAP: Port Arbitration Capability

20.5.48 VCICTL—Offset 120h

VCi control register

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

VCICTL: [B:0, D:27, F:0] + 120h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
VCiEN	Reserved_0	VCiID	Reserved_1	PARBSEL	LPARBTL	Reserved_2	VCiM	VCiM0

Bit Range	Default & Access	Description
31	0h RW	VCiEN: VCi Enable
30:27	0h RO	Reserved_0: Reserved
26:24	0h RW	VCiID: VCi ID
23:20	0h RO	Reserved_1: Reserved



VCi Resource Status

Type: PCI Configuration Register
(Size: 16 bits)

VCISTS: [B:0, D:27, F:0] + 126h

15	12	8	4	0
0	0	0	0	0
RESERVED				VCNP
				PARBTBLSTS

20.5.50 RCCAP—Offset 130h

Root Complex Link Declaration Capability Header

Type: PCI Configuration Register
(Size: 32 bits)

RCCAP: [B:0, D:27, F:0] + 130h

Default: 00010005h



20.5.52 L1DESC—Offset 140h

Link 1 Description

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

L1DESC: [B:0, D:27, F:0] + 140h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
TPORT				TCOMPID				LNKTYP LNKVLD

Bit Range	Default & Access	Description
31:24	0h RO	TPORT: Target Port Number
23:16	0h RO	TCOMPID: Target Component ID
15:2	0h RO	RESERVED: RESERVED
1	0h RO	LNKTYP: Link Type
0	1h RO	LNKVLD: Link Valid

20.5.53 L1LADD—Offset 148h

Link 1 Lower Address

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

L1LADD: [B:0, D:27, F:0] + 148h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
L1LADD						RESERVED		

Bit Range	Default & Access	Description
31:14	0h RO	L1LADD: Link 1 Lower Address
13:0	0h RO	RESERVED: RESERVED



20.6 HD Audio Memory Mapped I/O Registers

Table 225. Summary of HD Audio Memory Mapped I/O Registers—AZLBAR

Offset	Size	Register ID—Description	Default Value
0h	2	"GCAP—Offset 0h" on page 2713	4401h
2h	1	"VMIN—Offset 2h" on page 2714	00h
3h	1	"VMAJ—Offset 3h" on page 2714	01h
4h	2	"OUTPAY—Offset 4h" on page 2715	003Ch
6h	2	"INPAY—Offset 6h" on page 2715	001Dh
8h	4	"GCTL—Offset 8h" on page 2716	00000000h
Ch	1	"WAKEEN—Offset Ch" on page 2718	00h
Eh	1	"WAKESTS—Offset Eh" on page 2719	00h
10h	2	"GSTS—Offset 10h" on page 2719	0000h
18h	2	"OUTSTRMPAY—Offset 18h" on page 2720	0030h
1Ah	2	"INSTRMPAY—Offset 1Ah" on page 2721	0018h
20h	4	"INTCTL—Offset 20h" on page 2722	00000000h
24h	4	"INTSTS—Offset 24h" on page 2723	00000000h
30h	4	"WALCLK—Offset 30h" on page 2724	00000000h
38h	4	"SSYNC—Offset 38h" on page 2725	00000000h
40h	4	"CORBLBASE—Offset 40h" on page 2726	00000000h
44h	4	"CORBUBASE—Offset 44h" on page 2726	00000000h
48h	2	"CORBWP—Offset 48h" on page 2727	0000h
4Ah	2	"CORBRP—Offset 4Ah" on page 2728	0000h
4Ch	1	"CORBCTL—Offset 4Ch" on page 2728	00h
4Dh	1	"CORBSTS—Offset 4Dh" on page 2729	00h
4Eh	1	"CORBSIZE—Offset 4Eh" on page 2730	42h
50h	4	"RIRBLBASE—Offset 50h" on page 2731	00000000h
54h	4	"RIRBUBASE—Offset 54h" on page 2732	00000000h
58h	2	"RIRBWP—Offset 58h" on page 2733	0000h
5Ah	2	"RINTCNT—Offset 5Ah" on page 2734	0000h
5Ch	1	"RIRBCTL—Offset 5Ch" on page 2735	00h
5Dh	1	"RIRBSTS—Offset 5Dh" on page 2736	00h
5Eh	1	"RIRBSIZE—Offset 5Eh" on page 2737	42h
60h	4	"IC—Offset 60h" on page 2737	00000000h
64h	4	"IR—Offset 64h" on page 2738	00000000h
68h	2	"ICS—Offset 68h" on page 2739	0000h
70h	4	"DPLBASE—Offset 70h" on page 2739	00000000h
74h	4	"DPUBASE—Offset 74h" on page 2741	00000000h
80h	4	"ISD0CTL_STS—Offset 80h" on page 2742	00040000h
84h	4	"ISD0LPB—Offset 84h" on page 2743	00000000h



Table 225. Summary of HD Audio Memory Mapped I/O Registers—AZLBAR (Continued)

Offset	Size	Register ID—Description	Default Value
88h	4	"ISD0CBL—Offset 88h" on page 2744	00000000h
8Ch	2	"ISD0LVI—Offset 8Ch" on page 2745	0000h
8Eh	2	"ISD0FIFOW—Offset 8Eh" on page 2746	0004h
90h	2	"ISD0FIFOS—Offset 90h" on page 2746	0000h
92h	2	"ISD0FMT—Offset 92h" on page 2747	0000h
98h	4	"ISD0BDLPLBA—Offset 98h" on page 2748	00000000h
9Ch	4	"ISD0BDLPUBA—Offset 9Ch" on page 2749	00000000h
A0h	4	"ISD1CTL_STS—Offset A0h" on page 2750	00040000h
A4h	4	"ISD1LPIB—Offset A4h" on page 2751	00000000h
A8h	4	"ISD1CBL—Offset A8h" on page 2752	00000000h
ACh	2	"ISD1LVI—Offset ACh" on page 2753	0000h
AEh	2	"ISD1FIFOW—Offset AEh" on page 2753	0004h
B0h	2	"ISD1FIFOS—Offset B0h" on page 2754	0000h
B2h	2	"ISD1FMT—Offset B2h" on page 2754	0000h
B8h	4	"ISD1BDLPLBA—Offset B8h" on page 2755	00000000h
BCh	4	"ISD1BDLPUBA—Offset BCh" on page 2756	00000000h
C0h	4	"ISD2CTL_STS—Offset C0h" on page 2757	00040000h
C4h	4	"ISD2LPIB—Offset C4h" on page 2759	00000000h
C8h	4	"ISD2CBL—Offset C8h" on page 2760	00000000h
CCh	2	"ISD2LVI—Offset CCh" on page 2760	0000h
CEh	2	"ISD2FIFOW—Offset CEh" on page 2761	0004h
D0h	2	"ISD2FIFOS—Offset D0h" on page 2761	0000h
D2h	2	"ISD2FMT—Offset D2h" on page 2762	0000h
D8h	4	"ISD2BDLPLBA—Offset D8h" on page 2763	00000000h
DCh	4	"ISD2BDLPUBA—Offset DCh" on page 2764	00000000h
E0h	4	"ISD3CTL_STS—Offset E0h" on page 2765	00040000h
E4h	4	"ISD3LPIB—Offset E4h" on page 2766	00000000h
E8h	4	"ISD3CBL—Offset E8h" on page 2767	00000000h
ECh	2	"ISD3LVI—Offset ECh" on page 2768	0000h
EEh	2	"ISD3FIFOW—Offset EEh" on page 2768	0004h
F0h	2	"ISD3FIFOS—Offset F0h" on page 2769	0000h
F2h	2	"ISD3FMT—Offset F2h" on page 2769	0000h
F8h	4	"ISD3BDLPLBA—Offset F8h" on page 2770	00000000h
FCh	4	"ISD3BDLPUBA—Offset FCh" on page 2771	00000000h
100h	4	"OSD0CTL_STS—Offset 100h" on page 2772	00040000h
104h	4	"OSD0LPIB—Offset 104h" on page 2774	00000000h
108h	4	"OSD0CBL—Offset 108h" on page 2775	00000000h
10Ch	2	"OSD0LVI—Offset 10Ch" on page 2775	0000h
10Eh	2	"OSD0FIFOW—Offset 10Eh" on page 2776	0004h



Table 225. Summary of HD Audio Memory Mapped I/O Registers—AZLBAR (Continued)

Offset	Size	Register ID—Description	Default Value
110h	2	"OSD0FIFOS—Offset 110h" on page 2776	0000h
112h	2	"OSD0FMT—Offset 112h" on page 2777	0000h
118h	4	"OSD0BDLPLBA—Offset 118h" on page 2778	00000000h
11Ch	4	"OSD0BDLPUBA—Offset 11Ch" on page 2779	00000000h
120h	4	"OSD1CTL_STS—Offset 120h" on page 2780	00040000h
124h	4	"OSD1LPIB—Offset 124h" on page 2781	00000000h
128h	4	"OSD1CBL—Offset 128h" on page 2782	00000000h
12Ch	2	"OSD1LVI—Offset 12Ch" on page 2783	0000h
12Eh	2	"OSD1FIFOW—Offset 12Eh" on page 2783	0004h
130h	2	"OSD1FIFOS—Offset 130h" on page 2784	0000h
132h	2	"OSD1FMT—Offset 132h" on page 2784	0000h
138h	4	"OSD1BDLPLBA—Offset 138h" on page 2785	00000000h
13Ch	4	"OSD1BDLPUBA—Offset 13Ch" on page 2786	00000000h
140h	4	"OSD2CTL_STS—Offset 140h" on page 2787	00040000h
144h	4	"OSD2LPIB—Offset 144h" on page 2789	00000000h
148h	4	"OSD2CBL—Offset 148h" on page 2790	00000000h
14Ch	2	"OSD2LVI—Offset 14Ch" on page 2790	0000h
14Eh	2	"OSD2FIFOW—Offset 14Eh" on page 2791	0004h
150h	2	"OSD2FIFOS—Offset 150h" on page 2792	0000h
152h	2	"OSD2FMT—Offset 152h" on page 2792	0000h
158h	4	"OSD2BDLPLBA—Offset 158h" on page 2793	00000000h
15Ch	4	"OSD2BDLPUBA—Offset 15Ch" on page 2794	00000000h
160h	4	"OSD3CTL_STS—Offset 160h" on page 2795	00040000h
164h	4	"OSD3LPIB—Offset 164h" on page 2797	00000000h
168h	4	"OSD3CBL—Offset 168h" on page 2798	00000000h
16Ch	2	"OSD3LVI—Offset 16Ch" on page 2799	0000h
16Eh	2	"OSD3FIFOW—Offset 16Eh" on page 2799	0004h
170h	2	"OSD3FIFOS—Offset 170h" on page 2800	0000h
172h	2	"OSD3FMT—Offset 172h" on page 2801	0000h
178h	4	"OSD3BDLPLBA—Offset 178h" on page 2802	00000000h
17Ch	4	"OSD3BDLPUBA—Offset 17Ch" on page 2803	00000000h
2030h	4	"WLCLKA—Offset 2030h" on page 2803	00000000h
2084h	4	"ISD0LPIBA—Offset 2084h" on page 2804	00000000h
20A4h	4	"ISD1LPIBA—Offset 20A4h" on page 2805	00000000h
20C4h	4	"ISD2LPIBA—Offset 20C4h" on page 2805	00000000h
20E4h	4	"ISD3LPIBA—Offset 20E4h" on page 2806	00000000h
2104h	4	"OSD0LPIBA—Offset 2104h" on page 2807	00000000h



Bit Range	Default & Access	Description
0	01h RW	BIT_ADDRESS_SUPPORTED: A 1 indicates that the Intel HD Audio controller supports 64 bit addressing for BDL addresses data buffer addresses and command buffer addresses.

20.6.2 VMIN—Offset 2h

Minor Version

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

VMIN: [AZLBAR] + 2h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00h

7	4	0
0	0	0
MINOR_VERSION		

Bit Range	Default & Access	Description
7:0	00h RO	MINOR_VERSION: Indicates SoC supports minor revision number 00h of the Intel HD Audio specification.

20.6.3 VMAJ—Offset 3h

Major Version

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

VMAJ: [AZLBAR] + 3h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 01h

7	4	0
0	0	1
MAJOR_VERSION		



Bit Range	Default & Access	Description
7:0	01h RO	MAJOR_VERSION: Indicates SoC supports major revision number 1 of the Intel HD Audio specification.

20.6.4 OUTPAY—Offset 4h

Output Payload Capability

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

OUTPAY: [AZLBAR] + 4h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 003Ch


15			12				8				4			0
0	0	0	0	0	0	0	0	0	0	1	1	1	1	0
OUTPUT_PAYLOAD_CAPABILITY														

Bit Range	Default & Access	Description
15:0	003Ch RO	OUTPUT_PAYLOAD_CAPABILITY: Indicates the total output payload available on the link. This does not include bandwidth used for command and control. This measurement is in 16 bit word quantities per 48 kHz frame. The default link clock speed of 24.000 MHz the data is double pumped provides 1000 bits per frame or 62.5 words in total. 40 bits are used for command and control leaving 60 words available for data payload. 00h 0 words 01h 1 word payload FFh 255h word payload

20.6.5 INPAY—Offset 6h



Bit Range	Default & Access	Description
15:0	001Dh RO	INPUT_PAYLOAD_CAPABILITY: Indicates the total input payload available on the link. This does not include bandwidth used for response. This measurement is in 16 bit word quantities per 48 kHz frame. The default link clock speed of 24.000 MHz provides 500 bits per frame or 31.25 words in total. 36 bits are used for response leaving 29 words for data payload. 00h 0 words 01h 1 word payload FFh 255h word payload



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED0						ACCEPT_UNSOLICITED_RESPONSE_ENABLE	RESERVED1	FLUSH_CONTROL CONTROLLER_RESET

Bit Range	Default & Access	Description
31:9	0h RO	RESERVED0: reserved
8	0h RW	ACCEPT_UNSOLICITED_RESPONSE_ENABLE: If UNSOL is a 1 Unsolicited Responses from the codecs are accepted by the controller and placed into the Response Input Ring Buffer. If UNSOL is a 0 unsolicited responses are not accepted and dropped on the floor.
7:2	00h RO	RESERVED1: reserved
1	0h RW	FLUSH_CONTROL: Writing a 1 to this bit initiates a flush. When the flush completion is received by the controller hardware sets the Flush Status bit and clears this Flush Control bit. Before a flush cycle is initiated the DMA Position Buffer must be programmed with a valid memory address by software but the DMA Position Buffer bit 0 need not be set to enable the position reporting mechanism. Also all streams must be stopped the associated RUN bit must be 0 . When the flush is initiated the controller will flush pipelines to memory to guarantee that the hardware is ready to transition to a D3 state. Setting this bit is not a critical step in the power state transition if the content of the FIFOs is not critical.
0	0h RW	CONTROLLER_RESET: Writing a 0 to this bit causes the Intel HD Audio controller to be reset. All state machines FIFO s and non Suspend well memory mapped configuration registers except ECAP and PCI Configuration Registers in the controller will be reset. The Intel HD Audio link RESET signal will be asserted and all other link signals will be driven to their reset values. After the hardware has completed sequencing into the reset state it will report a 0 in this bit. Software must read a 0 from this bit to verify that the controller is in reset. Writing a 1 to this bit causes the controller to exit its reset state and de assert the Intel HD Audio link RESET signal. Software is responsible for setting clearing this bit such that the minimum Intel HD Audio link RESET signal assertion pulse width specification is met. When the controller hardware is ready to begin operation it will report a 1 in this bit. Software must read a 1 from this bit before accessing any controller registers. The CRST bit defaults to a 0 after hardware reset therefore software needs to write a 1 to this bit to begin operation. Note that the CORB RIRB RUN bits and all Stream RUN bits must be verified cleared to zero before CRST is written to 0 asserted in order to assure a clean re start. When setting or clearing CRST software must ensure that minimum link timing requirements minimum RESET assertion time etc. are met. When CRST is 0 indicating that the controller is in reset writes to all Intel HD Audio memory mapped registers are ignored as if the device is not present. The only exception is the Global Control register containing the CRST bit itself. The Global Control register is write able as a DWord Word or Byte even when CRST is 0 if the byte enable for the byte containing the CRST bit Byte Enable 0 is active. If Byte Enable 0 is not active writes to the Global Control register will be ignored when CRST is 0. When CRST is 0 reads to Intel HD Audio memory mapped registers will return their default value except for registers that are not reset with PLTRST or on a D3hot to D0 transition.



20.6.7 WAKEEN—Offset Ch

Wake Enable

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

WAKEEN: [AZLBAR] + Ch

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00h

7	4	0
0	0	0
RESERVED0		SDIN_WAKE_ENABLE_FLAGS

Bit Range	Default & Access	Description
7:4	0h RO	RESERVED0: reserved
3:0	0h RW	SDIN_WAKE_ENABLE_FLAGS: Bits which control which SDI signal s may generate a wake event. A 1 bit in the bit mask indicates that the associated SDIN signal is enabled to generate a wake.



20.6.8 WAKESTS—Offset Eh

Wake Status

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

WAKESTS: [AZLBAR] + Eh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
RESERVED0					SDIN_STATE				

Bit Range	Default & Access	Description
7:4	0h RO	RESERVED0: reserved
3:0	0h RO	SDIN_STATE: Flag bits that indicate which SDI signal s received a State Change event. The bits are cleared by writing 1 s to them.

20.6.9 GSTS—Offset 10h

Global Status

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

GSTS: [AZLBAR] + 10h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

15				12					8					4					0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
RESERVED0																FLUSH_STATUS		RESERVED1	

Bit Range	Default & Access	Description
15:2	0000h RO	RESERVED0: reserved
1	0h RW	FLUSH_STATUS: This bit is set to a 1 by the hardware to indicate that the flush cycle initiated when the FCNTRL bit was set has completed. Software must write a 1to clear this bit before the next time FCNTRL is set.

20.6.11 INSTRMPAY—Offset 1Ah

Input Stream Payload Capability

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

INSTRMPAY: [AZLBAR] + 1Ah**AZLBAR Type:** PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0018h

15	12			8			4			0					
0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0
INPUT_STREAM_PAYLOAD_CAPABILITY															

Bit Range	Default & Access	Description
15:0	0018h RO	INPUT_STREAM_PAYLOAD_CAPABILITY: Indicates maximum number of words per frame for any single input stream. This measurement is in 16 bit word quantities per 48 kHz frame. 24 Words 48B is the maximum supported therefore a value of 18h is reported in this register. Software must ensure that a format which would cause more words per frame than indicated is not programmed into the Input Stream Descriptor register. 00h 0 words 01h 1 word payload FFh 255h word payload



20.6.12 INTCTL—Offset 20h

Interrupt Control

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

INTCTL: [AZLBAR] + 20h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
GLOBAL_INTERRUPT_ENABLE	RESERVED0						STREAM_INTERRUPT_ENABLE	
CONTROLLER_INTERRUPT_ENABLE								

Bit Range	Default & Access	Description
31	0h RW	GLOBAL_INTERRUPT_ENABLE: Global bit to enable device interrupt generation. When set to 1 the Intel HD Audio function is enabled to generate an interrupt. This control is in addition to any bits in the bus specific address space such as the Interrupt Enable bit in the PCI Configuration Space. This bit is not affected by controller reset.
30	0h RW	CONTROLLER_INTERRUPT_ENABLE: Enables the general interrupt for controller functions. When set to 1 and GIE is enabled the controller generates an interrupt when the CIS bit gets set. This bit is not affected by controller reset.
29:8	0h RO	RESERVED0: reserved
7:0	00h RW	STREAM_INTERRUPT_ENABLE: When set to 1 the individual Streams are enabled to generate an interrupt when the corresponding stream status bits get set. A stream interrupt will be caused as a result of a buffer with IOC 1 in the BDL entry being completed or as a result of a FIFO error underrun or overrun occurring. Control over the generation of each of these sources is in the associated Stream Descriptor. The streams are numbered and the SIE bits assigned sequentially based on their order in the register set. Bit 0 Input Stream 1 Bit 1 Input Stream 2 Bit 2 Input Stream 3 Bit 3 Input Stream 4 Bit 4 Output Stream 1 Bit 5 Output Stream 2 Bit 6 Output Stream 3 Bit 7 Output Stream 4



20.6.14 WALCLK—Offset 30h

Wall Clock Counter

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

WALCLK: [AZLBAR] + 30h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

WALL_CLOCK_COUNTER

Bit Range	Default & Access	Description
31:0	0h RO	WALL_CLOCK_COUNTER: 32 bit counter that is incremented on each link BCLK period and rolls over from FFFF_FFFFh to 0000_0000h. This counter will roll over to zero with a period of approximately 179 seconds. This counter is enabled while the BCLK bit is set to 1. Software uses this counter to synchronize between multiple controllers. Will be reset on controller reset.

20.6.15 SSYNC—Offset 38h

Stream Synchronization

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSYNC: [AZLBAR] + 38h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED0								STREAM_SYNCHRONIZATION_BITS

Bit Range	Default & Access	Description
31:8	0h RO	RESERVED0: reserved
7:0	00h RW	STREAM_SYNCHRONIZATION_BITS: The Stream Synchronization bits when set to 1 block data from being sent on or received from the link. Each bit controls the associated Stream Descriptor bit 0 corresponds to the first Stream Descriptor etc. To synchronously start a set of DMA engines the bits in the SSYNC register are first set to a 1. The RUN bits for the associated Stream Descriptors are then set to a 1 to start the DMA engines. When all streams are ready FIFORDY 1 the associated SSYNC bits can all be set to 0 at the same time and transmission or reception of bits to or from the link will begin together at the start of the next full link frame. To synchronously stop streams first the bits are set in the SSYNC register and then the individual RUN bits in the Stream Descriptors are cleared by software. The streams are numbered and the SSYNC bits assigned sequentially based on their order in the register set. Bit 0 Input Stream 1 Bit 1 Input Stream 2 Bit 2 Input Stream 3 Bit 3 Input Stream 4 Bit 4 Output Stream 1 Bit 5 Output Stream 2 Bit 6 Output Stream 3 Bit 7 Output Stream 4 Each bit can be reset by their respective stream reset.



Access Method

CORBLBASE: [AZLBAR] + 40h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:7	0h RW	CORB_LOWER_BASE_ADDRESS: Lower address of the Command Output Ring Buffer allowing the CORB Base Address to be assigned on any 64 B boundary. This register field must not be written when the DMA engine is running or the DMA transfer may be corrupted.
6:0	00h RO	CORB_LOWER_BASE_UNIMPLEMENTED_BITS: Hardwired to 0. This requires the CORB to be allocated with 128 byte granularity to allow for cache line fetch optimizations.

20.6.17 CORBUBASE—Offset 44h

Access Method

CORBUBASE: [AZLBAR] + 44h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

20.6.18 CORBWP—Offset 48h



20.6.19 CORBRP—Offset 4Ah

CORB Read Pointer

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

CORBRP: [AZLBAR] + 4Ah

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
CORB_READ_POINTER_RESET	RESERVED0		CORB_READ_POINTER	

Bit Range	Default & Access	Description
15	0h RW	CORB_READ_POINTER_RESET: Software writes a 1 to this bit to reset the CORB Read Pointer to 0 and clear any residual pre fetched commands in the CORB hardware buffer within the Intel Audio controller. The hardware will physically update this bit to 1 when the CORB Pointer reset is complete. Software must read a 1 to verify that the reset completed correctly. Software must clear this bit back to 0 and read back the 0 to verify that the clear completed correctly. The CORB DMA engine must be stopped prior to resetting the Read Pointer or else DMA transfer may be corrupted.
14:8	00h RO	RESERVED0: reserved
7:0	00h RO	CORB_READ_POINTER: Software reads this field to determine how many commands it can write to the CORB without over running. The value read indicates the CORB Read Pointer offset in Dword granularity. The offset entry read from this field has been successfully fetched by the DMA controller and may be over written by software. Supports 256 CORB entries 256 x 4B 1KB . This field may be read while the DMA engine is running.

20.6.20 CORBCTL—Offset 4Ch

CORB Control

Access Method


Type: Memory Mapped I/O Register
(Size: 8 bits)

CORBCTL: [AZLBAR] + 4Ch

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00h



Bit Range	Default & Access	Description
7:2	00h RO	RESERVED0: reserved
1	0h RW	ENABLE_CORB_DMA_ENGINE: 0 DMA Stop 1 DMA Run After SW writes a 0 to this bit the HW may not stop immediately. The hardware will physically update the bit to a 0 when the DMA engine is truly stopped. SW must read a 0 from this bit to verify that the DMA is truly stopped.
0	0h RW	CORB_MEMORY_ERROR_INTERRUPT_ENABLE: If this bit is set and GIE and CIE are enabled the controller will generate an interrupt if the MEI status bit is set.

20.6.21 CORBSTS—Offset 4Dh

CORB Status

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

CORBSTS: [AZLBAR] + 4Dh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00h



7	4	0
0	0	0
RESERVED0		CORB_MEMORY_ERROR_INDICATION

Bit Range	Default & Access	Description
7:1	00h RO	RESERVED0: reserved
0	0h RW	CORB_MEMORY_ERROR_INDICATION: If this status bit is set the controller has detected an error in the pathway between the controller and memory. This may be an ECC bit error or any other type of detectable data error which renders the command data fetched invalid. Software can clear this bit by writing a 1 to it. However this type of error leaves the audio subsystem in an unviable state and typically requires CRST .

20.6.22 CORBSIZE—Offset 4Eh

CORB Size

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

CORBSIZE: [AZLBAR] + 4Eh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 42h

7	4	0
0	1	0
CORB_SIZE_CAPABILITY		RESERVED0
		CORB_SIZE

Bit Range	Default & Access	Description
7:4	4h RO	CORB_SIZE_CAPABILITY: 0100b indicates that the HD Audio controller only supports a CORB size of 256 CORB entries 1024B .



Bit Range	Default & Access	Description
3:2	0h RO	RESERVED0: reserved
1:0	02h RO	CORB_SIZE: Hardwired to 10b which sets the CORB size to 256 entries 1024B .

20.6.23 RIRBLBASE—Offset 50h

RIRB Lower Base Address

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RIRBLBASE: [AZLBAR] + 50h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RIRB_LOWER_BASE_ADDRESS								RIRB_LOWER_BASE_UNIMPLEMENTED_BITS

Bit Range	Default & Access	Description
31:7	0h RW	RIRB_LOWER_BASE_ADDRESS: Lower address of the Response Input Ring Buffer allowing the RIRB Base Address to be assigned on any 64 B boundary. This register field must not be written when the DMA engine is running or the DMA transfer may be corrupted.
6:0	00h RO	RIRB_LOWER_BASE_UNIMPLEMENTED_BITS: Hardwired to 0 to force 128 byte buffer alignment for cache line fetch optimizations.



20.6.25 RIRBWP—Offset 58h

RIRB Write Pointer

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

RIRBWP: [AZLBAR] + 58h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
RIRB_WRITE_POINTER_RESET	RESERVED0		RIRB_WRITE_POINTER	

Bit Range	Default & Access	Description
15	0h WO	RIRB_WRITE_POINTER_RESET: Software writes a 1 to this bit to reset the RIRB Write Pointer to 0 s. The RIRB DMA engine must be stopped prior to resetting the Write Pointer or else DMA transfer may be corrupted. This bit will always be read as 0.
14:8	00h RO	RESERVED0: reserved
7:0	00h RO	RIRB_WRITE_POINTER: Indicates the last valid RIRB entry written by the DMA controller. Software reads this field to determine how many responses it can read from the RIRB. The value read indicates the RIRB Write Pointer offset in 2 Dword RIRB entry units since each RIRB entry is 2 Dwords long . Supports up to 256 RIRB entries 256 x 8B 2KB . This field may be read while the DMA engine is running.



Access Method

RINTCNT: [AZLBAR] + 5Ah

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

Bit Range	Default & Access	Description
15:8	00h RO	RESERVED0: reserved
7:0	00h RW	N_RESPONSE_INTERRUPT_COUNT: 0000_0001b 1 Response sent to RIRB 1111_1111b 255 Responses sent to RIRB 0000_0000b 256 Responses sent to RIRB The DMA engine should be stopped when changing this field or else an interrupt may be lost. Note that each Response occupies 2 Dwords in the RIRB. This is compared to the total number of responses that have been returned as opposed to the number of frames in which there were responses. If more than one codec responds in one frame then the count is increased by the number of responses received in the frame.



20.6.27 RIRBCTL—Offset 5Ch

RIRB Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

RIRBCTL: [AZLBAR] + 5Ch

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
RESERVED0				RESPONSE_OVERRUN_INTERRUPT_CONTROL		RIRB_DMA_ENABLE	RESPONSE_INTERRUPT_CONTROL

Bit Range	Default & Access	Description
7:3	00h RO	RESERVED0: reserved
2	0h RW	RESPONSE_OVERRUN_INTERRUPT_CONTROL: If this bit is set and GIE and CIE are enabled the hardware will generate an interrupt when the Response Overrun Interrupt Status bit is set.
1	0h RW	RIRB_DMA_ENABLE: 0 DMA Stop 1 DMA Run After SW writes a 0 to this bit the HW may not stop immediately. The hardware will physically update the bit to a 0 when the DMA engine is truly stopped. SW must read a 0 from this bit to verify that the DMA is truly stopped.
0	0h RW	RESPONSE_INTERRUPT_CONTROL: 0 Disable Interrupt 1 Generate an interrupt if GIE and CIE are enabled after N number of Responses are sent to the RIRB buffer OR when an empty Response slot is encountered on all SDI_x inputs whichever occurs first . The N counter is reset when the interrupt is generated.



20.6.28 RIRBSTS—Offset 5Dh

RIRB Status

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

RIRBSTS: [AZLBAR] + 5Dh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00h

7	4	0
0	0	0
RESERVED0		RESPONSE_OVERRUN_INTERRUPT_STATUS
		RESPERVED1
		RESPONSE_INTERRUPT

Bit Range	Default & Access	Description
7:3	00h RO	RESERVED0: reserved
2	0h RW	RESPONSE_OVERRUN_INTERRUPT_STATUS: Hardware sets this bit to a 1 when the RIRB DMA engine is not able to write the incoming responses to memory before additional incoming responses overrun the internal FIFO. When the overrun occurs the hardware will drop the responses which overrun the buffer. An interrupt may be generated if the Response Overrun Interrupt Control bit is set. Note that this status bit is set even if an interrupt is not enabled for this event. Software clears this flag by writing a 1 to this bit.
1	0h RO	RESERVED1: reserved
0	0h RW	RESPONSE_INTERRUPT: Hardware sets this bit to a 1 when an interrupt has been generated after N number of Responses are sent to the RIRB buffer OR when an empty Response slot is encountered on all SDI x inputs whichever occurs first . Note that this status bit is set even if an interrupt is not enabled for this event. Software clears this flag by writing a 1 to this bit.



20.6.29 RIRBSIZE—Offset 5Eh

RIRB Size

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

RIRBSIZE: [AZLBAR] + 5Eh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 42h

7			4				0
0	1	0	0	0	0	1	0
RIRB_SIZE_CAPABILITY				RESERVED0		RIRB_SIZE	

Bit Range	Default & Access	Description
7:4	4h RO	RIRB_SIZE_CAPABILITY: 0100b indicates that the HD Audio controller only supports a RIRB size of 256 RIRB entries 2048B .
3:2	0h RO	RESERVED0: reserved
1:0	02h RO	RIRB_SIZE: Hardwired to 10b which sets the RIRB size to 256 entries 2048B .

20.6.30 IC—Offset 60h

Immediate Command

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

IC: [AZLBAR] + 60h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	IMMEDIATE_COMMAND_WRITE: The command to be sent to the codec via the Immediate Command mechanism is written to this register. The command stored in this register is sent out over the link during the next available frame after a 1 is written to the ICB bit.

20.6.31 IR—Offset 64h

Immediate Response

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

IR: [AZLBAR] + 64h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RO	IMMEDIATE_RESPONSE_READ: This register contains the response received from a codec resulting from a command sent via the Immediate Command mechanism. If multiple codecs responded in the same frame there is no guarantee as to which response will be latched. Therefore broadcast type commands must not be issued via the Immediate Command mechanism.

20.6.32 ICS—Offset 68h

Immediate Command Status

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

ICS: [AZLBAR] + 68h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
RESERVED0				
				IMMEDIATE_RESULT_VALID
				IMMEDIATE_COMMAND_BUSY

Bit Range	Default & Access	Description
15:2	0000h RO	RESERVED0: reserved
1	0h RW	IMMEDIATE_RESULT_VALID: This bit is set to a 1 by hardware when a new response is latched into the IRR register. This is a status flag indicating that software may read the response from the Immediate Response register. Software must clear this bit by writing a one to it before issuing a new command so that the software may determine when a new response has arrived.
0	0h RW	IMMEDIATE_COMMAND_BUSY: When this bit as read as a 0 it indicates that a new command may be issued using the Immediate Command mechanism. When this bit transitions from a 0 to a 1 via software writing a 1 the controller issues the command currently stored in the Immediate Command register to the codec over the link. When the corresponding response is latched into the Immediate Response register the controller hardware sets the IRV flag and clears the ICB bit back to 0. SW may write this bit to a 0 if the bit fails to return to 0 after a reasonable timeout period. Note that an Immediate Command must not be issued while the CORB RIRB mechanism is operating otherwise the responses conflict. This must be enforced by software.

20.6.33 DPLBASE—Offset 70h

DMA Position Lower Base Address

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

DPLBASE: [AZLBAR] + 70h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:7	0h RW	DMA_POSITION_LOWER_BASE_ADDRESS: Lower 32 bits of the DMA Position Buffer Base Address. This register field must not be written when any DMA engine is running or the DMA transfer may be corrupted. This same address is used by the Flush Control and must be programmed with a valid value before the FLCNRTL bit is set.
6:1	00h RO	DMA_POSITION_LOWER_BASE_UNIMPLEMENTED_BITS: Hardwired to 0 to force 128 byte buffer alignment for cache line write optimizations.
0	0h RW	DMA_POSITION_BUFFER_ENABLE: When this bit is set to a 1 the controller will write the DMA positions of each of the DMA engines to the buffer in main memory periodically typically once frame . Software can use this value to know what data in memory is valid data. The controller must guarantee that the values in the DMA Position Buffer that the software can read represent positions in the stream for which valid data exists in the Stream s DMA buffer. This has particular relevance in systems which support isochronous transfer the stream positions in the software visible memory buffer must represent stream data which has reached the Global Observation point.

20.6.34 DPUBASE—Offset 74h

DMA position Upper Base Address

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DPUBASE: [AZLBAR] + 74h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DMA_POSITION_UPPER_BASE_ADDRESS								

Bit Range	Default & Access	Description
31:0	0h RW	DMA_POSITION_UPPER_BASE_ADDRESS: Upper 32 bits of address of the DMA Position Buffer Base Address. This register field must not be written when the DMA engine is running or the DMA transfer may be corrupted.



Access Method

ISDOCTL STS: [AZLBAR] + 80h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00040000h

[illegible]

Bit Range	Default & Access	Description
31:30	0h RO	RESERVED1: reserved
29	0h RO	FIFO_READY: For input streams the controller hardware will set this bit to 1 when a valid descriptor is loaded and the engine is ready for the RUN bit to be set.
28	0h RW	DESCRIPTOR_ERROR: Indicates that a serious error occurred during the fetch of a descriptor. This could be a result of a Master Abort a Parity or ECC error on the bus or any other error which renders the current Buffer Descriptor or Buffer Descriptor List useless. This error is treated as a fatal stream error as the stream cannot continue running. The RUN bit will be cleared and the stream will stop. Software may attempt to restart the stream engine after addressing the cause of the error and writing a 1 to this bit to clear it.
27	0h RW	FIFO_ERROR: Set when a FIFO error occurs. Bit is cleared by writing a 1 to this bit position. This bit is set even if an interrupt is not enabled. For an input stream this indicates a FIFO overrun occurring while the RUN bit is set. When this happens the FIFO pointers don't increment and the incoming data is not written into the FIFO thereby being lost.
26	0h RW	BUFFER_COMPLETION_INTERRUPT_STATUS: This bit is set to 1 by the hardware after the last sample of a buffer has been processed AND if the Interrupt on Completion IOC bit is set in the command byte of the buffer descriptor. It remains active until software clears it by writing a 1 to this bit position.
25:24	0h RO	RESERVED2: reserved



Bit Range	Default & Access	Description
23:20	0h RW	STREAM_NUMBER: This value reflects the Tag associated with the data being transferred on the link. When an input stream is detected on any of the SDIx signals that match this value the data samples are loaded into the FIFO associated with this descriptor. Note that while a single SDIx input may contain data from more than one stream number two different SDIx inputs may not be configured with the same stream number. 0000 Reserved Indicates Unused 0001 Stream 1 1110 Stream 14 1111 Stream 15
19	0h RO	BIDIRECTIONAL_DIRECTION_CONTROL: This bit is only meaningful for Bidirectional streams. Therefore this bit is hardwired to 0.
18	01h RO	TRAFFIC_PRIORITY: Hardwired to 1 indicating that all streams will use VC1 if it is enabled throughout the PCI Express registers.
17:16	0h RO	STRIPE_CONTROL: This field is meaningless for input streams.
15:5	000h RO	RESERVED0: reserved
4	0h RW	DESCRIPTOR_ERROR_INTERRUPT_ENABLE: Controls whether an interrupt is generated when the Descriptor Error Status DESE bit is set.
3	0h RW	FIFO_ERROR_INTERRUPT_ENABLE: This bit controls whether the occurrence of a FIFO error overrun for input will cause an interrupt or not. If this bit is not set bit 3 in the Status register will be set but the interrupt will not occur. Either way the samples will be dropped.
2	0h RW	INTERRUPT_ON_COMPLETION_ENABLE: This bit controls whether or not an interrupt occurs when a buffer completes with the IOC bit set in its descriptor. If this bit is not set bit 2 in the Status register will be set but the interrupt will not occur.
1	0h RW	STREAM_RUN: When set to 1 the DMA engine associated with this input stream will be enabled to transfer data in the FIFO to main memory. The SSYNC bit must also be cleared in order for the DMA engine to run. When cleared to 0 the DMA engine associated with this input stream will be disabled. Hardware will report a 0 in this bit when the DMA engine is actually stopped. Software must read a 0 from this bit before modifying related control registers or restarting the DMA engine.
0	0h RW	STREAM_RESET: Writing a 1 causes the corresponding stream to be reset. The Stream Descriptor registers except the SRST bit itself and FIFO s for the corresponding stream are reset. After the stream hardware has completed sequencing into the reset state it will report a 1 in this bit. Software must read a 1 from this bit to verify that the stream is in reset. Writing a 0 causes the corresponding stream to exit reset. When the stream hardware is ready to begin operation it will report a 0 in this bit. Software must read a 0 from this bit before accessing any of the stream registers. The RUN bit must be cleared before SRST is asserted.

20.6.36 ISDLPB—Offset 84h

Input Stream Descriptor 0 Link Position in Buffer

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISDLPB: [AZLBAR] + 84h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

Input Stream Descriptor 0 Cyclic Buffer Length

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISDOCBL: [AZLBAR] + 88h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CYCLIC_BUFFER_LENGTH								

Bit Range	Default & Access	Description
31:0	0h RW	CYCLIC_BUFFER_LENGTH: Indicates the number of bytes in the complete cyclic buffer. CBL must represent an integer number of samples. Link Position in Buffer LPIB will be reset when it reaches this value. Software may only write to this register after Global Reset Controller Reset or Stream Reset has occurred. This value should only be modified when the RUN bit is 0 . Once the RUN bit has been set to enable the engine software must not write to this register until after the next reset is asserted or transfers may be corrupted.



Access Method

ISD0FIFOW: [AZLBAR] + 8Eh**AZLBAR Type:** PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0004h

Bit Range	Default & Access	Description
15:3	0000h RO	RESERVED0: reserved
2:0	04h RO	FIFO_WATERMARK: Indicates the minimum number of bytes accumulated in the FIFO before the controller will start an eviction of data. The HD Audio controller hardwires the FIFO Watermark either 32B or 64B based on the following. For input streams the FIFOW value is determined by the EM3.ISRWS SEM3.ISRWS field.

20.6.40 ISD0FIFOS—Offset 90h

Access Method

ISD0FIFOS: [AZLBAR] + 90h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

			15				12					8				4				0
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	FIFO_SIZE																			

20.6.41 ISD0FMT—Offset 92h



Input Stream Descriptor 0 Buffer Descriptor List Pointer Lower Base Address

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD0BDLPLBA: [AZLBAR] + 98h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BUFFER_DESCRIPTOR_LIST_LOWER_BASE_ADDRESS				RESERVED				PROTECTED

Bit Range	Default & Access	Description
31:7	0h RW	BUFFER_DESCRIPTOR_LIST_LOWER_BASE_ADDRESS: Lower address of the Buffer Descriptor List. This value should only be modified when the RUN bit is 0 or DMA transfers may be corrupted. Intel Reserved comment This field becomes WO and 0 s will be read when the Protect bit is set to 1.
6:1	00h RO	RESERVED0: reserved



Bit Range	Default & Access	Description
0	0h RW	PROTECT: When this bit is set to 1 bits 31:7:0 of this register are WO and will return 0's when read. When this bit is cleared to 0 bits 31:7:0 are RW. Note that this bit can only be changed when all four bytes of this register are written in a single write operation. If less than four bytes are written this bit retains its previous value. This bit is Intel Reserved.

20.6.43 ISD0BDLPUBA—Offset 9Ch

Input Stream Descriptor 0 Buffer Descriptor List Pointer Upper Base Address

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD0BDLPUBA: [AZLBAR] + 9Ch

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BUFFER_DESCRIPTOR_LIST_UPPER_BASE_ADDRESS								

Bit Range	Default & Access	Description
31:0	0h RW	BUFFER_DESCRIPTOR_LIST_UPPER_BASE_ADDRESS: Upper 32 bit address of the Buffer Descriptor List. This value should only be modified when the RUN bit is 0 or the DMA transfer may be corrupted.



Bit Range	Default & Access	Description
23:20	0h RW	STREAM_NUMBER: This value reflects the Tag associated with the data being transferred on the link. When an input stream is detected on any of the SDIx signals that match this value the data samples are loaded into the FIFO associated with this descriptor. Note that while a single SDIx input may contain data from more than one stream number two different SDIx inputs may not be configured with the same stream number. 0000 Reserved Indicates Unused 0001 Stream 1 1110 Stream 14 1111 Stream 15
19	0h RO	BIDIRECTIONAL_DIRECTION_CONTROL: This bit is only meaningful for Bidirectional streams. Therefore this bit is hardwired to 0.
18	01h RO	TRAFFIC_PRIORITY: Hardwired to 1 indicating that all streams will use VC1 if it is enabled throughout the PCI Express registers.
17:16	0h RO	STRIPE_CONTROL: This field is meaningless for input streams.
15:5	000h RO	RESERVED0: reserved
4	0h RW	DESCRIPTOR_ERROR_INTERRUPT_ENABLE: Controls whether an interrupt is generated when the Descriptor Error Status DESE bit is set.
3	0h RW	FIFO_ERROR_INTERRUPT_ENABLE: This bit controls whether the occurrence of a FIFO error overrun for input will cause an interrupt or not. If this bit is not set bit 3 in the Status register will be set but the interrupt will not occur. Either way the samples will be dropped.
2	0h RW	INTERRUPT_ON_COMPLETION_ENABLE: This bit controls whether or not an interrupt occurs when a buffer completes with the IOC bit set in its descriptor. If this bit is not set bit 2 in the Status register will be set but the interrupt will not occur.
1	0h RW	STREAM_RUN: When set to 1 the DMA engine associated with this input stream will be enabled to transfer data in the FIFO to main memory. The SSYNC bit must also be cleared in order for the DMA engine to run. When cleared to 0 the DMA engine associated with this input stream will be disabled. Hardware will report a 0 in this bit when the DMA engine is actually stopped. Software must read a 0 from this bit before modifying related control registers or restarting the DMA engine.
0	0h RW	STREAM_RESET: Writing a 1 causes the corresponding stream to be reset. The Stream Descriptor registers except the SRST bit itself and FIFO s for the corresponding stream are reset. After the stream hardware has completed sequencing into the reset state it will report a 1 in this bit. Software must read a 1 from this bit to verify that the stream is in reset. Writing a 0 causes the corresponding stream to exit reset. When the stream hardware is ready to begin operation it will report a 0 in this bit. Software must read a 0 from this bit before accessing any of the stream registers. The RUN bit must be cleared before SRST is asserted.

20.6.45 ISD1LPIB—Offset A4h

Input Stream Descriptor 1 Link Position in Buffer

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD1LPIB: [AZLBAR] + A4h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	LINK_POSITION_IN_BUFFER: Indicates the number of bytes that have been received off the link. This register will count from 0 to the value in the Cyclic Buffer Length register and then wrap to 0.

20.6.46 ISD1CBL—Offset A8h

Input Stream Descriptor 1 Cyclic Buffer Length

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD1CBL: [AZLBAR] + A8h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	CYCLIC_BUFFER_LENGTH: Indicates the number of bytes in the complete cyclic buffer. CBL must represent an integer number of samples. Link Position in Buffer LPiB will be reset when it reaches this value. Software may only write to this register after Global Reset Controller Reset or Stream Reset has occurred. This value should only be modified when the RUN bit is 0 . Once the RUN bit has been set to enable the engine software must not write to this register until after the next reset is asserted or transfers may be corrupted.

Input Stream Descriptor 1 FIFO Size

Type: Memory Mapped I/O Register
(Size: 16 bits)

ISD1FIFOS: [AZLBAR] + B0h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

[illegible]

20.6.50 ISD1FMT—Offset B2h


Type: Memory Mapped I/O Register
(Size: 16 bits)

ISD1FMT: [AZLBAR] + B2h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
2754



20.6.51 ISD1BDLPLBA—Offset B8h


Access Method

ISD1BDLPLBA: [AZLBAR] + B8h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:7	0h RW	BUFFER_DESCRIPTOR_LIST_LOWER_BASE_ADDRESS: Lower address of the Buffer Descriptor List. This value should only be modified when the RUN bit is 0 or DMA transfers may be corrupted. Intel Reserved comment This field becomes WO and 0 s will be read when the Protect bit is set to 1.
6:1	00h RO	RESERVED0: reserved
0	0h RW	PROTECT: When this bit is set to 1 bits 31 7 0 of this register are WO and will return 0 s when read. When this bit is cleared to 0 bits 31 7 0 are RW. Note that this bit can only be changed when all four bytes of this register are written in a single write operation. If less than four bytes are written this bit retains its previous value. This bit is Intel Reserved.

20.6.52 ISD1BDLPUBA—Offset BCh

Input Stream Descriptor 1 Buffer Descriptor List Pointer Upper Base Address

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD1BDLPUBA: [AZLBAR] + BCh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	BUFFER_DESCRIPTOR_LIST_UPPER_BASE_ADDRESS: Upper 32 bit address of the Buffer Descriptor List. This value should only be modified when the RUN bit is 0 or the DMA transfer may be corrupted.

20.6.53 ISD2CTL_STS—Offset C0h

Input Stream Descriptor 2 Control and status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD2CTL_STS: [AZLBAR] + C0h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00040000h



Access Method

ISD2CBL: [AZLBAR] + C8h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RW	CYCLIC_BUFFER_LENGTH: Indicates the number of bytes in the complete cyclic buffer. CBL must represent an integer number of samples. Link Position in Buffer LPIB will be reset when it reaches this value. Software may only write to this register after Global Reset Controller Reset or Stream Reset has occurred. This value should only be modified when the RUN bit is 0 . Once the RUN bit has been set to enable the engine software must not write to this register until after the next reset is asserted or transfers may be corrupted.

20.6.56 ISD2LVI—Offset CCh


Access Method

ISD2LVI: [AZLBAR] + CCh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
RESERVED0				FIFO_WATERMARK

Intel Atom® Processor E3800 Product Family
Datasheet
2761



ISD2FIFOS: [AZLBAR] + D0h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

Bit Range	Default & Access	Description
15:0	00h RW	FIFO_SIZE: Indicates the maximum number of bytes that could be revicted by the controller at one time. This is the maximum number of bytes that may have been received from the link but not yet DMA d into memory and is also the maximum possible value that the PICB count will increase by at one time. The FIFO size is calculated based on factors including the stream format programmed in ISD2FMT register. As the default value is zero, SW must write to the respective ISD2FMT register to kick of the FIFO size calculation, and read back to find out the HW allocated FIFO size.

20.6.59 ISD2FMT—Offset D2h

Input Stream Descriptor 2 Format

Access Method


ISD2FMT: [AZLBAR] + D2h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

Bit Range	Default & Access	Description
15	0h RO	RESERVED0: reserved



Bit Range	Default & Access	Description
23:20	0h RW	STREAM_NUMBER: This value reflects the Tag associated with the data being transferred on the link. When an input stream is detected on any of the SDIx signals that match this value the data samples are loaded into the FIFO associated with this descriptor. Note that while a single SDIx input may contain data from more than one stream number two different SDIx inputs may not be configured with the same stream number. 0000 Reserved Indicates Unused 0001 Stream 1 1110 Stream 14 1111 Stream 15
19	0h RO	BIDIRECTIONAL_DIRECTION_CONTROL: This bit is only meaningful for Bidirectional streams. Therefore this bit is hardwired to 0.
18	01h RO	TRAFFIC_PRIORITY: Hardwired to 1 indicating that all streams will use VC1 if it is enabled throughout the PCI Express registers.
17:16	0h RO	STRIPE_CONTROL: This field is meaningless for input streams.
15:5	000h RO	RESERVED0: reserved
4	0h RW	DESCRIPTOR_ERROR_INTERRUPT_ENABLE: Controls whether an interrupt is generated when the Descriptor Error Status DESE bit is set.
3	0h RW	FIFO_ERROR_INTERRUPT_ENABLE: This bit controls whether the occurrence of a FIFO error overrun for input will cause an interrupt or not. If this bit is not set bit 3 in the Status register will be set but the interrupt will not occur. Either way the samples will be dropped.
2	0h RW	INTERRUPT_ON_COMPLETION_ENABLE: This bit controls whether or not an interrupt occurs when a buffer completes with the IOC bit set in its descriptor. If this bit is not set bit 2 in the Status register will be set but the interrupt will not occur.
1	0h RW	STREAM_RUN: When set to 1 the DMA engine associated with this input stream will be enabled to transfer data in the FIFO to main memory. The SSYNC bit must also be cleared in order for the DMA engine to run. When cleared to 0 the DMA engine associated with this input stream will be disabled. Hardware will report a 0 in this bit when the DMA engine is actually stopped. Software must read a 0 from this bit before modifying related control registers or restarting the DMA engine.
0	0h RW	STREAM_RESET: Writing a 1 causes the corresponding stream to be reset. The Stream Descriptor registers except the SRST bit itself and FIFO s for the corresponding stream are reset. After the stream hardware has completed sequencing into the reset state it will report a 1 in this bit. Software must read a 1 from this bit to verify that the stream is in reset. Writing a 0 causes the corresponding stream to exit reset. When the stream hardware is ready to begin operation it will report a 0 in this bit. Software must read a 0 from this bit before accessing any of the stream registers. The RUN bit must be cleared before SRST is asserted.

20.6.63 ISD3LPB—Offset E4h

Input Stream Descriptor 3 Link Position in Buffer

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD3LPB: [AZLBAR] + E4h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RO	LINK_POSITION_IN_BUFFER: Indicates the number of bytes that have been received off the link. This register will count from 0 to the value in the Cyclic Buffer Length register and then wrap to 0.

20.6.64 ISD3CBL—Offset E8h

Input Stream Descriptor 3 Cyclic Buffer Length

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD3CBL: [AZLBAR] + E8h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	CYCLIC_BUFFER_LENGTH: Indicates the number of bytes in the complete cyclic buffer. CBL must represent an integer number of samples. Link Position in Buffer LPIB will be reset when it reaches this value. Software may only write to this register after Global Reset Controller Reset or Stream Reset has occurred. This value should only be modified when the RUN bit is 0 . Once the RUN bit has been set to enable the engine software must not write to this register until after the next reset is asserted or transfers may be corrupted.



Access Method

ISD3LVI: [AZLBAR] + ECh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

Bit Range	Default & Access	Description
15:8	00h RO	RESERVED0: reserved
7:0	00h RW	LAST_VALID_INDEX: The value written to this register indicates the index for the last valid Buffer Descriptor in the BDL. After the controller has processed this descriptor it will wrap back to the first descriptor in the list and continue processing. LVI must be at least 1 i.e. there must be at least two valid entries in the buffer descriptor list before DMA operations can begin. This value should only be modified when the RUN bit is 0

20.6.66 ISD3FIFOW—Offset EEh

Access Method

ISD3FIFOW: [AZLBAR] + EEh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0004h

[illegible]



15	12	8	4	0
0	0	0	0	0
RESERVED0	SAMPLE_BASE_RATE	SAMPLE_BASE_RATE_MULTIPLE	SAMPLE_BASE_RATE_DIVISOR	RESERVED1
			BITS_PER_SAMPLE	NUMBER_OF_CHANNELS

Bit Range	Default & Access	Description
15	0h RO	RESERVED0: reserved
14	0h RW	SAMPLE_BASE_RATE: 0 48 kHz 1 44.1 kHz
13:11	0h RW	SAMPLE_BASE_RATE_MULTIPLE: Sample Base Rate Multiple (MULT): 000=48kHz/44.1kHz or less 001=x2 96kHz 88.2kHz 32kHz 010=x3 144kHz 011=x4 192kHz 176.4kHz 100-111 Reserved
10:8	0h RW	SAMPLE_BASE_RATE_DIVISOR: Sample Base Rate Divisor (DIV): 000 Divide by 1, 48kHz 44.1kHz 001 Divide by 2, 24kHz 22.05kHz 010 Divide by 3, 16kHz 32kHz 011 Divide by 4, 11.025kHz 100 Divide by 5, 9.6kHz 101 Divide by 6, 8kHz 110 Divide by 7 111 Divide by 8, 6kHz
7	0h RO	RESERVED1: reserved
6:4	0h RW	BITS_PER_SAMPLE: Bits per Sample (BITS): 000=8 bits. The data will be packed in memory in 8 bit containers on 16 bit boundaries 001=16 bits. The data will be packed in memory in 16 bit containers on 16 bit boundaries 010=20 bits. The data will be packed in memory in 32 bit containers on 32 bit boundaries 011=24 bits. The data will be packed in memory in 32 bit containers on 32 bit boundaries 100=32 bits. The data will be packed in memory in 32 bit containers on 32 bit boundaries 101-111 Reserved
3:0	0h RW	NUMBER_OF_CHANNELS: Number of channels in each frame of the stream 0000=1 0001=2 1111=16

20.6.69 ISD3BDLPLBA—Offset F8h

Input Stream Descriptor 3 Buffer Descriptor List Pointer Lower Base Address

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD3BDLPLBA: [AZLBAR] + F8h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:7	0h RW	BUFFER_DESCRIPTOR_LIST_LOWER_BASE_ADDRESS: Lower address of the Buffer Descriptor List. This value should only be modified when the RUN bit is 0 or DMA transfers may be corrupted. Intel Reserved comment This field becomes WO and 0 s will be read when the Protect bit is set to 1.
6:1	00h RO	RESERVED0: reserved
0	0h RW	PROTECT: When this bit is set to 1 bits 31 7 0 of this register are WO and will return 0 s when read. When this bit is cleared to 0 bits 31 7 0 are RW. Note that this bit can only be changed when all four bytes of this register are written in a single write operation. If less than four bytes are written this bit retains its previous value. This bit is Intel Reserved.

20.6.70 ISD3BDLPUBA—Offset FCh

Input Stream Descriptor 3 Buffer Descriptor List Pointer Upper Base Address

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

ISD3BDLPUBA: [AZLBAR] + FCh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



20.6.71 OSD0CTL_STS—Offset 100h

Output Stream Descriptor 0 Control and status

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

OSDOCTL_STS: [AZLBAR] + 100h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00040000h



31	28				24				20				16				12				8				4				0																																										
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																										
RESERVED1				FIFO_READY				DESCRIPTOR_ERROR				FIFO_ERROR				BUFFER_COMPLETION_INTERRUPT_STATUS				RESERVED2								STREAM_NUMBER				BIDIRECTIONAL_DIRECTION_CONTROL				TRAFFIC_PRIORITY				STRIPE_CONTROL								RESERVED0				DESCRIPTOR_ERROR_INTERRUPT_ENABLE				FIFO_ERROR_INTERRUPT_ENABLE				INTERRUPT_ON_COMPLETION_ENABLE				STREAM_RUN				STREAM_RESET			

Bit Range	Default & Access	Description
31:30	0h RO	RESERVED1: reserved
29	0h RO	FIFO_READY: For output streams the controller hardware will set this bit to a 1 while the output DMA FIFO contains enough data to maintain the stream on then link. This bit defaults to 0 on reset because the FIFO is cleared on a reset.
28	0h RW	DESCRIPTOR_ERROR: Indicates that a serious error occurred during the fetch of a descriptor. This could be a result of a Master Abort a Parity or ECC error on the bus or any other error which renders the current Buffer Descriptor or Buffer Descriptor List useless. This error is treated as a fatal stream error as the stream cannot continue running. The RUN bit will be cleared and the stream will stop. Software may attempt to restart the stream engine after addressing the cause of the error and writing a 1 to this bit to clear it.
27	0h RW	FIFO_ERROR: Set when a FIFO error occurs. Bit is cleared by writing a 1 to this bit position. This bit is set even if an interrupt is not enabled. For an output stream this indicates a FIFO under run when there are still buffers to send. The hardware should not transmit anything on the link for the associated stream if there is not valid data to send.
26	0h RW	BUFFER_COMPLETION_INTERRUPT_STATUS: This bit is set to 1 by the hardware after the last sample of a buffer has been processed AND if the Interrupt on Completion IOC bit is set in the command byte of the buffer descriptor. It remains active until software clears it by writing a 1 to this bit position.
25:24	0h RO	RESERVED2: reserved
23:20	0h RW	STREAM_NUMBER: This value reflects the Tag associated with the data being transferred on the link. When data controlled by this descriptor is sent out over the link it will have this stream number encoded on the SYNC signal. 0000 Reserved Indicates Unused 0001 Stream 1 1110 Stream 14 1111 Stream 15
19	0h RO	BIDIRECTIONAL_DIRECTION_CONTROL: This bit is only meaningful for Bidirectional streams. Therefore this bit is hardwired to 0.
18	01h RO	TRAFFIC_PRIORITY: Hardwired to 1 indicating that all streams will use VC1 if it is enabled throughout the PCI Express registers.
17:16	0h RO	STRIPE_CONTROL: For output streams it controls the number of SDO signals to stripe data across. Only one SDO is supported in the HD Audio controller. Therefore it is hardwired to 0 s.
15:5	000h RO	RESERVED0: reserved



Output Stream Descriptor 0 Link Position in Buffer

Type: Memory Mapped I/O Register
(Size: 32 bits)

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RO	LINK_POSITION_IN_BUFFER: Indicates the number of bytes that have been received off the link. This register will count from 0 to the value in the Cyclic Buffer Length register and then wrap to 0.



Bit Range	Default & Access	Description
15:8	00h RO	RESERVED0: reserved
7:0	00h RW	LAST_VALID_INDEX: The value written to this register indicates the index for the last valid Buffer Descriptor in the BDL. After the controller has processed this descriptor it will wrap back to the first descriptor in the list and continue processing. LVI must be at least 1 i.e. there must be at least two valid entries in the buffer descriptor list before DMA operations can begin. This value should only be modified when the RUN bit is 0

20.6.75 OSD0FIFOW—Offset 10Eh

Output Stream Descriptor 0 FIFO Fetch Watermark

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

OSD0FIFOW: [AZLBAR] + 10Eh

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0004h

[illegible]

Bit Range	Default & Access	Description
15:3	0000h RO	RESERVED0: reserved
2:0	04h RO	FIFO_WATERMARK: Indicates the minimum number of bytes free in the FIFO before the controller will start a fetch of data. The HD Audio controller hardwires the FIFO Watermark either 32B or 64B based on the following. For output streams the FIFOW value is determined by the EM4.OSRWS SEM4.OSRWS field.

20.6.76 OSD0FIFOS—Offset 110h

Output Stream Descriptor 0 FIFO Size

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

OSD0FIFOS: [AZLBAR] + 110h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h



15	12	8	4	0
0	0	0	0	0
FIFO_SIZE				

Bit Range	Default & Access	Description
15:0	00h RW	FIFO_SIZE: Indicates the maximum number of bytes that could be fetched by the controller at one time. This is the maximum number of bytes that may have been DMA'd into memory but not yet transmitted on the link and is also the maximum possible value that the PICB count will increase by at one time. The FIFO size is calculated based on factors including the stream format programmed in OSD0FMT register. As the default value is zero, SW must write to the OSD0FMT register to kick off the FIFO size calculation and read back to find out the HW allocated FIFO size.

20.6.77 OSD0FMT—Offset 112h

Output Stream Descriptor 0 Format

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

OSDOFMT: [AZLBAR] + 112h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

[illegible]

Bit Range	Default & Access	Description
15	0h RO	RESERVED0: reserved
14	0h RW	SAMPLE_BASE_RATE: Sample Base Rate (BASE): 0=48kHz 1=44.1kHz
13:11	0h RW	SAMPLE_BASE_RATE_MULTIPLE: Sample Base Rate Multiple (MULT): 000=48kHz/44.1kHz or less 001=x2 96kHz 88.2kHz 32kHz 010=x3 144kHz 011=x4 192kHz 176.4kHz 100-111 Reserved



20.6.80 OSD1CTL_STS—Offset 120h

Output Stream Descriptor 1 Control and status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

OSD1CTL_STS: [AZLBAR] + 120h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00040000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED1	FIFO_READY	DESCRIPTOR_ERROR	FIFO_ERROR	RESERVED2	STREAM_NUMBER	BIDIRECTIONAL_DIRECTION_CONTROL	TRAFFIC_PRIORITY	STRIPE_CONTROL
						RESERVED0		
							DESCRIPTOR_ERROR_INTERRUPT_ENABLE	FIFO_ERROR_INTERRUPT_ENABLE
								INTERRUPT_ON_COMPLETION_ENABLE
								STREAM_RUN
								STREAM_RESET

Bit Range	Default & Access	Description
31:30	0h RO	RESERVED1: reserved
29	0h RO	FIFO_READY: For output streams the controller hardware will set this bit to a 1 while the output DMA FIFO contains enough data to maintain the stream on then link. This bit defaults to 0 on reset because the FIFO is cleared on a reset.
28	0h RW	DESCRIPTOR_ERROR: Indicates that a serious error occurred during the fetch of a descriptor. This could be a result of a Master Abort a Parity or ECC error on the bus or any other error which renders the current Buffer Descriptor or Buffer Descriptor List useless. This error is treated as a fatal stream error as the stream cannot continue running. The RUN bit will be cleared and the stream will stop. Software may attempt to restart the stream engine after addressing the cause of the error and writing a 1 to this bit to clear it.
27	0h RW	FIFO_ERROR: Set when a FIFO error occurs. Bit is cleared by writing a 1 to this bit position. This bit is set even if an interrupt is not enabled. For an output stream this indicates a FIFO under run when there are still buffers to send. The hardware should not transmit anything on the link for the associated stream if there is not valid data to send.
26	0h RW	BUFFER_COMPLETION_INTERRUPT_STATUS: This bit is set to 1 by the hardware after the last sample of a buffer has been processed AND if the Interrupt on Completion IOC bit is set in the command byte of the buffer descriptor. It remains active until software clears it by writing a 1 to this bit position.
25:24	0h RO	RESERVED2: reserved



Bit Range	Default & Access	Description
23:20	0h RW	STREAM_NUMBER: This value reflects the Tag associated with the data being transferred on the link. When data controlled by this descriptor is sent out over the link it will have this stream number encoded on the SYNC signal. 0000 Reserved Indicates Unused 0001 Stream 1 1110 Stream 14 1111 Stream 15
19	0h RO	BIDIRECTIONAL_DIRECTION_CONTROL: This bit is only meaningful for Bidirectional streams. Therefore this bit is hardwired to 0.
18	01h RO	TRAFFIC_PRIORITY: Hardwired to 1 indicating that all streams will use VC1 if it is enabled throughout the PCI Express registers.
17:16	0h RO	STRIPE_CONTROL: For output streams it controls the number of SDO signals to stripe data across. Only one SDO is supported in the HD Audio controller. Therefore it is hardwired to 0 s.
15:5	000h RO	RESERVED0: reserved
4	0h RW	DESCRIPTOR_ERROR_INTERRUPT_ENABLE: Controls whether an interrupt is generated when the Descriptor Error Status DESE bit is set.
3	0h RW	FIFO_ERROR_INTERRUPT_ENABLE: This bit controls whether the occurrence of a FIFO error under run for output will cause an interrupt or not. If this bit is not set bit 3 in the Status register will be set but the interrupt will not occur. Either way the samples will be dropped.
2	0h RW	INTERRUPT_ON_COMPLETION_ENABLE: This bit controls whether or not an interrupt occurs when a buffer completes with the IOC bit set in its descriptor. If this bit is not set bit 2 in the Status register will be set but the interrupt will not occur.
1	0h RW	STREAM_RUN: When set to 1 the DMA engine associated with this output stream will be enabled to transfer data in the main memory to FIFO. The SSYNC bit must also be cleared in order for the DMA engine to run. For output streams the cadence generator is reset whenever the RUN bit is set. When cleared to 0 the DMA engine associated with this output stream will be disabled. Hardware will report a 0 in this bit when the DMA engine is actually stopped. Software must read a 0 from this bit before modifying related control registers or restarting the DMA engine.
0	0h RW	STREAM_RESET: Writing a 1 causes the corresponding stream to be reset. The Stream Descriptor registers except the SRST bit itself and FIFO s for the corresponding stream are reset. After the stream hardware has completed sequencing into the reset state it will report a 1 in this bit. Software must read a 1 from this bit to verify that the stream is in reset. Writing a 0 causes the corresponding stream to exit reset. When the stream hardware is ready to begin operation it will report a 0 in this bit. Software must read a 0 from this bit before accessing any of the stream registers. The RUN bit must be cleared before SRST is asserted.

20.6.81 OSD1LPB—Offset 124h

Output Stream Descriptor 1 Link Position in Buffer

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

OSD1LPB: [AZLBAR] + 124h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

Output Stream Descriptor 1 Cyclic Buffer Length

Type: Memory Mapped I/O Register
(Size: 32 bits)

OSD1CBL: [AZLBAR] + 128h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Intel Atom® Processor E3800 Product Family
Datasheet
2782

Output Stream Descriptor 1 FIFO Size

Type: Memory Mapped I/O Register
(Size: 16 bits)

OSD1FIFOS: [AZLBAR] + 130h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

[illegible]

20.6.86 OSD1FMT—Offset 132h

Output Stream Descriptor 1 Format


Type: Memory Mapped I/O Register
(Size: 16 bits)

OSD1FMT: [AZLBAR] + 132h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h



20.6.87 OSD1BDLPLBA—Offset 138h


Access Method

OSD1BDLPLBA: [AZLBAR] + 138h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:7	0h RW	BUFFER_DESCRIPTOR_LIST_LOWER_BASE_ADDRESS: Lower address of the Buffer Descriptor List. This value should only be modified when the RUN bit is 0 or DMA transfers may be corrupted. Intel Reserved comment This field becomes WO and 0 s will be read when the Protect bit is set to 1.
6:1	00h RO	RESERVED0: reserved
0	0h RW	PROTECT: When this bit is set to 1 bits 31 7 0 of this register are WO and will return 0 s when read. When this bit is cleared to 0 bits 31 7 0 are RW. Note that this bit can only be changed when all four bytes of this register are written in a single write operation. If less than four bytes are written this bit retains its previous value. This bit is Intel Reserved.

20.6.88 OSD1BDLPUBA—Offset 13Ch

Output Stream Descriptor 1 Buffer Descriptor List Pointer Upper Base Address

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)


OSD1BDLPUBA: [AZLBAR] + 13Ch

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h





31				28				24				20				16				12				8				4				0																															
0				0				0				0				0				0				0				0				0																															
RESERVED1				FIFO_READY				DESCRIPTOR_ERROR				FIFO_ERROR				BUFFER_COMPLETION_INTERRUPT_STATUS				RESERVED2				STREAM_NUMBER				BIDIRECTIONAL_DIRECTION_CONTROL				TRAFFIC_PRIORITY				STRIPE_CONTROL				RESERVED0				DESCRIPTOR_ERROR_INTERRUPT_ENABLE				FIFO_ERROR_INTERRUPT_ENABLE				INTERRUPT_ON_COMPLETION_ENABLE				STREAM_RUN				STREAM_RESET			

Bit Range	Default & Access	Description
31:30	0h RO	RESERVED1: reserved
29	0h RO	FIFO_READY: For output streams the controller hardware will set this bit to a 1 while the output DMA FIFO contains enough data to maintain the stream on then link. This bit defaults to 0 on reset because the FIFO is cleared on a reset.
28	0h RW	DESCRIPTOR_ERROR: Indicates that a serious error occurred during the fetch of a descriptor. This could be a result of a Master Abort a Parity or ECC error on the bus or any other error which renders the current Buffer Descriptor or Buffer Descriptor List useless. This error is treated as a fatal stream error as the stream cannot continue running. The RUN bit will be cleared and the stream will stop. Software may attempt to restart the stream engine after addressing the cause of the error and writing a 1 to this bit to clear it.
27	0h RW	FIFO_ERROR: Set when a FIFO error occurs. Bit is cleared by writing a 1 to this bit position. This bit is set even if an interrupt is not enabled. For an output stream this indicates a FIFO under run when there are still buffers to send. The hardware should not transmit anything on the link for the associated stream if there is not valid data to send.
26	0h RW	BUFFER_COMPLETION_INTERRUPT_STATUS: This bit is set to 1 by the hardware after the last sample of a buffer has been processed AND if the Interrupt on Completion IOC bit is set in the command byte of the buffer descriptor. It remains active until software clears it by writing a 1 to this bit position.
25:24	0h RO	RESERVED2: reserved
23:20	0h RW	STREAM_NUMBER: This value reflects the Tag associated with the data being transferred on the link. When data controlled by this descriptor is sent out over the link it will have this stream number encoded on the SYNC signal. 0000 Reserved Indicates Unused 0001 Stream 1 1110 Stream 14 1111 Stream 15
19	0h RO	BIDIRECTIONAL_DIRECTION_CONTROL: This bit is only meaningful for Bidirectional streams. Therefore this bit is hardwired to 0.
18	01h RO	TRAFFIC_PRIORITY: Hardwired to 1 indicating that all streams will use VC1 if it is enabled throughout the PCI Express registers.
17:16	0h RO	STRIPE_CONTROL: For output streams it controls the number of SDO signals to stripe data across. Only one SDO is supported in the HD Audio controller. Therefore it is hardwired to 0 s.
15:5	000h RO	RESERVED0: reserved



Bit Range	Default & Access	Description
4	0h RW	DESCRIPTOR_ERROR_INTERRUPT_ENABLE: Controls whether an interrupt is generated when the Descriptor Error Status DESE bit is set.
3	0h RW	FIFO_ERROR_INTERRUPT_ENABLE: This bit controls whether the occurrence of a FIFO error under run for output will cause an interrupt or not. If this bit is not set bit 3 in the Status register will be set but the interrupt will not occur. Either way the samples will be dropped.
2	0h RW	INTERRUPT_ON_COMPLETION_ENABLE: This bit controls whether or not an interrupt occurs when a buffer completes with the IOC bit set in its descriptor. If this bit is not set bit 2 in the Status register will be set but the interrupt will not occur.
1	0h RW	STREAM_RUN: When set to 1 the DMA engine associated with this output stream will be enabled to transfer data in the main memory to FIFO. The SSYNC bit must also be cleared in order for the DMA engine to run. For output streams the cadence generator is reset whenever the RUN bit is set. When cleared to 0 the DMA engine associated with this output stream will be disabled. Hardware will report a 0 in this bit when the DMA engine is actually stopped. Software must read a 0 from this bit before modifying related control registers or restarting the DMA engine.
0	0h RW	STREAM_RESET: Writing a 1 causes the corresponding stream to be reset. The Stream Descriptor registers except the SRST bit itself and FIFO s for the corresponding stream are reset. After the stream hardware has completed sequencing into the reset state it will report a 1 in this bit. Software must read a 1 from this bit to verify that the stream is in reset. Writing a 0 causes the corresponding stream to exit reset. When the stream hardware is ready to begin operation it will report a 0 in this bit. Software must read a 0 from this bit before accessing any of the stream registers. The RUN bit must be cleared before SRST is asserted.

20.6.90 OSD2LPIB—Offset 144h

Output Stream Descriptor 2 Link Position in Buffer

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

OSD2LPIB: [AZLBAR] + 144h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
LINK_POSITION_IN_BUFFER								

Bit Range	Default & Access	Description
31:0	0h RO	LINK_POSITION_IN_BUFFER: Indicates the number of bytes that have been received off the link. This register will count from 0 to the value in the Cyclic Buffer Length register and then wrap to 0.



Access Method

OSD2CBL: [AZLBAR] + 148h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RW	CYCLIC_BUFFER_LENGTH: Indicates the number of bytes in the complete cyclic buffer. CBL must represent an integer number of samples. Link Position in Buffer LPIB will be reset when it reaches this value. Software may only write to this register after Global Reset Controller Reset or Stream Reset has occurred. This value should only be modified when the RUN bit is 0 . Once the RUN bit has been set to enable the engine software must not write to this register until after the next reset is asserted or transfers may be corrupted.

20.6.92 OSD2LVI—Offset 14Ch



Output Stream Descriptor 2 Last Valid Index

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

OSD2LVI: [AZLBAR] + 14Ch

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
RESERVED0				LAST_VALID_INDEX

Bit Range	Default & Access	Description
15:8	00h RO	RESERVED0: reserved
7:0	00h RW	LAST_VALID_INDEX: The value written to this register indicates the index for the last valid Buffer Descriptor in the BDL. After the controller has processed this descriptor it will wrap back to the first descriptor in the list and continue processing. LVI must be at least 1 i.e. there must be at least two valid entries in the buffer descriptor list before DMA operations can begin. This value should only be modified when the RUN bit is 0

20.6.93 OSD2FIFOW—Offset 14Eh

Output Stream Descriptor 2 FIFO Fetch Watermark

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

OSD2FIFOW: [AZLBAR] + 14Eh


AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 0004h

15	12	8	4	0
0	0	0	0	0
RESERVED0				FIFO_WATERMARK

Bit Range	Default & Access	Description
15:3	0000h RO	RESERVED0: reserved



20.6.96 OSD2BDLPLBA—Offset 158h


Access Method

OSD2BDLPLBA: [AZLBAR] + 158h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:7	0h RW	BUFFER_DESCRIPTOR_LIST_LOWER_BASE_ADDRESS: Lower address of the Buffer Descriptor List. This value should only be modified when the RUN bit is 0 or DMA transfers may be corrupted. Intel Reserved comment This field becomes WO and 0 s will be read when the Protect bit is set to 1.
6:1	00h RO	RESERVED0: reserved
0	0h RW	PROTECT: When this bit is set to 1 bits 31 7 0 of this register are WO and will return 0 s when read. When this bit is cleared to 0 bits 31 7 0 are RW. Note that this bit can only be changed when all four bytes of this register are written in a single write operation. If less than four bytes are written this bit retains its previous value. This bit is Intel Reserved.

20.6.97 OSD2BDLPUBA—Offset 15Ch

Output Stream Descriptor 2 Buffer Descriptor List Pointer Upper Base Address

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

OSD2BDLPUBA: [AZLBAR] + 15Ch

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h



Intel Atom® Processor E3800 Product Family
Datasheet
2795



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RESERVED1	FIFO_READY	RESERVED2	STREAM_NUMBER	BIDIRECTIONAL_DIRECTION_CONTROL	TRAFFIC_PRIORITY	STRIPE_CONTROL	RESERVED0	DESCRIPTOR_ERROR_INTERRUPT_ENABLE
	DESCRIPTOR_ERROR							FIFO_ERROR_INTERRUPT_ENABLE
	FIFO_ERROR							INTERRUPT_ON_COMPLETION_ENABLE
	BUFFER_COMPLETION_INTERRUPT_STATUS							STREAM_RUN
								STREAM_RESET

Bit Range	Default & Access	Description
31:30	0h RO	RESERVED1: reserved
29	0h RO	FIFO_READY: For output streams the controller hardware will set this bit to a 1 while the output DMA FIFO contains enough data to maintain the stream on then link. This bit defaults to 0 on reset because the FIFO is cleared on a reset.
28	0h RW	DESCRIPTOR_ERROR: Indicates that a serious error occurred during the fetch of a descriptor. This could be a result of a Master Abort a Parity or ECC error on the bus or any other error which renders the current Buffer Descriptor or Buffer Descriptor List useless. This error is treated as a fatal stream error as the stream cannot continue running. The RUN bit will be cleared and the stream will stop. Software may attempt to restart the stream engine after addressing the cause of the error and writing a 1 to this bit to clear it.
27	0h RW	FIFO_ERROR: Set when a FIFO error occurs. Bit is cleared by writing a 1 to this bit position. This bit is set even if an interrupt is not enabled. For an output stream this indicates a FIFO under run when there are still buffers to send. The hardware should not transmit anything on the link for the associated stream if there is not valid data to send.
26	0h RW	BUFFER_COMPLETION_INTERRUPT_STATUS: This bit is set to 1 by the hardware after the last sample of a buffer has been processed AND if the Interrupt on Completion IOC bit is set in the command byte of the buffer descriptor. It remains active until software clears it by writing a 1 to this bit position.
25:24	0h RO	RESERVED2: reserved
23:20	0h RW	STREAM_NUMBER: This value reflects the Tag associated with the data being transferred on the link. When data controlled by this descriptor is sent out over the link it will have this stream number encoded on the SYNC signal. 0000 Reserved Indicates Unused 0001 Stream 1 1110 Stream 14 1111 Stream 15
19	0h RO	BIDIRECTIONAL_DIRECTION_CONTROL: This bit is only meaningful for Bidirectional streams. Therefore this bit is hardwired to 0.
18	01h RO	TRAFFIC_PRIORITY: Hardwired to 1 indicating that all streams will use VC1 if it is enabled throughout the PCI Express registers.
17:16	0h RO	STRIPE_CONTROL: For output streams it controls the number of SDO signals to stripe data across. Only one SDO is supported in the HD Audio controller. Therefore it is hardwired to 0 s.
15:5	000h RO	RESERVED0: reserved

20.6.100 OSD3CBL—Offset 168h

Output Stream Descriptor 3 FIFO Size

Type: Memory Mapped I/O Register
(Size: 16 bits)

OSD3FIFOS: [AZLBAR] + 170h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
2800



20.6.105 OSD3BDLPLBA—Offset 178h

Output Stream Descriptor 3 Buffer Descriptor List Pointer Lower Base Address

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

OSD3BDLPLBA: [AZLBAR] + 178h

AZLBAR Type: PCI Configuration Register (Size: 32 bits)

AZLBAR Reference: [B:0, D:27, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BUFFER_DESCRIPTOR_LIST_LOWER_BASE_ADDRESS								RESERVED0
								PROTECT

Bit Range	Default & Access	Description
31:7	0h RW	BUFFER_DESCRIPTOR_LIST_LOWER_BASE_ADDRESS: Lower address of the Buffer Descriptor List. This value should only be modified when the RUN bit is 0 or DMA transfers may be corrupted. Intel Reserved comment This field becomes WO and 0 s will be read when the Protect bit is set to 1.
6:1	00h RO	RESERVED0: reserved
0	0h RW	PROTECT: When this bit is set to 1 bits 31 7 0 of this register are WO and will return 0 s when read. When this bit is cleared to 0 bits 31 7 0 are RW. Note that this bit can only be changed when all four bytes of this register are written in a single write operation. If less than four bytes are written this bit retains its previous value. This bit is Intel Reserved.



21 Low Power Engine (LPE) for Audio (I²S)


The Low Power Engine for Audio provides acceleration for common audio and voice functions. The voice and audio engine provides a mechanism for rendering audio and voice streams and tones from the operating system, applications to an audio or voice codec, and ultimately to the speaker, headphones, or Bluetooth headsets.

Audio streams in the SoC can be encoded and decoded by the Low Power Engine (LPE) in the Audio subsystem.

LPE Audio provides three external I²S audio interfaces.

Note: LPE_I2S[1:0] are multiplexed on the same balls as High Definition Audio.

Note: When LPE is active, the High Definition Audio functionality is disabled.



21.1 Signal Descriptions

See [Chapter 2, “Physical Interfaces”](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal’s function

**Table 226. LPE Signals**

Signal Name	Direction Plat. Power	Description
LPE_I2S2[0:2]_CLK	I/O V1P8S	Clock signal for I ² S
LPE_I2S2[0:2]_FRM	I/O V1P8S	Frame select signal for I ² S
LPE_I2S2[0:2]_DATAIN	I V1P8S	RX data for I ² S
LPE_I2S2[0:2]_DATAOUT	O V1P8S	TX data for I ² S

† All LPE signals are muxed and may be used by other functions.

21.2 Features

The LPE Audio Subsystem consists of the following:

- Integrated, power-efficient 32-bit architecture core with 24-bit audio processing instructions
- Core processing speeds up to 343 MHz
- Closely Coupled Memories (CCMs)
 - 80KB Instruction RAM
 - 160KB Data RAM
 - 48KB Instruction Cache
 - 96KB Data Cache
- Very low-power consumption coupled with high-fidelity 24-bit audio
- Dual-issue, static, super-scalar VLIW processing engine
- Mode-less switching between 16-, 24-, and 64-bit dual-issue instructions
- Dual MACs which can operate with 32 x 16-bit and/or 24 x 24-bit operands
- Inter-Process Communication (IPC) mechanism to communicate with the SoC Processor Core including 4KB mailbox memory
- Flexible audio interfaces include three SSPs with I²S port functionality for I-directional audio transfers
 - I²S mode supports PCM payloads
 - Frame counters for all I²S ports
- High Performance DMA
 - DMA IP to support multiple outstanding transactions
 - Interleaved scatter-gather support for Audio DMA transfers
- Clock switching logic including new frequency increments



- External timer function with an always running clock.

The LPE core runs at a peak clock frequency of 343 MHz and has dedicated on-chip program and data memories and caches. The LPE core can access shared SRAM blocks, and external DRAM through OCP fabric. It communicates with audio peripherals using the audio sub-fabric, and employs Inter-Processor Communication (IPC) mechanism to communicate with the SoC Processor Core.

The Audio subsystem includes two OCP-based DMA engines. These DMA engines support single and multi-block transfers. They can be configured to transfer data between DRAM and audio CCMs or transfer data between CCMs and the audio peripheral interfaces

All these interfaces are peripherals in the Audio subsystem. LPE, LPE DMA, or the SoC processor core may access the peripherals during normal operation. The PMC may access all peripherals during specific tasks such as at boot time or during power state changes. A complete audio solution based on an internal audio processing engine which includes several I²S-based output ports.

The audio core used is a dedicated audio DSP core designed specifically for audio processing (decoding, post-processing, mixing, etc.)


Note: LPE requires systems with more than 512MB memory. This is required since the LPE firmware must reside at a stolen memory location on 512MB boundaries below 3 GiB. The LPE firmware itself is ~1MB, and is reserved by BIOS for LPE use.

21.3 Detailed Block Level Description

21.3.1 LPE Core

The LPE core in the SoC runs at maximum frequency of 343 MHz and interfaces with the rest of the SoC system through the OCP bus. It is one of the masters on the Audio Sub-Fabric. The SoC Processor Core and LPE DMA engines are the other masters on the fabric. The following figure shows the LPE core and its interfaces.

Figure 106.Audio Cluster Block Diagram





The main DSP hardware is a two-multiplier, multiply/accumulate unit, a register file LPE_PR to hold pairs of 24-bit data items, a register file LPE_OR to hold 56-bit accumulator values, an arithmetic/logic unit to operate on the LPE_PR and LPE_OR values, and a shift unit to operate on the LPE_PR and LPE_OR values. The multiply/accumulate unit also supports multiplication of 32-bit values from LPE_OR registers by 16-bit values from LPE_PR registers, with the 48-bit result written or accumulated in the LPE_OR register. The instructions for the DSP subsystems are built from operations that are divided into two sets: the slot 0 set and the slot 1 set. In each execution cycle, zero or one operations from each set can be executed independently according to the static bundling expressed in the machine code.

21.3.2 Memory Architecture

The LPE core is configured to use local memory and local caches. It has 80KB of Instruction Closely Coupled Memory (CCM), 160KB of Data CCM, 48KB of Instruction Cache and 96KB of Data Cache. The LPE core also has access to 4KB of mailbox memory and external DRAM.

Figure 107. Memory Connections for LPE





21.3.3 Instruction Closely Coupled Memory (CCM)

Instruction CCM for the core is used for loading commonly used routines as well as time-critical processing. Examples of time critical processing are acoustic echo cancellation and noise cancellation during voice calls.

Instruction CCM is initialized after reset by an external DMA controller. Runtime update of instruction CCM can be done either using explicit instructions or using an external DMA controller with inbound access.

21.3.4 Data Closely Coupled Memory (CCM)

Data CCM can be initialized after reset by an external DMA controller using inbound access. Runtime update of data CCM can be done either using stores to Data CCM or using an external DMA controller with inbound access.

21.3.5 Mailbox Memory and Data Exchange

The mailbox memory is a shared memory region in LPE address space that is accessible by the SoC Processor Core, PMC, and LPE. It is used when Doorbell registers cannot hold all the information that one processor wishes to communicate to the other. A typical example of such data blocks are audio stream related parameters when starting a new stream. The structures of data communicated through the mailbox are not defined in hardware so that software may partition the mailbox memory in any desired way and create any meaningful structures required.

21.4 Software Implementation Considerations

21.4.1 SoC Processor Core Cache Coherence

Traffic generated by the LPE core is considered non-cacheable and non-coherent with respect to the SoC Processor Core cache. DMA traffic is considered cacheable and checked for coherency with the SoC Processor Core cache.

Implications of this implementation are as follows:

- All code and tables for the LPE core need to be explicitly flushed from the SoC Processor Core cache if they are ever accessed.
- If the LPE core directly accesses data buffers in system DDR, the driver must explicitly flush the buffer from the SoC Processor Core cache
- If DMA accesses data buffers from system DRAM, the driver need not flush the data buffer from the SoC Processor Core cache.



21.4.2 Interrupts

21.4.2.1 LPE Peripheral Interrupts

Each of the LPE peripherals generates its own interrupts. SSP0, SSP1, and SSP2 have one interrupt each. Each of the DMA channels have individual interrupt lines. These interrupts are connected to the LPE core through the PISR register. The same interrupts are routed to IOAPIC through the ISRX register. The LPE core and SoC Processor Core have individual masks to enable these interrupts.

21.4.2.2 Interrupts Between SoC Processor Core and the LPE

The interrupts between the SoC Processor Core and the LPE are handled through the inter-processor communication registers. Whenever the SoC Processor Core writes to the IPCX communication register an interrupt is generated to the LPE. The LPE firmware sees there is a message waiting from the SoC Processor Core, and reads the IPCX register for the data. This data is a pre-configured message, where the message structure has been decided beforehand between the SoC Processor Core and the LPE. Similarly we have the IPCD register for the communication between the LPE and SoC Processor Core. Once the LPE writes to the IPCD register, an interrupt should be generated for the SoC Processor Core and the SoC Processor Core should read the message from the IPCD register and act accordingly. From a software viewpoint, the mechanism remains the same as before. From a hardware view point, the interrupt to IA-32 gets routed by means of the IOAPIC block. The IPC from Audio to SoC Processor Core gets a dedicated interrupt line to the IOAPIC.

21.4.2.3 Interrupts between PMC and LPE

The interrupts between PMC and LPE are also handled using Inter Process Communication registers.

21.4.3 Power Management Options for the LPE Core

- WAITI
 - Allows the LPE core to suspend operation until an interrupt occurs by executing the optional WAITI instruction.
- External Run/Stall Control Signal
 - This processor input allows external logic to stall large portions of the LPE pipeline by shutting off the clock to much of the processor's logic to reduce operating power when the LPE computational capabilities are not immediately needed by the system.

Note: Using the WAITI instruction to power down the processor will save more power than use of the external run/stall signal because the WAITI instruction disables more of the LPE's internal clocks.



21.4.4 External Timer

This timer always runs from SSP clock (before M/N divider) at 19.2/25MHz. The timer starts running once the run bit (refer to the External timer register definition for details) is set and the clear bit is cleared.

The timer generates an Interrupt pulse when the counter value matches the “match” value. The interrupt does not get generated if the match value is set to “0”. The timer runs in free running mode and rolls over after all 32 bits have become all 1’s.

The timer continues to run as long as the run bit is set. Once the run bit is cleared the timer holds the current value. The clear bit needs to be set to restart the timer from “0”.

21.5 Clocks

21.5.1 Clock Frequencies

Table 227 shows the clock frequency options for the Audio functional blocks.

Table 227. Clock Frequencies

Clock	Frequency	Notes
Audio core	25/50/100/200/267/343 MHz	Audio input clock trunk. CCU drives one of several frequencies as noted.
DMA 0	25/50 MHz	DMA clock
DMA1	25/50 MHz	DMA clock
Audio fabric clock	25/50 MHz	Fabric clock derived from audio core clock
SSP0 Clock	Fabric side: 25/50 MHz Link side: Up to 19.2/25 MHz	SSP0 clock domains
SSP1 Clock	Fabric side: 25/50 MHz Link side: Up to 19.2/25 MHz	SSP1 clock domains
SSP2 Clock	Fabric side: 25/50 MHz Link side: Up to 19.2/25 MHz	SSP2 clock domains

21.5.2 50 MHz Clock for LPE

50 MHz, the 2X OSC clock, is added to increase MIPS for low power MP3 mode. This frequency will be supplied by the clock doubler internal to the SoC’s Clock Control Unit.

21.5.3 Cache and CCM Clocking

Data CCM, Data cache, Instruction CCM, and Instruction Cache run off of the LPE clock. These memories are in a single clock domain.

Note: All Data CCM and Instruction CCM run in the same clock domain.

21.5.4 SSP Clocking

SSP could be used as either clock masters or clock slaves. Consequently, these IP have dual clock domains.

The first clock domain is clocked from an internal clock (e.g., fabric clock) and is used for generic logic like interrupt generation and register access.

The second clock domain drives the serial shift register (either driven internally or externally). When driven internally, this clock can be sourced from XTAL clock 25 MHz or PLL 19.2 MHz. These clocks are then divided down within the serial interface IP to generate the final bit clock for the interface.


After power on, if the SSP input IO clock is in high state, first transition of the clock from high to low may be missing due to the Soc clock gating logic.

Note: “Frame Master” mode cannot be used when operating as clock slave and “Frame Slave” mode cannot be used when operating as clock master.

21.5.5 M/N Divider

LPE SSP in master mode uses the SSP CCLK to drive the serial clock. It has very limited option to divide CCLK. An M/N divider is added between the 19.2/25 MHz clock (XOSC) from CCU to each SSP CCLK input as shown in following diagram:

Figure 108.SSP CCLK Structure



Note: The maximum SSP CCLK frequency is listed in Table 132.



The LPE M/N divider is designed to produce a clock signal for the SSP block used in master mode. The divider is based on a generic NOM/DENOM divider. The supplied Master clock is 25 MHz (XTAL) or 19.2 MHz (LPPLL), but usually be used by the 25 MHz clock.

This mechanism is good for a wide spectrum of generated clocks. Two registers must be configured to get the target SSP clock. The values for the Nominator and Denominator registers are the smallest divider of:

$$\frac{\text{Nominator}}{\text{Denominator}} = \frac{\text{Source_clock}}{\text{Target_clock}}$$

21.5.5.1 Example

If we want to generate 17.64 MHz (=400x44.1 KHz) output clock out of 25 MHz clock, we need to program "NOM = 441" and "DENOM = 625":

$$17.64 \text{ MHz} = (441/625) \times 25 \text{ MHz}$$

In general the M over N can generate fractional divisor that could be used for generating the required clocks for Audio codec. [Table 228](#) describes some configuration options of this generic divider:

Table 228. M/N Values, Examples

Source Clock Frequency	Requested Clock	M/N Value
25 MHz	48 KHz	6/3125
	48K x 24 = 1.152 MHz	1152/25000
	48K x 32 = 1.536 MHz	1536/25000
	48K x 64 = 3.072 MHz	3072/25000
	44.1 KHz	441/250000
	48K x 400 = 19.2 MHz	96/125
	44.1K x 400 = 17.64 MHz	441/625

21.5.5.2 Accuracy and Jitter

The output of the M/N is equal to the desired clock in average with Jitter of 20nTXE for 25 MHz input clock.

21.5.5.3 Configuration

Following configurable fields per M/N divider/SSP are in LPE shim registers:

**Table 229. M/N Configurable Fields**

Field	Width	Description
Bypass	1 bit	When set M/N divider is bypass. Clock from CCU is connected directly to SSP CCLK
EN	1 bit	Enable the divider
Update	1 bit	Update divider parameters
M Value	20 bits	Nominator value
N Value	20 bits	Denominator value

21.6 SSP (I²S)

The SoC audio subsystem consists of the LPE Audio Engine and three Synchronous Serial Protocol (SSP) ports. These ports are used in PCM mode and enable simultaneous support of voice and audio streams over I²S. The SoC audio subsystem also includes two DMA controllers dedicated to the LPE. The LPE DMA controllers are used for transferring data between external memory and CCMs, between CCMs and the SSP ports, and between CCMs. All peripheral ports can operate simultaneously.

21.6.1 Introduction

The Enhanced SSP Serial Ports are full-duplex synchronous serial interfaces. They can connect to a variety of external analog-to-digital (A/D) converters, audio, and telecommunication codecs, and many other devices which use serial protocols for transferring data. Formats supported include National* Microwire, Texas Instruments* Synchronous Serial Protocol (SSP), Motorola* Serial Peripheral Interface (SPI) protocol and a flexible Programmable Serial Port protocol (PSP).

The Enhanced SSPs operate in master mode (the attached peripheral functions as a slave) or slave mode (the attached peripheral functions as a master), and support serial bit rates from 0 to 25 Mbps, dependent on the input clock. Serial data formats range from 4 to 32-bits in length. Two on-chip register blocks function as independent FIFOs for transmit and receive data.

FIFOs may be loaded or emptied by the system processor using single transfers or DMA burst transfers of up to the FIFO depth. Each 32-bit word from the bus fills one entry in a FIFO using the lower significant bits of a 32-bit word.

21.6.2 SSP Features

The SSP port features are:

- Inter-IC Sound (I²S) protocols, are supported by programming the Programmable Serial Protocol (PSP).
- One FIFO for transmit data (TXFIFO) and a second, independent, FIFO for receive data (RXFIFO), where each FIFO is 16 samples deep x 32 bits wide
- Data sample sizes from 8, 16, 18 and 24bits



- 12.5 Mbps maximum serial bit-rate in both modes: master and slave.
- Clock master or slave mode operations
- Receive-without-transmit operation
- Network mode with up to eight time slots for PSP formats, and independent transmit/receive in any/all/none of the time slots.
- After updating SSP configuration, for example active slot count, the SSP will need to be disabled and enabled again. In other words, a SSP will not function correctly if a user changes the configuration setting on the fly.

21.6.3 Operation

Serial data is transferred between the LPE core or the SoC Processor Core and an external peripheral through FIFOs in one of the SSP ports. Data transfers between an SSP port and memory are initiated by either the LPE core or the SoC Processor Core using programmed I/O, or by DMA bursts. Although it is possible to initiate transfers directly from the SoC Processor Core, current driver design uses LPE for all PCM operations. Separate transmit and receive FIFOs and serial data paths permit simultaneous transfers in both directions to and from the external peripheral, depending on the protocols chosen.

Programmed I/O can transfer data between:

- The LPE core and the FIFO Data register for the TXFIFO
- The SoC Processor Core and the FIFO Data register for the TXFIFO
- The LPE core and the FIFO Data register for the RXFIFO
- The SoC Processor Core and the FIFO Data register for the RXFIFO
- The SoC Processor Core and the control or status registers
- The LPE core and the control or status registers

DMA bursts can transfer data between:

- Universal memory and the FIFO Data register for the TXFIFO
- Universal memory and the FIFO Data register for the RXFIFO
- Universal memory and the sequentially addressed control or status registers

21.6.4 LPE and DMA FIFO Access

The LPE or DMA access data through the Enhanced SSP Port's Transmit and Receive FIFOs. An LPE access takes the form of programmed I/O, transferring one FIFO entry per access. LPE accesses would normally be triggered off of an SSSR Interrupt and must always be 32 bits wide. LPE Writes to the FIFOs are 32 bits wide, but the serializing logic will ignore all bits beyond the programmed FIFO data size (EDSS/DSS value). LPE Reads to the FIFOs are also 32 bits wide, but the Receive data written into the RX FIFO (from the RXD line) is stored with zeroes in the MSBs down to the programmed data size. The FIFOs can also be accessed by DMA bursts, which must be



in multiples of 1, 2 or 4 bytes, depending upon the EDSS value, and must also transfer one FIFO entry per access. When the SSCR0.EDSS bit is set, DMA bursts must be in multiples of 4 bytes (the DMA must have the Enhanced SSP configured as a 32-bit peripheral). The DMA's width register must be at least the SSP data size programmed into the SSP control registers EDSS and DSS. The FIFO is seen as one 32-bit location by the processor. For Writes, the Enhanced SSP port takes the data from the Transmit FIFO, serializes it, and sends it over the serial wire (I2S[2:0]_DATAOUT) to the external peripheral. Receive data from the external peripheral (on I2S[2:0]_DATAIN) is converted to parallel words and stored in the Receive FIFO.

A programmable FIFO trigger threshold, when exceeded, generates an Interrupt or DMA service request that, if enabled, signals the CPU or DMA respectively to empty the Receive FIFO or to refill the Transmit FIFO.

The Transmit and Receive FIFOs are differentiated by whether the access is a Read or a Write transfer. Reads automatically target the Receive FIFO, while Writes will write data to the Transmit FIFO. From a memory-map perspective, they are at the same address. FIFOs are 16 samples deep by 32 bits wide. Each read or write is to 1 SSP sample.


21.6.5 Supported Formats

The SSP consists of four pins that are used to transfer data between the SoC and external Audio codecs, modems, or other peripherals. Although four serial-data formats exist, each has the same basic structure, and in all cases the following pins are used in the following manner:

- I2Sx_CLK—Defines the bit rate at which serial data is driven onto and sampled from the port
- I2Sx_FRM—Defines the boundaries of a basic data "unit," comprised of multiple serial bits
- I2Sx_DATAIN—The serial data path for transmitted data, from system to peripheral
- I2Sx_DATAOUT—The serial data path for received data, from peripheral to system

A data frame can contain from 4 to 32 bits, depending on the selected format. Serial data is transmitted most significant bit first. The Programmable Serial Protocol (PSP) format is used to implement I²S.

Master and Slave modes are supported. When driven by the Enhanced SSP, the I2Sx_CLK only toggles during active transfers (not continuously) unless ECRA/ECRB functions are used. When the I2Sx_CLK is driven by another device, it is allowed to be either continuous or only driven during transfers, but certain restrictions on PSP parameters apply.



Normally, the serial clock (I2Sx_CLK), if driven by the Enhanced SSP Port, only toggles while an active data transfer is underway. There are several conditions, however, that may cause the clock to run continuously. If the Receive With Out Transmit mode is enabled by setting the SSCR1.RWOT bit to 1, the I2Sx_CLK will toggle regardless of whether Transmit data exists within the Transmit FIFO. The I2Sx_CLK will also toggle continuously if the Enhanced SSP is in Network mode, or if ECRA, or ECRB is enabled. At other times, I2Sx_CLK will be held in an inactive I2Sx_FRM or idle state, as defined by the specified protocol under which it operates.

21.6.5.1 Programmable Serial Protocol (PSP)

There are many variations of the frame behavior for different codecs and protocol formats. To allow flexibility the PSP format allows I2Sx_FRM to be programmable in direction, delay, polarity, and width. Master and Slave modes are supported. PSP can be programmed to be either full or half duplex.

The I2Sx_CLK function behavior varies between each format. PSP lets programmers choose which edge of I2Sx_CLK to use for switching Transmit data, and for sampling Receive data. In addition, programmers can control the idle state for I2Sx_CLK and the number of active clocks that precede and follow the data transmission.

The PSP format provides programmability for several parameters that determine the transfer timings between data samples. There are four possible serial clock sub-modes, depending on the I2Sx_CLK edges selected for driving data and sampling received data, and the selection of idle state of the clock.

For the PSP format, the Idle and Disable modes of the I2Sx_DATAOUT, I2Sx_CLK, and I2Sx_FRM are programmable by means of the SSPSP.ETDS, SSPSP.SCMODE and SSPSP.SFRMP bits. When Transmit data is ready, the I2Sx_CLK will remain in its Idle state for the number of serial clock (I2Sx_CLK) clock periods programmed within the Start Delay (SSPSP.STRTDLY) field. I2Sx_CLK will then start toggling, I2Sx_DATAOUT will remain in the idle state for the number of cycles programmed within the Dummy Start (SSPSP.DMYSTRT) field. The I2Sx_FRM signal will be asserted after the number of half-clocks programmed in the SSPSP.SFRDLY field. The I2Sx_FRM signal will remain asserted for the number of clocks programmed within the SSPSP.SFRMWDTH then de-assert. Four to 32 bits can be transferred per frame. Once the last bit (LSB) is transferred, the I2Sx_CLK will continue toggling based off the Dummy Stop (SSPSP.DMYSTOP) field. I2Sx_DATAOUT either retains the last value transmitted or is forced to zero, depending on the value programmed within the End of Transfer Data State (SSPSP.ETDS) field, when the controller goes into Idle mode, unless the Enhanced SSP port is disabled or reset (which forces I2Sx_DATAOUT to zero).

With the assertion of I2Sx_FRM, Receive data is simultaneously driven from the peripheral on I2Sx_DATAIN, most significant bit first. Data transitions on I2Sx_CLK based on the Serial Clock Mode selected and is sampled by the controller on the opposite edge. When the Enhanced SSP is a master to the frame synch (I2Sx_FRM) and a slave to the clock (I2Sx_CLK), then at least three extra clocks (I2Sx_CLKs) will be needed at the beginning and end of each block of transfers to synchronize control signals from the APB clock domain into the SSP clock domain (a block of transfers is a group of back-to-back continuous transfers).

Figure 109. Programmable Serial Protocol Format





Figure 110. Programmable Serial Protocol Format (Consecutive Transfers)




**Table 230. Programmable Protocol Parameters**

Symbol	Definition (Register.Bit Field)	Range	Units
	Serial Clock Mode (SSPSP.SCMODE)	(Drive, Sample, I2Sx_CLK Idle) 0 = Fall, Rise, Low 1 = Rise, Fall, Low 2 = Rise, Fall, High 3 = Fall, Rise, High	
	Serial Frame Polarity (SSPSP.SFRMP)	High or Low	
T1	Start Delay (SSPSP.STRTDLY)	0–7	Clock Period
T2	Dummy Start (SSPSP.DMYSTRT)	0–3	Clock Period
T3	Data Size (SSCRO.EDSS AND SSCRO.DSS)	4–32	Clock Period
T4	Dummy Stop (SSPSP.DMYSTOP)	0–3	Clock Period
T5	I2Sx_FRM Delay (SPSP.SFRMDLY)	0–88	Half Clock Period
T6	I2Sx_FRM Width (SSPSP.SFRMWDTH)	1–44	Clock Period
	End of Transfer Data State (SSPSP.ETDS)	Low or [bit 0]	

Note: The I2Sx_FRM Delay must not extend beyond the end of T4. I2Sx_FRM Width must be asserted for at least 1 I2Sx_CLK, and should be de-asserted before the end of the T4 cycle (for example, in terms of time, not bit values, $(T5 + T6) \leq (T1 + T2 + T3 + T4)$, $1 \leq T6 < (T2 + T3 + T4)$, and $(T5 + T6) \geq (T1 + 1)$ to ensure that I2Sx_FRM is asserted for at least 2 edges of the I2Sx_CLK). The T1 Start Delay value should be programmed to 0 when the I2Sx_CLK is enabled by either of the SSCR1.ECRA or SSCR1.ECRB bits. While the PSP can be programmed to generate the assertion of I2Sx_FRM during the middle of the data transfer (after the MSB was sent), the Enhanced SSP will not be able to receive data in Frame slave mode (SSCR1SFRMDIR = 1) if the assertion of Frame is not before the MSB is sent (i.e. $T5 \leq T2$ if SSCR1.SFRMDIR = 1). Transmit Data will transition from the “End of Transfer Data State” to the next MSB value upon the assertion of Frame. The Start Delay field should be programmed to 0 whenever I2Sx_CLK or I2Sx_FRM is configured as an input. Clock state is not defined between two active frame periods. Clock can be active or inactive between two active frame periods.

21.7 Programming Model

The CPU or DMA access data through the Enhanced SSP Port’s Transmit and Receive FIFOs. A CPU access takes the form of programmed I/O, transferring one FIFO entry per access. CPU accesses would normally be triggered off of an SSSR Interrupt and



must always be 32 bits wide. The CPU Writes to the FIFOs are 32 bits wide, but the serializing logic will ignore all bits beyond the programmed FIFO data size (EDSS/DSS value). CPU Reads to the FIFOs are also 32 bits wide, but the Receive data written into the RX FIFO (from the RXD line) is stored with zeroes in the MSBs down to the programmed data size. The FIFOs can also be accessed by DMA bursts, which must be in multiples of 1, 2, or 4 bytes, depending upon the EDSS value, and must also transfer one FIFO entry per access. When the SSCR0.EDSS bit is set, DMA bursts must be in multiples of 4 bytes (the DMA must have the Enhanced SSP configured as a 32-bit peripheral). The DMA DCMD.width register must be at least the SSP data size programmed into the SSP control registers EDSS and DSS. The FIFO is seen as one 32-bit location by the processor. For Writes, the Enhanced SSP port takes the data from the Transmit FIFO, serializes it, and sends it over the serial wire (I2Sx_DATAOUT) to the external peripheral. Receive data from the external peripheral (on I2Sx_DATAIN) is converted to parallel words and stored in the Receive FIFO.

A programmable FIFO trigger threshold, when exceeded, generates an Interrupt or DMA service request that, if enabled, signals the IA-32 CPU or DMA respectively to empty the Receive FIFO or to refill the Transmit FIFO. The Transmit and Receive FIFOs are differentiated by whether the access is a Read or a Write transfer. Reads automatically target the Receive FIFO, while Writes will write data to the Transmit FIFO. From a memory-map perspective, they are at the same address. Each read or write is 1 SSP sample.

21.7.1 PIO and DMA Programming Considerations

All CPU and DMA accesses transfer one FIFO entry per access. Data in the FIFOs is always stored with one 32-bit value per data sample, regardless of the format data word length. Within each 32-bit field, the stored data sample is right-justified, with the least significant bit of the word in bit 0. In the Receive FIFO, unused bits are packed as zeroes above the most significant bit. In the Transmit FIFO, unused don't-care bits are above the most significant bit (i.e., DMA and CPU access do not have to write to the unused bit locations). Logic in the Enhanced SSP automatically formats data in the Transmit FIFO so that the sample is properly transmitted on I2Sx_DATAOUT in the selected frame format.

Two separate and independent FIFOs are present for Transmit (to peripheral) and Receive (from peripheral) serial data. FIFOs are filled or emptied by programmed I/O or DMA bursts.

21.7.1.1 Programmed IO Considerations

FIFO filling and emptying can be performed by the processor in response to an Interrupt from the FIFO logic. Each FIFO has a programmable FIFO trigger threshold at which an Interrupt is triggered. When the number of entries in the Receive FIFO exceeds the SSCR1.RFT value, an interrupt is generated (if enabled), which signals the CPU to empty the Receive FIFO. When the number of entries in the Transmit FIFO is less than or equal to the SSCR1.TFT value plus 1, an Interrupt is generated (if enabled), which signals the CPU to refill the Transmit FIFO.



Users can also poll the Enhanced SSP Status register to determine how many samples are in a FIFO, and whether the FIFO is full or empty. Software is responsible for ensuring that the proper RFT and TFT values are chosen to prevent ROR and TUR error conditions.

Note: If the software attempts to read from an empty Receive FIFO, it will receive a duplicate of the previously read value.

21.7.1.2 DMA Considerations

The DMA controller can also be programmed to transfer data to and from the Enhanced SSP FIFOs. To prevent over-runs of the Transmit FIFO or under-runs of the Receive FIFO when using the DMA, be careful when setting the Transmit and Receive FIFO trigger threshold levels.

There are restrictions on how the DMA can be programmed when used with the SSP Controller.

- The DMA Transfer Width must be greater than or equal to the SSP data size. For example if the SSP Data Size is 16b then the DMA Transfer Width should be 16b.
- The DMA may not support the DMA Transfer Width of the SSP Data Size and therefore the DMA Transfer Width must be larger than the SSP Data Size. If this is the case then software must manage any extra data bits.
- The DMA Burst Transaction Length for RX must be less than or equal to the RX Threshold.
- The DMA Burst Transaction Length for TX must be less than or equal to the number of empty locations in the TX FIFO. A safe value is the Total TX FIFO Size - TX Threshold.
- DMA must be in Fixed Address mode to read or write the SSP Data Register.

In full-duplex formats where the Enhanced SSP always receives the same number of data samples as it transmits, the DMA should be set up to transmit and receive the same number of bytes.

Note: A TFT value of 0 means that there is one sample left in the TX FIFO.

Because the Enhanced SSP is not flow controlled, software must program the TX FIFO Threshold (TFT), RX FIFO Threshold (RFT), and the DMA burst size to ensure that a TX FIFO overflow or RX FIFO underflow does not occur. Software must also ensure that the Enhanced SSP DMA requests are properly prioritized in the system to prevent fatal overruns and under-runs.

The programming model for using the DMA is as follows:

- Program the total number of Transmit/Receive byte lengths, DMA burst, and DMA Width in the DMA.
- Set the preferred values in the Enhanced SSP Control registers.
- Enable the Enhanced SSP by setting SSCR0.SSE.
- Set the run bit in DMA Command Register.



- The DMA will wait for either the Transmit or Receive Service requests.
- If the Transmit/Receive byte length is not an even multiple of the transfer burst size, a trailing byte condition may occur.

21.7.2 Trailing Bytes in the Receive FIFO

When the number of samples in the Receive FIFO is less than its FIFO trigger threshold level, and no additional data is received, the remaining bytes are called trailing bytes. Trailing bytes can be handled by either the DMA or the processor, as indicated by the SSCR1.TRAIL bit. Trailing bytes are identified by means of a timeout mechanism and the existence of data within the Receive FIFO.

21.7.2.1 Timeout

A timeout condition exists when the Receive FIFO has been idle for a period of time (in APB clocks) defined by the value programmed within the Timeout register (SSTO). When a timeout occurs, the receiver timeout interrupt SSSR.TINT bit will be set to a 1, and if the Timeout Interrupt is enabled SSCR1.TINTE=1, a Timeout Interrupt will occur to signal the processor that a timeout condition has occurred. The timeout timer is reset after a new sample is received. Once the SSSR.TINT bit is set it must be cleared by software by writing a 1 to it. Clearing this bit also causes the Timeout Interrupt, if enabled, to be de-asserted.


21.7.2.2 Peripheral Trailing Byte Interrupt

It is possible for the DMA to reach the end of its Descriptor chain while removing Receive FIFO data. When this happens, the processor is forced to take over because the DMA can no longer service the Enhanced SSP request until a new chain is linked. When the DMA has reached the end of its Descriptor chain, and there is data in the receive FIFO, the Enhanced SSP will do the following:

- Sets the peripheral trailing byte interrupt SSSR.PINT bit to 1
- Asserts the Enhanced SSP Interrupt to signal to the processor that a Peripheral Trailing Byte Interrupt condition has occurred (if SSCR1.PINTE=1 to enable the interrupt).
- Sets the SSSR.EOC status bit which must be cleared by software. If more data is received after the EOC bit was set (and EOC bit is still set), then the SSSR.PINT bit will be set to a 1.

Once the SSSR.PINT bit is set, it must be cleared by software by writing a 1 to it. Clearing the SSSR.PINT bit also de-asserts the Peripheral Interrupt if it has been enabled (SSCR1.PINTE=1).

The remaining bytes must then be removed by means of a processor I/O as described in the processor-based method below, or by reprogramming a new Descriptor chain and restarting the DMA. Programmers need to be aware of this possibility. Refer to the DMA chapter for details on Descriptor programming and “end of chain” events.



21.7.2.3 Removing Trailing Bytes (Processor Based SSCR1.TRAIL=0)

This is the default method indicated by a zero in the SSCR1.TRAIL bit. In this case, no Receive DMA service request is generated. To read out the trailing bytes, software should wait for the timeout Interrupt and then read all remaining entries as indicated by the SSSR.RFL and SSSR.RNE bits within the Enhanced SSP Status register (SSSR).

Note: To use the Trailing bytes feature through the CPU, the Timeout Interrupt must be enabled by setting SSCR1.TINTE=1 (to enable the interrupt).


21.7.2.4 Removing Trailing Bytes (DMA Based SSCR1.TRAIL=1)


When the DMA is to handle trailing bytes (SSCR1.TRAIL = 1) a DMA service request is automatically issued for the remaining number of samples left in the Receive buffer. The DMA will then empty the contents of the Receive buffer unless the DMA reaches the end of its Descriptor chain. If a timeout occurs, the processor is only interrupted by means of a Timeout Interrupt if it has been enabled by setting SSCR1.TINTE=1. When handling trailing bytes by means of the DMA, if a timeout occurs and the receive FIFO is empty, an End-of-Receive (EOR) will be sent to the DMA Controller. If an EOC occurs at the time that the last sample is read out of the FIFO (the DMA descriptor chain was just exactly long enough), and the timeout counter is still running (that is, a time out has not occurred and the SSTS register is non-zero), then, when the time out does occur, the Enhanced SSP will generate a DMA request which will create an RAS interrupt from the DMA. When this occurs, software must re-program the DMA registers and re-enable the channel for the Enhanced SSP to send its EOR to the DMA controller.



21.8 Register Map

Figure 111.Low Power Engine for Audio Register Map





Type: Memory Mapped I/O Register
(Size: 32 bits)

STATUSCOMMAND: [0/21/0] + 4h

Default: 00100000h

31				28				24				20				16				12				8				4				0																											
0				0				0				0				0				0				0				0				0																											
Reserved0				RMA				RCA				Reserved1				CAPLIST				INTR_STATUS				Reserved2				Reserved3				INTR_DISABLE				Reserved4				SERR_ENABLE				Reserved5				BME				MSE				Reserved6			

Bit Range	Default & Access	Description
31:30	0h RO	Reserved0: reserved
29	0h RW/1C	RMA: Received Master Abort: Not Implemented
28	0h RW/1C	RCA: Received Target Abort: Not Implemented
27:21	00h RO	Reserved1: reserved
20	1h RO	CAPLIST: Capabilities List: Indicates that the controller contains a capabilities pointer list. The first item is pointed to by looking at the configuration offset 34h.
19	0h RO	INTR_STATUS: Interrupt Status: This bit reflects state of interrupt in the device Only when the Interrupt Disable bit in the command register is a 0 and this Interrupt Status bit is a 1, is the device/function interrupt message sent. Setting the Interrupt Disable bit to a 1 has no effect on the state of this bit. This bit reflects Legacy interrupt status.
18:16	0h RO	Reserved2: reserved
15:11	00h RO	Reserved3: reserved
10	0h RW	INTR_DISABLE: Setting this bit disables INTx assertion from Bridge. The interrupt disabled is legacy INTx# interrupt, which is the Bridge does not send Interrupt Assert message through the IOSF Sideband Channel. Reset value of this bit is 0. This bit has no connection with the interrupt status bit
9	0h RO	Reserved4: reserved
8	0h RW	SERR_ENABLE: not implemented
7:3	00h RO	Reserved5: reserved
2	0h RW	BME: If this bit is 0, the Bridge does not generate any new upstream transaction on IOSF as a master. Reset value of this bit is 0.
1	0h RW	MSE: Memory Space Enable: This bit controls Bridge response to downstream memory accesses. When set, accesses to memory space of the device is enabled. Reset value of this bit is 0.
0	0h RO	Reserved6: reserved



21.9.3 reg_REVCLASSCODE_type (REVCLASSCODE)—Offset 8h

REVCLASSCODE - Revision ID and Class Code

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

REVCLASSCODE: [0/21/0] + 8h

Default: 04010000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	0	0	0
0	1	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Description
31:8	040100h RO	CLASS_CODES: Class Code
7:0	00h RO	RID: Revision ID

21.9.4 reg_CLLATHEADERBIST_type (CLLATHEADERBIST)—Offset Ch

CLLATHEADERBIST - Cache Line Latency Header and BIST

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CLLATHEADERBIST: [0/21/0] + Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0			MULFNDEV	HEADERTYPE	LATTIMER	CACHELINE_SIZE		

Bit Range	Default & Access	Description
31:24	00h RO	Reserved0: Reserved
23	0h RO	MULFNDEV: MULFNDEV
22:16	00h RO	HEADERTYPE: Header Type: Implements Type 0 Configuration header.



BAR -Base Address Register

Type: Memory Mapped I/O Register
(Size: 32 bits) **BAR:** [0/21/0] + 10h

31				28				24				20				16				12				8				4				0															
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																
BASEADDR																SIZEINDICATOR																PREFETCHABLE				TYPE				MESSAGE_SPACE							

21.9.6 reg_BAR1_type (BAR1)—Offset 14h

Type: Memory Mapped I/O Register (Size: 32 bits) **BAR1:** [0/21/0] + 14h

October 2018
Document Number: 538136, Rev. 4.3





Access Method

EXPANSION ROM BASEADDR: [0/21/0] + 30h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSTON_ROM_BASE								

Bit Range	Default & Access	Description
31:0	00000000h RO	EXPANSION_ROM_BASE: Value of all zeros indicates no support for Expansion ROM

21.9.9 reg_CAPABILITYPTR_type (CAPABILITYPTR)—Offset 34h

CAPABILITYPTR - Capabilities Pointer

Access Method

CAPABILITYPTR: [0/21/0] + 34h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Description
31:8	000000h RO	Reserved0: reserved
7:0	80h RO	CAPPTR_POWER: Indicates what the next capability is. This capability points to the PM Capability, 0x80, structure.



21.9.10 reg_INTERRUPTREG_type (INTERRUPTREG)—Offset 3Ch

INTERRUPTREG - Interrupt Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

INTERRUPTREG: [0/21/0] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
MAX_LAT				MIN_GNT				INTPIN
				Reserved0				INTLINE

Bit Range	Default & Access	Description
31:24	00h RO	MAX_LAT: Value of 0 indicates device has no major requirements for the settings of latency timers
23:16	00h RO	MIN_GNT: Value of 0 indicates device has no major requirements for the settings of latency timers
15:12	0h RO	Reserved0: reserved
11:8	1h RO	INTPIN: Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space. For a single function device, this ideally is INTA
7:0	00h RW	INTLINE: Bridge does not use this field directly. It is used to communicate to software, the interrupt line to which the interrupt pin is connected.

21.9.11 reg_POWERCAPID_type (POWERCAPID)—Offset 80h

POWERCAPID - PowerManagement Capability ID

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

POWERCAPID: [0/21/0] + 80h

Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	1	1	0	0	0
PMESUPPORT				Reserved0				POWER_CAP
				VERSION				
				NXTCAP				





Bit Range	Default & Access	Description
2	0h RO	Reserved3: reserved
1:0	0h RW	POWERSTATE: This field is used both to determine the current power state and to set a new power state.[BR]The values are: 00 D0 state 11 D3HOT state Others Reserved Note: If the software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally. The data is discarded and no state change occurs. Note: When in the D3HOT states, interrupts are blocked. D3Hot cannot be used for downstream decode on fabric ports.

21.9.13 reg_MANID_type (MANID)—Offset F8h

Manufacturers ID

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MANID: [0/21/0] + F8h

Default: 01000F00h

31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

MANID

Bit Range	Default & Access	Description
31:0	01000f00h RO	MANID: Manufacturing ID

21.10 pci_mem Address Map

Table 232. Summary of Memory Mapped I/O Registers—0/21/0

Offset	Size	Register ID—Description	Default Value
0h	4	"reg_DEVVENDID_type (DEVVENDID)—Offset 0h" on page 2840	0F288086h
4h	4	"reg_STATUSCOMMAND_type (STATUSCOMMAND)—Offset 4h" on page 2840	00100000h
8h	4	"reg_REVCLASSCODE_type (REVCLASSCODE)—Offset 8h" on page 2841	04010000h
Ch	4	"reg_CLLATHEADERBIST_type (CLLATHEADERBIST)—Offset Ch" on page 2842	00000000h
10h	4	"reg_BAR_type (BAR)—Offset 10h" on page 2842	00000000h
14h	4	"reg_BAR1_type (BAR1)—Offset 14h" on page 2843	00000000h
2Ch	4	"reg_SUBSYSTEMID_type (SUBSYSTEMID)—Offset 2Ch" on page 2844	00000000h
30h	4	"reg_EXPANSION_ROM_BASEADDR_type (EXPANSION_ROM_BASEADDR)—Offset 30h" on page 2844	00000000h
34h	4	"reg_CAPABILITYPTR_type (CAPABILITYPTR)—Offset 34h" on page 2845	00000080h
3Ch	4	"reg_INTERRUPTREG_type (INTERRUPTREG)—Offset 3Ch" on page 2845	00000100h



SUBSYSTEMID -Subsystem Vendor and Subsystem ID


Type: Memory Mapped I/O Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SUBSYSTEMID					SUBSYSTEMVENDORID			

21.10.8 reg_EXPANSION_ROM_BASEADDR_type (EXPANSION_ROM_BASEADDR)—Offset 30h

Type: Memory Mapped I/O Register
(Size: 32 bits)

October 2018
Document Number: 538136, Rev. 4.3



21.10.9 reg_CAPABILITYPTR_type (CAPABILITYPTR)—Offset 34h

[illegible]

21.10.10 reg_INTERRUPTREG_type (INTERRUPTREG)—Offset 3Ch

Intel Atom[®] Processor E3800 Product Family
 Datasheet
 2845



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MAX_LAT				MIN_GNT				Reserved0
								INTPIN
								INTLINE

Bit Range	Default & Access	Description
31:24	00h RO	MAX_LAT: Value of 0 indicates device has no major requirements for the settings of latency timers
23:16	00h RO	MIN_GNT: Value of 0 indicates device has no major requirements for the settings of latency timers
15:12	0h RO	Reserved0: reserved
11:8	1h RO	INTPIN: Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space. For a single function device, this ideally is INTA
7:0	00h RW	INTLINE: Bridge does not use this field directly. It is used to communicate to software, the interrupt line to which the interrupt pin is connected.

21.10.11 reg_POWERCAPID_type (POWERCAPID)—Offset 80h

POWERCAPID - PowerManagement Capability ID

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

POWERCAPID: [0/21/0] + 80h

Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	1	1	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
PMESUPPORT				Reserved0				POWER_CAP

Bit Range	Default & Access	Description
31:27	00h RO	PMESUPPORT: This 5-bit field indicates the power states in which the function can assert the PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal at the same time in that power state. bit 11 X XXX1b: PME# can be asserted from D0 bit 12 X XX1Xb: PME# can be asserted from D1. Bridge does not support this state. bit 13 X X1XXb: PME# can be asserted from D2. Bridge does not support this state. bit 14 X 1XXXb: PME# can be asserted from D3hot bit 15 1 XXXXb: PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the private configuration space PME_Support XORed with the PME_Support strap.
26:19	00h RO	Reserved0: reserved
18:16	3h RO	VERSION: Indicates support for Revision 1.2 of the PCI Power Management Specification.



Bit Range	Default & Access	Description
15:8	00h RO	NXTCAP: Points to the next capability structure. This points to NULL
7:0	01h RO	POWER_CAP: Indicates this is power management capability.

21.10.12 reg_PMECTRLSTATUS_type (PMECTRLSTATUS)—Offset 84h

reserved

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

PMCTRLSTATUS: [0/21/0] + 84h

Default: 00000008h

31	28				24				20				16				12				8				4				0										
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0											
Reserved0																PMESTATUS	Reserved1								PMEENABLE	Reserved2								NO_SOFT_RESET	Reserved3				POWERSTATE

Bit Range	Default & Access	Description
31:16	0000h RO	Reserved0: reserved
15	0h RW/1C	PMESTATUS: 0 Software clears the bit by writing a 1 to it. 1 This bit is set when the PME# signal is asserted independent of the state of the PME Enable bit
14:9	00h RO	Reserved1: reserved
8	0h RW	PMEENABLE: pme enable
7:4	0h RO	Reserved2: reserved
3	1h RO	NO_SOFT_RESET: This bit indicates that devices transitioning from D3hot to D0 because of Powerstate commands do not perform an internal reset.Configuration Context is preserved.
2	0h RO	Reserved3: reserved
1:0	0h RW	POWERSTATE: This field is used both to determine the current power state and to set a new power state.[BR]The values are: 00 D0 state 11 D3HOT state Others Reserved Note: If the software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally. The data is discarded and no state change occurs. Note: When in the D3HOT states, interrupts are blocked. D3Hot cannot be used for downstream decode on fabric ports.



21.10.13 reg_MANID_type (MANID)—Offset F8h

Manufacturers ID

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


MANID: [0/21/0] + F8h

Default: 01000F00h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	1	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
1	1	1	1	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MANID								

Bit Range	Default & Access	Description
31:0	01000f00h RO	MANID: Manufacturing ID

§ §



21.11 Memory Mapped Shim Registers

Table 233. Summary of LPE Shim Memory Mapped I/O Registers—BAR

Offset	Size	Register ID—Description	Default Value
0h	8	"reg_CSR_type (CSR)—Offset 0h" on page 2850	0000000001E40001h
8h	8	"reg_XT_PISR_type (PISR)—Offset 8h" on page 2851	0000000000000000h
10h	8	"reg_XT_PIMR_type (PIMR)—Offset 10h" on page 2852	0000000000000000h
18h	8	"reg_IA_PISR_type (ISRX)—Offset 18h" on page 2853	0000000000000000h
20h	8	"reg_ISRD_type (ISRD)—Offset 20h" on page 2854	0000000000000000h
28h	8	"reg_IA_PIMR_type (IMRX)—Offset 28h" on page 2855	0000000000000000h
30h	8	"reg_IMRD_type (IMRD)—Offset 30h" on page 2856	0000000000000000h
38h	8	"reg_IPCX_type (IPCX)—Offset 38h" on page 2857	0000000000000000h
40h	8	"reg_IPCD_type (IPCD)—Offset 40h" on page 2858	0000000000000000h
48h	8	"reg_ISRSC_type (ISRSC)—Offset 48h" on page 2858	0000000000000000h
50h	8	"reg_ISRLPESC_type (ISRLPESC)—Offset 50h" on page 2859	0000000000000000h
58h	8	"reg_IMRSC_type (IMRSC)—Offset 58h" on page 2860	0000000000000000h
60h	8	"reg_IMRLPESC_type (IMRLPESC)—Offset 60h" on page 2861	0000000000000000h
68h	8	"reg_IPCSC_type (IPCSC)—Offset 68h" on page 2861	0000000000000000h
70h	8	"reg_IPCLPESC_type (IPCLPESC)—Offset 70h" on page 2862	0000000000000000h
78h	8	"reg_CLKCTL_type (CLKCTL)—Offset 78h" on page 2863	0000000000070013h
80h	8	"reg_FR_LAT_REQ_type (FR_LAT_REQ)—Offset 80h" on page 2863	0000000000000000h
88h	8	"reg_CHICKEN_BITS_type (CHICKEN_BITS)—Offset 88h" on page 2864	0000000000000000h
90h	8	"reg_ISRPSH_type (ISRPSH)—Offset 90h" on page 2865	0000000000000000h
98h	8	"reg_ISRLPEPSH_type (ISRLPEPSH)—Offset 98h" on page 2866	0000000000000000h
A0h	8	"reg_IMRPSH_type (IMRPSH)—Offset A0h" on page 2866	0000000000000000h
A8h	8	"reg_IMRLPEPSH_type (IMRLPEPSH)—Offset A8h" on page 2867	0000000000000000h
B0h	8	"reg_IPCPSH_type (IPCPSH)—Offset B0h" on page 2868	0000000000000000h
B8h	8	"reg_IPCLPEPSH_type (IPCLPEPSH)—Offset B8h" on page 2868	0000000000000000h
C0h	8	"reg_EXT_TIMER_CNTL_type (EXT_TIMER_CNTL)—Offset C0h" on page 2869	0000000000000000h
C8h	8	"reg_EXT_TIMER_STAT_type (EXT_TIMER_STAT)—Offset C8h" on page 2870	0000000000000000h
D0h	8	"reg_S0ix_TIMER_CNTL_type (S0ix_TIMER_CNTL)—Offset D0h" on page 2870	0000000000000000h
D8h	8	"reg_S0ix_TIMER_STAT_type (S0ix_TIMER_STAT)—Offset D8h" on page 2871	0000000000000000h
E0h	8	"reg_RAW_PISR_type (XT_RAW_PISR)—Offset E0h" on page 2872	0000000000000000h
E8h	8	"reg_SSP0_DIV_CTRL_type (SSP0_DIV_CTRL)—Offset E8h" on page 2873	8000000100000001h
F0h	8	"reg_SSP1_DIV_CTRL_type (SSP1_DIV_CTRL)—Offset F0h" on page 2873	8000000100000001h
F8h	8	"reg_SSP2_DIV_CTRL_type (SSP2_DIV_CTRL)—Offset F8h" on page 2874	8000000100000001h



21.11.1 reg_CSR_type (CSR)—Offset 0h

This register controls clock and reset of the block, various configurations of the block and reflects general status of the block.

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

CSR: [BAR + 140000h] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000001E40001h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0	
3	0	6	2	8	4	0	6	2	8	4	0	6	2				
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
RSVD0								rsvd_0	RSVD1		rsvd_5	rsvd_6	rsvd_7	SSP2IOCLKSEL	SSP1IOCLKSEL	SSP0IOCLKSEL	



Bit Range	Default & Access	Description
8	0b RW	Rsvd_3: Reserved
7	0b RO	RSVD3: Reserved
6	0b RW	SSP2baseclkssel: 1 =) Select 25 Mhz clock for the SSP2 base clock; 0 =) Select 19.2 Mhz clock for the SSP base clock
5	0b RW	SSP1baseclkssel: 1 =) Select 25 Mhz clock for the SSP1 base clock; 0 =) Select 19.2 Mhz clock for the SSP base clock
4	0b RW	SSP0baseclkssel: 1 =) Select 25 Mhz clock for the SSP0 base clock; 0 =) Select 19.2 Mhz clock for the SSP base clock
3	0b RO	PWaitMode: Satus bit when set to '1 indicates that LPE core is stalled.
2	0b RW	RunStall: When set to '1, LPE core is stalled.
1	0b RW	StatVectorSel: When set to '1, LPE core boots from the Alternate reset vector. This is set to ff2c_0000 - first address of Audio IRAM. Default reset vector is set to 0x100000. This needs to be set to 1'b1 for TNG.
0	1b RW	LPE_RST: LPE Reset. LPE held in reset state until this bit is set to 1. Minimum number of cycles is defined LPE manual. The bit should be cleared to bring the LPE out of reset.

21.11.2 reg_XT_PISR_type (PISR)—Offset 8h

PISR

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

PISR: [BAR + 140000h] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000
RSVD0								PIS_DMA1	PIS_DMA0	RSVD	RSVD1	RSVD	RSVD	RSVD	RSVD	RSVD2

Bit Range	Default & Access	Description
63:32	0b RO	RSVD0: Reserved
31:24	00000000b RW/1C	PIS_DMA1: DMA 1 interrupts
23:16	00000000b RW/1C	PIS_DMA0: DMA 0 interrupts
15	0b RO	Reserved (RSVD): Reserved.



PIMR

Access Method

PIMR: [BAR + 140000h] + 10h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 000000000000000000h

Bit Range	Default & Access	Description
63:32	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Description
31:24	00000000b RW	DMA1_Interrupts_XT_Mask: DMA 1 interrupts
23:16	00000000b RW	DMA0_Interrupts_XT_Mask: DMA 0 interrupts
15	0b RO	Reserved (RSVD): Reserved.
14:11	0b RO	RSVD1: Reserved
10	0b RO	Reserved (RSVD): Reserved.
9	0b RO	Reserved (RSVD): Reserved.
8	0b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.
6	0b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	0b RO	RSVD2: Reserved

21.11.4 reg_IA_PISR_type (ISR_X)—Offset 18h

PISR

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

ISR_X: [BAR + 140000h] + 18h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h



Bit Range	Default & Access	Description
63:32	0b RO	RSVD0: Reserved
31:24	00000000b RW/1C	IAPIS_DMA1: DMA 1 interrupts
23:16	00000000b RW/1C	IAPIS_DMA0: DMA 0 interrupts
15:10	0b RO	RSVD1: Reserved
9	0b RO	Reserved (RSVD): Reserved.
8	0b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.
6	0b RO	Reserved (RSVD): Reserved.
5	0b RW/1C	IAPIS_SSP0: SSP0 Interrupt Request for SC 1: interrupt when SSP0 interrupt is asserted. 0: Deasserted
4	0b RW/1C	IAPIS_SSP1: SSP1 Interrupt Request for SC 1: interrupt when SSP1 interrupt is asserted. 0: Deasserted
3	0b RW/1C	IAPIS_SSP2: SSP2 Interrupt Request for SC 1: interrupt when SSP2 interrupt is asserted. 0: Deasserted
2	0b RO	RSVD2: Reserved
1	0b RO	LPE_IA_IPC_Request_Status: IPCD Interrupt Request 1: interrupt when LPE writes a message into IPCD register with bit 63 set 0: Deasserted
0	0b RO	LPE_IA_IPC_Done_Status: IPCX Interrupt Request 1: interrupt when LPE writes a message into IPCX register with bit 62 set is asserted 0: Deasserted.

21.11.5 reg_ISRD_type (ISRD)—Offset 20h

ISRD

Access Method

Intel Atom® Processor E3800 Product Family
Datasheet
2855



Bit Range	Default & Access	Description
63:32	0b RO	RSVD0: Reserved
31:24	0b RW	DMA1_Interrupts_IA_Mask: DMA 1 interrupts mask
23:16	0b RW	DMA0_Interrupts_IA_Mask: DMA 0 interrupts mask
15:10	0b RO	RSVD1: Reserved
9	0b RO	Reserved (RSVD): Reserved.
8	0b RO	Reserved (RSVD): Reserved.
7	0b RO	Reserved (RSVD): Reserved.
6	0b RO	Reserved (RSVD): Reserved.
5	0b RW	IAPIS_SSP2: SSP2 Interrupt Mask for IA 1: Interrupt is masked 0: Interrupt is unmasked
4	0b RW	IAPIS_SSP1: SSP1 Interrupt Mask for IA 1: Interrupt is masked 0: Interrupt is unmasked
3	0b RW	IAPIS_SSP0: SSP0 Interrupt Mask for IA 1: Interrupt is masked 0: Interrupt is unmasked
2	0b RO	RSVD2: Reserved
1	0b RW	LPE_IA_IPC_Request_Mask: LPE to IA IPC Request Mask 1: Interrupt is masked 0: Interrupt is unmasked
0	0b RW	LPE_IA_IPC_Done_Mask: LPE to IA IPC Done Mask 1: Interrupt is masked 0: Interrupt is unmasked

21.11.7 reg_IMRD_type (IMRD)—Offset 30h

IMRD

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

IMRD: [BAR + 140000h] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h



21.11.8 reg_IPCX_type (IPCX)—Offset 38h

Access Method

IPCX: [BAR + 140000h] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

The timing diagram shows three signals over a period of 100 ns. The signals are:

- IA_LPE_BUSY**: A pulse that starts at 0 ns, goes high at 10 ns, and returns low at 30 ns.
- IA_LPE_DONE**: A pulse that starts at 0 ns, goes high at 10 ns, and returns low at 30 ns.
- IA_LPE_MSG**: A pulse that starts at 0 ns, goes high at 10 ns, and returns low at 30 ns.

The diagram also includes a numerical scale at the top, ranging from 0 to 100 in increments of 10, with corresponding vertical grid lines.

Intel Atom® Processor E3800 Product Family
Datasheet
2857



Bit Range	Default & Access	Description
62	0b RW	LPE_IA_DONE: Done. When the bit is set, the LPE completed the operation and requests attention
61:0	000000000 00000000h RW	IA_LPE_MSG: IA-32 to LPE Message

21.11.9 reg_IPCD_type (IPCD)—Offset 40h

Inter-process Status and Message register for LPE contains a message sent from LPE to IA-32 CPU. The format of the CPU message bits 29:0 is defined in the LPE Firmware specifications. The message may contain optional data fields stored in the shared memory region (mailbox). When software writes the message is in this register, it should set bit 63 to indicate that the new data is written. When IA-32 CPU reads the message code from the register, and writes back with the bit 63 cleared. When the IA-32 CPU processes the message sent by LPE, it may set bit 63 in IPCD to assert interrupt request to LPE. The LPE must not attempt to write into IPCLPEIA if bit 63 is set.

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

IPCD: [BAR + 140000h] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h



Bit Range	Default & Access	Description
63	0b RW	LPE_IA_BUSY: Busy. When this bit is cleared, the IA CPU is Ready to accept a new message
62	0b RW	IA_LPE_DONE: Done. When the bit is set, the IA CPU completed operation and requests attention from LPE
61:0	000000000 00000000h RW	LPE_IA_MSG: LPE to IA CPU Message

21.11.10 reg_ISRSC_type (ISRSC)—Offset 48h

ISRSC

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)


ISRSC: [BAR + 140000h] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h



Default: 0000000000000000h



Bit Range	Default & Access	Description
63:34	0b RO	RSVD0: Reserved
33	0b RW/1C	Wake_SCU_Status: This bit is set by hardware when a blocked transaction is detected. It generates a wake to the SCU
32	0b RW/1C	GoS0ixInt_SCU_Status: This bit is set by expiry of the Re-entry timer. The bit gets set only if GoS0ixInt_En bit is set and this interrupt is unmasked.
31:2	0b RO	RSVD1: Reserved
1	0b RO	LPE_SC_IPC_Request_Status: IPCLPESC Interrupt Request 1: interrupt when LPE writes a message into IPCLPESC register with bit 63 set 0: Deasserted
0	0b RW/1C	LPE_SC_IPC_Done_Status: IPCSC Interrupt Request 1: interrupt when LPE writes a message into IPCSC register with bit 62 set is asserted 0: Deasserted.

21.11.11 reg_ISRLPESC_type (ISRLPESC)—Offset 50h

ISRLPESC

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

ISRLPESC: [BAR + 140000h] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h



21.11.12 reg_IMRSC_type (IMRSC)—Offset 58h

IMRSC

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

IMRSC: [BAR + 140000h] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h

[illegible]

Bit Range	Default & Access	Description
63:35	0b RO	RSVD0: Reserved
34	0b RW/1C	GoS0ix_IntEn: This bit indicates that Reentry to S0iX interrupts to SCU are enabled. The bit is set by hardware when a transaction is blocked at the Audio to Secondary interface due to the secondary fabric being gated and the fabdisable bit being set. Software is expected to clear this bit along with the Secondary Fabric Reject bit. This disables the interrupts.
33	0b RW	FabDisable: This bit is used to generate the wake interrupt to SCU. When set the interrupt generation is enabled. When cleared the interrupt generation is disabled
32	0b RW	GoS0ixInt_SCU_Mask: Mask bit for S0ix Reentry interrupt to SCU
31:2	0b RO	RSVD1: Reserved
1	0b RW	LPE_SC_IPC_Request_Mask: IPCLPESC Interrupt Enable to SC CPU
0	0b RW	LPE_SC_IPC_Done_Mask: IPCSC Interrupt Enable to SC CPU

21.11.13 reg_IMRLPESC type (IMRLPESC)—Offset 60h

IMRLPRES

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

IMRLPESC: [BAR + 140000h] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 000000000000000000h



Bit Range	Default & Access	Description
63:2	0b RO	RSVD0: Reserved
1	0b RW	SC_LPE_IPC_Request_Mask: IPCSC interrupt Enable to LPE
0	0b RW	SC_LPE_IPC_Done_Mask: IPCLPESC interrupt Enable to LPE

21.11.14 reg_IPCSC_type (IPCSC)—Offset 68h

The Inter-process Status and Message register for SC contains a message sent from the SC CPU to LPE. The format of the CPU message bits (29:0) is not defined in the HW specs. It is defined in the LPE Firmware specifications. The message may contain optional data fields stored in the shared memory region (mailbox). When the message is written in this register, the software must set bit 63 to indicate that the IPCSC is not empty. Setting Busy also asserts interrupt request to LPE if the interrupt is enabled in the IMRLPESC. After LPE reads the message code from the register, it must perform a write with bit 63 cleared. The SC CPU must not attempt to write into IPCIA if bit 63 is set.

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

IPCSC: [BAR + 140000h] + 68h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h



Bit Range	Default & Access	Description
63	0b RW	SC_LPE_BUSY: Busy. When this bit is cleared, the LPE Ready to accept a message
62	0b RW	LPE_SC_DONE: Done. When the bit is set, the LPE completed the operation and requests attention
61:0	00000000 0000000h RW	SC_LPE_MSG: SC to LPE Message

21.11.15 reg_IPCLPESC_type (IPCLPESC)—Offset 70h

Inter-process Status and Message register for LPE contains a message sent from LPE to SC. The format of the CPU message bits 29:0 is defined in the LPE Firmware specifications. The message may contain optional data fields stored in the shared memory region (mailbox). When software writes the message is in this register, it should set bit 63 to indicate that the new data is written. When SC reads the message code from the register, and writes back with the bit 63 cleared. When the SC CPU processes the message sent by LPE, it may set bit 62 in IPCLPESC to assert interrupt request to LPE. The LPE must not attempt to write into IPCD if bit 63 is set.

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

IPCLPESC: [BAR + 140000h] + 70h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h



Bit Range	Default & Access	Description
63	0b RW	LPE_SC_BUSY: Busy. When this bit is cleared, the SC CPU is Ready to accept a new message
62	0b RW	SC_LPE_DONE: Done. When the bit is set, the SC CPU completed operation and requests attention from LPE
61:0	0h RW	LPE_SC_MSG: LPE to SC CPU Message



21.11.16 reg_CLKCTL_type (CLKCTL)—Offset 78h

LPE Clock Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

CLKCTL: [BAR + 140000h] + 78h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000070013h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2	0	0	1
0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	0
RSVD0									RSVD	RSVD1	EN_SSP2_CLK	EN_SSP1_CLK	EN_SSP0_CLK	RSVD2	OSC_MODE	FRCHNGGO
															FRCHNGACK	RSVD3
																CLK_DIV

Bit Range	Default & Access	Description
63:32	0b RO	RSVD0: Reserved
31:25	0000000b RO	RSVD: Reserved
24:19	0b RO	RSVD1: Reserved
18	1b RW	EN_SSP2_CLK: clock output enable
17	1b RW	EN_SSP1_CLK: clock output enable
16	1b RW	EN_SSP0_CLK: clock output enable
15:7	0b RO	RSVD2: Reserved
6	0b RO	OSC_MODE: 1 indicates that PLL is turned off
5	0b RW/1S	FRCHNGGO: Go bit indicating that the value in 2:0 can be applied to core. This bit will get cleared on the rising edge of the ack from Clock Control Unit.
4	1b RO	FRCHNGACK: Sets on the falling edge of ack. A 1'b1 indicates that the frequency change is done. The bit auto clears on the rising edge of frequency change request.
3	0b RO	RSVD3: Reserved
2:0	011b RW	CLK_DIV: 000: 25 MHz(XTAL) 001: 25 Mhz(XTAL) 010: 50 Mhz(2xXTAL) 011: 50 Mhz(default) 100: 100 Mhz 101: 200 Mhz 110: 267 Mhz 111: 343 Mhz

21.11.17 reg_FR_LAT_REQ_type (FR_LAT_REQ)—Offset 80h

LPE

Access Method



Type: Memory Mapped I/O Register
(Size: 64 bits)

FR_LAT_REQ: [BAR + 140000h] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
RSVD0														Latency_tol	RSVD1	Required_freq

Bit Range	Default & Access	Description
63:7	0b RO	RSVD0: Reserved
6:4	0b RW	Latency_tol: Latency tolerance for Cache Misses is listed here. SCU firmware is required to read this register and make a decision on whether it can enter a lower power state and still meet the latency tolerance.
3	0b RO	RSVD1: Reserved
2:0	0b RW	Required_freq: The following encoding specifies the frequency that the Audio Cluster requires for current operations. 000: 25 MHz(XTAL) 001: 25 Mhz(XTAL) 010: 50 Mhz(2xXTAL) 011: 50 Mhz(default) 100: 100 Mhz 101: 200 Mhz 110: 267 Mhz 111: 343 Mhz Please note, that this does not guarantee that this frequency will be generated from the CCU. The SCU firmware is required to read this register before making a decision on entering lower power states.

21.11.18 reg_CHICKEN_BITS_type (CHICKEN_BITS)—Offset 88h

LPE

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

CHICKEN_BITS: [BAR + 140000h] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
RSVD0														DMA_Debug_Select	XT_Posted_only_traffic	bug_2431329_fix_disable
														disable_ssp2_dma_finish	disable_ssp1_dma_finish	disable_ssp0_dma_finish
														wait_fix_enable		



Bit Range	Default & Access	Description
63:8	0b RO	RSVD0: Reserved
7	0b RW	DMA_Debug_Select: Setting this bit will select DMA 1 debug signals to be routed to the VISA Mux.
6	0b RW	XT_posted_only_traffic: Setting this bit will select make all the traffic from Tensilica to be posted.
5	0b RW	IPC_wakes_SCU: Setting this to 1 will cause the IPC to be fed into the wake cone for SCU.
4	0b RW	bug_2431329_fix_disable: Setting this to 1 will disable the synopsys compatible hardware handshake mechanism. Keep this set to 0 for regular hardware handshake operation.
3	0b RW	disable_ssp2_dma_finish: Setting this to 1 will cause the SSP Unit to ignore the dma_finish signal. Set this to 1 for MultiBlock transfers.
2	0b RW	disable_ssp1_dma_finish: Setting this to 1 will cause the SSP Unit to ignore the dma_finish signal. Set this to 1 for MultiBlock transfers.
1	0b RW	disable_ssp0_dma_finish: Setting this to 1 will cause the SSP Unit to ignore the dma_finish signal. Set this to 1 for MultiBlock transfers.
0	0b RW	waiti_fix_enable: Setting this bit to 1 makes the frequency change request to be valid only if the core is in WAITI.

21.11.19 reg_ISRPSH_type (ISRPSH)—Offset 90h

ISRPSH

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

ISRPSH: [BAR + 140000h] + 90h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h

6 3	6 0	5 6	5 2	4 8	4 4	4 0	3 6	3 2	2 8	2 4	2 0	1 6	1 2	8	4	
0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000
RSVD0																
LPE_PSH_IPC_Request_Status																

Bit Range	Default & Access	Description
63:2	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Description
1	0b RO	LPE_PSH_IPC_Request_Status: IPCLPEPSH Interrupt Request 1: interrupt when LPE writes a message into IPCLPEPSH register with bit 63 set 0: Deasserted
0	0b RW/1C	LPE_PSH_IPC_Done_Status: IPCPSH Interrupt Request 1: interrupt when LPE writes a message into IPCPSH register with bit 62 set is asserted 0: Deasserted.

21.11.20 reg_ISRLPEPSH_type (ISRLPEPSH)—Offset 98h

ISRLPEPSH

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

ISRLPEPSH: [BAR + 140000h] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
																PSH_LPE_IPC_Request_Status
																PSH_LPE_IPC_Done_Status

Bit Range	Default & Access	Description
63:2	0b RO	RSVD0: Reserved
1	0b RO	PSH_LPE_IPC_Request_Status: IPCPSH Interrupt Request to LPE 1: interrupt when PSH writes a message into IPCPSH register with bit 63 set. 0: Deasserted
0	0b RO	PSH_LPE_IPC_Done_Status: IPCLPEPSH Interrupt Request to LPE 1: interrupt when PSH CPU writes a message into IPCLPEIA register with bit 62 set is asserted 0: Deasserted.

21.11.21 reg_IMRPSH_type (IMRPSH)—Offset A0h

IMRPSH

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

IMRPSH: [BAR + 140000h] + A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h




Diagram illustrating the structure of a 64-bit IPv6 address, showing the distribution of bits across 16 groups (0 to 15). The address is divided into 16 groups of 4 bits each, with the total address length being 64 bits.

Group	Bits	Value
63	4	0000
60	4	0000
56	4	0000
52	4	0000
48	4	0000
44	4	0000
40	4	0000
36	4	0000
32	4	0000
28	4	0000
24	4	0000
20	4	0000
16	4	0000
12	4	0000
8	4	0000
4	4	0000
0	4	0000

The entire 64-bit address is labeled **RSVD0**.

Intel Atom® Processor E3800 Product Family
Datasheet
2867



Bit Range	Default & Access	Description
0	0b RW	PSH_LPE_IPC_Done_Mask: IPCLPEPSH interrupt Enable to LPE

21.11.23 reg_IPCPSH_type (IPCPSH)—Offset B0h

The Inter-process Status and Message register for PSH contains a message sent from the PSH CPU to LPE. The format of the CPU message bits (29:0) is not defined in the HW specs. It is defined in the LPE Firmware specifications. The message may contain optional data fields stored in the shared memory region (mailbox). When the message is written in this register, the software must set bit 63 to indicate that the IPCPSH is not empty. Setting Busy also asserts interrupt request to LPE if the interrupt is enabled in the IMRLPEPSH. After LPE reads the message code from the register, it must perform a write with bit 63 cleared. The PSH CPU must not attempt to write into IPCIA if bit 63 is set.

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

IPCPSH: [BAR + 140000h] + B0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h



Bit Range	Default & Access	Description
63	0b RW	PSH_LPE_BUSY: Busy. When this bit is cleared, the LPE Ready to accept a message
62	0b RW	LPE_PSH_DONE: Done. When the bit is set, the LPE completed the operation and requests attention
61:0	00000000 0000000h RW	PSH_LPE_MSG: PSH to LPE Message

21.11.24 reg_IPCLPEPSH_type (IPCLPEPSH)—Offset B8h

Inter-process Status and Message register for LPE contains a message sent from LPE to PSH. The format of the CPU message bits 29:0 is defined in the LPE Firmware specifications. The message may contain optional data fields stored in the shared memory region (mailbox). When software writes the message is in this register, it should set bit 63 to indicate that the new data is written. When PSH reads the message code from the register, and writes back with the bit 63 cleared. When the PSH CPU processes the message sent by LPE, it may set bit 62 in IPCLPEPSH to assert interrupt request to LPE. The LPE must not attempt to write into IPCD if bit 63 is set.



Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

IPCLPEPSH: [BAR + 140000h] + B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h

63	60	56	52	48	44	40	36	32	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
LPE_PSH_BUSY PSH_LPE_DONE																
LPE_PSH_MSG																

Bit Range	Default & Access	Description
63	0b RW	LPE_PSH_BUSY: Busy. When this bit is cleared, the PSH CPU is Ready to accept a new message
62	0b RW	PSH_LPE_DONE: Done. When the bit is set, the PSH CPU completed operation and requests attention from LPE
61:0	0h RW	LPE_PSH_MSG: LPE to PSH CPU Message

21.11.25 reg_EXT_TIMER_CNTL_type (EXT_TIMER_CNTL)—Offset C0h

External Timer Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

EXT_TIMER_CNTL: [BAR + 140000h] + C0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h

636056524844403632282420161284															
00															

Bit Range	Default & Access	Description
63	0b RW	Ext_Timer_Run: Timer Run bit. The timer runs only when this bit is set. It resumes running from the current value in the readvalue bits. Clearing the bit pauses the timer.
62	0b RW/S	Ext_Timer_Clear: Timer Clear bit. Clears the timer and sets the value back to zero. This should also be reflected in the readvalue bits



Bit Range	Default & Access	Description
61:32	0b RO	RSVD0: Reserved
31:0	0b RW	Ext_Timer_Matchvalue: The timer will generate a pulse when the Readvalue reaches Matchvalue. The pulse causes a level interrupt to get set in the PISR register. The PISR interrupt needs to be cleared before the next pulse is generated. The timer keeps counting beyond the Readvalue. Setting the Matchvalue to zero makes this a free running timer and no interrupt will be generated in this case. For correct operation, the ISR should either set a new Matchvalue or set it to zero. If nothing is done, the timer will roll over and trigger an interrupt again when it reaches the Matchvalue.

21.11.26 reg_EXT_TIMER_STAT_type (EXT_TIMER_STAT)—Offset C8h

External Timer Control Register

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

EXT_TIMER_STAT: [BAR + 140000h] + C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000	0000
RSVD0								Ext_Timer_Readvalue								

Bit Range	Default & Access	Description
63:32	0b RO	RSVD0: Reserved
31:0	0b RO	Ext_Timer_Readvalue: Shows the current count value of the timer

21.11.27 reg_S0ix_TIMER_CNTL_type (S0ix_TIMER_CNTL)—Offset D0h

External Timer Control Register

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

S0ix_TIMER_CNTL: [BAR + 140000h] + D0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h



Bit Range	Default & Access	Description
63	0b RW	S0ix_Timer_Run: Timer Run bit. The timer runs only when this bit is set. It resumes running from the current value in the readvalue bits. Clearing the bit pauses the timer.
62	0b RW/S	S0ix_Timer_Clear: Timer Clear bit. Clears the timer and sets the value back to zero. This should also be reflected in the readvalue bits
61:32	0b RO	RSVD0: Reserved
31:0	0b RW	S0ix_Timer_Matchvalue: The timer will generate a pulse when the Readvalue reaches Matchvalue. The pulse causes a level interrupt to get set in the PISR register. The PISR interrupt needs to be cleared before the next pulse is generated. The timer keeps counting beyond the Readvalue. Setting the Matchvalue to zero makes this a free running timer and no interrupt will be generated in this case. For correct operation, the ISR should either set a new Matchvalue or set it to zero. If nothing is done, the timer will roll over and trigger an interrupt again when it reaches the Matchvalue.

21.11.28 reg_S0ix_TIMER_STAT_type (S0ix_TIMER_STAT)—Offset D8h

External Timer Control Register

Access Method


Type: Memory Mapped I/O Register
(Size: 64 bits)

S0ix_TIMER_STAT: [BAR + 140000h] + D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000000000000000h



Bit Range	Default & Access	Description
63:32	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Description
2:0	0b RO	RSVD2: Reserved

21.11.30 reg_SSP0_DIV_CTRL_type (SSP0_DIV_CTRL)—Offset E8h

SSP0 M/N Clock Divider control - Add for VLV

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

SSP0_DIV_CTRL: [BAR + 140000h] + E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 8000000100000001h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2	8	4	0
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Divider_Bypass	Divider_En	Divider_Update	RSVD0	Divider_M	RSVD1	Divider_N										

Bit Range	Default & Access	Description
63	1b RW	Divider_Bypass: SSP0 Bypass divider
62	0b RW	Divider_En: SSP0 Enable divider
61	0b RW	Divider_Update: SSP0 Update divider
60:52	0b RO	RSVD0: Reserved
51:32	1b RW	Divider_M: SSP0 Nominator value
31:20	0b RO	RSVD1: Reserved
19:0	1b RW	Divider_N: SSP0 Denominator value

21.11.31 reg_SSP1_DIV_CTRL_type (SSP1_DIV_CTRL)—Offset F0h

SSP1 M/N Clock Divider control - Add for VLV

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

SSP1_DIV_CTRL: [BAR + 140000h] + F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h



Default: 8000000100000001h

63	60	56	52	48	44	40	36	32	28	24	20	16	12	8	4	0
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Divider_Bypass	Divider_En	Divider_Update	RSVD0				Divider_M				RSVD1	Divider_N				

Bit Range	Default & Access	Description
63	1b RW	Divider_Bypass: SSP1 Bypass divider
62	0b RW	Divider_En: SSP1 Enable divider
61	0b RW	Divider_Update: SSP1 Update divider
60:52	0b RO	RSVD0: Reserved
51:32	1b RW	Divider_M: SSP1 Nominator value
31:20	0b RO	RSVD1: Reserved
19:0	1b RW	Divider_N: SSP1 Denominator value

21.11.32 reg_SSP2_DIV_CTRL_type (SSP2_DIV_CTRL)—Offset F8h

SSP2 M/N Clock Divider control - Add for VLV

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

SSP2_DIV_CTRL: [BAR + 140000h] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 8000000100000001h

63	60	56	52	48	44	40	36	32	28	24	20	16	12	8	4	0
1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
Divider_Bypass	Divider_En	Divider_Update	RSVD0				Divider_M				RSVD1	Divider_N				

Bit Range	Default & Access	Description
63	1b RW	Divider_Bypass: SSP2 Bypass divider



Bit Range	Default & Access	Description
62	0b RW	Divider_En: SSP2 Enable divider
61	0b RW	Divider_Update: SSP2 Update divider
60:52	0b RO	RSVD0: Reserved
51:32	1b RW	Divider_M: SSP2 Nominator value
31:20	0b RO	RSVD1: Reserved
19:0	1b RW	Divider_N: SSP2 Denominator value



21.12 Low Power Audio I²S0 Address Map

Table 234. Summary of Low Power Audio I²S0 Memory Mapped I/O Registers—BAR

Offset	Size	Register ID—Description	Default Value
0h	4	"SSP Control 0 Register (SSCR0)—Offset 0h" on page 2876	00000000h
4h	4	"SSP Control 1 Register (SSCR1)—Offset 4h" on page 2877	43000000h
8h	4	"SSP Status Register (SSSR)—Offset 8h" on page 2879	0000F004h
Ch	4	"SSP Interrupt Test Register (SSITR)—Offset Ch" on page 2881	00000000h
10h	4	"SSP Data Register (SSDR)—Offset 10h" on page 2881	00000000h
28h	4	"SSP Time-Out Register (SSTO)—Offset 28h" on page 2882	00000000h
2Ch	4	"SSP Programmable Protocol Register (SSPSP)—Offset 2Ch" on page 2883	00000000h
30h	4	"SSM TX Time Slot Active Register (SSTSA)—Offset 30h" on page 2884	00000000h
34h	4	"SSP RX Time Slot Active Register (SSRSA)—Offset 34h" on page 2884	00000000h
38h	4	"SSP Time Slot Status Register (SSTSS)—Offset 38h" on page 2885	00000000h
3Ch	4	"SSP Audio Clock Divider (SSACD)—Offset 3Ch" on page 2885	00000000h
40h	4	"SSP Control 2 Register (SSCR2)—Offset 40h" on page 2886	000000C0h
44h	4	"SSP Frame Select Register (SSFS)—Offset 44h" on page 2887	00000001h
48h + [0-7]*4h	4	"SSP Slot Frame Counter Register[0-7] (FRAME_CNT[0-7])—Offset 48h, Count 8, Stride 4h" on page 2888	00000000h
68h	4	"SSP FIFO Level Register (SFIFOL)—Offset 68h" on page 2889	FFFF0000h
6Ch	4	"SSP FIFO Trigger Threshold Register (SFIFOTT)—Offset 6Ch" on page 2889	00000000h
70h	4	"SSP Control 3 Register (SSCR3)—Offset 70h" on page 2890	0002C604h
74h	4	"SSP Control 4 Register (SSCR4)—Offset 74h" on page 2891	00000000h
78h	4	"SSP Control 5 Register (SSCR5)—Offset 78h" on page 2892	00000000h
7Ch	4	"ASRC Free Running Timer (ASRC_FRT)—Offset 7Ch" on page 2893	00000000h
80h	4	"Frame Threshold for ASRC Frame Count (ASRC_FTC)—Offset 80h" on page 2893	00000000h
84h	4	"ASRC Timer Snapshot (ASRC_SNPSHT)—Offset 84h" on page 2894	00000000h
88h	4	"ASRC Frame Count (ASRC_FRMCNT)—Offset 88h" on page 2894	00000000h

21.12.1 SSP Control 0 Register (SSCR0)—Offset 0h

The Enhanced SSP Control 0 registers contain twelve different bit fields that control various functions within the Enhanced SSP. All bits must be set to the preferred value before enabling the Enhanced SSP. Note that Writes to reserved bits must be zeroes, and Read values of these bits is undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR0: [BAR + 0A0000h] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h




31					28					24					20					16					12					8					4					0																																							
0					0					0					0					0					0					0					0					0					0																																		
MOD					ACS					RSVD					RSVD					RSVD					FRDC					TIM					RIM					NCS					EDSS					SCR										SSE					ECS					FRF					DSS				

Bit Range	Default & Access	Description
31	0b RW	Mode Select (MOD): 0 = Normal SSP Mode 1 = Network Mode
30	0b RW	Audio Clock Select (ACS): 0 = Clock selection is determined by the NCS and ECS bits 1 = Audio Clock (and Audio Clock Divider) are used to clock the SSP's serial clock (SSPCLK)
29	0b RO	Reserved (RSVD): Reserved.
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26:24	000b RW	Frame Rate Divider Control (FRDC): Value 0-7 indicates the number of time slots per frame when in network mode (the actual number of time slots is FRDC+1, so 1 to 8 time slots).
23	0b RW	Transmit FIFO Under Run Interrupt Mask (TIM): 0 = TUR events will generate an SSP interrupt 1 = TUR events will not generate an SSP interrupt
22	0b RW	Receive FIFO Over Run Interrupt Mask (RIM): 0 = ROR events will generate an SSP interrupt 1 = ROR events will not generate an SSP interrupt
21	0b RW	Network Clock Select (NCS): 0 = Clock selection is determined by ECS bit 1 = Network clock is used to create the SSP's serial clock (SSPCLK)
20	0b RW	Extended Data Size Select (EDSS): 0 = A zero is preappended to the DSS value which sets the DSS range from 4-16 bits 1 = A one is pre-appended to the DSS value which sets the DSS range from 17-32 bits
19:8	000h RW	Serial Clock Rate (SCR): Value (0 to 4095) used to generate transmission rate of SSP. Serial bit rate = SSP clock/(SCR+1), where SCR is decimal integer.
7	0b RW	Synchronous Serial Port Enable (SSE): 0 = SSP operation disabled and FIFOs are cleared 1 = SSP operation enabled
6	0b RW	External Clock Select (ECS): 0 = On-chip clock used to produce the SSP's serial clock (SSPCLK) 1 = SSPEXTCLK/GPIO pin is used to create the SSP's SSPCLK
5:4	00b RW	Frame Format (FRF): 00 = Motorola Serial Peripheral Interface (SPI) 01 = Texas Instruments Synchronous Serial Protocol (SSP) 10 = National Semiconductor Microwire 11 = Programmable Serial Protocol (PSP)
3:0	0000b RW	Data Size Select (DSS): With EDSS as MSB, value+1 gives data size. Values 4 to 32 allowed.

21.12.2 SSP Control 1 Register (SSCR1)—Offset 4h

The Enhanced SSP Control 1 registers contain bit fields that control various SSP functions. Bits must be set to the preferred value before enabling the Enhanced SSP. Note that Writes to reserved bits should be zeroes, and Read value of these bits are undetermined.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR1: [BAR + 0A0000h] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 43000000h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	0	1	1	0
0	0	0	1	1	0	0	0	0
TTELP	TTE	EBCEI	SCFR	ECRA	ECRB	SCLKDIR	SFRMDIR	RWOT
								TRAIL
								TSRE
								RSRE
								TINTE
								PINTE
								RSVD
								IFS
								STRF
								EFWR
								RFT
								TFT
								MWDS
								SPH
								SPO
								LBM
								TIE
								RIE

Bit Range	Default & Access	Description
31	0b RW	TXD Tristate Enable on Last Phase (TTELP): 0 = TXD line will be tristated on same clock edge as TXD is to be flopped 1 = TXD line will be tristated 1/2 clock edge after TXD is to be flopped
30	1b RW	TXD Tristate Enable (TTE): 0 = TXD line will not be tristated 1 = TXD line will be tristated when no transmitting data
29	0b RW	Enable Bit Count Error Interrupt (EBCEI): 0 = Interrupt due to a bit count error is disabled 1 = Interrupt due to a bit count error is enabled
28	0b RW	Slave Clock Free Running (SCFR): 0 = clock input to SSPSCLK is continuously running 1 = clock input to SSPSCLK is only active durring transfers
27	0b RW	Enable Clock Request A (ECRA): 0 = clock request from other SSP is disabled 1 = clock request from other SSP is enabled
26	0b RW	Enable Clock Request B (ECRB): 0 = clock request from other SSP is disabled 1 = clock request from other SSP is enabled
25	1b RW	SSP Serial Bit Rate Clock (SSPSCLK) Direction (SCLKDIR): 0 = Master mode, SSP drives SSPSCLK 1 = Slave mode, SSP recieves SSPSCLK
24	1b RW	SSP Frame (SSPSFRM) Direction (SFRMDIR): 0 = Master mode, SSP drives SSPSFRM 1 = Slave mode, SSP receives SSPSFRM
23	0b RW	Receive With Out Transmit (RWOT): 0 = Transmit/Receive mode 1 = Receive without transmit mode
22	0b RW	Trailing Byte (TRAIL): 0 = Processor based, trailing bytes are handled by processor 1 = DMA based, trailing bytes are handled by DMA
21	0b RW	Transmit Service Request Enable (TSRE): 0 = DMA Service Request is disabled 1 = DMA Service Request is enabled
20	0b RW	Receive Service Request Enable (RSRE): 0 = DMA Service Request is disabled 1 = DMA Service Request is enabled
19	0b RW	Receiver Time-out Interrupt Enable (TINTE): 0 = Receiver Time-out interrupts are disabled 1 = Receiver Time-out interrupts are enabled
18	0b RW	Peripheral Trailing Byte Interrupts Enable (PINTE): 0 = Peripheral Trailing Byte Interrupts are disabled 1 = Peripheral Trailing Byte Interrupts are enabled
17	0b RW	RSVD: Reserved
16	0b RW	Invert Frame Signal (IFS): 0 = Frame polarity is determined by SSP format and PSP polarity bits 1 = Frame signal will be inverted from the normal SSP frame signal (as defined by the SSP format nad PSP polarity bits)



Bit Range	Default & Access	Description
15	0b RW	Select FIFO for EFWR (test mode bit) (when EFWR=1) (STRF): 0 = Transmit FIFO is selected for both writes and reads through the SSP Data Register (SSDR) 1 = Receive FIFO is selected for both writes and reads through the SSP Data Register (SSDR)
14	0b RW	Enable FIFO Write/Read (test mode bit) (EFWR): 0 = FIFO write/read special function is disabled (normal SSP operational mode) 1 = FIFO write/read special function is enabled
13:10	0000b RW	Receive FIFO Trigger Threshold (RFT): Sets threshold level at which receive FIFO asserts interrupt. This level should be set to the desired threshold value minus 1. This is a legacy field and only represents the lower 4b of the FIFO Trigger Threshold. Please see SFIFOTT register for complete threshold setting.
9:6	0000b RW	Transmit FIFO Trigger Threshold (TFT): Sets threshold level at which transmit FIFO asserts interrupt. This level should be set to the desired threshold value minus 1. This is a legacy field and only represents the lower 4b of the FIFO Trigger Threshold. Please see SFIFOTT register for complete threshold setting.
5	0b RW	Microwire Transmit Data Size (MWDS): 0 = 8-bit command words are transmitted 1 = 16-bit command words are transmitted
4	0b RW	Motorola SPI SSPSCLK Phase Setting (SPH): 0 = SSPSCLK is inactive one cycle at the start of a frame and 1/2 cycle at the end of a frame 1 = SSPSCLK is inactive 1/2 cycle at the start of a frame and one cycle at the end of a frame
3	0b RW	Motorola SPI SSPSCLK polarity setting (SPO): 0 = The inactive or idle state of SSPSCLK is low 1 = The inactive or idle state of SSPSCLK is high
2	0b RW	Loop-Back Mode (test mode bit) (LBM): 0 = Normal serial port operation enabled 1 = Output of transmit serial shifter connected to input of receive serial shifter, internally
1	0b RW	Transmit FIFO Interrupt Enable (TIE): 0 = Transmit FIFO level interrupt is disabled 1 = Transmit FIFO level interrupt is enabled
0	0b RW	Receive FIFO Interrupt Enable (RIE): 0 = Receive FIFO level interrupt is disabled 1 = Receive FIFO level interrupt is enabled

21.12.3 SSP Status Register (SSSR)—Offset 8h

The Enhanced SSP Status registers contain bits that signal overrun errors as well as the Transmit and Receive FIFO service requests. Each of these hardware-detected events signals an Interrupt request to the Interrupt controller. The Status register also contains flags that indicate when the Enhanced SSP is actively transmitting data, when the Transmit FIFO is not full, and when the Receive FIFO is not empty. One Interrupt signal is sent to the Interrupt Controller for each SSP. These events can cause an Interrupt: End-of-Chain, Receiver Time-out, Peripheral Trailing Byte, Receive FIFO overrun, Receive FIFO request, and Transmit FIFO request.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSSR: [BAR + 0A0000h] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000F004h



Bit Range	Default & Access	Description
1:0	00b RO	RSVD3: Reserved

21.12.4 SSP Interrupt Test Register (SSITR)—Offset Ch

The read-write SSP Interrupt Test registers should be used only for testing purposes. Writing a 1 to the test transmit FIFO request SSITR.TTFS, bit 5, will generate a non-maskable Interrupt strobe signal to the Interrupt controller, and a DMA request for the Transmit FIFO. Writing a 1 to the test receive FIFO request SSITR.TRFS, bit 6, will generate a non-maskable Interrupt strobe signal to the Interrupt controller, and a DMA request for the Receive FIFO. Writing a 1 to the test receive FIFO overrun bit SSITR.TROR, bit 7, will generate a non-maskable Interrupt strobe signal to the Interrupt controller only, no DMA request will be made. Setting any of these bits will also cause the corresponding status bit(s) to be set in the Enhanced SSP Status register (SSSR). The Interrupt and/or service request, caused by the setting of one of these test bits, will remain active until the test bit is cleared by writing a 0 it. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSITR: [BAR + 0A0000h] + Ch**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD1							TROR	RSVD2
							TRFS	
							TTFS	

Bit Range	Default & Access	Description
31:8	000000h RO	RSVD1: Reserved
7	0b RW	Test Receive FIFO overrun (TROR): 0 = No receive FIFO overrun service request 1 = Generates non-maskable interrupt to CPU. No DMA request is generated
6	0b RW	Test Receive FIFO service request (TRFS): 0 = No receive FIFO service request 1 = Generates non-maskable interrupt to CPU and a DMA request for receive FIFO
5	0b RW	Test Transmit FIFO service request (TTFS): 0 = No transmit FIFO service request pending 1 = Generates non-maskable interrupt to CPU and a DMA request for transmit FIFO
4:0	00000b RO	RSVD2: Reserved

21.12.5 SSP Data Register (SSDR)—Offset 10h

The Enhanced SSP Data registers are single address locations that Read-Write data transfers can access. The SSDR represents two physical registers: the first is temporary storage for data on its way out through the Transmit FIFO, the other is temporary storage for data coming in through the Receive FIFO. As the system accesses the



register, FIFO Control logic transfers data automatically between register and FIFO as fast as the system moves it. Data in the FIFO shifts up or down to accommodate the new word (unless it's an attempted Write to a full Transmit FIFO). Status bits (such as SSSR.TFL, SSSR.RFL, SSSR.RNE, and SSSR.TNF) show users whether the FIFO is full, above/below a programmable FIFO trigger threshold, or empty. For Transmit data transfers (Write from system to SSP peripheral), the register can be loaded (written) by the system processor anytime it falls below its threshold level when using programmed I/O. When a data size of less than 32-bits is selected, users should not left-justify data written to the Transmit FIFO. Transmit logic left-justifies the data and ignores any unused bits. Received data of less than 32-bits is automatically right-justified in the Receive FIFO. When the Enhanced SSP is programmed for National Semiconductor Microwire* frame format and if the size for Transmit data is 8-bits as selected by SSCR1.MWDS=0, then the most significant 24-bits are ignored. Similarly, if the size for the Transmit data is 16-bit as selected by SSCR1.MWDS=1, then most significant 16-bits are ignored. The SSCR0.DSS field controls the Receive data size.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSDR: [BAR + 0A0000h] + 10h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DATA								

Bit Range	Default & Access	Description
31:0	00000000h RO	Data (DATA): Data word to be written to/read from transmit/receive FIFO. When reading from this register when the SSP is disabled (SSE=0) then this will return indeterminate data.

21.12.6 SSP Time-Out Register (SSTO)—Offset 28h

The Enhanced SSP Time-Out registers have single bit fields that specify the time-out value used to signal a period of inactivity within the Receive FIFO. Note that Writes to reserved bits must be zeroes and reads are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTO: [BAR + 0A0000h] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				TIMEOUT				



Bit Range	Default & Access	Description
31:24	00h RO	RSVD: Reserved
23:0	000000h RW	Timeout Value (TIMEOUT): Is the value that defines the timeout interval, given by TIMEOUT/Peripheral Clock Frequency

21.12.7 SSP Programmable Protocol Register (SSPSP)—Offset 2Ch

The Enhanced SSP Programmable Protocol registers are read-write registers that contain eight fields that are used to program the various programmable serial-protocol parameters. When using PSP format in Network mode, the parameters SFRMDLY, STRTDLY, DMYSTP, DMYSTRT must be set to 0. Other parameters (such as FRMPOL, SCMODE, FSRT, SFRMDWDTH) are programmable. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSPSP: [BAR + 0A0000h] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																											
0				0				0				0				0				0				0				0				0				0																							
RSVD1								FSRT				DMYSTOP				RSVD2				SFRMWDTH								SFRMDLY								DMYSTRT				STRTDLY								ETDS				SFRMP				SCMODE			

Bit Range	Default & Access	Description
31:26	000000b RO	RSVD1: Reserved
25	0b RW	Frame Sync Relative Timing Bit (FSRT): 0 = Next frame is asserted after the end of the T4 timing 1 = Next frame is asserted with the LSB of the previous frame
24:23	00b RW	Dummy Stop (DMYSTP): Programmed value sets the number of SSPCLK cycles that follow the transmitted data
22	0b RW	RSVD2: Reserved
21:16	000000b RW	Serial Frame Width (SFRMDWDTH): Programmed value sets frame width (1-38)
15:9	000000b RW	Serial Frame Delay (SFRMDLY): Programmed value sets the number of half SSPCLK cycles from TXD/RXD being driven to SSPSPFRM being asserted (0-74)
8:7	00b RW	Dummy Start (DMYSTRT): Programmed value sets the number of SSPCLKs after STRTDLY is complete that precede the transmit/receive data
6:4	000b RW	Start Delay (STRTDLY): Programmed value sets start delay that is used to set the idle time of SSPCLK between transfers (0-7 SSPCLK periods)
3	0b RW	End of Transfer Data State (ETDS): 0 = Low 1 = Last value (bit 0)

31										28										24										20										16										12										8										4										0																													
0										0										0										0										0										0										0										0										0										0										0									
RSVD																				RTSA																																																																																									

Bit Range	Default & Access	Description
31:8	000000h RO	RSVD: Reserved
7:0	00h RW	RX Time Slot Active (RTSA): 0 = SSP will not receive data in this time slot 1 = SSP will receive data in this time slot

21.12.10 SSP Time Slot Status Register (SSTSS)—Offset 38h

The Enhanced SSP Time Slot Status registers are read only registers that indicate which Time Slot the Enhanced SSP is currently in when the Enhanced SSP is in Network Mode (SSCR0.MOD = 1). This register is not valid when the Enhanced SSP is not in Network Mode. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTSS: [BAR + 0A0000h] + 38h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

	31	28	24	20	16	12	8	4	0	
	0	0	0	0	0	0	0	0	0	0
NBSY	RSVD									TSS

Bit Range	Default & Access	Description
31	0b RO	Network Mode Busy (NBSY): 0 = No frame is currently active (in network mode only) 1 = SSP is in network mode and a frame is currently active
30:3	0000000h RO	RSVD: Reserved
2:0	000b RO	Time Slot Status (TSS): Value indicates which time slot is currently active

21.12.11 SSP Audio Clock Divider (SSACD)—Offset 3Ch

The Enhanced SSP Audio Clock Divider registers are read-write registers that indicate which clock frequency is sent to the Enhanced SSP and to the SYSCLK pin. If SSCR0.SCR is not 0, then there is no guaranteed phase relationship between SYSCLK and SSPSCLK. The SSPSFRM Frame Synch Sampling Frequency is calculated by dividing the chosen PLL output clock frequency (SSACD.ACPS) by the chosen divider (SSACD.ACDS) which gives the SYSCLK frequency. The SYSCLK is then divided by 4 (or by 1) to get the SSPSCLK. The SSPSCLK is divided by the data size (EDSS, DSS values) and by the number of time slots being used (SSCR0.FRDC value), if any, to give the

SSPSFRM frequency. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined. It's important to note that this feature is only available if implemented by the project instantiation. A clock source and mux must be instantiated outside of the SSP controller for this feature to work. Only this register is designed into the SSP Controller.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSACD: [BAR + 0A0000h] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:7	0000000h RO	RSVD: Reserved
6:4	000b RW	Audio Clock PLL Select (ACPS): Value indicates which PLL output clock is sent to the clock divider in the clock unit 000: 5.622MHz, 001: 11.345MHz, 010: 12.235MHz, 011: 14.857MHz, 100: 32.842MHz, 101: 48.000MHz, 110, 111: Reserved
3	0b RW	SYSCLK Divider Bypass (SCDB): 0 = SYSCLK is divided by 4 before being sent to SSP 1 = SYSCLK is not divided before being sent to SSP
2:0	000b RW	Audio Clock Divider Select (ACDS): Value indicates which divider will be used by the clock unit to create the SYSCLK output pin. Clock divider value will be 2^{ACDS} , max ACDS = 5.

21.12.12 SSP Control 2 Register (SSCR2)—Offset 40h

The command status register 2 is extension of command status register and contains various feature enable and disables.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR2: [BAR + 0A0000h] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 000000C0h

31	28	24	20	16	12	8	4	0									
0	0	0	0	0	0	0	0	0									
RSVD0																	
									ASRC_INTR_MASK	0	0	0	0	1	1	0	0
									ASRC_FRM_CNTR_EN	0	0	0	0	0	0	0	0
									ASRC_CNTR_CLR	0	0	0	0	0	0	0	0
									ASRC_CNTR_EN	0	0	0	0	0	0	0	0
FIFO_EMPTY_FIX_EN	0	0	0	0	0	0	0	0									
UNDRN_FIX_EN	0	0	0	0	0	0	0	0									
Reserved																	
CLK_DEL_EN	0	0	0	0	0	0	0	0									
SLV_EXT_CLK_RUN_EN	0	0	0	0	0	0	0	0									
Underrun_fix_1	0	0	0	0	0	0	0	0									
Underrun_fix_0	0	0	0	0	0	0	0	0									



Bit Range	Default & Access	Description
31:12	0b RO	RSVD0: Reserved
11	0b RW	ASRC Interrupt Mask (ASRC_INTR_MASK): Setting this bit to 1 masks the ASRC interrupt that is generated every time the frame count matches the frame threshold. Software should override this bit, since it have no reset value
10	0b RW	ASRC frame count enable (ASRC_FRM_CNTR_EN): Setting this bit enables the frame counter to start running. Clearing this bit will make the frame counter go back to zero immediately.
9	0b RW/AC	ASRC Counter Clear (ASRC_CNTR_CLR): Setting this to 1 will clear the ASRC Free running counter. This bit will self clear after the counter is cleared.
8	0b RW	ASRC Counter enable (ASRC_CNTR_EN): Setting this bit makes the Free running ASRC counter to start running. Clearing this bit will make it pause and hold it's current value.
7	1b RW	Fifo empty fix enable (FIFO_EMPTY_FIX_EN): Corner cases between the FIFO empty and APB writes happening to the TX FIFO around the time the new data needs to be sent out on the TXD are fixed with this bit.
6	1b RW	Underrun fix enable (UNDRN_FIX_EN): OSC to PLL switch along with underrun was causing unexpected behavior. This bit enables the fix for that bug.
5:4	00b RW	Reserved: This is a RW bit with no effect on IP behavior
3	0b RW	Clock Delay Enable (CLK_DEL_EN): When CLK_DEL_EN = 0, delay logic for capturing data from device is disabled. When CLK_DEL_EN = 1, delay logic for capturing data from device is delayed by half a period of the IO clock
2	0b RW	Slave Mode External Clock Run Enable (SLV_EXT_CLK_RUN_EN): When in Slave mode the receive state machine requires several clock edges (around 6) to properly sample incoming data. This bit enables a free running clock to the receive state machine before any data is received to properly sample the incoming data. 0 = Disable 1 = Enable
1	0b RW	Mode 1 Underrun Fix (Underrun_fix_1): Mode 1 of transmit underrun fix. In this mode, new data will start on the underrun slot. This function is only applied to TI and PSP modes. 0 = disable mode 1 1 = enable mode 1 If both underrun modes are enable, mode 1 has higher priority.
0	0b RW	Mode 0 Underrun Fix (Underrun_fix_0): Mode 0 of transmit underrun fix. In this mode, new data will always start at slot 0. This function is only applied to TI and PSP modes. 0 = disable mode 1 1 = enable mode 1

21.12.13 SSP Frame Select Register (SSFS)—Offset 44h

The SSP Frame select register is used to choose which frame signal to assert when accessing a slave device. SW drivers should set this register to assert the correct frame select to the targetted device.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSFS: [BAR + 0A0000h] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000001h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RSVD0								FRAME_SEL

Bit Range	Default & Access	Description
31:4	0b RO	RSVD0: Reserved
3:0	0001b RW	Frame Select Enable (FRAME_SEL): Each bit in this field corresponds to a frame signal of the SSP Controller. Not all SSP controllers have all frame selects pinned out so consult the pin list for indication of which SSP controllers support how many frame signals. [Bit 0] Frame Select 0 Master and Slave Supported [Bit 1] Frame Select 1 Master Only [Bit 2] Frame Select 2 Master Only [Bit 3] Frame Select 3 Master Only 0 = Frame Select Disabled 1 = Frame Select Enabled

21.12.14 SSP Slot Frame Counter Register[0-7] (FRAME_CNT[0-7])—Offset 48h, Count 8, Stride 4h

The slot frame counter is typically used in Audio modes and increments the counter every two SSPCLKs. This allows the OS to check the progress of a transfer. Since the SSP can support upto 8 slots in network mode there are 8 slot frame counters.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

FRAME_CNT[0-7]: [BAR + 0A0000h] + 48h + [0-7]*4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
FCNT_EN	RSVD0			FCNT_RST	FCNT			

Bit Range	Default & Access	Description
31	0b RW	Slot Frame Count Enable (FCNT_EN): 0 = Disable frame counter. 1 = Enable frame counter.
30:25	0b RO	RSVD0: Reserved
24	0b WO	Slot Frame Count Reset (FCNT_RST): SSP frame counter reset. Writing a 1 to this bit clears the frame counter.
23:0	000000h RO	Slot Frame Count (FCNT): SSP frame count.



21.12.15 SSP FIFO Level Register (SFIFOL)—Offset 68h

The SFIFOL register describes the current state of the RX and TX FIFOs. Not all bits of the TFL and RFL fields are used and depends on the actual hardware FIFO depth used in the instantiation of the SSP controller. This FIFO level register is meant to replace the SSSR.TFL and SSR.RFL fields.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SFIFOL: [BAR + 0A0000h] + 68h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: FFFF0000h

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
0	0	0	0	0	0	0	0	0
RFL				TFL				

Bit Range	Default & Access	Description
31:16	FFFFh RO	Receive FIFO Level (RFL): Number of entries minus one in Receive FIFO. Note: When the value of all 0xF's are read, the FIFO is either empty or full and the programmer should refer to the SSSR.RNE bit.
15:0	0000h RO	Transmit FIFO Level (TFL): Number of entries in Transmit FIFO. Note: When the value 0x0 is read, the FIFO is either empty or full and the programmer should refer to the SSSR.TNF bit.

21.12.16 SSP FIFO Trigger Threshold Register (SFIFOTT)—Offset 6Ch

The SFIFOTT is a register that determines when the the FIFOs will assert an interrupt for FIFO full indication. This is meant to replace the SSCR1.RFT and SSCR1.TFT legacy registers. The max size of these registers is based on the actualy FIFO depth in hardware and not the actual size of the bit field.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SFIFOTT: [BAR + 0A0000h] + 6Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RFL				TFL				

Bit Range	Default & Access	Description
31:16	0000h RW	Receive FIFO Trigger Threshold (RFT): Sets threshold level at which receive FIFO asserts interrupt. This level should be set to the desired threshold value minus 1. Notes on setting the RFT value. This applies to cases where SSP is receiving data from a device and is interfaced with a DMA channel via the hardware handshake mechanism. Please follow the following recommendations: 1. Number of bits denoted by the (DSS, EDSS) parameters in the SSP should match the SRC_TR_WIDTH programmed in the DMA channel. 2. (RFT+1) should be equal to (SRC_MSIZ). 3. Another option to 2 is to keep the BLOCK_TS in the DMA to be a multiple of (RFT+1)
15:0	0000h RW	Transmit FIFO Trigger Threshold (TFT): Sets threshold level at which transmit FIFO asserts interrupt. This level should be set to the desired threshold value minus 1.

21.12.17 SSP Control 3 Register (SSCR3)—Offset 70h

Software should only program this register if configuring the SSP in I2S/LJ mode or PCM master mode with the Tangier fixes. If neither is being enabled, SW can leave this register at the default power on value.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR3: [BAR + 0A0000h] + 70h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0002C604h

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
0				0				0				0				0				1				0				1				1				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0			

Bit Range	Default & Access	Description
31:18	0b RO	RSVD0: Reserved
17	1b RW	Sync Fix Enable (SYN_FIX_EN): This is a chicken bit for enabling the synchronizer fix for clr_underrun_ssp signal. SW should preserve this bit at its default value.
16	0b RW	Master Mode Clock Enable (MST_CLK_EN): When in single slot master mode (which is the mode used for emulating I2S or LJ master mode), the SSP core can stop the clock on a Tx underflow condition, preventing the Rx side from receiving data. This bit, when set, forces the clock to run when a Tx underflow happens, thereby allowing Rx side to continue functioning while Tx side is in underflow. SW should set this bit when I2S or LJ master mode is enabled i.e. bits 0 and 1 in this register are both set or when using 1-slot PCM (SFS or LFS) master mode operation. Otherwise, SW should leave this at 0.
15	1b RW	Stretch RX Pulse (STRETCH_RX): HW uses this as a chicken bit to stretch the RX pulse for proper clock crossing between SSP and APB domains. Note this bit is not tied to any specific SSP/PCM/I2S modes. SW should preserve this bit as the default value.
14	1b RW	Stretch TX Pulse (STRETCH_TX): HW uses this as a chicken bit to stretch the TX pulse for proper clock crossing between SSP and APB domains. Note this bit is not tied to any specific SSP/PCM/I2S modes. SW should preserve this bit as the default value.



Bit Range	Default & Access	Description
13	0b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	0b RW	I2S VISA Enable (I2S_VISA_EN): Enables newly added I2S and PCM wrapper logic debug signals sent out on the VISA bus instead of the core SSP debug signals. 0 = Core SSP Debug Signals 1 = New I2S and PCM Debug Signals
10	1b RW	I2S Receive Enable (I2S_RX_EN): When set, this bit enables data to be received on both the left and right slots of I2S. Otherwise, data on the slots are ignored. HW does not signal FIFO full condition when this bit is cleared. SW can set/clear this bit dynamically when I2S mode is operational.
9	1b RW	I2S Transmit Enable (I2S_TX_EN): When set, this bit enables data to be transmitted on both the left and right slots of I2S. Otherwise, data on the slots are ignored. HW does not signal FIFO full condition when this bit is cleared. SW can set/clear this bit dynamically when I2S mode is operational.
8	0b RO	Reserved (RSVD): Reserved.
7:6	00b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RW	I2S RX Slot Swap Fix Enable (I2S_RX_SS_FIX_EN): This bit enables the Rx overrun fix in I2S or LJ modes and prevents channel swapping when Rx overrun happens. Note that this bit does not apply to any PCM modes. PCM modes still have the Rx overflow channel aliasing issue, similar to PNW/CLV. SW should set this bit only when I2S or LJ mode (slave or master) is enabled. 0 = Disable 1 = Enable
3	0b RW	I2S TX Slot Swap Fix Enable (I2S_TX_SS_FIX_EN): This bit enables the TX underflow fix in I2S or LJ modes and prevents channel swapping when TX underflow happens. Note that this bit does not apply to any PCM modes. PCM modes still have the TX underflow channel aliasing issue, similar to PNW/CLV. SW should set this bit only when I2S or LJ mode (slave or master) is enabled. 0 = Disable 1 = Enable
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	I2S Mode Enable (I2S_MODE_EN): This bit enables I2S Mode. In I2S mode, slave or master mode operation is selected by appropriately clearing/setting bit 0 in this register. SW should select I2S mode operation before enabling the SSP controller. 0 = Disabled 1 = Enabled
0	0b RW	Frame Master Enable (FRM_MST_EN): When set, this bit enables the internal frame generator logic that allows accurate frame rate generation. This bit should be set for I2S and PCM master mode operations and cleared for all other modes. SW should select the proper value in this bit before enabling SSP controller. 0 = Disabled 1 = Enabled

21.12.18 SSP Control 4 Register (SSCR4)—Offset 74h

Software should only program this register if configuring the SSP in I2S/LJ mode or PCM master mode with the Tangier fixes. If neither is being enabled, SW can leave this register at the default power on value.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR4: [BAR + 0A0000h] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h



Bit Range	Default & Access	Description
0	0b RO	Reserved (RSVD): Reserved.

21.12.20 ASRC Free Running Timer (ASRC_FRT)—Offset 7Ch

This is a 32 bit free running counter that can be enabled, paused or cleared using bits in the SSCR2_XR register. The value reflected here will be noted down in the timer snapshot register when the frame count matches the frame threshold

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ASRC FRT: [BAR + 0A0000h] + 7Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
FREE_RUN_TIMER								

Bit Range	Default & Access	Description
31:0	00000000h RO/V	ASRC free running timer (FREE_RUN_TIMER): This field reflects the value of the free running timer.

21.12.21 Frame Threshold for ASRC Frame Count (ASRC_FTC)—Offset 80h

The frame threshold value at which the timer snapshot will be taken is written here.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ASRC_FTC: [BAR + 0A0000h] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0					ASRC_FTC			



Frame Snapshot Register

Type: Memory Mapped I/O Register
(Size: 32 bits)

ASRC SNPSHT: [BAR + 0A0000h] + 84h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
ASRC_TIMER_SNAPSHOT								

21.12.23 ASRC Frame Count (ASRC_FRMCNT)—Offset 88h

Frame Count Register


Type: Memory Mapped I/O Register
(Size: 32 bits)

ASRC_FRMCNT: [BAR + 0A0000h] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:0	0000h RO	ASRC Frame Count (ASRC_FRM_COUNT): This is the current frame count. This is a debug register and the value is noted in this register only when the LSB of the frame counter flips. If the counter is cleared when it was at an even value, the cleared value is not reflected here.



21.13 Low Power Audio I²S0 Address Map

Table 235. Summary of Low Power Audio I²S0 Memory Mapped I/O Registers—BAR

Offset	Size	Register ID—Description	Default Value
0h	4	"SSP Control 0 Register (SSCR0)—Offset 0h" on page 2896	00000000h
4h	4	"SSP Control 1 Register (SSCR1)—Offset 4h" on page 2897	43000000h
8h	4	"SSP Status Register (SSSR)—Offset 8h" on page 2899	0000F004h
Ch	4	"SSP Interrupt Test Register (SSITR)—Offset Ch" on page 2901	00000000h
10h	4	"SSP Data Register (SSDR)—Offset 10h" on page 2901	00000000h
28h	4	"SSP Time-Out Register (SSTO)—Offset 28h" on page 2902	00000000h
2Ch	4	"SSP Programmable Protocol Register (SSPSP)—Offset 2Ch" on page 2903	00000000h
30h	4	"SSM TX Time Slot Active Register (SSTSA)—Offset 30h" on page 2904	00000000h
34h	4	"SSP RX Time Slot Active Register (SSRSA)—Offset 34h" on page 2904	00000000h
38h	4	"SSP Time Slot Status Register (SSTSS)—Offset 38h" on page 2905	00000000h
3Ch	4	"SSP Audio Clock Divider (SSACD)—Offset 3Ch" on page 2905	00000000h
40h	4	"SSP Control 2 Register (SSCR2)—Offset 40h" on page 2906	000000C0h
44h	4	"SSP Frame Select Register (SSFS)—Offset 44h" on page 2907	00000001h
48h + [0-7]*4h	4	"SSP Slot Frame Counter Register[0-7] (FRAME_CNT[0-7])—Offset 48h, Count 8, Stride 4h" on page 2908	00000000h
68h	4	"SSP FIFO Level Register (SFIFOL)—Offset 68h" on page 2909	FFFF0000h
6Ch	4	"SSP FIFO Trigger Threshold Register (SFIFOTT)—Offset 6Ch" on page 2909	00000000h
70h	4	"SSP Control 3 Register (SSCR3)—Offset 70h" on page 2910	0002C604h
74h	4	"SSP Control 4 Register (SSCR4)—Offset 74h" on page 2911	00000000h
78h	4	"SSP Control 5 Register (SSCR5)—Offset 78h" on page 2912	00000000h
7Ch	4	"ASRC Free Running Timer (ASRC_FRT)—Offset 7Ch" on page 2913	00000000h
80h	4	"Frame Threshold for ASRC Frame Count (ASRC_FTC)—Offset 80h" on page 2913	00000000h
84h	4	"ASRC Timer Snapshot (ASRC_SNPSHT)—Offset 84h" on page 2914	00000000h
88h	4	"ASRC Frame Count (ASRC_FRMCNT)—Offset 88h" on page 2914	00000000h

21.13.1 SSP Control 0 Register (SSCR0)—Offset 0h

The Enhanced SSP Control 0 registers contain twelve different bit fields that control various functions within the Enhanced SSP. All bits must be set to the preferred value before enabling the Enhanced SSP. Note that Writes to reserved bits must be zeroes, and Read values of these bits is undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR0: [BAR + 0A1000h] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



31					28					24					20					16					12					8					4					0																																							
0					0					0					0					0					0					0					0					0					0																																		
MOD					ACS					RSVD					RSVD					RSVD					FRDC					TIM					RIM					NCS					EDSS					SCR										SSE					ECS					FRF					DSS				

Bit Range	Default & Access	Description
31	0b RW	Mode Select (MOD): 0 = Normal SSP Mode 1 = Network Mode
30	0b RW	Audio Clock Select (ACS): 0 = Clock selection is determined by the NCS and ECS bits 1 = Audio Clock (and Audio Clock Divider) are used to clock the SSP's serial clock (SSPCLK)
29	0b RO	Reserved (RSVD): Reserved.
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26:24	000b RW	Frame Rate Divider Control (FRDC): Value 0-7 indicates the number of time slots per frame when in network mode (the actual number of time slots is FRDC+1, so 1 to 8 time slots).
23	0b RW	Transmit FIFO Under Run Interrupt Mask (TIM): 0 = TUR events will generate an SSP interrupt 1 = TUR events will not generate an SSP interrupt
22	0b RW	Receive FIFO Over Run Interrupt Mask (RIM): 0 = ROR events will generate an SSP interrupt 1 = ROR events will not generate an SSP interrupt
21	0b RW	Network Clock Select (NCS): 0 = Clock selection is determined by ECS bit 1 = Network clock is used to create the SSP's serial clock (SSPCLK)
20	0b RW	Extended Data Size Select (EDSS): 0 = A zero is preappended to the DSS value which sets the DSS range from 4-16 bits 1 = A one is pre-appended to the DSS value which sets the DSS range from 17-32 bits
19:8	000h RW	Serial Clock Rate (SCR): Value (0 to 4095) used to generate transmission rate of SSP. Serial bit rate = SSP clock/(SCR+1), where SCR is decimal integer.
7	0b RW	Synchronous Serial Port Enable (SSE): 0 = SSP operation disabled and FIFOs are cleared 1 = SSP operation enabled
6	0b RW	External Clock Select (ECS): 0 = On-chip clock used to produce the SSP's serial clock (SSPCLK) 1 = SSPEXTCLK/GPIO pin is used to create the SSP's SSPCLK
5:4	00b RW	Frame Format (FRF): 00 = Motorola Serial Peripheral Interface (SPI) 01 = Texas Instruments Synchronous Serial Protocol (SSP) 10 = National Semiconductor Microwire 11 = Programmable Serial Protocol (PSP)
3:0	0000b RW	Data Size Select (DSS): With EDSS as MSB, value+1 gives data size. Values 4 to 32 allowed.

21.13.2 SSP Control 1 Register (SSCR1)—Offset 4h

The Enhanced SSP Control 1 registers contain bit fields that control various SSP functions. Bits must be set to the preferred value before enabling the Enhanced SSP. Note that Writes to reserved bits should be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR1: [BAR + 0A1000h] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 43000000h

31		28				24				20				16				12				8				4				0		
0	1	0	0	0	0	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
TTEP	TTE	EBCEI	SCFR	ECRA	ECRB	SCLKDIR	SFRMDIR	RWOT	TRAIL	TSRE	RSRE	TINTE	PINTE	RSVD	IFS	STRF	EFWR	RTF				TTF				MWDS		SPH	SPO	LBM	TIE	RTF

Bit Range	Default & Access	Description
31	0b RW	TXD Tristate Enable on Last Phase (TTLP): 0 = TXD line will be tristated on same clock edge as TXD is to be flopped 1 = TXD line will be tristated 1/2 clock edge after TXD is to be flopped
30	1b RW	TXD Tristate Enable (TTE): 0 = TXD line will not be tristated 1 = TXD line will be tristated when no transmitting data
29	0b RW	Enable Bit Count Error Interrupt (EBCEI): 0 = Interrupt due to a bit count error is disabled 1 = Interrupt due to a bit count error is enabled
28	0b RW	Slave Clock Free Running (SCFR): 0 = clock input to SSPSCLK is continuously running 1 = clock input to SSPSCLK is only active during transfers
27	0b RW	Enable Clock Request A (ECRA): 0 = clock request from other SSP is disabled 1 = clock request from other SSP is enabled
26	0b RW	Enable Clock Request B (ECRB): 0 = clock request from other SSP is disabled 1 = clock request from other SSP is enabled
25	1b RW	SSP Serial Bit Rate Clock (SSPSCLK) Direction (SCLKDIR): 0 = Master mode, SSP drives SSPSCLK 1 = Slave mode, SSP receives SSPSCLK
24	1b RW	SSP Frame (SSPSFRM) Direction (SFRMDIR): 0 = Master mode, SSP drives SSPSFRM 1 = Slave mode, SSP receives SSPSFRM
23	0b RW	Receive With Out Transmit (RWOT): 0 = Transmit/Receive mode 1 = Receive without transmit mode
22	0b RW	Trailing Byte (TRAIL): 0 = Processor based, trailing bytes are handled by processor 1 = DMA based, trailing bytes are handled by DMA
21	0b RW	Transmit Service Request Enable (TSRE): 0 = DMA Service Request is disabled 1 = DMA Service Request is enabled
20	0b RW	Receive Service Request Enable (RSRE): 0 = DMA Service Request is disabled 1 = DMA Service Request is enabled
19	0b RW	Receiver Time-out Interrupt Enable (TINTE): 0 = Receiver Time-out interrupts are disabled 1 = Receiver Time-out interrupts are enabled
18	0b RW	Peripheral Trailing Byte Interrupts Enable (PINTE): 0 = Peripheral Trailing Byte Interrupts are disabled 1 = Peripheral Trailing Byte Interrupts are enabled
17	0b RW	RSVD: Reserved
16	0b RW	Invert Frame Signal (IFS): 0 = Frame polarity is determined by SSP format and PSP polarity bits 1 = Frame signal will be inverted from the normal SSP frame signal (as defined by the SSP format nad PSP polarity bits)



Bit Range	Default & Access	Description
15	0b RW	Select FIFO for EFWR (test mode bit) (when EFWR=1) (STRF): 0 = Transmit FIFO is selected for both writes and reads through the SSP Data Register (SSDR) 1 = Receive FIFO is selected for both writes and reads through the SSP Data Register (SSDR)
14	0b RW	Enable FIFO Write/Read (test mode bit) (EFWR): 0 = FIFO write/read special function is disabled (normal SSP operational mode) 1 = FIFO write/read special function is enabled
13:10	0000b RW	Receive FIFO Trigger Threshold (RFT): Sets threshold level at which receive FIFO asserts interrupt. This level should be set to the desired threshold value minus 1. This is a legacy field and only represents the lower 4b of the FIFO Trigger Threshold. Please see SFIFOTT register for complete threshold setting.
9:6	0000b RW	Transmit FIFO Trigger Threshold (TFT): Sets threshold level at which transmit FIFO asserts interrupt. This level should be set to the desired threshold value minus 1. This is a legacy field and only represents the lower 4b of the FIFO Trigger Threshold. Please see SFIFOTT register for complete threshold setting.
5	0b RW	Microwire Transmit Data Size (MWDS): 0 = 8-bit command words are transmitted 1 = 16-bit command words are transmitted
4	0b RW	Motorola SPI SSPSCLK Phase Setting (SPH): 0 = SSPSCLK is inactive one cycle at the start of a frame and 1/2 cycle at the end of a frame 1 = SSPSCLK is inactive 1/2 cycle at the start of a frame and one cycle at the end of a frame
3	0b RW	Motorola SPI SSPSCLK polarity setting (SPO): 0 = The inactive or idle state of SSPSCLK is low 1 = The inactive or idle state of SSPSCLK is high
2	0b RW	Loop-Back Mode (test mode bit) (LBM): 0 = Normal serial port operation enabled 1 = Output of transmit serial shifter connected to input of receive serial shifter, internally
1	0b RW	Transmit FIFO Interrupt Enable (TIE): 0 = Transmit FIFO level interrupt is disabled 1 = Transmit FIFO level interrupt is enabled
0	0b RW	Receive FIFO Interrupt Enable (RIE): 0 = Receive FIFO level interrupt is disabled 1 = Receive FIFO level interrupt is enabled

21.13.3 SSP Status Register (SSSR)—Offset 8h

The Enhanced SSP Status registers contain bits that signal overrun errors as well as the Transmit and Receive FIFO service requests. Each of these hardware-detected events signals an Interrupt request to the Interrupt controller. The Status register also contains flags that indicate when the Enhanced SSP is actively transmitting data, when the Transmit FIFO is not full, and when the Receive FIFO is not empty. One Interrupt signal is sent to the Interrupt Controller for each SSP. These events can cause an Interrupt: End-of-Chain, Receiver Time-out, Peripheral Trailing Byte, Receive FIFO overrun, Receive FIFO request, and Transmit FIFO request.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSSR: [BAR + 0A1000h] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000F004h



Bit Range	Default & Access	Description
1:0	00b RO	RSVD3: Reserved

21.13.4 SSP Interrupt Test Register (SSITR)—Offset Ch

The read-write SSP Interrupt Test registers should be used only for testing purposes. Writing a 1 to the test transmit FIFO request SSITR.TTFS, bit 5, will generate a non-maskable Interrupt strobe signal to the Interrupt controller, and a DMA request for the Transmit FIFO. Writing a 1 to the test receive FIFO request SSITR.TRFS, bit 6, will generate a non-maskable Interrupt strobe signal to the Interrupt controller, and a DMA request for the Receive FIFO. Writing a 1 to the test receive FIFO overrun bit SSITR.TROR, bit 7, will generate a non-maskable Interrupt strobe signal to the Interrupt controller only, no DMA request will be made. Setting any of these bits will also cause the corresponding status bit(s) to be set in the Enhanced SSP Status register (SSSR). The Interrupt and/or service request, caused by the setting of one of these test bits, will remain active until the test bit is cleared by writing a 0 it. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSITR: [BAR + 0A1000h] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0							
RSVD1																				TROR				TRFS				TTFS				RSVD2			

Bit Range	Default & Access	Description
31:8	000000h RO	RSVD1: Reserved
7	0b RW	Test Receive FIFO overrun (TROR): 0 = No receive FIFO overrun service request 1 = Generates non-maskable interrupt to CPU. No DMA request is generated
6	0b RW	Test Receive FIFO service request (TRFS): 0 = No receive FIFO service request 1 = Generates non-maskable interrupt to CPU and a DMA request for receive FIFO
5	0b RW	Test Transmit FIFO service request (TTFS): 0 = No transmit FIFO service request pending 1 = Generates non-maskable interrupt to CPU and a DMA request for transmit FIFO
4:0	00000b RO	RSVD2: Reserved

21.13.5 SSP Data Register (SSDR)—Offset 10h

The Enhanced SSP Data registers are single address locations that Read-Write data transfers can access. The SSDR represents two physical registers: the first is temporary storage for data on its way out through the Transmit FIFO, the other is temporary storage for data coming in through the Receive FIFO. As the system accesses the



register, FIFO Control logic transfers data automatically between register and FIFO as fast as the system moves it. Data in the FIFO shifts up or down to accommodate the new word (unless it's an attempted Write to a full Transmit FIFO). Status bits (such as SSSR.TFL, SSSR.RFL, SSSR.RNE, and SSSR.TNF) show users whether the FIFO is full, above/below a programmable FIFO trigger threshold, or empty. For Transmit data transfers (Write from system to SSP peripheral), the register can be loaded (written) by the system processor anytime it falls below its threshold level when using programmed I/O. When a data size of less than 32-bits is selected, users should not left-justify data written to the Transmit FIFO. Transmit logic left-justifies the data and ignores any unused bits. Received data of less than 32-bits is automatically right-justified in the Receive FIFO. When the Enhanced SSP is programmed for National Semiconductor Microwire* frame format and if the size for Transmit data is 8-bits as selected by SSCR1.MWDS=0, then the most significant 24-bits are ignored. Similarly, if the size for the Transmit data is 16-bit as selected by SSCR1.MWDS=1, then most significant 16-bits are ignored. The SSCR0.DSS field controls the Receive data size.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSDR: [BAR + 0A1000h] + 10h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DATA								

Bit Range	Default & Access	Description
31:0	00000000h RO	Data (DATA): Data word to be written to/read from transmit/receive FIFO. When reading from this register when the SSP is disabled (SSE=0) then this will return indeterminate data.

21.13.6 SSP Time-Out Register (SSTO)—Offset 28h

The Enhanced SSP Time-Out registers have single bit fields that specify the time-out value used to signal a period of inactivity within the Receive FIFO. Note that Writes to reserved bits must be zeroes and reads are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTO: [BAR + 0A1000h] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				TIMEOUT				



Bit Range	Default & Access	Description
31:24	00h RO	RSVD: Reserved
23:0	000000h RW	Timeout Value (TIMEOUT): Is the value that defines the timeout interval, given by TIMEOUT/Peripheral Clock Frequency

21.13.7 SSP Programmable Protocol Register (SSPSP)—Offset 2Ch

The Enhanced SSP Programmable Protocol registers are read-write registers that contain eight fields that are used to program the various programmable serial-protocol parameters. When using PSP format in Network mode, the parameters SFRMDLY, STRTDLY, DMYSTP, DMYSTRT must be set to 0. Other parameters (such as FRMPOL, SCMODE, FSRT, SFRMDWDTH) are programmable. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSPSP: [BAR + 0A1000h] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0				0				0				0				0				0				0				0				0											
RSVD1				FSRT				DMYSTOP				RSVD2				SFRMWDTH				SFRMDLY				DMYSTRT				STRTDLY				ETDS				SFRMP				SCMODE			

Bit Range	Default & Access	Description
31:26	000000b RO	RSVD1: Reserved
25	0b RW	Frame Sync Relative Timing Bit (FSRT): 0 = Next frame is asserted after the end of the T4 timing 1 = Next frame is asserted with the LSB of the previous frame
24:23	00b RW	Dummy Stop (DMYSTOP): Programmed value sets the number of SSPCLK cycles that follow the transmitted data
22	0b RW	RSVD2: Reserved
21:16	000000b RW	Serial Frame Width (SFRMDWDTH): Programmed value sets frame width (1-38)
15:9	000000b RW	Serial Frame Delay (SFRMDLY): Programmed value sets the number of half SSPCLK cycles from TXD/RXD being driven to SSPSPFRM being asserted (0-74)
8:7	00b RW	Dummy Start (DMYSTRT): Programmed value sets the number of SSPCLKs after STRTDLY is complete that precede the transmit/receive data
6:4	000b RW	Start Delay (STRTDLY): Programmed value sets start delay that is used to set the idle time of SSPCLK between transfers (0-7 SSPCLK periods)
3	0b RW	End of Transfer Data State (ETDS): 0 = Low 1 = Last value (bit 0)



Bit Range	Default & Access	Description
2	0b RW	Serial Frame Polarity (SFRMP): 0 = SSPSFRM is active low 1 = SSPSFRM is active high
1:0	00b RW	Serial bit-rate Clock Mode (SCMODE): 00 = Data driven (falling), Data sampled (rising), Idle state (low) 01 = Data driven (rising), Data sampled (falling), Idle state (low) 10 = Data driven (rising), Data sampled (falling), Idle state (high) 11 = Data driven (falling), Data sampled (rising), Idle state (high)

21.13.8 SSM TX Time Slot Active Register (SSTSA)—Offset 30h

The Enhanced SSP TX Time Slot Active registers are read-write registers that indicate which Time Slot the Enhanced SSP will transmit data in and are ignored if the Enhanced SSP is not in Network Mode (SSCR0.MOD = 1). Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTSA: [BAR + 0A1000h] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Figure 1 illustrates the bitstream structure of the proposed scheme. The bitstream is 32 bits long, divided into two main sections: RSVD (Reserved) and TTSA (Test and Train Set Allocation). The RSVD section occupies the first 24 bits, and the TTSA section occupies the remaining 8 bits. The bitstream is represented as a sequence of 32 bits, with the first 24 bits grouped into six 4-bit blocks and the last 8 bits grouped into two 4-bit blocks.

Bit Range	Default & Access	Description
31:8	000000h RO	RSVD: Reserved
7:0	00h RW	TX Time Slot Active (TTSA): 0 = SSP will not transmit data in this time slot 1 = SSP will transmit data in this time slot

21.13.9 SSP RX Time Slot Active Register (SSRSA)—Offset 34h

The Enhanced SSP RX Time Slot Active registers are read-write registers that indicate which Time Slot the Enhanced SSP will receive data in and are ignored if the Enhanced SSP is not in Network Mode (SSCR0.MOD = 1). Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.


Type: Memory Mapped I/O Register
(Size: 32 bits)

SSRSA: [BAR + 0A1000h] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)


BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



	31	28	24	20	16	12	8	4	0	
	0	0	0	0	0	0	0	0	0	
INBSY	RSVD								TSS	

Intel Atom® Processor E3800 Product Family
Datasheet
2905



SSPSFRM frequency. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined. It's important to note that this feature is only available if implemented by the project instantiation. A clock source and mux must be instantiated outside of the SSP controller for this feature to work. Only this register is designed into the SSP Controller.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSACD: [BAR + 0A1000h] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RSVD							ACPS	SCDB	ACDS

Bit Range	Default & Access	Description
31:7	0000000h RO	RSVD: Reserved
6:4	000b RW	Audio Clock PLL Select (ACPS): Value indicates which PLL output clock is sent to the clock divider in the clock unit 000: 5.622MHz, 001: 11.345MHz, 010: 12.235MHz, 011: 14.857MHz, 100: 32.842MHz, 101: 48.000MHz, 110, 111: Reserved
3	0b RW	SYSCLK Divider Bypass (SCDB): 0 = SYSCLK is divided by 4 before being sent to SSP, 1 = SYSCLK is not divided before being sent to SSP
2:0	000b RW	Audio Clock Divider Select (ACDS): Value indicates which divider will be used by the clock unit to create the SYSCLK output pin. Clock divider value will be 2^ACDS, max ACDS = 5.

21.13.12 SSP Control 2 Register (SSCR2)—Offset 40h

The command status register 2 is extension of command status register and contains various feature enable and disables.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR2: [BAR + 0A1000h] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 000000C0h

31				28				24				20				16				12				8				4				0																											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0																													
RSVD0																ASRC_INTR_MASK				ASRC_FRM_CNTR_EN				ASRC_CNTR_CLR				ASRC_CNTR_EN				FIFO_EMPTY_FIX_EN				UNDRN_FIX_EN				Reserved				CLK_DEL_EN				SILV_EXT_CLK_RUN_EN				Underrun_fix_1				Underrun_fix_0			



Bit Range	Default & Access	Description
31:12	0b RO	RSVD0: Reserved
11	0b RW	ASRC Interrupt Mask (ASRC_INTR_MASK): Setting this bit to 1 masks the ASRC interrupt that is generated every time the frame count matches the frame threshold. Software should override this bit, since it have no reset value
10	0b RW	ASRC frame count enable (ASRC_FRM_CNTR_EN): Setting this bit enables the frame counter to start running. Clearing this bit will make the frame counter go back to zero immediately.
9	0b RW/AC	ASRC Counter Clear (ASRC_CNTR_CLR): Setting this to 1 will clear the ASRC Free running counter. This bit will self clear after the counter is cleared.
8	0b RW	ASRC Counter enable (ASRC_CNTR_EN): Setting this bit makes the Free running ASRC counter to start running. Clearing this bit will make it pause and hold it's current value.
7	1b RW	Fifo empty fix enable (FIFO_EMPTY_FIX_EN): Corner cases between the FIFO empty and APB writes happening to the TX FIFO around the time the new data needs to be sent out on the TXD are fixed with this bit.
6	1b RW	Underrun fix enable (UNDRN_FIX_EN): OSC to PLL switch along with underrun was causing unexpected behavior. This bit enables the fix for that bug.
5:4	00b RW	Reserved: This is a RW bit with no effect on IP behavior
3	0b RW	Clock Delay Enable (CLK_DEL_EN): When CLK_DEL_EN = 0, delay logic for capturing data from device is disabled. When CLK_DEL_EN = 1, delay logic for capturing data from device is delayed by half a period of the IO clock
2	0b RW	Slave Mode External Clock Run Enable (SLV_EXT_CLK_RUN_EN): When in Slave mode the receive state machine requires several clock edges (around 6) to properly sample incoming data. This bit enables a free running clock to the receive state machine before any data is received to properly sample the incoming data. 0 = Disable 1 = Enable
1	0b RW	Mode 1 Underrun Fix (Underrun_fix_1): Mode 1 of transmit underrun fix. In this mode, new data will start on the underrun slot. This function is only applied to TI and PSP modes. 0 = disable mode 1 1 = enable mode 1 If both underrun modes are enable, mode 1 has higher priority.
0	0b RW	Mode 0 Underrun Fix (Underrun_fix_0): Mode 0 of transmit underrun fix. In this mode, new data will always start at slot 0. This function is only applied to TI and PSP modes. 0 = disable mode 1 1 = enable mode 1

21.13.13 SSP Frame Select Register (SSFS)—Offset 44h

The SSP Frame select register is used to choose which frame signal to assert when accessing a slave device. SW drivers should set this register to assert the correct frame select to the targetted device.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSFS: [BAR + 0A1000h] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000001h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RSVD0								FRAME_SEL

Bit Range	Default & Access	Description
31:4	0b RO	RSVD0: Reserved
3:0	0001b RW	Frame Select Enable (FRAME_SEL): Each bit in this field corresponds to a frame signal of the SSP Controller. Not all SSP controllers have all frame selects pinned out so consult the pin list for indication of which SSP controllers support how many frame signals. [Bit 0] Frame Select 0 Master and Slave Supported [Bit 1] Frame Select 1 Master Only [Bit 2] Frame Select 2 Master Only [Bit 3] Frame Select 3 Master Only 0 = Frame Select Disabled 1 = Frame Select Enabled

21.13.14 SSP Slot Frame Counter Register[0-7] (FRAME_CNT[0-7])—Offset 48h, Count 8, Stride 4h

The slot frame counter is typically used in Audio modes and increments the counter every two SSPCLKs. This allows the OS to check the progress of a transfer. Since the SSP can support upto 8 slots in network mode there are 8 slot frame counters.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

FRAME_CNT[0-7]: [BAR + 0A1000h] + 48h + [0-7]*4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
FCNT_EN	RSVD0			FCNT_RST	FCNT			

Bit Range	Default & Access	Description
31	0b RW	Slot Frame Count Enable (FCNT_EN): 0 = Disable frame counter. 1 = Enable frame counter.
30:25	0b RO	RSVD0: Reserved
24	0b WO	Slot Frame Count Reset (FCNT_RST): SSP frame counter reset. Writing a 1 to this bit clears the frame counter.
23:0	000000h RO	Slot Frame Count (FCNT): SSP frame count.



21.13.15 SSP FIFO Level Register (SFIFOL)—Offset 68h

The SFIFOL register describes the current state of the RX and TX FIFOs. Not all bits of the TFL and RFL fields are used and depends on the actual hardware FIFO depth used in the instantiation of the SSP controller. This FIFO level register is meant to replace the SSSR.TFL and SSR.RFL fields.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SFIFOL: [BAR + 0A1000h] + 68h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: FFFF0000h

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
0	0	0	0	0	0	0	0	0
RFL				TFL				

Bit Range	Default & Access	Description
31:16	FFFFh RO	Receive FIFO Level (RFL): Number of entries minus one in Receive FIFO. Note: When the value of all 0xF's are read, the FIFO is either empty or full and the programmer should refer to the SSSR.RNE bit.
15:0	0000h RO	Transmit FIFO Level (TFL): Number of entries in Transmit FIFO. Note: When the value 0x0 is read, the FIFO is either empty or full and the programmer should refer to the SSSR.TNF bit.

21.13.16 SSP FIFO Trigger Threshold Register (SFIFOTT)—Offset 6Ch

The SFIFOTT is a register that determines when the the FIFOs will assert an interrupt for FIFO full indication. This is meant to replace the SSCR1.RFT and SSCR1.TFT legacy registers. The max size of these registers is based on the actualy FIFO depth in hardware and not the actual size of the bit field.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SFIFOTT: [BAR + 0A1000h] + 6Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RFL				TFL				

Bit Range	Default & Access	Description
31:16	0000h RW	Receive FIFO Trigger Threshold (RFT): Sets threshold level at which receive FIFO asserts interrupt. This level should be set to the desired threshold value minus 1. Notes on setting the RFT value. This applies to cases where SSP is receiving data from a device and is interfaced with a DMA channel via the hardware handshake mechanism. Please follow the following recommendations: 1. Number of bits denoted by the (DSS, EDSS) parameters in the SSP should match the SRC_TR_WIDTH programmed in the DMA channel. 2. (RFT+1) should be equal to (SRC_MSIZ). 3. Another option to 2 is to keep the BLOCK_TS in the DMA to be a multiple of (RFT+1)
15:0	0000h RW	Transmit FIFO Trigger Threshold (TFT): Sets threshold level at which transmit FIFO asserts interrupt. This level should be set to the desired threshold value minus 1.

21.13.17 SSP Control 3 Register (SSCR3)—Offset 70h

Software should only program this register if configuring the SSP in I2S/LJ mode or PCM master mode with the Tangier fixes. If neither is being enabled, SW can leave this register at the default power on value.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR3: [BAR + 0A1000h] + 70h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0002C604h

31				28				24				20				16				12				8				4				0												
0				0				0				0				0				1				0				1				1				0				0				0
RSVD0																				SYN_FIX_EN																								
																				MST_CLK_EN																								
																				STRETCH_RX																								
																				STRETCH_TX																								
																				RSVD																								
																				RSVD																								
																				I2S_VISA_EN																								
																				I2S_RX_EN																								
																				I2S_TX_EN																								
																				RSVD																								
																													RSVD															
																													RSVD															
																													I2S_RX_SS_FIX_EN															
																													I2S_TX_SS_FIX_EN															
																													RSVD															
																													I2S_MODE_EN															
																													FRM_MST_EN															

Bit Range	Default & Access	Description
31:18	0b RO	RSVD0: Reserved
17	1b RW	Sync Fix Enable (SYN_FIX_EN): This is a chicken bit for enabling the synchronizer fix for clr_underrun_ssp signal. SW should preserve this bit at its default value.
16	0b RW	Master Mode Clock Enable (MST_CLK_EN): When in single slot master mode (which is the mode used for emulating I2S or LJ master mode), the SSP core can stop the clock on a Tx underflow condition, preventing the Rx side from receiving data. This bit, when set, forces the clock to run when a Tx underflow happens, thereby allowing Rx side to continue functioning while Tx side is in underflow. SW should set this bit when I2S or LJ master mode is enabled i.e. bits 0 and 1 in this register are both set or when using 1-slot PCM (SFS or LFS) master mode operation. Otherwise, SW should leave this at 0.
15	1b RW	Stretch RX Pulse (STRETCH_RX): HW uses this as a chicken bit to stretch the RX pulse for proper clock crossing between SSP and APB domains. Note this bit is not tied to any specific SSP/PCM/I2S modes. SW should preserve this bit as the default value.
14	1b RW	Stretch TX Pulse (STRETCH_TX): HW uses this as a chicken bit to stretch the TX pulse for proper clock crossing between SSP and APB domains. Note this bit is not tied to any specific SSP/PCM/I2S modes. SW should preserve this bit as the default value.



Bit Range	Default & Access	Description
13	0b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	0b RW	I2S VISA Enable (I2S_VISA_EN): Enables newly added I2S and PCM wrapper logic debug signals sent out on the VISA bus instead of the core SSP debug signals. 0 = Core SSP Debug Signals 1 = New I2S and PCM Debug Signals
10	1b RW	I2S Receive Enable (I2S_RX_EN): When set, this bit enables data to be received on both the left and right slots of I2S. Otherwise, data on the slots are ignored. HW does not signal FIFO full condition when this bit is cleared. SW can set/clear this bit dynamically when I2S mode is operational.
9	1b RW	I2S Transmit Enable (I2S_TX_EN): When set, this bit enables data to be transmitted on both the left and right slots of I2S. Otherwise, data on the slots are ignored. HW does not signal FIFO full condition when this bit is cleared. SW can set/clear this bit dynamically when I2S mode is operational.
8	0b RO	Reserved (RSVD): Reserved.
7:6	00b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RW	I2S RX Slot Swap Fix Enable (I2S_RX_SS_FIX_EN): This bit enables the Rx overrun fix in I2S or LJ modes and prevents channel swapping when Rx overrun happens. Note that this bit does not apply to any PCM modes. PCM modes still have the Rx overflow channel aliasing issue, similar to PNW/CLV. SW should set this bit only when I2S or LJ mode (slave or master) is enabled. 0 = Disable 1 = Enable
3	0b RW	I2S TX Slot Swap Fix Enable (I2S_TX_SS_FIX_EN): This bit enables the TX underflow fix in I2S or LJ modes and prevents channel swapping when TX underflow happens. Note that this bit does not apply to any PCM modes. PCM modes still have the TX underflow channel aliasing issue, similar to PNW/CLV. SW should set this bit only when I2S or LJ mode (slave or master) is enabled. 0 = Disable 1 = Enable
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	I2S Mode Enable (I2S_MODE_EN): This bit enables I2S Mode. In I2S mode, slave or master mode operation is selected by appropriately clearing/setting bit 0 in this register. SW should select I2S mode operation before enabling the SSP controller. 0 = Disabled 1 = Enabled
0	0b RW	Frame Master Enable (FRM_MST_EN): When set, this bit enables the internal frame generator logic that allows accurate frame rate generation. This bit should be set for I2S and PCM master mode operations and cleared for all other modes. SW should select the proper value in this bit before enabling SSP controller. 0 = Disabled 1 = Enabled

21.13.18 SSP Control 4 Register (SSCR4)—Offset 74h

Software should only program this register if configuring the SSP in I2S/LJ mode or PCM master mode with the Tangier fixes. If neither is being enabled, SW can leave this register at the default power on value.


Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR4: [BAR + 0A1000h] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h



Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:7	000h RW	Total Frame Period (TOT_FRM_PRD): The total frame period (both asserted and deasserted time of frame), measured in bit clocks, that is driven in I2S, LJ and PCM master modes. This can be controlled to get the desired accuracy on frame rate. A value of 0 and a value smaller than the value programmed in SSCR5.FrameAssertedWidth are illegal
6:0	00h RO	Reserved (RSVD): Reserved.

Software should only program this register if configuring the SSP in I2S/LJ mode or PCM master mode with the Tangier fixes. If neither is being enabled, SW can leave this register at the default power on value.

Type: Memory Mapped I/O Register
(Size: 32 bits)


SSCR5: [BAR + 0A1000h] + 78h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:26	0b RO	RSVD0: Reserved
25:1	0000000h RW	Frame Assert Width (FRM_ASRT_WIDTH): This field controls the width of the asserted period of frame in I2S, LJ and PCM master modes. A value of 1 indicates a width of 2 bit clock period, 2 indicates a width of 3 bit clock periods, etc. The frame width is Frame Assert Width + 1.



Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:0	0000h RO	ASRC Frame Count (ASRC_FRM_COUNT): This is the current frame count. This is a debug register and the value is noted in this register only when the LSB of the frame counter flips. If the counter is cleared when it was at an even value, the cleared value is not reflected here.



21.14 Low Power Audio I²S0 Address Map

Table 236. Summary of Low Power Audio I²S0 Memory Mapped I/O Registers—BAR

Offset	Size	Register ID—Description	Default Value
0h	4	"SSP Control 0 Register (SSCR0)—Offset 0h" on page 2916	00000000h
4h	4	"SSP Control 1 Register (SSCR1)—Offset 4h" on page 2917	43000000h
8h	4	"SSP Status Register (SSSR)—Offset 8h" on page 2919	0000F004h
Ch	4	"SSP Interrupt Test Register (SSITR)—Offset Ch" on page 2921	00000000h
10h	4	"SSP Data Register (SSDR)—Offset 10h" on page 2921	00000000h
28h	4	"SSP Time-Out Register (SSTO)—Offset 28h" on page 2922	00000000h
2Ch	4	"SSP Programmable Protocol Register (SSPSP)—Offset 2Ch" on page 2923	00000000h
30h	4	"SSM TX Time Slot Active Register (SSTSA)—Offset 30h" on page 2924	00000000h
34h	4	"SSP RX Time Slot Active Register (SSRSA)—Offset 34h" on page 2924	00000000h
38h	4	"SSP Time Slot Status Register (SSTSS)—Offset 38h" on page 2925	00000000h
3Ch	4	"SSP Audio Clock Divider (SSACD)—Offset 3Ch" on page 2925	00000000h
40h	4	"SSP Control 2 Register (SSCR2)—Offset 40h" on page 2926	000000C0h
44h	4	"SSP Frame Select Register (SSFS)—Offset 44h" on page 2927	00000001h
48h + [0-7]*4h	4	"SSP Slot Frame Counter Register[0-7] (FRAME_CNT[0-7])—Offset 48h, Count 8, Stride 4h" on page 2928	00000000h
68h	4	"SSP FIFO Level Register (SFIFOL)—Offset 68h" on page 2929	FFFF0000h
6Ch	4	"SSP FIFO Trigger Threshold Register (SFIFOTT)—Offset 6Ch" on page 2929	00000000h
70h	4	"SSP Control 3 Register (SSCR3)—Offset 70h" on page 2930	0002C604h
74h	4	"SSP Control 4 Register (SSCR4)—Offset 74h" on page 2931	00000000h
78h	4	"SSP Control 5 Register (SSCR5)—Offset 78h" on page 2932	00000000h
7Ch	4	"ASRC Free Running Timer (ASRC_FRT)—Offset 7Ch" on page 2933	00000000h
80h	4	"Frame Threshold for ASRC Frame Count (ASRC_FTC)—Offset 80h" on page 2933	00000000h
84h	4	"ASRC Timer Snapshot (ASRC_SNPSHT)—Offset 84h" on page 2934	00000000h
88h	4	"ASRC Frame Count (ASRC_FRMCNT)—Offset 88h" on page 2934	00000000h

21.14.1 SSP Control 0 Register (SSCR0)—Offset 0h

The Enhanced SSP Control 0 registers contain twelve different bit fields that control various functions within the Enhanced SSP. All bits must be set to the preferred value before enabling the Enhanced SSP. Note that Writes to reserved bits must be zeroes, and Read values of these bits is undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR0: [BAR + 0A2000h] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



31					28					24					20					16					12					8					4					0																																							
0					0					0					0					0					0					0					0					0					0																																		
MOD					ACS					RSVD					RSVD					RSVD					FRDC					TIM					RIM					NCS					EDSS					SCR										SSE					ECS					FRF					DSS				

Bit Range	Default & Access	Description
31	0b RW	Mode Select (MOD): 0 = Normal SSP Mode 1 = Network Mode
30	0b RW	Audio Clock Select (ACS): 0 = Clock selection is determined by the NCS and ECS bits 1 = Audio Clock (and Audio Clock Divider) are used to clock the SSP's serial clock (SSPCLK)
29	0b RO	Reserved (RSVD): Reserved.
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26:24	000b RW	Frame Rate Divider Control (FRDC): Value 0-7 indicates the number of time slots per frame when in network mode (the actual number of time slots is FRDC+1, so 1 to 8 time slots).
23	0b RW	Transmit FIFO Under Run Interrupt Mask (TIM): 0 = TUR events will generate an SSP interrupt 1 = TUR events will not generate an SSP interrupt
22	0b RW	Receive FIFO Over Run Interrupt Mask (RIM): 0 = ROR events will generate an SSP interrupt 1 = ROR events will not generate an SSP interrupt
21	0b RW	Network Clock Select (NCS): 0 = Clock selection is determined by ECS bit 1 = Network clock is used to create the SSP's serial clock (SSPCLK)
20	0b RW	Extended Data Size Select (EDSS): 0 = A zero is preappended to the DSS value which sets the DSS range from 4-16 bits 1 = A one is pre-appended to the DSS value which sets the DSS range from 17-32 bits
19:8	000h RW	Serial Clock Rate (SCR): Value (0 to 4095) used to generate transmission rate of SSP. Serial bit rate = SSP clock/(SCR+1), where SCR is decimal integer.
7	0b RW	Synchronous Serial Port Enable (SSE): 0 = SSP operation disabled and FIFOs are cleared 1 = SSP operation enabled
6	0b RW	External Clock Select (ECS): 0 = On-chip clock used to produce the SSP's serial clock (SSPCLK) 1 = SSPEXTCLK/GPIO pin is used to create the SSP's SSPCLK
5:4	00b RW	Frame Format (FRF): 00 = Motorola Serial Peripheral Interface (SPI) 01 = Texas Instruments Synchronous Serial Protocol (SSP) 10 = National Semiconductor Microwire 11 = Programmable Serial Protocol (PSP)
3:0	0000b RW	Data Size Select (DSS): With EDSS as MSB, value+1 gives data size. Values 4 to 32 allowed.

21.14.2 SSP Control 1 Register (SSCR1)—Offset 4h

The Enhanced SSP Control 1 registers contain bit fields that control various SSP functions. Bits must be set to the preferred value before enabling the Enhanced SSP. Note that Writes to reserved bits should be zeroes, and Read value of these bits are undetermined.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR1: [BAR + 0A2000h] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 43000000h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	0	1	1	0
TTELP	TTE	EBCEI	SCFR	ECRA	ECRB	SCLKDIR	SFRMDIR	RWOT
								TRAIL
								TSRE
								RSRE
								TINTE
								PINTE
								RSVD
								IFS
								STRF
								EFWR
								RFT
								TFT
								MWDS
								SPH
								SPO
								LBM
								TIE
								RIE

Bit Range	Default & Access	Description
31	0b RW	TXD Tristate Enable on Last Phase (TTELP): 0 = TXD line will be tristated on same clock edge as TXD is to be flopped 1 = TXD line will be tristated 1/2 clock edge after TXD is to be flopped
30	1b RW	TXD Tristate Enable (TTE): 0 = TXD line will not be tristated 1 = TXD line will be tristated when no transmitting data
29	0b RW	Enable Bit Count Error Interrupt (EBCEI): 0 = Interrupt due to a bit count error is disabled 1 = Interrupt due to a bit count error is enabled
28	0b RW	Slave Clock Free Running (SCFR): 0 = clock input to SSPSCLK is continuously running 1 = clock input to SSPSCLK is only active durring transfers
27	0b RW	Enable Clock Request A (ECRA): 0 = clock request from other SSP is disabled 1 = clock request from other SSP is enabled
26	0b RW	Enable Clock Request B (ECRB): 0 = clock request from other SSP is disabled 1 = clock request from other SSP is enabled
25	1b RW	SSP Serial Bit Rate Clock (SSPSCLK) Direction (SCLKDIR): 0 = Master mode, SSP drives SSPSCLK 1 = Slave mode, SSP recieves SSPSCLK
24	1b RW	SSP Frame (SSPSFRM) Direction (SFRMDIR): 0 = Master mode, SSP drives SSPSFRM 1 = Slave mode, SSP receives SSPSFRM
23	0b RW	Receive With Out Transmit (RWOT): 0 = Transmit/Receive mode 1 = Receive without transmit mode
22	0b RW	Trailing Byte (TRAIL): 0 = Processor based, trailing bytes are handled by processor 1 = DMA based, trailing bytes are handled by DMA
21	0b RW	Transmit Service Request Enable (TSRE): 0 = DMA Service Request is disabled 1 = DMA Service Request is enabled
20	0b RW	Receive Service Request Enable (RSRE): 0 = DMA Service Request is disabled 1 = DMA Service Request is enabled
19	0b RW	Receiver Time-out Interrupt Enable (TINTE): 0 = Receiver Time-out interrupts are disabled 1 = Receiver Time-out interrupts are enabled
18	0b RW	Peripheral Trailing Byte Interrupts Enable (PINTE): 0 = Peripheral Trailing Byte Interrupts are disabled 1 = Peripheral Trailing Byte Interrupts are enabled
17	0b RW	RSVD: Reserved
16	0b RW	Invert Frame Signal (IFS): 0 = Frame polarity is determined by SSP format and PSP polarity bits 1 = Frame signal will be inverted from the normal SSP frame signal (as defined by the SSP format nad PSP polarity bits)



Bit Range	Default & Access	Description
15	0b RW	Select FIFO for EFWR (test mode bit) (when EFWR=1) (STRF): 0 = Transmit FIFO is selected for both writes and reads through the SSP Data Register (SSDR) 1 = Receive FIFO is selected for both writes and reads through the SSP Data Register (SSDR)
14	0b RW	Enable FIFO Write/Read (test mode bit) (EFWR): 0 = FIFO write/read special function is disabled (normal SSP operational mode) 1 = FIFO write/read special function is enabled
13:10	0000b RW	Receive FIFO Trigger Threshold (RFT): Sets threshold level at which receive FIFO asserts interrupt. This level should be set to the desired threshold value minus 1. This is a legacy field and only represents the lower 4b of the FIFO Trigger Threshold. Please see SFIFOTT register for complete threshold setting.
9:6	0000b RW	Transmit FIFO Trigger Threshold (TFT): Sets threshold level at which transmit FIFO asserts interrupt. This level should be set to the desired threshold value minus 1. This is a legacy field and only represents the lower 4b of the FIFO Trigger Threshold. Please see SFIFOTT register for complete threshold setting.
5	0b RW	Microwire Transmit Data Size (MWDS): 0 = 8-bit command words are transmitted 1 = 16-bit command words are transmitted
4	0b RW	Motorola SPI SSPSCLK Phase Setting (SPH): 0 = SSPSCLK is inactive one cycle at the start of a frame and 1/2 cycle at the end of a frame 1 = SSPSCLK is inactive 1/2 cycle at the start of a frame and one cycle at the end of a frame
3	0b RW	Motorola SPI SSPSCLK polarity setting (SPO): 0 = The inactive or idle state of SSPSCLK is low 1 = The inactive or idle state of SSPSCLK is high
2	0b RW	Loop-Back Mode (test mode bit) (LBM): 0 = Normal serial port operation enabled 1 = Output of transmit serial shifter connected to input of receive serial shifter, internally
1	0b RW	Transmit FIFO Interrupt Enable (TIE): 0 = Transmit FIFO level interrupt is disabled 1 = Transmit FIFO level interrupt is enabled
0	0b RW	Receive FIFO Interrupt Enable (RIE): 0 = Receive FIFO level interrupt is disabled 1 = Receive FIFO level interrupt is enabled

21.14.3 SSP Status Register (SSSR)—Offset 8h

The Enhanced SSP Status registers contain bits that signal overrun errors as well as the Transmit and Receive FIFO service requests. Each of these hardware-detected events signals an Interrupt request to the Interrupt controller. The Status register also contains flags that indicate when the Enhanced SSP is actively transmitting data, when the Transmit FIFO is not full, and when the Receive FIFO is not empty. One Interrupt signal is sent to the Interrupt Controller for each SSP. These events can cause an Interrupt: End-of-Chain, Receiver Time-out, Peripheral Trailing Byte, Receive FIFO overrun, Receive FIFO request, and Transmit FIFO request.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSSR: [BAR + 0A2000h] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0000F004h



Bit Range	Default & Access	Description
1:0	00b RO	RSVD3: Reserved

21.14.4 SSP Interrupt Test Register (SSITR)—Offset Ch

The read-write SSP Interrupt Test registers should be used only for testing purposes. Writing a 1 to the test transmit FIFO request SSITR.TTFS, bit 5, will generate a non-maskable Interrupt strobe signal to the Interrupt controller, and a DMA request for the Transmit FIFO. Writing a 1 to the test receive FIFO request SSITR.TRFS, bit 6, will generate a non-maskable Interrupt strobe signal to the Interrupt controller, and a DMA request for the Receive FIFO. Writing a 1 to the test receive FIFO overrun bit SSITR.TROR, bit 7, will generate a non-maskable Interrupt strobe signal to the Interrupt controller only, no DMA request will be made. Setting any of these bits will also cause the corresponding status bit(s) to be set in the Enhanced SSP Status register (SSSR). The Interrupt and/or service request, caused by the setting of one of these test bits, will remain active until the test bit is cleared by writing a 0 to it. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSITR: [BAR + 0A2000h] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0											
RSVD1																				TROR				TRFS				TTFS				RSVD2											

Bit Range	Default & Access	Description
31:8	000000h RO	RSVD1: Reserved
7	0b RW	Test Receive FIFO overrun (TROR): 0 = No receive FIFO overrun service request 1 = Generates non-maskable interrupt to CPU. No DMA request is generated
6	0b RW	Test Receive FIFO service request (TRFS): 0 = No receive FIFO service request 1 = Generates non-maskable interrupt to CPU and a DMA request for receive FIFO
5	0b RW	Test Transmit FIFO service request (TTFS): 0 = No transmit FIFO service request pending 1 = Generates non-maskable interrupt to CPU and a DMA request for transmit FIFO
4:0	00000b RO	RSVD2: Reserved

21.14.5 SSP Data Register (SSDR)—Offset 10h

The Enhanced SSP Data registers are single address locations that Read-Write data transfers can access. The SSDR represents two physical registers: the first is temporary storage for data on its way out through the Transmit FIFO, the other is temporary storage for data coming in through the Receive FIFO. As the system accesses the



register, FIFO Control logic transfers data automatically between register and FIFO as fast as the system moves it. Data in the FIFO shifts up or down to accommodate the new word (unless it's an attempted Write to a full Transmit FIFO). Status bits (such as SSSR.TFL, SSSR.RFL, SSSR.RNE, and SSSR.TNF) show users whether the FIFO is full, above/below a programmable FIFO trigger threshold, or empty. For Transmit data transfers (Write from system to SSP peripheral), the register can be loaded (written) by the system processor anytime it falls below its threshold level when using programmed I/O. When a data size of less than 32-bits is selected, users should not left-justify data written to the Transmit FIFO. Transmit logic left-justifies the data and ignores any unused bits. Received data of less than 32-bits is automatically right-justified in the Receive FIFO. When the Enhanced SSP is programmed for National Semiconductor Microwire* frame format and if the size for Transmit data is 8-bits as selected by SSCR1.MWDS=0, then the most significant 24-bits are ignored. Similarly, if the size for the Transmit data is 16-bit as selected by SSCR1.MWDS=1, then most significant 16-bits are ignored. The SSCR0.DSS field controls the Receive data size.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSDR: [BAR + 0A2000h] + 10h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DATA								

Bit Range	Default & Access	Description
31:0	00000000h RO	Data (DATA): Data word to be written to/read from transmit/receive FIFO. When reading from this register when the SSP is disabled (SSE=0) then this will return indeterminate data.

21.14.6 SSP Time-Out Register (SSTO)—Offset 28h

The Enhanced SSP Time-Out registers have single bit fields that specify the time-out value used to signal a period of inactivity within the Receive FIFO. Note that Writes to reserved bits must be zeroes and reads are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTO: [BAR + 0A2000h] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				TIMEOUT				



Bit Range	Default & Access	Description
31:24	00h RO	RSVD: Reserved
23:0	000000h RW	Timeout Value (TIMEOUT): Is the value that defines the timeout interval, given by TIMEOUT/Peripheral Clock Frequency

21.14.7 SSP Programmable Protocol Register (SSPSP)—Offset 2Ch

The Enhanced SSP Programmable Protocol registers are read-write registers that contain eight fields that are used to program the various programmable serial-protocol parameters. When using PSP format in Network mode, the parameters SFRMDLY, STRTDLY, DMYSTP, DMYSTRT must be set to 0. Other parameters (such as FRMPOL, SCMODE, FSRT, SFRMDWDTH) are programmable. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSPSP: [BAR + 0A2000h] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0				0				0				0				0				0				0				0				0				0							
RSVD1				FSRT				DMYSTOP				RSVD2				SFRMWDTH				SFRMDLY				DMYSTRT				STRTDLY				ETDS				SFRMP				SCMODE			

Bit Range	Default & Access	Description
31:26	000000b RO	RSVD1: Reserved
25	0b RW	Frame Sync Relative Timing Bit (FSRT): 0 = Next frame is asserted after the end of the T4 timing 1 = Next frame is asserted with the LSB of the previous frame
24:23	00b RW	Dummy Stop (DMYSTOP): Programmed value sets the number of SSPCLK cycles that follow the transmitted data
22	0b RW	RSVD2: Reserved
21:16	000000b RW	Serial Frame Width (SFRMDWDTH): Programmed value sets frame width (1-38)
15:9	000000b RW	Serial Frame Delay (SFRMDLY): Programmed value sets the number of half SSPCLK cycles from TXD/RXD being driven to SSPSPFRM being asserted (0-74)
8:7	00b RW	Dummy Start (DMYSTRT): Programmed value sets the number of SSPCLKs after STRTDLY is complete that precede the transmit/receive data
6:4	000b RW	Start Delay (STRTDLY): Programmed value sets start delay that is used to set the idle time of SSPCLK between transfers (0-7 SSPCLK periods)
3	0b RW	End of Transfer Data State (ETDS): 0 = Low 1 = Last value (bit 0)

31 28 24 20 16 12 8 4 0									
0 0 0 0 0 0 0 0 0 0									
RSVD RTSA									

Bit Range	Default & Access	Description
31:8	000000h RO	RSVD: Reserved
7:0	00h RW	RX Time Slot Active (RTSA): 0 = SSP will not receive data in this time slot 1 = SSP will receive data in this time slot

21.14.10 SSP Time Slot Status Register (SSTSS)—Offset 38h

The Enhanced SSP Time Slot Status registers are read only registers that indicate which Time Slot the Enhanced SSP is currently in when the Enhanced SSP is in Network Mode (SSCR0.MOD = 1). This register is not valid when the Enhanced SSP is not in Network Mode. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTSS: [BAR + 0A2000h] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
NBSY		RSVD						TSS	

Bit Range	Default & Access	Description
31	0b RO	Network Mode Busy (NBSY): 0 = No frame is currently active (in network mode only) 1 = SSP is in network mode and a frame is currently active
30:3	0000000h RO	RSVD: Reserved
2:0	000b RO	Time Slot Status (TSS): Value indicates which time slot is currently active

21.14.11 SSP Audio Clock Divider (SSACD)—Offset 3Ch

The Enhanced SSP Audio Clock Divider registers are read-write registers that indicate which clock frequency is sent to the Enhanced SSP and to the SYSCLK pin. If SSCR0.SCR is not 0, then there is no guaranteed phase relationship between SYSCLK and SSPSCLK. The SSPSFRM Frame Synch Sampling Frequency is calculated by dividing the chosen PLL output clock frequency (SSACD.ACPS) by the chosen divider (SSACD.ACDS) which gives the SYSCLK frequency. The SYSCLK is then divided by 4 (or by 1) to get the SSPSCLK. The SSPSCLK is divided by the data size (EDSS, DSS values) and by the number of time slots being used (SSCR0.FRDC value), if any, to give the



SSPSFRM frequency. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined. It's important to note that this feature is only available if implemented by the project instantiation. A clock source and mux must be instantiated outside of the SSP controller for this feature to work. Only this register is designed into the SSP Controller.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSACD: [BAR + 0A2000h] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							ACPS	SCDB
								ACDS

Bit Range	Default & Access	Description
31:7	0000000h RO	RSVD: Reserved
6:4	000b RW	Audio Clock PLL Select (ACPS): Value indicates which PLL output clock is sent to the clock divider in the clock unit 000: 5.622MHz, 001: 11.345MHz, 010: 12.235MHz, 011: 14.857MHz, 100: 32.842MHz, 101: 48.000MHz, 110, 111: Reserved
3	0b RW	SYSCLK Divider Bypass (SCDB): 0 = SYSCLK is divided by 4 before being sent to SSP 1 = SYSCLK is not divided before being sent to SSP
2:0	000b RW	Audio Clock Divider Select (ACDS): Value indicates which divider will be used by the clock unit to create the SYSCLK output pin. Clock divider value will be 2^{ACDS} , max ACDS = 5.

21.14.12 SSP Control 2 Register (SSCR2)—Offset 40h

The command status register 2 is extension of command status register and contains various feature enable and disables.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR2: [BAR + 0A2000h] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 000000C0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	1	1
RSVD0						ASRC_INTR_MASK	0	0
						ASRC_FRM_CNTR_EN	0	0
						ASRC_CNTR_CLR	0	0
						ASRC_CNTR_EN	0	0
						FIFO_EMPTY_FIX_EN	1	1
						UNDRN_FIX_EN	0	0
						Reserved	0	0
						CLK_DEL_EN	0	0
						SLV_EXT_CLK_RUN_EN	0	0
						Underrun_fix_1	0	0
						Underrun_fix_0	0	0



Bit Range	Default & Access	Description
31:12	0b RO	RSVD0: Reserved
11	0b RW	ASRC Interrupt Mask (ASRC_INTR_MASK): Setting this bit to 1 masks the ASRC interrupt that is generated every time the frame count matches the frame threshold. Software should override this bit, since it have no reset value
10	0b RW	ASRC frame count enable (ASRC_FRM_CNTR_EN): Setting this bit enables the frame counter to start running. Clearing this bit will make the frame counter go back to zero immediately.
9	0b RW/AC	ASRC Counter Clear (ASRC_CNTR_CLR): Setting this to 1 will clear the ASRC Free running counter. This bit will self clear after the counter is cleared.
8	0b RW	ASRC Counter enable (ASRC_CNTR_EN): Setting this bit makes the Free running ASRC counter to start running. Clearing this bit will make it pause and hold it's current value.
7	1b RW	Fifo empty fix enable (FIFO_EMPTY_FIX_EN): Corner cases between the FIFO empty and APB writes happening to the TX FIFO around the time the new data needs to be sent out on the TXD are fixed with this bit.
6	1b RW	Underrun fix enable (UNDRN_FIX_EN): OSC to PLL switch along with underrun was causing unexpected behavior. This bit enables the fix for that bug.
5:4	00b RW	Reserved: This is a RW bit with no effect on IP behavior
3	0b RW	Clock Delay Enable (CLK_DEL_EN): When CLK_DEL_EN = 0, delay logic for capturing data from device is disabled. When CLK_DEL_EN = 1, delay logic for capturing data from device is delayed by half a period of the IO clock
2	0b RW	Slave Mode External Clock Run Enable (SLV_EXT_CLK_RUN_EN): When in Slave mode the receive state machine requires several clock edges (around 6) to properly sample incoming data. This bit enables a free running clock to the receive state machine before any data is received to properly sample the incoming data. 0 = Disable 1 = Enable
1	0b RW	Mode 1 Underrun Fix (Underrun_fix_1): Mode 1 of transmit underrun fix. In this mode, new data will start on the underrun slot. This function is only applied to TI and PSP modes. 0 = disable mode 1 1 = enable mode 1 If both underrun modes are enable, mode 1 has higher priority.
0	0b RW	Mode 0 Underrun Fix (Underrun_fix_0): Mode 0 of transmit underrun fix. In this mode, new data will always start at slot 0. This function is only applied to TI and PSP modes. 0 = disable mode 1 1 = enable mode 1

21.14.13 SSP Frame Select Register (SSFS)—Offset 44h

The SSP Frame select register is used to choose which frame signal to assert when accessing a slave device. SW drivers should set this register to assert the correct frame select to the targetted device.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSFS: [BAR + 0A2000h] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000001h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RSVD0								FRAME_SEL

Bit Range	Default & Access	Description
31:4	0b RO	RSVD0: Reserved
3:0	0001b RW	Frame Select Enable (FRAME_SEL): Each bit in this field corresponds to a frame signal of the SSP Controller. Not all SSP controllers have all frame selects pinned out so consult the pin list for indication of which SSP controllers support how many frame signals. [Bit 0] Frame Select 0 Master and Slave Supported [Bit 1] Frame Select 1 Master Only [Bit 2] Frame Select 2 Master Only [Bit 3] Frame Select 3 Master Only 0 = Frame Select Disabled 1 = Frame Select Enabled

21.14.14 SSP Slot Frame Counter Register[0-7] (FRAME_CNT[0-7])—Offset 48h, Count 8, Stride 4h

The slot frame counter is typically used in Audio modes and increments the counter every two SSPSCLKs. This allows the OS to check the progress of a transfer. Since the SSP can support upto 8 slots in network mode there are 8 slot frame counters.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

FRAME_CNT[0-7]: [BAR + 0A2000h] + 48h + [0-7]*4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
FCNT_EN	RSVD0			FCNT_RST	FCNT			

Bit Range	Default & Access	Description
31	0b RW	Slot Frame Count Enable (FCNT_EN): 0 = Disable frame counter. 1 = Enable frame counter.
30:25	0b RO	RSVD0: Reserved
24	0b WO	Slot Frame Count Reset (FCNT_RST): SSP frame counter reset. Writing a 1 to this bit clears the frame counter.
23:0	000000h RO	Slot Frame Count (FCNT): SSP frame count.



21.14.15 SSP FIFO Level Register (SFIFOL)—Offset 68h

The SFIFOL register describes the current state of the RX and TX FIFOs. Not all bits of the TFL and RFL fields are used and depends on the actual hardware FIFO depth used in the instantiation of the SSP controller. This FIFO level register is meant to replace the SSSR.TFL and SSR.RFL fields.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SFIFOL: [BAR + 0A2000h] + 68h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: FFFF0000h

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
1	1	1	1	1	1	1	1	1
0	0	0	0	0	0	0	0	0
RFL				TFL				

Bit Range	Default & Access	Description
31:16	FFFFh RO	Receive FIFO Level (RFL): Number of entries minus one in Receive FIFO. Note: When the value of all 0xF's are read, the FIFO is either empty or full and the programmer should refer to the SSSR.RNE bit.
15:0	0000h RO	Transmit FIFO Level (TFL): Number of entries in Transmit FIFO. Note: When the value 0x0 is read, the FIFO is either empty or full and the programmer should refer to the SSSR.TNF bit.

21.14.16 SSP FIFO Trigger Threshold Register (SFIFOTT)—Offset 6Ch

The SFIFOTT is a register that determines when the the FIFOs will assert an interrupt for FIFO full indication. This is meant to replace the SSCR1.RFT and SSCR1.TFT legacy registers. The max size of these registers is based on the actualy FIFO depth in hardware and not the actual size of the bit field.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SFIFOTT: [BAR + 0A2000h] + 6Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RFL				TFL				

Bit Range	Default & Access	Description
31:16	0000h RW	Receive FIFO Trigger Threshold (RFT): Sets threshold level at which receive FIFO asserts interrupt. This level should be set to the desired threshold value minus 1. Notes on setting the RFT value. This applies to cases where SSP is receiving data from a device and is interfaced with a DMA channel via the hardware handshake mechanism. Please follow the following recommendations: 1. Number of bits denoted by the (DSS, EDSS) parameters in the SSP should match the SRC_TR_WIDTH programmed in the DMA channel. 2. (RFT+1) should be equal to (SRC_MSIZ). 3. Another option to 2 is to keep the BLOCK_TS in the DMA to be a multiple of (RFT+1)
15:0	0000h RW	Transmit FIFO Trigger Threshold (TFT): Sets threshold level at which transmit FIFO asserts interrupt. This level should be set to the desired threshold value minus 1.

21.14.17 SSP Control 3 Register (SSCR3)—Offset 70h

Software should only program this register if configuring the SSP in I2S/LJ mode or PCM master mode with the Tangier fixes. If neither is being enabled, SW can leave this register at the default power on value.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR3: [BAR + 0A2000h] + 70h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 0002C604h

[illegible]

Bit Range	Default & Access	Description
31:18	0b RO	RSVD0: Reserved
17	1b RW	Sync Fix Enable (SYN_FIX_EN): This is a chicken bit for enabling the synchronizer fix for clr_underrun_ssp signal. SW should preserve this bit at its default value.
16	0b RW	Master Mode Clock Enable (MST_CLK_EN): When in single slot master mode (which is the mode used for emulating I2S or LJ master mode), the SSP core can stop the clock on a Tx underflow condition, preventing the Rx side from receiving data. This bit, when set, forces the clock to run when a Tx underflow happens, thereby allowing Rx side to continue functioning while Tx side is in underflow. SW should set this bit when I2S or LJ master mode is enabled i.e. bits 0 and 1 in this register are both set or when using 1-slot PCM (SFS or LFS) master mode operation. Otherwise, SW should leave this at 0.
15	1b RW	Stretch RX Pulse (STRETCH_RX): HW uses this as a chicken bit to stretch the RX pulse for proper clock crossing between SSP and APB domains. Note this bit is not tied to any specific SSP/PCM/I2S modes. SW should preserve this bit as the default value.
14	1b RW	Stretch TX Pulse (STRETCH_TX): HW uses this as a chicken bit to stretch the TX pulse for proper clock crossing between SSP and APB domains. Note this bit is not tied to any specific SSP/PCM/I2S modes. SW should preserve this bit as the default value.



Bit Range	Default & Access	Description
13	0b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	0b RW	I2S VISA Enable (I2S_VISA_EN): Enables newly added I2S and PCM wrapper logic debug signals sent out on the VISA bus instead of the core SSP debug signals. 0 = Core SSP Debug Signals 1 = New I2S and PCM Debug Signals
10	1b RW	I2S Receive Enable (I2S_RX_EN): When set, this bit enables data to be received on both the left and right slots of I2S. Otherwise, data on the slots are ignored. HW does not signal FIFO full condition when this bit is cleared. SW can set/clear this bit dynamically when I2S mode is operational.
9	1b RW	I2S Transmit Enable (I2S_TX_EN): When set, this bit enables data to be transmitted on both the left and right slots of I2S. Otherwise, data on the slots are ignored. HW does not signal FIFO full condition when this bit is cleared. SW can set/clear this bit dynamically when I2S mode is operational.
8	0b RO	Reserved (RSVD): Reserved.
7:6	00b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RW	I2S RX Slot Swap Fix Enable (I2S_RX_SS_FIX_EN): This bit enables the Rx overrun fix in I2S or LJ modes and prevents channel swapping when Rx overrun happens. Note that this bit does not apply to any PCM modes. PCM modes still have the Rx overflow channel aliasing issue, similar to PNW/CLV. SW should set this bit only when I2S or LJ mode (slave or master) is enabled. 0 = Disable 1 = Enable
3	0b RW	I2S TX Slot Swap Fix Enable (I2S_TX_SS_FIX_EN): This bit enables the TX underflow fix in I2S or LJ modes and prevents channel swapping when TX underflow happens. Note that this bit does not apply to any PCM modes. PCM modes still have the TX underflow channel aliasing issue, similar to PNW/CLV. SW should set this bit only when I2S or LJ mode (slave or master) is enabled. 0 = Disable 1 = Enable
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	I2S Mode Enable (I2S_MODE_EN): This bit enables I2S Mode. In I2S mode, slave or master mode operation is selected by appropriately clearing/setting bit 0 in this register. SW should select I2S mode operation before enabling the SSP controller. 0 = Disabled 1 = Enabled
0	0b RW	Frame Master Enable (FRM_MST_EN): When set, this bit enables the internal frame generator logic that allows accurate frame rate generation. This bit should be set for I2S and PCM master mode operations and cleared for all other modes. SW should select the proper value in this bit before enabling SSP controller. 0 = Disabled 1 = Enabled

21.14.18 SSP Control 4 Register (SSCR4)—Offset 74h

Software should only program this register if configuring the SSP in I2S/LJ mode or PCM master mode with the Tangier fixes. If neither is being enabled, SW can leave this register at the default power on value.


Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR4: [BAR + 0A2000h] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h



Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:7	000h RW	Total Frame Period (TOT_FRM_PRD): The total frame period (both asserted and de-asserted time of frame), measured in bit clocks, that is driven in I2S, LJ and PCM master modes. This can be controlled to get the desired accuracy on frame rate. A value of 0 and a value smaller than the value programmed in SSCR5.FrameAssertedWidth are illegal
6:0	00h RO	Reserved (RSVD): Reserved.

Software should only program this register if configuring the SSP in I2S/LJ mode or PCM master mode with the Tangier fixes. If neither is being enabled, SW can leave this register at the default power on value.


Type: Memory Mapped I/O Register
(Size: 32 bits)

SSCR5: [BAR + 0A2000h] + 78h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:26	0b RO	RSVD0 : Reserved
25:1	0000000h RW	Frame Assert Width (FRM_ASRT_WIDTH) : This field controls the width of the asserted period of frame in I2S, LJ and PCM master modes. A value of 1 indicates a width of 2 bit clock period, 2 indicates a width of 3 bit clock periods, etc. The frame width is Frame Assert Width + 1.



October 2018
Document Number: 538136, Rev. 4.3



21.15 Low Power Audio DMA0 Memory Mapped IO Registers


**Table 237. Summary of Low Power Audio DMA0 Memory Mapped I/O Registers—
lpe_bridge.BAR**

Offset	Size	Register ID—Description	Default Value
0h	4	"reg_SAR_type (SAR0)—Offset 0h" on page 2939	00000000h
8h	4	"reg_DAR_type (DAR0)—Offset 8h" on page 2940	00000000h
10h	4	"reg_LL_P_type (LLP0)—Offset 10h" on page 2941	00000000h
18h	4	"reg_CTL_LO_type (CTL_LO0)—Offset 18h" on page 2942	00000000h
1Ch	4	"reg_CTL_HI_type (CTL_HI0)—Offset 1Ch" on page 2943	00000000h
20h	4	"reg_SSTAT_type (SSTAT0)—Offset 20h" on page 2944	00000000h
28h	4	"reg_DSTAT_type (DSTAT0)—Offset 28h" on page 2945	00000000h
30h	4	"reg_SSTATAR_type (SSTATAR0)—Offset 30h" on page 2945	00000000h
38h	4	"reg_DSTATAR_type (DSTATAR0)—Offset 38h" on page 2946	00000000h
40h	4	"reg_CFG_LO_type (CFG_LO0)—Offset 40h" on page 2946	00000203h
44h	4	"reg_CFG_HI_type (CFG_HI0)—Offset 44h" on page 2948	00000000h
48h	4	"reg_SGR_type (SGR0)—Offset 48h" on page 2949	00000000h
50h	4	"reg_DSR_type (DSR0)—Offset 50h" on page 2950	00000000h
58h	4	"reg_SAR_type (SAR1)—Offset 58h" on page 2950	00000000h
60h	4	"reg_DAR_type (DAR1)—Offset 60h" on page 2951	00000000h
68h	4	"reg_LL_P_type (LLP1)—Offset 68h" on page 2952	00000000h
70h	4	"reg_CTL_LO_type (CTL_LO1)—Offset 70h" on page 2953	00000000h
74h	4	"reg_CTL_HI_type (CTL_HI1)—Offset 74h" on page 2954	00000000h
78h	4	"reg_SSTAT_type (SSTAT1)—Offset 78h" on page 2955	00000000h
80h	4	"reg_DSTAT_type (DSTAT1)—Offset 80h" on page 2956	00000000h
88h	4	"reg_SSTATAR_type (SSTATAR1)—Offset 88h" on page 2956	00000000h
90h	4	"reg_DSTATAR_type (DSTATAR1)—Offset 90h" on page 2957	00000000h
98h	4	"reg_CFG_LO_type (CFG_LO1)—Offset 98h" on page 2957	00000203h
9Ch	4	"reg_CFG_HI_type (CFG_HI1)—Offset 9Ch" on page 2959	00000000h
A0h	4	"reg_SGR_type (SGR1)—Offset A0h" on page 2960	00000000h
A8h	4	"reg_DSR_type (DSR1)—Offset A8h" on page 2961	00000000h
B0h	4	"reg_SAR_type (SAR2)—Offset B0h" on page 2961	00000000h
B8h	4	"reg_DAR_type (DAR2)—Offset B8h" on page 2962	00000000h
C0h	4	"reg_LL_P_type (LLP2)—Offset C0h" on page 2963	00000000h
C8h	4	"reg_CTL_LO_type (CTL_LO2)—Offset C8h" on page 2964	00000000h
CCh	4	"reg_CTL_HI_type (CTL_HI2)—Offset CCh" on page 2965	00000000h
D0h	4	"reg_SSTAT_type (SSTAT2)—Offset D0h" on page 2966	00000000h
D8h	4	"reg_DSTAT_type (DSTAT2)—Offset D8h" on page 2967	00000000h
E0h	4	"reg_SSTATAR_type (SSTATAR2)—Offset E0h" on page 2967	00000000h
E8h	4	"reg_DSTATAR_type (DSTATAR2)—Offset E8h" on page 2968	00000000h



**Table 237. Summary of Low Power Audio DMA0 Memory Mapped I/O Registers—
lpe_bridge.BAR (Continued)**

Offset	Size	Register ID—Description	Default Value
F0h	4	"reg_CFG_LO_type (CFG_LO2)—Offset F0h" on page 2968	00000203h
F4h	4	"reg_CFG_HI_type (CFG_HI2)—Offset F4h" on page 2970	00000000h
F8h	4	"reg_SGR_type (SGR2)—Offset F8h" on page 2971	00000000h
100h	4	"reg_DSR_type (DSR2)—Offset 100h" on page 2972	00000000h
108h	4	"reg_SAR_type (SAR3)—Offset 108h" on page 2972	00000000h
110h	4	"reg_DAR_type (DAR3)—Offset 110h" on page 2973	00000000h
118h	4	"reg_LL_P_type (LLP3)—Offset 118h" on page 2974	00000000h
120h	4	"reg_CTL_LO_type (CTL_LO3)—Offset 120h" on page 2975	00000000h
124h	4	"reg_CTL_HI_type (CTL_HI3)—Offset 124h" on page 2976	00000000h
128h	4	"reg_SSTAT_type (SSTAT3)—Offset 128h" on page 2977	00000000h
130h	4	"reg_DSTAT_type (DSTAT3)—Offset 130h" on page 2978	00000000h
138h	4	"reg_SSTATAR_type (SSTATAR3)—Offset 138h" on page 2978	00000000h
140h	4	"reg_DSTATAR_type (DSTATAR3)—Offset 140h" on page 2979	00000000h
148h	4	"reg_CFG_LO_type (CFG_LO3)—Offset 148h" on page 2979	00000203h
14Ch	4	"reg_CFG_HI_type (CFG_HI3)—Offset 14Ch" on page 2981	00000000h
150h	4	"reg_SGR_type (SGR3)—Offset 150h" on page 2982	00000000h
158h	4	"reg_DSR_type (DSR3)—Offset 158h" on page 2983	00000000h
160h	4	"reg_SAR_type (SAR4)—Offset 160h" on page 2983	00000000h
168h	4	"reg_DAR_type (DAR4)—Offset 168h" on page 2984	00000000h
170h	4	"reg_LL_P_type (LLP4)—Offset 170h" on page 2985	00000000h
178h	4	"reg_CTL_LO_type (CTL_LO4)—Offset 178h" on page 2986	00000000h
17Ch	4	"reg_CTL_HI_type (CTL_HI4)—Offset 17Ch" on page 2987	00000000h
180h	4	"reg_SSTAT_type (SSTAT4)—Offset 180h" on page 2988	00000000h
188h	4	"reg_DSTAT_type (DSTAT4)—Offset 188h" on page 2989	00000000h
190h	4	"reg_SSTATAR_type (SSTATAR4)—Offset 190h" on page 2989	00000000h
198h	4	"reg_DSTATAR_type (DSTATAR4)—Offset 198h" on page 2990	00000000h
1A0h	4	"reg_CFG_LO_type (CFG_LO4)—Offset 1A0h" on page 2990	00000203h
1A4h	4	"reg_CFG_HI_type (CFG_HI4)—Offset 1A4h" on page 2992	00000000h
1A8h	4	"reg_SGR_type (SGR4)—Offset 1A8h" on page 2993	00000000h
1B0h	4	"reg_DSR_type (DSR4)—Offset 1B0h" on page 2994	00000000h
1B8h	4	"reg_SAR_type (SAR5)—Offset 1B8h" on page 2994	00000000h
1C0h	4	"reg_DAR_type (DAR5)—Offset 1C0h" on page 2995	00000000h
1C8h	4	"reg_LL_P_type (LLP5)—Offset 1C8h" on page 2996	00000000h
1D0h	4	"reg_CTL_LO_type (CTL_LO5)—Offset 1D0h" on page 2997	00000000h
1D4h	4	"reg_CTL_HI_type (CTL_HI5)—Offset 1D4h" on page 2998	00000000h
1D8h	4	"reg_SSTAT_type (SSTAT5)—Offset 1D8h" on page 2999	00000000h
1E0h	4	"reg_DSTAT_type (DSTAT5)—Offset 1E0h" on page 3000	00000000h
1E8h	4	"reg_SSTATAR_type (SSTATAR5)—Offset 1E8h" on page 3000	00000000h



**Table 237. Summary of Low Power Audio DMA0 Memory Mapped I/O Registers—
lpe_bridge.BAR (Continued)**

Offset	Size	Register ID—Description	Default Value
1F0h	4	"reg_DSTATAR_type (DSTATAR5)—Offset 1F0h" on page 3001	00000000h
1F8h	4	"reg_CFG_LO_type (CFG_LO5)—Offset 1F8h" on page 3001	00000203h
1FCh	4	"reg_CFG_HI_type (CFG_HI5)—Offset 1FCh" on page 3003	00000000h
200h	4	"reg_SGR_type (SGR5)—Offset 200h" on page 3004	00000000h
208h	4	"reg_DSR_type (DSR5)—Offset 208h" on page 3005	00000000h
210h	4	"reg_SAR_type (SAR6)—Offset 210h" on page 3005	00000000h
218h	4	"reg_DAR_type (DAR6)—Offset 218h" on page 3006	00000000h
220h	4	"reg_LL_P_type (LLP6)—Offset 220h" on page 3007	00000000h
228h	4	"reg_CTL_LO_type (CTL_LO6)—Offset 228h" on page 3008	00000000h
22Ch	4	"reg_CTL_HI_type (CTL_HI6)—Offset 22Ch" on page 3009	00000000h
230h	4	"reg_SSTAT_type (SSTAT6)—Offset 230h" on page 3010	00000000h
238h	4	"reg_DSTAT_type (DSTAT6)—Offset 238h" on page 3011	00000000h
240h	4	"reg_SSTATAR_type (SSTATAR6)—Offset 240h" on page 3011	00000000h
248h	4	"reg_DSTATAR_type (DSTATAR6)—Offset 248h" on page 3012	00000000h
250h	4	"reg_CFG_LO_type (CFG_LO6)—Offset 250h" on page 3012	00000203h
254h	4	"reg_CFG_HI_type (CFG_HI6)—Offset 254h" on page 3014	00000000h
258h	4	"reg_SGR_type (SGR6)—Offset 258h" on page 3015	00000000h
260h	4	"reg_DSR_type (DSR6)—Offset 260h" on page 3016	00000000h
268h	4	"reg_SAR_type (SAR7)—Offset 268h" on page 3016	00000000h
270h	4	"reg_DAR_type (DAR7)—Offset 270h" on page 3017	00000000h
278h	4	"reg_LL_P_type (LLP7)—Offset 278h" on page 3018	00000000h
280h	4	"reg_CTL_LO_type (CTL_LO7)—Offset 280h" on page 3019	00000000h
284h	4	"reg_CTL_HI_type (CTL_HI7)—Offset 284h" on page 3020	00000000h
288h	4	"reg_SSTAT_type (SSTAT7)—Offset 288h" on page 3021	00000000h
290h	4	"reg_DSTAT_type (DSTAT7)—Offset 290h" on page 3022	00000000h
298h	4	"reg_SSTATAR_type (SSTATAR7)—Offset 298h" on page 3022	00000000h
2A0h	4	"reg_DSTATAR_type (DSTATAR7)—Offset 2A0h" on page 3023	00000000h
2A8h	4	"reg_CFG_LO_type (CFG_LO7)—Offset 2A8h" on page 3023	00000203h
2ACh	4	"reg_CFG_HI_type (CFG_HI7)—Offset 2ACh" on page 3025	00000000h
2B0h	4	"reg_SGR_type (SGR7)—Offset 2B0h" on page 3026	00000000h
2B8h	4	"reg_DSR_type (DSR7)—Offset 2B8h" on page 3027	00000000h
2C0h	4	"reg_Raw_type (RawTfr)—Offset 2C0h" on page 3027	00000000h
2C8h	4	"reg_Raw_type (RawBlock)—Offset 2C8h" on page 3028	00000000h
2D0h	4	"reg_Raw_type (RawSrcTran)—Offset 2D0h" on page 3029	00000000h
2D8h	4	"reg_Raw_type (RawDstTran)—Offset 2D8h" on page 3029	00000000h
2E0h	4	"reg_Raw_type (RawErr)—Offset 2E0h" on page 3030	00000000h
2E8h	4	"reg_Status_type (StatusTfr)—Offset 2E8h" on page 3030	00000000h
2F0h	4	"reg_Status_type (StatusBlock)—Offset 2F0h" on page 3031	00000000h



**Table 237. Summary of Low Power Audio DMA0 Memory Mapped I/O Registers—
lpe_bridge.BAR (Continued)**

Offset	Size	Register ID—Description	Default Value
2F8h	4	"reg_Status_type (StatusSrcTran)—Offset 2F8h" on page 3032	00000000h
300h	4	"reg_Status_type (StatusDstTran)—Offset 300h" on page 3032	00000000h
308h	4	"reg_Status_type (StatusErr)—Offset 308h" on page 3033	00000000h
310h	4	"reg_Mask_type (MaskTfr)—Offset 310h" on page 3033	00000000h
318h	4	"reg_Mask_type (MaskBlock)—Offset 318h" on page 3034	00000000h
320h	4	"reg_Mask_type (MaskSrcTran)—Offset 320h" on page 3035	00000000h
328h	4	"reg_Mask_type (MaskDstTran)—Offset 328h" on page 3036	00000000h
330h	4	"reg_Mask_type (MaskErr)—Offset 330h" on page 3037	00000000h
338h	4	"reg_Clear_type (ClearTfr)—Offset 338h" on page 3037	00000000h
340h	4	"reg_Clear_type (ClearBlock)—Offset 340h" on page 3038	00000000h
348h	4	"reg_Clear_type (ClearSrcTran)—Offset 348h" on page 3039	00000000h
350h	4	"reg_Clear_type (ClearDstTran)—Offset 350h" on page 3039	00000000h
358h	4	"reg_Clear_type (ClearErr)—Offset 358h" on page 3040	00000000h
360h	4	"reg_StatusInt_type (StatusInt)—Offset 360h" on page 3040	00000000h
398h	4	"reg_DmaCfgReg_type (DmaCfgReg)—Offset 398h" on page 3041	00000000h
3A0h	4	"reg_ChEnReg_type (ChEnReg)—Offset 3A0h" on page 3041	00000000h
3B8h	4	"reg_CLASS_PRIORITY0_LO_type (ClassPriority0_LO)—Offset 3B8h" on page 3042	00000000h
3BCh	4	"reg_CLASS_PRIORITY0_HI_type (ClassPriority0_HI)—Offset 3BCh" on page 3043	00000000h
3C0h	4	"reg_CLASS_PRIORITY1_LO_type (ClassPriority1_LO)—Offset 3C0h" on page 3043	00000000h
3C4h	4	"reg_CLASS_PRIORITY1_HI_type (ClassPriority1_HI)—Offset 3C4h" on page 3044	00000000h
400h	4	"reg_FIFO_PARTITION0_LO_type (FifoPartition0_LO)—Offset 400h" on page 3044	00000000h
404h	4	"reg_FIFO_PARTITION0_HI_type (FifoPartition0_HI)—Offset 404h" on page 3045	00000000h
408h	4	"reg_FIFO_PARTITION1_LO_type (FifoPartition1_LO)—Offset 408h" on page 3046	00000000h
40Ch	4	"reg_FIFO_PARTITION1_HI_type (FifoPartition1_HI)—Offset 40Ch" on page 3046	00000000h
410h	4	"reg_SAI_Error_type (SAI_ERR)—Offset 410h" on page 3047	00000000h
418h	4	"reg_GLOBAL_CFG_type (GLOBAL_CFG)—Offset 418h" on page 3047	00000000h

21.15.1 reg_SAR_type (SAR0)—Offset 0h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR0: [BAR + 98000h] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	SAR : Current Source Address of DMA transfer. Updated after each source transfer. The SINC field in the CTL_LO[n]: Control Register determines whether the address increments or is left unchanged on every source transfer throughout the block transfer. When the channel is enabled (i.e. CH_EN is 1), the read back value will reflect the updated source transfer addresses. However, when the channel is disabled, the original programmed value will be reflected when reading this register. It's important to notice the following: 1. Once the block transfer is in progress (i.e. when channel is enabled), the read-back value correlates with the OCP Read Address that one would see in an OCP tracker. 2. If the read to this register comes during a block transfer, the LAST DMA Read address sent on the OCP before the register read is what's reflected in the read-back value. 3. If the last DMA read was a burst read (i.e. burst length) 1), the read-back value reflects the first address of the burst read since this is what gets sent on the OCP fabric. 4. If the read to the register occurred after the whole block got transferred, then the channel gets disabled and the returned value would be the original programmed value. 5. Since the read-back value is OCP based, only DW aligned addresses will be reflected (i.e. OCP Byte-Enable values would not be reflected) 6. Based on the above remarks, this value should be used as pseudo DMA read progress indicator when the channel is enabled and not an absolute one. Decrementing addresses are not supported

21.15.2 reg_DAR_type (DAR0)—Offset 8h

The starting destination address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the destination address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DAR0: [BAR + 98000h] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

DAR



21.15.4 reg_CTL_LO_type (CTL_LO0)—Offset 18h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO0: [BAR + 98000h] + 18h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0																																			
RSVD				LLP_SRC_EN				LLP_DST_EN				RSVD1				TT_FC				RSVD2				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZE				DEST_MSIZE				SINC				RSVD3				DINC				RSVD4				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZE: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZE: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.15.5 reg_CTL_HI_type (CTL_HI0)—Offset 1Ch

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI0: [BAR + 98000h] + 1Ch


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.15.6 reg_SSTAT_type (SSTAT0)—Offset 20h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT0: [BAR + 98000h] + 20h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.15.7 reg_DSTAT_type (DSTAT0)—Offset 28h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT0: [BAR + 98000h] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.15.8 reg_SSTATAR_type (SSTATAR0)—Offset 30h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR0: [BAR + 98000h] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.

21.15.9 reg_DSTATAR_type (DSTATAR0)—Offset 38h

Access Method

DSTATAR0: [BAR + 98000h] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RW	DSTATAR: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.

21.15.10 reg_CFG_LO_type (CFG_LO0)—Offset 40h


Access Method

CFG_LO0: [BAR + 98000h] + 40h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



Intel Atom® Processor E3800 Product Family
Datasheet
2947



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.15.11 reg_CFG_HI_type (CFG_HI0)—Offset 44h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


CFG_HI0: [BAR + 98000h] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0															
0				0				0				0				0				0				0				0				0															
DST_PER_EXT				SRC_PER_EXT				WR_ISSUE_THD																RD_ISSUE_THD																DST_PER				SRC_PER			



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2 \wedge \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2 \wedge \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.15.12 reg_SGR_type (SGR0)—Offset 48h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR0: [BAR + 98000h] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.15.13 reg_DSR_type (DSR0)—Offset 50h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR0: [BAR + 98000h] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.15.14 reg_SAR_type (SAR1)—Offset 58h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR1: [BAR + 98000h] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Intel Atom® Processor E3800 Product Family
Datasheet
2951



21.15.17 reg_CTL_LO_type (CTL_LO1)—Offset 70h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO1: [BAR + 98000h] + 70h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0											
RSVD				LLP_SRC_EN				RSVD1				TT_FC				RSVD2				SRC_MSIZ				DEST_MSIZ				SINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			
				LLP_DST_EN												DST_SCATTER_EN												SRC_GATHER_EN															

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.15.18 reg_CTL_HI_type (CTL_HI1)—Offset 74h

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI1: [BAR + 98000h] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HIin, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.15.19 reg_SSTAT_type (SSTAT1)—Offset 78h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT1: [BAR + 98000h] + 78h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.15.20 reg_DSTAT_type (DSTAT1)—Offset 80h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT1: [BAR + 98000h] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.15.21 reg_SSTATAR_type (SSTATAR1)—Offset 88h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR1: [BAR + 98000h] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

			31	28				24				20				16				12				8				4				0			
			0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
			SSTATAR																																
Bit Range	Default & Access	Description																																	
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.																																	

21.15.22 req_DSTATAR_type (DSTATAR1)—Offset 90h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR1: [BAR + 98000h] + 90h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

	31	28	24	20	16	12	8	4	0
	0	0	0	0	0	0	0	0	0
	DSTATAR								

Bit Range	Default & Access	Description
31:0	0h RW	DSTATAR: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.

21.15.23 reg_CFG_LO_type (CFG_LO1)—Offset 98h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO1: [BAR + 98000h] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.15.24 reg_CFG_HI_type (CFG_HI1)—Offset 9Ch

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


CFG_HI1: [BAR + 98000h] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31		28		24		20		16		12		8		4		0			
0		0		0		0		0		0		0		0		0			
DST_PER_EXT		SRC_PER_EXT		WR_ISSUE_THD						RD_ISSUE_THD						DST_PER		SRC_PER	



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2^{\wedge} \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2^{\wedge} \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.15.25 reg_SGR_type (SGR1)—Offset A0h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR1: [BAR + 98000h] + A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SAR								

Bit Range	Default & Access	Description
31:0	0h RW	SAR: Current Source Address of DMA transfer. Updated after each source transfer. The SINC field in the CTL_LO[n]: Control Register determines whether the address increments or is left unchanged on every source transfer throughout the block transfer. When the channel is enabled (i.e. CH_EN is 1), the read back value will reflect the updated source transfer addresses. However, when the channel is disabled, the original programmed value will be reflected when reading this register. It's important to notice the following: 1. Once the block transfer is in progress (i.e. when channel is enabled), the read-back value correlates with the OCP Read Address that one would see in an OCP tracker. 2. If the read to this register comes during a block transfer, the LAST DMA Read address sent on the OCP before the register read is what's reflected in the read-back value. 3. If the last DMA read was a burst read (i.e. burst length) 1), the read-back value reflects the first address of the burst read since this is what gets sent on the OCP fabric. 4. If the read to the register occurred after the whole block got transferred, then the channel gets disabled and the returned value would be the original programmed value. 5. Since the read-back value is OCP based, only DW aligned addresses will be reflected (i.e. OCP Byte-Enable values would not be reflected) 6. Based on the above remarks, this value should be used as pseudo DMA read progress indicator when the channel is enabled and not an absolute one. Decrementing addresses are not supported

21.15.28 reg_DAR_type (DAR2)—Offset B8h

The starting destination address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the destination address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


DAR2: [BAR + 98000h] + B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

	31		28		24		20		16		12		8		4		0
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
DAR																	



21.15.30 reg_CTL_LO_type (CTL_LO2)—Offset C8h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO2: [BAR + 98000h] + C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0																																			
RSVD				LLP_SRC_EN				LLP_DST_EN				RSVD1				TT_FC				RSVD2				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZE				DEST_MSIZE				SINC				RSVD3				DINC				RSVD4				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZE: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZE: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.15.31 reg_CTL_HI_type (CTL_HI2)—Offset CCh

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI2: [BAR + 98000h] + CCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.15.32 reg_SSTAT_type (SSTAT2)—Offset D0h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT2: [BAR + 98000h] + D0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.15.33 reg_DSTAT_type (DSTAT2)—Offset D8h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT2: [BAR + 98000h] + D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.15.34 reg_SSTATAR_type (SSTATAR2)—Offset E0h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR2: [BAR + 98000h] + E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.

21.15.35 reg_DSTATAR_type (DSTATAR2)—Offset E8h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR2: [BAR + 98000h] + E8h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RW	DSTATAR: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.

21.15.36 reg_CFG_LO_type (CFG_LO2)—Offset F0h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO2: [BAR + 98000h] + F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



Intel Atom® Processor E3800 Product Family
Datasheet
2969



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.15.37 reg_CFG_HI_type (CFG_HI2)—Offset F4h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI2: [BAR + 98000h] + F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0				0				0				0				0				0				0				0				0			
DST_PER_EXT				SRC_PER_EXT				WR_ISSUE_THD								RD_ISSUE_THD								DST_PER				SRC_PER							



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2 \wedge \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2 \wedge \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.15.38 reg_SGR_type (SGR2)—Offset F8h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR2: [BAR + 98000h] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.15.39 reg_DSR_type (DSR2)—Offset 100h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR2: [BAR + 98000h] + 100h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.15.40 reg_SAR_type (SAR3)—Offset 108h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR3: [BAR + 98000h] + 108h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Intel Atom® Processor E3800 Product Family
Datasheet
2973



Bit Range	Default & Access	Description
31:0	0h RW	DAR: Current Destination Address of DMA transfer. Updated after each destination transfer. The DINC field in the CTL_LO[n]: Control Register determines whether the address increments or is left unchanged on every destination transfer throughout the block transfer. When the channel is enabled (i.e. CH_EN is 1), the read back value will reflect the updated destination transfer addresses. However, when the channel is disabled, the original programmed value will be reflected when reading this register. It's important to notice the following: 1. Once the block transfer is in progress (i.e. when channel is enabled), the read-back value correlates with the OCP Write Address that one would see in an OCP tracker. 2. If the read to this register comes during a block transfer, the LAST DMA Write address sent on the OCP before the register read is what's reflected in the read-back value. 3. If the last DMA write was a burst write (i.e. burst length) 1), the read-back value reflects the first address of the burst write since this is what gets sent on the OCP fabric. 4. If the read to the register occurred after the whole block got transferred, then the channel gets disabled and the returned value would be the original programmed value. 5. Since the read-back value is OCP based, only DW aligned addresses will be reflected (i.e. OCP Byte-Enable values would not be reflected) 6. Based on the above remarks, this value should be used as pseudo DMA write progress indicator when the channel is enabled and not an absolute one. Decrementing addresses are not supported

21.15.42 reg_LLQ_type (LLP3)—Offset 118h

Note: You need to program this register to point to the first Linked List Item (LLI) in memory prior to enabling the channel if block chaining is enabled The LLP register has two functions: The logical result of the equation $LLP.LOC \neq 0$ is used to set up the type of DMA transfer-single or multi-block. Table shows how the method of updating the channel registers is a function of $LLP.LOC \neq 0$. If $LLP.LOC$ is set to 0x0, then transfers using linked lists are not enabled. This register must be programmed prior to enabling the channel in order to set up the transfer type. $LLP.LOC \neq 0$ contains the pointer to the next LLI for block chaining using linked lists, The LLPx register can also point to the address where write-back of the control and source/destination status information occur after block completion.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

LLP3: [BAR + 98000h] + 118h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LOC								RSVD2

Bit Range	Default & Access	Description
31:2	00000000h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled. Note that the two LSBs of the starting address are not stored because the address is assumed to be aligned to a 32-bit boundary. LLI accesses are always 32-bit accesses and cannot be changed or programmed to anything other than 32-bit.
1:0	0h RO	RSVD2: Reserved



21.15.43 reg_CTL_LO_type (CTL_LO3)—Offset 120h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO3: [BAR + 98000h] + 120h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD	LLP_SRC_EN	LLP_DST_EN	RSVD1	TT_FC	RSVD2	DST_SCATTER_EN	SRC_GATHER_EN	SRC_MSIZ
						DEST_MSIZ	SINC	RSVD3
						DINC	RSVD4	SRC_TR_WIDTH
								DST_TR_WIDTH
								INT_EN

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.15.44 reg_CTL_HI_type (CTL_HI3)—Offset 124h

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI3: [BAR + 98000h] + 124h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.15.45 reg_SSTAT_type (SSTAT3)—Offset 128h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT3: [BAR + 98000h] + 128h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.15.46 reg_DSTAT_type (DSTAT3)—Offset 130h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT3: [BAR + 98000h] + 130h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.15.47 reg_SSTATAR_type (SSTATAR3)—Offset 138h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR3: [BAR + 98000h] + 138h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

			31	28				24				20				16				12				8				4				0			
			0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
			SSTATAR																																
Bit Range	Default & Access	Description																																	
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.																																	

21.15.48 reg_DSTATAR_type (DSTATAR3)—Offset 140h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR3: [BAR + 98000h] + 140h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

			31	28				24				20				16				12				8				4				0	
			0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
			DSTATn																														
Bit Range	Default & Access	Description																															
31:0	0h RW	DSTATn: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.																															

21.15.49 reg_CFG_LO_type (CFG_LO3)—Offset 148h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO3: [BAR + 98000h] + 148h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



31		28				24				20				16				12				8				4				0																																									
0		0		0		0		0		0		0		0		0		0		0		1		0		0		0		0		0		0		0		1		1																															
RELOAD_DST		RELOAD_SRC		Reserved_29_22																								SRC_OPT_BL		DST_OPT_BL		SRC_HS_POL		DST_HS_POL		WR_CTLHI_SNP		WR_STAT_SNP		RD_STAT_SNP		RD_LL_P_SNP		WR_SNP		RD_SNP		Reserved_11		CH_DRAIN		FIFO_EMPTY		CH_SUSP		SS_UPD_EN		DS_UPD_EN		CTL_HI_UPD_EN		RSVD_4_4		HSHAKE_NP_WR		ALL_NP_WR		SRC_BURST_ALIGN		DST_BURST_ALIGN	

Bit Range	Default & Access	Description
31	0h RW	RELOAD_DST: Automatic Destination Reload. The DARN register can be automatically reloaded from its initial value at the end of every block for multi-block transfers. A new block transfer is then initiated.
30	0h RW	RELOAD_SRC: Automatic Source Reload. The SARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers. A new block transfer is then initiated.
29:22	00h RO	Reserved_29_22: Reserved
21	0h RW	SRC_OPT_BL: Optimize Source Burst Length : 0 = Writes will use only BL=1 or BL=(2 ^ SRC_MSIZ) 1 = Writes will use (1 (= BL (= (2 ^ SRC_MSIZ))) *** This bit should be set to (0) if Source HW-Handshake is enabled
20	0h RW	DST_OPT_BL: Optimize Destination Burst Length : 0 = Writes will use only BL=1 or BL=(2 ^ DST_MSIZ) 1 = Writes will use (1 (= BL (= (2 ^ DST_MSIZ))) *** This bit should be set to (0) if Destination HW-Handshake is enabled
19	0h RW	SRC_HS_POL: Source Handshaking Interface Polarity. 0 = Active high 1 = Active low
18	0h RW	DST_HS_POL: Destination Handshaking Interface Polarity. 0 = Active high 1 = Active low
17	0h RW	WR_CTLHI_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Write Port for writing back the CTL_HI register values
16	0h RW	WR_STAT_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Write Port for writing back the SSTAT/DSTAT register values
15	0h RW	RD_STAT_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Read Port for reading SSTAT/DSTAT register values
14	0h RW	RD_LL_P_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Read Port for reading LLP Descriptors
13	0h RW	WR_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Write Port
12	0h RW	RD_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Read Port
11	0b RO	Reserved_11: Reserved
10	0b RW	CH_DRAIN: Forces channel FIFO to drain while in suspension. This bit has effect only when CH_SUSPEND is asserted
9	1b RO	FIFO_EMPTY: Indicates if there is data left in the channel FIFO. Can be used in conjunction with CFGx.CH_SUSP to cleanly disable a channel. 1 = Channel FIFO empty 0 = Channel FIFO not empty



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.15.50 reg_CFG_HI_type (CFG_HI3)—Offset 14Ch

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI3: [BAR + 98000h] + 14Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31			28				24				20				16				12				8				4				0			
0			0				0				0				0				0				0				0				0			
DST_PER_EXT			SRC_PER_EXT				WR_ISSUE_THD								RD_ISSUE_THD								DST_PER				SRC_PER							



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2^{\wedge} \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2^{\wedge} \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.15.51 reg_SGR_type (SGR3)—Offset 150h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR3: [BAR + 98000h] + 150h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.15.52 reg_DSR_type (DSR3)—Offset 158h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR3: [BAR + 98000h] + 158h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.15.53 reg_SAR_type (SAR4)—Offset 160h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR4: [BAR + 98000h] + 160h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Access Method

DAR4: [BAR + 98000h] + 168h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

DAR



21.15.56 reg_CTL_LO_type (CTL_LO4)—Offset 178h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO4: [BAR + 98000h] + 178h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0																																			
RSVD				LLP_SRC_EN				LLP_DST_EN				RSVD1				TT_FC				RSVD2				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZE				DEST_MSIZE				SINC				RSVD3				DINC				RSVD4				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZE: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZE: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.15.57 reg_CTL_HI_type (CTL_HI4)—Offset 17Ch

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI4: [BAR + 98000h] + 17Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.15.58 reg_SSTAT_type (SSTAT4)—Offset 180h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT4: [BAR + 98000h] + 180h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.15.59 reg_DSTAT_type (DSTAT4)—Offset 188h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT4: [BAR + 98000h] + 188h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.15.60 reg_SSTATAR_type (SSTATAR4)—Offset 190h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR4: [BAR + 98000h] + 190h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.

21.15.61 reg_DSTATAR_type (DSTATAR4)—Offset 198h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR4: [BAR + 98000h] + 198h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RW	DSTATAR: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.

21.15.62 reg_CFG_LO_type (CFG_LO4)—Offset 1A0h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO4: [BAR + 98000h] + 1A0h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



Intel Atom® Processor E3800 Product Family
Datasheet
2991



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.15.63 reg_CFG_HI_type (CFG_HI4)—Offset 1A4h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI4: [BAR + 98000h] + 1A4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31		28				24				20				16				12				8				4				0			
0 0 0 0 0		0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0							
DST_PER_EXT		SRC_PER_EXT		WR_ISSUE_THD										RD_ISSUE_THD										DST_PER				SRC_PER					



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2 \wedge \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2 \wedge \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.15.64 reg_SGR_type (SGR4)—Offset 1A8h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR4: [BAR + 98000h] + 1A8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.15.65 reg_DSR_type (DSR4)—Offset 1B0h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR4: [BAR + 98000h] + 1B0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.15.66 reg_SAR_type (SAR5)—Offset 1B8h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR5: [BAR + 98000h] + 1B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Intel Atom® Processor E3800 Product Family
Datasheet
2995



21.15.69 reg_CTL_LO_type (CTL_LO5)—Offset 1D0h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO5: [BAR + 98000h] + 1D0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0											
RSVD				LLP_SRC_EN				RSVD1				TT_FC				RSVD2				SRC_MSIZ				DEST_MSIZ				SINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			
				LLP_DST_EN												DST_SCATTER_EN												SRC_GATHER_EN															

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.15.70 reg_CTL_HI_type (CTL_HI5)—Offset 1D4h

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI5: [BAR + 98000h] + 1D4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HIin, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.15.71 reg_SSTAT_type (SSTAT5)—Offset 1D8h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT5: [BAR + 98000h] + 1D8h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.15.72 reg_DSTAT_type (DSTAT5)—Offset 1E0h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT5: [BAR + 98000h] + 1E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.15.73 reg_SSTATAR_type (SSTATAR5)—Offset 1E8h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR5: [BAR + 98000h] + 1E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

	31	28	24	20	16	12	8	4	0
	0	0	0	0	0	0	0	0	0
	SSTATAR								
Bit Range	Default & Access	Description							
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.							

21.15.74 reg_DSTATAR_type (DSTATAR5)—Offset 1F0h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR5: [BAR + 98000h] + 1F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

			31	28				24				20				16				12				8				4				0		
			0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
			DSTATn																															
Bit Range	Default & Access	Description																																
31:0	0h RW	DSTATn: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.																																

21.15.75 reg_CFG_LO_type (CFG_LO5)—Offset 1F8h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO5: [BAR + 98000h] + 1F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.15.76 reg_CFG_HI_type (CFG_HI5)—Offset 1FCh

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI5: [BAR + 98000h] + 1FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31			28				24				20				16				12				8				4				0			
0			0				0				0				0				0				0				0				0			
DST_PER_EXT			SRC_PER_EXT				WR_ISSUE_THD								RD_ISSUE_THD								DST_PER				SRC_PER							



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2^{\wedge} \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2^{\wedge} \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.15.77 reg_SGR_type (SGR5)—Offset 200h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR5: [BAR + 98000h] + 200h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.15.78 reg_DSR_type (DSR5)—Offset 208h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR5: [BAR + 98000h] + 208h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.15.79 reg_SAR_type (SAR6)—Offset 210h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR6: [BAR + 98000h] + 210h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



21.15.82 reg_CTL_LO_type (CTL_LO6)—Offset 228h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO6: [BAR + 98000h] + 228h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0																																			
RSVD				LLP_SRC_EN				LLP_DST_EN				RSVD1				TT_FC				RSVD2				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZ				DEST_MSIZ				SINC				RSVD3				DINC				RSVD4				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.15.83 reg_CTL_HI_type (CTL_HI6)—Offset 22Ch

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI6: [BAR + 98000h] + 22Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.15.84 reg_SSTAT_type (SSTAT6)—Offset 230h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT6: [BAR + 98000h] + 230h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.15.85 reg_DSTAT_type (DSTAT6)—Offset 238h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT6: [BAR + 98000h] + 238h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.15.86 reg_SSTATAR_type (SSTATAR6)—Offset 240h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR6: [BAR + 98000h] + 240h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.

21.15.87 reg_DSTATAR_type (DSTATAR6)—Offset 248h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR6: [BAR + 98000h] + 248h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RW	DSTATAR: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.

21.15.88 reg_CFG_LO_type (CFG_LO6)—Offset 250h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO6: [BAR + 98000h] + 250h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



Intel Atom® Processor E3800 Product Family
Datasheet
3013



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.15.89 reg_CFG_HI_type (CFG_HI6)—Offset 254h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI6: [BAR + 98000h] + 254h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31		28				24				20				16				12				8				4				0			
0 0 0 0 0		0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0							
DST_PER_EXT		SRC_PER_EXT		WR_ISSUE_THD										RD_ISSUE_THD										DST_PER				SRC_PER					



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2 \wedge \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2 \wedge \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.15.90 reg_SGR_type (SGR6)—Offset 258h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


SGR6: [BAR + 98000h] + 258h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.15.91 reg_DSR_type (DSR6)—Offset 260h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR6: [BAR + 98000h] + 260h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.15.92 reg_SAR_type (SAR7)—Offset 268h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR7: [BAR + 98000h] + 268h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Intel Atom® Processor E3800 Product Family
Datasheet
3017



Bit Range	Default & Access	Description
31:0	0h RW	DAR: Current Destination Address of DMA transfer. Updated after each destination transfer. The DINC field in the CTL_LO[n]: Control Register determines whether the address increments or is left unchanged on every destination transfer throughout the block transfer. When the channel is enabled (i.e. CH_EN is 1), the read back value will reflect the updated destination transfer addresses. However, when the channel is disabled, the original programmed value will be reflected when reading this register. It's important to notice the following: 1. Once the block transfer is in progress (i.e. when channel is enabled), the read-back value correlates with the OCP Write Address that one would see in an OCP tracker. 2. If the read to this register comes during a block transfer, the LAST DMA Write address sent on the OCP before the register read is what's reflected in the read-back value. 3. If the last DMA write was a burst write (i.e. burst length) 1), the read-back value reflects the first address of the burst write since this is what gets sent on the OCP fabric. 4. If the read to the register occurred after the whole block got transferred, then the channel gets disabled and the returned value would be the original programmed value. 5. Since the read-back value is OCP based, only DW aligned addresses will be reflected (i.e. OCP Byte-Enable values would not be reflected) 6. Based on the above remarks, this value should be used as pseudo DMA write progress indicator when the channel is enabled and not an absolute one. Decrementing addresses are not supported

21.15.94 reg_LLp_type (LLP7)—Offset 278h

Note: You need to program this register to point to the first Linked List Item (LLI) in memory prior to enabling the channel if block chaining is enabled The LLP register has two functions: The logical result of the equation $LLP.LOC \neq 0$ is used to set up the type of DMA transfer-single or multi-block. Table shows how the method of updating the channel registers is a function of $LLP.LOC \neq 0$. If $LLP.LOC$ is set to 0x0, then transfers using linked lists are not enabled. This register must be programmed prior to enabling the channel in order to set up the transfer type. $LLP.LOC \neq 0$ contains the pointer to the next LLI for block chaining using linked lists, The LLPx register can also point to the address where write-back of the control and source/destination status information occur after block completion.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

LLP7: [BAR + 98000h] + 278h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LOC								RSVD2

Bit Range	Default & Access	Description
31:2	00000000h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled. Note that the two LSBs of the starting address are not stored because the address is assumed to be aligned to a 32-bit boundary. LLI accesses are always 32-bit accesses and cannot be changed or programmed to anything other than 32-bit.
1:0	0h RO	RSVD2: Reserved



21.15.95 reg_CTL_LO_type (CTL_LO7)—Offset 280h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO7: [BAR + 98000h] + 280h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																															
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0																											
RSVD				LLP_SRC_EN				RSVD1				TT_FC				RSVD2				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZ				DEST_MSIZ				SINC				RSVD3				DINC				RSVD4				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			
				LLP_DST_EN																																																											

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.15.96 reg_CTL_HI_type (CTL_HI7)—Offset 284h

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI7: [BAR + 98000h] + 284h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI.CTL_HI.DONE bit to see when a block transfer is complete. The LLI.CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.15.97 reg_SSTAT_type (SSTAT7)—Offset 288h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT7: [BAR + 98000h] + 288h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.15.98 reg_DSTAT_type (DSTAT7)—Offset 290h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT7: [BAR + 98000h] + 290h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.15.99 reg_SSTATAR_type (SSTATAR7)—Offset 298h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR7: [BAR + 98000h] + 298h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTATAR

Bit Range	Default & Access	Description
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.

21.15.100 reg_DSTATAR_type (DSTATAR7)—Offset 2A0h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR7: [BAR + 98000h] + 2A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTATAR

Bit Range	Default & Access	Description
31:0	0h RW	DSTATAR: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.

21.15.101 reg_CFG_LO_type (CFG_LO7)—Offset 2A8h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO7: [BAR + 98000h] + 2A8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RELOAD_DST	RELOAD_SRC	Reserved_29_22	SRC_OPT_BL	DST_OPT_BL	SRC_HS_POL	DST_HS_POL	WR_CTLHI_SNP	WR_STAT_SNP
					RD_STAT_SNP	RD_LL_P_SNP	WR_SNP	RD_SNP
					Reserved_11	CH_DRAIN	FIFO_EMPTY	CH_SUSP
						SS_UPD_EN	DS_UPD_EN	CTL_HI_UPD_EN
						RSVD_4_4	HSHAKE_NP_WR	ALL_NP_WR
							SRC_BURST_ALIGN	DST_BURST_ALIGN

Bit Range	Default & Access	Description
31	0h RW	RELOAD_DST: Automatic Destination Reload. The DARN register can be automatically reloaded from its initial value at the end of every block for multi-block transfers. A new block transfer is then initiated.
30	0h RW	RELOAD_SRC: Automatic Source Reload. The SARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers. A new block transfer is then initiated.
29:22	00h RO	Reserved_29_22: Reserved
21	0h RW	SRC_OPT_BL: Optimize Source Burst Length : 0 = Writes will use only BL=1 or BL=(2 ^ SRC_MSIZ) 1 = Writes will use (1 (= BL (= (2 ^ SRC_MSIZ))) *** This bit should be set to (0) if Source HW-Handshake is enabled
20	0h RW	DST_OPT_BL: Optimize Destination Burst Length : 0 = Writes will use only BL=1 or BL=(2 ^ DST_MSIZ) 1 = Writes will use (1 (= BL (= (2 ^ DST_MSIZ))) *** This bit should be set to (0) if Destination HW-Handshake is enabled
19	0h RW	SRC_HS_POL: Source Handshaking Interface Polarity. 0 = Active high 1 = Active low
18	0h RW	DST_HS_POL: Destination Handshaking Interface Polarity. 0 = Active high 1 = Active low
17	0h RW	WR_CTLHI_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Write Port for writing back the CTL_HI register values
16	0h RW	WR_STAT_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Write Port for writing back the SSTAT/DSTAT register values
15	0h RW	RD_STAT_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Read Port for reading SSTAT/DSTAT register values
14	0h RW	RD_LL_P_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Read Port for reading LLP Descriptors
13	0h RW	WR_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Write Port
12	0h RW	RD_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Read Port
11	0b RO	Reserved_11: Reserved
10	0b RW	CH_DRAIN: Forces channel FIFO to drain while in suspension. This bit has effect only when CH_SUSPEND is asserted
9	1b RO	FIFO_EMPTY: Indicates if there is data left in the channel FIFO. Can be used in conjunction with CFGx.CH_SUSP to cleanly disable a channel. 1 = Channel FIFO empty 0 = Channel FIFO not empty



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.15.102 reg_CFG_HI_type (CFG_HI7)—Offset 2ACh

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI7: [BAR + 98000h] + 2ACh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31		28				24				20				16				12				8				4				0			
0 0 0 0 0		0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0							
DST_PER_EXT		SRC_PER_EXT		WR_ISSUE_THD										RD_ISSUE_THD										DST_PER				SRC_PER					



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2 \wedge \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2 \wedge \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.15.103 reg_SGR_type (SGR7)—Offset 2B0h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR7: [BAR + 98000h] + 2B0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.15.104 reg_DSR_type (DSR7)—Offset 2B8h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR7: [BAR + 98000h] + 2B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.15.105 reg_Raw_type (RawTfr)—Offset 2C0h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

RawTfr: [BAR + 98000h] + 2C0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD						RAW		

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	RAW: Raw interrupt status

21.15.106 reg_Raw_type (RawBlock)—Offset 2C8h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RawBlock: [BAR + 98000h] + 2C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD						RAW		

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	RAW: Raw interrupt status



21.15.107 reg_Raw_type (RawSrcTran)—Offset 2D0h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RawSrcTran: [BAR + 98000h] + 2D0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							RAW	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	RAW: Raw interrupt status

21.15.108 reg_Raw_type (RawDstTran)—Offset 2D8h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RawDstTran: [BAR + 98000h] + 2D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD						RAW		
Bit Range	Default & Access	Description						
31:8	0h RO	RSVD: Reserved						
7:0	0h RO	RAW: Raw interrupt status						

21.15.109 reg_Raw_type (RawErr)—Offset 2E0h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RawErr: [BAR + 98000h] + 2E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD						RAW		

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	RAW: Raw interrupt status

21.15.110 reg_Status_type (StatusTfr)—Offset 2E8h

All interrupt events from all channels are stored in these Interrupt Status registers after masking: statusBlock, StatusDstTran, StatusErr, StatusSrcTran, and StatusTfr. Each Interrupt Status register has a bit allocated per channel, for example, StatusTfr(2) is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (int or int_n bus, depending on interrupt polarity) leaving the DMA.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

StatusTfr: [BAR + 98000h] + 2E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							STATUS	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	STATUS: Interrupt status

21.15.111 reg_Status_type (StatusBlock)—Offset 2F0h

All interrupt events from all channels are stored in these Interrupt Status registers after masking: statusBlock, StatusDstTran, StatusErr, StatusSrcTran, and StatusTfr. Each Interrupt Status register has a bit allocated per channel, for example, StatusTfr(2) is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (int or int_n bus, depending on interrupt polarity) leaving the DMA.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

StatusBlock: [BAR + 98000h] + 2F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							STATUS	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	STATUS: Interrupt status



Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	STATUS: Interrupt status

21.15.114 reg Status type (StatusErr)—Offset 308h

All interrupt events from all channels are stored in these Interrupt Status registers after masking: `statusBlock`, `StatusDstTran`, `StatusErr`, `StatusSrcTran`, and `StatusTfr`. Each Interrupt Status register has a bit allocated per channel, for example, `StatusTfr(2)` is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (`int` or `int_n` bus, depending on interrupt polarity) leaving the DMA.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

StatusErr: [BAR + 98000h] + 308h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD						STATUS		

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	STATUS: Interrupt status

21.15.115 reg_Mask_type (MaskTfr)—Offset 310h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel, for example, MaskTfr(2) is the mask bit for the Channel 2 transfer complete interrupt. When the source peripheral of DMA channel *i* is memory, then the source transaction complete interrupt, MaskSrcTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined signal. Similarly, when the destination peripheral of DMA channel *i* is memory, then the destination transaction complete interrupt, MaskDstTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined(_n) signal. A channel INT_MASK bit will be written only if the corresponding mask write enable bit in the INT_MASK_WE field is asserted on the same OCP write transfer. This allows software to set a mask bit without performing a read-modified write operation. For example, writing hex 01x1 to the MaskTfr register writes a 1 into MaskTfr(0), while MaskTfr(7:1) remains unchanged. Writing hex 00xx leaves MaskTfr(7:0) unchanged.



Writing a 1 to any bit in these registers unmasks the corresponding interrupt, thus allowing the DMA to set the appropriate bit in the Status registers and int_* port signals.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MaskTfr: [BAR + 98000h] + 310h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD2				INT_MASK_WE				INT_MASK

Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	INT_MASK_WE: Interrupt Mask Write Enable 0 = write disabled 1 = write enabled
7:0	0h RW	INT_MASK: Interrupt mask 0-mask 1-unmask

21.15.116 reg_Mask_type (MaskBlock)—Offset 318h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel, for example, MaskTfr(2) is the mask bit for the Channel 2 transfer complete interrupt. When the source peripheral of DMA channel i is memory, then the source transaction complete interrupt, MaskSrcTran(i), must be masked to prevent an erroneous triggering of an interrupt on the int_combined signal. Similarly, when the destination peripheral of DMA channel i is memory, then the destination transaction complete interrupt, MaskDstTran(i), must be masked to prevent an erroneous triggering of an interrupt on the int_combined(_n) signal. A channel INT_MASK bit will be written only if the corresponding mask write enable bit in the INT_MASK_WE field is asserted on the same OCP write transfer. This allows software to set a mask bit without performing a read-modified write operation. For example, writing hex 01x1 to the MaskTfr register writes a 1 into MaskTfr(0), while MaskTfr(7:1) remains unchanged. Writing hex 00xx leaves MaskTfr(7:0) unchanged. Writing a 1 to any bit in these registers unmasks the corresponding interrupt, thus allowing the DMA to set the appropriate bit in the Status registers and int_* port signals.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MaskBlock: [BAR + 98000h] + 318h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2				INT_MASK_WE				INT_MASK

Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	INT_MASK_WE: Interrupt Mask Write Enable 0 = write disabled 1 = write enabled
7:0	0h RW	INT_MASK: Interrupt mask 0-mask 1-unmask

21.15.117 reg_Mask_type (MaskSrcTran)—Offset 320h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel, for example, MaskTfr(2) is the mask bit for the Channel 2 transfer complete interrupt. When the source peripheral of DMA channel *i* is memory, then the source transaction complete interrupt, MaskSrcTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined signal. Similarly, when the destination peripheral of DMA channel *i* is memory, then the destination transaction complete interrupt, MaskDstTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined(_n) signal. A channel INT_MASK bit will be written only if the corresponding mask write enable bit in the INT_MASK_WE field is asserted on the same OCP write transfer. This allows software to set a mask bit without performing a read-modified write operation. For example, writing hex 01x1 to the MaskTfr register writes a 1 into MaskTfr(0), while MaskTfr(7:1) remains unchanged. Writing hex 00xx leaves MaskTfr(7:0) unchanged. Writing a 1 to any bit in these registers unmask the corresponding interrupt, thus allowing the DMA to set the appropriate bit in the Status registers and int_* port signals.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MaskSrcTran: [BAR + 98000h] + 320h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2				INT_MASK_WE				INT_MASK

21.15.118 reg Mask_type (MaskDstTran)—Offset 328h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel, for example, MaskTfr(2) is the mask bit for the Channel 2 transfer complete interrupt. When the source peripheral of DMA channel *i* is memory, then the source transaction complete interrupt, MaskSrcTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined signal. Similarly, when the destination peripheral of DMA channel *i* is memory, then the destination transaction complete interrupt, MaskDstTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined(_n) signal. A channel INT_MASK bit will be written only if the corresponding mask write enable bit in the INT_MASK_WE field is asserted on the same OCP write transfer. This allows software to set a mask bit without performing a read-modified write operation. For example, writing hex 01x1 to the MaskTfr register writes a 1 into MaskTfr(0), while MaskTfr(7:1) remains unchanged. Writing hex 00xx leaves MaskTfr(7:0) unchanged. Writing a 1 to any bit in these registers un masks the corresponding interrupt, thus allowing the DMA to set the appropriate bit in the Status registers and int_* port signals.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MaskDstTran: [BAR + 98000h] + 328h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD2				INT_MASK_WE				INT_MASK

Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	INT_MASK_WE: Interrupt Mask Write Enable 0 = write disabled 1 = write enabled
7:0	0h RW	INT_MASK: Interrupt mask 0-mask 1-unmask



21.15.119 reg_Mask_type (MaskErr)—Offset 330h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel, for example, MaskTfr(2) is the mask bit for the Channel 2 transfer complete interrupt. When the source peripheral of DMA channel *i* is memory, then the source transaction complete interrupt, MaskSrcTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined signal. Similarly, when the destination peripheral of DMA channel *i* is memory, then the destination transaction complete interrupt, MaskDstTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined(_n) signal. A channel INT_MASK bit will be written only if the corresponding mask write enable bit in the INT_MASK_WE field is asserted on the same OCP write transfer. This allows software to set a mask bit without performing a read-modified write operation. For example, writing hex 01x1 to the MaskTfr register writes a 1 into MaskTfr(0), while MaskTfr(7:1) remains unchanged. Writing hex 00xx leaves MaskTfr(7:0) unchanged. Writing a 1 to any bit in these registers unmask the corresponding interrupt, thus allowing the DMA to set the appropriate bit in the Status registers and int_* port signals.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MaskErr: [BAR + 98000h] + 330h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2				INT_MASK_WE				INT_MASK

Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	INT_MASK_WE: Interrupt Mask Write Enable 0 = write disabled 1 = write enabled
7:0	0h RW	INT_MASK: Interrupt mask 0-mask 1-unmask

21.15.120 reg_Clear_type (ClearTfr)—Offset 338h

Each bit in the Raw Status and Status registers is cleared on the same cycle by writing a 1 to the corresponding location in the Clear registers: ClearBlock, ClearDstTran, ClearErr, ClearSrcTran, and ClearTfr. Each Interrupt Clear register has a bit allocated per channel, for example, ClearTfr(2) is the clear bit for the Channel 2 transfer complete interrupt. Writing a 0 has no effect. These registers are not readable.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

ClearTfr: [BAR + 98000h] + 338h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							CLEAR	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h WO	CLEAR: Interrupt clear. 0 = no effect 1 = clear interrupt

21.15.121 reg_Clear_type (ClearBlock)—Offset 340h

Each bit in the Raw Status and Status registers is cleared on the same cycle by writing a 1 to the corresponding location in the Clear registers: ClearBlock, ClearDstTran, ClearErr, ClearSrcTran, and ClearTfr. Each Interrupt Clear register has a bit allocated per channel, for example, ClearTfr(2) is the clear bit for the Channel 2 transfer complete interrupt. Writing a 0 has no effect. These registers are not readable.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ClearBlock: [BAR + 98000h] + 340h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							CLEAR	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h WO	CLEAR: Interrupt clear. 0 = no effect 1 = clear interrupt



21.15.122 reg_Clear_type (ClearSrcTran)—Offset 348h

Each bit in the Raw Status and Status registers is cleared on the same cycle by writing a 1 to the corresponding location in the Clear registers: ClearBlock, ClearDstTran, ClearErr, ClearSrcTran, and ClearTfr. Each Interrupt Clear register has a bit allocated per channel, for example, ClearTfr(2) is the clear bit for the Channel 2 transfer complete interrupt. Writing a 0 has no effect. These registers are not readable.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ClearSrcTran: [BAR + 98000h] + 348h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							CLEAR	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h WO	CLEAR: Interrupt clear. 0 = no effect 1 = clear interrupt

21.15.123 reg_Clear_type (ClearDstTran)—Offset 350h

Each bit in the Raw Status and Status registers is cleared on the same cycle by writing a 1 to the corresponding location in the Clear registers: ClearBlock, ClearDstTran, ClearErr, ClearSrcTran, and ClearTfr. Each Interrupt Clear register has a bit allocated per channel, for example, ClearTfr(2) is the clear bit for the Channel 2 transfer complete interrupt. Writing a 0 has no effect. These registers are not readable.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ClearDstTran: [BAR + 98000h] + 350h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							CLEAR	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved

Bit Range	Default & Access	Description
31:5	0h RO	RSVD: Reserved
4	0h RO	ERR: OR of the contents of StatusErr register.
3	0h RO	DSTT: OR of the contents of StatusDst register.
2	0h RO	SRCT: OR of the contents of StatusSrcTran register
1	0h RO	BLOCK: OR of the contents of StatusBlock register.
0	0h RO	TFR: OR of the contents of StatusTfr register.

21.15.126 reg_DmaCfgReg_type (DmaCfgReg)—Offset 398h

This register is used to enable the DMA, which must be done before any channel activity can begin. If the global channel enable bit is cleared while any channel is still active, then `DmaCfgReg.DMA_EN` still returns 1 to indicate that there are channels still active until hardware has terminated all activity on all channels, at which point the `DmaCfgReg.DMA_EN` bit returns 0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DmaCfgReg: [BAR + 98000h] + 398h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RSVD									FDMA EN

Bit Range	Default & Access	Description
31:1	0h RO	RSVD: Reserved
0	0h RW	DMA_EN: DMA Enable bit. 0 = DMA Disabled 1 = DMA Enabled

21.15.127 reg_ChEnReg_type (ChEnReg)—Offset 3A0h

This is the DMA Channel Enable Register. If software needs to set up a new channel, then it can read this register in order to find out which channels are currently inactive, it can then enable an inactive channel with the required priority. All bits of this register are cleared to 0 when the global DMA channel enable bit, `DmaCrgReg(0)`, is 0. When the global channel enable bit is 0, then a write to the `ChEnReg` register is ignored and a read will always read back 0. The channel enable bit, `ChEnReg.CH_EN`, is written only if the corresponding channel write enable bit, `ChEnReg.CH_EN_WE`, is asserted on the



same OCP write transfer. For example, writing hex 01x1 writes a 1 into ChEnReg(0), while ChEnReg(7:1) remains unchanged. Writing hex 00xx leaves ChEnReg(7:0) unchanged. Note that a read-modified write is not required.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ChEnReg: [BAR + 98000h] + 3A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2				CH_EN_WE				CH_EN

Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	CH_EN_WE: Channel enable write enable.
7:0	0h RW	CH_EN: Enables/Disables the channel. Setting this bit enables a channel, clearing this bit disables the channel. 0 = Disable the Channel 1 = Enable the Channel The ChEnReg.CH_EN bit is automatically cleared by hardware to disable the channel after the last OCP transfer of the DMA transfer to the destination has completed. Software can therefore poll this bit to determine when this channel is free for a new DMA transfer.

21.15.128 reg_CLASS_PRIORITY0_LO_type (ClassPriority0_LO)—Offset 3B8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ClassPriority0_LO: [BAR + 98000h] + 3B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2				WT_CLASS_1				WT_CLASS_0

Bit Range	Default & Access	Description
31:22	0h RO	RSVD2: Reserved



Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD1				WT_CLASS_7				WT_CLASS_6

Bit Range	Default & Access	Description
31:22	0h RO	RSVD1: Reserved
21:11	0h RW	WT_CLASS_7: Class Weight 7: Value of K assigns a weight of (K+1) to Class 7. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Class Weight ranges from 1 to 2048 bytes.
10:0	0h RW	WT_CLASS_6: Class Weight 6: Value of K assigns a weight of (K+1) to Class 6. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Class Weight ranges from 1 to 2048 bytes.

21.15.132 reg_FIFO_PARTITION0_LO_type (FifoPartition0_LO)—Offset 400h

Intel Atom® Processor E3800 Product Family
Datasheet
3044



Type: Memory Mapped I/O Register
(Size: 32 bits)

FifoPartition0_LO: [BAR + 98000h] + 400h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2	PARTITION_UPDATE		PSIZE_CH_1				PSIZE_CH_0	

Bit Range	Default & Access	Description
31:27	0h RO	RSVD2: Reserved
26	0h RW	PARTITION_UPDATE: SW needs to write to this bit for the partitioning assignments to take effect.
25:13	0h RW	PSIZE_CH_1: Partition Byte Size assigned to Channel 1. Ranges from 0 Bytes to (2 ¹³ - 1)=8191 Bytes. However, size needs to be DW Aligned, i.e. a multiple of 4.
12:0	0h RW	PSIZE_CH_0: Partition Byte Size assigned to Channel 0. Ranges from 0 Bytes to (2 ¹³ - 1)=8191 Bytes. However, size needs to be DW Aligned, i.e. a multiple of 4.

21.15.133 reg_FIFO_PARTITION0_HI_type (FifoPartition0_HI)—Offset 404h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

FifoPartition0_HI: [BAR + 98000h] + 404h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD1		PSIZE_CH_3					PSIZE_CH_2	

Bit Range	Default & Access	Description
31:26	0h RO	RSVD1: Reserved
25:13	0h RW	PSIZE_CH_3: Partition Byte Size assigned to Channel 3. Ranges from 0 Bytes to (2 ¹³ - 1)=8191 Bytes. However, size needs to be DW Aligned, i.e. a multiple of 4.



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD							CH_SAI_ERR	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	CH_SAI_ERR: 1: SAI Error occurred on Ch [n] 0: No SAI Error occurred on Ch [n] SAI_ERROR[n] is set by HW on SAI violation for channel [n]. All bits get cleared by SW when reading this register

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
SCRATCH_PAD FRR_T11_REG									



Bit Range	Default & Access	Description
31:1	0h RW	SCRATCH_PAD: This field will have all bits with R/W attribute to be used for future configuration and de-feature bits.
0	0b RW	ERR_ILL_REG: 0x1 : Issue ERR response on reading illegal (non-existing) registers 0x0 : Issue DVA response on reading illegal (non-existing) registers



21.16 Low Power Audio DMA1 Memory Mapped IO Registers

**Table 238. Summary of Low Power Audio DMA1 Memory Mapped I/O Registers—
lpe_bridge.BAR**

Offset	Size	Register ID—Description	Default Value
0h	4	"reg_SAR_type (SAR0)—Offset 0h" on page 3052	00000000h
8h	4	"reg_DAR_type (DAR0)—Offset 8h" on page 3053	00000000h
10h	4	"reg_LL_P_type (LLP0)—Offset 10h" on page 3054	00000000h
18h	4	"reg_CTL_LO_type (CTL_LO0)—Offset 18h" on page 3055	00000000h
1Ch	4	"reg_CTL_HI_type (CTL_HI0)—Offset 1Ch" on page 3056	00000000h
20h	4	"reg_SSTAT_type (SSTAT0)—Offset 20h" on page 3057	00000000h
28h	4	"reg_DSTAT_type (DSTAT0)—Offset 28h" on page 3058	00000000h
30h	4	"reg_SSTATAR_type (SSTATAR0)—Offset 30h" on page 3058	00000000h
38h	4	"reg_DSTATAR_type (DSTATAR0)—Offset 38h" on page 3059	00000000h
40h	4	"reg_CFG_LO_type (CFG_LO0)—Offset 40h" on page 3059	00000203h
44h	4	"reg_CFG_HI_type (CFG_HI0)—Offset 44h" on page 3061	00000000h
48h	4	"reg_SGR_type (SGR0)—Offset 48h" on page 3062	00000000h
50h	4	"reg_DSR_type (DSR0)—Offset 50h" on page 3063	00000000h
58h	4	"reg_SAR_type (SAR1)—Offset 58h" on page 3063	00000000h
60h	4	"reg_DAR_type (DAR1)—Offset 60h" on page 3064	00000000h
68h	4	"reg_LL_P_type (LLP1)—Offset 68h" on page 3065	00000000h
70h	4	"reg_CTL_LO_type (CTL_LO1)—Offset 70h" on page 3066	00000000h
74h	4	"reg_CTL_HI_type (CTL_HI1)—Offset 74h" on page 3067	00000000h
78h	4	"reg_SSTAT_type (SSTAT1)—Offset 78h" on page 3068	00000000h
80h	4	"reg_DSTAT_type (DSTAT1)—Offset 80h" on page 3069	00000000h
88h	4	"reg_SSTATAR_type (SSTATAR1)—Offset 88h" on page 3069	00000000h
90h	4	"reg_DSTATAR_type (DSTATAR1)—Offset 90h" on page 3070	00000000h
98h	4	"reg_CFG_LO_type (CFG_LO1)—Offset 98h" on page 3070	00000203h
9Ch	4	"reg_CFG_HI_type (CFG_HI1)—Offset 9Ch" on page 3072	00000000h
A0h	4	"reg_SGR_type (SGR1)—Offset A0h" on page 3073	00000000h
A8h	4	"reg_DSR_type (DSR1)—Offset A8h" on page 3074	00000000h
B0h	4	"reg_SAR_type (SAR2)—Offset B0h" on page 3074	00000000h
B8h	4	"reg_DAR_type (DAR2)—Offset B8h" on page 3075	00000000h
C0h	4	"reg_LL_P_type (LLP2)—Offset C0h" on page 3076	00000000h
C8h	4	"reg_CTL_LO_type (CTL_LO2)—Offset C8h" on page 3077	00000000h
CCh	4	"reg_CTL_HI_type (CTL_HI2)—Offset CCh" on page 3078	00000000h
D0h	4	"reg_SSTAT_type (SSTAT2)—Offset D0h" on page 3079	00000000h
D8h	4	"reg_DSTAT_type (DSTAT2)—Offset D8h" on page 3080	00000000h
E0h	4	"reg_SSTATAR_type (SSTATAR2)—Offset E0h" on page 3080	00000000h
E8h	4	"reg_DSTATAR_type (DSTATAR2)—Offset E8h" on page 3081	00000000h



**Table 238. Summary of Low Power Audio DMA1 Memory Mapped I/O Registers—
lpe_bridge.BAR (Continued)**

Offset	Size	Register ID—Description	Default Value
F0h	4	"reg_CFG_LO_type (CFG_LO2)—Offset F0h" on page 3081	00000203h
F4h	4	"reg_CFG_HI_type (CFG_HI2)—Offset F4h" on page 3083	00000000h
F8h	4	"reg_SGR_type (SGR2)—Offset F8h" on page 3084	00000000h
100h	4	"reg_DSR_type (DSR2)—Offset 100h" on page 3085	00000000h
108h	4	"reg_SAR_type (SAR3)—Offset 108h" on page 3085	00000000h
110h	4	"reg_DAR_type (DAR3)—Offset 110h" on page 3086	00000000h
118h	4	"reg_LL_P_type (LLP3)—Offset 118h" on page 3087	00000000h
120h	4	"reg_CTL_LO_type (CTL_LO3)—Offset 120h" on page 3088	00000000h
124h	4	"reg_CTL_HI_type (CTL_HI3)—Offset 124h" on page 3089	00000000h
128h	4	"reg_SSTAT_type (SSTAT3)—Offset 128h" on page 3090	00000000h
130h	4	"reg_DSTAT_type (DSTAT3)—Offset 130h" on page 3091	00000000h
138h	4	"reg_SSTATAR_type (SSTATAR3)—Offset 138h" on page 3091	00000000h
140h	4	"reg_DSTATAR_type (DSTATAR3)—Offset 140h" on page 3092	00000000h
148h	4	"reg_CFG_LO_type (CFG_LO3)—Offset 148h" on page 3092	00000203h
14Ch	4	"reg_CFG_HI_type (CFG_HI3)—Offset 14Ch" on page 3094	00000000h
150h	4	"reg_SGR_type (SGR3)—Offset 150h" on page 3095	00000000h
158h	4	"reg_DSR_type (DSR3)—Offset 158h" on page 3096	00000000h
160h	4	"reg_SAR_type (SAR4)—Offset 160h" on page 3096	00000000h
168h	4	"reg_DAR_type (DAR4)—Offset 168h" on page 3097	00000000h
170h	4	"reg_LL_P_type (LLP4)—Offset 170h" on page 3098	00000000h
178h	4	"reg_CTL_LO_type (CTL_LO4)—Offset 178h" on page 3099	00000000h
17Ch	4	"reg_CTL_HI_type (CTL_HI4)—Offset 17Ch" on page 3100	00000000h
180h	4	"reg_SSTAT_type (SSTAT4)—Offset 180h" on page 3101	00000000h
188h	4	"reg_DSTAT_type (DSTAT4)—Offset 188h" on page 3102	00000000h
190h	4	"reg_SSTATAR_type (SSTATAR4)—Offset 190h" on page 3102	00000000h
198h	4	"reg_DSTATAR_type (DSTATAR4)—Offset 198h" on page 3103	00000000h
1A0h	4	"reg_CFG_LO_type (CFG_LO4)—Offset 1A0h" on page 3103	00000203h
1A4h	4	"reg_CFG_HI_type (CFG_HI4)—Offset 1A4h" on page 3105	00000000h
1A8h	4	"reg_SGR_type (SGR4)—Offset 1A8h" on page 3106	00000000h
1B0h	4	"reg_DSR_type (DSR4)—Offset 1B0h" on page 3107	00000000h
1B8h	4	"reg_SAR_type (SAR5)—Offset 1B8h" on page 3107	00000000h
1C0h	4	"reg_DAR_type (DAR5)—Offset 1C0h" on page 3108	00000000h
1C8h	4	"reg_LL_P_type (LLP5)—Offset 1C8h" on page 3109	00000000h
1D0h	4	"reg_CTL_LO_type (CTL_LO5)—Offset 1D0h" on page 3110	00000000h
1D4h	4	"reg_CTL_HI_type (CTL_HI5)—Offset 1D4h" on page 3111	00000000h
1D8h	4	"reg_SSTAT_type (SSTAT5)—Offset 1D8h" on page 3112	00000000h
1E0h	4	"reg_DSTAT_type (DSTAT5)—Offset 1E0h" on page 3113	00000000h
1E8h	4	"reg_SSTATAR_type (SSTATAR5)—Offset 1E8h" on page 3113	00000000h



**Table 238. Summary of Low Power Audio DMA1 Memory Mapped I/O Registers—
lpe_bridge.BAR (Continued)**

Offset	Size	Register ID—Description	Default Value
1F0h	4	"reg_DSTATAR_type (DSTATAR5)—Offset 1F0h" on page 3114	00000000h
1F8h	4	"reg_CFG_LO_type (CFG_LO5)—Offset 1F8h" on page 3114	00000203h
1FCh	4	"reg_CFG_HI_type (CFG_HI5)—Offset 1FCh" on page 3116	00000000h
200h	4	"reg_SGR_type (SGR5)—Offset 200h" on page 3117	00000000h
208h	4	"reg_DSR_type (DSR5)—Offset 208h" on page 3118	00000000h
210h	4	"reg_SAR_type (SAR6)—Offset 210h" on page 3118	00000000h
218h	4	"reg_DAR_type (DAR6)—Offset 218h" on page 3119	00000000h
220h	4	"reg_LL_P_type (LLP6)—Offset 220h" on page 3120	00000000h
228h	4	"reg_CTL_LO_type (CTL_LO6)—Offset 228h" on page 3121	00000000h
22Ch	4	"reg_CTL_HI_type (CTL_HI6)—Offset 22Ch" on page 3122	00000000h
230h	4	"reg_SSTAT_type (SSTAT6)—Offset 230h" on page 3123	00000000h
238h	4	"reg_DSTAT_type (DSTAT6)—Offset 238h" on page 3124	00000000h
240h	4	"reg_SSTATAR_type (SSTATAR6)—Offset 240h" on page 3124	00000000h
248h	4	"reg_DSTATAR_type (DSTATAR6)—Offset 248h" on page 3125	00000000h
250h	4	"reg_CFG_LO_type (CFG_LO6)—Offset 250h" on page 3125	00000203h
254h	4	"reg_CFG_HI_type (CFG_HI6)—Offset 254h" on page 3127	00000000h
258h	4	"reg_SGR_type (SGR6)—Offset 258h" on page 3128	00000000h
260h	4	"reg_DSR_type (DSR6)—Offset 260h" on page 3129	00000000h
268h	4	"reg_SAR_type (SAR7)—Offset 268h" on page 3129	00000000h
270h	4	"reg_DAR_type (DAR7)—Offset 270h" on page 3130	00000000h
278h	4	"reg_LL_P_type (LLP7)—Offset 278h" on page 3131	00000000h
280h	4	"reg_CTL_LO_type (CTL_LO7)—Offset 280h" on page 3132	00000000h
284h	4	"reg_CTL_HI_type (CTL_HI7)—Offset 284h" on page 3133	00000000h
288h	4	"reg_SSTAT_type (SSTAT7)—Offset 288h" on page 3134	00000000h
290h	4	"reg_DSTAT_type (DSTAT7)—Offset 290h" on page 3135	00000000h
298h	4	"reg_SSTATAR_type (SSTATAR7)—Offset 298h" on page 3135	00000000h
2A0h	4	"reg_DSTATAR_type (DSTATAR7)—Offset 2A0h" on page 3136	00000000h
2A8h	4	"reg_CFG_LO_type (CFG_LO7)—Offset 2A8h" on page 3136	00000203h
2ACh	4	"reg_CFG_HI_type (CFG_HI7)—Offset 2ACh" on page 3138	00000000h
2B0h	4	"reg_SGR_type (SGR7)—Offset 2B0h" on page 3139	00000000h
2B8h	4	"reg_DSR_type (DSR7)—Offset 2B8h" on page 3140	00000000h
2C0h	4	"reg_Raw_type (RawTfr)—Offset 2C0h" on page 3140	00000000h
2C8h	4	"reg_Raw_type (RawBlock)—Offset 2C8h" on page 3141	00000000h
2D0h	4	"reg_Raw_type (RawSrcTran)—Offset 2D0h" on page 3142	00000000h
2D8h	4	"reg_Raw_type (RawDstTran)—Offset 2D8h" on page 3142	00000000h
2E0h	4	"reg_Raw_type (RawErr)—Offset 2E0h" on page 3143	00000000h
2E8h	4	"reg_Status_type (StatusTfr)—Offset 2E8h" on page 3143	00000000h
2F0h	4	"reg_Status_type (StatusBlock)—Offset 2F0h" on page 3144	00000000h



**Table 238. Summary of Low Power Audio DMA1 Memory Mapped I/O Registers—
lpe_bridge.BAR (Continued)**

Offset	Size	Register ID—Description	Default Value
2F8h	4	"reg_Status_type (StatusSrcTran)—Offset 2F8h" on page 3145	00000000h
300h	4	"reg_Status_type (StatusDstTran)—Offset 300h" on page 3145	00000000h
308h	4	"reg_Status_type (StatusErr)—Offset 308h" on page 3146	00000000h
310h	4	"reg_Mask_type (MaskTfr)—Offset 310h" on page 3146	00000000h
318h	4	"reg_Mask_type (MaskBlock)—Offset 318h" on page 3147	00000000h
320h	4	"reg_Mask_type (MaskSrcTran)—Offset 320h" on page 3148	00000000h
328h	4	"reg_Mask_type (MaskDstTran)—Offset 328h" on page 3149	00000000h
330h	4	"reg_Mask_type (MaskErr)—Offset 330h" on page 3150	00000000h
338h	4	"reg_Clear_type (ClearTfr)—Offset 338h" on page 3150	00000000h
340h	4	"reg_Clear_type (ClearBlock)—Offset 340h" on page 3151	00000000h
348h	4	"reg_Clear_type (ClearSrcTran)—Offset 348h" on page 3152	00000000h
350h	4	"reg_Clear_type (ClearDstTran)—Offset 350h" on page 3152	00000000h
358h	4	"reg_Clear_type (ClearErr)—Offset 358h" on page 3153	00000000h
360h	4	"reg_StatusInt_type (StatusInt)—Offset 360h" on page 3153	00000000h
398h	4	"reg_DmaCfgReg_type (DmaCfgReg)—Offset 398h" on page 3154	00000000h
3A0h	4	"reg_ChEnReg_type (ChEnReg)—Offset 3A0h" on page 3154	00000000h
3B8h	4	"reg_CLASS_PRIORITY0_LO_type (ClassPriority0_LO)—Offset 3B8h" on page 3155	00000000h
3BCh	4	"reg_CLASS_PRIORITY0_HI_type (ClassPriority0_HI)—Offset 3BCh" on page 3156	00000000h
3C0h	4	"reg_CLASS_PRIORITY1_LO_type (ClassPriority1_LO)—Offset 3C0h" on page 3156	00000000h
3C4h	4	"reg_CLASS_PRIORITY1_HI_type (ClassPriority1_HI)—Offset 3C4h" on page 3157	00000000h
400h	4	"reg_FIFO_PARTITION0_LO_type (FifoPartition0_LO)—Offset 400h" on page 3157	00000000h
404h	4	"reg_FIFO_PARTITION0_HI_type (FifoPartition0_HI)—Offset 404h" on page 3158	00000000h
408h	4	"reg_FIFO_PARTITION1_LO_type (FifoPartition1_LO)—Offset 408h" on page 3159	00000000h
40Ch	4	"reg_FIFO_PARTITION1_HI_type (FifoPartition1_HI)—Offset 40Ch" on page 3159	00000000h
410h	4	"reg_SAI_Error_type (SAI_ERR)—Offset 410h" on page 3160	00000000h
418h	4	"reg_GLOBAL_CFG_type (GLOBAL_CFG)—Offset 418h" on page 3160	00000000h

21.16.1 reg_SAR_type (SAR0)—Offset 0h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR0: [BAR + 9C000h] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



21.16.2 reg_DAR_type (DAR0)—Offset 8h

Access Method

DARO: [BAR + 9C000h] + 8h

BAR Reference: [B:0, D:21, F:0] + 10h

	31	28	24	20	16	12	8	4	0
	0	0	0	0	0	0	0	0	0
DAR	0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Description
31:0	0h RW	DAR: Current Destination Address of DMA transfer. Updated after each destination transfer. The DINC field in the CTL_LO[n]: Control Register determines whether the address increments or is left unchanged on every destination transfer throughout the block transfer. When the channel is enabled (i.e. CH_EN is 1), the read back value will reflect the updated destination transfer addresses. However, when the channel is disabled, the original programmed value will be reflected when reading this register. It's important to notice the following: 1. Once the block transfer is in progress (i.e. when channel is enabled), the read-back value correlates with the OCP Write Address that one would see in an OCP tracker. 2. If the read to this register comes during a block transfer, the LAST DMA Write address sent on the OCP before the register read is what's reflected in the read-back value. 3. If the last DMA write was a burst write (i.e. burst length > 1), the read-back value reflects the first address of the burst write since this is what gets sent on the OCP fabric. 4. If the read to the register occurred after the whole block got transferred, then the channel gets disabled and the returned value would be the original programmed value. 5. Since the read-back value is OCP based, only DW aligned addresses will be reflected (i.e. OCP Byte-Enable values would not be reflected) 6. Based on the above remarks, this value should be used as pseudo DMA write progress indicator when the channel is enabled and not an absolute one. Decrementing addresses are not supported

21.16.3 reg_LLPType (LLP0)—Offset 10h

Note: You need to program this register to point to the first Linked List Item (LLI) in memory prior to enabling the channel if block chaining is enabled. The LLP register has two functions: The logical result of the equation $LLP.LOC \neq 0$ is used to set up the type of DMA transfer—single or multi-block. Table shows how the method of updating the channel registers is a function of $LLP.LOC \neq 0$. If $LLP.LOC$ is set to 0x0, then transfers using linked lists are not enabled. This register must be programmed prior to enabling the channel in order to set up the transfer type. $LLP.LOC \neq 0$ contains the pointer to the next LLI for block chaining using linked lists. The LLPx register can also point to the address where write-back of the control and source/destination status information occur after block completion.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

LLP0: [BAR + 9C000h] + 10h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LOC								RSVD2

Bit Range	Default & Access	Description
31:2	00000000h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled. Note that the two LSBs of the starting address are not stored because the address is assumed to be aligned to a 32-bit boundary. LLI accesses are always 32-bit accesses and cannot be changed or programmed to anything other than 32-bit.
1:0	0h RO	RSVD2: Reserved



21.16.4 reg_CTL_LO_type (CTL_LO0)—Offset 18h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO0: [BAR + 9C000h] + 18h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0											
RSVD				LLP_SRC_EN				RSVD1				TT_FC				RSVD2				SRC_MSIZ				DEST_MSIZ				SINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			
				LLP_DST_EN												DST_SCATTER_EN												SRC_GATHER_EN															

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.16.5 reg_CTL_HI_type (CTL_HI0)—Offset 1Ch

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI0: [BAR + 9C000h] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.16.6 reg_SSTAT_type (SSTAT0)—Offset 20h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT0: [BAR + 9C000h] + 20h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.16.7 reg_DSTAT_type (DSTAT0)—Offset 28h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT0: [BAR + 9C000h] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.16.8 reg_SSTATAR_type (SSTATAR0)—Offset 30h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR0: [BAR + 9C000h] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

			31	28				24				20				16				12				8				4				0			
			0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
			SSTATAR																																
Bit Range	Default & Access	Description																																	
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.																																	

21.16.9 reg_DSTATAR_type (DSTATAR0)—Offset 38h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR0: [BAR + 9C000h] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

			31	28				24				20				16				12				8				4				0		
			0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
			DSTATn																															
Bit Range	Default & Access	Description																																
31:0	0h RW	DSTATn: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.																																

21.16.10 reg_CFG_LO_type (CFG_LO0)—Offset 40h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO0: [BAR + 9C000h] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



31		28				24				20				16				12				8				4				0																																									
0		0		0		0		0		0		0		0		0		0		0		1		0		0		0		0		0		0		0		1		1																															
RELOAD_DST		RELOAD_SRC		Reserved_29_22																								SRC_OPT_BL		DST_OPT_BL		SRC_HS_POL		DST_HS_POL		WR_CTLHI_SNP		WR_STAT_SNP		RD_STAT_SNP		RD_LL_P_SNP		WR_SNP		RD_SNP		Reserved_11		CH_DRAIN		FIFO_EMPTY		CH_SUSP		SS_UPD_EN		DS_UPD_EN		CTL_HI_UPD_EN		RSVD_4_4		HSHAKE_NP_WR		ALL_NP_WR		SRC_BURST_ALIGN		DST_BURST_ALIGN	

Bit Range	Default & Access	Description
31	0h RW	RELOAD_DST: Automatic Destination Reload. The DARN register can be automatically reloaded from its initial value at the end of every block for multi-block transfers. A new block transfer is then initiated.
30	0h RW	RELOAD_SRC: Automatic Source Reload. The SARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers. A new block transfer is then initiated.
29:22	00h RO	Reserved_29_22: Reserved
21	0h RW	SRC_OPT_BL: Optimize Source Burst Length : 0 = Writes will use only BL=1 or BL=(2 ^ SRC_MSIZ) 1 = Writes will use (1 (= BL (= (2 ^ SRC_MSIZ))) *** This bit should be set to (0) if Source HW-Handshake is enabled
20	0h RW	DST_OPT_BL: Optimize Destination Burst Length : 0 = Writes will use only BL=1 or BL=(2 ^ DST_MSIZ) 1 = Writes will use (1 (= BL (= (2 ^ DST_MSIZ))) *** This bit should be set to (0) if Destination HW-Handshake is enabled
19	0h RW	SRC_HS_POL: Source Handshaking Interface Polarity. 0 = Active high 1 = Active low
18	0h RW	DST_HS_POL: Destination Handshaking Interface Polarity. 0 = Active high 1 = Active low
17	0h RW	WR_CTLHI_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Write Port for writing back the CTL_HI register values
16	0h RW	WR_STAT_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Write Port for writing back the SSTAT/DSTAT register values
15	0h RW	RD_STAT_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Read Port for reading SSTAT/DSTAT register values
14	0h RW	RD_LL_P_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Read Port for reading LLP Descriptors
13	0h RW	WR_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Write Port
12	0h RW	RD_SNP: This Snoop-Attribute bit is driven on the MSB of MReqInfo of DMA Read Port
11	0b RO	Reserved_11: Reserved
10	0b RW	CH_DRAIN: Forces channel FIFO to drain while in suspension. This bit has effect only when CH_SUSPEND is asserted
9	1b RO	FIFO_EMPTY: Indicates if there is data left in the channel FIFO. Can be used in conjunction with CFGx.CH_SUSP to cleanly disable a channel. 1 = Channel FIFO empty 0 = Channel FIFO not empty



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.16.11 reg_CFG_HI_type (CFG_HI0)—Offset 44h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


CFG_HI0: [BAR + 9C000h] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31			28				24				20				16				12				8				4				0			
0			0				0				0				0				0				0				0				0			
DST_PER_EXT			SRC_PER_EXT				WR_ISSUE_THD								RD_ISSUE_THD								DST_PER				SRC_PER							



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2^{\wedge} \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2^{\wedge} \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.16.12 reg_SGR_type (SGR0)—Offset 48h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR0: [BAR + 9C000h] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.16.13 reg_DSR_type (DSR0)—Offset 50h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR0: [BAR + 9C000h] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.16.14 reg_SAR_type (SAR1)—Offset 58h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR1: [BAR + 9C000h] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	SAR: Current Source Address of DMA transfer. Updated after each source transfer. The SINC field in the CTL_LO[n]: Control Register determines whether the address increments or is left unchanged on every source transfer throughout the block transfer. When the channel is enabled (i.e. CH_EN is 1), the read back value will reflect the updated source transfer addresses. However, when the channel is disabled, the original programmed value will be reflected when reading this register. It's important to notice the following: 1. Once the block transfer is in progress (i.e. when channel is enabled), the read-back value correlates with the OCP Read Address that one would see in an OCP tracker. 2. If the read to this register comes during a block transfer, the LAST DMA Read address sent on the OCP before the register read is what's reflected in the read-back value. 3. If the last DMA read was a burst read (i.e. burst length) 1), the read-back value reflects the first address of the burst read since this is what gets sent on the OCP fabric. 4. If the read to the register occurred after the whole block got transferred, then the channel gets disabled and the returned value would be the original programmed value. 5. Since the read-back value is OCP based, only DW aligned addresses will be reflected (i.e. OCP Byte-Enable values would not be reflected) 6. Based on the above remarks, this value should be used as pseudo DMA read progress indicator when the channel is enabled and not an absolute one. Decrementing addresses are not supported

21.16.15 reg_DAR_type (DAR1)—Offset 60h

The starting destination address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the destination address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DAR1: [BAR + 9C000h] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Diagram illustrating the structure of the 32-bit DAR field. The field is divided into eight 4-bit segments, each containing four '0' bits. The segments are labeled with bit positions 31, 28, 24, 20, 16, 12, 8, and 4 from left to right. The label 'DAR' is positioned below the first segment (bits 31-28).



21.16.17 reg_CTL_LO_type (CTL_LO1)—Offset 70h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO1: [BAR + 9C000h] + 70h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0				0				0				0				0				0				0				0				0											
RSVD				LLP_SRC_EN				RSVD1				TT_FC				RSVD2				SRC_MSIZE				DEST_MSIZE				SINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			
				LLP_DST_EN																																							

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZE: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZE: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.16.18 reg_CTL_HI_type (CTL_HI1)—Offset 74h

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI1: [BAR + 9C000h] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.16.19 reg_SSTAT_type (SSTAT1)—Offset 78h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT1: [BAR + 9C000h] + 78h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.16.20 reg_DSTAT_type (DSTAT1)—Offset 80h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT1: [BAR + 9C000h] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.16.21 reg_SSTATAR_type (SSTATAR1)—Offset 88h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR1: [BAR + 9C000h] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.

21.16.22 reg_DSTATAR_type (DSTATAR1)—Offset 90h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RW	DSTATAR: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.


21.16.23 reg_CFG_LO_type (CFG_LO1)—Offset 98h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



Intel Atom® Processor E3800 Product Family
Datasheet
3071



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.16.24 reg_CFG_HI_type (CFG_HI1)—Offset 9Ch

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI1: [BAR + 9C000h] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31		28				24				20				16				12				8				4				0																	
0 0 0 0 0		0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0																					
DST_PER_EXT		SRC_PER_EXT		WR_ISSUE_THD																		RD_ISSUE_THD																		DST_PER				SRC_PER			



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2 \wedge \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2 \wedge \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.16.25 reg_SGR_type (SGR1)—Offset A0h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR1: [BAR + 9C000h] + A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.16.26 reg_DSR_type (DSR1)—Offset A8h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR1: [BAR + 9C000h] + A8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.16.27 reg_SAR_type (SAR2)—Offset B0h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR2: [BAR + 9C000h] + B0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Intel Atom® Processor E3800 Product Family
Datasheet
3075



21.16.30 reg_CTL_LO_type (CTL_LO2)—Offset C8h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO2: [BAR + 9C000h] + C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0											
RSVD				LLP_SRC_EN				RSVD1				TT_FC				RSVD2				SRC_MSIZ				DEST_MSIZ				SINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			
				LLP_DST_EN												DST_SCATTER_EN												SRC_GATHER_EN															

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.16.31 reg_CTL_HI_type (CTL_HI2)—Offset CCh

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI2: [BAR + 9C000h] + CCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HIin, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.16.32 reg_SSTAT_type (SSTAT2)—Offset D0h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT2: [BAR + 9C000h] + D0h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.16.33 reg_DSTAT_type (DSTAT2)—Offset D8h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT2: [BAR + 9C000h] + D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.16.34 reg_SSTATAR_type (SSTATAR2)—Offset E0h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR2: [BAR + 9C000h] + E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

			31	28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
			0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

21.16.35 req_DSTATAR_type (DSTATAR2)—Offset E8h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR2: [BAR + 9C000h] + E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

			31	28				24				20				16				12				8				4				0		
			0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
			DSTATn																															
Bit Range	Default & Access	Description																																
31:0	0h RW	DSTATn: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.																																

21.16.36 reg_CFG_LO_type (CFG_LO2)—Offset F0h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO2: [BAR + 9C000h] + F0h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.16.37 reg_CFG_HI_type (CFG_HI2)—Offset F4h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI2: [BAR + 9C000h] + F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0				0				0				0				0				0				0				0				0			
DST_PER_EXT				SRC_PER_EXT				WR_ISSUE_THD				RD_ISSUE_THD				DST_PER				SRC_PER															



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2^{\wedge} \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2^{\wedge} \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.16.38 reg_SGR_type (SGR2)—Offset F8h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR2: [BAR + 9C000h] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.16.39 reg_DSR_type (DSR2)—Offset 100h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR2: [BAR + 9C000h] + 100h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.16.40 reg_SAR_type (SAR3)—Offset 108h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR3: [BAR + 9C000h] + 108h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



21.16.43 reg_CTL_LO_type (CTL_LO3)—Offset 120h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO3: [BAR + 9C000h] + 120h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0																																			
RSVD				LLP_SRC_EN				LLP_DST_EN				RSVD1				TT_FC				RSVD2				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZE				DEST_MSIZE				SINC				RSVD3				DINC				RSVD4				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZE: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZE: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.16.44 reg_CTL_HI_type (CTL_HI3)—Offset 124h

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI3: [BAR + 9C000h] + 124h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.16.45 reg_SSTAT_type (SSTAT3)—Offset 128h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT3: [BAR + 9C000h] + 128h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.16.46 reg_DSTAT_type (DSTAT3)—Offset 130h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT3: [BAR + 9C000h] + 130h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.16.47 reg_SSTATAR_type (SSTATAR3)—Offset 138h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR3: [BAR + 9C000h] + 138h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Intel Atom® Processor E3800 Product Family
Datasheet
3093



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.16.50 reg_CFG_HI_type (CFG_HI3)—Offset 14Ch

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI3: [BAR + 9C000h] + 14Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31		28				24				20				16				12				8				4				0			
0 0 0 0 0		0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0							
DST_PER_EXT		SRC_PER_EXT		WR_ISSUE_THD										RD_ISSUE_THD										DST_PER				SRC_PER					



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2 \wedge \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2 \wedge \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.16.51 reg_SGR_type (SGR3)—Offset 150h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR3: [BAR + 9C000h] + 150h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.16.52 reg_DSR_type (DSR3)—Offset 158h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR3: [BAR + 9C000h] + 158h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.16.53 reg_SAR_type (SAR4)—Offset 160h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR4: [BAR + 9C000h] + 160h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



	31	28	24	20	16	12	8	4	0
	0	0	0	0	0	0	0	0	0
DAR	0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Description
31:0	0h RW	DAR: Current Destination Address of DMA transfer. Updated after each destination transfer. The DINC field in the CTL_LO[n]: Control Register determines whether the address increments or is left unchanged on every destination transfer throughout the block transfer. When the channel is enabled (i.e. CH_EN is 1), the read back value will reflect the updated destination transfer addresses. However, when the channel is disabled, the original programmed value will be reflected when reading this register. It's important to notice the following: 1. Once the block transfer is in progress (i.e. when channel is enabled), the read-back value correlates with the OCP Write Address that one would see in an OCP tracker. 2. If the read to this register comes during a block transfer, the LAST DMA Write address sent on the OCP before the register read is what's reflected in the read-back value. 3. If the last DMA write was a burst write (i.e. burst length = 1), the read-back value reflects the first address of the burst write since this is what gets sent on the OCP fabric. 4. If the read to the register occurred after the whole block got transferred, then the channel gets disabled and the returned value would be the original programmed value. 5. Since the read-back value is OCP based, only DW aligned addresses will be reflected (i.e. OCP Byte-Enable values would not be reflected) 6. Based on the above remarks, this value should be used as pseudo DMA write progress indicator when the channel is enabled and not an absolute one. Decrementing addresses are not supported

21.16.55 reg_LLQ_type (LLP4)—Offset 170h

Note: You need to program this register to point to the first Linked List Item (LLI) in memory prior to enabling the channel if block chaining is enabled. The LLP register has two functions: The logical result of the equation $LLP.LOC \neq 0$ is used to set up the type of DMA transfer—single or multi-block. Table shows how the method of updating the channel registers is a function of $LLP.LOC \neq 0$. If $LLP.LOC$ is set to 0x0, then transfers using linked lists are not enabled. This register must be programmed prior to enabling the channel in order to set up the transfer type. $LLP.LOC \neq 0$ contains the pointer to the next LLI for block chaining using linked lists. The LLPx register can also point to the address where write-back of the control and source/destination status information occur after block completion.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

LLP4: [BAR + 9C000h] + 170h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LOC								RSVD2

Bit Range	Default & Access	Description
31:2	00000000h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled. Note that the two LSBs of the starting address are not stored because the address is assumed to be aligned to a 32-bit boundary. LLI accesses are always 32-bit accesses and cannot be changed or programmed to anything other than 32-bit.
1:0	0h RO	RSVD2: Reserved



21.16.56 reg_CTL_LO_type (CTL_LO4)—Offset 178h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO4: [BAR + 9C000h] + 178h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD	LLP_SRC_EN	LLP_DST_EN	RSVD1	TT_FC	RSVD2	DST_SCATTER_EN	SRC_GATHER_EN	SRC_MSIZ
						DEST_MSIZ	SINC	RSVD3
						DINC	RSVD4	SRC_TR_WIDTH
								DST_TR_WIDTH
								INT_EN

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.16.57 reg_CTL_HI_type (CTL_HI4)—Offset 17Ch

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI4: [BAR + 9C000h] + 17Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.16.58 reg_SSTAT_type (SSTAT4)—Offset 180h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT4: [BAR + 9C000h] + 180h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.16.59 reg_DSTAT_type (DSTAT4)—Offset 188h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT4: [BAR + 9C000h] + 188h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.16.60 reg_SSTATAR_type (SSTATAR4)—Offset 190h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR4: [BAR + 9C000h] + 190h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

[illegible]

21.16.61 req_DSTATAR_type (DSTATAR4)—Offset 198h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR4: [BAR + 9C000h] + 198h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

			31	28				24				20				16				12				8				4				0		
			0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
			DSTATn																															
Bit Range	Default & Access	Description																																
31:0	0h RW	DSTATn: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.																																

21.16.62 reg_CFG_LO_type (CFG_LO4)—Offset 1A0h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO4: [BAR + 9C000h] + 1A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.16.63 reg_CFG_HI_type (CFG_HI4)—Offset 1A4h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI4: [BAR + 9C000h] + 1A4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0							
DST_PER_EXT				SRC_PER_EXT				WR_ISSUE_THD								RD_ISSUE_THD								DST_PER				SRC_PER							



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2^{\wedge} \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2^{\wedge} \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.16.64 reg_SGR_type (SGR4)—Offset 1A8h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR4: [BAR + 9C000h] + 1A8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.16.65 reg_DSR_type (DSR4)—Offset 1B0h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR4: [BAR + 9C000h] + 1B0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.16.66 reg_SAR_type (SAR5)—Offset 1B8h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR5: [BAR + 9C000h] + 1B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



21.16.69 reg_CTL_LO_type (CTL_LO5)—Offset 1D0h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO5: [BAR + 9C000h] + 1D0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0																																			
RSVD				LLP_SRC_EN				LLP_DST_EN				RSVD1				TT_FC				RSVD2				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZ				DEST_MSIZ				SINC				RSVD3				DINC				RSVD4				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.16.70 reg_CTL_HI_type (CTL_HI5)—Offset 1D4h

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI5: [BAR + 9C000h] + 1D4h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.16.71 reg_SSTAT_type (SSTAT5)—Offset 1D8h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT5: [BAR + 9C000h] + 1D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.16.72 reg_DSTAT_type (DSTAT5)—Offset 1E0h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT5: [BAR + 9C000h] + 1E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.16.73 reg_SSTATAR_type (SSTATAR5)—Offset 1E8h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR5: [BAR + 9C000h] + 1E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.

21.16.74 reg_DSTATAR_type (DSTATAR5)—Offset 1F0h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

DSTATAR5: [BAR + 9C000h] + 1F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RW	DSTATAR: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.

21.16.75 reg_CFG_LO_type (CFG_LO5)—Offset 1F8h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel


Access Method

CFG_LO5: [BAR + 9C000h] + 1F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



Intel Atom® Processor E3800 Product Family
Datasheet
3115



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.16.76 reg_CFG_HI_type (CFG_HI5)—Offset 1FCh

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI5: [BAR + 9C000h] + 1FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0				0				0				0				0				0				0				0				0			
DST_PER_EXT				SRC_PER_EXT				WR_ISSUE_THD								RD_ISSUE_THD								DST_PER				SRC_PER							



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2 \wedge \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2 \wedge \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.16.77 reg_SGR_type (SGR5)—Offset 200h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR5: [BAR + 9C000h] + 200h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.16.78 reg_DSR_type (DSR5)—Offset 208h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR5: [BAR + 9C000h] + 208h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.16.79 reg_SAR_type (SAR6)—Offset 210h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAR6: [BAR + 9C000h] + 210h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Intel Atom® Processor E3800 Product Family
Datasheet
3119



21.16.82 reg_CTL_LO_type (CTL_LO6)—Offset 228h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO6: [BAR + 9C000h] + 228h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0											
RSVD				LLP_SRC_EN				RSVD1				TT_FC				RSVD2				SRC_MSIZ				DEST_MSIZ				SINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			
				LLP_DST_EN												DST_SCATTER_EN												SRC_GATHER_EN															

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZ: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZ: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.16.83 reg_CTL_HI_type (CTL_HI6)—Offset 22Ch

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI6: [BAR + 9C000h] + 22Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.16.84 reg_SSTAT_type (SSTAT6)—Offset 230h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT6: [BAR + 9C000h] + 230h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.16.85 reg_DSTAT_type (DSTAT6)—Offset 238h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT6: [BAR + 9C000h] + 238h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.16.86 reg_SSTATAR_type (SSTATAR6)—Offset 240h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR6: [BAR + 9C000h] + 240h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



312824201612840																															
000																															

21.16.87 req_DSTATAR_type (DSTATAR6)—Offset 248h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR6: [BAR + 9C000h] + 248h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

312824201612840 0 0 0 00 0 0 0 00 0 0 0 00 0 0 0 00 0 0 0 00 0 0 0 00 0 0 0 0															
DSTATn															
Bit Range	Default & Access	Description													
31:0	0h RW	DSTATn: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.													

21.16.88 reg_CFG_LO_type (CFG_LO6)—Offset 250h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO6: [BAR + 9C000h] + 250h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.16.89 reg_CFG_HI_type (CFG_HI6)—Offset 254h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


CFG_HI6: [BAR + 9C000h] + 254h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31		28		24		20		16		12		8		4		0			
0		0		0		0		0		0		0		0		0			
DST_PER_EXT		SRC_PER_EXT		WR_ISSUE_THD						RD_ISSUE_THD						DST_PER		SRC_PER	



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2^{\wedge} \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2^{\wedge} \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.16.90 reg_SGR_type (SGR6)—Offset 258h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR6: [BAR + 9C000h] + 258h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



21.16.95 reg_CTL_LO_type (CTL_LO7)—Offset 280h

This register contains fields that control the DMA transfer. The CTL_LO register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_LO7: [BAR + 9C000h] + 280h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0																																			
RSVD				LLP_SRC_EN				LLP_DST_EN				RSVD1				TT_FC				RSVD2				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZE				DEST_MSIZE				SINC				RSVD3				DINC				RSVD4				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Description
31:29	0h RO	RSVD: Reserved
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPn.LOC is non-zero and (LLP_EN == 1)
26:22	0h RO	RSVD1: RSVD
21:20	0h RW	TT_FC: Transfer Type and Flow Control. The following transfer types are supported. Memory to Memory (00) Memory to Peripheral (01) Peripheral to Memory (10) Peripheral to Peripheral (11) Flow Control is always assigned to the DMA.
19	0h RO	RSVD2: Reserved
18	0h RW	DST_SCATTER_EN: Destination scatter enable bit: 0 = Scatter disabled 1 = Scatter enabled Scatter on the destination side is applicable only when the CTL_LOn.DINC bit indicates an incrementing address control.
17	0h RW	SRC_GATHER_EN: Source gather enable bit: 0 = Gather disabled 1 = Gather enabled Gather on the source side is applicable only when the CTL_LOn.SINC bit indicates an incrementing address control.
16:14	0h RW	SRC_MSIZE: Source Burst Transaction Length. Number of data items, each of width CTL_LOn.SRC_TR_WIDTH, to be read from the source. TABLE 5-1 talks about the encoding for this field.
13:11	0h RW	DEST_MSIZE: Destination Burst Transaction Length. Number of data items, each of width CTL_LOn.DST_TR_WIDTH, to be written to the destination. TABLE 5-1 talks about the encoding for this field.
10	0h RW	SINC: Source Address Increment. Indicates whether to increment or decrement the source address on every source transfer. If the device is fetching data from a source peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No Change)



Bit Range	Default & Access	Description
9	0h RO	RSVD3: Reserved
8	0h RW	DINC: Destination Address Increment. Indicates whether to increment or decrement the destination address on every destination transfer. If your device is writing data to a destination peripheral FIFO with a fixed address, then set this field to No change. 0 = Increment 1 = Fixed (No change)
7	0h RO	RSVD4: Reserved
6:4	0h RW	SRC_TR_WIDTH: Source Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
3:1	0h RW	DST_TR_WIDTH: Destination Transfer Width. BURST_SIZE = (2 ^ MSIZE) 1. Transferred Bytes Per Burst = (BURST_SIZE * TR_WIDTH) 2. For incrementing addresses and (Transfer_Width (4 Bytes), the MSIZE parameter is ignored since only single transactions are supported (due to OCP limitations) Table 5-2 lists the decoding for this field. For a non-memory peripheral, this is typically the peripheral (source) FIFO width.
0	0h RW	INT_EN: Interrupt Enable Bit. If set, then all interrupt-generating sources are enabled.

21.16.96 reg_CTL_HI_type (CTL_HI7)—Offset 284h

This register contains fields that control the DMA transfer. The CTL_HI register is part of the block descriptor (linked list item - LLI) when block chaining is enabled. It can be varied on a block-by-block basis within a DMA transfer when block chaining is enabled. If status write-back is enabled, CTL_HI is written to then control registers location of the LLI in system memory at the end of the block transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CTL_HI7: [BAR + 9C000h] + 284h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH_CLASS	CH_WEIGHT				DONE	BLOCK_TS		

Bit Range	Default & Access	Description
31:29	0h RW	CH_CLASS: Channel Class. A Class of (N_CHNLS-1) is the highest priority, and 0 is the lowest. This field must be programmed within 0 to (N_CHNLS-1). A programmed value outside this range will cause erroneous behavior. ** See restriction in CH_WEIGHT below



Bit Range	Default & Access	Description
28:18	0h RW	CH_WEIGHT: Channel Weight : Value of K assigns a weight of (K+1) in the round-robin arbitration between channels of the same class. A value of 0x7FF assigns an arbitration weight of 2048. Since K is from 0 to $(2^{11}-1)=2047$, Arbitration Weight ranges from 1 to 2048 **Restrictions : 1. CH_CLASS and CH_WEIGHT cannot be changed on the fly. Changes to either values for ANY channel require that ALL channels be quiescent in order to propagate those changes to the read and write arbiters without affecting their functionality. 2. Another possible way of achieving the quiescence requirement is to suspend ALL channels before changing the CH_CLASS and CH_WEIGHT. 3. Caution must be taken in descriptor-based (linked-list) multi-block transfers since the LLI.CTL_HI is one of the DW that needs to be read and loaded into the CTL_HI internal register. Hence, user needs to ensure that the CH_CLASS and CH_WEIGHT fields do not change from one descriptor to another nor do they disturb the aforementioned quiescence requirement.
17	0h RW	DONE: If status write-back is enabled, the upper word of the control register, CTL_HI, is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTL_HI.DONE bit to see when a block transfer is complete. The LLI CTL_HI.DONE bit should be cleared when the linked lists are set up in memory prior to enabling the channel. The DMA will not transfer the block if the DONE bit in the LLI is not cleared.
16:0	0h RW	BLOCK_TS: Block Transfer Size (in Bytes). Since the DMA is always the flow controller, the user needs to write this field before the channel is enabled in order to indicate the block size. The number programmed into BLOCK_TS indicates the total number of bytes to transfer for every block transfer. Once the transfer starts (i.e. channel is enabled), the read-back value is the total number of bytes for which Read Commands have already been sent to the source. It doesn't mean Bytes that are already in the FIFO. However, when the channel is disabled, the original programmed value will be reflected when reading this register. Theoretical Byte Size range is from 0 to $(2^{17}-1) = (128\text{ KB} - 1)$.

21.16.97 reg_SSTAT_type (SSTAT7)—Offset 288h

After each block transfer completes, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register. This status information is then stored in the SSTATx register and written out to the SSTATx register location of the LLI before the start of the next block. Note : This register is a temporary placeholder for the source status information on its way to the SSTATx register location of the LLI. The source status information should be retrieved by software from the SSTATx register location of the LLI, and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTAT7: [BAR + 9C000h] + 288h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTAT



Bit Range	Default & Access	Description
31:0	0h RW	SSTAT: Source status information retrieved by hardware from the address pointed to by the contents of the Source Status Address Register. This register is a temporary placeholder for the source status information on its way to the SSTATn register location of the LLI. The source status information should be retrieved by software from the SSTATn register location of the LLI, and not by a read of this register over the DMA slave interface.

21.16.98 reg_DSTAT_type (DSTAT7)—Offset 290h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI. Note : This register is a temporary placeholder for the destination status information on its way to the DSTATx register location of the LLI. The destination status information should be retrieved by software from the DSTATx register location of the LLI and not by a read of this register over the DMA slave interface.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTAT7: [BAR + 9C000h] + 290h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Description
31:0	0h RW	DSTAT: Destination status information retrieved by hardware from the address pointed to by the contents of the Destination Status Address Register. This register is a temporary placeholder for the destination status information on its way to the DSTATn register location of the LLI. The destination status information should be retrieved by software from the DSTATn register location of the LLI and not by a read of this register over the DMA slave interface.

21.16.99 reg_SSTATAR_type (SSTATAR7)—Offset 298h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SSTATAR7: [BAR + 9C000h] + 298h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0h RW	SSTATAR: Pointer from where hardware can fetch the source status information, which is registered in the SSTATn register and written out to the SSTATn register location of the LLI before the start of the next block.

21.16.100 reg_DSTATAR_type (DSTATAR7)—Offset 2A0h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSTATAR7: [BAR + 9C000h] + 2A0h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Description
31:0	0h RW	DSTATAR: Pointer from where hardware can fetch the destination status information, which is registered in the DSTATn register and written out to the DSTATn register location of the LLI before the start of the next block.

21.16.101 reg_CFG_LO_type (CFG_LO7)—Offset 2A8h

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_LO7: [BAR + 9C000h] + 2A8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000203h



Intel Atom® Processor E3800 Product Family
Datasheet
3137



Bit Range	Default & Access	Description
8	0h RW	CH_SUSP: Channel Suspend. Suspends all DMA data transfers from the source until this bit is cleared. There is no guarantee that the current transaction will complete. Can also be used in conjunction with CFGx.FIFO_EMPTY to cleanly disable a channel without losing any data. 0 = Not suspended. 1 = Suspend DMA transfer from the source.
7	0h RW	SS_UPD_EN: Source Status Update Enable. Source status information is fetched only from the location pointed to by the SSTATARn register, stored in the SSTATn register and written out to the SSTATn location of the LLI if SS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
6	0h RW	DS_UPD_EN: Destination Status Update Enable. Destination status information is fetched only from the location pointed to by the DSTATARn register, stored in the DSTATn register and written out to the DSTATn location of the LLI if DS_UPD_EN is high. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
5	0h RW	CTL_HI_UPD_EN: CTL_HI Update Enable. If set, the CTL_HI register is written out to the CTL_HI location of the LLI. This bit is ignored if (LLP_EN == 0) or (LLP_WB_EN == 0)
4	0h RO	RSVD_4_4: Reserved
3	0h RW	HSHAKE_NP_WR: 0x1 : Issues Non-Posted writes on HW-Handshake on DMA Write Port 0x0 : Issues Posted writes on HW-Handshake on DMA Write Port (Except end-of-block writes which will be Non-Posted)
2	0h RW	ALL_NP_WR: 0x1 : Forces ALL writes to be Non-Posted on DMA Write Port 0x0 : Non-Posted Writes will only be used at end of block transfers and in HW-Handshake (if HW_NP_WR=1); for all other cases, Posted Writes will be used.
1	1h RW	SRC_BURST_ALIGN: 0x1 : SRC Burst Transfers are broken at a Burst Length aligned boundary 0x0 : SRC Burst Transfers are not broken at a Burst Length aligned boundary
0	1h RW	DST_BURST_ALIGN: 0x1 : DST Burst Transfers are broken at a Burst Length aligned boundary 0x0 : DST Burst Transfers are not broken at a Burst Length aligned boundary

21.16.102 reg_CFG_HI_type (CFG_HI7)—Offset 2ACh

This register contains fields that configure the DMA transfer. The channel configuration register remains fixed for all blocks of a multi-block transfer. This Register should be programmed to enabling the channel

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CFG_HI7: [BAR + 9C000h] + 2ACh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31		28				24				20				16				12				8				4				0			
0 0 0 0 0		0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0				0 0 0 0 0							
DST_PER_EXT		SRC_PER_EXT		WR_ISSUE_THD										RD_ISSUE_THD										DST_PER				SRC_PER					



Bit Range	Default & Access	Description
31:30	0h RW	DST_PER_EXT: Destination Peripheral Extension : This 2-bit field is used to extend the DST_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall destination peripheral ID becomes DST_PER_EXT[1:0], DST_PER[3:0] which covers the (0-63) range.
29:28	0h RW	SRC_PER_EXT: Source Peripheral Extension : This 2-bit field is used to extend the SRC_PER field below beyond the Synopsys limit of (0-15) to accommodate additional hardware handshaking interfaces (16-63). In other words, the overall source peripheral ID becomes SRC_PER_EXT[1:0], SRC_PER[3:0] which covers the (0-63) range.
27:18	0h RW	WR_ISSUE_THD: Write Issue Threshold. Used to relax the issue criterion for Writes (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Write burst size = $(2 \wedge \text{DST_MSIZE}) * \text{TW}$.
17:8	0h RW	RD_ISSUE_THD: Read Issue Threshold. Used to relax the issue criterion for Reads (Refer to Section 4.1.1.4). Value ranges from 0 to $(2^{10}-1 = 1023)$ but should not exceed maximum Read burst size = $(2 \wedge \text{SRC_MSIZE}) * \text{TW}$.
7:4	0h RW	DST_PER: Destination Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the destination of channel n. The channel can then communicate with the destination peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS
3:0	0h RW	SRC_PER: Source Peripheral ID : Assigns a hardware handshaking interface (0 - 15) to the source of channel n. The channel can then communicate with the source peripheral connected to that interface through the assigned hardware handshaking interface. NOTE: For correct DMA operation, only one peripheral (source or destination) should be assigned to the same handshaking interface. For more details on mapping please refer to 3.5.3 HARDWARE HANDSHAKE INTERFACE MAPPING TO DMA CHANNELS

21.16.103 reg_SGR_type (SGR7)—Offset 2B0h

The Source Gather register contains two fields: Source gather count field (SGRx.SGC). Specifies the number of contiguous source transfers of CTLx.SRC_TR_WIDTH between successive gather intervals. This is defined as a gather boundary. Source gather interval field (SGRx.SGI). Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer. The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SGR7: [BAR + 9C000h] + 2B0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				



Bit Range	Default & Access	Description
31:20	0h RW	SGC: Source gather count. Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	SGI: Source gather interval.

21.16.104 reg_DSR_type (DSR7)—Offset 2B8h

The Destination Scatter register contains two fields: Destination scatter count field (DSRx.DSC) . Specifies the number of contiguous destination transfers of CTLx.DST_TR_WIDTH between successive scatter boundaries. Destination scatter interval field (DSRx.DSI) . Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary when scatter mode is enabled for the destination transfer. The CTLx.DINC field controls whether the address increments or decrements. When the CTLx.DINC field indicates a fixed address control, then the address remains constant throughout the transfer and the DSRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

DSR7: [BAR + 9C000h] + 2B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Description
31:20	0h RW	DSC: Destination scatter count. Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	DSI: Destination scatter interval.

21.16.105 reg_Raw_type (RawTfr)—Offset 2C0h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

RawTfr: [BAR + 9C000h] + 2C0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							RAW	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	RAW: Raw interrupt status

21.16.106 reg_Raw_type (RawBlock)—Offset 2C8h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RawBlock: [BAR + 9C000h] + 2C8h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							RAW	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	RAW: Raw interrupt status



21.16.107 reg_Raw_type (RawSrcTran)—Offset 2D0h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RawSrcTran: [BAR + 9C000h] + 2D0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							RAW	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	RAW: Raw interrupt status

21.16.108 reg_Raw_type (RawDstTran)—Offset 2D8h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RawDstTran: [BAR + 9C000h] + 2D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
RSVD																				RAW															

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	RAW: Raw interrupt status

21.16.109 reg_Raw_type (RawErr)—Offset 2E0h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel, for example, RawTfr(2) is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers. The following RAW registers are available in the DMA RawTfr - Raw Status for Transfer Interrupts RawBlock - Raw Status for Block Interrupts Register RawSrcTran - Raw Status for Source Transaction Interrupts Register RawDstTran - Raw Status for Destination Transaction Interrupts Register RawErr - Raw Status for Error Interrupts Register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RawErr: [BAR + 9C000h] + 2E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

312824201612840																															
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0																															
RSVD																								RAW							

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	RAW: Raw interrupt status

21.16.110 reg_Status_type (StatusTfr)—Offset 2E8h

All interrupt events from all channels are stored in these Interrupt Status registers after masking: `statusBlock`, `StatusDstTran`, `StatusErr`, `StatusSrcTran`, and `StatusTfr`. Each Interrupt Status register has a bit allocated per channel, for example, `StatusTfr(2)` is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (`int` or `int_n` bus, depending on interrupt polarity) leaving the DMA.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

StatusTfr: [BAR + 9C000h] + 2E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							STATUS	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	STATUS: Interrupt status

21.16.111 reg_Status_type (StatusBlock)—Offset 2F0h

All interrupt events from all channels are stored in these Interrupt Status registers after masking: statusBlock, StatusDstTran, StatusErr, StatusSrcTran, and StatusTfr. Each Interrupt Status register has a bit allocated per channel, for example, StatusTfr(2) is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (int or int_n bus, depending on interrupt polarity) leaving the DMA.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

StatusBlock: [BAR + 9C000h] + 2F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							STATUS	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	STATUS: Interrupt status



21.16.112 reg_Status_type (StatusSrcTran)—Offset 2F8h

All interrupt events from all channels are stored in these Interrupt Status registers after masking: statusBlock, StatusDstTran, StatusErr, StatusSrcTran, and StatusTfr. Each Interrupt Status register has a bit allocated per channel, for example, StatusTfr(2) is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (int or int_n bus, depending on interrupt polarity) leaving the DMA.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

StatusSrcTran: [BAR + 9C000h] + 2F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD								STATUS

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	STATUS: Interrupt status

21.16.113 reg_Status_type (StatusDstTran)—Offset 300h

All interrupt events from all channels are stored in these Interrupt Status registers after masking: statusBlock, StatusDstTran, StatusErr, StatusSrcTran, and StatusTfr. Each Interrupt Status register has a bit allocated per channel, for example, StatusTfr(2) is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (int or int_n bus, depending on interrupt polarity) leaving the DMA.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

StatusDstTran: [BAR + 9C000h] + 300h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD								STATUS



All interrupt events from all channels are stored in these Interrupt Status registers after masking: `statusBlock`, `StatusDstTran`, `StatusErr`, `StatusSrcTran`, and `StatusTfr`. Each Interrupt Status register has a bit allocated per channel, for example, `StatusTfr(2)` is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (`int` or `int_n` bus, depending on interrupt polarity) leaving the DMA.

Type: Memory Mapped I/O Register
(Size: 32 bits)

StatusErr: [BAR + 9C000h] + 308h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD						STATUS		

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	STATUS: Interrupt status

21.16.115 reg_Mask_type (MaskTfr)—Offset 310h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel, for example, MaskTfr(2) is the mask bit for the Channel 2 transfer complete interrupt. When the source peripheral of DMA channel i is memory, then the source transaction complete interrupt, MaskSrcTran(i), must be masked to prevent an erroneous triggering of an interrupt on the int_combined signal. Similarly, when the destination peripheral of DMA channel i is memory, then the destination transaction complete interrupt, MaskDstTran(i), must be masked to prevent an erroneous triggering of an interrupt on the int_combined(_n) signal. A channel INT_MASK bit will be written only if the corresponding mask write enable bit in the INT_MASK_WE field is asserted on the same OCP write transfer. This allows software to set a mask bit without performing a read-modified write operation. For example, writing hex 01x1 to the MaskTfr register writes a 1 into MaskTfr(0), while MaskTfr(7:1) remains unchanged. Writing hex 00xx leaves MaskTfr(7:0) unchanged.



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2				INT_MASK_WE				INT_MASK

Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	INT_MASK_WE: Interrupt Mask Write Enable 0 = write disabled 1 = write enabled
7:0	0h RW	INT_MASK: Interrupt mask 0-mask 1-unmask

21.16.117 reg_Mask_type (MaskSrcTran)—Offset 320h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel, for example, MaskTfr(2) is the mask bit for the Channel 2 transfer complete interrupt. When the source peripheral of DMA channel *i* is memory, then the source transaction complete interrupt, MaskSrcTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined signal. Similarly, when the destination peripheral of DMA channel *i* is memory, then the destination transaction complete interrupt, MaskDstTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined(_n) signal. A channel INT_MASK bit will be written only if the corresponding mask write enable bit in the INT_MASK_WE field is asserted on the same OCP write transfer. This allows software to set a mask bit without performing a read-modified write operation. For example, writing hex 01x1 to the MaskTfr register writes a 1 into MaskTfr(0), while MaskTfr(7:1) remains unchanged. Writing hex 00xx leaves MaskTfr(7:0) unchanged. Writing a 1 to any bit in these registers unmask the corresponding interrupt, thus allowing the DMA to set the appropriate bit in the Status registers and int_* port signals.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MaskSrcTran: [BAR + 9C000h] + 320h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2				INT_MASK_WE				INT_MASK



Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	INT_MASK_WE: Interrupt Mask Write Enable 0 = write disabled 1 = write enabled
7:0	0h RW	INT_MASK: Interrupt mask 0-mask 1-unmask

21.16.118 reg_Mask_type (MaskDstTran)—Offset 328h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel, for example, MaskTfr(2) is the mask bit for the Channel 2 transfer complete interrupt. When the source peripheral of DMA channel *i* is memory, then the source transaction complete interrupt, MaskSrcTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined signal. Similarly, when the destination peripheral of DMA channel *i* is memory, then the destination transaction complete interrupt, MaskDstTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined(_n) signal. A channel INT_MASK bit will be written only if the corresponding mask write enable bit in the INT_MASK_WE field is asserted on the same OCP write transfer. This allows software to set a mask bit without performing a read-modified write operation. For example, writing hex 01x1 to the MaskTfr register writes a 1 into MaskTfr(0), while MaskTfr(7:1) remains unchanged. Writing hex 00xx leaves MaskTfr(7:0) unchanged. Writing a 1 to any bit in these registers unmask the corresponding interrupt, thus allowing the DMA to set the appropriate bit in the Status registers and int_* port signals.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MaskDstTran: [BAR + 9C000h] + 328h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2				INT_MASK_WE			INT_MASK	

Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	INT_MASK_WE: Interrupt Mask Write Enable 0 = write disabled 1 = write enabled
7:0	0h RW	INT_MASK: Interrupt mask 0-mask 1-unmask



21.16.119 reg_Mask_type (MaskErr)—Offset 330h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel, for example, MaskTfr(2) is the mask bit for the Channel 2 transfer complete interrupt. When the source peripheral of DMA channel *i* is memory, then the source transaction complete interrupt, MaskSrcTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined signal. Similarly, when the destination peripheral of DMA channel *i* is memory, then the destination transaction complete interrupt, MaskDstTran(*i*), must be masked to prevent an erroneous triggering of an interrupt on the int_combined(_n) signal. A channel INT_MASK bit will be written only if the corresponding mask write enable bit in the INT_MASK_WE field is asserted on the same OCP write transfer. This allows software to set a mask bit without performing a read-modified write operation. For example, writing hex 01x1 to the MaskTfr register writes a 1 into MaskTfr(0), while MaskTfr(7:1) remains unchanged. Writing hex 00xx leaves MaskTfr(7:0) unchanged. Writing a 1 to any bit in these registers unmask the corresponding interrupt, thus allowing the DMA to set the appropriate bit in the Status registers and int_* port signals.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MaskErr: [BAR + 9C000h] + 330h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD2				INT_MASK_WE				INT_MASK

Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	INT_MASK_WE: Interrupt Mask Write Enable 0 = write disabled 1 = write enabled
7:0	0h RW	INT_MASK: Interrupt mask 0-mask 1-unmask

21.16.120 reg_Clear_type (ClearTfr)—Offset 338h

Each bit in the Raw Status and Status registers is cleared on the same cycle by writing a 1 to the corresponding location in the Clear registers: ClearBlock, ClearDstTran, ClearErr, ClearSrcTran, and ClearTfr. Each Interrupt Clear register has a bit allocated per channel, for example, ClearTfr(2) is the clear bit for the Channel 2 transfer complete interrupt. Writing a 0 has no effect. These registers are not readable.

Access Method



21.16.122 reg_Clear_type (ClearSrcTran)—Offset 348h

Each bit in the Raw Status and Status registers is cleared on the same cycle by writing a 1 to the corresponding location in the Clear registers: ClearBlock, ClearDstTran, ClearErr, ClearSrcTran, and ClearTfr. Each Interrupt Clear register has a bit allocated per channel, for example, ClearTfr(2) is the clear bit for the Channel 2 transfer complete interrupt. Writing a 0 has no effect. These registers are not readable.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ClearSrcTran: [BAR + 9C000h] + 348h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							CLEAR	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h WO	CLEAR: Interrupt clear. 0 = no effect 1 = clear interrupt

21.16.123 reg_Clear_type (ClearDstTran)—Offset 350h

Each bit in the Raw Status and Status registers is cleared on the same cycle by writing a 1 to the corresponding location in the Clear registers: ClearBlock, ClearDstTran, ClearErr, ClearSrcTran, and ClearTfr. Each Interrupt Clear register has a bit allocated per channel, for example, ClearTfr(2) is the clear bit for the Channel 2 transfer complete interrupt. Writing a 0 has no effect. These registers are not readable.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ClearDstTran: [BAR + 9C000h] + 350h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD							CLEAR	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved



Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD2				CH_EN_WE				CH_EN

Bit Range	Default & Access	Description
31:16	0h RO	RSVD2: Reserved
15:8	0h WO	CH_EN_WE: Channel enable write enable.
7:0	0h RW	CH_EN: Enables/Disables the channel. Setting this bit enables a channel, clearing this bit disables the channel. 0 = Disable the Channel 1 = Enable the Channel The ChEnReg.CH_EN bit is automatically cleared by hardware to disable the channel after the last OCP transfer of the DMA transfer to the destination has completed. Software can therefore poll this bit to determine when this channel is free for a new DMA transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ClassPriority0_LO: [BAR + 9C000h] + 3B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD2				WT_CLASS_1				WT_CLASS_0

Bit Range	Default & Access	Description
31:22	0h RO	RSVD2: Reserved

21.16.129 reg_CLASS_PRIORITY0_HI_type (ClassPriority0_HI)—Offset 3BCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ClassPriority0_HI: [BAR + 9C000h] + 3BCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD1				STRICT_PRI	WT_CLASS_3			WT_CLASS_2

Bit Range	Default & Access	Description
31:23	0h RO	RSVD1: Reserved
22	0h RW	STRICT_PRI: If set, Higher class values will always have higher priorities than lower class values. If not set, round-robin arbitration will be used between different classes using WT_CLASS_n values.
21:11	0h RW	WT_CLASS_3: Class Weight 3: Value of K assigns a weight of (K+1) to Class 3. Since K is from 0 to (2 ¹¹ -1)=2047, Arbitration Class Weight ranges from 1 to 2048 bytes.
10:0	0h RW	WT_CLASS_2: Class Weight 2: Value of K assigns a weight of (K+1) to Class 2. Since K is from 0 to (2 ¹¹ -1)=2047, Arbitration Class Weight ranges from 1 to 2048 bytes.

21.16.130 reg_CLASS_PRIORITY1_LO_type (ClassPriority1_LO)—Offset 3C0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ClassPriority1_LO: [BAR + 9C000h] + 3C0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD2			WT_CLASS_5			WT_CLASS_4		

Bit Range	Default & Access	Description
31:22	0h RO	RSVD2: Reserved
21:11	0h RW	WT_CLASS_5: Class Weight 5: Value of K assigns a weight of (K+1) to Class 5. Since K is from 0 to (2^11-1)=2047, Arbitration Class Weight ranges from 1 to 2048 bytes.
10:0	0h RW	WT_CLASS_4: Class Weight 4: Value of K assigns a weight of (K+1) to Class 4. Since K is from 0 to (2^11-1)=2047, Arbitration Class Weight ranges from 1 to 2048 bytes.



Type: Memory Mapped I/O Register
(Size: 32 bits)

FifoPartition0_LO: [BAR + 9C000h] + 400h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD2	PARTITION_UPDATE	PSIZE_CH_1	PSIZE_CH_0					

Bit Range	Default & Access	Description
31:27	0h RO	RSVD2: Reserved
26	0h RW	PARTITION_UPDATE: SW needs to write to this bit for the partitioning assignments to take effect.
25:13	0h RW	PSIZE_CH_1: Partition Byte Size assigned to Channel 1. Ranges from 0 Bytes to (2 ¹³ - 1)=8191 Bytes. However, size needs to be DW Aligned, i.e. a multiple of 4.
12:0	0h RW	PSIZE_CH_0: Partition Byte Size assigned to Channel 0. Ranges from 0 Bytes to (2 ¹³ - 1)=8191 Bytes. However, size needs to be DW Aligned, i.e. a multiple of 4.

21.16.133 reg_FIFO_PARTITION0_HI_type (FifoPartition0_HI)—Offset 404h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

FifoPartition0_HI: [BAR + 9C000h] + 404h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD1	PSIZE_CH_3	PSIZE_CH_2						

Bit Range	Default & Access	Description
31:26	0h RO	RSVD1: Reserved
25:13	0h RW	PSIZE_CH_3: Partition Byte Size assigned to Channel 3. Ranges from 0 Bytes to (2 ¹³ - 1)=8191 Bytes. However, size needs to be DW Aligned, i.e. a multiple of 4.

21.16.136 req SAI Error type (SAI_ERR)—Offset 410h

Bit Range	Default & Access	Description
31:26	0h RO	RSVD1: Reserved
25:13	0h RW	PSIZE_CH_7: Partition Byte Size assigned to Channel 7. Ranges from 0 Bytes to (2^13 - 1)=8191 Bytes. However, size needs to be DW Aligned, i.e. a multiple of 4.
12:0	0h RW	PSIZE_CH_6: Partition Byte Size assigned to Channel 6. Ranges from 0 Bytes to (2^13 - 1)=8191 Bytes. However, size needs to be DW Aligned, i.e. a multiple of 4.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SAI_ERR: [BAR + 9C000h] + 410h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD							CH_SAI_ERR	

Bit Range	Default & Access	Description
31:8	0h RO	RSVD: Reserved
7:0	0h RO	CH_SAI_ERR: 1: SAI Error occurred on Ch [n] 0: No SAI Error occurred on Ch [n] SAI_ERROR[n] is set by HW on SAI violation for channel [n]. All bits get cleared by SW when reading this register

21.16.137 reg_GLOBAL_CFG_type (GLOBAL_CFG)—Offset 418h

GLOBAL_CFG: GLOBAL DMA Configuration Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GLOBAL_CFG: [BAR + 9C000h] + 418h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:21, F:0] + 10h

Default: 00000000h

	31	28	24	20	16	12	8	4	0	
	0	0	0	0	0	0	0	0	0	ERR_ILL_REG
SCRATCH_PAD										



Bit Range	Default & Access	Description
31:1	0h RW	SCRATCH_PAD: This field will have all bits with R/W attribute to be used for future configuration and de-feature bits.
0	0b RW	ERR_ILL_REG: 0x1 : Issue ERR response on reading illegal (non-existing) registers 0x0 : Issue DVA response on reading illegal (non-existing) registers



22 Intel® Trusted Execution Engine (TXE)

This section describes the security components and capabilities of the Intel® Trusted Execution Engine (TXE) security co-processor.

Note: TXE firmware is required on the Bay Trail Platform as part of the PCU SPI flash image. PCU SPI must be setup in descriptor mode. For security reasons, primarily to lock PCU SPI flash access permission and OTP fuse programming, TXE Manufacturing Mode must be Disabled before shipping to customers. See your Intel® representative for details.

22.1 Features


22.1.1 Security Feature

The Intel® TXE is a security co-processor responsible for supporting and handling security. Features include:

- 32-bit RISC processor
- 256KB Data/Code RAM accessible only to the Intel® TXE
- 128KB On Chip Mask ROM for storage of Intel® TXE code
- Common Timer 1-100 μ S granularity, configurable interrupt (under FW control)
- Inter-Processor Communication for message passing between the Host CPU and Intel® TXE
- 64 byte input and output command buffers
- 256 byte shared payload (enables 2048-bit keys to be exchanged as part of the command)
- No Host CPU address domain access to the Intel® TXE address domain by any Host CPU address domain units
- Security controller has direct access to Host CPU address domain (Some Restrictions Apply). Multiple context DMA engine to transfer data between Host CPU address domain (System memory) and the Intel® TXE; programmable by the Intel® TXE CPU only.
- One multi-tiered FW Key Ladder and one Intel Key ladder.
- Paging DMA operations includes encryption/decryption and integrity check value (ICV) calculation. Auxiliary GPIOs to support input alert and two GP Outputs.

22.1.1.1 HW Accelerators

- DES/3DES (ECB, CBC) – 128b ABA key for 3DES Key Ladder Operations
- Three AES engines - Two fast -128 and one slow- 128/256



- Exponentiation Acceleration Unit (EAU) for modular exponentiation, modular reduction, large number addition, subtraction, and multiplication
- SHA1, SHA256/384/512, MD5

22.1.1.2 FW Utilities and Ciphers

- RSA (with EAU acceleration)
- Flash Write Enable/Disable
- Comprehensive IPC Command Set
- Chip Unique Key encryption key wrapping of other platform keys (Flash)

22.1.1.3 Downloadable FW Utilities and Ciphers

- Integrated Theft Deterrence Technology - Intel® Anti-Theft Technology (Intel® AT)
- Media Vault - content protection and distribution product specifically focused on online content for streaming and download
- One Time Programmable (OTP)

22.2 Register Map

See Chapters [Section 3, "Register Access Methods"](#) on page 69 and [Section 4, "Mapping Address Spaces"](#) on page 75 for additional information.



22.3 Intel® TXE PCI Configuration Registers

Table 239. Summary of TXE PCI Configuration Registers—0/26/0

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"Device/Vendor ID (DEVVENDID)—Offset 0h" on page 3166	00108086h
4–7h	4	"Status Command (STATUSCOMMAND)—Offset 4h" on page 3166	00100000h
8–Bh	4	"Revision ID and Class Code (REVCLASSCODE)—Offset 8h" on page 3167	10800000h
C–Fh	4	"CLLATHEADERBISTR (CLLATHEADERBIST)—Offset Ch" on page 3168	00000000h
10–13h	4	"SAP Agent Memory BAR (SAPAGENTBAR)—Offset 10h" on page 3168	00000000h
14–17h	4	"Bridge Memory BAR (BRIDGEBAR)—Offset 14h" on page 3169	00000000h
18h + [0-3]*4h	4	"Dummy BAR[0-3] (DUMMY_BARS[0-3])—Offset 18h, Count 4, Stride 4h" on page 3170	00000000h
2C–2Fh	4	"SUBSYSTEMID—Offset 2Ch" on page 3170	00000000h
30–33h	4	"EXPANSION_ROM_BASEADDR—Offset 30h" on page 3171	00000000h
34–37h	4	"CAPABILITYPTR—Offset 34h" on page 3171	00000080h
3C–3Fh	4	"INTERRUPTREG—Offset 3Ch" on page 3172	00000100h
40–43h	4	"SEC_FW_STS1—Offset 40h" on page 3172	00000000h
44–47h	4	"SEC_MEM_REQ—Offset 44h" on page 3175	00000000h
48–4Bh	4	"SEC_FW_STS0—Offset 48h" on page 3175	00000000h
4Ch + [0-4]*4h	4	"PCI_CONF_SEC_TO_HOST_3_7[0-4] (PCI_CONF_SEC_TO_HOST_3_7_REGS[0-4])—Offset 4Ch, Count 5, Stride 4h" on page 3177	00000000h
60–63h	4	"DID_MSG—Offset 60h" on page 3178	00000000h
64h + [0-6]*4h	4	"PCI_CONF_HOST_TO_SEC[0-6] (PCI_CONF_HOST_TO_SEC_1_7_REGS[0-6])—Offset 64h, Count 7, Stride 4h" on page 3179	00000000h
80–83h	4	"POWERCAPID—Offset 80h" on page 3179	4803A001h
84–87h	4	"PMECTRLSTATUS—Offset 84h" on page 3180	00000008h
88–8Bh	4	"CLK_GATE_DIS—Offset 88h" on page 3181	000000FFh
8C–8Fh	4	"TPM_ICR—Offset 8Ch" on page 3182	00000000h
A0–A3h	4	"MSICAP—Offset A0h" on page 3182	00000005h
A4–A7h	4	"MSIADDR—Offset A4h" on page 3183	00000000h
A8–ABh	4	"MSIDATA—Offset A8h" on page 3183	00000000h
B0–B3h	4	"IADBGCTRL—Offset B0h" on page 3184	00000000h
B4–B7h	4	"CPU_BIOS_ENV_PROTECT—Offset B4h" on page 3185	00000000h
C0–C3h	4	"SATT_BIOS_CTRL—Offset C0h" on page 3185	00001008h
C4–C7h	4	"SATT_BIOS_BA—Offset C4h" on page 3186	00000000h
C8–CBh	4	"SATT_BIOS_SIZE—Offset C8h" on page 3187	00000000h
D0–D3h	4	"SATT_TPM_CTRL (SATT_TPM_CTRL)—Offset D0h" on page 3187	00001008h
D4–D7h	4	"SATT_TPM_BA—Offset D4h" on page 3188	00000000h
D8–DBh	4	"SATT_TPM_SIZE—Offset D8h" on page 3188	00000000h
F0–F3h	4	"URRE—Offset F0h" on page 3189	00000000h
F8–FBh	4	"MANID—Offset F8h" on page 3189	00000000h



Bit Range	Default & Access	Field Name (ID): Description
31	0b NA	RESERVED (RSVD_31_31): RESERVED BITS
30	X RW/C	SIGNALLED_SYSTEM_ERROR_30: SERR status, write 1 to clear.
29	X RW/C	RMA: SERR status, write 1 to clear.
28:21	0b NA	RESERVED (RSVD_28_21): RESERVED BITS
20	1b RO	CAPLIST: CAP: Indicates that the CAPPOINT register at 34h provides an offset into PCI Configuration Space containing a pointer to the location of the first item in the list
19	X RO	INTR_STATUS: IS: Reflects the state of the interrupt in the graphics device. Is set to 1 if interrupt (as determined by IIR and IER memory interface registers) is set to 1. Otherwise is set to 0
18:11	0b NA	RESERVED (RSVD_18_11): RESERVED BITS
10	X RW	INTR_DISABLE: ID: When 1, blocks the sending of a MSI interrupt and blocks the sending of a Message bus interrupt. The interrupt status is not blocked from being reflected in COMMANDSTATUS. INTR_STT. When 0, permits the sending of a MSI interrupt or Message bus interrupt. Note: Overall, a MSI interrupt is sent when the expression (COMMANDSTATUS. INTR_STT and ~COMMANDSTATUS. INTR_DIS and COMMANDSTATUS.BUS_MSTR_EN and MSI_CAPID.MSI_EN) changes from 0 to 1. Overall, a Message bus interrupt assert is sent when the expression (COMMANDSTATUS. INTR_STT and ~COMMANDSTATUS. INTR_DIS and ~MSI_CAPID.MSI_EN) changes from 0 to 1. The corresponding Message bus interrupt de-assert is sent when the expression (COMMANDSTATUS. INTR_STT and ~COMMANDSTATUS. INTR_DIS and ~MSI_CAPID.MSI_EN) changes from 1 to 0
9	0b NA	RESERVED (RSVD_9_9): RESERVED BITS
8	X RW	INTR_STATUS (SERR_EN_8): SERR enable.
7:3	0b NA	RESERVED (RSVD_7_3): RESERVED BITS
2	X RW	BME: BME: Enables GVD to function as a PCI compliant master. When 0, blocks the sending of MSI interrupts and DDR transactions. When 1, permits the sending of MSI interrupts and DDR transactions. Note: transactions to SEC paging IMR are not controlled (enabled/disabled) by this field
1	X RW	MSE: MSE: When set, accesses to this device's memory space is enabled. When 1, SEC will compare IOSF primary address MS bits with its BARs MS bits. If there is a match and if the IOSF command is either a MEMRD or MEMWR, SEC send the command to the destination pointed by the base address. Care should be taken in setting up SEC BARs that more than 1 match is not made as this will result in unpredictable behavior. When 0, the SEC will not select a MEMRD or MEMWR IOSF command
0	0b NA	RESERVED (RSVD_0_0): IOSE: Since SEC doesn't have I/O space, this bit is hard coded to 0. RESERVED BITS

22.3.3 Revision ID and Class Code (REVCLASSCODE)—Offset 8h

Revision ID and Class Code. Register acces control: FW=RO PMC=RW Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + 8h

Default: 10800000h



Bit Range	Default & Access	Field Name (ID): Description
31:20	X RW	BaseAddressRegion: BA: Set by the OS, these bits correspond to address signals [31:20]. SEC will compare the IOSF address (bits [31:20]) with SAP_BRIDGE_BAR.BASE_ADDR. If there is a match, and COMMANDSTATUS.MEM_SPC_EN = 1 and the IOSF command is either a MEMRD or MEMWR, SEC will send the command to its MMIO registers block. If there's no MMIO register in the accessed offset, SEC Bridge will send FFFF_FFFFh to indicate a miss on the IOSF bus
19:1	0b NA	RESERVED (RSVD_19_0): RESERVED BITS
0	0b RO	RESRC_TYP: RTE: Indicates a request for memory space

22.3.7 Dummy BAR[0-3] (DUMMY_BARS[0-3])—Offset 18h, Count 4, Stride 4h

Dummy BAR, Returns zeroes to indicate un-implemented BAR. Register acces control: FW=RO PMC=RW Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset[0-3]: [B:0, D:26, F:0] + 18h + [0-3]*4h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

RSVD_31_0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0b NA	RESERVED (RSVD_31_0): RESERVED BITS

22.3.8 SUBSYSTEMID—Offset 2Ch


PCI Subsystem Identifiers. Register acces control: FW=RO PMC=RW Host=RW

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + 2Ch

Default: 00000000h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
23:16	X RW	EXT_STAT_DAT_CURR_STATE: The interpretation of this field's value depends on the value of field INF_PROG_CODE. For INF_PROG_CODE value of ROM, values are as follows: 0x000: Covers a number of steps early in ROM flow before entering main 0x001: Initialize memory map 0x002: Initialize the TPM Establishment bit 0x003: Initialize SusRAM 0x004: Get Fuse values 0x005: Derive chipset keys 0x006: Fuses/ Straps indicate ME disabled 0x007: Initialize HECI buffers 0x008: Find a FPT/Manifest image 0x009: Validate manifest found 0x00A: Load module found in manifest 0x00B: Transfer control over to new module 0x00C: Locate the FPT within memory 0x00D: Locate the Code partition within the FPT 0x00E: Initialize Paging logic 0x00F: Function designed to be patched wasn't prior to use. 0x010: H/W Page fault occurred. 0x011: Derive chipset keys For INF_PROG_CODE value of Bringup, values are as follows: 0x00: Initialization starts 0x01: Disable the host wake event 0x02: Enabling clock gating for ME 0x03: Enabling PM ME handshaking 0x04: Flow determination start process 0x05: PMC patching process 0x06: Get the flash VSCC parameters 0x07: Set (program) the flash VSCC registers 0x08: Error reading/matching the VSCC table in the descriptor 0x09: Initialize EDFS (overlay and SDM memory management) 0x0A: Check to see if straps say ME DISABLED 0x0B: Timeout waiting for T34 0x0C: Check to see if effs say ME DISABLED 0x0D: Possibly handle BUP manufacturing override strap 0x0E: Check to see if effs say ME DISABLED 0x0F: Initialize PKTPM 0x10: Initialize MiniBLOB 0x11: Bringup in M3 0x12: Bringup in M0 0x13: Flow detection error 0x14: M3 clock switching 0x15: M3 clock switching error 0x16: M3 flash paging flow 0x17: M3 ICV recovery flow 0x18: M3 kernel load 0x19: M0 Host prep sequence 0x1A: M0 Host skip prep sequence 0x1B: ICC programming 0x1C: T34 missing - cannot program ICC 0x1D: FLEX SKU programming 0x1E: TPM start (interface unisolation 0x1F: Waiting for DID BIOS message 0x20: Waiting for DID BIOS message failure 0x21: DID reported no error 0x22: Enabling UMA 0x23: Enabling UMA error 0x24: Sending DID Ack to BIOS 0x25: Sending DID Ack to BIOS error 0x26: Switching clocks in M0 0x27: Switching clocks in M0 error 0x28: ME in temp disable 0x29: ME in temp disable - error 0x2A: ME in temp disable - exiting and UMA enabling 0x2B: ME IPK check 0x2C: ME IPK recreation 0x2D: ME IPK recreation error 0x2E: ME UMA validation for resume 0x2F: ME UMA validation for resume error 0x30: ME UMA validation for resume error, so IPK recreation 0x31: M0 PK VENOM start 0x32: M0 kernel load 0x33: PK Venom init phase 0x34: M0 PK VENOM shutdown 0x35: FIPS halt - BUP self-test error 0x36: FIPS halt - CRYPTO_DRV self-test error 0x37: FIPS halt - TLS self-test error: 0x38: FIPS halt - DT self-test error 0x39: FIPS halt - DT self-test error 0x3A: Error enabling memory access range 0x3B: ME reset limit reached 0x3C: Two ME resets within short time detected, enter recovery 0x3D: Unknown halt reason detected, halt ME 0x3E: Validating GLUT and NFT manifest 0x3F: Reading kernel fixed data from NVAR 0x40: Reading ICC data 0x41: Zeroing out UMA 0x42: Full Fw sku running on Ignition HW sku 0x43: Error when deriving chipset keys 0x44: Bad BIOS, CPU DOA, CPU Missing 0x46: Failure in loading FTP 0x47: ME halted in BUP from Mfg ME reset 0x48: ME was reset because of MPR protection violation 0x49: BUP_T34_POLL_BEGIN 0x4A: BUP_T34_POLL_END 0x4B: BUP_HOBITO_SET 0x4C: BUP_POLL_CPURST_DEASSERT_BEGIN 0x4D: BUP_CPURST_DEASSERT_DONE 0x4E: BUP_DID_POLL_BEGIN 0x4F: BUP_DID_RECVD 0x50: BUP_ZERO_UMA_BEGIN 0x51: BUP_ZERO_UMA_DONE 0x52: BUP_DID_ACK_SENT 0x53: ICC requested a global reset after DID timeout 0x54: Perform ROSC clock frequency check 0x55: Clock check failed 0x56: CPU_RESET_DONE_ACK not received 0x57: FW build does not support the WW and/or Year specified in the fuses 0x58: ULV PCH check in progress 0x59: ULV PCH not paired with LV/ULV CPU 0x5A: VDM handshake failure 0x5B: FFS entry 0x5C: FFS exit 0x60: Error when getting a random number from TRNG 0x61: Find stack protection canary from NVAR or TRNG 0x62: VDM Get SID Message in progress 0x63: Wait for CPU to issue VLB authentication response For INF_PROG_CODE value of Kernel and Policy Module, values are as follows: 0x00: Entry into KERNEL Module 0x01: Entry into ThreadX Application Define 0x02: Exit ThreadX Application Define 0x03: Received S3 entry MSI from PMC 0x04: Received S4 entry MSI from PMC 0x05: Received S5 entry MSI from PMC 0x06: Received UPD entry MSI from PMC 0x07: Received PCR entry MSI from PMC 0x08: Received NPCR entry MSI from PMC 0x09: Received host wake MSI from PMC 0x0A: Received AC(-)DC switch 0x0B: Received DRAM Init Done 0x0C: VSCC Data not found for flash device 0x0D: VSCC Table is not valid 0x0E: Flash Partition Boundary in Chipset Descriptor is outside flash address space 0x0F: ME region cannot access the Chipset Descriptor Region 0x10: Required VSCC values for flash parts do not match 0x12: /**(State Info specified by the Exception Handler */ 0x13: /**(State Info specified by the Exception Handler */ 0x14: /**(State Info specified by the Exception Handler */ 0x15: /**(State Info specified by the Exception Handler */ 0x16: /**(State Info specified by the Exception Handler */ 0x17: /**(State Info specified by the Exception Handler */ 0x18: /**(State Info specified by the Exception Handler */ 0x19: /**(State Info specified by the Exception Handler */ 0x1A: /**(State Info specified by the Exception Handler */ 0x1B: /**(State Info specified by the Exception Handler */ For INF_PROG_CODE value of Host Communication, values are as follows: 0x00: Host communication established. Firmware is up and running.



Bit Range	Default & Access	Field Name (ID): Description
15:0	X RW	FUNC_RSVD_15: RESERVED BITS, writable

22.3.13 SEC_MEM_REQ—Offset 44h

SeC Firmware Memory Request. SeC FW uses this register in order to pass its main memory request to BIOS. Register access control: FW=RW PMC=RO Host=RO

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MEM_REQ_VALID	MEM_REQ_INVALID	FUNC_RSVD_29_16				MEM_SIZE		

Bit Range	Default & Access	Field Name (ID): Description
31	X RW	MEM_REQ_VALID: 1: SeC is making a request for memory, the size of which is indicated by field MEM_SIZE. During early boot stages, BIOS must wait for either this bit to be set or the MEM_REQ_INVALID bit to be set before proceeding.
30	X RW	MEM_REQ_INVALID: 1: SeC is not making any request for memory, and MEM_SIZE field should be ignored. During early boot stages, BIOS must wait for either this bit to be set or the MEM_REQ_VALID bit to be set before proceeding.
29:16	X NA	FUNC_RSVD_29_16: The functionality of this field is currently reserved
15:0	X RW	MEM_SIZE: Memory size that SeC is expecting, in KB. Format is Little Endian (bit 0 least significant, bit 15 most significant).

22.3.14 SEC_FW_STS0—Offset 48h


SeC Firmware Status Register 0. SeC FW uses this register in order to report its status to host (e.g. BIOS). Register access control: FW=RW PMC=RO Host=RO

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + 48h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BIOS_MSG_ACK	ACK_DATA	FUNC_RSVD_24	SEC_RST_CNT	SEC_CURR_OPER_MODE	ERR_CODE	FW_UPD_IN_PROG	FW_BUP_LD_FLR	FW_INIT_COMP
						SEC_CURR_OP_STATE	FPT_BAD	MANUF_MODE
								SEC_CURR_WRK_STATE

Bit Range	Default & Access	Field Name (ID): Description
31:28	X RW	BIOS_MSG_ACK: DRAM Init Done ACK. 0x00: No ACK was written by SeC. 0x01: ACK was written by SeC.
27:25	X RW	ACK_DATA: DRAM Init Done ACK Data. This field contains an action which BIOS should take on receiving an ACK from SeC. 0x00: No DRAM Init Done ACK received. 0x01: Non-power cycle reset. 0x02: Power cycle reset. 0x03: Go to S3. 0x04: Go to S4. 0x05: Go to S5. 0x06: Perform Global Reset. 0x07: Continue to boot.
24	X RW	FUNC_RSVD_24: The functionality of this field is currently reserved
23:20	X RW	SEC_RST_CNT: Count of SeC Resets
19:16	X RW	SEC_CURR_OPER_MODE: The field indicates the firmware mode of operation during this boot cycle. The host must look at this field only after DRAM_INIT_DONE (DID) register based message unless the firmware is in ERR before sending the DID. The Operation Mode doesn't change at runtime. Possible values: 0: Normal. SeC is running in normal mode. 1: Reserved. 2: Debug mode. SeC firmware enters this operation mode when SeC firmware FLASH variable TBD is configured in FLASH to 1. Firmware stays in this mode until the SeC firmware FLASH variable TBD is set to 0. 3: Soft temporary disable. SeC firmware enters this operation mode when BIOS sends the Temporary Disable message to firmware. Firmware stays in this mode until BIOS sends a follow-up message to get SeC out of this mode. Entering this mode is not supported when the system is provisioned with Intel AT firmware. 4: SECOVR_JMPR: SeC firmware enters this operation mode when HDA_SDO asserts high. Asserting the HDA_SDO high on the rising edge of PWROK will also disable SeC and SeC applications. 5: SECOVR_HECI_MSG: SeC firmware enters this operation mode during the firmware image re-flash in the factory environments. BIOS sends the flash protection override message (HMRFPD ENABLE HECI command) and causes a global reset then SeC firmware stays in this state similar to 'Soft Temporary Disable'. Before sending End of Post message (at late POST timeframe), BIOS needs to send a HMRFPD DISABLE command if SECOVR_HECI_MSG is set. In the same boot, the user can flash an image and reset (global reset or G3- exit) the system that will cause firmware to boot with a normal mode.
15:12	X RW	ERR_CODE: Set to a nonzero value if the firmware has encountered a fatal error. The firmware has stopped normal operation. Encoding as follows: 0: No error. Firmware is operational in current state. 1: Uncategorized Failure. SeC firmware has experienced an uncategorized error and has disabled itself. Further details of the failure can be found in field FW_STS1.EXT_STAT_DAT. This state can only be exited by powering down or resetting the machine. 2: Reserved. 3: Image Failure. SeC firmware stored in the system flash is not valid. If supported by the platform, the host should program a full firmware image into SeC flash region through the SPI controller. After completion of the SeC flash region update, the host should generate a full system reset the platform (global reset). 4: Debug Failure. Set when more data is available to the firmware on the cause of the failure. Please refer to field FW_STS1.EXT_STAT_DAT_CURR_STATE for more details. 5: Internal ROM Error. 6: Invalid fuse configuration. 7: Failure to access SPI FLASH.
11	X RW	FW_UPD_IN_PROG: This bit is set when data migration is required during the Firmware-update process.



Bit Range	Default & Access	Field Name (ID): Description
10	X RW	FW_BUP_LD_FLR: This bit is set when firmware is not able to load BRINGUP from the fault tolerant (FT) code. When this bit set, it may or may not have the error code shown in field ERR_CODE. The reason is because the firmware can load BRINGUP from the non fault tolerant (NFT) code.
9	X RW	FW_INIT_COMP: When this bit is clear, firmware is still in loading process and has not made it to final steady state yet. When firmware has fully entered a stable state, this bit is set to 1 and 'Current Working State' field of this register provides the steady state of SeC.
8:6	000b RW	SEC_CURR_OP_STATE: This field describes the state in which SeC is currently functioning in at this moment. It's the combination of SeC power state and UMA. The field is set only upon entering the true hardware state. Values: 000b: Preboot (default) 001b: M0 with UMA. 010b: M0ff. 011b: Reserved. 100b: Reserved. 101b: Reserved. 110b: Bringup. 111b: M0 without UMA but with error. If there is no memory in the system, or upon identifying an error in UMA initialization, the SeC firmware will get into this operation state.
5	X RW	FPT_BAD: This bit is set when the firmware discovers a bad checksum of Flash Partition Table (FPT). When this bit set, it may or may not have the error code shown in field ERR_CODE. The system can get this bit clear by flashing the proper firmware image again.
4	X RW	MANUF_MODE: When this bit is set, the platform is still in Manufacturing mode. Host can use this bit to inform user that the platform is NOT ready for production yet. This bit is set as long as SeC Manufacturing Mode Done bit is set to 0 or SPI flash descriptor region is not locked. For shipping machine, this bit has to be to 0.
3:0	X RW	SEC_CURR_WRK_STATE: This field describes the current working state of the SeC firmware. Further information about the progress within the Current Working State can be found in field SEC_FW_STS1.EXT_STS_DAT. In spoken language, the 'Current Working State' indicates what firmware is doing at this moment. Encoding is as follows: 0: Reset. SeC firmware is in a reset state. 1: Initializing. SeC firmware is initializing, the final functional state is NOT known at this time. 2: Recovery: SeC firmware is recovering from an image update failure. Upon completion of this state, SeC firmware will enter the Initializing State. The firmware will stay in recovery state until a new firmware update is run. 3: Reserved. 4: Reserved. 5: Normal. SeC firmware is operating in normal state. 6: Platform Disable Wait. SeC firmware enters this state when it pauses itself with AT fuses set to halt platform after 30 minutes wait. 7: OP State Transition. SeC firmware sets this state before starting a transition to a new operation state. 8: Reserved.

22.3.15 PCI_CONF_SEC_TO_HOST_3_7[0-4] (PCI_CONF_SEC_TO_HOST_3_7_REGS[0-4])—Offset 4Ch, Count 5, Stride 4h

PCI Configuration register - SeC to Host 3-7. The functionality of this register is currently reserved. Register access control: FW=RW PMC=RO Host=RO

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset[0-4]: [B:0, D:26, F:0] + 4Ch + [0-4]*4h

Default: 00000000h



Access Method

Offset: [B:0, D:26, F:0] + 60h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DONE		STATUS		FUNC_RSVD_23_0				

Bit Range	Default & Access	Field Name (ID): Description
31:28	X RW	DONE: 0x00: DRAM Init not done. 0x01: DRAM Initialization Done. If STATUS field is success, this means that SATT1 register is set for SeC memory paging operation. Note that BIOS must not provide a DRAM Init Done message before setting up SATT1.
27:24	X RW	STATUS: 0x00: Success. 0x01: No memory in channels. 0x02: Memory Init Error.
23:0	X NA	FUNC_RSVD_23_0: RESERVED BITS



PME Control and Status. Register access control: FW=RO PMC=RW Host=RW

Type: PCI Configuration Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0			
0	0	0	0	0	0	0	0	0			
RSVD_31_16				PME_Status	RSVD_14_9		PME_En	RSVD_7_4	No_Soft_Reset	RSVD_2	POWERSTATE

Intel Atom® Processor E3800 Product Family
Datasheet
3180



Bit Range	Default & Access	Field Name (ID): Description
3	1b RO	No_Soft_Reset: PME Control and Status
2	0b NA	RESERVED (RSVD_2): RESERVED BITS
1:0	X RW	POWERSTATE: SeC Power state - TBD

22.3.20 CLK_GATE_DIS—Offset 88h

Clock Gating Disable. Register acces control: FW=RW PMC=RW Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + 88h

Default: 000000FFh

31	28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	
RSVD_31_8																																NFC_CG_DIS
																																SAP_CLKIDLE_DIS
																																SAP_IP_CG_DIS
																																SAP_CG_DIS
																																PRIM_XSM_CLKREQ_DIS
																																PRIM_CLKREQ_DIS
																																PRIM_CG_DIS
SR_CG_DIS																																

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b NA	RESERVED (RSVD_31_8): RESERVED BITS
7	1b RW	NFC_CG_DIS: I2C clock gating disable
6	1b RW	SAP_CLKIDLE_DIS: SAP clock idle disable
5	1b RO	SAP_IP_CG_DIS: Functional IP clock gating disable
4	1b RW	SAP_CG_DIS: Functional SEC clock gating disable (Bridge and IP)
3	1b RW	PRIM_XSM_CLKREQ_DIS: Primary XSM clock-request disable
2	1b RW	PRIM_CLKREQ_DIS: IOSF Primary clock request disable
1	1b RW	PRIM_CG_DIS: IOSF Primary clock gating disable
0	1b RW	SB_CG_DIS: IOSF Sideband Bridge clock gating disable



22.3.21 TPM_ICR—Offset 8Ch

TPM Interrupt Cause Register. Access control: FW=RO PMC=RW Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + 8Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

TPM_REQ

Bit Range	Default & Access	Field Name (ID): Description
31:0	X RW	TPM_REQ: Host writes this bit to indicate a TPM message is ready for fTPM handling. A write to this register will trigger an interrupt to the SEC, in ICR 30.

22.3.22 MSICAP—Offset A0h

MSI Capability. Register access control: FW=RO PMC=RW Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + A0h

Default: 00000005h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

RSVD_31_25

PER_VEC_CAP

BIT_ADDR_CAP

MME

RSVD_19_17

MSI_ENABLE

RSVD_15_8

MSI_CAP

Bit Range	Default & Access	Field Name (ID): Description
31:25	0b NA	RESERVED (RSVD_31_25): RESERVED BITS
24	X RO	PER_VEC_CAP: Per vector masking not supported.
23	X RO	BIT_ADDR_CAP: C64: 32-bit capable only
22:20	X RW	MME: MME: This field is RW for software compatibility, but only a single message is ever generated
19:17	0b NA	RESERVED (RSVD_19_17): RESERVED BITS , MMC: This device is only single message capable



Bit Range	Default & Access	Field Name (ID): Description
31:16	X NA	RESERVED (Reserved_31_16): RESERVED BITS
15:0	X RW	MSGDATAMSI: MA: Lower 32-bits of the system specified message data, always DW aligned. When the SEC issues an MSI interrupt as a MEMWR on the IOSF, the memory address corresponds to the value of this field

22.3.25 IADBGCTRL—Offset B0h

IA Debug Control. Register acces control: FW=RO PMC=RW Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + B0h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31	X RO	DBG_STS: DBG_STS. This bit allows a user to be informed that their system is (or is at risk of) being debugged. It is up to the OEM/OS to act on this bit being set and find a way to expose it to the user. CLTAP will send a signal to SEC indicating that debug of the SOC and/or access to the CPUTAP is possible. This will be (allow_cputap_access dfx_security_risk). Note: DBG_STS will be set in all Opt-In cases including pre-production and IDLM.
30	X RW/1L	IADBGCTRL_LOCK: Lock. If set, writes to bits 29:0 are dropped.
29:2	0b NA	RESERVED (RSVD_29_2): RESERVED BITS
1	X RW	EXPOSE_SOCID: Expose_SOCID. If set, software is requesting that this parts unique ID will be visible in a public SOTAP register to JTAG (on-board or EXI). It is never exposed to IA code. This bit is locked (writes ignored) if the LOCK bit is set. This bit will be written but ignored if SEC OEM-M[HONOR_IADBGCTRL]=0.



Bit Range	Default & Access	Field Name (ID): Description
0	X RW	CPU_PUBLIC_DBG_EN: CPUPublicDBG_EN. If set, software is requesting access be granted to the CPUTAP's public and non-protected functions. This bit is locked (writes ignored) if the LOCK bit is set. This bit will be written but ignored if SEC OEM-M[HONOR_IADBGCTRL]=0.

22.3.26 CPU BIOS ENV PROTECT—Offset B4h

CPU BIO Environment Protection. Register access control: FW=RW PMC=RO Host=RO
Note: This register does not support byte- or word- granularity write. All 32 bits of this register should be written at once. To change only part of the register, a read-modify-write process should be used on all 32 bits

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + B4h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD_31_4								CPU_BIOS_ENV_ATTACHED
								BIOS_RDY_FOR_EVENT
								CPU_DIS_BSP_INIT
								CPU_PROTECT_BIOS_FNV

Bit Range	Default & Access	Field Name (ID): Description
31:4	0b NA	RESERVED (RSVD_31_4): RESERVED BITS
3	X RW	CPU_BIOS_ENV_ATTACKED: CPU_BIOS_ENV_ATTACKED
2	X RW	BIOS_RDY_FOR_EVENT: BIOS_RDY_FOR_EVENT
1	X RW	CPU_DIS_BSP_INIT: CPU_DIS_BSP_INIT
0	X RW	CPU_PROTECT_BIOS_ENV: CPU_PROTECT_BIOS_ENV

22.3.27 SATT_BIOS_CTRL—Offset C0h

SEC Address Translation Table Entry no. 2 control register, used by the BIOS to configure the paging IMR related entry. Register access control: FW=RO PMC=RO Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + C0h

Default: 00001008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD_31_13					BRG_HOST_EN	BRG_BA_MSB	RSVD_7_4	TARGET
								VALID

Bit Range	Default & Access	Field Name (ID): Description
31:13	0b NA	RESERVED (RSVD_31_13): RESERVED BITS
12	1b RO	BRG_HOST_EN: Indicates whether or not the entry's BRG_BA is configurable by host CPU. Hard coded to 1b, to ensure host CPU only access
11:8	X RW	BRG_BA_MSB: 4 MS bits to be used for IOSF address, to be concatenated with the entry's BRG_BA_LSB[31:0]. This field is locked when SATT1_CTRL.ENTRY_VLD is set. Locked by entry_valid bit.
7:4	0b NA	RESERVED (RSVD_7_4): RESERVED BITS
3:1	100b RO	TARGET: The target to which the SAP transaction will be redirected: 000 - Bridge memory space 001 - Bridge PCI configuration space 010 - IOSF sideband (General) 011 - SPI via IOSF Sideband 100 - DDR via IOSF Primary Hard coded to '100' to let host configure paging IMR
0	X RW	VALID: Entry valid bit. This bit can be set only once (by BIOS). Once it's set to '1', it cannot be cleared, and all SAAT1 entry register fields are locked. Entry hit condition is: ENTRY_VLD and SAP_BA (= SAPAddr[+SAPSize] (SAP_BA + SAP_SIZE

22.3.28 SATT_BIOS_BA—Offset C4h

SEC address translation table entry 1 bridge base address. Register access control:
FW=RO PMC=RO Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + C4h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	X RW	BRG_BA: The bridge base address to be used for address translation using current SATT entry. This field is locked when SATT1_CTRL.ENTRY_VLD is set. Address calculation: FinalAddr = SAPAddr - SAP_BA + BRG_BA. Locked by entry_valid bit in SATT1_CTRL register.



Bit Range	Default & Access	Field Name (ID): Description
13	X RO	SEC_TPM_DISABLED: Indicates to the BIOS that the fTPM functionality is disabled (either by fuse or by fw).
12	1b RO	BRG_HOST_EN: Indicates whether or not the entry's BRG_BA is configurable by host CPU. Hard coded to 1b, to ensure host CPU only access
11:8	X RW	BRG_BA_MSB: 4 MS bits to be used for IOSF address, to be concatenated with the entry's BRG_BA_LSB[31:0] Locked by entry_valid bit.
7:4	0b NA	RESERVED (RSVD_7_4): RESERVED BITS
3:1	100b RO	TARGET: The target to which the SAP transaction will be redirected: 000 - Bridge memory space 001 - Bridge PCI configuration space 010 - IOSF sideband (General) 011 - SPI via IOSF Sideband 100 - DDR via IOSF Primary Hard coded to '100' to let host configure TPM
0	X RW	VALID: Entry valid bit. Entry hit condition is: ENTRY_VLD and SAP_BA (= SAPAddr[+SAPSize] (SAP_BA + SAP_SIZE 1'b0: SATT TPM Entry is disabled. 1'b1: SATT TPM Entry is enabled. Note: when TPM disable fuse is '1', this bit is hard coded to '0'. Asserting this bit will lock the TPM SATT entries. (CTRL, BA and SIZE).

22.3.31 SATT_TPM_BA—Offset D4h

SEC Address Translation Table Entry no. 4 SAP Address space Size register, used by the BIOS to configure the paging IMR related entry. Register access control: FW=RO PMC=RO Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + D4h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

BRG_BA

Bit Range	Default & Access	Field Name (ID): Description
31:0	X RW	BRG_BA: The bridge base address to be used for address translation using current SATT entry. Address calculation: FinalAddr = SAPAddr - SAP_BA + BRG_BA Locked by entry_valid bit in SATT1_CTRL register..

22.3.32 SATT_TPM_SIZE—Offset D8h


SEC Address Translation Table Entry no. 4 SAP Address space Size register, used by the BIOS to configure the paging IMR related entry. Register access control: FW=RO PMC=RO Host=RW

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:26, F:0] + D8h

Default: 00000000h



31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	0	0
									URR_1	URD

October 2018
Document Number: 538136, Rev. 4.3




31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD_31_28	DOT_PORT	MAN_ID_23_16	MAN_ID_15_8	MAN_ID_7_0				

Bit Range	Default & Access	Field Name (ID): Description
31:28	X RO	RESERVED (RSVD_31_28): RESERVED BITS
27:24	X RO	DOT_PORT: Dot Portion of Process: obtained from SETID message sent by PMC
23:16	X RO	MAN_ID_23_16: Manufacturing Stepping ID (MSID): obtained from SETID message sent by PMC
15:8	X RO	MAN_ID_15_8: Manufacturing ID (MID): obtained from SETID message sent by PMC
7:0	X RO	MAN_ID_7_0: Process Portion of Process ID: obtained from SETID message sent by PMC

23 *PCI Express* 2.0*

There are four lanes and up to four PCI Express root ports, each supporting the *PCI Express* Base Specification*, Rev. 2.0 at a maximum 5 GT/s signaling rate. The root ports can be configured to support a diverse set of lane assignments.



23.1 Signal Descriptions

Please see [Chapter 2, “Physical Interfaces”](#) for additional details.


The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function

Note: PMC_WAKE_PCIE[3:0]# are not listed, but can be used by PCI Express* devices. Please see [Section 30, “PCU – Power Management Controller \(PMC\)”](#) on page 4344 for details.


Table 240. Signals

Signal Name	Direction Plat. Power	Description
PCIE_TXP[3:0] PCIE_TXN[3:0]	O PCIESATA	PCI Express* Transmit PCI Express* Ports 3:0 transmit pair (P and N) signals. Each pair makes up the transmit half of a lane.
PCIE_RXP[3:0] PCIE_RXN[3:0]	I PCIESATA	PCI Express* Receive: PCI Express* Ports 3:0 receive pair (P and N) signals. Each pair makes up the receive half of lane.
PCIE_CLKP[3:0] PCIE_CLKN[3:0]	O V1P0S	PCI Express* Output Clock 100-MHz differential clock signals. These are not owned by the PCI Express* controller, but are platform clocks found in the Integrated Clock.
PCIE_CLKREQ[3:0]#	I V1P8S	PCI Express* Clock Request Used for devices that need to request one of the four output clocks. Each clock request maps to the matching clock output (e.g., PCIE_CLKREQ[0] maps to PCIE_CLKP/N[0]). These are not owned by the PCI Express* controller, but are platform clocks found in the Integrated Clock. <i>These signals are muxed and may be used by other functions.</i>
PCIE_RCOMP_P PCIE_RCOMP_N	I/O	These pins are used to connect the external resistors used for Rcomp. Please contact your Intel representative for details.

Figure 112. PCIe* 2.0 Lane 0 Signal Example


23.2 Features

- Conforms to *PCI Express* Base Specification, Rev. 2.0*
- 5.0 or 2.5 GT/s operation per root port
- Virtual Channel support for VC0
- x1, x2 and x4 link widths (auto negotiated)
- Flexible Root Port (1-4) configuration options
 - (4) x1's




- (2) x2's
- (1) x2 plus (2) x1's
- (1) x4
- Interrupts and Events
 - Legacy (INTx) and MSI Interrupts
 - General Purpose Events
 - Express Card Hot Plug Events
 - System Error Events
- Power Management
 - Link State support for L0s, L1 and L2
 - Powered down in ACPI S3 state - L3

23.2.1 Root Port Configurations

Depending on SKU, there are up to four possible lane assignments for root ports 1-4.

Figure 113. Root Port Configuration Options



Root port configurations are set by SoftStraps stored in SPI flash, and the default option is "(4) x1". Links for each root port will train automatically to the maximum possible for each port.

Note: x2 link widths are not common. Most devices will only train to x1 or x4.

Note: PCI functions in PCI configuration space are disabled for root ports not available.

23.2.2 Interrupts and Events

A root port is capable of handling interrupts and events from an end point device. A root port can also generate its own interrupts for some events, including power management and hot plug events, but also including error events.

There are two interrupt types a root port will receive from an end point device: INTx (legacy), and MSI. MSI's are automatically passed upstream by the root port, just as other memory writes would be. INTx messages are delivered to the Legacy block's interrupt router/controller by the root port.

Events and interrupts that are handled by the root port are shown with the possible interrupts they can deliver to the interrupt decoder/router.

Table 241. Possible Interrupts Generated From Events/Packets

Packet/Event	Type	INTx	MSI	SERR	SCI	SMI	GPE
INTx	Packet	X	X				
PM_PME	Packet	X	X				
Power Management (PM)	Event	X	X		X	X	
Hot Plug (HP)	Event	X	X		X	X	
ERR_CORR	Packet			X			
ERR_NONFATAL	Packet			X			
ERR_FATAL	Packet			X			
Internal Error	Event			X			
VDM	Packet						X

Note: Table 241 lists the possible interrupts and events generated based on Packets received, or events generated in the root port. Configuration needed by software to enable the different interrupts as applicable.

When INTx interrupts are received by an end point, they are mapped to the following interrupts and sent to the interrupt decoder/router in the iLB:


Table 242. Interrupt Generated for INT[A-D] Interrupts

	INTA	INTB	INTC	INTD
Root Port 1	INTA#	INTB#	INTC#	INTD#
Root Port 2	INTD#	INTA#	INTB#	INTC#
Root Port 3	INTC#	INTD#	INTA#	INTB#
Root Port 4	INTB#	INTC#	INTD#	INTA#

Note: Interrupts generated from events within the root port are not swizzled.

23.2.2.1 Express Card Hot Plug Events

Express Card Hot Plug is available based on Presence Detection for each root port.



Note: A full Hot Plug Controller is not implemented.

Presence detection occurs when a PCI Express* device is plugged in and power is supplied. The physical layer will detect the presence of the device, and the root port will set the SLSTS.PDS and SLSTS.PDC bits.

When a device is removed and detected by the physical layer, the root port will clear the SLSTS.PDS bit, and set the SLSTS.PDC bit.

Interrupts can be generated by the root port when a hot plug event occurs. A hot plug event is defined as the transition of the SLSTS.PDC bit from 0 to 1. Software can set the SLCTL.PDE and SLTCTL.HPE bits to allow hot plug events to generate an interrupt.

If SLCTL.PDE and SLTCTL.HPE are both set, and SLSTS.PDC transitions from 0 to 1, an interrupt will be generated.

23.2.2.2 System Error (SERR)

System Error events are support by both internal and external sources. See the PCI Express* Base Specification, Rev. 2.0 for details.

23.2.3 Power Management

Each root port's link supports L0s, L1, and L2/3 link states per PCI Express* Base Specification, Rev. 2.0. L2/3 is entered on entry to S3.

23.3 References


PCI Express Base Specification, Rev. 2.0*

23.4 Register Map

Each root port supports its own extended PCI bridge header in PCI configuration space. These headers are located on PCI bus 0, device 28, functions 0-3 as shown below. There are no other registers implemented by the root ports or their controller.

See Chapters [Chapter 3, "Register Access Methods"](#) and [Chapter 4, "Mapping Address Spaces"](#) for additional information.

Figure 114. PCI Express Register Map



23.5 PCI Configuration Registers

Registers listed are for function 0 (root port 1). All other root ports contain the same registers. Differences for other root ports (functions 1-3) will be noted in individual registers.



23.6 PCI Express* PCI Configuration Registers

Table 243. Summary of PCI Express* PCI Configuration Registers—0/28/0

Offset	Size	Register ID—Description	Default Value
0h	4	"Identifiers (ID)—Offset 0h" on page 3198	00008086h
4h	4	"Device Command; Primary Status (CMD_PSTS)—Offset 4h" on page 3199	00100000h
8h	4	"Revision ID; Class Code (RID_CC)—Offset 8h" on page 3200	06040000h
Ch	4	"Cache Line Size; Primary Latency Timer; Header Type (CLS_PLT_HTYPE)—Offset Ch" on page 3201	00810000h
18h	4	"Bus Numbers; Secondary Latency Timer (BNUM_SLT)—Offset 18h" on page 3201	00000000h
1Ch	4	"I/O Base and Limit; Secondary Status (IOBL_SSTS)—Offset 1Ch" on page 3202	00000000h
20h	4	"Memory Base and Limit (MBL)—Offset 20h" on page 3203	00000000h
24h	4	"Prefetchable Memory Base and Limit (PMBL)—Offset 24h" on page 3204	00010001h
28h	4	"Prefetchable Memory Base Upper 32 Bits (PMBU32)—Offset 28h" on page 3204	00000000h
2Ch	4	"Prefetchable Memory Limit Upper 32 Bits (PMLU32)—Offset 2Ch" on page 3205	00000000h
34h	4	"Capabilities List Pointer (CAPP)—Offset 34h" on page 3205	00000040h
3Ch	4	"Interrupt Information; Bridge Control (INTR_BCTRL)—Offset 3Ch" on page 3206	00000000h
40h	4	"Capabilities List; PCI Express Capabilities (CLIST_XCAP)—Offset 40h" on page 3207	00428010h
44h	4	"Device Capabilities (DCAP)—Offset 44h" on page 3208	00008000h
48h	4	"Device Control; Device Status (DCTL_DSTS)—Offset 48h" on page 3209	00100000h
4Ch	4	"Link Capabilities (LCAP)—Offset 4Ch" on page 3210	00310C02h
50h	4	"Link Control; Link Status (LCTL_LSTS)—Offset 50h" on page 3211	00010000h
54h	4	"Slot Capabilities (SLCAP)—Offset 54h" on page 3213	00040060h
58h	4	"Slot Control; Slot Status (SLCTL_SLSTS)—Offset 58h" on page 3214	00000000h
5Ch	4	"Root Control (RCTL)—Offset 5Ch" on page 3215	00000000h
60h	4	"Root Status (RSTS)—Offset 60h" on page 3216	00000000h
64h	4	"Device Capabilities 2 (DCAP2)—Offset 64h" on page 3217	00080816h
68h	4	"Device Control 2; Device Status 2 (DCTL2_DSTS2)—Offset 68h" on page 3217	00000000h
6Ch	4	"Link Capabilities 2 (LCAP2)—Offset 6Ch" on page 3218	00000000h
70h	4	"Link Control 2; Link Status 2 (LCTL2_LSTS2)—Offset 70h" on page 3219	00000000h
74h	4	"Slot Capabilities 2 (SLCAP2)—Offset 74h" on page 3220	00000000h
78h	4	"Slot Control 2; Slot Status 2 (SLCTL2_SLSTS2)—Offset 78h" on page 3221	00000000h
80h	4	"Message Signaled Interrupt Identifiers; Message Signaled Interrupt Message Control (MID_MC)—Offset 80h" on page 3221	00009005h
84h	4	"Message Signaled Interrupt Message Address (MA)—Offset 84h" on page 3222	00000000h
88h	4	"Message Signaled Interrupt Message Data (MD)—Offset 88h" on page 3222	00000000h
90h	4	"Subsystem Vendor Capability (SVCAP)—Offset 90h" on page 3223	0000A00Dh
94h	4	"Subsystem Vendor IDs (SVID)—Offset 94h" on page 3223	00000000h
A0h	4	"Power Management Capability; PCI Power Management Capabilities (PMCAP_PMC)—Offset A0h" on page 3224	C8030001h
A4h	4	"PCI Power Management Control And Status (PMCS)—Offset A4h" on page 3225	00000000h



23.6.2 Device Command; Primary Status (CMD_PSTS)—Offset 4h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

CMD_PSTS: [B:0, D:28, F:0] + 4h

Power Well: Core

Default: 00100000h

31		28				24				20				16				12				8				4				0																							
0		0		0		0		0		0		0		1		0		0		0		0		0		0		0		0		0																					
DPE		SSE		RMA		RTA		STA		PDTS		DPD		PFBC		RSVD		PC66		CLIST		IS		RSVD_1				RSVD_2				ID		FBE		SEE		WCC		PERE		VGA_PSE		MWIE		SCE		BME		MSE		TOSF	

Bit Range	Default & Access	Description
31	0b RW/C	DPE Detected Parity Error (DPE): Set when the root port receives a command or data from the backbone with a parity error. This is set even if CMD.PERE is not set.
30	0b RW/C	Signaled System Error (SSE): Set when the root port signals a system error to the internal SERR# logic.
29	0b RW/C	Received Master Abort (RMA): Set when the root port receives a completion with unsupported request status from the backbone.
28	0b RW/C	Received Target Abort (RTA): Set when the root port receives a completion with completer abort from the backbone.
27	0b RW/C	Signaled Target Abort (STA): Set whenever the root port forwards a target abort received from the downstream device onto the backbone.
26:25	00b RO	Primary DEVSEL# Timing Status (PSTS): Reserved per PCI-Express spec
24	0b RW/C	Master Data Parity Error Detected (DPD): Set when the root port receives a completion with a data parity error on the backbone and CMD.PERE is set.
23	0b RO	Primary Fast Back to Back Capable (PFBC): Reserved per PCI-Express spec.
22	0b RO	Reserved (RSVD): Reserved
21	0b RO	Primary 66 MHz Capable (PC66): Reserved per PCI-Express spec.
20	1b RO	Capabilities List (CLIST): Indicates the presence of a capabilities list.
19	0b RO/V	Interrupt Status (IS): Indicates status of hot plug and power management interrupts on the root port that result in INTx# message generation. This bit is not set if MSI is enabled. If MSI is not enabled, this bit is set regardless of the state of CMD.ID.
18:16	000b RO	Reserved (RSVD_1): Reserved
15:11	00h RO	Reserved (RSVD_2): Reserved



Bit Range	Default & Access	Description
10	0b RW/V	Interrupt Disable (ID): This disables pin-based INTx# interrupts on enabled hot plug and power management events. This bit has no effect on MSI operation. When set, internal INTx# messages will not be generated. When cleared, internal INTx# messages are generated if there is an interrupt for hot plug or power management and MSI is not enabled. This bit does not affect interrupt forwarding from devices connected to the root port. Assert_INTx and Deassert_INTx messages will still be forwarded to the internal interrupt controllers if this bit is set. For PCI Bus Emulation Mode compatibility, if the PCIBEM register is set, this register is RO and returns a value of 0 when read, else it is RW with the functionality described above.
9	0b RO	Fast Back to Back Enable (FBE): Reserved per PCI-Express spec.
8	0b RW	SERR# Enable (SEE): When set, enables the root port to generate an SERR# message when PSTS.SSE is set.
7	0b RO	Wait Cycle Control (WCC): Reserved per PCI-Express spec.
6	0b RW	Parity Error Response Enable (PERE): Indicates that the device is capable of reporting parity errors as a master on the backbone.
5	0b RO	VGA Palette Snoop (VGA_PSE): Reserved per PCI-Express spec.
4	0b RO	Memory Write and Invalidate Enable (MWIE): Reserved per PCI-Express spec.
3	0b RO	Special Cycle Enable (SCE): Reserved per PCI-Express and PCI bridge spec.
2	0b RW	Bus Master Enable (BME): When set, allows the root port to forward Memory and I/O Read/Write cycles onto the backbone from a PCI-Express device. When this bit is 0b, Memory and I/O requests received at a Root Port must be handled as Unsupported Requests (UR). This bit does not affect forwarding of Completions in either the Upstream or Downstream direction. The forwarding of Requests other than Memory or I/O requests is not controlled by this bit.
1	0b RW	Memory Space Enable (MSE): When set, memory cycles within the range specified by the memory base and limit registers can be forwarded to the PCI-Express device. When cleared, these memory cycles are master aborted on the backbone.
0	0b RW	I/O Space Enable (IOSE): When set, I/O cycles within the range specified by the I/O base and limit registers can be forwarded to the PCI-Express device. When cleared, these cycles are master aborted on the backbone..

23.6.3 Revision ID;Class Code (RID_CC)—Offset 8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

RID_CC: [B:0, D:28, F:0] + 8h

Power Well: Core

Default: 06040000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
	BCC		SCC		PI		RID	



Bit Range	Default & Access	Description
31:24	06h RO	Base Class Code (BCC): Indicates the device is a bridge device.
23:16	04h RO/V	Sub-Class Code (SCC): The default indicates the device is a PCI-to-PCI bridge.
15:8	00h RO/V	Programming Interface (PI): The value reported in this register is a function of the Decode Control.Subtractive Decode Enable (SDE) register. SDE Value reported in this register 0: 00h 1: 01h
7:0	00h RO/V	Revision ID (RID): Indicates the revision of the bridge.

23.6.4 Cache Line Size; Primary Latency Timer; Header Type (CLS_PLT_HTYPE)—Offset Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

CLS_PLT_HTYPE: [B:0, D:28, F:0] + Ch

Power Well: Core

Default: 00810000h

31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				MFD	HTYPE		CT	RSVD_1
							LS	

Bit Range	Default & Access	Description
31:24	00h RO	Reserved (RSVD): Reserved
23	1b RO	Multi-function Device (MFD): This bit is '1' to indicate a multi-function device.
22:16	01h RO/V	Header Type (HTYPE): The default mode identifies the header layout of the configuration space, which is a PCI-to-PCI bridge.
15:11	00h RO	Latency Count (CT): Reserved per PCI-Express spec
10:8	000b RO	Reserved (RSVD_1): Reserved
7:0	00h RW	Line Size (LS): This is read/write but contains no functionality, per PCI-Express spec

23.6.5 Bus Numbers; Secondary Latency Timer (BNUM_SLT)—Offset 18h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

BNUM_SLT: [B:0, D:28, F:0] + 18h

Power Well: Core



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SLT	SBBN	SCBN	PBN					

Bit Range	Default & Access	Description
31:24	00h RW/V	Secondary Latency Timer (SLT): For PCI Bus Emulation Mode compatibility, if the DC.PCIBEM register is set, this register is a RW register; else this register is RO and returns 0. This register does not affect the behavior of any HW logic.
23:16	00h RW	Subordinate Bus Number (SBBN): Indicates the highest PCI bus number below the bridge.
15:8	00h RW	Secondary Bus Number (SCBN): Indicates the bus number the port.
7:0	00h RW	Primary Bus Number (PBN): Indicates the bus number of the backbone.

23.6.6 I/O Base and Limit; Secondary Status (IOBL_SSTS)—Offset 1Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

IOBL_SSTS: [B:0, D:28, F:0] + 1Ch

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DPE	RSE	RMA	RTA	STA	SDTS	DPD	SFBC	RSVD
								SC66
								RSVD_1
								IOLA
								IOLC
								IOBA
								IOBC

Bit Range	Default & Access	Description
31	0b RW/C	Detected Parity Error (DPE): Set when the port receives a poisoned TLP.
30	0b RW/C	Received System Error (RSE): Set when the port receives an ERR_FATAL or ERR_NONFATAL message from the device.
29	0b RW/C	Received Master Abort (RMA): Set when the port receives a completion with 'Unsupported Request' status from the device.
28	0b RW/C	Received Target Abort (RTA): Set when the port receives a completion with 'Completion Abort' status from the device.
27	0b RW/C	Signaled Target Abort (STA): Set when the port generates a completion with 'Completion Abort' status to the device.
26:25	00b RO/V	Secondary DEVSEL# Timing Status (SDTS): Reserved per PCI-Express spec For PCI Bus Emulation Mode compatibility, if the PCIBEM register is set, this register returns a value of 01b when read, else this register returns a value of 00b.
24	0b RW/C	Data Parity Error Detected (DPD): Set when the BCTRL.PERE, and either of the following two conditions occurs: Port receives completion marked poisoned. Port poisons a write request to the secondary side.



Bit Range	Default & Access	Description
23	0b RO/V	Secondary Fast Back to Back Capable (SFBC): Reserved per PCI Express spec For PCI Bus Emulation Mode compatibility, if the PCIBEM register is set, this register returns a value of 1b when read, else this register returns a value of 0b.
22	0b RO	Reserved (RSVD): Reserved
21	0b RO	Secondary 66 MHz Capable (SC66): Reserved per PCI Express spec
20:16	00h RO	Reserved (RSVD_1): Reserved
15:12	0h RW	I/O Address Limit (IOLA): I/O Base bits corresponding to address lines 15:12 for 4KB alignment. Bits 11:0 are assumed to be padded to FFFh.
11:8	0h RO	I/O Limit Address Capability (IOLC): Indicates that the bridge does not support 32-bit I/O addressing.
7:4	0h RW	I/O Base Address (IOBA): I/O Base bits corresponding to address lines 15:12 for 4KB alignment. Bits 11:0 are assumed to be padded to 000h.
3:0	0h RO	I/O Base Address Capability (IOBC): Indicates that the bridge does not support 32-bit I/O addressing.

23.6.7 Memory Base and Limit (MBL)—Offset 20h

Accesses that are within the ranges specified in this register will be sent to the attached device if CMD.MSE is set. Accesses from the attached device that are outside the ranges specified will be forwarded to the backbone if CMD.BME is set. The comparison performed is MB [gt]= AD[lb]31:20[rb] [lt]= ML.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MBL: [B:0, D:28, F:0] + 20h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ML				RSVD	MB			RSVD_1

Bit Range	Default & Access	Description
31:20	000h RW	Memory Limit (ML): These bits are compared with bits 31:20 of the incoming address to determine the upper 1MB aligned value of the range.
19:16	0h RO	Reserved (RSVD): Reserved
15:4	000h RW	Memory Base (MB): These bits are compared with bits 31:20 of the incoming address to determine the lower 1MB aligned value of the range.
3:0	0h RO	Reserved (RSVD_1): Reserved



23.6.8 Prefetchable Memory Base and Limit (PMBL)—Offset 24h

Accesses that are within the ranges specified in this register will be sent to the device if CMD.MSE is set. Accesses from the device that are outside the ranges specified will be forwarded to the backbone if CMD.BME is set. The comparison performed is $PMBU32:PMB [gt] = AD[1b]63:32[rb]:AD[1b]31:20[rb] [lt] = PMLU32:PML$.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PMBL: [B:0, D:28, F:0] + 24h

Power Well: Core

Default: 00010001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
PML				I64L	PMB			

Bit Range	Default & Access	Description
31:20	000h RW	Prefetchable Memory Limit (PML): These bits are compared with bits 31:20 of the incoming address to determine the upper 1MB aligned value of the range.
19:16	1h RO	64-bit Indicator (I64L): Indicates support for 64-bit addressing.
15:4	000h RW	Prefetchable Memory Base (PMB): These bits are compared with bits 31:20 of the incoming address to determine the lower 1MB aligned value of the range.
3:0	1h RO	64-bit Indicator (I64B): Indicates support for 64-bit addressing.

23.6.9 Prefetchable Memory Base Upper 32 Bits (PMBU32)—Offset 28h

Size: 32 bits

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PMBU32: [B:0, D:28, F:0] + 28h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
PMBU								

Bit Range	Default & Access	Description
31:0	00000000h RW	Prefetchable Memory Base Upper Portion (PMBU): Upper 32-bits of the prefetchable address base.



23.6.12 Interrupt Information; Bridge Control (INTR_BCTRL)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)


INTR_BCTRL: [B:0, D:28, F:0] + 3Ch

Power Well: Core

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
RSVD				DTSE		DTS		SDT		PDT		FBE		SBR		MAM		V16		VE		IE		SE		PERE		IPIN				ILINE			

Bit Range	Default & Access	Description
31:28	0h RO	Reserved (RSVD): Reserved
27	0b RW/V	Discard Timer SERR# Enable (DTSE): Reserved per PCI-Express spec. For PCI Bus Emulation Mode compatibility, if the DC.PCIBEM register is set, this register is RW else it is RO. This register is only maintained for SW compatibility and has no functionality within the port.
26	0b RO	Discard Timer Status (DTS): Reserved per PCI-Express spec. For PCI Bus Emulation Mode compatibility, this register can remain RO as no secondary discard timer exists that will ever cause it to be set.
25	0b RW/V	Secondary Discard Timer (SDT): Reserved per Express spec. For PCI Bus Emulation Mode compatibility, if the DC.PCIBEM register is set, this register is RW else it is RO. This register is only maintained for SW compatibility and has no functionality within the port.
24	0b RW/V	Primary Discard Timer (PDT): Reserved per Express spec. For PCI Bus Emulation Mode compatibility, if the DC.PCIBEM register is set, this register is RW else it is RO. This register is only maintained for SW compatibility and has no functionality within the port.
23	0b RO	Fast Back to Back Enable (FBE): Reserved per Express spec.
22	0b RW	Secondary Bus Reset (SBR): Triggers a Hot Reset on the PCI-Express port.
21	0b RW/V	Master Abort Mode (MAM): Reserved per Express spec. For PCI Bus Emulation Mode compatibility, if the DC.PCIBEM register is set, this register is RW else it is RO. This register is only maintained for SW compatibility and has no functionality within the port.
20	0b RW	VGA 16-Bit Decode (V16): When set, indicates that the I/O aliases of the VGA range (see BCTRL:VE definition below), are not enabled. 0: Execute 10-bit address decode on VGA I/O accesses. 1: Execute 16-bit address decode on VGA I/O accesses.
19	0b RW	VGA Enable (VE): When set, the following ranges will be claimed off the backbone by the root port: Memory ranges A0000h-BFFFFh I/O ranges 3B0h 3BBh and 3C0h 3DFh, and all aliases of bits 15:10 in any combination of 1's
18	0b RW	ISA Enable (IE): This bit only applies to I/O addresses that are enabled by the I/O Base and I/O Limit registers and are in the first 64KB of PCI I/O space. If this bit is set, the root port will block any forwarding from the backbone to the device of I/O transactions addressing the last 768 bytes in each 1KB block (offsets 100h to 3FFh).
17	0b RW	SERR# Enable (SE): When set, ERR_COR, ERR_NONFATAL, and ERR_FATAL messages received are forwarded to the backbone. When cleared, they are not.
16	0b RW	Parity Error Response Enable (PERE): When set, poisoned write TLPs and completions indicating poisoned TLPs will set the SSTS.DPD.



23.6.14 Device Capabilities (DCAP)—Offset 44h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

DCAP: [B:0, D:28, F:0] + 44h

Power Well: Core

Default: 00008000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	FLRC	CSPS	CSPV	RSVD_1	RBER	RSVD_2	RSVD_3	RSVD_4
					E1AL	E0AL	ETFS	PFS
								MPS


Bit Range	Default & Access	Description
31:29	000b RO	Reserved (RSVD): Reserved
28	0b RO	Function Level Reset Capable (FLRC): Not supported in Root Ports
27:26	00b RO	Captured Slot Power Limit Scale (CSPS): Not supported
25:18	00h RO	Captured Slot Power Limit Value (CSPV): Not supported
17:16	00b RO	Reserved (RSVD_1): Reserved
15	1b RO	Role Based Error Reporting (RBER): When Set, this bit indicates that the Function implements the functionality originally defined in the Error Reporting ECN for PCI Express Base Specification, Revision 1.0a, and later incorporated into PCI Express Base Specification, Revision 1.1. This bit must be Set by all Functions conforming to the ECN, PCI Express Base Specification, Revision 1.1., or subsequent PCI Express Base Specification revisions.
14	0b RO	Reserved (RSVD_2): Reserved. On previous version of the specification this was Power Indicator Present (PIP)
13	0b RO	Reserved (RSVD_3): Reserved. On previous version of the specification this was Attention Indicator Present (AIP)
12	0b RO	Reserved (RSVD_4): Reserved. On previous version of the specification this was Attention Button Present (ABP)
11:9	000b RO	Endpoint L1 Acceptable Latency (E1AL): Reserved for root ports.
8:6	000b RO	Endpoint L0 Acceptable Latency (E0AL): Reserved for Root port.
5	0b RO	Extended Tag Field Supported (ETFS): The root port never needs to initiate a transaction as a Requester with the Extended Tag bits being set. This bit does not affect the root port's ability to forward requests as a bridge as the root port always supports forwarding requests with extended tags.
4:3	00b RO	Phantom Functions Supported (PFS): No phantom functions supported



Type: PCI Configuration Register
(Size: 32 bits)

Power Well: Core

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	1	0	0	0	0	1	1	0	0	0	0	0	0	0	0	1	0				
PN								RSVD				LBNC	LARC	SDERC	CPM	EL1				ELO				APMS				MLW				SLS			



Bit Range	Default & Access	Description
23:22	00b RO	Reserved (RSVD): Reserved
21	1b RO	Link Bandwidth Notification Capability (LBNC): This port supports Link Bandwidth Notification status and interrupt mechanisms.
20	1b RO	Link Active Reporting Capable (LARC): This port supports the optional capability of reporting the DL_Active state of the Data Link Control and Management State Machine.
19	0b RO	Surprise Down Error Reporting Capable (SDERC): Set to '0' to indicate the root port does not support Surprise Down Error Reporting
18	0b RO	Clock Power Management (CPM): '0' Indicates that root ports do not support the CLKREQ# mechanism.
17:15	010b RW/O	L1 Exit Latency (EL1): Indicates an exit latency of 2us to 4us. 000b - Less than 1 us 001b - 1 us to less than 2 us 010b - 2 us to less than 4 us 011b - 4 us to less than 8 us 100b - 8 us to less than 16 us 101b - 16 us to less than 32 us 110b - 32 us to 64 us 111b - More than 64 us Note: If PXP PLL shutdown is enabled, BIOS should program this latency to comprehend PLL lock latency.
14:12	000b RO/V	L0s Exit Latency (ELO): Indicates an exit latency based upon common-clock configuration.
11:10	11b RW/O	Active State Link PM Support (APMS): Indicates the level of active state power management on this link Bits Definition 00 (Reserved) 01 L0s Entry supported 10 Reserved 11 Both L0s and L1 supported Note: If STRPFUSECFG.ASPMDIS is 1, the default of this field is '01'. Otherwise, the default of this field is '11'. If STRPFUSECFG.ASPMDIS is 1, BIOS writing '11' to this field will have the same effect as writing '01'. '01' will be reflected on this register when read and the register will turn to Read-Only once written once.
9:4	000000b RO/V	Maximum Link Width (MLW): For the root ports, several values can be taken, based upon the value of the chipset configuration register field RPC.PC1 for ports 1-4: Port # Value of PN field RPC.PC1 00 01 10 11 1 01h 02h 02h 04h 2 01h 01h 01h 01h 3 01h 01h 02h 01h 4 01h 01h 01h 01h
3:0	2h RO/V	Supported Link Speeds (SLS): Indicates the supported link speeds of the Root Port. 0001b 2.5 GT/s Link speed supported 0010b 5.0 GT/s and 2.5GT/s Link speeds supported This register reports a value of 0001b if the Root Port Gen2 Disable Fuse is set, else this register reports a value of 0010b.

23.6.17 Link Control; Link Status (LCTL_LSTS)—Offset 50h

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

LCTL_LSTS: [B:0, D:28, F:0] + 50h

Power Well: Core

Default: 00010000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
LABS	LBMS	LA	SCC	LT	RSVD	NLW	CLS	RSVD_1
LABIE	LBMIE	HAWD	ECPM	ES	CCC	RL	LD	RCBC
RSVD_2	ASPM							



Bit Range	Default & Access	Description
31	0b RW/C	Link Autonomous Bandwidth Status (LABS): This bit is Set by hardware to indicate that hardware has autonomously changed Link speed or width, without the Port transitioning through DL_Down status, for reasons other than to attempt to correct unreliable Link operation. This bit must be set if the Physical Layer reports a speed or width change was initiated by the Downstream component that was indicated as an autonomous change. The default value of this bit is 0b.
30	0b RW/C	Link Bandwidth Management Status (LBMS): This bit is Set by hardware to indicate that either of the following has occurred without the Port transitioning through DL_Down status: - A Link retraining has completed following a write of 1b to the Retrain Link bit. Note: This bit is Set following any write of 1b to the Retrain Link bit, including when the Link is in the process of retraining for some other reason. - Hardware has changed Link speed or width to attempt to correct unreliable Link operation, either through an LTSSM timeout or a higher level process. This bit must be set if the Physical Layer reports a speed or width change was initiated by the Downstream component that was not indicated as an autonomous change. The default value of this bit is 0b.
29	0b RO/V	Link Active (LA): Set to 1b when the Data Link Control and Management State Machine is in the DL_Active state, 0b otherwise.
28	0b RO/V	Slot Clock Configuration (SCC): In normal mode, root port uses the same reference clock as on the platform and does not generate its own clock.
27	0b RO/V	Link Training (LT): The root port sets this bit whenever link training is occurring, or that 1b was written to the Retrain Link bit but Link training has not yet begun. It clears the bit upon completion of link training.
26	0b RO	Reserved (RSVD): Reserved. Previously this was defined as Link Training Error (LTE) but support for this bit was removed from subsequent versions of the PCI Express specification.
25:20	00h RO/V	Negotiated Link Width (NLW): For the root ports, this register could take on several values: Port # Value of PN field RPC.PC1 00 01 10 11 1 01h 02h 02h 04h 2 01h 01h 01h 01h 3 01h 01h 02h 01h 4 01h 01h 01h 01h The value of this register is undefined if the link has not successfully trained.
19:16	1h RO/V	Current Link Speed (CLS): 0001b Link is 2.5Gb/s Link 0010b 5.0 GT/s Link The value of this field is undefined if the link is not up.
15:12	0h RO	Reserved (RSVD_1): Reserved
11	0b RW	Link Autonomous Bandwidth Interrupt Enable (LABIE): Link Autonomous Bandwidth Interrupt Enable - When Set, this bit enables the generation of an interrupt to indicate that the Link Autonomous Bandwidth Status bit has been Set.
10	0b RW	Link Bandwidth Management Interrupt Enable (LBMIE): When Set, this bit enables the generation of an interrupt to indicate that the Link Bandwidth Management Status bit has been Set. This bit is not applicable and is reserved for Endpoints, PCI Express-to-PCI/PCI-X bridges, and Upstream Ports of Switches. Functions that do not implement the Link Bandwidth Notification Capability must hardwire this bit to 0b. Default value of this bit is 0b.
9	0b RW	Hardware Autonomous Width Disable (HAWD): When Set, this bit disables hardware from changing the Link width for reasons other than attempting to correct unreliable Link operation by reducing Link width. Default value of this bit is 0b.
8	0b RO	Enable Clock Power Management (ECPM): Reserved. Not supported on Root Ports.
7	0b RW	Extended Synch (ES): When set, forces extended transmission of FTS ordered sets in FTS and extra TS2 at exit from L1 prior to entering L0.
6	0b RW	Common Clock Configuration (CCC): Reserved.



Access Method

SLCTL SLSTS: [B:0, D:28, F:0] + 58h

Power Well: Core

Default: 00000000h

Bit Range	Default & Access	Description
31:25	00h RO	Reserved (RSVD): Reserved
24	0b RW/C	Data Link Layer State Changed (DLLSC): This bit is set when the value reported in Data Link Layer Link Active field of the Link Status register is changed. In response to a Data Link Layer State Changed event, software must read Data Link Layer Link Active field of the Link Status register to determine if the link is active before initiating configuration cycles to the hot plugged device.
23	0b RO	Electromechanical Interlock Status (EMIS): Reserved as this port does not support and electromechanical interlock.
22	0b RO/V	Presence Detect State (PDS): If XCAP.SI is set (indicating that this root port spawns a slot), then this bit indicates whether a device is connected ('1') or empty ('0'). If XCAP.SI is cleared, this bit is a '1'.
21	0b RO	MRL Sensor State (MS): Reserved as the MRL sensor is not implemented.



Bit Range	Default & Access	Description
20	0b RO	Command Completed (CC): This register is RO as this port does not implement a Hot Plug Controller..
19	0b RW/C	Presence Detect Changed (PDC): This bit is set by the root port when the SLSTS.PDS bit changes state.
18	0b RO	MRL Sensor Changed (MSC): Reserved as the MRL sensor is not implemented.
17	0b RO	Power Fault Detected (PFD): Reserved as a power controller is not implemented.
16	0b RO	Attention Button Pressed (ABP): This register is RO as this port does not implement an attention button
15:13	000b RO	Reserved (RSVD_1): Reserved
12	0b RW	Data Link Layer State Changed Enable (DLLSCE): When set, this field enables generation of a hot plug interrupt when the Data Link Layer Link Active field is changed
11	0b RO	Electromechanical Interlock Control (EMIC): Reserved as this port does not support an Electromechanical Interlock.
10	0b RO	Power Controller Control (PCC): This bit has no meaning for module based hot plug.
9:8	00b RO	Power Indicator Control (PIC): This register is RO as this port does not implement a Hot Plug Controller..
7:6	00b RO	Attention Indicator Control (AIC): This register is RO as this port does not implement a Hot Plug Controller..
5	0b RW	Hot Plug Interrupt Enable (HPE): When set, enables generation of a hot plug interrupt on enabled hot plug events.
4	0b RO	Command Completed Interrupt Enable (CCE): This register is RO as this port does not implement a Hot Plug Controller..
3	0b RW	Presence Detect Changed Enable (PDE): When set, enables the generation of a hot plug interrupt or wake message when the presence detect logic changes state.
2	0b RO	MRL Sensor Changed Enable (MSE): This register is RO as this port does not implement a Hot Plug Controller..
1	0b RO	Power Fault Detected Enable (PFE): This register is RO as this port does not implement a Hot Plug Controller...
0	0b RO	Attention Button Pressed Enable (ABE): This register is RO as this port does not implement a Hot Plug Controller..

23.6.20 Root Control (RCTL)—Offset 5Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

RCTL: [B:0, D:28, F:0] + 5Ch

Power Well: Core

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				RSVD_1				PIE
								SFE
								SNE
								SCE

Bit Range	Default & Access	Description
31:16	0000h RO	Reserved (RSVD): Reserved
15:4	000h RO	Reserved (RSVD_1): Reserved
3	0b RW	PME Interrupt Enable (PIE): When set, enables interrupt generation when RSTS.PS is in a set state (either due to a '0' to '1' transition, or due to this bit being set with RSTS.PS already set).
2	0b RW	System Error on Fatal Error Enable (SFE): When set, an SERR# will be generated if a fatal error is reported by any of the devices in the hierarchy of this root port, including fatal errors in this root port. This register is not dependent on CMD.SEE being set.
1	0b RW	System Error on Non-Fatal Error Enable (SNE): When set, an SERR# will be generated if a non-fatal error is reported by any of the devices in the hierarchy of this root port, including non-fatal errors in this root port. This register is not dependent on CMD.SEE being set.
0	0b RW	System Error on Correctable Error Enable (SCE): When set, an SERR# will be generated if a correctable error is reported by any of the devices in the hierarchy of this root port, including correctable errors in this root port. This register is not dependent on CMD.SEE being set.

23.6.21 Root Status (RSTS)—Offset 60h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

RSTS: [B:0, D:28, F:0] + 60h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				PP	PS	RID		

Bit Range	Default & Access	Description
31:18	0000h RO	Reserved (RSVD): Reserved
17	0b RO/V	PME Pending (PP): Indicates another PME is pending when the PME status bit is set. When the original PME is cleared by software, it will be set again, the requestor ID will be updated, and this bit will be cleared. Root ports have a one deep PME pending queue.
16	0b RW/C	PME Status (PS): Indicates that PME was asserted by the requestor ID in RID. Subsequent PMEs are kept pending until this bit is cleared.
15:0	0000h RO/V	PME Requestor ID (RID): Indicates the PCI requestor ID of the last PME requestor. Valid only when PS is set. Root ports are capable of storing the requestor ID for two PM_PME messages, with one active (this register) and a one deep pending queue. Subsequent PM_PME messages will be dropped.

23.6.22 Device Capabilities 2 (DCAP2)—Offset 64h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

DCAP2: [B:0, D:28, F:0] + 64h

Power Well: Core

Default: 00080816h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	1	0					
RSVD												OBFS	RSVD_1				LTRMS	RSVD_2				CTDS	CTRS												

Bit Range	Default & Access	Description
31:20	000h RO	Reserved (RSVD): Reserved
19:18	10b RW/O	Optimized Buffer Flush/Fill Supported (OBFFS): 00b - OBFF is not supported. 01b - OBFF is supported using Message signaling only. 10b - OBFF is supported using WAKE# signaling only. 11b - OBFF is supported using WAKE# and Message signaling. BIOS should program this field to 00b or 10b during system initialization to advertise the level of hardware OBFF support to software. BIOS should never program this field to 01b or 11b since OBFF messaging is not supported.
17:12	00h RO	Reserved (RSVD_1): Reserved
11	1b RW/O	LTR Mechanism Supported (LTRMS): A value of 1b indicates support for the optional Latency Tolerance Reporting (LTR) mechanism capability. BIOS must write to this register with either a '1' or a '0' to enable/disable the root port from declaring support for the LTR capability.
10:5	00h RO	Reserved (RSVD_2): Reserved
4	1b RO	Completion Timeout Disable Supported (CTDS): A value of 1b indicates support for the Completion Timeout Disable mechanism.
3:0	6h RO	Completion Timeout Ranges Supported (CTRS): This field indicates device support for the optional Completion Timeout programmability mechanism. This mechanism allows system software to modify the Completion Timeout value. This field is applicable only to Root Ports, Endpoints that issue requests on their own behalf, and PCI Express to PCI/PCI-X Bridges that take ownership of requests issued on PCI Express. For all other devices this field is reserved and must be hardwired to 0000b. Four time value ranges are defined: Range A: 50us to 10ms Range B: 10ms to 250ms Range C: 250ms to 4s Range D: 4s to 64s Bits are set according to the table below to show timeout value ranges supported. 0000b Completion Timeout programming not supported. 0001b Range A 0010b Range B 0011b Ranges A [amp] B 0110b Ranges B [amp] C [It]-- This is supported 0111b Ranges A, B [amp] C 1110b Ranges B, C [amp] D 1111b Ranges A, B, C [amp] D All other values are reserved.

23.6.23 Device Control 2; Device Status 2 (DCTL2_DSTS2)—Offset 68h


Access Method

Type: PCI Configuration Register
(Size: 32 bits)

DCTL2 DSTS2: [B:0, D:28, F:0] + 68h

Power Well: Core

Default: 00000000h



31				28				24				20				16				12				8				4				0			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0							
RSVD																RSVD_1		OBFFEN		RSVD_2		LTREN		RSVD_3				CTD		CTV					

Bit Range	Default & Access	Description
31:16	0000h RO	Reserved (RSVD): Reserved
15	0b RO	Reserved (RSVD_1): Reserved
14:13	00b RW	Optimized Buffer Flush/Fill Enable (OBFFEN): 00b Disable OBFF mechanism. 01b Enable OBFF mechanism using Message signaling (Variation A). 10b Enable OBFF mechanism using Message signaling (Variation B). 11b Enable OBFF using WAKE# signaling. Note: Only encoding 00b and 11b are supported. The encoding of 01b or 10b would be aliased to 00b. If DCAP2.OBFFS is clear, programming this field to any non-zero values will have no effect.
12:11	00b RO	Reserved (RSVD_2): Reserved
10	0b RW	LTR Mechanism Enable (LTREN): When Set to 1b, this bit enables the Latency Tolerance Reporting (LTR) mechanism. For Downstream Ports, this bit must be reset to the default value if the Port goes to DL_Down status. If DCAP2.LTRMS is clear, programming this field to any non-zero values will have no effect.
9:5	00h RO	Reserved (RSVD_3): Reserved
4	0b RW	Completion Timeout Disable (CTD): When set to 1b, this bit disables the Completion Timeout mechanism. This field is required for all devices that support the Completion Timeout Disable Capability. Software is permitted to set or clear this bit at any time. When set, the Completion Timeout detection mechanism is disabled. If there are outstanding requests when the bit is cleared, it is permitted but not required for hardware to apply the completion timeout mechanism to the outstanding requests. If this is done, it is permitted to base the start time for each request on either the time this bit was cleared or the time each request was issued.
3:0	0h RW	Completion Timeout Value (CTV): In Devices that support Completion Timeout programmability, this field allows system software to modify the Completion Timeout value. This field is applicable to Root Ports, Endpoints that issue requests on their own behalf, and PCI Express to PCI/PCI-X Bridges that take ownership of requests issued on PCI Express. For all other devices this field is reserved and must be hardwired to 0000b. A Device that does not support this optional capability must hardwire this field to 0000b and is required to implement a timeout value in the range 50us to 50ms. Devices that support Completion Timeout programmability must support the values given below corresponding to the programmability ranges indicated in the Completion Timeout Values Supported field. The root port targeted configurable ranges are listed below, along with the range allowed by the PCI Express 2.0 specification. Defined encodings: 0000b Default range: 40-50ms (spec range 50us to 50ms) Values available if Range B (10ms to 250ms) programmability range is supported: 0101b 40-50ms (spec range is 16ms to 55ms) 0110b 160-170ms (spec range is 65ms to 210ms) Values available if Range C (250ms to 4s) programmability range is supported: 1001b 400-500ms (spec range is 260ms to 900ms) 1010b 1.6-1.7s (spec range is 1s to 3.5s) Values not defined above are Reserved. Software is permitted to change the value in this field at any time. For requests already pending when the Completion Timeout Value is changed, hardware is permitted to use either the new or the old value for the outstanding requests, and is permitted to base the start time for each request either when this value was changed or when each request was issued.

23.6.24 Link Capabilities 2 (LCAP2)—Offset 6Ch

Size:32 bits



Bit Range	Default & Access	Description
22:20	000b RW	Multiple Message Enable (MME): These bits are RW for software compatibility, but only one message is ever sent by the root port.
19:17	000b RO	Multiple Message Capable (MMC): Only one message is required.
16	0b RW	MSI Enable (MSIE): If set, MSI is enabled and traditional interrupt pins are not used to generate interrupts. CMD.BME must be set for an MSI to be generated. If CMD.BME is cleared, and this bit is set, no interrupts (not even pin based) are generated.
15:8	90h RW/O	Next Pointer (NEXT): Indicates the location of the next capability in the list. The default value of this register is 90h which points to the Subsystem Vendor capability structure. BIOS can determine which capabilities will be exposed by including or removing them from the capability linked list. As this register is RWO, BIOS must write a value to this register, even if it is to re-write the default value.
7:0	05h RO	Capability ID (CID): Capabilities ID indicates MSI.

23.6.29 Message Signaled Interrupt Message Address (MA)—Offset 84h

Type: PCI Configuration Register
(Size: 32 bits)

MA: [B:0, D:28, F:0] + 84h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
ADDR								RS/D

Bit Range	Default & Access	Description
31:2	00000000h RW	Address (ADDR): Lower 32 bits of the system specified message address, always DW aligned.
1:0	00b RO	Reserved (RSVD): Reserved

23.6.30 Message Signaled Interrupt Message Data (MD)—Offset 88h

Type: PCI Configuration Register
(Size: 32 bits)

MD: [B:0, D:28, F:0] + 88h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSD/D				DATA				



Bit Range	Default & Access	Description
31:16	0000h RW/O	Subsystem Identifier (SID): Indicates the subsystem as identified by the vendor. This field is write once and is locked down until a bridge reset occurs (not the PCI bus reset).
15:0	0000h RW/O	Subsystem Vendor Identifier (SVID): Indicates the manufacturer of the subsystem. This field is write once and is locked down until a bridge reset occurs (not the PCI bus reset).

23.6.33 Power Management Capability; PCI Power Management Capabilities (PMCAP_PMC)—Offset A0h

Size: 32 bits

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PMCAP_PMC: [B:0, D:28, F:0] + A0h

Power Well: Core

Default: C8030001h

31	28	24	20	16	12	8	4	0
1	1	0	0	1	0	0	0	1
PMES	D2S	D1S	AC	DSI	RSVD	PMEC	VS	CID

Bit Range	Default & Access	Description
31:27	11001b RO	PME Support (PMES): Indicates PME# is supported for states D0, D3HOT and D3COLD. The root port does not generate PME#, but reporting that it does is necessary for legacy Microsoft operating systems to enable PME# in devices connected behind this root port.
26	0b RO	D2_Support (D2S): The D2 state is not supported.
25	0b RO	D1_Support (D1S): The D1 state is not supported.
24:22	000b RO	Aux_Current (AC): Reports 0mA (self-powered), as use of this controller does not add to suspend well power consumption.
21	0b RO	Device Specific Initialization (DSI): Indicates that no device-specific initialization is required.
20	0b RO	Reserved (RSVD): Reserved
19	0b RO	PME Clock (PMEC): Indicates that PCI clock is not required to generate PME#.
18:16	011b RO	Version (VS): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NEXT): Indicates this is the last item in the list.
7:0	01h RO	Capability Identifier (CID): Value of 01h indicates this is a PCI power management capability.



23.6.34 PCI Power Management Control And Status (PMCS)—Offset A4h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PMCS: [B:0, D:28, F:0] + A4h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DTA	BPCE	B23S	RSVD	PMES	DSC	DSEL	PMEE	RSVD_1
								NSR
								RSVD_2
								PS

Bit Range	Default & Access	Description
31:24	00h RO	Data (DTA): Reserved
23	0b RO	Bus Power / Clock Control Enable (BPCE): Reserved per PCI Express specification
22	0b RO	B2/B3 Support (B23S): Reserved per PCI Express specification.
21:16	00h RO	Reserved (RSVD): Reserved
15	0b RO	PME Status (PMES): Indicates a PME was received on the downstream link.
14:13	00b RO	Data Scale (DSC): Reserved
12:9	0h RO	Data Select (DSEL): Reserved
8	0b RW/P	PME Enable (PMEE): Indicates PME is enabled. This register maintains its value through S3/4/5 states.
7:4	0h RO	Reserved (RSVD_1): Reserved
3	0b RO	No Soft Reset (NSR): When set to 1 this bit indicates that devices transitioning from D3hot to D0 because of Power State commands do not perform an internal reset. Configuration context is preserved. Upon transition from D3hot to D0 Initialized state, no additional operating system intervention is required to preserve Configuration Context beyond writing the Power State bits. When clear, devices do perform an internal reset upon transitioning from D3hot to D0 via software control of the Power State bits. Configuration Context is lost when performing the soft reset. Upon transition from D3hot to D0 state, full reinitialization sequence is needed to return the device to D0 Initialized. Regardless of this bit, devices that transition from D3hot to D0 by a system or bus segment reset will return to the device state D0 Uninitialized with only PME context preserved if PME is supported and enabled.
2	0b RO	Reserved (RSVD_2): Reserved
1:0	00b RW	Power State (PS): This field is used both to determine the current power state of the root port and to set a new power state. The values are: 00 D0 state 11 D3HOT state When in the D3HOT state, the controller's configuration space is available, but the I/O and memory spaces are not. Type 1 configuration cycles are also not accepted. Interrupts are not required to be blocked as software will disable interrupts prior to placing the port into D3HOT. If software attempts to write a '10' or '01' to these bits, the write will be ignored.



23.6.35 Manufacturer's ID (MANID)—Offset F8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MANID: [B:0, D:28, F:0] + F8h

Power Well: Core

Default: 00000F00h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	DPID	SID	MID	PD				

Bit Range	Default & Access	Description
31:28	0h RO	Reserved (RSVD): Reserved
27:24	0h RO/V	Dot portion of Process ID (DPID): The value of this field is SoC specific. Example: Process/Dot (PD) is 1265.8. Indicates the dot as .8.
23:16	00h RO/V	Stepping Identifier (SID): This field is incremented for each stepping of the part. Note that this field can be used by software to differentiate steppings when the Revision ID may not change. A single Manufacturing Stepping ID can be implemented that is readable from all functions in the chip because all of them are incremented in lock-step.
15:8	0Fh RO	Manufacturing Identifier (MID): 0Fh = Intel
7:0	00h RO/V	Process/Dot (PD): Indicates the current process. The value of this field is SoC specific. Example: Process/Dot (PD) is 1265.8. Indicates the Process (1265).

23.6.36 Advanced Error Reporting Capability Header (AECH)—Offset 100h

The AER capability can optionally be included or excluded from the capabilities list. The full AER is supported.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

AECH: [B:0, D:28, F:0] + 100h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
NCO								

Bit Range	Default & Access	Description
31:20	000h RO	Next Capability Offset (NCO): Set to 000h as this is the last capability in the list.



Bit Range	Default & Access	Description
11:6	00h RO	Reserved (RSVD_1): Reserved
5	0b RO	Surprise Down Error Status (SDE): Surprise Down is not supported.
4	0b RW/1C/P	Data Link Protocol Error Status (DLPE): Indicates a data link protocol error occurred.
3:1	000b RO	Reserved (RSVD_2): Reserved
0	0b RO	Training Error Status (TE): Not supported.

23.6.38 Uncorrectable Error Mask (UEM)—Offset 108h

When set, the corresponding error in the UES register is masked, and the logged error will cause no action. When cleared, the corresponding error is enabled. This register is only reset by a loss of core power.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

UEM: [B:0, D:28, F:0] + 108h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
		RSVD	AVS	URE	EE	MT	RO	UC
			CM	CT	FCPE	PT		RSVD_1
							SDE	DLPE
								RSVD_2
								TE

Bit Range	Default & Access	Description
31:22	000h RO	Reserved (RSVD): Reserved
21	0b RO	ACS Violation Status (AVS): Reserved. Access Control Services are not supported
20	0b RW/P	Unsupported Request Error Mask (URE): Mask for uncorrectable errors.
19	0b RO	ECRC Error Mask (EE): ECRC is not supported.
18	0b RW/P	Malformed TLP Mask (MT): Mask for malformed TLPs
17	0b RW/P	Receiver Overflow Mask (RO): Mask for receiver overflows.
16	0b RW/P	Unexpected Completion Mask (UC): Mask for unexpected completions.
15	0b RW/P	Completer Abort Mask (CM): Mask for completer abort.



Bit Range	Default & Access	Description
14	0b RW/P	Completion Timeout Mask (CT): Mask for completion timeouts.
13	0b RO	Flow Control Protocol Error Mask (FCPE): Not supported.
12	0b RW/P	Poisoned TLP Mask (PT): Mask for poisoned TLPs.
11:6	00h RO	Reserved (RSVD_1): Reserved
5	0b RO	Surprise Down Error Mask (SDE): Surprise Down is not supported.
4	0b RW/P	Data Link Protocol Error Mask (DLPE): Mask for data link protocol errors.
3:1	000b RO	Reserved (RSVD_2): Reserved
0	0b RO	Training Error Mask (TE): Not supported.

23.6.39 Uncorrectable Error Severity (UEV)—Offset 10Ch

This register gives the option to make an uncorrectable error fatal or non-fatal. An error is fatal if the bit is set. An error is non-fatal if the bit is cleared. This register is only reset by a loss of core power.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

UEV: [B:0, D:28, F:0] + 10Ch

Power Well: Core

Default: 00060011h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
		RSVD	AVS	URE	EE	MT	RO	UC
								CA
								CT
								FCPE
								PT
								RSVD_1
								SDE
								DLPE
								RSVD_2
								TE

Bit Range	Default & Access	Description
31:22	000h RO	Reserved (RSVD): Reserved
21	0b RO	ACS Violation Severity (AVS): Reserved. Access Control Services are not supported
20	0b RW/P	Unsupported Request Error Severity (URE): Severity for unsupported request reception.
19	0b RO	ECRC Error Severity (EE): ECRC is not supported.
18	1b RW/P	Malformed TLP Severity (MT): Severity for malformed TLP reception.



This register is only reset by a loss of core power

Type: PCI Configuration Register
(Size: 32 bits) **CES:** [B:0, D:28, F:0] + 110h

Default: 00000000h

Bit Range	Default & Access	Description
31:14	00000h RO	Reserved (RSVD): Reserved
13	0b RW/1C/P	Advisory Non-Fatal Error Status (ANFES): When set, indicates that a Advisory Non-Fatal Error occurred.
12	0b RW/1C/P	Replay Timer Timeout Status (RTT): Indicates the replay timer timed out.



23.6.46 Header Log DW4 (HL_DW4)—Offset 128h

Size:32 bits These registers report the header for the TLP corresponding to a detected error. This register is only reset by a loss of core power.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

HL_DW4: [B:0, D:28, F:0] + 128h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DW4

Bit Range	Default & Access	Description
31:0	00000000h RO/V/P	4th dWord of TLP (DW4): Byte12 [amp][amp] Byte13 [amp][amp] Byte14 [amp][amp] Byte15

23.6.47 Root Error Command (REC)—Offset 12Ch

This register allows errors to generate interrupts.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

REC: [B:0, D:28, F:0] + 12Ch

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

RSVD

FERE
NERE
CERE

Bit Range	Default & Access	Description
31:3	00000000h RO	Reserved (RSVD): Reserved
2	0b RW	Fatal Error Reporting Enable (FERE): When set, the root port will generate an interrupt when a fatal error is reported by the attached device.
1	0b RW	Non-fatal Error Reporting Enable (NERE): When set, the root port will generate an interrupt when a non-fatal error is reported by the attached device.
0	0b RW	Correctable Error Reporting Enable (CERE): When set, the root port will generate an interrupt when a correctable error is reported by the attached device.



23.6.48 Root Error Status (RES)—Offset 130h

This register can track more than one error and set the 'multiple' bits if a second or subsequent error occurs and the first has not been serviced. This register is only reset by a loss of core power.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

RES: [B:0, D:28, F:0] + 130h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
AEMN	RSVD						FEMR	CR
							NFEMR	
							FUF	
							MENR	
							ENR	
							MCR	

Bit Range	Default & Access	Description
31:27	00h RO	Advanced Error Interrupt Message Number (AEMN): Reserved. There is only one error interrupt allocated.
26:7	00000h RO	Reserved (RSVD): Reserved
6	0b RW/1C/P	Fatal Error Message Received (FEMR): Set when one or more Fatal Uncorrectable Error Messages have been received.
5	0b RW/1C/P	Non-Fatal Error Messages Received (NFEMR): Set when one or more Non-Fatal Uncorrectable error messages have been received
4	0b RW/1C/P	First Uncorrectable Fatal (FUF): Set when the first Uncorrectable Error message received is for a fatal error.
3	0b RW/1C/P	Multiple ERR_FATAL/NONFATAL Received (MENR): Set when either a fatal or a non-fatal error is received and the ENR bit is already set.
2	0b RW/1C/P	ERR_FATAL/NONFATAL Received (ENR): Set when either a fatal or a non-fatal error message is received.
1	0b RW/1C/P	Multiple ERR_COR Received (MCR): Set when a correctable error message is received and the CR bit is already set.
0	0b RW/1C/P	ERR_COR Received (CR): Set when a correctable error message is received.

23.6.49 Error Source Identification (ESID)—Offset 134h

Size:32 bits Identifies the source (Requester ID) of the first correctable and uncorrectable (Non-Fatal / Fatal) errors reported in the Root Error Status register. This register is only reset by a loss of core power.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

ESID: [B:0, D:28, F:0] + 134h

Power Well: Core

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
EFNFSID				ECSID				

Bit Range	Default & Access	Description
31:16	0000h RO/V/P	ERR_FATAL/NONFATAL Source Identification (EFNFSID): Loaded with the Requester ID indicated in the received ERR_FATAL or ERR_NONFATAL Message with the ERR_FATAL/NONFATAL Received register is not already set.
15:0	0000h RO/V/P	ERR_COR Source Identification (ECSID): Loaded with the Requester ID indicated in the received ERR_COR Message with the ERR_COR Received register is not already set.

23.6.50 PCI Express Status 1 (PCIESTS1)—Offset 328h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCIESTS1: [B:0, D:28, F:0] + 328h

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LTSMSTATE				RSVD	LNKSTAT	REPLAYNUM	DLLRETRY	LANESTAT
								NXTTXSEQUENUM

Bit Range	Default & Access	Description
31:24	00h RO/V	LTSM State (LTSMSTATE): Indicates the LTSM present state. 00000: DETECTQUIET 00001: DETECTACTIVE 00010: POLLINGACTIVE 00011: POLLINGCOMPLIANCE 00100: POLLINGCONFIGURATION 00101: POLLINGSPEED 00110: CONFIGRCVRCFG 00111: CONFIGRCVRCFGLPBK 01000: CONFIGIDLE 01001: L0 01010: LOWAIT 01011: RECOVERYRCVRLOCK 01100: RECOVERYRCVRCFG 01101: RECOVERYIDLE 01110: RECOVERYIDLELPBK 01111: L1ENTRY 10000: L1IDLE 10001: L2IDLE 10010: LINKCONTROLRESET 10011: LOOPBACKENTRY 10100: LOOPBACKACTIVE 10101: LOOPBACKEXITM 10110: LOOPBACKEXITS 10111: DISABLED Note: This register field could be used by REUT software to monitor the link LTSSM substates.
23	0b RO	Reserved (RSVD): Reserved
22:19	0000b RO/V	Link Status (LNKSTAT): During Link initialization the Link will always traverse this list of state from the top (0000) to the bottom of the list (0111). One or more power management states may be skipped, but the direction of list traversal will remain the same. 0000 Link Down 0001 : Link Retrain 0011 : L1 0100 : L2 0101 : L3 0111 : L0 (Link Up) 1000 : L0s (Transmit [amp] Receive) 1001 : L0s (Transmit only) 1010 : L0s (Receive only) All others reserved
18:17	00b RO/V	Replay Number (REPLAYNUM): Number of times the Retry Buffer has been replayed since the last Link initialization / re-training. When the Data Link Layer has replayed the contents of the Retry Buffer four times a Link re-training will be initiated which will reset this value back to zero.



Bit Range	Default & Access	Description
16	0b RO/V	Data Link Layer Retry (DLLRETRY): Indicates when the Data Link Layer has received a corrupted TLP or has detected a dropped packet and is currently waiting for the remote agent to re-transmit the corrupted/dropped packet. The value of Next Receive Sequence Number will be the sequence number associated with the corrupted packet.
15:12	0h RO/V	Lane Status (LANESTAT): Indicates which lanes are trained. A '1' indicates that the corresponding lane is trained (i.e. bit 0 = '1' means lane 0 is trained).
11:0	000h RO/V	Next Transmitted Sequence Number (NXTTXSEQNUM): This is the sequence number to be applied to and pre-pended to the next outgoing TLP.

23.6.51 PCI Express Status 2 (PCIESTS2)—Offset 32Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCIESTS2: [B:0, D:28, F:0] + 32Ch

Power Well: Core

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
P48PNCCWSSCMES	P37PNCCWSSCMES	P26PNCCWSSCMES	P15PNCCWSSCMES	NXTRCVSEQ				LASTACKSEQNUM

Bit Range	Default & Access	Description
31	0b RO/V	PCIe Port 4 Non-Common Clock With SSC Mode Enable Strap (P48PNCCWSSCMES): '0': PCIe port 4/8 is not enabled to operate in non-common clock mode with SSC enabled. '1': PCIe port 4/8 is enabled to operate in non-common clock mode with SSC enabled.
30	0b RO/V	PCIe Port 3 Non-Common Clock With SSC Mode Enable Strap (P37PNCCWSSCMES): '0': PCIe port 3 is not enabled to operate in non-common clock mode with SSC enabled. '1': PCIe port 3 is enabled to operate in non-common clock mode with SSC enabled.
29	0b RO/V	PCIe Port 2 Non-Common Clock With SSC Mode Enable Strap (P26PNCCWSSCMES): '0': PCIe port 2 is not enabled to operate in non-common clock mode with SSC enabled. '1': PCIe port 2 is enabled to operate in non-common clock mode with SSC enabled.
28	0b RO/V	PCIe Port 1 Non-Common Clock With SSC Mode Enable Strap (P15PNCCWSSCMES): '0': PCIe port 1 is not enabled to operate in non-common clock mode with SSC enabled. '1': PCIe port 1 is enabled to operate in non-common clock mode with SSC enabled.
27:16	000h RO/V	Next Receive Sequence Number (NXTRCVSEQ): This is the sequence number associated with the TLP that is expected to be received next.
15:12	0h RO	Reserved (RSVD): Reserved
11:0	000h RO/V	Last Acknowledged Sequence Number (LASTACKSEQNUM): This is the sequence number associated with the last acknowledged TLP.



23.6.52 PCI Express Compliance Measurement Mode (CMM) Port Control (PCIECMMPC)—Offset 330h

Note that selecting a lane number that does not exist for a port may result in undefined behavior.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCIECMMPC: [B:0, D:28, F:0] + 330h

Power Well: Core

Default: 28000016h

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
0 0 1 0				1 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 1				0 1 1 0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
RSVD				SYM3SEL				SYM2SEL				SYM1SEL				SYM0SEL				RSVD_1				ERRLANENUM				RSVD_2				INVERT				SYMERRNUMINV				SYMERRNUM				ERRDET				SLNINVCMM				AUTOINVERT				STAT				INVEN				RSVD_3				START																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															

Bit Range	Default & Access	Description
31:30	00b RO	Reserved (RSVD): Reserved
29	1b RW	CMM Symbol[3] Select (SYM3SEL): 0: selects CMM Symbol [lb]3[rb] to a control character 1: selects CMM Symbol [lb]3[rb] as a data character
28	0b RW	CMM Symbol[2] Select (SYM2SEL): 0: selects CMM Symbol [lb]2[rb] to a control character 1: selects CMM Symbol [lb]2[rb] as a data character
27	1b RW	CMM Symbol[1] Select (SYM1SEL): 0: selects CMM Symbol [lb]1[rb] to a control character 1: selects CMM Symbol [lb]1[rb] as a data character
26	0b RW	CMM Symbol[0] Select (SYM0SEL): 0: selects CMM Symbol [lb]0[rb] to a control character 1: selects CMM Symbol [lb]0[rb] as a data character
25:24	00b RO	Reserved (RSVD_1): Reserved
23:22	00b RO/V	CMM Error Lane Number (ERRLANENUM): This field contains the lane number of the failing lane. Only valid when CMM Error Detected is 1.
21:16	00h RO	Reserved (RSVD_2): Reserved
15:13	000b RO/V	CMM Invert (INVERT): Indicates which lanes are inverted 000: No inversion 001: Lanes 0 010: Lanes 1 011: Lanes 2 100: Lanes 3 This field is only valid when CMM Error Detected (bit 7) is asserted. Additionally, when CMM Error Detected is asserted this field is locked (will not be updated)
12:10	000b RO/V	CMM Symbol Error Number Invert (SYMERRNUMINV): Indicates which register number miscompared on the failing lane, if the failing lane was an inverted lane. Only valid when CMM Error Detected is 1. 000: CMM Data D0 001: CMM Data D0 010: CMM Data D0 011: CMM Data D1 100: CMM Data D2 101: CMM Data D3 110: CMM Data D0 111: CMM Data D0
9:8	00b RO/V	CMM Symbol Error Number (SYMERRNUM): Indicates which register number miscompared on the failing lane, if the failing lane was not inverted. Only valid when CMM Error Detected is 1. 00: CMM Data 0 01: CMM Data 1 10: CMM Data 2 11: CMM Data 3



Bit Range	Default & Access	Description
7	0b RW/C	CMM Error Detected (ERRDET): 1: An error was detected 0: No error detected Note: This bit will be shadowed to an observability pin that can be used for IRQ generation.
6:5	00b RW	Select Lane Number to be inverted for CMM (SLNINVCMM): Select Lane Number to be inverted for CMM
4	1b RW	CMM AutoInvert (AUTOINVERT): 1: CMM autosequences through the inversion 0: CMM does not sequence inversion
3	0b RO/V	CMM Status (STAT): This bit is set when the CMM Start bit is set and cleared when the CMM mode has been entered successfully. 0: Compliance Measurement Mode is not active or CMM mode has been entered successfully. 1: Set as a result of CMM Start bit being set.
2	1b RW	CMM Invert Enable (INVEN): 1: Enables the Inversion of the lane 0: Lane not inverted
1	1b RW	Reserved (RSVD_3): Reserved
0	0b RW	CMM Start (START): 1: Start CMM 0: Stop CMM

23.6.53 PCI Express Compliance Measurement Mode Symbol Buffer (PCIECMMSB)—Offset 334h

Size: 32 bits

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCIECMMSB: [B:0, D:28, F:0] + 334h

Power Well: Core

Default: 4ABCB5BCh

31	28	24	20	16	12	8	4	0
0	1	0	0	1	0	1	0	0
1	0	1	0	1	0	1	0	1
1	0	1	1	1	0	0	1	0
1	1	0	0	1	0	1	1	0
1	0	1	1	0	1	0	1	1
1	1	0	0	1	0	1	1	0
1	1	0	0	1	0	1	1	0
DATA3	DATA2	DATA1	DATA0					

Bit Range	Default & Access	Description
31:24	4Ah RW	CMM Data [3] (DATA3): This character contains CMM Data [lb]3[rb] that will be transmitted on the link.
23:16	BCh RW	CMM Data [2] (DATA2): This character contains CMM Data [lb]2[rb] that will be transmitted on the link.
15:8	B5h RW	CMM Data [1] (DATA1): This character contains CMM Data [lb]1[rb] that will be transmitted on the link.
7:0	BCh RW	CMM Data [0] (DATA0): This character contains CMM Data [lb]0[rb] that will be transmitted on the link.



23.7 PCI Express* Lane 0 Electrical Address Map

Table 244. Summary of PCI Express* Lane 0 Electrical Message Bus Registers—0xA6 (Global Offset 200h)

Offset	Register ID—Description	Default Value
0h	"PCS_DWORD0 (pcs_dword0)—Offset 0h" on page 3241	00010080h
4h	"PCS_DWORD1 (pcs_dword1)—Offset 4h" on page 3243	00600060h
8h	"PCS_DWORD2 (pcs_dword2)—Offset 8h" on page 3244	00000000h
Ch	"PCS_DWORD3 (pcs_dword3)—Offset Ch" on page 3246	5515ACAAh
10h	"PCS_DWORD4 (pcs_dword4)—Offset 10h" on page 3246	575555C1h
14h	"PCS_DWORD5 (pcs_dword5)—Offset 14h" on page 3247	00003E63h
18h	"PCS_DWORD6 (pcs_dword6)—Offset 18h" on page 3249	FFFFFFFFh
1Ch	"PCS_DWORD7 (pcs_dword7)—Offset 1Ch" on page 3249	00000009h
20h	"PCS_DWORD8 (pcs_dword8)—Offset 20h" on page 3250	000000C4h
24h	"PCS_DWORD9 (pcs_dword9)—Offset 24h" on page 3252	00000000h
28h	"PCS_DWORD10 (pcs_dword10)—Offset 28h" on page 3253	00000000h
2Ch	"PCS_DWORD11 (pcs_dword11)—Offset 2Ch" on page 3254	0F000000h
30h	"PCS_DWORD12 (pcs_dword12)—Offset 30h" on page 3256	00250F00h
34h	"PCS_DWORD13 (pcs_dword13)—Offset 34h" on page 3257	00000000h
38h	"PCS_DWORD14 (pcs_dword14)—Offset 38h" on page 3258	007A0018h
3Ch	"PCS_DWORD15 (pcs_dword15)—Offset 3Ch" on page 3259	04100300h
40h	"PCS_DWORD16 (pcs_dword16)—Offset 40h" on page 3261	01000001h
44h	"PCS_DWORD17 (pcs_dword17)—Offset 44h" on page 3262	01000001h
48h	"PCS_DWORD18 (pcs_dword18)—Offset 48h" on page 3264	00008080h
4Ch	"PCS_DWORD19 (pcs_dword19)—Offset 4Ch" on page 3265	00004F10h
50h	"PCS_DWORD20 (pcs_dword20)—Offset 50h" on page 3266	80808080h
54h	"PCS_DWORD21 (pcs_dword21)—Offset 54h" on page 3267	80808080h
58h	"PCS_DWORD22 (pcs_dword22)—Offset 58h" on page 3268	00000000h
5Ch	"PCS_DWORD23 (pcs_dword23)—Offset 5Ch" on page 3268	00180888h
60h	"PCS_DWORD24 (pcs_dword24)—Offset 60h" on page 3269	0001C020h

23.7.1 PCS_DWORD0 (pcs_dword0)—Offset 0h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword0: [Port: 0xA6] + (200h + 0h)

Op Codes:

0h - Read, 1h - Write

Default: 00010080h



Bit Range	Default & Access	Description
5	0h RW	reg_tx_laneup: Unused in Tx
4	0h RW	reg_left_txfifo_rst_master2: override enable = reg_lanedeskew_strap_ovrd
3	0h RW	reg_right_txfifo_rst_master2: override enable = reg_lanedeskew_strap_ovrd
2	0h RW	reg_plllinksynch_ovrden: Override enable for reg_pllinsync_ovrd 0 = Use default delay in hardware 1 = Use reg_plllinksynch_ovrd
1	0h RW	reg_plllinksynch_ovrd: override value for plllinksynch
0	0h RW	reg_tx1_cmmdisparity: Sets the initial disparity during Compliance Measurement Mode, used together with pcs_txcompliance pulse. 0 = set negative disparity 1 = set positive disparity

23.7.2 PCS_DWORD1 (pcs_dword1)—Offset 4h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs dword1: [Port: 0xA6] + (200h + 4h)

Op Codes:

0h - Read, 1h - Write

Default: 00600060h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_tx fsm_4us_delay_7_0								
reg_softreset_enable								
cri_rxeb_eiosenable								
cri_rxdigfiltsq_enable								
reg_tx fsm_delay_ovrd								
reg_tx fsm_4us_delay_11_8								
reg_pclk_rate_1_0								
reg_rate_1_0								
reg_phymode_2_0								
reg_modeovren								
reg_datawidth								
soft_reset_n								
reg_diginelben								
reg_digifelben								
reg_strapgroup_ovrdn								
reg_vank_timer_done_b_ovrd								
reg_vank_timer_done_b_ovrd_en								

Bit Range	Default & Access	Description
31:24	0h RW	reg_tx fsm_4us_delay_7_0: Override counter value for 4 us delay in tx fsm lane reset to tx biased delay
23	0h RW	reg_softreset_enable: When '1' the soft_reset_n bit will control the lane reset When '0' the hardware reset will control the lane reset Note for DP: In addition to soft_reset_n, which will reset both TX0 and TX 1 in the lane, the reg_tx1_soft_reset_n bit can be used to reset only TX1 in the lane and reg_tx2_soft_reset_n bit can be used to reset only TX2
22	1h RW	cri_rxeb_eiosenable: When 1 enables EIOS based Rx power down



Bit Range	Default & Access	Description
21	1h RW	cri_rxdigfiltlsq_enable: When 1 enables unsquelch based Rx power up in P0 or P0s
20	0h RW	reg_txfsfm_delay_ovrd: Override enable bit for reg_txfsfm_4us_delay
19:16	0h RW	reg_txfsfm_4us_delay_11_8: Override counter value for 4 us delay in txfsfm lane reset to txbiasen delay
15:14	0h RW	reg_pclk_rate_1_0: Override for pclk_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
13:12	0h RW	reg_rate_1_0: Override for i_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
11:9	0h RW	reg_phymode_2_0: Override for PHY Mode Selection 000 = PCIE 001 = USB3 010 = GbE 011 = SATA/SAPIS 100 = Display 101 = DMI 110 = CIO 111 =Reserved
8	0h RW	reg_modeovren: When asserted selects register override bits for phymode, datawidth etc
7:6	1h RW	reg_datawidth: Override for Tx data interface width. 00 - Unused 01 - x8/x10 width (default) 10 - x16/x20 width 11 - x32/x40 width
5	1h RW	soft_reset_n: Active low soft reset override
4	0h RW	reg_diginelben: Override for near end digital loopback.
3	0h RW	reg_digifelben: Override for far end digital loopback
2	0h RW	reg_strapgroup_ovrden: Override Enable for Strap Group
1	0h RW	reg_yank_timer_done_b_ovrd: Override for yank_timer_done_b
0	0h RW	reg_yank_timer_done_b_ovrd_en: Override Enable for yank_timer_done_b

23.7.3 PCS_DWORD2 (pcs_dword2)—Offset 8h

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword2: [Port: 0xA6] + (200h + 8h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_pibiasoff_delay_3_0	cri_sqdbexittimer_override_3_0	cri_sqdbentrytimer_override_5_0	reg_rxdrcgtsqsel_1_0	cri_reut_SlaveSideDataCheckingEn	cri_sqdbtimer_ovren	cri_rxpwrfsm_timer_ovren	reg_rxidle	cri_rxrawdata_sel
				cri_dynkalign_eco3302703_mode	cri_dynkalign_eco3302703_ovren	reg_rxpwrfsm_pibiasoff_ovrride	cri_reset_kalignlck	cri_ebptrrst
							cri_comdispfix	cri_forcebankhit
							cri_kalignmode_1_0	cri_skpprocdis
								cri_elasticbuffer_maskdis

Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_pibiasoff_delay_3_0: Override value for delay (in 2ns increments) between deassertion of opianclkbufen and opibiasen
27:24	0h RW	cri_sqdbexittimer_override_3_0: Rx squelch exit debounce timer
23:18	0h RW	cri_sqdbentrytimer_override_5_0: Rx squelch entry debounce timer
17:16	0h RW	reg_rxdrcgtsqsel_1_0: Squelch output select
15	0h RW	cri_reut_SlaveSideDataCheckingEn: Enable REUT slave side checking while in loopback slave
14	0h RW	cri_sqdbtimer_ovren: Squelch debounce timer override enable
13	0h RW	cri_rxpwrfsm_timer_ovren: Rx power management fsm timer override enable
12	0h RW	reg_rxidle: Chicken bit to override i_rxidle from controller and keep Rx in P0 or P0s
11	0h RW	cri_rxrawdata_sel: When asserted bypass K-align, 10b/8b decoder and Elastic buffer
10	0h RW	cri_dynkalign_eco3302703_mode: Kalign Mode Override Value When cri_dynkalign_eco3302703_ovren is set, this value selects kalignmode 0 - use register bits cri_kalignmode[1:0] to select kalignmode 1 - select the 4 COM kalign mode'
9	0h RW	cri_dynkalign_eco3302703_ovren: Kalign Mode Override Enable Overrides kalign mode select pin, allowing config bit kalignmode_override_val to select kalignmode.
8	0h RW	reg_rxpwrfsm_pibiasoff_ovrride: When asserted selects reg_rxpwrfsm_pibiasoff_delay[3:0]
7	0h RW	cri_reset_kalignlck: When asserted resets Kalign lock indication and Kalign is performed again. The conditions when this would assert includes and is not restricted to any power management states (L0s, L1) or polling quiet states etc.
6	0h RW	cri_ebptrrst: Global broadcast to all lanes that the Elastic Buffer pointers should be reset. This is a pulse and will be generated when we need to reset the pointers because of collision or various other reasons.
5	0h RW	cri_comdispfix: Chicken bit to force disparity in dynamic K-align mode



Bit Range	Default & Access	Description
4	0h RW	cri_forcebankhit: Chicken bit to enable data appear on NOA post k-align lock although k-align block is not achieving lock. This is only for NOA observeability and not for other purpose
3:2	0h RW	cri_kalignmode_1_0: KALIGN Mode Select 00 = dynamic kalign all the time. Accounts for bit slips on incoming stream which can cause symbol to be detected on different bank 10 = dynamic kalign up to L0 x1 = static kalign (same as GDG). Assumes symbol always detected on same data bank
1	0h RW	cri_skpprocdis: SKIP Ordered-Set Processing Disable When this configuration bit is asserted, then SKIP ordered=sets will be ignored (in EB block). Used in Elastic buffer block. 0 = Normal operation. SKIP ordered=sets will be processed by the Elastic Buffer 1 = SKIP processing disabled.
0	0h RW	cri_elasticbuffer_maskdis: Config bit (chicken bit) to disable the masking logic after elec idle ordered set is seen

23.7.4 PCS_DWORD3 (pcs_dword3)—Offset Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword3: [Port: 0xA6] + (200h + Ch)

Op Codes:

0h - Read, 1h - Write


Default: 5515ACAAh

31	28	24	20	16	12	8	4	0
0	1	0	1	0	1	0	1	0
0	1	0	1	0	1	0	1	0
cri_dfx_patbuf_55_48	cri_dfx_patbuf_63_56	cri_dfx_patbuf_71_64	cri_dfx_patbuf_79_72					

Bit Range	Default & Access	Description
31:24	55h RW	cri_dfx_patbuf_55_48: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
23:16	15h RW	cri_dfx_patbuf_63_56: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
15:8	ACh RW	cri_dfx_patbuf_71_64: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
7:0	AAh RW	cri_dfx_patbuf_79_72: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.

23.7.5 PCS_DWORD4 (pcs_dword4)—Offset 10h

Access Method



Bit Range	Default & Access	Description
31	0h RW	cri_dfx_patbuftrain: Pattern Buffer Manual Training When DFXPATBUFTRAINOVR and DFXLCCESTART are asserted, this manually controls whether the Pattern Buffers are in training or have completed training. 0 : Send training patterns (default) 1 : Send contents of DFXPATBUF
30:28	0h RW	cri_dfx_prbspoly_2_0: PRBS Polynomial Select the polynomial to be used by the PRBS in the Pattern Generator and Pattern Checker. PRBS support 10b or 8b, which is indicated by the msb. 000 - $x^{16} + x^5 + x^4 + x^3 + 1$ (USB3/PCIe Scrambler) (8b) 001 - $x^{16} + x^{15} + x^{13} + x^4 + 1$ (SATA scrambler) (8b) 010 - $x^{31} + x^{28} + 1$ (8b) 011 - $x^7 + x^6 + 1$ (8b) 100 - $x^{15} + x^{14} + 1$ (10b) 101 - $x^{23} + x^{18} + 1$ (10b) 110 - $x^{31} + x^{28} + 1$ (10b) 111 - $x^7 + x^6 + 1$ (10b)
27:26	0h RW	cri_dfx_patbufsize_1_0: Pattern Buffer Size Select the size of the Pattern Buffer to use. The MSB will always be bit 79. The LSB will depend on this select and the DFXLCCESTART (10b or 8b mode). 00 : full 80b buffer (Default) 01 : 70b (while in 10b mode), 56b (while in 8b mode) 10 : 40b (while in 10b mode), 32b (while in 8b mode) 11 : 10b (while in 10b mode), 8b (while in 8b mode)
25	0h RW	cri_dfx_patbufloop: Pattern Buffer Looping Enable Enables looping of the Pattern Buffer. By default, the contents of Pattern Buffer will be used once and stop. Alternatively, the Pattern Buffer will continue to loop until the DFXLCCESTART is de-asserted. 0 : Run Pattern Buffer only once (default) 1 : Loop Pattern Buffer until stopped
24	0h RW	cri_dfx_patbufdwidth: Pattern Buffer Data Width Selects between 10 bit or 8 bit data width for the Pattern Buffer. Determines where in the Tx/Rx path the data is inserted/retrieved. 0 : 10b (default) 1 : 8b
23	0h RW	cri_dfx_patbuftrainovr: Pattern Buffer Training Override Enables manual training of the Pattern Buffer instead of the automated coordination between the Pattern Checker and Pattern Generator. When asserted, the DFXPATBUFTRAIN bit will be used to force when training is active and when it is complete. 0 : Automatic Training (default) 1 : Enable Manual Training
22	0h RW	cri_dfx_marginmode: Margin mode Overrides standard setup configurations for use with Eye Width Margining. 0 : Standard Mode (default) 1 : Margin Mode enabled
21	0h RW	cri_dfx_chk_sel: Pattern Checker 8b10b Select This determines where Rx data is compared, either in the 10-bit domain before decode or after 10b-8b decoding. 0: 10b domain 1: 8b domain
20	0h RW	cri_dfx_patchken: Pattern Checker Enable 0 : Disable Pattern Checker (default) 1 : Enable Pattern Checker
19	0h RW	cri_dfx_patgenen: Pattern Generator Enable This will activate the Dfx bypass muxes in the PCS Tx path. 0 : Disable Pattern Generator (default) 1 : Enable Pattern Generator
18	0h RW	cri_dfx_clrerrcnt: Clear Error Counter Resets the Pattern Checker's error counter. 0 : Error Counter allowed to run (default) 1 : Error Counter held in reset
17	0h RW	cri_dfx_lcereset: Local Compare Engine Reset Resets all components of the Local Compare Engine in both the Pattern Generator and the Pattern Checker. 0 : LCE not in reset (default) 1 : LCE in reset
16	0h RW	cri_dfx_lcestart: Local Compare Engine Start Controls the starting and stopping of the LCE. Allows for simultaneous or independent start across lanes. Once stopped, a DFXLCERESET is usually required. 0 : LCE stopped (default) 1 : LCE running
15:8	3Eh RW	cri_dfx_patbuf_7_0: Pattern Buffer Storage In 10b mode, the buffer is read as eight 10b chunks. The first 10 bits should not equal the Comma Symbol: '0011111010' (or its inversion '1100000101'). In 8b mode, the buffer is read as eight 10b chunks, where the 10th bit is unused and the 9th bit is the K-bit indicator. The first 10 bits should not equal the Comma Symbol: 'xx10111100'. DFXPATBUF[78] should not be '1'.
7:0	63h RW	cri_dfx_patbuf_15_8: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.



23.7.7 PCS_DWORD6 (pcs_dword6)—Offset 18h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword6: [Port: 0xA6] + (200h + 18h)

Op Codes:

0h - Read, 1h - Write

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
cri_dfx_prbseed_7_0								cri_dfx_prbseed_31_24

Bit Range	Default & Access	Description
31:24	FFh RW	cri_dfx_prbseed_7_0: PRBS Seed Can be used for HVM determinism. The use of all zeroes can result in lockup.
23:16	FFh RW	cri_dfx_prbseed_15_8: PRBS Seed See cri_dfx_prbseed[7:0] description.
15:8	FFh RW	cri_dfx_prbseed_23_16: PRBS Seed See cri_dfx_prbseed[7:0] description.
7:0	FFh RW	cri_dfx_prbseed_31_24: PRBS Seed See cri_dfx_prbseed[7:0] description.

23.7.8 PCS_DWORD7 (pcs_dword7)—Offset 1Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)


pcs_dword7: [Port: 0xA6] + (200h + 1Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000009h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
dfx_cri_errcnt_7_0								cri_dfx_prbstraincnt_3_0



Bit Range	Default & Access	Description
31:24	X RO	dfx_cri_errcnt_7_0: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
23:16	X RO	dfx_cri_errcnt_15_8: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
15	X RO	i_rxcaldone: RX Calibration Cycles Complete Indicator
14	X RO	dfx_cri_lcemgnerr: Local Compare Engine Margin Error Indicates that the error counter has reached its max value. This can be used by the Rx upartition during Margin Mode to determine when the eye width has closed.
13	X RO	cri_dfx_patgen2active: Pattern Generator 2 Active status indicator In a lane with two Tx paths, this indicates that the second Pattern Generator is in progress. The DFXPATGENACTIVE will only indicate that the first Pattern Generator is in progress.
12	X RO	dfx_cri_patbufallfail: Pattern Buffer All Fail status indicator Indicates that there has not been a single matching Pattern Buffer pattern. This could signify that an error occurred during training.
11	X RO	dfx_cri_patchkactive: Pattern Checker Active status indicator Indicates that the Pattern Checker is in progress (either Pattern Buffer or PRBS).
10	X RO	dfx_cri_patgenactive: Pattern Generator Active status indicator Indicates that the Pattern Generator is in progress (either Pattern Buffer or PRBS).
9	X RO	dfx_cri_lctraindone: Local Compare Engine Training Done status indicator Indicates that the Pattern Checker training is completed (either Pattern Buffer or PRBS). The Pattern Checker is now synchronized to the Pattern Generator.
8	X RO	dfx_cri_lctrainactive: Local Compare Engine Training Active status indicator Indicates that the Pattern Checker training is in progress (either Pattern Buffer or PRBS).
7	0h RW	reserved501: reserved
6	0h RW	cri_dfx_patgen2en: Pattern Generator 2 Enable In a lane with two Tx paths, this enables the second Pattern Generator. The DFXPATGENEN will enable the first Pattern Generator. 0 : Disable second Pattern Generator (default) 1 : Enable second Pattern Generator
5:4	0h RW	cri_dfx_maxerrcnt_1_0: Maximum Error Count Selectable maximum value that the DFXERRCNT can reach before the Local Compare Engine is automatically stopped. 00 : 2^{16} (default) 01 : 2^{10} 10 : 2^8 11 : 2^4
3:0	9h RW	cri_dfx_prbstraincnt_3_0: PRBS Training Count The number of consecutive cycles that the Pattern Checker's PRBS must be error free before it is considered synchronized. Default is 9.

23.7.9 PCS_DWORD8 (pcs_dword8)—Offset 20h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword8: [Port: 0xA6] + (200h + 20h)

Op Codes:

0h - Read, 1h - Write

Default: 000000C4h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reg_partial	reg_slumber	reg_tx2_cdr_override_2_0	reg_cdr_override_2_0	reg_ebuffmode	reg_usedclockchannel_1_0	reg_usedclockchannel_ovrride	reg_gbl_ovrride	reg_tx1_pclkon_inp2
								reg_tx2_pclkon_inp2
								reg_tx2_txenable
								cri_rxeb_ptr_init_3_0
								reg_powerfsm_ovrride
								reg_suspend
								reg_pclkcfginput
								reg_useqclock
								cri_rxeb_hiwater_3_0
								cri_rxeb_lowater_3_0

Bit Range	Default & Access	Description
31	0h RW	reg_partial: Override for i_partial
30	0h RW	reg_slumber: Override for i_slumber
29:27	0h RW	reg_tx2_cdr_override_2_0: Override for cdr_override strap for second tx2
26:24	0h RW	reg_cdr_override_2_0: Override for cdr_override strap
23	0h RW	reg_ebuffmode: Override for ebuffmode (no functionality in p1271 phase1 design)
22:21	0h RW	reg_usedclockchannel_1_0: Selects the active clock channel
20	0h RW	reg_usedclockchannel_ovrride: When asserted selects reg_usedclockchannel[1:0]
19	0h RW	reg_gbl_ovrride: Global override select
18	0h RW	reg_tx1_pclkon_inp2: When asserted keeps PCLK running in P2 mode. For DP this is used for Lane1
17	0h RW	reg_tx2_pclkon_inp2: When asserted keeps PCLK running in P2 mode. This is reserved (no impact) for PCIe/DMI and used for DP Lane2
16	0h RW	reg_tx2_txenable: Override for i_txenable for tx2
15:12	0h RW	cri_rxeb_ptr_init_3_0: Config override for initial value of Rx elastic buffer read pointer
11	0h RW	reg_powerfsm_ovrride: When asserted overrides for Tx power fsm are selected
10	0h RW	reg_suspend: Override for suspend
9	0h RW	reg_pclkcfginput: Override for pclkcfginput strap
8	0h RW	reg_useqclock: Override for useqclock; MUX select for I or Q clk for TX clocking
7:4	Ch RW	cri_rxeb_hiwater_3_0: Elastic buffer high watermark based on which SKP is removed

23.7.10 PCS_DWORD9 (pcs_dword9)—Offset 24h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword9: [Port: 0xA6] + (200h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31	0h RW	reserved502: reserved
30:26	0h RW	reg_strapgroup_4_0: Override for i_strapgroup
25:24	0h RW	reg_powerdown_1_0: Override for i_powerdown
23	0h RW	reg_pcs_txcmnkeepdisable_ovrd: Override for ipcs_txcmnkeepdisable input 0: Use value on ipcs_txcmnkeepdisable input pin to determine o_txgohighz state in P2/ slumber 1: Force pcs_txcmnkeepdisable to 0
22:18	0h RW	reg_straplane_5_0: Override for i_straplane
17	0h RW	reg_tx1_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx1 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
16	0h RW	reg_tx2_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx2 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
15	0h RW	reg_txdatavalid: Override for i_txdatavalid (register is NOT used)
14:13	0h RW	reg_txdeemp_1_0: Override for i_txdeemp



Bit Range	Default & Access	Description
12:10	0h RW	reg_txmargin_2_0: Override for i_txmargin
9	0h RW	reg_txswing: Override for i_txswing
8	0h RW	reg_txenable: Override for i_txenable
7:6	0h RW	reg_txterm_vcc_1_0: Override for txterm_vcc strap
5	0h RW	reg_txdetrxlpbk: Override for i_txdetrxlpbk
4	0h RW	reg_txelectidle: Override for i_txelectidle
3	0h RW	reg_txcompliance: Override for i_txcompliance
2	0h RW	reg_txoneszeroes: Override for i_txoneszeroes
1:0	0h RW	reg_latencyoptim_1_0: Override for i_latencyoptim

23.7.11 PCS_DWORD10 (pcs_dword10)—Offset 28h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword10: [Port: 0xA6] + (200h + 28h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_timer_WAIT_RX_PT_CLK_3_0	reg_rxpwrfsm_timer_ENABLE_RX_3_0	reg_rxpwrfsm_timer_RX_SEQEN_3_0	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0		reg_clk_valid_cnt_7_0	reg_rxterm	reg_rxpolarity	reg_rxeqtrain
						reg_rxsquelchen	cri_rxpwrfsm_sgentimer_ovrden	reg_rxintfritren_override
							reg_rxintfritren_l	reg_clk_valid_cnt_ovrd



Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PI_CLK_3_0: Rx Power state m/c timer value used to enable PI clock
27:24	0h RW	reg_rxpwrfsm_timer_ENABLE_RX_3_0: Rx Power state m/c timer value used to enable receivers
23:20	0h RW	reg_rxpwrfsm_timer_RX_SQEN_3_0: Rx Power FSM Rx Squelch Enable Timer Override Value Affect squelch enable startup sequence during 'synchronous' squelch startup mode. 0000 - Invalid 0001 - 1 susclk period ... 1111 - 15 susclk period
19:16	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0: Rx Power state m/c timer value used to enable PI BIAS
15:8	0h RW	reg_clk_valid_cnt_7_0: Over ride value for clock valid delay in clock top block before toggling phystatus.
7	0h RW	reg_rxterm: Override for i_rxterm
6	0h RW	reg_rxpolarity: Override for i_rxpolarity
5	0h RW	reg_rxeqtrain: Override for i_rxeqtrain
4	0h RW	reg_rxsquelchen: Override for i_rxsquelchen
3	0h RW	cri_rxpwrfsm_sqentimer_ovrden: Squelch Enable Timer Override Enable Used to override the squelch enable timer in PCS with the timer value set by the Rx Squelch Enable timer register (reg_rxpwrfsm_timer_RX_SQEN[3:0]).
2	0h RW	reg_rxintfltren_override: Rx Integral Filter Override Select 0: selects i_rxintfltren_l input pin. 1: selects reg_rxintfltren_l register
1	0h RW	reg_rxintfltren_l: Override for Rx integral filter enable i_rxintfltren_l
0	0h RW	reg_clk_valid_cnt_ovrd: Override enable for reg_clk_valid_cnt

23.7.12 PCS_DWORD11 (pcs_dword11)—Offset 2Ch

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword11: [Port: 0xA6] + (200h + 2Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0F000000h



Intel Atom® Processor E3800 Product Family
Datasheet
3255



Access Method

pcs_dword12: [Port: 0xA6] + (200h + 30h)

Op Codes:

Default: 00250F00h

Intel Atom® Processor E3800 Product Family
Datasheet
3256



Bit Range	Default & Access	Description
31	0h RW	reg_tx fsm_200ns_ovrd: Override reg_tx fsm_200ns_delay+G2
30:24	0h RW	reg_tx fsm_200ns_delay_6_0: Override value of counter for 200ns delay between txen and txloadgenen
23	0h RW	reg_loadgen2txen_fall_ovrd: reserved
22:20	2h RW	reg_tx2_stagger_mult_2_0: Stagger multiplier for Rx (or Tx1) (Same decoding as tx1_stagger_mult[2:0]) For Display, this multiplier applies to Tx2. For non-Display PHYs, this multiplier applies to the Rx. The multiplier limit for the Rx is 8x (3'b100); anything beyond that is invalid.
19	0h RW	reg_lanestagger_by_group: When = 1, uses group number for lane staggering, by devalues lane number is used.
18:16	5h RW	reg_tx1_stagger_mult_2_0: Stagger multiplier for Tx (or Tx1) These bits set the lane staggering multiplier for the transmitter based on the 'linkclk' period. 000 - 0x 001 - 1x 010 - 2x 011 - 4x 100 - 8x 101 - 16x 110 - 32x 111 - 64x For Display, this multiplier applies to Tx1.
15:14	0h RW	reserved509: reserved
13	0h RW	reserved510: reserved
12:8	Fh RW	reg_tx1_stagger_mask_4_0: Mask bit for lane number. Used to group lanes for staggering
7	0h RW	reserved507: reserved
6	0h RW	reg_lanestagger_strap_ovrd: When 1 config override for lane stagger strap (bits [4:0] of this register) is selected
5	0h RW	reserved508: reserved
4:0	0h RW	reg_lanestagger_strap_4_0: Override for lane stagger strap

23.7.14 PCS_DWORD13 (pcs_dword13)—Offset 34h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword13: [Port: 0xA6] + (200h + 34h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0			
visa_en		reserved512		visa_clk_sel1_4_0				visa_lane_sel1_7_0				visa_bypass		reserved511		visa_clk_sel0_4_0				visa_lane_sel0_7_0															



Access Method

pcs_dword14: [Port: 0xA6] + (200h + 38h)

Op Codes:

Default: 007A0018h

Bit Range	Default & Access	Description
31	0h RW	reg_clkbuf_stagger_ovrd: Override enable for reg_clkbuf_stagger_cnt
30	0h RW	reg_clkbuf_stagger_cnt_10: Counter override value for staggering delay of clock buffer control signals.



Bit Range	Default & Access	Description
29	0h RW	reg_slowclk_ovrden: Slow Clock Override Enable When set 1'b1, reg_slowclocken and reg_sclk250en are valid. When cleared 1'b0, output of FSM will drive slow clock enable.
28:24	0h RW	reg_txloadgenen2txen_fall_delay_4_0: reserved
23:20	7h RW	o_cmlmuxsthsel_3_0: CML Mux strength control
19:16	Ah RW	o_cmlsthsel_3_0: RX CML driver strength
15:12	0h RW	o_pcisel_3_0: I clk phase correction control
11:8	0h RW	o_pcqsel_3_0: Q clk phase correction control
7	0h RW	o_phaseicen: Iclk phase correction enable.
6	0h RW	o_phaseqcen: Qclk phase correction enabled.
5	0h RW	o_pcbypass: Phase correction bypass.
4	1h RW	o_slowclocken: Slow clock 1 enable Only valid if slow clock override enable is set 1'b1
3	1h RW	o_sclk250en: Slow clock 2 enable Only valid if slow clock override enable is set 1'b1
2:0	0h RW	cri_kalign_com_cnt: Upper 3 bits of a 7-bit counter that counts number of COM characters found. Used for special SAPIS mode where spread spectrum clocking can be utilized. Note: This register is used in conjunction with another PCS register cri_kalignmode[1:0] = 10 Register value Minimum COM count to achieve symbol lock 000 - 18 001 - 34 010 - 50 011 - 66 100 - 82 101 - 98 110 - 114 111 - 130

23.7.16 PCS_DWORD15 (pcs_dword15)—Offset 3Ch

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword15: [Port: 0xA6] + (200h + 3Ch)

Op Codes:

0h - Read, 1h - Write

Default: 04100300h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
13:8	3h RW	reserved513: reserved
7:0	0h RW	reg_clkbuf_stagger_cnt_9_2: Counter override value for staggering delay of clock buffer control signals.

23.7.17 PCS_DWORD16 (pcs_dword16)—Offset 40h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword16: [Port: 0xA6] + (200h + 40h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h

[illegible]

Bit Range	Default & Access	Description
31	0h RW	squelch_shunt_ovrd_en: Squelch Shunt Pulse Duration Override Enable Overrides the hardware default shunt pulse duration value 1: Shunt Pulse Duration Override Enable 0: Shunt Pulse Duration Override Disable
30:28	0h RW	squelch_shunt_cnt_2_0: Squelch Shunt Pulse Duration Override Value 000 = No shunt pulse generated 001 = 1 susclk cycles ... 111 = 7 susclk cycles
27	0h RW	reserved520: reserved
26	0h RW	i_rxsqfsm_timersel: Squelch FSM Timer Select 0 - Selects 25Mhz values for squelch timer and shunt pulse generation . 1 - Selects 100Mhz values for squelch timer and shunt pulse generation. This register is applicable to synchronous squelch startup mode.
25	0h RW	i_rxsq_asyncmode_h: Squelch Async Startup Mode This squelch startup mode is power state independent. When enabled, the squelchen signal sent to Modphy will asynchronously enable the squelch detector circuit. Once enabled, the squelch detector circuit will asynchronously send an unfiltered/unqualified squelch indication signal out of Modphy. The squelch indication signal will initially be unstable, so it is up to the consumer of this signal to filter/qualify it accordingly. The asynchronous squelch startup mode is beneficial because it significantly reduces the squelch startup latency. This decrease in latency does come at the cost of slightly higher power when squelch is not enabled as the IREF and Squelch Keeper circuits must remain enabled. When disabled, the squelch startup sequence is synchronous in nature and the squelch indication signal sent out of Modphy is stable/filtered.
24	1h RW	i_rxsquelchstby_h: Fast Squelch Enable Mode Bit to keep the IREF (ivrefen) on during P2 and reduce squelch startup time.



Bit Range	Default & Access	Description
23:18	0h RW	reserved519: reserved
17:16	0h RW	cri_dfx_evenoddmask_1_0: Pattern Checker Even/Odd Bit Error Mask Select 00 : no masking; all errors will be counted 01: select odd path, mask even path; only errors on bits [1,3,5,7,9] are counted 10: select even path, mask odd path; only errors on bits [0,2,4,6,8] are counted 11: reserved;
15:12	0h RW	reserved518: reserved
11:10	0h RW	cri_dfx_lce2patsrc_1_0: Local Compare Engine 2 Pattern Source In a lane with two Tx paths, this selects between using Pattern Buffer or PRBS as source of LCE patterns for the second LCE. The DFXLCEPATSR selects for the first LCE. 0 : Pattern Buffer (default) 1 : PRBS
9:8	0h RW	cri_dfx_lcepatsrc_1_0: Local Compare Engine Pattern Source. Selects between using Pattern Buffer or PRBS as source of LCE patterns. 00 : Pattern Buffer; use LCE default training pattern; 01: Pattern Buffer; use the first 40b of pattern buffer for training. 10: PRBS; use LCE default training pattern; 11: PRBS; use the first 40b of pattern buffer for training.
7:6	0h RW	reserved517: reserved
5:4	0h RW	txloadgen_ctr_val: TxLoadGen Pulse Width Control Controls the pulse width of txloadgenen from PCS to Tx upar. This is used in MAC initiated digital far end loopback mode in PCIE family. 00 - txloadgenen pulse width is 4 symbol clocks (default) 01- txloadgenen pulse width is 2 symbol clocks 10 - txloadgenen pulse not generated 11 - txloadgenen pulse width is 6 symbol clocks
3	0h RW	cri_txhighpowerei_ovrden: TxHighPowerEI Override Mode Enable 0 - TxHighPowerEI to TxuPAR driven by Logic 1 - TxHighPowerEI to TxuPAR driven by override register value(s).
2	0h RW	cri_tx1highpowerei_ovrdval: Tx1HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx1HighPowerEI disabled 1 - Tx1HighPowerEI enabled
1	0h RW	cri_tx2highpowerei_ovrdval: Tx2HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx2HighPowerEI disabled 1 - Tx2HighPowerEI enabled
0	1h RW	p2_fast_exit_en: P2 Fast Exit Mode Enable Common Mode sustainer will be enabled during P2 when this bit is asserted. 1: P2 Fast Exit Mode Enable 0: P2 Fast Exit Mode Disable

23.7.18 PCS_DWORD17 (pcs_dword17)—Offset 44h

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword17: [Port: 0xA6] + (200h + 44h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
oiredfxsel_1_0	iopampsfpn_h	iopampsfn_h	iopampn_h	iopampn_h	monanapgn	monubufbypassen	reserved522	reg_ivrefen
								ivrefen_ovrd
							reserved523	
							oiredfurmonsel	lrcdisable
							reserved521	
							lrc_rdy_pulsegen	
							lrc_rdy_target_1_0	
							lrc_rdy_ovd	
							rxtermprccen	
							rxvgaprrccen	
							txpmrrccen	
							irefpmrrccen	
							rxtermprccen	
							rxvgaprrccen	
							txpmrrccen	
							irefpmrrccen	

Bit Range	Default & Access	Description
31:30	0h RW	oiredfxsel_1_0: IREF Voltage Monitor Select Selects voltage to monitor within the IREF block. 00 - vref 01 - pgate 10 - vbc 11 - vref loop
29	0h RW	iopampsfpn_h: (NOT USED - noconned)
28	0h RW	iopampsfn_h: (NOT USED - noconned)
27	0h RW	iopampn_h: DC Monitor Unity-Gain Buffer Enable 0: disable (default) 1: enable
26	0h RW	iopampn_h: (NOT USED - noconned)
25	0h RW	monanapgn: DC Monitor to Monitor Port Enable Enables DC monitor passgate to monitor port via analog observability abutment.
24	1h RW	monubufbypassen: DC Monitor Unity-Gain Buffer Bypass 0: no bypass 1: bypass (default - required for LRC)
23:22	0h RW	reserved522: reserved
21	0h RW	reg_ivrefen: IvrefEn Override Value Register is valid when override mode is enabled (ivrefen_ovrd). During this mode, this register will have direct control to enable/disable the ivref opamp. 0 - Disable ivref opamp 1 - Enable ivref opamp
20	0h RW	ivrefen_ovrd: IvrefEn Override Select 0 - the enable for the ivref opamp (ivrefen) is driven by the FSM. 1 - the ivrefen is driven by the register (reg_ivrefen).
19:17	0h RW	reserved523: reserved
16	0h RW	oiredfurmonsel: IREF Current Monitor Select Enables current mirror from the IREF block to the 'shared' analog monitor port.
15	0h RW	lrcdisable: LRC Disable This bit disables the LRC. Any token received is passed to the next lane.
14:12	0h RW	reserved521: reserved
11	0h RW	lrc_rdy_pulsegen: LRC Ready PulseGen Generates a pulse 1 cal_clk cycle wide on the lrc_rdy signal to all four targets; does not recompute local Rcomp code. Values in DWD 0x14 (*rccodes[7:0]) will be latched into targets. User must clear this bit before generating another pulse. Note: User should disable PM and PER. FSM can take control and codes can be overridden.
10:9	0h RW	lrc_rdy_target_1_0: LRC Ready Pulse Target Indicates which lrc target to recompute when lrc_rdy_ovd is strobed 00: irefrrccode 01: txrrccode 10: rxtermrrccode 11: rxvgarrrccode



Bit Range	Default & Access	Description
31:24	80h RW	rxvgarccode_7_0: Rx VGA Rcomp Codes These bits are the final binary code used by the Rx VGA. This block only uses the X upper MSBs of this value. Writing to this register will override the rcomp code to the Rx VGA. An LRC Ready pulse must be generated to the Rx VGA target for this value to take effect. [7:n] - compensation code sent to Iref [n-1:0] - remaining LSBs from scaling and offset calculation
23:16	80h RW	rxtermrcode_7_0: Rx Termination Rcomp Codes These bits are the final binary code used by the Rx termination. This block only uses the 7 upper MSBs of this value. Writing to this register will override the rcomp code to Rxterm. An LRC Ready pulse must be generated to the Rxterm target for this value to take effect. [7:1] - compensation code sent to Rxterm [0] - remaining LSB from scaling and offset calculation
15:8	80h RW	txrcode_7_0: Tx Rcomp Codes These bits are the final binary code used by the Tx. This block only uses the 7 upper MSBs of this value. Writing to this register will override the rcomp code to the Tx. An LRC Ready pulse must be generated to the Tx target for this value to take effect. [7:1] - compensation code sent to Tx [0] - remaining LSB from scaling and offset calculation
7:0	80h RW	irefrccode_7_0: Iref Rcomp Codes These bits are the final binary code used by the Iref block. This block only uses the 6 upper MSBs of this value. Writing to this register will override the rcomp code to the Iref block. An LRC Ready pulse must be generated to the Iref target for this value to take effect. [7:2] - compensation code sent to Iref [1:0] - remaining LSBs from scaling and offset calculation

23.7.22 PCS_DWORD21 (pcs_dword21)—Offset 54h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs dword21: [Port: 0xA6] + (200h + 54h)

Op Codes:

0h - Read, 1h - Write

Default: 80808080h

	31	28	24	20	16	12	8	4	0							
	1	0	0	0	0	0	0	0	0	0						
	rxvgarscale_7_0				rxtermrscscale_7_0				txrcscale_7_0				irefrscale_7_0			

Bit Range	Default & Access	Description
31:24	80h RW	rxvgarcscale_7_0: Rx VGA Rcomp Scale Multiplier The LRC code is multiplied by this value before applying the offset to generate the final rxvgarccode. 0xFF: Scale=1.99219 0xC0: Scale=1.5 0x80: Scale=1.0 0x40: Scale=0.5 0x00: Scale=0
23:16	80h RW	rxtermrcscale_7_0: Rx Termination Rcomp Scale Multiplier The LRC code is multiplied by this value before applying the offset to generate the final rxtermrcode. 0xFF: Scale=1.99219 0xC0: Scale=1.5 0x80: Scale=1.0 0x40: Scale=0.5 0x00: Scale=0
15:8	80h RW	txrcscale_7_0: Tx Rcomp Scale Multiplier The LRC code is multiplied by this value before applying the offset to generate the final txrrcode. 0xFF: Scale=1.99219 0xC0: Scale=1.5 0x80: Scale=1.0 0x40: Scale=0.5 0x00: Scale=0
7:0	80h RW	irefrcscale_7_0: Iref Rcomp Scale Multiplier The LRC code is multiplied by this value before applying the offset to generate the final irefrccode. 0xFF: Scale=1.99219 0xC0: Scale=1.5 0x80: Scale=1.0 0x40: Scale=0.5 0x00: Scale=0



23.7.23 PCS_DWORD22 (pcs_dword22)—Offset 58h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword22: [Port: 0xA6] + (200h + 58h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
rxvgarcoffset_7_0				rxtermrcoffset_7_0				txrcoffset_7_0				irefrcoffset_7_0			

Bit Range	Default & Access	Description
31:24	0h RW	rxvgaroffset_7_0: Rx VGA Rcomp Offset Same description as IREF Rcomp Offset, but applies to RxVGA Rcomp.
23:16	0h RW	rxtermrcoffset_7_0: Rx Termination Rcomp Offset Same description as IREF Rcomp Offset, but applies to RxTerm Rcomp.
15:8	0h RW	txrcoffset_7_0: Tx Rcomp Offset Same description as IREF Rcomp Offset, but applies to Tx Rcomp.
7:0	0h RW	irefrcoffset_7_0: Iref Rcomp Offset This value is added to the scaled LRC code to determine the final calibration code used by the Iref block. 2's complement format. The full 8-bit offset is used with the scale multiplier to determine the final 8-bit value, but the Iref target only uses the upper MSBs of the final value. 0x00: Offset = 0 0x01: Offset = +1 0x7F: Offset = +127 0xFF: Offset = -1 0x80: Offset = -128 Note: The final rcomp code has rollover protection so the final rcomp code + offset will not exceed the min/max range.

23.7.24 PCS_DWORD23 (pcs_dword23)—Offset 5Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword23: [Port: 0xA6] + (200h + 5Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00180888h

31				28				24				20				16				12				8				4				0											
0				0				0				0				1				1				0				0				0				0				0			
iclkcqcf_spare_7_0								iclkcif_spare_7				iclkcif_spare_6_3				iclkcif_spare_2_0				reserved526				i_drvcfg_3_0				i_ploadcfg_3_0				ipbiasctrl_3_0											



Bit Range	Default & Access	Description
16	1h RW	cri_lanereset_clkgatectl: 1: The assertion of lane reset will have the effect of gating the susclk and de-asserting the internal laneclkreq. This mode is only valid when the data lane dynamic clock gating mode is set to a non-zero value (i.e. 01, 10, and 11). 0: The assertion of lane reset will have no effect on the gating of susclk and state of the internal laneclkreq signal.
15	1h RW	cri_lanereqforce: Controls whether the internal laneclkreq will be forced to 1 or 0 when cfg_data_dynclkgate_mode is set to 00 or 10. 1: force laneclkreq high 0: force laneclkreq low. This mode will likely be used when one of the lanes is disabled while other lanes in the family are enabled. In this case the internal laneclkreq of the disabled lane should be de-asserted (not influencing the clk gating decision)
14:10	10h RW	cri_susclkdisable_delay_4_0: This register will control the number of cycles to delay the susclk enable de-assertion, in addition to the de-assertion of the laneclkreq signal sent out of the data lane. The susclk enable must be continuously de-asserted for the duration of this delay in order for the de-asserted state to be captured by the clock gating controller. 5'b00000 - 0 Cycle Delay 5'b00001 - 1 Cycle Delay 5'b00010 - 2 Cycle Delay 5'b11110 - 30 Cycle Delay 5'b11111 - 31 Cycle Delay
9:8	0h RW	cri_data_dynclkgate_mode_1_0: Controls the dynamic clock gating behavior in the data lane. 00 - susclk gating and laneclkreq disabled (Forced to configured value). In this mode the susclk will not be gated under any circumstances and the laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 01 - susclk gating disabled, laneclkreq enabled . In this mode the susclk will not be gated under any circumstances. The laneclkreq sent out of the data lane will toggle based on whether the lane power state, susclk need and the previous lane's laneclkreq signal. 10 - susclk gating enabled, laneclkreq disabled (forced to configured value) - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 11 - susclk gating and laneclkreq enabled - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the data lane will toggle based on the lane power state, susclk need and the previous lane's laneclkreq signal.
7	0h RW	cri_eios_waittime_ovren: EIOS Wait Time Override Enable for Rx Turn OFF 0: hardware value for EIOS wait timer is selected. 1: selects cri_eios_waittime[6:0]
6:0	20h RW	cri_eios_waittime_6_0: EIOS Wait Time for Rx Turn OFF Represents override value timer in PCS that comes into play during EIOS based turn off Rx (Rx L0s) 0000000 - Timer is bypassed 0000001 - 1 PLL link clock period delay (2ns) 0000010 - 2 PLL link clock period delay (4ns) ... 0100000 - 32 PLL link clock periods delay (64ns) - default



Access Method

tx_dword1: [Port: 0xA6] + (280h + 4h)

Op Codes:

0h - Read, 1h - Write

Default: 20000000h

Bit Range	Default & Access	Description
31:30	0h RO	reserved510: reserved
29:24	20h RW	ofrcr2short3_5_0: number of slices in R2 for swing 3 (DE) MSB has no effect.
23:22	0h RO	reserved509: reserved
21:16	0h RO	reserved508: reserved
15:14	0h RO	reserved507: reserved
13:8	0h RO	reserved506: reserved



23.8.4 TX_DWORD3 (tx_dword3)—Offset Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword3: [Port: 0xA6] + (280h + Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0C782040h

31	28	24	20	16	12	8	4	0
0	0	0	0	1	1	0	0	0
0	0	0	0	0	1	1	1	0
0	0	0	0	0	0	0	0	0
opisorate8b_h	obeacondivratio	ouniqetrangenmethod_1_0	oscaledcompmethod_1_0	odeemswingngenmethod	odownscaleampmethod	omargin101_7_0	omargin100_7_0	omargin011_7_0

Bit Range	Default & Access	Description
31	0h RW	opisorate8b_h: if '0' the PISO is of 10 bits (the whole bus) if '1' the PISO is of 8 bits (The LSBs) It's relevant both in normal Tx and in loopback mode. Use: '1' in PCI-E gen 3 and CIO (if supported) '0' for all other interfaces
30	0h RW	obeacondivratio: Div ration of beacon signal from ick_suslow clock '0' - Beacon freq will be as sus clock freq '1' - Beacon freq will be 1/4 of sus clock freq (note LFPS spec is 10-50MHz)
29:28	0h RW	ouniqetrangenmethod_1_0: Used to define if we use uniq-transition-bit scaling or not. The purpose is to have gen dependant scaling / non-scaling When '00' - don't activate uniq-transition-bit When '01' - if fast-clock is not divided (gen2?) activate uniq-transition-bit otherwise (gen1?) don't. When '10' - if fast-clock is not divided or divided by 2 (gen2?) activate uniq-transition-bit otherwise (gen1?) don't. (will probably be down-scaling amount of slices) When '11' - activate uniq-transition-bit
27:26	3h RW	oscaledcompmethod_1_0: Used to define if we use scaling of the compansation values or not. The purpose is to have gen dependant scaling / non-scaling When '00' - don't used scaled comp When '01' - if fast-clock is not divided (gen2?) don't scale-comp otherwise (gen1?) use scaled-comp When '10' - if fast-clock is not divided or divided by 2 (gen2?) don't scale-comp otherwise (gen1?) use scaled-comp (will probably be down-scaling amount of slices) When '11' - if fast-clock is not divided (gen2?) use scaled-comp otherwise (gen1?) don't use scaled-comp (will probably be up-scaling amount of slices)
25	0h RW	odeemswingngenmethod: Used to select scaling of -3.5dB deemphasis either ow2tapgen1deemph3p5[7:0] or ow2tapgen2deemph3p5[7:0] When '0' - if fast-clock is not divided use gen2 otherwise use gen1 When '1' - if fast-clock is not divided or divided by 2 use gen2 otherwise use gen1
24	0h RW	odownscaleampmethod: when margin='001', this bit with dataratefit are used to select between margin000 (for gen2) and margin101 (for gen1) when '0' - if fast-clock is not divided use margin000 (gen2) otherwise use margin101 (gen1) when '1' - if fast-clock is not divided or divided by 2 use margin000 (gen2) otherwise use margin101 (gen1)
23:16	78h RW	omargin101_7_0: factor (X/128) of slices to use in main-R1 for full swing level. Used for ~1V p2p to be used in Gen1 mode (Gen1/Gen2 depends on dataratefit and downscaleamp register)
15:8	20h RW	omargin100_7_0: factor (X/128) of slices to use in main-R1 for full swing level. Used for ~1/4Vp2p



23.8.6 TX_DWORD5 (tx_dword5)—Offset 14h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword5: [Port: 0xA6] + (280h + 14h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
ocalcinit	reserved515				reserved514			



Bit Range	Default & Access	Description
30:24	1Fh RW	onswbypass_6_0: Determines # of slices activated in N-drv when in strong pulling to CM (after Rx-dtct/ gohighz / stongPD) same slices cannot be opened for P-drv and for N-drv. Determines # of slices for P-drv in All1/All0 DFTs when bybbycomp is not asserted. In these DFT modes pswpass can be set to the same value as nswbypass
23	0h RO	reserved519: reserved
22:16	20h RW	opswbypass_6_0: Determines # of slices activated in P-drv when in strong pulling to CM (after Rx-dtct/ gohighz / stongPD) Determines # of slices for P-drv in All1/All0 DFTs when bybbycomp is not asserted.
15	0h RO	reserved518: reserved
14:8	0h RO	reserved517: reserved
7	0h RW	ocalccont: initiate calculation of swing-control circuit. While this signal is '1' the calculation is being done consecutively
6:0	0h RO	reserved516: reserved

23.8.8 TX_DWORD7 (tx_dword7)—Offset 1Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword7: [Port: 0xA6] + (280h + 1Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0038383Fh

31				28				24				20				16				12				8				4				0															
0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	0	0	0	0	0	0	1	1	1	0	0	0	0	0	0	0	1	1	1	1	1												
reserved527				reserved526				reserved525				reserved524				reserved523				oslrctrl2_l_2_0				oslrctrl2_h_2_0				reserved522				oslrctrl_l_2_0				oslrctrl_h_2_0				reserved521				or2bypass_5_0			

Bit Range	Default & Access	Description
31:30	0h RO	reserved527: reserved
29:27	0h RO	reserved526: reserved
26:24	0h RO	reserved525: reserved
23	0h RO	reserved524: reserved
22	0h RO	reserved523: reserved



Access Method

tx dword8: [Port: 0xA6] + (280h + 20h)

0h - Read, 1h - Write

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	0	1	0
ontpdtime_7_0		ofrcdcoup_1_0		obybycomp		obybdfmode_4_0		
						odftpisodata1_7_0		
						odftpisodata0_1_0		
						reserved529		
						reserved528		

October 2018
Document Number: 538136, Rev. 4.3



Access Method

tx dword10: [Port: 0xA6] + (280h + 28h)

0h - Read, 1h - Write

31				28				24				20				16				12				8				4				0															
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0												
isparead_7_0								reserved532								reserved531				ircvdtctmpout				idftcapstsig				idftcrvdetectedtxp				idftcrvdetectedtxp				idftcrvdetectedfinished				intfinished				intpass_3_0			

Bit Range	Default & Access	Description
31:24	X RO	ispareread_7_0: spare reg read
23:16	0h RO	reserved532: reserved
15:10	0h RO	reserved531: reserved
9	0h RO	ircvdtctcmpout: Flash Comparator Output Value
8	X RO	idftcaptestsig: reserved
7	0h RO	idftrcvdetectedtxn: Receive Detect Result for Txn
6	0h RO	idftrcvdetectedtxp: Receive Detect Result for Txp
5	0h RO	idftrcvdetectfinished: Receive Detect Process status
4	X RO	intlfinished: indication of NTL finished
3:0	X RO	intlpass_3_0: the four outputs of NTL test



23.8.12 TX_DWORD11 (tx_dword11)—Offset 2Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword11: [Port: 0xA6] + (280h + 2Ch)

Op Codes:

0h - Read, 1h - Write


Default: 00001000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
oselsparetxclk_in_2_0	ofrcdotprocess_2_0	ofrcgohighzdis	ofrcgohighzen	ofrcstrongpddis	ofrcstrongpden	ofrcctxclkrootdis	ofrcctxclkrooten	reserved537
				ofrcpwrmodel1	ofrcpwrmodel0s	ofrcpwrmodel0	ofrcmkeepadnen	ofrcmkeepadpen
					ofrcmkeepadndis	ofrcmkeepadpdis	omakedeepfifo	ofrcclatencyoptm_2_0
							reserved536	ofrcrcvdtcten
							otxrcvdtctckrate_1_0	reserved535
								reserved534
								reserved533
								oneloopbacken

Bit Range	Default & Access	Description
31:29	0h RW	oselsparetxclk_in_2_0: Selects data to be used as alternative to fast clock. 000: DAC clock if in DAC mode - Default. 001: cri100m clock 010: i_obsontx_psg 011: i_obsontx_nsg 100: ick_txsymbolclk 101: icksusslow 110: ick_dac 111: spare
28:26	0h RW	ofrcdotprocess_2_0: forces the dotprocess information 0XX - information of dot process comes from i_dotprocess[1:0] input bus. 100: p1271 dot1 101: p1271 dot4 110: p1271 dot8 111: NA
25	0h RW	ofrcgohighzdis: forces disabling of high-z output
24	0h RW	ofrcgohighzen: forces enabling of high-z output
23	0h RW	ofrcstrongpddis: forces disabling of strong pull-down
22	0h RW	ofrcstrongpden: forces enabling of strong pull-down
21	0h RW	ofrcctxclkrootdis: forces disable of tx-clock output.
20	0h RW	ofrcctxclkrooten: forces tx-clock to operate and drive clock out.
19	0h RO	reserved537: reserved
18	0h RW	ofrcpwrmodel1: when aserted. Forces L1 state
17	0h RW	ofrcpwrmodel0s: when aserted. Forces L0s state
16	0h RW	ofrcpwrmodel0: when aserted. Forces L0 state
15	0h RW	ofrcmkeepadnen: Forces enabling of common-mode keeping of PadN



Bit Range	Default & Access	Description
14	0h RW	ofrcmkeeppadpen: Forces enabling of common-mode keeping of PadP
13	0h RW	ofrcmkeeppadndis: Forces disabling of common-mode keeping of PadN
12	1h RW	ofrcmkeeppadpdis: Forces disabling of common-mode keeping of PadP
11	0h RW	omakedeeperfifo: Make FIFO deeper by 1 symbol clock cycle. Still not implemented. Implementation costs 10 flops in symb clock domain. Implementation is required for 8bits PISO only which is in next phase of products.
10:8	0h RW	ofrc latencyoptim_2_0: Changes the latency from loadgenen assertion to the sampling of 10bits data into fast-clock domain. The latency is determined by Fuses (through i_latencyoptim[1:0]) + ... 0XX =) + 0 (Not changing the latency.) 100 =) - 4UI 101 =) - 2UI 110 =) + 2UI 111 =) + 4UI Important Note: When changing the latency too high or too low is will wrap-around what might cause data loss on beginning or end of transmitting. If you decide to plan with the latency consider changing 'omakedeeperfifo' too
7	0h RO	reserved536: reserved
6	0h RW	ofrcrcvdtcten: force initiation of Tx-detect-Rx procedure
5:4	0h RW	otxrcvdtctclkrate_1_0: determines the clock rate in the flash comparator. 00 - use sus-clock as is (25MHz in phase2) default 01 - use sus-clock by 4 10 - use sus-clock by 2 11 - reserved In phase1 the rate was 2'b10 susfreq125MHz
3	0h RO	reserved535: reserved
2	0h RO	reserved534: reserved
1	0h RO	reserved533: reserved
0	0h RW	oneloopbacken: Near-End LoopBack enable



23.8.13 TX_DWORD12 (tx_dword12)—Offset 30h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword12: [Port: 0xA6] + (280h + 30h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
otxclkbytsel_1_0	ofrcdataratefit_2_0	odistxfelbpin	otxclkampbypsn	otxclkampbypsp	reserved539	odfxanamuxen	odfxanamuxsel_1_0	obs_tx_gated_supply_1_0
					reserved538			
						oobsdigselectupn_3_0		
							oobsdigselectupp_3_0	
								oobsdigselectdownn_3_0
								oobsdigselectdownp_3_0

Bit Range	Default & Access	Description
31:30	0h RW	otxclkbytsel_1_0: Select if to bypass the divided normal clock with some other clock. 2'b00: Don't bypass. Regular clock. 2'b01: bypass the RX clock - dataratefit must be '11' 2'b10: Reserved 2'b11: bypass the sparetxclk clock - dataratefit must be '11'
29:27	0h RW	ofrcdataratefit_2_0: Forces TX data rate 3'b0XX - don't force a value. get it from the I/F pin 3'b100 - no divide (2UIs per clock cyc) 3'b101 - divide by 2 3'b110 - divide by 4 3'b111 - divide by 8 - used also for bypassing with other clocks
26	0h RW	odistxfelbpin: when asserted - disables the i_txfelben pin at the interface and force it 0. (needed in case the pin is asserted in KX or sata1 mode)
25	0h RW	otxclkampbypsn: 0': Normal operation '1': Enable of the passgate connected from the analog clock N to the control of the DC correction cell. The feedback OTA is disabled.
24	0h RW	otxclkampbypsp: 0': Normal operation '1': Enable of the passgate connected from the analog clock P to the control of the DC correction cell. The feedback OTA is disabled.
23	0h RO	reserved539: reserved
22	0h RW	odfxanamuxen: Enables analog signals probing mux out. When enabled the Vref of Tx-detect-Rx circuit is observed. Note that only one lane is allowed to have a the analog mux enabled to avoid collisions.
21:20	0h RW	odfxanamuxsel_1_0: selects analog signal to be sent to analog port in common lane. This bus has no affect at all currently because there is only one analog signal for observation which is observed by odfxanamuxen
19:18	0h RW	obs_tx_gated_supply_1_0: Monitor gated vcc supply to Tx upar
17:16	0h RO	reserved538: reserved
15:12	0h RW	oobsdigselectupn_3_0: selects data to be sent to observability port output 'o_obsup_nsg'. Same mapping as oobsdigselectdownn[3:0]
11:8	0h RW	oobsdigselectupp_3_0: selects data to be sent to observability port output 'o_obsup_psg'. Same mapping as oobsdigselectdownp[3:0]



Access Method

tx_dword13: [Port: 0xA6] + (280h + 34h)

0h - Read, 1h - Write

31																															28							24							20							16							12							8							4							0						
0																															0							0							0							0							0							0							0							0						
reserved543																															ir2short3_5_0							reserved542							ir2short0_5_0							reserved541							ir1main3_6_0							reserved540							ir1main0_6_0													

October 2018
Document Number: 538136, Rev. 4.3

23.8.15 TX DWORD14 (tx_dword14)—Offset 38h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword14: [Port: 0xA6] + (280h + 38h)

Op Codes:

0h - Read, 1h - Write

Default: 00400000h

[illegible]

Bit Range	Default & Access	Description
31:30	0h RW	ospare1_1_0: reserved
29	0h RW	osimmode: Counter threshold of receive-detect, NTL, strong-common-mode is shortened dramatically for fast simulation purposes. (does not impose risk to circuitly but electrical spec will not met)
28	0h RW	ontlmodepin2pin: 0 - NTL procedure will be done per pad while both pads are pulled to the same rail. 1 - NTL procedure will be done per pad while the pads are pulled to opposite rails.
27	0h RW	ofrcdatapathdis: DFT feature to optionally be used with other registers
26	0h RW	ofrcdatapathen: DFT feature to optionally be used with other registers
25	0h RW	ofrcdrvbypdis: DFT feature to optionally be used with other registers
24	0h RW	ofrcdrvbypen: DFT feature to optionally be used with other registers
23	0h RW	odfttxclkcaptesten: Enables the finger capacitor quality check in the DCC block in Tx-clock block. The test is for shorts between the capacitor terminals.
22	1h RW	otxdccbyps_1: Tx DCC Bypass Override Puts DCC (duty cycle correction) circuit in bypass mode 0 - clock's duty cycle is not fixed
21:19	0h RW	ofrcnmos32idv_2_0: change the value iabut_idvpmos32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
18:16	0h RW	ofrcpmos32idv_2_0: change the value iabut_idvpmos32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
15	0h RW	visa_en: VISA Enable for the Tx VISA logic
14:12	0h RW	ovisa1_clkssel_2_0: VISA Clock Select for Lane1. Selects the source synchronous clock to be used for data being sent on lane1.



Bit Range	Default & Access	Description
11:8	0h RW	ovisa1_lanesel_3_0 : VISA Lane Select for Lane1. Selects the byte of data to be sent out on lane1.
7	0h RW	ovisa_bypass : VISA Bypass. Allows for signals to be passed asynchronously through VISA block. Applies to both lane0 and lane1. 0 : Flop signals in local VISA block (default) 1 : Bypass flops in local VISA block
6:4	0h RW	ovisa0_clkssel_2_0 : VISA Clock Select for Lane0. Selects the source synchronous clock to be used for data being sent on lane0.
3:0	0h RW	ovisa0_lanesel_3_0 : VISA Lane Select for Lane0. Selects data byte to be driven out of VISA-0 byte. Can be either clocked or unclocked data

23.8.16 TX_DWORD15 (tx_dword15)—Offset 3Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword15: [Port: 0xA6] + (280h + 3Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved551	reserved550	reserved549	reserved548	reserved547	reserved546	reserved545	reserved544	

Bit Range	Default & Access	Description
31:30	0h RO	reserved551 : reserved
29:24	0h RO	reserved550 : The slices used in R2 for DE (PstC=X,C=Y,PreC=Y)
23:22	0h RO	reserved549 : reserved
21:16	0h RO	reserved548 : The slices used in R2 for FS (PstC=X,C=Y,PreC=X)
15	0h RO	reserved547 : reserved
14:8	0h RO	reserved546 : The slices used in R1 for DE (PstC=X,C=Y,PreC=Y)
7	0h RO	reserved545 : reserved
6:0	0h RO	reserved544 : The slices used in R1 for FS (PstC=X,C=Y,PreC=X)



23.9 PCI Express* Lane 1 Electrical Address Map

Table 246. Summary of PCI Express* Lane 1 Electrical Message Bus Registers—0xA6 (Global Offset 400h)

Offset	Register ID—Description	Default Value
0h	"PCS_DWORD0 (pcs_dword0)—Offset 0h" on page 3289	00010080h
4h	"PCS_DWORD1 (pcs_dword1)—Offset 4h" on page 3291	00600060h
8h	"PCS_DWORD2 (pcs_dword2)—Offset 8h" on page 3292	00000000h
Ch	"PCS_DWORD3 (pcs_dword3)—Offset Ch" on page 3294	5515ACAAh
10h	"PCS_DWORD4 (pcs_dword4)—Offset 10h" on page 3294	575555C1h
14h	"PCS_DWORD5 (pcs_dword5)—Offset 14h" on page 3295	00003E63h
18h	"PCS_DWORD6 (pcs_dword6)—Offset 18h" on page 3296	FFFFFFFFh
1Ch	"PCS_DWORD7 (pcs_dword7)—Offset 1Ch" on page 3297	00000009h
20h	"PCS_DWORD8 (pcs_dword8)—Offset 20h" on page 3298	000000C4h
24h	"PCS_DWORD9 (pcs_dword9)—Offset 24h" on page 3300	00000000h
28h	"PCS_DWORD10 (pcs_dword10)—Offset 28h" on page 3301	00000000h
2Ch	"PCS_DWORD11 (pcs_dword11)—Offset 2Ch" on page 3302	0F000000h
30h	"PCS_DWORD12 (pcs_dword12)—Offset 30h" on page 3304	00250F00h
34h	"PCS_DWORD13 (pcs_dword13)—Offset 34h" on page 3305	00000000h
38h	"PCS_DWORD14 (pcs_dword14)—Offset 38h" on page 3306	007A0018h
3Ch	"PCS_DWORD15 (pcs_dword15)—Offset 3Ch" on page 3307	04100300h
40h	"PCS_DWORD16 (pcs_dword16)—Offset 40h" on page 3309	01000001h
44h	"PCS_DWORD17 (pcs_dword17)—Offset 44h" on page 3310	01000001h
48h	"PCS_DWORD18 (pcs_dword18)—Offset 48h" on page 3312	00008080h
4Ch	"PCS_DWORD19 (pcs_dword19)—Offset 4Ch" on page 3313	00004F10h
50h	"PCS_DWORD20 (pcs_dword20)—Offset 50h" on page 3314	80808080h
54h	"PCS_DWORD21 (pcs_dword21)—Offset 54h" on page 3315	80808080h
58h	"PCS_DWORD22 (pcs_dword22)—Offset 58h" on page 3316	00000000h
5Ch	"PCS_DWORD23 (pcs_dword23)—Offset 5Ch" on page 3316	00180888h
60h	"PCS_DWORD24 (pcs_dword24)—Offset 60h" on page 3317	0001C020h

23.9.1 PCS_DWORD0 (pcs_dword0)—Offset 0h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword0: [Port: 0xA6] + (400h + 0h)

Op Codes:

0h - Read, 1h - Write

Default: 00010080h



Bit Range	Default & Access	Description
21	1h RW	cri_rxdigfiltlsq_enable: When 1 enables unsquelch based Rx power up in P0 or P0s
20	0h RW	reg_txfsfm_delay_ovrd: Override enable bit for reg_txfsfm_4us_delay
19:16	0h RW	reg_txfsfm_4us_delay_11_8: Override counter value for 4 us delay in txfsfm lane reset to txbiasen delay
15:14	0h RW	reg_pclk_rate_1_0: Override for pclk_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
13:12	0h RW	reg_rate_1_0: Override for i_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
11:9	0h RW	reg_phymode_2_0: Override for PHY Mode Selection 000 = PCIE 001 = USB3 010 = GbE 011 = SATA/SAPIS 100 = Display 101 = DMI 110 = CIO 111 =Reserved
8	0h RW	reg_modeovren: When asserted selects register override bits for phymode, datawidth etc
7:6	1h RW	reg_datawidth: Override for Tx data interface width. 00 - Unused 01 - x8/x10 width (default) 10 - x16/x20 width 11 - x32/x40 width
5	1h RW	soft_reset_n: Active low soft reset override
4	0h RW	reg_diginelben: Override for near end digital loopback.
3	0h RW	reg_digifelben: Override for far end digital loopback
2	0h RW	reg_strapgroup_ovrden: Override Enable for Strap Group
1	0h RW	reg_yank_timer_done_b_ovrd: Override for yank_timer_done_b
0	0h RW	reg_yank_timer_done_b_ovrd_en: Override Enable for yank_timer_done_b

23.9.3 PCS_DWORD2 (pcs_dword2)—Offset 8h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword2: [Port: 0xA6] + (400h + 8h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_pibiasoff_delay_3_0	cri_sqdbexittimer_override_3_0	cri_sqdbentrytimer_override_5_0	reg_rxdrcgtsqsel_1_0	cri_reut_SlaveSideDataCheckingEn	cri_sqdbtimer_ovren	cri_rxpwrfsm_timer_ovren	reg_rxidle	cri_rxrawdata_sel
				cri_dynkalign_eco3302703_mode	cri_dynkalign_eco3302703_ovren	reg_rxpwrfsm_pibiasoff_ovrride	cri_reset_kalignlck	cri_ebptrrst
							cri_comdispfix	cri_forcebankhit
							cri_kalignmode_1_0	cri_skpprocdis
								cri_elasticbuffer_maskdis

Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_pibiasoff_delay_3_0: Override value for delay (in 2ns increments) between deassertion of opianclkbufen and opibiasen
27:24	0h RW	cri_sqdbexittimer_override_3_0: Rx squelch exit debounce timer
23:18	0h RW	cri_sqdbentrytimer_override_5_0: Rx squelch entry debounce timer
17:16	0h RW	reg_rxdrcgtsqsel_1_0: Squelch output select
15	0h RW	cri_reut_SlaveSideDataCheckingEn: Enable REUT slave side checking while in loopback slave
14	0h RW	cri_sqdbtimer_ovren: Squelch debounce timer override enable
13	0h RW	cri_rxpwrfsm_timer_ovren: Rx power management fsm timer override enable
12	0h RW	reg_rxidle: Chicken bit to override i_rxidle from controller and keep Rx in P0 or P0s
11	0h RW	cri_rxrawdata_sel: When asserted bypass K-align, 10b/8b decoder and Elastic buffer
10	0h RW	cri_dynkalign_eco3302703_mode: Kalign Mode Override Value When cri_dynkalign_eco3302703_ovren is set, this value selects kalignmode 0 - use register bits cri_kalignmode[1:0] to select kalignmode 1 - select the 4 COM kalign mode'
9	0h RW	cri_dynkalign_eco3302703_ovren: Kalign Mode Override Enable Overrides kalign mode select pin, allowing config bit kalignmode_override_val to select kalignmode.
8	0h RW	reg_rxpwrfsm_pibiasoff_ovrride: When asserted selects reg_rxpwrfsm_pibiasoff_delay[3:0]
7	0h RW	cri_reset_kalignlck: When asserted resets Kalign lock indication and Kalign is performed again. The conditions when this would assert includes and is not restricted to any power management states (L0s, L1) or polling quiet states etc.
6	0h RW	cri_ebptrrst: Global broadcast to all lanes that the Elastic Buffer pointers should be reset. This is a pulse and will be generated when we need to reset the pointers because of collision or various other reasons.
5	0h RW	cri_comdispfix: Chicken bit to force disparity in dynamic K-align mode



Bit Range	Default & Access	Description
4	0h RW	cri_forcebankhit: Chicken bit to enable data appear on NOA post k-align lock although k-align block is not achieving lock. This is only for NOA observeability and not for other purpose
3:2	0h RW	cri_kalignmode_1_0: KALIGN Mode Select 00 = dynamic kalign all the time. Accounts for bit slips on incoming stream which can cause symbol to be detected on different bank 10 = dynamic kalign up to L0 x1 = static kalign (same as GDG). Assumes symbol always detected on same data bank
1	0h RW	cri_skpprocdis: SKIP Ordered-Set Processing Disable When this configuration bit is asserted, then SKIP ordered=sets will be ignored (in EB block). Used in Elastic buffer block. 0 = Normal operation. SKIP ordered=sets will be processed by the Elastic Buffer 1 = SKIP processing disabled.
0	0h RW	cri_elasticbuffer_maskdis: Config bit (chicken bit) to disable the masking logic after elec idle ordered set is seen

23.9.4 PCS_DWORD3 (pcs_dword3)—Offset Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword3: [Port: 0xA6] + (400h + Ch)

Op Codes:

0h - Read, 1h - Write


Default: 5515ACAAh

31	28	24	20	16	12	8	4	0
0	1	0	1	0	1	0	1	0
0	1	0	1	0	1	0	1	0
cri_dfx_patbuf_55_48	cri_dfx_patbuf_63_56	cri_dfx_patbuf_71_64	cri_dfx_patbuf_79_72					

Bit Range	Default & Access	Description
31:24	55h RW	cri_dfx_patbuf_55_48: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
23:16	15h RW	cri_dfx_patbuf_63_56: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
15:8	ACh RW	cri_dfx_patbuf_71_64: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
7:0	AAh RW	cri_dfx_patbuf_79_72: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.

23.9.5 PCS_DWORD4 (pcs_dword4)—Offset 10h

Access Method



Bit Range	Default & Access	Description
31	0h RW	cri_dfx_patbuftrain: Pattern Buffer Manual Training When DFXPATBUFTRAINOVR and DFXLCCESTART are asserted, this manually controls whether the Pattern Buffers are in training or have completed training. 0 : Send training patterns (default) 1 : Send contents of DFXPATBUF
30:28	0h RW	cri_dfx_prbspoly_2_0: PRBS Polynomial Select the polynomial to be used by the PRBS in the Pattern Generator and Pattern Checker. PRBS support 10b or 8b, which is indicated by the msb. 000 - $x^{16} + x^5 + x^4 + x^3 + 1$ (USB3/PCIe Scrambler) (8b) 001 - $x^{16} + x^{15} + x^{13} + x^4 + 1$ (SATA scrambler) (8b) 010 - $x^{31} + x^{28} + 1$ (8b) 011 - $x^7 + x^6 + 1$ (8b) 100 - $x^{15} + x^{14} + 1$ (10b) 101 - $x^{23} + x^{18} + 1$ (10b) 110 - $x^{31} + x^{28} + 1$ (10b) 111 - $x^7 + x^6 + 1$ (10b)
27:26	0h RW	cri_dfx_patbufsize_1_0: Pattern Buffer Size Select the size of the Pattern Buffer to use. The MSB will always be bit 79. The LSB will depend on this select and the DFXLCCESTART (10b or 8b mode). 00 : full 80b buffer (Default) 01 : 70b (while in 10b mode), 56b (while in 8b mode) 10 : 40b (while in 10b mode), 32b (while in 8b mode) 11 : 10b (while in 10b mode), 8b (while in 8b mode)
25	0h RW	cri_dfx_patbufloop: Pattern Buffer Looping Enable Enables looping of the Pattern Buffer. By default, the contents of Pattern Buffer will be used once and stop. Alternatively, the Pattern Buffer will continue to loop until the DFXLCCESTART is de-asserted. 0 : Run Pattern Buffer only once (default) 1 : Loop Pattern Buffer until stopped
24	0h RW	cri_dfx_patbufdwidth: Pattern Buffer Data Width Selects between 10 bit or 8 bit data width for the Pattern Buffer. Determines where in the Tx/Rx path the data is inserted/retrieved. 0 : 10b (default) 1 : 8b
23	0h RW	cri_dfx_patbuftrainovr: Pattern Buffer Training Override Enables manual training of the Pattern Buffer instead of the automated coordination between the Pattern Checker and Pattern Generator. When asserted, the DFXPATBUFTRAIN bit will be used to force when training is active and when it is complete. 0 : Automatic Training (default) 1 : Enable Manual Training
22	0h RW	cri_dfx_marginmode: Margin mode Overrides standard setup configurations for use with Eye Width Margining. 0 : Standard Mode (default) 1 : Margin Mode enabled
21	0h RW	cri_dfx_chk_sel: Pattern Checker 8b10b Select This determines where Rx data is compared, either in the 10-bit domain before decode or after 10b-8b decoding. 0: 10b domain 1: 8b domain
20	0h RW	cri_dfx_patchken: Pattern Checker Enable 0 : Disable Pattern Checker (default) 1 : Enable Pattern Checker
19	0h RW	cri_dfx_patgenen: Pattern Generator Enable This will activate the Dfx bypass muxes in the PCS Tx path. 0 : Disable Pattern Generator (default) 1 : Enable Pattern Generator
18	0h RW	cri_dfx_clrerrcnt: Clear Error Counter Resets the Pattern Checker's error counter. 0 : Error Counter allowed to run (default) 1 : Error Counter held in reset
17	0h RW	cri_dfx_lcereset: Local Compare Engine Reset Resets all components of the Local Compare Engine in both the Pattern Generator and the Pattern Checker. 0 : LCE not in reset (default) 1 : LCE in reset
16	0h RW	cri_dfx_lcestart: Local Compare Engine Start Controls the starting and stopping of the LCE. Allows for simultaneous or independent start across lanes. Once stopped, a DFXLCERESET is usually required. 0 : LCE stopped (default) 1 : LCE running
15:8	3Eh RW	cri_dfx_patbuf_7_0: Pattern Buffer Storage In 10b mode, the buffer is read as eight 10b chunks. The first 10 bits should not equal the Comma Symbol: '0011111010' (or its inversion '1100000101'). In 8b mode, the buffer is read as eight 10b chunks, where the 10th bit is unused and the 9th bit is the K-bit indicator. The first 10 bits should not equal the Comma Symbol: 'xx10111100'. DFXPATBUF[78] should not be '1'.
7:0	63h RW	cri_dfx_patbuf_15_8: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.

23.9.7 PCS_DWORD6 (pcs_dword6)—Offset 18h

Access Method



Type: Message Bus Register
(Size: 32 bits)

pcs_dword6: [Port: 0xA6] + (400h + 18h)

Op Codes:

0h - Read, 1h - Write

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
cri_dfx_prbseed_7_0								cri_dfx_prbseed_31_24

Bit Range	Default & Access	Description
31:24	FFh RW	cri_dfx_prbseed_7_0: PRBS Seed Can be used for HVM determinism. The use of all zeroes can result in lockup.
23:16	FFh RW	cri_dfx_prbseed_15_8: PRBS Seed See cri_dfx_prbseed[7:0] description.
15:8	FFh RW	cri_dfx_prbseed_23_16: PRBS Seed See cri_dfx_prbseed[7:0] description.
7:0	FFh RW	cri_dfx_prbseed_31_24: PRBS Seed See cri_dfx_prbseed[7:0] description.

23.9.8 PCS_DWORD7 (pcs_dword7)—Offset 1Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)


pcs_dword7: [Port: 0xA6] + (400h + 1Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000009h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
dfx_cri_errcnt_7_0								cri_dfx_prbstraincnt_3_0



Bit Range	Default & Access	Description
31:24	X RO	dfx_cri_errcnt_7_0: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
23:16	X RO	dfx_cri_errcnt_15_8: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
15	X RO	i_rxcaldone: RX Calibration Cycles Complete Indicator
14	X RO	dfx_cri_lcemgnerr: Local Compare Engine Margin Error Indicates that the error counter has reached its max value. This can be used by the Rx upartition during Margin Mode to determine when the eye width has closed.
13	X RO	cri_dfx_patgen2active: Pattern Generator 2 Active status indicator In a lane with two Tx paths, this indicates that the second Pattern Generator is in progress. The DFXPATGENACTIVE will only indicate that the first Pattern Generator is in progress.
12	X RO	dfx_cri_patbufallfail: Pattern Buffer All Fail status indicator Indicates that there has not been a single matching Pattern Buffer pattern. This could signify that an error occurred during training.
11	X RO	dfx_cri_patchkactive: Pattern Checker Active status indicator Indicates that the Pattern Checker is in progress (either Pattern Buffer or PRBS).
10	X RO	dfx_cri_patgenactive: Pattern Generator Active status indicator Indicates that the Pattern Generator is in progress (either Pattern Buffer or PRBS).
9	X RO	dfx_cri_lctraindone: Local Compare Engine Training Done status indicator Indicates that the Pattern Checker training is completed (either Pattern Buffer or PRBS). The Pattern Checker is now synchronized to the Pattern Generator.
8	X RO	dfx_cri_lctrainactive: Local Compare Engine Training Active status indicator Indicates that the Pattern Checker training is in progress (either Pattern Buffer or PRBS).
7	0h RW	reserved501: reserved
6	0h RW	cri_dfx_patgen2en: Pattern Generator 2 Enable In a lane with two Tx paths, this enables the second Pattern Generator. The DFXPATGENEN will enable the first Pattern Generator. 0 : Disable second Pattern Generator (default) 1 : Enable second Pattern Generator
5:4	0h RW	cri_dfx_maxerrcnt_1_0: Maximum Error Count Selectable maximum value that the DFXERRCNT can reach before the Local Compare Engine is automatically stopped. 00 : 2^{16} (default) 01 : 2^{10} 10 : 2^8 11 : 2^4
3:0	9h RW	cri_dfx_prbstraincnt_3_0: PRBS Training Count The number of consecutive cycles that the Pattern Checker's PRBS must be error free before it is considered synchronized. Default is 9.

23.9.9 PCS_DWORD8 (pcs_dword8)—Offset 20h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword8: [Port: 0xA6] + (400h + 20h)

Op Codes:

0h - Read, 1h - Write

Default: 000000C4h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reg_partial	reg_slumber	reg_tx2_cdr_override_2_0	reg_cdr_override_2_0	reg_ebuffmode	reg_usedclockchannel_1_0	reg_usedclockchannel_ovrride	reg_gbl_ovrride	reg_tx1_pclkon_inp2
								reg_tx2_pclkon_inp2
								reg_tx2_txenable
								cri_rxeb_ptr_init_3_0
								reg_powerfsm_ovrride
								reg_suspend
								reg_pclkcfginput
								reg_useqclock
								cri_rxeb_hiwater_3_0
								cri_rxeb_lowater_3_0

Bit Range	Default & Access	Description
31	0h RW	reg_partial: Override for i_partial
30	0h RW	reg_slumber: Override for i_slumber
29:27	0h RW	reg_tx2_cdr_override_2_0: Override for cdr_override strap for second tx2
26:24	0h RW	reg_cdr_override_2_0: Override for cdr_override strap
23	0h RW	reg_ebuffmode: Override for ebuffmode (no functionality in p1271 phase1 design)
22:21	0h RW	reg_usedclockchannel_1_0: Selects the active clock channel
20	0h RW	reg_usedclockchannel_ovrride: When asserted selects reg_usedclockchannel[1:0]
19	0h RW	reg_gbl_ovrride: Global override select
18	0h RW	reg_tx1_pclkon_inp2: When asserted keeps PCLK running in P2 mode. For DP this is used for Lane1
17	0h RW	reg_tx2_pclkon_inp2: When asserted keeps PCLK running in P2 mode. This is reserved (no impact) for PCIe/DMI and used for DP Lane2
16	0h RW	reg_tx2_txenable: Override for i_txenable for tx2
15:12	0h RW	cri_rxeb_ptr_init_3_0: Config override for initial value of Rx elastic buffer read pointer
11	0h RW	reg_powerfsm_ovrride: When asserted overrides for Tx power fsm are selected
10	0h RW	reg_suspend: Override for suspend
9	0h RW	reg_pclkcfginput: Override for pclkcfginput strap
8	0h RW	reg_useqclock: Override for useqclock; MUX select for I or Q clk for TX clocking
7:4	Ch RW	cri_rxeb_hiwater_3_0: Elastic buffer high watermark based on which SKP is removed

23.9.10 PCS_DWORD9 (pcs_dword9)—Offset 24h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs dword9: [Port: 0xA6] + (400h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31	0h RW	reserved502: reserved
30:26	0h RW	reg_strapgroup_4_0: Override for i_strapgroup
25:24	0h RW	reg_powerdown_1_0: Override for i_powerdown
23	0h RW	reg_pcs_txcmnkeepdisable_ovrd: Override for ipcs_txcmnkeepdisable input 0: Use value on ipcs_txcmnkeepdisable input pin to determine o_txgohighz state in P2/ slumber 1: Force pcs_txcmnkeepdisable to 0
22:18	0h RW	reg_straplane_5_0: Override for i_straplane
17	0h RW	reg_tx1_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx1 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
16	0h RW	reg_tx2_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx2 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
15	0h RW	reg_txdatavalid: Override for i_txdatavalid (register is NOT used)
14:13	0h RW	reg_txdeemp_1_0: Override for i_txdeemp



Bit Range	Default & Access	Description
12:10	0h RW	reg_txmargin_2_0: Override for i_txmargin
9	0h RW	reg_txswing: Override for i_txswing
8	0h RW	reg_txenable: Override for i_txenable
7:6	0h RW	reg_txterm_vcc_1_0: Override for txterm_vcc strap
5	0h RW	reg_txdetrxlpbk: Override for i_txdetrxlpbk
4	0h RW	reg_txelectidle: Override for i_txelectidle
3	0h RW	reg_txcompliance: Override for i_txcompliance
2	0h RW	reg_txoneszeroes: Override for i_txoneszeroes
1:0	0h RW	reg_latencyoptim_1_0: Override for i_latencyoptim

23.9.11 PCS_DWORD10 (pcs_dword10)—Offset 28h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword10: [Port: 0xA6] + (400h + 28h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_timer_WAIT_RX_PT_CLK_3_0	reg_rxpwrfsm_timer_ENABLE_RX_3_0	reg_rxpwrfsm_timer_RX_SEQEN_3_0	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0		reg_clk_valid_cnt_7_0	reg_rxterm	reg_rxpolarity	reg_rxeqtrain
						reg_rxsquelchen	cri_rxpwrfsm_sgentimer_ovrden	reg_rxintfren_override
							reg_rxintfren_l	reg_clk_valid_cnt_ovrd



Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PI_CLK_3_0: Rx Power state m/c timer value used to enable PI clock
27:24	0h RW	reg_rxpwrfsm_timer_ENABLE_RX_3_0: Rx Power state m/c timer value used to enable receivers
23:20	0h RW	reg_rxpwrfsm_timer_RX_SQEN_3_0: Rx Power FSM Rx Squelch Enable Timer Override Value Affect squelch enable startup sequence during 'synchronous' squelch startup mode. 0000 - Invalid 0001 - 1 susclk period ... 1111 - 15 susclk period
19:16	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0: Rx Power state m/c timer value used to enable PI BIAS
15:8	0h RW	reg_clk_valid_cnt_7_0: Over ride value for clock valid delay in clock top block before toggling phystatus.
7	0h RW	reg_rxterm: Override for i_rxterm
6	0h RW	reg_rxpolarity: Override for i_rxpolarity
5	0h RW	reg_rxeqtrain: Override for i_rxeqtrain
4	0h RW	reg_rxsquelchen: Override for i_rxsquelchen
3	0h RW	cri_rxpwrfsm_sqentimer_ovrden: Squelch Enable Timer Override Enable Used to override the squelch enable timer in PCS with the timer value set by the Rx Squelch Enable timer register (reg_rxpwrfsm_timer_RX_SQEN[3:0]).
2	0h RW	reg_rxintfltren_override: Rx Integral Filter Override Select 0: selects i_rxintfltren_l input pin. 1: selects reg_rxintfltren_l register
1	0h RW	reg_rxintfltren_l: Override for Rx integral filter enable i_rxintfltren_l
0	0h RW	reg_clk_valid_cnt_ovrd: Override enable for reg_clk_valid_cnt

23.9.12 PCS_DWORD11 (pcs_dword11)—Offset 2Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword11: [Port: 0xA6] + (400h + 2Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0F000000h



31	28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																						
0	0	0	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																					
reserved505				reg_tx2_stagger_mask_4_0				i_clkbuf_iclken_ovrd				i_clkbuf_qclken_ovrd				reserved503				i_clkbuf_txclkmuxen_ovrd				reserved504				reg_tx2_cmmdisparity				reg_tx1_ctrl_override				reg_tx2_ctrl_override				reg_tx2_txterm_vcc_1				reg_tx2_txterm_vcc_0				reg_tx2_txdetrxlpbk				reg_tx2_txelectidle				reg_tx2_txcompliance				reg_tx2_txoneszeroes				reg_tx2_powerdown_1_0				o_captesten_h				i_captestout				fuse_override				i_clkbuf_ibiasen_ovrd				reg_lanedeskew_strap_ovrd				reg_lane_reverse				reg_left_txifo_rst_master				reg_right_txifo_rst_master																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
reserved506																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																</			

Bit Range	Default & Access	Description
31:30	0h RW	reserved505: reserved
29	0h RW	reserved506: reserved
28:24	Fh RW	reg_tx2_stagger_mask_4_0: Mask bit for lane number. Used to group lanes for staggering. for tx2
23	0h RW	i_clkbuf_iclken_ovrd: I-Clock Override for the DataLane
22	0h RW	i_clkbuf_qclken_ovrd: Q-Clock Override for the DataLane
21	0h RW	reserved503: reserved
20	0h RW	i_clkbuf_txclkmuxen_ovrd: TX Clock Selection Mux Override
19	0h RW	reserved504: reserved
18	0h RW	reg_tx2_cmmdisparity: Sets the initial disparity during Compliance Measurement Mode, used together with pcs_txcompliance pulse. For TX2 0 = set negative disparity 1 = set positive disparity
17	0h RW	reg_tx1_ctrl_override: overrides input parameter/controls for tx1
16	0h RW	reg_tx2_ctrl_override: overrides input parameter/controls for tx2
15	0h RW	reg_tx2_txterm_vcc_1: Override for txterm_vcc strap[1] for tx2 in DP family. Override enable for inspecmm for non-DP families (reg_inspecmm_ovrd_enable).
14	0h RW	reg_tx2_txterm_vcc_0: Override for txterm_vcc strap[0] for tx2 in DP family. Override value for inspecmm for non-DP families (reg_inspecmm_ovrd_value).
13	0h RW	reg_tx2_txdetrxlpbk: Override for i_txdetrxlpbk for tx2



Access Method

pcs dword12: [Port: 0xA6] + (400h + 30h)

Op Codes:

0h - Read, 1h - Write

Default: 00250F00h

Intel Atom® Processor E3800 Product Family
Datasheet
3304



Access Method

pcs_dword14: [Port: 0xA6] + (400h + 38h)

Op Codes:

Default: 007A0018h

Bit Range	Default & Access	Description
31	0h RW	reg_clkbuf_stagger_ovrd: Override enable for reg_clkbuf_stagger_cnt
30	0h RW	reg_clkbuf_stagger_cnt_10: Counter override value for staggering delay of clock buffer control signals.



Bit Range	Default & Access	Description
29	0h RW	reg_slowclk_ovrden: Slow Clock Override Enable When set 1'b1, reg_slowclocken and reg_sclk250en are valid. When cleared 1'b0, output of FSM will drive slow clock enable.
28:24	0h RW	reg_txloadgenen2txen_fall_delay_4_0: reserved
23:20	7h RW	o_cmlmuxsthsel_3_0: CML Mux strength control
19:16	Ah RW	o_cmlsthsel_3_0: RX CML driver strength
15:12	0h RW	o_pcisel_3_0: I clk phase correction control
11:8	0h RW	o_pcqsel_3_0: Q clk phase correction control
7	0h RW	o_phaseicen: Iclk phase correction enable.
6	0h RW	o_phaseqcen: Qclk phase correction enabled.
5	0h RW	o_pcbypass: Phase correction bypass.
4	1h RW	o_slowclocken: Slow clock 1 enable Only valid if slow clock override enable is set 1'b1
3	1h RW	o_sclk250en: Slow clock 2 enable Only valid if slow clock override enable is set 1'b1
2:0	0h RW	cri_kalign_com_cnt: Upper 3 bits of a 7-bit counter that counts number of COM characters found. Used for special SAPIS mode where spread spectrum clocking can be utilized. Note: This register is used in conjunction with another PCS register cri_kalignmode[1:0] = 10 Register value Minimum COM count to achieve symbol lock 000 - 18 001 - 34 010 - 50 011 - 66 100 - 82 101 - 98 110 - 114 111 - 130

23.9.16 PCS_DWORD15 (pcs_dword15)—Offset 3Ch

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword15: [Port: 0xA6] + (400h + 3Ch)

Op Codes:

0h - Read, 1h - Write

Default: 04100300h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
13:8	3h RW	reserved513: reserved
7:0	0h RW	reg_clkbuf_stagger_cnt_9_2: Counter override value for staggering delay of clock buffer control signals.

23.9.17 PCS_DWORD16 (pcs_dword16)—Offset 40h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword16: [Port: 0xA6] + (400h + 40h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h

[illegible]

Bit Range	Default & Access	Description
31	0h RW	squelch_shunt_ovrd_en: Squelch Shunt Pulse Duration Override Enable Overrides the hardware default shunt pulse duration value 1: Shunt Pulse Duration Override Enable 0: Shunt Pulse Duration Override Disable
30:28	0h RW	squelch_shunt_cnt_2_0: Squelch Shunt Pulse Duration Override Value 000 = No shunt pulse generated 001 = 1 susclk cycles ... 111 = 7 susclk cycles
27	0h RW	reserved520: reserved
26	0h RW	i_rxsqfsm_timersel: Squelch FSM Timer Select 0 - Selects 25Mhz values for squelch timer and shunt pulse generation . 1 - Selects 100Mhz values for squelch timer and shunt pulse generation. This register is applicable to synchronous squelch startup mode.
25	0h RW	i_rxsq_asyncmode_h: Squelch Async Startup Mode This squelch startup mode is power state independent. When enabled, the squelchen signal sent to Modphy will asynchronously enable the squelch detector circuit. Once enabled, the squelch detector circuit will asynchronously send an unfiltered/unqualified squelch indication signal out of Modphy. The squelch indication signal will initially be unstable, so it is up to the consumer of this signal to filter/qualify it accordingly. The asynchronous squelch startup mode is beneficial because it significantly reduces the squelch startup latency. This decrease in latency does come at the cost of slightly higher power when squelch is not enabled as the IREF and Squelch Keeper circuits must remain enabled. When disabled, the squelch startup sequence is synchronous in nature and the squelch indication signal sent out of Modphy is stable/filtered.
24	1h RW	i_rxsquelchstby_h: Fast Squelch Enable Mode Bit to keep the IREF (ivrefen) on during P2 and reduce squelch startup time.



Bit Range	Default & Access	Description
23:18	0h RW	reserved519: reserved
17:16	0h RW	cri_dfx_evenoddmask_1_0: Pattern Checker Even/Odd Bit Error Mask Select 00 : no masking; all errors will be counted 01: select odd path, mask even path; only errors on bits [1,3,5,7,9] are counted 10: select even path, mask odd path; only errors on bits [0,2,4,6,8] are counted 11: reserved;
15:12	0h RW	reserved518: reserved
11:10	0h RW	cri_dfx_lce2patsrc_1_0: Local Compare Engine 2 Pattern Source In a lane with two Tx paths, this selects between using Pattern Buffer or PRBS as source of LCE patterns for the second LCE. The DFXLCEPATSRC selects for the first LCE. 0 : Pattern Buffer (default) 1 : PRBS
9:8	0h RW	cri_dfx_lcepatsrc_1_0: Local Compare Engine Pattern Source. Selects between using Pattern Buffer or PRBS as source of LCE patterns. 00 : Pattern Buffer; use LCE default training pattern; 01: Pattern Buffer; use the first 40b of pattern buffer for training. 10: PRBS; use LCE default training pattern; 11: PRBS; use the first 40b of pattern buffer for training.
7:6	0h RW	reserved517: reserved
5:4	0h RW	txloadgen_ctr_val: TxLoadGen Pulse Width Control Controls the pulse width of txloadgenen from PCS to Tx upar. This is used in MAC initiated digital far end loopback mode in PCIE family. 00 - txloadgenen pulse width is 4 symbol clocks (default) 01- txloadgenen pulse width is 2 symbol clocks 10 - txloadgenen pulse not generated 11 - txloadgenen pulse width is 6 symbol clocks
3	0h RW	cri_txhighpowerei_ovrden: TxHighPowerEI Override Mode Enable 0 - TxHighPowerEI to TxuPAR driven by Logic 1 - TxHighPowerEI to TxuPAR driven by override register value(s).
2	0h RW	cri_tx1highpowerei_ovrdval: Tx1HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx1HighPowerEI disabled 1 - Tx1HighPowerEI enabled
1	0h RW	cri_tx2highpowerei_ovrdval: Tx2HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx2HighPowerEI disabled 1 - Tx2HighPowerEI enabled
0	1h RW	p2_fast_exit_en: P2 Fast Exit Mode Enable Common Mode sustainer will be enabled during P2 when this bit is asserted. 1: P2 Fast Exit Mode Enable 0: P2 Fast Exit Mode Disable

23.9.18 PCS_DWORD17 (pcs_dword17)—Offset 44h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword17: [Port: 0xA6] + (400h + 44h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h



31				28				24				20				16				12				8				4				0																																																																			
0				0				0				0				0				0				0				0				0				0																																																															
oiredfxsel_1_0				iopampsfpn_h				iopampsfnen_h				iopampnen_h				iopampnen_h				monanapgn				monubufbypassen				reserved522				reg_ivrefen				ivrefen_ovrd				reserved523				oirefcurmonsel				lrcdisable				reserved521				lrc_rdy_pulsegen				lrc_rdy_target_1_0				lrc_rdy_ovd				rxtermprmcen				rxvgaprmcen				txpmrcen				irefpmrcen				rxtermprccen				rxvgaperrcen				txpmrcen				irefpmrcen			

Bit Range	Default & Access	Description
31:30	0h RW	oiredfxsel_1_0: IREF Voltage Monitor Select Selects voltage to monitor within the IREF block. 00 - vref 01 - pgate 10 - vbc 11 - vref loop
29	0h RW	iopampsfpn_h: (NOT USED - noconned)
28	0h RW	iopampsfn_h: (NOT USED - noconned)
27	0h RW	iopampn_h: DC Monitor Unity-Gain Buffer Enable 0: disable (default) 1: enable
26	0h RW	iopampn_h: (NOT USED - noconned)
25	0h RW	monanapgn: DC Monitor to Monitor Port Enable Enables DC monitor passgate to monitor port via analog observability abutment.
24	1h RW	monubufbypassen: DC Monitor Unity-Gain Buffer Bypass 0: no bypass 1: bypass (default - required for LRC)
23:22	0h RW	reserved522: reserved
21	0h RW	reg_ivrefen: IvrefEn Override Value Register is valid when override mode is enabled (ivrefen_ovrd). During this mode, this register will have direct control to enable/disable the ivref opamp. 0 - Disable ivref opamp 1 - Enable ivref opamp
20	0h RW	ivrefen_ovrd: IvrefEn Override Select 0 - the enable for the ivref opamp (ivrefen) is driven by the FSM. 1 - the ivrefen is driven by the register (reg_ivrefen).
19:17	0h RW	reserved523: reserved
16	0h RW	oierfurmonsel: IREF Current Monitor Select Enables current mirror from the IREF block to the 'shared' analog monitor port.
15	0h RW	lrcdisable: LRC Disable This bit disables the LRC. Any token received is passed to the next lane.
14:12	0h RW	reserved521: reserved
11	0h RW	lrc_rdy_pulsegen: LRC Ready PulseGen Generates a pulse 1 cal_clk cycle wide on the lrc_rdy signal to all four targets; does not recompute local Rcomp code. Values in DWD 0x14 (*rccodes[7:0]) will be latched into targets. User must clear this bit before generating another pulse. Note: User should disable PM and PER. FSM can take control and codes can be overridden.
10:9	0h RW	lrc_rdy_target_1_0: LRC Ready Pulse Target Indicates which lrc target to recompute when lrc_rdy_ovd is strobed 00: irefrcode 01: txrcode 10: rxtermrcode 11: rxvgarrcode



23.9.23 PCS_DWORD22 (pcs_dword22)—Offset 58h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword22: [Port: 0xA6] + (400h + 58h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0			
0	0	0	0	0	0	0	0	0			
rxvgarcoffset_7_0				rxtermrcoffset_7_0				txrcoffset_7_0			
								irefrcoffset_7_0			

Bit Range	Default & Access	Description
31:24	0h RW	rxvgaroffset_7_0: Rx VGA Rcomp Offset Same description as IREF Rcomp Offset, but applies to RxVGA Rcomp.
23:16	0h RW	rxtermrcoffset_7_0: Rx Termination Rcomp Offset Same description as IREF Rcomp Offset, but applies to RxTerm Rcomp.
15:8	0h RW	txrcoffset_7_0: Tx Rcomp Offset Same description as IREF Rcomp Offset, but applies to Tx Rcomp.
7:0	0h RW	irefrcoffset_7_0: Iref Rcomp Offset This value is added to the scaled LRC code to determine the final calibration code used by the Iref block. 2's complement format. The full 8-bit offset is used with the scale multiplier to determine the final 8-bit value, but the Iref target only uses the upper MSBs of the final value. 0x00: Offset = 0 0x01: Offset = +1 0x7F: Offset = +127 0xFF: Offset = -1 0x80: Offset = -128 Note: The final rcomp code has rollover protection so the final rcomp code + offset will not exceed the min/max range.

23.9.24 PCS_DWORD23 (pcs_dword23)—Offset 5Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)


pcs_dword23: [Port: 0xA6] + (400h + 5Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00180888h

31				28				24				20				16				12				8				4				0											
0				0				0				0				1				1				0				0				0				0				0			
iclkcqcf_spare_7_0								iclkcqcf_spare_7				iclkcqcf_spare_6_3				iclkcqcf_spare_2_0				reserved526				i_drvcfg_3_0				i_ploadcfg_3_0				ipbiasctrl_3_0											



Bit Range	Default & Access	Description
16	1h RW	cri_lanereset_clkgatectl: 1: The assertion of lane reset will have the effect of gating the susclk and de-asserting the internal laneclkreq. This mode is only valid when the data lane dynamic clock gating mode is set to a non-zero value (i.e. 01, 10, and 11). 0: The assertion of lane reset will have no effect on the gating of susclk and state of the internal laneclkreq signal.
15	1h RW	cri_lanereqforce: Controls whether the internal laneclkreq will be forced to 1 or 0 when cfg_data_dynclkgate_mode is set to 00 or 10. 1: force laneclkreq high 0: force laneclkreq low. This mode will likely be used when one of the lanes is disabled while other lanes in the family are enabled. In this case the internal laneclkreq of the disabled lane should be de-asserted (not influencing the clk gating decision)
14:10	10h RW	cri_susclkdisable_delay_4_0: This register will control the number of cycles to delay the susclk enable de-assertion, in addition to the de-assertion of the laneclkreq signal sent out of the data lane. The susclk enable must be continuously de-asserted for the duration of this delay in order for the de-asserted state to be captured by the clock gating controller. 5'b00000 - 0 Cycle Delay 5'b00001 - 1 Cycle Delay 5'b00010 - 2 Cycle Delay 5'b11110 - 30 Cycle Delay 5'b11111 - 31 Cycle Delay
9:8	0h RW	cri_data_dynclkgate_mode_1_0: Controls the dynamic clock gating behavior in the data lane. 00 - susclk gating and laneclkreq disabled (Forced to configured value). In this mode the susclk will not be gated under any circumstances and the laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 01 - susclk gating disabled, laneclkreq enabled . In this mode the susclk will not be gated under any circumstances. The laneclkreq sent out of the data lane will toggle based on whether the lane power state, susclk need and the previous lane's laneclkreq signal. 10 - susclk gating enabled, laneclkreq disabled (forced to configured value) - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 11 - susclk gating and laneclkreq enabled - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the data lane will toggle based on the lane power state, susclk need and the previous lane's laneclkreq signal.
7	0h RW	cri_eios_waittime_ovren: EIOS Wait Time Override Enable for Rx Turn OFF 0: hardware value for EIOS wait timer is selected. 1: selects cri_eios_waittime[6:0]
6:0	20h RW	cri_eios_waittime_6_0: EIOS Wait Time for Rx Turn OFF Represents override value timer in PCS that comes into play during EIOS based turn off Rx (Rx L0s) 0000000 - Timer is bypassed 0000001 - 1 PLL link clock period delay (2ns) 0000010 - 2 PLL link clock period delay (4ns) ... 0100000 - 32 PLL link clock periods delay (64ns) - default



Access Method


tx_dword1: [Port: 0xA6] + (480h + 4h)

Op Codes:

0h - Read, 1h - Write

Default: 20000000h

Bit Range	Default & Access	Description
31:30	0h RO	reserved510: reserved
29:24	20h RW	ofrcr2short3_5_0: number of slices in R2 for swing 3 (DE) MSB has no effect.
23:22	0h RO	reserved509: reserved
21:16	0h RO	reserved508: reserved
15:14	0h RO	reserved507: reserved
13:8	0h RO	reserved506: reserved



October 2018
Document Number: 538136, Rev. 4.3



23.10.5 TX_DWORD4 (tx_dword4)—Offset 10h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword4: [Port: 0xA6] + (480h + 10h)

Op Codes:

0h - Read, 1h - Write

Default: 2B40D55h

31	28	24	20	16	12	8	4	0
0	0	1	0	1	0	1	1	0
0	0	1	0	1	1	0	0	1
ow2tapdeemph9p5_7_0								
ow2tapdeemph6p0_7_0								
ow2tapgen2deemph3p5_7_0								
ow2tapgen1deemph3p5_7_0								

Bit Range	Default & Access	Description
31:24	2Bh RW	ow2tapdeemph9p5_7_0: factor (X/128) of slices to use in main-R1 out of the slices in main-R1 in full-swing. Normally - in order to have 9.5dB deemphais
23:16	40h RW	ow2tapdeemph6p0_7_0: factor (X/128) of slices to use in main-R1 out of the slices in main-R1 in full-swing. Normally - in order to have 6.0dB deemphais
15:8	4Dh RW	ow2tapgen2deemph3p5_7_0: factor (X/128) of slices to use in main-R1 out of the slices in main-R1 in full-swing. Normally - in order to have 3.5dB deemphais
7:0	55h RW	ow2tapgen1deemph3p5_7_0: factor (X/128) of slices to use in main-R1 out of the slices in main-R1 in full-swing. Normally - in order to have 3.5dB deemphais

23.10.6 TX_DWORD5 (tx_dword5)—Offset 14h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword5: [Port: 0xA6] + (480h + 14h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0				0				0				0				0				0				0				0				0			
ocalcinit				reserved515								reserved514								reserved513								reserved512							



Access Method

tx dword6: [Port: 0xA6] + (480h + 18h)

0h - Read, 1h - Write

31		28				24				20				16				12				8				4				0																														
0	0	0	1	1	1	1	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																												
reserved520					consbypass_6_0								reserved519								opsbypass_6_0								reserved518								reserved517								ocalcont								reserved516							

Bit Range	Default & Access	Description
31	0h RO	reserved520: reserved
30:24	1Fh RW	onswbypass_6_0: Determines # of slices activated in N-drv when in strong pulling to CM (after Rx-dtct/ gohighz / stongPD) same slices cannot be opened for P-drv and for N-drv. Determines # of slices for P-drv in All1/All0 DFTs when bypbycomp is not asserted. In these DFT modes pswpass can be set to the same value as nswbypass
23	0h RO	reserved519: reserved
22:16	20h RW	opswbypass_6_0: Determines # of slices activated in P-drv when in strong pulling to CM (after Rx-dtct/ gohighz / stongPD) Determines # of slices for P-drv in All1/All0 DFTs when bypbycomp is not asserted.
15	0h RO	reserved518: reserved
14:8	0h RO	reserved517: reserved
7	0h RW	ocalccont: initiate calculation of swing-control circuit. While this signal is '1' the calculation is being done consecutively

23.10.8 TX_DWORD7 (tx_dword7)—Offset 1Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx dword7: [Port: 0xA6] + (480h + 1Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0038383Fh

31				28				24				20				16				12				8				4				0															
0 0 0 0				0 0 0 0				0 0 1 1				1 0 0 0				0 0 1 1				1 0 0 0				0 0 1 1				1 1 1 1																			
reserved527				reserved526				reserved525				reserved524				reserved523				oslrctrl2_l_2_0				oslrctrl2_h_2_0				reserved522				oslrctrl_l_2_0				oslrctrl_h_2_0				reserved521				or2bypass_5_0			

Bit Range	Default & Access	Description
31:30	0h RO	reserved527: reserved
29:27	0h RO	reserved526: reserved
26:24	0h RO	reserved525: reserved
23	0h RO	reserved524: reserved
22	0h RO	reserved523: reserved
21:19	7h RW	oslrctrlr2_l_2_0: Slew rate trimming of driver in R2 resistor for gen1. '000' - disabled '001' - slowest '111' - fastest
18:16	0h RW	oslrctrlr2_h_2_0: Slew rate trimming of driver in R2 resistor for gen1 '111' - disabled (emulates suspend mode) '110' - slowest '000' - fastest
15:14	0h RO	reserved522: reserved
13:11	7h RW	oslrctrl_l_2_0: Slew rate trimming of driver in R1 resistor for gen1. '000' - disabled '001' - slowest '111' - fastest
10:8	0h RW	oslrctrl_h_2_0: Slew rate trimming of driver in R1 resistor for gen1 '111' - disabled (emulates suspend mode) '110' - slowest '000' - fastest
7:6	0h RO	reserved521: reserved
5:0	3Fh RW	or2bypass_5_0: Number of open R2s in normal EI (electrical idle) Used in DFTs with other values (leg connectivity scan all power of 2s) read also notes on obybybcomp. MSB has no effect.



23.10.9 TX_DWORD8 (tx_dword8)—Offset 20h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword8: [Port: 0xA6] + (480h + 20h)

Op Codes:

0h - Read, 1h - Write

Default: 0600AA80h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	0	1	0
0	0	0	0	0	0	0	0	0
0	1	1	0	0	0	0	0	0
ontlptime_7_0	ofrcdccoup_1_0	obybbycomp	obypdftmode_4_0	odftpisodata1_7_0	odftpisodata0_1_0	reserved529	reserved528	

Bit Range	Default & Access	Description
31:24	6h RW	ontlptime_7_0: [after step 1 of pullup] time (ick_susslow cycles) to wait (step 2) and let the pads leak downwards before comparing pads to Vref to determine if the pad exceeded Vref as a result of leakage.
23:22	0h RW	ofrcdccoup_1_0: 00
21	0h RW	obybbycomp: 0' the amount of slices used in dftbypmode is by 'nswbypass', 'pswbypass' and 'r2bypass' registers '1' the amount of slices used is by 'slices' from swing-control block. Number of slices in R2 in EI - is also affected by this bit
20:16	0h RW	obypdftmode_4_0: selects the DFT mode. 5'h00 - DFT_OFF 5'h01 - DFTHIZ 5'h02 - DFTEI 5'h03 - DFTFELB 5'h04 - DFTALL1DIF 5'h05 - DFTALL0DIF 5'h06 - DFTALL1SE 5'h07 - DFTALL0SE 5'h08 - DFTDAC 5'h09 - DFTFRCBEAC 5'h0a - DFTOBS 5'h0c - DFT ASYNC MODE OFF 5'h0d - DFT ASYNC MODE Tx (output) 5'h0e - DFT ASYNC MODE Rx (input) 5'h0f - DFT ASYNC MODE Both (inout) 5'h10 - DFTPISOLOAD 5'h12 - DFTEISTRNG
15:8	AAh RW	odftpisodata1_7_0: 8 MSB of alternative data input to PISO Load of this data is enabled when bypdftmode=DFTPISOLOAD
7:6	2h RW	odftpisodata0_1_0: 2 LSB of alternative data input to PISO Load of this data is enabled when bypdftmode=DFTPISOLOAD
5:3	0h RO	reserved529: reserved
2:0	0h RO	reserved528: reserved

23.10.10 TX_DWORD9 (tx_dword9)—Offset 24h

Access Method


Type: Message Bus Register
(Size: 32 bits)

tx_dword9: [Port: 0xA6] + (480h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00430C06h



23.10.11 TX_DWORD10 (tx_dword10)—Offset 28h

Type: Message Bus Register
(Size: 32 bits)

Op Codes:

Intel Atom® Processor E3800 Product Family
Datasheet
3327

23.10.12 TX_DWORD11 (tx_dword11)—Offset 2Ch

31				28				24				20				16				12				8				4				0			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0			
isparead_7_0								reserved532								reserved531								ircvdtctmpout				intpass_3_0							
																								idftcptestsig											
																								idftcrvdetectedtx											
																								idftcrvdetectedtxp											
																				idftcrvdetectedfinished															
																				intfinished															

Bit Range	Default & Access	Description
31:24	X RO	ispareread_7_0: spare reg read
23:16	0h RO	reserved532: reserved
15:10	0h RO	reserved531: reserved
9	0h RO	ircvdtctcmpout: Flash Comparator Output Value
8	X RO	idftcaptestsig: reserved
7	0h RO	idftrcvdetectedtxn: Receive Detect Result for Txn
6	0h RO	idftrcvdetectedtxp: Receive Detect Result for Txp
5	0h RO	idftrcvdetectfinished: Receive Detect Process status
4	X RO	intlfinished: indication of NTL finished
3:0	X RO	intlpass_3_0: the four outputs of NTL test

Access Method


Type: Message Bus Register
(Size: 32 bits)

tx_dword11: [Port: 0xA6] + (480h + 2Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00001000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
oselsparetxclkkin_2_0	ofrcdotprocess_2_0	ofrcgohighzdis	ofrcgohighzen	ofrcstrongpddis	ofrcstrongpden	ofrcctxclkrootdis	ofrcctxclkrooten	reserved537
				ofrcpwrmodel1	ofrcpwrmodel0s	ofrcpwrmodel0	ofrcmkeepadnen	ofrcmkeepadpen
							ofrcmkeepadndis	ofrcmkeepadpdis
							omakedeeperfifo	ofrcldatencyoptim_2_0
							reserved536	ofrcrcvdtcten
							ofrcrcvdtctrate_1_0	reserved535
								reserved534
								reserved533
								oneloopbacken

Bit Range	Default & Access	Description
31:29	0h RW	oselsparetxclkkin_2_0: Selects data to be used as alternative to fast clock. 000: DAC clock if in DAC mode - Default. 001: cri100m clock 010: i_obsontx_psg 011: i_obsontx_nsg 100: ick_txsymbolck 101: icksusslow 110: ick_dac 111: spare
28:26	0h RW	ofrcdotprocess_2_0: forces the dotprocess information 0XX - information of dot process comes from i_dotprocess[1:0] input bus. 100: p1271 dot1 101: p1271 dot4 110: p1271 dot8 111: NA
25	0h RW	ofrcgohighzdis: forces disabling of high-z output
24	0h RW	ofrcgohighzen: forces enabling of high-z output
23	0h RW	ofrcstrongpddis: forces disabling of strong pull-down
22	0h RW	ofrcstrongpden: forces enabling of strong pull-down
21	0h RW	ofrcctxclkrootdis: forces disable of tx-clock output.
20	0h RW	ofrcctxclkrooten: forces tx-clock to operate and drive clock out.
19	0h RO	reserved537: reserved
18	0h RW	ofrcpwrmodel1: when aserted. Forces L1 state
17	0h RW	ofrcpwrmodel0s: when aserted. Forces L0s state
16	0h RW	ofrcpwrmodel0: when aserted. Forces L0 state
15	0h RW	ofrcmkeepadnen: Forces enabling of common-mode keeping of PadN
14	0h RW	ofrcmkeepadpen: Forces enabling of common-mode keeping of PadP
13	0h RW	ofrcmkeepadndis: Forces disabling of common-mode keeping of PadN
12	1h RW	ofrcmkeepadpdis: Forces disabling of common-mode keeping of PadP
11	0h RW	omakedeeperfifo: Make FIFO deeper by 1 symbol clock cycle. Still not implemented. Implementation costs 10 flops in symb clock domain. Implementation is required for 8bits PISO only which is in next phase of products.



Bit Range	Default & Access	Description
10:8	0h RW	ofrclatencyoptim_2_0: Changes the latency from loadgenen assertion to the sampling of 10bits data into fast-clock domain. The latency is determined by Fuses (through i_latencyoptim[1:0]) + ... 0XX =) + 0 (Not changing the latency.) 100 =) - 4UI 101 =) - 2UI 110 =) + 2UI 111 =) + 4UI Important Note: When changing the latency too high or too low is will wrap-around what might cause data loss on beginning or end of transmitting. If you decide to plan with the latency consider changing 'omakedeeperfifo' too
7	0h RO	reserved536: reserved
6	0h RW	ofrcrcvdtcten: force initiation of Tx-detect-Rx procedure
5:4	0h RW	otxrcvdtctclkrate_1_0: determines the clock rate in the flash comparator. 00 - use sus-clock as is (25MHz in phase2) default 01 - use sus-clock by 4 10 - use sus-clock by 2 11 - reserved In phase1 the rate was 2'b10 susfreq125MHz
3	0h RO	reserved535: reserved
2	0h RO	reserved534: reserved
1	0h RO	reserved533: reserved
0	0h RW	oneloopbacken: Near-End LoopBack enable


Type: Message Bus Register
(Size: 32 bits)

tx dword12: [Port: 0xA6] + (480h + 30h)

0h - Read, 1h - Write

31				28				24				20				16				12				8				4				0																							
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0																							
otxcikbypsel_1_0				ofrcdatarefit_2_0				odistxfelbpin				otxcikampbypsn				otxcikampbypsp				reserved539				odfxanamuxen				odfxanamuxsel_1_0				obs_tx_gated_supply_1_0				reserved538				oobsdigselectupn_3_0				oobsdigselectupp_3_0				oobsdigselectdownn_3_0				oobsdigselectdownp_3_0			

Bit Range	Default & Access	Description
31:30	0h RW	otxclkbypsel_1_0: Select if to bypass the divided normal clock with some other clock. 2'b00: Don't bypass. Regular clock. 2'b01: bypass the RX clock - dataratefit must be '11' 2'b10: Reserved 2'b11: bypass the sparetxclk clock - dataratefit must be '11'



Bit Range	Default & Access	Description
29:27	0h RW	ofrcdata rate fit_2_0 : Forces TX data rate 3'b0XX - don't force a value. get it from the I/F pin 3'b100 - no divide (2UIs per clock cyc) 3'b101 - divide by 2 3'b110 - divide by 4 3'b111 - divide by 8 - used also for bypassing with other clocks
26	0h RW	odistxfelbpin : when asserted - disables the i_txfelben pin at the interface and force it 0. (needed in case the pin is asserted in KX or sata1 mode)
25	0h RW	otxcikampbypsn : 0': Normal operation '1': Enable of the passgate connected from the analog clock N to the control of the DC correction cell. The feedback OTA is disabled.
24	0h RW	otxcikampbypsp : 0': Normal operation '1': Enable of the passgate connected from the analog clock P to the control of the DC correction cell. The feedback OTA is disabled.
23	0h RO	reserved539 : reserved
22	0h RW	odfxanamuxen : Enables analog signals probing mux out. When enabled the Vref of Tx-detect-Rx circuit is observed. Note that only one lane is allowed to have the analog mux enabled to avoid collisions.
21:20	0h RW	odfxanamuxsel_1_0 : selects analog signal to be sent to analog port in common lane. This bus has no affect at all currently because there is only one analog signal for observation which is observed by odfxanamuxen
19:18	0h RW	obs_tx_gated_supply_1_0 : Monitor gated vcc supply to Tx upar
17:16	0h RO	reserved538 : reserved
15:12	0h RW	oobsdigselectupn_3_0 : selects data to be sent to observability port output 'o_obsup_nsg'. Same mapping as oobsdigselectdownn[3:0]
11:8	0h RW	oobsdigselectupp_3_0 : selects data to be sent to observability port output 'o_obsup_psg'. Same mapping as oobsdigselectdownp[3:0]
7:4	0h RW	oobsdigselectdownn_3_0 : Reserved.
3:0	0h RW	oobsdigselectdownp_3_0 : Reserved.

23.10.14 TX_DWORD13 (tx_dword13)—Offset 34h

Access Method

Type: Message Bus Register
(Size: 32 bits)


tx_dword13: [Port: 0xA6] + (480h + 34h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved543	ir2short3_5_0	reserved542	ir2short0_5_0	reserved541	ir1main3_6_0	reserved540	ir1main0_6_0	



Bit Range	Default & Access	Description
31:30	0h RO	reserved543: reserved
29:24	X RO	ir2short3_5_0: The slices used in R2 for DE (sub-DE in 3tap FIR) (PstC=Y,C=Y,PreC=Y)
23:22	0h RO	reserved542: reserved
21:16	X RO	ir2short0_5_0: The slices used in R2 for FS (sub-FS in 3tap FIR) (PstC=Y,C=Y,PreC=X)
15	0h RO	reserved541: reserved
14:8	X RO	ir1main3_6_0: The slices used in R1 for DE (sub-DE in 3tap FIR) (PstC=Y,C=Y,PreC=Y)
7	0h RO	reserved540: reserved
6:0	X RO	ir1main0_6_0: The slices used in R1 for FS (sub-FS in 3tap FIR) (PstC=Y,C=Y,PreC=X)

23.10.15 TX_DWORD14 (tx_dword14)—Offset 38h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword14: [Port: 0xA6] + (480h + 38h)

Op Codes:

0h - Read, 1h - Write

Default: 00400000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ospare1_1_0	osimmode	ontlmodepin2pin	ofrcdatapathdis	ofrcdatapathen	ofrcdrvbydpdis	ofrcdrvbyopen	odfttxclkcaptesten	otxdccbyps_i
			ofrcnm32ldv_2_0	ofrcpm32ldv_2_0	visa_en	ovisa1_clkssel_2_0	ovisa1_lanese1_3_0	ovisa_bypass
								ovisa0_clkssel_2_0
								ovisa0_lanese1_3_0

Bit Range	Default & Access	Description
31:30	0h RW	ospare1_1_0: reserved
29	0h RW	osimmode: Counter threshold of receive-detect, NTL, strong-common-mode is shortened dramatically for fast simulation porpuses. (does not impose risk to circuitly but electrical spec will not met)
28	0h RW	ontlmodepin2pin: 0 - NTL procedure will be done per pad while both pads are pulled to the same rail. 1 - NTL procedure will be done per pad while the pads are pulled to opposite rails.
27	0h RW	ofrcdatapathdis: DFT feature to optionally be used with other registers

Bit Range	Default & Access	Description
26	0h RW	ofrcdatapathen: DFT feature to optionally be used with other registers
25	0h RW	ofrcdrvbydis: DFT feature to optionally be used with other registers
24	0h RW	ofrcdrvbypen: DFT feature to optionally be used with other registers
23	0h RW	odfttxclkcaptesten: Enables the finger capacitor quality check in the DCC block in Tx-clock block. The test is for shorts between the capacitor terminals.
22	1h RW	otxdccbyps_l: Tx DCC Bypass Override Puts DCC (duty cycle correction) circuit in bypass mode 0 - clock's duty cycle is not fixed
21:19	0h RW	ofrcnmos32idv_2_0: change the value iabut_idvpms32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
18:16	0h RW	ofrcpms32idv_2_0: change the value iabut_idvpms32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
15	0h RW	visa_en: VISA Enable for the Tx VISA logic
14:12	0h RW	ovisa1_clkssel_2_0: VISA Clock Select for Lane1. Selects the source synchronous clock to be used for data being sent on lane1.
11:8	0h RW	ovisa1_lanesel_3_0: VISA Lane Select for Lane1. Selects the byte of data to be sent out on lane1.
7	0h RW	ovisa_bypass: VISA Bypass. Allows for signals to be passed asynchronously through VISA block. Applies to both lane0 and lane1. 0 : Flop signals in local VISA block (default) 1 : Bypass flops in local VISA block
6:4	0h RW	ovisa0_clkssel_2_0: VISA Clock Select for Lane0. Selects the source synchronous clock to be used for data being sent on lane0.
3:0	0h RW	ovisa0_lanesel_3_0: VISA Lane Select for Lane0. Selects data byte to be driven out of VISA-0 byte. Can be either clocked or unclocked data

23.10.16 TX DWORD15 (tx_dword15)—Offset 3Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword15: [Port: 0xA6] + (480h + 3Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
reserved551				reserved550				reserved549				reserved548				reserved547				reserved546				reserved545				reserved544							

23.10.17 TX_DWORD16 (tx_dword16)—Offset 40h

Bit Range	Default & Access	Description
31:30	0h RO	reserved551: reserved
29:24	0h RO	reserved550: The slices used in R2 for DE (PstC=X,C=Y,PreC=Y)
23:22	0h RO	reserved549: reserved
21:16	0h RO	reserved548: The slices used in R2 for FS (PstC=X,C=Y,PreC=X)
15	0h RO	reserved547: reserved
14:8	0h RO	reserved546: The slices used in R1 for DE (PstC=X,C=Y,PreC=Y)
7	0h RO	reserved545: reserved
6:0	0h RO	reserved544: The slices used in R1 for FS (PstC=X,C=Y,PreC=X)

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx dword16: [Port: 0xA6] + (480h + 40h)

Op Codes:

0h - Read, 1h - Write

Default: 00008A00h

31				28				24				20				16				12				8				4				0							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	0	1	0	0	0	0	0	0	0	0	0	0						
reserved554								reserved553								ocurcomp0ei_2_0				reserved552				omediumcompadn_1_0				omediumcompadp_1_0				ospare3_3_0				ospare2_3_0			

Bit Range	Default & Access	Description
31:24	0h RO	reserved554: reserved
23:16	0h RO	reserved553: reserved
15:13	4h RW	ocurconp0ei_2_0: current consumed (typically) 00X - 0.0mA - not active 01X - 0.9mA 10X - 1.8mA 11X - 2.7mA
12	0h RO	reserved552: reserved



Bit Range	Default & Access	Description
11:10	2h RW	omediumcmpadn_1_0: During P0-EI pad-N will be on medium strength CM and will cause the following current consumption: 00 - 0.00mA (disable) 01 - 2.45mA 10 - 4.87mA 11 - 9.73mA
9:8	2h RW	omediumcmpadp_1_0: During P0-EI pad-P will be on medium strength CM and will cause the following current consumption: 00 - 0.00mA (disable) 01 - 2.45mA 10 - 4.87mA 11 - 9.73mA
7:4	0h RW	ospare3_3_0: 4 spare CRI register bits
3:0	0h RW	ospare2_3_0: 4 spare CRI register bits



23.11 PCI Express* Lane 2 Electrical Address Map

Table 248. Summary of PCI Express* Lane 2 Electrical Message Bus Registers—0xA6 (Global Offset 600h)

Offset	Register ID—Description	Default Value
0h	"PCS_DWORD0 (pcs_dword0)—Offset 0h" on page 3337	00010080h
4h	"PCS_DWORD1 (pcs_dword1)—Offset 4h" on page 3339	00600060h
8h	"PCS_DWORD2 (pcs_dword2)—Offset 8h" on page 3340	00000000h
Ch	"PCS_DWORD3 (pcs_dword3)—Offset Ch" on page 3342	5515ACAAh
10h	"PCS_DWORD4 (pcs_dword4)—Offset 10h" on page 3342	575555C1h
14h	"PCS_DWORD5 (pcs_dword5)—Offset 14h" on page 3343	00003E63h
18h	"PCS_DWORD6 (pcs_dword6)—Offset 18h" on page 3345	FFFFFFFFh
1Ch	"PCS_DWORD7 (pcs_dword7)—Offset 1Ch" on page 3345	00000009h
20h	"PCS_DWORD8 (pcs_dword8)—Offset 20h" on page 3346	000000C4h
24h	"PCS_DWORD9 (pcs_dword9)—Offset 24h" on page 3348	00000000h
28h	"PCS_DWORD10 (pcs_dword10)—Offset 28h" on page 3349	00000000h
2Ch	"PCS_DWORD11 (pcs_dword11)—Offset 2Ch" on page 3350	0F000000h
30h	"PCS_DWORD12 (pcs_dword12)—Offset 30h" on page 3352	00250F00h
34h	"PCS_DWORD13 (pcs_dword13)—Offset 34h" on page 3353	00000000h
38h	"PCS_DWORD14 (pcs_dword14)—Offset 38h" on page 3354	007A0018h
3Ch	"PCS_DWORD15 (pcs_dword15)—Offset 3Ch" on page 3355	04100300h
40h	"PCS_DWORD16 (pcs_dword16)—Offset 40h" on page 3357	01000001h
44h	"PCS_DWORD17 (pcs_dword17)—Offset 44h" on page 3358	01000001h
48h	"PCS_DWORD18 (pcs_dword18)—Offset 48h" on page 3360	00008080h
4Ch	"PCS_DWORD19 (pcs_dword19)—Offset 4Ch" on page 3361	00004F10h
50h	"PCS_DWORD20 (pcs_dword20)—Offset 50h" on page 3362	80808080h
54h	"PCS_DWORD21 (pcs_dword21)—Offset 54h" on page 3363	80808080h
58h	"PCS_DWORD22 (pcs_dword22)—Offset 58h" on page 3364	00000000h
5Ch	"PCS_DWORD23 (pcs_dword23)—Offset 5Ch" on page 3364	00180888h
60h	"PCS_DWORD24 (pcs_dword24)—Offset 60h" on page 3365	0001C020h

23.11.1 PCS_DWORD0 (pcs_dword0)—Offset 0h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword0: [Port: 0xA6] + (600h + 0h)

Op Codes:

0h - Read, 1h - Write

Default: 00010080h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_txcfgchange_valid_delay_3_0	reg_txcfgchange_rst_delay_3_0	reserved500	reg_txcfgchange_width_4_0	reg_txcfgchange_ovrride	reg_tx2_soft_reset_n	reg_txswing_clkssel	reg_rcvdetect_ovrd	reg_rcvdetectfinished
							reg_rcvdetect_pulse_width_ovrd	reg_rcvdetect_pulse_width_2_0
							reg_tx1_soft_reset_n	reg_tx_8b10b_bypass
							reg_tx_laneup	reg_left_txiffo_rst_master2
							reg_right_txiffo_rst_master2	reg_plllinksynch_ovrden
							reg_plllinksynch_ovrd	reg_tx1_cmmdisparity

Bit Range	Default & Access	Description
31:28	0h RW	reg_txcfgchange_valid_delay_3_0: Controls counter to wait 128ns after txcfgchange asserts when coming out of reset. This will control phystatus de-assertion after reset. Note: Minimum value when programmed has to be 4'b0100 or greater.
27:24	0h RW	reg_txcfgchange_rst_delay_3_0: Counter value to delay txcfgchange toggle after coming out of reset.
23	0h RW	reserved500: reserved
22:18	0h RW	reg_txcfgchange_width_4_0: Tx power fsm output - divider ratio
17	0h RW	reg_txcfgchange_ovrride: Override txchfchange related counters. (reg_txcfgchange_width, reg_txcfgchange_valid_delay, reg_txcfgchange_rst_delay)
16	1h RW	reg_tx2_soft_reset_n: Active low reset to independently reset Tx lane2 in Display Port
15	0h RW	reg_txswing_clkssel: When 0 selects divide by 2 version of the ick_pllclk clock for Tx swing control logic When 1 selects ick_pllclk clock for Tx swing control logic.
14	0h RW	reg_rcvdetect_ovrd_____: override enable for rcvdetect and rcvdetectfinished
13	0h RW	reg_rcvdetect_____: override for rcvdetect
12	0h RW	reg_rcvdetectfinished_____: override for rcvdetectfinished
11	0h RW	reg_rcvdetect_pulse_width_ovrd: override enable for rcvdetect_pulse_width
10:8	0h RW	reg_rcvdetect_pulse_width_2_0: override value for rcvdetect_pulse_width
7	1h RW	reg_tx1_soft_reset_n: Active low reset to independently reset Tx lane1 in Display Port 0: Lane 1 reset 1: Lane 1 active
6	0h RW	reg_tx_8b10b_bypass: Bypass 8b10b encoder (for SAPIS etc interface.) 0 = Disable 8b/10b encoder bypass 1 = Enable 8b/10b encoder bypass



Bit Range	Default & Access	Description
5	0h RW	reg_tx_laneup: Unused in Tx
4	0h RW	reg_left_txfifo_rst_master2: override enable = reg_lanedeskew_strap_ovrd
3	0h RW	reg_right_txfifo_rst_master2: override enable = reg_lanedeskew_strap_ovrd
2	0h RW	reg_plllinksynch_ovrden: Override enable for reg_pllinsync_ovrd 0 = Use default delay in hardware 1 = Use reg_plllinksynch_ovrd
1	0h RW	reg_plllinksynch_ovrd: override value for plllinksynch
0	0h RW	reg_tx1_cmmdisparity: Sets the initial disparity during Compliance Measurement Mode, used together with pcs_txcompliance pulse. 0 = set negative disparity 1 = set positive disparity

23.11.2 PCS_DWORD1 (pcs_dword1)—Offset 4h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs dword1: [Port: 0xA6] + (600h + 4h)

Op Codes:

Op codes:
0h - Read, 1h - Write

Default: 00600060h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_txfsfm_4us_delay_7_0								
reg_softreset_enable								
cri_rxeb_eiosenable								
cri_rxdigfiltsq_enable								
reg_txfsfm_delay_ovrd								
reg_txfsfm_4us_delay_11_8								
reg_pclk_rate_1_0								
reg_rate_1_0								
reg_phymode_2_0								
reg_modeovren								
reg_datawidth								
soft_reset_n								
reg_diginelben								
reg_digifelben								
reg_strapgroup_ovrdn								
reg_yank_timer_done_b_ovrd								
reg_yank_timer_done_b_ovrd_en								

Bit Range	Default & Access	Description
31:24	0h RW	reg_tx fsm_4us_delay_7_0: Override counter value for 4 us delay in tx fsm lane reset to tx biaseden delay
23	0h RW	reg_softreset_enable: When '1' the soft_reset_n bit will control the lane reset When '0' the hardware reset will control the lane reset Note for DP: In addition to soft_reset_n, which will reset both TX0 and TX 1 in the lane, the reg_tx1_soft_reset_n bit can be used to reset only TX1 in the lane and reg_tx2_soft_reset_n bit can be used to reset only TX2
22	1h RW	cri_rxeb_eiosenable: When 1 enables EIOS based Rx power down



Bit Range	Default & Access	Description
21	1h RW	cri_rxdigfiltlsq_enable: When 1 enables unsquelch based Rx power up in P0 or P0s
20	0h RW	reg_txfsfm_delay_ovrd: Override enable bit for reg_txfsfm_4us_delay
19:16	0h RW	reg_txfsfm_4us_delay_11_8: Override counter value for 4 us delay in txfsfm lane reset to txbiasen delay
15:14	0h RW	reg_pclk_rate_1_0: Override for pclk_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
13:12	0h RW	reg_rate_1_0: Override for i_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
11:9	0h RW	reg_phymode_2_0: Override for PHY Mode Selection 000 = PCIE 001 = USB3 010 = GbE 011 = SATA/SAPIS 100 = Display 101 = DMI 110 = CIO 111 =Reserved
8	0h RW	reg_modeovren: When asserted selects register override bits for phymode, datawidth etc
7:6	1h RW	reg_datawidth: Override for Tx data interface width. 00 - Unused 01 - x8/x10 width (default) 10 - x16/x20 width 11 - x32/x40 width
5	1h RW	soft_reset_n: Active low soft reset override
4	0h RW	reg_diginelben: Override for near end digital loopback.
3	0h RW	reg_digifelben: Override for far end digital loopback
2	0h RW	reg_strapgroup_ovrden: Override Enable for Strap Group
1	0h RW	reg_yank_timer_done_b_ovrd: Override for yank_timer_done_b
0	0h RW	reg_yank_timer_done_b_ovrd_en: Override Enable for yank_timer_done_b

23.11.3 PCS_DWORD2 (pcs_dword2)—Offset 8h

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword2: [Port: 0xA6] + (600h + 8h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_pibiasoff_delay_3_0	cri_sqdbexittimer_override_3_0	cri_sqdbentrytimer_override_5_0	reg_rxdrcgtsqsel_1_0	cri_reut_SlaveSideDataCheckingEn	cri_sqdbtimer_ovren	cri_rxpwrfsm_timer_ovren	reg_rxidle	cri_rxrawdata_sel
				cri_dynkalign_eco3302703_mode	cri_dynkalign_eco3302703_ovren	reg_rxpwrfsm_pibiasoff_ovrride	cri_reset_kalignlck	cri_ebptrrst
							cri_comdispfix	cri_forcebankhit
							cri_kalignmode_1_0	cri_skpprocdis
								cri_elasticbuffer_maskdis

Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_pibiasoff_delay_3_0: Override value for delay (in 2ns increments) between deassertion of opianclkbufen and opibiasen
27:24	0h RW	cri_sqdbexittimer_override_3_0: Rx squelch exit debounce timer
23:18	0h RW	cri_sqdbentrytimer_override_5_0: Rx squelch entry debounce timer
17:16	0h RW	reg_rxdrcgtsqsel_1_0: Squelch output select
15	0h RW	cri_reut_SlaveSideDataCheckingEn: Enable REUT slave side checking while in loopback slave
14	0h RW	cri_sqdbtimer_ovren: Squelch debounce timer override enable
13	0h RW	cri_rxpwrfsm_timer_ovren: Rx power management fsm timer override enable
12	0h RW	reg_rxidle: Chicken bit to override i_rxidle from controller and keep Rx in P0 or P0s
11	0h RW	cri_rxrawdata_sel: When asserted bypass K-align, 10b/8b decoder and Elastic buffer
10	0h RW	cri_dynkalign_eco3302703_mode: Kalign Mode Override Value When cri_dynkalign_eco3302703_ovren is set, this value selects kalignmode 0 - use register bits cri_kalignmode[1:0] to select kalignmode 1 - select the 4 COM kalign mode'
9	0h RW	cri_dynkalign_eco3302703_ovren: Kalign Mode Override Enable Overrides kalign mode select pin, allowing config bit kalignmode_override_val to select kalignmode.
8	0h RW	reg_rxpwrfsm_pibiasoff_ovrride: When asserted selects reg_rxpwrfsm_pibiasoff_delay[3:0]
7	0h RW	cri_reset_kalignlck: When asserted resets Kalign lock indication and Kalign is performed again. The conditions when this would assert includes and is not restricted to any power management states (L0s, L1) or polling quiet states etc.
6	0h RW	cri_ebptrrst: Global broadcast to all lanes that the Elastic Buffer pointers should be reset. This is a pulse and will be generated when we need to reset the pointers because of collision or various other reasons.
5	0h RW	cri_comdispfix: Chicken bit to force disparity in dynamic K-align mode



Bit Range	Default & Access	Description
4	0h RW	cri_forcebankhit : Chicken bit to enable data appear on NOA post k-align lock although k-align block is not achieving lock. This is only for NOA observability and not for other purpose
3:2	0h RW	cri_kalignmode_1_0 : KALIGN Mode Select 00 = dynamic kalign all the time. Accounts for bit slips on incoming stream which can cause symbol to be detected on different bank 10 = dynamic kalign up to L0 x1 = static kalign (same as GDG). Assumes symbol always detected on same data bank
1	0h RW	cri_skpprocdis : SKIP Ordered-Set Processing Disable When this configuration bit is asserted, then SKIP ordered=sets will be ignored (in EB block). Used in Elastic buffer block. 0 = Normal operation. SKIP ordered=sets will be processed by the Elastic Buffer 1 = SKIP processing disabled.
0	0h RW	cri_elasticbuffer_maskdis : Config bit (chicken bit) to disable the masking logic after elec idle ordered set is seen

23.11.4 PCS_DWORD3 (pcs_dword3)—Offset Ch

Type: Message Bus Register
(Size: 32 bits)

pcs dword3: [Port: 0xA6] + (600h + Ch)

Op Codes:

0h - Read, 1h - Write

Default: 5515ACAAh

31	28	24	20	16	12	8	4	0							
0	1	0	1	0	1	0	1	0							
cri_dfx_patbuf_55_48				cri_dfx_patbuf_63_56				cri_dfx_patbuf_71_64				cri_dfx_patbuf_79_72			

Bit Range	Default & Access	Description
31:24	55h RW	cri_dfx_patbuf_55_48: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
23:16	15h RW	cri_dfx_patbuf_63_56: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
15:8	ACh RW	cri_dfx_patbuf_71_64: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
7:0	AAh RW	cri_dfx_patbuf_79_72: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.

23.11.5 PCS_DWORD4 (pcs_dword4)—Offset 10h

Access Method



Bit Range	Default & Access	Description
31	0h RW	cri_dfx_patbuftrain: Pattern Buffer Manual Training When DFXPATBUFTRAINOVR and DFXLCCESTART are asserted, this manually controls whether the Pattern Buffers are in training or have completed training. 0 : Send training patterns (default) 1 : Send contents of DFXPATBUF
30:28	0h RW	cri_dfx_prbspoly_2_0: PRBS Polynomial Select the polynomial to be used by the PRBS in the Pattern Generator and Pattern Checker. PRBS support 10b or 8b, which is indicated by the msb. 000 - $x^{16} + x^5 + x^4 + x^3 + 1$ (USB3/PCIe Scrambler) (8b) 001 - $x^{16} + x^{15} + x^{13} + x^4 + 1$ (SATA scrambler) (8b) 010 - $x^{31} + x^{28} + 1$ (8b) 011 - $x^7 + x^6 + 1$ (8b) 100 - $x^{15} + x^{14} + 1$ (10b) 101 - $x^{23} + x^{18} + 1$ (10b) 110 - $x^{31} + x^{28} + 1$ (10b) 111 - $x^7 + x^6 + 1$ (10b)
27:26	0h RW	cri_dfx_patbufsize_1_0: Pattern Buffer Size Select the size of the Pattern Buffer to use. The MSB will always be bit 79. The LSB will depend on this select and the DFXLCCESTART (10b or 8b mode). 00 : full 80b buffer (Default) 01 : 70b (while in 10b mode), 56b (while in 8b mode) 10 : 40b (while in 10b mode), 32b (while in 8b mode) 11 : 10b (while in 10b mode), 8b (while in 8b mode)
25	0h RW	cri_dfx_patbufloop: Pattern Buffer Looping Enable Enables looping of the Pattern Buffer. By default, the contents of Pattern Buffer will be used once and stop. Alternatively, the Pattern Buffer will continue to loop until the DFXLCCESTART is de-asserted. 0 : Run Pattern Buffer only once (default) 1 : Loop Pattern Buffer until stopped
24	0h RW	cri_dfx_patbufdwidth: Pattern Buffer Data Width Selects between 10 bit or 8 bit data width for the Pattern Buffer. Determines where in the Tx/Rx path the data is inserted/retrieved. 0 : 10b (default) 1 : 8b
23	0h RW	cri_dfx_patbuftrainovr: Pattern Buffer Training Override Enables manual training of the Pattern Buffer instead of the automated coordination between the Pattern Checker and Pattern Generator. When asserted, the DFXPATBUFTRAIN bit will be used to force when training is active and when it is complete. 0 : Automatic Training (default) 1 : Enable Manual Training
22	0h RW	cri_dfx_marginmode: Margin mode Overrides standard setup configurations for use with Eye Width Margining. 0 : Standard Mode (default) 1 : Margin Mode enabled
21	0h RW	cri_dfx_chk_sel: Pattern Checker 8b10b Select This determines where Rx data is compared, either in the 10-bit domain before decode or after 10b-8b decoding. 0: 10b domain 1: 8b domain
20	0h RW	cri_dfx_patchken: Pattern Checker Enable 0 : Disable Pattern Checker (default) 1 : Enable Pattern Checker
19	0h RW	cri_dfx_patgenen: Pattern Generator Enable This will activate the Dfx bypass muxes in the PCS Tx path. 0 : Disable Pattern Generator (default) 1 : Enable Pattern Generator
18	0h RW	cri_dfx_clrerrcnt: Clear Error Counter Resets the Pattern Checker's error counter. 0 : Error Counter allowed to run (default) 1 : Error Counter held in reset
17	0h RW	cri_dfx_lcereset: Local Compare Engine Reset Resets all components of the Local Compare Engine in both the Pattern Generator and the Pattern Checker. 0 : LCE not in reset (default) 1 : LCE in reset
16	0h RW	cri_dfx_lcestart: Local Compare Engine Start Controls the starting and stopping of the LCE. Allows for simultaneous or independent start across lanes. Once stopped, a DFXLCERESET is usually required. 0 : LCE stopped (default) 1 : LCE running
15:8	3Eh RW	cri_dfx_patbuf_7_0: Pattern Buffer Storage In 10b mode, the buffer is read as eight 10b chunks. The first 10 bits should not equal the Comma Symbol: '0011111010' (or its inversion '1100000101'). In 8b mode, the buffer is read as eight 10b chunks, where the 10th bit is unused and the 9th bit is the K-bit indicator. The first 10 bits should not equal the Comma Symbol: 'xx10111100'. DFXPATBUF[78] should not be '1'.
7:0	63h RW	cri_dfx_patbuf_15_8: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.



23.11.7 PCS_DWORD6 (pcs_dword6)—Offset 18h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword6: [Port: 0xA6] + (600h + 18h)

Op Codes:

0h - Read, 1h - Write

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
cri_dfx_prbseed_7_0								cri_dfx_prbseed_31_24

Bit Range	Default & Access	Description
31:24	FFh RW	cri_dfx_prbseed_7_0: PRBS Seed Can be used for HVM determinism. The use of all zeroes can result in lockup.
23:16	FFh RW	cri_dfx_prbseed_15_8: PRBS Seed See cri_dfx_prbseed[7:0] description.
15:8	FFh RW	cri_dfx_prbseed_23_16: PRBS Seed See cri_dfx_prbseed[7:0] description.
7:0	FFh RW	cri_dfx_prbseed_31_24: PRBS Seed See cri_dfx_prbseed[7:0] description.

23.11.8 PCS_DWORD7 (pcs_dword7)—Offset 1Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)


pcs_dword7: [Port: 0xA6] + (600h + 1Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000009h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
dfx_cri_errcnt_7_0								cri_dfx_prbstraincnt_3_0



Bit Range	Default & Access	Description
31:24	X RO	dfx_cri_errcnt_7_0: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
23:16	X RO	dfx_cri_errcnt_15_8: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
15	X RO	i_rxcaldone: RX Calibration Cycles Complete Indicator
14	X RO	dfx_cri_lcemgnerr: Local Compare Engine Margin Error Indicates that the error counter has reached its max value. This can be used by the Rx upartition during Margin Mode to determine when the eye width has closed.
13	X RO	cri_dfx_patgen2active: Pattern Generator 2 Active status indicator In a lane with two Tx paths, this indicates that the second Pattern Generator is in progress. The DFXPATGENACTIVE will only indicate that the first Pattern Generator is in progress.
12	X RO	dfx_cri_patbufallfail: Pattern Buffer All Fail status indicator Indicates that there has not been a single matching Pattern Buffer pattern. This could signify that an error occurred during training.
11	X RO	dfx_cri_patchkactive: Pattern Checker Active status indicator Indicates that the Pattern Checker is in progress (either Pattern Buffer or PRBS).
10	X RO	dfx_cri_patgenactive: Pattern Generator Active status indicator Indicates that the Pattern Generator is in progress (either Pattern Buffer or PRBS).
9	X RO	dfx_cri_lctraindone: Local Compare Engine Training Done status indicator Indicates that the Pattern Checker training is completed (either Pattern Buffer or PRBS). The Pattern Checker is now synchronized to the Pattern Generator.
8	X RO	dfx_cri_lctrainactive: Local Compare Engine Training Active status indicator Indicates that the Pattern Checker training is in progress (either Pattern Buffer or PRBS).
7	0h RW	reserved501: reserved
6	0h RW	cri_dfx_patgen2en: Pattern Generator 2 Enable In a lane with two Tx paths, this enables the second Pattern Generator. The DFXPATGENEN will enable the first Pattern Generator. 0 : Disable second Pattern Generator (default) 1 : Enable second Pattern Generator
5:4	0h RW	cri_dfx_maxerrcnt_1_0: Maximum Error Count Selectable maximum value that the DFXERRCNT can reach before the Local Compare Engine is automatically stopped. 00 : 2^{16} (default) 01 : 2^{10} 10 : 2^8 11 : 2^4
3:0	9h RW	cri_dfx_prbstraincnt_3_0: PRBS Training Count The number of consecutive cycles that the Pattern Checker's PRBS must be error free before it is considered synchronized. Default is 9.

23.11.9 PCS_DWORD8 (pcs_dword8)—Offset 20h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword8: [Port: 0xA6] + (600h + 20h)

Op Codes:

0h - Read, 1h - Write

Default: 000000C4h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reg_partial	reg_slumber	reg_tx2_cdr_override_2_0	reg_cdr_override_2_0	reg_ebuffmode	reg_usedclockchannel_1_0	reg_usedclockchannel_ovrride	reg_gbl_ovrride	reg_tx1_pclkon_inp2
								reg_tx2_pclkon_inp2
								reg_tx2_txenable
								cri_rxeb_ptr_init_3_0
								reg_powerfsm_ovrride
								reg_suspend
								reg_pclkcfginput
								reg_useqclock
								cri_rxeb_hiwater_3_0
								cri_rxeb_lowater_3_0

Bit Range	Default & Access	Description
31	0h RW	reg_partial: Override for i_partial
30	0h RW	reg_slumber: Override for i_slumber
29:27	0h RW	reg_tx2_cdr_override_2_0: Override for cdr_override strap for second tx2
26:24	0h RW	reg_cdr_override_2_0: Override for cdr_override strap
23	0h RW	reg_ebuffmode: Override for ebuffmode (no functionality in p1271 phase1 design)
22:21	0h RW	reg_usedclockchannel_1_0: Selects the active clock channel
20	0h RW	reg_usedclockchannel_ovrride: When asserted selects reg_usedclockchannel[1:0]
19	0h RW	reg_gbl_ovrride: Global override select
18	0h RW	reg_tx1_pclkon_inp2: When asserted keeps PCLK running in P2 mode. For DP this is used for Lane1
17	0h RW	reg_tx2_pclkon_inp2: When asserted keeps PCLK running in P2 mode. This is reserved (no impact) for PCIe/DMI and used for DP Lane2
16	0h RW	reg_tx2_txenable: Override for i_txenable for tx2
15:12	0h RW	cri_rxeb_ptr_init_3_0: Config override for initial value of Rx elastic buffer read pointer
11	0h RW	reg_powerfsm_ovrride: When asserted overrides for Tx power fsm are selected
10	0h RW	reg_suspend: Override for suspend
9	0h RW	reg_pclkcfginput: Override for pclkcfginput strap
8	0h RW	reg_useqclock: Override for useqclock; MUX select for I or Q clk for TX clocking
7:4	Ch RW	cri_rxeb_hiwater_3_0: Elastic buffer high watermark based on which SKP is removed

23.11.10 PCS_DWORD9 (pcs_dword9)—Offset 24h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs dword9: [Port: 0xA6] + (600h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31	0h RW	reserved502: reserved
30:26	0h RW	reg_strapgroup_4_0: Override for i_strapgroup
25:24	0h RW	reg_powerdown_1_0: Override for i_powerdown
23	0h RW	reg_pcs_txcmnkeepdisable_ovrd: Override for ipcs_txcmnkeepdisable input 0: Use value on ipcs_txcmnkeepdisable input pin to determine o_txgohighz state in P2/ slumber 1: Force pcs_txcmnkeepdisable to 0
22:18	0h RW	reg_straplane_5_0: Override for i_straplane
17	0h RW	reg_tx1_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx1 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
16	0h RW	reg_tx2_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx2 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
15	0h RW	reg_txdatavalid: Override for i_txdatavalid (register is NOT used)
14:13	0h RW	reg_txdeemp_1_0: Override for i_txdeemp



Bit Range	Default & Access	Description
12:10	0h RW	reg_txmargin_2_0: Override for i_txmargin
9	0h RW	reg_txswing: Override for i_txswing
8	0h RW	reg_txenable: Override for i_txenable
7:6	0h RW	reg_txterm_vcc_1_0: Override for txterm_vcc strap
5	0h RW	reg_txdetrxlpbk: Override for i_txdetrxlpbk
4	0h RW	reg_txelectidle: Override for i_txelectidle
3	0h RW	reg_txcompliance: Override for i_txcompliance
2	0h RW	reg_txoneszeroes: Override for i_txoneszeroes
1:0	0h RW	reg_latencyoptim_1_0: Override for i_latencyoptim

23.11.11 PCS_DWORD10 (pcs_dword10)—Offset 28h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword10: [Port: 0xA6] + (600h + 28h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_timer_WAIT_RX_PT_CLK_3_0	reg_rxpwrfsm_timer_ENABLE_RX_3_0	reg_rxpwrfsm_timer_RX_SEQEN_3_0	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0		reg_clk_valid_cnt_7_0	reg_rxterm	reg_rxpolarity	reg_rxeqtrain
						reg_rxsquelchen	cri_rxpwrfsm_sgentimer_ovrden	reg_rxintfren_override
							reg_rxintfren_l	reg_clk_valid_cnt_ovrd



Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PI_CLK_3_0: Rx Power state m/c timer value used to enable PI clock
27:24	0h RW	reg_rxpwrfsm_timer_ENABLE_RX_3_0: Rx Power state m/c timer value used to enable receivers
23:20	0h RW	reg_rxpwrfsm_timer_RX_SQEN_3_0: Rx Power FSM Rx Squelch Enable Timer Override Value Affect squelch enable startup sequence during 'synchronous' squelch startup mode. 0000 - Invalid 0001 - 1 susclk period ... 1111 - 15 susclk period
19:16	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0: Rx Power state m/c timer value used to enable PI BIAS
15:8	0h RW	reg_clk_valid_cnt_7_0: Over ride value for clock valid delay in clock top block before toggling phystatus.
7	0h RW	reg_rxterm: Override for i_rxterm
6	0h RW	reg_rxpolarity: Override for i_rxpolarity
5	0h RW	reg_rxeqtrain: Override for i_rxeqtrain
4	0h RW	reg_rxsquelchen: Override for i_rxsquelchen
3	0h RW	cri_rxpwrfsm_sqentimer_ovrden: Squelch Enable Timer Override Enable Used to override the squelch enable timer in PCS with the timer value set by the Rx Squelch Enable timer register (reg_rxpwrfsm_timer_RX_SQEN[3:0]).
2	0h RW	reg_rxintfltren_override: Rx Integral Filter Override Select 0: selects i_rxintfltren_l input pin. 1: selects reg_rxintfltren_l register
1	0h RW	reg_rxintfltren_l: Override for Rx integral filter enable i_rxintfltren_l
0	0h RW	reg_clk_valid_cnt_ovrd: Override enable for reg_clk_valid_cnt

23.11.12 PCS_DWORD11 (pcs_dword11)—Offset 2Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword11: [Port: 0xA6] + (600h + 2Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0F000000h



31	28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
0	0	0	0	1	1	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:30	0h RW	reserved505: reserved
29	0h RW	reserved506: reserved
28:24	Fh RW	reg_tx2_stagger_mask_4_0: Mask bit for lane number. Used to group lanes for staggering. for tx2
23	0h RW	i_clkbuf_iclken_ovrd: I-Clock Override for the DataLane
22	0h RW	i_clkbuf_qclken_ovrd: Q-Clock Override for the DataLane
21	0h RW	reserved503: reserved
20	0h RW	i_clkbuf_txclkmuxen_ovrd: TX Clock Selection Mux Override
19	0h RW	reserved504: reserved
18	0h RW	reg_tx2_cmmdisparity: Sets the initial disparity during Compliance Measurement Mode, used together with pcs_txcompliance pulse. For TX2 0 = set negative disparity 1 = set positive disparity
17	0h RW	reg_tx1_ctrl_override: overrides input parameter/controls for tx1
16	0h RW	reg_tx2_ctrl_override: overrides input parameter/controls for tx2
15	0h RW	reg_tx2_txterm_vcc_1: Override for txterm_vcc strap[1] for tx2 in DP family. Override enable for inspecmm for non-DP families (reg_inspecmm_ovrd_enable).
14	0h RW	reg_tx2_txterm_vcc_0: Override for txterm_vcc strap[0] for tx2 in DP family. Override value for inspecmm for non-DP families (reg_inspecmm_ovrd_value).
13	0h RW	reg_tx2_txdetrxlpbk: Override for i_txdetrxlpbk for tx2



Access Method

pcs_dword12: [Port: 0xA6] + (600h + 30h)

0h - Read, 1h - Write

31	28				24				20				16				12				8				4				0																																																																		
0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	0	0	0	0	0	1	1	1	1	0	0	0	0	0	0	0	0																																																																
reg_tx fsm_200ns_ovrd								reg_loadgen2txen_fall_ovrd								reg_tx2_stagger_mult_2_0								reg_lanestagger_by_group								reg_tx1_stagger_mult_2_0								reserved509								reserved510								reg_tx1_stagger_mask_4_0								reserved507				reg_lanestagger_strap_ovrd								reserved508								reg_lanestagger_strap_4_0											



Bit Range	Default & Access	Description
31	0h RW	reg_tx fsm_200ns_ovrd: Override reg_tx fsm_200ns_delay+G2
30:24	0h RW	reg_tx fsm_200ns_delay_6_0: Override value of counter for 200ns delay between txen and txloadgenen
23	0h RW	reg_loadgen2txen_fall_ovrd: reserved
22:20	2h RW	reg_tx2_stagger_mult_2_0: Stagger multiplier for Rx (or Tx1) (Same decoding as tx1_stagger_mult[2:0]) For Display, this multiplier applies to Tx2. For non-Display PHYs, this multiplier applies to the Rx. The multiplier limit for the Rx is 8x (3'b100); anything beyond that is invalid.
19	0h RW	reg_lanestagger_by_group: When = 1, uses group number for lane staggering, by devalues lane number is used.
18:16	5h RW	reg_tx1_stagger_mult_2_0: Stagger multiplier for Tx (or Tx1) These bits set the lane staggering multiplier for the transmitter based on the 'linkclk' period. 000 - 0x 001 - 1x 010 - 2x 011 - 4x 100 - 8x 101 - 16x 110 - 32x 111 - 64x For Display, this multiplier applies to Tx1.
15:14	0h RW	reserved509: reserved
13	0h RW	reserved510: reserved
12:8	Fh RW	reg_tx1_stagger_mask_4_0: Mask bit for lane number. Used to group lanes for staggering
7	0h RW	reserved507: reserved
6	0h RW	reg_lanestagger_strap_ovrd: When 1 config override for lane stagger strap (bits [4:0] of this register) is selected
5	0h RW	reserved508: reserved
4:0	0h RW	reg_lanestagger_strap_4_0: Override for lane stagger strap

23.11.14 PCS_DWORD13 (pcs_dword13)—Offset 34h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword13: [Port: 0xA6] + (600h + 34h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
visa_en				reserved512				visa_clk_sel1_4_0				visa_lane_sel1_7_0				visa_bypass				reserved511				visa_clk_sel0_4_0				visa_lane_sel0_7_0							



Access Method

pcs_dword14: [Port: 0xA6] + (600h + 38h)

Op Codes:

0h - Read, 1h - Write

Default: 007A0018h

Bit Range	Default & Access	Description
31	0h RW	reg_clkbuf_stagger_ovrd: Override enable for reg_clkbuf_stagger_cnt
30	0h RW	reg_clkbuf_stagger_cnt_10: Counter override value for staggering delay of clock buffer control signals.



Bit Range	Default & Access	Description
29	0h RW	reg_slowclk_ovrden: Slow Clock Override Enable When set 1'b1, reg_slowclocken and reg_sclk250en are valid. When cleared 1'b0, output of FSM will drive slow clock enable.
28:24	0h RW	reg_txloadgenen2txen_fall_delay_4_0: reserved
23:20	7h RW	o_cmlmuxsthsel_3_0: CML Mux strength control
19:16	Ah RW	o_cmlsthsel_3_0: RX CML driver strength
15:12	0h RW	o_pcisel_3_0: I clk phase correction control
11:8	0h RW	o_pcqsel_3_0: Q clk phase correction control
7	0h RW	o_phaseicen: Iclk phase correction enable.
6	0h RW	o_phaseqcen: Qclk phase correction enabled.
5	0h RW	o_pcbypass: Phase correction bypass.
4	1h RW	o_slowclocken: Slow clock 1 enable Only valid if slow clock override enable is set 1'b1
3	1h RW	o_sclk250en: Slow clock 2 enable Only valid if slow clock override enable is set 1'b1
2:0	0h RW	cri_kalign_com_cnt: Upper 3 bits of a 7-bit counter that counts number of COM characters found. Used for special SAPIS mode where spread spectrum clocking can be utilized. Note: This register is used in conjunction with another PCS register cri_kalignmode[1:0] = 10 Register value Minimum COM count to achieve symbol lock 000 - 18 001 - 34 010 - 50 011 - 66 100 - 82 101 - 98 110 - 114 111 - 130

23.11.16 PCS_DWORD15 (pcs_dword15)—Offset 3Ch

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword15: [Port: 0xA6] + (600h + 3Ch)


Op Codes:

0h - Read, 1h - Write

Default: 04100300h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
13:8	3h RW	reserved513: reserved
7:0	0h RW	reg_clkbuf_stagger_cnt_9_2: Counter override value for staggering delay of clock buffer control signals.

23.11.17 PCS_DWORD16 (pcs_dword16)—Offset 40h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword16: [Port: 0xA6] + (600h + 40h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h

31	28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																													
0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31	0h RW	sqelch_shunt_ovrd_en: Squelch Shunt Pulse Duration Override Enable Overrides the hardware default shunt pulse duration value 1: Shunt Pulse Duration Override Enable 0: Shunt Pulse Duration Override Disable
30:28	0h RW	sqelch_shunt_cnt_2_0: Squelch Shunt Pulse Duration Override Value 000 = No shunt pulse generated 001 = 1 susclk cycles ... 111 = 7 susclk cycles
27	0h RW	reserved520: reserved
26	0h RW	i_rxsqfsm_timersel: Squelch FSM Timer Select 0 - Selects 25Mhz values for squelch timer and shunt pulse generation . 1 - Selects 100Mhz values for squelch timer and shunt pulse generation. This register is applicable to synchronous squelch startup mode.
25	0h RW	i_rxsq_asyncmode_h: Squelch Async Startup Mode This squelch startup mode is power state independent. When enabled, the squelchen signal sent to Modphy will asynchronously enable the squelch detector circuit. Once enabled, the squelch detector circuit will asynchronously send an unfiltered/unqualified squelch indication signal out of Modphy. The squelch indication signal will initially be unstable, so it is up to the consumer of this signal to filter/qualify it accordingly. The asynchronous squelch startup mode is beneficial because it significantly reduces the squelch startup latency. This decrease in latency does come at the cost of slightly higher power when squelch is not enabled as the IREF and Squelch Keeper circuits must remain enabled. When disabled, the squelch startup sequence is synchronous in nature and the squelch indication signal sent out of Modphy is stable/filtered.
24	1h RW	i_rxsquelchstby_h: Fast Squelch Enable Mode Bit to keep the IREF (ivrefen) on during P2 and reduce squelch startup time.



Bit Range	Default & Access	Description
23:18	0h RW	reserved519: reserved
17:16	0h RW	cri_dfx_evenoddmask_1_0: Pattern Checker Even/Odd Bit Error Mask Select 00 : no masking; all errors will be counted 01: select odd path, mask even path; only errors on bits [1,3,5,7,9] are counted 10: select even path, mask odd path; only errors on bits [0,2,4,6,8] are counted 11: reserved;
15:12	0h RW	reserved518: reserved
11:10	0h RW	cri_dfx_lce2patsrc_1_0: Local Compare Engine 2 Pattern Source In a lane with two Tx paths, this selects between using Pattern Buffer or PRBS as source of LCE patterns for the second LCE. The DFXLCEPATSR selects for the first LCE. 0 : Pattern Buffer (default) 1 : PRBS
9:8	0h RW	cri_dfx_lcepatsrc_1_0: Local Compare Engine Pattern Source. Selects between using Pattern Buffer or PRBS as source of LCE patterns. 00 : Pattern Buffer; use LCE default training pattern; 01: Pattern Buffer; use the first 40b of pattern buffer for training. 10: PRBS; use LCE default training pattern; 11: PRBS; use the first 40b of pattern buffer for training.
7:6	0h RW	reserved517: reserved
5:4	0h RW	txloadgen_ctr_val: TxLoadGen Pulse Width Control Controls the pulse width of txloadgenen from PCS to Tx upar. This is used in MAC initiated digital far end loopback mode in PCIE family. 00 - txloadgenen pulse width is 4 symbol clocks (default) 01- txloadgenen pulse width is 2 symbol clocks 10 - txloadgenen pulse not generated 11 - txloadgenen pulse width is 6 symbol clocks
3	0h RW	cri_txhighpowerei_ovrden: TxHighPowerEI Override Mode Enable 0 - TxHighPowerEI to TxuPAR driven by Logic 1 - TxHighPowerEI to TxuPAR driven by override register value(s).
2	0h RW	cri_tx1highpowerei_ovrdval: Tx1HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx1HighPowerEI disabled 1 - Tx1HighPowerEI enabled
1	0h RW	cri_tx2highpowerei_ovrdval: Tx2HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx2HighPowerEI disabled 1 - Tx2HighPowerEI enabled
0	1h RW	p2_fast_exit_en: P2 Fast Exit Mode Enable Common Mode sustainer will be enabled during P2 when this bit is asserted. 1: P2 Fast Exit Mode Enable 0: P2 Fast Exit Mode Disable

23.11.18 PCS_DWORD17 (pcs_dword17)—Offset 44h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword17: [Port: 0xA6] + (600h + 44h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h



31				28				24				20				16				12				8				4				0																																																																			
0 0 0 0				0 0 0 0				0 0 0 1				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 1																																																																			
oiredfxsel_1_0				iopampsfpen_h				iopampsfnen_h				iopamppen_h				iopampnen_h				monanapgen				monubufbypassen				reserved522				reg_ivrefen				ivrefen_ovrd				reserved523				oirefcurmonsel				lrcdisable				reserved521				lrc_rdy_pulsegen				lrc_rdy_target_1_0				lrc_rdy_ovd				rxtermprccen				rxvgaprrccen				txpmrrccen				irefpmrrccen				rxtermprccen				rxvgaprrccen				txpmrrccen				irefpmrrccen			

Bit Range	Default & Access	Description
31:30	0h RW	oiredfxsel_1_0: IREF Voltage Monitor Select Selects voltage to monitor within the IREF block. 00 - vref 01 - pgate 10 - vbc 11 - vref loop
29	0h RW	iopampsfpen_h: (NOT USED - noconned)
28	0h RW	iopampsfnen_h: (NOT USED - noconned)
27	0h RW	iopamppen_h: DC Monitor Unity-Gain Buffer Enable 0: disable (default) 1: enable
26	0h RW	iopampnen_h: (NOT USED - noconned)
25	0h RW	monanapgen: DC Monitor to Monitor Port Enable Enables DC monitor passgate to monitor port via analog observability abutment.
24	1h RW	monubufbypassen: DC Monitor Unity-Gain Buffer Bypass 0: no bypass 1: bypass (default - required for LRC)
23:22	0h RW	reserved522: reserved
21	0h RW	reg_ivrefen: IvrefEn Override Value Register is valid when override mode is enabled (ivrefen_ovrd). During this mode, this register will have direct control to enable/disable the ivref opamp. 0 - Disable ivref opamp 1 - Enable ivref opamp
20	0h RW	ivrefen_ovrd: IvrefEn Override Select 0 - the enable for the ivref opamp (ivrefen) is driven by the FSM. 1 - the ivrefen is driven by the register (reg_ivrefen).
19:17	0h RW	reserved523: reserved
16	0h RW	oirefcurmonsel: IREF Current Monitor Select Enables current mirror from the IREF block to the 'shared' analog monitor port.
15	0h RW	lrcdisable: LRC Disable This bit disables the LRC. Any token received is passed to the next lane.
14:12	0h RW	reserved521: reserved
11	0h RW	lrc_rdy_pulsegen: LRC Ready PulseGen Generates a pulse 1 cal_clk cycle wide on the lrc_rdy signal to all four targets; does not recompute local Rcomp code. Values in DWD 0x14 (*rccodes[7:0]) will be latched into targets. User must clear this bit before generating another pulse. Note: User should disable PM and PER. FSM can take control and codes can be overridden.
10:9	0h RW	lrc_rdy_target_1_0: LRC Ready Pulse Target Indicates which lrc target to recompute when lrc_rdy_ovd is strobed 00: irefrrccode 01: txrrccode 10: rxtermrrccode 11: rxvgarrrccode

23.11.19 PCS_DWORD18 (pcs_dword18)—Offset 48h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword18: [Port: 0xA6] + (600h + 48h)

Op Codes:

0h - Read, 1h - Write

Default: 00008080h

31				28				24				20				16				12				8				4				0			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				1 0 0 0				0 0 0 0				1 0 0 0				0 0 0 0							
reserved524				reg_lrc_calcsonly				adcout_9_8				adcout_7_0								adc2_9_2								adc1_9_2							



Access Method

pcs_dword20: [Port: 0xA6] + (600h + 50h)

0h - Read, 1h - Write

[illegible]



23.11.23 PCS_DWORD22 (pcs_dword22)—Offset 58h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword22: [Port: 0xA6] + (600h + 58h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	
rxvgaroffset_7_0				rxtermrcoffset_7_0				txrcoffset_7_0	

Bit Range	Default & Access	Description
31:24	0h RW	rxvgaroffset_7_0: Rx VGA Rcomp Offset Same description as IREF Rcomp Offset, but applies to RxVGA Rcomp.
23:16	0h RW	rxtermrcoffset_7_0: Rx Termination Rcomp Offset Same description as IREF Rcomp Offset, but applies to RxTerm Rcomp.
15:8	0h RW	txrcoffset_7_0: Tx Rcomp Offset Same description as IREF Rcomp Offset, but applies to Tx Rcomp.
7:0	0h RW	irefrcoffset_7_0: Iref Rcomp Offset This value is added to the scaled LRC code to determine the final calibration code used by the Iref block. 2's complement format. The full 8-bit offset is used with the scale multiplier to determine the final 8-bit value, but the Iref target only uses the upper MSBs of the final value. 0x00: Offset = 0 0x01: Offset = +1 0x7F: Offset = +127 0xFF: Offset = -1 0x80: Offset = -128 Note: The final rcomp code has rollover protection so the final rcomp code + offset will not exceed the min/max range.

23.11.24 PCS_DWORD23 (pcs_dword23)—Offset 5Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword23: [Port: 0xA6] + (600h + 5Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00180888h

31				28				24				20				16				12				8				4				0											
0				0				0				0				1				1				0				0				0				0				0			
iclkcqcf_spare_7_0								iclkcif_spare_7				iclkcif_spare_6_3				iclkcif_spare_2_0				reserved526				i_drvcfg_3_0				i_plloadcfg_3_0				ipbiasctrl_3_0											



Bit Range	Default & Access	Description
16	1h RW	cri_lanereset_clkgatectl: 1: The assertion of lane reset will have the effect of gating the susclk and de-asserting the internal laneclkreq. This mode is only valid when the data lane dynamic clock gating mode is set to a non-zero value (i.e. 01, 10, and 11). 0: The assertion of lane reset will have no effect on the gating of susclk and state of the internal laneclkreq signal.
15	1h RW	cri_lanereqforce: Controls whether the internal laneclkreq will be forced to 1 or 0 when cfg_data_dynclkgate_mode is set to 00 or 10. 1: force laneclkreq high 0: force laneclkreq low. This mode will likely be used when one of the lanes is disabled while other lanes in the family are enabled. In this case the internal laneclkreq of the disabled lane should be de-asserted (not influencing the clk gating decision)
14:10	10h RW	cri_susclkdisable_delay_4_0: This register will control the number of cycles to delay the susclk enable de-assertion, in addition to the de-assertion of the laneclkreq signal sent out of the data lane. The susclk enable must be continuously de-asserted for the duration of this delay in order for the de-asserted state to be captured by the clock gating controller. 5'b00000 - 0 Cycle Delay 5'b00001 - 1 Cycle Delay 5'b00010 - 2 Cycle Delay 5'b11110 - 30 Cycle Delay 5'b11111 - 31 Cycle Delay
9:8	0h RW	cri_data_dynclkgate_mode_1_0: Controls the dynamic clock gating behavior in the data lane. 00 - susclk gating and laneclkreq disabled (Forced to configured value). In this mode the susclk will not be gated under any circumstances and the laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 01 - susclk gating disabled, laneclkreq enabled . In this mode the susclk will not be gated under any circumstances. The laneclkreq sent out of the data lane will toggle based on whether the lane power state, susclk need and the previous lane's laneclkreq signal. 10 - susclk gating enabled, laneclkreq disabled (forced to configured value) - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 11 - susclk gating and laneclkreq enabled - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the data lane will toggle based on the lane power state, susclk need and the previous lane's laneclkreq signal.
7	0h RW	cri_eios_waittime_ovren: EIOS Wait Time Override Enable for Rx Turn OFF 0: hardware value for EIOS wait timer is selected. 1: selects cri_eios_waittime[6:0]
6:0	20h RW	cri_eios_waittime_6_0: EIOS Wait Time for Rx Turn OFF Represents override value timer in PCS that comes into play during EIOS based turn off Rx (Rx L0s) 0000000 - Timer is bypassed 0000001 - 1 PLL link clock period delay (2ns) 0000010 - 2 PLL link clock period delay (4ns) ... 0100000 - 32 PLL link clock periods delay (64ns) - default



23.12 PCI Express* Lane 2 Electrical Address Map

Table 249. Summary of PCI Express* Lane 2 Electrical Message Bus Registers—0xA6 (Global Offset 680h)

Offset	Register ID—Description	Default Value
0h	"TX_DWORD0 (tx_dword0)—Offset 0h" on page 3367	2600003Ah
4h	"TX_DWORD1 (tx_dword1)—Offset 4h" on page 3368	20000000h
8h	"TX_DWORD2 (tx_dword2)—Offset 8h" on page 3369	5580983Ah
Ch	"TX_DWORD3 (tx_dword3)—Offset Ch" on page 3369	0C782040h
10h	"TX_DWORD4 (tx_dword4)—Offset 10h" on page 3371	2B404D55h
14h	"TX_DWORD5 (tx_dword5)—Offset 14h" on page 3371	00000000h
18h	"TX_DWORD6 (tx_dword6)—Offset 18h" on page 3372	1F200000h
1Ch	"TX_DWORD7 (tx_dword7)—Offset 1Ch" on page 3373	0038383Fh
20h	"TX_DWORD8 (tx_dword8)—Offset 20h" on page 3374	0600AA80h
24h	"TX_DWORD9 (tx_dword9)—Offset 24h" on page 3374	00430C06h
28h	"TX_DWORD10 (tx_dword10)—Offset 28h" on page 3375	00000000h
2Ch	"TX_DWORD11 (tx_dword11)—Offset 2Ch" on page 3376	00001000h
30h	"TX_DWORD12 (tx_dword12)—Offset 30h" on page 3378	00000000h
34h	"TX_DWORD13 (tx_dword13)—Offset 34h" on page 3379	00000000h
38h	"TX_DWORD14 (tx_dword14)—Offset 38h" on page 3380	00400000h
3Ch	"TX_DWORD15 (tx_dword15)—Offset 3Ch" on page 3381	00000000h
40h	"TX_DWORD16 (tx_dword16)—Offset 40h" on page 3382	00008A00h

23.12.1 TX_DWORD0 (tx_dword0)—Offset 0h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword0: [Port: 0xA6] + (680h + 0h)

Op Codes:

0h - Read, 1h - Write

Default: 2600003Ah

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
0				0				1				0				0				1				1				0				0				0				0				0				0				1				1				1				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0			

Bit Range	Default & Access	Description
31	0h RO	reserved504: reserved



Access Method

tx_dword1: [Port: 0xA6] + (680h + 4h)

Op Codes:

0h - Read, 1h - Write

Default: 20000000h

Bit Range	Default & Access	Description
31:30	0h RO	reserved510: reserved
29:24	20h RW	ofrcr2short3_5_0: number of slices in R2 for swing 3 (DE) MSB has no effect.
23:22	0h RO	reserved509: reserved
21:16	0h RO	reserved508: reserved
15:14	0h RO	reserved507: reserved
13:8	0h RO	reserved506: reserved



Bit Range	Default & Access	Description
7:6	0h RO	reserved505: reserved
5:0	0h RW	ofrcr2short0_5_0: number of slices in R2 for swing 0 (FS) MSB has no effect.

23.12.3 TX_DWORD2 (tx_dword2)—Offset 8h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword2: [Port: 0xA6] + (680h + 8h)

Op Codes:

0h - Read, 1h - Write

Default: 5580983Ah

31	28	24	20	16	12	8	4	0
0	1	0	1	0	1	1	0	0
0	1	0	1	1	0	0	0	1
0	1	0	1	1	0	0	0	1
omargin010_7_0	omargin000_7_0	ouniqtranscale_7_0	reserved511	ofrcslices_6_0				

Bit Range	Default & Access	Description
31:24	55h RW	omargin010_7_0: factor (X/128) of slices to use in main-R1 for full swing level. Used for ~2/3Vp2p
23:16	80h RW	omargin000_7_0: factor (X/128) of slices to use in main-R1 for full swing level. Used for ~1V p2p. To be used in Gen2 mode (Gen1/Gen2 depend on dataratefit and downscaleamp register)
15:8	98h RW	ouniqtranscale_7_0: scales the number of slices defined the ref circuit (or R-comp circuit) by factor of ouniqtranscale[7:0]/128 The scaled amount of slices might be used in the full-swing Uis according to ouniqtrangenmethod[1:0] The scaled amount of slices might be used in the full-swing Uis according to oscaledcompmethod[1:0]
7	0h RO	reserved511: reserved
6:0	3Ah RW	ofrcslices_6_0: number of used slices if forced Used in compensated GPIO mode

23.12.4 TX_DWORD3 (tx_dword3)—Offset Ch

Access Method


Type: Message Bus Register
(Size: 32 bits)

tx_dword3: [Port: 0xA6] + (680h + Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0C782040h



October 2018
Document Number: 538136, Rev. 4.3



Access Method

tx dword6: [Port: 0xA6] + (680h + 18h)

Op Codes:

0h - Read, 1h - Write

Default: 1F200000h

Bit Range	Default & Access	Description
31	0h RO	reserved520: reserved
30:24	1Fh RW	onswbypass_6_0: Determines # of slices activated in N-drv when in strong pulling to CM (after Rx-dtct/ gohighz / stongPD) same slices cannot be opened for P-drv and for N-drv. Determines # of slices for P-drv in All1/All0 DFTs when bybbycomp is not asserted. In these DFT modes pswpass can be set to the same value as nswbypass
23	0h RO	reserved519: reserved
22:16	20h RW	opswbypass_6_0: Determines # of slices activated in P-drv when in strong pulling to CM (after Rx-dtct/ gohighz / stongPD) Determines # of slices for P-drv in All1/All0 DFTs when bybbycomp is not asserted.
15	0h RO	reserved518: reserved
14:8	0h RO	reserved517: reserved
7	0h RW	ocalccont: initiate calculation of swing-control circuit. While this signal is '1' the calculation is being done consecutively



23.12.9 TX_DWORD8 (tx_dword8)—Offset 20h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword8: [Port: 0xA6] + (680h + 20h)

Op Codes:

0h - Read, 1h - Write

Default: 0600AA80h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ontlptime_7_0	ofrcdccoup_1_0	obybbycomp	obypdftmode_4_0	odftpisodata1_7_0	odftpisodata0_1_0	reserved529	reserved528	

Bit Range	Default & Access	Description
31:24	6h RW	ontlptime_7_0: [after step 1 of pullup] time (ick_susslow cycles) to wait (step 2) and let the pads leak downwards before comparing pads to Vref to determine if the pad exceeded Vref as a result of leakage.
23:22	0h RW	ofrcdccoup_1_0: 00
21	0h RW	obybbycomp: 0' the amount of slices used in dftbypmode is by 'nswbypass', 'pswbypass' and 'r2bypass' registers '1' the amount of slices used is by 'slices' from swing-control block. Number of slices in R2 in EI - is also affected by this bit
20:16	0h RW	obypdftmode_4_0: selects the DFT mode. 5'h00 - DFT_OFF 5'h01 - DFTHIZ 5'h02 - DFTEI 5'h03 - DFTFELB 5'h04 - DFTALL1DIF 5'h05 - DFTALL0DIF 5'h06 - DFTALL1SE 5'h07 - DFTALL0SE 5'h08 - DFTDAC 5'h09 - DFTFRCBEAC 5'h0a - DFTOBS 5'h0c - DFT ASYNC MODE OFF 5'h0d - DFT ASYNC MODE Tx (output) 5'h0e - DFT ASYNC MODE Rx (input) 5'h0f - DFT ASYNC MODE Both (inout) 5'h10 - DFTPIISOLOAD 5'h12 - DFTEISTRNG
15:8	AAh RW	odftpisodata1_7_0: 8 MSB of alternative data input to PISO Load of this data is enabled when bypdftmode=DFTPIISOLOAD
7:6	2h RW	odftpisodata0_1_0: 2 LSB of alternative data input to PISO Load of this data is enabled when bypdftmode=DFTPIISOLOAD
5:3	0h RO	reserved529: reserved
2:0	0h RO	reserved528: reserved

23.12.10 TX_DWORD9 (tx_dword9)—Offset 24h

Access Method


Type: Message Bus Register
(Size: 32 bits)

tx_dword9: [Port: 0xA6] + (680h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00430C06h




23.12.11 TX_DWORD10 (tx_dword10)—Offset 28h

Type: Message Bus Register
(Size: 32 bits)

Op Codes:

Intel Atom® Processor E3800 Product Family
Datasheet
3375



23.12.12 TX_DWORD11 (tx_dword11)—Offset 2Ch

Access Method


Type: Message Bus Register
(Size: 32 bits)

tx_dword11: [Port: 0xA6] + (680h + 2Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00001000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
oselsparetxclkkin_2_0	ofrcdotprocess_2_0	ofrcgohighzdis	ofrcgohighzen	ofrcstrongpddis	ofrcstrongpden	ofrcctxclkrootdis	ofrcctxclkrooten	reserved537
				ofrcpwrmodel1	ofrcpwrmodel0s	ofrcpwrmodel0	ofrcmkeepadnen	ofrcmkeepadpen
							ofrcmkeepadndis	ofrcmkeepadpdis
							omakedeeperfifo	ofrlatencyoptim_2_0
							reserved536	ofrcrvtcten
							ofrcrvtctrate_1_0	reserved535
								reserved534
								reserved533
								oneloopbacken

Bit Range	Default & Access	Description
31:29	0h RW	oselsparetxclkkin_2_0: Selects data to be used as alternative to fast clock. 000: DAC clock if in DAC mode - Default. 001: cri100m clock 010: i_obsontx_psg 011: i_obsontx_nsg 100: ick_txsymbolck 101: icksusslow 110: ick_dac 111: spare
28:26	0h RW	ofrcdotprocess_2_0: forces the dotprocess information 0XX - information of dot process comes from i_dotprocess[1:0] input bus. 100: p1271 dot1 101: p1271 dot4 110: p1271 dot8 111: NA
25	0h RW	ofrcgohighzdis: forces disabling of high-z output
24	0h RW	ofrcgohighzen: forces enabling of high-z output
23	0h RW	ofrcstrongpddis: forces disabling of strong pull-down
22	0h RW	ofrcstrongpden: forces enabling of strong pull-down
21	0h RW	ofrcctxclkrootdis: forces disable of tx-clock output.
20	0h RW	ofrcctxclkrooten: forces tx-clock to operate and drive clock out.
19	0h RO	reserved537: reserved
18	0h RW	ofrcpwrmodel1: when aserted. Forces L1 state
17	0h RW	ofrcpwrmodel0s: when aserted. Forces L0s state
16	0h RW	ofrcpwrmodel0: when aserted. Forces L0 state
15	0h RW	ofrcmkeepadnen: Forces enabling of common-mode keeping of PadN
14	0h RW	ofrcmkeepadpen: Forces enabling of common-mode keeping of PadP
13	0h RW	ofrcmkeepadndis: Forces disabling of common-mode keeping of PadN
12	1h RW	ofrcmkeepadpdis: Forces disabling of common-mode keeping of PadP
11	0h RW	omakedeeperfifo: Make FIFO deeper by 1 symbol clock cycle. Still not implemented. Implementation costs 10 flops in symb clock domain. Implementation is required for 8bits PISO only which is in next phase of products.




Access Method

tx dword12: [Port: 0xA6] + (680h + 30h)

0h - Read, 1h - Write

31				28				24				20				16				12				8				4				0																							
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0																							
otxcclkbypsel_1_0				ofrcdataaratefit_2_0				odistxflbpin				otxcikampbypsn				otxcikampbypsp				reserved539				odfxanamuxen				odfxanamuxsel_1_0				obs_tx_gated_supply_1_0				reserved538				oobsdigselectupn_3_0				oobsdigselectupp_3_0				oobsdigselectdownn_3_0				oobsdigselectdownp_3_0			

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
29:27	0h RW	ofrcdata rate fit_2_0 : Forces TX data rate 3'b0XX - don't force a value. get it from the I/F pin 3'b100 - no divide (2UIs per clock cyc) 3'b101 - divide by 2 3'b110 - divide by 4 3'b111 - divide by 8 - used also for bypassing with other clocks
26	0h RW	odistxfelbpin : when asserted - disables the i_txfelben pin at the interface and force it 0. (needed in case the pin is asserted in KX or sata1 mode)
25	0h RW	otxcikampbypsn : 0': Normal operation '1': Enable of the passgate connected from the analog clock N to the control of the DC correction cell. The feedback OTA is disabled.
24	0h RW	otxcikampbypsp : 0': Normal operation '1': Enable of the passgate connected from the analog clock P to the control of the DC correction cell. The feedback OTA is disabled.
23	0h RO	reserved539 : reserved
22	0h RW	odfxanamuxen : Enables analog signals probing mux out. When enabled the Vref of Tx-detect-Rx circuit is observed. Note that only one lane is allowed to have the analog mux enabled to avoid collisions.
21:20	0h RW	odfxanamuxsel_1_0 : selects analog signal to be sent to analog port in common lane. This bus has no affect at all currently because there is only one analog signal for observation which is observed by odfxanamuxen
19:18	0h RW	obs_tx_gated_supply_1_0 : Monitor gated vcc supply to Tx upar
17:16	0h RO	reserved538 : reserved
15:12	0h RW	oobsdigselectupn_3_0 : selects data to be sent to observability port output 'o_obsup_nsg'. Same mapping as oobsdigselectdownn[3:0]
11:8	0h RW	oobsdigselectupp_3_0 : selects data to be sent to observability port output 'o_obsup_psg'. Same mapping as oobsdigselectdownp[3:0]
7:4	0h RW	oobsdigselectdownn_3_0 : Reserved.
3:0	0h RW	oobsdigselectdownp_3_0 : Reserved.

23.12.14 TX_DWORD13 (tx_dword13)—Offset 34h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword13: [Port: 0xA6] + (680h + 34h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved543	ir2short3_5_0	reserved542	ir2short0_5_0	reserved541	ir1main3_6_0	reserved540	ir1main0_6_0	



Bit Range	Default & Access	Description
31:30	0h RO	reserved543: reserved
29:24	X RO	ir2short3_5_0: The slices used in R2 for DE (sub-DE in 3tap FIR) (PstC=Y,C=Y,PreC=Y)
23:22	0h RO	reserved542: reserved
21:16	X RO	ir2short0_5_0: The slices used in R2 for FS (sub-FS in 3tap FIR) (PstC=Y,C=Y,PreC=X)
15	0h RO	reserved541: reserved
14:8	X RO	ir1main3_6_0: The slices used in R1 for DE (sub-DE in 3tap FIR) (PstC=Y,C=Y,PreC=Y)
7	0h RO	reserved540: reserved
6:0	X RO	ir1main0_6_0: The slices used in R1 for FS (sub-FS in 3tap FIR) (PstC=Y,C=Y,PreC=X)

23.12.15 TX_DWORD14 (tx_dword14)—Offset 38h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword14: [Port: 0xA6] + (680h + 38h)

Op Codes:

0h - Read, 1h - Write

Default: 00400000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
ospare1_1_0	osimmode	ontlmodepin2pin	ofrcdatapathdis	ofrcdatapathen	ofrcdrvbydpdis	ofrcdrvbyopen	odfttxclkcaptesten	otxdccbyps_i
			ofrcnmos32ldv_2_0	ofrcpmos32ldv_2_0	visa_en	ovisa1_clkssel_2_0	ovisa1_lanese1_3_0	ovisa_bypass
							ovisa0_clkssel_2_0	ovisa0_lanese1_3_0

Bit Range	Default & Access	Description
31:30	0h RW	ospare1_1_0: reserved
29	0h RW	osimmode: Counter threshold of receive-detect, NTL, strong-common-mode is shortened dramatically for fast simulation porpuses. (does not impose risk to circuitly but electrical spec will not met)
28	0h RW	ontlmodepin2pin: 0 - NTL procedure will be done per pad while both pads are pulled to the same rail. 1 - NTL procedure will be done per pad while the pads are pulled to opposite rails.
27	0h RW	ofrcdatapathdis: DFT feature to optionally be used with other registers



Bit Range	Default & Access	Description
26	0h RW	ofrcdatapathen : DFT feature to optionally be used with other registers
25	0h RW	ofrcdrvbydis : DFT feature to optionally be used with other registers
24	0h RW	ofrcdrvbypen : DFT feature to optionally be used with other registers
23	0h RW	odfttxclkcaptesten : Enables the finger capacitor quality check in the DCC block in Tx-clock block. The test is for shorts between the capacitor terminals.
22	1h RW	otxdccbyps_1 : Tx DCC Bypass Override Puts DCC (duty cycle correction) circuit in bypass mode 0 - clock's duty cycle is not fixed
21:19	0h RW	ofrcnmos32idv_2_0 : change the value iabut_idvpmos32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
18:16	0h RW	ofrcpmos32idv_2_0 : change the value iabut_idvpmos32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
15	0h RW	visa_en : VISA Enable for the Tx VISA logic
14:12	0h RW	ovisa1_clkssel_2_0 : VISA Clock Select for Lane1. Selects the source synchronous clock to be used for data being sent on lane1.
11:8	0h RW	ovisa1_lanesel_3_0 : VISA Lane Select for Lane1. Selects the byte of data to be sent out on lane1.
7	0h RW	ovisa_bypass : VISA Bypass. Allows for signals to be passed asynchronously through VISA block. Applies to both lane0 and lane1. 0 : Flop signals in local VISA block (default) 1 : Bypass flops in local VISA block
6:4	0h RW	ovisa0_clkssel_2_0 : VISA Clock Select for Lane0. Selects the source synchronous clock to be used for data being sent on lane0.
3:0	0h RW	ovisa0_lanesel_3_0 : VISA Lane Select for Lane0. Selects data byte to be driven out of VISA-0 byte. Can be either clocked or unclocked data

23.12.16 TX_DWORD15 (tx_dword15)—Offset 3Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword15: [Port: 0xA6] + (680h + 3Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31				28				24				20				16				12				8				4				0																											
0				0				0				0				0				0				0				0				0																											
reserved551								reserved550								reserved549								reserved548								reserved547								reserved546								reserved545								reserved544			

23.12.17 TX_DWORD16 (tx_dword16)—Offset 40h

Bit Range	Default & Access	Description
31:30	0h RO	reserved551: reserved
29:24	0h RO	reserved550: The slices used in R2 for DE (PstC=X,C=Y,PreC=Y)
23:22	0h RO	reserved549: reserved
21:16	0h RO	reserved548: The slices used in R2 for FS (PstC=X,C=Y,PreC=X)
15	0h RO	reserved547: reserved
14:8	0h RO	reserved546: The slices used in R1 for DE (PstC=X,C=Y,PreC=Y)
7	0h RO	reserved545: reserved
6:0	0h RO	reserved544: The slices used in R1 for FS (PstC=X,C=Y,PreC=X)

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx dword16: [Port: 0xA6] + (680h + 40h)

Op Codes:

0h - Read, 1h - Write

Default: 00008A00h

31				28				24				20				16				12				8				4				0							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	0	1	0	0	0	0	0	0	0	0	0	0						
reserved554								reserved553								ocurcomp0ei_2_0				reserved552				omediumcompadn_1_0				omediumcompadp_1_0				ospare3_3_0				ospare2_3_0			

Bit Range	Default & Access	Description
31:24	0h RO	reserved554: reserved
23:16	0h RO	reserved553: reserved
15:13	4h RW	ocurconp0ei_2_0: current consumed (typically) 00X - 0.0mA - not active 01X - 0.9mA 10X - 1.8mA 11X - 2.7mA
12	0h RO	reserved552: reserved



Bit Range	Default & Access	Description
11:10	2h RW	omediumcmpadn_1_0: During P0-EI pad-N will be on medium strength CM and will cause the following current consumption: 00 - 0.00mA (disable) 01 - 2.45mA 10 - 4.87mA 11 - 9.73mA
9:8	2h RW	omediumcmpadp_1_0: During P0-EI pad-P will be on medium strength CM and will cause the following current consumption: 00 - 0.00mA (disable) 01 - 2.45mA 10 - 4.87mA 11 - 9.73mA
7:4	0h RW	ospare3_3_0: 4 spare CRI register bits
3:0	0h RW	ospare2_3_0: 4 spare CRI register bits



23.13 PCI Express* Lane 3 Electrical Address Map

Table 250. Summary of PCI Express* Lane 3 Electrical Message Bus Registers—0xA6 (Global Offset 800h)

Offset	Register ID—Description	Default Value
0h	"PCS_DWORD0 (pcs_dword0)—Offset 0h" on page 3385	00010080h
4h	"PCS_DWORD1 (pcs_dword1)—Offset 4h" on page 3387	00600060h
8h	"PCS_DWORD2 (pcs_dword2)—Offset 8h" on page 3388	00000000h
Ch	"PCS_DWORD3 (pcs_dword3)—Offset Ch" on page 3390	5515ACAAh
10h	"PCS_DWORD4 (pcs_dword4)—Offset 10h" on page 3390	575555C1h
14h	"PCS_DWORD5 (pcs_dword5)—Offset 14h" on page 3391	00003E63h
18h	"PCS_DWORD6 (pcs_dword6)—Offset 18h" on page 3393	FFFFFFFFh
1Ch	"PCS_DWORD7 (pcs_dword7)—Offset 1Ch" on page 3393	00000009h
20h	"PCS_DWORD8 (pcs_dword8)—Offset 20h" on page 3394	000000C4h
24h	"PCS_DWORD9 (pcs_dword9)—Offset 24h" on page 3396	00000000h
28h	"PCS_DWORD10 (pcs_dword10)—Offset 28h" on page 3397	00000000h
2Ch	"PCS_DWORD11 (pcs_dword11)—Offset 2Ch" on page 3398	0F000000h
30h	"PCS_DWORD12 (pcs_dword12)—Offset 30h" on page 3400	00250F00h
34h	"PCS_DWORD13 (pcs_dword13)—Offset 34h" on page 3401	00000000h
38h	"PCS_DWORD14 (pcs_dword14)—Offset 38h" on page 3402	007A0018h
3Ch	"PCS_DWORD15 (pcs_dword15)—Offset 3Ch" on page 3403	04100300h
40h	"PCS_DWORD16 (pcs_dword16)—Offset 40h" on page 3405	01000001h
44h	"PCS_DWORD17 (pcs_dword17)—Offset 44h" on page 3406	01000001h
48h	"PCS_DWORD18 (pcs_dword18)—Offset 48h" on page 3408	00008080h
4Ch	"PCS_DWORD19 (pcs_dword19)—Offset 4Ch" on page 3409	00004F10h
50h	"PCS_DWORD20 (pcs_dword20)—Offset 50h" on page 3410	80808080h
54h	"PCS_DWORD21 (pcs_dword21)—Offset 54h" on page 3411	80808080h
58h	"PCS_DWORD22 (pcs_dword22)—Offset 58h" on page 3412	00000000h
5Ch	"PCS_DWORD23 (pcs_dword23)—Offset 5Ch" on page 3412	00180888h
60h	"PCS_DWORD24 (pcs_dword24)—Offset 60h" on page 3413	0001C020h

23.13.1 PCS_DWORD0 (pcs_dword0)—Offset 0h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword0: [Port: 0xA6] + (800h + 0h)

Op Codes:

0h - Read, 1h - Write

Default: 00010080h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_txcfgchange_valid_delay_3_0	reg_txcfgchange_rst_delay_3_0	reserved500	reg_txcfgchange_width_4_0	reg_txcfgchange_ovrride	reg_tx2_soft_reset_n	reg_txswing_clkssel	reg_rcvdetect_ovrd	reg_rcvdetectfinished
							reg_rcvdetect_pulse_width_ovrd	reg_rcvdetect_pulse_width_2_0
							reg_tx1_soft_reset_n	reg_tx_8b10b_bypass
							reg_tx_laneup	reg_left_txiffo_rst_master2
							reg_right_txiffo_rst_master2	reg_plllinksynch_ovrden
							reg_plllinksynch_ovrd	reg_tx1_cmmdisparity

Bit Range	Default & Access	Description
31:28	0h RW	reg_txcfgchange_valid_delay_3_0: Controls counter to wait 128ns after txcfgchange asserts when coming out of reset. This will control phystatus de-assertion after reset. Note: Minimum value when programmed has to be 4'b0100 or greater.
27:24	0h RW	reg_txcfgchange_rst_delay_3_0: Counter value to delay txcfgchange toggle after coming out of reset.
23	0h RW	reserved500: reserved
22:18	0h RW	reg_txcfgchange_width_4_0: Tx power fsm output - divider ratio
17	0h RW	reg_txcfgchange_ovrride: Override txchfchange related counters. (reg_txcfgchange_width, reg_txcfgchange_valid_delay, reg_txcfgchange_rst_delay)
16	1h RW	reg_tx2_soft_reset_n: Active low reset to independently reset Tx lane2 in Display Port
15	0h RW	reg_txswing_clkssel: When 0 selects divide by 2 version of the ick_pllclk clock for Tx swing control logic When 1 selects ick_pllclk clock for Tx swing control logic.
14	0h RW	reg_rcvdetect_ovrd_____: override enable for rcvdetect and rcvdetectfinished
13	0h RW	reg_rcvdetect_____: override for rcvdetect
12	0h RW	reg_rcvdetectfinished_____: override for rcvdetectfinished
11	0h RW	reg_rcvdetect_pulse_width_ovrd: override enable for rcvdetect_pulse_width
10:8	0h RW	reg_rcvdetect_pulse_width_2_0: override value for rcvdetect_pulse_width
7	1h RW	reg_tx1_soft_reset_n: Active low reset to independently reset Tx lane1 in Display Port 0: Lane 1 reset 1: Lane 1 active
6	0h RW	reg_tx_8b10b_bypass: Bypass 8b10b encoder (for SAPIS etc interface.) 0 = Disable 8b/10b encoder bypass 1 = Enable 8b/10b encoder bypass

23.13.2 PCS_DWORD1 (pcs_dword1)—Offset 4h



Bit Range	Default & Access	Description
21	1h RW	cri_rxdigfiltlsq_enable: When 1 enables unsquelch based Rx power up in P0 or P0s
20	0h RW	reg_txfsfm_delay_ovrd: Override enable bit for reg_txfsfm_4us_delay
19:16	0h RW	reg_txfsfm_4us_delay_11_8: Override counter value for 4 us delay in txfsfm lane reset to txbiasen delay
15:14	0h RW	reg_pclk_rate_1_0: Override for pclk_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
13:12	0h RW	reg_rate_1_0: Override for i_rate 00 = gen1 01 = gen2 10 = gen3 11 = GbE
11:9	0h RW	reg_phymode_2_0: Override for PHY Mode Selection 000 = PCIE 001 = USB3 010 = GbE 011 = SATA/SAPIS 100 = Display 101 = DMI 110 = CIO 111 =Reserved
8	0h RW	reg_modeovren: When asserted selects register override bits for phymode, datawidth etc
7:6	1h RW	reg_datawidth: Override for Tx data interface width. 00 - Unused 01 - x8/x10 width (default) 10 - x16/x20 width 11 - x32/x40 width
5	1h RW	soft_reset_n: Active low soft reset override
4	0h RW	reg_diginelben: Override for near end digital loopback.
3	0h RW	reg_digifelben: Override for far end digital loopback
2	0h RW	reg_strapgroup_ovrden: Override Enable for Strap Group
1	0h RW	reg_yank_timer_done_b_ovrd: Override for yank_timer_done_b
0	0h RW	reg_yank_timer_done_b_ovrd_en: Override Enable for yank_timer_done_b

23.13.3 PCS_DWORD2 (pcs_dword2)—Offset 8h

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword2: [Port: 0xA6] + (800h + 8h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_pibiasoff_delay_3_0	cri_sqdbexittimer_override_3_0	cri_sqdbentrytimer_override_5_0	reg_rxdrcgtsqsel_1_0	cri_reut_SlaveSideDataCheckingEn	cri_sqdbtimer_ovren	cri_rxpwrfsm_timer_ovren	reg_rxidle	cri_rxrawdata_sel
				cri_dynkalign_eco3302703_mode	cri_dynkalign_eco3302703_ovren	reg_rxpwrfsm_pibiasoff_ovrride	cri_reset_kalignlck	cri_ebptrrst
							cri_comdispfix	cri_forcebankhit
							cri_kalignmode_1_0	cri_skpprocdis
								cri_elasticbuffer_maskdis

Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_pibiasoff_delay_3_0: Override value for delay (in 2ns increments) between deassertion of opianclkbufen and opibiasen
27:24	0h RW	cri_sqdbexittimer_override_3_0: Rx squelch exit debounce timer
23:18	0h RW	cri_sqdbentrytimer_override_5_0: Rx squelch entry debounce timer
17:16	0h RW	reg_rxdrcgtsqsel_1_0: Squelch output select
15	0h RW	cri_reut_SlaveSideDataCheckingEn: Enable REUT slave side checking while in loopback slave
14	0h RW	cri_sqdbtimer_ovren: Squelch debounce timer override enable
13	0h RW	cri_rxpwrfsm_timer_ovren: Rx power management fsm timer override enable
12	0h RW	reg_rxidle: Chicken bit to override i_rxidle from controller and keep Rx in P0 or P0s
11	0h RW	cri_rxrawdata_sel: When asserted bypass K-align, 10b/8b decoder and Elastic buffer
10	0h RW	cri_dynkalign_eco3302703_mode: Kalign Mode Override Value When cri_dynkalign_eco3302703_ovren is set, this value selects kalignmode 0 - use register bits cri_kalignmode[1:0] to select kalignmode 1 - select the 4 COM kalign mode'
9	0h RW	cri_dynkalign_eco3302703_ovren: Kalign Mode Override Enable Overrides kalign mode select pin, allowing config bit kalignmode_override_val to select kalignmode.
8	0h RW	reg_rxpwrfsm_pibiasoff_ovrride: When asserted selects reg_rxpwrfsm_pibiasoff_delay[3:0]
7	0h RW	cri_reset_kalignlck: When asserted resets Kalign lock indication and Kalign is performed again. The conditions when this would assert includes and is not restricted to any power management states (L0s, L1) or polling quiet states etc.
6	0h RW	cri_ebptrrst: Global broadcast to all lanes that the Elastic Buffer pointers should be reset. This is a pulse and will be generated when we need to reset the pointers because of collision or various other reasons.
5	0h RW	cri_comdispfix: Chicken bit to force disparity in dynamic K-align mode



Bit Range	Default & Access	Description
4	0h RW	cri_forcebankhit: Chicken bit to enable data appear on NOA post k-align lock although k-align block is not achieving lock. This is only for NOA observeability and not for other purpose
3:2	0h RW	cri_kalignmode_1_0: KALIGN Mode Select 00 = dynamic kalign all the time. Accounts for bit slips on incoming stream which can cause symbol to be detected on different bank 10 = dynamic kalign up to L0 x1 = static kalign (same as GDG). Assumes symbol always detected on same data bank
1	0h RW	cri_skpprocdis: SKIP Ordered-Set Processing Disable When this configuration bit is asserted, then SKIP ordered=sets will be ignored (in EB block). Used in Elastic buffer block. 0 = Normal operation. SKIP ordered=sets will be processed by the Elastic Buffer 1 = SKIP processing disabled.
0	0h RW	cri_elasticbuffer_maskdis: Config bit (chicken bit) to disable the masking logic after elec idle ordered set is seen

23.13.4 PCS_DWORD3 (pcs_dword3)—Offset Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword3: [Port: 0xA6] + (800h + Ch)

Op Codes:

0h - Read, 1h - Write


Default: 5515ACAAh

31	28	24	20	16	12	8	4	0
0	1	0	1	0	1	0	1	0
0	1	0	1	0	1	0	1	0
cri_dfx_patbuf_55_48	cri_dfx_patbuf_63_56	cri_dfx_patbuf_71_64	cri_dfx_patbuf_79_72					

Bit Range	Default & Access	Description
31:24	55h RW	cri_dfx_patbuf_55_48: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
23:16	15h RW	cri_dfx_patbuf_63_56: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
15:8	ACh RW	cri_dfx_patbuf_71_64: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.
7:0	AAh RW	cri_dfx_patbuf_79_72: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.

23.13.5 PCS_DWORD4 (pcs_dword4)—Offset 10h

Access Method



Bit Range	Default & Access	Description
31	0h RW	cri_dfx_patbuftrain: Pattern Buffer Manual Training When DFXPATBUFTRAINOVR and DFXLCCESTART are asserted, this manually controls whether the Pattern Buffers are in training or have completed training. 0 : Send training patterns (default) 1 : Send contents of DFXPATBUF
30:28	0h RW	cri_dfx_prbspoly_2_0: PRBS Polynomial Select the polynomial to be used by the PRBS in the Pattern Generator and Pattern Checker. PRBS support 10b or 8b, which is indicated by the msb. 000 - $x^{16} + x^5 + x^4 + x^3 + 1$ (USB3/PCIe Scrambler) (8b) 001 - $x^{16} + x^{15} + x^{13} + x^4 + 1$ (SATA scrambler) (8b) 010 - $x^{31} + x^{28} + 1$ (8b) 011 - $x^7 + x^6 + 1$ (8b) 100 - $x^{15} + x^{14} + 1$ (10b) 101 - $x^{23} + x^{18} + 1$ (10b) 110 - $x^{31} + x^{28} + 1$ (10b) 111 - $x^7 + x^6 + 1$ (10b)
27:26	0h RW	cri_dfx_patbufsize_1_0: Pattern Buffer Size Select the size of the Pattern Buffer to use. The MSB will always be bit 79. The LSB will depend on this select and the DFXLCCESTART (10b or 8b mode). 00 : full 80b buffer (Default) 01 : 70b (while in 10b mode), 56b (while in 8b mode) 10 : 40b (while in 10b mode), 32b (while in 8b mode) 11 : 10b (while in 10b mode), 8b (while in 8b mode)
25	0h RW	cri_dfx_patbufloop: Pattern Buffer Looping Enable Enables looping of the Pattern Buffer. By default, the contents of Pattern Buffer will be used once and stop. Alternatively, the Pattern Buffer will continue to loop until the DFXLCCESTART is de-asserted. 0 : Run Pattern Buffer only once (default) 1 : Loop Pattern Buffer until stopped
24	0h RW	cri_dfx_patbufdwidth: Pattern Buffer Data Width Selects between 10 bit or 8 bit data width for the Pattern Buffer. Determines where in the Tx/Rx path the data is inserted/retrieved. 0 : 10b (default) 1 : 8b
23	0h RW	cri_dfx_patbuftrainovr: Pattern Buffer Training Override Enables manual training of the Pattern Buffer instead of the automated coordination between the Pattern Checker and Pattern Generator. When asserted, the DFXPATBUFTRAIN bit will be used to force when training is active and when it is complete. 0 : Automatic Training (default) 1 : Enable Manual Training
22	0h RW	cri_dfx_marginmode: Margin mode Overrides standard setup configurations for use with Eye Width Margining. 0 : Standard Mode (default) 1 : Margin Mode enabled
21	0h RW	cri_dfx_chk_sel: Pattern Checker 8b10b Select This determines where Rx data is compared, either in the 10-bit domain before decode or after 10b-8b decoding. 0: 10b domain 1: 8b domain
20	0h RW	cri_dfx_patchken: Pattern Checker Enable 0 : Disable Pattern Checker (default) 1 : Enable Pattern Checker
19	0h RW	cri_dfx_patgenen: Pattern Generator Enable This will activate the Dfx bypass muxes in the PCS Tx path. 0 : Disable Pattern Generator (default) 1 : Enable Pattern Generator
18	0h RW	cri_dfx_clrerrcnt: Clear Error Counter Resets the Pattern Checker's error counter. 0 : Error Counter allowed to run (default) 1 : Error Counter held in reset
17	0h RW	cri_dfx_lcereset: Local Compare Engine Reset Resets all components of the Local Compare Engine in both the Pattern Generator and the Pattern Checker. 0 : LCE not in reset (default) 1 : LCE in reset
16	0h RW	cri_dfx_lcestart: Local Compare Engine Start Controls the starting and stopping of the LCE. Allows for simultaneous or independent start across lanes. Once stopped, a DFXLCERESET is usually required. 0 : LCE stopped (default) 1 : LCE running
15:8	3Eh RW	cri_dfx_patbuf_7_0: Pattern Buffer Storage In 10b mode, the buffer is read as eight 10b chunks. The first 10 bits should not equal the Comma Symbol: '0011111010' (or its inversion '1100000101'). In 8b mode, the buffer is read as eight 10b chunks, where the 10th bit is unused and the 9th bit is the K-bit indicator. The first 10 bits should not equal the Comma Symbol: 'xx10111100'. DFXPATBUF[78] should not be '1'.
7:0	63h RW	cri_dfx_patbuf_15_8: Pattern Buffer Storage See cri_dfx_patbuf[7:0] description.



23.13.7 PCS_DWORD6 (pcs_dword6)—Offset 18h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword6: [Port: 0xA6] + (800h + 18h)

Op Codes:

0h - Read, 1h - Write

Default: FFFFFFFFh

31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
cri_dfx_prbseed_7_0								cri_dfx_prbseed_31_24

Bit Range	Default & Access	Description
31:24	FFh RW	cri_dfx_prbseed_7_0: PRBS Seed Can be used for HVM determinism. The use of all zeroes can result in lockup.
23:16	FFh RW	cri_dfx_prbseed_15_8: PRBS Seed See cri_dfx_prbseed[7:0] description.
15:8	FFh RW	cri_dfx_prbseed_23_16: PRBS Seed See cri_dfx_prbseed[7:0] description.
7:0	FFh RW	cri_dfx_prbseed_31_24: PRBS Seed See cri_dfx_prbseed[7:0] description.

23.13.8 PCS_DWORD7 (pcs_dword7)—Offset 1Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)


pcs_dword7: [Port: 0xA6] + (800h + 1Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00000009h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
dfx_cri_errcnt_7_0								cri_dfx_prbstraincnt_3_0



Bit Range	Default & Access	Description
31:24	X RO	dfx_cri_errcnt_7_0: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
23:16	X RO	dfx_cri_errcnt_15_8: Error Counter Tracks how many bit errors the Pattern Checker has detected. Can be cleared using DFXCLRERRCNT or DFXLCERESSET.
15	X RO	i_rxcaldone: RX Calibration Cycles Complete Indicator
14	X RO	dfx_cri_lcemgnerr: Local Compare Engine Margin Error Indicates that the error counter has reached its max value. This can be used by the Rx upartition during Margin Mode to determine when the eye width has closed.
13	X RO	cri_dfx_patgen2active: Pattern Generator 2 Active status indicator In a lane with two Tx paths, this indicates that the second Pattern Generator is in progress. The DFXPATGENACTIVE will only indicate that the first Pattern Generator is in progress.
12	X RO	dfx_cri_patbufallfail: Pattern Buffer All Fail status indicator Indicates that there has not been a single matching Pattern Buffer pattern. This could signify that an error occurred during training.
11	X RO	dfx_cri_patchkactive: Pattern Checker Active status indicator Indicates that the Pattern Checker is in progress (either Pattern Buffer or PRBS).
10	X RO	dfx_cri_patgenactive: Pattern Generator Active status indicator Indicates that the Pattern Generator is in progress (either Pattern Buffer or PRBS).
9	X RO	dfx_cri_lctraindone: Local Compare Engine Training Done status indicator Indicates that the Pattern Checker training is completed (either Pattern Buffer or PRBS). The Pattern Checker is now synchronized to the Pattern Generator.
8	X RO	dfx_cri_lctrainactive: Local Compare Engine Training Active status indicator Indicates that the Pattern Checker training is in progress (either Pattern Buffer or PRBS).
7	0h RW	reserved501: reserved
6	0h RW	cri_dfx_patgen2en: Pattern Generator 2 Enable In a lane with two Tx paths, this enables the second Pattern Generator. The DFXPATGENEN will enable the first Pattern Generator. 0 : Disable second Pattern Generator (default) 1 : Enable second Pattern Generator
5:4	0h RW	cri_dfx_maxerrcnt_1_0: Maximum Error Count Selectable maximum value that the DFXERRCNT can reach before the Local Compare Engine is automatically stopped. 00 : 2^{16} (default) 01 : 2^{10} 10 : 2^8 11 : 2^4
3:0	9h RW	cri_dfx_prbstraincnt_3_0: PRBS Training Count The number of consecutive cycles that the Pattern Checker's PRBS must be error free before it is considered synchronized. Default is 9.

23.13.9 PCS_DWORD8 (pcs_dword8)—Offset 20h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword8: [Port: 0xA6] + (800h + 20h)

Op Codes:

0h - Read, 1h - Write

Default: 000000C4h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reg_partial	reg_slumber	reg_tx2_cdr_override_2_0	reg_cdr_override_2_0	reg_ebuffmode	reg_usedclockchannel_1_0	reg_usedclockchannel_ovrride	reg_gbl_ovrride	reg_tx1_pclkon_inp2
								reg_tx2_pclkon_inp2
								reg_tx2_txenable
								cri_rxeb_ptr_init_3_0
								reg_powerfsm_ovrride
								reg_suspend
								reg_pclkcfginput
								reg_useqclock
								cri_rxeb_hiwater_3_0
								cri_rxeb_lowater_3_0

Bit Range	Default & Access	Description
31	0h RW	reg_partial: Override for i_partial
30	0h RW	reg_slumber: Override for i_slumber
29:27	0h RW	reg_tx2_cdr_override_2_0: Override for cdr_override strap for second tx2
26:24	0h RW	reg_cdr_override_2_0: Override for cdr_override strap
23	0h RW	reg_ebuffmode: Override for ebuffmode (no functionality in p1271 phase1 design)
22:21	0h RW	reg_usedclockchannel_1_0: Selects the active clock channel
20	0h RW	reg_usedclockchannel_ovrride: When asserted selects reg_usedclockchannel[1:0]
19	0h RW	reg_gbl_ovrride: Global override select
18	0h RW	reg_tx1_pclkon_inp2: When asserted keeps PCLK running in P2 mode. For DP this is used for Lane1
17	0h RW	reg_tx2_pclkon_inp2: When asserted keeps PCLK running in P2 mode. This is reserved (no impact) for PCIe/DMI and used for DP Lane2
16	0h RW	reg_tx2_txenable: Override for i_txenable for tx2
15:12	0h RW	cri_rxeb_ptr_init_3_0: Config override for initial value of Rx elastic buffer read pointer
11	0h RW	reg_powerfsm_ovrride: When asserted overrides for Tx power fsm are selected
10	0h RW	reg_suspend: Override for suspend
9	0h RW	reg_pclkcfginput: Override for pclkcfginput strap
8	0h RW	reg_useqclock: Override for useqclock; MUX select for I or Q clk for TX clocking
7:4	Ch RW	cri_rxeb_hiwater_3_0: Elastic buffer high watermark based on which SKP is removed

23.13.10 PCS_DWORD9 (pcs_dword9)—Offset 24h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs dword9: [Port: 0xA6] + (800h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31	0h RW	reserved502: reserved
30:26	0h RW	reg_strapgroup_4_0: Override for i_strapgroup
25:24	0h RW	reg_powerdown_1_0: Override for i_powerdown
23	0h RW	reg_pcs_txcmnkeepdisable_ovrd: Override for ipcs_txcmnkeepdisable input 0: Use value on ipcs_txcmnkeepdisable input pin to determine o_txgohighz state in P2/ slumber 1: Force pcs_txcmnkeepdisable to 0
22:18	0h RW	reg_straplane_5_0: Override for i_straplane
17	0h RW	reg_tx1_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx1 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
16	0h RW	reg_tx2_powerdown_override: Overrides i_powerdown[1:0] indication from MAC for Tx2 1 : selects reg_powerdown[1:0] 0 : selects i_powerdown[1:0]
15	0h RW	reg_txdatavalid: Override for i_txdatavalid (register is NOT used)
14:13	0h RW	reg_txdeemp_1_0: Override for i_txdeemp



Bit Range	Default & Access	Description
12:10	0h RW	reg_txmargin_2_0: Override for i_txmargin
9	0h RW	reg_txswing: Override for i_txswing
8	0h RW	reg_txenable: Override for i_txenable
7:6	0h RW	reg_txterm_vcc_1_0: Override for txterm_vcc strap
5	0h RW	reg_txdetrxlpbk: Override for i_txdetrxlpbk
4	0h RW	reg_txelectidle: Override for i_txelectidle
3	0h RW	reg_txcompliance: Override for i_txcompliance
2	0h RW	reg_txoneszeroes: Override for i_txoneszeroes
1:0	0h RW	reg_latencyoptim_1_0: Override for i_latencyoptim

23.13.11 PCS_DWORD10 (pcs_dword10)—Offset 28h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword10: [Port: 0xA6] + (800h + 28h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reg_rxpwrfsm_timer_WAIT_RX_PT_CLK_3_0	reg_rxpwrfsm_timer_ENABLE_RX_3_0	reg_rxpwrfsm_timer_RX_SEQEN_3_0	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0		reg_clk_valid_cnt_7_0	reg_rxterm	reg_rxpolarity	reg_rxeqtrain
						reg_rxsquelchen	cri_rxpwrfsm_sgentimer_ovrden	reg_rxintfritren_override
							reg_rxintfritren_l	reg_clk_valid_cnt_ovrd



Bit Range	Default & Access	Description
31:28	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PI_CLK_3_0: Rx Power state m/c timer value used to enable PI clock
27:24	0h RW	reg_rxpwrfsm_timer_ENABLE_RX_3_0: Rx Power state m/c timer value used to enable receivers
23:20	0h RW	reg_rxpwrfsm_timer_RX_SQEN_3_0: Rx Power FSM Rx Squelch Enable Timer Override Value Affect squelch enable startup sequence during 'synchronous' squelch startup mode. 0000 - Invalid 0001 - 1 susclk period ... 1111 - 15 susclk period
19:16	0h RW	reg_rxpwrfsm_timer_WAIT_RX_PIBIAS_3_0: Rx Power state m/c timer value used to enable PI BIAS
15:8	0h RW	reg_clk_valid_cnt_7_0: Over ride value for clock valid delay in clock top block before toggling phystatus.
7	0h RW	reg_rxterm: Override for i_rxterm
6	0h RW	reg_rxpolarity: Override for i_rxpolarity
5	0h RW	reg_rxeqtrain: Override for i_rxeqtrain
4	0h RW	reg_rxsquelchen: Override for i_rxsquelchen
3	0h RW	cri_rxpwrfsm_sqentimer_ovrden: Squelch Enable Timer Override Enable Used to override the squelch enable timer in PCS with the timer value set by the Rx Squelch Enable timer register (reg_rxpwrfsm_timer_RX_SQEN[3:0]).
2	0h RW	reg_rxintfltren_override: Rx Integral Filter Override Select 0: selects i_rxintfltren_l input pin. 1: selects reg_rxintfltren_l register
1	0h RW	reg_rxintfltren_l: Override for Rx integral filter enable i_rxintfltren_l
0	0h RW	reg_clk_valid_cnt_ovrd: Override enable for reg_clk_valid_cnt

23.13.12 PCS_DWORD11 (pcs_dword11)—Offset 2Ch

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword11: [Port: 0xA6] + (800h + 2Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0F000000h



Intel Atom® Processor E3800 Product Family
Datasheet
3399



Access Method

pcs_dword12: [Port: 0xA6] + (800h + 30h)

Op Codes:

0h - Read, 1h - Write

Default: 00250F00h

[illegible]



Bit Range	Default & Access	Description
31	0h RW	reg_tx fsm_200ns_ovrd : Override reg_tx fsm_200ns_delay+G2
30:24	0h RW	reg_tx fsm_200ns_delay_6_0 : Override value of counter for 200ns delay between txen and txloadgenen
23	0h RW	reg_loadgen2txen_fall_ovrd : reserved
22:20	2h RW	reg_tx2_stagger_mult_2_0 : Stagger multiplier for Rx (or Tx1) (Same decoding as tx1_stagger_mult[2:0]) For Display, this multiplier applies to Tx2. For non-Display PHYs, this multiplier applies to the Rx. The multiplier limit for the Rx is 8x (3'b100); anything beyond that is invalid.
19	0h RW	reg_lanestagger_by_group : When = 1, uses group number for lane staggering, by devalues lane number is used.
18:16	5h RW	reg_tx1_stagger_mult_2_0 : Stagger multiplier for Tx (or Tx1) These bits set the lane staggering multiplier for the transmitter based on the 'linkclk' period. 000 - 0x 001 - 1x 010 - 2x 011 - 4x 100 - 8x 101 - 16x 110 - 32x 111 - 64x For Display, this multiplier applies to Tx1.
15:14	0h RW	reserved509 : reserved
13	0h RW	reserved510 : reserved
12:8	Fh RW	reg_tx1_stagger_mask_4_0 : Mask bit for lane number. Used to group lanes for staggering
7	0h RW	reserved507 : reserved
6	0h RW	reg_lanestagger_strap_ovrd : When 1 config override for lane stagger strap (bits [4:0] of this register) is selected
5	0h RW	reserved508 : reserved
4:0	0h RW	reg_lanestagger_strap_4_0 : Override for lane stagger strap

23.13.14 PCS_DWORD13 (pcs_dword13)—Offset 34h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword13: [Port: 0xA6] + (800h + 34h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
visa_en	reserved512	visa_clk_sel1_4_0	visa_lane_sel1_7_0	visa_bypass	reserved511	visa_clk_sel0_4_0	visa_lane_sel0_7_0	



Access Method

pcs_dword14: [Port: 0xA6] + (800h + 38h)

Op Codes:

Default: 007A0018h

Bit Range	Default & Access	Description
31	0h RW	reg_clkbuf_stagger_ovrd: Override enable for reg_clkbuf_stagger_cnt
30	0h RW	reg_clkbuf_stagger_cnt_10: Counter override value for staggering delay of clock buffer control signals.



Bit Range	Default & Access	Description
29	0h RW	reg_slowclk_ovrden: Slow Clock Override Enable When set 1'b1, reg_slowclocken and reg_sclk250en are valid. When cleared 1'b0, output of FSM will drive slow clock enable.
28:24	0h RW	reg_txloadgenen2txen_fall_delay_4_0: reserved
23:20	7h RW	o_cmlmuxsthsel_3_0: CML Mux strength control
19:16	Ah RW	o_cmlsthsel_3_0: RX CML driver strength
15:12	0h RW	o_pcisel_3_0: I clk phase correction control
11:8	0h RW	o_pcqsel_3_0: Q clk phase correction control
7	0h RW	o_phaseicen: Iclk phase correction enable.
6	0h RW	o_phaseqcen: Qclk phase correction enabled.
5	0h RW	o_pcbypass: Phase correction bypass.
4	1h RW	o_slowclocken: Slow clock 1 enable Only valid if slow clock override enable is set 1'b1
3	1h RW	o_sclk250en: Slow clock 2 enable Only valid if slow clock override enable is set 1'b1
2:0	0h RW	cri_kalign_com_cnt: Upper 3 bits of a 7-bit counter that counts number of COM characters found. Used for special SAPIS mode where spread spectrum clocking can be utilized. Note: This register is used in conjunction with another PCS register cri_kalignmode[1:0] = 10 Register value Minimum COM count to achieve symbol lock 000 - 18 001 - 34 010 - 50 011 - 66 100 - 82 101 - 98 110 - 114 111 - 130

23.13.16 PCS_DWORD15 (pcs_dword15)—Offset 3Ch

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword15: [Port: 0xA6] + (800h + 3Ch)


Op Codes:

0h - Read, 1h - Write

Default: 04100300h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
13:8	3h RW	reserved513: reserved
7:0	0h RW	reg_clkbuf_stagger_cnt_9_2: Counter override value for staggering delay of clock buffer control signals.

23.13.17 PCS_DWORD16 (pcs_dword16)—Offset 40h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword16: [Port: 0xA6] + (800h + 40h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h

31	28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																														
0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0</

Bit Range	Default & Access	Description
31	0h RW	sqelch_shunt_ovrd_en: Squelch Shunt Pulse Duration Override Enable Overrides the hardware default shunt pulse duration value 1: Shunt Pulse Duration Override Enable 0: Shunt Pulse Duration Override Disable
30:28	0h RW	sqelch_shunt_cnt_2_0: Squelch Shunt Pulse Duration Override Value 000 = No shunt pulse generated 001 = 1 susclk cycles ... 111 = 7 susclk cycles
27	0h RW	reserved520: reserved
26	0h RW	i_rxsqfsm_timersel: Squelch FSM Timer Select 0 - Selects 25Mhz values for squelch timer and shunt pulse generation . 1 - Selects 100Mhz values for squelch timer and shunt pulse generation. This register is applicable to synchronous squelch startup mode.
25	0h RW	i_rxsq_asyncmode_h: Squelch Async Startup Mode This squelch startup mode is power state independent. When enabled, the squelchen signal sent to Modphy will asynchronously enable the squelch detector circuit. Once enabled, the squelch detector circuit will asynchronously send an unfiltered/unqualified squelch indication signal out of Modphy. The squelch indication signal will initially be unstable, so it is up to the consumer of this signal to filter/qualify it accordingly. The asynchronous squelch startup mode is beneficial because it significantly reduces the squelch startup latency. This decrease in latency does come at the cost of slightly higher power when squelch is not enabled as the IREF and Squelch Keeper circuits must remain enabled. When disabled, the squelch startup sequence is synchronous in nature and the squelch indication signal sent out of Modphy is stable/filtered.
24	1h RW	i_rxsquelchstby_h: Fast Squelch Enable Mode Bit to keep the IREF (ivrefen) on during P2 and reduce squelch startup time.



Bit Range	Default & Access	Description
23:18	0h RW	reserved519: reserved
17:16	0h RW	cri_dfx_evenoddmask_1_0: Pattern Checker Even/Odd Bit Error Mask Select 00 : no masking; all errors will be counted 01: select odd path, mask even path; only errors on bits [1,3,5,7,9] are counted 10: select even path, mask odd path; only errors on bits [0,2,4,6,8] are counted 11: reserved;
15:12	0h RW	reserved518: reserved
11:10	0h RW	cri_dfx_lce2patsrc_1_0: Local Compare Engine 2 Pattern Source In a lane with two Tx paths, this selects between using Pattern Buffer or PRBS as source of LCE patterns for the second LCE. The DFXLCEPATSR selects for the first LCE. 0 : Pattern Buffer (default) 1 : PRBS
9:8	0h RW	cri_dfx_lcepatsrc_1_0: Local Compare Engine Pattern Source. Selects between using Pattern Buffer or PRBS as source of LCE patterns. 00 : Pattern Buffer; use LCE default training pattern; 01: Pattern Buffer; use the first 40b of pattern buffer for training. 10: PRBS; use LCE default training pattern; 11: PRBS; use the first 40b of pattern buffer for training.
7:6	0h RW	reserved517: reserved
5:4	0h RW	txloadgen_ctr_val: TxLoadGen Pulse Width Control Controls the pulse width of txloadgenen from PCS to Tx upar. This is used in MAC initiated digital far end loopback mode in PCIE family. 00 - txloadgenen pulse width is 4 symbol clocks (default) 01- txloadgenen pulse width is 2 symbol clocks 10 - txloadgenen pulse not generated 11 - txloadgenen pulse width is 6 symbol clocks
3	0h RW	cri_txhighpowerei_ovrden: TxHighPowerEI Override Mode Enable 0 - TxHighPowerEI to TxuPAR driven by Logic 1 - TxHighPowerEI to TxuPAR driven by override register value(s).
2	0h RW	cri_tx1highpowerei_ovrdval: Tx1HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx1HighPowerEI disabled 1 - Tx1HighPowerEI enabled
1	0h RW	cri_tx2highpowerei_ovrdval: Tx2HighPowerEI Override Value Valid when cri_txhighpowerei_ovrden = 1'b1. 0 - Tx2HighPowerEI disabled 1 - Tx2HighPowerEI enabled
0	1h RW	p2_fast_exit_en: P2 Fast Exit Mode Enable Common Mode sustainer will be enabled during P2 when this bit is asserted. 1: P2 Fast Exit Mode Enable 0: P2 Fast Exit Mode Disable

23.13.18 PCS_DWORD17 (pcs_dword17)—Offset 44h

Access Method


Type: Message Bus Register
(Size: 32 bits)

pcs_dword17: [Port: 0xA6] + (800h + 44h)

Op Codes:

0h - Read, 1h - Write

Default: 01000001h



31				28				24				20				16				12				8				4				0																																																																			
0 0 0 0				0 0 0 0				0 0 0 1				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 1																																																															
oiredfxsel_1_0				iopampsfpen_h				iopampsfnen_h				iopamppen_h				iopampnen_h				monanapgen				monubufbypassen				reserved522				reg_ivrefen				ivrefen_ovrd				reserved523				oirefcurmonsel				lrcdisable				reserved521				lrc_rdy_pulsegen				lrc_rdy_target_1_0				lrc_rdy_ovd				rxtermprccen				rxvgaprrccen				txpmrrccen				irefpmrrccen				rxtermprccen				rxvgaprrccen				txpmrrccen				irefpmrrccen			

Bit Range	Default & Access	Description
31:30	0h RW	oiredfxsel_1_0: IREF Voltage Monitor Select Selects voltage to monitor within the IREF block. 00 - vref 01 - pgate 10 - vbc 11 - vref loop
29	0h RW	iopampsfpen_h: (NOT USED - noconned)
28	0h RW	iopampsfnen_h: (NOT USED - noconned)
27	0h RW	iopamppen_h: DC Monitor Unity-Gain Buffer Enable 0: disable (default) 1: enable
26	0h RW	iopampnen_h: (NOT USED - noconned)
25	0h RW	monanapgen: DC Monitor to Monitor Port Enable Enables DC monitor passgate to monitor port via analog observability abutment.
24	1h RW	monubufbypassen: DC Monitor Unity-Gain Buffer Bypass 0: no bypass 1: bypass (default - required for LRC)
23:22	0h RW	reserved522: reserved
21	0h RW	reg_ivrefen: IvrefEn Override Value Register is valid when override mode is enabled (ivrefen_ovrd). During this mode, this register will have direct control to enable/disable the ivref opamp. 0 - Disable ivref opamp 1 - Enable ivref opamp
20	0h RW	ivrefen_ovrd: IvrefEn Override Select 0 - the enable for the ivref opamp (ivrefen) is driven by the FSM. 1 - the ivrefen is driven by the register (reg_ivrefen).
19:17	0h RW	reserved523: reserved
16	0h RW	oirefcurmonsel: IREF Current Monitor Select Enables current mirror from the IREF block to the 'shared' analog monitor port.
15	0h RW	lrcdisable: LRC Disable This bit disables the LRC. Any token received is passed to the next lane.
14:12	0h RW	reserved521: reserved
11	0h RW	lrc_rdy_pulsegen: LRC Ready PulseGen Generates a pulse 1 cal_clk cycle wide on the lrc_rdy signal to all four targets; does not recompute local Rcomp code. Values in DWD 0x14 (*rccodes[7:0]) will be latched into targets. User must clear this bit before generating another pulse. Note: User should disable PM and PER. FSM can take control and codes can be overridden.
10:9	0h RW	lrc_rdy_target_1_0: LRC Ready Pulse Target Indicates which lrc target to recompute when lrc_rdy_ovd is strobed 00: irefrrccode 01: txrrccode 10: rxtermrrccode 11: rxvgarrrccode



23.13.23 PCS_DWORD22 (pcs_dword22)—Offset 58h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword22: [Port: 0xA6] + (800h + 58h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	0	0							
rxvgarcoffset_7_0				rxtermrcoffset_7_0				txrcoffset_7_0				irefrcoffset_7_0			

Bit Range	Default & Access	Description
31:24	0h RW	rxvgaroffset_7_0: Rx VGA Rcomp Offset Same description as IREF Rcomp Offset, but applies to RxVGA Rcomp.
23:16	0h RW	rxtermrcoffset_7_0: Rx Termination Rcomp Offset Same description as IREF Rcomp Offset, but applies to RxTerm Rcomp.
15:8	0h RW	txrcoffset_7_0: Tx Rcomp Offset Same description as IREF Rcomp Offset, but applies to Tx Rcomp.
7:0	0h RW	irefrcoffset_7_0: Iref Rcomp Offset This value is added to the scaled LRC code to determine the final calibration code used by the Iref block. 2's complement format. The full 8-bit offset is used with the scale multiplier to determine the final 8-bit value, but the Iref target only uses the upper MSBs of the final value. 0x00: Offset = 0 0x01: Offset = +1 0x7F: Offset = +127 0xFF: Offset = -1 0x80: Offset = -128 Note: The final rcomp code has rollover protection so the final rcomp code + offset will not exceed the min/max range.

23.13.24 PCS_DWORD23 (pcs_dword23)—Offset 5Ch

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword23: [Port: 0xA6] + (800h + 5Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00180888h

31				28				24				20				16				12				8				4				0											
0				0				0				0				1				1				0				0				0				0				0			
iclkcqcf_spare_7_0								iclkcif_spare_7				iclkcif_spare_6_3				iclkcif_spare_2_0				reserved526				i_drvcfg_3_0				i_ploadcfg_3_0				ipbiasctrl_3_0											



Bit Range	Default & Access	Description
31:24	0h RW	iclkqcfg_spare_7_0: (Bonus bits for Data Lane Clk Distrubtion block)
23	0h RW	iclkicfg_spare_7: Repurposed for IREF backup mode in DL Select bit to enable diode based IREF in DL 0 - functional mode, use IREFGEN loop output 1 - bypass IREF loop, use diode connected PMOS output Ensure IREF loop amp is enabled by forcing reg_ivrefen and ivrefen_ovrd to 1
22:19	3h RW	iclkicfg_spare_6_3: TX MUX tail current strength setting
18:16	0h RW	iclkicfg_spare_2_0: CLK Distribution Monitor MUX Select
15:12	0h RW	reserved526: reserved
11:8	8h RW	i_drvcfg_3_0: CLK: Driver Tail Current Control
7:4	8h RW	i_ploadcfg_3_0: CLK: Pbias Ref Current Selection
3:0	8h RW	ipbiasctrl_3_0: CLK: Pmos-Load Pbias Voltage Control

23.13.25 PCS_DWORD24 (pcs_dword24)—Offset 60h

Access Method

Type: Message Bus Register
(Size: 32 bits)

pcs_dword24: [Port: 0xA6] + (800h + 60h)


Op Codes:

Op codes:
0h - Read, 1h - Write

Default: 0001C020h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 1	1 1 0 0	0 0 0 0	0 0 1 0	0 0 0 0	0
reserved528		reserved527	cri_lanereset_clkgatectl	cri_lanereqforce	cri_susclkdisable_delay_4_0	cri_data_dynclkgate_mode_1_0	cri_eios_waittime_ovren	cri_eios_waittime_6_0

Bit Range	Default & Access	Description
31:24	0h RW	reserved528: reserved
23:17	0h RW	reserved527: reserved



Bit Range	Default & Access	Description
16	1h RW	cri_lanereset_clkgatectl: 1: The assertion of lane reset will have the effect of gating the susclk and de-asserting the internal laneclkreq. This mode is only valid when the data lane dynamic clock gating mode is set to a non-zero value (i.e. 01, 10, and 11). 0: The assertion of lane reset will have no effect on the gating of susclk and state of the internal laneclkreq signal.
15	1h RW	cri_lanereqforce: Controls whether the internal laneclkreq will be forced to 1 or 0 when cfg_data_dynclkgate_mode is set to 00 or 10. 1: force laneclkreq high 0: force laneclkreq low. This mode will likely be used when one of the lanes is disabled while other lanes in the family are enabled. In this case the internal laneclkreq of the disabled lane should be de-asserted (not influencing the clk gating decision)
14:10	10h RW	cri_susclkdisable_delay_4_0: This register will control the number of cycles to delay the susclk enable de-assertion, in addition to the de-assertion of the laneclkreq signal sent out of the data lane. The susclk enable must be continuously de-asserted for the duration of this delay in order for the de-asserted state to be captured by the clock gating controller. 5'b00000 - 0 Cycle Delay 5'b00001 - 1 Cycle Delay 5'b00010 - 2 Cycle Delay 5'b11110 - 30 Cycle Delay 5'b11111 - 31 Cycle Delay
9:8	0h RW	cri_data_dynclkgate_mode_1_0: Controls the dynamic clock gating behavior in the data lane. 00 - susclk gating and laneclkreq disabled (Forced to configured value). In this mode the susclk will not be gated under any circumstances and the laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 01 - susclk gating disabled, laneclkreq enabled . In this mode the susclk will not be gated under any circumstances. The laneclkreq sent out of the data lane will toggle based on whether the lane power state, susclk need and the previous lane's laneclkreq signal. 10 - susclk gating enabled, laneclkreq disabled (forced to configured value) - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the lane will be forced to a programmed value (can be forced high or low) 11 - susclk gating and laneclkreq enabled - In this mode the susclk will be gated during P2/Slumber when there are no requests to change the TX common mode. The laneclkreq sent out of the data lane will toggle based on the lane power state, susclk need and the previous lane's laneclkreq signal.
7	0h RW	cri_eios_waittime_ovren: EIOS Wait Time Override Enable for Rx Turn OFF 0: hardware value for EIOS wait timer is selected. 1: selects cri_eios_waittime[6:0]
6:0	20h RW	cri_eios_waittime_6_0: EIOS Wait Time for Rx Turn OFF Represents override value timer in PCS that comes into play during EIOS based turn off Rx (Rx L0s) 0000000 - Timer is bypassed 0000001 - 1 PLL link clock period delay (2ns) 0000010 - 2 PLL link clock period delay (4ns) ... 0100000 - 32 PLL link clock periods delay (64ns) - default



23.14 PCI Express* Lane 3 Electrical Address Map

Table 251. Summary of PCI Express* Lane 3 Electrical Message Bus Registers—0xA6 (Global Offset 880h)

Offset	Register ID—Description	Default Value
0h	"TX_DWORD0 (tx_dword0)—Offset 0h" on page 3415	2600003Ah
4h	"TX_DWORD1 (tx_dword1)—Offset 4h" on page 3416	20000000h
8h	"TX_DWORD2 (tx_dword2)—Offset 8h" on page 3417	5580983Ah
Ch	"TX_DWORD3 (tx_dword3)—Offset Ch" on page 3417	0C782040h
10h	"TX_DWORD4 (tx_dword4)—Offset 10h" on page 3419	2B404D55h
14h	"TX_DWORD5 (tx_dword5)—Offset 14h" on page 3419	00000000h
18h	"TX_DWORD6 (tx_dword6)—Offset 18h" on page 3420	1F200000h
1Ch	"TX_DWORD7 (tx_dword7)—Offset 1Ch" on page 3421	0038383Fh
20h	"TX_DWORD8 (tx_dword8)—Offset 20h" on page 3422	0600AA80h
24h	"TX_DWORD9 (tx_dword9)—Offset 24h" on page 3422	00430C06h
28h	"TX_DWORD10 (tx_dword10)—Offset 28h" on page 3423	00000000h
2Ch	"TX_DWORD11 (tx_dword11)—Offset 2Ch" on page 3424	00001000h
30h	"TX_DWORD12 (tx_dword12)—Offset 30h" on page 3426	00000000h
34h	"TX_DWORD13 (tx_dword13)—Offset 34h" on page 3427	00000000h
38h	"TX_DWORD14 (tx_dword14)—Offset 38h" on page 3428	00400000h
3Ch	"TX_DWORD15 (tx_dword15)—Offset 3Ch" on page 3429	00000000h
40h	"TX_DWORD16 (tx_dword16)—Offset 40h" on page 3430	00008A00h

23.14.1 TX_DWORD0 (tx_dword0)—Offset 0h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword0: [Port: 0xA6] + (880h + 0h)

Op Codes:

0h - Read, 1h - Write

Default: 2600003Ah

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
0				0				1				0				0				1				1				0				0				0				0				0				0				1				1				1				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0				0			

Bit Range	Default & Access	Description
31	0h RO	reserved504: reserved



Access Method

tx_dword1: [Port: 0xA6] + (880h + 4h)

Op Codes:

0h - Read, 1h - Write

Default: 20000000h

Bit Range	Default & Access	Description
31:30	0h RO	reserved510: reserved
29:24	20h RW	ofrcr2short3_5_0: number of slices in R2 for swing 3 (DE) MSB has no effect.
23:22	0h RO	reserved509: reserved
21:16	0h RO	reserved508: reserved
15:14	0h RO	reserved507: reserved
13:8	0h RO	reserved506: reserved



Bit Range	Default & Access	Description
7:6	0h RO	reserved505: reserved
5:0	0h RW	ofrcr2short0_5_0: number of slices in R2 for swing 0 (FS) MSB has no effect.

23.14.3 TX_DWORD2 (tx_dword2)—Offset 8h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword2: [Port: 0xA6] + (880h + 8h)

Op Codes:

0h - Read, 1h - Write

Default: 5580983Ah

31	28	24	20	16	12	8	4	0
0	1	0	1	0	1	1	0	0
0	1	0	1	1	0	0	0	1
0	1	0	1	1	0	0	0	1
omargin010_7_0	omargin000_7_0	ouniqtranscale_7_0	reserved511	ofrcslices_6_0				

Bit Range	Default & Access	Description
31:24	55h RW	omargin010_7_0: factor (X/128) of slices to use in main-R1 for full swing level. Used for ~2/3Vp2p
23:16	80h RW	omargin000_7_0: factor (X/128) of slices to use in main-R1 for full swing level. Used for ~1V p2p. To be used in Gen2 mode (Gen1/Gen2 depend on dataratefit and downscaleamp register)
15:8	98h RW	ouniqtranscale_7_0: scales the number of slices defined the ref circuit (or R-comp circuit) by factor of ouniqtranscale[7:0]/128 The scaled amount of slices might be used in the full-swing Uis according to ouniqtrangenmethod[1:0] The scaled amount of slices might be used in the full-swing Uis according to oscaledcompmethod[1:0]
7	0h RO	reserved511: reserved
6:0	3Ah RW	ofrcslices_6_0: number of used slices if forced Used in compensated GPIO mode

23.14.4 TX_DWORD3 (tx_dword3)—Offset Ch

Access Method


Type: Message Bus Register
(Size: 32 bits)

tx_dword3: [Port: 0xA6] + (880h + Ch)

Op Codes:

0h - Read, 1h - Write

Default: 0C782040h



October 2018
Document Number: 538136, Rev. 4.3



23.14.9 TX_DWORD8 (tx_dword8)—Offset 20h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword8: [Port: 0xA6] + (880h + 20h)

Op Codes:

0h - Read, 1h - Write

Default: 0600AA80h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ontlptime_7_0	ofrcdccoup_1_0	obybbycomp	obypdftmode_4_0	odftpisodata1_7_0	odftpisodata0_1_0	reserved529	reserved528	

Bit Range	Default & Access	Description
31:24	6h RW	ontlptime_7_0: [after step 1 of pullup] time (ick_susslow cycles) to wait (step 2) and let the pads leak downwards before comparing pads to Vref to determine if the pad exceeded Vref as a result of leakage.
23:22	0h RW	ofrcdccoup_1_0: 00
21	0h RW	obybbycomp: 0' the amount of slices used in dftbypmode is by 'nswbypass', 'pswbypass' and 'r2bypass' registers '1' the amount of slices used is by 'slices' from swing-control block. Number of slices in R2 in EI - is also affected by this bit
20:16	0h RW	obypdftmode_4_0: selects the DFT mode. 5'h00 - DFT_OFF 5'h01 - DFTHIZ 5'h02 - DFTEI 5'h03 - DFTFELB 5'h04 - DFTALL1DIF 5'h05 - DFTALL0DIF 5'h06 - DFTALL1SE 5'h07 - DFTALL0SE 5'h08 - DFTDAC 5'h09 - DFTFRCBEAC 5'h0a - DFTOBS 5'h0c - DFT ASYNC MODE OFF 5'h0d - DFT ASYNC MODE Tx (output) 5'h0e - DFT ASYNC MODE Rx (input) 5'h0f - DFT ASYNC MODE Both (inout) 5'h10 - DFTPISOLoad 5'h12 - DFTEISTRNG
15:8	AAh RW	odftpisodata1_7_0: 8 MSB of alternative data input to PISO Load of this data is enabled when bypdftmode=DFTPISOLoad
7:6	2h RW	odftpisodata0_1_0: 2 LSB of alternative data input to PISO Load of this data is enabled when bypdftmode=DFTPISOLoad
5:3	0h RO	reserved529: reserved
2:0	0h RO	reserved528: reserved

23.14.10 TX_DWORD9 (tx_dword9)—Offset 24h

Access Method


Type: Message Bus Register
(Size: 32 bits)

tx_dword9: [Port: 0xA6] + (880h + 24h)

Op Codes:

0h - Read, 1h - Write

Default: 00430C06h



23.14.11 TX_DWORD10 (tx_dword10)—Offset 28h

Type: Message Bus Register
(Size: 32 bits)

Op Codes:

Intel Atom® Processor E3800 Product Family
Datasheet
3423

23.14.12 TX_DWORD11 (tx_dword11)—Offset 2Ch

31				28				24				20				16				12				8				4				0			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0			
isparead_7_0								reserved532								reserved531								ircvdtctmpout				intpass_3_0							
																								idftcptestsig											
																								idftcrvdetectedtx											
																								idftcrvdetectedtxp											
																				idftcrvdetectedfinished															
																				intfinished															

Bit Range	Default & Access	Description
31:24	X RO	ispareread_7_0: spare reg read
23:16	0h RO	reserved532: reserved
15:10	0h RO	reserved531: reserved
9	0h RO	ircvdtctcmpout: Flash Comparator Output Value
8	X RO	idftcaptestsig: reserved
7	0h RO	idftrcvdetectedtxn: Receive Detect Result for Txn
6	0h RO	idftrcvdetectedtxp: Receive Detect Result for Txp
5	0h RO	idftrcvdetectfinished: Receive Detect Process status
4	X RO	intlfinished: indication of NTL finished
3:0	X RO	intlpass_3_0: the four outputs of NTL test

Access Method


Type: Message Bus Register
(Size: 32 bits)

tx_dword11: [Port: 0xA6] + (880h + 2Ch)

Op Codes:

0h - Read, 1h - Write

Default: 00001000h



Intel Atom® Processor E3800 Product Family
Datasheet
3425




Access Method

tx dword12: [Port: 0xA6] + (880h + 30h)

0h - Read, 1h - Write

31				28				24				20				16				12				8				4				0																							
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0																							
otxcclkbypsel_1_0				ofrcdataaratefit_2_0				odistxflbpin				otxcikampbypsn				otxcikampbypsp				reserved539				odfxanamuxen				odfxanamuxsel_1_0				obs_tx_gated_supply_1_0				reserved538				oobsdigselectupn_3_0				oobsdigselectupp_3_0				oobsdigselectdownn_3_0				oobsdigselectdownp_3_0			

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
29:27	0h RW	ofrcdata rate fit_2_0 : Forces TX data rate 3'b0XX - don't force a value. get it from the I/F pin 3'b100 - no divide (2UIs per clock cyc) 3'b101 - divide by 2 3'b110 - divide by 4 3'b111 - divide by 8 - used also for bypassing with other clocks
26	0h RW	odistxfelbpin : when asserted - disables the i_txfelben pin at the interface and force it 0. (needed in case the pin is asserted in KX or sata1 mode)
25	0h RW	otxcikampbypsn : 0': Normal operation '1': Enable of the passgate connected from the analog clock N to the control of the DC correction cell. The feedback OTA is disabled.
24	0h RW	otxcikampbypsp : 0': Normal operation '1': Enable of the passgate connected from the analog clock P to the control of the DC correction cell. The feedback OTA is disabled.
23	0h RO	reserved539 : reserved
22	0h RW	odfxanamuxen : Enables analog signals probing mux out. When enabled the Vref of Tx-detect-Rx circuit is observed. Note that only one lane is allowed to have the analog mux enabled to avoid collisions.
21:20	0h RW	odfxanamuxsel_1_0 : selects analog signal to be sent to analog port in common lane. This bus has no affect at all currently because there is only one analog signal for observation which is observed by odfxanamuxen
19:18	0h RW	obs_tx_gated_supply_1_0 : Monitor gated vcc supply to Tx upar
17:16	0h RO	reserved538 : reserved
15:12	0h RW	oobsdigselectupn_3_0 : selects data to be sent to observability port output 'o_obsup_nsg'. Same mapping as oobsdigselectdownn[3:0]
11:8	0h RW	oobsdigselectupp_3_0 : selects data to be sent to observability port output 'o_obsup_psg'. Same mapping as oobsdigselectdownp[3:0]
7:4	0h RW	oobsdigselectdownn_3_0 : Reserved.
3:0	0h RW	oobsdigselectdownp_3_0 : Reserved.

23.14.14 TX_DWORD13 (tx_dword13)—Offset 34h

Access Method

Type: Message Bus Register
(Size: 32 bits)


tx_dword13: [Port: 0xA6] + (880h + 34h)

Op Codes:

0h - Read, 1h - Write

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved543	ir2short3_5_0	reserved542	ir2short0_5_0	reserved541	ir1main3_6_0	reserved540	ir1main0_6_0	



Bit Range	Default & Access	Description
31:30	0h RO	reserved543: reserved
29:24	X RO	ir2short3_5_0: The slices used in R2 for DE (sub-DE in 3tap FIR) (PstC=Y,C=Y,PreC=Y)
23:22	0h RO	reserved542: reserved
21:16	X RO	ir2short0_5_0: The slices used in R2 for FS (sub-FS in 3tap FIR) (PstC=Y,C=Y,PreC=X)
15	0h RO	reserved541: reserved
14:8	X RO	ir1main3_6_0: The slices used in R1 for DE (sub-DE in 3tap FIR) (PstC=Y,C=Y,PreC=Y)
7	0h RO	reserved540: reserved
6:0	X RO	ir1main0_6_0: The slices used in R1 for FS (sub-FS in 3tap FIR) (PstC=Y,C=Y,PreC=X)

23.14.15 TX_DWORD14 (tx_dword14)—Offset 38h

Access Method

Type: Message Bus Register
(Size: 32 bits)

tx_dword14: [Port: 0xA6] + (880h + 38h)

Op Codes:

0h - Read, 1h - Write

Default: 00400000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
ospare1_1_0	osimmode	ontlmodepin2pin	ofrcdatapathdis	ofrcdatapathen	ofrcdrvbydpdis	ofrcdrvbyopen	odfttxclkcaptesten	otxdccbyps_i
			ofrcnmos32ldv_2_0	ofrcpmos32ldv_2_0	visa_en	ovisa1_clkssel_2_0	ovisa1_lanese1_3_0	ovisa_bypass
							ovisa0_clkssel_2_0	ovisa0_lanese1_3_0

Bit Range	Default & Access	Description
31:30	0h RW	ospare1_1_0: reserved
29	0h RW	osimmode: Counter threshold of receive-detect, NTL, strong-common-mode is shortened dramatically for fast simulation porpuses. (does not impose risk to circuitly but electrical spec will not met)
28	0h RW	ontlmodepin2pin: 0 - NTL procedure will be done per pad while both pads are pulled to the same rail. 1 - NTL procedure will be done per pad while the pads are pulled to opposite rails.
27	0h RW	ofrcdatapathdis: DFT feature to optionally be used with other registers

Bit Range	Default & Access	Description
26	0h RW	ofrcdatapathen: DFT feature to optionally be used with other registers
25	0h RW	ofrcdrvbydis: DFT feature to optionally be used with other registers
24	0h RW	ofrcdrvbypen: DFT feature to optionally be used with other registers
23	0h RW	odfttxclkcaptesten: Enables the finger capacitor quality check in the DCC block in Tx-clock block. The test is for shorts between the capacitor terminals.
22	1h RW	otxdccbyps_l: Tx DCC Bypass Override Puts DCC (duty cycle correction) circuit in bypass mode 0 - clock's duty cycle is not fixed
21:19	0h RW	ofrcnmos32idv_2_0: change the value iabut_idvpms32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
18:16	0h RW	ofrcpms32idv_2_0: change the value iabut_idvpms32_h[1:0] pushes to txclk 3'b0?? - don't affect the idv comp 3'b100 - pull the idv information to be always at slow 3'b101 - pull the idv information a bit slower. 3'b110 - pull the idv information a bit faster. 3'b111 - pull the idv information to be always at fast
15	0h RW	visa_en: VISA Enable for the Tx VISA logic
14:12	0h RW	ovisa1_clkssel_2_0: VISA Clock Select for Lane1. Selects the source synchronous clock to be used for data being sent on lane1.
11:8	0h RW	ovisa1_lanesel_3_0: VISA Lane Select for Lane1. Selects the byte of data to be sent out on lane1.
7	0h RW	ovisa_bypass: VISA Bypass. Allows for signals to be passed asynchronously through VISA block. Applies to both lane0 and lane1. 0 : Flop signals in local VISA block (default) 1 : Bypass flops in local VISA block
6:4	0h RW	ovisa0_clkssel_2_0: VISA Clock Select for Lane0. Selects the source synchronous clock to be used for data being sent on lane0.
3:0	0h RW	ovisa0_lanesel_3_0: VISA Lane Select for Lane0. Selects data byte to be driven out of VISA-0 byte. Can be either clocked or unclocked data



Access Method

tx dword16: [Port: 0xA6] + (880h + 40h)

Op Codes:

0h - Read, 1h - Write

Default: 00008A00h

Bit Range	Default & Access	Description
31:24	0h RO	reserved554: reserved
23:16	0h RO	reserved553: reserved
15:13	4h RW	ocurcomp0ei_2_0: current consumed (typically) 00X - 0.0mA - not active 01X - 0.9mA 10X - 1.8mA 11X - 2.7mA
12	0h RO	reserved552: reserved




Bit Range	Default & Access	Description
11:10	2h RW	omediumcmpadn_1_0: During P0-EI pad-N will be on medium strength CM and will cause the following current consumption: 00 - 0.00mA (disable) 01 - 2.45mA 10 - 4.87mA 11 - 9.73mA
9:8	2h RW	omediumcmpadp_1_0: During P0-EI pad-P will be on medium strength CM and will cause the following current consumption: 00 - 0.00mA (disable) 01 - 2.45mA 10 - 4.87mA 11 - 9.73mA
7:4	0h RW	ospare3_3_0: 4 spare CRI register bits
3:0	0h RW	ospare2_3_0: 4 spare CRI register bits

24 Serial IO (SIO) Overview

The Serial I/O (SIO) is a collection of hardware blocks that implement simple but key serial I/O interfaces for platform usage. These hardware blocks include:

- SIO - I²C Interface
- SIO - High Speed UART
- SIO - Serial Peripheral Interface (SPI)
- SIO - Pulse Width Modulation (PWM)



24.1 Serial I/O (SIO) Register Map

Refer to [Chapter 3, "Register Access Methods"](#) and [Chapter 4, "Mapping Address Spaces"](#) for additional information.

§



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				MULFNDEV	HEADERTYPE			
					LATTIMER			
					CACHELINE_SIZE			

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

24.2.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR						SIZEINDICATOR	PREFETCHABLE	TYPE
								MESSAGE_SPACE

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.



Bit Range	Default & Access	Field Name (ID): Description
2:1	0h RO	Type (TYPE): 00 indicates BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE): 0. Indicates this BAR is present in the memory space.

24.2.6 Base Address Register 1 (BAR1)—Offset 14h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:0] + 14h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		
PREFETCHABLE1			TYPE1			MESSAGE_SPACE1		

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address Register 1 (BASEADDR1): BAR1 of the LP10 device.
11:4	00h RO	SIZEINDICATOR1: Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE1): Indicates that this BAR is not.
2:1	0h RO	Type (TYPE1): 00 Indicates BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE1): 0. Indicates this BAR is present in the memory space.

24.2.7 Subsystem Vendor and Subsystem ID (SUBSYSTEMID)—Offset 2Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:0] + 2Ch

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SUBSYSTEMID				SUBSYSTEMVENDORID				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW/O	Subsystem ID (SUBSYSTEMID): This register should be implemented for any function that could be instantiated more than once in a given system. The SID register, in combination with the Subsystem Vendor ID register, make it possible for the operating environment to distinguish one audio subsystem from the other. This register is a Read Write Once type register.
15:0	0000h RW/O	Subsystem Vendor ID (SUBSYSTEMVENDORID): This register should be implemented for any function that could be instantiated more than once in a given system. The SVID register, in combination with the Subsystem ID register, enables the operating environment to distinguish one subsystem from the other. This register is a Read Write Once register.

24.2.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:0] + 30h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSION_ROM_BASE								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	EXPANSION_ROM_BASE: Reserved.

24.2.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:0] + 34h



Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
PMESUPPORT				Reserved0				POWER_CAP

Bit Range	Default & Access	Field Name (ID): Description
31:27	00h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. - bit(11) X XXX1b - PME# can be asserted from D0. - bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. - bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. - bit(14) X 1XXXb - PME# can be asserted from D3hot. - bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the strap strap_pme_support.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.

24.2.12 PME Control and Status Register (PMECTRLSTATUS)—Offset 84h

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:0] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				PMESTATUS	Reserved1	PMEENABLE	Reserved2	NO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.



Access Method

Offset: [B:0, D:30, F:0] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
MANID								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



24.3 SIO DMA Memory Mapped I/O Registers for SPI, HSUART, PWM

Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"Source Address Register for Channel 0 - Low (SAR0_LO)—Offset 0h" on page 3451	00000000h
4–7h	4	"Source Address Register for Channel 0 - High (SAR0_HI)—Offset 4h" on page 3452	00000000h
8–Bh	4	"Destination Address Register for Channel 0 - Low (DAR0_LO)—Offset 8h" on page 3452	00000000h
C–Fh	4	"Destination Address Register for Channel 0 - High (DAR0_HI)—Offset Ch" on page 3453	00000000h
10–13h	4	"Linked List Pointer Register for Channel 0 - Low (LLP0_LO)—Offset 10h" on page 3453	00000000h
14–17h	4	"Linked List Pointer Register for Channel 0 - High (LLP0_HI)—Offset 14h" on page 3454	00000000h
18–1Bh	4	"Control Register for Channel 0 - Low (CTL0_LO)—Offset 18h" on page 3454	00304801h
1C–1Fh	4	"Control Register for Channel 0 - High (CTL0_HI)—Offset 1Ch" on page 3456	00000002h
20–23h	4	"Source Status Register for Channel 0 - Low (SSTAT0_LO)—Offset 20h" on page 3457	00000000h
24–27h	4	"Source Status Register for Channel 0 - High (SSTAT0_HI)—Offset 24h" on page 3457	00000000h
28–2Bh	4	"Dest Status Register for Channel 0 - Low (DSTAT0_LO)—Offset 28h" on page 3458	00000000h
2C–2Fh	4	"Dest Status Register for Channel 0 - High (DSTAT0_HI)—Offset 2Ch" on page 3458	00000000h
30–33h	4	"Source Status Address Register for Channel 0 - Low (SSTATAR0_LO)—Offset 30h" on page 3459	00000000h
34–37h	4	"Source Status Address Register for Channel 0 - High (SSTATAR0_HI)—Offset 34h" on page 3459	00000000h
38–3Bh	4	"Dest Status Address Register for Channel 0 - Low (DSTATAR0_LO)—Offset 38h" on page 3460	00000000h
3C–3Fh	4	"Dest Status Address Register for Channel 0 - High (DSTATAR0_HI)—Offset 3Ch" on page 3460	00000000h
40–43h	4	"Configuration Register for Channel 0 - Low (CFG0_LO)—Offset 40h" on page 3461	00000E00h
44–47h	4	"Configuration Register for Channel 0 - High (CFG0_HI)—Offset 44h" on page 3462	00000004h
48–4Bh	4	"Source Gather Register for Channel 0 - Low (SGR0_LO)—Offset 48h" on page 3463	00000000h
4C–4Fh	4	"Source Gather Register for Channel 0 - High (SGR0_HI)—Offset 4Ch" on page 3464	00000000h
50–53h	4	"Destination Scatter Register for Channel 0 - Low (DSR0_LO)—Offset 50h" on page 3464	00000000h
54–57h	4	"Dest Scatter Register for Channel 0 - High (DSR0_HI)—Offset 54h" on page 3465	00000000h
58–5Bh	4	"Source Address Register for Channel 1 - Low (SAR1_LO)—Offset 58h" on page 3465	00000000h

**Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR (Continued)**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
5C–5Fh	4	"Source Address Register for Channel 1 - High (SAR1_HI)—Offset 5Ch" on page 3465	00000000h
60–63h	4	"Destination Address Register for Channel 1 - Low (DAR1_LO)—Offset 60h" on page 3466	00000000h
64–67h	4	"Destination Address Register for Channel 1 - High (DAR1_HI)—Offset 64h" on page 3466	00000000h
68–6Bh	4	"Linked List Pointer Register for Channel 1 - Low (LLP1_LO)—Offset 68h" on page 3467	00000000h
6C–6Fh	4	"Linked List Pointer Register for Channel 1 - High (LLP1_HI)—Offset 6Ch" on page 3467	00000000h
70–73h	4	"Control Register for Channel 1 - Low (CTL1_LO)—Offset 70h" on page 3468	00304801h
74–77h	4	"Control Register for Channel 1 - High (CTL1_HI)—Offset 74h" on page 3469	00000002h
78–7Bh	4	"Source Status Register for Channel 1 - Low (SSTAT1_LO)—Offset 78h" on page 3470	00000000h
7C–7Fh	4	"Source Status Register for Channel 1 - High (SSTAT1_HI)—Offset 7Ch" on page 3470	00000000h
80–83h	4	"Dest Status Register for Channel 1 - Low (DSTAT1_LO)—Offset 80h" on page 3471	00000000h
84–87h	4	"Dest Status Register for Channel 1 - High (DSTAT1_HI)—Offset 84h" on page 3471	00000000h
88–8Bh	4	"Source Status Address Register for Channel 1 - Low (SSTATAR1_LO)—Offset 88h" on page 3472	00000000h
8C–8Fh	4	"Source Status Address Register for Channel 1 - High (SSTATAR1_HI)—Offset 8Ch" on page 3472	00000000h
90–93h	4	"Dest Status Address Register for Channel 1 - Low (DSTATAR1_LO)—Offset 90h" on page 3473	00000000h
94–97h	4	"Dest Status Address Register for Channel 1 - High (DSTATAR1_HI)—Offset 94h" on page 3473	00000000h
98–9Bh	4	"Configuration Register for Channel 1 - Low (CFG1_LO)—Offset 98h" on page 3473	00000E20h
9C–9Fh	4	"Configuration Register for Channel 1 - High (CFG1_HI)—Offset 9Ch" on page 3475	00000004h
A0–A3h	4	"Source Gather Register for Channel 1 - Low (SGR1_LO)—Offset A0h" on page 3476	00000000h
A4–A7h	4	"Source Gather Register for Channel 1 - High (SGR1_HI)—Offset A4h" on page 3476	00000000h
A8–ABh	4	"Destination Scatter Register for Channel 1 - Low (DSR1_LO)—Offset A8h" on page 3477	00000000h
AC–AFh	4	"Dest Scatter Register for Channel 1 - High (DSR1_HI)—Offset ACh" on page 3477	00000000h
B0–B3h	4	"Source Address Register for Channel 2 - Low (SAR2_LO)—Offset B0h" on page 3478	00000000h
B4–B7h	4	"Source Address Register for Channel 2 - High (SAR2_HI)—Offset B4h" on page 3478	00000000h
B8–BBh	4	"Destination Address Register for Channel 2 - Low (DAR2_LO)—Offset B8h" on page 3478	00000000h
BC–BFh	4	"Destination Address Register for Channel 2 - High (DAR2_HI)—Offset BCh" on page 3479	00000000h



Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
C0–C3h	4	"Linked List Pointer Register for Channel 2 - Low (LLP2_LO)—Offset C0h" on page 3479	00000000h
C4–C7h	4	"Linked List Pointer Register for Channel 2 - High (LLP2_HI)—Offset C4h" on page 3480	00000000h
C8–CBh	4	"Control Register for Channel 2 - Low (CTL2_LO)—Offset C8h" on page 3480	00304801h
CC–CFh	4	"Control Register for Channel 2 - High (CTL2_HI)—Offset CCh" on page 3482	00000002h
D0–D3h	4	"Source Status Register for Channel 2 - Low (SSTAT2_LO)—Offset D0h" on page 3482	00000000h
D4–D7h	4	"Source Status Register for Channel 2 - High (SSTAT2_HI)—Offset D4h" on page 3483	00000000h
D8–DBh	4	"Dest Status Register for Channel 2 - Low (DSTAT2_LO)—Offset D8h" on page 3483	00000000h
DC–DFh	4	"Dest Status Register for Channel 2 - High (DSTAT2_HI)—Offset DCh" on page 3484	00000000h
E0–E3h	4	"Source Status Address Register for Channel 2 - Low (SSTATAR2_LO)—Offset E0h" on page 3484	00000000h
E4–E7h	4	"Source Status Address Register for Channel 2 - High (SSTATAR2_HI)—Offset E4h" on page 3485	00000000h
E8–EBh	4	"Dest Status Address Register for Channel 2 - Low (DSTATAR2_LO)—Offset E8h" on page 3485	00000000h
EC–EFh	4	"Dest Status Address Register for Channel 2 - High (DSTATAR2_HI)—Offset ECh" on page 3486	00000000h
F0–F3h	4	"Configuration Register for Channel 2 - Low (CFG2_LO)—Offset F0h" on page 3486	00000E40h
F4–F7h	4	"Configuration Register for Channel 2 - High (CFG2_HI)—Offset F4h" on page 3487	00000004h
F8–FBh	4	"Source Gather Register for Channel 2 - Low (SGR2_LO)—Offset F8h" on page 3488	00000000h
FC–FFh	4	"Source Gather Register for Channel 2 - High (SGR2_HI)—Offset FCh" on page 3489	00000000h
100–103h	4	"Destination Scatter Register for Channel 2 - Low (DSR2_LO)—Offset 100h" on page 3489	00000000h
104–107h	4	"Dest Scatter Register for Channel 2 - High (DSR2_HI)—Offset 104h" on page 3490	00000000h
108–10Bh	4	"Source Address Register for Channel 3 - Low (SAR3_LO)—Offset 108h" on page 3490	00000000h
10C–10Fh	4	"Source Address Register for Channel 3 - High (SAR3_HI)—Offset 10Ch" on page 3491	00000000h
110–113h	4	"Destination Address Register for Channel 3 - Low (DAR3_LO)—Offset 110h" on page 3491	00000000h
114–117h	4	"Destination Address Register for Channel 3 - High (DAR3_HI)—Offset 114h" on page 3492	00000000h
118–11Bh	4	"Linked List Pointer Register for Channel 3 - Low (LLP3_LO)—Offset 118h" on page 3492	00000000h
11C–11Fh	4	"Linked List Pointer Register for Channel 3 - High (LLP3_HI)—Offset 11Ch" on page 3493	00000000h
120–123h	4	"Control Register for Channel 3 - Low (CTL3_LO)—Offset 120h" on page 3493	00304801h
124–127h	4	"Control Register for Channel 3 - High (CTL3_HI)—Offset 124h" on page 3495	00000002h



Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
128–12Bh	4	"Source Status Register for Channel 3 - Low (SSTAT3_LO)—Offset 128h" on page 3495	00000000h
12C–12Fh	4	"Source Status Register for Channel 3 - High (SSTAT3_HI)—Offset 12Ch" on page 3496	00000000h
130–133h	4	"Dest Status Register for Channel 3 - Low (DSTAT3_LO)—Offset 130h" on page 3496	00000000h
134–137h	4	"Dest Status Register for Channel 3 - High (DSTAT3_HI)—Offset 134h" on page 3497	00000000h
138–13Bh	4	"Source Status Address Register for Channel 3 - Low (SSTATAR3_LO)—Offset 138h" on page 3497	00000000h
13C–13Fh	4	"Source Status Address Register for Channel 3 - High (SSTATAR3_HI)—Offset 13Ch" on page 3498	00000000h
140–143h	4	"Dest Status Address Register for Channel 3 - Low (DSTATAR3_LO)—Offset 140h" on page 3498	00000000h
144–147h	4	"Dest Status Address Register for Channel 3 - High (DSTATAR3_HI)—Offset 144h" on page 3499	00000000h
148–14Bh	4	"Configuration Register for Channel 3 - Low (CFG3_LO)—Offset 148h" on page 3499	00000E60h
14C–14Fh	4	"Configuration Register for Channel 3 - High (CFG3_HI)—Offset 14Ch" on page 3500	00000004h
150–153h	4	"Source Gather Register for Channel 3 - Low (SGR3_LO)—Offset 150h" on page 3501	00000000h
154–157h	4	"Source Gather Register for Channel 3 - High (SGR3_HI)—Offset 154h" on page 3502	00000000h
158–15Bh	4	"Destination Scatter Register for Channel 3 - Low (DSR3_LO)—Offset 158h" on page 3502	00000000h
15C–15Fh	4	"Dest Scatter Register for Channel 3 - High (DSR3_HI)—Offset 15Ch" on page 3503	00000000h
160–163h	4	"Source Address Register for Channel 4 - Low (SAR4_LO)—Offset 160h" on page 3503	00000000h
164–167h	4	"Source Address Register for Channel 4 - High (SAR4_HI)—Offset 164h" on page 3504	00000000h
168–16Bh	4	"Destination Address Register for Channel 4 - Low (DAR4_LO)—Offset 168h" on page 3504	00000000h
16C–16Fh	4	"Destination Address Register for Channel 4 - High (DAR4_HI)—Offset 16Ch" on page 3505	00000000h
170–173h	4	"Linked List Pointer Register for Channel 4 - Low (LLP4_LO)—Offset 170h" on page 3505	00000000h
174–177h	4	"Linked List Pointer Register for Channel 4 - High (LLP4_HI)—Offset 174h" on page 3506	00000000h
178–17Bh	4	"Control Register for Channel 4 - Low (CTL4_LO)—Offset 178h" on page 3506	00304801h
17C–17Fh	4	"Control Register for Channel 4 - High (CTL4_HI)—Offset 17Ch" on page 3507	00000002h
180–183h	4	"Source Status Register for Channel 4 - Low (SSTAT4_LO)—Offset 180h" on page 3508	00000000h
184–187h	4	"Source Status Register for Channel 4 - High (SSTAT4_HI)—Offset 184h" on page 3508	00000000h
188–18Bh	4	"Dest Status Register for Channel 4 - Low (DSTAT4_LO)—Offset 188h" on page 3509	00000000h



Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
18C–18Fh	4	"Dest Status Register for Channel 4 - High (DSTAT4_HI)—Offset 18Ch" on page 3509	00000000h
190–193h	4	"Source Status Address Register for Channel 4 - Low (SSTATAR4_LO)—Offset 190h" on page 3510	00000000h
194–197h	4	"Source Status Address Register for Channel 4 - High (SSTATAR4_HI)—Offset 194h" on page 3510	00000000h
198–19Bh	4	"Dest Status Address Register for Channel 4 - Low (DSTATAR4_LO)—Offset 198h" on page 3511	00000000h
19C–19Fh	4	"Dest Status Address Register for Channel 4 - High (DSTATAR4_HI)—Offset 19Ch" on page 3511	00000000h
1A0–1A3h	4	"Configuration Register for Channel 4 - Low (CFG4_LO)—Offset 1A0h" on page 3512	00000E80h
1A4–1A7h	4	"Configuration Register for Channel 4 - High (CFG4_HI)—Offset 1A4h" on page 3513	00000004h
1A8–1ABh	4	"Source Gather Register for Channel 4 - Low (SGR4_LO)—Offset 1A8h" on page 3514	00000000h
1AC–1AFh	4	"Source Gather Register for Channel 4 - High (SGR4_HI)—Offset 1ACh" on page 3515	00000000h
1B0–1B3h	4	"Destination Scatter Register for Channel 4 - Low (DSR4_LO)—Offset 1B0h" on page 3515	00000000h
1B4–1B7h	4	"Dest Scatter Register for Channel 4 - High (DSR4_HI)—Offset 1B4h" on page 3515	00000000h
1B8–1BBh	4	"Source Address Register for Channel 5 - Low (SAR5_LO)—Offset 1B8h" on page 3516	00000000h
1BC–1BFh	4	"Source Address Register for Channel 5 - High (SAR5_HI)—Offset 1BCh" on page 3516	00000000h
1C0–1C3h	4	"Destination Address Register for Channel 5 - Low (DAR5_LO)—Offset 1C0h" on page 3517	00000000h
1C4–1C7h	4	"Destination Address Register for Channel 5 - High (DAR5_HI)—Offset 1C4h" on page 3517	00000000h
1C8–1CBh	4	"Linked List Pointer Register for Channel 5 - Low (LLP5_LO)—Offset 1C8h" on page 3518	00000000h
1CC–1CFh	4	"Linked List Pointer Register for Channel 5 - High (LLP5_HI)—Offset 1CCh" on page 3518	00000000h
1D0–1D3h	4	"Control Register for Channel 5 - Low (CTL5_LO)—Offset 1D0h" on page 3519	00304801h
1D4–1D7h	4	"Control Register for Channel 5 - High (CTL5_HI)—Offset 1D4h" on page 3520	00000002h
1D8–1DBh	4	"Source Status Register for Channel 5 - Low (SSTAT5_LO)—Offset 1D8h" on page 3521	00000000h
1DC–1DFh	4	"Source Status Register for Channel 5 - High (SSTAT5_HI)—Offset 1DCh" on page 3521	00000000h
1E0–1E3h	4	"Dest Status Register for Channel 5 - Low (DSTAT5_LO)—Offset 1E0h" on page 3522	00000000h
1E4–1E7h	4	"Dest Status Register for Channel 5 - High (DSTAT5_HI)—Offset 1E4h" on page 3522	00000000h
1E8–1EBh	4	"Source Status Address Register for Channel 5 - Low (SSTATAR5_LO)—Offset 1E8h" on page 3523	00000000h
1EC–1EFh	4	"Source Status Address Register for Channel 5 - High (SSTATAR5_HI)—Offset 1ECh" on page 3523	00000000h

**Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR (Continued)**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
1F0–1F3h	4	"Dest Status Address Register for Channel 5 - Low (DSTATAR5_LO)—Offset 1F0h" on page 3524	00000000h
1F4–1F7h	4	"Dest Status Address Register for Channel 5 - High (DSTATAR5_HI)—Offset 1F4h" on page 3524	00000000h
1F8–1FBh	4	"Configuration Register for Channel 5 - Low (CFG5_LO)—Offset 1F8h" on page 3524	00000EA0h
1FC–1FFh	4	"Configuration Register for Channel 5 - High (CFG5_HI)—Offset 1FCh" on page 3526	00000004h
200–203h	4	"Source Gather Register for Channel 5 - Low (SGR5_LO)—Offset 200h" on page 3527	00000000h
204–207h	4	"Source Gather Register for Channel 5 - High (SGR5_HI)—Offset 204h" on page 3527	00000000h
208–20Bh	4	"Destination Scatter Register for Channel 5 - Low (DSR5_LO)—Offset 208h" on page 3528	00000000h
20C–20Fh	4	"Dest Scatter Register for Channel 5 - High (DSR5_HI)—Offset 20Ch" on page 3528	00000000h
210–213h	4	"Source Address Register for Channel 6 - Low (SAR6_LO)—Offset 210h" on page 3529	00000000h
214–217h	4	"Source Address Register for Channel 6 - High (SAR6_HI)—Offset 214h" on page 3529	00000000h
218–21Bh	4	"Destination Address Register for Channel 6 - Low (DAR6_LO)—Offset 218h" on page 3530	00000000h
21C–21Fh	4	"Destination Address Register for Channel 6 - High (DAR6_HI)—Offset 21Ch" on page 3530	00000000h
220–223h	4	"Linked List Pointer Register for Channel 6 - Low (LLP6_LO)—Offset 220h" on page 3531	00000000h
224–227h	4	"Linked List Pointer Register for Channel 6 - High (LLP6_HI)—Offset 224h" on page 3531	00000000h
228–22Bh	4	"Control Register for Channel 6 - Low (CTL6_LO)—Offset 228h" on page 3532	00304801h
22C–22Fh	4	"Control Register for Channel 6 - High (CTL6_HI)—Offset 22Ch" on page 3533	00000002h
230–233h	4	"Source Status Register for Channel 6 - Low (SSTAT6_LO)—Offset 230h" on page 3534	00000000h
234–237h	4	"Source Status Register for Channel 6 - High (SSTAT6_HI)—Offset 234h" on page 3534	00000000h
238–23Bh	4	"Dest Status Register for Channel 6 - Low (DSTAT6_LO)—Offset 238h" on page 3535	00000000h
23C–23Fh	4	"Dest Status Register for Channel 6 - High (DSTAT6_HI)—Offset 23Ch" on page 3535	00000000h
240–243h	4	"Source Status Address Register for Channel 6 - Low (SSTATAR6_LO)—Offset 240h" on page 3536	00000000h
244–247h	4	"Source Status Address Register for Channel 6 - High (SSTATAR6_HI)—Offset 244h" on page 3536	00000000h
248–24Bh	4	"Dest Status Address Register for Channel 6 - Low (DSTATAR6_LO)—Offset 248h" on page 3537	00000000h
24C–24Fh	4	"Dest Status Address Register for Channel 6 - High (DSTATAR6_HI)—Offset 24Ch" on page 3537	00000000h
250–253h	4	"Configuration Register for Channel 6 - Low (CFG6_LO)—Offset 250h" on page 3538	00000EC0h



Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
254–257h	4	"Configuration Register for Channel 6 - High (CFG6_HI)—Offset 254h" on page 3539	00000004h
258–25Bh	4	"Source Gather Register for Channel 6 - Low (SGR6_LO)—Offset 258h" on page 3540	00000000h
25C–25Fh	4	"Source Gather Register for Channel 6 - High (SGR6_HI)—Offset 25Ch" on page 3540	00000000h
260–263h	4	"Destination Scatter Register for Channel 6 - Low (DSR6_LO)—Offset 260h" on page 3541	00000000h
264–267h	4	"Dest Scatter Register for Channel 6 - High (DSR6_HI)—Offset 264h" on page 3541	00000000h
268–26Bh	4	"Source Address Register for Channel 7 - Low (SAR7_LO)—Offset 268h" on page 3542	00000000h
26C–26Fh	4	"Source Address Register for Channel 7 - High (SAR7_HI)—Offset 26Ch" on page 3542	00000000h
270–273h	4	"Destination Address Register for Channel 7 - Low (DAR7_LO)—Offset 270h" on page 3543	00000000h
274–277h	4	"Destination Address Register for Channel 7 - High (DAR7_HI)—Offset 274h" on page 3543	00000000h
278–27Bh	4	"Linked List Pointer Register for Channel 7 - Low (LLP7_LO)—Offset 278h" on page 3544	00000000h
27C–27Fh	4	"Linked List Pointer Register for Channel 7 - High (LLP7_HI)—Offset 27Ch" on page 3544	00000000h
280–283h	4	"Control Register for Channel 7 - Low (CTL7_LO)—Offset 280h" on page 3545	00304801h
284–287h	4	"Control Register for Channel 7 - High (CTL7_HI)—Offset 284h" on page 3546	00000002h
288–28Bh	4	"Source Status Register for Channel 7 - Low (SSTAT7_LO)—Offset 288h" on page 3547	00000000h
28C–28Fh	4	"Source Status Register for Channel 7 - High (SSTAT7_HI)—Offset 28Ch" on page 3547	00000000h
290–293h	4	"Dest Status Register for Channel 7 - Low (DSTAT7_LO)—Offset 290h" on page 3548	00000000h
294–297h	4	"Dest Status Register for Channel 7 - High (DSTAT7_HI)—Offset 294h" on page 3548	00000000h
298–29Bh	4	"Source Status Address Register for Channel 7 - Low (SSTATAR7_LO)—Offset 298h" on page 3549	00000000h
29C–29Fh	4	"Source Status Address Register for Channel 7 - High (SSTATAR7_HI)—Offset 29Ch" on page 3549	00000000h
2A0–2A3h	4	"Dest Status Address Register for Channel 7 - Low (DSTATAR7_LO)—Offset 2A0h" on page 3550	00000000h
2A4–2A7h	4	"Dest Status Address Register for Channel 7 - High (DSTATAR7_HI)—Offset 2A4h" on page 3550	00000000h
2A8–2ABh	4	"Configuration Register for Channel 7 - Low (CFG7_LO)—Offset 2A8h" on page 3551	00000EE0h
2AC–2AFh	4	"Configuration Register for Channel 7 - High (CFG7_HI)—Offset 2ACh" on page 3552	00000004h
2B0–2B3h	4	"Source Gather Register for Channel 7 - Low (SGR7_LO)—Offset 2B0h" on page 3553	00000000h
2B4–2B7h	4	"Source Gather Register for Channel 7 - High (SGR7_HI)—Offset 2B4h" on page 3553	00000000h




Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
2B8–2BBh	4	"Destination Scatter Register for Channel 7 - Low (DSR7_LO)—Offset 2B8h" on page 3554	00000000h
2BC–2BFh	4	"Dest Scatter Register for Channel 7 - High (DSR7_HI)—Offset 2BCh" on page 3554	00000000h
2C0–2C3h	4	"Interrupt Raw Status Registers - Low (RawTfr_LO)—Offset 2C0h" on page 3555	00000000h
2C4–2C7h	4	"Interrupt Raw Status Registers - High (RawTfr_HI)—Offset 2C4h" on page 3556	00000000h
2C8–2CBh	4	"Interrupt Raw Status Registers - Low (RawBlock_LO)—Offset 2C8h" on page 3556	00000000h
2CC–2CFh	4	"Interrupt Raw Status Registers - High (RawBlock_HI)—Offset 2CCh" on page 3557	00000000h
2D0–2D3h	4	"Interrupt Raw Status Registers - Low (RawSrcTran_LO)—Offset 2D0h" on page 3557	00000000h
2D4–2D7h	4	"Interrupt Raw Status Registers - High (RawSrcTran_HI)—Offset 2D4h" on page 3558	00000000h
2D8–2DBh	4	"Interrupt Raw Status Registers - Low (RawDstTran_LO)—Offset 2D8h" on page 3558	00000000h
2DC–2DFh	4	"Interrupt Raw Status Registers - High (RawDstTran_HI)—Offset 2DCh" on page 3559	00000000h
2E0–2E3h	4	"Interrupt Raw Status Registers - Low (RawErr_LO)—Offset 2E0h" on page 3559	00000000h
2E4–2E7h	4	"Interrupt Raw Status Registers - High (RawErr_HI)—Offset 2E4h" on page 3560	00000000h
2E8–2EBh	4	"Interrupt Status Registers - Low (StatusTfr_LO)—Offset 2E8h" on page 3560	00000000h
2EC–2EFh	4	"Interrupt Status Registers - High (StatusTfr_HI)—Offset 2ECh" on page 3561	00000000h
2F0–2F3h	4	"Interrupt Status Registers - Low (StatusBlock_LO)—Offset 2F0h" on page 3561	00000000h
2F4–2F7h	4	"Interrupt Status Registers - High (StatusBlock_HI)—Offset 2F4h" on page 3562	00000000h
2F8–2FBh	4	"Interrupt Status Registers - Low (StatusSrcTran_LO)—Offset 2F8h" on page 3562	00000000h
2FC–2FFh	4	"Interrupt Status Registers - High (StatusSrcTran_HI)—Offset 2FCh" on page 3563	00000000h
300–303h	4	"Interrupt Status Registers - Low (StatusDstTran_LO)—Offset 300h" on page 3563	00000000h
304–307h	4	"Interrupt Status Registers - High (StatusDstTran_HI)—Offset 304h" on page 3564	00000000h
308–30Bh	4	"Interrupt Status Registers - Low (StatusErr_LO)—Offset 308h" on page 3564	00000000h
30C–30Fh	4	"Interrupt Status Registers - High (StatusErr_HI)—Offset 30Ch" on page 3565	00000000h
310–313h	4	"Interrupt Mask Registers - Low (MaskTfr_LO)—Offset 310h" on page 3565	00000000h
314–317h	4	"Interrupt Mask Registers - High (MaskTfr_HI)—Offset 314h" on page 3566	00000000h
318–31Bh	4	"Interrupt Mask Registers - Low (MaskBlock_LO)—Offset 318h" on page 3566	00000000h
31C–31Fh	4	"Interrupt Mask Registers - High (MaskBlock_HI)—Offset 31Ch" on page 3567	00000000h
320–323h	4	"Interrupt Mask Registers - Low (MaskSrcTran_LO)—Offset 320h" on page 3567	00000000h
324–327h	4	"Interrupt Mask Registers - High (MaskSrcTran_HI)—Offset 324h" on page 3568	00000000h
328–32Bh	4	"Interrupt Mask Registers - Low (MaskDstTran_LO)—Offset 328h" on page 3568	00000000h



Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
32C–32Fh	4	"Interrupt Mask Registers - High (MaskDstTran_HI)—Offset 32Ch" on page 3569	00000000h
330–333h	4	"Interrupt Mask Registers - Low (MaskErr_LO)—Offset 330h" on page 3569	00000000h
334–337h	4	"Interrupt Mask Registers - High (MaskErr_HI)—Offset 334h" on page 3570	00000000h
338–33Bh	4	"Interrupt Clear Registers - Low (ClearTfr_LO)—Offset 338h" on page 3570	00000000h
33C–33Fh	4	"Interrupt Clear Registers - High (ClearTfr_HI)—Offset 33Ch" on page 3571	00000000h
340–343h	4	"Interrupt Clear Registers - Low (ClearBlock_LO)—Offset 340h" on page 3572	00000000h
344–347h	4	"Interrupt Clear Registers (ClearBlock_HI)—Offset 344h" on page 3572	00000000h
348–34Bh	4	"Interrupt Clear Registers - Low (ClearSrcTran_LO)—Offset 348h" on page 3573	00000000h
34C–34Fh	4	"Interrupt Clear RegistersClearSrc - High (ClearSrcTran_HI)—Offset 34Ch" on page 3573	00000000h
350–353h	4	"Interrupt Clear Registers - Low (ClearDstTran_LO)—Offset 350h" on page 3574	00000000h
354–357h	4	"Interrupt Clear Registers - High (ClearDstTran_HI)—Offset 354h" on page 3574	00000000h
358–35Bh	4	"Interrupt Clear Registers - Low (ClearErr_LO)—Offset 358h" on page 3575	00000000h
35C–35Fh	4	"Interrupt Clear Registers - High (ClearErr_HI)—Offset 35Ch" on page 3575	00000000h
360–363h	4	"Combined Interrupt Status Register - Low (StatusInt_LO)—Offset 360h" on page 3576	00000000h
364–367h	4	"Combined Interrupt Status Register - High (StatusInt_HI)—Offset 364h" on page 3576	00000000h
368–36Bh	4	"Source Software Transaction Request Register - Low (ReqSrcReg_LO)—Offset 368h" on page 3577	00000000h
36C–36Fh	4	"Source Software Transaction Request Register - High (ReqSrcReg_HI)—Offset 36Ch" on page 3578	00000000h
370–373h	4	"Destination Software Transaction Request Register - Low (ReqDstReg_LO)—Offset 370h" on page 3578	00000000h
374–377h	4	"Destination Software Transaction Request Register - High (ReqDstReg_HI)—Offset 374h" on page 3579	00000000h
378–37Bh	4	"Single Source Software Transaction Request Register - Low (SglRqSrcReg_LO)—Offset 378h" on page 3579	00000000h
37C–37Fh	4	"Single Source Software Transaction Request Register - High (SglRqSrcReg_HI)—Offset 37Ch" on page 3580	00000000h
380–383h	4	"Single Destination Software Transaction Request Register - Low (SglRqDstReg_LO)—Offset 380h" on page 3581	00000000h
384–387h	4	"Single Destination Software Transaction Request Register - High (SglRqDstReg_HI)—Offset 384h" on page 3581	00000000h
388–38Bh	4	"Last Source Transaction Request Register - Low (LstSrcReg_LO)—Offset 388h" on page 3582	00000000h
38C–38Fh	4	"Last Source Transaction Request Register - High (LstSrcReg_HI)—Offset 38Ch" on page 3582	00000000h
390–393h	4	"Last Destination Transaction Request Register - Low (LstDstReg_LO)—Offset 390h" on page 3583	00000000h
394–397h	4	"Last Destination Transaction Request Register - High (LstDstReg_HI)—Offset 394h" on page 3584	00000000h
398–39Bh	4	"DW_ahb_dmac Configuration Register - Low (DmaCfgReg_LO)—Offset 398h" on page 3584	00000000h
39C–39Fh	4	"DW_ahb_dmac Configuration Register - High (DmaCfgReg_HI)—Offset 39Ch" on page 3585	00000000h

**Table 253. Summary of SIO DMA 1 Memory Mapped I/O Registers—BAR (Continued)**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
3A0–3A3h	4	"DW_ahb_dmac Channel Enable Register - Low (ChEnReg_LO)—Offset 3A0h" on page 3585	00000000h
3A4–3A7h	4	"DW_ahb_dmac Channel Enable Register - High (ChEnReg_HI)—Offset 3A4h" on page 3586	00000000h
3A8–3ABh	4	"DW_ahb_dmac ID Register - Low (DmaIdReg_LO)—Offset 3A8h" on page 3586	C0CAC01Ah
3AC–3AFh	4	"DW_ahb_dmac ID Register - High (DmaIdReg_HI)—Offset 3ACh" on page 3587	00000000h
3B0–3B3h	4	"DW_ahb_dmac Test Register - Low (DmaTestReg_LO)—Offset 3B0h" on page 3587	00000000h
3B4–3B7h	4	"DW_ahb_dmac Test Register - High (DmaTestReg_HI)—Offset 3B4h" on page 3588	00000000h
3C8–3CBh	4	"DW_ahb_dmac Component Parameters Register 6 - Low (DMA_COMP_PARAMS_6_LO)—Offset 3C8h" on page 3588	00000000h
3CC–3CFh	4	"DW_ahb_dmac Component Parameters Register 6 - High (DMA_COMP_PARAMS_6_HI)—Offset 3CCh" on page 3589	38220300h
3D0–3D3h	4	"DW_ahb_dmac Component Parameters Register 5 - Low (DMA_COMP_PARAMS_5_LO)—Offset 3D0h" on page 3591	38220300h
3D4–3D7h	4	"DW_ahb_dmac Component Parameters Register 5 - High (DMA_COMP_PARAMS_5_HI)—Offset 3D4h" on page 3594	38220300h
3D8–3DBh	4	"DW_ahb_dmac Component Parameters Register 4 - Low (DMA_COMP_PARAMS_4_LO)—Offset 3D8h" on page 3596	38220300h
3DC–3DFh	4	"DW_ahb_dmac Component Parameters Register 4 - High (DMA_COMP_PARAMS_4_HI)—Offset 3DCh" on page 3599	38220300h
3E0–3E3h	4	"DW_ahb_dmac Component Parameters Register 3 - Low (DMA_COMP_PARAMS_3_LO)—Offset 3E0h" on page 3601	38220300h
3E4–3E7h	4	"DW_ahb_dmac Component Parameters Register 3 - High (DMA_COMP_PARAMS_3_HI)—Offset 3E4h" on page 3604	38220300h
3E8–3EBh	4	"DW_ahb_dmac Component Parameters Register 2 - Low (DMA_COMP_PARAMS_2_LO)—Offset 3E8h" on page 3606	38220300h
3EC–3EFh	4	"DW_ahb_dmac Component Parameters Register 2 - High (DMA_COMP_PARAMS_2_HI)—Offset 3ECh" on page 3608	00000000h
3F0–3F3h	4	"DW_ahb_dmac Component Parameters Register 1 - Low (DMA_COMP_PARAMS_1_LO)—Offset 3F0h" on page 3611	AAAAAAAAh
3F4–3F7h	4	"DW_ahb_dmac Component Parameters Register 1 - High (DMA_COMP_PARAMS_1_HI)—Offset 3F4h" on page 3612	37000F04h
3F8–3FBh	4	"DMA Component ID RegisterDma - Low (DmaCompsID_LO)—Offset 3F8h" on page 3614	44571110h
3FC–3FFh	4	"DMA Component ID Register - High (DmaCompsID_HI)—Offset 3FCh" on page 3615	3231362Ah

24.3.1 Source Address Register for Channel 0 - Low (SAR0_LO)—Offset 0h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current AHB transfer.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SAR

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Source Address of DMA Transfer (SAR): Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.

24.3.2 Source Address Register for Channel 0 - High (SAR0_HI)—Offset 4h

Refer to the description for register Source Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0


Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.3 Destination Address Register for Channel 0 - Low (DAR0_LO)—Offset 8h

The starting destination address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the destination address of the current AHB transfer.

Access Method



24.3.6 Linked List Pointer Register for Channel 0 - High (LLP0_HI)—Offset 14h

Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.7 Control Register for Channel 0 - Low (CTL0_LO)—Offset 18h

Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00304801h



31				28				24				20				16				12				8				4				0																															
0				0				0				0				0				0				1				0				1																															
Undefined_				LLP_SRC_EN				LLP_DST_EN				SMS				DMS				TT_FC				Undefined				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZ				DEST_MSIZ				SINC				DINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RW	Undefined_ : RESERVED
28	0h RW	LLP_SRC_EN : Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPx.LOC is non-zero
27	0h RW	LLP_DST_EN : Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPx.LOC is non-zero.
26:25	0h RW	Source Master Select (SMS) : Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS) : Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC) : The following transfer types are supported. - Memory to Memory - Memory to Peripheral - Peripheral to Memory - Peripheral to Peripheral Flow Control can be assigned to the DW_ahb_dmac, the source peripheral, or the destination peripheral.
19	0h RW	Undefined : RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN) : 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN) : 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ) : Number of data items, each of width CTLx.SRC_TR_WIDTH, to be read from the source every time a source burst transaction request is made from either the corresponding hardware or software handshaking interface.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ) : Number of data items, each of width CTLx.DST_TR_WIDTH, to be written to the destination every time a destination burst transaction request is made from either the corresponding hardware or software handshaking interface.
10:9	0h RW	Source Address Increment (SINC) : 00 = Increment 01 = Decrement 1x = No change



Bit Range	Default & Access	Field Name (ID): Description
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.3.8 Control Register for Channel 0 - High (CTL0_HI)—Offset 1Ch

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000002h

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:13	0h RW	Undefined_ : RESERVED
12	0h RW	Done Bit (DONE) : If status write-back is enabled, the upper word of the control register, CTLx[63:32], is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTLx.DONE bit to see when a block transfer is complete. The LLI CTLx.DONE bit should be cleared when the linked lists are set up in memory, prior to enabling the channel. LLI accesses are always 32-bit accesses (Hsize = 2) aligned to 32-bit boundaries and cannot be changed or programmed to anything other than 32-bit.
11:0	2h RW	Block Transfer Size (BLOCK_TS) : When the DW_ahb_dmac is the flow controller, the user writes this field before the channel is enabled in order to indicate the block size.



24.3.11 Dest Status Register for Channel 0 - Low (DSTAT0_LO)—Offset 28h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register. This status information is then stored in the DSTATx register and written out to the DSTATx register location of the LLI before the start of the next block. For conditions under which the destination status information is fetched, refer to the abovementioned spec.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 28h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest status information retrieved by hw from the addrx pointed to by DSTATAR0 register.

24.3.12 Dest Status Register for Channel 0 - High (DSTAT0_HI)—Offset 2Ch

Refer to the register description for Dest Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



24.3.13 Source Status Address Register for Channel 0 - Low (SSTATAR0_LO)—Offset 30h

After the completion of each block transfer, hardware can retrieve the source status information from the address pointed to by the contents of the SSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.3.14 Source Status Address Register for Channel 0 - High (SSTATAR0_HI)—Offset 34h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



24.3.15 Dest Status Address Register for Channel 0 - Low (DSTATAR0_LO)—Offset 38h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTATAR

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTATAR (SSTATAR): Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.3.16 Dest Status Address Register for Channel 0 - High (DSTATAR0_HI)—Offset 3Ch

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

31				28				24				20				16				12				8				4				0											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0								
Undefined								DEST_PER								SRC_PER								SS_UPD_EN				DS_UPD_EN				PROTCTL				FIFO_MODE				FCMODE			

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
5	0h RW	Destination Status Update Enable (DS_UPD_EN): Destination status information is fetched only from the location pointed to by the DSTATARx register, stored in the DSTATx register and written out to the DSTATx location of the LLI if DS_UPD_EN is high.
4:2	1h RW	PROTCTL: Protection Control bits used to drive the AHB HPROT[3:1] bus.
1	0h RW	FIFO Mode Select (FIFO_MODE): Determines how much space or data needs to be available in the FIFO before a burst transaction request is serviced. 0 = Space/data available for single AHB transfer of the specified transfer width. 1 = Data available is greater than or equal to half the FIFO depth for destination transfers and space available is greater than half the fifo depth for source transfers.
0	0h RW	Flow Control Mode (FCMODE): Determines when source transaction requests are serviced when the Destination Peripheral is the flow controller. 0 = Source transaction requests are serviced when they occur. Data pre-fetching is enabled. 1 = Source transaction requests are not serviced until a destination transaction request occurs.

24.3.19 Source Gather Register for Channel 0 - Low (SGR0_LO)—Offset 48h

The CTLx.SINC field controls whether the address increments or decrements. When the CTLx.SINC field indicates a fixed-address control, then the address remains constant throughout the transfer and the SGRx register is ignored.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SGC				SGI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Specifies the source address increment/decrement in multiples of CTLx.SRC_TR_WIDTH on a gather boundary when gather mode is enabled for the source transfer.



Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

	31		28			24			20			16			12			8			4			0					
	0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0
	Undefined																												

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.21 Destination Scatter Register for Channel 0 - Low (DSR0_LO)—Offset 50h

Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Dest Scatter Count (DSC): Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	Dest Scatter Interval (DSI): Specifies the destination address increment/decrement in multiples of CTLx.DST_TR_WIDTH on a scatter boundary, when scatter mode is enabled for the destination transfer.



Offset: [BAR] + 5Ch

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Memory layout diagram showing a 32-bit address space (0 to 31). The address 16 is marked as 'Undefined'. The memory is divided into 8 groups of 4 bits each, with bit values 0 or 1 indicated in each group.

Address Range	Bit Values
0 - 3	0 0 0 0
4 - 7	0 0 0 0
8 - 11	0 0 0 0
12 - 15	0 0 0 0
16 - 19	0 0 0 0
20 - 23	0 0 0 0
24 - 27	0 0 0 0
28 - 31	0 0 0 0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.25 Destination Address Register for Channel 1 - Low (DAR1_LO)—Offset 60h

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Offset: [BAR] + 60h

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Diagram illustrating the structure of the 32-bit DAR field. The field is divided into eight 4-bit segments, each containing four '0' bits. The segments are labeled with bit positions 31, 28, 24, 20, 16, 12, 8, and 4 from left to right. The label 'DAR' is positioned below the first four segments (bits 31 to 16).

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Destination Address of DMA Transfer (DAR): Updated after each destination transfer. The DINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every destination transfer throughout the block transfer.

24.3.26 Destination Address Register for Channel 1 - High (DAR1_HI)—Offset 64h

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Offset: [BAR] + 64h

BAR Reference: [B:0, D:30, F:0] + 10h

24.3.29 Control Register for Channel 1 - Low (CTL1_LO)—Offset 70h



Bit Range	Default & Access	Field Name (ID): Description
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ): Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Refer to the description for CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.3.30 Control Register for Channel 1 - High (CTL1 HI)—Offset 74h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000002h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
Undefined																DONE				BLOCK_TS															

Bit Range	Default & Access	Field Name (ID): Description
31:13	0h RW	Undefined_ : RESERVED



Refer to the register description for Source Status Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

24.3.32 Source Status Register for Channel 1 - High (SSTAT1_HI)—Offset 7Ch

Refer to the register description for Source Status Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Intel Atom® Processor E3800 Product Family
Datasheet
3470



Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.33 Dest Status Register for Channel 1 - Low (DSTAT1_LO)—Offset 80h

Refer to the register description for Dest Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

DSTAT

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest. status information retrieved by hw from the addrx pointed to by DSTATAR0 register.

24.3.34 Dest Status Register for Channel 1 - High (DSTAT1_HI)—Offset 84h

Refer to the register description for Dest Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 84h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Diagram illustrating the structure of a 32-bit register, divided into eight 4-bit nibbles. The nibbles are labeled 31, 28, 24, 20, 16, 12, 8, and 4 from left to right. The 16th nibble is labeled "Undefined".

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.3.36 Source Status Address Register for Channel 1 - High (SSTATAR1_HI)—Offset 8Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



Refer to the register description for Source Gather Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Refer to the description for SGR0_LO.SGI.

24.3.42 Source Gather Register for Channel 1 - High (SGR1_HI)—Offset A4h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Intel Atom® Processor E3800 Product Family
Datasheet
3476



Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.43 Destination Scatter Register for Channel 1 - Low (DSR1_LO)—Offset A8h

Refer to the register description for Destination Scatter Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + A8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Dest Scatter Count (DSC): Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	Dest Scatter Interval (DSI): Refer to the description for DSR0_LO.DSI.

24.3.44 Dest Scatter Register for Channel 1 - High (DSR1_HI)—Offset ACh

Refer to the register description for Destination Scatter Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + ACh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



Access Method

Offset: [BAR] + B0h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Diagram illustrating the SAR (Shift Register) structure, showing bit positions 31 down to 0, grouped into segments of 4 bits each (31-28, 28-24, 20-16, 16-12, 12-8, 8-4, 4-0). The label 'SAR' is positioned below the 16-12 segment.

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SAR: Current Source Address of DMA transfer. Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.

24.3.46 Source Address Register for Channel 2 - High (SAR2_HI)—Offset B4h

Access Method

Offset: [BAR] + B4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.47 Destination Address Register for Channel 2 - Low (DAR2_LO)—Offset B8h

Access Method



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
LOC								LMS

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.

24.3.50 Linked List Pointer Register for Channel 2 - High (LLP2_HI)—Offset C4h

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + C4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.51 Control Register for Channel 2 - Low (CTL2_LO)—Offset C8h

Refer to the register description for Control Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00304801h



31				28				24				20				16				12				8				4				0																															
0 0 0 0				0 0 0 0				0 0 1 1				0 0 0 0				0 1 0 0				1 0 0 0				0 0 0 0				0 0 0 0				0 0 0 1																															
Undefined_				LLP_SRC_EN				LLP_DST_EN				SMS				DMS				TT_FC				Undefined				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZ				DEST_MSIZ				SINC				DINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RW	Undefined_ : RESERVED
28	0h RW	LLP_SRC_EN : Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPx.LOC is non-zero
27	0h RW	LLP_DST_EN : Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPx.LOC is non-zero.
26:25	0h RW	Source Master Select (SMS) : Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS) : Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC) : Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined : RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN) : 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN) : 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ) : Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ) : Refer to the description for CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC) : 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC) : Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH) : This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH) : This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.



Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTAT: Source status information retrieved by hw from the addrx pointed to by SSTATAR0 register.

24.3.54 Source Status Register for Channel 2 - High (SSTAT2_HI)—Offset D4h

Refer to the register description for Source Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + D4h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.55 Dest Status Register for Channel 2 - Low (DSTAT2_LO)—Offset D8h

Refer to the register description for Dest Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + D8h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

DSTAT

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest status information retrieved by hw from the addrx pointed to by DSTATAR0 register.



Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

24.3.57 Source Status Address Register for Channel 2 - Low (SSTATAR2_LO)—Offset E0h

Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

October 2018
Document Number: 538136, Rev. 4.3



Access Method

Offset: [BAR] + ECh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

24.3.61 Configuration Register for Channel 2 - Low (CFG2_LO)—Offset F0h

Access Method

Offset: [BAR] + F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

31				28				24				20				16				12				8				4				0																											
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				1 1 1 0				0 1 0 0				0 0 0 0																															
RELOAD_DST				RELOAD_SRC				MAX_ABRST				SRC_HS_POL				DST_HS_POL				LOCK_B				LOCK_CH				LOCK_B_L				LOCK_CH_L				HS_SEL_SRC				HS_SEL_DST				FIFO_EMPTY				CH_SUSP				CH_PRIOR				Undefined			

Intel Atom® Processor E3800 Product Family
Datasheet
3486



Bit Range	Default & Access	Field Name (ID): Description
29:20	0h RW	Maximum AMBA Burst Length (MAX_ABRST): Maximum AMBA burst length that is used for DMA transfers on this channel. A value of 0 indicates that software is not limiting the maximum AMBA burst length for DMA transfers on this channel.
19	0h RW	Source Handshaking Interface Polarity (SRC_HS_POL): 0 = Active high 1 = Active low
18	0h RW	Destination Handshaking Interface Polarity (DST_HS_POL): 0 = Active high 1 = Active low
17	0h RW	Bus Lock Bit (LOCK_B): When active, the AHB bus master signal hlock is asserted for the duration specified in CFGx.LOCK_B_L.
16	0h RW	Channel Lock Bit (LOCK_CH): When the channel is granted control of the master bus interface and if the CFGx.LOCK_CH bit is asserted, then no other channels are granted control of the master bus interface for the duration specified in CFGx.LOCK_CH_L. Indicates to the master bus interface arbiter that this channel wants exclusive access to the master bus interface for the duration specified in CFGx.LOCK_CH_L.
15:14	0h RW	Bus Lock Level (LOCK_B_L): Indicates the duration over which CFGx.LOCK_B bit applies. 00 = Over complete DMA transfer 01 = Over complete DMA block transfer 1x = Over complete DMA transaction
13:12	0h RW	Channel Lock Level (LOCK_CH_L): Indicates the duration over which CFGx.LOCK_CH bit applies. 00 = DMA transfer 01 = DMA block transfer 1x = DMA transaction
11	1h RW	Source Software or Hardware Handshaking Select (HS_SEL_SRC): 0 = HW handshaking 1 = SW handshaking
10	1h RW	Destination Software or Hardware Handshaking Select (HS_SEL_DST): 0 = HW handshaking 1 = SW handshaking
9	1h RO	FIFO_EMPTY: Indicates if there is data left in the channel FIFO.
8	0h RW	Channel Suspend (CH_SUSP): Suspends all DMA transfers from source until this bit is cleared.
7:5	2h RW	Channel Priority (CH_PRIOR): Priority of 7 is the highest priority.
4:0	0h RW	Undefined: RESERVED

24.3.62 Configuration Register for Channel 2 - High (CFG2_HI)—Offset F4h

Refer to the register description for Configuration Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h





Access Method

Offset: [BAR] + FCh

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.65 Destination Scatter Register for Channel 2 - Low (DSR2_LO)—Offset 100h

Access Method

Offset: [BAR] + 100h

BAR Reference: [B:0, D:30, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSC				DSI				



Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.67 Source Address Register for Channel 3 - Low (SAR3_LO)—Offset 108h

Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

Diagram illustrating the SAR (Shift Register) structure, showing bit positions 31 down to 0, with segments of 4 bits each (28, 24, 20, 16, 12, 8, 4, 0).



Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Source Address of DMA Transfer (SAR): Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.

24.3.68 Source Address Register for Channel 3 - High (SAR3_HI)—Offset 10Ch

Refer to the description for register Source Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 10Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.69 Destination Address Register for Channel 3 - Low (DAR3_LO)–Offset 110h

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 110h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

DAR



Access Method

Offset: [BAR] + 114h

BAR Reference: [B:0, D:30, F:0] + 10h

	31	28	24	20	16	12	8	4	0																							
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Undefined																															

24.3.71 Linked List Pointer Register for Channel 3 - Low (LLP3_LO)—Offset 118h

Access Method

Offset: [BAR] + 118h

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.

24.3.72 Linked List Pointer Register for Channel 3 - High (LLP3_HI)—Offset 11Ch

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 11Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.73 Control Register for Channel 3 - Low (CTL3_LO)—Offset 120h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [BAR] + 120h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00304801h

31				28				24				20				16				12				8				4				0																															
0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	1	0	0	1	0	0	0	0	0	0	0	0	0	0	0	1																														
Undefined_				LLP_SRC_EN				LLP_DST_EN				SMS				DMS				TT_FC				Undefined				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZ				DEST_MSIZ				SINC				DINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_FN			



Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RW	Undefined_: RESERVED
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPx.LOC is non-zero
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPx.LOC is non-zero.
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ): Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Refer to the description for CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.



24.3.76 Source Status Register for Channel 3 - High (SSTAT3_HI)—Offset 12Ch

Refer to the register description for Source Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 12Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.77 Dest Status Register for Channel 3 - Low (DSTAT3_LO)—Offset 130h

Refer to the register description for Dest Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 130h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

DSTAT

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest status information retrieved by hw from the addrx pointed to by DSTATAR0 register



24.3.80 Source Status Address Register for Channel 3 - High (SSTATAR3_HI)—Offset 13Ch

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 13Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.81 Dest Status Address Register for Channel 3 - Low (DSTATAR3_LO)—Offset 140h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 140h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SSTATAR								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTATAR (SSTATAR): Pointer from where the hw can fetch the source status information registered in SSTAT0.



Bit Range	Default & Access	Field Name (ID): Description
29:20	0h RW	Maximum AMBA Burst Length (MAX_ABRST): Maximum AMBA burst length that is used for DMA transfers on this channel. A value of 0 indicates that software is not limiting the maximum AMBA burst length for DMA transfers on this channel.
19	0h RW	Source Handshaking Interface Polarity (SRC_HS_POL): 0 = Active high 1 = Active low
18	0h RW	Destination Handshaking Interface Polarity (DST_HS_POL): 0 = Active high 1 = Active low
17	0h RW	Bus Lock Bit (LOCK_B): When active, the AHB bus master signal hlock is asserted for the duration specified in CFGx.LOCK_B_L.
16	0h RW	Channel Lock Bit (LOCK_CH): When the channel is granted control of the master bus interface and if the CFGx.LOCK_CH bit is asserted, then no other channels are granted control of the master bus interface for the duration specified in CFGx.LOCK_CH_L. Indicates to the master bus interface arbiter that this channel wants exclusive access to the master bus interface for the duration specified in CFGx.LOCK_CH_L.
15:14	0h RW	Bus Lock Level (LOCK_B_L): Indicates the duration over which CFGx.LOCK_B bit applies. 00 = Over complete DMA transfer 01 = Over complete DMA block transfer 1x = Over complete DMA transaction
13:12	0h RW	Channel Lock Level (LOCK_CH_L): Indicates the duration over which CFGx.LOCK_CH bit applies. 00 = DMA transfer 01 = DMA block transfer 1x = DMA transaction
11	1h RW	Source Software or Hardware Handshaking Select (HS_SEL_SRC): 0 = HW handshaking 1 = SW handshaking
10	1h RW	Destination Software or Hardware Handshaking Select (HS_SEL_DST): 0 = HW handshaking 1 = SW handshaking
9	1h RO	FIFO_EMPTY: Indicates if there is data left in the channel FIFO.
8	0h RW	Channel Suspend (CH_SUSP): Suspends all DMA transfers from source until this bit is cleared.
7:5	3h RW	Channel Priority (CH_PRIOR): Priority of 7 is the highest priority.
4:0	0h RW	Undefined: RESERVED

24.3.84 Configuration Register for Channel 3 - High (CFG3_HI)—Offset 14Ch

Refer to the register description for Configuration Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 14Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Refer to the description for SGR0_LO.SGI.

24.3.86 Source Gather Register for Channel 3 - High (SGR3_HI)—Offset 154h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 154h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: Reserved.						

24.3.87 Destination Scatter Register for Channel 3 - Low (DSR3_LO)—Offset 158h

Refer to the register description for Destination Scatter Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 158h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				



Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Dest Scatter Count (DSC): Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	Dest Scatter Interval (DSI): Refer to the description for DSR0_LO.DSI.

24.3.88 Dest Scatter Register for Channel 3 - High (DSR3_HI)—Offset 15Ch

Refer to the register description for Destination Scatter Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 15Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Diagram illustrating the bit positions (0 to 31) and the corresponding values (0 to 0) for the register. The register is divided into four 8-bit segments, each containing the value 0. The entire register is labeled 'Undefined'.

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.89 Source Address Register for Channel 4 - Low (SAR4_LO)—Offset 160h

Refer to the description for register Source Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 160h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

[illegible]



24.3.92 Destination Address Register for Channel 4 - High (DAR4_HI)—Offset 16Ch

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 16Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.93 Linked List Pointer Register for Channel 4 - Low (LLP4_LO)—Offset 170h

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 170h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LOC								LMS

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.



24.3.94 Linked List Pointer Register for Channel 4 - High (LLP4_HI)—Offset 174h

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 174h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.95 Control Register for Channel 4 - Low (CTL4_LO)—Offset 178h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 178h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00304801h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RW	Undefined_: RESERVED
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPx.LOC is non-zero
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPx.LOC is non-zero.



Bit Range	Default & Access	Field Name (ID): Description
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ): Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Refer to the description for CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.3.96 Control Register for Channel 4 - High (CTL4_HI)—Offset 17Ch

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 17Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000002h



Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SSTAT								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTAT: Source status information retrieved by hw from the addrx pointed to by SSTATAR0 register.

24.3.98 Source Status Register for Channel 4 - High (SSTAT4_HI)—Offset 184h

Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

October 2018
Document Number: 538136, Rev. 4.3



Access Method

Offset: [BAR] + 188h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

24.3.100 Dest Status Register for Channel 4 - High (DSTAT4_HI)—Offset 18Ch

Access Method

Offset: [BAR] + 18Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.3.101 Source Status Address Register for Channel 4 - Low (SSTATAR4_LO)—Offset 190h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 190h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SSTATAR								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.						

24.3.102 Source Status Address Register for Channel 4 - High (SSTATAR4_HI)—Offset 194h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 194h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.3.105 Configuration Register for Channel 4 - Low (CFG4_LO)—Offset 1A0h

Refer to the register description for Configuration Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000E80h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RELOAD_DST	RELOAD_SRC	MAX_ABRST	SRC_HS_POL	DST_HS_POL	LOCK_B	LOCK_CH	LOCK_B_L	LOCK_CH_L






Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.111 Source Address Register for Channel 5 - Low (SAR5_LO)—Offset 1B8h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SAR: Current Source Address of DMA transfer. Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.

24.3.112 Source Address Register for Channel 5 - High (SAR5_HI)—Offset 1BCh



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: Reserved.						

24.3.115 Linked List Pointer Register for Channel 5 - Low (LLP5_LO)—Offset 1C8h

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LOC								LMS

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.

24.3.116 Linked List Pointer Register for Channel 5 - High (LLP5_HI)—Offset 1CCh

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1CCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.117 Control Register for Channel 5 - Low (CTL5_LO)—Offset 1D0h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1D0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00304801h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 1 1	0 0 0 0	0 1 0 0	1 0 0 0	0 0 0 0	0 0 0 0
Undefined_	LLP_SRC_EN	LLP_DST_EN	SMS	DMS	TT_FC	Undefined	DST_SCATTER_EN	SRC_GATHER_EN
						SRC_MSIZ	DEST_MSIZ	
							SINC	DINC
								SRC_TR_WIDTH
								DST_TR_WIDTH
								INT_FN

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RW	Undefined_: RESERVED
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPx.LOC is non-zero
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPx.LOC is non-zero.
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED





Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSTAT								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest status information retrieved by hw from the addrx pointed to by DSTATAR0 register

24.3.122 Dest Status Register for Channel 5 - High (DSTAT5_HI)—Offset 1E4h

Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

Diagram illustrating the bit positions (31 down to 0) and the value 0x00000000. The register is divided into four 8-bit segments, each containing eight zeros. A label 'Undefined' points to the bit field from position 16 to 31.

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



24.3.123 Source Status Address Register for Channel 5 - Low (SSTATAR5_LO)—Offset 1E8h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SSTATAR								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.						

24.3.124 Source Status Address Register for Channel 5 - High (SSTATAR5_HI)—Offset 1ECh

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1ECh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						



24.3.125 Dest Status Address Register for Channel 5 - Low (DSTATAR5_LO)—Offset 1F0h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTATAR

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTATAR (SSTATAR): Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.3.126 Dest Status Address Register for Channel 5 - High (DSTATAR5_HI)—Offset 1F4h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.127 Configuration Register for Channel 5 - Low (CFG5_LO)—Offset 1F8h

Refer to the register description for Configuration Register for Channel 0 - Low.



Access Method

Offset: [BAR] + 1FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000004h

Bit Range	Default & Access	Field Name (ID): Description
31:15	0h RW	Undefined: Reserved.
14:11	0h RW	DEST_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the destination of channel x if the CFGx.HS_SEL_DST field is 0; otherwise, this field is ignored.
10:7	0h RW	SRC_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the source of channel x if the CFGx.HS_SEL_SRC field is 0; otherwise, this field is ignored.
6	0h RW	Source Status Update Enable (SS_UPD_EN): Source status information is fetched only from the location pointed to by the SSTATARx register, stored in the SSTATx register and written out to the SSTATx location of the LLI (refer to Figure 52 on page 243) if SS_UPD_EN is high.
5	0h RW	Destination Status Update Enable (DS_UPD_EN): Destination status information is fetched only from the location pointed to by the DSTATARx register, stored in the DSTATx register and written out to the DSTATx location of the LLI if DS_UPD_EN is high.
4:2	1h RW	PROTCTL: Protection Control bits used to drive the AHB HPROT[3:1] bus.



Bit Range	Default & Access	Field Name (ID): Description
1	0h RW	FIFO Mode Select (FIFO_MODE): Determines how much space or data needs to be available in the FIFO before a burst transaction request is serviced. 0 = Space/data available for single AHB transfer of the specified transfer width. 1 = Data available is greater than or equal to half the FIFO depth for destination transfers and space available is greater than half the FIFO depth for source transfers.
0	0h RW	Flow Control Mode (FCMODE): Determines when source transaction requests are serviced when the Destination Peripheral is the flow controller. 0 = Source transaction requests are serviced when they occur. Data pre-fetching is enabled. 1 = Source transaction requests are not serviced until a destination transaction request occurs.

24.3.129 Source Gather Register for Channel 5 - Low (SGR5_LO)—Offset 200h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 200h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SGC				SGI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Refer to the description for SGR0_LO.SGI.

24.3.130 Source Gather Register for Channel 5 - High (SGR5_HI)—Offset 204h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 204h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 208h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Dest Scatter Count (DSC): Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	Dest Scatter Interval (DSI): Refer to the description for DSR0_LO.DSI.

24.3.132 Dest Scatter Register for Channel 5 - High (DSR5_HI)—Offset 20Ch

Access Method

Offset: [BAR] + 20Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 210h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Source Address of DMA Transfer (SAR): Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.

24.3.134 Source Address Register for Channel 6 - High (SAR6_HI)—Offset 214h

Access Method

Offset: [BAR] + 214h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 218h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

312824201612840																															
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0																															
DAR																															
Bit Range		Default & Access		Field Name (ID): Description																											
31:0		0h RW		Current Destination Address of DMA Transfer (DAR): Updated after each destination transfer. The DINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every destination transfer throughout the block transfer.																											

24.3.136 Destination Address Register for Channel 6 - High (DAR6_HI)—Offset 21Ch

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Offset: [BAR] + 21Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 220h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.

24.3.138 Linked List Pointer Register for Channel 6 - High (LLP6_HI)—Offset 224h

Access Method

Offset: [BAR] + 224h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h





Access Method

Offset: [BAR] + 230h

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
STAT								0

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTAT: Source status information retrieved by hw from the addrx pointed to by SSTATAR0 register

24.3.142 Source Status Register for Channel 6 - High (SSTAT6_HI)—Offset 234h

Access Method

Offset: [BAR] + 234h

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.3.143 Dest Status Register for Channel 6 - Low (DSTAT6_LO)—Offset 238h

Refer to the register description for Dest Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 238h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest status information retrieved by hw from the addrx pointed to by DSTATAR0 register

24.3.144 Dest Status Register for Channel 6 - High (DSTAT6_HI)—Offset 23Ch

Refer to the register description for Dest Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 23Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



24.3.145 Source Status Address Register for Channel 6 - Low (SSTATAR6_LO)—Offset 240h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 240h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTATAR

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.3.146 Source Status Address Register for Channel 6 - High (SSTATAR6_HI)—Offset 244h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 244h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



Access Method

Offset: [BAR] + 250h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000EC0h

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	Automatic Destination Reload (RELOAD_DST): The DARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
30	0h RW	Automatic Source Reload (RELOAD_SRC): The SARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
29:20	0h RW	Maximum AMBA Burst Length (MAX_ABRST): Maximum AMBA burst length that is used for DMA transfers on this channel. A value of 0 indicates that software is not limiting the maximum AMBA burst length for DMA transfers on this channel.
19	0h RW	Source Handshaking Interface Polarity (SRC_HS_POL): 0 = Active high 1 = Active low
18	0h RW	Destination Handshaking Interface Polarity (DST_HS_POL): 0 = Active high 1 = Active low
17	0h RW	Bus Lock Bit (LOCK_B): When active, the AHB bus master signal hlock is asserted for the duration specified in CFGx.LOCK_B_L.
16	0h RW	Channel Lock Bit (LOCK_CH): When the channel is granted control of the master bus interface and if the CFGx.LOCK_CH bit is asserted, then no other channels are granted control of the master bus interface for the duration specified in CFGx.LOCK_CH_L. Indicates to the master bus interface arbiter that this channel wants exclusive access to the master bus interface for the duration specified in CFGx.LOCK_CH_L.
15:14	0h RW	Bus Lock Level (LOCK_B_L): Indicates the duration over which CFGx.LOCK_B bit applies. 00 = Over complete DMA transfer 01 = Over complete DMA block transfer 1x = Over complete DMA transaction
13:12	0h RW	Channel Lock Level (LOCK_CH_L): Indicates the duration over which CFGx.LOCK_CH bit applies. 00 = DMA transfer 01 = DMA block transfer 1x = DMA transaction

24.3.150 Configuration Register for Channel 6 - High (CFG6_HI)—Offset 254h

Refer to the register description for Configuration Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 254h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000004h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:15	0h RW	Undefined: Reserved.
14:11	0h RW	DEST_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the destination of channel x if the CFGx.HS_SEL_DST field is 0; otherwise, this field is ignored.
10:7	0h RW	SRC_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the source of channel x if the CFGx.HS_SEL_SRC field is 0; otherwise, this field is ignored.
6	0h RW	Source Status Update Enable (SS_UPD_EN): Source status information is fetched only from the location pointed to by the SSTATARx register, stored in the SSTATx register and written out to the SSTATx location of the LLI (refer to Figure 52 on page 243) if SS_UPD_EN is high.



Bit Range	Default & Access	Field Name (ID): Description
5	0h RW	Destination Status Update Enable (DS_UPD_EN): Destination status information is fetched only from the location pointed to by the DSTATARx register, stored in the DSTATx register and written out to the DSTATx location of the LLI if DS_UPD_EN is high.
4:2	1h RW	PROTCTL: Protection Control bits used to drive the AHB HPROT[3:1] bus.
1	0h RW	FIFO Mode Select (FIFO_MODE): Determines how much space or data needs to be available in the FIFO before a burst transaction request is serviced. 0 = Space/data available for single AHB transfer of the specified transfer width. 1 = Data available is greater than or equal to half the FIFO depth for destination transfers and space available is greater than half the fifo depth for source transfers.
0	0h RW	Flow Control Mode (FCMODE): Determines when source transaction requests are serviced when the Destination Peripheral is the flow controller. 0 = Source transaction requests are serviced when they occur. Data pre-fetching is enabled. 1 = Source transaction requests are not serviced until a destination transaction request occurs.

24.3.151 Source Gather Register for Channel 6 - Low (SGR6_LO)—Offset 258h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 258h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC	SGI							

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Refer to the description for SGR0_LO.SGI.

24.3.152 Source Gather Register for Channel 6 - High (SGR6_HI)—Offset 25Ch

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 25Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h



Access Method

Offset: [BAR] + 268h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0															
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0															
SAR															
Bit Range	Default & Access	Field Name (ID): Description													
31:0	0h RW	Current Source Address of DMA Transfer (SAR): Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.													

24.3.156 Source Address Register for Channel 7 - High (SAR7_HI)—Offset 26Ch

Access Method

Offset: [BAR] + 26Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.3.157 Destination Address Register for Channel 7 - Low (DAR7_LO)—Offset 270h

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 270h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

312824201612840																															
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0																															
DAR																															
Bit Range		Default & Access		Field Name (ID): Description																											
31:0		0h RW		Current Destination Address of DMA Transfer (DAR): Updated after each destination transfer. The DINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every destination transfer throughout the block transfer.																											

24.3.158 Destination Address Register for Channel 7 - High (DAR7_HI)—Offset 274h

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 274h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 278h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
LMS								LMS

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.

24.3.160 Linked List Pointer Register for Channel 7 - High (LLP7_HI)—Offset 27Ch

Access Method

Offset: [BAR] + 27Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h





24.3.169 Dest Status Address Register for Channel 7 - Low (DSTATAR7_LO)—Offset 2A0h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTATAR

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTATAR (SSTATAR): Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.3.170 Dest Status Address Register for Channel 7 - High (DSTATAR7_HI)—Offset 2A4h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2A4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



Access Method

Offset: [BAR] + 2ACh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000004h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0				
Undefined																DEST_PER				SRC_PER				SS_UPD_EN		DS_UPD_EN		PROTCTL		FIFO_MODE		FCMODE			

Bit Range	Default & Access	Field Name (ID): Description
31:15	0h RW	Undefined: Reserved.
14:11	0h RW	DEST_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the destination of channel x if the CFGx.HS_SEL_DST field is 0; otherwise, this field is ignored.
10:7	0h RW	SRC_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the source of channel x if the CFGx.HS_SEL_SRC field is 0; otherwise, this field is ignored.
6	0h RW	Source Status Update Enable (SS_UPD_EN): Source status information is fetched only from the location pointed to by the SSTATARx register, stored in the SSTATx register and written out to the SSTATx location of the LLI (refer to Figure 52 on page 243) if SS_UPD_EN is high.



Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Refer to the description for SGR0_LO.SGI.

24.3.174 Source Gather Register for Channel 7 - High (SGR7_HI)—Offset 2B4h

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.175 Destination Scatter Register for Channel 7 - Low (DSR7_LO)—Offset 2B8h

Refer to the register description for Destination Scatter Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Dest Scatter Count (DSC): Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	Dest Scatter Interval (DSI): Refer to the description for DSR0_LO.DSI.

24.3.176 Dest Scatter Register for Channel 7 - High (DSR7_HI)—Offset 2BCh

Refer to the register description for Destination Scatter Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2BCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

24.3.177 Interrupt Raw Status Registers - Low (RawTfr_LO)—Offset 2C0h



Access Method

Offset: [BAR] + 2C4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.179 Interrupt Raw Status Registers - Low (RawBlock_LO)—Offset 2C8h

Access Method

Offset: [BAR] + 2C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RW	Raw Interrupt Status (RAW): Reserved.



Access Method

Offset: [BAR] + 2D4h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.183 Interrupt Raw Status Registers - Low (RawDstTran_LO)—Offset 2D8h

Access Method

Offset: [BAR] + 2D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RW	Raw Interrupt Status (RAW): Reserved.



Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

	31			28					24					20					16					12					8					4					0	
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	Undefined																																							

24.3.185 Interrupt Raw Status Registers - Low (RawErr_LO)—Offset 2E0h

Access Method

BAR Reference: [B:0, D:30, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined							RAW	

Intel Atom® Processor E3800 Product Family
Datasheet
3559



24.3.186 Interrupt Raw Status Registers - High (RawErr_HI)—Offset 2E4h

Refer to the description of the register with short name RawTfr_LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2E4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.187 Interrupt Status Registers - Low (StatusTfr_LO)—Offset 2E8h

Refer to the description for register StatusTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined							STATUS	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RO	Interrupt Status (STATUS): Reserved.



24.3.188 Interrupt Status Registers - High (StatusTfr_HI)—Offset 2ECh

All interrupt events from all channels are stored in these Interrupt Status registers after masking: StatusBlock, StatusDstTran, StatusErr, StatusSrcTran, and StatusTfr. Each Interrupt Status register has a bit allocated per channel; for example, StatusTfr[2] is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (int or int_n bus, depending on interrupt polarity) leaving the DW_ahb_dmac.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2ECh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.189 Interrupt Status Registers - Low (StatusBlock_LO)—Offset 2F0h

Refer to the description for register StatusTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined							STATUS	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RO	Interrupt Status (STATUS): Reserved.



24.3.190 Interrupt Status Registers - High (StatusBlock_HI)—Offset 2F4h

Refer to the description for register StatusTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.191 Interrupt Status Registers - Low (StatusSrcTran_LO)—Offset 2F8h

Refer to the description for register StatusTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined							STATUS	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RO	Interrupt Status (STATUS): Reserved.



Access Method

Offset: [BAR] + 304h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.195 Interrupt Status Registers - Low (StatusErr_LO)—Offset 308h

Access Method

Offset: [BAR] + 308h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RO	Interrupt Status (STATUS): Reserved.



Access Method

Offset: [BAR] + 324h

BAR Reference: [B:0, D:30, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.203 Interrupt Mask Registers - Low (MaskDstTran_LO)—Offset 328h

Access Method

Offset: [BAR] + 328h

BAR Reference: [B:0, D:30, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				INT_MASK_WE				INT_MASK



Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Interrupt Mask Write Enable (INT_MASK_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Interrupt Mask (INT_MASK): 0 = masked 1 = unmasked

24.3.204 Interrupt Mask Registers - High (MaskDstTran_HI)—Offset 32Ch

Refer to the description for register MaskBlock LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 32Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.205 Interrupt Mask Registers - Low (MaskErr_LO)—Offset 330h

Refer to the description for register MaskBlock_LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 330h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				INT_MASK_WE				INT_MASK

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Interrupt Mask Write Enable (INT_MASK_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Interrupt Mask (INT_MASK): 0 = masked 1 = unmasked

24.3.206 Interrupt Mask Registers - High (MaskErr_HI)—Offset 334h

Refer to the description for register MaskBlock_LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 334h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.207 Interrupt Clear Registers - Low (ClearTfr_LO)—Offset 338h

Each bit in the Raw Status and Status registers is cleared on the same cycle by writing a 1 to the corresponding location in the Clear registers: ClearBlock, ClearDstTran, ClearErr, ClearSrcTran, and ClearTfr. Each Interrupt Clear register has a bit allocated per channel; for example, ClearTfr[2] is the clear bit for the Channel 2 transfer complete interrupt. Writing a 0 has no effect. These registers are not readable.

Access Method



24.3.209 Interrupt Clear Registers - Low (ClearBlock_LO)—Offset 340h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 340h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined							CLEAR	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h WO	Clear Interrupt Status (CLEAR): Interrupt clear. 0 = no effect 1 = clear interrupt

24.3.210 Interrupt Clear Registers (ClearBlock_HI)—Offset 344h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 344h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



24.3.211 Interrupt Clear Registers - Low (ClearSrcTran_LO)—Offset 348h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 348h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined							CLEAR	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h WO	Clear Interrupt Status (CLEAR): Interrupt clear. 0 = no effect 1 = clear interrupt

24.3.212 Interrupt Clear RegistersClearSrc - High (ClearSrcTran_HI)—Offset 34Ch

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



24.3.213 Interrupt Clear Registers - Low (ClearDstTran_LO)—Offset 350h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 350h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined							CLEAR	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h WO	Clear Interrupt Status (CLEAR): Interrupt clear. 0 = no effect 1 = clear interrupt

24.3.214 Interrupt Clear Registers - High (ClearDstTran_HI)—Offset 354h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 354h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



24.3.217 Combined Interrupt Status Register - Low (StatusInt_LO)— Offset 360h

The contents of each of the five Status registers StatusTfr, StatusBlock, StatusSrcTran, StatusDstTran, StatusErr is ORed to produce a single bit for each interrupt type in the Combined Status register (StatusInt). This register is read-only.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 360h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined							ERR	DSTT
							SRCT	BLOCK
							TFR	

Bit Range	Default & Access	Field Name (ID): Description
31:5	0h RW	Undefined: Reserved.
4	0h RO	ERR: OR of the contents of StatusErr register.
3	0h RO	DSTT: OR of the contents of StatusDst register.
2	0h RO	SRCT: OR of the contents of StatusSrcTran register.
1	0h RO	BLOCK: OR of the contents of StatusBlock register.
0	0h RO	TFR: OR of the contents of StatusTfr register.

24.3.218 Combined Interrupt Status Register - High (StatusInt_HI)— Offset 364h

Refer to the description for register StatusInt_LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 364h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 36Ch

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.221 Destination Software Transaction Request Register - Low (ReqDstReg_LO)—Offset 370h

Access Method

Offset: [BAR] + 370h

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
15:8	0h WO	Destination Request Write Enable (DST_REQ_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Destination Request (DST_REQ): A bit is assigned for each channel in this register. ReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

24.3.222 Destination Software Transaction Request Register - High (RegDstReg_HI)—Offset 374h

A bit is assigned for each channel in this register. ReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 374h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

Diagram illustrating the bit positions (0 to 31) and the corresponding bit values (0 or 1) for the register. The register is divided into four 8-bit segments, each labeled with its bit range (0-7, 8-15, 16-23, 24-31). The bit values are shown as 0 or 1, indicating the state of each bit. The entire register is labeled "Undefined".

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.223 Single Source Software Transaction Request Register - Low (SglRqSrcReg_LO)—Offset 378h

A bit is assigned for each channel in this register. SglReqSrcReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 378h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				SRC_SGLREQ_WE				SRC_SGLREQ

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Source Req Write Enable (SRC_SGLREQ_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Source Single Request (SRC_SGLREQ): A channel SRC_SGLREQ bit is written only if the corresponding channel write enable bit in the SRC_SGLREQ_WE field is asserted on the same AHB write transfer, and if the channel is enabled in the ChEnReg register.

24.3.224 Single Source Software Transaction Request Register - High (SglRqSrcReg_HI)—Offset 37Ch

A bit is assigned for each channel in this register. SglReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 37Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



24.3.225 Single Destination Software Transaction Request Register - Low (SglRqDstReg_LO)—Offset 380h

A bit is assigned for each channel in this register. SglReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 380h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				DST_SGLREQ_WE				DST_SGLREQ

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Destination Request Write Enable (DST_SGLREQ_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Destination Single or Burst Request (DST_SGLREQ): A channel DST_SGLREQ bit is written only if the corresponding channel write enable bit in the DST_SGLREQ_WE field is asserted on the same AHB write transfer, and if the channel is enabled in the ChEnReg register.

24.3.226 Single Destination Software Transaction Request Register - High (SglRqDstReg_HI)—Offset 384h

A bit is assigned for each channel in this register. SglReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 384h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

24.3.229 Last Destination Transaction Request Register - Low (LstDstReq LO)—Offset 390h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 390h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				LSTDST_WE				LSTDST

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Last Destination Transaction Request Write Enable (LSTDST_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Destination Last Transaction Request (LSTDST): 0 = Not last transaction in current block 1 = Last transaction in current block



Refer to the description for DW_ahb_dmac Channel Enable Register - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.235 DW_ahb_dmac ID Register - Low (DmaIdReg_LO)—Offset 3A8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: C0CAC01Ah

31	28	24	20	16	12	8	4	0
1	1	0	0	0	0	0	1	0
DMA_ID								



Bit Range	Default & Access	Field Name (ID): Description
31:0	c0cac01ah RO	Hardcoded DW_ahb_dmac Peripheral ID (DMA_ID): coreConsultantconfigured hardcoded ID number DMAH_ID_NUM.

24.3.236 DW_ahb_dmac ID Register - High (DmaIdReg_HI)—Offset 3ACh

Refer to the description of DW_ahb_dmac ID Register - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3ACh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.3.237 DW_ahb_dmac Test Register - Low (DmaTestReg_LO)—Offset 3B0h

This register is used to put the AHB slave interface into test mode, during which the readback value of the writable registers match the value written, assuming the DW_ahb_dmac configuration has not optimized the same registers. In normal operation, the readback value of some registers is a function of the DW_ahb_dmac state, and does not match the value written.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3B0h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
TEST SIV IF								



24.3.239 DW_ahb_dmac Component Parameters Register 6 - Low (DMA_COMP_PARAMS_6_LO)—Offset 3C8h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0


Undefined

24.3.240 DW_ahb_dmac Component Parameters Register 6 - High (DMA_COMP_PARAMS_6_HI)—Offset 3CCCh

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	Undefined: Reserved.
30:28	3h RO	CH7_FIFO_DEPTH: The value of this register is derived from the DMAH_CH7_FIFO_DEPTH coreConsultant parameter. For a description of this parameter, refer to page 106. • 0h = 8 • 1h = 16 • 2h = 32 • 3h = 64 • 4h = 128
27:25	4h RO	CH7_SMS: The value of this register is derived from the DMAH_CH7_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. • 0h = MASTER_1 • 1h = MASTER_2 • 2h = MASTER_3 • 3h = MASTER_4 • 4h = NO_HARDCODE
24:22	0h RO	CH7_LMS: The value of this register is derived from the DMAH_CH7_LMS coreConsultant parameter. For a description of this parameter, refer to page 111. • 0h = MASTER_1 • 1h = MASTER_2 • 2h = MASTER_3 • 3h = MASTER_4 • 4h = NO_HARDCODE




Bit Range	Default & Access	Field Name (ID): Description
21:19	4h RO	CH7_DMS: The value of this register is derived from the DMAH_CH7_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH7_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH7_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH7_FC: The value of this register is derived from the DMAH_CH7_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH7_HC_LLP: The value of this register is derived from the DMAH_CH7_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH7_CTL_WB_EN: The value of this register is derived from the DMAH_CH7_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
11	0h RO	CH7_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH7_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH7_LOCK_EN: The value of this register is derived from the DMAH_CH7_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH7_SRC_GAT_EN: The value of this register is derived from the DMAH_CH7_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH7_DST_SCA_EN: The value of this register is derived from the DMAH_CH7_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH7_STAT_SRC: The value of this register is derived from the DMAH_CH7_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
30:28	3h RO	CH6_FIFO_DEPTH: The value of this register is derived from the DMAH_CH6_FIFO_DEPTH coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 8 1h = 16 2h = 32 3h = 64 4h = 128
27:25	4h RO	CH6_SMS: The value of this register is derived from the DMAH_CH6_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
24:22	0h RO	CH6_LMS: The value of this register is derived from the DMAH_CH6_LMS coreConsultant parameter. For a description of this parameter, refer to page 111. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
21:19	4h RO	CH6_DMS: The value of this register is derived from the DMAH_CH6_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH6_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH6_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH6_FC: The value of this register is derived from the DMAH_CH6_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH6_HC_LLP: The value of this register is derived from the DMAH_CH6_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH6_CTL_WB_EN: The value of this register is derived from the DMAH_CH6_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE




Bit Range	Default & Access	Field Name (ID): Description
11	0h RO	CH6_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH6_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH6_LOCK_EN: The value of this register is derived from the DMAH_CH6_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH6_SRC_GAT_EN: The value of this register is derived from the DMAH_CH6_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH6_DST_SCA_EN: The value of this register is derived from the DMAH_CH6_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH6_STAT_SRC: The value of this register is derived from the DMAH_CH6_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
6	0h RO	CH6_STAT_DST: The value of this register is derived from the DMAH_CH6_STAT_DST coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
5:3	0h RO	CH6_STW: The value of this register is derived from the DMAH_CH6_STW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
2:0	0h RO	CH6_DTW: The value of this register is derived from the DMAH_CH6_DTW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved



Bit Range	Default & Access	Field Name (ID): Description
21:19	4h RO	CH5_DMS: The value of this register is derived from the DMAH_CH5_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH5_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH5_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH5_FC: The value of this register is derived from the DMAH_CH5_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH5_HC_LLP: The value of this register is derived from the DMAH_CH5_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH5_CTL_WB_EN: The value of this register is derived from the DMAH_CH5_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
11	0h RO	CH5_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH5_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH5_LOCK_EN: The value of this register is derived from the DMAH_CH5_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH5_SRC_GAT_EN: The value of this register is derived from the DMAH_CH5_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH5_DST_SCA_EN: The value of this register is derived from the DMAH_CH5_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH5_STAT_SRC: The value of this register is derived from the DMAH_CH5_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE






Bit Range	Default & Access	Field Name (ID): Description
30:28	3h RO	CH4_FIFO_DEPTH: The value of this register is derived from the DMAH_CH4_FIFO_DEPTH coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 8 1h = 16 2h = 32 3h = 64 4h = 128
27:25	4h RO	CH4_SMS: The value of this register is derived from the DMAH_CH4_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
24:22	0h RO	CH4_LMS: The value of this register is derived from the DMAH_CH4_LMS coreConsultant parameter. For a description of this parameter, refer to page 111. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
21:19	4h RO	CH4_DMS: The value of this register is derived from the DMAH_CH4_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH4_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH4_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH4_FC: The value of this register is derived from the DMAH_CH4_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH4_HC_LLP: The value of this register is derived from the DMAH_CH4_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH4_CTL_WB_EN: The value of this register is derived from the DMAH_CH4_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
11	0h RO	CH4_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH4_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH4_LOCK_EN: The value of this register is derived from the DMAH_CH4_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH4_SRC_GAT_EN: The value of this register is derived from the DMAH_CH4_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH4_DST_SCA_EN: The value of this register is derived from the DMAH_CH4_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH4_STAT_SRC: The value of this register is derived from the DMAH_CH4_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
6	0h RO	CH4_STAT_DST: The value of this register is derived from the DMAH_CH4_STAT_DST coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
5:3	0h RO	CH4_STW: The value of this register is derived from the DMAH_CH4_STW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
2:0	0h RO	CH4_DTW: The value of this register is derived from the DMAH_CH4_DTW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved

24.3.244 DW_ahb_dmac Component Parameters Register 4 - High (DMA_COMP_PARAMS_4_HI)—Offset 3DCh



Bit Range	Default & Access	Field Name (ID): Description
21:19	4h RO	CH3_DMS: The value of this register is derived from the DMAH_CH3_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH3_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH3_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH3_FC: The value of this register is derived from the DMAH_CH3_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH3_HC_LLP: The value of this register is derived from the DMAH_CH3_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH3_CTL_WB_EN: The value of this register is derived from the DMAH_CH3_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
11	0h RO	CH3_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH3_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH3_LOCK_EN: The value of this register is derived from the DMAH_CH3_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH3_SRC_GAT_EN: The value of this register is derived from the DMAH_CH3_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH3_DST_SCA_EN: The value of this register is derived from the DMAH_CH3_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH3_STAT_SRC: The value of this register is derived from the DMAH_CH3_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE






Bit Range	Default & Access	Field Name (ID): Description
30:28	3h RO	CH2_FIFO_DEPTH: The value of this register is derived from the DMAH_CH2_FIFO_DEPTH coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 8 1h = 16 2h = 32 3h = 64 4h = 128
27:25	4h RO	CH2_SMS: The value of this register is derived from the DMAH_CH2_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
24:22	0h RO	CH2_LMS: The value of this register is derived from the DMAH_CH2_LMS coreConsultant parameter. For a description of this parameter, refer to page 111. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
21:19	4h RO	CH2_DMS: The value of this register is derived from the DMAH_CH2_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH2_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH2_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH2_FC: The value of this register is derived from the DMAH_CH2_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH2_HC_LLP: The value of this register is derived from the DMAH_CH2_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH2_CTL_WB_EN: The value of this register is derived from the DMAH_CH2_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
11	0h RO	CH2_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH2_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to the spec. 0 = FALSE 1 = TRUE
10	0h RO	CH2_LOCK_EN: The value of this register is derived from the DMAH_CH2_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH2_SRC_GAT_EN: The value of this register is derived from the DMAH_CH2_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH2_DST_SCA_EN: The value of this register is derived from the DMAH_CH2_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH2_STAT_SRC: The value of this register is derived from the DMAH_CH2_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
6	0h RO	CH2_STAT_DST: The value of this register is derived from the DMAH_CH2_STAT_DST coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
5:3	0h RO	CH2_STW: The value of this register is derived from the DMAH_CH2_STW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
2:0	0h RO	CH2_DTW: The value of this register is derived from the DMAH_CH2_DTW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved



Bit Range	Default & Access	Field Name (ID): Description
21:19	4h RO	CH1_DMS: The value of this register is derived from the DMAH_CH1_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH1_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH1_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH1_FC: The value of this register is derived from the DMAH_CH1_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH1_HC_LLP: The value of this register is derived from the DMAH_CH1_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH1_CTL_WB_EN: The value of this register is derived from the DMAH_CH1_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
11	0h RO	CH1_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH1_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH1_LOCK_EN: The value of this register is derived from the DMAH_CH1_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH1_SRC_GAT_EN: The value of this register is derived from the DMAH_CH1_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH1_DST_SCA_EN: The value of this register is derived from the DMAH_CH1_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH1_STAT_SRC: The value of this register is derived from the DMAH_CH1_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
30:28	3h RO	CH0_FIFO_DEPTH: The value of this register is derived from the DMAH_CH0_FIFO_DEPTH coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 8 1h = 16 2h = 32 3h = 64 4h = 128
27:25	4h RO	CH0_SMS: The value of this register is derived from the DMAH_CH0_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
24:22	0h RO	CH0_LMS: The value of this register is derived from the DMAH_CH0_LMS coreConsultant parameter. For a description of this parameter, refer to page 111. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
21:19	4h RO	CH0_DMS: The value of this register is derived from the DMAH_CH0_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH0_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH0_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH0_FC: The value of this register is derived from the DMAH_CH0_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH0_HC_LLP: The value of this register is derived from the DMAH_CH0_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH0_CTL_WB_EN: The value of this register is derived from the DMAH_CH0_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
11	0h RO	CHO_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH0_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CHO_LOCK_EN: The value of this register is derived from the DMAH_CH0_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CHO_SRC_GAT_EN: The value of this register is derived from the DMAH_CH0_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CHO_DST_SCA_EN: The value of this register is derived from the DMAH_CH0_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CHO_STAT_SRC: The value of this register is derived from the DMAH_CH0_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
6	0h RO	CHO_STAT_DST: The value of this register is derived from the DMAH_CH0_STAT_DST coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
5:3	0h RO	CHO_STW: Refer to the description for bit field DMA_COMP_PARAMS_2_LO.CH0_DTW
2:0	0h RO	CHO_DTW: The value of this register is derived from the DMAH_CH0_DTW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved

24.3.248 DW_ahb_dmac Component Parameters Register 2 - High (DMA_COMP_PARAMS_2_HI)—Offset 3ECh

This is a constant read-only register that contains encoded information about the component parameter settings. The reset value depends on coreConsultant parameter(s).

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3ECh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH7_MULTI_BLK_TYPE	CH6_MULTI_BLK_TYPE	CH5_MULTI_BLK_TYPE	CH4_MULTI_BLK_TYPE	CH3_MULTI_BLK_TYPE	CH2_MULTI_BLK_TYPE	CH1_MULTI_BLK_TYPE	CH0_MULTI_BLK_TYPE	

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RO	CH7_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LL 5h = RELOAD_LL 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LL
27:24	0h RO	CH6_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LL 5h = RELOAD_LL 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LL
23:20	0h RO	CH5_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LL 5h = RELOAD_LL 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LL
19:16	0h RO	CH4_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LL 5h = RELOAD_LL 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LL



Bit Range	Default & Access	Field Name (ID): Description
15:12	0h RO	CH3_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP
11:8	0h RO	CH2_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP
7:4	0h RO	CH1_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP
3:0	0h RO	CH0_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP



24.3.249 DW_ahb_dmac Component Parameters Register 1 - Low (DMA_COMP_PARAMS_1_LO)—Offset 3F0h

This is a constant read-only register that contains encoded information about the component parameter settings. The reset value depends on coreConsultant parameter(s).

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3F0h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: AAAAAAAAh

31	28	24	20	16	12	8	4	0
1	0	1	0	1	0	1	0	1
0	1	0	1	0	1	0	1	0
CH7_MAX_BLK_SIZE	CH6_MAX_BLK_SIZE	CH5_MAX_BLK_SIZE	CH4_MAX_BLK_SIZE	CH3_MAX_BLK_SIZE	CH2_MAX_BLK_SIZE	CH1_MAX_BLK_SIZE	CH0_MAX_BLK_SIZE	

Bit Range	Default & Access	Field Name (ID): Description
31:28	ah RO	CH7_MAX_BLK_SIZE: The values of these bit fields are derived from the DMAH_CHx_MAX_BLK_SIZE coreConsultant parameter. For a description of these parameters, refer to page 107. 0h = 3 1h = 7 2h = 15 3h = 31 4h = 63 5h = 127 6h = 255 7h = 511 8h = 1023 9h = 2047 - Ah = 4095
27:24	ah RO	CH6_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
23:20	ah RO	CH5_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
19:16	ah RO	CH4_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
15:12	ah RO	CH3_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
11:8	ah RO	CH2_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
7:4	ah RO	CH1_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
3:0	ah RO	CH0_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.



Bit Range	Default & Access	Field Name (ID): Description
20:19	0h RO	M3_HDATA_WIDTH: The value of this register is derived from the DMAH_M3_HDATA_WIDTH coreConsultant parameter. For a description of this parameter, refer to page 105. 0h = 32 bits 1h = 64 bits 2h = 128 bits 3h = 256 bits
18:17	0h RO	M2_HDATA_WIDTH: The value of this register is derived from the DMAH_M2_HDATA_WIDTH coreConsultant parameter. For a description of this parameter, refer to page 105. 0h = 32 bits 1h = 64 bits 2h = 128 bits 3h = 256 bits
16:15	0h RO	M1_HDATA_WIDTH: The value of this register is derived from the DMAH_M1_HDATA_WIDTH coreConsultant parameter. For a description of this parameter, refer to page 105. 0h = 32 bits 1h = 64 bits 2h = 128 bits 3h = 256 bits
14:13	0h RO	S_HDATA_WIDTH: The value of this register is derived from the DMAH_S_HDATA_WIDTH coreConsultant parameter. For a description of this parameter, refer to page 105. 0h = 32 bits 1h = 64 bits 2h = 128 bits 3h = 256 bits
12:11	01h RO	NUM_MASTER_INT: The value of this register is derived from the DMAH_NUM_MASTER_INT coreConsultant parameter. For a description of this parameter, refer to page 102. 0h = 1 to 3h = 4
10:8	7h RO	NUM_CHANNELS: The value of this register is derived from the DMAH_NUM_CHANNELS coreConsultant parameter. For a description of this parameter, refer to page 102. 0h = 1 to 7h = 8
7:4	0h RW	Undefined0: Reserved.
3	0h RO	MABRST: The value of this register is derived from the DMAH_MABRST coreConsultant parameter. For a description of this parameter, refer to page 103. 0 = FALSE 1 = TRUE
2:1	2h RO	INTR_IO: The value of this register is derived from the DMAH_INTR_IO coreConsultant parameter. For a description of this parameter, refer to page 103. 0h = ALL 1h = TYPE 2h = COMBINED 3h = reserved
0	0h RO	BIG_ENDIAN: The value of this register is derived from the DMAH_BIG_ENDIAN coreConsultant parameter. For a description of this parameter, refer to page 104. 0 = FALSE 1 = TRUE



24.3.251 DMA Component ID RegisterDma - Low (DmaCompsID_LO)— Offset 3F8h

This is the DW_ahb_dmac Component Version register, which is a read-only register that specifies the version of the packaged component in the upper 32 bits and the component type in the lower 32 bits.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 44571110h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	1	0	0	0
0	1	0	0	0	1	0	0	0
0	1	0	1	0	1	1	0	0
0	0	0	1	0	0	0	1	0
0	0	0	1	0	0	0	1	0
0	0	0	1	0	0	0	1	0
0	0	0	1	0	0	0	1	0
DMA_COMP_TYPE								

Bit Range	Default & Access	Field Name (ID): Description
31:0	44571110h RO	Designware Component Type (DMA_COMP_TYPE): Designware Component Type number = 0x44_57_11_10. This assigned unique hex value is constant and is derived from the two ASCII letters -DW- followed by a 32-bit unsigned number.



24.3.252 DMA Component ID Register - High (DmaCompsID_HI)—Offset 3FCh

This is the DW_ahb_dmac Component Version register, which is a read-only register that specifies the version of the packaged component in the upper 32 bits and the component type in the lower 32 bits.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:0] + 10h

Default: 3231362Ah

31	28	24	20	16	12	8	4	0											
0	0	1	1	0	0	1	0	0	0	1	1	0	0	1	0	1	0	1	0
DMA_COMP_VERSION																			

Bit Range	Default & Access	Field Name (ID): Description
31:0	3231362ah RO	Version of the Component (DMA_COMP_VERSION): Reserved.

24.4.3 Revision ID and Class Code (REVCLASSCODE)—Offset 8h

Bit Range	Default & Access	Field Name (ID): Description
7:3	00h RO	Reserved5: Reserved.
2	0h RW	Bus Master Enable (BME): If this bit is 0, Bridge does not generate any new upstream transaction on IOSF as a master.
1	0h RW	Memory Space Enable (MSE): This bit controls Bridge's response to downstream Memory accesses. When set, accesses to memory space of the device is enabled.
0	0h RO	Reserved6: Reserved.

24.4.3 Revision ID and Class Code (REVCLASSCODE)—Offset 8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:0] + 8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES						RID		

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Class Code (CLASS_CODES): The Class Code register is read-only and used to identify the generic function of the device and, in some cases, a specific register level programming interface. The register is broken into three byte size fields. The upper byte (at offset 0Bh) is a base class code which broadly classifies the type of function the device performs. The middle byte (at offset 0Ah) is a sub-class code which identifies more specifically the function of the device. The lower byte (at offset 09h) identifies a specific register-level programming interface (if any) so that device independent software can interact with the device. This register is tied to a strap at the top level.
7:0	00h RO	Revision ID (RID): Revision ID identifies the revision of particular AHB device. This is tied to a strap at the top level.

24.4.4 Cache Line Latency Header and BIST (CLLATHEADERBIST)—Offset Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:0] + Ch

Default: 00800000h



31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				MULFNDEV	HEADERTYPE			
					LATTIMER			
								CACHELINE_SIZE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

24.4.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR						SIZEINDICATOR	PREFETCHABLE	TYPE
								MESSAGE_SPACE

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SUBSYSTEMID					SUBSYSTEMVENDORID			

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW/O	Subsystem ID (SUBSYSTEMID): This register should be implemented for any function that could be instantiated more than once in a given system. The SID register, in combination with the Subsystem Vendor ID register, make it possible for the operating environment to distinguish one audio subsystem from the other. This register is a Read Write Once type register.
15:0	0000h RW/O	Subsystem Vendor ID (SUBSYSTEMVENDORID): This register should be implemented for any function that could be instantiated more than once in a given system. The SVID register, in combination with the Subsystem ID register, enables the operating environment to distinguish one subsystem from the other. This register is a Read Write Once register.

24.4.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:0] + 30h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSION_ROM_BASE								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	EXPANSION_ROM_BASE: Reserved.

24.4.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:0] + 34h



Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.
7:0	00h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. If PM capability is disabled then this register has 00h.

24.4.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:0] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	1	0	0
MAX_LAT				MIN_GNT				INTLINE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a Single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to tell software which interrupt line the interrupt pin is connected to.

24.4.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:0] + 80h



Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
PMESUPPORT				Reserved0	VERSION	NXTCAP	POWER_CAP	

Bit Range	Default & Access	Field Name (ID): Description
31:27	00h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. - bit(11) X XXX1b - PME# can be asserted from D0. - bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. - bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. - bit(14) X 1XXXb - PME# can be asserted from D3hot. - bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the strap strap_pme_support.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.

24.4.12 PME Control and Status Register (PMECTRLSTATUS)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:0] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				PMESTATUS	Reserved1	PMEENABLE	Reserved2	NO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit (bit 8 in this register).
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.
3	1h RO	No_Soft_Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state - Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for Downstream decode on fabric ports.

24.4.13 Manufacturer ID (MANID)—Offset F8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:0] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

MANID

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



24.5 SIO DMA Memory Mapped I/O Registers for I2C

Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"Source Address Register for Channel 0 - Low (SAR0_LO)—Offset 0h" on page 3635	00000000h
4–7h	4	"Source Address Register for Channel 0 - High (SAR0_HI)—Offset 4h" on page 3635	00000000h
8–Bh	4	"Destination Address Register for Channel 0 - Low (DAR0_LO)—Offset 8h" on page 3636	00000000h
C–Fh	4	"Destination Address Register for Channel 0 - High (DAR0_HI)—Offset Ch" on page 3636	00000000h
10–13h	4	"Linked List Pointer Register for Channel 0 - Low (LLP0_LO)—Offset 10h" on page 3637	00000000h
14–17h	4	"Linked List Pointer Register for Channel 0 - High (LLP0_HI)—Offset 14h" on page 3637	00000000h
18–1Bh	4	"Control Register for Channel 0 - Low (CTL0_LO)—Offset 18h" on page 3638	00304801h
1C–1Fh	4	"Control Register for Channel 0 - High (CTL0_HI)—Offset 1Ch" on page 3639	00000002h
20–23h	4	"Source Status Register for Channel 0 - Low (SSTAT0_LO)—Offset 20h" on page 3640	00000000h
24–27h	4	"Source Status Register for Channel 0 - High (SSTAT0_HI)—Offset 24h" on page 3640	00000000h
28–2Bh	4	"Dest Status Register for Channel 0 - Low (DSTAT0_LO)—Offset 28h" on page 3641	00000000h
2C–2Fh	4	"Dest Status Register for Channel 0 - High (DSTAT0_HI)—Offset 2Ch" on page 3641	00000000h
30–33h	4	"Source Status Address Register for Channel 0 - Low (SSTATAR0_LO)—Offset 30h" on page 3642	00000000h
34–37h	4	"Source Status Address Register for Channel 0 - High (SSTATAR0_HI)—Offset 34h" on page 3642	00000000h
38–3Bh	4	"Dest Status Address Register for Channel 0 - Low (DSTATAR0_LO)—Offset 38h" on page 3643	00000000h
3C–3Fh	4	"Dest Status Address Register for Channel 0 - High (DSTATAR0_HI)—Offset 3Ch" on page 3643	00000000h
40–43h	4	"Configuration Register for Channel 0 - Low (CFG0_LO)—Offset 40h" on page 3644	00000E00h
44–47h	4	"Configuration Register for Channel 0 - High (CFG0_HI)—Offset 44h" on page 3645	00000004h
48–4Bh	4	"Source Gather Register for Channel 0 - Low (SGR0_LO)—Offset 48h" on page 3646	00000000h
4C–4Fh	4	"Source Gather Register for Channel 0 - High (SGR0_HI)—Offset 4Ch" on page 3647	00000000h
50–53h	4	"Destination Scatter Register for Channel 0 - Low (DSR0_LO)—Offset 50h" on page 3647	00000000h
54–57h	4	"Dest Scatter Register for Channel 0 - High (DSR0_HI)—Offset 54h" on page 3648	00000000h
58–5Bh	4	"Source Address Register for Channel 1 - Low (SAR1_LO)—Offset 58h" on page 3648	00000000h
5C–5Fh	4	"Source Address Register for Channel 1 - High (SAR1_HI)—Offset 5Ch" on page 3649	00000000h




Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
60–63h	4	"Destination Address Register for Channel 1 - Low (DAR1_LO)—Offset 60h" on page 3649	00000000h
64–67h	4	"Destination Address Register for Channel 1 - High (DAR1_HI)—Offset 64h" on page 3650	00000000h
68–6Bh	4	"Linked List Pointer Register for Channel 1 - Low (LLP1_LO)—Offset 68h" on page 3650	00000000h
6C–6Fh	4	"Linked List Pointer Register for Channel 1 - High (LLP1_HI)—Offset 6Ch" on page 3651	00000000h
70–73h	4	"Control Register for Channel 1 - Low (CTL1_LO)—Offset 70h" on page 3651	00304801h
74–77h	4	"Control Register for Channel 1 - High (CTL1_HI)—Offset 74h" on page 3652	00000002h
78–7Bh	4	"Source Status Register for Channel 1 - Low (SSTAT1_LO)—Offset 78h" on page 3653	00000000h
7C–7Fh	4	"Source Status Register for Channel 1 - High (SSTAT1_HI)—Offset 7Ch" on page 3653	00000000h
80–83h	4	"Dest Status Register for Channel 1 - Low (DSTAT1_LO)—Offset 80h" on page 3654	00000000h
84–87h	4	"Dest Status Register for Channel 1 - High (DSTAT1_HI)—Offset 84h" on page 3654	00000000h
88–8Bh	4	"Source Status Address Register for Channel 1 - Low (SSTATAR1_LO)—Offset 88h" on page 3655	00000000h
8C–8Fh	4	"Source Status Address Register for Channel 1 - High (SSTATAR1_HI)—Offset 8Ch" on page 3655	00000000h
90–93h	4	"Dest Status Address Register for Channel 1 - Low (DSTATAR1_LO)—Offset 90h" on page 3656	00000000h
94–97h	4	"Dest Status Address Register for Channel 1 - High (DSTATAR1_HI)—Offset 94h" on page 3656	00000000h
98–9Bh	4	"Configuration Register for Channel 1 - Low (CFG1_LO)—Offset 98h" on page 3657	00000E20h
9C–9Fh	4	"Configuration Register for Channel 1 - High (CFG1_HI)—Offset 9Ch" on page 3658	00000004h
A0–A3h	4	"Source Gather Register for Channel 1 - Low (SGR1_LO)—Offset A0h" on page 3659	00000000h
A4–A7h	4	"Source Gather Register for Channel 1 - High (SGR1_HI)—Offset A4h" on page 3660	00000000h
A8–ABh	4	"Destination Scatter Register for Channel 1 - Low (DSR1_LO)—Offset A8h" on page 3660	00000000h
AC–AFh	4	"Dest Scatter Register for Channel 1 - High (DSR1_HI)—Offset ACh" on page 3661	00000000h
B0–B3h	4	"Source Address Register for Channel 2 - Low (SAR2_LO)—Offset B0h" on page 3661	00000000h
B4–B7h	4	"Source Address Register for Channel 2 - High (SAR2_HI)—Offset B4h" on page 3662	00000000h
B8–BBh	4	"Destination Address Register for Channel 2 - Low (DAR2_LO)—Offset B8h" on page 3662	00000000h
BC–BFh	4	"Destination Address Register for Channel 2 - High (DAR2_HI)—Offset BCh" on page 3663	00000000h
C0–C3h	4	"Linked List Pointer Register for Channel 2 - Low (LLP2_LO)—Offset C0h" on page 3663	00000000h

**Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR (Continued)**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
C4–C7h	4	"Linked List Pointer Register for Channel 2 - High (LLP2_HI)—Offset C4h" on page 3664	00000000h
C8–CBh	4	"Control Register for Channel 2 - Low (CTL2_LO)—Offset C8h" on page 3664	00304801h
CC–CFh	4	"Control Register for Channel 2 - High (CTL2_HI)—Offset CCh" on page 3665	00000002h
D0–D3h	4	"Source Status Register for Channel 2 - Low (SSTAT2_LO)—Offset D0h" on page 3666	00000000h
D4–D7h	4	"Source Status Register for Channel 2 - High (SSTAT2_HI)—Offset D4h" on page 3666	00000000h
D8–DBh	4	"Dest Status Register for Channel 2 - Low (DSTAT2_LO)—Offset D8h" on page 3667	00000000h
DC–DFh	4	"Dest Status Register for Channel 2 - High (DSTAT2_HI)—Offset DCh" on page 3667	00000000h
E0–E3h	4	"Source Status Address Register for Channel 2 - Low (SSTATAR2_LO)—Offset E0h" on page 3668	00000000h
E4–E7h	4	"Source Status Address Register for Channel 2 - High (SSTATAR2_HI)—Offset E4h" on page 3668	00000000h
E8–EBh	4	"Dest Status Address Register for Channel 2 - Low (DSTATAR2_LO)—Offset E8h" on page 3669	00000000h
EC–EFh	4	"Dest Status Address Register for Channel 2 - High (DSTATAR2_HI)—Offset ECh" on page 3669	00000000h
F0–F3h	4	"Configuration Register for Channel 2 - Low (CFG2_LO)—Offset F0h" on page 3670	00000E40h
F4–F7h	4	"Configuration Register for Channel 2 - High (CFG2_HI)—Offset F4h" on page 3671	00000004h
F8–FBh	4	"Source Gather Register for Channel 2 - Low (SGR2_LO)—Offset F8h" on page 3672	00000000h
FC–FFh	4	"Source Gather Register for Channel 2 - High (SGR2_HI)—Offset FCh" on page 3673	00000000h
100–103h	4	"Destination Scatter Register for Channel 2 - Low (DSR2_LO)—Offset 100h" on page 3673	00000000h
104–107h	4	"Dest Scatter Register for Channel 2 - High (DSR2_HI)—Offset 104h" on page 3674	00000000h
108–10Bh	4	"Source Address Register for Channel 3 - Low (SAR3_LO)—Offset 108h" on page 3674	00000000h
10C–10Fh	4	"Source Address Register for Channel 3 - High (SAR3_HI)—Offset 10Ch" on page 3675	00000000h
110–113h	4	"Destination Address Register for Channel 3 - Low (DAR3_LO)—Offset 110h" on page 3675	00000000h
114–117h	4	"Destination Address Register for Channel 3 - High (DAR3_HI)—Offset 114h" on page 3676	00000000h
118–11Bh	4	"Linked List Pointer Register for Channel 3 - Low (LLP3_LO)—Offset 118h" on page 3676	00000000h
11C–11Fh	4	"Linked List Pointer Register for Channel 3 - High (LLP3_HI)—Offset 11Ch" on page 3677	00000000h
120–123h	4	"Control Register for Channel 3 - Low (CTL3_LO)—Offset 120h" on page 3677	00304801h
124–127h	4	"Control Register for Channel 3 - High (CTL3_HI)—Offset 124h" on page 3678	00000002h
128–12Bh	4	"Source Status Register for Channel 3 - Low (SSTAT3_LO)—Offset 128h" on page 3679	00000000h



Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
12C–12Fh	4	"Source Status Register for Channel 3 - High (SSTAT3_HI)—Offset 12Ch" on page 3679	00000000h
130–133h	4	"Dest Status Register for Channel 3 - Low (DSTAT3_LO)—Offset 130h" on page 3680	00000000h
134–137h	4	"Dest Status Register for Channel 3 - High (DSTAT3_HI)—Offset 134h" on page 3680	00000000h
138–13Bh	4	"Source Status Address Register for Channel 3 - Low (SSTATAR3_LO)—Offset 138h" on page 3681	00000000h
13C–13Fh	4	"Source Status Address Register for Channel 3 - High (SSTATAR3_HI)—Offset 13Ch" on page 3681	00000000h
140–143h	4	"Dest Status Address Register for Channel 3 - Low (DSTATAR3_LO)—Offset 140h" on page 3682	00000000h
144–147h	4	"Dest Status Address Register for Channel 3 - High (DSTATAR3_HI)—Offset 144h" on page 3682	00000000h
148–14Bh	4	"Configuration Register for Channel 3 - Low (CFG3_LO)—Offset 148h" on page 3683	00000E60h
14C–14Fh	4	"Configuration Register for Channel 3 - High (CFG3_HI)—Offset 14Ch" on page 3684	00000004h
150–153h	4	"Source Gather Register for Channel 3 - Low (SGR3_LO)—Offset 150h" on page 3685	00000000h
154–157h	4	"Source Gather Register for Channel 3 - High (SGR3_HI)—Offset 154h" on page 3686	00000000h
158–15Bh	4	"Destination Scatter Register for Channel 3 - Low (DSR3_LO)—Offset 158h" on page 3686	00000000h
15C–15Fh	4	"Dest Scatter Register for Channel 3 - High (DSR3_HI)—Offset 15Ch" on page 3687	00000000h
160–163h	4	"Source Address Register for Channel 4 - Low (SAR4_LO)—Offset 160h" on page 3687	00000000h
164–167h	4	"Source Address Register for Channel 4 - High (SAR4_HI)—Offset 164h" on page 3688	00000000h
168–16Bh	4	"Destination Address Register for Channel 4 - Low (DAR4_LO)—Offset 168h" on page 3688	00000000h
16C–16Fh	4	"Destination Address Register for Channel 4 - High (DAR4_HI)—Offset 16Ch" on page 3689	00000000h
170–173h	4	"Linked List Pointer Register for Channel 4 - Low (LLP4_LO)—Offset 170h" on page 3689	00000000h
174–177h	4	"Linked List Pointer Register for Channel 4 - High (LLP4_HI)—Offset 174h" on page 3690	00000000h
178–17Bh	4	"Control Register for Channel 4 - Low (CTL4_LO)—Offset 178h" on page 3690	00304801h
17C–17Fh	4	"Control Register for Channel 4 - High (CTL4_HI)—Offset 17Ch" on page 3691	00000002h
180–183h	4	"Source Status Register for Channel 4 - Low (SSTAT4_LO)—Offset 180h" on page 3692	00000000h
184–187h	4	"Source Status Register for Channel 4 - High (SSTAT4_HI)—Offset 184h" on page 3692	00000000h
188–18Bh	4	"Dest Status Register for Channel 4 - Low (DSTAT4_LO)—Offset 188h" on page 3693	00000000h
18C–18Fh	4	"Dest Status Register for Channel 4 - High (DSTAT4_HI)—Offset 18Ch" on page 3693	00000000h



Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
190–193h	4	"Source Status Address Register for Channel 4 - Low (SSTATAR4_LO)—Offset 190h" on page 3694	00000000h
194–197h	4	"Source Status Address Register for Channel 4 - High (SSTATAR4_HI)—Offset 194h" on page 3694	00000000h
198–19Bh	4	"Dest Status Address Register for Channel 4 - Low (DSTATAR4_LO)—Offset 198h" on page 3695	00000000h
19C–19Fh	4	"Dest Status Address Register for Channel 4 - High (DSTATAR4_HI)—Offset 19Ch" on page 3695	00000000h
1A0–1A3h	4	"Configuration Register for Channel 4 - Low (CFG4_LO)—Offset 1A0h" on page 3696	00000E80h
1A4–1A7h	4	"Configuration Register for Channel 4 - High (CFG4_HI)—Offset 1A4h" on page 3697	00000004h
1A8–1ABh	4	"Source Gather Register for Channel 4 - Low (SGR4_LO)—Offset 1A8h" on page 3698	00000000h
1AC–1AFh	4	"Source Gather Register for Channel 4 - High (SGR4_HI)—Offset 1ACh" on page 3699	00000000h
1B0–1B3h	4	"Destination Scatter Register for Channel 4 - Low (DSR4_LO)—Offset 1B0h" on page 3699	00000000h
1B4–1B7h	4	"Dest Scatter Register for Channel 4 - High (DSR4_HI)—Offset 1B4h" on page 3700	00000000h
1B8–1BBh	4	"Source Address Register for Channel 5 - Low (SAR5_LO)—Offset 1B8h" on page 3700	00000000h
1BC–1BFh	4	"Source Address Register for Channel 5 - High (SAR5_HI)—Offset 1BCh" on page 3701	00000000h
1C0–1C3h	4	"Destination Address Register for Channel 5 - Low (DAR5_LO)—Offset 1C0h" on page 3701	00000000h
1C4–1C7h	4	"Destination Address Register for Channel 5 - High (DAR5_HI)—Offset 1C4h" on page 3702	00000000h
1C8–1CBh	4	"Linked List Pointer Register for Channel 5 - Low (LLP5_LO)—Offset 1C8h" on page 3702	00000000h
1CC–1CFh	4	"Linked List Pointer Register for Channel 5 - High (LLP5_HI)—Offset 1CCh" on page 3703	00000000h
1D0–1D3h	4	"Control Register for Channel 5 - Low (CTL5_LO)—Offset 1D0h" on page 3703	00304801h
1D4–1D7h	4	"Control Register for Channel 5 - High (CTL5_HI)—Offset 1D4h" on page 3704	00000002h
1D8–1DBh	4	"Source Status Register for Channel 5 - Low (SSTAT5_LO)—Offset 1D8h" on page 3705	00000000h
1DC–1DFh	4	"Source Status Register for Channel 5 - High (SSTAT5_HI)—Offset 1DCh" on page 3705	00000000h
1E0–1E3h	4	"Dest Status Register for Channel 5 - Low (DSTAT5_LO)—Offset 1E0h" on page 3706	00000000h
1E4–1E7h	4	"Dest Status Register for Channel 5 - High (DSTAT5_HI)—Offset 1E4h" on page 3706	00000000h
1E8–1EBh	4	"Source Status Address Register for Channel 5 - Low (SSTATAR5_LO)—Offset 1E8h" on page 3707	00000000h
1EC–1EFh	4	"Source Status Address Register for Channel 5 - High (SSTATAR5_HI)—Offset 1ECh" on page 3707	00000000h
1F0–1F3h	4	"Dest Status Address Register for Channel 5 - Low (DSTATAR5_LO)—Offset 1F0h" on page 3708	00000000h



Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
1F4–1F7h	4	"Dest Status Address Register for Channel 5 - High (DSTATAR5_HI)—Offset 1F4h" on page 3708	00000000h
1F8–1FBh	4	"Configuration Register for Channel 5 - Low (CFG5_LO)—Offset 1F8h" on page 3709	00000EA0h
1FC–1FFh	4	"Configuration Register for Channel 5 - High (CFG5_HI)—Offset 1FCh" on page 3710	00000004h
200–203h	4	"Source Gather Register for Channel 5 - Low (SGR5_LO)—Offset 200h" on page 3711	00000000h
204–207h	4	"Source Gather Register for Channel 5 - High (SGR5_HI)—Offset 204h" on page 3712	00000000h
208–20Bh	4	"Destination Scatter Register for Channel 5 - Low (DSR5_LO)—Offset 208h" on page 3712	00000000h
20C–20Fh	4	"Dest Scatter Register for Channel 5 - High (DSR5_HI)—Offset 20Ch" on page 3713	00000000h
210–213h	4	"Source Address Register for Channel 6 - Low (SAR6_LO)—Offset 210h" on page 3713	00000000h
214–217h	4	"Source Address Register for Channel 6 - High (SAR6_HI)—Offset 214h" on page 3713	00000000h
218–21Bh	4	"Destination Address Register for Channel 6 - Low (DAR6_LO)—Offset 218h" on page 3714	00000000h
21C–21Fh	4	"Destination Address Register for Channel 6 - High (DAR6_HI)—Offset 21Ch" on page 3714	00000000h
220–223h	4	"Linked List Pointer Register for Channel 6 - Low (LLP6_LO)—Offset 220h" on page 3715	00000000h
224–227h	4	"Linked List Pointer Register for Channel 6 - High (LLP6_HI)—Offset 224h" on page 3715	00000000h
228–22Bh	4	"Control Register for Channel 6 - Low (CTL6_LO)—Offset 228h" on page 3716	00304801h
22C–22Fh	4	"Control Register for Channel 6 - High (CTL6_HI)—Offset 22Ch" on page 3717	00000002h
230–233h	4	"Source Status Register for Channel 6 - Low (SSTAT6_LO)—Offset 230h" on page 3718	00000000h
234–237h	4	"Source Status Register for Channel 6 - High (SSTAT6_HI)—Offset 234h" on page 3718	00000000h
238–23Bh	4	"Dest Status Register for Channel 6 - Low (DSTAT6_LO)—Offset 238h" on page 3719	00000000h
23C–23Fh	4	"Dest Status Register for Channel 6 - High (DSTAT6_HI)—Offset 23Ch" on page 3719	00000000h
240–243h	4	"Source Status Address Register for Channel 6 - Low (SSTATAR6_LO)—Offset 240h" on page 3720	00000000h
244–247h	4	"Source Status Address Register for Channel 6 - High (SSTATAR6_HI)—Offset 244h" on page 3720	00000000h
248–24Bh	4	"Dest Status Address Register for Channel 6 - Low (DSTATAR6_LO)—Offset 248h" on page 3721	00000000h
24C–24Fh	4	"Dest Status Address Register for Channel 6 - High (DSTATAR6_HI)—Offset 24Ch" on page 3721	00000000h
250–253h	4	"Configuration Register for Channel 6 - Low (CFG6_LO)—Offset 250h" on page 3722	00000EC0h
254–257h	4	"Configuration Register for Channel 6 - High (CFG6_HI)—Offset 254h" on page 3723	00000004h

**Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR (Continued)**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
258–25Bh	4	"Source Gather Register for Channel 6 - Low (SGR6_LO)—Offset 258h" on page 3724	00000000h
25C–25Fh	4	"Source Gather Register for Channel 6 - High (SGR6_HI)—Offset 25Ch" on page 3724	00000000h
260–263h	4	"Destination Scatter Register for Channel 6 - Low (DSR6_LO)—Offset 260h" on page 3725	00000000h
264–267h	4	"Dest Scatter Register for Channel 6 - High (DSR6_HI)—Offset 264h" on page 3725	00000000h
268–26Bh	4	"Source Address Register for Channel 7 - Low (SAR7_LO)—Offset 268h" on page 3726	00000000h
26C–26Fh	4	"Source Address Register for Channel 7 - High (SAR7_HI)—Offset 26Ch" on page 3726	00000000h
270–273h	4	"Destination Address Register for Channel 7 - Low (DAR7_LO)—Offset 270h" on page 3727	00000000h
274–277h	4	"Destination Address Register for Channel 7 - High (DAR7_HI)—Offset 274h" on page 3727	00000000h
278–27Bh	4	"Linked List Pointer Register for Channel 7 - Low (LLP7_LO)—Offset 278h" on page 3728	00000000h
27C–27Fh	4	"Linked List Pointer Register for Channel 7 - High (LLP7_HI)—Offset 27Ch" on page 3728	00000000h
280–283h	4	"Control Register for Channel 7 - Low (CTL7_LO)—Offset 280h" on page 3729	00304801h
284–287h	4	"Control Register for Channel 7 - High (CTL7_HI)—Offset 284h" on page 3730	00000002h
288–28Bh	4	"Source Status Register for Channel 7 - Low (SSTAT7_LO)—Offset 288h" on page 3731	00000000h
28C–28Fh	4	"Source Status Register for Channel 7 - High (SSTAT7_HI)—Offset 28Ch" on page 3731	00000000h
290–293h	4	"Dest Status Register for Channel 7 - Low (DSTAT7_LO)—Offset 290h" on page 3732	00000000h
294–297h	4	"Dest Status Register for Channel 7 - High (DSTAT7_HI)—Offset 294h" on page 3732	00000000h
298–29Bh	4	"Source Status Address Register for Channel 7 - Low (SSTATAR7_LO)—Offset 298h" on page 3733	00000000h
29C–29Fh	4	"Source Status Address Register for Channel 7 - High (SSTATAR7_HI)—Offset 29Ch" on page 3733	00000000h
2A0–2A3h	4	"Dest Status Address Register for Channel 7 - Low (DSTATAR7_LO)—Offset 2A0h" on page 3734	00000000h
2A4–2A7h	4	"Dest Status Address Register for Channel 7 - High (DSTATAR7_HI)—Offset 2A4h" on page 3734	00000000h
2A8–2ABh	4	"Configuration Register for Channel 7 - Low (CFG7_LO)—Offset 2A8h" on page 3735	00000EE0h
2AC–2AFh	4	"Configuration Register for Channel 7 - High (CFG7_HI)—Offset 2ACh" on page 3736	00000004h
2B0–2B3h	4	"Source Gather Register for Channel 7 - Low (SGR7_LO)—Offset 2B0h" on page 3737	00000000h
2B4–2B7h	4	"Source Gather Register for Channel 7 - High (SGR7_HI)—Offset 2B4h" on page 3737	00000000h
2B8–2BBh	4	"Destination Scatter Register for Channel 7 - Low (DSR7_LO)—Offset 2B8h" on page 3738	00000000h



Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
2BC–2BFh	4	"Dest Scatter Register for Channel 7 - High (DSR7_HI)—Offset 2BCh" on page 3738	00000000h
2C0–2C3h	4	"Interrupt Raw Status Registers - Low (RawTfr_LO)—Offset 2C0h" on page 3739	00000000h
2C4–2C7h	4	"Interrupt Raw Status Registers - High (RawTfr_HI)—Offset 2C4h" on page 3740	00000000h
2C8–2CBh	4	"Interrupt Raw Status Registers - Low (RawBlock_LO)—Offset 2C8h" on page 3740	00000000h
2CC–2CFh	4	"Interrupt Raw Status Registers - High (RawBlock_HI)—Offset 2CCh" on page 3741	00000000h
2D0–2D3h	4	"Interrupt Raw Status Registers - Low (RawSrcTran_LO)—Offset 2D0h" on page 3741	00000000h
2D4–2D7h	4	"Interrupt Raw Status Registers - High (RawSrcTran_HI)—Offset 2D4h" on page 3742	00000000h
2D8–2DBh	4	"Interrupt Raw Status Registers - Low (RawDstTran_LO)—Offset 2D8h" on page 3742	00000000h
2DC–2DFh	4	"Interrupt Raw Status Registers - High (RawDstTran_HI)—Offset 2DCh" on page 3743	00000000h
2E0–2E3h	4	"Interrupt Raw Status Registers - Low (RawErr_LO)—Offset 2E0h" on page 3743	00000000h
2E4–2E7h	4	"Interrupt Raw Status Registers - High (RawErr_HI)—Offset 2E4h" on page 3744	00000000h
2E8–2EBh	4	"Interrupt Status Registers - Low (StatusTfr_LO)—Offset 2E8h" on page 3744	00000000h
2EC–2EFh	4	"Interrupt Status Registers - High (StatusTfr_HI)—Offset 2ECh" on page 3745	00000000h
2F0–2F3h	4	"Interrupt Status Registers - Low (StatusBlock_LO)—Offset 2F0h" on page 3745	00000000h
2F4–2F7h	4	"Interrupt Status Registers - High (StatusBlock_HI)—Offset 2F4h" on page 3746	00000000h
2F8–2FBh	4	"Interrupt Status Registers - Low (StatusSrcTran_LO)—Offset 2F8h" on page 3746	00000000h
2FC–2FFh	4	"Interrupt Status Registers - High (StatusSrcTran_HI)—Offset 2FCh" on page 3747	00000000h
300–303h	4	"Interrupt Status Registers - Low (StatusDstTran_LO)—Offset 300h" on page 3747	00000000h
304–307h	4	"Interrupt Status Registers - High (StatusDstTran_HI)—Offset 304h" on page 3748	00000000h
308–30Bh	4	"Interrupt Status Registers - Low (StatusErr_LO)—Offset 308h" on page 3748	00000000h
30C–30Fh	4	"Interrupt Status Registers - High (StatusErr_HI)—Offset 30Ch" on page 3749	00000000h
310–313h	4	"Interrupt Mask Registers - Low (MaskTfr_LO)—Offset 310h" on page 3749	00000000h
314–317h	4	"Interrupt Mask Registers - High (MaskTfr_HI)—Offset 314h" on page 3750	00000000h
318–31Bh	4	"Interrupt Mask Registers - Low (MaskBlock_LO)—Offset 318h" on page 3750	00000000h
31C–31Fh	4	"Interrupt Mask Registers - High (MaskBlock_HI)—Offset 31Ch" on page 3751	00000000h
320–323h	4	"Interrupt Mask Registers - Low (MaskSrcTran_LO)—Offset 320h" on page 3751	00000000h
324–327h	4	"Interrupt Mask Registers - High (MaskSrcTran_HI)—Offset 324h" on page 3752	00000000h
328–32Bh	4	"Interrupt Mask Registers - Low (MaskDstTran_LO)—Offset 328h" on page 3752	00000000h
32C–32Fh	4	"Interrupt Mask Registers - High (MaskDstTran_HI)—Offset 32Ch" on page 3753	00000000h
330–333h	4	"Interrupt Mask Registers - Low (MaskErr_LO)—Offset 330h" on page 3753	00000000h



Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
334–337h	4	"Interrupt Mask Registers - High (MaskErr_HI)—Offset 334h" on page 3754	00000000h
338–33Bh	4	"Interrupt Clear Registers - Low (ClearTfr_LO)—Offset 338h" on page 3754	00000000h
33C–33Fh	4	"Interrupt Clear Registers - High (ClearTfr_HI)—Offset 33Ch" on page 3755	00000000h
340–343h	4	"Interrupt Clear Registers - Low (ClearBlock_LO)—Offset 340h" on page 3756	00000000h
344–347h	4	"Interrupt Clear Registers (ClearBlock_HI)—Offset 344h" on page 3756	00000000h
348–34Bh	4	"Interrupt Clear Registers - Low (ClearSrcTran_LO)—Offset 348h" on page 3757	00000000h
34C–34Fh	4	"Interrupt Clear RegistersClearSrc - High (ClearSrcTran_HI)—Offset 34Ch" on page 3757	00000000h
350–353h	4	"Interrupt Clear Registers - Low (ClearDstTran_LO)—Offset 350h" on page 3758	00000000h
354–357h	4	"Interrupt Clear Registers - High (ClearDstTran_HI)—Offset 354h" on page 3758	00000000h
358–35Bh	4	"Interrupt Clear Registers - Low (ClearErr_LO)—Offset 358h" on page 3759	00000000h
35C–35Fh	4	"Interrupt Clear Registers - High (ClearErr_HI)—Offset 35Ch" on page 3759	00000000h
360–363h	4	"Combined Interrupt Status Register - Low (StatusInt_LO)—Offset 360h" on page 3760	00000000h
364–367h	4	"Combined Interrupt Status Register - High (StatusInt_HI)—Offset 364h" on page 3760	00000000h
368–36Bh	4	"Source Software Transaction Request Register - Low (ReqSrcReg_LO)—Offset 368h" on page 3761	00000000h
36C–36Fh	4	"Source Software Transaction Request Register - High (ReqSrcReg_HI)—Offset 36Ch" on page 3762	00000000h
370–373h	4	"Destination Software Transaction Request Register - Low (ReqDstReg_LO)—Offset 370h" on page 3762	00000000h
374–377h	4	"Destination Software Transaction Request Register - High (ReqDstReg_HI)—Offset 374h" on page 3763	00000000h
378–37Bh	4	"Single Source Software Transaction Request Register - Low (SglRqSrcReg_LO)—Offset 378h" on page 3763	00000000h
37C–37Fh	4	"Single Source Software Transaction Request Register - High (SglRqSrcReg_HI)—Offset 37Ch" on page 3764	00000000h
380–383h	4	"Single Destination Software Transaction Request Register - Low (SglRqDstReg_LO)—Offset 380h" on page 3765	00000000h
384–387h	4	"Single Destination Software Transaction Request Register - High (SglRqDstReg_HI)—Offset 384h" on page 3765	00000000h
388–38Bh	4	"Last Source Transaction Request Register - Low (LstSrcReg_LO)—Offset 388h" on page 3766	00000000h
38C–38Fh	4	"Last Source Transaction Request Register - High (LstSrcReg_HI)—Offset 38Ch" on page 3766	00000000h
390–393h	4	"Last Destination Transaction Request Register - Low (LstDstReg_LO)—Offset 390h" on page 3767	00000000h
394–397h	4	"Last Destination Transaction Request Register - High (LstDstReg_HI)—Offset 394h" on page 3768	00000000h
398–39Bh	4	"DW_ahb_dmac Configuration Register - Low (DmaCfgReg_LO)—Offset 398h" on page 3768	00000000h
39C–39Fh	4	"DW_ahb_dmac Configuration Register - High (DmaCfgReg_HI)—Offset 39Ch" on page 3769	00000000h
3A0–3A3h	4	"DW_ahb_dmac Channel Enable Register - Low (ChEnReg_LO)—Offset 3A0h" on page 3769	00000000h



Table 255. Summary of SIO DMA 2 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
3A4–3A7h	4	"DW_ahb_dmac Channel Enable Register - High (ChEnReg_HI)—Offset 3A4h" on page 3770	00000000h
3A8–3ABh	4	"DW_ahb_dmac ID Register - Low (DmaIdReg_LO)—Offset 3A8h" on page 3770	C0CAC01Ah
3AC–3AFh	4	"DW_ahb_dmac ID Register - High (DmaIdReg_HI)—Offset 3ACh" on page 3771	00000000h
3B0–3B3h	4	"DW_ahb_dmac Test Register - Low (DmaTestReg_LO)—Offset 3B0h" on page 3771	00000000h
3B4–3B7h	4	"DW_ahb_dmac Test Register - High (DmaTestReg_HI)—Offset 3B4h" on page 3772	00000000h
3C8–3CBh	4	"DW_ahb_dmac Component Parameters Register 6 - Low (DMA_COMP_PARAMS_6_LO)—Offset 3C8h" on page 3772	00000000h
3CC–3CFh	4	"DW_ahb_dmac Component Parameters Register 6 - High (DMA_COMP_PARAMS_6_HI)—Offset 3CCh" on page 3773	38220300h
3D0–3D3h	4	"DW_ahb_dmac Component Parameters Register 5 - Low (DMA_COMP_PARAMS_5_LO)—Offset 3D0h" on page 3775	38220300h
3D4–3D7h	4	"DW_ahb_dmac Component Parameters Register 5 - High (DMA_COMP_PARAMS_5_HI)—Offset 3D4h" on page 3778	38220300h
3D8–3DBh	4	"DW_ahb_dmac Component Parameters Register 4 - Low (DMA_COMP_PARAMS_4_LO)—Offset 3D8h" on page 3780	38220300h
3DC–3DFh	4	"DW_ahb_dmac Component Parameters Register 4 - High (DMA_COMP_PARAMS_4_HI)—Offset 3DCh" on page 3783	38220300h
3E0–3E3h	4	"DW_ahb_dmac Component Parameters Register 3 - Low (DMA_COMP_PARAMS_3_LO)—Offset 3E0h" on page 3785	38220300h
3E4–3E7h	4	"DW_ahb_dmac Component Parameters Register 3 - High (DMA_COMP_PARAMS_3_HI)—Offset 3E4h" on page 3788	38220300h
3E8–3EBh	4	"DW_ahb_dmac Component Parameters Register 2 - Low (DMA_COMP_PARAMS_2_LO)—Offset 3E8h" on page 3790	38220300h
3EC–3EFh	4	"DW_ahb_dmac Component Parameters Register 2 - High (DMA_COMP_PARAMS_2_HI)—Offset 3ECh" on page 3792	00000000h
3F0–3F3h	4	"DW_ahb_dmac Component Parameters Register 1 - Low (DMA_COMP_PARAMS_1_LO)—Offset 3F0h" on page 3795	AAAAAAAAh
3F4–3F7h	4	"DW_ahb_dmac Component Parameters Register 1 - High (DMA_COMP_PARAMS_1_HI)—Offset 3F4h" on page 3796	37000F04h
3F8–3FBh	4	"DMA Component ID RegisterDma - Low (DmaCompsID_LO)—Offset 3F8h" on page 3798	44571110h
3FC–3FFh	4	"DMA Component ID Register - High (DmaCompsID_HI)—Offset 3FCh" on page 3799	3231362Ah



24.5.1 Source Address Register for Channel 0 - Low (SAR0_LO)—Offset 0h

The starting source address is programmed by software before the DMA channel is enabled, or by an LLI update before the start of the DMA transfer. While the DMA transfer is in progress, this register is updated to reflect the source address of the current AHB transfer.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SAR								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Source Address of DMA Transfer (SAR): Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.

24.5.2 Source Address Register for Channel 0 - High (SAR0_HI)—Offset 4h

Refer to the description for register Source Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



Access Method

Offset: [BAR] + 8h

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Destination Address of DMA Transfer (DAR): Updated after each destination transfer. The DINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every destination transfer throughout the block transfer.

24.5.4 Destination Address Register for Channel 0 - High (DAR0_HI)—Offset Ch

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Offset: [BAR] + Ch

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



24.5.6 Linked List Pointer Register for Channel 0 - High (LLP0_HI)—Offset 14h



24.5.7 Control Register for Channel 0 - Low (CTL0_LO)—Offset 18h

This register contains fields that control the DMA transfer. **Note:** You need to program this register prior to enabling the channel.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 18h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00304801h

31				28				24				20				16				12				8				4				0																															
0				0				0				0				0				0				1				0				1																															
Undefined_				LLP_SRC_EN				LLP_DST_EN				SMS				DMS				TT_FC				Undefined				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZE				DEST_MSIZE				SINC				DINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RW	Undefined_: RESERVED
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPx.LOC is non-zero
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPx.LOC is non-zero.
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): The following transfer types are supported. - Memory to Memory - Memory to Peripheral - Peripheral to Memory - Peripheral to Peripheral Flow Control can be assigned to the DW_ahb_dmac, the source peripheral, or the destination peripheral.
19	0h RW	Undefined: RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZE): Number of data items, each of width CTLx.SRC_TR_WIDTH, to be read from the source every time a source burst transaction request is made from either the corresponding hardware or software handshaking interface.



Bit Range	Default & Access	Field Name (ID): Description
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Number of data items, each of width CTLx.DST_TR_WIDTH, to be written to the destination every time a destination burst transaction request is made from either the corresponding hardware or software handshaking interface.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.5.8 Control Register for Channel 0 - High (CTL0_HI)—Offset 1Ch

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000002h

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																		
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	

Bit Range	Default & Access	Field Name (ID): Description
31:13	0h RW	Undefined_ : RESERVED
12	0h RW	Done Bit (DONE): If status write-back is enabled, the upper word of the control register, CTLx[63:32], is written to the control register location of the Linked List Item (LLI) in system memory at the end of the block transfer with the done bit set. Software can poll the LLI CTLx.DONE bit to see when a block transfer is complete. The LLI CTLx.DONE bit should be cleared when the linked lists are set up in memory, prior to enabling the channel. LLI accesses are always 32-bit accesses (Hsize = 2) aligned to 32-bit boundaries and cannot be changed or programmed to anything other than 32-bit.



Access Method

Offset: [BAR] + 30h

BAR Reference: [B:0, D:24, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.5.14 Source Status Address Register for Channel 0 - High (SSTATAR0_HI)—Offset 34h

Access Method

Offset: [BAR] + 34h

BAR Reference: [B:0, D:24, F:0] + 10h

Diagram illustrating the bit positions (31 down to 0) and the value 0x00000000. The register is divided into four 8-bit segments, each containing eight zeros. A vertical line labeled "Undefined" is positioned between bit 16 and bit 17.



Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.5.15 Dest Status Address Register for Channel 0 - Low (DSTATAR0_LO)—Offset 38h

After the completion of each block transfer, hardware can retrieve the destination status information from the address pointed to by the contents of the DSTATARx register.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTATAR (SSTATAR): Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.5.16 Dest Status Address Register for Channel 0 - High (DSTATAR0_HI)—Offset 3Ch

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Diagram illustrating a 32-bit register state. The register contains 32 bits, all of which are 0. The bits are grouped into 8 sets of 4 bits each. The bit positions are labeled as 31, 28, 24, 20, 16, 12, 8, and 4. A vertical label 'Undefined' is positioned between bit 16 and bit 12.

24.5.17 Configuration Register for Channel 0 - Low (CFG0_LO)—Offset 40h





Access Method

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.23 Source Address Register for Channel 1 - Low (SAR1_LO)—Offset 58h

Access Method

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Source Address of DMA Transfer (SAR): Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.



24.5.24 Source Address Register for Channel 1 - High (SAR1_HI)—Offset 5Ch

Refer to the description for register Source Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 5Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.5.25 Destination Address Register for Channel 1 - Low (DAR1_LO)—Offset 60h

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DAR								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Destination Address of DMA Transfer (DAR): Updated after each destination transfer. The DINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every destination transfer throughout the block transfer.



Access Method

Offset: [BAR] + 64h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.27 Linked List Pointer Register for Channel 1 - Low (LLP1_LO)—Offset 68h

Access Method


Offset: [BAR] + 68h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.



Bit Range	Default & Access	Field Name (ID): Description
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ): Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Refer to the description for CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.5.30 Control Register for Channel 1 - High (CTL1_HI)—Offset 74h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000002h

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
3653



Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.5.33 Dest Status Register for Channel 1 - Low (DSTAT1_LO)—Offset 80h

Access Method

Offset: [BAR] + 80h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest. status information retrieved by hw from the addrx pointed to by DSTATAR0 register.

24.5.34 Dest Status Register for Channel 1 - High (DSTAT1_HI)—Offset 84h

Access Method

Offset: [BAR] + 84h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 90h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31282420161284000																															
---	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

24.5.38 Dest Status Address Register for Channel 1 - High (DSTATAR1_HI)—Offset 94h

Access Method

Offset: [BAR] + 94h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000E20h

31		28				24				20				16				12				8				4				0																															
0		0				0				0				0				0				1				0				0				0																											
RELOAD_DST	RELOAD_SRC					MAX_ABRST								SRC_HS_POL				DST_HS_POL				LOCK_B				LOCK_CH				LOCK_B_L				LOCK_CH_L				HS_SEL_SRC				HS_SEL_DST				FIFO_EMPTY				CH_SUSP				CH_PRIOR				Undefined			

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	Automatic Destination Reload (RELOAD_DST): The DARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
30	0h RW	Automatic Source Reload (RELOAD_SRC): The SARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
29:20	0h RW	Maximum AMBA Burst Length (MAX_ABRST): Maximum AMBA burst length that is used for DMA transfers on this channel. A value of 0 indicates that software is not limiting the maximum AMBA burst length for DMA transfers on this channel.
19	0h RW	Source Handshaking Interface Polarity (SRC_HS_POL): 0 = Active high 1 = Active low
18	0h RW	Destination Handshaking Interface Polarity (DST_HS_POL): 0 = Active high 1 = Active low
17	0h RW	Bus Lock Bit (LOCK_B): When active, the AHB bus master signal hlock is asserted for the duration specified in CFGx.LOCK_B_L.





Bit Range	Default & Access	Field Name (ID): Description
14:11	0h RW	DEST_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the destination of channel x if the CFGx.HS_SEL_DST field is 0; otherwise, this field is ignored.
10:7	0h RW	SRC_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the source of channel x if the CFGx.HS_SEL_SRC field is 0; otherwise, this field is ignored.
6	0h RW	Source Status Update Enable (SS_UPD_EN): Source status information is fetched only from the location pointed to by the SSTATARx register, stored in the SSTATx register and written out to the SSTATx location of the LLI (refer to Figure 52 on page 243) if SS_UPD_EN is high.
5	0h RW	Destination Status Update Enable (DS_UPD_EN): Destination status information is fetched only from the location pointed to by the DSTATARx register, stored in the DSTATx register and written out to the DSTATx location of the LLI if DS_UPD_EN is high.
4:2	1h RW	PROTCTL: Protection Control bits used to drive the AHB HPROT[3:1] bus.
1	0h RW	FIFO Mode Select (FIFO_MODE): Determines how much space or data needs to be available in the FIFO before a burst transaction request is serviced. 0 = Space/data available for single AHB transfer of the specified transfer width. 1 = Data available is greater than or equal to half the FIFO depth for destination transfers and space available is greater than half the fifo depth for source transfers.
0	0h RW	Flow Control Mode (FCMODE): Determines when source transaction requests are serviced when the Destination Peripheral is the flow controller. 0 = Source transaction requests are serviced when they occur. Data pre-fetching is enabled. 1 = Source transaction requests are not serviced until a destination transaction request occurs.

24.5.41 Source Gather Register for Channel 1 - Low (SGR1_LO)—Offset A0h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC	SGI							

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Refer to the description for SGR0_LO.SGI.



Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

	31			28				24				20				16				12				8				4				0		
	0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0
	Undefined																																	

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.43 Destination Scatter Register for Channel 1 - Low (DSR1_LO)—Offset A8h

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Dest Scatter Count (DSC): Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	Dest Scatter Interval (DSI): Refer to the description for DSR0_LO.DSI.



Access Method

Offset: [BAR] + B4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.5.47 Destination Address Register for Channel 2 - Low (DAR2_LO)—Offset B8h

Access Method

Offset: [BAR] + B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DAR: Current Destination address of DMA transfer. Updated after each destination transfer. The DINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every destination transfer throughout the block transfer.



24.5.48 Destination Address Register for Channel 2 - High (DAR2_HI)—Offset BCh

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + BCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.49 Linked List Pointer Register for Channel 2 - Low (LLP2_LO)—Offset C0h

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + C0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LOC								LMS

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.



Bit Range	Default & Access	Field Name (ID): Description
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ): Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Refer to the description for CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.5.52 Control Register for Channel 2 - High (CTL2_HI)—Offset CCh

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + CCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000002h



Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

	31		28		24		20		16		12		8		4		0
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
SSTAT																	

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTAT : Source status information retrieved by hw from the addrx pointed to by SSTATAR0 register.

24.5.54 Source Status Register for Channel 2 - High (SSTAT2_HI)—Offset D4h

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

October 2018
Document Number: 538136, Rev. 4.3



Access Method

Offset: [BAR] + D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest status information retrieved by hw from the addrx pointed to by DSTATAR0 register.

24.5.56 Dest Status Register for Channel 2 - High (DSTAT2_HI)—Offset DCh

Access Method

Offset: [BAR] + DCh**BAR Type:** PCI Configuration Register (Size: 32 bits)

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.5.57 Source Status Address Register for Channel 2 - Low (SSTATAR2_LO)—Offset E0h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SSTATAR								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.						

24.5.58 Source Status Address Register for Channel 2 - High (SSTATAR2_HI)—Offset E4h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + E4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.5.59 Dest Status Address Register for Channel 2 - Low (DSTATAR2_LO)—Offset E8h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

3128242016128400																															
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

24.5.60 Dest Status Address Register for Channel 2 - High (DSTATAR2_HI)—Offset ECh

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + ECh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + F0h

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000E40h

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	Automatic Destination Reload (RELOAD_DST): The DARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
30	0h RW	Automatic Source Reload (RELOAD_SRC): The SARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
29:20	0h RW	Maximum AMBA Burst Length (MAX_ABRST): Maximum AMBA burst length that is used for DMA transfers on this channel. A value of 0 indicates that software is not limiting the maximum AMBA burst length for DMA transfers on this channel.
19	0h RW	Source Handshaking Interface Polarity (SRC_HS_POL): 0 = Active high 1 = Active low
18	0h RW	Destination Handshaking Interface Polarity (DST_HS_POL): 0 = Active high 1 = Active low
17	0h RW	Bus Lock Bit (LOCK_B): When active, the AHB bus master signal hlock is asserted for the duration specified in CFGx.LOCK_B_L.



Bit Range	Default & Access	Field Name (ID): Description
16	0h RW	Channel Lock Bit (LOCK_CH): When the channel is granted control of the master bus interface and if the CFGx.LOCK_CH bit is asserted, then no other channels are granted control of the master bus interface for the duration specified in CFGx.LOCK_CH_L. Indicates to the master bus interface arbiter that this channel wants exclusive access to the master bus interface for the duration specified in CFGx.LOCK_CH_L.
15:14	0h RW	Bus Lock Level (LOCK_B_L): Indicates the duration over which CFGx.LOCK_B bit applies. 00 = Over complete DMA transfer 01 = Over complete DMA block transfer 1x = Over complete DMA transaction
13:12	0h RW	Channel Lock Level (LOCK_CH_L): Indicates the duration over which CFGx.LOCK_CH bit applies. 00 = DMA transfer 01 = DMA block transfer 1x = DMA transaction
11	1h RW	Source Software or Hardware Handshaking Select (HS_SEL_SRC): 0 = HW handshaking 1 = SW handshaking
10	1h RW	Destination Software or Hardware Handshaking Select (HS_SEL_DST): 0 = HW handshaking 1 = SW handshaking
9	1h RO	FIFO_EMPTY: Indicates if there is data left in the channel FIFO.
8	0h RW	Channel Suspend (CH_SUSP): Suspends all DMA transfers from source until this bit is cleared.
7:5	2h RW	Channel Priority (CH_PRIOR): Priority of 7 is the highest priority.
4:0	0h RW	Undefined: RESERVED

24.5.62 Configuration Register for Channel 2 - High (CFG2_HI)—Offset F4h

Refer to the register description for Configuration Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000004h

31				28				24				20				16				12				8				4				0											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0													
Undefined								DEST_PER								SRC_PER								SS_UPD_EN				DS_UPD_EN				PROTCTL				FIFO_MODE				FCMODE			





Access Method

Offset: [BAR] + 104h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.67 Source Address Register for Channel 3 - Low (SAR3_LO)—Offset 108h

Access Method

Offset: [BAR] + 108h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Source Address of DMA Transfer (SAR): Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.

24.5.68 Source Address Register for Channel 3 - High (SAR3_HI)—Offset 10Ch



Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.71 Linked List Pointer Register for Channel 3 - Low (LLP3_LO)—Offset 118h

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
LOC								LMS

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.



Bit Range	Default & Access	Field Name (ID): Description
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ): Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Refer to the description for CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.5.74 Control Register for Channel 3 - High (CTL3_HI)—Offset 124h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 124h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000002h



--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Intel Atom® Processor E3800 Product Family
Datasheet
3679



Access Method

Offset: [BAR] + 130h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

24.5.78 Dest Status Register for Channel 3 - High (DSTAT3_HI)—Offset 134h

Access Method

Offset: [BAR] + 134h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.5.79 Source Status Address Register for Channel 3 - Low (SSTATAR3_LO)—Offset 138h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 138h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

312824201612840 0 0 0 00 0 0 0 00 0 0 0 00 0 0 0 00 0 0 0 00 0 0 0 00 0 0 0 00 0 0 0 0 SSTATAR																															
Bit Range	Default & Access	Field Name (ID): Description																													
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.																													

24.5.80 Source Status Address Register for Channel 3 - High (SSTATAR3_HI)—Offset 13Ch

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 13Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.5.81 Dest Status Address Register for Channel 3 - Low (DSTATAR3_LO)—Offset 140h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 140h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SSTATAR								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTATAR (SSTATAR): Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.5.82 Dest Status Address Register for Channel 3 - High (DSTATAR3_HI)—Offset 144h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 144h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 148h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000E60h

31				28				24				20				16				12				8				4				0																									
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				1 1 1 0				0 1 1 0				0 0 0 0																													
RELOAD_DST	RELOAD_SRC	MAX_ABRST								SRC_HS_POL				DST_HS_POL				LOCK_B				LOCK_CH				LOCK_B_L				LOCK_CH_L				HS_SEL_SRC				HS_SEL_DST				FIFO_EMPTY				CH_SUSP				CH_PRIOR				Undefined			

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	Automatic Destination Reload (RELOAD_DST): The DARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
30	0h RW	Automatic Source Reload (RELOAD_SRC): The SARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
29:20	0h RW	Maximum AMBA Burst Length (MAX_ABRST): Maximum AMBA burst length that is used for DMA transfers on this channel. A value of 0 indicates that software is not limiting the maximum AMBA burst length for DMA transfers on this channel.
19	0h RW	Source Handshaking Interface Polarity (SRC_HS_POL): 0 = Active high 1 = Active low
18	0h RW	Destination Handshaking Interface Polarity (DST_HS_POL): 0 = Active high 1 = Active low
17	0h RW	Bus Lock Bit (LOCK_B): When active, the AHB bus master signal hlock is asserted for the duration specified in CFGx.LOCK_B_L.





Bit Range	Default & Access	Field Name (ID): Description
31:15	0h RW	Undefined: Reserved.
14:11	0h RW	DEST_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the destination of channel x if the CFGx.HS_SEL_DST field is 0; otherwise, this field is ignored.
10:7	0h RW	SRC_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the source of channel x if the CFGx.HS_SEL_SRC field is 0; otherwise, this field is ignored.
6	0h RW	Source Status Update Enable (SS_UPD_EN): Source status information is fetched only from the location pointed to by the SSTATARx register, stored in the SSTATx register and written out to the SSTATx location of the LLI (refer to Figure 52 on page 243) if SS_UPD_EN is high.
5	0h RW	Destination Status Update Enable (DS_UPD_EN): Destination status information is fetched only from the location pointed to by the DSTATARx register, stored in the DSTATx register and written out to the DSTATx location of the LLI if DS_UPD_EN is high.
4:2	1h RW	PROCTL: Protection Control bits used to drive the AHB HPROT[3:1] bus.
1	0h RW	FIFO Mode Select (FIFO_MODE): Determines how much space or data needs to be available in the FIFO before a burst transaction request is serviced. 0 = Space/data available for single AHB transfer of the specified transfer width. 1 = Data available is greater than or equal to half the FIFO depth for destination transfers and space available is greater than half the fifo depth for source transfers.
0	0h RW	Flow Control Mode (FCMODE): Determines when source transaction requests are serviced, when the Destination Peripheral is the flow controller. 0 = Source transaction requests are serviced when they occur. Data pre-fetching is enabled. 1 = Source transaction requests are not serviced until a destination transaction request occurs.

24.5.85 Source Gather Register for Channel 3 - Low (SGR3_LO)—Offset 150h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 150h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

	31		28		24		20		16		12		8		4		0
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	SGC							SGI									

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Refer to the description for SGR0_LO.SGI.



Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.87 Destination Scatter Register for Channel 3 - Low (DSR3_LO)—Offset 158h

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Dest Scatter Count (DSC): Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	Dest Scatter Interval (DSI): Refer to the description for DSR0_LO.DSI.



24.5.88 Dest Scatter Register for Channel 3 - High (DSR3_HI)—Offset 15Ch

Refer to the register description for Destination Scatter Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 15Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.89 Source Address Register for Channel 4 - Low (SAR4_LO)—Offset 160h

Refer to the description for register Source Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 160h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SAR								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SAR: Current Source Address of DMA transfer. Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.



Access Method

Offset: [BAR] + 164h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.5.91 Destination Address Register for Channel 4 - Low (DAR4_LO)—Offset 168h

Access Method

Offset: [BAR] + 168h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Destination Address of DMA Transfer (DAR): Updated after each destination transfer. The DINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every destination transfer throughout the block transfer.



24.5.92 Destination Address Register for Channel 4 - High (DAR4_HI)—Offset 16Ch

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 16Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.93 Linked List Pointer Register for Channel 4 - Low (LLP4_LO)—Offset 170h

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 170h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
LOC								LMS

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.



24.5.94 Linked List Pointer Register for Channel 4 - High (LLP4_HI)—Offset 174h

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 174h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.5.95 Control Register for Channel 4 - Low (CTL4_LO)—Offset 178h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 178h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00304801h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RW	Undefined_: RESERVED
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPx.LOC is non-zero
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPx.LOC is non-zero.



Bit Range	Default & Access	Field Name (ID): Description
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ): Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Refer to the description for CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.5.96 Control Register for Channel 4 - High (CTL4_HI)—Offset 17Ch

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 17Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000002h



Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

31	28	24	20	16	12	8	4	0																											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
SSTAT																																			

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTAT : Source status information retrieved by hw from the addrx pointed to by SSTATAR0 register.

24.5.98 Source Status Register for Channel 4 - High (SSTAT4_HI)—Offset 184h

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

October 2018
Document Number: 538136, Rev. 4.3



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.5.101 Source Status Address Register for Channel 4 - Low (SSTATAR4_LO)—Offset 190h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 190h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SSTATAR								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.						

24.5.102 Source Status Address Register for Channel 4 - High (SSTATAR4_HI)—Offset 194h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 194h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.5.103 Dest Status Address Register for Channel 4 - Low (DSTATAR4_LO)—Offset 198h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 198h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

3128242016128400																															
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

24.5.104 Dest Status Address Register for Channel 4 - High (DSTATAR4_HI)—Offset 19Ch

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 19Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.5.105 Configuration Register for Channel 4 - Low (CFG4_LO)—Offset 1A0h

Refer to the register description for Configuration Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000E80h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RELOAD_DST	RELOAD_SRC	MAX_ABRST	SRC_HS_POL	DST_HS_POL	LOCK_B	LOCK_CH	LOCK_B_L	LOCK_CH_L
					</			



Bit Range	Default & Access	Field Name (ID): Description
16	0h RW	Channel Lock Bit (LOCK_CH): When the channel is granted control of the master bus interface and if the CFGx.LOCK_CH bit is asserted, then no other channels are granted control of the master bus interface for the duration specified in CFGx.LOCK_CH_L. Indicates to the master bus interface arbiter that this channel wants exclusive access to the master bus interface for the duration specified in CFGx.LOCK_CH_L.
15:14	0h RW	Bus Lock Level (LOCK_B_L): Indicates the duration over which CFGx.LOCK_B bit applies. 00 = Over complete DMA transfer 01 = Over complete DMA block transfer 1x = Over complete DMA transaction
13:12	0h RW	Channel Lock Level (LOCK_CH_L): Indicates the duration over which CFGx.LOCK_CH bit applies. 00 = DMA transfer 01 = DMA block transfer 1x = DMA transaction
11	1h RW	Source Software or Hardware Handshaking Select (HS_SEL_SRC): 0 = HW handshaking 1 = SW handshaking
10	1h RW	Destination Software or Hardware Handshaking Select (HS_SEL_DST): 0 = HW handshaking 1 = SW handshaking
9	1h RO	FIFO_EMPTY: Indicates if there is data left in the channel FIFO.
8	0h RW	Channel Suspend (CH_SUSP): Suspends all DMA transfers from source until this bit is cleared.
7:5	4h RW	Channel Priority (CH_PRIOR): Priority of 7 is the highest priority.
4:0	0h RW	Undefined: RESERVED

24.5.106 Configuration Register for Channel 4 - High (CFG4_HI)—Offset 1A4h

Refer to the register description for Configuration Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1A4h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000004h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0						
Undefined								DEST_PER								SRC_PER				SS_UPD_EN		DS_UPD_EN		PROTCTL		FIFO_MODE		FCMODE							





Access Method

Offset: [BAR] + 1B4h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.111 Source Address Register for Channel 5 - Low (SAR5_LO)—Offset 1B8h

Access Method

Offset: [BAR] + 1B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SAR: Current Source Address of DMA transfer. Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.



Access Method

Offset: [BAR] + 1C4h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.115 Linked List Pointer Register for Channel 5 - Low (LLP5_LO)—Offset 1C8h

Access Method

Offset: [BAR] + 1C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.



Bit Range	Default & Access	Field Name (ID): Description
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ): Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Refer to the description for CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mx_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.5.118 Control Register for Channel 5 - High (CTL5_HI)—Offset 1D4h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1D4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000002h

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
3705



Access Method

Offset: [BAR] + 1E0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSTAT								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest status information retrieved by hw from the addrx pointed to by DSTATAR0 register

24.5.122 Dest Status Register for Channel 5 - High (DSTAT5_HI)—Offset 1E4h

Access Method

Offset: [BAR] + 1E4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.5.123 Source Status Address Register for Channel 5 - Low (SSTATAR5_LO)—Offset 1E8h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

312824201612840																															
00000000000000000000000000000000																															
SSTATAR																															
Bit Range		Default & Access		Field Name (ID): Description																											
31:0		0h RW		SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.																											

24.5.124 Source Status Address Register for Channel 5 - High (SSTATAR5_HI)—Offset 1ECh

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1ECh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 1F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

312824201612840																															
00																															

24.5.126 Dest Status Address Register for Channel 5 - High (DSTATAR5_HI)—Offset 1F4h

Access Method

Offset: [BAR] + 1F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 1F8h

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000EA0h

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	Automatic Destination Reload (RELOAD_DST): The DARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
30	0h RW	Automatic Source Reload (RELOAD_SRC): The SARx register can be automatically reloaded from its initial value at the end of every block for multi-block transfers.
29:20	0h RW	Maximum AMBA Burst Length (MAX_ABRST): Maximum AMBA burst length that is used for DMA transfers on this channel. A value of 0 indicates that software is not limiting the maximum AMBA burst length for DMA transfers on this channel.
19	0h RW	Source Handshaking Interface Polarity (SRC_HS_POL): 0 = Active high 1 = Active low
18	0h RW	Destination Handshaking Interface Polarity (DST_HS_POL): 0 = Active high 1 = Active low
17	0h RW	Bus Lock Bit (LOCK_B): When active, the AHB bus master signal hlock is asserted for the duration specified in CFGx.LOCK_B_L.



Bit Range	Default & Access	Field Name (ID): Description
16	0h RW	Channel Lock Bit (LOCK_CH): When the channel is granted control of the master bus interface, and if the CFGx.LOCK_CH bit is asserted, then no other channels are granted control of the master bus interface for the duration specified in CFGx.LOCK_CH_L. Indicates to the master bus interface arbiter that this channel wants exclusive access to the master bus interface for the duration specified in CFGx.LOCK_CH_L.
15:14	0h RW	Bus Lock Level (LOCK_B_L): Indicates the duration over which CFGx.LOCK_B bit applies. 00 = Over complete DMA transfer 01 = Over complete DMA block transfer 1x = Over complete DMA transaction
13:12	0h RW	Channel Lock Level (LOCK_CH_L): Indicates the duration over which CFGx.LOCK_CH bit applies. 00 = DMA transfer 01 = DMA block transfer 1x = DMA transaction
11	1h RW	Source Software or Hardware Handshaking Select (HS_SEL_SRC): 0 = HW handshaking 1 = SW handshaking
10	1h RW	Destination Software or Hardware Handshaking Select (HS_SEL_DST): 0 = HW handshaking 1 = SW handshaking
9	1h RO	FIFO_EMPTY: Indicates if there is data left in the channel FIFO.
8	0h RW	Channel Suspend (CH_SUSP): Suspends all DMA transfers from source until this bit is cleared.
7:5	5h RW	Channel Priority (CH_PRIOR): Priority of 7 is the highest priority.
4:0	0h RW	Undefined: RESERVED

24.5.128 Configuration Register for Channel 5 - High (CFG5_HI)—Offset 1FCh

Refer to the register description for Configuration Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000004h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined				DEST_PER	SRC_PER	SS_UPD_EN	DS_UPD_EN	PROTCTL
								FIFO_MODE
								FCMODE



BAR Reference: [B:0, D:24, F:0] + 10h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.5.135 Destination Address Register for Channel 6 - Low (DAR6_LO)—Offset 218h

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h


Diagram illustrating the structure of the 32-bit DAR field. The field is divided into eight 4-bit segments, each containing four '0' bits. The segments are labeled with bit positions 31, 28, 24, 20, 16, 12, 8, and 4 from left to right. The label 'DAR' is positioned below the first four segments (bits 31 to 16).

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Destination Address of DMA Transfer (DAR): Updated after each destination transfer. The DINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every destination transfer throughout the block transfer.

24.5.136 Destination Address Register for Channel 6 - High (DAR6_HI)—Offset 21Ch

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h



Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 220h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.

Refer to the description for register Linked List Pointer Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 224h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						

24.5.139 Control Register for Channel 6 - Low (CTL6_LO)—Offset 228h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 228h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00304801h

31	28				24				20				16				12				8				4				0																																		
0	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	1	0	0	1	0	0	0	0	0	0	0	0	0	0	1																														
Undefined_				LLP_SRC_EN				LLP_DST_EN				SMS				DMS				TT_FC				Undefined				DST_SCATTER_EN				SRC_GATHER_EN				SRC_MSIZE				DEST_MSIZE				SINC				DINC				SRC_TR_WIDTH				DST_TR_WIDTH				INT_EN			

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RW	Undefined_: RESERVED
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPx.LOC is non-zero
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPx.LOC is non-zero.
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED



Bit Range	Default & Access	Field Name (ID): Description
18	0h RW	Destination Scatter Enable Bit (DST_SCATTER_EN): 0 = disabled 1 = enabled
17	0h RW	Source Gather Enable Bit (SRC_GATHER_EN): 0 = disabled 1 = enabled
16:14	1h RW	Source Burst Transaction Length (SRC_MSIZ): Refer to the description of CTL0_LO.SRC_MSIZ.
13:11	1h RW	Destination Burst Transaction Length (DEST_MSIZ): Refer to the description of CTL0_LO.DEST_MSIZ.
10:9	0h RW	Source Address Increment (SINC): 00 = Increment 01 = Decrement 1x = No change
8:7	0h RW	Destination Address Increment (DINC): Indicates whether to increment or decrement the destination address on every destination transfer. 00 = Increment 01 = Decrement 1x = No change
6:4	0h RW	Source Transfer Width (SRC_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where x is the AHB layer 1 to 4 where the source resides.
3:1	0h RW	Destination Transfer Width (DST_TR_WIDTH): This value must be less than or equal to DMAH_Mk_HDATA_WIDTH, where k is the AHB layer 1 to 4 where the destination resides.
0	1h RW	Interrupt Enable Bit (INT_EN): If set, then all interrupt-generating sources are enabled.

24.5.140 Control Register for Channel 6 - High (CTL6_HI)—Offset 22Ch

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 22Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000002h

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:13	0h RW	Undefined_: RESERVED



Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED

24.5.143 Dest Status Register for Channel 6 - Low (DSTAT6_LO)—Offset 238h

Refer to the register description for Dest Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 238h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Diagram of the 32-bit DSTAT register. The register is divided into eight 4-bit fields. The top row shows bit positions 31, 28, 24, 20, 16, 12, 8, and 4. The bottom row shows bit positions 0, 4, 8, 12, 16, 20, 24, and 28. The label 'DSTAT' is centered below the register.

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest status information retrieved by hw from the addrx pointed to by DSTATAR0 register

24.5.144 Dest Status Register for Channel 6 - High (DSTAT6_HI)—Offset 23Ch

Refer to the register description for Dest Status Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 23Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



24.5.145 Source Status Address Register for Channel 6 - Low (SSTATAR6_LO)—Offset 240h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 240h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTATAR

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.5.146 Source Status Address Register for Channel 6 - High (SSTATAR6_HI)—Offset 244h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 244h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



Bit Range	Default & Access	Field Name (ID): Description
5	0h RW	Destination Status Update Enable (DS_UPD_EN): Destination status information is fetched only from the location pointed to by the DSTATARx register, stored in the DSTATx register and written out to the DSTATx location of the LLI if DS_UPD_EN is high.
4:2	1h RW	PROTCTL: Protection Control bits used to drive the AHB HPROT[3:1] bus.
1	0h RW	FIFO Mode Select (FIFO_MODE): Determines how much space or data needs to be available in the FIFO before a burst transaction request is serviced. 0 = Space/data available for single AHB transfer of the specified transfer width. 1 = Data available is greater than or equal to half the FIFO depth for destination transfers and space available is greater than half the fifo depth for source transfers.
0	0h RW	Flow Control Mode (FCMODE): Determines when source transaction requests are serviced when the Destination Peripheral is the flow controller. 0 = Source transaction requests are serviced when they occur. Data pre-fetching is enabled. 1 = Source transaction requests are not serviced until a destination transaction request occurs.

24.5.151 Source Gather Register for Channel 6 - Low (SGR6_LO)—Offset 258h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 258h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC	SGI							

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Refer to the description for SGR0_LO.SGI.

24.5.152 Source Gather Register for Channel 6 - High (SGR6_HI)—Offset 25Ch

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 25Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h



Access Method

Offset: [BAR] + 268h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31 28 24 20 16 12 8 4 0															
0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0															
SAR															
Bit Range	Default & Access	Field Name (ID): Description													
31:0	0h RW	Current Source Address of DMA Transfer (SAR): Updated after each source transfer. The SINC field in the CTLx register determines whether the address increments, decrements, or is left unchanged on every source transfer throughout the block transfer.													

24.5.156 Source Address Register for Channel 7 - High (SAR7_HI)—Offset 26Ch

Access Method

Offset: [BAR] + 26Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

24.5.157 Destination Address Register for Channel 7 - Low (DAR7_LO)– Offset 270h

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 270h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
DAR								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Current Destination Address of DMA Transfer (DAR): Updated after each destination transfer. The DINC field in the CTLX register determines whether the address increments, decrements, or is left unchanged on every destination transfer throughout the block transfer.

24.5.158 Destination Address Register for Channel 7 - High (DAR7_HI)—Offset 274h

Refer to the description for register Destination Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 274h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + 278h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
LMS								LMS

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	LOC: Starting Address In Memory of next LLI if block chaining is enabled.
1:0	0h RW	List Master Select (LMS): Identifies the AHB layer/interface where the memory device that stores the next linked list item resides.

24.5.160 Linked List Pointer Register for Channel 7 - High (LLP7_HI)—Offset 27Ch

Access Method

Offset: [BAR] + 27Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



312824201612840																															
00000000000000000000000000000000																															
Undefined																															
Bit Range		Default & Access		Field Name (ID): Description																											
31:0		0h RW		Undefined: RESERVED																											

24.5.161 Control Register for Channel 7 - Low (CTL7_LO)—Offset 280h

Refer to the register description for Control Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 280h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00304801h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 1 1	0 0 0 0	0 1 0 0	1 0 0 0	0 0 0 0	0 0 0 0
Undefined_	LLP_SRC_EN	LLP_DST_EN	SMS	DMS	TT_FC	Undefined	DST_SCATTER_EN	SRC_GATHER_EN
						SRC_MSIZ	DEST_MSIZ	SINC
							DINC	
							SRC_TR_WIDTH	
							DST_TR_WIDTH	
								INT_EN

Bit Range	Default & Access	Field Name (ID): Description
31:29	0h RW	Undefined_: RESERVED
28	0h RW	LLP_SRC_EN: Block chaining is enabled on the source side only if the LLP_SRC_EN field is high and LLPx.LOC is non-zero
27	0h RW	LLP_DST_EN: Block chaining is enabled on the destination side only if the LLP_DST_EN field is high and LLPx.LOC is non-zero.
26:25	0h RW	Source Master Select (SMS): Identifies the Master Interface layer from which the source device (peripheral or memory) is accessed.
24:23	0h RW	Destination Master Select (DMS): Identifies the Master Interface layer where the destination device (peripheral or memory) resides.
22:20	3h RW	Transfer Type and Flow Control (TT_FC): Refer to description for CTL0_LO.TT_FC.
19	0h RW	Undefined: RESERVED





Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
DSTAT								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTAT: Dest status information retrieved by hw from the addrx pointed to by DSTATAR0 register

24.5.166 Dest Status Register for Channel 7 - High (DSTAT7_HI)—Offset 294h

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

Diagram of a 32-bit register structure. The register is divided into four 8-bit segments. The first segment (bits 0-7) is labeled 'Undefined'. The second segment (bits 8-15) is labeled 'Reserved'. The third segment (bits 16-23) is labeled 'Reserved'. The fourth segment (bits 24-31) is labeled 'Reserved'.

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



24.5.167 Source Status Address Register for Channel 7 - Low (SSTATAR7_LO)—Offset 298h

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 298h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SSTATAR								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	SSTATAR: Pointer from where the hw can fetch the source status information registered in SSTAT0.						

24.5.168 Source Status Address Register for Channel 7 - High (SSTATAR7_HI)—Offset 29Ch

Refer to the description for register Source Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 29Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								
Bit Range	Default & Access	Field Name (ID): Description						
31:0	0h RW	Undefined: RESERVED						



24.5.169 Dest Status Address Register for Channel 7 - Low (DSTATAR7_LO)—Offset 2A0h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

SSTATAR

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	DSTATAR (SSTATAR): Pointer from where the hw can fetch the source status information registered in SSTAT0.

24.5.170 Dest Status Address Register for Channel 7 - High (DSTATAR7_HI)—Offset 2A4h

Refer to the description for register Dest Status Address Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2A4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Undefined

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: RESERVED



Access Method

Offset: [BAR] + 2ACh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000004h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				DEST_PER		SRC_PER		SS_UPD_EN
								DS_UPD_EN
						PROTCTL		FIFO_MODE
								ECMODE

Bit Range	Default & Access	Field Name (ID): Description
31:15	0h RW	Undefined: Reserved.
14:11	0h RW	DEST_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the destination of channel x if the CFGx.HS_SEL_DST field is 0; otherwise, this field is ignored.
10:7	0h RW	SRC_PER: Assigns a hardware handshaking interface (0 - DMAH_NUM_HS_INT-1) to the source of channel x if the CFGx.HS_SEL_SRC field is 0; otherwise, this field is ignored.
6	0h RW	Source Status Update Enable (SS_UPD_EN): Source status information is fetched only from the location pointed to by the SSTATARx register, stored in the SSTATx register and written out to the SSTATx location of the LLI (refer to Figure 52 on page 243) if SS_UPD_EN is high.



Bit Range	Default & Access	Field Name (ID): Description
5	0h RW	Destination Status Update Enable (DS_UPD_EN): Destination status information is fetched only from the location pointed to by the DSTATARx register, stored in the DSTATx register and written out to the DSTATx location of the LLI if DS_UPD_EN is high.
4:2	1h RW	PROTCTL: Protection Control bits used to drive the AHB HPROT[3:1] bus.
1	0h RW	FIFO Mode Select (FIFO_MODE): Determines how much space or data needs to be available in the FIFO before a burst transaction request is serviced. 0 = Space/data available for single AHB transfer of the specified transfer width. 1 = Data available is greater than or equal to half the FIFO depth for destination transfers and space available is greater than half the fifo depth for source transfers.
0	0h RW	Flow Control Mode (FCMODE): Determines when source transaction requests are serviced when the Destination Peripheral is the flow controller. 0 = Source transaction requests are serviced when they occur. Data pre-fetching is enabled. 1 = Source transaction requests are not serviced until a destination transaction request occurs.

24.5.173 Source Gather Register for Channel 7 - Low (SGR7_LO)—Offset 2B0h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2B0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
SGC				SGI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Source Gather Count (SGC): Source contiguous transfer count between successive gather boundaries.
19:0	0h RW	Source Gather Interval (SGI): Refer to the description for SGR0_LO.SGI.

24.5.174 Source Gather Register for Channel 7 - High (SGR7_HI)—Offset 2B4h

Refer to the register description for Source Gather Register for Channel 0 - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2B4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.175 Destination Scatter Register for Channel 7 - Low (DSR7_LO)—Offset 2B8h

Refer to the register description for Destination Scatter Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2B8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DSC				DSI				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0h RW	Dest Scatter Count (DSC): Destination contiguous transfer count between successive scatter boundaries.
19:0	0h RW	Dest Scatter Interval (DSI): Refer to the description for DSR0_LO.DSI.

24.5.176 Dest Scatter Register for Channel 7 - High (DSR7_HI)—Offset 2BCh

Refer to the register description for Destination Scatter Register for Channel 0 - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2BCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.177 Interrupt Raw Status Registers - Low (RawTfr_LO)—Offset 2C0h

Interrupt events are stored in these Raw Interrupt Status registers before masking: RawBlock, RawDstTran, RawErr, RawSrcTran, and RawTfr. Each Raw Interrupt Status register has a bit allocated per channel; for example, RawTfr[2] is the Channel 2 raw transfer complete interrupt. Each bit in these registers is cleared by writing a 1 to the corresponding location in the ClearTfr, ClearBlock, ClearSrcTran, ClearDstTran, ClearErr registers.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2C0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
Undefined																				RAW															

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RW	Raw Interrupt Status (RAW): Reserved.



Access Method

Offset: [BAR] + 2C4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.179 Interrupt Raw Status Registers - Low (RawBlock_LO)—Offset 2C8h

Access Method

Offset: [BAR] + 2C8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RW	Raw Interrupt Status (RAW): Reserved.



Access Method

Offset: [BAR] + 2D4h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.183 Interrupt Raw Status Registers - Low (RawDstTran_LO)—Offset 2D8h

Access Method

Offset: [BAR] + 2D8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RW	Raw Interrupt Status (RAW): Reserved.



Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.185 Interrupt Raw Status Registers - Low (RawErr_LO)—Offset 2E0h

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined							RAW	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RW	Raw Interrupt Status (RAW): Reserved.



Access Method

Offset: [BAR] + 2E4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.187 Interrupt Status Registers - Low (StatusTfr_LO)—Offset 2E8h

Access Method

Offset: [BAR] + 2E8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RO	Interrupt Status (STATUS): Reserved.



24.5.188 Interrupt Status Registers - High (StatusTfr_HI)—Offset 2ECh

All interrupt events from all channels are stored in these Interrupt Status registers after masking: StatusBlock, StatusDstTran, StatusErr, StatusSrcTran, and StatusTfr. Each Interrupt Status register has a bit allocated per channel; for example, StatusTfr[2] is the Channel 2 status transfer complete interrupt. The contents of these registers are used to generate the interrupt signals (int or int_n bus, depending on interrupt polarity) leaving the DW_ahb_dmac.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2ECh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.189 Interrupt Status Registers - Low (StatusBlock_LO)—Offset 2F0h

Refer to the description for register StatusTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined							STATUS	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RO	Interrupt Status (STATUS): Reserved.



24.5.190 Interrupt Status Registers - High (StatusBlock_HI)—Offset 2F4h

Refer to the description for register StatusTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.191 Interrupt Status Registers - Low (StatusSrcTran_LO)—Offset 2F8h

Refer to the description for register StatusTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 2F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined							STATUS	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RO	Interrupt Status (STATUS): Reserved.



Access Method

Offset: [BAR] + 304h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.195 Interrupt Status Registers - Low (StatusErr_LO)—Offset 308h

Access Method

Offset: [BAR] + 308h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h RO	Interrupt Status (STATUS): Reserved.



Access Method

Offset: [BAR] + 314h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.199 Interrupt Mask Registers - Low (MaskBlock_LO)—Offset 318h

The contents of the Raw Status registers are masked with the contents of the Mask registers: MaskBlock, MaskDstTran, MaskErr, MaskSrcTran, and MaskTfr. Each Interrupt Mask register has a bit allocated per channel; for example, MaskTfr[2] is the mask bit for the Channel 2 transfer complete interrupt.

Access Method

Offset: [BAR] + 318h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Interrupt Mask Write Enable (INT_MASK_WE): 0 = write disabled 1 = write enabled



Bit Range	Default & Access	Field Name (ID): Description
7:0	0h RW	INT_MASK: Interrupt Mask 0 = masked 1 = unmasked

24.5.200 Interrupt Mask Registers - High (MaskBlock_HI)—Offset 31Ch

Refer to the description for register MaskBlock_LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 31Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.201 Interrupt Mask Registers - Low (MaskSrcTran_LO)—Offset 320h

Refer to the description for register MaskBlock_LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 320h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				INT_MASK_WE				INT_MASK

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.



Access Method

Offset: [BAR] + 324h

BAR Reference: [B:0, D:24, F:0] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.203 Interrupt Mask Registers - Low (MaskDstTran_LO)—Offset 328h

Access Method

Offset: [BAR] + 328h

BAR Reference: [B:0, D:24, F:0] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				INT_MASK_WE				INT_MASK



Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Interrupt Mask Write Enable (INT_MASK_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Interrupt Mask (INT_MASK): 0 = masked 1 = unmasked

24.5.204 Interrupt Mask Registers - High (MaskDstTran_HI)—Offset 32Ch

Refer to the description for register MaskBlock LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 32Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.205 Interrupt Mask Registers - Low (MaskErr_LO)—Offset 330h

Refer to the description for register MaskBlock_LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 330h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				INT_MASK_WE				INT_MASK

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Interrupt Mask Write Enable (INT_MASK_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Interrupt Mask (INT_MASK): 0 = masked 1 = unmasked

24.5.206 Interrupt Mask Registers - High (MaskErr_HI)—Offset 334h

Refer to the description for register MaskBlock_LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 334h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.207 Interrupt Clear Registers - Low (ClearTfr_LO)—Offset 338h

Each bit in the Raw Status and Status registers is cleared on the same cycle by writing a 1 to the corresponding location in the Clear registers: ClearBlock, ClearDstTran, ClearErr, ClearSrcTran, and ClearTfr. Each Interrupt Clear register has a bit allocated per channel; for example, ClearTfr[2] is the clear bit for the Channel 2 transfer complete interrupt. Writing a 0 has no effect. These registers are not readable.

Access Method



24.5.209 Interrupt Clear Registers - Low (ClearBlock_LO)—Offset 340h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 340h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined							CLEAR	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h WO	Clear Interrupt Status (CLEAR): Interrupt clear. 0 = no effect 1 = clear interrupt

24.5.210 Interrupt Clear Registers (ClearBlock_HI)—Offset 344h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 344h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



24.5.211 Interrupt Clear Registers - Low (ClearSrcTran_LO)—Offset 348h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 348h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined							CLEAR	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h WO	Clear Interrupt Status (CLEAR): Interrupt clear. 0 = no effect 1 = clear interrupt

24.5.212 Interrupt Clear RegistersClearSrc - High (ClearSrcTran_HI)—Offset 34Ch

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



24.5.213 Interrupt Clear Registers - Low (ClearDstTran_LO)—Offset 350h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 350h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined							CLEAR	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0h RW	Undefined: Reserved.
7:0	0h WO	Clear Interrupt Status (CLEAR): Interrupt clear. 0 = no effect 1 = clear interrupt

24.5.214 Interrupt Clear Registers - High (ClearDstTran_HI)—Offset 354h

Refer to the description for register ClearTfr_HI.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 354h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



24.5.217 Combined Interrupt Status Register - Low (StatusInt_LO)— Offset 360h

The contents of each of the five Status registers StatusTfr, StatusBlock, StatusSrcTran, StatusDstTran, StatusErr is ORed to produce a single bit for each interrupt type in the Combined Status register (StatusInt). This register is read-only.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 360h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined							ERR	DSTT
							SRCT	BLOCK
							TFR	

Bit Range	Default & Access	Field Name (ID): Description
31:5	0h RW	Undefined: Reserved.
4	0h RO	ERR: OR of the contents of StatusErr register.
3	0h RO	DSTT: OR of the contents of StatusDst register.
2	0h RO	SRCT: OR of the contents of StatusSrcTran register.
1	0h RO	BLOCK: OR of the contents of StatusBlock register.
0	0h RO	TFR: OR of the contents of StatusTfr register.

24.5.218 Combined Interrupt Status Register - High (StatusInt_HI)— Offset 364h

Refer to the description for register StatusInt_LO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 364h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
15:8	0h WO	Destination Request Write Enable (DST_REQ_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Destination Request (DST_REQ): A bit is assigned for each channel in this register. ReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

24.5.222 Destination Software Transaction Request Register - High (RegDstReg HI)—Offset 374h

A bit is assigned for each channel in this register. ReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 374h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Diagram illustrating the bit positions (0 to 31) of a 32-bit register. The register is divided into four 8-bit segments, each labeled with its bit range and the value 0x00000000. The entire register is labeled 'Undefined'.

Bit Range	Value
31 to 24	0x00000000
23 to 16	0x00000000
15 to 8	0x00000000
7 to 0	0x00000000

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.223 Single Source Software Transaction Request Register - Low (SglRqSrcReg_LO)—Offset 378h

A bit is assigned for each channel in this register. SglReqSrcReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 378h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined				SRC_SGLREQ_WE				SRC_SGLREQ

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Source Req Write Enable (SRC_SGLREQ_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Source Single Request (SRC_SGLREQ): A channel SRC_SGLREQ bit is written only if the corresponding channel write enable bit in the SRC_SGLREQ_WE field is asserted on the same AHB write transfer, and if the channel is enabled in the ChEnReg register.

24.5.224 Single Source Software Transaction Request Register - High (SglRqSrcReg_HI)—Offset 37Ch

A bit is assigned for each channel in this register. SglReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 37Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Undefined								

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.



24.5.225 Single Destination Software Transaction Request Register - Low (SglRqDstReg_LO)—Offset 380h

A bit is assigned for each channel in this register. SglReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 380h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined				DST_SGLREQ_WE				DST_SGLREQ

Bit Range	Default & Access	Field Name (ID): Description
31:16	0h RW	Undefined: Reserved.
15:8	0h WO	Destination Request Write Enable (DST_SGLREQ_WE): 0 = write disabled 1 = write enabled
7:0	0h RW	Destination Single or Burst Request (DST_SGLREQ): A channel DST_SGLREQ bit is written only if the corresponding channel write enable bit in the DST_SGLREQ_WE field is asserted on the same AHB write transfer, and if the channel is enabled in the ChEnReg register.

24.5.226 Single Destination Software Transaction Request Register - High (SglRqDstReg_HI)—Offset 384h

A bit is assigned for each channel in this register. SglReqDstReg[n] is ignored when software handshaking is not enabled for the source of channel n.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 384h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Undefined								

24.5.227 Last Source Transaction Request Register - Low (LstSrcReg_LO)—Offset 388h



Refer to the description for DW_ahb_dmac Channel Enable Register - Low.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.235 DW_ahb_dmac ID Register - Low (DmaIdReg_LO)—Offset 3A8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: C0CAC01Ah

31	28	24	20	16	12	8	4	0
1	1	0	0	0	0	0	1	0
DMA_ID								



Bit Range	Default & Access	Field Name (ID): Description
31:0	c0cac01ah RO	Hardcoded DW_ahb_dmac Peripheral ID (DMA_ID): coreConsultantconfigured hardcoded ID number DMAH_ID_NUM.

24.5.236 DW_ahb_dmac ID Register - High (DmaIdReg_HI)—Offset 3ACh

Refer to the description of DW_ahb_dmac ID Register - Low.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3ACh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Diagram illustrating the bit positions (0 to 31) of a 32-bit register. The register is divided into four 8-bit segments, each labeled '0' at the top. A vertical line is drawn after the 16th bit, and the word 'Undefined' is written vertically next to it, indicating that bits 17 through 31 are undefined.

Bit Range	Default & Access	Field Name (ID): Description
31:0	0h RW	Undefined: Reserved.

24.5.237 DW_ahb_dmac Test Register - Low (DmaTestReg_LO)—Offset 3B0h

This register is used to put the AHB slave interface into test mode, during which the readback value of the writable registers match the value written, assuming the DW_ahb_dmac configuration has not optimized the same registers. In normal operation, the readback value of some registers is a function of the DW_ahb_dmac state, and does not match the value written.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3B0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

[illegible]



Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

24.5.239 DW_ahb_dmac Component Parameters Register 6 - Low (DMA_COMP_PARAMS_6_LO)—Offset 3C8h

Access Method

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h

Diagram illustrating the bit positions (31 down to 0) and the state of the register. The register contains 16 zeros. A vertical line is drawn at bit position 16, labeled "Undefined".




Bit Range	Default & Access	Field Name (ID): Description
21:19	4h RO	CH7_DMS: The value of this register is derived from the DMAH_CH7_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH7_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH7_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH7_FC: The value of this register is derived from the DMAH_CH7_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH7_HC_LLP: The value of this register is derived from the DMAH_CH7_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH7_CTL_WB_EN: The value of this register is derived from the DMAH_CH7_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
11	0h RO	CH7_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH7_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH7_LOCK_EN: The value of this register is derived from the DMAH_CH7_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH7_SRC_GAT_EN: The value of this register is derived from the DMAH_CH7_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH7_DST_SCA_EN: The value of this register is derived from the DMAH_CH7_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH7_STAT_SRC: The value of this register is derived from the DMAH_CH7_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
30:28	3h RO	CH6_FIFO_DEPTH: The value of this register is derived from the DMAH_CH6_FIFO_DEPTH coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 8 1h = 16 2h = 32 3h = 64 4h = 128
27:25	4h RO	CH6_SMS: The value of this register is derived from the DMAH_CH6_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
24:22	0h RO	CH6_LMS: The value of this register is derived from the DMAH_CH6_LMS coreConsultant parameter. For a description of this parameter, refer to page 111. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
21:19	4h RO	CH6_DMS: The value of this register is derived from the DMAH_CH6_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH6_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH6_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH6_FC: The value of this register is derived from the DMAH_CH6_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH6_HC_LLP: The value of this register is derived from the DMAH_CH6_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH6_CTL_WB_EN: The value of this register is derived from the DMAH_CH6_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE




Bit Range	Default & Access	Field Name (ID): Description
11	0h RO	CH6_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH6_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH6_LOCK_EN: The value of this register is derived from the DMAH_CH6_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH6_SRC_GAT_EN: The value of this register is derived from the DMAH_CH6_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH6_DST_SCA_EN: The value of this register is derived from the DMAH_CH6_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH6_STAT_SRC: The value of this register is derived from the DMAH_CH6_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
6	0h RO	CH6_STAT_DST: The value of this register is derived from the DMAH_CH6_STAT_DST coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
5:3	0h RO	CH6_STW: The value of this register is derived from the DMAH_CH6_STW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
2:0	0h RO	CH6_DTW: The value of this register is derived from the DMAH_CH6_DTW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved



Bit Range	Default & Access	Field Name (ID): Description
21:19	4h RO	CH5_DMS: The value of this register is derived from the DMAH_CH5_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH5_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH5_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH5_FC: The value of this register is derived from the DMAH_CH5_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH5_HC_LLP: The value of this register is derived from the DMAH_CH5_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH5_CTL_WB_EN: The value of this register is derived from the DMAH_CH5_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
11	0h RO	CH5_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH5_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH5_LOCK_EN: The value of this register is derived from the DMAH_CH5_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH5_SRC_GAT_EN: The value of this register is derived from the DMAH_CH5_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH5_DST_SCA_EN: The value of this register is derived from the DMAH_CH5_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH5_STAT_SRC: The value of this register is derived from the DMAH_CH5_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE






Bit Range	Default & Access	Field Name (ID): Description
30:28	3h RO	CH4_FIFO_DEPTH: The value of this register is derived from the DMAH_CH4_FIFO_DEPTH coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 8 1h = 16 2h = 32 3h = 64 4h = 128
27:25	4h RO	CH4_SMS: The value of this register is derived from the DMAH_CH4_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
24:22	0h RO	CH4_LMS: The value of this register is derived from the DMAH_CH4_LMS coreConsultant parameter. For a description of this parameter, refer to page 111. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
21:19	4h RO	CH4_DMS: The value of this register is derived from the DMAH_CH4_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH4_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH4_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH4_FC: The value of this register is derived from the DMAH_CH4_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH4_HC_LLP: The value of this register is derived from the DMAH_CH4_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH4_CTL_WB_EN: The value of this register is derived from the DMAH_CH4_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
11	0h RO	CH4_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH4_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH4_LOCK_EN: The value of this register is derived from the DMAH_CH4_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH4_SRC_GAT_EN: The value of this register is derived from the DMAH_CH4_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH4_DST_SCA_EN: The value of this register is derived from the DMAH_CH4_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH4_STAT_SRC: The value of this register is derived from the DMAH_CH4_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
6	0h RO	CH4_STAT_DST: The value of this register is derived from the DMAH_CH4_STAT_DST coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
5:3	0h RO	CH4_STW: The value of this register is derived from the DMAH_CH4_STW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
2:0	0h RO	CH4_DTW: The value of this register is derived from the DMAH_CH4_DTW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved

24.5.244 DW_ahb_dmac Component Parameters Register 4 - High (DMA_COMP_PARAMS_4_HI)—Offset 3DCh




Bit Range	Default & Access	Field Name (ID): Description
21:19	4h RO	CH3_DMS: The value of this register is derived from the DMAH_CH3_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH3_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH3_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH3_FC: The value of this register is derived from the DMAH_CH3_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH3_HC_LLP: The value of this register is derived from the DMAH_CH3_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH3_CTL_WB_EN: The value of this register is derived from the DMAH_CH3_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
11	0h RO	CH3_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH3_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH3_LOCK_EN: The value of this register is derived from the DMAH_CH3_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH3_SRC_GAT_EN: The value of this register is derived from the DMAH_CH3_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH3_DST_SCA_EN: The value of this register is derived from the DMAH_CH3_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH3_STAT_SRC: The value of this register is derived from the DMAH_CH3_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
30:28	3h RO	CH2_FIFO_DEPTH: The value of this register is derived from the DMAH_CH2_FIFO_DEPTH coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 8 1h = 16 2h = 32 3h = 64 4h = 128
27:25	4h RO	CH2_SMS: The value of this register is derived from the DMAH_CH2_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
24:22	0h RO	CH2_LMS: The value of this register is derived from the DMAH_CH2_LMS coreConsultant parameter. For a description of this parameter, refer to page 111. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
21:19	4h RO	CH2_DMS: The value of this register is derived from the DMAH_CH2_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH2_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH2_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH2_FC: The value of this register is derived from the DMAH_CH2_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH2_HC_LLP: The value of this register is derived from the DMAH_CH2_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH2_CTL_WB_EN: The value of this register is derived from the DMAH_CH2_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
11	0h RO	CH2_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH2_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to the spec. 0 = FALSE 1 = TRUE
10	0h RO	CH2_LOCK_EN: The value of this register is derived from the DMAH_CH2_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH2_SRC_GAT_EN: The value of this register is derived from the DMAH_CH2_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH2_DST_SCA_EN: The value of this register is derived from the DMAH_CH2_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH2_STAT_SRC: The value of this register is derived from the DMAH_CH2_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
6	0h RO	CH2_STAT_DST: The value of this register is derived from the DMAH_CH2_STAT_DST coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
5:3	0h RO	CH2_STW: The value of this register is derived from the DMAH_CH2_STW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
2:0	0h RO	CH2_DTW: The value of this register is derived from the DMAH_CH2_DTW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved



Bit Range	Default & Access	Field Name (ID): Description
21:19	4h RO	CH1_DMS: The value of this register is derived from the DMAH_CH1_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH1_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH1_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH1_FC: The value of this register is derived from the DMAH_CH1_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH1_HC_LLP: The value of this register is derived from the DMAH_CH1_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH1_CTL_WB_EN: The value of this register is derived from the DMAH_CH1_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
11	0h RO	CH1_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH1_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CH1_LOCK_EN: The value of this register is derived from the DMAH_CH1_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CH1_SRC_GAT_EN: The value of this register is derived from the DMAH_CH1_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CH1_DST_SCA_EN: The value of this register is derived from the DMAH_CH1_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CH1_STAT_SRC: The value of this register is derived from the DMAH_CH1_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE





Bit Range	Default & Access	Field Name (ID): Description
30:28	3h RO	CH0_FIFO_DEPTH: The value of this register is derived from the DMAH_CH0_FIFO_DEPTH coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 8 1h = 16 2h = 32 3h = 64 4h = 128
27:25	4h RO	CH0_SMS: The value of this register is derived from the DMAH_CH0_SMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
24:22	0h RO	CH0_LMS: The value of this register is derived from the DMAH_CH0_LMS coreConsultant parameter. For a description of this parameter, refer to page 111. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
21:19	4h RO	CH0_DMS: The value of this register is derived from the DMAH_CH0_DMS coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = MASTER_1 1h = MASTER_2 2h = MASTER_3 3h = MASTER_4 4h = NO_HARDCODE
18:16	2h RO	CH0_MAX_MULT_SIZE: The value of this register is derived from the DMAH_CH0_MULT_SIZE coreConsultant parameter. For a description of this parameter, refer to page 106. 0h = 4 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved
15:14	0h RO	CH0_FC: The value of this register is derived from the DMAH_CH0_FC coreConsultant parameter. For a description of this parameter, refer to page 107. 0h = DMA 1h = SRC 2h = DST 3h = ANY
13	0h RO	CH0_HC_LLP: The value of this register is derived from the DMAH_CH0_HC_LLP coreConsultant parameter. For a description of this parameter, refer to page 110. 0 = FALSE 1 = TRUE
12	0h RO	CH0_CTL_WB_EN: The value of this register is derived from the DMAH_CH0_CTL_WB_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE



Bit Range	Default & Access	Field Name (ID): Description
11	0h RO	CHO_MULTI_BLK_EN: The value of this register is derived from the DMAH_CH0_MULTI_BLK_EN coreConsultant parameter. For a description of this parameter, refer to page 109. 0 = FALSE 1 = TRUE
10	0h RO	CHO_LOCK_EN: The value of this register is derived from the DMAH_CH0_LOCK_EN coreConsultant parameter. For a description of this parameter, refer to page 107. 0 = FALSE 1 = TRUE
9	1h RO	CHO_SRC_GAT_EN: The value of this register is derived from the DMAH_CH0_SRC_GAT_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
8	1h RO	CHO_DST_SCA_EN: The value of this register is derived from the DMAH_CH0_DST_SCA_EN coreConsultant parameter. For a description of this parameter, refer to page 112. 0 = FALSE 1 = TRUE
7	0h RO	CHO_STAT_SRC: The value of this register is derived from the DMAH_CH0_STAT_SRC coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
6	0h RO	CHO_STAT_DST: The value of this register is derived from the DMAH_CH0_STAT_DST coreConsultant parameter. For a description of this parameter, refer to page 111. 0 = FALSE 1 = TRUE
5:3	0h RO	CHO_STW: Refer to the description for bit field DMA_COMP_PARAMS_2_LO.CH0_DTW
2:0	0h RO	CHO_DTW: The value of this register is derived from the DMAH_CH0_DTW coreConsultant parameter. For a description of this parameter, refer to page 108. 0h = NO_HARDCODE 1h = 8 2h = 16 3h = 32 4h = 64 5h = 128 6h = 256 7h = reserved

24.5.248 DW_ahb_dmac Component Parameters Register 2 - High (DMA_COMP_PARAMS_2_HI)—Offset 3ECh

This is a constant read-only register that contains encoded information about the component parameter settings. The reset value depends on coreConsultant parameter(s).

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3ECh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 00000000h




31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CH7_MULTI_BLK_TYPE	CH6_MULTI_BLK_TYPE	CH5_MULTI_BLK_TYPE	CH4_MULTI_BLK_TYPE	CH3_MULTI_BLK_TYPE	CH2_MULTI_BLK_TYPE	CH1_MULTI_BLK_TYPE	CH0_MULTI_BLK_TYPE	

Bit Range	Default & Access	Field Name (ID): Description
31:28	0h RO	CH7_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP
27:24	0h RO	CH6_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP
23:20	0h RO	CH5_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP
19:16	0h RO	CH4_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP



Bit Range	Default & Access	Field Name (ID): Description
15:12	0h RO	CH3_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP
11:8	0h RO	CH2_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP
7:4	0h RO	CH1_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP
3:0	0h RO	CH0_MULTI_BLK_TYPE: The values of these bit fields are derived from the DMAH_CHx_MULTI_BLK_TYPE coreConsultant parameter. For a description of these parameters, refer to page 110. 0h = NO_HARDCODE 1h = CONT_RELOAD 2h = RELOAD_CONT 3h = RELOAD_RELOAD 4h = CONT_LLP 5h = RELOAD_LLP 6h = LLP_CONT 7h = LLP_RELOAD 8h = LLP_LLP



24.5.249 DW_ahb_dmac Component Parameters Register 1 - Low (DMA_COMP_PARAMS_1_LO)—Offset 3F0h

This is a constant read-only register that contains encoded information about the component parameter settings. The reset value depends on coreConsultant parameter(s).

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3F0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: AAAAAAAAAh

31	28	24	20	16	12	8	4	0
1	0	1	0	1	0	1	0	1
0	1	0	1	0	1	0	1	0
CH7_MAX_BLK_SIZE	CH6_MAX_BLK_SIZE	CH5_MAX_BLK_SIZE	CH4_MAX_BLK_SIZE	CH3_MAX_BLK_SIZE	CH2_MAX_BLK_SIZE	CH1_MAX_BLK_SIZE	CH0_MAX_BLK_SIZE	

Bit Range	Default & Access	Field Name (ID): Description
31:28	ah RO	CH7_MAX_BLK_SIZE: The values of these bit fields are derived from the DMAH_CHx_MAX_BLK_SIZE coreConsultant parameter. For a description of these parameters, refer to page 107. 0h = 3 1h = 7 2h = 15 3h = 31 4h = 63 5h = 127 6h = 255 7h = 511 8h = 1023 9h = 2047 - Ah = 4095
27:24	ah RO	CH6_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
23:20	ah RO	CH5_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
19:16	ah RO	CH4_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
15:12	ah RO	CH3_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
11:8	ah RO	CH2_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
7:4	ah RO	CH1_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.
3:0	ah RO	CH0_MAX_BLK_SIZE: Refer to the description for DMA_COMP_PARAMS_1_LO.CH7_MAX_BLK_SIZE.



Bit Range	Default & Access	Field Name (ID): Description
20:19	0h RO	M3_HDATA_WIDTH: The value of this register is derived from the DMAH_M3_HDATA_WIDTH coreConsultant parameter. For a description of this parameter, refer to page 105. 0h = 32 bits 1h = 64 bits 2h = 128 bits 3h = 256 bits
18:17	0h RO	M2_HDATA_WIDTH: The value of this register is derived from the DMAH_M2_HDATA_WIDTH coreConsultant parameter. For a description of this parameter, refer to page 105. 0h = 32 bits 1h = 64 bits 2h = 128 bits 3h = 256 bits
16:15	0h RO	M1_HDATA_WIDTH: The value of this register is derived from the DMAH_M1_HDATA_WIDTH coreConsultant parameter. For a description of this parameter, refer to page 105. 0h = 32 bits 1h = 64 bits 2h = 128 bits 3h = 256 bits
14:13	0h RO	S_HDATA_WIDTH: The value of this register is derived from the DMAH_S_HDATA_WIDTH coreConsultant parameter. For a description of this parameter, refer to page 105. 0h = 32 bits 1h = 64 bits 2h = 128 bits 3h = 256 bits
12:11	01h RO	NUM_MASTER_INT: The value of this register is derived from the DMAH_NUM_MASTER_INT coreConsultant parameter. For a description of this parameter, refer to page 102. 0h = 1 to 3h = 4
10:8	7h RO	NUM_CHANNELS: The value of this register is derived from the DMAH_NUM_CHANNELS coreConsultant parameter. For a description of this parameter, refer to page 102. 0h = 1 to 7h = 8
7:4	0h RW	Undefined0: Reserved.
3	0h RO	MABRST: The value of this register is derived from the DMAH_MABRST coreConsultant parameter. For a description of this parameter, refer to page 103. 0 = FALSE 1 = TRUE
2:1	2h RO	INTR_IO: The value of this register is derived from the DMAH_INTR_IO coreConsultant parameter. For a description of this parameter, refer to page 103. 0h = ALL 1h = TYPE 2h = COMBINED 3h = reserved
0	0h RO	BIG_ENDIAN: The value of this register is derived from the DMAH_BIG_ENDIAN coreConsultant parameter. For a description of this parameter, refer to page 104. 0 = FALSE 1 = TRUE



24.5.251 DMA Component ID RegisterDma - Low (DmaCompsID_LO)— Offset 3F8h

This is the DW_ahb_dmac Component Version register, which is a read-only register that specifies the version of the packaged component in the upper 32 bits and the component type in the lower 32 bits.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 44571110h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	1	0	0	0
0	1	0	0	0	1	0	0	0
0	1	0	1	0	0	0	1	0
0	0	0	1	0	0	0	1	0
0	0	0	1	0	0	0	1	0
0	0	0	1	0	0	0	1	0
0	0	0	1	0	0	0	1	0

DMA_COMP_TYPE

Bit Range	Default & Access	Field Name (ID): Description
31:0	44571110h RO	Designware Component Type (DMA_COMP_TYPE): Designware Component Type number = 0x44_57_11_10. This assigned unique hex value is constant and is derived from the two ASCII letters -DW- followed by a 32-bit unsigned number.



24.5.252 DMA Component ID Register - High (DmaCompsID_HI)—Offset 3FCh

This is the DW_ahb_dmac Component Version register, which is a read-only register that specifies the version of the packaged component in the upper 32 bits and the component type in the lower 32 bits.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:0] + 10h

Default: 3231362Ah

31		28		24		20		16		12		8		4		0															
0	0	1	1	0	0	1	0	0	0	1	1	0	0	1	1	0	0	1	0	1	0	1	0	0	0	1	0	1	0	1	0
DMA_COMP_VERSION																															
Bit Range		Default & Access		Field Name (ID): Description																											
31:0		3231362ah RO		Version of the Component (DMA_COMP_VERSION): Reserved.																											

§ §



Bit Range	Default & Access	Field Name (ID): Description
3	0h RW	gpo1: not applicable
2	0h RW	reset_e: not applicable
1	0h RW	sleep_enable: not applicable
0	0h RW	power_enable: not applicable



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0	MULFNDEV	HEADERTYPE	LATTIMER	CACHELINE_SIZE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

24.7.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR	SIZEINDICATOR	PREFETCHABLE	TYPE	MESSAGE_SPACE				

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.



Bit Range	Default & Access	Field Name (ID): Description
2:1	0h RO	Type (TYPE): 00 indicates BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE): 0. Indicates this BAR is present in the memory space.

24.7.6 Base Address Register 1 (BAR1)—Offset 14h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:2] + 14h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		
PREFETCHABLE1			TYPE1			MESSAGE_SPACE1		

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address Register 1 (BASEADDR1): BAR1 of the LP10 device.
11:4	00h RO	SIZEINDICATOR1: Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE1): Indicates that this BAR is not.
2:1	0h RO	Type (TYPE1): 00 Indicates BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE1): 0. Indicates this BAR is present in the memory space.

24.7.7 Subsystem Vendor and Subsystem ID (SUBSYSTEMID)—Offset 2Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:2] + 2Ch

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW/O	Subsystem ID (SUBSYSTEMID): This register should be implemented for any function that could be instantiated more than once in a given system. The SID register in combination with the Subsystem Vendor ID register, make it possible for the operating environment to distinguish one audio subsystem from the other. This register is a Read Write Once type register.
15:0	0000h RW/O	Subsystem Vendor ID (SUBSYSTEMVENDORID): This register should be implemented for any function that could be instantiated more than once in a given system. The SVID register, in combination with the Subsystem ID register, enables the operating environment to distinguish one subsystem from the other. This register is a Read Write Once register.

Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:2] + 30h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSTON_ROM_BASE								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	EXPANSION_ROM_BASE: Reserved.

24.7.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:2] + 34h



Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
PMESUPPORT					Reserved0			VERSION
					NXTCAP			POWER_CAP

Bit Range	Default & Access	Field Name (ID): Description
31:27	00h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. - bit(11) X XXX1b - PME# can be asserted from D0. - bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. - bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. - bit(14) X 1XXXb - PME# can be asserted from D3hot. - bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the strap strap_pme_support.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.

24.7.12 PME Control and Status Register (PMECTRLSTATUS)—Offset 84h

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:2] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0
Reserved0					PMESTATUS	Reserved1	PMEENABLE	Reserved2
								NO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.



Access Method

Offset: [B:0, D:30, F:2] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
MANID								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



24.8 sSIO PWM 1 Memory Mapped I/O Registers

Table 258. Summary of PWM 1 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"PWM Control Register (PWMCTRL)—Offset 0h" on page 3812	00010000h
804–807h	4	"Software Reset (RESETS)—Offset 804h" on page 3813	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 3813	00000010h

24.8.1 PWM Control Register (PWMCTRL)—Offset 0h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:2] + 10h

Default: 00010000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
PWM_ENABLE	PWM_SW_UPDATE	RSVD0	PWM_BASE_UNIT	PWM_ON_TIME_DIVISOR				

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	PWM Enable (PWM_ENABLE): 0 = Disable PWM Output 1 = Enable PWM Output
30	0b RW	PWM Software Update (PWM_SW_UPDATE): Indication that there is an update to PWM settings pending. SW sets this bit to 1 when updating the PWM_base_unit or PWM_on_time_divisor fields. The PWM module will apply the new settings at the end of the current cycle and reset this bit. 0 = No updates pending 1 = Update pending
29:24	0b RO	RSVD0: Reserved
23:8	0100h RW	PWM Base Unit (PWM_BASE_UNIT): Base unit register. Unsigned 8 integer bits, 8 fraction bits. Used to determine PWM output frequency.
7:0	00h RW	PWM On Time Divisor (PWM_ON_TIME_DIVISOR): PWM duty cycle = PWM_on-time_divisor/256.




Bit Range	Default & Access	Field Name (ID): Description
3	0h RW	gpo1: not applicable
2	0h RW	reset_e: not applicable
1	0h RW	sleep_enable: not applicable
0	0h RW	power_enable: not applicable

25 SIO - Serial Peripheral Interface (SPI)

The Serial I/O implements one SPI controller that supports master mode.

Note: This SPI controller does not support platform firmware (BIOS). See the SPI controller in the PCU instead.



25.1 Signal Descriptions

Please see [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function

Figure 115.SPI Interface Signals (Sheet 1 of 2)

Signal Name	Direction Plat. Power	Description
SIO_SPI_CLK	I/O V1P8S	SPI Serial Clock



Figure 115.SPI Interface Signals (Sheet 2 of 2)

Signal Name	Direction Plat. Power	Description
SIO_SPI_CS#	I/O V1P8S	SPI Chip Select SPI Chip Select is active low.
SIO_SPI_MOSI	O V1P8S	SPI Master Output Slave Input
SIO_SPI_MISO	I V1P8S	SPI Slave Output Master Input

25.2 Features

The following is a list of SPI features:


- Single interrupt line
 - Could be assigned to interrupt PCI INT [A] or ACPISIO INT[1]
- Configurable frame format, clock polarity and clock phase
- supporting one SPI peripheral only
- Supports master mode only
- Receive and transit buffers are both 256x32bits
 - The receive buffer has only 1 water mark
 - The transmit buffer has 2 water marks
- Supports up to 15 Mbps

25.2.1 Clock Phase and Polarity

SPI clock phase and clock polarity overview.

- The SSCR1.SPO polarity setting bit determines whether the serial transfer occurs on the rising edge of the clock or the falling edge of the clock.
 - When SSCR1.SPO = 0, the inactive or idle state of SIO_SPI_CLK is low.
 - When SSCR1.SPO = 1, the inactive or idle state of SIO_SPI_CLK is high.
- The SSCR1.SPH phase setting bit selects the relationship of the serial clock with the slave select signal.
 - When SSCR1.SPH = 0, SIO_SPI_CLK is inactive until one cycle after the start of a frame and active until 1/2 cycle after the end of a frame.
 - When SSCR1.SPH = 1, SIO_SPI_CLK is inactive until 1/2 cycle after the start of a frame and active until one cycle after the end of a frame.

Below figure shows an 8-bit data transfer with different phase and polarity settings.

Figure 116. Clock Phase and Polarity

- In a single frame transfer, the SPI controller supports all four possible combinations for the serial clock phase and polarity.

25.2.2 Mode Numbers

The combinations of polarity and phases are referred to as modes which are commonly numbered according to the following convention, with SSCR1.SPO as the high order bit and SSCR1.SPH as the low order bit.

Table 259. SPI Modes

Mode	SSCR1.SPO	SSCR1.SPH
0	0	0
1	0	1
2	1	0
3	1	1




25.2.3 Frame Direction

The SSCR1.SFRMDIR bit is a read-write bit that determines whether the SSP is the master or slave with respect to driving the SSPSFRM. When SSCR1.SFRMDIR=0, the SSP generates the SSPSFRM internally, acts as the master and drives it. When SSCR1.SFRMDIR=1, the SSP acts as the slave and receives the SSPSFRM signal from an external device. When the SSP is to be configured as a slave to the frame, the external device driving frame must wait until the SSSR.CSS bit is cleared after enabling the SSP before asserting frame (i.e. not external clock cycles are needed, the external device just needs to wait a certain amount of time before asserting frame). When the GPIO alternate function is selected for the SSP, this bit has precedence over the GPIO direction bit (i.e. if SFRMDIR=1, the GPIO is an input, and if SFRMDIR=0, then the pin is an output). Therefore, the SCLKDIR and SFRMDIR bits should be written to before the GPIO direction bits (to prevent any possible contention of the SSPSCLK or SSPSFRM pins). Also, when the SCLKDIR bit is set, the SSCR0.NCS and SSCR0.ECS bits must be cleared.

25.3 Register Map

Figure 117.SIO - SPI Register Map





Type: PCI Configuration Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SUBSYSTEMID					SUBSYSTEMVENDORID			

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
15:0	0000h RW/O	Subsystem Vendor ID (SUBSYSTEMVENDORID): This register should be implemented for any function that could be instantiated more than once in a given system. The SVID register, in combination with the Subsystem ID register, enables the operating environment to distinguish one subsystem from the other. This register is a Read Write Once register.

25.4.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:5] + 30h

Default: 00000000h

31	28				24				20				16				12				8				4				0		
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
EXPANSTION_ROM_BASE																															

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	EXPANSION_ROM_BASE: Reserved.

25.4.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:5] + 34h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. If PM capability is disabled then this register has 00h.

25.4.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:5] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MAX_LAT				MIN_GNT				INTPIN
				Reserved0				INTLINE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a Single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to tell software which interrupt line the interrupt pin is connected to.

25.4.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:5] + 80h

Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
PMESUPPORT				Reserved0				POWER_CAP
				VERSION				
				NXTCAP				

25.4.13 Manufacturer ID (MANID)—Offset F8h

Bit Range	Default & Access	Field Name (ID): Description
3	1h RO	No_Soft_Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state - Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for Downstream decode on fabric ports.

25.4.13 Manufacturer ID (MANID)—Offset F8h

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:5] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
MANID								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	Mode (MOD): 0 = Normal SSP Mode 1 = Network Mode
30	0b RW	Audio Clock Select (ACS): 0 = Clock selection is determined by the NCS and ECS bits 1 = Audio Clock (and Audio Clock Divider) are used to create the SSP's serial clock (SSPCLK)
29	0b RO	Reserved (RSVD): Reserved.
28:27	00b RO	RSVD: Reserved
26:24	000b RW	Frame Rate Divider Control (FRDC): Value 0-7 indicates the number of time slots per frame when in network mode (the actual number of time slots is FRDC+1, so 1 to 8 time slots).
23	0b RW	Transmit FIFO Under Run Interrupt Mask (TIM): 0 = TUR events will generate an SSP interrupt 1 = TUR events will not generate an SSP interrupt
22	0b RW	Receive FIFO Over Run Interrupt Mask (RIM): 0 = ROR events will generate an SSP interrupt 1 = ROR events will not generate an SSP interrupt
21	0b RW	Network Clock Select (NCS): 0 = Clock selection is determined by ECS bit 1 = Network clock is used to create the SSP's serial clock (SSPCLK)
20	0b RW	Extended Data Size Select (EDSS): 0 = A zero is prepended to the DSS value, which sets the DSS range from 4-16 bits 1 = A one is pre-appended to the DSS value which sets the DSS range from 17-32 bits
19:8	000h RW	Serial Clock Rate (SCR): Value (0 to 4095) used to generate transmission rate of SSP. Serial bit rate = SSP clock/(SCR+1), where SCR is decimal integer.
7	0b RW	Synchronous Serial Port Enable (SSE): 0 = SSP operation disabled 1 = SSP operation enabled
6	0b RW	External Clock Select (ECS): 0 = On-chip clock used to produce the SSP's serial clock (SSPCLK) 1 = SSPEXTCLK/GPIO pin is used to create the SSP's SSPCLK
5:4	00b RW	Frame Format (FRF): 00 = Motorola Serial Peripheral Interface (SPI) 01 = Texas Instruments Synchronous Serial Protocol (SSP) 10 = National Semiconductor Microwire 11 = Programmable Serial Protocol (PSP)
3:0	0000b RW	Data Size Select (DSS): With EDSS as MSB, value+1 gives data size. Values 4 to 32 allowed.



25.5.2 SSP Control Register 1 (SSCR1)—Offset 4h

The Enhanced SSP Control 1 registers contain bit fields that control various SSP functions. Bits must be set to the preferred value before enabling the Enhanced SSP. Note that Writes to reserved bits should be zeroes, and Read value of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h


31				28				24				20				16				12				8				4				0																																																																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																							
TTTEP				TTE				EBCEI				SCFR				ECRA				ECRB				SCLKDIR				SFRMDIR				RWOT				TRAIL				TSRE				RSRE				TINTE				PINTE				RSVD				IFS				STRF				EFWR				RFT				TFT				MWDS				SPH				SPO				LBM				TIE				RIE			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RW	TXD Tristate Enable on Last Phase (TTELP): 0 = TXD line will be tristated on same clock edge as TXD is to be flopped 1 = TXD line will be tristated clock edge after TXD is to be flopped
30	0b RW	TXD Tristate Enable (TTE): 0 = TXD line will not be tristated 1 = TXD line will be tristated when no transmitting data
29	0b RW	Enable Bit Count Error Interrupt (EBCEI): 0 = Interrupt due to a bit count error is disabled 1 = Interrupt due to a bit count error is enabled
28	0b RW	Slave Clock Free Running (SCFR): 0 = clock input to SSPSCLK is continuously running 1 = clock input to SSPSCLK is only active during transfers
27	0b RW	Enable Clock Request A (ECRA): 0 = clock request from other SSP is disabled 1 = clock request from other SSP is enabled
26	0b RW	Enable Clock Request B (ECRB): 0 = clock request from other SSP is disabled 1 = clock request from other SSP is enabled
25	0b RW	SSP Serial Bit Rate Clock (SSPSCLK) Direction (SCLKDIR): 0 = Master mode, SSP drives SSPSCLK 1 = Slave mode, SSP receives SSPSCLK
24	0b RW	SSP Frame (SSPSFRM) Direction (SFRMDIR): 0 = Master mode, SSP drives SSPSFRM 1 = Slave mode, SSP receives SSPSFRM
23	0b RW	Receive With Out Transmit (RWOT): 0 = Transmit/Receive mode 1 = Receive without Transmit mode
22	0b RW	Trailing Byte (TRAIL): 0 = Processor based, trailing bytes are handled by processor 1 = DMA based, trailing bytes are handled by DMA



Bit Range	Default & Access	Field Name (ID): Description
21	0b RW	Transmit Service Request Enable (TSRE): 0 = DMA Service Request is disabled 1 = DMA Service Request is enabled
20	0b RW	Receive Service Request Enable (RSRE): 0 = DMA Service Request is disabled 1 = DMA Service Request is enabled
19	0b RW	Receiver Time-out Interrupt Enable (TINTE): 0 = Receiver Time-out interrupts are disabled 1 = Receiver Time-out interrupts are enabled
18	0b RW	Peripheral Trailing Byte Interrupts Enable (PINTE): 0 = Peripheral Trailing Byte Interrupts are disabled 1 = Peripheral Trailing Byte Interrupts are enabled
17	0b RW	RSVD: Reserved
16	0b RW	Invert Frame Signal (IFS): 0 = Frame polarity is determined by SSP format and PSP polarity bits. 1 = Frame signal will be inverted from the normal SSP frame signal (as defined by the SSP format and PSP polarity bits).
15	0b RW	STRF: Select FIFO for EFWR (test mode bit) (when EFWR=1) 0 = Transmit FIFO is selected for both writes and reads through the SSP Data Register (SSDR) 1 = Receive FIFO is selected for both writes and reads through the SSP Data Register (SSDR)
14	0b RW	Enable FIFO Write/Read (EFWR): Test mode bit. 0 = FIFO write/read special function is disabled (normal SSP operational mode) 1 = FIFO write/read special function is enabled
13:10	0000b RW	Receive FIFO Trigger Threshold (RFT): Sets threshold level at which receive FIFO asserts interrupt. This level should be set to the desired threshold value minus 1.
9:6	0000b RW	Transmit FIFO Trigger Threshold (TFT): Sets threshold level at which transmit FIFO asserts interrupt. This level should be set to the desired threshold value minus 1.
5	0b RW	Microwire Transmit Data Size (MWDS): 0 = 8-bit command words are transmitted 1 = 16-bit command words are transmitted
4	0b RW	Motorola SPI SSPCLK Phase Setting (SPH): 0 = SSPCLK is inactive one cycle at the start of a frame and cycle at the end of a frame 1 = SSPCLK is inactive cycle at the start of a frame and one cycle at the end of a frame
3	0b RW	Motorola SPI SSPCLK Polarity Setting (SPO): 0 = The inactive or idle state of SSPCLK is low 1 = The inactive or idle state of SSPCLK is high
2	0b RW	Loop-Back Mode (LBM): Test mode bit. 0 = Normal serial port operation enabled 1 = Output of transmit serial shifter connected to input of receive serial shifter, internally
1	0b RW	Transmit FIFO Interrupt Enable (TIE): 0 = Transmit FIFO level interrupt is disabled 1 = Transmit FIFO level interrupt is enabled

25.5.3 SSP Status Register (SSSR)—Offset 8h



Bit Range	Default & Access	Field Name (ID): Description
17:16	00b RO	RSVD2: Reserved
15:12	1111b RO	Receive FIFO Level (RFL): Number of entries minus one in Receive FIFO. Note: When the value 0xF is read, the FIFO is either empty or full and the programmer should refer to the RNE bit.
11:8	0000b RO	Transmit FIFO Level (TFL): Number of entries in Transmit FIFO. Note: When the value 0x0 is read, the FIFO is either empty or full and the programmer should refer to the TNF bit.
7	0b RW1C	Receive FIFO Overrun (ROR): 0 = Receive FIFO has not experienced an overrun 1 = Attempted data write to full receive FIFO, request interrupt
6	0b RO	Receive FIFO Service Request (RFS): 0 = Receive FIFO level is at or below RFT threshold (RFT), or SSP disabled 1 = Receive FIFO level exceeds RFT threshold (RFT), request interrupt
5	0b RO	Transmit FIFO Service Request (TFS): 0 = Transmit FIFO level exceeds the TFT threshold (TFT+1), or SSP disabled 1 = Transmit FIFO level is at or below TFT threshold (TFT+1), request interrupt
4	0b RO	SSP Busy (BSY): 0 = SSP is idle or disabled 1 = SSP currently transmitting or receiving a frame
3	0b RO	Receive FIOF Not Empty (RNE): 0 = Receive FIFO is empty 1 = Receive FIFO is not empty
2	1b RO	Transmit FIFO Not Full (TNF): 0 = Transmit FIFO is full 1 = Transmit FIFO is not full
1:0	00b RO	RSVD3: Reserved

25.5.4 SSP Interrupt Test Register (SSITR)—Offset Ch

The read-write SSP Interrupt Test registers should be used only for testing purposes. Writing a 1 to the test transmit FIFO request SSITR.TTFS, bit 5, will generate a non-maskable Interrupt strobe signal to the Interrupt controller, and a DMA request for the Transmit FIFO. Writing a 1 to the test receive FIFO request SSITR.TRFS, bit 6, will generate a non-maskable Interrupt strobe signal to the Interrupt controller, and a DMA request for the Receive FIFO. Writing a 1 to the test receive FIFO overrun bit SSITR.TROR, bit 7, will generate a non-maskable Interrupt strobe signal to the Interrupt controller only, no DMA request will be made. Setting any of these bits will also cause the corresponding status bit(s) to be set in the Enhanced SSP Status register (SSSR). The Interrupt and/or service request, caused by the setting of one of these test bits, will remain active until the test bit is cleared by writing a 0 it. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h



25.5.5 SSP Data (SSDR)—Offset 10h

Access Method

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h



The Enhanced SSP Time-Out registers have single bit fields that specify the time-out value used to signal a period of inactivity within the Receive FIFO. Note that Writes to reserved bits must be zeroes, and Read values of these bits are undetermined.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				TIMEOUT				

25.5.7 SSP Programmable Serial Protocol (SSPSP)—Offset 2Ch

The Enhanced SSP Programmable Protocol registers are read-write registers that contain eight fields that are used to program the various programmable serial-protocol parameters. When using PSP format in Network mode, the parameters SFRMDLY, STRTDLY, DMYSTP, DMYSTRT must be set to 0. Other parameters (such as FRMPOL, SCMODE, FSRT, SFRMDWTH) are programmable. Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD1	FSRT	DMYSTOP	RSVD2	SFRMWDTH	SFRMDLY	DMYSTRT	STRTDLY	ETDS
								SFRMP
								SCMODE

Bit Range	Default & Access	Field Name (ID): Description
31:26	000000b RO	RSVD1: Reserved
25	0b RW	Frame Sync Relative Timing Bit (FSRT): 0 = Next frame is asserted after the end of the T4 timing 1 = Next frame is asserted with the LSB of the previous frame
24:23	00b RW	Dummy Stop (DMYSTOP): Programmed value sets the number of SSPSCLK cycles that follow the transmitted data.
22	0b RW	RSVD2: Reserved
21:16	000000b RW	Serial Frame Width (SFRMWDTH): Programmed value sets frame width (1-38).
15:9	0000000b RW	Serial Frame Delay (SFRMDLY): Programmed value sets the number of half SSPSCLK cycles from TXD/RXD being driven to SSPSFRM being asserted (0-74).
8:7	00b RW	Dummy Start (DMYSTRT): Programmed value sets the number of SSPSCLKs, after STRTDLY is complete, that precede the transmit/receive data.
6:4	000b RW	Start Delay (STRTDLY): Programmed value sets start delay that is used to set the idle time of SSPSCLK between transfers (0-7 SSPSCLK periods).
3	0b RW	End of Transfer Data State (ETDS): 0 = Low 1 = Last value (bit 0)
2	0b RW	Serial Frame Polarity (SFRMP): 0 = SSPSFRM is active low 1 = SSPSFRM is active high
1:0	00b RW	Serial Bit-rate Clock Mode (SCMODE): 00 = Data driven (falling), Data sampled (rising), Idle state (low) 01 = Data driven (rising), Data sampled (falling), Idle state (low) 10 = Data driven (rising), Data sampled (falling), Idle state (high) 11 = Data driven (falling), Data sampled (rising), Idle state (high)

25.5.8 SSP TX Time Slot Active (SSTSA)—Offset 30h

The Enhanced SSP TX Time Slot Active registers are read-write registers that indicate which Time Slot the Enhanced SSP will transmit data in. They are ignored if the Enhanced SSP is not in Network Mode (SSCR0.MOD = 1). Note that Writes to reserved bits must be zeroes, and Read value of these bits are undetermined.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD						TTSA		

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	RSVD: Reserved
7:0	00h RW	TX Time Slot Active (TTSA): 0 = SSP will not transmit data in this time slot 1 = SSP will transmit data in this time slot

25.5.9 SSP RX Time Slot Active (SSRSA)—Offset 34h

The Enhanced SSP RX Time Slot Active registers are read-write registers that indicate which Time Slot the Enhanced SSP will receive data in. They are ignored if the Enhanced SSP is not in Network Mode (SSCR0.MOD = 1). Note that Writes to reserved bits must be zeroes, and Read values of these bits are undetermined.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD						RTSA		

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	RSVD: Reserved
7:0	00h RW	RX Time Slot Active (RTSA): 0 = SSP will not receive data in this time slot 1 = SSP will receive data in this time slot

25.5.10 SSP Time Slot Status (SSTSS)—Offset 38h

The Enhanced SSP Time Slot Status registers are read only registers that indicate which Time Slot the Enhanced SSP is currently in when the Enhanced SSP is in Network Mode (SSCR0.MOD = 1). This register is not valid when the Enhanced SSP is not in Network Mode. Note that Writes to reserved bits must be zeroes, and Read values of these bits are undetermined.

Access Method



Bit Range	Default & Access	Field Name (ID): Description
6:4	000b RW	Audio Clock PLL Select (ACPS): Value indicates which PLL output clock is sent to the clock divider in the clock unit. 000b = 5.622MHz 001b = 11.345MHz 010b = 12.235MHz 011b = 14.857MHz 100b = 32.842MHz 101b = 48.000MHz 110b, 111b = Reserved
3	0b RW	SYSCLK Divider Bypass (SCDB): 0 = SYSCLK is divided by 4 before being sent to SSP 1 = SYSCLK is not divided before being sent to SSP
2:0	000b RW	Audio Clock Divider Select (ACDS): Value indicates which divider will be used by the clock unit to create the SYSCLK output pin. Clock divider value will be 2^{ACDS} , max ACDS = 5.

25.5.12 I2S Transmit FIFO (ITF)—Offset 40h

The I2S Transmit FIFO register is for writing the water mark for the I2S transmit FIFO, and also for reading the number of entries in the I2S transmit FIFO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	ITFL			LWMTF			HWMTF	

Bit Range	Default & Access	Field Name (ID): Description
31	0h RO	RSVD: Reserved
30:20	0b RO	I2S Transmit FIFO Level (ITFL): Number of entries in I2S Transmit FIFO.
19:10	0b RW	Low Water Mark Transmit FIFO (LWMTF): Set the low water mark of the I2S transmit FIFO.
9:0	0b RW	High Water Mark Transmit FIFO (HWMTF): Set the high water mark of the I2S transmit FIFO.



25.5.13 SPI Transmit FIFO (SITF)—Offset 44h

The SPI Transmit FIFO register is for writing the water mark for the SPI transmit FIFO and also for reading the number of entries in the SPI transmit FIFO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0							
0				0				0				0				0				0				0				0				0				0			
RSVD								SITFL								LWMTF								HWMTF															

Bit Range	Default & Access	Field Name (ID): Description
31:25	0h RO	RSVD: Reserved
24:16	0b RO	SPI Transmit FIFO Level (SITFL): Number of entries in SPI Transmit FIFO.
15:8	0b RW	Low Water Mark Transmit FIFO (LWMTF): Set the low water mark of the SPI transmit FIFO.
7:0	0b RW	High Water Mark Transmit FIFO (HWMTF): Set the high water mark of the SPI transmit FIFO.

25.5.14 SPI Receive FIFO (SIRF)—Offset 48h

The SPI Receive FIFO register is for writing the water mark for the SPI receive FIFO, and also for reading the number of entries in the SPI receive FIFO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				SIRFL				WMRF

Bit Range	Default & Access	Field Name (ID): Description
31:17	0h RO	RSVD: Reserved



Bit Range	Default & Access	Field Name (ID): Description
16:8	0b RO	SPI Receive FIFO Level (SIRFL): Number of entries in SPI Receive FIFO.
7:0	0b RW	WMRF: Water Mark Receive FIFO. Set the water mark of the SPI receive FIFO.

25.5.15 Private Clock Params (PRV_CLOCK_PARAMS)—Offset 400h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 400h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	0	0	
clk_update	n_val				m_val				clk_en

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	clk_update: Update the clock divider after setting new m and n values.
30:16	0h RW	N_VAL (n_val): n value for the m over n divider.
15:1	0h RW	M_VAL (m_val): m value for the m over n divider.
0	0h RW	clk_en: clk en of the m over n divider.

25.5.16 Software Reset (RESETS)—Offset 404h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 404h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	0	0
reserved										reset_func
										reset_anh

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	Reserved (reserved): Reserved
1	0h RW	reset_func: Reset the func clock domain.
0	0h RW	reset_apb: Reset the apb domain.

25.5.17 General Purpose Register (GENERAL)—Offset 408h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 408h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RSVD0		spi_terminate_tx_on_rx_full_disable	RSVD1						gpo3
		spi1_dma_rxtx_holdoff_disable							gpo2
									gpo1
									reset_e
									sleep_enable
									power_enable

Bit Range	Default & Access	Field Name (ID): Description
31:26	0b RO	RSVDO: Reserved



Access Method

Offset: [BAR] + 40Ch

BAR Reference: [B:0, D:30, F:5] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:4	0b RO	RSVD0: Reserved
3	0h RW	gpio_sspsclken: Not applicable.
2	0h RW	brg_pio_r: Not applicable.



Bit Range	Default & Access	Field Name (ID): Description
1	0h RW	ILB_CKBIT: This bit field is a legacy (chicken bit) bug fix established in previous Intel projects. The driver should set this bit to 0b to ensure correct operation.
0	0h RW	disable_ssp_dma_finish: disable ssp dma finish

25.5.19 reg_SPI_CS_CTRL_REG (SPI_CS_CTRL)—Offset 418h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 418h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:5] + 10h


Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	spi_cs_state	spi_cs_mode
reserved										

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	reserved: reserved
1	0h RW	spi_cs_state: SW override of CS line in SW mode for spi.
0	0h RW	spi_cs_mode: Selects HW mode or SW mode for chip select for spi.

26 SIO - I²C Interface

The SoC supports 7 instances of I²C controller. Both 7-bit and 10-bit addressing modes are supported. These controllers operate in master mode only.



26.1 Signal Descriptions

I²C is a two-wire bus for inter-IC communication. Data and clock signals carry information between the connected devices. The following is the I²C Interface. The SoC supports 7 I²C interfaces for general purpose to control external devices. The I²C signals are muxed over GPIOs.


Please see [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function

Table 262. I²C[6:0] Signals

Signal Name	Direction Plat. Power	Description
SIO_I2C[6:0]_DATA	I/O V1P8S	I²C Serial Data <i>These signals are muxed and may be used by other functions.</i>
SIO_I2C[6:0]_CLK	I/O V1P8S	I²C Serial Clock <i>These signals are muxed and may be used by other functions.</i>



26.2 Features

26.2.1 I²C Protocol

The I²C bus is a two-wire serial interface, consisting of a serial data line and a serial clock. These wires carry information between the devices connected to the bus. Each device is recognized by a unique address and can operate as either a “transmitter” or “receiver,” depending on the function of the device. Devices are considered slaves when performing data transfers, as the SoC will always be a Master. A master is a device which initiates a data transfer on the bus and generates the clock signals to permit that transfer. At that time, any device addressed is considered a slave.

- The SoC is always the I²C master; and it supports multi-master mode.
- The SoC can support clock stretching by slave devices.
- The SIO_I2Cx_DATA line is a bidirectional signal and changes only while the SIO_I2Cx_CLK line is low, except for STOP, START, and RESTART conditions.
- The output drivers are open-drain or open-collector to perform wire-AND functions on the bus.
- The maximum number of devices on the bus is limited by the maximum capacitance specification of 400 pF
- Refer to [Chapter 9, “Electrical Specifications”](#) for details.
- Data is transmitted in byte packages.

26.2.2 I²C Modes of Operation

The I²C module can operate in the following modes:

- Standard mode (with a bit rate up to 100 Kb/s)
- Fast mode (with a bit rate up to 400 Kb/s)
- Fast-mode Plus (Fm+, with a bit rate up to 1 Mb/s)
- High-speed mode (Hs-mode, with a bit rate up to 3.4 Mb/s)

Note: Higher speeds require tuning of the analog buffers. Please work with your BIOS vendor to incorporate.

The I²C can communicate with devices only using these modes as long as they are attached to the bus. Additionally, high speed mode, fast mode plus and fast mode devices are downward compatible.


- High-speed mode devices can communicate with fast mode and standard mode devices in a mixed speed bus system.
- Fast mode devices can communicate with standard mode devices in a 0–100 Kb/s I²C bus system.

However, according to the I²C specification, standard mode devices are not upward compatible and should not be incorporated in a fast-mode I²C bus system since they cannot follow the higher transfer rate and unpredictable states would occur.

26.2.3 Functional Description

- The I²C master is responsible for generating the clock and controlling the transfer of data.
- The slave is responsible for either transmitting or receiving data to/from the master.
- The acknowledgment of data is sent by the device that is receiving data, which can be either a master or a slave.
- Each slave has a unique address that is determined by the system designer:
 - When a master wants to communicate with a slave, the master transmits a START/RESTART condition that is then followed by the slave's address and a control bit (R/W), to determine if the master wants to transmit data or receive data from the slave.
 - The slave then sends an acknowledge (ACK) pulse after the address.
- If the master (master-transmitter) is writing to the slave (slave-receiver)
 - The receiver gets one byte of data.
 - This transaction continues until the master terminates the transmission with a STOP condition.
- If the master is reading from a slave (master-receiver)
 - The slave transmits (slave-transmitter) a byte of data to the master, and the master then acknowledges the transaction with the ACK pulse.
 - This transaction continues until the master terminates the transmission by not acknowledging (NACK) the transaction after the last byte is received, and then the master issues a STOP condition. This behavior is illustrated in below figure.

Figure 118. Data Transfer on the I²C Bus






26.2.3.1 START and STOP Conditions

When the bus is idle, both the clock and data signals are pulled high through external pull-up resistors on the bus.

When the master wants to start a transmission on the bus, the master issues a START condition.

- This is defined to be a high-to-low transition of the data signal while the clock is high.
- When the master wants to terminate the transmission, the master issues a STOP condition. This is defined to be a low-to-high transition of the data line while the clock is high. [Figure 119](#) shows the timing of the START and STOP conditions.
- When data is being transmitted on the bus, the data line must be stable when the clock is high.

Figure 119. START and STOP Conditions



The signal transitions for the START/STOP conditions, as depicted above, reflect those observed at the output of the master driving the I²C bus. Care should be taken when observing the data/clock signals at the input of the slave(s), because unequal line delays may result in an incorrect data/clock timing relationship.


26.2.3.2 Addressing Slave Protocol

There are two address formats—seven-bit address format and 10-bit address format.

Seven-bit Address Format

- During the seven-bit address format, the first seven bits (bits 7:1) of the first byte set the slave address and the LSB bit (bit 0) is the R/W bit as shown in [Figure 120](#).
- When bit 0 (R/W) is set to 0, the master writes to the slave. When bit 0 (R/W) is set to 1, the master reads from the slave.


Figure 120. Seven-Bit Address Format



Ten-bit Address Format

- During 10-bit addressing, 2 bytes are transferred to set the 10-bit address. The transfer of the first byte contains the following bit definition.
 - The first five bits (bits 7:3) notify the slaves that this is a 10-bit transfer. The next two bits (bits 2:1) set the slaves address bits 9:8, and the LSB bit (bit 0) is the RW bit.
 - The second byte transferred sets bits 7:0 of the slave address.
 - Figure 121 shows the 10-bit address format, and Table 263 defines the special purpose and reserved first byte addresses.

Figure 121. Ten-Bit Address Format


Table 263. I²C Definition of Bits in First Byte (Sheet 1 of 2)

Slave Address	RW Bit	Description
0000 000	0	General Call Address —The I ² C controller places the data in the receive buffer and issues a General Call interrupt.
0000 000	1	START byte —For more details, refer to I ² C bus specification section 3.15.
0000 001	X	CBUS address —I ² C controller ignores these accesses.
0000 010	X	Reserved
0000 011	X	Reserved

Table 263. I²C Definition of Bits in First Byte (Sheet 2 of 2)

Slave Address	RW Bit	Description
0000 1XX	X	High-speed master code
1111 1XX	X	Reserved
1111 0XX	X	Ten (10)-bit slave addressing

26.2.3.3 Transmit and Receive Protocol


The master can initiate data transmission and reception to/from the bus, acting as either a master-transmitter or master-receiver. A slave responds to requests from the master by either transmitting data or receiving data to/from the bus, acting as either a slave-transmitter or slave-receiver, respectively.

Master-Transmitter and Slave-Receiver

All data is transmitted in byte format, with no limit on the number of bytes transferred per data transfer. After the master sends the address and RW bit or the master transmits a byte of data to the slave, the slave-receiver must respond with the acknowledge signal (ACK). When a slave-receiver does not respond with an ACK pulse, the master aborts the transfer by issuing a STOP condition. The slave must leave the data line high so that the master can abort the transfer.

If the master-transmitter is transmitting data as shown in Figure 122, then the slave-receiver responds to the master-transmitter with an acknowledge pulse after every byte of data is received.

Figure 122. Master Transmitter Protocol




Master-Receiver and Slave-Transmitter

If the master is receiving data as shown in Figure 123, the master responds to the Slave-Transmitter with an acknowledge pulse after a byte of data has been received, except for the last byte. This is the way the Master-Receiver notifies the Slave-Transmitter that this is the last byte. The Slave-Transmitter relinquishes the data line after detecting the No Acknowledge (NACK) so that the master can issue a STOP condition.

When a master does not want to relinquish the bus with a STOP condition, the master can issue a RESTART condition. This is identical to a START condition except it occurs after the ACK pulse. The master can then communicate with the same slave.


Figure 123. Master Receiver Protocol




26.2.3.4 START BYTE Transfer Protocol

The START BYTE Transfer protocol is set up for systems that do not have an on-board dedicated I²C hardware module. When the I²C controller is a master, it supports the generation of START BYTE transfers at the beginning of every transfer in case a slave device requires it. This protocol consists of 7 '0's being transmitted followed by a 1, as illustrated in Figure 124. This allows the processor that is polling the bus to under-sample the address phase until 0s are detected. Once the microcontroller detects a 0, it switches from the under sampling rate to the correct rate of the master.

Figure 124. START Byte Transfer





The START BYTE procedure is as follows:

1. Master generates a START condition.
2. Master transmits the START byte (0000 0001).
3. Master transmits the ACK clock pulse. (Present only to conform with the byte handling format used on the bus.)
4. No slave sets the ACK signal to 0.
5. Master generates a RESTART (R) condition.

A hardware receiver does not respond to the START BYTE because it is a reserved address and resets after the RESTART condition is generated.

26.3 Use

26.3.1 Master Mode Operation

To use the I²C controller as a master, perform the following steps:

1. Disable the I²C controller by writing 0 (zero) to IC_ENABLE.ENABLE.
2. Write to the IC_CON register to set the maximum speed mode supported for slave operation IC_CON.SPEED and to specify whether the I²C controller starts its transfers in 7/10 bit addressing mode when the device is a slave (IC_CON.IC_10BITADDR_SLAVE).
3. Write to the IC_TAR register the address of the I²C device to be addressed. It also indicates whether a General Call or a START BYTE command is going to be performed by I²C. The desired speed of the I²C controller master-initiated transfers, either 7-bit or 10-bit addressing, is controlled by the IC_TAR.IC_10BITADDR_MASTER bit field.
4. Write to the IC_HS_MADDR register the desired master code for the I²C controller. The master code is programmer-defined.
5. Enable the I²C controller by writing a 1 in IC_ENABLE.
6. Now write the transfer direction and data to be sent to the IC_DATA_CMD register. If the IC_DATA_CMD register is written before the I²C controller is enabled, the data and commands are lost as the buffers are kept cleared when the I²C controller is not enabled.

The I²C controller supports updating of the IC_TAR.IC_TAR and IC_TAR.IC_10BITADDR_MASTER. The IC_TAR register can be written to provided the following conditions are met:

- The I²C controller is not enabled (IC_ENABLE.ENABLE=0)

The I²C controller supports switching back and forth between reading and writing based on what is written in IC_CMD register. To transmit data, write the data to be written to the lower byte of the I²C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD). The IC_DATA_CMD.CMD should be written to 0 for I²C write operations. Subsequently, a read command may be issued by writing "don't cares" to IC_DATA_CMD.DAT register bits, and a 1 should be written to the IC_DATA_CMD.CMD bit.

26.3.2 Disabling the I²C Controller

The register IC_ENABLE allows software to unambiguously determine when the hardware has completely shutdown in response to the IC_ENABLE.ENABLE register being cleared from 1 to 0.

Procedure


1. Define a timer interval (t_{i2c_poll}) equal to 10 times the signaling period for the highest I²C transfer speed used in the system and supported by the I²C controller. For example, if the highest I²C transfer mode is 400Kb/s, then this t_{i2c_poll} is 25 μ s.
2. Define a maximum time-out parameter, MAX_T_POLL_COUNT, such that if any repeated polling operation exceeds this maximum value, an error is reported.
3. Execute a blocking thread/process/function that prevents any further I²C master transactions to be started by software, but allows any pending transfers to be completed.
4. The variable POLL_COUNT is initialized to zero (0).
5. Clear IC_ENABLE.ENABLE to zero (0).
6. Read the IC_ENABLE_STATUS.IC_EN bit. Increment POLL_COUNT by one. If $POLL_COUNT \geq MAX_T_POLL_COUNT$, exit with the relevant error code.
7. If IC_ENABLE_STATUS.IC_EN is 1, then sleep for t_{i2c_poll} and proceed to the previous step. Otherwise, exit with a relevant success code.

26.4 References

I²C-Bus Specification and User Manual, Revision 03: <http://ics.nxp.com/support/documents/interface/pdf/i2c.bus.specification.pdf>

26.5 Register Map

Refer to [Chapter 3, "Register Access Methods"](#) and [Chapter 4, "Mapping Address Spaces"](#) for additional information.

Figure 125.SIO - I²C Register Map



Access Method

Offset: [B:0, D:24, F:1] + 8h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

26.6.4 Cache Line Latency Header and BIST (CLLATHEADERBIST)—Offset Ch

Access Method

Offset: [B:0, D:24, F:1] + Ch

October 2018
Document Number: 538136, Rev. 4.3



31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				MULFNDEV	HEADERTYPE			
					LATTIMER			
								CACHELINE_SIZE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

26.6.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR						SIZEINDICATOR	PREFETCHABLE	TYPE
								MESSAGE_SPACE

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.



Access Method

Offset: [B:0, D:24, F:1] + 14h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		
						PREFETCHABLE1		
						TYPE1		
						MESSAGE_SPACE1		

26.6.7 Subsystem Vendor and Subsystem ID (SUBSYSTEMID)—Offset 2Ch

Access Method

Offset: [B:0, D:24, F:1] + 2Ch

October 2018
Document Number: 538136, Rev. 4.3



26.6.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Offset: [B:0, D:24, F:1] + 30h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSION_ROM_BASE								

26.6.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Offset: [B:0, D:24, F:1] + 34h



Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
PMESUPPORT				Reserved0	VERSION	NXTCAP	POWER_CAP	

Bit Range	Default & Access	Field Name (ID): Description
31:27	00h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. - bit(11) X XXX1b - PME# can be asserted from D0. - bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. - bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. - bit(14) X 1XXXb - PME# can be asserted from D3hot. - bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the strap strap_pme_support.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.

26.6.12 PME Control and Status Register (PMECTRLSTATUS)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:1] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				PMESTATUS	Reserved1	PMEENABLE	Reserved2	NO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.



Access Method

Offset: [B:0, D:24, F:1] + F8h

[illegible]

October 2018
Document Number: 538136, Rev. 4.3



26.7 SIO I²C 0 Memory Mapped I/O Registers

Table 265. Summary of I²C 0 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"I2C Control Register (IC_CON)—Offset 0h" on page 3867	0000007Fh
4–7h	4	"I2C Target Address Register (IC_TAR)—Offset 4h" on page 3868	00001055h
8–Bh	4	"I2C Slave Address Register (IC_SAR)—Offset 8h" on page 3869	00000055h
C–Fh	4	"I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch" on page 3869	00000001h
10–13h	4	"I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h" on page 3870	00000000h
14–17h	4	"Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h" on page 3871	00000190h
18–1Bh	4	"Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h" on page 3872	000001D6h
1C–1Fh	4	"Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch" on page 3872	0000003Ch
20–23h	4	"Fast Speed I2C Clock SCL Low Count Register (IC_FS_SCL_LCNT)—Offset 20h" on page 3873	00000082h
24–27h	4	"High Speed I2C Clock SCL High Count Register (IC_HS_SCL_HCNT)—Offset 24h" on page 3873	0000000Ch
28–2Bh	4	"High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h" on page 3874	00000020h
2C–2Fh	4	"I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch" on page 3875	00000000h
30–33h	4	"I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h" on page 3876	000008FFh
34–37h	4	"I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h" on page 3877	00000000h
38–3Bh	4	"I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h" on page 3878	00000010h
3C–3Fh	4	"I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch" on page 3879	00000010h
40–43h	4	"Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h" on page 3879	00000000h
44–47h	4	"Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h" on page 3880	00000000h
48–4Bh	4	"Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h" on page 3880	00000000h
4C–4Fh	4	"Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch" on page 3881	00000000h
50–53h	4	"Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h" on page 3881	00000000h
54–57h	4	"Clear TX_ABORT Interrupt Register (IC_CLR_TX_ABORT)—Offset 54h" on page 3882	00000000h
58–5Bh	4	"Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h" on page 3882	00000000h
5C–5Fh	4	"Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch" on page 3883	00000000h
60–63h	4	"Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h" on page 3883	00000000h




Table 265. Summary of I²C 0 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
64–67h	4	"Clear START_DET Interrupt Register (IC_CLR_START_DET)—Offset 64h" on page 3884	00000000h
68–6Bh	4	"Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h" on page 3884	00000000h
6C–6Fh	4	"I2C Enable Register (IC_ENABLE)—Offset 6Ch" on page 3885	00000000h
70–73h	4	"I2C Status Register (IC_STATUS)—Offset 70h" on page 3886	00000006h
74–77h	4	"I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h" on page 3887	00000000h
78–7Bh	4	"I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h" on page 3887	00000000h
7C–7Fh	4	"I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch" on page 3888	00000001h
80–83h	4	"I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h" on page 3889	00000000h
84–87h	4	"Generate Slave Data NACK Register (IC_SLV_DATA_NACK_ONLY)—Offset 84h" on page 3890	00000000h
88–8Bh	4	"DMA Control Register (IC_DMA_CR)—Offset 88h" on page 3891	00000000h
8C–8Fh	4	"DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch" on page 3892	00000000h
90–93h	4	"I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h" on page 3892	00000000h
94–97h	4	"I2C SDA Setup Register (IC_SDA_SETUP)—Offset 94h" on page 3893	00000064h
98–9Bh	4	"I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h" on page 3894	00000001h
9C–9Fh	4	"I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch" on page 3894	00000000h
A0–A3h	4	"IC_FS_SPKLEN—Offset A0h" on page 3895	00000005h
A4–A7h	4	"IC_HS_SPKLEN—Offset A4h" on page 3896	00000002h
F4–F7h	4	"Component Parameter Register 1 (IC_COMP_PARAM_1)—Offset F4h" on page 3897	00FFFFFFh
F8–FBh	4	"I2C Component Version Register (IC_COMP_VERSION)—Offset F8h" on page 3898	3131352Ah
FC–FFh	4	"I2C Component Type Register (IC_COMP_TYPE)—Offset FCh" on page 3898	44570140h
800–803h	4	"reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h" on page 3899	00000000h
804–807h	4	"Software Reset (RESETS)—Offset 804h" on page 3899	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 3900	55000000h
818–81Bh	4	"I2C_ACK_COUNT—Offset 818h" on page 3901	00000000h
820–823h	4	"I2C_TX_COMPLETE_INTR_STAT—Offset 820h" on page 3902	00000000h
824–827h	4	"reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h" on page 3903	00000000h



- DW_apb_i2c is NOT enabled (IC_ENABLE is set to 0)
- OR
- DW_apb_i2c is enabled (IC_ENABLE=1)
- AND
- DW_apb_i2c is NOT engaged in any Master (tx, rx) operation (IC_STATUS[5]=0)
- AND
- DW_apb_i2c is enabled to operate in Master mode (IC_CON[0]=1)
- AND
- There are NO entries in the TX FIFO (IC_STATUS[2]=1)

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_13_31						IC_10BITADDR_MASTER	SPECIAL	
						GC_OR_START		
						IC_TAR		
0	0	0	0	0	0	0	0	1

Bit Range	Default & Access	Field Name (ID): Description
31:13	0b RW	Reserved_13_31: Reserved.
12	1h RW	IC_10BITADDR_MASTER: This bit controls whether the DW_apb_i2c starts its transfers in 7-or 10-bit addressing mode when acting as a master. 0: 7-bit addressing 1: 10-bit addressing



Bit Range	Default & Access	Field Name (ID): Description
11	0h RW	SPECIAL: This bit indicates whether software performs a General Call or START BYTE command. 0 = ignore bit 10 GC_OR_START and use IC_TAR normally 1 = perform special I2C command as specified in GC_OR_START bit
10	0h RW	GC_OR_START: If bit 11 (SPECIAL) is set to 1, then this bit indicates whether a General Call(0) or START(1) byte command is to be performed by the DW_apb_i2c.
9:0	55h RW	IC_TAR: This is the target address for any master transaction. When transmitting a General Call, these bits are ignored. To generate a START BYTE, the CPU needs to write only once into these bits.

26.7.3 I2C Slave Address Register (IC_SAR)—Offset 8h

The IC SAR Address Register holds the slave address when the I2C is operating as a slave.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000055h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
Reserved_10_31							IC_SAR	

Bit Range	Default & Access	Field Name (ID): Description
31:10	0b RW	Reserved_10_31: Reserved.
9:0	55h RW	IC_SAR: The IC_SAR holds the slave address when the I2C is operating as a slave. For 7-bit addressing, only IC_SAR[6:0] is used. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.7.4 I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch

Note: It is not necessary to perform any write to this register if DW_apb_i2c is enabled as an I2C slave only.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h



Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_3_31								IC_HS_MAR

Bit Range	Default & Access	Field Name (ID): Description
31:3	0b RW	Reserved_3_31: Reserved.
2:0	1h RW	IC_HS_MAR: This bit field holds the value of the I2C HS mode master code. HS-mode master codes are reserved 8-bit codes (00001xxx) that are not used for slave addressing or other purposes. Each master has its unique master code; up to eight highspeed mode masters can be present on the same I2C bus system. Valid values are from 0 to 7. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.7.5 I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h

This is the register written to by the CPU when filling the TX FIFO, and read from by the CPU when retrieving bytes from RX FIFO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 10h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_11_31						RESTART	STOP	CMD
								DAT

Bit Range	Default & Access	Field Name (ID): Description
31:11	0b RW	Reserved_11_31: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
10	0h RW	RESTART: This bit controls whether a RESTART is issued before the byte is sent or received. This bit is available only if IC_EMPTYFIFO_HOLD_MASTER_EN is configured to 1. 1 If IC_RESTART_EN is 1, a RESTART is issued before the data is sent/received (according to the value of CMD), regardless of whether or not the transfer direction is changing from the previous command; if IC_RESTART_EN is 0, a STOP followed by a START is issued instead. 0 If IC_RESTART_EN is 1, a RESTART is issued only if the transfer direction is changing from the previous command; if IC_RESTART_EN is 0, a STOP followed by a START is issued instead.
9	0h RW	STOP: This bit determines whether STOP is generated after a data byte is sent or received.
8	0h RW	CMD: This bit controls whether a read or a write is performed. This bit does not control the direction when the DW_apb_i2c acts as a slave. It only controls the direction when it acts as a master. 1 = Read 0 = Write
7:0	0h RW	DAT: This register contains the data to be transmitted or received on the I2C bus. If you are writing to this register and want to perform a read, bits 7:0 (DAT) are ignored by the DW_apb_i2c. When you read this register, however, these bits return the value of data received on the DW_apb_i2c interface.

26.7.6 Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h

This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock high-period count for standard speed.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 14h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000190h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	1	0
Reserved_16_31				IC_SS_SCL_HCNT				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	190h RW	Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 18h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 000001D6h

31	28	24	20	16	12	8	4	0							
0	0	0	0	0	0	0	1	1	1	0	1	0	1	1	0
Reserved_16_31								IC_SS_SCL_LCNT							

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	01d6h RW	Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.7.8 Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch

This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock high-period count for fast speed. It is used in high-speed mode to send the Master Code and START BYTE or General CALL.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 0000003Ch

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IC_FS_SCL_HCNT				



26.7.12 I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch

Access Method

Offset: [BAR] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

31	28			24				20				16				12				8				4				0															
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0											
Reserved_12_31																																R_GEN_CALL	R_START_DET	R_STOP_DET	R_ACTIVITY	R_RX_DONE	R_TX_ABORT	R_RD_REQ	R_TX_EMPTY	R_TX_OVER	R_RX_FULL	R_RX_OVER	R_RX_UNDER

Intel Atom® Processor E3800 Product Family
Datasheet
3875



Bit Range	Default & Access	Field Name (ID): Description
8	0h RO	R_ACTIVITY: This bit captures DW_apb_i2c activity and stays set until it is cleared. There are four ways to clear it: Disabling the DW_apb_i2c, Reading the IC_CLR_ACTIVITY register, Reading the IC_CLR_INTR register, System reset
7	0h RO	R_RX_DONE: When the DW_apb_i2c is acting as a slave-transmitter, this bit is set to 1 if the master does not acknowledge a transmitted byte. This occurs on the last byte of the transmission, indicating that the transmission is done.
6	0h RO	R_TX_ABRT: This bit indicates whether DW_apb_i2c, as an I2C transmitter, is unable to complete the intended actions on the contents of the transmit FIFO.
5	0h RO	R_RD_REQ: This bit is set to 1 when DW_apb_i2c is acting as a slave and another I2C master is attempting to read data from DW_apb_i2c.
4	0h RO	R_TX_EMPTY: This bit is set to 1 when the transmit buffer is at or below the threshold value set in the IC_TX_TL register.
3	0h RO	R_TX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH, and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
2	0h RO	R_RX_FULL: Set when the receive buffer reaches or goes above the RX_TL threshold in the IC_RX_TL register.
1	0h RO	R_RX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
0	0h RO	R_RX_UNDER: Set if the processor attempts to read the receive buffer when it is empty by reading from the IC_DATA_CMD register.

26.7.13 I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h

These bits mask their corresponding interrupt status bits. This register is active low.

- 0 masks the interrupt
- 1 unmask the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 000008FFh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_12_31						M_GEN_CALL	M_START_DET	M_STOP_DET
						M_ACTIVITY	M_RX_DONE	M_TX_ABRT
						M_RD_REQ	M_TX_EMPTY	M_TX_OVER
						M_RX_FULL	M_RX_OVER	M_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.





Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Receive FIFO Threshold Level (RX_TL): The valid range is 0-255, with the additional restriction that hardware does not allow this value to be set to a value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.

26.7.16 I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							TX_TL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Transmit FIFO Threshold Level (TX_TL): Controls the level of entries (or below) that trigger the TX_EMPTY interrupt (bit 4 in IC_RAW_INTR_STAT register). The valid range is 0-255, with the additional restriction that it may not be set to value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.

26.7.17 Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_INTR: Read this register to clear the combined interrupt, all individual interrupts, and the IC_TX_ABRT_SOURCE register. This bit does not clear hardware clearable interrupts but software clearable interrupts.

26.7.18 Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_UNDER: Read this register to clear the RX_UNDER interrupt (bit 0) of the IC_RAW_INTR_STAT register.

26.7.19 Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
				Reserved_1_31					CLR_RD_REQ

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RD_REQ: Read this register to clear the RD_REQ interrupt (bit 5) of the IC_RAW_INTR_STAT register.

26.7.22 Clear TX_ABORT Interrupt Register (IC_CLR_TX_ABORT)—Offset 54h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_ABORT

26.7.23 Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h



Offset: [BAR] + 60h

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_STOP_DET: Read this register to clear the STOP_DET interrupt (bit 9) of the IC_RAW_INTR_STAT register.

Access Method

Offset: [BAR] + 64h

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_START_DET: Read this register to clear the START_DET interrupt (bit 10) of the IC_RAW_INTR_STAT register.

Access Method



26.7.30 I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h

This register contains the number of valid data entries in the transmit FIFO buffer. It is cleared whenever:

- The I2C is disabled
- There is a transmit abort -- that is, TX_ABRT bit is set in the IC_RAW_INTR_STAT register
- The slave bulk transmit mode is aborted

The register increments whenever data is placed into the transmit FIFO and decrements when data is taken from the transmit FIFO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_9_31							TXFLR	

Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Transmit FIFO Level (TXFLR): Contains the number of valid data entries in the transmit FIFO.

26.7.31 I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h

This register contains the number of valid data entries in the receive FIFO buffer. The register is cleared by the following methods:

- The I2C is disabled
- Whenever there is a transmit abort caused by any of the events tracked in IC_TX_ABRT_SOURCE

The register increments whenever data is placed into the receive FIFO and decrements when data is taken from the receive FIFO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 78h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h



This register controls the amount of hold time on the SDA signal after a negative edge of SCL in both master and slave mode, in units of `ic_clk` period. The value programmed must be greater than the minimum hold time in each mode for the value to be implemented: one cycle in master mode, seven cycles in slave mode. Writes to this register succeed only when `IC_ENABLE=0`. The programmed SDA hold time cannot exceed at any time the duration of the low part of `scl`. Therefore the programmed value cannot be larger than `N_SCL_LOW-2`, where `N_SCL_LOW` is the duration of the low part of the `scl` period measured in `ic_clk` cycles.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 7Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IC_SDA_HOLD				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved
15:0	1h RW	IC_SDA_HOLD: Sets the required SDA hold time in units of ic_clk period.



26.7.33 I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h

This register has 16 bits that indicate the source of the TX_ABRT bit. Except for Bit 9, this register is cleared whenever the IC_CLR_TX_ABRT register or the IC_CLR_INTR register is read. To clear Bit 9, the source of the ABRT_SBYTE_NORSTRT must be fixed first; RESTART must be enabled (IC_CON[5]=1), the SPECIAL bit must be cleared (IC_TAR[11]), or the GC_OR_START bit must be cleared (IC_TAR[10]). Once the source of the ABRT_SBYTE_NORSTRT is fixed, then this bit can be cleared in the same manner as other bits in this register. If the source of the ABRT_SBYTE_NORSTRT is not fixed before attempting to clear this bit, Bit 9 clears for one cycle and is then re-asserted.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																																			
0				0				0				0				0				0				0				0				0																																																			
TX_FLUSH_CNT								Reserved_17_23								ABRT_USER_ABRT				ABRT_SLVRD_INTX				ABRT_SLV_ARBLOST				ABRT_SLVFLUSH_TXFIFO				ARB_LOST				ABRT_MASTER_DIS				ABRT_10B_RD_NORSTRT				ABRT_SBYTE_NORSTRT				ABRT_HS_NORSTRT				ABRT_SBYTE_ACKDET				ABRT_HS_ACKDET				ABRT_GCALL_READ				ABRT_GCALL_NOACK				ABRT_TXDATA_NOACK				ABRT_10ADDR2_NOACK				ABRT_10ADDR1_NOACK				ABRT_7B_ADDR_NOACK			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RO	TX_FLUSH_CNT: This field preserves the TXFLR value prior to the last TX_ABRT event. It is enabled when fix_ctrl_1680 = 1. It is cleared whenever I2C is disabled.
23:17	0b RW	Reserved_17_23: Reserved
16	0h RO	ABRT_USER_ABRT: This is a master-mode only bit. Master has detected the user initiated transfer abort (IC_ENABLE[1]). It is enabled only when fix_ctrl_1680 = 1
15	0h RO	ABRT_SLVRD_INTX: 1 = When the processor side responds to a slave mode request for data to be transmitted to a remote master and user writes a 1 in CMD (bit 8) of IC_DATA_CMD register.
14	0h RO	ABRT_SLV_ARBLOST: 1 = Slave lost the bus while transmitting data to a remote master. IC_TX_ABRT_SOURCE[12] is set at the same time.
13	0h RO	ABRT_SLVFLUSH_TXFIFO: 1 = Slave has received a read command and some data exists in the TX FIFO so the slave issues a TX_ABRT interrupt to flush old data in TX FIFO.
12	0h RO	ARB_LOST: 1 = Master has lost arbitration, or if IC_TX_ABRT_SOURCE[14] is also set, then the slave transmitter has lost arbitration.
11	0h RO	ABRT_MASTER_DIS: 1 = User tries to initiate a Master operation with the Master mode disabled.



Bit Range	Default & Access	Field Name (ID): Description
10	0h RO	ABRT_10B_RD_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the master sends a read command in 10-bit addressing mode.
9	0h RO	ABRT_SBYTE_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to send a START Byte.
8	0h RO	ABRT_HS_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to use the master to transfer data in High Speed mode.
7	0h RO	ABRT_SBYTE_ACKDET: 1 = Master has sent a START Byte and the START Byte was acknowledged (wrong behavior).
6	0h RO	ABRT_HS_ACKDET: 1 = Master is in High Speed mode and the High Speed Master code was acknowledged (wrong behavior).
5	0h RO	ABRT_GCALL_READ: 1 = DW_apb_i2c in master mode sent a General Call but the user programmed the byte following the General Call to be a read from the bus (IC_DATA_CMD[9] is set to 1).
4	0h RO	ABRT_GCALL_NOACK: 1 = DW_apb_i2c in master mode sent a General Call and no slave on the bus acknowledged the General Call.
3	0h RO	ABRT_TXDATA_NOACK: 1 = This is a master-mode only bit. Master has received an acknowledgement for the address, but when it sent data byte(s) following the address, it did not receive an acknowledge from the remote slave(s).
2	0h RO	ABRT_10ADDR2_NOACK: 1 = Master is in 10-bit address mode and the second address byte of the 10-bit address was not acknowledged by any slave.
1	0h RO	ABRT_10ADDR1_NOACK: 1 = Master is in 10-bit address mode and the first 10-bit address byte was not acknowledged by any slave.
0	0h RO	ABRT_7B_ADDR_NOACK: 1 = Master is in 7-bit addressing mode and the address sent was not acknowledged by any slave.

26.7.34 Generate Slave Data NACK Register (IC_SLV_DATA_NACK_ONLY)—Offset 84h

The register is used to generate a NACK for the data part of a transfer when DW_apb_i2c is acting as a slave-receiver. A write can occur on this register if either of the following conditions are met.

- DW_apb_i2c is disabled (IC_ENABLE[0] = 0)
- Slave part is inactive (IC_STATUS[6] = 0)

NOTE = The IC_STATUS[6] is a register read-back location for the internal slv_activity signal; the user should poll this before writing the ic_slv_data_nack_only bit.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 84h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h



26.7.39 I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h

The register controls whether DW_apb_i2c responds with an ACK or NACK when it receives an I2C General Call address.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_1_31								ACK_GEN_CALL

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	1h RW	ACK General Call (ACK_GEN_CALL): When set to 1, DW_apb_i2c responds with a ACK (by asserting ic_data_oe) when it receives a General Call. When set to 0, the DW_apb_i2c does not generate General Call interrupts.

26.7.40 I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch

The register is used to report the DW_apb_i2c hardware status when the IC_ENABLE register is set from 1 to 0, that is, when DW_apb_i2c is disabled.

- If IC_ENABLE has been set to 1, bits 2:1 are forced to 0, and bit 0 is forced to 1.
- If IC_ENABLE has been set to 0, bits 2:1 will only be valid as soon as bit 0 is read as 0.

NOTE = When IC_ENABLE has been written with 0, a delay occurs for bit 0 to be read as 0 because disabling the DW_apb_i2c depends on I2C bus activities.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + A4h

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	2h RW	IC_HS_SPKLEN: This register must be set before any I2C bus transaction can take place to ensure stable operation. This register sets the duration, measured in ic_clk cycles, of the longest spike in the SCL or SDA lines that are filtered out by the spike suppression logic; for more information, refer to Spike Suppression on page 52. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect. The minimum valid value is 1; hardware prevents values less than this being written, and if attempted results in 2 being set.



26.7.44 I2C Component Version Register (IC_COMP_VERSION)—Offset F8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 3131352Ah

31	28	24	20	16	12	8	4	0
0	0	1	1	0	0	0	1	0
0	0	0	1	0	0	1	1	0
0	0	1	1	0	0	0	1	0
0	1	0	1	0	0	1	0	1
0	0	1	0	1	0	1	0	1
0	1	0	1	0	1	0	1	0
0	0	1	0	1	0	1	0	1

IC_COMP_VERSION

Bit Range	Default & Access	Field Name (ID): Description
31:0	3131352Ah RO	IC_COMP_VERSION: Specific values for this register are described in the Releases Table in the AMBA 2 release notes.

26.7.45 I2C Component Type Register (IC_COMP_TYPE)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 44570140h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	1	0	0	0
0	1	0	0	0	1	0	0	0
0	1	0	1	0	1	1	1	0
0	0	0	0	0	0	0	0	1
0	0	0	0	1	0	1	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

IC_COMP_TYPE

Bit Range	Default & Access	Field Name (ID): Description
31:0	44570140h RO	IC_COMP_TYPE: Designware Component Type number = 0x44_57_01_40. This assigned unique hex value is constant and is derived from the two ASCII letters DW followed by a 16-bit unsigned number.



26.7.46 reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h

indicate if the i2c uses 133MHz or 100MHz

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 800h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								hs_source_clock

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RO	hs_source_clock: Reflects the value configured in hs_source_clock_sel in GPIODEF0. 0 -100MHz (LPT-LP compatible) 1 -133MHz (high-speed operation compatible)

26.7.47 Software Reset (RESETS)—Offset 804h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 804h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved								reset_apb reset_func

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	Reserved (reserved): Reserved.
1	0h RW	reset_apb: reset the apb domain
0	0h RW	reset_func: reset the func clock domain

26.7.48 General Purpose Register (GENERAL)—Offset 808h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 808h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 55000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	sda_mux_sel: Reserved.
30	1h RW	sda_signal_state: Reserved.
29	0h RW	scl_mux_sel: Reserved.
28	1h RW	scl_signal_state: Reserved.
27	0h RO	sda_rd_pre_drive: Reserved.
26	1h RO	sda_rd_post_drive: Reserved.
25	0h RO	scl_rd_pre_drive: Reserved.
24	1h RO	scl_rd_post_drive: Reserved.
23:10	0h RO	Reserved: Reserved
9	0h RW	i2c_fix_ctrl_1680: Control port to enable fix 9000521680,Generation of STOP condition without data transfer
8	0h RW	i2c_fix_ctrl_0770: Control port to enable fix 9000530770,Stop generating DMA requests during Tx FIFO flush conditions
7	0h RW	i2c_fix_ctrl_1699: Control port to enable fix 9000481699,Rx data is pushed to Rx FIFO only after Tx FIFO is not-empty
6	0h RW	i2c_374798_fix_disable: chicken bit for Fix for NACK bug (HSD # 374798)
5	0h RW	i2c_374609_fix_disable: chicken bit for Fix for NACK bug (HSD # 374609)



Bit Range	Default & Access	Field Name (ID): Description
4	0h RW	i2c_tx_lastbyte_flag: SW indicates it's last byte for TX transaction (HSD # 374798)
3:0	0h RW	reserved: reserved

26.7.49 I2C_ACK_COUNT—Offset 818h

TX transaction counter

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 818h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0				i2c_tx_ack_count_clr_overflow	RSVD1	i2c_tx_count_overflow	i2c_tx_ack_count	

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RO	RSVD0: Reserved
19	0h RW	i2c_tx_ack_count_clr_overflow: SW clear of TX transaction (byte) counter
18:17	0b RO	RSVD1: Reserved
16	0h RO	i2c_tx_count_overflow: indicate there was count overflow
15:0	0h RO	i2c_tx_ack_count: indicate TX transaction count for SW to read



Access Method

Offset: [BAR] + 820h

BAR Reference: [B:0, D:24, F:1] + 10h

	31	28	24	20	16	12	8	4	0	
	0	0	0	0	0	0	0	0	0	
										i2c_tx_complete_interrupt_mask
										i2c_tx_completion_interrupt

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RO	Reserved: Reserved
1	0h RW	i2c_tx_complete_interrupt_mask: Mask TX transaction has finished interrupt
0	0h RO	i2c_tx_completion_interrupt: indicate TX transaction has finished



26.7.51 reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h

indicate TX transaction has finished write 1 to clear the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 824h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								i2c_tx_complete_intr_clr

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	i2c_tx_complete_intr_clr: indicate TX transaction has finished write 1 to clear the interrupt



Bit Range	Default & Access	Field Name (ID): Description
7:3	00h RO	Reserved5: Reserved.
2	0h RW	Bus Master Enable (BME): If this bit is 0, Bridge does not generate any new upstream transaction on IOSF as a master.
1	0h RW	Memory Space Enable (MSE): This bit controls Bridge's response to downstream Memory accesses. When set, accesses to memory space of the device is enabled.
0	0h RO	Reserved6: Reserved.

26.8.3 Revision ID and Class Code (REVCLASSCODE)—Offset 8h

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:2] + 8h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Class Code (CLASS_CODES): The Class Code register is read-only and used to identify the generic function of the device and, in some cases, a specific register level programming interface. The register is broken into three byte size fields. The upper byte (at offset 0Bh) is a base class code which broadly classifies the type of function the device performs. The middle byte (at offset 0Ah) is a sub-class code which identifies more specifically the function of the device. The lower byte (at offset 09h) identifies a specific register-level programming interface (if any) so that device independent software can interact with the device. This register is tied to a strap at the top level.
7:0	00h RO	Revision ID (RID): Revision ID identifies the revision of particular AHB device. This is tied to a strap at the top level.



26.8.4 Cache Line Latency Header and BIST (CLLATHEADERBIST)—Offset Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:2] + Ch

Default: 00800000h

31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				MULFNDEV	HEADERTYPE			
					LATTIMER			
					CACHELINE_SIZE			

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.



26.8.6 Base Address Register 1 (BAR1)—Offset 14h







26.8.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:2] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MAX_LAT				MIN_GNT				INTLINE
				Reserved0				INTPIN

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a Single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to tell software which interrupt line the interrupt pin is connected to.

26.8.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:2] + 80h

Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
PMESUPPORT				Reserved0				POWER_CAP
				VERSION				NXTCAP



Access Method

Offset: [B:0, D:24, F:2] + 84h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0				PMESTATUS	Reserved1		PMEENABLE	Reserved2
								NO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit (bit 8 in this register).
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
3	1h RO	No_Soft_Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state - Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for Downstream decode on fabric ports.

26.8.13 Manufacturer ID (MANID)—Offset F8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:2] + F8h

Default: 00000000h

Diagram illustrating the structure of the 32-bit MANID field. The field is divided into eight 4-bit segments, each labeled with a hexadecimal value: 31, 28, 24, 20, 16, 12, 8, and 4. The segments are represented by boxes containing the values 0, 0, 0, 0. The label 'MANID' is positioned vertically below the first segment.

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



26.9 SIO I²C 1 PCI Configuration Registers

Table 267. Summary of I²C 1 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"I2C Control Register (IC_CON)—Offset 0h" on page 3916	0000007Fh
4–7h	4	"I2C Target Address Register (IC_TAR)—Offset 4h" on page 3917	00001055h
8–Bh	4	"I2C Slave Address Register (IC_SAR)—Offset 8h" on page 3918	00000055h
C–Fh	4	"I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch" on page 3918	00000001h
10–13h	4	"I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h" on page 3919	00000000h
14–17h	4	"Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h" on page 3920	00000190h
18–1Bh	4	"Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h" on page 3920	000001D6h
1C–1Fh	4	"Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch" on page 3921	0000003Ch
20–23h	4	"Fast Speed I2C Clock SCL Low Count Register (IC_FS_SCL_LCNT)—Offset 20h" on page 3922	00000082h
24–27h	4	"High Speed I2C Clock SCL High Count Register (IC_HS_SCL_HCNT)—Offset 24h" on page 3922	0000000Ch
28–2Bh	4	"High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h" on page 3923	00000020h
2C–2Fh	4	"I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch" on page 3924	00000000h
30–33h	4	"I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h" on page 3925	000008FFh
34–37h	4	"I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h" on page 3926	00000000h
38–3Bh	4	"I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h" on page 3927	00000010h
3C–3Fh	4	"I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch" on page 3928	00000010h
40–43h	4	"Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h" on page 3928	00000000h
44–47h	4	"Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h" on page 3929	00000000h
48–4Bh	4	"Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h" on page 3929	00000000h
4C–4Fh	4	"Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch" on page 3930	00000000h
50–53h	4	"Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h" on page 3930	00000000h
54–57h	4	"Clear TX_ABORT Interrupt Register (IC_CLR_TX_ABORT)—Offset 54h" on page 3931	00000000h
58–5Bh	4	"Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h" on page 3931	00000000h
5C–5Fh	4	"Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch" on page 3932	00000000h
60–63h	4	"Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h" on page 3932	00000000h




Table 267. Summary of I²C 1 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
64–67h	4	"Clear START_DET Interrupt Register (IC_CLR_START_DET)—Offset 64h" on page 3933	00000000h
68–6Bh	4	"Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h" on page 3933	00000000h
6C–6Fh	4	"I2C Enable Register (IC_ENABLE)—Offset 6Ch" on page 3934	00000000h
70–73h	4	"I2C Status Register (IC_STATUS)—Offset 70h" on page 3934	00000006h
74–77h	4	"I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h" on page 3935	00000000h
78–7Bh	4	"I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h" on page 3936	00000000h
7C–7Fh	4	"I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch" on page 3937	00000001h
80–83h	4	"I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h" on page 3937	00000000h
84–87h	4	"Generate Slave Data NACK Register (IC_SLV_DATA_NACK_ONLY)—Offset 84h" on page 3939	00000000h
88–8Bh	4	"DMA Control Register (IC_DMA_CR)—Offset 88h" on page 3940	00000000h
8C–8Fh	4	"DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch" on page 3940	00000000h
90–93h	4	"I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h" on page 3941	00000000h
94–97h	4	"I2C SDA Setup Register (IC_SDA_SETUP)—Offset 94h" on page 3942	00000064h
98–9Bh	4	"I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h" on page 3943	00000001h
9C–9Fh	4	"I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch" on page 3943	00000000h
A0–A3h	4	"IC_FS_SPKLEN—Offset A0h" on page 3944	00000005h
A4–A7h	4	"IC_HS_SPKLEN—Offset A4h" on page 3945	00000002h
F4–F7h	4	"Component Parameter Register 1 (IC_COMP_PARAM_1)—Offset F4h" on page 3946	00FFFFFFh
F8–FBh	4	"I2C Component Version Register (IC_COMP_VERSION)—Offset F8h" on page 3947	3131352Ah
FC–FFh	4	"I2C Component Type Register (IC_COMP_TYPE)—Offset FCh" on page 3947	44570140h
800–803h	4	"reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h" on page 3948	00000000h
804–807h	4	"Software Reset (RESETS)—Offset 804h" on page 3948	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 3949	55000000h
818–81Bh	4	"I2C_ACK_COUNT—Offset 818h" on page 3950	00000000h
820–823h	4	"I2C_TX_COMPLETE_INTR_STAT—Offset 820h" on page 3951	00000000h
824–827h	4	"reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h" on page 3952	00000000h

26.9.2 I2C Target Address Register (IC_TAR)—Offset 4h



26.9.3 I2C Slave Address Register (IC_SAR)—Offset 8h

The IC SAR Address Register holds the slave address when the I2C is operating as a slave.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000055h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	1	1
Reserved_10_31							IC_SAR	

Bit Range	Default & Access	Field Name (ID): Description
31:10	0b RW	Reserved_10_31: Reserved.
9:0	55h RW	IC_SAR: The IC_SAR holds the slave address when the I2C is operating as a slave. For 7-bit addressing, only IC_SAR[6:0] is used. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.9.4 I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch

Note: It is not necessary to perform any write to this register if DW_apb_i2c is enabled as an I2C slave only.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + Ch


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
Reserved_3_31							IC_HS_MAR	

26.9.5 I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h



Bit Range	Default & Access	Field Name (ID): Description
7:0	0h RW	DAT: This register contains the data to be transmitted or received on the I2C bus. If you are writing to this register and want to perform a read, bits 7:0 (DAT) are ignored by the DW_apb_i2c. When you read this register, however, these bits return the value of data received on the DW_apb_i2c interface.

26.9.6 Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h

This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock high-period count for standard speed.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 14h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000190h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IC_SS_SCL_HCNT				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	190h RW	Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.9.7 Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h

This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock low period count for standard speed.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 18h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 000001D6h



26.9.8 Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch

Access Method

Offset: [BAR] + 1Ch


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 0000003Ch

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IC_FS_SCL_HCNT				

Intel Atom[®] Processor E3800 Product Family
Datasheet
3921



26.9.11 High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h

Access Method

BAR Reference: [B:0, D:24, F:2] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				TC_HS_SCL_LCNT				



Access Method

Offset: [BAR] + 2Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0			
Reserved_12_31																												R_GEN_CALL							
																												R_START_DET							
																												R_STOP_DET							
																												R_ACTIVITY							
																												R_RX_DONE							
																												R_TX_ABORT							
																												R_RD_REQ							
																												R_TX_EMPTY							
																												R_TX_OVER							
																												R_RX_FULL							
R_RX_OVER																																			
R_RX_UNDER																																			

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	0h RO	R_GEN_CALL: Set only when a General Call address is received and acknowledged. It stays set until it is cleared either by disabling DW_apb_i2c or when the CPU reads bit 0 of the IC_CLR_GEN_CALL register.
10	0h RO	R_START_DET: Indicates whether a START or RESTART condition has occurred on the I2C interface, regardless of whether DW_apb_i2c is operating in slave or master mode.
9	0h RO	R_STOP_DET: Indicates whether a STOP condition has occurred on the I2C interface, regardless of whether DW_apb_i2c is operating in slave or master mode.
8	0h RO	R_ACTIVITY: This bit captures DW_apb_i2c activity and stays set until it is cleared. There are four ways to clear it: Disabling the DW_apb_i2c, Reading the IC_CLR_ACTIVITY register, Reading the IC_CLR_INTR register, System reset
7	0h RO	R_RX_DONE: When the DW_apb_i2c is acting as a slave-transmitter, this bit is set to 1 if the master does not acknowledge a transmitted byte. This occurs on the last byte of the transmission, indicating that the transmission is done.
6	0h RO	R_TX_ABRT: This bit indicates whether DW_apb_i2c, as an I2C transmitter, is unable to complete the intended actions on the contents of the transmit FIFO.
5	0h RO	R_RD_REQ: This bit is set to 1 when DW_apb_i2c is acting as a slave and another I2C master is attempting to read data from DW_apb_i2c.



Bit Range	Default & Access	Field Name (ID): Description
4	0h RO	R_TX_EMPTY: This bit is set to 1 when the transmit buffer is at or below the threshold value set in the IC_TX_TL register.
3	0h RO	R_TX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH, and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
2	0h RO	R_RX_FULL: Set when the receive buffer reaches or goes above the RX_TL threshold in the IC_RX_TL register.
1	0h RO	R_RX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
0	0h RO	R_RX_UNDER: Set if the processor attempts to read the receive buffer when it is empty by reading from the IC_DATA_CMD register.

26.9.13 I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h

These bits mask their corresponding interrupt status bits. This register is active low.

- 0 masks the interrupt
- 1 unmask the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 30h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 000008FFh

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	1	1	1	1	1	1	1				
Reserved_12_31																M_GEN_CALL	M_START_DET	M_STOP_DET	M_ACTIVITY	M_RX_DONE	M_TX_ABORT	M_RD_REQ	M_TX_EMPTY	M_TX_OVER	M_RX_FULL	M_RX_OVER	M_RX_UNDER								

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	1h RW	M_GEN_CALL: See description of M_TX_EMPTY bit field.
10	0h RW	M_START_DET: See description of M_TX_EMPTY bit field.
9	0h RW	M_STOP_DET: See description of M_TX_EMPTY bit field.
8	0h RW	M_ACTIVITY: See description of M_TX_EMPTY bit field.



Bit Range	Default & Access	Field Name (ID): Description
7	1h RW	M_RX_DONE: See description of M_TX_EMPTY bit field.
6	1h RW	M_TX_ABRT: See description of M_TX_EMPTY bit field.
5	1h RW	M_RD_REQ: See description of M_TX_EMPTY bit field.
4	1h RW	M_TX_EMPTY: These bits mask their corresponding interrupt status bits in the IC_INTR_STAT register. Reset value: 12h8ff
3	1h RW	M_TX_OVER: See description of M_TX_EMPTY bit field.
2	1h RW	M_RX_FULL: See description of M_TX_EMPTY bit field.
1	1h RW	M_RX_OVER: See description of M_TX_EMPTY bit field.
0	1h RW	M_RX_UNDER: See description of M_TX_EMPTY bit field.

26.9.14 I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h

Unlike the IC_INTR_STAT register, these bits are not masked -- so they always show the true status of the DW_apb_i2c.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_12_31						GEN_CALL	START_DET	STOP_DET
						ACTIVITY	RX_DONE	TX_ABRT
						RD_REQ	TX_EMPTY	TX_OVER
						RX_FULL	RX_OVER	RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	0h RO	GEN_CALL: Same as in reg_IC_INTR_STAT.
10	0h RO	START_DET: Same as in reg_IC_INTR_STAT.



Bit Range	Default & Access	Field Name (ID): Description
9	0h RO	STOP_DET: Same as in reg_IC_INTR_STAT.
8	0h RO	ACTIVITY: Same as in reg_IC_INTR_STAT.
7	0h RO	RX_DONE: Same as in reg_IC_INTR_STAT.
6	0h RO	TX_ABRT: Same as in reg_IC_INTR_STAT.
5	0h RO	RD_REQ: Same as in reg_IC_INTR_STAT.
4	0h RO	TX_EMPTY: Same as in reg_IC_INTR_STAT.
3	0h RO	TX_OVER: Same as in reg_IC_INTR_STAT.
2	0h RO	RX_FULL: Same as in reg_IC_INTR_STAT.
1	0h RO	RX_OVER: Same as in reg_IC_INTR_STAT.
0	0h RO	RX_UNDER: Same as in reg_IC_INTR_STAT.

26.9.15 I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0				
0	0	0	0	0	0	0	0	1	0	0	0	0
Reserved_8_31								RX_TL				

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Receive FIFO Threshold Level (RX_TL): The valid range is 0-255, with the additional restriction that hardware does not allow this value to be set to a value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.



26.9.16 I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
Reserved_8_31							TX_TL	0

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Transmit FIFO Threshold Level (TX_TL): Controls the level of entries (or below) that trigger the TX_EMPTY interrupt (bit 4 in IC_RAW_INTR_STAT register). The valid range is 0-255, with the additional restriction that it may not be set to value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.

26.9.17 Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_INTR

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_INTR: Read this register to clear the combined interrupt, all individual interrupts, and the IC_TX_ABRT_SOURCE register. This bit does not clear hardware clearable interrupts but software clearable interrupts.



26.9.18 Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_UNDER: Read this register to clear the RX_UNDER interrupt (bit 0) of the IC_RAW_INTR_STAT register.

26.9.19 Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_OVER: Read this register to clear the RX_OVER interrupt (bit 1) of the IC_RAW_INTR_STAT register.



26.9.20 Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_OVER: Read this register to clear the TX_OVER interrupt (bit 3) of the IC_RAW_INTR_STAT register.

26.9.21 Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RD_REQ

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RD_REQ: Read this register to clear the RD_REQ interrupt (bit 5) of the IC_RAW_INTR_STAT register.



26.9.22 Clear TX_ABRT Interrupt Register (IC_CLR_TX_ABRT)—Offset 54h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_ABRT

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_ABRT: Read this register to clear the TX_ABRT interrupt (bit 6) of the IC_RAW_INTR_STAT register, and the IC_TX_ABRT_SOURCE register. This also releases the TX FIFO from the flushed/reset state, allowing more writes to the TX FIFO.

26.9.23 Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_DONE

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_DONE: Read this register to clear the RX_DONE interrupt (bit 7) of the IC_RAW_INTR_STAT register.



26.9.24 Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 5Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_ACTIVITY

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_ACTIVITY: Reading this register clears the ACTIVITY interrupt if the I2C is not active anymore. If the I2C module is still active on the bus, the ACTIVITY interrupt bit continues to be set. It is automatically cleared by hardware if the module is disabled and if there is no further activity on the bus. The value read from this register to get status of the ACTIVITY interrupt (bit 8) of the IC_RAW_INTR_STAT register.

26.9.25 Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_STOP_DET

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_9_31						TXFLR		

Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Transmit FIFO Level (TXFLR): Contains the number of valid data entries in the transmit FIFO.

26.9.31 I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h

This register contains the number of valid data entries in the receive FIFO buffer. The register is cleared by the following methods:

- The I2C is disabled
- Whenever there is a transmit abort caused by any of the events tracked in IC_TX_ABRT_SOURCE

The register increments whenever data is placed into the receive FIFO and decrements when data is taken from the receive FIFO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 78h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_9_31						RXFLR		



Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Receive FIFO Level (RXFLR): Contains the number of valid data entries in the receive FIFO.

26.9.32 I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch

This register controls the amount of hold time on the SDA signal after a negative edge of SCL in both master and slave mode, in units of ic_clk period. The value programmed must be greater than the minimum hold time in each mode for the value to be implemented one cycle in master mode, seven cycles in slave mode. Writes to this register succeed only when IC_ENABLE=0. The programmed SDA hold time cannot exceed at any time the duration of the low part of scl. Therefore the programmed value cannot be larger than N_SCL_LOW-2, where N_SCL_LOW is the duration of the low part of the scl period measured in ic_clk cycles.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 7Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_16_31								IC_SDA_HOLD

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved
15:0	1h RW	IC_SDA_HOLD: Sets the required SDA hold time in units of ic_clk period.

26.9.33 I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h

This register has 16 bits that indicate the source of the TX_ABRT bit. Except for Bit 9, this register is cleared whenever the IC_CLR_TX_ABRT register or the IC_CLR_INTR register is read. To clear Bit 9, the source of the ABRT_SBYTE_NORSTRT must be fixed first; RESTART must be enabled (IC_CON[5]=1), the SPECIAL bit must be cleared (IC_TAR[11]), or the GC_OR_START bit must be cleared (IC_TAR[10]). Once the source of the ABRT_SBYTE_NORSTRT is fixed, then this bit can be cleared in the same



manner as other bits in this register. If the source of the ABRT_SBYTE_NORSTRT is not fixed before attempting to clear this bit, Bit 9 clears for one cycle and is then re-asserted.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																																			
0				0				0				0				0				0				0				0				0																																																			
TX_FLUSH_CNT								Reserved_17_23								ABRT_USER_ABRT				ABRT_SLVRD_INTX				ABRT_SLV_ARBLOST				ABRT_SLVFLUSH_TXFIFO				ARB_LOST				ABRT_MASTER_DIS				ABRT_10B_RD_NORSTRT				ABRT_SBYTE_NORSTRT				ABRT_HS_NORSTRT				ABRT_SBYTE_ACKDET				ABRT_HS_ACKDET				ABRT_GCALL_READ				ABRT_GCALL_NOACK				ABRT_TXDATA_NOACK				ABRT_10ADDR2_NOACK				ABRT_10ADDR1_NOACK				ABRT_7B_ADDR_NOACK			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RO	TX_FLUSH_CNT: This field preserves the TXFLR value prior to the last TX_ABRT event. It is enabled when fix_ctrl_1680 = 1. It is cleared whenever I2C is disabled.
23:17	0b RW	Reserved_17_23: Reserved
16	0h RO	ABRT_USER_ABRT: This is a master-mode only bit. Master has detected the user initiated transfer abort (IC_ENABLE[1]). It is enabled only when fix_ctrl_1680 = 1
15	0h RO	ABRT_SLVRD_INTX: 1 = When the processor side responds to a slave mode request for data to be transmitted to a remote master and user writes a 1 in CMD (bit 8) of IC_DATA_CMD register.
14	0h RO	ABRT_SLV_ARBLOST: 1 = Slave lost the bus while transmitting data to a remote master. IC_TX_ABRT_SOURCE[12] is set at the same time.
13	0h RO	ABRT_SLVFLUSH_TXFIFO: 1 = Slave has received a read command and some data exists in the TX FIFO so the slave issues a TX_ABRT interrupt to flush old data in TX FIFO.
12	0h RO	ARB_LOST: 1 = Master has lost arbitration, or if IC_TX_ABRT_SOURCE[14] is also set, then the slave transmitter has lost arbitration.
11	0h RO	ABRT_MASTER_DIS: 1 = User tries to initiate a Master operation with the Master mode disabled.
10	0h RO	ABRT_10B_RD_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the master sends a read command in 10-bit addressing mode.
9	0h RO	ABRT_SBYTE_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to send a START Byte.
8	0h RO	ABRT_HS_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to use the master to transfer data in High Speed mode.
7	0h RO	ABRT_SBYTE_ACKDET: 1 = Master has sent a START Byte and the START Byte was acknowledged (wrong behavior).

26.9.35 DMA Control Register (IC DMA CR)—Offset 88h

Bit Range	Default & Access	Field Name (ID): Description
0	0h RW	Generate NACK (NACK): This NACK generation only occurs when DW_apb_i2c is a slavereceiver. If this register is set to a value of 1, it can only generate a NACK after a data byte is received; hence, the data transfer is aborted and the data received is not pushed to the receive buffer. When the register is set to a value of 0, it generates NACK/ACK, depending on normal criteria. 1 = generate NACK after data byte received 0 = generate NACK/ACK normally

26.9.35 DMA Control Register (IC DMA CR)—Offset 88h

This register is only valid when DW_apb_i2c is configured with a set of DMA Controller interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist and writing to the registers address has no effect and reading from this register address will return zero. The register is used to enable the DMA Controller interface operation. There is a separate bit for transmit and receive. This can be programmed regardless of the state of IC_ENABLE.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	TDMAE	RDMAE
Reserved_2_31										

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	Reserved_2_31: Reserved.
1	0h RW	Transmit DMA Enable (TDMAE): This bit enables/disables the transmit FIFO DMA channel. 0 = Transmit DMA disabled 1 = Transmit DMA enabled
0	0h RW	Receive DMA Enable (RDMAE): This bit enables/disables the receive FIFO DMA channel. 0 = Receive DMA disabled 1 = Receive DMA enabled

26.9.36 DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch

This register is only valid when the DW_apb_i2c is configured with a set of DMA interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMATDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	0h RW	Transmit Data Level (DMATDL): This bit field controls the level at which a DMA request is made by the transmit logic. It is equal to the watermark level; that is, the dma_tx_req signal is generated when the number of valid data entries in the transmit FIFO is equal to or below this field value, and TDMAE = 1.

26.9.37 I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h

This register is only valid when DW_apb_i2c is configured with a set of DMA interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 90h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMARDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.



26.9.39 I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h

The register controls whether DW_apb_i2c responds with an ACK or NACK when it receives an I2C General Call address.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_1_31								ACK_GEN_CALL

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	1h RW	ACK General Call (ACK_GEN_CALL): When set to 1, DW_apb_i2c responds with a ACK (by asserting ic_data_oe) when it receives a General Call. When set to 0, the DW_apb_i2c does not generate General Call interrupts.

26.9.40 I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch

The register is used to report the DW_apb_i2c hardware status when the IC_ENABLE register is set from 1 to 0, that is, when DW_apb_i2c is disabled.

- If IC_ENABLE has been set to 1, bits 2:1 are forced to 0, and bit 0 is forced to 1.
- If IC_ENABLE has been set to 0, bits 2:1 will only be valid as soon as bit 0 is read as 0.

NOTE = When IC_ENABLE has been written with 0, a delay occurs for bit 0 to be read as 0 because disabling the DW_apb_i2c depends on I2C bus activities.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h





Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	5h RW	IC_FS_SPKLEN: This register must be set before any I2C bus transaction can take place to ensure stable operation. This register sets the duration, measured in ic_clk cycles, of the longest spike in the SCL or SDA lines that are filtered out by the spike suppression logic; for more information, refer to Spike Suppression on page 52. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect. The minimum valid value is 1; hardware prevents values less than this being written, and if attempted results in 2 being set.

26.9.42 IC HS SPKLEN—Offset A4h

This register is used to store the duration, measured in ic_clk cycles, of the longest spike that is filtered out by the spike suppression logic when the component is operating in HS mode. The relevant I2C requirement is tSP (Table 6) as detailed in the I2C Bus Specification. This register must be programmed with a minimum value of 1

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + A4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	2h RW	IC_HS_SPKLEN: This register must be set before any I2C bus transaction can take place to ensure stable operation. This register sets the duration, measured in ic_clk cycles, of the longest spike in the SCL or SDA lines that are filtered out by the spike suppression logic; for more information, refer to Spike Suppression on page 52. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect. The minimum valid value is 1; hardware prevents values less than this being written, and if attempted results in 2 being set.



26.9.44 I2C Component Version Register (IC_COMP_VERSION)—Offset F8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 3131352Ah

31	28	24	20	16	12	8	4	0											
0	0	1	1	0	0	0	1	0	0	1	1	0	1	0	0	1	0	1	0
IC_COMP_VERSION																			

Bit Range	Default & Access	Field Name (ID): Description
31:0	3131352Ah RO	IC_COMP_VERSION: Specific values for this register are described in the Releases Table in the AMBA 2 release notes.

26.9.45 I2C Component Type Register (IC_COMP_TYPE)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 44570140h

31	28	24	20	16	12	8	4	0									
0	1	0	0	0	1	0	0	0	0	1	0	1	1	0	0	0	0
IC_COMP_TYPE																	

Bit Range	Default & Access	Field Name (ID): Description
31:0	44570140h RO	IC_COMP_TYPE: Designware Component Type number = 0x44_57_01_40. This assigned unique hex value is constant and is derived from the two ASCII letters DW followed by a 16-bit unsigned number.



26.9.46 reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h

indicate if the i2c uses 133MHz or 100MHz

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 800h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								hs_source_clock

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RO	hs_source_clock: Reflects the value configured in hs_source_clock_sel in GPIODEF0. 0 -100MHz (LPT-LP compatible) 1 -133MHz (high-speed operation compatible)

26.9.47 Software Reset (RESETS)—Offset 804h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 804h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved								reset_apb reset_func

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	Reserved (reserved): Reserved.
1	0h RW	reset_apb: reset the apb domain
0	0h RW	reset_func: reset the func clock domain

26.9.48 General Purpose Register (GENERAL)—Offset 808h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 808h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 55000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	sda_mux_sel: Reserved.
30	1h RW	sda_signal_state: Reserved.
29	0h RW	scl_mux_sel: Reserved.
28	1h RW	scl_signal_state: Reserved.
27	0h RO	sda_rd_pre_drive: Reserved.
26	1h RO	sda_rd_post_drive: Reserved.
25	0h RO	scl_rd_pre_drive: Reserved.
24	1h RO	scl_rd_post_drive: Reserved.
23:10	0h RO	Reserved: Reserved
9	0h RW	i2c_fix_ctrl_1680: Control port to enable fix 9000521680,Generation of STOP condition without data transfer
8	0h RW	i2c_fix_ctrl_0770: Control port to enable fix 9000530770,Stop generating DMA requests during Tx FIFO flush conditions
7	0h RW	i2c_fix_ctrl_1699: Control port to enable fix 9000481699,Rx data is pushed to Rx FIFO only after Tx FIFO is not-empty
6	0h RW	i2c_374798_fix_disable: chicken bit for Fix for NACK bug (HSD # 374798)
5	0h RW	i2c_374609_fix_disable: chicken bit for Fix for NACK bug (HSD # 374609)

TX transaction counter

Offset: [BAR] + 818h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RO	RSVD0: Reserved
19	0h RW	i2c_tx_ack_count_clr_overflow: SW clear of TX transaction (byte) counter
18:17	0b RO	RSVD1: Reserved
16	0h RO	i2c_tx_count_overflow: indicate there was count overflow
15:0	0h RO	i2c_tx_ack_count: indicate TX transaction count for SW to read



26.9.50 I2C_TX_COMPLETE_INTR_STAT—Offset 820h

TX transaction has finished interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 820h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved								i2c_tx_complete_interrupt_mask
								i2c_tx_completion_interrupt

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RO	Reserved: Reserved
1	0h RW	i2c_tx_complete_interrupt_mask: Mask TX transaction has finished interrupt
0	0h RO	i2c_tx_completion_interrupt: indicate TX transaction has finished



26.9.51 reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h

indicate TX transaction has finished write 1 to clear the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 824h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:2] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								i2c_tx_complete_intr_clr

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	i2c_tx_complete_intr_clr: indicate TX transaction has finished write 1 to clear the interrupt



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0	MULFNDEV	HEADERTYPE	LATTIMER	CACHELINE_SIZE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

26.10.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR	SIZEINDICATOR	PREFETCHABLE	TYPE	MESSAGE_SPACE				

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.



Bit Range	Default & Access	Field Name (ID): Description
2:1	0h RO	Type (TYPE): 00 indicates BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE): 0. Indicates this BAR is present in the memory space.

26.10.6 Base Address Register 1 (BAR1)—Offset 14h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:3] + 14h

Default: 00000000h

31				28				24				20				16				12				8				4				0											
0				0				0				0				0				0				0				0				0				0							
BASEADDR1																SIZEINDICATOR1																PREFETCHABLE1				TYPE1				MESSAGE_SPACE1			

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address Register 1 (BASEADDR1): BAR1 of the LP10 device.
11:4	00h RO	SIZEINDICATOR1: Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE1): Indicates that this BAR is not.
2:1	0h RO	Type (TYPE1): 00 Indicates BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE1): 0. Indicates this BAR is present in the memory space.



26.10.7 Subsystem Vendor and Subsystem ID (SUBSYSTEMID)—Offset 2Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:3] + 2Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SUBSYSTEMID					SUBSYSTEMVENDORID			

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW/O	Subsystem ID (SUBSYSTEMID): This register should be implemented for any function that could be instantiated more than once in a given system. The SID register, in combination with the Subsystem Vendor ID register, make it possible for the operating environment to distinguish one audio subsystem from the other. This register is a Read Write Once type register.
15:0	0000h RW/O	Subsystem Vendor ID (SUBSYSTEMVENDORID): This register should be implemented for any function that could be instantiated more than once in a given system. The SVID register, in combination with the Subsystem ID register, enables the operating environment to distinguish one subsystem from the other. This register is a Read Write Once register.



26.10.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.
7:0	00h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. If PM capability is disabled then this register has 00h.



26.10.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:3] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
MAX_LAT	MIN_GNT	Reserved0	INTPIN	INTLINE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a Single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to tell software which interrupt line the interrupt pin is connected to.

26.10.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:3] + 80h

Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0
PMESUPPORT	Reserved0	VERSION	NXTCAP	POWER_CAP				

26.10.13 Manufacturer ID (MANID)—Offset F8h

Bit Range	Default & Access	Field Name (ID): Description
3	1h RO	No_Soft_Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state - Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for Downstream decode on fabric ports.

26.10.13 Manufacturer ID (MANID)—Offset F8h

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:3] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
MANID								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



26.11 SIO I²C 2 Memory Mapped I/O Registers

Table 269. Summary of I²C 2 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"I2C Control Register (IC_CON)—Offset 0h" on page 3965	0000007Fh
4–7h	4	"I2C Target Address Register (IC_TAR)—Offset 4h" on page 3966	00001055h
8–Bh	4	"I2C Slave Address Register (IC_SAR)—Offset 8h" on page 3967	00000055h
C–Fh	4	"I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch" on page 3967	00000001h
10–13h	4	"I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h" on page 3968	00000000h
14–17h	4	"Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h" on page 3969	00000190h
18–1Bh	4	"Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h" on page 3969	000001D6h
1C–1Fh	4	"Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch" on page 3970	0000003Ch
20–23h	4	"Fast Speed I2C Clock SCL Low Count Register (IC_FS_SCL_LCNT)—Offset 20h" on page 3971	00000082h
24–27h	4	"High Speed I2C Clock SCL High Count Register (IC_HS_SCL_HCNT)—Offset 24h" on page 3971	0000000Ch
28–2Bh	4	"High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h" on page 3972	00000020h
2C–2Fh	4	"I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch" on page 3973	00000000h
30–33h	4	"I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h" on page 3974	000008FFh
34–37h	4	"I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h" on page 3975	00000000h
38–3Bh	4	"I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h" on page 3976	00000010h
3C–3Fh	4	"I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch" on page 3977	00000010h
40–43h	4	"Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h" on page 3977	00000000h
44–47h	4	"Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h" on page 3978	00000000h
48–4Bh	4	"Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h" on page 3978	00000000h
4C–4Fh	4	"Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch" on page 3979	00000000h
50–53h	4	"Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h" on page 3979	00000000h
54–57h	4	"Clear TX_ABORT Interrupt Register (IC_CLR_TX_ABORT)—Offset 54h" on page 3980	00000000h
58–5Bh	4	"Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h" on page 3980	00000000h
5C–5Fh	4	"Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch" on page 3981	00000000h
60–63h	4	"Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h" on page 3981	00000000h



Table 269. Summary of I²C 2 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
64–67h	4	"Clear START_DET Interrupt Register (IC_CLR_START_DET)—Offset 64h" on page 3982	00000000h
68–6Bh	4	"Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h" on page 3982	00000000h
6C–6Fh	4	"I2C Enable Register (IC_ENABLE)—Offset 6Ch" on page 3983	00000000h
70–73h	4	"I2C Status Register (IC_STATUS)—Offset 70h" on page 3983	00000006h
74–77h	4	"I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h" on page 3984	00000000h
78–7Bh	4	"I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h" on page 3985	00000000h
7C–7Fh	4	"I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch" on page 3986	00000001h
80–83h	4	"I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h" on page 3986	00000000h
84–87h	4	"Generate Slave Data NACK Register (IC_SLV_DATA_NACK_ONLY)—Offset 84h" on page 3988	00000000h
88–8Bh	4	"DMA Control Register (IC_DMA_CR)—Offset 88h" on page 3989	00000000h
8C–8Fh	4	"DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch" on page 3989	00000000h
90–93h	4	"I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h" on page 3990	00000000h
94–97h	4	"I2C SDA Setup Register (IC_SDA_SETUP)—Offset 94h" on page 3991	00000064h
98–9Bh	4	"I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h" on page 3992	00000001h
9C–9Fh	4	"I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch" on page 3992	00000000h
A0–A3h	4	"IC_FS_SPKLEN—Offset A0h" on page 3993	00000005h
A4–A7h	4	"IC_HS_SPKLEN—Offset A4h" on page 3994	00000002h
F4–F7h	4	"Component Parameter Register 1 (IC_COMP_PARAM_1)—Offset F4h" on page 3995	00FFFFFFh
F8–FBh	4	"I2C Component Version Register (IC_COMP_VERSION)—Offset F8h" on page 3996	3131352Ah
FC–FFh	4	"I2C Component Type Register (IC_COMP_TYPE)—Offset FCh" on page 3996	44570140h
800–803h	4	"reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h" on page 3997	00000000h
804–807h	4	"Software Reset (RESETS)—Offset 804h" on page 3997	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 3998	55000000h
818–81Bh	4	"I2C_ACK_COUNT—Offset 818h" on page 3999	00000000h
820–823h	4	"I2C_TX_COMPLETE_INTR_STAT—Offset 820h" on page 4000	00000000h
824–827h	4	"reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h" on page 4001	00000000h



26.11.2 I2C Target Address Register (IC_TAR)—Offset 4h

Writes to IC_TAR succeed when one of the following conditions are true:

- DW_apb_i2c is NOT enabled (IC_ENABLE is set to 0)
-
- OR
-
- DW_apb_i2c is enabled (IC_ENABLE=1)
- AND
- DW_apb_i2c is NOT engaged in any Master (tx, rx) operation (IC_STATUS[5]=0)
- AND
- DW_apb_i2c is enabled to operate in Master mode (IC_CON[0]=1)
- AND
- There are NO entries in the TX FIFO (IC_STATUS[2]=1)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)


BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00001055h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_13_31					IC_10BITADDR_MASTER	SPECIAL		
						GC_OR_START		
						IC_TAR		

Bit Range	Default & Access	Field Name (ID): Description
31:13	0b RW	Reserved_13_31: Reserved.
12	1h RW	IC_10BITADDR_MASTER: This bit controls whether the DW_apb_i2c starts its transfers in 7-or 10-bit addressing mode when acting as a master.
11	0h RW	SPECIAL: This bit indicates whether software performs a General Call or START BYTE command. • 0 = ignore bit 10 GC_OR_START and use IC_TAR normally • 1 = perform special I2C command as specified in GC_OR_START bit
10	0h RW	GC_OR_START: If bit 11 (SPECIAL) is set to 1, then this bit indicates whether a General Call(0) or START(1) byte command is to be performed by the DW_apb_i2c.
9:0	55h RW	IC_TAR: This is the target address for any master transaction. When transmitting a General Call, these bits are ignored. To generate a START BYTE, the CPU needs to write only once into these bits.





This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock high-period count for standard speed.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
Reserved_16_31				IC_SS_SCL_HCNT				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	190h RW	Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock low period count for standard speed.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 000001D6h



This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock high-period count for fast speed. It is used in high-speed mode to send the Master Code and START BYTE or General CALL.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 0000003Ch

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31					IC_FS_SCL_HCNT			

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	003ch RW	Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.



This register must be set before any I2C bus transaction can take place, to ensure proper I/O timing. This register sets the SCL clock low-period count for fast speed. It is used in high-speed mode to send the Master Code and START BYTE or General CALL. The SCL High time depends on the loading of the bus. For 100pF loading, the SCL High time is 60ns; for 400pF loading, the SCL High time is 120ns. This register goes away and becomes read-only if `IC_MAX_SPEED_MODE` != high. This register can be written only when the I2C interface is disabled, which corresponds to the `IC_ENABLE` register being set to 0. Writes at other times have no effect. The minimum valid value is 8; hardware prevents values less than this being written, and, if attempted, results in 8 being set. For designs with `APB_DATA_WIDTH` == 8 the order of programming is important to ensure the correct operation of the `DW_apb_i2c`. The lower byte must be programmed first. Then the upper byte can be programmed.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 28h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000020h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IIC_HS_SCL_LCNT				



Bit Range	Default & Access	Field Name (ID): Description
4	0h RO	R_TX_EMPTY: This bit is set to 1 when the transmit buffer is at or below the threshold value set in the IC_TX_TL register.
3	0h RO	R_TX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH, and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
2	0h RO	R_RX_FULL: Set when the receive buffer reaches or goes above the RX_TL threshold in the IC_RX_TL register.
1	0h RO	R_RX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
0	0h RO	R_RX_UNDER: Set if the processor attempts to read the receive buffer when it is empty by reading from the IC_DATA_CMD register.

26.11.13 I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h

These bits mask their corresponding interrupt status bits. This register is active low.

- 0 masks the interrupt
- 1 unmasks the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 000008FFh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_12_31						M_GEN_CALL	M_START_DET	M_STOP_DET
						M_ACTIVITY	M_RX_DONE	M_TX_ABORT
						M_RD_REQ	M_TX_EMPTY	M_TX_OVER
						M_RX_FULL	M_RX_OVER	M_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	1h RW	M_GEN_CALL: See description of M_TX_EMPTY bit field.
10	0h RW	M_START_DET: See description of M_TX_EMPTY bit field.
9	0h RW	M_STOP_DET: See description of M_TX_EMPTY bit field.
8	0h RW	M_ACTIVITY: See description of M_TX_EMPTY bit field.

26.11.14 I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)– Offset 34h



Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)
BAR Reference: [B:0, D:24, F:3] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							RX_TL	

October 2018
Document Number: 538136, Rev. 4.3



26.11.16 I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
Reserved_8_31							TX_TL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Transmit FIFO Threshold Level (TX_TL): Controls the level of entries (or below) that trigger the TX_EMPTY interrupt (bit 4 in IC_RAW_INTR_STAT register). The valid range is 0-255, with the additional restriction that it may not be set to value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.

26.11.17 Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_INTR

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_INTR: Read this register to clear the combined interrupt, all individual interrupts, and the IC_TX_ABRT_SOURCE register. This bit does not clear hardware clearable interrupts but software clearable interrupts.



26.11.18 Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_UNDER: Read this register to clear the RX_UNDER interrupt (bit 0) of the IC_RAW_INTR_STAT register.

26.11.19 Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_OVER: Read this register to clear the RX_OVER interrupt (bit 1) of the IC_RAW_INTR_STAT register.



26.11.20 Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_OVER: Read this register to clear the TX_OVER interrupt (bit 3) of the IC_RAW_INTR_STAT register.

26.11.21 Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RD_REQ

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RD_REQ: Read this register to clear the RD_REQ interrupt (bit 5) of the IC_RAW_INTR_STAT register.



26.11.22 Clear TX_ABRT Interrupt Register (IC_CLR_TX_ABRT)—Offset 54h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_ABRT

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_ABRT: Read this register to clear the TX_ABRT interrupt (bit 6) of the IC_RAW_INTR_STAT register, and the IC_TX_ABRT_SOURCE register. This also releases the TX FIFO from the flushed/reset state, allowing more writes to the TX FIFO.

26.11.23 Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_DONE

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_DONE: Read this register to clear the RX_DONE interrupt (bit 7) of the IC_RAW_INTR_STAT register.



26.11.24 Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 5Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_ACTIVITY

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_ACTIVITY: Reading this register clears the ACTIVITY interrupt if the I2C is not active anymore. If the I2C module is still active on the bus, the ACTIVITY interrupt bit continues to be set. It is automatically cleared by hardware if the module is disabled and if there is no further activity on the bus. The value read from this register to get status of the ACTIVITY interrupt (bit 8) of the IC_RAW_INTR_STAT register.

26.11.25 Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_STOP_DET

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.



26.11.27 Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h



Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_GEN_CALL: Read this register to clear the GEN_CALL interrupt (bit 11) of IC_RAW_INTR_STAT register.

26.11.28 I2C Enable Register (IC_ENABLE)—Offset 6Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 6Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	Reserved_2_31: Reserved
1	0h WO	ABORT: Software can abort the I2C transfer by setting this bit. This bit can be set only when ENABLE = 1 and fix_ctrl_1680 = 1. The HW will clear the ABORT bit once the STOP condition has been sent.
0	0h RW	ENABLE: Controls whether the DW_apb_i2c is enabled. 0 = Disables DW_apb_i2c (TX and RX FIFOs are held in an erased state) 1 = Enables DW_apb_i2c

26.11.29 I2C Status Register (IC_STATUS)—Offset 70h

This is a read-only register used to indicate the current transfer status and FIFO status. The status register may be read at any time. None of the bits in this register request an interrupt. The following occurs when the I2C is disabled by writing 0 in bit 0 of the IC_ENABLE register:

- Bits 1 and 2 are set to 1
- Bits 3 and 4 are set to 0

When the master or slave state machines goes to idle and `ic_en=0`:

- Bits 5 and 6 are set to 0

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 70h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000006h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_7_31							SLV_ACTIVITY	
							MST_ACTIVITY	
							RFF	
							RFNE	
							TFE	
							TFNF	
							ACTIVITY	

Bit Range	Default & Access	Field Name (ID): Description
31:7	0b RW	Reserved_7_31: Reserved.
6	0h RO	Slave FSM Activity Status (SLV_ACTIVITY): When the Slave Finite State Machine (FSM) is not in the IDLE state, this bit is set.
5	0h RO	Master FSM Activity Status (MST_ACTIVITY): When the Master Finite State Machine (FSM) is not in the IDLE state, this bit is set.
4	0h RO	Receive FIFO Completely Full (RFF): When the receive FIFO is completely full, this bit is set. When the receive FIFO contains one or more empty location, this bit is cleared.
3	0h RO	Receive FIFO Not Empty (RFNE): This bit is set when the receive FIFO contains one or more entries; it is cleared when the receive FIFO is empty.
2	1h RO	Transmit FIFO Completely Empty (TFE): When the transmit FIFO is completely empty, this bit is set. When it contains one or more valid entries, this bit is cleared. This bit field does not request an interrupt.
1	1h RO	Transmit FIFO Not Full (TFNF): Set when the transmit FIFO contains one or more empty locations, and is cleared when the FIFO is full.
0	0h RO	ACTIVITY: I2C Activity Status

26.11.30 I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h

This register contains the number of valid data entries in the transmit FIFO buffer. It is cleared whenever:

- The I2C is disabled
- There is a transmit abort -- that is, TX_ABRT bit is set in the IC_RAW_INTR_STAT register
- The slave bulk transmit mode is aborted

The register increments whenever data is placed into the transmit FIFO and decrements when data is taken from the transmit FIFO.

Access Method



Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Receive FIFO Level (RXFLR): Contains the number of valid data entries in the receive FIFO.

26.11.32 I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch

This register controls the amount of hold time on the SDA signal after a negative edge of SCL in both master and slave mode, in units of ic_clk period. The value programmed must be greater than the minimum hold time in each mode for the value to be implemented one cycle in master mode, seven cycles in slave mode. Writes to this register succeed only when IC_ENABLE=0. The programmed SDA hold time cannot exceed at any time the duration of the low part of scl. Therefore the programmed value cannot be larger than N_SCL_LOW-2, where N_SCL_LOW is the duration of the low part of the scl period measured in ic_clk cycles.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 7Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_16_31								IC_SDA_HOLD

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved
15:0	1h RW	IC_SDA_HOLD: Sets the required SDA hold time in units of ic_clk period.

26.11.33 I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h

This register has 16 bits that indicate the source of the TX_ABRT bit. Except for Bit 9, this register is cleared whenever the IC_CLR_TX_ABRT register or the IC_CLR_INTR register is read. To clear Bit 9, the source of the ABRT_SBYTE_NORSTRT must be fixed first; RESTART must be enabled (IC_CON[5]=1), the SPECIAL bit must be cleared (IC_TAR[11]), or the GC_OR_START bit must be cleared (IC_TAR[10]). Once the source of the ABRT_SBYTE_NORSTRT is fixed, then this bit can be cleared in the same



manner as other bits in this register. If the source of the ABRT_SBYTE_NORSTRT is not fixed before attempting to clear this bit, Bit 9 clears for one cycle and is then re-asserted.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
0				0				0				0				0				0				0				0				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
TX_FLUSH_CNT								Reserved_17_23								ABRT_USER_ABORT				ABRT_SLVRD_INTX				ABRT_SLV_ARBLOST				ABRT_SLVFLUSH_TXFIFO				ARB_LOST				ABRT_MASTER_DIS				ABRT_10B_RD_NORSTRT				ABRT_SBYTE_NORSTRT				ABRT_HS_NORSTRT				ABRT_SBYTE_ACKDET				ABRT_HS_ACKDET				ABRT_GCALL_READ				ABRT_GCALL_NOACK				ABRT_TXDATA_NOACK				ABRT_10ADDR2_NOACK				ABRT_10ADDR1_NOACK				ABRT_7B_ADDR_NOACK																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RO	TX_FLUSH_CNT: This field preserves the TXFLR value prior to the last TX_ABORT event. It is enabled when fix_ctrl_1680 = 1. It is cleared whenever I2C is disabled.
23:17	0b RW	Reserved_17_23: Reserved
16	0h RO	ABRT_USER_ABORT: This is a master-mode only bit. Master has detected the user initiated transfer abort (IC_ENABLE[1]). It is enabled only when fix_ctrl_1680 = 1
15	0h RO	ABRT_SLVRD_INTX: 1 = When the processor side responds to a slave mode request for data to be transmitted to a remote master and user writes a 1 in CMD (bit 8) of IC_DATA_CMD register.
14	0h RO	ABRT_SLV_ARBLOST: 1 = Slave lost the bus while transmitting data to a remote master. IC_TX_ABORT_SOURCE[12] is set at the same time.
13	0h RO	ABRT_SLVFLUSH_TXFIFO: 1 = Slave has received a read command and some data exists in the TX FIFO so the slave issues a TX_ABORT interrupt to flush old data in TX FIFO.
12	0h RO	ARB_LOST: 1 = Master has lost arbitration, or if IC_TX_ABORT_SOURCE[14] is also set, then the slave transmitter has lost arbitration.
11	0h RO	ABRT_MASTER_DIS: 1 = User tries to initiate a Master operation with the Master mode disabled.
10	0h RO	ABRT_10B_RD_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the master sends a read command in 10-bit addressing mode.
9	0h RO	ABRT_SBYTE_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to send a START Byte.
8	0h RO	ABRT_HS_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to use the master to transfer data in High Speed mode.
7	0h RO	ABRT_SBYTE_ACKDET: 1 = Master has sent a START Byte and the START Byte was acknowledged (wrong behavior).



- DW_apb_i2c is disabled (IC_ENABLE[0] = 0)
- Slave part is inactive (IC_STATUS[6] = 0)

Access Method

Offset: [BAR] + 84h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								NACK



Bit Range	Default & Access	Field Name (ID): Description
0	0h RW	Generate NACK (NACK): This NACK generation only occurs when DW_apb_i2c is a slavereceiver. If this register is set to a value of 1, it can only generate a NACK after a data byte is received; hence, the data transfer is aborted and the data received is not pushed to the receive buffer. When the register is set to a value of 0, it generates NACK/ACK, depending on normal criteria. 1 = generate NACK after data byte received 0 = generate NACK/ACK normally

26.11.35 DMA Control Register (IC DMA CR)—Offset 88h

This register is only valid when DW_apb_i2c is configured with a set of DMA Controller interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist and writing to the registers address has no effect and reading from this register address will return zero. The register is used to enable the DMA Controller interface operation. There is a separate bit for transmit and receive. This can be programmed regardless of the state of IC_ENABLE.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	Reserved_2_31: Reserved.
1	0h RW	Transmit DMA Enable (TDMAE): This bit enables/disables the transmit FIFO DMA channel. 0 = Transmit DMA disabled 1 = Transmit DMA enabled
0	0h RW	Receive DMA Enable (RDMAE): This bit enables/disables the receive FIFO DMA channel. 0 = Receive DMA disabled 1 = Receive DMA enabled

26.11.36 DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch

This register is only valid when the DW_apb_i2c is configured with a set of DMA interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMATDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	0h RW	Transmit Data Level (DMATDL): This bit field controls the level at which a DMA request is made by the transmit logic. It is equal to the watermark level; that is, the dma_tx_req signal is generated when the number of valid data entries in the transmit FIFO is equal to or below this field value, and TDMAE = 1.

26.11.37 I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h

This register is only valid when DW_apb_i2c is configured with a set of DMA interface signals(IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 90h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMARDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.



This register controls the amount of time delay (in terms of number of ic_clk clock periods) introduced in the rising edge of SCL -- relative to SDA changing -- by holding SCL low when DW_apb_i2c services a read request while operating as a slave-transmitter. The relevant I2C requirement is tSU:DAT (note 4) as detailed in the I2C Bus Specification. This register must be programmed with a value equal to or greater than 2. **NOTE:** The length of setup time is calculated using $[(IC_SDA_SETUP - 1) * (ic_clk_period)]$, so if the user requires 10 ic_clk periods of setup time, they should program a value of 11. The IC_SDA_SETUP register is only used by the DW_apb_i2c when operating as a slave transmitter.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000064h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	64h RW	SDA Setup (SDA_SETUP): It is recommended that if the required delay is 1000ns, then for an ic_clk frequency of 10 MHz, IC_SDA_SETUP should be programmed to a value of 11.



26.11.39 I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h

The register controls whether DW_apb_i2c responds with an ACK or NACK when it receives an I2C General Call address.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_1_31								ACK_GEN_CALL

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	1h RW	ACK General Call (ACK_GEN_CALL): When set to 1, DW_apb_i2c responds with a ACK (by asserting ic_data_oe) when it receives a General Call. When set to 0, the DW_apb_i2c does not generate General Call interrupts.

26.11.40 I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch

The register is used to report the DW_apb_i2c hardware status when the IC_ENABLE register is set from 1 to 0, that is, when DW_apb_i2c is disabled.

- If IC_ENABLE has been set to 1, bits 2:1 are forced to 0, and bit 0 is forced to 1.
- If IC_ENABLE has been set to 0, bits 2:1 will only be valid as soon as bit 0 is read as 0.

NOTE = When IC_ENABLE has been written with 0, a delay occurs for bit 0 to be read as 0 because disabling the DW_apb_i2c depends on I2C bus activities.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

26.11.41 IC FS SPKLEN—Offset A0h



Access Method

Offset: [BAR] + A4h

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	2h RW	IC_HS_SPKLEN: This register must be set before any I2C bus transaction can take place to ensure stable operation. This register sets the duration, measured in ic_clk cycles, of the longest spike in the SCL or SDA lines that are filtered out by the spike suppression logic; for more information, refer to Spike Suppression on page 52. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect. The minimum valid value is 1; hardware prevents values less than this being written, and if attempted results in 2 being set.



26.11.44 I2C Component Version Register (IC_COMP_VERSION)—Offset F8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 3131352Ah

31	28	24	20	16	12	8	4	0
0	0	1	1	0	0	0	1	0
0	0	0	1	0	0	1	1	0
0	0	0	1	0	0	0	1	0
0	1	0	1	0	0	1	0	1
0	0	1	0	1	0	1	0	1
0	0	1	0	1	0	1	0	1
0	0	1	0	1	0	1	0	1

IC_COMP_VERSION

Bit Range	Default & Access	Field Name (ID): Description
31:0	3131352Ah RO	IC_COMP_VERSION: Specific values for this register are described in the Releases Table in the AMBA 2 release notes.

26.11.45 I2C Component Type Register (IC_COMP_TYPE)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 44570140h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	1	0	0	0
0	1	0	0	0	1	0	0	0
0	1	0	1	0	1	1	1	0
0	0	0	0	0	0	0	0	1
0	0	0	0	1	0	1	0	0
0	0	0	0	1	0	1	0	0
0	0	0	0	1	0	1	0	0

IC_COMP_TYPE

Bit Range	Default & Access	Field Name (ID): Description
31:0	44570140h RO	IC_COMP_TYPE: Designware Component Type number = 0x44_57_01_40. This assigned unique hex value is constant and is derived from the two ASCII letters DW followed by a 16-bit unsigned number.



26.11.46 reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h

indicate if the i2c uses 133MHz or 100MHz

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 800h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								hs_source_clock

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RO	hs_source_clock: Reflects the value configured in hs_source_clock_sel in GPIODEF0. 0 -100MHz (LPT-LP compatible) 1 -133MHz (high-speed operation compatible)

26.11.47 Software Reset (RESETS)—Offset 804h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 804h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved								reset_apb reset_func

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	Reserved (reserved): Reserved.
1	0h RW	reset_apb: reset the apb domain
0	0h RW	reset_func: reset the func clock domain



Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 55000000h

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	sda_mux_sel: Reserved.
30	1h RW	sda_signal_state: Reserved.
29	0h RW	scl_mux_sel: Reserved.
28	1h RW	scl_signal_state: Reserved.
27	0h RO	sda_rd_pre_drive: Reserved.
26	1h RO	sda_rd_post_drive: Reserved.
25	0h RO	scl_rd_pre_drive: Reserved.
24	1h RO	scl_rd_post_drive: Reserved.
23:10	0h RO	Reserved: Reserved
9	0h RW	i2c_fix_ctrl_1680: Control port to enable fix 9000521680,Generation of STOP condition without data transfer
8	0h RW	i2c_fix_ctrl_0770: Control port to enable fix 9000530770,Stop generating DMA requests during Tx FIFO flush conditions
7	0h RW	i2c_fix_ctrl_1699: Control port to enable fix 9000481699,Rx data is pushed to Rx FIFO only after Tx FIFO is not-empty
6	0h RW	i2c_374798_fix_disable: chicken bit for Fix for NACK bug (HSD # 374798)
5	0h RW	i2c_374609_fix_disable: chicken bit for Fix for NACK bug (HSD # 374609)



Bit Range	Default & Access	Field Name (ID): Description
4	0h RW	i2c_tx_lastbyte_flag: SW indicates it's last byte for TX transaction (HSD # 374798)
3:0	0h RW	reserved: reserved

26.11.49 I2C ACK COUNT—Offset 818h

TX transaction counter

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 818h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0				i2c_tx_ack_count_clr_overflow	RSVD1		i2c_tx_count_overflow	
							i2c_tx_ack_count	

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RO	RSVD0: Reserved
19	0h RW	i2c_tx_ack_count_clr_overflow: SW clear of TX transaction (byte) counter
18:17	0b RO	RSVD1: Reserved
16	0h RO	i2c_tx_count_overflow: indicate there was count overflow
15:0	0h RO	i2c_tx_ack_count: indicate TX transaction count for SW to read



26.11.50 I2C_TX_COMPLETE_INTR_STAT—Offset 820h

TX transaction has finished interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 820h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved								i2c_tx_complete_interrupt_mask
								i2c_tx_completion_interrupt

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RO	Reserved: Reserved
1	0h RW	i2c_tx_complete_interrupt_mask: Mask TX transaction has finished interrupt
0	0h RO	i2c_tx_completion_interrupt: indicate TX transaction has finished



26.11.51 reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h

indicate TX transaction has finished write 1 to clear the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 824h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								i2c_tx_complete_intr_clr

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	i2c_tx_complete_intr_clr: indicate TX transaction has finished write 1 to clear the interrupt

26.12.3 Revision ID and Class Code (REVCLASSCODE)—Offset 8h

Bit Range	Default & Access	Field Name (ID): Description
7:3	00h RO	Reserved5: Reserved.
2	0h RW	Bus Master Enable (BME): If this bit is 0, Bridge does not generate any new upstream transaction on IOSF as a master.
1	0h RW	Memory Space Enable (MSE): This bit controls Bridge's response to downstream Memory accesses. When set, accesses to memory space of the device is enabled.
0	0h RO	Reserved6: Reserved.

26.12.3 Revision ID and Class Code (REVCLASSCODE)—Offset 8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:4] + 8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Class Code (CLASS_CODES): The Class Code register is read-only and used to identify the generic function of the device and, in some cases, a specific register level programming interface. The register is broken into three byte size fields. The upper byte (at offset 0Bh) is a base class code which broadly classifies the type of function the device performs. The middle byte (at offset 0Ah) is a sub-class code which identifies more specifically the function of the device. The lower byte (at offset 09h) identifies a specific register-level programming interface (if any) so that device independent software can interact with the device. This register is tied to a strap at the top level.
7:0	00h RO	Revision ID (RID): Revision ID identifies the revision of particular AHB device. This is tied to a strap at the top level.

26.12.4 Cache Line Latency Header and BIST (CLLATHEADERBIST)—Offset Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:4] + Ch

Default: 00800000h



31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				MULFNDEV	HEADERTYPE			
					LATTIMER			
						CACHELINE_SIZE		

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

26.12.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR						SIZEINDICATOR	PREFETCHABLE	TYPE
								MESSAGE_SPACE

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.



Access Method

Offset: [B:0, D:24, F:4] + 14h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		
						PREFETCHABLE1		
						TYPE1		
						MESSAGE_SPACE1		

26.12.7 Subsystem Vendor and Subsystem ID (SUBSYSTEMID)—Offset 2Ch

Access Method

Offset: [B:0, D:24, F:4] + 2Ch

October 2018
Document Number: 538136, Rev. 4.3



26.12.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Type: PCI Configuration Register
(Size: 32 bits)

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSION_ROM_BASE								

October 2018
Document Number: 538136, Rev. 4.3



26.12.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:4] + 34h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.
7:0	00h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. If PM capability is disabled then this register has 00h.

26.12.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:4] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
MAX_LAT				MIN_GNT				INTLINE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a Single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to tell software which interrupt line the interrupt pin is connected to.



26.12.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:4] + 80h

Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
PMESUPPORT		Reserved0		VERSION		NXTCAP		POWER_CAP

Bit Range	Default & Access	Field Name (ID): Description
31:27	00h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. - bit(11) X XXX1b - PME# can be asserted from D0. - bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. - bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. - bit(14) X 1XXXb - PME# can be asserted from D3hot. - bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the strap strap_pme_support.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.



26.13 SIO I²C 3 Memory Mapped I/O Registers

Table 271. Summary of I²C 3 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"I2C Control Register (IC_CON)—Offset 0h" on page 4014	0000007Fh
4–7h	4	"I2C Target Address Register (IC_TAR)—Offset 4h" on page 4015	00001055h
8–Bh	4	"I2C Slave Address Register (IC_SAR)—Offset 8h" on page 4016	00000055h
C–Fh	4	"I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch" on page 4016	00000001h
10–13h	4	"I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h" on page 4017	00000000h
14–17h	4	"Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h" on page 4018	00000190h
18–1Bh	4	"Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h" on page 4018	000001D6h
1C–1Fh	4	"Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch" on page 4019	0000003Ch
20–23h	4	"Fast Speed I2C Clock SCL Low Count Register (IC_FS_SCL_LCNT)—Offset 20h" on page 4020	00000082h
24–27h	4	"High Speed I2C Clock SCL High Count Register (IC_HS_SCL_HCNT)—Offset 24h" on page 4020	0000000Ch
28–2Bh	4	"High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h" on page 4021	00000020h
2C–2Fh	4	"I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch" on page 4022	00000000h
30–33h	4	"I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h" on page 4023	000008FFh
34–37h	4	"I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h" on page 4024	00000000h
38–3Bh	4	"I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h" on page 4025	00000010h
3C–3Fh	4	"I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch" on page 4026	00000010h
40–43h	4	"Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h" on page 4026	00000000h
44–47h	4	"Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h" on page 4027	00000000h
48–4Bh	4	"Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h" on page 4027	00000000h
4C–4Fh	4	"Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch" on page 4028	00000000h
50–53h	4	"Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h" on page 4028	00000000h
54–57h	4	"Clear TX_ABORT Interrupt Register (IC_CLR_TX_ABORT)—Offset 54h" on page 4029	00000000h
58–5Bh	4	"Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h" on page 4029	00000000h
5C–5Fh	4	"Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch" on page 4030	00000000h
60–63h	4	"Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h" on page 4030	00000000h



Table 271. Summary of I²C 3 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
64–67h	4	"Clear START_DET Interrupt Register (IC_CLR_START_DET)—Offset 64h" on page 4031	00000000h
68–6Bh	4	"Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h" on page 4031	00000000h
6C–6Fh	4	"I2C Enable Register (IC_ENABLE)—Offset 6Ch" on page 4032	00000000h
70–73h	4	"I2C Status Register (IC_STATUS)—Offset 70h" on page 4032	00000006h
74–77h	4	"I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h" on page 4033	00000000h
78–7Bh	4	"I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h" on page 4034	00000000h
7C–7Fh	4	"I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch" on page 4035	00000001h
80–83h	4	"I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h" on page 4035	00000000h
84–87h	4	"Generate Slave Data NACK Register (IC_SLV_DATA_NACK_ONLY)—Offset 84h" on page 4037	00000000h
88–8Bh	4	"DMA Control Register (IC_DMA_CR)—Offset 88h" on page 4038	00000000h
8C–8Fh	4	"DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch" on page 4038	00000000h
90–93h	4	"I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h" on page 4039	00000000h
94–97h	4	"I2C SDA Setup Register (IC_SDA_SETUP)—Offset 94h" on page 4040	00000064h
98–9Bh	4	"I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h" on page 4040	00000001h
9C–9Fh	4	"I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch" on page 4041	00000000h
A0–A3h	4	"IC_FS_SPKLEN—Offset A0h" on page 4042	00000005h
A4–A7h	4	"IC_HS_SPKLEN—Offset A4h" on page 4043	00000002h
F4–F7h	4	"Component Parameter Register 1 (IC_COMP_PARAM_1)—Offset F4h" on page 4044	00FFFFFFh
F8–FBh	4	"I2C Component Version Register (IC_COMP_VERSION)—Offset F8h" on page 4045	3131352Ah
FC–FFh	4	"I2C Component Type Register (IC_COMP_TYPE)—Offset FCh" on page 4045	44570140h
800–803h	4	"reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h" on page 4046	00000000h
804–807h	4	"Software Reset (RESETS)—Offset 804h" on page 4046	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 4047	55000000h
818–81Bh	4	"I2C_ACK_COUNT—Offset 818h" on page 4048	00000000h
820–823h	4	"I2C_TX_COMPLETE_INTR_STAT—Offset 820h" on page 4049	00000000h
824–827h	4	"reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h" on page 4050	00000000h



26.13.3 I2C Slave Address Register (IC_SAR)—Offset 8h

The IC SAR Address Register holds the slave address when the I2C is operating as a slave.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000055h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	1	1
Reserved_10_31							IC_SAR	

Bit Range	Default & Access	Field Name (ID): Description
31:10	0b RW	Reserved_10_31: Reserved.
9:0	55h RW	IC_SAR: The IC_SAR holds the slave address when the I2C is operating as a slave. For 7-bit addressing, only IC_SAR[6:0] is used. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.13.4 I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch

Note: It is not necessary to perform any write to this register if DW_apb_i2c is enabled as an I2C slave only.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
Reserved_3_31							IC_HS_MAR	





This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock high-period count for standard speed.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 14h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000190h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
Reserved_16_31				IC_SS_SCL_HCNT				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	190h RW	Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.13.7 Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h

This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock low period count for standard speed.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 18h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 000001D6h



26.13.8 Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch

Access Method


Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IC_FS_SCL_HCNT				

Intel Atom® Processor E3800 Product Family
Datasheet
4019



26.13.11 High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h


Access Method

Offset: [BAR] + 28h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IC_HS_SCL_LCNT				

26.13.12 I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch



31				28				24				20				16				12				8				4				0																															
0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				0 0 0 0				1 0 0 0				1 1 1 1				1 1 1 1																																			
Reserved_12_31																M_GEN_CALL				M_START_DET				M_STOP_DET				M_ACTIVITY				M_RX_DONE				M_TX_ABORT				M_RD_REQ				M_TX_EMPTY				M_TX_OVER				M_RX_FULL				M_RX_OVER				M_RX_UNDER			



Bit Range	Default & Access	Field Name (ID): Description
7	1h RW	M_RX_DONE: See description of M_TX_EMPTY bit field.
6	1h RW	M_TX_ABRT: See description of M_TX_EMPTY bit field.
5	1h RW	M_RD_REQ: See description of M_TX_EMPTY bit field.
4	1h RW	M_TX_EMPTY: These bits mask their corresponding interrupt status bits in the IC_INTR_STAT register. Reset value: 12h8ff
3	1h RW	M_TX_OVER: See description of M_TX_EMPTY bit field.
2	1h RW	M_RX_FULL: See description of M_TX_EMPTY bit field.
1	1h RW	M_RX_OVER: See description of M_TX_EMPTY bit field.
0	1h RW	M_RX_UNDER: See description of M_TX_EMPTY bit field.

26.13.14 I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h

Unlike the IC_INTR_STAT register, these bits are not masked -- so they always show the true status of the DW_apb_i2c.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_12_31						GEN_CALL	START_DET	STOP_DET
						ACTIVITY	RX_DONE	TX_ABRT
						RD_REQ	TX_EMPTY	TX_OVER
						RX_FULL	RX_OVER	RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	0h RO	GEN_CALL: Same as in reg_IC_INTR_STAT.
10	0h RO	START_DET: Same as in reg_IC_INTR_STAT.



Bit Range	Default & Access	Field Name (ID): Description
9	0h RO	STOP_DET: Same as in reg_IC_INTR_STAT.
8	0h RO	ACTIVITY: Same as in reg_IC_INTR_STAT.
7	0h RO	RX_DONE: Same as in reg_IC_INTR_STAT.
6	0h RO	TX_ABRT: Same as in reg_IC_INTR_STAT.
5	0h RO	RD_REQ: Same as in reg_IC_INTR_STAT.
4	0h RO	TX_EMPTY: Same as in reg_IC_INTR_STAT.
3	0h RO	TX_OVER: Same as in reg_IC_INTR_STAT.
2	0h RO	RX_FULL: Same as in reg_IC_INTR_STAT.
1	0h RO	RX_OVER: Same as in reg_IC_INTR_STAT.
0	0h RO	RX_UNDER: Same as in reg_IC_INTR_STAT.

26.13.15 I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000010h

Reserved_8_31																RX_TL									
31	28			24			20			16			12			8			4			0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Receive FIFO Threshold Level (RX_TL): The valid range is 0-255, with the additional restriction that hardware does not allow this value to be set to a value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.



26.13.16 I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
Reserved_8_31							TX_TL	0

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Transmit FIFO Threshold Level (TX_TL): Controls the level of entries (or below) that trigger the TX_EMPTY interrupt (bit 4 in IC_RAW_INTR_STAT register). The valid range is 0-255, with the additional restriction that it may not be set to value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.

26.13.17 Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_INTR

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_INTR: Read this register to clear the combined interrupt, all individual interrupts, and the IC_TX_ABRT_SOURCE register. This bit does not clear hardware clearable interrupts but software clearable interrupts.



26.13.18 Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_UNDER: Read this register to clear the RX_UNDER interrupt (bit 0) of the IC_RAW_INTR_STAT register.

26.13.19 Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_OVER: Read this register to clear the RX_OVER interrupt (bit 1) of the IC_RAW_INTR_STAT register.



26.13.20 Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_OVER: Read this register to clear the TX_OVER interrupt (bit 3) of the IC_RAW_INTR_STAT register.

26.13.21 Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RD_REQ

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RD_REQ: Read this register to clear the RD_REQ interrupt (bit 5) of the IC_RAW_INTR_STAT register.



26.13.24 Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 5Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_ACTIVITY

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_ACTIVITY: Reading this register clears the ACTIVITY interrupt if the I2C is not active anymore. If the I2C module is still active on the bus, the ACTIVITY interrupt bit continues to be set. It is automatically cleared by hardware if the module is disabled and if there is no further activity on the bus. The value read from this register to get status of the ACTIVITY interrupt (bit 8) of the IC_RAW_INTR_STAT register.

26.13.25 Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_STOP_DET

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.



Access Method

Offset: [BAR] + 6Ch

BAR Reference: [B:0, D:24, F:4] + 10h

[illegible]

26.13.29 I2C Status Register (IC_STATUS)—Offset 70h

- Bits 1 and 2 are set to 1
- Bits 3 and 4 are set to 0

- Bits 5 and 6 are set to 0

October 2018
Document Number: 538136, Rev. 4.3



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_9_31						TXFLR		

Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Transmit FIFO Level (TXFLR): Contains the number of valid data entries in the transmit FIFO.

26.13.31 I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h

This register contains the number of valid data entries in the receive FIFO buffer. The register is cleared by the following methods:

- The I2C is disabled
- Whenever there is a transmit abort caused by any of the events tracked in IC_TX_ABRT_SOURCE

The register increments whenever data is placed into the receive FIFO and decrements when data is taken from the receive FIFO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 78h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_9_31						RXFLR		



Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Receive FIFO Level (RXFLR): Contains the number of valid data entries in the receive FIFO.

26.13.32 I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch

This register controls the amount of hold time on the SDA signal after a negative edge of SCL in both master and slave mode, in units of ic_clk period. The value programmed must be greater than the minimum hold time in each mode for the value to be implemented one cycle in master mode, seven cycles in slave mode. Writes to this register succeed only when IC_ENABLE=0. The programmed SDA hold time cannot exceed at any time the duration of the low part of scl. Therefore the programmed value cannot be larger than N_SCL_LOW-2, where N_SCL_LOW is the duration of the low part of the scl period measured in ic_clk cycles.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 7Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_16_31								IC_SDA_HOLD

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved
15:0	1h RW	IC_SDA_HOLD: Sets the required SDA hold time in units of ic_clk period.

26.13.33 I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h

This register has 16 bits that indicate the source of the TX_ABRT bit. Except for Bit 9, this register is cleared whenever the IC_CLR_TX_ABRT register or the IC_CLR_INTR register is read. To clear Bit 9, the source of the ABRT_SBYTE_NORSTRT must be fixed first; RESTART must be enabled (IC_CON[5]=1), the SPECIAL bit must be cleared (IC_TAR[11]), or the GC_OR_START bit must be cleared (IC_TAR[10]). Once the source of the ABRT_SBYTE_NORSTRT is fixed, then this bit can be cleared in the same



manner as other bits in this register. If the source of the ABRT_SBYTE_NORSTRT is not fixed before attempting to clear this bit, Bit 9 clears for one cycle and is then re-asserted.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0																																																			
0				0				0				0				0				0				0				0				0																																																			
TX_FLUSH_CNT								Reserved_17_23								ABRT_USER_ABRT				ABRT_SLVRD_INTX				ABRT_SLV_ARBLOST				ABRT_SLVFLUSH_TXFIFO				ARB_LOST				ABRT_MASTER_DIS				ABRT_10B_RD_NORSTRT				ABRT_SBYTE_NORSTRT				ABRT_HS_NORSTRT				ABRT_SBYTE_ACKDET				ABRT_HS_ACKDET				ABRT_GCALL_READ				ABRT_GCALL_NOACK				ABRT_TXDATA_NOACK				ABRT_10ADDR2_NOACK				ABRT_10ADDR1_NOACK				ABRT_7B_ADDR_NOACK			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RO	TX_FLUSH_CNT: This field preserves the TXFLR value prior to the last TX_ABRT event. It is enabled when fix_ctrl_1680 = 1. It is cleared whenever I2C is disabled.
23:17	0b RW	Reserved_17_23: Reserved
16	0h RO	ABRT_USER_ABRT: This is a master-mode only bit. Master has detected the user initiated transfer abort (IC_ENABLE[1]). It is enabled only when fix_ctrl_1680 = 1
15	0h RO	ABRT_SLVRD_INTX: 1 = When the processor side responds to a slave mode request for data to be transmitted to a remote master and user writes a 1 in CMD (bit 8) of IC_DATA_CMD register.
14	0h RO	ABRT_SLV_ARBLOST: 1 = Slave lost the bus while transmitting data to a remote master. IC_TX_ABRT_SOURCE[12] is set at the same time.
13	0h RO	ABRT_SLVFLUSH_TXFIFO: 1 = Slave has received a read command and some data exists in the TX FIFO so the slave issues a TX_ABRT interrupt to flush old data in TX FIFO.
12	0h RO	ARB_LOST: 1 = Master has lost arbitration, or if IC_TX_ABRT_SOURCE[14] is also set, then the slave transmitter has lost arbitration.
11	0h RO	ABRT_MASTER_DIS: 1 = User tries to initiate a Master operation with the Master mode disabled.
10	0h RO	ABRT_10B_RD_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the master sends a read command in 10-bit addressing mode.
9	0h RO	ABRT_SBYTE_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to send a START Byte.
8	0h RO	ABRT_HS_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to use the master to transfer data in High Speed mode.
7	0h RO	ABRT_SBYTE_ACKDET: 1 = Master has sent a START Byte and the START Byte was acknowledged (wrong behavior).



This register is only valid when DW_apb_i2c is configured with a set of DMA Controller interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist and writing to the registers address has no effect and reading from this register address will return zero. The register is used to enable the DMA Controller interface operation. There is a separate bit for transmit and receive. This can be programmed regardless of the state of IC_ENABLE.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	Reserved_2_31: Reserved.
1	0h RW	Transmit DMA Enable (TDMAE): This bit enables/disables the transmit FIFO DMA channel. 0 = Transmit DMA disabled 1 = Transmit DMA enabled
0	0h RW	Receive DMA Enable (RDMAE): This bit enables/disables the receive FIFO DMA channel. 0 = Receive DMA disabled 1 = Receive DMA enabled

26.13.36 DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch

This register is only valid when the DW_apb_i2c is configured with a set of DMA interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMATDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	0h RW	Transmit Data Level (DMATDL): This bit field controls the level at which a DMA request is made by the transmit logic. It is equal to the watermark level; that is, the dma_tx_req signal is generated when the number of valid data entries in the transmit FIFO is equal to or below this field value, and TDMAE = 1.

26.13.37 I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h

This register is only valid when DW_apb_i2c is configured with a set of DMA interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 90h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMARDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.

26.13.38 I2C SDA Setup Register (IC_SDA_SETUP)—Offset 94h



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_1_31								ACK_GEN_CALL

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	1h RW	ACK General Call (ACK_GEN_CALL): When set to 1, DW_apb_i2c responds with a ACK (by asserting ic_data_oe) when it receives a General Call. When set to 0, the DW_apb_i2c does not generate General Call interrupts.

26.13.40 I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch

The register is used to report the DW_apb_i2c hardware status when the IC_ENABLE register is set from 1 to 0, that is, when DW_apb_i2c is disabled.

- If IC_ENABLE has been set to 1, bits 2:1 are forced to 0, and bit 0 is forced to 1.
- If IC_ENABLE has been set to 0, bits 2:1 will only be valid as soon as bit 0 is read as 0.

NOTE = When IC_ENABLE has been written with 0, a delay occurs for bit 0 to be read as 0 because disabling the DW_apb_i2c depends on I2C bus activities.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h



26.13.44 I2C Component Version Register (IC_COMP_VERSION)—Offset F8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 3131352Ah

31	28	24	20	16	12	8	4	0
0	0	1	1	0	0	0	1	0
0	0	0	1	0	0	1	1	0
0	0	1	1	0	0	0	1	0
0	0	1	1	0	0	1	1	0
0	1	0	1	0	1	0	1	0
0	0	1	0	0	0	1	0	0
1	0	1	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	3131352Ah RO	IC_COMP_VERSION: Specific values for this register are described in the Releases Table in the AMBA 2 release notes.

26.13.45 I2C Component Type Register (IC_COMP_TYPE)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 44570140h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	1	0	0	0
0	1	0	0	0	1	0	0	0
0	1	0	1	0	1	1	1	0
0	1	1	1	0	0	0	0	0
0	0	0	0	0	0	0	1	0
0	1	0	0	0	0	1	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	44570140h RO	IC_COMP_TYPE: Designware Component Type number = 0x44_57_01_40. This assigned unique hex value is constant and is derived from the two ASCII letters DW followed by a 16-bit unsigned number.



26.13.46 reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h

indicate if the i2c uses 133MHz or 100MHz

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 800h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								hs_source_clock

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RO	hs_source_clock: Reflects the value configured in hs_source_clock_sel in GPIODEF0. 0 -100MHz (LPT-LP compatible) 1 -133MHz (high-speed operation compatible)

26.13.47 Software Reset (RESETS)—Offset 804h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 804h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved								reset_apb reset_func

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	Reserved (reserved): Reserved.
1	0h RW	reset_apb: reset the apb domain
0	0h RW	reset_func: reset the func clock domain

26.13.48 General Purpose Register (GENERAL)—Offset 808h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 808h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 55000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	sda_mux_sel: Reserved.
30	1h RW	sda_signal_state: Reserved.
29	0h RW	scl_mux_sel: Reserved.
28	1h RW	scl_signal_state: Reserved.
27	0h RO	sda_rd_pre_drive: Reserved.
26	1h RO	sda_rd_post_drive: Reserved.
25	0h RO	scl_rd_pre_drive: Reserved.
24	1h RO	scl_rd_post_drive: Reserved.
23:10	0h RO	Reserved: Reserved
9	0h RW	i2c_fix_ctrl_1680: Control port to enable fix 9000521680,Generation of STOP condition without data transfer
8	0h RW	i2c_fix_ctrl_0770: Control port to enable fix 9000530770,Stop generating DMA requests during Tx FIFO flush conditions
7	0h RW	i2c_fix_ctrl_1699: Control port to enable fix 9000481699,Rx data is pushed to Rx FIFO only after Tx FIFO is not-empty
6	0h RW	i2c_374798_fix_disable: chicken bit for Fix for NACK bug (HSD # 374798)
5	0h RW	i2c_374609_fix_disable: chicken bit for Fix for NACK bug (HSD # 374609)

TX transaction counter

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RO	RSVD0: Reserved
19	0h RW	i2c_tx_ack_count_clr_overflow: SW clear of TX transaction (byte) counter
18:17	0b RO	RSVD1: Reserved
16	0h RO	i2c_tx_count_overflow: indicate there was count overflow
15:0	0h RO	i2c_tx_ack_count: indicate TX transaction count for SW to read



26.13.50 I2C_TX_COMPLETE_INTR_STAT—Offset 820h

TX transaction has finished interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 820h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved								i2c_tx_complete_interrupt_mask
								i2c_tx_completion_interrupt

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RO	Reserved: Reserved
1	0h RW	i2c_tx_complete_interrupt_mask: Mask TX transaction has finished interrupt
0	0h RO	i2c_tx_completion_interrupt: indicate TX transaction has finished



26.13.51 reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h

indicate TX transaction has finished write 1 to clear the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 824h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:4] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								i2c_tx_complete_intr_clr

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	i2c_tx_complete_intr_clr: indicate TX transaction has finished write 1 to clear the interrupt

26.14.3 Revision ID and Class Code (REVCLASSCODE)—Offset 8h

Bit Range	Default & Access	Field Name (ID): Description
7:3	00h RO	Reserved5: Reserved.
2	0h RW	Bus Master Enable (BME): If this bit is 0, Bridge does not generate any new upstream transaction on IOSF as a master.
1	0h RW	Memory Space Enable (MSE): This bit controls Bridge's response to downstream Memory accesses. When set, accesses to memory space of the device is enabled.
0	0h RO	Reserved6: Reserved.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:5] + 8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Class Code (CLASS_CODES): The Class Code register is read-only and used to identify the generic function of the device and, in some cases, a specific register level programming interface. The register is broken into three byte size fields. The upper byte (at offset 0Bh) is a base class code which broadly classifies the type of function the device performs. The middle byte (at offset 0Ah) is a sub-class code which identifies more specifically the function of the device. The lower byte (at offset 09h) identifies a specific register-level programming interface (if any) so that device independent software can interact with the device. This register is tied to a strap at the top level.
7:0	00h RO	Revision ID (RID): Revision ID identifies the revision of particular AHB device. This is tied to a strap at the top level.



26.14.4 Cache Line Latency Header and BIST (CLLATHEADERBIST)—Offset Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:5] + Ch

Default: 00800000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0	MULFNDEV	HEADERTYPE	LATTIMER	CACHELINE_SIZE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.



Access Method

Offset: [B:0, D:24, F:5] + 2Ch

31 28 24 20 16 12 8 4 0																														
0 0																														
SUBSYSTEMID																SUBSYSTEMVENDORID														

26.14.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Access Method

Offset: [B:0, D:24, F:5] + 30h

October 2018
Document Number: 538136, Rev.4.3



Type: PCI Configuration Register
(Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.
7:0	00h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. If PM capability is disabled then this register has 00h.

26.14.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Type: PCI Configuration Register
(Size: 32 bits)

Default: 00000100h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
MAX_LAT				MIN_GNT				INTPIN
				Reserved0				INTLINE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a Single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to tell software which interrupt line the interrupt pin is connected to.

26.14.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:5] + 80h

Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0
PMESUPPORT				Reserved0				POWER_CAP
				VERSION				
				NXTCAP				

Bit Range	Default & Access	Field Name (ID): Description
31:27	00h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. - bit(11) X XXX1b - PME# can be asserted from D0. - bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. - bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. - bit(14) X 1XXXb - PME# can be asserted from D3hot. - bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the strap strap_pme_support.
26:19	00h RO	Reserved0: Reserved.



26.15 SIO I²C 4 Memory Mapped I/O Registers

Table 273. Summary of I²C 4 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"I2C Control Register (IC_CON)—Offset 0h" on page 4063	0000007Fh
4–7h	4	"I2C Target Address Register (IC_TAR)—Offset 4h" on page 4064	00001055h
8–Bh	4	"I2C Slave Address Register (IC_SAR)—Offset 8h" on page 4065	00000055h
C–Fh	4	"I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch" on page 4065	00000001h
10–13h	4	"I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h" on page 4066	00000000h
14–17h	4	"Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h" on page 4067	00000190h
18–1Bh	4	"Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h" on page 4067	000001D6h
1C–1Fh	4	"Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch" on page 4068	0000003Ch
20–23h	4	"Fast Speed I2C Clock SCL Low Count Register (IC_FS_SCL_LCNT)—Offset 20h" on page 4069	00000082h
24–27h	4	"High Speed I2C Clock SCL High Count Register (IC_HS_SCL_HCNT)—Offset 24h" on page 4069	0000000Ch
28–2Bh	4	"High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h" on page 4070	00000020h
2C–2Fh	4	"I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch" on page 4071	00000000h
30–33h	4	"I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h" on page 4072	000008FFh
34–37h	4	"I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h" on page 4073	00000000h
38–3Bh	4	"I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h" on page 4074	00000010h
3C–3Fh	4	"I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch" on page 4075	00000010h
40–43h	4	"Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h" on page 4075	00000000h
44–47h	4	"Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h" on page 4076	00000000h
48–4Bh	4	"Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h" on page 4076	00000000h
4C–4Fh	4	"Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch" on page 4077	00000000h
50–53h	4	"Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h" on page 4077	00000000h
54–57h	4	"Clear TX_ABRT Interrupt Register (IC_CLR_TX_ABRT)—Offset 54h" on page 4078	00000000h
58–5Bh	4	"Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h" on page 4078	00000000h
5C–5Fh	4	"Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch" on page 4079	00000000h
60–63h	4	"Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h" on page 4079	00000000h



Table 273. Summary of I²C 4 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
64–67h	4	"Clear START_DET Interrupt Register (IC_CLR_START_DET)—Offset 64h" on page 4080	00000000h
68–6Bh	4	"Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h" on page 4080	00000000h
6C–6Fh	4	"I2C Enable Register (IC_ENABLE)—Offset 6Ch" on page 4081	00000000h
70–73h	4	"I2C Status Register (IC_STATUS)—Offset 70h" on page 4081	00000006h
74–77h	4	"I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h" on page 4082	00000000h
78–7Bh	4	"I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h" on page 4083	00000000h
7C–7Fh	4	"I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch" on page 4084	00000001h
80–83h	4	"I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h" on page 4084	00000000h
84–87h	4	"Generate Slave Data NACK Register (IC_SLV_DATA_NACK_ONLY)—Offset 84h" on page 4086	00000000h
88–8Bh	4	"DMA Control Register (IC_DMA_CR)—Offset 88h" on page 4087	00000000h
8C–8Fh	4	"DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch" on page 4087	00000000h
90–93h	4	"I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h" on page 4088	00000000h
94–97h	4	"I2C SDA Setup Register (IC_SDA_SETUP)—Offset 94h" on page 4089	00000064h
98–9Bh	4	"I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h" on page 4090	00000001h
9C–9Fh	4	"I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch" on page 4090	00000000h
A0–A3h	4	"IC_FS_SPKLEN—Offset A0h" on page 4091	00000005h
A4–A7h	4	"IC_HS_SPKLEN—Offset A4h" on page 4092	00000002h
F4–F7h	4	"Component Parameter Register 1 (IC_COMP_PARAM_1)—Offset F4h" on page 4093	00FFFFFFh
F8–FBh	4	"I2C Component Version Register (IC_COMP_VERSION)—Offset F8h" on page 4094	3131352Ah
FC–FFh	4	"I2C Component Type Register (IC_COMP_TYPE)—Offset FCh" on page 4094	44570140h
800–803h	4	"reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h" on page 4095	00000000h
804–807h	4	"Software Reset (RESETS)—Offset 804h" on page 4095	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 4096	55000000h
818–81Bh	4	"I2C_ACK_COUNT—Offset 818h" on page 4097	00000000h
820–823h	4	"I2C_TX_COMPLETE_INTR_STAT—Offset 820h" on page 4098	00000000h
824–827h	4	"reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h" on page 4099	00000000h



26.15.2 I2C Target Address Register (IC_TAR)—Offset 4h

Writes to IC_TAR succeed when one of the following conditions are true:

- DW_apb_i2c is NOT enabled (IC_ENABLE is set to 0)
-
- OR
-
- DW_apb_i2c is enabled (IC_ENABLE=1)
- AND
- DW_apb_i2c is NOT engaged in any Master (tx, rx) operation (IC_STATUS[5]=0)
- AND
- DW_apb_i2c is enabled to operate in Master mode (IC_CON[0]=1)
- AND
- There are NO entries in the TX FIFO (IC_STATUS[2]=1)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00001055h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_13_31					IC_10BITADDR_MASTER	SPECIAL		
						GC_OR_START		
						IC_TAR		

Bit Range	Default & Access	Field Name (ID): Description
31:13	0b RW	Reserved_13_31: Reserved.
12	1h RW	IC_10BITADDR_MASTER: This bit controls whether the DW_apb_i2c starts its transfers in 7-or 10-bit addressing mode when acting as a master.
11	0h RW	SPECIAL: This bit indicates whether software performs a General Call or START BYTE command. • 0 = ignore bit 10 GC_OR_START and use IC_TAR normally • 1 = perform special I2C command as specified in GC_OR_START bit
10	0h RW	GC_OR_START: If bit 11 (SPECIAL) is set to 1, then this bit indicates whether a General Call(0) or START(1) byte command is to be performed by the DW_apb_i2c.
9:0	55h RW	IC_TAR: This is the target address for any master transaction. When transmitting a General Call, these bits are ignored. To generate a START BYTE, the CPU needs to write only once into these bits.





This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock high-period count for fast speed. It is used in high-speed mode to send the Master Code and START BYTE or General CALL.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 0000003Ch

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31					IC_FS_SCL_HCNT			

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	003ch RW	Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.



This register must be set before any I2C bus transaction can take place, to ensure proper I/O timing. This register sets the SCL clock low-period count for fast speed. It is used in high-speed mode to send the Master Code and START BYTE or General CALL. The SCL High time depends on the loading of the bus. For 100pF loading, the SCL High time is 60ns; for 400pF loading, the SCL High time is 120ns. This register goes away and becomes read-only if `IC_MAX_SPEED_MODE` != high. This register can be written only when the I2C interface is disabled, which corresponds to the `IC_ENABLE` register being set to 0. Writes at other times have no effect. The minimum valid value is 8; hardware prevents values less than this being written, and, if attempted, results in 8 being set. For designs with `APB_DATA_WIDTH == 8` the order of programming is important to ensure the correct operation of the `DW_apb_i2c`. The lower byte must be programmed first. Then the upper byte can be programmed.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 28h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000020h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IIC_HS_SCL_LCNT				



Bit Range	Default & Access	Field Name (ID): Description
4	0h RO	R_TX_EMPTY: This bit is set to 1 when the transmit buffer is at or below the threshold value set in the IC_TX_TL register.
3	0h RO	R_TX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH, and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
2	0h RO	R_RX_FULL: Set when the receive buffer reaches or goes above the RX_TL threshold in the IC_RX_TL register.
1	0h RO	R_RX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
0	0h RO	R_RX_UNDER: Set if the processor attempts to read the receive buffer when it is empty by reading from the IC_DATA_CMD register.

26.15.13 I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h

These bits mask their corresponding interrupt status bits. This register is active low.

- 0 masks the interrupt
- 1 unmasks the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 000008FFh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_12_31						M_GEN_CALL	M_START_DET	M_STOP_DET
						M_ACTIVITY	M_RX_DONE	M_TX_ABORT
						M_RD_REQ	M_TX_EMPTY	M_TX_OVER
						M_RX_FULL	M_RX_OVER	M_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	1h RW	M_GEN_CALL: See description of M_TX_EMPTY bit field.
10	0h RW	M_START_DET: See description of M_TX_EMPTY bit field.
9	0h RW	M_STOP_DET: See description of M_TX_EMPTY bit field.
8	0h RW	M_ACTIVITY: See description of M_TX_EMPTY bit field.



Bit Range	Default & Access	Field Name (ID): Description
7	1h RW	M_RX_DONE: See description of M_TX_EMPTY bit field.
6	1h RW	M_TX_ABRT: See description of M_TX_EMPTY bit field.
5	1h RW	M_RD_REQ: See description of M_TX_EMPTY bit field.
4	1h RW	M_TX_EMPTY: These bits mask their corresponding interrupt status bits in the IC_INTR_STAT register. Reset value: 12h8ff
3	1h RW	M_TX_OVER: See description of M_TX_EMPTY bit field.
2	1h RW	M_RX_FULL: See description of M_TX_EMPTY bit field.
1	1h RW	M_RX_OVER: See description of M_TX_EMPTY bit field.
0	1h RW	M_RX_UNDER: See description of M_TX_EMPTY bit field.

26.15.14 I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)– Offset 34h

Unlike the IC_INTR_STAT register, these bits are not masked -- so they always show the true status of the DW_apb_i2c.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

	31	28	24	20	16	12	8	4	0
	0	0	0	0	0	0	0	0	0
	Reserved_12_31							GEN_CALL	
								START_DET	
								STOP_DET	
								ACTIVITY	
								RX_DONE	
								TX_ABRT	
								RD_REQ	
								TX_EMPTY	
								TX_OVER	
								RX_FULL	
								RX_OVER	
								RX_UNDRF	

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	0h RO	GEN_CALL: Same as in reg_IC_INTR_STAT.
10	0h RO	START_DET: Same as in reg_IC_INTR_STAT.



Bit Range	Default & Access	Field Name (ID): Description
9	0h RO	STOP_DET: Same as in reg_IC_INTR_STAT.
8	0h RO	ACTIVITY: Same as in reg_IC_INTR_STAT.
7	0h RO	RX_DONE: Same as in reg_IC_INTR_STAT.
6	0h RO	TX_ABRT: Same as in reg_IC_INTR_STAT.
5	0h RO	RD_REQ: Same as in reg_IC_INTR_STAT.
4	0h RO	TX_EMPTY: Same as in reg_IC_INTR_STAT.
3	0h RO	TX_OVER: Same as in reg_IC_INTR_STAT.
2	0h RO	RX_FULL: Same as in reg_IC_INTR_STAT.
1	0h RO	RX_OVER: Same as in reg_IC_INTR_STAT.
0	0h RO	RX_UNDER: Same as in reg_IC_INTR_STAT.

26.15.15 I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0
Reserved_8_31							RX_TL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Receive FIFO Threshold Level (RX_TL): The valid range is 0-255, with the additional restriction that hardware does not allow this value to be set to a value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.



26.15.16 I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
Reserved_8_31							TX_TL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Transmit FIFO Threshold Level (TX_TL): Controls the level of entries (or below) that trigger the TX_EMPTY interrupt (bit 4 in IC_RAW_INTR_STAT register). The valid range is 0-255, with the additional restriction that it may not be set to value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.

26.15.17 Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_INTR

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_INTR: Read this register to clear the combined interrupt, all individual interrupts, and the IC_TX_ABRT_SOURCE register. This bit does not clear hardware clearable interrupts but software clearable interrupts.



26.15.18 Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_UNDER: Read this register to clear the RX_UNDER interrupt (bit 0) of the IC_RAW_INTR_STAT register.

26.15.19 Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_OVER: Read this register to clear the RX_OVER interrupt (bit 1) of the IC_RAW_INTR_STAT register.



26.15.20 Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_OVER: Read this register to clear the TX_OVER interrupt (bit 3) of the IC_RAW_INTR_STAT register.

26.15.21 Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RD_REQ

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RD_REQ: Read this register to clear the RD_REQ interrupt (bit 5) of the IC_RAW_INTR_STAT register.



26.15.22 Clear TX_ABRT Interrupt Register (IC_CLR_TX_ABRT)—Offset 54h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_ABRT

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_ABRT: Read this register to clear the TX_ABRT interrupt (bit 6) of the IC_RAW_INTR_STAT register, and the IC_TX_ABRT_SOURCE register. This also releases the TX FIFO from the flushed/reset state, allowing more writes to the TX FIFO.

26.15.23 Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_DONE

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_DONE: Read this register to clear the RX_DONE interrupt (bit 7) of the IC_RAW_INTR_STAT register.



26.15.24 Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 5Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_ACTIVITY

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_ACTIVITY: Reading this register clears the ACTIVITY interrupt if the I2C is not active anymore. If the I2C module is still active on the bus, the ACTIVITY interrupt bit continues to be set. It is automatically cleared by hardware if the module is disabled and if there is no further activity on the bus. The value read from this register to get status of the ACTIVITY interrupt (bit 8) of the IC_RAW_INTR_STAT register.

26.15.25 Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_STOP_DET

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.



26.15.27 Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
Reserved_1_31									CLR_GEN_CAL



Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_GEN_CALL: Read this register to clear the GEN_CALL interrupt (bit 11) of IC_RAW_INTR_STAT register.

26.15.28 I2C Enable Register (IC_ENABLE)—Offset 6Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 6Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	Reserved_2_31: Reserved
1	0h WO	ABORT: Software can abort the I2C transfer by setting this bit. This bit can be set only when ENABLE = 1 and fix_ctrl_1680 = 1. The HW will clear the ABORT bit once the STOP condition has been sent.
0	0h RW	ENABLE: Controls whether the DW_apb_i2c is enabled. 0 = Disables DW_apb_i2c (TX and RX FIFOs are held in an erased state) 1 = Enables DW_apb_i2c

26.15.29 I2C Status Register (IC_STATUS)—Offset 70h

This is a read-only register used to indicate the current transfer status and FIFO status. The status register may be read at any time. None of the bits in this register request an interrupt. The following occurs when the I2C is disabled by writing 0 in bit 0 of the IC_ENABLE register:

- Bits 1 and 2 are set to 1
- Bits 3 and 4 are set to 0

When the master or slave state machines goes to idle and `ic_en=0`:

- Bits 5 and 6 are set to 0

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 70h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000006h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_7_31							SLV_ACTIVITY	
							MST_ACTIVITY	
							RFF	
							RFNE	
							TFE	
							TFNF	
							ACTIVITY	

Bit Range	Default & Access	Field Name (ID): Description
31:7	0b RW	Reserved_7_31: Reserved.
6	0h RO	Slave FSM Activity Status (SLV_ACTIVITY): When the Slave Finite State Machine (FSM) is not in the IDLE state, this bit is set.
5	0h RO	Master FSM Activity Status (MST_ACTIVITY): When the Master Finite State Machine (FSM) is not in the IDLE state, this bit is set.
4	0h RO	Receive FIFO Completely Full (RFF): When the receive FIFO is completely full, this bit is set. When the receive FIFO contains one or more empty location, this bit is cleared.
3	0h RO	Receive FIFO Not Empty (RFNE): This bit is set when the receive FIFO contains one or more entries; it is cleared when the receive FIFO is empty.
2	1h RO	Transmit FIFO Completely Empty (TFE): When the transmit FIFO is completely empty, this bit is set. When it contains one or more valid entries, this bit is cleared. This bit field does not request an interrupt.
1	1h RO	Transmit FIFO Not Full (TFNF): Set when the transmit FIFO contains one or more empty locations, and is cleared when the FIFO is full.
0	0h RO	ACTIVITY: I2C Activity Status


26.15.30 I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h

This register contains the number of valid data entries in the transmit FIFO buffer. It is cleared whenever:

- The I2C is disabled
- There is a transmit abort -- that is, TX_ABRT bit is set in the IC_RAW_INTR_STAT register
- The slave bulk transmit mode is aborted

The register increments whenever data is placed into the transmit FIFO and decrements when data is taken from the transmit FIFO.

Access Method



Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Receive FIFO Level (RXFLR): Contains the number of valid data entries in the receive FIFO.

26.15.32 I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch

This register controls the amount of hold time on the SDA signal after a negative edge of SCL in both master and slave mode, in units of ic_clk period. The value programmed must be greater than the minimum hold time in each mode for the value to be implemented one cycle in master mode, seven cycles in slave mode. Writes to this register succeed only when IC_ENABLE=0. The programmed SDA hold time cannot exceed at any time the duration of the low part of scl. Therefore the programmed value cannot be larger than N_SCL_LOW-2, where N_SCL_LOW is the duration of the low part of the scl period measured in ic_clk cycles.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 7Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_16_31								IC_SDA_HOLD

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved
15:0	1h RW	IC_SDA_HOLD: Sets the required SDA hold time in units of ic_clk period.

26.15.33 I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h

This register has 16 bits that indicate the source of the TX_ABRT bit. Except for Bit 9, this register is cleared whenever the IC_CLR_TX_ABRT register or the IC_CLR_INTR register is read. To clear Bit 9, the source of the ABRT_SBYTE_NORSTRT must be fixed first; RESTART must be enabled (IC_CON[5]=1), the SPECIAL bit must be cleared (IC_TAR[11]), or the GC_OR_START bit must be cleared (IC_TAR[10]). Once the source of the ABRT_SBYTE_NORSTRT is fixed, then this bit can be cleared in the same

26.15.34 Generate Slave Data NACK Register (IC_SLV_DATA_NACK_ONLY)—Offset 84h



Bit Range	Default & Access	Field Name (ID): Description
0	0h RW	Generate NACK (NACK): This NACK generation only occurs when DW_apb_i2c is a slavereceiver. If this register is set to a value of 1, it can only generate a NACK after a data byte is received; hence, the data transfer is aborted and the data received is not pushed to the receive buffer. When the register is set to a value of 0, it generates NACK/ACK, depending on normal criteria. 1 = generate NACK after data byte received 0 = generate NACK/ACK normally

26.15.35 DMA Control Register (IC_DMA_CR)—Offset 88h

This register is only valid when DW_apb_i2c is configured with a set of DMA Controller interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist and writing to the registers address has no effect and reading from this register address will return zero. The register is used to enable the DMA Controller interface operation. There is a separate bit for transmit and receive. This can be programmed regardless of the state of IC_ENABLE.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	Reserved_2_31: Reserved.
1	0h RW	Transmit DMA Enable (TDMAE): This bit enables/disables the transmit FIFO DMA channel. 0 = Transmit DMA disabled 1 = Transmit DMA enabled
0	0h RW	Receive DMA Enable (RDMAE): This bit enables/disables the receive FIFO DMA channel. 0 = Receive DMA disabled 1 = Receive DMA enabled

26.15.36 DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch

This register is only valid when the DW_apb_i2c is configured with a set of DMA interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMATDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	0h RW	Transmit Data Level (DMATDL): This bit field controls the level at which a DMA request is made by the transmit logic. It is equal to the watermark level; that is, the dma_tx_req signal is generated when the number of valid data entries in the transmit FIFO is equal to or below this field value, and TDMAE = 1.

26.15.37 I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h

This register is only valid when DW_apb_i2c is configured with a set of DMA interface signals(IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 90h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMARDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.



This register controls the amount of time delay (in terms of number of ic_clk clock periods) introduced in the rising edge of SCL -- relative to SDA changing -- by holding SCL low when DW_apb_i2c services a read request while operating as a slave-transmitter. The relevant I2C requirement is tSU:DAT (note 4) as detailed in the I2C Bus Specification. This register must be programmed with a value equal to or greater than 2. **NOTE:** The length of setup time is calculated using $[(IC_SDA_SETUP - 1) * (ic_clk_period)]$, so if the user requires 10 ic_clk periods of setup time, they should program a value of 11. The IC_SDA_SETUP register is only used by the DW_apb_i2c when operating as a slave transmitter.

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000064h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	64h RW	SDA Setup (SDA_SETUP): It is recommended that if the required delay is 1000ns, then for an ic_clk frequency of 10 MHz, IC_SDA_SETUP should be programmed to a value of 11.



26.15.39 I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h

The register controls whether DW_apb_i2c responds with an ACK or NACK when it receives an I2C General Call address.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_1_31								ACK_GEN_CALL

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	1h RW	ACK General Call (ACK_GEN_CALL): When set to 1, DW_apb_i2c responds with a ACK (by asserting ic_data_oe) when it receives a General Call. When set to 0, the DW_apb_i2c does not generate General Call interrupts.

26.15.40 I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch

The register is used to report the DW_apb_i2c hardware status when the IC_ENABLE register is set from 1 to 0, that is, when DW_apb_i2c is disabled.

- If IC_ENABLE has been set to 1, bits 2:1 are forced to 0, and bit 0 is forced to 1.
- If IC_ENABLE has been set to 0, bits 2:1 will only be valid as soon as bit 0 is read as 0.

NOTE = When IC_ENABLE has been written with 0, a delay occurs for bit 0 to be read as 0 because disabling the DW_apb_i2c depends on I2C bus activities.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h



26.15.41 IC FS SPKLEN—Offset A0h

Access Method

BAR Reference: [B:0, D:24, F:5] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_8_31							IC_FS_SPKLEN	



Access Method

Offset: [BAR] + A4h

BAR Reference: [B:0, D:24, F:5] + 10h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	2h RW	IC_HS_SPKLEN: This register must be set before any I2C bus transaction can take place to ensure stable operation. This register sets the duration, measured in ic_clk cycles, of the longest spike in the SCL or SDA lines that are filtered out by the spike suppression logic; for more information, refer to Spike Suppression on page 52. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect. The minimum valid value is 1; hardware prevents values less than this being written, and if attempted results in 2 being set.

26.15.43 Component Parameter Register 1 (IC_COMP_PARAM_1)—Offset F4h



26.15.44 I2C Component Version Register (IC_COMP_VERSION)—Offset F8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 3131352Ah

31	28	24	20	16	12	8	4	0
0	0	1	1	0	0	0	1	0
0	0	0	1	0	0	1	1	0
0	0	1	1	0	0	0	1	0
0	1	0	1	0	0	1	0	1
0	0	1	0	1	0	1	0	1
0	1	0	1	0	1	0	1	0
0	0	1	0	1	0	1	0	1

IC_COMP_VERSION

Bit Range	Default & Access	Field Name (ID): Description
31:0	3131352Ah RO	IC_COMP_VERSION: Specific values for this register are described in the Releases Table in the AMBA 2 release notes.

26.15.45 I2C Component Type Register (IC_COMP_TYPE)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 44570140h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	1	0	0	0
0	1	0	0	0	1	0	0	0
0	1	0	1	0	1	1	1	0
0	0	0	0	0	0	0	0	1
0	0	0	0	1	0	1	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

IC_COMP_TYPE

Bit Range	Default & Access	Field Name (ID): Description
31:0	44570140h RO	IC_COMP_TYPE: Designware Component Type number = 0x44_57_01_40. This assigned unique hex value is constant and is derived from the two ASCII letters DW followed by a 16-bit unsigned number.

26.15.48 General Purpose Register (GENERAL)—Offset 808h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 808h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 55000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	sda_mux_sel: Reserved.
30	1h RW	sda_signal_state: Reserved.
29	0h RW	scl_mux_sel: Reserved.
28	1h RW	scl_signal_state: Reserved.
27	0h RO	sda_rd_pre_drive: Reserved.
26	1h RO	sda_rd_post_drive: Reserved.
25	0h RO	scl_rd_pre_drive: Reserved.
24	1h RO	scl_rd_post_drive: Reserved.
23:10	0h RO	Reserved: Reserved
9	0h RW	i2c_fix_ctrl_1680: Control port to enable fix 9000521680,Generation of STOP condition without data transfer
8	0h RW	i2c_fix_ctrl_0770: Control port to enable fix 9000530770,Stop generating DMA requests during Tx FIFO flush conditions
7	0h RW	i2c_fix_ctrl_1699: Control port to enable fix 9000481699,Rx data is pushed to Rx FIFO only after Tx FIFO is not-empty
6	0h RW	i2c_374798_fix_disable: chicken bit for Fix for NACK bug (HSD # 374798)
5	0h RW	i2c_374609_fix_disable: chicken bit for Fix for NACK bug (HSD # 374609)



Bit Range	Default & Access	Field Name (ID): Description
4	0h RW	i2c_tx_lastbyte_flag: SW indicates it's last byte for TX transaction (HSD # 374798)
3:0	0h RW	reserved: reserved

26.15.49 I2C_ACK_COUNT—Offset 818h

TX transaction counter

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 818h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
		RSVD0		i2c_tx_ack_count_clr_overflow	RSVD1		i2c_tx_ack_count	
				i2c_tx_count_overflow				

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RO	RSVD0: Reserved
19	0h RW	i2c_tx_ack_count_clr_overflow: SW clear of TX transaction (byte) counter
18:17	0b RO	RSVD1: Reserved
16	0h RO	i2c_tx_count_overflow: indicate there was count overflow
15:0	0h RO	i2c_tx_ack_count: indicate TX transaction count for SW to read



Access Method

Offset: [BAR] + 820h

BAR Reference: [B:0, D:24, F:5] + 10h

	31	28	24	20	16	12	8	4	0	
	0	0	0	0	0	0	0	0	0	
										i2c_tx_complete_interrupt_mask
										i2c_tx_completion_interrupt

Intel Atom® Processor E3800 Product Family
Datasheet
4098



26.15.51 reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h

indicate TX transaction has finished write 1 to clear the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 824h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:5] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								i2c_tx_complete_intr_clr

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	i2c_tx_complete_intr_clr: indicate TX transaction has finished write 1 to clear the interrupt



Access Method

Offset: [B:0, D:24, F:6] + 8h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Class Code (CLASS_CODES): The Class Code register is read-only and used to identify the generic function of the device and, in some cases, a specific register level programming interface. The register is broken into three byte size fields. The upper byte (at offset 0Bh) is a base class code which broadly classifies the type of function the device performs. The middle byte (at offset 0Ah) is a sub-class code which identifies more specifically the function of the device. The lower byte (at offset 09h) identifies a specific register-level programming interface (if any) so that device independent software can interact with the device. This register is tied to a strap at the top level.
7:0	00h RO	Revision ID (RID): Revision ID identifies the revision of particular AHB device. This is tied to a strap at the top level.



26.16.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR						SIZEINDICATOR		PREFETCHABLE
								TYPE
								MESSAGE_SPACE

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.
2:1	0h RO	Type (TYPE): 00 indicates BAR lies in 32 bit address range.
0	0h RO	Memory Space Indicator (MESSAGE_SPACE): 0. Indicates this BAR is present in the memory space.

26.16.6 Base Address Register 1 (BAR1)—Offset 14h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:6] + 14h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		PREFETCHABLE1
								TYPE1
								MESSAGE_SPACE1

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address Register 1 (BASEADDR1): BAR1 of the LPIO device.



Type: PCI Configuration Register
(Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW/O	Subsystem ID (SUBSYSTEMID): This register should be implemented for any function that could be instantiated more than once in a given system. The SID register in combination with the Subsystem Vendor ID register, make it possible for the operating environment to distinguish one audio subsystem from the other. This register is a Read Write Once type register.
15:0	0000h RW/O	Subsystem Vendor ID (SUBSYSTEMVENDORID): This register should be implemented for any function that could be instantiated more than once in a given system. The SVID register, in combination with the Subsystem ID register, enables the operating environment to distinguish one subsystem from the other. This register is a Read Write Once register.

**Offset:** [B:0, D:24, F:6] + 30h

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	EXPANSION_ROM_BASE: Reserved.

Offset: [B:0, D:24, F:6] + 34h

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.
7:0	00h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. If PM capability is disabled then this register has 00h.



26.16.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:6] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
MAX_LAT				MIN_GNT				INTLINE
				Reserved0				INTPIN

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a Single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to tell software which interrupt line the interrupt pin is connected to.

26.16.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:6] + 80h

Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
PMESUPPORT				Reserved0				POWER_CAP
				VERSION				
				NXTCAP				



Access Method

Offset: [B:0, D:24, F:6] + 84h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0				PMESTATUS	Reserved1		PMEENABLE	Reserved2
								NO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit (bit 8 in this register).
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
3	1h RO	No_Soft_Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state - Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for Downstream decode on fabric ports.

26.16.13 Manufacturer ID (MANID)—Offset F8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:6] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
MANID								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



26.17 SIO I²C 5 Memory Mapped I/O Registers

Table 275. Summary of I²C 5 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"I2C Control Register (IC_CON)—Offset 0h" on page 4112	0000007Fh
4–7h	4	"I2C Target Address Register (IC_TAR)—Offset 4h" on page 4113	00001055h
8–Bh	4	"I2C Slave Address Register (IC_SAR)—Offset 8h" on page 4114	00000055h
C–Fh	4	"I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch" on page 4114	00000001h
10–13h	4	"I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h" on page 4115	00000000h
14–17h	4	"Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h" on page 4116	00000190h
18–1Bh	4	"Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h" on page 4116	000001D6h
1C–1Fh	4	"Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch" on page 4117	0000003Ch
20–23h	4	"Fast Speed I2C Clock SCL Low Count Register (IC_FS_SCL_LCNT)—Offset 20h" on page 4118	00000082h
24–27h	4	"High Speed I2C Clock SCL High Count Register (IC_HS_SCL_HCNT)—Offset 24h" on page 4118	0000000Ch
28–2Bh	4	"High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h" on page 4119	00000020h
2C–2Fh	4	"I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch" on page 4120	00000000h
30–33h	4	"I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h" on page 4121	000008FFh
34–37h	4	"I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h" on page 4122	00000000h
38–3Bh	4	"I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h" on page 4123	00000010h
3C–3Fh	4	"I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch" on page 4124	00000010h
40–43h	4	"Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h" on page 4124	00000000h
44–47h	4	"Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h" on page 4125	00000000h
48–4Bh	4	"Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h" on page 4125	00000000h
4C–4Fh	4	"Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch" on page 4126	00000000h
50–53h	4	"Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h" on page 4126	00000000h
54–57h	4	"Clear TX_ABORT Interrupt Register (IC_CLR_TX_ABORT)—Offset 54h" on page 4127	00000000h
58–5Bh	4	"Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h" on page 4127	00000000h
5C–5Fh	4	"Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch" on page 4128	00000000h
60–63h	4	"Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h" on page 4128	00000000h



Table 275. Summary of I²C 5 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
64–67h	4	"Clear START_DET Interrupt Register (IC_CLR_START_DET)—Offset 64h" on page 4129	00000000h
68–6Bh	4	"Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h" on page 4129	00000000h
6C–6Fh	4	"I2C Enable Register (IC_ENABLE)—Offset 6Ch" on page 4130	00000000h
70–73h	4	"I2C Status Register (IC_STATUS)—Offset 70h" on page 4130	00000006h
74–77h	4	"I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h" on page 4131	00000000h
78–7Bh	4	"I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h" on page 4132	00000000h
7C–7Fh	4	"I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch" on page 4133	00000001h
80–83h	4	"I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h" on page 4133	00000000h
84–87h	4	"Generate Slave Data NACK Register (IC_SLV_DATA_NACK_ONLY)—Offset 84h" on page 4135	00000000h
88–8Bh	4	"DMA Control Register (IC_DMA_CR)—Offset 88h" on page 4136	00000000h
8C–8Fh	4	"DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch" on page 4136	00000000h
90–93h	4	"I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h" on page 4137	00000000h
94–97h	4	"I2C SDA Setup Register (IC_SDA_SETUP)—Offset 94h" on page 4138	00000064h
98–9Bh	4	"I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h" on page 4139	00000001h
9C–9Fh	4	"I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch" on page 4139	00000000h
A0–A3h	4	"IC_FS_SPKLEN—Offset A0h" on page 4140	00000005h
A4–A7h	4	"IC_HS_SPKLEN—Offset A4h" on page 4141	00000002h
F4–F7h	4	"Component Parameter Register 1 (IC_COMP_PARAM_1)—Offset F4h" on page 4142	00FFFFFFh
F8–FBh	4	"I2C Component Version Register (IC_COMP_VERSION)—Offset F8h" on page 4143	3131352Ah
FC–FFh	4	"I2C Component Type Register (IC_COMP_TYPE)—Offset FCh" on page 4143	44570140h
800–803h	4	"reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h" on page 4144	00000000h
804–807h	4	"Software Reset (RESETS)—Offset 804h" on page 4144	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 4145	55000000h
818–81Bh	4	"I2C_ACK_COUNT—Offset 818h" on page 4146	00000000h
820–823h	4	"I2C_TX_COMPLETE_INTR_STAT—Offset 820h" on page 4147	00000000h
824–827h	4	"reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h" on page 4148	00000000h



26.17.1 I2C Control Register (IC_CON)—Offset 0h

This register can be written only when the DW_apb_i2c is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 0000007Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_7_31							IC_SLAVE_DISABLE	IC_RESTART_EN
							IC_10BITADDR_MASTER_rd_only	IC_10BITADDR_SLAVE
							SPEED	MASTER_MODE

Bit Range	Default & Access	Field Name (ID): Description
31:7	0b RW	Reserved_7_31: Reserved.
6	1h RW	IC_SLAVE_DISABLE: This bit controls whether I2C has its slave disabled. By default, the slave is always enabled (in reset state as well). If you need to disable it after reset, set this bit to 1. If this bit is set (slave is disabled), DW_apb_i2c functions only as a master and does not perform any action that requires a slave.
5	1h RW	IC_RESTART_EN: Determines whether RESTART conditions may be sent when acting as a master. When the RESTART is disabled, the DW_apb_i2c master is incapable of performing the following functions: - Sending a START BYTE - Performing any high-speed mode operation - Performing direction changes in combined format mode - Performing a read operation with a 10-bit address
4	1h RO	IC_10BITADDR_MASTER (IC_10BITADDR_MASTER_rd_only): Controls whether the DW_apb_i2c starts its transfers in 7- or 10-bit addressing mode when acting as a master. If I2C_DYNAMIC_TAR_UPDATE = 1, then this bit is read-only copy of bit 12 of IC_TAR register.
3	1h RW	IC_10BITADDR_SLAVE: When acting as a slave, this bit controls whether the DW_apb_i2c responds to 7- or 10-bit addresses.
2:1	3h RW	SPEED: These bits control at which speed the DW_apb_i2c operates; its setting is relevant only if one is operating the DW_apb_i2c in master mode. Hardware protects against illegal values being programmed by software. This register should be programmed only with a value in the range of 1 to IC_MAX_SPEED_MODE; otherwise, hardware updates this register with the value of IC_MAX_SPEED_MODE.
0	1h RW	MASTER MODE (MASTER_MODE): This bit controls whether the DW_apb_i2c master is enabled. Software should ensure that if this bit is set to X, then bit 6 should also be set to X.

26.17.2 I2C Target Address Register (IC_TAR)—Offset 4h



26.17.3 I2C Slave Address Register (IC_SAR)—Offset 8h

The IC SAR Address Register holds the slave address when the I2C is operating as a slave.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000055h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	1	1
Reserved_10_31							IC_SAR	

Bit Range	Default & Access	Field Name (ID): Description
31:10	0b RW	Reserved_10_31: Reserved.
9:0	55h RW	IC_SAR: The IC_SAR holds the slave address when the I2C is operating as a slave. For 7-bit addressing, only IC_SAR[6:0] is used. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.17.4 I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch

Note: It is not necessary to perform any write to this register if DW_apb_i2c is enabled as an I2C slave only.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
Reserved_3_31							IC_HS_MAR	

26.17.5 I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h



Access Method

Offset: [BAR] + 14h

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000190h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
Reserved_16_31				IC_SS_SCL_HCNT				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	190h RW	Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.17.7 Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h


This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock low period count for standard speed.

Access Method

Offset: [BAR] + 18h

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 000001D6h



26.17.8 Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch

Access Method

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 0000003Ch

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IC_FS_SCL_HCNT				

Intel Atom® Processor E3800 Product Family
Datasheet
4117



Access Method

Offset: [BAR] + 20h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000082h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31					IC_FS_SCL_LCNT			

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	0082h RW	Fast Speed I2C Clock SCL Low Count Register (IC_FS_SCL_LCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.17.10 High Speed I2C Clock SCL High Count Register (IC_HS_SCL_HCNT)—Offset 24h


Access Method

Offset: [BAR] + 24h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 0000000Ch



26.17.11 High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h

Access Method

BAR Reference: [B:0, D:24, F:6] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IC_HS_SCL_LCNT				

26.17.12 I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch



Bit Range	Default & Access	Field Name (ID): Description
4	0h RO	R_TX_EMPTY: This bit is set to 1 when the transmit buffer is at or below the threshold value set in the IC_TX_TL register.
3	0h RO	R_TX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH, and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
2	0h RO	R_RX_FULL: Set when the receive buffer reaches or goes above the RX_TL threshold in the IC_RX_TL register.
1	0h RO	R_RX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
0	0h RO	R_RX_UNDER: Set if the processor attempts to read the receive buffer when it is empty by reading from the IC_DATA_CMD register.

26.17.13 I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h

These bits mask their corresponding interrupt status bits. This register is active low.

- 0 masks the interrupt
- 1 unmask the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 30h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 000008FFh

31				28				24				20				16				12				8				4				0				
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1	1	1	1	1	1	1	1	1
Reserved_12_31																																				
																												M_GEN_CALL								
																												M_START_DET								
																												M_STOP_DET								
																												M_ACTIVITY								
																												M_RX_DONE								
																												M_TX_ABORT								
Reserved_12_31																																				
																												M_RD_REQ								
																												M_TX_EMPTY								
																												M_TX_OVER								
Reserved_12_31																																				
																												M_RX_FULL								
																												M_RX_OVER								
Reserved_12_31																																				
																												M_RX_UNDER								

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	1h RW	M_GEN_CALL: See description of M_TX_EMPTY bit field.
10	0h RW	M_START_DET: See description of M_TX_EMPTY bit field.
9	0h RW	M_STOP_DET: See description of M_TX_EMPTY bit field.
8	0h RW	M_ACTIVITY: See description of M_TX_EMPTY bit field.



Bit Range	Default & Access	Field Name (ID): Description
7	1h RW	M_RX_DONE: See description of M_TX_EMPTY bit field.
6	1h RW	M_TX_ABRT: See description of M_TX_EMPTY bit field.
5	1h RW	M_RD_REQ: See description of M_TX_EMPTY bit field.
4	1h RW	M_TX_EMPTY: These bits mask their corresponding interrupt status bits in the IC_INTR_STAT register. Reset value: 12h8ff
3	1h RW	M_TX_OVER: See description of M_TX_EMPTY bit field.
2	1h RW	M_RX_FULL: See description of M_TX_EMPTY bit field.
1	1h RW	M_RX_OVER: See description of M_TX_EMPTY bit field.
0	1h RW	M_RX_UNDER: See description of M_TX_EMPTY bit field.

26.17.14 I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h

Unlike the IC_INTR_STAT register, these bits are not masked -- so they always show the true status of the DW_apb_i2c.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_12_31						GEN_CALL	START_DET	STOP_DET
						ACTIVITY	RX_DONE	TX_ABRT
						RD_REQ	TX_EMPTY	TX_OVER
							RX_FULL	RX_OVER
								RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	0h RO	GEN_CALL: Same as in reg_IC_INTR_STAT.
10	0h RO	START_DET: Same as in reg_IC_INTR_STAT.



Bit Range	Default & Access	Field Name (ID): Description
9	0h RO	STOP_DET: Same as in reg_IC_INTR_STAT.
8	0h RO	ACTIVITY: Same as in reg_IC_INTR_STAT.
7	0h RO	RX_DONE: Same as in reg_IC_INTR_STAT.
6	0h RO	TX_ABRT: Same as in reg_IC_INTR_STAT.
5	0h RO	RD_REQ: Same as in reg_IC_INTR_STAT.
4	0h RO	TX_EMPTY: Same as in reg_IC_INTR_STAT.
3	0h RO	TX_OVER: Same as in reg_IC_INTR_STAT.
2	0h RO	RX_FULL: Same as in reg_IC_INTR_STAT.
1	0h RO	RX_OVER: Same as in reg_IC_INTR_STAT.
0	0h RO	RX_UNDER: Same as in reg_IC_INTR_STAT.

26.17.15 I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000010h

Reserved_8_31																RX_TL									
31	28			24			20			16			12			8			4			0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Receive FIFO Threshold Level (RX_TL): The valid range is 0-255, with the additional restriction that hardware does not allow this value to be set to a value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.



26.17.16 I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
Reserved_8_31							TX_TL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Transmit FIFO Threshold Level (TX_TL): Controls the level of entries (or below) that trigger the TX_EMPTY interrupt (bit 4 in IC_RAW_INTR_STAT register). The valid range is 0-255, with the additional restriction that it may not be set to value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.

26.17.17 Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_INTR

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_INTR: Read this register to clear the combined interrupt, all individual interrupts, and the IC_TX_ABRT_SOURCE register. This bit does not clear hardware clearable interrupts but software clearable interrupts.



26.17.18 Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_UNDER: Read this register to clear the RX_UNDER interrupt (bit 0) of the IC_RAW_INTR_STAT register.

26.17.19 Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_OVER: Read this register to clear the RX_OVER interrupt (bit 1) of the IC_RAW_INTR_STAT register.



26.17.20 Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_OVER: Read this register to clear the TX_OVER interrupt (bit 3) of the IC_RAW_INTR_STAT register.

26.17.21 Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RD_REQ

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RD_REQ: Read this register to clear the RD_REQ interrupt (bit 5) of the IC_RAW_INTR_STAT register.



Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_ABRT: Read this register to clear the TX_ABRT interrupt (bit 6) of the IC_RAW_INTR_STAT register, and the IC_TX_ABRT_SOURCE register. This also releases the TX FIFO from the flushed/reset state, allowing more writes to the TX FIFO.

26.17.23 Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h

Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_DONE: Read this register to clear the RX_DONE interrupt (bit 7) of the IC_RAW_INTR_STAT register.



26.17.24 Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 5Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_ACTIVITY

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_ACTIVITY: Reading this register clears the ACTIVITY interrupt if the I2C is not active anymore. If the I2C module is still active on the bus, the ACTIVITY interrupt bit continues to be set. It is automatically cleared by hardware if the module is disabled and if there is no further activity on the bus. The value read from this register to get status of the ACTIVITY interrupt (bit 8) of the IC_RAW_INTR_STAT register.

26.17.25 Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_STOP_DET

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
0	0h RO	CLR_STOP_DET: Read this register to clear the STOP_DET interrupt (bit 9) of the IC_RAW_INTR_STAT register.

26.17.26 Clear START_DET Interrupt Register (IC_CLR_START_DET)—Offset 64h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 64h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
Reserved_1_31									
CIR_START_DF									

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_START_DET: Read this register to clear the START_DET interrupt (bit 10) of the IC_RAW_INTR_STAT register.

26.17.27 Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 68h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								Reserved_1_31
								CLR_GEN_CALL



Access Method

Offset: [BAR] + 6Ch

BAR Reference: [B:0, D:24, F:6] + 10h

[illegible]

26.17.29 I2C Status Register (IC_STATUS)—Offset 70h

- Bits 1 and 2 are set to 1
- Bits 3 and 4 are set to 0

- Bits 5 and 6 are set to 0

October 2018
Document Number: 538136, Rev. 3.9



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 74h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_9_31						TXFLR		

Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Transmit FIFO Level (TXFLR): Contains the number of valid data entries in the transmit FIFO.

26.17.31 I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h

This register contains the number of valid data entries in the receive FIFO buffer. The register is cleared by the following methods:

- The I2C is disabled
- Whenever there is a transmit abort caused by any of the events tracked in IC_TX_ABRT_SOURCE

The register increments whenever data is placed into the receive FIFO and decrements when data is taken from the receive FIFO.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 78h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_9_31						RXFLR		



Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Receive FIFO Level (RXFLR): Contains the number of valid data entries in the receive FIFO.

26.17.32 I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch

This register controls the amount of hold time on the SDA signal after a negative edge of SCL in both master and slave mode, in units of ic_clk period. The value programmed must be greater than the minimum hold time in each mode for the value to be implemented one cycle in master mode, seven cycles in slave mode. Writes to this register succeed only when IC_ENABLE=0. The programmed SDA hold time cannot exceed at any time the duration of the low part of scl. Therefore the programmed value cannot be larger than N_SCL_LOW-2, where N_SCL_LOW is the duration of the low part of the scl period measured in ic_clk cycles.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 7Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h


Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_16_31								IC_SDA_HOLD

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved
15:0	1h RW	IC_SDA_HOLD: Sets the required SDA hold time in units of ic_clk period.

26.17.33 I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h

This register has 16 bits that indicate the source of the TX_ABRT bit. Except for Bit 9, this register is cleared whenever the IC_CLR_TX_ABRT register or the IC_CLR_INTR register is read. To clear Bit 9, the source of the ABRT_SBYTE_NORSTRT must be fixed first; RESTART must be enabled (IC_CON[5]=1), the SPECIAL bit must be cleared (IC_TAR[11]), or the GC_OR_START bit must be cleared (IC_TAR[10]). Once the source of the ABRT_SBYTE_NORSTRT is fixed, then this bit can be cleared in the same



manner as other bits in this register. If the source of the ABRT_SBYTE_NORSTRT is not fixed before attempting to clear this bit, Bit 9 clears for one cycle and is then re-asserted.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28				24				20				16				12				8				4				0																																														
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																									
TX_FLUSH_CNT								Reserved_17_23								ABRT_USER_ABRT				ABRT_MASTER_DIS				ABRT_10B_RD_NORSTRT				ABRT_SBYTE_NORSTRT				ABRT_HS_NORSTRT				ABRT_SBYTE_ACKDET				ABRT_HS_ACKDET				ABRT_GCALL_READ				ABRT_GCALL_NOACK				ABRT_TXDATA_NOACK				ABRT_10ADDR2_NOACK				ABRT_10ADDR1_NOACK				ABRT_7B_ADDR_NOACK											
																ABRT_SLVRD_INTX				ABRT_SLV_ARBLOST				ABRT_SLVFLUSH_TXFIFO				ARB_LOST																																															

Bit Range	Default & Access	Field Name (ID): Description
31:24	0h RO	TX_FLUSH_CNT: This field preserves the TXFLR value prior to the last TX_ABRT event. It is enabled when fix_ctrl_1680 = 1. It is cleared whenever I2C is disabled.
23:17	0b RW	Reserved_17_23: Reserved
16	0h RO	ABRT_USER_ABRT: This is a master-mode only bit. Master has detected the user initiated transfer abort (IC_ENABLE[1]). It is enabled only when fix_ctrl_1680 = 1
15	0h RO	ABRT_SLVRD_INTX: 1 = When the processor side responds to a slave mode request for data to be transmitted to a remote master and user writes a 1 in CMD (bit 8) of IC_DATA_CMD register.
14	0h RO	ABRT_SLV_ARBLOST: 1 = Slave lost the bus while transmitting data to a remote master. IC_TX_ABRT_SOURCE[12] is set at the same time.
13	0h RO	ABRT_SLVFLUSH_TXFIFO: 1 = Slave has received a read command and some data exists in the TX FIFO so the slave issues a TX_ABRT interrupt to flush old data in TX FIFO.
12	0h RO	ARB_LOST: 1 = Master has lost arbitration, or if IC_TX_ABRT_SOURCE[14] is also set, then the slave transmitter has lost arbitration.
11	0h RO	ABRT_MASTER_DIS: 1 = User tries to initiate a Master operation with the Master mode disabled.
10	0h RO	ABRT_10B_RD_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the master sends a read command in 10-bit addressing mode.
9	0h RO	ABRT_SBYTE_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to send a START Byte.
8	0h RO	ABRT_HS_NORSTRT: 1 = The restart is disabled (IC_RESTART_EN bit (IC_CON[5]) = 0) and the user is trying to use the master to transfer data in High Speed mode.
7	0h RO	ABRT_SBYTE_ACKDET: 1 = Master has sent a START Byte and the START Byte was acknowledged (wrong behavior).

26.17.35 DMA Control Register (IC DMA CR)—Offset 88h

Bit Range	Default & Access	Field Name (ID): Description
0	0h RW	Generate NACK (NACK): This NACK generation only occurs when DW_apb_i2c is a slavereceiver. If this register is set to a value of 1, it can only generate a NACK after a data byte is received; hence, the data transfer is aborted and the data received is not pushed to the receive buffer. When the register is set to a value of 0, it generates NACK/ACK, depending on normal criteria. 1 = generate NACK after data byte received 0 = generate NACK/ACK normally

26.17.35 DMA Control Register (IC DMA CR)—Offset 88h

This register is only valid when DW_apb_i2c is configured with a set of DMA Controller interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist and writing to the registers address has no effect and reading from this register address will return zero. The register is used to enable the DMA Controller interface operation. There is a separate bit for transmit and receive. This can be programmed regardless of the state of IC_ENABLE.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

	31	28			24			20			16			12			8			4			0			
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
																								TDMAE	RDMAE	

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	Reserved_2_31: Reserved.
1	0h RW	Transmit DMA Enable (TDMAE): This bit enables/disables the transmit FIFO DMA channel. 0 = Transmit DMA disabled 1 = Transmit DMA enabled
0	0h RW	Receive DMA Enable (RDMAE): This bit enables/disables the receive FIFO DMA channel. 0 = Receive DMA disabled 1 = Receive DMA enabled

26.17.36 DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch

This register is only valid when the DW_apb_i2c is configured with a set of DMA interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMATDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	0h RW	Transmit Data Level (DMATDL): This bit field controls the level at which a DMA request is made by the transmit logic. It is equal to the watermark level; that is, the dma_tx_req signal is generated when the number of valid data entries in the transmit FIFO is equal to or below this field value, and TDMAE = 1.

26.17.37 I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h

This register is only valid when DW_apb_i2c is configured with a set of DMA interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 90h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMARDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.



This register controls the amount of time delay (in terms of number of ic_clk clock periods) introduced in the rising edge of SCL -- relative to SDA changing -- by holding SCL low when DW_apb_i2c services a read request while operating as a slave-transmitter. The relevant I2C requirement is tSU:DAT (note 4) as detailed in the I2C Bus Specification. This register must be programmed with a value equal to or greater than 2. **NOTE:** The length of setup time is calculated using $[(IC_SDA_SETUP - 1) * (ic_clk_period)]$, so if the user requires 10 ic_clk periods of setup time, they should program a value of 11. The IC_SDA_SETUP register is only used by the DW_apb_i2c when operating as a slave transmitter.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 94h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000064h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	64h RW	SDA Setup (SDA_SETUP): It is recommended that if the required delay is 1000ns, then for an ic_clk frequency of 10 MHz, IC_SDA_SETUP should be programmed to a value of 11.



26.17.39 I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h

The register controls whether DW_apb_i2c responds with an ACK or NACK when it receives an I2C General Call address.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_1_31								ACK_GEN_CALL

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	1h RW	ACK General Call (ACK_GEN_CALL): When set to 1, DW_apb_i2c responds with a ACK (by asserting ic_data_oe) when it receives a General Call. When set to 0, the DW_apb_i2c does not generate General Call interrupts.

26.17.40 I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch

The register is used to report the DW_apb_i2c hardware status when the IC_ENABLE register is set from 1 to 0, that is, when DW_apb_i2c is disabled.

- If IC_ENABLE has been set to 1, bits 2:1 are forced to 0, and bit 0 is forced to 1.
- If IC_ENABLE has been set to 0, bits 2:1 will only be valid as soon as bit 0 is read as 0.

NOTE = When IC_ENABLE has been written with 0, a delay occurs for bit 0 to be read as 0 because disabling the DW_apb_i2c depends on I2C bus activities.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h





Access Method

Offset: [BAR] + F4h

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00FFFFFFEh

31				28				24				20				16				12				8				4				0															
0	0	0	0	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	0	1	1	1	1	0														
Reserved_24_31								TX_BUFFER_DEPTH								RX_BUFFER_DEPTH								HADD_ENCODED_PARAMS				HAS_DMA				INTR_IO				HC_COUNT_VALUES				MAX_SPEED_MODE				APB_DATA_WIDTH			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RW	Reserved_24_31: Reserved.
23:16	ffh RO	TX_BUFFER_DEPTH: The value of this register is derived from the IC_TX_BUFFER_DEPTH coreConsultant parameter.
15:8	ffh RO	RX_BUFFER_DEPTH: The value of this register is derived from the IC_RX_BUFFER_DEPTH coreConsultant parameter.
7	1h RO	ADD_ENCODED_PARAMS: The value of this register is derived from the IC_ADD_ENCODED_PARAMS coreConsultant parameter.
6	1h RO	HAS_DMA: The value of this register is derived from the IC_HAS_DMA coreConsultant parameter.
5	1h RO	INTR_IO: The value of this register is derived from the IC_INTR_IO coreConsultant parameter.
4	0h RO	HC_COUNT_VALUES: The value of this register is derived from the IC_HC_COUNT_VALUES coreConsultant parameter.
3:2	3h RO	MAX_SPEED_MODE: The value of this register is derived from the IC_MAX_SPEED_MODE coreConsultant parameter.
1:0	2h RO	APB_DATA_WIDTH: The value of this register is derived from the APB_DATA_WIDTH coreConsultant parameter.



26.17.46 reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h

indicate if the i2c uses 133MHz or 100MHz

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 800h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								hs_source_clock

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RO	hs_source_clock: Reflects the value configured in hs_source_clock_sel in GPIODEF0. 0 -100MHz (LPT-LP compatible) 1 -133MHz (high-speed operation compatible)

26.17.47 Software Reset (RESETS)—Offset 804h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 804h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved								reset_apb reset_func

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	Reserved (reserved): Reserved.
1	0h RW	reset_apb: reset the apb domain
0	0h RW	reset_func: reset the func clock domain

26.17.48 General Purpose Register (GENERAL)—Offset 808h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 808h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 55000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	sda_mux_sel: Reserved.
30	1h RW	sda_signal_state: Reserved.
29	0h RW	scl_mux_sel: Reserved.
28	1h RW	scl_signal_state: Reserved.
27	0h RO	sda_rd_pre_drive: Reserved.
26	1h RO	sda_rd_post_drive: Reserved.
25	0h RO	scl_rd_pre_drive: Reserved.
24	1h RO	scl_rd_post_drive: Reserved.
23:10	0h RO	Reserved: Reserved
9	0h RW	i2c_fix_ctrl_1680: Control port to enable fix 9000521680,Generation of STOP condition without data transfer
8	0h RW	i2c_fix_ctrl_0770: Control port to enable fix 9000530770,Stop generating DMA requests during Tx FIFO flush conditions
7	0h RW	i2c_fix_ctrl_1699: Control port to enable fix 9000481699,Rx data is pushed to Rx FIFO only after Tx FIFO is not-empty
6	0h RW	i2c_374798_fix_disable: chicken bit for Fix for NACK bug (HSD # 374798)
5	0h RW	i2c_374609_fix_disable: chicken bit for Fix for NACK bug (HSD # 374609)

TX transaction counter

Offset: [BAR] + 818h

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RO	RSVD0: Reserved
19	0h RW	i2c_tx_ack_count_clr_overflow: SW clear of TX transaction (byte) counter
18:17	0b RO	RSVD1: Reserved
16	0h RO	i2c_tx_count_overflow: indicate there was count overflow
15:0	0h RO	i2c_tx_ack_count: indicate TX transaction count for SW to read



26.17.51 reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h

indicate TX transaction has finished write 1 to clear the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 824h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:6] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								i2c_tx_complete_intr_clr

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	i2c_tx_complete_intr_clr: indicate TX transaction has finished write 1 to clear the interrupt



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0	MULFNDEV	HEADERTYPE	LATTIMER	CACHELINE_SIZE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

26.18.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR	SIZEINDICATOR	PREFETCHABLE	TYPE	MESSAGE_SPACE				

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RW/O	Subsystem ID (SUBSYSTEMID): This register should be implemented for any function that could be instantiated more than once in a given system. The SID register in combination with the Subsystem Vendor ID register, make it possible for the operating environment to distinguish one audio subsystem from the other. This register is a Read Write Once type register.
15:0	0000h RW/O	Subsystem Vendor ID (SUBSYSTEMVENDORID): This register should be implemented for any function that could be instantiated more than once in a given system. The SVID register, in combination with the Subsystem ID register, enables the operating environment to distinguish one subsystem from the other. This register is a Read Write Once register.

26.18.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Type: PCI Configuration Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSTION_ROM_BASE								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	EXPANSION_ROM_BASE: Reserved.



26.18.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:7] + 80h

Default: 00030001h

31				28				24				20				16				12				8				4				0																			
0				0				0				0				1				1				0				0				0				0				0				0				1			
PMESUPPORT								Reserved0																VERSION								NXTCAP								POWER_CAP											

Bit Range	Default & Access	Field Name (ID): Description
31:27	00h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. - bit(11) X XXX1b - PME# can be asserted from D0. - bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. - bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. - bit(14) X 1XXXb - PME# can be asserted from D3hot. - bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the strap strap_pme_support.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.

26.18.12 PME Control and Status Register (PMECTRLSTATUS)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:24, F:7] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0				PMESTATUS	Reserved1		PMEEENABLE	Reserved2
								PMO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit (bit 8 in this register).
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.
3	1h RO	No_Soft_Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state - Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for Downstream decode on fabric ports.



Type: PCI Configuration Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
MANID								

October 2018
Document Number: 538136, Rev. 4.3



26.19 SIO I²C 6 Memory Mapped I/O Registers

Table 277. Summary of I²C 6 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"I2C Control Register (IC_CON)—Offset 0h" on page 4161	0000007Fh
4–7h	4	"I2C Target Address Register (IC_TAR)—Offset 4h" on page 4162	00001055h
8–Bh	4	"I2C Slave Address Register (IC_SAR)—Offset 8h" on page 4163	00000055h
C–Fh	4	"I2C High Speed Master Mode Code Address Register (IC_HS_MADDR)—Offset Ch" on page 4163	00000001h
10–13h	4	"I2C Rx/Tx Data Buffer and Command Register (IC_DATA_CMD)—Offset 10h" on page 4164	00000000h
14–17h	4	"Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h" on page 4165	00000190h
18–1Bh	4	"Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h" on page 4165	000001D6h
1C–1Fh	4	"Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT)—Offset 1Ch" on page 4166	0000003Ch
20–23h	4	"Fast Speed I2C Clock SCL Low Count Register (IC_FS_SCL_LCNT)—Offset 20h" on page 4167	00000082h
24–27h	4	"High Speed I2C Clock SCL High Count Register (IC_HS_SCL_HCNT)—Offset 24h" on page 4167	0000000Ch
28–2Bh	4	"High Speed I2C Clock SCL Low Count Register (IC_HS_SCL_LCNT)—Offset 28h" on page 4168	00000020h
2C–2Fh	4	"I2C Interrupt Status Register (IC_INTR_STAT)—Offset 2Ch" on page 4169	00000000h
30–33h	4	"I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h" on page 4170	000008FFh
34–37h	4	"I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)—Offset 34h" on page 4171	00000000h
38–3Bh	4	"I2C Receive FIFO Threshold Register (IC_RX_TL)—Offset 38h" on page 4172	00000010h
3C–3Fh	4	"I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch" on page 4173	00000010h
40–43h	4	"Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h" on page 4173	00000000h
44–47h	4	"Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h" on page 4174	00000000h
48–4Bh	4	"Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h" on page 4174	00000000h
4C–4Fh	4	"Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch" on page 4175	00000000h
50–53h	4	"Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h" on page 4175	00000000h
54–57h	4	"Clear TX_ABRT Interrupt Register (IC_CLR_TX_ABRT)—Offset 54h" on page 4176	00000000h
58–5Bh	4	"Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h" on page 4176	00000000h
5C–5Fh	4	"Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch" on page 4177	00000000h
60–63h	4	"Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h" on page 4177	00000000h



Table 277. Summary of I²C 6 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
64–67h	4	"Clear START_DET Interrupt Register (IC_CLR_START_DET)—Offset 64h" on page 4178	00000000h
68–6Bh	4	"Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h" on page 4178	00000000h
6C–6Fh	4	"I2C Enable Register (IC_ENABLE)—Offset 6Ch" on page 4179	00000000h
70–73h	4	"I2C Status Register (IC_STATUS)—Offset 70h" on page 4179	00000006h
74–77h	4	"I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h" on page 4180	00000000h
78–7Bh	4	"I2C Receive FIFO Level Register (IC_RXFLR)—Offset 78h" on page 4181	00000000h
7C–7Fh	4	"I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch" on page 4182	00000001h
80–83h	4	"I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h" on page 4182	00000000h
84–87h	4	"Generate Slave Data NACK Register (IC_SLV_DATA_NACK_ONLY)—Offset 84h" on page 4184	00000000h
88–8Bh	4	"DMA Control Register (IC_DMA_CR)—Offset 88h" on page 4185	00000000h
8C–8Fh	4	"DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch" on page 4185	00000000h
90–93h	4	"I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h" on page 4186	00000000h
94–97h	4	"I2C SDA Setup Register (IC_SDA_SETUP)—Offset 94h" on page 4187	00000064h
98–9Bh	4	"I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h" on page 4188	00000001h
9C–9Fh	4	"I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch" on page 4188	00000000h
A0–A3h	4	"IC_FS_SPKLEN—Offset A0h" on page 4189	00000005h
A4–A7h	4	"IC_HS_SPKLEN—Offset A4h" on page 4190	00000002h
F4–F7h	4	"Component Parameter Register 1 (IC_COMP_PARAM_1)—Offset F4h" on page 4191	00FFFFFFh
F8–FBh	4	"I2C Component Version Register (IC_COMP_VERSION)—Offset F8h" on page 4192	3131352Ah
FC–FFh	4	"I2C Component Type Register (IC_COMP_TYPE)—Offset FCh" on page 4192	44570140h
800–803h	4	"reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h" on page 4193	00000000h
804–807h	4	"Software Reset (RESETS)—Offset 804h" on page 4193	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 4194	55000000h
818–81Bh	4	"I2C_ACK_COUNT—Offset 818h" on page 4195	00000000h
820–823h	4	"I2C_TX_COMPLETE_INTR_STAT—Offset 820h" on page 4196	00000000h
824–827h	4	"reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h" on page 4197	00000000h



26.19.2 I2C Target Address Register (IC_TAR)—Offset 4h

Writes to IC_TAR succeed when one of the following conditions are true:

- DW_apb_i2c is NOT enabled (IC_ENABLE is set to 0)
-
- OR
-
- DW_apb_i2c is enabled (IC_ENABLE=1)
- AND
- DW_apb_i2c is NOT engaged in any Master (tx, rx) operation (IC_STATUS[5]=0)
- AND
- DW_apb_i2c is enabled to operate in Master mode (IC_CON[0]=1)
- AND
- There are NO entries in the TX FIFO (IC_STATUS[2]=1)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00001055h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_13_31					IC_10BITADDR_MASTER	SPECIAL		
						GC_OR_START		
					IC_TAR			

Bit Range	Default & Access	Field Name (ID): Description
31:13	0b RW	Reserved_13_31: Reserved.
12	1h RW	IC_10BITADDR_MASTER: This bit controls whether the DW_apb_i2c starts its transfers in 7-or 10-bit addressing mode when acting as a master.
11	0h RW	SPECIAL: This bit indicates whether software performs a General Call or START BYTE command. • 0 = ignore bit 10 GC_OR_START and use IC_TAR normally • 1 = perform special I2C command as specified in GC_OR_START bit
10	0h RW	GC_OR_START: If bit 11 (SPECIAL) is set to 1, then this bit indicates whether a General Call(0) or START(1) byte command is to be performed by the DW_apb_i2c.
9:0	55h RW	IC_TAR: This is the target address for any master transaction. When transmitting a General Call, these bits are ignored. To generate a START BYTE, the CPU needs to write only once into these bits.



Access Method

Offset: [BAR] + 10h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_11_31						RESTART	DAT	
						STOP		
						CMD		

Bit Range	Default & Access	Field Name (ID): Description
31:11	0b RW	Reserved_11_31: Reserved.
10	0h RW	RESTART: This bit controls whether a RESTART is issued before the byte is sent or received. This bit is available only if IC_EMPTYFIFO_HOLD_MASTER_EN is configured to 1. 1 If IC_RESTART_EN is 1, a RESTART is issued before the data is sent/received (according to the value of CMD), regardless of whether or not the transfer direction is changing from the previous command; if IC_RESTART_EN is 0, a STOP followed by a START is issued instead. 0 If IC_RESTART_EN is 1, a RESTART is issued only if the transfer direction is changing from the previous command; if IC_RESTART_EN is 0, a STOP followed by a START is issued instead.
9	0h RW	STOP: This bit determines whether STOP is generated after a data byte is sent or received.
8	0h RW	CMD: This bit controls whether a read or a write is performed. This bit does not control the direction when the DW_apb_i2c acts as a slave. It only controls the direction when it acts as a master. 1 = Read 0 = Write



Bit Range	Default & Access	Field Name (ID): Description
7:0	0h RW	DAT: This register contains the data to be transmitted or received on the I2C bus. If you are writing to this register and want to perform a read, bits 7:0 (DAT) are ignored by the DW_apb_i2c. When you read this register, however, these bits return the value of data received on the DW_apb_i2c interface.

26.19.6 Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT)—Offset 14h

This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock high-period count for standard speed.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 14h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000190h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	190h RW	Standard Speed I2C Clock SCL High Count Register (IC_SS_SCL_HCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.

26.19.7 Standard Speed I2C Clock SCL Low Count Register (IC_SS_SCL_LCNT)—Offset 18h

This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock low period count for standard speed.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 18h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 000001D6h



This register must be set before any I2C bus transaction can take place to ensure proper I/O timing. This register sets the SCL clock high-period count for fast speed. It is used in high-speed mode to send the Master Code and START BYTE or General CALL.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 0000003Ch

312824201612840																															
00000				000000				000000				000000				000000				000000				00011				11000			
Reserved_16_31																IC_FS_SCL_HCNT															

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved.
15:0	003ch RW	Fast Speed I2C Clock SCL High Count Register (IC_FS_SCL_HCNT): This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect.



This register must be set before any I2C bus transaction can take place, to ensure proper I/O timing. This register sets the SCL clock low-period count for fast speed. It is used in high-speed mode to send the Master Code and START BYTE or General CALL. The SCL High time depends on the loading of the bus. For 100pF loading, the SCL High time is 60ns; for 400pF loading, the SCL High time is 120ns. This register goes away and becomes read-only if IC_MAX_SPEED_MODE!= high. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect. The minimum valid value is 8; hardware prevents values less than this being written, and, if attempted, results in 8 being set. For designs with APB_DATA_WIDTH == 8 the order of programming is important to ensure the correct operation of the DW_apb_i2c. The lower byte must be programmed first. Then the upper byte can be programmed.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 28h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000020h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_16_31				IIC_HS_SCL_LCNT				



Bit Range	Default & Access	Field Name (ID): Description
4	0h RO	R_TX_EMPTY: This bit is set to 1 when the transmit buffer is at or below the threshold value set in the IC_TX_TL register.
3	0h RO	R_TX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH, and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
2	0h RO	R_RX_FULL: Set when the receive buffer reaches or goes above the RX_TL threshold in the IC_RX_TL register.
1	0h RO	R_RX_OVER: Set during transmit if the transmit buffer is filled to IC_TX_BUFFER_DEPTH and the processor attempts to issue another I2C command by writing to the IC_DATA_CMD register.
0	0h RO	R_RX_UNDER: Set if the processor attempts to read the receive buffer when it is empty by reading from the IC_DATA_CMD register.

26.19.13 I2C Interrupt Mask Register (IC_INTR_MASK)—Offset 30h

These bits mask their corresponding interrupt status bits. This register is active low.

- 0 masks the interrupt
- 1 unmasks the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 000008FFh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_12_31						M_GEN_CALL	M_START_DET	M_STOP_DET
						M_ACTIVITY	M_RX_DONE	M_TX_ABORT
						M_RD_REQ	M_TX_EMPTY	M_TX_OVER
						M_RX_FULL	M_RX_OVER	M_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:12	0b RW	Reserved_12_31: Reserved.
11	1h RW	M_GEN_CALL: See description of M_TX_EMPTY bit field.
10	0h RW	M_START_DET: See description of M_TX_EMPTY bit field.
9	0h RW	M_STOP_DET: See description of M_TX_EMPTY bit field.
8	0h RW	M_ACTIVITY: See description of M_TX_EMPTY bit field.

26.19.14 I2C Raw Interrupt Status Register (IC_RAW_INTR_STAT)– Offset 34h





26.19.16 I2C Transmit FIFO Threshold Register (IC_TX_TL)—Offset 3Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 3Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000010h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
Reserved_8_31							TX_TL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	10h RW	Transmit FIFO Threshold Level (TX_TL): Controls the level of entries (or below) that trigger the TX_EMPTY interrupt (bit 4 in IC_RAW_INTR_STAT register). The valid range is 0-255, with the additional restriction that it may not be set to value larger than the depth of the buffer. If an attempt is made to do that, the actual value set will be the maximum depth of the buffer.

26.19.17 Clear Combined and Individual Interrupt Register (IC_CLR_INTR)—Offset 40h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 40h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_INTR

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_INTR: Read this register to clear the combined interrupt, all individual interrupts, and the IC_TX_ABRT_SOURCE register. This bit does not clear hardware clearable interrupts but software clearable interrupts.



26.19.18 Clear RX_UNDER Interrupt Register (IC_CLR_RX_UNDER)—Offset 44h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_UNDER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_UNDER: Read this register to clear the RX_UNDER interrupt (bit 0) of the IC_RAW_INTR_STAT register.

26.19.19 Clear RX_OVER Interrupt Register (IC_CLR_RX_OVER)—Offset 48h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_OVER: Read this register to clear the RX_OVER interrupt (bit 1) of the IC_RAW_INTR_STAT register.



26.19.20 Clear TX_OVER Interrupt Register (IC_CLR_TX_OVER)—Offset 4Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_OVER

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_OVER: Read this register to clear the TX_OVER interrupt (bit 3) of the IC_RAW_INTR_STAT register.

26.19.21 Clear RD_REQ Interrupt Register (IC_CLR_RD_REQ)—Offset 50h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 50h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RD_REQ

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RD_REQ: Read this register to clear the RD_REQ interrupt (bit 5) of the IC_RAW_INTR_STAT register.



26.19.22 Clear TX_ABRT Interrupt Register (IC_CLR_TX_ABRT)—Offset 54h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_TX_ABRT

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_TX_ABRT: Read this register to clear the TX_ABRT interrupt (bit 6) of the IC_RAW_INTR_STAT register, and the IC_TX_ABRT_SOURCE register. This also releases the TX FIFO from the flushed/reset state, allowing more writes to the TX FIFO.

26.19.23 Clear RX_DONE Interrupt Register (IC_CLR_RX_DONE)—Offset 58h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_RX_DONE

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_RX_DONE: Read this register to clear the RX_DONE interrupt (bit 7) of the IC_RAW_INTR_STAT register.



26.19.24 Clear ACTIVITY Interrupt Register (IC_CLR_ACTIVITY)—Offset 5Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 5Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_ACTIVITY

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_ACTIVITY: Reading this register clears the ACTIVITY interrupt if the I2C is not active anymore. If the I2C module is still active on the bus, the ACTIVITY interrupt bit continues to be set. It is automatically cleared by hardware if the module is disabled and if there is no further activity on the bus. The value read from this register to get status of the ACTIVITY interrupt (bit 8) of the IC_RAW_INTR_STAT register.

26.19.25 Clear STOP_DET Interrupt Register (IC_CLR_STOP_DET)—Offset 60h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved_1_31								CLR_STOP_DET

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.



26.19.27 Clear GEN_CALL Interrupt Register (IC_CLR_GEN_CALL)—Offset 68h



Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	0h RO	CLR_GEN_CALL: Read this register to clear the GEN_CALL interrupt (bit 11) of IC_RAW_INTR_STAT register.

26.19.28 I2C Enable Register (IC_ENABLE)—Offset 6Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 6Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	Reserved_2_31: Reserved
1	0h WO	ABORT: Software can abort the I2C transfer by setting this bit. This bit can be set only when ENABLE = 1 and fix_ctrl_1680 = 1. The HW will clear the ABORT bit once the STOP condition has been sent.
0	0h RW	ENABLE: Controls whether the DW_apb_i2c is enabled. 0 = Disables DW_apb_i2c (TX and RX FIFOs are held in an erased state) 1 = Enables DW_apb_i2c

26.19.29 I2C Status Register (IC_STATUS)—Offset 70h


This is a read-only register used to indicate the current transfer status and FIFO status. The status register may be read at any time. None of the bits in this register request an interrupt. The following occurs when the I2C is disabled by writing 0 in bit 0 of the IC_ENABLE register:

- Bits 1 and 2 are set to 1
- Bits 3 and 4 are set to 0

When the master or slave state machines goes to idle and `ic_en=0`:

- Bits 5 and 6 are set to 0

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 70h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000006h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_7_31							SLV_ACTIVITY	
							MST_ACTIVITY	
							RFF	
							RFNE	
							TFE	
							TFNF	
							ACTIVITY	

Bit Range	Default & Access	Field Name (ID): Description
31:7	0b RW	Reserved_7_31: Reserved.
6	0h RO	Slave FSM Activity Status (SLV_ACTIVITY): When the Slave Finite State Machine (FSM) is not in the IDLE state, this bit is set.
5	0h RO	Master FSM Activity Status (MST_ACTIVITY): When the Master Finite State Machine (FSM) is not in the IDLE state, this bit is set.
4	0h RO	Receive FIFO Completely Full (RFF): When the receive FIFO is completely full, this bit is set. When the receive FIFO contains one or more empty location, this bit is cleared.
3	0h RO	Receive FIFO Not Empty (RFNE): This bit is set when the receive FIFO contains one or more entries; it is cleared when the receive FIFO is empty.
2	1h RO	Transmit FIFO Completely Empty (TFE): When the transmit FIFO is completely empty, this bit is set. When it contains one or more valid entries, this bit is cleared. This bit field does not request an interrupt.
1	1h RO	Transmit FIFO Not Full (TFNF): Set when the transmit FIFO contains one or more empty locations, and is cleared when the FIFO is full.
0	0h RO	ACTIVITY: I2C Activity Status


26.19.30 I2C Transmit FIFO Level Register (IC_TXFLR)—Offset 74h

This register contains the number of valid data entries in the transmit FIFO buffer. It is cleared whenever:

- The I2C is disabled
- There is a transmit abort -- that is, TX_ABRT bit is set in the IC_RAW_INTR_STAT register
- The slave bulk transmit mode is aborted

The register increments whenever data is placed into the transmit FIFO and decrements when data is taken from the transmit FIFO.

Access Method



Bit Range	Default & Access	Field Name (ID): Description
31:9	0b RW	Reserved_9_31: Reserved
8:0	0h RO	Receive FIFO Level (RXFLR): Contains the number of valid data entries in the receive FIFO.

26.19.32 I2C SDA Hold Time Length Register (IC_SDA_HOLD)—Offset 7Ch

This register controls the amount of hold time on the SDA signal after a negative edge of SCL in both master and slave mode, in units of ic_clk period. The value programmed must be greater than the minimum hold time in each mode for the value to be implemented one cycle in master mode, seven cycles in slave mode. Writes to this register succeed only when IC_ENABLE=0. The programmed SDA hold time cannot exceed at any time the duration of the low part of scl. Therefore the programmed value cannot be larger than N_SCL_LOW-2, where N_SCL_LOW is the duration of the low part of the scl period measured in ic_clk cycles.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 7Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_16_31								IC_SDA_HOLD

Bit Range	Default & Access	Field Name (ID): Description
31:16	0b RW	Reserved_16_31: Reserved
15:0	1h RW	IC_SDA_HOLD: Sets the required SDA hold time in units of ic_clk period.

26.19.33 I2C Transmit Abort Source Register (IC_TX_ABRT_SOURCE)—Offset 80h

This register has 16 bits that indicate the source of the TX_ABRT bit. Except for Bit 9, this register is cleared whenever the IC_CLR_TX_ABRT register or the IC_CLR_INTR register is read. To clear Bit 9, the source of the ABRT_SBYTE_NORSTRT must be fixed first; RESTART must be enabled (IC_CON[5]=1), the SPECIAL bit must be cleared (IC_TAR[11]), or the GC_OR_START bit must be cleared (IC_TAR[10]). Once the source of the ABRT_SBYTE_NORSTRT is fixed, then this bit can be cleared in the same



- DW_apb_i2c is disabled (IC_ENABLE[0] = 0)
- Slave part is inactive (IC_STATUS[6] = 0)

Access Method

Offset: [BAR] + 84h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								NACK



Bit Range	Default & Access	Field Name (ID): Description
0	0h RW	Generate NACK (NACK): This NACK generation only occurs when DW_apb_i2c is a slavereceiver. If this register is set to a value of 1, it can only generate a NACK after a data byte is received; hence, the data transfer is aborted and the data received is not pushed to the receive buffer. When the register is set to a value of 0, it generates NACK/ACK, depending on normal criteria. 1 = generate NACK after data byte received 0 = generate NACK/ACK normally

26.19.35 DMA Control Register (IC_DMA_CR)—Offset 88h

This register is only valid when DW_apb_i2c is configured with a set of DMA Controller interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist and writing to the registers address has no effect and reading from this register address will return zero. The register is used to enable the DMA Controller interface operation. There is a separate bit for transmit and receive. This can be programmed regardless of the state of IC_ENABLE.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 88h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RW	Reserved_2_31: Reserved.
1	0h RW	Transmit DMA Enable (TDMAE): This bit enables/disables the transmit FIFO DMA channel. 0 = Transmit DMA disabled 1 = Transmit DMA enabled
0	0h RW	Receive DMA Enable (RDMAE): This bit enables/disables the receive FIFO DMA channel. 0 = Receive DMA disabled 1 = Receive DMA enabled

26.19.36 DMA Transmit Data Level Register (IC_DMA_TDLR)—Offset 8Ch

This register is only valid when the DW_apb_i2c is configured with a set of DMA interface signals (IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMATDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	0h RW	Transmit Data Level (DMATDL): This bit field controls the level at which a DMA request is made by the transmit logic. It is equal to the watermark level; that is, the dma_tx_req signal is generated when the number of valid data entries in the transmit FIFO is equal to or below this field value, and TDMAE = 1.

26.19.37 I2C Receive Data Level Register (IC_DMA_RDLR)—Offset 90h

This register is only valid when DW_apb_i2c is configured with a set of DMA interface signals(IC_HAS_DMA = 1). When DW_apb_i2c is not configured for DMA operation, this register does not exist, writing to its address has no effect, and reading from its address returns zero.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 90h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved_8_31							DMARDL	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
7:0	0h RW	Receive Data Level (DMARDL): This bit field controls the level at which a DMA request is made by the receive logic. The watermark level = DMARDL+1; that is, dma_rx_req is generated when the number of valid data entries in the receive FIFO is equal to or more than this field value + 1, and RDMAE =1. For instance, when DMARDL is 0, then dma_rx_req is asserted when 1 or more data entries are present in the receive FIFO.

26.19.38 I2C SDA Setup Register (IC_SDA_SETUP)—Offset 94h

This register controls the amount of time delay (in terms of number of ic_clk clock periods) introduced in the rising edge of SCL -- relative to SDA changing -- by holding SCL low when DW_apb_i2c services a read request while operating as a slave-transmitter. The relevant I2C requirement is tSU:DAT (note 4) as detailed in the I2C Bus Specification. This register must be programmed with a value equal to or greater than 2. **NOTE:** The length of setup time is calculated using $[(IC_SDA_SETUP - 1) * (ic_clk_period)]$, so if the user requires 10 ic_clk periods of setup time, they should program a value of 11. The IC_SDA_SETUP register is only used by the DW_apb_i2c when operating as a slave transmitter.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 94h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000064h

	31	28	24	20	16	12	8	4	0		
	0	0	0	0	0	0	0	0	0	0	
	0	0	0	0	0	0	0	0	0	0	
	Reserved_8_31							SDA_SETUP			

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	64h RW	SDA Setup (SDA_SETUP): It is recommended that if the required delay is 1000ns, then for an ic_clk frequency of 10 MHz, IC_SDA_SETUP should be programmed to a value of 11.



26.19.39 I2C ACK General Call Register (IC_ACK_GENERAL_CALL)—Offset 98h

The register controls whether DW_apb_i2c responds with an ACK or NACK when it receives an I2C General Call address.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 98h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
Reserved_1_31								ACK_GEN_CALL

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RW	Reserved_1_31: Reserved.
0	1h RW	ACK General Call (ACK_GEN_CALL): When set to 1, DW_apb_i2c responds with a ACK (by asserting ic_data_oe) when it receives a General Call. When set to 0, the DW_apb_i2c does not generate General Call interrupts.

26.19.40 I2C Enable Status Register (IC_ENABLE_STATUS)—Offset 9Ch

The register is used to report the DW_apb_i2c hardware status when the IC_ENABLE register is set from 1 to 0, that is, when DW_apb_i2c is disabled.

- If IC_ENABLE has been set to 1, bits 2:1 are forced to 0, and bit 0 is forced to 1.
- If IC_ENABLE has been set to 0, bits 2:1 will only be valid as soon as bit 0 is read as 0.

NOTE = When IC_ENABLE has been written with 0, a delay occurs for bit 0 to be read as 0 because disabling the DW_apb_i2c depends on I2C bus activities.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h



Access Method

Offset: [BAR] + A4h

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RW	Reserved_8_31: Reserved.
7:0	2h RW	IC_HS_SPKLEN: This register must be set before any I2C bus transaction can take place to ensure stable operation. This register sets the duration, measured in ic_clk cycles, of the longest spike in the SCL or SDA lines that are filtered out by the spike suppression logic; for more information, refer to Spike Suppression on page 52. This register can be written only when the I2C interface is disabled, which corresponds to the IC_ENABLE register being set to 0. Writes at other times have no effect. The minimum valid value is 1; hardware prevents values less than this being written, and if attempted results in 2 being set.

26.19.43 Component Parameter Register 1 (IC_COMP_PARAM_1)—Offset F4h



26.19.44 I2C Component Version Register (IC_COMP_VERSION)—Offset F8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 3131352Ah

31	28	24	20	16	12	8	4	0
0	0	1	1	0	0	0	1	0
0	0	0	1	0	0	1	1	0
0	0	1	1	0	0	0	1	0
0	1	0	1	0	0	1	0	1
0	0	1	0	1	0	1	0	1
0	1	0	1	0	1	0	1	0
0	0	1	0	1	0	1	0	1

IC_COMP_VERSION

Bit Range	Default & Access	Field Name (ID): Description
31:0	3131352Ah RO	IC_COMP_VERSION: Specific values for this register are described in the Releases Table in the AMBA 2 release notes.

26.19.45 I2C Component Type Register (IC_COMP_TYPE)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 44570140h

31	28	24	20	16	12	8	4	0
0	1	0	0	0	1	0	0	0
0	1	0	0	0	1	0	0	0
0	1	0	1	0	1	1	1	0
0	0	0	0	0	0	0	0	1
0	0	0	0	1	0	1	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

IC_COMP_TYPE

Bit Range	Default & Access	Field Name (ID): Description
31:0	44570140h RO	IC_COMP_TYPE: Designware Component Type number = 0x44_57_01_40. This assigned unique hex value is constant and is derived from the two ASCII letters DW followed by a 16-bit unsigned number.



26.19.46 reg_CLOCK_PARAMS (CLOCK_PARAMS)—Offset 800h

indicate if the i2c uses 133MHz or 100MHz

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 800h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								hs_source_clock

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RO	hs_source_clock: Reflects the value configured in hs_source_clock_sel in GPIODEF0. 0 -100MHz (LPT-LP compatible) 1 -133MHz (high-speed operation compatible)

26.19.47 Software Reset (RESETS)—Offset 804h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 804h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved								reset_apb reset_func

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	Reserved (reserved): Reserved.
1	0h RW	reset_apb: reset the apb domain
0	0h RW	reset_func: reset the func clock domain



Type: Memory Mapped I/O Register
(Size: 32 bits)

BAR Type: PCI Configuration Register (Size: 32 bits)

Default: 55000000h

Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	sda_mux_sel: Reserved.
30	1h RW	sda_signal_state: Reserved.
29	0h RW	scl_mux_sel: Reserved.
28	1h RW	scl_signal_state: Reserved.
27	0h RO	sda_rd_pre_drive: Reserved.
26	1h RO	sda_rd_post_drive: Reserved.
25	0h RO	scl_rd_pre_drive: Reserved.
24	1h RO	scl_rd_post_drive: Reserved.
23:10	0h RO	Reserved: Reserved
9	0h RW	i2c_fix_ctrl_1680: Control port to enable fix 9000521680,Generation of STOP condition without data transfer
8	0h RW	i2c_fix_ctrl_0770: Control port to enable fix 9000530770,Stop generating DMA requests during Tx FIFO flush conditions
7	0h RW	i2c_fix_ctrl_1699: Control port to enable fix 9000481699,Rx data is pushed to Rx FIFO only after Tx FIFO is not-empty
6	0h RW	i2c_374798_fix_disable: chicken bit for Fix for NACK bug (HSD # 374798)
5	0h RW	i2c_374609_fix_disable: chicken bit for Fix for NACK bug (HSD # 374609)



Bit Range	Default & Access	Field Name (ID): Description
4	0h RW	i2c_tx_lastbyte_flag: SW indicates it's last byte for TX transaction (HSD # 374798)
3:0	0h RW	reserved: reserved

26.19.49 I2C ACK COUNT—Offset 818h

TX transaction counter

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 818h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0				i2c_tx_ack_count_clr_overflow	RSVD1		i2c_tx_count_overflow	
							i2c_tx_ack_count	

Bit Range	Default & Access	Field Name (ID): Description
31:20	0b RO	RSVD0: Reserved
19	0h RW	i2c_tx_ack_count_clr_overflow: SW clear of TX transaction (byte) counter
18:17	0b RO	RSVD1: Reserved
16	0h RO	i2c_tx_count_overflow: indicate there was count overflow
15:0	0h RO	i2c_tx_ack_count: indicate TX transaction count for SW to read



Access Method

Offset: [BAR] + 820h

BAR Reference: [B:0, D:24, F:7] + 10h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
Reserved									i2c_tx_complete_interrupt_mask
									i2c_tx_completion_interrupt

Intel Atom® Processor E3800 Product Family
Datasheet
4196



26.19.51 reg_I2C_TX_COMPLETE_INTR_CLR (I2C_TX_COMPLETE_INTR_CLR)—Offset 824h

indicate TX transaction has finished write 1 to clear the interrupt

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 824h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:24, F:7] + 10h


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								i2c_tx_complete_intr_clr

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	i2c_tx_complete_intr_clr: indicate TX transaction has finished write 1 to clear the interrupt

27 SIO – High Speed UART

The SoC implements two instances of high speed UART controller that support baud rates between 300 and 3686400. Hardware flow control is also supported.



27.1 Signal Descriptions

Please see [Chapter 2, “Physical Interfaces”](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal’s function

Table 278. UART 1 Interface Signals

Signal Name	Direction Plat. Power	Description
SIO_UART1_RXD	I V1P8S	High-speed UART receive data input: <i>This signal is muxed and may be used by other functions.</i>
SIO_UART1_TXD	O V1P8S	High-speed UART transmit data: <i>This signal is muxed and may be used by other functions.</i>
SIO_UART1_RTS#	O V1P8S	High-speed UART request to send: <i>This signal is muxed and may be used by other functions.</i>
SIO_UART1_CTS#	I V1P8S	High-speed UART clear to send: <i>This signal is muxed and may be used by other functions.</i>

Table 279. UART 2 Interface Signals

Signal Name	Direction Plat. Power	Description
SIO_UART2_RXD	I V1P8S	High-speed UART receive data input: <i>This signal is muxed and may be used by other functions.</i>
SIO_UART2_TXD	O V1P8S	High-speed UART transmit data: <i>This signal is muxed and may be used by other functions.</i>
SIO_UART2_RTS#	O V1P8S	High-speed UART request to send: <i>This signal is muxed and may be used by other functions.</i>
SIO_UART2_CTS#	I V1P8S	High-speed UART clear to send: <i>This signal is muxed and may be used by other functions.</i>


27.2 Features

27.2.1 UART Function

The UART transmits and receives data in bit frames as shown in Figure 126.

- Each data frame is between 7 and 12 bits long, depending on the size of data programmed and if parity and stop bits are enabled.
- The frame begins with a start bit that is represented by a high-to-low transition.
- Next, 5 to 8 bits of data are transmitted, beginning with the least significant bit. An optional parity bit follows, which is set if even parity is enabled and an odd number of ones exist within the data byte; or, if odd parity is enabled and the data byte contains an even number of ones.
- The data frame ends with one, one-and-one-half, or two stop bits (as programmed by users), which is represented by one or two successive bit periods of a logic one.

Figure 126. UART Data Transfer Flow



Each UART has a Transmit FIFO and a Receive FIFO and each holds 64 characters of data. There are two separate methods for moving data into/out of the FIFOs—Interrupts and Polling.



27.2.2 Clock and Reset

The BAUD rate generates from serial clock (**Sclock**) frequency which is based on a fixed base/system clock (**Fbase**) of 100 MHz processed through an M/N divider. M/N divider settings are found in the HSUART's PRV_CLOCK_PARAMS register. **Sclock** frequency = (Fbase*M)/N. Some useful Sclock frequencies and related M/N values are shown below:

Table 280. Sclock Frequencies from M/N Settings

M Value	N Value	Sclock
288 (0x120)	15625 (0x3D09)	1.84320 MHz
1024 (0x400)	3125 (0xC35)	32.7680 MHz
9216 (0x2400)	15625 (0x3D09)	58.9824 MHz

27.2.3 Baud Rate Generator

The baud rates for the UARTs are generated with from the serial clock frequency (Sclock) by programming the DLH and DLL registers as a divisor. The hexadecimal value of the **divisor** is (IER_DLH[7:0]<8) | RBR_THR_DLL[7:0].


Fbase is the system clock frequency in Hz (100,000,000 in decimal when the system clock frequency is 100 MHz.).

The output baud rate is as follows:

$$\text{— } \text{baud rate} = (\text{Sclock}) / (16 * \text{divisor})$$

Table 281. Baud Rates Achievable with Different DLAB Settings

DLH,DLL Divisor	DLH,DLL Divisor Hexadecimal	Baud Rate
Sclock = 1.84320 MHz		
1	0001	115200
2	0002	57600
3	0003	38400
6	0006	19200
12	000C	9600
24	0018	4800
48	0030	2400
192	00C0	600
384	0180	300
Sclock = 58.9824 MHz		
4	0004	921600
8	0008	460800
16	0010	230400
24	0018	153600
Sclock = 32.768 MHz		
8	0008	256000
16	0010	128000



27.3 Use

Each UART has a transmit FIFO and a receive FIFO, each FIFO holding 64 characters of data. Three separate methods move data into and out of the FIFOs: interrupts, DMA, and polled.

27.3.1 DMA Mode Operation

27.3.1.1 Receiver DMA

The data transfer from the HSUART to host memory is controlled by the DMA write channel. To configure the channel in write mode, channel direction in the channel control register needs to be programmed to "1". The software need to program the descriptor start address register, descriptor transfer size register, and descriptor control register before starting the channel using the channel active bit in the channel control register.

27.3.1.2 Transmit DMA

The data transfer from host memory to HSUART is controlled by DMA read channel. To configure the channel in read mode, channel direction in the channel control register needs to be programmed to "0". The software need to program the descriptor start address register, descriptor transfer size register, and descriptor control register before starting the channel using the channel active bit in the channel control register.

27.3.1.3 Removing Trailing Bytes in DMA Mode

When the number of entries in the Receive FIFO is less than its trigger level, and no additional data is received, the remaining bytes are called Trailing bytes. These are DMAed out by the DMA as it has visibility into the FIFO Occupancy register.

27.3.2 FIFO Polled-Mode Operation

With the FIFOs enabled (IIR_FCR.IID0_FIFOE bit set to 1), clearing IER_DLH[7] and IER_DLH[4:0] puts the serial port in the FIFO Polled Operation mode. Because the receiver and the transmitter are controlled separately, either one or both can be in Polled Operation mode. In this mode, software checks Receiver and Transmitter status using the Line Status Register (LSR). The processor polls the following bits for Receive and Transmit Data Service.

27.3.2.1 Receive Data Service

The processor checks data ready (LSR.DR) bit which is set when 1 or more bytes remains in the Receive FIFO or Receive Buffer Register (RBR_THR_DLL).

27.3.2.2 Transmit Data Service

The processor checks transmit data request LSR.THRE bit, which is set when the transmitter needs data.



The processor can also check transmitter empty LSR.TEMT, which is set when the Transmit FIFO or Holding register is empty.

27.3.2.3 Autoflow Control

Autoflow Control uses Clear-to-Send (nCTS) and Request-to-Send (nRTS) signals to automatically control the flow of data between the UART and external modem. When autoflow is enabled, the remote device is not allowed to send data unless the UART asserts nRTS low. If the UART de-asserts nRTS while the remote device is sending data, the remote device is allowed to send one additional byte after nRTS is deasserted. An overflow could occur if the remote device violates this rule. Likewise, the UART is not allowed to transmit data unless the remote device asserts nCTS low. This feature increases system efficiency and eliminates the possibility of a Receive FIFO Overflow error due to long interrupt latency.

Autoflow mode can be used in two ways: Full autoflow, automating both nCTS and nRTS, and half autoflow, automating only nCTS. Full Autoflow is enabled by writing a 1 to bits 1 and 5 of the Modem Control Register (MCR). Auto-nCTS-Only mode is enabled by writing a 1 to bit 5 and a 0 to bit 1 of the MCR register.

27.3.2.4 RTS (UART Output)

When in full autoflow mode, nRTS is asserted when the UART FIFO is ready to receive data from the remote transmitter. This occurs when the amount of data in the Receive FIFO is below the programmable threshold value. When the amount of data in the Receive FIFO reaches the programmable threshold, nRTS is de-asserted. It will be asserted once again when enough bytes are removed from the FIFO to lower the data level below the threshold.


27.3.2.5 CTS (UART Input)

When in Full or Half-Autoflow mode, nCTS is asserted by the remote receiver when the receiver is ready to receive data from the UART. The UART checks nCTS before sending the next byte of data and will not transmit the byte until nCTS is low. If nCTS goes high while the transfer of a byte is in progress, the transmitter will complete this byte.

27.4 Register Map

Refer to [Chapter 3, “Register Access Methods”](#) and [Chapter 4, “Mapping Address Spaces”](#) for additional information.

Figure 127.SIO - HSUART Register Map





Access Method

Offset: [B:0, D:30, F:3] + 8h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

27.5.4 Cache Line Latency Header and BIST (CLLATHEADERBIST)—Offset Ch

Access Method

Offset: [B:0, D:30, F:3] + Ch

October 2018
Document Number: 538136, Rev. 4.3



31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				MULFNDEV	HEADERTYPE			
					LATTIMER			
								CACHELINE_SIZE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

27.5.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR						SIZEINDICATOR	PREFETCHABLE	TYPE
								MESSAGE_SPACE

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.



Access Method

Offset: [B:0, D:30, F:3] + 14h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		
						PREFETCHABLE1		
						TYPE1		
						MESSAGE_SPACE1		

27.5.7 Subsystem Vendor and Subsystem ID (SUBSYSTEMID)—Offset 2Ch

Access Method

Offset: [B:0, D:30, F:3] + 2Ch

Default: 00000000h




27.5.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Offset: [B:0, D:30, F:3] + 30h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSION_ROM_BASE								

27.5.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Offset: [B:0, D:30, F:3] + 34h



October 2018
Document Number: 538136, Rev. 4.3

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.
7:0	00h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. If PM capability is disabled then this register has 00h.

27.5.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:3] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
MAX_LAT				MIN_GNT		INTPIN		INTLINE	

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a Single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to tell software which interrupt line the interrupt pin is connected to.

27.5.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:3] + 80h



Bit Range	Default & Access	Field Name (ID): Description
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit (bit 8 in this register).
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.
3	1h RO	No_Soft_Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state - Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for Downstream decode on fabric ports.

27.5.13 Manufacturer ID (MANID)—Offset F8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:3] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

MANID

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



27.6 SIO HSUART 0 Memory Mapped I/O Registers

Table 283. Summary of HSUART 1 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"Receive Buffer Register/Transmit Holding Register/Divisor Latch (Low). (RBR_THR_DLL)—Offset 0h" on page 4214	00000000h
4–7h	4	"Divisor Latch (High)/ Interrupt Enable Register. (IER_DLH)—Offset 4h" on page 4215	00000000h
8–Bh	4	"Interrupt Identification Register and FIFO Control Register. (IIR_FCR)—Offset 8h" on page 4216	00000001h
C–Fh	4	"Line Control Register (LCR)—Offset Ch" on page 4217	00000000h
10–13h	4	"Modem Control Register (MCR)—Offset 10h" on page 4218	00000000h
14–17h	4	"Line Status Register (LSR)—Offset 14h" on page 4219	00000060h
18–1Bh	4	"Modem Status Register (MSR)—Offset 18h" on page 4221	00000000h
1C–1Fh	4	"Scratchpad Register (SCR)—Offset 1Ch" on page 4222	00000000h
30–33h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 0 (SRBR_STHR0)—Offset 30h" on page 4223	00000000h
34–37h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 1 (SRBR_STHR1)—Offset 34h" on page 4224	00000000h
38–3Bh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 2 (SRBR_STHR2)—Offset 38h" on page 4224	00000000h
3C–3Fh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 3 (SRBR_STHR3)—Offset 3Ch" on page 4225	00000000h
40–43h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 4 (SRBR_STHR4)—Offset 40h" on page 4225	00000000h
44–47h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 5 (SRBR_STHR5)—Offset 44h" on page 4226	00000000h
48–4Bh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 6 (SRBR_STHR6)—Offset 48h" on page 4226	00000000h
4C–4Fh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 7 (SRBR_STHR7)—Offset 4Ch" on page 4227	00000000h
50–53h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 8 (SRBR_STHR8)—Offset 50h" on page 4227	00000000h
54–57h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 9 (SRBR_STHR9)—Offset 54h" on page 4228	00000000h
58–5Bh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 10 (SRBR_STHR10)—Offset 58h" on page 4228	00000000h
5C–5Fh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 11 (SRBR_STHR11)—Offset 5Ch" on page 4229	00000000h
60–63h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 12 (SRBR_STHR12)—Offset 60h" on page 4229	00000000h
64–67h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 13 (SRBR_STHR13)—Offset 64h" on page 4230	00000000h
68–6Bh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 14 (SRBR_STHR14)—Offset 68h" on page 4230	00000000h
6C–6Fh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 15 (SRBR_STHR15)—Offset 6Ch" on page 4231	00000000h
70–73h	4	"FIFO Access Register (FAR)—Offset 70h" on page 4231	00000000h

Table 283. Summary of HSUART 1 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
74–77h	4	"Transmit FIFO Read (TFR)—Offset 74h" on page 4232	00000000h
78–7Bh	4	"Receive FIFO Write (RFW)—Offset 78h" on page 4232	00000000h
7C–7Fh	4	"UART Status Register (USR)—Offset 7Ch" on page 4233	00000006h
80–83h	4	"Transmit FIFO Level (TFL)—Offset 80h" on page 4234	00000000h
84–87h	4	"Receive FIFO Level (RFL)—Offset 84h" on page 4234	00000000h
88–8Bh	4	"Software Reset Register (SRR)—Offset 88h" on page 4235	00000000h
8C–8Fh	4	"Shadow Request to Send (SRTS)—Offset 8Ch" on page 4235	00000000h
90–93h	4	"Shadow Break Control Register (SBCR)—Offset 90h" on page 4236	00000000h
94–97h	4	"Shadow DMA Mode (SDMAM)—Offset 94h" on page 4237	00000000h
98–9Bh	4	"Shadow FIFO Enable (SFE)—Offset 98h" on page 4237	00000000h
9C–9Fh	4	"Shadow Request to Send (SRTS)—Offset 8Ch" on page 4235	00000000h
A0–A3h	4	"Shadow TX Empty Trigger (STET)—Offset A0h" on page 4238	00000000h
A4–A7h	4	"Halt TX (HTX)—Offset A4h" on page 4239	00000000h
A8–ABh	4	"DMA Software Acknowledge (DMASA)—Offset A8h" on page 4239	00000000h
F4–F7h	4	"Component Parameter Register (CPR)—Offset F4h" on page 4240	00043F32h
F8–FBh	4	"UART Component Version (UCV)—Offset F8h" on page 4241	3330382Ah
FC–FFh	4	"Component Type Register (CTR)—Offset FCh" on page 4242	44570110h
800–803h	4	"Private Clock Params (PRV_CLOCK_PARAMS)—Offset 800h" on page 4242	00000000h
804–807h	4	"Software Resets (RESETS)—Offset 804h" on page 4243	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 4243	00000050h
818–81Bh	4	"UART_BYTE_COUNT—Offset 818h" on page 4244	00000000h
820–823h	4	"UART_OVERFLOW_INTR_STAT—Offset 820h" on page 4245	00000000h

27.6.1 Receive Buffer Register/Transmit Holding Register/Divisor Latch (Low). (RBR THR DLL)—Offset 0h

Register is used for different purposes depending on the mode. See description details

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0							rbr_thr_dll	



Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	rbr_thr_dll: RBR[7:0] (Receive Buffer Register) (Read Only): Data byte received on the serial input port (sin) in UART mode. The data in this register is valid only if the Data Ready (DR) bit in the Line Status Register (LCR) is set. If FIFOs are disabled (FCR[0] set to zero), the data in the RBR must be read before the next data arrives, otherwise it is overwritten, resulting in an over-run error. If FIFOs are enabled (FCR[0] set to one), this register accesses the head of the receive FIFO. If the receive FIFO is full and this register is not read before the next data character arrives, then the data already in the FIFO is preserved, but any incoming data are lost and an over-run error occurs. THR[7:0] (Transmit Holding Register) (Write Only): Data to be transmitted on the serial output port (sout) in UART mode. Data should only be written to the THR when the THR Empty (THRE) bit (LSR[5]) is set. If in non-FIFO mode or FIFOs are disabled (FCR[0] = 0) and THRE is set, writing a single character to the THR clears the THRE. Any additional writes to the THR before the THRE is set again causes the THR data to be overwritten. If in FIFO mode and FIFOs are enabled (FCR[0] = 1) and THRE is set, x number of characters of data may be written to the THR before the FIFO is full. The number x (default=16) is determined by the value of FIFO Depth that you set during configuration. Any attempt to write data when the FIFO is full results in the write data being lost. DLL[7:0] (Divisor Latch Low) (Read-Write): Lower 8 bits of a 16-bit, read/write, Divisor Latch register that contains the baud rate divisor for the UART. this register may be accessed only when the DLAB bit (LCR[7]) is set. The output baud rate is equal to the serial frequency divided by sixteen times the value of the baud rate divisor, as follows: $\text{baud rate} = (\text{serial clock freq}) / (16 * \text{divisor})$. Note that with the Divisor Latch Registers (DLL and DLH) set to zero, the baud clock is disabled and no serial communications occur. Also, once the DLL is set, at least 8 clock cycles of the slowest HSUART clock should be allowed to pass before transmitting or receiving data.

27.6.2 Divisor Latch (High)/ Interrupt Enable Register. (IER_DLH)—Offset 4h

Register bits [7:0] is used for different purposes depending on the mode. DLH (Divisor Latch High) Upper 8-bits of a 16-bit, read/write, Divisor Latch register that contains the baud rate divisor for the UART. This register may be accessed only when the DLAB bit (LCR[7]) is set. The output baud rate is equal to the serial clock frequency divided by sixteen times the value of the baud rate divisor, as follows: $\text{baud rate} = (\text{serial clock freq}) / (16 * \text{divisor})$. Note that with the Divisor Latch Registers (DLL and DLH) set to zero, the baud clock is disabled and no serial communications occur. Also, once the DLH is set, at least 8 clock cycles of the slowest HSUART clock should be allowed to pass before transmitting or receiving data.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0							PTIME_dlh7	RSVD1
							EDSSI_dlh3	ELSI_dlh2
							ETBEI_dlh1	ERBFI_dlh0

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7	0h RW	PTIME_dlh7: PTIME (PTIME) This is used to enable/disable the generation of THRE Interrupt. 0 = disabled 1 = enabled
6:4	0b RO	RSVD1: Reserved
3	0h RW	EDSSI_dlh3: EDSSI (Enable Modem Status Interrupt) This is used to enable/disable the generation of Modem Status Interrupt. This is the fourth highest priority interrupt. 0 = disabled 1 = enabled
2	0h RW	ELSI_dlh2: ELSI (Enable Line Status Interrupt) This is used to enable/disable the generation of Receiver Line Status Interrupt. This is the highest priority interrupt. 0 = disabled 1 = enabled
1	0h RW	ETBEI_dlh1: ETBEI (Enable Transmit Holding Register Empty Interrupt) This is used to enable/disable the generation of Transmitter Holding Register Empty Interrupt. This is the third highest priority interrupt. 0 = disabled 1 = enabled
0	0h RW	ERBFI_dlh0: ERBFI (Enable Received Data Available Interrupt) This is used to enable/disable the generation of Received Data Available Interrupt and the Character Timeout Interrupt (if in FIFO mode and FIFOs enabled). These are the second highest priority interrupts. 0 = disabled 1 = enabled

27.6.3 Interrupt Identification Register and FIFO Control Register. (IIR_FCR)—Offset 8h

Register is used for different purposes depending on the mode. See description details
 Interrupt ID [3:0] 0001: No Interrupt Pending 0110: Receiver Line Status (1st Priority)
 0100: Receiver Data Available (2nd Priority) 1100: Character Timeout (2nd Priority)
 0010: THR Empty (3rd Priority) 0000: Modem Status (4th Priority) 0111: Busy Detect
 Indication (5th Priority)

Access Method

Type: Memory Mapped I/O Register
 (Size: 32 bits)

Offset: [BAR] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000001h



31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:6	0h RW	FIFOE_RCVR (RCVR): FIFOE (FIFOs Enabled) This is used to indicate whether the FIFOs are enabled or disabled. 00 = disabled 11 = enabled RCVR Trigger. This is used to select the trigger level in the receiver FIFO at which the Received Data Available Interrupt is generated. In auto flow control mode it is used to determine when the rts_n signal is de-asserted. It also determines when the dma_rx_req_n signal is asserted in certain modes of operation. The following trigger levels are supported: 00 = 1 character in the FIFO 01 = FIFO full 10 = FIFO full 11 = FIFO 2 less than full
5:4	0h RW	Res_TET (TET): TX Empty Trigger. This is used to select the empty threshold level at which the THRE Interrupts are generated when the mode is active. It also determines when the dma_tx_req_n signal is asserted when in certain modes of operation. The following trigger levels are supported: 00 = FIFO empty 01 = 2 characters in the FIFO 10 = FIFO full 11 = FIFO full
3	0h RW	IID3_DMAM (DMAM): DMA Mode. Reserved
2	0h RW	IID2_XFIFOR (XFIFOR): XMIT FIFO Reset. This resets the control portion of the transmit FIFO and treats the FIFO as empty. Note that this bit is 'self-clearing'. It is not necessary to clear this bit.
1	0h RW	IID1_RFIFOR (RFIFOR): RCVR FIFO Reset. This resets the control portion of the receive FIFO and treats the FIFO as empty. Note that this bit is 'self-clearing'. It is not necessary to clear this bit.
0	1h RW	IID0_FIFO Enable (FIFOE): This enables/disables the transmit (XMIT) and receive (RCVR) FIFOs. Whenever the value of this bit is changed both the XMIT and RCVR controller portion of FIFOs is reset

27.6.4 Line Control Register (LCR)—Offset Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
RSVD0																								DLAB	Break	RSVD1	EPS	PEN	STOP	DLS					



Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RO	RSVD0: Reserved
5	0h RW	Auto Flow Control Enable (AFCE): When FIFOs are enabled and the Auto Flow Control Enable (AFCE) bit is set, 0 = Auto Flow Control Mode disabled 1 = Auto Flow Control Mode enabled Reset Value: 0x0
4	0h RW	LoopBack Bit (LoopBack): This is used to put the UART into a diagnostic mode for test purposes. If operating in UART mode (MCR[6] set to zero), data on the sout line is held high, while serial data output is looped back to the sin line, internally. In this mode all the interrupts are fully functional. Also, in loopback mode, the modem control inputs (dsr_n, cts_n, ri_n, dcd_n) are disconnected and the modem control outputs (dtr_n, rts_n, out1_n, out2_n) are looped back to the inputs, internally. Reset Value: 0x0
3	0h RW	Output2 (OUT2): This is used to directly control the user-designated Output2 (out2_n) output. The value written to this location is inverted and driven out on out2_n, that is: 0 = out2_n de-asserted (logic 1) 1 = out2_n asserted (logic 0) Note that in Loopback mode (MCR[4] set to one), the out2_n output is held inactive high while the value of this location is internally looped back to an input. Reset Value: 0x0
2	0h RW	Output1 (OUT1): This is used to directly control the user-designated Output1 (out1_n) output. The value written to this location is inverted and driven out on out1_n, that is: 0 = out1_n de-asserted (logic 1) 1 = out1_n asserted (logic 0) Note that in Loopback mode (MCR[4] set to one), the out1_n output is held inactive high while the value of this location is internally looped back to an input. Reset Value: 0x0
1	0h RW	Request to Send (RTS): This is used to directly control the Request to Send (rts_n) output. The Request To Send (rts_n) output is used to inform the modem or data set that the UART is ready to exchange data. When Auto RTS Flow Control is not enabled (MCR[5] set to zero), the rts_n signal is set low by programming MCR[1] (RTS) to a high. In Auto Flow Control, (MCR[5] set to one) and FIFOs enable (FCR[0] set to one), the rts_n output is controlled in the same way, but is also gated with the receiver FIFO threshold trigger (rts_n is inactive high when above the threshold). The rts_n signal is de-asserted when MCR[1] is set low. Note that in Loopback mode (MCR[4] set to one), the rts_n output is held inactive high while the value of this location is internally looped back to an input. Reset Value: 0x0
0	0h RW	Data Terminal Ready (DTR): This is used to directly control the Data Terminal Ready (dtr_n) output. The value written to this location is inverted and driven out on dtr_n, that is: 0 = dtr_n de-asserted (logic 1) 1 = dtr_n asserted (logic 0) The Data Terminal Ready output is used to inform the modem or data set that the UART is ready to establish communications. Note that in Loopback mode (MCR[4] set to one), the dtr_n output is held inactive high while the value of this location is internally looped back to an input. Reset Value: 0x0

27.6.6 Line Status Register (LSR)—Offset 14h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 14h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000060h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							RFE	TEMT
							THRE	BI
							FE	PE
							OE	DR

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7	0h RW	Receiver FIFO Error Bit (RFE): This bit is only relevant when FIFOs are enabled (FCR[0] set to one). This is used to indicate if there is at least one parity error, framing error, or break indication in the FIFO. 0 = no error in RX FIFO 1 = error in RX FIFO This bit is cleared when the LSR is read, the character with the error is at the top of the receiver FIFO, and there are no subsequent errors in the FIFO. Reset Value: 0x0
6	1h RW	Transmitter Empty Bit (TEMT): If FIFOs enabled (FCR[0] set to one), this bit is set whenever the Transmitter Shift Register and the FIFO are both empty. If in non-FIFO mode or FIFOs are disabled, this bit is set whenever the Transmitter Holding Register and the Transmitter Shift Register are both empty. Reset Value: 0x1
5	1h RW	Transmit Holding Register Empty Bit (THRE): If THRE mode is disabled (IER[7] set to zero), this bit indicates that the THR or TX FIFO is empty. This bit is set whenever data is transferred from the THR or TX FIFO to the transmitter shift register and no new data has been written to the THR or TX FIFO. This also causes a THRE Interrupt to occur, if the THRE Interrupt is enabled. If THRE mode is enabled and and FIFOs enabled (IER[7] set to one and FCR[0] set to one respectively), the functionality is switched to indicate the transmitter FIFO is full, and no longer controls THRE interrupts, which are then controlled by the FCR[5:4] threshold setting. Reset Value: 0x1
4	0h RW	Break Interrupt Bit (BI): This is used to indicate the detection of a break sequence on the serial input data. If in UART mode it is set whenever the serial input, sin, is held in a logic '0' state for longer than the sum of start time + data bits + parity + stop bits. In the FIFO mode, the character associated with the break condition is carried through the FIFO and is revealed when the character is at the top of the FIFO. Reading the LSR clears the BI bit. In the non-FIFO mode, the BI indication occurs immediately and persists until the LSR is read.
3	0h RW	Framing Error Bit (FE): This is used to indicate the occurrence of a framing error in the receiver. A framing error occurs when the receiver does not detect a valid STOP bit in the received data. In the FIFO mode, since the framing error is associated with a character received, it is revealed when the character with the framing error is at the top of the FIFO. When a framing error occurs, the UART tries to resynchronize. It does this by assuming that the error was due to the start bit of the next character and then continues receiving the other bit i.e. data, and/or parity and stop. It should be noted that the Framing Error (FE) bit (LSR[3]) is set if a break interrupt has occurred, as indicated by Break Interrupt (BI) bit (LSR[4]). 0 = no framing error 1 = framing error Reading the LSR clears the FE bit. Reset Value: 0x0
2	0h RW	Parity Error Bit (PE): This is used to indicate the occurrence of a parity error in the receiver if the Parity Enable (PEN) bit (LCR[3]) is set. In the FIFO mode, since the parity error is associated with a character received, it is revealed when the character with the parity error arrives at the top of the FIFO. It should be noted that the Parity Error (PE) bit (LSR[2]) is set if a break interrupt has occurred, as indicated by Break Interrupt (BI) bit (LSR[4]). 0 = no parity error 1 = parity error Reading the LSR clears the PE bit. Reset Value: 0x0



Bit Range	Default & Access	Field Name (ID): Description
1	0h RW	Overrun Error Bit (OE): This is used to indicate the occurrence of an overrun error. This occurs if a new data character was received before the previous data was read. In the non-FIFO mode, the OE bit is set when a new character arrives in the receiver before the previous character was read from the RBR. When this happens, the data in the RBR is overwritten. In the FIFO mode, an overrun error occurs when the FIFO is full and a new character arrives at the receiver. The data in the FIFO is retained and the data in the receive shift register is lost. 0 = no overrun error 1 = overrun error Reading the LSR clears the OE bit. Reset Value: 0x0
0	0h RW	Data Ready Bit (DR): This is used to indicate that the receiver contains at least one character in the RBR or the receiver FIFO. 0 = no data ready 1 = data ready This bit is cleared when the RBR is read in non-FIFO mode, or when the receiver FIFO is empty, in FIFO mode. Reset Value: 0x0

27.6.7 Modem Status Register (MSR)—Offset 18h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 18h


BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
RSVD0																				DCD	RI	DSR	CTS	DDCD	TERI	DDSR	DCTS								

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7	0h RW	Data Carrier Detect (DCD): This is used to indicate the current state of the modem control line dcd_n. This bit is the complement of dcd_n. When the Data Carrier Detect input (dcd_n) is asserted, it is an indication that the carrier has been detected by the modem or data set. 0 = dcd_n input is de-asserted (logic 1) 1 = dcd_n input is asserted (logic 0) In Loopback Mode (MCR[4] set to one), DCD is the same as MCR[3] (Out2). Reset Value: 0x0
6	0h RW	Ring Indicator (RI): This is used to indicate the current state of the modem control line ri_n. This bit is the complement of ri_n. When the Ring Indicator input (ri_n) is asserted it is an indication that a telephone ringing signal has been received by the modem or data set. 0 = ri_n input is de-asserted (logic 1) 1 = ri_n input is asserted (logic 0) In Loopback Mode (MCR[4] set to one), RI is the same as MCR[2] (Out1). Reset Value: 0x0



Bit Range	Default & Access	Field Name (ID): Description
5	0h RW	Data Set Ready (DSR): This is used to indicate the current state of the modem control line dsr_n. This bit is the complement of dsr_n. When the Data Set Ready input (dsr_n) is asserted it is an indication that the modem or data set is ready to establish communications with the DW_apb_uart. 0 = dsr_n input is de-asserted (logic 1) 1 = dsr_n input is asserted (logic 0) In Loopback Mode (MCR[4] set to one), DSR is the same as MCR[0] (DTR). Reset Value: 0x0
4	0h RW	Clear to Send (CTS): This is used to indicate the current state of the modem control line cts_n. This bit is the complement of cts_n. When the Clear to Send input (cts_n) is asserted, it is an indication that the modem or data set is ready to exchange data with the DW_apb_uart. 0 = cts_n input is de-asserted (logic 1) 1 = cts_n input is asserted (logic 0) In Loopback Mode (MCR[4] = 1), CTS is the same as MCR[1] (RTS). Reset Value: 0x0
3	0h RW	Delta Data Carrier Detect (DDCD): This is used to indicate that the modem control line dcd_n has changed since the last time the MSR was read. 0 = no change on dcd_n since last read of MSR 1 = change on dcd_n since last read of MSR Reading the MSR clears the DDCD bit. In Loopback Mode (MCR[4] = 1), DDCD reflects changes on MCR[3] (Out2). Note, if the DDCD bit is not set and the dcd_n signal is asserted (low) and a reset occurs (software or otherwise), then the DDCD bit is set when the reset is removed if the dcd_n signal remains asserted. Reset Value: 0x0
2	0h RW	Trailing Edge of Ring Indicator (TERI): This is used to indicate that a change on the input ri_n (from an active-low to an inactive-high state) has occurred since the last time the MSR was read. 0 = no change on ri_n since last read of MSR 1 = change on ri_n since last read of MSR Reading the MSR clears the TERI bit. In Loopback Mode (MCR[4] = 1), TERI reflects when MCR[2] (Out1) has changed state from a high to a low. Reset Value: 0x0
1	0h RW	Delta Data Set Ready (DDSR): This is used to indicate that the modem control line dsr_n has changed since the last time the MSR was read. 0 = no change on dsr_n since last read of MSR 1 = change on dsr_n since last read of MSR Reading the MSR clears the DDSR bit. In Loopback Mode (MCR[4] = 1), DDSR reflects changes on MCR[0] (DTR). Note, if the DDSR bit is not set and the dsr_n signal is asserted (low) and a reset occurs (software or otherwise), then the DDSR bit is set when the reset is removed if the dsr_n signal remains asserted. Reset Value: 0x0
0	0h RW	Delta Clear to Send (DCTS): This is used to indicate that the modem control line cts_n has changed since the last time the MSR was read. 0 = no change on cts_n since last read of MSR 1 = change on cts_n since last read of MSR Reading the MSR clears the DCTS bit. In Loopback Mode (MCR[4] = 1), DCTS reflects changes on MCR[1] (RTS). Note that if the DCTS bit is not set, the cts_n signal is asserted (low) and a reset occurs (software or otherwise), then the DCTS bit is set when the reset is removed if the cts_n signal remains asserted. Reset Value: 0x0

27.6.8 Scratchpad Register (SCR)—Offset 1Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

27.6.9 Shadow Receive Buffer Register and Shadow Transmit Holding Register 0 (SRBR, STHR0)—Offset 30h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 30h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0							rsrbr_sthr0	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr0: This is a shadow register for the RBR and has been allocated sixteen 32-bit locations to accommodate burst accesses from the master. This register contains the data byte received on the serial input port (sin) in UART mode or the serial infrared input (sir_in) in infrared mode. The data in this register is valid only if the Data Ready (DR) bit in the Line status Register (LSR) is set. If FIFOs are disabled (FCR[0] set to zero), the data in the RBR must be read before the next data arrives, otherwise it is overwritten, resulting in an overrun error. If FIFOs are enabled (FCR[0] set to one), this register accesses the head of the receive FIFO. If the receive FIFO is full and this register is not read before the next data character arrives, then the data already in the FIFO are preserved, but any incoming data are lost. An overrun error also occurs. Reset Value: 0x0



27.6.10 Shadow Receive Buffer Register and Shadow Transmit Holding Register 1 (SRBR_STHR1)—Offset 34h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr1	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr1: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.6.11 Shadow Receive Buffer Register and Shadow Transmit Holding Register 2 (SRBR_STHR2)—Offset 38h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr2	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr2: Refer to bit field description for SRBR_STHR0.srbr_sthr0.



27.6.14 Shadow Receive Buffer Register and Shadow Transmit Holding Register 5 (SRBR_STHR5)—Offset 44h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr5	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr5: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.6.15 Shadow Receive Buffer Register and Shadow Transmit Holding Register 6 (SRBR_STHR6)—Offset 48h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr6	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr6: Refer to bit field description for SRBR_STHR0.srbr_sthr0.



Access Method

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr7: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.6.17 Shadow Receive Buffer Register and Shadow Transmit Holding Register 8 (SRBR, STHR8)—Offset 50h

Access Method

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr8: Refer to bit field description for SRBR_STHR0.srbr_sthr0.



27.6.18 Shadow Receive Buffer Register and Shadow Transmit Holding Register 9 (SRBR_STHR9)—Offset 54h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr9	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr9: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.6.19 Shadow Receive Buffer Register and Shadow Transmit Holding Register 10 (SRBR_STHR10)—Offset 58h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr10	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr10: Refer to bit field description for SRBR_STHR0.srbr_sthr0.



27.6.22 Shadow Receive Buffer Register and Shadow Transmit Holding Register 13 (SRBR_STHR13)—Offset 64h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 64h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr13	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr13: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.6.23 Shadow Receive Buffer Register and Shadow Transmit Holding Register 14 (SRBR_STHR14)—Offset 68h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 68h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr14	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr14: Refer to bit field description for SRBR_STHR0.srbr_sthr0.



27.6.24 Shadow Receive Buffer Register and Shadow Transmit Holding Register 15 (SRBR_STHR15)—Offset 6Ch

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 6Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr15	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr15: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.6.25 FIFO Access Register (FAR)—Offset 70h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 70h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0								srbr_sthr

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved



Access Method

Offset: [BAR] + 74h

BAR Reference: [B:0, D:30, F:3] + 10h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	Transmit FIFO Read (tfr): These bits are only valid when FIFO access mode is enabled (FAR[0] is set to one). When FIFOs are implemented and enabled, reading this register gives the data at the top of the transmit FIFO. Each consecutive read pops the transmit FIFO and gives the next data value that is currently at the top of the FIFO. When FIFOs are not implemented or not enabled, reading this register gives the data in the THR. Reset Value: 0x0

27.6.27 Receive FIFO Write (RFW)—Offset 78h

Access Method

Offset: [BAR] + 78h

BAR Reference: [B:0, D:30, F:3] + 10h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
RSVD0																RFPE	RFPE	RFWD																	



Bit Range	Default & Access	Field Name (ID): Description
1	1h RW	Transmit FIFO Not Full (TFNF): This bit is only valid when FIFO_STAT == YES. This is used to indicate that the transmit FIFO is not full. 0 = Transmit FIFO is full 1 = Transmit FIFO is not full This bit is cleared when the TX FIFO is full. Reset Value: 0x1
0	0h RW	UART Busy (BUSY): Reserved

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 80h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								tfl

Bit Range	Default & Access	Field Name (ID): Description
31:5	0b RO	RSVD0: Reserved
4:0	0h RW	Transmit FIFO Level (tfl): This indicates the number of data entries in the transmit FIFO. Reset Value: 0x0

27.6.30 Receive FIFO Level (RFL)—Offset 84h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 84h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								rfl

Bit Range	Default & Access	Field Name (ID): Description
31:5	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Field Name (ID): Description
4:0	0h RW	Receive FIFO Level (rfl): This indicates the number of data entries in the receive FIFO. Reset Value: 0x0

27.6.31 Software Reset Register (SRR)—Offset 88h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 88h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:3	0b RO	RSVDD0: Reserved
2	0h RW	XMIT FIFO Reset (XFR): This is a shadow register for the XMIT FIFO Reset bit (FCR[2]). This can be used to remove the burden on software having to store previously written FCR values (which are pretty static) just to reset the transmit FIFO. This resets the control portion of the transmit FIFO and treats the FIFO as empty. This also de-asserts the DMA TX request and single signals when additional DMA handshaking signals are selected (DMA_EXTRA == YES). Note that this bit is 'self-clearing'. It is not necessary to clear this bit. Reset Value: 0x0
1	0h RW	RCVR FIFO Reset (RFR): This is a shadow register for the RCVR FIFO Reset bit (FCR[1]). This can be used to remove the burden on software having to store previously written FCR values (which are pretty static) just to reset the receive FIFO. This resets the control portion of the receive FIFO and treats the FIFO as empty. This also de-asserts the DMA RX request and single signals when additional DMA handshaking signals are selected (DMA_EXTRA == YES). Note that this bit is 'self-clearing'. It is not necessary to clear this bit. Reset Value: 0x0
0	0h RW	UART Reset (UR): This asynchronously resets the DW_apb_uart and synchronously removes the reset assertion. For a two clock implementation both pclk and sclk domains are reset. Reset Value: 0x0

27.6.32 Shadow Request to Send (SRTS)—Offset 8Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

27.6.33 Shadow Break Control Register (SBCR)—Offset 90h

This is a shadow register for the Break bit (LCR[6]), this can be used to remove the burden of having to performing a read modify write on the LCR. This is used to cause a break condition to be transmitted to the receiving device. If set to one the serial output is forced to the spacing (logic 0) state. When not in Loopback Mode, as determined by MCR[4], the sout line is forced low until the Break bit is cleared.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 90h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RSVD0									shb

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	Shadow Break Control Bit (sbc_b): Reserved.

27.6.36 Shadow RCVR Trigger (SRT)—Offset 9Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								st

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RO	RSVD0: Reserved
1:0	0h RW	Shadow RCVR Trigger (srt): This is a shadow register for the RCVR trigger bits (FCR[7:6]). This can be used to remove the burden of having to store the previously written value to the FCR in memory and having to mask this value so that only the RCVR trigger bit gets updated. This is used to select the trigger level in the receiver FIFO at which the Received Data Available Interrupt is generated. It also determines when the dma_rx_req_n signal is asserted when DMA Mode (FCR[3]) = 1. The following trigger levels are supported: 00 = 1 character in the FIFO 01 = FIFO full 10 = FIFO full 11 = FIFO 2 less than full Reset Value: 0x0

27.6.37 Shadow TX Empty Trigger (STET)—Offset A0h

This is a shadow register for the TX empty trigger bits (FCR[5:4]). This can be used to remove the burden of having to store the previously written value to the FCR in memory and having to mask this value so that only the TX empty trigger bit gets updated. This is used to select the empty threshold level at which the THRE Interrupts are generated when the mode is active. The following trigger levels are supported:

- 00 = FIFO empty
- 01 = 2 characters in the FIFO
- 10 = FIFO full
- 11 = FIFO full

Reset Value: 0x0

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
								RSVD0
								htx

27.6.40 Component Parameter Register (CPR)—Offset F4h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RSVD0									dma

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	dmaa: This register is use to perform a DMA software acknowledge if a transfer needs to be terminated due to an error condition. For example, if the DMA disables the channel, then the DW_apb_uart should clear its request. This causes the TX request, TX single, RX request and RX single signals to de-assert. Note that this bit is 'self-clearing'. It is not necessary to clear this bit. Reset Value: 0x0 Dependencies: Writes have no effect when DMA_EXTRA == No.

27.6.40 Component Parameter Register (CPR)—Offset F4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00043F32h

31				28				24				20				16				12				8				4				0																																			
0				0				0				0				0				0				0				0				0																																			
RSVD0								FIFO_MODE								RSVD1				DMA_EXTRA				UART_ADD_ENCODED_PARAMS				SHADOW				FIFO_STAT				FIFO_ACCESS				ADDITIONAL_FEAT				SIR_LP_MODE				SIR_MODE				THRE_MODE				AFCE_MODE				RSVD2				APB_DATA_WIDTH			

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RO	RSVD0: Reserved
23:16	4h RO	FIFO MODE (FIFO_MODE): • 0x00 = 0 • 0x01 = 16 • 0x02 = 32 • to • 0x80 = 2048 • 0x81- 0xff = reserved
15:14	0b RO	RSVD1: Reserved



Bit Range	Default & Access	Field Name (ID): Description
13	1h RO	DMA EXTRA (DMA_EXTRA): 0 = FALSE 1 = TRUE
12	1h RO	UART ADD ENCODED PARAMS (UART_ADD_ENCODED_PARAMS): 0 = FALSE, 1 = TRUE
11	1h RO	SHADOW: 0 = FALSE, 1 = TRUE
10	1h RO	FIFO STAT (FIFO_STAT): 0 = FALSE, 1 = TRUE
9	1h RO	FIFO ACCESS (FIFO_ACCESS): 0 = FALSE, 1 = TRUE
8	1h RO	ADDITIONAL FEAT (ADDITIONAL_FEAT): 0 = FALSE, 1 = TRUE
7	0h RO	SIR LP MODE (SIR_LP_MODE): 0 = FALSE, 1 = TRUE
6	0h RO	SIR MODE (SIR_MODE): 0 = FALSE, 1 = TRUE
5	1h RO	THRE MODE (THRE_MODE): 0 = FALSE, 1 = TRUE
4	1h RO	AFCE MODE (AFCE_MODE): 0 = FALSE, 1 = TRUE
3:2	0b RO	RSVD2: Reserved
1:0	2h RO	APB DATA WIDTH (APB_DATA_WIDTH): 00 = 8 bits 01 = 16 bits 10 = 32 bits 11 = reserved

27.6.41 UART Component Version (UCV)—Offset F8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 3330382Ah



31	28	24	20	16	12	8	4	0														
0	0	1	1	0	0	1	1	0	0	1	1	1	0	0	0	0	1	0	1	0	1	0
UART																						

Bit Range	Default & Access	Field Name (ID): Description
31:0	3330382ah RO	UART: ASCII value for each number in the version, followed by *. For example 32_30_31_2A represents the version 2.01*. Reset Value: See the releases table in the AMBA 2 release notes.

27.6.42 Component Type Register (CTR)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 44570110h

		31				28				24				20				16				12				8				4				0			
		0	1	0	0	0	1	0	0	0	1	0	1	1	1	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0						
		PeripheralID																																			

Bit Range	Default & Access	Field Name (ID): Description
31:0	44570110h RO	Peripheral ID (PeripheralID): This register contains the peripherals identification code. Reset Value: 0x44570110

27.6.43 Private Clock Params (PRV_CLOCK_PARAMS)—Offset 800h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 800h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0															
0				0				0				0				0				0				0				0				0				0											
clk_update				n_val																				m_val																				clk_en			



Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	clk_update: update the clock divider after seeting new m and n values
30:16	0h RW	N_VAL (n_val): n value for the m over n divider
15:1	0h RW	M_VAL (m_val): m value for the m over n divider
0	0h RW	clk_en: clk en of the m over n divider

27.6.44 Software Resets (RESETS)—Offset 804h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 804h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	Reserved (reserved): Reserved.
1	0h RW	reset_apb: reset the apb domain
0	0h RW	reset_func: reset the func clock domain

27.6.45 General Purpose Register (GENERAL)—Offset 808h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 808h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000050h






27.7 PCU PMC Memory Mapped I/O Registers

**Table 284. Summary of PCU iLB PMC Memory Mapped I/O Registers—
PMC_BASE_ADDRESS**

Offset	Size	Register ID—Description	Default Value
0h	4	"PRSTS - Power and Reset Status (PRSTS)—Offset 0h" on page 4247	00000000h
8h	4	"PM_CFG - Power Management Configuration (PMC_CFG)—Offset 8h" on page 4248	00000000h
Ch	4	"VLV_PM_STS - VLV Power Management Status (VLV_PM_STS)—Offset Ch" on page 4249	00000000h
10h	4	"MTPMC - Message to PMC (MTPMC)—Offset 10h" on page 4251	00000000h
20h	4	"General PM Configuration 1 (GEN_PMCON1)—Offset 20h" on page 4251	00004004h
24h	4	"General PM Configuration 2 (GEN_PMCON2)—Offset 24h" on page 4254	00000000h
28h	4	"MFPMC - Message from PMC (MFPMC)—Offset 28h" on page 4255	00000000h
2Ch	4	"SEC_STS - SEC Status (SEC_STS)—Offset 2Ch" on page 4256	00000000h
30h	4	"Configured Revision ID (CRID)—Offset 30h" on page 4256	00000000h
34h	4	"Function Disable (FUNC_DIS)—Offset 34h" on page 4257	00000000h
38h	4	"Function Disable 2 (FUNC_DIS_2)—Offset 38h" on page 4258	00000000h
3Ch	4	"S0ix wake enable (S0IX_WAKE_EN)—Offset 3Ch" on page 4258	00FFFFFFh
40h	4	"S0ix wake Status (S0IX_WAKE_STS)—Offset 40h" on page 4260	00000000h
44h	4	"S0ix control (S0IX_CTL)—Offset 44h" on page 4261	00000050h
48h	4	"ETR - Extended Test Mode Register (ETR)—Offset 48h" on page 4262	00230000h
50h	4	"VLT - Voltage Detect Register (VLT)—Offset 50h" on page 4263	00000000h
58h	4	"GPIO_ROUT - GPIO_ROUT register (GPIO_ROUT)—Offset 58h" on page 4263	00000000h
60h	4	"PLT_CLK_CTL_0 - Platform Clock Control 0 (PLT_CLK_CTL_0)—Offset 60h" on page 4264	00000003h
64h	4	"PLT_CLK_CTL_1 - Platform Clock Control 1 (PLT_CLK_CTL_1)—Offset 64h" on page 4265	00000003h
68h	4	"PLT_CLK_CTL_2 - Platform Clock Control 2 (PLT_CLK_CTL_2)—Offset 68h" on page 4265	00000003h
6Ch	4	"PLT_CLK_CTL_3 - Platform Clock Control 3 (PLT_CLK_CTL_3)—Offset 6Ch" on page 4266	00000003h
70h	4	"PLT_CLK_CTL_4 - Platform Clock Control 4 (PLT_CLK_CTL_4)—Offset 70h" on page 4266	00000003h
74h	4	"PLT_CLK_CTL_5 - Platform Clock Control 5 (PLT_CLK_CTL_5)—Offset 74h" on page 4267	00000003h
80h	4	"S0IR_TMR - S0I Ready Residency Timer (S0IR_TMR)—Offset 80h" on page 4268	00000000h
84h	4	"S0I1_TMR - S0I1 Residency Timer (S0I1_TMR)—Offset 84h" on page 4268	00000000h
88h	4	"S0I2_TMR - S0I2 Residency Timer (S0I2_TMR)—Offset 88h" on page 4269	00000000h
8Ch	4	"S0I3_TMR - S0I3 Residency Timer (S0I3_TMR)—Offset 8Ch" on page 4269	00000000h
90h	4	"S0_TMR - S0 Residency Timer (S0_TMR)—Offset 90h" on page 4270	00000000h
98h	4	"PSS - Power island Power Status (PSS)—Offset 98h" on page 4270	00000000h
A0h	4	"D3_STS_0 - D3 Status register 0 (D3_STS_0)—Offset A0h" on page 4271	00000000h
A4h	4	"D3_STS_1 - D3 Status register 1 (D3_STS_1)—Offset A4h" on page 4271	00000000h



Bit Range	Default & Access	Description
31:24	0b RO	Power Management Controller Product ID (PMC_PRODID) (pmc_prodid): This field communicates the Product Family of the power management functionality
23:16	0b RO	Power Management Controller Revision ID (PMC_REVID) (pmc_revid): This field communicates the implementation revision of the power management functionality.
15	0b RW	PMC Watchdog Timer Status (PMC_WDT_STS) (pmc_wdt_sts): This bit will be set to '1' when the PMC Watch Dog Timer triggers a reset. It will be cleared by a write of '1' by software.
14:12	0b RO	reserved: Reserved.
11	0b RO	Code Copied Over Status (CODE_COPIED_STS) (code_copied_sts): The SOC sets this bit when PMC code is successfully authenticated and loaded from the flash
10	0b RO	reserved (reserved1): Reserved.
9	0b RO	Code Load Timeout Status (CODE_LOAD_TO) (code_load_to): The SOC sets this bit if the loading function fails to complete within a reasonable time limit. This bit remains valid after a PMC Code load is attempted until the next global reset
8	0b RO	PMC Operational Status (PMC_OP_STS) (pmc_op_sts): The SOC sets this bit when the PMC becomes operational after completing the Code Load. BIOS must wait for this bit to be set before performing resets or sleep events. This bit remains valid after a PMC Code load until the next global reset
7	0b RW	SEC Watch Dog Timer Status (SEC_GBLRST_STS) (sec_gblrst_sts): This bit will be set to '1' when the SEC FW triggers a reset. It will be cleared by a write of '1' by software.
6	0b RW	SEC Watch Dog Timer Status (SEC_WDT_STS) (sec_wdt_sts): This bit will be set to '1' when the SEC Watch Dog Timer triggers a reset. It will be cleared by a write of '1' by software.
5	0b RW	Wake On LAN Override Wake Status (WOL_OVR_WK_STS) (wol_ovr_wk_sts): This bit gets set when integrated LAN Signals a Power Management Event AND the system is in S5. BIOS can read this status bit to determine this wake source. Software clears this bit by writing a 1 to it.
4	0b RW	PMC_HOST_WAKE_STS (PMC_HOST_WAKE_STS) (pmc_host_wake_sts): The SOC Power Management Controller sets this bit if it wakes the host for reasons other than typical host-visible wake events. This status bit provides information to BIOS that the PMC caused the wake.
3:0	0b RO	reserved2: Reserved.

27.7.2 PM_CFG - Power Management Configuration (PMC_CFG)—Offset 8h

This register contains misc. fields used to configure the SOC's power management behavior.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PMC_CFG: [PMC_BASE_ADDRESS] + 8h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved							sps	no_reboot
							sx_ent_to_en	reserved2
								timing_t581

Bit Range	Default & Access	Description
31:6	0b RO	reserved: Reserved.
5	0b RW	Shutdown Policy Select (SPS) (sps): When cleared (default) the SOC will drive INIT# in response to the shutdown Message. When set to 1, SOC will treat the shutdown message similar to receiving a CF9h I/O write, and will drive PMU_PLTRST active. . BIOS guide note: This register is reset any time PMU_PLTRST asserts.
4	0b RW	No Reboot (NO_REBOOT) (no_reboot): This bit is set when the No Reboot strap is sampled high on COREPWROK. This bit may be set or cleared by software if the strap is sampled low but may not override the strap when it indicates No Reboot. When set, the TCO timer will count down and generate the SMI# on the first timeout, but will not reboot on the second timeout.
3	0b RW	S1/3/4/5 Entry Timeout Enable (SX_ENT_TO_EN) (sx_ent_to_en): This policy bit determines whether the SOC will apply a timeout to the S1/S3/S4/S5 entry flow. If this timeout is enabled and the entry flow appears to be hung, the SOC will trigger a straight-to-S5 global reset. Encodings: 0: Timeout disabled (default) 1: Timeout enabled reset_type=RSMRST_B
2	0b RO	reserved (reserved2): Reserved.
1:0	0b RW	Timing t581 (TIMING_T581) (timing_t581): This field configures the t581 timing involved in the power down flow (CPU Power Good indication inactive to PLL Enable inactive). Encodings (all min timings): 00: 10 us (default) 01: 100 us 10: 1 ms 11: 10 ms reset_type=Resume Well Reset#

27.7.3 VLV_PM_STS - VLV Power Management Status (VLV_PM_STS)—Offset Ch

This register contains misc. fields used to record events pertaining to SOC power management. Unless otherwise indicated, all RWC bits are cleared with a write of 1 by software.

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

VLV_PM_STS: [PMC_BASE_ADDRESS] + Ch


PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h


Default: 00000000h



October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Description
23	0b RW	DRAM Initialization Scratchpad Bit (DISB) (disb): This bit does not effect hardware functionality in any way. It is provided as a scratchpad bit that is maintained through main power well resets and CF9h-initiated resets. BIOS is expected to set this bit prior to starting the DRAM initialization sequence and to clear this bit after completing the DRAM initialization sequence. BIOS can detect that a DRAM initialization sequence was interrupted by a reset by reading this bit during the boot sequence. If the bit is 1, then the DRAM initialization was interrupted. This bit is reset by the assertion of the RSMRST_B pin.
22	0b RO	RSVDO: Reserved
21	0b RO	Memory Placed in Self-Refresh (MEM_SR) (mem_sr): This bit will be set to 1 if DRAM should have remained powered and held in Self-Refresh through the last power state transition (i.e. the last time the system left S0). The scenarios where this should be the case are: - successful S3 entry and exit - successful Host partition reset without power cycle This bit will be cleared whenever the SOC begins a transition out of S0. Note: This bit should not be consulted upon wake from S1, as that state does not involve the same type of handshake or placing memory into Self-Refresh. It is assumed that software is already aware that memory context is not impacted by S1 and therefore does not need to check this bit. reset_type=global reset
20	0b RW	System Reset Status (SRS) (srs): SOC sets this bit when the PMU_RESETBUTTON_B# button is pressed. BIOS is expected to read this bit and clear it if it is set. This bit is also reset by RSMRST_B and CF9h resets. reset_type=Resume Well Reset#
19	0b RW	CPU Thermal Trip Status (CTS) (cts): This bit is set when the SOC thermal trip active while the system is in a valid state to honor the pin. This bit is also reset by RSMRST_B and CF9h resets. It is not reset by the shutdown and reboot associated with the thermal trip event. reset_type=Resume Well Reset#
18	0b RW	Minimum PMU_SLP_S4_B Assertion Width Violation Status (MS4V) (ms4v): Hardware sets this bit when the PMU_SLP_S4_B assertion width is less than the time programmed in the PMU_SLP_S4_B Minimum Assertion Width field. The SOC begins the timer when PMU_SLP_S4_B pin is asserted during S4/S5 entry, or when the RSMRST_B input is deasserted during SUS well power-up. The status bit is cleared by software writing a 1 to the bit. Note that this bit is functional regardless of the value in the PMU_SLP_S4_B Assertion Stretch Enable and the Disable-SLP_X-Stretching-After-SUS-Power-Failure bits. This bit is reset by the assertion of the RSMRST_B pin, but can be set in some cases before the default value is readable. reset_type=RSMRST_B
17	0b RO	reserved3: Reserved.
16	0b RW	COREPWROK Failure (PWR_FLR) (pwr_flr): Intel SOC sets this bit any time COREPWROK goes low if the system was in an S0 or S1 state. The bit will be cleared only by software writing a 1 back to the bit or by SUS well power loss. reset_type=global reset
15	0b RW	PME B0 S5 Disable (PME_B0_S5_DIS) (pme_b0_s5_dis): When set to '1', this bit blocks wake events from PME_B0_STS in S5, regardless of the state of PME_B0_EN. When cleared (default), wake events from PME_B0_STS are allowed in S5 if PME_B0_EN = '1'. Wakes from power states other than S5 are not affected by this policy bit. The net effect of setting PME_B0_S5_DIS = '1' is described by the truth table below: Y = Wake N = Don't wake B0 = PME_B0_EN OV = WOL Enable Override B0/OV S1/S3/S4 S5 00 N N 01 N Y (LAN only) 11 Y (all PME B0 sources) Y (LAN only) 10 Y (all PME B0 sources) N This bit is cleared by the SRTCST_B pin. reset_type=SRTCST_B
14	1b RW	SUS Well Power Failure (SUS_PWR_FLR) (sus_pwr_flr): This bit is set to '1' whenever SUS well power is lost, as indicated by RSMRST_B assertion. Software writes a 1 to this bit to clear it. This bit is in the SUS well, and defaults to '1' based on RSMRST_B assertion (not cleared by any type of reset). Implementation Note: RSMRST_B is an asynchronous set term to this bit. reset_type=RSMRST_B



Bit Range	Default & Access	Description
13	0b RW	WOL Enable Override (WOL_EN_OVRD) (wol_en_ovrd): When this bit is set to 1, the integrated LAN is enabled to wake the system from S5 regardless of the value in the PME_B0_EN bit in the GPE0a_EN register. This allows the system BIOS to enable Wake-On-LAN regardless of the policies selected through the operating system. This bit is maintained in the RTC power well, therefore permitting WOL following a surprise power failure even in cases in which the system may have been running in S0 without the PME Enables set. (Note that the LAN NVRAM configuration must support WOL after SUS power loss.) When this bit is cleared to 0, the wake-on-LAN policies are determined by OS-visible bits. This bit has no effect on wakes from S1, S3, or S4. This bit is cleared by the SRTCST_B pin reset_type=SRTCST_B
12	0b RW	Disable SLP_X Stretching After SUS Well Power Up (DIS_SLP_X_STRCH_SUS_UP) (dis_slp_x_strch_sus_up): When this bit is set to 1, all SLP_* pin stretching is disabled when powering up after a SUS well power loss. When this bit is left at 0, SLP_* stretching will be performed after SUS power failure as enabled in various other fields. Note that if this bit is a 0, SLP_* stretch timers start on SUS well power up (the SOC has no ability to count stretch time while the SUS well is powered down). Setting this bit can therefore prevent long delays after SUS power loss which may be common in mobile platforms and in manufacturing flow testing, while still allowing for the full power cycling during S3, S4 and S5 states. If the platform guarantees minimum SUS power down residence in other ways, an additional SOC-induced delay is not needed or wanted. This field is not writable when the SLP_Sx# Stretching Policy Lock-Down bit is set. This bit is cleared by the SRTCST_B pin.
11:10	0b RW	PMU_SLP_S3_B Minimum Assertion Width (SLP_S3_MIN_ASST_WDTH) (slp_s3_min_asst_wdth): This 2-bit value indicates the minimum assertion width of the PMU_SLP_S3_B signal to guarantee that the Main power supplies have been fully power-cycled. This value may be modified per platform depending on power supply capacitance, board capacitance, power failure detection circuits, etc. Settings are: 00: 60 usec 01: 1 ms 10: 50 ms 11: 2 sec This field is not writable when the SLP_Sx# Stretching Policy Lock-Down bit is set. This bit is cleared by the RSMRST_B pin. reset_type=RSMRST_B
9	0b RW	General Reset Status (GEN_RST_STS) (gen_rst_sts): This bit is set by hardware whenever PMU_PLTRST asserts for any reason other than going into a software-entered sleep state (via PM1_CNT.SLP_EN write). This bit is an optional tool to help BIOS determine when a reset might have collided with a wake from a valid sleep state. A possible usage model would be to consult and then write a '1' to clear this bit during the boot flow before determining what action to take based on reading PM1_STS.WAK_STS = '1'. If GEN_RST_STS = '1', the cold reset boot path could be followed rather than the resume path, regardless of the setting of WAK_STS. This bit does not affect SOC operation in any way, and can therefore be left set if BIOS chooses not to use it. This bit is set by global reset. reset_type=global reset
8	0b RW	RTC_reserved (rtc_reserved): reset_type=SRTCST_B
7:6	0b RW	SWSMI Rate Select (SWSMI_RATESEL) (swsmi_ratesel): This 2-bit value indicates when the SWSMI timer will time out. Valid values are: 00 1.5ms +/- 0.6ms 01 16ms +/- 4ms 10 32ms +/- 4ms 11 64ms +/- 4ms These bits are not cleared by any type of reset except SRTCST_B.
5:4	0b RW	PMU_SLP_S4_B Minimum Assertion Width (S4MAW) (s4maw): This 2-bit value indicates the minimum assertion width of the PMU_SLP_S4_B signal to guarantee that the DRAMs have been safely power-cycled. This value may be modified per platform depending on DRAM types, power supply capacitance, etc. Valid values are: - 11: 1 second - 10: 2 seconds - 01: 3 seconds - 00: 4 seconds This value is used in two ways: 1. If the PMU_SLP_S4_B assertion width is ever shorter than this time, a status bit is set for BIOS to read when S0 is entered 2. If enabled by bit 3 in this register, the hardware will prevent the PMU_SLP_S4_B signal from deasserting within this minimum time period after asserting. Note that the logic that measures this time is in the suspend power well. Therefore, when leaving a G3 state, the minimum time is measured from the deassertion of the internal suspend well reset (unless the Disable SLP_X Stretching After SUS Power Failure bit is set). This field is not writable when the SLP_Sx# Stretching Policy Lock-Down bit is set. SRTCST_B forces this field to the conservative default state (00b). reset_type=SRTCST_B



Access Method

GEN PMCON2: [PMC BASE ADDRESS] + 24h

PMC BASE ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

Bit Range	Default & Access	Description
31:19	0b RO	reserved (reserved4): Reserved.



Bit Range	Default & Access	Description
18	0b RW	SLP_Sx# Stretching Policy Lock-Down (SLPSX_STR_POL_LOCK) (slpsx_str_pol_lock): When set to 1, this bit locks down the following fields: - GEN_PMC_1.DIS_SLP_X_STRCH_SUSPF - GEN_PMC_1.SLP_S3_MIN_ASST_WDTH - GEN_PMC_1.S4MAW - GEN_PMC_1.S4ASE Those bits become read-only. This bit becomes locked when a value of 1b is written to it. Writes of 0 to this bit are always ignored. Once locked by writing 1, the only way to clear this bit is to perform a platform reset.
17:11	0b RO	reserved (reserved3): Reserved.
10	0b RW	BIOS PCI Express Enable (BIOS_PCI_EXP_EN) (bios_pci_exp_en): This bit acts as a global enable for the SCI associated with the PCI express ports. If this bit is not set, then the various PCI Express ports cannot cause the PCI_EXP_STS bit to go active.
9	0b RO	Power Button Level (PWRBTN_LVL) (pwrbtn_lvl): This read-only bit indicates the current state of the PMU_PWRBTN_B signal. 1= High, 0 = Low. The value reflected in this bit is the debounced PMU_PWRBTN_B pin value that is seen at the output of a 16ms debouncer.
8:5	0b RO	reserved (reserved1): Reserved.
4	0b RW	SMI Lock (SMI_LOCK) (smi_lock): When this bit is set, writes to the GBL_SMI_EN bit will have no effect. Once the SMI_LOCK bit is set, writes of 0 to SMI_LOCK bit will have no effect (i.e. once set, this bit can only be cleared by PMU_PLTRST).
3:2	0b RO	reserved: Reserved.
1:0	0b RW	Period SMI Select (PER_SMI_SEL) (per_smi_sel): Software sets these bits to control the rate at which the periodic SMI# is generated: 00 = 64 seconds (default), 01 = 32 seconds, 10 = 16 seconds, 11 = 8 seconds Tolerance for the timer is +/- 1 second.

27.7.7 MFPMC - Message from PMC (MFPMC)—Offset 28h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MFPMC: [PMC_BASE_ADDRESS] + 28h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

mfpmc_bits

Bit Range	Default & Access	Description
31:0	0b RW	Message from PMC (MFPMC) (mfpmc_bits): The data in this register is typically updated in response to a host write to the MTPMC register.



27.7.8 SEC_STS - SEC Status (SEC_STS)—Offset 2Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SEC_STS: [PMC_BASE_ADDRESS] + 2Ch

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved								sec_exclusion_cause

Bit Range	Default & Access	Description
31:4	0b RO	reserved: Reserved.
3:0	0b RW	SEC_EXCLUSION_CAUSE (sec_exclusion_cause): The cause associated with SeC setting requesting exclusion from power flows in SEC_EXCLUSION_REQ field. 0000b: SeC FW Fault Tolerant Initialization failed. 0001b: SeC FLASH Descriptor Override invoked. 0010b: SeC disabled using SW means (such as OEM setting). 0011b: Post-boot SeC applications not supported. 0100b: ROM BIST failure. 0101b: Fuse unit completed with unsupported request for group 1. 0110b: Invalid fuses bit at line 3 of group 1 fuses wasn't written with value 0. 0111b: DRAM Initializaiton by BIOS failed. Other values reserved.

27.7.9 Configured Revision ID (CRID)—Offset 30h

Note: Configure by Bios Code. Please contact Intel representative if you have questions on CRID support

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

CRID: [PMC_BASE_ADDRESS] + 30h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved								rid_sel



Bit Range	Default & Access	Description
31:2	0b RO	reserved: Reserved.
1:0	0b RW	RID Select(RID_SEL) (rid_sel): Software writes this field to select the Revision ID reflected in PCI config space. The decoding is: 00 - Revision ID 01 - CRID 0 10 - CRID 1 11 - CRID 2 Once written, this field can only be cleared by a platform reset. reset_type=PMU_PLTRST

27.7.10 Function Disable (FUNC_DIS)—Offset 34h

BIOS uses this register to disable specific function. Upon writing this register PMC will set the corresponding Function Disable bit in the PSF

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

FUNC_DIS: [PMC_BASE_ADDRESS] + 34h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

func_dis_bits

Bit Range	Default & Access	Description
31:0	0b RW	FUNC_DIS_BITS (func_dis_bits): When a bit is set, the corresponding function should be disabled. 31 LPSS2_F7_Disable LPSS2 Function7 (I2C#7) Disable. 1'b1: Disable 1'b0: Enable 30 LPSS2_F6_Disable LPSS2 Function6 (I2C#6) Disable. 1'b1: Disable 1'b0: Enable 29 LPSS2_F5_Disable LPSS2 Function5 (I2C#5) Disable. 1'b1: Disable 1'b0: Enable 28 LPSS2_F4_Disable LPSS2 Function4 (I2C#4) Disable. 1'b1: Disable 1'b0: Enable 27 LPSS2_F3_Disable LPSS2 Function3 (I2C#3) Disable. 1'b1: Disable 1'b0: Enable 26 LPSS2_F2_Disable LPSS2 Function2 (I2C#2) Disable. 1'b1: Disable 1'b0: Enable 25 LPSS2_F1_Disable LPSS2 Function1 (I2C#1) Disable. 1'b1: Disable 1'b0: Enable 24 LPSS2_F0_Disable LPSS2 Function0 (DMA) Disable. 1'b1: Disable 1'b0: Enable 23 PCIe_P3_Disable PCIe Port3 Disable. 1'b1: Disable 1'b0: Enable 22 PCIe_P2_Disable PCIe Port2 Disable. 1'b1: Disable 1'b0: Enable 21 PCIe_P1_Disable PCIe Port1 Disable. 1'b1: Disable 1'b0: Enable 20 PCIe_P0_Disable PCIe Port0 Disable. 1'b1: Disable 1'b0: Enable 19 Reserved2 reserved 18 USB_Disable USB2 (EHCI) Disable. 1'b1: Disable 1'b0: Enable 17 SATA_Disable SATA Disable. 1'b1: Disable 1'b0: Enable 16 LAN_Disable LAN Disable. 1'b1: Disable 1'b0: Enable 15 USH_Disable USH Disable. 1'b1: Disable 1'b0: Enable 14 OTG_Disable OTG Disable. 1'b1: Disable 1'b0: Enable 13 LPE_Disable LPE Disable. 1'b1: Disable 1'b0: Enable 12 HDA_Disable HDA Disable. 1'b1: Disable 1'b0: Enable 11 SCC_MIPI_Disable MIPI-HSI Disable. 1'b1: Disable 1'b0: Enable 10 SCC_SDCARD_Disable SDCARD Disable. 1'b1: Disable 1'b0: Enable 9 SCC_SDIO_Disable SDIO Disable. 1'b1: Disable 1'b0: Enable 8 SCC_eMMC_Disable eMMC Disable. 1'b1: Disable 1'b0: Enable 7 LPSS1_F7_Disable Reserved for LPSS1 function 7 6 LPSS1_F6_Disable Reserved for LPSS1 function 6 5 LPSS1_F5_Disable PSS1 Function5 (SPI) Disable. 1'b1: Disable 1'b0: Enable 4 LPSS1_F4_Disable LPSS1 Function4 (HSUART#2) Disable. 1'b1: Disable 1'b0: Enable 3 LPSS1_F3_Disable LPSS1 Function3 (HSUART#1) Disable. 1'b1: Disable 1'b0: Enable 2 LPSS1_F2_Disable LPSS1 Function2 (PWM#2) Disable. 1'b1: Disable 1'b0: Enable 1 LPSS1_F1_Disable LPSS1 Function1 (PWM#1) Disable. 1'b1: Disable 1'b0: Enable 0 LPSS1_F0_Disable LPSS1 Function0 (DMA) Disable. 1'b1: Disable 1'b0: Enable



27.7.11 Function Disable 2 (FUNC_DIS_2)—Offset 38h

BIOS uses this register to disable specific function. Upon writing this register PMC will set the corresponding Function Disable bit in the PSF

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

FUNC_DIS_2: [PMC_BASE_ADDRESS] + 38h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								ush_ss_phy_dis
								otg_ss_phy_dis
								smb_dis

Bit Range	Default & Access	Description
31:3	0b RO	RSVD0: Reserved
2	0b RW	USH_SS_PHY_DIS (ush_ss_phy_dis): When this bit is set, USH Super Speed PHY should be disabled.
1	0b RW	OTG_SS_PHY_DIS (otg_ss_phy_dis): When this bit is set, OTG Super Speed PHY should be disabled.
0	0b RW	SMB_DIS (smb_dis): When this bit is set, SMB function should be disabled.

27.7.12 S0ix wake enable (S0IX_WAKE_EN)—Offset 3Ch

This register contains wake enable bit per S0ix wake event. Note: Common wake events with sleep sates have their wake enables in the ACPI space.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

S0IX_WAKE_EN: [PMC_BASE_ADDRESS] + 3Ch

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00FFFFFFh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved				wake_en_23	wake_en_22	wake_en_21	wake_en_20	wake_en_19
				wake_en_18	wake_en_17	wake_en_16	wake_en_15	wake_en_14
				wake_en_13	wake_en_12	wake_en_11	wake_en_10	wake_en_9
				wake_en_8	wake_en_7	wake_en_6	wake_en_5	wake_en_4
				wake_en_3	wake_en_2	wake_en_1	wake_en_0	



Bit Range	Default & Access	Description
31:24	0b RO	Reserved (reserved): Reserved.
23	1b RW	WAKE_EN_23 (wake_en_23): wake enable bit 23 - Spare bit
22	1b RW	WAKE_EN_22 (wake_en_22): wake enable bit 22 - Spare bit
21	1b RW	WAKE_EN_21 (wake_en_21): wake enable bit 21 - Spare bit
20	1b RW	WAKE_EN_20 (wake_en_20): wake enable bit 20 - Shared IRQ from GPSS
19	1b RW	WAKE_EN_19 (wake_en_19): wake enable bit 19 - Ored dedicated IRQs from GPSC
18	1b RW	WAKE_EN_18 (wake_en_18): wake enable bit 18 - Ored dedicated IRQs from GPSS
17	1b RW	WAKE_EN_17 (wake_en_17): wake enable bit 17 - Wake LAN
16	1b RW	WAKE_EN_16 (wake_en_16): wake enable bit 16 - Pending NMI
15	1b RW	WAKE_EN_15 (wake_en_15): wake enable bit 15 - SCI
14	1b RW	WAKE_EN_14 (wake_en_14): wake enable bit 14 - SMI
13	1b RW	WAKE_EN_13 (wake_en_13): wake enable bit 13 - OTG wake
12	1b RW	WAKE_EN_12 (wake_en_12): wake enable bit 12 - AONT Si03 wake
11	1b RW	WAKE_EN_11 (wake_en_11): wake enable bit 11 - AONT Si02 wake
10	1b RW	WAKE_EN_10 (wake_en_10): wake enable bit 10 - AONT Si01 wake
9	1b RW	WAKE_EN_9 (wake_en_9): wake enable bit 9 - IOAPIC delivery status
8	1b RW	WAKE_EN_8 (wake_en_8): wake enable bit 8 - Shared IRQ from GPNC
7	1b RW	WAKE_EN_7 (wake_en_7): wake enable bit 7 - GPE from GPSS
6	1b RW	WAKE_EN_6 (wake_en_6): wake enable bit 6 - GPE from GPSC
5	1b RW	WAKE_EN_5 (wake_en_5): wake enable bit 5 - Shared IRQ from GPSC
4	1b RW	WAKE_EN_4 (wake_en_4): wake enable bit 4 - LPC Clock run
3	1b RW	WAKE_EN_3 (wake_en_3): wake enable bit 3 - SEC Timers
2	1b RW	WAKE_EN_2 (wake_en_2): wake enable bit 2 - LPE IPC



Access Method

SOIX_WAKE_STS: [PMC_BASE_ADDRESS] + 40h

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28				24				20				16				12				8				4				0																																																																																																			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																																																																																																		
reserved									wake_sts_23					wake_sts_22					wake_sts_21					wake_sts_20					wake_sts_19					wake_sts_18					wake_sts_17					wake_sts_16					wake_sts_15					wake_sts_14					wake_sts_13					wake_sts_12					wake_sts_11					wake_sts_10					wake_sts_9					wake_sts_8					wake_sts_7					wake_sts_6					wake_sts_5					wake_sts_4					wake_sts_3					wake_sts_2					wake_sts_1					wake_sts_0				

Bit Range	Default & Access	Description
31:24	0b RO	Reserved (reserved): Reserved.
23	0b RW	WAKE_STS_23 (wake_sts_23): wake status bit 23 - Spare bit
22	0b RW	WAKE_STS_22 (wake_sts_22): wake status bit 22 - Spare bit
21	0b RW	WAKE_STS_21 (wake_sts_21): wake status bit 21 - Spare bit
20	0b RW	WAKE_STS_20 (wake_sts_20): wake status bit 20- Shared IRQ from GPSS
19	0b RW	WAKE_STS_19 (wake_sts_19): wake status bit 19 - Ored dedicated IRQs from GPSC
18	0b RW	WAKE_STS_18 (wake_sts_18): wake status bit 18 - Ored dedicated IRQs from GPSS
17	0b RW	WAKE_STS_17 (wake_sts_17): wake status bit 17 - Wake LAN
16	0b RW	WAKE_STS_16 (wake_sts_16): wake status bit 16 - Pending NMI
15	0b RW	WAKE_STS_15 (wake_sts_15): wake status bit 15 - SCI



Bit Range	Default & Access	Description
14	0b RW	WAKE_STS_14 (wake_sts_14): wake status bit 14 - SMI
13	0b RW	WAKE_STS_13 (wake_sts_13): wake status bit 13 - OTG wake
12	0b RW	WAKE_STS_12 (wake_sts_12): wake status bit 12 - AONT Si03 wake
11	0b RW	WAKE_STS_11 (wake_sts_11): wake status bit 11 - AONT Si02 wake
10	0b RW	WAKE_STS_10 (wake_sts_10): wake status bit 10 - AONT Si01 wake
9	0b RW	WAKE_STS_9 (wake_sts_9): wake status bit 9 - IOAPIC delivery status
8	0b RW	WAKE_STS_8 (wake_sts_8): wake status bit 8 - Shared IRQ from GPNC
7	0b RW	WAKE_STS_7 (wake_sts_7): wake status bit 7 - GPE from GPSS
6	0b RW	WAKE_STS_6 (wake_sts_6): wake status bit 6- GPE from GPSC
5	0b RW	WAKE_STS_5 (wake_sts_5): wake status bit 5 - Shared IRQ from GPSC
4	0b RW	WAKE_STS_4 (wake_sts_4): wake status bit 4 - LPC Clock run
3	0b RW	WAKE_STS_3 (wake_sts_3): wake status bit 3 - SEC Timers
2	0b RW	WAKE_STS_2 (wake_sts_2): wake status bit 2 - LPE IPC
1	0b RW	WAKE_STS_1 (wake_sts_1): wake status bit 1 - LPE wake
0	0b RW	WAKE_STS_0 (wake_sts_0): wake status bit 0 - NFC wake

27.7.14 S0ix control (S0IX_CTL)—Offset 44h

This register contains S0ix miscellaneous controls

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

S0IX_CTL: [PMC_BASE_ADDRESS] + 44h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000050h



Bit Range	Default & Access	Description
19	0b RO	reserved (reserved1): Reserved.
18	0b RW	CF9h Without Resume Well Reset Enable (CWORWRE) (cworwre): When this bit is set, a CF9h write of 6h or Eh will not cause internal Resume Well Reset (WrsmrstB) to be asserted and thus resume well logic will maintain its state. When this bit is cleared, CF9h write of 6h or Eh will also reset resume well logic. This bit is to be used when a second reset through CF9 write is desired upon power up or after resume from low power states. This bit has to be set prior to the write to CF9 register and has to be cleared upon completing the reset. Failing to do so prevents resume well registers from being reset in the future CF9 writes. reset_type=RSMRST_B
17:16	11b RW	MAX_S0IX (MAX_S0IX (max_s0ix): Indicated the maximum S0i state SOC can go
15:0	0b RO	reserved (reserved2): Reserved.

27.7.16 VLT - Voltage Detect Register (VLT)—Offset 50h

This register reflects the Voltage detect fuses.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

VLT: [PMC BASE ADDRESS] + 50h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved							vlt_fuses	

Bit Range	Default & Access	Description
31:8	0b RO	reserved: Reserved.
7:0	0b RO	VLT Fuses (VLT_FUSES) (vlt_fuses): These bits reflects the Voltage detect fuses

27.7.17 GPIO_ROUT - GPIO_ROUT register (GPIO_ROUT)—Offset 58h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GPIO_ROUT: [PMC_BASE_ADDRESS] + 58h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC BASE ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	0b RW	GPIO Rout (GPIO_ROUT) (gpio_rout): Bits [15:0] determines GPIO SUS events rout. Bits [31:16] determines GPIO CORE events rout. Bits [1:0] determines GPIO SUS event 0. Bits [3:2] determines GPIO SUS event 1 and so on. Bits [17:16] determines GPIO CORE event 0. Bits [19:18] determines GPIO CORE event 1 and so on. If the corresponding GPIO is implemented and is set to an input, a '1' in the GP_LVL bit can be routed to cause an interrupt. If the GPIO is not set to an input, this field has no effect. * 00 No effect (or GPIO unimplemented), * 01 SMI# (if corresponding ALT_GPIO_SMI bit also set), * 10 SCI (if corresponding GPE0a_EN bit also set), * 11 Reserved If the system is in an S0-S5 state and if the GPE0a_EN bit is also set, then the GPIO can cause a Wake event, even if the GPIO is NOT routed to cause an interrupt. Exception: If the system is in S5 state due to a powerbutton override, then the GPIO's will not cause wake events. Note: Core well GPIO's are not capable of waking the system from sleep states where the core well is not powered.

27.7.18 PLT_CLK_CTL_0 - Platform Clock Control 0 (PLT_CLK_CTL_0)– Offset 60h

Access Method

PLT_CLK_CTL 0: [PMC BASE ADDRESS] + 60h

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	0	1
reserved									clk_freq	clk_ctl

Bit Range	Default & Access	Description
31:3	0b RO	reserved (reserved5): Reserved.
2	0b RW	CLK_FREQ (Clock frequency) (clk_freq): This field controls clock frequency: 0 - 25 MHz (XTAL), 1: 19.2 (PLL)
1:0	11b RW	CLK_CTL (Clock control) (clk_ctl): This field controls clock gating: 00 - gated on D3 01 - force on, 1* - force off



This register controls Platform clocks.

Type: Memory Mapped I/O Register
(Size: 32 bits)

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

Default: 00000003h

Bit Range	Default & Access	Description
31:3	0b RO	reserved (reserved5): Reserved.
2	0b RW	CLK_FREQ (Clock frequency) (clk_freq): This field controls clock frequency: 0 - 25 MHz (XTAL), 1: 19.2 (PLL)
1:0	11b RW	CLK_CTL (Clock control) (clk_ctl): This field controls clock gating: 00 - gated on D3, 01 - force on, 1* - force off

27.7.22 PLT_CLK_CTL_4 - Platform Clock Control 4 (PLT_CLK_CTL_4) – Offset 70h

This register controls Platform clocks.

Type: Memory Mapped I/O Register
(Size: 32 bits)

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000003h



Access Method

PLT CLK CTL 5: [PMC BASE ADDRESS] + 74h

PMC BASE ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000003h

Bit Range	Default & Access	Description
31:3	0b RO	reserved (reserved5): Reserved.
2	0b RW	CLK_FREQ (Clock frequency) (clk_freq): This field controls clock frequency: 0 - 25 MHz (XTAL), 1: 19.2 (PLL)
1:0	11b RW	CLK_CTL (Clock control) (clk_ctl): This field controls clock gating: 00 - gated on D3 01 - force on, 1* - force off



27.7.24 S0IR_TMR - S0I Ready Residency Timer (S0IR_TMR)—Offset 80h

This timer accumulates time spent in S0I Ready state

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

S0IR_TMR: [PMC_BASE_ADDRESS] + 80h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
rtime								

Bit Range	Default & Access	Description
31:0	0b RW	RTIME (Residency Time) (rtime): time spent in S0I Ready state, in units of 32 uS

27.7.25 S0I1_TMR - S0I1 Residency Timer (S0I1_TMR)—Offset 84h

This timer accumulates time spent in S0I1 state

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

S0I1_TMR: [PMC_BASE_ADDRESS] + 84h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
rtime								

Bit Range	Default & Access	Description
31:0	0b RW	RTIME (Residency Time) (rtime): time spent in S0I1 state, in units of 32 uS



27.7.26 S0I2_TMR - S0I2 Residency Timer (S0I2_TMR)—Offset 88h

This timer accumulates time spent in S0I2 state

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

S0I2_TMR: [PMC_BASE_ADDRESS] + 88h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
rtime								

Bit Range	Default & Access	Description
31:0	0b RW	RTIME (Residency Time) (rtime): time spent in S0I2 state, in units of 32 uS

27.7.27 S0I3_TMR - S0I3 Residency Timer (S0I3_TMR)—Offset 8Ch

This timer accumulates time spent in S0I3 state

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

S0I3_TMR: [PMC_BASE_ADDRESS] + 8Ch

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
rtime								

Bit Range	Default & Access	Description
31:0	0b RW	RTIME (Residency Time) (rtime): time spent in S0I3 state, in units of 32 uS



27.7.28 S0_TMR - S0 Residency Timer (S0_TMR)—Offset 90h

This timer accumulates time spent in S0 state

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

S0_TMR: [PMC_BASE_ADDRESS] + 90h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
rtime								

Bit Range	Default & Access	Description
31:0	0b RW	RTIME (Residency Time) (rtime): time spent in S0 state, in units of 32 uS

27.7.29 PSS - Power island Power Status (PSS)—Offset 98h

This register reflects the power status for each physical power island controlled by PMC.
note it doesnt reflect the tap override values

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

PSS: [PMC_BASE_ADDRESS] + 98h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved				pg_sts				

Bit Range	Default & Access	Description
31:18	0b RO	reserved: Reserved.
17:0	0b RO	PG_STS (POWER GATE status) (pg_sts): reflects the power gate status of all power islands 0 - power island is powered on. 1 - power island is powered off bits mapping: 0 - GBE 1 - SATA 2 - HDA 3 - SEC 4 - PCIE 5 - LPSS 6 - LPE 7 - DFX 8 - USH control 9 - USH SUS 10 - USH VCCS 11 - USH VCCA 12 - OTG control 13 - OTG VCCS 14 - OTG VCCACLK 15 - OTG VCCA 16 - USB 17 - USB SUS



27.7.30 D3_STS_0 - D3 Status register 0 (D3_STS_0)—Offset A0h

This register reflects D3 status of functions

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

D3_STS_0: [PMC_BASE_ADDRESS] + A0h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0b RO	D3_STS (D3 status) (d3_sts): reflects D3 status of the following functions. 0 - Function is in D0. 1 - Function is in D3 bits mapping: 0 - LPSS 0 function 0 1 - LPSS 0 function 1 2 - LPSS 0 function 2 3 - LPSS 0 function 3 4 - LPSS 0 function 4 5 - LPSS 0 function 5 6 - LPSS 0 function 6 7 - LPSS 0 function 7 8 - SCC function 0 9 - SCC function 1 10 - SCC function 2 11 - MIPI 12 - HDA 13 - LPE 14 - OTG 15 - USH 16 - GBE 17 - SATA 18 - USB 19 - SEC 20 - PCIE function 0 21 - PCIE function 1 22 - PCIE function 2 23 - PCIE function 3 24 - LPSS 1 function 0 25 - LPSS 1 function 1 26 - LPSS 1 function 2 27 - LPSS 1 function 3 28 - LPSS 1 function 4 29 - LPSS 1 function 5 30 - LPSS 1 function 6 31 - LPSS 1 function 7

27.7.31 D3_STS_1 - D3 Status register 1 (D3_STS_1)—Offset A4h

This register reflects D3 status of functions

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

D3_STS_1: [PMC_BASE_ADDRESS] + A4h


PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:2	0b RO	reserved: Reserved.
1:0	0b RO	D3_STS (D3 status) (d3_sts): reflects D3 status of the following functions. 0 - Function is in D0. 1 - Function is in D3 bits mapping: 0 - SMB 1 - USH Super speed PHY 2 - OTG Super speed PHY 3 - DFX



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

D3 STDBY STS 0: [PMC BASE ADDRESS] + A8h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

27.7.33 D3_STDBY_STS_1 - D3 Standby Status register 1 (D3_STDBY_STS_1)—Offset ACh

This register reflects D3 status of functions at the moment Standby Ready Message was received

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

D3_STDBY_STS_1: [PMC_BASE_ADDRESS] + ACh

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

Intel Atom® Processor E3800 Product Family
Datasheet
4272



Type: Memory Mapped I/O Register
(Size: 32 bits)

MTPMC 1: [PMC BASE ADDRESS] + B0h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC BASE ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
reserved																mtpmc				lock_exi				push_exi_en				otfr_exi_en							

Bit Range	Default & Access	Description
31:8	0b RO	reserved: Reserved.
7:3	0b RW	Message to PMC (MTPMC) (mtpmc): A write to this field causes an interrupt to the PMC. The PMC can read the contents of this register. The host must wait until the PMC has taken action on the previous write to MTPMC, as indicated by the PMC Message Full Status (PMC_MSG_1_FULL_STS) bit being cleared, before initiating another write to the MTPMC register. time spent in S0 state, in units of 32 uS
2	0b RW	LOCK EXI (lock_exi): This field locks the ush_exi_en and otg_exi_en fields. The lock is soft lock, meaning register value will be changed but FW will keep the value on internal register GP1[2] until warm reset
1	0b RW	USH_EXI_Enable (ush_exi_en): A write to this field causes an interrupt to the PMC. The PMC FW will read the contents of this register and will set pcu_ush_exi_enable_xttnfwh signal. This will prevent USH PIMA power down upon S0IX entry. The host must wait until the PMC has taken action, as indicated by the PMC Message Full Status (PMC_MSG_1_FULL_STS) bit being cleared, before initiating another write to the MTPMC register. time spent in S0 state, in units of 32 uS. This field will be copied to FW internal register and it will hold the value until global reset.
0	0b RW	OTG_EXI_Enable (otg_exi_en): A write to this field causes an interrupt to the PMC. The PMC FW will read the contents of this register and will set pcu_otg_exi_enable_xttnfwh signal. This will prevent OTG PIMA power down upon S0IX entry. The host must wait until the PMC has taken action, as indicated by the PMC Message Full Status (PMC_MSG_1_FULL_STS) bit being cleared, before initiating another write to the MTPMC register. time spent in S0 state, in units of 32 uS. This field will be copied to FW internal register and it will hold the value until global reset



27.7.35 MTPMC_2 - Message to PMC 2 (MTPMC_2)—Offset B4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MTPMC_2: [PMC_BASE_ADDRESS] + B4h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved							mtpmc	

Bit Range	Default & Access	Description
31:8	0b RO	reserved: Reserved.
7:0	0b RW	Message to PMC (MTPMC) (mtpmc): A write to this field causes an interrupt to the PMC. The PMC can read the contents of this register. The host must wait until the PMC has taken action on the previous write to MTPMC, as indicated by the PMC Message Full Status (PMC_MSG_2_FULL_STS) bit being cleared, before initiating another write to the MTPMC register. time spent in S0 state, in units of 32 uS

27.7.36 MTPMC_3 - Message to PMC 3 (MTPMC_3)—Offset B8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MTPMC_3: [PMC_BASE_ADDRESS] + B8h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved							mtpmc	

Bit Range	Default & Access	Description
31:8	0b RO	reserved: Reserved.
7:0	0b RW	Message to PMC (MTPMC) (mtpmc): A write to this field causes an interrupt to the PMC. The PMC can read the contents of this register. The host must wait until the PMC has taken action on the previous write to MTPMC, as indicated by the PMC Message Full Status (PMC_MSG_3_FULL_STS) bit being cleared, before initiating another write to the MTPMC register. time spent in S0 state, in units of 32 uS



27.7.39 GPE Level Edge mode (GPE_LEVEL_EDGE)—Offset C4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GPE_LEVEL_EDGE: [PMC_BASE_ADDRESS] + C4h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0				gpe_level_edge				

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:0	0b RW	Edge Level mode (gpe_level_edge): When set GPE is in level mode when clear GPE is in edge mode gpe_level_edge[15:8] used for GPIO Core gpe_level_edge[7:0] used for GPIO SUS

27.7.40 GPE polarity mode (GPE_POLARITY)—Offset C8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GPE_POLARITY: [PMC_BASE_ADDRESS] + C8h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0				gpe_polarity				

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:0	0b RW	Polarity (gpe_polarity): When set GPE is active high when clear GPE is active low gpe_polarity[15:8] used for GPIO Core gpe_polarity[7:0] used for GPIO SUS



27.7.41 Lock Register (LOCK)—Offset CCh

Register Field Lock bit ----- GEN_PMCON1
PME_B0_S5_DIS LOCK.Sx_WAKE GEN_PMCON1 WOL_EN_OVRD LOCK.Sx_WAKE
GEN_PMCON1 AG3E LOCK.Sx_WAKE GEN_PMCON2 BIOS_PCI_EXP_EN LOCK.PCIE
GEN_PMCON2 PER_SMI_SEL LOCK.PER_SMI_FUNC_DIS all LOCK.FUNC_DIS
FUNC_DIS_2 all LOCK.FUNC_DIS S0IX_WAKE_EN all LOCK.S0IX S0IX_CTL
S0IX_RAIL_RAMP LOCK.S0IX_ETR_IGNORE_HPET LOCK.S0IX_ETR_MAX_S0IX
LOCK.S0IX_GPIO_ROUT all LOCK.GPIO_ROUT_PLT_CLK_CTL_0 all LOCK.PLT_CLK
PLT_CLK_CTL_1 all LOCK.PLT_CLK_PLT_CLK_CTL_2 all LOCK.PLT_CLK_PLT_CLK_CTL_3
all LOCK.PLT_CLK_PLT_CLK_CTL_4 all LOCK.PLT_CLK_PLT_CLK_CTL_5 all LOCK.PLT_CLK

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

LOCK: [PMC_BASE_ADDRESS] + CCh

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0							sx_wake	pcie
							per_smi	func_dis
							s0ix	gpio_rout
							plt_clk	

Bit Range	Default & Access	Description
31:7	0b RO	RSVD0: Reserved
6	0b RW	SX_WAKE lock (sx_wake): Reserved.
5	0b RW	PCIE lock (pcie): Reserved.
4	0b RW	PER_SMI lock (per_smi): Reserved.
3	0b RW	FUNC_DIS (func_dis): Reserved.
2	0b RW	S0IX lock (s0ix): Reserved.
1	0b RW	GPIO_ROUT lock (gpio_rout): Reserved.
0	0b RW	PLT_CLK lock (plt_clk): Reserved.

27.7.42 Virtual UART register (VUART1)—Offset D0h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

VUART1: [PMC_BASE_ADDRESS] + D0h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0b RW	Virtual UART register (vuart): Reserved.

27.7.43 Virtual UART register (VUART2)—Offset D4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

VUART2: [PMC_BASE_ADDRESS] + D4h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	0b RW	Virtual UART register (vuart): Reserved.

27.7.44 Virtual UART register (VUART3)—Offset D8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

VUART3: [PMC_BASE_ADDRESS] + D8h

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Description
31:0	0b RW	Virtual UART register (vuart): Reserved.

27.7.45 Virtual UART register (VUART4)—Offset DCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

VUART4: [PMC BASE ADDRESS] + DCh

PMC_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

PMC_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 44h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:0	0b RW	Virtual UART register (vuart): Reserved.

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:4] + 4h

Default: 00100000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0h RO	Reserved0: Reserved.
30	0h RW/1C	SSE: Reserved.
29	0h RW/1C	Received Master Abort (RMA): If the completion status received from IOSF is UR, Bridge sets this bit. S/W writes a 1. to this bit to clear it. This bit will not be set for the Fabric port. This bit is not used for the Fabric Port.
28	0h RW/1C	Received Target Abort (RTA): If the completion status received from IOSF is CA, Bridge sets this bit. S/W writes a 1.1 to this bit to clear it. This bit will not be set for the fabric port. This bit is not used for the Fabric Port.
27	0h RW/1C	STA: Reserved.
26:21	00h RO	Reserved1: Reserved.
20	1h RO	Capabilities List (CAPLIST): Hardwired to 1. Indicates that the controller contains a capabilities pointer list. The first item is pointed to by looking at configuration offset 34h. If PM capability is not required, then this bit should be tied to 0.
19	0h RO	Interrupt Status (INTR_STATUS): This bit reflects state of interrupt in the device. Only when the Interrupt Disable bit in the command register is a 0 and this Interrupt Status bit is a 1, will the device.s/function.s INTx# signal be asserted. Setting the Interrupt Disable bit to a 1 has no effect on the state of this bit. This bit reflects Legacy interrupt status.
18:16	0h RO	Reserved2: Reserved.
15:11	00h RO	Reserved3: Reserved.
10	0h RW	Interrupt Disable (INTR_DISABLE): Setting this bit disables INTx assertion from Bridge. The interrupt disabled is legacy INTx# interrupt, i.e. Bridge does not send Interrupt Assert message through the IOSF SideBand Channel.
9	0h RO	Reserved4: Reserved.
8	0h RW	SERR# Enable (SERR_ENABLE): If both SERR# Enable and the Unsupported Request Reporting Enable(URRE) register are 1., the agent sets the Signaled System Error bit in the PCI Status Register and sends an ERR_NONFATAL message on the IOSF sideband interface.
7:3	00h RO	Reserved5: Reserved.
2	0h RW	Bus Master Enable (BME): If this bit is 0, Bridge does not generate any new upstream transaction on IOSF as a master.



Access Method

Offset: [B:0, D:30, F:4] + 8h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

27.8.4 Cache Line Latency Header and BIST (CLLATHEADERBIST)—Offset Ch

Access Method

Offset: [B:0, D:30, F:4] + Ch

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0				MULFNDEV	HEADERTYPE		LATTIMER	CACHELINE_SIZE



Type: PCI Configuration Register
(Size: 32 bits)

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SUBSYSTEMID					SUBSYSTEMVENDORID			

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
15:0	0000h RW/O	Subsystem Vendor ID (SUBSYSTEMVENDORID): This register should be implemented for any function that could be instantiated more than once in a given system. The SVID register, in combination with the Subsystem ID register, enables the operating environment to distinguish one subsystem from the other. This register is a Read Write Once register.

27.8.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:4] + 30h

Default: 00000000h

31	28				24				20				16				12				8				4				0		
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
EXPANSTION_ROM_BASE																															

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	EXPANSION_ROM_BASE: Reserved.

27.8.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:4] + 34h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0							CAPPTR_POWER	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Reserved0: Reserved.



Bit Range	Default & Access	Field Name (ID): Description
7:0	00h RO	Capabilities Pointer (CAPPTR_POWER): Indicates what the next capability is. This capability can be programmed to be PM Capability (0x80) if PM Capability is enabled in SB. If PM capability is disabled then this register has 00h.

27.8.10 Interrupt Register (INTERRUPTREG)—Offset 3Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:4] + 3Ch

Default: 00000100h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
MAX_LAT	MIN_GNT	Reserved0	INTPIN	INTLINE				

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Max_Lat (MAX_LAT): Value of 0 indicates device has no major requirements for the settings of latency timers.
23:16	00h RO	Min_Gnt (MIN_GNT): Value of 0 indicates device has no major requirements for the settings of latency timers.
15:12	0h RO	Reserved0: Reserved.
11:8	1h RO	Interrupt Pin (INTPIN): Each AHB IP on Bridge is a Single function device. Hence Bridge only generates INTA on IOSF SB. The Fabric on AHB Bridge appears as a Multifunction device. Interrupt Pin Value in this register is reflected from the IPIN value in the private configuration space.
7:0	00h RW	Interrupt Line (INTLINE): Bridge does not use this field directly. It is used to tell software which interrupt line the interrupt pin is connected to.

27.8.11 PowerManagement Capability ID (POWERCAPID)—Offset 80h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:4] + 80h

Default: 00030001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0
PMESUPPORT	Reserved0	VERSION	NXTCAP	POWER_CAP				



Bit Range	Default & Access	Field Name (ID): Description
31:27	00h RO	PME_Support (PMESUPPORT): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. - bit(11) X XXX1b - PME# can be asserted from D0. - bit(12) X XX1Xb - PME# can be asserted from D1. Bridge does not support this state. - bit(13) X X1XXb - PME# can be asserted from D2. Bridge does not support this state. - bit(14) X 1XXXb - PME# can be asserted from D3hot. - bit(15) 1 XXXXb - PME# can be asserted from D3cold. Bridge does not support this state. This field is taken from the strap strap_pme_support.
26:19	00h RO	Reserved0: Reserved.
18:16	3h RO	Version (VERSION): Indicates support for Revision 1.2 of the PCI Power Management Specification.
15:8	00h RO	Next Capability (NXTCAP): Points to the next capability structure. This points to NULL.
7:0	01h RO	Power Management Capability (POWER_CAP): Indicates this is power management capability.

27.8.12 PME Control and Status Register (PMECTRLSTATUS)—Offset 84h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:4] + 84h

Default: 00000008h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
Reserved0				PMESTATUS	Reserved1		PMENABLE	Reserved2
								NO_SOFT_RESET
								Reserved3
								POWERSTATE

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved0: Reserved.
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit (bit 8 in this register).
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.

27.8.13 Manufacturer ID (MANID)—Offset F8h

Bit Range	Default & Access	Field Name (ID): Description
3	1h RO	No_Soft_Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state - Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for Downstream decode on fabric ports.

27.8.13 Manufacturer ID (MANID)—Offset F8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:4] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
MANID								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.



27.9 SIO HSUART 0 Memory Mapped I/O Registers

Table 286. Summary of HSUART 1 Memory Mapped I/O Registers—BAR

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"Receive Buffer Register/Transmit Holding Register/Divisor Latch (Low). (RBR_THR_DLL)—Offset 0h" on page 4290	00000000h
4–7h	4	"Divisor Latch (High)/ Interrupt Enable Register. (IER_DLH)—Offset 4h" on page 4291	00000000h
8–Bh	4	"Interrupt Identification Register and FIFO Control Register. (IIR_FCR)—Offset 8h" on page 4292	00000001h
C–Fh	4	"Line Control Register (LCR)—Offset Ch" on page 4293	00000000h
10–13h	4	"Modem Control Register (MCR)—Offset 10h" on page 4294	00000000h
14–17h	4	"Line Status Register (LSR)—Offset 14h" on page 4295	00000060h
18–1Bh	4	"Modem Status Register (MSR)—Offset 18h" on page 4297	00000000h
1C–1Fh	4	"Scratchpad Register (SCR)—Offset 1Ch" on page 4298	00000000h
30–33h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 0 (SRBR_STHR0)—Offset 30h" on page 4299	00000000h
34–37h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 1 (SRBR_STHR1)—Offset 34h" on page 4300	00000000h
38–3Bh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 2 (SRBR_STHR2)—Offset 38h" on page 4300	00000000h
3C–3Fh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 3 (SRBR_STHR3)—Offset 3Ch" on page 4301	00000000h
40–43h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 4 (SRBR_STHR4)—Offset 40h" on page 4301	00000000h
44–47h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 5 (SRBR_STHR5)—Offset 44h" on page 4302	00000000h
48–4Bh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 6 (SRBR_STHR6)—Offset 48h" on page 4302	00000000h
4C–4Fh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 7 (SRBR_STHR7)—Offset 4Ch" on page 4303	00000000h
50–53h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 8 (SRBR_STHR8)—Offset 50h" on page 4303	00000000h
54–57h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 9 (SRBR_STHR9)—Offset 54h" on page 4304	00000000h
58–5Bh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 10 (SRBR_STHR10)—Offset 58h" on page 4304	00000000h
5C–5Fh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 11 (SRBR_STHR11)—Offset 5Ch" on page 4305	00000000h
60–63h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 12 (SRBR_STHR12)—Offset 60h" on page 4305	00000000h
64–67h	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 13 (SRBR_STHR13)—Offset 64h" on page 4306	00000000h
68–6Bh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 14 (SRBR_STHR14)—Offset 68h" on page 4306	00000000h
6C–6Fh	4	"Shadow Receive Buffer Register and Shadow Transmit Holding Register 15 (SRBR_STHR15)—Offset 6Ch" on page 4307	00000000h
70–73h	4	"FIFO Access Register (FAR)—Offset 70h" on page 4307	00000000h

Table 286. Summary of HSUART 1 Memory Mapped I/O Registers—BAR (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
74–77h	4	"Transmit FIFO Read (TFR)—Offset 74h" on page 4308	00000000h
78–7Bh	4	"Receive FIFO Write (RFW)—Offset 78h" on page 4308	00000000h
7C–7Fh	4	"UART Status Register (USR)—Offset 7Ch" on page 4309	00000006h
80–83h	4	"Transmit FIFO Level (TFL)—Offset 80h" on page 4310	00000000h
84–87h	4	"Receive FIFO Level (RFL)—Offset 84h" on page 4310	00000000h
88–8Bh	4	"Software Reset Register (SRR)—Offset 88h" on page 4311	00000000h
8C–8Fh	4	"Shadow Request to Send (SRTS)—Offset 8Ch" on page 4311	00000000h
90–93h	4	"Shadow Break Control Register (SBCR)—Offset 90h" on page 4312	00000000h
94–97h	4	"Shadow DMA Mode (SDMAM)—Offset 94h" on page 4313	00000000h
98–9Bh	4	"Shadow FIFO Enable (SFE)—Offset 98h" on page 4313	00000000h
9C–9Fh	4	"Shadow Request to Send (SRTS)—Offset 8Ch" on page 4311	00000000h
A0–A3h	4	"Shadow TX Empty Trigger (STET)—Offset A0h" on page 4314	00000000h
A4–A7h	4	"Halt TX (HTX)—Offset A4h" on page 4315	00000000h
A8–ABh	4	"DMA Software Acknowledge (DMASA)—Offset A8h" on page 4315	00000000h
F4–F7h	4	"Component Parameter Register (CPR)—Offset F4h" on page 4316	00043F32h
F8–FBh	4	"UART Component Version (UCV)—Offset F8h" on page 4317	3330382Ah
FC–FFh	4	"Component Type Register (CTR)—Offset FCh" on page 4318	44570110h
800–803h	4	"Private Clock Params (PRV_CLOCK_PARAMS)—Offset 800h" on page 4318	00000000h
804–807h	4	"Software Resets (RESETS)—Offset 804h" on page 4319	00000000h
808–80Bh	4	"General Purpose Register (GENERAL)—Offset 808h" on page 4319	00000050h
818–81Bh	4	"UART_BYTE_COUNT—Offset 818h" on page 4320	00000000h
820–823h	4	"UART_OVERFLOW_INTR_STAT—Offset 820h" on page 4321	00000000h

27.9.1 Receive Buffer Register/Transmit Holding Register/Divisor Latch (Low). (RBR THR DLL)—Offset 0h

Register is used for different purposes depending on the mode. See description details

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	rbr_thr_dll: RBR[7:0] (Receive Buffer Register) (Read Only): Data byte received on the serial input port (sin) in UART mode. The data in this register is valid only if the Data Ready (DR) bit in the Line Status Register (LCR) is set. If FIFOs are disabled (FCR[0] set to zero), the data in the RBR must be read before the next data arrives, otherwise it is overwritten, resulting in an over-run error. If FIFOs are enabled (FCR[0] set to one), this register accesses the head of the receive FIFO. If the receive FIFO is full and this register is not read before the next data character arrives, then the data already in the FIFO is preserved, but any incoming data are lost and an over-run error occurs. THR[7:0] (Transmit Holding Register) (Write Only): Data to be transmitted on the serial output port (sout) in UART mode. Data should only be written to the THR when the THR Empty (THRE) bit (LSR[5]) is set. If in non-FIFO mode or FIFOs are disabled (FCR[0] = 0) and THRE is set, writing a single character to the THR clears the THRE. Any additional writes to the THR before the THRE is set again causes the THR data to be overwritten. If in FIFO mode and FIFOs are enabled (FCR[0] = 1) and THRE is set, x number of characters of data may be written to the THR before the FIFO is full. The number x (default=16) is determined by the value of FIFO Depth that you set during configuration. Any attempt to write data when the FIFO is full results in the write data being lost. DLL[7:0] (Divisor Latch Low) (Read-Write): Lower 8 bits of a 16-bit, read/write, Divisor Latch register that contains the baud rate divisor for the UART. this register may be accessed only when the DLAB bit (LCR[7]) is set. The output baud rate is equal to the serial frequency divided by sixteen times the value of the baud rate divisor, as follows: $\text{baud rate} = (\text{serial clock freq}) / (16 * \text{divisor})$. Note that with the Divisor Latch Registers (DLL and DLH) set to zero, the baud clock is disabled and no serial communications occur. Also, once the DLL is set, at least 8 clock cycles of the slowest HSUART clock should be allowed to pass before transmitting or receiving data.

27.9.2 Divisor Latch (High)/ Interrupt Enable Register. (IER_DLH)—Offset 4h

Register bits [7:0] is used for different purposes depending on the mode. DLH (Divisor Latch High) Upper 8-bits of a 16-bit, read/write, Divisor Latch register that contains the baud rate divisor for the UART. This register may be accessed only when the DLAB bit (LCR[7]) is set. The output baud rate is equal to the serial clock frequency divided by sixteen times the value of the baud rate divisor, as follows: $\text{baud rate} = (\text{serial clock freq}) / (16 * \text{divisor})$. Note that with the Divisor Latch Registers (DLL and DLH) set to zero, the baud clock is disabled and no serial communications occur. Also, once the DLH is set, at least 8 clock cycles of the slowest HSUART clock should be allowed to pass before transmitting or receiving data.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0						PTIME_dlh7	RSVD1	EDSSI_dlh3 ELSI_dlh2 ETBEI_dlh1 ERBFI_dlh0

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7	0h RW	PTIME_dlh7: PTIME (PTIME) This is used to enable/disable the generation of THRE Interrupt. 0 = disabled 1 = enabled
6:4	0b RO	RSVD1: Reserved
3	0h RW	EDSSI_dlh3: EDSSI (Enable Modem Status Interrupt) This is used to enable/disable the generation of Modem Status Interrupt. This is the fourth highest priority interrupt. 0 = disabled 1 = enabled
2	0h RW	ELSI_dlh2: ELSI (Enable Line Status Interrupt) This is used to enable/disable the generation of Receiver Line Status Interrupt. This is the highest priority interrupt. 0 = disabled 1 = enabled
1	0h RW	ETBEI_dlh1: ETBEI (Enable Transmit Holding Register Empty Interrupt) This is used to enable/disable the generation of Transmitter Holding Register Empty Interrupt. This is the third highest priority interrupt. 0 = disabled 1 = enabled
0	0h RW	ERBFI_dlh0: ERBFI (Enable Received Data Available Interrupt) This is used to enable/disable the generation of Received Data Available Interrupt and the Character Timeout Interrupt (if in FIFO mode and FIFOs enabled). These are the second highest priority interrupts. 0 = disabled 1 = enabled

27.9.3 Interrupt Identification Register and FIFO Control Register. (IIR_FCR)—Offset 8h

Register is used for different purposes depending on the mode. See description details
 Interrupt ID [3:0] 0001: No Interrupt Pending 0110: Receiver Line Status (1st Priority)
 0100: Receiver Data Available (2nd Priority) 1100: Character Timeout (2nd Priority)
 0010: THR Empty (3rd Priority) 0000: Modem Status (4th Priority) 0111: Busy Detect
 Indication (5th Priority)

Access Method

Type: Memory Mapped I/O Register
 (Size: 32 bits)

Offset: [BAR] + 8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000001h



31				28				24				20				16				12				8				4				0											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1												
RSVD0																				RCVR				TET				DMAM				XFIFOR				RFIFOR				FIFOE			

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:6	0h RW	FIFOE_RCVR (RCVR): FIFOE (FIFOs Enabled) This is used to indicate whether the FIFOs are enabled or disabled. 00 = disabled 11 = enabled RCVR Trigger. This is used to select the trigger level in the receiver FIFO at which the Received Data Available Interrupt is generated. In auto flow control mode it is used to determine when the rts_n signal is de-asserted. It also determines when the dma_rx_req_n signal is asserted in certain modes of operation. The following trigger levels are supported: 00 = 1 character in the FIFO 01 = FIFO full 10 = FIFO full 11 = FIFO 2 less than full
5:4	0h RW	Res_TET (TET): TX Empty Trigger. This is used to select the empty threshold level at which the THRE Interrupts are generated when the mode is active. It also determines when the dma_tx_req_n signal is asserted when in certain modes of operation. The following trigger levels are supported: 00 = FIFO empty 01 = 2 characters in the FIFO 10 = FIFO full 11 = FIFO full
3	0h RW	IID3_DMAM (DMAM): DMA Mode. Reserved
2	0h RW	IID2_XFIFOR (XFIFOR): XMIT FIFO Reset. This resets the control portion of the transmit FIFO and treats the FIFO as empty. Note that this bit is 'self-clearing'. It is not necessary to clear this bit.
1	0h RW	IID1_RFIFOR (RFIFOR): RCVR FIFO Reset. This resets the control portion of the receive FIFO and treats the FIFO as empty. Note that this bit is 'self-clearing'. It is not necessary to clear this bit.
0	1h RW	IID0_FIFO Enable (FIFOE): This enables/disables the transmit (XMIT) and receive (RCVR) FIFOs. Whenever the value of this bit is changed both the XMIT and RCVR controller portion of FIFOs is reset

27.9.4 Line Control Register (LCR)—Offset Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
RSVD0																								DLAB	Break	RSVD1	EPS	PEN	STOP	DLS					



Bit Range	Default & Access	Field Name (ID): Description
31:6	0b RO	RSVD0: Reserved
5	0h RW	Auto Flow Control Enable (AFCE): When FIFOs are enabled and the Auto Flow Control Enable (AFCE) bit is set, 0 = Auto Flow Control Mode disabled 1 = Auto Flow Control Mode enabled Reset Value: 0x0
4	0h RW	LoopBack Bit (LoopBack): This is used to put the UART into a diagnostic mode for test purposes. If operating in UART mode (MCR[6] set to zero), data on the sout line is held high, while serial data output is looped back to the sin line, internally. In this mode all the interrupts are fully functional. Also, in loopback mode, the modem control inputs (dsr_n, cts_n, ri_n, dcd_n) are disconnected and the modem control outputs (dtr_n, rts_n, out1_n, out2_n) are looped back to the inputs, internally. Reset Value: 0x0
3	0h RW	Output2 (OUT2): This is used to directly control the user-designated Output2 (out2_n) output. The value written to this location is inverted and driven out on out2_n, that is: 0 = out2_n de-asserted (logic 1) 1 = out2_n asserted (logic 0) Note that in Loopback mode (MCR[4] set to one), the out2_n output is held inactive high while the value of this location is internally looped back to an input. Reset Value: 0x0
2	0h RW	Output1 (OUT1): This is used to directly control the user-designated Output1 (out1_n) output. The value written to this location is inverted and driven out on out1_n, that is: 0 = out1_n de-asserted (logic 1) 1 = out1_n asserted (logic 0) Note that in Loopback mode (MCR[4] set to one), the out1_n output is held inactive high while the value of this location is internally looped back to an input. Reset Value: 0x0
1	0h RW	Request to Send (RTS): This is used to directly control the Request to Send (rts_n) output. The Request To Send (rts_n) output is used to inform the modem or data set that the UART is ready to exchange data. When Auto RTS Flow Control is not enabled (MCR[5] set to zero), the rts_n signal is set low by programming MCR[1] (RTS) to a high. In Auto Flow Control, (MCR[5] set to one) and FIFOs enable (FCR[0] set to one), the rts_n output is controlled in the same way, but is also gated with the receiver FIFO threshold trigger (rts_n is inactive high when above the threshold). The rts_n signal is de-asserted when MCR[1] is set low. Note that in Loopback mode (MCR[4] set to one), the rts_n output is held inactive high while the value of this location is internally looped back to an input. Reset Value: 0x0
0	0h RW	Data Terminal Ready (DTR): This is used to directly control the Data Terminal Ready (dtr_n) output. The value written to this location is inverted and driven out on dtr_n, that is: 0 = dtr_n de-asserted (logic 1) 1 = dtr_n asserted (logic 0) The Data Terminal Ready output is used to inform the modem or data set that the UART is ready to establish communications. Note that in Loopback mode (MCR[4] set to one), the dtr_n output is held inactive high while the value of this location is internally looped back to an input. Reset Value: 0x0

27.9.6 Line Status Register (LSR)—Offset 14h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 14h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000060h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							RFE	TEMT
							THRE	BI
							FE	PE
							OE	DR

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7	0h RW	Receiver FIFO Error Bit (RFE): This bit is only relevant when FIFOs are enabled (FCR[0] set to one). This is used to indicate if there is at least one parity error, framing error, or break indication in the FIFO. 0 = no error in RX FIFO 1 = error in RX FIFO This bit is cleared when the LSR is read, the character with the error is at the top of the receiver FIFO, and there are no subsequent errors in the FIFO. Reset Value: 0x0
6	1h RW	Transmitter Empty Bit (TEMT): If FIFOs enabled (FCR[0] set to one), this bit is set whenever the Transmitter Shift Register and the FIFO are both empty. If in non-FIFO mode or FIFOs are disabled, this bit is set whenever the Transmitter Holding Register and the Transmitter Shift Register are both empty. Reset Value: 0x1
5	1h RW	Transmit Holding Register Empty Bit (THRE): If THRE mode is disabled (IER[7] set to zero), this bit indicates that the THR or TX FIFO is empty. This bit is set whenever data is transferred from the THR or TX FIFO to the transmitter shift register and no new data has been written to the THR or TX FIFO. This also causes a THRE Interrupt to occur, if the THRE Interrupt is enabled. If THRE mode is enabled and and FIFOs enabled (IER[7] set to one and FCR[0] set to one respectively), the functionality is switched to indicate the transmitter FIFO is full, and no longer controls THRE interrupts, which are then controlled by the FCR[5:4] threshold setting. Reset Value: 0x1
4	0h RW	Break Interrupt Bit (BI): This is used to indicate the detection of a break sequence on the serial input data. If in UART mode it is set whenever the serial input, sin, is held in a logic '0' state for longer than the sum of start time + data bits + parity + stop bits. In the FIFO mode, the character associated with the break condition is carried through the FIFO and is revealed when the character is at the top of the FIFO. Reading the LSR clears the BI bit. In the non-FIFO mode, the BI indication occurs immediately and persists until the LSR is read.
3	0h RW	Framing Error Bit (FE): This is used to indicate the occurrence of a framing error in the receiver. A framing error occurs when the receiver does not detect a valid STOP bit in the received data. In the FIFO mode, since the framing error is associated with a character received, it is revealed when the character with the framing error is at the top of the FIFO. When a framing error occurs, the UART tries to resynchronize. It does this by assuming that the error was due to the start bit of the next character and then continues receiving the other bit i.e. data, and/or parity and stop. It should be noted that the Framing Error (FE) bit (LSR[3]) is set if a break interrupt has occurred, as indicated by Break Interrupt (BI) bit (LSR[4]). 0 = no framing error 1 = framing error Reading the LSR clears the FE bit. Reset Value: 0x0
2	0h RW	Parity Error Bit (PE): This is used to indicate the occurrence of a parity error in the receiver if the Parity Enable (PEN) bit (LCR[3]) is set. In the FIFO mode, since the parity error is associated with a character received, it is revealed when the character with the parity error arrives at the top of the FIFO. It should be noted that the Parity Error (PE) bit (LSR[2]) is set if a break interrupt has occurred, as indicated by Break Interrupt (BI) bit (LSR[4]). 0 = no parity error 1 = parity error Reading the LSR clears the PE bit. Reset Value: 0x0



Bit Range	Default & Access	Field Name (ID): Description
1	0h RW	Overrun Error Bit (OE): This is used to indicate the occurrence of an overrun error. This occurs if a new data character was received before the previous data was read. In the non-FIFO mode, the OE bit is set when a new character arrives in the receiver before the previous character was read from the RBR. When this happens, the data in the RBR is overwritten. In the FIFO mode, an overrun error occurs when the FIFO is full and a new character arrives at the receiver. The data in the FIFO is retained and the data in the receive shift register is lost. 0 = no overrun error 1 = overrun error Reading the LSR clears the OE bit. Reset Value: 0x0
0	0h RW	Data Ready Bit (DR): This is used to indicate that the receiver contains at least one character in the RBR or the receiver FIFO. 0 = no data ready 1 = data ready This bit is cleared when the RBR is read in non-FIFO mode, or when the receiver FIFO is empty, in FIFO mode. Reset Value: 0x0

27.9.7 Modem Status Register (MSR)—Offset 18h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Offset: [BAR] + 18h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
RSVD0																				DCD	RI	DSR	CTS	DDCD	TERI	DDSR	DCTS								

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7	0h RW	Data Carrier Detect (DCD): This is used to indicate the current state of the modem control line dcd_n. This bit is the complement of dcd_n. When the Data Carrier Detect input (dcd_n) is asserted, it is an indication that the carrier has been detected by the modem or data set. 0 = dcd_n input is de-asserted (logic 1) 1 = dcd_n input is asserted (logic 0) In Loopback Mode (MCR[4] set to one), DCD is the same as MCR[3] (Out2). Reset Value: 0x0
6	0h RW	Ring Indicator (RI): This is used to indicate the current state of the modem control line ri_n. This bit is the complement of ri_n. When the Ring Indicator input (ri_n) is asserted it is an indication that a telephone ringing signal has been received by the modem or data set. 0 = ri_n input is de-asserted (logic 1) 1 = ri_n input is asserted (logic 0) In Loopback Mode (MCR[4] set to one), RI is the same as MCR[2] (Out1). Reset Value: 0x0



Bit Range	Default & Access	Field Name (ID): Description
5	0h RW	Data Set Ready (DSR): This is used to indicate the current state of the modem control line dsr_n. This bit is the complement of dsr_n. When the Data Set Ready input (dsr_n) is asserted it is an indication that the modem or data set is ready to establish communications with the DW_apb_uart. 0 = dsr_n input is de-asserted (logic 1) 1 = dsr_n input is asserted (logic 0) In Loopback Mode (MCR[4] set to one), DSR is the same as MCR[0] (DTR). Reset Value: 0x0
4	0h RW	Clear to Send (CTS): This is used to indicate the current state of the modem control line cts_n. This bit is the complement of cts_n. When the Clear to Send input (cts_n) is asserted, it is an indication that the modem or data set is ready to exchange data with the DW_apb_uart. 0 = cts_n input is de-asserted (logic 1) 1 = cts_n input is asserted (logic 0) In Loopback Mode (MCR[4] = 1), CTS is the same as MCR[1] (RTS). Reset Value: 0x0
3	0h RW	Delta Data Carrier Detect (DDCD): This is used to indicate that the modem control line dcd_n has changed since the last time the MSR was read. 0 = no change on dcd_n since last read of MSR 1 = change on dcd_n since last read of MSR Reading the MSR clears the DDCD bit. In Loopback Mode (MCR[4] = 1), DDCD reflects changes on MCR[3] (Out2). Note, if the DDCD bit is not set and the dcd_n signal is asserted (low) and a reset occurs (software or otherwise), then the DDCD bit is set when the reset is removed if the dcd_n signal remains asserted. Reset Value: 0x0
2	0h RW	Trailing Edge of Ring Indicator (TERI): This is used to indicate that a change on the input ri_n (from an active-low to an inactive-high state) has occurred since the last time the MSR was read. 0 = no change on ri_n since last read of MSR 1 = change on ri_n since last read of MSR Reading the MSR clears the TERI bit. In Loopback Mode (MCR[4] = 1), TERI reflects when MCR[2] (Out1) has changed state from a high to a low. Reset Value: 0x0
1	0h RW	Delta Data Set Ready (DDSR): This is used to indicate that the modem control line dsr_n has changed since the last time the MSR was read. 0 = no change on dsr_n since last read of MSR 1 = change on dsr_n since last read of MSR Reading the MSR clears the DDSR bit. In Loopback Mode (MCR[4] = 1), DDSR reflects changes on MCR[0] (DTR). Note, if the DDSR bit is not set and the dsr_n signal is asserted (low) and a reset occurs (software or otherwise), then the DDSR bit is set when the reset is removed if the dsr_n signal remains asserted. Reset Value: 0x0
0	0h RW	Delta Clear to Send (DCTS): This is used to indicate that the modem control line cts_n has changed since the last time the MSR was read. 0 = no change on cts_n since last read of MSR 1 = change on cts_n since last read of MSR Reading the MSR clears the DCTS bit. In Loopback Mode (MCR[4] = 1), DCTS reflects changes on MCR[1] (RTS). Note that if the DCTS bit is not set, the cts_n signal is asserted (low) and a reset occurs (software or otherwise), then the DCTS bit is set when the reset is removed if the cts_n signal remains asserted. Reset Value: 0x0

27.9.8 Scratchpad Register (SCR)—Offset 1Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 1Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h



Shadow Receive Buffer Register and Shadow Transmit Holding Register 0 (SRBR STHR0)—Offset 30h

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr0: This is a shadow register for the RBR and has been allocated sixteen 32-bit locations to accommodate burst accesses from the master. This register contains the data byte received on the serial input port (sin) in UART mode or the serial infrared input (sir_in) in infrared mode. The data in this register is valid only if the Data Ready (DR) bit in the Line status Register (LSR) is set. If FIFOs are disabled (FCR[0] set to zero), the data in the RBR must be read before the next data arrives, otherwise it is overwritten, resulting in an overrun error. If FIFOs are enabled (FCR[0] set to one), this register accesses the head of the receive FIFO. If the receive FIFO is full and this register is not read before the next data character arrives, then the data already in the FIFO are preserved, but any incoming data are lost. An overrun error also occurs. Reset Value: 0x0



27.9.10 Shadow Receive Buffer Register and Shadow Transmit Holding Register 1 (SRBR_STHR1)—Offset 34h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 34h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr1	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr1: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.9.11 Shadow Receive Buffer Register and Shadow Transmit Holding Register 2 (SRBR_STHR2)—Offset 38h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 38h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr2	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr2: Refer to bit field description for SRBR_STHR0.srbr_sthr0.



27.9.14 Shadow Receive Buffer Register and Shadow Transmit Holding Register 5 (SRBR_STHR5)—Offset 44h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 44h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr5	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr5: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.9.15 Shadow Receive Buffer Register and Shadow Transmit Holding Register 6 (SRBR_STHR6)—Offset 48h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 48h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr6	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr6: Refer to bit field description for SRBR_STHR0.srbr_sthr0.



27.9.18 Shadow Receive Buffer Register and Shadow Transmit Holding Register 9 (SRBR_STHR9)—Offset 54h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 54h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr9	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr9: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.9.19 Shadow Receive Buffer Register and Shadow Transmit Holding Register 10 (SRBR_STHR10)—Offset 58h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 58h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr10	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr10: Refer to bit field description for SRBR_STHR0.srbr_sthr0.



27.9.20 Shadow Receive Buffer Register and Shadow Transmit Holding Register 11 (SRBR_STHR11)—Offset 5Ch

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 5Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr11	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr11: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.9.21 Shadow Receive Buffer Register and Shadow Transmit Holding Register 12 (SRBR_STHR12)—Offset 60h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 60h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr12	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr12: Refer to bit field description for SRBR_STHR0.srbr_sthr0.



27.9.22 Shadow Receive Buffer Register and Shadow Transmit Holding Register 13 (SRBR_STHR13)—Offset 64h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 64h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr13	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr13: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.9.23 Shadow Receive Buffer Register and Shadow Transmit Holding Register 14 (SRBR_STHR14)—Offset 68h

Refer to bit field description for SRBR_STHR0.srbr_sthr0.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 68h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							srbr_sthr14	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	srbr_sthr14: Refer to bit field description for SRBR_STHR0.srbr_sthr0.

27.9.26 Transmit FIFO Read (TFR)—Offset 74h

Bit Range	Default & Access	Field Name (ID): Description
0	0h RW	srbr_sthr: Writes have no effect when FIFO_ACCESS == No, always readable. This register is used to enable a FIFO access mode for testing, so that the receive FIFO can be written by the master and the transmit FIFO can be read by the master when FIFOs are implemented and enabled. When FIFOs are not implemented or not enabled it allows the RBR to be written by the master and the THR to be read by the master. 0 = FIFO access mode disabled 1 = FIFO access mode enabled Note that when the FIFO access mode is enabled/disabled, the control portion of the receive FIFO and transmit FIFO is reset and the FIFOs are treated as empty. Reset Value: 0x0

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 74h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0							tfr	

Bit Range	Default & Access	Field Name (ID): Description
31:8	0b RO	RSVD0: Reserved
7:0	0h RW	Transmit FIFO Read (tfr): These bits are only valid when FIFO access mode is enabled (FAR[0] is set to one). When FIFOs are implemented and enabled, reading this register gives the data at the top of the transmit FIFO. Each consecutive read pops the transmit FIFO and gives the next data value that is currently at the top of the FIFO. When FIFOs are not implemented or not enabled, reading this register gives the data in the THR. Reset Value: 0x0

27.9.27 Receive FIFO Write (RFW)—Offset 78h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 78h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
RSVD0																RFPE	RFPE	RFWD																	



Access Method

Offset: [BAR] + 80h

BAR Reference: [B:0, D:30, F:3] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RS/D0								tr

27.9.30 Receive FIFO Level (RFL)—Offset 84h

Access Method

Offset: [BAR] + 84h

BAR Reference: [B:0, D:30, F:3] + 10h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RS/D0								F

Bit Range	Default & Access	Field Name (ID): Description
31:5	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Field Name (ID): Description
4:0	0h RW	Receive FIFO Level (rfl): This indicates the number of data entries in the receive FIFO. Reset Value: 0x0

27.9.31 Software Reset Register (SRR)—Offset 88h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 88h**BAR Type:** PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:3	0b RO	RSVDD0: Reserved
2	0h RW	XMIT FIFO Reset (XFR): This is a shadow register for the XMIT FIFO Reset bit (FCR[2]). This can be used to remove the burden on software having to store previously written FCR values (which are pretty static) just to reset the transmit FIFO. This resets the control portion of the transmit FIFO and treats the FIFO as empty. This also de-asserts the DMA TX request and single signals when additional DMA handshaking signals are selected (DMA_EXTRA == YES). Note that this bit is 'self-clearing'. It is not necessary to clear this bit. Reset Value: 0x0
1	0h RW	RCVR FIFO Reset (RFR): This is a shadow register for the RCVR FIFO Reset bit (FCR[1]). This can be used to remove the burden on software having to store previously written FCR values (which are pretty static) just to reset the receive FIFO. This resets the control portion of the receive FIFO and treats the FIFO as empty. This also de-asserts the DMA RX request and single signals when additional DMA handshaking signals are selected (DMA_EXTRA == YES). Note that this bit is 'self-clearing'. It is not necessary to clear this bit. Reset Value: 0x0
0	0h RW	UART Reset (UR): This asynchronously resets the DW_apb_uart and synchronously removes the reset assertion. For a two clock implementation both pclk and sclk domains are reset. Reset Value: 0x0

27.9.32 Shadow Request to Send (SRTS)—Offset 8Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 8Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

27.9.33 Shadow Break Control Register (SBCR)—Offset 90h

This is a shadow register for the Break bit (LCR[6]), this can be used to remove the burden of having to performing a read modify write on the LCR. This is used to cause a break condition to be transmitted to the receiving device. If set to one the serial output is forced to the spacing (logic 0) state. When not in Loopback Mode, as determined by MCR[4], the sout line is forced low until the Break bit is cleared.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 90h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RSVD0									shb

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	Shadow Break Control Bit (sbcb): Reserved.

27.9.36 Shadow RCVR Trigger (SRT)—Offset 9Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 9Ch

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								st

Bit Range	Default & Access	Field Name (ID): Description
31:2	0b RO	RSVD0: Reserved
1:0	0h RW	Shadow RCVR Trigger (srt): This is a shadow register for the RCVR trigger bits (FCR[7:6]). This can be used to remove the burden of having to store the previously written value to the FCR in memory and having to mask this value so that only the RCVR trigger bit gets updated. This is used to select the trigger level in the receiver FIFO at which the Received Data Available Interrupt is generated. It also determines when the dma_rx_req_n signal is asserted when DMA Mode (FCR[3]) = 1. The following trigger levels are supported: 00 = 1 character in the FIFO 01 = FIFO full 10 = FIFO full 11 = FIFO 2 less than full Reset Value: 0x0

27.9.37 Shadow TX Empty Trigger (STET)—Offset A0h

This is a shadow register for the TX empty trigger bits (FCR[5:4]). This can be used to remove the burden of having to store the previously written value to the FCR in memory and having to mask this value so that only the TX empty trigger bit gets updated. This is used to select the empty threshold level at which the THRE Interrupts are generated when the mode is active. The following trigger levels are supported:

- 00 = FIFO empty
- 01 = 2 characters in the FIFO
- 10 = FIFO full
- 11 = FIFO full

Reset Value: 0x0

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + A0h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

27.9.40 Component Parameter Register (CPR)—Offset F4h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
RSVD0									dma

Bit Range	Default & Access	Field Name (ID): Description
31:1	0b RO	RSVD0: Reserved
0	0h RW	dmaa: This register is use to perform a DMA software acknowledge if a transfer needs to be terminated due to an error condition. For example, if the DMA disables the channel, then the DW_apb_uart should clear its request. This causes the TX request, TX single, RX request and RX single signals to de-assert. Note that this bit is 'self-clearing'. It is not necessary to clear this bit. Reset Value: 0x0 Dependencies: Writes have no effect when DMA_EXTRA == No.

27.9.40 Component Parameter Register (CPR)—Offset F4h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F4h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00043F32h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:24	0b RO	RSVD0: Reserved
23:16	4h RO	FIFO MODE (FIFO_MODE): 0x00 = 0 0x01 = 16 0x02 = 32 - to 0x80 = 2048 0x81- 0xff = reserved
15:14	0b RO	RSVD1: Reserved



Bit Range	Default & Access	Field Name (ID): Description
13	1h RO	DMA EXTRA (DMA_EXTRA): 0 = FALSE 1 = TRUE
12	1h RO	UART ADD ENCODED PARAMS (UART_ADD_ENCODED_PARAMS): 0 = FALSE, 1 = TRUE
11	1h RO	SHADOW: 0 = FALSE, 1 = TRUE
10	1h RO	FIFO STAT (FIFO_STAT): 0 = FALSE, 1 = TRUE
9	1h RO	FIFO ACCESS (FIFO_ACCESS): 0 = FALSE, 1 = TRUE
8	1h RO	ADDITIONAL FEAT (ADDITIONAL_FEAT): 0 = FALSE, 1 = TRUE
7	0h RO	SIR LP MODE (SIR_LP_MODE): 0 = FALSE, 1 = TRUE
6	0h RO	SIR MODE (SIR_MODE): 0 = FALSE, 1 = TRUE
5	1h RO	THRE MODE (THRE_MODE): 0 = FALSE, 1 = TRUE
4	1h RO	AFCE MODE (AFCE_MODE): 0 = FALSE, 1 = TRUE
3:2	0b RO	RSVD2: Reserved
1:0	2h RO	APB DATA WIDTH (APB_DATA_WIDTH): 00 = 8 bits 01 = 16 bits 10 = 32 bits 11 = reserved

27.9.41 UART Component Version (UCV)—Offset F8h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + F8h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 3330382Ah



31	28	24	20	16	12	8	4	0																
0	0	1	1	0	0	1	1	0	0	1	1	0	0	0	0	0	0	1	1	0	0	1	1	0
UART																								

Bit Range	Default & Access	Field Name (ID): Description
31:0	3330382ah RO	UART: ASCII value for each number in the version, followed by *. For example 32_30_31_2A represents the version 2.01*. Reset Value: See the releases table in the AMBA 2 release notes.

27.9.42 Component Type Register (CTR)—Offset FCh

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + FCh

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 44570110h

31	28	24	20	16	12	8	4	0															
0	1	0	0	0	1	0	0	0	0	1	0	0	0	0	0	1	0	0	0	0	0	0	0
PeripheralID																							
Bit Range	Default & Access	Field Name (ID): Description																					
31:0	44570110h RO	Peripheral ID (PeripheralID): This register contains the peripherals identification code. Reset Value: 0x44570110																					

27.9.43 Private Clock Params (PRV_CLOCK_PARAMS)—Offset 800h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 800h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Field Name (ID): Description
31	0h RW	clk_update: update the clock divider after seeting new m and n values
30:16	0h RW	N_VAL (n_val): n value for the m over n divider
15:1	0h RW	M_VAL (m_val): m value for the m over n divider
0	0h RW	clk_en: clk en of the m over n divider

27.9.44 Software Resets (RESETS)—Offset 804h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 804h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:2	0h RW	Reserved (reserved): Reserved.
1	0h RW	reset_apb: reset the apb domain
0	0h RW	reset_func: reset the func clock domain

27.9.45 General Purpose Register (GENERAL)—Offset 808h

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [BAR] + 808h

BAR Type: PCI Configuration Register (Size: 32 bits)

BAR Reference: [B:0, D:30, F:3] + 10h

Default: 00000050h



27.9.47 UART_OVERFLOW_INTR_STAT—Offset 820h


Default: 00000000h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	0
reserved									uart_overflow_intr_mask
									uart_overflow_intr

October 2018
Document Number: 538136, Rev. 4.3

28 SIO – Pulse Width Modulation (PWM)

The Pulse Width Modulation block allows control the frequency and duty cycle of an output signal. The SoC has 2 instances of the PWM interface.



28.1 Signal Descriptions

Please see [Chapter 2, “Physical Interfaces”](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal’s function


Figure 128.PWM Signals

Signal Name	Direction Plat. Power	Description
SIO_PWM[0]	O V1P8S	Pulse Width Modulation output 0.
SIO_PWM[1]	O V1P8S	Pulse Width Modulation output 1.

28.2 Features

The software controls the PWM block by updating the PWMCTRL register and setting the PWMCTRL.PWM_SW_UPDATE bit whenever a change in frequency or duty cycle of the PWM output signal is required. The PWM block applies the new settings at the start of the next output cycle and resets the PWMCTRL.PWM_SW_UPDATE bit. The SoC uses a 25 MHz base clock rate for the PWM counter. See [Figure 129](#) for PWM block diagram:

Figure 129. PWM Block Diagram



There are two controls of the PWM output:

- **Frequency** is controlled by the PWMCTRL.PWM_BASE_UNIT register. The PWMCTRL.PWM_BASE_UNIT value is added to the 16 bit PWM counter every base clock cycle. The counter roll-over/overflow marks the start of a new cycle and resets the counter to the value in PWMCTRL.PWM_BASE_UNIT.
- **Duty Cycle** is controlled by the PWMCTRL.PWM_ON_TIME_DIVISOR setting (0 to 255). When the 16 bit PWM counter is less than PWM_ON_TIME_DIVISOR * 256, the PWM output is low (0). When the 16 bit PWM counter is equal to or greater than PWM_ON_TIME_DIVISOR * 256, the PWM output is high (1).

The PWM block is clocked by the 25 MHz oscillator clock. The output frequency can be estimated with the equation:

- Target frequency = $25 \text{ MHz} / \text{CEILING}(65536/\text{PWM_BASE_UNIT})$
Note that the larger the value of base_unit, the larger the error that the PWM output frequency will have with respect to the equation above. For example any $\text{Base_unit_value}/256 > 128$ will result in 12.5 MHz max frequency. Any value between 86 and 128 will result in 8.33 MHz output frequency. And accordingly the larger the base_unit value the smaller duty cycle resolution. Maximum duty cycle resolution is 8 bits.

[Table 287](#) illustrates the output frequency and duty-cycle resolution for different settings of the base_unit_value (when using 25 MHz oscillator clock).

**Table 287. Example PWM Output Frequency and Resolution**

Target Frequency	Base Unit Value Register	Base 25 MHz Cycle Count	Duty Cycle Resolution
12.5 MHz	$\geq 128 * 256$	1	no resolution
1.07 MHz	$11 * 256$	23	<8 bit resolution
488 kHz	$5 * 256$	51	<8 bit resolution
97.6 kHz	$1 * 256$	256	8 resolution
48.4 kHz	$0.5 * 256$	512	≥ 8 bit resolution
0	0	0	Flat 0 output

28.3 Use

28.3.1 PWM Programming Sequence

For first time activation, follow sequence:

1. Program the counter value PWMCTRL.PWM_BASE_UNIT and PWMCTRL.PWM_ON_TIME_DIVISOR
2. Set the PWMCTRL.PWM_SW_UPDATE bit
3. Enable PWM output by setting the PWMCTRL.PWM_ENABLE bit


For update on the fly, follow sequence:

1. Program the counter value PWMCTRL.PWM_BASE_UNIT and PWMCTRL.PWM_ON_TIME_DIVISOR
2. Set the update bit PWMCTRL.PWM_SW_UPDATE

28.4 Register Map

Refer to [Chapter 3, “Register Access Methods”](#) and [Chapter 4, “Mapping Address Spaces”](#) for additional information.

Figure 130.SIO - PWM Register Map



28.5.3 Revision ID and Class Code (REVCLASSCODE)—Offset 8h

Bit Range	Default & Access	Field Name (ID): Description
7:3	00h RO	Reserved5: Reserved.
2	0h RW	Bus Master Enable (BME): If this bit is 0, Bridge does not generate any new upstream transaction on IOSF as a master.
1	0h RW	Memory Space Enable (MSE): This bit controls Bridge's response to downstream Memory accesses. When set, accesses to memory space of the device is enabled.
0	0h RO	Reserved6: Reserved.

28.5.3 Revision ID and Class Code (REVCLASSCODE)—Offset 8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:1] + 8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
CLASS_CODES							RID	

Bit Range	Default & Access	Field Name (ID): Description
31:8	000000h RO	Class Code (CLASS_CODES): The Class Code register is read-only and used to identify the generic function of the device and, in some cases, a specific register level programming interface. The register is broken into three byte size fields. The upper byte (at offset 0Bh) is a base class code which broadly classifies the type of function the device performs. The middle byte (at offset 0Ah) is a sub-class code which identifies more specifically the function of the device. The lower byte (at offset 09h) identifies a specific register-level programming interface (if any) so that device independent software can interact with the device. This register is tied to a strap at the top level.
7:0	00h RO	Revision ID (RID): Revision ID identifies the revision of particular AHB device. This is tied to a strap at the top level.

28.5.4 Cache Line Latency Header and BIST (CLLATHEADERBIST)—Offset Ch

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:1] + Ch

Default: 00800000h



31	28	24	20	16	12	8	4	0
0	0	0	0	1	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
Reserved0				MULFNDEV	HEADERTYPE			
					LATTIMER			
								CACHELINE_SIZE

Bit Range	Default & Access	Field Name (ID): Description
31:24	00h RO	Reserved0: Reserved.
23	1h RO	Multi Function Device (MULFNDEV): This bit is always 0 for non fabric ports. For Fabric ports it is driven from fabric_mult_function strap. 1 = multifunction device 0 = single function device
22:16	00h RO	Header Type (HEADERTYPE): Implements Type 0 Configuration header.
15:8	00h RO	Latency Timer (LATTIMER): Does not apply to PCI Express. Hardwired to 00h.
7:0	00h RW	Cache Line Size (CACHELINE_SIZE): Doesn't apply to PCI Express. PCI Express spec requires this to be implemented as a R/W register but has no functional impact on the AHB Device connected.

28.5.5 Base Address Register (BAR)—Offset 10h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Offset: [B:0, D:30, F:1] + 10h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BASEADDR						SIZEINDICATOR	PREFETCHABLE	TYPE
								MESSAGE_SPACE

Bit Range	Default & Access	Field Name (ID): Description
31:12	00000h RW	Base Address (BASEADDR): Base address of the AHB device memory space. Taken from Strap values as 1.s
11:4	00h RO	Size Indicator Read Only (SIZEINDICATOR): Always returns zero. The size of this register depends on the size of the Memory space. This size is determined by a top level of STRAP values as 0.s. Always will be zero as minimum size is 4K.
3	0h RO	Prefetchable (PREFETCHABLE): Indicates that this BAR is not prefetchable.



Access Method

Offset: [B:0, D:30, F:1] + 14h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BASEADDR1						SIZEINDICATOR1		
						PREFETCHABLE1		
						TYPE1		
						MESSAGE_SPACE1		

28.5.7 Subsystem Vendor and Subsystem ID (SUBSYSTEMID)—Offset 2Ch

Access Method

Offset: [B:0, D:30, F:1] + 2Ch

October 2018
Document Number: 538136, Rev. 4.3



28.5.8 Expansion ROM Base Address (EXPANSION_ROM_BASEADDR)—Offset 30h

Offset: [B:0, D:30, F:1] + 30h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
EXPANSION_ROM_BASE								

28.5.9 Capabilities Pointer (CAPABILITYPTR)—Offset 34h

Offset: [B:0, D:30, F:1] + 34h



Bit Range	Default & Access	Field Name (ID): Description
15	0h RW/1C	PME Status (PMESTATUS): 0 = Software clears the bit by writing a 1 to it. 1 = This bit is set when the AHB Device would normally assert the PME# signal independent of the state of the PME Enable bit (bit 8 in this register).
14:9	00h RO	Reserved1: Reserved.
8	0h RW	PME Enable (PMEENABLE): A 1 enables the function to assert PME#. When 0, PME# message on SB is disabled.
7:4	0h RO	Reserved2: Reserved.
3	1h RO	No_Soft_Reset (NO_SOFT_RESET): This bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved.
2	0h RO	Reserved3: Reserved.
1:0	0h RW	Power State (POWERSTATE): This field is used both to determine the current power state of the AHB IP and to set a new power state. The values are: 00 = D0 state 11 = D3HOT state - Others = Reserved Notes: If software attempts to write a value of 01b or 10b in to this field, the write operation must complete normally; however, the data is discarded and no state change occurs. When in the D3HOT states, interrupts are blocked. D3Hot will not be used for Downstream decode on fabric ports.

28.5.13 Manufacturer ID (MANID)—Offset F8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)


Offset: [B:0, D:30, F:1] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

MANID

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RO	Manufacturer ID (MANID): This register is brought out as straps to the top level.




29 Platform Controller Unit (PCU) Overview

The Platform Controller Unit (PCU) is a collection of HW blocks that are critical for implementing a Windows* compatible platform. These HW blocks include:

- PCU – Power Management Controller (PMC)
- PCU – Serial Peripheral Interface (SPI)
 - For boot FW and system configuration data Flash storage
- PCU – Universal Asynchronous Receiver/Transmitter (UART)PCU – System Management Bus (SMBus)
- PCU – Intel® Legacy Block (iLB) Overview

The PCU also implements some high level configuration features for BIOS/EFI boot.



29.1 Features

The key features of the individual blocks are as follows:

- Universal Asynchronous Receiver/Transmitter (UART)
 - 16550 controller compliant
 - Reduced Signal Count: TX and RX only
 - COM1 interface
- Serial Peripheral Interface (SPI)
 - For one or two SPI Flash, of up to 16MB size each, only. No other SPI peripherals are supported.
 - Stores boot FW and system configuration data



- Supports frequencies of 20 MHz, 33MHz and 50MHz.
- Power Management Controller (PMC)
 - Controls many of the power management features present in the SoC.
- Intel Legacy Block (iLB)
 - Supports legacy PC platform features
 - Sub-blocks include LPC, GPIO, 8259 PIC, IO-APIC, 8254 timers, HPET timers and the RTC.

§



29.2 PCU iLB LPC Port 80h I/O Registers

Table 289. Summary of PCU iLB LPC Port 80h I/O Registers—

Offset	Size	Register ID—Description	Default Value
80h	1	"PC80—Offset 80h" on page 4337	00h
81h	1	"PC81—Offset 81h" on page 4338	00h
82h	1	"PC82—Offset 82h" on page 4338	00h
83h	1	"PC83—Offset 83h" on page 4338	00h
84h	1	"PC84—Offset 84h" on page 4339	00h
85h	1	"PC85—Offset 85h" on page 4339	00h
86h	1	"PC86—Offset 86h" on page 4340	00h
87h	1	"PC87—Offset 87h" on page 4340	00h
88h	1	"PC88—Offset 88h" on page 4340	00h
89h	1	"PC89—Offset 89h" on page 4341	00h
8Ah	1	"PC8A—Offset 8Ah" on page 4341	00h
8Bh	1	"PC8B—Offset 8Bh" on page 4342	00h
8Ch	1	"PC8C—Offset 8Ch" on page 4342	00h
8Dh	1	"PC8D—Offset 8Dh" on page 4342	00h
8Eh	1	"PC8E—Offset 8Eh" on page 4343	00h
8Fh	1	"PC8F—Offset 8Fh" on page 4343	00h

29.2.1 PC80—Offset 80h

Post Code 80 register

Access Method

Type: I/O Register
(Size: 8 bits)

PC80: 80h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
				PC80REG			

Bit Range	Default & Access	Description
7:0	0h RW	PC80REG: Post Code 80 register



29.2.2 PC81—Offset 81h

Post Code 81 regsite

Access Method

Type: I/O Register
(Size: 8 bits)

PC81: 81h

Default: 00h

7				4					0
0		0		0		0		0	0
					PC81REG				

Bit Range	Default & Access	Description
7:0	X RW	PC81REG: Post Code 81 regsite

29.2.3 PC82—Offset 82h

Post Code 82 regsite

Access Method

Type: I/O Register
(Size: 8 bits)

PC82: 82h

Default: 00h

7				4					0
0		0		0		0		0	0
					PC82REG				

Bit Range	Default & Access	Description
7:0	X RW	PC82REG: Post Code 82 regsite

29.2.4 PC83—Offset 83h

Post Code 83 regsite

Access Method

Type: I/O Register
(Size: 8 bits)

PC83: 83h

Default: 00h



7				4					0
0	0	0	0	0	0	0	0	0	0
					PC83REG				

Bit Range	Default & Access	Description
7:0	X RW	PC83REG: Post Code 83 regisiter

29.2.5 PC84—Offset 84h

Post Code 84 regsiteer

Access Method

Type: I/O Register
(Size: 8 bits)

PC84: 84h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
					PC84REG				
Bit Range	Default & Access	Description							
7:0	X RW	PC80REG (PC84REG): Post Code 84 regsiteer							

29.2.6 PC85—Offset 85h

Post Code 85 regsiteer

Access Method

Type: I/O Register
(Size: 8 bits)

PC85: 85h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
					PC85REG				
Bit Range	Default & Access	Description							
7:0	X RW	PC85REG: Post Code 85 regsiteer							



29.2.7 PC86—Offset 86h

Post Code 86 regsiter

Access Method

Type: I/O Register
(Size: 8 bits)

PC86: 86h

Default: 00h

7				4				0
0	0	0	0	0	0	0	0	0
				PC86REG				

Bit Range	Default & Access	Description
7:0	X RW	PC86REG: Post Code 86 regsiter

29.2.8 PC87—Offset 87h

Post Code 87 regsiter

Access Method

Type: I/O Register
(Size: 8 bits)

PC87: 87h

Default: 00h

7				4				0
0	0	0	0	0	0	0	0	0
				PC87REG				

Bit Range	Default & Access	Description
7:0	X RW	PC87REG: Post Code 87 regsiter

29.2.9 PC88—Offset 88h

Post Code 88 regsiter

Access Method

Type: I/O Register
(Size: 8 bits)

PC88: 88h

Default: 00h



7				4					0
0	0	0	0	0	0	0	0	0	0
					Reserved				

Bit Range	Default & Access	Description
7:0	0h RO	Reserved: Reserved.

29.2.10 PC89—Offset 89h

Post Code 89 register

Access Method

Type: I/O Register
(Size: 8 bits)

PC89: 89h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
					Reserved				

Bit Range	Default & Access	Description
7:0	0h RO	Reserved: Reserved.

29.2.11 PC8A—Offset 8Ah

Post Code 8A register

Access Method

Type: I/O Register
(Size: 8 bits)

PC8A: 8Ah

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
					Reserved				

Bit Range	Default & Access	Description
7:0	0h RO	Reserved: Reserved.



29.2.12 PC8B—Offset 8Bh

Post Code 8B register

Access Method

Type: I/O Register
(Size: 8 bits)

PC8B: 8Bh

Default: 00h

7				4					0
0		0		0		0		0	0
					Reserved				

Bit Range	Default & Access	Description
7:0	0h RO	Reserved: Reserved.

29.2.13 PC8C—Offset 8Ch

Post Code 8C register

Access Method

Type: I/O Register
(Size: 8 bits)

PC8C: 8Ch

Default: 00h

7				4					0
0		0		0		0		0	0
					Reserved				

Bit Range	Default & Access	Description
7:0	0h RO	Reserved: Reserved.

29.2.14 PC8D—Offset 8Dh

Post Code 8D register

Access Method

Type: I/O Register
(Size: 8 bits)

PC8D: 8Dh

Default: 00h



7				4					0
0	0	0	0	0	0	0	0	0	0
Reserved									

Bit Range	Default & Access	Description
7:0	0h RO	Reserved: Reserved.

29.2.15 PC8E—Offset 8Eh

Post Code 8E register

Access Method

Type: I/O Register
(Size: 8 bits)

PC8E: 8Eh

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
Reserved									

Bit Range	Default & Access	Description
7:0	0h RO	Reserved: Reserved.

29.2.16 PC8F—Offset 8Fh

Post Code 8F register

Access Method

Type: I/O Register
(Size: 8 bits)


PC8F: 8Fh

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
					Reserved				
Bit Range	Default & Access	Description							
7:0	0h RO	Reserved: Reserved.							

30 PCU – Power Management Controller (PMC)

The Power Management Controller (PMC) controls many of the power management features present in the SoC.



30.1 Signal Descriptions

Please see [Chapter 2, “Physical Interfaces”](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal’s function

Table 290. PMC Signals (Sheet 1 of 3)

Signal Name	Direction Plat. Power	Description
PMC_ACPRESENT	I V1P8A	AC Present: This input pin indicates when the platform is plugged into AC power.
PMC_BATLOW#	I V1P8A	Battery Low: An input from the battery to indicate that there is insufficient power to boot the system. Assertion will prevent wake from the S5 state. This signal can also be enabled to cause an SMI# when asserted. In configurations without a battery, this signal should be tied high to V1P8_S5.




Table 290. PMC Signals (Sheet 2 of 3)

Signal Name	Direction Plat. Power	Description
PMC_CORE_PWROK	I VRTC	Core Power OK: When asserted, this signal is an indication to the SoC that all of its core power rails have been stable for 10 ms. It can be driven asynchronously. When it is negated, the SoC asserts PMC_PLTRST#. NOTE: It is required that the power rails associated with PCI Express (typically the 3.3V, 5V, and 12V core well rails) have been valid for 99 ms prior to PMC_CORE_PWROK assertion in order to comply with the 100 ms T_{PVPERL} PCI Express 2.0 specification on PMC_PLTRST# deassertion. NOTE: PMC_CORE_PWROK must not glitch, even if PMC_RSMRST# is low.
PMC_PLTRST#	O V1P8A	Platform Reset: The SoC asserts this signal to reset devices on the platform. The SoC asserts the signal during power-up and when software initiates a reset sequence through the Reset Control (RST_CNT) register when RST_CNT.sys_rst=1b.
PMC_PWRBTN#	I V1P8A	Power Button: The signal will cause SCI to indicate a system request to go to a sleep state. If the system is already in a sleep state, this signal will cause a wake event. If the signal is pressed for more than 4 seconds, this will cause an unconditional transition (power button override) to the S5 state. Override will occur even if the system is in the S3 & S4 states. This signal has an internal pull-up resistor and has an internal ~16 ms de-bounce on the input.
PMC_RSMRST#	I VRTC	Resume Well Reset: Used for resetting the resume well. An external RC circuit is required to guarantee that the resume well power is valid prior to this signal going high.
PMC_RSTBTN#	I V1P8S	System Reset: This signal forces an internal reset after being debounced (~16 ms).
PMC_SLP_S3#	O V1P8A	S3 Sleep Control: This signal is for power plane control. It can be used to control system power when it is in a S3 (Suspend To RAM), S4 (Suspend to Disk), or S5 (Soft Off) states.
PMC_SLP_S4#	O V1P8A	S4 Sleep Control: This signal is for power plane control. It can be used to control system power when it is in a S4 (Suspend to Disk) or S5 (Soft Off) state.
PMC_SUS_STAT#	O V1P8A	Suspend Status: This signal is asserted by the SoC to indicate that the system will be entering a low power state soon. This can be monitored by devices with memory that need to switch from normal refresh to suspend refresh mode. It can also be used by other peripherals as an indication that they should isolate their outputs that may be going to powered-off planes. <i>This signal is muxed and may be used by other functions.</i>




Table 290. PMC Signals (Sheet 3 of 3)

Signal Name	Direction Plat. Power	Description
PMC_SUSCLK	O V1P8A	Suspend Clock: This 32 kHz clock is an output of the RTC generator circuit for use by other chips for refresh clock. <i>This signal is muxed and may be used by other functions.</i>
PMC_SUSPWRDNA CK	O V1P8A	Suspend Power Down Acknowledge: Asserted by the SoC on S0 to S4/5 transition when it does not require its Suspend well to be powered. This pin requires a pull-up to UNCORE_V1P8_G3. <i>This signal is muxed and may be used by other functions.</i>
PMC_WAKE_PCIE[3 :0]#	I V1P8A	PCI Express* Port [3:0] Wake Event: Sideband wake signal on PCI Express asserted by a component requesting wake up. <i>This signal is muxed and may be used by other functions.</i>
PMC_PLT_CLK[5:0]	O V1P8S	Platform Clocks: Configurable single ended clocks, configurable to 25 MHz. <i>This signal is muxed and may be used by other functions.</i>

30.2 Features


30.2.1 Sx-G3-Sx, Handling Power Failures

Depending on when the power failure occurs and how the system is designed, different transitions could occur due to a power failure.

The GEN_PMCON1.AG3E bit provides the ability to program whether or not the system should boot once power returns after a power loss event. If the policy is to not boot, the system remains in an S5 state (unless previously in S4). There are only two possible events that will wake the system after a power failure.

- **PMC_PWRBTN#:** PMC_PWRBTN# is always enabled as a wake event. When RSMRST# is low (G3 state), the PM1_STS_EN.PWRBTN_STS bit is reset. When the SoC exits G3 after power returns (PMC_RSMRST# goes high), the PMC_PWRBTN# signal is already high (because the suspend plane goes high before PMC_RSMRST# goes high) and the PM1_STS_EN.PWRBTN_STS bit is 0b.
- **RTC Alarm:** The PM1_STS_EN.RTC_EN bit is in the RTC well and is preserved after a power loss. Like PM1_STS_EN.PWRBTN_STS the PM1_STS_EN.RTC_STS bit is cleared when PMC_RSMRST# goes low.

The SoC monitors both PMC_CORE_PWROK and PMC_RSMRST# to detect for power failures. If PMC_CORE_PWROK goes low, the GEN_PMCON1.PWR_FLR bit is set. If PMC_RSMRST# goes low, GEN_PMCON1.SUS_PWR_FLR is set.

**Table 291. Transitions Due to Power Failure**

State at Power Failure	GEN_PMCON1.AG3E bit	Transition When Power Returns
S0, S3	1 0	S5 S0
S4	1 0	S4 S0
S5	1 0	S5 S0

30.2.2 Event Input Signals and Their Usage

The SoC has various input signals that trigger specific events. This section describes those signals and how they should be used.

30.2.3 PCI Express* WAKE# Signal and PME Event Message

PCI Express ports can wake the platform from any sleep state (S3, S4, or S5) using the PMC_WAKE_PCIE[3:0]# pins.

Note: PMC_WAKE_PCIE[3:0]# functionality is disabled by setting PM1_STS_EN.PCIEXP_WAKE_DIS to 1b.

PCI Express ports have the ability to cause PME using messages. When a PME message is received, the SoC will set the GPE0a_STS.PCI_EXP_STS bit.

30.2.3.1 PMC_PWRBTN# (Power Button)

The PMC_PWRBTN# signal operates as a “Fixed Power Button” as described in the Advanced Configuration and Power Interface specification. The signal has a 16 ms debounce on the input. The state transition descriptions are included in [Table 292](#). Note that the transitions start as soon as the PMC_PWRBTN# is pressed (but after the debounce logic), and does not depend on when the power button is released.

Note: During the time that the PMC_SLP_S4# signal is stretched for the minimum assertion width (if enabled), the power button is not a wake event. Refer to note below for more details.



Table 292. Transitions Due to Power Button

Present State	Event	Transition/Action	Comment
S0/Cx	PMC_PWRBTN# goes low	SCI generated (depending on PM1_CNT.SCI_EN and PM1_STS_EN.PWRBTN_EN)	Software typically initiates a Sleep state
S3–S4/S5	PMC_PWRBTN# goes low	Wake Event. Transitions to S0 state	Standard wakeup
G3	PMC_PWRBTN# pressed	None	No effect since no power Not latched nor detected
S0, S3–S4	PMC_PWRBTN# held low for at least 4 consecutive seconds	Unconditional transition to S5 state	No dependence on processor or any other subsystem


Power Button Override Function

If PMC_PWRBTN# is observed active for at least four consecutive seconds, the state machine should unconditionally transition to the S5 state, regardless of present state (S0–S4), even if the PMC_CORE_PWROK is not active. In this case, the transition to the G2/S5 state should not depend on any particular response from the processor nor any similar dependency from any other subsystem.

The PMC_PWRBTN# status is readable to check if the button is currently being pressed or has been released. The status is taken after the de-bounce, and is readable using the GEN_PMC2.PWRBTN_LVL bit.

Note: The 4-second PMC_PWRBTN# assertion should only be used if a system lock-up has occurred. The 4-second timer starts counting when the SoC is in a S0 state. If the PMC_PWRBTN# signal is asserted and held active when the system is in a suspend state (S3–S4), the assertion causes a wake event. Once the system has resumed to the S0 state, the 4-second timer starts.

Note: During the time that the SLP_S4# signal is stretched for the minimum assertion width (if enabled by GEN_PMC1.S4ASE), the power button is not a wake event. As a result, it is conceivable that the user will press and continue to hold the power button waiting for the system to awake. Since a 4-second press of the power button is already defined as an unconditional power down, the power button timer will be forced to inactive while the power-cycle timer is in progress. Once the power-cycle timer has expired, the power button awakes the system. Once the minimum PMC_SLP_S4# power cycle expires, the power button must be pressed for another 4 to 5 seconds to create the override condition to S5.



30.2.3.2 Sleep Button

The Advanced Configuration and Power Interface specification defines an optional sleep button. It differs from the power button in that it only is a request to go from S0 to S3–S4 (not S5). Also, in an S5 state, the power button can wake the system, but the sleep button cannot.

Although the SoC does not include a specific signal designated as a sleep button, one of the GPIO signals can be used to create a “Control Method” sleep button. See the Advanced Configuration and Power Interface specification for implementation details.

30.2.3.3 PME_B0 (PCI Power Management Event Bus 0)

The GPE0a_STS.PME_B0_STS bit exists to implement PME#-like functionality for any internal device on Bus 0 with PCI power management capabilities.

30.2.3.4 PMC_RSTBTN# Signal

When the PMC_RSTBTN# pin is detected as active after the 16 ms debounce logic, the SoC attempts to perform a “graceful” reset, by waiting for the relevant internal devices to signal their idleness. If all devices are idle when the pin is detected active, the reset occurs immediately; otherwise, a counter starts. If at any point during the count all devices go idle the reset occurs. If the counter expires and any device is still active, a reset is forced upon the system even though activity is still occurring.

Once the reset is asserted, it remains asserted for 5 to 6 ms regardless of whether the PMC_RSTBTN# input remains asserted or not. It cannot occur again until PMC_RSTBTN# has been detected inactive after the debounce logic, and the system is back to a full S0 state with PMC_PLTRST# inactive. Note that if RST_CNT.FULL_RST is set then PMC_RSTBTN# will result in a Host Reset with Power Cycle.

30.2.4 System Power Planes

The system has several independent power planes, as described in [Table 293](#). Note that when a particular power plane is shut off, it should go to a 0 V level.

Table 293. System Power Planes (Sheet 1 of 2)

Plane	Controlled By	Description
CPU	PMC_SLP_S3#	The SLP_S3# signal can be used to cut the CORE_VCC_S3 rail completely.
Main	PMC_SLP_S3#	When SLP_S3# goes active, power can be shut off to any circuit not required to wake the system from the S3 state. Since the S3 state requires that the memory context be preserved, power must be retained to the main memory. Devices on LPC bus, PCI-Express, and SATA will typically be shut when the Main power plane is shut, although they may have small subsections powered.



Table 293. System Power Planes (Sheet 2 of 2)

Plane	Controlled By	Description
Devices and Memory	PMC_SLP_S4#	When PMC_SLP_S4# goes active, power can be shut off to any circuit not required to wake the system from the S4/S5. Since the memory context does not need to be preserved in the S4/S5 state, the power to the memory can also be shut down. S4 and S5 requests are treated the same so no PMC_SLP_S5# signal is implemented.
Devices	Implementation Specific	Individual subsystems may have their own power plane. For example, GPIO signals may be used to control the power to disk drives, audio amplifiers, or the display screen.
Suspend	PMC_SUSPWRDNACK	The suspend power planes are generally left on whenever the system has a charged main battery or is plugged in to AC power, even in S4/S5. In some cases, it may be preferable to disable the suspend power planes in S4/S5 states to save additional power. This requires some external logic (such as an embedded controller) to decide on the appropriate power plane control actions and ensure that a wake event is still possible (such as the power button).

30.2.4.1 Power Plane Control with PMC_SLP_S3#, PMC_SLP_S4#


The PMC_SLP_S3# output signal can be used to cut power to the system core supply, since it only goes active for the Suspend-to-RAM state (typically mapped to ACPI S3). Power must be maintained to the SoC suspend well, and to any other circuits that need to generate wake signals from the Suspend-to-RAM state. During S3 (Suspend-to-RAM) all signals attached to powered down plans will be tri-stated or driven low, unless they are pulled using a pull-up resistor. Cutting power to the core may be done using the power supply, or by external FETs on the motherboard.

The PMC_SLP_S4# output signal can be used to cut power to the system core supply, as well as power to the system memory, since the context of the system is saved on the disk. Cutting power to the memory may be done using the power supply, or by external FETs on the motherboard.

30.2.4.2 PMC_SLP_S4# and Suspend-To-RAM Sequencing

The PMC_SLP_S4# signal should be used to remove power to system memory. The PMC_SLP_S4# logic in the SoC provides a mechanism to fully cycle the power to the DRAM and/or detect if the power is not cycled for a minimum time.

Note: To use the minimum DRAM power-down feature that is enabled by the GEN_PMC_CON1.S4ASE bit, the DRAM power must be controlled by the PMC_SLP_S4# signal.



30.2.4.3 PMC_CORE_PWROK Signal

When asserted, PMC_CORE_PWROK is an indication to the SoC that its core well power rails are powered and stable. PMC_CORE_PWROK can be driven asynchronously. When PMC_CORE_PWROK is low, the SoC asynchronously asserts PMC_PLTRST#. PMC_CORE_PWROK must not glitch, even if PMC_RSMRST# is low.

It is required that the power rails associated with PCI Express have been valid for 99 ms prior to PWROK assertion in order to comply with the 100 ms T_{PVPERL} PCI Express 2.0 specification on PMC_PLTRST# deassertion.

Note: PMC_RSTBTN# is recommended for implementing the system reset button. This saves external logic that is needed if the PMC_CORE_PWROK input is used. Additionally, it allows for better handling of the processor resets and avoids improperly reporting power failures.

30.2.4.4 PMC_BATLOW# (Battery Low)

The PMC_BATLOW# input can inhibit waking from S3, S4, and S5 states if there is not sufficient power. It also causes an SMI if the system is already in an S0 state.

30.2.5 SMI#/SCI Generation

Upon any enabled SMI event taking place while the SMI_EN.EOS bit is set, the SoC will clear the EOS bit and assert SMI to the CPU core, which will cause it to enter SMM space. SMI assertion is performed using a Virtual Legacy Wire (VLW) message. Prior system generations (those based upon legacy processors) used an actual SMI# pin.

Once the SMI message has been delivered, the SoC takes no action on behalf of active SMI events until Host software sets the End of SMI (EOS) bit. At that point, if any SMI events are still active, the SoC will send another SMI message.

The SCI is a level-mode interrupt that is typically handled by an ACPI-aware operating system. In non-APIC systems (which is the default), the SCI IRQ is routed to one of the 8259 interrupts (IRQ 9, 10, or 11). The 8259 interrupt controller must be programmed to level mode for that interrupt.

In systems using the APIC, the SCI can be routed to interrupts IRQs[11:9] or IRQs[23:20]. The interrupt polarity changes depending on whether it is on an interrupt shareable with a PIRQ or not. The interrupt remains asserted until all SCI sources are removed.

Table 294 shows which events can cause an SMI and SCI. Note that some events can be programmed to cause either an SMI or SCI. The usage of the event for SCI (instead of SMI) is typically associated with an ACPI-based system. Each SMI or SCI source has a corresponding enable and status bit.



Table 294. Causes of SMI and SCI (Sheet 1 of 3)

Event	Status Indication ¹	Enable Condition	Interrupt Result			
			SMI_EN. GBL_SMI_EN=1b		SMI_EN. GBL_SMI_EN=0b	
			PM1_CNT. SCI_EN=1b	PM1_CNT. SCI_EN=0b	PM1_CNT. SCI_EN=1b	PM1_CNT. SCI_EN=0b
Power Button Override ³	PM1_STS_EN. PWRBTNOR_STS	None	SCI	None	SCI	None
RTC Alarm	PM1_STS_EN. RTC_STS	PM1_STS_EN_EN. RTC_EN=1b	SCI	SMI	SCI	None
Power Button Press	PM1_STS_EN. PWRBTN_STS	PM1_STS_EN_EN. PWRBTN_EN=1b	SCI	None	SCI	None
SMI_EN.BIOS_RL S bit written to 1b ⁴	PM1_STS_EN. GBL_STS	PM1_STS_EN_EN. GBL_EN=1b	SCI			
ACPI Timer overflow (2.34 seconds)	PM1_STS_EN. TMROF_STS	PM1_STS_EN_EN. TMROF_EN =1b	SCI	SMI	SCI	None
GPI[n] ⁹	GPE0a_STS. CORE_GPIO_STS[n] ² or GPE0a_STS. SUS_GPIO_STS[n] ²	GPIO_ROUT[n] = 10b & GPE0a_EN. CORE_GPIO_EN[n] ² =1b or GPE0a_EN. SUS_GPIO_EN[n] ² =1b	SCI	None	SCI	None
Internal, Bus 0, PME-Capable Agents (PME_B0)	GPE0a_STS. PME_B0_STS	GPE0_EN. PME_B0_EN=1b	SCI	SMI	SCI	None
BATLOW# pin goes low	GPE0a_STS. BATLOW_STS#	GPE0_EN. BATLOW_EN=1b	SCI	SMI	SCI	None
PCI Express GPE messages	GPE0a_STS. HOT_PLUG_STS	GPE0_EN. HOT_PLUG_EN=1b	SCI	None	SCI	None
Software Generated GPE	GPE0a_STS. SWGPE_STS	GPE0_EN. SWGPE_EN=1b	SCI	SMI	SCI	None
PCI Express Hot Plug SCI Message	GPE0a_STS. HOT_PLUG_STS	GPE0_EN. HOT_PLUG_EN=1b	SCI	None	SCI	None
ASSERT_SCI message from PCIe	GPE0a_STS. PCI_EXP_STS	None (enabled by PCIe controller)	SCI	None	SCI	None




Table 294. Causes of SMI and SCI (Sheet 2 of 3)

Event	Status Indication ¹	Enable Condition	Interrupt Result			
			SMI_EN. GBL_SMI_EN=1b		SMI_EN. GBL_SMI_EN=0b	
			PM1_CNT. SCI_EN=1b	PM1_CNT. SCI_EN=0b	PM1_CNT. SCI_EN=1b	PM1_CNT. SCI_EN=0b
Write to APM register	SMI_STS.apm_sts	SMI_EN.apmc_en = 1'b1	SMI	SMI	None	None
DOSCI message from P-Unit	GPE0a_STS.punit_sci_sts	None (enabled by P-Unit)	SCI	None	SCI	None
DOSMI message from P-Unit	SMI_STS.punit_sci_sts	None (enabled by P-Unit)	SMI	SMI	None	None
DOSCI message from GUNIT ⁵	GPE0a_STS.GUNIT_STS	None (enabled by G-Unit ⁸)	SCI	None	SCI	None
ASSERT_SMI message from SPI ⁵	SMI_STS.SPI_SMI_STS	None (enabled by SPI controller)	SMI		None	
ASSERT_SMI message from PCIe ⁵	SMI_STS.PCI_EXP_SMI_STS	None (enabled by PCIe controller)	SMI		None	
ASSERT_IS_SMI message from USB	SMI_STS.USB_IS_STS	SMI_EN.USB_IS_SMI_EN = 1b	SMI		None	
ASSERT_SMI message from USB	SMI_STS.USB_STS	SMI_EN.USB_SMI_EN = 1b	SMI		None	
ASSERT_SMI message from iLB ⁵	SMI_STS.iLB_SMI_STS	None (enabled by iLB)	SMI		None	
Periodic timer expires	SMI_STS.PERIODIC_STS	SMI_EN.PERIODIC_EN = 1b	SMI		None	
WDT first expiration	SMI_STS.TCO_STS	SMI_EN.TCO_EN = 1b	SMI		None	
64 ms timer expires	SMI_STS.SWSMI_TMR_STS	SMI_EN.SWSMI_TMR_EN = 1b	SMI		None	
PM1_CNT.SLP_EN bit written to 1b	SMI_STS.SMI_ON_SLP_EN_STS	SMI_EN.SMI_ON_SLP_EN = 1b	Sync SMI ⁶		None	
PM1_CNT.GBL_RLS written to 1b	SMI_STS.BIOS_STS	SMI_EN.BIOS_EN = 1b	Sync SMI ⁶		None	
DOSMI message from GUNIT ⁵	SMI_STS.GUNIT_SMI_STS	None (enabled by G-Unit ⁸)	SMI		None	
ASSERT_IS_SMI message from iLB ⁵	SMI_STS.iLB_SMI_STS	None (enabled by iLB)	Sync SMI ⁷		None	





Table 294. Causes of SMI and SCI (Sheet 3 of 3)

Event	Status Indication ¹	Enable Condition	Interrupt Result			
			SMI_EN. GBL_SMI_EN=1b		SMI_EN. GBL_SMI_EN=0b	
			PM1_CNT. SCI_EN=1b	PM1_CNT. SCI_EN=0b	PM1_CNT. SCI_EN=1b	PM1_CNT. SCI_EN=0b
ASSERT_IS_SMI message from PCIe ⁵	SMI_STS. PCI_EXP_SMI_STS	None (enabled by PCIe controller)	SMI		None	
PMC_WAKE_PCIE [3:0]# Assertion	GPE0a_STS.PCI_WAKE[3:0]_STS	GPE0a_STS.PCI_WAKE[3:0]_EN = 1b	SCI	None	SCI	None
GPI[n] ¹⁰	ALT_GPIO_SMI. CORE_GPIO_SMI_STS[n] ² or ALT_GPIO_SMI. SUS_GPIO_SMI_STS[n] ²	GPIO_ROUT[n]=0 1b & ALT_GPIO_SMI. CORE_GPIO_SMI_EN[n] ² =1b or ALT_GPIO_SMI. SUS_GPIO_SMI_EN[n] ² =1b	SMI		None	
USB Per-Port Registers Write Enable bit is changed from 0b to 1b	UPRWC.WE_STS & SMI_STS. USB_IS_STS	UPRWC. WE_SMI_E=1b & SMI_EN. USB_IS_SMI_EN=1b	Sync SMI ⁶		None	

NOTES:

- Most of the status bits (except otherwise is noted) are set according to event occurrence regardless to the enable bit.
- GPIO status bits are set only if enable criteria is true. GPIO_ROUT[n]=10b & GPE0a_EN.x_GPIO_EN[n] for GPE0a_STS.x_GPIO_STS[n] (SCI). GPIO_ROUT[n]=01b & ALT_GPIO_SMI.x_GPIO_SMI_EN[n]=1b for ALT_GPIO_SMI.x_GPIO_SMI_STS[n] (SMI).
- When power button override occurs, the system will transition immediately to S5. The SCI will only occur after the next wake to S0 if the residual status bit (PM1_STS_EN.PWRBTNOR_STS) is not cleared prior to setting PM1_CNT.SCI_EN.
- PM1_STS_EN.GBL_STS being set will cause an SCI, even if the PM1_CNT.SCI_EN bit is not set. Software must take great care not to set the SMI_ENBIOS_RLS bit (which causes PM1_STS_EN.GBL_STS to be set) if the SCI handler is not in place.
- No enable bits for these SCI/SMI messages in the PMC. Enable capability should be implemented in the source unit.
- Sync SMI has the same message opcode toward T-Unit. Special treatment regarding this Sync SMI is holding completion to host till SYNC_SMI_ACK message is received from T-Unit.
- Sync SMI has the same message opcode toward T-Unit. Special treatment regarding this Sync SMI is holding the SSMI_ACK message to iLB till SYNC_SMI_ACK message is received from T-Unit.
- The G-Unit is an internal functional sub-block which forms part of the graphics functional block.
- The GPE0a_STS.CORE_GPIO_STS[31:24] & GPE0a_EN.CORE_GPIO_EN[31:24] register bits correspond to GPIO_S0_SC[7:0]. GPE0a_STS.SUS_GPIO_STS[23:16] & GPE0a_EN.SUS_GPIO_EN[23:16] correspond to GPIO_S5[7:0].
- The ALT_GPIO_SMI.CORE_GPIO_SMI_STS[31:24] & ALT_GPIO_SMI.CORE_GPIO_SMI_EN[15:8] register bits correspond to GPIO_S0_SC[7:0]. ALT_GPIO_SMI.SUS_GPIO_SMI_STS[23:16] & ALT_GPIO_SMI.SUS_GPIO_SMI_EN[7:0] correspond to GPIO_S5[7:0].



30.2.6 Platform Clock Support

The SoC supports up to 6 clocks (PMC_PLT_CLK[5:0]) with a frequency of either 19.2 MHz or 25 MHz. These clocks are available for general system use, where appropriate and each have Control & Frequency register fields associated with them.

Note: Intel recommends 25 MHz. 19.2 MHz is not validated.

30.2.7 INIT# (Initialization) Generation

The INIT# functionality is implemented as a 'virtual wire' internal to the SoC rather than a discrete signal. This virtual wire is asserted based on any one of the events described in below table. When any of these events occur, INIT# is asserted for 16 PCI clocks and then driven high.

INIT#, when asserted, resets integer registers inside the CPU cores without affecting its internal caches or floating-point registers. The cores then begin execution at the power on Reset vector configured during power on configuration.

Table 295. INIT# Assertion Causes

Cause	Comment
PORT92.INIT_NOW transitions from 0b to 1b.	
RST_CNT.SYS_RST = 0b and RST_CNT.RST_CPU transitions from 0b to 1b	

30.3 USB Per-Port Register Write Control

The PMC contains the UPRWC.USB_PER_PORT_WE (USB Per-Port Registers Write Enable) bit. When this bit is written from 0b to 1b, the UPRWC.WE_STS (Write Enable Status) bit is asserted. This transaction initiates sync-SMI if the UPRWC.WE_SMIEN (Write Enable SMI Enable) bit and the SMI_EN.USB_IS_SMI_EN (USB Intel Specific SMI Enable) bit are set to 1b.

30.4 References

Advanced Configuration and Power Interface Specification, Revision 3.0: <http://www.acpi.info/>

30.5 Register Map



30.6 PCU PMC IO Registers

Table 296. Summary of PCI iLB PMC I/O Registers

Offset	Size	Register ID—Description	Default Value
92h	1	"PORT92: Init Register (PORT92)—Offset 92h" on page 4356	00h
B2h	1	"APM Register (APM)—Offset B2h" on page 4357	00h
B3h	1	"APM_STS Register (APM_STS)—Offset B3h" on page 4357	00h
CF9h	1	"RST_CNT: Reset Control Register (RST_CNT)—Offset CF9h" on page 4358	00h

30.6.1 PORT92: Init Register (PORT92)—Offset 92h

Access Method

Type: I/O Register
(Size: 8 bits)

PORT92: 92h

Default: 00h

7	4	0
0	0	0
reserved		alt_a20_gate
		init_now

Bit Range	Default & Access	Description
7:2	0b RO	reserved: Reserved.
1	0b RW	ALT_A20_GATE - Alternate A20 Gate (alt_a20_gate): Legacy bit - kept just in case DOS expects it to be read/write
0	0b RW	INIT_NOW (init_now): When this bit transitions from a 0 to a 1, PMC will sent an INIT# VLW to T-Unit



30.6.2 APM Register (APM)—Offset B2h

Access Method

Type: I/O Register
(Size: 8 bits)

APM: B2h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
apm_reg									

Bit Range	Default & Access	Description
7:0	0b RW	APM_Register (apm_reg): TBD

30.6.3 APM_STS Register (APM_STS)—Offset B3h

Access Method

Type: I/O Register
(Size: 8 bits)

APM_STS: B3h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
apm_sts									

Bit Range	Default & Access	Description
7:0	0b RW	APM_STS (apm_sts): Advanced Power Managment Status Port. used to pass data between the OS and the SMI handler. Basically, this is scratchpad register and is not effected by any other register or function (other than a PCI reset)



30.6.4 RST_CNT: Reset Control Register (RST_CNT)—Offset CF9h

Access Method

Type: I/O Register
(Size: 8 bits)

RST_CNT: CF9h

Default: 00h

7				4					0
0		0		0		0		0	0
reserved					full_rst	rst_cpu	sys_rst	reserved1	

Bit Range	Default & Access	Description
7:4	0b RO	reserved: Reserved.
3	0b RW	Full Reset (FULL_RST) (full_rst): When this bit is set to 1 and bit 1 is set to 1 (indicating Hard Reset, not Soft Reset), and the RST_CPU bit (bit 2) is written from 0 to 1, the PMC will do a full reset, including driving PMU_SLP_S3_B and PMU_SLP_S4_B active (low) for at least 3 (and no more than 5) seconds. When this bit is set, it also causes the full power cycle (PMU_SLP_S3/4_B assertion) in response to PMU_RESETBUTTON_B, COREPWROK, and Watchdog timer reset sources.
2	0b RW	Reset CPU (RST_CPU) (rst_cpu): This bit will cause either a hard or soft reset to the CPU depending on the state of the SYS_RST bit (bit 1 in this same register). The software will cause the reset by setting bit 2 from a 0 to a 1.
1	0b RW	System Reset (SYS_RST) (sys_rst): This bit determines the type of reset caused via RST_CPU (bit 2 of this register). If SYS_RST is 0 when RST_CPU goes from 0 to 1, then the PMC will force INIT# active for 16 PCI clocks. If SYS_RST is 1 when RST_CPU goes from 0 to 1, then the PMC will force PCI reset active for about 1 ms, however the PMU_SLP_S3_B and PMU_SLP_S4_B signals assertion is dependent on the value of the FULL_RST (bit3 of this register).
0	0b RO	reserved1: Reserved.



Bit Range	Default & Access	Description
31	0b RO	reserved4: Reserved.
30	0b RW	PCI Express Wake Disable (PCIEXP_WAKE_DIS) (pciexp_wake_dis): This bit disables the inputs to the PCIEXP_WAKE_STS bit in the PM1 Status register from waking the system. Modification of this bit has no impact on the value of the PCIEXP_WAKE_STS bit. reset_type=Resume Well Reset#
29	0b RW	USB clockless Wake Enable (USB_CLKLESS_EN) (usb_clkless_en): This bit enables the inputs to the USB_CLKLESS_STS bit in the PM1 Status register to wake the system. Modification of this bit has no impact on the value of the USB_CLKLESS_STS bit. reset_type=Resume Well Reset#
28:27	0b RO	reserved5: Reserved.
26	0b RW	RTC Alarm Enable (RTC_EN) (rtc_en): This is the RTC alarm enable bit. It works in conjunction with the SCI_EN bit: RTC_EN SCI_EN Effect when RTC_STS is set 0 x No SMI# or SCI. If system was in S1-S5, no wake even occurs. 1 0 SMI#. If system was in S1-S5, then a wake event occurs before the SMI#. 1 1 SCI. If system was in S1-S5, then a wake event occurs before the SCI. Note: This bit needs to be backed by the RTC well to allow an RTC event to wake after a power failure. In addition to being reset by SRTCST_B assertion, PMC also clears this bit due to certain events: - Power button override - CPU thermal trip reset_type=SRTCST_B
25	0b RO	reserved6: Reserved.
24	0b RW	Power Button Enable (PWRBTN_EN) (pwrbtn_en): This bit is the power button enable. It works in conjunction with the SCI_EN bit: PWRBTN_EN SCI_EN Effect when PWRBTN_STS is set 0 x No SMI# or SCI. 1 0 SMI#. 1 1 SCI. NOTE: PWRBTN_EN has no effect on the PWRBTN_STS bit being set by the assertion of the power button. The Power Button is always enabled as a Wake event. reset_type=Resume Well Reset#
23:22	0b RO	reserved7: Reserved.
21	0b RW	Global Enable (GBL_EN) (gbl_en): The global enable bit. When both the GBL_EN and the GBL_STS are set, PMC generates an SCI. reset_type=PMU_PLTRST_B
20:17	0b RO	reserved8: Reserved.
16	0b RW	Timer Overflow Interrupt Enable (TMROF_EN) (tmrof_en): This is the timer overflow interrupt enable bit. It works in conjunction with the SCI_EN bit: TMROF_EN SCI_EN Effect when TMROF_STS is set 0 x No SMI# or SCI. . 1 0 SMI#. 1 1 SCI. reset_type=PMU_PLTRST_B
15	0b RW	Wake Status (WAK_STS) (wak_sts): This bit is set when the system is in one of the Sleep states (via the SLP_EN bit) and an enabled Wake event occurs. Upon setting this bit, the PMC will transition the system to the ON state. This bit can only be set by hardware and can only be cleared by writing a one to this bit position. This bit is not affected by hard resets caused by a CF9 write, but is reset by RSMRST_B. If a power failure occurs (such as removed batteries) without the SLP_EN bit set, the WAK_STS bit will not be set when the power returns if the AFTER_G3 bit is 0. If the AFTER_G3 bit is 1, then the WAK_STS bit will be set after waking from a power failure. If necessary, the BIOS can clear the WAK_STS bit in this case This is based on discussions with Microsoft. That behavior is not in the ACPI spec. reset_type=RSMRST_B



Bit Range	Default & Access	Description
14	0b RW	PCI Express Wake Status (PCIEXP_WAKE_STS) (pciexp_wake_sts): This bit is set by hardware to indicate that the system woke due to a PCI Express wakeup event. This event can be caused by the PCI Express WAKE# pins (PMU_WAKE_B, PCI_WAKE1_B, PCI_WAKE2_B, PCI_WAKE3_B) being active, or one or more of the PCI Express ports being in beacon state, or receipt of a PCI Express PME message at root port. This bit should only be set when one of these events causes the system to transition from a non-S0 system power state to the S0 system power state. This bit is set independent of the PCIEXP_WAKE_DIS bit. Software writes a 1 to clear this bit. If one of the WAKE# pins is still active during the write or one or more PCI Express ports is in the beacon state or PME message received indication is not cleared in the root port, then the bit will remain Power Management active (i.e. all inputs to this bit are level sensitive) Note: This bit does not itself cause a wake event or prevent entry to a sleeping state. Thus if the bit is 1 and the system is put into a sleeping state, the system will not automatically wake. reset_type=pmc_global_rst_b
13	0b RW	USB clockless Wake Status (USB_CLKLESS_STS) (usb_clkless_sts): This bit is set by hardware to indicate that the system woke due to change in USB serial lines. This bit is set independent of the USB_CLKLESS_EN bit. Software writes a 1 to clear this bit. reset_type=pmc_global_rst_b
12	0b RO	reserved: Reserved.
11	0b RW	Power Button Override (PWRBTNOR_STS) (pwrbtnor_sts): This bit is set any time a Power Button Override Event occurs (i.e. the power button is pressed for at least 4 consecutive seconds), or due to an internal thermal sensor catastrophic condition. These events cause an unconditional transition to the S5 state. The BIOS or SCI handler clears this bit by writing a 1 to it. This bit is not affected by hard resets via CF9h writes, and is not reset by RSMRST_B. Thus, this bit is preserved through power failures. Note that this bit is still asserted when the global SCI_EN is set to '1' then an SCI will be generated. reset_type=SRTCST_B
10	0b RW	RTC Status (RTC_STS) (rtc_sts): This bit is set when the RTC generates an alarm (assertion of the IRQ8# signal), and is not affected by any other enable bit. See RTC_EN for the effect when RTC_STS goes active. This bit is only set by hardware and can only be reset by writing a one to this bit position. This bit is not affected by hard resets caused by a CF9 write, but is reset by RSMRST_B. reset_type=RSMRST_B
9	0b RO	reserved1: Reserved.
8	0b RW	Power Button Status (PWRBTN_STS) (pwrbtn_sts): This bit is set when the PMU_PWRBTN_B signal is asserted (low), independent of any other enable bit. See PWRBTN_EN for the effect when PWRBTN_STS goes active. PWRBTN_STS is always a wake event. This bit is only set by hardware and can be cleared by software writing a one to this bit position. This bit is not affected by hard resets caused by a CF9 write, but is reset by RSMRST_B. If the PMU_PWRBTN_B signal is held low for more than 4 seconds, the PMC clears the PWRBTN_STS bit, sets the PWRBTNOR_STS bit, the system transitions to the S5 state, and only PMU_PWRBTN_B is enabled as a wake event. If PWRBTN_STS bit is cleared by software while the PMU_PWRBTN_B pin is still held low, this will not cause the PWRBTN_STS bit to be set. The PMU_PWRBTN_B signal must go inactive and active again to set the PWRBTN_STS bit. Note that the CPU Thermal Trip and the Internal Thermal Sensors' Catastrophic Condition result in behavior matching the Powerbutton Override, which includes clearing this bit. reset_type=RSMRST_B
7:6	0b RO	reserved2: Reserved.
5	0b RW	GBL Status (GBL_STS) (gbl_sts): This bit is set when an SCI is generated due to the BIOS wanting the attention of the SCI handler. BIOS has a corresponding bit, BIOS_RLS, which will cause an SCI and set this bit. The SCI handler should then clear this bit by writing a 1 to it. This bit will not cause wake events or SMI#. This bit is not effected by SCI_EN. Note: GBL_STS being set will cause an SCI, even if the SCI_EN bit is not set. Software must take great care not to set the BIOS_RLS bit (which causes GBL_STS to be set) if the SCI handler is not in place. reset_type=PMU_PLTRST_B
4:1	0b RO	reserved3 (rserved3): reserved



Type: I/O Register
(Size: 32 bits)

PM1 CNT: [ACPI BASE ADDRESS] + 4h


ACPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ACPI BASE ADDRESS Reference: [B:0, D:31, F:0] + 40h


Default: 00000000h

31				28				24				20				16				12				8				4				0							
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0									
reserved												slp_en				slp_typ				reserved1								gbl_ris				bm_rld				scr_en			

Bit Range	Default & Access	Description
31:14	0b RO	reserved: Reserved.
13	0b WO	Sleep Enable (SLP_EN) (slp_en): This is a write-only bit and reads to it always return a zero. Setting this bit causes the system to sequence into the Sleep state defined by the SLP_TYP field.
12:10	0b RW	Sleep Type (SLP_TYP) (slp_typ): This 3-bit field defines the type of Sleep the system should enter when the SLP_EN bit is set to 1. These bits are reset by SRTCST_B only. Bits Mode Typical Mapping 000 ON S0 001 Puts CPU in S1 state. S1 010 Reserved 011 Reserved 100 Reserved 101 Suspend-To-RAM S3 110 Suspend-To-Disk S4 111 Soft Off S5
9:3	0b RO	reserved1: Reserved.
2	0b RW	GBL_RLS (GBL_RLS) (gbl_rls): This bit is used by the ACPI software to raise an event to the BIOS software. BIOS software has a corresponding enable and status bits to control its ability to receive ACPI events. This bit always reads as 0.
1	0b RW	BM_RLD (BM_RLD) (bm_rld): This bit is treated as a scratchpad bit
0	0b RW	SCI Enable (SCI_EN) (sci_en): SCI Enable (SCI_EN): Selects the SCI interrupt or the SMI# for various events. When this bit is 1, then the events will generate an SCI interrupt. When this bit is 0, these events will generate an SMI#.



Bit Range	Default & Access	Description
31	0b RW	CORE GPIO Status (CORE_GPIO_STS) (core_gpio_sts7): These bits are set any time the corresponding Core GPIO is set up as an input and the corresponding GPIO signal is asserted. Core GPIO pins are: SATA_GP0 (GPIO core 0) SATA_GP1 (GPIO core 1) SATA_LEDN (GPIO core 2) PCIE_CLKREQ0B (GPIO core 3) PCIE_CLKREQ1B (GPIO core 4) PCIE_CLKREQ2B (GPIO core 5) PCIE_CLKREQ3B (GPIO core 6) PCIE_CLKREQ4B (GPIO core 7) If the corresponding enable bit is set in the GPE0a_EN register, then when the CORE_GPIO_STS[n] bit is set, an SCI will be caused, depending on the GPIO_ROUT bits for the corresponding GPIO. These bits are sticky bits and are cleared by writing a 1 back to this bit position. reset_type=Resume Well Reset#
30	0b RW	CORE GPIO Status (CORE_GPIO_STS) (core_gpio_sts6): These bit is part of CORE GPIO Status (CORE_GPIO_STS)
29	0b RW	CORE GPIO Status (CORE_GPIO_STS) (core_gpio_sts5): These bit is part of CORE GPIO Status (CORE_GPIO_STS)
28	0b RW	CORE GPIO Status (CORE_GPIO_STS) (core_gpio_sts4): These bit is part of CORE GPIO Status (CORE_GPIO_STS)
27	0b RW	CORE GPIO Status (CORE_GPIO_STS) (core_gpio_sts3): These bit is part of CORE GPIO Status (CORE_GPIO_STS)
26	0b RW	CORE GPIO Status (CORE_GPIO_STS) (core_gpio_sts2): These bit is part of CORE GPIO Status (CORE_GPIO_STS)
25	0b RW	CORE GPIO Status (CORE_GPIO_STS) (core_gpio_sts1): These bit is part of CORE GPIO Status (CORE_GPIO_STS)
24	0b RW	CORE GPIO Status (CORE_GPIO_STS) (core_gpio_sts0): These bit is part of CORE GPIO Status (CORE_GPIO_STS)
23	0b RW	SUS GPIO Status (SUS_GPIO_STS) (sus_gpio_sts7): These bits are set any time the corresponding Sus GPIO is set up as an input and the corresponding GPIO signal is asserted. Sus GPIO pins are GPIO_SUS0-7. If the corresponding enable bit is set in the GPE0a_EN register, then when the SUS_GPIO_STS[n] bit is set: * If the system is in an S3-S5 state, the event will also wake the system. * If the system is in an S0 state (or upon waking back to an S0 state), an SCI will be caused, depending on the GPIO_ROUT bits for the corresponding GPI. These bits are sticky bits and are cleared by writing a 1 back to this bit position. reset_type=Resume Well Reset#
22	0b RW	SUS GPIO Status (SUS_GPIO_STS) (sus_gpio_sts6): These bits are part of SUS GPIO Status (SUS_GPIO_STS)
21	0b RW	SUS GPIO Status (SUS_GPIO_STS) (sus_gpio_sts5): These bits are part of SUS GPIO Status (SUS_GPIO_STS)
20	0b RW	SUS GPIO Status (SUS_GPIO_STS) (sus_gpio_sts4): These bits are part of SUS GPIO Status (SUS_GPIO_STS)
19	0b RW	SUS GPIO Status (SUS_GPIO_STS) (sus_gpio_sts3): These bits are part of SUS GPIO Status (SUS_GPIO_STS)
18	0b RW	SUS GPIO Status (SUS_GPIO_STS) (sus_gpio_sts2): These bits are part of SUS GPIO Status (SUS_GPIO_STS)
17	0b RW	SUS GPIO Status (SUS_GPIO_STS) (sus_gpio_sts1): These bits are part of SUS GPIO Status (SUS_GPIO_STS)
16	0b RW	SUS GPIO Status (SUS_GPIO_STS) (sus_gpio_sts0): These bits are part of SUS GPIO Status (SUS_GPIO_STS)
15:14	0b RO	reserved (reserved4): Reserved.



Bit Range	Default & Access	Description
13	0b RW	Power Management Event Bus 0 Status (PME_B0_STS) (pme_b0_sts): This bit will be set to 1 by the PMC when any internal device with PCI Power Management capabilities on bus 0 asserts the equivalent of the PME# signal. Additionally, if the PME_B0_EN and SCI_EN bits are set, and the system is in an S0 state, then the setting of the PME_B0_STS bit will generate an SCI (or SMI# if SCI_EN is not set). This bit is cleared by a software write of '1'. Internal devices which can set this bit: - Integrated LAN - HD Audio - SATA - USB
12:11	0b RO	reserved (reserved3): Reserved.
10	0b RW	Battery Low Status (BATLOW_STS) (batlow_sts): This bit will be set to 1 by hardware when the PMU_BATLOW_B signal goes low. Software clears the bit by writing a 1 to the bit position. In Desktop Mode, this bit will be treated as Reserved.
9	0b RW	PCI Express Status (PCI_EXP_STS) (pci_exp_sts): This bit will be set to 1 by hardware to indicate that: - The PME event message was received on one or more of the PCI-Express Ports Note: The PCI PMU_WAKE_B pin and the PCI-Express Beacons have no impact on this bit. Software attempts to clear this bit by writing a 1 to this bit position. If the bit is not cleared and the corresponding PCI_EXP_EN bit is set, the leveltriggered SCI will remain active. Note that a race condition exists where the PCI Express device sends another PME message because the PCI Express device was not serviced within the time when it must resend the message. This may result in a spurious interrupt, and this is comprehended and approved by the PCI Express specification. The window for this race condition is approximately 95-105 milliseconds.
8	0b RW	PCI Express Wake3 Status (PCIE_WAKE3_STS) (pcie_wake3_sts): This bit is set by hardware to indicate that the PCI_WAKE3_B pin was asserted. Software writes a 1 to clear this bit. If PCI_WAKE3_B pin is still active during the write, then the bit will remain active (i.e. input to this bit is level sensitive). reset_type=pmc_global_rst_b
7	0b RW	PCI Express Wake2 Status (PCIE_WAKE2_STS) (pcie_wake2_sts): This bit is set by hardware to indicate that the PCI_WAKE2_B pin was asserted. Software writes a 1 to clear this bit. If PCI_WAKE2_B pin is still active during the write, then the bit will remain active (i.e. input to this bit is level sensitive). reset_type=pmc_global_rst_b
6	0b RW	PCI Express Wake1 Status (PCIE_WAKE1_STS) (pcie_wake1_sts): This bit is set by hardware to indicate that the PCI_WAKE1_B pin was asserted. Software writes a 1 to clear this bit. If PCI_WAKE1_B pin is still active during the write, then the bit will remain active (i.e. input to this bit is level sensitive). reset_type=pmc_global_rst_b
5	0b RW	GUNIT SCI status (GUNIT_SCI_STS) (gunit_sci_sts): This bit will be set if the Graphics Unit requests SCI
4	0b RW	PUNIT SCI status (PUNIT_SCI_STS) (punit_sci_sts): This bit will be set if the Power Management Unit requests SCI
3	0b RW	PCI Express Wake0 Status (PCIE_WAKE0_STS) (pcie_wake0_sts): This bit is set by hardware to indicate that the PMU_WAKE_B pin was asserted. Software writes a 1 to clear this bit. If PMU_WAKE_B pin is still active during the write, then the bit will remain active (i.e. input to this bit is level sensitive). reset_type=pmc_global_rst_b
2	0b RW	Software GPE Status (SWGPE_STS) (swgpe_sts): The SWGPE_CTRL bit (bit 1 of GPE_CTRL reg) acts as a level input to this bit.
1	0b RO	Hot Plug Status (HOT_PLUG_STS) (hot_plug_sts): This bit is set to 1 by hardware when a PCI-Express hotplug event occurs. This will cause an SCI if the HOT_PLUG_EN and SCI_EN bits are set. This bit is cleared by writing a 1 to this bit position. The following events cause this bit to set - Assert_GPE message received from any of the PCI_E ports in the SOC - Assert_HPGPE message received from any of the PCI_E ports in the SOC
0	0b RO	reserved: Reserved.



30.7.5 GPE0a_EN - General Purpose Event 0 Enables (GPE0a_EN)—Offset 28h

Note: This register is symmetrical to the General Purpose Event 0a Status Register.
reset_type=Resume Well Reset#

Access Method

Type: I/O Register
(Size: 32 bits)

GPE0a_EN: [ACPI_BASE_ADDRESS] + 28h

ACPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ACPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 40h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
core_gpio_en			sus_gpio_en		reserved3	pme_b0_en	reserved2	batlow_en
						pci_exp_en	pcie_wake3_en	pcie_wake2_en
						pcie_wake1_en	reserved1	pcie_wake0_en
								swgpe_en
								hot_plug_en
								reserved

Bit Range	Default & Access	Description
31:24	0b RW	CORE GPIO Enable (CORE_GPIO_EN) (core_gpio_en): These bits enable the corresponding CORE_GPIO_STS[n] bits being set to cause an SCI and/or wake event.
23:16	0b RW	SUS GPIO Enable (SUS_GPIO_EN) (sus_gpio_en): These bits enable the corresponding SUS_GPIO_STS[n] bits being set to cause an SCI and/or wake event.
15:14	0b RO	reserved (reserved3): Reserved.
13	0b RW	PME_B0 Enable (PME_B0_EN) (pme_b0_en): Enables the setting of the PME_B0_STS bit to generate a wake event and/or an SCI or SMI#. In addition to being reset by SRTCST_B assertion, the PMC also clears this bit due to certain events: - Power button override - CPU thermal trip reset_type=SRTCST_B
12:11	0b RO	reserved (reserved2): Reserved.
10	0b RW	Low Battery Enable (BATLOW_EN) (batlow_en): This bit enables the PMU_BATLOW_B signal to cause an SMI# or SCI (depending on the SCI_EN bit) when it goes low. This bit does not prevent the PMU_BATLOW_B signal from inhibiting the wake event. In Desktop Mode this bit will be treated as Reserved. In addition to being reset by SRTCST_B assertion, the PMC also clears this bit due to certain events: - Power button override - CPU thermal trip reset_type=SRTCST_B
9	0b RW	PCI Express Enable (PCI_EXP_EN) (pci_exp_en): Enables the PMC to cause an SCI when PCI_EXP_STS bit is set. This is used to allow the PCI Express ports, to cause an SCI due to wake/PME events
8	0b RW	PCI Express Wake3 Enable (PCIE_WAKE3_EN) (pcie_wake3_en): This bit, when set to 1, enables the PCIE_WAKE3_STS to to cause an SCI
7	0b RW	PCI Express Wake2 Enable (PCIE_WAKE2_EN) (pcie_wake2_en): This bit, when set to 1, enables the PCIE_WAKE2_STS to to cause an SCI
6	0b RW	PCI Express Wake1 Enable (PCIE_WAKE1_EN) (pcie_wake1_en): This bit, when set to 1, enables the PCIE_WAKE1_STS to to cause an SCI
5:4	0b RO	reserved (reserved1): Reserved.



Access Method

SMI STS: [ACPI BASE ADDRESS] + 34h


ACPI BASE ADDRESS Reference: [B:0, D:31, F:0] + 40h

Default: 00000000h

[illegible]



Bit Range	Default & Access	Description
31:30	0b RO	reserved : Reserved.
29	0b RW	GUNIT SMI Status (GUNIT_SMI_STS): (gunit_smi_sts) : This bit will be set if Graphics unit is requesting an SMI#. Writing a '1' to this bit position clears this bit to '0'.
28	0b RW	PUNIT SMI Status (PUNIT_SMI_STS): (punit_smi_sts) : This bit will be set if Power Management is requesting an SMI#. Writing a '1' to this bit position clears this bit to '0'.
27	0b RO	reserved (reserved1) : Reserved.
26	0b RO	SPI_SMI Status (SPI_SMI_STS): (spi_smi_sts) : This bit will be set when the SPI logic is requesting an SMI#.
25:22	0b RO	reserved (reserved2) : Reserved.
21	0b RW	reserved (reserved5) : This bit is reserved for future use.
20	0b RO	PCI_EXP_SMI Status (PCI_EXP_SMI_STS): (pci_exp_smi_sts) : 1- PCI Express SMI event occurred. This could be due to a PCI Express PME event.
19	0b RO	reserved (reserved8) : Reserved.
18	0b RO	Intel USB2 Status (USB_IS_STS): (usb_is_sts) : This non-sticky read-only bit is a logical OR of each of the SMI status bits in the Intel-Specific USB2 SMI Status Register ANDed with the corresponding enable bits. Additionally, the Port Disable Write Enable SMI is reported in this bit; the specific status bit for this event is contained in the USB Per-Port Registers Write Control Register in this I/O space. This bit will not be active if the enable bits are not set. Writes to this bit will have no effect. All integrated USB2 Host Controllers are represented with this bit.
17	0b RO	USB Status (USB_STS): (usb_sts) : This bit will be set when the USB logic is requesting an SMI#.
16	0b RO	SMBUS_SMI Status (SMBUS_SMI_STS): (smbus_smi_sts) : This bit will be set when the SMBUS logic is requesting an SMI#.
15	0b RO	ILB_SMI Status (ILB_SMI_STS): (ilb_smi_sts) : This bit will be set when the ILB logic is requesting an SMI#.
14	0b RW	Periodic Status (PERIODIC_STS): (periodic_sts) : This bit will be set at the rate determined by the PER_SMI_SEL bits. If the PERIODIC_EN bit is also set, the PMC will generate an SMI#. This bit is cleared by writing a 1 to this bit position.
13	0b RW	TCO Status (TCO_STS): (tco_sts) : Indicates SMI was caused by the TCO logic. This bit is cleared by writing a 1 to this bit position.
12:10	0b RO	reserved (reserved3) : Reserved.
9	0b RO	GPE0a Status (GPE0a_STS): (gpe0_sts) : There are several status/enable bit pairs in GPE0a_STS/EN that are capable of triggering SMI. This bit is a logical OR of all of those pairs (i.e. this bit is asserted whenever at least one of those pairs has both the status and enable bit asserted). This bit is NOT sticky. Writes to this bit will have no effect. Note: The setting of this bit does not cause the SMI#.
8	0b RO	PM1 Status Register (PM1_STS_REG): (pm1_sts_reg) : This is an OR of the bits (except for bits 5 and 4) in the ACPI PM1_STS_EN Status Reg. Not sticky. Writes to this bit have no effect. Note: The setting of this bit does not cause the SMI#.
7	0b RO	reserved (reserved4) : Reserved.



Bit Range	Default & Access	Description
6	0b RW	Software SMI Timer Status (SWSMI_TMR_STS): (swsmi_tmr_sts): This bit will be set to 1 by the hardware when the Software SMI# Timer expires. This bit will remain 1 until the software writes a 1 to this bit.
5	0b RW	APM_STS (apm_sts): APM Status - SMI# was generated by a write access to the APM control register and if the APMC_EN bit is set. This bit is cleared by writing a one to its bit position.
4	0b RW	SMI_ON_SLP_EN Status (SMI_ON_SLP_EN_STS): (smi_on_slp_en_sts): This bit will be set by the PMC when a write access attempts to set the SLP_EN bit. This bit is cleared by writing a 1 to this bit position
3	0b RO	reserved (reserved6): Reserved.
2	0b RW	BIOS Status (BIOS_STS): (bios_sts): This bit gets set by hardware when a 1 is written by software to the GBL_RLS bit. When both BIOS_EN and the BIOS_STS bit are set, an SMI# will be generated. The BIOS_STS bit is cleared when software writes a 1 to this bit position.
1:0	0b RO	reserved (reserved7): Reserved.

30.7.8 ALT_GPIO_SMI - Alternate GPIO SMI Status and Enable Register. (ALT_GPIO_SMI)—Offset 38h

reset_type=Resume Well Reset#

Access Method

Type: I/O Register
(Size: 32 bits)

ALT_GPIO_SMI: [ACPI_BASE_ADDRESS] + 38h

ACPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ACPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 40h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
core_gpio_smi_sts	core_gpio_smi_sts	sus_gpio_smi_sts	sus_gpio_smi_sts	core_gpio_smi_en	core_gpio_smi_en	sus_gpio_smi_en	sus_gpio_smi_en	

Bit Range	Default & Access	Description
31:24	0b RW	CORE GPIO SMI Status Setting (CORE_GPIO_SMI_STS): (core_gpio_smi_sts): These bits report the status of the corresponding GPIO's. 1 = active, -0 = inactive. These bits are sticky. If the following conditions are true, then an SMI# will be generated: 1. The corresponding enable bit in this register is set 2. The corresponding GPIO must be routed in the GPIO_ROUT register to cause an SMI. 3. The corresponding GPIO must be implemented. Core GPIO pins are: SATA_GP0 (GPIO core 0) SATA_GP1 (GPIO core 1) SATA_LEDN (GPIO core 2) PCIE_CLKREQ0B (GPIO core 3) PCIE_CLKREQ1B (GPIO core 4) PCIE_CLKREQ2B (GPIO core 5) PCIE_CLKREQ3B (GPIO core 6) PCIE_CLKREQ4B (GPIO core 7) All bits are in the resume well. Default for these bits are dependent on the state of the GPIO pins.



30.7.10 GPE_CTRL - General Purpose Event Control (GPE_CTRL)—Offset 40h

Access Method

Type: I/O Register
(Size: 32 bits)

GPE_CTRL: [ACPI_BASE_ADDRESS] + 40h

ACPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ACPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 40h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved				swgpe_ctrl	reserved1			RSVD0

Bit Range	Default & Access	Description
31:18	0b RO	reserved: Reserved.
17	0b RW	Software GPE Control (SWGPE_CTRL) (swgpe_ctrl): This bit allows software to control the assertion of SWGPE_STS bit. This bit is used by hardware as the level input signal for the SWGPE_STS bit in the GPE0a_STS register. When SWGPE_CTRL is 1, SWGPE_STS will be set to 1, and writes to SWGPE_STS with a value of 1 to clear SWGPE_STS will result in SWGPE_STS being set back to 1 by hardware. When SWGPE_CTRL is 0, writes to SWGPE_STS with a value of 1 will clear SWGPE_STS to 0. In addition to being reset by RSMRST_B assertion, the PMC also clears this bit due to certain events: - Power button override - CPU thermal trip
16:4	0b RO	reserved1: Reserved.
3:0	0b RO	RSVD0: Reserved

30.7.11 PM2A_CNT_BLK - PM2a Control Block (PM2A_CNT_BLK)—Offset 50h

Access Method

Type: I/O Register
(Size: 32 bits)

PM2A_CNT_BLK: [ACPI_BASE_ADDRESS] + 50h

ACPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ACPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 40h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved								arb_dis



Bit Range	Default & Access	Description
31:1	0b RO	reserved: Reserved.
0	0b RW	ARB_DIS (ARB_DIS) (arb_dis): This bit is essentially just a scratchpad bit for legacy software compatibility.

30.7.12 TCO_RLD: TCO Reload Register (TCO_RLD)—Offset 60h

Access Method

Type: I/O Register
(Size: 32 bits)

TCO_RLD: [ACPI_BASE_ADDRESS] + 60h

ACPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ACPI BASE ADDRESS Reference: [B:0, D:31, F:0] + 40h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved						RSVD0	tco_val	

Bit Range	Default & Access	Description
31:11	0b RO	reserved: Reserved.
10	0b RO	RSVD0: Reserved
9:0	0b RO	TCO Timer Value (TCO_TVAL) (tco_val): Reading this register will return the current count of the TCO timer. Writing any value to this register will reload the timer to prevent the timeout.

30.7.13 TCO_STS: TCO Timer Status (TCO_STS)—Offset 64h

Access Method

Type: I/O Register
(Size: 32 bits)

TCO_STS: [ACPI BASE ADDRESS] + 64h

ACPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ACPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 40h

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0		
reserved2				second_to_sts	reserved1				tco_timeout	reserved



Bit Range	Default & Access	Description
31:18	0b RO	reserved (reserved2): Reserved.
17	0b RW	Second Timeout Status(SECOND_TO_STS) (second_to_sts): PMC sets this bit to 1 to indicate that the TIMEOUT bit had been (or is currently) set and a second timeout occurred before the TCO_RLD register was written. If this bit is set and the NO_REBOOT config bit is 0, then the PMC will reboot the system after the second timeout. The reboot is done by asserting PMU_PLTRST_B. This bit is only cleared by writing a 1 to this bit or by a RSMRST_B.
16:4	0b RO	reserved (reserved1): Reserved.
3	0b RW	TCO Timeout (TCO_TIMEOUT) (tco_timeout): Bit set to 1 by PMC to indicate that the SMI was caused by TCO timer reaching 0.
2:0	0b RO	reserved: Reserved.

30.7.14 TCO1_CNT: TCO Timer Control (TCO1_CNT)—Offset 68h

Type: I/O Register
(Size: 32 bits)

TCO1 CNT: [ACPI BASE ADDRESS] + 68h

ACPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ACPI BASE ADDRESS Reference: [B:0, D:31, F:0] + 40h

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0					
reserved								os_policy				reserved2				tco_lock				tco_tm_r_halt				reserved1											


Bit Range	Default & Access	Description
31:22	0b RO	reserved: Reserved.
21:20	0b RW	OS_POLICY (os_policy): OS-based software writes to these bits to select the policy that the BIOS will use after the platform resets due the WDT. The following convention is recommended for the BIOS and OS: 00 Boot normally 01 Shut down 10 Dont load OS. Hold in pre-boot state and use LAN to determine next step 11 Reserved
19:13	0b RO	reserved (reserved2): Reserved.
12	0b RW	TCO Lock (TCO_LOCK) (tco_lock): When set to 1, this bit prevents writes from changing the TCO_EN bit (in offset 30h of Power Management I/O space). Once this bit is set to 1, it can not be cleared by software writing a 0 to this bit location. A core-well reset is required to change this bit from 1 to 0. This bit defaults to 0.
11	0b RW	TCO Timer Halt (TCO_TMR_HALT) (tco_tmr_halt): 1 = The TCO timer will halt. It will not count, and thus cannot reach a value that would cause an SMI# or to cause the SECOND_TO_STS bit to be set. This will also prevent rebooting. 0 = The TCO timer is enabled to count. This is the default.

31 PCU – Serial Peripheral Interface (SPI)

The SoC implements a SPI controller as the interface for BIOS Flash storage. This SPI Flash device is also required to support firmware for the Trusted Execution Engine (required). The controller supports a maximum of two SPI Flash devices, using two chip select signals, with speeds of 20 MHz, 33 MHz or 50 MHz.

Note: The default interface speed is 20 MHz.

Note: SPI must operate in descriptor mode for correct operation of the SoC.




31.1 Signal Descriptions

Please see [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function

**Table 298. SPI Signals**

Signal Name	Direction Plat. Power	Description
PCU_SPI_CLK	O V1P8A	SPI Clock: When the bus is idle, the owner will drive the clock signal low.
PCU_SPI_CS[0]#	O V1P8A	SPI Chip Select 0: Used as the SPI bus request signal for the first SPI Flash device.
PCU_SPI_CS[1]#	O V1P8A	SPI Chip Select 1: Used as the SPI bus request signal for the second SPI Flash devices. <i>This signal is muxed and may be used by other functions.</i>
PCU_SPI_MISO	I V1P8A	SPI Master IN Slave OUT: Data input pin for the SoC.
PCU_SPI_MOSI	I/O V1P8A	SPI Master OUT Slave IN: Data output pin for the SoC. Operates as a second data input pin for the SoC when in Single Input, Dual Output Fast Read mode.

Note: All SPI signals are tri-stated with 20k ohm internal weak pull-up until PMC_CORE_PWROK is asserted.

31.2 Features

The SPI controller supports up to two SPI Flash devices using two separate chip select pins. Each SPI Flash device can be up to 16 MB. The SoC SPI interface supports 20 MHz, 33 MHz and 50 MHz SPI Flash devices. No other types of SPI devices are supported.

Communication on the SPI bus is done with a Master – Slave protocol. The Slave is connected to the SoC and is implemented as a tri-state bus.

Note: When GCS.BBS = 00b, LPC is selected as the location for BIOS. The SPI Flash may still contain data and firmware for other SoC functionality.

Note: When GCS.BBS = 11b and a SPI device is detected by the SoC, LPC based BIOS Flash is disabled.

31.2.1 Operation Mode Feature Overview

The SPI controller has two operational modes, Non-Descriptor and Descriptor.

31.2.1.1 Non-Descriptor Mode

If no valid signature is read (either because there is no SPI Flash, or there is an SPI Flash with no valid descriptor), the Flash Controller will operate in a Non-Descriptor mode.

The following features are not supported in Non-Descriptor mode:



- Trusted Execution Engine
- Secure Boot
- Soft Straps
- Two SPI Flash device support
- Hardware sequencing access
- Descriptor-based security access restrictions

Note: When operating in Non-Descriptor mode, software sequencing must be used to access the Flash.

Note: When operating in Non-Descriptor Mode, and a SPI Flash is attached to the SoC, it is required that the Flash Valid Signature, at offset 10h of the Flash Descriptor, does not equal the expected valid value (0FF0A55Ah) or the SPI Controller will wrongly interpret that it has a valid signature and that a Flash Descriptor has been implemented.

31.2.2 Descriptor Mode

Descriptor Mode is required to enable many features of the SoC:


- Trusted Execution Engine
- Secure Boot
- PCI Express* root port configuration
- Supports for two SPI components using two separate chip select pins
- Hardware enforced security restricting master accesses to different regions
- Soft Strap region providing the ability to use Flash NVM to remove the need for pull-up/pull-down resistors for strapping SoC features
- Support for the SPI Fast Read instruction and frequencies greater than 20 MHz
- Support for Single Input, Dual Output Fast reads
- Use of standardized Flash instruction set

SPI Flash Regions

In Descriptor Mode the Flash is divided into five separate regions:

Table 299. SPI Flash Regions

Region	Content
0	Flash Descriptor
1	BIOS
2	Trusted Execution Engine
3	Reserved
4	Platform Data



Only two masters can access the 3 regions: The SoC CPU core running BIOS code and the Trusted Execution Engine. The only required region is Region 0, the Flash Descriptor. Region 0 must be located in the first sector of Device 0.

Flash Regions Sizes

SPI Flash space requirements differ by platform and configuration. [Table 300](#) indicates the space needed in the Flash for each region.

Table 300. Region Size Versus Erase Granularity of Flash Components


Region	Size with 4 KB Blocks	Size with 8 KB Blocks	Size with 64 KB Blocks
Descriptor	4 KB	8 KB	64 KB
BIOS	Varies by Platform	Varies by Platform	Varies by Platform
Trusted Execution Engine	Varies by Platform	Varies by Platform	Varies by Platform

31.2.3 Flash Descriptor


The maximum size of the Flash Descriptor is 4 KB. If the block/sector size of the SPI Flash device is greater than 4 KB, the Flash descriptor will only use the first 4 KB of the first block. The Flash descriptor requires its own block at the bottom of memory (00h). The information stored in the Flash Descriptor can only be written during the manufacturing process as its read/write permissions must be set to Read only when the system containing the SoC leaves the manufacturing floor.

The Flash Descriptor is made up of eleven sections as indicated in below figure.

Figure 131. Flash Descriptor Sections



- The **Reserved** section at offset 0h is related to functionality not supported by the SoC.
- The **Signature** section selects Descriptor Mode as well as verifies if the Flash is programmed and functioning. The data at the bottom of the Flash (offset 10h) must be 0FF0A55Ah in order to be in Descriptor mode.
- The **Descriptor Map** section defines the logical structure of the Flash in addition to the number of components used.
- The **Component** section has information about the SPI Flash in the system including:
 - Density of each component
 - Illegal instructions (such as chip erase)
 - Frequencies for read, fast read and write/erase instructions.
- The **Region** section points to the four other regions as well as the size of each region.
- The **Master** region contains the security settings for the Flash, granting read/write permissions for each region and identifying each master by a requestor ID.
- The **Soft Straps** section contains parameter bits that can be used to configure SoC features and/or behaviors.



- The **Reserved** section between the top of the **Soft Straps** section and the bottom of the **VSCC Table** is reserved for future SoC usages.
- The **VSCC Table** section holds the JEDEC ID and the VSCC (Vendor Specific Component Capabilities) information of the entire SPI Flash supported by the NVM image.
- The **Descriptor Upper Map** section determines the length and base address of the **VSCC Table** section.
- The **OEM Section** is 256 Bytes reserved at the top of the Flash Descriptor for use by an OEM.

31.2.3.1 Master Section

The Master section defines read and write access setting for each region of the SPI device, when the SPI controller is running in Descriptor mode. The master region recognize two masters: SoC CPU core running BIOS code and the Trusted Execution Engine.

Note: Each master is only allowed to do direct reads of its primary regions. The Trusted Execution Engine is may also do a direct read of the BIOS region if it has been given read access to that region. See [Section 31.2.4.1, "Direct Access" on page 4382](#) for further details on direct reads.

Table 301. Region Access Control

Master Read/Write Access		
Region	BIOS	Trusted Execution Engine
Descriptor	N/A	N/A
BIOS	CPU core and BIOS can always read from and write to BIOS Region	Read / Write
Trusted Execution Engine	Read / Write	Trusted Execution can always read from and write to Trusted Execution Engine Region
Platform Data	N/A	N/A

31.2.3.2 Invalid Flash Descriptor Handling

The SoC will respond to an invalid Flash Descriptor with the following:

- The SPI controller will operate in Non-Descriptor mode.
- If the BBS strap (see [Section 31.2.2](#) for details) is set to 1, BIOS direct read access will be forwarded to the SPI Controller without any address translation.
- The HSFSTS.FDV register bits remains at 0b.



- All security checks are disabled and the entire Flash is open for reading and writing. No restriction on the 4k crossing.
- Trusted Execution Engine direct read accesses will not be handled, and the SPI controller will return all 1's.

Note: To ensure BIOS boot access even when the Flash Descriptor is invalid the BIOS region can be placed at the top of Flash Component 0. Placing the BIOS region in any other location will necessitate a full reprogramming of the Flash before boot is possible from that Flash.

31.2.3.3 Descriptor Security Override Strap

A strap is implemented on GPIO_S0_SC[065] to allow descriptor security to be overridden when the strap is sampled low.

If the strap is set (0b), it will have the following effect:

- The Master Region Read Access and Master Region Write Access permissions that were loaded from the Flash Descriptor Master Section will be overridden giving every master read and write permissions to the entire Flash component including areas outside the defined regions.
- BIOS Protected Range 4 (PR4), if enabled by soft strap, will be overridden so that all masters are able to write to the PR4. The PR4 base and limit addresses are fetched and received from soft strap.

31.2.4 Flash Access

There are two types of Flash accesses: Direct Access and Program Register Access.

31.2.4.1 Direct Access

- Direct writes are not allowed for any master.
- The SoC CPU core is only allowed to do a direct read of the BIOS region
- The Trusted Execution Engine is only allowed to do a direct read of the Trusted Execution Engine region. It may also do a direct read of the BIOS region if it has been given read access to that region.


Note: Trusted Execution Engine region direct reads are not supported when the SPI controller is operating in Non-Descriptor mode. The SPI controller returns all 1s if a direct read is attempted.

31.2.4.2 Security

- Calculated Flash Linear Address (FLA) must fall between primary region base/limit

Note: During non descriptor mode, the Flash Physical Address is used instead. Only the two BIOS ranges at the E0000h and F0000h segments just below 1MB are supported.

- Direct Read Cache contents are reset to 0's on a read from a different master



31.2.4.3 Program Register Access

- Reads, Writes and Erases are all supported.
- Program Register Access may use Hardware or Software Sequencing. See [Section 31.3.1, “Hardware vs. Software Sequencing” on page 4389](#) for further information.
- Program Register Accesses are not allowed to cross a 4 KB boundary and can not issue a command that might extend across two components
- Software programs the FLA corresponding to the region desired
 - Software must read the devices Primary Region Base/Limit address to create a FLA.

Each master accesses the Flash through a set of memory mapped registers that are dedicated to each device.

There are two separate control and status registers that software can use when using register access to the Flash. The Hardware Sequencing control/status registers rely on hardware to issue appropriate Flash instructions and atomic sequences. The Software Sequencer puts control into the hands of the software for what instructions to issue and when.

The goal is to support all Flash components through hardware sequencing. Software sequencing is intended only for a back-up strategy.


Note: Software sequencing is required when operating in a non-descriptor mode.

31.2.4.4 Security

- Only primary region masters can access the registers
- Masters are only allowed to read or write those regions they have read/write permission
- Using the Flash region access permissions, one master can give another master read/write permissions to their area
- Using the five Protected Range registers, each master can add separate read/write protection above that granted in the Flash Descriptor for their own accesses
 - Example: BIOS may want to protect different regions of BIOS from being erased
 - Ranges can extend across region boundaries

31.2.5 Serial Flash Device Compatibility Requirements

A variety of serial Flash devices exist in the market. For a serial Flash device to be compatible with the SoC SPI bus, it must meet the minimum requirements detailed in the following sections.



31.2.5.1 BIOS SPI Flash Requirements


The SPI Flash device must meet the following minimum requirements when used explicitly for system BIOS storage.

- Erase size capability of at least one of the following: 64 Kbytes, 8 Kbytes, 4 Kbytes, or 256 bytes.
- Device must support multiple writes to a page without requiring a preceding erase cycle (Refer to [Section 31.2.6.](#))
- Serial Flash device must ignore the upper address bits such that an address of FFFFFFFh aliases to the top of the Flash memory.
- SPI Compatible Mode 0 support (clock phase is 0 and data is latched on the rising edge of the clock).
- If the device receives a command that is not supported or incomplete (less than 8 bits), the device must complete the cycle gracefully without any impact on the Flash content.
- An erase command (page, sector, block, chip, etc.) must set all bits inside the designated area (page, sector, block, chip, etc.) to 1 (Fh).
- Status Register bit 0 must be set to 1 when a write, erase or write to status register is in progress and cleared to 0 when a write or erase is NOT in progress.
- Devices requiring the Write Enable command must automatically clear the Write Enable Latch at the end of Data Program instructions.
- Byte write must be supported. The flexibility to perform a write between 1 byte to 64 bytes is recommended.
- Hardware Sequencing requirements are optional in BIOS only platforms.
- SPI Flash devices that do not meet hardware sequencing command set requirements may work in BIOS only platforms using software sequencing.
- If implementing two SPI flash devices, both devices must have the same erasable block/sector size. Additionally, the first device must be of a binary size.

31.2.5.2 Intel Trusted Execution Engine Firmware SPI Flash Requirements

Intel Trusted Execution Engine Firmware must meet all the requirements in [Section 31.2.5.1](#) plus:

- Hardware sequencing
- The Flash device must have a uniform 4-KB erasable block throughout the entire device or have 64 KB blocks with the first block (lowest address) divided into 4-KB or 8-KB blocks.
- The write protection scheme must meet SPI Flash unlocking requirements for the Trusted Execution Engine



SPI Flash Unlocking Requirements for the Trusted Execution Engine

Flash devices must be globally unlocked (read, write and erase access on the Trusted Execution Engine region) from power on by writing 00h to the Flash's status register to disable write protection.

If the status register must be unprotected, it must use the enable write status register command 50h or write enable 06h.

Opcode 01h (write to status register) must then be used to write a single byte of 00h into the status register. This must unlock the entire device. If the SPI Flash's status register has non-volatile bits that must be written to, bits [5:2] of the Flash's status register must be all 0h to indicate that the Flash is unlocked.

If bits [5:2] return a non zero values, the Trusted Execution Engine firmware will send a write of 00h to the status register. This must keep the Flash part unlocked.

If there is no need to execute a write enable on the status register, then opcodes 06h and 50h must be ignored.

After global unlock, the BIOS has the ability to lock down small sections of the Flash as long as they do not involve the Trusted Execution Engine.

31.2.5.3 Hardware Sequencing Requirements

Below table contains a list of commands and the associated opcodes that a SPI-based serial Flash device must support in order to be compatible with hardware sequencing.

Table 302. Hardware Sequencing Commands and Opcode Requirements

Commands	Opcode	Notes
Write to Status Register	01h	Writes a byte to SPI Flash's status register. Enable Write to Status Register command must be run prior to this command.
Program Data	02h	Single byte or 64 byte write as determined by Flash part capabilities and software.
Read Data	03h	
Write Disable	04h	
Read Status	05h	Outputs contents of SPI Flash's status register
Write Enable	06h	
Fast Read	0Bh	
Enable Write to Status Register	50h	Enables a bit in the status register to allow an update to the status register
Erase	Programmable	Uses the value from LVSSC.LEO register or UVSSC.UEO register depending on the FLA and whether it is below or above the FPBA respectively


Single Input, Dual Output Fast Read

The SPI controller supports the functionality of a single input, dual output fast read: Opcode 3Bh. This instruction has the same timing (including a dummy byte) and the same frequencies as the Fast Read instruction, with the difference that the read data from the Flash is presented on both the MISO and MOSI pins. During a Dual Read instruction, the odd data bits are on the MISO pin and the even data bits are on the MOSI pin.

Note: When Dual Output Fast Read Support is enabled the Fast Read Support must be enabled as well.


Note: Micronix* SPI Flash uses a different opcode for dual fast read, and requires that during the address phase that the address bits are sent on both MOSI and MISO. The SoC does not support this implementation of the protocol.

Figure 132. Dual Output Fast Read Timing



JEDEC ID

Since each serial Flash device may have unique capabilities and commands, the JEDEC ID is the necessary mechanism for identifying the device so the uniqueness of the device can be comprehended by the controller (master). The JEDEC ID uses the opcode 9Fh and a specified implementation and usage model. This JEDEC Standard Manufacturer and Device ID read method is defined in Standard JESD21-C, PRN03-NV.



Error Correction and Detection

If the first 8 bits specify an opcode which is not supported the slave will not respond and wait for the next high to low transition on PCU_SPI_CS[1:0]#. The SPI controller should automatically discard 8 bit words that were not completely received upon de-assertion of the signal.

Any other error correction or detection mechanisms must be implemented in firmware and/or software.

31.2.6 Multiple Page Write Usage Model

The BIOS and Trusted Execution Engine firmware usage models require that the serial Flash device support multiple writes to a page (minimum of 512 writes) without requiring a preceding erase command. The BIOS commonly uses capabilities such as counters that are used for error logging and system boot progress logging. These counters are typically implemented by using byte-writes to 'increment' the bits within a page that have been designated as the counter. The Trusted Execution Engine firmware usage model requires the capability for multiple data updates within any given page. These data updates occur using byte-writes without executing a preceding erase to the given page. Both the BIOS and Trusted Execution Engine firmware multiple page write usage models apply to sequential and non-sequential data writes.

This usage model requirement is based on any given bit only being written once from a '1' to a '0' without requiring the preceding erase. An erase would be required to change bits back to the 1 state.

31.2.7 Soft Flash Protection

There are two types of Flash protection that are not defined in the Flash descriptor supported by the SPI controller:

1. Flash Range Read and Write Protection
2. Global Write Protection

31.2.7.1 Flash Range Read and Write Protection

The SPI controller provides a method for blocking reads and writes to specific ranges in the Flash when the Protected Ranges are enabled. This is achieved by checking the read or write cycle type and the address of the requested command against the base and limit fields of a Read or Write Protected range. Protected range registers are only applied to Programmed Register accesses and have no effect on Direct Reads.

Note: Once BIOS has locked down the Protected BIOS Range registers, this mechanism remains in place until the next system reset.



31.2.7.2 Global Write Protection

The SPI controller has a Write Protection Disable (BCR.WPD) configuration bit. When BCR.WPD=0b, BIOS is not able to perform any write or erase commands to the Flash. When BCR.WPD=1b, protection against BIOS erase and rewrite is disabled. When the lock enable (BCR.LE) bit is set, the BIOS can disable this protection only during System Management Mode (SMM) execution.

If BCR.LE=1b, the SPI controller confirms that only SMM code succeeds to set BCR.WPD=1b. In addition, if BCS.SMIWPEN=1b, the SPI controller should initiate an SMI when non SMM code tries to set BCR.WPD=1b.

31.2.8 SPI Flash Device Recommended Pinout

This table contains the recommended serial Flash device pin-out for an 8-pin device. Use of the recommended pin-out on an 8-pin device reduces complexities involved with designing the serial Flash device onto a motherboard and allows for support of a common footprint usage model (refer to [Section 31.2.9.1](#)).

Table 303. Recommended Pinout for 8-Pin Serial Flash Device

Pin #	Signal
1	Chips Select
2	Data Output
3	Write Protect
4	Ground
5	Data Input
6	Serial Clock
7	Hold / Reset
8	Supply Voltage

Although an 8-pin device is preferred over a 16-pin device due to footprint compatibility, [Table 304](#) contains the recommended serial Flash device pin-out for a 16-pin SOIC.

31.2.9 Serial Flash Device Package

Table 304. Recommended Pinout for 16-Pin Serial Flash Device

Pin #	Signal	Pin #	Signal
1	Hold / Reset	9	Write Protect
2	Supply Voltage	10	Ground
3	No Connect	11	No Connect
4	No Connect	12	No Connect
5	No Connect	13	No Connect

**Table 304. Recommended Pinout for 16-Pin Serial Flash Device**

Pin #	Signal	Pin #	Signal
6	No Connect	14	No Connect
7	Chip Select	15	Serial Data In
8	Serial Data Out	16	Serial Clock

31.2.9.1 Common Footprint Usage Model

To minimize platform motherboard redesign and to enable platform Bill of Material (BOM) selectability, many OEMs design their motherboard with a single common footprint. This common footprint allows the population of a soldered down device or a socket that accepts a leadless device. This enables the board manufacturer to support, using selection of the appropriate BOM, either of these solutions on the same system without requiring any board redesign.

The common footprint usage model is desirable during system debug and by Flash content developers since the leadless device can be easily removed and reprogrammed without damage to device leads. When the board and Flash content is mature for high-volume production, both the socketed leadless solution and the soldered down leaded solution are available through BOM selection.

31.2.9.2 Serial Flash Device Package Recommendations

It is highly recommended that the common footprint usage model be supported. An example of how this can be accomplished is as follows:

- The recommended pinout for 8-pin serial Flash devices is used (refer to [Table 303](#)).
- The 8-pin device is supported in either an 8-contact VDFPN (6x5 mm MLP) package or an 8-contact WSON (5x6 mm) package. These packages can fit into a socket that is land pattern compatible with the wide body SO8 package.
- The 8-pin device is supported in the SO8 (150 mil) and in the wide-body SO8 (200 mil) packages.
- The 16-pin device is supported in the SO16 (300 mil) package.

31.3 Use

31.3.1 Hardware vs. Software Sequencing

Hardware and Software sequencing are the two methods the SoC uses to communicate with the Flash via programming registers for each of the three masters.

31.3.1.1 Hardware Sequencing

Hardware sequencing has a predefined list of opcodes, see [Table 302](#) for more details, with only the erase opcode being programmable. This mode is only available if the descriptor is present and valid. Security Engine firmware must use HW sequencing, so



BIOS must properly set up the SoC to account for this. The Host VSCC registers and VSCC Table have to be correctly configured for BIOS and Security Engine have read/write access to SPI.

31.3.1.2 Software Sequencing

All commands other than the standard (memory) reads must be programmed by the software in the Software Sequencing Control, Flash Address, Flash Data, and Opcode configuration registers. Software must issue either Read ID or Read JEDEC ID, or a combination of the two to determine what Flash component is attached. Based on the Read ID, software can determine the appropriate Opcode instructions sets to set in the program registers and at what SPI frequency to run the command.

Software must program the Flash Linear Address for all commands, even for those commands that don't require address such as the Read ID or Read Status. This is because the SPI controller uses the address to determine which chip select to use.

The opcode type and data byte count fields determine how many clocks to run before deasserting the chip enable. The Flash data is always shifted in for the number of bytes specified and the Flash Data out is always shifted out for the number of data bytes specified. Note that the hardware restricts the burst lengths that are allowed.


A status bit indicates when the cycle has completed on the SPI port allowing the host to know when read results can be checked and/or when to initiate a new command.

The controller also provides the "Atomic Cycle Sequence" for performing erases and writes to the SPI Flash. When this bit is 1 (and the Go bit is written to 1), a sequence of cycles is performed on the SPI interface without allowing other SPI device to arbitrate and interleave cycles to the Flash device. In this case, the specified cycle is preceded by the Prefix Command (8-bit programmable Opcode) and followed by repeated reads to the Status Register (Opcode 05h) until bit 0 indicates the cycle has completed. The hardware does not attempt to check that the programmed cycle is a write or erase.

If a Programmed Access is initiated (Cycle Go written to 1) while the SPI controller is already busy with a Direct Memory Read, then the SPI Host hardware will hold the new Programmed Access pending until the preceding SPI access completes.

Once the SPI controller has committed to running a programmed access, subsequent writes to the programmed cycle registers that occur before it has completed will not modify the original transaction and will result in the assertion of the FCERR bit. Software should never purposely behave in this way and rely on this behavior. However, the FCERR bit provides basic error-reporting in this situation. Writes to the following registers cause the FCERR bit assertion in this situation:

- Software Sequencing Control
- Software Sequencing Address
- SPI Data




With the exception of Illegal Opcodes, the SPI controller does not police which opcodes are valid to be used in SW Sequencing. For example, if SW programs a Dual Output Fast Read opcode, then the Dual Output Fast Read cycle will be issued, independent of whether the Dual Output Fast Read enable bit was set in the component descriptor section.

31.4 Register Map

Refer to [Chapter 3, "Register Access Methods"](#) and [Chapter 4, "Mapping Address Spaces"](#) for additional information.

Figure 133.SIO - HSUART Register Map





31.5 PCU SPI for Firmware Memory Mapped I/O Registers

Table 305. Summary of PCU SPI for Firmware Memory Mapped I/O Registers—SPI_BASE_ADDRESS

Offset	Size	Register ID—Description	Default Value
0h	4	"BFPREG (BIOS_Flash_Primary_Region_bios)—Offset 0h" on page 4394	00001FFFh
4h	2	"HSFSTS (Hardware_Sequencing_Flash_Status_bios)—Offset 4h" on page 4395	0000h
6h	2	"HSFCTL (Hardware_Sequencing_Flash_Control_bios)—Offset 6h" on page 4396	0000h
8h	4	"FADDR (Flash_Address_bios)—Offset 8h" on page 4397	00000000h
10h	4	"FDATA0 (Flash_Data_0_bios)—Offset 10h" on page 4397	00000000h
14h	4	"FDATA1 (Flash_Data_1_bios)—Offset 14h" on page 4398	00000000h
18h	4	"FDATA2 (Flash_Data_2_bios)—Offset 18h" on page 4398	00000000h
1Ch	4	"FDATA3 (Flash_Data_3_bios)—Offset 1Ch" on page 4399	00000000h
20h	4	"FDATA4 (Flash_Data_4_bios)—Offset 20h" on page 4399	00000000h
24h	4	"FDATA5 (Flash_Data_5_bios)—Offset 24h" on page 4400	00000000h
28h	4	"FDATA6 (Flash_Data_6_bios)—Offset 28h" on page 4400	00000000h
2Ch	4	"FDATA7 (Flash_Data_7_bios)—Offset 2Ch" on page 4401	00000000h
30h	4	"FDATA8 (Flash_Data_8_bios)—Offset 30h" on page 4401	00000000h
34h	4	"FDATA9 (Flash_Data_9_bios)—Offset 34h" on page 4402	00000000h
38h	4	"FDATA10 (Flash_Data_10_bios)—Offset 38h" on page 4402	00000000h
3Ch	4	"FDATA11 (Flash_Data_11_bios)—Offset 3Ch" on page 4403	00000000h
40h	4	"FDATA12 (Flash_Data_12_bios)—Offset 40h" on page 4403	00000000h
44h	4	"FDATA13 (Flash_Data_13_bios)—Offset 44h" on page 4404	00000000h
48h	4	"FDATA14 (Flash_Data_14_bios)—Offset 48h" on page 4404	00000000h
4Ch	4	"FDATA15 (Flash_Data_15_bios)—Offset 4Ch" on page 4405	00000000h
50h	4	"FRACC (Flash_Region_Access_Permissions_bios)—Offset 50h" on page 4405	00000202h
54h	4	"FREG0 (Flash_Region_0_bios)—Offset 54h" on page 4406	00001FFFh
58h	4	"FREG1 (Flash_Region_1_bios)—Offset 58h" on page 4407	00001FFFh
5Ch	4	"FREG2 (Flash_Region_2_bios)—Offset 5Ch" on page 4407	00001FFFh
60h	4	"FREG3 (Flash_Region_3_bios)—Offset 60h" on page 4408	00001FFFh
64h	4	"FREG4 (Flash_Region_4_bios)—Offset 64h" on page 4408	00001FFFh
74h	4	"PR0 (Protected_Range_0_bios)—Offset 74h" on page 4409	00000000h
78h	4	"PR1 (Protected_Range_1_bios)—Offset 78h" on page 4410	00000000h
7Ch	4	"PR2 (Protected_Range_2_bios)—Offset 7Ch" on page 4411	00000000h
80h	4	"PR3 (Protected_Range_3_bios)—Offset 80h" on page 4411	00000000h
84h	4	"PR4 (Protected_Range_4_bios)—Offset 84h" on page 4412	00000000h
90h	4	"SSFCTLSTS (Software_Sequencing_Flash_Control_Status_bios)—Offset 90h" on page 4413	F8000000h
94h	2	"PREOP (Prefix_Opcode_Configuration_bios)—Offset 94h" on page 4415	0000h
96h	2	"OPTYPE (Opcode_Type_Configuration_bios)—Offset 96h" on page 4415	0000h
98h	4	"OPMENU0 (Opcode_Menu_Configuration_0_bios)—Offset 98h" on page 4416	00000000h



31.5.2 HSFSTS (Hardware_Sequencing_Flash_Status_bios)—Offset 4h

Hardware sequencing flash status Note: If operating in Non-Descriptor mode, the Software Sequencing Flash Status register must be used.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Hardware_Sequencing_Flash_Status_bios: [SPI_BASE_ADDRESS] + 4h


SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
FLOCKDN	FDV	FDOPSS	RSVD0	SCIP
			BERASE	AEL
				FCERR
				FDONE

Bit Range	Default & Access	Description
15	0b RW/L	Flash Configuration Lock-Down (FLOCKDN): When set to 1, those Flash Program Registers that are locked down by this FLOCKDN bit cannot be written. Once set to 1, this bit can only be cleared by a hardware reset.
14	0b RO	Flash Descriptor Valid (FDV): This bit is set to a 1 if the Flash Controller read the correct Flash Descriptor Signature. If the Flash Descriptor Valid bit is not 1, software cannot use the Hardware Sequencing registers, but must use the software sequencing registers. Any attempt to use the Hardware Sequencing registers will result in the FCERR bit being set.
13	0b RO	Flash Descriptor Override Pin-Strap Status (FDOPSS): This register reflects the value the Flash Descriptor Override Pin-Strap. '1': No override '0': The Flash Descriptor Override strap is set
12:6	0b RO	RSVD0: Reserved
5	0b RO	SPI Cycle In Progress (SCIP): Hardware sets this bit when software sets the Flash Cycle Go (FGO) bit in the Hardware Sequencing Flash Control register. This bit remains set until the cycle completes on the SPI interface. Hardware automatically sets and clears this bit so that software can determine when read data is valid and/or when it is safe to begin programming the next command. Software must only program the next command when this bit is 0.
4:3	00b RO	Block/Sector Erase Size (BERASE): This field identifies the erasable sector size for all Flash components. Valid Bit Settings: 00 : 256 Byte 01 : 4K Byte 10 : 8K Byte 11 : 64K Byte If the FLA (FPBA then this field reflects the value in the LVSCC.LBES register. If the FLA)= FPBA then this field reflects the value in the UVSCC.UBES register.
2	0b RW/1C	Access Error Log (AEL): Hardware sets this bit to a 1 when a direct read was made by BIOS that violated the security restrictions. Or, when a SB transaction to read/write one of the BIOS registers was accepted with bad SAI - see security table. This bit has no affect on indirect accesses. This bit is cleared by software writing a 1.
1	0b RW/1C	Flash Cycle Error (FCERR): Hardware sets this bit to 1 when an program register access is blocked to the FLASH due to one of the protection policies or when any of the programmed cycle registers is written while a programmed access is already in progress. This bit remains asserted until cleared by software writing a 1 or until hardware reset occurs. Software must clear this bit before setting the FLASH Cycle GO bit in this register.



Bit Range	Default & Access	Description
0	0b RW/1C	Flash Cycle Done (FDONE): The SPI controller sets this bit to 1 when the SPI Cycle completes after software previously set the FGO bit. This bit remains asserted until cleared by software writing a 1 or hardware reset. When this bit is set and the SPI SMI# Enable bit is set, an internal signal is asserted to the SMI# generation block. Software must make sure this bit is cleared prior to enabling the SPI SMI# assertion for a new programmed access.

31.5.3 HSFCTL (Hardware_Sequencing_Flash_Control_bios)—Offset 6h

Hardware sequencing flash control.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Hardware_Sequencing_Flash_Control_bios: [SPI_BASE_ADDRESS] + 6h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
FSMIE	RSVD0	FDBC	RRWSP	FCYCLE
				FGO

Bit Range	Default & Access	Description
15	0b RW	Flash SPI SMI# Enable (FSMIE): When set to 1, the SPI asserts an SMI# request whenever the Flash Cycle Done bit is 1.
14	0b RO	RSVD0: Reserved
13:8	00h RW	Flash Data Byte Count (FDBC): This field specifies the number of bytes to shift in or out during the data portion of the SPI cycle. The contents of this register are 0s based with 0b representing 1 byte and 111111b representing 64 bytes. The number of bytes transferred is the value of this field plus 1. This field is ignored for the Block Erase command.
7:3	00h RW	Reserved RW Scratch Pad (RRWSP): Reserved: Scratch Pad bits that are R/W to be used during ECO
2:1	00b RW	FLASH Cycle (FCYCLE): This field defines the Flash SPI cycle type generated to the FLASH when the FGO bit is set as defined below: 00 Read (1 up to 64 bytes by setting FDBC) 01 Reserved 10 Write (1 up to 64 bytes by setting FDBC) 11 Block Erase Implementation Note: if reserved 2'b01 is programmed to this field, flash controller will handle it as if it is 00 (Read)
0	0b RW/SE	Flash Cycle Go (FGO): A write to this register with a 1 in this bit initiates a request to the Flash SPI Arbiter to start a cycle. This register is cleared by hardware when the cycle is granted by the SPI arbiter to run the cycle on the SPI bus. When the cycle is complete, the FDONE bit is set. Software is forbidden to write to any register in the HSFCTL register between the FGO bit getting set and the FDONE bit being cleared. Any attempt to violate this rule will be ignored by hardware. Hardware allows other bits in this register to be programmed for the same transaction when writing this bit to 1. This saves an additional memory write. This bit always returns 0 on reads.

Flash data #1

Access Method

Flash Data 1 bios: [SPI BASE ADDRESS] + 14h

SPI BASE ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 1 (FD1): Similar definition as Flash Data 0. However, this register does not begin shifting until FD0 has completely shifted in/out.

31.5.7 FDATA2 (Flash_Data_2_bios)—Offset 18h

Flash data #2

Access Method

Flash Data 2 bios: [SPI BASE ADDRESS] + 18h

SPI BASE ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31 28 24 20 16 12 8 4 0

0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0 | 0 0 0 0

FD2



Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 2 (FD2): Similar definition as Flash Data 0. However, this register does not begin shifting until FD1 has completely shifted in/out.

31.5.8 FDATA3 (Flash_Data_3_bios)—Offset 1Ch

Flash data #3

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash Data 3 bios: [SPI BASE ADDRESS] + 1Ch

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
FD3								

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 3 (FD3): Similar definition as Flash Data 0. However, this register does not begin shifting until FD2 has completely shifted in/out.

31.5.9 FDATA4 (Flash_Data_4_bios)—Offset 20h

Flash data #4

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_4_bios: [SPI_BASE_ADDRESS] + 20h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

	31			28					24					20					16					12					8					4					0																										
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0																									
																																	FD4↑																																

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 4 (FD4): Similar definition as Flash Data 0. However, this register does not begin shifting until FD3 has completely shifted in/out.



31.5.10 FDATA5 (Flash_Data_5_bios)—Offset 24h

Flash data #5

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_5_bios: [SPI_BASE_ADDRESS] + 24h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 5 (FD5): Similar definition as Flash Data 0. However, this register does not begin shifting until FD4 has completely shifted in/out.

31.5.11 FDATA6 (Flash_Data_6_bios)—Offset 28h

Flash data #6

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_6_bios: [SPI_BASE_ADDRESS] + 28h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 6 (FD6): Similar definition as Flash Data 0. However, this register does not begin shifting until FD5 has completely shifted in/out.



31.5.12 FDATA7 (Flash_Data_7_bios)—Offset 2Ch

Flash data #7

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_7_bios: [SPI_BASE_ADDRESS] + 2Ch

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

FD7

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 7 (FD7): Similar definition as Flash Data 0. However, this register does not begin shifting until FD6 has completely shifted in/out.

31.5.13 FDATA8 (Flash_Data_8_bios)—Offset 30h

Flash data #8

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_8_bios: [SPI_BASE_ADDRESS] + 30h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

FD8

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 8 (FD8): Similar definition as Flash Data 0. However, this register does not begin shifting until FD7 has completely shifted in/out.



31.5.14 FDATA9 (Flash_Data_9_bios)—Offset 34h

Flash data #9

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_9_bios: [SPI_BASE_ADDRESS] + 34h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 9 (FD9): Similar definition as Flash Data 0. However, this register does not begin shifting until FD8 has completely shifted in/out.

31.5.15 FDATA10 (Flash_Data_10_bios)—Offset 38h

Flash data #10

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_10_bios: [SPI_BASE_ADDRESS] + 38h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 10 (FD10): Similar definition as Flash Data 0. However, this register does not begin shifting until FD9 has completely shifted in/out.



31.5.18 FDATA13 (Flash_Data_13_bios)—Offset 44h

Flash data #13

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_13_bios: [SPI_BASE_ADDRESS] + 44h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

FD13

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 13 (FD13): Similar definition as Flash Data 0. However, this register does not begin shifting until FD12 has completely shifted in/out.

31.5.19 FDATA14 (Flash_Data_14_bios)—Offset 48h

Flash data #14

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_14_bios: [SPI_BASE_ADDRESS] + 48h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

FD14

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 14 (FD14): Similar definition as Flash Data 0. However, this register does not begin shifting until FD13 has completely shifted in/out.



31.5.20 FDATA15 (Flash_Data_15_bios)—Offset 4Ch

Flash data #15

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Data_15_bios: [SPI_BASE_ADDRESS] + 4Ch

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
FD15								

Bit Range	Default & Access	Description
31:0	00000000h RW	Flash Data 15 (FD15): Similar definition as Flash Data 0. However, this register does not begin shifting until FD14 has completely shifted in/out.

31.5.21 FRACC (Flash_Region_Access_Permissions_bios)—Offset 50h

Flash region access permissions

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Region_Access_Permissions_bios: [SPI_BASE_ADDRESS] + 50h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000202h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
0	0	0	0	0	0	0	1	0	
BMWAG			BMRAG			BRWA		BRRA	

Flash region 0 (flash descriptor)

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash Region 0 bios: [SPI BASE ADDRESS] + 54h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI BASE ADDRESS Reference: [B:0, D:31, F:0] + 54h

	31		28		24		20		16		12		8		4		0								
	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1							
RSVD0	RL																	RSVD1	RB						

Intel Atom[®] Processor E3800 Product Family
Datasheet
4406



31.5.23 FREG1 (Flash_Region_1_bios)—Offset 58h

Flash region 1 (BIOS)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Region_1_bios: [SPI_BASE_ADDRESS] + 58h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 00001FFFh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	1	1	1
0	0	0	0	0	0	1	1	1
0	0	0	0	0	0	1	1	1
RSVD0	RL				RSVD1	RB		

Bit Range	Default & Access	Description
31:29	0b RO	RSVD0: Reserved
28:16	0000h RO	Region Limit (RL): This specifies address bits 24:12 for the Region 1 Limit. The value in this register is loaded from the contents in the Flash Descriptor.FLREG1.Region Limit
15:13	0b RO	RSVD1: Reserved
12:0	1FFFh RO	Region Base (RB): This specifies address bits 24:12 for the Region 1 Base. The value in this register is loaded from the contents in the Flash Descriptor.FLREG1.Region Base

31.5.24 FREG2 (Flash_Region_2_bios)—Offset 5Ch

Flash region 2 (SEC)

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Flash_Region_2_bios: [SPI_BASE_ADDRESS] + 5Ch


SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 00001FFFh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	1	1	1
0	0	0	0	0	0	1	1	1
0	0	0	0	0	0	1	1	1
RSVD0	RL				RSVD1	RB		

Bit Range	Default & Access	Description
31:29	0b RO	RSVD0: Reserved
28:16	0000h RO	Region Limit (RL): This specifies address bits 24:12 for the Region 2 Limit. The value in this register is loaded from the contents in the Flash Descriptor.FLREG2.Region Limit



31.5.27 PR0 (Protected Range 0 bios)—Offset 74h

Access Method

SPI BASE ADDRESS Reference: [B:0, D:31, F:0] + 54h

31 28 24 20 16 12 8 4 0																																							
0 0																																							
WPE		RSVD0		PRL																RPE		RSVD1		PRB															

Intel Atom[®] Processor E3800 Product Family
Datasheet
4409



Bit Range	Default & Access	Description
14:13	0b RO	RSVD1: Reserved
12:0	0000h RW/L	Protected Range Base (PRB): This field corresponds to FLA address bits 24:12 and specifies the lower base of the protected range. Address bits 11:0 are assumed to be 12'h000 for the base comparison. Any address less than the value programmed in this field is unaffected by this protected range.

31.5.28 PR1 (Protected_Range_1_bios)—Offset 78h

Protected range #1. This register can not be written when the FLOCKDN or PR1LOCKDN bits are set to 1.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Protected_Range_1_bios: [SPI_BASE_ADDRESS] + 78h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
WPE	RSVD0	PRL				RPE	RSVD1	PRB

Bit Range	Default & Access	Description
31	0b RW/L	Write Protection Enable (WPE): When set, this bit indicates that the Base and Limit fields in this register are valid and that writes directed to addresses between them (inclusive) must be blocked by hardware. The base and limit fields are ignored when this bit is cleared.
30:29	0b RO	RSVD0: Reserved
28:16	0000h RW/L	Protected Range Limit (PRL): This field corresponds to FLA address bits 24:12 and specifies the upper limit of the protected range. Address bits 11:0 are assumed to be 12'hFFF for the limit comparison. Any address greater than the value programmed in this field is unaffected by this protected range.
15	0b RW/L	Read Protection Enable (RPE): When set, this bit indicates that the Base and Limit fields in this register are valid and that read directed to addresses between them (inclusive) must be blocked by hardware. The base and limit fields are ignored when this bit is cleared.
14:13	0b RO	RSVD1: Reserved
12:0	0000h RW/L	Protected Range Base (PRB): This field corresponds to FLA address bits 24:12 and specifies the lower base of the protected range. Address bits 11:0 are assumed to be 12'h000 for the base comparison. Any address less than the value programmed in this field is unaffected by this protected range.



31.5.29 PR2 (Protected_Range_2_bios)—Offset 7Ch

Protected range #2. This register can not be written when the FLOCKDN or PR2LOCKDN bits are set to 1.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Protected_Range_2_bios: [SPI_BASE_ADDRESS] + 7Ch

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
WPE	RSVD0	PRL				RPE	RSVD1	PRB

Bit Range	Default & Access	Description
31	0b RW/L	Write Protection Enable (WPE): When set, this bit indicates that the Base and Limit fields in this register are valid and that writes directed to addresses between them (inclusive) must be blocked by hardware. The base and limit fields are ignored when this bit is cleared.
30:29	0b RO	RSVD0: Reserved
28:16	0000h RW/L	Protected Range Limit (PRL): This field corresponds to FLA address bits 24:12 and specifies the upper limit of the protected range. Address bits 11:0 are assumed to be 12'hFFF for the limit comparison. Any address greater than the value programmed in this field is unaffected by this protected range.
15	0b RW/L	Read Protection Enable (RPE): When set, this bit indicates that the Base and Limit fields in this register are valid and that read directed to addresses between them (inclusive) must be blocked by hardware. The base and limit fields are ignored when this bit is cleared.
14:13	0b RO	RSVD1: Reserved
12:0	0000h RW/L	Protected Range Base (PRB): This field corresponds to FLA address bits 24:12 and specifies the lower base of the protected range. Address bits 11:0 are assumed to be 12'h000 for the base comparison. Any address less than the value programmed in this field is unaffected by this protected range.

31.5.30 PR3 (Protected_Range_3_bios)—Offset 80h

Protected range #3. This register can not be written when the FLOCKDN or PR3LOCKDN bits are set to 1.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Protected_Range_3_bios: [SPI_BASE_ADDRESS] + 80h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
WPE	RSVD0	PRL				RPE	RSVD1	PRB

Bit Range	Default & Access	Description
31	0b RW/L	Write Protection Enable (WPE): When set, this bit indicates that the Base and Limit fields in this register are valid and that writes directed to addresses between them (inclusive) must be blocked by hardware. The base and limit fields are ignored when this bit is cleared.
30:29	0b RO	RSVD0: Reserved
28:16	0000h RW/L	Protected Range Limit (PRL): This field corresponds to FLA address bits 24:12 and specifies the upper limit of the protected range. Address bits 11:0 are assumed to be 12'hFFF for the limit comparison. Any address greater than the value programmed in this field is unaffected by this protected range.
15	0b RW/L	Read Protection Enable (RPE): When set, this bit indicates that the Base and Limit fields in this register are valid and that read directed to addresses between them (inclusive) must be blocked by hardware. The base and limit fields are ignored when this bit is cleared.
14:13	0b RO	RSVD1: Reserved
12:0	0000h RW/L	Protected Range Base (PRB): This field corresponds to FLA address bits 24:12 and specifies the lower base of the protected range. Address bits 11:0 are assumed to be 12'h000 for the base comparison. Any address less than the value programmed in this field is unaffected by this protected range.

31.5.31 PR4 (Protected_Range_4_bios)—Offset 84h

Protected range #4. This register use for H/W range protection. All register values are coming from soft-straps, and the Write Protection Enable is controlled also by the Flash Security Override Pin Strap

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)


Protected_Range_4_bios: [SPI_BASE_ADDRESS] + 84h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
WPE	RSVD0	PRL				RPE	RSVD1	PRB



Bit Range	Default & Access	Description
26:24	000b RW/L	SPI Cycle Frequency (SCF): 000 : 20MHz 001 : 33MHz 010 : 66MHz (reserved - not supported on VLV) 011 : 25MHz (reserved - not supported on VLV) 100 : 50MHz (reserved - not supported on VLV-DC) All Others: Reserved This register sets frequency to use for all SPI Software Sequencing cycles (write, erase, fast read, read status, .etc) except for the Read cycle which always run at 20MHz. This register is locked when the SPI Configuration Lock-Down bit is set or when FREQLOCKDN bit is set.
23	0b RW	SPI SMI# Enable (SME): When set to 1, the SPI asserts an SMI# request whenever the Cycle Done Status bit is 1.
22	0b RW	Data Cycle (DC): When set to 1, there is data that corresponds to this transaction. When 0, no data is delivered for this cycle, and the DBC and data fields themselves are don't cares.
21:16	000000b RW	Data Byte Count (DBC): This field specifies the number of bytes to shift in or out during the data portion of the SPI cycle. The valid settings (in decimal) are any value from 0 to 63. The number of bytes transferred is the value of this field plus 1. Note that when this field is 00_0000b, then there is 1 byte to transfer and that 11_1111b means there are 64 bytes to transfer.
15	0b RO	RSVD0: Reserved
14:12	000b RW	Cycle Opcode Pointer (COP): This field selects one of the programmed opcodes in the Opcode Menu to be used as the SPI Command/Opcode. In the case of an Atomic Cycle Sequence, this determines the second command.
11	0b RW	Sequence Prefix Opcode Pointer (SPOP): This field selects one of the two programmed prefix opcodes for use when performing an Atomic Cycle Sequence. A value of 0 points to the opcode in the least significant byte of the Prefix Opcodes register. By making this programmable, the SPI controller supports flash devices that have different opcodes for enabling writes to the data space vs. status register.
10	0b RW	Atomic Cycle Sequence (ACS): When set to 1 along with the SCGO assertion, the SPI controller will execute a sequence of commands on the SPI interface without allowing the LAN component to arbitrate and interleave cycles. The sequence is composed of:) Atomic Sequence Prefix Command (8-bit opcode only)) Primary Command specified below by software (can include address and data)) Polling the Flash Status Register (opcode 8'h05) until bit 0 becomes 1'b0. The SPI Cycle in Progress bit remains set and the Cycle Done Status bit remains unset until the Busy bit in the Flash Status Register returns 0.
9	0b RW/SE	SPI Cycle Go (SCGO): This bit always returns 1'b0 on reads. However, a write to this register with a 1'b1 in this bit starts the SPI cycle defined by the other bits of this register. The SPI Cycle in Progress (SCIP) bit gets set by this action. Hardware must ignore writes to this bit while the Cycle In Progress bit is set. Hardware allows other bits in this register to be programmed for the same transaction when writing this bit to 1'b1. This saves an additional memory write.
8	0b RO	RSVD1: Reserved
7	0b RO/U	Fast Read Supported (FRS): This bit reflects the value of the Fast Read Support bit in the Flash Descriptor Component Section.
6	0b RO/U	Dual Output Fast Read Supported (DOFRS): This bit reflects the value of the Dual Output Fast Read Support bit in the Flash Descriptor Component Section.
5	0b RO	RSVD2: Reserved
4	0b RO	Access Error Log (AEL): This bit reflects the value of the Hardware Sequencing Status.AEL register.
3	0b RW/1C	Flash Cycle Error (FCERR): Hardware sets this bit to 1'b1 when a programmed access is blocked from running on the SPI interface due to one of the protection policies or when any of the programmed cycle registers is written while a programmed access is already in progress. This bit remains asserted until cleared by software writing a 1'b1 or hardware reset.



Bit Range	Default & Access	Description
2	0b RW/1C	Cycle Done Status (CDS): The SPI controller sets this bit to 1'b1 when the SPI Cycle completes i.e., SCIP bit is 1'b0) after software sets the GO bit. This bit remains asserted until cleared by software writing a 1'b1 or hardware reset. When this bit is set and the SPI SMI# Enable bit is set, an internal signal is asserted to the SMI# generation block. Software must make sure this bit is cleared prior to enabling the SPI SMI# assertion for a new programmed access.
1	0b RO	RSVD3: Reserved
0	0b RO	SPI Cycle In Progress (SCIP): Hardware sets this bit when software sets the SPI Cycle Go bit in the Command register. This bit remains set until the cycle completes on the SPI interface. Hardware automatically sets and clears this bit so that software can determine when read data is valid and/or when it is safe to begin programming the next command. Software must only program the next command when this bit is 1'b0.

31.5.33 PREOP (Prefix Opcode Configuration bios)—Offset 94h

Prefix opcode configuration. This register is not writable when the SPI Configuration Lock-Down bit is set or when the PREOPLOCKDN bit is set.

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

Prefix_Opcode_Configuration_bios: [SPI_BASE_ADDRESS] + 94h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI BASE ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 0000h

15				12					8					4					0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
PO1									PO0										

Bit Range	Default & Access	Description
15:8	00h RW/L	Prefix Opcode 1 (PO1): Software programs an SPI opcode into this field that is permitted to run as the first command in an atomic cycle sequence.
7:0	00h RW/L	Prefix Opcode 0 (PO0): Prefix Opcode 0: Software programs an SPI opcode into this field that is permitted to run as the first command in an atomic cycle sequence.

31.5.34 OPTYPE (Opcode_Type_Configuration_bios)—Offset 96h

Opcode type configuration. This register is not writable when the Flash Configuration Lock-Down bit is set or when the OPTYPELOCKDN bit is set. Entries in this register correspond to the entries in the Opcode Menu Configuration register. Note that the definition below only provides write protection for opcodes that have addresses associated with them. Therefore, any erase or write opcodes that do not use an address should be avoided (for example, Chip Erase and Auto-Address Increment Byte Program).

Access Method



Type: Memory Mapped I/O Register
(Size: 16 bits)

Opcode_Type_Configuration_bios: [SPI_BASE_ADDRESS] + 96h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 0000h

15	12	8	4	0
0	0	0	0	0
OT7	OT6	OT5	OT4	OT3

Bit Range	Default & Access	Description
15:14	00b RW/L	Opcode Type 7 (OT7): See the description for bits 1:0
13:12	00b RW/L	Opcode Type 6 (OT6): See the description for bits 1:0
11:10	00b RW/L	Opcode Type 5 (OT5): See the description for bits 1:0
9:8	00b RW/L	Opcode Type 4 (OT4): See the description for bits 1:0
7:6	00b RW/L	Opcode Type 3 (OT3): See the description for bits 1:0
5:4	00b RW/L	Opcode Type 2 (OT2): See the description for bits 1:0
3:2	00b RW/L	Opcode Type 1 (OT1): See the description for bits 1:0
1:0	00b RW/L	Opcode Type 0 (OT0): This field specifies information about the corresponding Opcode 0. This information allows the hardware to 1) know whether to use the address field and 2) provide BIOS and Shared Flash protection capabilities. The hardware implementation also uses the read vs. write information for modifying the behavior of the SPI interface logic. The encoding of the two bits is: 00 = No Address associated with this Opcode and Read Cycle type 01 = No Address associated with this Opcode and Write Cycle type 10 = Address required, Read cycle type 11 = Address required, Write cycle type

31.5.35 OPMENU0 (Opcode_Menu_Configuration_0_bios)—Offset 98h

Opcode (0-3) Menu Configuration. This register is not writable when the SPI Configuration Lock-Down bit is set or when OPMENULOCKDN bit is set. Four entries are available in this register and four are available in OPMENU1 register to give BIOS a sufficient set of commands for communicating with the flash device, while also restricting what malicious software can do. This keeps the hardware flexible enough to operate with a wide variety of SPI devices. It is recommended that BIOS avoid programming Write Enable opcodes in this menu. Malicious software could then perform writes and erases to the SPI flash without using the atomic cycle mechanism. This could cause functional failures in a shared flash environment. Write Enable opcodes should only be programmed in the Prefix Opcodes.

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Opcode_Menu_Configuration_0_bios: [SPI_BASE_ADDRESS] + 98h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
AO3				AO2				AO1

Bit Range	Default & Access	Description
31:24	00h RW/L	Allowable Opcode 3 (AO3): See the description for bits 7:0
23:16	00h RW/L	Allowable Opcode 2 (AO2): See the description for bits 7:0
15:8	00h RW/L	Allowable Opcode 1 (AO1): See the description for bits 7:0
7:0	00h RW/L	Allowable Opcode 0 (AO0): Software programs an SPI opcode into this field for use when initiating SPI commands through the Control Register.

31.5.36 OPMENU1 (Opcode_Menu_Configuration_1_bios)—Offset 9Ch

Opcode (7-4) Menu Configuration. This register is not writable when the SPI Configuration Lock-Down bit is set or when OPMENULOCKDN bit is set. Four entries are available in this register and four are available in OPMENU0 register to give BIOS a sufficient set of commands for communicating with the flash device, while also restricting what malicious software can do. This keeps the hardware flexible enough to operate with a wide variety of SPI devices. It is recommended that BIOS avoid programming Write Enable opcodes in this menu. Malicious software could then perform writes and erases to the SPI flash without using the atomic cycle mechanism. This could cause functional failures in a shared flash environment. Write Enable opcodes should only be programmed in the Prefix Opcodes.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Opcode_Menu_Configuration_1_bios: [SPI_BASE_ADDRESS] + 9Ch

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Power Well: EPW


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
AO7				AO6				AO5



31.5.41 LVSCC (Lower_Vendor_Specific_Component_Capabilities_bios)– Offset C4h





Bit Range	Default & Access	Description
31:13	0b RO	RSVD0: Reserved
12:0	0000h RO/U	Flash Partition Boundary Address (FPBA): This register reflects the value of the Flash Descriptor Component FPBA field



31.5.44 SCS (SMI_Control_Status_Register_bios)—Offset F8h

SMI Control and Status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SMI_Control_Status_Register_bios: [SPI_BASE_ADDRESS] + F8h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 00000080h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0						SMIWPEN	SMIWPST	RSVD1

Bit Range	Default & Access	Description
31:8	0b RO	RSVD0: Reserved
7	1b RW	SMI WPD Enable (SMIWPEN): When this bit is set to a 1'b1, it enables the SPI controller to generate SMI upon not SMM code is trying to set WPD from a 1'b0 to a 1'b1 while LE is set.
6	0b RW/1C	SMI WPD Status (SMIWPST): Set when SMI is generated upon trying to set WPD from a 1'b0 to a 1'b1 by not SMM code (while LE and SMIWPEN are set). Write a 1'b1 to this bit should clear it and clear the SMI (send DEASSERT_SMI)
5:0	0b RO	RSVD1: Reserved

31.5.45 BCR (BIOS Control Register bios)—Offset FCh

BIOS control register. This register formerly was in the 0:31:0 config space

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

BIOS Control Register bios: [SPI BASE ADDRESS] + FCh

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 00000020h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0			
RSVD0																												EISS	RSVD1	SRC	LE	WPT			

Bit Range	Default & Access	Description
31:6	0b RO	RSVD0: Reserved
5	1b RW/L	Enable InSMM_STS (EISS): When this bit is set, the BIOS region is writable only to SMM code. Today BIOS Flash is writable if WPD is a '1'. If this bit [lb]5[rb] is set, then WPD must be a 1'b1 and iosfep_xxx_hprot[lb]1[rb] signal be 1'b1 also. If this bit [lb]5[rb] is clear, then BIOS is writable based only on WPD = 1'b1 and the iosfep_xxx_hprot[lb]1[rb] signal is a don't care.
4	0b RO	RSVD1: Reserved
3:2	00b RW	SPI Read Configuration (SRC): This 2-bit field controls two policies related to BIOS reads on the SPI interface: Bit 3 - Prefetch Enable, Bit 2 - Cache Disable. Settings are summarized below: '00' : No prefetching, but caching enabled. Direct Memory reads load the read buffer cache with 'valid' data, allowing repeated reads to the same range to complete quickly. '01' : No prefetching and no caching. One-to-one correspondence of host BIOS reads to SPI cycles. This value can be used to invalidate the cache. '10' : Prefetching and Caching enabled. This mode is used for long sequences of short reads to consecutive addresses (i.e. shadowing) '11' : Illegal. Caching must be enabled when Prefetching is enabled. This eliminates the need for a complex prefetch-flushing mechanism. Note that if BIOS direct read caching is disabled while data has already been cached internally, subsequent BIOS direct reads will continue to return data from the cache until the cache is invalidated.
1	0b RW/L	Lock Enable (LE): When set, WPD bit could be set from a 1'b0 to a 1'b1 only by SMM code. When cleared, setting the WP bit is allowed in all modes and SMI is not generated. Once set, this bit can only be cleared by a PLTRST#. When this bit is set, EISS - bit [lb]5[rb] of this register is locked down.
0	0b RW	Write Protect Disable (WPD): When set, access to the BIOS space is enabled for both read and write cycles. When cleared, only read cycles are permitted to the flash. When LE bit is set this bit could be written from a 1'b0 to a 1'b1 only by SMM code. When not SMM code tries to writes this bit from a 1'b0 to a 1'b1, bit remain in its 1'b0 value. An Async-SMI is generated (Send ASSERT_SMI) if SMIWPEN is set. This ensures that only SMM code can update BIOS.



31.5.46 TCGC (Trunk_Clock_Gating_Control_bios)—Offset 100h

Trunk_Clock_Gating_Control

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Trunk_Clock_Gating_Control_bios: [SPI_BASE_ADDRESS] + 100h

SPI_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

SPI_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 54h

Default: 00000510h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	0
0	0	0	0	0	0	0	0	0
RSVD0						RSVD	FCGDIS	SBCGCDEF
						SBCGEN	SBCGCNT	

Bit Range	Default & Access	Description
31:12	0b RO	RSVD0: Reserved
11	0b RO	Reserved (RSVD): Reserved.
10	1b RW	FCGDIS: Functional clock gating disable, chicken bit for the func_clk_gating FSM
9	0b RW	SBCGCDEF: SideBanb Control Gating Clock Defeature .Clock gate defeature bit which allows the ISM to transition to idle, but prevents the final clock masking from occurring. The value of this bit goes to the 'cgctrl_clkgatedef' port of the SideBand EndPoint
8	1b RW	SBCGEN: SideBanb Control Gating Clock Enable. Clock gate enable which prevents ISM from leaving ACTIVE. Also prevents the clocks from being gated. The value of this bit goes to the 'cgctrl_clkgaten' port of the SideBand EndPoint
7:0	10h RW	SBCGCNT: SideBanb Control Gating Clock Counter. Idle count limit for ISM which is used to determine the block is idle.Recommended value 8'd16 . The value of those bits goes to the 'cgctrl_idlecnt' ports of the SideBand EndPoint

32 PCU – Universal Asynchronous Receiver/Transmitter (UART)

This section describes the Universal Asynchronous Receiver/Transmitter (UART) serial port integrated into the PCU. The UART may be controlled through programmed IO.

Note: Only a minimal ball-count, comprising receive & transmit signals, UART port is implemented. Further, a maximum baud rate of only 115,200 bps is supported. For this reason, it is recommended that the UART port be used for debug purposes only.



32.1 Signal Descriptions

Please see [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function

Table 306. UART Signals

Signal Name	Direction Plat. Power	Description
PCU_UART_RXD	I V1P8S	COM1 Receive: Serial data input from device pin to the receive port. <i>This signal is muxed and may be used by other functions.</i>
PCU_UART_TXD	O V1P8S	COM1 Transmit: Serial data output from transmit port to the device pin. <i>This signal is muxed and may be used by other functions.</i>



32.2 Features

The serial port consists of a UART which supports a subset of the functions of the 16550 industry standard.

The UART performs serial-to-parallel conversion on data characters received from a peripheral device and parallel-to-serial conversion on data characters received from the processor. The processor may read the complete status of the UART at any time during the functional operation. Available status information includes the type and condition of the transfer operations being performed by the UART and any error conditions.

The serial port may operate in either FIFO or non-FIFO mode. In FIFO mode, a 16-byte transmit FIFO holds data from the processor to be transmitted on the serial link and a 16-byte Receive FIFO buffers data from the serial link until read by the processor.

The UART includes a programmable baud rate generator which is capable of generating a baud rate of between 50 bps and 115,200 bps from a fixed baud clock input of 1.8432 MHz. The baud rate is calculated as follows:

Baud Rate Calculation:


$$\text{BaudRate} = \frac{1.8432 \times 10^6}{16 \times \text{Divisor}}$$

The divisor is defined by the Divisor Latch LSB and Divisor Latch MSB registers. Some common values are shown in [Table 307](#).

Table 307. Baud Rate Examples

Desired Baud Rate	Divisor	Divisor Latch LSB Register	Divisor Latch MSB Register
115,200	1	1h	0h
57,600	2	2h	0h
38,400	3	3h	0h
19,200	6	6h	0h
9,600	12	Ch	0h
4,800	24	18h	0h
2,400	48	30h	0h
1,200	96	60h	0h
300	384	80h	1h
50	2,304	0h	9h

The UART has interrupt support and those interrupts may be programmed to the user's requirements, minimizing the computing required to handle the communications link. Each UART may operate in a polled or an interrupt driven environment as configured by software.



32.2.1 FIFO Operation

32.2.1.1 FIFO Interrupt Mode Operation

Receiver Interrupt

When the Receive FIFO and receiver interrupts are enabled (FIFO Control Register, bit 0 = 1b and Interrupt Enable Register (IIR), bit 0 = 1b), receiver interrupts occur as follows:

- The receive data available interrupt is invoked when the FIFO has reached its programmed trigger level. The interrupt is cleared when the FIFO drops below the programmed trigger level.
- The IIR receive data available indication also occurs when the FIFO trigger level is reached, and like the interrupt, the bits are cleared when the FIFO drops below the trigger level.
- The receiver line status interrupt (IIR = C6h), as before, has the highest priority. The receiver data available interrupt (IIR = C4h) is lower. The line status interrupt occurs only when the character at the top of the FIFO has errors.
- The COM1_LSR.DR bit is set to 1b as soon as a character is transferred from the shift register to the Receive FIFO. This bit is reset to 0b when the FIFO is empty.

Character Time Out Interrupt

When the receiver FIFO and receiver time out interrupt are enabled, a character time out interrupt occurs when all of the following conditions exist:

- At least one character is in the FIFO.
- The last received character was longer than four continuous character times ago (if 2 stop bits are programmed the second one is included in this time delay).
- The most recent processor read of the FIFO was longer than four continuous character times ago.
- The receiver FIFO trigger level is greater than one.

The maximum time between a received character and a timeout interrupt is 160 ms at 300 baud with a 12-bit receive character (i.e., 1 start, 8 data, 1 parity, and 2 stop bits).

When a time out interrupt occurs, it is cleared and the timer is reset when the processor reads one character from the receiver FIFO. If a time out interrupt has not occurred, the time out timer is reset after a new character is received or after the processor reads the receiver FIFO.

Transmit Interrupt

When the transmitter FIFO and transmitter interrupt are enabled (FIFO Control Register, bit 0 = 1b and Interrupt Enable Register, bit 0 = 1b), transmit interrupts occur as follows:



The Transmit Data Request interrupt occurs when the transmit FIFO is half empty or more than half empty. The interrupt is cleared as soon as the Transmit Holding Register is written (1 to 16 characters may be written to the transmit FIFO while servicing the interrupt) or the Interrupt Identification Register is read.

32.2.1.2 FIFO Polled Mode Operation

With the FIFOs enabled (FIFO Control register, bit 0 = 1b), setting Interrupt Enable register (IER), bits 3:0 = 000b puts the serial port in the FIFO polled mode of operation. Since the receiver and the transmitter are controlled separately, either one or both may be in the polled mode of operation. In this mode, software checks receiver and transmitter status through the Line Status Register (LSR). As stated in the register description:

- LSR[0] is set as long as there is one byte in the receiver FIFO.
- LSR[1] through LSR[4] specify which error(s) has occurred for the character at the top of the FIFO. Character error status is handled the same way as interrupt mode. The Interrupt Identification Register is not affected since IER[2] = 0b.
- LSR[5] indicates when the transmitter FIFO needs data.
- LSR[6] indicates that both the transmitter FIFO and shift register are empty.
- LSR[7] indicates whether there are any errors in the receiver FIFO.

32.3 Use

32.3.1 Base I/O Address

32.3.1.1 COM1

The base I/O address for the COM1 UART is fixed to 3F8h.

32.3.2 Legacy Interrupt


32.3.2.1 COM1

The legacy interrupt assigned to the COM1 UART is fixed to IRQ4.

32.4 UART Enable/Disable

The COM1 UART may be enabled or disabled using the UART_CONT.COM1EN register bit. By default, the UART is disabled.

Note: It is recommended that the UART be disabled during normal platform operation since it is a PIO device and, as such, can prevent residency in lower power states by the processor.



32.5 IO Mapped Registers

There are 12 registers associated with the UART. These registers share eight address locations in the IO address space. Table 308 shows the registers and their addresses as offsets of a base address. Note that the state of the COM1_LCR.DLAB register bit, which is the most significant bit (MSB) of the Serial Line Control register, affects the selection of certain of the UART registers. The COM1_LCR.DLAB register bit must be set high by the system software to access the Baud Rate Generator Divisor Latches.

Table 308. Register Access List

Register Address (Offset to Base IO Address)	COM1_LCR.DLAB B Value	Register Access Type	Register Accessed
0h	0b	RO	Receiver Buffer ¹
0h	0b	WO	Transmitter Holding ¹
0h	1b	RW	Divisor Latch LSB (Lowest Significant Bit) ¹
1h	0b	RW	Interrupt Enable ²
1h	1b	RW	Divisor Latch MSB (Most Significant Bit) ²
2h	xb	RO	Interrupt Identification ³
2h	xb	WO	FIFO Control ³
3h	xb	RW	Line Control
4h	xb	RW	Modem Control ⁴
5h	xb	RO	Line Status
6h	xb	RO	Modem Status ⁴
7h	xb	RW	Scratchpad

Notes:

1. These registers are consolidated in the Receiver Buffer / Transmitter Holding Register (COM1_RX_TX_BUFFER)
2. These registers are consolidated in the Interrupt Enable Register (COM1_IER)
3. These registers are consolidated in the Interrupt Identification / FIFO Control Register (COM1_IIR)
4. These registers are implemented but unused since the UART signals related to modem interaction are not implemented.



32.6 PCU iLB UART IO Registers

Table 309. Summary of PCU iLB UART I/O Registers—

Offset	Size	Register ID—Description	Default Value
3F8h	1	"Receiver Buffer / Transmitter Holding Register (COM1_Rx_Tx_Buffer)—Offset 3F8h" on page 4432	00h
3F9h	1	"Interrupt Enable Register (COM1_IER)—Offset 3F9h" on page 4433	00h
3FAh	1	"Interrupt Identification / FIFO Control Register (COM1_IIR)—Offset 3FAh" on page 4434	01h
3FBh	1	"Line Control Register (COM1_LCR)—Offset 3FBh" on page 4435	00h
3FCh	1	"Modem Control Register (COM1_MCR)—Offset 3FCh" on page 4436	00h
3FDh	1	"Line Status Register (COM1_LSR)—Offset 3FDh" on page 4437	60h
3FEh	1	"Modem Status Register (COM1_MSR)—Offset 3FEh" on page 4438	00h
3FFh	1	"Scratchpad Register (COM1_SCR)—Offset 3FFh" on page 4440	00h

32.6.1 Receiver Buffer / Transmitter Holding Register (COM1_Rx_Tx_Buffer)—Offset 3F8h

This register is a combination of three registers: the receiver buffer register (RBR) that is a read-only register when DLAB=0, the transmitter holding register (THR) that is a write-only register when DLAB=0 and the divisor latch LSB (DLL) register when DLAB=1.

Access Method

Type: I/O Register
(Size: 8 bits)

COM1_Rx_Tx_Buffer: 3F8h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
				RBR_THR_DLL			



Bit Range	Default & Access	Description																																												
7:0	00h RW	Receiver buffer / transmitter holding (RBR_THR_DLL): When reading from this register and DLAB=1'b0, it contains the byte received if no FIFO is used, or the oldest unread byte with FIFO's. If FIFO buffering is used, each new read action of the register will return the next byte, until no more bytes are present. Bit 0 in the LSR line status register can be used to check if all received bytes have been read. This bit will change to zero if no more bytes are present. When writing to this register and DLAB=1'b0, it is used to buffer outgoing characters. If no FIFO buffering is used, only one character can be stored. Otherwise the amount of characters depends on the type of UART. Bit 5 in the LSR, line status register can be used to check if new information must be written to this register. The value 1'b1 indicates that the register is empty. If FIFO buffering is used, more than one character can be written to the transmitter holding register when the bit signals an empty state. There is no indication of the amount of bytes currently present in the transmitter FIFO. This register is not used to transfer the data directly. The byte is first transferred to a shift register where the information is broken in single bits which are sent one by one. If DLAB=1'b1, this register is used as DLL (Divisor Latch LSB). For generating its timing information, each UART uses an oscillator generating a frequency of about 1.8432 MHz. This frequency is divided by 16 to generate the time base for communication. Because of this division, the maximum allowed communication speed is 115200 bps. Modern UARTS like the 16550 are capable of handling higher input frequencies up to 24 MHz which makes it possible to communicate with a maximum speed of 1.5 Mbps. On PC's higher frequencies than the 1.8432 MHz are rarely seen because this would be software incompatible with the original XT configuration. This 115200 bps communication speed is not suitable for all applications. To change the communication speed, the frequency can be further decreased by dividing it by a programmable value. For very slow communications, this value can go beyond 255. Therefore, the divisor is stored in two separate bytes, the divisor latch registers DLL and DLM which contain the least, and most significant byte. For error free communication, it is necessary that both the transmitting and receiving UART use the same time base. Default values have been defined which are commonly used. The table shows the most common values with the appropriate settings of the divisor latch bytes. Note that these values only hold for a PC compatible system where a clock frequency of 1.8432 MHz is used. <table><tr><th>Speed(bps)</th><th>Divisor</th><th>DLL</th><th>DLM</th></tr><tr><td>50</td><td>2,304</td><td>0x00</td><td>0x09</td></tr><tr><td>1,200</td><td>96</td><td>0x60</td><td>0x00</td></tr><tr><td>4,800</td><td>24</td><td>0x18</td><td>0x00</td></tr><tr><td>19,200</td><td>6</td><td>0x06</td><td>0x00</td></tr><tr><td>57,600</td><td>2</td><td>0x02</td><td>0x00</td></tr><tr><td>300</td><td>384</td><td>0x80</td><td>0x01</td></tr><tr><td>2,400</td><td>48</td><td>0x30</td><td>0x00</td></tr><tr><td>9,600</td><td>12</td><td>0x0C</td><td>0x00</td></tr><tr><td>38,400</td><td>3</td><td>0x03</td><td>0x00</td></tr><tr><td>115,200</td><td>1</td><td>0x01</td><td>0x00</td></tr></table>	Speed(bps)	Divisor	DLL	DLM	50	2,304	0x00	0x09	1,200	96	0x60	0x00	4,800	24	0x18	0x00	19,200	6	0x06	0x00	57,600	2	0x02	0x00	300	384	0x80	0x01	2,400	48	0x30	0x00	9,600	12	0x0C	0x00	38,400	3	0x03	0x00	115,200	1	0x01	0x00
Speed(bps)	Divisor	DLL	DLM																																											
50	2,304	0x00	0x09																																											
1,200	96	0x60	0x00																																											
4,800	24	0x18	0x00																																											
19,200	6	0x06	0x00																																											
57,600	2	0x02	0x00																																											
300	384	0x80	0x01																																											
2,400	48	0x30	0x00																																											
9,600	12	0x0C	0x00																																											
38,400	3	0x03	0x00																																											
115,200	1	0x01	0x00																																											

32.6.2 Interrupt Enable Register (COM1_IER)—Offset 3F9h

This register is a combination of two registers: the interrupt enable register (IER) when DLAB=0 and the divisor latch MSB (DLM) register when DLAB=1.


Access Method

Type: I/O Register
(Size: 8 bits)

COM1_IER: 3F9h

Default: 00h

7	6	5	4	3	2	1	0
0	0	0	0	0	0	0	0
				IER_DLM			



Bit Range	Default & Access	Description
7:0	00h RW	Interrupt Enable (IER_DLM): If DLAB=1'b0 , This field is used as interrupt enable register. The smartest way to perform serial communications on a PC is using interrupt driven routines. In that configuration, it is not necessary to poll the registers of the UART periodically for state changes. The UART will signal each change by generating a processor interrupt. A software routine must be present to handle the interrupt and to check what state change was responsible for it. Interrupts are not generated, unless the UART is told to do so. This is done by setting bits in the IER, interrupt enable register. A bit value 1 indicates, that an interrupt may take place. Bit Description 0 ERBFI - Enable Received Data Available Interrupt. This is used to enable/disable the generation of Received Data Available Interrupt and the Character Timeout Interrupt (if in FIFO mode and FIFOs enabled). These are the second highest priority interrupts. 1 ETBEI - Enable Transmit Holding Register Empty Interrupt. This is used to enable/disable the generation of Transmitter Holding Register Empty Interrupt. This is the third highest priority interrupt. 2 ELSI - Enable Receiver Line Status Interrupt. This is used to enable/disable the generation of Receiver Line Status Interrupt. This is the highest priority interrupt. 3 EDSSI - Enable Modem Status Interrupt. This is used to enable/disable the generation of Modem Status Interrupt. This is the fourth highest priority interrupt. 4 Reserved and read as zero 5 Reserved and read as zero 6 Reserved and read as zero 7 PTIME - Programmable THRE Interrupt Mode Enable that can be written to only when THRE_MODE_USER == Enabled, always readable. This is used to enable/disable the generation of THRE Interrupt. If DLAB=1'b1 , this register is used as DLM (Divisor Latch MSB). See DLL field description in the Rx_Tx_Buffer register.

32.6.3 Interrupt Identification / FIFO Control Register (COM1_IIR)—Offset 3FAh

This register is a combination of two registers: the interrupt identification register (IIR) that is a read-only register and the FIFO control register (FCR) that is a write-only register. If FIFOs are not implemented, the FIFO control register does not exist and writing to this register address has no effect.

Access Method

Type: I/O Register
(Size: 8 bits)

COM1_IIR: 3FAh

Default: 01h

7	4	0
0	0	0
FERT	TET	IIR

Bit Range	Default & Access	Description
7:6	00b RO	FIFOs Enabled / RCVR Trigger (FERT): Read from this field is used to indicate whether the FIFOs are enabled or disabled. '00' - disabled '11' - enabled Write to this field is used to select the trigger level in the receiver FIFO at which the Received Data Available Interrupt is generated. In auto flow control mode it is used to determine when the rts_n signal is de-asserted. The following trigger levels are supported: '00' - 1 character in the FIFO '01' - FIFO 1/4 full '10' - FIFO 1/2 full '11' - FIFO 2 less than full
5:4	00b RO	TX Empty Trigger (TET): Read from this field is reserved and should return zero Write to this field is used to select the empty threshold level at which the THRE Interrupts are generated when the mode is active. The following trigger levels are supported: '00' - FIFO empty '01' - 2 characters in the FIFO '10' - FIFO 1/4 full '11' - FIFO 1/2 full



Bit Range	Default & Access	Description
3:0	0001b RO	Interrupt ID (IIR): Read from this field indicates the highest priority pending interrupt which can be one of the following types: '0000' - modem status '0001' - no interrupt pending '0010' - THR empty '0100' - received data available '0110' - receiver line status '0111' - busy detect '1100' - character timeout Write to this field is split to four bits: Bit Description 3 DMA Mode, determines the DMA signalling mode used: '0' - mode 0, '1' - mode 1 2 XMIT FIFO Reset, resets the control portion of the transmit FIFO and treats the FIFO as empty. 1 RCVR FIFO Reset, resets the control portion of the receive FIFO and treats the FIFO as empty. 0 FIFO Enable. This enables/disables the transmit (XMIT) and receive (RCVR) FIFOs. Whenever the value of this bit is changed both the XMIT and RCVR controller portion of FIFOs is reset.

32.6.4 Line Control Register (COM1_LCR)—Offset 3FBh

The LCR, line control register is used at initialisation to set the communication parameters. Parity and number of data bits can be changed for example. The register also controls the accessibility of the DLL and DLM registers. These registers are mapped to the same I/O port as the RBR, THR and IER registers. Because they are only accessed at initialisation when no communication occurs this register swapping has no influence on performance.

Access Method


Type: I/O Register
(Size: 8 bits)

COM1_LCR: 3FBh

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
DLAB	BC	SP	EPS	PEN	STOP		DLS

Bit Range	Default & Access	Description
7	0b RW	Divisor Latch Access Bit (DLAB): This field is used to enable reading and writing of the Divisor Latch register (DLL and DLH) to set the baud rate of the UART. This bit must be cleared after initial baud rate setup in order to access other registers. '0' - RBR, THR and IER accessible '1' - DLL and DLM accessible See Rx_Tx_Buffer and IER registers description for more details.
6	0b RW	Break Control (BC): This is used to cause a break condition to be transmitted to the receiving device. If set to one the serial output is forced to the spacing (logic 0) state. When not in Loopback Mode, as determined by MCR[4], the serial output is forced low until the Break bit is cleared. If SIR_MODE == Enabled and active (MCR[6] set to one) the sir_out_n line is continuously pulsed. When in Loopback Mode, the break condition is internally looped back to the receiver and the sir_out_n line is forced low.
5	0b RO	Stick Parity (SP): Reserved and read as zero
4	0b RW	Even Parity Select (EPS): This is used to select between even and odd parity, when parity is enabled (PEN set to one). If set to one, an even number of logic 1s is transmitted or checked. If set to zero, an odd number of logic 1s is transmitted or checked.
3	0b RW	Parity Enable (PEN): This is used to enable and disable parity generation and detection in transmitted and received serial character respectively. '0' - parity disabled '1' - parity enabled



Bit Range	Default & Access	Description
2	0b RW	Number of Stop bits (STOP): This is used to select the number of stop bits per character that the peripheral transmits and receives. If set to zero, one stop bit is transmitted in the serial data. If set to one and the data bits are set to 5 (LCR[1:0] set to zero) one and a half stop bits is transmitted. Otherwise, two stop bits are transmitted. Note that regardless of the number of stop bits selected, the receiver checks only the first stop bit. '0' - 1 stop bit '1' - 1.5 stop bits when DLS (LCR[1:0]) is zero, else 2 stop bit
1:0	00b RW	Data Length Select (DLS): This is used to select the number of data bits per character that the peripheral transmits and receives. The number of bit that may be selected areas follows: '00' - 5 bits '01' - 6 bits '10' - 7 bits '11' - 8 bits

32.6.5 Modem Control Register (COM1_MCR)—Offset 3FCh

The MCR, modem control register is used to perform handshaking actions with the attached device. In the original UART series including the 16550, setting and resetting of the control signals must be done by software. The new 16750 is capable of handling flow control automatically, thereby reducing the load on the processor.

Access Method

Type: I/O Register
(Size: 8 bits)

COM1_MCR: 3FCh

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
RSVD0	SIRE	AFCE	LB	OUT2	OUT1	RTS	DTR

Bit Range	Default & Access	Description
7	0b RO	RSVD0: Reserved
6	0b RW	SIR Mode Enable (SIRE): Writeable only when SIR_MODE == Enabled, always readable. This is used to enable/disable the IrDA SIR Mode features as described in 'IrDA 1.0 SIR Protocol' on Synopsys UART specification. '0' - IrDA SIR Mode disabled '1' - IrDA SIR Mode enabled
5	0b RW	Auto Flow Control Enable (AFCE): Writeable only when AFCE_MODE == Enabled, always readable. When FIFOs are enabled and the Auto Flow Control Enable (AFCE) bit is set, Auto Flow Control features are enabled as described in 'Auto Flow Control' on Synopsys UART specification. '0' - Auto Flow Control Mode disabled '1' - Auto Flow Control Mode enabled
4	0b RW	LoopBack (LB): This is used to put the UART into a diagnostic mode for test purposes. If operating in UART mode (SIR_MODE != Enabled or not active, MCR[6] set to zero), data on the sout line is held high, while serial data output is looped back to the sin line, internally. In this mode all the interrupts are fully functional. Also, in loopback mode, the modem control inputs (dsr_n, cts_n, ri_n, dcd_n) are disconnected and the modem control outputs (dtr_n, rts_n, out1_n, out2_n) are looped back to the inputs, internally. If operating in infrared mode (SIR_MODE == Enabled AND active, MCR[6] set to one), data on the sir_out_n line is held low, while serial data output is inverted and looped back to the sir_in line.
3	0b RW	Auxiliary output 2 (OUT2): This is used to directly control the user-designated Output2 (out2_n) output. The value written to this location is inverted and driven out on out2_n, that is: '0' - out2_n de-asserted (logic 1) '1' - out2_n asserted (logic 0) Note that in Loopback mode (MCR[4] set to one), the out2_n output is held inactive high while the value of this location is internally looped back to an input.



Bit Range	Default & Access	Description
2	0b RW	Auxiliary output 1 (OUT1): This is used to directly control the user-designated Output1 (out1_n) output. The value written to this location is inverted and driven out on out1_n, that is: '0' - out1_n de-asserted (logic 1) '1' - out1_n asserted (logic 0) Note that in Loopback mode (MCR[4] set to one), the out1_n output is held inactive high while the value of this location is internally looped back to an input.
1	0b RW	Request to Send (RTS): This is used to directly control the Request to Send (rts_n) output. The Request To Send (rts_n) output is used to inform the modem or data set that the UART is ready to exchange data. When Auto RTS Flow Control is not enabled (MCR[5] set to zero), the rts_n signal is set low by programming MCR[1] (RTS) to a high. In Auto Flow Control, AFCE_MODE == Enabled and active (MCR[5] set to one) and FIFOs enable (FCR[0] set to one), the rts_n output is controlled in the same way, but is also gated with the receiver FIFO threshold trigger (rts_n is inactive high when above the threshold). The rts_n signal is de-asserted when MCR[1] is set low. Note that in Loopback mode (MCR[4] set to one), the rts_n output is held inactive high while the value of this location is internally looped back to an input. Note that PCU-UART does not implement the Request to Send (rts_n) output.
0	0b RW	Data Terminal Ready (DTR): This is used to directly control the Data Terminal Ready (dtr_n) output. The value written to this location is inverted and driven out on dtr_n, that is: '0' - dtr_n de-asserted (logic 1) '1' - dtr_n asserted (logic 0) The Data Terminal Ready output is used to inform the modem or data set that the UART is ready to establish communications. Note that in Loopback mode (MCR[4] set to one), the dtr_n output is held inactive high while the value of this location is internally looped back to an input. Note that PCU-UART does not implement the Data Terminal Ready (dtr_n) output.

32.6.6 Line Status Register (COM1_LSR)—Offset 3FDh

The LSR, line status register shows the current state of communication. Errors are reflected in this register. The state of the receive and transmit buffers is also available.

Access Method


Type: I/O Register
(Size: 8 bits)

COM1_LSR: 3FDh

Default: 60h

7	4	0
0	1	0
RFE	TEMT	THRE
BI	FE	PE
	OE	DR

Bit Range	Default & Access	Description
7	0b RO	Receiver FIFO Error (RFE): This bit is only relevant when FIFO_MODE != NONE AND FIFOs are enabled (FCR[0] set to one). This is used to indicate if there is at least one parity error, framing error, or break indication in the FIFO. '0' - no error in RX FIFO '1' - error in RX FIFO This bit is cleared when the LSR is read and the character with the error is at the top of the receiver FIFO and there are no subsequent errors in the FIFO.
6	1b RO	Transmitter Empty (TEMT): If in FIFO mode (FIFO_MODE != NONE) and FIFOs enabled (FCR[0] set to one), this bit is set whenever the Transmitter Shift Register and the FIFO are both empty. If in non-FIFO mode or FIFOs are disabled, this bit is set whenever the Transmitter Holding Register and the Transmitter Shift Register are both empty.



Bit Range	Default & Access	Description
5	1b RO	Transmit Holding Register Empty (THRE): If THRE_MODE_USER == Disabled or THRE mode is disabled (IER[7] set to zero) and regardless of FIFO's being implemented/enabled or not, this bit indicates that the THR or TX FIFO is empty. This bit is set whenever data is transferred from the THR or TX FIFO to the transmitter shift register and no new data has been written to the THR or TX FIFO. This also causes a THRE Interrupt to occur, if the THRE Interrupt is enabled. If THRE_MODE_USER == Enabled AND FIFO_MODE != NONE and both modes are active (IER[7] set to one and FCR[0] set to one respectively), the functionality is switched to indicate the transmitter FIFO is full, and no longer controls THRE interrupts, which are then controlled by the FCR[5:4] threshold setting.
4	0b RO	Break Interrupt (BI): This is used to indicate the detection of a break sequence on the serial input data. If in UART mode (SIR_MODE == Disabled), it is set whenever the serial input, sin, is held in a logic '0' state for longer than the sum of start time + data bits + parity + stop bits. If in infrared mode (SIR_MODE == Enabled), it is set whenever the serial input, sir_in, is continuously pulsed to logic '0' for longer than the sum of start time + data bits + parity + stop bits. A break condition on serial input causes one and only one character, consisting of all zeros, to be received by the UART. In the FIFO mode, the character associated with the break condition is carried through the FIFO and is revealed when the character is at the top of the FIFO. Reading the LSR clears the BI bit. In the non-FIFO mode, the BI indication occurs immediately and persists until the LSR is read.
3	0b RO	Framing Error (FE): This is used to indicate the occurrence of a framing error in the receiver. A framing error occurs when the receiver does not detect a valid STOP bit in the received data. In the FIFO mode, since the framing error is associated with a character received, it is revealed when the character with the framing error is at the top of the FIFO. When a framing error occurs, the UART tries to resynchronize. It does this by assuming that the error was due to the start bit of the next character and then continues receiving the other bit i.e. data, and/or parity and stop. It should be noted that the Framing Error (FE) bit (LSR[3]) is set if a break interrupt has occurred, as indicated by Break Interrupt (BI) bit (LSR[4]). '0' - no framing error '1' - framing error Reading the LSR clears the FE bit.
2	0b RO	Parity Error (PE): This is used to indicate the occurrence of a parity error in the receiver if the Parity Enable (PEN) bit (LCR[3]) is set. In the FIFO mode, since the parity error is associated with a character received, it is revealed when the character with the parity error arrives at the top of the FIFO. It should be noted that the Parity Error (PE) bit (LSR[2]) is set if a break interrupt has occurred, as indicated by Break Interrupt (BI) bit (LSR[4]). '0' - no parity error '1' - parity error Reading the LSR clears the PE bit.
1	0b RO	Overrun Error (OE): This is used to indicate the occurrence of an overrun error. This occurs if a new data character was received before the previous data was read. In the non-FIFO mode, the OE bit is set when a new character arrives in the receiver before the previous character was read from the RBR. When this happens, the data in the RBR is overwritten. In the FIFO mode, an overrun error occurs when the FIFO is full and a new character arrives at the receiver. The data in the FIFO is retained and the data in the receive shift register is lost. '0' - no overrun error '1' - overrun error Reading the LSR clears the OE bit.
0	0b RO	Data Ready (DR): This is used to indicate that the receiver contains at least one character in the RBR or the receiver FIFO. '0' - no data ready '1' - data ready This bit is cleared when the RBR is read in non-FIFO mode, or when the receiver FIFO is empty, in FIFO mode.

32.6.7 Modem Status Register (COM1_MSR)—Offset 3FEh

The MSR, modem status register contains information about the four incoming modem control lines on the device. The information is split in two nibbles. The four most significant bits contain information about the current state of the inputs where the least significant bits are used to indicate state changes. The four LSB's are reset, each time the register is read. Whenever bits 0, 1, 2 or 3 are set to logic one, to indicate a change on the modem control inputs, a modem status interrupt is generated if enabled through the IER, regardless of when the change occurred. Since the delta



bits (bits 0, 1, 3) can get set after a reset if their respective modem signals are active (see individual bits for details), a read of the MSR after reset can be performed to prevent unwanted interrupts.

Access Method

Type: I/O Register
(Size: 8 bits)

COM1_MSR: 3FEh

Default: 00h

7				4				0
0	0	0	0	0	0	0	0	0
DCD	RI	DSR	CTS	DDCD	TERI	DDSR	DCTS	

Bit Range	Default & Access	Description
7	0b RO	Data Carrier Detect (DCD): This is used to indicate the current state of the modem control line dcd_n. This bit is the complement of dcd_n. When the Data Carrier Detect input (dcd_n) is asserted it is an indication that the carrier has been detected by the modem or data set. '0' - dcd_n input is de-asserted (logic 1) '1' - dcd_n input is asserted (logic 0) In Loopback Mode (MCR[4] set to one), DCD is the same as MCR[3] (Out2). Note that PCU-UART does not implement the Data Carrier Detect (dcd_n) input.
6	0b RO	Ring Indicator (RI): This is used to indicate the current state of the modem control line ri_n. This bit is the complement of ri_n. When the Ring Indicator input (ri_n) is asserted it is an indication that a telephone ringing signal has been received by the modem or data set. '0' - ri_n input is de-asserted (logic 1) '1' - ri_n input is asserted (logic 0) In Loopback Mode (MCR[4] set to one), RI is the same as MCR[2] (Out1). Note that PCU-UART does not implement the Ring Indicator (ri_n) input.
5	0b RO	Data Set Ready (DSR): This is used to indicate the current state of the modem control line dsr_n. This bit is the complement of dsr_n. When the Data Set Ready input (dsr_n) is asserted it is an indication that the modem or data set is ready to establish communications with the DW_apb_uart. '0' - dsr_n input is de-asserted (logic 1) '1' - dsr_n input is asserted (logic 0) In Loopback Mode (MCR[4] set to one), DSR is the same as MCR[0] (DTR). Note that PCU-UART does not implement the Data Set Ready (dsr_n) input.
4	0b RO	Clear to Send (CTS): This is used to indicate the current state of the modem control line cts_n. This bit is the complement of cts_n. When the Clear to Send input (cts_n) is asserted it is an indication that the modem or data set is ready to exchange data with the DW_apb_uart. '0' - cts_n input is de-asserted (logic 1) '1' - cts_n input is asserted (logic 0) In Loopback Mode (MCR[4] = 1), CTS is the same as MCR[1] (RTS). Note that PCU-UART does not implement the Clear to Send (cts_n) input.
3	0b RO	Delta Data Carrier Detect (DDCD): This is used to indicate that the modem control line dcd_n has changed since the last time the MSR was read. '0' - no change on dcd_n since last read of MSR '1' - change on dcd_n since last read of MSR Reading the MSR clears the DDCD bit. In Loopback Mode (MCR[4] = 1), DDCD reflects changes on MCR[3] (Out2). Note, if the DDCD bit is not set and the dcd_n signal is asserted (low) and a reset occurs (software or otherwise), then the DDCD bit is set when the reset is removed if the dcd_n signal remains asserted. Note that PCU-UART does not implement the Data Carrier Detect (dcd_n) input.
2	0b RO	Trailing Edge of Ring Indicator (TERI): This is used to indicate that a change on the input ri_n (from an active-low to an inactive-high state) has occurred since the last time the MSR was read. '0' - no change on ri_n since last read of MSR '1' - change on ri_n since last read of MSR Reading the MSR clears the TERI bit. In Loopback Mode (MCR[4] = 1), TERI reflects when MCR[2] (Out1) has changed state from a high to a low. Note that PCU-UART does not implement the Ring Indicator (ri_n) input.



Bit Range	Default & Access	Description
1	0b RO	Delta Data Set Ready (DDSR): This is used to indicate that the modem control line dsr_n has changed since the last time the MSR was read. '0' - no change on dsr_n since last read of MSR '1' - change on dsr_n since last read of MSR Reading the MSR clears the DDSR bit. In Loopback Mode (MCR[4] = 1), DDSR reflects changes on MCR[0] (DTR). Note, if the DDSR bit is not set and the dsr_n signal is asserted (low) and a reset occurs (software or otherwise), then the DDSR bit is set when the reset is removed if the dsr_n signal remains asserted. Note that PCU-UART does not implement the Data Set Ready (dsr_n) input.
0	0b RO	Delta Clear to Send (DCTS): This is used to indicate that the modem control line cts_n has changed since the last time the MSR was read. '0' - no change on cts_n since last read of MSR '1' - change on cts_n since last read of MSR Reading the MSR clears the DCTS bit. In Loopback Mode (MCR[4] = 1), DCTS reflects changes on MCR[1] (RTS). Note, if the DCTS bit is not set and the cts_n signal is asserted (low) and a reset occurs (software or otherwise), then the DCTS bit is set when the reset is removed if the cts_n signal remains asserted. Note that PCU-UART does not implement the Clear to Send (cts_n) input.

32.6.8 Scratchpad Register (COM1_SCR)—Offset 3FFh

Access Method

Type: I/O Register
(Size: 8 bits)

COM1_SCR: 3FFh

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
SC									

Bit Range	Default & Access	Description
7:0	00h RW	Scratchpad (SC): This register is for programmers to use as a temporary storage space.


33 PCU – System Management Bus (SMBus)

The SoC provides a System Management Bus (SMBus) 2.0 host controller. The host controller provides a mechanism for the processor to initiate communications with SMBus peripherals (slaves). The SoC is also capable of operating in a mode in which it can communicate with I²C compatible devices.

The SoC can perform SMBus messages with packet error checking (PEC) enabled or disabled. The actual PEC calculation and checking can be performed in either hardware or software.

The SMBus Address Resolution Protocol (ARP) is supported by using the existing host controller commands through software, except for the Host Notify command (which is actually a received message).

The programming model of the host controller is combined into two portions: a PCI configuration portion, and a system I/O mapped portion. All static configuration, such as the I/O base address, is done using the PCI configuration space. Real-time programming of the Host interface is done in system I/O space.



33.1 Signal Descriptions

Please see [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function



Table 310. SMBus Signal Names

Signal Name	Direction Plat. Power	Description
PCU_SMB_ALERT#	I/OD V1P8S	SMBus Alert: This signal is used to generate internal SMI#. <i>This signal is muxed and may be used by other functions.</i>
PCU_SMB_CLK	I/OD V1P8S	SMBus Clock: External pull-up resistor is required. <i>This signal is muxed and may be used by other functions.</i>
PCU_SMB_DATA	I/OD V1P8S	SMBus Data: External pull-up resistor is required. <i>This signal is muxed and may be used by other functions.</i>

33.2 Features

33.2.1 Host Controller


The SMBus host controller is used to send commands to other SMBus slave devices. Software sets up the host controller with an address, command, and, for writes, data and optional PEC; and then tells the controller to start. When the controller has finished transmitting data on writes, or receiving data on reads, it generates an SMI# or interrupt, if enabled.

The host controller supports 8 command protocols of the SMBus interface (see *System Management Bus (SMBus) Specification, Version 2.0*): Quick Command, Send Byte, Receive Byte, Write Byte/Word, Read Byte/Word, Process Call, Block Read/Write and Block Write-Block Read Process Call. Additionally, it supports 1 command protocol for I²C devices: I²C Read.

The SMBus host controller requires that the various data and command fields be setup for the type of command to be sent. When software sets the START bit, the SMBus Host controller performs the requested transaction, and interrupts the processor (or generates an SMI#) when the transaction is completed. Once a START command has been issued, the values of the “active registers” (Host Control (SMB_Mem_HCTL), Host Command (SMB_Mem_HCMD), Transmit Slave Address (SMB_Mem_TSA), Data 0 (SMB_Mem_HD0), Data 1 (SMB_Mem_HD1)) should not be changed or read until the interrupt status message (SMB_Mem_HSTS.INTR) has been set (indicating the completion of the command). Any register values needed for computation purposes should be saved prior to issuing of a new command, as the SMBus host controller updates all registers while completing the new command.

33.2.1.1 Command Protocols

In all of the following commands, the Host Status (SMB_Mem_HSTS) register is used to determine the progress of the command. While the command is in operation, the SMB_Mem_HSTS.HBSY bit is set. If the command completes successfully, the SMB_Mem_HSTS.INTR bit will be set. If the device does not respond with an



acknowledge, and the transaction times out, the SMB_Mem_HSTS.DEVERR bit is set. If software sets the SMB_Mem_HCTL.KILL bit while the command is running, the transaction will stop and the SMB_Mem_HSTS.FAILED bit will be set.

Quick Command

When programmed for a Quick Command, the Transmit Slave Address (SMB_Mem_TSA) register is sent. The PEC byte is never appended to the Quick Protocol. Software should force the SMB_Config_HCTL.PECEN bit to 0b when performing the Quick Command. Software must force the SMB_Config_HCFG.I2C_EN bit to 0b when running this command. See section 5.5.1 of the *System Management Bus (SMBus) Specification*, Version 2.0 for the format of the protocol.

Send Byte / Receive Byte

For the Send Byte command, the Transmit Slave Address (SMB_Mem_TSA) and Host Command (SMB_Mem_HCMTD) registers are sent. For the Receive Byte command, the Transmit Slave Address (SMB_Mem_TSA) register is sent. The data received is stored in the Data 0 (SMB_Mem_HD0) register. Software must force the SMB_Config_HCFG.I2C_EN bit to 0b when running this command.

The Receive Byte is similar to a Send Byte, the only difference is the direction of data transfer. See sections 5.5.2 and 5.5.3 of the *System Management Bus (SMBus) Specification*, Version 2.0 for the format of the protocol.

Write Byte/Word

The first byte of a Write Byte/Word access is the command code. The next 1 or 2 bytes are the data to be written. When programmed for a Write Byte/Word command, the Transmit Slave Address (SMB_Mem_TSA), Host Command (SMB_Mem_HCMTD), and Data 0 (SMB_Mem_HD0) registers are sent. In addition, the Data 1 (SMB_Mem_HD1) register is sent on a Write Word command. Software must force the SMB_Config_HCFG.I2C_EN bit to 0 when running this command. See section 5.5.4 of the *System Management Bus (SMBus) Specification*, Version 2.0 for the format of the protocol.

Read Byte/Word

Reading data is slightly more complicated than writing data. First the SoC must write a command to the slave device. Then it must follow that command with a repeated start condition to denote a read from that device's address. The slave then returns 1 or 2 bytes of data. Software must force the SMB_Config_HCFG.I2C_EN bit to 0b when running this command.

When programmed for the read byte/word command, the Transmit Slave Address (SMB_Mem_TSA) and Host Command (SMB_Mem_HCMTD) registers are sent. Data is received into the Data 0 (SMB_Mem_HD0) on the read byte, and the Data 0



(SMB_Mem_HD0) and Data 1 (SMB_Mem_HD1) registers on the read word. See section 5.5.5 of the *System Management Bus (SMBus) Specification*, Version 2.0 for the format of the protocol.

Process Call

The process call is so named because a command sends data and waits for the slave to return a value dependent on that data. The protocol is simply a Write Word followed by a Read Word, but without a second command or stop condition.

When programmed for the Process Call command, the SoC transmits the Transmit Slave Address (SMB_Mem_TSA), Host Command (SMB_Mem_HCMD), Data 0 (SMB_Mem_HD0) and Data 1 (SMB_Mem_HD1) registers. Data received from the device is stored in the Data 0 (SMB_Mem_HD0) and Data 1 (SMB_Mem_HD1) registers. The Process Call command with SMB_Config_HCFG.I2C_EN set and the SMB_Config_HCTL.PECEN bit set produces undefined results. Software must force either SMB_Config_HCFG.I2C_EN or SMB_Config_HCTL.PECEN & SMB_Mem_AUXC.AAC to 0b when running this command. See section 5.5.6 of the *System Management Bus (SMBus) Specification*, Version 2.0 for the format of the protocol.

Note: For process call command, the value written into SMB_Mem_TSA.RW needs to be 0b.

Note: If the SMB_Config_HCFG.I2C_EN bit is set, the protocol sequence changes slightly: the Command Code (Bits 18:11 in the bit sequence) are not sent - as a result, the slave will not acknowledge (Bit 19 in the sequence).

Block Read/Write


The SoC contains a 32-byte buffer for read and write data which can be enabled by setting SMB_Mem_AUXC.E32B, as opposed to a single byte of buffering. This 32-byte buffer is filled with write data before transmission, and filled with read data on reception. In the SoC, the interrupt is generated only after a transmission or reception of 32 bytes, or when the entire byte count has been transmitted/received.

Note: When operating in I²C mode (SMB_Config_HCFG.I2C_EN bit is set), the SoC will never use the 32-byte buffer for any block commands.

The byte count field is transmitted but ignored by the SoC as software will end the transfer after all bytes it cares about have been sent or received.

For a Block Write, software must either force the SMB_Config_HCFG.I2C_EN bit or both the SMB_Config_HCTL.PECEN and SMB_Mem_AUXC.AAC bits to 0b when running this command.

The block write begins with a slave address and a write condition. After the command code the SoC issues a byte count describing how many more bytes will follow in the message. If a slave had 20 bytes to send, the first byte would be the number 20 (14h), followed by 20 bytes of data. The byte count may not be 0. A Block Read or Write is allowed to transfer a maximum of 32 data bytes.



When programmed for a block write command, the Transmit Slave Address (SMB_Mem_TSA), Host Command (SMB_Mem_HCMD) and Data 0 (SMB_Mem_HD0) registers are sent. Data is then sent from the Host Block Data (SMB_Mem_HBD) register; the total data sent being the value stored in the Data 0 (SMB_Mem_HD0) register. On block read commands, the first byte received is stored in the Data 0 (SMB_Mem_HD0) register, and the remaining bytes are stored in the Host Block Data (SMB_Mem_HBD) register. See section 5.5.7 of the *System Management Bus (SMBus) Specification*, Version 2.0 for the format of the protocol.

Note: For Block Write, if the SMB_Config_HCFG.I2C_EN bit is set, the format of the command changes slightly. The SoC will still send the number of bytes (on writes) or receive the number of bytes (on reads) indicated in the Data 0 (SMB_Mem_HD0) register. However, it will not send the contents of the Data 0 (SMB_Mem_HD0) register as part of the message. Also, the Block Write protocol sequence changes slightly: the Byte Count (bits 27:20 in the bit sequence) are not sent - as a result, the slave will not acknowledge (bit 28 in the sequence).

Block Write–Block Read Process Call

The block write-block read process call is a two-part message. The call begins with a slave address and a write condition. After the command code the host issues a write byte count (M) that describes how many more bytes will be written in the first part of the message. If a master has 6 bytes to send, the byte count field will have the value 6 (0000 0110b), followed by the 6 bytes of data. The write byte count (M) cannot be 0.

The second part of the message is a block of read data beginning with a repeated start condition followed by the slave address and a Read bit. The next byte is the read byte count (N), which may differ from the write byte count (M). The read byte count (N) cannot be 0.

The combined data payload must not exceed 32 bytes. The byte length restrictions of this process call are summarized as follows:

- $M \geq 1$ byte
- $N \geq 1$ byte
- $M + N \leq 32$ bytes

The read byte count does not include the PEC byte. The PEC is computed on the total message beginning with the first slave address and using the normal PEC computational rules. It is highly recommended that a PEC byte be used with the Block Write-Block Read Process Call. Software must do a read to the Host Command (SMB_Mem_HCMD) register to reset the 32 byte buffer pointer prior to reading the Host Block Data (SMB_Mem_HBD) register.

Note that there is no STOP condition before the repeated START condition, and that a NACK signifies the end of the read transfer.

Note: The SMB_Mem_AUXC.E32B bit in the Auxiliary Control register must be set when using this protocol.



See section 5.5.8 of the *System Management Bus (SMBus) Specification, Version 2.0* for the format of the protocol.

I²C Read

This command allows the SoC to perform block reads to certain I²C devices, such as serial EEPROMs. The SMBus Block Read supports the 7-bit addressing mode only.

However, this does not allow access to devices using the I²C “Combined Format” that has data bytes after the address. Typically these data bytes correspond to an offset (address) within the serial memory chips.


Note: This command is supported independent of the setting of the SMB_Config_HCFG.I2C_EN bit. The I²C Read command with the SMB_Config_HCTL.PECEN bit set produces undefined results. Software must force both the SMB_Config_HCTL.PECEN and SMB_Mem_AUXC.AAC bit to 0b when running this command.

For I²C Read command, the value written into SMB_Mem_TSA.RW needs to be 1b. The format that is used for the command is shown in below table.

Table 311. I²C Block Read

Bit	Description
1	Start
8:2	Slave Address – 7 bits
9	Write
10	Acknowledge from slave
18:11	Send Data 1 (SMB_Mem_HD1) register
19	Acknowledge from slave
20	Repeated Start
27:21	Slave Address – 7 bits
28	Read
29	Acknowledge from slave
37:30	Data byte 1 from slave – 8 bits
38	Acknowledge
46:39	Data byte 2 from slave – 8 bits
47	Acknowledge
–	Data bytes from slave / Acknowledge
–	Data byte N from slave – 8 bits
–	NOT Acknowledge
–	Stop

The SoC will continue reading data from the peripheral until the NAK is received.



33.2.2 Bus Arbitration

Several masters may attempt to get on the bus at the same time by driving the PCU_SMB_DATA line low to signal a start condition. The SoC continuously monitors the PCU_SMB_DATA line. When the SoC is attempting to drive the bus to a 1 by letting go of the PCU_SMB_DATA line, and it samples PCU_SMB_DATA low, then some other master is driving the bus and the SoC will stop transferring data.

If the SoC sees that it has lost arbitration, the condition is called a collision. The SoC will set SMB_Mem_HSTS.BERR, and if enabled, generate an interrupt or SMI#. The processor is responsible for restarting the transaction.

The SoC, as a SMBus master, drives the clock. When the SoC is sending address or command or data bytes on writes, it drives data relative to the clock it is also driving. It will not start toggling the clock until the start or stop condition meets proper setup and hold time. The SoC will also ensure minimum time between SMBus transactions as a master.

33.2.3 Bus Timing

33.2.3.1 Clock Stretching

Some devices may not be able to handle their clock toggling at the rate that the SoC as an SMBus master would like. They have the capability of stretching the low time of the clock. When the SoC attempts to release the clock (allowing the clock to go high), the clock will remain low for an extended period of time.

The SoC monitors the SMBus clock line after it releases the bus to determine whether to enable the counter for the high time of the clock. While the bus is still low, the high time counter must not be enabled. Similarly, the low period of the clock can be stretched by an SMBus master if it is not ready to send or receive data.

33.2.3.2 Bus Time Out (SoC as SMBus Master)

If there is an error in the transaction, such that an SMBus device does not signal an acknowledge, or holds the clock lower than the allowed time-out time, the transaction will time out. The SoC will discard the cycle and set the SMB_Mem_HSTS.DEVERR bit. The time out minimum is 25 ms (800 RTC clocks). The time-out counter inside the SoC will start after the last bit of data is transferred by the SoC and it is waiting for a response.

The 25-ms time-out counter will not count under the following conditions:

1. The SMB_Mem_HSTS.BYTE_DONE_STS bit is set
2. The TCO_STS.SECOND_TO_STS bit is not set (this indicates that the system has not locked up).



33.2.4 Interrupts / SMI#

The SoC SMBus controller uses INTB as its virtual interrupt wire. However, the system can alternatively be set up to generate SMI# instead of an interrupt, by setting the SMB_Config_HCFG.SMI_EN bit.

Below tables specify how the various enable bits in the SMBus function control the generation of the interrupt and Host SMI internal signals. The rows in the tables are additive, which means that if more than one row is true for a particular scenario then the Results for all of the activated rows will occur.

Table 312. Enable for PCU_SMB_ALERT#

Event	SMB_Mem_HCTL.INTREN	SMB_Config_HCFG.SMI_EN	SMB_Mem_SCMD.SMBALTDIS	Result
PCU_SMB_ALERT# asserted low (always reported in SMB_Mem_HSTS.SMBALERT)	X	1	0	Slave SMI# generated (SMBUS_SMI_STS)
	1	0	0	Interrupt generated

Table 313. Enables for SMBus Host Events


Event	SMB_Mem_HCTL.INTREN	SMB_Config_HCFG.SMI_EN	Event
Any combination of SMB_Mem_HSTS.FAILED, SMB_Mem_HSTS.BERR, SMB_Mem_HSTS.DEVERR, SMB_Mem_HSTS.INTR asserted	0	X	None
	1	0	Interrupt generated
	1	1	Host SMI# generated

Table 314. Enables for the Host Notify Command

SMB_Mem_SCMD.HNINTREN	SMB_Config_HCFG.SMI_EN	SMB_Mem_SCMD.HNWAKEEN	Result
0	X	0	None
1	0	X	Interrupt generated
1	1	X	Slave SMI# generated (SMBUS_SMI_STS)

33.2.5 PCU_SMB_ALERT#

PCU_SMB_ALERT# is multiplexed with GPIO_S0_SC[53]. When enabled and the signal is asserted, the SoC can generate an interrupt or an SMI#.



Note: Using this signal as a wake event from is not supported.

33.2.6 SMBus CRC Generation and Checking

If the SMB_Mem_AUXC.AAC is set, the SoC automatically calculates and drives CRC at the end of the transmitted packet for write cycles, and will check the CRC for read cycles. It will not transmit the contents of the Packet Error Check Data Register (SMB_Mem_PEC) PEC register for CRC. The SMB_Mem_HCTL.PECEN bit must not be set if this bit is set, or unspecified behavior will result.

If the read cycle results in a CRC error, the SMB_Mem_HSTS.DEVERR bit and the SMB_Mem_AUXS.CRCE bit will be set.

33.2.7 SMBus Slave Interface

The SoC does not implement a complete SMBus slave interface. Only the Host Notify Command is implemented to maintain specification compatibility.

33.2.7.1 Format of Host Notify Command

The SoC tracks and responds to the standard Host Notify command as specified in the System Management Bus (SMBus) Specification, Version 2.0. The host address for this command is fixed to 0001000b. If the SoC already has data for a previously-received host notify command which has not been serviced yet by the host software (as indicated by the SMB_Mem_SSTS.HNST bit), then it will NACK following the host address byte of the protocol. This allows the host to communicate non-acceptance to the master and retain the host notify address and data values for the previous cycle until host software completely services the interrupt.

Note: Host software must always clear the SMB_Mem_SSTS.HNST bit after completing any necessary reads of the address and data registers.

Below table shows the Host Notify format.

Table 315. Host Notify Format (Sheet 1 of 2)

Bit	Description	Driven By	Comment
1	Start	External Master	
8:2	SMB Host Address – 7 bits	External Master	Always 0001_000
9	Write	External Master	Always 0
10	ACK (or NACK)	SoC	SoC NACKs if SMB_Mem_SSTS.HNST is 1
17:11	Device Address – 7 bits	External Master	Indicates the address of the master; loaded into the Notify Device Address Register (SMB_Mem_NDA)
18	Unused – Always 0	External Master	7-bit-only address; this bit is inserted to complete the byte
19	ACK	SoC	



Table 315. Host Notify Format (Sheet 2 of 2)

Bit	Description	Driven By	Comment
27:20	Data Byte Low – 8 bits	External Master	Loaded into the Notify Data Low Byte Register (SMB_Mem_NDLB)
28	ACK	SoC	
36:29	Data Byte High – 8 bits	External Master	Loaded into the Notify Data High Byte Register (SMB_Mem_NDHB)
37	ACK	SoC	
38	Stop	External Master	

33.3 Use

33.3.1 Function Disable

The SMBus interface may be disabled by setting FUNC_DIS_2.SMB_DIS to 1b.

33.3.2 SPD Write Disable

DRAM memory modules contain a 256-byte EEPROM, called SPD, accessible via SMBus used to store configuration information such as timing, physical size and more. A malicious user with administrative privileges can change and permanently lock invalid settings which could then lead to a permanent denial of service attack or a memory aliasing attack.

Write access to the SPI should be disabled by setting SMB_Config_HCFG.SPD_WD to 1b.

33.4 References

- System Management Bus (SMBus) Specification Version 2.0: <http://www.smbus.org/specs/>

33.5 Register Map

Refer to Chapter 3, “Register Access Methods” and Chapter 4, “Mapping Address Spaces” for additional information.





Figure 134.PCU - SMBus Register Map





Bit Range	Default & Access	Description
7	0b RO	Wait Cycle Ctrl (WCC): Wait cycle control - reserved as '0'
6	0b RO	Parity error response (PER): Parity error - reserved as '0'
5	0b RO	VGA palette snoop (VGAPS): VGA palette snoop - reserved as '0'
4	0b RO	PMWE: Postable Memory Write Enable - reserved as '0'
3	0b RO	SCE: Special Cycle Enable - reserved as '0'
2	0b RO	BME: Bus Master Enable - reserved as '0'
1	0b RW	MSE: Memory space enable - 1 enables access to the SM Bus memory space registers as defined by the Base Address Registers
0	0b RW	IOSE: I/O space enable - 1 enables access to the SM Bus I/O space registers as defined by the Base Address Register

33.6.4 D31_F3_Device_Status (SMB_Config_STAT)—Offset 6h

Configuration status register

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

SMB_Config_STAT: [B:0, D:31, F:3] + 6h

Default: 0290h

15	12	8	4	0
0	0	0	0	0
0	0	1	0	0
DPE	SSE	RMA	RTA	STA
		DEVT	DPED	FB2B
			UDF	FREQ66
			CLI	INTS
				RSV

Bit Range	Default & Access	Description
15	0b RO	DPE: Detect Parity Error - reserved as '0'
14	0b RO	SSE: Signaled System Error - reserved as '0'
13	0b RO	RMA: Received Master Abort - reserved as '0'
12	0b RO	RTA: Received Target Abort - reserved as '0'
11	0b RO	STA: Signaled Target Abort - reserved as '0'
10:9	01b RO	DEVT: Devsel Timing Status reserved as 2'b01
8	0b RO	DPED: Data Parity Error Detected - reserved as '0'



Bit Range	Default & Access	Description
7	1b RO	Fast Back To Back (FB2B): Fast Back To Back Capable - reserved as '1'
6	0b RO	UDF: User Defined Features - reserved as '0'
5	0b RO	66 MHz Capable (FREQ66): 66 MHz Capable - reserved as '0'
4	1b RO	Capabilities List Indicator (CLI): Capabilities List Indicator - set to '1'
3	0b RO	INTS: This bit indicates that an interrupt is pending. It is independent from the state of the Interrupt Enable bit in the command register
2:0	000b RO	Reserved (RSV): Reserved

33.6.5 D31_F3_Revision ID (SMB_Config_REV)—Offset 8h

The value reported in this register is coming from centralize unit by the SETIDVALUE message

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_Config_REV: [B:0, D:31, F:3] + 8h

Default: 00h

7	4	0
0	0	0
REVID		

Bit Range	Default & Access	Description
7:0	00h RO	Revision ID (REVID): Revision ID

33.6.6 D31_F3_Programming Interface (SMB_Config_PRGIF)—Offset 9h

The value reported in this register is coming from centralize unit by the SETIDVALUE message

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_Config_PRGIF: [B:0, D:31, F:3] + 9h

Default: 00h

7	4	0
0	0	0
PRGIF		



Bit Range	Default & Access	Description
7:0	00h RO	Programming Interface (PRGIF): Programming Interface

33.6.7 D31_F3_Sub Class Code (SMB_config_SCC)—Offset Ah

A value of 05h indicates that this device is a SM Bus serial controller

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_config_SCC: [B:0, D:31, F:3] + Ah

Default: 05h

7			4				0
0	0	0	0	0	0	1	0
				SCC			

Bit Range	Default & Access	Description
7:0	05h RO	SCC: Sub Class Code

33.6.8 D31_F3_Base Class Code (SMB_Config_BCC)—Offset Bh

A value of 0Ch indicates that this device is a serial controller

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_Config_BCC: [B:0, D:31, F:3] + Bh

Default: 0Ch

7			4				0
0	0	0	0	0	1	1	0
				BCC			

Bit Range	Default & Access	Description
7:0	0Ch RO	BCC: Base Class Code

33.6.9 D31_F3_SMBus Memory Base Address (SMB_Config_MBARL)—Offset 10h

The memory bar

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SMB_Config_MBARL: [B:0, D:31, F:3] + 10h

Default: 00000000h



Bit Range	Default & Access	Description
31:0	00000000h RO	BAR: RESERVED

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	1	
RSV1				BAR				RSV2	TOST



Bit Range	Default & Access	Description
15:0	0000h RW/O	SID: Subsystem ID

33.6.14 D31_F3_CAP_POINTER (SMB_Config_CAP_POINTER)—Offset 34h

This optional register is used to point to a linked list of new capabilities implemented by this device. This register is only valid if the Capabilities List bit in the Status Register is set. If implemented, the bottom two bits are reserved and should be set to 00b. Software should mask these bits off before using this register as a pointer in Configuration Space to the first entry of a linked list of new capabilities.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_Config_CAP_POINTER: [B:0, D:31, F:3] + 34h

Default: 50h

7			4				0
0	1	0	1	0	0	0	0
CAP							

Bit Range	Default & Access	Description
7:0	50h RO	Capability Pointer (CP): Indicates the offset of the first Capability Item.

33.6.15 D31_F3_Interrupt Line (SMB_Config_INTLN)—Offset 3Ch

This data is not used

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_Config_INTLN: [B:0, D:31, F:3] + 3Ch

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
INTLN							

Bit Range	Default & Access	Description
7:0	00h RW	INTLN: Interrupt Line



33.6.16 D31_F3_Interrupt Pin (SMB_Config_INTPN)—Offset 3Dh

This register reflects the D31IP.SMIP in chipset configuration space

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_Config_INTPN: [B:0, D:31, F:3] + 3Dh

Default: 02h

7	4	0
0	0	0
INTPN		

Bit Range	Default & Access	Description
7:0	02h RO	INTPN: The 4 msb bits are hardwired to 0, and the 4 lsb bits are hardwired to 4'h2 indicates the INTB is used by the SMBus controller

33.6.17 D31_F3_Host Configuration (SMB_Config_HCFG)—Offset 40h

Host Configuration Register

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_Config_HCFG: [B:0, D:31, F:3] + 40h

Default: 00h

7	4	0
0	0	0
RSV1	SPD_WD	SSRST
		I2C_EN
		SMT_EN
		HST_EN

Bit Range	Default & Access	Description
7:5	000b RO	Reserved (RSV1): Reserved
4	0b RW/O	SPD write disable (SPD_WD): This bit is must be set to 1b1 to disable writes to SPD which are on Host SMB address ranges 0xA0 0xAE. The SMBus range is unwriteable until next platform reset HW Default is 1b0. Note: This bit is locked on 1b1 and will be reset on PLTRST# reset. This should be set by BIOS memory reference code to 1b1. SW can only program this bit when both HCTL[6] = 1b0 (START) and HSTS[0] = 1b0 (HBSY), else it may result in an undefined behavior.
3	0b RW	SSRST: Soft SMBus Reset - When this bit is 1, the SMBus state machine and logic is reset. The HW will reset this bit to 0 when reset operation is completed
2	0b RW	I2C_EN: When this bit is 1, the SMBus host is enabled to communicate with I2C devices. This will change the formatting of some commands. When this bit is 0, behavior is for SMBus
1	0b RW	SMT_EN: When this bit is set, any source of an SMB interrupt will instead be routed to generate an SMI



Bit Range	Default & Access	Description
0	0b RW	HST_EN: When set, the SMB Host Controller interface is enabled to execute commands. The SMB_Mem_HCTL.INTREN bit needs to be enabled in order for the SMB Host Controller to interrupt or SMI#. Additionally, the SMB Host Controller will not respond to any new requests until all interrupt requests have been cleared

33.6.18 D31_F3_PID (SMB_Config_CAP_ID)—Offset 50h

Power Management Capability ID

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

SMB_Config_CAP_ID: [B:0, D:31, F:3] + 50h

Default: 0001h

15	12	8	4	0
0	0	0	0	1
Next_Item_Ptr				Cap_ID

Bit Range	Default & Access	Description
15:8	00h RO	Next Item Pointer (Next_Item_Ptr): This field provides an offset into the functions PCI Configuration Space pointing to the location of next item in the functions capability list. If there are no additional items in the Capabilities List, this register is set to 00h.
7:0	01h RO	Capability Identifier (Cap_ID): This field, when 01h identifies the linked list item as being the PCI Power Management registers.

33.6.19 D31_F3_PC (SMB_Config_PMC)—Offset 52h

Power Management Capabilities

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

SMB_Config_PMC: [B:0, D:31, F:3] + 52h

Default: 0003h

15	12	8	4	0
0	0	0	0	1
PMES		D2S	D1S	AC
			DSI	RSV1
				PMEC
				VS

Bit Range	Default & Access	Description
15:11	00000b RO	PME_Support (PMES): This 5-bit field indicates the power states in which the function may assert PME#. A value of 0b for any bit indicates that the function is not capable of asserting the PME# signal while in that power state. bit(11) X XXX1b - PME# can be asserted from D0 bit(12) X XX1Xb - PME# can be asserted from D1 bit(13) X X1XXb - PME# can be asserted from D2 bit(14) X 1XXXb - PME# can be asserted from D3hot bit(15) 1 XXXXb - PME# can be asserted from D3cold



Bit Range	Default & Access	Description
10	0b RO	D2_Support (D2S): If this bit is a '1', this function supports the D2 Power Management State. Functions that do not support D2 must always return a value of '0' for this bit.
9	0b RO	D1_Support (D1S): If this bit is a '1', this function supports the D1 Power Management State. Functions that do not support D2 must always return a value of '0' for this bit.
8:6	000b RO	Aux_Current (AC): Auxiliary current - should be 3'b000
5	0b RO	DSI: Device specific initialization
4	0b RO	Reserved (RSV1): Reserved
3	0b RO	PME Clock (PMEC): PME Clock. Does not apply.
2:0	011b RO	Version (VS): A value of 011b indicates that this function complies with revision 1.2 of the PCI Power Management Interface Specification.

33.6.20 D31_F3_PMCSR (SMB_Config_PMCSR)—Offset 54h

Power Management Control/Status Register

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

SMB_Config_PMCSR: [B:0, D:31, F:3] + 54h

Default: 0008h

15	12	8	4	0
0	0	0	0	0
PMES	DATA_SCALE	DATA_SEL	PMEE	RSV1
				DSI
				RSV2
				PS

Bit Range	Default & Access	Description
15	0b RO	PME_Status (PMES): SMBus does not initiate PME#. Hence this bit should be always '0'
14:13	00b RO	Data_Scale (DATA_SCALE): If the Data register has not been implemented, this field must return '00b' when the PMCSR is read.
12:9	0000b RO	Data_Select (DATA_SEL): If the Data register is not implemented, this field should be read only and return '0000b' when the PMCSR is read.
8	0b RO	PME_En (PMEE): Should be '0' since SMBus does not initiate PME#
7:4	0000b RO	Reserved (RSV1): Reserved



Bit Range	Default & Access	Description
3	1b RO	No_Soft_Reset (DSI): When set (1), this bit indicates that devices transitioning from D3hot to D0 because of PowerState commands do not perform an internal reset. Configuration Context is preserved. Upon transition from the D3hot to the D0 Initialized state, no additional operating system intervention is required to preserve Configuration Context beyond writing the PowerState bits.
2	0b RO	Reserved (RSV2): Reserved
1:0	00b RW	PowerState (PS): This 2-bit field is used both to determine the current power state of a function and to set the function into a new power state. The definition of the field values is given below. 00b - D0 01b - D1 10b - D2 11b - D3hot If software attempts to write an unsupported, optional state to this field, the write operation must complete normally on the bus; however, the data is discarded and no state change occurs.

33.6.21 D31_F3_PMCSR_BSE (SMB_Config_PMCSR_BSE)—Offset 56h

PMCSR_BSE supports PCI bridge specific functionality and is required for all PCI-to-PCI bridges.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_Config_PMCSR_BSE: [B:0, D:31, F:3] + 56h

Default: 00h

7		4	0
0	0	0	0
BPCCE	B23	RSV1	

Bit Range	Default & Access	Description
7	0b RO	BPCC_En (BPCCE): Bus Power/Clock Control Enable - Does not apply
6	0b RO	B2_B3 (B23): B2/B3 support for D3hot - Does not apply
5:0	00h RO	Reserved (RSV1): Reserved



33.6.22 D31_F3_DATA (SMB_Config_DATA)—Offset 57h

PMCSR_BSE supports PCI bridge specific functionality and is required for all PCI-to-PCI bridges.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

SMB_Config_DATA: [B:0, D:31, F:3] + 57h

Default: 00h

7	4	0
0	0	0
DT		

Bit Range	Default & Access	Description
7:0	00h RO	Data (DT): Data - Does not apply

33.6.23 IOSF Error Control (SMB_Config_ERR)—Offset F0h

IOSF Error Control- is set when an Unsupported Request Detected

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SMB_Config_ERR: [B:0, D:31, F:3] + F0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSV1								URD

Bit Range	Default & Access	Description
31:1	0000h RO	Reserved (RSV1): Reserved
0	0b RW	URD: Unsupported Request Detected, SMBus could not receive unsupported request hence this bit is tied to 1b0



33.6.24 D31_F3_Manufacturer's ID (SMB_Config_MANID)—Offset F8h

Manufacturer's ID Register, The value reported in this register is coming from centralize unit by the SETIDVALUE message

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SMB_Config_MANID: [B:0, D:31, F:3] + F8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSV1	DOTID	SID	MID	PPID				

Bit Range	Default & Access	Description
31:28	00h RO	Reserved (RSV1): Reserved
27:24	0000b RO	DOTID: The value reported in this field is coming from centralize unit by the SETIDVALUE message
23:16	00h RO	SID: The value reported in this field is coming from centralize unit by the SETIDVALUE message
15:8	00h RO	MID: The value reported in this field is coming from centralize unit by the SETIDVALUE message
7:0	00h RO	PPID: The value reported in this field is coming from centralize unit by the SETIDVALUE message



33.7 PCU SMBUS Memory Mapped I/O Registers

Table 317. Summary of PCU SMBUS Memory Mapped I/O Registers—SMB_Config_MBARL

Offset	Size	Register ID—Description	Default Value
0h	1	"Host Status Register (SMB_Mem_HSTS)—Offset 0h" on page 4466	00h
2h	1	"Host Control Register (SMB_Mem_HCTL)—Offset 2h" on page 4467	00h
3h	1	"Host Command Register (SMB_Mem_HCMD)—Offset 3h" on page 4470	00h
4h	1	"Transmit Slave Address Register (SMB_Mem_TSA)—Offset 4h" on page 4470	00h
5h	1	"Data 0 Register (SMB_Mem_HD0)—Offset 5h" on page 4471	00h
6h	1	"Data 1 Register (SMB_Mem_HD1)—Offset 6h" on page 4471	00h
7h	1	"Host Block Data (SMB_Mem_HBD)—Offset 7h" on page 4471	00h
8h	1	"Packet Error Check Data Register (SMB_Mem_PEC)—Offset 8h" on page 4472	00h
Ch	1	"Auxiliary Status (SMB_Mem_AUXS)—Offset Ch" on page 4473	00h
Dh	1	"Auxiliary Control (SMB_Mem_AUXC)—Offset Dh" on page 4473	00h
Fh	1	"SMBUS_PIN_CTL Register (SMB_Mem_SMBC)—Offset Fh" on page 4474	07h
10h	1	"Slave Status Register (SMB_Mem_SSTS)—Offset 10h" on page 4474	00h
11h	1	"Slave Command Register (SMB_Mem_SCMD)—Offset 11h" on page 4475	00h
14h	1	"Notify Device Address Register (SMB_Mem_NDA)—Offset 14h" on page 4476	00h
16h	1	"Notify Data Low Byte Register (SMB_Mem_NDLB)—Offset 16h" on page 4476	00h
17h	1	"Notify Data High Byte Register (SMB_Mem_NDHB)—Offset 17h" on page 4477	00h

33.7.1 Host Status Register (SMB_Mem_HSTS)—Offset 0h

All status bits are set by hardware and cleared by the software writing a one to the particular bit position. Writing a zero to any bit position has no affect

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_HSTS: [MBARL] + 0h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
BDS	IUS	SMB_ALERTB	FAILED	BERR	DEVERR	INTR	HBSY



Bit Range	Default & Access	Description
7	0b RW	BDS: BYTE_DONE_STS (BDS) - This bit will be set to 1 when the host controller has received a byte (for Block Read commands) or if it has completed transmission of a byte (for Block Write commands) when the 32-byte buffer is not being used. Note that this bit will be set, even on the last byte of the transfer. Software clears the bit by writing a 1 to the bit position. This bit has no meaning for block transfers when the 32-byte buffer is enabled. Note: When the last byte of a block message is received, the host controller will set this bit. However, it will not immediately set the INTR bit (bit 1 in this register). When the interrupt handler clears the BYTE_DONE_STS bit, the message is considered complete, and the host controller will then set the INTR bit (and generate another interrupt). Thus, for a block message of n bytes, the SMBus host will generate n+1 interrupts. The interrupt handler needs to be implemented to handle these cases.
6	0b RW	IUS: In Use Status (IUS) - After a full PCI reset, a read to this bit returns a 0. After the first read, subsequent reads will return a 1. A write of a 1 to this bit will reset the next read value to 0. Writing a 0 to this bit has no effect. Software can poll this bit until it reads a 0, and will then own the usage of the host controller. This bit has no other effect on the hardware, and is only used as semaphore among various independent software threads that may need to use the SMBus host
5	0b RW	SMB_ALERTB: the SOC sets this bit to a '1' to indicates source of the interrupt or SMI# was the SMB_ALERTB signal. Software resets this bit by writing a 1 to this location.
4	0b RW	FAILED: Failed (FAIL) - When set, this indicates that the source of the interrupt or SMI was a failed bus transaction. This is set in response to the KILL bit being set to terminate the host transaction.
3	0b RW	BERR: Bus Error (BERR) - When set, this indicates the source of the interrupt or SMI was a transaction collision.
2	0b RW	DEVERR: Device Error (DERR) - When set, this indicates that the source of the interrupt or SMI was due one of the following: Illegal Command Field Unclaimed Cycle (host initiated) Host Device Time-out Error. CRC Error Write Protection Access Error (START bit will be cleared, Device Error will be set and Host Busy is never set because SMB Transaction never took place).
1	0b RW	INTR: Interrupt (INTR) - When set, this indicates that the source of the interrupt or SMI was the successful completion of its last command.
0	0b RW	HBSY: Host Busy (HBSY) - A '1' indicates that the SMBus host is running a command from the host interface. No SMB registers should be accessed while this bit is set. Exception: The BLOCK DATA REGISTER can be accessed when this bit is set ONLY when the SMB_CMD bits (in Host control register) are programmed for Block command or I2C Read command. This is necessary in order to check the DONE_STS bit.

33.7.2 Host Control Register (SMB_Mem_HCTL)—Offset 2h

Host Control Register

Note: A read to this register will clear the pointer in the 32-byte buffer.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_HCTL: [MBARL] + 2h

MBARL Type: PCI Configuration Register (Size: 32 bits)


MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h



7			4			0
0	0	0	0	0	0	0
PECEN	SATRT	LBYTE	SMBCMD		KILL	INTREN

Bit Range	Default & Access	Description
7	0b RW	PECEN: PEC_EN: When set to '1', this bit causes the host controller to perform the SMBus transaction with the Packet Error Checking phase appended. For writes, the value of the PEC byte is transferred from the PEC Register. For reads, the PEC byte is loaded in to the PEC Register. When this bit is cleared to '0', the SMBus host controller does not perform the transaction with the PEC phase appended. This bit must be written prior to the write in which the START bit is set.
6	0b WO	START (SATRT): START: This write-only bit is used to initiate the command described in the SMB_CMD field. All registers should be setup prior to writing a '1' to this bit position. This bit always reads zero. The HOST_BUSY bit in the Host Status register (offset 00h) can be used to identify when the SMBus controller has finished the command.
5	0b RW	LBYTE: LAST_BYTE: Used for I2C Read commands as an indication that the next byte will be the last one to be received for that block. The algorithm and usage model for this bit will be as follows (assume a message of n bytes): A. When the software sees the BYTE_DONE_STS bit set (bit 7 in the SMBus Host Status Register) for each of bytes 1 through n-2 of the message, the software should then read the Block Data Byte Register to get the byte that was just received. B. After reading each of bytes 1 to n-2 of the message, the software will then clear the BYTE_DONE_STS bit. C. After receiving byte n-1 of the message, the software will then set the 'LAST BYTE' bit. The software will then clear the BYTE_DONE_STS bit. D. The Intel SOC will then receive the last byte of the message (byte n). However, the Intel SOC state machine will see the LAST_BYTE bit set, and instead of sending an ACK after receiving the last byte, it will instead send a NAK. E. After receiving the last byte (byte n), the software will still clear the BYTE_DONE_STS bit. However, the LAST_BYTE bit will be irrelevant at that point. Note: This bit may be set when the TCO timer causes the SECOND_TO_STS bit to be set. See the TCO_STS.SECOND_TO_STS register, for more details on that bit. The SMBus device driver should clear the LAST_BYTE bit (if it is set) before starting any new command. Note: In addition to I2C Read Commands, the LAST_BYTE bit will also cause Block Read/Write cycles to stop prematurely (at the end of the next byte).



Bit Range	Default & Access	Description
4:2	000b RW	SMBCMD: SMB_CMD - As shown by the bit encoding below, indicates which command the SMBus host is to perform. If enabled, the SMBus host will generate an interrupt or SMI when the command has completed. If the value is for a non-supported or reserved command, the SMBus host will set the device error (DEV_ERR) status bit and generate an interrupt when the START bit is set. The SMBus controller will perform no command, and will not operate until DEV_ERR is cleared. 3'b000 - Quick The slave address and read/write value (bit 0) are stored in the tx slave address register 3'b001 - Byte This command uses the transmit slave address and command registers. Bit 0 of the slave address register determines if this is a read or write command. If it is a read, after the command completes the DATA0 register will contain the read data. 3'b010 - Byte Data This command uses the transmit slave address, command, and DATA0 registers. Bit 0 of the slave address register determines if this is a read or write command. If it is a read, the DATA0 register will contain the read data 3'b011 - Word Data This command uses the transmit slave address, command, DATA0 and DATA1 registers. Bit 0 of the slave address register determines if this is a read or write command. If it is a read, after the command completes the DATA0 and DATA1 registers will contain the read data. 3'b100 - Process Call This command uses the transmit slave address, command, DATA0 and DATA1 registers. Bit 0 of the slave address register determines if this is a read or write command. After the command completes, the DATA0 and DATA1 registers will contain the read data. 3'b101 - Block This command uses the transmit slave address, command, and DATA0 registers, and the Block Data Byte register. For block write, the count is stored in the DATA0 register and indicates how many bytes of data will be transferred. For block reads, the count is received and stored in the DATA0 register. Bit 0 of the slave address register selects if this is a read or write command. For writes, data is retrieved from the first n (where n is equal to the specified count) addresses of the SRAM array. For reads, the data is stored in the Block Data Byte register. 3'b110 - I2C Read This command uses the transmit slave address, command, DATA0, DATA1 registers, and the Block Data Byte register. The read data is stored in the Block Data Byte register. The Intel SOC will continue reading data until the NAK is received. 3'b111 - Block Process This command uses the transmit slave address, command, DATA0 and the Block Data Byte register. For block write, the count is stored in the DATA0 register and indicates how many bytes of data will be transferred. For block read, the count is received and stored in the DATA0 register. Bit 0 of the slave address register always indicate a write command. For writes, data is retrieved from the first m (where m is equal to the specified count) addresses of the SRAM array. For reads, the data is stored in the Block Data Byte register. Note: E32B bit in the Auxiliary Control Register must be set for this command to work.
1	0b RW	KILL: KILL - When set, kills the current host transaction taking place, sets the FAILED status bit, and asserts the interrupt (or SMI) selected by the SMB_Cfg_HCFG.SMI_EN field. This bit, once set, must be cleared to allow the SMB Host Controller to function normally
0	0b RW	INTREN: Enable the generation of an interrupt or SMI upon the completion of the command. Enables also other interrupt sendings , like ALERT and HOST_NOTIFY



33.7.3 Host Command Register (SMB_Mem_HCMD)—Offset 3h

This eight bit field is transmitted by the host controller in the command field of the SMB protocol during the execution of any command.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_HCMD: [MBARL] + 3h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7	4	0
0	0	0
HCMD		

Bit Range	Default & Access	Description
7:0	00h RW	HCMD: Command to be transmitted

33.7.4 Transmit Slave Address Register (SMB_Mem_TSA)—Offset 4h

This register is transmitted by the host controller in the slave address field of the SMB protocol. This is the address of the target

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_TSA: [MBARL] + 4h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7	4	0
0	0	0
ADDR		RW

Bit Range	Default & Access	Description
7:1	0000000b RW	ADDR: 7-bit address of the targeted slave
0	0b RW	RW: Direction of the host transfer. 1 = read, 0 = write Note: Writes to TSA values of 0xA0 0xAE are blocked depending on the setting of the SPD write disable bit in HCFG D31_F3_HostConfiguration.



33.7.5 Data 0 Register (SMB_Mem_HD0)—Offset 5h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_HD0: [MBARL] + 5h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7				4				0
0	0	0	0	0	0	0	0	0
HD0								

Bit Range	Default & Access	Description
7:0	00h RW	HD0: DATA0/COUNT - This field contains the eight bit data sent in the DATA0 field of the SMB protocol. For block write commands, this register reflects the number of bytes to transfer. This register should be programmed to a value between 1 and 32 for block counts. A count of 0 or a count above 32 will result in unpredictable behavior. The host controller does not check or log illegal block counts.

33.7.6 Data 1 Register (SMB_Mem_HD1)—Offset 6h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_HD1: [MBARL] + 6h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7				4				0
0	0	0	0	0	0	0	0	0
HD1								

Bit Range	Default & Access	Description
7:0	00h RW	HD1: DATA1 - This eight bit register is transmitted in the DATA1 field of the SMB protocol during the execution of any command.

33.7.7 Host Block Data (SMB_Mem_HBD)—Offset 7h

Access Method


Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_HBD: [MBARL] + 7h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h



7	4	0
0	0	0
HBD		
Bit Range	Default & Access	Description
7:0	00h RW	HBD: Block Data (BDTA) - This is either a register, or a pointer into a 32-byte block array, depending upon whether the E32B bit is set in the Auxiliary Control register. When the E32B bit is cleared, this is a register containing a byte of data to be sent on a block write or read from on a block read, just as it behaved on the INTEL SOC. When the E32B bit is set, reads and writes to this register are used to access the 32-byte block data storage array. An internal index pointer is used to address the array, which is reset to 0 by reading the HCTL register (offset 02h). The index pointer then increments automatically upon each access to this register. The transfer of block data into (read) or out of (write) this storage array during an SMBus transaction always starts at index address 0. When the E32B bit is set, for writes, software will write up to 32-bytes to this register as part of the setup for the command. After the Host Controller has sent the Address, Command, and Byte Count fields, it will send the bytes in the SRAM pointed to by this register. When the E32B bit is cleared for writes, software will place a single byte in this register. After the host controller has sent the address, command, and byte count fields, it will send the byte in this register. If there is more data to send, software will write the next series of bytes to the FIFO pointed to by this register and clear the DONE_STS bit. The controller will then send the next byte. During the time between the last byte being transmitted to the next byte being transmitted, the controller will insert wait-states on the interface. When the E32B bit is set for reads, after receiving the byte count into the Data0 register, the first series of data bytes go into the FIFO pointed to by this register. If the byte count has been exhausted or the 32-byte FIFO has been filled, the controller will generate an SMI or interrupt (depending on configuration) and set the DONE_STS bit. Software will then read the data. During the time between when the last byte is read from the FIFO to when the DONE_STS bit is cleared, the controller will insert wait-states on the interface.

33.7.8 Packet Error Check Data Register (SMB_Mem_PEC)—Offset 8h

This register contains the 8-bit CRC value that is used as the Packet Error Check on SMBus. For writes, this register is written by software prior to running the command. For reads, this register is read by software after the read command is completed on SMBus.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_PEC: [MBARL] + 8h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7	4	0
0	0	0
PEC		
Bit Range	Default & Access	Description
7:0	00h RW	PEC: This 8-bit register is written with the SMBus PEC data prior to a write transaction. For read transactions, the PEC data is loaded from the SMBus into this register and is then read by software. Software must ensure that the IUS bit is properly maintained to avoid having this field over-written by a write transaction following a read transaction.



33.7.9 Auxiliary Status (SMB_Mem_AUXS)—Offset Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_AUXS: [MBARL] + Ch

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7	4	0
0	0	0
RSVD		CRCE

Bit Range	Default & Access	Description
7:1	000000b RO	Reserved (RSVD): Reserved.
0	0b RW	CRCE: CRC Error (CRCE) - This bit is set if a received message contained a CRC error. When this bit is set, the DEVERR bit of the host status register will also be set. This bit will be set by the controller if a software abort occurs in the middle of the CRC portion of the cycle or an abort happens after SMBus controller has received the final data bit transmitted by external slave.

33.7.10 Auxiliary Control (SMB_Mem_AUXC)—Offset Dh

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_AUXC: [MBARL] + Dh

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7	4	0
0	0	0
RSV1		E32B AAC

Bit Range	Default & Access	Description
7:2	000000b RO	Reserved (RSV1): Reserved
1	0b RW	E32B: Enable 32-byte Buffer (E32B) - When set, the Host Block Data register is a pointer into a 32-byte buffer, as opposed to a single register. This enables the block commands to transfer or receive up to 32-bytes before the controller generates an interrupt
0	0b RW/O	AAC: Automatically Append CRC (AAC) - When set, the SMBus controller will automatically append the CRC. This bit must not be changed during SM Bus transactions, or undetermined behavior will result. It should be programmed only once during the lifetime of the function.



33.7.11 SMBUS_PIN_CTL Register (SMB_Mem_SMBC)—Offset Fh

Software bus accesses register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_SMBC: [MBARL] + Fh

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 07h

7	4	0
0	0	1
RSV1	SMBCLKCTL	SMBCLK

Bit Range	Default & Access	Description
7:3	00000b RO	Reserved (RSV1): Reserved
2	1b RW	SMBCLKCTL: This Read/Write bit has a default of 1. 0 = SMBus controller will drive the SMB_CLK pin low, independent of what the other SMB logic would otherwise indicate for the SMB_CLK pin. 1 = The SMB_CLK pin is Not overdriven low. The other SMBus logic controls the state of the pin.
1	1b RO	SMBDAT: This pin returns the value on the SMB_DATA pin. It will be 1 to indicate high, 0 to indicate low. This allows software to read the current state of the pin.
0	1b RO	SMBCLK: This pin returns the value on the SMB_CLK pin. It will be 1 to indicate high, 0 to indicate low. This allows software to read the current state of the pin.

33.7.12 Slave Status Register (SMB_Mem_SSTS)—Offset 10h

All bits in this register are implemented in the 64 kHz clock domain. Therefore, software must poll the register until a write takes effect before assuming that a write has completed internally

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_SSTS: [MBARL] + 10h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7	4	0
0	0	0
RSV1	HNST	



Bit Range	Default & Access	Description
7:1	0000000b RO	Reserved (RSV1): Reserved
0	0b RW	HNST: HOST_NOTIFY_STS: The SMBus controller sets this bit to a 1 when it has completely received a successful Host Notify Command on the SMBus pins. Software reads this bit to determine that the source of the interrupt or SMI# was the reception of the Host Notify Command. Software clears this bit after reading any information needed from the Notify address and data registers by writing a 1 to this bit. Note that the SMBus controller will allow the Notify Address and Data registers to be over-written once this bit has been cleared. When this bit is 1, the SMBus controller will NACK the first byte (host address) of any new 'Host Notify' commands on the SMBus. Writing a 0 to this bit has no effect.

33.7.13 Slave Command Register (SMB_Mem_SCMD)—Offset 11h

All bits in this register are implemented in a slow (64khz) clock domain. Therefore, software must poll the register until a write takes effect before assuming that a write has completed internally. Also, software must confirm the prior written value before writing to the register again.

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_SCMD: [MBARL] + 11h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7	4	0
0	0	0
RSV1		
SMBALTDIS		
HNWAKEEN		
HNINTREN		

Bit Range	Default & Access	Description
7:3	00000b RO	Reserved (RSV1): Reserved
2	0b RW	SMBALTDIS: Software sets this bit to 1 to block the generation of the interrupt or SMI# due to the SMB_ALERTB source. This bit is logically inverted and 'AND'ed with the SMB_ALERTB bit of HSTS register. The resulting signal is distributed to the SMI# and/or interrupt generation logic.
1	0b RW	HNWAKEEN: Software sets this bit to 1 to enable the reception of a Host Notify command as a wake event.
0	0b RW	HNINTREN: Software sets this bit to 1 to enable the generation of interrupt or SMI when HOST_NOTIFY_STS is 1. This enable does not affect the setting of the HOST_NOTIFY_STS bit. When the interrupt is generated, either INTRB or SMI is generated, depending on the value of the SMI_EN bit (D31, F3, Off40h, B1). If the HOST_NOTIFY_STS bit is set when this bit is written to a 1, then the interrupt (or SMI) will be generated. The interrupt (or SMI) is logically generated by AND'ing the STS and INTREN bits.



33.7.14 Notify Device Address Register (SMB_Mem_NDA)—Offset 14h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_NDA: [MBARL] + 14h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7	0	0	0	4	0	0	0	0	0
NDA								RSV1	

Bit Range	Default & Access	Description
7:1	0000000b RO	NDA: DEVICE_ADDRESS - This field contains the 7-bit device address received during the Host Notify protocol of the SMBus 2.0 specification. Software should only consider this field valid when the HOST_NOTIFY_STS bit is set to 1.
0	0b RO	Reserved (RSV1): Reserved

33.7.15 Notify Data Low Byte Register (SMB_Mem_NDLB)—Offset 16h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_NDLB: [MBARL] + 16h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7	0	0	0	4	0	0	0	0	0
NDLB									

Bit Range	Default & Access	Description
7:0	00h RO	NDLB: DATA_LOW_BYTE - This field contains the first (low) byte of data received during the Host Notify protocol of the SMBus 2.0 specification. Software should only consider this field valid when the HOST_NOTIFY_STS bit is set to 1.



33.7.16 Notify Data High Byte Register (SMB_Mem_NDHB)—Offset 17h

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

SMB_Mem_NDHB: [MBARL] + 17h

MBARL Type: PCI Configuration Register (Size: 32 bits)

MBARL Reference: [B:0, D:31, F:3] + 10h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
NDHB									

Bit Range	Default & Access	Description
7:0	00h RO	NDHB: DATA_HIGH_BYTE - This field contains the second (high) byte of data received during the Host Notify protocol of the SMBus 2.0 specification. Software should only consider this field valid when the HOST_NOTIFY_STS bit is set to 1.



33.8 PCU SMBUS I/O Registers

Table 318. Summary of PCU SMBUS I/O Registers—SMB_Config_IOBAR

Offset	Size	Register ID—Description	Default Value
0h	1	"Host Status Register (SMB_Mem_HSTS_io)—Offset 0h" on page 4478	00h
2h	1	"Host Control Register (SMB_Mem_HCTL_io)—Offset 2h" on page 4479	00h
3h	1	"Host Command Register (SMB_Mem_HCMD_io)—Offset 3h" on page 4482	00h
4h	1	"Transmit Slave Address Register (SMB_Mem_TSA_io)—Offset 4h" on page 4482	00h
5h	1	"Data 0 Register (SMB_Mem_HD0_io)—Offset 5h" on page 4483	00h
6h	1	"Data 1 Register (SMB_Mem_HD1_io)—Offset 6h" on page 4483	00h
7h	1	"Host Block Data (SMB_Mem_HBD_io)—Offset 7h" on page 4483	00h
8h	1	"Packet Error Check Data Register (SMB_Mem_PEC_io)—Offset 8h" on page 4484	00h
Ch	1	"Auxiliary Status (SMB_Mem_AUXS_io)—Offset Ch" on page 4485	00h
Dh	1	"Auxiliary Control (SMB_Mem_AUXC_io)—Offset Dh" on page 4485	00h
Fh	1	"SMBUS_PIN_CTL Register (SMB_Mem_SMBC_io)—Offset Fh" on page 4486	07h
10h	1	"Slave Status Register (SMB_Mem_SSTS_io)—Offset 10h" on page 4486	00h
11h	1	"Slave Command Register (SMB_Mem_SCMD_io)—Offset 11h" on page 4487	00h
14h	1	"Notify Device Address Register (SMB_Mem_NDA_io)—Offset 14h" on page 4488	00h
16h	1	"Notify Data Low Byte Register (SMB_Mem_NDLB_io)—Offset 16h" on page 4488	00h
17h	1	"Notify Data High Byte Register (SMB_Mem_NDHB_io)—Offset 17h" on page 4489	00h

33.8.1 Host Status Register (SMB_Mem_HSTS_io)—Offset 0h

All status bits are set by hardware and cleared by the software writing a one to the particular bit position. Writing a zero to any bit position has no affect

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_HSTS_io: [IOBAR] + 0h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
BDS	IUS	SMB_ALERTB	FAILED	BERR	DEVERR	INTR	HBSY



Bit Range	Default & Access	Description
7	0b RW	BDS: BYTE_DONE_STS (BDS) - This bit will be set to 1 when the host controller has received a byte (for Block Read commands) or if it has completed transmission of a byte (for Block Write commands) when the 32-byte buffer is not being used. Note that this bit will be set, even on the last byte of the transfer. Software clears the bit by writing a 1 to the bit position. This bit has no meaning for block transfers when the 32-byte buffer is enabled. Note: When the last byte of a block message is received, the host controller will set this bit. However, it will not immediately set the INTR bit (bit 1 in this register). When the interrupt handler clears the BYTE_DONE_STS bit, the message is considered complete, and the host controller will then set the INTR bit (and generate another interrupt). Thus, for a block message of n bytes, the SMBus host will generate n+1 interrupts. The interrupt handler needs to be implemented to handle these cases.
6	0b RW	IUS: In Use Status (IUS) - After a full PCI reset, a read to this bit returns a 0. After the first read, subsequent reads will return a 1. A write of a 1 to this bit will reset the next read value to 0. Writing a 0 to this bit has no effect. Software can poll this bit until it reads a 0, and will then own the usage of the host controller. This bit has no other effect on the hardware, and is only used as semaphore among various independent software threads that may need to use the SMBus host
5	0b RW	SMB_ALERTB: the SOC sets this bit to a '1' to indicates source of the interrupt or SMI# was the SMB_ALERTB signal. Software resets this bit by writing a 1 to this location.
4	0b RW	FAILED: Failed (FAIL) - When set, this indicates that the source of the interrupt or SMI was a failed bus transaction. This is set in response to the KILL bit being set to terminate the host transaction.
3	0b RW	BERR: Bus Error (BERR) - When set, this indicates the source of the interrupt or SMI was a transaction collision.
2	0b RW	DEVERR: Device Error (DERR) - When set, this indicates that the source of the interrupt or SMI was due one of the following: Illegal Command Field Unclaimed Cycle (host initiated) Host Device Time-out Error. CRC Error Write Protection Access Error (START bit will be cleared, Device Error will be set and Host Busy is never set because SMB Transaction never took place).
1	0b RW	INTR: Interrupt (INTR) - When set, this indicates that the source of the interrupt or SMI was the successful completion of its last command.
0	0b RW	HBSY: Host Busy (HBSY) - A '1' indicates that the SMBus host is running a command from the host interface. No SMB registers should be accessed while this bit is set. Exception: The BLOCK DATA REGISTER can be accessed when this bit is set ONLY when the SMB_CMD bits (in Host control register) are programmed for Block command or I2C Read command. This is necessary in order to check the DONE_STS bit.

33.8.2 Host Control Register (SMB_Mem_HCTL_io)—Offset 2h

Host Control Register

Note: A read to this register will clear the pointer in the 32-byte buffer.

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_HCTL_io: [IOBAR] + 2h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h



7			4			0
0	0	0	0	0	0	0
PECEN	SATRT	LBYTE	SMBCMD		KILL	INTREN

Bit Range	Default & Access	Description
7	0b RW	PECEN: PEC_EN: When set to '1', this bit causes the host controller to perform the SMBus transaction with the Packet Error Checking phase appended. For writes, the value of the PEC byte is transferred from the PEC Register. For reads, the PEC byte is loaded in to the PEC Register. When this bit is cleared to '0', the SMBus host controller does not perform the transaction with the PEC phase appended. This bit must be written prior to the write in which the START bit is set.
6	0b WO	START (SATRT): START: This write-only bit is used to initiate the command described in the SMB_CMD field. All registers should be setup prior to writing a '1' to this bit position. This bit always reads zero. The HOST_BUSY bit in the Host Status register (offset 00h) can be used to identify when the SMBus controller has finished the command.
5	0b RW	LBYTE: LAST_BYTE: Used for I2C Read commands as an indication that the next byte will be the last one to be received for that block. The algorithm and usage model for this bit will be as follows (assume a message of n bytes): A. When the software sees the BYTE_DONE_STS bit set (bit 7 in the SMBus Host Status Register) for each of bytes 1 through n-2 of the message, the software should then read the Block Data Byte Register to get the byte that was just received. B. After reading each of bytes 1 to n-2 of the message, the software will then clear the BYTE_DONE_STS bit. C. After receiving byte n-1 of the message, the software will then set the 'LAST BYTE' bit. The software will then clear the BYTE_DONE_STS bit. D. The Intel PCH will then receive the last byte of the message (byte n). However, the Intel PCH state machine will see the LAST_BYTE bit set, and instead of sending an ACK after receiving the last byte, it will instead send a NAK. E. After receiving the last byte (byte n), the software will still clear the BYTE_DONE_STS bit. However, the LAST_BYTE bit will be irrelevant at that point. Note: This bit may be set when the TCO timer causes the SECOND_TO_STS bit to be set. See the TCO2_STS Register in Volume 1, bit 1 for more details on that bit. The SMBus device driver should clear the LAST_BYTE bit (if it is set) before starting any new command. Note: In addition to I2C Read Commands, the LAST_BYTE bit will also cause Block Read/Write cycles to stop prematurely (at the end of the next byte).



Bit Range	Default & Access	Description
4:2	000b RW	SMBCMD: SMB_CMD - As shown by the bit encoding below, indicates which command the SMBus host is to perform. If enabled, the SMBus host will generate an interrupt or SMI when the command has completed. If the value is for a non-supported or reserved command, the SMBus host will set the device error (DEV_ERR) status bit and generate an interrupt when the START bit is set. The SMBus controller will perform no command, and will not operate until DEV_ERR is cleared. 3'b000 - Quick The slave address and read/write value (bit 0) are stored in the tx slave address register 3'b001 - Byte This command uses the transmit slave address and command registers. Bit 0 of the slave address register determines if this is a read or write command. If it is a read, after the command completes the DATA0 register will contain the read data. 3'b010 - Byte Data This command uses the transmit slave address, command, and DATA0 registers. Bit 0 of the slave address register determines if this is a read or write command. If it is a read, the DATA0 register will contain the read data 3'b011 - Word Data This command uses the transmit slave address, command, DATA0 and DATA1 registers. Bit 0 of the slave address register determines if this is a read or write command. If it is a read, after the command completes the DATA0 and DATA1 registers will contain the read data. 3'b100 - Process Call This command uses the transmit slave address, command, DATA0 and DATA1 registers. Bit 0 of the slave address register determines if this is a read or write command. After the command completes, the DATA0 and DATA1 registers will contain the read data. 3'b101 - Block This command uses the transmit slave address, command, and DATA0 registers, and the Block Data Byte register. For block write, the count is stored in the DATA0 register and indicates how many bytes of data will be transferred. For block reads, the count is received and stored in the DATA0 register. Bit 0 of the slave address register selects if this is a read or write command. For writes, data is retrieved from the first n (where n is equal to the specified count) addresses of the SRAM array. For reads, the data is stored in the Block Data Byte register. 3'b110 - I2C Read This command uses the transmit slave address, command, DATA0, DATA1 registers, and the Block Data Byte register. The read data is stored in the Block Data Byte register. The Intel PCH will continue reading data until the NAK is received. 3'b111 - Block Process This command uses the transmit slave address, command, DATA0 and the Block Data Byte register. For block write, the count is stored in the DATA0 register and indicates how many bytes of data will be transferred. For block read, the count is received and stored in the DATA0 register. Bit 0 of the slave address register always indicate a write command. For writes, data is retrieved from the first m (where m is equal to the specified count) addresses of the SRAM array. For reads, the data is stored in the Block Data Byte register. Note: E32B bit in the Auxiliary Control Register must be set for this command to work.
1	0b RW	KILL: KILL - When set, kills the current host transaction taking place, sets the FAILED status bit, and asserts the interrupt (or SMI) selected by the SMB_INTRSEL field. This bit, once set, must be cleared to allow the SMB Host Controller to function normally
0	0b RW	INTREN: Enable the generation of an interrupt or SMI upon the completion of the command. Enables also other interrupt sendings , like ALERT and HOST_NOTIFY



33.8.3 Host Command Register (SMB_Mem_HCMD_io)—Offset 3h

This eight bit field is transmitted by the host controller in the command field of the SMB protocol during the execution of any command.

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_HCMD_io: [IOBAR] + 3h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7	4	0
0	0	0
HCMD		

Bit Range	Default & Access	Description
7:0	00h RW	HCMD: Command to be transmitted

33.8.4 Transmit Slave Address Register (SMB_Mem_TSA_io)—Offset 4h

This register is transmitted by the host controller in the slave address field of the SMB protocol. This is the address of the target

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_TSA_io: [IOBAR] + 4h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7	4	0
0	0	0
ADDR		RW

Bit Range	Default & Access	Description
7:1	0000000b RW	ADDR: 7-bit address of the targeted slave
0	0b RW	RW: Direction of the host transfer. 1 = read, 0 = write Note: Writes to TSA values of 0xA0 0xAE are blocked depending on the setting of the SPD write disable bit in HCFG D31_F3_HostConfiguration.



33.8.5 Data 0 Register (SMB_Mem_HD0_io)—Offset 5h

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_HD0_io: [IOBAR] + 5h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7				4				0
0	0	0	0	0	0	0	0	0
HD0								

Bit Range	Default & Access	Description
7:0	00h RW	HD0: DATA0/COUNT - This field contains the eight bit data sent in the DATA0 field of the SMB protocol. For block write commands, this register reflects the number of bytes to transfer. This register should be programmed to a value between 1 and 32 for block counts. A count of 0 or a count above 32 will result in unpredictable behavior. The host controller does not check or log illegal block counts.

33.8.6 Data 1 Register (SMB_Mem_HD1_io)—Offset 6h

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_HD1_io: [IOBAR] + 6h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7				4				0
0	0	0	0	0	0	0	0	0
HD1								

Bit Range	Default & Access	Description
7:0	00h RW	HD1: DATA1 - This eight bit register is transmitted in the DATA1 field of the SMB protocol during the execution of any command.

33.8.7 Host Block Data (SMB_Mem_HBD_io)—Offset 7h

Access Method


Type: I/O Register
(Size: 8 bits)

SMB_Mem_HBD_io: [IOBAR] + 7h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h



7	4	0
0	0	0
HBD		
Bit Range	Default & Access	Description
7:0	00h RW	HBD: Block Data (BDTA) - This is either a register, or a pointer into a 32-byte block array, depending upon whether the E32B bit is set in the Auxiliary Control register. When the E32B bit is cleared, this is a register containing a byte of data to be sent on a block write or read from on a block read, just as it behaved on the INTEL SOC. When the E32B bit is set, reads and writes to this register are used to access the 32-byte block data storage array. An internal index pointer is used to address the array, which is reset to 0 by reading the HCTL register (offset 02h). The index pointer then increments automatically upon each access to this register. The transfer of block data into (read) or out of (write) this storage array during an SMBus transaction always starts at index address 0. When the E32B bit is set, for writes, software will write up to 32-bytes to this register as part of the setup for the command. After the Host Controller has sent the Address, Command, and Byte Count fields, it will send the bytes in the SRAM pointed to by this register. When the E32B bit is cleared for writes, software will place a single byte in this register. After the host controller has sent the address, command, and byte count fields, it will send the byte in this register. If there is more data to send, software will write the next series of bytes to the FIFO pointed to by this register and clear the DONE_STS bit. The controller will then send the next byte. During the time between the last byte being transmitted to the next byte being transmitted, the controller will insert wait-states on the interface. When the E32B bit is set for reads, after receiving the byte count into the Data0 register, the first series of data bytes go into the FIFO pointed to by this register. If the byte count has been exhausted or the 32-byte FIFO has been filled, the controller will generate an SMI or interrupt (depending on configuration) and set the DONE_STS bit. Software will then read the data. During the time between when the last byte is read from the FIFO to when the DONE_STS bit is cleared, the controller will insert wait-states on the interface.

33.8.8 Packet Error Check Data Register (SMB_Mem_PEC_io)—Offset 8h

This register contains the 8-bit CRC value that is used as the Packet Error Check on SMBus. For writes, this register is written by software prior to running the command. For reads, this register is read by software after the read command is completed on SMBus.

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_PEC_io: [IOBAR] + 8h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7	4	0
0	0	0
PEC		
Bit Range	Default & Access	Description
7:0	00h RW	PEC: This 8-bit register is written with the SMBus PEC data prior to a write transaction. For read transactions, the PEC data is loaded from the SMBus into this register and is then read by software. Software must ensure that the IUS bit is properly maintained to avoid having this field over-written by a write transaction following a read transaction.



33.8.9 Auxiliary Status (SMB_Mem_AUXS_io)—Offset Ch

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_AUXS_io: [IOBAR] + Ch

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7				4					0
0		0		0		0		0	0
RSVD									CRCE

Bit Range	Default & Access	Description
7:1	0000000b RO	Reserved (RSVD): Reserved.
0	0b RW	CRCE: CRC Error (CRCE) - This bit is set if a received message contained a CRC error. When this bit is set, the DEVERR bit of the host status register will also be set. This bit will be set by the controller if a software abort occurs in the middle of the CRC portion of the cycle or an abort happens after SMBus controller has received the final data bit transmitted by external slave.

33.8.10 Auxiliary Control (SMB_Mem_AUXC_io)—Offset Dh

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_AUXC_io: [IOBAR] + Dh

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7				4					0
0		0		0		0		0	0
RSV1									E32B
									AAC

Bit Range	Default & Access	Description
7:2	000000b RO	Reserved (RSV1): Reserved
1	0b RW	E32B: Enable 32-byte Buffer (E32B) - When set, the Host Block Data register is a pointer into a 32-byte buffer, as opposed to a single register. This enables the block commands to transfer or receive up to 32-bytes before the controller generates an interrupt
0	0b RW/O	AAC: Automatically Append CRC (AAC) - When set, the SMBus controller will automatically append the CRC. This bit must not be changed during SM Bus transactions, or undetermined behavior will result. It should be programmed only once during the lifetime of the function.



33.8.11 SMBUS_PIN_CTL Register (SMB_Mem_SMBC_io)—Offset Fh

Software bus accesses register

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_SMBC_io: [IOBAR] + Fh

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 07h

7	4	0
0	0	1
RSV1		SMBCLK

Bit Range	Default & Access	Description
7:3	0000b RO	Reserved (RSV1): Reserved
2	1b RW	SMBCLKCTL: This Read/Write bit has a default of 1. 0 = SMBus controller will drive the SMB_CLK pin low, independent of what the other SMB logic would otherwise indicate for the SMB_CLK pin. 1 = The SMB_CLK pin is Not overdriven low. The other SMBus logic controls the state of the pin.
1	1b RO	SMBDAT: This pin returns the value on the SMB_DATA pin. It will be 1 to indicate high, 0 to indicate low. This allows software to read the current state of the pin.
0	1b RO	SMBCLK: This pin returns the value on the SMB_CLK pin. It will be 1 to indicate high, 0 to indicate low. This allows software to read the current state of the pin.

33.8.12 Slave Status Register (SMB_Mem_SSTS_io)—Offset 10h

All bits in this register are implemented in the 64 kHz clock domain. Therefore, software must poll the register until a write takes effect before assuming that a write has completed internally

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_SSTS_io: [IOBAR] + 10h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7	4	0
0	0	0
RSV1		HNST



Bit Range	Default & Access	Description
7:1	0000000b RO	Reserved (RSV1): Reserved
0	0b RW	HNST: HOST_NOTIFY_STS: The SMBus controller sets this bit to a 1 when it has completely received a successful Host Notify Command on the SMBus pins. Software reads this bit to determine that the source of the interrupt or SMI# was the reception of the Host Notify Command. Software clears this bit after reading any information needed from the Notify address and data registers by writing a 1 to this bit. Note that the SMBus controller will allow the Notify Address and Data registers to be over-written once this bit has been cleared. When this bit is 1, the SMBus controller will NACK the first byte (host address) of any new 'Host Notify' commands on the SMBus. Writing a 0 to this bit has no effect.

33.8.13 Slave Command Register (SMB_Mem_SCMD_io)—Offset 11h

All bits in this register are implemented in a slow (64khz) clock domain. Therefore, software must poll the register until a write takes effect before assuming that a write has completed internally. Also, software must confirm the prior written value before writing to the register again.

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_SCMD_io: [IOBAR] + 11h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7	4	0
0	0	0
RSV1		
SMBALTDIS		
HNWAKEEN		
HNINTREN		

Bit Range	Default & Access	Description
7:3	00000b RO	Reserved (RSV1): Reserved
2	0b RW	SMBALTDIS: Software sets this bit to 1 to block the generation of the interrupt or SMI# due to the SMB_ALERTB source. This bit is logically inverted and 'AND'ed with the SMB_ALERTB bit of HSTS register. The resulting signal is distributed to the SMI# and/or interrupt generation logic.
1	0b RW	HNWAKEEN: Software sets this bit to 1 to enable the reception of a Host Notify command as a wake event.
0	0b RW	HNINTREN: Software sets this bit to 1 to enable the generation of interrupt or SMI when HOST_NOTIFY_STS is 1. This enable does not affect the setting of the HOST_NOTIFY_STS bit. When the interrupt is generated, either INTRB or SMI is generated, depending on the value of the SMI_EN bit (D31, F3, Off40h, B1). If the HOST_NOTIFY_STS bit is set when this bit is written to a 1, then the interrupt (or SMI) will be generated. The interrupt (or SMI) is logically generated by AND'ing the STS and INTREN bits.



33.8.14 Notify Device Address Register (SMB_Mem_NDA_io)—Offset 14h

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_NDA_io: [IOBAR] + 14h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7	4	0
0	0	0
NDA		RSV1

Bit Range	Default & Access	Description
7:1	0000000b RO	NDA: DEVICE_ADDRESS - This field contains the 7-bit device address received during the Host Notify protocol of the SMBus 2.0 specification. Software should only consider this field valid when the HOST_NOTIFY_STS bit is set to 1.
0	0b RO	Reserved (RSV1): Reserved

33.8.15 Notify Data Low Byte Register (SMB_Mem_NDLB_io)—Offset 16h

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_NDLB_io: [IOBAR] + 16h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7	4	0
0	0	0
NDLB		

Bit Range	Default & Access	Description
7:0	00h RO	NDLB: DATA_LOW_BYTE - This field contains the first (low) byte of data received during the Host Notify protocol of the SMBus 2.0 specification. Software should only consider this field valid when the HOST_NOTIFY_STS bit is set to 1.



33.8.16 Notify Data High Byte Register (SMB_Mem_NDHB_io)—Offset 17h

Access Method

Type: I/O Register
(Size: 8 bits)

SMB_Mem_NDHB_io: [IOBAR] + 17h

IOBAR Type: PCI Configuration Register (Size: 32 bits)

IOBAR Reference: [B:0, D:31, F:3] + 20h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
NDHB									


Bit Range	Default & Access	Description
7:0	00h RO	NDHB: DATA_HIGH_BYTE - This field contains the second (high) byte of data received during the Host Notify protocol of the SMBus 2.0 specification. Software should only consider this field valid when the HOST_NOTIFY_STS bit is set to 1.

34 PCU – Intel® Legacy Block (iLB) Overview

The Intel Legacy Block (iLB) is a collection of disparate functional blocks that are critical for implementing the legacy PC platform features. These blocks include:

- PCU – iLB – Low Pin Count (LPC) Bridge
- PCU – iLB – Real Time Clock (RTC)
- PCU – iLB – 8254 Timers
- PCU – iLB – High Precision Event Timer (HPET)
- PCU – iLB – GPIO
- PCU – iLB – IO APIC
- PCU – iLB – 8259 Programmable Interrupt Controllers (PIC)

The iLB also implements a register range for configuration of some of those blocks along with support for Non-Maskable Interrupts (NMI).



34.1 Signal Descriptions

Please see [Chapter 2, “Physical Interfaces”](#) for additional details as well as the subsequent sections.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal’s function



Table 319. iLB Signals

Signal Name	Direction Plat. Power	Description
ILB_NMI	I V1P8S	Non-Maskable Interrupt: This is an NMI event indication into the SoC. <i>This signal is muxed and may be used by other functions.</i>

34.2 Features

34.2.1 Key Features

The key features of various blocks are as follows:

- Subtractive agent for the PCU
- LPC Interface
 - Supports Low Pin Count (LPC) 1.1 Specification
 - No support for DMA or bus mastering
 - Supports Trusted Platform Module (TPM) 1.2 and 2.0
 - Subtractive agent for the Intel Legacy Block
- General Purpose Input Output
 - Control interface for SoC GPIOs
 - I/O mapped registers
- 8259 Programmable Interrupt Controller
 - Legacy interrupt support
 - 15 total interrupts through two cascaded controllers
 - I/O and Memory mapped registers
- I/O Advanced Programmable Interrupt Controller
 - Legacy-free interrupt support
 - 87 total interrupts
 - Memory mapped registers
- 8254
 - Legacy timer support
 - Three timers with fixed uses: System Timer, Refresh Request Signal and Speaker Tone
 - I/O mapped registers
- HPET - High Performance Event Timers
 - Legacy-free timer support



- Three timers and one counter
- Memory mapped registers
- Real-Time Clock (RTC)
 - 242 byte RAM backed by battery (aka CMOS RAM)
 - Can generate wake/interrupt when time matches programmed value
 - I/O and indexed registers

34.2.2 Non-Maskable Interrupt

NMI support is enabled by setting the NMI Enable (NMI_EN) bit, at IO Port 70h, Bit 7, to 0b.

Non-Maskable Interrupts (NMIs) can be generated by several sources, as described in [Table 320](#).

Table 320. NMI Sources

NMI Source	NMI Source Enabler/ Disabler	NMI Source Status	Alternate Configuration
SERR# goes active NOTE: A SERR# is only generated internally in the SoC)	NSC.SNE	NSC.SNS	All NMI sources may, alternatively, generate a SMI by setting GNMI.NMI2SMIEN=1b The SoC uses GNMI.NMI2SMIST for observing SMI status
IOCHK# goes active NOTE: A IOCHK# is only generated as a SERIRQ# frame	NSC.INE	NSC.INS	
ILB_NMI goes active NOTE: Active can be defined as being on the positive or negative edge of the signal using the GNMI.GNMIED register bit.	GNMI.GNMIED	GNMI.GNMIS	
Software sets the GNMI.NMIN register bit	GNMI.NMIN	GNMI.NMINS	



34.3 PCU iLB Interrupt Decode and Route

Table 321. Summary of PCU iLB Interrupt Decode and Route Memory Mapped I/O Registers—ILB_BASE_ADDRESS

Offset	Size	Register ID—Description	Default Value
0h	4	"ACTL—Offset 0h" on page 4494	00000003h
4h	4	"MC—Offset 4h" on page 4495	00000000h
8h	1	"PIRQA—Offset 8h" on page 4495	80h
9h	1	"PIRQB—Offset 9h" on page 4496	80h
Ah	1	"PIRQC—Offset Ah" on page 4497	80h
Bh	1	"PIRQD—Offset Bh" on page 4497	80h
Ch	1	"PIRQE—Offset Ch" on page 4498	80h
Dh	1	"PIRQF—Offset Dh" on page 4498	80h
Eh	1	"PIRQG—Offset Eh" on page 4499	80h
Fh	1	"PIRQH—Offset Fh" on page 4499	80h
10h	4	"SCNT—Offset 10h" on page 4500	00000000h
14h	4	"KMC—Offset 14h" on page 4501	00000000h
18h	4	"FS—Offset 18h" on page 4502	00112233h
1Ch	4	"BC—Offset 1Ch" on page 4502	00000100h
20h	2	"IR0—Offset 20h" on page 4503	0000h
22h	2	"IR1—Offset 22h" on page 4504	0000h
24h	2	"IR2—Offset 24h" on page 4504	0000h
26h	2	"IR3—Offset 26h" on page 4505	0000h
28h	2	"IR4—Offset 28h" on page 4505	0000h
2Ah	2	"IR5—Offset 2Ah" on page 4506	0000h
2Ch	2	"IR6—Offset 2Ch" on page 4506	0000h
2Eh	2	"IR7—Offset 2Eh" on page 4507	0000h
30h	2	"IR8—Offset 30h" on page 4508	0000h
32h	2	"IR9—Offset 32h" on page 4508	0000h
34h	2	"IR10—Offset 34h" on page 4509	0000h
36h	2	"IR11—Offset 36h" on page 4509	0000h
38h	2	"IR12—Offset 38h" on page 4510	0000h
3Ah	2	"IR13—Offset 3Ah" on page 4510	0000h
3Ch	2	"IR14—Offset 3Ch" on page 4511	0000h
3Eh	2	"IR15—Offset 3Eh" on page 4512	0000h
40h	2	"IR16—Offset 40h" on page 4512	0000h
42h	2	"IR17—Offset 42h" on page 4513	0000h
44h	2	"IR18—Offset 44h" on page 4513	0000h
46h	2	"IR19—Offset 46h" on page 4514	0000h
48h	2	"IR20—Offset 48h" on page 4514	0000h

Table 321. Summary of PCU iLB Interrupt Decode and Route Memory Mapped I/O Registers—ILB_BASE_ADDRESS (Continued)

Offset	Size	Register ID—Description	Default Value
4Ah	2	"IR21—Offset 4Ah" on page 4515	0000h
4Ch	2	"IR22—Offset 4Ch" on page 4516	0000h
4Eh	2	"IR23—Offset 4Eh" on page 4516	0000h
50h	2	"IR24—Offset 50h" on page 4517	0000h
52h	2	"IR25—Offset 52h" on page 4517	0000h
54h	2	"IR26—Offset 54h" on page 4518	0000h
56h	2	"IR27—Offset 56h" on page 4518	0000h
58h	2	"IR28—Offset 58h" on page 4519	0000h
5Ah	2	"IR29—Offset 5Ah" on page 4520	0000h
5Ch	2	"IR30—Offset 5Ch" on page 4520	0000h
5Eh	2	"IR31—Offset 5Eh" on page 4521	0000h
60h	4	"OIC—Offset 60h" on page 4522	00001100h
64h	4	"RC—Offset 64h" on page 4523	00000000h
6Ch	4	"BCS - BIOS Control Status (BCS)—Offset 6Ch" on page 4523	00000002h
70h	4	"LE—Offset 70h" on page 4524	00000003h
80h	4	"NMI (GNMI)—Offset 80h" on page 4524	00000004h
84h	4	"LPCC—Offset 84h" on page 4525	00000001h
88h	4	"IRQEN (IRQE)—Offset 88h" on page 4526	00000000h

34.3.1 ACTL—Offset 0h

ACPI Control

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

ACTL: [ILB_BASE_ADDRESS] + 0h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB BASE ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000003h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0							

Bit Range	Default & Access	Description
31:3	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Description
2:0	011b RW	SCIS: SCI IRQ Select (SCIS): Specifies on which IRQ SCI will rout to. If not using APIC, SCI must be routed to IRQ9-11 , and that interrupt is not sharable with SERIRQ, but is shareable with other interrupts. If using APIC, SCI can be mapped to IRQ20-23, and can be shared with other interrupts. When the interrupt is mapped to APIC interrupts 9, 10 or 11, APIC must be programmed for active-high reception. When the interrupt is mapped to APIC interrupts 20 through 23, APIC must be programmed for active-low reception.

34.3.2 MC—Offset 4h

Miscellaneous Control

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

MC: [ILB BASE ADDRESS] + 4h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB BASE ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000000h

[illegible]

Bit Range	Default & Access	Description
31:4	0b RO	RSVD0 : Reserved
3	0b RW	DRTC : Disable RTC (DRTC): When set, decodes to the RTC will be disabled, and the accesses instead will be sent to LPC. This allows testing to determine whether these functions are needed for XP and Vista 'EDS Note: Do not include this field in the EDS.
2	0b RW	D8259 : Disable 8259 (D8259): When set, decodes to the 8259 will be disabled, and the accesses instead will be sent to LPC. This allows testing to determine whether these functions are needed for XP and Vista 'EDS Note: Do not include this field in the EDS.
1	0b RW	D8254 : Disable 8254 (D8254): When set, decodes to the 8254 will be disabled, and the accesses instead will be sent to LPC. This allows testing to determine whether these functions are needed for XP and Vista 'EDS Note: Do not include this field in the EDS.
0	0b RW	AME : Alt Access Mode is a mode that enables host reading some WO registers . 1. Read 8254 (legacy timers) indirect WO registers 2. Read 8259 (legacy interrupt controller) indirect WO registers 3. Read port 0x70 - port 0x70 includes the RTC memory address [6:0] and the NMI enable bit [7]

34.3.3 PIROA—Offset 8h

PIROA Routing Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

PIROA: [ILB BASE ADDRESS] + 8h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h



Default: 80h

7			4				0
1	0	0	0	0	0	0	0
REN		RSVD0			IR		

Bit Range	Default & Access	Description
7	1b RW	REN: Interrupt Routing Enable (REN): When cleared, the corresponding PIRQx is routed to one of the legacy interrupts specified in bits[3:0]. When set, the PIRQx is not routed to the 8259.
6:4	0b RO	RSVD0: Reserved
3:0	0b RW	IR: IRQ Routing (IR): Indicates how to route PIRQx Bits Mapping Bits Mapping 0h Reserved 8h Reserved 1h Reserved 9h IRQ9 2h Reserved Ah IRQ10 3h IRQ3 Bh IRQ11 4h IRQ4 Ch IRQ12 5h IRQ5 Dh Reserved 6h IRQ6 Eh IRQ14 7h IRQ7 Fh IRQ15

34.3.4 PIRQB—Offset 9h

PIRQB Routing Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

PIRQB: [ILB_BASE_ADDRESS] + 9h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 80h

7			4				0
1	0	0	0	0	0	0	0
REN		RSVD0			IR		

Bit Range	Default & Access	Description
7	1b RW	REN: Interrupt Routing Enable (REN): When cleared, the corresponding PIRQx is routed to one of the legacy interrupts specified in bits[3:0]. When set, the PIRQx is not routed to the 8259.
6:4	0b RO	RSVD0: Reserved
3:0	0b RW	IR: IRQ Routing (IR): Indicates how to route PIRQx Bits Mapping Bits Mapping 0h Reserved 8h Reserved 1h Reserved 9h IRQ9 2h Reserved Ah IRQ10 3h IRQ3 Bh IRQ11 4h IRQ4 Ch IRQ12 5h IRQ5 Dh Reserved 6h IRQ6 Eh IRQ14 7h IRQ7 Fh IRQ15



34.3.5 PIRQC—Offset Ah

PIRQC Routing Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

PIRQC: [ILB_BASE_ADDRESS] + Ah

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 80h

7		4		0
1	0	0	0	0
REN		RSVD0		IR

Bit Range	Default & Access	Description
7	1b RW	REN: Interrupt Routing Enable (REN): When cleared, the corresponding PIRQx is routed to one of the legacy interrupts specified in bits[3:0]. When set, the PIRQx is not routed to the 8259.
6:4	0b RO	RSVD0: Reserved
3:0	0b RW	IR: IRQ Routing (IR): Indicates how to route PIRQx Bits Mapping Bits Mapping 0h Reserved 8h Reserved 1h Reserved 9h IRQ9 2h Reserved Ah IRQ10 3h IRQ3 Bh IRQ11 4h IRQ4 Ch IRQ12 5h IRQ5 Dh Reserved 6h IRQ6 Eh IRQ14 7h IRQ7 Fh IRQ15

34.3.6 PIRQD—Offset Bh

PIRQD Routing Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

PIRQD: [ILB_BASE_ADDRESS] + Bh

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 80h

7		4		0
1	0	0	0	0
REN		RSVD0		IR

Bit Range	Default & Access	Description
7	1b RW	REN: Interrupt Routing Enable (REN): When cleared, the corresponding PIRQx is routed to one of the legacy interrupts specified in bits[3:0]. When set, the PIRQx is not routed to the 8259.
6:4	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Description
3:0	0b RW	IR: IRQ Routing (IR): Indicates how to route PIRQx Bits Mapping Bits Mapping 0h Reserved 8h Reserved 1h Reserved 9h IRQ9 2h Reserved Ah IRQ10 3h IRQ3 Bh IRQ11 4h IRQ4 Ch IRQ12 5h IRQ5 Dh Reserved 6h IRQ6 Eh IRQ14 7h IRQ7 Fh IRQ15

34.3.7 PIRQE—Offset Ch

PIRQE Routing Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

PIRQE: [ILB_BASE_ADDRESS] + Ch

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 80h

7		4	0
1	0	0	0
REN		RSVD0	IR

Bit Range	Default & Access	Description
7	1b RW	REN: Interrupt Routing Enable (REN): When cleared, the corresponding PIRQx is routed to one of the legacy interrupts specified in bits[3:0]. When set, the PIRQx is not routed to the 8259.
6:4	0b RO	RSVD0: Reserved
3:0	0b RW	IR: IRQ Routing (IR): Indicates how to route PIRQx Bits Mapping Bits Mapping 0h Reserved 8h Reserved 1h Reserved 9h IRQ9 2h Reserved Ah IRQ10 3h IRQ3 Bh IRQ11 4h IRQ4 Ch IRQ12 5h IRQ5 Dh Reserved 6h IRQ6 Eh IRQ14 7h IRQ7 Fh IRQ15

34.3.8 PIRQF—Offset Dh

PIRQF Routing Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

PIRQF: [ILB_BASE_ADDRESS] + Dh

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 80h

7		4	0
1	0	0	0
REN		RSVD0	IR



Bit Range	Default & Access	Description
7	1b RW	REN: Interrupt Routing Enable (REN): When cleared, the corresponding PIRQx is routed to one of the legacy interrupts specified in bits[3:0]. When set, the PIRQx is not routed to the 8259.
6:4	0b RO	RSVD0: Reserved
3:0	0b RW	IR: IRQ Routing (IR): Indicates how to route PIRQx Bits Mapping Bits Mapping 0h Reserved 8h Reserved 1h Reserved 9h IRQ9 2h Reserved Ah IRQ10 3h IRQ3 Bh IRQ11 4h IRQ4 Ch IRQ12 5h IRQ5 Dh Reserved 6h IRQ6 Eh IRQ14 7h IRQ7 Fh IRQ15

34.3.9 PIRQG—Offset Eh

PIRQG Routing Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

PIRQG: [ILB_BASE_ADDRESS] + Eh

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 80h

7		4		0
1	0	0	0	0
REN		RSVD0		IR

Bit Range	Default & Access	Description
7	1b RW	REN: Interrupt Routing Enable (REN): When cleared, the corresponding PIRQx is routed to one of the legacy interrupts specified in bits[3:0]. When set, the PIRQx is not routed to the 8259.
6:4	0b RO	RSVD0: Reserved
3:0	0b RW	IR: IRQ Routing (IR): Indicates how to route PIRQx Bits Mapping Bits Mapping 0h Reserved 8h Reserved 1h Reserved 9h IRQ9 2h Reserved Ah IRQ10 3h IRQ3 Bh IRQ11 4h IRQ4 Ch IRQ12 5h IRQ5 Dh Reserved 6h IRQ6 Eh IRQ14 7h IRQ7 Fh IRQ15

34.3.10 PIRQH—Offset Fh

PIRQH Routing Control

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

PIRQH: [ILB_BASE_ADDRESS] + Fh

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 80h



Bit Range	Default & Access	Description
7	1b RW	REN: Interrupt Routing Enable (REN): When cleared, the corresponding PIRQx is routed to one of the legacy interrupts specified in bits[3:0]. When set, the PIRQx is not routed to the 8259.
6:4	0b RO	RSVD0: Reserved
3:0	0b RW	IR: IRQ Routing (IR): Indicates how to route PIRQx Bits Mapping Bits Mapping 0h Reserved 8h Reserved 1h Reserved 9h IRQ9 2h Reserved Ah IRQ10 3h IRQ3 Bh IRQ11 4h IRQ4 Ch IRQ12 5h IRQ5 Dh Reserved 6h IRQ6 Eh IRQ14 7h IRQ7 Fh IRQ15

34.3.11 SCNT—Offset 10h

SCNT - Serial IRO Control

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

SCNT: [ILB BASE ADDRESS] + 10h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB BASE ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000000h

Bit Range	Default & Access	Description
31:8	0b RO	RSVD0: Reserved
7	0b RW	MD: Mode (MD): When set, the SERIRQ is in continuous mode. When cleared, SERIRQ is in quiet mode. This bit must be set to guarantee that the first action of SERIRQ is a start frame.
6:0	0b RO	RSVD1: Reserved



34.3.12 KMC—Offset 14h

USB Legacy Keyboard/Mouse Control

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

KMC: [ILB_BASE_ADDRESS] + 14h


ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0						TRAPBY64W	TRAPBY64R	TRAPBY60W
						TRAPBY60R	RSVD1	R64WEN
								R64REN
								R60WEN
								R60REN

Bit Range	Default & Access	Description
31:12	0b RO	RSVD0: Reserved
11	0b RW/1C	TRAPBY64W: TRAPBY64W - SMI Caused by Port 64 Write: Indicates if the event occurred. Note that even if the corresponding enable bit is not set in the Bit 3, then this bit will still be active. It is up to the SMM code to use the enable bit to determine the exact cause of the SMI#. Writing a 1 to this bit will clear the latch.
10	0b RW/1C	TRAPBY64R: TRAPBY64R - SMI Caused by Port 64 Read: Indicates if the event occurred. Note that even if the corresponding enable bit is not set in the Bit 2, then this bit will still be active. It is up to the SMM code to use the enable bit to determine the exact cause of the SMI#. Writing a 1 to this bit will clear the latch.
9	0b RW/1C	TRAPBY60W: TRAPBY60W - SMI Caused by Port 60 Write: Indicates if the event occurred. Note that even if the corresponding enable bit is not set in the Bit 1, then this bit will still be active. It is up to the SMM code to use the enable bit to determine the exact cause of the SMI#. Writing a 1 to this bit will clear the latch.
8	0b RW/1C	TRAPBY60R: TRAPBY60R - SMI Caused by Port 60 Read: Indicates if the event occurred. Note that even if the corresponding enable bit is not set in the Bit 0, then this bit will still be active. It is up to the SMM code to use the enable bit to determine the exact cause of the SMI#. Writing a 1 to this bit will clear the latch.
7:4	0b RO	RSVD1: Reserved
3	0b RW	R64WEN: R64WEN - SMI on Port 64 Writes Enable: When set, a 1 in bit 11 will cause an SMI event.
2	0b RW	R64REN: R64REN - SMI on Port 64 Reads Enable: When set, a 1 in bit 10 will cause an SMI event.
1	0b RW	R60WEN: R60WEN - SMI on Port 60 Writes Enable: When set, a 1 in bit 9 will cause an SMI event.
0	0b RW	R60REN: R60REN - SMI on Port 60 Reads Enable: When set, a 1 in bit 8 will cause an SMI event.



34.3.13 FS—Offset 18h

FS - FWH ID Select

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

FS: [ILB_BASE_ADDRESS] + 18h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00112233h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
IF8	IF0	IE8	IE0	ID8	ID0	IC8	IC0	

Bit Range	Default & Access	Description
31:28	0h RO	IF8: F8-FF IDSEL (IF8): IDSEL to use in FWH cycle for range enabled by BDE.EF8. The Address ranges are: FFF80000h - FFFFFFFFh, FFB80000h - FFBFFFFFh and 000E0000h - 000FFFFFh
27:24	0h RW	IF0: F0-F7 IDSEL (IF0): IDSEL to use in FWH cycle for range enabled by BDE.EF0. The Address ranges are: FFF00000h - FFF7FFFFh, FFB00000h - FFB7FFFFh
23:20	1h RW	IE8: E8-EF IDSEL (IE8): IDSEL to use in FWH cycle for range enabled by BDE.EE8. The Address ranges are: FFE80000h - FFEFFFFFh, FFA80000h - FFAFFFFFh
19:16	1h RW	IE0: E0-E7 IDSEL (IE0): IDSEL to use in FWH cycle for range enabled by BDE.EE0. The Address ranges are: FFE00000h - FFE7FFFFh, FFA00000h - FFA7FFFFh
15:12	2h RW	ID8: D8-DF IDSEL (ID8): IDSEL to use in FWH cycle for range enabled by BDE.ED8. The Address ranges are: FFD80000h - FFDFFFFFh, FF980000h - FF9FFFFFh
11:8	2h RW	ID0: D0-D7 IDSEL (ID0): IDSEL to use in FWH cycle for range enabled by BDE.ED0. The Address ranges are: FFD00000h - FFD7FFFFh, FF900000h - FF97FFFFh
7:4	3h RW	IC8: C8-CF IDSEL (IC8): IDSEL to use in FWH cycle for range enabled by BDE.EC8. The Address ranges are: FFC80000h - FFCFFFFFh, FF880000h - FF8FFFFFh
3:0	3h RW	IC0: C0-C7 IDSEL (IC0): IDSEL to use in FWH cycle for range enabled by BDE.EC0. The Address ranges are: FFC00000h - FFC7FFFFh, FF800000h - FF87FFFFh

34.3.14 BC—Offset 1Ch

BC - BIOS Control

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

BC: [ILB_BASE_ADDRESS] + 1Ch

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000100h



34.3.16 IR1—Offset 22h

IR1 - Interrupt Routing Device 1

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR1: [ILB_BASE_ADDRESS] + 22h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD		IRC		IRA

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.17 IR2—Offset 24h

IR2 - Interrupt Routing Device 2

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR2: [ILB_BASE_ADDRESS] + 24h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD		IRC		IRA

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H



Bit Range	Default & Access	Description
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.18 IR3—Offset 26h

IR3 - Interrupt Routing Device 3

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR3: [ILB_BASE_ADDRESS] + 26h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
IRD	IRC	IRB	IRA	

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.19 IR4—Offset 28h

IR4 - Interrupt Routing Device 4

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR4: [ILB_BASE_ADDRESS] + 28h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
IRD	IRC	IRB	IRA	



Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD : INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC : INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB : INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA : INTA mapping to IRQ A-H

34.3.20 IR5—Offset 2Ah

IR5 - Interrupt Routing Device 5

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR5: [ILB_BASE_ADDRESS] + 2Ah

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15		12		8		4		0
0	0	0	0	0	0	0	0	0
IRD				IRC				IRA

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD : INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC : INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB : INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA : INTA mapping to IRQ A-H

34.3.21 IR6—Offset 2Ch

IR6 - Interrupt Routing Device 6

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR6: [ILB_BASE_ADDRESS] + 2Ch

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h



Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H



34.3.23 IR8—Offset 30h

IR8 - Interrupt Routing Device 8

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR8: [ILB_BASE_ADDRESS] + 30h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD		IRC		IRA

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.24 IR9—Offset 32h

IR9 - Interrupt Routing Device 9

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR9: [ILB_BASE_ADDRESS] + 32h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD		IRC		IRA

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H



Bit Range	Default & Access	Description
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.25 IR10—Offset 34h

IR10 - Interrupt Routing Device 10

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR10: [ILB_BASE_ADDRESS] + 34h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
IRD	IRC	IRB	IRA	

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.26 IR11—Offset 36h

IR11 - Interrupt Routing Device 11

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR11: [ILB_BASE_ADDRESS] + 36h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
IRD	IRC	IRB	IRA	



Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD : INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC : INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB : INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA : INTA mapping to IRQ A-H

34.3.27 IR12—Offset 38h

IR12 - Interrupt Routing Device 12

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR12: [ILB_BASE_ADDRESS] + 38h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD	IRC	IRB	IRA	

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD : INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC : INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB : INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA : INTA mapping to IRQ A-H

34.3.28 IR13—Offset 3Ah

IR13 - Interrupt Routing Device 13

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR13: [ILB_BASE_ADDRESS] + 3Ah

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h



15				12				8				4				0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
IRD				IRC				IRB				IRA				

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.29 IR14—Offset 3Ch

IR14 - Interrupt Routing Device 14

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR14: [ILB_BASE_ADDRESS] + 3Ch

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15			12			8			4			0
0	0	0	0	0	0	0	0	0	0	0	0	0
IRD				IRC			IRB			IRA		

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H



Access Method

IR15: [ILB BASE ADDRESS] + 3Eh

ILB BASE ADDRESS Reference: [B:0, D:31, F:0] + 50h

15			12			8			4			0
0	0	0	0	0	0	0	0	0	0	0	0	0
IRD				IRC			IRB			IRA		

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.31 IR16—Offset 40h

Access Method

IR16: [ILB BASE ADDRESS] + 40h

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

15	12	8	4	0
0	0	0	0	0
IRD	IRC	IRB	IRA	

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H



Bit Range	Default & Access	Description
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.32 IR17—Offset 42h

IR17 - Interrupt Routing Device 17

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR17: [ILB_BASE_ADDRESS] + 42h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
IRD	IRC	IRB	IRA	

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.33 IR18—Offset 44h

IR18 - Interrupt Routing Device 18

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR18: [ILB_BASE_ADDRESS] + 44h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
IRD	IRC	IRB	IRA	



Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD : INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC : INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB : INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA : INTA mapping to IRQ A-H

34.3.34 IR19—Offset 46h

IR19 - Interrupt Routing Device 19

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR19: [ILB_BASE_ADDRESS] + 46h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD	IRC	IRB	IRA	

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD : INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC : INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB : INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA : INTA mapping to IRQ A-H

34.3.35 IR20—Offset 48h

IR20 - Interrupt Routing Device 20

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR20: [ILB_BASE_ADDRESS] + 48h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h



15				12				8				4				0
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
IRD				IRC				IRB				IRA				

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.36 IR21—Offset 4Ah

IR21 - Interrupt Routing Device 21

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR21: [ILB_BASE_ADDRESS] + 4Ah

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15			12			8			4			0
0	0	0	0	0	0	0	0	0	0	0	0	0
IRD				IRC			IRB			IRA		

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H



34.3.37 IR22—Offset 4Ch

IR22 - Interrupt Routing Device 22

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR22: [ILB_BASE_ADDRESS] + 4Ch

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD		IRC		IRA

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.38 IR23—Offset 4Eh

IR23 - Interrupt Routing Device 23

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR23: [ILB_BASE_ADDRESS] + 4Eh

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD		IRC		IRA

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H



Bit Range	Default & Access	Description
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.39 IR24—Offset 50h

IR24 - Interrupt Routing Device 24

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR24: [ILB_BASE_ADDRESS] + 50h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
IRD	IRC	IRB	IRA	

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.40 IR25—Offset 52h

IR25 - Interrupt Routing Device 25

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR25: [ILB_BASE_ADDRESS] + 52h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
0	0	0	0	0
IRD	IRC	IRB	IRA	



Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD : INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC : INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB : INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA : INTA mapping to IRQ A-H

34.3.41 IR26—Offset 54h

IR26 - Interrupt Routing Device 26

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR26: [ILB_BASE_ADDRESS] + 54h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD	IRC	IRB	IRA	

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD : INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC : INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB : INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA : INTA mapping to IRQ A-H

34.3.42 IR27—Offset 56h

IR27 - Interrupt Routing Device 27

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR27: [ILB_BASE_ADDRESS] + 56h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h





Access Method

IR29: [ILB BASE ADDRESS] + 5Ah

ILB BASE ADDRESS Reference: [B:0, D:31, F:0] + 50h

15	12	8	4	0
0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0	0 0 0 0
IRD	IRC	IRB	IRA	

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.45 IR30—Offset 5Ch

Access Method

IR30: [ILB BASE ADDRESS] + 5Ch

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

15			12			8			4			0			
0	0	0	0	0	0	0	0	0	0	0	0	0			
IRD				IRC				IRB				IRA			

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H



Bit Range	Default & Access	Description
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H

34.3.46 IR31—Offset 5Eh

IR31 - Interrupt Routing Device 31

Access Method

Type: Memory Mapped I/O Register
(Size: 16 bits)

IR31: [ILB_BASE_ADDRESS] + 5Eh

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 0000h

15	12	8	4	0
0	0	0	0	0
IRD		IRC	IRB	IRA

Bit Range	Default & Access	Description
15:12	4'd3 RW	IRD: INTD mapping to IRQ A-H
11:8	4'd2 RW	IRC: INTC mapping to IRQ A-H
7:4	4'd1 RW	IRB: INTB mapping to IRQ A-H
3:0	4'd0 RW	IRA: INTA mapping to IRQ A-H



Other Interrupt Control

Access Method

OIC: [ILB BASE ADDRESS] + 60h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB BASE ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00001100h

Bit Range	Default & Access	Description
31:13	0b RO	RSVD0: Reserved
12	1b RW	SIRQEN: When set, enables the internal SIRQ . when cleared the internal sIRQ is disabled
11:9	0b RO	RSVD1: Reserved
8	1b RW	AEN: When set, enables the internal IOAPIC and its address decode, when cleared the internal IOxAPIC is disabled. software should read this register after modifying the APIC enable prior to acces to IOxAPIC addresss range.
7:0	0b RO	RSVD2: Reserved

34.3.48 RC—Offset 64h

RC - RTC Configuration

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RC: [ILB BASE ADDRESS] + 64h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	0	0
RSVD0									UL	=

Bit Range	Default & Access	Description
31:2	0b RO	RSVD0 : Reserved
1	0b RW/L	UL : Upper 128 Byte Lock (UL): When set, bytes 38h-3Fh in the upper 128 byte bank of RTC RAM are locked. Writes will be dropped and reads will not return any guaranteed data.
0	0b RW/L	LL : Lower 128 Byte Lock (LL): When set, bytes 38h-3Fh in the lower 128 byte bank of RTC RAM are locked. Writes will be dropped and reads will not return any guaranteed data.

34.3.49 BCS - BIOS Control Status (BCS)—Offset 6Ch

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

BCS: [ILB BASE ADDRESS] + 6Ch


ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB BASE ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000002h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0	1	0
RSVD0									SM1WPEN	SM1WPST

Bit Range	Default & Access	Description
31:2	0b RO	RSVD0: Reserved
1	1b RW	SMIWPEN: SMI WP Enable (SMIWPEN): When this bit is set to a 1, it enables the LPC to generate SMI upon not SMM code is trying to set BC.WP from a 0 to a 1 while BC.LE is set.



Bit Range	Default & Access	Description
0	0b RW/1C	SMIWPST: SMI WP Status (SMIWPST): Set when SMI is generated upon trying to set BC.WP from a 0 to a 1 by not SMM code (while BC.LE and SMIWPEN are set). Write a 1 to this bit should clear it and clear the SMI (send DEASSERT_SMI)

34.3.50 LE—Offset 70h

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

LE: [ILB_BASE_ADDRESS] + 70h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000003h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	1
RSVD0								IRQ12C
								IRQ1C

Bit Range	Default & Access	Description
31:2	0b RO	RSVD0: Reserved
1	1b RW	IRQ12_CAUSE (IRQ12C): When software sets the bit to 1, IRQ12 will be high (asserted), When software set bit to 0,IRQ12 will be low (deasserted). default for this bit is 1
0	1b RW	IRQ1_CAUSE (IRQ1C): When software sets the bit to 1, IRQ11 will be high (asserted), When software set bit to 0,IRQ1 will be low (deasserted). default for this bit is 1

34.3.51 NMI (GNMI)—Offset 80h

NMI register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

GNMI: [ILB_BASE_ADDRESS] + 80h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000004h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	1
RSVD0								NMI2SMIEN
								NMI2SMIST
								NMIN
								NMINS
								GNMIED
								GNMIE
								GNMIS



Bit Range	Default & Access	Description
31:7	0b RO	RSVD0: Reserved
6	0b RW	NMI2SMIEN: NMI to SMI Enable (NMI2SMIEN): When set, instead of NMI message SMI message will be sent.
5	0b RO	NMI2SMIST: NMI to SMI bit Status (NMI2SMIST)
4	0b RW/1C	NMIN: NMI NOW (NMIN): When set, NMI message will be sent. Writing 1'b1 to NMI_NOW inverts NMI_NOW and NMI_NOW_STS value
3	0b RO	NMINS: NMI_NOW_STS is a result of the NMI_NOW configuration bit. Writing 1'b1 to NMI_NOW inverts NMI_NOW_STS value. Resulting that the first time NMI_NOW is written sets the NMI_NOW_STS and initiates NMI. Next writing clears the NMI_NOW_STS and allows initiating NMI by the next writing to NMI_NOW
2	1b RW	GNMIED: GPIO NMI Edge Detection (GNMIED): When set, NMI message will be sent on NMI GPIO posedge. when cleared the NMI message will be sent on negedge
1	0b RW	GNMIE: GPIO NMI Enable (GNMIE): When set, NMI message will be sent when NMI GPIO occurred. when cleared the message will not be sent
0	0b RW/1C	GNMS (GNMIS): GPIO NMI Status (GNMIS), when NMI is received from GPIO this bit is set. write '1' to this register to clear the status bit

34.3.52 LPCC—Offset 84h

LPC Control register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

LPCC: [ILB_BASE_ADDRESS] + 84h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
RSVD0						LPCCCLK_SLC	RSVD1	LPCCCLK_force_off CLKRUN_EN LPCCCLK1EN LPCCCLK0EN

Bit Range	Default & Access	Description
31:9	0b RO	RSVD0: Reserved
8	0b RO	LPCCCLK_SLC: iLPCCCLK mux select (0 - ilpcclk0, 1 ilpcclk1) This bit get value from soft strap.
7:4	0b RO	RSVD1: Reserved



Bit Range	Default & Access	Description
3	0b RW	LPCCCLK_force_off: when asserted, oLPCCCLK shut off similarly to CLKRUN protocol while ignoring iCLKRUN (LPC device reactions)
2	0b RW	CLKRUN_EN: LPC CLKRUN protocol enable (when not asserted, oLPCCCLK toggles)
1	0b RO	LPCCCLK1EN: Clock 1 Enable (EN): This bit get value from soft strap. When set, LPC clock 1 is enabled. When cleared, it is disabled.
0	1b RO	LPCCCLK0EN: Clock 0 Enable (EN): When set, LPC clock 0 is enabled. When cleared, it is disabled.

34.3.53 IRQEN (IRQE)—Offset 88h

IRQ Enable Control

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

IRQ: [ILB_BASE_ADDRESS] + 88h

ILB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

ILB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + 50h

Default: 00000000h


31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0							UARTIRQEN	RSVD1

Bit Range	Default & Access	Description
31:5	0b RO	RSVD0: Reserved
4	0b RO	UARTIRQEN: UART IRQ4 Enable
3:0	0b RO	RSVD1: Reserved

35 PCU – iLB – Low Pin Count (LPC) Bridge

The SoC implements an LPC Interface as described in the LPC 1.1 Specification. The Low Pin Count (LPC) bridge function of the SoC resides in PCI Device 31, Function 0.

Note: In addition to the LPC bridge interface function, D31:F0 contains other functional units including interrupt controllers, timers, power management, system management, GPIO, and RTC.



35.1 Signal Descriptions

Please see [Chapter 2, "Physical Interfaces"](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function

Note: If the VGA interfaces is used, VLPC must have a nominal voltage of 3.3V.



Table 322. LPC Signals


Signal Name	Direction Plat. Power	Description
ILB_LPC_AD[3:0]	I/O VLPC	LPC Multiplexed Command, Address, Data: Internal pull-ups are provided for these signals. <i>These signals are muxed and may be used by other functions.</i>
ILB_LPC_CLK[0]	O VLPC	LPC Clock [0] Out: 33 MHz PCI-like clock driven to LPC peripherals. <i>These signals are muxed and may be used by other functions.</i>
ILB_LPC_CLK[1]	O or I VLPC	LPC Clock [1] Out: 33 MHz PCI-like clock driven to LPC peripherals. Can be configured as an input to compensate for board routing delays through Soft Strap. <i>These signals are muxed and may be used by other functions.</i>
ILB_LPC_CLKRUN#	I/OD VLPC	LPC Clock Run: Input to determine the status of ILB_LPC_CLK and an open drain output used to request starting or speeding up ILB_LPC_CLK. This is a sustained tri-state signal used by the central resource to request permission to stop or slow ILB_LPC_CLK. The central resource is responsible for maintaining the signal in the asserted state when ILB_LPC_CLK is running and deasserts the signal to request permission to stop or slow ILB_LPC_CLK. An internal pull-up is provided for this signal. <i>This signal is muxed and may be used by other functions.</i>
ILB_LPC_FRAME#	O VLPC	LPC Frame: This signal indicates the start of an LPC cycle, or an abort. <i>This signal is muxed and may be used by other functions.</i>
ILB_LPC_SERIRQ	I/O V1P8S	Serial Interrupt Request: This signal implements the serial interrupt protocol. <i>This signal is muxed and may be used by other functions.</i>

35.2 Features

The LPC interface to the SoC is shown in [Figure 135](#). Note that the SoC implements all of the signals that are shown as optional, but peripherals are not required to do so.

Note: The LPC controller does not implement bus mastering cycles or DMA.

Note: The LPC controller is the subtractive agent of the Intel Legacy Block. All transactions not claimed elsewhere are sent to the LPC controller.

Figure 135.LPC Interface Diagram**NOTES:**

1. The General Purpose Input (GPI) must use a SMI capable GPIO: GPIO_S0_SC[7:0].

35.2.1 Memory Cycle Notes

For cycles below 16M, the LPC Controller will perform standard LPC memory cycles. For cycles targeting firmware (BIOS/EFI code only), firmware memory cycles are used. Only 8-bit transfers are performed. If a larger transfer appears, the LPC controller will break it into multiple 8-bit transfers until the request is satisfied.

If the cycle is not claimed by any peripheral (and subsequently aborted), the LPC Controller will return a value of all 1's to the CPU.

35.2.2 Trusted Platform Module (TPM) 1.2 Support

The LPC interface supports accessing Trusted Platform Module (TPM) 1.2 and 2.0 devices via the LPC TPM START encoding. Memory addresses within the range FED40000h to FED40FFFh will be accepted by the LPC Bridge and sent on LPC as TPM special cycles. No additional checking of the memory cycle is performed.

Note: This is different to the FED00000h to FED4BFFFh range implemented on some other Intel components since no Intel® Trusted Execution Technology (Intel® TXT) transactions are supported.

35.2.3 FWH Cycle Notes

If the LPC controller receives any SYNC returned from the device other than short (0101), long wait (0110), or ready (0000) when running a FWH cycle, indeterminate results may occur. A FWH device is not allowed to assert an Error SYNC.

BIOS/EFI boot from LPC is not supported when Secure Boot is enabled.



35.2.4 Other Notes

All cycles that are not decoded internally, and are not targeted for LPC (i.e. configuration cycles and IO cycles above 64kb) will be sent to LPC with ILB_LPC_FRAME# not asserted. Memory cycles above 16 MB that are not decoded internally, and are not targeted for LPC will be sent to LPC with ILB_LPC_FRAME# asserted.

35.2.5 POST Code Redirection

Writes to addresses 80h - 8Fh in IO register space will also be passed to the LPC bus.

Note: Reads of these addresses do not result in any LPC transactions.

35.2.6 Power Management

35.2.6.1 LPCPD# Protocol


Same timings as for PMC_SUS_STAT#. After driving PMC_SUS_STAT# active, the SoC drives ILB_LPC_FRAME# low, and tri-states (or drives low) ILB_LPC_AD[3:0].

Note: The Low Pin Count Interface Specification, Revision 1.1 defines the LPCPD# protocol where there is at least 30 μ s from LPCPD# assertion to LRST# assertion. This specification explicitly states that this protocol only applies to entry/exit of low power states which does not include asynchronous reset events. The SoC asserts both PMC_SUS_STAT# (connects to LPCPD#) and ILB_PLTRST# (connects to LRST#) at the same time during a global reset. This is not inconsistent with the LPC LPCPD# protocol.

35.2.6.2 Clock Run (CLKRUN)

When there are no pending LPC cycles, and SERIRQ is in quiet mode, the SoC can shut down the LPC clock. The SoC indicates that the LPC clock is going to shut down by de-asserting the ILB_LPC_CLKRUN# signal. LPC devices that require the clock to stay running should drive ILB_LPC_CLKRUN# low within 4 clocks of its de-assertion. If no device drives the signal low within 4 clocks, the LPC clock will stop. If a device asserts ILB_LPC_CLKRUN#, the SoC will start the LPC clock and assert ILB_LPC_CLKRUN#.

Note: The CLKRUN protocol is disabled by default. See [Section 35.3.2.2, "Clock Run Enable" on page 4534](#) for further details.



35.2.7 Serialized IRQ (SERIRQ)

35.2.7.1 Overview

The interrupt controller supports a serial IRQ scheme. The signal used to transmit this information is shared between the interrupt controller and all peripherals that support serial interrupts. The signal line, ILB_LPC_SERIRQ, is synchronous to LPC clock, and follows the sustained tri-state protocol that is used by LPC signals. The serial IRQ protocol defines this sustained tri-state signaling in the following fashion:

- **S - Sample Phase:** Signal driven low
- **R - Recovery Phase:** Signal driven high
- **T - Turn-around Phase:** Signal released

The interrupt controller supports 21 serial interrupts. These represent the 15 ISA interrupts (IRQ0- 1, 3-15), the four PCI interrupts, and the control signals SMI# and IOCHK#. Serial interrupt information is transferred using three types of frames:

- **Start Frame:** ILB_LPC_SERIRQ line driven low by the interrupt controller to indicate the start of IRQ transmission
- **Data Frames:** IRQ information transmitted by peripherals. The interrupt controller supports 21 data frames.
- **Stop Frame:** ILB_LPC_SERIRQ line driven low by the interrupt controller to indicate end of transmission and next mode of operation.

35.2.7.2 Start Frame

The serial IRQ protocol has two modes of operation which affect the start frame:

- **Continuous Mode:** The interrupt controller is solely responsible for generating the start frame
- **Quiet Mode:** Peripheral initiates the start frame, and the interrupt controller completes it.

These modes are entered via the length of the stop frame.

Continuous mode must be entered first, to start the first frame. This start frame width is 8 LPC clocks. This is a polling mode.

In Quiet mode, the ILB_LPC_SERIRQ line remains inactive and pulled up between the Stop and Start Frame until a peripheral drives ILB_LPC_SERIRQ low. The interrupt controller senses the line low and drives it low for the remainder of the Start Frame. Since the first LPC clock of the start frame was driven by the peripheral, the interrupt controller drives ILB_LPC_SERIRQ low for 1 LPC clock less than in continuous mode. This mode of operation allows for lower power operation.



35.2.7.3 Data Frames

Once the Start frame has been initiated, the ILB_LPC_SERIRQ peripherals start counting frames based on the rising edge of ILB_LPC_SERIRQ. Each of the IRQ/DATA frames has exactly 3 phases of 1 clock each:

- **Sample Phase:** During this phase, a device drives ILB_LPC_SERIRQ low if its corresponding interrupt signal is low. If its corresponding interrupt is high, then the ILB_LPC_SERIRQ devices tri-state ILB_LPC_SERIRQ. ILB_LPC_SERIRQ remains high due to pull-up resistors.
- **Recovery Phase:** During this phase, a device drives ILB_LPC_SERIRQ high if it was driven low during the Sample Phase. If it was not driven during the sample phase, it remains tri-stated in this phase.
- **Turn-around Phase:** The device tri-states ILB_LPC_SERIRQ.

35.2.7.4 Stop Frame

After the data frames, a Stop Frame will be driven by the interrupt controller. ILB_LPC_SERIRQ will be driven low for two or three LPC clocks. The number of clocks is determined by the SCNT.MD register bit. The number of clocks determines the next mode, as indicated in [Table 323](#).

Table 323. SERIRQ, Stop Frame Width to Operation Mode Mapping

Stop Frame Width	Next Mode
Two LPC clocks	Quiet Mode: Any SERIRQ device initiates a Start Frame
Three LPC clocks	Continuous Mode: Only the interrupt controller initiates a Start Frame

35.2.7.5 Serial Interrupts Not Supported


There are four interrupts on the serial stream which are not supported by the interrupt controller. These interrupts are:

- IRQ0: Heartbeat interrupt generated off of the internal 8254 counter 0.
- IRQ8: RTC interrupt can only be generated internally.
- IRQ13: This interrupt (floating point error) is not supported.
- IRQ14: Interrupt can only be generated by the SATA controller in Legacy mode.

The interrupt controller will ignore the state of these interrupts in the stream.

35.2.7.6 Data Frame Format and Issues

Table below shows the format of the data frames. The decoded INT[A:D]# values are ANDed with the corresponding PCI-express input signals (PIRQ[A:D]#). This way, the interrupt can be shared.



The other interrupts decoded via SERIRQ are also ANDed with the corresponding internal interrupts. For example, if IRQ10 is set to be used as the SCI, then it is ANDed with the decoded value for IRQ10 from the SERIRQ stream.

Table 324. SERIRQ Interrupt Mapping

Data Frame #	Interrupt	Clocks Past Start Frame	Comment
1	IRQ0	2	Ignored. Can only be generated via the internal 8524
2	IRQ1	5	Before port 60h latch
3	SMI#	8	Causes SMI# if low. Sets SMI_STS.ILB_SMI_STS register bit.
4	IRQ3	11	
5	IRQ4	14	
6	IRQ5	17	
7	IRQ6	20	
8	IRQ7	23	
9	IRQ8	26	Ignored. IRQ8# can only be generated internally
10	IRQ9	29	
11	IRQ10	32	
12	IRQ11	35	
13	IRQ12	38	Before port 60h latch
14	IRQ13	41	Ignored
15	IRQ14	44	Ignored
16	IRQ15	47	
17	IOCHCK#	50	Same as ISA IOCHCK# going active.
18	PCI INTA#	53	
19	PCI INTB#	56	
20	PCI INTC#	59	
21	PCI INTD#	62	

35.3 Use

35.3.1 LPC Clock Delay Compensation

In order to meet LPC interface AC timing requirements, a LPC clock loop back is required. The operation of this loop back can be configured in two ways:

1. On the SOC: In this configuration, ILB_LPC_CLK[0] is looped back on itself on the SOC pad.

a. Benefit:

ILB_LPC_CLK[0] and ILB_LPC_CLK[1] are both available for system clocking



b. Drawback:

Clock delay compensation is less effective at compensating for mainboard delay

c. Soft Strap & Register Requirements:

Soft Strap LPCCLK_SLC = 0b

Configuration is reflected by register bit LPCC.LPCCLK_SLC=0b

Soft Strap LPCCLK1_ENB = 0b (ILB_LPC_CLK[1] disabled) or 1b (ILB_LPC_CLK[1] enabled)

2. Configuration is reflected by register bit LPCC.LPCCLK1EN=0b (ILB_LPC_CLK[1] disabled) or 1b (ILB_LPC_CLK[1] enabled)

3. On the main board: In this configuration, ILB_LPC_CLK[0] is looped back to ILB_LPC_CLK[1] on the main board.

a. Benefit:

Clock delay compensation is more effective at compensating for main board delay

b. Drawback:

Only ILB_LPC_CLK[0] is available for system clocking. ILB_LPC_CLK[1] must be disabled.

c. Soft Strap & Register Requirements:

Soft Strap LPCCLK_SLC = 1b

Configuration is reflected by register bit LPCC.LPCCLK_SLC=1b

Soft Strap LPCCLK1_ENB = 0b (ILB_LPC_CLK[1] disabled)

Configuration is reflected by register bit LPCC.LPCCLK1EN=0b

35.3.2 LPC Power Management

35.3.2.1 Clock Enabling


The LPC clocks can be enabled or disabled by setting or clearing, respectively, the LPCC.LPCCLK[1:0]EN bits.

35.3.2.2 Clock Run Enable

The Clock Run protocol is disabled by default and should only be enabled once all LPC devices have been initialized. The Clock Run protocol is enabled by setting the LPCC.CLKRUN_EN register bit.

35.3.3 SERIRQ Disable

Serialized IRQ support may be disabled by setting the OIC.SIRQEN bit to 0b.




35.4 References

- Low Pin Count Interface Specification, Revision 1.1 (LPC): <http://www.intel.com/design/chipsets/industry/lpc.htm>
- Serialized IRQ Support for PCI Systems, Revision 6.0: http://www.smsc.com/media/Downloads_Public/papers/serirq60.doc
- Implementing Industry Standard Architecture (ISA) with Intel® Express Chipsets (318244): <http://www.intel.com/assets/pdf/whitepaper/318244.pdf>

35.5 Register Map

Refer to [Chapter 3, “Register Access Methods”](#) and [Chapter 4, “Mapping Address Spaces”](#) for additional information.

Figure 136. PCU – iLB – LPC Register Map





35.6 PCU iLB Low Pin Count (LPC) Bridge PCI Configuration Registers

Table 325. Summary of PCU iLB Low Pin Count (LPC) Bridge PCI Configuration Registers—0/31/0

Offset	Size	Register ID—Description	Default Value
0h	4	"Identifiers Register (PCIE_REG_Identifiers)—Offset 0h" on page 4538	00008086h
4h	2	"Command (PCIE_REG_COMMAND)—Offset 4h" on page 4538	0007h
6h	2	"Status (PCIE_REG_STATUS)—Offset 6h" on page 4539	0210h
8h	4	"Revision ID and Class Code (PCIE_REG_REVISION_ID_CLASS_CODE)—Offset 8h" on page 4540	06010000h
Dh	1	"Master Latency Timer (PCIE_REG_MASTER_LAT_TIMER)—Offset Dh" on page 4541	00h
Eh	1	"Header Type (PCIE_REG_HEADER_TYPE)—Offset Eh" on page 4541	80h
2Ch	4	"Subsystem ID and Vendor ID (PCIE_REG_SUBSYS_VENDOR_ID)—Offset 2Ch" on page 4542	00000000h
34h	4	"Capability List Pointer (PCIE_REG_CAP_POINTER)—Offset 34h" on page 4543	000000E0h
40h	4	"ABASE (ACPI_BASE_ADDRESS)—Offset 40h" on page 4543	00000001h
44h	4	"PBASE (PMC_BASE_ADDRESS)—Offset 44h" on page 4544	00000000h
48h	4	"GBASE (GPIO_BASE_ADDRESS)—Offset 48h" on page 4544	00000001h
4Ch	4	"IOBASE (IO_CONTROLLER_BASE_ADDRESS)—Offset 4Ch" on page 4545	00000000h
50h	4	"IBASE (ILB_BASE_ADDRESS)—Offset 50h" on page 4546	00000000h
54h	4	"SBASE (SPI_BASE_ADDRESS)—Offset 54h" on page 4547	00000000h
58h	4	"MPBASE (MPHY_BASE_ADDRESS)—Offset 58h" on page 4547	00000000h
5Ch	4	"PUBASE (PUNIT_BASE_ADDRESS)—Offset 5Ch" on page 4548	00000000h
80h	4	"UART Control (UART_CONT)—Offset 80h" on page 4549	00000000h
D8h	2	"BIOS Decode Enable (PCIE_REG_BIOS_DECODE_EN)—Offset D8h" on page 4549	FFCFh
E0h	2	"FDCAP (Feature_Detection_Capability_ID)—Offset E0h" on page 4551	0009h
E2h	1	"FDLEN (Feature_Detection_Capability_Length)—Offset E2h" on page 4551	0Ch
E3h	1	"FDVER (Feature_Detection_Version_Register)—Offset E3h" on page 4552	10h
E4h	4	"FVECTIDX (Feature_Vector_Index)—Offset E4h" on page 4552	00000000h
E8h	4	"FVECTD (Feature_Vector_Data)—Offset E8h" on page 4553	00000000h
F0h	4	"RCBA (RCRB_BASE_ADDRESS)—Offset F0h" on page 4553	00000000h
F8h	4	"Manufacturer ID (PCIE_REG_MANUFACTURER_ID) - Offset F8h" on page 4553	01xx0F1A



Bit Range	Default & Access	Description
7	0b RO	Wait Cycle Control (WCC): Reserved as '0' per PCI-Express spec
6	0b RW	Parity Error Response Enable (PERE): This bit controls the device's response to parity errors. When the bit is set, the device must take its normal action when a parity error is detected. When the bit is 0, the device sets its Detected Parity Error status bit (bit 15 in the Status register) when an error is detected, but does not assert PERR# and continues normal operation.
5	0b RO	VGA Palette Snoop (VGA_PSE): This bit controls how VGA compatible and graphics devices handle accesses to VGA palette registers. When this bit is 1, palette snooping is enabled (i.e., the device does not respond to palette register writes and snoops the data). When the bit is 0, the device should treat palette write accesses like all other accesses. Reserved as '0' per PCI-Express spec
4	0b RO	Memory Write and Invalidate Enable (MWIE): This is an enable bit for using the Memory Write and Invalidate command. When this bit is 1, masters may generate the command. When it is 0, Memory Write must be used instead. Reserved as '0' per PCI-Express spec
3	0b RO	Special Cycle Enable (SCE): Controls a device's action on Special Cycle operations. A value of 0 causes the device to ignore all Special Cycle operations. A value of 1 allows the device to monitor Special Cycle operations. Reserved as '0' per PCI-Express spec
2	1b RO	Bus Master Enable (BME): Controls a device's ability to act as a master on the PCI bus. A value of 0 disables the device from generating PCI accesses. A value of 1 allows the device to behave as a bus master. Bus master cannot be disabled on LPC
1	1b RO	Memory Space Enable (MSE): Controls a device's response to Memory Space accesses. A value of 0 disables the device response. A value of 1 allows the device to respond to Memory Space accesses. Memory space cannot be disable on LPC
0	1b RO	I/O Space Enable (IOSE): Controls a device's response to I/O Space accesses. A value of 0 disables the device response. A value of 1 allows the device to respond to I/O Space accesses. I/O space cannot be disable on LPC

35.6.3 Status (PCIE_REG_STATUS)—Offset 6h

The Status register is used to record status information for PCI bus related events. Reads to this register behave normally. Writes are slightly different in that bits can be reset, but not set. A one bit is reset (if it is not read-only) whenever the register is written, and the write data in the corresponding bit location is a 1. For instance, to clear bit 14 and not affect any other bits, write the value 0100_0000_0000_0000b to the register.

Access Method


Type: PCI Configuration Register
(Size: 16 bits)

PCIE_REG_STATUS: [B:0, D:31, F:0] + 6h

Default: 0210h

15	12	8	4	0
0	0	0	0	0
0	0	1	0	0
0	0	0	1	0
0	0	0	0	0
DPE	SSE	RMA	RTA	STA
				DTS
				DPD
				FBC
				RSVD0
				C66
				CLIST
				IS
				RSVD1

Bit Range	Default & Access	Description
15	0b RW	Detected Parity Error (DPE): This bit must be set by the device whenever it detects a parity error, even if parity error handling is disabled (as controlled by bit 6 in the Command register).



Bit Range	Default & Access	Description
14	0b RW	Signaled System Error (SSE): This bit must be set whenever the device asserts SERR#. Set when the LPC bridge signals a system error to the internal SERR# logic.
13	0b RW	Received Master Abort (RMA): This bit must be set by a master device whenever its transaction (except for Special Cycle) is terminated with Master-Abort. All master devices must implement this bit.
12	0b RW	Received Target Abort (RTA): This bit must be set by a master device whenever its transaction is terminated with Target-Abort. All master devices must implement this bit.
11	0b RW	Signaled Target Abort (STA): This bit must be set by a target device whenever it terminates a transaction with Target-Abort. Devices that will never signal Target- Abort do not need to implement this bit.
10:9	01b RO	DEVSEL# Timing Status (DTS): These bits encode the timing of DEVSEL#. These are encoded as 00b for fast, 01b for medium, and 10b for slow (11b is reserved). These bits Indicate medium timing, although this has no meaning on the backbone
8	0b RW	Data Parity Error Detected (DPD): This bit is only implemented by bus masters. It is set when three conditions are met: 1) the bus agent asserted PERR# itself (on a read) or observed PERR# asserted (on a write); 2) the agent setting the bit acted as the bus master for the operation in which the error occurred; and 3) the Parity Error Response bit (Command register) is set.
7	0b RO	Fast Back to Back Capable (FBC): This optional read-only bit indicates whether or not the target is capable of accepting fast back-to-back transactions when the transactions are not to the same agent. This bit can be set to 1 if the device can accept these transactions and must be set to 0 otherwise. This bit has no meaning on internal backbone.
6	0b RO	RSVD0: Reserved
5	0b RO	66 MHz Capable (C66): This optional read-only bit indicates whether or not this device is capable of running at 66 MHz. A value of zero indicates 33 MHz. A value of 1 indicates that the device is 66 MHz capable. This bit has no meaning on internal backbone
4	1b RO	Capabilities List (CLIST): This optional read-only bit indicates whether or not this device implements the pointer for a New Capabilities linked list at offset 34h. A value of zero indicates that no New Capabilities linked list is available. A value of one indicates that the value read at offset 34h is a pointer in Configuration Space to a linked list of new capabilities. There is a capabilities list in the LPC bridge.
3	0b RO	Interrupt Status (IS): This read-only bit reflects the state of the interrupt in the device/function. Only when the Interrupt Disable bit in the command register is a 0 and this Interrupt Status bit is a 1, will the device's/function's INTx# signal be asserted. Setting the Interrupt Disable bit to a 1 has no effect on the state of this bit. The LPC bridge does not generate interrupts
2:0	0b RO	RSVD1: Reserved

35.6.4 Revision ID and Class Code (PCIE_REG_REVISION_ID_CLASS_CODE)—Offset 8h

This register is a combination of two registers the Revision ID register and the Class Code register. The revision ID register specifies a device specific revision identifier. The value is chosen by the vendor. Zero is an acceptable value. The Class Code register is read-only and is used to identify the generic function of the device and, in some cases, a specific registerlevel programming interface.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCIE_REG_REVISION_ID_CLASS_CODE: [B:0, D:31, F:0] + 8h

Default: 06010000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	1	1	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BCC				SCC				Pi
								RIS

Bit Range	Default & Access	Description
31:24	06h RO	Base Class Code (BCC): This field is a base class code which broadly classifies the type of function the device performs. Indicates the device is a bridge device.
23:16	01h RO	Sub-Class Code (SCC): This field is a sub-class code which identifies more specifically the function of the device. Indicates the device a PCI to ISA bridge
15:8	00h RO	Programming Interface (PI): This field identifies a specific register-level programming interface if any) so that device independent software can interact with the device. The LPC bridge has no programming interface.
7:0	X RO	Revision ID (RIS): This register specifies a device specific revision identifier. The value is chosen by the vendor. Zero is an acceptable value. This field should be viewed as a vendor defined extension to the Device ID. This field is controlled by the LPC RID fuses. Coming from the SETIDVALUE message Revision ID field

35.6.5 Master Latency Timer (PCIE_REG_MASTER_LAT_TIMER)—Offset Dh

This register specifies, in units of PCI bus clocks, the value of the Latency Timer for this PCI bus master. This register is implemented as read-only, the register must be initialized to 0.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

PCIE_REG_MASTER_LAT_TIMER: [B:0, D:31, F:0] + Dh

Default: 00h

7	4	0
0	0	0
0	0	0
MLC		RSVD0

Bit Range	Default & Access	Description
7:3	00h RO	Master Latency Count (MLC): Reserved per PCIe spec.
2:0	0b RO	RSVD0: Reserved


35.6.6 Header Type (PCIE_REG_HEADER_TYPE)—Offset Eh

This byte identifies the layout of the second part of the predefined header (beginning at byte 10h in Configuration Space) and also whether or not the device contains multiple functions.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

PCIE_REG_HEADER_TYPE: [B:0, D:31, F:0] + Eh



Default: 80h

7	4	0
1	0	0
MFD	HTYPE	

Bit Range	Default & Access	Description
7	1b RO	Multi-function Device (MFD): This field is used to identify a multi-function device. If the bit is 0, then the device is single function. If the bit is 1, then the device has multiple functions.
6:0	00h RO	Header Type (HTYPE): This field identifies the layout of the second part of the predefined header. The encoding 00h specifies the standard layout.

35.6.7 Subsystem ID and Vendor ID (PCIE_REG_SUBSYS_VENDOR_ID)—Offset 2Ch

This register is used to uniquely identify the add-in card or subsystem where the PCI device resides. It provides a mechanism for add-in card vendors to distinguish their add-in cards from one another even though the add-in cards may have the same PCI controller on them (and, therefore, the same Vendor ID and Device ID). Implementation of this register is required for all PCI devices except those that have a base class 6 with sub class 0-4 (0, 1, 2, 3, 4), or a base class 8 with sub class 0-3 (0, 1, 2, 3). Subsystem Vendor IDs can be obtained from the PCI SIG and are used to identify the vendor of the add-in card or subsystem. Values for the Subsystem ID are vendor specific. Values in these registers must be loaded and valid prior to the system firmware or any system software accessing the PCI Configuration Space. How these values are loaded is not specified but could be done during the manufacturing process or loaded from external logic (e.g., strapping options, serial ROMs, etc.). These values must not be loaded using expansion ROM software because expansion ROM software is not guaranteed to be run during POST in all systems. Devices are responsible for guaranteeing the data is valid before allowing reads to these registers to complete. This can be done by responding to any accesses with Retry until the data is valid. If a device is designed to be used exclusively on the system board, the system vendor may use system specific software to initialize these registers after each power-on. This register can be written only once after PMU_PLTRST_B de-assertion.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCIE_REG_SUBSYS_VENDOR_ID: [B:0, D:31, F:0] + 2Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
SSID	SSVID							

Bit Range	Default & Access	Description
31:16	0000h RW	Subsystem ID (SSID): This is written by BIOS. No hardware action taken on this value. This field could be written only once.
15:0	0000h RW	Subsystem Vendor ID (SSVID): This is written by BIOS. No hardware action taken on this value. This field could be written only once.



35.6.8 Capability List Pointer (PCIE_REG_CAP_POINTER)—Offset 34h

This optional register is used to point to a linked list of new capabilities implemented by this device. This register is only valid if the Capabilities List bit in the Status Register is set. If implemented, the bottom two bits are reserved and should be set to 00b. Software should mask these bits off before using this register as a pointer in Configuration Space to the first entry of a linked list of new capabilities.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PCIE_REG_CAP_POINTER: [B:0, D:31, F:0] + 34h

Default: 000000E0h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	1	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							CP	

Bit Range	Default & Access	Description
31:8	0b RO	RSVD0: Reserved
7:0	E0h RO	Capability Pointer (CP): Indicates the offset of the first Capability Item.

35.6.9 ABASE (ACPI_BASE_ADDRESS)—Offset 40h

ACPI is mapped into I/O space. It is used by the PMC. Base Address registers that map into I/O Space are always 32 bits wide with bit 0 hardwired to a 1. Bit 1 is used to enable IO range pointed by this base address. Bits 31:16 are reserved and must return 0 on reads and the other bits could be used to map the device into I/O Space.

Access Method


Type: PCI Configuration Register
(Size: 32 bits)

ACPI_BASE_ADDRESS: [B:0, D:31, F:0] + 40h

Default: 00000001h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	1
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD0							BA	EN
							RSVD1	MEMI

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:7	000h RW	Base Address (BA): Provides the 128 bytes of I/O space for ACPI and TCO logic
6:2	0b RO	RSVD1: Reserved



Bit Range	Default & Access	Description
1	0b RW	Enable (EN): When set, decode of the IO range pointed to by the ABASE is enabled.
0	1b RO	Memory Space Indication (MEMI): This read-only bit always is 1, indicating that this BAR is IO mapped

35.6.10 PBASE (PMC_BASE_ADDRESS)—Offset 44h

PMC registers are mapped into memory space. It is used by the PMC. Base Address registers that map into Memory Space are always 32 bits wide bit 0 hardwired to a 0. Bit 1 is used to enable memory range pointed by this base address. For Memory Base Address registers, bit 2 indicates if base address could be on 64 bit space or only on 32 bit space. Bit 3 should be set to 1 if the data is prefetchable and reset to 0 otherwise

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PMC_BASE_ADDRESS: [B:0, D:31, F:0] + 44h

Default: 00000000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0		
BA						RSVD0	PREF	ADDRNG	EN	MEMI

Bit Range	Default & Access	Description
31:9	000000h RW	Base Address (BA): Provides 512 byte system memory base address for the PMC logic
8:4	0b RO	RSVD0: Reserved
3	0b RO	Prefetchable (PREF): Hardwired to 0. Indicated that this BAR is not prefetchable. Set to one, only if there are no side effects on reads, the device returns all bytes on reads regardless of the byte enables, and host bridges can merge processor writes into this range without causing errors.
2	0b RO	Address Range (ADDRNG): If set indicates that this BAR can be located in 64 bit address space, if clear indicates that this BAR can be located only in 32 bit address space.
1	0b RW	Enable (EN): When set, decode of the memory range pointed to by the PBASE is enabled.
0	0b RO	Memory Space Indication (MEMI): This read-only bit always is 0, indicating that this BAR is memory mapped

35.6.11 GBASE (GPIO_BASE_ADDRESS)—Offset 48h

GPIO registers are mapped into I/O space. It is used by the Proxy agent (to IO controllers). Base Address registers that map into I/O Space are always 32 bits wide with bit 0 hardwired to a 1. Bit 1 is used to enable IO range pointed by this base address. Bits 31:16 are reserved and must return 0 on reads and the other bits could be used to map the device into I/O Space.

Access Method



Type: PCI Configuration Register
(Size: 32 bits)

GPIO_BASE_ADDRESS: [B:0, D:31, F:0] + 48h

Default: 00000001h

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	1	
RSVD0				BA				EN	MEMT

Bit Range	Default & Access	Description
31:16	0b RO	RSVD0: Reserved
15:8	00h RW	Base Address (BA): Provides the 256 bytes of I/O space for GPIO logic
7:2	0b RO	RSVD1: Reserved
1	0b RW	Enable (EN): When set, decode of the IO range pointed to by the GBASE is enabled.
0	1b RO	Memory Space Indication (MEMI): This read-only bit always is 1, indicating that this BAR is IO mapped

35.6.12 IOBASE (IO_CONTROLLER_BASE_ADDRESS)—Offset 4Ch

IO Controllers registers are mapped into memory space. It is used by the Proxy agent (to IO controllers). Base Address registers that map into Memory Space are always 32 bits wide bit 0 hardwired to a 0. Bit 1 is used to enable memory range pointed by this base address. For Memory Base Address registers, bit 2 indicates if base address could be on 64 bit space or only on 32 bit space. Bit 3 should be set to 1 if the data is prefetchable and reset to 0 otherwise

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

IO_CONTROLLER_BASE_ADDRESS: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31		28		24		20		16		12		8		4		0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
BA										RSVD0						PREF	ADDRNG	EN	MEMT

Bit Range	Default & Access	Description
31:14	00000h RW	Base Address (BA): Provides 8K byte system memory base address for the IO controllers logic
13:4	0b RO	RSVD0: Reserved



35.6.14 SBASE (SPI_BASE_ADDRESS)—Offset 54h

SPI registers are mapped into memory space. It is used by the SPI. Base Address registers that map into Memory Space are always 32 bits wide bit 0 hardwired to a 0. Bit 1 is used to enable memory range pointed by this base address. For Memory Base Address registers, bit 2 indicates if base address could be on 64 bit space or only on 32 bit space. Bit 3 should be set to 1 if the data is prefetchable and reset to 0 otherwise

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

SPI_BASE_ADDRESS: [B:0, D:31, F:0] + 54h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BA							RSVD0	PREF ADDRNG EN MEMI

Bit Range	Default & Access	Description
31:9	000000h RW	Base Address (BA): Provides 512 byte system memory base address for the SPI logic
8:4	0b RO	RSVD0: Reserved
3	0b RO	Prefetchable (PREF): Hardwired to 0. Indicated that this BAR is not prefetchable. Set to one, only if there are no side effects on reads, the device returns all bytes on reads regardless of the byte enables, and host bridges can merge processor writes into this range without causing errors.
2	0b RO	Address Range (ADDRNG): If set indicates that this BAR can be located in 64 bit address space, if clear indicates that this BAR can be located only in 32 bit address space.
1	0b RW	Enable (EN): When set, decode of the memory range pointed to by the SBASE is enabled.
0	0b RO	Memory Space Indication (MEMI): This read-only bit always is 0, indicating that this BAR is memory mapped

35.6.15 MPBASE (MPHY_BASE_ADDRESS)—Offset 58h

M-phys registers are mapped into memory space. It is used by the Proxy agent (to M-phys). Base Address registers that map into Memory Space are always 32 bits wide bit 0 hardwired to a 0. Bit 1 is used to enable memory range pointed by this base address. For Memory Base Address registers, bit 2 indicates if base address could be on 64 bit space or only on 32 bit space. Bit 3 should be set to 1 if the data is prefetchable and reset to 0 otherwise

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

MPHY_BASE_ADDRESS: [B:0, D:31, F:0] + 58h

Default: 00000000h



31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BA				RSVD0				PREF
								ADDRNG
								EN
								MEMI

Bit Range	Default & Access	Description
31:20	000h RW	Base Address (BA): Provides 1M byte system memory base address for the M phys logic
19:4	0b RO	RSVD0: Reserved
3	0b RO	Prefetchable (PREF): Hardwired to 0. Indicated that this BAR is not prefetchable. Set to one, only if there are no side effects on reads, the device returns all bytes on reads regardless of the byte enables, and host bridges can merge processor writes into this range without causing errors.
2	0b RO	Address Range (ADDRNG): If set indicates that this BAR can be located in 64 bit address space, if clear indicates that this BAR can be located only in 32 bit address space.
1	0b RW	Enable (EN): When set, decode of the memory range pointed to by the MPBASE is enabled.
0	0b RO	Memory Space Indication (MEMI): This read-only bit always is 0, indicating that this BAR is memory mapped

35.6.16 PUBASE (PUNIT_BASE_ADDRESS)—Offset 5Ch

P-Unit registers are mapped into memory space. It is used by the Proxy agent (to P-Unit). Base Address registers that map into Memory Space are always 32 bits wide bit 0 hardwired to a 0. Bit 1 is used to enable memory range pointed by this base address. For Memory Base Address registers, bit 2 indicates if base address could be on 64 bit space or only on 32 bit space. Bit 3 should be set to 1 if the data is prefetchable and reset to 0 otherwise

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

PUNIT_BASE_ADDRESS: [B:0, D:31, F:0] + 5Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
BA				RSVD0				PREF
								ADDRNG
								EN
								MEMI

Bit Range	Default & Access	Description
31:11	00000h RW	Base Address (BA): Provides 2K byte system memory base address for the P-Unit registers
10:4	0b RO	RSVD0: Reserved



Bit Range	Default & Access	Description
3	0b RO	Prefetchable (PREF): Hardwired to 0. Indicated that this BAR is not prefetchable. Set to one, only if there are no side effects on reads, the device returns all bytes on reads regardless of the byte enables, and host bridges can merge processor writes into this range without causing errors.
2	0b RO	Address Range (ADDRNG): If set indicates that this BAR can be located in 64 bit address space, if clear indicates that this BAR can be located only in 32 bit address space.
1	0b RW	Enable (EN): When set, decode of the memory range pointed to by the PUBASE is enabled.
0	0b RO	Memory Space Indication (MEMI): This read-only bit always is 0, indicating that this BAR is memory mapped

35.6.17 UART Control (UART_CONT)—Offset 80h

Controls the internal PCU UART ports

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

UART_CNT: [B:0, D:31, F:0] + 80h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0								COM1FN

Bit Range	Default & Access	Description
31:1	0b RO	RSVD0: Reserved
0	0b RW	COM1 Enable (COM1EN): When set, enables the internal PCU COM1 UART port.

35.6.18 BIOS Decode Enable (PCIE_REG_BIOS_DECODE_EN)—Offset D8h

This register enables ranges in the BIOS for decoding purposes. Note that this register affects the BIOS decode regardless of whether the BIOS is resident on LPC or SPI. The concept of Feature Space does not apply to SPI-based flash. PCU EP simply decodes these ranges as memory accesses when enabled for the SPI/LPC flash interface.

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

PCIE_REG BIOS DECODE EN: [B:0, D:31, F:0] + D8h

Default: FFCFh



15				12				8				4				0			
1	1	1	1	1	1	1	1	1	1	0	0	1	1	1	1				
EF8	EF0	EE8	EE0	ED8	ED0	EC8	EC0	LFE	LEE	RSVD0		E70	E60	E50	E40				

Bit Range	Default & Access	Description
15	1b RW	F8-FF Enable (EF8): Enables decoding of 512K of the following BIOS range: - Data space: 0xFFF80000 - 0xFFFFFFFF - Feature space: 0xFFB80000 - 0xFFBFFFFF
14	1b RW	F0-F8 Enable (EF0): Enables decoding of 512K of the following BIOS range: - Data space: 0xFFF00000 - 0xFFF7FFFF - Feature space: 0xFFB00000 - 0xFFB7FFFF
13	1b RW	E8-EF Enable (EE8): Enables decoding of 512K of the following BIOS range: - Data space: 0xFFE80000 - 0xFFEFFFFF - Feature space: 0xFFA80000 - 0xFFAFFFFF
12	1b RW	E0-E8 Enable (EE0): Enables decoding of 512K of the following BIOS range: - Data space: 0xFFE00000 - 0xFFE7FFFF - Feature space: 0xFFA00000 - 0xFFA7FFFF
11	1b RW	D8-DF Enable (ED8): Enables decoding of 512K of the following BIOS range: - Data space: 0xFFD80000 - 0xFFDFFFFF - Feature space: 0xFF980000 - 0xFF9FFFFF
10	1b RW	D0-D8 Enable (ED0): Enables decoding of 512K of the following BIOS range: - Data space: 0xFFD00000 - 0xFFD7FFFF - Feature space: 0xFF900000 - 0xFF97FFFF
9	1b RW	C8-CF Enable (EC8): Enables decoding of 512K of the following BIOS range: - Data space: 0xFFC80000h - 0xFFCFFFFF - Feature space: 0xFF880000h - 0xFF8FFFFF
8	1b RW	C0-C8 Enable (EC0): Enables decoding of 512K of the following BIOS range: - Data space: 0xFFC00000 - 0xFFC7FFFF - Feature space: 0xFF800000 - 0xFF87FFFF
7	1b RW	Legacy F Segment Enable (LFE): This enables the decoding of the legacy 64KB range at 0xF0000 - 0xFFFFF
6	1b RW	Legacy E Segment Enable (LEE): This enables the decoding of the legacy 64KB range at 0xE0000 - 0xEFFFF
5:4	0b RO	RSVD0: Reserved
3	1b RW	70-7F Enable (E70): Enables decoding of 1MB of the following BIOS range: - Data space: 0xFF700000 - 0xFF7FFFFF - Feature space: 0xFF300000 - 0xFF3FFFFF
2	1b RW	60-6F Enable (E60): Enables decoding of 1MB of the following BIOS range: - Data space: 0xFF600000 - 0xFF6FFFFF - Feature Space: 0xFF200000 - 0xFF2FFFFF
1	1b RW	50-5F Enable (E50): Enables decoding of 1MB of the following BIOS range: - Data space: 0xFF500000 - 0xFF5FFFFF - Feature space: 0xFF100000 - 0xFF1FFFFF
0	1b RW	40-4F Enable (E40): Enables decoding of 1MB of the following BIOS range: - Data space: 0xFF400000 - 0xFF4FFFFF - Feature Space: 0xFF000000 - 0xFF0FFFFF



35.6.19 FDCAP (Feature_Detection_Capability_ID)—Offset E0h

Feature detection capability ID.

Access Method

Type: PCI Configuration Register
(Size: 16 bits)

Feature_Detection_Capability_ID: [B:0, D:31, F:0] + E0h

Default: 0009h

15	12	8	4	0
0	0	0	0	1
0	0	0	0	0
0	0	0	0	1
NEXT				CAPID

Bit Range	Default & Access	Description
15:8	00h RO	Next Item Pointer (NEXT): Configuration offset of the next Capability Item. 0x00 indicates the last item in the Capability List.
7:0	09h RO	Capability ID (CAPID): Value of 0x09 indicates a Vendor Specific Capability

35.6.20 FDLEN (Feature_Detection_Capability_Length)—Offset E2h

Feature detection capability length.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Feature_Detection_Capability_Length: [B:0, D:31, F:0] + E2h

Default: 0Ch

7	4	0
0	0	0
0	0	0
0	0	0
CAPLEN		

Bit Range	Default & Access	Description
7:0	0Ch RO	Capability Length (CAPLEN): Indicates the length of this Vendor Specific capability, as required by PCI Spec



35.6.21 FDVER (Feature_Detection_Version_Register)—Offset E3h

Feature detection version register.

Access Method

Type: PCI Configuration Register
(Size: 8 bits)

Feature_Detection_Version_Register: [B:0, D:31, F:0] + E3h

Default: 10h

7	4	0
0	0	0
VSCID		CAPVER

Bit Range	Default & Access	Description
7:4	1h RO	Vendor-Specific Capability ID (VSCID): A value of 0x1 in this 4-bit field identifies this Capability as Feature Detection Type. This field allows software to differentiate the Feature Detection Capability from other Vendor-Specific capabilities.
3:0	0h RO	Capability Version (CAPVER): This field indicates the version of the Feature Detection capability

35.6.22 FVECTIDX (Feature_Vector_Index)—Offset E4h

Feature vector index - Reserved

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Feature_Vector_Index: [B:0, D:31, F:0] + E4h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD								

Bit Range	Default & Access	Description
31:0	00000000h RO	RSVD: RSVD



35.6.23 FVECTD (Feature_Vector_Data)—Offset E8h

Feature vector data

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

Feature_Vector_Data: [B:0, D:31, F:0] + E8h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
DATA								

Bit Range	Default & Access	Description
31:0	00000000h RO	Data (DATA): 32-bit data value that is taken from capability feature fuses

35.6.24 RCBA (RCRB_BASE_ADDRESS)—Offset F0h

Root Complex registers are mapped into memory space. It is used by the PCU EP and Proxy engine.

Access Method

Type: PCI Configuration Register
(Size: 32 bits)

RCRB_BASE_ADDRESS: [B:0, D:31, F:0] + F0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
BA						RSVD0		EN

Bit Range	Default & Access	Description
31:10	000000h RW	Base Address (BA): Base Address for the root complex register block decode range. This address is aligned on a 1KB boundary.
9:1	0b RO	RSVD0: Reserved
0	0b RW	Enable (EN): When set, enables the range specified in BA to be claimed as the RCRB.


35.6.25 Manufacturer ID (PCIE_REG_MANUFACTURER_ID) - Offset F8h

Access Method

Type: PCI Configuration Register
(Size: 32 bits)


RCRB_BASE_ADDRESS: [B:0, D:31, F:0] + F8h

Default: 00000000h



31				28				24				20				16				12				8				4				0							
0	0	0	0	0	0	0	1	x	x	x	x	x	x	x	x	0	0	0	0	1	1	1	1	0	0	0	1	1	0	1	0	0							
RSVD								MSID								RSVD1																							

Bit Range	Default & Access	Description
31:24	01h RO	RSVD0: Reserved
23:16	xxh RO	Manufacturing Stepping ID (MSID): This value of this filed depends on the stepping of the processor • B2:0Ah • B3:0Ch • D0:11h • D1:13h
15:0	0F1Ah RO	RSVD1: Reserved



35.7 PCU iLB LPC BIOS Control Memory Mapped I/O Registers

Table 326. Summary of PCU iLB LPC BIOS Control Memory Mapped I/O Registers—RCRB_BASE_ADDRESS

Offset	Size	Register ID—Description	Default Value
0h	4	"GCS (RCRB_GENERAL_CONTROL)—Offset 0h" on page 4555	00000000h

35.7.1 GCS (RCRB_GENERAL_CONTROL)—Offset 0h

General Control and Status - contains BIOS configuration and status

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

RCRB_GENERAL_CONTROL: [RCRB_BASE_ADDRESS] + 0h

RCRB_BASE_ADDRESS Type: PCI Configuration Register (Size: 32 bits)

RCRB_BASE_ADDRESS Reference: [B:0, D:31, F:0] + F0h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD0	BBSize	RSVD1				BBS	RSVD2	TS BILD


Bit Range	Default & Access	Description
31	0b RO	RSVD0: Reserved
30:29	X RO	Boot Block Size (BBSize): This field determines the size of the BIOS boot block. Default is controlled by 'Boot Block Size' soft strap. 00 : 64KB (Default) : Invert A16 if Top Swap is enabled 01 : 128KB : Invert A17 if Top Swap is enabled 10 : 256KB : Invert A18 if Top Swap is enabled 11 : Reserved This soft strap only applies when booting from SPI. Boot from LPC (FWH) only supports a 64KB boot block size (Invert A16) and this soft strap value is a don't care.
28:12	0b RO	RSVD1: Reserved
11:10	X RW	Boot BIOS Straps (BBS): This field determines the destination of accesses to the BIOS memory range. Default is controlled by 'Boot BIOS Straps' pin strap. 00 LPC 01 Reserved 10 Reserved 11 SPI The value in this field can be overwritten by software as long as the BIOS Interface Lock-Down (bit 0) is not set.
9:2	0b RO	RSVD2: Reserved
1	X RW	Top Swap (TS): When set, PCU EP will invert either A16, A17, or A18 for cycles going to the BIOS space (but not the feature space) in the FWH. When cleared, PCU EP will not invert A16. If booting from LPC (FWH), then the Boot Block size is 64KB and A16 is inverted if Top Swap is enabled. If booting from SPI, then the BOOT_BLOCK_SIZE soft strap determines if A16, A17, or A18 should be inverted if Top Swap is enabled. If Top-Swap pin-strap is active, then this bit cannot be cleared by software. This bit should be kept in RTC well and should be reset only by SRTCRST_b
0	0h RW	BIOS Interface Lock-Down (BILD): When set, prevents GCS.TS and GCS.BBS from being changed. This bit can only be written from 0 to 1 once.

36 PCU – iLB – Real Time Clock (RTC)

The SoC contains a Motorola MC146818B-compatible real-time clock with 242 bytes of battery-backed RAM. The real-time clock performs two key functions—keeping track of the time of day and storing system data, even when the system is powered down. The RTC operates on a 32.768 kHz crystal and a 3.3 V battery.

The RTC supports two lockable memory ranges. By setting bits in the configuration space, two 8-byte ranges can be locked to read and write accesses. This prevents unauthorized reading of passwords or other system security information.

The RTC supports a date alarm that allows for scheduling a wake up event up to 30 days in advance.



36.1 Signal Descriptions

Please see [Chapter 2, “Physical Interfaces”](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal’s function




Table 327. RTC Signals

Signal Name	Direction Plat. Power	Description
ILB_RTC_X1	I VRTC	Crystal Input 1: This signal is connected to the 32.768 kHz crystal. If no external crystal is used, the signal can be driven with the desired clock rate.
ILB_RTC_X2	I VRTC	Crystal Input 2: This signal is connected to the 32.768 kHz crystal. If no external crystal is used, the signal should be left floating.
ILB_RTC_RST#	I VRTC	RTC Reset: An external RC circuit creates a time delay for the signal such that it will go high (de-assert) sometime after the battery voltage is valid. The RC time delay should be in the 18-25 ms range. Contact your Intel representative for details. When asserted, this signal resets all register bits in the RTC well except for GEN_PMC1.RPS. NOTE: Unless registers are being cleared (only to be done in the G3 power state), the signal input must always be high when all other RTC power planes are on. NOTE: In the case where the RTC battery is dead or missing on the platform, the signal should be deasserted before the PMC_RSMRST# signal is deasserted.
ILB_RTC_TEST#	I VRTC	RTC Battery Test: An external RC circuit creates a time delay for the signal such that it will go high (de-assert) sometime after the battery voltage is valid. The RC time delay should be in the 18-25 ms range. Contact your Intel representative for details. If the battery is missing/weak, this signal appears low (asserted) at boot just after the suspend power rail (V3P3A) is up since it will not have time to meet Vih when V3P3A is high. The weak/missing battery condition is reported in the GEN_PMC1.RPS (RTC Power Status) register. When asserted, BIOS may clear the RTC CMOS RAM. NOTE: Unless CMOS is being cleared (only to be done in the G3 power state) or the battery is low, the signal input must always be high when all other RTC power planes are on. NOTE: This signal may also be used for debug purposes, as part of a XDP port. Contact your Intel representative for details.
ILB_RTC_EXTPAD	I VRTC	External capacitor connection

36.2 Features

The Real Time Clock (RTC) module provides a battery backed-up date and time keeping device. Three interrupt features are available: time of day alarm with once a second to once a month range, periodic rates of 122 us to 500 ms, and end of update cycle notification. Seconds, minutes, hours, days, day of week, month, and year are counted.



The hour is represented in twelve or twenty-four hour format, and data can be represented in BCD or binary format. The design is meant to be functionally compatible with the Motorola MS146818B. The time keeping comes from a 32.768 kHz oscillating source, which is divided to achieve an update every second. The lower 14 bytes on the lower RAM block have very specific functions. The first ten are for time and date information. The next four (0Ah to 0Dh) are registers, which configure and report RTC functions. A host-initiated write takes precedence over a hardware update in the event of a collision.

36.2.1 Update Cycles

An update cycle occurs once a second, if the B.SET bit is not asserted and the divide chain is properly configured. During this procedure, the stored time and date are incremented, overflow checked, a matching alarm condition is checked, and the time and date are rewritten to the RAM locations. The update cycle starts at least 488 us after A.UIP is asserted, and the entire cycle does not take more than 1984 us to complete. The time and date RAM locations (00h to 09h) are disconnected from the external bus during this time.

36.3 Interrupts

The real-time clock interrupt is internally routed within the SoC both to the I/O APIC and the 8259. It is mapped to interrupt vector 8. This interrupt does not leave the SoC, nor is it shared with any other interrupt. IRQ8# from the ILB_LPC_SERIRQ stream is ignored. However, the High Performance Event Timers can also be mapped to IRQ8#; in this case, the RTC interrupt is blocked.

36.3.1 Lockable RAM Ranges


The RTC battery-backed RAM supports two 8-byte ranges that can be locked: the RC.UL and RC.LL register bits. When the locking bits are set, the corresponding range in the RAM is not readable or writable. A write cycle to those locations will have no effect. A read cycle to those locations will not return the location's actual value (resultant value is undefined).

Once a range is locked, the range can be unlocked only by a hard reset, which will invoke the BIOS and allow it to re-lock the RAM range.

36.3.2 Clearing Battery-Backed RTC CMOS RAM

Clearing CMOS RAM in an SoC-based platform can be done by using a jumper on ILB_RTC_TEST# or a GPI. Implementations should not attempt to clear CMOS by using a jumper to pull RTC_VCC low.

Note: The entire Extended Bank and bytes 0Eh-7Fh of the Standard Bank will be cleared.



36.3.2.1 Using ILB_RTC_TEST# to Clear the RTC CMOS RAM

A jumper on ILB_RTC_TEST# can be used to clear CMOS values. When ILB_RTC_TEST# is low, the GEN_PMC1.RPS register bit will be set. BIOS can monitor the state of this bit, and manually clear the RTC CMOS array once the system is booted. The normal position will cause ILB_RTC_TEST# to be pulled up through a weak pull-up resistor. This ILB_RTC_TEST# jumper technique allows the jumper to be moved and then replaced—all while the system is powered off. Then, once booted, the GEN_PMC1.RPS bit can be detected in the set state.

36.3.3 Using a GPI to Clear CMOS

A jumper on a GPI can also be used to clear CMOS values. BIOS should detect the setting of this GPI on system boot-up, and manually clear the CMOS array.

Note: The GPI strap technique to clear CMOS requires multiple steps to implement. The system is booted with the jumper in new position, then powered back down. The jumper is replaced back to the normal position, then the system is rebooted again.

Warning: Do not implement a jumper on RTC_VCC to clear CMOS.

36.3.4 Clearing Battery Backed RTC Registers

Clearing Battery Backed RTC Registers in an SoC based platform can be done by using a jumper on ILB_RTC_RST#. Implementations should not attempt to clear the registers by using a jumper to pull RTC_VCC low. A jumper on ILB_RTC_RST# pulled to ground can be used to reset the state of those Battery Backed RTC Register configurations bit that reside in the RTC power well to their default state. [Table 328](#) shows which bits are set to their default state when ILB_RTC_RST# is asserted low.

Table 328. Register Bits Reset by ILB_RTC_RST# Assertion (Sheet 1 of 2)

Register Bit	Bit(s)	Default State
RCRB_GENERAL_CONTROL.TS	1	xb
GEN_PMC1.PME_B0_S5_DIS	15	0b
GEN_PMC1.WOL_EN_OVRD	13	0b
GEN_PMC1.DIS_SLP_X_STRCH_SUS_UP	12	0b
GEN_PMC1.RTC Reserved	8	0b
GEN_PMC1.SWSMI_RATESEL	7:6	00b
GEN_PMC1.S4MAW	5:4	00b
GEN_PMC1.S4ASE	3	0b
GEN_PMC1.AG3E	0	0b
PM1_STS_EN.RTC_EN	26	0b
PM1_STS_EN.PWRBTNOR_STS	11	0b



Table 328. Register Bits Reset by ILB_RTC_RST# Assertion (Sheet 2 of 2)

Register Bit	Bit(s)	Default State
PM1_CNT.SLP_TYP	12:10	0b
GPE0a_EN.PME_B0_EN	13	0b
GPE0a_EN.BATLOW_EN	10	0b

36.4 References

Accessing the Real Time Clock Registers and the NMI Enable Bit: <http://download.intel.com/design/intarch/PAPERS/321088.pdf>

36.5 Register Map

36.6 IO Mapped Registers

The RTC internal registers and RAM is organized as two banks of 128 bytes each, called the standard and extended banks.

Note: It is not possible to disable the extended bank.

The first 14 bytes of the standard bank contain the RTC time and date information along with four registers, A - D, that are used for configuration of the RTC. The extended bank contains a full 128 bytes of battery backed SRAM. All data movement between the host CPU and the RTC is done through registers mapped to the standard I/O space.


Note: Registers reg_RTC_IR_type and reg_RTC_TR_type are used for data movement to and from the standard bank. Registers reg_RTC_RIR_type and reg_RTC_RTR_type are used for data movement to and from the extended bank. All of these registers have alias I/O locations, as indicated in Table 329.

Table 329. I/O Registers Alias Locations

Register	Original I/O Location	Alias I/O Location
reg_RTC_IR_type	70h	74h
reg_RTC_TR_type	71h	75h
reg_RTC_RIR_type	72h	76h
reg_RTC_RTR_type	73h	77h

36.7 Indexed Registers

The RTC contains indexed registers that are accessed via the reg_RTC_IR_type and reg_RTC_TR_type registers.

**Table 330. RTC Indexed Registers**

Start	End	Name
00h	00h	Seconds
01h	01h	Seconds Alarm
02h	02h	Minutes
03h	03h	Minutes Alarm
04h	04h	Hours
05h	05h	Hours Alarm
06h	06h	Day of Week
07h	07h	Day of Month
08h	08h	Month
09h	09h	Year
0Ah	0Ah	Register A
0Bh	0Bh	Register B
0Ch	0Ch	Register C
0Dh	0Dh	Register D
0Eh	7Fh	114 Bytes of User RAM

§



36.8 PCU iLB Real Time Clock (RTC) I/O Registers

Table 331. Summary of PCU iLB Real Time Clock (RTC) I/O Registers—

Offset	Size	Register ID—Description	Default Value
70h	1	"IR (reg_RTC_IR_type)—Offset 70h" on page 4562	00h
71h	1	"TR (reg_RTC_TR_type)—Offset 71h" on page 4562	00h
72h	1	"RIR (reg_RTC_RIR_type)—Offset 72h" on page 4563	00h
73h	1	"RTR (reg_RTC_RTR_type)—Offset 73h" on page 4563	00h

36.8.1 IR (reg_RTC_IR_type)—Offset 70h

Indexed Registers

Access Method

Type: I/O Register
(Size: 8 bits)

reg_RTC_IR_type: 70h

Default: 00h

7	4	0
0	0	0
IR		

Bit Range	Default & Access	Description
7:0	X RW	IR: Real-Time Clock (Standard RAM) Index Register Note: Writes to 72h, 74h, and 76h do not affect the NMI enable (bit 7 of 70h)

36.8.2 TR (reg_RTC_TR_type)—Offset 71h

Target Registers

Access Method

Type: I/O Register
(Size: 8 bits)

reg_RTC_TR_type: 71h

Default: 00h

7	4	0
0	0	0
TR		

Bit Range	Default & Access	Description
7:0	X RW	TR: Real-Time Clock (Standard RAM) Target Register



36.8.3 RIR (reg_RTC_RIR_type)—Offset 72h

Extended RAM Index Register

Access Method

Type: I/O Register
(Size: 8 bits)

reg_RTC_RIR_type: 72h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
RIR									

Bit Range	Default & Access	Description
7:0	X RW	RIR: Extended RAM Index Register

36.8.4 RTR (reg_RTC_RTR_type)—Offset 73h

Extended RAM Target Register

Access Method

Type: I/O Register
(Size: 8 bits)

reg_RTC_RTR_type: 73h

Default: 00h

7				4					0
0	0	0	0	0	0	0	0	0	0
RTR									

Bit Range	Default & Access	Description
7:0	X RW	RTR: Extended RAM Target Register

37.1 Signal Descriptions

The diagram illustrates the Platform Control Unit (PCU) architecture. The PCU is connected to a system bus and various components including APIC, 8259, HPET, 8254, RTC, GPIO, LPC, PMC, SPI, UART, and SMB. It also interfaces with I/O devices.


37.1 Signal Descriptions

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane.
- **Description:** A brief explanation of the signal's function

Table 332. 8254 Signals

Signal Name	Direction Plat. Power	Description
ILB_8254_SPKR	O V1P8S	Speaker: The signal drives an external speaker driver device, which in turn drives the system speaker. Upon PMC_PLTRST#, its output state is 0. <i>This signal is muxed and may be used by other functions.</i>



37.2 Features

37.2.1 Counter 0, System Timer

This counter functions as the system timer by controlling the state of IRQ0 and is programmed for Mode 3 operation. The counter produces a square wave with a period equal to the product of the counter period (838 ns) and the initial count value. The counter loads the initial count value one counter period after software writes the count value to the counter I/O address. The counter initially asserts IRQ0 and decrements the count value by two each counter period. The counter negates IRQ0 when the count value reaches 0. It then reloads the initial count value and again decrements the initial count value by two each counter period. The counter then asserts IRQ0 when the count value reaches 0, reloads the initial count value, and repeats the cycle, alternately asserting and negating IRQ0.

37.2.2 Counter 1, Refresh Request Signal

This counter is programmed for Mode 2 operation and impacts the period of the NSC.RTS register bit. Programming the counter to anything other than Mode 2 results in undefined behavior.

37.2.3 Counter 2, Speaker Tone

This counter provides the speaker tone and is typically programmed for Mode 3 operation. The counter provides a speaker frequency equal to the counter clock frequency (1.193 MHz) divided by the initial count value. The speaker must be enabled by a write to the NSC.SDE register bit.

37.3 Use

37.3.1 Timer Programming

The counter/timers are programmed in the following fashion:

1. Write a control word to select a counter.
2. Write an initial count for that counter.
3. Load the least and/or most significant bytes (as required by Control Word Bits 5, 4) of the 16-bit counter.
4. Repeat with other counters.

Only two conventions need to be observed when programming the counters. First, for each counter, the control word must be written before the initial count is written. Second, the initial count must follow the count format specified in the control word (least significant byte only, most significant byte only, or least significant byte and then most significant byte).

A new initial count may be written to a counter at any time without affecting the counter's programmed mode. Counting is affected as described in the mode definitions. The new count must follow the programmed count format.

If a counter is programmed to read/write two-byte counts, the following precaution applies: A program must not transfer control between writing the first and second byte to another routine which also writes into that same counter. Otherwise, the counter will be loaded with an incorrect count.

The Control Word Register at port 43h controls the operation of all three counters. Several commands are available:

- **Control Word Command.** Specifies which counter to read or write, the operating mode, and the count format (binary or BCD).
- **Counter Latch Command.** Latches the current count so that it can be read by the system. The countdown process continues.
- **Read Back Command.** Reads the count value, programmed mode, the current state of the OUT pins, and the state of the Null Count Flag of the selected counter.

Table 333 lists the six operating modes for the interval counters.


Table 333. Counter Operating Modes

Mode	Function	Description
0	Out signal on end of count (=0)	Output is 0. When count goes to 0, output goes to 1 and stays at 1 until counter is reprogrammed.
1	Hardware re-triggerable one-shot	Output is 0. When count goes to 0, output goes to 1 for one clock time.
2	Rate generator (divide by n counter)	Output is 1. Output goes to 0 for one clock time, then back to 1 and counter is reloaded.
3	Square wave output	Output is 1. Output goes to 0 when counter rolls over, and counter is reloaded. Output goes to 1 when counter rolls over, and counter is reloaded, etc.
4	Software triggered strobe	Output is 1. Output goes to 0 when count expires for one clock time.
5	Hardware triggered strobe	Output is 1. Output goes to 0 when count expires for one clock time.

37.3.2 Reading from the Interval Timer

It is often desirable to read the value of a counter without disturbing the count in progress. There are three methods for reading the counters: a simple read operation, counter Latch command, and the Read-Back command. Each is explained below.

With the simple read and counter latch command methods, the count must be read according to the programmed format; specifically, if the counter is programmed for two byte counts, two bytes must be read. The two bytes do not have to be read one right after the other. Read, write, or programming operations for other counters may be inserted between them.



37.3.2.1 Simple Read

The first method is to perform a simple read operation. The counter is selected through Port 40h (Counter 0), 41h (Counter 1), or 42h (Counter 2).

Note: Performing a direct read from the counter does not return a determinate value, because the counting process is asynchronous to read operations. However, in the case of Counter 2, the count can be stopped by writing 0b to the NSC.TC2E register bit.

37.3.2.2 Counter Latch Command

The Counter Latch command, written to Port 43h, latches the count of a specific counter at the time the command is received. This command is used to ensure that the count read from the counter is accurate, particularly when reading a two-byte count. The count value is then read from each counter's Count register as was programmed by the Control register.

The count is held in the latch until it is read or the counter is reprogrammed. The count is then unlatched. This allows reading the contents of the counters on the fly without affecting counting in progress. Multiple Counter Latch Commands may be used to latch more than one counter. Counter Latch commands do not affect the programmed mode of the counter in any way.

If a counter is latched and then, some time later, latched again before the count is read, the second Counter Latch command is ignored. The count read is the count at the time the first Counter Latch command was issued.

37.3.2.3 Read Back Command

The Read Back command, written to Port 43h, latches the count value, programmed mode, and current states of the OUT pin and Null Count flag of the selected counter or counters. The value of the counter and its status may then be read by I/O access to the counter address.

The Read Back command may be used to latch multiple counter outputs at one time. This single command is functionally equivalent to several counter latch commands, one for each counter latched. Each counter's latched count is held until it is read or reprogrammed. Once read, a counter is unlatched. The other counters remain latched until they are read. If multiple count Read Back commands are issued to the same counter without reading the count, all but the first are ignored.

The Read Back command may additionally be used to latch status information of selected counters. The status of a counter is accessed by a read from that counter's I/O port address. If multiple counter status latch operations are performed without reading the status, all but the first are ignored.

Both count and status of the selected counters may be latched simultaneously. This is functionally the same as issuing two consecutive, separate Read Back commands. If multiple count and/or status Read Back commands are issued to the same counters without any intervening reads, all but the first are ignored.



If both count and status of a counter are latched, the first read operation from that counter returns the latched status, regardless of which was latched first. The next one or two reads, depending on whether the counter is programmed for one or two type counts, returns the latched count. Subsequent reads return unlatched count.

37.4 Register Map

37.5 IO Mapped Registers

The IO ports listed in [Table 334](#) have multiple register functions depending on the current programmed state of the 8254. The port numbers referenced in the register descriptions following [Table 334](#) is one possible combination but not the only one.

Table 334. Register Aliases

Port	Alias	Register Name	Default Value	Access
40h	50h	Counter 0 Interval Time Status Byte Format (C0TS)	0xxxxxxb	RO
		Counter 0 Counter Access Port Register (C0AP)	Undefined	RW
41h	51h	Counter 1 Interval Time Status Byte Format (C1TS)	0xxxxxxb	RO
		Counter 1 Counter Access Port Register (C1AP)	Undefined	RW
42h	52h	Counter 2 Interval Time Status Byte Format (C2TS)	0xxxxxxb	RO
		Counter 2 Counter Access Port Register (C2AP)	Undefined	RW
43h	-	Timer Control Word Register (TCW)	Undefined	WO
		Read Back Command (RBC)	xxxxxx0b	WO
		Counter Latch Command (CLC)	xxxx0000b	WO



37.6 PCU iLB 8254 Timers IO Registers

Table 335. Summary of PCU iLB 8254 Timers I/O Registers—

Offset	Size	Register ID—Description	Default Value
40h	1	"COTS—Offset 40h" on page 4569	00h
41h	1	"C1TS—Offset 41h" on page 4570	00h
42h	1	"C2TS—Offset 42h" on page 4570	00h
43h	1	"TCW—Offset 43h" on page 4571	00h
50h	1	"C0AP—Offset 50h" on page 4572	00h
51h	1	"C1AP—Offset 51h" on page 4572	00h
52h	1	"C2AP—Offset 52h" on page 4572	00h
61h	1	"NSC—Offset 61h" on page 4573	20h

37.6.1 COTS—Offset 40h

Counter 0 Interval Time Status Byte Format. Status byte can be read following a Read Back Command. If latch status is chosen (bit 4=0, Read Back Command) as a read back option for counter 0, the next read from this register returns the status byte.

Access Method

Type: I/O Register
(Size: 8 bits)

COTS: 40h

Default: 00h

7				4				0
0	0	0	0	0	0	0	0	0
CS	CR		RWS			MD		CT

Bit Range	Default & Access	Description
7	0b RO	CS: Counter State (CS): When set, OUT of the counter is set. When cleared, OUT of the counter is 0.
6	X RO	CR: Count Register: When cleared, indicates when the last count written to the Count Register (CR) has been loaded into the counting element (CE) and is available for reading. The time this happens depends on the counter mode.
5:4	X RO	RWS: Read/Write Selection: These reflect the read/write selection made through bits[5:4] of the control register. The binary codes returned during the status read match the codes used to program the counter read/write selection. 00 Counter Latch Command 01 Read/Write Least Significant Byte (LSB) 10 Read/Write Most Significant Byte (MSB) 11 Read/Write LSB then MSB
3:1	X RO	MD: Mode: Returns the counter mode programming. The binary code returned matches the code used to program the counter mode, as listed under the bit function above. Bits Mode Description 000 0 Out signal on end of count (=0) 001 1 Hardware retriggerable one-shot x10 2 Rate generator (divide by n counter) x11 3 Square wave output 100 4 Software triggered strobe 101 5 Hardware triggered strobe
0	X RO	CT: Countdown Type: 0 for binary countdown or a 1 for binary coded decimal (BCD) countdown.



37.6.2 C1TS—Offset 41h

Counter 1 Interval Time Status Byte Format. Counter 1 Interval Time Status Byte Format. Status byte can be read following a Read Back Command. If latch status is chosen (bit 4=0, Read Back Command) as a read back option for counter 1, the next read from this register returns the status byte.

Access Method

Type: I/O Register
(Size: 8 bits)

C1TS: 41h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
CS	CR	RWS		MD		CT	

Bit Range	Default & Access	Description
7	0b RO	CS: Counter State (CS): When set, OUT of the counter is set. When cleared, OUT of the counter is 0.
6	X RO	CR: Count Register: When cleared, indicates when the last count written to the Count Register (CR) has been loaded into the counting element (CE) and is available for reading. The time this happens depends on the counter mode.
5:4	X RO	RWS: Read/Write Selection: These reflect the read/write selection made through bits[5:4] of the control register. The binary codes returned during the status read match the codes used to program the counter read/write selection. 00 Counter Latch Command 01 Read/Write Least Significant Byte (LSB) 10 Read/Write Most Significant Byte (MSB) 11 Read/Write LSB then MSB
3:1	X RO	MD: Mode: Returns the counter mode programming. The binary code returned matches the code used to program the counter mode, as listed under the bit function above. Bits Mode Description 000 0 Out signal on end of count (=0) 001 1 Hardware retriggerable one-shot x10 2 Rate generator (divide by n counter) x11 3 Square wave output 100 4 Software triggered strobe 101 5 Hardware triggered strobe
0	X RO	CT: Countdown Type: 0 for binary countdown or a 1 for binary coded decimal (BCD) countdown.

37.6.3 C2TS—Offset 42h

Counter 2 Interval Time Status Byte Format. Counter 2 Interval Time Status Byte Format. Status byte can be read following a Read Back Command. If latch status is chosen (bit 4=0, Read Back Command) as a read back option for counter 2, the next read from this register returns the status byte.

Access Method

Type: I/O Register
(Size: 8 bits)

C2TS: 42h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
CS	CR	RWS		MD		CT	



Bit Range	Default & Access	Description
7	0b RO	CS: Counter State (CS): When set, OUT of the counter is set. When cleared, OUT of the counter is 0.
6	X RO	CR: Count Register: When cleared, indicates when the last count written to the Count Register (CR) has been loaded into the counting element (CE) and is available for reading. The time this happens depends on the counter mode.
5:4	X RO	RWS: Read/Write Selection: These reflect the read/write selection made through bits[5:4] of the control register. The binary codes returned during the status read match the codes used to program the counter read/write selection. 00 Counter Latch Command 01 Read/Write Least Significant Byte (LSB) 10 Read/Write Most Significant Byte (MSB) 11 Read/Write LSB then MSB
3:1	X RO	MD: Mode: Returns the counter mode programming. The binary code returned matches the code used to program the counter mode, as listed under the bit function above. Bits Mode Description 000 0 Out signal on end of count (=0) 001 1 Hardware retriggerable one-shot x10 2 Rate generator (divide by n counter) x11 3 Square wave output 100 4 Software triggered strobe 101 5 Hardware triggered strobe
0	X RO	CT: Countdown Type: 0 for binary countdown or a 1 for binary coded decimal (BCD) countdown.

37.6.4 TCW—Offset 43h

Timer Control Word Register. This register is programmed prior to any counter being accessed to specify counter modes. Following reset, the control words for each register are undefined and each counter output is 0. Each timer must be programmed to bring it into a known state.

Access Method

Type: I/O Register
(Size: 8 bits)

TCW: 43h

Default: 00h

7	4	0
0	0	0
CS	RWS	CMS
		BCS

Bit Range	Default & Access	Description
7:6	X WO	CS: Counter Select (CS): The Counter Selection bits select the counter the control word acts upon as shown below. The Read Back Command is selected when bits[7:6] are both 1 00 Counter 0 select 01 Counter 1 select 10 Counter 2 select 11 Read Back Command
5:4	X WO	RWS: Read/Write Select RWS): The counter programming is done through the counter port (40h for counter 0, 41h for counter 1, and 42h for counter 2) 00 Counter Latch Command 01 Read/Write Least Significant Byte (LSB) 10 Read/Write Most Significant Byte (MSB) 11 Read/Write LSB then MSB
3:1	X WO	CMS: Counter Mode Selection (CMS): Selects one of six modes of operation for the selected counter. 000 = Out signal on end of count (=0) 001 = Hardware retriggerable one-shot x10 = Rate generator (divide by n counter) x11 = Square wave output 100 = Software triggered strobe 101 = Hardware triggered strobe
0	X WO	BCS: Binary/BCD Countdown Select (BCS): 0 Binary countdown is used. The largest possible binary count is 216 1 Binary coded decimal (BCD) count is used. The largest possible BCD count is 104



37.6.5 C0AP—Offset 50h

Counter 0 Counter Access Port Register

Access Method

Type: I/O Register
(Size: 8 bits)

C0AP: 50h

Default: 00h

7	4	0
0	0	0
0		

Bit Range	Default & Access	Description
7:0	X RW	CP: Counter Port: Each counter port address is used to program the 16-bit Count Register. The order of programming, either LSB only, MSB only, or LSB then MSB, is defined with the Interval Counter Control Register at port 43h. The counter port is also used to read the current count from the Count Register, and return the status of the counter programming following a Read Back Command.

37.6.6 C1AP—Offset 51h

Counter 1 Counter Access Port Register

Access Method

Type: I/O Register
(Size: 8 bits)

C1AP: 51h

Default: 00h

7	4	0
0	0	0
0		

Bit Range	Default & Access	Description
7:0	X RW	CP: Counter Port: Each counter port address is used to program the 16-bit Count Register. The order of programming, either LSB only, MSB only, or LSB then MSB, is defined with the Interval Counter Control Register at port 43h. The counter port is also used to read the current count from the Count Register, and return the status of the counter programming following a Read Back Command.

37.6.7 C2AP—Offset 52h

Counter 2 Counter Access Port Register

Access Method

Type: I/O Register
(Size: 8 bits)

C2AP: 52h

Default: 00h

7	4	0
0	0	0
0		



Bit Range	Default & Access	Description
7:0	X RW	CP: Counter Port: Each counter port address is used to program the 16-bit Count Register. The order of programming, either LSB only, MSB only, or LSB then MSB, is defined with the Interval Counter Control Register at port 43h. The counter port is also used to read the current count from the Count Register, and return the status of the counter programming following a Read Back Command.

37.6.8 NSC—Offset 61h

NMI Status and Control

Access Method

Type: I/O Register
(Size: 8 bits)

NSC: 61h


Default: 20h

7			4				0
0	0	1	0	0	0	0	0
SNS	INS	T2S	RTS	INE	SNE	SDE	TC2E

Bit Range	Default & Access	Description
7	0b RO	SNS: SERR# NMI Status (SNS): Set on errors from a PCIe port or internal functions that generate SERR#. SNE in this register must be cleared in order for this bit to be set. To reset the interrupt, set bit 2 to 1 and then set it to 0.
6	0b RO	INS: IOCHK NMI Status (INS): Set when SERIRQ asserts IOCHK# and INE in this register is cleared. To reset the interrupt, set bit 3 to 1 and then set it to 0.
5	1b RO	RTS (T2S): Timer Counter 2 Status (T2S): Reflects the current state of the 8254 counter 2 outputs. Counter 2 must be programmed for this bit to have a determinate value.
4	0b RO	RTS: Refresh Cycle Toggle Status (RTS): Reflects the current state of 8254 counter 1
3	X RW	INE: IOCHK NMI Enable (INE): When set, IOCHK# NMIs are disabled. When cleared, IOCHK# NMIs are enabled.
2	0b RW	SNE: SERR# NMI Enable (SNE): When set, SERR# NMIs are disabled. When cleared, SERR# NMIs are enabled.
1	0b RW	SDE: Speaker Data Enable (SDE): When this bit is a 0, the SPKR output is a 0. When this bit is a 1, the SPKR output is equivalent to the Counter 2 OUT signal value.
0	0b RW	TC2E: Timer Counter 2 Enable (TC2E): When cleared, counter 2 counting is disabled. When set, counting is enabled.

38 PCU – iLB – High Precision Event Timer (HPET)

This function provides a set of timers that to be used by the operating system for timing events. One timer block is implemented, containing one counter and three timers.



38.1 Features


38.1.1 Non-Periodic Mode - All Timers

This mode can be thought of as creating a one-shot. When a timer is set up for non-periodic mode, it generates an interrupt when the value in the main counter matches the value in the timer's comparator register. As timers 1 and 2 are 32-bit, they will generate another interrupt when the main counter wraps.

T0CV cannot be programmed reliably by a single 64-bit write in a 32-bit environment unless only the periodic rate is being changed. If T0CV needs to be re-initialized, the following algorithm is performed:

1. Set T0C.TVS
2. Set T0CV[31:0]
3. Set T0C.TVS
4. Set T0CV[63:32]

Every timer is required to support the non-periodic mode of operation.



38.1.2 Periodic Mode - Timer 0 only

When set up for periodic mode, when the main counter value matches the value in T0CV, an interrupt is generated (if enabled). Hardware then increases T0CV by the last value written to T0CV. During run-time, T0CV can be read to find out when the next periodic interrupt will be generated. Software is expected to remember the last value written to T0CV.

Example: if the value written to T0CV is 00000123h, then

- An interrupt will be generated when the main counter reaches 00000123h.
- T0CV will then be adjusted to 00000246h.
- Another interrupt will be generated when the main counter reaches 00000246h.
- T0CV will then be adjusted to 00000369h.

When the incremented value is greater than the maximum value possible for T0CV, the value will wrap around through 0. For example, if the current value in a 32-bit timer is FFFF0000h and the last value written to this register is 20000, then after the next interrupt the value will change to 00010000h.

If software wants to change the periodic rate, it writes a new value to T0CV. When the timer's comparator matches, the new value is added to derive the next matching point. If software resets the main counter, the value in the comparator's value register must also be reset by setting T0C.TVS. To avoid race conditions, this should be done with the main counter halted. The following usage model is expected:

1. Software clears GCFG.EN to prevent any interrupts.
2. Software clears the main counter by writing a value of 00h to it.
3. Software sets T0C.TVS.
4. Software writes the new value in T0CV.
5. Software sets GCFG.EN to enable interrupts.

38.1.2.1 Interrupts

If each timer has a unique interrupt and the timer has been configured for edge-triggered mode, then there are no specific steps required. If configured to level-triggered mode, then its interrupt must be cleared by software by writing a '1' back to the bit position for the interrupt to be cleared.

Interrupts associated with the various timers have several interrupt mapping options. Software should mask GCFG.LRE when reprogramming HPET interrupt routing to avoid spurious interrupts.

38.1.2.2 Mapping Option #1: Legacy Option (GCFG.LRE set)

This forces the following mapping:

**Table 336. 8254 Interrupt Mapping**

Time r	8259 Mapping	APIC Mapping	Comment
0	IRQ0	IRQ2	The 8254 timer will not cause any interrupts
1	IRQ8	IRQ8	RTC will not cause any interrupts.
2	T2C.IR	T2C.IRC	

38.1.2.3 Mapping Option #2: Standard Option (GCFG.LRE cleared)

Each timer has its own routing control. The interrupts can be routed to various interrupts in the I/O APIC. T[2:0]C.IRC indicates which interrupts are valid options for routing. If a timer is set for edge-triggered mode, the timers should not be shared with any other interrupts.

38.2 References

IA-PC HPET (High Precision Event Timers) Specification, Revision 1.0a: http://www.intel.com/hardware design/hpetspec_1.pdf

38.3 Register Map**38.4 Memory Mapped Registers**

The register space is memory mapped to a 1K block at address FED00000h. All registers are in the core well. Accesses that cross register boundaries result in undefined behavior.



38.5 PCU iLB High Performance Event Timer (HPET) Memory Mapped IO Registers

Table 337. Summary of PCU iLB High Performance Event Timer (HPET) Memory Mapped I/O Registers—

Offset	Size	Register ID—Description	Default Value
FED00000h	8	"GCID (HPET_GCID)—Offset FED00000h" on page 4577	0429B17F8086A201h
FED00010h	8	"GCFG (HPET_GCFG)—Offset FED00010h" on page 4578	0000000000000000h
FED00020h	8	"GIS (HPET_GIS)—Offset FED00020h" on page 4578	0000000000000000h
FED000F0h	8	"MCV (HPET_MCV)—Offset FED000F0h" on page 4579	0000000000000000h
FED00100h	8	"T0C (HPET_T0C)—Offset FED00100h" on page 4579	00F0000000000030h
FED00108h	4	"T0CV_L (HPET_T0CV_L)—Offset FED00108h" on page 4580	FFFFFFFFh
FED0010Ch	4	"T0CV_U (HPET_T0CV_U)—Offset FED0010Ch" on page 4581	FFFFFFFFh
FED00120h	8	"T1C (HPET_T1C)—Offset FED00120h" on page 4581	00F0000000000000h
FED00128h	8	"T1CV (HPET_T1CV)—Offset FED00128h" on page 4582	00000000FFFFFFFFh
FED00140h	8	"T2C (HPET_T2C)—Offset FED00140h" on page 4583	00F0080000000000h
FED00148h	8	"T2CV (HPET_T2CV)—Offset FED00148h" on page 4584	00000000FFFFFFFFh

38.5.1 GCID (HPET_GCID)—Offset FED00000h

General Capabilities and ID

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

HPET_GCID: FED00000h

Default: 0429B17F8086A201h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	1	0	0	1	1	0	1	1	1	1	0	0	0	1
CTP								VID				LRC	RESERVED	CS	NT	RID

Bit Range	Default & Access	Description
63:32	0429B17Fh RO	CTP: Counter Tick Period (CTP): Indicates a period of 69.841279ns, (14.1318 MHz clock period)
31:16	8086h RO	VID: Vendor ID (VID): Value of 8086h indicates Intel.
15	1b RO	LRC: Legacy Rout Capable (LRC): Indicates support for Legacy Interrupt Rout.
14	0b RO	RESERVED: Reserved.
13	1b RO	CS: Counter Size (CS): This bit is set to indicate that the main counter is 64 bits wide.



Bit Range	Default & Access	Description
12:8	02h RO	NT: Number of Timers (NT): Indicates that 3 timers are supported.
7:0	01h RO	RID: Revision ID (RID): Indicates that revision 1.0 of the specification is implemented.

38.5.2 GCFG (HPET_GCFG)—Offset FED00010h

General Configuration

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

HPET_GCFG: FED00010h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
RESERVED																U Z M

Bit Range	Default & Access	Description
63:2	0b RO	RESERVED: Reserved.
1	0b RW	LRE: Legacy Rout Enable (LRE): When set, interrupts will be routed as follows: Timer 0 will be routed to IRQ0 in 8259 or IRQ2 in the I/O APIC Timer 1 will be routed to IRQ8 in 8259 and I/O APIC Timer 2 will be routed as per the routing in T2C When set, the T[1:0]C.IR will have no impact for timers 0 and 1.
0	0b RW	EN: Overall Enable (EN): When set, the timers can generate interrupts. When cleared, the main counter will halt and no interrupts will be caused by any timer. For level-triggered interrupts, if an interrupt is pending when this bit is cleared, the GIS.Tx will not be cleared.

38.5.3 GIS (HPET_GIS)—Offset FED00020h

General Interrupt Status

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

HPET_GIS: FED00020h

Default: 0000000000000000h

6	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
RESERVED																N C P



Bit Range	Default & Access	Description
63:3	0b RO	RESERVED: Reserved.
2	0b RW	T2: Timer 2 Status (T2): Same functionality as T0, for timer 2.
1	0b RW	T1: Timer 1 Status (T1): Same functionality as T0, for timer 1.
0	0b RW	T0: Timer 0 Status (T0): In edge triggered mode, this bit always reads as 0. In level triggered mode, this bit is set when an interrupt is active.

38.5.4 MCV (HPET_MCV)—Offset FED000F0h

Main Counter Value

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

HPET_MCV: FED000F0h

Default: 0000000000000000h

63	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
63:0	0b RW	CV: Counter Value (CV): Reads return the current value of the counter. Writes load the new value to the counter. Timers 1 and 2 return 0 for the upper 32-bits of this register.

38.5.5 TOC (HPET_TOC)—Offset FED00100h

Timer 0 Config and Capabilities

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

HPET_TOC: FED00100h

Default: 00F0000000000030h

63	6	5	5	4	4	4	3	3	2	2	2	1	1	8	4	0
3	0	6	2	8	4	0	6	2	8	4	0	6	2			
0	0	0	0	1	1	1	0	0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Description
63:32	00f00000h RO	IRC (CV): Interrupt Rout Capability (IRC): Indicates I/OxAPIC interrupts the timer can use: Timer 0,1: 00f00000h. Indicates support for IRQ20, 21, 22, 23 Timer 2: 00f00800h. Indicates support for IRQ11, 20, 21, 22, and 23



31	28	24	20	16	12	8	4	0
1	1	1	1	1	1	1	1	1
TOCV_L								



Bit Range	Default & Access	Description
3	0b RO	TYP: Timer Type (TYP): If PIC is set, this bit is read/write, and can be used to enable the timer to generate a periodic interrupt. This bit is RW for timer 0, and RO for timers 1 and 2.
2	0b RW	IE: Interrupt Enable (IE): When set, enables the timer to cause an interrupt when it times out. When cleared, the timer count and generates status bits, but will not cause an interrupt.
1	0b RW	IT: Timer Interrupt Type (IT): When cleared, interrupt is edge triggered. When set, interrupt is level triggered and will be held active until it is cleared by writing 1 to GIS.Tn. If another interrupt occurs before the interrupt is cleared, the interrupt remains active.
0	0b RO	RESERVED (RESERVED3): Reserved.

38.5.11 T2CV (HPET_T2CV)—Offset FED00148h

Timer 2 Comperator Value

Access Method

Type: Memory Mapped I/O Register
(Size: 64 bits)

HPET_T2CV: FED00148h


Default: 00000000FFFFFFFFh

63	60	56	52	48	44	40	36	32	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0	0	1	1	1	1	1	1	1
RESERVED1									T2CV							

Bit Range	Default & Access	Description
63:32	0b RO	RESERVED (RESERVED1): Reserved.
31:0	FFFFFFFFh RO	T2CV: Timer 2 Comperator Value

39 PCU – iLB – GPIO

102 GPIOs are available for use during the S0 ACPI state, and 44 are available for use from S5 to S0 (SUS). Most of these GPIOs can be used as legacy GPIOs through IO registers.



39.1 Signal Descriptions

Please see [Chapter 2, “Physical Interfaces”](#) for additional details.

The signal description table has the following headings:

- **Signal Name:** The name of the signal/pin
- **Direction:** The buffer direction can be either input, output, or I/O (bidirectional)
- **Platform Power:** The reference power plane
- **Description:** A brief explanation of the signal’s function

Table 338. GPIO Signals

Signal Name	Direction Plat. Power	Description
GPIO_S0_SC[101:0]	I/O Varies	These GPIO pins are powered and active in S0 only. Many of these are multiplexed with other functions and may have different default pin names.
GPIO_S5[43:0]	I/O Varies	These GPIO pins are powered and active in S5-S0 (SUS). Many of these are multiplexed with other functions and may have different default pin names. Some are used as straps.

39.2 Features

GPIOs can generate general purpose events (GPEs) on rising and/or falling edges.

39.3 Legacy Use

Each GPIO has six registers that control how it is used, or report its status:

- Use Select
- I/O Select
- GPIO Level
- Trigger Positive Edge
- Trigger Negative Edge
- Trigger Status

The Use Select register selects a GPIO pin as a GPIO, or leaves it as its programmed function. This register must be set for all other registers to affect the GPIO.

The I/O Select register determines the direction of the GPIO.

The Trigger Positive Edge and Trigger Negative Edge registers enable general purpose events on a rising and falling edge respectively. This only applies to GPIOs set as input.

The Trigger Status register is used by software to determine if the GPIO triggered a GPE. This only applies to GPIOs set as input and with one or both of the Trigger modes enabled.

Additionally, there is one additional register for each S5 GPIO:

- Wake Enable

This register allows S5 GPIOs to trigger a wake event based on the Trigger registers' settings.

39.4 Memory Mapped Use


Each GPIO has two registers that control how it is used, or report its status:

- Pad Configuration (PCONF0)
- Pad Value (PAD_VAL)

Note: These registers are also implemented for the available Virtual GPIOs (vGPIOs).

The Pad Configuration register has the following functions:

- Configure the function of the pin as a GPIO or multiplexed native functions
- Configure pull resistors
- Configure electrical behavior
- Configure edge detection
- Configure interrupt handling



Note: The PCONF0 register is valid irrespective of whether or not the pin is configured as a GPIO

The Pad Value register has the following functions:

- Reads the GPIO value, when configured as a GPI
- Writes the GPIO value, when configured as a GPO
- Enables/disables input and output capabilities

Note: The Pad Value register is only valid when the pin is configured as a GPIO in the Pad Configuration register.

Additionally, there are a number of general configuration registers that control groups of GPIOs or report their status. These include:

- IRQ Status (IRQ_TS)
- Direct IRQ Multiplexer (DIRECT_IRQ)

The IRQ Status register indicates if an IRQ associated with a GPIO has been triggered.

The Direct IRQ Multiplexer register allows for a selection of GPIOs to be assigned a dedicated APIC interrupt.

The GPIO South CORE and GPIO South SUS families have 16 dedicated IRQ outputs for each. Each of these 16 has a mux with an 8 bit select that can pick which of the input pads are mapped to that direct IRQ (the pad would still need to be programmed). Refer to the Intel Bios Writers Guide. This programming is done with the Direct IRQ 0 - 3 registers for SCORE and SSUS domains listed in the GPIO Family Register section.

The 16 GPSCORE direct IRQs are mapped to IOAPIC_IRQ [66:51].


The 16 GPSSUS direct IRQs are mapped to IOAPIC_IRQ [82:67].

For example:

1. Programming GPSCORE Direct IRQ 0 [dirq0] = 4 will map GPIO_S0_SC[004]/pCIE_CLKREQ[1#] to IRQ51.
2. Programming GPSCORE Direct IRQ 0 [dirq1] = 8 will map GPIO_S0_SC[008]/I2S0_CLK to IRQ52.


39.5 Register Map

Figure 137.SIO - I²C Register Map



39.6 GPIO Registers

Registers are broken into two groups: memory mapped and legacy IO registers. Memory mapped registers are used by BIOS and firmware to select the configurable function of the GPIO and setup analog states needed for that function's operation. They



are named based on the pin/ball name. Legacy IO registers are the more traditional GPIO control/status type, and are used when the function selected is a traditional GPIO (direction, level, use registers). They are numbered based on the GPIO number.

Each group is further broken down into SCORE (internal partition naming) and SSUS. SCORE are for the GPIO's named GPIO_S0_SC[xxx], while SSUS are for the GPIO's named GPIO_S5[xx].

Note: All GPIO registers must be accessed as double words. Unpredictable results will occur otherwise.

Note: All memory mapped GPIO *_PAD_VAL's must set Ienenb = 0 in order to read the pad_val of the GPIO. This applies to RO GPIO's as well.

Note: vGPIO's are virtual GPIO's for use by software to generate interrupts. They are not tied to physical pins.

Note: When a GPIO is selected via the IO USE_SEL, Memory accesses are denied (pconf0, pconf1 and pad_val).

§



39.7 PCU iLB GPIO S0 IO Addressed Registers

Table 339. Summary of PCU iLB GPIO S0 IO Registers—GPIO_BASE_ADDRESS

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"South Core Use Select 1 (cfio_ioreg_SC_USE_SEL_31_0_)—Offset 0h" on page 4591	00000000h
4–7h	4	"South Core Io Select 1 (cfio_ioreg_SC_IO_SEL_31_0_)—Offset 4h" on page 4592	00000000h
8–Bh	4	"South Core Gpio Level 1 (cfio_ioreg_SC_GP_LVL_31_0_)—Offset 8h" on page 4593	00000000h
C–Fh	4	"South Core Trigger Positive Edge Enable 1 (cfio_ioreg_SC_TPE_31_0_)—Offset Ch" on page 4594	00000000h
10–13h	4	"South Core Trigger Negative Enable 1 (cfio_ioreg_SC_TNE_31_0_)—Offset 10h" on page 4595	00000000h
14–17h	4	"South Core Trigger Status 1 (cfio_ioreg_SC_TS_31_0_)—Offset 14h" on page 4596	00000000h
20–23h	4	"South Core Use Select 2 (cfio_ioreg_SC_USE_SEL_63_32_)—Offset 20h" on page 4597	00000000h
24–27h	4	"South Core Io Select 2 (cfio_ioreg_SC_IO_SEL_63_32_)—Offset 24h" on page 4598	00000000h
28–2Bh	4	"South Core Gpio Level 2 (cfio_ioreg_SC_GP_LVL_63_32_)—Offset 28h" on page 4599	00000000h
2C–2Fh	4	"South Core Trigger Positive Edge Enable 2 (cfio_ioreg_SC_TPE_63_32_)—Offset 2Ch" on page 4600	00000000h
30–33h	4	"South Core Trigger Negative Enable 2 (cfio_ioreg_SC_TNE_63_32_)—Offset 30h" on page 4601	00000000h
34–37h	4	"South Core Trigger Status 2 (cfio_ioreg_SC_TS_63_32_)—Offset 34h" on page 4602	00000000h
40–43h	4	"South Core Use Select 3 (cfio_ioreg_SC_USE_SEL_95_64_)—Offset 40h" on page 4603	00000000h
44–47h	4	"South Core Io Select 3 (cfio_ioreg_SC_IO_SEL_95_64_)—Offset 44h" on page 4604	00000000h
48–4Bh	4	"South Core Gpio Level 3 (cfio_ioreg_SC_GP_LVL_95_64_)—Offset 48h" on page 4605	00000000h
4C–4Fh	4	"South Core Trigger Positive Edge Enable 3 (cfio_ioreg_SC_TPE_95_64_)—Offset 4Ch" on page 4606	00000000h
50–53h	4	"South Core Trigger Negative Enable 3 (cfio_ioreg_SC_TNE_95_64_)—Offset 50h" on page 4607	00000000h
54–57h	4	"South Core Trigger Status 3 (cfio_ioreg_SC_TS_95_64_)—Offset 54h" on page 4608	00000000h
60–63h	4	"South Core Use Select 4 (cfio_ioreg_SC_USE_SEL_127_96_)—Offset 60h" on page 4609	00000000h
64–67h	4	"South Core Io Select 4 (cfio_ioreg_SC_IO_SEL_127_96_)—Offset 64h" on page 4610	00000000h
68–6Bh	4	"South Core Gpio Level 4 (cfio_ioreg_SC_GP_LVL_127_96_)—Offset 68h" on page 4610	00000000h

Table 339. Summary of PCU iLB GPIO S0 IO Registers—GPIO_BASE_ADDRESS

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
6C–6Fh	4	"South Core Trigger Positive Edge Enable 4 (cfio_ioreg_SC_TPE_127_96_)—Offset 6Ch" on page 4611	00000000h
70–73h	4	"South Core Trigger Negative Enable 4 (cfio_ioreg_SC_TNE_127_96_)—Offset 70h" on page 4612	00000000h
74–77h	4	"South Core Trigger Status 4 (cfio_ioreg_SC_TS_127_96_)—Offset 74h" on page 4612	00000000h

39.7.1 South Core Use Select 1 (cfio_ioreg_SC_USE_SEL_31_0_)—Offset 0h

Access via PCU proxy, the register is setting the corresponding GPIO to be selected and to be changed to IO access instead of the default Memory access. Bit 0 will set GPIO[0], and bit 1 will set GPIO[1] and so on. The default of IO GPIO pad is input so pull must be activated in the pad pconf0 register.

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 0h

GBASE Type: PCI Configuration Register (Size: 32 bits)**GBASE Reference:** [B:0, D:31, F:0] + 48h

Default: 00000000h

[illegible]





Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	To Select (io_sel): bit 31 - SDMMC2_D3_CD_B bit 30 - SDMMC2_D2 bit 29 - SDMMC2_D1 bit 28 - SDMMC2_D0 bit 27 - SDMMC2_CLK bit 26 - MMC1_RESET_B bit 25 - SDMMC1_CMD bit 24 - MMC1_D7 bit 23 - MMC1_D6 bit 22 - MMC1_D5 bit 21 - MMC1_D4_SD_WE bit 20 - SDMMC1_D3_CD_B bit 19 - SDMMC1_D2 bit 18 - SDMMC1_D1 bit 17 - SDMMC1_D0 bit 16 - SDMMC1_CLK bit 15 - HDA_DOCKENB bit 14 - HDA_DOCKRSTB bit 13 - HDA_SDI1 bit 12 - HDA_SDI0 bit 11 - HDA_SDO bit 10 - HDA_CLK bit 9 - HDA_SYNC bit 8 - HDA_RSTB bit 7 - PCIE_CLKREQ4B bit 6 - PCIE_CLKREQ3B bit 5 - PCIE_CLKREQ2B bit 4 - PCIE_CLKREQ1B bit 3 - PCIE_CLKREQ0B bit 2 - SATA_LEDN bit 1 - SATA_GP1 bit 0 - SATA_GP0

39.7.3 South Core Gpio Level 1 (cfio_ioreg_SC_GP_LVL_31_0_)—Offset 8h

Access via PCU proxy, the registers are implemented as dual read/write with dedicated storage for write. Write value will be stored in the write register, while read is coming from the pad directly. If GPIO(n) is programmed to be an output (via the corresponding bit in the GP_IO_SEL register), then the corresponding GP_LVL(n) write register value will drive a high or low value on the output pin. 1 = high, 0 = low. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 8h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

gp_lvl



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Gpio Level (gp_lvl): bit 31 - SDMMC2_D3_CD_B bit 30 - SDMMC2_D2 bit 29 - SDMMC2_D1 bit 28 - SDMMC2_D0 bit 27 - SDMMC2_CLK bit 26 - MMC1_RESET_B bit 25 - SDMMC1_CMD bit 24 - MMC1_D7 bit 23 - MMC1_D6 bit 22 - MMC1_D5 bit 21 - MMC1_D4_SD_WE bit 20 - SDMMC1_D3_CD_B bit 19 - SDMMC1_D2 bit 18 - SDMMC1_D1 bit 17 - SDMMC1_D0 bit 16 - SDMMC1_CLK bit 15 - HDA_DOCKENB bit 14 - HDA_DOCKRSTB bit 13 - HDA_SD11 bit 12 - HDA_SD10 bit 11 - HDA_SDO bit 10 - HDA_CLK bit 9 - HDA_SYNC bit 8 - HDA_RSTB bit 7 - PCIE_CLKREQ4B bit 6 - PCIE_CLKREQ3B bit 5 - PCIE_CLKREQ2B bit 4 - PCIE_CLKREQ1B bit 3 - PCIE_CLKREQ0B bit 2 - SATA_LEDN bit 1 - SATA_GP1 bit 0 - SATA_GP0

39.7.4 South Core Trigger Positive Edge Enable 1 (cfio_ioreg_SC_TPE_31_0_)—Offset Ch

Access via PCU proxy, it is trigger Positive Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 0 to 1 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 0 to 1 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + Ch

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Tpe (tpe): bit 31 - SDMMC2_D3_CD_B bit 30 - SDMMC2_D2 bit 29 - SDMMC2_D1 bit 28 - SDMMC2_D0 bit 27 - SDMMC2_CLK bit 26 - MMC1_RESET_B bit 25 - SDMMC1_CMD bit 24 - MMC1_D7 bit 23 - MMC1_D6 bit 22 - MMC1_D5 bit 21 - MMC1_D4_SD_WE bit 20 - SDMMC1_D3_CD_B bit 19 - SDMMC1_D2 bit 18 - SDMMC1_D1 bit 17 - SDMMC1_D0 bit 16 - SDMMC1_CLK bit 15 - HDA_DOCKENB bit 14 - HDA_DOCKRSTB bit 13 - HDA_SDI1 bit 12 - HDA_SDI0 bit 11 - HDA_SDO bit 10 - HDA_CLK bit 9 - HDA_SYNC bit 8 - HDA_RSTB bit 7 - PCIE_CLKREQ4B bit 6 - PCIE_CLKREQ3B bit 5 - PCIE_CLKREQ2B bit 4 - PCIE_CLKREQ1B bit 3 - PCIE_CLKREQ0B bit 2 - SATA_LEDN bit 1 - SATA_GP1 bit 0 - SATA_GP0

39.7.5 South Core Trigger Negative Enable 1 (cfio_ioreg_SC_TNE_31_0)—Offset 10h

Trigger Negative Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 1 to 0 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 1 to 0 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 10h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

tpe



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Tne (tne): bit 31 - SDMMC2_D3_CD_B bit 30 - SDMMC2_D2 bit 29 - SDMMC2_D1 bit 28 - SDMMC2_D0 bit 27 - SDMMC2_CLK bit 26 - MMC1_RESET_B bit 25 - SDMMC1_CMD bit 24 - MMC1_D7 bit 23 - MMC1_D6 bit 22 - MMC1_D5 bit 21 - MMC1_D4_SD_WE bit 20 - SDMMC1_D3_CD_B bit 19 - SDMMC1_D2 bit 18 - SDMMC1_D1 bit 17 - SDMMC1_D0 bit 16 - SDMMC1_CLK bit 15 - HDA_DOCKENB bit 14 - HDA_DOCKRSTB bit 13 - HDA_SD11 bit 12 - HDA_SDIO bit 11 - HDA_SDO bit 10 - HDA_CLK bit 9 - HDA_SYNC bit 8 - HDA_RSTB bit 7 - PCIE_CLKREQ4B bit 6 - PCIE_CLKREQ3B bit 5 - PCIE_CLKREQ2B bit 4 - PCIE_CLKREQ1B bit 3 - PCIE_CLKREQ0B bit 2 - SATA_LEDN bit 1 - SATA_GP1 bit 0 - SATA_GP0

39.7.6 South Core Trigger Status 1 (cfio_ioreg_SC_TS_31_0)—Offset 14h

Access via PCU proxy, when set to a 1, the corresponding GPIO (if enabled in the GPIO_USE_SEL register) if enabled as input via IO_SEL(n), triggered an GPE or SMI. This will be set if a 0 to 1 transition occurred and TPE(n) was set, or a 1 to 0 transition occurred and TNE(n) was set. If both TPE(n) and TNE(n) are set, then this bit will be set on both a 0 to 1 and a 1 to 0 transition. This bit will not be set if the GPIO is configured as an output. - Only the 8 lsb are used in VLV and it cannot be tested by the host

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 14h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 000000b WOC	ts: bit 31 - SDMMC2_D3_CD_B bit 30 - SDMMC2_D2 bit 29 - SDMMC2_D1 bit 28 - SDMMC2_D0 bit 27 - SDMMC2_CLK bit 26 - MMC1_RESET_B bit 25 - SDMMC1_CMD bit 24 - MMC1_D7 bit 23 - MMC1_D6 bit 22 - MMC1_D5 bit 21 - MMC1_D4_SD_WE bit 20 - SDMMC1_D3_CD_B bit 19 - SDMMC1_D2 bit 18 - SDMMC1_D1 bit 17 - SDMMC1_D0 bit 16 - SDMMC1_CLK bit 15 - HDA_DOCKENB bit 14 - HDA_DOCKRSTB bit 13 - HDA_SDI1 bit 12 - HDA_SDI0 bit 11 - HDA_SDO bit 10 - HDA_CLK bit 9 - HDA_SYNC bit 8 - HDA_RSTB bit 7 - PCIE_CLKREQ4B bit 6 - PCIE_CLKREQ3B bit 5 - PCIE_CLKREQ2B bit 4 - PCIE_CLKREQ1B bit 3 - PCIE_CLKREQ0B bit 2 - SATA_LEDN bit 1 - SATA_GP1 bit 0 - SATA_GP0

39.7.7 South Core Use Select 2 (cfio_ioreg_SC_USE_SEL_63_32_)—Offset 20h

Access via PCU proxy, the register is setting the corresponding GPIO to be selected and to be changed to IO access instead of the default Memory access. Bit 0 will set GPIO[32], and bit 1 will set GPIO[33] and so on. The default of IO GPIO pad is input so pull must be activated in the pad pconf0 register.

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 20h**GBASE Type:** PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Use Select (use_sel): bit 31 - GP_SSP_2_FS bit 30 - GP_SSP_2_CLK bit 29 - MHSI_CAREADY bit 28 - MHSI_CAFLAG bit 27 - MHSI_CADATA bit 26 - MHSI_ACWAKE bit 25 - MHSI_ACREADY bit 24 - MHSI_ACFLAG bit 23 - MHSI_ACDATA bit 22 - SPKR bit 21 - SMB_ALERTB bit 20 - SMB_CLK bit 19 - SMB_DATA bit 18 - ILB_SERIRQ bit 17 - LPC_CLKRUNB bit 16 - LPC_CLKOUT1 bit 15 - LPC_CLKOUT0 bit 14 - LPC_FRAMEB bit 13 - LPC_AD3 bit 12 - LPC_AD2 bit 11 - LPC_AD1 bit 10 - LPC_AD0 bit 9 - SDMMC3_PWR_EN_B bit 8 - SDMMC3_1P8_EN bit 7 - SDMMC3_CMD bit 6 - SDMMC3_CD_B bit 5 - SDMMC3_D3 bit 4 - SDMMC3_D2 bit 3 - SDMMC3_D1 bit 2 - SDMMC3_D0 bit 1 - SDMMC3_CLK bit 0 - SDMMC2_CMD

39.7.8 South Core Io Select 2 (cfio_ioreg_SC_IO_SEL_63_32_)—Offset 24h

Access via PCU proxy, define the Input Output Select: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) is programmed as an input. When set to 0, the GPIO signal is programmed as an output - Only the 8 lsb are used in VLV. Default values will be read as 0 if IO is not used

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 24h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

io_sel



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	To Select (io_sel): bit 31 - GP_SSP_2_FS bit 30 - GP_SSP_2_CLK bit 29 - MHSTI_CAREADY bit 28 - MHSTI_CAFLAG bit 27 - MHSTI_CADATA bit 26 - MHSTI_ACWAKE bit 25 - MHSTI_ACREADY bit 24 - MHSTI_ACFLAG bit 23 - MHSTI_ACDATA bit 22 - SPKR bit 21 - SMB_ALERTB bit 20 - SMB_CLK bit 19 - SMB_DATA bit 18 - ILB_SERIRQ bit 17 - LPC_CLKRUNB bit 16 - LPC_CLKOUT1 bit 15 - LPC_CLKOUT0 bit 14 - LPC_FRAMEB bit 13 - LPC_AD3 bit 12 - LPC_AD2 bit 11 - LPC_AD1 bit 10 - LPC_AD0 bit 9 - SDMMC3_PWR_EN_B bit 8 - SDMMC3_1P8_EN bit 7 - SDMMC3_CMD bit 6 - SDMMC3_CD_B bit 5 - SDMMC3_D3 bit 4 - SDMMC3_D2 bit 3 - SDMMC3_D1 bit 2 - SDMMC3_D0 bit 1 - SDMMC3_CLK bit 0 - SDMMC2_CMD

39.7.9 South Core Gpio Level 2 (cfio_ioreg_SC_GP_LVL_63_32_)—Offset 28h

Access via PCU proxy, the registers are implemented as dual read/write with dedicated storage for write. Write value will be stored in the write register, while read is coming from the pad directly. If GPIO(n) is programmed to be an output (via the corresponding bit in the GP_IO_SEL register), then the corresponding GP_LVL(n) write register value will drive a high or low value on the output pin. 1 = high, 0 = low. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 28h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

gp_lvl



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Gpio Level (gp_lvl): bit 31 - GP_SSP_2_FS bit 30 - GP_SSP_2_CLK bit 29 - MHSI_CAREADY bit 28 - MHSI_CAFLAG bit 27 - MHSI_CADATA bit 26 - MHSI_ACWAKE bit 25 - MHSI_ACREADY bit 24 - MHSI_ACFLAG bit 23 - MHSI_ACDATA bit 22 - SPKR bit 21 - SMB_ALERTB bit 20 - SMB_CLK bit 19 - SMB_DATA bit 18 - ILB_SERIRQ bit 17 - LPC_CLKRUNB bit 16 - LPC_CLKOUT1 bit 15 - LPC_CLKOUT0 bit 14 - LPC_FRAMEB bit 13 - LPC_AD3 bit 12 - LPC_AD2 bit 11 - LPC_AD1 bit 10 - LPC_AD0 bit 9 - SDMMC3_PWR_EN_B bit 8 - SDMMC3_1P8_EN bit 7 - SDMMC3_CMD bit 6 - SDMMC3_CD_B bit 5 - SDMMC3_D3 bit 4 - SDMMC3_D2 bit 3 - SDMMC3_D1 bit 2 - SDMMC3_D0 bit 1 - SDMMC3_CLK bit 0 - SDMMC2_CMD

39.7.10 South Core Trigger Positive Edge Enable 2 (cfio_ioreg_SC_TPE_63_32_)—Offset 2Ch

Access via PCU proxy, the register trigger Positive Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 0 to 1 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 0 to 1 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 2Ch

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Tpe (tpe): bit 31 - GP_SSP_2_FS bit 30 - GP_SSP_2_CLK bit 29 - MHSI_CAREADY bit 28 - MHSI_CAFLAG bit 27 - MHSI_CADATA bit 26 - MHSI_ACWAKE bit 25 - MHSI_ACREADY bit 24 - MHSI_ACFLAG bit 23 - MHSI_ACDATA bit 22 - SPKR bit 21 - SMB_ALERTB bit 20 - SMB_CLK bit 19 - SMB_DATA bit 18 - ILB_SERIRQ bit 17 - LPC_CLKRUNB bit 16 - LPC_CLKOUT1 bit 15 - LPC_CLKOUT0 bit 14 - LPC_FRAMEB bit 13 - LPC_AD3 bit 12 - LPC_AD2 bit 11 - LPC_AD1 bit 10 - LPC_AD0 bit 9 - SDMMC3_PWR_EN_B bit 8 - SDMMC3_1P8_EN bit 7 - SDMMC3_CMD bit 6 - SDMMC3_CD_B bit 5 - SDMMC3_D3 bit 4 - SDMMC3_D2 bit 3 - SDMMC3_D1 bit 2 - SDMMC3_D0 bit 1 - SDMMC3_CLK bit 0 - SDMMC2_CMD

39.7.11 South Core Trigger Negative Enable 2 (cfio_ioreg_SC_TNE_63_32_)—Offset 30h

Access via PCU proxy, the register trigger Negative Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 1 to 0 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 1 to 0 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 30h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

tne



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Tne (tne): bit 31 - GP_SSP_2_FS bit 30 - GP_SSP_2_CLK bit 29 - MHSI_CAREADY bit 28 - MHSI_CAFLAG bit 27 - MHSI_CADATA bit 26 - MHSI_ACWAKE bit 25 - MHSI_ACREADY bit 24 - MHSI_ACFLAG bit 23 - MHSI_ACDATA bit 22 - SPKR bit 21 - SMB_ALERTB bit 20 - SMB_CLK bit 19 - SMB_DATA bit 18 - ILB_SERIRQ bit 17 - LPC_CLKRUNB bit 16 - LPC_CLKOUT1 bit 15 - LPC_CLKOUT0 bit 14 - LPC_FRAMEB bit 13 - LPC_AD3 bit 12 - LPC_AD2 bit 11 - LPC_AD1 bit 10 - LPC_AD0 bit 9 - SDMMC3_PWR_EN_B bit 8 - SDMMC3_1P8_EN bit 7 - SDMMC3_CMD bit 6 - SDMMC3_CD_B bit 5 - SDMMC3_D3 bit 4 - SDMMC3_D2 bit 3 - SDMMC3_D1 bit 2 - SDMMC3_D0 bit 1 - SDMMC3_CLK bit 0 - SDMMC2_CMD

39.7.12 South Core Trigger Status 2 (cfio_ioreg_SC_TS_63_32_)—Offset 34h

When set to a 1, the corresponding GPIO (if enabled in the GPIO_USE_SEL register) if enabled as input via IO_SEL(n), triggered an GPE or SMI. This will be set if a 0 to 1 transition occurred and TPE(n) was set, or a 1 to 0 transition occurred and TNE(n) was set. If both TPE(n) and TNE(n) are set, then this bit will be set on both a 0 to 1 and a 1 to 0 transition. This bit will not be set if the GPIO is configured as an output. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 34h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Use Select (use_sel): bit 31 - PWM1 bit 30 - PWM0 bit 29 - I2C_NFC_SCL bit 28 - I2C_NFC_SDA bit 27 - I2C6_SCL bit 26 - I2C6_SDA bit 25 - I2C5_SCL bit 24 - I2C5_SDA bit 23 - I2C4_SCL bit 22 - I2C4_SDA bit 21 - I2C3_SCL bit 20 - I2C3_SDA bit 19 - I2C2_SCL bit 18 - I2C2_SDA bit 17 - I2C1_SCL bit 16 - I2C1_SDA bit 15 - I2C0_SCL bit 14 - I2C0_SDA bit 13 - UART2_CTS_B bit 12 - UART2_RTS_B bit 11 - UART2_TXD bit 10 - UART2_RXD bit 9 - UART1_CTS_B bit 8 - UART1_RTS_B bit 7 - UART1_TXD bit 6 - UART1_RXD bit 5 - SPI1_CLK bit 4 - SPI1_MOSI bit 3 - SPI1_MISO bit 2 - SPI1_CS0_B bit 1 - GP_SSP_2_TXD bit 0 - GP_SSP_2_RXD

39.7.14 South Core Io Select 3 (cfio_ioreg_SC_IO_SEL_95_64_)—Offset 44h

Access via PCU proxy, it defines Input Output Select: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) is programmed as an input. When set to 0, the GPIO signal is programmed as an output - Only the 8 lsb are used in VLV. Default values will be read as 0 if IO is not used

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 44h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

io_sel



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	To Select (io_sel): bit 31 - PWM1 bit 30 - PWM0 bit 29 - I2C_NFC_SCL bit 28 - I2C_NFC_SDA bit 27 - I2C6_SCL bit 26 - I2C6_SDA bit 25 - I2C5_SCL bit 24 - I2C5_SDA bit 23 - I2C4_SCL bit 22 - I2C4_SDA bit 21 - I2C3_SCL bit 20 - I2C3_SDA bit 19 - I2C2_SCL bit 18 - I2C2_SDA bit 17 - I2C1_SCL bit 16 - I2C1_SDA bit 15 - I2C0_SCL bit 14 - I2C0_SDA bit 13 - UART2_CTS_B bit 12 - UART2_RTS_B bit 11 - UART2_TXD bit 10 - UART2_RXD bit 9 - UART1_CTS_B bit 8 - UART1_RTS_B bit 7 - UART1_TXD bit 6 - UART1_RXD bit 5 - SPI1_CLK bit 4 - SPI1_MOSI bit 3 - SPI1_MISO bit 2 - SPI1_CS0_B bit 1 - GP_SSP_2_TXD bit 0 - GP_SSP_2_RXD

39.7.15 South Core Gpio Level 3 (cfio_ioreg_SC_GP_LVL_95_64_)—Offset 48h

This registers are implemented as dual read/write with dedicated storage for write. Write value will be stored in the write register, while read is coming from the pad directly. If GPIO(n) is programmed to be an output (via the corresponding bit in the GP_IO_SEL register), then the corresponding GP_LVL(n) write register value will drive a high or low value on the output pin. 1 = high, 0 = low. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 48h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

gp_lvl



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Gpio Level (gp_lvl): bit 31 - PWM1 bit 30 - PWM0 bit 29 - I2C_NFC_SCL bit 28 - I2C_NFC_SDA bit 27 - I2C6_SCL bit 26 - I2C6_SDA bit 25 - I2C5_SCL bit 24 - I2C5_SDA bit 23 - I2C4_SCL bit 22 - I2C4_SDA bit 21 - I2C3_SCL bit 20 - I2C3_SDA bit 19 - I2C2_SCL bit 18 - I2C2_SDA bit 17 - I2C1_SCL bit 16 - I2C1_SDA bit 15 - I2C0_SCL bit 14 - I2C0_SDA bit 13 - UART2_CTS_B bit 12 - UART2_RTS_B bit 11 - UART2_TXD bit 10 - UART2_RXD bit 9 - UART1_CTS_B bit 8 - UART1_RTS_B bit 7 - UART1_TXD bit 6 - UART1_RXD bit 5 - SPI1_CLK bit 4 - SPI1_MOSI bit 3 - SPI1_MISO bit 2 - SPI1_CS0_B bit 1 - GP_SSP_2_TXD bit 0 - GP_SSP_2_RXD

39.7.16 South Core Trigger Positive Edge Enable 3 (cfio_ioreg_SC_TPE_95_64_)—Offset 4Ch

Access via PCU proxy, the register trigger Positive Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 0 to 1 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 0 to 1 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 4Ch

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Tpe (tpe): bit 31 - PWM1 bit 30 - PWM0 bit 29 - I2C_NFC_SCL bit 28 - I2C_NFC_SDA bit 27 - I2C6_SCL bit 26 - I2C6_SDA bit 25 - I2C5_SCL bit 24 - I2C5_SDA bit 23 - I2C4_SCL bit 22 - I2C4_SDA bit 21 - I2C3_SCL bit 20 - I2C3_SDA bit 19 - I2C2_SCL bit 18 - I2C2_SDA bit 17 - I2C1_SCL bit 16 - I2C1_SDA bit 15 - I2C0_SCL bit 14 - I2C0_SDA bit 13 - UART2_CTS_B bit 12 - UART2_RTS_B bit 11 - UART2_TXD bit 10 - UART2_RXD bit 9 - UART1_CTS_B bit 8 - UART1_RTS_B bit 7 - UART1_TXD bit 6 - UART1_RXD bit 5 - SPI1_CLK bit 4 - SPI1_MOSI bit 3 - SPI1_MISO bit 2 - SPI1_CS0_B bit 1 - GP_SSP_2_TXD bit 0 - GP_SSP_2_RXD

39.7.17 South Core Trigger Negative Enable 3 (cfio_ioreg_SC_TNE_95_64_)—Offset 50h

Access via PCU proxy, the register trigger Negative Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 1 to 0 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 1 to 0 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 50h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

tne



Bit Range	Default & Access	Field Name (ID): Description
31:0	000000000 000000000 000000000 00000b RW	Tne (tne): bit 31 - PWM1 bit 30 - PWM0 bit 29 - I2C_NFC_SCL bit 28 - I2C_NFC_SDA bit 27 - I2C6_SCL bit 26 - I2C6_SDA bit 25 - I2C5_SCL bit 24 - I2C5_SDA bit 23 - I2C4_SCL bit 22 - I2C4_SDA bit 21 - I2C3_SCL bit 20 - I2C3_SDA bit 19 - I2C2_SCL bit 18 - I2C2_SDA bit 17 - I2C1_SCL bit 16 - I2C1_SDA bit 15 - I2C0_SCL bit 14 - I2C0_SDA bit 13 - UART2_CTS_B bit 12 - UART2_RTS_B bit 11 - UART2_TXD bit 10 - UART2_RXD bit 9 - UART1_CTS_B bit 8 - UART1_RTS_B bit 7 - UART1_TXD bit 6 - UART1_RXD bit 5 - SPI1_CLK bit 4 - SPI1_MOSI bit 3 - SPI1_MISO bit 2 - SPI1_CS0_B bit 1 - GP_SSP_2_TXD bit 0 - GP_SSP_2_RXD

39.7.18 South Core Trigger Status 3 (cfio_ioreg_SC_TS_95_64_)—Offset 54h

When set to a 1, the corresponding GPIO (if enabled in the GPIO_USE_SEL register) if enabled as input via IO_SEL(n), triggered an GPE or SMI. This will be set if a 0 to 1 transition occurred and TPE(n) was set, or a 1 to 0 transition occurred and TNE(n) was set. If both TPE(n) and TNE(n) are set, then this bit will be set on both a 0 to 1 and a 1 to 0 transition. This bit will not be set if the GPIO is configured as an output. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 54h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

39.7.20 South Core Io Select 4 (cfio_ioreg_SC_IO_SEL_127_96_)—Offset 64h

Bit Range	Default & Access	Field Name (ID): Description
31:6	000000000 000000000 00000000b RO	Reserved (reserved): reserved
5:0	0b RW	Use Select (use_sel): bit 5 - PLT_CLK5 bit 4 - PLT_CLK4 bit 3 - PLT_CLK3 bit 2 - PLT_CLK2 bit 1 - PLT_CLK1 bit 0 - PLT_CLK0

Access via PCU proxy, it defines Input Output Select: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) is programmed as an input. When set to 0, the GPIO signal is programmed as an output - Only the 8 lsb are used in VLV. Default values will be read as 0 if IO is not used

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 64h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved							io_sel	

Bit Range	Default & Access	Field Name (ID): Description
31:6	000000000 000000000 00000000b RO	Reserved (reserved): reserved
5:0	0b RW	Io Select (io_sel): bit 5 - PLT_CLK5 bit 4 - PLT_CLK4 bit 3 - PLT_CLK3 bit 2 - PLT_CLK2 bit 1 - PLT_CLK1 bit 0 - PLT_CLK0

39.7.21 South Core Gpio Level 4 (cfio_ioreg_SC_GP_LVL_127_96_)—Offset 68h

This registers are implemented as dual read/write with dedicated storage for write. Write value will be stored in the write register, while read is coming from the pad directly. If GPIO(n) is programmed to be an output (via the corresponding bit in the GP_IO_SEL register), then the corresponding GP_LVL(n) write register value will drive a high or low value on the output pin. 1 = high, 0 = low. - Only the 8 lsb are used in VLV



Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 68h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved							gp_lvl	

Bit Range	Default & Access	Field Name (ID): Description
31:6	000000000 000000000 00000000b RO	Reserved (reserved): reserved
5:0	0b RW	Gpio Level (gp_lvl): bit 5 - PLT_CLK5 bit 4 - PLT_CLK4 bit 3 - PLT_CLK3 bit 2 - PLT_CLK2 bit 1 - PLT_CLK1 bit 0 - PLT_CLK0

39.7.22 South Core Trigger Positive Edge Enable 4 (cfio_ioreg_SC_TPE_127_96_)—Offset 6Ch

Access via PCU proxy, the register trigger Positive Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 0 to 1 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 0 to 1 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 6Ch

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved							tpe	

Bit Range	Default & Access	Field Name (ID): Description
31:6	000000000 000000000 00000000b RO	Reserved (reserved): reserved



Bit Range	Default & Access	Field Name (ID): Description
5:0	0b RW	Tpe (tpe): bit 5 - PLT_CLK5 bit 4 - PLT_CLK4 bit 3 - PLT_CLK3 bit 2 - PLT_CLK2 bit 1 - PLT_CLK1 bit 0 - PLT_CLK0

39.7.23 South Core Trigger Negative Enable 4 (cfio_ioreg_SC_TNE_127_96)—Offset 70h

Access via PCU proxy, the register trigger Negative Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 1 to 0 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 1 to 0 transition. - Only the 8 lsb are used in VLV

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE] + 70h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved							the	

Bit Range	Default & Access	Field Name (ID): Description
31:6	000000000 000000000 00000000b RO	Reserved (reserved): reserved
5:0	0b RW	Tne (tne): bit 5 - PLT_CLK5 bit 4 - PLT_CLK4 bit 3 - PLT_CLK3 bit 2 - PLT_CLK2 bit 1 - PLT_CLK1 bit 0 - PLT_CLK0

39.7.24 South Core Trigger Status 4 (cfio_ioreg_SC_TS_127_96_)—Offset 74h

When set to a 1, the corresponding GPIO (if enabled in the GPIO_USE_SEL register) if enabled as input via IO_SEL(n), triggered an GPE or SMI. This will be set if a 0 to 1 transition occurred and TPE(n) was set, or a 1 to 0 transition occurred and TNE(n) was set. If both TPE(n) and TNE(n) are set, then this bit will be set on both a 0 to 1 and a 1 to 0 transition. This bit will not be set if the GPIO is configured as an output. - Only the 8 lsb are used in VLV

Access Method



39.8 PCU iLB GPIO S0 Memory Addressed Registers

Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"Uart1 Rts B Pad Configuration (cfio_regs_pad_uart1_rts_b_PCONF0)—Offset 0h" on page 4627	2003CC80h
8–Bh	4	"Uart1 Rts B Pad Value (cfio_regs_pad_uart1_rts_b_PAD_VAL)—Offset 8h" on page 4629	00000002h
10–13h	4	"Uart1 Txd Pad Configuration (cfio_regs_pad_uart1_txd_PCONF0)—Offset 10h" on page 4630	2003CC80h
18–1Bh	4	"Uart1 Txd Pad Value (cfio_regs_pad_uart1_txd_PAD_VAL)—Offset 18h" on page 4632	00000002h
20–23h	4	"Uart1 Rxd Pad Configuration (cfio_regs_pad_uart1_rxd_PCONF0)—Offset 20h" on page 4633	2003CC80h
28–2Bh	4	"Uart1 Rxd Pad Value (cfio_regs_pad_uart1_rxd_PAD_VAL)—Offset 28h" on page 4636	00000002h
30–33h	4	"I2c Nfc Scl Pad Configuration (cfio_regs_pad_i2c_nfc_scl_PCONF0)—Offset 30h" on page 4636	2003CC80h
38–3Bh	4	"I2c Nfc Scl Pad Value (cfio_regs_pad_i2c_nfc_scl_PAD_VAL)—Offset 38h" on page 4639	00000002h
40–43h	4	"Uart1 Cts B Pad Configuration (cfio_regs_pad_uart1_cts_b_PCONF0)—Offset 40h" on page 4639	2003CC80h
48–4Bh	4	"Uart1 Cts B Pad Value (cfio_regs_pad_uart1_cts_b_PAD_VAL)—Offset 48h" on page 4642	00000002h
50–53h	4	"I2c Nfc Sda Pad Configuration (cfio_regs_pad_i2c_nfc_sda_PCONF0)—Offset 50h" on page 4643	2003CC80h
58–5Bh	4	"I2c Nfc Sda Pad Value (cfio_regs_pad_i2c_nfc_sda_PAD_VAL)—Offset 58h" on page 4645	00000002h
60–63h	4	"Uart2 Rxd Pad Configuration (cfio_regs_pad_uart2_rxd_PCONF0)—Offset 60h" on page 4646	2003CC80h
68–6Bh	4	"Uart2 Rxd Pad Value (cfio_regs_pad_uart2_rxd_PAD_VAL)—Offset 68h" on page 4648	00000002h
70–73h	4	"Uart2 Txd Pad Configuration (cfio_regs_pad_uart2_txd_PCONF0)—Offset 70h" on page 4649	2003CC80h
78–7Bh	4	"Uart2 Txd Pad Value (cfio_regs_pad_uart2_txd_PAD_VAL)—Offset 78h" on page 4652	00000002h
80–83h	4	"Uart2 Cts B Pad Configuration (cfio_regs_pad_uart2_cts_b_PCONF0)—Offset 80h" on page 4652	2003CC80h
88–8Bh	4	"Uart2 Cts B Pad Value (cfio_regs_pad_uart2_cts_b_PAD_VAL)—Offset 88h" on page 4655	00000002h
90–93h	4	"Uart2 Rts B Pad Configuration (cfio_regs_pad_uart2_rts_b_PCONF0)—Offset 90h" on page 4655	2003CC80h
98–9Bh	4	"Uart2 Rts B Pad Value (cfio_regs_pad_uart2_rts_b_PAD_VAL)—Offset 98h" on page 4658	00000002h
A0–A3h	4	"Pwm0 Pad Configuration (cfio_regs_pad_pwm0_PCONF0)—Offset A0h" on page 4659	2003CD00h
A8–ABh	4	"Pwm0 Pad Value (cfio_regs_pad_pwm0_PAD_VAL)—Offset A8h" on page 4661	00000002h
B0–B3h	4	"Pwm1 Pad Configuration (cfio_regs_pad_pwm1_PCONF0)—Offset B0h" on page 4662	2003CD00h
B8–BBh	4	"Pwm1 Pad Value (cfio_regs_pad_pwm1_PAD_VAL)—Offset B8h" on page 4664	00000002h



Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
C0–C3h	4	"Gp Ssp 2 Fs Pad Configuration (cfio_regs_pad_gp_ssp_2_fs_PCONF0)—Offset C0h" on page 4665	2003CC80h
C8–CBh	4	"Gp Ssp 2 Fs Pad Value (cfio_regs_pad_gp_ssp_2_fs_PAD_VAL)—Offset C8h" on page 4667	00000002h
D0–D3h	4	"Gp Ssp 2 Clk Pad Configuration (cfio_regs_pad_gp_ssp_2_clk_PCONF0)—Offset D0h" on page 4668	2003CD00h
D8–DBh	4	"Gp Ssp 2 Clk Pad Value (cfio_regs_pad_gp_ssp_2_clk_PAD_VAL)—Offset D8h" on page 4671	00000002h
E0–E3h	4	"Gp Ssp 2 Txd Pad Configuration (cfio_regs_pad_gp_ssp_2_txd_PCONF0)—Offset E0h" on page 4671	2003CC80h
E8–EBh	4	"Gp Ssp 2 Txd Pad Value (cfio_regs_pad_gp_ssp_2_txd_PAD_VAL)—Offset E8h" on page 4674	00000002h
F0–F3h	4	"Gp Ssp 2 Rxd Pad Configuration (cfio_regs_pad_gp_ssp_2_rxd_PCONF0)—Offset F0h" on page 4674	2003CD00h
F8–FBh	4	"Gp Ssp 2 Rxd Pad Value (cfio_regs_pad_gp_ssp_2_rxd_PAD_VAL)—Offset F8h" on page 4677	00000002h
100–103h	4	"Spi1 Clk Pad Configuration (cfio_regs_pad_spi1_clk_PCONF0)—Offset 100h" on page 4678	2003CD00h
108–10Bh	4	"Spi1 Clk Pad Value (cfio_regs_pad_spi1_clk_PAD_VAL)—Offset 108h" on page 4680	00000002h
110–113h	4	"Spi1 Cs0 B Pad Configuration (cfio_regs_pad_spi1_cs0_b_PCONF0)—Offset 110h" on page 4681	2003CC80h
118–11Bh	4	"Spi1 Cs0 B Pad Value (cfio_regs_pad_spi1_cs0_b_PAD_VAL)—Offset 118h" on page 4683	00000002h
120–123h	4	"Spi1 Miso Pad Configuration (cfio_regs_pad_spi1_miso_PCONF0)—Offset 120h" on page 4684	2003CC80h
128–12Bh	4	"Spi1 Miso Pad Value (cfio_regs_pad_spi1_miso_PAD_VAL)—Offset 128h" on page 4687	00000002h
130–133h	4	"Spi1 Mosi Pad Configuration (cfio_regs_pad_spi1_mosi_PCONF0)—Offset 130h" on page 4687	2003CC80h
138–13Bh	4	"Spi1 Mosi Pad Value (cfio_regs_pad_spi1_mosi_PAD_VAL)—Offset 138h" on page 4690	00000002h
140–143h	4	"I2c5 Scl Pad Configuration (cfio_regs_pad_i2c5_scl_PCONF0)—Offset 140h" on page 4690	2003CC80h
148–14Bh	4	"I2c5 Scl Pad Value (cfio_regs_pad_i2c5_scl_PAD_VAL)—Offset 148h" on page 4693	00000002h
150–153h	4	"I2c5 Sda Pad Configuration (cfio_regs_pad_i2c5_sda_PCONF0)—Offset 150h" on page 4694	2003CC80h
158–15Bh	4	"I2c5 Sda Pad Value (cfio_regs_pad_i2c5_sda_PAD_VAL)—Offset 158h" on page 4696	00000002h
160–163h	4	"I2c6 Scl Pad Configuration (cfio_regs_pad_i2c6_scl_PCONF0)—Offset 160h" on page 4697	2003CC80h
168–16Bh	4	"I2c6 Scl Pad Value (cfio_regs_pad_i2c6_scl_PAD_VAL)—Offset 168h" on page 4699	00000002h
170–173h	4	"I2c4 Scl Pad Configuration (cfio_regs_pad_i2c4_scl_PCONF0)—Offset 170h" on page 4700	2003CC80h
178–17Bh	4	"I2c4 Scl Pad Value (cfio_regs_pad_i2c4_scl_PAD_VAL)—Offset 178h" on page 4703	00000002h



Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—IOWBASE (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
180–183h	4	"I2c6 Sda Pad Configuration (cfio_regs_pad_i2c6_sda_PCONF0)—Offset 180h" on page 4703	2003CC80h
188–18Bh	4	"I2c6 Sda Pad Value (cfio_regs_pad_i2c6_sda_PAD_VAL)—Offset 188h" on page 4706	00000002h
190–193h	4	"I2c3 Sda Pad Configuration (cfio_regs_pad_i2c3_sda_PCONF0)—Offset 190h" on page 4706	2003CC80h
198–19Bh	4	"I2c3 Sda Pad Value (cfio_regs_pad_i2c3_sda_PAD_VAL)—Offset 198h" on page 4709	00000002h
1A0–1A3h	4	"I2c4 Sda Pad Configuration (cfio_regs_pad_i2c4_sda_PCONF0)—Offset 1A0h" on page 4710	2003CC80h
1A8–1ABh	4	"I2c4 Sda Pad Value (cfio_regs_pad_i2c4_sda_PAD_VAL)—Offset 1A8h" on page 4712	00000002h
1B0–1B3h	4	"I2c2 Scl Pad Configuration (cfio_regs_pad_i2c2_scl_PCONF0)—Offset 1B0h" on page 4713	2003CC80h
1B8–1BBh	4	"I2c2 Scl Pad Value (cfio_regs_pad_i2c2_scl_PAD_VAL)—Offset 1B8h" on page 4715	00000002h
1C0–1C3h	4	"I2c3 Scl Pad Configuration (cfio_regs_pad_i2c3_scl_PCONF0)—Offset 1C0h" on page 4716	2003CC80h
1C8–1CBh	4	"I2c3 Scl Pad Value (cfio_regs_pad_i2c3_scl_PAD_VAL)—Offset 1C8h" on page 4719	00000002h
1D0–1D3h	4	"I2c2 Sda Pad Configuration (cfio_regs_pad_i2c2_sda_PCONF0)—Offset 1D0h" on page 4719	2003CC80h
1D8–1DBh	4	"I2c2 Sda Pad Value (cfio_regs_pad_i2c2_sda_PAD_VAL)—Offset 1D8h" on page 4722	00000002h
1E0–1E3h	4	"I2c1 Scl Pad Configuration (cfio_regs_pad_i2c1_scl_PCONF0)—Offset 1E0h" on page 4722	2003CC80h
1E8–1EBh	4	"I2c1 Scl Pad Value (cfio_regs_pad_i2c1_scl_PAD_VAL)—Offset 1E8h" on page 4725	00000002h
1F0–1F3h	4	"I2c1 Sda Pad Configuration (cfio_regs_pad_i2c1_sda_PCONF0)—Offset 1F0h" on page 4726	2003CC80h
1F8–1FBh	4	"I2c1 Sda Pad Value (cfio_regs_pad_i2c1_sda_PAD_VAL)—Offset 1F8h" on page 4728	00000002h
200–203h	4	"I2c0 Scl Pad Configuration (cfio_regs_pad_i2c0_scl_PCONF0)—Offset 200h" on page 4729	2003CC80h
208–20Bh	4	"I2c0 Scl Pad Value (cfio_regs_pad_i2c0_scl_PAD_VAL)—Offset 208h" on page 4731	00000002h
210–213h	4	"I2c0 Sda Pad Configuration (cfio_regs_pad_i2c0_sda_PCONF0)—Offset 210h" on page 4732	2003CC80h
218–21Bh	4	"I2c0 Sda Pad Value (cfio_regs_pad_i2c0_sda_PAD_VAL)—Offset 218h" on page 4735	00000002h
220–223h	4	"Hda Rstb Pad Configuration (cfio_regs_pad_hda_rstb_PCONF0)—Offset 220h" on page 4735	2003ED00h
228–22Bh	4	"Hda Rstb Pad Value (cfio_regs_pad_hda_rstb_PAD_VAL)—Offset 228h" on page 4738	00000002h
230–233h	4	"Hda Sdi1 Pad Configuration (cfio_regs_pad_hda_sdi1_PCONF0)—Offset 230h" on page 4738	2003ED00h
238–23Bh	4	"Hda Sdi1 Pad Value (cfio_regs_pad_hda_sdi1_PAD_VAL)—Offset 238h" on page 4741	00000002h

**Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
240–243h	4	"Hda Clk Pad Configuration (cfio_regs_pad_hda_clk_PCONF0)—Offset 240h" on page 4742	2003ED00h
248–24Bh	4	"Hda Clk Pad Value (cfio_regs_pad_hda_clk_PAD_VAL)—Offset 248h" on page 4744	00000002h
250–253h	4	"Hda Sync Pad Configuration (cfio_regs_pad_hda_sync_PCONF0)—Offset 250h" on page 4745	2003ED00h
258–25Bh	4	"Hda Sync Pad Value (cfio_regs_pad_hda_sync_PAD_VAL)—Offset 258h" on page 4747	00000002h
260–263h	4	"Hda Sdo Pad Configuration (cfio_regs_pad_hda_sdo_PCONF0)—Offset 260h" on page 4748	2003ED00h
268–26Bh	4	"Hda Sdo Pad Value (cfio_regs_pad_hda_sdo_PAD_VAL)—Offset 268h" on page 4751	00000002h
270–273h	4	"Hda Sdio Pad Configuration (cfio_regs_pad_hda_sdio_PCONF0)—Offset 270h" on page 4751	2003ED00h
278–27Bh	4	"Hda Sdio Pad Value (cfio_regs_pad_hda_sdio_PAD_VAL)—Offset 278h" on page 4754	00000002h
280–283h	4	"Hda Dockrstb Pad Configuration (cfio_regs_pad_hda_dockrstb_PCONF0)—Offset 280h" on page 4754	2003ED00h
288–28Bh	4	"Hda Dockrstb Pad Value (cfio_regs_pad_hda_dockrstb_PAD_VAL)—Offset 288h" on page 4757	00000002h
290–293h	4	"Sdmmc3 D1 Pad Configuration (cfio_regs_pad_sdmmc3_d1_PCONF0)—Offset 290h" on page 4758	20038C80h
298–29Bh	4	"Sdmmc3 D1 Pad Value (cfio_regs_pad_sdmmc3_d1_PAD_VAL)—Offset 298h" on page 4760	00000002h
2A0–2A3h	4	"Sdmmc3 D3 Pad Configuration (cfio_regs_pad_sdmmc3_d3_PCONF0)—Offset 2A0h" on page 4761	20038C80h
2A8–2ABh	4	"Sdmmc3 D3 Pad Value (cfio_regs_pad_sdmmc3_d3_PAD_VAL)—Offset 2A8h" on page 4763	00000002h
2B0–2B3h	4	"Sdmmc3 Clk Pad Configuration (cfio_regs_pad_sdmmc3_clk_PCONF0)—Offset 2B0h" on page 4763	20038D00h
2B4–2B7h	4	"Sdmmc3 Clk Delay Line Multiplexer (cfio_regs_pad_sdmmc3_clk_PCONF1)—Offset 2B4h" on page 4765	00008000h
2B8–2BBh	4	"Sdmmc3 Clk Pad Value (cfio_regs_pad_sdmmc3_clk_PAD_VAL)—Offset 2B8h" on page 4766	00000002h
2C0–2C3h	4	"Sdmmc3 Cmd Pad Configuration (cfio_regs_pad_sdmmc3_cmd_PCONF0)—Offset 2C0h" on page 4767	20038C80h
2C8–2CBh	4	"Sdmmc3 Cmd Pad Value (cfio_regs_pad_sdmmc3_cmd_PAD_VAL)—Offset 2C8h" on page 4769	00000002h
2D0–2D3h	4	"Sdmmc3 D2 Pad Configuration (cfio_regs_pad_sdmmc3_d2_PCONF0)—Offset 2D0h" on page 4770	20038C80h
2D8–2DBh	4	"Sdmmc3 D2 Pad Value (cfio_regs_pad_sdmmc3_d2_PAD_VAL)—Offset 2D8h" on page 4772	00000002h
2E0–2E3h	4	"Sdmmc3 D0 Pad Configuration (cfio_regs_pad_sdmmc3_d0_PCONF0)—Offset 2E0h" on page 4772	20038C80h
2E8–2EBh	4	"Sdmmc3 D0 Pad Value (cfio_regs_pad_sdmmc3_d0_PAD_VAL)—Offset 2E8h" on page 4774	00000002h
2F0–2F3h	4	"Sdmmc2 D1 Pad Configuration (cfio_regs_pad_sdmmc2_d1_PCONF0)—Offset 2F0h" on page 4775	2003EC80h




Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
2F8–2FBh	4	"Sdmmc2 D1 Pad Value (cfio_regs_pad_sdmmc2_d1_PAD_VAL)—Offset 2F8h" on page 4778	00000002h
300–303h	4	"Sdmmc2 Cmd Pad Configuration (cfio_regs_pad_sdmmc2_cmd_PCONF0)—Offset 300h" on page 4778	2003EC80h
308–30Bh	4	"Sdmmc2 Cmd Pad Value (cfio_regs_pad_sdmmc2_cmd_PAD_VAL)—Offset 308h" on page 4781	00000002h
310–313h	4	"Sdmmc2 D3 Cd B Pad Configuration (cfio_regs_pad_sdmmc2_d3_cd_b_PCONF0)—Offset 310h" on page 4781	2003EC80h
318–31Bh	4	"Sdmmc2 D3 Cd B Pad Value (cfio_regs_pad_sdmmc2_d3_cd_b_PAD_VAL)—Offset 318h" on page 4784	00000002h
320–323h	4	"Sdmmc2 Clk Pad Configuration (cfio_regs_pad_sdmmc2_clk_PCONF0)—Offset 320h" on page 4785	2003ED00h
324–327h	4	"Sdmmc2 Clk Delay Line Multiplexer (cfio_regs_pad_sdmmc2_clk_PCONF1)—Offset 324h" on page 4787	00008000h
328–32Bh	4	"Sdmmc2 Clk Pad Value (cfio_regs_pad_sdmmc2_clk_PAD_VAL)—Offset 328h" on page 4788	00000002h
330–333h	4	"Mmc1 Reset B Pad Configuration (cfio_regs_pad_mmc1_reset_b_PCONF0)—Offset 330h" on page 4788	2003ED00h
338–33Bh	4	"Mmc1 Reset B Pad Value (cfio_regs_pad_mmc1_reset_b_PAD_VAL)—Offset 338h" on page 4791	00000002h
340–343h	4	"Sdmmc2 D2 Pad Configuration (cfio_regs_pad_sdmmc2_d2_PCONF0)—Offset 340h" on page 4791	2003EC80h
348–34Bh	4	"Sdmmc2 D2 Pad Value (cfio_regs_pad_sdmmc2_d2_PAD_VAL)—Offset 348h" on page 4794	00000002h
350–353h	4	"Sdmmc2 D0 Pad Configuration (cfio_regs_pad_sdmmc2_d0_PCONF0)—Offset 350h" on page 4795	2003EC80h
358–35Bh	4	"Sdmmc2 D0 Pad Value (cfio_regs_pad_sdmmc2_d0_PAD_VAL)—Offset 358h" on page 4797	00000002h
360–363h	4	"Sdmmc1 D3 Cd B Pad Configuration (cfio_regs_pad_sdmmc1_d3_cd_b_PCONF0)—Offset 360h" on page 4798	2003EC80h
368–36Bh	4	"Sdmmc1 D3 Cd B Pad Value (cfio_regs_pad_sdmmc1_d3_cd_b_PAD_VAL)—Offset 368h" on page 4800	00000002h
370–373h	4	"Mmc1 D6 Pad Configuration (cfio_regs_pad_mmc1_d6_PCONF0)—Offset 370h" on page 4801	2003EC80h
378–37Bh	4	"Mmc1 D6 Pad Value (cfio_regs_pad_mmc1_d6_PAD_VAL)—Offset 378h" on page 4804	00000002h
380–383h	4	"Mmc1 D4 Sd We Pad Configuration (cfio_regs_pad_mmc1_d4_sd_we_PCONF0)—Offset 380h" on page 4804	2003EC80h
388–38Bh	4	"Mmc1 D4 Sd We Pad Value (cfio_regs_pad_mmc1_d4_sd_we_PAD_VAL)—Offset 388h" on page 4807	00000002h
390–393h	4	"Sdmmc1 Cmd Pad Configuration (cfio_regs_pad_sdmmc1_cmd_PCONF0)—Offset 390h" on page 4807	2003EC80h
398–39Bh	4	"Sdmmc1 Cmd Pad Value (cfio_regs_pad_sdmmc1_cmd_PAD_VAL)—Offset 398h" on page 4810	00000002h
3A0–3A3h	4	"Sdmmc3 Cd B Pad Configuration (cfio_regs_pad_sdmmc3_cd_b_PCONF0)—Offset 3A0h" on page 4811	2003CC80h
3A8–3ABh	4	"Sdmmc3 Cd B Pad Value (cfio_regs_pad_sdmmc3_cd_b_PAD_VAL)—Offset 3A8h" on page 4813	00000002h



Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
3B0–3B3h	4	"Sdmmc1 D2 Pad Configuration (cfio_regs_pad_sdmmc1_d2_PCONF0)—Offset 3B0h" on page 4814	2003EC80h
3B8–3BBh	4	"Sdmmc1 D2 Pad Value (cfio_regs_pad_sdmmc1_d2_PAD_VAL)—Offset 3B8h" on page 4816	00000002h
3C0–3C3h	4	"Mmc1 D5 Pad Configuration (cfio_regs_pad_mmc1_d5_PCONF0)—Offset 3C0h" on page 4817	2003EC80h
3C8–3CBh	4	"Mmc1 D5 Pad Value (cfio_regs_pad_mmc1_d5_PAD_VAL)—Offset 3C8h" on page 4820	00000002h
3D0–3D3h	4	"Sdmmc1 D0 Pad Configuration (cfio_regs_pad_sdmmc1_d0_PCONF0)—Offset 3D0h" on page 4820	2003EC80h
3D8–3DBh	4	"Sdmmc1 D0 Pad Value (cfio_regs_pad_sdmmc1_d0_PAD_VAL)—Offset 3D8h" on page 4823	00000002h
3E0–3E3h	4	"Sdmmc1 Clk Pad Configuration (cfio_regs_pad_sdmmc1_clk_PCONF0)—Offset 3E0h" on page 4823	2003ED00h
3E4–3E7h	4	"Sdmmc1 Clk Delay Line Multiplexer (cfio_regs_pad_sdmmc1_clk_PCONF1)—Offset 3E4h" on page 4826	00008000h
3E8–3EBh	4	"Sdmmc1 Clk Pad Value (cfio_regs_pad_sdmmc1_clk_PAD_VAL)—Offset 3E8h" on page 4826	00000002h
3F0–3F3h	4	"Mmc1 D7 Pad Configuration (cfio_regs_pad_mmc1_d7_PCONF0)—Offset 3F0h" on page 4827	2003EC80h
3F8–3FBh	4	"Mmc1 D7 Pad Value (cfio_regs_pad_mmc1_d7_PAD_VAL)—Offset 3F8h" on page 4830	00000002h
400–403h	4	"Sdmmc1 D1 Pad Configuration (cfio_regs_pad_sdmmc1_d1_PCONF0)—Offset 400h" on page 4830	2003EC80h
408–40Bh	4	"Sdmmc1 D1 Pad Value (cfio_regs_pad_sdmmc1_d1_PAD_VAL)—Offset 408h" on page 4833	00000002h
410–413h	4	"Lpc Clkout1 Pad Configuration (cfio_regs_pad_lpc_clkout1_PCONF0)—Offset 410h" on page 4834	20038D00h
418–41Bh	4	"Lpc Clkout1 Pad Value (cfio_regs_pad_lpc_clkout1_PAD_VAL)—Offset 418h" on page 4836	00000002h
420–423h	4	"Lpc Ad3 Pad Configuration (cfio_regs_pad_lpc_ad3_PCONF0)—Offset 420h" on page 4836	20038C80h
428–42Bh	4	"Lpc Ad3 Pad Value (cfio_regs_pad_lpc_ad3_PAD_VAL)—Offset 428h" on page 4838	00000002h
430–433h	4	"Lpc Ad2 Pad Configuration (cfio_regs_pad_lpc_ad2_PCONF0)—Offset 430h" on page 4839	20038C80h
438–43Bh	4	"Lpc Ad2 Pad Value (cfio_regs_pad_lpc_ad2_PAD_VAL)—Offset 438h" on page 4841	00000002h
440–443h	4	"Lpc Ad1 Pad Configuration (cfio_regs_pad_lpc_ad1_PCONF0)—Offset 440h" on page 4842	20038C80h
448–44Bh	4	"Lpc Ad1 Pad Value (cfio_regs_pad_lpc_ad1_PAD_VAL)—Offset 448h" on page 4844	00000002h
450–453h	4	"Lpc Frameb Pad Configuration (cfio_regs_pad_lpc_frameb_PCONF0)—Offset 450h" on page 4845	20038C80h
458–45Bh	4	"Lpc Frameb Pad Value (cfio_regs_pad_lpc_frameb_PAD_VAL)—Offset 458h" on page 4847	00000002h
460–463h	4	"Lpc Ad0 Pad Configuration (cfio_regs_pad_lpc_ad0_PCONF0)—Offset 460h" on page 4848	20038C80h



Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
468–46Bh	4	"Lpc Ad0 Pad Value (cfio_regs_pad_lpc_ad0_PAD_VAL)—Offset 468h" on page 4850	00000002h
470–473h	4	"Lpc Clkout0 Pad Configuration (cfio_regs_pad_lpc_clkout0_PCONF0)—Offset 470h" on page 4850	20038D00h
478–47Bh	4	"Lpc Clkout0 Pad Value (cfio_regs_pad_lpc_clkout0_PAD_VAL)—Offset 478h" on page 4852	00000002h
480–483h	4	"Lpc Clkrnb Pad Configuration (cfio_regs_pad_lpc_clkrnb_PCONF0)—Offset 480h" on page 4853	20038C80h
488–48Bh	4	"Lpc Clkrnb Pad Value (cfio_regs_pad_lpc_clkrnb_PAD_VAL)—Offset 488h" on page 4855	00000002h
490–493h	4	"Hv Crt Ddc Clk Pad Configuration (cfio_regs_pad_hv_crt_ddc_clk_PCONF0)—Offset 490h" on page 4856	2003C800h
498–49Bh	4	"Hv Crt Ddc Clk Pad Value (cfio_regs_pad_hv_crt_ddc_clk_PAD_VAL)—Offset 498h" on page 4858	00000002h
4A0–4A3h	4	"Hv Crt Vsync Pad Configuration (cfio_regs_pad_hv_crt_vsync_PCONF0)—Offset 4A0h" on page 4859	20038800h
4A8–4ABh	4	"Hv Crt Vsync Pad Value (cfio_regs_pad_hv_crt_vsync_PAD_VAL)—Offset 4A8h" on page 4861	00000002h
4B0–4B3h	4	"Hv Crt Hsync Pad Configuration (cfio_regs_pad_hv_crt_hsync_PCONF0)—Offset 4B0h" on page 4862	20038800h
4B8–4BBh	4	"Hv Crt Hsync Pad Value (cfio_regs_pad_hv_crt_hsync_PAD_VAL)—Offset 4B8h" on page 4864	00000002h
4C0–4C3h	4	"Hv Crt Ddc Data Pad Configuration (cfio_regs_pad_hv_crt_ddc_data_PCONF0)—Offset 4C0h" on page 4865	2003C800h
4C8–4CBh	4	"Hv Crt Ddc Data Pad Value (cfio_regs_pad_hv_crt_ddc_data_PAD_VAL)—Offset 4C8h" on page 4867	00000002h
4D0–4D3h	4	"Mhsi Acdat Pad Configuration (cfio_regs_pad_mhsi_acdat_PCONF0)—Offset 4D0h" on page 4868	2003CD00h
4D8–4DBh	4	"Mhsi Acdat Pad Value (cfio_regs_pad_mhsi_acdat_PAD_VAL)—Offset 4D8h" on page 4871	00000002h
4E0–4E3h	4	"Mhsi Acwake Pad Configuration (cfio_regs_pad_mhsi_acwake_PCONF0)—Offset 4E0h" on page 4871	2003CD00h
4E8–4EBh	4	"Mhsi Acwake Pad Value (cfio_regs_pad_mhsi_acwake_PAD_VAL)—Offset 4E8h" on page 4874	00000002h
4F0–4F3h	4	"Mhsi Aclag Pad Configuration (cfio_regs_pad_mhsi_aclag_PCONF0)—Offset 4F0h" on page 4875	2003CC80h
4F8–4FBh	4	"Mhsi Aclag Pad Value (cfio_regs_pad_mhsi_aclag_PAD_VAL)—Offset 4F8h" on page 4877	00000002h
500–503h	4	"Mhsi Caflag Pad Configuration (cfio_regs_pad_mhsi_caflag_PCONF0)—Offset 500h" on page 4878	2003CD00h
504–507h	4	"Mhsi Caflag Delay Line Multiplexer (cfio_regs_pad_mhsi_caflag_PCONF1)—Offset 504h" on page 4880	00008000h
508–50Bh	4	"Mhsi Caflag Pad Value (cfio_regs_pad_mhsi_caflag_PAD_VAL)—Offset 508h" on page 4881	00000002h
510–513h	4	"Mhsi Cadat Pad Configuration (cfio_regs_pad_mhsi_cadat_PCONF0)—Offset 510h" on page 4882	2003CD00h
514–517h	4	"Mhsi Cadat Delay Line Multiplexer (cfio_regs_pad_mhsi_cadat_PCONF1)—Offset 514h" on page 4884	00008000h

**Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
518–51Bh	4	"Mhsi Cadata Pad Value (cfio_regs_pad_mhsi_cadata_PAD_VAL)—Offset 518h" on page 4885	00000002h
520–523h	4	"Mhsi Caready Pad Configuration (cfio_regs_pad_mhsi_caready_PCONF0)—Offset 520h" on page 4885	2003CC80h
528–52Bh	4	"Mhsi Caready Pad Value (cfio_regs_pad_mhsi_caready_PAD_VAL)—Offset 528h" on page 4888	00000002h
530–533h	4	"Mhsi Acready Pad Configuration (cfio_regs_pad_mhsi_acready_PCONF0)—Offset 530h" on page 4888	2003CD00h
538–53Bh	4	"Mhsi Acready Pad Value (cfio_regs_pad_mhsi_acready_PAD_VAL)—Offset 538h" on page 4891	00000002h
540–543h	4	"Hda Dockenb Pad Configuration (cfio_regs_pad_hda_dockenb_PCONF0)—Offset 540h" on page 4892	2003CD00h
548–54Bh	4	"Hda Dockenb Pad Value (cfio_regs_pad_hda_dockenb_PAD_VAL)—Offset 548h" on page 4894	00000002h
550–553h	4	"Sata Gp0 Pad Configuration (cfio_regs_pad_sata_gp0_PCONF0)—Offset 550h" on page 4895	2003CD00h
558–55Bh	4	"Sata Gp0 Pad Value (cfio_regs_pad_sata_gp0_PAD_VAL)—Offset 558h" on page 4897	00000002h
560–563h	4	"Ilb Serirq Pad Configuration (cfio_regs_pad_ilb_serirq_PCONF0)—Offset 560h" on page 4898	2003CC80h
568–56Bh	4	"Ilb Serirq Pad Value (cfio_regs_pad_ilb_serirq_PAD_VAL)—Offset 568h" on page 4901	00000002h
570–573h	4	"Plt Clk1 Pad Configuration (cfio_regs_pad_plt_clk1_PCONF0)—Offset 570h" on page 4901	2003CD00h
578–57Bh	4	"Plt Clk1 Pad Value (cfio_regs_pad_plt_clk1_PAD_VAL)—Offset 578h" on page 4904	00000002h
580–583h	4	"Smb Clk Pad Configuration (cfio_regs_pad_smb_clk_PCONF0)—Offset 580h" on page 4904	2003CC80h
588–58Bh	4	"Smb Clk Pad Value (cfio_regs_pad_smb_clk_PAD_VAL)—Offset 588h" on page 4907	00000002h
590–593h	4	"Sata Gp1 Pad Configuration (cfio_regs_pad_sata_gp1_PCONF0)—Offset 590h" on page 4908	2003CD00h
598–59Bh	4	"Sata Gp1 Pad Value (cfio_regs_pad_sata_gp1_PAD_VAL)—Offset 598h" on page 4910	00000002h
5A0–5A3h	4	"Smb Data Pad Configuration (cfio_regs_pad_smb_data_PCONF0)—Offset 5A0h" on page 4911	2003CC80h
5A8–5ABh	4	"Smb Data Pad Value (cfio_regs_pad_smb_data_PAD_VAL)—Offset 5A8h" on page 4913	00000002h
5B0–5B3h	4	"Plt Clk2 Pad Configuration (cfio_regs_pad_plt_clk2_PCONF0)—Offset 5B0h" on page 4914	2003CD00h
5B8–5BBh	4	"Plt Clk2 Pad Value (cfio_regs_pad_plt_clk2_PAD_VAL)—Offset 5B8h" on page 4917	00000002h
5C0–5C3h	4	"Smb Alertb Pad Configuration (cfio_regs_pad_smb_alertb_PCONF0)—Offset 5C0h" on page 4917	2003CC80h
5C8–5CBh	4	"Smb Alertb Pad Value (cfio_regs_pad_smb_alertb_PAD_VAL)—Offset 5C8h" on page 4920	00000002h
5D0–5D3h	4	"Sata Ledn Pad Configuration (cfio_regs_pad_sata_ledn_PCONF0)—Offset 5D0h" on page 4920	2003CC80h




Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
5D8–5DBh	4	"Sata Ledn Pad Value (cfio_regs_pad_sata_ledn_PAD_VAL)—Offset 5D8h" on page 4923	00000002h
5E0–5E3h	4	"Pmu Resetbutton B Pad Configuration (cfio_regs_pad_pmu_resetbutton_b_PCONF0)—Offset 5E0h" on page 4924	2003CC80h
5E8–5EBh	4	"Pmu Resetbutton B Pad Value (cfio_regs_pad_pmu_resetbutton_b_PAD_VAL)—Offset 5E8h" on page 4926	00000006h
5EC–5EFh	4	"Pmu Resetbutton B Pad Test (cfio_regs_pad_pmu_resetbutton_b_PAD_DFT)—Offset 5ECh" on page 4927	00000400h
5F0–5F3h	4	"Sdmmc3 1p8 En Pad Configuration (cfio_regs_pad_sdmmc3_1p8_en_PCONF0)—Offset 5F0h" on page 4928	2003CD00h
5F8–5FBh	4	"Sdmmc3 1p8 En Pad Value (cfio_regs_pad_sdmmc3_1p8_en_PAD_VAL)—Offset 5F8h" on page 4930	00000002h
600–603h	4	"Pcie Clkreq0b Pad Configuration (cfio_regs_pad_pcie_clkreq0b_PCONF0)—Offset 600h" on page 4931	2003CC80h
608–60Bh	4	"Pcie Clkreq0b Pad Value (cfio_regs_pad_pcie_clkreq0b_PAD_VAL)—Offset 608h" on page 4934	00000002h
610–613h	4	"Plt Clk4 Pad Configuration (cfio_regs_pad_plt_clk4_PCONF0)—Offset 610h" on page 4934	2003CD00h
618–61Bh	4	"Plt Clk4 Pad Value (cfio_regs_pad_plt_clk4_PAD_VAL)—Offset 618h" on page 4937	00000002h
620–623h	4	"Pcie Clkreq3b Pad Configuration (cfio_regs_pad_pcie_clkreq3b_PCONF0)—Offset 620h" on page 4937	2003CC80h
628–62Bh	4	"Pcie Clkreq3b Pad Value (cfio_regs_pad_pcie_clkreq3b_PAD_VAL)—Offset 628h" on page 4940	00000002h
630–633h	4	"Pcie Clkreq1b Pad Configuration (cfio_regs_pad_pcie_clkreq1b_PCONF0)—Offset 630h" on page 4941	2003CC80h
638–63Bh	4	"Pcie Clkreq1b Pad Value (cfio_regs_pad_pcie_clkreq1b_PAD_VAL)—Offset 638h" on page 4943	00000002h
640–643h	4	"Plt Clk5 Pad Configuration (cfio_regs_pad_plt_clk5_PCONF0)—Offset 640h" on page 4944	2003CD00h
648–64Bh	4	"Plt Clk5 Pad Value (cfio_regs_pad_plt_clk5_PAD_VAL)—Offset 648h" on page 4946	00000002h
650–653h	4	"Pcie Clkreq4b Pad Configuration (cfio_regs_pad_pcie_clkreq4b_PCONF0)—Offset 650h" on page 4947	2003CC80h
658–65Bh	4	"Pcie Clkreq4b Pad Value (cfio_regs_pad_pcie_clkreq4b_PAD_VAL)—Offset 658h" on page 4950	00000002h
660–663h	4	"Pcie Clkreq2b Pad Configuration (cfio_regs_pad_pcie_clkreq2b_PCONF0)—Offset 660h" on page 4950	2003CC80h
668–66Bh	4	"Pcie Clkreq2b Pad Value (cfio_regs_pad_pcie_clkreq2b_PAD_VAL)—Offset 668h" on page 4953	00000002h
670–673h	4	"Spkr Pad Configuration (cfio_regs_pad_spkr_PCONF0)—Offset 670h" on page 4953	2003CC80h
678–67Bh	4	"Spkr Pad Value (cfio_regs_pad_spkr_PAD_VAL)—Offset 678h" on page 4956	00000002h
680–683h	4	"Plt Clk3 Pad Configuration (cfio_regs_pad_plt_clk3_PCONF0)—Offset 680h" on page 4957	2003CD00h
688–68Bh	4	"Plt Clk3 Pad Value (cfio_regs_pad_plt_clk3_PAD_VAL)—Offset 688h" on page 4959	00000002h
690–693h	4	"Sdmmc3 Pwr En B Pad Configuration (cfio_regs_pad_sdmmc3_pwr_en_b_PCONF0)—Offset 690h" on page 4960	2003CC80h

**Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)**

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
698–69Bh	4	"Sdmmc3 Pwr En B Pad Value (cfio_regs_pad_sdmmc3_pwr_en_b_PAD_VAL)—Offset 698h" on page 4962	00000002h
6A0–6A3h	4	"Plt Clk0 Pad Configuration (cfio_regs_pad_plt_clk0_PCONF0)—Offset 6A0h" on page 4963	2003CD00h
6A8–6ABh	4	"Plt Clk0 Pad Value (cfio_regs_pad_plt_clk0_PAD_VAL)—Offset 6A8h" on page 4966	00000002h
6B0–6B3h	4	"Vgpio 0 Pad Configuration (cfio_regs_pad_vgpio_0_PCONF0)—Offset 6B0h" on page 4966	20038800h
6B8–6BBh	4	"Vgpio 0 Pad Value (cfio_regs_pad_vgpio_0_PAD_VAL)—Offset 6B8h" on page 4968	00000004h
6C0–6C3h	4	"Vgpio 1 Pad Configuration (cfio_regs_pad_vgpio_1_PCONF0)—Offset 6C0h" on page 4969	20038800h
6C8–6CBh	4	"Vgpio 1 Pad Value (cfio_regs_pad_vgpio_1_PAD_VAL)—Offset 6C8h" on page 4971	00000004h
6D0–6D3h	4	"Vgpio 2 Pad Configuration (cfio_regs_pad_vgpio_2_PCONF0)—Offset 6D0h" on page 4972	20038800h
6D8–6DBh	4	"Vgpio 2 Pad Value (cfio_regs_pad_vgpio_2_PAD_VAL)—Offset 6D8h" on page 4974	00000004h
6E0–6E3h	4	"Vgpio 3 Pad Configuration (cfio_regs_pad_vgpio_3_PCONF0)—Offset 6E0h" on page 4975	20038800h
6E8–6EBh	4	"Vgpio 3 Pad Value (cfio_regs_pad_vgpio_3_PAD_VAL)—Offset 6E8h" on page 4977	00000004h
6F0–6F3h	4	"Vgpio 4 Pad Configuration (cfio_regs_pad_vgpio_4_PCONF0)—Offset 6F0h" on page 4978	20038800h
6F8–6FBh	4	"Vgpio 4 Pad Value (cfio_regs_pad_vgpio_4_PAD_VAL)—Offset 6F8h" on page 4980	00000006h
700–703h	4	"Vgpio 5 Pad Configuration (cfio_regs_pad_vgpio_5_PCONF0)—Offset 700h" on page 4980	20038800h
708–70Bh	4	"Vgpio 5 Pad Value (cfio_regs_pad_vgpio_5_PAD_VAL)—Offset 708h" on page 4982	00000004h
710–713h	4	"Vgpio 6 Pad Configuration (cfio_regs_pad_vgpio_6_PCONF0)—Offset 710h" on page 4983	20038800h
718–71Bh	4	"Vgpio 6 Pad Value (cfio_regs_pad_vgpio_6_PAD_VAL)—Offset 718h" on page 4985	00000004h
720–723h	4	"Vgpio 7 Pad Configuration (cfio_regs_pad_vgpio_7_PCONF0)—Offset 720h" on page 4986	20038800h
728–72Bh	4	"Vgpio 7 Pad Value (cfio_regs_pad_vgpio_7_PAD_VAL)—Offset 728h" on page 4988	00000004h
730–733h	4	"Vgpio 8 Pad Configuration (cfio_regs_pad_vgpio_8_PCONF0)—Offset 730h" on page 4989	20038800h
738–73Bh	4	"Vgpio 8 Pad Value (cfio_regs_pad_vgpio_8_PAD_VAL)—Offset 738h" on page 4991	00000004h
740–743h	4	"Vgpio 9 Pad Configuration (cfio_regs_pad_vgpio_9_PCONF0)—Offset 740h" on page 4992	20038800h
748–74Bh	4	"Vgpio 9 Pad Value (cfio_regs_pad_vgpio_9_PAD_VAL)—Offset 748h" on page 4994	00000004h
750–753h	4	"Vgpio 10 Pad Configuration (cfio_regs_pad_vgpio_10_PCONF0)—Offset 750h" on page 4994	20038800h



Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
758–75Bh	4	"Vgpio 10 Pad Value (cfio_regs_pad_vgpio_10_PAD_VAL)—Offset 758h" on page 4996	00000004h
760–763h	4	"Vgpio 11 Pad Configuration (cfio_regs_pad_vgpio_11_PCONF0)—Offset 760h" on page 4997	20038800h
768–76Bh	4	"Vgpio 11 Pad Value (cfio_regs_pad_vgpio_11_PAD_VAL)—Offset 768h" on page 4999	00000004h
770–773h	4	"Vgpio 12 Pad Configuration (cfio_regs_pad_vgpio_12_PCONF0)—Offset 770h" on page 5000	20038800h
778–77Bh	4	"Vgpio 12 Pad Value (cfio_regs_pad_vgpio_12_PAD_VAL)—Offset 778h" on page 5002	00000004h
780–783h	4	"Vgpio 13 Pad Configuration (cfio_regs_pad_vgpio_13_PCONF0)—Offset 780h" on page 5003	20038800h
788–78Bh	4	"Vgpio 13 Pad Value (cfio_regs_pad_vgpio_13_PAD_VAL)—Offset 788h" on page 5005	00000004h
790–793h	4	"Vgpio 14 Pad Configuration (cfio_regs_pad_vgpio_14_PCONF0)—Offset 790h" on page 5006	20038800h
798–79Bh	4	"Vgpio 14 Pad Value (cfio_regs_pad_vgpio_14_PAD_VAL)—Offset 798h" on page 5008	00000004h
7A0–7A3h	4	"Vgpio 15 Pad Configuration (cfio_regs_pad_vgpio_15_PCONF0)—Offset 7A0h" on page 5008	20038800h
7A8–7ABh	4	"Vgpio 15 Pad Value (cfio_regs_pad_vgpio_15_PAD_VAL)—Offset 7A8h" on page 5010	00000004h
7B0–7B3h	4	"Vgpio 16 Pad Configuration (cfio_regs_pad_vgpio_16_PCONF0)—Offset 7B0h" on page 5011	20038800h
7B8–7BBh	4	"Vgpio 16 Pad Value (cfio_regs_pad_vgpio_16_PAD_VAL)—Offset 7B8h" on page 5013	00000004h
7C0–7C3h	4	"Vgpio 17 Pad Configuration (cfio_regs_pad_vgpio_17_PCONF0)—Offset 7C0h" on page 5014	20038800h
7C8–7CBh	4	"Vgpio 17 Pad Value (cfio_regs_pad_vgpio_17_PAD_VAL)—Offset 7C8h" on page 5016	00000004h
7D0–7D3h	4	"Vgpio 18 Pad Configuration (cfio_regs_pad_vgpio_18_PCONF0)—Offset 7D0h" on page 5017	20038800h
7D8–7DBh	4	"Vgpio 18 Pad Value (cfio_regs_pad_vgpio_18_PAD_VAL)—Offset 7D8h" on page 5019	00000004h
7E0–7E3h	4	"Vgpio 19 Pad Configuration (cfio_regs_pad_vgpio_19_PCONF0)—Offset 7E0h" on page 5020	20038800h
7E8–7EBh	4	"Vgpio 19 Pad Value (cfio_regs_pad_vgpio_19_PAD_VAL)—Offset 7E8h" on page 5022	00000004h
7F0–7F3h	4	"Vgpio 20 Pad Configuration (cfio_regs_pad_vgpio_20_PCONF0)—Offset 7F0h" on page 5022	20038800h
7F8–7FBh	4	"Vgpio 20 Pad Value (cfio_regs_pad_vgpio_20_PAD_VAL)—Offset 7F8h" on page 5024	00000004h
800–803h	4	"TS0 SCORE Interrupt Status 0 (cfio_regs_REG_TS0_SCORE_IRQ_TS_0)—Offset 800h" on page 5025	00000000h
804–807h	4	"TS1 SCORE Interrupt Status 1 (cfio_regs_REG_TS1_SCORE_IRQ_TS_1)—Offset 804h" on page 5026	00000000h
808–80Bh	4	"TS2 SCORE Interrupt Status 2 (cfio_regs_REG_TS2_SCORE_IRQ_TS_2)—Offset 808h" on page 5027	00000000h



Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—I/OBASE (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
80C–80Fh	4	"TS3 SCORE Interrupt Status 3 (cfio_regs_REG_TS3_SCORE_IRQ_TS_3)—Offset 80Ch" on page 5028	00000000h
810–813h	4	"C71p1cfiomvscoreaza Compensation Configuration (cfio_regs_fam_c71p1cfiomvscoreaza_FAM_RCOMP_CFG)—Offset 810h" on page 5029	00078080h
81C–81Fh	4	"C71p1cfiomvscoreaza Compensation DFX Override (cfio_regs_fam_c71p1cfiomvscoreaza_FAM_RCOMP_DFX)—Offset 81Ch" on page 5030	01000080h
820–823h	4	"C71p1cfiomvrscoresdio1 Compensation Configuration (cfio_regs_fam_c71p1cfiomvrscoresdio1_FAM_RCOMP_CFG)—Offset 820h" on page 5031	00078080h
82C–82Fh	4	"C71p1cfiomvrscoresdio1 Compensation DFX Override (cfio_regs_fam_c71p1cfiomvrscoresdio1_FAM_RCOMP_DFX)—Offset 82Ch" on page 5032	01000080h
830–833h	4	"C71p1cfiohvrscorepsdio3 Compensation Configuration (cfio_regs_fam_c71p1cfiohvrscorepsdio3_FAM_RCOMP_CFG)—Offset 830h" on page 5032	00078080h
83C–83Fh	4	"C71p1cfiohvrscorepsdio3 Compensation DFX Override (cfio_regs_fam_c71p1cfiohvrscorepsdio3_FAM_RCOMP_DFX)—Offset 83Ch" on page 5033	01000080h
840–843h	4	"C71p1cfiohvrscoreplpc Compensation Configuration (cfio_regs_fam_c71p1cfiohvrscoreplpc_FAM_RCOMP_CFG)—Offset 840h" on page 5034	00078080h
84C–84Fh	4	"C71p1cfiohvrscoreplpc Compensation DFX Override (cfio_regs_fam_c71p1cfiohvrscoreplpc_FAM_RCOMP_DFX)—Offset 84Ch" on page 5035	01000080h
850–853h	4	"Aza1 Strength Group (cfio_regs_aza1_STRENGTH)—Offset 850h" on page 5036	BABECAFeh
854–857h	4	"Clkreq Strength Group (cfio_regs_clkreq_STRENGTH)—Offset 854h" on page 5036	0003000Fh
858–85Bh	4	"Crt I2c Clk Strength Group (cfio_regs_crt_i2c_clk_STRENGTH)—Offset 858h" on page 5037	00020002h
85C–85Fh	4	"Crt I2c Data Strength Group (cfio_regs_crt_i2c_data_STRENGTH)—Offset 85Ch" on page 5037	00020002h
860–863h	4	"Hsi Strength Group (cfio_regs_hsi_STRENGTH)—Offset 860h" on page 5038	0003000Fh
864–867h	4	"I2c Strength Group (cfio_regs_i2c_STRENGTH)—Offset 864h" on page 5038	0003000Fh
868–86Bh	4	"Lpc Strength Group (cfio_regs_lpc_STRENGTH)—Offset 868h" on page 5038	BABECAFeh
86C–86Fh	4	"Mmc3 Strength Group (cfio_regs_mmc3_STRENGTH)—Offset 86Ch" on page 5039	BABECAFeh
870–873h	4	"Mvt Mmc3 Strength Group (cfio_regs_mvt_mmc3_STRENGTH)—Offset 870h" on page 5039	0003000Fh
874–877h	4	"Mvt Rcomp Strength Group (cfio_regs_mvt_rcomp_STRENGTH)—Offset 874h" on page 5040	BABECAFeh
878–87Bh	4	"Nfc Strength Group (cfio_regs_nfc_STRENGTH)—Offset 878h" on page 5040	0003000Fh
87C–87Fh	4	"Pltclk Strength Group (cfio_regs_pltclk_STRENGTH)—Offset 87Ch" on page 5041	0003000Fh
880–883h	4	"Pwm Strength Group (cfio_regs_pwm_STRENGTH)—Offset 880h" on page 5041	0003000Fh
884–887h	4	"Sata Strength Group (cfio_regs_sata_STRENGTH)—Offset 884h" on page 5042	0003000Fh
888–88Bh	4	"Smb Strength Group (cfio_regs_smb_STRENGTH)—Offset 888h" on page 5042	0003000Fh




Table 340. Summary of iLB GPIO S0 Memory Mapped I/O Registers—IOWBASE (Continued)

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
88C–88Fh	4	"Spi Strength Group (cfio_regs_spi_STRENGTH)—Offset 88Ch" on page 5043	0003000Fh
890–893h	4	"Spkr Strength Group (cfio_regs_spkr_STRENGTH)—Offset 890h" on page 5043	0003000Fh
894–897h	4	"Ssp Strength Group (cfio_regs_ssp_STRENGTH)—Offset 894h" on page 5043	0003000Fh
898–89Bh	4	"Uart1 Strength Group (cfio_regs_uart1_STRENGTH)—Offset 898h" on page 5044	0003000Fh
950–953h	4	"WR PATH SCORE Master Delay Line Write Address (cfio_regs_DLL_WR_PATH_SCORE_MDL_WRITE_PATH_C_F_ADDR)—Offset 950h" on page 5044	00080000h
954–957h	4	"WR PATH1 MUX SCORE Delay Line Write Multiplexer 1 (cfio_regs_DLL_WR_PATH1_MUX_SCORE_DLL_WRITE_PATH1_MUX)—Offset 954h" on page 5045	00000000h
958–95Bh	4	"WR PATH2 MUX SCORE Delay Line Write Multiplexer 2 (cfio_regs_DLL_WR_PATH2_MUX_SCORE_DLL_WRITE_PATH2_MUX)—Offset 958h" on page 5046	00000000h
95C–95Fh	4	"WR PATH3 MUX SCORE Delay Line Write Multiplexer 3 (cfio_regs_DLL_WR_PATH3_MUX_SCORE_DLL_WRITE_PATH3_MUX)—Offset 95Ch" on page 5046	00000000h
970–973h	4	"CTRL SCORE Master Delay Line Fsm Control (cfio_regs_DLL_CTRL_SCORE_MDL_FSM_CTRL)—Offset 970h" on page 5047	00000000h
980–983h	4	"DIRECT IRQ0 SCORE Direct Interrupt Multiplexer 0 (cfio_regs_REG_DIRECT_IRQ0_SCORE_DIRECT_IRQ_0)—Offset 980h" on page 5048	00000000h
984–987h	4	"DIRECT IRQ1 SCORE Direct Interrupt Multiplexer 1 (cfio_regs_REG_DIRECT_IRQ1_SCORE_DIRECT_IRQ_1)—Offset 984h" on page 5049	00000000h
988–98Bh	4	"DIRECT IRQ2 SCORE Direct Interrupt Multiplexer 2 (cfio_regs_REG_DIRECT_IRQ2_SCORE_DIRECT_IRQ_2)—Offset 988h" on page 5050	00000000h
98C–98Fh	4	"DIRECT IRQ3 SCORE Direct Interrupt Multiplexer 3 (cfio_regs_REG_DIRECT_IRQ3_SCORE_DIRECT_IRQ_3)—Offset 98Ch" on page 5050	00000000h
9A4–9A7h	4	"E EMMC 4.5 max high speed mux (cfio_regs_SCORE_EMMC_45_HSMAX)—Offset 9A4h" on page 5051	00000000h
9A8–9ABh	4	"E EMMC 4.5 sdr50 speed mux (cfio_regs_SCORE_EMMC_45_SDR50)—Offset 9A8h" on page 5052	00000000h
9AC–9AFh	4	"E EMMC 4.5 ddr50 speed mux (cfio_regs_SCORE_EMMC_45_DDR50)—Offset 9ACh" on page 5053	00000000h
9B0–9B3h	4	"E EMMC 4.5 max high speed mux (cfio_regs_SCORE_EMMC_45_HSMAX)—Offset 9A4h" on page 5051	00000000h
9B4–9B7h	4	"E EMMC 4.5 norm speed mux (cfio_regs_SCORE_EMMC_45_NORM)—Offset 9B4h" on page 5054	00000000h
9C0–9C3h	4	"E Special configuration bits (cfio_regs_SCORE_SPECIAL_BITS)—Offset 9C0h" on page 5055	00000000h
9D0–9D3h	4	"E Debounce Control (cfio_regs_SCORE_DEBOUNCE_CTRL)—Offset 9D0h" on page 5056	00000000h
9F4–9F7h	4	"E eMMC 4.5 TAP select register (cfio_regs_SCORE_TAP_SEL_REG)—Offset 9F4h" on page 5056	00000000h



39.8.1 Uart1 Rts B Pad Configuration (cfio_regs_pad_uart1_rts_b_PCONF0)—Offset 0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
								RSVD
								ihyscti
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved





39.8.3 Uart1 Txd Pad Configuration (cfio_regs_pad_uart1_txd_PCONF0)—Offset 10h

Access Method

Offset: [IOBASE] + 10h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31				28				24				20				16				12				8				4				0																																																							
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 0				1 0 0 0				1 0 0 0				0 0 0 0																																																							
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				debounce				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.5 Uart1 Rxd Pad Configuration (cfio_regs_pad_uart1_rxd_PCONF0)—Offset 20h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 20h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_70 function 1 is UART1_RXD function 2 is MHSL_CAREADY




31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



PADs Memory space Value register

Type: Memory Mapped I/O Register
(Size: 32 bits)

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

PADs Memory space configuration register

Intel Atom® Processor E3800 Product Family
Datasheet
4639



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 40h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.





39.8.11 I2c Nfc Sda Pad Configuration (cfio_regs_pad_i2c_nfc_sda_PCONF0)—Offset 50h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 50h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
								RSVD
								ihyscti
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Bit Range	Default & Access	Field Name (ID): Description
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is I2C_NFC_SDA function 1 is GPIOC_92

39.8.12 I2c Nfc Sda Pad Value (cfio_regs_pad_i2c_nfc_sda_PAD_VAL)—Offset 58h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 58h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.



Access Method

Offset: [IOBASE] + 60h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.15 Uart2 Txd Pad Configuration (cfio_regs_pad_uart2_txd_PCONF0)—Offset 70h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 70h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_75 function 1 is UART2_TXD



Access Method

Offset: [IOBASE] + 78h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.17 Uart2 Cts B Pad Configuration (cfio_regs_pad_uart2_cts_b_PCONF0)—Offset 80h

Access Method

Offset: [IOBASE] + 80h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_77 function 1 is UART2_CTS_B

39.8.18 Uart2 Cts B Pad Value
(cfio_regs_pad_uart2_cts_b_PAD_VAL)—Offset 88h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 88h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h


[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.19 Uart2 Rts B Pad Configuration (cfio_regs_pad_uart2_rts_b_PCONF0)—Offset 90h

PADs Memory space configuration register

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 90h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihysctl	RSVD	bypass_flop
pull_str	pull_assign	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.





39.8.21 Pwm0 Pad Configuration (cfio_regs_pad_pwm0_PCONF0)—Offset A0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + A0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
								RSVD
								ihyscti
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



39.8.23 Pwm1 Pad Configuration (cfio_regs_pad_pwm1_PCONF0)—Offset B0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + B0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihysctl
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved



PADs Memory space Value register

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + B8h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

[illegible]

Intel Atom® Processor E3800 Product Family
Datasheet
4664



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pin_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.25 Gp Ssp 2 Fs Pad Configuration (cfio_regs_pad_gp_ssp_2_fs_PCONF0)—Offset C0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + C0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD					RSVD
			debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
								ihysctl
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + D0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_62 function 1 is GP_SSP_2_CLK For this function, software should make sure it changes the default pull from down to up. pull assign field, bits [8:7] should be set to 2'b01 function 2 is SATA_DEVSLP1 function 3 is EDM_CFIO



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD
func_pin_mux								

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + E8h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.31 Gp Ssp 2 Rxd Pad Configuration (cfio regs pad gp ssp 2 rxd PCONF0)—Offset F0h

PADs Memory space configuration register



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + F0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysct	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_64 function 1 is GP_SSP_2_RXD

39.8.32 Gp Ssp 2 Rxd Pad Value (cfio_regs_pad_gp_ssp_2_rxd_PAD_VAL)—Offset F8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + F8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	
RSVD												RSVD																linenb	loutenb	lnad val					

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



39.8.33 Spi1 Clk Pad Configuration (cfio_regs_pad_spi1_clk_PCONF0)—Offset 100h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 100h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE] + 108h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

[illegible]

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pin_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.35 Spi1 Cs0 B Pad Configuration (cfio_regs_pad_spi1_cs0_b_PCONF0)—Offset 110h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 110h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
							fast_clkgate	RSVD
					ihysctl	RSVD	bypass_flop	pull_str
							pull_assign	RSVD
							RSVD	RSVD
							RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.

Bit Range	Default & Access	Field Name (ID): Description
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_66 function 1 is SPI1_CS0_B For this function, software should make sure it changes the default pull from up to down. pull assign field, bits [8:7] should be set to 2'b10

39.8.36 Spi1 Cs0 B Pad Value (cfio_regs_pad_spi1_cs0_b_PAD_VAL)–Offset 118h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 118h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.37 Spi1 Miso Pad Configuration (cfio_regs_pad_spi1_miso_PCONF0)—Offset 120h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 120h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_67 function 1 is SPI1_MISO



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 140h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



39.8.43 I2c5 Sda Pad Configuration (cfio_regs_pad_i2c5_sda_PCONF0)—Offset 150h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 150h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE] + 158h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pin_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.45 I2c6 Scl Pad Configuration (cfio_regs_pad_i2c6_scl_PCONF0)—Offset 160h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 160h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
					RSVD	ihysctl	RSVD	bypass_flop
								pull_str
								pull_assign
							RSVD	RSVD
							RSVD	RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_91 function 1 is I2C6_SCL function 2 is SDMMC3_WP

39.8.46 I2c6 Scl Pad Value (cfio_regs_pad_i2c6_scl_PAD_VAL)—Offset 168h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 168h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_87 function 1 is I2C4_SCL



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD
func_pin_mux								

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 190h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



39.8.53 I2c4 Sda Pad Configuration (cfio_regs_pad_i2c4_sda_PCONF0)—Offset 1A0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 1A0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE] + 1A8h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

[illegible]

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pin_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.55 I2c2 Scl Pad Configuration (cfio_regs_pad_i2c2_scl_PCONF0)—Offset 1B0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 1B0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
							fast_clkgate	RSVD
					ihysctl	RSVD	bypass_flop	pull_str
							pull_assign	RSVD
							RSVD	RSVD
							RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_83 function 1 is I2C2_SCL function 2 is Unused

39.8.56 I2c2 Scl Pad Value (cfio_regs_pad_i2c2_scl_PAD_VAL)—Offset 1B8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 1B8h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_85 function 1 is I2C3_SCL function 2 is Unused



Access Method

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.59 I2c2 Sda Pad Configuration (cfio_regs_pad_i2c2_sda_PCONF0)—Offset 1D0h

Access Method

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD
func_pin_mux								

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.

39.8.60 I2c2 Sda Pad Value (cfio_regs_pad_i2c2_sda_PAD_VAL)–Offset 1D8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 1D8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.61 I2c1 Scl Pad Configuration (cfio_regs_pad_i2c1_scl_PCONF0)—Offset 1E0h

PADs Memory space configuration register



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 1E0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD					RSVD
			debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
								ihysctl
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.





39.8.63 I2c1 Sda Pad Configuration (cfio_regs_pad_i2c1_sda_PCONF0)—Offset 1F0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 1F0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE] + 1F8h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

[illegible]

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pin_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.65 I2c0 Scl Pad Configuration (cfio_regs_pad_i2c0_scl_PCONF0)—Offset 200h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 200h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
							fast_clkgate	RSVD
					ihysctl			RSVD
					bypass_flop			
					pull_str			
					pull_assign			
					RSVD			
					RSVD			
					RSVD			
					func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 210h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_78 function 1 is I2C0_SDA function 2 is Unused



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
					debounce	filter_en	filter_slow	slow_clkgate
					fast_clkgate	RSVD	ihysctl	RSVD
							bypass_flop	pull_str
							pull_assign	RSVD
							RSVD	RSVD
							RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 228h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

	31	28	24	20	16	12	8	4	0															
	0	0	0	0		0	0	0	0		0	0	0	0		0	0	0	0		0	0	1	0
	RSVD									RSVD									linenb	toutenb	val			

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.71 Hda Sdi1 Pad Configuration (cfio_regs_pad_hda_sdi1_PCONF0)—Offset 230h

PADs Memory space configuration register



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 230h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003ED00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysct	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



39.8.73 Hda Clk Pad Configuration (cfio_regs_pad_hda_clk_PCONF0)—Offset 240h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 240h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003ED00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved





Bit Range	Default & Access	Field Name (ID): Description
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924



Access Method

Offset: [IOBASE] + 260h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003ED00h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_11 function 1 is GP_SSP_0_I2S_RXD function 2 is HDA_SDO For this function, software should make sure it changes the default pull from down to up. pull assign field, bits [8:7] should be set to 2'b01



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
					debounce	filter_en	filter_slow	slow_clkgate
					fast_clkgate	RSVD	ihysctl	RSVD
							bypass_flop	pull_str
							pull_assign	RSVD
							RSVD	RSVD
							RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 278h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.81 Hda Dockrstb Pad Configuration (cfio_regs_pad_hda_dockrstb_PCONF0)—Offset 280h

PADs Memory space configuration register



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 280h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003ED00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysct	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 290h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038C80h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 298h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



39.8.85 Sdmmc3 D3 Pad Configuration (cfio_regs_pad_sdmmc3_d3_PCONF0)—Offset 2A0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 2A0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038C80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	RSVD
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_37 function 1 is SDMMC3_D3



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
					debounce	filter_en	filter_slow	slow_clkgate
					fast_clkgate	RSVD	RSVD	RSVD
					RSVD	RSVD	RSVD	RSVD
					bypass_flop	pull_str	pull_assign	RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_33 function 1 is SDMMC3_CLK

39.8.88 Sdmmc3 Clk Delay Line Multiplexer (cfio_regs_pad_sdmmc3_clk_PCONF1)—Offset 2B4h

DLL Multiplexer

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 2B4h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00008000h



Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved (RSVD): Reserved.
15	1b RW	Dll Cf Od (dll_cf_od): 0 - Enable Master DLL tuning, 1 - Disable Master DLL tuning.
14:10	00000b RW	Dll Ddr Mux (dll_dds_mux): Set the used number of dll cells to use for ddr speed for read path DLL. Recommended value is 3.5ns (5'b01101).
9:5	00000b RW	Dll Hgh Mux (dll_hgh_mux): Set the used number of dll cells to use for high speed for read path DLL. Recommended value is 3.5ns (5'b01101).
4:0	00000b RW	Dll Std Mux (dll_std_mux): Set the used number of dll cells to use for standard speed for read path DLL. Recommended value is 3.5ns (5'b01101).

39.8.89 Sdmmc3 Clk Pad Value (cfio_regs_pad_sdmmc3_clk_PAD_VAL)—Offset 2B8h

Access Method

Offset: [IOBASE] + 2B8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required



Bit Range	Default & Access	Field Name (ID): Description
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.90 Sdmmc3 Cmd Pad Configuration (cfio_regs_pad_sdmmc3_cmd_PCONF0)—Offset 2C0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 2C0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038C80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	RSVD
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pn_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad



Bit Range	Default & Access	Field Name (ID): Description
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_39 function 1 is SDMMC3_CMD

39.8.91 Sdmmc3 Cmd Pad Value (cfio_regs_pad_sdmmc3_cmd_PAD_VAL)—Offset 2C8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 2C8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0					
RSVD												RSVD																ii	enb	enb	val				

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



39.8.92 Sdmmc3 D2 Pad Configuration (cfio_regs_pad_sdmmc3_d2_PCONF0)—Offset 2D0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 2D0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038C80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	bypass_flop	pull_str
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	pull_assign	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_36 function 1 is SDMMC3_D2



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	RSVD
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_34 function 1 is SDMMC3_D0

39.8.95 Sdmmc3 D0 Pad Value (cfio_regs_pad_sdmmc3_d0_PAD_VAL)—Offset 2E8h

PADs Memory space Value register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 2E8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h



Intel Atom® Processor E3800 Product Family
Datasheet
4775



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_29 function 1 is SDMMC2_D1



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_32 function 1 is SDMMC2_CMD

39.8.99 Sdmmc2 Cmd Pad Value
(`cfio_regs.pad_sdmmc2.cmd_PAD_VAL`)—Offset 308h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 308h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h


[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.100 Sdmmc2 D3 Cd B Pad Configuration (cfio_regs_pad_sdmmc2_d3_cd_b_PCONF0)—Offset 310h

PADs Memory space configuration register

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 310h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003EC80h

31				28				24				20				16				12				8				4				0																																																							
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 1 0				1 1 0 0				1 0 0 0				0 0 0 0				0 0 0 0																																																							
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				debounce				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.





39.8.102 Sdmmc2 Clk Pad Configuration (cfio_regs_pad_sdmmc2_clk_PCONF0)—Offset 320h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 320h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003ED00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
								RSVD
								ihyscti
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Bit Range	Default & Access	Field Name (ID): Description
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_27 function 1 is SDMMC2_CLK

39.8.103 Sdmmc2 Clk Delay Line Multiplexer (cfio_regs_pad_sdmmc2_clk_PCONF1)—Offset 324h

DLL Multiplexer

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 324h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00008000h

31	28	24	20	16	12	8	4	0		
0	0	0	0	0	0	0	0	0		
RSVD				dll_cf_od	dll_ddr_mux		dll_high_mux		dll_std_mux	

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved (RSVD): Reserved.
15	1b RW	Dll Cf Od (dll_cf_od): 0 - Enable Master DLL tuning, 1 - Disable Master DLL tuning.
14:10	00000b RW	Dll Ddr Mux (dll_dds_mux): Set the used number of dll cells to use for ddr speed for read path DLL. Recommended value is 3.5ns (5'b01101).
9:5	00000b RW	Dll Hgh Mux (dll_hgh_mux): Set the used number of dll cells to use for high speed for read path DLL. Recommended value is 3.5ns (5'b01101).
4:0	00000b RW	Dll Std Mux (dll_std_mux): Set the used number of dll cells to use for standard speed for read path DLL. Recommended value is 3.5ns (5'b01101).




31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

**Offset:** [IOBASE] + 340h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003EC80h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 348h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				RSVD				inenb
								ioutenb
								pad_val

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



39.8.109 Sdmmc2 D0 Pad Configuration (cfio_regs_pad_sdmmc2_d0_PCONF0)—Offset 350h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 350h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003EC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
								RSVD
								ihyscti
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE] + 360h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003EC80h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.

39.8.112 Sdmmc1 D3 Cd B Pad Value (cfio_regs_pad_sdmmc1_d3_cd_b_PAD_VAL)—Offset 368h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 368h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.113 Mmc1 D6 Pad Configuration (cfio_regs_pad_mmc1_d6_PCONF0)—Offset 370h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 370h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003EC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihysct	RSVD	bypass_flop
pull_str	pull_assign	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
func_pin_mux								

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_23 function 1 is MMC1_D6 function 2 is Unused function 3 is MMC_45_D6



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_21 function 1 is MMC1_D4_SD_WE function 2 is Unused function 3 is MMC_45_D4_SD_WE

39.8.116 Mmc1 D4 Sd We Pad Value
(cfio regs pad mmc1 d4 sd we PAD VAL)—Offset 388h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 388h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	
RSVD												RSVD																				linenb	loutenb	val	

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.117 Sdmmc1 Cmd Pad Configuration (cfio_regs_pad_sdmmc1_cmd_PCONF0)—Offset 390h

PADs Memory space configuration register



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 390h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003EC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihyscti	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



39.8.119 Sdmmc3 Cd B Pad Configuration (cfio_regs_pad_sdmmc3_cd_b_PCONF0)—Offset 3A0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 3A0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
								RSVD
								ihysctl
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved



Bit Range	Default & Access	Field Name (ID): Description
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_38 function 1 is SDMMC3_CD_B

39.8.120 Sdmmc3 Cd B Pad Value (cfio_regs_pad_sdmmc3_cd_b_PAD_VAL)—Offset 3A8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 3A8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required



Access Method

Offset: [IOBASE] + 3B0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003EC80h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad



Bit Range	Default & Access	Field Name (ID): Description
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924

39.8.122 Sdmmc1 D2 Pad Value (cfio_regs_pad_sdmmc1_d2_PAD_VAL)—Offset 3B8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 3B8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.123 Mmc1 D5 Pad Configuration (cfio_regs_pad_mmc1_d5_PCONF0)—Offset 3C0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 3C0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003EC80h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_22 function 1 is MMC1_D5 function 2 is Unused function 3 is MMC_45_D5




31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 3E0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003ED00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihyscti	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.

39.8.128 Sdmmc1 Clk Delay Line Multiplexer (cfio_regs_pad_sdmmc1_clk_PCONF1)—Offset 3E4h

DLL Multiplexer

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 3E4h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00008000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				dll_cf_od	dll_ddr_mux		dll_high_mux	
							dll_std_mux	

Bit Range	Default & Access	Field Name (ID): Description
31:16	0000h RO	Reserved (RSVD): Reserved.
15	1b RW	Dll Cf Od (dll_cf_od): 0 - Enable Master DLL tuning, 1 - Disable Master DLL tuning.
14:10	00000b RW	Dll Ddr Mux (dll_dds_mux): Set the used number of dll cells to use for ddr speed for read path DLL. Recommended value is 3.5ns (5'b01101).
9:5	00000b RW	Dll Hgh Mux (dll_hgh_mux): Set the used number of dll cells to use for high speed for read path DLL. Recommended value is 3.5ns (5'b01101).
4:0	00000b RW	Dll Std Mux (dll_std_mux): Set the used number of dll cells to use for standard speed for read path DLL. Recommended value is 3.5ns (5'b01101).

39.8.129 Sdmmc1 Clk Pad Value (cfio_regs_pad_sdmmc1_clk_PAD_VAL)—Offset 3E8h

PADs Memory space Value register



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
					debounce	filter_en	filter_slow	slow_clkgate
					fast_clkgate	RSVD	ihysctl	RSVD
							bypass_flop	pull_str
							pull_assign	RSVD
							RSVD	RSVD
							RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 3F8h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.132 Sdmmc1 D1 Pad Configuration (cfio_regs_pad_sdmmc1_d1_PCONF0)—Offset 400h

PADs Memory space configuration register



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



39.8.134 Lpc Clkout1 Pad Configuration (cfio_regs_pad_lpc_clkout1_PCONF0)—Offset 410h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 410h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038D00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	RSVD
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_48 function 1 is LPC_CLKOUT1



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	RSVD
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_45 function 1 is LPC_AD3

39.8.137 Lpc Ad3 Pad Value (cfio_regs_pad_lpc_ad3_PAD_VAL)—Offset 428h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 428h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

39.8.138 Lpc Ad2 Pad Configuration (cfio_regs_pad_lpc_ad2_PCONF0)–Offset 430h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 430h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038C80h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_44 function 1 is LPC_AD2

39.8.139 Lpc Ad2 Pad Value (cfio_regs_pad_lpc_ad2_PAD_VAL)—Offset 438h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 438h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.




Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved





31				28				24				20				16				12				8				4				0																																																							
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 0 0 0				1 1 0 0				1 0 0 0				0 0 0 0				0 0 0 0																																																							
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				debounce				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				RSVD				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			



Bit Range	Default & Access	Field Name (ID): Description
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



39.8.144 Lpc Ad0 Pad Configuration (cfio_regs_pad_lpc_ad0_PCONF0)—Offset 460h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 460h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038C80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	bypass_flop	pull_str
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	pull_assign	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_42 function 1 is LPC_AD0



Access Method

Offset: [IOBASE] + 468h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.


39.8.146 Lpc Clkout0 Pad Configuration (cfio_regs_pad_lpc_clkout0_PCONF0)—Offset 470h

Access Method

Offset: [IOBASE] + 470h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038D00h



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	RSVD
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_47 function 1 is LPC_CLKOUT0

39.8.147 Lpc Clkout0 Pad Value (cfio_regs_pad_lpc_clkout0_PAD_VAL)—Offset 478h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 478h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 490h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003C800h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.94435 max vil(V) - 1.3965 min vih(V) - 0.94435 max vih(V) - 1.3965 01: min vil(V) - 0.90365 max vil(V) - 1.30405 min vih(V) - 1.09065 max vih(V) - 1.44045 10: min vil(V) - 0.90365 max vil(V) - 1.30405 min vih(V) - 1.20945 max vih(V) - 1.52185 11: min vil(V) - 0.8569 max vil(V) - 1.2243 min vih(V) - 1.2243 max vih(V) - 1.5455
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RW	Pull Str (pull_str): Pull strength: 00 - reserved 01 - reserved 10 - 20K 11 - reserved
8:7	00b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is HV_CRT_DDC_CLK

39.8.151 Hv Crt Ddc Clk Pad Value (cfio_regs_pad_hv_crt_ddc_clk_PAD_VAL)—Offset 498h

PADs Memory space Value register

Access Method



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RW	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is HV_CRT_VSYNC

39.8.153 Hv Crt Vsync Pad Value (cfio_regs_pad_hv_crt_vsync_PAD_VAL)—Offset 4A8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 4A8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch





Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.94435 max vil(V) - 1.3965 min vih(V) - 0.94435 max vih(V) - 1.3965 01: min vil(V) - 0.90365 max vil(V) - 1.30405 min vih(V) - 1.09065 max vih(V) - 1.44045 10: min vil(V) - 0.90365 max vil(V) - 1.30405 min vih(V) - 1.20945 max vih(V) - 1.52185 11: min vil(V) - 0.8569 max vil(V) - 1.2243 min vih(V) - 1.2243 max vih(V) - 1.5455
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RW	Pull Str (pull_str): Pull strength: 00 - reserved 01 - reserved 10 - 20K 11 - reserved
8:7	00b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is HV_CRT_DDC_DATA

39.8.157 Hv Crt Ddc Data Pad Value (cfio_regs_pad_hv_crt_ddc_data_PAD_VAL)—Offset 4C8h

PADs Memory space Value register

Access Method

39.8.158 Mhsi Acdata Pad Configuration (cfio_regs_pad_mhsi_acdata_PCONF0)—Offset 4D0h

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 4C8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] ± 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RO	Reserved (RSVD): Reserved.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 4D0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_55 function 1 is MHSI_ACDATA

39.8.159 Mhsi Acdata Pad Value
(`cfio_regs_pad_mhsi_acdata_PAD_VAL`)—Offset 4D8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 4D8h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

31	28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
RSVD									RSVD																	linenb	ioutenb	pad_val				

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.160 Mhsi Acwake Pad Configuration (cfio regs pad mhsi acwake PCONF0)—Offset 4E0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 4E0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28				24				20				16				12				8				4				0						
0	0	1	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	0	1	1	0	1	0	0	0	0	0	0	0						
RSVD				direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD		RSVD		debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD		ihysctl		RSVD		bypass_flop		pull_str		pull_assign		RSVD		RSVD		RSVD		func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.





39.8.162 Mhsi Acflag Pad Configuration (cfio_regs_pad_mhsi_acflag_PCONF0)—Offset 4F0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 4F0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
								RSVD
								ihyscti
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved

39.8.164 Mhsi Caflag Pad Configuration (cfio_regs_pad_mhsi_caflag_PCONF0)—Offset 500h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 500h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



39.8.167 Mhsi Cadata Pad Configuration (cfio_regs_pad_mhsi_cadata_PCONF0)—Offset 510h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 510h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved





31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
					debounce	filter_en	filter_slow	slow_clkgate
					fast_clkgate	RSVD	ihysctl	RSVD
					bypass_flop	pull_str	pull_assign	RSVD
					RSVD	RSVD	RSVD	RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 530h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	RSVD	bypass_flop	pull_str
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	pull_assign	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_57 function 1 is UART3_TXD

39.8.173 Mhsi Acready Pad Value (cfio regs pad mhsi acready PAD VAL)—Offset 538h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 538h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0					
RSVD												RSVD																iin	enb	ad	val				

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



39.8.174 Hda Dockenb Pad Configuration (cfio_regs_pad_hda_dockenb_PCONF0)—Offset 540h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 540h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE] + 548h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pin_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.176 Sata Gp0 Pad Configuration (cfio_regs_pad_sata_gp0_PCONF0)—Offset 550h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 550h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD					RSVD
			debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
								ihysctl
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_0 function 1 is SATA_GP0

39.8.177 Sata Gp0 Pad Value (cfio_regs_pad_sata_gp0_PAD_VAL)–Offset 558h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 558h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.178 Ilb Serirq Pad Configuration (cfio_regs_pad_ilb_serirq_PCONF0)—Offset 560h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 560h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_50 function 1 is ILB_SERIRQ

31				28				24				20				16				12				8				4				0																																																							
0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	0	1	1	0	1	0	0	0	0	0	0	0	0																																																							
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				debounce				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 578h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
RSVD												RSVD																linenb		ioutenb		load val			

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.182 Smb Clk Pad Configuration (cfio_regs_pad_smb_clk_PCONF0)—Offset 580h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 580h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	RSVD	bypass_flop	pull_str
RSVD	RSVD	RSVD	RSVD	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



39.8.184 Sata Gp1 Pad Configuration (cfio_regs_pad_sata_gp1_PCONF0)—Offset 590h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 590h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved





Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pin_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.186 Smb Data Pad Configuration (cfio_regs_pad_smb_data_PCONF0)—Offset 5A0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 5A0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
					RSVD	ihysctl	RSVD	bypass_flop
								pull_str
								pull_assign
							RSVD	RSVD
							RSVD	RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 5B0h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_98 function 1 is PLT_CLK2



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
					debounce	filter_en	filter_slow	slow_clkgate
					fast_clkgate	RSVD	ihysctl	RSVD
							bypass_flop	pull_str
							pull_assign	RSVD
							RSVD	RSVD
							RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 5D0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate
RSVD	RSVD	RSVD	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE] + 5E0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31				28				24				20				16				12				8				4				0																																			
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 0				1 0 0 0				1 0 0 0				0 0 0 0																																			
RSVD				RSVD				RSVD				RSVD				RSVD				RSVD				RSVD				RSVD				RSVD				RSVD				func_pin_mux																											
disable_second_mask												debounce				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved



Access Method

Offset: [IOBASE] + 5E8h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000006h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.196 Pmu Resetbutton B Pad Test (cfio_regs_pad_pmu_resetbutton_b_PAD_DFT)—Offset 5ECh

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 5ECh

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000400h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:11	0h RO	Reserved (RSVD): Reserved.
10	1b RW	Bscan Bypass (bscan_bypass): Bypassing the bscan controll
9:6	0000b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2	0b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.199 Pcie Clkreq0b Pad Configuration (cfio_regs_pad_pcie_clkreq0b_PCONF0)—Offset 600h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 600h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti	RSVD	bypass_flop
pull_str	pull_assign	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_3 function 1 is PCIE_CLKREQ0B



Access Method

Offset: [IOBASE] + 608h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.


39.8.201 Plt Clk4 Pad Configuration (cfio_regs_pad_plt_clk4_PCONF0)—Offset 610h

Access Method

Offset: [IOBASE] + 610h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_100 function 1 is PLT_CLK4

39.8.202 Plt Clk4 Pad Value (cfio_regs_pad_plt_clk4_PAD_VAL)—Offset 618h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 618h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.203 Pcie Clkreq3b Pad Configuration (cfio regs pad pcie clkreq3b PCONF0)—Offset 620h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 620h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31				28				24				20				16				12				8				4				0																																																							
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 0				1 0 0 0				1 0 0 0				0 0 0 0																																																							
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				debounce				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.





39.8.205 Pcie Clkreq1b Pad Configuration (cfio_regs_pad_pcie_clkreq1b_PCONF0)—Offset 630h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 630h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
								RSVD
								ihyscti
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE] + 640h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

31	28				24				20				16				12				8				4				0																																																										
0	0	1	0	0	0	0	0	0	0	0	0	0	0	1	1	1	0	0	1	1	0	1	0	0	0	0	0	0	0	0	0																																																								
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				debounce				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.209 Pcie Clkreq4b Pad Configuration (cfio_regs_pad_pcie_clkreq4b_PCONF0)—Offset 650h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 650h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_7 function 1 is PCIE_CLKREQ4B function 2 is SDMMC3_WP




31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti
RSVD	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



PADs Memory space Value register

Type: Memory Mapped I/O Register
(Size: 32 bits)

IOBASE Type: PCI Configuration Register (Size: 32 bits)


IOBASE Reference: [B:0, D:31, F:0] + 4Ch

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

PADs Memory space configuration register

Intel Atom® Processor E3800 Product Family
Datasheet
4953



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 670h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31				28				24				20				16				12				8				4				0																																																							
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 0				1 0 0 0				0 0 0 0				0 0 0 0																																																							
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				debounce				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.



Bit Range	Default & Access	Field Name (ID): Description
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.



39.8.215 Plt Clk3 Pad Configuration (cfio_regs_pad_plt_clk3_PCONF0)—Offset 680h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 680h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
			RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate
								fast_clkgate
								RSVD
								ihyscti
								RSVD
								bypass_flop
								pull_str
								pull_assign
								RSVD
								RSVD
								RSVD
								func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE] + 690h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

31	28				24				20				16				12				8				4				0	
0	0	1	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	0	1	1	0	0	1	0	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihysctl	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	RSVD	func_pin_mux					

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.

39.8.218 Sdmmc3 Pwr En B Pad Value (cfio_regs_pad_sdmmc3_pwr_en_b_PAD_VAL)—Offset 698h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 698h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.8.219 Plt Clk0 Pad Configuration (cfio_regs_pad_plt_clk0_PCONF0)—Offset 6A0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 6A0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
debounce	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihyscti	RSVD	bypass_flop
pull_str	pull_assign	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RW	Debounce (debounce): Enabling the debouncer for this pad. Debounce time will be according to the community setting at the debounce control register
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOC_96 function 1 is PLT_CLK0



Access Method

Offset: [IOBASE] + 6A8h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.


39.8.221 Vgpio 0 Pad Configuration (cfio_regs_pad_vgpio_0_PCONF0)—Offset 6B0h

Access Method

Offset: [IOBASE] + 6B0h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038800h



Intel Atom® Processor E3800 Product Family
Datasheet
4967



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.222 Vgpio 0 Pad Value (cfio_regs_pad_vgpio_0_PAD_VAL)—Offset 6B8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 6B8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.224 Vgpio 1 Pad Value (cfio_regs_pad_vgpio_1_PAD_VAL)—Offset 6C8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 6C8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.227 Vgpio 3 Pad Configuration (cfio_regs_pad_vgpio_3_PCONF0)—Offset 6E0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 6E0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] ± 4Ch

Default: 20038800h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.228 Vgpio 3 Pad Value (cfio_regs_pad_vgpio_3_PAD_VAL)—Offset 6E8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 6E8h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.



Access Method

Offset: [IOBASE] + 6F8h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000006h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.


39.8.231 Vgpios Pad Configuration (cfio_regs_pad_vgpio_5_PCONF0)—Offset 700h

Access Method

Offset: [IOBASE] + 700h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038800h



Intel Atom® Processor E3800 Product Family
Datasheet
4981



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.232 Vgpio 5 Pad Value (cfio_regs_pad_vgpio_5_PAD_VAL)—Offset 708h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 708h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

39.8.233 Vgpio 6 Pad Configuration (cfio_regs_pad_vgpio_6_PCONF0)—Offset 710h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.

Bit Range	Default & Access	Field Name (ID): Description
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.234 Vgpios 6 Pad Value (cfio_regs_pad_vgpio_6_PAD_VAL)—Offset 718h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 718h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

I/OBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

[illegible]



Access Method

Offset: [IOBASE] + 720h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038800h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.238 Vgpio 8 Pad Value (cfio_regs_pad_vgpio_8_PAD_VAL)—Offset 738h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 738h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.239 Vgpios 9 Pad Configuration (cfio_regs_pad_vgpio_9_PCONF0)—Offset 740h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 740h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038800h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.



Access Method

Offset: [IOBASE] + 748h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.


39.8.241 Vgpio 10 Pad Configuration (cfio_regs_pad_vgpio_10_PCONF0)—Offset 750h

Access Method

Offset: [IOBASE] + 750h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038800h



Intel Atom® Processor E3800 Product Family
Datasheet
4995



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.242 Vgpios 10 Pad Value (cfio_regs_pad_vgpios_10_PAD_VAL)—Offset 758h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 758h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.244 Vgpio 11 Pad Value (cfio_regs_pad_vgpio_11_PAD_VAL)–Offset 768h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 768h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

[illegible]



Access Method

Offset: [IOBASE] + 770h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038800h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.247 Vgpio 13 Pad Configuration (cfio_regs_pad_vgpio_13_PCONF0)—Offset 780h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 780h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] ± 4Ch

Default: 20038800h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.



Access Method

Offset: [IOBASE] + 798h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.


39.8.251 Vgpio 15 Pad Configuration (cfio_regs_pad_vgpio_15_PCONF0)—Offset 7A0h

Access Method

Offset: [IOBASE] + 7A0h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038800h



Intel Atom® Processor E3800 Product Family
Datasheet
5009



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.252 Vgpios 15 Pad Value (cfio_regs_pad_vgpios_15_PAD_VAL)—Offset 7A8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 7A8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.254 Vgpio 16 Pad Value (cfio_regs_pad_vgpio_16_PAD_VAL)–Offset 7B8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 7B8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

[illegible]



Access Method

Offset: [IOBASE] + 7C0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 20038800h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.258 Vgpio 18 Pad Value (cfio_regs_pad_vgpio_18_PAD_VAL)–Offset 7D8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 7D8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	0b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.8.259 Vgpio 19 Pad Configuration (cfio_regs_pad_vgpio_19_PCONF0)—Offset 7E0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 7E0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch


Default: 20038800h

31				28				24				20				16				12				8				4				0			
0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	0	0	0	1	0	0	0	1	0	0	0	0	0	0	0	0	0	
RSVD				direct_irq_en				RSVD				RSVD			RSVD			RSVD			RSVD			bypass_flop				RSVD			RSVD			RSVD	
RSVD				gd_tne				RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
disable_second_mask				gd_tpe				RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
RSVD				gd_level				RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	
								RSVD				RSVD			RSVD			RSVD			RSVD							RSVD			RSVD			RSVD	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.



Intel Atom® Processor E3800 Product Family
Datasheet
5023



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	00b RO	Reserved (RSVD): Reserved.
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function.

39.8.262 Vgpios 20 Pad Value (cfio_regs_pad_vgpios_20_PAD_VAL)—Offset 7F8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 7F8h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000004h





Diagram illustrating the bit fields of the `status` register. The register is 32 bits wide, divided into eight 4-bit nibbles. The bit positions are labeled 31, 28, 24, 20, 16, 12, 8, and 4. The register contains the value 0000 0000 0000 0000 0000 0000 0000 0000.



IRQ TS 2 status register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 808h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

[illegible]

39.8.266 TS3 SCORE Interrupt Status 3 (cfio_regs_REG_TS3_SCORE_IRQ_TS_3)—Offset 80Ch

IRQ TS 3 status register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 80Ch

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

[illegible]



Access Method

Offset: [IOBASE] + 81Ch

IOBASE Reference: [B:0, D:31, F:0] + 4Ch


Default: 01000080h

Bit Range	Default & Access	Field Name (ID): Description
31:16	0100h RW	Ircdfx Pstr (ircdfx_pstr): Override strength compensation p-leg value. Should be 50ohm typical corner.
15:0	0080h RW	Ircdfx Nstr (ircdfx_nstr): Override strength compensation n-leg value Should be 50ohm typical corner.



Bit Range	Default & Access	Field Name (ID): Description
31:16	0100h RW	Ircdfx Pstr (ircdfx_pstr): Override strength compensation p-leg value. Should be 50ohm typical corner.
15:0	0080h RW	Ircdfx Nstr (ircdfx_nstr): Override strength compensation n-leg value Should be 50ohm typical corner.

39.8.271 C71p1cfiohvrscorpsdio3 Compensation Configuration (cfio_regs_fam_c71p1cfiohvrscorpsdio3_FAM_RCOMP_CFG)–Offset 830h



39.8.272 C71p1cfiohvrcorespsdio3 Compensation DFX Override (cfio_regs_fam_c71p1cfiohvrcorespsdio3_FAM_RCOMP_DFX)–Offset 83Ch


Intel Atom® Processor E3800 Product Family
Datasheet
5033



Bit Range	Default & Access	Field Name (ID): Description
31:16	0100h RW	Ircdfx Pstr (ircdfx_pstr): Override strength compensation p-leg value. Should be 50ohm typical corner.
15:0	0080h RW	Ircdfx Nstr (ircdfx_nstr): Override strength compensation n-leg value Should be 50ohm typical corner.

39.8.273 C71p1cfiohvrscoreplpc Compensation Configuration (cfio_regs_fam_c71p1cfiohvrscoreplpc_FAM_RCOMP_CFG)–Offset 840h

Bit Range	Default & Access	Field Name (ID): Description
31:19	0000h RO	Reserved (RSVD): Reserved.
18	1b RW	Ircclk En (ircclk_en): This is enabling the rcomp clock. When rcomp clock is gated, rcomp reset is forced too, so when it is ungated again it will compensate
17:16	11b RW	Ircintclkperiod (ircintclkperiod): reserved as 0x3



Bit Range	Default & Access	Field Name (ID): Description
31:16	0100h RW	Ircdfx Pstr (ircdfx_pstr): Override strength compensation p-leg value. Should be 50ohm typical corner.
15:0	0080h RW	Ircdfx Nstr (ircdfx_nstr): Override strength compensation n-leg value. Should be 50ohm typical corner.

39.8.275 Aza1 Strength Group (cfio_regs_aza1_STRENGTH)—Offset 850h

P and N strength register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 850h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: BABECAFh

31	28	24	20	16	12	8	4	0
1	0	1	1	1	0	1	1	1
1	0	1	1	1	0	1	1	1
pstr				nstr				

Bit Range	Default & Access	Field Name (ID): Description
31:16	babeh RO	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	cafeh RO	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.8.276 Clkreq Strength Group (cfio_regs_clkreq_STRENGTH)—Offset 854h

P and N strength register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 854h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 0003000Fh

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
pstr				nstr				

Bit Range	Default & Access	Field Name (ID): Description
31:16	0003h RW	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used



Access Method

Offset: [IOBASE] + 860h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 0003000Fh

Bit Range	Default & Access	Field Name (ID): Description
31:16	0003h RW	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	000Fh RW	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.8.280 I2c Strength Group (cfio_regs_i2c_STRENGTH)—Offset 864h

Access Method

Offset: [IOBASE] + 864h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 0003000Fh

Bit Range	Default & Access	Field Name (ID): Description
31:16	0003h RW	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	000Fh RW	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.8.281 Lpc Strength Group (cfio_regs_lpc_STRENGTH)—Offset 868h

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 868h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: BABECAFEh

31	28	24	20	16	12	8	4	0
1	0	1	1	1	0	1	1	1
0	1	0	1	1	0	0	1	0
1	0	1	1	1	0	1	1	1
1	1	1	1	0	1	1	1	0
pstr				nstr				

Bit Range	Default & Access	Field Name (ID): Description
31:16	babeh RO	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	cafeh RO	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.8.282 Mmc3 Strength Group (cfio_regs_mmc3_STRENGTH)—Offset 86Ch

P and N strength register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 86Ch

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: BABECAFEh

31	28	24	20	16	12	8	4	0
1	0	1	1	1	0	1	1	1
1	0	1	0	1	1	0	1	0
1	0	1	1	1	0	1	0	1
1	1	0	0	1	0	1	1	1
1	1	1	1	0	1	1	1	0
pstr				nstr				

Bit Range	Default & Access	Field Name (ID): Description
31:16	babeh RO	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	cafeh RO	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.8.283 Mvt Mmc3 Strength Group (cfio_regs_mvt_mmc3_STRENGTH)—Offset 870h

P and N strength register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 870h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch



Access Method

Offset: [IOBASE] + 874h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

31 28 24 20 16 12 8 4 0

1 0 1 1 | 1 0 1 0 | 1 0 1 1 | 1 1 1 0 | 1 1 0 0 | 1 0 1 0 | 1 1 1 1 | 1 1 1 0

pstr nstr

Bit Range	Default & Access	Field Name (ID): Description
31:16	babeh RO	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	cafeh RO	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.8.285 Nfc Strength Group (cfio_regs_nfc_STRENGTH)—Offset 878h

Access Method

Offset: [IOBASE] + 878h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

31		28		24		20		16		12		8		4		0																				
0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	0	1	1	1	1													
									<i>pstr</i>																					<i>nstr</i>						

**Offset:** [IOBASE] + 894h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 0003000Fh

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:16	0003h RW	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	000Fh RW	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.8.293 Uart1 Strength Group (cfio_regs_uart1_STRENGTH)—Offset 898h

P and N strength register

Access Method

Offset: [IOBASE] + 898h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 0003000Fh

	31		28		24		20		16		12		8		4		0	
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
	pstr									nstr								

Bit Range	Default & Access	Field Name (ID): Description
31:16	0003h RW	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	000Fh RW	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.8.294 WR PATH SCORE Master Delay Line Write Address (cfio_regs_DLL_WR_PATH_SCORE_MDL_WRITE_PATH_C_F_AD DR)—Offset 950h

Master delay line write path values

Access Method



Access Method

Offset: [IOBASE] + 958h**IOBASE Type:** PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				d1l_mux_2		d1l_mux_1		d1l_mux_0

Bit Range	Default & Access	Field Name (ID): Description
31:15	0h RO	Reserved (RSVD): Reserved.
14:10	0h RW	Dll Mux 2 (dll_mux_2): SD-Card TX Slave DLL tap select for HS Mode. Adjusts TX Clk to Data spacing in 250ps steps. Valid values are 0 to 10011 (0 to 19 for 0 to 5ns range). Recommended value is 3.5ns (5'b01101).
9:5	0h RW	Dll Mux 1 (dll_mux_1): SDIO TX Slave DLL tap select for HS Mode. Adjusts TX Clk to Data spacing in 250ps steps. Valid values are 0 to 10011 (0 to 19 for 0 to 5ns range). Recommended value is 3.5ns (5'b01101).
4:0	0h RW	Dll Mux 0 (dll_mux_0): eMMC TX Slave DLL tap select for HS Mode. Adjusts TX Clk to Data spacing in 250ps steps. Valid values are 0 to 10011 (0 to 19 for 0 to 5ns range). Recommended value is 3.5ns (5'b01101).

39.8.297 WR PATH3 MUX SCORE Delay Line Write Multiplexer 3 (cfio_regs_DLL_WR_PATH3_MUX_SCORE_DLL_WRITE_PATH3_MUX)—Offset 95Ch

Master delay line write path mux values

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 95Ch

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				dll_mux_2		dll_mux_1		dll_mux_0

Bit Range	Default & Access	Field Name (ID): Description
31:15	0h RO	Reserved (RSVD): Reserved.
14:10	0h RW	Dll Mux 2 (dll_mux_2): SD-Card TX Slave DLL tap select for FS Mode. Adjusts TX Clk to Data spacing in 250ps steps. Valid values are 0 to 10011 (0 to 19 for 0 to 5ns range). Recommended value is 3.5ns (5'b01101).
9:5	0h RW	Dll Mux 1 (dll_mux_1): SDIO TX Slave DLL tap select for FS Mode. Adjusts TX Clk to Data spacing in 250ps steps. Valid values are 0 to 10011 (0 to 19 for 0 to 5ns range). Recommended value is 3.5ns (5'b01101).
4:0	0h RW	Dll Mux 0 (dll_mux_0): eMMC TX Slave DLL tap select for FS Mode. Adjusts TX Clk to Data spacing in 250ps steps. Valid values are 0 to 10011 (0 to 19 for 0 to 5ns range). Recommended value is 3.5ns (5'b01101).

39.8.298 CTRL SCORE Master Delay Line Fsm Control (cfio_regs_DLL_CTRL_SCORE_MDL_FSM_CTRL)—Offset 970h

Master delay line fsm controller

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 970h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD				ctrl_val		delay_mux_val		swing



Bit Range	Default & Access	Field Name (ID): Description
31:13	0h RO	Reserved (RSVD): Reserved.
12:9	0b RW	Ctrl Val (ctrl_val): fsm control value bit 3: Local Reset 2: Enable FSM 1: Reseved for debug 0: recalibrate
8:4	00000b RW	Delay Mux Val (delay_mux_val): fsm delay mux value to select how many delay cells master dll should use to lock on 5ns. If value is too low, DLL might not succeed to lock. Recomend value is 19 (highest posible), to allow smallest margin.
3:0	0000b RW	Swing (swing): number of swings untill the lock in the fsm (from the cfio register). Recomend value 3.

39.8.299 DIRECT IRQ0 SCORE Direct Interrupt Multiplexer 0 (cfio_regs_REG_DIRECT_IRQ0_SCORE_DIRECT_IRQ_0)—Offset 980h

Direct irq select register for irq 0 - 3.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 980h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD	direct3	RSVD	direct2	RSVD	direct1	RSVD	direct0	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30:24	0000000b RW	Direct3 (direct3): Selects the 3rd direct irq.
23	0b RO	Reserved (RSVD): Reserved.
22:16	0000000b RW	Direct2 (direct2):
15	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:8	0000000b RW	Direct1 (direct1)
7	0b RO	Reserved (RSVD): Reserved.
6:0	0000000b RW	Direct0 (direct0)

39.8.300 DIRECT IRQ1 SCORE Direct Interrupt Multiplexer 1 (cfio_regs_REG_DIRECT_IRQ1_SCORE_DIRECT_IRQ_1)—Offset 984h

Direct irq select register for irq 4 - 7

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 984h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD	direct7	rsv6	direct6	rsv5	direct5	RSVD	direct4	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30:24	0000000b RW	Direct7 (direct7): Selects the 7th direct irq.
23	0b RO	Rsv6 (rsv6): reserved
22:16	0000000b RW	Direct6 (direct6): Selects the 6th direct irq.
15	0b RO	Rsv5 (rsv5): reserved
14:8	0000000b RW	Direct5 (direct5): Selects the 5th direct irq.
7	0b RO	Reserved (RSVD): Reserved.
6:0	0000000b RW	Direct4 (direct4): Selects the 4th direct irq.



39.8.301 DIRECT IRQ2 SCORE Direct Interrupt Multiplexer 2 (cfio_regs_REG_DIRECT_IRQ2_SCORE_DIRECT_IRQ_2)— Offset 988h

Direct irq select register for irq 8 - 11

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 988h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31		28				24				20				16				12				8				4				0																	
0		0		0		0		0		0		0		0		0		0		0		0		0		0		0		0		0															
RSVD		direct11										RSVD		direct10										RSVD		direct9										RSVD		direct8									

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30:24	000000b RW	Direct11 (direct11): Selects the 11th direct irq. S
23	0b RO	Reserved (RSVD): Reserved.
22:16	000000b RW	Direct10 (direct10): Selects the 10th direct irq.
15	0b RO	Reserved (RSVD): Reserved.
14:8	000000b RW	Direct9 (direct9): Selects the 9th direct irq.
7	0b RO	Reserved (RSVD): Reserved.
6:0	000000b RW	Direct8 (direct8): Selects the 8th direct irq.

39.8.302 DIRECT IRQ3 SCORE Direct Interrupt Multiplexer 3 (cfio_regs_REG_DIRECT_IRQ3_SCORE_DIRECT_IRQ_3)— Offset 98Ch

Direct irq select register for irq 12 - 15

Access Method



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 98Ch

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD	direct15	rsv14	direct14	RSVD	direct13	RSVD	direct12	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30:24	0000000b RW	Direct15 (direct15): Selects the 15th direct irq.
23	0b RO	Rsv14 (rsv14): reserved
22:16	0000000b RW	Direct14 (direct14): Selects the 14th direct irq. S
15	0b RO	Reserved (RSVD): Reserved.
14:8	0000000b RW	Direct13 (direct13): Selects the 13th direct irq.
7	0b RO	Reserved (RSVD): Reserved.
6:0	0000000b RW	Direct12 (direct12): Selects the 12th direct irq. S

39.8.303 E Emmc 4.5 max high speed mux (cfio_regs_SCORE_EMMC_45_HSMAX)—Offset 9A4h

Setting the DLL mux when highest speed is selected

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 9A4h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h



Access Method

Offset: [IOBASE] + 9A8h

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RSVD				tx_dat_dly_sel_sdr50	RSVD				rx_dly_sel_sdr50

October 2018
Document Number: 538136, Rev. 4.3



Bit Range	Default & Access	Field Name (ID): Description
20:16	0b RW	Tx Dat Dly Sel Sdr50 (tx_dat_dly_sel_sdr50): Set the tx delay for sdr50 for eMMC 4.5 clock. Recommended value is 3.5ns (5'b01101).
15:5	0h RO	Reserved (RSVD): Reserved.
4:0	0b RW	Rx Dly Sel Sdr50 (rx_dly_sel_sdr50): Set the rx delay for sdr50 for eMMC 4.5 clock. Recommended value is 3.5ns (5'b01101).

39.8.305 E Emmc 4.5 ddr50 speed mux
(cfio regs SCORE EMMC 45 DDR50)—Offset 9ACh

Setting the DLL mux when ddr50 speed is selected and 1.8v is used

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE] + 9ACh

IOBASE Type: PCI Configuration Register (Size: 32 bits)

IOBASE Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD				tx_dat_dly_sel_ddr50	RSVD			rx_dly_sel_ddr50

Bit Range	Default & Access	Field Name (ID): Description
31:21	0h RO	Reserved (RSVD): Reserved.
20:16	0b RW	Tx Dat Dly Sel Ddr50 (tx_dat_dly_sel_ddr50): Set the tx delay for ddr50 for eMMC 4.5 clock. Recommended value is 3.5ns (5'b01101).
15:5	0h RO	Reserved (RSVD): Reserved.
4:0	0b RW	Rx Dly Sel Ddr50 (rx_dly_sel_ddr50): Set the rx delay for ddr50 for eMMC 4.5 clock. Recommended value is 3.5ns (5'b01101).

39.8.306 E Emmc 4.5 hs speed mux (cfio_regs_SCORE_EMMC_45_HS)– Offset 9B0h

Setting the DLL mux when 1. hs speed is selected or 2. ddr 50 and 1.8V Signaling Enable is set to 0. The SDMMC1 IO will still use 1.8V.



Bit Range	Default & Access	Field Name (ID): Description
31:21	0h RO	Reserved (RSVD): Reserved.
20:16	0b RW	Tx Dat Dly Sel Hs (tx_dat_dly_sel_hs): Set the tx delay for hs for eMMC 4.5 clock. Recommended value is 3.5ns (5'b01101).
15:5	0h RO	Reserved (RSVD): Reserved.
4:0	0b RW	Rx Dly Sel Hs (rx_dly_sel_hs): Set the rx delay for hs for eMMC 4.5 clock. Recommended value is 3.5ns (5'b01101).

31	28	24	20	16	12	8	4	0	
0	0	0	0	0	0	0	0	0	
RSVD				tx_dat_dly_sel_norm	RSVD				rx_dly_sel_norm



Access Method

Offset: [IOBASE] + 9D0h

IOBASE Type: PCI Configuration Register (Size: 32 bits)

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:3	0h RO	Reserved (reserved): reserved
2:0	0h RW	Debounce Pulse Cfg (debounce_pulse_cfg): This will divide the rtc clock, for generating the pulse of the debounce. When all cleared, pulse will be always high. 3'b001 375us debounce 3'b010 750us debounce 3'b011 1.5ms debounce 3'b100 3ms debounce 3'b101 6ms debounce 3'b110 12ms debounce 3'b111 24ms debounce Recommended values are between 3 to 12 ms

39.8.310 E eMMC 4.5 TAP select register (cfio_regs_SCORE_TAP_SEL_REG)—Offset 9F4h

The register is controlling the community debounce



39.9 PCU iLB GPIO S5 IO Addressed Registers

Table 341. Summary of PCU iLB GPIO S5 IO Registers—GBASE + 80h

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"Sus Use Select 1 (cfio_ioreg_SUS_USE_SEL_31_0_)—Offset 0h" on page 5059	00000000h
4–7h	4	"Sus Io Select 1 (cfio_ioreg_SUS_IO_SEL_31_0_)—Offset 4h" on page 5060	00000000h
8–Bh	4	"Sus Gpio Level 1 (cfio_ioreg_SUS_GP_LVL_31_0_)—Offset 8h" on page 5061	00000000h
C–Fh	4	"Sus Trigger Positive Edge Enable 1 (cfio_ioreg_SUS_TPE_31_0_)—Offset Ch" on page 5062	00000000h
10–13h	4	"Sus Trigger Negative Edge Enable 1 (cfio_ioreg_SUS_TNE_31_0_)—Offset 10h" on page 5063	00000000h
14–17h	4	"Sus Trigger Status 1 (cfio_ioreg_SUS_TS_31_0_)—Offset 14h" on page 5063	00000000h
18–1Bh	4	"Sus Wake Enable 1 (cfio_ioreg_SUS_WAKE_EN_31_0_)—Offset 18h" on page 5065	00000000h
20–23h	4	"Sus Use Select 2 (cfio_ioreg_SUS_USE_SEL_43_32_)—Offset 20h" on page 5066	00000000h
24–27h	4	"Sus Io Select 2 (cfio_ioreg_SUS_IO_SEL_43_32_)—Offset 24h" on page 5066	00000000h
28–2Bh	4	"Sus Gpio Level 2 (cfio_ioreg_SUS_GP_LVL_43_32_)—Offset 28h" on page 5067	00000000h
2C–2Fh	4	"Sus Trigger Positive Edge Enable 2 (cfio_ioreg_SUS_TPE_43_32_)—Offset 2Ch" on page 5068	00000000h
30–33h	4	"Sus Trigger Negative Edge Enable 2 (cfio_ioreg_SUS_TNE_43_32_)—Offset 30h" on page 5069	00000000h
34–37h	4	"Sus Trigger Status (cfio_ioreg_SUS_TS_43_32_)—Offset 34h" on page 5070	00000000h
38–3Bh	4	"Sus Wake Enable 2 (cfio_ioreg_SUS_WAKE_EN_43_32_)—Offset 38h" on page 5071	00000000h



39.9.2 Sus Io Select 1 (cfio_ioreg_SUS_IO_SEL_31_0_)—Offset 4h

Access via PCU Proxy, it defines Input Output Select: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) is programmed as an input. When set to 0, the GPIO signal is programmed as an output - Only the 8 lsb are used in VLV. Default values will be read as 0 if IO is not used

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE + 80h] + 4h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	To Select (io_sel): bit 31 - USB_ULPI_0_CLK bit 30 - GPIO_DFX8 bit 29 - GPIO_DFX7 bit 28 - GPIO_DFX6 bit 27 - GPIO_DFX5 bit 26 - GPIO_DFX4 bit 25 - GPIO_DFX3 bit 24 - GPIO_DFX2 bit 23 - GPIO_DFX1 bit 22 - GPIO_DFX0 bit 21 - SPI_CS1_B bit 20 - USB_OC1_B bit 19 - USB_OC0_B bit 18 - SUS_STAT_B bit 17 - PMU_WAKE_LAN_B bit 16 - PMU_PWRBTN_B bit 15 - PMU_WAKE_B bit 14 - PMU_SLP_LAN_B bit 13 - PMU_SLP_S0IX_B bit 12 - PMU_SUSCLK bit 11 - SUSPWRDNACK bit 10 - SEC_GPIO_SUS10 bit 9 - SEC_GPIO_SUS9 bit 8 - SEC_GPIO_SUS8 bit 7 - GPIO_SUS7 bit 6 - GPIO_SUS6 bit 5 - GPIO_SUS5 bit 4 - GPIO_SUS4 bit 3 - GPIO_SUS3 bit 2 - GPIO_SUS2 bit 1 - GPIO_SUS1 bit 0 - GPIO_SUS0



39.9.3 Sus Gpio Level 1 (cfio_ioreg_SUS_GP_LVL_31_0_)—Offset 8h

Access via PCU Proxy, the registers are implemented as dual read/write with dedicated storage for write. Write value will be stored in the write register, while read is coming from the pad directly. If GPIO(n) is programmed to be an output (via the corresponding bit in the GP_IO_SEL register), then the corresponding GP_LVL(n) write register value will drive a high or low value on the output pin. 1 = high, 0 = low. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE + 80h] + 8h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

gp_lvl

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Gpio Level (gp_lvl): bit 31 - USB_ULPI_0_CLK bit 30 - GPIO_DFX8 bit 29 - GPIO_DFX7 bit 28 - GPIO_DFX6 bit 27 - GPIO_DFX5 bit 26 - GPIO_DFX4 bit 25 - GPIO_DFX3 bit 24 - GPIO_DFX2 bit 23 - GPIO_DFX1 bit 22 - GPIO_DFX0 bit 21 - SPI_CS1_B bit 20 - USB_OC1_B bit 19 - USB_OC0_B bit 18 - SUS_STAT_B bit 17 - PMU_WAKE_LAN_B bit 16 - PMU_PWRBTN_B bit 15 - PMU_WAKE_B bit 14 - PMU_SLP_LAN_B bit 13 - PMU_SLP_S0IX_B bit 12 - PMU_SUSCLK bit 11 - SUSPWRDNACK bit 10 - SEC_GPIO_SUS10 bit 9 - SEC_GPIO_SUS9 bit 8 - SEC_GPIO_SUS8 bit 7 - GPIO_SUS7 bit 6 - GPIO_SUS6 bit 5 - GPIO_SUS5 bit 4 - GPIO_SUS4 bit 3 - GPIO_SUS3 bit 2 - GPIO_SUS2 bit 1 - GPIO_SUS1 bit 0 - GPIO_SUS0



39.9.4 Sus Trigger Positive Edge Enable 1 (cfio_ioreg_SUS_TPE_31_0_)—Offset Ch

Access via PCU Proxy, the register trigger Positive Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 0 to 1 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 0 to 1 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE + 80h] + Ch

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
tpe								

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RW	Tpe (tpe): bit 31 - USB_ULPI_0_CLK bit 30 - GPIO_DFX8 bit 29 - GPIO_DFX7 bit 28 - GPIO_DFX6 bit 27 - GPIO_DFX5 bit 26 - GPIO_DFX4 bit 25 - GPIO_DFX3 bit 24 - GPIO_DFX2 bit 23 - GPIO_DFX1 bit 22 - GPIO_DFX0 bit 21 - SPI_CS1_B bit 20 - USB_OC1_B bit 19 - USB_OC0_B bit 18 - SUS_STAT_B bit 17 - PMU_WAKE_LAN_B bit 16 - PMU_PWRBTN_B bit 15 - PMU_WAKE_B bit 14 - PMU_SLP_LAN_B bit 13 - PMU_SLP_SOIX_B bit 12 - PMU_SUSCLK bit 11 - SUSPWRDNACK bit 10 - SEC_GPIO_SUS10 bit 9 - SEC_GPIO_SUS9 bit 8 - SEC_GPIO_SUS8 bit 7 - GPIO_SUS7 bit 6 - GPIO_SUS6 bit 5 - GPIO_SUS5 bit 4 - GPIO_SUS4 bit 3 - GPIO_SUS3 bit 2 - GPIO_SUS2 bit 1 - GPIO_SUS1 bit 0 - GPIO_SUS0



Access via PCU Proxy, When set to a 1, the corresponding GPIO (if enabled in the GPIO_USE_SEL register) if enabled as input via IO_SEL(n), triggered an GPE or SMI. This will be set if a 0 to 1 transition occurred and TPE(n) was set, or a 1 to 0 transition occurred and TNE(n) was set. If both TPE(n) and TNE(n) are set, then this bit will be set on both a 0 to 1 and a 1 to 0 transition. This bit will not be set if the GPIO is configured as an output. - Only the 8 lsb are used in VLV and it cannot be tested by the host

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE + 80h] + 14h


GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h WOC	Ts (ts): bit 31 - USB_ULPI_0_CLK bit 30 - GPIO_DFX8 bit 29 - GPIO_DFX7 bit 28 - GPIO_DFX6 bit 27 - GPIO_DFX5 bit 26 - GPIO_DFX4 bit 25 - GPIO_DFX3 bit 24 - GPIO_DFX2 bit 23 - GPIO_DFX1 bit 22 - GPIO_DFX0 bit 21 - SPI_CS1_B bit 20 - USB_OC1_B bit 19 - USB_OC0_B bit 18 - SUS_STAT_B bit 17 - PMU_WAKE_LAN_B bit 16 - PMU_PWRBTN_B bit 15 - PMU_WAKE_B bit 14 - PMU_SLP_LAN_B bit 13 - PMU_SLP_S0IX_B bit 12 - PMU_SUSCLK bit 11 - SUSPWRDNACK bit 10 - SEC_GPIO_SUS10 bit 9 - SEC_GPIO_SUS9 bit 8 - SEC_GPIO_SUS8 bit 7 - GPIO_SUS7 bit 6 - GPIO_SUS6 bit 5 - GPIO_SUS5 bit 4 - GPIO_SUS4 bit 3 - GPIO_SUS3 bit 2 - GPIO_SUS2 bit 1 - GPIO_SUS1 bit 0 - GPIO_SUS0



39.9.10 Sus Gpio Level 2 (cfio ioreg SUS_GP_LVL_43_32)—Offset 28h

Access Method

Offset: [GBASE + 80h] + 28h**GBASE Type:** PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
reserved2						gp_ivl		

Intel Atom® Processor E3800 Product Family
Datasheet
5067



Access via PCU Proxy, the register trigger Positive Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 0 to 1 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 0 to 1 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE + 80h] + 2Ch

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

Bit Range	Default & Access	Field Name (ID): Description
31:12	0h RO	Reserved (reserved2): Reserved.
11:0	0h RW	Tpe (tpe): bit 11 - USB_ULPI_0_REFCLK bit 10 - USB_ULPI_0_STP bit 9 - USB_ULPI_0_NXT bit 8 - USB_ULPI_0_DIR bit 7 - USB_ULPI_0_DATA7 bit 6 - USB_ULPI_0_DATA6 bit 5 - USB_ULPI_0_DATA5 bit 4 - USB_ULPI_0_DATA4 bit 3 - USB_ULPI_0_DATA3 bit 2 - USB_ULPI_0_DATA2 bit 1 - USB_ULPI_0_DATA1 bit 0 - USB_ULPI_0_DATA0



39.9.12 Sus Trigger Negative Edge Enable 2 (cfio_ioreg_SUS_TNE_43_32_)—Offset 30h

Access via PCU Proxy, the register trigger Negative Edge Enable: When set to a 1, the corresponding GPIO signal (if enabled in the GPIO_USE_SEL register) will case an GPE or SMI when a 1 to 0 transition occurs. When set to 0, the GPIO signal is not enabled to trigger an GPE or SMI on a 1 to 0 transition. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE + 80h] + 30h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved2						tne		

Bit Range	Default & Access	Field Name (ID): Description
31:12	0h RO	Reserved (reserved2): Reserved.
11:0	0h RW	Tne (tne): bit 11 - USB_ULPI_0_REFCLK bit 10 - USB_ULPI_0_STP bit 9 - USB_ULPI_0_NXT bit 8 - USB_ULPI_0_DIR bit 7 - USB_ULPI_0_DATA7 bit 6 - USB_ULPI_0_DATA6 bit 5 - USB_ULPI_0_DATA5 bit 4 - USB_ULPI_0_DATA4 bit 3 - USB_ULPI_0_DATA3 bit 2 - USB_ULPI_0_DATA2 bit 1 - USB_ULPI_0_DATA1 bit 0 - USB_ULPI_0_DATA0



39.9.13 Sus Trigger Status (cfio_ioreg_SUS_TS_43_32_)—Offset 34h

Access via PCU Proxy, When set to a 1, the corresponding GPIO (if enabled in the GPIO_USE_SEL register) if enabled as input via IO_SEL(n), triggered an GPE or SMI. This will be set if a 0 to 1 transition occurred and TPE(n) was set, or a 1 to 0 transition occurred and TNE(n) was set. If both TPE(n) and TNE(n) are set, then this bit will be set on both a 0 to 1 and a 1 to 0 transition. This bit will not be set if the GPIO is configured as an output. - Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE + 80h] + 34h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved2						S		

Bit Range	Default & Access	Field Name (ID): Description
31:12	0h RO	Reserved (reserved2): Reserved.
11:0	0h WOC	Ts (ts): bit 11 - USB_ULPI_0_REFCLK bit 10 - USB_ULPI_0_STP bit 9 - USB_ULPI_0_NXT bit 8 - USB_ULPI_0_DIR bit 7 - USB_ULPI_0_DATA7 bit 6 - USB_ULPI_0_DATA6 bit 5 - USB_ULPI_0_DATA5 bit 4 - USB_ULPI_0_DATA4 bit 3 - USB_ULPI_0_DATA3 bit 2 - USB_ULPI_0_DATA2 bit 1 - USB_ULPI_0_DATA1 bit 0 - USB_ULPI_0_DATA0



39.9.14 Sus Wake Enable 2 (cfio_ioreg_SUS_WAKE_EN_43_32_)— Offset 38h

Access via PCU Proxy, When set to a 1 and TS(n) is set, wake event should be initiated.
- Only the 8 lsb are used in VLV

Access Method

Type: I/O Register
(Size: 32 bits)

Offset: [GBASE + 80h] + 38h

GBASE Type: PCI Configuration Register (Size: 32 bits)

GBASE Reference: [B:0, D:31, F:0] + 48h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
reserved2						wake_en		

Bit Range	Default & Access	Field Name (ID): Description
31:12	0h RO	Reserved (reserved2): Reserved.
11:0	0h RW	Wake Enable (wake_en): bit 11 - USB_ULPI_0_REFCLK bit 10 - USB_ULPI_0_STP bit 9 - USB_ULPI_0_NXT bit 8 - USB_ULPI_0_DIR bit 7 - USB_ULPI_0_DATA7 bit 6 - USB_ULPI_0_DATA6 bit 5 - USB_ULPI_0_DATA5 bit 4 - USB_ULPI_0_DATA4 bit 3 - USB_ULPI_0_DATA3 bit 2 - USB_ULPI_0_DATA2 bit 1 - USB_ULPI_0_DATA1 bit 0 - USB_ULPI_0_DATA0



39.10 PCU iLB GPIO S5 Memory Address Map

Table 342. Summary of iLB GPIO S5 Memory Mapped I/O Registers—I/OBASE + 0x2000

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
0–3h	4	"Usb Oc1 B Pad Configuration (cfio_regs_pad_usb_oc1_b_PCONF0)—Offset 0h" on page 5078	2003CC80h
8–Bh	4	"Usb Oc1 B Pad Value (cfio_regs_pad_usb_oc1_b_PAD_VAL)—Offset 8h" on page 5080	00000002h
10–13h	4	"Pmu Wake B Pad Configuration (cfio_regs_pad_pmu_wake_b_PCONF0)—Offset 10h" on page 5081	2003CC80h
18–1Bh	4	"Pmu Wake B Pad Value (cfio_regs_pad_pmu_wake_b_PAD_VAL)—Offset 18h" on page 5084	00000002h
1C–1Fh	4	"Pmu Wake B Pad Test (cfio_regs_pad_pmu_wake_b_PAD_DFT)—Offset 1Ch" on page 5084	00000400h
20–23h	4	"Spi Cs1 B Pad Configuration (cfio_regs_pad_spi_cs1_b_PCONF0)—Offset 20h" on page 5085	2003EC80h
28–2Bh	4	"Spi Cs1 B Pad Value (cfio_regs_pad_spi_cs1_b_PAD_VAL)—Offset 28h" on page 5088	00000002h
30–33h	4	"Spi Cs0 B Pad Configuration (cfio_regs_pad_spi_cs0_b_PCONF0)—Offset 30h" on page 5089	2003E800h
38–3Bh	4	"Spi Cs0 B Pad Value (cfio_regs_pad_spi_cs0_b_PAD_VAL)—Offset 38h" on page 5091	00000002h
40–43h	4	"Spi Clk Pad Configuration (cfio_regs_pad_spi_clk_PCONF0)—Offset 40h" on page 5092	2003E800h
48–4Bh	4	"Spi Clk Pad Value (cfio_regs_pad_spi_clk_PAD_VAL)—Offset 48h" on page 5094	00000002h
50–53h	4	"Spi Mosi Pad Configuration (cfio_regs_pad_spi_mosi_PCONF0)—Offset 50h" on page 5095	2003EC80h
58–5Bh	4	"Spi Mosi Pad Value (cfio_regs_pad_spi_mosi_PAD_VAL)—Offset 58h" on page 5098	00000002h
60–63h	4	"Spi Miso Pad Configuration (cfio_regs_pad_spi_miso_PCONF0)—Offset 60h" on page 5098	2003EC80h
68–6Bh	4	"Spi Miso Pad Value (cfio_regs_pad_spi_miso_PAD_VAL)—Offset 68h" on page 5101	00000006h
70–73h	4	"Suspwrdsnack Pad Configuration (cfio_regs_pad_suspwrdsnack_PCONF0)—Offset 70h" on page 5102	2003CD00h
78–7Bh	4	"Suspwrdsnack Pad Value (cfio_regs_pad_suspwrdsnack_PAD_VAL)—Offset 78h" on page 5104	00000002h
7C–7Fh	4	"Suspwrdsnack Pad Test (cfio_regs_pad_suspwrdsnack_PAD_DFT)—Offset 7Ch" on page 5105	00000400h
80–83h	4	"Pmu Pwrbtn B Pad Configuration (cfio_regs_pad_pmu_pwrbtn_b_PCONF0)—Offset 80h" on page 5106	2003CC80h
88–8Bh	4	"Pmu Pwrbtn B Pad Value (cfio_regs_pad_pmu_pwrbtn_b_PAD_VAL)—Offset 88h" on page 5108	00000002h
90–93h	4	"Pmu Batlow B Pad Configuration (cfio_regs_pad_pmu_batlow_b_PCONF0)—Offset 90h" on page 5109	2003CC80h
98–9Bh	4	"Pmu Batlow B Pad Value (cfio_regs_pad_pmu_batlow_b_PAD_VAL)—Offset 98h" on page 5112	00000006h
9C–9Fh	4	"Pmu Batlow B Pad Test (cfio_regs_pad_pmu_batlow_b_PAD_DFT)—Offset 9Ch" on page 5112	00000400h



Table 342. Summary of iLB GPIO S5 Memory Mapped I/O Registers—I/OBASE + 0x2000

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
A0–A3h	4	"Pmu Wake Lan B Pad Configuration (cfio_regs_pad_pmu_wake_lan_b_PCONF0)—Offset A0h" on page 5113	2003CC80h
A8–ABh	4	"Pmu Wake Lan B Pad Value (cfio_regs_pad_pmu_wake_lan_b_PAD_VAL)—Offset A8h" on page 5116	00000002h
AC–AFh	4	"Pmu Wake Lan B Pad Test (cfio_regs_pad_pmu_wake_lan_b_PAD_DFT)—Offset ACh" on page 5116	00000400h
B0–B3h	4	"Pmu Susclk Pad Configuration (cfio_regs_pad_pmu_susclk_PCONF0)—Offset B0h" on page 5118	2003CD00h
B8–BBh	4	"Pmu Susclk Pad Value (cfio_regs_pad_pmu_susclk_PAD_VAL)—Offset B8h" on page 5120	00000002h
BC–BFh	4	"Pmu Susclk Pad Test (cfio_regs_pad_pmu_susclk_PAD_DFT)—Offset BCh" on page 5121	00000400h
C0–C3h	4	"Usb Oc0 B Pad Configuration (cfio_regs_pad_usb_oc0_b_PCONF0)—Offset C0h" on page 5122	2003CC80h
C8–CBh	4	"Usb Oc0 B Pad Value (cfio_regs_pad_usb_oc0_b_PAD_VAL)—Offset C8h" on page 5124	00000002h
D0–D3h	4	"Pmu Slp S3 B Pad Configuration (cfio_regs_pad_pmu_slp_s3_b_PCONF0)—Offset D0h" on page 5125	2003C800h
D8–DBh	4	"Pmu Slp S3 B Pad Value (cfio_regs_pad_pmu_slp_s3_b_PAD_VAL)—Offset D8h" on page 5128	00000002h
DC–DFh	4	"Pmu Slp S3 B Pad Test (cfio_regs_pad_pmu_slp_s3_b_PAD_DFT)—Offset DCh" on page 5128	00000400h
E0–E3h	4	"Pmu Ac Present Pad Configuration (cfio_regs_pad_pmu_ac_present_PCONF0)—Offset E0h" on page 5129	2003CD00h
E8–EBh	4	"Pmu Ac Present Pad Value (cfio_regs_pad_pmu_ac_present_PAD_VAL)—Offset E8h" on page 5132	00000006h
EC–EFh	4	"Pmu Ac Present Pad Test (cfio_regs_pad_pmu_ac_present_PAD_DFT)—Offset ECh" on page 5133	00000400h
F0–F3h	4	"Pmu Slp S4 B Pad Configuration (cfio_regs_pad_pmu_slp_s4_b_PCONF0)—Offset F0h" on page 5134	2003C800h
F8–FBh	4	"Pmu Slp S4 B Pad Value (cfio_regs_pad_pmu_slp_s4_b_PAD_VAL)—Offset F8h" on page 5136	00000002h
FC–FFh	4	"Pmu Slp S4 B Pad Test (cfio_regs_pad_pmu_slp_s4_b_PAD_DFT)—Offset FCh" on page 5137	00000400h
100–103h	4	"Pmu Pltrst B Pad Configuration (cfio_regs_pad_pmu_pltrst_b_PCONF0)—Offset 100h" on page 5138	2003C800h
108–10Bh	4	"Pmu Pltrst B Pad Value (cfio_regs_pad_pmu_pltrst_b_PAD_VAL)—Offset 108h" on page 5140	00000002h
10C–10Fh	4	"Pmu Pltrst B Pad Test (cfio_regs_pad_pmu_pltrst_b_PAD_DFT)—Offset 10Ch" on page 5141	00000400h
110–113h	4	"Pmu Slp Lan B Pad Configuration (cfio_regs_pad_pmu_slp_lan_b_PCONF0)—Offset 110h" on page 5142	2003CC80h
118–11Bh	4	"Pmu Slp Lan B Pad Value (cfio_regs_pad_pmu_slp_lan_b_PAD_VAL)—Offset 118h" on page 5145	00000002h
11C–11Fh	4	"Pmu Slp Lan B Pad Test (cfio_regs_pad_pmu_slp_lan_b_PAD_DFT)—Offset 11Ch" on page 5145	00000400h
120–123h	4	"Sec Gpio Sus10 Pad Configuration (cfio_regs_pad_sec_gpio_sus10_PCONF0)—Offset 120h" on page 5146	2003CC80h



Table 342. Summary of iLB GPIO S5 Memory Mapped I/O Registers—I/OBASE + 0x2000

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
128–12Bh	4	"Sec Gpio Sus10 Pad Value (cfio_regs_pad_sec_gpio_sus10_PAD_VAL)—Offset 128h" on page 5149	00000002h
130–133h	4	"Sus Stat B Pad Configuration (cfio_regs_pad_sus_stat_b_PCONF0)—Offset 130h" on page 5150	2003CD00h
138–13Bh	4	"Sus Stat B Pad Value (cfio_regs_pad_sus_stat_b_PAD_VAL)—Offset 138h" on page 5152	00000002h
13C–13Fh	4	"Sus Stat B Pad Test (cfio_regs_pad_sus_stat_b_PAD_DFT)—Offset 13Ch" on page 5153	00000400h
140–143h	4	"Pmu Slp S0ix B Pad Configuration (cfio_regs_pad_pmu_slp_s0ix_b_PCONF0)—Offset 140h" on page 5154	2003CD00h
148–14Bh	4	"Pmu Slp S0ix B Pad Value (cfio_regs_pad_pmu_slp_s0ix_b_PAD_VAL)—Offset 148h" on page 5156	00000002h
14C–14Fh	4	"Pmu Slp S0ix B Pad Test (cfio_regs_pad_pmu_slp_s0ix_b_PAD_DFT)—Offset 14Ch" on page 5157	00000400h
150–153h	4	"Gpio Dfx5 Pad Configuration (cfio_regs_pad_gpio_dfx5_PCONF0)—Offset 150h" on page 5158	2003CC80h
158–15Bh	4	"Gpio Dfx5 Pad Value (cfio_regs_pad_gpio_dfx5_PAD_VAL)—Offset 158h" on page 5161	00000002h
160–163h	4	"Gpio Dfx4 Pad Configuration (cfio_regs_pad_gpio_dfx4_PCONF0)—Offset 160h" on page 5161	2003CD00h
168–16Bh	4	"Gpio Dfx4 Pad Value (cfio_regs_pad_gpio_dfx4_PAD_VAL)—Offset 168h" on page 5164	00000002h
170–173h	4	"Gpio Dfx0 Pad Configuration (cfio_regs_pad_gpio_dfx0_PCONF0)—Offset 170h" on page 5165	2003CD00h
178–17Bh	4	"Gpio Dfx0 Pad Value (cfio_regs_pad_gpio_dfx0_PAD_VAL)—Offset 178h" on page 5167	00000002h
180–183h	4	"Gpio Dfx6 Pad Configuration (cfio_regs_pad_gpio_dfx6_PCONF0)—Offset 180h" on page 5168	2003CC80h
188–18Bh	4	"Gpio Dfx6 Pad Value (cfio_regs_pad_gpio_dfx6_PAD_VAL)—Offset 188h" on page 5170	00000002h
190–193h	4	"Gpio Dfx7 Pad Configuration (cfio_regs_pad_gpio_dfx7_PCONF0)—Offset 190h" on page 5171	2003CC80h
198–19Bh	4	"Gpio Dfx7 Pad Value (cfio_regs_pad_gpio_dfx7_PAD_VAL)—Offset 198h" on page 5174	00000002h
1A0–1A3h	4	"Gpio Dfx8 Pad Configuration (cfio_regs_pad_gpio_dfx8_PCONF0)—Offset 1A0h" on page 5174	2003CC80h
1A8–1ABh	4	"Gpio Dfx8 Pad Value (cfio_regs_pad_gpio_dfx8_PAD_VAL)—Offset 1A8h" on page 5177	00000002h
1B0–1B3h	4	"Gpio Dfx3 Pad Configuration (cfio_regs_pad_gpio_dfx3_PCONF0)—Offset 1B0h" on page 5178	2003CD00h
1B8–1BBh	4	"Gpio Dfx3 Pad Value (cfio_regs_pad_gpio_dfx3_PAD_VAL)—Offset 1B8h" on page 5180	00000002h
1C0–1C3h	4	"Gpio Dfx2 Pad Configuration (cfio_regs_pad_gpio_dfx2_PCONF0)—Offset 1C0h" on page 5181	2003CD00h
1C8–1CBh	4	"Gpio Dfx2 Pad Value (cfio_regs_pad_gpio_dfx2_PAD_VAL)—Offset 1C8h" on page 5183	00000002h
1D0–1D3h	4	"Gpio Sus0 Pad Configuration (cfio_regs_pad_gpio_sus0_PCONF0)—Offset 1D0h" on page 5184	2003CC80h



Table 342. Summary of iLB GPIO S5 Memory Mapped I/O Registers—I/OBASE + 0x2000

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
1D8–1DBh	4	"Gpio Sus0 Pad Value (cfio_regs_pad_gpio_sus0_PAD_VAL)—Offset 1D8h" on page 5187	00000002h
1E0–1E3h	4	"Gpio Sus2 Pad Configuration (cfio_regs_pad_gpio_sus2_PCONF0)—Offset 1E0h" on page 5187	2003CC80h
1E8–1EBh	4	"Gpio Sus2 Pad Value (cfio_regs_pad_gpio_sus2_PAD_VAL)—Offset 1E8h" on page 5190	00000002h
1F0–1F3h	4	"Gpio Sus3 Pad Configuration (cfio_regs_pad_gpio_sus3_PCONF0)—Offset 1F0h" on page 5191	2003CC80h
1F8–1FBh	4	"Gpio Sus3 Pad Value (cfio_regs_pad_gpio_sus3_PAD_VAL)—Offset 1F8h" on page 5193	00000002h
200–203h	4	"Gpio Sus4 Pad Configuration (cfio_regs_pad_gpio_sus4_PCONF0)—Offset 200h" on page 5194	2003CD00h
208–20Bh	4	"Gpio Sus4 Pad Value (cfio_regs_pad_gpio_sus4_PAD_VAL)—Offset 208h" on page 5196	00000002h
210–213h	4	"Gpio Sus1 Pad Configuration (cfio_regs_pad_gpio_sus1_PCONF0)—Offset 210h" on page 5197	2003CC80h
218–21Bh	4	"Gpio Sus1 Pad Value (cfio_regs_pad_gpio_sus1_PAD_VAL)—Offset 218h" on page 5200	00000002h
220–223h	4	"Gpio Sus5 Pad Configuration (cfio_regs_pad_gpio_sus5_PCONF0)—Offset 220h" on page 5201	2003CD00h
228–22Bh	4	"Gpio Sus5 Pad Value (cfio_regs_pad_gpio_sus5_PAD_VAL)—Offset 228h" on page 5203	00000002h
230–233h	4	"Gpio Sus7 Pad Configuration (cfio_regs_pad_gpio_sus7_PCONF0)—Offset 230h" on page 5204	2003CD00h
238–23Bh	4	"Gpio Sus7 Pad Value (cfio_regs_pad_gpio_sus7_PAD_VAL)—Offset 238h" on page 5206	00000002h
240–243h	4	"Gpio Sus6 Pad Configuration (cfio_regs_pad_gpio_sus6_PCONF0)—Offset 240h" on page 5207	2003CD00h
248–24Bh	4	"Gpio Sus6 Pad Value (cfio_regs_pad_gpio_sus6_PAD_VAL)—Offset 248h" on page 5210	00000002h
250–253h	4	"Sec Gpio Sus9 Pad Configuration (cfio_regs_pad_sec_gpio_sus9_PCONF0)—Offset 250h" on page 5210	2003CD00h
258–25Bh	4	"Sec Gpio Sus9 Pad Value (cfio_regs_pad_sec_gpio_sus9_PAD_VAL)—Offset 258h" on page 5213	00000002h
260–263h	4	"Sec Gpio Sus8 Pad Configuration (cfio_regs_pad_sec_gpio_sus8_PCONF0)—Offset 260h" on page 5214	2003CD00h
268–26Bh	4	"Sec Gpio Sus8 Pad Value (cfio_regs_pad_sec_gpio_sus8_PAD_VAL)—Offset 268h" on page 5216	00000002h
270–273h	4	"Gpio Dfx1 Pad Configuration (cfio_regs_pad_gpio_dfx1_PCONF0)—Offset 270h" on page 5217	2003CD00h
278–27Bh	4	"Gpio Dfx1 Pad Value (cfio_regs_pad_gpio_dfx1_PAD_VAL)—Offset 278h" on page 5219	00000002h
280–283h	4	"Usb Ulpi 0 Refclk Pad Configuration (cfio_regs_pad_usb_ulpi_0_refclk_PCONF0)—Offset 280h" on page 5220	2003CD00h
288–28Bh	4	"Usb Ulpi 0 Refclk Pad Value (cfio_regs_pad_usb_ulpi_0_refclk_PAD_VAL)—Offset 288h" on page 5223	00000002h
290–293h	4	"Tck Pad Configuration (cfio_regs_pad_tck_PCONF0)—Offset 290h" on page 5223	2003C900h
298–29Bh	4	"Tck Pad Value (cfio_regs_pad_tck_PAD_VAL)—Offset 298h" on page 5226	00000006h




Table 342. Summary of iLB GPIO S5 Memory Mapped I/O Registers—I/OBASE + 0x2000

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
2A0–2A3h	4	"Trst B Pad Configuration (cfio_regs_pad_trst_b_PCONF0)—Offset 2A0h" on page 5227	2003C880h
2A8–2ABh	4	"Trst B Pad Value (cfio_regs_pad_trst_b_PAD_VAL)—Offset 2A8h" on page 5229	00000006h
2B0–2B3h	4	"Tdi Pad Configuration (cfio_regs_pad_tdi_PCONF0)—Offset 2B0h" on page 5230	2003C880h
2B8–2BBh	4	"Tdi Pad Value (cfio_regs_pad_tdi_PAD_VAL)—Offset 2B8h" on page 5232	00000006h
2C0–2C3h	4	"Tms Pad Configuration (cfio_regs_pad_tms_PCONF0)—Offset 2C0h" on page 5233	2003C880h
2C8–2CBh	4	"Tms Pad Value (cfio_regs_pad_tms_PAD_VAL)—Offset 2C8h" on page 5236	00000006h
2D0–2D3h	4	"Cx Prdy B Pad Configuration (cfio_regs_pad_cx_prdy_b_PCONF0)—Offset 2D0h" on page 5237	2003C880h
2D8–2DBh	4	"Cx Prdy B Pad Value (cfio_regs_pad_cx_prdy_b_PAD_VAL)—Offset 2D8h" on page 5239	00000002h
2E0–2E3h	4	"Cx Preq B Pad Configuration (cfio_regs_pad_cx_preq_b_PCONF0)—Offset 2E0h" on page 5240	2003C880h
2E8–2EBh	4	"Cx Preq B Pad Value (cfio_regs_pad_cx_preq_b_PAD_VAL)—Offset 2E8h" on page 5243	00000006h
2F0–2F3h	4	"Tdo Pad Configuration (cfio_regs_pad_tdo_PCONF0)—Offset 2F0h" on page 5243	2003C800h
2F8–2FBh	4	"Tdo Pad Value (cfio_regs_pad_tdo_PAD_VAL)—Offset 2F8h" on page 5246	00000002h
300–303h	4	"Usb Ulpi 0 Data4 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data4_PCONF0)—Offset 300h" on page 5247	2003CD00h
308–30Bh	4	"Usb Ulpi 0 Data4 Pad Value (cfio_regs_pad_usb_ulpi_0_data4_PAD_VAL)—Offset 308h" on page 5249	00000002h
310–313h	4	"Usb Ulpi 0 Data2 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data2_PCONF0)—Offset 310h" on page 5250	2003CD00h
318–31Bh	4	"Usb Ulpi 0 Data2 Pad Value (cfio_regs_pad_usb_ulpi_0_data2_PAD_VAL)—Offset 318h" on page 5252	00000002h
320–323h	4	"Usb Ulpi 0 Data6 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data6_PCONF0)—Offset 320h" on page 5253	2003CD00h
328–32Bh	4	"Usb Ulpi 0 Data6 Pad Value (cfio_regs_pad_usb_ulpi_0_data6_PAD_VAL)—Offset 328h" on page 5256	00000002h
330–333h	4	"Usb Ulpi 0 Clk Pad Configuration (cfio_regs_pad_usb_ulpi_0_clk_PCONF0)—Offset 330h" on page 5256	2003CD00h
338–33Bh	4	"Usb Ulpi 0 Clk Pad Value (cfio_regs_pad_usb_ulpi_0_clk_PAD_VAL)—Offset 338h" on page 5259	00000002h
340–343h	4	"Usb Ulpi 0 Dir Pad Configuration (cfio_regs_pad_usb_ulpi_0_dir_PCONF0)—Offset 340h" on page 5260	2003CC80h
348–34Bh	4	"Usb Ulpi 0 Dir Pad Value (cfio_regs_pad_usb_ulpi_0_dir_PAD_VAL)—Offset 348h" on page 5262	00000002h
350–353h	4	"Usb Ulpi 0 Nxt Pad Configuration (cfio_regs_pad_usb_ulpi_0_nxt_PCONF0)—Offset 350h" on page 5263	2003CD00h
358–35Bh	4	"Usb Ulpi 0 Nxt Pad Value (cfio_regs_pad_usb_ulpi_0_nxt_PAD_VAL)—Offset 358h" on page 5265	00000002h
360–363h	4	"Usb Ulpi 0 Data1 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data1_PCONF0)—Offset 360h" on page 5266	2003CD00h
368–36Bh	4	"Usb Ulpi 0 Data1 Pad Value (cfio_regs_pad_usb_ulpi_0_data1_PAD_VAL)—Offset 368h" on page 5269	00000002h



Table 342. Summary of iLB GPIO S5 Memory Mapped I/O Registers—I/OBASE + 0x2000

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
370–373h	4	"Usb Ulpi 0 Data3 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data3_PCONF0)—Offset 370h" on page 5269	2003CD00h
378–37Bh	4	"Usb Ulpi 0 Data3 Pad Value (cfio_regs_pad_usb_ulpi_0_data3_PAD_VAL)—Offset 378h" on page 5272	00000002h
380–383h	4	"Usb Ulpi 0 Data0 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data0_PCONF0)—Offset 380h" on page 5273	2003CD00h
388–38Bh	4	"Usb Ulpi 0 Data0 Pad Value (cfio_regs_pad_usb_ulpi_0_data0_PAD_VAL)—Offset 388h" on page 5275	00000002h
390–393h	4	"Usb Ulpi 0 Data5 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data5_PCONF0)—Offset 390h" on page 5276	2003CD00h
398–39Bh	4	"Usb Ulpi 0 Data5 Pad Value (cfio_regs_pad_usb_ulpi_0_data5_PAD_VAL)—Offset 398h" on page 5278	00000002h
3A0–3A3h	4	"Usb Ulpi 0 Data7 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data7_PCONF0)—Offset 3A0h" on page 5279	2003CD00h
3A8–3ABh	4	"Usb Ulpi 0 Data7 Pad Value (cfio_regs_pad_usb_ulpi_0_data7_PAD_VAL)—Offset 3A8h" on page 5282	00000002h
3B0–3B3h	4	"Usb Ulpi 0 Stp Pad Configuration (cfio_regs_pad_usb_ulpi_0_stp_PCONF0)—Offset 3B0h" on page 5282	2003CC80h
3B8–3BBh	4	"Usb Ulpi 0 Stp Pad Value (cfio_regs_pad_usb_ulpi_0_stp_PAD_VAL)—Offset 3B8h" on page 5285	00000002h
610–613h	4	"C71p1cfiomvnsusdfxgpio1 Compensation Configuration (cfio_regs_fam_c71p1cfiomvnsusdfxgpio1_FAM_RCOMP_CFG)—Offset 610h" on page 5286	00078080h
61C–61Fh	4	"C71p1cfiomvnsusdfxgpio1 Compensation DFX Override (cfio_regs_fam_c71p1cfiomvnsusdfxgpio1_FAM_RCOMP_DFX)—Offset 61Ch" on page 5287	01000080h
800–803h	4	"TS0 SSUS Interrupt Status 0 (cfio_regs_REG_TS0_SSUS_IRQ_TS_0)—Offset 800h" on page 5287	00000000h
804–807h	4	"TS1 SSUS Interrupt Status 1 (cfio_regs_REG_TS1_SSUS_IRQ_TS_1)—Offset 804h" on page 5288	00000000h
808–80Bh	4	"TS2 SSUS Interrupt Status 2 (cfio_regs_REG_TS2_SSUS_IRQ_TS_2)—Offset 808h" on page 5289	00000000h
80C–80Fh	4	"TS3 SSUS Interrupt Status 3 (cfio_regs_REG_TS3_SSUS_IRQ_TS_3)—Offset 80Ch" on page 5289	00000000h
850–853h	4	"Itp Strength Group (cfio_regs_itp_STRENGTH)—Offset 850h" on page 5290	0003000Fh
854–857h	4	"Sus Rcomp Strength Group (cfio_regs_sus_rcomp_STRENGTH)—Offset 854h" on page 5290	BABECAFeh
858–85Bh	4	"Sus Spi Strength Group (cfio_regs_sus_spi_STRENGTH)—Offset 858h" on page 5291	0003000Fh
85C–85Fh	4	"Ulpi Strength Group (cfio_regs_ulpi_STRENGTH)—Offset 85Ch" on page 5291	0003000Fh
980–983h	4	"DIRECT IRQ0 SSUS Direct Interrupt Multiplexer 0 (cfio_regs_REG_DIRECT_IRQ0_SSUS_DIRECT_IRQ_0)—Offset 980h" on page 5292	00000000h

Table 342. Summary of iLB GPIO S5 Memory Mapped I/O Registers—I/OBASE + 0x2000

Offset	Size (Bytes)	Register Name (Register Symbol)	Default Value
984–987h	4	"DIRECT IRQ1 SSUS Direct Interrupt Multiplexer 1 (cfio_regs_REG_DIRECT_IRQ1_SSUS_DIRECT_IRQ_1)—Offset 984h" on page 5293	00000000h
988–98Bh	4	"DIRECT IRQ2 SSUS Direct Interrupt Multiplexer 2 (cfio_regs_REG_DIRECT_IRQ2_SSUS_DIRECT_IRQ_2)—Offset 988h" on page 5294	00000000h
98C–98Fh	4	"DIRECT IRQ3 SSUS Direct Interrupt Multiplexer 3 (cfio_regs_REG_DIRECT_IRQ3_SSUS_DIRECT_IRQ_3)—Offset 98Ch" on page 5295	00000000h

39.10.1 Usb Oc1 B Pad Configuration (cfio_regs_pad_usb_oc1_b_PCONF0)—Offset 0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 0h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31				28				24				20				16				12				8				4				0																																																							
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 0				1 0 0 0				0 0 0 0				0 0 0 0																																																							
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				RSVD				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad



Bit Range	Default & Access	Field Name (ID): Description
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924



Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.10.3 Pmu Wake B Pad Configuration (cfio_regs_pad_pmu_wake_b_PCONF0)—Offset 10h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 10h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

[illegible]


Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.




Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is PMU_WAKE_B function 1 is GPIO5_15



Intel Atom® Processor E3800 Product Family
Datasheet
5085





Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.

39.10.7 Spi Cs1 B Pad Value (cfio_regs_pad_spi_cs1_b_PAD_VAL)–Offset 28h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 28h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.10.8 Spi Cs0 B Pad Configuration (cfio_regs_pad_spi_cs0_b_PCONF0)—Offset 30h



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is SPI_CS0_B

39.10.9 Spi Cs0 B Pad Value (cfio_regs_pad_spi_cs0_b_PAD_VAL)—Offset 38h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 38h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + 40h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003E800h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924





Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	11b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is SPI_MOSI



Access Method

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h


Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RO	Reserved (RSVD): Reserved.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

PADs Memory space configuration register

Access Method

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003EC80h



Intel Atom® Processor E3800 Product Family
Datasheet
5099



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	11b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is SPI_MISO

39.10.15 Spi Miso Pad Value (cfio_regs_pad_spi_miso_PAD_VAL)—Offset 68h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 68h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000006h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	1b RO	Reserved (RSVD): Reserved.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.10.16 Suspwrndack Pad Configuration (cfio_regs_pad_suspwrndack_PCONF0)—Offset 70h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 70h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.10.18 Suspwrdsnack Pad Test (cfio_regs_pad_suspwrdsnack_PAD_DFT)—Offset 7Ch

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 7Ch

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000400h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:11	0h RO	Reserved (RSVD): Reserved.
10	1b RW	Bscan Bypass (bscan_bypass): Bypassing the bscan controll
9:6	0000b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.10.21 Pmu Batlow B Pad Configuration (cfio_regs_pad_pmu_batlow_b_PCONF0)—Offset 90h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 90h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31			28				24				20				16				12				8				4				0																			
0 0 1 0			0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 0				1 0 0 0				1 0 0 0				0 0 0 0																			
RSVD			RSVD				RSVD				RSVD				RSVD				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			
disable_second_mask																			ihysctl																															


Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is PMU_BATLOW_B



39.10.24 Pmu Wake Lan B Pad Configuration (cfio_regs_pad_pmu_wake_lan_b_PCONF0)—Offset A0h

Default: 2003CC80h



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + ACh

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000400h

31				28				24				20				16				12				8				4				0					
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0						
RSVD																				bscan_bypass		RSVD				RSVD		RSVD		RSVD		RSVD		RSVD		RSVD	

Bit Range	Default & Access	Field Name (ID): Description
31:11	0h RO	Reserved (RSVD): Reserved.
10	1b RW	Bscan Bypass (bscan_bypass): Bypassing the bscan controll
9:6	0000b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2	0b RO	Reserved (RSVD): Reserved.
1	0b RO	Reserved (RSVD): Reserved.
0	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved

39.10.28 Pmu Susclk Pad Value (cfio_regs_pad_pmu_susclk_PAD_VAL)—Offset B8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + B8h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.10.29 Pmu Susclk Pad Test (cfio_regs_pad_pmu_susclk_PAD_DFT)–Offset BCh

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + BCh

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000400h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:11	0h RO	Reserved (RSVD): Reserved.
10	1b RW	Bscan Bypass (bscan_bypass): Bypassing the bscan controll
9:6	0000b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
1	0b RO	Reserved (RSVD): Reserved.
0	0b RO	Reserved (RSVD): Reserved.

39.10.30 Usb Oc0 B Pad Configuration (cfio_regs_pad_usb_oc0_b_PCONF0)—Offset C0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + C0h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
disable_second_mask	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD	RSVD	RSVD	RSVD
filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihysctl	RSVD	bypass_flop	pull_str
pull_assign	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.






Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is PMU_SLP_S3_B



Intel Atom® Processor E3800 Product Family
Datasheet
5129



Bit Range	Default & Access	Field Name (ID): Description
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.



39.10.38 Pmu Slp S4 B Pad Configuration (cfio_regs_pad_pmu_slp_s4_b_PCONF0)—Offset F0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + F0h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003C800h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + F8h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.10.40 Pmu Slp S4 B Pad Test (cfio_regs_pad_pmu_slp_s4_b PAD_DFT)—Offset FCh

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + FCh

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000400h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:11	0h RO	Reserved (RSVD): Reserved.
10	1b RW	Bscan Bypass (bscan_bypass): Bypassing the bscan controll
9:6	0000b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + 100h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003C800h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924





Access Method

Offset: [IOBASE + 0x2000] + 110h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is PMU_SLP_LAN_B function 1 is GPIO5_14 function 2 is ULPI_RESET_N

39.10.47 Sec Gpio Sus10 Pad Configuration (cfio_regs_pad_sec_gpio_sus10_PCONF0)—Offset 120h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 120h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD						bscan_bypass	RSVD	
							RSVD	RSVD
							RSVD	RSVD
							RSVD	RSVD
							RSVD	RSVD
							RSVD	RSVD

Bit Range	Default & Access	Field Name (ID): Description
31:11	0h RO	Reserved (RSVD): Reserved.
10	1b RW	Bscan Bypass (bscan_bypass): Bypassing the bscan controll
9:6	0000b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2	0b RO	Reserved (RSVD): Reserved.
1	0b RO	Reserved (RSVD): Reserved.
0	0b RO	Reserved (RSVD): Reserved.



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
ihyscti	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved





Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.10.51 Sus Stat B Pad Test (cfio_regs_pad_sus_stat_b_PAD_DFT)–Offset 13Ch

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 13Ch

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000400h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:11	0h RO	Reserved (RSVD): Reserved.
10	1b RW	Bscan Bypass (bscan_bypass): Bypassing the bscan controll
9:6	0000b RO	Reserved (RSVD): Reserved.
5	0b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + 140h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.

39.10.53 Pmu Slp S0ix B Pad Value (cfio regs pad pmu slp s0ix b PAD VAL)—Offset 148h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 148h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + 150h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one



Bit Range	Default & Access	Field Name (ID): Description
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO5_27 function 1 is SUS_OBS_4 function 2 is USH_CRC_RESET function 3 is ICLKPH1 function 4 is GCLKPH function 5 is Cx_BPM0_TX



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + 168h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.



39.10.59 Gpio Dfx0 Pad Configuration (cfio_regs_pad_gpio_dfx0_PCONF0)—Offset 170h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 170h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
RSVD	RSVD	RSVD	RSVD	ihysct	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE + 0x2000] + 180h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



31	28	24	20	16	12	8	4	0			
0	0	0	0	0	0	0	0	0	0	0	0
RSVD									RSVD		
									inenb	ioutenb	pad_val



Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.10.63 Gpio Dfx7 Pad Configuration (cfio_regs_pad_gpio_dfx7_PCONF0)—Offset 190h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 190h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO5_29 function 1 is SUS_OBS_6 function 2 is EXT_TRIG1 function 3 is HFPLL1 function 4 is ICLKPH1 function 5 is Cx_BPM2_TX



Access Method

Offset: [IOBASE + 0x2000] + 198h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.10.65 Gpio Dfx8 Pad Configuration (cfio_regs_pad_gpio_dfx8_PCONF0)—Offset 1A0h

Access Method

Offset: [IOBASE + 0x2000] + 1A0h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
ihysctl	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOs_30 function 1 is SUS_OBS_7 function 2 is SECTAP_TDO function 3 is CCK_ACLKPH function 4 is DCLKPH[1] function 5 is Cx_BPM3_TX

39.10.66 Gpio Dfx8 Pad Value (cfio_regs_pad_gpio_dfx8_PAD_VAL)–Offset 1A8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 1A8h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.10.67 Gpio Dfx3 Pad Configuration (cfio_regs_pad_gpio_dfx3_PCONF0)—Offset 1B0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 1B0h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31				28				24				20				16				12				8				4				0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 1				0 0 0 0				0 0 0 0																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																							
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				RSVD				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																															
disable_second_mask																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved





Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.10.69 Gpio Dfx2 Pad Configuration (cfio_regs_pad_gpio_dfx2_PCONF0)—Offset 1C0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 1C0h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + 1D0h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO_SUS0 function 1 is RO_BYPASS



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.





39.10.75 Gpio Sus3 Pad Configuration (cfio_regs_pad_gpio_sus3_PCONF0)—Offset 1F0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 1F0h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
RSVD	RSVD	RSVD	RSVD	ihysct	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE + 0x2000] + 200h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31				28				24				20				16				12				8				4				0															
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 1				0 0 0 0				0 0 0 0																			
RSVD				direct_irq_en				RSVD				filter_en				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				func_pin_mux			
RSVD				gd_tne				RSVD				filter_slow				RSVD				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				func_pin_mux			
disable_second_mask				gd_tpe				RSVD				slow_clkgate				RSVD				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				func_pin_mux			
RSVD				gd_level				RSVD				fast_clkgate				RSVD				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad



Bit Range	Default & Access	Field Name (ID): Description
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924



Bit Range	Default & Access	Field Name (ID): Description
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO_SUS4 function 1 is SEC_TDO function 2 is USH_HPB[17] function 3 is SSA_MISR_S2CDAT function 4 is Unused function 5 is Unused function 6 is Unused function 7 is DFX_VISA_OBS2

39.10.78 Gpio Sus4 Pad Value (cfio_regs_pad_gpio_sus4_PAD_VAL)—Offset 208h

PADs Memory space Value register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 208h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h



Intel Atom® Processor E3800 Product Family
Datasheet
5197



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



39.10.81 Gpio Sus5 Pad Configuration (cfio_regs_pad_gpio_sus5_PCONF0)—Offset 220h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 220h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
RSVD	RSVD	RSVD	RSVD	ihysct	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE + 0x2000] + 230h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31				28				24				20				16				12				8				4				0															
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 1				0 0 0 0				0 0 0 0																			
RSVD				direct_irq_en				RSVD				filter_en				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				func_pin_mux			
RSVD				gd_tne				RSVD				filter_slow				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				func_pin_mux							
disable_second_mask				gd_tpe				RSVD				slow_clkgate				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				func_pin_mux							
RSVD				gd_level				RSVD				fast_clkgate				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				func_pin_mux							

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad



Bit Range	Default & Access	Field Name (ID): Description
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924



Bit Range	Default & Access	Field Name (ID): Description
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO_SUS7 function 1 is PMU_SUSCLK3 function 2 is USH_HBP[20] function 3 is SSA_MISR_C2CDAT function 4 is Unused function 5 is Unused function 6 is Unused function 7 is DFX_VISA_OBS5

39.10.84 Gpio Sus7 Pad Value (cfio_regs_pad_gpio_sus7_PAD_VAL)—Offset 238h

PADs Memory space Value register

Access Method


Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 238h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h



Intel Atom® Processor E3800 Product Family
Datasheet
5207



Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO_SUS6 function 1 is PMU_SUSCLK2 function 2 is USH_HBP[15] function 3 is SSA_MISR_C2CREQ function 4 is Unused function 5 is Unused function 6 is Unused function 7 is DFX_VISA_OBS4



Access Method

Offset: [IOBASE + 0x2000] + 248h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

PADs Memory space configuration register

Access Method

Offset: [IOBASE + 0x2000] + 250h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
ihyscti	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is SEC_GPIO_SUS9 function 1 is Unused function 2 is USH_HBP[13] function 3 is MCSI_LPDEBUG[1] function 4 is DUN0_MISR_DATA_OUT_B function 5 is DUN1_MISR_DATA_OUT_B function 6 is Unused function 7 is DFX_VISA_OBS7

39.10.88 Sec Gpio Sus9 Pad Value (cfio_regs_pad_sec_gpio_sus9_PAD_VAL)—Offset 258h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 258h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.10.89 Sec Gpio Sus8 Pad Configuration (cfio_regs_pad_sec_gpio_sus8_PCONF0)—Offset 260h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 260h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Access Method

Offset: [IOBASE + 0x2000] + 268h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required



Bit Range	Default & Access	Field Name (ID): Description
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switching to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter. Note: If changing from 0 to 1, it will change to slow clock. If changing from 1 to 0, it will change to fast clock.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924

Bit Range	Default & Access	Field Name (ID): Description
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO5_23 function 1 is SUS_OBS_0 function 2 is USH_CRC_DEBUG function 3 is CCLKPH1[0] function 4 is GCLKPH function 5 is Cx_BPM0_TX

39.10.92 Gpio Dfx1 Pad Value (cfio_regs_pad_gpio_dfx1_PAD_VAL)–Offset 278h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 278h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]





Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOs_43 function 1 is USB_ULPI_0_REFCLK function 2 is USH_HBP[11] function 3 is MCSI_LPDEBUG[3]



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + 298h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000006h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	1b RO	Reserved (RSVD): Reserved.
1	1b RO	Reserved (RSVD): Reserved.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.



Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
10:9	00b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is TRST_B

39.10.98 Trst B Pad Value (cfio_regs_pad_trst_b_PAD_VAL)—Offset 2A8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 2A8h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000006h

31				28				24				20				16				12				8				4				0			
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	0				
RSVD												RSVD																RSVD		RSVD		pad val			

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + 2B0h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003C880h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is TDI

39.10.100 Tdi Pad Value (cfio_regs_pad_tdi_PAD_VAL)—Offset 2B8h

PADs Memory space Value register



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1



Access Method

Offset: [IOBASE + 0x2000] + 2E0h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003C880h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
27	0b RO	Reserved (RSVD): Reserved.
26	0b RO	Reserved (RSVD): Reserved.
25	0b RO	Reserved (RSVD): Reserved.
24	0b RO	Reserved (RSVD): Reserved.
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RO	Reserved (RSVD): Reserved.
18	0b RO	Reserved (RSVD): Reserved.
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is CX_PREQ_B



Bit Range	Default & Access	Field Name (ID): Description
17	1b RO	Slow Clkgate (slow_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
16	1b RO	Fast Clkgate (fast_clkgate): Reserved as 1 Reserved (RSVD): Reserved.
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	00b RO	Reserved (RSVD): Reserved.
8:7	00b RO	Reserved (RSVD): Reserved.
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



39.10.109 Usb Ulpi 0 Data4 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data4_PCONF0)—Offset 300h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 300h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihscti
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	bypass_flop	pull_str
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	pull_assign	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Bit Range	Default & Access	Field Name (ID): Description
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO5_36 function 1 is USB_ULPI_0_DATA4 function 2 is USH_HBP[6] function 3 is MCSI_LPDEBUG[10]

39.10.110 Usb Ulpi 0 Data4 Pad Value (cfio_regs_pad_usb_ulpi_0_data4_PAD_VAL)—Offset 308h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 308h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.



Access Method

Offset: [IOBASE + 0x2000] + 310h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.





Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.10.113 Usb Ulpi 0 Data6 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data6_PCONF0)—Offset 320h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 320h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31				28				24				20				16				12				8				4				0																																																																			
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 1				0 0 0 0				0 0 0 0				0 0 0 0																																																																			
RSVD				RSVD				disable_second_mask				RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				RSVD				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOs_38 function 1 is USB_ULPI_0_DATA6 function 2 is USH_HBP[4] function 3 is MCSI_LPDEBUG[8]

39.10.114 Usb Ulpi 0 Data6 Pad Value (cfio_regs_pad_usb_ulpi_0_data6_PAD_VAL)—Offset 328h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 328h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.10.115 Usb Ulpi 0 Clk Pad Configuration (cfio regs pad usb ulpi 0 clk PCONF0)—Offset 330h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 330h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h



31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
ihyscti	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOs_31 function 1 is USB_ULPI_0_CLK function 2 is USH_HBP_CLK1 function 3 is MCS1_LPDEBUG[15]

39.10.116 Usb Ulpi 0 Clk Pad Value (cfio_regs_pad_usb_ulpi_0_clk_PAD_VAL)—Offset 338h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 338h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



Access Method

Offset: [IOBASE + 0x2000] + 340h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved

39.10.118 Usb Ulpi 0 Dir Pad Value (cfio_regs_pad_usb_ulpi_0_dir_PAD_VAL)—Offset 348h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 348h


IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.



Bit Range	Default & Access	Field Name (ID): Description
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pin_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.10.119 Usb Ulpi 0 Nxt Pad Configuration (cfio_regs_pad_usb_ulpi_0_nxt_PCONF0)—Offset 350h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 350h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
RSVD	RSVD	RSVD	RSVD	ihyscti	RSVD	bypass_flop	pull_str	pull_assign
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO5_41 function 1 is USB_ULPI_0_NXT function 2 is USH_HBP[1] function 3 is MCS1_LPDEBUG[5]

39.10.120 Usb Ulpi 0 Nxt Pad Value (cfio_regs_pad_usb_ulpi_0_nxt_PAD_VAL)—Offset 358h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 358h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]



Access Method

Offset: [IOBASE + 0x2000] + 360h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31				28				24				20				16				12				8				4				0																																																							
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 1				0 0 0 0				0 0 0 0				0 0 0 0																																																							
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				RSVD				filter_en				filter_slow				slow_cikgate				fast_cikgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO3_33 function 1 is USB_ULPI_0_DATA1 function 2 is USH_HBP[9] function 3 is MCS1_LPDEBUG[13]

31				28				24				20				16				12				8				4				0																																																							
0 0 1 0				0 0 0 0				0 0 0 0				0 0 1 1				1 1 0 0				1 1 0 1				0 0 0 0				0 0 0 0																																																											
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				RSVD				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



Access Method

Offset: [IOBASE + 0x2000] + 378h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



39.10.125 Usb Ulpi 0 Data0 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data0_PCONF0)—Offset 380h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 380h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD	ihscti
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	bypass_flop	pull_str
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	pull_assign	RSVD
RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved



Bit Range	Default & Access	Field Name (ID): Description
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIO5_32 function 1 is USB_ULPI_0_DATA0 function 2 is USH_HBP[10] function 3 is MCS1_LPDEBUG[14]

39.10.126 Usb Ulpi 0 Data0 Pad Value (cfio_regs_pad_usb_ulpi_0_data0_PAD_VAL)—Offset 388h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 388h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.



Access Method

Offset: [IOBASE + 0x2000] + 390h

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

31	28				24				20				16				12				8				4				0																																																										
0	0	1	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0	0	1	1	0	1	0	0	0	0	0	0	0	0																																																									
RSVD				direct_irq_en				gd_tne				gd_tpe				gd_level				RSVD				RSVD				RSVD				filter_en				filter_slow				slow_clkgate				fast_clkgate				RSVD				ihysctl				RSVD				bypass_flop				pull_str				pull_assign				RSVD				RSVD				RSVD				func_pin_mux			

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq



Bit Range	Default & Access	Field Name (ID): Description
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.

[illegible]



Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must be cleared to allow this register to reflect the output state.

39.10.129 Usb Ulpi 0 Data7 Pad Configuration (cfio_regs_pad_usb_ulpi_0_data7_PCONF0)—Offset 3A0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 3A0h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CD00h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.



Bit Range	Default & Access	Field Name (ID): Description
14:13	10b RW	Ihysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	10b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.
2:0	000b RW	Func Pin Mux (func_pin_mux): Func_Pin_Mux: Functional Pin Muxing Default function is always 0. These 3 bits are setting the memory function. function 0 is GPIOs_39 function 1 is USB_ULPI_0_DATA7 function 2 is USH_HBP[3] function 3 is MCSI_LPDEBUG[7]

39.10.130 Usb Ulpi 0 Data7 Pad Value
(**cfio_regs_pad_usb_ulpi_0_data7_PAD_VAL**)—Offset 3A8h

PADs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 3A8h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000002h

	31	28	24	20	16	12	8	4	0									
	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	
	RSVD								RSVD							linenb	ioutenb	pad_val

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.

39.10.131 Usb Ulpi 0 Stp Pad Configuration (cfio regs_pad_usb_ulpi_0_stp_PCONF0)—Offset 3B0h

PADs Memory space configuration register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 3B0h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 2003CC80h




31	28	24	20	16	12	8	4	0
0	0	1	0	0	0	0	0	0
RSVD	RSVD	disable_second_mask	RSVD	direct_irq_en	gd_tne	gd_tpe	gd_level	RSVD
RSVD	RSVD	RSVD	RSVD	filter_en	filter_slow	slow_clkgate	fast_clkgate	RSVD
ihyscti	RSVD	bypass_flop	pull_str	pull_assign	RSVD	RSVD	RSVD	func_pin_mux

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30	0b RO	Reserved (RSVD): Reserved.
29	1b RW	Disable Second Mask (disable_second_mask): Reserved as one
28	0b RO	Reserved (RSVD): Reserved.
27	0b RW	Direct Irq En (direct_irq_en): If this bit is set, interrupt will use direct wire and not shared. This bit should be cleared if io access mode is selected for this pad
26	0b RW	Gd Tne (gd_tne): Negative edge detect for general detect event. 0 - No falling edge detect. 1 - Detect falling edge. For level interrupt mode it will enable active low level irq
25	0b RW	Gd Tpe (gd_tpe): Positive edge detect for general detect event. 0 - No rising edge detect. 1 - Detect rising edge. For level interrupt mode it will enable active high level irq
24	0b RW	Gd Level (gd_level): When this bit is set a level irq will be choose and not edge irq
23	0b RO	Reserved (RSVD): Reserved.
22:21	0h RO	Reserved (RSVD): Reserved.
20	0b RO	Reserved (RSVD): Reserved.
19	0b RW	Filter En (filter_en): Enabling the glitch filter.
18	0b RW	Filter Slow (filter_slow): Switchg to slow mode glitch filter, using 32KHz clock with 62.5us glitch window filter.
17	1b RW	Slow Clkgate (slow_clkgate): Reserved as 1



Bit Range	Default & Access	Field Name (ID): Description
16	1b RW	Fast Clkgate (fast_clkgate): Reserved as 1
15	1b RO	Reserved (RSVD): Reserved.
14:13	10b RW	Thysctl (ihysctl): Hysteresis control. 00: min vil(V) - 0.61254 max vih(V) - 1.19637 min vil(%) - 36.9 max vih(%) - 63.9 min hysteresis(V) - 0.25232 01: min vil(V) - 0.6391 max vih(V) - 1.19637 min vil(%) - 38.5 max vih(%) - 63.9 min hysteresis(V) - 0.21912 10: min vil(V) - 0.61254 max vih(V) - 1.16991 min vil(%) - 36.9 max vih(%) - 62.3 min hysteresis(V) - 0.22244 11: min vil(V) - 0.6391 max vih(V) - 1.16991 min vil(%) - 38.5 max vih(%) - 62.3 min hysteresis(V) - 0.18924
12	0b RO	Reserved (RSVD): Reserved.
11	1b RO	Bypass Flop (bypass_flop): Reserved as 1
10:9	10b RW	Pull Str (pull_str): Pull strength: 00 - 2K 01 - reserved 10 - 20K 11 - reserved
8:7	01b RW	Pull Assign (pull_assign): Pull assignment is only applicable when pad is in input mode. 00 - Non pull 01 - Pull up 10 - Pull down 11 - reserved
6:5	00b RO	Reserved (RSVD): Reserved.
4	0b RO	Reserved (RSVD): Reserved.
3	0b RO	Reserved (RSVD): Reserved.



PADs Memory space Value register

Type: Memory Mapped I/O Register
(Size: 32 bits)

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

Default: 00000002h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:22	0h RO	Reserved (RSVD): Reserved.
21:3	0h RO	Reserved (RSVD): Reserved.
2	0b RW	Iinenb (iinenb): input disable. 0 - input enabled 1 - input disabled. This bit must be cleared if output readback is required
1	1b RW	Ioutenb (ioutenb): output disable. 0 - output enabled 1 - output disabled.
0	0b RW	Pad Val (pad_val): Use this bit to set the output value or to read the pin state in memory mapped GPIO mode. Memory mapped GPIO mode is enabled when this configurable pad is set to the GPIO function via its respective func_pn_mux field and only accessed via memory mapped registers. When used as a memory mapped GPIO output, clear both ioutenb and iinenb bits. Even when used as output, the iinenb bit must to cleared to allow this register to reflect the output state.



Bit Range	Default & Access	Field Name (ID): Description
1	0b RO	Reserved (RSVD): Reserved.
0	0b RW	Ircdfx Select (ircdfx_select): Bypass RCOMP calibration values and use DFX values instead. Setting this bit (1) would let ircdfx_pstr and ircdfx_nstr value loaded into all buffers.

39.10.134 C71p1cfiomvnsusdfxgpio1 Compensation DFX Override (cfio_regs_fam_c71p1cfiomvnsusdfxgpio1_FAM_RCOMP_DFX) —Offset 61Ch

FAMs Memory space Value register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 61Ch

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 01000080h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:16	0100h RW	Ircdfx Pstr (ircdfx_pstr): Override strength compensation p-leg value. Should be 50ohm typical corner.
15:0	0080h RW	Ircdfx Nstr (ircdfx_nstr): Override strength compensation n-leg value. Should be 50ohm typical corner.

39.10.135 TS0 SSUS Interrupt Status 0 (cfio_regs_REG_TS0_SSUS_IRQ_TS_0)—Offset 800h

IRQ TS 0 status register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 800h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h



Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RWOC	Status (status): Trigger IRQ Status: Write one to clear. This status is reflecting IRQ in MMIO access mode only Bellow is the given list of gpio number and pads, the irq status refers to bit 11 - USB_ULPI_0_REFCLK bit 10 - USB_ULPI_0_STP bit 9 - USB_ULPI_0_NXT bit 8 - USB_ULPI_0_DIR bit 7 - USB_ULPI_0_DATA7 bit 6 - USB_ULPI_0_DATA6 bit 5 - USB_ULPI_0_DATA5 bit 4 - USB_ULPI_0_DATA4 bit 3 - USB_ULPI_0_DATA3 bit 2 - USB_ULPI_0_DATA2 bit 1 - USB_ULPI_0_DATA1 bit 0 - USB_ULPI_0_DATA0

39.10.137 TS2 SSUS Interrupt Status 2 (cfio_regs_REG_TS2_SSUS_IRQ_TS_2)—Offset 808h

IRQ TS 2 status register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 808h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:0	00000000h RWOC	Status (status): Trigger IRQ Status: Write one to clear. This status is reflecting IRQ in MMIO access mode only Below is the given list of gpio number and pads, the irq status refers to

39.10.138 TS3 SSUS Interrupt Status 3 (cfio_regs_REG_TS3_SSUS_IRQ_TS_3)—Offset 80Ch

IRQ TS 3 status register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 80Ch

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h



Access Method

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 0003000Fh

Bit Range	Default & Access	Field Name (ID): Description
31:16	0003h RW	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	000Fh RW	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.10.140 Sus Rcomp Strength Group (cfio_regs_sus_rcomp_STRENGTH)—Offset 854h

Access Method

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: BABECAFEh

31	28	24	20	16	12	8	4	0
1	0	1	1	1	0	1	0	1
0	1	1	0	1	0	1	1	1
1	0	1	0	1	1	1	1	0
1	0	1	1	1	0	1	0	1
1	0	0	0	1	0	1	0	1
1	0	1	0	1	1	1	1	0
1	1	1	1	1	1	1	1	0
pnstr					nstr			



Bit Range	Default & Access	Field Name (ID): Description
31:16	babeh RO	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	cafeh RO	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.10.141 Sus Spi Strength Group (cfio_regs_sus_spi_STRENGTH)—Offset 858h

P and N strength register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 858h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 0003000Fh

[illegible]

Bit Range	Default & Access	Field Name (ID): Description
31:16	0003h RW	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	000Fh RW	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.10.142 Uipi Strength Group (cfio_regs_ulpi_STRENGTH)—Offset 85Ch

P and N strength register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 85Ch

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 0003000Fh

31				28					24					20					16					12					8					4					0										
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	1	1	0											
										pstr																				nstr																			



Bit Range	Default & Access	Field Name (ID): Description
31:16	0003h RW	Pstr (pstr): positive strength - for cfiohvio buffers, only the 2 lsb bits will be used
15:0	000Fh RW	Nstr (nstr): negative strength - for cfiohvio buffers, only the 3 lsb bits will be used

39.10.143 DIRECT IRQ0 SSUS Direct Interrupt Multiplexer 0 (cfio_regs_REG_DIRECT_IRQ0_SSUS_DIRECT_IRQ_0)—Offset 980h

Direct irq select register for irq 0 - 3.

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 980h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31				28				24				20				16				12				8				4				0							
0				0				0				0				0				0				0				0				0				0			
RSVD				direct3				RSVD				direct2				RSVD				direct1				RSVD				direct0											

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30:24	000000b RW	Direct3 (direct3): Selects the 3rd direct irq.
23	0b RO	Reserved (RSVD): Reserved.
22:16	000000b RW	Direct2 (direct2): Selects the 2nd direct irq.
15	0b RO	Reserved (RSVD): Reserved.
14:8	000000b RW	Direct1 (direct1): Selects the 1st direct irq.
7	0b RO	Reserved (RSVD): Reserved.
6:0	000000b RW	Direct0 (direct0): Selects the direct irq 0.



39.10.144 DIRECT IRQ1 SSUS Direct Interrupt Multiplexer 1 (cfio_regs_REG_DIRECT_IRQ1_SSUS_DIRECT_IRQ_1)—Offset 984h

Direct irq select register for irq 4 - 7

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 984h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD	direct7	rsv6	direct6	rsv5	direct5	RSVD	direct4	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30:24	0000000b RW	Direct7 (direct7): Selects the 7th direct irq.
23	0b RO	Rsv6 (rsv6): reserved
22:16	0000000b RW	Direct6 (direct6): Selects the 6th direct irq.
15	0b RO	Rsv5 (rsv5): reserved
14:8	0000000b RW	Direct5 (direct5): Selects the 5th direct irq.
7	0b RO	Reserved (RSVD): Reserved.
6:0	0000000b RW	Direct4 (direct4): Selects the 4th direct irq.



39.10.145 DIRECT IRQ2 SSUS Direct Interrupt Multiplexer 2 (cfio_regs_REG_DIRECT_IRQ2_SSUS_DIRECT_IRQ_2)—Offset 988h

Direct irq select register for irq 8 - 11

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 988h

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31				28				24				20				16				12				8				4				0			
0				0				0				0				0				0				0				0				0			
RSVD				direct11				RSVD				direct10				RSVD				direct9				RSVD				direct8							

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30:24	0000000b RW	Direct11 (direct11): Selects the 11th direct irq.
23	0b RO	Reserved (RSVD): Reserved.
22:16	0000000b RW	Direct10 (direct10): Selects the 10th direct irq.
15	0b RO	Reserved (RSVD): Reserved.
14:8	0000000b RW	Direct9 (direct9): Selects the 9th direct irq.
7	0b RO	Reserved (RSVD): Reserved.
6:0	0000000b RW	Direct8 (direct8): Selects the 8th direct irq.



39.10.146 DIRECT IRQ3 SSUS Direct Interrupt Multiplexer 3 (cfio_regs_REG_DIRECT_IRQ3_SSUS_DIRECT_IRQ_3)—Offset 98Ch

Direct irq select register for irq 12 - 15

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

Offset: [IOBASE + 0x2000] + 98Ch

IOBASE + 0x2000 Type: PCI Configuration Register (Size: 32 bits)

IOBASE + 0x2000 Reference: [B:0, D:31, F:0] + 4Ch

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
RSVD	direct15	rsv14	direct14	RSVD	direct13	RSVD	direct12	

Bit Range	Default & Access	Field Name (ID): Description
31	0b RO	Reserved (RSVD): Reserved.
30:24	0000000b RW	Direct15 (direct15): Selects the 15th direct irq. S
23	0b RO	Rsv14 (rsv14): reserved
22:16	0000000b RW	Direct14 (direct14): Selects the 14th direct irq.
15	0b RO	Reserved (RSVD): Reserved.
14:8	0000000b RW	Direct13 (direct13): Selects the 13th direct irq.
7	0b RO	Reserved (RSVD): Reserved.
6:0	0000000b RW	Direct12 (direct12): Selects the 12th direct irq.

40 *PCU – iLB – Interrupt Decoding and Routing*

The interrupt decoder is responsible for receiving interrupt messages from other devices in the SoC and decoding them for consumption by the interrupt router, the [PCU – iLB – 8259 Programmable Interrupt Controllers \(PIC\)](#) and/or the [PCU – iLB – IO APIC](#).

The interrupt router is responsible for mapping each incoming interrupt to the appropriate PIRQx, for consumption by the [PCU – iLB – 8259 Programmable Interrupt Controllers \(PIC\)](#) and/or [PCU – iLB – IO APIC](#).

40.1 Features

40.1.1 Interrupt Decoder

The interrupt decoder receives interrupt messages from devices in the SoC. These interrupts can be split into two primary groups:

- For consumption by the interrupt router
- For consumption by the 8259 PIC

40.1.1.1 For Consumption by the Interrupt Router

When a PCI-mapped device in the SoC asserts or de-asserts an INT[A:D] interrupt, an interrupt message is sent to the decoder. This message is decoded to indicate to the interrupt router which specific interrupt is asserted or de-asserted and which device the INT[A:D] interrupt originated from.


40.1.1.2 For Consumption by the 8259 PIC

When a device in the SoC asserts or de-asserts a legacy interrupt (IRQ), an interrupt message is sent to the decoder. This message is decoded to indicate to the 8259 PIC, which specific interrupt (IRQ[3, 14 or 15]) was asserted or de-asserted.

40.1.2 Interrupt Router

The interrupt router aggregates the INT[A:D] interrupts for each PCI-mapped device in the SoC, received from the interrupt decoder, and the INT[A:D] interrupts direct from the Serialized IRQ controller. It then maps these aggregated interrupts to 8 PCI based interrupts: PIRQ[A:H]. This mapping is configured using the IR[31:0] registers.

PCI based interrupts PIRQ[A:H] are then available for consumption by either the 8259 PICs or the IO-APIC, depending on the configuration of the 8 PIRQx Routing Control Registers: PIRQA, PIQRB, PIRQC, PIRQD, PIRQE, PIRQF, PIRQG, PIRQH.



40.1.2.1 Routing PCI Based Interrupts to 8259 PIC


The interrupt router can be programmed to allow PIRQA-PIRQH to be routed internally to the 8259 as ISA compatible interrupts IRQ 3–7, 9–12 & 14–15. The assignment is programmable through the 8 PIRQx Routing Control Registers: PIRQA, PIQRB, PIRQC, PIRQD, PIRQE, PIRQF, PIRQG, PIRQH. One or more PIRQs can be routed to the same IRQ input. If ISA Compatible Interrupts are not required, the Route registers can be programmed to disable steering.

The PIRQx# lines are defined as active low, level sensitive. When a PIRQx# is routed to specified IRQ line, software must change the IRQ's corresponding ELCR bit to level sensitive mode. The SoC internally inverts the PIRQx# line to send an active high level to the PIC. When a PCI interrupt is routed onto the PIC, the selected IRQ can no longer be used by an active high device (through SERIRQ). However, active low interrupts can share their interrupt with PCI interrupts.

§


41 PCU – iLB – IO APIC

The IO Advanced Programmable Interrupt Controller (APIC) is used to support line interrupts more flexibly than the 8259 PIC. Line interrupts are routed to it from multiple sources, including legacy devices, via the interrupt decoder and serial IRQs, or they are routed to it from the interrupt router in the iLB. These line based interrupts are then used to generate interrupt messages targeting the local APIC in the processor.




41.1 Features

- 87 interrupt lines
 - IRQ0-86
- Edge or level trigger mode per interrupt
- Active low or high polarity per interrupt
- Works with local APIC in processor via MSIs
- MSIs can target specific processor core
- Established APIC programming model

Figure 138. Detailed Block Diagram

MSIs generated by the I/O APIC are sent as 32-bit memory writes to the Local APIC. The address and data of the write transaction are used as follows.

Figure 139. MSI Address and Data



Destination ID (DID) and Extended Destination ID (EDID) are used to target a specific processor core's local APIC.

41.2 Use


The I/O APIC contains indirectly accessed I/O APIC registers and normal memory mapped registers. There are three memory mapped registers:

- Index Register (IDX)
- Window Register (WDW)
- End Of Interrupt Register (EOI)

The Index register selects an indirect I/O APIC register (ID/VS/RTE[n]) to appear in the Window register.

The Window register is used to read or write the indirect register selected by the Index register.

The EOI register is written to by the Local APIC in the processor. The I/O APIC compares the lower eight bits written to the EOI register to the Vector set for each interrupt (RTE.VCT). All interrupts that match this vector will have their RTE.RIRR register cleared. All other EOI register bits are ignored.



41.3 Indirect I/O APIC Registers

These registers are selected with the IDX register, and read/written through the WDW register. Accessing these registers must be done as DW requests, otherwise unspecified behavior will result. Software should not attempt to write to reserved registers. Reserved registers may return non-zero values when read.

Note: There is one pair of redirection (RTE) registers per interrupt line. Each pair forms a 64-bit RTE register.

Note: Specified offsets should be placed in IDX, not added to IDX.

§



41.4 PCU iLB IO APIC Memory Mapped I/O Registers

Table 343. Summary of PCU iLB I/O APIC Memory Mapped I/O Registers—

Offset	Size	Register ID—Description	Default Value
FEC00000h	1	"IDX (IOAPIC_IDX)—Offset FEC00000h" on page 5302	00h
FEC00010h	4	"WDW (IOAPIC_WDW)—Offset FEC00010h" on page 5302	00000000h
FEC00040h	4	"EOI (IOAPIC_EOI)—Offset FEC00040h" on page 5303	00000000h

41.4.1 IDX (IOAPIC_IDX)—Offset FEC00000h

Index Register

Access Method

Type: Memory Mapped I/O Register
(Size: 8 bits)

IOAPIC_IDX: FEC00000h

Default: 00h

7	4	0
0	0	0
1IDX		

Bit Range	Default & Access	Description
7:0	0h RW	IDX: This 8-bit register selects which indirect register appears in the window register to be manipulated by software. Software will program this register to select the desired APIC internal register.

41.4.2 WDW (IOAPIC_WDW)—Offset FEC00010h

Window Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

IOAPIC_WDW: FEC00010h

Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
WDW								

Bit Range	Default & Access	Description
31:0	0h RW	WDW: This 32-bit register specifies the data to be read or written to the register pointed to by the IDX register. This register can be accessed only in DW quantities.



41.4.3 EOI (IOAPIC_EOI)—Offset FEC00040h

EOI Register

Access Method

Type: Memory Mapped I/O Register
(Size: 32 bits)

IOAPIC_EOI: FEC00040h


Default: 00000000h

31	28	24	20	16	12	8	4	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
0	0	0	0	0	0	0	0	0
RESERVED1							EOI	

Bit Range	Default & Access	Description
31:8	0b WO	RESERVED (RESERVED1): Reserved.
7:0	0h WO	EOI: When a write is issued to this register, the IOxAPIC will check the lower 8 bits written to this register, and compare it with the vector field for each entry in the I/O Redirection Table. When a match is found, RTE.RIRR for that entry will be cleared. If multiple entries have the same vector, each of those entries will have RTE.RIRR cleared.

42 PCU – iLB – 8259 Programmable Interrupt Controllers (PIC)


The SoC provides an ISA-compatible programmable interrupt controller (PIC) that incorporates the functionality of two, cascaded 8259 interrupt controllers.



42.1 Features

In addition to providing support for ISA compatible interrupts, this interrupt controller can also support PCI based interrupts (PIRQs) by mapping the PCI interrupt onto a compatible ISA interrupt line. Each 8259 controller supports eight interrupts, numbered 0–7. [Table 344](#) shows how the controllers are connected.

Note: The SoC does not implement any external PIRQ# signals. The PIRQs referred to in this chapter originate from the interrupt routing unit.

**Table 344. Interrupt Controller Connections**

8259	8259 Input	Connected Pin / Function
Master	0	Internal Timer / Counter 0 output or HPET #0; determined by GCFG.LRE register bit
	1	IRQ1 using SERIRQ, Keyboard Emulation
	2	Slave controller INTR output
	3	IRQ3 via SERIRQ or PIRQx
	4	IRQ4 SERIRQ, PIRQx or PCU UART
	5	IRQ5 via SERIRQ or PIRQx
	6	IRQ6 via SERIRQ or PIRQx
	7	IRQ7 via SERIRQ or PIRQx
Slave	0	Inverted IRQ8# from internal RTC or HPET
	1	IRQ9 via SERIRQ, SCI or PIRQx
	2	IRQ10 via SERIRQ, SCI or PIRQx
	3	IRQ11 via SERIRQ, SCI, HPET or PIRQx
	4	IRQ12 via SERIRQ, PIRQx or mouse emulation
	5	None
	6	PIRQx or IRQ14 from SATA controller
	7	IRQ15 via SERIRQ or PIRQx or IRQ15 from SATA controller

The SoC cascades the slave controller onto the master controller through master controller interrupt input 2. This means there are only 15 possible interrupts for the SoC PIC.

Interrupts can be programmed individually to be edge or level, except for IRQ0, IRQ2 and IRQ8#.

Note: Active-low interrupt sources (such as a PIRQ#) are inverted inside the SoC. In the following descriptions of the 8259s, the interrupt levels are in reference to the signals at the internal interface of the 8259s, after the required inversions have occurred. Therefore, the term “high” indicates “active,” which means “low” on an originating PIRQ#.

42.1.1 Interrupt Handling

42.1.1.1 Generating Interrupts

The PIC interrupt sequence involves three bits, from the IRR, ISR, and IMR, for each interrupt level. These bits are used to determine the interrupt vector returned, and status of any other pending interrupts. [Table 345](#) defines the IRR, ISR, and IMR.



Table 345. Interrupt Status Registers

Bit	Description
IRR	Interrupt Request Register. This bit is set on a low to high transition of the interrupt line in edge mode, and by an active high level in level mode.
ISR	Interrupt Service Register. This bit is set, and the corresponding IRR bit cleared, when an interrupt acknowledge cycle is seen, and the vector returned is for that interrupt.
IMR	Interrupt Mask Register. This bit determines whether an interrupt is masked. Masked interrupts will not generate INTR.

42.1.1.2 Acknowledging Interrupts

The processor generates an interrupt acknowledge cycle that is translated into a Interrupt Acknowledge Cycle to the SoC. The PIC translates this command into two internal INTA# pulses expected by the 8259 controllers. The PIC uses the first internal INTA# pulse to freeze the state of the interrupts for priority resolution. On the second INTA# pulse, the master or slave sends the interrupt vector to the processor with the acknowledged interrupt code. This code is based upon the ICW2.IVBA bits, combined with the ICW2.IRL bits representing the interrupt within that controller.


Note: References to ICWx and OCWx registers are relevant to both the master and slave 8259 controllers.

Table 346. Content of Interrupt Vector Byte

Master, Slave Interrupt	Bits [7:3]	Bits [2:0]
IRQ7,15	ICW2.IVBA	111
IRQ6,14		110
IRQ5,13		101
IRQ4,12		100
IRQ3,11		011
IRQ2,10		010
IRQ1,9		001
IRQ0,8		000

42.1.1.3 Hardware/Software Interrupt Sequence

1. One or more of the Interrupt Request lines (IRQ) are raised high in edge mode, or seen high in level mode, setting the corresponding IRR bit.
2. The PIC sends INTR active to the processor if an asserted interrupt is not masked.
3. The processor acknowledges the INTR and responds with an interrupt acknowledge cycle.



4. Upon observing the special cycle, the SoC converts it into the two cycles that the internal 8259 pair can respond to. Each cycle appears as an interrupt acknowledge pulse on the internal INTA# pin of the cascaded interrupt controllers.
5. Upon receiving the first internally generated INTA# pulse, the highest priority ISR bit is set and the corresponding IRR bit is reset. On the trailing edge of the first pulse, a slave identification code is broadcast by the master to the slave on a private, internal three bit wide bus. The slave controller uses these bits to determine if it must respond with an interrupt vector during the second INTA# pulse.
6. Upon receiving the second internally generated INTA# pulse, the PIC returns the interrupt vector. If no interrupt request is present because the request was too short in duration, the PIC returns vector 7 from the master controller.
7. This completes the interrupt cycle. In AEOI mode the ISR bit is reset at the end of the second INTA# pulse. Otherwise, the ISR bit remains set until an appropriate EOI command is issued at the end of the interrupt subroutine.

42.1.2 Initialization Command Words (ICWx)

Before operation can begin, each 8259 must be initialized. In the SoC, this is a four byte sequence. The four initialization command words are referred to by their acronyms: ICW1, ICW2, ICW3, and ICW4.

The base address for each 8259 initialization command word is a fixed location in the I/O memory space: 20h for the master controller, and A0h for the slave controller.

42.1.2.1 ICW1

A write to the master or slave controller base address with data bit 4 equal to 1 is interpreted as a write to ICW1. Upon sensing this write, the PIC expects three more byte writes to 21h for the master controller, or A1h for the slave controller, to complete the ICW sequence.

A write to ICW1 starts the initialization sequence during which the following automatically occur:

1. Following initialization, an interrupt request (IRQ) input must make a low-to-high transition to generate an interrupt.
2. The Interrupt Mask Register is cleared.
3. IRQ7 input is assigned priority 7.
4. The slave mode address is set to 7.
5. Special mask mode is cleared and Status Read is set to IRR.

42.1.2.2 ICW2

The second write in the sequence (ICW2) is programmed to provide bits [7:3] of the interrupt vector that will be released during an interrupt acknowledge. A different base is selected for each interrupt controller.



42.1.2.3 ICW3

The third write in the sequence (ICW3) has a different meaning for each controller.

- For the master controller, ICW3 is used to indicate which IRQ input line is used to cascade the slave controller. Within the SoC, IRQ2 is used. Therefore, MICW3.CCC is set to a 1, and the other bits are set to 0s.
- For the slave controller, ICW3 is the slave identification code used during an interrupt acknowledge cycle. On interrupt acknowledge cycles, the master controller broadcasts a code to the slave controller if the cascaded interrupt won arbitration on the master controller. The slave controller compares this identification code to the value stored in its ICW3, and if it matches, the slave controller assumes responsibility for broadcasting the interrupt vector.

42.1.2.4 ICW4

The final write in the sequence (ICW4) must be programmed for both controllers. At the very least, ICW4.MM must be set to a 1 to indicate that the controllers are operating in an Intel Architecture-based system.

42.1.3 Operation Command Words (OCW)

These command words reprogram the Interrupt controller to operate in various interrupt modes.


- OCW1 masks and unmask interrupt lines.
- OCW2 controls the rotation of interrupt priorities when in rotating priority mode, and controls the EOI function.
- OCW3 sets up ISR/IRR reads, enables/disables the special mask mode (SMM), and enables/disables polled interrupt mode.

42.1.4 Modes of Operation

42.1.4.1 Fully Nested Mode

In this mode, interrupt requests are ordered in priority from 0 through 7, with 0 being the highest. When an interrupt is acknowledged, the highest priority request is determined and its vector placed on the bus. Additionally, the ISR for the interrupt is set. This ISR bit remains set until: the processor issues an EOI command immediately before returning from the service routine; or if in AEOI mode, on the trailing edge of the second INTA#. While the ISR bit is set, all further interrupts of the same or lower priority are inhibited, while higher levels generate another interrupt.

Interrupt priorities can be changed in the rotating priority mode.



42.1.4.2 Special Fully-Nested Mode

This mode is used in the case of a system where cascading is used, and the priority has to be conserved within each slave. In this case, the special fully-nested mode is programmed to the master controller. This mode is similar to the fully-nested mode with the following exceptions:

- When an interrupt request from a certain slave is in service, this slave is not locked out from the master's priority logic and further interrupt requests from higher priority interrupts within the slave are recognized by the master and initiate interrupts to the processor. In the normal-nested mode, a slave is masked out when its request is in service.
- When exiting the Interrupt Service routine, software has to check whether the interrupt serviced was the only one from that slave. This is done by sending a Non-Specific EOI command to the slave and then reading its ISR. If it is 0, a non-specific EOI can also be sent to the master.

42.1.4.3 Automatic Rotation Mode (Equal Priority Devices)

In some applications, there are a number of interrupting devices of equal priority. Automatic rotation mode provides for a sequential 8-way rotation. In this mode, a device receives the lowest priority after being serviced. In the worst case, a device requesting an interrupt has to wait until each of seven other devices are serviced at most once.

There are two ways to accomplish automatic rotation using OCW2.REOI; the Rotation on Non-Specific EOI Command (OCW2.REOI=101b) and the rotate in automatic EOI mode which is set by (OCW2.REOI=100b).

42.1.4.4 Specific Rotation Mode (Specific Priority)

Software can change interrupt priorities by programming the bottom priority. For example, if IRQ5 is programmed as the bottom priority device, then IRQ6 is the highest priority device. The Set Priority Command is issued in OCW2 to accomplish this, where: OCW2.REOI=11xb, and OCW2.ILS is the binary priority level code of the bottom priority device.

In this mode, internal status is updated by software control during OCW2. However, it is independent of the EOI command. Priority changes can be executed during an EOI command by using the Rotate on Specific EOI Command in OCW2 (OCW2.REOI=111b) and OCW2.ILS=IRQ level to receive bottom priority.

42.1.4.5 Poll Mode

Poll mode can be used to conserve space in the interrupt vector table. Multiple interrupts that can be serviced by one interrupt service routine do not need separate vectors if the service routine uses the poll command. Poll mode can also be used to expand the number of interrupts. The polling interrupt service routine can call the appropriate service routine, instead of providing the interrupt vectors in the vector



table. In this mode, the INTR output is not used and the microprocessor internal Interrupt Enable flip-flop is reset, disabling its interrupt input. Service to devices is achieved by software using a Poll command.

The Poll command is issued by setting OCW3.PMC. The PIC treats its next I/O read as an interrupt acknowledge, sets the appropriate ISR bit if there is a request, and reads the priority level. Interrupts are frozen from the OCW3 write to the I/O read. The byte returned during the I/O read contains a 1 in Bit 7 if there is an interrupt, and the binary code of the highest priority level in Bits 2:0.

42.1.4.6 Edge and Level Triggered Mode

In ISA systems this mode is programmed using ICW1.LTIM, which sets level or edge for the entire controller. In the SoC, this bit is disabled and a register for edge and level triggered mode selection, per interrupt input, is included. This is the Edge/Level control Registers ELCR1 and ELCR2.

If an ELCR bit is 0, an interrupt request will be recognized by a low-to-high transition on the corresponding IRQ input. The IRQ input can remain high without generating another interrupt. If an ELCR bit is 1, an interrupt request will be recognized by a high level on the corresponding IRQ input and there is no need for an edge detection. The interrupt request must be removed before the EOI command is issued to prevent a second interrupt from occurring.

In both the edge and level triggered modes, the IRQ inputs must remain active until after the falling edge of the first internal INTA#. If the IRQ input goes inactive before this time, a default IRQ7 vector is returned.


42.1.5 End of Interrupt (EOI) Operations

An EOI can occur in one of two fashions: by a command word write issued to the PIC before returning from a service routine, the EOI command; or automatically when the ICW4.AEOI bit is set to 1.

42.1.5.1 Normal End of Interrupt

In normal EOI, software writes an EOI command before leaving the interrupt service routine to mark the interrupt as completed. There are two forms of EOI commands: Specific and Non-Specific. When a Non-Specific EOI command is issued, the PIC clears the highest ISR bit of those that are set to 1. Non-Specific EOI is the normal mode of operation of the PIC within the SoC, as the interrupt being serviced currently is the interrupt entered with the interrupt acknowledge. When the PIC is operated in modes that preserve the fully nested structure, software can determine which ISR bit to clear by issuing a Specific EOI.

An ISR bit that is masked is not cleared by a Non-Specific EOI if the PIC is in the special mask mode. An EOI command must be issued for both the master and slave controller.



42.1.5.2 Automatic End of Interrupt Mode

In this mode, the PIC automatically performs a Non-Specific EOI operation at the trailing edge of the last interrupt acknowledge pulse. From a system standpoint, this mode should be used only when a nested multi-level interrupt structure is not required within a single PIC. The AEOI mode can only be used in the master controller and not the slave controller.

Note: Both the master and slave PICs have an AEOI bit: MICW4.AEOI and SICW4.AEOI respectively. Only the MICW4.AEOI bit should be set by software. The SICW4.AEOI bit should not be set by software.

42.1.6 Masking Interrupts

42.1.6.1 Masking on an Individual Interrupt Request

Each interrupt request can be masked individually by the Interrupt Mask Register (IMR). This register is programmed through OCW1. Each bit in the IMR masks one interrupt channel. Masking IRQ2 on the master controller masks all requests for service from the slave controller.

42.1.6.2 Special Mask Mode

Some applications may require an interrupt service routine to dynamically alter the system priority structure during its execution under software control. For example, the routine may wish to inhibit lower priority requests for a portion of its execution but enable some of them for another portion.

The special mask mode enables all interrupts not masked by a bit set in the Mask register. Normally, when an interrupt service routine acknowledges an interrupt without issuing an EOI to clear the ISR bit, the interrupt controller inhibits all lower priority requests. In the special mask mode, any interrupts may be selectively enabled by loading the Mask Register with the appropriate pattern.

The special mask mode is set by OCW3.ESMM=1b & OCW3.SMM=1b, and cleared where OCW3.ESMM=1b & OCW3.SMM=0b.

42.2 IO Mapped Registers

The interrupt controller registers are located at 20h and 21h for the master controller (IRQ0 - 7), and at A0h and A1h for the slave controller (IRQ8 - 13). These registers have multiple functions, depending upon the data written to them. [Table 347](#) is a description of the different register possibilities for each address.

Note: The register descriptions after [Table 347](#) represent one register possibility.



Table 347. I/O Registers Alias Locations

Registers	Original I/O Location	Alias I/O Locations
MICW1 MOCW2 MOCW3	20h	24h
		28h
		2Ch
		30h
		34h
		38h
		3Ch
MICW2 MICW3 MICW4 MOCW1	21h	25h
		29h
		2Dh
		31h
		35h
		39h
		3Dh
SICW1 SOCW2 SOCW3	A0h	A4h
		A8h
		ACh
		B0h
		B4h
		B8h
		BCh
SICW2 SICW3 SICW4 SOCW1	A1h	A5h
		A9h
		ADh
		B1h
		B5h
		B9h
		BDh
ELCR1	4D0h	N/A
ELCR2	4D1h	N/A

§



42.3 PCU iLB 8259 Interrupt Controller (PIC) I/O Registers

Table 348. Summary of PCU iLB 8259 Interrupt Controller (PIC) I/O Registers—

Offset	Size	Register ID—Description	Default Value
20h	1	"MICW1—Offset 20h" on page 5313	00h
21h	1	"MICW2—Offset 21h" on page 5314	00h
24h	1	"MOCW2—Offset 24h" on page 5314	20h
25h	1	"MICW3—Offset 25h" on page 5315	00h
28h	1	"MOCW3—Offset 28h" on page 5315	22h
29h	1	"MICW4—Offset 29h" on page 5316	01h
2Dh	1	"MOCW1—Offset 2Dh" on page 5317	00h
A0h	1	"SICW1—Offset A0h" on page 5317	00h
A1h	1	"SICW2—Offset A1h" on page 5318	00h
A4h	1	"SOCW2—Offset A4h" on page 5319	20h
A5h	1	"SICW3—Offset A5h" on page 5319	00h
A8h	1	"SOCW3—Offset A8h" on page 5320	22h
A9h	1	"SICW4—Offset A9h" on page 5320	01h
ADh	1	"SOCW1—Offset ADh" on page 5321	00h
4D0h	1	"ELCR1—Offset 4D0h" on page 5321	00h
4D1h	1	"ELCR2—Offset 4D1h" on page 5322	00h

42.3.1 MICW1—Offset 20h

Master Initialization Command Word 1.A write to Initialization Command Word 1 starts the interrupt controller initialization sequence, during which the following occurs: * The Interrupt Mask register is cleared. * IRQ7 input is assigned priority 7. * The slave mode address is set to 7. * Special Mask Mode is cleared and Status Read is set to IRR. Once this write occurs, the controller expects writes to ICW2, ICW3, and ICW4 to complete the initialization sequence.

Access Method

Type: I/O Register
(Size: 8 bits)

MICW1: 20h

Default: 00h

7	4	0				
0	0	0	0	0	0	0
MCS85			ICWOCWSEL	LTIM	ADI	SINGL
						IC4
Bit Range	Default & Access	Description				
7:5	X WO	MCS85: These bits are MCS-85 specific, and not needed. Should be programmed to 000				



Bit Range	Default & Access	Description
4	X WO	ICWOCWSEL: ICW/OCW select: This bit must be a 1 to select ICW1 and enable the ICW2, ICW3, and ICW4 sequence.
3	X WO	LTIM: Edge/Level Bank Select (LTIM): Disabled. Replaced by ELCR1 and ELCR2.
2	X WO	ADI: ADI. Ignored for VLV. Should be programmed to 0.
1	X WO	SNGL: Single or Cascade (SNGL): Must be programmed to a 0 to indicate two controllers operating in cascade mode.
0	X WO	IC4: wICW4 Write Required (IC4): This bit must be programmed to a 1 to indicate that ICW4 needs to be programmed.

42.3.2 MICW2—Offset 21h

Master ICW2 is used to initialize the interrupt controller with the five most significant bits of the interrupt vector address. The value programmed for bits[7:3] is used by the CPU to define the base address in the interrupt vector table for the interrupt routines associated with each IRQ on the controller. Typical ISA ICW2 values are 08h for the master controller and 70h for the slave controller.

Access Method

Type: I/O Register
(Size: 8 bits)

MICW2: 21h

Default: 00h

7	4	0
0	0	0
IVBA		IRL

Bit Range	Default & Access	Description
7:3	X WO	IVBA: Interrupt Vector Base Address: Bits [7:3] define the base address in the interrupt vector table for the interrupt routines associated with each interrupt request level input.
2:0	X WO	IRL: Interrupt Request Level: When writing ICW2, these bits should all be 0. During an interrupt acknowledge cycle, these bits are programmed by the interrupt controller with the interrupt to be serviced. This is combined with bits [7:3] to form the interrupt vector driven onto the data bus during the second INTA# cycle. The code is a three bit binary code: Code Master Interrupt Slave Interrupt 000 IRQ0 IRQ8 001 IRQ1 IRQ9 010 IRQ2 IRQ10 011 IRQ3 IRQ11 100 IRQ4 IRQ12 101 IRQ5 IRQ13 110 IRQ6 IRQ14 111 IRQ7 IRQ15

42.3.3 MOCW2—Offset 24h

Master Operational Control Word 2 (Interrupt Mask).Following a part reset or ICW initialization, the controller enters the fully nested mode of operation. Non-specific EOI without rotation is the default. Both rotation mode and specific EOI mode are disabled following initialization.

Access Method

Type: I/O Register
(Size: 8 bits)

MOCW2: 24h



Default: 20h

7			4				0
0	0	1	0	0	0	0	0
REOI			OCW2S	ILS			

Bit Range	Default & Access	Description
7:5	001b WO	REOI: Rotate and EOI Codes: R, SL, EOI - These three bits control the Rotate and End of Interrupt modes and combinations of the two. A chart of these combinations is listed above under the bit definition. 000 - Rotate in Auto EOI Mode (Clear) 001 - Non-specific EOI command 010 - No Operation 011 - *Specific EOI Command 100 - Rotate in Auto EOI Mode (Set) 101 - Rotate on Non-Specific EOI Command 110 - *Set Priority Command 111 - *Rotate on Specific EOI Command *L0 - L2 Are Used
4:3	X WO	OCW2S: OCW2 Select: When selecting OCW2, bits 4:3 = 00
2:0	X WO	ILS: Interrupt Level Select (L2, L1, L0): L2, L1, and L0 determine the interrupt level acted upon when the SL bit is active. A simple binary code, outlined above, selects the channel for the command to act upon. When the SL bit is inactive, these bits do not have a defined function; programming L2, L1 and L0 to 0 is sufficient in this case. Bits Interrupt Level Bits Interrupt Level 000 IRQ0/8 100 IRQ4/12 001 IRQ1/9 101 IRQ5/13 010 IRQ2/10 110 IRQ6/14 011 IRQ3/11 111 IRQ7/15

42.3.4 MICW3—Offset 25h

Master Initialization Command Word 3

Access Method

Type: I/O Register
(Size: 8 bits)

MICW3: 25h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
MBZ				CCC	MBZ1		

Bit Range	Default & Access	Description
7:3	X WO	MBZ: These bits must be programmed to zero.
2	X WO	CCC: Cascaded Controller Connection (CCC): This bit must always be programmed to a 1 to indicate the slave controller for interrupts 8 15 is cascaded on IRQ2.
1:0	X WO	MBZ (MBZ1): These bits must be programmed to zero.

42.3.5 MOCW3—Offset 28h

Master Operational Control Word 3

Access Method

Type: I/O Register
(Size: 8 bits)

MOCW3: 28h



Default: 22h

7			4				0
0	0	1	0	0	0	1	0
RESERVED	SMM	ESMM	O3S	PMC	RRC		

Bit Range	Default & Access	Description
7	0b RO	RESERVED: Reserved. Must be 0.
6	0b WO	SMM: Special Mask Mode (SMM): If this bit is set, the Special Mask Mode can be used by an interrupt service routine to dynamically alter the system priority structure while the routine is executing, through selective enabling/ disabling of the other channel's mask bits. Bit 6, the ESMM bit, must be set for this bit to have any meaning.
5	1b WO	ESMM: Enable Special Mask Mode (ESMM): When set, the SMM bit is enabled to set or reset the Special Mask Mode. When cleared, the SMM bit becomes a don't care.
4:3	X WO	O3S: OCW3 Select (O3S): When selecting OCW3, bits 4:3 = 01
2	X WO	PMC: Poll Mode Command (PMC): When cleared, poll command is not issued. When set, the next I/O read to the interrupt controller is treated as an interrupt acknowledge cycle. An encoded byte is driven onto the data bus, representing the highest priority level requesting service.
1:0	10b WO	RRC: Register Read Command (RRC): These bits provide control for reading the ISR and Interrupt IRR. When bit 1=0, bit 0 will not affect the register read selection. Following ICW initialization, the default OCW3 port address read will be read IRR. To retain the current selection (read ISR or read IRR), always write a 0 to bit 1 when programming this register. The selected register can be read repeatedly without reprogramming OCW3. To select a new status register, OCW3 must be reprogrammed prior to attempting the read. 00 No Action 01 No Action 10 Read IRQ Register 11 Read IS Register

42.3.6 MICW4—Offset 29h

Master Initialization Command Word 4

Access Method

Type: I/O Register
(Size: 8 bits)

MICW4: 29h

Default: 01h

7			4				0
0	0	0	0	0	0	0	1
	MBZ		SFNM	BUF	MSBM	AEOT	MM

Bit Range	Default & Access	Description
7:5	X WO	MBZ: These bits must be programmed to zero.
4	0b WO	SFNM: Special Fully Nested Mode (SFNM): Should normally be disabled by writing a 0 to this bit. If SFNM=1, the special fully nested mode is programmed.



Bit Range	Default & Access	Description
3	0b WO	BUF: Buffered Mode (BUF): Must be cleared for non-buffered mode. Writing 1 will result in undefined behavior.
2	0b WO	MSBM: Master/Slave in Buffered Mode (MSBM): Not used. Should always be programmed to 0.
1	0b WO	AEOI: Automatic End of Interrupt (AEOI): This bit should normally be programmed to 0. This is the normal end of interrupt. If this bit is 1, the automatic end of interrupt mode is programmed.
0	1b WO	MM: Microprocessor Mode (MM): This bit must be written to 1 to indicate that the controller is operating in an Intel Architecture-based system. Writing 0 will result in undefined behavior.

42.3.7 MOCW1—Offset 2Dh

Master Operational Control Word 1 (Interrupt Mask)

Access Method

Type: I/O Register
(Size: 8 bits)

MOCW1: 2Dh

Default: 00h

7	4	0
0	0	0
IRM		

Bit Range	Default & Access	Description
7:0	00h RW	IRM: Interrupt Request Mask (IRM): When a 1 is written to any bit in this register, the corresponding IRQ line is masked. When a 0 is written to any bit in this register, the corresponding IRQ mask bit is cleared, and interrupt requests will again be accepted by the controller. Masking IRQ2 on the master controller will also mask the interrupt requests from the slave controller.

42.3.8 SICW1—Offset A0h

Slave Initialization Command Word 1. A write to Initialization Command Word 1 starts the interrupt controller initialization sequence, during which the following occurs: * The Interrupt Mask register is cleared. * IRQ7 input is assigned priority 7. * The slave mode address is set to 7. * Special Mask Mode is cleared and Status Read is set to IRR. Once this write occurs, the controller expects writes to ICW2, ICW3, and ICW4 to complete the initialization sequence.

Access Method

Type: I/O Register
(Size: 8 bits)

SICW1: A0h

Default: 00h



7			4				0
0	0	0	0	0	0	0	0
MCS85			ICWOCWSEL	LTIM	ADI	SNGL	IC4

Bit Range	Default & Access	Description
7:5	X WO	MCS85: These bits are MCS-85 specific, and not needed. Should be programmed to 000.
4	X WO	ICWOCWSEL: ICW/OCW select: This bit must be a 1 to select ICW1 and enable the ICW2, ICW3, and ICW4 sequence.
3	X WO	LTIM: Edge/Level Bank Select (LTIM): Disabled. Replaced by ELCR1 and ELCR2.
2	X WO	ADI: ADI. Ignored for VLV. Should be programmed to 0.
1	X WO	SNGL: Single or Cascade (SNGL): Must be programmed to a 0 to indicate two controllers operating in cascade mode.
0	X WO	IC4: wICW4 Write Required (IC4): This bit must be programmed to a 1 to indicate that ICW4 needs to be programmed.

42.3.9 SICW2—Offset A1h

Slave ICW2 is used to initialize the interrupt controller with the five most significant bits of the interrupt vector address. The value programmed for bits[7:3] is used by the CPU to define the base address in the interrupt vector table for the interrupt routines associated with each IRQ on the controller. Typical ISA ICW2 values are 08h for the master controller and 70h for the slave controller.

Access Method

Type: I/O Register
(Size: 8 bits)

SICW2: A1h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
IVBA				IRL			

Bit Range	Default & Access	Description
7:3	X WO	IVBA: Interrupt Vector Base Address: Bits [7:3] define the base address in the interrupt vector table for the interrupt routines associated with each interrupt request level input.
2:0	X WO	IRL: Interrupt Request Level: When writing ICW2, these bits should all be 0. During an interrupt acknowledge cycle, these bits are programmed by the interrupt controller with the interrupt to be serviced. This is combined with bits [7:3] to form the interrupt vector driven onto the data bus during the second INTA# cycle. The code is a three bit binary code: Code Master Interrupt Slave Interrupt 000 IRQ0 IRQ8 001 IRQ1 IRQ9 010 IRQ2 IRQ10 011 IRQ3 IRQ11 100 IRQ4 IRQ12 101 IRQ5 IRQ13 110 IRQ6 IRQ14 111 IRQ7 IRQ15



42.3.10 SOCW2—Offset A4h

Slave Operational Control Word 2 (Interrupt Mask). Following a part reset or ICW initialization, the controller enters the fully nested mode of operation. Non-specific EOI without rotation is the default. Both rotation mode and specific EOI mode are disabled following initialization.

Access Method

Type: I/O Register
(Size: 8 bits)

SOCW2: A4h

Default: 20h

7			4				0
0	0	1	0	0	0	0	0
REOI			OCW2S	ILS			

Bit Range	Default & Access	Description
7:5	001b WO	REOI: Rotate and EOI Codes: R, SL, EOI - These three bits control the Rotate and End of Interrupt modes and combinations of the two. A chart of these combinations is listed above under the bit definition. 000 - Rotate in Auto EOI Mode (Clear) 001 - Non-specific EOI command 010 - No Operation 011 - *Specific EOI Command 100 - Rotate in Auto EOI Mode (Set) 101 - Rotate on Non-Specific EOI Command 110 - *Set Priority Command 111 - *Rotate on Specific EOI Command *L0 - L2 Are Used
4:3	X WO	OCW2S: OCW2 Select: When selecting OCW2, bits 4:3 = 00
2:0	X WO	ILS: Interrupt Level Select (L2, L1, L0): L2, L1, and L0 determine the interrupt level acted upon when the SL bit is active. A simple binary code, outlined above, selects the channel for the command to act upon. When the SL bit is inactive, these bits do not have a defined function; programming L2, L1 and L0 to 0 is sufficient in this case. Bits Interrupt Level Bits Interrupt Level 000 IRQ0/8 100 IRQ4/12 001 IRQ1/9 101 IRQ5/13 010 IRQ2/10 110 IRQ6/14 011 IRQ3/11 111 IRQ7/15

42.3.11 SICW3—Offset A5h

Slave Initialization Command Word 3

Access Method

Type: I/O Register
(Size: 8 bits)

SICW3: A5h

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
MBZ			CCC		MBZ1		

Bit Range	Default & Access	Description
7:3	X WO	MBZ: These bits must be programmed to zero.
2	X WO	CCC: Cascaded Controller Connection (CCC): This bit must always be programmed to a 1 to indicate the slave controller for interrupts 8 15 is cascaded on IRQ2.



Bit Range	Default & Access	Description
1:0	X WO	MBZ (MBZ1): These bits must be programmed to zero.

42.3.12 SOCW3—Offset A8h

Slave Operational Control Word 3

Access Method

Type: I/O Register
(Size: 8 bits)

SOCW3: A8h

Default: 22h

7			4			0
0	0	1	0	0	0	1
RESERVED	SMM	ESMM	O3S	PMC	RRC	

Bit Range	Default & Access	Description
7	0b RO	RESERVED: Reserved. Must be 0.
6	0b WO	SMM: Special Mask Mode (SMM): If this bit is set, the Special Mask Mode can be used by an interrupt service routine to dynamically alter the system priority structure while the routine is executing, through selective enabling/ disabling of the other channel's mask bits. Bit 6, the ESMM bit, must be set for this bit to have any meaning.
5	1b WO	ESMM: Enable Special Mask Mode (ESMM): When set, the SMM bit is enabled to set or reset the Special Mask Mode. When cleared, the SMM bit becomes a don't care.
4:3	X WO	O3S: OCW3 Select (O3S): When selecting OCW3, bits 4:3 = 01
2	X WO	PMC: Poll Mode Command (PMC): When cleared, poll command is not issued. When set, the next I/O read to the interrupt controller is treated as an interrupt acknowledge cycle. An encoded byte is driven onto the data bus, representing the highest priority level requesting service.
1:0	10b WO	RRC: Register Read Command (RRC): These bits provide control for reading the ISR and Interrupt IRR. When bit 1=0, bit 0 will not affect the register read selection. Following ICW initialization, the default OCW3 port address read will be read IRR. To retain the current selection (read ISR or read IRR), always write a 0 to bit 1 when programming this register. The selected register can be read repeatedly without reprogramming OCW3. To select a new status register, OCW3 must be reprogrammed prior to attempting the read. 00 No Action 01 No Action 10 Read IRQ Register 11 Read IS Register

42.3.13 SICW4—Offset A9h

Slave Initialization Command Word 4

Access Method

Type: I/O Register
(Size: 8 bits)

SICW4: A9h

Default: 01h



7			4				0
0	0	0	0	0	0	0	1
MBZ			SFNM	BUF	MSBM	AEOI	MM

Bit Range	Default & Access	Description
7:5	X WO	MBZ: These bits must be programmed to zero.
4	0b WO	SFNM: Special Fully Nested Mode (SFNM): Should normally be disabled by writing a 0 to this bit. If SFNM=1, the special fully nested mode is programmed.
3	0b WO	BUF: Buffered Mode (BUF): Must be cleared for non-buffered mode. Writing 1 will result in undefined behavior.
2	0b WO	MSBM: Master/Slave in Buffered Mode (MSBM): Not used. Should always be programmed to 0.
1	0b WO	AEOI: Automatic End of Interrupt (AEOI): This bit should normally be programmed to 0. This is the normal end of interrupt. If this bit is 1, the automatic end of interrupt mode is programmed.
0	1b WO	MM: Microprocessor Mode (MM): This bit must be written to 1 to indicate that the controller is operating in an Intel Architecture-based system. Writing 0 will result in undefined behavior.

42.3.14 SOCW1—Offset ADh

Slave Operational Control Word 1 (Interrupt Mask)

Access Method

Type: I/O Register
(Size: 8 bits)

SOCW1: ADh

Default: 00h

7			4				0
0	0	0	0	0	0	0	0
IRM							

Bit Range	Default & Access	Description
7:0	00h RW	IRM: Interrupt Request Mask (IRM): When a 1 is written to any bit in this register, the corresponding IRQ line is masked. When a 0 is written to any bit in this register, the corresponding IRQ mask bit is cleared, and interrupt requests will again be accepted by the controller. Masking IRQ2 on the master controller will also mask the interrupt requests from the slave controller.

42.3.15 ELCR1—Offset 4D0h

Master Edge/Level Control

Access Method

Type: I/O Register
(Size: 8 bits)

ELCR1: 4D0h

Default: 00h



7	4	0
0	0	0
ELC		RESERVED

Bit Range	Default & Access	Description
7:3	X RW	ELC: Edge Level Control (ECL[7:3]): In edge mode, (bit cleared), the interrupt is recognized by a low to high transition. In level mode (bit set), the interrupt is recognized by a high level.
2:0	0b RO	RESERVED: Reserved.

42.3.16 ELCR2—Offset 4D1h

Slave Edge/Level Control

Access Method

Type: I/O Register
(Size: 8 bits)

ELCR2: 4D1h

Default: 00h

7	4	0
0	0	0
ELC1	RESERVED	ELC2
		RESERVED1

Bit Range	Default & Access	Description
7:6	X RW	ELC1: Edge Level Control (ECL[15:14]): In edge mode, (bit cleared), the interrupt is recognized by a low to high transition. In level mode (bit set), the interrupt is recognized by a high level. Bit 7 applies to IRQ15, and bit 6 to IRQ14.
5	0b RO	RESERVED: Reserved.
4:1	X RW	ELC2: Edge Level Control (ECL[12:9]): In edge mode, (bit cleared), the interrupt is recognized by a low to high transition. In level mode (bit set), the interrupt is recognized by a high level. Bit 4 applies to IRQ12, bit 3 to IRQ11, bit 2 to IRQ10, and bit 1 to IRQ9.
0	0b RO	RESERVED (RESERVED1): Reserved.

§ §

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Intel:](#)

[FH8065301487916 S R1RD](#) [FH8065301567311 S R1RB](#) [FH8065301567411 S R1RA](#) [FH8065301542213 S R1RC](#)
[FH8065301487704S R1LQ](#) [FH8065301567400S R1LU](#) [FH8065301567300S R1LT](#) [FH8065301542202S R1LS](#)
[FH8065301487715 S R1RE](#) [FH8065301487905S R1LR](#) [FH8065301989700S R20Y](#) [FH8065301487717S R1X6](#)
[FH8065301567414S R1XA](#) [FH8065301487918S R1X7](#) [FH8065301542215S R1X8](#) [FH8065301567313S R1X9](#)
[FH8065301567416S R3V2](#) [FH8065301567414S R3V1](#) [FH8065301487920S R3UW](#) [FH8065301542215S R3UX](#)
[FH8065301567313S R3UZ](#) [FH8065301487717S R3UT](#) [FH8065301487918S R3UV](#) [FH8065301542217S R3UY](#)
[FH8065301567315S R3V0](#) [FH8065301487719S R3UU](#) [FH8065301989700S R3V3](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru