

Interactive Catalog Supplements Catalog PDFs

If you need detailed product information, or help choosing the right product for your application, see our **Interactive Catalog**. Use the **Interactive Catalog** to access the most complete and up-to-date information available.

The **Interactive Catalog** provides an extensive collection of product specifications, application data, and technical literature that can be searched based on criteria you select.

This PDF catalog information was published in November 2000.



Sensing and Control
**Interactive
Catalog...**

**Click this icon to try
the Interactive Catalog.**

Sensing and Control


Honeywell Inc.

11 West Spring Street

Freeport, IL 61032

www.honeywell.com/sensing

Momentary Cable Pull Limit Switches: For Signaling Applications



MOMENTARY (CONTACT SWITCH) OPERATING HEAD

Momentary CLS Series Cable Pull Limit Switches are designed for signaling applications; they are not to be used as emergency stop devices. (For emergency stop applications, see the Maintained Cable Pull Limit Switches in the Safety Products catalog.)

When using direct acting contacts, Momentary Cable Pull Limit Switches provide a means to manually force disconnection of a normally closed control circuit by pulling on an attached cable. Momentary switches cause contact transfer if the cable is manually pulled and held. When the cable is released, switch contacts return to their original state. Momentary switches have either direct-acting contacts or snap-action contacts.

Cable length may be up to 200 ft. in a straight line for Single Head switches, and up to 400 ft. (200 ft. in each direction) for Duplex Head switches.

FEATURES


- Offered in Single Head and Duplex Head versions
- Optional direct acting contacts enhance reliability
- Duplex Head switches cover up to 400 ft. cable spans (200 ft. in each direction)
- Single Head switches have one normally open auxiliary contact, while Duplex Head switches have up to three normally open and two normally closed auxiliary contacts
- Four conduit opening thread size options: 1/2-14 NPT, 20mm, PF1/2 and PG13.5
- Compact size of Single Head switches fits into tight spaces
- Sealed to NEMA 1, 3, 4 and 13
- Smart Distributed System output available on Duplex version for monitoring only
- UL listed
- CSA certified
- CE certified
- Temperature range: -1° to 70°C (30° to 158°F)
- Available with indicators
- Duplex versions available with high visibility pilot light

Limit/Enclosed

TYPICAL APPLICATIONS

- Conveyors
- Packaging machinery
- Assembly lines
- Process equipment
- Transfer lines

TYPICAL DUPLEX HEAD SWITCH INSTALLATION



TECHNICAL DATA CLS SERIES SPECIFICATIONS

Electrical		
Rate thermal current	$I_{th} = 10\text{ A}$	
Rate insulation voltage	$U_i = 660\text{ VAC}/660\text{ VDC}$	
Impulse voltage	$U_{mp} = 2.5\text{ kV}$	
Contact resistance	$< 25\text{ milliohms}$	
Operating rating	AC15	$U = 600\text{ V}; I = 1.2\text{ A}$
		$U = 240\text{ V}; I = 3\text{ A}$
		$U = 120\text{ V}; I = 6\text{ A}$
	DC13	$U = 250\text{ V}; I = 0.27\text{ A}$
		$U = 24\text{ V}; I = 2.8\text{ A}$
UL/CSA	A600/Q300	
Mechanical		
Protection class	NEMA 1, 3, 4 and 13	
Mechanical life	10^5 operations maximum	
Temperature Range	-1° to 70°C (30° to 158°F)	
Terminal identification	Numbering to EN50013	
Head/housing material	Zinc die cast	

CABLE PULL SWITCH CHARACTERISTICS

Momentary Cable Pull Limit Switches are offered with a black operating head and a blue body. There is a choice of four different conduit openings: 1/2-14 NPT, 20mm, PF 1/2, and PG13.5. Duplex switches have 3 standard conduit openings with two conduit plugs provided.

All switches come with a 1NO auxiliary contact as standard.

An additional auxiliary switch is also available in the Duplex. This auxiliary switch may be configured as 1NO - 1NC direct acting, 2NO - 2NC snap action (monitoring only) or 1NO - 1NC with Smart Distributed System output (monitoring only).

Neon and LED indicators are available. A 6 watt incandescent pilot light is available on the Duplex for high visibility at long distances.

SMART DISTRIBUTED SYSTEM OUTPUT VERSION

The Smart Distributed System Output Version provides Smart Distributed System compatible switch status messaging. The primary contact block (NC) must be wired to the control current. The auxiliary contact block has been replaced with the Smart Distributed System circuitry.

NOTICE

Snap action contact blocks and the Smart Distributed Output Version should be used for monitoring only. These types of switches should not be used in control circuits.

Momentary Cable Pull Limit Switches: For Signaling Applications

SINGLE HEAD CLS ORDER GUIDE

CLS -

BODY CODE

A BLUE BODY – PG13.5
B BLUE BODY – 1/2 NPT
C BLUE BODY – 20MM
D BLUE BODY – PF1/2

MODIFICATION CODES

1 HEAD ASSEMBLED WITH ACTUATOR TO THE LEFT
2 HEAD ASSEMBLED WITH ACTUATOR TO THE FRONT
3 HEAD ASSEMBLED WITH ACTUATOR TO THE MOUNTING SURFACE

BASIC SWITCH CODE

3 1NO-1NC SNAP ACTION (Monitoring Only)
4 1NO-1NC DIRECT ACTING
5 1NO-1NC DIRECT ACTING 240V NEON INDICATOR
6 1NO-1NC DIRECT ACTING 120V NEON INDICATOR
7 1NO-1NC DIRECT ACTING 24V LED INDICATOR

HEAD CODES

B MOMENTARY

- Notes:
- Leave the MODIFICATION CODE blank if a modification is not required.
 - Standard head orientation is with actuator to the right.
 - Unit may be field modified.

EXAMPLE CATALOG LISTING

Catalog Listing	Description
CLSD4B-1	Single Head Cable Pull Limit Switch, Blue Body – PF 1/2, 1NO - 1NC Direct Acting, Momentary, Head assembled with actuator to the left

DUPLEX HEAD 2CLS ORDER GUIDE

2CLS -

BODY CODE

A BLUE BODY – PG13.5
B BLUE BODY – 1/2 NPT
C BLUE BODY – 20MM
D BLUE BODY – PF1/2

MODIFICATION CODES

(See chart below for numbered modification codes.)

INDICATOR – PILOT LIGHT CODE

A 120V – 6W RED PILOT LIGHT
B 120V NEON INDICATOR
C 240V NEON INDICATOR
D 24V LED INDICATOR

PRIMARY BASIC SWITCH CODE – LEFT

1 1NO – 1NC DIRECT ACTING

AUXILIARY BASIC SWITCH CODE – RIGHT

1 1NO – 1NC DIRECT ACTING
3 2NO – 2NC (DPDT) SNAP ACTION (Monitoring Only)
4 1NO – 1NC WITH SDS OUTPUT (Monitoring Only)
9 NO SWITCH

OPERATING HEAD

B MOMENTARY, BOTH SIDES

- Notes:
- No numbered modification code indicates both heads oriented to side (Duplex Head).
 - Standard Conduit openings are left, center, and right with two conduit plugs furnished.
 - Leave the INDICATOR – PILOT LIGHT CODE blank if a pilot light is not required.
 - Leave the HEAD ORIENTATION NUMBERED MODIFICATION CODE blank if not required. Do not enter zero.

EXAMPLE CATALOG LISTING

Catalog Listing	Description
2CLSB1B1-3	Duplex Head Cable Limit Switch, Blue Body – 1/2 NPT, 1NO – 1NC Direct Acting, Momentary – Both Sides, 1NO – 1NC Direct Acting, No Pilot Light, Left Head Front – Right Head Side



HEAD ORIENTATION NUMBERED MOD CODES		
MOD CODE	LEFT HEAD	RIGHT HEAD
1	FRONT	FRONT
2	FRONT	REAR
3	FRONT	SIDE
4	REAR	FRONT
5	REAR	REAR
6	REAR	SIDE
7	SIDE	FRONT
8	SIDE	REAR

Limit/Enclosed

Momentary Cable Pull Limit Switches: For Signaling Applications

MOUNTING DIMENSIONS

(For reference only)





- INSTALLATION HARDWARE**
- Aircraft cable precut to 25, 50, 100, 150 and 200 feet lengths
 - Lockout attachment
 - End springs for long cable spans to compensate for temperature variations
 - Installation hardware kit supports cable installations of 25 ft. and 50 ft.

INSTALLATION HARDWARE ORDER GUIDE

Catalog Listings	Description
CLSZC1	25 ft. Red Aircraft Cable, finished cable dia. 0.187 in
CLSZC2	50 ft. Red Aircraft Cable, finished cable dia. 0.187 in
CLSZC3	100 ft. Red Aircraft Cable, finished cable dia. 0.187 in
CLSZC4	150 ft. Red Aircraft Cable, finished cable dia. 0.187 in
CLSZC5	200 ft. Red Aircraft Cable, finished cable dia. 0.187 in
CLSZ1S	End Spring
CLSZ00	Installation Kit includes: 4 thimbles, 8 wire rope clamps, 1 turnbuckle (w/lock nuts), 9 eyebolts (w/hardware), 1 endspring, 1 conduit fitting

- Notes:
1. Eyebolts should be spaced 1.8 to 2.4 m (6 to 8 ft.) apart.
 2. One used for each 7.5 m (25 ft.) of cable span.

Limit/Enclosed

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru