STGW40H65DFB-4

Trench gate field-stop IGBT, HB series 650 V, 40 A high speed in a TO247-4 package

Datasheet - production data



Figure 1: Internal schematic diagram



Features

- Maximum junction temperature: T_J = 175 °C
- Kelvin pin
- Minimized tail current
- Low saturation voltage: $V_{CE(sat)}$ = 1.6 V (typ.) @ I_C = 40 A
- Tight parameter distribution
- Safe paralleling
- Low thermal resistance
- Very fast soft recovery antiparallel diode

Applications

- Photovoltaic inverters
- High frequency converters

Description

This device is an IGBT developed using an advanced proprietary trench gate field-stop structure. The device is part of the new HB series of IGBTs, which represents an optimum compromise between conduction and switching loss to maximize the efficiency of any frequency converter. A faster switching event can be achieved by the Kelvin pin, which separates power path from driving signal. Furthermore, the slightly positive $V_{CE(sat)}$ temperature coefficient and very tight parameter distribution result in safer paralleling operation.

Table 1: Device summary

Order code	Marking	Package	Packing
STGW40H65DFB-4	G40H65DFB	TO247-4	Tube

This is information on a product in full production.

www.st.com

Contents

1 Electrical ratings 3
2 Electrical characteristics 4
2.1 Electrical characteristics (curves) 7
3 Test circuits 12
4 Package information 13
4.1 TO247-4 package information 13
5 Revision history 15

1 Electrical ratings

Table 2: Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{CES}	Collector-emitter voltage (V_{GE} = 0 V)	650	V
I_C	Continuous collector current at T_C = 25 °C	80	A
I_C	Continuous collector current at T_C = 100 °C	40	A
I_{CP}(1)	Pulsed collector current	160	A
V_{GE}	Gate-emitter voltage	±20	V
I_F	Continuous forward current at T_C = 25 °C	80	A
I_F	Continuous forward current at T_C = 100 °C	40	A
I_{FP}(1)	Pulsed forward current	160	A
P_{TOT}	Total dissipation at T_C = 25 °C	283	W
T_{STG}	Storage temperature range	-55 to 150	°C
T_J	Operating junction temperature range	-55 to 175	°C

Notes:

(1)Pulse width is limited by maximum junction temperature.

Table 3: Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance junction-case IGBT	0.53	°C/W
R_{thJC}	Thermal resistance junction-case diode	1.14	°C/W
R_{thJA}	Thermal resistance junction-ambient	50	°C/W

2 Electrical characteristics

T_C = 25 °C unless otherwise specified

Table 4: Static characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)CES}$	Collector-emitter breakdown voltage	V_{GE} = 0 V, I_C = 2 mA	650			V
$V_{CE(sat)}$	Collector-emitter saturation voltage	V_{GE} = 15 V, I_C = 40 A		1.6	2	V
		V_{GE} = 15 V, I_C = 40 A, T_J = 125 °C		1.7		
		V_{GE} = 15 V, I_C = 40 A, T_J = 175 °C		1.8		
V_F	Forward on-voltage	I_F = 40 A		1.7	2.45	V
		I_F = 40 A, T_J = 125 °C		1.4		
		I_F = 40 A, T_J = 175 °C		1.3		
$V_{GE(th)}$	Gate threshold voltage	V_{CE} = V_{GE}, I_C = 1 mA	5	6	7	V
I_{CES}	Collector cut-off current	V_{GE} = 0 V, V_{CE} = 650 V			25	µA
I_{GES}	Gate-emitter leakage current	V_{CE} = 0 V, V_{GE} = ±20 V			±250	µA

Table 5: Dynamic characteristics

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{ies}	Input capacitance	V_{CE} = 25 V, f = 1 MHz, V_{GE} = 0 V	-	5412	-	pF
C_{oes}	Output capacitance		-	198	-	
C_{res}	Reverse transfer capacitance		-	107	-	
Q_g	Total gate charge	V_{CC} = 520 V, I_C = 40 A, V_{GE} = 0 to 15 V (see *Figure 29: " Gate charge test circuit"*)	-	210	-	nC
Q_{ge}	Gate-emitter charge		-	39	-	
Q_{gc}	Gate-collector charge		-	82	-	

Table 6: IGBT switching characteristics (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	V_{CE} = 400 V, I_C = 40 A, V_{GE} = 15 V, R_G = 5 Ω (see *Figure 28: " Test circuit for inductive load switching"*)	-	40	-	ns
t_r	Current rise time		-	13	-	ns
$(di/dt)_{on}$	Turn-on current slope		-	2553	-	A/µs
$t_{d(off)}$	Turn-off-delay time		-	142	-	ns
t_f	Current fall time		-	26	-	ns
E_{on}(1)	Turn-on switching energy		-	200	-	µJ
E_{off}(2)	Turn-off switching energy		-	410	-	µJ
E_{ts}	Total switching energy		-	610	-	µJ
$t_{d(on)}$	Turn-on delay time	V_{CE} = 400 V, I_C = 40 A, V_{GE} = 15 V, R_G = 5 Ω, T_J = 175 °C (see *Figure 28: " Test circuit for inductive load switching"*)	-	40	-	ns
t_r	Current rise time		-	14.8	-	ns
$(di/dt)_{on}$	Turn-on current slope		-	2216	-	A/µs
$t_{d(off)}$	Turn-off-delay time		-	148	-	ns
t_f	Current fall time		-	61	-	ns
E_{on}(1)	Turn-on switching energy		-	472	-	µJ
E_{off}(2)	Turn-off switching energy		-	816	-	µJ
E_{ts}	Total switching energy		-	1288	-	µJ

Notes:

(1)Including the reverse recovery of the diode.

(2)Including the tail of the collector current.

Table 7: Diode switching characteristics (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
t_{rr}	Reverse recovery time	I_F = 40 A, V_R = 400 V, V_{GE} = 15 V, di/dt = 100 A/µs (see *Figure 28: " Test circuit for inductive load switching"*)	-	62	-	ns
Q_{rr}	Reverse recovery charge		-	99	-	nC
I_{rrm}	Reverse recovery current		-	3.3	-	A
dI_{rr}/dt	Peak rate of fall of reverse recovery current during t_b		-	187	-	A/µs
E_{rr}	Reverse recovery energy		-	68	-	µJ
t_{rr}	Reverse recovery time	I_F = 40 A, V_R = 400 V, V_{GE} = 15 V, T_J = 175 °C, di/dt = 100 A/µs (see *Figure 28: " Test circuit for inductive load switching"*)	-	310	-	ns
Q_{rr}	Reverse recovery charge		-	1550	-	nC
I_{rrm}	Reverse recovery current		-	10	-	A
dI_{rr}/dt	Peak rate of fall of reverse recovery current during t_b		-	70	-	A/µs
E_{rr}	Reverse recovery energy		-	674	-	µJ

2.1 Electrical characteristics (curves)

Figure 2: Power dissipation vs. case temperature



Figure 3: Collector current vs. case temperature



Figure 4: Output characteristics (TJ = 25°C)



Figure 5: Output characteristics (TJ = 175°C)



Figure 6: VCE(sat) vs. junction temperature



Figure 7: VCE(sat) vs. collector current



Figure 8: Collector current vs. switching frequency



Figure 9: Forward bias safe operating area



Figure 10: Transfer characteristics



Figure 11: Diode VF vs. forward current



Figure 12: Normalized VGE(th) vs junction temperature



Figure 13: Normalized V(BR)CES vs. junction temperature



Figure 14: Capacitance variations



Figure 15: Gate charge vs. gate-emitter voltage



Figure 16: Switching energy vs collector current



Figure 17: Switching energy vs gate resistance



Figure 18: Switching energy vs temperature



Figure 19: Switching energy vs. collector emitter voltage



Figure 20: Switching times vs. collector current



Figure 21: Switching times vs. gate resistance



Figure 22: Reverse recovery current vs. diode current slope



Figure 23: Reverse recovery time vs. diode current slope



Figure 24: Reverse recovery charge vs. diode current slope



Figure 25: Reverse recovery energy vs. diode current slope



Figure 26: Thermal impedance for IGBT



Figure 27: Thermal impedance for diode



3 Test circuits

Figure 28: Test circuit for inductive load switching



Figure 29: Gate charge test circuit



Figure 30: Switching waveform



Figure 31: Diode reverse recovery waveform



4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: ***www.st.com***. ECOPACK® is an ST trademark.

4.1 TO247-4 package information

Figure 32: TO247-4 package outline



Table 8: TO247-4 mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.90	5.00	5.10
A1	2.31	2.41	2.51
A2	1.90	2.00	2.10
b	1.16		1.29
b1	1.15	1.20	1.25
b2	0		0.20
c	0.59		0.66
c1	0.58	0.60	0.62
D	20.90	21.00	21.10
D1	16.25	16.55	16.85
D2	1.05	1.20	1.35
D3	24.97	25.12	25.27
E	15.70	15.80	15.90
E1	13.10	13.30	13.50
E2	4.90	5.00	5.10
E3	2.40	2.50	2.60
e	2.44	2.54	2.64
e1	4.98	5.08	5.18
L	19.80	19.92	20.10
P	3.50	3.60	3.70
P1			7.40
P2	2.40	2.50	2.60
Q	5.60		6.00
S		6.15	
T	9.80		10.20
U	6.00		6.40

5 Revision history

Table 9: Document revision history

Date	Revision	Changes
04-Mar-2016	1	First release
13-Mar-2017	2	Updated Table 6: "IGBT switching characteristics (inductive load)". Updated Section 2.1: "Electrical characteristics (curves)". Minor text changes
17-Aug-2017	3	Updated title in cover page. Updated *Table 7: "Diode switching characteristics (inductive load)"*. Updated *Section 4.1: "TO247-4 package information"* Minor text changes.

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2017 STMicroelectronics – All rights reserved

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru