

High Temperature Silicon Carbide Power Schottky Diode

V_{RRM}	=	1200 V
$I_F @ 25^\circ\text{C}$	=	2.5 A
Q_C	=	6 nC

Features

- 1200 V Schottky rectifier
- 250°C maximum operating temperature
- Zero reverse recovery charge
- Superior surge current capability
- Positive temperature coefficient of V_F
- Temperature independent switching behavior
- Lowest figure of merit Q_C/I_F
- Available screened to Mil-PRF-19500



Die Size = 0.9 mm x 0.9 mm

Advantages

- High temperature operation
- Improved circuit efficiency (Lower overall cost)
- Low switching losses
- Ease of paralleling devices without thermal runaway
- Smaller heat sink requirements
- Industry's lowest reverse recovery charge
- Industry's lowest device capacitance
- Ideal for output switching of power supplies
- Best in class reverse leakage current at operating temperature

Applications

- Down Hole Oil Drilling
- Geothermal Instrumentation
- Solenoid Actuators
- General Purpose High-Temperature Switching
- Amplifiers
- Solar Inverters
- Switched-Mode Power Supply (SMPS)
- Power Factor Correction (PFC)

Maximum Ratings at $T_j = 250^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values	Unit
Repetitive peak reverse voltage	V_{RRM}		1200	V
Continuous forward current	I_F	$T_C = 25^\circ\text{C}$, $R_{thJC} = 9.52$	2.5	A
Continuous forward current	I_F	$T_C \leq 225^\circ\text{C}$, $R_{thJC} = 9.52$	0.75	A
RMS forward current	$I_{F(RMS)}$	$T_C \leq 225^\circ\text{C}$, $R_{thJC} = 9.52$	1.3	A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25^\circ\text{C}$, $t_p = 10\text{ ms}$	8	A
Non-repetitive peak forward current	$I_{F,max}$	$T_C = 25^\circ\text{C}$, $t_p = 10\text{ }\mu\text{s}$	65	A
I^2t value	$\int i^2 dt$	$T_C = 25^\circ\text{C}$, $t_p = 10\text{ ms}$	0.5	A^2S
Power dissipation	P_{tot}	$T_C = 25^\circ\text{C}$, $R_{thJC} = 9.52$	26	W
Operating and storage temperature	T_j, T_{stg}		-55 to 250	$^\circ\text{C}$

Electrical Characteristics at $T_j = 250^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Diode forward voltage	V_F	$I_F = 0.75\text{ A}$, $T_j = 25^\circ\text{C}$ $I_F = 0.75\text{ A}$, $T_j = 210^\circ\text{C}$		1.7 2.8		V
Reverse current	I_R	$V_R = 1200\text{ V}$, $T_j = 25^\circ\text{C}$ $V_R = 1200\text{ V}$, $T_j = 250^\circ\text{C}$		1 10	10 100	μA
Total capacitive charge	Q_C	$I_F \leq I_{F,MAX}$ $dI_F/dt = 200\text{ A}/\mu\text{s}$ $T_j = 210^\circ\text{C}$	$V_R = 400\text{ V}$ $V_R = 960\text{ V}$	6 11		nC
Switching time	t_s			$V_R = 400\text{ V}$ $V_R = 960\text{ V}$	< 17	ns
Total capacitance	C	$V_R = 1\text{ V}$, $f = 1\text{ MHz}$, $T_j = 25^\circ\text{C}$ $V_R = 400\text{ V}$, $f = 1\text{ MHz}$, $T_j = 25^\circ\text{C}$ $V_R = 1000\text{ V}$, $f = 1\text{ MHz}$, $T_j = 25^\circ\text{C}$		66 10 8		pF

Figures:




Figure 1: Typical Forward Characteristics




Figure 2: Typical Reverse Characteristics




Figure 3: Typical Junction Capacitance vs Reverse Voltage Characteristics





Figure 4: Typical Capacitive Energy vs Reverse Voltage Characteristics

Mechanical Parameters

Die Dimensions	0.9 x 0.9	mm ²
Anode pad size	0.64 x 0.64	
Die Area total / active	0.81/0.36	
Die Thickness	360	μm
Wafer Size	100	mm
Flat Position	0	deg
Die Frontside Passivation	Polyimide	
Anode Pad Metallization	4000 nm Al	
Backside Cathode Metallization	400 nm Ni + 200 nm Au	
Die Attach	Electrically conductive glue or solder	
Wire Bond	Al ≤ 350 μm	
Reject ink dot size	Φ ≥ 0.3 mm	
Recommended storage environment	Store in original container, in dry nitrogen, < 6 months at an ambient temperature of 23 °C	

Chip Dimensions:



DIE	A [mm]	0.9
	B [mm]	0.9
METAL	C [mm]	0.64
	D [mm]	0.64
WIRE BONDABLE	E [mm]	0.6
	F [mm]	0.6

Revision History

Date	Revision	Comments	Supersedes
2015/02/09	1	Inserted Mechanical Parameters	
2012/04/03	0	Initial release	

Published by

GeneSiC Semiconductor, Inc.
43670 Trade Center Place Suite 155
Dulles, VA 20166

GeneSiC Semiconductor, Inc. reserves right to make changes to the product specifications and data in this document without notice.

GeneSiC disclaims all and any warranty and liability arising out of use or application of any product. No license, express or implied to any intellectual property rights is granted by this document.

Unless otherwise expressly indicated, GeneSiC products are not designed, tested or authorized for use in life-saving, medical, aircraft navigation, communication, air traffic control and weapons systems, nor in applications where their failure may result in death, personal injury and/or property damage.

SPICE Model Parameters

This is a secure document. Please copy this code from the SPICE model PDF file on our website (http://www.genesicsemi.com/images/hit_sic/baredie/schottky/GB01SHT12-CAL_SPICE.pdf) into LTSPICE (version 4) software for simulation of the GB01SHT12-CAL.

```
*      MODEL OF GeneSiC Semiconductor Inc.
*
*      $Revision:   1.0           $
*      $Date:      05-SEP-2013    $
*
*      GeneSiC Semiconductor Inc.
*      43670 Trade Center Place Ste. 155
*      Dulles, VA 20166
*
*      COPYRIGHT (C) 2013 GeneSiC Semiconductor Inc.
*      ALL RIGHTS RESERVED
*
*  These models are provided "AS IS, WHERE IS, AND WITH NO WARRANTY
*  OF ANY KIND EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED
*  TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A
*  PARTICULAR PURPOSE."
*  Models accurate up to 2 times rated drain current.
*
*  Start of GB01SHT12-CAL SPICE Model
*
.SUBCKT GB01SHT12 ANODE KATHODE
R1 ANODE INT R=((TEMP-24)*0.0099); Temperature Dependant Resistor
D1 INT KATHODE GB01SHT12_25C; Call the 25C Diode Model
D2 ANODE KATHODE GB01SHT12_PIN; Call the PiN Diode Model
.MODEL GB01SHT12_25C D
+ IS      1.88E-18      RS      0.9255
+ N        1          IKF      98.29122743
+ EG       1.2         XTI      3
+ CJO      7.90E-11    VJ       0.367
+ M         1.63       FC       0.5
+ TT       1.00E-10    BV       1200
+ IBV      1.00E-03    VPK      1200
+ IAVE     1          TYPE     SiC_Schottky
+ MFG      GeneSiC_Semiconductor
.MODEL GB01SHT12_PIN D
+ IS      2.76E-16      RS      0.84243
+ N        1          IKF      2.98675
+ EG       3.23        XTI      30
+ FC       0.5         TT       0
+ BV       1200        IBV      1.00E-03
+ VPK      1200        IAVE     1
+ TYPE     SiC_PiN
.ENDS
*
*  End of GB01SHT12-CAL SPICE Model
```

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[GeneSiC Semiconductor:](#)

[GB01SHT12-CAL](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru