




96-PIN DIN VME EUROCARD 6U




E160-6U-1 9.19"H x 6.3"L x .062" TH
E220-6U-1 9.19"H x 8.66"L x .062" TH
 (233mm x 220mm & 160mm)
 0.100" grid in 6U Eurocard size. Pad-Per-Hole pattern both sides with plated-thru holes. Voltage and ground busses on board perimeter both sides. Row and column legends. 0.042" diameter holes.
 16 pin DIP Capacity: 100, 140 Socket Pin: R32
 WW Terminals: T44, T46, T49, T68
 Male Right Angle WW Connector: RE96MWR
 Extender: VMEE-M Material: FR-4
 Card Cage: CCK160-6U, CCK220-6U



E160-6U-2 9.19"H x 6.3"L x .062" TH
E220-6U-2 9.19"H x 8.66"L x .062" TH
 (233mm x 220mm or 160mm)
 0.100" grid in 6U Eurocard size. Voltage and ground busses on board perimeter both sides. Row and column legends. Bare inner prototype area with no pads both sides. 0.042" diameter holes.
 16 pin DIP Capacity: 100, 140 Socket Pin: R32
 WW Terminals: T44, T46, T49, T68
 Male Right Angle WW Connector: RE96MWR.
 Extender: VMEE-M. Material: FR-4
 Card Cage: CCK160-6U, CCK220-6U




E160-6U-3 9.19"H x 6.3"L x .062" TH
E220-6U-3 9.19"H x 8.66"L x .062" TH
 (233mm x 220mm or 160mm)
 0.100" grid in 6U Eurocard size. Overall voltage ground plane with no pads or busses on either side provide excellent shielding and power distribution. Row and column legends. To simulate plated-thru holes committed to voltage or ground planes, use Vector T123 eyelets. To commit Wire Wrap pins to voltage or ground planes, use Vector T124 solder washers 0.055" diameter holes.
 16 pin DIP Capacity: 105, 168 Socket Pin: R32, R53 Male Right Angle WW Connector: RE96MWR. Extender: VMEE-M. Material: FR-4
 Card Cage: CCK160-6U, CCK220-6U



4615 9.19"H x 6.3"L x .062" TH
 (233.4mm x 160mm)
 0.100" grid in 6U Eurocard size (9.19" x 6.3"),
 3-Hole Solder Pad (0.28" x 0.080")
 .042" holes plated thru on 2 sides
 16-Pin DIP= 50
 Material: FR4 Epoxy Glass
 WW Terminals: T44, T46, T49, T68
 WW Socket Pin: R32
 Rec.Card Cage: CCK160-6U
 96-Pin Din Connector: RE96MWR


160-PIN VME64X EUROCARD



4616 9.19"H x 6.3"L x .062" TH
 (233mm x 160mm)
4616P3 With P1, P2, P0 connectors
 (installed on back of card)

0.100" grid in 6U Eurocard size. Three-hole solder pad (0.28" x 0.080") pattern both sides with plated-thru holes. Interleaved busses on both sides, back to back. .042" diameter holes and column legends. Green soldermask board has mounting for 5-row P1 and P2 VME64X connectors and 6-row HM P0 connectors. Both can mount on front OR back of card

16-Pin DIP= 50 Material:
 WW Terminals: T44, T46, T49, T68
 WW Socket Pin: R32
 Male Right Angle WW Connector: RE96MWR
 Card Cage: CCK28-84-00



4616-1 9.19"H x 6.3"L x .062" TH
 (233mm x 160mm)
4616-1P3 With P1, P2, P0 connectors
 (installed on back of card)

0.100" grid in 6U Eurocard size. Pad-Per-Hole pattern both sides with plated-thru holes. Voltage and ground busses on board perimeter both sides. Column legends.

0.042" diameter holes.
 16-Pin DIP= 100 Material:
 WW Terminals: T44, T46, T49, T68
 WW Socket Pin: R32
 Male Right Angle WW Connector:
 RE96MWR
 Card Cage: CCK28-84-00

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru