

## Cascadable Amplifier 10 to 2000 MHz

Rev. V3

### Features

- HIGH OUTPUT POWER: +22 dBm (TYP.)
- HIGH THIRD ORDER I.P.: +34 dBm (TYP.)
- WIDE BANDWIDTH: 10-2000 MHz

### Description


The A39 RF amplifier is a discrete thin film hybrid design, which incorporates the use of thin film manufacturing processes for accurate performance and high reliability. This single stage bipolar transistor feedback amplifier design displays impressive performance over a broadband frequency range. An active DC biasing network is used for temperature-stable performance, in addition to an RF Choke, used for power supply decoupling. Both TO-8 and Surface Mount packages are hermetically sealed, and MIL-STD-883 environmental screening is available.

### Ordering Information

| Part Number | Package           |
|-------------|-------------------|
| A39         | TO-8              |
| SMA39       | Surface Mount     |
| CA39 **     | SMA Connectorized |

\*\* The connectorized version is not RoHs compliant.

### Product Image



### Electrical Specifications: $Z_0 = 50\Omega$ , $V_{CC} = +15 V_{DC}$

| Parameter                          | Units | Typical       | Guaranteed    |                |
|------------------------------------|-------|---------------|---------------|----------------|
|                                    |       | 25°C          | 0° to 50°C    | -54° to +85°C* |
| Frequency                          | MHz   | 5-2050        | 10-2000       | 10-2000        |
| Small Signal Gain (min)            | dB    | 7.5           | 6.5           | 6.0            |
| Gain Flatness (max)                | dB    | ±0.3          | ±0.7          | ±1.0           |
| Reverse Isolation                  | dB    | 14            |               |                |
| Noise Figure (max)                 | dB    | 8.5           | 9.5           | 10.0           |
| Power Output<br>@ 1 dB comp. (min) | dBm   | 22.0          | 20.0          | 19.5           |
| IP3                                | dBm   | +34           |               |                |
| IP2                                | dBm   | +50           |               |                |
| Second Order Harmonic IP           | dBm   | +55           |               |                |
| VSWR Input / Output (max)          |       | 1.6:1 / 1.6:1 | 2.2:1 / 2.2:1 | 2.3:1 / 2.3:1  |
| DC Current @ 15 Volts (max)        | mA    | 90            | 94            | 98             |

### Absolute Maximum Ratings

| Parameter                                 | Absolute Maximum |
|-------------------------------------------|------------------|
| Storage Temperature                       | -62°C to +125°C  |
| Case Temperature                          | 125°C            |
| DC Voltage                                | +17 V            |
| Continuous Input Power                    | +50 dBm          |
| Short Term Input power<br>(1 minute max.) | 100 mW           |
| Peak Power (3 µsec max.)                  | 0.5 W            |
| "S" Series Burn-In<br>Temperature (case)  | 125°C            |

### Thermal Data: $V_{CC} = +15 V_{DC}$

| Parameter                                        | Rating  |
|--------------------------------------------------|---------|
| Thermal Resistance $\theta_{jc}$                 | 100°C/W |
| Transistor Power Dissipation $P_d$               | 0.935 W |
| Junction Temperature Rise<br>Above Case $T_{jc}$ | 93°C    |

1 \* Over temperature performance limits for part number CA39, guaranteed from 0°C to +50°C only.

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document.



THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.



## Rev. V3

## Outline Drawing: TO-8 \*



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)