



# TS831

## MICROPOWER VOLTAGE SUPERVISOR RESET ACTIVE LOW

- ULTRA LOW POWER CONSUMPTION :  
12 $\mu$ A maximum
- PRECISION RESET THRESHOLD
- THRESHOLD VOLTAGE:  
4.33V typ. FOR TS831-5  
4.50V typ. FOR TS831-4  
2.71V typ. FOR TS831-3
- GUARANTEED RESET OPERATION FOR  
V<sub>CC</sub> DOWN TO 1V
- OPEN DRAIN OUTPUT COMPARATOR
- FAST RESPONSE TIME : 20 $\mu$ s FOR A 10mV  
OVERDRIVE
- INTERNAL BUILT-IN HYSTERESIS
- PIN TO PIN COMPATIBLE WITH MC33064  
AND MC33164

### DESCRIPTION

The TS831 is an ultra low power integrated circuit incorporating a high stability band-gap voltage reference and a comparator with an open drain output.

The threshold voltage is set at 4.33V for TS831-5, 4.5V for TS831-4 and 2.71V for TS831-3 by internal thermally matched resistors.

The comparator exhibits a 20 $\mu$ s response (with 10mV overdrive) and has an open drain output active when input voltage is lower than the threshold. An internal hysteresis, 100mV for TS831-4 / TS831-5 and 60mV for TS831-3, increases the comparator's noise margin and prevents false reset operation.

### APPLICATION

- Power-on reset generator for microcontroller
- Power failure detector


### ORDER CODE

| Part Number | Temperature Range | Package |   |   |
|-------------|-------------------|---------|---|---|
|             |                   | D       | Z | P |
| TS831-5I    | -40, +125°C       | •       | • | • |
| TS831-4I    |                   | •       | • | • |
| TS831-3I    |                   | •       | • | • |


Z= TO92 Plastic package

D = Small Outline Package (SO) - also available in Tape & Reel (DT)

P = Thin Shrink Small Outline Package (TSSOP) - only available in Tape & Reel (PT)



### PIN CONNECTIONS (top view)



**ABSOLUTE MAXIMUM RATINGS**

| Symbol    | Parameter                                                 | Value                  | Unit |
|-----------|-----------------------------------------------------------|------------------------|------|
| $V_{CC}$  | Supply Voltage <sup>1)</sup>                              | 7                      | V    |
| $V_{OUT}$ | Output Voltage                                            | -0.3 to $V_{CC} + 0.3$ | V    |
| $I_{OUT}$ | Output Sink Current<br>TS831-5 and TS831-4<br>TS831-3     | 20<br>5                | mA   |
| $P_D$     | Power Dissipation <sup>2)</sup><br>TO92<br>SO8<br>TSSOP8  | 625<br>700<br>625      | mW   |
| $I_F$     | Clamp Diode Forward Current, pin 1 to pin 2 <sup>3)</sup> | 100                    | mA   |
| $T_{STG}$ | Storage Temperature                                       | -65 to +150            | °C   |

1. All voltages values, except differential voltage are with respect to network ground terminal.

2.  $T_j = 150^\circ\text{C}$ ,  $T_{amb} = 25^\circ\text{C}$  with  $R_{thja} = 200^\circ\text{C/W}$  for TO-92 package  
 $R_{thja} = 175^\circ\text{C/W}$  for SO8 package  
 $R_{thja} = 200^\circ\text{C/W}$  for TSSOP8 package

3. Maximum package power dissipation limits must be observed.

**OPERATING CONDITIONS**

| Symbol     | Parameter                            | Value       | Unit |
|------------|--------------------------------------|-------------|------|
| $V_{CC}$   | Supply Voltage                       | 1 to 5.5    | V    |
| $T_{OPER}$ | Operating Free Air Temperature Range | -40 to +125 | °C   |

**TS831-5**
**ELECTRICAL CHARACTERISTICS**  $T_{amb} = 25^\circ\text{C}$  (unless otherwise specified)

| Symbol    | Parameter                                                                                                             | Min.         | Typ. | Max.                | Unit |
|-----------|-----------------------------------------------------------------------------------------------------------------------|--------------|------|---------------------|------|
| $V_{THI}$ | Threshold Voltage with $V_{CC}$ Increasing<br>-40°C ≤ $T_{amb}$ ≤ +85°C<br>-40°C ≤ $T_{amb}$ ≤ +125°C                 | 4.11<br>4.11 | 4.33 | 4.46<br>4.50        | V    |
| $V_{THD}$ | Threshold Voltage with $V_{CC}$ Decreasing<br>-40°C ≤ $T_{amb}$ ≤ +85°C<br>-40°C ≤ $T_{amb}$ ≤ +125°C                 | 4.10<br>4.06 | 4.21 | 4.46<br>4.46        | V    |
| $V_{HYS}$ | Hysteresis Voltage                                                                                                    | 50           | 100  | 200                 | mV   |
| $I_{CC}$  | Current Consumption $V_{CC} = 5V$                                                                                     |              |      | 12                  | μA   |
| $V_{OL}$  | Low Level Output Voltage<br>-40°C ≤ $T_{amb}$ ≤ +85°C<br>-40°C ≤ $T_{amb}$ ≤ +125°C<br>$V_{CC} = 4V$ , $I_{OL} = 8mA$ |              | 450  | 800<br>1000<br>1300 | mV   |
| $I_{OH}$  | High Level Output Current<br>-40°C ≤ $T_{amb}$ ≤ +125°C<br>$V_{CC} = 5V$                                              |              | 2    | 100<br>1000         | nA   |
| $T_{PHL}$ | Response Time High to Low<br>$R_L = 10k\Omega$ , $C_L = 15pF$ , $V_{CC} = V_{THD} - 10mV$                             |              | 20   |                     | μs   |

**Note :** Limits are 100% production tested at 25°C. Limits over temperature are guaranteed through correlation and by design.

**TS831-4****ELECTRICAL CHARACTERISTICS** Tamb = 25°C (unless otherwise specified)

| Symbol    | Parameter                                                                                             | Min.         | Typ. | Max.                | Unit |
|-----------|-------------------------------------------------------------------------------------------------------|--------------|------|---------------------|------|
| $V_{THI}$ | Threshold Voltage with $V_{CC}$ Increasing<br>-40°C ≤ Tamb ≤ +85°C<br>-40°C ≤ Tamb ≤ +125°C           | 4.18<br>4.18 | 4.50 | 4.66<br>4.70        | V    |
| $V_{THD}$ | Threshold Voltage with $V_{CC}$ Decreasing<br>-40°C ≤ Tamb ≤ +85°C<br>-40°C ≤ Tamb ≤ +125°C           | 4.17<br>4.13 | 4.40 | 4.66<br>4.66        | V    |
| $V_{HYS}$ | Hysteresis Voltage                                                                                    | 50           | 100  | 200                 | mV   |
| $I_{CC}$  | Current Consumption $V_{CC} = 5V$                                                                     |              |      | 12                  | μA   |
| $V_{OL}$  | Low Level Output Voltage $V_{CC} = 4V, I_{OL} = 8mA$<br>-40°C ≤ Tamb ≤ +85°C<br>-40°C ≤ Tamb ≤ +125°C |              | 450  | 800<br>1000<br>1300 | mV   |
| $I_{OH}$  | High Level Output Current $V_{CC} = 5V$<br>-40°C ≤ Tamb ≤ +125°C                                      |              | 2    | 100<br>1000         | nA   |
| $T_{PHL}$ | Response Time High to Low<br>$R_L = 10k\Omega, C_L = 15pF, V_{CC} = V_{THD} - 10mV$                   |              | 20   |                     | μs   |


**Note :** Limits are 100% production tested at 25°C. Limits over temperature are guaranteed through correlation and by design.

**TS831-3****ELECTRICAL CHARACTERISTICS** Tamb = 25°C (unless otherwise specified)


| Symbol    | Parameter                                                                           | Min. | Typ. | Max.        | Unit |
|-----------|-------------------------------------------------------------------------------------|------|------|-------------|------|
| $V_{THI}$ | Threshold Voltage with $V_{CC}$ Increasing<br>-40°C ≤ Tamb ≤ +125°C                 | 2.55 | 2.71 | 2.8         | V    |
| $V_{THD}$ | Threshold Voltage with $V_{CC}$ Decreasing<br>-40°C ≤ Tamb ≤ +125°C                 | 2.55 | 2.65 | 2.8         | V    |
| $V_{HYS}$ | Hysteresis Voltage                                                                  | 30   | 60   | 100         | mV   |
| $I_{CC}$  | Current Consumption $V_{CC} = 3V$                                                   |      |      | 12          | μA   |
| $V_{OL}$  | Low Level Output Voltage $V_{CC} = 2.4V, I_{OL} = 1mA$<br>-40°C ≤ Tamb ≤ +125°C     |      | 140  | 400<br>500  | mV   |
| $I_{OH}$  | High Level Output Current $V_{CC} = 3V$<br>-40°C ≤ Tamb ≤ +125°C                    |      | 2    | 100<br>1000 | nA   |
| $T_{PHL}$ | Response Time High to Low<br>$R_L = 10k\Omega, C_L = 15pF, V_{CC} = V_{THD} - 10mV$ |      | 20   |             | μs   |

**Note :** Limits are 100% production tested at 25°C. Limits over temperature are guaranteed through correlation and by design.


## EQUIVALENT SCHEMATIC DIAGRAM




## TIMING DIAGRAM




Output voltage versus Vcc




Reset output voltage versus Vcc




Output voltage versus Vcc




Reset output voltage versus Vcc




Output voltage versus Vcc




Reset output voltage versus Vcc




$V_{THI}$  versus temperature




$V_{THD}$  versus temperature




Hysteresis voltage versus temperature




Supply current versus temperature







Supply current vs V<sub>CC</sub> & temperature




Voltage output low vs I<sub>sink</sub> & temperature




Supply current vs  $V_{CC}$  & temperatureVoltage output low vs  $I_{SINK}$  & temperatureSupply current vs  $V_{CC}$  & temperatureVoltage output low vs  $I_{SINK}$  & temperature


Clamp diode forward current versus voltage



Response time




## Basic configuration




**PACKAGE MECHANICAL DATA**

8 PINS - PLASTIC MICROPACKAGE (SO)




| Dim. | Millimeters |      |      | Inches |       |       |
|------|-------------|------|------|--------|-------|-------|
|      | Min.        | Typ. | Max. | Min.   | Typ.  | Max.  |
| A    |             |      | 1.75 |        |       | 0.069 |
| a1   | 0.1         |      | 0.25 | 0.004  |       | 0.010 |
| a2   |             |      | 1.65 |        |       | 0.065 |
| a3   | 0.65        |      | 0.85 | 0.026  |       | 0.033 |
| b    | 0.35        |      | 0.48 | 0.014  |       | 0.019 |
| b1   | 0.19        |      | 0.25 | 0.007  |       | 0.010 |
| C    | 0.25        |      | 0.5  | 0.010  |       | 0.020 |
| c1   | 45° (typ.)  |      |      |        |       |       |
| D    | 4.8         |      | 5.0  | 0.189  |       | 0.197 |
| E    | 5.8         |      | 6.2  | 0.228  |       | 0.244 |
| e    |             | 1.27 |      |        | 0.050 |       |
| e3   |             | 3.81 |      |        | 0.150 |       |
| F    | 3.8         |      | 4.0  | 0.150  |       | 0.157 |
| L    | 0.4         |      | 1.27 | 0.016  |       | 0.050 |
| M    |             |      | 0.6  |        |       | 0.024 |
| S    | 8° (max.)   |      |      |        |       |       |

**PACKAGE MECHANICAL DATA**  
3 PINS - PLASTIC PACKAGE TO92



| Dim. | Millimeters |      |       | Inches |        |        |
|------|-------------|------|-------|--------|--------|--------|
|      | Min         | Typ. | Max.  | Min.   | Typ.   | Max.   |
| L    |             | 1.27 |       |        | 0.05   |        |
| B    | 3.2         | 3.7  | 4.2   | 0.126  | 0.1457 | 0.1654 |
| O1   | 4.45        | 5.00 | 5.2   | 0.1752 | 0.1969 | 0.2047 |
| C    | 4.58        | 5.03 | 5.33  | 0.1803 | 0.198  | 0.2098 |
| K    | 12.7        |      |       | 0.5    |        |        |
| O2   | 0.407       | 0.5  | 0.508 | 0.016  | 0.0197 | 0.02   |
| a    | 0.35        |      |       | 0.0138 |        |        |

**PACKAGE MECHANICAL DATA****8 PINS - THIN SHRINK SMALL OUTLINE PACKAGE**

| Dim. | Millimeters |      |      | Inches |        |       |
|------|-------------|------|------|--------|--------|-------|
|      | Min.        | Typ. | Max. | Min.   | Typ.   | Max.  |
| A    |             |      | 1.20 |        |        | 0.05  |
| A1   | 0.05        |      | 0.15 | 0.01   |        | 0.006 |
| A2   | 0.80        | 1.00 | 1.05 | 0.031  | 0.039  | 0.041 |
| b    | 0.19        |      | 0.30 | 0.007  |        | 0.15  |
| c    | 0.09        |      | 0.20 | 0.003  |        | 0.012 |
| D    | 2.90        | 3.00 | 3.10 | 0.114  | 0.118  | 0.122 |
| E    |             | 6.40 |      |        | 0.252  |       |
| E1   | 4.30        | 4.40 | 4.50 | 0.169  | 0.173  | 0.177 |
| e    |             | 0.65 |      |        | 0.025  |       |
| k    | 0°          |      | 8°   | 0°     |        | 8°    |
| l    | 0.50        | 0.60 | 0.75 | 0.09   | 0.0236 | 0.030 |

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a registered trademark of STMicroelectronics

© 2001 STMicroelectronics - Printed in Italy - All Rights Reserved  
STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - China - Finland - France - Germany - Hong Kong - India - Italy - Japan - Malaysia - Malta - Morocco  
Singapore - Spain - Sweden - Switzerland - United Kingdom

© <http://www.st.com>



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)