

# POWER RELAY

## 2 POLES-2A High Insulation/wide Gap FTR-C1 Series

### ■ FEATURES

- 2 Poles, 2 form C
- Contact gap: more than 0.6mm
- High surge voltage: 2500V between open contacts  
5000V between coil & contact  
Complies with Telcordia (former Bellcore) 2nd level surge
- Dielectric strength: 1500VAC between open contacts  
3000VAC between coil and contact
- Dimensions of large contact gap relay  
Height: 9.3mm maximum (THT)  
9.65mm maximum (SMT)  
Length: 15mm maximum  
Width: 7.5mm maximum
- Conforms to IEC60950/ EN60950/UL1950/CSA C 22.2  
No. 950 working voltage 250V (supplementary)
- High insulation: Clearance: min 2.0mm (coil and contacts)  
Creepage: min 2.5mm (coil and contacts)
- High reliability-Bifurcated contacts
- Low power consumption 280mW (latching type 140mW)
- RoHS compliant



### ■ PARTNUMBER INFORMATION

[Example] FTR-C1 C A 012 G - B05  
(a) (b) (c) (d) (e) (f)

|     |                       |                       |                                                    |
|-----|-----------------------|-----------------------|----------------------------------------------------|
| (a) | Relay type            | FTR-C1: FTR-C1 Series |                                                    |
| (b) | Contact Configuration | C                     | : Through hole type                                |
|     |                       | G                     | : Surface mount type                               |
|     |                       | S                     | : Surface mount type-reduced mounting area         |
| (c) | Coil Type / Enclosure | A                     | : Standard type                                    |
|     |                       | B                     | : Single coil latching type                        |
| (d) | Coil rated Voltage    | 012                   | : 3.....24 VDC<br>Coil table at page 3             |
| (e) | Contact Material      | G                     | : Gold plated silver palladium                     |
| (f) | Tape / reel ordering  | Nil                   | : standard packaging (tube)                        |
|     |                       | B05                   | : tape / reel package, only available for SMT type |

Actual marking does not carry the type name : "FTR"

E.g.: Ordering code: FTR-C1CA012G

Actual marking: C1CA012G

# FTR-C1 SERIES

## ■ SPECIFICATION

| Item         |                          |                   | Non-latching<br>FTR-C1 ( ) A                                              | Latching<br>FTR-C1 ( ) B |
|--------------|--------------------------|-------------------|---------------------------------------------------------------------------|--------------------------|
| Contact Data | Configuration            |                   | 2C                                                                        |                          |
|              | Construction             |                   | Bifurcated                                                                |                          |
|              | Material                 |                   | Gold plated silver palladium                                              |                          |
|              | Resistance (Initial)     |                   | ≤ 100mOhm @1A, 6VDC                                                       |                          |
|              | Contact rating resistive |                   | 1A, 30VDC / 0.3A, 125VAC / 0.3A, 110VDC                                   |                          |
|              | Max. Switching Voltage   |                   | 250VAC / 220VDC                                                           |                          |
|              | Max. Switching Power     |                   | 62.5VA / 30W                                                              |                          |
|              | Max. Carry Current       |                   | 2A                                                                        |                          |
|              | Min. Switching Load *    |                   | 10mA, 10mVDC                                                              |                          |
| Life         | Mechanical               |                   | 2x 10 <sup>6</sup>                                                        |                          |
|              | Electrical               |                   | 100x 10 <sup>3</sup> at 0.3A, 125VAC / 1A, 30VDC                          |                          |
| Coil Data    | Rated Power              |                   | 280 to 300mW                                                              | 140 to 180mW             |
|              | Operate Power            |                   | 158 to 162mW                                                              | 158 to 162mW             |
|              | Operating temp range     |                   | -40 to +85C (no frost)                                                    |                          |
| Timing Data  | Operate                  |                   | ≤ 6ms (at nominal voltage, no bounce)                                     |                          |
|              | Release                  |                   | ≤ 6ms (at nominal voltage, no bounce)                                     |                          |
| Insulation   | Resistance (Initial)     |                   | ≥ 1000MOhm @500VDC                                                        |                          |
|              | Dielectric strength      | Open contacts     | 1500VAC (50/60Hz) 1min                                                    |                          |
|              | Strength                 | Contacts to coil  | 3000VAC (50/60Hz) 1min                                                    |                          |
|              | Surge strength           | Coil to contacts  | 5000V, 1.2 x 10 <sup>6</sup> standard wave / 6000V, 1.2 x 50 <sup>6</sup> |                          |
|              | Clearance                | open contacts     | 0.6mm                                                                     |                          |
|              | Clearance                | adjecent contacts | 1.54mm                                                                    |                          |
|              | Clearance                | coil and contacts | 2.0mm                                                                     |                          |
|              | Creepage                 | open contacts     | 1.54mm                                                                    |                          |
|              | Creepage                 | coil and contacts | 2.0mm                                                                     |                          |
| Other        | Vibration Resistance     | Misoperation>1us  | 10 to 55Hz double amplitude 3.3mm                                         |                          |
|              |                          | Endurance         | 10 to 55Hz double amplitude 5mm                                           |                          |
|              | Shock                    | Misoperation>1us  | Min. 500m/s <sup>2</sup>                                                  |                          |
|              |                          | Endurance         | Min. 1000m/s <sup>2</sup>                                                 |                          |
|              | Weight                   |                   | Approx. 2 g                                                               |                          |

\* Minimum switching loads mentioned above are reference values. Please perform the confirmation test with actual load before production since reference values may vary according to switching frequencies, environmental conditions and expected reliability levels.

# FTR-C1 SERIES

## ■ COIL RATING

Standard type

| Coil Code | Rated Coil Voltage (VDC) | Coil Resistance +/- 10% (Ohm) | Must Operate Voltage (V) *1 | Must Release-Voltage (V) *1 | Max. Coil Voltage (V) | Nominal Coil Power (mW) |
|-----------|--------------------------|-------------------------------|-----------------------------|-----------------------------|-----------------------|-------------------------|
| 003       | 3                        | 32.1                          | 2.25                        | 0.3                         | 4.5                   | 230                     |
| 4.5       | 6                        | 72.3                          | 3.38                        | 0.45                        | 6.75                  |                         |
| 005       | 9                        | 89.3                          | 3.75                        | 0.5                         | 7.5                   |                         |
| 012       | 12                       | 514                           | 9                           | 1.2                         | 18                    |                         |
| 024       | 18                       | 1920                          | 18                          | 2.4                         | 36                    | 300                     |

Latching type

| Coil Code | Rated Coil Voltage (VDC) | Coil Resistance +/- 10% (Ohm) | Must Operate Voltage (V) *1 | Must Release-Voltage (V) *1 | Max. Coil Voltage (V) | Nominal Coil Power (mW) |
|-----------|--------------------------|-------------------------------|-----------------------------|-----------------------------|-----------------------|-------------------------|
| 003       | 3                        | 64.0                          | +2.25                       | 2.25                        | 4.5                   | 140                     |
| 4.5       | 4.5                      | 145                           | +3.38                       | 3.38                        | 6.75                  |                         |
| 005       | 5                        | 179                           | +3.75                       | 3.75                        | 7.5                   |                         |
| 012       | 12                       | 1029                          | +9                          | 9                           | 18                    |                         |
| 024       | 24                       | 3200                          | +18                         | 18                          | 36                    | 180                     |

Note: All values in the table are measured at 20°C.

No contact current at 20°C

\*1: Specified values are subject to pulse wave voltage




## ■ SAFETY STANDARDS

| Type | Compliance               | Contact rating                          |
|------|--------------------------|-----------------------------------------|
| UL   | UL 508                   | Flammability: UL 94-V0 (plastics)       |
|      | E63615                   | 0.3A, 125 VAC (resistive)<br>1 A, 30VDC |
| CSA  | C22.2 No. 14<br>LR 40304 | 0.3A, 110VDC                            |
| BSI  | IEC 60950-1              |                                         |

# FTR-C1 SERIES

## ■ DIMENSIONS AND SCHEMATICS


Through hole type




Unit: mm

## ■ TERMINAL DESIGNATIONS


Standard type  
(Bottom view de-energized position)



Single Coil Latching type  
(Bottom view reset position)



## ■ RECOMMENDED MOUNTING PAD




S shows the polarity of set position  
R shows the polarity of reset position

Unit: mm

# FTR-C1 SERIES

## ■ DIMENSIONS AND SCHEMATICS


Surface mount type



## ■ TERMINAL DESIGNATIONS


Standard type

(Bottom view reset position)




Single Coil Latching type

(Bottom view reset position)



## ■ RECOMMENDED MOUNTING PAD




S shows the polarity of set position  
R shows the polarity of reset position

Unit: mm

# FTR-C1 SERIES


## ■ DIMENSIONS AND SCHEMATICS

Space saving type




### PC board mounting pad layout

Top view



### Schematics

Top view



Unit: mm

# FTR-C1 SERIES

## ■ RECOMMENDED SOLDERING CONDITIONS SMT


(TEMPERATURE PROFILE, please see page 9)

- Note:
1. Temperature profiles show the temperature of PC board surface.
  2. Please perform soldering test with your actual PC board before mass production, since the temperatures of PC board surfaces vary according to the size of PC board, status of parts mounting and heating method.


## ■ PACKAGING

Packaging method (only tape packaging is available)


1. Taping standards: JIS C 0806 and RC-10092B (EIAJ)
2. Reel type: TB2416 or TB2416
3. Reel type: RD24D
4. Quantity of 1 reel: 500 pieces



Tape Dimensions:



Reel Dimensions:



Unit: mm

## RoHS Compliance and Lead Free Information

### 1. General Information

- All signal and power relays produced by Fujitsu Components are compliant with RoHS directive 2002/95/EC including amendments.
- Cadmium as used in electrical contacts is exempted from the RoHS directives on October 21st, 2005. (Amendment to Directive 2002/95/EC)
- All of our signal and power relays are lead-free. Please refer to Lead-Free Status Info for older date codes at: <http://www.fujitsu.com/us/downloads/MICRO/fcai/relays/lead-free-letter.pdf>
- Lead free solder plating on relay terminals is Sn-3.0Ag-0.5Cu, unless otherwise specified. This material has been verified to be compatible with PbSn assembly process.
- "LF" is marked on each outer and inner carton. (No marking on individual relays).

### 2. Recommended Lead Free Solder Profile

- Recommended solder Sn-3.0Ag-0.5Cu.

**Flow Solder condition:**

Pre-heating: maximum 120°C  
Soldering: dip within 5 sec. at  
260°C solder bath

**Solder by Soldering Iron:**

Soldering Iron  
Temperature: maximum 360°C  
Duration: maximum 3 sec.

**We highly recommend that you confirm your actual solder conditions**

### 3. Moisture Sensitivity

- Moisture Sensitivity Level standard is not applicable to electromechanical relays, unless otherwise indicated.

### 4. Tin Whiskers

- Dipped SnAgCu solder is known as presenting a low risk to tin whisker development. No considerable length whisker was found by our in house test.

# FTR-C1 SERIES

## Fujitsu Components International Headquarter Offices

### Japan

Fujitsu Component Limited  
Gotanda-Chuo Building  
3-5, Higashigotanda 2-chome, Shinagawa-ku  
Tokyo 141, Japan  
Tel: (81-3) 5449-7010  
Fax: (81-3) 5449-2626  
Email: [promothq@ft.ed.fujitsu.com](mailto:promothq@ft.ed.fujitsu.com)  
Web: [www.fcl.fujitsu.com](http://www.fcl.fujitsu.com)

### North and South America

Fujitsu Components America, Inc.  
250 E. Caribbean Drive  
Sunnyvale, CA 94089 U.S.A.  
Tel: (1-408) 745-4900  
Fax: (1-408) 745-4970  
Email: [components@us.fujitsu.com](mailto:components@us.fujitsu.com)  
Web: <http://www.fujitsu.com/us/services/edevices/components/>

### Europe

Fujitsu Components Europe B.V.  
Diamantlaan 25  
2132 WV Hoofddorp  
Netherlands  
Tel: (31-23) 5560910  
Fax: (31-23) 5560950  
Email: [info@fceu.fujitsu.com](mailto:info@fceu.fujitsu.com)  
Web: [emea.fujitsu.com/components/](http://emea.fujitsu.com/components/)

### Asia Pacific

Fujitsu Components Asia Ltd.  
102E Pasir Panjang Road  
#01-01 Citilink Warehouse Complex  
Singapore 118529  
Tel: (65) 6375-8560  
Fax: (65) 6273-3021  
Email: [fcal@fcal.fujitsu.com](mailto:fcsl@fcal.fujitsu.com)  
Web: <http://www.fujitsu.com/sg/services/micro/components/>

©2009 Fujitsu Components Europe B.V. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

The contents, data and information in this datasheet are provided by Fujitsu Component Ltd. as a service only to its user and only for general information purposes.

The use of the contents, data and information provided in this datasheet is at the users' own risk.

Fujitsu has assembled this datasheet with care and will endeavor to keep the contents, data and information correct, accurate, comprehensive, complete and up to date.

Fujitsu Components Europe B.V. and affiliated companies do however not accept any responsibility or liability on their behalf, nor on behalf of its employees, for any loss or damage, direct, indirect or consequential, with respect to this datasheet, its contents, data, and information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof.

Nor do Fujitsu Components Europe B.V. and affiliated companies accept on their behalf, nor on behalf of its employees, any responsibility or liability for any representation or warrant of any kind, express or implied, including warranties of any kind for merchantability or fitness for particular use, with respect to these datasheets, its contents, data, information and related graphics and the correctness, reliability, accuracy, comprehensiveness, usefulness, availability and completeness thereof. Rev. June 4, 2009

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)