Time Delay Relays – Application Data

Definition:

Time Delay is defined as the controlled period between the functioning of two events. A Time Delay relay is a combination of an electromechanical output relay and a control circuit. The control circuit is comprised of solid state components and timing circuits that control operation of the relay and timing range. Typical time delay functions include On-Delay, Repeat cycle (starting off), Interval, Off-Delay, Retriggerable One Shot, Repeat cycle (starting on), Pulse Generator, One Shot, On/Off Delay, and Memory Latch. Each function is explained in the table below. Time delay relays have a broad choice of timing ranges from less than one second to many days. There are many choices of timing adjustments from calibrated external knobs, DIP switches, thumbwheel switches, or recessed potentiometer. The output contacts on the electromechanical output relay are direct wired to the output terminals. The contact load ratings are specified for each specific type of time delay relay.

Understanding the differences between all the functions available in time delay relays can sometimes be a daunting task. When designing circuits using time delay relays questions such as:

"What initiates a time delay relay?"

"Does the timing start with the application or release of voltage?"

"When does the output relay come on?"

must be asked.

Time delay relays are simply control relays with a time delay built in. Their purpose is to control an event based on time. The difference between relays and time delay relays is when the output contacts open & close: on a control relay, it happens when voltage is applied and removed from the coil; on time delay relays, the contacts will open or close before or after a pre-selected, timed interval.

Typically, time delay relays are initiated or triggered by one of two methods:

- application of input voltage (On Delay, Interval On, Flasher, Repeat Cycle, Delayed Interval & Interval/Flasher).
- opening or closing of a trigger signal (Off Delay, Single Shot & Watchdog).

These trigger signals can be one of two designs:

- a control switch (dry contact), i.e., limit switch, push button, float switch, etc.
- voltage (commonly known as a power trigger).

To help understand, some definitions are important:

Input Voltage: Control voltage applied to the input terminals (see wiring diagrams below). Depending on the function, input voltage will either initiate the unit or make it ready to initiate when a trigger signal is applied.

Trigger Signal: On certain timing functions, a trigger signal is used to initiate the unit after input voltage has been applied. As noted above, this trigger signal can either be a control switch (dry contact switch) or a power trigger (voltage).

Output (Load): Every time delay relay has an internal relay (usually mechanical) with contacts that open & close to control the load. They are represented by the dotted lines in the wiring diagrams. Note that the user must provide the voltage to power the load being switched by the output contacts of the time delay relay.

The following tables contain both written and visual descriptions on how the common timing functions operate. A Timing Chart shows the relationship between Input Voltage, Trigger Signal (if present) and Output Contacts.



FUNCTION DEFINITION TABLE

Function	Operation	Timing Chart		
A. ON DELAY Power On	When the input voltage U is applied, timing delay t begins. Relay contacts R change state after time delay is complete. Contacts R return to their shelf state when input voltage U is removed. Trigger switch is not used in this function.	U R off t t		
B. REPEAT CYCLE Starting Off	When input voltage U is applied, time delay t begins. When time delay t is complete, relay contacts R change state for time delay t . This cycle will repeat until input voltage U is removed. Trigger switch is not used in this function.	U on t t t R off t t t		
C. INTERVAL Power On	When input voltage U is applied, relay contacts R change state immediately and timing cycle begins. When time delay is complete, contacts return to shelf state. When input voltage U is removed, contacts will also return to their shelf state. Trigger switch is not used in this function.	U t t R		
D. OFF DELAY S Break	Input voltage U must be applied continuously. When trigger switch S is closed, relay contacts R change state. When trigger switch S is opened, delay t begins. When delay t is complete, contacts R return to their shelf state. If trigger switch S is closed before time delay t is complete, then time is reset. When trigger switch S is opened, the delay begins again, and relay contacts R return to their energized state. If input voltage U is removed, relay contacts R return to their shelf state.	U S close open on t t R off		
E. RETRIGGERABLE ONE SHOT	Upon application of input voltage U , the relay is ready to accept trigger signal S . Upon application of the trigger signal S , the relay contacts R transfer and the preset time t begins. At the end of the preset time t , the relay contacts R return to their normal condition unless the trigger switch S is opened and closed prior to time out t (before preset time elapses). Continuous cycling of the trigger switch S at a rate faster than the preset time will cause the relay contacts R to remain closed. If input voltage U is removed, relay contacts R return to their shelf state.	U S open t on t R off		
F. REPEAT CYCLE Starting On	When input voltage U is applied, relay contacts R change state immediately and time delay t begins. When time delay t is complete, contacts return to their shelf state for time delay t . This cycle will repeat until input voltage U is removed. Trigger switch is not used in this function.	U t t t t t		
G. PULSE GENERATOR	Upon application of input voltage U , a single output pulse of 0.5 seconds is delivered to relay after time delay t . Power must be removed and reapplied to repeat pulse. Trigger switch is not used in this function.	U on Pulse Pulse R off t t		
H. ONE SHOT	Upon application of input voltage U , the relay is ready to accept trigger signal S . Upon application of the trigger signal S , the relay contacts R transfer and the preset time t begins. During time-out, the trigger signal S is ignored. The relay resets by applying the trigger switch S when the relay is not energized.	U S open t R off		
I. ON/OFF DELAY S Make/Break	Input voltage U must be applied continuously. When trigger switch S is closed, time delay t begins. When time delay t is complete, relay contacts R change state and remain transferred until trigger switch S is opened. If input voltage U is removed, relay contacts R return to their shelf state.	U S open t t t t R off t		
J. MEMORY LATCH S Make	Input voltage U must be applied continuously. Output changes state with every trigger switch S closure. If input voltage U is removed, relay contacts R return to their shelf state.	U S open R off		

Advantages of the 820 Series Time Delay Relays





The new 820 Series Time Delay Relays are DIN rail mountable products offering 10 different timing functions, 2 status LEDs, ultra-wide timing range (0.1 sec to 10 days) and a universal voltage input (12-240 VAC/VDC) all in one modular package.

The 821 is available as a 15 amp SPDT timer while its counterpart 822 is available as a DPDT timer also capable of switching up to 15 amps per pole.

Solid State Circuitry Used for Time and function Control.

Output Terminals Accepts up to a 14 AWG Wire.

- Offers a "one stop solution" for your power management system.
- Available in both SPDT and DPDT contact configuration.
- The two LED status indicators indicate status at a glance.
- The Green LED is on when power is applied to the input terminals. The Red LED blinks during time-out, and is ON when the output is energized.
- Color and appearance designed for high visibility in all environments.
- Only 17.5 mm wide making it ideal for tight spaces.
- Engineering availability allows for customized relay solutions.



Optional Panel Adapter (16-788C1) See Section 3 p.18

www.magnecraft.com 847-441-2540

820 Series Time Delay Relays/SPDT, DPDT 15 Amp Rating



General Specifications (@ 25°C) (UL 508)

CE

RoHS

Number and type of Contacts SPDT DPDT Contract Material Silver Allay Silver Allay 15 Current roting @ 240 VAC, 24 VDC A 15 15 Switching voltage V 240 AC, 50/60 Hz 240 VAC, 12 @ 120 VAC 1/2 @ 120	Output Characteristics	•	Units	821TD10H-UNI	822TD10H-UNI
Contact Material Silver Alloy Silver Alloy Current roling @ 240 VAC, 24 VDC A 15 15 Switching voltage V 240 C 12 @ 240 VAC 11 @ 240 VAC 12 @ 240 VAC 10 @ 10 11 @ 1 @ 10 11 @ 1 @ 1 @ 1 @ 1 @ 1 @ 1 @ 1 @ 1 @ 1	Number and type of Contacts			SPDT	DPDT
Current rating @ 240 VAC, 24 VDC A 15 15 Switching voltage V 240 AC, 50/60 Hz	Contact Material			Silver Allov	Silver Allov
Switching voltage V 240 AC, 50/60 Hz <	Current rating	@ 240 VAC, 24 VDC	Α	15	15
V 24 DC 24 DC HP 1/2 @ 120xAC 1/2 @ 120xAC HP 1@ 240 VAC 1@ 240 VAC Pilot Dury B3000 B300 Minimum Switching Requirement mA 100 100 Indication LED On = Energized Red Red Oblage Ronge % of Nominal Maximum Consumption 1.2 12240 Operating Ronge % of Nominal AC VAC / VDC 12240 12240 Maximum Consumption AC VA 3 3 3 Indication LED Green Green Green Time Scales 10 10 10 10 Time Ranges Available (See page 5/3) A,B,C,D,E,F,G,H,I,J A,B,C,D,E,F,G,H,I,J A,B,C,D,E,F,G,H,I,J Time Ranges Available (See page 5/3) A,B,C,D,E,F,G,H,I,J A,B,C,D,E,F,G,H,I,J 110 Time Ranges Available (See page 5/3) A,B,C,D,E,F,G,H,I,J A,B,C,D,E,F,G,H,I,J 110 Time Ranges Available S	Switching voltage	· · · · · · ·	V	240 AC, 50/60 Hz	240 AC, 50/60 Hz
HP 1/2 @ 120VAC 1/2 @ 120VAC Minimum Switching Requirement Indication Pilot Duty B300 B300 Indication LED Blinks = Timing On = Energized Red Red Input Characteristics VAC / VDC 12240 12240 Operating Ronge % of Nominal 85% to 110% 85% to 110% Maximum consumption AC VA 3 3 Indication LED Blinks = Timing On = Energized 85% to 110% 85% to 110% Maximum consumption AC VA 3 3 3 Indication LED Green Green Green Time Scales 0 0.11 0.110 110 Time Scales 0 0.11 0.110 110 Time Ronges Available sec 110 110 110 Time Ronges Available Maximum min 0.11 0.11 0.11 Time Scales 0 0.2 0.2 0.2 0.2			V	24 DC	24 DC
HP 1 @ 2.40 VAC 1 @ 2.40 VAC Minimum Switching Requirement mA 100 B300 Indication IED Blinks = Timing Red Red Indication IED Blinks = Timing Red Red Object Range 0 = Energized Not C / VDC 12240 12240 Operating Range % of Nominal AC VAC / VDC 12240 12240 Maximum cosumption DC W 1.7 1.7 1.7 Indication IED Greeen Greeen Greeen Greeen Time Scales 10 110 110 110 110 Time Ranges Available (See page 5/3) A.B.C.D.E.F.C.H.I.J A.B.C.D.E.F.C.H.I.J A.B.C.D.E.F.C.H.I.J Time Scales 10 110 110 110 Time Ranges Available See C 110 110 110 Time Scales 0.11 0.11 0.11 110 Time Scales 0.2 <td></td> <td></td> <td>HP</td> <td>1/2 @ 120VAC</td> <td>1/2@120VAC</td>			HP	1/2 @ 120VAC	1/2@120VAC
Pilot Duty B300 B300 Indication LED Blinks = Timing On = Energized Red Red Input Characteristics On = Energized 00 12240 12240 Operating Range % of Nominal 85% to 110% 85% to 110% 85% to 110% Maximum consumption AC VA 3 3 Indication LED CVC 12240 12240 Indication LED 85% to 110% 85% to 110% 85% to 110% Maximum consumption AC VA 3 3 3 Indication LED Green Green Green Green Time Scales 0.110 1010 0.110 1010 1010 Time Ranges Available sec 110 1010 1010 1010 Time Ranges Ine Machanical Setting % 5 5 5 Repeatability Constant Valage and Temperature % 0.2 0.2 0.2 0.2			HP	1 @ 240 VAC	1 @ 240 VAC
Minimum Switching Requirement mA 100 100 Indication LED Blinks = Timing On = Energized Red Red Input Characteristics VAC / VDC 12240 12240 Operating Range % of Nominal 85% to 110% 85% to 110% 85% to 110% Maximum Consumption AC VA 3 3 Indication LED W 1.7 1.7 Indication LED Green Green Green Time Scales 10 10 10 10 Time Scales 10 11 11 11 Time Scales 0.11 0.11 11 11 Time Scales 0 0.11 110 110 11 <td< td=""><td></td><td></td><td>Pilot Duty</td><td>B300</td><td>B300</td></td<>			Pilot Duty	B300	B300
Indication LED Blinks = Timing On = Energized Red Red Input Characteristics Voltage Range Volt (VDC) 12240 12240 Operating Range % of Nominal 85% to 110% 85% to 110% 85% to 110% Maximum consumption AC VA 3 3 Maximum consumption AC VA 3 3 Indication LED Green Green Green Time Scales 10 10 10 10 Time Scales 0.11 0.11 0.11 110 Time Ranges Available sec 110 110 110 Indication Kechanical Setting % 5 5 Repeatability Constant Voltage and Temperature % 0.2 0.2 0.2 Reset Time Maximum ms 150 150 150 Time Scales V 100,000 100,000 100,000 100,000 Read Collarity Constant Voltage	Minimum Switching Requirement		mA	100	100
On = Energized On = Energized Volage Range VaC / VDC 12240 12240 Operating Range % of Nominal 85% to 110% 85% to 110% 85% to 110% Maximum cosumption AC VA 3 3 Indication LED Green Green Timing Characteristics	Indication	LED	Blinks = Timina	Red	Red
Input Characteristics VAC / VDC 12240 12240 Operating Range % of Nominal AC VA 3 3 Maximum consumption AC VA 3 3 3 Indication LED Green Green Green Timing Characteristics Functions Available (See page 5/3) A,B,C,D,E,F,G,H,I,J A,B,C,D,E,F,G,H,I,J Time Scales 0.11 0.11 0.11 0.11 Time Ranges Available See 0.11 0.11 0.11 Indication Kechanical Setting % 5 5 Repeatability Constant Values and Temperature % 0.2 0.2 Reset Time Maximum ms 1.50 150 5 Trigger Pulse Length Minimum ms 50 50 50 Performance Constant Values and Temperature % 0.2 2500 AC 2500 AC Reset Time Maximum ms 1.50 150 100,00			On = Energized		
Valc / VDC 12240 12240 Operating Range % of Nominal AC VAC / VDC 85% to 110% 85% to 110% Maximum consumption AC VA 3 3 Indication LED Green Green Timing Characteristics	Input Characteristics		0		
Operating Range % of Nominal AC VA 3 3 3 1	Voltage Range		VAC / VDC	12240	12240
Maximum consumption AC DC VA DC 3 W 3 1.7 3 1.7 Indication LED Green Green Green Timing Characteristics	Operating Range	% of Nominal		85% to 110%	85% to 110%
DC W 1.7 1.7 Indication LED Green Green Green Timing Characteristics	Maximum consumption	AC	VA	3	3
Indication LED Green Green Timing Characteristics Functions Available (See page 5/3) A,B,C,D,E,F,G,H,I,J A,B,C,D,E,F,G,H,I,J Time Scales 0,1,,1 0,1,,1 Time Ranges Available sec 1,,10 10,1,,1 Time Ranges Available sec 1,,10 0,1,,1 Time Ranges Available sec 1,,10 0,1,,1 Marin 1,,10 0,1,,1 Marin 1,,10 0,1,,1 Marin 1,,10 0,1,,1 Marin 1,,10 0,1,,1 Tolerance Mechanical Setting % 5 5 Repeatability Constant Voltage and Temperature % 0,2 0,2 Reset Time Maximum ms 150 150 Trigger Pulse Length Minimum ms 50 Performance Characteristics V 2500 AC Terminal Vire Capacity Input to Contacts V 2500 AC Terminal Vire Capacity Award Vire 100,000 100,000 Dielectric strength Input to Contacts V 2500 AC Between Open Contacts V 10000 AC Terminal Torque (maximum) Table Nam) 7,1 (0,8) 7,1 (0,8) Environment Product certifications Standard version UL, CE UL, CE Performance device Operation % CC 2500 AC Degree of protection V 0,000 IP200 Version V 1000 AC Performante Maximum VI 10,000,000 IV, CE Product certifications Standard version UL, CE UL, CE Product certifications Standard version V 1000 AC Performante Maximum CC 2, 20,+55 Degree of protection V 1200 IP20 Version CC 2, 20,+55 Degree of protection VP20 Version CC 2, 20,+55 Degree of p		DC	W	1.7	1.7
Timing Characteristics A,B,C,D,E,F,G,H,I,J A,II A,II,J A,II,	Indication	LED		Green	Green
Functions Available (See page 5/3) A,B,C,D,E,F,G,H,I,J A,B,C,D,E,F,G,H,I,J A,B,C,D,E,F,G,H,I,J Time Scales 10 10 10 Time Ranges Available sec 110 110 Sec 110 110 110 Immin 110 110 110 Immin 110 110 110 Immin 0.11 0.11 0.11 Immin 0.11 0.11 0.11 Immin 110 110 110 Immin Immin 110 110 Immin Immin Immin 110 Immin Immin Immin Immin Immin Immin Immin Immin Imm	Timing Characteristics				
Time Scales 10 10 10 Time Ranges Available 0.11 0.11 0.11 Sec 110 110 110 min 110 110 110 Mechanical Setting % 5 5 Repeatability Constant Voltage and Temperature % 0.2 0.2 Reset Time Maximum ms 150 150 Trigger Pulse length Minimum ms 50 5 Performance Characteristics Electrical Life Operations @ Rated Current (Resistive) 100,000 100,000 Mechanical Life Unpowered V 2500 AC 2500 AC Dielectric strength Input to Contacts V 2500 AC 2500 AC Terminal Vire Capacity Input to Contacts V 100,000 100,000,000 Dielectric strength Input to Contacts V 2500 AC 2500 AC Terminal Vire Capacity Inbut to in lb (Nm) 7.1 [0.8] 7.1 [0.8] Environment	Functions Available	(See page 5/3)		A.B.C.D.E.F.G.H.I.J	A.B.C.D.E.F.G.H.I.J
Time Ranges Available 0.11 0.11 sec 110 110 min 110 110 min 110 110 0.11 0.11 0.11 min 110 110 0.11 0.11 0.11 min 110 110 0.11 0.11 0.11 day 110 110 1 0.11 0.11 day 110 110 Tolerance Mechanical Setting % Reset Time Maximum 0.2 0.2 Reset Time Maximum ms 150 Trigger Pulse length Minimum ms 50 Performance Characteristics Electrical Life Operations @ Rated Current [Resistive] 100,000 100,000,000 Dielectric strength Input to Contacts V 2500 AC 2500 AC Between Open Contacts V 1000 AC 10	Time Scales	[***]** 3** 7		10	10
sec 110 110 min 0.11 0.11 min 110 110 0.11 0.11 0.11 hr 110 110 1 0.11 0.11 hr 110 110 1 0.11 0.11 1 0.11 0.11 1 0.11 0.11 1 0.11 0.11 1 0.110 110 1 0.11 0.11 day 110 110 Trigger Pulse Length Maximum ms Trigger Pulse Length Minimum ms Mechanical Life Operations @ Rated Current [Resistive] 100,000 Mechanical Life Unpowered 10,000,000 100,000,000 Dielectric strength Input to Contacts V 2500 AC 2500 AC Terminal Wire Capacity AWG [mm2] 14 (2.1) 14 (2.1) Terminal	Time Ranaes Available			0.11	0.11
min 0.11 0.11 min 110 110 0.11 0.11 0.11 hr 110 110 1 0.11 0.11 hr 110 110 1 0.11 0.11 1 0.11 0.11 1 0.11 0.11 1 0.11 0.11 1 0.11 0.11 1 0.11 0.11 1 0.11 0.11 1 0.1 0.1 1 0.1 0.1 1 0.1 0.1 0.1 1 0.2 0.2 0.2 1 0.000 10.00 150 1 1 1.1 1.1 1 1 1.1 1.1 1 1 1.1 1.1 1 1 1.1 1.1	3		sec	110	110
min 110 110 hr 0.11 0.11 hr 110 110 1 0.11 0.11 day 110 110 Tolerance Mechanical Setting % 5 Repeatability Constant Voltage and Temperature % 0.2 0.2 Reset Time Maximum ms 150 150 Trigger Pulse Length Minimum ms 50 50 Performance Characteristics Electrical Life Operations @ Rated Current [Resistive] 100,000 100,000 Mechanical Life Unpowered 100,000 100,000 100,000 Dielectric strength Input to Contacts V 2500 AC 2500 AC Terminal Wire Capacity atWG (mm2) 14 (2.1) 14 (2.1) Terminal Torque (maximum) in lb (Nm) 7.1 (0.8) 7.1 (0.8) Product certifications Standard version UL, CE UL, CE Ambient air temperature Storage °C				0.11	0.11
$\begin{tabular}{ c c c c c c c c c c c c c c c c c c c$			min	110	110
$\begin{tabular}{ c c c c c c c } & hr & 110 & 110 \\ & 0.11 & 0.11 \\ & 0.11 & 0.11 \\ & 0.110 & 110 \\ \hline \\ $				0.11	0.11
Image: Constant Voltage and Setting 0.11 0.11 ToleranceMechanical Setting $\%$ 5 5 RepeatabilityConstant Voltage and Temperature $\%$ 0.2 0.2 Reset TimeMaximumms 150 150 Trigger Pulse LengthMinimumms 50 50 Performance CharacteristicsElectrical LifeOperations @ Rated Current (Resistive) $100,000$ $100,000$ Mechanical LifeUnpowered $10,000,000$ $10,000,000$ Dielectric strengthInput to ContactsV 2500 ACBetween Open ContactsV 1000 AC 1000 ACTerminal Vire CapacityAWG (mm2) 14 (2.1) 14 (2.1)Terminal Torque (maximum)in lb (Nm) 7.1 (0.8) 7.1 (0.8)EnvironmentV $200+70$ $30+70$ Product certificationsStandard versionUL, CEUL, CEAmbient air temperature around the deviceOperation $^{\circ}$ C $-20+55$ Degree of protectionIP 20IP 20IP 20Weightgrams 65 65			hr	110	110
day 110 110 Tolerance Mechanical Setting % 5 5 Repeatability Constant Voltage and Temperature % 0.2 0.2 Reset Time Maximum ms 150 150 Trigger Pulse Length Minimum ms 50 50 Performance Characteristics U 100,000 100,000 Reset Time Operations @ Rated Current (Resistive) 100,000 100,000 Mechanical Life Operations @ Rated Current (Resistive) 100,000 100,000,000 Dielectric strength Input to Contacts V 2500 AC 2500 AC Between Open Contacts V 1000 AC 1000 AC 1000 AC Terminal Wire Capacity AWG (mm2) 14 (2.1) 14 (2.1) 14 (2.1) Terminal Torque (maximum) in lb (Nm) 7.1 (0.8) 7.1 (0.8) 7.1 (0.8) Environment C -30+70 -30+70 -30+70 -30+70 Pegree of protection Operation °C -2				0.11	0.11
ToleranceMechanical Setting%'55RepeatabilityConstant Voltage and Temperature%0.20.2Reset TimeMaximumms150150Trigger Pulse LengthMinimumms5050Performance CharacteristicsElectrical LifeOperations @ Rated Current (Resistive)100,000100,000Mechanical LifeUnpowered100,000100,000Dielectric strengthInput to ContactsV2500 ACBetween Open ContactsV1000 AC1000 ACTerminal Vire CapacityAWG (mm2)14 (2.1)14 (2.1)Terminal Torque (maximum)in Ib (Nm)7.1 (0.8)7.1 (0.8)EnvironmentProduct certificationsStandard versionUL, CEUL, CEAmbient air temperature around the deviceOperation°C-30+70-30+70Degree of protectionIP 20IP 20IP 20IP 20IP 20WeightStandardgrams656565			day	110	110
RepeatabilityConstant Voltage and Temperature%0.20.2Reset TimeMaximumms150150Trigger Pulse LengthMinimumms5050Performance CharacteristicsElectrical LifeOperations @ Rated Current (Resistive)100,000100,000Mechanical LifeUnpowered10,000,00010,000,000Dielectric strengthInput to ContactsV2500 ACBetween Open ContactsV1000 AC1000 ACTerminal Vire CapacityAWG (mm2)14 (2.1)14 (2.1)Terminal Torque (maximum)in Ib (Nm)7.1 (0.8)7.1 (0.8)Froduct certificationsStandard versionUL, CEUL, CEUL, CEAmbient air temperatureStorage°C-30+70around the deviceOperation°C-20+55-20+55Degree of protectionIP 20IP 20IP 20Weightgrams6565	Tolerance	Mechanical Setting	%	5	5
Reset TimeMaximumms150150Trigger Pulse LengthMinimumms5050Performance CharacteristicsElectrical LifeOperations @ Rated Current (Resistive)100,000100,000Mechanical LifeUnpowered10,000,00010,000,000Dielectric strengthInput to ContactsV2500 ACBetween Open ContactsV1000 AC1000 ACTerminal Wire CapacityAWG (mm2)14 (2.1)14 (2.1)Terminal Torque (maximum)in Ib (Nm)7.1 (0.8)7.1 (0.8)EnvironmentProduct certificationsStandard versionUL, CEUL, CEAmbient air temperature around the deviceOperation°C-30+70Degree of protectionIP 20IP 20IP 20Weightgrams6565	Repeatability	Constant Voltage and Temperature	%	0.2	0.2
Trigger Pulse LengthMinimumms5050Performance CharacteristicsElectrical LifeOperations @ Rated Current [Resistive]100,000100,000Mechanical LifeUnpowered10,000,00010,000,000Dielectric strengthInput to ContactsV2500 AC2500 ACBetween Open ContactsV1000 AC1000 AC1000 ACTerminal Wire CapacityAWG (mm2)114 [2.1)114 [2.1]Terminal Torque (maximum)in lb (Nm)7.1 (0.8)7.1 (0.8)EnvironmentProduct certificationsStandard versionUL, CEUL, CEAmbient air temperature around the deviceStorage°C-30+70-30+70Perge of protection°C-20+55-20+55-20+55Degree of protectionIP 20IP 20IP 20Weightgrams656565	Reset Time	Maximum	ms	150	150
Performance Characteristics Electrical Life Operations @ Rated Current (Resistive) Mechanical Life Unpowered Input to Contacts V Between Open Contacts V Between Open Contacts V Input to Contacts V Input to Contacts V Between Open Contacts V Input to Contacts V <td>Trigger Pulse Length</td> <td>Minimum</td> <td>ms</td> <td>50</td> <td>50</td>	Trigger Pulse Length	Minimum	ms	50	50
Performance Characteristics Electrical Life Operations @ Rated Current (Resistive) 100,000 100,000 Mechanical Life Unpowered 10,000,000 10,000,000 Dielectric strength Input to Contacts V 2500 AC 2500 AC Between Open Contacts V 1000 AC 1000 AC 1000 AC Terminal Wire Capacity AWG (mm2) 14 (2.1) 14 (2.1) Terminal Torque (maximum) in lb (Nm) 7.1 (0.8) 7.1 (0.8) Environment UL, CE UL, CE UL, CE Ambient air temperature Storage °C -30+70 -30+70 around the device Operation °C -20+55 -20+55 Degree of protection IP 20 IP 20 IP 20 Weight grams 65 65 65					
Electrical Life Operations @ Rated Current (Resistive) 100,000 100,000 Mechanical Life Unpowered 10,000,000 10,000,000 Dielectric strength Input to Contacts V 2500 AC 2500 AC Between Open Contacts V 1000 AC 1000 AC Terminal Wire Capacity AWG (mm2) 14 (2.1) 14 (2.1) Terminal Torque (maximum) in lb (Nm) 7.1 (0.8) 7.1 (0.8) Environment Product certifications Standard version UL, CE UL, CE Ambient air temperature Storage °C -30+70 -30+70 around the device Operation °C -20+55 -20+55 Degree of protection IP 20 IP 20 IP 20 Weight grams 65 65	Performance Characteristics				
Mechanical LifeUnpowered10,000,00010,000,000Dielectric strengthInput to ContactsV2500 AC2500 ACBetween Open ContactsV1000 AC1000 AC1000 ACTerminal Wire CapacityAWG (mm2)14 (2.1)14 (2.1)Terminal Torque (maximum)in lb (Nm)7.1 (0.8)7.1 (0.8)EnvironmentProduct certificationsStandard versionUL, CEUL, CEAmbient air temperatureStorage°C-30+70-30+70around the deviceOperation°C-20+55-20+55Degree of protectionIP 20IP 20IP 20Weightgrams656565	Electrical Lite	Operations @ Rated Current (Resistive)		100,000	100,000
Dielectric strengthInput to ContactsV2500 AC2500 ACBetween Open ContactsV1000 AC1000 ACTerminal Wire CapacityAWG (mm2)14 (2.1)14 (2.1)Terminal Torque (maximum)in lb (Nm)7.1 (0.8)7.1 (0.8)EnvironmentProduct certificationsStandard versionUL, CEAmbient air temperatureStorage°C-30+70around the deviceOperation°C-20+55-20+55Degree of protectionIP 20IP 20IP 20Weightgrams656565	Mechanical Life	Unpowered		10,000,000	10,000,000
Between Open Contacts V 1000 AC 1000 AC Terminal Wire Capacity AWG (mm2) 14 (2.1) 14 (2.1) Terminal Torque (maximum) in lb (Nm) 7.1 (0.8) 7.1 (0.8) Environment UL, CE UL, CE Product certifications Standard version UL, CE -30+70 Ambient air temperature Storage °C -30+70 -30+70 around the device Operation °C -20+55 -20+55 Degree of protection IP 20 IP 20 Weight grams 65 65	Dielectric strength	Input to Contacts	V	2500 AC	2500 AC
Iterminal Wire Capacity AWG (mm2) 14 (2.1) Terminal Torque (maximum) in lb (Nm) 7.1 (0.8) Environment VIL, CE UL, CE Product certifications Standard version UL, CE Ambient air temperature Storage °C -30+70 around the device Operation °C -20+55 Degree of protection IP 20 IP 20 Weight grams 65 65		Between Open Contacts	V	1000 AC	1000 AC
In Ib (Nm) 7.1 (0.8) Environment Product certifications Standard version Ambient air temperature Storage around the device Operation Degree of protection IP 20 Weight grams	Ierminal Wire Capacity		AWG (mm2)	14 (2.1)	14 (2.1)
EnvironmentUL, CEProduct certificationsStandard versionUL, CEAmbient air temperatureStorage°C-30+70around the deviceOperation°C-20+55Degree of protectionIP 20IP 20Weightgrams6565	Terminal Torque (maximum)		in lb (Nm)	7.1 (0.8)	7.1 (0.8)
Product certificationsStandard versionUL, CEUL, CEAmbient air temperature around the deviceStorage°C-30+70-30+70Degree of protection°C-20+55-20+55-20+55WeightIP 20IP 20Storage6565	Environment				
Ambient air temperature around the deviceStorage°C-30+70-30+70Degree of protection°C-20+55-20+55-20+55WeightIP 20IP 20IP 20	Product certifications	Standard version		UL, CE	UL, CE
around the device Operation °C -20+55 -20+55 Degree of protection IP 20 IP 20 IP 20 Weight grams 65 65	Ambient air temperature	Storage	°C	-30+70	-30+70
Degree of protection IP 20 IP 20 Weight grams 65 65	around the device	Operation	°C	-20+55	-20+55
Weight grams 65 65	Degree of protection			IP 20	IP 20
	Weight		grams	65	65





Optional Panel Adapter (16-788C1) See Section 3 p.18

Standard Part Numbers

BOLD-FACED PART NUMBERS ARE NORMALLY STOCKED					
Part Number	Input Voltage	Timing Range	Functions Available	Contact Configuration	Rated Load Current
821TD10H-UNI	12240 VAC/VDC	0.1s10d	A,B,C,D,E,F,G,H,I,J	SPDT	15 Amps
822TD10H-UNI	12240 VAC/VDC	0.1s10d	A,B,C,D,E,F,G,H,I,J	DPDT	15 Amps

FUNCTION DEFINITIONS
See Section 5 p.3

Part Number Builder

Series	Relay Style	Number of Functions	-	Input Voltage
821 = SPDT	TD - Time Delay	10H = 10 Functions		UNI = 12240 VAC/VDC
822 = DPDT				



SECTION 5



ООО "ЛайфЭлектроникс"

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru

www.lifeelectronics.ru