



**ATTENTION**  
OBSERVE PRECAUTIONS  
FOR HANDLING  
ELECTROSTATIC  
DISCHARGE  
SENSITIVE  
DEVICES

Part Number: APTF1616LSEKJ3ZGKQBC

Hyper Red  
Green  
Blue




### Features

- 1.6mmX1.6mm SMD LED, 0.7mm thickness.
- Low power consumption.
- Can produce any color in visible spectrum, including white light.
- Package : 2000pcs / reel.
- Moisture sensitivity level : level 3.
- Low current IF=2mA operating.
- RoHS compliant.

### Descriptions

- The Hyper Red device is based on light emitting diode chip made from AlGaInP.
- The Green source color devices are made with InGaN on Sapphire Light Emitting Diode.
- The Blue source color devices are made with InGaN Light Emitting Diode.
- Electrostatic discharge and power surge could damage the LEDs.
- It is recommended to use a wrist band or anti-electrostatic glove when handling the LEDs.
- All devices, equipments and machineries must be electrically grounded.

### Package Dimensions



#### Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.2(0.008)$  unless otherwise noted.
3. The specifications, characteristics and technical data described in the datasheet are subject to change without prior notice.
4. The device has a single mounting surface. The device must be mounted according to the specifications.



## Selection Guide

| Part No.             | Emitting Color (Material) | Lens Type   | Iv (mcd) [2]<br>@ 2mA |      | Viewing<br>Angle [1] |
|----------------------|---------------------------|-------------|-----------------------|------|----------------------|
|                      |                           |             | Min.                  | Typ. | 2θ1/2                |
| APTF1616LSEKJ3ZGKQBC | Hyper Red (AlGaInP)       | Water Clear | 20                    | 40   | 120°                 |
|                      | Green (InGaN)             |             | 20                    | 50   |                      |
|                      | Blue (InGaN)              |             | 6                     | 14   |                      |

### Notes:

1. θ1/2 is the angle from optical centerline where the luminous intensity is 1/2 of the optical peak value.
2. Luminous intensity / Luminous Flux: +/-15%.
3. Luminous intensity value is traceable to the CIE127-2007 compliant national standards.

## Electrical / Optical Characteristics at TA=25°C

| Symbol | Parameter                | Emitting Color             | Typ.                | Max.              | Units | Test Conditions |
|--------|--------------------------|----------------------------|---------------------|-------------------|-------|-----------------|
| λpeak  | Peak Wavelength          | Hyper Red<br>Green<br>Blue | 640<br>515<br>460   |                   | nm    | If=2mA          |
| λD [1] | Dominant Wavelength      | Hyper Red<br>Green<br>Blue | 625<br>525<br>465   |                   | nm    | If=2mA          |
| Δλ1/2  | Spectral Line Half-width | Hyper Red<br>Green<br>Blue | 20<br>35<br>25      |                   | nm    | If=2mA          |
| C      | Capacitance              | Hyper Red<br>Green<br>Blue | 27<br>45<br>100     |                   | pF    | Vf=0V;f=1MHz    |
| Vf [2] | Forward Voltage          | Hyper Red<br>Green<br>Blue | 1.8<br>2.65<br>2.65 | 2.1<br>3.1<br>3.1 | V     | If=2mA          |
| IR     | Reverse Current          | Hyper Red<br>Green<br>Blue |                     | 10<br>50<br>50    | uA    | VR=5V           |

### Notes:


1. Wavelength: +/-1nm.
2. Forward Voltage: +/-0.1V.
3. Wavelength value is traceable to the CIE127-2007 compliant national standards.
4. Excess driving current and/or operating temperature higher than recommended conditions may result in severe light degradation or premature failure.

## Absolute Maximum Ratings at TA=25°C






| Parameter                               | Hyper Red      | Green | Blue | Units |
|-----------------------------------------|----------------|-------|------|-------|
| Power dissipation                       | 63             | 77.5  | 93   | mW    |
| DC Forward Current                      | 30             | 25    | 30   | mA    |
| Peak Forward Current [1]                | 150            | 150   | 150  | mA    |
| Electrostatic Discharge Threshold (HBM) | 3000           | 450   | 250  | V     |
| Reverse Voltage                         | 5              |       |      | V     |
| Operating Temperature                   | -40°C To +85°C |       |      |       |
| Storage Temperature                     | -40°C To +85°C |       |      |       |

### Notes:






1. 1/10 Duty Cycle, 0.1ms Pulse Width.








## APTF1616LSEKJ3ZGKQBC Hyper Red



## Green




## Blue



## APTF1616LSEKJ3ZGKQBC

Reflow soldering is recommended and the soldering profile is shown below.  
Other soldering methods are not recommended as they might cause damage to the product.


Reflow Soldering Profile For Lead-free SMT Process.




### NOTES:

1. We recommend the reflow temperature 245°C(+/-5°C). The maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.


### Recommended Soldering Pattern (Units : mm; Tolerance: $\pm 0.1$ )



### Reel Dimension




### Tape Dimensions (Units : mm)



## PACKING & LABEL SPECIFICATIONS

APTF1616LSEKJ3ZGKQBC



|                                                                                     |      |                              |
|-------------------------------------------------------------------------------------|------|------------------------------|
| <b>Kingbright</b>                                                                   |      |                              |
| P/NO: APTF1616xxx                                                                   |      |                              |
| QTY: 2,000 pcs                                                                      | Q.C. | Q.C.<br>XX-XX-XXXX<br>PASSED |
| S/N: XXXX                                                                           |      |                              |
| CODE: XXX                                                                           |      |                              |
| LOT NO:                                                                             |      |                              |
|  |      |                              |
| RoHS Compliant                                                                      |      |                              |

### Terms and conditions for the usage of this document

1. The information included in this document reflects representative usage scenarios and is intended for technical reference only.
2. The part number, type, and specifications mentioned in this document are subject to future change and improvement without notice. Before production usage customer should refer to the latest datasheet for the updated specifications.
3. When using the products referenced in this document, please make sure the product is being operated within the environmental and electrical limits specified in the datasheet. If customer usage exceeds the specified limits, Kingbright will not be responsible for any subsequent issues.
4. The information in this document applies to typical usage in consumer electronics applications. If customer's application has special reliability requirements or have life-threatening liabilities, such as automotive or medical usage, please consult with Kingbright representative for further assistance.
5. The contents and information of this document may not be reproduced or re-transmitted without permission by Kingbright.
6. All design applications should refer to Kingbright application notes available at <http://www.KingbrightUSA.com/ApplicationNotes>

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)