

dsPIC30F Soft Modem Library

Summary

The Microchip data modem library is composed of ITU-T compliant algorithms for V.21, V.22, V.22bis, V.23, V.32 and V.32bis modem recommendations. Bell standard 103 is also included in this library.

V.21, V.23 and Bell 103 are Frequency Shift Keying (FSK) modems. V.32, V.32bis and V.22bis are Quadrature Amplitude Modulated (QAM) modems. V.22 is a Quadrature Phase Shift Keyed (QPSK) modem. V.21, V.22, V.22bis, V.32 and V.32bis are all 2-wire, Full Duplex modems. V.23 is Full-Duplex when it operates with a 75 bps backwards channel.

V.22bis includes fallback to V.22, V.23 and V.21 standards. V.32bis optionally falls back to V.22bis, V.22, V.23 and V.21 standards.

Typical Applications

The dsPIC Soft Modem is well suited for small transaction orientated based applications such as, but not limited to:

- POS Terminals
- Set Top Boxes
- Drop Boxes
- Fire Panels
- Internet-enabled Home Security Systems
- Internet-connected Power, Gas and Water Meters
- Internet-connected Vending Machines
- Smart Appliances
- Industrial Monitoring

Contents

The data modem library is provided in two basic software packages:

- V.22bis/V.22, which is offered free with full source code, includes the following components:
 - V.22bis/V.22, V.23, V.21/Bell 103, V.42, DP and V.42 API, AT Command Set
- V.32bis/V.32, which is offered in object code, includes the following components:
 - V.32bis/V.32, V.22bis/V.22, V.23, V.21/Bell 103, V.42, DP and V.42 API, AT Command Set

The library currently supports single channel data-pump implementations.

Both libraries are supported with fallback data pump modulations down to V.21. Each data modem library is provided with a respective library archive containing all the data pump object code modules required to link to the user's application. Hardware component drivers, such as UART and Data Converter Interface for DAA/AFE I/O are provided in assembly source code for linking with the user's application.

ITU-T Recommendation V.42 is provided with each library. V.42 contains a High Level Data Link Control (HDLC) protocol referred to as Link Access Procedure for Modems (LAPM) and defines error-correcting protocols for modems.

All data pump modulations are developed in ASM30 assembly code yielding optimal code size and execution time. The AT, V.42 and Data Pump APIs are based on C30 C language.

Electronic documentation accompanies the modem library to help you become familiar with and implement the library functions. A comprehensive *Soft Modem User's Guide* describes the required APIs for the AT, V.42 and Data Pump layers.

Features and Performance of Data Modems

| Algorithm ⁽¹⁾ | Performance | | | Program Memory ⁽²⁾ (Kbytes) | Data Memory ⁽²⁾ (Kbytes) | MIPS |
|--------------------------|---------------------|---------------------|--------------|---|--|------|
| | Data Rate (Kbps) | Half/Full Duplex | Data Mod. | | | |
| V.21/Bell 103 | 0.3 | Full | FSK | 13 | 1.0 | 4.5 |
| V.22/V.22bis | 1.2 | Full | PSK/QAM | 22 | 1.7 | 7 |
| | 2.4 | | | | | |
| V.23 | 1.2 | Half | FSK | 15 | 1.0 | 4.5 |
| | 0.6 | | | | | |
| V.32 | 9.6 | Full | QAM/TCM | 31 | 3.2 | 12 |
| | 4.8 | | | | | |
| V.32bis | 14.4 | Full | QAM/TCM | 36 | 3.6 | 15 |
| | 12 | | | | | |
| | 9.6 | | | | | |
| | 7.2 | | | | | |
| | 4.8 | | | | | |
| V.42 | | n/a | | 14 | 2.0 | 1.5 |
| DP + V.42 API | | n/a | | 7 | 1.2 | - |
| AT Command Set | | n/a | | 8 | 0.15 | - |

Notes:

1. Data pump modules, V.21, V.22, V.22bis, V.23, V.32, V.32bis and Bell 103 are implemented in Assembly language. V.42, Data Pump and AT Command APIs are implemented in C language.
2. The program/data memory usage for the V-series data pumps is NOT cumulative, due to the sharing of components internally.
3. Memory size does not account for application which combines data pump, V.42 and AT commands (if required).
4. V.21/Bell 103 and V.23 data pumps do not require V.42.



MICROCHIP

Development Systems

Microchip Technology Incorporated

Technical Notes

V.21 operates at 300 symbols per second, at mean frequencies of 1080+/-100 Hz and 1750+/-100 Hz. V.23 operates at mean frequencies of 1500+/-200 Hz for the 600bps forward channel and 1700+/-400 Hz for the 1200 bps forward channel. The V.23, 75 bps, backwards channel has a mean frequency of 420+/-30 Hz.

V.32 and V.32bis data modems operate at 2400 symbols per second on a carrier frequency of 1800 Hz, in both directions. Both V.32 and V.32bis implement trellis coding modulation (TCM) for all data rates, except 4800 bps. V.32 also includes uncoded 9600 bps.

Host System Requirements

- PC-compatible system with an Intel Pentium® class or higher processor, or equivalent
- A minimum of 16 MB RAM
- A minimum of 40 MB available hard drive space
- Microsoft Windows® 98, Windows 2000 or Windows XP

Part Numbers and Ordering Information:

dsPIC30F Soft Modem Library

| Part Number | Description | Availability |
|---------------|---|--------------|
| SW300002 | ITU-T compliant V.22bis Data-Modem Library (Free download from Microchip web site) | Now |
| SW300003-EVAL | ITU-T compliant V.32bis Data-Modem Library Software License (Evaluation Only) ⁽¹⁾ | Now |
| SW300003 | ITU-T compliant V.32bis Data-Modem Library Software License (Up to 5K units) ⁽²⁾ | Now |
| SW300004 | ITU-T compliant V.32bis Data-Modem Library Software License (5K+ to 25K units) ⁽²⁾ | Now |
| SW300005 | ITU-T compliant V.32bis Data-Modem Library Software License (25K+ to 100K units) ⁽²⁾ | Now |

Note 1: The evaluation version offers the same functions and features as the other versions. The evaluation period is one year.

2: Quantities are per project, payable as a one-time license fee based on estimated lifetime volume for products resulting from the project. Please consult the factory for quantities above 100K.

dsPIC® Development Tools from Microchip

| | |
|---|---------------------|
| MPLAB® IDE | Free |
| MPLAB® Visual Device Initializer (included in MPLAB® IDE) | |
| MPLAB® C30 C Compiler | SW006012 |
| MPLAB® ICD 2 In-Circuit Debugger/Programmer | DV164005, DV164007 |
| MPLAB® ICE 4000 | ICE4000 |
| MPLAB® PM3 Universal Device Programmer | DV007004 |
| dsPIC30F Math Library (included in download of MPLAB® C30 C Compiler) | Free |
| dsPIC30F DSP Library | Free |
| dsPIC30F Peripheral Library | Free |
| dsPICworks™ Data Analysis and DSP Software | Free |
| dsPIC® Digital Filter Design | SW300001 |
| dsPIC30F Soft-Modem Library | SW300002/3/4/5 |
| dsPIC® Speech Recognition Library | SW300010/11/12 |
| dsPIC® Symmetric Key Embedded Encryption Library | SW300050 |
| dsPIC® Asymmetric Key Embedded Encryption Library | SW300055 |
| dsPIC30F Acoustic Echo Cancellation Library | SW300060 |
| dsPIC30F Noise Suppression Library | SW300040 |
| CMX-RTX™ for dsPIC30F | SW300031 |
| CMX-Tiny+™ for dsPIC30F | SW300032 |
| CMX-Scheduler™ for dsPIC® Devices | Free at www.cmx.com |
| dsPICDEM™ Starter Demonstration Board | DM300016 |
| dsPICDEM™ 28-pin Starter Demonstration Board | DM300017 |
| dsPICDEM™ 1.1 General Purpose Development Board | DM300014 |
| dsPICDEM™ MC1 Motor Control Development System | DM300020 |
| dsPICDEM.net™ 1 Connectivity Development Boards | DM300004-1 |
| dsPICDEM.net™ 2 Connectivity Development Boards | DM300004-2 |

Americas: Atlanta (770) 640-0034 • Boston (978) 692-3848 • Chicago (630) 285-0071 • Dallas (972) 818-7423 • Detroit (248) 538-2250 • Kokomo (765) 864-8360 • Los Angeles (949) 462-9523 • Phoenix (480) 792-7200 • San Jose (650) 215-1444 • Toronto (905) 673-0699 • **Asia/Pacific:** Australia-Sydney 61-2-9868-6733 • China-Beijing 86-10-8528-2100 • China-Chengdu 86-28-8676-6200 • China-Fuzhou 86-591-8750-3506 • China-Hong Kong SAR 852-2401-1200 • China-Qingdao 86-532-502-7355 • China-Shanghai 86-21-5407-5533 • China-Shenyang 86-24-2334-2829 • China-Shenzhen 86-755-8203-2660 • China-Shunde 86-757-2839-5507 • India-Bangalore 91-80-2229-0061 • Japan-Kanagawa 81-45-471-6166 • Korea-Seoul 82-2-554-7200 • Singapore 65-6334-8870 • Taiwan-Taipei 886-2-2500-6610 • Taiwan-Kaohsiung 886-7-536-4818 • Taiwan-Hsinchu 886-3-572-9526 • **Europe:** Austria-Weis 43-7242-2244-399 • Denmark-Ballerup 45-4420-9895 • France-Massy 33-1-69-53-63-20 • Germany-Ismaning 49-89-627-144-0 • Italy-Milan 39-0331-742611 • Netherlands-Drunen 31-416-690399 • England-Berkshire 44-118-921-5869 (As of 11/04)

Microchip Technology Inc. • 2355 W. Chandler Blvd. • Chandler, AZ 85224-6199 USA • (480) 792-7200 • FAX (480) 792-7277

The Microchip name and logo, the Microchip logo, Accuron, dsPIC, KeELoQ, microID, MPLAB, PIC, PICmicro, PICSTART, PRO MATE, PowerSmart, rPIC, and SmartShunt are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. AmpLab, FilterLab, MXDEV, MXLAB, PICMASTER, SEEVAL, SmartSensor and The Embedded Control Solutions Company are registered trademarks of Microchip Technology Incorporated in the U.S.A. Analog-for-the-Digital Age, Application Maestro, dsPICDEM, dsPICDEM.net, dsPICworks, ECAN, ECONOMONITOR, FanSense, FlexROM, fuzzyLAB, In-Circuit Serial Programming, ICSP, ICEPIC, Migratable Memory, MPASM, MPLIB, MPLINK, MPSIM, PICKIT, PICDEM, PICDEM.net, PICLAB, PICtail, PowerCal, PowerInfo, PowerMate, PowerTool, rLAB, rPICDEM, Select Mode, Smart Serial, SmartTel and Total Endurance are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries. SQTP is a service mark of Microchip Technology Incorporated in the U.S.A. All other trademarks mentioned herein are property of their respective companies.

© 2005, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved. 1/05

DS70126C



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru