



## Features

- Single Turn / Cermet / Industrial / Sealed
- Available on tape and reel
- Available with a knob for finger adjust
- Available with extended shaft
- Available with cross-slot rotor
- Top and side adjust types (F, P, H, W, X most popular)

- RoHS compliant\* version available
- For trimmer applications/processing guidelines, [click here](#)

## 3386 - 3/8" Square Trimpot® Trimming Potentiometer

### Electrical Characteristics

|                                 |                      |
|---------------------------------|----------------------|
| Standard Resistance Range       | 10 ohms to 2 megohms |
| (see standard resistance table) |                      |
| Resistance Tolerance            | ±10 % std.           |
| (tighter tolerance available)   |                      |
| Absolute Minimum Resistance     | 2 ohms max.          |
| Contact Resistance Variation    | 2 % or 3 ohms max.   |
| (whichever is greater)          |                      |
| Adjustability                   |                      |
| Voltage                         | ±0.05 %              |
| Resistance                      | ±0.15 %              |
| Resolution                      | Infinite             |
| Insulation Resistance           | 500 vdc.             |
| 1,000 megohms min.              |                      |
| Dielectric Strength             |                      |
| Sea Level                       | 900 vac              |
| 70,000 Feet                     | 350 vac              |
| Adjustment Angle                | 280 ° nom.           |

### Environmental Characteristics

|                               |                              |
|-------------------------------|------------------------------|
| Power Rating (300 volts max.) |                              |
| 85 °C                         | 0.5 watt                     |
| 125 °C                        | 0 watt                       |
| Temperature Range             | -55 °C to +125 °C            |
| Temperature Coefficient       | ±100 ppm/°C                  |
| Seal Test                     | 85 °C Fluorinert†            |
| Humidity                      | MIL-STD-202 Method 103       |
| 96 hours                      |                              |
| (2 % ΔTR, 10 Megohms min.)    |                              |
| Vibration                     | 30 G (1 % ΔTR; 1 % ΔVR)      |
| Shock                         | 100 G (1 % ΔTR; 1 % ΔVR)     |
| Load Life                     | 1,000 hours 0.5 watt @ 70 °C |
| (3 % ΔTR; 1 % or 1 ohm,       |                              |
| whichever is greater, CRV)    |                              |
| Rotational Life               | 200 cycles                   |
| (4 % ΔTR; 1 % or 1 ohm,       |                              |
| whichever is greater, CRV)    |                              |

### Physical Characteristics





|                             |                        |
|-----------------------------|------------------------|
| Mechanical Angle            | 310 ° nom.             |
| Torque                      | 5.0 oz-in. max.        |
| Stop Strength               | 15.0 oz-in. min.       |
| Terminals                   | Solderable pins        |
| Weight                      | 0.03 oz.               |
| Marking                     | Manufacturer's         |
| trademark, resistance code, |                        |
| wiring diagram, date code,  |                        |
| manufacturer's model        |                        |
| number and style            |                        |
| Flammability                | U.L. 94V-0             |
| Standard Packaging          | 50 pcs. per tube       |
| Wiper                       | 50 % (Actual TR) ±10 % |
| Adjustment Tool             | H-90                   |

### Product Dimensions

#### Common Dimensions Side Adjust Models B,C,J,X



#### Common Dimensions Side Adjust Models H,S,W



DIMENSIONS:  $\frac{\text{MM}}{(\text{INCHES})}$

TOLERANCES: ±  $\frac{0.25}{(.010)}$  EXCEPT WHERE NOTED

### Standard Resistance Table

| Resistance (Ohms) | Resistance Code |
|-------------------|-----------------|
| 10                | 100             |
| 20                | 200             |
| 50                | 500             |
| 100               | 101             |
| 200               | 201             |
| 500               | 501             |
| 1,000             | 102             |
| 2,000             | 202             |
| 5,000             | 502             |
| 10,000            | 103             |
| 20,000            | 203             |
| 25,000            | 253             |
| 50,000            | 503             |
| 100,000           | 104             |
| 200,000           | 204             |
| 250,000           | 254             |
| 500,000           | 504             |
| 1,000,000         | 105             |
| 2,000,000         | 205             |

Popular distribution resistance values listed in boldface. Special resistances available.

### How To Order

|                                                |      |
|------------------------------------------------|------|
| Model                                          | 3386 |
| Style                                          | P    |
| Standard or Modified                           | -1   |
| Product Indicator                              | -103 |
| -1 = Standard Product                          |      |
| -EY5 = Extended Shaft                          |      |
| Resistance Code                                | T    |
| Optional Suffix Letter                         | LF   |
| T = Knob**                                     |      |
| Packaging Designator                           |      |
| Blank = Tube (Standard)                        |      |
| R = Tape & Reel (W and U Pin Styles Only)      |      |
| A = Ammo Pack (W and U Pin Styles Only)        |      |
| Terminations                                   |      |
| LF = 100 % Tin-plated (RoHS compliant)         |      |
| Blank = 90 % Tin / 10 % Lead-plated (Standard) |      |

\*\*Knob option is available only in standard tube packaging.  
Consult factory for other available options.

\*RoHS Directive 2002/95/EC Jan 27, 2003 including Annex.  
†"Fluorinert" is a registered trademark of 3M Co.

Specifications are subject to change without notice.





Customers should verify actual device performance in their specific applications.

# 3386 - 3/8" Square Trimpot® Trimming Potentiometer


**BOURNS®**

## Product Dimensions



### Common Dimensions Top Adjust Models F,G,K,P,R,U,V,Y




### Common Dimensions Top Adjust Models M,T



### 3386H-EY5 3386X-EY5 – SHOWN



The Model 3386 is available with a knob for finger adjustment. Add suffix letter "T" to order code for F, P and X terminal styles.



DIMENSIONS:  $\frac{\text{MM}}{(\text{INCHES})}$   
 TOLERANCES:  $\pm \frac{0.25}{(.010)}$  EXCEPT WHERE NOTED

Specifications are subject to change without notice.  
 Customers should verify actual device performance in their specific applications.

# 3386 - 3/8 " Square Trimpot® Trimming Potentiometer

**BOURNS®**

## Packaging Specifications

### SIDE ADJUST 3386W-1



### TOP ADJUST 3386U-1



Meets EIA Specification 468.

DIMENSIONS:  $\frac{MM}{(INCHES)}$

REV. 10/11

"Trimpot" is a registered trademark of Bourns, Inc.  
Specifications are subject to change without notice.  
Customers should verify actual device performance in their specific applications.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)