

RJ45 10/100/1000 Base-TX Tab down 1x4 Jack with Magnetic Module

ARJ14A

RoHS
Compliant



59.12 x 13.60 x 21.50 mm /
58.40 x 11.50 x 17.60 mm

FEATURES:

- Tab down
- Available with or without LED
- Suitable CAT 5 & 6 cable and UTP
- Comply IEEE 802.3ab
- LAN Magnetic with RJ45
- Suitable for RoHS compliant reflow

APPLICATIONS:

- 10, 100 and 1000 Base-T LAN
- NIC, LoM and PC

STANDARD SPECIFICATIONS at 25°C

Operating temperature range: 0°C to +70°C **Storage temperature range: -40°C to +85°C**

Part Number	Ratio ± 5%		Tab Option	EMI Fingers (see Mechanical)	LEDs L/R	Insertion Loss (dB typ) 0.3- 100 MHz	Return Loss (dB typ @100Ω±15%)		
	TX	RX					1- 10 MHz	30 MHz	60-80 MHz
ARJ14A-M□SA-MU2	1CT:1CT	1CT:1CT	DOWN	Yes/No	-	-1.2	-18	-16	-12
ARJ14A-M□SB-MU2	1CT:1CT	1CT:1CT	DOWN	Yes/No	-	-1.2	-18	-16	-12
ARJ14A-M□SC-MU2	1CT:1CT	1CT:1CT	DOWN	Yes/No	-	-1.2	-18	-16	-12
ARJ14A-M□SD-A-B-ΔMU2	1CT:1CT	1CT:1CT	DOWN	Yes	G/Y	-1.2	-18	-16	-12
ARJ14A-M□SD-MU2	1CT:1CT	1CT:1CT	DOWN	Yes/No	-	-1.2	-18	-16	-12

Part Number	Crosstalk (dB TYP)			Common Mode Rejection (dB TYP)		Hipot (Vrms)
	1 - 10 MHz	30 - 60 MHz	60 - 100 MHz	1 - 50 MHz	50 - 130 MHz	
ARJ14A-M□SA-MU2	-40	-35	-30	-30	-20	1500
ARJ14A-M□SB-MU2	-30	-30	-30	-30	-20	1500
ARJ14A-M□SC-MU2	-40	-35	-30	-30	-20	1500
ARJ14A-M□SD-A-B-ΔMU2	-40	-35	-30	-30	-20	1500
ARJ14A-M□SD-MU2	-40	-35	-30	-30	-20	1500

□: Mechanical option: E, F or I for non- LED; A or B for LED.

Δ: LED polarity option E or F


Contact Abracon for more custom configurations. See options to build a custom configuration.

OPTIONS AND PART IDENTIFICATION

ARJ14A - □ □ - □ - □ - □ □ □ □

Mechanical	Schematic	Left LED color (e.g. B for Yellow, AB for Green-Yellow)	Right LED color (e.g. B for Yellow, AB for Green-Yellow)	LED polarity	Turns Ratio (Tx)	Turns Ratio (Rx)	Gold plating
MA ~ MI (Please see mechanical section)	SA ~ SZ (Please see schematic section)	Blank: No LED A: Green B: Yellow C: Amber D: Orange	Blank: No LED A: Green B: Yellow C: Amber D: Orange	Blank: No LED E ~ H (Please see 7.0 LED polarity section)	K: 1CT:1.41 L: 1CT:1 M: 1CT:1CT N: 1.414:1CT O: 1CT:1.41CT P: 1:2CT Q: 1:1.414CT R: 1CT:2.5	S: 1CT:1.41 T: 1CT:1 U: 1CT:1CT V: 1.414:1CT W: 1CT:1.41CT X: 1:2CT Y: 1:1.414CT Z: 1CT:2.5	1: 3u “ 2: 6u “ 3: 15u “ 4: 30u “ 5: 50u “

ABRACON IS
ISO 9001:2008
CERTIFIED



ABRACON
CORPORATION


Visit www.abracon.com for Terms & Conditions of Sale
30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Revised: 08.04.11


**RoHS
Compliant**

MECHANICAL DIMENSIONS

Figure 1: Mechanical drawing of the LED module. The drawing shows a top view and a side view. The top view indicates a total length of 59.12 and a central section length of 41.91. It shows four LED units with pins labeled 1 and 8. Dimensions for the LED units are given as @1.27x7=8.89. The side view shows a height of 13.60, a width of 21.50, and a mounting hole diameter of 3.30±0.51. Other dimensions include 3.05, 10.90, 2.54±0.20, and 8.89±0.20. Labels include 'Left LED', 'Right LED', and 'PRE-SOLDERING'.



The drawing shows the mechanical specifications of the LED module. The top view (left) indicates an overall width of 59.12 and a central section width of 41.91. It shows four LED units, each with 8 pins, and labels for 'Left LED' and 'Right LED'. The pin pitch is specified as $@1.27 \times 7 = 8.89$. The side view (right) shows a height of 13.60, a mounting tab width of 21.50, and a mounting hole diameter of 3.30 ± 0.51 . The distance from the mounting hole to the LED pins is 3.05, and the distance from the mounting hole to the next pin is 2.54 ± 0.20 . The total distance from the mounting hole to the end of the pin array is 8.89 ± 0.20 . The distance from the mounting hole to the next LED unit is 10.90.



**RoHS
Compliant**

MECHANICAL DIMENSIONS

Technical drawings of the LED module showing dimensions and components.

Top View (Left): Overall length 59.12. LED pitch @1.27x9=11.43. LED height 13.60. Labels: Left LED, Right LED.


Top View (Right): Width 21.50. Height 3.30±0.51. Pre-soldering area. Dimensions: 3.05, 10.90, 2.54±0.20, 8.89±0.20.

Bottom View: Overall length 58.93. Overall width 10.16. Hole diameters: 40xØ0.90, 3xØ1.70, 2xØ1.70, 2xØ3.20, 16xØ1.00. Dimensions: 13.97, 13.97, 12.70, 2.54, 3.05, 8.89, 10.16, 2.28, 4.06, 53.34, 54.84, 58.93, 1.04, 7.85, 11.12, 13.14, 12.93, 1.04.

RJ45 10/100/1000 Base-TX Tab down 1x4 Jack with Magnetic Module

ARJ14A


RoHS
Compliant




59.12 x 13.60 x 21.50 mm /
58.40 x 11.50 x 17.60 mm

MECHANICAL DIMENSIONS

ME (10/100 Base-T) (8 EMI Fingers)



MF (10/100 Base-T) (3 EMI Fingers)



**RoHS
Compliant**

MECHANICAL DIMENSIONS

Technical drawing of a 4x8 pin connector showing top, side, and bottom views with dimensions.

Top View Dimensions:

- Overall width: 59.12
- Pin pitch: $@1.27 \times 9 = 11.43$
- Pin 1 and 8 locations are marked.

Side View Dimensions:

- Overall height: 13.60
- Pin height: 21.50
- Pin diameter: 3.30 ± 0.51
- PRE-SOLDERING area is indicated.
- Bottom dimensions: 3.05, 10.90, 2.54 ± 0.20 , 8.89 ± 0.20

Bottom View Dimensions:

- Overall width: 53.34
- Overall width (including mounting holes): 58.93
- Mounting hole pattern: $40 \times \varnothing 0.90$, $3 \times \varnothing 1.70$
- Pin pitch: $@1.27 \times 9 = 11.43$
- Pin locations 1, 2, 9, 10 are marked.
- Dimensions for mounting holes: 2.54, 13.97, 13.97, 12.70, 2.54, 3.05, 8.89, 10.16

RJ45 10/100/1000 Base-TX Tab down 1x4 Jack with Magnetic Module

ARJ14A


RoHS
Compliant



59.12 x 13.60 x 21.50 mm /
58.40 x 11.50 x 17.60 mm

MECHANICAL DIMENSIONS


MI (10/100 Base-T)



RJ45 10/100/1000 Base-TX Tab down 1x4 Jack with Magnetic Module


ARJ14A

RoHS
Compliant



59.12 x 13.60 x 21.50 mm /
58.40 x 11.50 x 17.60 mm


SCHEMATICS



RJ45 10/100/1000 Base-TX Tab down 1x4 Jack with Magnetic Module










ARJ14A

RoHS
Compliant



59.12 x 13.60 x 21.50 mm /
58.40 x 11.50 x 17.60 mm

SCHEMATICS - continued



RJ45 10/100/1000 Base-TX Tab down 1x4 Jack with Magnetic Module












59.12 x 13.60 x 21.50 mm /
58.40 x 11.50 x 17.60 mm

RoHS
Compliant

ARJ14A

SCHEMATICS



RJ45 10/100/1000 Base-TX Tab down 1x4 Jack with Magnetic Module

ARJ14A

RoHS
Compliant




59.12 x 13.60 x 21.50 mm /
58.40 x 11.50 x 17.60 mm


LED POLARITY

8PIN:

E




F




10PIN:

G



H



RJ45 10/100/1000 Base-TX Tab down 1x4 Jack with Magnetic Module

ARJ14A

RoHS
Compliant





59.12 x 13.60 x 21.50 mm /
58.40 x 11.50 x 17.60 mm

PACKING: 20pcs/tray


Packaging material: PET

Outer carton unit 400 pcs/ 20 Trays/box



Dimensions: cm

REFLOW PROFILE:



A. Preheating B. Soldering C. Gradual Cooling

Peak temperature(T_p) : $250 \pm 10^\circ\text{C}$

Peak temperature(T_p) time : 5sec max

ATTENTION: Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS
ISO 9001:2008
CERTIFIED



ABRACON
CORPORATION

Visit www.abracon.com for Terms & Conditions of Sale

30332 Esperanza, Rancho Santa Margarita, California 92688
tel 949-546-8000 | fax 949-546-8001 | www.abracon.com

Revised: 08.04.11

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru