

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.





LOC
DW

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A5		REVISED (ECR-12-012115) OBSOLETE 1734324-6, 3-134324-4	26OCT'12	E.L.	W.K.

LED SCHEMATIC	
LED 2	LED 1
9+  -10	11+  -12



NOTE:

1. MATERIAL:

- 1.1 HOUSING: PA46, WITH 30% GF, UL94 V-0, BLACK COLOR.
- 1.2 INSERT HOUSING: PA46, WITH 30% GF, UL94 V-0, BLACK COLOR.
- 1.3 CONTACTS: PHOSPHOR BRONZE.
- 1.4 SHELL: BRASS.
- 1.5 LED SOLDER TAIL: STEEL.
- 1.6 MYLAR: SILICONE POLYMER.

2. FINISH:

- 2.1 CONTACTS: (SEE TABLE) GOLD PLATED ON CONTACT AREA.
GOLD FLASH ON SOLDER TAIL.
1.27um [50u"] MIN. NICKEL UNDERPLATED OVERALL.
- 2.2 SHELL: 0.508um [20u"] MIN. NICKEL PLATED.
- 2.3 LED: 1.02um [40u"] COPPER UNDERPLATED OVERALL.
1.27um [50u"] NICKEL OVERALL.
1.27um [50u"] SILVER ON BONDING AREA.
2.54um [100u"] BRIGHT-TIN ON SOLDER AREA.


3. LED MUST BE REFLOW COMPATIBLE TO FOLLOWING

TEMPERATURE PROFILE (FOR 1 CYCLE): ABOVE 160°C FOR 120 SECONDS, PEAKING AT 220°C FOR 10 SECONDS.

4. LED DEFECT RATE IS 6000 PPM MAX. AFTER IR REFLOW PROCESS AS NOTE 3.

5. WAVE SOLDER CAPABLE TO 265°C PER TE SPEC 109-202, CONDITION B.

6. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI.



6 OBSOLETE

6 OBSOLETE


OBSOLETE

6 OBSOLETE

6 OBSOLETE

6 OBSOLETE

6 OBSOLETE

THIS DRAWING IS A CONTROLLED DOCUMENT.	
DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:
	0 PLC ± -
	1 PLC ± 0.3
	2 PLC ± 0.2
	3 PLC ± 0.15
	4 PLC ± 0.1
	ANGLES ± 3°
MATERIAL SEE NOTE	FINISH SEE NOTE



DWN A. WU 04MAR2008	04MAR2008
CHK S. HOU 04MAR2008	04MAR2008
APVD W. KODAMA 04MAR2008	04MAR2008
PRODUCT SPEC 108-57535	
APPLICATION SPEC	
WEIGHT 4.5 GRAMS	
CUSTOMER DRAWING	

REEL	2.2	YELLOW	GREEN	1.27um[50u"]	1-1734324-8
				0.762um[30u"]	1-1734324-7
TRAY	2.2	GREEN	YELLOW	0.381um[15u"]	1-1734324-6
				0.152um[6u"]	1-1734324-5
PACKAGE	DIM A	POSITION 2	POSITION 1	1.27um[50u"]	1-1734324-4
				0.762um[30u"]	1-1734324-3
INDICATOR COLOR				0.381um[15u"]	1-1734324-2
				0.152um[6u"]	1-1734324-1
MIN. GOLD THICKNESS				1.27um[50u"]	1-1734324-8
				0.762um[30u"]	1734324-7
PART NUMBER				0.381um[15u"]	1734324-6
				0.152um[6u"]	1734324-5

STE

TE Connectivity

NAME			
MODULAR JACK CONNECTOR RJ45 WITH LED, 8P8C, SHIELDED TAB DOWN, DIP TYPE, H=11.3mm			
SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C=1734324	-
SCALE		SHEET	REV
-		1 OF 7	A5



1.1 HOUSING: PA46, WITH 30% GF, UL94 V-0, BLACK COLOR.
1.2 INSERT HOUSING: PA46, WITH 30% GF, UL94 V-0, BLACK COLOR.
1.3 CONTACTS: PHOSPHOR BRONZE.
1.4 SHELL: BRASS.
1.5 LED SOLDER TAIL: STEEL.
1.6 MYLAR: SILICONE POLYMER.


2.1 CONTACTS: (SEE TABLE) GOLD PLATED ON CONTACT AREA.
GOLD FLASH ON SOLDER TAIL.
1.27um [50u"] MIN. NICKEL UNDERPLATED OVERALL.

2.2 SHELL: 0.508um [20u"] MIN. NICKEL PLATED.

2.3 LED: 1.02um [40u"] COPPER UNDERPLATED OVERALL.
1.27um [50u"] NICKEL OVERALL.
1.27um [50u"] SILVER ON BONDING AREA.
2.54um [100u"] BRIGHT-TIN ON SOLDER AREA.

5. WAVE SOLDER CAPABLE TO 265°C PER TE SPEC 109-202, CONDITION B.

6. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI.



△6	OBSOLETE	W/O	TAPE & REEL	YELLOW	GREEN	1.27um[50u"]	3-1734324
						0.762um[30u"]	3-1734324
						0.381um[15u"]	3-1734324
						0.152um[6u"]	3-1734324
	OBSOLETE			GREEN	YELLOW	1.27um[50u"]	3-1734324
			0.762um[30u"]			3-1734324	
			0.381um[15u"]			3-1734324	
			0.152um[6u"]			3-1734324	
△6	OBSOLETE	W/	TRAY	YELLOW	GREEN	1.27um[50u"]	2-1734324
						0.762um[30u"]	2-1734324
						0.381um[15u"]	2-1734324
						0.152um[6u"]	2-1734324
				GREEN	YELLOW	1.27um[50u"]	2-1734324
						0.762um[30u"]	2-1734324
						0.381um[15u"]	2-1734324
						0.152um[6u"]	2-1734324
	RIB	PACKAGE	POSITION 2 INDICATOR	POSITION 1 COLOR	MIN. GOLD THICKNESS	PART NUMBER	

DIMENSIONS: mm	
	
MATERIAL	


TOLERANCES UNLESS OTHERWISE SPECIFIED:	
0 PLC	$\pm -$
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	$\pm -$
ANGLES	$\pm 3'$
FINISH	





TE Connectivity

NAME	MODULAR JACK CONNECTOR RJ45 WITH LED, 8P8C, SHIELDED TAB DOWN, DIP TYPE. H=11.3mm
------	---

SIZE	CAGE CODE	DRAWING NO	RESTRICTED
A3	00779	C-1734324	—
		SCALE	SHEET
		—	2 of 7
			REV A5







- 1.1 HOUSING: PA9T, WITH 30% GF, UL94 V-0, BLACK COLOR.
- 1.2 INSERT HOUSING: PA46, WITH 30% GF, UL94 V-0, BLACK COLOR.
- 1.3 CONTACTS: PHOSPHOR BRONZE.
- 1.4 SHELL: BRASS.
- 1.5 LED SOLDER TAIL: STEEL.
- 1.6 MYLAR: SILICONE POLYMER.


2.1 CONTACTS: (SEE TABLE) GOLD PLATED ON CONTACT AREA.
GOLD FLASH ON SOLDER TAIL.
1.27um [50u"] MIN. NICKEL UNDERPLATED OVERALL.

2.2 SHELL: 0.508um [20u"] MIN. NICKEL PLATED.

2.3 LED: 1.02um [40u"] COPPER UNDERPLATED OVERALL.
1.27um [50u"] NICKEL OVERALL.
1.27um [50u"] SILVER ON BONDING AREA.
2.54um [100u"] BRIGHT-TIN ON SOLDER AREA.

3. LED MUST BE REFLOW COMPATIBLE TO FOLLOWING TEMPERATURE PROFILE (FOR 1 CYCLE): ABOVE 160°C FOR 120 SECONDS, PEAKING AT 220°C FOR 10 SECONDS.
4. LED DEFECT RATE IS 6000 PPM MAX. AFTER IR REFLOW PROCESS AS NOTE 3.

5. WAVE SOLDER CAPABLE TO 265°C PER TE SPEC 109-202, CONDITION B.



TAPE & REEL	GREEN/ ORANGE	YELLOW	1.27um[50u"]	6-1734324-
			0.762um[30u"]	6-1734324-
			0.381um[15u"]	6-1734324-
			0.152um[6u"]	6-1734324-
TRAY			1.27um[50u"]	6-1734324-
			0.762um[30u"]	6-1734324-
			0.381um[15u"]	6-1734324-
			0.152um[6u"]	6-1734324-
PACKAGE	POSITION 2	POSITION 1	MIN. GOLD THICKNESS	PART NUMBER
	INDICATOR	COLOR		

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED	
mm			
		0 PLC	±
		1 PLC	± 0.3
		2 PLC	± 0.2
		3 PLC	± 0.15
		4 PLC	±
ANGLES		± 3°	
MATERIAL		FINISH	
—		—	

DWN	—	 TE Connectivity			
CHK	—				
APVD	—				
PRODUCT SPEC	—	NAME MODULAR JACK CONNECTOR RJ45 WITH LED, 8P8C, SHIELDED TAB DOWN, DIP TYPE, H=11.3mm			
APPLICATION SPEC	—				
WEIGHT	—				
		SIZE	CAGE CODE	DRAWING NO	RESTRICTED
		A3	00779	Ⓒ=1734324	—
CUSTOMER DRAWING				SCALE	SHEET 5 OF 7 REV A5

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION


© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC
DW

DIST

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
		SEE SHEET 1.			



NOTES:

1. MATERIAL:
TRAY: PVC.
BOX: CORRUGATED FIBER.
2. DIMENSION: SEE DRAWING
3. QUANTITY: SEE TABLE
4. WEIGHT: SEE TABLE

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	TE Connectivity			
DIMENSIONS: mm		CHK				
		APVD				
		PRODUCT SPEC				
		APPLICATION SPEC				
MATERIAL		WEIGHT	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
FINISH		CUSTOMER DRAWING	A3	00779	C=1734324	—
			SCALE	SHEET	6 of 7	REV A5

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT 2010 BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.

LOC
DW

DIST

REVISIONS

P

LTR



DESCRIPTION

DATE

DWN






APVD

SEE SHEET 1.



NOTE:

1. EACH BAG SHALL BE INCLUDED:
*DESICCANT
2. PEELING STRENGTH: $0.1 \sim 1.3N$ ($1 \sim 130$ GRAMS) FOR $12 \sim 56mm$ WIDE CARRIER TAPES
3. PEELING SPEED: 300mm/MINUTES.
4. PACKAGING MATERIAL:
 - 4.1 COVER TAPE—COMPOSITE OF POLYETHYLENE TEREPHTHALATE (PET)
 - 4.2 CARRIER—POLYSTYRENE (PS)
 - 4.3 CARRIER REEL—POLYSTYRENE



8.5KG	6.1KG	180	8	1440	6-1734324-5~8
					3-1734324-X
					1-1734324-X
GROSS WEIGHT	NET WEIGHT	PCS /REEL	REEL /BOX	PCS /BOX	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

MATERIAL

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	$\pm .$
1 PLC	± 0.3
2 PLC	± 0.2
3 PLC	± 0.15
4 PLC	$\pm .$
ANGLES	$\pm 3^{\circ}$

FINISH

DWN

CHK

APVD

PRODUCT SPEC

APPLICATION SPEC

WEIGHT

CUSTOMER DRAWING

STE

TE Connectivity

NAME

MODULAR JACK CONNECTOR
RJ45 WITH LED, 8P8C, SHIELDED
TAB DOWN, DIP TYPE, H=11.3mm

SIZE

CAGE CODE

DRAWING NO

RESTRICTED TO

A3

00779

C=1734324

SCALE

SHEET

7 of 7

REV A5

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru