

40 Series



Ohmite® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard



Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- RoHS compliant; add "E" suffix to part number to specify.

SERIES SPECIFICATIONS

Series	Wattage	Ohms	Voltage
41	1.0	0.10-6K	150
42	2.0	0.10-8K	100
43	3.0	0.10-20K	200
45	5.0	0.10-70K	460
47	7.0	0.10-80K	670
40	10.0	0.10-150K	1000

Non-Inductive versions available. Insert "N" before tolerance code.
Example: 42NJ27R

CHARACTERISTICS

Coating	Conformal silicone-ceramic.
Core	Ceramic.
Terminals	Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu
Derating	Linearly from 100% @ +25°C to 0% @ +275°C.
Tolerance	±5% (J type), ±1% (F type) (other tolerances available).
Power rating	Based on 25°C free air rating
Overload	Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.
Temperature coefficient	Under 1Ω: ±90 ppm/°C; 1Ω to 9.99Ω: ±50 ppm/°C; 10Ω and over: ±20 ppm/°C
Operating temp. range	-55°C to 275°C

DIMENSIONS

(in./mm max.)



Series	Wattage	Length	Diam.	Lead ga.
41	1.0	0.437 / 11.1	0.125 / 3.2	24
42	2.0	0.406 / 10.3	0.219 / 5.6	20
43	3.0	0.593 / 15.1	0.219 / 5.6	20
45	5.0	0.937 / 23.8	0.343 / 8.7	18
47	7.0	1.280 / 32.5	0.343 / 8.7	18
40	10.0	1.900 / 48.3	0.406 / 10.3	18

(continued)

40 Series

Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard

ORDERING INFORMATION

Standard part numbers

Ohmic value	Wattage and Tolerance					Ohmic value	Wattage and Tolerance					Ohmic value	Wattage and Tolerance				
	Part No. Prefix > Suffix >	1% Tolerance	3	5	10		Part No. Prefix > Suffix >	1% Tolerance	3	5	10		Part No. Prefix > Suffix >	1% Tolerance	3	5	10
0.1	R10	✓	✓	✓	✓	68	68R	✓	✓	✓	✓	2,200	2K2	✓	✓	✓	✓
0.15	R15	✓	✓	✓	✓	75	75R	✓	✓	✓	✓	2,500	2K5	✓	✓	✓	✓
0.2	R20	✓	✓	✓	✓	82	82R	✱	✓	✓	✓	2,700	2K7	✱	✱	✓	✓
0.25	R25	✓	✓	✓	✓	100	100	✓	✓	✓	✓	3,000	3K0	✓	✓	✓	✓
0.3	R30	✓	✓	✓	✓	120	120	✱	✓	✓	✓	3,300	3K3	✱	✱	✓	✓
0.33	R33	✓	✓	✓	✓	125	125	✓	✱	✱	✓	3,500	3K5	✓	✓	✓	✓
0.4	R40	✓	✓	✓	✓	150	150	✓	✓	✓	✱	3,900	3K9	✓	✓	✓	✓
0.5	R50	✓	✓	✓	✓	180	180	✓	✓	✓	✱	4,000	4K0	✓	✓	✓	✓
0.75	R75	✓	✱	✓	✓	200	200	✓	✓	✓	✓	4,500	4K5	✱	✱	✓	✓
1	R10	✓	✓	✓	✓	220	220	✓	✓	✱	✱	4,700	4K7	✓	✓	✓	✓
1.5	R15	✓	✓	✓	✓	225	225	✱	✱	✱	✓	5,000	5K0	✓	✓	✓	✓
2	R20	✓	✓	✓	✓	250	250	✓	✓	✓	✓	6,000	6K0	✓	✓	✓	✓
2.2	R22	✓	✓	✓	✓	270	270	✓	✓	✓	✓	6,800	6K8	✓	✓	✓	✓
3	R30	✓	✓	✓	✱	300	300	✓	✱	✓	✓	7,000	7K0	✓	✓	✓	✓
4	R40	✓	✓	✓	✓	330	330	✓	✱	✱	✓	7,500	7K5	✓	✓	✓	✓
5	R50	✓	✓	✓	✓	350	350	✱	✓	✱	✓	8,000	8K0	✓	✓	✓	✓
7.5	R75	✓	✓	✓	✓	390	390	✱	✓	✱	✓	9,000	9K0	✓	✓	✓	✓
10	R10	✓	✓	✓	✓	400	400	✓	✓	✓	✓	10,000	10K	✓	✓	✓	✓
12	R12	✓	✓	✓	✱	450	450	✱	✓	✱	✓	12,000	12K	✓	✓	✓	✓
15	R15	✓	✓	✓	✱	470	470	✓	✓	✱	✓	13,000	13K	✓	✓	✓	✓
18	R18	✱	✓	✱	✱	500	500	✓	✓	✓	✓	15,000	15K	✓	✓	✓	✓
20	R20	✓	✓	✓	✓	560	560	✓	✓	✓	✓	17,000	17K	✓	✱	✓	✓
22	R22	✓	✓	✓	✱	600	600	✓	✓	✓	✓	20,000	20K	✓	✓	✓	✓
25	R25	✓	✓	✓	✱	680	680	✓	✓	✓	✓	22,000	22K	✓	✓	✓	✓
27	R27	✓	✓	✓	✱	750	750	✓	✓	✓	✓	25,000	25K	✓	✓	✓	✓
30	R30	✓	✓	✓	✓	800	800	✓	✓	✓	✓	30,000	30K	✓	✓	✓	✓
33	R33	✓	✓	✓	✓	820	820	✓	✓	✓	✓	33,000	33K	✓	✓	✓	✓
35	R35	✓	✓	✓	✓	900	900	✓	✓	✓	✓	35,000	35K	✓	✓	✓	✓
39	R39	✓	✓	✓	✓	1,000	1K0	✓	✓	✓	✓	40,000	40K	✓	✓	✓	✓
40	R40	✓	✓	✓	✓	1,100	1K1	✓	✓	✓	✓	50,000	50K	✓	✓	✓	✓
47	R47	✓	✓	✓	✓	1,200	1K2	✓	✓	✓	✓	✓ = Standard values					
50	R50	✓	✓	✓	✓	1,500	1K5	✓	✓	✓	✓	✱ = Non-standard values subject to minimum handling charge per item					
56	R56	✓	✓	✓	✓	1,800	1K8	✓	✓	✓	✓						
62	R62	✓	✓	✓	✓	2,000	2K0	✓	✓	✓	✓						

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru