

40 Series

Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard



Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- RoHS compliant; add "E" suffix to part number to specify.

SERIES SPECIFICATIONS

Series	Wattage	Ohms	Voltage
41	1.0	0.10-6K	150
42	2.0	0.10-8K	100
43	3.0	0.10-20K	200
45	5.0	0.10-70K	460
47	7.0	0.10-80K	670
40	10.0	0.10-150K	1000

Non-Inductive versions available. Insert "N" before tolerance code.
Example: 42NJ27R

CHARACTERISTICS

Coating	Conformal silicone-ceramic.
Core	Ceramic.
Terminals	Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu
Derating	Linearly from 100% @ +25°C to 0% @ +275°C.
Tolerance	±5% (J type), ±1% (F type) (other tolerances available).
Power rating	Based on 25°C free air rating
Overload	Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.
Temperature coefficient	Under 1Ω: ±90 ppm/°C; 1Ω to 9.99Ω: ±50 ppm/°C; 10Ω and over: ±20 ppm/°C
Operating temp. range	-55°C to 275°C

DIMENSIONS

(in./mm max.)



Series	Wattage	Length	Diam.	Lead ga.
41	1.0	0.437 / 11.1	0.125 / 3.2	24
42	2.0	0.406 / 10.3	0.219 / 5.6	20
43	3.0	0.593 / 15.1	0.219 / 5.6	20
45	5.0	0.937 / 23.8	0.343 / 8.7	18
47	7.0	1.280 / 32.5	0.343 / 8.7	18
40	10.0	1.900 / 48.3	0.406 / 10.3	18

(continued)

40 Series

Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard

ORDERING INFORMATION

Standard part numbers

Wattage and Tolerance										Wattage and Tolerance										Wattage and Tolerance																	
Ohmic value	1% Tolerance					5% Tolerance					Ohmic value	1% Tolerance					5% Tolerance					Ohmic value	1% Tolerance					5% Tolerance									
	Part No. Prefix ▶ Suffix ▼	1	3	5	10	1	2	3	5	10		Part No. Prefix ▶ Suffix ▼	1	3	5	10	1	2	3	5	10		Part No. Prefix ▶ Suffix ▼	1	3	5	10	1	2	3	5	10					
0.1	—R10	✓				✓					68	—68R	✓				✓					2,200	—2K2	✓				✓				✓					
0.15	—R15	✓	✓			✓	✓				75	—75R	✓				✓	✓				2,500	—2K5	✓	✓			✓	✓			✓	✓				
0.2	—R20	✓	✓	✓		✓					82	—82R	✱				✓	✓				2,700	—2K7	✓	✓	✓		✓	✓			✓	✓				
0.25	—R25										100	—100	✓				✓	✓				3,000	—3K0					✓	✓			✓	✓				
0.3	—R30	✓		✓		✓				✓	120	—120	✱				✓	✓				3,300	—3K3		✓	✓	✓	✓			✓	✓					
0.33	—R33									✓	125	—125	✓	✱			✓	✓				3,500	—3K5		✓			✓				✓	✓				
0.4	—R40		✓							✓	150	—150	✓	✓			✓	✓				3,900	—3K9		✓	✓						✓	✓				
0.5	—R50	✓	✓	✓		✓	✓			✓	180	—180	✓		✱		✓	✓				4,000	—4K0		✓	✓	✓			✓	✓		✓	✓			
0.75	—R75	✓	✱			✓				✓	200	—200	✓				✓	✓				4,500	—4K5		✓	✓	✓			✓	✓		✓	✓			
1	—1R0	✓	✓			✓				✓	220	—220	✓	✓		✱	✓	✓				4,700	—4K7			✓	✓	✓			✓	✓		✓	✓		
1.5	—1R5	✓	✓	✓		✓				✓	225	—225	✱	✱			✓	✓	✱			5,000	—5K0		✓	✓	✓				✓	✓	✓	✓			
2	—2R0					✓	✓			✓	250	—250	✓	✓			✓	✓				6,000	—6K0		✓	✓	✓				✓	✓		✓	✓		
2.2	—2R2	✓	✓	✓		✓				✓	270	—270	✓		✱		✓	✓	✱			6,800	—6K8		✓	✓					✓	✓		✓	✓		
3	—3R0	✓	✓	✓	✱					✓	300	—300	✓	✱			✓	✓				7,000	—7K0		✓	✓	✓			✓	✓		✓	✓			
4	—4R0	✓	✓	✓	✓	✓				✓	330	—330	✓	✱	✱		✓	✓				7,500	—7K5		✓	✓	✓	✓			✓	✓		✓	✓		
5	—5R0	✓	✓	✓		✓				✓	350	—350	✱				✓	✓	✱			8,000	—8K0			✓	✓					✓	✓		✓	✓	
7.5	—7R5	✓	✓	✓	✓	✓				✱	390	—390	✱				✓	✓				9,000	—9K0		✓	✓	✓	✱			✓	✓		✓	✓		
10	—10R					✓				✓	400	—400	✓	✓		✱	✓	✓				10,000	—10K		✓	✓				✓	✓		✓	✓			
12	—12R	✱	✓	✓	✱	✓	✓			✓	450	—450	✓				✓	✓	✱	✱		12,000	—12K			✓	✓										
15	—15R	✓	✓	✓	✱	✓	✱			✓	470	—470	✓	✓	✓	✱	✓	✓				13,000	—13K			✓	✓	✓									
18	—18R	✱	✓	✓	✱	✓	✓			✱	500	—500	✓	✓			✓	✓				15,000	—15K		✓	✓											
20	—20R	✓	✓	✓		✓				✱	560	—560	✓	✓	✓		✓	✓	✱			17,000	—17K			✓	✓										
22	—22R	✓	✓	✓	✱	✓				✓	600	—600	✓				✓	✓				20,000	—20K		✓	✓											
25	—25R	✓	✓	✓	✱	✓				✱	680	—680	✓		✱		✓	✓				22,000	—22K		✓	✓	✓										
27	—27R	✱	✓	✓	✓	✓				✱	750	—750	✓	✓	✓	✓	✓	✓				25,000	—25K		✓	✓											
30	—30R	✓	✓	✓	✓	✓	✱			✓	800	—800	✓	✓	✓	✓	✓	✱	✱			30,000	—30K			✓	✓										
33	—33R	✓	✓	✓	✱	✓				✓	820	—820	✓				✓	✓				33,000	—33K														
35	—35R	✓	✱		✓	✓				✓	900	—900	✓		✱		✓	✓				35,000	—35K														
39	—39R	✓	✓	✓	✱	✓				✓	1,000	—1K0	✓	✓	✓	✓	✓	✓				40,000	—40K														
40	—40R	✓	✓	✓		✓	✱			✓	1,100	—1K1	✱	✱			✓	✓	✱	✱		50,000	—50K														
47	—47R	✓	✓	✓	✱	✓				✓	1,200	—1K2	✓	✱			✓	✓				✓ = Standard values															
50	—50R	✓	✓	✓		✓				✓	1,500	—1K5	✓	✓	✓	✓	✓	✓				✱ = Non-standard values subject to mini-															
56	—56R	✓	✓	✓	✱	✓				✓	1,800	—1K8	✓	✓	✓	✓	✓	✓				mum handling charge per item															
62	—62R	✓	✓	✓	✓	✓				✱	2,000	—2K0	✓	✓			✓	✓																			

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

✓ = Standard values

✦ = Non-standard values subject to minimum handling charge per item

40 Series
Ohmicone®
Silicone Ceramic
Conformal Axial
Term. Wirewound

Non-Inductive
Winding
optional
(blank= std.
winding)

RoHS
Compliant

41NJR10E-T

Wattage
1 = 1W
2
3
5
7
0 = 10W

Tolerance
F = 1%
J = 5%

Resistance
R10 = 0.10Ω
1R0 = 1.0Ω
10R = 10.0Ω
250 = 250Ω
1K0 = 1,000Ω
4K5 = 4,500Ω
50K = 50,000Ω

Tape & reel
optional
pc/reel:
41: 5000
42: 1250
43: 1250
45: 1000
47: 500
40: 500

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru