

40 Series

Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard



Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- RoHS compliant; add "E" suffix to part number to specify.

SERIES SPECIFICATIONS

Series	Wattage	Ohms	Voltage
41	1.0	0.10-6K	150
42	2.0	0.10-8K	100
43	3.0	0.10-20K	200
45	5.0	0.10-70K	460
47	7.0	0.10-80K	670
40	10.0	0.10-150K	1000

Non-Inductive versions available. Insert "N" before tolerance code.
Example: 42NJ27R

CHARACTERISTICS

Coating	Conformal silicone-ceramic.
Core	Ceramic.
Terminals	Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu
Derating	Linearly from 100% @ +25°C to 0% @ +275°C.
Tolerance	±5% (J type), ±1% (F type) (other tolerances available).
Power rating	Based on 25°C free air rating
Overload	Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.
Temperature coefficient	Under 1Ω: ±90 ppm/°C; 1Ω to 9.99Ω: ±50 ppm/°C; 10Ω and over: ±20 ppm/°C
Operating temp. range	-55°C to 275°C

DIMENSIONS

(in./mm max.)



Series	Wattage	Length	Diam.	Lead ga.
41	1.0	0.437 / 11.1	0.125 / 3.2	24
42	2.0	0.406 / 10.3	0.219 / 5.6	20
43	3.0	0.593 / 15.1	0.219 / 5.6	20
45	5.0	0.937 / 23.8	0.343 / 8.7	18
47	7.0	1.280 / 32.5	0.343 / 8.7	18
40	10.0	1.900 / 48.3	0.406 / 10.3	18

(continued)

40 Series

Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard

ORDERING INFORMATION

Standard part numbers

Wattage and Tolerance										
1% Tolerance										
5% Tolerance										
Ohmic value	Part No. Prefix ▶ Suffix ▼	1	3	5	10	1	2	3	5	10
0.1	R10	✓	✓	✓	✓	✓	✓	✓	✓	✓
0.15	R15	✓	✓	✓	✓	✓	✓	✓	✓	✓
0.2	R20	✓	✓	✓	✓	✓	✓	✓	✓	✓
0.25	R25	✓	✓	✓	✓	✓	✓	✓	✓	✓
0.3	R30	✓	✓	✓	✓	✓	✓	✓	✓	✓
0.33	R33	✓	✓	✓	✓	✓	✓	✓	✓	✓
0.4	R40	✓	✓	✓	✓	✓	✓	✓	✓	✓
0.5	R50	✓	✓	✓	✓	✓	✓	✓	✓	✓
0.75	R75	✓	✓	✓	✓	✓	✓	✓	✓	✓
1	R100	✓	✓	✓	✓	✓	✓	✓	✓	✓
1.5	R150	✓	✓	✓	✓	✓	✓	✓	✓	✓
2	R200	✓	✓	✓	✓	✓	✓	✓	✓	✓
2.2	R220	✓	✓	✓	✓	✓	✓	✓	✓	✓
3	R300	✓	✓	✓	✓	✓	✓	✓	✓	✓
4	R400	✓	✓	✓	✓	✓	✓	✓	✓	✓
5	R500	✓	✓	✓	✓	✓	✓	✓	✓	✓
7.5	R750	✓	✓	✓	✓	✓	✓	✓	✓	✓
10	R1000	✓	✓	✓	✓	✓	✓	✓	✓	✓
12	R1200	✓	✓	✓	✓	✓	✓	✓	✓	✓
15	R1500	✓	✓	✓	✓	✓	✓	✓	✓	✓
18	R1800	✓	✓	✓	✓	✓	✓	✓	✓	✓
20	R2000	✓	✓	✓	✓	✓	✓	✓	✓	✓
22	R2200	✓	✓	✓	✓	✓	✓	✓	✓	✓
25	R2500	✓	✓	✓	✓	✓	✓	✓	✓	✓
27	R2700	✓	✓	✓	✓	✓	✓	✓	✓	✓
30	R3000	✓	✓	✓	✓	✓	✓	✓	✓	✓
33	R3300	✓	✓	✓	✓	✓	✓	✓	✓	✓
35	R3500	✓	✓	✓	✓	✓	✓	✓	✓	✓
39	R3900	✓	✓	✓	✓	✓	✓	✓	✓	✓
40	R4000	✓	✓	✓	✓	✓	✓	✓	✓	✓
47	R4700	✓	✓	✓	✓	✓	✓	✓	✓	✓
50	R5000	✓	✓	✓	✓	✓	✓	✓	✓	✓
56	R5600	✓	✓	✓	✓	✓	✓	✓	✓	✓
62	R6200	✓	✓	✓	✓	✓	✓	✓	✓	✓

Wattage and Tolerance										
1% Tolerance										
5% Tolerance										
Ohmic value	Part No. Prefix ▶ Suffix ▼	1	3	5	10	1	2	3	5	10
68	R68	✓	✓	✓	✓	✓	✓	✓	✓	✓
75	R75	✓	✓	✓	✓	✓	✓	✓	✓	✓
82	R82	✓	✓	✓	✓	✓	✓	✓	✓	✓
100	R100	✓	✓	✓	✓	✓	✓	✓	✓	✓
120	R120	✓	✓	✓	✓	✓	✓	✓	✓	✓
125	R125	✓	✓	✓	✓	✓	✓	✓	✓	✓
150	R150	✓	✓	✓	✓	✓	✓	✓	✓	✓
180	R180	✓	✓	✓	✓	✓	✓	✓	✓	✓
200	R200	✓	✓	✓	✓	✓	✓	✓	✓	✓
220	R220	✓	✓	✓	✓	✓	✓	✓	✓	✓
225	R225	✓	✓	✓	✓	✓	✓	✓	✓	✓
250	R250	✓	✓	✓	✓	✓	✓	✓	✓	✓
270	R270	✓	✓	✓	✓	✓	✓	✓	✓	✓
300	R300	✓	✓	✓	✓	✓	✓	✓	✓	✓
330	R330	✓	✓	✓	✓	✓	✓	✓	✓	✓
350	R350	✓	✓	✓	✓	✓	✓	✓	✓	✓
390	R390	✓	✓	✓	✓	✓	✓	✓	✓	✓
400	R400	✓	✓	✓	✓	✓	✓	✓	✓	✓
450	R450	✓	✓	✓	✓	✓	✓	✓	✓	✓
470	R470	✓	✓	✓	✓	✓	✓	✓	✓	✓
500	R500	✓	✓	✓	✓	✓	✓	✓	✓	✓
560	R560	✓	✓	✓	✓	✓	✓	✓	✓	✓
600	R600	✓	✓	✓	✓	✓	✓	✓	✓	✓
680	R680	✓	✓	✓	✓	✓	✓	✓	✓	✓
750	R750	✓	✓	✓	✓	✓	✓	✓	✓	✓
800	R800	✓	✓	✓	✓	✓	✓	✓	✓	✓
820	R820	✓	✓	✓	✓	✓	✓	✓	✓	✓
900	R900	✓	✓	✓	✓	✓	✓	✓	✓	✓
1,000	R1K0	✓	✓	✓	✓	✓	✓	✓	✓	✓
1,100	R1K1	✓	✓	✓	✓	✓	✓	✓	✓	✓
1,200	R1K2	✓	✓	✓	✓	✓	✓	✓	✓	✓
1,500	R1K5	✓	✓	✓	✓	✓	✓	✓	✓	✓
1,800	R1K8	✓	✓	✓	✓	✓	✓	✓	✓	✓
2,000	R2K0	✓	✓	✓	✓	✓	✓	✓	✓	✓

Wattage and Tolerance										
1% Tolerance										
5% Tolerance										
Ohmic value	Part No. Prefix ▶ Suffix ▼	1	3	5	10	1	2	3	5	10
2,200	R2K2	✓	✓	✓	✓	✓	✓	✓	✓	✓
2,500	R2K5	✓	✓	✓	✓	✓	✓	✓	✓	✓
2,700	R2K7	✓	✓	✓	✓	✓	✓	✓	✓	✓
3,000	R3K0	✓	✓	✓	✓	✓	✓	✓	✓	✓
3,300	R3K3	✓	✓	✓	✓	✓	✓	✓	✓	✓
3,500	R3K5	✓	✓	✓	✓	✓	✓	✓	✓	✓
3,900	R3K9	✓	✓	✓	✓	✓	✓	✓	✓	✓
4,000	R4K0	✓	✓	✓	✓	✓	✓	✓	✓	✓
4,500	R4K5	✓	✓	✓	✓	✓	✓	✓	✓	✓
4,700	R4K7	✓	✓	✓	✓	✓	✓	✓	✓	✓
5,000	R5K0	✓	✓	✓	✓	✓	✓	✓	✓	✓
6,000	R6K0	✓	✓	✓	✓	✓	✓	✓	✓	✓
6,800	R6K8	✓	✓	✓	✓	✓	✓	✓	✓	✓
7,000	R7K0	✓	✓	✓	✓	✓	✓	✓	✓	✓
7,500	R7K5	✓	✓	✓	✓	✓	✓	✓	✓	✓
8,000	R8K0	✓	✓	✓	✓	✓	✓	✓	✓	✓
9,000	R9K0	✓	✓	✓	✓	✓	✓	✓	✓	✓
10,000	R10K	✓	✓	✓	✓	✓	✓	✓	✓	✓
12,000	R12K	✓	✓	✓	✓	✓	✓	✓	✓	✓
13,000	R13K	✓	✓	✓	✓	✓	✓	✓	✓	✓
15,000	R15K	✓	✓	✓	✓	✓	✓	✓	✓	✓
17,000	R17K	✓	✓	✓	✓	✓	✓	✓	✓	✓
20,000	R20K	✓	✓	✓	✓	✓	✓	✓	✓	✓
22,000	R22K	✓	✓	✓	✓	✓	✓	✓	✓	✓
25,000	R25K	✓	✓	✓	✓	✓	✓	✓	✓	✓
30,000	R30K	✓	✓	✓	✓	✓	✓	✓	✓	✓
33,000	R33K	✓	✓	✓	✓	✓	✓	✓	✓	✓
35,000	R35K	✓	✓	✓	✓	✓	✓	✓	✓	✓
40,000	R40K	✓	✓	✓	✓	✓	✓	✓	✓	✓
50,000	R50K	✓	✓	✓	✓	✓	✓	✓	✓	✓

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

✓ = Standard values

✦ = Non-standard values subject to minimum handling charge per item

40 Series
Ohmicone®
Silicone Ceramic
Conformal Axial
Term. Wirewound

Non-Inductive
Winding
optional
(blank= std.
winding)

RoHS
Compliant

41NJR10E-T — Tape & reel
optional
pc/reel:

Wattage
1 = 1W
2
3
5
7
0 = 10W

Tolerance
F = 1%
J = 5%

Resistance
R10 = 0.10Ω
1R0 = 1.0Ω
10R = 10.0Ω
250 = 250Ω
1K0 = 1,000Ω
4K5 = 4,500Ω
50K = 50,000Ω

41: 5000
42: 1250
43: 1250
45: 1000
47: 500
40: 500

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru