



ZXTN25040DFH

40V NPN MEDIUM POWER PLANAR TRANSISTOR IN SOT23

Features and Benefits

- $BV_{CEO} > 40V$
- $I_C = 4A$ Continuous Collector Current
- Low Saturation Voltage $V_{CE(sat)} < 55mV @ 1A$
- $R_{CE(sat)} = 35m\Omega$
- h_{FE} characterised up to 10A
- High h_{FE} min 300 @ 1A
- 1.25W power dissipation
- 130V forward blocking voltage
- 6V reverse blocking voltage
- Complementary part number ZXTP25040DFH
- **“Lead-Free”, RoHS Compliant (Note 1)**
- **Halogen and Antimony Free. “Green” Device (Note 2)**
- **Qualified to AEC-Q101 Standards for High Reliability**


Mechanical Data

- Case: SOT23
- Case material: Molded Plastic. “Green” Molding Compound (Note 2) UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish; Solderable per MIL-STD-202, Method 208
- Weight: 0.008 grams (Approximate)


Applications

- MOSFET gate drivers
- Power switches
- Motor control
- DC fans
- DC-DC converters


SOT23



Top View



Device Symbol




Top View
Pin Configuration

Ordering Information (Note 3)

Product	Marking	Reel size (inches)	Tape width (mm)	Quantity per reel
ZXTN25040DFHTA	1A4	7	8	3,000

- Notes:
1. No purposefully added lead.
 2. Diodes Inc's “Green” Policy can be found on our website at <https://www.diodes.com/>
 3. Devices with lot number starting from PID0155145 (March 2010) are “Green” products.

Marking Information



1A4 = Product Type Marking Code

Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified






Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V_{CBO}	130	V
Collector-Emitter Voltage (Forward Blocking)	V_{CEX}	130	V
Collector-Emitter Voltage	V_{CEO}	40	V
Emitter-Collector Voltage (Reverse Blocking)	V_{ECO}	6	V
Emitter-Base Voltage	V_{EBO}	7	V
Continuous Collector Current (Note 6)	I_C	4	A
Peak Pulse Current	I_{CM}	10	A
Base Current	I_B	1	A

Thermal Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Value	Unit
Power Dissipation Linear Derating Factor	P_D -	0.73	W mW/ $^\circ\text{C}$
		5.84	
		1.05	
		8.4	
		1.25	
Thermal Resistance, Junction to Ambient	$R_{\theta JA}$	9.6	$^\circ\text{C/W}$
		1.81	
		14.5	
		171	
Thermal Resistance, Junction to Lead	$R_{\theta JL}$	119	$^\circ\text{C/W}$
		100	
		69	
		74.95	
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	$^\circ\text{C}$

- Notes:
4. For a device surface mounted on 15mm X 15mm X 1.6mm FR4 PCB with high coverage of single sided 1 oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
 5. For a device surface mounted on 25mm X 25mm X 1.6mm FR4 PCB with high coverage of single sided 2 oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
 6. For a device surface mounted on 50mm X 50mm X 1.6mm FR4 PCB with high coverage of single sided 2 oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
 7. As note 6 above, measured at $t < 5$ seconds
 8. Thermal resistance from junction to solder-point (at the end of the collector lead).

Typical Thermal Characteristics








Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS						
Collector-Base Breakdown Voltage	BV_{CBO}	130	170	-	V	$I_C = 100\mu\text{A}$
Collector-emitter breakdown voltage (forward blocking)	BV_{CEX}	130	170	-	V	$I_C = 100\mu\text{A}; R_{BE} < 1\text{k}\Omega$ or $-1\text{V} < V_{BE} < 0.25\text{V}$
Collector-Emitter Breakdown Voltage (base open) (Note 9)	BV_{CEO}	40	63	-	V	$I_C = 10\text{mA}$
Emitter-Base Breakdown Voltage	BV_{EBO}	7	8.3	-	V	$I_E = 100\mu\text{A}$
Emitter-collector breakdown voltage (reverse blocking)	BV_{ECX}	6	7.4	-	V	$I_E = 100\mu\text{A}; R_{BC} < 1\text{k}\Omega$ or $-0.25\text{V} < V_{BC} < 0.25\text{V}$
Emitter-collector breakdown voltage (base open)	BV_{ECO}	6	7.4	-	V	$I_E = 100\mu\text{A};$
Collector-base Cut-off Current	I_{CBO}	-	<1	50	nA	$V_{CB} = 100\text{V}$
				20	μA	$V_{CB} = 100\text{V}, T_A = 100^\circ\text{C}$
Collector-emitter Cut-off Current	I_{CEX}	-	-	100	nA	$V_{CE} = 100\text{V}; R_{BE} < 1\text{k}\Omega$ or $-1\text{V} < V_{BE} < 0.25\text{V}$
Emitter-base Cut-off Current	I_{EBO}	-	<1	50	nA	$V_{EB} = 5.6\text{V}$
ON CHARACTERISTICS (Note 9)						
Static Forward Current Transfer Ratio	h_{FE}	300	450	900	-	$I_C = 10\text{mA}, V_{CE} = 2\text{V}$
		300	450	-		
		30	60	-		
		-	10	-		
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	-	45	55	mV	$I_C = 1\text{A}, I_B = 100\text{mA}$
		-	120	210		
		-	135	210		
		-	140	190		
Base-Emitter Saturation Voltage	$V_{BE(sat)}$	-	960	1050	mV	$I_C = 4\text{A}, I_B = 400\text{mA}$
Base-Emitter On Voltage	$V_{BE(on)}$	-	840	950	mV	$I_C = 4\text{A}, V_{CE} = 2\text{V}$
SMALL SIGNAL CHARACTERISTICS (Note 9)						
Transition Frequency	f_T	-	190	-	MHz	$I_C = 50\text{mA}, V_{CE} = 10\text{V}, f = 100\text{MHz}$
Collector Output Capacitance	C_{obo}	-	11.7	20	pF	$V_{CB} = 10\text{V}, f = 1\text{MHz}$
Delay time	t_d	-	64	-	ns	$V_{CC} = 10\text{V}, I_C = 1\text{A}, I_{B1} = I_{B2} = 10\text{mA}$
Rise time	t_r	-	108	-	ns	
Storage time	t_s	-	428	-	ns	
Fall time	t_f	-	130	-	ns	

Notes: 9. Measured under pulsed conditions. Pulse width $\leq 300\mu\text{s}$. Duty cycle $\leq 2\%$

Typical Electrical Characteristics




Package Outline Dimensions



Dim.	Millimeters		Inches		Dim.	Millimeters		Inches	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	-	1.12	-	0.044	e1	1.90 NOM		0.075 NOM	
A1	0.01	0.10	0.0004	0.004	E	2.10	2.64	0.083	0.104
b	0.30	0.50	0.012	0.020	E1	1.20	1.40	0.047	0.055
c	0.085	0.20	0.003	0.008	L	0.25	0.60	0.0098	0.0236
D	2.80	3.04	0.110	0.120	L1	0.45	0.62	0.018	0.024
e	0.95 NOM		0.037 NOM		-	-	-	-	-

Note: Controlling dimensions are in millimeters. Approximate dimensions are provided in inches

Suggested Pad Layout



IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2012, Diodes Incorporated

www.diodes.com

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru