



## Main

|                                    |   |
|------------------------------------|---|
| Range of product                   | Altivar Process ATV900  |
| Product or component type          | Variable speed drive  |
| Device application                 | Industrial application  |
| Device short name                  | ATV930  |
| Variant                            | Standard version<br>With braking chopper  |
| Product destination                | Asynchronous motors<br>Synchronous motors   |
| Mounting mode                      | Wall mount  |
| EMC filter                         | Integrated conforming to EN/IEC 61800-3 category C3 with $\leq 50$ m motor cable maxi   |
| IP degree of protection            | IP00 conforming to IEC 60529<br>IP00 conforming to IEC 61800-5-1<br>IP21 conforming to IEC 60529 with kit VW3A9112<br>IP21 conforming to IEC 61800-5-1 with kit VW3A9112  |
| Type of cooling                    | Forced convection   |
| Supply frequency                   | 50...60 Hz (+/- 5 %)  |
| Network number of phases           | 3 phases  |
| [Us] rated supply voltage          | 380...480 V (- 15...10 %)   |
| Motor power kW                     | 160 kW (heavy duty)<br>220 kW (normal duty)   |
| Motor power hp                     | 350 hp (normal duty)<br>250 hp (heavy duty)   |
| Line current                       | 397 A at 380 V (normal duty)<br>324 A at 480 V (normal duty)<br>296 A at 380 V (heavy duty)<br>246 A at 480 V (heavy duty)  |
| Prospective line I <sub>sc</sub>   | 50 kA   |
| Apparent power                     | 247 kVA at 480 V (normal duty)<br>187 kVA at 480 V (heavy duty)   |
| Continuous output current          | 302 A at 2.5 kHz (heavy duty)<br>427 A at 2.5 kHz (normal duty)   |
| Maximum transient current          | 453 A during 60 s (heavy duty)<br>512 A during 60 s (normal duty)   |
| Asynchronous motor control profile | Constant torque standard<br>Variable torque standard<br>Optimized torque mode   |
| Synchronous motor control profile  | Permanent magnet motor<br>Synchronous reluctance motor  |
| Speed drive output frequency       | 0.1...599 Hz  |
| Nominal switching frequency        | 2.5 kHz   |
| Switching frequency                | 2.5...8 kHz with derating factor<br>1...8 kHz adjustable  |
| Safety function                    | STO (safe torque off) SIL 3   |
| Discrete input logic               | 16 preset speeds  |
| Communication port protocol        | Ethernet/IP<br>Modbus serial<br>Modbus TCP  |
| Option card                        | Slot A: communication module Profibus DP V1<br>Slot A: communication module Profinet<br>Slot A: communication module DeviceNet<br>Slot A: communication module CANopen daisy chain RJ45<br>Slot A: communication module CANopen SUB-D 9 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Slot A: communication module CANopen screw terminals  
 Slot A: communication module EtherCAT  
 Slot A/slot B/slot C: digital and analog I/O extension module  
 Slot A/slot B/slot C: output relay extension module  
 Slot B: 5/12 V digital encoder interface module  
 Slot B: analog encoder interface module  
 Slot B: resolver encoder interface module  
 Communication module for Ethernet Powerlink

## Complementary

|                                     |  |
|-------------------------------------|--|
| Output voltage                      | <= power supply voltage  |
| Motor slip compensation             | Adjustable<br>Automatic whatever the load<br>Can be suppressed<br>Not available in permanent magnet motor law  |
| Acceleration and deceleration ramps | Linear adjustable separately from 0.01...9999 s  |
| Braking to standstill               | By DC injection  |
| Protection type                     | Motor: thermal protection<br>Motor: safe torque off<br>Motor: motor phase break<br>Drive: thermal protection<br>Drive: safe torque off<br>Drive: overheating<br>Drive: overcurrent between output phases and earth<br>Drive: overload of output voltage<br>Drive: short-circuit protection<br>Drive: motor phase break<br>Drive: overvoltages on the DC bus<br>Drive: line supply overvoltage<br>Drive: line supply undervoltage<br>Drive: line supply phase loss<br>Drive: overspeed<br>Drive: break on the control circuit |
| Frequency resolution                | Display unit: 0.1 Hz<br>Analog input: 0.012/50 Hz  |
| Electrical connection               | Control, screw terminal: 0.5...1.5 mm <sup>2</sup> (AWG 20...AWG 16)<br>Motor, screw terminal : 2 x 150 mm <sup>2</sup> (2 x 350 kcmil)<br>Line side, screw terminal : 2 x 150 mm <sup>2</sup> (2 x 350 kcmil)<br>DC bus, screw terminal : 2 x 150 mm <sup>2</sup> (2 x 350 kcmil)   |
| Connector type                      | 2 RJ45 (on the control block) Ethernet IP/Modbus TCP<br>1 RJ45 (on the control block) Modbus serial  |
| Physical interface                  | 2-wire RS 485 Modbus serial  |
| Transmission frame                  | RTU Modbus serial  |
| Transmission rate                   | 10/100 Mbit/s Ethernet IP/Modbus TCP<br>4.8, 9.6, 19.2, 38.4 kbit/s for Modbus serial  |
| Exchange mode                       | Half duplex, full duplex, autonegotiation Ethernet IP/Modbus TCP   |
| Data format                         | 8 bits, configurable odd, even or no parity Modbus serial  |
| Type of polarization                | No impedance Modbus serial   |
| Number of addresses                 | 1...247 Modbus serial  |
| Method of access                    | Slave Modbus TCP   |
| Supply                              | External supply for digital inputs: 24 V DC (19...30 V) current <= 1.25 mA (overload and short-circuit protection)<br>Internal supply for reference potentiometer (1 to 10 kOhm): 10.5 V DC +/- 5 % current <= 10 mA (overload and short-circuit protection)<br>Internal supply for digital inputs and STO: 24 V DC (21...27 V) current <= 200 mA (overload and short-circuit protection)  |
| Local signalling                    | 3 mono/dual colour LED for local diagnostic<br>1 red LED for presence of voltage<br>3 dual colour LED for embedded communication status<br>4 dual colour LED for communication module status   |
| Width                               | 17.32 in (440 mm)  |
| Height                              | 47.05 in (1195 mm)   |
| Depth                               | 14.96 in (380 mm)  |
| Product weight                      | 379.2 lb(US) (172 kg)  |
| Analogue input number               | 3  |
| Analogue input type                 | Software-configurable voltage AI1, AI2, AI3: 0...10 V DC impedance 30 kOhm,  |

|                           |  |
|---------------------------|--|
|                           | resolution 12 bits<br>Software-configurable current AI1, AI2, AI3 : 0...20 mA/4...20 mA impedance 250 Ohm,<br>resolution 12 bits   |
| Discrete input number     | 10   |
| Discrete input type       | Programmable DI1...DI8: 24 V DC ( $\leq 30$ V) impedance 3.5 kOhm<br>Programmable as pulse input DI7, DI8 0...30 kHz: 24 V DC ( $\leq 30$ V)<br>Safe torque off STOA, STOB: 24 V DC ( $\leq 30$ V) impedance $> 2.2$ kOhm  |
| Input compatibility       | Discrete input STOA, STOB: level 1 PLC conforming to EN/IEC 61131-2<br>Discrete input DI1...DI8: level 1 PLC conforming to EN/IEC 61131-2<br>Pulse input DI7, DI8: level 1 PLC conforming to IEC 65A-68  |
| Discrete input logic      | DI1...DI8, DI1...DI8 positive logic (source) : $< 5$ V (state 0) $> 11$ V (state 1)<br>DI1...DI8, DI1...DI8 negative logic (sink) : $> 16$ V (state 0) $< 10$ V (state 1)<br>DI7, DI8, DI7, DI8 positive logic (source) : $< 0.6$ V (state 0) $> 2.5$ V (state 1)<br>STOA, STOB, STOA, STOB positive logic (source) : $< 5$ V (state 0) $> 11$ V (state 1)   |
| Analogue output number    | 2  |
| Analogue output type      | Software-configurable voltage AQ1, AQ2, AQ1, AQ2 : 0...10 V DC impedance 470 Ohm, resolution 10 bits<br>Software-configurable current AQ1, AQ2, AQ1, AQ2 : 0...20 mA impedance 500 Ohm, resolution 10 bits   |
| Discrete output number    | 2  |
| Discrete output type      | Logic output DQ+ : 0...1 kHz ( $\leq 30$ V) DC, 100 mA<br>Programmable as pulse output DQ+ : 0...30 kHz ( $\leq 30$ V) DC, 20 mA<br>Logic output DQ- : 0...1 kHz ( $\leq 30$ V) DC, 100 mA   |
| Sampling duration         | Discrete input DI1...DI8: 2 ms (+/- 0.5 ms)<br>Pulse input DI7, DI8: 5 ms (+/- 1 ms)<br>Analog input AI1, AI2, AI3: 1 ms (+/- 1 ms)<br>Analog output AQ1, AQ2: 5 ms (+/- 1 ms)   |
| Accuracy                  | Analog input AI1, AI2, AI3: +/- 0.6 % for a temperature variation 60 °C<br>Analog output AQ1, AQ2: +/- 1 % for a temperature variation 60 °C   |
| Linearity error           | Analog input AI1, AI2, AI3: +/- 0.15 % of maximum value<br>Analog output AQ1, AQ2: +/- 0.2 %   |
| Maximum switching current | Relay output R1 on inductive load ( $\cos \phi = 0.4$ and $L/R = 7$ ms) : 2 A at 250 V AC<br>Relay output R1 on inductive load ( $\cos \phi = 0.4$ and $L/R = 7$ ms) : 2 A at 30 V DC<br>Relay output R2, R3 on inductive load ( $\cos \phi = 0.4$ and $L/R = 7$ ms) : 2 A at 250 V AC<br>Relay output R2, R3 on inductive load ( $\cos \phi = 0.4$ and $L/R = 7$ ms) : 2 A at 30 V DC<br>Relay output R1 on resistive load ( $\cos \phi = 1$ ) : 3 A at 250 V AC<br>Relay output R1 on resistive load ( $\cos \phi = 1$ ) : 3 A at 30 V DC<br>Relay output R2, R3 on resistive load ( $\cos \phi = 1$ ) : 5 A at 250 V AC<br>Relay output R2, R3 on resistive load ( $\cos \phi = 1$ ) : 5 A at 30 V DC |
| Relay output number       | 3  |
| Relay output type         | Configurable relay logic R1: fault relay NO/NC electrical durability 100000 cycles<br>Configurable relay logic R2: sequence relay NO electrical durability 1000000 cycles<br>Configurable relay logic R3: sequence relay NO electrical durability 1000000 cycles   |
| Refresh time              | Relay output R1, R2, R3: 5 ms (+/- 0.5 ms)   |
| Minimum switching current | Relay output R1, R2, R3: 5 mA at 24 V DC   |
| Isolation                 | Between power and control terminals  |
| IP degree of protection   | IP00   |

## Environment

|                               |  |
|-------------------------------|--|
| insulation resistance         | $> 1$ mOhm at 500 V DC for 1 minute to earth   |
| noise level                   | 73 dB conforming to 86/188/EEC   |
| power dissipation in W        | 451 W (natural convection) at 380 V switching frequency 2.5 kHz<br>5030 W (forced convection) at 380 V switching frequency 2.5 kHz   |
| vibration resistance          | 1 gn ( $f = 13...200$ Hz) conforming to IEC 60068-2-6<br>1.5 mm peak to peak ( $f = 2...13$ Hz) conforming to IEC 60068-2-6  |
| shock resistance              | 15 gn during 11 ms conforming to IEC 60068-2-27  |
| volume of cooling air         | 227192.03 Gal/hr(US) (860 m <sup>3</sup> /h)   |
| operating position            | Vertical +/- 10 degree   |
| THDI                          | $\leq 48$ % full load conforming to IEC 61000-3-12   |
| electromagnetic compatibility | 1.2/50 $\mu$ s - 8/20 $\mu$ s surge immunity test level 3 conforming to IEC 61000-4-5<br>Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4<br>Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2<br>Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3<br>Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6 |

|                                       |  |
|---------------------------------------|--|
| pollution degree                      | 2 EN/IEC 61800-5-1   |
| environmental characteristic          | Dust pollution resistance class 3S2 conforming to EN/IEC 60721-3-3<br>Chemical pollution resistance class 3C2 conforming to EN/IEC 60721-3-3   |
| relative humidity                     | 5...95 % without condensation conforming to IEC 60068-2-3  |
| ambient air temperature for operation | 14...104 °F (-10...40 °C) without derating<br>40...60 °C with derating factor  |
| ambient air temperature for storage   | -13...158 °F (-25...70 °C)   |
| operating altitude                    | <= 3280.84 ft (1000 m) without derating<br>3280.84...9842.52 ft (1000...3000 m) with current derating 1 % per 100 m  |
| standards                             | EN/IEC 61800-3<br>UL 508C<br>EN/IEC 61800-5-1<br>IEC 61000-3-12<br>IEC 60721-3<br>IEC 61508<br>IEC 13849-1<br>EN/IEC 61800-3 (environment 1 category C2)<br>EN/IEC 61800-3 (environment 2 category C3) |
| product certifications                | CSA<br>TÜV<br>UL<br>REACH  |
| marking                               | CE   |

## Offer Sustainability

|  |  |
|--|--|
| Green Premium product  | Green Premium product  |
| Compliant - since 1714 - Schneider Electric declaration of conformity  | Compliant - since 1714 - Schneider Electric declaration of conformity  |
| Reference not containing SVHC above the threshold  | Reference not containing SVHC above the threshold  |
| Available  | Available  |
| Available  | Available  |
| WARNING: This product can expose you to chemicals including:   | WARNING: This product can expose you to chemicals including:   |
| Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. |
| For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    | For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>                                    |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)