ComPAC™
DC-DC Switchers

50 to 600 Watts; 1 to 3 outputs

Features

- RoHS Compliant (VE versions)
- Inputs 24, 48, and 300 Vdc
- Any output: 1 to 95 Vdc
- Meets EN55022 Class A conducted emissions (See Notes)
- cULus, cTÜVus (60950-1)
- CE marked (LVD)
- 80 – 90% efficiency
- Up to 10 W/cubic inch
- Master disable
- Overvoltage shutdown

Product Highlights

ComPAC delivers up to 600 W from one, two, or three outputs in a package just 0.99″ (25,2 mm) in height with the field proven performance, high efficiency and high reliability inherent in Vicor's component level power converters. ComPAC meets conducted emissions of EN55022 Class A. ComPAC is offered with input voltage ranges optimized for industrial and telecommunication applications and provides extended input overvoltage capability, undervoltage lockout, and master disable.

Packaging Options

Conduction Cooled Models Available Add "-CC" to the end of the part number. *(Consult factory for details.)*
Extended heat sink available add "–H1" to end of part number.

ComPAC Configuration Chart

Substitute VE– for VI– for RoHS compliant versions

Configuration	Output Power	# of Modules	Dimensions
Single Output			
VI-LC	50 – 200 W	1	8.6" x 2.5" x 0.99" (218,4 x 63,5 x 25,2 mm)
VI-MC	100 – 400 W	2	8.6" x 4.9" x 0.99" (218,4 x 124,5 x 25,2 mm)
VI-NC	300 – 600 W	3	8.6" x 7.3" x 0.99" (218,4 x 185,4 x 25,2 mm)
Dual Output			
VI-PC	100 – 400 W	2	8.6" x 4.9" x 0.99" (218,4 x 124,5 x 25,2 mm)
VI-QC	150 – 600 W	3	8.6" x 7.3" x 0.99" (218,4 x 185,4 x 25,2 mm)
Triple Output			
VI-RC	150 – 600 W	3	8.6" x 7.3" x 0.99" (218,4 x 185,4 x 25,2 mm)

Input Voltage

Nominal	Input Range Full Power	Maximum Power [a]	Low Line 75% Max. Power	Transient [b]
1 = 24 V	21 – 32 V	(1)	18	36
W = 24 V	18 – 36 V	(1)	n/a	n/a
3 = 48 V	42 – 60 V	(2)	41	72
N = 48 V	36 – 76 V	(2)	n/a	n/a
6 = 300 V	200 – 400 V	(2)	188	425

[a]

Max. Output Per Module	5 V Outputs	>5 V Outputs	<5 V Outputs
(1)	150 W	150 W	30 A
(2)	200 W	200 W	40 A

[b] Transient voltage for one second

Output Voltage

Z = 2 V	**2** = 15 V
Y = 3.3 V	**N** = 18.5 V
0 = 5 V	**3** = 24 V
X = 5.2 V	**L** = 28 V
W = 5.5 V	**J** = 36 V
V = 5.8 V	**K** = 40 V
T = 6.5 V	**4** = 48 V
R = 7.5 V	**H** = 52 V
M = 10 V	**F** = 72 V
1 = 12 V	**D** = 85 V
P = 13.8 V	**B** = 95 V

Product Grade Temps. °C

Grade	Operating	Storage
E =	–10 to +85	–20 to +100
C =	–25 to +85	–40 to +100
I =	–40 to +85	–55 to +100
M =	–55 to +85	–65 to +100

Temperatures apply to product case.

Output Power/Current

$V_{OUT} \geq 5$ V	$V_{OUT} < 5$ V
Y = 50 W	**Y** = 10 A
X = 75 W	**X** = 15 A
W = 100 W	**W** = 20 A
V = 150 W	**V** = 30 A
U = 200 W	**U** = 40 A

Output Power/Current

$V_{OUT} \geq 5$ V	$V_{OUT} < 5$ V
W = 100 W	**W** = 20 A
V = 150 W	**V** = 30 A
U = 200 W	**U** = 40 A
S = 300 W	**S** = 60 A
Q = 400 W	**Q** = 80 A

Output Power/Current

$V_{OUT} \geq 5$ V	$V_{OUT} < 5$ V
S = 300 W	**S** = 60 A
P = 450 W	**P** = 90 A
M = 600 W	**M** = 120 A

COMPAC SPECIFICATIONS

(typical at T_{BP} = 25°C, nominal line and 75% load, unless otherwise specified, VNOM is factory set output voltage and INOM is maximum rated output current.)

■ INPUT SPECIFICATIONS

	E-Grade			C-, I-, M-Grade				
Parameter	**Min**	**Typ**	**Max**	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
24 V	21	24	32	21	24	32	Vdc	See Fusing Information on Page 3
24 V Wide	18	24	36	18	24	36	Vdc	
48 V	42	48	60	42	48	60	Vdc	
48 V Wide	36	48	76	36	48	76	Vdc	
300 V	200	300	400	200	300	400	Vdc	
No load power dissipation [a]	1.35		2	1.35		2	Watts	
Master disable input current [a] (Absolute max., 20 mA)	4			4			mA	Sink or source to disable optocoupler (See Section 18 ComPAC Technical Description in VI-200/VI-J00 Applications Manual)
Quiescent Input current logic disable [a]		7	10		7	10	mA	Current drawn from source when disabled

[a] For MC, PC series, multiply value by 2; for NC, QC, RC series, multiply value by 3.

■ OUTPUT SPECIFICATIONS (Applies to each output individually)

	E-Grade			C-, I-, M-Grade				
Parameter	**Min**	**Typ**	**Max**	**Min**	**Typ**	**Max**	**Units**	**Test Conditions**
Set point accuracy		1%	2%		0.5%	1%	VNOM	
Load / line regulation			0.5%		0.05%	0.2%	VNOM	LL to HL, 10% to full load
Load / line regulation			1%		0.2%	0.5%	VNOM	LL to HL, no load to full load
Output temperature drift		0.02			0.01	0.02	%/°C	Over rated temperature range
Long term drift		0.02			0.02		%/1 k hrs.	
Output ripple								
2 V, 3.3 V			150		60	100	mVp-p	20 MHz bandwidth
5 V			250		100	150	mVp-p	20 MHz bandwidth
10 – 48 V			3%		0.75%	1.5%	VNOMp-p	20 MHz bandwidth
Output voltage trimming [a]	50%		110%	50%		110%	VNOM	
Total remote sense compensation [a]	0.5			0.5			Volts	0.25 V maximum allowable drop in –Out lead
OVP set point		125%		115%	125%	135%	VNOM	Recycle power to restart
Current limit	105%		135%	105%		125%	INOM	Automatic restart
Short circuit current [b]	20%		140%	20%		130%	INOM	

[a] 10 V, 12 V and 15 V outputs, trim range ± 10%. Consult factory for wider trim range.
[b] Output voltages of 5 V or less incorporate foldback current limiting, outputs greater than 5 V incorporate straight line current limiting.

CONFIGURABLE SPECIFICATIONS (Cont.)

■ THERMAL CHARACTERISTICS

	E-Grade			C-, I-, M-Grade				
Parameter	**Min**	**Typ**	**Max**	**Min**	**Typ**	**Max**	**Units**	**Test Conditions**
Efficiency		78 – 88%			80 – 90%			for 5 V outputs and higher
Shut down temp. — case [a]	90	95	105	90	95	105	°C	Cool and recycle power to restart
Operating temp. — case			85			85	°C	See Thermal Curves

[a] Shut down temperature threshold is above maximum operating temperature. For over temperature protection, external means of disable should be employed below maximum operating temperature.

■ ISOLATION CHARACTERISTICS

	E-Grade			C-, I-, M-Grade				
Parameter	**Min**	**Typ**	**Max**	**Min**	**Typ**	**Max**	**Unit**	**Test Conditions**
Isolation								
Input to output	4,242			4,242			Vdc	
Output to case	707			707			Vdc	
Input to case	2,121			2,121			Vdc	

■ MECHANICAL SPECIFICATIONS

	E-Grade			C-, I-, M-Grade				
Parameter	**Min**	**Typ**	**Max**	**Min**	**Typ**	**Max**	**Units**	**Test Conditions**
Weight [a]	19.2			19.2			Ounces	
	544			544			Grams	

[a] For MC, PC series, multiply value by 2; for NC, QC, RC series, multiply value by 3.

■ FUSING INFORMATION

Input Voltage	**24 V**	**48 V**	**300 V**
LC series (200 W)	10 A	7 A	2 A
MC, PC series (400 W)	20 A	15 A	4 A
NC, QC, RC series (600 W)	35 A	25 A	6 A

CONFIGURABLE SPECIFICATIONS (Cont.)

■ AGENCY APPROVALS

Safety Standards	Markings	Notes
ANSI / ISA 12.12.01 - 2012, C22.2 No. 213-M1987	cURus	
UL / CSA / EN / IEC 60950-1	cURus, cTÜVus,CE Marked	Low Voltage Directive and RoHS Recast Directive as applicable.

■ EMI / EMC Characteristics (Performed on selected samples representative of the ComPac product family.)

Parameter	Notes
Conducted Emissions EN 55022, class A	3 Module configurations may require additional filter components under certain line and load conditions to comply with EN55022 class A.
ESD IEC 61000-4-2 level 4	Top, Bottom and Sides

THERMAL CURVES

FREE AIR — 50 LFM — 100 LFM — 250 LFM — 500 LFM — 750 LFM — 1000 LFM

2 V to 7.5 V Output, Standard heat sink



LC Series



MC, PC Series



NC, QC, RC Series

10 V to 95 V Output, Standard heat sink



LC Series



MC, PC Series



NC, QC, RC Series

2 V to 7.5 V Output , H1 heat sink



LC Series



MC, PC Series



NC, QC, RC Series

10 V to 95 V Output, H1 heat sink



LC Series



MC, PC Series



NC, QC, RC Series

MECHANICAL DRAWINGS

ALL MODELS

INPUTS	
1	Ground
2	-Input
3	+Input
4	Disable-
5	Disable+
OUTPUTS	
A	+Output
B	+Sense
C	Trim
D	-Sense
E	-Output



LC SERIES



MC, PC SERIES



NC, QC, RC Series



LONG TERM SAFE OPERATING AREA CURVES

(1% duty cycle max., Z_s = .5 , for short duration transient capability refer to specifications)



I.S.W.: Input surge withstand, no degradation of performance. **R.E.:** Ratings Exceeded **S.D.:** Shutdown

Vicor's comprehensive line of power solutions includes high density AC-DC and DC-DC modules and accessory components, fully configurable AC-DC and DC-DC power supplies, and complete custom power systems.

Information furnished by Vicor is believed to be accurate and reliable. However, no responsibility is assumed by Vicor for its use. Vicor makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication. Vicor reserves the right to make changes to any products, specifications, and product descriptions at any time without notice. Information published by Vicor has been checked and is believed to be accurate at the time it was printed; however, Vicor assumes no responsibility for inaccuracies. Testing and other quality controls are used to the extent Vicor deems necessary to support Vicor's product warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.
Specifications are subject to change without notice.

Vicor's Standard Terms and Conditions

All sales are subject to Vicor's Standard Terms and Conditions of Sale, which are available on Vicor's webpage or upon request.

Product Warranty

In Vicor's standard terms and conditions of sale, Vicor warrants that its products are free from non-conformity to its Standard Specifications (the "Express Limited Warranty"). This warranty is extended only to the original Buyer for the period expiring two (2) years after the date of shipment and is not transferable.
UNLESS OTHERWISE EXPRESSLY STATED IN A WRITTEN SALES AGREEMENT SIGNED BY A DULY AUTHORIZED VICOR SIGNATORY, VICOR DISCLAIMS ALL REPRESENTATIONS, LIABILITIES, AND WARRANTIES OF ANY KIND (WHETHER ARISING BY IMPLICATION OR BY OPERATION OF LAW) WITH RESPECT TO THE PRODUCTS, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OR REPRESENTATIONS AS TO MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, INFRINGEMENT OF ANY PATENT, COPYRIGHT, OR OTHER INTELLECTUAL PROPERTY RIGHT, OR ANY OTHER MATTER.

This warranty does not extend to products subjected to misuse, accident, or improper application, maintenance, or storage. Vicor shall not be liable for collateral or consequential damage. Vicor disclaims any and all liability arising out of the application or use of any product or circuit and assumes no liability for applications assistance or buyer product design. Buyers are responsible for their products and applications using Vicor products and components. Prior to using or distributing any products that include Vicor components, buyers should provide adequate design, testing and operating safeguards.

Vicor will repair or replace defective products in accordance with its own best judgment. For service under this warranty, the buyer must contact Vicor to obtain a Return Material Authorization (RMA) number and shipping instructions. Products returned without prior authorization will be returned to the buyer. The buyer will pay all charges incurred in returning the product to the factory. Vicor will pay all reshipment charges if the product was defective within the terms of this warranty.

Life Support Policy

VICOR'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS PRIOR WRITTEN APPROVAL OF THE CHIEF EXECUTIVE OFFICER AND GENERAL COUNSEL OF VICOR CORPORATION. As used herein, life support devices or systems are devices which (a) are intended for surgical implant into the body, or (b) support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in a significant injury to the user. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system or to affect its safety or effectiveness. Per Vicor Terms and Conditions of Sale, the user of Vicor products and components in life support applications assumes all risks of such use and indemnifies Vicor against all liability and damages.

Intellectual Property Notice

Vicor and its subsidiaries own Intellectual Property (including issued U.S. and Foreign Patents and pending patent applications) relating to the products described in this data sheet. No license, whether express, implied, or arising by estoppel or otherwise, to any intellectual property rights is granted by this document. Interested parties should contact Vicor's Intellectual Property Department.

Vicor Corporation
25 Frontage Road
Andover, MA, USA 01810
Tel: 800-735-6200
Fax: 978-475-6715

email
Customer Service: custserv@vicorpower.com
Technical Support: apps@vicorpower.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Vicor:
VI-NC13-IP

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru